

REVEAL

Description

Display the field attributes of the emulation and the value of the ASCII character at the current cursor position.

This command can only be used during terminal emulation. The following information is shown in the status line of the terminal emulation screen, starting at column 38:

```
aaa/bbb fields ccccc dd
```

aaa is the number of input fields on the screen.

bbb is the number of unprotected input fields on the screen.

cccc indicates that the cursor is positioned on one of the following fields:

FM	field mark (attribute)
PROT	protected field
NUM	unprotected numeric field
ALPHA	unprotected alphanumeric field
NON-DISP	non-display field

dd is the ASCII value of the character (in hexadecimal notation) at the current cursor position.

Example:

```
043/001 fields PROT 6e
```

If the REVEAL command is in effect, data transfer is disabled. Data transfer buffers are shown on the screen. The information is shown until you issue the REVEAL command again. Using a key combination, you can switch this mode on and off.

The default key combination depends on the type of session and the corresponding default key scheme.

Type of Session / Default Key Scheme	Default Key Combination
TN3270 / SAGKEYS1	CTRL+R
BS2000 / BS2000KEYS	ALT+R
VTxxx / VT220PC	ALT+R

Syntax

```
REVEAL
```

Procedure File Example

Revattr.ncp

Variables Returned

None

Usage

Procedure File: Yes

Command Line: No

Key: Yes

API: Yes