

Entire Output Management

Installation and Customization

Version 3.5.3

October 2025

This document applies to Entire Output Management Version 3.5.3 and all subsequent releases.

Specifications contained herein are subject to change and these changes will be reported in subsequent release notes or new editions.

Copyright © 1990-2025 Software GmbH, Darmstadt, Germany and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software GmbH product names are either trademarks or registered trademarks of Software GmbH and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software GmbH and/or its subsidiaries is located at <https://softwareag.com/licenses>.

Use of this software is subject to adherence to Software GmbH's licensing conditions and terms. These terms are part of the product documentation, located at <https://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third-Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software GmbH Products / Copyright and Trademark Notices of Software GmbH Products". These documents are part of the product documentation, located at <https://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

Use, reproduction, transfer, publication or disclosure is prohibited except as specifically provided for in your License Agreement with Software GmbH.

Document ID: NOM-ONOMINSTALL-353-20251001

Table of Contents

| | |
|---|----|
| Installation and Customization | v |
| 1 About this Documentation | 1 |
| Document Conventions | 2 |
| Online Information and Support | 2 |
| Data Protection | 3 |
| 2 Installation and Customization on Mainframes | 5 |
| 3 Before the Installation | 7 |
| Installation Jobs | 8 |
| Using System Maintenance Aid | 8 |
| Prerequisites | 8 |
| Contents of Installation Medium | 8 |
| Copying the Data Sets to Disk | 9 |
| 4 Installing Entire Output Management | 13 |
| Step 1: Prepare, Convert, Assemble and Link the License File | 14 |
| Step 2: Load the Data File - for First-Time Installation Only | 14 |
| Step 3: Load the Container File | 14 |
| Step 4: Activate Index Compression (optional) | 15 |
| Step 5: Scratch NOM Libraries - for Update Installation Only | 15 |
| Step 6: Adapt Parameter Modules and Link Jobs for Batch and Online Natural | 15 |
| Step 7: Load the INPL File | 18 |
| 5 Completing the Installation | 19 |
| Adapting to an Existing Environment | 20 |
| Natural Profile Parameters | 21 |
| Natural Security Definitions | 22 |
| Entire Output Management in a Non-Security Environment | 23 |
| Define Environment for Entire Output Management Server | 23 |
| Migrating from Previous Versions | 26 |
| Starting Entire Output Management for the First Time | 28 |
| Installation Verification | 29 |
| 6 Installing Optional Features | 33 |
| Printing from Natural to Entire Output Management Directly | 34 |
| Natural Advanced Facilities | 35 |
| Report Format Conversion - Additional Requirements | 36 |
| 3GL Interface Installation and Verification | 37 |
| Re-Routing VTAM Output to Entire Output Management | 42 |

Installation and Customization

Installation and Customization on Mainframes

How to install Entire Output Management on a mainframe operating system.

Notations *vrs* and *vr*

When used in this documentation, the notations *vrs* and *vr* represent the product version number.

1

About this Documentation

| | |
|--|---|
| ■ Document Conventions | 2 |
| ■ Online Information and Support | 2 |
| ■ Data Protection | 3 |

Document Conventions

| Convention | Description |
|----------------|--|
| Bold | Identifies elements on a screen. |
| Monospace font | Identifies service names and locations in the format <i>folder.subfolder.service</i> , APIs, Java classes, methods, properties. |
| <i>Italic</i> | Identifies: Variables for which you must supply values specific to your own situation or environment. New terms the first time they occur in the text. References to other documentation sources. |
| Monospace font | Identifies: Text you must type in. Messages displayed by the system. Program code. |
| { } | Indicates a set of choices from which you must choose one. Type only the information inside the curly braces. Do not type the { } symbols. |
| | Separates two mutually exclusive choices in a syntax line. Type one of these choices. Do not type the symbol. |
| [] | Indicates one or more options. Type only the information inside the square brackets. Do not type the [] symbols. |
| ... | Indicates that you can type multiple options of the same type. Type only the information. Do not type the ellipsis (...). |

Online Information and Support

Product Documentation

You can find the product documentation on our documentation website at <https://documentation.softwareag.com>.

Product Training

You can find helpful product training material on our Learning Portal at <https://learn.software-ag.com>.

Tech Community

You can collaborate with Software GmbH experts on our Tech Community website at <https://tech-community.softwareag.com>. From here you can, for example:

- Browse through our vast knowledge base.
- Ask questions and find answers in our discussion forums.
- Get the latest Software GmbH news and announcements.
- Explore our communities.
- Go to our public GitHub and Docker repositories at <https://github.com/softwareag> and <https://hub.docker.com/publishers/softwareag> and discover additional Software GmbH resources.

Product Support

Support for Software GmbH products is provided to licensed customers via our Empower Portal at <https://empower.softwareag.com>. Many services on this portal require that you have an account. If you do not yet have one, you can request it at <https://empower.softwareag.com/register>. Once you have an account, you can, for example:

- Download products, updates and fixes.
- Search the Knowledge Center for technical information and tips.
- Subscribe to early warnings and critical alerts.
- Open and update support incidents.
- Add product feature requests.

Data Protection

Software AG products provide functionality with respect to processing of personal data according to the EU General Data Protection Regulation (GDPR). Where applicable, appropriate steps are documented in the respective administration documentation.

2 Installation and Customization on Mainframes

This documentation describes how to install Entire Output Management on a mainframe operating system.

This documentation is organized under the following headings:

| | |
|--|--|
| Before the Installation | Information you need to know and steps to perform before you start the installation. |
| Installing Entire Output Management | How to install Entire Output Management. |
| Completing the Installation | How to proceed after the installation. |
| Installing Optional Features | How to install various optional features. |

Notations *vrs* and *vr*

When used in this documentation, the notations *vrs* and *vr* represent the product version number.

3

Before the Installation

| | |
|---|---|
| ■ Installation Jobs | 8 |
| ■ Using System Maintenance Aid | 8 |
| ■ Prerequisites | 8 |
| ■ Contents of Installation Medium | 8 |
| ■ Copying the Data Sets to Disk | 9 |

This section covers the following topics:

Installation Jobs

The installation of Software GmbH products is performed by installation jobs. These jobs are either created manually or generated by System Maintenance Aid (SMA).

For each step of the installation procedure described below, the job number of a job performing the respective task is indicated. This job number refers to an installation job generated by SMA. If you are not using SMA, an example installation job of the same number is provided in the job library on the Entire Output Management installation medium; you have to adapt this example job to your requirements.



Note: The job numbers on the installation medium are preceded by the product code (for example, NOMI060).

Using System Maintenance Aid

For information on using Software GmbH's System Maintenance Aid (SMA) for the installation process, refer to the *System Maintenance Aid* documentation.

Prerequisites

Before you can install Entire Output Management, certain prerequisite products must be installed at your site. For detailed information on these products, see the *Prerequisites* sections in the *Release Notes*.

Contents of Installation Medium

The installation medium contains the files listed below.

The sequence of the files is shown in the *Software GmbH product Delivery Report* which accompanies the installation medium.

Notation vrs or vr: If used in the following document, the notation *vrs* or *vr* stands for the relevant version. For further information on product versions, refer to the entry *Version* in the *Glossary* of the Natural documentation.

z/OS

| File Name | Contents |
|-------------|---|
| NOMvrs.JOBS | Entire Output Management installation jobs. |
| NOMvrs.SRCE | Entire Output Management source library. |
| NOMvrs.LOAD | Entire Output Management load library. |
| NOMvrs.INPL | Entire Output Management system libraries (Natural). |
| NOMvrs.SYSF | Entire Output Management definition-data/active-data file (Adabas). |
| NOMvrs.SYS2 | Entire Output Management container file (Adabas). |

Copying the Data Sets to Disk

- [Copying the Data Sets to a z/OS Disk](#)

Copying the Data Sets to a z/OS Disk

Copy the data sets from the supplied installation medium to your disk before you perform the individual installation procedure for each component to be installed.

The way you copy the data sets depends on the installation method and the medium used:

- If you use System Maintenance Aid (SMA), refer to the copy job instructions provided in the *System Maintenance Aid* documentation.
- If you are not using SMA and want to copy the data sets from CD-ROM, refer to the README.TXT file on the CD-ROM.
- If you are not using SMA and want to copy the data sets from tape, follow the instructions in this section.

This section explains how to copy all data sets from tape to disk.

- [Step 1: Copy Data Set COPY.JOB from Tape to Disk](#)
- [Step 2: Modify hilev.COPY.JOB on Your Disk](#)

- [Step 3: Submit COPY.JOB](#)

Step 1: Copy Data Set COPY.JOB from Tape to Disk

- Modify the following sample job according to your requirements:

```
//SAGTAPE JOB SAG,CLASS=1,MSGCLASS=X
//* -----
//COPY EXEC PGM=IEBGENER
//SYSUT1 DD DSN=COPY.JOB,
// DISP=(OLD,PASS),
// UNIT=(CASS,,DEFER),
// VOL=(,RETAIN,SER=tape-volser),
// LABEL=(2,SL)
//SYSUT2 DD DSN=hilev.COPY.JOB,
// DISP=(NEW,CATLG,DELETE),
// UNIT=3390,VOL=SER=disk-volser,
// SPACE=(TRK,(1,1),RLSE),
// DCB=*.SYSUT1
//SYSPRINT DD SYSOUT=*
//SYSIN DD DUMMY
//
```

where:

tape-volser is the VOLSER of the tape, for example: T12345,
hilev is a valid high-level qualifier, and
disk-volser is the VOLSER of the disk.

- Execute the job to copy the data set COPY.JOB to your disk.

Step 2: Modify hilev.COPY.JOB on Your Disk

- Modify *hilev*.COPY.JOB according to your requirements:

Set EXPDT to a valid expiration date, for example, 99365.

Set HILEV to a valid high-level qualifier, for example, USERLIB.

Set LOCATION to a storage location, for example, STORCLAS=ABC or UNIT=3390,VOL=SER=USR123.

Step 3: Submit COPY.JOB

- Execute `hilev.COPY.JOB` to copy single, multiple, or all data sets to your disk.

4

Installing Entire Output Management

| | |
|--|----|
| ■ Step 1: Prepare, Convert, Assemble and Link the License File | 14 |
| ■ Step 2: Load the Data File - for First-Time Installation Only | 14 |
| ■ Step 3: Load the Container File | 14 |
| ■ Step 4: Activate Index Compression (optional) | 15 |
| ■ Step 5: Scratch NOM Libraries - for Update Installation Only | 15 |
| ■ Step 6: Adapt Parameter Modules and Link Jobs for Batch and Online Natural | 15 |
| ■ Step 7: Load the INPL File | 18 |

To install Entire Output Management on z/OS, perform the following steps:

Step 1: Prepare, Convert, Assemble and Link the License File

(Job I007, Steps 2801, 2802, 2804)

You have to install a valid Entire Output Management license file. For detailed information on license files and product licensing, see the *Mainframe Product Licensing* documentation.

1. Copy the license file from the installation medium to disk, or transfer it from the PC as described under *Transferring a Licence File from PC to z/OS Host Using FTP* in the *Mainframe Product Licensing* documentation.
2. Step 2801 - Check the license file (here named) `NOMLIC`. This job executes the CHECK function of the LICUTIL license utility.
3. Step 2802 - Convert the license file into an assembler source. This job executes the MAKE function of the LICUTIL license utility.
4. Step 2804 - Assemble and link the assembler source to generate load module `NOMLIC`. This module is then linked to the nucleus in Job I060 (see below).

The functions and option settings provided by LICUTIL are described under *Using the License Utility LICUTIL* in the *Mainframe Product Licensing* documentation.

Step 2: Load the Data File - for First-Time Installation Only

(Job I050, Step 2800)

If you are installing Entire Output Management for the first time, use the Adabas load utility to load the `NOMvrs.SYSF` file. The data file contains some examples and initializations.

Step 3: Load the Container File

(Job I050, Step 2801)

When working with container files, load one or more files using `NOMvrs.SYS2` with `NUMREC=0`. For more information on how to use container files, see *Defining Container Files* in the *System Administration* documentation.

Step 4: Activate Index Compression (optional)

In large environments, it may be useful to activate Adabas index compression for the Entire Output Management system files. This will result in less space required in the Adabas ASSO container, as Entire Output Management uses several similar descriptors which can be compressed very efficiently.

If you decide to perform this step, it is recommended to do so now during the installation. However, it is also possible to perform it later if desired.

To activate Adabas index compression, invoke the Adabas reorder utility as follows:

```
ADAORD REORFASSO FILE=NOM-system-file-number INDEXCOMPRESSION=YES
```

Step 5: Scratch NOM Libraries - for Update Installation Only

(Job I051, Step 2800)

If Entire Output Management has been installed before, scratch all objects from the libraries `SYSNOM`, `SYSNOMS`, `SYSNOMH1` and `SYSNOMH2`.

Step 6: Adapt Parameter Modules and Link Jobs for Batch and Online Natural

Monitors of the System Automation Tools product family run as a Natural subtask. For further information, see the section *Monitor Defaults* in the *System Administration* documentation, and the sections *Installing System Automation Tools* and *Starting a Server* in the *System Automation Tools* documentation.

For 3GL programs, `NOMPUT`, `NOMADA` and `NOMCOMPR` must be linked to the 3GL program itself.

In addition to the specifications described in the *System Automation Tools Installation* documentation, you have to adapt and link the following:

1. Adapt the Batch Natural Parameter Module (Job I060)

Add or change the following parameters in your Natural parameter module:

| | |
|---|--|
| CSTATIC=(ESFCLOS,ESFOPEN,ESFPURG, ↵ ESFREAD,ESFROUT,ESFSTAT,ESFWRITE) | Optional; required only if CA Spool is installed. Note: If you wish to access TCP/IP printers directly, you also have to specify the module ESMLPR in the CSTATIC list. See the section <i>TCP/IP Direct Printing</i> in the <i>Concepts and Facilities</i> documentation. |
| NTLFILE 91,dbid,fnr | The database ID and file number of the Entire Output Management active data file. If you wish to keep all data in a single Entire Output Management data file, specify the same database ID and file number as for NTLFILE 206 (see below). |
| NTLFILE 206,dbid,fnr | The database ID and file number of the Entire Output Management data file. |
| NTLFILE 131,dbid,fnr | The database ID and file number of the System Automation Tools system file (mandatory). |
| NTSORT WRKSIZE=30,STORAGE=MAIN,EXT=OFF | Sort program specifications. Note: The Natural SORT statement may optionally invoke an external sort program. In this case, EXT=ON must be specified. For further information, see the section <i>External Sort Programs</i> in the <i>Natural Operations</i> documentation. |
| RUNSIZE=64 | Required for the correct execution of the Entire Output Management monitor. |

2. Link the Natural Batch Module (Job I060)

z/OS:

Take the link job as described in the *System Automation Tools Installation* documentation and adapt the following libraries for the linkage:

| | |
|---|---|
| //NOMLIB DD DISP=SHR,DSN=SAGLIB.NOMvrs.LOAD | Supplied Entire Output Management load library. |
| //CMALIB DD DISP=SHR,DSN=CMASPOOL.LOAD | Supplied CA Spool load library (optional). |
| INCLUDE NOMLIB(NOMCOMPR) | Compression. |
| INCLUDE NOMLIB(NOMPUT) | Install Natural Advanced Facilities printer type "NOM". |
| INCLUDE NOMLIB(NOMADA) | |
| INCLUDE NOMLIB(NATAM12) | Install Natural printer type "NOM". |
| INCLUDE CMALIB(AESFPRIV) | Optional. Only if CA Spool is installed. |

3. Adapt the Online Natural Parameter Module (Job I080)

Add or change the following parameters in your Natural parameter module:

| | |
|---|--|
| NTLFILE 91,dbid,fnr | The database ID and file number of the Entire Output Management active data file. If you wish to keep all data in a single Entire Output Management data file, specify the same database ID and file number as for NTLFILE 206 (see below). |
| NTLFILE 206,dbid,fnr | The database ID and file number of the Entire Output Management data file. |
| NTLFILE 131,dbid,fnr | The database ID and file number of the System Automation Tools system file (mandatory). |
| NTSORT WRKSIZE=30,STORAGE=MAIN,EXT=OFF | Sort program specifications. Note: The Natural SORT statement may optionally invoke an external sort program. In this case, EXT=ON must be specified. For further information, see the section <i>External Sort Programs</i> in the <i>Natural Operations</i> documentation. |

4. Link the Online Natural Parameter Module (Job I080)

Take the link job as described in the *System Automation Tools Installation* documentation and adapt the following:

z/OS:

Take the link job as described in the *System Automation Tools Installation* documentation and adapt the following libraries for the linkage:

| | |
|---|---|
| //NOMLIB DD DISP=SHR,DSN=SAGLIB.NOMvrs.LOAD | Supplied Entire Output Management load library. |
| INCLUDE NOMLIB(NOMCOMPR) | Compression. |
| INCLUDE NOMLIB(NOMPUT) | Install Natural Advanced Facilities printer type "NOM". |
| INCLUDE NOMLIB(NOMADA) | |
| INCLUDE NOMLIB(NATAM12) | Access method AM=NOM. |

Additional Steps

If you want to print from Natural to Entire Output Management directly (without a spooling system), additional steps are required; see the section [Printing from Natural to Entire Output Management Directly](#).

If you want to print from Natural Advanced Facilities to Entire Output Management directly, additional steps are required; see the section [Using NOMPUT](#).

Step 7: Load the INPL File

(Job I061, Step 2800)

Load the INPL file. The following libraries are loaded:

| Library | File | Contents |
|----------|------|---|
| SYSNOM | FNAT | Entire Output Management application. |
| SYSNOMH1 | FNAT | Entire Output Management help system (English). |
| SYSNOMH2 | FNAT | Entire Output Management help system (German). |
| SYSNOMS | FNAT | JCL skeletons and separator examples. |

5

Completing the Installation

| | |
|--|----|
| ■ Adapting to an Existing Environment | 20 |
| ■ Natural Profile Parameters | 21 |
| ■ Natural Security Definitions | 22 |
| ■ Entire Output Management in a Non-Security Environment | 23 |
| ■ Define Environment for Entire Output Management Server | 23 |
| ■ Migrating from Previous Versions | 26 |
| ■ Starting Entire Output Management for the First Time | 28 |
| ■ Installation Verification | 29 |

This section covers the following topics:

Adapting to an Existing Environment

- [Step 1: Create a User Library](#)
- [Step 2: Modify the Job Skeletons](#)
- [Step 3: VTAM Definitions](#)
- [Step 4: Entire System Server Parameters](#)

Step 1: Create a User Library

The library `SYSNOMS` contains standard separator pages for reports and bundles, as well as job skeletons which have to be modified to suit your requirements. As the contents of `SYSNOMS` are overwritten by every new product release, copy the job skeletons you wish to modify from `SYSNOMS` to the library `SYSNOMU`, and modify them there.

If you want to use the Entire Output Management standard separation exits for reports and bundles, copy the current versions of the members `RS*` and `BS*` (with `REPLACE` option) to the library `SYSNOMU`.

Always copy the current versions of the following data areas (with the `REPLACE` option) to the library `SYSNOMU`:

- `P-UEXIT` and `P-UEXITE` (for separation exits),
- `P-PEXIT` (for printing exits),
- `NOMEXP*` and `NOMEX08E` (for user exits).

Then recatalog your user exits which use these parameter data areas.

The sample exits `UEX*` in the library `SYSNOMS` also use these parameter data areas. For further information on user exits, see the source of subprogram `UEXFRAME` in the library `SYSNOMS`.

Step 2: Modify the Job Skeletons

The following tasks require job skeletons which have to be adapted to your requirements. Adapt the sources in the library `SYSNOMU` which are specified in the Source column and make them available under the Target name as shown below:

| Task | Environment | Source | Target |
|----------|--|----------|--------------------------|
| ARCHIVE | z/OS Tape | JARCMTAP | JARCSKEL |
| | z/OS GDG or predefined Disk VOLSERs | JARCMDSK | |
| | z/OS, SMS | JARCMSMS | |
| REVIVE | z/OS Tape | JREVMTAP | JREVSKEK |
| | z/OS GDG or predefined Disk VOLSERs or SMS | JREVMDSK | |
| CONDENSE | z/OS Tape | JCDNMTAP | JCDNSKEL |
| | z/OS GDG or predefined Disk VOLSERs | JCDNMDSK | |
| | z/OS, SMS | JCDNMSMS | |
| PRINT | JES | SYSPRJES | SYSPRJES or user-defined |
| | z/OS Disk | DISKMVS | DISKMVS or user-defined |
| | z/OS Tape | TAPEMVS | TAPEMVS or user-defined |

Step 3: VTAM Definitions

To enable Entire Output Management to print to VTAM printers, add the definition from the member `NOMVTAM` in the Entire Output Management source library to your `SYS1.VTAMLST` library and activate it. If your `SYS1.VTAMLST` already contains a definition for Entire System Server, include only the definition for Entire Output Management in it.

In the Entire System Server parameters, assign the value for `SPOOLACB` as defined in your `SYS1.VTAMLST`.

Step 4: Entire System Server Parameters

To activate the common data pool, assign a value of at least "1" to the `CDALEN` parameter.

To run Natural subtasks, assign a value of at least "80" to the `NABS` parameter.

Natural Profile Parameters

For all online and batch tasks which execute Entire Output Management, the following Natural profile parameters have to be set:

| Parameter | Description |
|-----------|-------------------------------------|
| CVMIN=ON | Control variable modified at input. |
| ID=' ' | Set input delimiter to blank. |
| WH=ON | Wait for locked Adabas records. |

If UNIX or Windows platforms are to be used as external spooling system source, the following Natural profile parameters have to be set:

| Parameter | Description |
|---------------------------|--------------------------------|
| CFICU=ON | Unicode and code page support. |
| CP=ON | Default code page. |
| XML=(ON,RDOC=ON,PARSE=ON) | XML support. |

Natural Security Definitions

If Natural Security is installed at your site, you have to create security profiles for the following libraries and users.

Libraries

| Library | Description | with Steplibs |
|----------|---|---|
| SYSNOM | Entire Output Management online application. | <ul style="list-style-type: none"> ■ SYSSAT ■ SYSNOMU ■ SYSSEC (optional) ■ any other library containing user routines (optional) (see also note below) |
| SYSNOMH1 | Entire Output Management help system (English). | - |
| SYSNOMH2 | Entire Output Management help system (German). | - |
| SYSNOMU | User copy of SYSNOMS library. | - |



Note: When a user routine is requested, the steplibs are searched sequentially in the order in which they are specified in the security profile of SYSNOM, and the user-routine member from the first steplib in which it is found will be used. If a user-routine member and library are specified in a report definition and this library is not specified as steplib in the SYSNOM security profile, it will be temporarily appended to the list of steplibs being searched. For the user-routine member from that library to be used, a member of the same name must therefore not be contained in any of the other steplibs listed before in the library profile.

Users

Create a Natural Security user profile of user type "Person" for the user representing the Entire Output Management server, with the user ID and password identical to the `NSCUSER` and `NSCPSWD` parameters taken from the main member `SATPnnn` or `SPnnnnn`.

You can use one user ID for all or different user IDs for each server type. See also the [example](#) under *Define Environment for Entire Output Management Server* below.

Entire Output Management in a Non-Security Environment

Entire Output Management's start program `MENU` is executed from `SYSSAT`. In a non-security environment, this means that `MENU` will not be found as start program. Therefore you have to rename the program `MENUNOM` in the library `SYSNOM` to `MENU`. As an alternative, you can copy the program `MENU` of the library `SYSSAT` into the library `SYSTEM`. This, however, may have the disadvantage of causing other applications to erroneously find the program `MENU` in the library `SYSTEM`, thus producing undesired results.

If Natural Security is not installed at your site, the following steplib is automatically assigned to the library `SYSNOM`:

- `SYSSAT`
- `SYSNOMU`

Define Environment for Entire Output Management Server

- [General Layout of a Parameter Block](#)
- [Parameter Blocks and Parameters for Entire Output Management](#)

See also the section *Defining SAT, Natural and Product Parameters* in the *System Automation Tools Installation* documentation.

For each Entire Output Management Server you must define the run-time environment in one or more Natural members in the System Automation Tools user library `SYSSATU`.

If you want to run various Entire Output Management Servers under different Entire System Server nodes `nnn`, you must provide startup parameters at least in the related "main" members. These must conform to the following naming convention: `SATPnnn` or `SPnnnnn`. In addition, you can provide further Entire Output Management-specific parameters in a second member, whose name must not match the naming convention for the main members.

General Layout of a Parameter Block

```
<Prefix> <block-identifier>[<keyword>=<value>,...]
```

where:

| Parameter | Description |
|-------------------------|---|
| <Prefix> | SAT or compressed product code + prefix as specified in the SATSTART instruction. |
| <block-identifier> | SATENV/NATENV/SATSTART or product block identifier. |
| [<keyword>=<value>,...] | Block-specific parameter. |

Parameter Blocks and Parameters for Entire Output Management

Mandatory Parameters

| Parameter Block | Parameter | Description |
|-----------------|--------------------|---|
| SATENV | NSC=YES/NO | Indicates whether Natural Security is installed or not. |
| | NSCUSER= | If Natural Security is installed, this is the user ID for logging on to it. |
| | NSCPSWD= | Password for logging on to Natural Security. |
| | ESYUSER= | User ID for logging on to Entire System Server, if it is installed and an interface to an external security system is activated. |
| | NATTASK= | Name of the Natural subtask module for starting a server as a subtask. |
| SATSTART | PRODUCT=NOM | 3-byte product code. |
| | PREFIX= | PRODUCT and PREFIX are compressed into a prefix which identifies the Server-specific parameters. Usually the version <i>vrs</i> is specified as PREFIX. However, if you run more than one Entire Output Management Monitor on the same node, you have to specify SATSTART blocks with different PREFIXes for them. |
| | TYPE=SUBTASK/BATCH | Entire Output Management Servers are always started as subtasks. |

| Parameter Block | Parameter | Description |
|-----------------|---|--|
| | APPLIB=SYSNOM | Name of the Natural library where Entire Output Management Server is installed. |
| | SERVSYSF= | Pointer to the Entire Output Management data file (must be unique within all SATSTART instructions of this node). |
| NOMENV | ETID=* | Generate unique ETIDs for tasks. |
| | ETIDPREF= | 6-byte prefix for ETIDs. |
| NATENV | LFILE=(206,NOMSYSF-DBID,NOMSYSF-FNR) or LFILE=(131,SATSYSF-DBID,SATSYSF-FNR) or LFILE=(91,NOMACTDATA-DBID,NOMACTDATA-FNR) | These pointers can be set either in the common Natural parameter module created for the System Automation Tools products or in a Natural parameter profile indicated by the Natural parameter PROFILE. Make sure that the system-file pointer coincides with the pointer to the Entire Output Management system file 1 provided with the SERVSYSF parameter in the SATSTART block. |
| | WH=ON | The user is placed in "wait" status until either the requested record becomes available, or an error message is issued due to Adabas exceeding a time limit or other limit while attempting to place the record in "hold" status. |

Optional Parameters

You can overwrite the SATENV and NATENV parameters with Entire Output Management-specific or even Entire Output Management-subtask-specific assignments. The naming convention for the prefix which identifies the parameter block is:

```

                                (PRT for Print Task)
<Prefix> = NOM + <PREFIX> + (ARC for Archive Task)
                                (REV for Revive Task)

```

| Parameter Block | Parameter | |
|-----------------|---------------------|---|
| SATSTART | MEMBER= <i>name</i> | You can specify a member in which Entire Output Management-specific parameters are located. |

Example - Contents of "Main" Member for Node 148 - SATP148 or SP00148 in SYSSATU

The member SATP148 in SYSSAT provides an example of a "main" member. You can take this as the basis for your own member: Copy it to SYSSATU and adapt it.

| | | | |
|-----------|----------|--|--|
| SAT | SATENV | NATTASK=SAT3ST, NSC=YES, NSCUSER=SATMON, NSCPSWD=SATMON | Sets the SAT defaults for all System Automation Tools products. |
| NOMvrsPRT | SATENV | NSCUSER=NOMPRT NSCPSWD=NOMPRT ← | Indicates that a separate user ID/password can be used for Entire Output Management's Print task. |
| NOMvrsARC | SATENV | NSCUSER=NOMARC NSCPSWD=NOMARC | Indicates that a separate user ID/password can be used for Entire Output Management's Archive task. |
| NOMvrsREV | SATENV | NSCUSER=NOMREV NSCPSWD=NOMREV | Indicates that a separate user ID/password can be used for Entire Output Management's Revive task. |
| SAT | NATENV | DU=OFF, PROFILE=SATMON | Sets the Natural defaults for all System Automation Tools products: the Natural profile parameters are provided in the profile SATMON. |
| SAT | SATSTART | PRODUCT=NOM, PREFIX=vrs, TYPE=SUBTASK, APPLIB=SYSNOM, SERVSYSF=(88,51) | Specifies that the server for Entire Output Management is to be started as a subtask. |

Migrating from Previous Versions

- [Migration from Version 3.5.1 or 3.5.2 to Version 3.5.3 on Mainframes](#)
- [Migration from Version 3.4.3 to Version 3.5.3 on Mainframes](#)
- [Migration on UNIX Systems](#)

Migrations from earlier versions are not supported.

Migration from Version 3.5.1 or 3.5.2 to Version 3.5.3 on Mainframes

Migration Procedure

Execute the following jobs:

| Job | Step(s) | Action |
|------|---------|--|
| I200 | 2811 | Start of current system-file version (MIGSTART). |
| | 2812 | Migration of printers (MIGPRT). |
| | 2814 | Migration of the Monitor (MIGMON). |
| | 2819 | Setting of current system file version (MIGEND). |

Important:

In addition to the above migration procedure, you have to perform with Version 3.5.3 the following two recatalog steps:

- Recatalog all your user exits and all programs which use Entire Output Management application programming interfaces.
- If you use the program `NOMTP` in the library `SYSNOMS`, recatalog it (because the parameter data area `NOMTP - - P` used by it has been modified).

Migration from Version 3.4.3 to Version 3.5.3 on Mainframes

Important:

- Before you start the migration, make sure that:
 - the Entire System Server node on which the Entire Output Management Monitor runs is active,
 - the Entire Output Management Monitor itself is inactive.
- In addition to the migration procedure described below, you have to perform with Version 3.5.3 the following two recatalog steps:
 - Recatalog all your user exits and all programs which use Entire Output Management application programming interfaces.
 - If you use the program `NOMTP` in the library `SYSNOMS`, recatalog it (because the parameter data area `NOMTP - - P` used by it has been modified).
- As of Entire Output Management Monitor Version 3.4.1 on mainframes, record spanning is required to keep long buffers in Adabas. If the Adabas parameter `MIXDSDEV` is used in the `ADALOD` utility, record spanning is not available. Therefore the `MIXDSDEV` parameter must be omitted.

Migration Procedure

Execute the following jobs:

| Job | Step(s) | Action |
|------|------------------------|--|
| I082 | 2850, 2852, 2853, 2855 | Migration of system-file structure. |
| | 2851, 2854 (*) | Migration of system-file structure. |
| I200 | 2811 | Start of current system-file version (MIGSTART). |
| | 2812 | Migration of printers (MIGPRT). |
| | 2813 (**) | Migration of user exits (MIGUEX). |
| | 2814 | Migration of the Monitor (MIGMON). |
| | 2815 | Check of report identifications (CHCKIDNT). |
| | 2816 | Migration of the SAT logs of NOM (MIGSAT). |
| | 2819 | Setting of current system file version (MIGEND). |

(*) These steps are only required if you use two Entire Output Management data files, one containing definition data and one containing active data.

(**) MIGUEX always ends with condition code 0 in order to continue the migration process. Check the output of MIGUEX for indications of missing or outdated modules.

Migration on UNIX Systems

See *Migration* in the *Installation and Customization on UNIX* documentation.

Starting Entire Output Management for the First Time

➤ To start Entire Output Management for the first time:

- 1 Make sure that the Entire System Server node under which the Entire Output Management Monitor runs is active.
- 2 Log on to the library `SYSNOM`.
- 3 Execute the program `INSTALL`.

This program adds the first user ID, modifies some example definitions, and asks you to specify various Entire Output Management parameters.

Make the necessary specifications, and leave each screen with `PF3`

When you have completed this step, the Entire Output Management **Main Menu** is displayed.

- 4 Enter the command `START MONITOR` in the command line to start the Entire Output Management Monitor online.

For information on how to automatically start the Entire Output Management Monitor when starting Entire System Server, see the section *AUTO-START* in the *System Automation Tools Installation* documentation.

Installation Verification

To verify that Entire Output Management has been installed correctly, perform the following steps.

Step 1: Verify the Startup Parameters Defined in Library SYSSATU

➤ **To do so:**

- 1 Log on to the library SYSSATU where you keep your master definitions for all servers of the System Automation Tools family.
- 2 Check that the SATnnnnn entry in the member SATDIR points to the correct FNAT for the application SYSSAT.
- 3 Check member SATPnnn or SPnnnnn for the SATSTART entry with PRODUCT=NOM. The TYPE parameter should have the value SUBTASK; the APPLLIB parameter must have the value SYSNOM, and the SERVSYSF parameter must point to the correct Entire Output Management system file where the object definitions are kept.
- 4 Check member SATPnnn or SPnnnnn for the SATENV parameter NATTASK. The value in effect for Entire Output Management must indicate the correct Natural subtask module. This Natural module must be correctly linked and accessible in the run-time environment of the Entire System Server node nnn.
- 5 Check the member SATPnnn or SPnnnnn for the SATENV parameters NSCUSER, NSCPSWD and ESYUSER. If you use Natural Security, <NSCUSER> must be defined as user and must have access to the libraries SYSNOM and SYSNOMU.

If Entire System Server is running with security (i.e.: SECURITY<>NONE), the user ID indicated by <ESYUSER> must be defined in the external security system and have sufficient authorization.

Step 2: Verify the Monitor Defaults

➤ To do so:

- 1 Log on to the library `SYSNOM` and invoke the program `MENU`.
- 2 Enter the direct command `8.1`. On the **Default Definition Menu**, select Option 1 to verify that the System Default parameters `DBID` and `FNR` parameters point to the correct Entire Output Management system file.
- 3 Return to the menu by pressing `PF3`, and then select Option 2 to verify the Monitor Defaults:

- node, batch module and system server jobname should be correct;
- at least one printer task should be specified;
- at least one output class reserved for Entire Output Management is specified (z/OS);



Note: For JES3, these classes must be defined as `HOLD=EXTWTR`

- temporary class is specified.

Step 3: Start the Entire Output Management Server Automatically with Entire System Server

If the Entire System Server is active, proceed with *Step 4* below, to start the Entire Output Management Server online.

If the `SATSTART` block for the Entire Output Management Server in the `SYSSATU` member `SATPnnn` or `SPnnnnnn` is provided correctly, the Server is started automatically with the Entire System Server node `nnn`.

➤ To do so:

- 1 Start the Entire System Server node `nnn`.

The successful start of the Entire System Server is indicated by the console message:

```
Entire System Server IS READY - X-COM NODE nnn IS INITIALIZED
```

The successful start of the Entire Output Management Server is indicated in the Entire Output Management log (direct command `DLOG MON`):

```

NOM1522 Monitor logged on to NPR UserId = NOMMON.
NOM1510 Monitor initialization completed successfully.
NOM1524 Number of Printer Tasks 2.
NOM1525 Printer task Type ..... SUBTASK.
NOM1503 Monitor minimum wait .. 30.
NOM1504 Monitor maximum wait .. 30 .
NOM1505 Monitor increment ..... 5.
NOM1506 Monitor node ..... 148.
NOM1507 Monitor DBID ..... 1.
NOM1508 Monitor FNR ..... 37.
NOM1527 Operating System Type . MVS/ESA.
NOM1528 Spool Type ..... JES2.
NOM1509 Start monitor initialization.
NOM1511 Monitor startup.

```

The corresponding console messages will be displayed:

```

NOM1510 Monitor initialization completed successfully.
NOM1603 Monitor NOMXTS dbid fnr on node node started.

```

- 2 If this sequence does not appear after a while, check the following:
 - If the Entire System Server node is running under z/OS, check the SYSOUT files of the node.
- 3 Proceed with *Step 5* below.

Step 4: Start the Entire Output Management Server Online

➤ To do so:

- In the Entire Output Management online system, enter the direct command `START MON.`

Step 5: Produce Sample Output in one of Entire Output Management's Reserved Classes

➤ To do so:

- 1 Run any job which produces output in one of the classes defined as reserved for Entire Output Management.
- 2 When the job has finished, invoke the **Monitor Management** screen, and wake up the Monitor by pressing PF10.

The Monitor should now start creating reports derived from the report definition UEX-DEFAULT.
- 3 Enter the direct command `LIST AREP`, and then the line command `LI` for the folder `#Inbasket` to list the active reports contained in it.

Then enter the line command `BR` to browse the arrived reports.

6

Installing Optional Features

| | |
|--|----|
| ■ Printing from Natural to Entire Output Management Directly | 34 |
| ■ Natural Advanced Facilities | 35 |
| ■ Report Format Conversion - Additional Requirements | 36 |
| ■ 3GL Interface Installation and Verification | 37 |
| ■ Re-Routing VTAM Output to Entire Output Management | 42 |

This section covers the following topics:

Printing from Natural to Entire Output Management Directly

Instead of printing output from Natural programs in a spooling system, you can route it to an Entire Output Management container file (SYS2) in which the trigger data are to be stored, and from which the output can be distributed, bundled or separated. On the Entire Output Management side, NAT reports are handled exactly the same as NAF reports (same report identification attributes, same spool attributes except that the source type is 10 for NAT, and 11 for NAF).

In order to create NAT reports, `NOMPUT`, `NOMADA` and `NOMCOMPR` must be linked with Natural (`NOMADA` has to be assembled the same as for NAF) and `LFILE 206` must specify the appropriate Entire Output Management system file. The report data are written into the trigger container file, which has to be defined and activated (otherwise active reports will not be created); see *Trigger Container File*.

To install the access method, you have to link the following modules to your Natural nucleus:

```
NATAM12
NOMADA
NOMCOMPR
NOMPUT
```

Include the modules in your operating-system environment as described under [Using `NOMPUT`](#).

Example - Writing Data to Entire Output Management, where Printer 2 is Defined as NOM Printer:

Start Natural with the profile parameter `PRINT=(2,AM=NOM)`.

Then execute the following program:

```
DEFINE PRINTER (2) OUTPUT 'NOM'
  PROFILE 'PROF'
  FORMS 'FORM'
  NAME 'LISTNAME'
  DISP 'D'
  CLASS 'X'
  COPIES 3

WRITE (2) 'HELLO, THIS IS PRINTER 2.'
CLOSE PRINTER (2)
END
```


Your output will be written directly to the defined Entire Output Management container file, without using any spooling system.

Natural Advanced Facilities

This section is only relevant if you use Natural Advanced Facilities. It covers the following topics:

- [Printing from Natural Advanced Facilities to Entire Output Management](#)
- [Printing from Entire Output Management to Natural Advanced Facilities](#)

Printing from Natural Advanced Facilities to Entire Output Management

Instead of printing output from Natural programs in the Natural Advanced Facilities (NAF) spool file (FSPOOL), you can route it to an Entire Output Management file (SYS2), from which it can be distributed, bundled or separated.

Here you can define whether the NAF/NOM interface is active and from which Natural Advanced Facilities environments output is to be processed. A separate Entire Output Management container file can be assigned to each FSPOOL file. However, you can also assign the same container file to all FSPOOL files.

To define default parameters for Natural Advanced Facilities for printing to Entire Output Management, see *Natural Advanced Facilities Defaults* in the *System Administration* documentation.

Printing from Entire Output Management to Natural Advanced Facilities

To print from Entire Output Management to Natural Advanced Facilities:

- Natural Advanced Facilities must be installed in the Natural nuclei used by the monitor and for batch printing.
- The necessary Natural Advanced Facilities modules must be linked.
- The parameter modules must define printers 3 and 4 as type *NAF*, as well as specifying any site-specific parameters such as *NAFSIZE*, *NAFUPF* and *FSPOOL*.

For further information, see the *Natural Advanced Facilities* documentation.

Report Format Conversion - Additional Requirements

If report format conversion - as described under *Converting the Report Format* in the *Concepts and Facilities* documentation - is intended, the utilities Ghostscript and Enscript have to be installed. The corresponding commands - `gs` and `enscript` respectively - must reside on any open systems machine where the conversions will be executed. Entire System Server has to be installed there as well, and each conversion node must be defined as a UNIX node in Entire Output Management (8.1/13 menu, can be deactivated).

On UNIX systems, both packages are in most cases already installed.

On Windows, it is recommended that the entire "gnuwin32" package be installed. You can find download pages at:

- <http://sourceforge.net/projects/ghostscript/>
- <http://sourceforge.net/projects/gnuwin32/>

The following utilities all of which, except Ghostscript, are GNU software, will be used:

```
ghostscript
enscript
file
find
sed
pdftk (optional)
```

The package `pdftk` is used if a report or a printer requires a mask file which is to be overlaid to the original report. It is available for UNIX and Windows systems.

The existence of the utilities will be checked using the execution path. This means that the path of both utilities has to be added to the current execution path (environment variable `PATH`).

If the module names are different from `gs` and `enscript`, two additional environment variables are required. The following environment variables of the user ID which is used in the UNIX node definition of Entire Output Management can be defined:

- If Ghostscript is not invoked with `gs`, define the environment variable `GSMOD`. In the following example, Ghostscript 9.06 for Windows has been installed. `GSMOD` contains: `gswin64c.exe`
- If Enscript is not invoked with `enscript`, enter the correct name in the environment variable `ENMOD` in a similar way.



Note: The above-mentioned UNIX utilities are invoked by Entire Output Management, but are not part of it; they are third-party products which we neither deliver nor provide support for.

3GL Interface Installation and Verification

- **3GL Interface Defaults (1 and 2)**
- **SYSERR - Display Short Messages**
- **Report Definition - General Attributes and 3GL ID (3)**
- **Using NOMPOT**

This section describes how to define a 3GL interface and how to test it with the supplied sample programs.

1. Load a container file (SYS2) with no records. The output will be stored in this file.
2. Define the 3GL interface defaults, as described under *3GL Interface Maintenance* in the *System Administration* documentation:

3GL Interface Defaults (1)

```

11:40:31          **** Entire Output Management ****          05/05/2024
UserId XYZ          - 3GL Interface Defaults -

3GL Interface 104

active ..... Y
Time Limit ..... _
Description ..... User-defined Spool (3GL Interface 104)_____

NOM container file
DBID ..... 1_
FNR ..... 138

Identifying Attributes
Prompt          Offset  Length  Order  Generic (*)
1040_____      1_      8_      1_      Y
1041_____      9_      8_      2_      N
1042_____     17_      8_      3_      N
_____          _       _       _       _

File identification
1043_____     33_      8_

```

3GL Interface Defaults (2)

```
11:45:54          **** Entire Output Management ****          05/05/2024
UserId XYZ          - 3GL Interface Defaults -

3GL Interface 104

active ..... Y
Description ..... User-defined Spool (3GL Interface 104)_____

Attributes
Prompt          Offset  Length
1045_____      25_    8__
1044_____      41_    50_
_____          ____  ____
_____          ____  ____
_____          ____  ____
_____          ____  ____
_____          ____  ____
_____          ____  ____
_____          ____  ____
_____          ____  ____
_____          ____  ____
```

- 3. In the SYSERR utility, enter the prompt texts under the defined numbers (library SYSNOMU). If both the English and the German version of Entire Output Management are used, you have to enter the texts for both languages.

SYSERR - Display Short Messages

| 11:55:13 | ***** NATURAL SYSERR Utility ***** | 05/05/2024 |
|-------------|------------------------------------|------------|
| | - Display Short Messages - | |
| Number | Short Message (English) | |
| ----- | ----- | |
| SYSNOMU0001 | User Id | |
| SYSNOMU0002 | Name | |
| SYSNOMU0003 | First Name | |
| SYSNOMU0004 | Birth date | |
| SYSNOMU1040 | User ID | |
| SYSNOMU1041 | Terminal ID | |
| SYSNOMU1042 | Program | |
| SYSNOMU1043 | List-Name | |
| SYSNOMU1044 | Description | |
| SYSNOMU1045 | List ID | |
| SYSNOMU1234 | testprompt | |

4. Create a default report for your 3GL interface. Enter an asterisk (*) for the identifying attribute that you defined with Generic=Y in the definition. For further information, see *Report Identification for 3GL Interface* in the *User's Guide*.

Report Definition - General Attributes

12:12:40**** Entire Output Management ****05/05/2024

User ID XYZ- Report Definition >General Attributes -

Report

Name USR104-DEFAULT____

Description Default definition for 3GL interface 104_____

Type D

Keywords _____

Master Owner MRS_____

Store in NOM DB N

Archive directly N

Retention

Report

Archive

Revive

Number 1____

Unit A

Calendar _____

Action P

Report Definition - 3GL Identification (3)

```
15:13:43          **** Entire Output Management ****          05/05/2024
User ID XYZ      - Report Definition >3GL Identification -
```

```
Report
  Name ..... USR100-DEFAULT____
3GL Interface 100 Attributes
```

```
and
```

| |
|--|
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |

5. Enter the database ID and file number of your container file in the module NOMADA. These are simply defaults which can be overwritten in the 3GL program.
6. SHUTDOWN and START the Monitor.
7. Modify the supplied member ASMNOM and assemble the module NOMADA.

To execute the COBOL example, continue with Step 13 below.

8. Modify the supplied module NOMEX3GL. O\$ATTR must contain the spool attributes (identifying attributes, file identification and other attributes) as defined in the interface. N\$SRCTYP must contain the interface number at OPEN. N\$DBID and N\$FNR must contain the database ID and file number respectively.
9. Assemble the module NOMEX3GL.
10. Modify the member LNKEX3GL and link the sample program.
11. Modify the member RUNEX3GL and run the sample program.
12. Check the Monitor Log to see whether a report has been created.
13. Modify the supplied module NOMEX3CO. NOMPOT-ATTRIBUTES must contain the spool attributes as defined in the interface. In the subsection BA-INITIALISE, the interface number must be assigned to the field NOMPOT-CB-SOURCE-TYPE, the database number to the field NOMPOT-CB-CONT-DBID, and the file number of the container file to field NOMPOT-CB-CONT-FNR.
14. Modify the member COBNOM and compile the module NOMEX3CO.
15. Modify the member LNKEX3CO and link the sample program.

16. Modify the member RUNEX3CO and run the sample program.
17. Check the Monitor Log to see whether a report has been created.

Using NOMPOT

Installing an Entire Output Management Logical Printer in Natural Advanced Facilities

1. The delivered module NOMADA is assembled with the following parameters and will be valid for use with Natural and Natural Advanced Facilities. If you want to use NOMPOT with Natural, proceed with Step 4. If you are using 3GL languages, adapt the parameters to suit your requirements:

| Parameter | Explanation |
|--------------------|---|
| AUTOET=0 | Do not perform ETs. |
| CICS=YES/NO | CICS environment required / not required (see below). |
| NATURAL=NO | Natural/Adabas not required. |
| NATVERS= <i>vr</i> | Version of Natural. |
| NOMDBID=0 | Database ID of Entire Output Management container file. |
| NOMFNR=0 | File number of Entire Output Management container file. |

NOMADA is the interface between NOMPOT and Adabas, and it can be used by:

- 3GL batch programs, in which case CICS=NO must be set;
 - 3GL programs running under CICS, in which case CICS=YES must be set.
2. Assemble NOMADA using Entire Output Management, Natural and Adabas source libraries as steplib; for example, see z/OS sample job ASMNOM:
 3. INCLUDE the modules NOMPOT and NOMADA to the nucleus where NAFNUC is included (usually the shared nucleus):
 4. For printing from Natural Advanced Facilities, define the Natural Advanced Facilities printers as follows:

```
NTPRINT(m-n),AM=NAF
```

5. Define a logical printer in Natural Advanced Facilities with type NOM.
6. Edit the Natural Advanced Facilities defaults in Entire Output Management to link the Natural Advanced Facilities spool file and Entire Output Management container file and activate the Natural Advanced Facilities interface with "Y".
7. Direct the output of your Natural program to Entire Output Management using:

```
DEFINE PRINTER (n) OUTPUT logical-NAF-printername
```

Output of this type is stored in the specified Entire Output Management container file. Note that container files must be located on the local system where Entire Output Management runs; remote container files accessed via Network are not possible.

Re-Routing VTAM Output to Entire Output Management

It is possible to re-route output from a VTAM application to Entire Output Management. This applies, for example, to reports generated by a user in a VTAM application (for example, Complete or CICS) which are written to VTAM printers. These reports can be the results of hardcopy requests, print requests, a Natural Advanced Facilities report, etc.

For this purpose, the VTAM virtual-printer application `NOMVPRNT` is provided, which simulates a VTAM printer. `NOMVPRNT` can run as a started task, or as a sub-task under Entire System Server. The output can be re-routed either to the JES spool or to the Entire Output Management container file. In Entire Output Management, the output will be processed according to the corresponding report definitions.

To use this feature, you have to make the following definitions:

- [Definitions in VTAM](#)
- [Definitions in Entire Output Management](#)
- [Running NOMVPRNT Under Control of Entire System Server](#)

Definitions in VTAM

In VTAM, you define each virtual printer as follows:

```
printer-name APPL AUTH=NVPAGE,EAS=1,PARSESS=NO,DLOGMOD=DSC2K,SESSLIM=YES
```

The following startup parameters have to be specified for `NOMVPRNT`:

| Parameter | Explanation |
|--|--|
| <code>PRINTER=<i>printer-name</i></code> | Specify an entry for each printer whose printouts are to be handled by Entire Output Management. |
| <code>STORE=DB/SP</code> | Specify the destination of the re-routed output: <code>STORE=DB</code> - Output is written to the Entire Output Management container file. <code>STORE=SP</code> - Output is written to the JES spool. |
| <code>NOM-DBID=nnnnn</code> | If <code>STORE=DB</code> , specify the database ID of the container file. If <code>STORE=SP</code> , specify the database ID of the Entire System Server node for Entire Output Management. |
| <code>NOM-FNR=nnnnn</code> | Only applicable with <code>STORE=DB</code> : Specify the file number of the container file. |

| Parameter | Explanation |
|----------------------------|--|
| NOM-CLASS= <i>c</i> | Only applicable with STORE=SP: Specify the JES class which is to be handled by the Entire Output Management monitor. |
| NOM-USER= <i>uuuuuuuuu</i> | Only applicable with STORE=SP: Specify the user ID to be used by Entire System Server. For this Entire System Server node, you specify the startup parameter STDUSER= <i>uuuuuuuuu</i> . |
| ADA-SVC= <i>nnn</i> | Specify the number of the Adabas SVC. The default value is 249. |
| SNAP=YES/NO | For tracing, specify YES. The default is NO. |
| WTOTRACE=YES/NO | For tracing, specify YES. The default is NO. |

Under z/OS, the DD-card NOMSPRM points to the startup parameters.

If NOMVPRNT runs under control of Entire System Server (see below), this DD-card can be omitted.

Sample JCL - z/OS:

```
//EXEC  PGM=NOMVMAIN,TIME=1440
//STEPLIB DD DSN=nom.load,DISP=SHR
//      DD DSN=adabas.loadlib,DISP=SHR
//NOMSPRM DD DSN=parm-file,DISP=SHR
//NOMPRSNP DD SYSOUT=X
```

Definitions in Entire Output Management

- [Output to JES Spool](#)
- [Output to Container File](#)

Output to JES Spool

If the output is to be re-routed to the JES spool, the JES report definitions in Entire Output Management apply.

The following report definitions are required:

- On the **Report Definition > General Attributes** screen, the field **Store in NOM DB** must be set to "Y". This ensures that the report can be viewed even if the spool file in JES is deleted.
- On the **Report Definition > JES Identification** screen, the *printer-name* must be specified in the **Writer** field.

Output to Container File

If the output is to be re-routed to Entire Output Management container file, the following definitions are required:

- **System defaults:**
On the **3GL Interface Defaults** screen, set the field **active** to "Y", and in the fields **NOM Container File DBID/FNR**, specify the same database ID and file number as in the VTAM startup parameters (see above).

See Example A below.

- **Report definition for each report:**
On the **Report Definition > 3GL Identification** screen (which is invoked by pressing PF7 on the **Report Definition > General Attributes** screen, and then PF8 and then selecting the desired 3GL interface), specify the printer name (NOMPRTnn) in the **3GL Interface nnn Attributes** field.

See Example B below.

Example A - Define 3GL interface 105 (function 8.1.12 on the Main Menu):

```
23:55:10          **** ENTIRE OUTPUT MANAGEMENT ****          2024-07-07
UserId XYZ          - 3GL Interface Defaults -

3GL Interface 105
active ..... Y
Time Limit ..... _
Description ..... NOMPVRT to container_____

NOM container file
DBID ..... 9_
FNR ..... 246_

Identifying Attributes
Prompt      Offset  Length  Order  Generic (*)
1234_____ 1_      8_      1_      N
_____      _      _      _      _
_____      _      _      _      _
_____      _      _      _      _

File identification
*_____ 1_      8_

Command => _____
Enter-PF1---PF2---PF3---PF4---PF5---PF6---PF7---PF8---PF9---PF10---PF11---PF12---
      Help      Exit  Flip                               Attrb                               Menu
```

Example B - with selected interface 105:

```

User ID XYZ          - Report Definition >3GL Identification -
Report
  Name ..... REP2112_____
3GL Interface 105 Attributes
  ..... NOMPRT42

```

Running NOMVPRNT Under Control of Entire System Server

NOMVPRNT can run under control of Entire System Server as follows:

- [NOMVPRNT As Subtask](#)
- [NOMVPRNT As Started Task](#)
- [NOMVPRNT As Batch Job](#)

If NOMVPRNT runs under control of Entire System Server, the file which contains the startup parameters is specified in SATENV with the keyword DATASET.

All output from NOMVPRNT will be written into a separate SYSOUT file under the DD-name NMVvrsMS.

If AUTO=OFF is specified in the SATSTART parameter block, NOMVPRNT can be started and stopped from Entire Output Management, menu 8.11.

For details on the parameter blocks and startup parameters mentioned above and in the three sections below, see also [Define Environment for Entire Output Management Server](#).

NOMVPRNT As Subtask

If NOMVPRNT is to run as a subtask, you have to specify the following System Automation Tools startup parameters.

The parameter block SATENV must be specified as follows:

```
NMVvrs SATENV DATASET=dataset(member) [/volser]
```

The parameter block SATSTART must be specified as follows:

```
SAT SATSTART PRODUCT=NMV,  
              TYPE=SUBTASK,  
              PREFIX=vrs  
              SERVSYSF=(dbid,fnr)  
*              AUTO=OFF
```

where *vrs* must be the same as specified in SATENV, and *dbid* and *fnr* must be the same as specified for LFILE 206.

The parameter block NATENV can be omitted.

NOMVPRNT As Started Task

If NOMVPRNT is to run as a started task, you have to specify the following System Automation Tools startup parameters.

The parameter block SATENV must be specified as follows:

```
NMVvrs SATENV DATASET=dataset(member)  
              STC=started-task-name
```

The parameter block SATSTART must be specified as follows:

```
SAT SATSTART PRODUCT=NMV,  
              TYPE=BATCH,  
              PREFIX=vrs  
              SERVSYSF=(dbid,fnr)  
*              AUTO=OFF
```

where *dbid* and *fnr* must be the same as specified for LFILE 206.

The parameter block NATENV can be omitted.

NOMVPRNT As Batch Job

If NOMVPRNT is to run as a batch job, you have to specify the following System Automation Tools startup parameters.

The parameter block SATENV must be specified as follows:

```
NMVvrs SATENV DATASET=dataset(member)  
          NATSKEL=job-skeleton-name
```

The library `SYSNOMS` contains the job skeletons `JNMVMVS1` and `JNMVVSE1`, which you can adapt to suit your requirements.

The parameter block `SATSTART` must be specified as follows:

```
SAT SATSTART PRODUCT=NMV,  
              TYPE=BATCH,  
              PREFIX=vrs  
              SERVSYSF=(dbid,fnr)  
*              AUTO=OFF
```

The parameter block `NATENV` can be omitted.

