

**webMethods Oracle Applications Adapter
11.5.10 Predefined Transaction Services
Installation Guide**

Version 6.0

January 2006

This document applies to webMethods Oracle Applications Adapter Version 6.0 and to all subsequent releases.

Specifications contained herein are subject to change and these changes will be reported in subsequent release notes or new editions.

Copyright © 2006 Software AG, Darmstadt, Germany and/or Software AG USA, Inc., Reston, VA, United States of America, and/or their licensors.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://documentation.softwareag.com/legal/>.

Use of this software is subject to adherence to Software AG's licensing conditions and terms. These terms are part of the product documentation, located at <http://documentation.softwareag.com/legal/> and/or in the root installation directory of the licensed product(s).

This software may include portions of third-party products. For third-party copyright notices and license terms, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products." This document is part of the product documentation, located at <http://documentation.softwareag.com/legal/> and/or in the root installation directory of the licensed product(s).

Contents

- Overview3
- Requirements3
- Install the Predefined Transaction Services4
- Uninstall Predefined Transaction Services6

Overview

This guide provides system requirements for the webMethods Oracle Applications Adapter 11.5.10 Predefined Transaction Services 6.0 for use with the webMethods Oracle Applications Adapter 6.0 and explains how to install and uninstall them.



Important! The information in this guide might have been updated since the guide was published. Go to the webMethods Advantage Web site at <http://advantage.webmethods.com> for the latest version of the guide.

Requirements

The webMethods Oracle Applications Adapter 11.5.10 Predefined Transaction Services 6.0 have the same software or hardware requirements and support the same platforms as the webMethods Oracle Applications Adapter 6.0.

If you have not yet installed the webMethods Oracle Applications Adapter 6.0, install the adapter before continuing. For instructions, see the *webMethods Oracle Applications Adapter Installation Guide*.



Important! You *must* also have installed webMethods Oracle Applications Adapter 6.0 Fix 1. Additionally, it is recommended that you also install all other fixes to the adapter.

Install the Predefined Transaction Services



Important! This section provides only instructions that are specific to using the webMethods Installer to install the predefined transaction services. For complete instructions on using the webMethods Installer, see the *webMethods Installation Guide*.

Install the 11.5.10 predefined transaction services on the machine that hosts your webMethods Oracle Applications Adapter 6.0. If you are installing the services in a clustered environment, you must install the services on each webMethods Oracle Applications Adapter in the cluster, and each installation must be identical. For more information about using the webMethods Oracle Applications Adapter in a clustered environment, see the *webMethods Oracle Applications Adapter User's Guide* and the *webMethods Oracle Applications Adapter 11.5.10 Predefined Transaction Services User's Guide*.

To install the predefined transaction services

- 1 Configure Oracle Applications Adapter to support 11.5.10 predefined transaction services. To do so:
 - a Open the Server Administrator.
 - b From the **Settings** menu of the navigation panel, click **Extended**.
 - c Click **Edit Extended Settings**.
 - d Update or add the following property to add 11.5.10 as a supported version:
watt.WmOAAadapter.additionalVersions

For example:
 - To add support for Oracle Applications version 11.5.10, specify:
watt.WmOAAadapter.additionalVersions=11510
 - If you want to add additional versions to support a repository of your own creation, be sure your repository name is different from any actual version names; otherwise, your information may be overwritten. For example:
watt.WmOAAadapter.additionalVersions=11510U
 - e Click **Save Changes**.
- 2 Shut down the Integration Server that hosts webMethods Oracle Applications Adapter 6.0.
- 3 If you have not yet installed webMethods Oracle Applications Adapter 6.0 Fix 1, do so before continuing.
- 4 Download the webMethods Installer from the webMethods Advantage Web site at <http://advantage.webmethods.com> and start the Installer.

- 5 Specify the installation directory as the webMethods installation directory (by default, webMethods6).
- 6 In the component selection list, navigate to the **Adapters** folder. Within the **Adapters** folder, navigate to **webMethods Oracle Applications Adapter 6.0 ▶ Predefined Transactions 11.5.10**. Choose to install **Documentation and Program Files** plus any packages containing the predefined transaction services for Oracle Applications 11.5.10 that you want to install.

The Installer installs the predefined transaction services packages in the *Integration Server_directory/packages* directory. The Installer also installs a shared package named *WmOACCommon11510*. Documentation for the predefined transaction services is installed in the */doc* subdirectory in the *WmOACCommon11510* package.



Note: You can install additional predefined transaction service packages later by re-running the Installer.

- 7 Restart the Integration Server.
- 8 You must set up the Oracle Applications database to work with the predefined transaction services you installed. To do this, you install components such as stored procedures, views, and triggers that are specific to the services on the database. For instructions, see the *webMethods Oracle Applications Adapter 11.5.10 Predefined Transaction Services User's Guide*.



Note: When you first install webMethods Oracle Applications Adapter 11.5.10 Predefined Transaction Services, the *WmOACCommon11510* package is disabled and the predefined transaction services packages are not displayed even though they are installed. To view the predefined transaction services packages, use the Package Management screens of the Server Administrator to enable the *WmOACCommon11510* package and restart the Integration Server. This allows you to view all available predefined services packages (they will be disabled). Enable the predefined transaction services packages you want to use.

Uninstall Predefined Transaction Services

This section provides instructions for using the webMethods Uninstaller to uninstall the 6.0 predefined transaction services. For complete instructions on using the webMethods Uninstaller, see the *webMethods Installation Guide*.

To uninstall predefined transaction services

- 1 From the Oracle Applications database, remove all components for the predefined transaction services you are going to uninstall. For instructions, see the *webMethods Oracle Applications Adapter 11.5.10 Predefined Transaction Services User's Guide*.



Important! If you do not remove these components, they could consume resources on your Oracle Applications system. This is particularly true if you have components such as custom tables or triggers for send services.

- 2 Shut down the Integration Server that hosts the services.
- 3 Start the webMethods Uninstaller.
- 4 Choose the predefined transaction services packages to uninstall.
- 5 The Uninstaller does not delete files created after you installed the adapter (for example, user-created or configuration files), nor does it delete the directory structure that contains the files. If you do not want to save the files that the Uninstaller did not remove, navigate to the *Integration Server_directory*\packages directory and delete the predefined transaction services package directory you want to remove.
- 6 Restart the Integration Server.