

Starting the Development Workplace

The development workplace is the central point for starting tools for layout development.

This chapter covers the following topics:

- Starting the Servlet Container
 - Starting the Development Workplace
-

Starting the Servlet Container

In order to start the development workplace, your servlet container must have been started. This can be Tomcat or any other servlet container. See also *Installation Information* in the *Installation* documentation.

Starting the Development Workplace

The development workplace can be invoked from all supported Windows and UNIX platforms.

▶ To start the development workplace in the browser

- Invoke your browser and start the development workplace with the following URL:

```
http://localhost:51000/cis/HTMLBasedGUI/workplace/ide.html
```

Note:

If you have defined another port number during installation, enter this port number instead of the default port number 51000.

The development workplace is shown in your browser. See *Elements of the Development Workplace* for further information.

▶ To start the development workplace in the SWT client

1. Invoke your browser and enter the following URL:

```
http://localhost:51000/cis/SWTBasedGUI/index.html
```

Note:

If you have defined another port number during installation, enter this port number instead of the default port number 51000.

2. Choose the following link: *Launch SWTBasedGUI - Development*.

When Java Web Start has been installed, the development workplace is shown in your browser. See *Elements of the Development Workplace* for further information.

For limitations, see *SWT Client* in the *Special Development Topics* documentation.