

# CISFO:FOOTER2

Printouts typically have a header and/or footer to indicate the page content. You may use the footer to output the document's title, the page number and the date of creation. It opens a container area that holds any other controls inside.

---

## Properties

| Color           |  |          |  |
|-----------------|--|----------|--|
| backgroundcolor | This attribute sets the background color of an element, either a <code>&lt;color&gt;</code> value or the keyword "transparent", to make the underlying colors shine through. | Optional | #000000<br>#808080<br>#FFFFFF<br>#FF0000 |
| color           | Color in which the element is output.  | Optional | #000000<br>#808080<br>#FFFFFF<br>#FF0000 |
| Border          |  |          |  |
| bordercolor     | Color for all borders (bottom, top, left, right). Values are any valid color specification.  | Optional | #000000<br>#808080<br>#FFFFFF<br>#FF0000 |
| borderstyle     | This attribute specifies the line style of all box's border. Some valid values are "solid", "double" or "dashed".  | Optional | solid<br>none                            |
| borderwidth     | The border width attribute specifies the width of all borders. Some valid values are "thin", "medium", "thick" or a concrete size (e.g. "2pt").                              | Optional | 1pt<br>5pt<br>1mm<br>5mm                 |

|                   |   |          |  |
|-------------------|---|----------|--|
| bordertopcolor    | Color for the border on the top. Values are any valid color specification.  | Optional | #000000<br>#808080<br>#FFFFFF<br>#FF0000 |
| bordertopstyle    | This attribute specifies the line style of a box's top border. Some valid values are "solid", "double" or "dashed".                                 | Optional | solid<br>none                            |
| bordertopwidth    | The border width attribute specifies the width of the top border. Some valid values are "thin", "medium", "thick" or a concrete size (e.g. "2pt").  | Optional | 1pt<br>5pt<br>1mm<br>5mm                 |
| borderleftcolor   | Color for the border on the left side. Values are any valid color specification.  | Optional | #000000<br>#808080<br>#FFFFFF<br>#FF0000 |
| borderleftstyle   | This attribute specifies the line style of a box's left border. Some valid values are "solid", "double" or "dashed".                                | Optional | solid<br>none                            |
| borderleftwidth   | The border width attribute specifies the width of the left border. Some valid values are "thin", "medium", "thick" or a concrete size (e.g. "2pt"). | Optional | 1pt<br>5pt<br>1mm<br>5mm                 |
| borderbottomcolor | Color for the border on the bottom. Values are any valid color specification.   | Optional | #000000<br>#808080<br>#FFFFFF<br>#FF0000 |
| borderbottomstyle | This attribute specifies the line style of a box's bottom border. Valid values are 'solid', 'double' or 'dashed'.                                   | Optional | solid<br>none                            |

|                   |   |          |   |
|-------------------|---|----------|---|
| borderbottomwidth | The border width attribute specifies the width of the bottom border. Valid values are "thin", "medium", "thick" or a concrete size (e.g. "2pt").  | Optional | 1pt<br>5pt<br>1mm<br>5mm                                |
| borderrightcolor  | Color for the border on the right side. Values are any valid color specification.   | Optional | #000000<br>#808080<br>#FFFFFF<br>#FF0000                |
| borderrightstyle  | This attribute specifies the line style of a box's right border. Some valid values are "solid", "double" or "dashed".   | Optional | solid<br>none   |
| borderrightwidth  | The border width attribute specifies the width of the right border. Some valid values are "thin", "medium", "thick" or a concrete size (e.g. "2pt").  | Optional | 1pt<br>5pt<br>1mm<br>5mm                                |
| <b>Font</b>       |   |          |   |
| fontfamily        | This attribute specifies a prioritized list of font family names and/or generic family names. To deal with the problem that a single font may not contain glyphs to display all the characters in a document, or that not all fonts are available on all systems, this property allows authors to specify a list of fonts, all of the same style and size, that are tried in sequence to see if they contain a glyph for a certain character. This list is called a "font set". | Optional | Helvetica<br>Times<br>Courier<br>Symbol<br>ZapfDingbats |
| fontsize          | This attribute describes the size of the font when set as "solid". The font size corresponds to the em square, a concept used in typography. Note that certain glyphs may bleed outside their em squares. Some valid values are "xxsmall", "medium", "smaller" or a concrete size, e.g. "110%".   | Optional | 8pt<br>10pt<br>16pt                                     |
| fontstyle         | This attribute requests normal (sometimes referred to as "roman" or "upright"), italic, and oblique faces within a font family. Valid values are "normal", "italic" and "oblique".  | Optional | normal<br>italic<br>oblique                             |

|               |   |          |   |
|---------------|---|----------|---|
| fontvariant   | In a small-caps font, the glyphs for lowercase letters look similar to the uppercase ones, but in a smaller size and with slightly different proportions. The "font-variant" property requests such a font for bicameral (having two cases, as with Roman script). This property has no visible effect for scripts that are unicameral (having only one case, as with most of the world's writing systems). Valid values are "normal" and "small-caps". | Optional | normal<br>small-caps  |
| fontweight    | This attribute specifies the weight of the font. Some valid values are 'normal', 'bold', 'bolder', 'lighter', '100' or '900', where 'normal' is the same as '400', 'bold' is the same as '700'.   | Optional | normal<br>bold<br>100<br>200<br>300<br>400<br>500<br>600<br>700<br>800<br>900 |
| <b>Margin</b> |   |          |   |
| margin        | Sets the margin of a box. Negative values for margin properties are allowed, but there may be implementation-specific limits.   | Optional | 1pt<br>5pt<br>1mm<br>5mm  |
| margintop     | Sets the top margin of a box. Negative values for margin properties are allowed, but there may be implementation-specific limits.   | Optional | 1pt<br>5pt<br>1mm<br>5mm  |
| marginleft    | Sets the left margin of a box. Negative values for margin properties are allowed, but there may be implementation-specific limits.  | Optional | 1pt<br>5pt<br>1mm<br>5mm  |

|                |  |          |                          |
|----------------|--|----------|--------------------------|
| marginbottom   | Sets the bottom margin of a box. Negative values for margin properties are allowed, but there may be implementation-specific limits.                         | Optional | 1pt<br>5pt<br>1mm<br>5mm |
| marginright    | Sets the right margin of a box. Negative values for margin properties are allowed, but there may be implementation-specific limits.                          | Optional | 1pt<br>5pt<br>1mm<br>5mm |
| <b>Padding</b> |  |          |                          |
| padding        | Specifies the width of the padding of a block-area or inline-area. Unlike margin properties, values for padding properties cannot be negative.               | Optional | 1pt<br>5pt<br>1mm<br>5mm |
| paddingtop     | Specifies the width of the padding on the top of a block-area or inline-area. Unlike margin properties, values for padding properties cannot be negative.    | Optional | 1pt<br>5pt<br>1mm<br>5mm |
| paddingleft    | Specifies the width of the padding on the left of a block-area or inline-area. Unlike margin properties, values for padding properties cannot be negative.   | Optional | 1pt<br>5pt<br>1mm<br>5mm |
| paddingbottom  | Specifies the width of the padding on the bottom of a block-area or inline-area. Unlike margin properties, values for padding properties cannot be negative. | Optional | 1pt<br>5pt<br>1mm<br>5mm |
| paddingright   | Specifies the width of the padding on the right of a block-area or inline-area. Unlike margin properties, values for padding properties cannot be negative.  | Optional | 1pt<br>5pt<br>1mm<br>5mm |