

webMethods Unit Test Framework Help

Version 10.15

October 2022

This document applies to webMethods Test Suite 10.15 and to all subsequent releases.

Specifications contained herein are subject to change and these changes will be reported in subsequent release notes or new editions.

Copyright © 2017-2022 Software AG, Darmstadt, Germany and/or Software AG USA, Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <https://softwareag.com/licenses/>.

Use of this software is subject to adherence to Software AG's licensing conditions and terms. These terms are part of the product documentation, located at <https://softwareag.com/licenses/> and/or in the root installation directory of the licensed product(s).

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <https://softwareag.com/licenses/> and/or in the root installation directory of the licensed product(s).

Document ID: GWM-WWST-1015-20221015

Table of Contents

About this Guide	5
Document Conventions.....	6
Online Information and Support.....	6
Data Protection.....	7
1 Unit Test Framework	9
Overview.....	10
Terms and Concepts.....	10
Capabilities.....	13
Server Definition.....	14
Environment.....	14
What it is not.....	15
2 Working with Unit Test Framework	17
Opening the Unit Test Framework Perspective.....	18
Layout.....	18
Test Suite Preferences.....	19
3 Creating a Test Suite	23
Before You Begin.....	24
To Create a Test Suite.....	24
Creating a Sample Test Suite.....	24
4 Adding Test Cases	25
Adding a Test Case.....	26
Test Details.....	26
Service Details.....	26
Inputs.....	26
Expected Output.....	27
Output Comparison.....	27
5 Generating Tests	31
Generating Tests Suites using Service Execution Results.....	32
6 Mocks	35
Using Mocks.....	36
Sample Mock Factory.....	37
Mocks Beyond Unit Testing.....	38
7 Advanced Options	39
Pipeline Filter.....	40

Comparators.....	40
Client Mock Factory.....	40
XPath Expressions.....	41
8 Test Suite Internals.....	43
Test Suite Internals.....	44
9 Java Unit Tests.....	45
Java Unit Tests.....	46
10 Executing Tests.....	49
Executing Test Cases.....	50
Executing Test Suites.....	50
Debugging Java Code.....	50
Continuous Integration.....	51
11 Code Coverage Analysis.....	57
Running a Coverage Analysis.....	58
Viewing Code Coverage Analysis.....	59
Viewing Mock Event Details.....	60
Defining the Coverage Scope.....	61
Coverage Analysis in Headless Mode.....	62
12 Service Usage.....	63
WmServiceMock Services.....	64
WmServiceMock specification.....	65
References.....	66

About this Guide

- Document Conventions 6
- Online Information and Support 6
- Data Protection 7

This guide provides information on service testing options of Integration Server using webMethods Test Suite. The scope of this document is to introduce the suite, design and execute test cases.

It is assumed that the user is familiar with the standard build and test tools such as, Ant and JUnit.

Document Conventions

Convention	Description
Bold	Identifies elements on a screen.
Narrowfont	Identifies service names and locations in the format <i>folder.subfolder.service</i> , APIs, Java classes, methods, properties.
<i>Italic</i>	Identifies: Variables for which you must supply values specific to your own situation or environment. New terms the first time they occur in the text. References to other documentation sources.
Monospace font	Identifies: Text you must type in. Messages displayed by the system. Program code.
{ }	Indicates a set of choices from which you must choose one. Type only the information inside the curly braces. Do not type the { } symbols.
	Separates two mutually exclusive choices in a syntax line. Type one of these choices. Do not type the symbol.
[]	Indicates one or more options. Type only the information inside the square brackets. Do not type the [] symbols.
...	Indicates that you can type multiple options of the same type. Type only the information. Do not type the ellipsis (...).

Online Information and Support

Product Documentation

You can find the product documentation on our documentation website at <https://documentation.softwareag.com>.

In addition, you can also access the cloud product documentation via <https://www.softwareag.cloud>. Navigate to the desired product and then, depending on your solution, go to “Developer Center”, “User Center” or “Documentation”.

Product Training

You can find helpful product training material on our Learning Portal at <https://knowledge.softwareag.com>.

Tech Community

You can collaborate with Software AG experts on our Tech Community website at <https://techcommunity.softwareag.com>. From here you can, for example:

- Browse through our vast knowledge base.
- Ask questions and find answers in our discussion forums.
- Get the latest Software AG news and announcements.
- Explore our communities.
- Go to our public GitHub and Docker repositories at <https://github.com/softwareag> and <https://hub.docker.com/publishers/softwareag> and discover additional Software AG resources.

Product Support

Support for Software AG products is provided to licensed customers via our Empower Portal at <https://empower.softwareag.com>. Many services on this portal require that you have an account. If you do not yet have one, you can request it at <https://empower.softwareag.com/register>. Once you have an account, you can, for example:

- Download products, updates and fixes.
- Search the Knowledge Center for technical information and tips.
- Subscribe to early warnings and critical alerts.
- Open and update support incidents.
- Add product feature requests.

Data Protection

Software AG products provide functionality with respect to processing of personal data according to the EU General Data Protection Regulation (GDPR). Where applicable, appropriate steps are documented in the respective administration documentation.

1 Unit Test Framework

■ Overview	10
■ Terms and Concepts	10
■ Capabilities	13
■ Server Definition	14
■ Environment	14
■ What it is not	15

Overview

Test Suite is an Eclipse based testing tool that allows developers to create unit tests for their development. These tests improve the overall development quality and provide a mechanism to create automated tools for continuous integration and delivery.

Test Suite provides the following functionalities:

- Provides service unit testing and regression testing tools that allows service developers to assemble unit tests without the need for additional development
- Enables integration with JUnit to leverage a standard unit testing framework, which already works well with Continuous Integration tools
- Enables ease of use for test development
- Provides a Java API for advanced users to create JUnit test cases
- Provides a user interface that is integrated in Software AG Designer. Software AG Designer ensures that users do not switch between tools for services development and corresponding test cases
- Provides a mechanism to repeatedly execute the service with same inputs and compare the results with an expected set of outputs
- Provides a framework for mocking service execution for steps that cannot be executed during the testing. For details, see [“Using Mocks ” on page 36](#)

Terms and Concepts

This section provides information on the terms and concepts used to understand Test Suite.

Services

The webMethods Integration Server hosts packages that contain services and related files. The server contains several packages.

For example, Packages that contain built-in services, which can be invoked from services or client applications and services that demonstrate features of the webMethods Integration Platform.


You can create additional packages to hold the services that your developers create. Developers can create services that perform functions, such as, integrating your business systems with those of your partners, retrieving data from legacy systems, and accessing and updating databases.

Integration Server provides an environment for the orderly, efficient, and secure execution of services. It decodes client requests, identifies the requested services, invokes the services, passes data to them in the expected format, encodes the output produced by the services, and returns output to the clients.

Pipeline

Pipeline refers to the data structure in which input and output values are maintained for a flow service. It allows services in the flow to share data.

The pipeline holds the input and output for a flow service



Pipeline starts with the input to the flow service and collects inputs and outputs from subsequent services in the flow. The service in the flow has access to all data in the pipeline at that point.

Unit Testing

Test Suite uses the concepts of service execution, pipeline data, and the open source JUnit testing framework to provide unit testing functionality for Integration Server Flow and Java services. Test Suite provides the ability to create a suite of tests consisting of individual test cases. Each test case defines a service to be tested, the type of test to be performed, and provides a user interface to define input data to the test case through the pipeline. When the service execution is completed, the pipeline output is validated against the expected output defined in the test case.

Test Case

A test case is a unit of testing for a service that provides:

- service to be tested
- inputs to the service
- expected output from the service

A test case can also define expected output from a service as an exception or error. The service returns the defined errors when incorrect data is sent to it.

Test Suite

A test suite is one or more test cases grouped together. Test suites are used to organize test cases into sets of related tests. For example, a service may provide a variety of capabilities based upon the inputs provided to it. A complete test suite should include test cases that provide inputs that fully test all of the possible outputs of the service, including errors or exceptions.

Mock

Mocks provide a means of simulating interaction with resources that are unavailable or the data provided by these resources or systems is not consistent for test purposes. Mocks also have a lifetime that can either be limited to the test case in which they are defined or applied to all of the test cases that follow within a test suite from the point of the definition.

Mock intercept can control the session, user, and server based on the scope setting. If the scope is set to session, the test sessions will be affected by the mock. It is recommended to set the scope to session for most users. If the scope is set to user, all the sessions for the particular user will be affected by the mock. If the scope is set to server, all user sessions will be affected by the mock. Mocks can be enabled or disabled for test case or test suite execution.

Service Mock

A service mock is used to replace the call to a service with a call to a different service. Any call to the mocked service is intercepted and the alternate service defined in the mock is called instead. The output of the mocked service is then returned to the calling service. This kind of mock is useful

when the output of the mocked service needs to be dynamic based on some logic that can be created in the service.

Exception Mock

An exception mock is used to return an error or exception to the calling service and can be useful for testing error handling in a service. As with the other mocks described, any call to the service defined in the mock is intercepted and the exception defined in the mock is returned instead. This kind of mock is useful to simulate behavior that can cause exceptions in the normal flow.

Factory Mock

A factory mock is used when a call to a service produce multiple different outputs based on the provided input. A factory mock is implemented as a Java class. Any call to the class defined in a factory mock is intercepted and the input is passed to the factory which evaluates the input and returns the appropriate results. While both the factory mock and the service mock options provide dynamic output simulation, the factory mock does not require an extra test service to be created on the server and relies on a lightweight java implementation.

Capabilities

Test Suite has following capabilities:

- Unit testing
- Mock testing
- Regression testing
- Code coverage

Unit testing

Test Suite is a unit-testing tool. You can design, build, and execute unit test cases using Eclipse User Interface. You can also execute the test cases externally using Ant scripts.

Mock testing

Mocking is a feature that mimics the functionality of services that are dependent on external resources. When a test case encounters a service that is mocked, it executes the service.

Regression testing

You can save the test cases, along with their inputs and outputs, in xml files. Run the reusable artifacts to ensure that the latest changes do not reintroduce the errors fixed in the earlier versions.

Code coverage

Unit Test Framework records and analyzes the flow steps and map actions of your flow service(s) that are executed during a test launch. It helps you to identify the untested steps and improve the corresponding tests.

Server Definition

Integration Server preferences in Designer describe the connection to for Test Suite.

Designer always uses the active default Integration Server definition for Test Suite. Secure connection option in default server definition indicates whether the session will be opened through HTTP or HTTPS. In Designer, navigate to **Window > Preferences > Software AG > Integration Server** to add, edit, and update connection configurations. For details, refer the *webMethods Service Development Help*.

Unit Test Framework can also connect to a remote Integration Server through a proxy server. In Designer, navigate to **Window > Preferences > General > Network Connections** to provide the proxy server's settings.

The editor does not always require an active connection to the test development. But some of the introspection features that allow service lookup and service signature are not available if a connection is not available and so, the user should enter them manually.

Environment

Option	Description
Hardware Requirements	No additional hardware is required other than the ones that are already in use for Integration Server and Software AG Designer.
Software Requirements	<p>Developer Installation Requirements</p> <ul style="list-style-type: none">■ Unit Test Framework Eclipse plug-in (Designer > Services > Unit Test Framework)■ WmServiceMock package for Integration Server (Integration Server or Microservices Runtime Packages > Unit Test Framework) <p>Unit Test Framework Software AG Designer plug-in can work with both Local and Remote Integration Server.</p> <p>Continuous Integration Installation Requirements</p> <ul style="list-style-type: none">■ WmServiceMock package for Integration Server (Integration Server or Microservices Runtime Packages > Unit Test Framework)■ Unit Test Framework libraries (Infrastructure > Libraries > Unit Test Framework Libraries)

Option	Description
	<ul style="list-style-type: none">■ Ant Build tool 1.7 (optional)■ JDK 1.8 or later
Version Compatibilities	<p>This suite depends on open source products like Ant and JUnit.</p> <p>Following are the supported versions:</p> <ul style="list-style-type: none">■ Ant: 1.7■ JUnit: 4.11 <p>Unit Test Framework works with all the currently supported General Availability (GA) versions of Integration Server and Software AG Designer.</p>

What it is not

- Test Suite is not an integration or system test platform. However, this suite is used to mock the application dependencies and simulate the integration or system test.
- Test Suite is not a performance-testing tool. It cannot be used for performance, load, or volume testing.

2 Working with Unit Test Framework

■ Opening the Unit Test Framework Perspective	18
■ Layout	18
■ Test Suite Preferences	19

Opening the Unit Test Framework Perspective


Software AG Designer provides a Unit Test Framework perspective that contains the views, editors, and tabs needed to build test suites and other supporting elements.

1. In Designer, select **Windows > Open Perspective > Other**.
2. In the Open Perspective dialog box, select Unit Test Framework and click **OK**.

Designer switches to Unit Test Framework perspective.

Layout

The figure below shows various components of Software AG Designer with a test suite file open for editing.



Use the following icons on the toolbar to tailor the layout.

Icon	Description
	Allows you to place the Master and Details views next to each other, master on the right and details on the left.
	Allows you to make the master appear at the top of the display, and the details view gets aligned underneath it.
	Allows you to toggle the display between the master and details views, each occupying the entire display. Click again to return to the original layout .

Test Suite Preferences

To display the preferences dialog box, select **Window>Preferences>Software AG>webMethods TestSuite**.

Advanced

The Advanced preferences control other behaviors of Test Suite.

Preference	Description
Use Relative Paths in Filenames	Makes file name references relative to the Eclipse project containing the test suite rather than using the full path. Using relative names helps in executing tests when the test suite and data files are moved between environments and systems. This option is enabled by default.
Allow Comparator Configuration	Controls the display of the field that allows the selection of the comparator and does not allow/disallow this during execution.
Allow client side mock factory objects	Enables the option of creating client side factory object that do not need to be deployed on the server before executing test cases. This option controls the display of the field that controls whether the mock factory objects are needed on the server or can be pushed during the execution of the tests.
Display all fields in the expression editor	Enables additional fields in the Expected Output section of a test case. This option is useful if you want to check several output conditions together.
Allow editing of XML (Effective after reopen)	Enables editing of the XML source for the test suite. This option requires that the open test suite file is closed and reopened before its behavior reflects in the editor.
Allow scope selection for mocks	Enables scope selection for the mock. The default setting of unchecked is appropriate for most test case scenarios.
Confirm delete of single objects	Enables the display of a confirmation dialog box for every mock service or data entry delete.
Confirm delete of multiple objects	Enables the display of a confirmation dialog box when you delete multiple mock service or data entries.
Confirm service paste	Enables the display of a confirmation dialog box when you paste a test services.

Code Coverage

The advanced code coverage preferences controls the behaviors of code coverage execution in Test Suite.

Preference	Description
Include Execution Model Report in Code Coverage Execution	Generates an additional Execution Model report during code coverage execution in Test Suite.
Include Service Level Coverage Report in Code Coverage Execution	Generates an additional Service Level Coverage report during code coverage execution in Test Suite.
Include Launch Code Coverage Execution in Debug Mode	Enables you to debug a Java code during the code coverage execution in Test Suite.

License

The License preferences provide the license related information of Test Suite.

Preference	Description
License file	Allows you to select the license file for Test Suite.
Check License	Allows you to check the validity of the license file.

Editor

The Editor preference allows you to list the packages to load to the service browser. connection to webMethods Integration Server.

Preference	Description
Package Filter	Optional. Allows you to optionally enter a comma-separated list of packages for Test Suite to load to the service browser. When a large number of packages exist on the Integration Server, this feature loads only those services for which test cases are developed and thereby conserves memory in Test Suite.

Validation

The Validation preferences describe when and how Test Suite should validate the information that you enter.

Preference	Description
Validate on Save	Allows Test Suite to validate the test suite prior to saving it to the file system. This option is enabled by default.
Validate before switching mode	Allows Test Suite to perform validation of the test suite prior to switching from the XML editor mode to the test suite editor.
Validate against schema	Allows Test Suite to validate the test suite against the XML schema. This is useful if you use the XML Source tab to enter details of one or more test cases in the suite. This option is enabled by default.

3 Creating a Test Suite

- Before You Begin 24
- To Create a Test Suite 24
- Creating a Sample Test Suite 24

Before You Begin

Before creating a test suite, ensure that you organize the required test cases and data files in a test folder.

If the test cases are packaged in the Integration Server package, it provides a common source location for all related assets. You can import the package on eclipse workspace.

Example: Consider that the test cases are created in the resources test folder of the Integration Server package.

While any organizational structure that conforms to Integration Server package structure can be used, the following example provides a useful approach for organizing test cases in your environment. For ease of organization, follow the steps below:

1. Right click the **resources** directory and create a subdirectory under it called **test**.
2. Right-click the **test** directory and create two additional folders **data** and **setup**.
3. Add the test suites to the **setup** directory and organize the **data** directory using subdirectories for each test suite to contain the input data files for the test cases comprising a test suite.

To Create a Test Suite

Follow the below steps to create a test suite:

1. Navigate to **resources > test > setup** folder.
2. Select **File > New > Test Suite**.
3. On the **webMethods TestSuite** screen, enter the folder path that contains the test suite setup files, provide a file name, and a suite name.
4. Click **Finish**.

You can now start creating the test cases.

Creating a Sample Test Suite

Designer allows you to create sample Test Suite projects.

1. Select **File > New > Test Suite Example**.
2. On the **Sample wmTestSuite Project** screen, enter the project name and location. You can choose to use the default values.

This Test Suite familiarises you on building test cases.

4 Adding Test Cases

- Adding a Test Case 26
- Test Details 26
- Service Details 26
- Inputs 26
- Expected Output 27
- Output Comparison 27

Adding a Test Case

Adding a test case involves the following steps:

1. Adding required test details. See [“Test Details” on page 26](#).
2. Adding the required service details. See [“Service Details” on page 26](#).
3. Defining inputs to services. See [“Inputs” on page 26](#).
4. Defining the expected output. See [“Expected Output” on page 27](#).

Test Details

To add test cases:

- Right click on the **webMethods Test Suite** section.

The **Test Details** section appears in the details area to the right side of the display. Provide a name and description for the test case.

Service Details

After creating the test details, you can now select the service to be tested.

1. Click **Browse** in the Service Details section to enable searching for the service within the Integration Server.

Note:

You can narrow the search by entering a package name or service name and the service browser will restrict the display to only those packages or services matching the search criteria entered.

2. Click ▾ to refresh or set additional options for service browser.

Inputs

Test Suite looks at the *service signature* for services in Integration Server. You can perform the following operations while defining the inputs to the service selected in [“Service Details” on page 26](#).

- Click **Edit** to modify the values of the input parameters and click OK to save the changes.
 - Click **Save...** to save the file in the location designated for the input data after defining the input.
 - Click **Load** to import a saved input data.

- Click **Browse** to add a saved file as the input to the service.




Expected Output

The final step in defining a test case is to complete the Expected Output section. Expected Output can be in the form of data returned from the service or an exception returned from the service.

Use the class browser to define an exception or error output from the service. Click **Browse** to display the classes and select the proper exception class to use.

To define the data output from the service, use the following methods:

- Use XPath expressions to define which data elements in the output data should be evaluated.
 1. Copy the XPath expressions from Software AG Designer. To copy the XPath expression, right click on the variable in the **Results** area when executing the service within Software AG Designer and select **Copy**.

2. Click , , or  and paste the copied value into the XPath field.

An entry for the variable selected is created. However, in most cases it is not required to edit them as the webMethods paths are 0 index based whereas XPath expressions are 1 index based.

3. Enter the expected output for the field in the **Value** field.

You can select AND, OR, parentheses, and operators from the drop-down lists to create complex evaluations of the output.

- Use regular expressions to evaluate the output returned from the service. The regular expression should be placed in the Value field preceded and followed by "/" character.




Output Comparison

Unit Test Framework allows you to select predefined or customize the output comparison to compare service results and check the destination table to confirm the operation executed successfully.

Note:

By default, the Output Comparison section appears on the webMethods Test Suite screen. To hide the section, go to **Window > Preferences > Software AG > webMethods TestSuite > Advanced**, and clear the **Allow Comparator Configuration** check box.

1. On the Output Comparison section, select **Comparator Type**.
2. Select one of the following options:

Select...	To...
Default	Compare the actual and expected service result without any filter.
Ignore Namespace Prefix	Ignore the namespace prefix from the service results. For example, for a field value <code>demotest:employee</code> in the actual result, where <code>demotest</code> is the namespace prefix, Unit Test Framework ignores the namespace and uses <code>employee</code> for comparison.
Use Field Alias	Specify which fields in the service result should be compared. You have to provide a field alias for the field in the actual result that you want to Unit Test Framework to compare against in the expected output. For example, for a field value <code>demotest:employee</code> in the actual result, you can assign a <code>1002</code> as the field alias. Then, Unit Test Framework uses <code>1002</code> instead of <code>demotest:employee</code> for comparison. Click  to add the list of fields to compare. Click  , or  to edit or delete the entries.
Custom	Specify a custom comparator for expected output other than provided with the plug-in.
Custom Service	Overrides the default comparator in webMethods Test Suite with an Integration Server service that has a custom assertion logic.

Field	Description
Comparator Service	Select an Integration Server service that implements the custom assertion logic for an output comparison. The service signature must conform to the <code>wm.spec:result_comparator</code> specification in the <code>WmServiceMock</code> package. You can import the specification directly into the service or replicate it manually in the Integration Server service. For more information on the specification, see “WmServiceMock specification” on page 65 .

Implement the custom service to suit your testing requirements. If you select a custom service as the comparator, the outcome of the comparison between the actual and expected test results is determined by the assertion logic in the custom service chosen.

Select...**To...**

The custom service supports only the "file" type selected in the Expected Output section for comparison. However, providing a file is optional. If no file is selected, the comparator service receives "null" data for comparison.


Note:

If you define the expected outcome as XPath fields and Values, the comparator service ignores such "fields" during comparison.

5 Generating Tests

- [Generating Tests Suites using Service Execution Results](#) 32

Generating Tests Suites using Service Execution Results


Test Suite allows you to generate tests from the details of recently run services present in the Result view. Using the Generate Test icon  on the Results view, you can export the available service invoke or run details to form a unit test and save in a Test Suite.

Ensure that you have installed the Test Suite Designer plugin.

1. In the Service Development perspective, navigate to the **Results** view of recently run services and select the service for which you want to generate a test.

Note:

For details on viewing the Results view, see the *Software AG Designer Online Help*.

2. Click .
3. In the Export Pipeline dialog box, provide the following details and click **Finish**.

Type	Function
Container	<p>Specifies the project or directory location of the Test Suite.</p> <p>Ensure that you use an organizational structure that conforms to Integration Server package structure.</p> <p>Ensure that the specified project exists in the workspace.</p>
TestSuite	<p>Specifies the name of the TestSuite file.</p> <p>Use Overwrite to rebuild the Test Suite. This overwrites the existing Test Suite.</p> <p>Use Append to append to the existing Test Suite.</p> <p>Note: Ensure that you provide the filename with the extension. For example, <i>wmTestSuite.xml</i>.</p>
Input	<p>Specifies the service input file location.</p> <p>Note: You can choose to retain the default value.</p>
Output	<p>Specifies the expected output file location.</p> <p>Note: You can choose to retain the default value.</p>

The Test Suite is created at the specified location.

4. Double click the newly created Test Suite.

The test details are displayed. You can edit the test details. To edit the test details, see [“Adding a Test Case”](#) on page 26.

6 Mocks

■ Using Mocks	36
■ Sample Mock Factory	37
■ Mocks Beyond Unit Testing	38

Using Mocks

Mocks are used when resources that a service may require to properly execute may not be available when a test case or test suite is developed or executed. Mocks provide a means of simulating interaction with resources that are unavailable.

> To create a mock

1. Expand the test case for which you want to define the mock, right click on **Mocks** and select **Add**.
2. Click **Browse** and use the **Service Browser** to select the service to be mocked.
3. Enter the first few characters of the service name to reduce the list. Click to refresh the list and access preferences for the **Service Browser**.
4. Select the required **Lifetime**.

Valid selections are **test** (mock is effective only for the selected test case) and **suite** (mock will be effective for all of the test cases that follow in the test suite).

5. Select the required **Type**.

Following are the valid selections:

Type	Function
pipeline	Intercepts the service and returns the specified pipeline (for details on creating or editing pipeline data see “Inputs” on page 26).
service	Intercepts the service and substitutes the selected service with a call (for details on working with the Service Browser, see “Service Details” on page 26).
exception	Intercepts the service and returns an exception (for details on selecting exception classes, see “Expected Output” on page 27).
factory	Intercepts a call to the mocked service and returns the data based on the input (for details on creating a mock factory, see “Sample Mock Factory” on page 37).

6. Select the scope.

It is recommended to use the **session** scope for most purposes. To allow the scope selection, select the corresponding preference.

Sample Mock Factory

The following code snippet illustrates the minimum requirements for creating a mock factory. The factory class and any other classes should be designed to evaluate the input data to the factory and return data relevant to that input in an IData format. The example below returns static data.

```

package com.wm.ps.serviceMock.samples;
import com.wm.app.b2b.server.BaseService;
import com.wm.app.b2b.server.invoke.ServiceStatus;
import com.wm.data.IData;
import com.wm.data.IDataFactory;
import com.wm.ps.serviceMock.MockDataFactory;
public class SampleMockDataFactory implements MockDataFactory
{
    private static final long serialVersionUID = 2L;

    public IData createData(BaseService baseService, IData pipeline,
        ServiceStatus serviceStatus)
    {
        IData[] results = new IData[]{IDataFactory.create(new Object[][]{
            {"originationSource","W"},
            {"bizType","RT"},
            {"lockExpirationDate","20050427"},
            {"floatLoanIndicator","Y"},
            {"uwFinalDecisionCode","0"},
            {"uwDecisionExpiryDate","20050427"},
            {"canDate","20050427"},
            {"loanCloseStatusType","T"},
            {"fileReceivedAtRocDate","20050221"},
            {"loanReadyToFundIndicator","P"},
            {"regisDate","20051221"},
            {"loanSubmitToUwDate","20050427"},
            {"loanNumber","0000000001"},
            {"branch","TOTAL ADVANTEDGE LLC          "},
            {"underwritingDecisionCode","0"},
            {"underwritingDecisionExpirationDate","20050427"},
            {"lockDate","20051220"},
            {"lockIndicator","Y"},
            {"tmoLoanStageCode","3"},
            {"tmoLoanStageDate","20050427"},
            {"product","C30          "},
            {"borrowerFirstName",".          "},
            {"borrowerLastName","XX          "},
            {"propertyAddress","937 S MEYER          "},
            {"propertyCity","TUCSON          "},
            {"propertyState","AZ"},
            {"propertyZip","85701"}
        })};

        IData output = IDataFactory.create(new Object[][]{{"results", results}});
        return IDataFactory.create(new Object[][]{{"getPotentialDuplicatesOutput",
            output}});
    }
}

```

Mocks Beyond Unit Testing

Although Test Suite added the ability to mock service calls in Integration Server for unit testing, the feature is so powerful that its use cannot be limited to unit testing alone. One common case is to use the mocking capability to provide flow service instrumentation.

Using the `wm.ps.serviceMock:loadMock` service in the `WmServiceMock` package, any service can be mocked with an alternate service or class. The new service or Java class code can invoke any operations and then invoke the original mocked service. The mocking framework is intelligent enough to detect recursion and, as such, provides an instrumentation capability.

Mocks can be used to design test cases. A service being tested can also itself be mocked with other code. In such a scenario, the mocked test service can be replaced with other code that can execute pre and post-test operations. This can provide some basic functional testing capabilities for Test Suite.

7 Advanced Options

■ Pipeline Filter	40
■ Comparators	40
■ Client Mock Factory	40
■ XPath Expressions	41

Pipeline Filter

The execution of test cases is initiated as a client to the Integration Server hosting the services to be tested. For this reason, the inputs supplied to the service during execution and the expected outputs need to be serialized over the client-server interaction. If the input or output pipeline contains non-serializable objects, these objects are either lost or seen incorrectly during test execution. In addition, the service input needs to be more dynamic in nature than the static pipeline setup in the test case. Pipeline Filter helps to resolve these issues.

The Pipeline Filter is set once for the entire suite and provides a callback mechanism for the test developer to inject code that can modify various pipeline objects during execution. The Pipeline Filter is a class that implements the `com.wm.ps.test.PipelineFilter` interface and enables a user to add, remove, or change variables in the pipeline that are created from files, as pipelines created from files may not be able to persist custom java objects. The output pipeline from a service can also be filtered using the appropriate method. Only one such instance of the implementing class is created for the test suite and the name of test case is passed as a parameter.

The pipeline filter can be setup for the test suite in the main panel for the suite parameters.

Comparators

Comparator provides an extension that can be used to extend, enhance, or replace the standard comparison of expected output.

Each test suite can have its comparator that can be specified from the user interface.

"Custom" comparator type are Java classes that implement the `com.wm.ps.test.ResultsValidator` interface. This also provides a mechanism to execute operations pre and post service execution.

The "Custom Service" comparator type allows you to select an Integration Server service that has an assertion logic for the test. The service signature must conform to the `wm.spec:result_comparator` specification.

Using "Custom" and "Custom Service" comparator types, you can build some basic functional testing capability. For example, if a service writes to a database table, a comparator can compare the results from the service and check the destination table to confirm the operation executed successfully. You can also specify filters while comparing.

Client Mock Factory

The benefit of using a mock factory object as opposed to a service is that it provides a light-weight alternative that does not require the creation of a new service on the server.

Test Suite provides an option to dynamically push the classes needed for supporting the mock factory on the server during test execution. This option can be used to avoid the need for frequent restart when Java objects are changing. Once stabilized, it would be helpful to deploy the code to the server as this feature is experimental in nature and will only work if the dependency tree is not too complex. Using the user interface, you can set the option to dynamically push the objects to the server.

If the option is disabled, enable the corresponding preference as discussed in the Advanced section.

webMethods expression	JXPath equivalent
PosRequest/ns:Log/ns:Transaction[0]/@Flag	PosRequest[@name='ns:Log'] [@name='ns:Transaction'][1][@name='@Flag']
PosRequest/ns:Log/ns:Transaction[0]/ns:BUnit[0]/ns:ID/*body	PosRequest[@name='ns:Log'] [@name='ns:Transaction'][1][@name='ns:BUnit'] [1][@name='ns:ID'][@name='*body']

XPath Expressions

The XPath expressions used in the expected output panel are different from the usual webMethods path expressions. As mentioned in the “[Expected Output](#)” on page 27 section, the indices start at 1 instead of the 0 based webMethods indices.

Test Suite uses JXPath for evaluating XPath expressions. For details on JXPath expressions, visit <http://commons.apache.org/jxpath/>. Special characters such as '@' and ':' in the name have special meaning in JXPath expressions hence, you should use special syntax variant to use these characters in variable name.

8 Test Suite Internals

■ Test Suite Internals	44
------------------------------	----

Test Suite Internals

In Software AG Designer, test suite editor provides a user interface to graphically and quickly develop test cases for Integration Server services. The test suite and the test cases are saved in an XML file. The Software AG Designer editor allows editing the XML source directly, provided that the user is aware of the format and the associated schema.

It is not recommended to edit the XML file as it is error-prone. It provides the option to automate the creation of test cases automatically by using code to generate the XML file directly. One such use case is the scenario where service inputs and outputs have been captured in an environment and test cases have to be generated to use these files for regression testing.

A sample XML test suite file in its simplified form can be as shown in the figure below:

```
<?xml version="1.0" encoding="UTF-8"?>
<webMethodsTestSuite description=
"Sample tests for the WmServiceMockSamples implementation" name="Sample Tests">
  <webMethodsTestCase description=
"Duplicate Check Success with IData results" name="Duplicate Check Success
With Results">
  <mock folder="wmServiceMockSamples.data.services"
name="getPotentialDuplicates">
    <pipeline filename="resources/test/data/
mockDupCheckOutputResults.xml"/>
  </mock>
  <service folder="wmServiceMockSamples.services" name="getDuplicateLoans">
    <input>
      <file filename="resources/test/data/dupCheckInput.xml"/>
    </input>
    <expected>
      <file filename="resources/test/data/
dupCheckSuccessWithResults.xml"/>
    </expected>
  </service>
</webMethodsTestCase>
  <webMethodsTestCase description=
"Duplicate Check Failure handled by the catch block" name="Duplicate Check
Catch Block">
    <mock folder="wmServiceMockSamples.data.services"
name="getPotentes">
      <exception class="java.lang.IllegalArgumentException"
message="Bad argument"/>
    </mock>
    <service folder="wmServiceMockSamples.services" name="getDuplicateLoans">
      <input>
        <file filename="resources/test/data/dupCheckInput.xml"/>
      </input>
      <expected>
        <exception class="java.lang.IllegalArgumentException"
message="Bad argument"/>
      </expected>
    </service>
  </webMethodsTestCase>
</webMethodsTestSuite>
```

9 Java Unit Tests

■ Java Unit Tests	46
-------------------------	----

Java Unit Tests

Test Suite Java API allows you to create JUnit test cases that provide the same features as user interface-driven codeless test cases.

The change when creating a Test Suite JUnit test case from the traditional test case is that the implementing class extends `com.wm.ps.test.WmTestCase` instead of `junit.framework.TestCase`. `com.wm.ps.test.WmTestCase` does extend the `junit.framework.TestCase`. The two important methods that are needed for creating test cases using the java API are:

- `invokeService` – The method to invoke a service on the server.
- `mockService` – There are various variants of this method that allow the user to setup a mock for a service on the server.

A sample JUnit test case is provided here:

```
package com.wm.ps.serviceMock.samples;
import com.wm.data.*;
import com.wm.ps.test.*;
public class DuplicateCheckTest extends WmTestCase
{
    public void testDupCheckCatchBlock() throws Exception
    {
        IData input = IDataFactory.create(new Object[][]{
            {"lienType", "1"},
            {"borrowerSSN", "111-11-1111"},
            {"propertyAddress", "937 S Meyer"},
            {"propertyZip", "85701"}
        });

        String exceptionText = "Bad argument";
        mockService("wmServiceMockSamples.data.services",
            "getPotentialDuplicates", new
            IllegalArgumentException(exceptionText));
        try
        {
            invokeService("wmServiceMockSamples.services",
                "getDuplicateLoans", input);
            assertFalse(true); //Control getting here means failure
        }
        catch (Exception e)
        {
            assertTrue(e.getMessage().endsWith(exceptionText));
        }
    }
    public void testDupCheckSucessWithResults() throws Exception
    {
        IData input = IDataFactory.create(new Object[][]{
            {"lienType", "1"},
            {"borrowerSSN", "111-11-1111"},
            {"propertyAddress", "937 S Meyer"},
            {"propertyZip", "85701"}
        });

        IData mockOutput =
        WmTestSuiteUtils.getIDataFromFile("resources/test/data/
```

```
mockDupCheckOutputResults.xml");
    mockService("wmServiceMockSamples.data.services", "getPotentialDuplicates",
        mockOutput);
    IData output = invokeService("wmServiceMockSamples.services",
        "getDuplicateLoans",
        input);
    IDataCursor outCursor = output.getCursor();
    IData response = IDataUtil.getIData(outCursor, "response");
    IDataCursor responseCursor = response.getCursor();
    String creationTime = IDataUtil.getString(responseCursor, "@creationTime");
    assertNotNull(creationTime);
    assertEquals(28, creationTime.length());
    IData[] duplicateLoans = IDataUtil.getIDataArray(responseCursor,
        "duplicateLoans");
    assertEquals(duplicateLoans.length, 1);
}
}
```


10 Executing Tests

■ Executing Test Cases	50
■ Executing Test Suites	50
■ Debugging Java Code	50
■ Continuous Integration	51

Executing Test Cases

To execute test cases created with Test Suite, right click in the webMethods Tests section and select one of the following options:

- **Run Tests** - executes the selected test case, using the mocks that are defined for the test case.
- **Run Test with Mocks Disabled** - executes the selected test case by disabling the mocks defined for the test case.
- **Disable Test** - marks test case as disabled. Tests are not executed until it is enabled again.
- **Disable Mocking in Tests** - marks mocks defined for selected test as disabled. Mocks are not executed until they are enabled again.
- **Add** - adds another test case to the suite.
- **Insert** - inserts another test case to the suite after the selected test case.
- **Remove** - removes the selected test case from the suite.

Executing Test Suites

To execute test suites created using Test Suite, right click in the webMethods Tests section and select one of the following options:

- **Run Suite** - executes the selected test suite, using the mocks that are defined for the test suite.
- **Run Suite with Mocks Disabled** - executes the selected test suite by disabling the mocks de-fined for the test suite.
- **Disable Suite** - marks test suite as disabled. The test suite is not executed until it is enabled again.
- **Disable Mocking in Suite** - marks mocks defined for this suite as disabled. Mocks are not executed until they are enabled again.
- **Shift Up or Shift Down** - changes the order of test cases in the test suite by shifting the selected test case up or down in the test suite.

Debugging Java Code

Various components in Test Suite rely on Java code.

Example: Java mock factory and pipeline filter classes.

Use the **Debug** menu to debug a Java code. The support library jar files also have source code associated with them. Debugging into the source can be helpful to understand the internals of the test execution or to enhance capabilities new features like custom comparators.

Continuous Integration

Software AG Designer allows you to create a Test Suite Executor project which provides a default *Ant* script (`run-composite-runner.xml`) to start with continuous integration setup. When you execute the *Ant* script, it invokes the Test Suite projects in headless mode. After the successful execution, the script generates the test reports and code coverage reports. You can use the *Jenkins JUnit* and *HTML Publisher* plugins to view these reports in *Jenkins*.

Creating a Test Suite Executor

Software AG Designer allows you to create *Test Suite Executor* projects and execute tests in headless mode.

Perform the following steps to create a sample *Test Suite Executor* project using the default files.

1. Select **File > New > Test Suite Executor**.
2. On the **Test Suite Executor Project** screen, enter the project name, folder path that contains the test suite setup files, and the file system. You can choose to use the default values.
3. Click **Finish**.

Project contains default Ant build targets and properties to drive the tests.

Configuring a Test Suite Executor

Software AG Designer allows you to configure a *Test Suite Executor* project after you have successfully created it.

Perform the following steps to configure a sample *Test Suite* using the default files.

1. To initiate the tests, use the ant build file, `run-composite-runner.xml` and ant target, `composite-runner-all-tests`.
2. Modify the properties file, `run-test-suites.properties` to specify project locations and setting up target Integration Server definition.
3. Specify the following properties in the `run-test-suites.properties` file.

Server Information

Name	Description
<code>webMethods.integrationServer.name</code>	Specifies the Integration Server host name. For example: localhost, 127.0.0.1
<code>webMethods.integrationServer.port</code>	Specifies the Integration Server port.

Name	Description
<code>webMethods.integrationServer.userid</code>	For example: 5555 Specifies the Integration Server user name. For example: Administrator, Developer
<code>webMethods.integrationServer.password</code>	Specifies the Integration Server user password. For example: manage
<code>webMethods.integrationServer.ssl</code>	Specifies the Integration Server port uses SSL connection or normal. For example: false or true
<code>watt.net.proxyHost</code>	Specifies the hostname or the IP address of a proxy server. For example: <code>watt.net.proxyHost=webcache.example.com</code>
<code>watt.net.proxyPort</code>	Specifies the port number of the proxy server. The default value is 80. For example: <code>watt.net.proxyPort=8080</code>
<code>watt.net.proxyUser</code>	Specifies the name of a user account on the proxy server.
<code>watt.net.proxyPass</code>	Specifies the password for the username set using <code>watt.net.proxyUser</code> .
<code>watt.net.secureProxyHost</code>	Specifies the hostname or the IP address of the proxy server to be used in SSL connections. For example: <code>watt.net.secureProxyHost=webcache.example.com</code>
<code>watt.net.secureProxyPort</code>	Specifies the port number of a proxy server to be used in SSL connections. For example: <code>watt.net.secureProxyPort=443</code>
<code>watt.net.secureProxyUser</code>	Specifies the name of a user account on the proxy server.
<code>watt.net.secureProxyPass</code>	Specifies the password for the username set using <code>watt.net.secureProxyUser</code> .
<code>http.nonProxyHosts</code>	Specifies the list of hosts that should be accessed directly, bypassing the proxy. This

Name	Description
	<p>is a pattern separated by ' ' character, which can also have * for wildcards.</p> <p>Any host matching one of these patterns is accessed through direct connection, bypassing the proxy.</p> <p>For example: <code>http.nonProxyHosts=".foo.com localhost 127.* [:1]"</code> indicates that every host in the foo.com domain and localhost should be accessed directly even if a proxy server is specified.</p>

Project Information

Name	Description
<code>webMethods.home</code>	<p>Specifies the product installation location.</p> <p>For example: <code>C:\SoftwareAG</code></p>
<code>webMethods.test.setup.location</code>	<p>Specifies multiple project locations (absolute directory path) in</p> <p><code>\$AbsolutePathLocation1,\</code> <code>\$AbsolutePathLocation2,\</code> <code>\$AbsolutePathLocation3</code></p> <p>format. In this case, a <i>Test Suite Executor</i> searches for all available and valid <i>Test Suite</i> files in these directories.</p> <p>For example:</p> <p><code>C:/SoftwareAG/IntegrationServer/instances/default/packages/SampleTestSuite,\,</code> <code>C:/_gitRepo/packages/SampleTestSuite1</code></p> <p>It executes specific and multiple <i>Test Suite</i> files by specifying it in the following format:</p> <p><code>\$AbsolutePathLocation1;</code> <code>\$RelativeTestSuitePath1,\</code> <code>\$AbsolutePathLocation2;</code> <code>\$RelativeTestSuitePath2</code></p>

Name	Description
<code>webMethods.test.setup.external.classpath.layout</code>	<p>For example :</p> <pre>C:/SoftwareAG/IntegrationServer/instances/default/packages/SampleTestSuite;resources/test/setup/wmTestSuite.xml,\ C:/_gitRepo/packages/SampleTestSuite1;resources/test/setup/wmTestSuite.xml</pre> <p>Specifies the relative paths within the projects where the required classes or jar files are expected to be present in a <i>Test Suite Executor</i> project build-classpath. For example, when third-party libraries or Mockfactory classes are referred from the Tests, specify the locations where these are stored at, so that executor can load these dependencies during headless tests. Append the default comma separated list if required.</p> <p>Default value:</p> <pre>resources/test/classes,resources/java/classes,resources/test/jars,resources/java/jars,resources/jars</pre>
<code>webMethods.test.profile.result.location</code>	<p>Specifies the absolute directory location where the reports are stored.</p> <p>For example:</p> <pre>C:/git_sources/GitRepo3/WmTestSuiteExecutor/test/reports/</pre>

Note:

Alternatively, you can also use the ant build file `run-test-suites.xml` and target `runall-test`. Test Suite Executor cleans and builds the projects included in target `runall-test`, then searches for the TestSuites and executes. List of projects can be included within `runall-test` target (under `dirset` contents). Reports are generated at the following default location: `$basedir/test/reports`. To use `runall-test`, the test projects or packages has to conform to the default project layout. Refer to the `SampleTestSuite` for the default project layout.

Important:

It is recommended not to customize the code coverage report resources and the Ant build file artifacts of the *Test Suite Executor* project directly, Instead:

- Import the available Ant targets in use to any new Ant build files and reuse them, which prevents any conflicts during the migration of the *Test Suite Executor* project artifacts to the latest fixes or new releases.
- Keep the *Test Suite Executor* artifacts in sync with the fix or release version of the product in use to avoid compatibility issues.
- Recreate the *Test Suite Executor* project in Designer, which distributes compatible resources.

View JUnit Test Results and Code Coverage Reports

When you execute the *Ant* script (`run-composite-runner.xml`) from the Test Suite Executor project, the build process generates the *JUnit* reports and code coverage reports. You can find these reports in the folder defined by the `webMethods.test.profile.result.location` property in the `run-test-suites.properties` file.

View JUnit reports

The *Ant* script invokes the headless test execution build which generates *JUnit* reports in XML and HTML formats.

When the JUnit report is...	Then...
XML	<p>The <i>Ant</i> script invokes the headless test execution build which generates the XML report in the location as defined by the <code>webMethods.test.profile.result.location</code> property in the <code>run-test-suites.properties</code> file.</p> <p>Use the <i>JUnit</i> test report extension of your continuous integration tool to view the test report. For example, the <i>Jenkins JUnit</i> plugin. This plugin provides a graphical representation of the historical test results and a web interface to view test reports and track failures.</p>
HTML	<p>The <i>Ant</i> script invokes the headless test execution build which creates the <code>html</code> folder containing a HTML report. The build process creates the <code>html</code> folder in the location as defined by the <code>webMethods.test.profile.result.location</code> property in the <code>run-test-suites.properties</code> file.</p> <p>Use a plugin supported by your continuous integration tool to publish the test report. For example, the <i>Jenkins HTML Publisher</i>.</p>

View code coverage report

The *Ant* script invokes the headless test execution build which generates the code coverage report when the `webMethods.test.setup.profile.mode` property is set to **Coverage** in the `run-test-suites.properties` file.

The build process generates the *wmcodecoverage* folder in the same location as defined by the `webMethods.test.profile.result.location` property in the `run-test-suites.properties` file and saves the code coverage report inside the *wmcodecoverage* folder.

To publish the code coverage report, you can use a plugin supported by your continuous integration tool. For example, the *Jenkins HTML Publisher*. You can use any supported application server to view the code coverage reports in your web browser. For example, NodeJs or Tomcat. To view the report, you must copy the *wmcodecoverage* folder to the application server.

11 Code Coverage Analysis

■ Running a Coverage Analysis	58
■ Viewing Code Coverage Analysis	59
■ Viewing Mock Event Details	60
■ Defining the Coverage Scope	61
■ Coverage Analysis in Headless Mode	62

Running a Coverage Analysis

Unit Test Framework allows you to record and analyze which flow steps and map actions of your flow service(s) are executed during a particular test launch. It helps to identify untested steps and improve the corresponding tests.

Pre-requisites:

Before running the test coverage analysis, activate the wM Code Coverage Agent. You can activate the wM Code Coverage Agent either through Designer or Integration Server startup script or Microservices Runtime startup script.

■ Through Designer

Perform one of the following steps to activate the wM Code Coverage Agent:

- On the Package Navigator, right-click the default Integration Server instance, and select **wM Code Coverage Agent > Activate**.

OR

1. In Designer, navigate to **Window > Preferences > Software AG > Integration Server**, and select the default server.
2. Click **wM Code Coverage Agent**.
3. On the wM Code Coverage Agent Settings dialog, select **Activate**.

■ Through the Integration Server startup script or Microservices Runtime startup script.

Perform one of the following steps to activate the wM Code Coverage Agent:

■ Integration Server

- If Integration Server launches using the Tanuki Java service wrapper in the startup script, configure the Java agent in `custom_wrapper.cnf` as follows:

```
wrapper.java.additional.400=-javaagent:$IntegrationServer_packages_location/WmServiceMock/resources/int=utf-agent.jar=log=level=INFO.
```

Replace `$IntegrationServer_packages_location` with the absolute path of Integration Server packages.

Note:

Software AG recommends that any new custom properties added to `custom_wrapper.conf` be assigned a number of 400 or higher to prevent conflicts with properties added by Software AG.

- If Integration Server launches without using a wrapper, configure the Java agent settings in the `Integration Server_directory/bin/setenv.bat(sh)` file as follows:

```
JAVA_OPTS="-javaagent: $IntegrationServer_packages_location /WmServiceMock/resources/int=utf-agent.jar=log=level=INFO".
```

Replace `$IntegrationServer_packages_location` with the absolute path of Integration Server packages.

- **Microservices Runtime**

If Microservices Runtime launches using the startup script, configure the Java agent settings in the `Integration Server_directory/bin/setenv.bat(sh)` file as follows:

- `PROFILER_ENABLED=false`
- `JAVA_PROFILER_OPTS="-javaagent: $IntegrationServer_packages_location /WmServiceMock/resources/int/utf-agent.jar=log=level=INFO"`.

Replace `$IntegrationServer_packages_location` with the absolute path of Integration Server packages.

➤ **To run a test coverage analysis**

1. In the webMethods Tests section, right click and select **wM Code Coverage Tools**.
2. Select one of the following:
 - **Run Suite**: executes the selected test suite.
 - **Run Suite with Mocks disabled**: executes the selected test suite with Mocks disabled.
 - **Run Tests**: executes the selected test case.
 - **Run Tests with Mocks disabled**: executes the selected test case with Mocks disabled.

The test or suite coverage analysis appear as a graphical data under the **wM Code Coverage** view.

You can generate code coverage reports using the default maximum memory size specified in Integration Server. This report effectively handles the Test Suite containing more number of lines of code and test cases for a service. If a service comprises an exceptionally high number of lines of code or tests executed in a single test execution session, Integration Server must upgrade the default maximum memory size.

Viewing Code Coverage Analysis

After you run the test, wM Code Coverage view displays a detailed coverage report of the test session.

The tested flow steps and map actions or Services appear in green and the untested flow steps and map actions appear in red.

➤ **To view the code coverage analysis**

1. On the **wM Code Coverage** view, perform one of the following:

Click...	To..
Full Packages View	Represent elements under the corresponding Packages and Service namespace. This view provides detailed coverage analysis of the flow steps and map actions of all the individual service(s) under test in the test suite.
Service Level View	Represent only Invoked Services as elements under corresponding Packages. This view provides the coverage analysis of only the services invoked during the test case or test suite execution.
Execution Model View	Represents the complete execution hierarchy details of the service under test in the Test Suite.
Exclude System Packages	Hides all the Integration Server Core Packages from the Report. This option is selected by default and depends on Service Level View .
Show All Entries	Displays full coverage details. This is default selection.
Hide Missed Entries	Hides the untested parts of test coverage This does not effect the Coverage percentage.
Hide Covered Entries	Hides the tested parts of test coverage. This does not effect the Coverage percentage.

Viewing Mock Event Details

After you run the test, wM Code Coverage view displays the details of all the mock events during the test execution session. This view highlights the list of the mocked services, mock types, test case name, and the result.

> To view the mock event details

1. On the **wM Code Coverage** view, select the **Mock Events View** from the drop-down menu item.

Note:

- The **Full Packages View** and the **Service Level View** highlights the specific services if pipeline, exception or factory type of mocking is detected. The views also show the number of times a particular service is mocked.
- The **Execution Model View** highlights the services that contains service type of the mocking. Here, the view renders the mock service details in the execution chain instead of the mocked service. The view also shows the details of the actual service that is mocked.

Defining the Coverage Scope

Unit Test Framework allows you to edit and redefine the scope of a test coverage session. To achieve this, you can edit an existing launch configuration or create one. You can select packages that you want to include under the coverage purview. Flow elements and services belonging to the selected packages determine the coverage percentage.

> To create a launch configuration

1. In the webMethods Tests section, right click and select **wM Code Coverage Tools**.
2. Click **Code Coverage Launch Configurations...**
3. On the Code Coverage Launch Configurations box, select **wM Code Coverage** and click to add a new launch configuration.
4. Enter a name in the **Name** field and a project name in **Project** field.
5. On the Test tab, enter the following information:

Field	Description
Project	Specifies the project name for..... You can click Browse... to select from the
Test Suite	Specifies the test suite path. You can click Search... to select from a list of valid test suite files in the specified Project.
Test Method	Optional. Specifies the test name. You can click Search... to fetch the list of tests from the specified test suite. If this field is left blank, all the tests are selected.

6. On the Project Filter tab, perform the following

Field	Description
Server Node	Specifies the server node name. You can select the Default server node to list all the available packages from the server.
Profiler Scope	Defines the scope of coverage analysis for the launch. You can select the required packages from the list.

7. Click **wM Code Coverage Tools**.

The coverage analysis appear as a graphical data under the **wM Code Coverage** view.

Coverage Analysis in Headless Mode

The *Test Suite Executor* (see [“Creating a Test Suite Executor” on page 51](#)) provides the Ant build file `run-composite-runner.xml` with necessary tasks and properties to start a test. Use the task `composite-runner-all-tests` for headless test execution to generate code coverage analysis report.

Specify the following properties:

Name	Description
<code>webMethods.test.setup.profile.mode</code>	Set to Coverage to generate coverage report. Set to None for regular test execution.
<code>webMethods.test.scope.packages</code>	Specifies the list of comma separated target Integration Server package names. This Defines the full scope for the coverage analysis and percentage calculation. Example: <code>SampleTestSuite,SampleTestSuite1</code>
<code>webMethods.test.profile.result.includeExecutionModelReport</code>	Set to true to generate the Execution Model code coverage report. Set to false (default) to generate the regular code coverage report.
<code>webMethods.test.profile.result.includeServiceLevelReport</code>	Set to true to generate the Service Level code coverage report. Set to false (default) to generate the regular code coverage report.

12 Service Usage

- WmServiceMock Services 64
- WmServiceMock specification 65
- References 66

WmServiceMock Services

The services in the WmServiceMock package deal with the mocking aspects of testing. These services provide a way to enable or disable mocks for individual services or server-wide.

wm.ps.serviceMock:loadMock

Sets up mocking for a service.

Inputs	scope	session, user, or server. The default is session.	
	service	The name of the service to be mocked. No validation is performed on the name of the server or its existence.	
	mockObject	The mockObject is an object type. The behavior of the mock is controlled by the type of the actual object.	
		java.lang.String	The name of the alternate service to mock the mocked service with.
		java.lang.Exception	The exception to be thrown for the mocked service.
		com.wm.data.IData	The fixed pipeline to return for the mocked service
		com.wm.ps.serviceMock.MockDataFactory	The implementation of the factory objects that creates the dynamic pipeline for the mocked service.
	parms	Optional document containing all extra parameters for the alternate service. This parameter is only needed when mocking a service with an alternate service and the alternate service needs additional inputs.	

Outputs None

wm.ps.serviceMock:clearMock

Removes mocking for a service.

Inputs	scope	session, user or server. The default is session.	
	service	The name of the service to be mocked. No validation is performed on the name of the server or its existence.	

Outputs None

wm.ps.serviceMock:clearAllMocks

Removes mocking for all services.

Inputs None

Outputs None

wm.ps.serviceMock:suspendMocks

Suspends mocking for all services.

Inputs None

Outputs None

wm.ps.serviceMock:resumeMocks

Resumes mocking for all services, for which it was suspended.

Inputs None

Outputs None

wm.ps.serviceMock:getMockedServices

Retrieves the list of services that are currently mocked in all the scopes.

Inputs None

Outputs mockedServices The list of services that are currently mocked in the session, user, or server scope.

WmServiceMock specification

wm.spec:result_comparator

Contains specifications that an Integration Server service must conform to when selected as a comparator service.

Inputs actualData **Document.** The actual output produced through the execution of a service under test.

 expectedData **Document** Optional. The expected output of a service as defined in an IData file selected in the Expected Output section.

Outputs result **Boolean.** The test result based on the outcome of an assertion logic implemented in an Integration Server service.

wm.spec:result_comparator

exceptionMessage **String** Optional. Additional information that is shown only when the test fails.

Note:

If you specify a message in the exceptionMessage field, the test result shows the message set as additional information only when there is a failure.

References

- [Javadoc API Reference](#) - The javadoc reference for the Test Suite java API. This is useful for advanced Test Suite features as well as creating pure java unit tests for Integration Server services.
- [XPath](#) - Documentation for XPath API.