

Using Digital Event Services to Communicate between Software AG Products

Version 10.5

October 2019

This document applies to Software AG Digital Event Services Version 10.5 and to all subsequent releases.

Specifications contained herein are subject to change and these changes will be reported in subsequent release notes or new editions.

Copyright © 2016-2019 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

Use of this software is subject to adherence to Software AG's licensing conditions and terms. These terms are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

Use, reproduction, transfer, publication or disclosure is prohibited except as specifically provided for in your License Agreement with Software AG.

Table of Contents

About this Guide.....	5
Document Conventions.....	5
Online Information and Support.....	6
Data Protection.....	7
Understanding Digital Event Services.....	9
Digital Event Services Overview.....	10
Support of Digital Event Services.....	10
The Digital Event Type Model.....	11
Delivery Modes for Digital Event Services.....	11
The Store-and-Forward Queue.....	11
Non-Queued Delivery of Digital Events.....	12
Messaging Services and Service Groups.....	13
Administering Digital Event Services.....	15
About Administering Digital Event Services.....	16
Configuring Services.....	16
Configuring Universal Messaging Services.....	16
Using Universal Messaging Services with SSL.....	18
Defining a DES Keystore.....	18
Defining a DES Truststore.....	19
Using the In-Process Service.....	20
Configuring Service Groups.....	20
Configuring the Default Service Group.....	21
Configuring Custom Service Groups.....	22
Considerations When Modifying a Service Group Configuration.....	25
Configuring Event Type Associations.....	25
Configuring Storage Settings.....	27
Using DES Command Line Tools.....	28
Monitoring Digital Event Services.....	29
Secure Password Handling.....	29
Changing the Master Password.....	30
Lifecycle Actions for Digital Event Services.....	31
Managing Digital Event Services Licenses.....	31
Registering a DES License in Command Central.....	31
Updating a Digital Event Services License in Command Central.....	32
Viewing Digital Event Services License Details.....	32
Performance Considerations on Linux.....	32
Deployment of Digital Event Types.....	35
Deployment of Digital Event Types.....	36
Considerations for Deploying Digital Event Types.....	36

Design-Time Considerations.....	37
Design-Time Considerations for Digital Event Services.....	38
Digital Event Services MBeans.....	39
Event Type Information MBean.....	40
Universal Messaging Service MBean.....	40
In-Process Service MBean.....	44
Queue MBean.....	47
Subscriber MBean.....	49

About this Guide

This document gives you an overview of Software AG Digital Event Services, which is Software AG's tool for managing simple event-based interactions.

The goal of Digital Event Services is to facilitate the integration between Software AG products and applications by easily allowing them to communicate.

Document Conventions

Convention	Description
Bold	Identifies elements on a screen.
Narrowfont	Identifies service names and locations in the format <i>folder.subfolder.service</i> , APIs, Java classes, methods, properties.
<i>Italic</i>	Identifies: Variables for which you must supply values specific to your own situation or environment. New terms the first time they occur in the text. References to other documentation sources.
Monospace font	Identifies: Text you must type in. Messages displayed by the system. Program code.
{ }	Indicates a set of choices from which you must choose one. Type only the information inside the curly braces. Do not type the { } symbols.
	Separates two mutually exclusive choices in a syntax line. Type one of these choices. Do not type the symbol.
[]	Indicates one or more options. Type only the information inside the square brackets. Do not type the [] symbols.

Convention	Description
...	Indicates that you can type multiple options of the same type. Type only the information. Do not type the ellipsis (...).

Online Information and Support

Software AG Documentation Website

You can find documentation on the Software AG Documentation website at <http://documentation.softwareag.com>. The site requires credentials for Software AG's Product Support site Empower. If you do not have Empower credentials, you must use the TECHcommunity website.

Software AG Empower Product Support Website

If you do not yet have an account for Empower, send an email to empower@softwareag.com with your name, company, and company email address and request an account.

Once you have an account, you can open Support Incidents online via the eService section of Empower at <https://empower.softwareag.com/>.

You can find product information on the Software AG Empower Product Support website at <https://empower.softwareag.com>.

To submit feature/enhancement requests, get information about product availability, and download products, go to [Products](#).

To get information about fixes and to read early warnings, technical papers, and knowledge base articles, go to the [Knowledge Center](#).

If you have any questions, you can find a local or toll-free number for your country in our Global Support Contact Directory at https://empower.softwareag.com/public_directory.asp and give us a call.

Software AG TECHcommunity

You can find documentation and other technical information on the Software AG TECHcommunity website at <http://techcommunity.softwareag.com>. You can:

- Access product documentation, if you have TECHcommunity credentials. If you do not, you will need to register and specify "Documentation" as an area of interest.
- Access articles, code samples, demos, and tutorials.
- Use the online discussion forums, moderated by Software AG professionals, to ask questions, discuss best practices, and learn how other customers are using Software AG technology.
- Link to external websites that discuss open standards and web technology.

Data Protection

Software AG products provide functionality with respect to processing of personal data according to the EU General Data Protection Regulation (GDPR). Where applicable, appropriate steps are documented in the respective administration documentation.

1 Understanding Digital Event Services

■ Digital Event Services Overview	10
■ Support of Digital Event Services	10
■ The Digital Event Type Model	11
■ Delivery Modes for Digital Event Services	11
■ The Store-and-Forward Queue	11
■ Non-Queued Delivery of Digital Events	12
■ Messaging Services and Service Groups	13

Digital Event Services Overview

Software AG Digital Event Services (DES) enables other Software AG products to intercommunicate by exchanging *digital events*. Digital events are typed and serialized data structures that are used to convey or record information about the execution of a runtime. This information can be application information, such as the state of a business process step, including any associated business data, or it can be system information, for example, how much memory and how many threads an application is using.

Any digital event has a *digital event type*. Each digital event type has an associated *digital event type definition* that is created and stored in the digital event type repository for the installation. Digital event types are created by users in a development environment, and subsequently deployed to production installations. The format of the events is based on Google Protocol Buffers.

Digital Event Services uses the *publish-subscribe* model. Applications can both *emit* and *subscribe* to streams of events of a given event type. When publishing a digital event, the originating application *emits* the event without considering whether other applications might receive the event, or whether the event might be archived to an event repository. On the other hand, applications that are consumers of events subscribe to digital events of a specific event type.

The destinations, also known as *destination services*, to which events are routed, are not defined at design-time. Instead, a system administrator manages the destination services at run-time.

Communication using Digital Event Services can be *persistent* or *non-persistent*. With persistent communication, the delivery of a digital event is guaranteed at least once. With non-persistent communication, the delivery of a digital event is not guaranteed.

A developer may set the *delivery preference* for a given event type, but the DES administrator controls the final *delivery mode*.

Support of Digital Event Services

Software AG Digital Event Services (DES) is used for communication only between the following products:

- webMethods Integration Server
- Apama
- webMethods Business Rules
- webMethods API Gateway
- webMethods Task Engine

You cannot use DES with other Software AG products. For more information about how to use DES from the perspective of the listed products, see the product documentation of the adopting products.

The Digital Event Type Model

Any digital event has a *digital event type*. A digital event type is a high-level definition of the event format that is independent of the underlying over-the-wire representation of an event. The event type model is designed to support an easy conversion of an event type into other Software AG type languages, such as Integration Server Document Type and Apama Event Processing Language.

For more information about the mapping of events from Integration Server and Apama to Digital Event Services, see *webMethods Integration Server Administrator's Guide* and *Connecting Apama Applications to External Components*, respectively.

Delivery Modes for Digital Event Services

Digital Event Services (DES) enables an administrator to set a delivery mode per event type. The delivery mode setting governs the quality of service if the DES runtime stops responding and becomes unavailable.

Digital events are stored in-memory or on-disk until their delivery is acknowledged. To ensure that at least one copy of an event is delivered, administrators can define the event type delivery mode as *persistent*. This means that the events of an event type are stored on-disk. If the runtime where DES is embedded becomes unavailable, the events are resent the next time the runtime starts.

If the delivery mode for an event type is *non-persistent*, events are stored in-memory. If the runtime where DES is embedded becomes unavailable events are not resent. Administrators can define on-disk and in-memory capacity globally and per event type.

The Store-and-Forward Queue

By default, Digital Event Services (DES) stores events in a local queue until DES receives an acknowledgement that the events have reached the configured destination services. When you configure a service group, you can specify destination services that listen for events of the event types that you associate with the service group. Before these events reach a destination service, DES stores the events in a local *store-and-forward queue*. The store-and-forward queue ensures that no events are lost when a destination service becomes unavailable.

In the Command Central web user interface, you can modify the delivery mode for each event type. Depending on the delivery mode you specify, the store-and-forward queue for the event type can be held on-disk or in-memory. After an event is added to

the queue, DES is ready to accept new events. In the meantime, DES delivers the queued events to the destination services in the order in which they were added to the queue.

Consideration for Using the Store-and-Forward Queue

- When a destination service becomes unavailable, DES tries to redeliver the events until the destination service becomes available. Meanwhile, events accumulate in the store-and-forward queue until the capacity of the queue is reached. When the capacity of the queue is reached, depending on the runtime in which DES is embedded, DES either throws an exception or blocks the sending of further events until some of the accumulated events reach the destination service.
- When you stop DES while it is in the process of sending events, if the destination service is active, DES allows for a grace period of 30 seconds during which DES tries to route the events that remain on the store-and-forward queue to the destination service. After the grace period is over, depending on the delivery mode of the events that you send, DES does the following:
 - If the events are from an event type that has a persistent delivery mode, after the grace period is over, any events that do not reach a destination service remain in storage until you start DES again and the events can be delivered.
 - If the events are from an event type that has non-persistent delivery mode, DES removes any events that remain waiting for the destination in the store-and-forward queue after the grace period is over.
- When you remove a destination service from a service group:
 - If a destination service is available and you remove it from a service group, DES gives this service a grace period of 30 seconds to process and acknowledge events in the store-and-forward queue that wait for this destination service. DES removes any events that remain waiting for the destination in the store-and-forward queue after the grace period is over.
 - If a destination service is currently unavailable and you remove it from a service group, DES removes any events in the store-and-forward queue that wait for this service to become available.

Related Topics

[Non-Queued Delivery of Digital Events](#)

[Configuring Event Type Associations](#)

[Configuring Service Groups](#)

[Configuring Storage Settings](#)

Non-Queued Delivery of Digital Events

If you configure a service group to have a single destination service, you can choose to bypass the local store-and-forward queue and instead use *non-queued delivery*. You can

choose this option when you do not want events to accumulate in the store-and-forward queue.

You can use non-queued delivery for a service group that has a destination service of type Universal Messaging.

When you configure event type associations in the Command Central web user interface, you can specify a persistent or a non-persistent delivery mode. Bypassing the store-and-forward queue and using non-queued delivery does not affect the delivery mode preference you configure.

Note: When you use non-queued delivery, DES ignores the storage settings you specify for the store-and-forward queue.

Considerations for Using Non-Queued Delivery

- When you use non-queued delivery and an event fails to reach the destination service, depending on the runtime where DES is embedded, DES either throws an exception that notifies the application that the destination service is unavailable or blocks the sending of further events until the destination service becomes available.
- When you stop DES while it is in the process of sending events, DES does not guarantee that all events reach the configured destination service before it shuts down. After you restart DES, it does not deliver any events that you sent after DES stopped.

Related Topics

[The Store-and-Forward Queue](#)

[Configuring Event Type Associations](#)

[Configuring Service Groups](#)

Messaging Services and Service Groups

Messaging services are endpoints where events are published. Depending on your application's capabilities to emit or subscribe to events, you can tag the messaging service as either a destination, a source, or both. Digital Event Services (DES) supports the following service types:

- **Universal Messaging services** - use services of this type to send events to or receive events from a Universal Messaging server realm or cluster.
- **In-Process service** - use this pre-configured service to send and receive events within the same server runtime.

Services are grouped together as a set of one or more services to which events can be sent. One of the services in a service group can be tagged as the source of events for all event types associated with the service group.

Each Digital Event Services runtime contains a default service group, which is sufficient for most use cases. However, you can also define a custom service group for a particular runtime.

Considerations when Using Service Groups

- If a service group contains no source service and your application creates a subscription for this service group, no events are received. The subscription remains inactive until a source service is configured.
- If an application emits events to a service group that has no destination service configured, then the emitted events are not received anywhere.
- Administrators can create a service group that contains no services for troubleshooting purposes.

2 Administering Digital Event Services

■ About Administering Digital Event Services	16
■ Configuring Services	16
■ Configuring Service Groups	20
■ Configuring Event Type Associations	25
■ Configuring Storage Settings	27
■ Using DES Command Line Tools	28
■ Monitoring Digital Event Services	29
■ Secure Password Handling	29
■ Lifecycle Actions for Digital Event Services	31
■ Managing Digital Event Services Licenses	31
■ Performance Considerations on Linux	32

About Administering Digital Event Services

You can administer Software AG Digital Event Services (DES) using the Command Central web user interface, templates, or command-line interface.

Using the Command Central web user interface, you can perform the following operations:

- Configure messaging services and service groups.
- Configure event type associations.
- Configure storage settings for digital events.

Important: Do not edit configuration files manually.

Developers can also provision and configure DES using the Command Central templates available in Software AG's GitHub project [sagdevops-templates.git](https://github.com/sagdevops-templates). You can use the following templates as samples that you adapt to fit your own use case:

- `sag-des` - this template shows how to provision DES and how to configure a default messaging service.
- `sag-des-config` - this templates shows how to provision DES, so that it uses secure communication with Java keystores and truststores. For this purpose, the template also shows how to configure a custom service group and associate one digital event type with it. You can also use secure communication with the default service group.

Note: Integration Server and Apama developers can also use the DES command-line tool to configure messaging connectivity without using Command Central. You can open a command-line prompt and type `java -jar` followed by `Software_AG_directory\common\lib\events-configuration-tool.jar` to run the utility.

For information about using Command Central CLI commands and Command Central templates, see *Software AG Command Central Help*.

Configuring Services

Digital Event Services (DES) provides a default Universal Messaging service, which you can modify or delete, and a pre-defined In-Process service. In addition, you can create, modify, and delete custom Universal Messaging services using Command Central.

Configuring Universal Messaging Services

You can create and configure services of Universal Messaging type, add them to groups, and associate event types to them.

To configure a Universal Messaging service

1. In Command Central, navigate to **Environments > Instances > All > *instance_name* > Digital Event Services > Configuration**.
2. Select **Messaging Services** from the drop-down menu, and then click .
3. Specify values for each **Field** in the table as outlined in the **Description** column:

Field	Description
Service Name	Required. A unique name for the service. The service name is not case-sensitive and must start with a character. You can use the following characters as separators: . (dot) and - (dash).
Description	Required. A description of the purpose of the service.
Provider URL	Required. The host and port of the Universal Messaging server to which the service connects. Supported transport protocols are NSP (TCP connection) and NSPS (SSL connection). The default value is <code>nsp://localhost:9000</code> . Note: When you configure an SSL connection to Universal Messaging, you must also specify values for Keystore Alias , Key Alias , and Truststore Alias .
Keystore Alias	Optional. The alias that identifies the keystore for establishing an SSL connection to Universal Messaging. You define a client keystore as described in " Defining a DES Keystore " on page 18.
Key Alias	Optional. The label that identifies a specific key within the keystore for establishing an SSL connection to Universal Messaging.
Truststore Alias	Optional. The alias that identifies the truststore for establishing an SSL connection to Universal Messaging. You define a client truststore as described in " Defining a DES Truststore " on page 19.
User Name	Optional. The name of the user authorized to connect to a Universal Messaging server with server-side authentication enabled.

Field	Description
Password	<p>Optional. The password of the user authorized to connect to a Universal Messaging server with server-side authentication enabled.</p> <p>If you only update the Password field, you must restart the runtime where the DES component is embedded for the new password to take effect.</p>

Important: You cannot rename existing services. If you want to modify a service name, you must delete the existing service and create a new one with a different name.

Before deleting a service, you must first remove it from any service groups to which the service belongs.

- Optionally, click **Test** to verify that your configuration is valid.

Note: When performing validation, Command Central checks whether the specified configuration information complies with the field requirements. This action does not ping a server to verify that a connection is possible.

- Save your changes.

Using Universal Messaging Services with SSL

Digital Event Services (DES) supports the Universal Messaging NSPS protocol for secure communication over Secure Sockets Layer (SSL).

To enable DES to communicate with an SSL-enabled Universal Messaging server over NSPS, you must first define a keystore and a truststore file for DES. The keystore and truststore function as repositories for the storage of keys and certificates necessary for SSL authentication, encryption/decryption, and digital signing/verification services.

You must define at least one keystore and one truststore for DES. If you cannot create new keystore and truststore files, you can refer to existing keystore and truststore files that are used for Universal Messaging communication and contain the appropriate private keys and certificates.

For more information about configuring Universal Messaging for SSL communication, see the Universal Messaging documentation. For more information about operations with keystore and truststore files, see the documentation for your certificate management tool.

Defining a DES Keystore

To use Digital Event Services (DES) with an SSL-enabled Universal Messaging server, you must specify the keystore that contains the private keys and certificates that authenticate DES for communication over NSPS.

To define keystores for DES

1. In Command Central, navigate to **Environments > Instances > All > *instance_name* > Digital Event Services > Configuration**.
2. Select **Keystores** from the drop-down menu, and then click .
3. Specify values for each **Field** in the table as outlined in the **Description** column:

Field	Description
Keystore Name	Required. A unique name for the keystore. The keystore name is not case-sensitive and must start with a character. You can use the following characters as separators: . (dot) and - (dash).
Description	Optional. A description for the keystore.
Location	Optional. The absolute file path to the location of the keystore.
Password	Optional. The password for the keystore.

4. Optionally, click **Test** to verify that your configuration is valid.

Note: When performing validation, Command Central checks whether the specified configuration information complies with the field requirements. Command Central does not check whether the information you provide is accurate.

5. Save your changes.
6. Restart the runtime in which DES is embedded.

Defining a DES Truststore

To use Digital Event Services (DES) with an SSL-enabled Universal Messaging server, you must specify the DES truststore that contains the trusted Universal Messaging certificates for establishing an SSL connection.

To define truststores for DES

1. In Command Central, navigate to **Environments > Instances > All > *instance_name* > Digital Event Services > Configuration**.
2. Select **Truststores** from the drop-down menu, and then click .
3. Specify values for each **Field** in the table as outlined in the **Description** column:

Field	Description
Truststore Name	Required. A unique name for the truststore. The truststore name is not case-sensitive and must start with a character. You can use the following characters as separators: . (dot) and - (dash).
Description	Optional. A description for the truststore.
Location	Required. The absolute file path to the location of the truststore.
Password	Optional. The password for the truststore.

- Optionally, click **Test** to verify that your configuration is valid.

Note: When performing validation, Command Central checks whether the specified configuration information complies with the field requirements. Command Central does not check whether the information you provide is accurate.

- Save your changes.
- Restart the runtime in which DES is embedded.

Using the In-Process Service

The In-Process (IP) service is a pre-defined service that enables different parts of an application runtime to exchange digital events without using an external messaging server. Only one In-Process service exists per runtime.

You cannot modify the configuration of the pre-defined In-Process service or create a custom In-Process service. You can only add the In-Process service to a service group. In the service group, you can set the **Usage** property for the In-Process service only to **Source and Destination**.

Related Topics

[Configuring Custom Service Groups](#)

Configuring Service Groups

A service group is a defined set of services, where each service has a specific usage. Digital Event Services allows administrators to associate event types with a custom

service group during the creation of the group. You use Command Central to configure service groups.

Configuring the Default Service Group

Each product runtime where Digital Event Services (DES) is used has a default service group. All event types that are not explicitly associated with a custom service group are associated with the default service group. All events of these event types are delivered to the services within the default service group.

Note: You cannot rename or delete the default service group.

You can modify the default behavior of DES by adding services to or removing services from the default service group.

Note: You must create the services before adding them to the default service group.

To configure the default service group

1. In Command Central, navigate to **Environments > Instances > All > *instance_name* > Digital Event Services > Configuration**.
2. Select **Service Groups** from the drop-down menu, and then click **Default** in the **Service Group Name** column.
3. Click  to add services to the group.
4. Select the services from the drop-down menu in the **Service Name** field.
5. For each service that you add to the default service group, define the **Usage** property as outlined in the **Description** column of this table:

Usage	Description
Source Only	Specify this option if your application subscribes to digital events. Note: Your service group must contain at most one source service. You cannot include the same service twice in the same service group.
Destination Only	Specify this option if your application emits events. This is the default value.
Source and Destination	Specify this option if your application both emits and subscribes to events.

6. Optionally, in the **Use Local Store&Forward Queue** field, select one of the following values:

- **Yes** - Default. DES stores events in a local store-and-forward queue until DES receives an acknowledgement that the events have reached the configured destination services.
- **No** - The events bypass the local store-and-forward queue and reach the destination service directly.

Note: You can use this option only when a single destination service is configured in the service group.

For more information about using the local store-and-forward queue and how it differs from non-queued delivery, see "[The Store-and-Forward Queue](#)" on page 11 and "[Non-Queued Delivery of Digital Events](#)" on page 12.

7. Optionally, click **Test** to verify that your configuration is valid.

Note: The validation is done on a field level, and checks whether the specified information complies with the field requirements.

8. Save your changes.

Related Topics

[Configuring Services](#)

[Configuring Custom Service Groups](#)

[Considerations When Modifying a Service Group Configuration](#)

Configuring Custom Service Groups

By default, Digital Event Services (DES) provides a default service group that contains a pre-configured Universal Messaging service. You can create one or more custom service groups and associate a set of event types with them.

When events of those particular event types are sent or received, they go to all services within the service group. One of the services in the group can be defined as source and/or destination of events for all event types associated with the service group.

Note: You cannot delete a custom service group that has event types associated with it.

To configure a custom service group

1. In Command Central, navigate to **Environments > Instances > All > *instance_name* > Digital Event Services > Configuration**.
2. Select **Service Groups** from the drop-down menu.
3. Click  to add a new custom group.

4. Specify values for each **Field** in the table as outlined in the **Description** column:

Field	Description
Group Name	<p>Required. Specify a unique name for the service group. The name is not case-sensitive and must start with a character. You can use the following characters as separators: .(dot) and - (dash).</p> <p>Note: You cannot rename a service group. If you want to modify a service group name, you must delete the existing service group and recreate the group with a different name.</p>
Description	<p>Required. Specify a description of the purpose of the service group.</p>
Services	<p>Optional. Click <input type="button" value="+"/> to add services to the group and then do the following:</p> <ul style="list-style-type: none"> ■ In the Service Name column, select a service. ■ In the Usage column, select one of the following options: <ul style="list-style-type: none"> ■ Source Only - if your application subscribes to digital events. ■ Destination Only - if your application emits events. ■ Source and Destination - if your application both emits and subscribes to events. This is the default value. <p>Note: Your service group must contain at most one source service. In addition, you cannot include the same service twice in the same service group.</p> <p>If you add the pre-defined In-Process service to a service group, you can set its usage only to Source and Destination. Any other services to the service group, you can only set them as Destination Only.</p>
Event Types	<p>Optional. Use the dual list box to manage the digital event types assigned to a service group.</p> <p>The box on the left shows event types that are not associated with any service group. The box on the right shows the event types currently assigned to this service group. Use the arrows to move event types between the two boxes.</p>

Field	Description
	<p>Tip: Use the search box to filter the list of available digital event types. You can also select multiple event types by holding down the CTRL button and clicking specific entries, or by holding down the SHIFT button and clicking the first and last entry of a range.</p> <p>You can also manage the association of event types with service groups on the Digital Event Services > Configuration > Event Types page in Command Central.</p> <p>Important: An event type can only be associated with a single service group. If you want to change the service group with which an event type is associated, you must first dis-associate the event type from its original service group, so that the event type shows in the dual list box.</p>
<p>Use Local Store&Forward Queue</p>	<p>Optional. Specify whether DES stores the events of the event types associated with the service group in a local store-and-forward queue. Select one of the following options:</p> <ul style="list-style-type: none"> ■ Yes - Default. DES stores events in a local store-and-forward queue until DES receives an acknowledgement that the events have reached the configured destination services. ■ No - The events bypass the local store-and-forward queue and reach the destination service directly. <p>Note: You can use this option only when a single destination service is configured in the service group.</p> <p>For more information about using the local store-and-forward queue and how it differs from non-queued delivery, see "The Store-and-Forward Queue" on page 11 and "Non-Queued Delivery of Digital Events" on page 12.</p>

5. Optionally, click **Test** to verify that your configuration is consistent.
6. Save your changes.

Related Topics

[Configuring Event Type Associations](#)

[Considerations When Modifying a Service Group Configuration](#)

Considerations When Modifying a Service Group Configuration

When you change the Universal Messaging source service of a service group, make sure that the Universal Messaging server specified in the original source service is running when Digital Event Services (DES) is applying the configuration change. DES applies the new configuration shortly after you make the changes in Command Central when the runtime in which DES is embedded is started, or the next time when the runtime is started.

If the Universal Messaging server for the original source service is unavailable when DES is processing the configuration change, the durable subscription objects on the channel of the source Universal Messaging server are not deleted. As a result, any events sent to this Universal Messaging channel are kept on it and consume memory. Even if you configure the new source service to use the original Universal Messaging server again, the events sent prior to this change do not reach the subscribers for the event type.

Configuring Event Type Associations

When events of a particular event type are sent or received, Digital Event Services (DES) delivers them to the services within a service group. To configure to where events are sent you need to associate event types with their respective service groups.

Applications cannot subscribe for digital event types that are not present in the DES event type repository.

To configure digital event type associations

1. In Command Central, navigate to **Environments > Instances > All > *instance_name* > Digital Event Services > Configuration**.
2. Select **Event Types** from the drop-down menu.
3. In the **Name** column, click **Event Types**, and then click **Edit**.
4. For each digital event type in the **Event Types** table, specify values for each **Field** in the following table as outlined in the **Description** column:

Field	Description
Delivery Mode	<p>The quality of service per event type, if the runtime in which DES is embedded stops responding and becomes unavailable. Values are:</p> <ul style="list-style-type: none"> ■ Follow Preference - events are delivered according to the delivery mode preference set in the event type definition. This is the default value. ■ Persistent - events are stored on-disk and resent after the runtime becomes available again.

Field	Description
	<ul style="list-style-type: none"> ■ Non-persistent - events are stored in-memory and are not resent after the runtime becomes available. <p>Important: Changing the delivery mode preference for an event type in the digital event type definition requires a restart of the runtime in which DES is embedded for the changes to take effect.</p> <p>To avoid restarting the runtime, instead of Follow Preference, you can select either Persistent or Non-Persistent in the Delivery Mode field to reflect the change in the event type.</p>
In-Memory Capacity	<p>The maximum number of events that are kept in-memory for an event type. You can specify any positive integer, or you can specify 1K (1024), 1M (1024K), or 1G (1024M).</p> <p>Alternatively, you can leave an empty string or specify <code>Default</code> to use the global default setting of the In-Memory Capacity property.</p>
On-Disk Capacity	<p>The maximum number of events that are kept on-disk for an event type. You can specify any positive integer, or you can specify 1K (1024), 1M (1024K), or 1G (1024M).</p> <p>Alternatively, you can leave an empty string or specify <code>Default</code> to use the global default setting of the On-Disk Capacity property.</p>
Service Group	<p>Select a service group from the drop-down menu with which to associate the event type.</p> <p>Note: Digital event types that are not explicitly associated with a custom service group are associated with the default service group.</p> <p>You can also associate event types with service groups during the configuration of a service group.</p>

5. Optionally, click **Test** to verify that your configuration is consistent.
6. Save your changes.

Related Topics

[Considerations for Deploying Digital Event Types](#)

[Delivery Modes for Digital Event Services](#)

[Configuring Storage Settings](#)

[Configuring Custom Service Groups](#)

Configuring Storage Settings

Depending on the delivery mode that you configure for an event type, events sent to Digital Event Services (DES) are stored on-disk or in-memory. Use the following procedure to configure storage settings for DES.

Note: Depending on the runtime in which DES is embedded, events are emitted synchronously or asynchronously. When events are emitted synchronously, DES ignores the **Sync Batch Size** and **Sync Timeout** settings.

To configure the storage settings for DES

1. In Command Central, navigate to **Environments > Instances > All > instance_name > Digital Event Services > Configuration**.
2. Select **Runtime Configuration** from the drop-down menu.
3. In the **Name** column, select **Runtime Configuration**, and then click **Edit**.
4. Specify values for each **Field** in the table as outlined in the **Description** column:

Field	Description
Storage Location	<p>Optional. Defines the location where events are stored on-disk. Specify an existing folder in your file system.</p> <div style="background-color: #f0f0f0; padding: 5px; margin: 5px 0;"> <p>Important: Before you specify a new storage location, if the existing storage location is in use, you must copy any existing files manually to the new storage location.</p> </div> <p>If you do not specify a value, events are stored in the same directory as the configuration.</p> <p>You must restart the runtime where the DES component is embedded for the changes to the Storage Location property to take effect.</p>
Sync Batch Size	<p>Required. Defines the number of events that are added to the store-and-forward queue before the queue is persisted to disk. DES ignores the Sync Batch Size setting if events are sent synchronously.</p>

Field	Description
	The default value is 100 events.
Sync Timeout	<p>Required. Defines the timeout in milliseconds that the on-disk store-and-forward queue waits before the events in the queue are persisted, in case the batch size has not been reached. DES ignores the Sync Timeout setting if events are sent synchronously.</p> <p>The default value is 500 milliseconds.</p>
Default On-Disk Capacity	<p>Required. Defines the maximum number of events of each event type that can be stored on disk. The default value is 1000000.</p> <p>Note: You can override the setting by specifying On-Disk Capacity per event type.</p>
Default In-Memory Capacity	<p>Required. Defines the maximum number of events of each event type that can be stored in the memory. The default value is 1000.</p> <p>Note: You can override the setting by specifying In-Memory Capacity per event type.</p>

5. Save your changes.

Related Topics

[Configuring Event Type Associations](#)

[Delivery Modes for Digital Event Services](#)

Using DES Command Line Tools

Digital Event Services (DES) provides several command line (CLI) tools that you use along with the user interfaces in Command Central and Software AG Designer to administer DES. You can find the following command line tools in the *Software AG_directory/common/lib* directory:

- `events-console.jar` - Use this tool to monitor the publishing of digital events.
- `events-generator.jar` - Use this tool to generate streams of digital events.
- `events-configuration-tool.jar` - Use this tool to configure message connectivity.

- `events-passman-tool.jar` - Use this tool to change the DES master password.

To access the usage information and run any of the available CLI tools for administering DES, open a command prompt and type `java -jar` followed by `Software_AG_directory\common\lib\` and the file name of the tool, for example:

```
java -jar Software_AG_directory\common\lib\events-console.jar
```

Related Topics

[Changing the Master Password](#)

Monitoring Digital Event Services

You can monitor the status of Digital Event Services (DES) in real time by using:

- **Optimize for Infrastructure.** Optimize for Infrastructure provides you with a set of default rules for notification of object failure and also enables you to define your own custom rules. For more information about monitoring DES by using Optimize for Infrastructure, see *Administering webMethods Optimize*.
- **The DES Monitoring API.** The monitoring API is based on Java Management Extensions (JMX) and represents services and queues by using managed beans (MBeans).

To enable monitoring by MBeans, set the `com.softwareag.events.routing.enable.jmx` system property to `true`. For more information about setting the property, see the product documentation of the DES runtime.

In addition, you can use the JMX Remote API to monitor remotely a server runtime where DES is running. To enable monitoring from remote systems, when you start the server runtime set `com.sun.management.jmxremote.port` system property. For more information about setting the property, see the product documentation of the DES runtime.

Important: When you enable remote monitoring of DES, ensure that the exposed information can only be accessed after authorization. For more information about securing the DES runtime, see the product documentation of the server runtime and the Java documentation.

Related Topics

[Digital Event Services MBeans](#)

Secure Password Handling

You can use Digital Event Services (DES) services to connect to password-protected systems.

DES service configuration files need to contain a password to successfully establish a secure connection to systems that require password authentication. To protect these passwords, DES encrypts and decrypts passwords using a master password that is also encrypted. In a Software AG installation, all runtimes where DES is embedded use a single master password. The master password is stored in *Software AG_directory/common/DigitalEventServices/security/passman*.

Important: When you first install DES, the default master password is "manage". Software AG recommends that you change the default master password shortly after installing DES.

Changing the Master Password

Digital Event Services (DES) provides you with a command line tool for changing the master password. The command line tool is installed in *Software AG_directory/common/lib/events-passman-tool.jar*.

Note: You can find usage information for the command line utility by opening a command line prompt in *Software AG_directory/common/lib* and by executing the following command:

```
java -jar events-passman-tool.jar
```

To change the master password:

1. Open command line prompt in the *Software AG_directory /common/lib*.
2. Specify a new master password by typing the following command:

```
java -jar events-passman-tool.jar change-mpw old_mpw new_mpw passman_config_location
```

where:

- *old_mpw* is the old master password that is needed for authentication.
- *new_mpw* is the new master password.
- *passman_config_location* is the storage location of the master password: *Software AG_directory/common/DigitalEventServices/security/passman*.

Note: If the passwords and/or the configuration location contain characters that affect the parameter resolution of the command shell, you need to apply appropriate escaping.

The command line tool changes the master password of the given configuration to the value you specify for *new_mpw*, and reports the number of updated passwords in service definitions.

Lifecycle Actions for Digital Event Services

Digital Event Services (DES) does not support any lifecycle actions, such as start, stop, or restart. Although the **Lifecycle Actions** setting for DES is active in the Command Central web user interface, administrators should not use this functionality.

For more information about shutting down and starting Integration Server and Apama, see *webMethods Integration Server Administrator's Guide* and *Deploying and Managing Apama Applications*, respectively.

Managing Digital Event Services Licenses

You must have a valid license file to use Digital Event Services (DES). When you install DES, Software AG Installer asks you to provide your license file for DES. If you do not provide a license file, DES is installed with a 30-day trial license. Installer copies the license file, named `license.xml`, to the `Software AG_directory/common/DigitalEventServices/license` directory.

DES requires a single license file per Software AG installation. This license applies to all runtimes that use digital events to communicate.

To overwrite the trial license or change a license that has expired, you must:

1. Register your license, as described in "[Registering a DES License in Command Central](#)" on page 31.
2. Update the license, as described in "[Updating a Digital Event Services License in Command Central](#)" on page 32.

Important: A missing license file is regarded as an invalid license.

If you do not use Command Central to administer DES, you can manually update the DES license by copying the new license to the `Software AG_directory/common/DigitalEventServices/license` directory. The new file must be named `license.xml`.

For more information about licensing, see *Installing Software AG Products*.

Related Topics

[Viewing Digital Event Services License Details](#)

Registering a DES License in Command Central

Use the following procedure to add a Digital Event Services (DES) license file in the Command Central web user interface.

To add a Digital Event Services license

1. In Command Central, navigate to **Licensing > Keys**.
2. Click **+**, and then select **Add License Key**.
3. Specify values for each **Field** in the table as outlined in the **Description** column:

Field	Description
License key	Required. The location of the license file.
Alias	Required. The alias name of the license key.

4. Click **Add**.

Updating a Digital Event Services License in Command Central

Before updating a Digital Event Services (DES) license, you must register the license file in Command Central.

To update a Digital Event Services license

1. In Command Central, navigate to **Environments > Instances > All > SPM > DES Common > Configuration**.
2. Select **Licenses** from the drop-down menu, and then click **DigitalEventServices**.
3. Click **Edit** and select a license key alias in the **License Alias** field.
4. Save your changes.

Viewing Digital Event Services License Details

You can view license details for Digital Event Services (DES), including the status and expiration date of the license, the actual license key, and product information in the Command Central web user interface.

To view license details

1. In Command Central, navigate to **Environments > Instances > All > SPM > DES Common > Configuration**.
2. Select **Licenses** from the drop-down menu, and then click **DigitalEventServices**.

Performance Considerations on Linux

For deployments on a Linux operating system where performance is a concern, use an XFS file system for the Digital Event Services store-and-forward queue. If the

throughput is high, XFS file systems perform better compared to the default ext4 file systems.

3 Deployment of Digital Event Types

- Deployment of Digital Event Types 36

Deployment of Digital Event Types

Deployment, in the context of Software AG Digital Event Services (DES), is the process of provisioning a run-time environment with digital event types.

You use repository-based deployment in webMethods Deployer to deploy digital event type composites to one or more target runtimes. You must install the Asset Build Environment (ABE) to use repository-based deployment.

The digital event type composites that you create prior to deployment must have a specific structure in order to be deployable using Deployer.

You create digital event types from the native document type definitions of Apama and Integration Server by synchronizing them to a local event type repository for the installation. The local event type repository is the source for the digital event type composites. When you run the ABE build script, the script searches the specified event type repositories and creates a composite for all digital event types in it.

Digital event type definitions are individual assets that the Asset Build Environment packs into zip archives. A single zip file can contain multiple event type definitions.

For more information about installing the Asset Build Environment, see *Installing Software AG Products*. For more information about building composites for repository-based deployment, see *webMethods Deployer User's Guide*.

Considerations for Deploying Digital Event Types

Consider the following information when deploying digital event types from your local environment to other instances of Integration Server or Apama:

- Applications cannot subscribe to digital event types that are not present in the DES event type repository.
- Do not modify the internal structure of the event type repository or the names of digital event types.

4 Design-Time Considerations

- Design-Time Considerations for Digital Event Services 38

Design-Time Considerations for Digital Event Services

In Software AG Designer, you develop Integration Server and Apama applications that communicate with one another by exchanging digital events. Each digital event type has an associated digital event type definition that is created and stored in the digital event type repository for the installation. You can use both Integration Server and Apama tooling to generate a digital event type from their native type definitions.

Important: The ownership of a digital event type is non-transferable and belongs to a single application.

Consider the following information when developing applications that use Software AG Digital Event Services (DES) to communicate:

- Do not create the same digital event type definition from both an Apama event type and an Integration Server document type. This constraint applies to both digital event types and the digital event types that they require implicitly in their event type definitions.
- Start by generating a digital event type from an Integration Server document type when an Integration Server application processes digital events. Integration Server does not support the creation of Integration Server document types from digital event types.
- Do not modify Apama event types that you generate from a digital event type. Instead, modify the source Integration Server document type and re-generate the digital event type from it. Use Apama tooling to re-generate the Apama event type definition from the digital event type.

A Digital Event Services MBeans

■ Event Type Information MBean	40
■ Universal Messaging Service MBean	40
■ In-Process Service MBean	44
■ Queue MBean	47
■ Subscriber MBean	49

Event Type Information MBean

Retrieves information about an event type.

MBean Name

```
com.softwareag.events.routing:type=EventTypes,eventType=event_type_name,
category=Information
```

where *event_type_name* is the name of the event type.

MBean Attributes

The following table lists the attributes of the Event Type Information MBean and their descriptions:

Attribute	Description
deliveryMode	String. The delivery mode of the event type. Values are: <ul style="list-style-type: none"> ■ Persistent ■ Non-Persistent

Universal Messaging Service MBean

Retrieves information about the Universal Messaging (UM) services configured in a service group that is associated with an event type.

MBean Name

```
com.softwareag.events.routing:type=EventTypes,eventType=event_type_name,
category=Services,serviceName=service_name
```

where *event_type_name* is the name of the event type and *service_name* is the name of the Universal Messaging service.

MBean Attributes

The following table lists the attributes of the Universal Messaging Service MBean and their descriptions:

Attribute	Description
name	String. The name of the service.

Attribute	Description
usage	<p>String. The usage of the service. Values are:</p> <ul style="list-style-type: none"> ■ <code>SourceOnly</code> - you can subscribe to the service, but you cannot use the service to send events. ■ <code>DestinationOnly</code> - you can use the service to only send events. ■ <code>SourceAndDestination</code> - you can both subscribe to the service and use the service to send events.
providerUrl	<p>String. The URL of the Universal Messaging server. The <code>providerUrl</code> attribute has the following format: <code>protocol://host:port</code>. The default value is <code>nsp://localhost:9000</code>.</p>
connected	<p>Boolean. Indicates whether the service is connected to the configured Universal Messaging server.</p>
connectTime	<p>Instant. The time when the service connected to the Universal Messaging server, or reconnected to the server after losing connection.</p>
disconnectTime	<p>Instant. The time when the service disconnected from the Universal Messaging server.</p>
activeExclusiveDurable-SubscribersCount	<p>Integer. The number of active exclusive durable subscribers to the service. If the service usage is <code>DestinationOnly</code>, the value of this attribute is empty.</p>
activeExclusiveDurable-SubscribersIds	<p>List<String>. The identifiers of the active exclusive durable subscribers to the service. If the service usage is <code>DestinationOnly</code>, the value of this attribute is empty.</p>
activeSharedDurable-SubscribersCount	<p>Integer. The number of active shared durable subscribers to the service. If the service usage is <code>DestinationOnly</code>, the value of this attribute is empty.</p>
activeSharedDurable-SubscribersIds	<p>List<String>. The identifiers of the active shared durable subscribers to the service. If the service</p>

Attribute	Description
	usage is <code>DestinationOnly</code> , the value of this attribute is empty.
activeSerialDurable-SubscribersCount	Integer. The number of active serial durable subscribers to the service. If the service usage is <code>DestinationOnly</code> , the value of this attribute is empty.
activeSerialDurable-SubscribersIds	List<String>. The identifiers of the active serial durable subscribers to the service. If the service usage is <code>DestinationOnly</code> , the value of this attribute is empty.
inactiveExclusiveDurable-SubscribersCount	Integer. The number of exclusive durable subscribers to the service that are inactive but still subscribed. If the service usage is <code>DestinationOnly</code> , the value of this attribute is empty.
inactiveExclusiveDurable-SubscribersIds	List<String>. The identifiers of the exclusive durable subscribers to the service that are inactive but still subscribed. If the service usage is <code>DestinationOnly</code> , the value of this attribute is empty.
inactiveSharedDurable-SubscribersCount	Integer. The number of shared durable subscribers to this service that are inactive but still subscribed. If the service usage is <code>DestinationOnly</code> , the value of this attribute is empty.
inactiveSharedDurable-SubscribersIds	List<String>. The identifiers of the shared durable subscribers to the service that are inactive, but still subscribed. If the service usage is <code>DestinationOnly</code> , the value of this attribute is empty.
inactiveSerialDurable-SubscribersCount	Integer. The number of serial durable subscribers to the service that are inactive but still subscribed. If the service usage is <code>DestinationOnly</code> , the value of this attribute is empty.
inactiveSerialDurable-SubscribersIds	List<String>. The identifiers of the serial durable subscribers to the service that are inactive but still subscribed. If the service usage is <code>DestinationOnly</code> , the value of this attribute is empty.

Attribute	Description
nonDurable-SubscribersCount	Integer. The number of non-durable subscribers to the service. If the service usage is <code>DestinationOnly</code> , the value of this attribute is empty.
receivedEvents	Long. The number of events received by all subscribers to the service since the service became active. If the service usage is <code>DestinationOnly</code> , the value of this attribute is empty.
lastSendingStatus	<p>String. The status of the last sending operation performed by the service. Values are:</p> <ul style="list-style-type: none"> ■ <code>Green</code> - when the last sending operation to the Universal Messaging server is successful. ■ <code>Red</code> - when the last sending operation to the Universal Messaging server failed. Possible reasons for a <code>Red</code> sending status are: <ul style="list-style-type: none"> ■ The Universal Messaging server is unavailable. ■ The Universal Messaging server is overloaded and responds with a delay. ■ The events that DES sends exceed the capacity of the Universal Messaging channel in use. ■ There is no network connectivity or it is slow. <p>Important If the Universal Messaging server becomes unavailable, but no events are sent for long time, the <code>lastSendingStatus</code> might still be <code>Green</code> because the status is updated only after a transaction to the server.</p> <p>To determine whether the server is available without sending events, check the <code>connected</code>, <code>connectTime</code>, and <code>disconnectTime</code> attributes.</p>
lastSendingStatusDetails	String. Information about the last sending status. When the status is <code>Red</code> , the explanation contains the exception that caused the sending operation to fail.
sentEvents	Long. The number of events sent to the service. If the service usage is <code>SourceOnly</code> , the value of this attribute is empty.

Attribute	Description
acknowledgedSentEvents	Long. The number of events sent to the service and successfully acknowledged by the Universal Messaging server. If the service usage is <code>SourceOnly</code> , the value of this attribute is empty.
lastSendingTime	Instant. The time when the last event was sent to the Universal Messaging server. Note: The <code>lastSendingTime</code> attribute reflects the time when an event was last sent to the destination service. The <code>lastSendingTime</code> attribute does not carry information about whether an event was acknowledged by the destination service. To see whether an event was acknowledged by the destination service, check the <code>lastCompletedAcknowledgementTime</code> attribute.
lastCompletedAcknowledgementTime	Instant. The last time when an event sent to the service was successfully acknowledged by the Universal Messaging server. If the service usage is <code>SourceOnly</code> , the value of this attribute is empty.
regularDelivery-InterruptionsCount	Integer. The number of times when the service switched to redelivery mode because of a failure to deliver an event to the Universal Messaging server. If the service usage is <code>SourceOnly</code> , the value of this attribute is empty.

In-Process Service MBean

Retrieves information about the In-Process (IP) service configured in a service group that is associated with an event type.

MBean Name

```
com.softwareag.events.routing:type=EventTypes,eventType=event_type_name,category=Services,serviceName=In-Process
```

where `event_type_name` is the name of the event type.

MBean Attributes

The following table lists the attributes of the In-Process Service MBean and their descriptions:

Attribute	Description
name	String. The name of the service. The value of name is always <code>In-Process</code> .
usage	String. The usage of the service. The value of usage is always <code>SourceAndDestination</code> .
connected	Boolean. Indicates whether the service is connected. The value of connected is always <code>true</code> .
connectTime	Instant. The time when the IP service connects on first usage.
disconnectTime	Instant. The time when the IP service disconnects. The value of disconnectTime is always empty.
activeExclusiveDurable-SubscribersCount	Integer. The number of active exclusive durable subscribers to the IP service.
activeExclusiveDurable-SubscribersIds	List<String>. The identifiers of the active exclusive durable subscribers to the service.
activeSharedDurable-SubscribersCount	Integer. The IP service does not support shared durable subscribers. The value of activeSharedDurableSubscribersCount is always 0.
activeSharedDurable-SubscribersIds	List<String>. The IP service does not support shared durable subscribers. The value of activeSharedDurableSubscribersIds is always an empty list.
activeSerialDurable-SubscribersCount	Integer. The IP service does not support serial durable subscribers. The value of activeSerialDurableSubscribersCount is always 0.
activeSerialDurable-SubscribersIds	List<String>. The IP service does not support serial durable subscribers. The value of activeSerialDurableSubscribersIds is always an empty list.
inactiveExclusiveDurable-SubscribersCount	Integer. The number of exclusive durable subscribers to the service that are inactive but still subscribed.

Attribute	Description
inactiveExclusiveDurable-SubscribersIds	List<String>. The identifiers of the exclusive durable subscribers to the service that are inactive but still subscribed.
inactiveSharedDurable-SubscribersCount	Integer. The IP service does not support shared durable subscribers. The value of inactiveSharedDurableSubscribersCount is always 0.
inactiveSharedDurable-SubscribersIds	List<String>. The IP service does not support shared durable subscribers. The value of inactiveSharedDurableSubscribersIds is always an empty list.
inactiveSerialDurable-SubscribersCount	Integer. The IP service does not support serial durable subscribers. The value of inactiveSerialDurableSubscribersCount is always 0.
inactiveSerialDurable-SubscribersIds	List<String>. The IP service does not support serial durable subscribers. The value of inactiveSerialDurableSubscribersIds is always an empty list.
nonDurable-SubscribersCount	Integer. The number of non-durable subscribers to the service.
receivedEvents	Long. The number of events received by all subscribers to the IP service since the service became active.
lastSendingStatus	String. The status of the last sending operation performed by the IP service. Values are: <ul style="list-style-type: none"> ■ Green - when the last sending operation is successful. ■ Red - when the last sending operation has failed.
lastSendingStatusDetails	String. Information about the last sending status. If the status is Red, the explanation contains the exception that caused the sending operation to fail.
sentEvents	Long. The number of events sent to the IP service.

Attribute	Description
acknowledgedSentEvents	Long. The number of events sent to the IP service and successfully acknowledged by the client event processor.
lastSendingTime	Instant. The time when the last event was sent to the client event processor. Note: The <code>lastSendingTime</code> attribute reflects the time when an event was last sent to the destination service. The <code>lastSendingTime</code> attribute does not carry information about whether an event was acknowledged by the client event processor. To see whether an event was acknowledged by the destination service, check the <code>lastCompletedAcknowledgementTime</code> attribute.
lastCompletedAcknowledgementTime	Instant. The last time when an event sent to the IP service was successfully acknowledged by the client event processor.
regularDelivery-InterruptionsCount	Integer. The number of times when the service switched to redelivery mode. The IP service does not support redelivery and the value of <code>regularDeliveryInterruptionsCount</code> is always 0.

Queue MBean

Retrieves on-disk and in-memory storage details per event type.

MBean Name

```
com.softwareag.events.routing:type=EventTypes,eventType=event_type_name,category=Queues,queueType=queue_type
```

where *event_type_name* is the name of the event type and *queue_type* is type of storage used for the queue. Values for *queue_type* are *On-Disk* and *In-Memory*.

MBean Attributes

The following table lists the attributes of the Queue MBean and their descriptions:

Attribute	Description
status	String. The status of the queue. Values are:

Attribute	Description
	<ul style="list-style-type: none"> ■ Green ■ Yellow ■ Red
statusDetails	<p>String. An explanation of the current status. Values are:</p> <ul style="list-style-type: none"> ■ Green - the utilization is below 90%. ■ Yellow - the queue is functioning properly, but the utilization is equal to or greater than 90% but still less than 100%. ■ Red - the queue is full.
capacity	<p>Long. The maximum number of events that the queue can store.</p>
currentSize	<p>Long. The number of events currently stored in the queue.</p>
averageUtilization	<p>Float. The average <i>size:capacity</i> ratio since the first send operation for the event type that uses the queue.</p>
queueBufferFullCount	<p>Integer. The number of times that the queue becomes full, that is when <i>currentSize</i> is equal to <i>capacity</i>.</p>
usedMemorySize	<p>Long. The memory space that events currently occupy in the store.</p> <p>If an error occurs while reading the value from the store, the value you retrieve is -1.</p>
usedDiskSpace	<p>Long. The bytes on disk that events currently occupy in the store.</p> <p>If the event type is configured with non-persistent delivery mode, or if an error occurs while reading the value from the store, the value you retrieve is -1.</p>
freeFileSpacePercentage	<p>Long. The percentage of free space in the store.</p>

Attribute	Description
	If the event type is configured with non-persistent delivery mode, or if an error occurred while reading the value from the store, the value you retrieve is -1.

Subscriber MBean

Monitors the subscribers to Digital Event Services (DES) event types.

MBean Name

where *event_type_name* is the name of the event type and *subscriber_name* is the unique name that DES generated for the subscriber.

Note: You can retrieve the subscriber ID that you specify when creating a durable subscriber from the `subscriberId` attribute.

MBean Attributes

The following table lists the attributes of the Subscriber MBean and their descriptions:

Attribute	Description
<code>subscriberId</code>	String. The identifier of a subscriber.
<code>type</code>	String. The type of the subscriber. Values are: <ul style="list-style-type: none"> ■ <code>Exclusive durable</code> ■ <code>Shared durable</code> ■ <code>Serial durable</code> ■ <code>Exclusive non-durable</code> For more information about the different types of subscribers, see <i>webMethods Service Development Help</i> .
<code>sourceService</code>	String. The name of the source service from which the subscriber receives events.
<code>status</code>	String. The status of the subscriber. Values are: <ul style="list-style-type: none"> ■ <code>Active</code> - the subscriber is working as expected. ■ <code>Inactive</code> - the subscriber is closed but still subscribed.

Attribute	Description
	<ul style="list-style-type: none"> <li data-bbox="634 327 1344 457">■ Not configured - no source service is configured for the event type, or the source service is removed from the configuration after the subscriber was created. <p data-bbox="683 485 1352 615">If the source service in a service group is an In-Process (IP) service, the status of the serial durable subscribers is Not configured. The IP service does not support serial durable subscribers.</p> <div data-bbox="634 632 1352 762" style="background-color: #f0f0f0; padding: 5px;"> <p data-bbox="651 653 1287 747">Note: When a subscriber is <i>closed and unsubscribed</i>, its MBean is unregistered. In this case, the subscriber has no status.</p> </div>
statusDetails	String. An explanation of the current subscriber status.
receivedEvents	Long. The number of events received by the subscriber, including redelivered events.
lastReceivedEventTime	Instant. The time when the last event was received by the subscriber.
receivedRedeliveredEvents	Long. The number of redelivered events received by the subscriber.
lastReceivedRedelivered-EventTime	Instant. The time when the last redelivered event was received by the subscriber.
acknowledgedEvents	Long. The number of events acknowledged by the client event processor associated with the subscriber.
lastAcknowledgementTime	Instant. The time of the last event acknowledgement by the client event processor associated with the subscriber.