

webMethods EntireX

Administration under z/OS

Version 10.8

October 2022

This document applies to webMethods EntireX Version 10.8 and all subsequent releases.

Specifications contained herein are subject to change and these changes will be reported in subsequent release notes or new editions.

Copyright © 1997-2022 Software AG, Darmstadt, Germany and/or Software AG USA, Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA, Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at http://softwareag.com/licenses.

Use of this software is subject to adherence to Software AG's licensing conditions and terms. These terms are part of the product documentation, located at http://softwareag.com/licenses/ and/or in the root installation directory of the licensed product(s).

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third-Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at http://softwareag.com/licenses and/or in the root installation directory of the licensed product(s).

Use, reproduction, transfer, publication or disclosure is prohibited except as specifically provided for in your License Agreement with Software AG

Document ID: EXX-ADMIN-108-20220601ZOS

Table of Contents

1 About this Documentation	1
Document Conventions	2
Online Information and Support	2
Data Protection	3
2 Setting up Broker Instances	5
Setting up TCP/IP Transport	6
Running Broker with SSL/TLS Transport	6
Setting up Entire Net-Work/Adabas SVC Transport	12
Starting and Stopping the Broker	12
Dual Command Log Files	13
Tracing EntireX Broker	13
Protecting a Broker against Denial-of-Service Attacks	17
Setting the Time Zone for Broker	17
Achieving FIPS Compliance	18
3 Broker Attributes	
Name and Location of Attribute File	21
Attribute Syntax	21
Broker-specific Attributes	23
Service-specific Attributes	43
Codepage-specific Attributes	55
Adabas SVC/Entire Net-Work-specific Attributes	
Security-specific Attributes	61
TCP/IP-specific Attributes	68
c-tree-specific Attributes	71
SSL/TLS-specific Attributes	73
DIV-specific Attributes	78
Adabas-specific Attributes	
Application Monitoring-specific Attributes	
Authorization Rule-specific Attributes	
Variable Definition File	84
4 Configuring Broker for Internationalization	85
Configuring ICU Conversion	86
Building and Installing ICU Custom Converters	
Writing Translation User Exits	90
Configuring Translation User Exits	
Writing SAGTRPC User Exits	
Configuring SAGTRPC User Exits	99
5 Managing the Broker Persistent Store	
Implementing an Adabas Database as Persistent Store	
Implementing a DIV Persistent Store	
Migrating the Persistent Store	
6 Broker Resource Allocation	
General Considerations	118

	Specifying Global Resources	119
	Restricting the Resources of Particular Services	119
	Specifying Attributes for Privileged Services	121
	Maximum Units of Work	122
	Calculating Resources Automatically	122
	Dynamic Memory Management	124
	Dynamic Worker Management	125
	Storage Report	127
	Maximum TCP/IP Connections per Communicator	128
7 Ac	lministering Broker Stubs	129
	Available Stubs	130
	ARFETB	131
	BROKER	131
	CICSETB	134
	COMETB	136
	IDMSETB	137
	MPPETB	137
	NATETB23	138
	NATETBZ	139
	Tracing for Broker Stubs	139
	Timeout Settings for Broker Stubs	143
	Transport Methods for Broker Stubs	146
	SVC Number for Broker Communication	
	Considerations for Users without Adabas	149
	Support of Clustering in a High Availability Scenario	149
8 Br	oker Command-line Utilities	
	ETBINFO	152
	ETBCMD	161
9 Or	perator Commands	171
	Command Syntax	172
	General Broker Commands	172
	Participant-specific Commands	178
	Security-specific Commands	184
	Transport-specific Commands	185
	XCOM-specific Commands	189
	Application Monitoring-specific Commands	192
10 T	racing EntireX Broker	193
	Switching on Tracing	194
	Switching off Tracing	194
	Deferred Tracing	194
	Dynamically Switching On or Off the EntireX Broker Trace	195
11 B	roker Shutdown Statistics	197
	Shutdown Statistics Output	198
	Table of Shutdown Statistics	
12 C	Command Logging in EntireX	203

Introduction to Command Logging	204
Command Log Filtering using Command-line Interface ETBCMD	
ACI-driven Command Logging	208
Dual Command Log Files	208
13 Accounting in EntireX Broker	209
EntireX Accounting Data Fields	210
Using Accounting under z/OS	213
Example Uses of Accounting Data	215

1 About this Documentation

Document Conventions	. 2
Online Information and Support	
Data Protection	

Document Conventions

Convention	Description	
Bold	Identifies elements on a screen.	
Monospace font Identifies service names and locations in the format folder.subfolder.s		
Italic	Identifies:	
	Variables for which you must supply values specific to your own situation or environment.	
	New terms the first time they occur in the text.	
	References to other documentation sources.	
Monospace for	t Identifies:	
	Text you must type in.	
	Messages displayed by the system.	
	Program code.	
{}	Indicates a set of choices from which you must choose one. Type only the information inside the curly braces. Do not type the { } symbols.	
I	Separates two mutually exclusive choices in a syntax line. Type one of these choices. Do not type the symbol.	
[]	Indicates one or more options. Type only the information inside the square brackets. Do not type the [] symbols.	
	Indicates that you can type multiple options of the same type. Type only the information. Do not type the ellipsis ().	

Online Information and Support

Product Documentation

You can find the product documentation on our documentation website at https://documentation.softwareag.com.

In addition, you can also access the cloud product documentation via https://www.software-ag.cloud. Navigate to the desired product and then, depending on your solution, go to "Developer Center", "User Center" or "Documentation".

Product Training

You can find helpful product training material on our Learning Portal at https://knowledge.soft-wareag.com.

Tech Community

You can collaborate with Software AG experts on our Tech Community website at https://tech-community.softwareag.com. From here you can, for example:

- Browse through our vast knowledge base.
- Ask questions and find answers in our discussion forums.
- Get the latest Software AG news and announcements.
- Explore our communities.
- Go to our public GitHub and Docker repositories at https://github.com/softwareag and https://hub.docker.com/publishers/softwareag and discover additional Software AG resources.

Product Support

Support for Software AG products is provided to licensed customers via our Empower Portal at https://empower.softwareag.com. Many services on this portal require that you have an account. If you do not yet have one, you can request it at https://empower.softwareag.com/register. Once you have an account, you can, for example:

- Download products, updates and fixes.
- Search the Knowledge Center for technical information and tips.
- Subscribe to early warnings and critical alerts.
- Open and update support incidents.
- Add product feature requests.

Data Protection

Software AG products provide functionality with respect to processing of personal data according to the EU General Data Protection Regulation (GDPR). Where applicable, appropriate steps are documented in the respective administration documentation.

2 Setting up Broker Instances

6
6
12
12
13
13
17
17
18

This chapter contains information on setting up the Broker under z/OS. It assumes that you have completed the relevant steps described under *Installing EntireX under z/OS*.

Setting up TCP/IP Transport

The recommended way to set up the TCP/IP communicator is to define PORT=nnnn and optionally HOST=x.x.x.x| hostname and STACK-NAME=stackname under TCP/IP-specific Attributes.

However, if no port number is specified in the broker attribute file, the EntireX Broker kernel uses getservbyname to determine the TCP/IP port on which it will listen for incoming connections. The specified name is the value of BROKER-ID in the attribute file. An entry for this value must be made in the local machine's /etc/services file. Example:

ETBnnn yyyyy/tcp # local host

where *etbnnn* is the BROKER-ID and *yyyyy* is the intended port number. This is the same place from which local Broker stubs will obtain the port information. If getservbyname fails, then a default port number of 1971 will be used. This is the same default port number that the stubs use.

Running Broker with SSL/TLS Transport

- Introduction
- Using IBM's Application Transparent Transport Layer Security (AT-TLS)
- Migration from Broker's Direct SSL/TLS Support to AT-TLS

Introduction

The Broker can use Secure Sockets Layer/Transport Layer Security (SSL/TLS) as the transport medium. The term "SSL" in this section refers to both SSL and TLS. RPC-based clients and servers as well as ACI clients and servers are always SSL clients. The broker is always the SSL server. For an introduction see *SSL/TLS*, *HTTP(S)*, and *Certificates with EntireX* in the platform-independent Administration documentation.


SSL delivered on a z/OS mainframe will typically use the Resource Access Control Facility (RACF) as the certificate authority (CA). Certificates managed by RACF can only be accessed through the RACF keyring container. A keyring is a collection of certificates that identify a networking trust relationship (also called a trust policy). In an SSL client/server network environment, entities identify themselves using digital certificates called through a keyring. Server applications on z/OS that wish to establish network connections to other entities can use keyrings and their certificate contents to determine the trustworthiness of the client or peer entity. Note that certificates can belong to more than one keyring, and you can assign different users to the same keyring. Because

of the way RACF internally references certificates, they must be uniquely identifiable by owner and label, and also unique by serial number plus data set name (DSN).

For establishing an SSL connection on z/OS, IBM's Application Transparent Transport Layer Security (AT-TLS) can be used, where the establishment of the SSL connection is pushed down the stack into the TCP layer.

Using IBM's Application Transparent Transport Layer Security (AT-TLS)

Configure the AT-TLS rules for the policy agent (PAGENT) using an appropriate client and the z/OS Management Facility (z/OSMF) Together with SSL parameters (to provide certificates stored in z/OS as RACF keyrings) define AT-TLS rules, for example by using the application bigo name and local TCP port number. If the rules match, the TCP connection is turned into an SSL connection Refer to your IBM documentation for more information, for example the IBM Red-book *Communications Server for z/OS VxRy TCP/IP Implementation Volume 4: Security and Policy-Based Networking*.



- 1 Client to interact with z/OS Management Facility (z/OSMF).
- AT-TLS rules are defined with z/OSMF policy management.
- Oscillation of the story of
- 4 Policy Agent, MVS task PAGENT, provides AT-TLS rules through a policy enforcement point (PEP) to TCP/IP stack.
- 6 Application using TCP connection.
- 6 If AT-TLS rules match, the TCP connection is turned into an SSL connection.

Notes:

- 1. The client 1 may vary per operating system, for example a Web browser for z/OS 2.1.
- 2. z/OSMF 2 includes other administration and management tasks in addition to policy management.
- 3. Policy Management 3 includes other rules, such as IP filtering, network address translation etc.

> To set up SSL with AT-TLS

- To operate with SSL, certificates need to be provided and maintained. Depending on the platform, Software AG provides default certificates, but we strongly recommend that you create your own. See *SSL/TLS Sample Certificates Delivered with EntireX* in the EntireX Security documentation.
- 2 Modify broker-specific attributes. Configure the Broker to use TCP:

```
DEFAULTS = BROKER
...
TRANSPORT = TCP

DEFAULTS = TCP
PORT = 1958
```

See also *Setting up TCP/IP Transport*.

- Configure AT-TLS to turn the TCP/IP connection to an SSL connection, using a client to interact with the z/OS Management Facility (z/OSMF). The outcome of this configuration is a Policy Repository with AT-TLS rules stored as z/OS files. This file is the configuration file for the Policy Agent, MVS task PAGENT.
- 4 Make sure the SSL clients connecting to the broker are prepared for SSL connections as well. See *Using SSL/TLS with EntireX Components*.

Migration from Broker's Direct SSL/TLS Support to AT-TLS

- Steps
- z/OSMF Considerations

Example

Steps

> To migrate to AT-TLS

1 Migrate Broker SSL port to TCP.

Move the PORT=value line from the DEFAULTS=SSL section to the DEFAULTS=TCP section in the Broker attribute file to establish it as TCP/IP server port to be controlled by the Policy Agent PAGENT and TCP stack.

After this step you can delete the DEFAULTS=SSL section in the Broker attribute file.

2 Migrate Broker SSL attributes KEY-LABEL and TRUST-STORE.

Configure AT-TLS to turn the TCP/IP connection to an SSL connection, using a client to interact with the z/OS Management Facility (z/OSMF). The outcome of this configuration is a Policy Repository with AT-TLS rules stored as z/OS files. This file is the configuration file for the Policy Agent, MVS task PAGENT.

Part of this configuration is to provide the value of the Broker SSL attributes:

- KEY-LABEL as value of parameter CertificateLabel in the policy statement TTLSConnectionAdvancedParms, for example CertificateLabel ExxAppCert.
- TRUST-STORE as value of parameter Keyring in the policy statement TTLSKeyringParms, for example Keyring EXX/EXXRING.

z/OSMF Considerations

General steps to perform in the Network Configuration Assistant of the z/OS Management Facility:

- 1. Create a new Traffic Descriptor and specify
 - the local port for an SSL server (Broker) or remote port for an SSL client (EntireX client or server)
 - the TCP connect direction (inbound for the Broker and outbound for an EntireX client or server)
 - the AT-TLS handshake role (server for the Broker or client for EntireX client or server)

You can specify the jobname to define the connection to the Broker. You also need to define the existing RACF keyring (format user ID/keyring) or OMVS keystore.

2. Expand or create a new Requirement Map to map the new Traffic Descriptor to an existing security level.



Note: The client and server need to use the same security protocol.

3. Create a new rule for the specific TCP/IP stack based on the Requirement Map. Install and activate the rule, using the PAGENT.

For more information on z/OSMF, see your IBM documentation.

Example

The following is an excerpt of a Policy Agent, MVS task PAGENT configuration file defining a Broker TCP/IP port as secure SSL port as outcome of this configuration:

```
TTLSRule
                                 ConnRule01~33
     LocalAddr
                                      ALL
      RemoteAddr
                                     ALL
      LocalPortRangeRef
                                     portR1
      RemotePortRangeRef
                                     portR2
      Jobname
                                     <job_name> e.g. ETBNUC
     Direction
                                     Inbound
      Priority
                                     223
     TTLSConnectionActionRef
                                    cAct1
     TTLSEnvironmentActionRef
                                     eAct1
     TTLSGroupActionRef
                                     gAct1
    TTLSConnectionAction
                                     cAct1
     HandshakeRole
                                     Server
     TTLSCipherParmsRef
                                     cipher1
      TTLSConnectionAdvancedParmsRef cAdv1
     CtraceClearText
                                     Off
      Trace
                                      6
    TTLSEnvironmentAction
                                     eAct1
     HandshakeRole
                                     Server
      EnvironmentUserInstance
      TTLSKeyringParmsRef
                                      keyR1
    TTLSGroupAction
                                      gAct1
     TTLSEnabled
                                      0n
    TTLSConnectionAdvancedParms
                                      cAdv1
      CertificateLabel
                                      <certificate_label> e.g. ExxAppCert
      SecondaryMap
                                      0ff
                                      0ff
      SSLv3
      TLSv1
                                      0n
```

```
TLSv1.1
                                    0n
  TLSv1.2
                                    0n
TTLSKeyringParms
                                    keyR1
                                    <user_id / keyring> e.g. EXX/EXXRING
  Keyring
PortRange
                                    portR1
  Port
                                    <port_number> e.g. 1958
PortRange
                                    portR2
  Port
                                    1024-65535
CipherParms
                                    cipher1
  V3CipherSuites
                                   TLS_RSA_WITH_AES_256_GCM_SHA384
  V3CipherSuites
                                    TLS_DHE_RSA_WITH_3DES_EDE_CBC_SHA
```

In this example, EntireX Broker is configured to establish TCP/IP port 1958 and the Policy Agent gets instructions to make 1958 an SSL server port.

Therefore, section <code>TTLSRule</code> needs <code>LocalPortRangeRef</code> set to port 1958 and <code>RemotePortRangeRef</code> set to ports 1024-65535. The jobname of the Broker is needed, and the <code>Direction</code> of an SSL server port is <code>Inbound</code>.

The TTLSRule also refers to the following sections:

- TTLSConnectionActionRef defines the HandshakeRole Server and refers to cipher parameters and advanced parameters for the connection
- TTLSEnvironmentActionRef defines the HandshakeRole Server and refers to the Keyring parameter
- TTLSGroupActionRef defines TTLSEnabled On

Advanced parameters for the connection define the sample CertificateLabel value ExxAppCert and the protocols to be used or not to be used.

The Keyring parameter specifies the RACF keyring using the following format: USER-ID / KEY-RING-NAME.

Setting up Entire Net-Work/Adabas SVC Transport

> To set up EntireX Net-Work communication mechanism

- 1 Ensure that all load libraries in the Broker kernel steplib are APF-authorized.
- 2 Ensure that appropriate values are supplied in the Broker attribute file section <code>DEFAULTS=NET</code>, paying particular attention to the IUBL parameter which specifies the maximum send/receive buffer length that can be sent between an application and Broker kernel within a single request and NABS, which governs the total amount of storage available concurrently for all users communicating over this transport mechanism. See <code>Adabas SVC/Entire Net-Work-specific Attributes</code>.
- 3 Ensure that communication with the EntireX Broker is possible by running the installation verification programs using transport type NET. See *Sample Programs for Client (BCOC) and Server (BCOS)* in the z/OS Installation documentation.

Starting and Stopping the Broker

To start the Broker

- 1 Create a user ID for the started task or job where your Broker kernel is going to run.
- If you are using a started task, ensure that the user ID is defined in the list of user IDs for started tasks and that the sample Broker kernel JCL is modified appropriately to create a PROC.
- 3 Start the Broker kernel either from the Broker kernel job (JCL) or started task (PROC).

> To stop the Broker

■ Issue the operator command P <JOBNAME>

Or:

Execute the ETBCMD utility using the example syntax below:

```
//ETBCMD EXEC PGM=ETBCMD,
// PARM=('/-bhost:port:TCP ',
// '-cSHUTDOWN -dBROKER -xuid -ypwd')
```

See Operator Commands for a full list and also Broker Command-line Utilities.

Dual Command Log Files

Command logging is a feature to assist in debugging Broker ACI applications. A command in this context represents one user request sent to the Broker and the related response of Broker.

Broker uses two command log files, enabling data to be written to one of the files while the other is being copied for archival purposes. Two file names must be specified for the dual command logs. At startup, Broker initializes both files and keeps the first open for printing command log data. Broker kernel switches to the other command log when the first file becomes full - or when the size of the open file reaches the value optionally specified by CMDLOG-FILE-SIZE (specified in KB).



Note: It is always advisable to copy the contents of a full command log file before Broker fills the subsequent command log file. Otherwise, the information in the first file (full and closed) will be overwritten.

The file requirements are two equally sized, physical sequential files defined with a record length of 121 bytes, i.e.

DCB=(LRECL=121, RECFM=PS, BLKSIZE=nnnn). We recommend you allocate files with a single (primary) extent only. For example SPACE=(CYL, (30,0)). The minimum file size is approximately 3 cylinders of 3390 device.

Alternatively, the dual command log files can be allowed in USS HFS file system.

For more information, see *Command Logging in EntireX*.

Tracing EntireX Broker

This section covers the following topics:

- Broker TRACE-LEVEL Attribute
- Attribute File Trace Setting
- Deferred Tracing
- Dynamically Switching On or Off the EntireX Broker Trace

Flushing Trace Data to a GDG Data Set

Broker TRACE-LEVEL Attribute

The Broker TRACE-LEVEL attribute determines the level of tracing to be performed while Broker is running. The Broker has a master TRACE-LEVEL specified in the Broker section of the attribute file as well as several individual TRACE-LEVEL settings that are specified in the following sections of the attribute file.

Individual Settings	Specified in Attribute File Section	Note
Master trace level	DEFAULTS=BROKER	1,2
Persistent store trace level	DEFAULTS=ADABAS CTREE DIV	1
Conversion trace level	DEFAULTS=SERVICE; Trace option of the service-specific broker attribute CONVERSION.	
Security trace level	DEFAULTS=SECURITY	1
Transport trace level	DEFAULTS=NET TCP SSL	1
Application Monitoring trace level	DEFAULTS=APPLICATION-MONITORING	



Notes:

- 1. For temporary changes to the master or individual TRACE-LEVEL without restarting the Broker, use the Broker command-line utility ETBCMD.
- 2. For temporary changes to the master TRACE-LEVEL without restarting the broker, use operator command TRACE.

Attribute File Trace Setting

Trace Level	Description
0	No tracing. Default value.
1	Traces incoming requests, outgoing replies, and resource usage.
2	All of Trace Level 1, plus all main routines executed.
3	All of Trace Level 2, plus all routines executed.
4	All of Trace Level 3, plus Broker ACI control block displays.

Note: Trace levels 2 and above should be used only when requested by Software AG Support.

Deferred Tracing

It is not always convenient to run with TRACE-LEVEL defined, especially when higher trace levels are involved. Deferred tracing is triggered when a specific condition occurs, such as an ACI response code or a broker subtask abend. Such conditions cause the contents of the trace buffer to be written, showing trace information leading up the specified event. If the specified event does not occur, the Broker trace will contain only startup and shutdown information (equivalent to TRACE-LEVEL=0). Operating the trace in this mode requires the following additional attributes in the broker section of the attribute file. Values for TRBUFNUM and TRAP-ERROR are only examples.

Attribute	Value	Description			
TRBUFNUM	3	Specifies the deferred trace buffer size = 3 * 64 K.			
TRMODE WRAP Indicates trace is not written until an event occurs.					
TRAP-ERROR	322	Assigns the event ACI response code 00780322 "PSI: UPDATE failed".			

Dynamically Switching On or Off the EntireX Broker Trace

The following methods are available to switch on or off the EntireX Broker trace dynamically. You do not need to restart the broker for the changes to take effect.

■ ETBCMD

Run command utility ETBCMD with option - c TRACE-ON or - c TRACE-OFF. See ETBCMD.

Operator Command

Issue an operator command. See TRACE.

See also Deferred Tracing.

Flushing Trace Data to a GDG Data Set

With broker-specific attributes TRMODE=WRAP and TRBUFNUM=*n*, Broker writes trace data to internal buffers instead of stderr (DD:SYSOUT). These buffers are used in round-robin mode and do not involve any I/O operation. If you need trace data for diagnostic purposes, use the operator command FLUSH to write the trace data from the internal buffers to a data set. A FLUSH command is performed automatically in case of error exceptions. The output data set is not readable for any other user when the broker is running. To avoid this problem, you can use a GDG (generation data group) data set as output data set. First you must allocate the GDG and define it to the broker. These preparatory steps are outlined below. The GDG name EXX.GDG is used in the examples.



Note: GDG is supported for deferred tracing only.

- Allocating a GDG
- Defining the GDG to Broker

Writing to the GDG Data Set

Allocating a GDG

Define the GDG with IDCAMS. This definition is needed before working with the GDG data sets. You can use the following JCL to define a GDG. The LIMIT parameter is set to 16, but may contain other values according to your needs.

```
//IDCAMS EXEC PGM=IDCAMS,REGION=4096K
//SYSPRINT DD SYSOUT=*
//SYSIN DD *
   DEFINE GENERATIONDATAGROUP -
   (NAME(EXX.GDG) -
   NOEMPTY -
   SCRATCH -
   LIMIT(16))
/*
```

Defining the GDG to Broker

The GDG data set as target for trace data can be managed without changes to the Broker JCL. However, the DD statement for such a GDG data set has to be defined as a Broker attribute in order to propagate the file characteristics to the runtime library of the IBM Language Environment.

See TRACE-DD under Broker-specific Broker Attributes.

Writing to the GDG Data Set

After successful broker initialization, a new data set of the GDG is allocated and opened. Based on the defined GDG name EXX.GDG in the sample JCL above, data set names EXX.GDG.G0001V00, EXX.GDG.G0002V00, EXX.GDG.G0003V00 and so on will be allocated and written.

Use operator command FLUSH to write all trace data from internal buffers to the GDG data set. The data set will be closed at the end of the FLUSH processing, and the next GDG data set is allocated and opened. During broker shutdown, the GDG data set is filled with all available trace data and closed.

Protecting a Broker against Denial-of-Service Attacks

An optional feature of EntireX Broker is available to protect a broker running with SECURITY=YES against denial-of-service attacks. An application that is running with invalid user credentials will get a security response code. However, if the process is doing this in a processing loop, the whole system could be affected. If PARTICIPANT-BLACKLIST is set to YES, EntireX Broker maintains a blacklist to handle such "attacks". If an application causes ten consecutive security class error codes within 30 seconds, the blacklist handler puts the participant on the blacklist. All subsequent requests from this participant are blocked until the BLACKLIST-PENALTY-TIME has elapsed.

Server Shutdown Use Case

Here is a scenario illustrating another use of this feature that is not security-related.

An RPC server is to be shut down immediately, using Broker Command and Information Services (CIS), and has no active request in the broker. The shutdown results in the LOGOFF of the server. The next request that the server receives will probably result in message 00020002 "User does not exist", which will cause the server to reinitialize itself. It was not possible to inform the server that shutdown was meant to be performed.

With the *blacklist*, this is now possible. As long as the blacklist is not switched off, when a server is shut down immediately using CIS and when there is no active request in the broker, a marker is set in the blacklist. When the next request is received, this marker results in message 00100050 "Shutdown IMMED required", which means that the server is always informed of the shutdown.

Setting the Time Zone for Broker

Broker obtains the time zone value by reading the environment variable $\top Z$. If not specified, Broker retrieves the assignment of $\top Z$ from the configuration file /etc/profile.

Check your /etc/profile for an appropriate setting of environment variable TZ. The TZ value should reflect the appropriate value for your location.

Remember that the new Daylight Saving Time rule according to the Energy Policy Act in the U.S. takes effect in 2007. If you live in an area affected by the new rule, you may append it to the TZ environment variable.

For example, TZ=EST5EDT, M4.1.0, M10.5.0 is no longer valid. TZ=EST5EDT, M3.2.0, M11.1.0 must be used instead.

If you don't want to change your /etc/profile, you may configure Broker's startup JCL to define environment variable TZ. Modify the EXEC statement thus:

```
//BROKER EXEC PGM=ETBNUC, REGION=OM, TIME=1440,
// PARM='ENVAR(''TZ=EST5EDT, M3.2.0, M11.1.0'')/'
```

The value of $\top Z$ should reflect the appropriate value for your location. Put the time zone value in quotation marks and parentheses, as outlined above. The rule for daylight saving time changes can be appended after the time zone value.

Achieving FIPS Compliance

The z/OS operating system can be configured to run EntireX Broker FIPS 140-2 compliant. This requires changes in the following system components:

- AT-TLS (Application Transparent Transport Layer Security)
- System SSL
- ICSF (z/OS Integrated Cryptographic Service Facility)

The TCP/IP port of Broker must run under the control of AT-TLS, and all applications using Broker need the Secure Socket Layer protocol (TLS/SSL) as transport. You do not need to change the attribute file of Broker.

The IBM support pages provide the document *Setting up AT-TLS for FIPS 140 mode.pdf*. It contains an overview of necessary system changes and describes the steps in detail.

3 Broker Attributes

Name and Location of Attribute File	21
Attribute Syntax	
Broker-specific Attributes	
Service-specific Attributes	
Codepage-specific Attributes	
Adabas SVC/Entire Net-Work-specific Attributes	
Security-specific Attributes	
■ TCP/IP-specific Attributes	68
c-tree-specific Attributes	
SSL/TLS-specific Attributes	73
■ DIV-specific Attributes	
Adabas-specific Attributes	80
Application Monitoring-specific Attributes	
Authorization Rule-specific Attributes	83
■ Variable Definition File	84



Note: This section lists all EntireX Broker parameters. Not all parameters are applicable to all supported operating systems.

The Broker attribute file contains a series of parameters (attributes) that control the availability and characteristics of clients and servers, as well as of the Broker itself. You can customize the Broker environment by modifying the attribute settings.

Name and Location of Attribute File

The name and location of the broker attribute file is platform-dependent.

Platform	File Name/Location
z/OS	Member <i>EXBATTR</i> in the EntireX Broker source library.

Attribute Syntax

Each entry in the attribute file has the format:

ATTRIBUTE-NAME=value

The following rules and restrictions apply:

- A line can contain multiple entries separated by commas.
- Attribute names can be entered in mixed upper and lowercase.
- Spaces between attribute names, values and separators are ignored.
- Spaces in the attribute names are not allowed.
- Commas and equal signs are not allowed in value notations.
- Lines starting with an asterisk (*) are treated as comment lines. Within a line, characters following an * or # sign are also treated as comments.
- The CLASS keyword must be the first keyword in a service definition.
- Multiple services can be included in a single service definition section. The attribute settings will apply to all services defined in the section.
- Attributes specified after the service definition (CLASS, SERVER, SERVICE *keywords*) overwrite the default characteristics for the service.
- Attribute values can contain variables of the form \${variable name} or \$variable name:
 - Due to variations in EBCDIC codepages, braces should only be used on ASCII (UNIX or Windows) platforms or EBCDIC platforms using the IBM-1047 (US) codepage.
 - The variable name can contain only alphanumeric characters and the underscore (_) character.
 - The first non-alphanumeric or underscore character terminates the variable name.
 - Under UNIX and Windows, the string \${variable name} is replaced with the value of the corresponding environment variable.
 - On z/OS, variable values are read from a file defined by the DD name ETBVARS. The syntax of this file is the same as the attribute file.

- If a variable has no value: if the variable name is enclosed in braces, error 00210594 is given, otherwise \$variable name will be used as the variable value.
- If you encounter problems with braces (and this is quite possible in a z/OS environment), we suggest you omit the braces.

Broker-specific Attributes

The broker-specific attribute section begins with the keyword DEFAULTS=BROKER. It contains attributes that apply to the broker. At startup time, the attributes are read and duplicate or missing values are treated as errors. When an error occurs, the broker stops execution until the problem is corrected.



Tip: To avoid resource shortages for your applications, be sure to specify sufficiently large values for the broker attributes that define the global resources.

	Values	Opt/		Operating System		
Attribute		Req	z/OS	UNIX	Windows	BS2000
ABEND-LOOP-DETECTION	YES I NO	0	z	u	w	b
	YES Stop broker if a task term at the same abend location abend loop.		-			
	known error leads to an	NO Use only if requested by Software AG Support. This setting may make sense if a known error leads to an abnormal termination, but a hotfix solving the problem has not yet been provided. Reset to YES when the hotfix has been installed.				
ABEND-MEMORY-DUMP	YES I NO	О	z	u	w	b
	YES Print all data pools of the broker if a task terminates abnormally. This dumneeded to analyze the abend.NO If the dump has already been sent to Software AG, you can set to NO to avoi extra overhead.				-	
ACCOUNTING	<u>NO</u> I 128-255	О	Z			
	NO YES[SEPARATOR=char]	О		u	W	b
	Determines whether accounting		are created.			
	NO Do not create accounting records. nnn The SMF record number to use when writing the accounting records.					
	YES Create accounting data. char=separator characte using the SEPARATOR su ACCOUNTING = (YES, If no separator character	er(s). Up to boption, for SEPARATOR	seven sepa r example: R=;)	rator chara	cters can be	e specified
	See also <i>Accounting in EntireX</i> documentation.	-				
ACCOUNTING-VERSION	1 2 3 4 5	О	Z	u	W	b

		Opt/ Op						
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000		
	Determines whether accounting	ng records	are created.					
	1 Collect accounting information. This value is supported for reasons of compatibility with EntireX Broker 7.2.1 and below.							
	2 Collect extended accounting information in addition to that available with option							
	3 Create accounting records in layout of version 3.							
	4 Create accounting records in layout of version 4.							
	5 Create accounting records i	5 Create accounting records in layout of version 5.						
	This parameter applies when	ACCOUNTIN	NG is activate	ed.				
ACI-CONVERSION	YES I NO	О	Z	u	w	b		
	Determines the handling of A	CI request	and respons	se strings o	of USTATUS			
	 YES Convert ACI request and response strings with ICU. See ICU Conver Internationalization documentation. NO Translate ACI request and response with internal translation table with of national characters. See Translation User Exit in the Internationali documentation. Note: This attribute was undocumented in EntireX versions prior to 10.3 default value NO. This meant that a translation user exit was used instead 							
	longer recommended.	r	1			r		
APPLICATION-MONITORING	YES I <u>NO</u>	О	Z	u	W	b		
or APPMON	Enable application monitoring	g in EntireX	(Broker.					
	YES Enable application monitoring.							
	NO Disable application monitoring.							
	See the separate Application Monitoring documentation.							
AUTOLOGON	YES I NO	0	z	u	w	ь		
	YES LOGON occurs automatica NO The application has to iss			ND or REGI	STER.			
AUTOSTART	NO I YES	О		u	w			
	This attribute defines the autostart behavior of a broker.							
	NO Broker is <i>not</i> started autor	•		•				

			Operating System					
Attribute	Values	Opt/ Req	z/OS	UNIX	Windows	BS2000		
	Note: Prior to EntireX version	1 10.5 this w	ı zas handled	by the Bro	ı ker Admini	istration		
	Service.			,				
BLACKLIST-PENALTY-TIME	<u>5M</u> <i>n</i> <i>n</i> S <i>n</i> M <i>n</i> H	R	z	u	w	b		
	Define the length of time a participant is placed on the PARTICIPANT-BLACKLIST to prevent a denial-of-service attack.							
	<i>n</i> Same as <i>n</i> S.							
	nS Non-activity time in secon	nds (max. 2	147483647).					
	nM Non-activity time in minu	ites (max. 3	5791394).					
	n ∈ Non-activity time in hours	s (max. 596	523).					
	See <i>Protecting a Broker against Denial-of-Service Attacks</i> in the platform-specific Administration documentation.							
BROKER-ID	A32	R	Z	u	W	b		
	Identifies the broker to which the attribute file applies. The broker ID must be unique per machine.							
	Note: The numerical section of the BROKER-ID is no longer used to determine the DBID in the EntireX Broker kernel with Entire Net-Work transport (NET). To determine the DBID, use attribute NODE in the DEFAULTS=NET section of the attribute file.							
CLIENT-NONACT	15M n nS nM nH	R	z	u	w	b		
	Define the non-activity time for	or clients.						
	n Same as n S.							
	nS Non-activity time in seconds (max. 2147483647).							
	nM Non-activity time in minutes (max. 35791394).							
	nH Non-activity time in hours (max. 596523).							
	A client that does not issue a broker request within the specified time limit is treated as inactive and all resources for the client are freed.							
CMDLOG	NO I YES	О	z	u	w	b		
	NO Command logging will not be available in the broker. YES Command logging features will be available in the broker.							
CMDLOG-FILE-SIZE	<u>1024</u> <i>n</i>	О	z	u	w	b		
	Defines the maximum size of The value must be 1024 or hig file grows to this size, broker so Command Logging in EntireX.	ther. The de	fault value	is 1024. Wh	nen one con	nmand log		
CONTROL-INTERVAL	60S n nS nM nH	О	z	u	w	b		
		l	L	1	L	Ĭ.		

Attribute		Opt/		Operatin	g System			
	Values	Req	z/OS	UNIX	Windows	BS2000		
	Defines the time interval of t	ime-driven b	roker-to-b	roker calls.				
	1. It controls the time between handshake attempts.							
	2. The standby broker will control-INTERVAL time		us of the st	andard bro	ker after the	e elapsed		
	<i>n</i> Same as <i>n</i> S.							
	nS Interval in seconds (max	. 2147483647	·).					
	nM Interval in minutes (max	a. 35791394).						
	nH Interval in hours (max. 5	96523).						
	The minimum value is 16 seconds), except for very slo		0,	mmend the	e default val	ue (60		
CONV-DEFAULT	UNLIM I n	О	z	u	w	b		
DEFERRED	UNLIM The number of conversations is restricted only by the number of conversation globally available. Precludes the use of NUM-CONVERSATION. **Number of conversations.** This value can be overridden by specifying a CONV-LIMIT for the service. A value of 0 (zero) is invalid. **NO YES							
DYNAMIC-MEMORY- MANAGEMENT	YES An initial portion of memory is allocated at broker startup based on defined NUM-* attributes or internal default values if no NUM-* attributes have been defined. More memory is allocated without broker restart if there is a need to use more storage. Unused memory is deallocated. The upper limit of memory consumption can be defined by the attribute MAX-MEMORY. See <i>Dynamic Memory Management</i> under <i>Broker Resource Allocation</i> in the platform-independent Administration documentation. NO All memory is allocated at broker startup based on the calculation from the defined NUM-* attributes. Size of memory cannot be changed. This was the know behavior of EntireX 7.3 and earlier.							

Attribute		Opt/	Operating System						
	Values	Req	z/OS	UNIX	Windows	BS2000			
	If you run your broker with attribute DYNAMIC-MEMORY-MANAGEMENT=YES, the following attributes are not needed:								
	■ CONV-DEFAULT	■ NUM-CONV[ERSATION]						
	■ HEAP-SIZE	■ NUM-LONG[-BUFFER]						
	■ LONG-BUFFER-DEFAULT	■ NUM-SERVE	.R						
	■ SERVER-DEFAULT	■ NUM-SERVIC	CE-EXTENSI	NC					
	■ SHORT-BUFFER-DEFAULT	■ NUM-SERVI	CE						
	■ NUM-CLIENT	■ NUM-SHORT	[-BUFFER]						
	■ NUM-CMDLOG-FILTER	■ NUM-UOW MA	X-UOWS MU	DW					
	■ NUM-COMBUF	■ NUM-WQE							
	Caution: However, if one of size of that particular brok		tes is define	ed, it deter	mines the al	location			
DYNAMIC-WORKER-	NO I YES	0	Z	u	w	b			
	NO All worker tasks are started at broker startup. The number of worker tasks is defined by NUM-WORKER. After this initial step, no further worker tasks can be started. This is default and simulates the behavior of EntireX version 8.0 and earlier. YES As above, the initial portion of worker tasks started at broker startup is determined by NUM-WORKER. However, if there is a need to handle an increased workload, additional worker tasks can be started at runtime without restarting broker. Conversely, if a worker task remains unused, it is stopped. The upper and lower limit of running worker tasks can be defined by the attributes WORKER-MIN and WORKER-MAX. If you run broker with DYNAMIC-WORKER-MANAGEMENT=YES, the following attributes are useful to optimize the overall processing: WORKER-MAX WORKER-MIN WORKER-NONACT WORKER-QUEUE-DEPTH WORKER-START-DELAY The attribute NUM-WORKER defines the initial number of worker tasks started during initialization. See <i>Dynamic Worker Management</i> .								
ETBCOM	NO I YES	О	z	u	w				
	YES I NO	О				b			
	Bundles the output of the	various broker	tasks in tas	k ETBCOM.					
FORCE	<u>NO</u> I YES	О		u					

Attribute	Values	Opt/	Operating System						
		Req	z/OS	UNIX	Windows	BS2000			
	NO Go down with error if IPC resources still exist. YES Clean up the left-over IPC resources of a previous run.								
	Note: 1. If broker is started twice, the second instance will kill the first by removing the I resources.								
	2. For z/OS and BS2000, see se	eparate attr	ibute FORC	E under <i>DE</i>	FAULTS=NE	T.			
HEAP-SIZE	<u>1024</u> <i>n</i>	О	z	u	w	b			
	Defines the size of the internal heap in KB. Not required if you are using DYNAMIC-MEMORY-MANAGEMENT. If you are <i>not</i> using dynamic memory managemen we strongly recommend specifying - as a minimum - the default value of 1024 KB.								
ICU-CONVERSION	YES I NO	О	z	u	w	b			
	YES ICU is loaded and availance CONVERSION=SAGTCHA and NO ICU is not loaded and not CONVERSION=SAGTRPC of If any of the broker service de Conversion, that is, CONVERSIO must be set to YES. If you are in the Internationalization document approach for all your brokers ICU requires additional storage ICU-CONVERSION to NO will here.	end CONVER ot available cannot be use finitions use N=SAGTCHA using only cumentation service definate to run pro-	for conversed. sees the chara or CONVERS a user exit (a) or CONVER initions, ICU	acter conversions SION=SAGTI (see User Exersion=NO and	rsion appro RPC, ICU-CO cits under In s character ION can be so n is not need consumption	pach ICU DNVERSION atroduction conversion set to NO. ded, setting			
ICU-DATA-DIRECTORY	Folder or directory name in quotes.	O	Z	u	W	71			
	The location where the broker searches for ICU custom converters. See <i>Building and Installing ICU Custom Converters</i> in the platform-specific Administration documentation.								
ICU-SET-DATA-DIRECTORY	YES I NO	О	Z	u	w				
TDVC	Disable or enable ICU custom converter usage. YES The broker tries to locate ICU custom converters with the mechanism defined by the platform. See <i>Building and Installing ICU Custom Converters</i> in the platform-specific Administration documentation. NO Use of ICU custom converters is not possible.								
IPV6	YES I NO	0	Z	u	W	b			

Attribute		Opt/	Operating System							
	Values	Req	z/OS	UNIX	Windows	BS2000				
	YES Establish SSL and TCP/IP transport in IPv6 and IPv4 networks according to the TCP/IP stack configuration.									
	NO Establish SSL and TCP/I	NO Establish SSL and TCP/IP transport in IPv4 network only.								
	This attribute applies to Entire	eX version	9.0 and abc	ove.						
LONG-BUFFER-DEFAULT	UNLIM I n	О	z	u	W	b				
	Number of long buffers to be	allocated fo	or each serv	rice.						
	 UNLIM The number of long message buffers is restricted only by the number globally available. Precludes the use of NUM-LONG-BUFFER. n Number of buffers. This value can be overridden by specifying a LONG-BUFFER-LIMIT for the 									
l	value of 0 (zero) is invalid.									
MAX-MEMORY	<u>O</u> n nK nM nG UNLIM	О	z	u	W	b				
	Defines the upper limit of med DYNAMIC-MEMORY-MANAGEME 0, UNLIM No memory limit. others Defines the maximum 671 "Requested allowed and the state of the state o	ENT=YES has	s been defin	ned. nemory. If l						
MAX-MESSAGE-LENGTH	<u>2147483647</u> <i>n</i>	О	Z	u	W	b				
	Maximum message size that the broker kernel can process. This value is transport-dependent. The default value represents the highest positive number that can be stored in a four-byte integer.									
MAX-MESSAGES-IN-UOW	<u>16</u> <i>n</i>	О	z	u	w	b				
	Maximum number of message	es in a unit	of work.			L				
MAX-MSG	See MAX-MESSAGE-LENGTH.									
MAX-TRACE-FILES	<u>4</u> <i>n</i>	О		u	W					
	Defines the number of backup 1; maximum is 999. A new trac is exceeded. These two attribu File Handling under UNIX W	ce file is allo ites prevent	ocated wher	n the value	for TRACE-F	FILE-SIZE				
MAX-UOW-MESSAGE-LENGTH	See MAX-MESSAGE-LENGTH.									
MAX-UOWS	<u>0</u> <i>n</i>	О	z	u	W	b				
	The maximum number of UO default value is 0 (zero), which are not part of a unit of work. MAX-UOWS value must be 1 or	ch means tha . If UOW pr	at the broke rocessing is	er will prod	cess only me	ssages tha				

Attribute		ng System	System					
	Values	Opt/ Req	z/OS	UNIX	Windows	BS2000		
	The MAX - UOWS value for the se is an alias of this parameter.	rvice will d	efault to the	value set f	or the broke	r. NUM-UOW		
MESSAGE-CASE	NONE I UPPER I LOWER	О	z	u	w	b		
	Indicates if certain error message texts returned by the broker to its clients or written by the broker to its log file are to be in mixed case, uppercase, or lowercase. NONE No changes are made to message case.							
	UPPER Messages are changed							
	LOWER Messages are changed	to lowerca	ase.					
MUOW	See NUM-UOW.	T	T	1				
NEW-UOW-MESSAGES	YES I NO	О	Z	u	W	b		
NUM-BLACKLIST-ENTRIES	NO New UOW messages are not allowed. This applies to UOW when using Persistence and should not be used for non-persistent UOWs. A usage example could be the following: The broker persistent store reaches capacity and the broker shuts down. You can set NEW-UOW-MESSAGES to NO to prevent new UOW messages from being added after a broker restart. This action allows only consumption (not production) of UOWs to occur after broker restart. After the persistent store capacity has been sufficiently reduced, the EntireX Broker administrator can issue a CIS command, see ALLOW-NEWUOWMSGS. This action allows new UOW messages to be sent to the broker. Reset attribute NEW-UOW-MESSAGES to YES, which permits new UOW messages to be produced in subsequent broker sessions.							
NUM-BLACKLIST-ENTRIES	Number of entries in the parti with BLACKLIST-PENALTY-T to protect a broker running w Protecting a Broker against Denia documentation.	IME and PAI ith SECURI	RTICIPANT TY=YES aga	-BLACKLIS ainst denial	T, this attrib -of-service a	oute is used attacks. See		
NUM-CLIENT	n	R	Z	u	W	b		
	Number of clients that can acc	ess the brol	ker concurre	ently. A val	ue of 0 (zero)) is invalid.		
NUM-CMDLOG-FILTER	1 <i>n</i> Maximum number of filters the	O nat can be s	z pecified sin	u nultaneous	w ly.	b		
	Tip: We recommend you limi monitored. Minimum value is is set to YES. See <i>Command Log</i> more information.	t this value s 1. A value	to the num	ber of serv	ices that are n the attribu	ıte CMDLOG		

Opt/ Operating System							
Values	Req	z/OS	UNIX	Windows	BS2000		
<u>1024</u> I 1-999999	R	z	u	w	b		
Determines the maximum number of communication buffers available for processing commands arriving in the broker kernel. The size of one communication buffer is usually 16 KB split into 32 slots of 512 bytes, but it ultimately depends on the hardware architecture of your CPU. A value of 0 (zero) is invalid.							
n I AUTO	R	Z	u	w	b		
 specified should be high enough to account for both conversational and non-conversational requests. (Non-conversational requests are treated internally as one-conversation requests.) n Number of conversations. AUTO Uses the CONV-DEFAULT and the service-specific CONV-LIMIT values to calculate the number of conversations. Do not set the values used in the calculation to UNLIM. Note: 1. A value of 0 (zero) is invalid. If a wildcard service is defined in the service-specific section of the attribute file, the value of AUTO is invalid. 							
1096 L n L AUTO	R	7	11	147	b		
length of 4096 bytes and are uses toring a request of 8192 bytes, n Number of buffers. AUTO Uses the LONG-BUFFER values to calculate the report Do not set the values used. A value of 0 (zero) is invalid. In non-conversational mode, mea reply from the server. If no resoon as the server receives the	sed to store for example - DEFAULT anumber of lesed in the cossage contacted by the cost of the cost o	e requests the, would recond the serve long messagalculation t	hat are larg quire two lo ice-specific ge buffers. o UNLIM. leased as so ssage conta	er than 2048 ong message LONG-BUFF on as the clie iners are rel	B bytes. containers. ER-LIMIT ent receives eased as		
	Determines the maximum nucommands arriving in the brousually 16 KB split into 32 slot architecture of your CPU. A volume of your CPU. A volume of the number of converse specified should be high enough one-conversational requests. One-conversational requests. One-conversation requests. One-conversation requests. One of the conversation of the values us the number of conversation of the attribute file, 2. See Wildcard Service Define of the attribute file, 2. See Wildcard Service Define of 4096 n AUTO of the number of long malength of 4096 bytes and are us storing a request of 8192 bytes, now not set the values of the value	Values Req 1024 1 - 999999 R Determines the maximum number of corcommands arriving in the broker kernel. usually 16 KB split into 32 slots of 512 byt architecture of your CPU. A value of 0 (z n AUTO R Defines the number of conversations that specified should be high enough to accommon-conversational requests. (Non-conversation requests.) N	Values Req Z/OS	Values Req z/OS UNIX 1024 1 - 999999 R z u Determines the maximum number of communication buffers a commands arriving in the broker kernel. The size of one commusually 16 KB split into 32 slots of 512 bytes, but it ultimately dearchitecture of your CPU. A value of 0 (zero) is invalid. n AUTO R z u Defines the number of conversations that can be active concurr specified should be high enough to account for both conversationn-conversational requests. (Non-conversational requests are one-conversation requests.) n Number of conversations. AUTO Uses the CONV-DEFAULT and the service-specific CONV-LI the number of conversations. Do not set the values used in the calculation to UNLIM. Note: 1. A value of 0 (zero) is invalid. If a wildcard service is defined section of the attribute file, the value of AUTO is invalid. 2. See Wildcard Service Definitions. 4096 n AUTO R z u Defines the number of long message containers. Long message length of 4096 bytes and are used to store requests that are larg Storing a request of 8192 bytes, for example, would require two long a request of 8192 bytes, for example, would require two long as the Long-BUFFER-DEFAULT and the service-specific values to calculate the number of long message buffers. Do not set the values used in the calculation to UNLIM. A value of 0 (zero) is invalid. In non-conversational mode, message c	Values Req Z/OS UNIX Windows 1024 1-999999 R z u w Determines the maximum number of communication buffers available for commands arriving in the broker kernel. The size of one communication bu usually 16 KB split into 32 slots of 512 bytes, but it ultimately depends on the architecture of your CPU. A value of 0 (zero) is invalid. n AUTO R z u w Defines the number of conversations that can be active concurrently. The n specified should be high enough to account for both conversational and non-conversational requests. (Non-conversational requests are treated inte one-conversation requests.) n Number of conversations. AUTO Uses the CONV-DEFAULT and the service-specific CONV-LIMIT values the number of conversations. Do not set the values used in the calculation to UNLIM. Note: 1. A value of 0 (zero) is invalid. If a wildcard service is defined in the service section of the attribute file, the value of AUTO is invalid. 2. See Wildcard Service Definitions. 4096 n AUTO R z u w Defines the number of long message containers. Long message containers he length of 4096 bytes and are used to store requests that are larger than 2048 Storing a request of 8192 bytes, for example, would require two long message on the length of 4096 bytes and are used to store requests that are larger than 2048 Storing a request of 8192 bytes, for example, would		

		Opt/	Operating System				
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000	
	1. If a catch-all service is defir value of AUTO is invalid.	ned in the s	ervice-speci	fic section	of the attrib	ute file, the	
	2. See Wildcard Service Defin	itions.					
NUM-PARTICIPANT-	n	О	z	u	w	b	
EXTENSION	Defines the number of particip	ant extens	ions to link p	participant	s as clients a	nd servers.	
	n Number of partic not specified If this attribute is NUM-CLIENT and	not set, the	e default va	lue is calcu	lated based	on	
	A value of 0 (zero) is invalid.						
NUM-SERVER	n I AUTO	R	z	u	w	b	
	Note: 1. Setting this value higher the replicas that provide the sa 2. A value of 0 (zero) is invalisection of the attribute file, 3. See <i>Wildcard Service Defin</i>	f servers. sed in the contains the number service d. If a wild the value contains.	ralculation to the of services	o UNLIM. ices allows e is defined	the starting	of server ce-specific	
NUM-SERVICE		R	z	u	W	b	
	Defines the number of service number of servers that can off invalid.		0				
NUM-SERVICE-EXTENSION	n I AUTO	О	Z	u	w	b	
	Defines the number of service extensions to link servers to services. Number of service extensions.						
	AUTO Uses the value specified or calculated for NUM-SERVER + NUM-CLIENT, plus an extra cushion.						
	not specified If this attribute is NUM-SERVICE.	not set, the	e default va	lue is NUM-	SERVER mu	ltiplied by	

		g System	em					
Attribute	Values	Opt/ Req	z/OS	UNIX	Windows	BS2000		
	The minimum value is NUM-S		1. 11		0.5			
	The maximum value is NUM-S	ERVER mu l	tiplied by N	IUM-SERVI	CE.			
	Caution is recommended with	n this attrib	ute:					
	Set this attribute only if the to be restricted.	Set this attribute only if the storage resources allocated for service extensions need to be restricted.						
	Note that the value n allows only the specified number of server instances of n to be used.							
	■ Value AUTO will calculate the number of allowed server instances from NUM-SERVER, which itself might be set to AUTO. In this case, this also considers the value of SERVER-DEFAULT and even the individual SERVER-LIMIT for each service definition.							
NUM-SHORT-BUFFER or	n I AUTO	R	Z	u	W	b		
NUM-SHORT	Defines the number of short message containers. Short message containers have length of 256 bytes and are used to store requests of no more than 2048 bytes. Ta request of 1024 bytes, for example, would require four short message contain Number of buffers. AUTO Uses the SHORT-BUFFER-DEFAULT and the service-specific SHORT-BUFFER-LIMIT values to calculate the number of short message b							
	Do not set the values us Note:	sed in the c	alculation t	o UNLIM.				
	1. In <i>non-conversational</i> mode, message containers are released as soon as the client receives a reply from the server. If no reply is requested, message containers are released as soon as the server receives the client request.							
	2. In <i>conversational</i> mode, the received.	last messag	ge received :	is always k	ept until a r	new one is		
	3. If a wildcard service is defir value of AUTO is invalid.	ned in the s	ervice-speci	fic section o	of the attrib	ute file, the		
	4. See Wildcard Service Defin	itions.						
NUM-UOW	<u>0</u>	О	z	u	W	b		
	The maximum number of UOWs that can be concurrently active broker-wide. The default value is 0 (zero), which means that the broker will process only messages that are not part of a unit of work. If UOW processing is to be done by any service, a NUM-UOW value must be 1 or larger for the broker. (MAX-UOWS is an alias for this attribute.)							
	The NUM-UOW value for the ser	vice will d	efault to the	value set f	or the brok	er.		
NUM-WORKER	<u>1</u> n (max. 64)	R	z	u	W	b		

	Opt/ Req	Opt/ Operating System				
Values		z/OS	UNIX	Windows	BS2000	
the number of functions (SENI	D, RECEIVE,	,REGISTER	, etc.) that o	can be proce		
1-32768	R	z	u	w	b	
Maximum number of requests that can be processed by the broker in parallel, over a transport mechanisms. Each broker command is assigned a worker queue element, regardless of the transport mechanism being used. This element is released when the user has received the result of the command, including the case where the command has timed out.						
					h	
					he broker	
NO Do not create a participal See <i>Protecting a Broker against 1</i>	nt blacklist Denial-of-Se		s in the pla	tform-speci	fic	
A32	R	Z	u	w	b	
methods TCP and SSL are sup	ported. See	e Transport-1	method-style	e Broker ID f	_	
<u>90</u> 1-100	О	z	u	w	b	
YES I <u>NO</u>	О	Z	u			
In earlier EntireX versions, the maximum number of TCP/IP connections per communicator was limited; see <i>Maximum TCP/IP Connections per Communicator</i> for platform-specific list. With attribute POLL introduced in EntireX version 9.0, this restriction can be lifted under z/OS and UNIX. NO This setting is used to run the compatibility mode in Broker. The poll() system call is not used. The limitations described under <i>Maximum TCP/IP Connections per Communicator</i> apply. YES The poll() system call is used to lift the resource restrictions with select() in multiplexing file descriptor sets.						
be exceeded by POLL=YES.						
	Number of worker tasks that the number of functions (SENI concurrently. At least one word 1-32768 Maximum number of requests transport mechanisms. Each broker command is assign mechanism being used. This exports of the command, including the YES NO Determines whether participate are to be put on a blacklist. YES Create a participant black NO Do not create a participate Administration documentation A32 This is the address of the load methods TCP and SSL are supdetails. This attribute is required and solution of the communication was limited; see platform-specific list. With attrestriction can be lifted under NO This setting is used to runcall is not used. The limite per Communicator apply YES The poll() system call is multiplexing file descriptors. Note: The maximum number be exceeded by POLL=YES.	Number of worker tasks that the broker can the number of functions (SEND, RECEIVE, concurrently. At least one worker task is: 1-32768 R Maximum number of requests that can be transport mechanisms. Each broker command is assigned a work mechanism being used. This element is re of the command, including the case when YES NO R Determines whether participants attempt are to be put on a blacklist. YES Create a participant blacklist. NO Do not create a participant blacklist. See Protecting a Broker against Denial-of-Se Administration documentation. A32 R This is the address of the load/unload bromethods TCP and SSL are supported. See details. This attribute is required if the at 90 1-100 O Broker will issue a message if the defined (available file descriptors) is exceeded. Dedescriptors. YES NO O In earlier EntireX versions, the maximum communicator was limited; see Maximum platform-specific list. With attribute POLD restriction can be lifted under z/OS and U NO This setting is used to run the compactal is not used. The limitations descriptor restriction can be lifted under z/OS and U NO This setting is used to run the compactal is not used. The limitations descriptor restriction can be accepted by POLL=YES.	Number of worker tasks that the broker can use. Then the number of functions (SEND, RECEIVE, REGISTER concurrently. At least one worker task is required; the number of functions (SEND, RECEIVE, REGISTER concurrently. At least one worker task is required; the number of functions (SEND, RECEIVE, REGISTER concurrently. At least one worker task is required; the number of requests that can be processed transport mechanisms. Each broker command is assigned a worker queue elemechanism being used. This element is released whe of the command, including the case where the command, including the case where the command is a participant sattempting a denial are to be put on a blacklist. YES Create a participant blacklist. NO Do not create a participant blacklist. See Protecting a Broker against Denial-of-Service Attack. Administration documentation. A32 R z This is the address of the load/unload broker in transethods TCP and SSL are supported. See Transportedetails. This attribute is required if the attribute RUN 90 1 - 100 D Z Broker will issue a message if the defined percentage (available file descriptors) is exceeded. Default is 90 descriptors. YES NO D Z In earlier EntireX versions, the maximum number of communicator was limited; see Maximum TCP/IP Coplatform-specific list. With attribute POLL introducer restriction can be lifted under z/OS and UNIX. NO This setting is used to run the compatibility mocall is not used. The limitations described under per Communicator apply. YES The poll() system call is used to lift the resound multiplexing file descriptor sets. Note: The maximum number of file descriptors per ple exceeded by POLL=YES.	Number of worker tasks that the broker can use. The number of when the number of functions (SEND, RECEIVE, REGISTER, etc.) that a concurrently. At least one worker task is required; this is the defined processed by the brother task is required; this is the defined processed by the brother task is required; this is the defined processed by the brother task is required; this is the defined processed by the brother task is required; this is the defined processed by the brother task is required; this is the defined processed by the brother task is required; this is the defined processed by the brother task is required; this is the defined processed by the brother task is required; the defined processed by the brother task is required in the user if the command, including the case where the command has the processed when the user if the command, including the case where the command has the processed when the user if the command, including the case where the command has the processed when the user if the command has the processed when the user if the command has the processed when the user if the command has the processed when the user if the processed when the user if the processed when the user if the processed when the user is the processed and including the case where the command has the processed and including the case where the command has the processed when the user is the processed and including the case where the command has the processed when the user is the defined processed when the user is the processed when the user	Number of worker tasks that the broker can use. The number of worker tasks the number of functions (SEND, RECEIVE, REGISTER, etc.) that can be processor concurrently. At least one worker task is required; this is the default value. 1-32768 R z u w Maximum number of requests that can be processed by the broker in paral transport mechanisms. Each broker command is assigned a worker queue element, regardless of the mechanism being used. This element is released when the user has received of the command, including the case where the command has timed out. YES NO R z u w Determines whether participants attempting a denial-of-service attack on the are to be put on a blacklist. YES Create a participant blacklist. NO Do not create a participant blacklist. See Protecting a Broker against Denial-of-Service Attacks in the platform-special Administration documentation. A32 R z u w W This is the address of the load/unload broker in transport-method-style. Transports attribute is required if the attribute RUN-MODE is specified. 90 1 - 100 O z u w w Broker will issue a message if the defined percentage value of TCP/IP concavations. YES NO O z u w w Broker will issue a message if the defined percentage value of TCP/IP concavations are serviced in the available file descriptors) is exceeded. Default is 90 percent of the available descriptors. YES NO O z u w w In earlier EntireX versions, the maximum number of TCP/IP Connections per Communicator was limited; see Maximum TCP/IP Connections per Communicator was limited; see Maximum TCP/IP Connections per Communicator apply. YES The poll() system call is used to lift the resource restrictions with se multiplexing file descriptor sets. Note: The maximum number of file descriptors per process is a hard limit to the concavation of the descriptor sets.	

		Opt/	Operating System					
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000		
	■ you need more than the max				•			
	as described under <i>Maximu</i>			•				
	this maximum number is le process	ss than the	maximum	number of	file descrip	tors per		
	We recommend POLL=NO to re	educe CPU	consumpti	on.				
POSTPONED-QUEUE	YES I NO	О	Z	u	W			
	Enable or disable the creation	of a postpo	oned queue	for Broker				
	YES Enable creation of a post service-specific attributes	$\hat{\mathbf{s}}$ POSTPONE	E-ATTEMPT					
	NO Disable creation of a pos	tponed que	eue.					
	See Postponing Units of Work.							
PSTORE	NO I HOT I COLD	О	z	u	W	b		
	Defines the status of the persistent units of work (UOV be set. NO No persistent store.			•	_			
	HOT Persistent UOWs are restored to their prior state during initialization.							
	COLD Persistent UOWs are not restored during initialization, and the persistent store is considered empty.							
	Note: For a hot or cold start, t is restarted.	he persiste	nt store mu	st be availa	able when y	our broker		
PSTORE-REPORT	<u>NO</u> I YES	О	z	u	w	b		
	Determines whether PSTORE	report is cı	reated.					
	NO Do not create the PSTORE report file. YES Create the PSTORE report file.							
	See also Persistent Store Report							
PSTORE-TYPE	DIV (z/OS) CTREE (UNIX, Windows) ADABAS (all platforms)	О	Z	u	W	b		
	Describes the type of persistent store driver required.							
	DIV Data in Virtual. z/OS Attributes below and					specific		

				Opt/ Operating System					
Attribute	Values		Req	z/OS	UNIX	Windows	BS2000		
	c-tree Di	atabase. UNI atabase as Pers		•					
		. All platforn ig the Broker i entation.					•		
PSTORE-VERSION	<u>5</u>		О	z	u	W	b		
	Determines the version since Ent	ireX version	10.8.			·	••		
	Note: To change (all units of work the Broker with a ETBM0745.	must be cor	sumed). If	the persiste	ent store is	not empty, t	he start of		
RUN-MODE	STANDARD I STAI PSTORE-LOAD I PSTORE-UNLOAD	NDBY I	О	z	u	W	b		
	Determines the in	nitial run mo	de of the b	roker.	1		I.		
	STANDARD Default value. Normal mode.								
	STANDBY	Deprecated	. Supported	d for compa	atibility rea	sons.			
	PSTORE - LOAD Deprecated. Broker will run as load broker to write Persistent Store data to a new persistent store. See also Migrating the Persistent Store								
	PSTORE-UNLOAD	Deprecated persistent s	. Broker wi tore and pa	ll run as ur ass the data	nload broke to a broker	er to read an	existing		
	Note: RUN-MODE options PSTORE-LOAD and PSTORE-UNLOAD are deprecated and wil								
	not be supported	in the next v	version of E	IntireX.		_			
SECURITY	<u>NO</u> I YES		О	Z	u	W	b		
	Determines whet	her EntireX	Security is a	activated.	1	1	1		
	NO EntireX Sec	urity is not a	ctivated.						
	YES EntireX Security is activated.								
	See EntireX Secur	ity.							
SERVER-DEFAULT	n I UNLIM		О	z	u	W	b		
	Default number	of servers tha	at are allow	ed for ever	y service.				
	n Number	of servers.							

		Opt/		Operati	ng System	
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000
	UNLIM The number of server available. Precludes the				r of servers ફ	globally
	This value can be overridden of 0 (zero) is invalid.	by specifyi	ing a SERVE	R-LIMIT f	or the servic	e. A value
SERVICE-UPDATES	YES I NO	О	Z	u	W	b
	Switch on/off the automatic u	pdate mod	le of the bro	ker.	ļ	
	YES The broker reads the attr This allows the broker to The attribute file is read of it is not reread when a se NO The attribute file is read attribute file will be hone	honor mod only when the econd replication	lifications ir he first serve ca is activat during brok	the attribuer registers eed. eer startup.	ite file without for a particu	<i>ıt</i> a restart lar service
SHORT-BUFFER-DEFAULT	UNLIM n	О	z	u	W	b
	UNLIM The number of short m globally available. Pre n Number of buffers. This value can be overridden A value of 0 (zero) is invalid.	ecludes the	use of NUM-	-SHORT - BU	JFFER=AUTO	•
STORAGE-REPORT	NO I YES	О	Z	u	W	b
	NO Do not create the storage YES Create the storage report.	e report.	mory usage			
STORE	<u>OFF</u> I BROKER	О	z	u	w	b
	Sets the default STORE attribute by the STORE field in the Broken OFF Units of work are not BROKER Units of work are personal statements.	er ACI cor t persisten	ntrol block.	This attri	bute can be	overridder
TRACE-DD	A255	О	Z			
	A string containing data set a describe the trace output file a					

		Opt/	Operating System						
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000			
	(generation data group) as ou under <i>Tracing EntireX Broker</i> .	tput data s	et. See Flush	ning Trace D	Data to a GDC	7 Data Set			
	The following keywords are s	upported a	s part of the	e TRACE-D	D value:				
	■ DATACLAS		■ MG	GMTCLAS					
	■ DCB including BLKSIZE, DS RECFM	SORG, LREC		PACE FORCLAS					
	■ DISP		■ 51						
	■ DSN								
	Refer to your JCL Reference M	Ianual for a	a complete	descriptior	of the synta	ıx.			
	Example:	Example:							
	TRACE-DD = "DSNAME=EXX. DCB=(BLKSIZE= DISP=(NEW,CAT SPACE=(CYL,(1 STORCLAS=SMS"	1210,DSOF LG,CATLG		CL=121,R&	ECFM=FB),				
	Note: If you specify TRACE-DITRBUFNUM for the setting to ta	•	t also speci	fy TRMODE=	=WRAP and a	value for			
TRACE-FILE-SIZE	n I nK I nM I nG	О		u	w				
	Defines the size of one trace fi exceeded, a new trace file is all with MAX-TRACE-FILES is real help prevent a constantly grow Windows.	ocated unti ached. Ther	l the maxime is no defa	ium numbe ault value. '	er of trace file These two p	es specified arameters			
TRACE-LEVEL	<u>0</u> - 4	0	z	u	W	b			
	The level of tracing to be performance O No tracing. Default value. Traces incoming requests, of All of trace level 1, plus all All of trace level 2, plus all All of trace level 3, plus Brown	outgoing re main routii routines ex oker ACI co	plies, resou nes execute ecuted. ontrol block	irce usage a d. displays.	and conversi				
	Trace levels 2, 3 and 4 should	be used on	ly when red	quested by	Software AC	3 Support			

		Opt/		Operatin	g System			
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000		
	If you modify the TRACE-LEV to take effect. For temporary command Central or the Enti	hanges to	TRACE - LEV	EL without	a broker re	_		
TRANSPORT	TCP-NET TCP SSL NET	О	Z			b		
	TCP SSL	0		u	w			
	The broker transport may be s following methods:	specified as	any combi	nation of or	ne or more	of the		
	TCP TCP/IP is supported.							
	SSL SSL/TLS is supported.							
	NET Entire Net-Work is supp UNIX or Windows.	orted. This	value is no	t supported	l for a broke	er under		
	Examples:							
	TRANSPORT=NET specifies that only the Entire Net-Work transport method will be supported by the broker.							
	TRANSPORT=TCP-NET specifies that both the TCP/IP and Net-Work transport method will be supported by the broker.							
	TRANSPORT=TCP-SSL-NET sp transport methods will be sup	•		P, SSL/TLS,	and Entire	Net-Work		
	The parameters for each transp	ort method	l are describ	ed in the re	spective sec	tion: TCP		
TRAP-ERROR	nnnn	0	z	u	w	b		
	Where <i>nnnn</i> is the four-digit <i>p</i> example 0007 (Service not reg default value. See <i>Deferred Tracing</i> under z/C Administration documentatio	istered). Le	eading zeros	s are not re	quired. The	re is no		
TRBUFNUM	n	О	z	u	w	b		
	Changes the trace to write trace buffer in 64 KB units. There is			e buffers. <i>n</i>	is the size o	of the trace		
TRMODE	WRAP	О	z	u	w	b		
	Changes the trace mode. WRAP is the only possible value. This value instructs broker to write the trace buffer (see TRBUFNUM) if an event occurs. This event is triggered by a matching TRAP - ERROR during request processing or when an exception occurs.							
UMSG	See MAX-MESSAGES-IN-UOW.							
UOW-DATA-LIFETIME	<u>1D</u> nS nM nH nD	О	Z	u	w	b		
	Defines the default lifetime fo	r units of w	vork for the	service.	-			

		Opt/		Operatir	g System				
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000			
	nS Number of seconds the U		,	•					
	nM Number of minutes the U		•	•					
	<i>n</i> H Number of hours the UO		•	•					
	<i>n</i> D Number of days the UOW	/ can exist (max. 24855	5).					
	I	If the UOW is inactive - that is, is not processed within the time limit - it is deleted and given a status of TIMEOUT. This attribute can be overridden by the UWTIME field in the Broker ACI control block.							
	See Timeout Considerations for EntireX Broker.								
UOW-MSGS	See MAX-MESSAGES-IN-UOW.								
UOW-STATUS-LIFETIME	no value n[S] nM nH nD	no value In[S] InMInHInD O z u w 1							
	The value to be added to the UOW-DATA-LIFETIME (lifetime of associated UC value is entered, it must be 1 or greater; a value of 0 will result in an error. If is entered, the lifetime of the UOW <i>status</i> information will be the same as the of the UOW itself.								
	<i>n</i> S Number of seconds the UOW status exists longer than the UOW itself (max. 2147483647).								
	nM Number of minutes (max. 35791394).								
	nH Number of hours (max. 596523).								
	nD Number of days (max. 24855).								
	This attribute is ignored if PSTORE=N0 is defined.								
	The lifetime determines how a persistent store and is calculated any of the following statuses: DISCARDED. The additional lift is executing. Value in UOW-ST attribute UWSTATP.	ted from the PROCESSEI fetime of the	e time at w), TIMEOUT e UOW stat	hich the as , BACKEDOU tus is calcul	sociated UC IT, CANCELL ated only w	W enters ED, hen broker			
	Note: If no unit is specified, the	ne default u	ınit is secor	nds. The un	it does not l	nave to be			
	identical to the unit specified								
UWSTAT-LIFETIME	Alias for UOW-STATUS-LIFET	IME.							
UWSTATP	<u>0</u> <i>n</i>	О	Z	u	W	b			
	Contains a multiplier used to compute the lifetime of a persistent status for the The UWSTATP value is multiplied by the UOW-DATA-LIFETIME value (the lifetime associated UOW) to determine the length of time the status will be retain persistent store.								
	0 The status is not persi	stent.							

		Opt/		Operating System					
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000			
	1 2	1-254 Multiplied by the value of UOW-DATA-LIFETIME to determine how long a persistent status will be retained.							
	Note: This attribute has not be UOW-STATUS-LIFETIME inste		ted since Er	ntireX versi	on 7.3. Use				
UWTIME	Alias for UOW-DATA-LIFETIM	1E.							
WAIT-FOR-ACTIVE-PSTORE	NO I YES	О	z	u	w	b			
	Determines whether broker shactive, or until c-tree PSTORE NO If broker should start with	E files becom th a PSTORE	ne available -TYPE=ADA	.					
	or is not accessible, broke If broker should start with in use, broker will stop.	i th a PSTORI	E-TYPE=CT						
	YES If broker should start with or is not accessible, broke with the PSTORE. Broke the Adabas database. If broker should start with use, broker will retry ever reject any user requests to	er will retry er will reject th a PSTORE ery 10 secon	every 10 se t any user re E-TYPE=CT nds to rebuil	conds to ini equests unt REE and the Id the persis	itiate comm il it is able t e c-tree files stent data. I	unications to contact are still in			
WORKER-MAX	64 <i>n</i> (min. 1, max. 64)	О	z	u	w	b			
1	Maximum number of worker	tasks the b	roker can u	se.	·L				
WORKER-MIN	<u>1</u> <i>n</i> (min. 1, max. 64)	О	z	u	w	b			
	Minimum number of worker	tasks the br	oker can us	se.					
WORKER-NONACT	70S n nS nM nH	О	Z	u	w	b			
	Non-activity time to elapse before a worker tasks is stopped. n Same as nS. nS Non-activity time in seconds (default 70, max. 2147483647). nM Non-activity time in in minutes (max. 35791394). nH Non-activity time in hours (max. 596523). Caution: A value of 0 (zero) is invalid. If you set this value too low, additional overhead is required for starting and stopping worker tasks. The default and recommended								
WORKER-QUEUE-DEPTH	value is 70\$. 1 n (min. 1)	0	z	u	w	b			
WORKER QUEUE DETTI	± ' '' (IIIII: 1)			u	**				

		Opt/		Operating System				
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000		
	Number of unassigned user requests in the input queue before another worker task gets started. The default and recommended value is 1. A higher value will result in longer broker response times.							
WORKER-START-DELAY <u>internal-value</u> I n O z u w								
	n Delay is extended by n second Delay after a successful worker started to handle current incomo frecursive invocation of work workload increase. If no value is specified, an integral dynamic worker management start a worker task.	er task invo ming work ker tasks, b ernal value	load. This a ecause star	ttribute is uting a work	used to avoi ker task itsel er is used to	d the risk If causes O optimize		

Service-specific Attributes

Each section begins with the keyword <code>DEFAULTS=SERVICE</code>. Services with common attribute values can be grouped together. The attributes defined in the grouping apply to all services specified within it. However, if a different attribute value is defined immediately following the service definition, that new value applies. See also the sections <code>Wildcard Service Definitions</code> and <code>Service Update Modes</code> below the table.

		Opt/	Operating System					
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000		
APPLICATION-MONITORING	YES I NO	0	z	u	w	b		
or APPMON	YES Enable application monitoring for t NO Disable application monitoring for See the separate Application Monitoring	l servi						
APPLICATION-MONITORING-	A100	O	Z	u u	w	b		
NAME or APPMON - NAME	Specifies the application monitoring name. Used to set the ApplicationName KPI.							
	If omitted, the default value from the APPLICATION-MONITORING section is used. If this value is also not specified, the corresponding CLASS/SERVER/SERVICE names are used. See the separate Application Monitoring documentation.							
CLASS	A32 (case-sensitive)	R	z	u	W	b		
	Part of the name that identifies the service together with the SERVER and SERVICE attributes. CLASS must be specified first, followed immediately by SERVER and SERVICE. The following rules apply:							
	Classes starting with any of the following are reserved for use by Software AG. Do not use these in applications you write: BROKER, SAG, ENTIRE, ETB, RPC, ADABAS, NATURAL.							
	■ Valid characters for class name are letters a-z, A-Z, numbers 0-9, hyphen and underscore.							
	Do not use dollar, percent, period or co	omma	١.					
	See also the restriction for SERVICE attribute names.							
CLIENT-RPC-	<u>N</u> Y	О	z			b		
AUTHORIZATION	Determines whether this service is subject to RPC authorization checking. N No RPC authorization checking is performed.							

		C	Opt/ Operating System								
Attribute	Values		Req	z/OS	UNIX	Windows	BS2000				
	Y RPC library and program name as performed by EntireX Security. Spervices. To allow conformity with Natural Security of the parameter can optionally be defined	pecify \	YES he Cl	only to	o RPC - RPC -	C-support	ted ZATION				
	CLIENT-RPC-AUTHORIZATION= (YES, <pre>character>).</pre>										
CONV-LIMIT	UNLIM I n		О	Z	u	W	b				
	Allocates a number of conversations	Allocates a number of conversations especially for this service. UNLIM The number of conversations is restricted only by the number of conversations globally available. Precludes the use of NUM-CONVERSATION=AUTO in the Broker section of the attribute fil Number of conversations.									
	conversations globally availa NUM-CONVERSATION=AUTOi										
	A value of 0 (zero) is invalid. If NUM-CONVERSATION=AUTO is specified in the Broker section of the attribute file, CONV-LIMIT=UNLIM is not allowed in the service section. A value must be specified or the CONV-LIMIT attribute must be suppressed entirely for the service so that the default (CONV-DEFAULT) becomes active.										
CONV-NONACT	<u>5M</u> <i>n</i> <i>n</i> S <i>n</i> M <i>n</i> H		R	z	u	W	b				
	Non-activity time for connections.										
	n Same as nS.										
	nS Non-activity time in seconds (m	nax. 214	174 80	3647).							
	nM Non-activity time in minutes (m	nax. 357	7913	94).							
	n H Non-activity time in hours (max	x. 59652	23).								
	A value of 0 (zero) is invalid. If a cortime, that is, a server or a client does rethe connection in any way, the connection allocated resources are freed.	not issu	ıe a b	oroker	reque	est that ref	ferences				
CONVERSION	A255		О	z	u	W	b				
	<pre>(SAGTCHA[, TRACE=n][, OPTION= SAGTRPC[, TRACE=n][, OPTION= name[, TRACE=n] NO)</pre>										
	Defines ICU conversion or SAGTRPO Internationalization with EntireX.	Cuser	exit	for cha	aracte	r convers	ion. See				
	SAGTCHA (1) Conversion using ICU (Conver	SAGTCHA (1) Conversion using ICU Conversion for ACI-based Programming								

			Opt/	Opt/ Operating System				
Attribute	Values		Req	z/OS	UNIX	Windows	BS2000	
		Conversion using ICU Converdent Reliable RPC.	version	n for R	PC-ba	sed Comp	onents	
		and Reliable RPC. See also C under <i>Configuring Broker for</i> platform-specific Administr SAGTRPC User Exits under	tration documentation and Writing					
	6	f conversion is not to be use attribute or specify CONVERS payload.						
	for a service.	ION attribute overrides the TI That is, when TRANSLATION N will be ignored.						
	Note:							
		onfiguring ICU Conversion un alization in the platform-spec		, ,	_		ntation.	
		is not supported on BS2000s, use SAGTCHA on BS2000 C.				_	-	
	3. SAGTRPC	user exit is not supported of	on BS2	2000.				
	TRACE							
		witched on, the trace outpugg trace levels are available:	t is wr	ritten t	o the	broker lo	g file.	
	0 No tracing	;						
	1 STANDARD	This level is an "on-error" conversion errors only. For library, IDL program and the for Conversion are set, errors.	r RPC he dat	calls t a. Note	his ine e that	cludes the	e IDL	
		Tracing of incoming, outgo	oing p	arame	eters a	nd the pa	yload.	
	3 SUPPORT	This trace level is for supp requested by Software AG		-	ics. U	se only w	hen	
	OPTION							
	See table of p	ossible values under <i>OPTIC</i>	N Valı	ues foi	Con	version.		

		Opt/	Operating System						
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000			
DEFERRED	NO I YES	O	z	u	w	b			
	NO Units of work cannot be sent to the service until it is available. YES Units of work can be sent to a service that is not up and register units of work will be processed when the service becomes available.								
LOAD-BALANCING	YES I NO	О	z	u	w	b			
	YES When servers that offer a particular service are started, new conversations will be assigned to these servers in a round-robin fash. The first waiting server will get the first new conversation, the sec waiting server will get the second new conversation, and so on. NO A new conversation is always assigned to the first server in the que								
LONG-BUFFER-LIMIT	UNLIM n	О	z	u	w	b			
	UNLIM The number of long message buffers is restricted only by the num of buffers globally available. Precludes the use of NUM-LONG-BUFFER=AUTO in the Broker section of the attribute in Number of long message buffers. A value of 0 (zero) is invalid. If NUM-LONG-BUFFER=AUTO is specified in Broker section of the attribute file, LONG-BUFFER-LIMIT=UNLIM is not allowed in the service section. A value must be specified or the LONG-BUFFER-LIMIT attribute must be suppressed entirely for the service so that the default (LONG-BUFFER-DEFAULT) becomes active.								
MAX-MESSAGES-IN-UOW	<u>16</u> <i>n</i>	О	z	u	w	b			
	Maximum number of messages in a UOI	N.							
MAX-MESSAGE-LENGTH	<u>2147483647</u> <i>n</i>	O	Z	u	w	b			
	Maximum message size that can be sent to a service. This is transport-dependent. The default value represents the highest positive number that can be stored in a four-byte integer.								
MAX-MSG	See MAX-MESSAGE-LENGTH.								
MAX-UOW-MESSAGE-LENGTH	See MAX-MESSAGE-LENGTH.								
MAX-UOWS	<u>0</u>	Ο	Z	u	w	b			
	0 The service does not accept units of w messages that are not part of a UOW. of UOWs to services that are not intention	Using	zero p	oreven	its the ser	- 1			

		Opt/			ting Syste	
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000
	n Maximum number of UOWs that can be If you do not provide a MAX-UOWS value MAX-UOWS setting for the broker. If you of the broker, the service MAX-UOWS is sand a warning message is issued. Specify MAX-UOWS=0 for Natural RPC Servivith a later release.	ie for i prov set to t	the ser ide a v he bro	rvice, i value t oker's l	it default hat excee MAX - UOW	s to the eds that S value
MUOW	See MAX-UOWS.					
NOTIFY-EOC	NO I YES	О	z	u	W	b
	Specifies whether timed-out conversation	ns are	to be s	stored	or discar	rded.
	YES Store the EOC notifications if the set then notify the server if possible. If a server is not ready to receive an EOC discarded. If it is stored, the server is not	notifi	cation	, it car	ı be store	ed or
	to receive. Caution: The behavior activated by this purpose during a single lifetime of the broker kern containing units of work, whose lifetime sessions, cannot be assumed to show this	oaram nel. Sp can sp	eter ca	an be r ally, co ultiple	relied upo onversati broker k	on only
	to receive. Caution: The behavior activated by this purpose during a single lifetime of the broker kern containing units of work, whose lifetime sessions, cannot be assumed to show this NOTIFY-EOC=YES.	oaram nel. Sp can sp	eter ca	an be r ally, co ultiple	relied upo onversati broker k	on only
NUM-UOW	to receive. Caution: The behavior activated by this particular during a single lifetime of the broker kern containing units of work, whose lifetime sessions, cannot be assumed to show this NOTIFY-EOC=YES. Alias for MAX-UOWS.	oaram nel. Sp can sp s beha	eter ca pecific pan m vior, e	an be r ally, co ultiple	relied upo onversati broker k	on only
NUM-UOW POSTPONE-ATTEMPTS	to receive. Caution: The behavior activated by this purpose during a single lifetime of the broker kern containing units of work, whose lifetime sessions, cannot be assumed to show this NOTIFY-EOC=YES. Alias for MAX-UOWS. O n	oaram nel. Sp can sp s beha	eter ca pecification mi vior, e	an be r ally, co ultiple ven w	relied uponversati broker k ith	on only ons kernel
	to receive. Caution: The behavior activated by this particular during a single lifetime of the broker kern containing units of work, whose lifetime sessions, cannot be assumed to show this NOTIFY-EOC=YES. Alias for MAX-UOWS.	oaram nel. Sp can sp s beha O receive tpone PONE pone queu Vs will IE-DE D-QUE	eter capecification missing the control of the cont	u unit of water for the UC elivere as elapust be e	wwork (UO later production CANCEL) venored. CANCEL DW statud to the rosed.	on only ons kernel W) due cessing. vill be tead of ; the s will receiver default)

		Opt/ Operating Syst		ting Syster	n				
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000			
	The length of time a UOW is kept in state	us POS	STPON	ED.					
	No postponed queue is created and a ignored.	attribu	ıte POS	STPON	E-ATTEMI	PTS is			
	nS Number of seconds the UOW stays u with status POSTPONED (max. 214748			n the p	ostponed	queue			
	<i>n</i> M Number of minutes the UOW stays unreadable in the postponed queue with status POSTPONED (max. 35791394).								
	<i>n</i> H Number of hours the UOW stays unreadable in the postponed queue with status POSTPONED (max. 596523).								
	<i>n</i> D Number of days the UOW stays unreadable in the postponed queue with status POSTPONED (max. 24855).								
	The status of the UOW will be changed from POSTPONED to ACCEPTED after elapsed POSTPONE-DELAY. This delay time does not affect the UOW-DATA-LIFETIME. The POSTPONE-DELAY must be less than UOW-STATUS-LIFETIME in order to make the UOW receivable again.								
	Note: Broker-specific attribute POSTPONED - QUEUE must be enabled (default)								
	for this attribute to take effect. The default is 0, that is, no postponed queue is created, but if a value is entered, the minimum delay is 30 seconds. Any value entered that is less than 30 seconds will be increased to this value. See <i>Postponing Units of Work</i> .								
SERVER	A32 (case-sensitive)	R	Z	u	w	b			
	Part of the name that identifies the service SERVICE attributes.	e toge	ether v	vith th	e CLASS a	and			
	CLASS must be specified first, followed im	media	itely by	r SERV	ER and SE	RVICE.			
	Valid characters for server name are lette and underscore. Do not use dollar, perce				-	yphen			
SERVER-DEFAULT	n I UNLIM	О	z	u	w	b			
	Default number of servers that are allow	ed for	every	servi	ce.				
	<i>n</i> Number of servers.								
	UNLIM The number of servers is restricted globally available. Precludes the		-			ervers			
	A value of 0 (zero) is invalid.								
	This value can be overridden by specifyin	ga S	ERVER	-LIMI	⊺ for the s	service.			
SERVER-LIMIT	n I UNLIM	0	z	u	W	b			
	Allows a number of servers especially fo	r this	servic	e.					

		Operating System								
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000				
	 Number of servers. UNLIM The number of servers is restricted only by the number of servers globally available. Precludes the use of NUM-SERVER=AUTO in the Broker section of the attribute file. 									
	A value of 0 (zero) is invalid. If NUM-SERVER=AUTO is specified in the Broker section of the attribute file, SERVER-LIMIT=UNLIM is not allowed in the service section. A value must be specified or the SERVER-LIMIT attribute must be suppressed entirely for the service section.									
	Note: UNIX and Windows: This limit also includes any attach server you are using. Make sure you increase the number by one for each attach servey you use.									
SERVER-NONACT	<u>5M</u> <i>n</i> <i>n</i> S <i>n</i> M <i>n</i> H	R	Z	u	w	b				
	Non-activity time for servers. A server that does not issue a broker request within the specified time limit is treated as inactive and all resources for the server are freed. n Same as nS.									
	nS Non-activity time in seconds (max. 2		-							
	nM Non-activity time in minutes (max. 3 nH Non-activity time in hours (max. 596). If a server registers multiple services, the	5523).	•	ue of	all the se	rvices				
	registered is taken as non-activity time for	_			an are se	VICES				
SERVICE	A32 (case-sensitive)	R	z	u	W	b				
	Part of the name that identifies the service SERVER attributes.	ce togo	ether v	vith th	ne CLASS	and				
	CLASS must be specified first, followed im		, ,							
	The SERVICE attribute names EXTRACTOR and DEPLOYMENT are reserved ff Software AG internal use and should not be used in customer-written applications. Valid characters for service name are letters a-z, A-Z, number 0-9, hyphen and underscore. Do not use dollar, percent, period or commanded also the restriction for CLASS attribute names.									
SHORT-BUFFER-LIMIT	UNLIM n	О	Z	u	W	b				
	Allocates a number of short message but	ffers fo	or the	servic	e.					

		Opt/		Opera	Operating System						
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000					
	UNLIM The number of short message buffers is restricted only by the number of buffers globally available. Precludes the use of NUM-SHORT-BUFFER=AUTO in the Broker section of the attribute file.										
	n Number of short message buffers	5.									
	If NUM-SHORT-BUFFER=AUTO is specified in the Broker section of the attribute file, SHORT-BUFFER-LIMIT=UNLIM is not allowed in the service section. A value must be specified or the SHORT-BUFFER-LIMIT attribute must be suppressed entirely for the service so that the default (SHORT-BUFFER-DEFAULT) becomes active.										
STORE	<u>OFF</u> I BROKER	О	z	u	w	b					
	Sets the default STORE attribute for all units of work sent to the service. OFF Units of work are not persistent. BROKER Units of work are persistent.										
	This attribute can be overridden by the ST block.	ORE fi	ield in	the Br	oker ACI	control					
TRANSLATION	NO I name (A255)	О	z	u	W	b					
	 NO If translation is not to be used - for example for binary payload (broken messages) - either omit the TRANSLATION attribute or specify TRANSLATION=NO. name Name of Translation User Exit. See also Configuring Translation User Exits under Configuring Broker for Internationalization in the platform-specific Administration documentation or Writing Translation User Exits under Configuring Broker for Internationalization in the platform-specific Administration documentation. The CONVERSION attribute overrides the TRANSLATION attribute when defined 										
	for a service; that is, when TRANSLATION TRANSLATION will be ignored.										
UMSG	Alias for MAX-MESSAGES-IN-UOW.		1	1	I						
UOW-DATA-LIFETIME	Defines the default lifetime for units of w	O vork fo	or the	u servic	e.	b					
	<i>n</i> \$ Number of seconds the UOW can ex	ist (ma	ax. 214	174836	47).						
	nM Number of minutes the UOW can ex	ist (m	ax. 357	791394	ł).						
	<i>n</i> H Number of hours the UOW can exist	(max	. 59652	23).							
	nD Number of days the UOW can exist ((max. :	24855)).							

		Opt/		Opera	ting Syste	m				
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000				
	This attribute is ignored if PSTORE=NO is	defin	ed.		-					
	If the unit of work (UOW) is inactive, the limit, it is deleted and given a status of Toverridden by the UWTIME field in the Br	IMEO	UT. Th	is attri	ibute can					
UOW-MSGS	Alias for MAX-MESSAGES-IN-UOW.									
UOW-STATUS-LIFETIME	no value I n[S] I nM I nH I nD	О	z	u	w	b				
	The value to be added to the UOW-DATA-LIFETIME lifetime of associated UOW). If a value is entered, it must be 1 or greater; a value of 0 will result in an error. If no value is entered, the lifetime of the UOW status information will be the same as the lifetime of the UOW itself. **nS** Number of seconds the UOW status exists longer than the UOW itself (max. 2147483647). **nM** Number of minutes (max. 35791394). **nH** Number of hours (max. 596523). **nD** Number of days (max. 24855). The lifetime determines how much additional time the UOW status is retained in the persistent store and is calculated from the time at which the associated UOW enters any of the following statuses: PROCESSED, TIMEOUT, BACKEDOUT, CANCELLED, DISCARDED. The additional lifetime of the UOW status is calculated only when broker is executing. Value in UOW-STATUS-LIFETIME*									
	supersedes the value (if specified) in attr									
	Note: If no unit is specified, the default the base to be identical to the unit specified.					es not				
UWSTATP	have to be identical to the unit specified 0 n	0	1	T	1	b				
ONSTATI	Contains a multiplier used to compute the service. The UWSTATP value is multiple value (the lifetime of the associated UOV the status will be retained in the persistent).	he life lied by V) to o	the U(determ	OW-ST	ATUS-LI	atus for				
	0 The status is not persistent.									
	1 - 254 Multiplied by the value of UOW-Dong a persistent status will be re-			IME to) determii	ne how				
	This attribute is ignored if PSTORE=NO is	defin	ied.							
	Note: This attribute has not been supported since EntireX version 7.3. Use UOW-STATUS-LIFETIME instead.									
UWSTAT-LIFETIME	Alias for UOW-STATUS-LIFETIME.									
UWTIME	Alias for UOW-DATA-LIFETIME.									
	<u> </u>									

Wildcard Service Definitions

The special names of CLASS = *, SERVER = * and SERVICE = * are allowed in the service-specific and authorization rule-specific sections of the broker attribute file. These are known as "wildcard" service definitions. If this name is present in the attribute file, any service that registers with the broker and does not have its own entry in the attribute file will inherit the attributes that apply to the first wildcard service definition found.

For example, a server that registers with CLASS=ACLASS, SERVER=ASERVER and SERVICE=ASERVICE can inherit attributes from any of the following entries in the attribute file (this list is not necessarily complete):

```
CLASS = *, SERVER = ASERVER, SERVICE = ASERVICE
CLASS = ACLASS, SERVER = *, SERVICE = *
CLASS = *, SERVER = *, SERVICE = *
```

Of course, if there is a set of attributes that are specifically defined for CLASS=ACLASS, SERVER=ASERVER, SERVICE=ASERVICE, then all of the wildcard service definitions will be ignored in favor of the exact matching definition.

Service Update Modes

EntireX has two modes for handling service-specific attributes. See broker-specific attribute SER-VICE-UPDATES.

- In **service update mode** (SERVICE-UPDATES=YES), the service configuration sections of the attribute file are read whenever the first replica of a particular service registers.
- In **non-update mode** (SERVICE-UPDATES=NO), the attribute file is not reread. All attributes are read during startup and the broker does not honor any changes in the attribute file. This mode is useful if
 - there is a high frequency of REGISTER operations, or
 - the attribute file is rather large and results in a high I/O rate for the broker.

The disadvantage to using non-update mode is that if specific attributes are modified, the broker must be restarted to effect the changes. Generally, this mode should be used only if the I/O rate of the broker is considerably high, and if the environment seldom changes.

OPTION Values for Conversion

The different option values allow you to either handle character conversion deficiencies as errors, or to ignore them:

- 1. Do not ignore any character conversion errors and force an error always (value STOP). This is the default behavior.
- 2. Ignore if characters cannot be converted into the receiver's codepage, but force an error if sender characters do not match the sender's codepage (value SUBSTITUTE-NONCONV).
- 3. Ignore any character conversion errors (values SUBSTITUTE and BLANKOUT).

Situations 1 and 2 above are reported to the broker log file if the TRACE option for CONVERSION is set to level 1.

Value	Description	Options Supported for		if TRACE Option CONVERSION is Bad Input Characters (Sender's	
SUBSTITUTE	Substitutes both non-convertible characters (receiver's codepage) and bad input characters (sender's codepage) with a codepage-dependent default replacement character.	YES	YES	No message.	No message
SUBSTITUTE-NONCONV	If a corresponding code point is not available in the receiver's codepage, the character cannot be converted and is substituted with a codepage-dependent default replacement character. Bad input characters in sender's codepage are not substituted and result in an error.	YES	YES	Write detailed conversion error message.	No message.
BLANKOUT	Substitutes non-convertible characters with a codepage-dependent default replacement; blanks out the complete RPC IDL field containing one or more bad input characters.	NO	YES	No message.	No message.

		Options Su		Report Situation in Broker Log if TRACE Option for CONVERSION is set to 1	
Value	Description	SAGTCHA		Bad Input Characters (Sender's Codepage)	Non-convertible Characters (Receiver's Codepage)
STOP	Signals an error on detecting a non-convertible or bad input character. This is the default behavior if no option is specified.	YES	YES	Write detailed conversion error message.	Write detailed conversion error message.

Codepage-specific Attributes

The codepage-specific attribute section begins with the keyword <code>DEFAULTS=CODEPAGE</code> as shown in the sample attribute file. You can use the attributes in this section to customize the broker's locale string defaults and customize the mapping of locale strings to codepages for character conversion with ICU conversion and SAGTRPC user exit. See <code>Internationalization with EntireX</code> for more information.

		Opt/		Operatin	g System					
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000				
DEFAULT_ASCII	Any ICU converter name or alias. See also <i>Additional Notes</i> below.	Ο	Z	u	W	b				
	Customize the broker's locale string defaults by assigning the default codepage for EntireX components (client or server). See <i>Broker's Locale String Defaults</i> . This value is used instead of the broker's locale string defaults if the calling component does not send a locale string itself, and the calling component is running on an ASCII platform (UNIX, Windows, etc.) Example: DEFAULTS=CODEPAGE * Broker Locale String Defaults									
	For more examples, see <i>Configuring Broker's Locale String Defaults</i> in the Internationalization documentation and also <i>Additional Notes</i> below.									
DEFAULT_EBCDIC_IBM	Any ICU converter name or alias	0	Z	u	W	b				
	Customize the broker's locale string defaults by assigning the default codepage for EntireX components (client or server). See <i>Broker's Locale String Defaults</i> . This value is used instead of the broker's locale string defaults if the calling component does not send a locale string itself and the calling component is running on an IBM mainframe platform									
	Example:									

		Opt/	Operating System							
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000				
	DEFAULT=CODEPAGE DEFAULT_EBCDIC_									
	For more examples, see <i>Configuring Broker's Locale String Defaults</i> in the Internationalization documentation and also <i>Additional Notes</i> below.									
DEFAULT_EBCDIC_SNI	Any ICU converter O z u w b name or alias. Customize the broker's locale string defaults by assigning the default codepage for EntireX components (client or server). See Broker's Locale String Defaults. This value is used instead of the locale string defaults if									
	the calling component does not send a locale string itself, and									
	the calling componen (BS2000)	■ the calling component is running on a Fujitsu EBCDIC mainframe platform (BS2000)								
	Example:									
	DEFAULT=CODEPAGE DEFAULT_EBCDIC_	DEFAULT=CODEPAGE DEFAULT_EBCDIC_SNI= bs2000-edf03drv								
	For more examples, see Internationalization doc			_	•					
locale-string	Any ICU converter name or alias. See also <i>Additional Notes</i> below.	0	Z	u	W					
	Customize the mapping locale string processing useful:		_							
	if the broker's locale s to the wrong codepag your requirements.	0 1	0							
	if you want to install usee <i>Building and Install</i> Administration docum	ling ICU Cu								
	The attribute (locale stri (client or server) and the that locale string. In the application sends ASCII ISO 8859_1. In the same All other locale strings a Broker's Built-in Locale St	e value is the first line of I as a locale way EUC_J I are mapped	e codepage the exampl string; the l P_LINUX is by the brol	that you we e below, the proker maps mapped to ker's mappin	ant to use in e client or se s this to the ibm-33722_	place of rver codepage P12A-1999.				

		Opt/				
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000
	DEFAULTS=CODEPAGE * Broker Loca ASCII=IS08859 EUC_JP_LINUX= * Customer-wr CP1140=myebco CP0819=myasci	le String :ibm-33722_ :itten ICU lic	P12A-1999	-	ts	
	For more examples, s Additional Notes belo	υ,	Broker's Buili	t-in Locale Si	tring Mappin	g and also

Additional Notes

- Locale string matching is case insensitive when bypassing the broker's built-in mechanism, that is, when the broker examines the codepages section in the attribute file.
- If ICU is used for character conversion and the style in not known by ICU, e.g. <ll>_<cc> etc., the name will be mapped to a suitable ICU alias. For more details on the mapping mechanism, see *Broker's Built-in Locale String Mapping*. For more details on ICU and ICU converter name standards, see *ICU Resources*.
- If SAGTRPC user exit is used for the character conversion, we recommend assigning the codepage in the form CP<nnnnn>. To determine the number given to SAGTRPC user exit, see *Broker's Built-in Locale String Mapping*.
- See CONVERSION on this page for the character conversion in use.

Adabas SVC/Entire Net-Work-specific Attributes

The Adabas SVC/Entire Net-Work-specific attribute section begins with the keyword <code>DEFAULTS=NET</code> as shown in the sample attribute file. The attributes in this section are needed to execute the Adabas SVC/Entire Net-Work communicator of the EntireX Broker kernel.

Note: This section applies to mainframe platforms only. It does not apply to UNIX and Windows.

		Opt/		Operatin	g System			
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000		
ADASVC	nnn	R	z					
	Sets the Adabas SVC numb	er for Ent	ireX Broke	r access.		l		
	The Adabas SVC is used to perform various internal functions, communication between the caller program and EntireX Broke. Not supported on BS2000.							
EXTENDED - ACB - SUPPORT		0	z			b		
	Determines whether extend supported.	ded featur	es of Adab	as version	8 (or abov	e) are		
	NO No features of Adabas version 8 or above will be used.							
	YES Informs broker kernel to provide Adabas/WAL version 8 trans- capability. This parameter is required for sending/receiving mo 32 KB data over Adabas [NET] transport. This value should be you have installed Adabas/WAL version 8, Adabas SVC, and i Adabas/WAL version 8 load libraries into the steplib of broker otherwise, unpredictable results can occur.							
FORCE	<u>NO</u> I YES	0	Z			b		
	Determines whether DBID table entries can be overwritten. NO Overwrite of DBID table entries not permitted. YES Overwrite of DBID table entries permitted. This is required when the DBID table entry is not deleted after abnormal termination.							
	Caution: Overwriting an existing entry prevents any further communication							
	with the overwritten node. Use FORCE=YES only if you are absolutely sure that no target node with that DBID is active.							
IDTNAME	idtname(A8) ADABAS5B	О				b		
	If an ID table name is specified with the appropriate ADARUN parameter for Entire Net-Work, Adabas or Natural, the same name must be specified here.							

	Opt/			Operatir	g System		
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000	
	The ID table is used to per- communication between the supported under BS2000.				0		
IUBL	8000 I n	О	z			b	
	This parameter sets the map passed from the caller to Er as the maximum value of t <i>Manual</i> . IUBL must be large enough required for any caller proand Entire Net-Work contracts	ntireX Brok he Adabas to hold the gram plus	er. The ma paramete maximum any admir	iximum siz r LU. See tl a send-leng	ze of IUBLi he <i>Adabas</i> C th plus rece	s the sam Operations sive-lengt	
LOCAL	NO I YES	О	Z			b	
	For remote nodes accessed whether the target ID defir locally, or also remotely. NO DBID is <i>global</i> and can YES DBID is <i>local</i> and can Net-Work.	ned with the	ne NODE att	ribute can	be accesse	d only Net-Work	
MAX-MESSAGE-LENGTH	2147483647 n	О	z	u	w	b	
	Maximum message size that the broker kernel can process using transport method NET. The default value represents the highest positive number that car be stored in a four-byte integer.						
NABS	<u>10</u> <i>n</i>	О	z			b	
	An attached buffer is an in An attached buffer pool equallocated. This buffer pool parallel calls to EntireX Brown The following formula can NABS = NCQE *IUBL / 4	ternal buff ual to the l must be la oker. be used to	er used fo NABS value rge enoug	r interproc e multiplie h to hold a	ed by 4096 v all data (IU	will be	
NCQE	<u>10</u> <i>n</i>	О	z			b	
	NCQE defines the number of processing commands arrive transport mechanism. Suffirmechanism to process multiqueue element requires 195 user (client or server) has resistened out.	ring at the b cient NCQE tiple broker 2 bytes, and	oroker kerr should be r command d the elem	nel over Ac allocated t ds concurr ent is relea	labas SVC / o allow this ently. Each ased when	Net-World transport command either the	

	Operating System							
Values	Req z/OS UNIX Windows BS							
The number of command queue elements required to handle broker calls depends on the number of parallel active broker calls that are using the transport mechanism Adabas SVC / Entire Net-Work. For example, all broker commands issued by client or server components using this transport mechanism:								
1-65534	R	Z			b			
Defines the unique DBID for EntireX Broker. Used for internode Adabas/Entire Net-Work communication. There is no default; the value of NODE must be a value greater than or equal to 1 or less than or equal to 65534. If you set the parameter LOCAL=YES, you can use the same node number for different installations of EntireX Broker in an Entire Net-Work environment.								
<u>30</u> l <i>n</i>	О	z			b			
					results of			
<u>0</u> - 4	О	Z			b			
The level of tracing to be performed while the broker is running with transport method NET. It overrides the global value of trace level for all NET routines. 0 No tracing. Default value. 1 Display invalid Adabas commands. 2 All of trace level 1, plus errors if request entries could not be allocated. 3 All of trace level 2, plus all routines executed. 4 All of trace level 3, plus function arguments and return values. Trace levels 2, 3 and 4 should be used only when requested by Software AG Support. If you modify the TRACE-LEVEL attribute, you must restart the broker for the								
	The number of command query on the number of parallel at mechanism Adabas SVC / lissued by client or server of 1-65534 Defines the unique DBID for Used for internode Adabas, the value of NODE must be at to 65534. If you set the parameter different installations of 30 n This parameter sets the time a broker call must be received 0-4 The level of tracing to be permethod NET. It overrides to 0 No tracing. Default valued 1 Display invalid Adabas 2 All of trace level 1, plus 3 All of trace level 2, plus 4 All of trace level 3, plus 1 Trace levels 2, 3 and 4 shows Support. If you modify the TRACE-Lichange to take effect. For testing to the parameter sets the time a broker call must be received 1.	The number of command queue elements on the number of parallel active brokes mechanism Adabas SVC / Entire Netrissued by client or server components. 1-65534 R Defines the unique DBID for EntireX. Used for internode Adabas/Entire Netron the value of NODE must be a value great to 65534. If you set the parameter LOCA for different installations of EntireX Brown and the service of the service	The number of command queue elements require on the number of parallel active broker calls that mechanism Adabas SVC / Entire Net-Work. For issued by client or server components using this 1-65534 R z Defines the unique DBID for EntireX Broker. Used for internode Adabas/Entire Net-Work components using this to 65534. If you set the parameter LOCAL=YES, you for different installations of EntireX Broker in an above call must be received by the caller with a broker call must be received by the caller with 0-4 Oz The level of tracing to be performed while the bromethod NET. It overrides the global value of trace 1 Display invalid Adabas commands. 2 All of trace level 1, plus errors if request entrowants and trace level 2, plus all routines executed 4 All of trace level 3, plus function arguments at 1 Trace levels 2, 3 and 4 should be used only whe support. If you modify the TRACE-LEVEL attribute, you rechange to take effect. For temporary changes to 1	The number of command queue elements required to handle on the number of parallel active broker calls that are using mechanism Adabas SVC / Entire Net-Work. For example, issued by client or server components using this transport. 1 - 65534 R Z Defines the unique DBID for EntireX Broker. Used for internode Adabas/Entire Net-Work communication the value of NODE must be a value greater than or equal to a to 65534. If you set the parameter LOCAL=YES, you can use the for different installations of EntireX Broker in an Entire Network above realls in sea a broker call must be received by the caller within this time. 1	The number of command queue elements required to handle broker call on the number of parallel active broker calls that are using the transport mechanism Adabas SVC / Entire Net-Work. For example, all broker of issued by client or server components using this transport mechanism. 1 - 65534 R Z Defines the unique DBID for EntireX Broker. Used for internode Adabas/Entire Net-Work communication. There is not the value of NODE must be a value greater than or equal to 1 or less that to 65534. If you set the parameter LOCAL=YES, you can use the same not for different installations of EntireX Broker in an Entire Net-Work environment of the parameter sets the timeout value for broker calls in seconds. The abroker call must be received by the caller within this time limit. 1			

Security-specific Attributes

The security-specific attribute section begins with the keyword <code>DEFAULTS=SECURITY</code> as shown in the sample attribute file. This section applies only if broker-specific attribute <code>SECURITY=YES</code> is specified.

	Opt/ Operating System						
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000	
ACCESS-SECURITY-	NO I YES	0				b	
SERVER	Determines where authors NO Authentication is o	hecked in th	e broker task			be running	
	y ES Authentication is of does not require be Server for BS2000.	checked in th	e EntireX Br	oker Security	y Server for E		
APPLICATION-NAME	A8	О	Z				
	Specifies the name of the In RACF, for example, a defined with following RDEFINE APPL BROKER PERMIT BROKER CLASS SETROPTS CLASSACT() See attribute FACILITY	n application commands: R UACC(NON S(APPL) ID	n BROKER wi E) (DOE) ACCE	th read perm			
AUTHORIZATION-	YES I NO	О		u	W		
DEFAULT	Determines whether access is granted to a specified service if the specified service coul not be found listed in the repository of authorization rules or in section <code>DEFAULTS=AUTHORIZATION-RULES</code> of the attribute file. YES Grant access. NO Deny access. Applies only when using EntireX Security under UNIX and Windows. Authorization rules can be stored within a repository. When an authorization call occurs, EntireX Security uses the values of this parameter to perform an access check for a particular broker instance against an (authenticated) user ID and list of rules.						
CHECK-IP-ADDRESS	See also <i>Authorization R</i> YES NO	1	-				
 		O TCP/IP add	Z Iross of the s	llon io ordia	et to a massacr	yoo ahaala	
	Determines whether the	e i CP/IP ado	iress of the ca	aner is subjec	ct to a resour	ce cneck.	

		Opt/ Operating System							
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000			
ERRTXT-MODULE	NA2MSGO NA2MSG1 NA2MSG2 ModuleName	0	Z						
	Specifies the name of the messages. For instruction <i>Messages</i> (<i>Optional</i>) under	ons on how to	o customize	messages, se	e Build Lang				
FACILITY-CHECK	<u>NO</u> I YES	О	Z						
	It is possible to check where the user is not allowed and does not try to authorize the user's password being performed first. See attraction where the user's password being performed first. See attraction where the user's password being performed first. See attraction where the user's password being performed first. See attraction where the user's password being performed first see attraction where the user's password being performed first.	ssword check owed to use the tenticate the ag revoked; ibute APPLI	t. The advanthis applications. Failing this situation CATION-NAM	tage of this a on, the broke an authentic is avoided i E for further	dditional cher returns ereation checker the facility details.	eck is that ror 00080013 may lead to check is			
	before each authentication call.								
IGNORE-STOKEN	<u>NO</u> I YES	О	Z	u	w	b			
	Determines whether the value of the ACI field SECURITY-TOKEN is verified on each call.								
INCLUDE-CLASS	YES I NO	О	Z						
	Determines whether the	class name	is included i	n the resour	ce check.				
INCLUDE-NAME	YES I NO	0	Z						
	Determines whether the	server nam	e is included	in the resou	rce check.				
INCLUDE-SERVICE	YES I NO	О	Z						
	Determines whether the	service nam	ne is included	d in the reso	urce check.				
LDAP-	ldapUrl	О		u	w				
AUTHENTICATION- URL	Authentication is performed against the LDAP repository specified under <code>ldapUrl</code> . TCP Specify repository URL:								
	LDAP-AUTHENTICATION-URL="ldap://HostName[:PortNumber]" SSL/TLS Specify repository URL with ldaps:								

		Opt/		Operating System				
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000		
LDAP- AUTHORIZATION-	If no port number is specific transport. Example LDAP - AUTHENTICATION LDAP - AUTHENTICATION LDAP - AUTHENTICATION ldapUrl	ecified, the des for TCP ar N-URL="1da N-URL="1da	efault is the sand SSL/TLS: p://myhostps://myhos	standard LD. c.mydomain st.mydomai	AP port num .com" n.com:636"			
URL	Authorization is performed against the LDAP repository specified under \$\frac{7}{dapUr}\$? TCP Specify repository URL: LDAP-AUTHORIZATION-URL="ldap://HostName[:PortNumber]" If no port number is specified, the default is the standard LDAP port number 389 for TCP transport. Example for TCP: LDAP-AUTHORIZATION-URL="ldap://myhost.mydomain.com:389" This attribute replaces the parameters host, port and protocol in the \$xds.ini\$ file.							
LDAP - AUTH - DN	EntireX version 9.10 and authDN	О		u	W			
	For authenticated access cn=admin,dc=softwar This attribute replaces p below.	re-ag,dc=d parameter au	e					
LDAP-AUTH-PASSWD- ENCRYPTED	For authenticated access to the LDAP server. Specifies the encrypted value of the use password. Use program etbnattr to get the encrypted password: etbnattr -x clear_text_password -echo_password_only This writes the encrypted password to standard output. This attribute replaces parameter authPass in the xds.ini file of EntireX version 9.10 and below.							
LDAP- AUTHORIZATION- RULE	A32	0		u	W			

		Opt/	Operating System						
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000			
	List of authorization rules. Multiple sets of rules can be defined, each set is limited to 32 chars. The maximum number of LDAP-AUTHORIZATION-RULE entries in the attribute file is 16. Applies only when using EntireX Security under UNIX or Windows and SECURITY-SYSTEM=1dapUr1. Authorization rules can be stored in an LDAP repository. When an authorization call occurs, EntireX Security uses the values of this parameter and AUTHORIZATION-DEFAULT to perform an access check for a particular broker instance against an (authenticated) user ID and list of rules.								
LDAP-BASE-DN	See also Authorization RabaseDN	0		u	W				
	Specifies the base distinguished name of the directory object that is the root of all objects for authorization rules. Default value: dc=software-ag,dc=de This attribute replaces parameter baseDN in the xds.ini file of EntireX version 9.10 and below.								
LDAP-PERSON-BASE-	1 dapDn	О		u	W				
BINDDN LDAP-REPOSITORY-	Used with LDAP authen information is stored. To Example: LDAP-PERSON-BASE-BE OPENLDAP	his value is p	orefixed with	the user ID	field name (s				
TYPE	ActiveDirectory I SunOneDirectory I Tivoli I Novell I ApacheDS			u	V				
	Use predefined known to type that most closely me Directory, the user ID is	natches your	actual repos	itory. In the	case of Wind				
LDAP-SASL-	<u>NO</u> I YES	О			W				
AUTHENTICATION	Specifies whether or not Simple Authentication and Security Layer (SASL) is to perform the authentication check. In practice, this determines whether or not the password supplied by the user is passed in plain text between the broker kernel and the LDA server. If SASL is activated, this implies that the password is encrypted. NO Password is sent to LDAP server in plain text. YES Password is sent to LDAP server encrypted.								
LDAP-USERID-FIELD	<u>cn</u> <i>uidFieldName</i>	О		u	W				

		Opt/		Operati	ng System				
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000			
	Used with LDAP authe Distinguished Name, fo	or example:	specify the fi	rst field nan	ne of a user in	the			
	LDAP-USERID-FIELD=		T	1		ı			
MAX-SAF-PROF- LENGTH	1-256	О	Z						
LENGTH	This parameter should length of the profile con This parameter defaults	nprising " <cl< td=""><td>ass>.<server< td=""><td>:>.<service>'</service></td><td></td><td></td></server<></td></cl<>	ass>. <server< td=""><td>:>.<service>'</service></td><td></td><td></td></server<>	:>. <service>'</service>					
PASSWORD-TO-	NO I YES	0							
UPPER-CASE		Determines whether the password and new password are converted to uppercase							
PRODUCT	RACF ACF2 TOP-SECRET	О	Z						
	Specifies the name of the security-system-specific					•			
	RACF Security system RACF is installed. Default.								
	ACF2 Security system ACF2 is installed.								
	TOP-SECRET Security system CA Top Secret is installed.								
	The default value is use	d if an incor	rect or no va	lue is specif	fied.				
PROPAGATE-	YES I NO	О	Z						
TRUSTED-USERID	Determines whether a clis propagated to a serve		•) mechanism			
SAF-CLASS	NBKSAG SAFClassName	О	Z						
	Specifies the name of the profiles.	e SAF class/i	type used to	hold the En	ntireX-related	resource			
SAF-CLASS-IP	NBKSAG SAFClassName	O	Z						
	Specifies the name of the checks.	SAF class/ty	pe used whe	en performin	ıg IP address a	uthorization			
SECURITY-LEVEL	AUTHORIZATION I AUTHENTICATION	О	Z	u	W	b			
	Specifies the mode of operation Automotion A	horization ar	nd authentic	ration (not u	nder BS2000).				
	Note: In version 8.0, the	e default valu	ue for this pa	arameter wa	s AUTHORIZA	TION.			

		Opt/		Operating System					
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000			
SECURITY-NODE	YES I name	0	Z						
	This parameter can be used to specify a prefix that is added to all authorization of enabling different broker kernels, in different environments, to perform separate authorization checks according to each broker kernel. For example, it is often implete distinguish between production, test, and development environments. YES This causes the broker ID to be used as a prefix for all authorization check name This causes the actual text (maximum 8 characters) to be prefixed onto all authorization checks. Note: By not setting this parameter, no prefix is added to the resource check (the displacement).								
	behavior).				T				
SECURITY-SYSTEM	OS I LDAP	О	Z	u	W	b			
	OS Authentication is performed against the local operating system. Default if SECURITY=YES is specified and section DEFAULTS=SECURITY is omitted from the attribute file. LDAP Authentication and authorization are performed against the LDAP repository specified under LDAP-AUTHENTICATION-URL and LDAP-AUTHORIZATION-URL.								
TRACE-LEVEL	<u>0</u> - 4	О	Z	u	W	b			
	Trace level for EntireX Security. It overrides the global value of trace level in the attribute file. 0 No tracing. Default value. 1 Log security violations and access denied/permitted. 2 All of trace level 1, plus internal errors. 3 All of trace level 2, plus function entered/exit messages with argument values and some progress messages. 4 All of trace level 3, plus some selected data areas for problem analysis. Trace levels 2, 3 and 4 should be used only when requested by Software AG Support. If you modify the TRACE-LEVEL attribute, you must restart the broker for the change to take effect. For temporary changes to TRACE-LEVEL without a broker restart, use the EntireX Broker command-line utility ETBCMD. Note: Setting this value also affects tracing for authorization rules.								
TRUSTED-USERID	YES I NO	0	z						
JOTES JOENTS	Activates the trusted us Adabas IPC mechanism	er ID mecha		ker requests	arriving ove	r the local			
USERID-TO-	NO I YES	О	z						

		Opt/	Operating System						
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000			
UPPER-CASE	Determines whether us	Determines whether user ID is converted to uppercase before verification.							
UNIVERSAL	NO I YES	О	z						
	Determines whether acc	Determines whether access to undefined resource profiles is allowed.							
WARN-MODE	NO I YES	О	Z	u	W	b			
	Determines whether a resource check failure results in just a warning or an error.								

TCP/IP-specific Attributes

The TCP/IP-specific attribute section begins with the keyword <code>DEFAULTS=TCP</code> as shown in the sample attribute file. It contains attributes that apply to the TCP/IP transport communicator. The transport is activated by <code>TRANSPORT=TCP</code> in the Broker-specific section of the attribute file. A maximum of five TCP/IP communicators can be activated by <code>specifying</code> up to five <code>HOST/PORT</code> pairs.

		Opt/ Operating System						
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000		
CERT-AUTHENTICATION	NO I YES	О	z					
	NO Do not use SSL certificates for authentication. YES Use corresponding port for certificate-based authentication. See <i>Using SSL Certificates for Authentication</i> in the EntireX Security documentation for z/OS.							
CONNECTION-NONACT	n I nS I nM I nH	О	z	u	w	b		
	Non-activity of the TCP/IP connection, after which a close is performed and the connection resources are freed. If this parameter is not specified here, broker will close the connection only when the application (or the network itself) terminates the connection. n Same as nS. nS Non-activity time in seconds (min. 600, max. 2147483647). nM Non-activity time in minutes (min. 10, max. 35791394). nH Non-activity time in hours (max. 596523). If not specified, the connection non-activity test is disabled. On the stub side, non-activity can be set with the environment variable ETB_NONACT. See <i>Limiting the TCP/IP Connection Lifetime</i> under z/OS UNIX Windows z/VSE in the							
HOST	0.0.0.0 hostname IP address	О	Z	u	W	b		
	The address of the network interface on which broker will listen for connection requests. If HOST is not specified, broker will listen on any attached interface adapter of the system (or stack). A maximum of five HOST/PORT pairs can be specified to start multiple instances of broker's TCP/IP transport communicator.							
MAX-MESSAGE-LENGTH	2147483647 n	О	z	u	w	b		

		Opt/	Operating System					
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000		
	Maximum message size TCP/IP. The default valustored in a four-byte int	ae represen		•				
PORT	1025-65535	0	Z	u	w	b		
	The TCP/IP port number	r on which	the broker	will listen fo	or connectio	n requests.		
	If not specified, the brok TCP/IP services file, using the default value of 197	ng getserv	•		•			
	A maximum of five HOS of broker's TCP/IP trans	_	_	ecified to s	tart multipl	e instances		
	Example for multiple po	orts on z/OS	5:					
	HOST=localhost, PORT=3930 HOST=0.0.0.0, PORT=3931							
	Port 3930 is used for <i>local</i> TCP/IP communication only and is not visible outside the z/OS host.							
	■ Port 3931 is used for <i>global</i> TCP/IP communication. With IBM's AT-TLS this port is turned into a TLS port, see <i>Running Broker with SSL/TLS Transport</i> in the z/OS Administration documentation.							
	With this configuration you can reach the broker from outside the z/OS host via the secure TLS connection only (port 3931). The TCP connection (port 3930) can only be used from inside the z/OS host.							
RESTART	YES I NO	О	Z	u	w	b		
	YES The broker kernel	will not try	to restart tl	ne TCP/IP o				
	This setting applies to a	_	ommunicat	ors.	T			
RETRY-LIMIT	20 n UNLIM Maximum number of at	-		u CP/IP com	w municator. T	b This setting		
DETDY TIME	applies to all TCP/IP con	_		Ι		,		
RETRY-TIME	3M n nS nM nH O z u w b Wait time between stopping the TCP/IP communicator due to an unrecoverable error and the next attempt to restart it.							
	n Same as nS.nS Wait time in secondnM Wait time in minute	s (max. 214	7483647).					

		Opt/	Opt/ Operating System							
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000				
	<i>n</i> H Wait time in hours (max. 596523).									
	Minimum wait time is	1S.								
	This setting applies to a	all TCP/IP co	ommunicat	ors.						
REUSE-ADDRESS	YES I NO	О	z	u		b				
	YES I <u>NO</u>	0			w					
	YES The TCP port assigned to the broker can be taken over and assigned to other applications (this is the default value on all non-Windows platforms). NO The TCP port assigned to the broker cannot be taken over and assigned to other applications. This is the default setting on Windows, and we strongly advise you do not change this value on this platform. Note: This setting might be required at your site when restarting broker immediately after stopping it. This is due to the inherent latency of the TCP/IP stack when closing connections.									
STACK-NAME	StackName	О	z							
	Name of the TCP/IP stack that the broker is using. If not specified, broker will connect to the default TCP/IP stack running on the machine.									
TRACE-LEVEL	<u>0</u> - 4	О	z	u	w	b				
	The level of tracing to be performed while the broker is running with transport method TCP/IP. It overrides the global value of trace level for all TCP/IP routines.									
	0 No tracing. Default v	value.								
	1 Display IP address o error responses.	of incoming	request, dis	play error ı	number of c	outgoing				
	2 All of trace level 1, p	lus errors if	request ent	ries could 1	not be alloca	ated.				
	3 All of trace level 2, p	lus all routi	nes execute	d.						
	4 All of trace level 3, plus function arguments and return values.									
	Trace levels 2, 3 and 4 should be used only when requested by Software AG Support.									
	If you modify the TRACE-LEVEL attribute, you must restart the broker for the change to take effect. For temporary changes to TRACE-LEVEL without a broker restart, use the EntireX Broker command-line utility ETBCMD.									

c-tree-specific Attributes

The c-tree-specific attribute section begins with the keyword <code>DEFAULTS = CTREE</code>. The attributes in this section are optional. This section applies only if <code>PSTORE-TYPE = CTREE</code> is specified.

Not available under z/OS or BS2000.

		Opt/		Operatin	g System					
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000				
COMPATIBILITY	NO I YES	О		u	W					
	Determines whether the following c-tree parameters are set:									
	■ COMPATIBILITY PREV610A_FLUSH									
	■ COMPATIBILITY FDATASYNC									
	■ SUPPRESS_LOG_FLUSH YES									
	■ PREIMAGE_DUMP YES									
	See your FairCom documentation for a description of these parameters.									
	NO The c-tree parameters listed above are not set. Default.									
	YES The c-tree parameters listed above are set. This provides compatibility with c-tree behavior prior to EntireX Broker 10.5.									
FLUSH-DIR	YES I NO	O		u	w					
	Controls whether metadata is flushed to disk immediately after creates, renames, and deletes of transaction log files and transaction-dependent files.									
	YES Metadata is flushed to disk.									
	NO Metadata is not flu prior to EntireX Br FairCom documen	oker version	10.5. See COM	1PATIBÎLITY	/ NO_FLUSH_					
MAXSIZE	n I nM I nG	О		u	w					
	Defines the maximum size of c-tree data files. Broker allocates one data file for control data and another data file for message data:									
	n Maximum size in MB.									
	nM Maximum size in MB.									
	nG Maximum size in GB.									
PAGESIZE	n I nK	О		u	w					
	Determines how many l required after changing	•	ilable in each	c-tree node.	PSTORE COL	D start is				

		Opt/		Operatin	g System				
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000			
	 n Same as nK nK PAGESIZE in KB. The default and minimular If PSD Reason Code = PAGESIZE value and resto a new PSTORE with a and define the increased 	527 is retu start broker v an increased	rned during vith PSTORE= PAGESIZE va	=COLD, or mig alue. See <i>Mig</i>	grate the exist	ting PSTORE			
PATH	A255	О		u	w				
	Path name of the target directory for c-tree index and data files.								
SYNCIO	<u>NO</u> I YES	0		u	w				
	YES c-tree transaction log is opened in synchronous mode to improve data security. It may degrade performance of PSTORE operations, but offers the highest level of data security. See <i>c-tree Database as Persistent Store</i> in the UNIX Windows Administration documentation.								
TRACE-LEVEL	<u>0</u> - 4	О		u	w				
	Trace level for c-tree persistent store. It overrides the global value of trace level in the attribute file. 0 No tracing. Default value. 1 Log memory allocation failures and errors during close of files.								
	2 n/a								
	 3 All of trace level 1, plus UOWID in use for the various c-tree requests and function entered/exit mesages. 4 All of trace level 3, plus returned function values. 								
	Trace levels 2, 3 and 4 should be used only when requested by Software AG Support.								
	If you modify the TRACE-LEVEL attribute, you must restart the broker for the change to take effect. For temporary changes to TRACE-LEVEL without a broker restart, use the EntireX Broker command-line utility ETBCMD.								

SSL/TLS-specific Attributes

The Broker can use Secure Sockets Layer/Transport Layer Security (SSL/TLS) as the transport medium. The term "SSL" in this section refers to both SSL and TLS. RPC-based clients and servers, as well as ACI clients and servers, are always SSL clients. The broker is always the SSL server. For an introduction see *SSL/TLS*, *HTTP(S)*, and *Certificates with EntireX*. Your operating system determines whether this section of the attribute file is required:

■ z/OS

The SSL-specific attribute section is not used. You can use IBM's Application Transparent Transport Layer Security (AT-TLS).

See Running Broker with SSL/TLS Transport in the z/OS Administration documentation.

UNIX and Windows

The SSL-specific attribute section is required, and begins with the keyword DEFAULTS=SSL as shown in the sample attribute file.

The attributes in this section are needed to execute the SSL communicator of the EntireX Broker kernel.

See also *Running Broker with SSL/TLS Transport* under UNIX | Windows.

		Operating System				
Attribute	Values	Opt/ Req	z/OS	UNIX	Windows	BS2000
CIPHER-SUITE	string	О		u	W	b
	String that is passed to the standardized protocol the symmetric and asymmetric in the SSL/TLS stack; othe both parties agree by "hand key lengths used. It both sides are capable of CIPHER-SUITE for the Server side). Thus stubs clients. Under UNIX, Windows The SSL protocol is obsessuccessor of SSL and is successor	at uses difference on the control of	erent crypto ion etc.). So onal. When on the ciph scenario, the influenced right the broker of longer available in Open uses FIPS nonymous The resulting on:	graphic furme of these an SSL/TLS are suite, the distinction in SSL implemental and thereby allable. The penSSL appropries and the penSSL appropries are of ciples and ciples are of ciples are and ciples are of ciples are	nctions (hash must be im S connection at is, the algorithm tion dependent the attributed ways impley become the mentation in the TLS protocome roved ciphed man (ADH ther suites page	n functions, plemented is created, gorithms ds on what e ements the ne SSL/TLS is used.

		Opt/		Operatin	g System		
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000	
	See https://www.openss	sl.org/docs/	man1.1.1/n	nan1/cipher	rs.		
CONNECTION-NONACT	n I nS I nM I nH	О		u	w	b	
	Non-activity of the SSL connection resources ar will close the connection terminates the connection	e freed. If the nonly whe	his parame	ter is not sp	pecified her	e, broker	
	n Same as nS.						
	nS Non-activity time ir	n seconds (1	min. 600, m	ax. 2147483	3647).		
	nM Non-activity time in	n minutes (1	min. 10, ma	ıx. 3579139	4).		
	nH Non-activity time in hours (max. 596523).						
	If not specified, the con	nection nor	n-activity te	st is disabl	ed.		
HOST	hostname	О		u	w	b	
	The address of the netw requests. If HOST is not specified, the system (or stack). A maximum of five HOS	broker will	l listen on a rs can be sp	ny attache	d interface a	adapter of	
KEY-FILE	of EntireX Broker's TCP		ort commur		T	1-	
NET FILE	File that contains the br test purposes, EntireX d SSL/TLS Sample Certifica	lelivers cert tes Delivere	tificates for d with Entir	use on var reX.			
	Example for UNIX and						
	Note: EntireX Broker do.jks).	oes not sup	port Java c	ertificates (keystore file	es of type	
KEY-PASSWD	password (A32)	R	1	u	W	b	
KET TASSIE	Password used to prote MyAppKey.pem. Deprec	ct the priva		ocks the KE	Y-FILE, fo		
KEY-PASSWD-ENCRYPTED	•	R		u	w	b	
	Password used to protect the private key. Unlocks the KEY-FILE, for example MyAppKey.pem. This attribute replaces KEY-PASSWD to avoid a clear-text password as attribute value. If KEY-PASSWD and KEY-PASSWD-ENCRYTPED are both supplied, KEY-PASSWD-ENCRYTPED takes precedence.						
	Use program etbnattr	to get the	encrypted :	password:			

		Operating System					
Attribute	Values	Opt/ Req	z/OS	UNIX	Windows	BS2000	
	etbnattr -w ssl_ke	y_passwor	decho <u></u>	_password	l_only		
	This writes the encrypte	ed passwor	d to standa	rd output.			
KEY-STORE	filename	R		u	w	b	
	SSL certificate; may concertificates for use on varieth EntireX.	•	•				
	Example for UNIX and	Windows:	ExxAppCer	t.рет.			
	Note: EntireX Broker do	oes not sup	port Java c	ertificates (l	keystore file	es of type	
MAX-MESSAGE-LENGTH	.jks). 2147483647 n	О				b	
MAX-MESSAGE-LENGIA			1 1	u	· ·		
	Maximum message size that the broker kernel can process using transport method SSL. The default value represents the highest positive number that can be stored in a four-byte integer.						
PORT	1025-65535	О		u	w	b	
	The SSL port number on which the broker will listen for connection requests. If not changed, this parameter takes the standard value as specified in the sample attribute file. If the port number is not specified, the broker will use the default value of 1958.						
RESTART	YES I NO	О		u	W	b	
	YES The broker kernel the default value). NO The broker kernel	_					
RETRY-LIMIT	<u>20</u> <i>n</i> UNLIM	О		u	w	b	
	Maximum number of at		estart the S	SSL commu	nicator.		
RETRY-TIME	<u>3M</u> <i>n</i> <i>n</i> S <i>n</i> M <i>n</i> H	0		u	w	b	
Wait time between suspending SSL communication due to unrecoveral and the next attempt to restart it. n Same as nS. nS Wait time in seconds (max.2147483647). nM Wait time in minutes (max. 35791394). nH Wait time in hours (max. 596523).							
	Minimum: 1S						
REUSE-ADDRESS	YES I NO	О		u	w	b	
	L.	i .		i .	1		

		Operating System						
Attribute	Values	Opt/ Req	z/OS	UNIX	Windows	BS2000		
	YES The SSL port assig				ver and assi	gned to		
	 NO The SSL port assigned to the broker cannot be taken over and assigned to other applications. Note: This setting might be required at your site when restarting broker immediately after stopping it. This is due to the inherent latency of the TCP/IP stack when closing connections. 							
STACK-NAME	name	О		u	w			
	Name of the TCP/IP sta	ck that the	broker is u	sing.				
	If not specified, broker machine.	will connec	t to the def	ault TCP/II	P stack runr	iing on the		
TRACE-LEVEL	<u>0</u> - 4	О		u	w	b		
TRUCT CTORE	D-4 O u w b The level of tracing to be performed while the broker is running with transport method SSL/TLS. It overrides the global value of trace level for all SSL/TLS routines. O No tracing. Default value. Display IP address of incoming request, display error number of outgoing error responses. All of trace level 1, plus errors if request entries could not be allocated. All of trace level 2, plus all routines executed. All of trace level 3, plus function arguments and return values. Trace levels 2, 3 and 4 should be used only when requested by Software AG Support. If you modify the TRACE-LEVEL attribute, you must restart the broker for the change to take effect. For temporary changes to TRACE-LEVEL without a broker							
TRUST-STORE	filename keyring	R		u	w	b		
	Location of the store containing certificates of trust Certificate Authorities (or CAs). Specify the file name of the CA certificate store. Examples: EXXCACERT. PEM,							
	C:\Certs\ExxCACert							
VERIFY-CLIENT	NO I YES	О		u	w	b		
	YES Additional client of NO No client certificat		•					

	Opt/		Operating System				
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000	
	For more information see <i>SSL/TLS</i> , <i>HTTP</i> (<i>S</i>), and <i>Certificates with EntireX</i> .						

DIV-specific Attributes

These attributes define a persistent store that is implemented as a VSAM linear data set (LDS) accessed using Data In Virtual (DIV). This DIV persistent store is a container for units of work. The DIV-specific attribute section begins with the keyword <code>DEFAULTS = DIV</code>. The attributes in this section are required if <code>PSTORE-TYPE = DIV</code> is specified.



Note: All attributes except the deprecated DIV were introduced with EntireX version 9.12. They replace the *Format Parameters* of earlier versions, which are deprecated but still supported for compatibility reasons.

		Opt/		Operatin	g System			
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000		
DIV	A511	0	z					
	The VSAM persistent store parameters, enclosed in double quotes (""). The value can span more than one line.							
	Note: Deprecated. This attribute is applicable only if you are supplying the persistent store parameters using <i>Format Parameters</i> of earlier versions. We recommend you use the attributes below that were introduced with EntireX 9.12 instead.							
DATASPACE-NAME	A8	О	z					
DATASPACE-PAGES	Defines the name of the dataspace that will be used to map the persistent store. Default value is DSPSTORE.							
DATASPACE-PAGES	126-524284	О	z					
	Defines the size of the dataspace used to map the persistent store (size=DATASPACE-PAGES * 4 KB). We recommend using the maximum value. Default value is 2048.							
DDNAME	A8	R	z					
	Defines the JCL DDNAME	that will be	used to acce	ess the persis	tent store.			
STORE	A8	R	Z					
	Defines an internal nam	e that is use	d to identify	the persister	nt store.			
TRACE-LEVEL	<u>0</u> - 4	О	Z					
	Trace level for DIV. It overrides the global value of trace level in the attribute file. 0 No tracing. Default value. 1 Log selected DIV SAVE calls taking longer than 2 seconds elapsed time. 2 n/a 3 All of trace level 1, plus UOWID in use for the various DIV requests. 4 n/a							

		Opt/	Operating System			
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000
	Trace levels 2, 3 and 4 sl If you modify the TRAC to take effect. For tempo the EntireX Broker com	E-LEVEL attr orary change	ribute, you m s to TRACE-I	nust restart t	he broker foi	r the change

Adabas-specific Attributes

The Adabas-specific attribute section begins with the keyword <code>DEFAULTS = ADABAS</code>. The attributes in this section are required if <code>PSTORE-TYPE = ADABAS</code> is specified. In previous versions of EntireX, these Adabas-specific attributes and values were specified in the broker-specific <code>PSTORE-TYPE</code> attribute.

		Opt/	Operating System					
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000		
BLKSIZE	126-20000	О	Z	u	W	b		
	Optional blocking factor used for message data. If not specified, broker will split the message data into 2 KB blocks to be stored in Adabas records. The maximum value depends on the physical device assigned to data storage. See the <i>Adabas</i> documentation. For reasons of efficiency, do not specify a BLKSIZE much larger than the actual total size of the UOW data to be written. The total UOW size is the sum of all messages in the UOW plus 41 bytes of header information. This takes effect only after COLD start. The BLKSIZE parameter applies only for a cold start of broker; subsequently the value of BLKSIZE is taken from the last cold start.							
DBID	Default value is 2000.	R	z	u	w	b		
5515	Database ID of Adabas							
FNR	1-32535	R	z	u	w	b		
	File number of broker persistent store file.							
FORCE-COLD	<u>N</u> I Y	О	z	u	w	b		
	Determines whether a behas been used by anoth Specify Y to allow existi	er broker ID a	and/or platfor	rm.	e a persistent	store file that		
MAXSCAN	<u>0</u> l n	О	Z	u	W	b		
	Limits display of persistent UOW information in the persistent store through Command and Information Services. Default value is 1000.							
OPENRQ	<u>N</u> I Y	О	z	u	W	b		
	Determines whether driver for Adabas persistent store is to issue an OPEN command to Adabas.							
SVC	200-255	R	z					
	Use this parameter to sp store driver.	pecify the Ada	nbas SVC nun	nber to be use	d by the Adal	pas persistent		

	Opt/ Operating System								
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000			
TRACE-LEVEL	<u>0</u> - 4	0	Z	u	W	b			
	Trace level for Adabas persistent store. It overrides the global value of trace level in the attribute file.								
	0 No tracing. Default v	alue.							
	1 Log selected Adabas CB fields (command code, response code, subcode, ISN, additions).								
	2 n/a								
	3 All of trace level 1, plus UOWID in use for the various Adabas requests and function entered/exit mesages.								
	4 All of trace level 3, plus more Adabas CB fields for successful requests and returned function values.								
	Trace levels 2, 3 and 4 should be used only when requested by Software AG Support.								
	If you modify the TRACE-LEVEL attribute, you must restart the broker for the change to take effect. For temporary changes to TRACE-LEVEL without a broker restart, use the EntireX Broker command-line utility ETBCMD.								

Application Monitoring-specific Attributes

The application monitoring-specific attribute section begins with the keyword DEFAULTS=APPLICATION-MONITORING. It contains attributes that apply to the application monitoring functionality. At startup time, the attributes are read if the Broker-specific attribute APPLICATION-MONITORING=YES is specified. Duplicate or missing values are treated as errors. When an error occurs, application monitoring is turned off and EntireX Broker continues execution. See the separate Application Monitoring documentation.

		Opt/		Operatin	g System			
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000		
APPLICATION-MONITORING	A100	0	z	u	w	b		
- NAME or APPMON - NAME	Specifies a default application monitoring name. Used to set the value of the ApplicationName KPI.							
COLLECTOR-BROKER-ID	A64	R	z	u	w	b		
	Identifies the Application Monitoring Data Collector. Has the format <code>host_name:port_number</code> , where where <code>host_name</code> is the host where the Application Monitoring Data Collector is running, and <code>port_number</code> is the port number of the Application Monitoring Data Collector.					ng Data		
	The default port is 57900.							
TRACE-LEVEL	<u>0</u> - 4	0	z	u	w	b		
	The level of tracing to be performed while the broker is running with application monitoring. 0 No tracing. Default value.							
	1 Display application monitoring errors.							
	2 All of trace level 1, plus measuring points for application monitoring.3 All of trace level 2, plus function entered/exit messages with argument values and monitoring buffers.							
	4 All of trace level 3, plus returned function values.							
	Trace levels 2, 3 and 4 should be used only when requested by Software AG Support.							
	If you modify the TRACE-LEVEL attribute, you must restart the broker for the change to take effect. TRACE-LEVEL cannot be changed dynamically for application monitoring.							

Authorization Rule-specific Attributes

The authorization rule-specific attribute section begins with the keyword DEFAULTS=AUTHORIZATION-RULES. It contains attributes that enhance security-related definitions. At startup time, the attributes are read if the following conditions are met:

- Broker-specific attribute SECURITY=YES
- Security-specific attributes SECURITY-SYSTEM=OS and SECURITY-LEVEL=AUTHORIZATION

When an error occurs, the EntireX Broker stops. See *Authorization Rules*.

		Opt/	ot/ Operating System					
Attribute	Values	Req	z/OS	UNIX	Windows	BS2000		
RULE-NAME	A32	R		u	W			
	Specifies a rule name. A server user IDs. All user this rule. See example u	s defined in	a rule are au	thorized to u	ase all service			
CLASS	A32	R		u	w			
SERVICE	These three attributes together identify the service. CLASS must be specified first, followed immediately by SERVER and SERVICE. <i>Wildcard Service Definitions</i> are allowed.							
CLIENT-USER-ID	A32	R		u	W			
	Defines an authorized client user ID.							
SERVER-USER-ID	A32	R		u	W			
	Defines an authorized se	erver user ID).					

Variable Definition File

The broker attribute file contains the configuration of one EntireX Broker instance. In order to share attribute files between different brokers, you identify the attributes that are unique and move them to a variable definition file. This file enables you to share one attribute file among different brokers. Each broker in such a scenario requires its own variable definition file.

The following attributes are considered unique for each machine:

- BROKER-ID (in *Broker-specific Attributes*)
- NODE (in Adabas SVC/Entire Net-Work-specific Attributes)
- PORT (in SSL/TLS-specific Attributes and TCP/IP-specific Attributes)

How you use the variable definition file will depend upon your particular needs. For instance, some optional attributes may require uniqueness - for example, DBID and FNR in DEFAULTS=ADABAS - so that you may specify the persistent store.

4 Configuring Broker for Internationalization

Configuring ICU Conversion	86
Building and Installing ICU Custom Converters	
Writing Translation User Exits	
Configuring Translation User Exits	
Writing SAGTRPC User Exits	
Configuring SAGTRPC User Exits	
Configuring SAGTRPC User Exits	99

Software internationalization is the process of designing products and services so that they can be adapted easily to a variety of different local languages and cultures. Internationalization within EntireX means internationalization of messages: the incoming and outgoing messages are converted to the desired codepage of the platform in use. This chapter explains in detail how to configure the broker for character conversion.

See also Internationalization with EntireX.

Configuring ICU Conversion

> To configure ICU conversion

- In the Broker attribute file, set the service-specific attribute CONVERSION. Examples:
 - ICU Conversion with SAGTCHA for *ACI-based Programming*:

```
CONVERSION=(SAGTCHA,OPTION=SUBSTITUTE)
```

■ ICU Conversion with SAGTRPC for *RPC-based Components* and *Reliable RPC*:

```
CONVERSION=(SAGTRPC,OPTION=STOP)
```

- 2 Optionally configure a CONVERSION OPTION to tune error behavior to meet your requirements; see *OPTION Values for Conversion*.
- For the Broker attribute, check if ICU conversion is possible, that is, the attribute ICU-CONVER-SION is either
 - not defined, its default is YES
 - set to YES

To configure locale string defaults (optional)

■ If the broker's locale string defaults do not match your requirements (see *Broker's Locale String Defaults*), we recommend you assign suitable locale string defaults for your country and region, see the respective attribute in *Codepage-specific Attributes* for how to customize the broker's locale string defaults.

> To customize mapping of locale strings (optional)

■ If the built-in locale string mapping mechanism does not match your requirements, you can assign specific codepages to locale strings. See *Broker's Built-in Locale String Mapping* and locale-string for information on customizing the mapping of locale strings to codepages.

Building and Installing ICU Custom Converters

User-written ICU custom-converters can be used for *ACI-based Programming*, *RPC-based Components*, and *Reliable RPC*. This section covers the following topics:

- Writing a User-written ICU Converter
- Compiling a User-written ICU Converter
- Installing a User-written ICU Converter

Writing a User-written ICU Converter

ICU uses algorithmic conversion, non-algorithmic conversion and combinations of both. See *ICU Conversion*. Non-algorithmic converters defined by the UCM format are the easiest way to define user-written ICU converters. See *UCM Format*.

To write a (non-algorithmic) user-written ICU converter

- Define the ICU converter file in UCM format using a text editor to meet your requirements.
 - **Note:** For further explanation of the UCM file format, see *ICU Resources*.

Writing algorithmic and partially algorithmic converters can be complex. However, they can be installed into EntireX in the same way as the table-driven, non-algorithmic ones. A description of how to write algorithmic and partially algorithmic converters is beyond the scope of this documentation. See the ICU documentation and other sources specified under *ICU Resources* for more information.

Compiling a User-written ICU Converter

To compile the user-written ICU converter

- Extract the ICU tool makeconv and ICU shared libraries as described under *Installing the EntireX ICU Custom Converter Build Environment under z/OS UNIX*.
- Compile the converter source files (extension .ucm) into binary converter files (extension ".cnv") using the ICU tool makeconv. Example:

makeconv -v myebcdic.ucm

This produces a binary converter file named *myebcdic.cnv*.



Caution: The binary format "cnv" depends on the endianness (big/little-endian) and character set family (ASCII/EBCDIC) of the computer where it is produced. For example, a binary converter file produced on a machine with big endianes cannot be executed on a machine with little-endian (and vice versa) or character set family *EBCDIC* cannot be executed on a machine with character set family *ASCII* (and vice versa). It is highly recommended to compile the converter source file(s) on the same target platform where the broker runs - otherwise unpredictable result may occur.

Installing a User-written ICU Converter

> To install the user-written ICU converter

1 Define the broker attribute ICU-DATA-DIRECTORY. See *Broker-specific Attributes*.

Example:

```
ICU DATA DIRECTORY="/home/sag/EntireX/config/etb"
```

2 Define the subdirectory icudt<icu-version><endianness> within the ICU-DATA-DIRECTORY

```
where <icu-version> is the ICU version used, for example 54, and <endianness> is "e" EBCDIC (big-endian)
```

Example:

/home/sag/EntireX/config/etb/icudt54e



Notes:

- 1. The subdirectory and its naming are given by ICU standard. It is not invented by Software AG.
- 2. See the Release Notes to determine the ICU version used by the broker you are running and form the correct name otherwise the user-written ICU converter will not be located.
- 3. There are also other approaches supported by ICU to locate converters. These approaches are (also) ICU version dependent. However, Software AG recommends the mechanism described above. See the ICU website for more information under *ICU Resources*.
- Copy the user-written ICU converter binary file (extension "cnv") to the referenced by ICU-DATA-DIRECTORY and its subdirectory defined under steps 1 and 2 above. Examples:

```
/home/sag/EntireX/config/etb/icudt54e/myebcdic.cnv
/home/sag/EntireX/config/etb/icudt54e/myascii.cnv
```

If the converter name is not sent as the locale string by your application, customize the mapping of locale strings by assigning the user-written ICU converter (codepage) to locale strings in the Broker attribute file, see locale-string for how to customize the mapping of locale strings to codepages. Example:

```
DEFAULTS=CODEPAGE
/* Customer-written ICU converter */
CP1140=myebcdic
CP0819=myascii
```

- For the Broker attribute, check whether ICU conversion is possible, that is, the attribute ICU-CONVERSION is not defined (default=YES) or set to YES.
- For the Broker attribute, check whether use of ICU custom converters is possible, that is, the attribute ICU-SET-DATA-DIRECTORY is not defined (default=YES) or set to YES.

Writing Translation User Exits

This section covers the following topics:

- Introduction
- Structure of the TRAP Control Block
- Using the TRAP Fields

Introduction

EntireX Broker provides an interface to enable user-written translation routines in the programming language Assembler. It contains three parameters:

- The address of the TRAP control block (TRAP = Translation Routine / Area for Parameters).
- The address of a temporary work area. It is aligned to fullword / long integer boundary (divisible by 4). The work area can only be used for temporary needs and is cleared after return.
- A fullword (long integer) that contains the length of the work area.
- **Note:** Names for user-written translation routines starting with "SAG" are reserved for Software AG usage and must not be used, e.g. "SAGTCHA" and "SAGTRPC".

Structure of the TRAP Control Block

The Assembler dummy section TR\$TRAP covers the layout of the TRAP control block:

```
TR$TRAP DSECT,
                 F
TR$TYPE DS
                              TRAP type
                 2
                              TRAP type ETB 121
TR$TYP2 EQU
                              Input buffer length
TR$ILEN DS
TR$IBUF DS
                 Α
                              Address of input buffer
                 F
                              Output buffer length
TR$OLEN DS
                              Address of output buffer
TR$OBUF DS
                              Length of data returned:
TR$DLEN DS
                              Should be set to the minimum value of TR$ILEN
                              and TR$OLEN.
TR$SHOST DS
                              Sender's host:
                              x'00000000' = little endian
                              x'00000001' = big endian
TR$SCODE DS
                              Sender's character set:
SEBCIBM EQU
                 X'00000022' EBCDIC (IBM)
                 X'00000042' EBCDIC (SNI)
SEBCSNI EQU
                 X'00000080' ASCII
SA88591 EQU
TR$RHOST DS
                              Receiver's host --> see TR$SHOST
TR$RCODE DS
                              Receiver's char set --> see TR$SCODE
                              BROKER host --> see TR$SHOST BROKER char set --> see TR$SCODE
                 F
TR$BHOST DS
TR$BCODE DS
                 F
TR$SENVA DS
                              Sender's ENVIRONMENT field supplied:
    EQU
                 X'00000000' ENVIRONMENT field not set
0FF
ON
       EQU
                 X'00000001' ENVIRONMENT field set
                              Receiver's ENVIRONMENT field supplied:
TR$RENVA DS
                              --> see TR$SENVA
TR$SENV DS
                 CL32
                              Sender's ENVIRONMENT field
                 CL32
TR$RENV DS
                              Receiver's ENVIRONMENT field
TR$LEN
        EQU
                 *-TR$TRAP
                              Length of TRAP
```

Using the TRAP Fields

The TR\$DLEN must be supplied by the user-written translation routine. It tells the Broker the length of the message of the translation. In our example its value is set to the minimum length of the input and output buffer.

All other TRAP fields are supplied by the Broker and must not be modified by the user-written translation routine.

The incoming message is located in a buffer pointed to by TR\$IBUF. The length (not to be exceeded) is supplied in TR\$ILEN. The character set information from the send buffer can be taken from TR\$SCODE.

The outgoing message must be written to the buffer pointed to by TR\$0BUF. The length of the output buffer is given in the field TR\$0LEN. The character set is specified in TR\$RCODE. If the addresses

given in TR\$IBUF and TR\$OBUF point to the same location, it is not necessary to copy the data from the input buffer to the output buffer.

The environment fields TR\$SENVA and TR\$RENVA are provided to handle site-dependent character set information. For the SEND and/or RECEIVE functions, you can specify data in the ENVIRONMENT field of the Broker ACI control block. This data is translated into the codepage of the platform where EntireX Broker is running (see field TR\$BCODE) and is available to the TR\$SENV or TR\$RENV field in the TRAP control block. TR\$SENVA or TR\$RENVA are set to 0N if environmental data is available. Any values given in the API field ENVIRONMENT must correspond to the values handled in the translation routine.

To assemble and link the SAGTCHA user-written translation routine

Assemble and link your translation routine. You can give the resulting load module any name that does not begin with "SAG". Names starting with "SAG", such as "SAGTCHA", are reserved for Software AG.

Configuring Translation User Exits

> To configure translation user exits

As a prerequisite, the user-written translation module must be accessible to the Broker worker threads.

- 1 Copy the user-written translation module into any library of the Broker's steplib concatenation.
- In the Broker attribute file, set the service-specific attribute TRANSLATION to the name of the user-written translation routine. Example:

TRANSLATION=MYTRANS

Writing SAGTRPC User Exits


This section covers the following topics:

- Introduction
- Structure of the User Exit Control Block
- Using the User Exit Interface Fields
- Character Set and Codepage

Introduction

EntireX Broker provides an interface to SAGTRPC user exit routines written in the programming language Assembler. The interface contains three parameters:

- The address of the UE (user exit) control block.
- The address of a temporary work area. It is aligned to a fullword / long-integer boundary (divisible by 4). The work area can only be used temporarily and is cleared after return.
- A fullword (long integer) that contains the length of the work area.



Structure of the User Exit Control Block

The Assembler dummy section UE\$CB shows the layout of the user exit control block.

	D0505			
UE\$CB	DSECT	,	User Exit Control Block	
*			*****	
*				Direction
*				
UE\$VERS	DS	F	UECB version	input
UE\$VER1	EQU	1	UECB version 1	
UE\$IBUF	DS	Α	Address of input buffer	input
UE\$ILEN	DS	F	Input buffer length	input
UE\$OBUF	DS	Α	Address of output buffer	input
UE\$OLEN	DS	F	Output buffer length	input
UE\$DLEN *	DS	F	Length of data returned	output
UE\$SHOST	DS	F	Senders host:	input
*			x'00000000' = little endian	
*			x'00000001' = big endian	
*				
UE\$SCODE	DS	F	Senders character set:	input
SEBCIBM	EQU X'	00000022'	EBCDIC (IBM)	
SEBCSNI	EQU X'	00000042'	EBCDIC (SNI)	
SA88591	EQU X'	00000080'	ASCII	
*				
UE\$RHOST	DS	F	Receivers host> see UE\$SHOST	input
UE\$RCODE	DS	F	Receivers char set> see UE\$SCODE	input
UE\$BHOST	DS	F	BROKER host> see UE\$SHOST	input
UE\$BCODE	DS	F	BROKER char set> see UE\$SCODE	input
*				· ·
UE\$SCP	DS	F	Sender Codepage number	
UE\$RCP	DS	F	Receiver Codepage number	
UE\$BCP	DS	F	Broker Codepage number	
*	-			
UE\$FCT	DS	CL1	Function	input
	EQU	C'C'	Function CONVERT	
FCTCONV	FUU	(, (,	I WILCUIT CONVENT	

```
Function GETLENGTH
FCTGLEN
        EQU
               C'L'
UE$DIR
         DS
               CL1
                        Direction
                                                               input
DIRS2B
               C'1'
                        Direction Sender to Broker
         EQU
               C'2'
DIRS2R
         EQU
                        Direction Sender to Receiver
               C'3'
DIRB2R
         EQU
                        Direction Broker to Receiver
UE$FMT
         DS
               CL2
                        Format
                                                               input
               C'01'
                        User Data like User ID, Program, Library
FMTUSER
        EQU
               C'02'
FMTMETA
         EQU
                        Meta Data Header
               C'03'
                        Format Buffer
FMTFB
         EQU
               C'04'
                        String Buffer
FMTSB
         EQU
               C'05'
                        Meta data value buffer
FMTVBN
         EQU
               C'99'
FMTPRE
         EQU
                        Preview format buffer
FMTA
         EQU
               C'A '
                        Data Type A
                        Data Type AV
               C'AV'
FMTAV
         EQU
               C'B '
                        Data Type B
FMTB
         EQU
FMTBV
         EQU
               C'BV'
                        Data Type BV
               C'D'
FMTD
         EQU
                        Data Type D
               C'F4'
                        Data Type F4
FMTF4
         EQU
               C'F8'
                        Data Type F8
FMTF8
         EQU
               C'I1'
                        Data Type I1
FMTI1
         EQU
               C'I2'
                        Data Type I2
FMTI2
         EQU
               C'I4'
                        Data Type I4
FMTI4
         EQU
                        Data Type K
FMTK
         EQU
               C'K '
               C'KV'
                        Data Type KV
FMTKV
         EQU
               C'L '
         EQU
                        Data Type L
FMTL
FMTN
         EQU
               C'N'
                        Data Type N
               C'P '
FMTP
         EQU
                        Data Type P
               C'T'
                        Data Type T
FMTT
         EQU
               C'U '
FMTU
         EQU
                        Data Type U
               C'UV'
                        Data Type UV
FMTUV
         EQU
               CL40
                        Error Text output
UE$ETXT
        DS
UE$LEN
               *-UE$CB Length of UECB
         EQU
         SPACE ,
```

The user-written conversion exit example USRTRPC is delivered in the EntireX common source library EXX108.SRCE. The related JCL to build USRTCHA is in member EXBUSRXT in the EntireX common jobs library. See *Contents of Mainframe Installation Medium*.

Using the User Exit Interface Fields

The user exit provides two separate functions, CONVERT and GETLENGTH. The field UE\$FCT indicates the function to execute.

Errors

Both functions can send an error, using register 15 in the range 1 to 9999 to SAGTRPC together with an error text in the field UE\$ETXT.

- A value of 0 returned in register 15 means successful response.
- Error 9999 is reserved for output buffer overflow. See *CONVERT Function*.
- When an error occurs, the conversion of the message will be aborted and the error text will be sent to the receiver (client or server). The error is prefixed with the error class 1011. See *Message Class* 1011 *User-definable SAGTRPC Conversion Exit*.

Example:

The user exit returns 1 in register 15 and the message "Invalid Function" in UE\$ETXT. The receiver gets the error message 10110001 Invalid Function.

CONVERT Function

This function has to be executed when the contents of UE\$FCT match the definition FCTCONV.

UE\$DLEN must be supplied by SAGTRPC's user-written conversion exit. Its value must be set to the length of the output buffer.

All other interface fields are supplied by the Broker and must not be modified by SAGTRPC's user-written conversion exit.

The incoming data is located in a buffer pointed to by UE\$IBUF. UE\$ILEN defines the length.

The outgoing converted message must be written to the buffer pointed to by UE\$0BUF. The field TR\$0LEN defines the maximum length available.

For variable length data such as AV and KV, an output buffer overflow can occur if the message size increases after conversion or the receiver's receive buffer is too small. In this case error 9999 "output buffer overflow" must be returned, which calls the <code>GETLENGTH Function</code> for the remaining fields.

GETLENGTH Function

The GETLENGTH function evaluates the needed length of the output buffer after conversion. An actual conversion must not be performed. The length needed must be returned in the field UE\$OLEN.

The GETLENGTH function is called for remaining fields after the CONVERT function returned the error 9999 "output buffer overflow".

The purpose of this function is to evaluate the length needed by the receiver's receive buffer. This length is returned to the receiver in the ACI field RETURN-LENGTH. The receiver can then use the

Broker ACI function RECEIVE with the option LAST together with a receive buffer large enough to reread the message.

Character Set and Codepage

The character-set information used is the same as in the user-written translation routine and is taken from UE\$SCODE (for the sender), UE\$RCODE (for the receiver) and UE\$BCODE (for the Broker). The character-set information depends on the direction information given in the field UE\$DIR. See the following table:

UE\$DIR	From Character Set	To Character Set
DIRS2B (Sender to Broker)	UE\$SCODE	UE\$BCODE
DIRS2R (Sender to Receiver)	UE\$SCODE	UE\$RCODE
DIRB2R (Broker to Receiver)	UE\$BCODE	UE\$RCODE

Alternatively, the codepage as derived from the locale string mapping process is provided in UE\$SCP (sender codepage), UE\$RCP (receiver codepage) and UE\$BCP (Broker codepage), and can be used to find the correct conversion table. See the following table and also *Locale String Mapping*.

UE\$DIR	From Codepage	To Codepage
DIRS2B (Sender to Broker)	UE\$SCP	UE\$BCP
DIRS2R (Sender to Receiver)	UE\$SCP	UE\$RCP
DIRB2R (Broker to Receiver)	UE\$BCP	UE\$RCP

Software AG IDL Data Types to Convert

The field UE\$FMT provides the SAGTRPC user-written conversion exit with the information on the IDL data types to convert. Each data type can be handled independently.

UE\$FMT	Data to be converted	Notes
FMTA	IDL data type A	1, 3, 4
FMTAV	IDL data type AV	4, 5
FMTB	IDL data type B	1, 2, 7
FMTBV	IDL data type BV	1, 2, 7
FMTD	IDL data type D	1, 2, 7
FMTF4	IDL data type F4	1, 2, 7
FMTF8	IDL data type F8	1, 2, 7
FMTI1	IDL data type I1	1, 2, 7
FMTI2	IDL data type I2	1, 2, 7

UE\$FMT	Data to be converted	Notes
FMTI4	IDL data type I4	1, 2, 7
FMTK	IDL data type K	1, 3, 4
FMTKV	IDL data type KV	4, 5
FMTL	IDL data type L	1, 2, 7
FMTN	IDL data type N	1, 2, 7
FMTP	IDL data type P	1, 2, 7
FMTT	IDL data type T	1, 2, 8
FMTU	IDL data type U	1, 2, 7
FMTUV	IDL data type UV	1, 2, 7
FMTUSER	RPC user data such as user ID, library, program	1, 3, 4
FMTMETA	RPC metadata	1, 2, 7
FMTFB	RPC format buffer	1, 2, 7
FMTSB	RPC metadata variable length	4, 5, 7
FMTPRE	Preview data	4, 6, 7

Notes:

- 1. Field length is constant.
- 2. The field content length must not increase or decrease during conversion. If this happens, the user exit should produce an error.
- 3. If the field content length *decreases* during the conversion, suitable padding characters (normally blanks) have to be used.
 - If the field content length *increases* during conversion and exceeds the field length, the contents must be truncated or, alternatively, the conversion can be aborted and an error produced.
- 4. If the contents are truncated, character boundaries are the responsibility of the user exit. Complete valid characters after conversion have to be guaranteed. This may be a complex task for codepages described under *Arabic Shaping*, *EBCDIC Stateful Codepages* or *Multibyte or Double-byte Codepages*. For single-byte codepages it is simple because the character boundaries are the same as the byte boundaries.
- 5. The field length can decrease or increase during the conversion up to the output buffer length. The new field length must be returned in UE\$DLEN. If the output buffer in the CONVERT function is too small, error 9999 must be returned to the caller.
- 6. The field buffer should continue to be converted until the output buffer is full or the input buffer has been processed. If the field content length increases or truncations occur, no error should be produced. If the field content length decreases, there should be no padding. The new field length should simply be returned to the caller.

7. Codepages used for RPC data streams must meet several requirements. See *Codepage Requirements* for RPC Data Stream Conversions. If these are not met, the codepage cannot be used to convert RPC data streams.

> To assemble and link the SAGTRPC user-written conversion exit

- Assemble and link your conversion exit. You can give the resulting load module any name that does not begin with "SAG". Names starting with "SAG", such as "SAGTRPC", are reserved for Software AG. Refer to the JCL provided in member EXBUSRXT in data set EXX108.JOBS.
- > To install and configure the SAGTRPC user-written conversion exit
- Refer to the instructions under *Configuring SAGTRPC User Exits*.

Configuring SAGTRPC User Exits

> To configure SAGTRPC user exits

- 1 The user-written conversion module must be accessible to the Broker worker threads. Therefore, copy the user-written conversion module into any library of the Broker's steplib concatenation.
- In the Broker attribute file, set the service-specific attribute CONVERSION to the name of the user-written SAGTRPC user exit routine. Example:

CONVERSION=(MYTRANS)

> To configure locale string defaults

■ If the broker's locale string defaults do not match your requirements, we recommend you assign suitable locale string defaults for your country and region. See the appropriate attribute under *Codepage-specific Attributes* for information on customizing broker's locale string defaults, and also *Locale String Mapping*.

> To customize mapping of locale strings

■ If the broker's built-in locale string mechanism does not match your requirements, you can assign specific codepages to locale strings. See *Broker's Built-in Locale String Mapping* and the appropriate attribute under *Codepage-specific Attributes* for information on customizing broker's locale string defaults.

Managing the Broker Persistent Store

Implementing an Adabas Database as Persistent Store	10	02
Implementing a DIV Persistent Store		
Migrating the Persistent Store	1	13

The persistent store is used for storing unit-of-work messages to disk. This means message and status information can be recovered after a hardware or software failure to the previous commit point issued by each application component.

Under z/OS, the broker persistent store can be implemented with:

- the Adabas database of Software AG
- a VSAM linear data set (LDS) accessed using Data In Virtual (DIV)

See also Concepts of Persistent Messaging.

Implementing an Adabas Database as Persistent Store

- Introduction
- Configuring and Operating the Adabas Persistent Store
- Adabas DBA Considerations

Introduction

EntireX provides an Adabas persistent driver. This enables Broker unit of work (UOW) messages and their status to be stored in an Adabas file. It is designed to work with Adabas databases under z/OS, UNIX, Windows, BS2000 and z/VSE, and can be used where the database resides on a different machine to Broker kernel. For performance reasons, we recommend using EntireX Broker on the same machine as the Adabas database.

Configuring and Operating the Adabas Persistent Store

Selecting the Adabas Persistent Store Driver

The Adabas persistent store driver module is contained within the regular Broker load library or binaries directory. Module ADAPSI is activated by specifying the PSTORE-TYPE parameter. Use the supplied job EXBJ015 from data set EXX108.JOBS to define and install the persistent store file in your Adabas database. This job creates and loads the Adabas file into the database.

Restrictions

If a HOT start is performed, the Broker kernel must be executed on the same platform on which also the previous Broker executed. This is because some portions of the persistent data are stored in the native character set and format of the Broker kernel. It is also necessary to start Broker with the same Broker ID as the previous Broker executed.

If a COLD start is executed, a check is made to ensure the Broker ID and platform information found in the persistent store file is consistent with the Broker being started (provided the persistent store file is not empty). This is done to prevent accidental deletion of data in the persistent store by a different Broker ID. If you intend to COLD start Broker and to utilize a persistent store file which has been used previously by a different Broker ID, you must supply the additional PSTORE-TYPE parameter FORCE-COLD=Y.

Recommendations

- Perform regular backup operations on your Adabas database. The persistent store driver writes C1 checkpoint records at each start up and shut down of Broker.
- Significant performance improvements can be achieved using Adabas/Fastpath where available. See Adabas/Fastpath documentation for details of installation and configuration of Adabas/Fastpath.
- For performance reasons, execute Broker on the same machine as Adabas.

Broker Checkpoints in Adabas

During startup, Broker writes the following C1 checkpoint records to the Adabas database. The time, date and job name are recorded in the Adabas checkpoint log. This enables Adabas protection logs to be coordinated with Broker executions. This information can be read from Adabas, using the ADAREP utility with option CPLIST:

Broker Execution Name	Broker Execution Type	Adabas
ETBC	Broker Cold Start	Normal Cold Start
ЕТВН	Broker Hot Start	Normal Hot Start
ETBT	Broker Termination	Normal Termination

Adabas DBA Considerations

- BLKSIZE: Adabas Persistent Store Parameter for Broker
- Table of Adabas Parameter Settings
- Estimating the Number of Records to be Stored
- Estimating the Number of Records to be Stored
- Tips on Transports, Platforms and Versions

BLKSIZE: Adabas Persistent Store Parameter for Broker

Caution should be exercised when defining the block size (BLKSIZE) parameter for the Adabas persistent store. This determines how much UOW message data can be stored within a single Adabas record. Therefore, do not define a much larger block size than the size of the maximum unit of work being processed by Broker. (Remember to add 41 bytes for each message in the unit of work.) The advantage of having a good fit between the unit of work and the block size is that fewer records are required for each I/O operation.

It is necessary to consider the following Adabas parameters and settings when using Adabas for the persistent store file:

Table of Adabas Parameter Settings

Topic	Description
Allowing Sufficient Adabas UQ Elements	Allow sufficient Adabas user queue (UQ) elements each time you start Broker. The Broker utilizes a number of user queue elements equal to the number of worker tasks (NUM-WORKER), plus two. Adabas timeout parameter (TNAE) determines how long the user queue elements will remain. This can be important if Broker is restarted after an abnormal termination, and provision must be made for sufficient user queue elements in the event of restarting Broker.
	Sample JCL SAGJ014 is provided in data set EXX108.JOBS for z/OS to enforce clean-up of any user queue element belonging to the previous Broker job. This JCL can be inserted into the job step before starting up Broker.
Setting Size of Hold Queue Parameters	Consideration must be given to the Adabas hold queue parameters NISNHQ and NH. These must be sufficiently large to allow Adabas to add/update/delete the actual number of records within a single unit of work.
	Example: where there are 100 message within a unit of work and the average message size is 10,000 bytes, the total unit of work size is 1 MB. If, for example, a 2 KB block size (default BLKSIZE=2000) is utilized by the Adabas persistent store driver, there will be 500 distinct records within a single Adabas commit (ET) operation, and provision must be made for this to occur successfully.

Торіс	Description
Setting Adabas TT Parameter	Consideration must be given to the Adabas transaction time (TT) parameter for cases where a large number of records is being updated within a single unit of work.
Defining LWP Size	Sufficient logical work pool (LWP) size must be defined so that the Adabas persistent store can update and commit the units of work. Adabas must be able to accommodate this in addition to any other processing for which it is used.
Executing Broker Kernel and Adabas Nucleus on Separate Machines	If Broker kernel is executed on a separate machine to the Adabas nucleus, with a different architecture and codepage, then we recommend running the Adabas nucleus with the UEC (universal conversion) option in order to ensure that Adabas C1 checkpoints are legible within the Adabas checkpoint log.
Setting INDEXCOMPRESSION=YES	This Adabas option can be applied to the Adabas file to reduce by approximately 50% the amount of space consumed in the indexes. This is the default setting in job EXBJ015, which is supplied in data set EXX108.JOBS to define the Adabas persistent store file.
4-byte ISNs	If you anticipate having more than 16 million records within the persistent store file, you must use 4-byte ISNs when defining the Adabas file for EntireX.
Specification of Adabas LP	Caution: This parameter must be specified large enough to allow the
Parameter	largest UOW to be stored in Adabas.
	If this is not large enough, Broker will detect an error (response 9; subresponse - 4 bytes - X'0003',C'LP') and Broker will not be able to write any further UOWs.
	See the description of the LP parameter under <i>ADARUN Parameters</i> in the <i>DBA Reference Summary</i> of the Adabas documentation.

Estimating the Number of Records to be Stored

To calculate the Adabas file size it is necessary to estimate the number of records being stored. As an approximate guide, there will be one Adabas record (500 bytes) for each unprocessed unit of work, plus also *n* records containing the actual message data, which depends on the logical block size and the size of the unit of work. In addition, there will be one single record (500 bytes) for each unit of work having a persisted status.

Always allow ample space for the Adabas persistent store file since the continuous operation of Broker relies of the availability of this file to store and retrieve information.



Note: If the Adabas file space is exceeded, no new units of work will be accepted.

Estimating the Number of Records to be Stored

In this example there are 100,000 Active UOW records at any one time. Each of these is associated with two message records containing the message data. UOW records are 500 bytes in length. Each message record contains 2,000 bytes. In addition, there are 500,000 UOW status records residing in the persistent store, for which the UOW has already been completely processed. These are 500 bytes long.



Note: The actual size of the data stored within the UOW message records is the sum of all the messages within the UOW, plus a 41-byte header for each message. Therefore, if the average message length is 59 bytes, the two 2,000 bytes, messages records, could contain n = 4,000 / (59+41), or 40 messages. Adabas is assumed to compress the message data by 50% in the example (this can vary according to the nature of the message data).

3-byte ISNs and RABNs are assumed in this example. A device type of 8393 is used; therefore, the ASSO block size is 4,096, and DATA block size is 27,644. Padding factor of 10% is specified.

The following example calculates the space needed for Normal Index (NI), Upper Index (UI), Address Converter (AC) and Data Storage (DS).

Calculation Factors	Required Space
■ Number entries for descriptor WK	= number UOW records: 0.1 + 0.5 million
(21-byte unique key)	+ number message records: 0.2 million
■ NI Space for descriptor WK	■ = 800,000 * (3 + 21 + 2)
(3-byte ISN)	= 20,800,000 bytes
(4,092 ASSO block 10% padding)	■ = 5,648 blocks
■ UI Space for descriptor WK	= 5,648 * (21 + 3 + 3 + 1)
■ (3-byte ISN + 3-byte RABN)	■ = 158,140 bytes
(4,092 ASSO block 10% padding)	■ = 43 blocks
Number entries for descriptor WI (8-byte unique key)	= number processed UOW records: 0.5 million
■ NI Space for descriptor WI	= = 500,000 * (3 + 8 + 2)
(3-byte ISN)	■ = 6,500,000 bytes
(4,092 ASSO block 10% padding)	■ = 1,765 blocks
■ UI Space for descriptor WI	■ = 17,649 * (8 + 3 + 3 + 1)
(3-byte ISN and 3 byte RABN)	■ = 26,475 bytes
(4,092 ASSO block 10% padding)	■ = 8 blocks

Calculation Factors	Required Space
■ Number entries for descriptor WL	= number UOW records 0.1 + 0.5 million
(96 byte key)	
, , ,	
■ NI Space for descriptor WL	= = 600,000 * (3 + 96 + 2)
(3-byte ISN)	= 60,600,000 bytes
(4,092 ASSO block 10% padding)	■ = 16,455 blocks
■ UI Space for descriptor WL	■ = 164,548 * (96 + 3 + 3 + 1)
(3-byte ISN and 3 byte RABN)	■ = 16,948,517 bytes
(4,092 ASSO block 10% padding)	■ = 461 blocks
Address Converter space	= = (800,000 + 1) * 3 / 4092
■ (4,092 ASSO block)	■ = 587 blocks
■ Data storage for message data	= 0.2 million * 2000 * 0.5 = 200,000,000 bytes
(2,000-byte records compressed by 50%)	
■ Data storage for UOW data	= 0.6 million * 500 * 0.5 = 150,000,000 byte
(2,000-byte records compressed by 50%)	
Combined space required for data	■ = 14,068 blocks
(27,644 DATA block 10% padding)	
Entity Requiring Space	Total Required Space
Normal Index (NI)	= 23,868 blocks
Upper Index (UI)	= 512 blocks
Data Storage (DS)	= 14,068 blocks
Address Converter (AC)	= 587 blocks

Tips on Transports, Platforms and Versions

■ Entire Net-Work

If you intend to use Adabas persistent store through Entire Net-Work, see the Entire Net-Work documentation for installation and configuration details.

■ Adabas Versions

Adabas persistent store can be used on all Adabas versions currently released and supported by Software AG.

■ Prerequisite Versions of Entire Net-Work with Adabas

See the Adabas and Entire Net-Work documentation to determine prerequisite versions of Entire Net-Work to use with Adabas at your site.

Implementing a DIV Persistent Store



Note: From EntireX version 9.7, broker attribute PSTORE-VERSION must be set to 4 for a persistent store of type DIV. If you were using a lower version, you will need to perform a cold start. See PSTORE=COLD under *Broker-specific Broker Attributes*.

This section covers the following topics:

- Introduction
- Format Parameters
- Operations using IDCAMS

Introduction

The persistent store is implemented as a VSAM linear data set (LDS) accessed using Data In Virtual (DIV). This DIV persistent store is a container for units of work.

DIV is an access method that utilizes the system paging facilities for fast I/O to and from an LDS. Performance is best if the LDS is placed on the fastest storage device available such as those used for paging. An LDS may span multiple volumes.

The DIV persistent store has an internal structure that is formatted by EntireX Broker during a COLD start (see broker attribute PSTORE). This format is controlled by format parameter statements that the Broker reads from the attribute file. See *DIV-specific Attributes*.

Persistent store data sets are maintained using the IBM z/OS utility IDCAMS. See *Operations using IDCAMS* for more information.

Format Parameters



Note: This method of specifying persistent store format parameters is deprecated, but still supported for compatibility reasons. We recommend you use the attributes introduced with EntireX version 9.12 instead. See *DIV-specific Attributes*.

The persistent store format parameters define how a persistent store is formatted during a cold start operation and how it is accessed during all operations. These parameters are supplied in the attribute file section <code>DEFAULTS=DIV</code>. Knowledge of the application usage of units of work (UOWs) will be very helpful in selecting appropriate values for the parameters used to define the persistent store.

The persistent store format parameters file must begin with the word DEFINE, followed by "parameter name parameter value" specifications. Each parameter name must be separated from the parameter value by whitespace (blanks, tabs, or new lines). Comments may be added to the file.

A comment begins with /* and ends with */, just as in the C language. The parameters must be entered in uppercase. In the following parameter descriptions, lowercase is used to denote variables:

```
DEFINE STORE name
DDNAME ddname
DATASPACE NAME name-of-dataspace
DATASPACE PAGES count-of-pages
```

Parameter	Value	Opt/ Req	Description
STORE	A8	R	Defines an internal name that is used to identify the persistent store.
DDNAME	A8	R	Defines the JCL DDNAME that will be used to access the persistent store.
DATASPACE NAME	A8	O	Defines the name of the data space that will be used to map the persistent store. Default value=DSPSTORE.
DATASPACE PAGES	126-524284	О	Defines the size of the dataspace used to map the persistent store (size=DATASPACE-PAGES*4KB). We recommend using the maximum value. Default value is 2048.

Example

```
DEFAULTS = DIV
DIV = "DEFINE STORE PSD01 DDNAME STORE01"
```

Operations using IDCAMS

This section covers the following topics:

- Defining a Persistent Store Linear Data Set
- Printing a Persistent Store for Diagnosis
- Copying a Persistent Store for Backup or Diagnosis
- Sample IDCAMS JCL

Defining a Persistent Store Linear Data Set

The following IDCAMS statement can be used to allocate the persistent store. It assumes that the local environment is using z/OS SMS for data management. SMS allows for simple definition, but it may not be used at your site or it may not provide optimal performance. You may therefore need to modify the following statement under the direction of your local system administrator:

```
DEFINE CLUSTER (NAME(dsn_pstore) -
MEGABYTES(15,5) -
SHAREOPTIONS(1,3) - /*this is required*/
LINEAR) /*this is required*/
```

where *dsn_pstore* is the DSNAME you chose for the PSTORE linear data set (LDS).



Note: The size of the linear data set (LDS) should be 16K times the value specified for DATASPACE PAGES. For example, 16K * 2048 = 32768K = 32M would be the LDS size needed to contain the default number of pages. Less than the required amount will cause initialization to fail; more will be unused space.

Printing a Persistent Store for Diagnosis

The following statement lists the catalog information for the linear data set:

```
LISTCAT ENTRIES(dsn_pstore) ALL
```

where *dsn_pstore* is the DSNAME you chose for the PSTORE linear data set (LDS).

The following statement prints the contents of a persistent store in dump format:

```
PRINT IDS(dsn_pstore) DUMP
```

Copying a Persistent Store for Backup or Diagnosis

REPRO IDS(dsn_pstore) ODS(your_backup_name)

Sample IDCAMS JCL

Sample JCL is provided as member IDCAMS in the installation source library. Each operation is contained in a separate DD. To select an operation, modify the SYSIN DD DDNAME= to the name of the DD enclosing the statements to be selected.

Migrating the Persistent Store

The contents of EntireX Broker's persistent store can be migrated to a new persistent store in order to change the PSTORE type or to use the same type of PSTORE with increased capacity.

The migration procedure outlined here requires two Broker instances started with a special RUN-MODE parameter. One Broker unloads the contents of the persistent store and transmits the data to the other Broker, which loads data into the new PSTORE. Therefore, for the purposes of this discussion, we will refer to an *unload* Broker and a *load* Broker.

This procedure is based on Broker-to-Broker communication to establish a communication link between two Broker instances. It does not use any conversion facilities, since the migration procedure is supported for homogeneous platforms only.

- Configuration
- Migration Procedure

Configuration



Note: RUN-MODE options PSTORE-LOAD and PSTORE-UNLOAD are deprecated and will not be supported in the next version of EntireX.

The migration procedure requires two Broker instances started with the RUN-MODE parameter. The unload Broker should be started with the following attribute:

RUN-MODE=PSTORE-UNLOAD

The load Broker should be started with the following attribute:

RUN-MODE=PSTORE-LOAD

These commands instruct the Broker instances to perform the PSTORE migration.



Note: The attribute PARTNER-CLUSTER-ADDRESS must be defined in both Broker instances to specify the transport address of the load Broker. The unload Broker must know the address of the load broker, and the load Broker must in turn know the address of the unload Broker.

Example:

Broker ETB001 performs the unload on host HOST1, and Broker ETB002 performs the load on host HOST2. The transmission is based on TCP/IP. Therefore, Broker ETB001 starts the TCP/IP communicator to establish port 1971, and Broker ETB002 starts the TCP/IP communicator to establish port 1972.

For ETB001, attribute PARTNER-CLUSTER-ADDRESS=HOST2:1972:TCP is set, and for ETB002, attribute PARTNER-CLUSTER-ADDRESS=HOST1:1971:TCP is set to establish the Broker-to-Broker communication between the two Broker instances.

In addition to attributes RUN-MODE and PARTNER-CLUSTER-ADDRESS, a fully functioning Broker configuration is required when starting the two Broker instances. To access an existing PSTORE on the unloader side, you must set the attribute PSTORE=HOT. To load the data into the new PSTORE on the loader side, you must set the attribute PSTORE=COLD. The load process requires an empty PSTORE at the beginning of the load process.



Note: Use caution not to assign PSTORE=COLD to your unload Broker instance, as this startup process will erase all data currently in the PSTORE.

For the migration process, the unload Broker and the load Broker must be assigned different persistent stores.

A report can be generated to detail all of the contents of the existing persistent store. At the end of the migration process, a second report can be run on the resulting new persistent store. These two reports can be compared to ensure that all contents were migrated properly. To run these reports, set the attribute PSTORE-REPORT=YES. See PSTORE for detailed description, especially for the file assignment.

Migration Procedure

The migration procedure is made up of three steps.

Step 1

The unload Broker and the load Broker instances can be started independently of each other. Each instance will wait for the other to become available before starting the unload/load procedure.

The unload Broker instance sends a handshake request to the load Broker instance in order to perform an initial compatibility check. This validation is performed by Broker according to platform architecture type and Broker version number. The handshake ensures a correctly configured partner cluster address and ensures that the user did not assign the same PSTORE to both Broker instances. If a problem is detected, an error message will be issued and both Broker instances will stop.

Step 2

The unload Broker instance reads all PSTORE data in a special non-destructive raw mode and transmits the data to the load Broker instance. The load Broker instance writes the unchanged raw data to the new PSTORE. A report is created if PSTORE-REPORT=YES is specified, and a valid output file for the report is specified.

Step 3

The unload Broker instance requests a summary report from the load Broker instance to compare the amount of migrated data. The result of this check is reported by the unload Broker instance and the load Broker instance before they shut down.

When a Broker instances is started in RUN-MODE=PSTORE-LOAD or RUN-MODE=PSTORE-UNLOAD, the Broker instances only allow Administration requests. All other user requests are prohibited.



Notes:

- 1. The contents of the persistent store are copied to the new persistent store as an exact replica. No filtering of unnecessary information will be performed, for example, UOWs in received state. The master records will not be updated.
- 2. Before restarting your Broker with the new persistent store, be sure to change your PSTORE attribute to PSTORE=HOT. *Do not* start your broker with the new persistence store using PSTORE=COLD; this startup process will erase all of the data in your persistent store.
- 3. After completing the migration process and restarting your broker in a normal run-mode, it is important not to bring both the new PSTORE and the old PSTORE back online using separate Broker instances; otherwise, applications would receive the same data twice. Once the migration process is completed satisfactorily, and is validated, the old PSTORE contents should be discarded.

6 Broker Resource Allocation

General Considerations	118
Specifying Global Resources	
Restricting the Resources of Particular Services	119
Specifying Attributes for Privileged Services	121
Maximum Units of Work	122
Calculating Resources Automatically	122
Dynamic Memory Management	124
Dynamic Worker Management	
Storage Report	
Maximum TCP/IP Connections per Communicator	

The EntireX Broker is a multithreaded application and communicates among multiple tasks in memory pools. If you do not need to restrict the memory expansion of EntireX Broker, we strongly recommend you enable the dynamic memory management in order to handle changing workload appropriately. See *Dynamic Memory Management* below. If dynamic memory management is disabled, non-expandable memory is allocated during startup to store all internal control blocks and the contents of messages.

General Considerations

Resource considerations apply to both the global and service-specific levels:

- Dynamic assignment of global resources to services that need them prevents the return of a "Resource Shortage" code to an application when resources are available globally. It also enables the EntireX Broker to run with fewer total resources, although it does not guarantee the availability of a specific set of resources for a particular service.
- Flow control ensures that individual services do not influence the behavior of other services by accident, error, or simply overload. This means that you can restrict the resource consumption of particular services in order to shield the other services.

In order to satisfy both global and service-specific requirements, the EntireX Broker allows you to allocate resources for each individual service or define global resources which are then allocated dynamically to any service that needs them.

The resources in question are the number of conversations, number of servers, plus units of work and the message storage, separated in a long buffer of 4096 bytes and short buffer of 256 bytes. These resources are typically the bottleneck in a system, especially when you consider that non-conversational communication is treated as the special case of "conversations with a single message only" within the EntireX Broker.

Global resources are defined by the parameters in the Broker section of the attribute file. The number of conversations allocated to each service is defined in the service-specific section of the attribute file. Because the conversations are shared by all servers that provide the service, a larger number of conversations should be allocated to services that are provided by more than one server. The number of conversations required is also affected by the number of clients accessing the service in parallel.

Specifying Global Resources

You can specify a set of global resources with no restrictions on which service allocates the resources:

- Specify the global attributes with the desired values.
- Do not specify any additional restrictions. That is, do not provide values for the following Broker-specific attributes:

```
LONG-BUFFER-DEFAULT
SHORT-BUFFER-DEFAULT
CONV-DEFAULT
SERVER-DEFAULT
```

■ Also, do not provide values for the following server-specific attributes:

```
LONG-BUFFER-LIMIT
SERVER-LIMIT
SHORT-BUFFER-LIMIT
CONV-LIMIT
```

Example

The following example defines global resources. If no additional definitions are specified, resources are allocated and assigned to any server that needs them.

```
NUM-CONVERSATION=1000
NUM-LONG-BUFFER=200
NUM-SHORT-BUFFER=2000
NUM-SERVER=100
```

Restricting the Resources of Particular Services

You can restrict resource allocation for particular services in advance:

- Use CONV-LIMIT to limit the resource consumption for a specific service.
- Use CONV-DEFAULT to provide a default limit for services for which CONV-LIMIT is not defined.

Example

In the following example, attributes are used to restrict resource allocation:

```
DEFAULTS=BROKER
NUM-CONVERSATION=1000
CONV-DEFAULT=200

DEFAULTS=SERVICE
CLASS=A, SERVER=A, SERVICE=A, CONV-LIMIT=100
CLASS=B, SERVER=B, SERVICE=B, CONV-LIMIT=UNLIM
CLASS=C, SERVER=C, SERVICE=C
```

- Memory for a total of 1000 conversations is allocated (NUM-CONVERSATION=1000).
- Service A (CLASS A, SERVER A, SERVICE A) is limited to 100 conversation control blocks used simultaneously (CONV-LIMIT=100). The application that wants to start more conversations than specified by the limit policy will receive a "Resource shortage" return code. This return code should result in a retry of the desired operation a little later, when the resource situation may have changed.
- Service B (CLASS B, SERVER B, SERVICE B) is allowed to try to allocate as many resources as necessary, provided the resources are available and not occupied by other services. The number of conversations that may be used by this service is unlimited (CONV-LIMIT=UNLIM).
- Service C (CLASS C, SERVER C, SERVICE C) has no explicit value for the CONV-LIMIT attribute. The number of conversation control blocks that it is allowed to use is therefore limited to the default value which is defined by the CONV-DEFAULT Broker attribute.

The same scheme applies to the allocation of message buffers and servers:

In the following example, long message buffers are allocated using the keywords NUM-LONG-BUFFER, LONG-BUFFER-DEFAULT and LONG-BUFFER-LIMIT:

```
DEFAULTS=BROKER
NUM-LONG-BUFFER=2000
LONG-BUFFER-DEFAULT=250

DEFAULTS=SERVICE
CLASS=A, SERVER=A, SERVICE=A, LONG-BUFFER-LIMIT=100
CLASS=B, SERVER=B, SERVICE=B, LONG-BUFFER-LIMIT=UNLIM
CLASS=C, SERVER=C, SERVICE=C
```

■ In the following example, short message buffers are allocated using the keywords NUM-SHORT-BUFFER, SHORT-BUFFER-DEFAULT and SHORT-BUFFER-LIMIT:

```
DEFAULTS=BROKER
NUM-SHORT-BUFFER=2000
SHORT-BUFFER-DEFAULT=250

DEFAULTS=SERVICE
CLASS=A, SERVER=A, SERVICE=A, SHORT-BUFFER-LIMIT=100
CLASS=B, SERVER=B, SERVICE=B, SHORT-BUFFER-LIMIT=UNLIM
CLASS=C, SERVER=C, SERVICE=C
```

In the following example, servers are allocated using the keywords NUM-SERVER, SERVER-DEFAULT and SERVER-LIMIT:

```
DEFAULTS=BROKER
NUM-SERVER=2000
SERVER-DEFAULT=250

DEFAULTS=SERVICE
CLASS=A, SERVER=A, SERVICE=A, SERVER-LIMIT=100
CLASS=B, SERVER=B, SERVICE=B, SERVER-LIMIT=UNLIM
CLASS=C, SERVER=C, SERVICE=C
```

Specifying Attributes for Privileged Services

If privileged services (services with access to unlimited resources) exist, specify UNLIMITED for the attributes CONV-LIMIT, SERVER-LIMIT, LONG-BUFFER-LIMIT and SHORT-BUFFER-LIMIT in the service-specific section of the attribute file.

For example:

```
DEFAULTS=SERVICE
CONV-LIMIT=UNLIM
LONG-BUFFER-LIMIT=UNLIM
SHORT-BUFFER-LIMIT=UNLIM
SERVER-LIMIT=UNLIM
```

To ensure a resource reservoir for peak load of privileged services, define more resources than would normally be expected by specifying larger numbers for the Broker attributes that control global resources:

```
NUM-SERVER
NUM-CONVERSATION
CONV-DEFAULT
LONG-BUFFER-DEFAULT
SHORT-BUFFER-DEFAULT
SERVER-DEFAULT
```

Maximum Units of Work

The maximum number of units of work (UOWs) that can be active concurrently is specified in the Broker attribute file. The MAX-UOWS attribute can be specified for the Broker globally as well as for individual services. It cannot be calculated automatically. If a service is intended to process UOWs, a MAX-UOWS value must be specified.

If message processing only is to be done, specify MAX-UOWS=0 (zero). The Broker (or the service) will not accept units of work, that is, it will process only messages that are not part of a UOW. Zero is used as the default value for MAX-UOWS in order to prevent the sending of UOWs to services that are not intended to process them.

Calculating Resources Automatically

To ensure that each service runs without impacting other services, allow the EntireX Broker to calculate resource requirements automatically:

- Ensure that the attributes that define the default total for the Broker and the limit for each service are not set to UNLIM.
- Specify AUTO for the Broker attribute that defines the total number of the resource.
- Specify a suitable value for the Broker attribute that defines the default number of the resource.

The total number required will be calculated from the number defined for each service. The resources that can be calculated this way are Number of Conversations, Number of Servers, Long Message Buffers and Short Message Buffers.

Avoid altering the service-specific definitions at runtime. Doing so could corrupt the conversation consistency. Applications might receive a message such as "NUM-CONVERSATIONS reached" although the addressed service does not serve as many conversations as defined. The same applies to the attributes that define the long and short buffer resources.

Automatic resource calculation has the additional advantage of limiting the amount of memory used to run the EntireX Broker. Over time, you should be able to determine which services need more resources by noting the occurrence of the return code "resource shortage, please retry". You can then increase the resources for these services. To avoid disruption to the user, you could instead allocate a relatively large set of resources initially and then decrease the values using information gained from the Administration Monitor application.

Number of Conversations

To calculate the total number of conversations automatically, ensure that the CONV-DEFAULT Broker attribute and the CONV-LIMIT service-specific attribute are not set to UNLIM anywhere in the attribute

file. Specify NUM-CONVERSATION=AUTO and an appropriate value for the CONV-DEFAULT Broker attribute. The total number of conversations will be calculated using the value specified for each service.

For example:

```
DEFAULTS=BROKER
NUM-CONVERSATION=AUTO
CONV-DEFAULT=200

DEFAULTS=SERVICE
CLASS=A, SERVER=A, SERVICE=A
CLASS=B, SERVER=B, SERVICE=B, CONV-LIMIT=100
CLASS=C, SERVER=C, SERVICE=C
```

- Service A and Service C both need 200 conversations (the default value). Service B needs 100 conversations (CONV-LIMIT=100).
- Because NUM-CONVERSATIONS is defined as AUTO, the broker calculates a total of 500 conversations (200 + 200 + 100).
- NUM-CONVERSATIONS=AUTO allows the number of conversations to be flexible without requiring additional specifications. It also ensures that the broker is started with enough resources to meet all the demands of the individual services.
- AUTO and UNLIM are mutually exclusive. If CONV-DEFAULT or a single CONV-LIMIT is defined as UNLIM, the EntireX Broker cannot determine the number of conversations to use in the calculation, and the EntireX Broker cannot be started.

Number of Servers

To calculate the number of servers automatically, ensure that the SERVER-DEFAULT Broker attribute and the SERVER-LIMIT service-specific attribute are not set to UNLIM anywhere in the attribute file. Specify NUM-SERVER=AUTO and an appropriate value for the SERVER-DEFAULT Broker attribute. The total number of server buffers will be calculated using the value specified for each service.

For example:

```
DEFAULTS=BROKER
NUM-SERVER=AUTO
SERVER-DEFAULT=250

DEFAULTS=SERVICE
CLASS=A, SERVER=A, SERVICE=A, SERVER-LIMIT=100
CLASS=B, SERVER=B, SERVICE=B
CLASS=C, SERVER=C, SERVICE=C
```

Long Message Buffers

To calculate the number of long message buffers automatically, ensure that the LONG-BUFFER-DE-FAULT Broker attribute and the LONG-BUFFER-LIMIT service-specific attribute are not set to UNLIM

anywhere in the attribute file. Specify NUM-LONG-BUFFER=AUTO and an appropriate value for the LONG-BUFFER-DEFAULT Broker attribute. The total number of long message buffers will be calculated using the value specified for each service.

For example:

```
DEFAULTS=BROKER
NUM-LONG-BUFFER=AUTO
LONG-BUFFER-DEFAULT=250

DEFAULTS=SERVICE
CLASS=A, SERVER=A, SERVICE=A, LONG-BUFFER-LIMIT=100
CLASS=B, SERVER=B, SERVICE=B
CLASS=C, SERVER=C, SERVICE=C
```

Short Message Buffers

To calculate the number of short message buffers automatically, ensure that the SHORT-BUFFER-DEFAULT Broker attribute and the SHORT-BUFFER-LIMIT service-specific attribute are not set to UNLIM anywhere in the attribute file. Specify NUM-SHORT-BUFFER=AUTO and an appropriate value for the SHORT-BUFFER-DEFAULT Broker attribute. The total number of short message buffers will be calculated using the value specified for each service.

For example:

```
DEFAULTS=BROKER
NUM-SHORT-BUFFER=AUTO
SHORT-BUFFER-DEFAULT=250

DEFAULTS=SERVICE
CLASS=A, SERVER=A, SERVICE=A
CLASS=B, SERVER=B, SERVICE=B, SHORT-BUFFER-LIMIT=100
CLASS=C, SERVER=C, SERVICE=C
```

Dynamic Memory Management

Dynamic memory management is a feature to handle changing Broker workload without any restart of the Broker task. It increases the availability of the Broker by using various memory pools for various Broker resources and by being able to use a variable number of pools for the resources.

If more memory is needed than currently available, another memory pool is allocated for the specific type of resource. If a particular memory pool is no longer used, it will be deallocated.

The following Broker attributes can be omitted if DYNAMIC-MEMORY-MANAGEMENT=YES has been defined:

```
■ NUM-CLIENT ■ NUM-LONG[-BUFFER] ■ NUM-SHORT[-BUFFER]
■ NUM-CMDLOG-FILTER ■ NUM-SERVER ■ NUM-UOW|MAX-UOWS|MUOW
■ NUM-COMBUF ■ NUM-SERVICE ■ NUM-WQE
■ NUM-CONV[ERSATION] ■ NUM-SERVICE-EXTENSION
```

If you want statistics on allocation and deallocation operations in Broker, you can configure Broker to create a storage report with the attribute STORAGE-REPORT. See *Storage Report* below.



Note: To ensure a stable environment, some pools of Broker are not deallocated automatically. The first pools of type COMMUNICATION, CONVERSATION, CONNECTION, HEAP, PARTICIPANT, PARTICIPANT EXTENSION, SERVICE ATTRIBUTES, SERVICE, SERVICE EXTENSION, TIMEOUT QUEUE, TRANSLATION, WORK QUEUE are excluded from the automatic deallocation even when they have not been used for quite some time. Large pools cannot be reallocated under some circumstances if the level of fragmentation in the address space has been increased in the meantime.

Dynamic Worker Management

Dynamic worker management is a feature to handle the fluctuating broker workload without restarting the Broker task. It adjusts the number of running worker tasks according to current workload. The initial portion of worker tasks started at Broker startup is still determined by NUM-WORKER.

If more workers are needed than currently available, another worker task is started. If a worker task is no longer needed, it will be stopped.

The following Broker attributes are used for the configuration if DYNAMIC-WORKER-MANAGEMENT=YES has been defined:

- WORKER-MAX
- WORKER-MIN
- WORKER-NONACT
- WORKER-OUEUE-DEPTH
- WORKER-START-DELAY

The following two attributes are very performance-sensitive:

Attribute WORKER-QUEUE-DEPTH defines the number of unassigned user requests in the input queue before a new worker task is started.

Attribute WORKER-START-DELAY defines the time between the last worker task startup and the next check for another possible worker task startup. It is needed to consider the time for activating a worker task.

Both attributes depend on the environment, in particular the underlying operating system and the hardware. The goal is to achieve high-performance user request processing without starting too many worker tasks.

A good starting point to achieve high performance is not to change the attributes and to observe the performance of the application programs after activating the dynamic worker management.

If broker attribute DYNAMIC-WORKER-MANAGEMENT=YES is set, operator commands are available under z/OS to deactivate and subsequently reactivate dynamic worker management.

The following section illustrates the two different modes of dynamic worker management:

■ Scenario 1

```
DYNAMIC-WORKER-MANAGEMENT=YES

NUM-WORKER = 5

WORKER-MIN = 1

WORKER-MAX = 32
```

Broker is started with 5 worker tasks and then dynamically varies the number of worker tasks within the range from WORKER-MIN=1 to WORKER-MAX=32 due to DYNAMIC-WORKER-MANAGEMENT=YES.

■ Scenario 2

```
DYNAMIC-WORKER-MANAGEMENT=NO
NUM-WORKER = 5
WORKER-MIN = 1
WORKER-MAX = 32
```

Broker is started with 5 worker tasks. The WORKER-MIN/MAX attributes are ignored due to DYNAMIC-WORKER-MANAGEMENT=NO.

Storage Report

You can create an optional report file that provides details about all activities to allocate or to deallocate memory pools. This section details how to create the report and provides a sample report.

- Creating a Storage Report
- Platform-specific Rules
- Sample Storage Report

See also Broker-specific attribute STORAGE-REPORT.

Creating a Storage Report

Use Broker's global attribute STORAGE-REPORT with the value YES. If attribute value YES is supplied, all memory pool operations will be reported if the output mechanism is available. If the value NO is specified, no report will be created.

Platform-specific Rules

DDNAME ETBSREP assigns the report file. Format RECFM=FB, LRECL=121 is used.

Sample Storage Report

The following is an excerpt from a sample STORAGE report.

```
EntireX 8.1.0.00 STORAGE Report 2009-06-26 12:28:58 Page 1

Identifier Address Size Total Date Time Action KERNEL POOL 0x25E48010 407184 bytes 407184 bytes 2009-06-26 12:... Allocated HEAP POOL 0x25EB4010 1050692 bytes 1457876 bytes 2009-06-26 12:... Allocated ...
```

Header	Description
Identifier	Name of the memory pool.
Address	Start address of the memory pool.
Size	Size of the memory pool.
Total	Total size of all obtained memory pools.
Date, Time	Date and time of the action.
Action	The action of Broker. The following actions are currently supported: Allocated: memory pool is allocated. Deallocated: memory pool is deallocated.

Maximum TCP/IP Connections per Communicator

This table shows the generated maximum number of TCP/IP connections per communicator. See also:

Note for z/OS

Platform	Maximum Number of TCP/IP Connections per Communicator
BS2000	2,048
Linux	65,534
Windows	4,096
z/OS	16,384

With the Broker-specific attribute POLL, these restrictions can be lifted under z/OS and UNIX. See POLL.

The number of communicators multiplied by the maximum number of connections cannot exceed the maximum number of file descriptors per process.

See also MAX-CONNECTIONS under TCP-OBJECT (Struct INFO_TCP) under Broker CIS Data Structures in the ACI Programming documentation.

Note for z/OS

Under z/OS, the following message may appear in the broker log:

```
ETBD0286 Diagnostic Values: accept: 124, EDC5124I Too many open files.errno2: 84607302 050B0146
```

The most common reason for this TCP/IP Communicator diagnostic message is the limitation of open files per user. The value of MAXFILEPROC in the BPXPRMOO parmlib member should be greater than the expected number of TCP/IP connections.

7 Administering Broker Stubs

Available Stubs	130
■ ARFETB	131
■ BROKER	131
■ CICSETB	134
■ COMETB	136
■ IDMSETB	137
■ MPPETB	
■ NATETB23	
■ NATETBZ	139
Tracing for Broker Stubs	139
Timeout Settings for Broker Stubs	143
Transport Methods for Broker Stubs	
SVC Number for Broker Communication	147
Considerations for Users without Adabas	149
Support of Clustering in a High Availability Scenario	149

Available Stubs

This table lists all broker stubs available under z/OS are to be used with the programming languages Assembler |C| COBOL | Natural | PL/I.

Your selection of a specific broker stub depends on the following:

- the environment (TP monitor, TSO, Batch, Natural)
- the transport method (NET or TCP)
- the availability of administration features such as trace
- the Software AG product using the stub

	Suppo	orted Tr	ansport		Default Transport		Trace	
Environment	NET	ТСР	SSL	Stub Module			ТСР	NET
Batch, TSO	Yes	Yes	(1)	BROKER (4)	NET	Setting the	Setting Trace	
IMS (BMP)	Yes	Yes	(1)	BROKER (4)	NET	Default Transport Method		
IMS (MPP)	Yes	Yes	(1)	MPPETB (4)	NET	n/a	_	
CICS	Yes	Yes	(1)	CICSETB (4)	NET	n/a		
Com-plete	Yes	Yes	(1)	COMETB (4)	NET	n/a		
Natural	Yes	Yes	(1)	NATETB23 (4)	NET	n/a	Setting Trace	n/a ⁽³⁾
Natural RPC Server	Yes	Yes	(1)	NATETBZ (2)	NET	n/a	n/a ⁽³⁾	n/a ⁽³⁾
Event Replicator for Adabas	Yes	Yes	(1)	ARFETB (2)	NET	n/a	n/a	n/a
IDMS/DC	No	Yes	(1)	IDMSETB (4)	TCP	n/a	n/a	n/a



Notes:

- 1. Use IBM's Application Transparent Transport Layer Security (AT-TLS). See *Using SSL/TLS with EntireX Components*.
- 2. These stubs may run in SRB mode and are zIIP-eligible. Refer to the related SAG product documentation for further details. Stubs capable of running in SRB mode do not support tracing.
- 3. For error detection, see *Tracing Broker Communication in Natural*.
- 4. The listed stub modules are the front ends for your application. Depending on transport and usage of *EntireX Security*, additional modules from EXX108.LOAD are loaded dynamically.

ARFETB

This reentrant stub is for exclusive use by Adabas Replication Services.

Prerequisites and Installation Notes

- No linkage is required.
- It may run in SRB mode and is zIIP-eligible.
- The load library containing ARFETB must be added to the STEPLIB chain of the ARF started task.

BROKER

BROKER is the recommended stub for any batch environment except Natural. For Natural, use NATETB23 or NATETBZ.

- Prerequisites and Installation Notes
- Linkage

Prerequisites and Installation Notes

- This stub can be used in a multithreading (subtasking) environment, provided ADAUSER is not linked to the application.
- It is recommended to load BROKER dynamically within the application program and not to link BROKER with any Adabas link routine. BROKER will attempt to load ADALNKR dynamically.
- However, if BROKER has to be statically linked, see the subsection *Linkage* below.
- At runtime you *must* ensure that library EXX108.LOAD is in the steplib of the application and that Adabas library WAL842.LOAD (or above) is in the steplib when using NET transport. See *Contents of Mainframe Installation Medium* in the z/OS Installation documentation.

Linkage

Choose the method most appropriate for your application:

- Method 1: Reentrant (Thread-safe)
- Method 2: Non-reentrant

Method 1: Reentrant (Thread-safe)

Link your application to module BROKER from the EntireX load library (EXX108.LOAD).

Linkage statements:

```
INCLUDE userlib(mainpgm) Main Program
INCLUDE exxlib(BROKER) Broker stub
ENTRY mainpgm
NAME ...
```

The SVC number may be specified as part of the Broker ID, for example:

```
ETB220:SVC237:NET
```

Method 2: Non-reentrant

Link your application to module BROKER from the EntireX load library (EXX108.LOAD) and the module ADAUSER from the Adabas load library.

Linkage statements:

```
INCLUDE userlib(mainpgm) Main Program
INCLUDE exxlib(BROKER) Broker stub
INCLUDE wallib(ADAUSER) Adabas batch/TSO front end
ENTRY mainpgm
NAME ...
```

By linking with ADAUSER you can specify the required SVC in the Adabas DDCARD parameter of the application job, as shown below:

```
//J020S1 EXEC PGM=PROGRAM

//STEPLIB DD DISP=SHR,DSN=EXX108.L0AD

// DD DISP=SHR,DSN=WAL842.L0AD

//ETBPRINT DD SYSOUT=*

//SYSUDUMP DD SYSOUT=*

//DDCARD DD *

ADARUN MODE=MULTI,PROGRAM=USER,SVC=237

/*
```

When linking the stub for use in IMS (BMP), substitute the appropriate Adabas link module for this environment.

Make sure the Adabas link routine (ADALNK/ADALNKR) does not contain any exits that assume the length of the Adabas data area UB is extended beyond its default value. Contact Software AG Support if you are unsure about this.

CICSETB

CICSETB is the recommended stub for any CICS environment except Natural. For Natural, use NATETB23 or NATETBZ.

- Prerequisites and Installation Notes
- Linkage

Prerequisites and Installation Notes

- EntireX RPC Server for z/OS CICS® uses CICSETB as default.
- It is recommended to load CICSETB dynamically within the application program.
- CICSETB will attempt to load ADACICS dynamically, using EXEC CICS LINK PROGRAM.
- CICSETB, CICSETB2 and EXAGLUE must be available in the CICS RPL search chain if called dynamically. Alter the CICS procedure or job, adding the EXX load library to both the STEPLIB and DFHRPL library concatenations. See also the job EXXCICS in the EXX jobs library for altering the CICS-related entries.
- CICSETB can be used with or without a CICS TWA (transaction work area).

■ With TWA

At least 24 bytes of transaction work area must be defined in your CICS transaction if you choose to specify a TWA.

■ Without TWA

Prerequisite is building an Adabas CICS interface, specifying PARMTYP=ALL for either the ADAGSET or LGBLSET MACRO (depending upon the Adabas version). There are no application changes required for using CICSETB without TWA.

■ If the name of your Adabas CICS link routine is different from "ADACICS", please use zap EXX108.ZAPS(EXX0007) to set the site-specific name of your Adabas CICS link routine. By default, the zap will change the name to "ADABAS".

Linkage

Link your application to member CICSETB from the EntireX load library (EXX108.LOAD).

Linkage statements for COBOL applications:

```
INCLUDE cicslib(DFHECI) CICS Prolog Module
INCLUDE userlib(mainpgm) Main Program
INCLUDE cicslib(DFHELII) CICS Module
INCLUDE exxlib(CICSETB) Broker stub
ENTRY mainpgm
NAME ...
```

Linkage statements for Assembler applications:

```
INCLUDE cicslib(DFHEAI) CICS Prolog Module
INCLUDE userlib(mainpgm) Main Program
INCLUDE cicslib(DFHEAIO) CICS Module
INCLUDE exxlib(CICSETB) Broker stub
ENTRY mainpgm
NAME ...
```

COMETB

COMETB is the stub for any Com-plete environment. For Natural, use NATETB23 or NATETB2.

- Prerequisites and Installation Notes
- Linkage
- EXAENV Environment Store

Prerequisites and Installation Notes

- We recommend you load COMETB dynamically within the application program.
- COMETB must be available in the COMPLIB search chain if called dynamically. Modify the Com-plete procedure or job, adding the EXX load library to the COMPLIB library concatenations.
- COMETB requires about 950 KB storage above the line. Increase the Com-plete SYSPARM THSIZEABOVE by 950 KB.
- If the *EXAENV Environment Store* is used (DD EXAENV is defined in the Com-plete started task JCL), increase the ULIB region size for your application that calls COMETB by 4 KB storage below the line.

Linkage

It is also possible to link your application to member COMETB from the EntireX load library (EXX108.LOAD).

EXAENV Environment Store

The EXAENV Environment Store is used under Com-plete only. A partitioned data set is assigned by DD EXAENV. It represents the environment store for all Com-plete users. PDS members in the store are used to define variables and assign values. The PDS member name used is the name of the user logged on to Com-plete. If you want to define your own variables, add a text member with your user name and put all variables into it.

A member with the name DEFAULT may contain global variables valid for all users.

The environment store has following data set characteristics:

DSORG=PO LRECL=80 RECFM=FB

A line in the text member setting a variable and its value looks like:

ETB_STUBLOG=1

Variable name and variable value are left-justified and delimited by an equals sign. The first blank in the line identifies the end of the environment value definition.

See also Prerequisites and Installation Notes.

IDMSETB

Prerequisites and Installation Notes

IDMSETB cannot be called dynamically.

Linkage

Link your application to member IDMSETB from the EntireX load library (EXX108.LOAD).

MPPETB

Prerequisites and Installation Notes

MPPETB can be called dynamically, but the appropriate ADALNK (ADALNI) must be linked to MPPTB beforehand.

Linkage

Link your application to member MPPETB from the EntireX load library (EXX108.LOAD) and the appropriate Adabas link module from the Adabas load library.

NATETB23

NATETB23 is the recommended stub for Natural. See also *NATETB2*.

- Prerequisites and Installation Notes for Natural
- Linkage under Natural
- Installation Verification under Natural

Prerequisites and Installation Notes for Natural

- Set the Natural size parameters so that Natural can provide the stub with 34 KB at runtime.
- Send/receive buffers of greater than 32 KB can be used with NATETB23 provided that Adabas library WAL842 (or above) is installed. See Contents of Mainframe Installation Medium in the z/OS Installation documentation.

Linkage under Natural

- Linking the stub for use in z/OS Batch, TSO, CICS, IMS(BMP), IMS(MPP) and Com-plete:
 - Link NATETB23 in the Load Library to the shared part of the Natural nucleus. NATETB23 is a reentrant and relocatable module.
- Alternatively, the NATETB23 stub can be dynamically invoked by the following Natural parameters:

RCA=BROKER, RCALIAS=(BROKER, NATETB23)

Installation Verification under Natural

> To verify the installation of the stub under Natural

- 1 Log on to Natural library SYSRPC and type MENU.
- 2 Invoke SM Service Directory Maintenance from the main menu.
- 3 Define the Node and Server and save.
- 4 Invoke XC Server Command Execution from the main menu for the node and server defined in the previous step.
- 5 Ping the server with the command PI.

Your environment and the stub are installed correctly if you receive

02150148 Connection error, meaning that the broker and the RPC server are down;

- 00070007 Service not registered, meaning that the broker is up and the RPC server is down;
- an answer from the RPC server.

For other return codes, see *Error Messages and Codes*.

NATETBZ

This reentrant stub is for exclusive use by Natural RPC Server.

Prerequisites and Installation Notes for Natural

- It may run in SRB mode and is zIIP-eligible.
- Set the Natural size parameters so that Natural can provide the stub with 34 KB at runtime.

Linkage under Natural

- To *statically* link the stub for use in z/OS Batch, link NATETBZ into the load library where the Batch Natural nucleus resides. NATETBZ is a reentrant and relocatable module.
- Alternatively, the NATETBZ stub can be called *dynamically* with the following Natural parameters:

RCA=BROKER, RCALIAS=(BROKER, NATETBZ)

Tracing for Broker Stubs

- Setting Trace
- Examples
- Tracing Broker Communication in Natural

Setting Trace

	Stub Module					
How to Set Trace	BROKER, MPPETB	CICSETB	NATETB23		NATETBZ, ARFETB, IDMSETB	
		Define the		Add the following	Trace is	
	Define the	following DD	Define the	variables to the	not	
	following DD	statements in	following DD	EXAENV	supported.	
			statements in			
	your JCL (1):	start CICS (2):	your JCL (3):	Store (4):		

			Stub Module				
Но	w to Set Trac	e	BROKER, MPPETB	CICSETB	NATETB23	СОМЕТВ	NATETBZ, ARFETB, IDMSETB
1	STANDARD		//EXALOG1 ↔ DD SYSOUT=* //TRACE1 ↔ DD SYSOUT=*		//EXALOG1 ↔ DD DUMMY //TRACE1 ↔ DD ↔ SYSOUT=*	EXA_LOG=1 ETB_STUBLOG=1	
2	ADVANCED	Used primarily by system engineers, traces everything from level 1 and provides additional information, for example the Broker ACI control block, as well as information from the transports.	//EXALOG2 ↔ DD SYSOUT=* //TRACE1 ↔ DD SYSOUT=*		//EXALOG2 ↔ DD DUMMY //TRACE1 ↔ DD ↔ SYSOUT=*	EXA_LOG=2 ETB_STUBLOG=2	
3	SUPPORT	This is full tracing through the stub, including detailed traces of control blocks, message information, etc.	//EXALOG3 ↔ DD SYSOUT=* //TRACE1 ↔ DD SYSOUT=*		//EXALOG3 ↔ DD DUMMY //TRACE1 ↔ DD ↔ SYSOUT=*	EXA_LOG=3 ETB_STUBLOG=3	
0	NONE	No tracing. Switch tracing off.	Do not define EXALOG1, EXALOG2 and EXALOG3 DD statements in your JCL.	Do not define EXALOG1, EXALOG2 and EXALOG3 DD statements in your JCL to start CICS.	EXALOG1,	Do not define the variable ETB_STUBLOG and EXA_LOG in EXAENV environment store or set its value to zero.	

	Stub Module					
How to Set Trace	BROKER, MPPETB	CICSETB	NATETB23	СОМЕТВ	NATETBZ, ARFETB, IDMSETB	
Trace Output Location	TCP trace output is written to TRACE1 DD statement while NET trace output is routed to EXALOGn DD statement defined in your JCL.	TCP as well as NET trace output is written to CICS TD queue CSSL. This TD queue is typically assigned to DD statement MSGUSER. Refer to the JCL to start CICS.	TCP trace output is written to TRACE1 DD statement	TCP trace output is controlled by the hardcopy setting in Com-plete. See hardcopy function from the UUTIL menu. If no device name has been defined, the trace is displayed on the terminal. If HC has been specified, the trace will be written to the Com-plete spool and routed to the device name supplied using HC=name. NET trace output is written via COMPLETE Printout Spooling, default destination "SYSOUT=X".		

Notes:

- 1. In this approach, DD assignments are checked by the stub module in order to determine the trace level and output location.
- 2. In this approach, DD assignments are checked by the stub module in order to determine the trace level.
- 3. NATETB23 supports TCP trace but does not support NET trace. For error detection with NET transport, see *Tracing Broker Communication in Natural*.
- 4. In this approach a variable definition in a partitioned data set (PDS) member, the so-called EXAENV environment store is checked in order to determine the trace level. See *EXAENV Environment Store*.

Examples

- > To set trace level 3 for stub module BROKER or MPPETB
- Define the following DD statements in your JCL:

```
//EXALOG3 DD SYSOUT=*
//TRACE1 DD SYSOUT=*
```

- > To set trace level 2 for stub module CICSETB
- Define the following DD statement in the JCL to start CICS:

```
//EXALOG2 DD DUMMY
```

- ➤ To set trace level 1 for stub module COMETB
- Add the following variable name and value to the EXAENV environment store:

```
EXA_LOG=1
ETB_STUBLOG=1
```

Tracing Broker Communication in Natural

If a stub module for Natural does not support tracing (for example NATETBZ, NATETB23 for NET transport) and you want detect errors in broker communication, we recommend using temporarily the platform-specific stub instead.

■ For CICS, use

```
RCA=BROKER, RCALIAS=(BROKER, CICSETB)
```

■ For Com-plete, use

```
RCA=BROKER, RCALIAS=(BROKER, COMETB)
```

Also, PRIVILEG status is required in Com-plete for COMETB.

See Available Stubs for an overview of stub modules and Setting Trace.

142

Timeout Settings for Broker Stubs

Setting timeouts for the transport layer is possible for the transport method TCP. The transport method NET does not support timeouts.

- Setting the TCP/IP Timeout
- Limiting the TCP/IP Connection Lifetime
- SAGTOKEN Utility

Setting the TCP/IP Timeout

If the transport layer is interrupted, communication between the broker and the stub - that is, client or server application - is no longer possible. A client or server might possibly wait infinitely for a broker reply or message in such a situation. To prevent this and return control to your calling application in such a situation, set a timeout value for the transport method.

The timeout value for the transport method is set by the environment variable ETB_TIMEOUT on the stub side. This transport timeout is used together with the broker timeout - which is set by the application in the WAIT field of the broker ACI control block - to calculate the actual value for the transport layer's timeout. This timeout for the transport layer is independent of the timeout settings of the broker kernel.

The following table describes the possible values for the TCP timeout and how to set it per stub module:

		Stub Module		
How to S	et the TCP Timeout	BROKER ⁽²⁾ , MPPETB ⁽²⁾ , BROKER ⁽²⁾ , MPPETB ⁽²⁾ , NATETB23 ⁽²⁾ , NATETBZ ⁽³⁾ , ARFETB ⁽³⁾	COMETB ⁽²⁾	IDMSETB
		Use the SAGTOKEN Utility to set the TCP timeout.	Add the following variable to the <i>EXAENV Environment Store</i> :	TCP timeout is not supported.
0	Infinite wait for the application.	//STEP EXEC ↔ PGM=SAGTOKEN, PARM=('SET ↔ LOCAL, TIMEOUT=O') //STEPLIB DD ↔ DISP=SHR, DSN=EXX108.LOAD	ETB_TIMEOUT=0	

		Stub Module		
How to S	et the TCP Timeout	BROKER ⁽²⁾ , MPPETB ⁽²⁾ , BROKER ⁽²⁾ , MPPETB ⁽²⁾ , NATETB23 ⁽²⁾ , NATETBZ ⁽³⁾ , ARFETB ⁽³⁾	COMETB ⁽²⁾	IDMSETB
n	The transport method additionally waits this time in seconds. A negative value is treated as TIMEOUT=0 (infinite wait for the application). (1)	//STEP EXEC ↔ PGM=SAGTOKEN, PARM=('SET ↔ LOCAL, TIMEOUT=n') //STEPLIB DD ↔ DISP=SHR, DSN=EXX108.LOAD	ETB_TIMEOUT=n	
nothing set	Transport method waits additional 20 seconds. (1)	PGM=SAGTOKEN, PARM=('DELETE ↔	Do not define the variable ETB_TIMEOUT in EXAENV environment store.	

Notes:

- 1. The actual timeout for transport layer equals broker timeout (WAIT field) + transport timeout.
- 2. The stub supports this timeout in the connection phase and during data transfer.
- 3. The stub supports this timeout in the connection phase only.

Limiting the TCP/IP Connection Lifetime

With transport method TCP/IP the broker stub establishes one or more TCP/IP connections to the brokers specified with BROKER-ID. These connections can be controlled by the transport-specific CONNECTION-NONACT attribute on the broker side, but also by the transport-specific environment variable ETB_NONACT on the stub side. If ETB_NONACT is not 0, it defines the non-activity time (in seconds) of active TCP/IP connections to any broker. See ETB_NONACT under *Environment Variables in EntireX*. Whenever the broker stub is called, it checks for the elapsed non-activity time and closes connections with a non-activity time greater than the value defined with ETB_NONACT. This timeout for the transport layer is independent of the timeout settings of the broker kernel.

The following table describes the possible values to limit TCP connection lifetime and how to set it per stub module:

		Stub Module			
How to Limit the TCP Connection Lifetime		BROKER, MPPETB, NATETB23	СОМЕТВ	NATETBZ ⁽¹⁾ , ARFETB ⁽¹⁾ , IDMSETB ⁽¹⁾	
		Use the SAGTOKEN Utility to set the TCP timeout.	Add the following variable to the <i>EXAENV Environment Store</i> :	cannot be	
0	Infinite wait for the application.	//STEP EXEC ↔ PGM=SAGTOKEN, PARM=('SET ↔ LOCAL, NONACT=0') //STEPLIB DD ↔ DISP=SHR, DSN=EXX108.LOAD	ETB_NONACT=0	limited.	
n	The transport method additionally waits this time in seconds. A negative value is treated as TIMEOUT=0 (infinite wait for the application). ⁽¹⁾	//STEP EXEC ↔ PGM=SAGTOKEN, PARM=('SET ↔ LOCAL, NONACT=n') //STEPLIB DD ↔ DISP=SHR, DSN=EXX108. LOAD	ETB_NONACT=n		
nothing set	Transport method waits additional 20 seconds. (1)	//STEP EXEC ↔ PGM=SAGTOKEN, PARM=('DELETE ↔ LOCAL, NONACT) //STEPLIB DD ↔ DISP=SHR, DSN=EXX108.LOAD	Do not define the variable ETB_NONACT in EXAENV environment store.		

SAGTOKEN Utility

SAGTOKEN allows you to set variables. When setting variables with SAGTOKEN, SAGTOKEN error messages may be displayed on the operator console. The steplib EXX108.LOAD of SAGTOKEN must be APF-authorized. See *EntireX SAGTOKEN Messages*.

Syntax

```
//STEP EXEC PGM=SAGTOKEN,PARM=('command scope, variable=value')
//STEPLIB DD DISP=SHR,DSN=EXX108.LOAD
```

Operands

Command	Use
SET	Set or replace a SAGTOKEN variable.
DELETE	Delete a SAGTOKEN variable.
DISPLAY	Display a SAGTOKEN variable.

Scope	Meaning
LOCAL	Applies to the address space.
GLOBAL	Applies to the z/OS image.

Variable	Value
TIMEOUT	For information on TIMEOUT values, see $\it Timeout Settings for Broker Stubs$.
NONACT	For information on NONACT, see <i>Limiting the TCP/IP Connection Lifetime</i> .



Note: If a job uses SAGTOKEN to set local tokens in one step, we recommend that you delete these tokens prior to job termination in order to release all acquired resources.

Transport Methods for Broker Stubs

- Transport Method Values
- Setting the Default Transport Method

Transport Method Values

Transport Value	Description / Tips
	Use Adabas Cross-Memory Services as transport method. See <i>Installing Adabas Components for EntireX under z/OS</i> . It is also possible to communicate remotely with the transport method NET from an application (client or server) to the broker kernel using Entire Net-Work. For remote NET communication, Entire Net-Work must be installed both on the machine where the broker kernel runs and on the machine where your application (client or server) runs, and a connection must be established. Using Adabas modules WAL811 or above allows more than 32 KB of data to be communicated. Otherwise the following maximum values are allowed:

Transport Value	Description /	Tips	
	ACI Version	Max Send/Receive length	
	1	32167	
	2, 3	31647	
	4-8	31643	
	9 or above	31123	
	Note: If Ad	labas version 8 or above	is <i>not</i> used, these same limits still apply under
TCP	Use TCP/IF	as transport method.	

For Secure Sockets Layer/Transport Layer Security (SSL/TLS) as transport method, see table *Using SSL/TLS with EntireX Components*.

Setting the Default Transport Method

For stub module BROKER, DD assignments are checked in order to determine the default transport method.

Transport	How to set Default Transport?
TCP	Define EXATCP as dummy DD statement in your JCL:
	//EXATCP DD DUMMY
NET	Define EXANET as dummy DD statement in your JCL:
	//EXANET DD DUMMY

SVC Number for Broker Communication

Stub	Notes
ARFETB	See your Event Replicator for Adabas documentation for information on how to specify the SVC number used for Broker communication.
BROKER	When Entire Net-Work transport is used, the default SVC number (249) can be overridden in the following ways:
	■ By specifying the SVC number as part of the Broker ID, for example:

Stub	Notes
	ETB220:SVC237:NET
	 By including ADAUSER when linking the stub with the application. This enables the SVC number to be specified in the ADARUN cards of the application job. This option cannot be employed if the application operates within a multithreading application (multiple TCBs). By using the supplied zap if neither of the above options is chosen. See BROKER.
CLCCETT	
CICSETB	When Entire Net-Work transport is used and the default SVC number (249) has to be changed, the Adabas communications module under CICS determines how the SVC number can be changed. See the Adabas documentation for information on how to change the SVC number.
COMETB	■ The Adabas interface is integrated within the TP Monitor Com-plete.
	Add the ADASVC5 parameter to Com-plete (or Adabas TPF) startup parameters as specified below:
	ADASVC5=(dbid,svc)
	where <i>dbid</i> is the node ID selected for use by the EntireX Broker address space, and <i>svc</i> is the Adabas SVC number used by the EntireX Broker started task/job.
	 Optionally consider how to specify the SVC number used for Broker communication maintained within Com-plete's Adabas interface. See the Com-plete documentation.
MPPETB	When Entire Net-Work transport is used and the default SVC number (249) has to be changed, the Adabas communications module under IMS/DC determines how the SVC number can be changed. See the Adabas documentation for information on how to change the SVC number.
NATETB23	■ If you are communicating with EntireX Broker from Com-plete or Adabas TPF, add the ADASVC5 parameter to Com-plete (or Adabas TPF) startup parameters as specified below:
	ADASVC5=(dbid,svc)
	where <code>dbid</code> is the node ID selected for use by the EntireX Broker address space, and <code>svc</code> is the Adabas SVC number used by the EntireX Broker started task/job. For all other environments, see the Natural documentation for information on how to specify the SVC number used for Broker communication.
NATETBZ	See your Natural documentation for information on how to specify the SVC number used for Broker communication.

Considerations for Users without Adabas

For customers who do not have Adabas installed at their site,

- we recommend installing the Adabas modules (library WAL842) delivered with EntireX. See also *Contents of Mainframe Installation Medium* in the z/OS Installation documentation.
- the Adabas modules will greatly improve performance if the transport method NET is used and broker kernel and applications (client or server) communicating through the stub to the broker kernel on the same machine locally, see *Transport Methods for Broker Stubs*.

For information on how to install the Adabas SVC and install Adabas with TP Monitors, see *Installing Adabas Components for EntireX under z/OS*.

Support of Clustering in a High Availability Scenario

EntireX Broker supports clustering in a high-availability scenario, using the environment variable ETB_SOCKETPOOL. See *Environment Variables in EntireX*. This section covers the following topics:

- Introduction
- Exceptions
- Default
- Restriction

See also *High Availability in EntireX*.

Introduction

A TCP/IP connection established between stub and broker is not exclusively assigned to a particular thread. With multithreaded applications, two or more threads may use the same connection. On the other hand, if a connection is busy, another new one is created to exchange data.

In order to access the same broker instance in a clustering environment, an affinity between application thread and TCP/IP connection is needed to always use the same connection within an application thread. Therefore, an environment variable is evaluated to control the handling of TCP/IP connections.

If environment variable ETB_SOCKETPOOL is set to "OFF" (ETB_SOCKETPOOL=OFF), an affinity between threads and TCP/IP connections is established. All requests to one particular broker will use the same TCP/IP connection. ETB_SOCKETPOOL controls all TCP/IP connections.

Stubs ARFETB and NATETBZ always establish an affinity between subtask and TCP/IP connection.

Exceptions

Broker attribute CONNECTION-NONACT is used by the broker to close TCP/IP connections after the elapsed non-activity time. Omit this attribute to keep the TCP/IP connection alive.

Default

ETB_SOCKETPOOL=ON is the default setting. In this case, an established broker connection can be used by any thread if the connection is not busy.

Restriction

Support for this feature is currently not available under CICS, Com-plete, and IDMS/DC.

8 Broker Command-line Utilities

ETBINFO	. 1	15	52
ETBCMD	1	16	31

EntireX Broker provides the internal services ETBINFO and ETBCMD.

These services are implemented internally; nothing has to be started or configured. You can use these services immediately after starting EntireX Broker.

ETBINFO

With this command-line utility you can query the Broker for different types of information, generating an output text string with basic formatting. This text output can be further processed by script languages. ETBINFO uses data descriptions called profiles to control the type of data that is returned for a request. ETBINFO is useful for monitoring and administering EntireX Broker efficiently, for example how many users can run concurrently and whether the number of specified message containers is large enough. You can format your output

- using a profile (recommended)
- using a format string (this may be useful for ad hoc queries)
- by other means external to the broker

This section covers the following topics:

- Running the Command-line Utility
- Command-line Parameters
- Table of Options and Profiles
- Command-line Parameters from File
- Profile
- Format String
- Using SSL/TLS

Running the Command-line Utility

In a z/OS environment, run the command-line utility ETBINFO as shown below.

Note: The service data set name and member cannot be accessed directly, but only indirectly by its DD name in the JCL.

```
//ETBINFO EXEC PGM=ETBINFO,
// PARM=('ENVAR(''ETB_STUBLOG=0'')/ -p "//''EXX108.JOBS(BROKER)''" ',
// '-bbrokerid -dBROKER -xuid -ypwd')
//STEPLIB DD DISP=SHR,DSN=< EXB-load-lib >
//
         DD
               DISP=SHR,DSN=< EXX-load-lib >
//
          DD
               DISP=SHR,DSN=< WAL-load-lib >
//TRACE1 DD
               SYSOUT=*
                                                    stublog
//SYSOUT DD
               SYSOUT=*
                                                    stderr
```

```
//SYSPRINT DD SYSOUT=* stdout
//
```

The SVC number specified in the ADARUN parameter must match the SVC number used for the target Broker ID.

Command-line Parameters

The table below explains the command-line parameters. The format string and profile parameters are described in detail following the table. All entries in the Option column are case-sensitive.

Option	Command-line Parameter	Req/ Opt	Explanation				
- b	brokerid	R	Broker identifier, for example localhost:1971:TCP.				
- C	class	0	Class as selection criterion.				
- C		О	Create output with comma-separated values, suitable for input into a preadsheet or other analysis tool. Any format string specified by means of format string or profile command-line parameters is ignored.				
- d	object	R	Defines the information retrieved from broker. If an optional profile is provided, object and profile must match. See <i>Table of Options and Profiles</i> .				
- e	recv class	О	Receiver's class name. This selection criterion is valid only for object PSF.				
- f	Format String	0	Format string how you expect the output. See <i>Profile</i> .				
- g	recv service	О	Receiver's service name. This selection criterion is valid only for object PSF.				
- h	help	О	Prints help information.				
- i	convid	Ο	Conversation ID as selection criterion. Only valid for object CONVERSATION.				
- I	conv type	О	Conversation's type.				
- j	recv server	Ο	Receiver's server name. This selection criterion is valid only for object PSF.				
- k	recv token	0	Receiver's token. This selection criterion is valid only for object PSF.				
-]	level	O	The amount of information displayed: FULL All information. SHORT User-specific information.				
- m	recv userid	0	Receiver's user ID. This selection criterion is valid only for object PSF.				
- n	server name	0	Server name. This selection criterion is valid only for the objects SERVER, SERVICE or CONVERSATION.				
- p	pds(member)	0	Here you can specify a PDS member that defines the layout of the output. See <i>Table of Options and Profiles</i> .				

Option	Command-line Parameter	Req/ Opt	Explanation			
- q	puserid	O	Physical user ID. This selection criterion is valid only for objects CLIENT, SERVER, CONVERSATION. Note: Must be a hex value.			
- r	sec	0	Refresh information after seconds.			
- S	service	Ο	Service. This selection criterion is valid only for objects SERVER, SERVICE or CONVERSATION.			
-t	token	Ο	This selection criterion is valid only for objects CLIENT, SERVER, SERVICE or CONVERSATION.			
- u	userid	Ο	User ID. This selection criterion is only valid for the display types CLIENT, SERVER, SERVICE or CONVERSATION.			
- V	UOW status	О	Unit of work status. This selection criterion is valid only for object PSF.			
- W	UOW ID	О	Unit of work ID. This selection criterion is valid only for object PSF.			
- X	userid	О	User ID. For security purposes.			
- y	password	О	Password. For security purposes.			
- Z	token	Ο	Used with userid to uniquely identify a caller to Command and Information Services.			

Table of Options and Profiles

Profiles are provided for a more structured and improved understandable output. If you do not use the profile option or a format string, your output will be an unformatted list with all columns of that display type. To display specific columns, specify a profile (you can create your own) that includes only those columns.



Note: The deprecated profiles are still delivered for compatibility reasons.

			Information Object
Option -d (object)	Option -p (profile)	Option - p (deprecated profile)	(see Information Reply Structures)
BROKER	broker2	broker	BROKER-OBJECT
CLIENT	client2	client	CLIENT-SERVER-PARTICIPANT-OBJECT
CMDLOG-FILTER	clogflt2	clogflt	CMDLOG_FILTER-OBJECT
CONVERSATION	conv2	conv	CONVERSATION-OBJECT
NET	net2	net	NET-OBJECT
POOL	pool2	pool	POOL-USAGE-OBJECT
PSF	psf2	psf	PSF-OBJECT
PSFADA	psfada2	psfada	PSFADA-OBJECT
PSFCTREE	psfctre2	psfctree	PSFCTREE-OBJECT

			Information Object
Option -d (object)	Option -p (profile)	Option -p (deprecated profile)	(see Information Reply Structures)
PSFDIV	psfdiv2	psfdiv	PSFDIV-OBJECT
RESOURCE	resourc2	resource	RESOURCE-USAGE-OBJECT
SECURITY	securit2	security	SECURITY-OBJECT
SERVER	server2	server	CLIENT-SERVER-PARTICIPANT-OBJECT
SERVICE	service2	service	SERVICE-OBJECT
SSL	ss12	ssl	SSL-OBJECT
STATISTICS	statist2	statis	STATISTICS-OBJECT
TCP	tcp2	tcp	TCP-OBJECT
UOW-STATISTICS	uowstat2	uowstat	UOW-STATISTICS
USER	user2	user	USER-OBJECT
WORKER	worker2	worker	WORKER-OBJECT
WORKER-USAGE	wkrusag2	wkrusag	WORKER-USAGE-OBJECT

Command-line Parameters from File

ETBINFO supports an alternative method of passing command-line parameters.

If the DDNAME INFFILE is allocated, using

```
//INFFILE DD DISP=SHR,DSN=pds(member)
```


and no command-line parameters are specified in the EXEC instruction, the content of the allocated member is evaluated. See sample member below (the apostrophes are included to show the record format (LRECL 80):

```
'-blocalhost:3930:TCP
'-dBROKER
```

If ETBINFO is configured using INFFILE and a profile is specified, the syntax of the -p is as follows:

```
-p//'dsname(member)' if a PDS member is used-p//'dsname' if a sequential data set is used
```

The syntax is based on IBM conventions for fopen.



Profile

If you do not use the profile option or a format string, your output will be an unformatted list with all columns of that display type. We recommend using the profiles described under *Table of Options* and *Profiles*.

On z/OS, the profiles used to control the format of data displayed are members of the EXB source library and are named SERVER2, CLIENT2, etc. They can be saved as either sequential files or PDS members.

- Hints for Creating your own Profile
- Example 1 Default Profile
- Example 2 Custom Profile

Hints for Creating your own Profile

You can either delete the columns not required or copy the default profile and modify the order of the columns. Ensure that the column names have a leading "%". Column names can be written in one line or on separate lines. The output is always written side by side. With profile parameters <code>%DATE</code> and <code>%TIME</code> you can provide a timestamp for the command-line query.

Example 1 - Default Profile

This example uses the default profile delivered with EntireX for object BROKER: BROKER2:

```
//ETBINFO EXEC PGM=ETBINFO,PARM=('/-b ETBO01::NET -d SERVICE ',
// '-p "//''EXX108.JOBS(SERVICE)''" -1 FULL -xUID')
```

The following list is displayed:

```
Broker Identification
       Broker Information of BROKER-ID:
       on Platform:
                                             PC Windows 10 Enterprise
       SYSPLEX-NAME:
       Process ID (PID):
                                            11056
       Thread ID (TID):
                                            2B34
       Running on Host:
                                            myHost
   Version and License information
       Product Version:
                                             EntireX 10.8.0.00
       Highest supported API Version:
                                            xOD (Hex value)
       Highest supported CIS Version:
Active license (LICENSE-FILE):
                                            xOC (Hex value)
       Active License (LICENSE-FILE):
C:\SoftwareAG\Suite1011\EntireX\config\license.xml
       SNMP Licensed:
                                            01 (00: no, 01: yes)
       Valid until (EXPIRATION):
                                            UNLIMITED
```

```
Configuration Details
Broker attribute file:

C:\SoftwareAG\Suite1011\EntireX\config\etb\ETB001\ETB001.atr
Broker Log File:

C:\SoftwareAG\Suite1011\EntireX\config\etb\ETB001\ETB001.log
Size of Broker Log File:
Security Type:

00

00: No Security
01: EntireX Security
02: Light
03: Other
```

Example 2 - Custom Profile

This example uses profile MYPROF you created yourself:

```
//ETBINFO EXEC PGM=ETBINFO,PARM=('/-b ETBO01::NET -d SERVICE ',
// '-p "//''EXX108.JOBS(MYPROF)''" -xUID')
```

In this example, profile MYPROF contains: %4.4SERVERCLASS %SERVERNAME. The following list is displayed:

```
ACLA ASERVER
BCLA BSERVER
CCLA CSERVER
```

Format String

The format string, if specified, will override the use of a profile. The format string is built like a printf() in C language. The string must be enclosed in quotation marks. You can specify the columns by using a "%" and the column name. The column name must contain letters only. Numeric characters are not allowed. You can specify the length of column output by using a format precision, as in the ANSI-C printf() function. The column name must be followed by a blank. For example:

```
etbinfo -b ETB001 -d BROKER -f "%12.12CPLATNAME %NUM-SERVER %NUM-CLIENT"
```

which produces the following output, for example:

```
MVS/SP 7.04 30 100
```

You can also use an arbitrary column separator, which can be any character other than "%". You can use \n for a new line in the output and \t for a tabulator in the format string or profile. For example:

```
etbinfo -b ETB001 -d SERVER -f "UserID: %5.5USER-ID Token: %5.5TOKEN"
```

which produces:

```
UserID: HUGO Token: MYTOK
UserID: EGON Token:
UserID: HELMU Token: Helmu
```

If you want to structure your output a little more, you can operate with the \n or \t character. For example:

```
etbinfo -b ETB001 -d SERVICE -f "Class:%5.5SERVER-CLASS \n\tName:%5.5SERVER-NAME ↔\n\tService:%5.5SERVICE"
```

which produces:

```
Class:DATAB
Name:DB10
Service:Admin
Class:PRINT
Name:LPT1
Service:PRINT
...
```

You can also add a timestamp to the query:

```
etbinfo -b ETB001 -d BROKER -f "%DATE %TIME"
```


which produces:

```
2014-08-19 10:00:00.234
```

Using SSL/TLS

For establishing an SSL connection on z/OS, IBM's Application Transparent Transport Layer Security (AT-TLS) can be used where the establishment of the SSL connection is pushed down the stack into the TCP layer.

Configure the AT-TLS rules for the policy agent (PAGENT) 4 using an appropriate client 1 and the z/OS Management Facility (z/OSMF) 2. Together with SSL parameters (to provide certificates stored in z/OS as RACF keyrings) define AT-TLS rules, for example by using the application 5 job name and local TCP port number. If the rules match, the TCP connection is turned into an SSL connection 6. Refer to your IBM documentation for more information, for example the IBM Redbook Communications Server for z/OS VxRy TCP/IP Implementation Volume 4: Security and Policy-Based Networking.



- ① Client to interact with z/OS Management Facility (z/OSMF).
- ② AT-TLS rules are defined with z/OSMF policy management.
- 3 Policy Repository with AT-TLS rules stored as z/OS files.
- Policy Agent, MVS task PAGENT, provides AT-TLS rules through a policy enforcement point (PEP) to TCP/IP stack.
- 6 Application using TCP connection.
- 6 If AT-TLS rules match, the TCP connection is turned into an SSL connection.

Notes:

- 1. The client \odot may vary per operating system, for example a Web browser for z/OS 2.1.
- 2. z/OSMF 2 includes other administration and management tasks in addition to policy management.
- 3. Policy Management 3 includes other rules, such as IP filtering, network address translation etc.

> To set up SSL with AT-TLS

- To operate with SSL, certificates need to be provided and maintained. Depending on the platform, Software AG provides default certificates, but we strongly recommend that you create your own. See *SSL/TLS Sample Certificates Delivered with EntireX* in the EntireX Security documentation.
- Set up the tool for a TCP/IP connection. On mainframe platforms, use *Transport-method-style Broker ID*. Example:

ETB024:1699:TCP

- Configure AT-TLS to turn the TCP/IP connection to an SSL connection, using a client to interact with the z/OS Management Facility (z/OSMF). The outcome of this configuration is a Policy Repository with AT-TLS rules stored as z/OS files. This file is the configuration file for the Policy Agent, MVS task PAGENT.
- 4 Make sure the broker is prepared for SSL connections as well. See *Running Broker with SSL/TLS Transport* in the platform-specific Administration documentation.

ETBCMD

With this command-line utility you can take actions - for example purge a unit of work, stop a server, shut down a Broker - against EntireX Broker.

- Running the Command-line Utility
- Command-line Parameters
- Command-line Parameters from File
- List of Commands and Objects
- Examples
- Using SSL/TLS

Running the Command-line Utility

In a z/OS environment, run the ETBCMD command-line utility like this:

```
//ETBCMD EXEC PGM=ETBCMD,
// PARM=('ENVAR(''ETB_STUBLOG=0'')/ -bbrokerid ',
// '-dBROKER -c... -xuid -ypwd')
//STEPLIB DD DISP=SHR,DSN=< EXB-load-lib >
// DD DISP=SHR,DSN=< EXX-load-lib >
// DD DISP=SHR,DSN=< WAL-load-lib >
//TRACE1 DD SYSOUT=* stderr
//SYSPRINT DD SYSOUT=* stdout
//
```

The SVC number specified in the ADARUN parameter must match the SVC number used for the target Broker ID.

Command-line Parameters

The table below explains the command-line parameters. All entries in the **Option** column are case-sensitive.

Command-line Parameter	Option	Parameter	Req/ Opt	Explanation
brokerid	- b	e.g. ETB001	R	Broker ID.
command	- C	■ ALLOW-NEWUOWMSGS	R	Command to be performed. See <i>List</i>
		APPMON-ON		of Commands and Objects below.
		■ APPMON-OFF		
		■ CLEAR-CMDLOG-FILTER		
		■ CONNECT-PSTORE		

Command-line Parameter	Option	Parameter	Req/ Opt	Explanation
		■ DISABLE-ACCOUNTING		
		■ DISABLE-CMDLOG-FILTER		
		■ DISABLE-CMDLOG		
		■ DISABLE-DYN-WORKER		
		■ DISCONNECT-PSTORE		
		■ ENABLE-ACCOUNTING		
		■ ENABLE-CMDLOG-FILTER		
		■ ENABLE-CMDLOG		
		■ ENABLE-DYN-WORKER		
		■ FORBID-NEWUOWMSGS		
		PING		
		■ PRODUCE-STATISTICS		
		■ PURGE		
		■ RESET-USER		
		■ RESUME		
		■ SET-CMDLOG-FILTER		
		■ SET-COLLECTOR		
		■ SET-UOW-STATUS		
		■ SHUTDOWN		
		■ START		
		■ STATUS		
		■ STOP		
		SUSPEND		
		■ SWITCH-CMDLOG		
		■ TRACE-FLUSH		
		■ TRACE-OFF		
		■ TRACE-ON		
		■ TRAP-ERROR		
object type	- d	■ BROKER	R	The object type to be operated on. See
		<pre>CONVERSATION</pre>		List of Commands and Objects below. Within EntireX Broker
		■ PARTICIPANT		nomenclature, a participant is an
		■ PSF		application implicitly or explicitly
		■ SECURITY		logged on to the Broker as a specific user. See <i>Implicit Logon</i> and <i>Explicit</i>

Command-line Parameter	Option	Parameter	Req/ Opt	Explanation
		■ SERVER		Logon. A participant could act as
		■ SERVICE		client or server.
		■ TRANSPORT		
	- D	collector brokerid	0	For command SET-COLLECTOR only. If provided, sets the collector ID to the given collector broker ID.
	- e	errornumber	О	Error number being trapped.
	- E		0	Exclude attach servers from service shutdown.
help	- h		О	Prints help information.
class/server/service	- n	class/server/service	0	Service triplet.
option	- O	■ ACCEPTED	О	Command option.
		■ CANCELLED		
		■ IMMED		
		■ QUIESCE		
		■ LEVEL <i>n</i> , where $n=1-8$		
puserid	- p	puserid	О	Physical User ID. For SERVER and PARTICIPANT objects only. This must be a hex value.
seqno	- S	sequence number	О	Sequence number of participant.
token	-t	token	О	Token. For PARTICIPANT object only.
uowid	- u	uowid	О	Unit of work ID. For PSF object only.
userid	- U	userid	О	User ID. For PARTICIPANT object only.
secuserid	- X	userid	О	User ID for security purposes.
transportid	- X	Transport ID	0	One of the following: $COM NET SSL Snn TCP Tnn$. See table below.
secpassword	- y	password	О	Password for security purposes.

Transport ID Values

This table explains the possible values for parameter transportid:

Transport ID	Explanation
СОМ	all communicators
NET	NET transport communicator
SSL	all SSL communicators
S00	SSL communicator 1
S01	SSL communicator 2
S02	SSL communicator 3
S03	SSL communicator 4
S04	SSL communicator 5
TCP	all TCP/IP communicators
T00	TCP/IP communicator 1
T01	TCP/IP communicator 2
T02	TCP/IP communicator 3
T03	TCP/IP communicator 4
T04	TCP/IP communicator 5

Command-line Parameters from File

ETBCMD supports an alternative method of passing command-line parameters.

If the DDNAME CMDFILE is allocated, using

```
//CMDFILE DD DISP=SHR,DSN=pds(member)
```

and no command-line parameters are specified in the EXEC instruction, the content of the allocated member is evaluated. See sample member below (the apostrophes are included to show the record format (LRECL 80):

```
'-blocalhost:3930:TCP
'-dBROKER
```



Caution: Make sure CMDFILE does not contain line numbers in columns 73-80. If line numbers are present, arguments are not passed correctly. Only one option per line is supported.

List of Commands and Objects

This table lists the available commands and the objects to which they can be applied.

	Object								
	BROKER	CONVERS-	PARTICI-	PSF	SECURITY	SERVER	SERVICE	TRANSPORT	
Command		ATION	PANT						
ALLOW-NEWUOWMSGS				х					
APPMON-OFF	х								
APPMON-ON	х								
CLEAR-CMDLOG-FILTER	х								
CONNECT-PSTORE				х					
DISABLE-ACCOUNTING	х								
DISABLE-CMDLOG-FILTER	х								
DISABLE-CMDLOG	х								
DISABLE-DYN-WORKER	х								
DISCONNECT-PSTORE				х					
ENABLE-ACCOUNTING	х								
ENABLE-CMDLOG-FILTER	х								
ENABLE-CMDLOG	х								
ENABLE-DYN-WORKER	х								
FORBID-NEWUOWMSGS				х					

	Object							
	BROKER	CONVERS-	PARTICI-	PSF	SECURITY	SERVER	SERVICE	TRANSPORT
Command		ATION	PANT					
PING	х							
PRODUCE-STATISTICS	х							
PURGE				х				
RESET-USER					х			
RESUME								х
SET-CMDLOG-FILTER	х							
SET-COLLECTOR	х							
SET-UOW-STATUS				х				
SHUTDOWN	х	х	х			х	х	
START								х
STATUS								х
STOP								х
SUSPEND								х
SWITCH-CMDLOG	х							
TRACE-FLUSH	х							
TRACE-OFF	х			х	х			
TRACE-ON	х			х	х			
TRAP-ERROR	х							

Examples


Example	Description
etbcmd -b etb001 -h	Displays ETBCMD help text.
etbcmd -b etb001 -d BROKER -c TRACE-OFF	Turns Broker tracing off.
etbcmd -b etb001 -d BROKER -c TRACE-ON -o LEVEL2	Sets Broker trace level to 2.
etbcmd -b etb001 -d BROKER -c SHUTDOWN	Performs Broker shutdown.
etbcmd -b etb001 -d SERVICE -c SHUTDOWN -o IMMED -n ACLASS/ASERVER/ASERVICE	Shut down service CLASS=ACLASS, SERVER=ASERVER, SERVICE=ASERVICE. See also SHUTDOWN SERVICE under <i>Broker Command and Information Services</i> in the EntireX Broker documentation for more information on shutdown options.
	Create list of servers and shutdown specific server in two steps (first step uses ETBINFO). See also SHUTDOWN SERVER.

Example	Description			
etbinfo -b etb001 -d SERVER -1 FULL -f"%USER-ID %SEQNO"	1. Determine a list of all servers with sequence numbers			
etbcmd -b etb001 -d SERVER -c SHUTDOWN -o IMMED -S32	2. Shutdown server with sequence number 32.			
etbcmd -b etb001 -d BROKER -c PING	Performs an EntireX ping against the Broker.			
etbcmd -b etb001 -d PSF -c DISCONNECT-PSTORE	Disconnects the Broker PSTORE.			
etbcmd -b etb001 -d PSF -c CONNECT-PSTORE	Connects the Broker PSTORE.			
etbcmd -b etb001 -d PSF -c PURGE -u 100000000000001A	Purges a unit of work.			
etbcmd -b etb001 -d PSF -c ALLOW-NEWUOWMSGS	Allows new units of work to be stored.			
etbcmd -b etb001 -d PSF -c FORBID-NEWUOWMSGS	Disallows new units of work to be stored.			
etbcmd -b etb001 -d PSF -c SET-UOW-STATUS -o ACCEPTED -n ACLASS/ASERVER/ASERVICE	Sets the status of UOWs that reside in the postpone queue back to ACCEPTED for service ACLASS/ASERVER/ASERVICE. See also <i>Postponing Units of Work</i> under <i>Using Persistence and Units of Work</i> in the platform-independent Administration documentation.			
etbcmd -b etb001 -d PSF -c SET-UOW-STATUS -o CANCELLED -u 001000000000000000	Cancel UOW with UOWID 001000000000100 that resides in the postpone queue. See also <i>Postponing Units of Work</i> .			

Using SSL/TLS

For establishing an SSL connection on z/OS, IBM's Application Transparent Transport Layer Security (AT-TLS) can be used where the establishment of the SSL connection is pushed down the stack into the TCP layer.

Configure the AT-TLS rules for the policy agent (PAGENT) 4 using an appropriate client 1 and the z/OS Management Facility (z/OSMF) 2. Together with SSL parameters (to provide certificates stored in z/OS as RACF keyrings) define AT-TLS rules, for example by using the application 5 job name and local TCP port number. If the rules match, the TCP connection is turned into an SSL connection 6. Refer to your IBM documentation for more information, for example the IBM Redbook Communications Server for z/OS VxRy TCP/IP Implementation Volume 4: Security and Policy-Based Networking.



- 1 Client to interact with z/OS Management Facility (z/OSMF).
- 2 AT-TLS rules are defined with z/OSMF policy management.
- 3 Policy Repository with AT-TLS rules stored as z/OS files.
- 4 Policy Agent, MVS task PAGENT, provides AT-TLS rules through a policy enforcement point (PEP) to TCP/IP stack.
- **6** Application using TCP connection.
- **6** If AT-TLS rules match, the TCP connection is turned into an SSL connection.

Notes:

- 1. The client 1 may vary per operating system, for example a Web browser for z/OS 2.1.
- z/OSMF 2 includes other administration and management tasks in addition to policy management.
- 3. Policy Management 3 includes other rules, such as IP filtering, network address translation etc.

> To set up SSL with AT-TLS

- To operate with SSL, certificates need to be provided and maintained. Depending on the platform, Software AG provides default certificates, but we strongly recommend that you create your own. See *SSL/TLS Sample Certificates Delivered with EntireX* in the EntireX Security documentation.
- Set up the tool for a TCP/IP connection. On mainframe platforms, use *Transport-method-style Broker ID*. Example:

ETB024:1699:TCP

- Configure AT-TLS to turn the TCP/IP connection to an SSL connection, using a client to interact with the z/OS Management Facility (z/OSMF). The outcome of this configuration is a Policy Repository with AT-TLS rules stored as z/OS files. This file is the configuration file for the Policy Agent, MVS task PAGENT.
- 4 Make sure the broker is prepared for SSL connections as well. See *Running Broker with SSL/TLS Transport* in the platform-specific Administration documentation.

9 Operator Commands

Command Syntax	172
General Broker Commands	
Participant-specific Commands	178
Security-specific Commands	
Transport-specific Commands	
■ XCOM-specific Commands	
Application Monitoring-specific Commands	192

Command Syntax

The following command format is required to communicate with EntireX Broker, using the operator console. Parameters in UPPERCASE must be typed "as is". Parameters in lowercase must be substituted with a valid value. Operator commands have the following format:

F task_name, command[parameter]

where task_name is the name of the EntireX Broker started task or job at your installation

command is the operator command

parameter is an optional parameter allowed by the operator command you are issuing

Note: In earlier versions, the command prefix "APPL=" was required by an internal interface that is no longer used. You may omit "APPL=" now, but this is still valid for compatibility reasons.

General Broker Commands

The following broker commands are available:

- BROKER TRACE
- DPOOL
- DRES
- DSTAT
- DWM
- ETBEND
- ETBSTOP
- FLUSH
- PSTORE TRACE
- SHUTDOWN class, server, service
- TRACE

■ TRAP-ERROR

BROKER TRACE

Alias of broker command TRACE. Modifies the setting of the broker-specific attribute TRACE-LEVEL.

Example

- > To set a trace level 2 for broker
- Enter command:

```
/F taskname, BROKER TRACE=2
```

If the console prompt is suppressed, enter an MSG command before the console command:

```
MSG partition_id
```

See TRACE-LEVEL under Broker-specific Broker Attributes.

DPOOL

Lists all memory pools currently allocated by EntireX Broker. Start address, pool size in bytes and name of pool are provided. There can be multiple entries for a specific type of pool.

Sample Output

```
ETBM0720 Operator typed in: DP00L
ETBM0657 Broker pool usage:
ETBM0657 0x2338FFB8 16781380 bytes COMMUNICATION POOL
ETBM0657 0x243A9EB8 368964 bytes CONVERSATION PO
ETBM0657 0x24404F38 233668 bytes CONNECTION POOL
                          368964 bytes CONVERSATION POOL
                         4395204 bytes LONG MESSAGES POOL
ETBM0657 0x2443EF38
ETBM0657 0x24870BB8 3703876 bytes SHORT MESSAGES POOL
ETBM0657 0x24BF9398 134244 bytes PARTICIPANT POOL
                            36996 bytes PARTICIPANT EXTENSION POOL
ETBM0657 0x24C1AF78
ETBM0657 0x24C24798
ETBM0657 0x24C2BDA8
                            26724 bytes PROXY QUEUE POOL
                           131668 bytes SERVICE ATTRIBUTES POOL
ETBM0657 0x24C4CB98
                            54372 bytes SERVICE POOL
ETBM0657 0x24C5AF78
                            32900 bytes SERVICE EXTENSION POOL
ETBM0657 0x24C63B18
ETBM0657 0x24C79398
ETBM0657 0x24CA5F38
ETBM0657 0x24CD1798
                            87268 bytes TIMEOUT QUEUE POOL
                           179300 bytes TRANSLATION POOL
                           176324 bytes UNIT OF WORK POOL
                           391268 bytes WORK QUEUE POOL
ETBM0582 Function completed
```

DRES

Displays EntireX Broker's resource usage for conversations, message buffers, participants, services, the timeout queue, units of work, and the work queue. Resource usage provides the total number, the number of free elements, and the number of used elements.

Sample Output

ETBM0720	Operator typed in: DRES				
ETBM0581	Broker resource usage:				
ETBM0581	Resource	Total #	Free #	Used #	
ETBM0581	Conversations	4096	852	3244	
ETBM0581	Long message buffers	0	0	0	
ETBM0581	Short message buffers	8192	7384	808	
ETBM0581	Participants	256	235	21	
ETBM0581	Services	256	240	16	
ETBM0581	Timeout Queue	1280	845	435	
ETBM0581	Units Of Work	0	0	0	
ETBM0581	Work Queue	256	239	17	
ETBM0582	Function completed				

DSTAT

Displays the total number of active elements, and an optional high watermark for services, clients, servers, conversations and message buffers.

Sample Output

```
ETBM0720 Operator typed in: DSTAT
ETBM0580 Broker statistics:
ETBM0580 NUM-SERVICE ..... 0
ETBM0580 Services active ...... 7
ETBM0580 NUM-CLIENT ..... 0
ETBM0580 Clients active ...... 10
ETBM0580 Clients active HWM ..... 10
ETBM0580 NUM-SERVER ..... 0
ETBM0580 Servers active ...... 10
ETBM0580 Servers active HWM ..... 10
ETBM0580 NUM-CONVERSATION ..... 0
ETBM0580 Conversations active ..... 607
ETBM0580 Conversations active HWM .. 968
ETBM0580 NUM-LONG-BUFFER ..... 0
ETBM0580 Long buffers active ..... 0
ETBM0580 Long buffers active HWM ... 0
ETBM0580 NUM-SHORT-BUFFER ..... 0
ETBM0580 Short buffers active ..... 1219
ETBM0580 Short buffers active HWM .. 1928
ETBM0582 Function completed
```

DWM

If broker attribute DYNAMIC-WORKER-MANAGEMENT=YES is activated, use command DWM=OFF to switch off dynamic worker management, or DWM=ON to reactivate it.

Example

- > To deactivate dynamic worker management
- Enter command:

/F taskname, DWM=OFF

See Dynamic Worker Management.

ETBEND

Processing stops immediately. Current calls to the EntireX Broker are not allowed to finish.

ETBSTOP

Alias of ETBEND.

FLUSH

Flush all trace data kept in internal trace buffers to stderr (DD: SYSOUT). The broker-specific attribute TRMODE=WRAP is required.

PSTORE TRACE

Modifies the trace level for the Adabas persistent store (Adabas-specific attribute TRACE-LEVEL).

Example

- > To set a trace level 2 for the Adabas persistent store
- Enter command:

```
/F taskname, PSTORE TRACE=2
```

See TRACE-LEVEL under Adabas-specific Broker Attributes.

SHUTDOWN class, server, service

Shuts down the specified service immediately and stops all servers that have registered this service.

Example

- ➤ To shut down service CLASS=RPC, SERVER=SRV1, SERVICE=CALLNAT
- Enter command:

```
/F taskname, SHUTDOWN RPC, SRV1, CALLNAT
```

TRACE

Modifies the setting of the broker-specific attribute TRACE-LEVEL.

Sample Commands

- > To modify the trace level
- Enter command, for example:

```
/F taskname,TRACE=0
/F taskname,TRACE=1
/F taskname,TRACE=4
```

See TRACE-LEVEL under Broker-specific Broker Attributes.

TRAP-ERROR

Modifies the setting of the broker-specific attribute TRAP-ERROR.

Sample Command

- > To modify the setting for TRAP-ERROR
- Enter command:

/F taskname,TRAP-ERROR=nnnn

where *nnnn* is the four-digit API error number that triggers the trace handler.

See TRAP-ERROR under Broker-specific Broker Attributes.

Participant-specific Commands

Within EntireX Broker nomenclature, a participant is an application implicitly or explicitly logged on to the Broker as a specific user. See *Implicit Logon* and *Explicit Logon*. A participant could act as client or server. The following participant-specific commands are available:

- CANCEL parameter
- FREEZE
- RUN
- USERLIST
- USERS parameter

CANCEL parameter

Operator command CANCEL is used to delete participants from EntireX Broker. The following parameters are supported:

Parameter	Description
	Cancel all participants with the specified $user_id$. Non-persistent resources will be freed by the timeout manager. Prefix "USER=" is the default value and may be omitted.
·	Cancel the participant with the sequence number <code>seqno</code> . Non-persistent resources will be freed by the timeout manager. Operator commands <code>USERLIST</code> and <code>USERS</code> display sequence numbers of all selected participants.

Sample Commands

- > To cancel all participant entries of user "DOE"
- Enter command:

/F taskname, CANCEL DOE

Or:

/F taskname, CANCEL USER=DOE

- > To cancel participant with sequence number "11"
- Enter command:

/F taskname, CANCEL SEQNO=11

FREEZE

Operator command FREEZE freezes user request processing in Broker.

Sample Command

- > To freeze user request processing in Broker
- Enter command:

```
/F taskname, FREEZE
```

RUN

Operator command RUN resumes user request processing in Broker.

Sample Command

- > To resume user request processing in Broker
- Enter command:

```
/F taskname, RUN
```

USERLIST

Operator command USERLIST displays a list of selected participant entries. The following parameters are supported:

Param	eter	Description	
none * Display all participants.		Display all participants.	
user_	_id	Display all participants with user ID <i>user_id</i> . Wildcard characters are supported.	

Sample Commands

- > To display all participants
- Enter command:

```
/F taskname, USERLIST
Or:
/F taskname, USERLIST *
```

- > To display all participants with user ID "DOE"
- Enter command:

```
/F taskname,USERLIST DOE
```

This produces the following output. See *Description of USERLIST Output Columns* below.

- To display all participants with user ID starting with uppercase "D"
- Enter command:

```
/F taskname, USERLIST D*
```

This produces the following output. See *Description of USERLIST Output Columns* below.

- To display all participants with 4-character user ID, starting with uppercase "D" and with uppercase "E" as third character
- Enter command:

```
/F taskname, USERLIST D?E?
```

This produces the following output. See *Description of USERLIST Output Columns* below.

Description of USERLIST Output Columns

Keyword	d Description	
USER-ID	User ID (32 bytes, case-sensitive). See USER-ID under Broker ACI Fields.	
С	Client.	
	Y Participant is a client, otherwise "N".	
S	Server.	
	Y Participant is a server, otherwise "N".	
E	Big endian.	
	Y Participant is on a big-endian machine.	
	N Participant is on a little-endian machine.	
CHR	Character set.	
	ASC Participant is an ASCII user.	
	EBC Participant is an EBCDIC user.	
SEQNO	Sequence number of participant. Can be used for operator command CANCEL parameter	

USERS parameter

Operator command USERS displays selected user data of participant entries. The following parameters are supported:

	Parameter	Pr Description Description	
none * Display all participants.		Display all participants.	
	user_id	Display all participants with user ID $user_id$. Wildcard characters are supported.	

Sample Commands

> To display all participants

■ Enter command:

```
/F taskname, USERS
Or:
/F taskname, USERS *
```

To display all participants with user ID "DOE"

■ Enter command:

```
/F taskname, USERS DOE
```

This produces the following output. See *Description of USERS Output Columns* below.

```
ETBM0720 Operator typed in: USERS DOE
ETBM0687 Participants:
ETBM0687 USER-ID: DOE
ETBM0687 CLIENT: N SERVER:
ETBM0687 SEQNO: 6 BIG ENDIAN: Y CHARSET: ASCII PUID:
ETBM0687 202073756E6578322D2D30303030324646462D2D303030303030303031
ETBM0687 TOKEN:
ETBM0582 Function completed
```

Description of USERS Output Columns

Keyword	Description	
USER-ID	User ID (32 bytes, case-sensitive). See USER-ID under Broker ACI Fields.	
CLIENT		
	Y Participant is a client, otherwise "N".	
SERVER		
	Y Participant is a server, otherwise "N".	
BIG ENDIAN		
	Y Participant is on a big-endian machine.	

Keyword	Description	
	N Participant is on a little-endian machine.	
CHARSET		
	ASC Participant is an ASCII user.	
	EBC Participant is an EBCDIC user.	
PUID	Internal unique ID of participant. Hexadecimal 28-byte value in printable format.	
TOKEN	Optionally identifies the participant. See TOKEN under <i>Broker ACI Fields</i> .	

Security-specific Commands

DSECSTAT

Displays the number of successful and failed Security authentications and Security authorizations.

Sample Output

```
ETBM0720 Operator typed in: DSECSTAT
ETBM0579 Security Authentications - successful: 20 failed: 0
ETBM0579 Security Authorizations - successful: 0 failed: 0
```

RESET userid

Resets the Security context for the specified user ID.

Sample Output

```
ETBM0720 Operator typed in: RESET EXXBATCH
ETBM0578 Reset ACEE for SAF-ID EXXBATCH : 20 instances found
```

SECURITY TRACE

Modifies the trace level for the EntireX Security (security-specific attribute TRACE-LEVEL). Broker-specific attribute SECURITY=YES must be set.

Example

- To set a trace level 2 for EntireX Security
- Enter command:

```
/F taskname, SECURITY TRACE=2
```

See TRACE-LEVEL under Security-specific Broker Attributes.

Transport-specific Commands

Transport-specific commands are available for Adabas/Entire Net-Work communicators, SSL communicators and TCP communicators; the COM command can be used for all communicators. The following command syntax applies:

$$\text{/F } \textit{task_name}, \left\{ \begin{array}{l} \text{COM} \\ \text{NET} \\ \text{SSL} \\ \text{Snn} \\ \text{TCP} \\ \text{Tnn} \end{array} \right\} \left\{ \begin{array}{l} \text{STATUS} \\ \text{SUSPEND} \\ \text{RESUME} \\ \text{STOP} \\ \text{START} \\ \text{TRACE=\{0-8\}} \end{array} \right\}$$

COM parameter

This command is executed by all configured transport communicators. The following parameters are supported:

Parameter	Description	
STATUS	Displays the current status of the transport communicator.	
SUSPEND	Used to suspend the transport communicator. The transport communicator is halted but will not shut down. User requests receive response code 148.	
RESUME	Resume a suspended transport communicator. If the communicator was not suspended before, an error message will be displayed.	
STOP	Stop an active or suspended transport communicator. The transport communicator will shut down. All transport-specific resources will be freed. User requests receive response code 148.	
START	Start a transport communicator that was previously stopped. If the communicator was not stopped before, an error message will be displayed.	
TRACE Sets the trace level for the transport method. If the global trace level (see TRACE) command /F taskname, TRACE=n this applies to all transport methods. This command will also override any exist transport-specific settings. If you subsequently enter command /F taskname, TCP TRACE=n only the trace level for TCP/IP transport is modified.		
	Note: With commands TCP Tnn, and SSL and Snn, the trace level is set for <i>all</i> TCP and SSL communicators respectively. Setting a trace level for a single TCP or SSL instance is not supported. For example: although it is possible to submit the command /F taskname, T01 TRACE=1 this command sets the trace level for all TCP communicators.	

Sample Output

```
ETBM0720 Operator typed in: COM STATUS

ETBW0718 TCP Communicator 0 currently active

ETBW0718 SSL Communicator 1 currently suspended

ETBW0718 NET Communicator 0 currently suspended

XC00039I 00113 Total number of commands = 17

XC00057I 00113 Operator entry active

ETBM0720 Operator typed in: COM SUSPEND

ETBM0721 TCP Communicator 0 suspended

ETBM0721 TCP Communicator 1 suspended

ETBM0721 SSL Communicator 0 suspended

ETBM0721 NET Communicator 0 suspended
```

NET parameter

This command is executed by X-COM, the Adabas/Entire Net-Work communicator. See command COM above for a list of supported parameters.

Sample Output

```
ETBM0720 Operator typed in: NET STATUS
ETBW0718 NET Communicator 0 currently active
XC00039I 00113 Total number of commands = 17
XC00057I 00113 Operator entry active
```

SSL parameter

This command is executed by all SSL communicators. See command COM above for a list of supported parameters.

Sample Output

```
ETBM0720 Operator typed in: SSL STATUS
ETBW0718 SSL Communicator O currently active
```

To manipulate a specific communicator instance (max. five instances can be started), use the command \$00, \$01, \$02, \$03 or \$04 for the respective SSL instance.

TCP parameter

This command is executed by TCP communicators. See command COM above for a list of supported parameters.

Sample Output

```
ETBM0720 Operator typed in: TCP STATUS
ETBW0718 TCP Communicator 0 currently active
ETBW0718 TCP Communicator 1 currently active
```

```
ETBM0720 Operator typed in: TCP RESUME
ETBM0721 TCP Communicator 0 resumed
ETBM0721 TCP Communicator 1 resumed
```

To manipulate a specific communicator instance (max. five instances can be started), use the command T00, T01, T02, T03 or T04 for the respective TCP instance.

Sample Output

```
ETBM0720 Operator typed in: T00 STATUS
ETBW0718 TCP Communicator O currently active
```

```
ETBM0720 Operator typed in: T01 STATUS
ETBW0718 TCP Communicator 1 currently active
```

Sample Transport Commands

- > To display status of all transport communicators
- Enter command:

```
/F taskname, COM STATUS
```

- To suspend first TCP communicator
- Enter command:

```
/F taskname,T00 SUSPEND
```

- > To stop all SSL transport communicators
- Enter command:

/F taskname, SSL STOP

XCOM-specific Commands



Note: All operator commands beginning with "X" belong to X-COM, the Adabas/Entire Net-Work communicator. The following commands operate only on the Adabas transport mechanism: XCQES, XHALT, XPARM, XSTART, XSTAT and XUSER. These commands have no effect on functions not related to the Adabas transport mechanism.

XEND and XSTOP function independently of the transport mechanism. (They stop the Broker's processing immediately, whereby existing calls to the EntireX Broker are not allowed to finish.)

XABS

Displays the total size, the number of bytes in use, the number of free bytes and the largest free windows in the Adabas attached buffer pool on the console.



Note: This command operates on the Adabas transport mechanism only. It has no effect on functions not related to the Adabas transport mechanism.

Sample Output

```
ETBM0720 Operator typed in: XABS

XC00090I 10113 Attached buffer usage

XC00090I 10113 38912000 bytes total = 9500 NABS

XC00090I 10113 0 bytes used

XC00090I 10113 0 bytes used HWM

XC00090I 10113 38912000 bytes free

XC00090I 10113 38912000 bytes current largest free windows

XC00090I 10113 38912000 bytes minimum of all largest free windows
```

XCQES

Displays the current number, and the highest number, of Adabas command queue elements to the console.



Note: This command operates on the Adabas transport mechanism only. It has no effect on functions not related to the Adabas transport mechanism.

Sample Output

```
ETBM0720 Operator typed in: XCQES
XC00030I 00113 Number of active CQEs = 0
XC00031I 00113 Highest number of active CQEs = 1
```

XEND

Alias of ETBEND.

XHALT

New calls to the EntireX Broker are temporarily rejected. Processing is resumed by issuing the XSTART operator command. XHALT is an alias for command NET SUSPEND.



Note: This command operates on the Adabas transport mechanism only. It has no effect on functions not related to the Adabas transport mechanism.

Sample Output

```
ETBM0720 Operator typed in: XHALT
ETBM0721 NET Communicator O suspended
```

XPARM

Displays the values of Adabas SVC, database ID, number of CQEs, number of attached buffers, and the application name for the Adabas transport to the console.



Note: This command operates on the Adabas transport mechanism only. It has no effect on functions not related to the Adabas transport mechanism.

Sample Output

```
ETBM0720 Operator typed in: XPARM

XC00032I 00113 Parameters for this session:

XC00033I 00113 SVC = 249

XC00034I 00113 NODE = 00113

XC00035I 00113 NCQE = 00100

XC00036I 00113 NABS = 10000

XC00037I 00113 User application = ETBNUC
```

XSTART

Processing of new calls to the EntireX Broker, interrupted with the XHALT command, is resumed. XSTART is an alias of command NET RESUME.



Note: This command operates on the Adabas transport mechanism only. It has no effect on functions not related to the Adabas transport mechanism.

Sample Output

```
ETBM0720 Operator typed in: XSTART
ETBM0721 NET Communicator O resumed
```

XSTAT

Displays the EntireX Broker statistics as console messages.



Note: This command operates on the Adabas transport mechanism only. It has no effect on functions not related to the Adabas transport mechanism.

XSTOP

Alias of ETBEND.

XUSER

Displays the current number, as well as the highest number, of users actively issuing commands using the Adabas transport mechanism to the console.



Note: The number of users displayed with this operator command will not represent all of the Broker clients and servers but only the subset of users issuing commands using the Adabas transport mechanism. Command and Information Services provides comprehensive information about all Broker clients and servers.

Application Monitoring-specific Commands

This section covers the following topics:

- APPMON=NO|YES
- COLLECTOR=host:port
- DISPLAY APPMON

APPMON=NO|YES

Use APPMON=NO to turn off the Application Monitoring feature in Broker. In addition to changing the current status, APPLICATION-MONITORING=NO is written to the Broker attribute file.

Use APPMON=YES to turn on the Application Monitoring feature in Broker. In addition to changing the current status, APPLICATION-MONITORING=YES is written to the Broker attribute file.

COLLECTOR=host:port

Use COLLECTOR=host:port to set the collector broker ID in Broker. COLLECTOR-BROKER-ID=value is written to the Broker attribute file. If the APPLICATION-MONITORING section is not already defined in the attribute file, the section is added, that is, a line containing DEFAULTS = APPLICATION-MONITORING followed by attribute COLLECTOR-BROKER-ID=value.

DISPLAY APPMON

Use DISPLAY APPMON to show the current settings of Application Monitoring. Sample output:

ETBM0720 Operator typed in: DISPLAY APPMON ETBM0793 APPLICATION-MONITORING=YES ETBM0793 COLLECTOR-BROKER-ID=SUSEXX04C:3930

10 Tracing EntireX Broker

Switching on Tracing	194
Switching off Tracing	194
Deferred Tracing	194
Dynamically Switching On or Off the EntireX Broker Trace	195

See also *Tracing for Broker Stubs*.

Switching on Tracing

> To switch on tracing

- Set the attribute TRACE-LEVEL in the broker attribute file
 - for minimal trace output to "1"
 - for detailed trace output to "2"
 - for full trace output to "3"

Example:

TRACE-LEVEL=2

See also EntireX Broker Return Codes.

Switching off Tracing

> To switch off tracing

■ Set the attribute TRACE-LEVEL in the broker attribute file to 0:

TRACE-LEVEL=0

Or:

Omit the TRACE-LEVEL attribute.

Deferred Tracing

It is not always convenient to run with TRACE-LEVEL defined, especially when higher trace levels are involved. Deferred tracing is triggered when a specific condition occurs, such as an ACI response code or a broker subtask abend. Such conditions cause the contents of the trace buffer to be written, showing trace information leading up the specified event. If the specified event does not occur, the Broker trace will contain only startup and shutdown information (equivalent to TRACE-LEVEL=0).

Operating the trace in this mode requires the following additional attributes in the broker section of the attribute file. Values for TRBUFNUM and TRAP-ERROR are only examples.

Attribute	Value	Description	
TRBUFNUM	3	Specifies the deferred trace buffer size = 3 * 64 K.	
TRMODE	WRAP	Indicates trace is not written until an event occurs.	
TRAP-ERROR 322 Assigns the event ACI response code 00780322 "PSI: UPDA		Assigns the event ACI response code 00780322 "PSI: UPDATE failed".	

Dynamically Switching On or Off the EntireX Broker Trace

The following methods are available to switch on or off the EntireX Broker trace dynamically. You do not need to restart the broker for the changes to take effect.

■ ETBCMD

Run command utility ETBCMD with option - c TRACE-ON or - c TRACE-OFF. See ETBCMD.

Operator Command Issue an operator command. See TRACE.

See also Deferred Tracing.

11 Broker Shutdown Statistics

Shutdown Statistics Output	1	9	8
Table of Shutdown Statistics	1	Ĉ	18

Shutdown Statistics Output

After a successful Broker execution, shutdown statistics and related information are produced. This output is written in the following sequence:

- 1. The diagnostic message ETBD0444 is written into the Broker trace log.
- 2. The output i.e. statistics, internals and user-specified parameters is written into the end of the Broker trace log file at shutdown.

Table of Shutdown Statistics

See *Legend* below for explanation of output type.

Output Type	Display Field	Description
U	Broker ID	Identifies the Broker kernel to which the attribute file applies. See BROKER-ID.
I	Version	The version of the Broker kernel currently running.
I	Generated platform family	The platform family for which this Broker kernel was built.
I	Runtime platform	The platform on which this Broker kernel is currently running.
I	Start time	The date and time when this Broker kernel started.
S	Restart count	The restart count indicates how many times the Broker kernel has been started with the persistent store. Therefore, after a cold start (PSTORE=COLD), the restart count will be 1. Then, after subsequent hot starts (PSTORE=HOT), the restart count will be 2 or greater.
U	Trace level	The value for the trace setting for this Broker kernel. See TRACE-LEVEL.
U	Worker tasks	The number of worker tasks for this Broker kernel. See NUM-WORKER.
U	MAX-MEMORY	The value of MAX-MEMORY or 0 if not defined. See MAX-MEMORY.
S	Memory allocated	Size of the allocated memory, in bytes.
S	Memory allocated HWM	Highest size of allocated memory in bytes since Broker started.
U	NUM-SERVICE	Value of NUM-SERVICE or 0 if not defined. See NUM-SERVICE.
S	Services active	The number of services currently active for this Broker kernel.
U	NUM-CLIENT	Value of NUM-CLIENT or 0 if not defined. See NUM-CLIENT.
S	Clients active	The number of clients currently active for this Broker kernel.
S	Clients active HWM	The high watermark for the number of clients active for this Broker kernel.

Output Type	Display Field	Description
U	NUM-SERVER	Value of NUM-SERVER or 0 if not defined. See NUM-SERVER.
S	Servers active	The number of servers currently active for this Broker kernel.
S	Servers active HWM	The high watermark for the number of servers active for this Broker kernel.
U	NUM-CONVERSATION	Value of NUM-CONVERSATION or 0 if not defined. See NUM-CONVERSATION.
S	Conversations active	The number of conversations currently active for this Broker kernel.
S	Conversations active HWM	The high watermark for the number of conversations active for this Broker kernel.
U	NUM-LONG-BUFFER	Value of NUM-LONG-BUFFER or 0 if not defined. See NUM-LONG-BUFFER.
S	Long buffers active	The number of long message buffers currently in use for this Broker kernel.
S	Long buffers active HWM	The high watermark for the number of long message buffers used for this Broker kernel.
U	NUM-SHORT-BUFFER	Value of NUM-SHORT-BUFFER or 0 if not defined. See NUM-SHORT-BUFFER.
S	Short buffers active	The number of short message buffers currently in use for this Broker kernel.
S	Short buffers active HWM	The high watermark for the number of short message buffers used for this Broker kernel.
U	Persistent store type	The type of persistent store used by this Broker kernel. See PSTORE-TYPE.
U	UOW persistence	Indicates whether units of work are persistent or not in this Broker kernel. See STORE.
U	Persistent store startup	Indicates the status of the persistent store at Broker startup. See PSTORE.
U	Persistent status lifetime	The multiplier to compute the lifetime of the persistent status. See ${\tt UWSTATP}.$
U	Deferred UOWs allowed	Indicates whether or not deferred units of work are allowed. See DEFERRED.
U	Maximum allowed UOWs	The maximum number of units of work that can be active concurrently for this Broker kernel. See MAX-UOWS.
U	Maximum messages per UOW	The maximum number of messages allowed in a unit of work. See MAX-MESSAGES-IN-UOW.
U	UOW lifetime in seconds	Indicates the default lifetime for a unit of work. See UOW-DATA-LIFETIME.
U	Maximum message length	Indicates the maximum message size that can be sent. See MAX-UOW-MESSAGE-LENGTH.

Output Type	Display Field	Description			
U	New UOW messages allowed	Indicates whether or not new units of work are allowed in this Broker kernel. See NEW-UOW-MESSAGES.			
S	UOWs active	The number of units of work currently active in this Broker kernel.			
S	Current UOW	The number of the last unit of work in this Broker kernel.			
U	Accounting	Indicates the status of accounting records in this Broker kernel. See ACCOUNTING.			
U	SSL port *	If applicable, the SSL port number on which this Broker kernel will listen for connection requests. See SSL-specific attribute POR			
U	TCP port *	If applicable, the TCP port number on which this Broker kernel will listen for connection requests. See TCP-specific attribute PORT.			
I	Number of function calls	Marks the beginning of the section of summary statistics for all the function calls.			
S	DEREGISTER	The number of Broker DEREGISTER function calls since startup.			
S	EOC	The number of Broker EOC function calls since startup.			
S	KERNELVERS	The number of Broker KERNELVERS function calls since startup.			
S	LOGOFF	The number of Broker LOGOFF function calls since startup.			
S	LOGON	The number of Broker LOGON function calls since startup.			
S	RECEIVE	The number of Broker RECEIVE function calls since startup.			
S	REGISTER	The number of Broker REGISTER function calls since startup.			
S	SEND	The number of Broker SEND function calls since startup.			
S	SYNCPOINT	The number of Broker SYNCPOINT function calls since startup.			
S	UNDO	The number of Broker UNDO function calls since startup.			
S	REPLY_ERROR	The number of Broker REPLY_ERROR function calls since startup.			
I	Worker task statistics	Marks the beginning of the section of summary statistics for all the worker tasks.			
I	Worker number	The identifier of the worker task.			
I	Status	The status of the worker task at shutdown.			
S	# of calls	The number of Broker calls handled by the worker task since startup.			
S	Idle time in seconds	The number of seconds the worker task has been idle since startup.			

^{*} Does not apply to z/OS.

Legend

Output Type	Description	Value	Origin of Value
I	Internal Information	Static	Determined by Software AG EntireX.
S	Shutdown Statistic	Variable	Determined by Broker activity during execution.
U	User-Specified Parameter	Variable	Specified by Broker administrator before or, if allowable, during execution.

12 Command Logging in EntireX

Introduction to Command Logging	204
Command Log Filtering using Command-line Interface ETBCMD	
ACI-driven Command Logging	
Dual Command Log Files	

Command logging is a feature to assist in debugging Broker ACI applications. A command in this context represents one user request sent to the Broker and the related response of Broker.

Command logging is a feature that writes the user requests and responses to file in a way it is already known with Broker trace and TRACE-LEVEL=1. But command logging works completely independent from trace, and data is written to a file only if defined command trace filters detect a match.

Broker stub applications send commands or requests to the Broker kernel, and the Broker kernel returns a response to the requesting application. Developers who need to resolve problems in an application need access to those request and response strings inside the Broker kernel. That's where command logging comes in. With command logging, request and response strings from or to an application are written to a file that is separate from the Broker trace file. Command logging works based on defined filters. Nothing is logged if there are no filters. If filters are defined and if there is a match, this user request is logged.



Note: All applied filters are lost after Broker restart and have to be applied again.

Introduction to Command Logging

This section provides an introduction to command logging in EntireX and offers examples of how command logging is implemented. It covers the following topics:

- Overview
- Command Log Files
- Defining Filters
- Programmatically Turning on Command Logging

Overview

Command logging is similar to a Broker trace that is generated when the Broker attribute TRACE-LEVEL is set to 1. Broker trace and command logging are independent of each other, and therefore the configuration of command logging is separate from Broker tracing.

The following Broker attributes are involved in command logging:

Attribute	Description
CMDLOG	Set this to "N" if command logging is not needed.
CMDLOG-FILE-SIZE	A numeric value indicating the maximum size of command log file in KB.
NUM-CMDLOG-FILTER	The maximum number of filters that can be set.

In addition to CMDLOG=YES, the Broker needs the assignment of the dual command logging files during startup. If these assignments are missing, Broker will set CMDLOG=NO. See also *Broker Attributes*.

Command Log Files

The Broker keeps a record of commands (request and response strings) in a command log file.

At Broker startup, you will need to supply two command log file names and paths. Only one file is open at a time, however, and the Broker writes commands (requests and responses) to this file.

Under z/OS, the file requirements are two equally sized, physical sequential files defined with a record length of 121 bytes, i.e.

DCB=(LRECL=121, RECFM=FB, BLKSIZE=nnnn). We recommend you allocate files with a single (primary) extent only. For example SPACE=(CYL, (30,0)). The minimum file size is approximately 3 cylinders of 3390 device. Alternatively, the dual command log files can be allowed in USS HFS file system.

- If the value of CMDLOG-FILE-SIZE is lower than the capacity of the CMDLOG data set, CMDLOG-FILE-SIZE is used.
- If the value of CMDLOG-FILE-SIZE is greater than the capacity of the CMDLOG data set, CMDLOG-FILE-SIZE is adjusted to the capacity of the data set.
- If no CMDLOG-FILE-SIZE was defined, it is set to the capacity of the CMDLOG data set.

When the size of the active command log file reaches the KB limit set by CMDLOG-FILE-SIZE, the file is closed and the second file is opened and becomes active. When the second file also reaches the KB limit set by CMDLOG-FILE-SIZE, the first file is opened and second file is closed. Existing log data in a newly opened file will be lost.

Defining Filters

In command logging, a filter is used to store and identify a class, server, or service, as well as a user ID.

Use the command-line tool etbcmd to define a filter. During processing, the Broker evaluates the class, server, service, and user ID associated with each incoming request and compares them with the same parameters specified in the filters. If there is a match, the request string and response string of the request is printed out to the command log file.

Programmatically Turning on Command Logging

Applications using ACI version 9 or above have access to the new field LOG-COMMAND in the ACI control block.

If this field is set, the accompanying request and the Broker's response to this request is logged to the command log file.

Note: Programmatic command logging ignores any filters set in the kernel.

Command Log Filtering using Command-line Interface ETBCMD

The examples assume that Broker has been started with the attribute CMDLOG=Y.

- Setting Filters
- Deleting Filters
- Disabling and Enabling a Filter

Setting Filters

Filters need to be set before running the stub applications whose commands are to be logged. Filter for class, server, service may contain fully qualified names (ACLASS/ASERVER/ASERVICE) or asterisk for any (e.g. ACLASS/*/ASERVICE). Partially qualified filter names (ACLA*/ASERVER/ASERV*) are not supported.

Command	Description
<pre>//ETBCMD EXEC PGM=ETBCMD, // PARM=('/-blocalhost:1970:TCP ↔ -cSET-CMDLOG-FILTER -xuser ', // '-dBROKER ↔ -nACLASS/ASERVER/ASERVICE')</pre>	This command sets filters on ACLASS/ASERVER/ASERVICE. All ACI calls issued by <i>all</i> users to this service will be logged.
<pre>//ETBCMD EXEC PGM=ETBCMD, // PARM=('/-blocalhost:1970:TCP ↔ -cSET-CMDLOG-FILTER -xuser ', // '-dBROKER -nACLASS/ASERVER/ASERVICE ↔ -Usaguser1')</pre>	This command sets filters on ACLASS/ASERVER/ASERVICE and user ID saguser1. All ACI calls to this service as well as those issued by saguser1 will be logged.



Note: If more than one service is set as a filter, all ACI calls sent to any of these services will be logged. Identical filters cannot be set. Attempts to set a second filter that matches an existing filter will be rejected. Similarly, the maximum number of filters that can be added is defined in NUM-CMDLOG-FILTER. If the maximum number of filters is already being used, delete an existing filter to make room for a new filter.

Deleting Filters

The following provides an example of how to delete an existing filter on a service.

> To delete a filter

■ Enter the following command.

```
//ETBCMD EXEC PGM=ETBCMD,
// PARM=('/-blocalhost:1970:TCP -cCLEAR-CMDLOG-FILTER -xuser ',
// '-dBROKER -nACLASS/ASERVER/ASERVICE')
```

If the filter does not exist, the command will return an error.

Disabling and Enabling a Filter

Filters can be set and still be disabled (made inactive).

> To disable a filter

■ Enter the following command.

```
//ETBCMD EXEC PGM=ETBCMD,
// PARM=('/-blocalhost:1970:TCP -cDISABLE-CMDLOG-FILTER -xuser ',
// '-dBROKER -nACLASS/ASERVER/ASERVICE -Usaguser1')
```

Note: A disabled filter will not bring down the count of filters in use.

> To enable a filter

■ Enter the following command to enable the disabled filter.

```
//ETBCMD EXEC PGM=ETBCMD,
// PARM=('/-blocalhost:1970:TCP -cENABLE-CMDLOG-FILTER -xuser ',
// '-dBROKER -nACLASS/ASERVER/ASERVICE -Usaguser1')
```

ACI-driven Command Logging

EntireX components that communicate with Broker can trigger command logging by setting the field LOG-COMMAND in the ACI control block.

When handling ACI functions with command log turned on, Broker will not evaluate any filters. Application developers must remember to reset the LOG-COMMAND field if subsequent requests are not required to be logged.

Dual Command Log Files

Broker's use of two command log files prevents any one command log file from becoming too large.

When starting a Broker with command log support, you must therefore specify two data sets and DD names - one for each of the two command log files. The sample started task EXBSTART delivered with the EXX108.JOBS data set uses DDCLOGR1 and DDCLOGR2 as default command log file names.

At startup, Broker initializes both files and keeps one of them open. Command log statements are printed to the open file until the size of this file reaches the value specified in the Broker attribute CMDLOG-FILE-SIZE. This value must be specified in KB.

When the size of the open file exceeds the value specified in the Broker attribute CMDLOG-FILE-SIZE, Broker closes this file and opens the other, dormant file. Because the Broker closes a log file only when unable to print out a complete log line, the size of a *full* file may be smaller than CMDLOG-FILE-SIZE.

To switch log files on demand, using ETBCMD

■ An open command log file can be forcibly closed even before the size limit is reached. Enter the following command.

```
//ETBCMD EXEC PGM=ETBCMD,
// PARM=('/-blocalhost:1970:TCP -cSWITCH-CMDLOG -xuser ',
// '-dBROKER')
```

The command above will close the currently open file and open the one that has been dormant.

Accounting in EntireX Broker

EntireX Accounting Data Fields	21	(
Using Accounting under z/OS		
Example Uses of Accounting Data		

This chapter describes the accounting records for Broker that can be used for several purposes, including:

application chargeback

for apportioning EntireX resource consumption on the conversation and/or the application level;

performance measurement

for analyzing application throughput (bytes, messages, etc.) to determine overall performance;

■ trend analysis

for using data to determine periods of heavy and/or light resource and/or application usage.

EntireX Accounting Data Fields

In the EntireX Accounting record, there are various types of data available for consumption by applications that process the accounting data:

Field Name	Accounting Version	Type of Field	Description	
SMF Record Type	1	1-byte unsigned integer	Type of SMF record.	
Record Write Time	1	I4I4 timestamp	SMF timestamp in format I4I4 (time in hundredths of seconds followed by date in format X'0CYYDDDF' (packed decimal number)).	
SMF system ID	1	4-byte string	ID of the SMF system.	
SMF subsystem ID	1	4-byte string	ID of the SMF subsystem.	
EntireX Broker ID	1	A32	Broker ID from attribute file.	
EntireX Version	1	A8	Version information, v.r.s.p where v =version r =release s =service pack p =patch level for example 10.8.0.00.	
Platform of Operation	1	A8	Platform where EntireX is running.	
EntireX Start Time	1	I4I4 timestamp	The time EntireX was initialized in format I4I4 (time in hundredths of seconds followed by dat in format X'0CYYDDDF' (packed decimal number)).	
Accounting Record Type	1	A1	It is always C for conversation. Future Types will have a different value in this field.	

Field Name	Accounting Version	Type of Field	Description
Client User ID	1	A32	USER-ID ACI field from the client in the conversation.
Client Token	1	A32	TOKEN field from the ACI from the client.
Client Physical ID	1	A56	The physical user ID of the client, set by EntireX.
Client Communication Type	1	I1	Communication used by client: 1 = Net-Work 2 = TCP/IP 3 = APPC 4 = IBM® MQ 5 = SSL
Client Requests Made	1	I4	Number of Requests made by client.
Client Sent Bytes	1	I4	Number of bytes sent by client.
Client Received Bytes	1	I4	Number of bytes received by client.
Client Sent Messages	1	I4	Number of messages sent by client.
Client Received Messages	1	I4	Number of messages received by client.
Client Sent UOWs	1	I4	Number of UOWs sent by client.
Client UOWs Received	1	I4	Number of UOWs received by client.
Client Completion Code	1	I4	Completion code client received when conversation ended.
Server User ID	1	A32	USER-ID ACI field from the server in the conversation.
Server Token	1	A32	TOKEN field from the ACI from the server.
Server Physical ID	1	A56	The physical user ID of the server, set by EntireX.
Server Communication Type			1 = Entire Net-Work 2 = TCP/IP 3 = APPC 4 = IBM® MQ
Server Requests Made	1	I4	Number of requests made by server.
Server Sent Bytes	1	I4	Number of bytes sent by server.
Server Received Bytes	1	I4	Number of bytes received by server.
Server Sent Messages	1	I4	Number of messages sent by server.
Server Received Messages	1	I4	Number of messages received by server.
Server Sent UOWs	1	I4	Number of UOWs sent by server.
Server Received UOWs	1	I4	Number of UOWs received by server.
Server Completion Code	1	I4	Completion code server received when conversation ended.

Field Name	Accounting Version	Type of Field	Description
Conversation ID	1	A16	CONV-ID from ACI.
Server Class	1	A32	SERVER-CLASS from ACI.
Server Name	1	A32	SERVER-NAME from ACI.
Service Name	1	A32	SERVICE from ACI.
CID=NONE Indicator	1	A1	Will be N if CONV-ID=NONE is indicated in application.
Restarted Indicator	1	A1	Will be R if a conversation was restarted after a Broker shutdown.
Conversation Start Time	1	I4I4 timestamp	The time the conversation began in format I4I4 (time in hundredths of seconds followed by date in format X'0CYYDDDF' (packed decimal number)).
Conversation End Time	1	I4I4 timestamp	The time the conversation was cleaned up in format I4I4 (time in hundredths of seconds followed by date in format X'0CYYDDDF' (packed decimal number)).
Conversation CPU Time	1	I4	Number of microseconds of CPU time used by the conversation
Client Security Identity	2	A32	Actual identity of client derived from authenticated user ID.
Client Application Node	2	A32	Node name of machine where client application executes.
Client Application Type	2	A8	Stub type used by client application.
Client Application Name	2	A64	Name of the executable that called the broker. Corresponds to the Broker Information Service field APPLICATION-NAME.
Client Credentials Type	2	I1	Mechanism by which authentication is performed for client.
Server Security Identity	2	A32	Actual identity of server derived from authenticated user ID.
Server Application Node	2	A32	Node name of machine where server application executes.
Server Application Type	2	A8	Stub type used by server application.
Server Application Name	2	A64	Name of the executable that called the broker. Corresponds to the Broker Information Service field APPLICATION-NAME.
Server Credentials Type	2	I1	Mechanism by which authentication is performed for server.
Client RPC Library	3	A128	RPC library referenced by client when sending the only/first request message of the conversation.

Field Name	Accounting Version	Type of Field	Description
Client RPC Program	3	A128	RPC Program referenced by client when sending the only/first request message of the conversation.
Server RPC Library	3	A128	RPC library referenced by server when sending the only/first response message of the conversation.
Server RPC Program	3	A128	RPC Program referenced by server when sending the only/first response message of the conversation.
Client IPv4 Address	4	A16	IPv4 address of the client.
Server IPv4 Address	4	A16	IPv4 address of the server.
Client Application Version	4	A16	Application version of the client.
Server Application Version	4	A16	Application version of the server.
Client IPv6 Address	5	A46	IPv6 address of the client.
Server IPv6 Address	5	A46	IPv6 address of the server.



Note: Accounting fields of any version greater than 1 are created only if the attribute AC-COUNTING-VERSION value is greater than or equal to the corresponding version. For example: accounting fields of version 2 are visible only if ACCOUNTING-VERSION=2 or higher is specified.

Using Accounting under z/OS

The ACCOUNTING attribute indicates if accounting records will be generated. Accounting records are written upon successful completion of a conversation. A conversation ending in an application error (such as a timeout) is considered to be a successful conversation.

- Attribute File
- Retrieving Accounting Records
- Accounting Record Layouts
- Notes

Attribute File

ACCOUNTING={NO | 128-255}

Set this parameter to "NO" (that is, do not create accounting records) or to a number between 128 and 255, which specifies the SMF record type to use when writing the accounting records. In order to avoid conflicts with other applications that also produce SMF records, check with your z/OS systems programmer for an appropriate number. In addition, check with your z/OS systems programmer to ensure that the selected SMF record number is set up to be written.

Default value: NO

Retrieving Accounting Records

The standard IBM IFASMFDP utility program may be used to selectively offload Broker SMF records. Analysis and report routines - either user-written or those available from IBM or various software vendors - may subsequently be used to process the offloaded records.

```
//* Copies selected records from the "live" SMF data sets
//*
//* Replace nnn (OUTDD parameter) with a valid SMF record type
//*
//* Note: the "DISPLAY SMF" operator command will show the names of the
//* SMF data sets
//*
//IFASMFDP EXEC PGM=IFASMFDP
//SYSPRINT DD SYSOUT=*
//MAN1 DD DISP=SHR, DSN=SYS1.MAN1
//MAN2 DD DISP=SHR, DSN=SYS1.MAN2
//MAN3 DD DISP=SHR, DSN=SYS1.MAN3
//OUTPUT DD DISP=(MOD, CATLG).
// UNIT=SYSDA, SPACE=(TRK, (15,15), RLSE),
// DCB=(RECFM=VBS, LRECL=32760, BLKSIZE=0),
// DSN=EXX.SMF.RECORDS
//SYSIN DD *
 DATE(2002001,2099366)
 START(0000)
 END(2359)
 INDD(MAN1,OPTIONS(DUMP))
 INDD(MAN2,OPTIONS(DUMP))
 INDD(MAN3,OPTIONS(DUMP))
 OUTDD(OUTPUT, TYPE(nnn))
```

Note: The IBM publication *MVS System Management Facilities (SMF)* provides complete information on SMF.

Accounting Record Layouts

EntireX provides three mappings for its accounting records in the following members, all located in the EXX108.SRCE data set:

- EXXCACT A C language include file that maps the accounting record;
- EXXACTR An Assembler language MACRO that will generate a DSECT of the accounting record;
- EXXSACT An SAS DATA step that will read in a file with the appropriate field names.

Notes

- Since there is no server for Broker Command and Information Services, no server data is generated in the SMF records for Command and Information Services conversations.
- The unit for CPUTIME is expressed in microseconds.

Example Uses of Accounting Data

- Chargeback
- Trend Analysis
- Tuning for Application Performance

Chargeback

Customers can use the EntireX accounting data to perform chargeback calculations for resource utilization in a data center. Suppose EntireX Broker is being used to dispatch messages for three business departments: Accounts Receivable, Accounts Payable, and Inventory. At the end of each month, the customer needs to determine how much of the operation and maintenance cost of EntireX Broker should be assigned to these departments. For a typical month, assume the following is true:

Department	Amount of Data	Percentage	Messages Sent	Percentage	Average Percentage
Accts Payable	50 MB	25	4000	20	22.5
Accts Receivable	40 MB	20	6000	30	25
Inventory	110 MB	55	10000	50	52.5

The use of Broker resources here is based upon both the amount of traffic sent to the Broker (bytes) as well as how often the Broker is called (messages). The average of the two percentages is used to internally bill the departments, so 52.5% of the cost of running EntireX Broker would be paid by the Inventory Department, 25% by the Accounts Receivable Department, and 22.5% by the Accounts Payable Department.

Trend Analysis

The Accounting Data can also be used for trend analysis. Suppose a customer has several point-of-sale systems in several stores throughout the United States that are tied into the corporate inventory database with EntireX. The stubs would be running at the stores, and the sales data would be transmitted to the Broker, which would hand it off to the appropriate departments in inventory. If these departments wish to ascertain when the stores are busiest, they can use the accounting data to monitor store transactions. Assume all of the stores are open every day from 9 AM to 10 PM.

Local Time	Average: Weekday Transactions per Store	Maximum Weekday Transactions in any Store	Average Weekend Transactions per Store	Maximum Weekend Transactions in any Store
9 AM	7.3	27	28.2	83
10 AM	11.2	31	29.3	102
11 AM	14.6	48	37.9	113
12 noon	56.2	106	34.8	98
1 PM	25.6	65	34.2	95
2 PM	17.2	52	38.5	102
3 PM	12.1	23	42.7	99
4 PM	18.3	34	43.2	88
5 PM	26.2	47	45.2	93
6 PM	38.2	87	40.6	105
7 PM	29.6	83	39.2	110
8 PM	18.6	78	28.6	85
9 PM	11.2	55	17.5	62

The owner of the stores can examine the data and make decisions based upon the data here. For example, on weekdays, he or she can see that there is little business until lunchtime, when the number of transactions increase. It then decreases during lunch hour; then there is another increase from 5 PM to 8 PM, after people leave work. Based on this data, the owner might investigate changing the store hours on weekdays to 10 AM to 9 PM. On the weekend the trends are different, and the store hours could be adjusted as well, although there is a more regular customer flow each hour on the weekends.

Tuning for Application Performance

Assume that a customer has two applications that perform basic request/response messaging for similar sized messages. The applications consist of many Windows PC clients and Natural RPC Servers on UNIX. An analysis of the accounting data shows the following:

Application Type	Class	Server			Average Client Messages Received per Conversation
Application 1:	CLASS1	SERVER1	SERVICE1	10.30	10.29
Application 2:	CLASS2	SERVER2	SERVICE2	10.30	8.98

A further analysis of the accounting data reveals that there are a lot of non-zero response codes in the records pertaining to Application 2, and that a lot of these non-zero responses indicate timeouts. With that information, the customer can address the problem by modifying the server code, or by adjusting the timeout parameters for SERVER2 so that it can have more time to get a response from the Service.