

## **webMethods Error Message Reference**

Version 10.1

October 2017

This document applies to webMethods Product Suite Version 10.1 and all subsequent releases.

Specifications contained herein are subject to change and these changes will be reported in subsequent release notes or new editions.

Copyright © 2017 Software AG, Darmstadt, Germany and/or Software AG USA, Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA, Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

Use of this software is subject to adherence to Software AG's licensing conditions and terms. These terms are part of the product documentation, located at <http://softwareag.com/licenses/> and/or in the root installation directory of the licensed product(s).

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third-Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

Use, reproduction, transfer, publication or disclosure is prohibited except as specifically provided for in your License Agreement with Software AG.

**Document ID: XSU-MESSAGES2-101-20171004**

## Table of Contents

1 ActiveTransfer Messages .....	1
2 Application Designer Messages .....	7
3 Application Development Plug-in Messages .....	9
4 Application Platform Server Messages .....	25
5 Business Rules Messages .....	47
6 CentraSite Messages .....	55
7 CloudStreams Messages .....	355
8 Command Central Messages .....	445
9 Common Monitoring Provider Messages .....	519
10 Database Component Configurator Messages .....	561
11 Deployer Messages .....	563
12 Designer Composite Application Framework .....	649
13 Digital Event Services .....	653
14 Event-Driven Architecture Tools Messages .....	673
15 Event Persistence Messages .....	701
16 Installer Messages .....	751
17 Integration Server Messages .....	755
18 Mediator Messages .....	1299
19 My webMethods Server Messages .....	1347
20 OSGi Messages .....	1505
21 Platform Manager Messages .....	1523
22 Presto Messages .....	1615
23 Process Engine Messages .....	1865
24 Realtime Monitoring Messages .....	1929
25 Security Messages .....	2077
26 Tamino Messages .....	2105
27 Trading Network Messages .....	2573
28 webMethods Social BPM Messages .....	2827
29 Web Services Stack Messages .....	2833
30 Universal Messaging Messages .....	2869



# 1 ActiveTransfer Messages

---

- 1003            **Error while initializing ActiveTransfer database connection. The original error message was: {0}**
- 2001            **Invalid or unsupported RDBMS vendor: {0}.**
- 2002            **The database connection pool associated with ActiveTransfer should allow at least 2 connections. Your ActiveTransfer pool is currently configured with a maximum of {0} connections. Aborting TN startup. Please increase your ActiveTransfer database pool maximum and restart the server.**
- 2003            **There was an error while reading the dbops.sql file. The original error message was: {0}**
- 2004            **There was an error while reading the dblimits.cnf file. The original error message was: {0}**
- 2005            **A connection was returned to the connection pool with autoCommit = false. This may indicate some changes to the database were not committed properly. The changes will be rolled back. Stack trace {0}**

- 2006            **ActiveTransfer database pool is not configured. Please configure a database pool for functional alias "ActiveTransfer".**
  
- 2007            **There was an error while connecting to ActiveTransfer connection pool. The original error message was: {0}**
  
- 2008            **ActiveTransfer database pool is not configured properly. Make sure that a valid database pool is assigned for functional alias "ActiveTransfer".**
  
- 2009            **Error while reading the database configuration. The exception message is : {0}**
  
- 2011            **ActiveTransfer could not retrieve data from your database. Go to the JDBC Pools page in the Integration Server Administrator and make sure your database URL, user name, and password are set correctly. Also make sure you created the ActiveTransfer database tables as described in the Product Installation Guide.**
  
- 3001            **A scheduled action with this name already exists.**
  
- 3004            **Unable to save scheduled archive service "{0}".**
  
- 3009            **Interval value for fixed interval scheduled event cannot be empty.**
  
- 3010            **Interval value is not valid.**
  
- 3011            **Interval must be greater than zero.**
  
- 3012            **The scheduled {0} is invalid. Format must be YYYY/MM/DD.**
  
- 3013            **The scheduled {0} is invalid. Format must be hh:mm:ss.**

3020	<b>The scheduled delivery date/time is in the past.</b>
3021	<b>If an end time is supplied, an end date must also be supplied.</b>
3022	<b>End date/time is in the past.</b>
3023	<b>End date/time is before start date/time.</b>
3024	<b>Could not construct a valid timestamp from this schedule. Dates must be in YYYY/MM/DD format and times must be in hh:mm:ss format.</b>
3025	<b>Delivery schedule dates must be in the format "YYYY/MM/DD" and times must be in the format "hh:mm:ss".</b>
3031	<b>A post process event with this name already exists.</b>
3032E	<b>The action name "{0}" repeats for multiple actions in this event. Retry with unique action names.</b>
<b>Explanation</b>	Each action defined in an ActiveTransfer event must have a unique name.
<b>Action</b>	Specify a unique name for each action in an ActiveTransfer event.
3033	<b>The action name cannot be null.</b>
3034E	<b>Scheduled event "{0}" does not exist. Retry with an existing scheduled event.</b>
<b>Explanation</b>	The scheduleName parameter provided for the wm.mft.schedule:executeEvent service is not a valid scheduled event in ActiveTransfer.
<b>Action</b>	Ensure that the scheduled event name specified by the scheduleName parameter is defined in ActiveTransfer.
4003E	<b>Update of asset failed.</b>
<b>Explanation</b>	ActiveTransfer Server could not update the asset.
<b>Action</b>	Check the ActiveTransfer error logs for details.

<b>4005E</b>	<b>Insertion of asset failed.</b>
<b>Explanation</b>	ActiveTransfer could not insert the asset on the target server.
<b>Action</b>	Check the ActiveTransfer error logs for details.
<b>4006E</b>	<b>The export file name cannot be null.</b>
<b>Explanation</b>	The exportData service could not execute because no export file was specified.
<b>Action</b>	In the exportFileName parameter, specify the path and name of the XML file in which to save the exported assets.
<b>4007E</b>	<b>The import file name cannot be null.</b>
<b>Explanation</b>	The importData service could not execute because no import file was specified.
<b>Action</b>	In the importDataFileName parameter, specify the path and name of the XML file containing the assets to import.
<b>4008E</b>	<b>The import file {0} does not exist.</b>
<b>Explanation</b>	The specified file containing the assets to import does not exist.
<b>Action</b>	In the importDataFileName parameter, specify a valid path and name of the XML file containing the assets to import.
<b>4009E</b>	<b>The import file {0} cannot be read.</b>
<b>Explanation</b>	ActiveTransfer Server could not read the specified import file.
<b>Action</b>	In the importDataFileName parameter, specify a file name that ActiveTransfer Server can access.
<b>4010E</b>	<b>Specify values for input parameter {0} or set input parameter all to true.</b>
<b>Explanation</b>	The "all" input parameter for the importData service is set to "false," but no assets are specified to import.
<b>Action</b>	Either set the "all" input parameter to "true" or specify the assets to import in the "importData" parameter.
<b>4011E</b>	<b>The value of input parameter assetType of {0}{{1}} is null. Specify a value for the asset type.</b>
<b>Explanation</b>	ActiveTransfer Server could not import the asset for the indicated importData document because no asset type was specified.
<b>Action</b>	Specify a value in the assetType variable for each asset type you want to import.

---

<b>4012E</b>	<b>No assets to import.</b>
<b>Explanation</b>	The export file is blank or the assets selected for import are not in the export file.
<b>4013E</b>	<b>The version information in the import file cannot be null.</b>
<b>Explanation</b>	The version information in the import file is null. ActiveTransfer supports import of assets into ActiveTransfer 9.5 or later. The server could not find version information in the file the importData service is attempting to import.
<b>4014E</b>	<b>The version information provided in the file for Import operation is {0}, only the data exported from version {1} can be imported.</b>
<b>Explanation</b>	ActiveTransfer supports the export of assets from version 9.5 or later. This export file was created from an earlier version of ActiveTransfer
<b>4015E</b>	<b>A reference is not available on the target server. Reference details- type:{0}, name:{1}, and ID:{2}.</b>
<b>Explanation</b>	A reference to a server instance is not available on the target server.
<b>4016</b>	<b>assetType element not found in XML.</b>
<b>7001</b>	<b>A server with the same protocol and 'host + port' combination already exists.</b>
<b>7002</b>	<b>A server tunnel with the same name already exists.</b>
<b>7003</b>	<b>Error while updating the server. Check the logs.</b>
<b>7004</b>	<b>A proxy instance with the same host and port combination already exists.</b>
<b>7005</b>	<b>A proxy instance with the same name already exists.</b>
<b>8001</b>	<b>An invalid template has been specified for the user. Template ID:{0}</b>

- 8002            **A user template with the same name already exists.**
  
- 8003            **A user with the specified id does not exist. User ID:{0}**
  
- 8004            **The user does not have an associated template. User ID:{0}**
  
- 8005            **The user "{0}" already exists.**
  
- 8006            **No default user template is defined in ActiveTransfer. Please create a default user template before creating a user.**
  
- 8007            **Default template cannot be deleted.**
  
- 8101            **A virtual folder with the same name already exists.**

## 2 Application Designer Messages

---

<b>INMBAE0001</b>	<b>Login failed. The reason could be an incorrect username and/or password, or a database access error.</b>
<b>Explanation</b>	The system could not log you on. An error occurred during authentication.
<b>Action</b>	Specify correct user name (possibly including domain name) and password. Note that letters in passwords must be typed using the correct case. You may also want to check whether the CentraSite server is started.
<b>INMBAE0002</b>	<b>Please enter an appropriate value.</b>
<b>Explanation</b>	Please enter an appropriate value.
<b>Action</b>	Please enter an appropriate value.
<b>INMBAE0003</b>	<b>Cannot uninstall plug-in with id {0}, is required e.g. by plug-in with id {1}.</b>
<b>Explanation</b>	The plug-in you wish to uninstall cannot be uninstalled because another plug-in depends on it.
<b>Action</b>	Check whether to uninstall the dependent plug-in as well.
<b>INMBAE0005</b>	<b>Failed to delete {0}.</b>
<b>Explanation</b>	The given file or directory could not be deleted.
<b>Action</b>	Check whether in use by another program.

<b>INMBAE0006</b>	<b>Unable to load JAAS Configuration. The jaas.config file may have syntax errors.</b>
<b>Explanation</b>	JAAS Configuration seems to be invalid and hence cannot be loaded. The jaas.config file may have syntax errors
<b>Action</b>	Ensure the syntax correctness of jaas.config file. Fix any additional issues as pointed out in the error message
<b>INMBAE0009</b>	<b>Subject does not supply credentials. The subject instance is {0}.</b>
<b>Explanation</b>	Authenticated subject does not have credentials after authentication.
<b>Action</b>	This is most probably due to a CentraSite security misconfiguration.
<b>INMBAE0010</b>	<b>Connection handler {0} failed to establish connection.</b>
<b>Explanation</b>	Connection handler {0} failed to establish connection.
<b>Action</b>	Check logs.
<b>INMBAE0011</b>	<b>Plug-in {0} has been disabled.</b>
<b>Explanation</b>	Plug-in {0} has been disabled.
<b>Action</b>	Check logs for reason.
<b>INMBAE0012</b>	<b>Database access error. Can't connect to server CentraSite.</b>
<b>Explanation</b>	CentraSite Server is not running.
<b>Action</b>	Start CentraSite Server.
<b>INMBAW0004</b>	<b>Forced uninstall of plug-in with id {0} will cause disabling of dependent plug-in with id {1}.</b>
<b>Explanation</b>	When the plug-in is uninstalled, the dependent plug-in will no longer be usable.
<b>Action</b>	The dependent plug-in will be re-enabled when the required plug-in is available again.

# 3 Application Development Plug-in Messages

---

**JmxServiceConnectError – Designer was unable to physically connect to the server over JMX on port {0}. Verify the Server view's JMX port configuration matches the port configuration for the server. Verify the server is started and listening for socket connections on this port.**

**Explanation** Application Platform uses a JMX service to communicate with a server at design time.  
**Action** Verify the Server view's JMX port configuration matches the port configuration for the server. Verify the server is started and listening for socket connections on this port.

**JmxServiceNoInstanceError – Designer is connected to the server over JMX as required; however, the App Platform remote service is unavailable. Verify the 'Application Platform Support' component is installed for this server.**

**Explanation** Application Platform is using a JMX service to communicate with the server on port {0}. It connected to the server; however, the service is not available.  
**Action** The 'Application Platform Support' component must be installed for each server. Verify this component was installed; otherwise, please contact Global Support. Please provide the Designer and server logs.

**JmxServiceServerError – An error occurred while executing an Application Platform Designer remote JMX service on the server.**

**Explanation** Application Platform is using a JMX service to communicate with the server. An exception occurred on the server while executing a task.  
**Action** Determine the source of this server-side error and contact Global Support if unable to resolve the issue.

<b>PLDBBCE0000</b>	<b>Unable to establish a JMX connection to the {0} server over port {1}. Cause: {2}</b>
<b>Explanation</b>	Designer failed to establish a JMX to the remote development server.
<b>Action</b>	Verify that the server is started and that the installed PLS bundle deploy service bundle is active.
<b>PLDBBCE0001</b>	<b>Unable to access the bundle publisher service.</b>
<b>Explanation</b>	The Dependency Manager was unable to access the publisher service when the remote server was started. The dependency manager needs the publisher service in order to obtain the list of deployed bundles in the server's OSGi container.
<b>Action</b>	Restart Designer and verify that the PLD bundle deploy client bundle is active.
<b>PLDBBCE0002</b>	<b>Unable to access the Dependency Manager service.</b>
<b>Explanation</b>	The Dependency Manager service is contributed to the OSGi service registry but it is not registered to it.
<b>Action</b>	Restart Designer and verify that the PLD bundle builder core bundle is active.
<b>PLDBBUE0000</b>	<b>An error occurred while resolving the list of libraries in the Application Platform common classpath container for project: {0}. Cause: {1}</b>
<b>Explanation</b>	The list of libraries that are automatically created by Application Platform for the project cannot be resolved. One or more libraries, provided by Application Platform, must be present for projects with Application Platform project facets.
<b>Action</b>	Remove the Application Platform core project facet from the project and add it again. Verify that the Application Platform bundles exist in the target installation path under 'common/runtime/bundles/pls-core/eclipse/plugins' and 'common/runtime/bundles/applatform/eclipse/plugins'. If these directories do not exist, verify that all of the Application Platform components were selected during installation.
<b>PLDBBUE0001</b>	<b>An error occurred while initializing the Application Platform classpath container for project {0}. Cause: {1}</b>
<b>Explanation</b>	Designer could not initialize the classpath container for the existing project during the workspace initialization. The error is isolated to the initializer of this container.
<b>Action</b>	Remove the Application Platform core project facet from the project and add it again. Verify that the Application Platform bundles exist in the target installation path under 'common/runtime/bundles/pls-core/eclipse/plugins' and 'common/runtime/bundles/applatform/eclipse/plugins'. If these directories do not exist, verify that all of the Application Platform components were selected during installation.

---

<b>PLDBMGE0000</b>	<b>An exception occurred while reloading the Bundle Manager view. Cause: {0}</b>
<b>Explanation</b>	Designer could not reload the Bundle Manager view. Reloading the Bundle Manager view involves the following sources: a selected project, a connected server, and a configured set of directories.
<b>Action</b>	Determine the source where the error occurred (directory, project or server).
<b>PLDBMGE0001</b>	<b>An exception was produced while accessing the Dependency Manager Service.</b>
<b>Explanation</b>	Designer could not access the Dependency Manager Service. The Dependency Manager Service is an OSGi service. Application Platform uses this service for verifying bundles and their relationships to other bundles.
<b>Action</b>	Restart Designer and try again. If the error persists, contact Software AG Global Support.
<b>PLDBMGE0002</b>	<b>An exception was produced while accessing the Bundle Manager Service.</b>
<b>Explanation</b>	Designer could not access the Bundle Manager Service. The Bundle Manager Service is an OSGi service used by the Application Platform Bundle Manager View.
<b>Action</b>	Restart Designer and try again. If the error persists, contact Software AG Global Support.
<b>PLDBMGE0003</b>	<b>An error occurred while restoring the Bundle Manager to its default settings. Cause: {0}</b>
<b>Explanation</b>	An error occurred while resetting the Bundle Manager to its default values. The configuration settings of the Bundle Manager are stored by the Eclipse preferences API.
<b>Action</b>	Check the details of the exception and try to resolve the problem.
<b>PLDBMGE0005</b>	<b>Error opening Bundle Manager configuration settings dialog. Cause: {0}</b>
<b>Explanation</b>	The Bundle Manager configuration settings dialog failed to open. The configuration settings dialog contains configuration settings that impact the Bundle Manager view.
<b>Action</b>	Restart Designer and try again. Try to access the Bundle Manager configuration settings dialog from the Windows/Preferences/SoftwareAG/Bundle Manager menu path.
<b>PLDBMGE0006</b>	<b>Invalid number format for the App Platform server configuration key: {0}. Value: {1}</b>
<b>Explanation</b>	The server configuration property received an invalid value. A numeric value is required for the App Platform server configuration key.
<b>Action</b>	Verify that the server configuration value is non-null and that it is numeric.

**PLDBMGE0007**      **Bundle Manager encountered an error while publishing bundle {0} into the server's repository. Cause: {1}**

**Explanation**      The Bundle Manager could not publish the selected bundle to the server's bundle repository. The bundle must be published to the repository before it can be installed to the server's OSGi container. For this purpose, the bundle is first copied to a staging directory. Designer transfers the bundle to this directory by using a JMX interface via the port number, configured in the WST server

**Action**            Review the contents of the staging directory under the server's installation directory, for example: profiles/IS\_default/workspace/temp/app-platform/deployer/bundles/. Verify that the configuration of the WST server is correct and that the server is started and it is listening on the JMX port.

**PLDBMGE0008**      **Bundle Manager encountered an error while installing bundle {0} to the server's OSGi container. Cause: {1}**

**Explanation**      The Bundle Manager failed to install the bundle to the server's OSGi container.

**Action**            Verify that the bundle was copied from the staging directory to the repository directory under the installation directory, for example: profiles/IS\_default/workspace/app-platform/deployer/bundles/. If required bundles or imported packages are missing, review the OSGi dependencies to ensure that all required dependencies are met.

**PLDBMGE0009**      **Bundle Manager encountered an error while unpublishing the bundle {0} from the server's repository. Cause: {1}**

**Explanation**      The Bundle Manager failed to unpublish the bundle from the server's repository. The bundle can be unpublished from the server's repository after it is uninstalled from the OSGi container.

**Action**            Verify that the bundle was successfully removed from the repository directory under the installation folder, for example: profiles/IS\_default/workspace/app-platform/deployer/bundles/. If the bundle is still in the directory, delete it manually by removing the file from this directory and restarting the server.

**PLDBMGE0010**      **Bundle Manager encountered an error while removing bundle {0} from the server's OSGi container. Cause: {1}**

**Explanation**      The Bundle Manager failed to uninstall the bundle from the server's OSGi container. The bundle must be uninstalled from the OSGi container before it can be unpublished from the p2 repository.

**Action**            Verify that the bundle was successfully removed from the repository directory under the installation folder, for example: profiles/IS\_default/workspace/app-platform/deployer/bundles/. If the bundle is still in the directory, delete it manually by removing the file from this directory and restarting the server.

---

<b>PLDBMGE0011</b>	<b>The Bundle Manager encountered an unexpected error while executing the update server task. Cause: {0}</b>
<b>Explanation</b>	The Bundle Manager failed to update the server. The Bundle Manager runs an update server task when a server is started or bundle changes are committed.
<b>Action</b>	Review the contents of the staging directory under the server's installation directory. Verify that the configuration of the WST server is correct and that the server is started and it is listening on the JMX port. If you have uninstalled bundles from the server, verify that they bundle were successfully removed from the repository directory under the installation folder. If one or more bundles are still in the directory, delete it manually by removing the file from this directory and restarting the server.
<b>PLDBMGE0012</b>	<b>An Application Platform server must be configured and started for this operation.</b>
<b>Explanation</b>	This Application Platform operation in Designer requires access to a server instance. A server configuration must be created and successfully started.
<b>Action</b>	From the Servers view create an Application Platform server and start it.
<b>PLDBMGE0015</b>	<b>Error creating wrapper bundle. Cause: {0}</b>
<b>Explanation</b>	An unexpected error occurred while creating a wrapper bundle for the set of jars.
<b>Action</b>	Verify that the jar files and the bundle manifest are valid. If they are valid and the error persists, contact Software AG Global Support.
<b>PLDBMGE0017</b>	<b>An error occurred while creating a wrapper bundle. Cause: {0}</b>
<b>Explanation</b>	The Bundle Manager view failed to create a wrapper bundle for the given plain jar(s).
<b>Action</b>	Verify that the jars to be included in the wrapper jar are valid Java archives. Review the generated OSGi manifest entry in the jar (META-INF/MANIFEST.MF) and verify that the target directory, where the bundle is to be created, exists and has appropriate file permissions for the current user.
<b>PLDBMGE0019</b>	<b>Error removing wrapper bundle. Cause: {0}</b>
<b>Explanation</b>	An unexpected error occurred while removing one or more wrapper bundles.
<b>Action</b>	Verify that the associated jar files exist and that they are not opened in another application.
<b>PLDBMGE0021</b>	<b>File {0} was not installed on the server. The file is not a bundle.</b>
<b>Explanation</b>	The file you attempted for publishing to the server is not an OSGi bundle. Designer can only publish OSGi bundlers to the product server.
<b>Action</b>	Review the file contents and publish only OSGi bundles to the server.

<b>PLDBMGE0022</b>	<b>Unable to validate project {0}'s bundle file before attempting to publish or unpublish.</b>
<b>Explanation</b>	The file could not be validated by Designer. Designer needs a valid project archive file with OSGi bundle headers before it can perform publisher-related operations against a server.
<b>Action</b>	Rebuild the project to ensure its contents are up to date.
<b>PLDBMGI0020</b>	<b>The server must be started before bundles can be removed. The server is used to confirm they the bundles are not installed.</b>
<b>Explanation</b>	You cannot remove bundles when the server is started. Published bundles cannot be removed, so the server must first confirm that the selected bundles for removal are not installed.
<b>Action</b>	Start the Application Platform server in Designer and select unpublished bundles for removal.
<b>PLDBMGW0014</b>	<b>Clear the text filter to ensure that all bundles or jars are included in this action.</b>
<b>Explanation</b>	The filter cannot be cleared programmatically before the selected task is runned because the task is running on the same UI thread.
<b>Action</b>	Clear the text box and repeat the operation.
<b>PLDCDGE0000</b>	<b>Unknown data type from DataKey annotation for field {0}; type: {1}</b>
<b>Explanation</b>	The DataKey annotation is incorrect. The DataKey annotation identifies an element to be used in IS service signature. These signatures support only a limited set of data types. The data type of the field identified here is not supported.
<b>Action</b>	Update the DataKey annotation to use a supported data type.
<b>PLDCDGE0001</b>	<b>Unable to create POJO wrappers for IS node: {0}</b>
<b>Explanation</b>	The node is not recognized by the IS server as a defined service or a shared doctype or specification reference.
<b>Action</b>	Make sure that the selected node is valid on the selected IS server.
<b>PLDCDGE0002</b>	<b>Unexpected Integration Server node-type {0} for node {1}, expecting {2}</b>
<b>Explanation</b>	An unexpected node-type was found in the Integration Server node that was retrieved. This may be caused by an incorrect node name.
<b>Action</b>	Correct the Integration Server node name.

---

<b>PLDCDGE0003</b>	<b>Unable to retrieve Integration Server {0} description for node {1}; caught: {2}</b>
<b>Explanation</b>	Retrieving the service or record details for the given Integration Server node was unsuccessful. This error may result from improper configuration either in the IS server identification, or in the IS service.
<b>Action</b>	Check the error logs for more details about this error.
<b>PLDCDGE0004</b>	<b>Unexpected signature node type: {0}; field is {1}, generating bean: {2},{3}</b>
<b>Explanation</b>	The field-type used when generating a Java source for the IS service signature was not recognized. This may occur because of an unsupported IS service configuration.
<b>Action</b>	Contact Software AG Global Support.
<b>PLDCDGE0005</b>	<b>Cannot use a connection that is null or disconnected: {0}</b>
<b>Explanation</b>	Failed to connect to Integration Server. Application Platform attempted to generate a code for an IS service but the connection is not working.
<b>Action</b>	Verify that the connection to Integration Server is working. If the error persists with a working connection, contact Software AG Global Support.
<b>PLDCDGE0006</b>	<b>Unable to retrieve Integration Server {0} description for package {1}; caught: {2}</b>
<b>Explanation</b>	Retrieving the details for the given Integration Server package was unsuccessful. This error may result from improper configuration either in the IS server identification, or in the IS package.
<b>Action</b>	Check the error logs for more details about this error.
<b>PLDCFTE0000</b>	<b>An error occurred while creating Application Platform project facets in the project template. Cause: {0}</b>
<b>Explanation</b>	The creation of Application Platform project facets failed. Designer uses a template of Eclipse project facets when creating a service project. The Application Platform server uses these facets to determine if it can publish a project's module.
<b>Action</b>	Verify that all of the Application Platform components were installed in Designer.
<b>PLDCFTE0001</b>	<b>An error occurred in the Application Platform service project wizard while creating a project. Cause: {0}</b>
<b>Explanation</b>	The Application Platform service project wizard failed to create a project. The service project wizard creates a Designer project and performs tasks for each of the selected project facets.
<b>Action</b>	Review the error and verify that the project facet selections are valid.

<b>PLDCSPE0001</b>	<b>An error occurred while unpublishing a project resource from the server, configured for Application Platform.</b>
<b>Explanation</b>	An unexpected error occurred while unpublishing a project resource to the configured server.
<b>Action</b>	Verify that the project is still deployed on the server, that the server configuration is complete, and that the server can be started successfully.
<b>PLDCSPE0003</b>	<b>An error occurred while publishing a project resource to the Application Platform server.</b>
<b>Explanation</b>	An unexpected error occurred while publishing a project resource to the configured server.
<b>Action</b>	Verify that the project contents are valid, that the server configuration is complete, and that the server can be started successfully.
<b>PLDCSPE0004</b>	<b>Designer was unable to confirm the server's status during startup/shutdown. Details: {0}</b>
<b>Explanation</b>	The configured Application Platform server uses a polling ping approach to confirm if the remote server was successfully started or stopped. An error occurred during the ping operation and the status of the server could not be confirmed.
<b>Action</b>	If you are running the server via its native shell scripts, stop the server. Then try to restart the server in Designer.
<b>PLDCSPE0005</b>	<b>An exception was encountered while trying to synchronize the Application Platform server {0}'s run status in the Servers view. Cause: {1}</b>
<b>Explanation</b>	Designer was unable to synchronize the status of the Application Platform server. The Servers view for Application Platform has a configuration setting, which is used to control how Designer synchronizes its status against the server.
<b>Action</b>	Verify that the configuration parameters are correct. If the server properties section does not show any properties, delete the server configuration and recreate it.
<b>PLDCSPE0006</b>	<b>An error occurred while refreshing the Bundle Manager during the server status update to {1}. Cause: {2}</b>
<b>Explanation</b>	Designer failed to refresh the Bundle Manager when the server was started or stopped.
<b>Action</b>	Restart Designer. If the error persists, contact Software AG Global Support.

---

<b>PLDCSPE0009</b>	<b>An error occurred while updating the Application Platform server run status {0}. Cause: {1}</b>
<b>Explanation</b>	The Server's view for the Application Platform includes an entry for each configured server. Designer has received a WST server event, but an error has occurred while Designer attempted to update a server's run state.
<b>Action</b>	Review the server configuration in the Servers view and verify that the required server data is present. If the data is incorrect or some server properties are not displayed, delete the server configuration and recreate it.
<b>PLDCSPE0010</b>	<b>Error getting a URL for server {0} for verifying the run status of Integration Server. Cause: {1}</b>
<b>Explanation</b>	Designer was unable to obtain a URL for the server. The URL is needed in order to perform a ping operation against the server and to determine its current status.
<b>Action</b>	Verify that the server configuration properties are correct and try again.
<b>PLDCSPE0011</b>	<b>Unable to create Application Platform custom module.</b>
<b>Explanation</b>	Application Platform was unable to create a custom module. Application Platform uses a custom module in order to differentiate its server from other servers, like Tomcat, for example. The custom module is needed for adding all application projects containing the Application Platform project facets to the server. This is a critical component required for publishing bundles to the server.
<b>Action</b>	Contact Software AG Global Support.
<b>PLDCSPE0012</b>	<b>An unexpected error occurred while validating a project facet for module {0}. Cause: {1}</b>
<b>Explanation</b>	Designer could not validate a project facet for the module. Designer projects use facets in order to define capabilities, supported by the servers that host the projects. This ensures that no attempts for publishing a project to a server that does not support that project can be made.
<b>Action</b>	Review the error details and verify that the correct project facets are added to the project.
<b>PLDCSPE0013</b>	<b>An error occurred while adding server {0} to the lifecycle listener. Cause: {1}</b>
<b>Explanation</b>	Designer failed to add the server to the lifecycle listener. A collection of listeners is maintained for servers that are added or removed from Designer. The listeners contain all the information that is needed for performing server actions, like publishing or unpublishing project bundles.
<b>Action</b>	Restart Designer.

<b>PLDCSPE0014</b>	<b>An error occurred while synchronizing WST Servers View configuration updates. Cause: {0}</b>
<b>Explanation</b>	Application Platform uses the Eclipse WST subsystem server configuration data. An exception occurred while updating Application Platform plugins.
<b>Action</b>	Restart Designer.
<b>PLDCSPE0015</b>	<b>Missing credentials for server connection to the following url: {0}</b>
<b>Explanation</b>	No credentials have been provided to verify the server status.
<b>Action</b>	Verify that the server connection has appropriate credentials.
<b>PLDCSPW0000</b>	<b>An attempt was made to publish or unpublish a project module to a server that is not started.</b>
<b>Explanation</b>	An error occurred while publishing or unpublishing the project module because the server is not started. You can only publish or unpublish Application Server projects to a server, which is started.
<b>Action</b>	Verify that the server is started and repeat the action.
<b>PLDCSPW0002</b>	<b>No project modules were specified for the Application Platform publish operation.</b>
<b>Explanation</b>	The Application Platform publisher received a publish request but no project modules were included in the request.
<b>Action</b>	Confirm that there is at least one project added to the Application Platform server configuration and try to publish again.
<b>PLDCSPW0008</b>	<b>You must stop and restart the server after you change and save the server settings.</b>
<b>Explanation</b>	You must restart the server after you change the server settings. Many of the server settings you can configure in Designer update server configurations, such as port numbers.
<b>Action</b>	Restart the server, and then restart the configured server in Designer.
<b>PLDCUIE0001</b>	<b>An unexpected error occurred while configuring an Application Platform runtime environment.</b>
<b>Explanation</b>	The Application Platform runtime configuration failed. The runtime preference page is used to define the runtime instance used for Application Platform server and project configurations.
<b>Action</b>	Go to the Window/Preferences/Server/Runtime Environments preference panel and create a runtime instance for the Application Platform server. If no server entry is displayed, confirm that all the required Application Platform components were installed.

---

<b>PLDCUIE0002</b>	<b>Unable to verify preference setting {0} from the imported preferences file. Cause: {1}</b>
<b>Explanation</b>	Application Platform verifies all directory path preference settings during the import step. An error occurred while verifying one of the preference settings.
<b>Action</b>	Update the preference setting manually.
<b>PLDCUIE0003</b>	<b>{0} preference setting's directory path does not exist. ({1})</b>
<b>Explanation</b>	While importing Designer preferences, Application Platform encountered a preference setting that contains a non-existent directory path.
<b>Action</b>	Update the imported preference setting with a valid directory path.
<b>PLDCUII0000</b>	<b>No Application Platform runtime instance configuration was found.</b>
<b>Explanation</b>	Designer could not find an Application Platform runtime instance configuration. The Application Platform server and projects require a runtime configuration.
<b>Action</b>	Create a runtime instance in the 'Runtime Environments' preference page in Designer.
<b>PLDISPE0000</b>	<b>No Integration Server connections with valid URLs are defined in 'Window/Preferences/SoftwareAG/Integration Servers' for this Designer instance.</b>
<b>Explanation</b>	The Application Platform server was not able to start because there are no valid Integration Server connections defined.
<b>Action</b>	Configure a valid connection to a local Integration Server via the configuration panel. You can find the configuration panel in Window/Preferences/Software AG/Integration Servers.
<b>PLDISPE0007</b>	<b>An error occurred while retrieving the list of Integration Server connections. Details: {0}</b>
<b>Explanation</b>	Designer failed to retrieve the list of Integration Server connections. Designer maintains the list of connections in Window/Preferences/SoftwareAG/Integration Servers view.
<b>Action</b>	Contact Software AG Global Support.
<b>PLDISPE0008</b>	<b>No server connections are accessible in Window/Preferences/SoftwareAG/Integration Servers.</b>
<b>Explanation</b>	The Application Platform server configuration must have a Designer Integration Server connection defined for the same host and port. No servers were returned from the server connection manager.
<b>Action</b>	Verify that at least one server connection is defined in the preference view.

<b>PLDISWE0000</b>	<b>An error occurred while executing a task in the IS service wizard.</b>
<b>Explanation</b>	An error occurred while using the IS service wizard for creating POJO bean wrappers for Integration Server services.
<b>Action</b>	Restart Designer and try again.
<b>PLDISWE0001</b>	<b>The IS service wizard encountered an error while generating POJO classes for IS service: {0}</b>
<b>Explanation</b>	Application Platform was unable to produce Java POJO service wrappers for the selected IS service(s).
<b>Action</b>	Verify that the IS service is properly defined and retry the code generation step.
<b>PLDISWE0002</b>	<b>An Application Platform IS facet is not installed on this project.</b>
<b>Explanation</b>	The project is not configured to use the custom Application Platform facet for Integration Server extensions.
<b>Action</b>	Enable the Application Platform IS facet on the project's properties page.
<b>PLDISWI0003</b>	<b>IS services from IS product packages are not supported. Do not use this in a production setting.</b>
<b>Explanation</b>	The checkbox for selecting all IS services is provided only for demonstration purposes.
<b>Action</b>	Create new services to be used with the Application Platform.
<b>PLDNAVE0000</b>	<b>{0} model class is missing its identifier.</b>
<b>Explanation</b>	Every graph node in the Visual Navigator must have a unique identifier, which is provided by the model node provider implementation.
<b>Action</b>	Check if the class type is produced by a custom model node provider implementation and try to resolve the problem.
<b>PLDNAVE0002</b>	<b>Exception creating model node for object type {0}. Details: {1}</b>
<b>Explanation</b>	An error occurred while creating the model content for a graph node.
<b>Action</b>	Check if this is a custom implementation and try to resolve the problem.
<b>PLDNAVE0003</b>	<b>A class type is required when creating a category for a model object. Category name: {0}</b>
<b>Explanation</b>	You must provide a class type for all categories that you create for model node providers.
<b>Action</b>	Check if this is a custom implementation and try to resolve the problem.

---

<b>PLDNAVE0004</b>	<b>Exception creating list of package fragments from {0}. Details: {1}</b>
<b>Explanation</b>	An error occurred while the Visual Navigator was rendering a graph for the class dimension.
<b>Action</b>	Verify that there are no compilation errors in your projects and try again.
<b>PLDNAVE0005</b>	<b>Exception loading method {0}'s references. Details: {1}</b>
<b>Explanation</b>	The Method dimension in the navigator view could not find a reference to the method in Designer when rendering the graph view.
<b>Action</b>	Check the details of the exception and try to resolve the problem.
<b>PLDNAVE0006</b>	<b>Exception creating model nodes for class type {0} from native object {1}. Details: {2}</b>
<b>Explanation</b>	The Visual Navigator uses the currently selected object as input when it switches from one dimension to another. An error occurred while extracting the model from this input for the next dimension graph.
<b>Action</b>	Check the details of the exception and try to resolve the problem.
<b>PLDNAVE0007</b>	<b>Exception loading projects {0}'s references. Details: {1}</b>
<b>Explanation</b>	The Project dimension in the navigator view could not find a reference to the project in Designer when rendering the graph view.
<b>Action</b>	Check the details of the exception and try to resolve the problem.
<b>PLDNAVE0008</b>	<b>Exception loading resource {0}'s references. Details: {1}</b>
<b>Explanation</b>	The Resource dimension in the navigator view could not find a reference to the resource in Designer when rendering the graph view.
<b>Action</b>	Check the details of the exception and try to resolve the problem.
<b>PLDNAVE0010</b>	<b>Error executing model node providers for dimension {0} in the navigator view. Details: {1}</b>
<b>Explanation</b>	The Visual Navigator encountered an error while building the object model for its graph view.
<b>Action</b>	Check the details of the exception and try to resolve the problem.

<b>PLDNAVE0013</b>	<b>Universe with id {0} does not exist.</b>
<b>Explanation</b>	You can register universes containing unique IDs through the Visual Navigator API. However, the specified ID does not match any registered universe.
<b>Action</b>	Contact Software AG Global Support.
<b>PLDNAVE0014</b>	<b>Model node classname is required when creating an instance key.</b>
<b>Explanation</b>	Every graph node, created in the Visual Navigator must have a unique ID, which includes the model node class name.
<b>Action</b>	Contact Software AG Global Support.
<b>PLDNAVW0009</b>	<b>Unable to load annotation provider {0} for the navigator view. Details: {1}</b>
<b>Explanation</b>	The Visual Navigator failed to load the annotation provider, which is required for extending the content added to the graph view.
<b>Action</b>	Check the details of the exception and try to resolve the problem.
<b>PLDUTLE0000</b>	<b>An error occurred while updating Application Platform {0} project classpath. Cause: {1}</b>
<b>Explanation</b>	The project classpath failed to updated. The project classpath is updated when Application Platform project facets are installed or removed.
<b>Action</b>	Manually update the project classpath in Designer.
<b>PLDUTLE0001</b>	<b>Unable to resolve OSGi service: {0}</b>
<b>Explanation</b>	Designer could not resolve the OSGi service. This suggests that the OSGi service interface has no implementations in the service registry. A possible reason is that the bundle contributing an implementation did not activate as expected or is missing from the container.
<b>Action</b>	Restart Designer and retry.
<b>PLDWSE0000</b>	<b>An error occurred while adding Application Platform classpath containers to the {0} project. Cause: {1}</b>
<b>Explanation</b>	Adding Application Platform classpath containers failed with an error. When Application Platform project facets are added to a project, additional classpath containers are also added to the project. This error can be caused by a corrupt Java project.
<b>Action</b>	Delete the Java project and create it again. While creating the project, make sure that you do not delete project contents.

---

<b>PLDWSE0001</b>	<b>An invalid number format was found for Application Platform server configuration key: {0}. Value: {1}</b>
<b>Explanation</b>	The Application Platform server configuration key has an invalid number format. A numeric value is required.
<b>Action</b>	Verify that the server configuration value is non-null and numeric.
<b>PLDWSE0002</b>	<b>An attempt was made to register an Application Platform WST server instance with no server name.</b>
<b>Explanation</b>	A registration attempt was made for an Application Platform WST server instance with no server name. A server name is required.
<b>Action</b>	Verify that the server configuration has a server name and restart the server instance.
<b>PLDWSE0003</b>	<b>An error occurred while removing Application Platform classpath containers from the {0} project. Cause: {1}</b>
<b>Explanation</b>	Removing Application Platform classpath containers from the project failed with an error. When Application Platform project facets are removed from a project, additional classpath containers are also removed from the project. This error can be caused by a corrupt Java project.
<b>Action</b>	Delete the Java project and create it again. While creating the project, make sure that you do not delete project contents.
<b>ProfilesPageContentProvider_0 – Cannot resolve the server profiles from the base directory: {0}.</b>	
<b>Explanation</b>	An error occurred while resolving the server profiles using the base installation directory.
<b>Action</b>	Check if the ECLIPSE_HOME classpath variable for Designer points to the correct location. The default location is SAG_INSTALL_DIR/Designer/eclipse.



# 4 Application Platform Server Messages

---

<b>PLSAPPE0000</b>	<b>Need instance of MethodMetadataImpl, can not use type: {0}</b>
<b>Explanation</b>	Not all implementations of the metadata interfaces can be used for service invocation.
<b>Action</b>	Change your service configuration to use an acceptable implementation.
<b>PLSAPPE0001</b>	<b>OsgiService.validate failed because it cannot work with null metadata.</b>
<b>Explanation</b>	The OSGi service object was not properly initialized because of null metadata.
<b>Action</b>	Contact Software AG Global Support.
<b>PLSAPPE0002</b>	<b>OsgiService.initializeService failed with exception: type({0}), msg({1})</b>
<b>Explanation</b>	The OSGi service was not properly initialized.
<b>Action</b>	Check the error logs for more details about this error.
<b>PLSAPPE0003</b>	<b>OsgiService.baseInvoke found a non-null svc object for {0} from an unexpected class loader; expected {1}, found {2}</b>
<b>Explanation</b>	The OSGi service invocation used a service class from an unknown, unexpected class loader. This has caused an OSGi container or a bundle configuration problem.
<b>Action</b>	Contact Software AG Global Support.
<b>PLSAPPE0004</b>	<b>OsgiService.baseInvoke: unable to get service object for {0} from registry</b>
<b>Explanation</b>	Integration Server is expected to register an OSGi service to expose Integration Server artifacts in Application Platform. The OSGi service could not be found.
<b>Action</b>	Contact Software AG Global Support.

<b>PLSAPPE0005</b>	<b>Error initializing App Platform generated service binding {0}. Details: {1}</b>
<b>Explanation</b>	Integration Server (IS) calls Application Platform services that are exposed to IS by using a generated IS service.
<b>Action</b>	Unpublish the Application Platform service project and republish it again.
<b>PLSBDSE0000</b>	<b>Bundle deployment changes could not be initiated.</b>
<b>Explanation</b>	The Software AG Common Platform OSGi service, responsible for installing a bundle into the container, is missing.
<b>Action</b>	Restart the server and try again.
<b>PLSBDSE0001</b>	<b>The required OSGi deployment service is missing.</b>
<b>Explanation</b>	The Software AG Common Platform OSGi service, responsible for installing a bundle into the container, is missing.
<b>Action</b>	Restart the server and try again.
<b>PLSBDSE0006</b>	<b>{0} failed due to error: {1}</b>
<b>Explanation</b>	The install/uninstall operation failed because of the indicated error. The project bundle operation did not complete successfully and had to be retried after fixing the error.
<b>Action</b>	Review the error logs for more details about this error.
<b>PLSBDSE0007</b>	<b>Bundle installed, but failed to activate due to error: {0}</b>
<b>Explanation</b>	The project bundle was successfully installed in the runtime but its activation failed due to the specified error.
<b>Action</b>	Verify that all required libraries, with which the project has dependencies, are installed and available in the runtime.
<b>PLSBDSE0008</b>	<b>Installation failed! Bundle not present in installed bundles list</b>
<b>Explanation</b>	A bundle deploy call failed to install the specified bundle in the runtime. A possible cause is that the bundle deploy call was made to a runtime that does not contain the bundle jar file in the staging directory.
<b>Action</b>	If both runtime instance you are using and the server runtime configured in Designer are local, verify that they are the same.

---

<b>PLSBDSE0009</b>	<b>An exception was raised while uninstalling bundle {0}. Cause: {1}</b>
<b>Explanation</b>	The server encountered a fatal error while attempting to uninstall the referenced bundle.
<b>Action</b>	Check the error logs for more details about this error.
<b>PLSBDSE0010</b>	<b>An exception was raised while installing bundle {0}. Cause: {1}</b>
<b>Explanation</b>	The server encountered a fatal error while attempting to install the referenced bundle.
<b>Action</b>	Check the error logs for more details about this error.
<b>PLSBDSE0011</b>	<b>The bundle was not installed. The server was unable to copy {0} bundle into the bundle repository.</b>
<b>Explanation</b>	The bundle installation failed because the bundle could not be copied to the bundle repository.
<b>Action</b>	Perform a clean build and republish the bundle, if it is a project bundle. Inspect the server's bundle repository directory and the staging directories to determine condition of the bundle jar.
<b>PLSBDSE0014</b>	<b>An error occurred while transferring chunk {0} of bundle {1} from source {2}. Cause: {3}</b>
<b>Explanation</b>	The server encountered an exception while processing a chunk of resource transferred from Designer.
<b>Action</b>	Check the error logs for more details about this error.
<b>PLSBDSE0017</b>	<b>No test bundle with symbolic name: "{0}" and version: "{1}" is installed in the runtime! Unable to run test method: "{2}" in class: "{3}"</b>
<b>Explanation</b>	The bundle containing the JUnit App Platform Integration tests with the specified bundle symbolic name and version failed to install in the runtime.
<b>Action</b>	Deploy the project containing the integration tests to the running runtime instance before running the JUnit test through Designer.
<b>PLSBRME0000</b>	<b>The repository manager operation was not performed due to missing bundle key.</b>
<b>Explanation</b>	The repository manager operation failed because of a missing bundle key. Designer operations for publishing and unpublishing bundles from the server require a bundle key object.
<b>Action</b>	Contact Software AG Global Support.

**PLSBRME0001**      **Could not determine the location of the bundle repository from the location of the configured server.**

**Explanation**      Obtaining the bundle repository directory path failed. This directory contains project bundles and other bundles that are installed by the Bundle Publisher on the server's OSGi container. The bundle repository location is determined by the value, defined for the 'osgi.instance.area' configuration of the OSGi container running on the server.

**Action**              Verify that the server's config.ini file has a valid value for 'osgi.instance.area'.

**PLSBRME0002**      **Could not determine the server's OSGi instance area.**

**Explanation**      The 'osgi.instance.area' key, which is the value of the server's OSGi instance area could not be determined. The key is part of the required data included in the server's config.ini file. The problem may be caused by a corrupted config.ini file.

**Action**              Review the contents of the config. ini file.

**PLSBRME0004**      **Could not determine the bundle repository staging location from the location of the configured server.**

**Explanation**      Obtaining the bundle repository staging directory path failed. This is the directory path on the server where project bundles and other bundles, installed by the Bundle Publisher, are located when they are initially transferred to the server. This initial transfer is made prior to installing the bundles to OSGi container. The bundle repository location is determined by the value, defined for the 'osgi.instance.area' configuration of the OSGi container running in the server.

**Action**              Verify that the server's config.ini file has a valid value for 'osgi.instance.area'.

**PLSBRME0007**      **Unable to create directory path. {0}**

**Explanation**      The specified directory path could not be created.

**Action**              Verify that the specified path is valid on the file system and that there are no processes that are using it or that have locked it. Retry the operation afterwards.

**PLSBRME0008**      **An attempt was made to install or uninstall a bundle before the bundle has been transferred to the server's staging directory. {0}**

**Explanation**      Installing or uninstalling the bundle failed because the bundle is not transferred to the server. Bundles must first be transferred to the server before they can be installed or removed from its OSGi container.

**Action**              Retry the operation and verify that the bundle is transferred to the staging directory under the server profile's workspace.

---

<b>PLSBRME0009</b>	<b>An error occurred while refreshing the Application Platform project bundles in the bundle repository. {0}</b>
<b>Explanation</b>	Refreshing the Application Platform project bundles failed with an error. When you refresh the repository manager, the repository directory path is retrieved prior to registering the jars located there.
<b>Action</b>	Check the error logs for more details about this error.
<b>PLSBRME0010</b>	<b>Unable to refresh bundle file {0} in the bundle repository. {1}</b>
<b>Explanation</b>	Refreshing the bundle file in the bundle repository failed with an error. When you refresh the repository manager, it checks the OSGi manifest for each jar file in the directory. In this way the repository manager prepares for registering each bundle prior to installation.
<b>Action</b>	Check the error logs for more details about this error and try to determine if the jar file is corrupt.
<b>PLSBRME0011</b>	<b>Bundle {0}, which is transferred from Designer, does not match manifest {1} for this jar {2}.</b>
<b>Explanation</b>	The transferred bundle does not match the manifest for this jar. When Designer publishes bundles to the server, the bundle's name and version are included with the transfer request and they must match the name and version, declared in the jar file's OSGi manifest file.
<b>Action</b>	Perform a clean project build and repeat the operation.
<b>PLSBRME0012</b>	<b>Attempt to uninstall a bundle that is missing from the bundle repository manager. {0}</b>
<b>Explanation</b>	The Application Platform bundle repository manager maintains a map of all the bundles provisioned into the server. A bundle with this symbolic name and version was not found. This may have occurred because of changing the version of the project bundle without unpublishing the project bundle first.
<b>Action</b>	Unpublish the project bundle with the prior version and then update the project with the new version.
<b>PLSBRME0013</b>	<b>Attempt to uninstall a bundle missing from the bundle repository manager. {0}. (Note, another bundle version ({1}) is provisioned in the server.)</b>
<b>Explanation</b>	The Application Platform bundle repository manager maintains a map of all the bundles provisioned into the server. A bundle with this symbolic name and version was not found. This may have occurred because of changing the version of the project bundle without unpublishing the project bundle first.
<b>Action</b>	Unpublish the project bundle with the prior version and then update the project with the new version.

<b>PLSCOME0001</b>	<b>Unable to resolve the required OSGi service: {0}</b>
<b>Explanation</b>	A service implementation for the required OSGi service was not found in the OSGi registry.
<b>Action</b>	Check the error logs for more details about this error.
<b>PLSCOME0002</b>	<b>Data corruption was found on chunk {0} of bundle {1} during transfer from Designer to the server.</b>
<b>Explanation</b>	The hash computed by the server did not match the value computed by the sender. This may be caused by a faulty network or a modification from an intermediary.
<b>Action</b>	Verify that there are no network issues on proxy servers and so on.
<b>PLSCOME0003</b>	<b>Unable to delete this file: {0}</b>
<b>Explanation</b>	Your attempt to remove the file has failed according to your operating system.
<b>Action</b>	Verify that the file permissions are appropriate for the user that is running the server.
<b>PLSCOME0004</b>	<b>Unable to create this file: {0}</b>
<b>Explanation</b>	Your attempt to create the file has failed according to your operating system.
<b>Action</b>	Verify that the file permissions are appropriate for the user that is running the server.
<b>PLSCOME0005</b>	<b>Unable to create this directory path: {0}</b>
<b>Explanation</b>	Your attempt to create the directory path has failed according to your operating system.
<b>Action</b>	Verify that the file permissions are appropriate for the user that is running the server.
<b>PLSCOME0006</b>	<b>An illegal sequence was detected during a file transfer.</b>
<b>Explanation</b>	A chunk of a file resource that was transferred to the server had an unexpected sequence number.
<b>Action</b>	Repeat the failed operation.
<b>PLSCOME0007</b>	<b>Unable to read a non-existent file. {0}</b>
<b>Explanation</b>	An attempt was made to transfer a non-existent resource to the server.
<b>Action</b>	Verify that the expected files exist and repeat the operation.

<b>PLSCOME0008</b>	<b>The server does not have any of the expected message digest algorithms. {0}. At least one of these is required.</b>
<b>Explanation</b>	No message digest algorithms were found on the server. Application Platform needs a message digest to verify the integrity of data transferred from Designer to the server.
<b>Action</b>	Update Application Platform to include one of the digest algorithms.
<b>PLSCOME0009</b>	<b>File {0} is not a valid zip archive or it does not contain a manifest file.</b>
<b>Explanation</b>	The file is invalid. A Java archive file with manifest is expected.
<b>Action</b>	Review the file contents and update as necessary.
<b>PLSCOME0010</b>	<b>File {0} is not a valid bundle.</b>
<b>Explanation</b>	The file is invalid. An OSGi bundle with a valid manifest, containing the required OSGi headers, is expected.
<b>Action</b>	Review the file contents and update as necessary.
<b>PLSCOME0011</b>	<b>Connect operation timed out: {0}</b>
<b>Explanation</b>	A socket timeout error occurred when trying to connect to the JMX endpoint.
<b>Action</b>	Verify that target server is running and that the JMX port matches the server-side configuration.
<b>PLSGWIE0000</b>	<b>GatewayServiceImpl cannot work with NULL method metadata</b>
<b>Explanation</b>	The code, which calls GatewayServiceImpl, fails with an error. GatewayServiceImpl has no metadata and parameter details, which are required for identifying the service and invoking its method.
<b>Action</b>	Make sure that the code does not call the method, unless the required metadata is available.
<b>PLSGWIE0001</b>	<b>GatewayServiceImpl.delegateInvoke: unable to extract parameter values from IData for service ({0},{1}); caught: ({2}), msg({3})</b>
<b>Explanation</b>	The conversion of IData contents to Java method parameters failed. This may be caused by a mismatch between expected parameter types (as specified in metadata) and actual pipeline values (as presented during runtime). Check the exception message for more information about the cause.
<b>Action</b>	Compare the actual parameter values with the expected types, specified in the metadata.

<b>PLSGWIE0002</b>	<b>GatewayServiceImpl.delegateInvoke: unable to invoke targeted service ({0}.{1}); caught: ({2}), msg({3})</b>
<b>Explanation</b>	The invocation of the indicated method failed. This may be caused by a mismatch between expected parameter types (as specified in metadata) and actual pipeline values (as presented during runtime). Another possible cause is that the expected service is not registered with OSGi. Check the exception message for more information about the cause.
<b>Action</b>	Verify that the expected OSGi service is registered. Compare the actual parameter values with the expected types, specified in the metadata.
<b>PLSGWIE0003</b>	<b>GatewayServiceImpl.delegateInvoke: unable to extract IData from the object returned by ({0}.{1}); caught: ({2}), msg({3})</b>
<b>Explanation</b>	The conversion of Java object to IData failed. This may be caused by a mismatch between expected parameter types (as specified in metadata) and actual pipeline values (as presented during runtime). Check the exception message for more information about the cause.
<b>Action</b>	Compare the actual parameter values with the expected types, specified in the metadata.
<b>PLSGWIE0004</b>	<b>Unable to convert class name string ({0}) to class object using loader from {1}; caught type({2}), msg({3})</b>
<b>Explanation</b>	The named class from the metadata could not be loaded. This may be caused by a dependency issue.
<b>Action</b>	Make sure that the bundle that is hosting the targeted service can access the class.
<b>PLSGWIE0005</b>	<b>Unable to find method {0}({1}) on class {2}; caught type({3}), msg({4})</b>
<b>Explanation</b>	The method, expecting the indicated parameter types list, could not be found on the indicated class. This may be caused by a mismatch between expected parameter types (as specified in metadata) and available method signatures. Check the exception message for more information about the cause.
<b>Action</b>	Verify that the metadata is consistent with the targeted class.
<b>PLSGWIE0012</b>	<b>Unable to invoke method ({0}), a problem occurred with the conversion of input pipeline: {1}</b>
<b>Explanation</b>	The Application Platform gateway service encountered a problem converting the Integration Server pipeline to Java method parameters.
<b>Action</b>	Contact Software AG Global Support.

<b>PLSGWIE0013</b>	<b>Cannot invoke method {0}.{1}, no OSGi service is registered for {1}</b>
<b>Explanation</b>	The OSGi service was not found. GatewayService requires registration of the OSGi service.
<b>Action</b>	Verify that the indicated service is exposed by an active Application Platform bundle.
<b>PLSGWIE0014</b>	<b>Failed attempt to execute App Platform service {0} due to missing required metadata.</b>
<b>Explanation</b>	App Platform service implementations published to the Integration Server must contain additional metadata in a META-INF/gatewayMetadata.xml file. This information is needed to assist with the transformation to and from the Integration Server's data model.
<b>Action</b>	Review the server logs for any errors. Inspect the project bundle and verify its metadata file is present, and redeploy if necessary.
<b>PLSGWIE0015</b>	<b>Failed attempt to execute App Platform service {0}'s method {1}. The method signature does not match the signature expected by the Integration Server's generated service binding.</b>
<b>Explanation</b>	When Integration Server services execute service bindings of App Platform OSGi services, the IO signatures must match the OSGi service implementation.
<b>Action</b>	Republish the App Platform service project and verify the generated IS service bindings are updated.
<b>PLSGWIW0006</b>	<b>IData2Pojo.createCollectionValue: unable to convert collection object type: {0}</b>
<b>Explanation</b>	The Application Platform gateway failed to convert the indicated collection type from IData to Java type.
<b>Action</b>	Contact Software AG Global Support.
<b>PLSGWIW0007</b>	<b>IData2Pojo.valueFromDataArray: unable to convert collection property type: {0}</b>
<b>Explanation</b>	The Application Platform gateway failed to convert the indicated property type from IData to Java type.
<b>Action</b>	Contact Software AG Global Support.
<b>PLSGWIW0008</b>	<b>IData2Pojo.constructList(): expected element {0} to be IData but found {1} instead.</b>
<b>Explanation</b>	An unexpected data type was found in an IData parameter array.
<b>Action</b>	Verify that the calling code uses appropriate data types.

<b>PLSGWIW0009</b>	<b>IData2Pojo.constructList(): expected pipeline to hold an array but found {0} instead.</b>
<b>Explanation</b>	An unexpected data type was found in an IData parameter array.
<b>Action</b>	Verify that the calling code uses appropriate data types.
<b>PLSGWIW0010</b>	<b>IData2Pojo.constructCollection(): unexpected collection type: {0}</b>
<b>Explanation</b>	Application Platform encountered an unexpected collection data type while converting from IData to Java object.
<b>Action</b>	Verify that the calling code uses appropriate data types.
<b>PLSGWIW0011</b>	<b>Pojo2IData.collectionToData: unexpected collection data type: {0}</b>
<b>Explanation</b>	The Application Platform conversion from Java object to IData encountered an unexpected collection data type.
<b>Action</b>	Verify that the calling code uses appropriate data types.
<b>PLSOBEE0000</b>	<b>Unable to invoke service {0} after trying with {1} principal names.</b>
<b>Explanation</b>	None of the principal names associated with the current session were allowed to invoke the designated service.
<b>Action</b>	Check the log for previous entries that show failed invocation attempts by each principal. Make sure that you use a valid Integration Server user ID for the IS service invocation.
<b>PLSOBEE0002</b>	<b>An exception was caught while attempting to identify the Subject for the current session; attempting to invoke authorization service {0}; caught: {1}</b>
<b>Explanation</b>	Attempting to identify the Subject for the current session failed with an exception. This exception may be caused by a problem with the Authorization Service in Software AG Common Platform.
<b>Action</b>	Contact Software AG Global Support.
<b>PLSOBEE0003</b>	<b>Cannot introspect a NULL service for IS package {0}, metadata: {1}.</b>
<b>Explanation</b>	An attempt was made to construct a PipelineGenerator around a null OSGi Service object. This could indicate a problem with the Application Platform project preparation.
<b>Action</b>	Check the package name and metadata details in order to identify the targeted service.

---

<b>PLSOBEE0004</b>	<b>Cannot introspect a NULL class for IS package {0}, service: {1}, methods: {2}.</b>
<b>Explanation</b>	An attempt was made to construct a PipelineGenerator around a null Class object. This could indicate a problem with the Application Platform project preparation.
<b>Action</b>	Check the package name and metadata details in order to identify the targeted class.
<b>PLSOBEE0005</b>	<b>Unable to parse source details string {0}; caught this: type ({1}), msg({2})</b>
<b>Explanation</b>	An error was encountered while attempting to parse an XML string into source details objects.
<b>Action</b>	Contact Software AG Global Support.
<b>PLSOBEE0006</b>	<b>Unable to read contents from bundle URL {0}; caught this: type ({1}), msg({2})</b>
<b>Explanation</b>	An error was encountered while attempting to extract the contents of a file.
<b>Action</b>	Contact Software AG Global Support.
<b>PLSOBEE0007</b>	<b>A failure occurred during JAX-B unmarshalling from URL {0}; caught this: type ({1}), msg({2})</b>
<b>Explanation</b>	An error was encountered while attempting to convert the contents of a file.
<b>Action</b>	Contact Software AG Global Support.
<b>PLSOBEE0008</b>	<b>Unable to load class {0} from bundle {1}; caught this: type ({2}), msg({3})</b>
<b>Explanation</b>	The OSGi bundle was expected to contain the identified class.
<b>Action</b>	Contact Software AG Global Support.
<b>PLSOBEE0009</b>	<b>Unable to create IS services representing method {0} from the {1} class, in IS package {2}; caught this: type ({3}), msg({4})</b>
<b>Explanation</b>	Creating IS services representing the method failed. The problem may originated in the IS service creation or in the preparation of the IS pipeline used for service creation.
<b>Action</b>	Contact Software AG Global Support.
<b>PLSOBEE0010</b>	<b>A mismatch was found between source details and source annotation; class ({0}) has annotation, but source details have no element: {1}</b>
<b>Explanation</b>	The source details and source annotation do not match because the annotation service does not have an entry in the source details. This could indicate a problem in the Application Platform project preparation.
<b>Action</b>	Contact Software AG Global Support.

<b>PLSOBEE0011</b>	<b>Improper initialization using IS Service({0}), authz service ({1}), user({2}), cannot use null IS Service reference.</b>
<b>Explanation</b>	The initialization failed because the Metadata Extender did not find one or more elements. The element may be unavailable only for a short period.
<b>Action</b>	Try a subsequent invocation.
<b>PLSOBEE0012</b>	<b>Unable to initialize Bundle Tracker for Application Platform extender; caught this: type ({0}), msg({1})</b>
<b>Explanation</b>	This is an internal bundle initialization error. The bundle tracker that monitors user bundles for IS service metadata files could not be initialized correctly due to the specified error.
<b>Action</b>	Contact Software AG Global Support.
<b>PLSOBEE0013</b>	<b>PackageInstaller cannot write IS package zip into replicate directory ({0}); caught: type({1}), msg({2})</b>
<b>Explanation</b>	The PackageInstaller failed to put the package Zip file into the IS installation. This can be caused by the permission configuration on the file system.
<b>Action</b>	Verify that the directory permissions on the file system allow this operation.
<b>PLSOBEE0014</b>	<b>An attempt to extract the file ({0}) from the Jar file failed; caught: type({1}), msg({2})</b>
<b>Explanation</b>	The IS package Zip file could not be extracted from the Application Platform extender bundle.
<b>Action</b>	Contact Software AG Global Support.
<b>PLSOBEE0015</b>	<b>PackageInstaller cannot obtain a reference to Bundle Context after waiting {0} {1}; caught: type({2}), msg({3})</b>
<b>Explanation</b>	A problem was encountered while waiting for the extender bundle context.
<b>Action</b>	Contact Software AG Global Support.
<b>PLSOBEE0016</b>	<b>An attempt to invoke the IS service ({0}) failed; caught: type({1}), msg({2})</b>
<b>Explanation</b>	The Application Platform Package Installer failed to invoke the IS service(s), which are required for installation.
<b>Action</b>	Contact Software AG Global Support.

---

<b>PLSOBEE0017</b>	<b>IS Service({0}) returned NULL IData</b>
<b>Explanation</b>	The Application Platform Package Installer received a null result from the IS service.
<b>Action</b>	Contact Software AG Global Support.
<b>PLSOBEE0018</b>	<b>Improper initialization using IS Service({0}), authz service ({1}), user({2}), cannot use null authorization service reference.</b>
<b>Explanation</b>	The Metadata Extender could not find one or more expected elements. The elements may be unavailable only for a short period.
<b>Action</b>	Try a subsequent invocation.
<b>PLSOBEE0019</b>	<b>Improper initialization using IS Service({0}), authz service ({1}), user({2}), cannot use null/empty user ID.</b>
<b>Explanation</b>	The Metadata Extender could not find one or more expected elements. The elements may be unavailable only for a short period.
<b>Action</b>	Try a subsequent invocation.
<b>PLSOBEE0020</b>	<b>Unable to load class for service: {0}, from bundle BSN/ID: {1}/{2}, IS package: {3}</b>
<b>Explanation</b>	An interface named for exposure as an IS service could not be found. This means that the .class file for the interface could not be found.
<b>Action</b>	Verify that the fully qualified path to the interface is present in the classpath and that it is spelled correctly.
<b>PLSOBEE0022</b>	<b>Unable to load {0} bundle with state: {1}. Details: {2}</b>
<b>Explanation</b>	Application Platform was unable to access the bundle because of its state.
<b>Action</b>	Contact Software AG Global Support.
<b>PLSOBEE0023</b>	<b>Unable to remove IS services representing method {0} from the {1} class, in IS package {2}; caught this: type ({3}), msg({4})</b>
<b>Explanation</b>	Failed to remove the IS services that represent the method. The problem may originate in the IS service creation, or in the preparation of the IS pipeline used for service creation.
<b>Action</b>	Contact Software AG Global Support.

**PLSOBEE0024**      **Unable to create Integration Server client bindings for annotated OSGi service(s) in bundle {0}.**

**Explanation**      The generated project bundle is missing its OSGi manifest headers.

**Action**            Verify the project bundle's META-INF/MANIFEST.MF file is valid for the App Platform project bundle.

**PLSOBEE0025**      **The project bundle containing service class {0} is missing its gatewayMetadata.xml file.**

**Explanation**      A special metadata file is created and inserted in a project bundle if the bundle contains App Platform services when it's published into the server runtime container. This file is missing or corrupted.

**Action**            Review the Integration Server's OSGi server logs for errors. If the bundle is created using the Asset Build Environment (ABE) product, please review the configuration settings and inspect ABE logs for errors.

**PLSOBEE0026**      **The project bundle containing service class {0} is missing its Integration Server package annotation.**

**Explanation**      App Platform service implementations which are exposed to the Integration Server, must include the @ExposeToIS class annotation with packageName attribute set to a valid Integration Server package.

**Action**            Verify the source file is properly annotated and the package name is defined in the gatewayMetadata.xml file included in the deployed project bundle.

**PLSOBEE0027**      **Metadata mismatch for App Platform service class {0}'s {1} method. The number of parameters detected in the class ({2}) does not match the number defined in the gatewayMetadata.xml file ({3}).**

**Explanation**      The project bundle's META-INF/gatewayMetadata.xml file's metadata does not match the method signature of the currently deployed service.

**Action**            Rebuild and deploy the project bundle.

**PLSOBEE0028**      **Exception while introspecting App Platform service class {0}. Details: {1}**

**Explanation**      When an App Platform service contains complex request or response messages, Java Bean Introspection is used to analyze the class types in order to produce the necessary metadata to marshal the data to and from the Integration Server.

**Action**            Review the class and ensure it is a proper Java Bean.

<b>PLSOBEE0029</b>	<b>Illegal use of App Platform services with a recursive data model. Affected class: {0}.</b>
<b>Explanation</b>	App Platform service implementations with recursive object models are not supported.
<b>Action</b>	App Platform service implementations with recursive object models are not supported.
<b>PLSOBEI0001</b>	<b>An exception was caught while invoking IS service {0} with user {1}: {2}</b>
<b>Explanation</b>	The designated service could not be invoked.
<b>Action</b>	Check the exception message for more information about the cause of the failure. Attempt the same invocation with the service invoker using different user IDs. If one attempt succeeds, the failures may be ignored.
<b>PLSOBEW0021</b>	<b>Cannot change user ID to null/empty value, keeping previous value {0}</b>
<b>Explanation</b>	The default user ID was dynamically updated with an inappropriate value.
<b>Action</b>	Provide a non-empty value string.
<b>PLSSECE0000</b>	<b>Unauthorized! Method {0} execution not allowed</b>
<b>Explanation</b>	The specified method cannot be invoked by the currently logged user. The method has the @DenyAll annotation specified directly on it, or inherited from the type level.
<b>Action</b>	Change the method access security level by removing @DenyAll annotation and specifying the users that are allowed by using the @RolesAllowed annotation.
<b>PLSSECE0001</b>	<b>Unauthorized! Methods in type {0} cannot be invoked!</b>
<b>Explanation</b>	The methods in the specified class cannot be invoked because the @DenyAll annotation is invoked on them.
<b>Action</b>	Remove the @DenyAll annotation from the class level. Optionally, also specify explicitly the user roles that are allowed.
<b>PLSSECE0002</b>	<b>Unauthorized! User not in allowed roles to execute this method</b>
<b>Explanation</b>	The user that is currently logged in does not belong to the list of allowed roles to execute this method.
<b>Action</b>	Login as a user with a role that belongs to the list of allowed roles to execute the method and call the method again.

<b>PLSSECE0003</b>	<b>No valid authenticated subject found! An authenticated user is required when invoking this method.</b>
<b>Explanation</b>	In order to access this service method, you must be logged in with a user that has a valid account for the connected runtime.
<b>Action</b>	Ensure that the logged in user account has access rights to invoke the methods in the service.
<b>PLSSECE0005</b>	<b>Error injecting SecurityContext instance in field {0}! Reason: {1}</b>
<b>Explanation</b>	An error occurred while injecting an instance of the SecurityContext class into the field with the same type in the POJO service.
<b>Action</b>	Review the error log for more details about this error.
<b>PLSSECW0004</b>	<b>No security annotations found for @Secure annotated service type!</b>
<b>Explanation</b>	The service class with @Secure annotation does not contain any expected security annotations. Unless runtime authorization checks are performed, invocations will be allowed for all service methods.
<b>Action</b>	Ensure that correct authorization checks are performed for the methods in this service.
<b>PLSSISE0000</b>	<b>Error creating filter {0} IS_Transport login realm delegate may not be initialized properly! Reason: {1}</b>
<b>Explanation</b>	An error occurred while initializing the OSGi filter in order to obtain the IS_Transport Login Realm service.
<b>Action</b>	Review error logs for more information about this error.
<b>PLSUPGC0006</b>	<b>Unexpected error while verifying product source directory: {0}. Cause: {1}</b>
<b>Explanation</b>	The migration utility encountered an unexpected error.
<b>Action</b>	Confirm that the source directory path contains a product installation.
<b>PLSUPGE0002</b>	<b>App Platform server migration did not complete successfully. Cause: {0}</b>
<b>Explanation</b>	An error occurred while executing the server migration steps.
<b>Action</b>	Contact Software AG Global Support.

---

<b>PLSUPGE0003</b>	<b>Unable to determine App Platform product version for source installation using this product property file. {0}</b>
<b>Explanation</b>	The migration utility requires a product source version in order to determine the required migration tasks.
<b>Action</b>	Provide the product version by using the migration utility "-srcVersion" parameter.
<b>PLSUPGE0005</b>	<b>No servers are installed in this directory. {0}</b>
<b>Explanation</b>	To be rendered as a valid path, the specified directory must contain a 'profiles' directory, which contains one or more servers.
<b>Action</b>	Select another directory path that contains server profiles.
<b>PLSUPGE0007</b>	<b>Please ensure the current working directory contains the App Platform migrate.sh bat script.</b>
<b>Explanation</b>	The migration utility locates required components by using relative paths, which are offset from the current working directory.
<b>Action</b>	Update the working to a directory that contains the required Application batch script.
<b>PLSUPGE0008</b>	<b>The product properties file does not exist. {0}</b>
<b>Explanation</b>	Application Platform uses the product properties file in order to automatically detect the product version during migration.
<b>Action</b>	Ensure that the directory path is correct and it contains the product properties file.
<b>PLSUPGE0009</b>	<b>Unable to locate version string in product properties file.</b>
<b>Explanation</b>	The Application Platform migration script uses the product property file to detect the version, installed in the specified directory.
<b>Action</b>	Verify that the directory path is correct.
<b>PLSUPGE0011</b>	<b>Overinstall is not supported. The source and destination paths must be different.</b>
<b>Explanation</b>	The migration script can be run only in for side-by-side upgrade.
<b>Action</b>	Ensure that the source and the destination directories are different.
<b>PLSUPGE0012</b>	<b>Error resolving canonical path for directory: {0}. Cause: {1}</b>
<b>Explanation</b>	Application Platform uses relative paths to locate key directories. An error occurred while resolving a path to its canonical form. For example, this can happen when the parent path references have been removed ( ../ ).
<b>Action</b>	Verify that the directory path exists.

<b>PLSUPGE0021</b>	<b>Error copying project file "{0}" to destination directory: {1}. Cause: {2}</b>
<b>Explanation</b>	An error occurred while migrating the file to the destination directory.
<b>Action</b>	Copy the file manually.
<b>PLSUPGI0022</b>	<b>{0} files NOT migrated due to errors.</b>
<b>Explanation</b>	An error occurred while migrating some the files.
<b>Action</b>	Review the migration log in the installation directory's 'install/logs' folder to determine which project files were affected. Copy the required files manually.
<b>PLSUPGI0029</b>	<b>Project bundle files</b>
<b>PLSUPGI0030</b>	<b>{0} existing project bundles copied to destination (files from the destination were copied to the archive directory before overwriting).</b>
<b>Explanation</b>	The target installation contained project bundle file(s), and these files were replaced with the migrated ones. Copies of these files may be found in the archive directory under the common/migrate/ directory.
<b>Action</b>	No action necessary.
<b>PLSUPGW0010</b>	<b>Unable to detect product version for the specified directory. Cause: {0}</b>
<b>Explanation</b>	Application Platform was unable to determine the version of the installation path that was provided. This may have happened because the 'install/products' directory was deleted.
<b>Action</b>	Enter the version manually.
<b>PLSUPGW0017</b>	<b>These instances are missing in the destination installation. {0}</b>
<b>Explanation</b>	The source installation contains server instances that do not exist in the target installation. These servers will not be migrated for Application Platform.
<b>Action</b>	If required, create the missing server instances. Otherwise, proceed with the migration.
<b>PLSUPGW0019</b>	<b>Project file "{0}" overwritten in destination directory: {1}</b>
<b>Explanation</b>	The migration utility detected that a project file already exists in the destination directory. The contents are not overwritten.
<b>Action</b>	If you require to replace the old file with the new one, review the new file and copy it manually. This will overwrite the old file in the destination directory.

---

<b>PLSUPGW0028</b>	<b>Unable to archive existing files. Cause: {0}</b>
<b>Explanation</b>	If possible, the migration utility saves existing files before overwriting with migrated versions.
<b>Action</b>	No action is required. The migration will progress normally. However, the original files will not be retained.
<b>PLSUPGW0031</b>	<b>No zip entries detected in project file "{0}".</b>
<b>Explanation</b>	This suggests the project file was either an empty archive or its contents could not be migrated.
<b>Action</b>	Verify the file is a valid zip archive and copy it manually to the destination directory if necessary.
<b>PLSUPGW0032</b>	<b>Bundle {0} is missing its manifest.</b>
<b>Explanation</b>	OSGi bundles require manifests in the META-INF/MANIFEST directory of the archive. The migration tool will skip this bundle.
<b>Action</b>	No action required.
<b>PLSUPGW0033</b>	<b>Project bundle {0} contains a package {1} with import version range {2} that must be upgraded manually.</b>
<b>Explanation</b>	The migration utility has detected a customer project bundle which has a dependency to a different version of the App Platform SDK.
<b>Action</b>	Please update the source project to use this new SDK version.
<b>PLSWRPE0002</b>	<b>Unable to invoke service {0} after trying up to {1} principal names; caught: {2}</b>
<b>Explanation</b>	Invoking the service failed. This can be caused by a credentials issue, in which none of the principals associated with the current session was allowed to invoke the designated service. Another possible cause is a problem with the input parameters.
<b>Action</b>	Check the error logs for more details about this error. If the problem is caused by an authentication or authorization error, then search the log for more details about which principal names were successful or not. Verify that you are using a valid Integration Server user ID.
<b>PLSWRPE0003</b>	<b>An exception was caught while marshalling input object to IData for service {0}; {1}</b>
<b>Explanation</b>	The conversion of input bean to IData for the designated service failed with an exception.
<b>Action</b>	Check the exception message for more information about this error.

**PLSWRPE0004**      **An exception was caught while unmarshalling IData to output object for service {0}: {1}**

**Explanation**      The conversion of IData to output bean for the designated service failed with an exception.

**Action**            Check the exception message for more information about this error.

**PLSWRPE0005**      **Input argument to ServiceWrapper.invoke() needs 'InputData' annotation.**

**Explanation**      The invoke method requires specific type characteristics.

**Action**            Use a different input type, or add the required annotation.

**PLSWRPE0006**      **Return type for ServiceWrapper.invoke() needs 'OutputData' annotation**

**Explanation**      The invoke method requires specific output type characteristics.

**Action**            Use a different return type, or add the required annotation.

**PLSWRPE0007**      **Unable to fill data for key {0} with parameter ({1}), dim>1 not yet supported**

**Explanation**      This is a temporary shortcoming in the implementation.

**Action**            Contact Software AG Global Support.

**PLSWRPE0008**      **Unable to fill object {0} for key ({1}), dim>1 not yet supported**

**Explanation**      This is a temporary shortcoming in the implementation.

**Action**            Contact Software AG Global Support.

**PLSWRPE0010**      **An exception was caught while attempting to identify the Subject for the current session in order to invoke IS service {0}; current user is identified by {1}, exception: {2}**

**Explanation**      Identifying the Subject for the current session failed with an exception. This can indicate a problem with the Authorization Service in the Software AG Common Platform.

**Action**            Contact Software AG Global Support.

**PLSWRPE0012**      **ServiceWrapper cannot work with NULL return type.**

**Explanation**      An attempt was made for ServiceWrapper to work with a NULL return type. This can be caused by a problem with the Authorization Service source code generation.

**Action**            Contact Software AG Global Support.

<b>PLSWRPI0009</b>	<b>An exception was caught while invoking IS Service ({0}) with user ({1}): {2}</b>
<b>Explanation</b>	Invoking the designated service failed with an exception. Check the exception message for more information about the cause of failure.
<b>Action</b>	Attempt the same invocation with the service invoker using different user IDs. If one attempt succeeds, the failures may be ignored.



# 5 Business Rules Messages

---

**AbstractMainPage\_projectOutdatedError – The project is outdated. Please upgrade to the current version.**

**Explanation** The version of the rule project to be exported is outdated.

**Action** Right-click the rule project in the Rules Explorer view and select Upgrade project.

**AbstractMainPage\_serverVersionOutdated – The server version is outdated. Please upgrade the server to the current version.**

**Explanation** The version of the rules environment on the server is older than the version of the rule project to be exported.

**Action** Upgrade the server.

**ActionSelectionWizardPage\_InputOrOutputDataModelIsMissing – The selected action is invalid, because one of its data models is missing.**

**Explanation** An action can have multiple data models. The data model files are referenced in the xml of the action. If one or more of the data models are missing, this error occurs. Action data models are not shown in the Rules Explorer view.

**Action** Clean all projects in Software AG Designer. If that did not help and the data models are not shown in the Navigator view, the action might be corrupted. Try to create an action that uses the same type of data models. If this should fail, please contact your system administrator.

**EditorProjectToNewComposite\_ErrorDescription – Could not open the editor:**

**Explanation** There is an asset in the specified rule project that has a version newer than the version of the installed Rules Development plugin.

**Action** Update the Rules Development plugin of Software AG Designer.

**EditorProjectToNewComposite\_ErrorMessage – The rule project "{0}" was created with a newer version of Software AG Designer ({1}). Please upgrade the Rules Development feature.**

**Explanation** There is an asset in the specified rule project that has a version newer than the version of the installed Rules Development plugin.

**Action** Update the Rules Development plugin of Software AG Designer.

**EditorUpgradeComposite\_ErrorMessage – The rule project "{0}" is outdated.**

**Explanation** The rule project "{0}" is outdated. It needs to be updated first.

**Action** Right-click the rule project in the Rules Explorer view and select "Update".

**EditorUtility\_file\_must\_not\_be\_null – File must not be null**

**Explanation** An error occurred while opening the editor for the file.

**Action** Try to refresh your rule project. See error log for additional information.

**EditorUtility\_no\_active\_WorkbenchPage – No active workbench page**

**Explanation** No active workbench could be obtained for opening the file.

**Action** Try to restart Software AG Designer. See log for additional errors.

**EditorUtility\_no\_editorInput – Could not get an editor input for the given element**

**Explanation** No editor input could be created for the file.

**Action** Check, if the file is corrupt. See log for detailed information about the error.

**EventModelSourceSelectionPage\_FileNotFoundError – There is no file at the specified location.**

**Explanation** In the textbox on page two of the New Event Model wizard, the given location for the schema file is invalid.

**Action** Use the browse button on the same page to search for an existing schema file, or enter a valid location for a schema file.

**EventModelSourceSelectionPage\_File\_Not\_Parsed – Error while importing Event Type. File could not be parsed.**

**Explanation** Problem while trying to parse an NSRecord from the chosen XSD.

**Action** Make sure the chosen file is an event type (payload), or select a different file.

**EventModelSourceSelectionPage\_Stream\_Null – Error while retrieving contents of Event Type.**

<b>Explanation</b>	NSRecords could not be created from the given schema file.
<b>Action</b>	Make sure the selected schema file is a valid event type (payload), or select a different file.

**ExportWizard\_ExportFailedMessage – Export failed**

<b>Explanation</b>	Export failed.
<b>Action</b>	Please consult the log file for further information.

**ExportWizard\_ExportFailedReason – Could not export project. Make sure you have selected the right server and that it is configured correctly. See documentation, the Eclipse Error Log and check the IS Server log for more detailed information about the error.**

<b>Explanation</b>	The rule project could not be exported.
<b>Action</b>	Make sure that you have selected the right server and that it is configured correctly. For more information, consult the product documentation and the Eclipse Error Log.

**ISExporter\_ServerNotFound – Couldn't find server: "{0}"**

<b>Explanation</b>	The specified Integration Server could not be found.
<b>Action</b>	In Software AG Designer preferences, check if the selected Integration Server is available and configured properly.

**MWS\_InternalError An internal server error occurred. To resolve the problem please check the My webMethods Server log.**

<b>Explanation</b>	This happens when an error in Rule Management Console occurs.
<b>Action</b>	Check the Eclipse and MWS log for more information.

**MainIsExportPage\_pingServiceNotExisting – Unable to contact the Rule engine server.**

<b>Explanation</b>	An error occurred while invoking the ping service on the Integration Server.
<b>Action</b>	Try again. Check the versions of Software AG Designer and the Integration Server. Check connection.

**MainMwsImportPage\_ProjectToNewErrorMessage – The remote rule project "{0}" was created with a newer version of Software AG Designer ({1}). Please upgrade the Rules Development feature.**

<b>Explanation</b>	Cannot import a rule project that was created with a newer version of the Rules Development feature.
<b>Action</b>	Upgrade the Software AG Designer plugins.

**MainMwsImportPage\_WillUpgradeImportedProjectInfo – Outdated rule projects will be automatically upgraded to the current version of the Rules Development feature.**

**Explanation** The rule project in the My webMethods Server repository is outdated. It will be updated in a temporary location before it is copied into the workspace.

**Action** n/a

**MetaphorCorrectionProcessor\_error\_quickassist\_message – An error occurred while computing quick assists. Check log for details.**

**Explanation** An error occurred while computing quick assists.

**Action** Check log for details.

**MetaphorCorrectionProcessor\_error\_quickfix\_message – An error occurred while computing quick fixes. Check log for details.**

**Explanation** An error occurred while computing quick fixes.

**Action** Check log for details.

**MetaphorCorrectionProcessor\_error\_status – Exception while processing quick fixes or quick assists**

**Explanation** An error occurred while computing quick fixes or quick assists.

**Action** Check log for details.

**MetaphorSuppressWarningsProposal\_Error\_Msg – An exception occurred while applying the quick fix**

**Explanation** An error occurred while applying the quick fix.

**Action** Please see the dialog and/or error log for additional information on the error.

**NewEventModelWizard\_ErrorCreatingEventModel – Error creating event model**

**Explanation** An error occurred while importing the event type .xsd-file. NSRecord (event model) files may have not been created.

**Action** Try again, or try another schema file. Refer to the logged exception.

**ParameterSelectionComposite\_SelectAtLeastOne\_Error – Select at least one data model for a parameter.**

**Explanation** No data model is selected as an input or output parameter.

**Action** On the current wizard page, select a data model and move it to the right to make it available as parameter.

**Resources\_OutOfSyncResources\_Msg – Some resources are out of synch**

**Explanation** One or more resources are out of synch with the file system. They need to be refreshed inside Software AG Designer.

**Action** Please refresh your rule project.

**Resources\_OutOfSync\_Msg – Resource "{0}" is out of synch with the file system**

**Explanation** One or more resources are out of synch with the file system. They need to be refreshed inside Software AG Designer.

**Action** Please refresh your rule project.

**RuleFile\_ErrorParsingDTXMLForProcessingMode – Error parsing decision table XML for ProcessingModeType.**

**Explanation** An error occurred while parsing one of the selected files.

**Action** Try to deselect the files and retry your selection.

**RuleLocalLaunchRunner\_ErrorUndeploying\_Msg – An error occurred while undeploying the rule project [%s].**

**Explanation** The execution of the launch was terminated abnormally, and an attempt was made to clean up the rule project. The attempt failed.

**Action** Start Software AG Designer with -clean option. If the problem persists, send the details of this exception to your technical support.

**WOKDELE0016** Unable to invoke REST call to get Business Rules dashboard

**WOKDELI0013** Close

**WOKDELI0014** Click to view/edit decision entity

**WOKDELI0015** View/Hide

**WOKDTDE0003** Unable to retrieve Business Rules decision entity from REST service.

<b>WOKDTDE0004</b>	<b>Selected decision entity not found.</b>
<b>WOKDTDE0005</b>	<b>Rule project name not found</b>
<b>WOKDTDE0006</b>	<b>Rule decision entity name not found</b>
<b>WOKDTDI0000</b>	<b>Decision Table</b>
<b>WOKDTDI0001</b>	<b>More...</b>
<b>WOKDTDI0002</b>	<b>No Data Available</b>
<b>WOKDTDI0007</b>	<b>In Effect</b>
<b>WOKDTDI0008</b>	<b>ALWAYS</b>
<b>WOKDTDI0009</b>	<b>Inferential</b>
<b>WOKDTDI0010</b>	<b>Sequential First</b>
<b>WOKDTDI0011</b>	<b>Sequential All</b>
<b>WOKDTDI0012</b>	<b>OTHERWISE</b>
<b>WOKDTDI0013</b>	<b>Loading...</b>
<b>WOKDTSE0007</b>	<b>Unable to retrieve Business Rules decision entity from REST service.</b>

---

<b>WOKDTSI0000</b>	<b>Info</b>
<b>WOKDTSI0001</b>	<b>Processing Mode:</b>
<b>WOKDTSI0002</b>	<b>Description:</b>
<b>WOKMRIE0011</b>	<b>Operation not supported</b>
<b>Explanation</b>	The operation attempted to be executed is not supported
<b>WOKMRIE0012</b>	<b>{0} is required</b>
<b>Explanation</b>	If configuration is enabled, {0} is required
<b>WOKMRIE0016</b>	<b>The URL "{0}" is invalid</b>
<b>Explanation</b>	The URL resulting from the entered values is invalid.
<b>WOKMRII0006</b>	<b>The Integration Server is online.</b>
<b>Explanation</b>	The Integration Server is online.
<b>WOKMRII0009</b>	<b>Business verification</b>
<b>Explanation</b>	Business verification REST server configuration
<b>Action</b>	Configure here the one single REST server for doing business verification
<b>WOKMRII0010</b>	<b>Master Integration Server</b>
<b>Explanation</b>	Connection Master Integration Server (wM Business Rules)
<b>WOKMRII0013</b>	<b>The configuration is valid.</b>
<b>Explanation</b>	The configuration is valid.
<b>WOKMRII0014</b>	<b>Data provider</b>
<b>Explanation</b>	Data provider REST service configuration
<b>Action</b>	Configure here the one single REST service for the Data provider

<b>WOKMRH0015</b>	<b>Principal types</b>
<b>Explanation</b>	Principal types configuration
<b>Action</b>	Here you can configure the principal types that should be visible in the PrincipalPicker
<b>WOKMRIW0000</b>	<b>An internal error occurred</b>
<b>Explanation</b>	Integration Server URL is not accessible: {0}
<b>Action</b>	Please check specified host and port and make sure Integration Server is running.
<b>WOKMRIW0001</b>	<b>Integration Server credentials are missing.</b>
<b>Explanation</b>	Username and password are needed for authentication.
<b>Action</b>	Please provide values for username and password.
<b>WOKMRIW0002</b>	<b>Integration Server password is missing.</b>
<b>Explanation</b>	The password is needed for authentication.
<b>Action</b>	Please provide a password for the Integration Server.
<b>WOKMRIW0003</b>	<b>Integration Server host and/or port are missing.</b>
<b>Explanation</b>	A valid hostname and port are needed to access Integration Server.
<b>Action</b>	Please provide host and port to access Integration Server.
<b>WOKMRIW0005</b>	<b>The server specified is not an Integration Server</b>
<b>Explanation</b>	A server has been contacted with the information provided. However it does not seem to be an Integration Server.
<b>Action</b>	Please check whether the server specified is an Integration Server. If this is the case this warning can be ignored.
<b>WOKMRIW0008</b>	<b>Authentication failed.</b>
<b>Explanation</b>	Authentication failed with the credentials provided. Please check username and password.
<b>Action</b>	Please check username and password.

## 6 CentraSite Messages

---

**E\_assertionNotFound30000** – Signifies that a particular publisher assertion (consisting of two businessKey values, and a keyed reference with three components) cannot be identified in a save or delete operation.

**Explanation** The specified publisher assertion does not exist in the registry.

**Action** Please make sure the publisher assertion exists before deleting or updating it.

**E\_authTokenRequired10120AUTH** – The authentication token value is missing in the authInfo argument of the UDDI request.

**Explanation** The authInfo element is not present in the UDDI request. CentraSite requires the authInfo element to be present in the request with a valid authToken.

**Action** Please make sure that authInfo is present in UDDI request.

**E\_authTokenRequired10120DEF** – Signifies that an invalid authentication token was passed to an API call that requires authentication.

**Explanation** The authentication token passed is not valid.

**Action** Please fetch the authentication token using get\_authToken API and use it in the API.

**E\_authTokenRequired10120INVAUTH** – The authentication token value {0} passed in the authInfo argument of the UDDI request is not valid.

**Explanation** The authentication token passed is not valid.

**Action** Please fetch the authentication token again using get\_authToken API and use it in the API.

**E\_fatalError10500** {0}

**Explanation** Fatal error occurred while processing the request.

**Action** Please retry and make sure the UDDI request is valid.

**E\_fatalError10500APPDOWN – UDDI application not properly initialized. Please try restarting the CentraSite server.**

**Explanation** UDDI application received UDDI API calls before the UDDI web application initialized properly.

**Action** Restart the CentraSite server.

**E\_fatalError10500CUSTOWN – Custody and Ownership Transfer API calls are not supported when security policy is Deactivated**

**Explanation** CentraSite needs a security policy to be activated for processing the Custody and Ownership Transfer API.

**Action** Please activate a security policy.

**E\_fatalError10500INFOSEL – Attribute infoSelection is not present in request.**

**Explanation** The get\_registeredInfo API requires the infoSelection attribute. If it is not present in the request then this error will occur.

**Action** Please make sure the infoSelection attribute is present in the get\_registeredInfo request.

**E\_fatalError10500INVFINDGET – Invalid find\_xx or get\_xx api specified in the subscriptionFilter**

**Explanation** The subscriptionFilter does not contain the valid UDDI v3 subscription filter.

**Action** Please make sure the subscription filter in the save\_subscription request is valid.

**E\_fatalError10500KREFNATB – KeyedReference does not contain required attribute.**

**Explanation** The KeyedReference should contain the keyValue attribute.

**Action** Please make sure the keyedReference in the request has attribute keyValue.

**E\_fatalError10500MISCFAT – Saving subscription failed due to internal registry error.**

**Explanation** Internal registry error.

**Action** Please retry the request.

**E\_fatalError10500MSE – Search limit exceeded, maximum allowed is {0}. Contact node operator to increase the search limit.**

**Explanation** Maximum search limit reached.

**Action** Please reduce the number of search keys in the inquiry request or increase the search limit via the System Management Hub.

**E\_fatalError10500PERF – Performance metrics with key {0} cannot be saved. Please make sure Performance Log is enabled in SMH.**

**Explanation** The user is trying to save performance metrics, but the performance log is disabled in SMH. Performance metrics will be saved only if the performance log is enabled in SMH.

**Action** Please make sure the performance log is enabled in SMH.

**E\_fatalError10500SUBKEXP – The subscription with subscriptionKey {0} has expired. Please renew this subscription.**

**Explanation** The subscription has expired as the specified expiration date has been reached.

**Action** Please renew the subscription by saving it with a new expiration date.

**E\_invalidCombination40500QUA – The combination of Qualifiers is not allowed**

**Explanation** Invalid find qualifier combinations were found in the request.

**Action** Please make sure the combination of find qualifiers present in the inquiry request is valid. The invalid combinations are: andAllKeys, orAllKeys and orLikeKeys are mutually exclusive; sortByNameAsc and sortByNameDesc are mutually exclusive; sortByDateAsc and sortByDateDesc are mutually exclusive; combineCategoryBags, serviceSubset and bindingSubset are mutually exclusive; exactMatch and approximateMatch are mutually exclusive; exactMatch and caseInsensitiveMatch are mutually exclusive; binarySort and UTS-10 are mutually exclusive, as are all collation algorithm tModels with each other; diacriticSensitiveMatch and diacriticInsensitiveMatch are mutually exclusive; exactMatch and diacriticInsensitiveMatch are mutually exclusive; caseSensitiveSort and caseInsensitiveSort are mutually exclusive; caseSensitiveMatch and caseInsensitiveMatch are mutually exclusive.

**E\_invalidCompletionStatus30100 – {0} is not a valid completion status.**

**Explanation** An invalid value was passed for completion status argument. Valid completion status are status:complete, status:fromKey\_incomplete, status:toKey\_incomplete and status:both\_incomplete.

**Action** Please provide a proper completion status.

**E\_invalidKeyPassed10210 – No matching key found in the registry for {0}.**

**Explanation** CentraSite does not contain any UDDI entity with the key specified in the UDDI request.

**Action** Please make sure the key specified in the request is valid.

**E\_invalidKeyPassed10210BEBEK – Could not find the business entity corresponding to the business key.**

**Explanation** CentraSite does not contain any business entity with the key specified in the UDDI request.

**Action** Please make sure the business key specified in the request is valid.

**E\_invalidKeyPassed10210BEBK – Could not find the business service corresponding to the binding key {0}.**

**Explanation** CentraSite does not contain a business service corresponding to the service key specified in the binding template.

**Action** Please make sure the service key specified in the request is valid.

**E\_invalidKeyPassed10210BEMAT – No businessEntity in the UDDI registry matched the key {0}.**

**Explanation** CentraSite does not contain any business entity with the key specified in the UDDI request.

**Action** Please make sure the business key specified in the request is valid.

**E\_invalidKeyPassed10210BKBE – Tried to get a businessEntity with key {0}, but key did not match with any existing businessEntities.**

**Explanation** CentraSite does not contain any business entity with the business key specified in the UDDI request.

**Action** Please make sure the business entity with the specified business key exists in CentraSite.

**E\_invalidKeyPassed10210BKINV – BusinessKey invalid.**

**Explanation** The BusinessKey specified in the request is invalid.

**Action** Please make sure the specified businessKey is valid.

**E\_invalidKeyPassed10210BKMAT – No bindingTemplate in the UDDI registry matched the key {0}.**

**Explanation** CentraSite does not contain a binding template with the key specified in the UDDI request.

**Action** Please make sure the binding key specified in the request is valid.

**E\_invalidKeyPassed10210BSMAT – No businessService in the UDDI registry matched the key {0}.**

**Explanation** CentraSite does not contain a business service with the key specified in the UDDI request.

**Action** Please make sure the service key specified in the request is valid.

**E\_invalidKeyPassed10210BSNE – A businessService with key {0} does not exist.**

**Explanation** CentraSite does not contain a business service with the key specified in the UDDI request.

**Action** Please make sure the service key specified in the request is valid.

**E\_invalidKeyPassed10210BSNF – Could not find the businessService corresponding to the service key {0}**

**Explanation** CentraSite does not contain a business service corresponding to the service key specified in the binding template.

**Action** Please make sure the service key specified in the request is valid.

**E\_invalidKeyPassed10210BT – The bindingKey of the bindingTemplate to save does not match any existing bindingTemplate in the UDDI registry.**

**Explanation** CentraSite does not contain a binding template with the key specified in the UDDI request.

**Action** Please make sure the binding key specified in the request is valid.

**E\_invalidKeyPassed10210BTNF – Could not find the binding Template corresponding to the binding key {0}**

**Explanation** CentraSite does not contain a binding template with the key specified in the UDDI request.

**Action** Please make sure the binding key specified in the request is valid.

**E\_invalidKeyPassed10210BTSK – The bindingTemplate to save does not contain a serviceKey.**

**Explanation** The binding template to be saved does not contain the service key required for this binding template. The service key has to be specified when saving a binding template.

**Action** Please specify a valid service key in the UDDI request.

**E\_invalidKeyPassed10210CAT – Invalid tModelKey in categoryBag.**

**Explanation** The category bag should contain keyedReference/KeyedReferenceGroups with valid values for tModelKey and KeyValue.

**Action** Please specify valid values for tModelKey/KeyValue in the category bag.

**E\_invalidKeyPassed10210DBE – Tried to delete a businessEntity with key {0}, but key did not match with any existing businessEntities.**

**Explanation** CentraSite does not contain any business entity with the business key specified in the delete request.

**Action** Please make sure the business key specified in the request is valid.

**E\_invalidKeyPassed10210DEF – Signifies that the uuid\_key value passed did not match with any known key values.**

**Explanation** CentraSite does not contain any UDDI entity with the key specified in the UDDI request.

**Action** Please make sure the key specified in the request is valid.

**E\_invalidKeyPassed10210DELSUB – Tried to delete a subscription with key {0}, but key did not match with any existing subscriptions.**

**Explanation** CentraSite does not contain any subscription with the key specified in the delete request.

**Action** Please make sure the key specified in the request is valid.

**E\_invalidKeyPassed10210EMTTMBAG – Tmodel bag is empty**

**Explanation** TModelBag cannot be empty, but the UDDI request contains an empty tModelBag.

**Action** Please make sure tModelBag contains the required values.

**E\_invalidKeyPassed10210FRMK – No businessEntity in the UDDI registry matched the fromKey {0}**

**Explanation** The fromKey specified in the add\_publisherAssertion request is either invalid, or no business entity matched the fromKey.

**Action** Please make sure the fromKey specified in the request is valid.

**E\_invalidKeyPassed10210HIDTM – Tried to delete a tModel with key {0} which is not hidden.**

**Explanation** Hidden Tmodels cannot be deleted.

**Action** Hidden tModels cannot be deleted. Please update the tModel and delete it.

**E\_invalidKeyPassed10210IBAG – Invalid tModelKey in identifierBag.**

**Explanation** The identifier bag should contain keyedReference/KeyedReferenceGroups with valid values for tModelKey and KeyValue.

**Action** Please specify valid values for tModelKey/KeyValue in the identifier bag.

**E\_invalidKeyPassed10210INVKEY – The Key {0} is invalid.**

**Explanation** The specified key is not valid.

**Action** Please make sure the key is valid according to the UDDI standard.

**E\_invalidKeyPassed10210INVTMK – Invalid tModelKey {0}.**

**Explanation** CentraSite does not contain a TModel with the key specified in the UDDI request.

**Action** Please specify a valid tModelKey in the UDDI request.

**E\_invalidKeyPassed10210KBAGK – key {0} passed in the key bag does not match any businessEntity or tModel.**

**Explanation** CentraSite does not contain a business entity or tModel with the key specified in key bag of the discard\_transferToken request.

**Action** Please specify a valid business key or tModel key in the key bag.

**E\_invalidKeyPassed10210KREF – KeyedReference should be passed !**

**Explanation** The publisher assertion should contain a keyedReference and it is missing in the UDDI request.

**Action** Please specify a KeyedReference for the publisher assertion.

**E\_invalidKeyPassed10210MITS – Multiple instances of the same {0} {1} were passed.**

**Explanation** Keys should be unique for all UDDI entities. The UDDI request contains an existing UDDI entity key.

**Action** Please provide a unique key for the UDDI entity.

**E\_invalidKeyPassed10210MREF – The tModelKey cannot have multiple references to be deleted.**

**Explanation** Multiple references of a tModelKey were specified in the UDDI request.

**Action** Please make sure that a single reference exists for a single tModelKey in the request.

**E\_invalidKeyPassed10210NBE – Tried to update a businessEntity with key {0}, but no businessEntity in the UDDI registry matched the key.**

**Explanation** CentraSite does not contain any business entity with the business key specified in the save request.

**Action** Please make sure the business key specified in the request is valid.

**E\_invalidKeyPassed10210NULTM – Tried to delete a tModel with key, but the key did not match with any existing tModel or it is null.**

**Explanation** CentraSite does not contain any TModel with the key specified in the delete request.

**Action** Please make sure the key specified in the request is valid.

**E\_invalidKeyPassed10210OPINFMAT – No OperationalInfo in the UDDI registry matched the key {0}.**

**Explanation** The operational info cannot be found for the given key.

**Action** Please make sure the key specified in the request is valid.

**E\_invalidKeyPassed10210PAINV – The Publisher Assigned Key {0} is not a valid key.**

**Explanation** The key provided for the UDDI entity by the publisher is not valid.

**Action** Please specify the key according to the UDDI standard

**E\_invalidKeyPassed10210PANAL – The Publisher Assigned Key is not allowed.**

**Explanation** The user is not allowed to assign keys for the UDDI entity (CentraSite object).

**Action** Save the UDDI entity without assigning a key to it.

**E\_invalidKeyPassed10210SUBMAT – No subscription in the UDDI registry matched the key {0}.**

**Explanation** CentraSite does not contain any subscription with the key specified in the delete request.

**Action** Please make sure the key specified in the request is valid.

**E\_invalidKeyPassed10210SUBNE – The subscription having subscriptionKey as {0} does not exist.**

**Explanation** CentraSite does not contain any subscription with the key specified in the delete request.

**Action** Please make sure the key specified in the request is valid.

**E\_invalidKeyPassed10210TMIBK – Invalid tModelKey in tModelInstanceInfo for BindingKey {0}.**

**Explanation** The specified binding template does not contain a valid tModelKey in tModelInstanceInfo.

**Action** Please make sure the tModelKey specified in tModelInstanceInfo of the binding template is valid.

**E\_invalidKeyPassed10210TMKN – TModelvalue should not be null !**

**Explanation** The key value of KeyedReference does not contain a valid value.

**Action** Please specify a valid key value for the KeyedReference.

**E\_invalidKeyPassed10210TMKNF – No matching tmodelkey was found. Please check that the tModelKey is of relationship type.**

**Explanation** CentraSite does not contain a tModel with the key specified in the UDDI request.

**Action** The tModelKey of the keyedReference in the publisher assertion must be the key of the uddi-org:relationships tModel.

**E\_invalidKeyPassed10210TMKREF – tModelKey not specified in one of the keyedReferenceGroup.**

**Explanation** The tModel key has to be specified for all KeyedReferenceGroups.

**Action** Please specify a valid tModel key for all KeyedReferenceGroups.

**E\_invalidKeyPassed10210TMMAT – No tModel in the UDDI registry matched the key {0}.**

**Explanation** CentraSite does not contain a tModel with the key specified in the UDDI request.

**Action** Please specify a valid tModel key in the UDDI request.

**E\_invalidKeyPassed10210TMNF – The specified tModelkey {0} cannot be found.**

**Explanation** CentraSite does not contain a TModel with the key specified in the UDDI request.  
**Action** Please specify a valid tModelKey in the UDDI request.

**E\_invalidKeyPassed10210TOK – No businessEntity in the UDDI registry matched the toKey {0}**

**Explanation** The toKey specified in the add\_publisherAssertion request is either invalid or no business entity matched the toKey.  
**Action** Please make sure the toKey specified in the request is valid.

**E\_invalidKeyPassed10210USUBK – Tried to update a subscription with key {0}, but no subscription in the UDDI registry matched the key.**

**Explanation** CentraSite does not contain any subscription with the key specified in the delete request.  
**Action** Please make sure the key specified in the request is valid.

**E\_invalidKeyPassed10210UTM – Tried to update a TModel with key {0}, but no TModel in the UDDI registry matched the key.**

**Explanation** CentraSite does not contain a TModel with the key specified in the UDDI request.  
**Action** Please specify a valid tModelKey in the UDDI request.

**E\_invalidProjection20230 – No businessService with service key {0} exists in the UDDI registry.**

**Explanation** CentraSite does not contain a business service with the key specified in the UDDI request.  
**Action** Please make sure the service key specified in the request is valid.

**E\_invalidTime40030 Invalid time period specified or the date/time pair is invalid.**

**Explanation** The date/time provided in the UDDI request is not valid.  
**Action** Please provide the date/time in the format specified in UDDI specification.

**E\_invalidValue20200EXPAFTDAT – The specified expiresAfter date value is incorrect**

**Explanation** The specified expiresAfter value for the subscription is not in the proper format.  
**Action** Please provide expiresAfter in the proper format.

**E\_invalidValue20200EXPAFTVAL – expiresAfter has a value older than the current date/time.**

**Explanation** The expiresAfter element of the subscription denotes when the subscription will expire. However, the value specified in the expiresAfter element is older than the current time.

**Action** Please provide a newer date/time value than the current time for the expiresAfter attribute.

**E\_invalidValue20200INV – {0} is not a valid value**

**Explanation** The specified attribute does not contain a valid value in the UDDI request.

**Action** Please provide a valid value.

**E\_invalidValue20200INVVAL – Invalid Value: {0}**

**Explanation** The key value of the relationship KeyedReference is invalid.

**Action** Please provide a valid key value.

**E\_invalidValue20200KNAMNUL – keyName and keyValue should be specified for {0} keyedReference**

**Explanation** In UDDI, the keyedReference with tModelKey “uddi:uddi.org:categorization:general\_keywords or uuid:A035A07C-F362-44dd-8F95-E2B134BF43B4” has different behavior. Unchecked value sets can be specified using this KeyedReference. Since this is unchecked, the value sets keyName and KeyValue are mandatory.

**Action** Please provide a value for KeyName and the KeyValue attribute of the uddi-org:general\_keywords KeyedReference.

**E\_invalidValue20200KVALINV – The attribute keyValue {0} for keyedReference {1} failed validation.**

**Explanation** Validation failed for the KeyedReference as it does not contain a proper key value.

**Action** Please provide valid key value.

**E\_invalidValue20200KVALNUL – The attribute keyValue should not be null for a keyedReference.**

**Explanation** KeyValue is a mandatory attribute and it should contain a valid value.

**Action** Please provide a value for the KeyValue attribute of KeyedReference.

**E\_invalidValue20200MAXENT – maxEntities has a negative value.**

**Explanation** The maxEntities attribute of the subscription should contain a positive number.  
**Action** Please provide a positive value for the maxEntities attribute.

**E\_invalidValue20200NOVAL – For asynchronous subscription, both the bindingKey and notificationInterval values should be specified**

**Explanation** To identify whether a subscription is asynchronous or synchronous, the elements bindingKey and notificationInterval are used. Element bindingKey is used to identify to which web service/email address the notification has to be sent. Element notificationInterval is used to identify how often the notification has to be sent. Both elements are required for asynchronous subscription.  
**Action** Please provide values for the bindingKey and notificationInterval attributes for asynchronous subscription.

**E\_invalidValue20200NTFINT – {0} is not a valid value for notification interval.**

**Explanation** The notificationInterval attribute has to be specified in xsd:duration format.  
**Action** Please provide notificationInterval attribute in xsd:duration format.

**E\_tokenAlreadyExists40070 – Token Generated for key {0} has expired or the token is already occupied for the specified entities.**

**Explanation** CentraSite already generated a transfer token for the specified entities.  
**Action** Please re-generate the token or use the existing token for the specified entities.

**E\_transferNotAllowed40600DEF – Transfer Not Allowed!!**

**Explanation** CentraSite does not allow this transfer. The specified transfer token is not present in CentraSite. It might be discarded.  
**Action** Transfer of the entities are not allowed

**E\_transferNotAllowed40600DNE – TransferToken does not exist.**

**Explanation** The specified transfer token does not exist in CentraSite. It might be invalid or discarded.  
**Action** Please generate new transfer token.

**E\_transferNotAllowed40600INV – Transfer not allowed. Custody (Operator) or ownership are not same.**

**Explanation** CentraSite does not allow the entities to be transferred if the owners or operator are not the same.

**Action** Operator and ownership must be the same to transfer entities.

**E\_transferNotAllowed40600TCBE – Transfer the custody of this businessEntity {0} to the node {1} on which it is modified.**

**Explanation** CentraSite does not support transferring the node businessEntity.

**Action** The transfer is not allowed for this business entity.

**E\_transferNotAllowed40600TCBS – Transfer the custody of this businessService {0} to the node {1} on which it is modified.**

**Explanation** The node of the businessService does not match the CentraSite node businessEntity.

**Action** Transfer is not allowed for this businessService.

**E\_transferNotAllowed40600TCBT – Transfer the custody of this bindingTemplate {0} to the node {1} on which it is modified.**

**Explanation** The node of the bindingTemplate does not match the CentraSite node businessEntity.

**Action** Transfer is not allowed for this bindingTemplate.

**E\_transferNotAllowed40600TCTM – Transfer the custody of this tModel {0} to the node {1} on which it is modified.**

**Explanation** The node of the tModel does not match the CentraSite node businessEntity.

**Action** Transfer is not allowed for this tModel.

**E\_transferNotAllowed40600TTNEX – This TransferToken does not exist.**

**Explanation** CentraSite does not contain the specified transfer token.

**Action** Please fetch a new transfer token.

**E\_unknownUser10150ID – User ID {0} and password pair passed in a get\_authToken API is unknown to the UDDI node or is not valid.**

**Explanation** A user ID in the get\_authToken request is mandatory, but the userId element in the get\_authTokenRequest request is null.

**Action** Please provide a valid user ID and password in the get\_authToken request.

**E\_unknownUser10150PASS – User ID and password {0} pair passed in a get\_authToken API is unknown to the UDDI node or is not valid.**

**Explanation** The cred element in the get\_authToken request is mandatory, but the cred element in the get\_authTokenRequest request is null.

**Action** Please provide a valid user ID and password in the get\_authToken request.

**E\_unrecognizedVersion10040 – Namespace {0} is unsupported by the node being queried.**

**Explanation** The request is not a valid UDDI request or the request cannot be processed by CentraSite.

**Action** Please provide a valid UDDI request as defined in the UDDI specification.

**E\_unsupported10050 Feature {0} is not supported.**

**Explanation** The request is not a valid UDDI request or the request cannot be processed by CentraSite.

**Action** Please provide a valid UDDI request as defined in the UDDI specification.

**E\_unsupported10050AUTH – authInfo element present in get\_assertionStatusReport element is required.**

**Explanation** Authorization is required to process the get\_assertionStatusReport call.

**Action** Please provide an authInfo element with a proper authToken in the get\_assertionStatusReport call. Please fetch the authToken using a get\_authToken call.

**E\_unsupported10050INVFINDGET – Invalid find\_xx or get\_xx api specified in the subscriptionFilter or some part of the subscription to be saved is invalid.**

**Explanation** The subscription filter for the subscription is not valid.

**Action** Please provide the subscription filter for the subscription according to the UDDI specification.

**E\_unsupported10050INVFQ – {0} is not a valid find qualifier value in version {1}.**

**Explanation** The provided find qualifier is not valid. The valid qualifiers can be found in UDDI specification.

**Action** Please provide find qualifiers compliant with the UDDI specification.

**E\_unsupported10050NINV – The notification interval specified is less than {0}. Please increase the notification interval.**

**Explanation** UDDI configuration parameter UDDIMinimalNotificationInterval specified the minimal notification interval that the UDDI engine can handle. If the given value is less than the UDDIMinimalNotification interval then this error will occur.

**Action** Please increase the notification interval

**E\_unsupported10050QUA – This Qualifier is not allowed with FindBinding Inquiry API.**

**Explanation** The find qualifiers binarySort, bindingSubset, caseInsensitiveSort, caseSensitiveSort, combineCategoryBags, sortByNameAsc, sortByNameDesc, serviceSubset and suppressProjectedServices are not supported in the find\_binding call.

**Action** Please specify find qualifiers other than binarySort, bindingSubset, caseInsensitiveSort, caseSensitiveSort, combineCategoryBags, sortByNameAsc, sortByNameDesc, serviceSubset and suppressProjectedServices for the find\_binding call.

**E\_unsupported10050QUARELB – This Qualifier is not allowed with FindRelatedBusinesses Inquiry API.**

**Explanation** The find qualifiers andAllKeys, bindingSubset, combineCategoryBags, orAllKeys, orLikeKeys, serviceSubset and suppressProjectedServices are not supported in the find\_relatedBusinesses call.

**Action** Please specify find qualifiers other than andAllKeys, bindingSubset, combineCategoryBags, orAllKeys, orLikeKeys, serviceSubset and suppressProjectedServices for the find\_relatedBusinesses call.

**E\_unsupported10050QUARSER – This Qualifier is not allowed with FindService Inquiry API.**

**Explanation** The serviceSubset find qualifier is not supported in the find\_service call.

**Action** Please remove the serviceSubset find qualifier from the find\_service request.

**E\_unsupported10050QUARTM – This Qualifier is not allowed with FindTModel Inquiry API.**

**Explanation** The find qualifiers bindingSubset, combineCategoryBags, serviceSubset and suppressProjectedServices are not supported in the find\_tModel call.

**Action** Please specify find qualifiers other than bindingSubset, combineCategoryBags, serviceSubset and suppressProjectedServices for the find\_tModel call.

**E\_unvalidatable20220UNVALID – The referenced tModel has been marked unvalidatable.**

**Explanation** CentraSite does not allow an unvalidatable KeyedReference to be present in the UDDI request.

**Action** The specified tModel cannot be used in the keyedReference.

**E\_userMismatch10140 – Signifies that an attempt was made to use the publishing API to change data that is controlled by another party.**

**Explanation** An access violation exception occurred as the user tried to modify a UDDI entity owner by another user.

**Action** Please make sure proper permissions are assigned to the user to update the entity.

**E\_userMismatch10140DELSUBUSR – Tried to delete a subscription that is controlled by another individual.**

**Explanation** An access violation exception occurred as the user tried to delete the subscription owned by another user.

**Action** Please provide the authToken of the user who owns the subscription.

**E\_userMismatch10140DIFSUB – The owner of the subscription is different.**

**Explanation** The subscription is not owned by the specified user.

**Action** Please provide the authToken of the user who owns the subscription.

**E\_userMismatch10140FRMTOK – USER-MISMATCH for publisherAssertion fromKey {0} and toKey {1}.**

**Explanation** The user should own the business specified in fromKey or toKey.

**Action** Please provide the business key owned by the user either in fromKey or in toKey.

**E\_userMismatch10140PBE – You are not authorized to publish a businessEntity.**

**Explanation** The user does not have permission to create a business in CentraSite.

**Action** Please make sure the user has permission to create a business in CentraSite.

**E\_userMismatch10140TT – You are not authorized to get the TransferToken for the key {0} which is owned by another publisher.**

**Explanation** The transfer token for an entity can be fetched by the user who owns the entity. Transfer token for the entities which the user does not own cannot be fetched.

**Action** Please provide the key of the owned UDDI entity.

**E\_userMismatch10140UEK – Tried to update the {0} {1} that is controlled by another individual.**

**Explanation** The user does not own or does not have permission to update the UDDI entity.  
**Action** Make sure the user has permission to update the UDDI entity, or make sure the user owns the UDDI entity.

**E\_userMismatch10140USUBUSR – Tried to update the subscription with key {0}, that is controlled by another individual.**

**Explanation** The subscription is not owned by the specified user.  
**Action** Please provide the authToken of the user who owns the subscription.

**E\_valueNotAllowed20210NODE – This checked category system is only permitted to be used by the node itself.**

**Explanation** The node business cannot be updated by the user.  
**Action** The node business cannot be updated by the user.

**INMAFE0001 The registry object must not be null.**

**Explanation** The constructor CSAppFixedRegistryObject() is trying to create a new instance so the registry object passed can't be null.  
**Action** Pass valid registry object.

**INMAFE0002 A fixed registry object's name cannot be changed.**

**Explanation** This is a fixed Registry Object. It's name must not be changed.  
**Action** Don't change a fixed registry object's name.

**INMAFE0003 Different object with duplicate key already registered: {0}**

**Explanation** Two different objects that have the same keys are being registered.  
**Action** Check for any reasons why the duplicate keys exist or change one of the object's keys.

**INMAFE0004 Different association type with duplicate name already registered {0}**

**Explanation** Two different associations that have the same names are being registered.  
**Action** Change one of the association's names.

**INMAFE0005**      **Different object type with duplicate name already registered {0}**  
**Explanation**      Object types have to have unique names.  
**Action**              Change the object type name to a unique one.

**INMAFE0006**      **Different child list already registered for parent path: {0}**  
**Explanation**      for this path there is already a defined child list.  
**Action**              Create another parent path to add the new child list.

**INMAFE0007**      **Unknown taxonomy: {0}**  
**Explanation**      The desired taxonomy does not exist.  
**Action**              Use an existing Taxonomy.

**INMAFE0008**      **Multiple taxonomies named {0} found.**  
**Explanation**      Taxonomies must have unique names.  
**Action**              Find a way to make the used taxonomies have a unique name.

**INMAFE0010**      **Different object with duplicate name already registered: {0}**  
**Explanation**      The objects are classification schemes, their names must be unique.  
**Action**              Find a way to change the object names to unique ones.

**INMAFE0011**      **No such concept: {0}**  
**Explanation**      This Concept does not exist in the database.  
**Action**              Create such a Concept or change to an existing one.

**INMAFE0012**      **No such classification scheme: {0}**  
**Explanation**      This classification scheme does not exist in the database.  
**Action**              Create a new one or change to an existing classification scheme.

**INMAFE0013**      **No such association type: {0}**  
**Explanation**      This association type does not exist in the database.  
**Action**              Create a new one or change to an existing association type.

<b>INMAFE0014</b>	<b>No such object type: {0}</b>
<b>Explanation</b>	This object type does not exist in the database.
<b>Action</b>	Create a new one or change to an existing object type.
<b>INMAFE0015</b>	<b>Child list not available for parent {0}, did you set the cache strategy 'childs'?</b>
<b>Explanation</b>	The cache strategy "childs" needs to be set in order to access child concepts.
<b>Action</b>	Set the cache strategy 'childs'.
<b>INMAFE0017</b>	<b>Child list not available for taxonomy {0}, did you set the cache strategy 'childs'?</b>
<b>Explanation</b>	The cache strategy "childs" needs to be set in order to access child concepts.
<b>Action</b>	Set the cache strategy 'childs'.
<b>INMAFE0018</b>	<b>Child list not available for parent concept {0}, did you set the cache strategy 'childs'?</b>
<b>Explanation</b>	The cache strategy "childs" needs to be set in order to access child concepts.
<b>Action</b>	Set the cache strategy childs.
<b>INMAFE0019</b>	<b>No object with key {0} is known by the pool.</b>
<b>Explanation</b>	No fixed RegistryObject was found in the bean pool.
<b>Action</b>	The fixed registry object must be added to the bean pool.
<b>INMAFE0021</b>	<b>Invalid element {0}, expected either of {1}</b>
<b>Explanation</b>	The specified element is not contained in the list of expected elements.
<b>Action</b>	Use or change the element to one of the expected types.
<b>INMAFE0023</b>	<b>Missing attribute: {0}</b>
<b>Explanation</b>	The searched attribute is mandatory and must be provided.
<b>Action</b>	Provide the missing attribute or change it so it is not mandatory any more.
<b>INMAFE0024</b>	<b>Empty attribute: {0}</b>
<b>Explanation</b>	The attribute is empty.
<b>Action</b>	Provide data for the attribute.

**INMAFE0025**      **Duplicate objectType name: {0}**  
**Explanation**      Object Types must have unique names.  
**Action**              Provide a unique name for the object type, delete or rename the existing one.

**INMAFE0026**      **Duplicate associationType name: {0}**  
**Explanation**      The assoiation type name must be unique.  
**Action**              Provide a unique association type name, delete or rename the existitng one.

**INMAFE0027**      **Duplicate taxonomy name: {0}**  
**Explanation**      Taxonomy name must be unique.  
**Action**              Provide unique name for the Taxonomy, rename or delete the existing one.

**INMAFE0028**      **Invalid value for {0}**  
**Explanation**      The specified value is invalid.  
**Action**              Provide valid value.

**INMAFE0029**      **Invalid element {0}, expected {1}**  
**Explanation**      The specified element does not match the expected element.  
**Action**              The element must be changed accordingly to the expected item.

**INMAFE0031**      **Duplicate concept value for taxonomy {0}**  
**Explanation**      Taxonomy must have a unique concept value.  
**Action**              Provide a unique concept value for the taxonomy.

**INMAFE0032**      **Duplicate concept value for concept {0}**  
**Explanation**      Concept must have a unique concept value.  
**Action**              Provide a unique concept value for the concept.

**INMAFE0033**      **Invalid argument: {0}**  
**Explanation**      The specified argument is invalid.  
**Action**              Provide a valid argument.

<b>INMAFE0034</b>	<b>The class {0} has no annotation of type {1} or has an empty 'implementation' attribute.</b>
<b>Explanation</b>	The given class does not have the expected annotation, or the annotation's "implementation" attribute is empty.
<b>Action</b>	Provide an annotation of the given type or fill in the 'implementation' attribute.
<b>INMAFE0037</b>	<b>The object type's qualified name must not be null.</b>
<b>Explanation</b>	One of the arguments has a null value.
<b>Action</b>	Provide arguments with a valid value.
<b>INMAFE0038</b>	<b>A classification's scheme must not be null.</b>
<b>Explanation</b>	The classification has a null value.
<b>Action</b>	Provide a valid value for classification.
<b>INMAFE0039</b>	<b>A classification's value must not be null.</b>
<b>Explanation</b>	The classification has a null value.
<b>Action</b>	Provide a valid value for classification.
<b>INMAFE0040</b>	<b>The object type's qualified name must not be null.</b>
<b>Explanation</b>	The object type's qualified name has null value.
<b>Action</b>	Provide a valid value for object type's qualified name.
<b>INMAFE0041</b>	<b>The classification schemes must not be null.</b>
<b>Explanation</b>	The classification schemes have a null value.
<b>Action</b>	Provida a valid value for the classification schemes.
<b>INMAFE0042</b>	<b>This object is unmodifiable.</b>
<b>Explanation</b>	The object cannot be modified.
<b>Action</b>	Do not try to modify the object.
<b>INMAFE0043</b>	<b>Unknown property {0}</b>
<b>Explanation</b>	The property has unknown value.
<b>Action</b>	Provide a valid value for the property.

<b>INMAFE0044</b>	<b>The IOC annotation of the field {0} has no ID or an empty ID.</b>
<b>Explanation</b>	Some annotation has an empty ID or no ID.
<b>Action</b>	Provide a valid ID for the annotation.
<b>INMAFE0045</b>	<b>The object to initialize must not be null.</b>
<b>Explanation</b>	The initializer has a null value.
<b>Action</b>	Provide a valid value for the initializer.
<b>INMAFE0046</b>	<b>The document must not be null.</b>
<b>Explanation</b>	The document is null.
<b>Action</b>	Provide a valid value for the document.
<b>INMAFE0047</b>	<b>The QName {0} is invalid, because it contains no terminating '}' character.</b>
<b>Explanation</b>	The value argument has no enclosing '}' character.
<b>Action</b>	Make sure the value argument has an enclosing '}' character.
<b>INMAFE0049</b>	<b>Expected {0} element, got {1}</b>
<b>Explanation</b>	The element is different than expected.
<b>Action</b>	Make sure the element type is as expected.
<b>INMAFE0051</b>	<b>Missing attribute for {0}</b>
<b>Explanation</b>	The attribute has a null value.
<b>Action</b>	Provide a valid value for the attribute.
<b>INMAFE0052</b>	<b>Invalid attribute {0} for element {1}</b>
<b>Explanation</b>	The attribute has an invalid value.
<b>Action</b>	Provide a valid value for the attribute.
<b>INMAFE0054</b>	<b>The attribute {0} for element {1} is using an invalid prefix: {2}</b>
<b>Explanation</b>	Some of the attributes have an invalid prefix.
<b>Action</b>	Make sure the attribute has a valid prefix.

<b>INMAFE0056</b>	<b>Missing attribute: {0}</b>
<b>Explanation</b>	Attribute is missing.
<b>Action</b>	Provide attribute.
<b>INMAFE0057</b>	<b>Empty attribute: {0}</b>
<b>Explanation</b>	Attribute is missing.
<b>Action</b>	Provide attribute.
<b>INMAFE0058</b>	<b>The class {0} doesn't implement {1}</b>
<b>Explanation</b>	Wrong class provided.
<b>Action</b>	Provide a valid class.
<b>INMAFE0116</b>	<b>Missing @RegistryObject annotation on persistent class {0}</b>
<b>Explanation</b>	The processed class has no @RegistryObject annotation. As long as there is no such annotation the persistent class cannot be considered a RegistryBean and cannot be processed.
<b>Action</b>	Add a @RegistryObject annotation to the persistent class interface or use different RegistryBean.
<b>INMAFE0119</b>	<b>The given registry bean is managed by another pool: {0}</b>
<b>Explanation</b>	A registry bean instance can be managed by one bean pool only. For example it is not allowed to read a bean with one bean pool instance and update it with another.
<b>Action</b>	Check for multiple beanPool instances managing your registry beans. For a single thread, make one bean pool instance to handle the registry beans.
<b>INMAFE0121</b>	<b>The given registry bean is not managed by the pool: {0}</b>
<b>Explanation</b>	The registry bean is being used by a bean pool it does not belong to.
<b>Action</b>	Find and use the bean pool instance that this registry bean belongs to. For example if a registry bean is read or created by one bean pool instance, this is the instance it belongs to and it cannot be managed by another one.
<b>INMAFE0123</b>	<b>Missing information for attribute with name {0} of type {1}</b>
<b>Explanation</b>	This attribute should have an attribute description but it does not. For example, attribute description is required for @Relationship , @DateAttribute and other attributes.
<b>Action</b>	When using @Relationship, @DateAttribute etc. an attributeName property must be specified, which corresponds to the name of an existing AttributeDescription. Either create new attribute description, or change the name of the attributeName property to an existing one.

<b>INMAFE0128</b>	<b>The RegistryObject must be an association, but is a {0}</b>
<b>Explanation</b>	The RegistryObject to be processed must be a javax.xml.registry.infomodel.Association. The method is trying to create a RegistryBean instance from a javax.xml.registry.infomodel.Association instance.
<b>Action</b>	Check the mapping of theRegistryBean that is being created for any inconsistencies.
<b>INMAFE0129</b>	<b>AssociationTarget property of {0} is null. Association target cannot be null.</b>
<b>Explanation</b>	While creating a javax.xml.registry.infomodel.Association instance from a registry bean Association instance. The target of the association must be present in order to create a javax.xml.registry.infomodel.Association.
<b>Action</b>	Set target for the association.
<b>INMAFE0130</b>	<b>Unable to determine object type. Missing RegistryObject annotation for class {0}.</b>
<b>Explanation</b>	Either the processed registry bean is not a registry bean at all, or it is missing its RegistryObject annotation. Without it the registry bean cannot be created and it is not considered a registry bean.
<b>Action</b>	Either use a different registry bean that has a RegistryObject annotation, or add the annotation in the used registry bean interface.
<b>INMAFE0131</b>	<b>Missing concept with key {0}.</b>
<b>Explanation</b>	The key that is specified is either wrong or does not belong to a concept instance.
<b>Action</b>	Use a different object type key for this annotation.
<b>INMAFE0132</b>	<b>Missing concept with name {0}</b>
<b>Explanation</b>	The name that is specified is either wrong or does not belong to a concept instance.
<b>Action</b>	Use a different object type name for this annotation.
<b>INMAFE0133</b>	<b>The RegistryObject must be a classification.</b>
<b>Explanation</b>	The registry object to be processed must be a javax.xml.registry.infomodel.Classification instance.
<b>Action</b>	Use a registry object that is an instance of javax.xml.registry.infomodel.Classification.

<b>INMAFE0134</b>	<b>ClassificationConcept property of {0} is null. The concept for internal classification cannot be null.</b>
<b>Explanation</b>	The classification's concept property is not specified.
<b>Action</b>	Specify a concept for this classification.
<b>INMAFE0135</b>	<b>Missing {0} annotation. {1} must be classified instance.</b>
<b>Explanation</b>	The ClassifiedInstances annotation is missing. It must be present in order to create a ClassifiedInstances property.
<b>Action</b>	Add the ClassifiedInstances annotation to the registry bean.
<b>INMAFE0136</b>	<b>{0} is not specified as ClassifiedInstance</b>
<b>Explanation</b>	None of the bean interfaces is a classified instance in the ClassifiedInstances annotation's instances.
<b>Action</b>	Specify a bean interface as ClassifiedInstance.
<b>INMAFE0137</b>	<b>Cannot find the required classification on {0}</b>
<b>Explanation</b>	There is no corresponding classification for the given registry object.
<b>Action</b>	Provide the classification.
<b>INMAFE0138</b>	<b>BeanInfo {0} for {1} must be instance of {2}</b>
<b>Explanation</b>	The BeanInfo instance is not of type BackedBeanInfo.
<b>Action</b>	Make the BeanInfo an instance of BackedBeanInfo.
<b>INMAFE0139</b>	<b>No setter found for property {0} in class {1}</b>
<b>Explanation</b>	The name of the setter is different and a corresponding setter cannot be found in the jaxr representation of this registry bean.
<b>Action</b>	Change the name of the setter in the registry bean interface.
<b>INMAFE0140</b>	<b>Missing type information for {0}</b>
<b>Explanation</b>	The BeanType for this jaxr registry object cannot be found in the registry object model. It is not supported by CSAF.
<b>Action</b>	Add BeanType for the required jaxr registry object type in the registry object model.

<b>INMAFE0141</b>	<b>Getter returns unexpected value type: {0} . Expected: Collection. For property: {1} in class: {2}</b>
<b>Explanation</b>	The value returned by the getter method does not match the return type specified in the bean interface.
<b>Action</b>	Change the return type to collection or change the annotation used for this property.
<b>INMAFE0142</b>	<b>No instance of SlotHandler registered for the type {0}</b>
<b>Explanation</b>	None of the existing slot handlers handles the given property type.
<b>Action</b>	Add a slot handler or change the property type.
<b>INMAFE0143</b>	<b>Expected RegistryObject of type javax.xml.registry.infomodel.User or javax.xml.registry.infomodel.Organization {0}</b>
<b>Explanation</b>	The javax.xml.registry.infomodel.TelephoneNumbers support type can only be found in a javax.xml.registry.infomodel.User or javax.xml.registry.infomodel.Organization instance.
<b>Action</b>	Use a javax.xml.registry.infomodel.User or javax.xml.registry.infomodel.Organization instance for operations with javax.xml.registry.infomodel.TelephoneNumbers.
<b>INMAFE0144</b>	<b>A Collection is expected {0}</b>
<b>Explanation</b>	TelephoneNumbers is always a collection. Single property is not allowed.
<b>Action</b>	Use a collection of TelephoneNumbers.
<b>INMAFE0145</b>	<b>Expected RegistryObject of type User or Organization RegistryBeans {0}</b>
<b>Explanation</b>	The CSAF support type TelephoneNumbers can only be found in a User or Organization RegistryBean instance.
<b>Action</b>	Use a User or Organization RegistryBean instance for operations with CSAF TelephoneNumbers.
<b>INMAFE0146</b>	<b>Beans to restore must be of BackedBeanInfo instance</b>
<b>Explanation</b>	Only BackedBeanInfo instances can provide access to the underlying RegistryObject.
<b>Action</b>	Use BackedBeanInfo to provide access to the RegistryObject that is standing behind the RegistryBean.

<b>INMAFE0147</b>	<b>Invalid bean mode</b>
<b>Explanation</b>	The bean mode of a configuration can be BACKED or SIMPLE (has been deprecated). Any other bean mode set to the configuration will result in this exception.
<b>Action</b>	Set the bean mode of the configuration to BACKED. The BACKED constant is located under com.softwareag.centrasite.appl.framework.persistence.BeanMode.java.
<b>INMAFE0148</b>	<b>The object to be read must be a RegistryObject instance: {0}</b>
<b>Explanation</b>	The object to be read must be an instance of javax.xml.registry.infomodel.RegistryObject but is not.
<b>Action</b>	Read a different object that is of javax.xml.registry.infomodel.RegistryObject instance.
<b>INMAFE0149</b>	<b>Unsupported value type passed: {0}</b>
<b>Explanation</b>	The value type passed is not supported by this method and cannot be processed.
<b>Action</b>	Change the value Type or change the method you are using to process this value. For example, the toJaxrValue() method expects one of the support types defined in CSAF (EmailAddress, TelephoneNumbers etc.) and processes it to a JAXR support type , while the toBeanValue method does the opposite.
<b>INMAFE0150</b>	<b>Missing type information for {0}</b>
<b>Explanation</b>	No BeanType found in the registry object model for the given registry object. It is not supported by CSAF.
<b>Action</b>	Create a BeanType and add it to the registry object model for the given registry object type.
<b>INMAFE0151</b>	<b>The BulkResponse collection must currently be java.util.List {0}</b>
<b>Explanation</b>	The result method of the Search class always has to return a java.util.List object.
<b>Action</b>	Change the Search's BulkResponse collection to java.util.List.
<b>INMAFE0152</b>	<b>Missing type information for {0}</b>
<b>Explanation</b>	No BeanType found in the registry object model for the given registry object. It is not supported by CSAF.
<b>Action</b>	Create a BeanType and add it to the registry object model for the given registry object type.

<b>INMAFE0153</b>	<b>Property is null, this kind of predicate is not allowed</b>
<b>Explanation</b>	A predicate has been created for a property that does not exist.
<b>Action</b>	Check the search criteria for wrong property names.
<b>INMAFE0154</b>	<b>The given class: {0} is not supported</b>
<b>Explanation</b>	No BeanType found for the given class in the registry object model.
<b>Action</b>	Add BeanType in the registry object model for the desired class.
<b>INMAFE0159</b>	<b>Invalid attribute name. Attribute name must not contain a space or special characters.</b>
<b>Explanation</b>	Creating a slot attribute with spaces or special characters in its name is not allowed.
<b>Action</b>	Use camel case (example: SlotAttribute) or '_' (example: Slot_Attribute) in the name instead of space, or change the name in a different way that it does not contain spaces.
<b>INMAFE0160</b>	<b>Invalid slot attribute data type.</b>
<b>Explanation</b>	The data type passed when creating slot attribute is not supported.
<b>Action</b>	Change the data type to one that is supported. Constants with supported data types can be found in AttributeDescription class.
<b>INMAFE0161</b>	<b>Unknown Error</b>
<b>Explanation</b>	The error that has been thrown has unknown reasons.
<b>Action</b>	Contact your software supplier.
<b>INMAFE0162</b>	<b>The parent concept must not be null.</b>
<b>Explanation</b>	The Concept must have a parent.
<b>Action</b>	Add parent to the concept.
<b>INMAFE0163</b>	<b>Invalid namespace prefix: {0}</b>
<b>Explanation</b>	The namespace prefix is invalid.
<b>Action</b>	Change the namespace to a valid one.
<b>INMAFE0164</b>	<b>Don't know how to handle skipped entity: {0}</b>
<b>Explanation</b>	The Parser has encountered a skipped entity. CSAF does not support skipped entities.
<b>Action</b>	Exclude the skipped entities from the entity list.

<b>INMAFE0165</b>	<b>Expected empty stack.</b>
<b>Explanation</b>	The Parser has reached the end of the file, and its stack should be empty.
<b>Action</b>	Check the file for any inconsistencies or errors.
<b>INMAFE0166</b>	<b>No getter for property {0} found in class {1}</b>
<b>Explanation</b>	In order to access a RegistryBean property it must have a getter method.
<b>Action</b>	Provide a getter method for this RegistryBean property. In some cases the getter methods are not provided for a purpose. These RegistryBeans should be documented.
<b>INMAFE0167</b>	<b>The method {0} in class {1} must be public, and neither static, nor abstract.</b>
<b>Explanation</b>	There is a restriction that must be followed.
<b>Action</b>	Change the method to public and remove any static or abstract modifiers.
<b>INMAFE0168</b>	<b>Failed to parse getter name: {0}</b>
<b>Explanation</b>	A getter method follows a rule when created. It must begin with either get or is. Any other case will result in this exception.
<b>Action</b>	Rename the getter method so it follows the described rule.
<b>INMAFE0169</b>	<b>The setter {0} in class {1} has return type {2} , not void.</b>
<b>Explanation</b>	A setter method must have a void return type.
<b>Action</b>	Change the setter return type to void.
<b>INMAFE0170</b>	<b>The method {0} in class {1} must be public, and not static.</b>
<b>Explanation</b>	There is a restriction to this method, namely it must be public and not static.
<b>Action</b>	Follow the restriction.
<b>INMAFE0171</b>	<b>Failed to parse method name: {0}</b>
<b>Explanation</b>	The method must start with either get, set, has or is. This is necessary in order to be recognized by the parser so a property name can be extracted.
<b>Action</b>	Change the method name accordingly.

<b>INMAFE0172</b>	<b>Illegal access to default constructor of class {0} : {1}</b>
<b>Explanation</b>	Nested exception is thrown here. The constructor has to be called with an empty expression list, or check {1} for more information.
<b>Action</b>	Change the constructor accordingly.
<b>INMAFE0173</b>	<b>Failed to instantiate class {0} : {1}</b>
<b>Explanation</b>	Nested exception is thrown here. More details are found in {1}
<b>Action</b>	Handle according to the nested exception message.
<b>INMAFE0174</b>	<b>Illegal access to default constructor of class {0} : {1}</b>
<b>Explanation</b>	Nested exception is thrown here. The constructor has to be called with an empty expression list, or check {1} for more information.
<b>Action</b>	Change the constructor accordingly.
<b>INMAFE0175</b>	<b>Failed to instantiate class {0} : {1}</b>
<b>Explanation</b>	Nested exception is thrown here. More details are found in {1}
<b>Action</b>	Handle according to the nested exception message.
<b>INMAFE0176</b>	<b>Failed to invoke constructor of class {0} : {1}</b>
<b>Explanation</b>	Nested Exception. See {1} for more information.
<b>Action</b>	Handle the case according to information in {1}.
<b>INMAFE0177</b>	<b>No field named {0} found in class {1} or any of its superclasses.</b>
<b>Explanation</b>	The desired field is not present in the class, nor in any of the superclasses.
<b>Action</b>	Provide the missing field, or change the field name being searched.
<b>INMAFE0178</b>	<b>Illegal access to field {0} in class {1} : {2}</b>
<b>Explanation</b>	Nested Exception thrown, see {2} for more details.
<b>Action</b>	Handle according to the information in {2}.
<b>INMAFE0179</b>	<b>Failed to load the class named {0}.</b>
<b>Explanation</b>	The class with the given name was not found.
<b>Action</b>	Provide the missing class.

<b>INMAFE0180</b>	<b>Invalid property specification: {0}</b>
<b>Explanation</b>	The property has opening bracket [ but no closing bracket ].
<b>Action</b>	Provide the closing bracket ] .
<b>INMAFE0181</b>	<b>Invalid property specification: {0}</b>
<b>Explanation</b>	The property was not specified correctly.
<b>Action</b>	Make sure that the property follows all rules.
<b>INMAFE0182</b>	<b>No list was returned for property specification {0}</b>
<b>Explanation</b>	This property is expected to return a list.
<b>Action</b>	Check the property for any inconsistencies.
<b>INMAFE0183</b>	<b>No add method found for property {0} in class {1}</b>
<b>Explanation</b>	The property must correspond to an add method, but it doesn't.
<b>Action</b>	Provide an add method, change the property or check the property for inconsistencies.
<b>INMAFE0184</b>	<b>No remove method found for property {0} in class {1}</b>
<b>Explanation</b>	The property must correspond to a remove method, but it doesn't.
<b>Action</b>	Provide a remove method, change the property or check the property for inconsistencies.
<b>INMAFE0185</b>	<b>A fixed registry object's description cannot be changed.</b>
<b>Explanation</b>	This registry object description cannot be changed.
<b>Action</b>	Don't attempt to change a fixed registry object's description.
<b>INMAFE0186</b>	<b>The interface {0} doesn't have its implementation attribute set in the {1} annotation.</b>
<b>Explanation</b>	Each interface bean needs to specify its implementation class.
<b>Action</b>	Please use correct value for the annotation attribute.
<b>INMAFE0187</b>	<b>The key must not be null.</b>
<b>Explanation</b>	Each key must have a non-null id value.
<b>Action</b>	Provide non-empty, unique key value.

<b>INMAFE0188</b>	<b>The concept key must point to a Concept: {0}</b>
<b>Explanation</b>	Classifications can only be based on concepts.
<b>Action</b>	Make sure that the Classification's concept key is actually pointing to a Concept registry object.
<b>INMAFE0189</b>	<b>The registry object type key must point to a Concept from the ObjectType taxonomy: {0}</b>
<b>Explanation</b>	The required object needs to be a child of the "ObjectType" taxonomy.
<b>Action</b>	Make sure that object type key points to a Concept from the ObjectType taxonomy (Classification Scheme).
<b>INMAFE0190</b>	<b>The association type key must point to a Concept from the AssociationType taxonomy: {0}</b>
<b>Explanation</b>	The required object needs to be a child of the "AssociationType" taxonomy.
<b>Action</b>	Make sure that association type key points to a Concept from the AssociationType taxonomy (Classification Scheme).
<b>INMAFE0191</b>	<b>The property is null.</b>
<b>Explanation</b>	The getMapper() method requires a non-null property argument.
<b>Action</b>	Make sure the property is available.
<b>INMAFE0192</b>	<b>No property mapper found for Property {0}</b>
<b>Explanation</b>	The property mapper for the desired property does not exist.
<b>Action</b>	Make sure that a suitable property mapper is available for this property.
<b>INMAFE0193</b>	<b>Wrong value type passed. Expected Collection&lt;com.softwareag.centrasite.appl.framework.beans.standard.TelephoneNumber&gt;</b>
<b>Explanation</b>	The method requires an argument of type "Collection".
<b>Action</b>	Make sure the correct value type is used.
<b>INMAFE0194</b>	<b>Cannot parse string to long(timestamp) {0}</b>
<b>Explanation</b>	The given value does not match the syntax rules for long numeric values.
<b>Action</b>	Expected long numeric value.

<b>INMAFE0195</b>	<b>Cannot parse date string {0}</b>
<b>Explanation</b>	The given value does not match the syntax rules for dates.
<b>Action</b>	Make sure the string is in the proper date format.
<b>INMAFE0196</b>	<b>Unsupported value passed: {0}. String value expected: either {namespace}localPart or localPart only.</b>
<b>Explanation</b>	The method expects a vlue of type "String".
<b>Action</b>	Please provide the correct value.
<b>INMAFE0197</b>	<b>Unsupported value type {0}</b>
<b>Explanation</b>	The KeyPredicate value type must be one of "String", "Key", or "RegistryBean".
<b>Action</b>	Please provide a valid value.
<b>INMAFE0198</b>	<b>Unable to create predicate for : {0}. Check the passed sequence and try again.</b>
<b>Explanation</b>	The values specified for the predicate cannot be properly converted to a query criterion.
<b>Action</b>	Please provide a valid predicate.
<b>INMAFE0199</b>	<b>The given object is not a RegistryObject.</b>
<b>Explanation</b>	The method requires a RegistryObject parameter.
<b>Action</b>	Please provide the correct object.
<b>INMAFE0200</b>	<b>Given object is not Classification: {0}</b>
<b>Explanation</b>	The method requires a Classification object.
<b>Action</b>	Please provide a valid Classification object.
<b>INMAFE0201</b>	<b>Unsupported collection. Should be java.util.List or java.util.Set.</b>
<b>Explanation</b>	The method requires a parameter of type List or Set.
<b>Action</b>	Please provide a collection of valid type.
<b>INMAFE0202</b>	<b>Only attributes of type Slot can be indexed.</b>
<b>Explanation</b>	Index definitions are only possible for Slot attributes.
<b>Action</b>	Use an attribute of valid type.

<b>INMAFE0203</b>	<b>Value and forward label must not be null.</b>
<b>Explanation</b>	When creating a new association type it is mandatory to specify a value and a forward label.
<b>Action</b>	Correct the application program.
<b>INMAFE0204</b>	<b>Object type to be generated not found: {0}</b>
<b>Explanation</b>	The object type name specified when calling the RegistryBeanGenerator does not exist.
<b>Action</b>	Specify an existing type name.
<b>INMAFE0205</b>	<b>Invalid object ({0}) passed to delete operation</b>
<b>Explanation</b>	The delete operation only accepts RegistryBean instances. In particular, NULL pointers are rejected.
<b>Action</b>	Call the delete operation with correct RegistryBean instances.
<b>INMAPE0001</b>	<b>The user {0} does not have the view permission; contact the asset owner or administrator for help.</b>
<b>Explanation</b>	If the current user has no permission to view this object, then this error will be thrown.
<b>Action</b>	The user needs to be provided proper permission to view this object.
<b>INMBUE0002</b>	<b>Invalid URI {0}.</b>
<b>Explanation</b>	You have entered an invalid URI.
<b>Action</b>	Enter a valid URI.
<b>INMBUE0003</b>	<b>Invalid phone number.</b>
<b>Explanation</b>	You have entered an invalid phone number.
<b>Action</b>	Enter a valid phone number.
<b>INMBUE0004</b>	<b>Search scope is empty.</b>
<b>Explanation</b>	You have not entered a valid search scope in the recipe.
<b>Action</b>	Enter a valid search scope.

<b>INMBUE0007</b>	<b>Saved search token is not valid.</b>
<b>Explanation</b>	You have entered an invalid saved search token in the URL.
<b>Action</b>	Enter a valid saved search token.
<b>INMBUE0009</b>	<b>Failed to initialize the Unwatch action on selected assets.</b>
<b>Explanation</b>	Could not initialize the Unwatch action on selected assets; possibly because one or more of the selected assets are not already watched.
<b>Action</b>	Choose the assets that are already watched.
<b>INMBUE0011</b>	<b>Enter a valid IP address</b>
<b>Explanation</b>	Enter a valid IP address
<b>Action</b>	Enter a valid IP address
<b>INMBUE0012</b>	<b>Duplicate values for {0}</b>
<b>Explanation</b>	A user was selected as an administrator, but this user has already been selected.
<b>Action</b>	Avoid selecting a user as administrator that has already been chosen.
<b>INMBUE0013</b>	<b>Invalid URL</b>
<b>Explanation</b>	You have entered an invalid URL.
<b>Action</b>	Enter a valid URL.
<b>INMBUE0014</b>	<b>Enter a valid Administrator</b>
<b>Explanation</b>	You have entered an invalid administrator name.
<b>Action</b>	Enter a valid administrator name.
<b>INMBUE0015</b>	<b>Group name is empty</b>
<b>Explanation</b>	You have not entered a group name while creating a local group.
<b>Action</b>	Enter a group name.
<b>INMBUE0016</b>	<b>Invalid URI.</b>
<b>Explanation</b>	You have entered an invalid URI.
<b>Action</b>	Enter a valid URI.

<b>INMBUE0017</b>	<b>Invalid numeric value in attribute.</b>
<b>Explanation</b>	You have entered an invalid numeric value for this attribute.
<b>Action</b>	Enter a valid numeric value.
<b>INMBUE0018</b>	<b>Invalid attribute value.</b>
<b>Explanation</b>	You have entered an invalid attribute value for the chosen type.
<b>Action</b>	Enter a valid value for the chosen type.
<b>INMBUE0019</b>	<b>Required attribute value is empty.</b>
<b>Explanation</b>	You have entered a blank value for the required attribute.
<b>Action</b>	Enter a value for the required attribute.
<b>INMBUE0020</b>	<b>Enter a valid string value for the attribute.</b>
<b>Explanation</b>	You have entered an invalid value for this string attribute.
<b>Action</b>	Enter a valid string value.
<b>INMBUE0021</b>	<b>Enter a valid IP address.</b>
<b>Explanation</b>	You have entered an invalid IP address.
<b>Action</b>	Enter a valid IP address.
<b>INMBUE0022</b>	<b>Enter a valid email address.</b>
<b>Explanation</b>	You have entered an invalid email address. You must enter a valid email address (e.g. example@example).
<b>Action</b>	Enter a valid email address (e.g. example@example).
<b>INMBUE0023</b>	<b>Invalid category name.</b>
<b>Explanation</b>	You have entered an invalid category name for this classification attribute.
<b>Action</b>	Enter a valid category name for the defined taxonomy.
<b>INMBUE0024</b>	<b>Refresh interval is empty.</b>
<b>Explanation</b>	Number. Required. An input denoting the time interval for refreshing a portlet automatically is not specified.
<b>Action</b>	Enter a value (in seconds) for refresh interval.

<b>INMBUE0025</b>	<b>Required attribute value is empty.</b>
<b>Explanation</b>	You have entered a blank value for the required attribute.
<b>Action</b>	Enter a value for the required attribute.
<b>INMBUE0026</b>	<b>Invalid search condition.</b>
<b>Explanation</b>	An invalid search condition has occurred. A search condition consists of one or more predicates, each joined by a keyword (ALL or ANY). A predicate can be a comparison predicate, such as an Equals predicate, NotEquals predicate, StartsWith predicate, or a Contains predicate. This error occurs when none of the above search conditions are met.
<b>Action</b>	Correct the search condition.
<b>INMBUE0028</b>	<b>Invalid combination of x and y axes; at least one of the axes must have a numeric attribute for the graph to render properly.</b>
<b>Explanation</b>	One of the attribute in the x or y axis should have a numeric value.
<b>Action</b>	Choose a numeric attribute in one of the two axes.
<b>INMBUE0029</b>	<b>Invalid search for charts; you must choose at least one numeric attribute.</b>
<b>Explanation</b>	The chosen search does not have a numeric attribute to plot the chart. To plot a chart you must have a combination of non-numeric attribute and numeric attribute.
<b>Action</b>	Choose a search with at least one numeric attribute.
<b>INMBUE0030</b>	<b>Organization name is empty</b>
<b>Explanation</b>	The organization name field is empty, but the organization name must be provided when creating an organization.
<b>Action</b>	Enter the organization name.
<b>INMBUE0031</b>	<b>Role name is empty</b>
<b>Explanation</b>	The role name field is empty, but the role name must be provided when creating a role.
<b>Action</b>	Enter a role name.

<b>INMBUE0032</b>	<b>Enter a valid consumer application name.</b>
<b>Explanation</b>	The consumer application name specified is either invalid or empty.
<b>Action</b>	Enter a valid consumer application name.
<b>INMBUE0035</b>	<b>Base URL should not be empty.</b>
<b>Explanation</b>	The Base URL is empty.
<b>Action</b>	Enter the Base URL.
<b>INMBUE0036</b>	<b>Add at least one method to the resource.</b>
<b>Explanation</b>	A resource should have at least one HTTP method to perform a certain operation. This error occurs when an attempt is made to add a resource in the API without specifying at least one method.
<b>Action</b>	Add at least one HTTP method for the resource.
<b>INMBUE0037</b>	<b>Parameter name must not be empty.</b>
<b>Explanation</b>	The parameter name is empty.
<b>Action</b>	Enter the parameter name.
<b>INMBUE0038</b>	<b>Method name must not be empty.</b>
<b>Explanation</b>	The method name is empty.
<b>Action</b>	Enter the method name.
<b>INMBUE0039</b>	<b>Resource name must not be empty.</b>
<b>Explanation</b>	The resource name is empty.
<b>Action</b>	Enter the resource name.
<b>INMBUE0040</b>	<b>Resource path must not be empty.</b>
<b>Explanation</b>	The resource path is empty.
<b>Action</b>	Enter the resource path.
<b>INMBUE0041</b>	<b>Default value should be a value in the possible values list.</b>
<b>Explanation</b>	The default value does not match with any of the values in the list of possible values.
<b>Action</b>	Enter a value from the list of possible values.

<b>INMBUE0042</b>	<b>The resource already exists.</b>
<b>Explanation</b>	An attempt was made to add a resource with the same name as an existing resource in the same service.
<b>Action</b>	Enter a new resource name that is not already in use in the service.
<b>INMBUE0043</b>	<b>Resource with path already exists in this API.</b>
<b>Explanation</b>	An attempt was made to add a resource with the same path as an existing resource in the same API.
<b>Action</b>	Enter a new resource path which is not already in use in the API.
<b>INMBUE0044</b>	<b>Parameter already exists for this parameter type.</b>
<b>Explanation</b>	An attempt was made to add a parameter with the same name as an existing parameter for the given parameter type.
<b>Action</b>	Enter a new parameter name that is not already available for the parameter type.
<b>INMBUE0045</b>	<b>Select at least one resource to virtualize.</b>
<b>Explanation</b>	An attempt was made to virtualize a REST service without selecting the resource.
<b>Action</b>	Select at least one resource to virtualize the REST service.
<b>INMBUE0046</b>	<b>Request message cannot be empty.</b>
<b>Explanation</b>	You have not entered a request message when adding sample request and response to the REST service.
<b>Action</b>	Enter the sample request message.
<b>INMBUE0051</b>	<b>API Portal Name field cannot be empty.</b>
<b>Explanation</b>	You have not entered the name of API Portal when registering API Portal in CentraSite.
<b>Action</b>	Enter the API Portal name.
<b>INMBUE0052</b>	<b>API Portal Alias field cannot be empty.</b>
<b>Explanation</b>	You have not entered the name of API Portal alias when registering API Portal in CentraSite.
<b>Action</b>	Enter the API Portal alias name.

<b>INMBUE0053</b>	<b>Deployment Endpoint field cannot be empty.</b>
<b>Explanation</b>	You have not entered the deployment endpoint address when registering API Portal in CentraSite.
<b>Action</b>	Enter a valid deployment endpoint.
<b>INMBUE0054</b>	<b>CentraSite Alias field cannot be empty.</b>
<b>Explanation</b>	You have not entered the name of CentraSite alias when registering API Portal in CentraSite.
<b>Action</b>	Enter the CentraSite alias name.
<b>INMBUE0055</b>	<b>Consumer Onboarding Organization field cannot be empty.</b>
<b>Explanation</b>	You have not entered the name of the consumer onboarding organization when registering API Portal in CentraSite.
<b>Action</b>	Enter the consumer onboarding organization name.
<b>INMBUE0056</b>	<b>The base URL already exists.</b>
<b>Explanation</b>	An attempt was made to add a base URL with the same value as an existing base URL in the same service.
<b>Action</b>	Enter a new base URL value that is not already in use in the service.
<b>INMBUE0058</b>	<b>Select at least one API Portal to publish.</b>
<b>Explanation</b>	An attempt was made to publish the API without selecting at least one API Portal.
<b>Action</b>	Select at least one API Portal to publish the API.
<b>INMBUE0059</b>	<b>Username field cannot be empty.</b>
<b>Explanation</b>	You have not entered the CentraSite username when registering API Portal in CentraSite.
<b>Action</b>	Enter a valid CentraSite username.
<b>INMBUE0060</b>	<b>Password field cannot be empty.</b>
<b>Explanation</b>	You have not entered the CentraSite password when registering API Portal in CentraSite.
<b>Action</b>	Enter a valid CentraSite password.

---

<b>INMBUE0062</b>	<b>Gateway URL is not valid. Specify a valid URL, and try again.</b>
<b>Explanation</b>	The gateway URL is not valid, or not in the correct format.
<b>Action</b>	Specify a valid gateway URL, and try again.
<b>INMBUE0063</b>	<b>Invalid value</b>
<b>Explanation</b>	Value entered is not valid.
<b>Action</b>	Enter a valid value and try again.
<b>INMBUE0065</b>	<b>Maximum payload size cannot take the value "0".</b>
<b>Explanation</b>	You have specified the value "0" for the maximum payload size parameter.
<b>Action</b>	Specify "-1" for unlimited size or an integer value greater than "0" for the maximum payload size, and try again.
<b>INMBUE0066</b>	<b>Select at least one request content type.</b>
<b>Explanation</b>	A request content type is required if you have added either a schema or an example content for request.
<b>Action</b>	Add at least one content type for request.
<b>INMBUE0067</b>	<b>Select at least one response content type.</b>
<b>Explanation</b>	A response content type is required if you have added either a schema or an example content for response.
<b>Action</b>	Add at least one content type for response.
<b>INMBUE0068</b>	<b>The request(s) of this method do not consume the content type(s) {0}.</b>
<b>Explanation</b>	There is a mismatch between the method's request Content-Types and the Content-Type set for the request.
<b>Action</b>	Provide the correct method content type that matches the request content type.
<b>INMBUE0069</b>	<b>The response(s) of this method do not consume the content type(s) {0}.</b>
<b>Explanation</b>	There is a mismatch between the method's response Content-Types and the Content-Type set for the Response.
<b>Action</b>	Provide the correct method content type that matches the response content type.

<b>INMBUE0074</b>	<b>The error status code is not valid.</b>
<b>Explanation</b>	You have entered an incorrect error status code.
<b>Action</b>	Enter an error status code between 400 to 500.
<b>INMBUE0076</b>	<b>Message Subject field cannot be empty.</b>
<b>Explanation</b>	You have not entered the subject line of the email which is used for the consumer notifications.
<b>Action</b>	Enter the subject line of the email in the Message Subject field.
<b>INMBUE0077</b>	<b>Message Body field cannot be empty.</b>
<b>Explanation</b>	You have not entered the message content of the email which is used for the consumer notifications.
<b>Action</b>	Enter the message content of the email in the Message Body field.
<b>INMBUE0078</b>	<b>Required alias '<code>#{sys:dyn-Endpoint}</code>' is missing in the Route Through field.</b>
<b>Explanation</b>	You have not specified the alias ' <code>#{sys:dyn-Endpoint}</code> ' in the Route Through field.
<b>Action</b>	Make sure the alias ' <code>#{sys:dyn-Endpoint}</code> ' is specified in the Route Through field.
<b>INMBUE0079</b>	<b>Taxonomy name cannot be empty.</b>
<b>Explanation</b>	You have not provided a name for the taxonomy.
<b>Action</b>	Provide a name for the taxonomy.
<b>INMBUE0080</b>	<b>Asset type name cannot be empty.</b>
<b>Explanation</b>	You have not provided a name for the asset type.
<b>Action</b>	Provide a name for the asset type.
<b>INMBUE0081</b>	<b>Invalid profile name.</b>
<b>Explanation</b>	The entered value for profile name is not valid.
<b>Action</b>	Enter a valid profile name.
<b>INMBUE0082</b>	<b>Invalid attribute name.</b>
<b>Explanation</b>	The entered value for attribute name is not valid.
<b>Action</b>	Enter a valid attribute name.

<b>INMBUI0005</b>	<b>No document(s) available.</b>
<b>Explanation</b>	Documents are not available to download.
<b>Action</b>	No action required.
<b>INMBUI0006</b>	<b>Selected item(s) not applicable for Export</b>
<b>Explanation</b>	The selected item(s) are not applicable for export.
<b>Action</b>	No action required.
<b>INMBUI0008</b>	<b>No target found for deployment.</b>
<b>Explanation</b>	No target found was for deployment
<b>Action</b>	Register a target for deployment before initiating the Publish action.
<b>INMBUI0010</b>	<b>Error while instantiating the activity {0}.</b>
<b>Explanation</b>	Could not instantiate the activity {0}. The failure is likely to be cause by incorrect configuration.
<b>Action</b>	Verify that the activity has been configured correctly.
<b>INMBUI0027</b>	<b>Unable to view the profile information.</b>
<b>Explanation</b>	You do not have sufficient access right to view the profile information.
<b>Action</b>	Verify that you have the appropriate access rights. Contact your administrator and request access if necessary and then try again.
<b>INMBUI0033</b>	<b>Enter the base URL for API requests.</b>
<b>Explanation</b>	Base URL is mandatory for making requests to the API.
<b>Action</b>	Enter the base URL for API requests.
<b>INMBUI0034</b>	<b>Enter a namespace.</b>
<b>Explanation</b>	A namespace should be specified for the API.
<b>Action</b>	Enter a valid namespace.
<b>INMBUI0057</b>	<b>Select a sandbox for base URL.</b>
<b>Explanation</b>	No sandbox has been selected for the base URL. A base URL is classified with a sandbox environment such as a Development, Production or Test to indicate the usage.
<b>Action</b>	Select a sandbox for the base URL.

<b>INMBUI0075</b>	<b>Enter the Endpoint Prefix for the API.</b>
<b>Explanation</b>	Endpoint Prefix is optional for Virtual API.
<b>Action</b>	Enter the Endpoint Prefix for the API.
<b>INMBUW0001</b>	<b>Invalid search query.</b>
<b>Explanation</b>	You have entered an invalid search query, possibly because the query is not available in the CentraSite repository.
<b>Action</b>	The search query {0} is not available. Configure your portlet with a valid search query.
<b>INMBUW0047</b>	<b>Specified value is a duplicate value. Specify a valid unique value.</b>
<b>Explanation</b>	An alias value is already defined for this target.
<b>Action</b>	Specify a valid unique value.
<b>INMBUW0048</b>	<b>A value is already specified for the target. Select a different gateway.</b>
<b>Explanation</b>	This is an alias value already defined for this target.
<b>Action</b>	Select a different gateway.
<b>INMBUW0049</b>	<b>Provide an alias value.</b>
<b>Explanation</b>	You have to provide an alias value.
<b>Action</b>	No action required.
<b>INMBUW0050</b>	<b>Specify a value for this target, else delete the row.</b>
<b>Explanation</b>	You must specify a value for this target.
<b>Action</b>	Specify target specific alias value or else delete the entire row.
<b>INMBUW0061</b>	<b>To add multiple resources, you must manually reconfigure the Route to endpoint field. To reconfigure the Route to endpoint, append the resource path tokenizer <code>/\${sys:resource_path}</code> with the base URL of the native API in the format <code>&lt;base-url&gt;/\${sys:resource_path}</code>. For more information about handling multiple resources, see the documentation <a href="#">Run-Time Goveranance with CentraSite</a>.</b>
<b>Explanation</b>	To add multiple resources, you must manually reconfigure the Route to endpoint field. To reconfigure the Route to endpoint, append the resource path tokenizer <code>/\${sys:resource_path}</code> with the base URL of the native API in the format <code>&lt;base-url&gt;/\${sys:resource_path}</code> . For more information about handling multiple resources, see the documentation <a href="#">Run-Time Goveranance with CentraSite</a> .
<b>Action</b>	To add multiple resources, you must manually reconfigure the Route to endpoint field. To reconfigure the Route to endpoint, append the resource path tokenizer <code>/\${sys:resource_path}</code> with the base URL of the native API in the format

<base-url>/\${sys:resource\_path}. For more information about handling multiple resources, see the documentation Run-Time Governance with CentraSite.

**INMBU\_ERR\_EMPTY\_ERROR\_TEMPLATE – Select an error template in the Use as Default option.**

**Explanation** You have not specified an error template to use as the default in the Use as Default option.

**Action** Configure a default error template for the error condition and try again.

**INMBU\_ERR\_SAME\_TYPE\_MULTIPLE\_SELECTION – Multiple error templates are not permitted for same content type.**

**Explanation** You have selected more than one error template for the same content type.

**Action** Remove duplicate error templates with same content type and try again.

**INMBU\_LBL\_API\_UNPUBLISH\_WARNING – If you unpublish an API from API Portal, the API keys associated with the API will be lost.**

**INMBU\_LBL\_USER\_BEEPER\_PHONE – Beeper**

**INMBU\_LBL\_USER\_DOMAIN\_NAME – Display Name**

**INMBXE0003 Enter a valid username or password.**

**Explanation** You have entered an invalid username or password. To log in to CentraSite, you must enter a valid username and password.

**Action** Enter a valid username or password.

**INMBXE0004 Enter your username (full email address).**

**Explanation** You have entered an invalid username. To log in to CentraSite, you must enter your email address as username.

**Action** Enter a valid username.

**INMBXE0005 Enter a valid email address (e.g. example@example)**

**Explanation** You have entered a wrong or blank email address. You must enter a valid email address (e.g. example@example).

**Action** Enter a valid email address (e.g. example@example).

<b>INMBXE0009</b>	<b>Enter your password.</b>
<b>Explanation</b>	To request an account in CentraSite, you must enter a password.
<b>Action</b>	Enter a valid password.
<b>INMBXE0010</b>	<b>Enter your first name. Example: John.</b>
<b>Explanation</b>	To request an account in CentraSite, you must enter your first name.
<b>Action</b>	Enter your first name.
<b>INMBXE0011</b>	<b>Enter your last name. Example: Smith.</b>
<b>Explanation</b>	To request an account in CentraSite, you must enter your last name.
<b>Action</b>	Enter your last name.
<b>INMBXE0012</b>	<b>Enter a reason for requesting access to CentraSite.</b>
<b>Explanation</b>	To register an account in CentraSite, you must provide a valid reason for requesting the account to CentraSite.
<b>Action</b>	Enter a valid reason for requesting access to CentraSite.
<b>INMBXE0016</b>	<b>Password does not match</b>
<b>Explanation</b>	The password for Confirm Password does not match the given password.
<b>Action</b>	Confirm the given password by entering the same password again.
<b>INMBXE0017</b>	<b>Access is denied.</b>
<b>Explanation</b>	Could not log in to the CentraSite Business UI as a guest user, probably because the guest access is disabled.
<b>Action</b>	Verify the centrasite.xml file. Make sure that the property element "Guest visibility" is set to "true". For more information about the usage of "Guest visibility" property, see the CentraSite Administrator's Guide. If the property is already set to "true" and the error persists, contact your administrator.
<b>INMBXI0001</b>	<b>CentraSite gives your organization a single place to store, find and reuse service and process assets. That speeds up development. Automatic policy enforcement helps you ensure new services and processes perform consistently and to the quality standards you've set.</b>
<b>Explanation</b>	This message provides an introduction to CentraSite in the login page.
<b>Action</b>	Get an overview of the product.

<b>INMBXI0002</b>	<b>Log in to Your Account</b>
<b>Explanation</b>	Enter the user account credentials to log in to CentraSite.
<b>Action</b>	Log in to CentraSite.
<b>INMBXI0006</b>	<b>Create Your Account</b>
<b>Explanation</b>	Request for an account in CentraSite.
<b>Action</b>	Enter the user credentials and create an account in CentraSite.
<b>INMBXI0008</b>	<b>Thank you for your registration in CentraSite.</b>
<b>Explanation</b>	Thank you for your registration. We will contact you soon and inform you of the next steps. In the meantime you may visit CentraSite as a guest.
<b>Action</b>	Log in to CentraSite as a guest.
<b>INMBXI0013</b>	<b>You will be contacted by a CentraSite administrator.</b>
<b>Explanation</b>	The CentraSite administrator will process your registration request and contact you shortly.
<b>Action</b>	The CentraSite Administrator will process your request and contact you shortly.
<b>INMBXI0014</b>	<b>Access CentraSite as a guest.</b>
<b>Explanation</b>	You may access CentraSite as a guest.
<b>Action</b>	Access CentraSite as a guest.
<b>INMBXW0015</b>	<b>JavaScript is not enabled in your web browser.</b>
<b>Explanation</b>	If JavaScript is already installed but the application does not work, you may need to enable JavaScript in your web browser.
<b>Action</b>	Enable the JavaScript in your web browser.
<b>INMBX_LBL_ERROR_PAGE – Enable your CentraSite license</b>	
<b>Explanation</b>	Members of the CentraSite Community Edition (CE) are not allowed to use the CentraSite Business UI. This is because the Community Edition is a free-of-charge version of CentraSite that does not include a CentraSite license. In order to use the CentraSite Business UI, you must have the CentraSite license installed.
<b>Action</b>	Install the CentraSite license. For further information contact your software supplier.

**INMBX\_LBL\_IE8\_COMPATIBILITY\_TEXT – CentraSite Business UI is not designed to run in compatibility mode. Disable the compatibility mode to render the Business UI.**

**Explanation** CentraSite Business UI is not designed to run in compatibility mode.

**Action** Disable the compatibility mode to render the Business UI.

**INMBX\_LIC\_ACCESS\_ERROR – Error accessing license information. Check the error log for more information.**

**Explanation** Error encountered while accessing the CentraSite license information.

**Action** If this error persists, contact your administrator.

**INMCBE0009 You do not have sufficient access rights to modify this object.**

**Explanation** You do not have sufficient access rights to modify this object.

**Action** Verify that you have the appropriate access rights. Contact your administrator and request access if necessary and then try again.

**INMCBE0012 Invalid password specified.**

**Explanation** You have specified an invalid password.

**Action** Correct password and try again.

**INMCBE0013 HTTP response {0} received while updating password.**

**Explanation** While updating the password, the user received an http error with the given error code.

**Action** Analyse the reason for this error based on the http error code.

**INMCBE0014 Error occurred when reading configuration file at {0}.**

**Explanation** An error occurred when reading the user-specific configuration file at the given location.

**Action** Refer to the stack trace - you may need to delete the given file from the repository.

**INMCBE0015 You have entered no file or folder name.**

**Explanation** You have entered no file or folder name.

**Action** Enter a name.

<b>INMCBE0016</b>	<b>The name you have entered is invalid. Web Folder names cannot include any of the following characters: :?*&lt;&gt; \"</b>
<b>Explanation</b>	The name you have entered is invalid. Web folder names cannot include any of the following characters: :?*<> \"
<b>Action</b>	Specify another name.
<b>INMCBE0017</b>	<b>The name you have entered exceeds the maximum allowed name length.</b>
<b>Explanation</b>	The name you have entered exceeds the maximum allowed name length.
<b>Action</b>	Specify a shorter name.
<b>INMCBE0018</b>	<b>No report definition is linked to given report object</b>
<b>Explanation</b>	The report must have an external link referencing the report definition created via BIRT.
<b>Action</b>	Repeat the import of the report either via the "Import Report" command in the user interface or via the "Export to CentraSite" command in the BIRT plugin of Eclipse.
<b>INMCBE0020</b>	<b>Failed to obtain value of parameter {0}</b>
<b>Explanation</b>	Could not determine value for the parameter with given name.
<b>Action</b>	Contact your software supplier.
<b>INMCBE0021</b>	<b>The domain of the specified user is invalid.</b>
<b>Explanation</b>	The domain of the specified user is invalid. For non-windows platforms, only the domain LOCAL or LDAP is allowed.
<b>Action</b>	Enter a valid domain. For non-Windows platforms, only the domain LOCAL or LDAP is allowed.
<b>INMCBE0022</b>	<b>Object no longer available</b>
<b>Explanation</b>	The selected object does not exist, possibly because it has been implicitly discarded before or an import has failed.
<b>Action</b>	Check recent activities.
<b>INMCBE0024</b>	<b>The passwords you typed do not match.</b>
<b>Explanation</b>	The passwords you typed do not match.
<b>Action</b>	Enter the new password in both text boxes.

<b>INMCBE0027</b>	<b>The specified user does not exist.</b>
<b>Explanation</b>	The specified user is not present in CentraSite.
<b>Action</b>	Specify a valid user.
<b>INMCBE0029</b>	<b>Error occurred when initializing CentraSite Control - disabling plug-in.</b>
<b>Explanation</b>	An error occurred when initializing CentraSite Control.
<b>Action</b>	Check details of error message for further information.
<b>INMCBE0030</b>	<b>Invalid change of data type for existing data.</b>
<b>Explanation</b>	An attempt is being made to change the data type of a property that already has data present that is not of the type specified.
<b>Action</b>	Select a data type that matches the existing data.
<b>INMCBE0032</b>	<b>Asset name must not be empty.</b>
<b>Explanation</b>	No name is specified for the asset.
<b>Action</b>	Enter a valid asset name.
<b>INMCBE0033</b>	<b>Asset type not valid.</b>
<b>Explanation</b>	The selected asset type is not valid for this operation.
<b>Action</b>	Select a valid asset type.
<b>INMCBE0035</b>	<b>The associated object of type Associated with could not be deleted</b>
<b>Explanation</b>	User does not have permission to delete the associated object
<b>Action</b>	Grant delete permission to the user for the associated object
<b>INMCBE0036</b>	<b>The associated object of type WS-Policy attachment could not be deleted</b>
<b>Explanation</b>	The user does not have permission to delete the WS-Policy associated with the virtual service.
<b>Action</b>	Verify that you have the appropriate access rights. Contact your administrator and request access if necessary and then try again.

<b>INMCBE0037</b>	<b>The associated object of type External Link could not be deleted</b>
<b>Explanation</b>	The user does not have permission to delete associated external links.
<b>Action</b>	Verify that you have the appropriate access rights. Contact your administrator and request access if necessary and then try again.
<b>INMCBE0038</b>	<b>Asset with name {0} already exists of type {1}</b>
<b>Explanation</b>	There is a duplicate asset name.
<b>Action</b>	Enter another name for the asset.
<b>INMCBI0001</b>	<b>New ExternalLink has been copied to the internal clipboard. It can be added to arbitrary registry objects now.</b>
<b>Explanation</b>	The newly created ExternalLink object has been copied to the internal clipboard. It can be used to add the ExternalLink to any registry object via the tab "External Links".
<b>Action</b>	No action required.
<b>INMCBW0002</b>	<b>Resource cannot be deleted as it is the target of one or more ExternalLink objects.</b>
<b>Explanation</b>	You cannot delete this resource as it is referenced by one or more external links.
<b>Action</b>	You may run the impact analysis in order to determine the registry objects that have an external link referencing this resource.
<b>INMCBW0003</b>	<b>Folder cannot be deleted as it is the target of one or more ExternalLink objects.</b>
<b>Explanation</b>	You cannot delete this folder as it is referenced by one or more External Links.
<b>Action</b>	You may run the impact analysis in order to determine the registry objects that have an external link depending on this folder.
<b>INMCBW0004</b>	<b>Resource cannot be renamed as it is the target of one or more ExternalLink objects.</b>
<b>Explanation</b>	You cannot rename this resource as it is referenced by one or more registry objects.
<b>Action</b>	You may run the impact analysis in order to determine the registry objects that have an external link depending on this resource.
<b>INMCBW0007</b>	<b>No report is linked to type {0}.</b>
<b>Explanation</b>	No report has been associated to the type via the 'Link Reports' command.
<b>Action</b>	You can associate a report via the command 'Link Reports' for the respective type.

<b>INMCBW0010</b>	<b>No operation is defined for type {0}.</b>
<b>Explanation</b>	The definition of the respective type does not contain any operations.
<b>Action</b>	You can add operations via the 'Modify Type' command for the respective type.
<b>INMCBW0011</b>	<b>You are connected as a read-only user. This will lead to limited functionality being available.</b>
<b>Explanation</b>	A read-only user does not have privileges to modify registry objects.
<b>Action</b>	Log in as another user if you want to modify registry objects.
<b>INMCBW0019</b>	<b>No items have been exported</b>
<b>Explanation</b>	No items have been exported - this may happen if items selected for export are embedded into other objects and thus cannot be exported without their parent objects.
<b>Action</b>	Select the parent object for export.
<b>INMCBW0031</b>	<b>File cannot be deleted as it is the target of one or more Favorite objects of My CentraSite.</b>
<b>Explanation</b>	You cannot delete this file as it is referenced by one or more External Links in My CentraSite.
<b>Action</b>	You may run the impact analysis in order to determine the Favorite Object in My CentraSite that has an external link referencing this resource.
<b>INMCCE0001</b>	<b>Command {0} is not supported by CentraSite command line tool</b>
<b>Explanation</b>	The specified command cannot be executed by the CentraSite command line tool. It is not in the list of supported commands.
<b>Action</b>	Please check the usage of CentraSiteCommand and make sure you specify the command which is listed in the usage.
<b>INMCCE0002</b>	<b>Exception while fetching email properties</b>
<b>Explanation</b>	CentraSiteCommand is not able to fetch the email properties from CentraSite.
<b>Action</b>	Please make sure all the parameters are valid and re-execute the command.
<b>INMCCE0003</b>	<b>Exception while storing email properties</b>
<b>Explanation</b>	CentraSiteCommand is not able to store the email properties into CentraSite.
<b>Action</b>	Please make sure all the parameters are valid and re-execute the command.

<b>INMCCE0006</b>	<b>Parsing failed! Please make sure configuration file syntax and path are correct.</b>
<b>Explanation</b>	Parsing the CentraSiteCommand option and/or configFile failed.
<b>Action</b>	Please make sure the CentraSiteCommand options are specified properly and configFile exists in the specified location.
<b>INMCCE0007</b>	<b>Parsing failed! Please make sure configuration file syntax and path are correct.</b>
<b>Explanation</b>	This error can occur because of two reasons. 1) The syntax of the configuration file is not valid. 2) The specified configuration file path is incorrect.
<b>Action</b>	Please refer to the documentation for information on creating a valid configuration file.
<b>INMCCE0008</b>	<b>Failed to execute command {0}</b>
<b>Explanation</b>	Error occurred while executing the command.
<b>Action</b>	Please check the error message for details.
<b>INMCCE0009</b>	<b>Internal error occurred</b>
<b>Explanation</b>	This error may occur because of problems in the system execution.
<b>Action</b>	Please contact the administrator.
<b>INMCCE0010</b>	<b>{0} is an invalid log unit, possible values are {1}</b>
<b>Explanation</b>	The provided log unit is invalid. This can occur when the user specifies a log unit other than the supported ones.
<b>Action</b>	Please refer to the error message for the possible values.
<b>INMCCE0011</b>	<b>{0} is invalid log unit value, possible values are {1}</b>
<b>Explanation</b>	The provided log unit value is invalid. This can occur when the user specifies a log unit value other than the supported ones.
<b>Action</b>	Please refer to the error message for the possible values.
<b>INMCCE0012</b>	<b>Purger unavailable for {0}</b>
<b>Explanation</b>	No purger was found for the given log unit. This error can occur if an appropriate purger is not found/available for the given log unit.
<b>Action</b>	Please ensure the correct log units are provided in the configuration file.

<b>INMCCE0013</b>	<b>Purging stopped for {0} as there is no write permission for export location {1}</b>
<b>Explanation</b>	This error will occur when the user does not have the required write permission for the export location.
<b>Action</b>	Please provide required permissions before purging.
<b>INMCCE0014</b>	<b>Insufficient disk space in {0}. Required space {1}. Available space {2}.</b>
<b>Explanation</b>	The specified export location does not contain enough space for the exported logs. Please refer to the error message for the available and required space.
<b>Action</b>	Please choose a different export location.
<b>INMCCE0015</b>	<b>Purging Failed. Following error occurred {0}.</b>
<b>Explanation</b>	Purging failed for the log unit mentioned in the error message. Some failures may happen because of network time out and similar problems.
<b>Action</b>	Please try again later or contact the administrator for assistance.
<b>INMCCE0016</b>	<b>Unable to archive the export directory {0}</b>
<b>Explanation</b>	The archiving of the exported logs failed. This may happen because of files being accessed by an other application.
<b>Action</b>	Please close the other application and try again.
<b>INMCCE0017</b>	<b>Unable to create the export directory {0}</b>
<b>Explanation</b>	This error can occur when the user does not have the required write permission for the export location or the export location is invalid.
<b>Action</b>	Please provide required permissions before purging or make sure the export location is valid.
<b>INMCCE0018</b>	<b>Command {0} is not supported by CentraSite command line tool</b>
<b>Explanation</b>	The displayed command is invalid. This can occur when the user specifies a command other than the supported ones. For example, to purge logs, you should specify -command purge_logs.
<b>Action</b>	Please refer to the documentation for the list of supported commands and their usage.

<b>INMCCE0019</b>	<b>castUri option is mandatory for the command {1}</b>
<b>Explanation</b>	The castUri option is required for the specified commands.
<b>Action</b>	Please specify the cast URI in the -castUri option.
<b>INMCCE0020</b>	<b>CentraSite Application Server Object (CAST) already registered in CentraSite with the specified castUri {0}</b>
<b>Explanation</b>	The CAST will be identified using the host present in castUri option, and CentraSite already contains a CAST registered with the specified host.
<b>Action</b>	Specify a different value in the castUri option or de-register the existing CAST and register it again. A CAST can be de-registered using the deregister_cast command.
<b>INMCCE0021</b>	<b>{0} and {1} both present in configuration for log unit {2}</b>
<b>Explanation</b>	The tags Until and OlderThan are both present in the configuration file.
<b>Action</b>	Please use only one of the given tags in the configuration file. For more information, please refer to the Administration guide.
<b>INMCCE0022</b>	<b>Unable to obtain policy query manager. Cause: {0}</b>
<b>Explanation</b>	It was not possible to obtain the policy query manager.
<b>Action</b>	Verify your installation or contact the administrator.
<b>INMCCE0023</b>	<b>Exception occurred during restore operation. Cause: {0}.</b>
<b>Explanation</b>	An exception occurred during the restore operation.
<b>Action</b>	Please check the exception message for more details.
<b>INMCCE0024</b>	<b>Archive seal error. Invalid start/end date entries in the archive seal properties for the Archive file {0} located in {1}.</b>
<b>Explanation</b>	An archive seal error occurred. There are invalid start/end date entries in the archive seal properties.
<b>Action</b>	Please verify the seal properties file for correctness.
<b>INMCCE0025</b>	<b>Error creating archive seal file. Cause {0}.</b>
<b>Explanation</b>	An error occurred while creating the archive seal file.
<b>Action</b>	Please check the error message for more details.

<b>INMCCE0026</b>	<b>Command option {0} missing</b>
<b>Explanation</b>	The specified command requires a command option.
<b>Action</b>	See the usage information for the correct command syntax.
<b>INMCCE0028</b>	<b>Domain {0} not found</b>
<b>Explanation</b>	The domain to be processed does not exist.
<b>Action</b>	Correct the specified domain name.
<b>INMCCE0029</b>	<b>Domain {0} already exist</b>
<b>Explanation</b>	A domain entry with the specified name is already present.
<b>Action</b>	Correct the specified domain name.
<b>INMCCE0030</b>	<b>Error processing configuration file: {0}</b>
<b>Explanation</b>	The configuration file does not contain a valid domain entry.
<b>Action</b>	Correct the domain entry in the configuration file.
<b>INMCCE0031</b>	<b>Error deleting domain entry: {0}</b>
<b>Explanation</b>	The specified domain entry could not be deleted.
<b>Action</b>	Contact your support center.
<b>INMCCE0039</b>	<b>{0} is not a LDAP domain</b>
<b>Explanation</b>	The validate command is only supported for LDAP domains.
<b>Action</b>	Specify an LDAP domain for validating an authentication configuration.
<b>INMCCE0040</b>	<b>LDAP basic configuration validation error</b>
<b>Explanation</b>	The basic LDAP configuration is invalid.
<b>Action</b>	Check the basic settings for the specified domain.
<b>INMCCE0041</b>	<b>LDAP user login validation error</b>
<b>Explanation</b>	The user could not log on with supplied user name and password.
<b>Action</b>	Check if the user name and password were specified correctly. Check the settings for the specified domain.

<b>INMCCE0042</b>	<b>LDAP user properties validation error</b>
<b>Explanation</b>	The user properties configuration is invalid.
<b>Action</b>	Check the user properties settings for the specified domain.
<b>INMCCE0043</b>	<b>LDAP group resolution validation error</b>
<b>Explanation</b>	The group resolution configuration is invalid.
<b>Action</b>	Check the group resolution settings for the specified domain.
<b>INMCCE0046</b>	<b>CS Admin user {0} not created</b>
<b>Explanation</b>	An error occurred while attempting to create a user with the CentraSite Administrator role.
<b>Action</b>	See the additional information provided to find the reason.
<b>INMCCE0047</b>	<b>CS Admin user {0} ({1}) not created</b>
<b>Explanation</b>	An error occurred while attempting to create a user with the CentraSite Administrator role.
<b>Action</b>	See the additional information provided to find the reason.
<b>INMCCE0053</b>	<b>{0} No Users found!</b>
<b>Explanation</b>	Searched users are not found
<b>Action</b>	user has to retry the search
<b>INMCCE0054</b>	<b>{0} No group properties found!</b>
<b>Explanation</b>	The group properties entered for the configuration are not correct.
<b>Action</b>	Correct the group properties.
<b>INMCCE0055</b>	<b>Can't get group properties. {0}</b>
<b>Explanation</b>	{0} --> error message from the LDAP
<b>Action</b>	re-configuration needs to be done
<b>INMCCE0056</b>	<b>cannot read user property {0}</b>
<b>Explanation</b>	{0} --> user property configured
<b>Action</b>	Re-configure the user properties

<b>INMCCE0058</b>	<b>cannot read user property {0}</b>
<b>Explanation</b>	{0} --> user property
<b>Action</b>	Re-configure the property
<b>INMCCE0059</b>	<b>{0} No user properties found!</b>
<b>Explanation</b>	{0} --> status warning message
<b>Action</b>	Re-configure the user properties
<b>INMCCE0060</b>	<b>Cannot contact the server. {0}</b>
<b>Explanation</b>	An attempt to connect to the server failed with the error message {0}.
<b>Action</b>	Re-configure the server properties.
<b>INMCCE0066</b>	<b>Unable to connect to socket!</b>
<b>Explanation</b>	There was a problem while connecting to the socket.
<b>Action</b>	Re-configure the connection.
<b>INMCCE0067</b>	<b>The old file is not deleted</b>
<b>Explanation</b>	An SSX trace file already exists and should be deleted.
<b>Action</b>	The SSX trace file needs to be deleted manually.
<b>INMCCE0068</b>	<b>Unable to listen to port</b>
<b>Explanation</b>	It was not possible to connect to the given port.
<b>Action</b>	Re-configure the port.
<b>INMCCE0088</b>	<b>Cannot write to log4j.</b>
<b>Explanation</b>	A message could not be written to the log4j log file.
<b>Action</b>	Check your log4j configuration.
<b>INMCCE0089</b>	<b>Cannot write in the {0}</b>
<b>Explanation</b>	A message could not be written to the SSX trace file {0}.
<b>Action</b>	Check your trace file configuration.

<b>INMCCE0090</b>	<b>cannot connect to database - possibly password wrong?</b>
<b>Explanation</b>	An error was detected while trying to connect to the database.
<b>Action</b>	Check that you entered the correct password.
<b>INMCCE0091</b>	<b>Database 'CentraSite' not running</b>
<b>Explanation</b>	The database 'CentraSite' is not running.
<b>Action</b>	Start the CentraSite database.
<b>INMCCE0092</b>	<b>{0} User authentication for "{0}" failed!</b>
<b>Explanation</b>	{0} --> State error {1} --> user name
<b>Action</b>	Re-enter the user authentication
<b>INMCCE0093</b>	<b>The user repository cannot be created with parameters: {0}</b>
<b>Explanation</b>	The user repository cannot be created with the given parameters.
<b>Action</b>	Re-configure the repository.
<b>INMCCE0094</b>	<b>{0} open SSXRepository - {1}</b>
<b>Explanation</b>	The SSX repository is not connected. The state error is {0} and the error message is {1}.
<b>Action</b>	Re-configure the connection to the repository.
<b>INMCCE0096</b>	<b>Can't get users {0}</b>
<b>Explanation</b>	The user mapping does not match any entry on the LDAP server.
<b>Action</b>	Provide a user mapping that matches an entry in LDAP.
<b>INMCCE0100</b>	<b>Can't get member of group {0}</b>
<b>Explanation</b>	An incorrect group ID was specified.
<b>Action</b>	Provide a correct group ID.
<b>INMCCE0103</b>	<b>Can't get groups for user {0}</b>
<b>Explanation</b>	No groups were found for the given user.
<b>Action</b>	Provide a proper group resolution.

<b>INMCCE0105</b>	<b>db 'CentraSite' not running</b>
<b>Explanation</b>	The database "CentraSite" is not currently active.
<b>Action</b>	Restart the "CentraSite" database.
<b>INMCCE0111</b>	<b>Failed to obtain the user {0} folder from CentraSite</b>
<b>Explanation</b>	Could not obtain the folder for the user with given name. The username is used to store a search definition in CentraSite.
<b>Action</b>	Make sure the user is registered in CentraSite.
<b>INMCCE0112</b>	<b>Search definition {0} already exists in CentraSite</b>
<b>Explanation</b>	An attempt was made to overwrite the existing report search definition.
<b>Action</b>	Make sure that you publish a new module or pass the argument -overwrite option_value.
<b>INMCCE0113</b>	<b>File {0} not found</b>
<b>Explanation</b>	The file {0} was not found in the folder.
<b>Action</b>	Check the availability of the file in the specified path.
<b>INMCCE0114</b>	<b>Retrieving the namespace from {0} failed because the namespace is null.</b>
<b>Explanation</b>	Cannot retrieve the namespace in the search definition since the namespace is null.
<b>Action</b>	Make sure a valid namespace is declared in the search definition.
<b>INMCCE0115</b>	<b>Namespace does not match with the module</b>
<b>Explanation</b>	The specified namespace does not match with the new module and search definition.
<b>Action</b>	Make sure that the namespace matches with the new module and search definition.
<b>INMCCE0116</b>	<b>Error loading the module</b>
<b>Explanation</b>	Failed to load the new module into CentraSite.
<b>Action</b>	Make sure the module format is correct.
<b>INMCCE0117</b>	<b>The namespace {0} is already used by a module in CentraSite</b>
<b>Explanation</b>	The specified namespace {0} was already used by a module. The module namespace should be unique in CentraSite.
<b>Action</b>	Define a new module namespace or use -overwrite TRUE to overwrite the existing module with this new namespace.

<b>INMCCE0118</b>	<b>The user you specified does not exist</b>
<b>Explanation</b>	The user you specified is not a known user.
<b>Action</b>	Specify the name of a known user.
<b>INMCCE0119</b>	<b>The number of Arguments for the command SetAsymmetricBindingConfigurations is not sufficient</b>
<b>Explanation</b>	The number of Arguments for the command SetAsymmetricBindingConfigurations is not sufficient
<b>Action</b>	Please provide proper number of Arguments
<b>INMCCE0120</b>	<b>Additional arguments provided to the Command SetAsymmetricBindingConfiguration</b>
<b>Explanation</b>	Additional arguments provided to the Command SetAsymmetricBindingConfiguration
<b>Action</b>	Please delete the unwanted arguments
<b>INMCCE0121</b>	<b>Required parameters missing</b>
<b>Explanation</b>	At least one of the parameters among InitiatorTokenInclusion, RecipientTokenInclusion, AlgorithmSuite and Layout required for the command.
<b>Action</b>	Please Add one of InitiatorTokenInclusion, RecipientTokenInclusion, AlgorithmSuite or Layout
<b>INMCCE0122</b>	<b>Invalid values provided for InitiatorTokenInclusion</b>
<b>Explanation</b>	InitiatorTokenInclusion value can only be one among Always, AlwaysToRecipient, AlwaysToInitiator, Once, Never
<b>Action</b>	Please provide one value among Always, AlwaysToRecipient, AlwaysToInitiator, Once, Never
<b>INMCCE0123</b>	<b>Invalid values provided for RecipientTokenInclusion</b>
<b>Explanation</b>	RecipientTokenInclusion value can be one among AlwaysToRecipient, Always, AlwaysToInitiator, Once, Never
<b>Action</b>	Please provide one among AlwaysToRecipient, Always, AlwaysToInitiator, Once, Never

<b>INMCCE0124</b>	<b>Invalid values provided for AlgorithmSuite</b>
<b>Explanation</b>	Invalid values provided for AlgorithmSuite
<b>Action</b>	Please provide a valid value
<b>INMCCE0125</b>	<b>Invalid value provided for Layout</b>
<b>Explanation</b>	Layout can have one value among Strict,Lax,LaxTsFirst,LaxTsLast
<b>Action</b>	Please provide one value among Strict,Lax,LaxTsFirst,LaxTsLast
<b>INMCCE0126</b>	<b>Exception writing the values to the repository .Reason : {0}</b>
<b>Explanation</b>	{0}
<b>Action</b>	{0}
<b>INMCCE0127</b>	<b>Exception while reading from the repository .Reason : {0}</b>
<b>Explanation</b>	{0}
<b>Action</b>	{0}
<b>INMCCE0129</b>	<b>The target for federation cannot be configured in the file at {0}</b>
<b>Explanation</b>	While trying to configure a target for federation, the file at location {0} will be modified to include the configuration. This error occurs if the "multicast" element cannot be found in the file.
<b>Action</b>	Check to ensure that the "multicast" element is available after "from" in the file {0}.
<b>INMCCE0130</b>	<b>The mandatory parameter(s), {0} is/are not specified for the command</b>
<b>Explanation</b>	The command requires some parameters for proper execution and they are not specified. Without these mandatory parameters, the execution cannot proceed.
<b>Action</b>	Provide the parameters needed for the command execution. If you don't know the command format, just provide the command name alone to get the usage for the command.
<b>INMCCE0131</b>	<b>The provided configFile {0} is not configured with the {1} element.</b>
<b>Explanation</b>	While parsing the XML configFile, {0}, the parser cannot obtain the {1} element which is needed for the command execution.
<b>Action</b>	Check the configFile {0} to see if the {1} element is configured. If it is not, provide the necessary details.

<b>INMCCE0132</b>	<b>The given federation id {0} does not have any target associated with it.</b>
<b>Explanation</b>	The provided ID {0} is not configured to have a federation target.
<b>Action</b>	Use show_uddi_federation to determine the list of configured federation targets and identifiers.
<b>INMCCE0139</b>	<b>An Internal Error occurred</b>
<b>Explanation</b>	An Internal Error occurred
<b>Action</b>	An Internal Error occurred
<b>INMCCE0140</b>	<b>Invalid Credentials</b>
<b>Explanation</b>	Invalid Credentials provided
<b>Action</b>	Please provide valid credentials
<b>INMCCE0141E</b>	<b>Provide details for any one of the following parameters: api, accessToken, apiPortal</b>
<b>Explanation</b>	An error occurred while sending the access tokens using the send AccessTokens command because the details for more than one of the parameters was provided.
<b>Action</b>	Provide details for any one of the parameters.
<b>INMCCE0142</b>	<b>Invalid Virtual Service name</b>
<b>Explanation</b>	The specified virtual service name is invalid.
<b>Action</b>	Enter a valid virtual service name.
<b>INMCCE0144</b>	<b>Invalid Target name</b>
<b>Explanation</b>	The target is not created or is invalid for virtual services to be deployed, undeployed or redeployed.
<b>Action</b>	Please provide a valid target name.
<b>INMCCE0152</b>	<b>Command execution failed. Parameter value cannot be null or empty.</b>
<b>Explanation</b>	A command parameter value was not entered.
<b>Action</b>	Before you execute a command, make sure that you set a value for every parameter in the command.

<b>INMCCE0153</b>	<b>Command execution failed. Description of the path already exists.</b>
<b>Explanation</b>	Description of the command path already exists.
<b>Action</b>	Before you execute a command, make sure that you set a valid command path.
<b>INMCCE0154</b>	<b>Command execution failed. Combination of the path already exists.</b>
<b>Explanation</b>	Combination of the command path already exists.
<b>Action</b>	Before you execute a command, make sure that you set a valid command combination.
<b>INMCCE0155</b>	<b>Command execution failed. The name for command token is not valid.</b>
<b>Explanation</b>	You have entered an invalid name for the command token.
<b>Action</b>	Enter a valid name for the command token.
<b>INMCCE0156</b>	<b>Command execution failed. The input for command token is not valid.</b>
<b>Explanation</b>	You have entered invalid input for the command token.
<b>Action</b>	Enter a valid input for the command token.
<b>INMCCE0157</b>	<b>Command execution failed. Path already exists for the tokens: {0}</b>
<b>Explanation</b>	The path already exists for the command tokens: {0}.
<b>Action</b>	Before you execute a command, make sure that you set a valid path for the tokens.
<b>INMCCE0158</b>	<b>Command execution failed. Parameter value cannot be null or empty.</b>
<b>Explanation</b>	A command parameter value was not entered.
<b>Action</b>	Before you execute a command, make sure that you set a value for every parameter in the command.
<b>INMCCE0159</b>	<b>Command execution failed. Token or parameter value cannot be null or empty.</b>
<b>Explanation</b>	A command token or parameter value was not entered.
<b>Action</b>	Before you execute a command, make sure that you set a value for every token and parameter in the command.
<b>INMCCE0160</b>	<b>Command execution failed. Combination of the command tokens {} already exists.</b>
<b>Explanation</b>	An attempt was made to specify the same token that is already present in the command.
<b>Action</b>	Before you execute a command, make sure that you set a valid token in the command.

<b>INMCCE0161</b>	<b>Parameter {0} should not empty.</b>
<b>Explanation</b>	The '{0}' parameter is mandatory.
<b>Action</b>	Enter a value for the {0} parameter.
<b>INMCCE0162</b>	<b>Check the length of the command help.</b>
<b>Explanation</b>	The command help text you have entered does not meet the minimum requirement of {0} characters.
<b>Action</b>	Correct the help text appropriately.
<b>INMCCE0163</b>	<b>Command execution failed. Unable to join null or empty strings, or a single string.</b>
<b>Explanation</b>	The combination of a null and empty string, or a null and single string is not valid.
<b>Action</b>	Before you execute a command, make sure that you set valid combination of strings in the command.
<b>INMCCE0164</b>	<b>Configuration property {0} cannot be empty.</b>
<b>Explanation</b>	The configuration property '{0}' was not specified.
<b>Action</b>	Specify the property {0}.
<b>INMCCE0165</b>	<b>Command execution failed. Invalid value {0} for configuration parameter {1}.</b>
<b>Explanation</b>	The value {0} for configuration parameter {1} is not valid.
<b>Action</b>	Before you execute a command, make sure that you set a valid value for parameter {1} in the command.
<b>INMCCE0166</b>	<b>Invalid input file.</b>
<b>Explanation</b>	The specified input file is invalid, possibly because there are one or more elements which are not allowed for this command.
<b>Action</b>	Specify a valid input file and try again. If the problem persists, contact your administrator.
<b>INMCCE0170</b>	<b>The default domain {0} cannot be deleted.</b>
<b>Explanation</b>	The specified domain entry is the domain displayed by default and cannot be deleted.
<b>Action</b>	To delete the default domain first designate a different domain as the default domain.

<b>INMCCE0171</b>	<b>The "set Log" command failed due to incorrect data.</b>
<b>Explanation</b>	This is an internal error probably because the "set Log" command expects starting element {0} instead of {1}.
<b>Action</b>	Verify the config.xml contents. Make sure the configuration has starting element as <LogSettings>. For more information about the usage of "set Log" command, see the CentraSite Administrator's Guide. Contact your administrator if the problem persists.
<b>INMCCE0172</b>	<b>The "set Log" command failed due to incorrect data.</b>
<b>Explanation</b>	This is an internal error probably because the specified "set Log" command expects child element {0} instead of {1}.
<b>Action</b>	Verify the config.xml contents. Make sure the configuration has child element as <LogUnit>. For more information about the usage of "set Log" command, see the CentraSite Administrator's Guide. Contact your administrator if the problem persists.
<b>INMCCE0173</b>	<b>The "set Log" command failed due to incorrect data.</b>
<b>Explanation</b>	This is an internal error probably because the "set Log" command expects a <LogUnit> element {0} instead of {1}.
<b>Action</b>	Verify the config.xml contents. Make sure the configuration contain <LogUnit> element with attribute <name>. For more information about the usage of "set Log" command, see the CentraSite Administrator's Guide. Contact your administrator if the problem persists.
<b>INMCCE0174</b>	<b>Upload failed! The file {0} has an invalid extension.</b>
<b>Explanation</b>	An attempt was made to upload the specified file {0} with extension other than .xml.
<b>Action</b>	Upload a valid XML file.
<b>INMCCE0175</b>	<b>Failed to obtain the Organization folder of the user {0} from CentraSite.</b>
<b>Explanation</b>	Could not fetch the Organization folder of the specified user {0}, possibly because the user has been deleted from the CentraSite registry.
<b>Action</b>	Make sure the specified user exists in the CentraSite registry. If the user exists and the error persists, contact your administrator.
<b>INMCCE0178</b>	<b>The set gateway command failed. {0}</b>
<b>Explanation</b>	The gateway command has failed to create a new gateway or update the specified gateway. You might not have the necessary permissions to create/update a gateway in CentraSite or CentraSite might be down.
<b>Action</b>	Ensure that you have the necessary permissions in CentraSite and that CentraSite is up and running. Also, provide all the mandatory parameters when you run the command to create/update a gateway.

<b>INMCCE0180</b>	<b>Gateway deletion failed. {0}</b>
<b>Explanation</b>	The gateway command has failed to delete the specified gateway. You might not have the necessary permissions to delete a gateway in CentraSite or CentraSite might be down.
<b>Action</b>	Ensure that you have the necessary permissions in CentraSite and that CentraSite is up and running. Also, ensure that you have provided the correct gateway name or ID.
<b>INMCCE0181</b>	<b>The list gateways command failed. {0}</b>
<b>Explanation</b>	Check the CentraSite logs for the reason for the failure.
<b>Action</b>	Run the command again after you have identified and fixed the issue(s). Ensure that all the parameters are correct and valid before you run the command. If the issue persists, contact Software AG support.
<b>INMCCE0183</b>	<b>Unable to find a gateway in CentraSite with the name or key "{0}".</b>
<b>Explanation</b>	You have provided a gateway name or key that does not exist in CentraSite. The delete gateway command failed to delete the specified gateway.
<b>Action</b>	Ensure that the gateway name or ID that you specify is correct and exists in CentraSite.
<b>INMCCE0184</b>	<b>Unable to find an organization in CentraSite with the specified name or key "{0}".</b>
<b>Explanation</b>	You have provided an organization name or key that does not exist in CentraSite. The set gateway command failed to create a new gateway.
<b>Action</b>	Ensure that the organization name or key that you specify is correct and exists in CentraSite.
<b>INMCCE0185</b>	<b>Unable to find a sandbox in CentraSite with the specified name or key "{0}".</b>
<b>Explanation</b>	You have provided a name or key of a sandbox category that does not exist in CentraSite. The set gateway command failed to create a new gateway.
<b>Action</b>	Ensure that the sandbox category with the specified name or key exists in CentraSite.
<b>INMCCE0186</b>	<b>Report with that name doesn't exist or name is not unique.</b>
<b>Explanation</b>	Either the name is misspelled or multiple reports with that name exist.
<b>Action</b>	Check the report name and provide a valid report name.

<b>INMCCE0187</b>	<b>Sharing of report failed.</b>
<b>Explanation</b>	Sharing of report failed possibly due to an internal error.
<b>Action</b>	Contact your local support.
<b>INMCCE0189E</b>	<b>Error occurred while publishing API Key {0} to API Portal {1}.</b>
<b>Explanation</b>	An error occurred while trying to publish API Key {0} to API Portal {1}.
<b>Action</b>	Ensure that the API Portal server is up and running. If the problem persists, contact your administrator.
<b>INMCCE0191E</b>	<b>Error occurred while publishing OAuth token {0} to API Portal {1}.</b>
<b>Explanation</b>	An error occurred while trying to publish OAuth token {0} to API Portal {1}.
<b>Action</b>	Ensure that the API Portal server is up and running. If the problem persists, contact your administrator.
<b>INMCCE0197</b>	<b>"{0}" is not a valid value for "{1}".</b>
<b>Explanation</b>	You have provided a value which is not part of the specified list.
<b>Action</b>	Ensure that the provided value is part of the specified list.
<b>INMCCE0198</b>	<b>Report with name "{0}" was not found.</b>
<b>Explanation</b>	You have provided a report name that does not exist in CentraSite.
<b>Action</b>	Ensure that the report name that you specified is correct and exists in CentraSite.
<b>INMCCE0199</b>	<b>More than one reports with the name "{0}" found.</b>
<b>Explanation</b>	You have provided a report name which is not unique in CentraSite.
<b>Action</b>	If the report name is not unique in CentraSite specify the report id.
<b>INMCCE0200</b>	<b>Unable to add a new Report to CentraSite.</b>
<b>Explanation</b>	An error occurred during the "add report" operation.
<b>Action</b>	A new report could not be created. For more information check the CentraSiteCommand log.

<b>INMCCE0201</b>	<b>Unable to delete the report with the id "{0}".</b>
<b>Explanation</b>	An error occurred during the "delete report" operation.
<b>Action</b>	Ensure that the report id is correct and exists in CentraSite. For more information check the CentraSiteCommand log.
<b>INMCCE0202</b>	<b>Unable to access the specified Report Template file.</b>
<b>Explanation</b>	You have provided a path to a report template file which does not exist.
<b>Action</b>	Ensure that the specified report template file exists.
<b>INMCCE0203</b>	<b>Unable to update the report with id "{0}".</b>
<b>Explanation</b>	An error occurred during the "update report" operation.
<b>Action</b>	Ensure that the report id is correct and exists in CentraSite. For more information please check the CentraSiteCommand log.
<b>INMCCE0204</b>	<b>Scheduled report with name "{0}" was not found.</b>
<b>Explanation</b>	You have provided a scheduled report name that does not exist in CentraSite.
<b>Action</b>	Ensure that the scheduled report name that you specified is correct and exists in CentraSite.
<b>INMCCE0205</b>	<b>More than one scheduled report with the name "{0}" found.</b>
<b>Explanation</b>	You have provided a scheduled report name which is not unique in CentraSite.
<b>Action</b>	If the scheduled report name is not unique in CentraSite the scheduled report id has to be specified.
<b>INMCCE0206</b>	<b>Unable to add a new scheduled report to CentraSite.</b>
<b>Explanation</b>	An error occurred during the "add scheduled report" operation.
<b>Action</b>	A new scheduled report could not be created. For more information check the CentraSiteCommand log.
<b>INMCCE0207</b>	<b>Unable to delete the scheduled report with the id "{0}"</b>
<b>Explanation</b>	An error occurred during the "delete scheduled report" operation.
<b>Action</b>	Ensure that the scheduled report id is correct and exists in CentraSite. For more information please check the CentraSiteCommand log.

<b>INMCCE0208</b>	<b>Unable to trigger the execution of the scheduled report with the id "{0}".</b>
<b>Explanation</b>	An error occurred during the "trigger scheduled report" operation.
<b>Action</b>	Ensure that the scheduled report id is correct and exists in CentraSite. For more information check the CentraSiteCommand log.
<b>INMCCE0209</b>	<b>Unable to update the scheduled report with the id "{0}".</b>
<b>Explanation</b>	An error occurred during the "update scheduled report" operation.
<b>Action</b>	Ensure that the scheduled report id is correct and exists in CentraSite. For more information check the CentraSiteCommand log.
<b>INMCCE0210</b>	<b>The property "{0}" is mandatory.</b>
<b>Explanation</b>	You have provided a configuration file where the property is missing.
<b>Action</b>	Ensure that the property is set in the configuration file.
<b>INMCCE0211</b>	<b>Unable to download the report template for the report id "{0}".</b>
<b>Explanation</b>	An error occurred during the "download report template" operation.
<b>Action</b>	Ensure that the report id is correct and exists in CentraSite. For more information check the CentraSiteCommand log.
<b>INMCCE0215</b>	<b>File {0} already exists.</b>
<b>Explanation</b>	The specified file already exists.
<b>Action</b>	Provide the correct file name.
<b>INMCCE0217</b>	<b>User level scope is not allowed.</b>
<b>Explanation</b>	You have provided the scope as user level.
<b>Action</b>	Change the scope either to global or org.
<b>INMCCE0218</b>	<b>Provide details for any one of the following parameters: scope, targetUser</b>
<b>Explanation</b>	An error occurred while copying the saved search because details for more than one of the parameters was provided.
<b>Action</b>	Provide details for any one of the parameters.

<b>INMCCE0219</b>	<b>Cannot find saved search with name {0}.</b>
<b>Explanation</b>	Cannot find saved search with name {0} while performing copy saved search operation.
<b>Action</b>	Make sure the saved search with name {0} is present.
<b>INMCCE0220</b>	<b>Specify a value for scope or targetUser.</b>
<b>Explanation</b>	You have not provided a value for both scope and targetUser.
<b>Action</b>	Enter a valid value for scope or targetUser.
<b>INMCCE0222</b>	<b>Insufficient privilege for user "{0}" to execute copy search command.</b>
<b>Explanation</b>	To execute copy search the user should be either an CentraSite Administrator or an Organization Administrator.
<b>Action</b>	Please make sure you have sufficient privileges.
<b>INMCCE0224</b>	<b>Insufficient privilege for user "{0}" to execute add search command in organization scope.</b>
<b>Explanation</b>	To execute add search in organization scope the user should be either an CentraSite Administrator or an Organization Administrator.
<b>Action</b>	Please make sure you have sufficient privileges.
<b>INMCCE0225</b>	<b>LDAP server {0} is not known.</b>
<b>Explanation</b>	The specified LDAP server {0} is not known, probably because the IP address or the host name of the LDAP server could not be determined.
<b>Action</b>	Enter a valid IP address, or the fully qualified host name of the LDAP server.
<b>INMCCE0226</b>	<b>LDAP server {0} is not reachable.</b>
<b>Explanation</b>	The specified LDAP server {0} is not reachable.
<b>Action</b>	Make sure that the LDAP server is reachable.
<b>INMCCE0227</b>	<b>Authentication failed {0}.</b>
<b>Explanation</b>	An error occurred while trying to access the LDAP server, possibly because of invalid credentials.
<b>Action</b>	Make sure the credentials for accessing the LDAP server are valid.

<b>INMCCE0231</b>	<b>The temporary configuration file name {0} already exists.</b>
<b>Explanation</b>	The name you are giving the temporary configuration file already exists for another file in CentraSite.
<b>Action</b>	Enter a configuration file name that does not already exist in CentraSite.
<b>INMCCE0234</b>	<b>Invalid object class.</b>
<b>Explanation</b>	The specified object class for users or groups does not exist in the LDAP server.
<b>Action</b>	Make sure the specified object class name exists in the LDAP server.
<b>INMCCE0235</b>	<b>Invalid root DN.</b>
<b>Explanation</b>	The specified root DN (distinguished name) for user or group searches does not exist in the LDAP server.
<b>Action</b>	Make sure the specified root DN exists in the LDAP server.
<b>INMCCE0238</b>	<b>Invalid attribute name.</b>
<b>Explanation</b>	The specified attribute name does not exist in the LDAP server.
<b>Action</b>	Make sure the specified attribute name exists in the LDAP server.
<b>INMCCE0259</b>	<b>Dynamic configuration property files of domain {0} are not unique.</b>
<b>Explanation</b>	The dynamic configuration property files of the specified domain {0} are not unique. The dynamic configuration files include the property files for the domain, and the property files for the alias declaration.
<b>Action</b>	Remove either the property files for the domain, or the property files for the alias declaration.
<b>INMCCE0260</b>	<b>The Truststore Type and Truststore URL fields or the Keystore Type and Keystore URL fields cannot be empty.</b>
<b>Explanation</b>	You have not entered values for the required Truststore Type and Truststore URL fields, or the Keystore Type and Keystore URL fields, when using LDAP over SSL (LDAPS).
<b>Action</b>	Enter valid values for either the Truststore Type and Truststore URL fields, or the Keystore Type and Keystore URL fields.

<b>INMCCE0261</b>	<b>Malformed URL.</b>
<b>Explanation</b>	Either no legal protocol could be found in the URL string or the URL string could not be parsed.
<b>Action</b>	Enter a valid URL.
<b>INMCCE0262</b>	<b>URL is not accessible.</b>
<b>Explanation</b>	An exception occurred when trying to connect to the specified URL.
<b>Action</b>	Check that the URL is correct.
<b>INMCCE0266</b>	<b>Target user {0} does not exist in the CentraSite registry.</b>
<b>Explanation</b>	Could not find the specified target user {0}, possibly because the user has been deleted from the CentraSite registry.
<b>Action</b>	Make sure the specified target user exists in the CentraSite registry. If the target user exists and the error persists, contact your administrator. If the target user does not exist, enter a valid CentraSite username.
<b>INMCCE0267</b>	<b>Incorrect date format {0}.</b>
<b>Explanation</b>	The specified date format is incorrect.
<b>Action</b>	Specify a valid date in the format yyyy-mm-dd.
<b>INMCCE0268</b>	<b>The access key or token does not match the authentication option.</b>
<b>Explanation</b>	The specified access key or token does not match the given authentication option.
<b>Action</b>	Specify the correct access key or token configured in the authentication option.
<b>INMCCE0269</b>	<b>Incorrect value for year {0}.</b>
<b>Explanation</b>	The specified value for year is incorrect.
<b>Action</b>	Specify a valid value for year in the format 'yyyy'.
<b>INMCCE0270</b>	<b>Incorrect value for month {0}.</b>
<b>Explanation</b>	The specified value for month is incorrect.
<b>Action</b>	Specify a valid value for month in the format 'mm'.

<b>INMCCE0271</b>	<b>Incorrect value for date {0}.</b>
<b>Explanation</b>	The specified value for date is incorrect.
<b>Action</b>	Specify a valid value for date in the format 'dd'.
<b>INMCCE0272</b>	<b>Failed to purge access token {0}.</b>
<b>Explanation</b>	Could not purge the specified access token using the CentraSite Command "purge accesstokens", possibly because of insufficient permissions or CentraSite database server is down.
<b>Action</b>	Make sure the CentraSite database server is up and running, and you have sufficient permissions to purge access tokens.
<b>INMCCE0273</b>	<b>The specified key is not available in DB.</b>
<b>Explanation</b>	The specified key is not available in DB .
<b>Action</b>	The specified key is not available in DB.
<b>INMCCE0274</b>	<b>Type with the given name does not exist or is not unique in the CentraSite registry.</b>
<b>Explanation</b>	Type with the given name does not exist or multiple type with the same name exist in the CentraSite registry.
<b>Action</b>	Provide a valid type name.
<b>INMCCE0276</b>	<b>{0} is the current logged in user.</b>
<b>Explanation</b>	An attempt was made to delete the logged in user.
<b>Action</b>	Ensure that the selected user for deletion is not the current logged in user.
<b>INMCCE0277</b>	<b>{0} is the primary contact of {1}.</b>
<b>Explanation</b>	The logged in user tried to delete the primary contact of an organization.
<b>Action</b>	Ensure that the selected user for deletion is not the primary contact of an organization.
<b>INMCCE0278</b>	<b>{0} is the CentraSite Administrator.</b>
<b>Explanation</b>	The logged in user tried to delete the user who is the CentraSite Administrator.
<b>Action</b>	Ensure that the selected user for deletion is not the CentraSite Administrator.

<b>INMCCE0279</b>	<b>At least one {0} should be present.</b>
<b>Explanation</b>	This is possible because there is only one user with the CentraSite Administrator or Organization Administrator role, and an attempt is made to delete this user.
<b>Action</b>	Make sure there is at least one CentraSite Administrator or Organization Administrator user at any time.
<b>INMCCE0280</b>	<b>User {0} has pending approvals and cannot be deleted.</b>
<b>Explanation</b>	The user selected for deletion has one or more pending approvals.
<b>Action</b>	Approve or reject the pending approvals for the selected user.
<b>INMCCE0281</b>	<b>Provide details for any one of these parameters: forceDelete, targetUser</b>
<b>Explanation</b>	An error occurred while deleting organization because details for more than one of these parameters were provided: forceDelete, targetUser.
<b>Action</b>	Provide details for any one of these parameters.
<b>INMCCE0282</b>	<b>Could not delete the organization that has deployed service(s).</b>
<b>Explanation</b>	Could not delete the organization, possibly because there is at least one service with key {0} deployed to a gateway.
<b>Action</b>	Undeploy the services before deleting the organization.
<b>INMCCE0284</b>	<b>Insufficient permissions for user "{0}" to execute delete search command in organization scope.</b>
<b>Explanation</b>	To execute delete search in organization scope the user should be either an CentraSite Administrator or an Organization Administrator.
<b>Action</b>	Make sure you have sufficient permissions to execute delete search command in organization scope.
<b>INMCCE0285</b>	<b>Insufficient permissions for user "{0}" to execute delete search command in global scope.</b>
<b>Explanation</b>	To execute delete search in global scope the user should be an CentraSite Administrator.
<b>Action</b>	Make sure you have sufficient permissions to execute delete search command in global scope.

<b>INMCCE0286</b>	<b>The list Action Categories command failed: {0}</b>
<b>Explanation</b>	Check the CentraSite logs for the reason for the failure.
<b>Action</b>	Run the command again after you have identified and fixed the issue(s). Ensure that all the parameters are correct and valid before you run the command. If the issue persists, contact Software AG support.
<b>INMCCE0287</b>	<b>Action category with the given name {0} already exists.</b>
<b>Explanation</b>	Action category with the given name {0} already exists.
<b>Action</b>	Specify an unique ID (uuid) to rename the action category.
<b>INMCCE0289</b>	<b>Invalid ID(uuid) {0}.</b>
<b>Explanation</b>	Action category with the given ID(uuid) {0} does not exist.
<b>Action</b>	Provide valid UDDI key for the action category.
<b>INMCCE0292</b>	<b>Action category named {0} is updated successfully, but could not update the category type.</b>
<b>Explanation</b>	N/A
<b>Action</b>	N/A
<b>INMCCE0293</b>	<b>The add Action Category command failed: {0}</b>
<b>Explanation</b>	Check the CentraSite logs for the reason for the failure.
<b>Action</b>	run the command again after you have identified and fixed the issue(s). Ensure that all the parameters are correct and valid before you run the command. If the issue persists, contact Software AG support.
<b>INMCCE0294</b>	<b>The delete Action Category command failed: {0}</b>
<b>Explanation</b>	Check the CentraSite logs for the reason for the failure.
<b>Action</b>	run the command again after you have identified and fixed the issue(s). Ensure that all the parameters are correct and valid before you run the command. If the issue persists, contact Software AG support.
<b>INMCCE0295</b>	<b>Action category deletion failed. The category includes at least one active policy action. \nPolicy Action details: {0}</b>
<b>Explanation</b>	Check the CentraSite logs for the reason for the failure.
<b>Action</b>	run the command again after you have identified and fixed the issue(s). Ensure that all the parameters are correct and valid before you run the command. If the issue persists, contact Software AG support.

<b>INMCCE0297</b>	<b>The list Action Categories command failed: {0}</b>
<b>Explanation</b>	Check the CentraSite logs for the reason for the failure.
<b>Action</b>	Run the command again after you have identified and fixed the issue(s). Ensure that all the parameters are correct and valid before you run the command. If the issue persists, contact Software AG support.
<b>INMCCE0303</b>	<b>The add action template command failed. {0}</b>
<b>Explanation</b>	Could not execute the add action template command.
<b>Action</b>	Check the CentraSite logs for the reason for the failure. Run the command again after you have identified and fixed the issue(s). Ensure that all the parameters are correct and valid before you run the command. If the issue persists, contact Software AG support.
<b>INMCCE0313</b>	<b>The delete Action Category command failed: {0}</b>
<b>Explanation</b>	Check the CentraSite logs for the reason for the failure.
<b>Action</b>	Run the command again after you have identified and fixed the issue(s). Ensure that all the parameters are correct and valid before you run the command. If the issue persists, contact Software AG support.
<b>INMCCE0314</b>	<b>The update action template command failed. {0}</b>
<b>Explanation</b>	Could not execute the update action template command.
<b>Action</b>	Check the CentraSite logs for the reason for the failure. Run the command again after you have identified and fixed the issue(s). Ensure that all the parameters are correct and valid before you run the command. If the issue persists, contact Software AG support.
<b>INMCCE0315</b>	<b>The download Action Template command failed: {0}</b>
<b>Explanation</b>	Check the CentraSite logs for the reason for the failure.
<b>Action</b>	Run the command again after you have identified and fixed the issue(s). Ensure that all the parameters are correct and valid before you run the command. If the issue persists, contact Software AG support.
<b>INMCCE0317</b>	<b>The get action template command failed. {0}</b>
<b>Explanation</b>	Could not execute the get action template command.
<b>Action</b>	Check the CentraSite logs for the reason for the failure. Run the command again after you have identified and fixed the issue(s). Ensure that all the parameters are correct and valid before you run the command. If the issue persists, contact Software AG support.

<b>INMCCE0319</b>	<b>File path does not exist.</b>
<b>Explanation</b>	Destination Directory does not exist.
<b>Action</b>	Create Directory and execute the command again
<b>INMCCE0321</b>	<b>The setup Custom Action command failed: {0}</b>
<b>Explanation</b>	Check the CentraSite logs for the reason for the failure.
<b>Action</b>	Run the command again after you have identified and fixed the issue(s). Ensure that all the parameters are correct and valid before you run the command. If the issue persists, contact Software AG support.
<b>INMCCE0322</b>	<b>The sync Ldap group command failed: {0}</b>
<b>Explanation</b>	Check the CentraSite logs for the reason for the failure.
<b>Action</b>	Run the command again after you have identified and fixed the issue(s). Ensure that all the parameters are correct and valid before you run the command. If the issue persists, contact Software AG support.
<b>INMCCI0027</b>	<b>Domain {0} not found</b>
<b>Explanation</b>	The domain to be processed does not exist.
<b>Action</b>	Correct the specified domain name.
<b>INMCCI0032</b>	<b>Domain {0} successfully added</b>
<b>Explanation</b>	The domain entry of the authentication configuration was created.
<b>Action</b>	No action required.
<b>INMCCI0033</b>	<b>Domain {0} successfully removed</b>
<b>Explanation</b>	The domain entry of the authentication configuration was removed.
<b>Action</b>	No action required.
<b>INMCCI0034</b>	<b>Validating LDAP domain {0}</b>
<b>Explanation</b>	The validate command has started.
<b>Action</b>	No action required.

<b>INMCCI0035</b>	<b>The LDAP server configuration has been successfully validated.</b>
<b>Explanation</b>	The specified LDAP server configuration is valid.
<b>Action</b>	No action required.
<b>INMCCI0036</b>	<b>LDAP user login validated successfully</b>
<b>Explanation</b>	The user could log on with supplied user name and password.
<b>Action</b>	No action required.
<b>INMCCI0037</b>	<b>LDAP user properties validated successfully</b>
<b>Explanation</b>	The user properties configuration is valid.
<b>Action</b>	No action required.
<b>INMCCI0038</b>	<b>LDAP group resolution validated successfully</b>
<b>Explanation</b>	The group resolution settings are valid.
<b>Action</b>	No action required.
<b>INMCCI0044</b>	<b>Creating CS Admin user {0} for domain {1}</b>
<b>Explanation</b>	The processing for creating a user with the CentraSite Administrator role has started.
<b>Action</b>	No action required.
<b>INMCCI0045</b>	<b>CS Admin user {0} created</b>
<b>Explanation</b>	A user with the CentraSite Administrator role has been successfully created.
<b>Action</b>	No action required.
<b>INMCCI0048</b>	<b>Do you want to see the LDAP search trace? {0}:</b>
<b>Explanation</b>	This prompt asks you whether or not you want to see the LDAP search results.
<b>Action</b>	Type Y (for yes) or N (for no) as appropriate, then press Enter. The default is N.
<b>INMCCI0049</b>	<b>User elements found: {0}. Do you want to see them?</b>
<b>Explanation</b>	The LDAP search found the given number of users.
<b>Action</b>	Type Y to see the results, otherwise N.

<b>INMCCI0050</b>	<b>Do you want to see all the users? (Y/N) [N]:</b>
<b>Explanation</b>	This prompt asks you whether or not to display all of the users.
<b>Action</b>	Type Y (for yes) or N (for no) as appropriate, then press Enter. The default is N.
<b>INMCCI0051</b>	<b>User with filter: {0}</b>
<b>Explanation</b>	User search filter
<b>Action</b>	search filter needs to be entered
<b>INMCCI0052</b>	<b>{0} The following group was found:</b>
<b>Explanation</b>	{0} --> ok
<b>Action</b>	No action
<b>INMCCI0057</b>	<b>Can't get user properties. {0}</b>
<b>Explanation</b>	{0} --> error message
<b>Action</b>	re-configure the user properties
<b>INMCCI0061</b>	<b>{0} User authenticated successfully</b>
<b>Explanation</b>	The user authentication was successful. The returned status is {0}.
<b>Action</b>	No action required.
<b>INMCCI0062</b>	<b>Trying to ping the server now...</b>
<b>Explanation</b>	An attempt is being made to connect to the server.
<b>Action</b>	No action required.
<b>INMCCI0063</b>	<b>Is the connection to the server protected with SSL? (Y/N) [N]:</b>
<b>Explanation</b>	This prompt asks you whether or not the LDAP connection to the server is protected with SSL.
<b>Action</b>	Type Y (for yes) or N (for no) as appropriate, then press Enter. The default is N.
<b>INMCCI0064</b>	<b>Do you want use LDAP Technical User? (Y/N) [N]:</b>
<b>Explanation</b>	The prompt asks whether or not you wish to use the LDAP Technical User.
<b>Action</b>	Type Y (for yes) or N (for no) as required. The default is N.

<b>INMCCI0065</b>	<b>Provide the LDAP Technical User credentials file:</b>
<b>Explanation</b>	The credentials file of the the LDAP Technical User needs to be given as input.
<b>Action</b>	Specify the credentials file.
<b>INMCCI0069</b>	<b>Direct binding using the constructed DN was successful.</b>
<b>Explanation</b>	A direct binding using the constructed DN was successful.
<b>Action</b>	No action required.
<b>INMCCI0070</b>	<b>Do you want use LDAP Technical User Key file?</b>
<b>Explanation</b>	User key file needs to be given or not
<b>Action</b>	File path will be given as input
<b>INMCCI0071</b>	<b>Trying to connect to LDAP at: {0}:{1}</b>
<b>Explanation</b>	An attempt is being made to connect to LDAP at host {0} and port {1}.
<b>Action</b>	No action required.
<b>INMCCI0072</b>	<b>To test the connection, please provide the credentials of a valid LDAP user.</b>
<b>Explanation</b>	To test the connection, the credentials of a valid LDAP user are required.
<b>Action</b>	Provide the credentials of a valid LDAP user.
<b>INMCCI0074</b>	<b>Do you want to save the configuration to CentraSite? (Y/N) [N]:</b>
<b>Explanation</b>	The prompt asks you whether or not to save the modified configuration to CentraSite.
<b>Action</b>	Reply Y (for yes) or N (for no). The default value is N.
<b>INMCCI0075</b>	<b>To store the connection, please provide the credentials of a user with role "CentraSite Administrator".</b>
<b>Explanation</b>	The connection can only be stored by a user with the role "CentraSite Administrator".
<b>Action</b>	Provide the credentials of a user with the role "CentraSite Administrator".
<b>INMCCI0076</b>	<b>Repeat configuration step {0}, Continue, or End? (R/C/E) [C]:</b>
<b>Explanation</b>	You can either repeat the given configuration step, continue to the next step, or end the processing.
<b>Action</b>	Type R, C or E to select the required option. The default is C.

<b>INMCCI0077</b>	<b>Repeat configuration step {0} or End? (R/E) [R]:</b>
<b>Explanation</b>	You can repeat the given configuration step or end the processing.
<b>Action</b>	Type R or E to select the required option. The default is R.
<b>INMCCI0078</b>	<b>Check {0} - Validating LDAP server configuration. Please wait...</b>
<b>Explanation</b>	This message is displayed when validating the LDAP server configuration settings.
<b>Action</b>	No action required.
<b>INMCCI0079</b>	<b>Check 2: LDAP User &gt;&gt; PLEASE WAIT...</b>
<b>Explanation</b>	This message is shown when the configuration of the LDAP user is being checked.
<b>Action</b>	No action required.
<b>INMCCI0080</b>	<b>Check 3: LDAP User Authentication &gt;&gt; PLEASE WAIT...</b>
<b>Explanation</b>	This message is shown when the configuration of the LDAP user authentication is being checked.
<b>Action</b>	No action required.
<b>INMCCI0081</b>	<b>Check 3: LDAP User Properties &gt;&gt; PLEASE WAIT...</b>
<b>Explanation</b>	This message is shown when the configuration of the LDAP user properties is being checked.
<b>Action</b>	No action required.
<b>INMCCI0082</b>	<b>Check 4: LDAP User Search &gt;&gt; PLEASE WAIT...</b>
<b>Explanation</b>	This message is shown when the configuration of the LDAP user search is being checked.
<b>Action</b>	No action required.
<b>INMCCI0083</b>	<b>Check 5: LDAP Group &gt;&gt; PLEASE WAIT...</b>
<b>Explanation</b>	This message is shown when the configuration of the LDAP group is being checked.
<b>Action</b>	No action required.

<b>INMCCI0084</b>	<b>Check 6: LDAP Group Mapping &gt;&gt; PLEASE WAIT...</b>
<b>Explanation</b>	This message is shown when the configuration of the LDAP group mapping is being checked.
<b>Action</b>	No action required.
<b>INMCCI0085</b>	<b>Check 7: LDAP Group Search &gt;&gt; PLEASE WAIT...</b>
<b>Explanation</b>	This message is shown when the configuration of the LDAP group search is being checked.
<b>Action</b>	No action required.
<b>INMCCI0086</b>	<b>Check 8: LDAP Group Resolution Host &gt;&gt; PLEASE WAIT...</b>
<b>Explanation</b>	This message is shown when the configuration of the LDAP group resolution host is being checked.
<b>Action</b>	No action required.
<b>INMCCI0087</b>	<b>Check 9: Displaying and saving configuration in CentraSite &gt;&gt; PLEASE WAIT...</b>
<b>Explanation</b>	This message is shown when the checked LDAP configuration is being saved in CentraSite.
<b>Action</b>	No action required.
<b>INMCCI0095</b>	<b>Do you want to see the complete trace? {0} :</b>
<b>Explanation</b>	The prompt asks you whether or not you want to see the complete trace.
<b>Action</b>	Type Y (yes) or N (no) as required. The default is N.
<b>INMCCI0097</b>	<b>Group elements found: {0} . Do you want to see them?</b>
<b>Explanation</b>	This is a confirmation message indicating that group elements have been found.
<b>Action</b>	Reply Yes if you want to see the group elements.
<b>INMCCI0098</b>	<b>Do you want to see all groups? {0} :</b>
<b>Explanation</b>	This prompt asks you if you want to see all groups.
<b>Action</b>	Reply Yes if you want to see the groups.

<b>INMCCI0099</b>	<b>Groups with filter: {0}</b>
<b>Explanation</b>	This is a confirmation message indicating that groups have been found with the filter.
<b>Action</b>	No action required.
<b>INMCCI0101</b>	<b>Groups for user found: {0} Do you want to see them?</b>
<b>Explanation</b>	Groups were found for the given user.
<b>Action</b>	Reply Yes if you want to see the groups that were found.
<b>INMCCI0107</b>	<b>Do you want to use the LDAP Technical User {0}:</b>
<b>Explanation</b>	This prompt asks you whether you want to use the LDAP Technical User (LDAP Principal) to access the LDAP user repository. If you reply Y, all authentication requests sent to the LDAP server will be made using this user. If you reply N, the client has to send its own credentials to LDAP to access a user record.
<b>Action</b>	Type Y (for yes) or N (for no) as appropriate, then press Enter. The default is N.
<b>INMCCI0108</b>	<b>Provide the LDAP Technical User credentials file.</b>
<b>Explanation</b>	This prompt asks you to provide the LDAP Technical User credentials file.
<b>Action</b>	Provide the LDAP Technical User credentials file.
<b>INMCCI0109</b>	<b>Provide the LDAP Technical User Key file</b>
<b>Explanation</b>	This prompt asks you to provide the LDAP Technical User Key file.
<b>Action</b>	Provide the LDAP Technical User key file.
<b>INMCCI0110</b>	<b>Trying to connect to LDAP at: {0}</b>
<b>Explanation</b>	An attempt is being made to connect to the LDAP Server with the given host name and port.
<b>Action</b>	No action required.
<b>INMCCI0133</b>	<b>The target identified by "{0}" has been removed from the configured federation targets.</b>
<b>Explanation</b>	The target identified by "{0}" has been removed from the configured federation targets during the execution of the command.
<b>Action</b>	No action required.

<b>INMCCI0134</b>	<b>A target is already associated with the given federation id "{0}".</b>
<b>Explanation</b>	The provided federation identifier already has a target associated with it.
<b>Action</b>	To obtain more details about the target associated with ID "{0}", execute the command <code>show_uddi_federation</code> .
<b>INMCCI0135</b>	<b>Do you want to update/overwrite the target at {0} ? {1} :</b>
<b>Explanation</b>	While running the <code>add_uddi_federation</code> command with the ID {0}, it may be already configured with another target. Then you should choose whether you want to update the target or not.
<b>Action</b>	Enter either y (Yes) to update/overwrite the target, or n (No) to do no modification. The default is y (Yes).
<b>INMCCI0136</b>	<b>Not overwriting the current configuration. Please provide another federation identifier</b>
<b>Explanation</b>	While executing the <code>add_uddi_federation</code> command, if an already existing identifier is provided, and you choose not to overwrite the target, then this message is displayed.
<b>Action</b>	You can provide a new identifier which does not already exist. To obtain the list of configured federation identifiers, execute the command <code>show_uddi_federation</code> .
<b>INMCCI0137</b>	<b>Overwriting/updating the target identified by "{0}"</b>
<b>Explanation</b>	While executing the command <code>add_uddi_federation</code> , if the provided federation identifier already exists, and you choose to overwrite/update the target, then you get this message.
<b>Action</b>	No action required.
<b>INMCCI0138</b>	<b>A target has been added/updated with the federation identifier {0}</b>
<b>Explanation</b>	This message is displayed if a target for federation has been successfully configured with the provided federation ID.
<b>Action</b>	No action required.
<b>INMCCI0143</b>	<b>Number of targets configured for federation : {0}</b>
<b>Explanation</b>	This message displays the number of targets configured for federation. {0} - Number of targets
<b>Action</b>	No action required.

<b>INMCCI0145</b>	<b>Deployment succeeded</b>
<b>Explanation</b>	The deployment succeeded.
<b>Action</b>	No action required.
<b>INMCCI0147</b>	<b>There are no Consumer Applications to deploy.</b>
<b>Explanation</b>	There are no consumer applications created in CentraSite to deploy.
<b>Action</b>	Create consumer applications in CentraSite to deploy to Mediator.
<b>INMCCI0148</b>	<b>The XML configuration of the Federation target "{0}":</b>
<b>Explanation</b>	The XML configuration of the federation target identified by {0} will be displayed in the console.
<b>Action</b>	No action required.
<b>INMCCI0149</b>	<b>The XML configuration of the Federation target "{0}" has been written to file "{1}"</b>
<b>Explanation</b>	This message informs that the XML configuration of the federation target identified by {0} has been written to the file located at {1}.
<b>Action</b>	No action required.
<b>INMCCI0150</b>	<b>The XML log configuration can be seen below:</b>
<b>Explanation</b>	The XML log configuration will be displayed to the console.
<b>Action</b>	No action required.
<b>INMCCI0151</b>	<b>The XML log configuration has been written to the file "{0}"</b>
<b>Explanation</b>	This message informs that the XML log configuration has been written to the file located at {0}.
<b>Action</b>	No action required.
<b>INMCCI0176</b>	<b>Domain {0} not found in jaas.config</b>
<b>Explanation</b>	The domain to be processed does not exist in jaas.config
<b>Action</b>	Correct the specified domain name.

<b>INMCCI0228</b>	<b>Do you really want to save the configuration {0}</b>
<b>Explanation</b>	When the end of the command is reached, the user is asked if the created LDAP configuration should be added to the current jaas.config file.
<b>Action</b>	Reply Y (for yes) or N (for no). There is no default value.
<b>INMCCI0229</b>	<b>The configuration has been saved successfully.</b>
<b>Explanation</b>	The LDAP configuration has been added successfully to the current jaas.config file.
<b>Action</b>	No action required.
<b>INMCCI0232</b>	<b>Check {0} - Validating LDAP user configuration. Please wait...</b>
<b>Explanation</b>	This message is displayed when validating the LDAP user configuration settings.
<b>Action</b>	No action required.
<b>INMCCI0233</b>	<b>The LDAP user configuration has been successfully validated.</b>
<b>Explanation</b>	The specified LDAP user configuration is valid.
<b>Action</b>	No action required.
<b>INMCCI0236</b>	<b>Check {0} - Validating LDAP user mapping configuration. Please wait...</b>
<b>Explanation</b>	This message is displayed when validating the LDAP user mapping configuration settings.
<b>Action</b>	No action required.
<b>INMCCI0237</b>	<b>The LDAP user mapping configuration has been successfully validated.</b>
<b>Explanation</b>	The specified LDAP user mapping configuration is valid.
<b>Action</b>	No action required.
<b>INMCCI0239</b>	<b>The following attributes have been retrieved for the LDAP user {0}:</b>
<b>Explanation</b>	Displays a list of mapped user attributes for the LDAP user {0}.
<b>Action</b>	No action required.
<b>INMCCI0240</b>	<b>No attributes could be retrieved for user {0}.</b>
<b>Explanation</b>	Could not retrieve attributes for the specified LDAP user {0}, possibly because all of the attributes are empty.
<b>Action</b>	No action required.

<b>INMCCI0241</b>	<b>No users were found matching search criteria {0}.</b>
<b>Explanation</b>	Could not find any users matching the specified search criteria {0}.
<b>Action</b>	No action required.
<b>INMCCI0242</b>	<b>The following users match the search criteria {0}:</b>
<b>Explanation</b>	Displays a list of LDAP users matching the search criteria {0}.
<b>Action</b>	No action required.
<b>INMCCI0243</b>	<b>The following users match the search criteria {0}. The following list only displays the first ten users matching the specified search criteria:</b>
<b>Explanation</b>	Displays the first ten users matching the search criteria {0}.
<b>Action</b>	No action required.
<b>INMCCI0244</b>	<b>No attributes could be retrieved for group {0}.</b>
<b>Explanation</b>	Could not retrieve attributes for the specified LDAP group {0}, possibly because all of the attributes are empty.
<b>Action</b>	No action required.
<b>INMCCI0245</b>	<b>No groups were found matching search criteria {0}.</b>
<b>Explanation</b>	Could not find any groups matching the specified search criteria {0}.
<b>Action</b>	No action required.
<b>INMCCI0246</b>	<b>The following groups match the search criteria {0}:</b>
<b>Explanation</b>	Displays a list of LDAP groups matching the search criteria {0}.
<b>Action</b>	No action required.
<b>INMCCI0247</b>	<b>The following groups match the search criteria {0}. The following list only displays the first ten groups matching the specified search criteria:</b>
<b>Explanation</b>	Displays the first ten groups matching the search criteria {0}.
<b>Action</b>	No action required.

<b>INMCCI0248</b>	<b>The LDAP group mapping configuration has been successfully validated.</b>
<b>Explanation</b>	The specified LDAP group mapping configuration is valid.
<b>Action</b>	No action required.
<b>INMCCI0249</b>	<b>Check {0} - Validating LDAP group mapping configuration. Please wait...</b>
<b>Explanation</b>	This message is displayed when validating the LDAP group mapping configuration settings.
<b>Action</b>	No action required.
<b>INMCCI0250</b>	<b>The following attributes have been retrieved for the LDAP group {0}:</b>
<b>Explanation</b>	Displays a list of mapped group attributes for the LDAP group {0}.
<b>Action</b>	No action required.
<b>INMCCI0251</b>	<b>Check {0} - Validating LDAP group configuration. Please wait...</b>
<b>Explanation</b>	This message is displayed when validating the LDAP group configuration settings.
<b>Action</b>	No action required.
<b>INMCCI0252</b>	<b>The specified LDAP group could not be found.</b>
<b>Explanation</b>	Could not find the specified LDAP group in the LDAP server.
<b>Action</b>	No action required.
<b>INMCCI0253</b>	<b>The LDAP group configuration has been successfully validated.</b>
<b>Explanation</b>	The specified LDAP group configuration is valid.
<b>Action</b>	No action required.
<b>INMCCI0254</b>	<b>Check {0} - Validating LDAP group resolution configuration. Please wait...</b>
<b>Explanation</b>	This message is displayed when validating the LDAP group resolution configuration settings.
<b>Action</b>	No action required.
<b>INMCCI0255</b>	<b>User {0} belongs to the following groups:</b>
<b>Explanation</b>	Displays a list of LDAP groups to which the user with name {0} belongs to.
<b>Action</b>	No action required.

<b>INMCCI0256</b>	<b>The LDAP group resolution configuration has been successfully validated.</b>
<b>Explanation</b>	The specified LDAP group resolution configuration is valid.
<b>Action</b>	No action required.
<b>INMCCI0257</b>	<b>User {0} belongs to the following groups:</b>
<b>Explanation</b>	Displays the first ten LDAP groups to which the user with name {0} belongs to.
<b>Action</b>	No action required.
<b>INMCCI0258</b>	<b>No groups were found to which the user {0} belongs to.</b>
<b>Explanation</b>	Could not find any groups to which the specified user with name {0} belongs to.
<b>Action</b>	No action required.
<b>INMCCI0263</b>	<b>Test user has successfully logged in.</b>
<b>Explanation</b>	Test user has successfully logged in.
<b>Action</b>	No action required.
<b>INMCCI0265</b>	<b>Search for user was successful.</b>
<b>INMCCI0288</b>	<b>Action category named {0} is created successfully.</b>
<b>Explanation</b>	N/A
<b>Action</b>	N/A
<b>INMCCI0290</b>	<b>Action category named {0} is updated successfully.</b>
<b>Explanation</b>	N/A
<b>Action</b>	N/A
<b>INMCCI0291</b>	<b>No changes available</b>
<b>Explanation</b>	N/A
<b>Action</b>	N/A

<b>INMCCI0296</b>	<b>Action category named {0} is deleted successfully.</b>
<b>Explanation</b>	NA
<b>Action</b>	NA
<b>INMCCI0298</b>	<b>Action template named {0} is created successfully.</b>
<b>Explanation</b>	N/A
<b>Action</b>	N/A
<b>INMCCI0310</b>	<b>Action template named {0} is updated successfully.</b>
<b>Explanation</b>	N/A
<b>Action</b>	N/A
<b>INMCCI0312</b>	<b>Action template named {0} is deleted successfully.</b>
<b>Explanation</b>	NA
<b>Action</b>	NA
<b>INMCCI0316</b>	<b>Action template named {0} is downloaded successfully to {1}.</b>
<b>Explanation</b>	NA
<b>Action</b>	NA
<b>INMCCI0318</b>	<b>Action template named {0} is downloaded successfully to {1}.</b>
<b>Explanation</b>	NA
<b>Action</b>	NA
<b>INMCCI0320</b>	<b>Custom policy action setup successful at {0}.</b>
<b>Explanation</b>	NA
<b>Action</b>	NA
<b>INMCCI0323</b>	<b>Group {0} synchronized successfully.</b>
<b>Explanation</b>	N/A
<b>Action</b>	N/A

<b>INMCCI0324</b>	<b>Members of the group {0} are already registered in CentraSite.</b>
<b>Explanation</b>	NA
<b>Action</b>	NA
<b>INMCCW0004</b>	<b>Default Organization is not present in CentraSite. Hence UDDI configurations cannot be saved.</b>
<b>Explanation</b>	UDDI Configurations for CentraSite will be stored in "Default Organization". CentraSiteCommand is not able to find the "Default Organization" in CentraSite and hence cannot store the UDDI configurations.
<b>Action</b>	Make sure the user provided to execute the command has permission to update the "Default Organization".
<b>INMCCW0005</b>	<b>No CentraSite Application Server Tier (CAST) found in CentraSite with specified cast URI {0}. Please specify fully qualified host name in -casturi option.</b>
<b>Explanation</b>	UDDI configurations for a CAST will be stored in an Application Server object. The object will have the host and port details. This object is required to store the local configurations for the CAST. CentraSiteCommand is not able to find the ApplicationServer object with the host specified in the cast URI option.
<b>Action</b>	Please make sure the value specified for the option cast URI is valid. Please specify the host as a fully qualified domain name in the cast URI option.
<b>INMCCW0104</b>	<b>unknown host</b>
<b>Explanation</b>	The host name provided is not the name of a known host.
<b>Action</b>	Provide a proper host name.
<b>INMCCW0128</b>	<b>An error occurred while trying to close a resource - {0}</b>
<b>Explanation</b>	Occasionally an error might be encountered while trying to close open connections, streams, etc., This is just a warning that an error was encountered and can be ignored.
<b>Action</b>	Make sure that the resource in question is not opened and/or modified by another program/application.
<b>INMCCW0146</b>	<b>Deployment failed</b>
<b>Explanation</b>	The deployment failed.
<b>Action</b>	Check related messages to find the reason why the deployment failed.

<b>INMCCW0168</b>	<b>Missing &lt;LogSetting&gt; attribute for &lt;LogUnit&gt; {0}.</b>
<b>Explanation</b>	The <LogSetting> attribute used to configure <LogUnit> {0} is missing.
<b>Action</b>	The <LogSetting> attribute is specified as an attribute name when configuring log unit in the config.xml file. For more information about log settings, see the CentraSite Administrator's Guide.
<b>INMCCW0169</b>	<b>The &lt;LogUnit&gt; {0} has a null value for the &lt;LogSetting&gt; attribute.</b>
<b>Explanation</b>	Required <LogSetting> attribute value is missing.
<b>Action</b>	The <LogSetting> value is specified as an attribute value when configuring log unit in the config.xml file. For more information about log settings, see the CentraSite Administrator's Guide.
<b>INMCCW0230</b>	<b>Configuration was not saved on user request!</b>
<b>Explanation</b>	The configuration was not saved, possibly because the user chose to reject it.
<b>Action</b>	No action required.
<b>INMCCW0264</b>	<b>Test User was not found.</b>
<b>Explanation</b>	Could not find the specified test user.
<b>Action</b>	No action required.
<b>INMCCW0275</b>	<b>You cannot deactivate the user(s). Reason</b>
<b>Explanation</b>	The user cannot be deactivated for the following reason(s):
<b>Action</b>	Check for the above reasons and then try again.
<b>INMCCW0299</b>	<b>Implementation-File parameter cannot be empty. Enter the name of a Java implementation file for policy action.</b>
<b>Explanation</b>	N/A
<b>Action</b>	N/A
<b>INMCCW0300</b>	<b>Action category named {0} does not exist.</b>
<b>Explanation</b>	N/A
<b>Action</b>	N/A

<b>INMCCW0301</b>	<b>Template-File parameter cannot be empty. Enter the name of an output file to download the action template.</b>
<b>Explanation</b>	N/A
<b>Action</b>	N/A
<b>INMCCW0302</b>	<b>Action template named {0} already exists.</b>
<b>Explanation</b>	N/A
<b>Action</b>	N/A
<b>INMCCW0304</b>	<b>Action must be associated at least to one object type.</b>
<b>Explanation</b>	N/A
<b>Action</b>	N/A
<b>INMCCW0305</b>	<b>Event type should have at least one value.</b>
<b>Explanation</b>	N/A
<b>Action</b>	N/A
<b>INMCCW0306</b>	<b>Parameter name cannot be empty.</b>
<b>Explanation</b>	N/A
<b>Action</b>	N/A
<b>INMCCW0307</b>	<b>Parameter type cannot be empty.</b>
<b>Explanation</b>	N/A
<b>Action</b>	N/A
<b>INMCCW0308</b>	<b>Policy action template with the given name {0} does not exist.</b>
<b>Explanation</b>	NA
<b>Action</b>	NA
<b>INMCCW0309</b>	<b>Implementation file of predefined action templates cannot be modified.</b>
<b>Explanation</b>	NA
<b>Action</b>	NA

<b>INMCCW0311</b>	<b>One or more required parameters in the action template configuration are missing.</b>
<b>Explanation</b>	NA
<b>Action</b>	NA
<b>INMCCW0325</b>	<b>Group with the given name {0} does not exist in {1}.</b>
<b>Explanation</b>	NA
<b>Action</b>	NA
<b>INMCCW0326</b>	<b>The specified object group {0} has wrong type.</b>
<b>Explanation</b>	NA
<b>Action</b>	NA
<b>INMCLE0005</b>	<b>CentraSite cannot delete the gateway. {0}</b>
<b>Explanation</b>	An error occurred while deleting a gateway in CentraSite.
<b>Action</b>	Contact your system administrator with the stack trace information in the CentraSite log.
<b>INMCLE0013</b>	<b>Caught an exception while retrieving the configurator instance.</b>
<b>Explanation</b>	This is an internal error. It is probably because of an invalid data in the configuration file.
<b>Action</b>	Verify that the data in configuration file are valid.
<b>INMCLE0014</b>	<b>System is unable to retrieve value for {0}.</b>
<b>Explanation</b>	This is an internal error. It is probably because of an invalid data in the configuration file.
<b>Action</b>	Verify that the data in configuration file are valid.
<b>INMCLE0015</b>	<b>Invalid path {0}.</b>
<b>Explanation</b>	You have entered an invalid path.
<b>Action</b>	Enter a valid path.

<b>INMCLE0017</b>	<b>Failed to check whether or not property of {0} is read-only.</b>
<b>Explanation</b>	Could not check whether or not the property of the given path {0} is read-only. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information.
<b>INMCLE0018</b>	<b>Caught an exception while retrieving the configuration file of type {0}.</b>
<b>Explanation</b>	This is an internal error. It is probably because of an invalid data in the configuration file.
<b>Action</b>	Verify that the data in configuration file are valid.
<b>INMCLE0019</b>	<b>Caught an exception while trying to save the configuration file of type {0}.</b>
<b>Explanation</b>	This is an internal error. It is probably because of an invalid data in the configuration file.
<b>Action</b>	Verify that the data in configuration file are valid.
<b>INMCLE0020</b>	<b>Failed to remove {0}.</b>
<b>Explanation</b>	This is an internal error. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information.
<b>INMCLE0021</b>	<b>Caught an exception while trying to get the configuration file URL for type {0}.</b>
<b>Explanation</b>	Could not get configuration file URL for type {0}, possibly because of an invalid data in the configuration file.
<b>Action</b>	Verify that the data in configuration file are valid.
<b>INMCLE0022</b>	<b>Path or property value is empty.</b>
<b>Explanation</b>	You have entered an empty path or property value.
<b>Action</b>	Enter a valid path or property value.
<b>INMCLE0023</b>	<b>Failed to set configuration(s) for the path(s), {0}</b>
<b>Explanation</b>	Unable to set configuration(s) for the path(s). This is probably because of the following reasons: 1) configuration file is modified 2) failed to save the configuration file.
<b>Action</b>	Check to make sure that the configuration in a higher level is not already protected. Else, check the stack trace for detailed information.

<b>INMCLE0024</b>	<b>Failed to setProtectAll.</b>
<b>Explanation</b>	Unable to set ProtectAll configuration. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information.
<b>INMCLE0025</b>	<b>Failed to getAllItems.</b>
<b>Explanation</b>	Unable to get one or more configuration items. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information.
<b>INMCLE0026</b>	<b>Unable to construct ActivityMenuItem for id {0}.</b>
<b>Explanation</b>	Could not construct ActivityMenuItem for the given id {0}, possibly because the XPath of the ActivityMenuItem is invalid.
<b>Action</b>	Verify that the XPath of the ActivityMenuItem is valid.
<b>INMCLE0027</b>	<b>Unable to construct activity for id {0}.</b>
<b>Explanation</b>	Could not construct activity for the given id {0}, possibly because the XPath of the activity is invalid.
<b>Action</b>	Verify that the XPath of the activity is valid.
<b>INMCLE0028</b>	<b>Unable to construct ActivityMenuItem for activity {0}.</b>
<b>Explanation</b>	Check for the above possible reasons. If the problem persists, contact the CentraSite administrator.
<b>Action</b>	Check to make sure that the XPath of the ActivityMenuItem and Activity is correct and the corresponding Activity could be created.
<b>INMCLE0029</b>	<b>Failed to instantiate class {0}.</b>
<b>Explanation</b>	Could not instantiate the implementation class {0}, possibly because the class does not follow a valid syntax.
<b>Action</b>	Verify that the implementation class follows a valid syntax. Refer to the documentation reference for Activity Implementation class.
<b>INMCLE0030</b>	<b>Unable to find activity entry for id {0}.</b>
<b>Explanation</b>	Could not find an activity entry for the given id {0}, possibly because the id is invalid.
<b>Action</b>	Verify that the given activity id is correct.

<b>INMCLE0031</b>	<b>Unable to construct an ActivityMenu using activities.</b>
<b>Explanation</b>	Could not construct an ActivityMenu using the given activities. It is probably because, the activities do not exist.
<b>Action</b>	Verify that the activities exist. If the problem persists, contact the CentraSite administrator.
<b>INMCLE0033</b>	<b>Failed to remove ActivityMenuItems.</b>
<b>Explanation</b>	Could not remove the ActivityMenuItems from given configuration file. It is possibly because of the following reasons: 1) XPath to remove the ActivityMenuItem is invalid. 2) ActivityMenuItem does not exist.
<b>Action</b>	Check for the above possible reasons. If the problem persists, contact the CentraSite administrator.
<b>INMCLE0034</b>	<b>Failed to save ActivityMenuItems.</b>
<b>Explanation</b>	Could not save the ActivityMenuItems from given configuration file. It is possibly because of the following reasons: 1) XPath to save the ActivityMenuItem is invalid. 2) ActivityMenuItem does not exist.
<b>Action</b>	Check for the above possible reasons. If the problem persists, contact the CentraSite administrator.
<b>INMCLE0035</b>	<b>User has not passed the CentraSite connection object. For a valid diagnostics configuration, CentraSite connection object is mandatory.</b>
<b>Explanation</b>	User has not passed the CentraSite connection object, which is mandatory for a valid diagnostics configuration.
<b>Action</b>	Enter a valid CentraSite connection object.
<b>INMCLE0036</b>	<b>Email address is empty,</b>
<b>Explanation</b>	You have not entered the email address for diagnostics configuration. An email address is mandatory to send the diagnostic information.
<b>Action</b>	Enter a valid email address.
<b>INMCLE0037</b>	<b>Email subject and template are empty.</b>
<b>Explanation</b>	You have not entered the email subject and template for diagnostics configuration. An email template is mandatory to send the diagnostic information. Refer to the CentraSite online documentation's section "Message Handling and Diagnostics".
<b>Action</b>	Enter the email subject and a valid template.

<b>INMCLE0038</b>	<b>Failed to get all activities.</b>
<b>Explanation</b>	Could not get all the activities, possibly because the activity classes are not set in the classpath.
<b>Action</b>	Verify that the activity classes are set in the classpath. If the problem persists, contact the CentraSite administrator.
<b>INMCLE0039</b>	<b>Failed to remove activity for given id {0}.</b>
<b>Explanation</b>	Could not remove the activity for given id {0}, possibly because the activity id is invalid.
<b>Action</b>	Verify that the given activity id is valid.
<b>INMCLE0040</b>	<b>Failed to show one or more activity menu items that are associated with activity menu.</b>
<b>Explanation</b>	Could not display one or more activity menu items, possibly because the menu items are not associated with the activity menu.
<b>Action</b>	Verify that all the activity menu items are associated with activity menu.
<b>INMCLE0041</b>	<b>Failed to populate diagnostic context.</b>
<b>Explanation</b>	Could not populate the diagnostic context object, possibly because the CentraSite Connection object is incorrect.
<b>Action</b>	Verify that the CentraSite Connection object is correct.
<b>INMCLE0042</b>	<b>Invalid CentraSite connection URL {0}.</b>
<b>Explanation</b>	You have entered an invalid CentraSite Connection URL.
<b>Action</b>	Enter a valid CentraSite Connection URL.
<b>INMCLE0043</b>	<b>User has not passed CLLEException object. For a valid diagnostics configuration, CLLEException object is mandatory.</b>
<b>Explanation</b>	User has not passed the CLLEException object which is mandatory for the diagnostics configuration.
<b>Action</b>	Enter a valid CLLEException object.

<b>INMCLE0044</b>	<b>Unable to fetch email template from repository {0}.</b>
<b>Explanation</b>	Could not fetch the email template from given repository {0}, possibly because of the following reasons: 1) email template does not exist 2) repository URL is invalid.
<b>Action</b>	Check for the above possible reasons. If the problem persists, contact the CentraSite administrator.
<b>INMCLE0045</b>	<b>Error loading implementation class for ActivityManager.</b>
<b>Explanation</b>	An unexpected error occurred while trying to load the implementation class for given ActivityManager. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information.
<b>INMCLE0046</b>	<b>Error loading diagnosticHandler implementation class.</b>
<b>Explanation</b>	An unexpected error occurred while trying to load the diagnosticHandler implementation class. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information.
<b>INMCLE0048</b>	<b>Failed to instantiate class {0}.</b>
<b>Explanation</b>	Could not instantiate the given class {0}, possibly because of the following reasons: 1) class file does not exist 2) classpath is incorrect.
<b>Action</b>	Check for the above possible reasons. If the problem persists, contact the CentraSite administrator.
<b>INMCLE0049</b>	<b>Failed to initialize {0}.</b>
<b>Explanation</b>	Could not initialize the given component {0}.
<b>Action</b>	If the problem persists, contact the CentraSite administrator.
<b>INMCLE0050</b>	<b>Failed to get CentraSite registry object property {0}.</b>
<b>Explanation</b>	Could not get the CentraSite registry object property. The cause is not immediately known.
<b>Action</b>	If the problem persists, contact the CentraSite administrator.
<b>INMCLE0051</b>	<b>Failed to set registry object property {0}.</b>
<b>Explanation</b>	Could not set the CentraSite registry object property. The cause is not immediately known.
<b>Action</b>	If the problem persists, contact the CentraSite administrator.

<b>INMCLE0052</b>	<b>Failed to save CentraSite object {0}.</b>
<b>Explanation</b>	An error occurred while trying to save CentraSite model object.  Possible reasons: {1}
<b>Action</b>	If the problem persists, contact the CentraSite administrator.
<b>INMCLE0053</b>	<b>Failed to delete CentraSite object {0}.</b>
<b>Explanation</b>	Could not delete the CentraSite object. The cause is not immediately known.
<b>Action</b>	If the problem persists, contact the CentraSite administrator.
<b>INMCLE0054</b>	<b>Failed to get CentraSite object for id {0}.</b>
<b>Explanation</b>	Could not get CentraSite object for the given id {0}, possibly because the object id is invalid.
<b>Action</b>	Verify that the object id is valid.
<b>INMCLE0055</b>	<b>Failed to create CentraSite object {0}.</b>
<b>Explanation</b>	You cannot create the CentraSite object {0}, possibly because of the following reasons: 1) insufficient privileges to create the object 2) object type is invalid.
<b>Action</b>	Check for the above possible reasons and execute again. If the problem persists, contact the CentraSite administrator.
<b>INMCLE0056</b>	<b>Failed to delete CentraSite object.</b>
<b>Explanation</b>	You cannot delete the CentraSite object {0}, possibly because you do not have the required permission to delete the object.
<b>Action</b>	Verify that you have the required permission to delete the CentraSite object. Contact your administrator and request permission if necessary and try again.
<b>INMCLE0057</b>	<b>Unable to get list of CentraSite objects: {0}.</b>
<b>Explanation</b>	You cannot retrieve the following list of CentraSite objects: {0}. It is possibly because you do not have the required permission to retrieve the objects.
<b>Action</b>	Verify that you have the required permission to retrieve the given objects. Contact your administrator and request permission if necessary and try again.

<b>INMCLE0058</b>	<b>Unable to save list of CentraSite objects: {0}</b>
<b>Explanation</b>	You cannot save the following list of CentraSite objects: {0}. It is possibly because you do not have the required permission to save the objects.{0}
<b>Action</b>	Verify that you have the required permission to save the given objects. Contact your administrator and request permission if necessary and try again.
<b>INMCLE0059</b>	<b>Unable to delete list of CentraSite objects:</b>
<b>Explanation</b>	You cannot delete the following list of CentraSite objects: {0}. It is possibly because you do not have the required permission to delete the objects.
<b>Action</b>	Verify that you have the required permission to delete the given objects. Contact your administrator and request permission if necessary and try again.
<b>INMCLE0060</b>	<b>Caught an unexpected exception while converting concept to CentraSiteObjectType.</b>
<b>Explanation</b>	This is an unexpected exception. The cause is not immediately known.
<b>Action</b>	If the problem persists, contact the CentraSite administrator.
<b>INMCLE0061</b>	<b>Failed to populate ObjectType for given name {0}.</b>
<b>Explanation</b>	Could not populate the ObjectType for display name {0}, possibly because the given display name is incorrect.
<b>Action</b>	Verify that the display name is correct.
<b>INMCLE0062</b>	<b>Error retrieving the list of gateways.</b>
<b>Explanation</b>	CentraSite could not retrieve the list of existing gateways because of an error during gateway name validations.
<b>Action</b>	Contact your CentraSite Administrator.
<b>INMCLE0063</b>	<b>Unsupported attribute {0} for object type {1}.</b>
<b>Explanation</b>	This is an internal error. Cannot find the attribute {0} of the specified object type {1}.
<b>Action</b>	Check to make sure that the attribute {0} is present in the object type {1}.
<b>INMCLE0064</b>	<b>Failed to fetch attributes for {0}.</b>
<b>Explanation</b>	Could not fetch attributes for {0}, possibly because the object type {1} is invalid.
<b>Action</b>	Verify that the object type {1} is valid.

<b>INMCLE0065</b>	<b>Unable to obtain value for attribute {0}.</b>
<b>Explanation</b>	Could not obtain the value for attribute {0}. The cause is not immediately known.
<b>Action</b>	Verify integrity of the object and try later.
<b>INMCLE0066</b>	<b>Unsupported method for attribute {0} of object type {1}.</b>
<b>Explanation</b>	This method is not applicable for attribute {0} of object type {1}.
<b>Action</b>	Do not use this method for attribute {0} of object type {1}.
<b>INMCLE0067</b>	<b>Error while initializing CentraSiteConnector {0}.</b>
<b>Explanation</b>	Could not initialize the CentraSiteConnector {0}. It is probably because of the following reasons: 1) invalid class as CentraSite Connection Factory 2) invalid system property (com.softwareag.centrasite.common.connection.impl) for initializing.
<b>Action</b>	Check for the above possible reasons and execute again. If the problem persists, contact the CentraSite administrator.
<b>INMCLE0068</b>	<b>Failed to create an ActivityMenuItem for id {0}.</b>
<b>Explanation</b>	Could not create the ActivityMenuItem for above id, possibly because of the invalid configurations.
<b>Action</b>	Verify that the activity id and class name are configured properly.
<b>INMCLE0069</b>	<b>Error when closing connection {0}.</b>
<b>Explanation</b>	Error occurred when trying to close the underlying connection.
<b>Action</b>	Initialize before opening a connection.
<b>INMCLE0070</b>	<b>Failed to log in {0}.</b>
<b>Explanation</b>	Could not log in {0}, possibly because the login credentials are invalid.
<b>Action</b>	Enter valid login credentials.
<b>INMCLE0071</b>	<b>Cannot instantiate CentraSiteConnector class {0}.</b>
<b>Explanation</b>	Could not instantiate the CentraSiteConnector implementation class, possibly because the implementation class is invalid.
<b>Action</b>	Check to make sure that the CentraSiteConnector class is valid.

<b>INMCLE0072</b>	<b>Error loading email template {0} {1}.</b>
<b>Explanation</b>	Error when loading the admin and/or user email templates, possibly because the email template path is invalid.
<b>Action</b>	Verify that the email template path is valid.
<b>INMCLE0073</b>	<b>Email address is empty.</b>
<b>Explanation</b>	You have not entered an email address.
<b>Action</b>	Enter a valid email address.
<b>INMCLE0074</b>	<b>Invalid attribute {0} {1}.</b>
<b>Explanation</b>	The attribute {1} is not a valid {0} attribute.
<b>Action</b>	Check to make sure that the {1} attribute is valid.
<b>INMCLE0075</b>	<b>Usage of {0} operation in object {1} is not supported.</b>
<b>Explanation</b>	This operation is not supported on the given object {1}.
<b>Action</b>	Refer to the usage document for further information on the supported APIs.
<b>INMCLE0076</b>	<b>Unable to obtain relationship details of attribute {0} to object type {1}.</b>
<b>Explanation</b>	Could not obtain the relationship details of attribute {0} associated to the above object type {1}.
<b>Action</b>	Make sure that the attribute {0} is a valid relationship attribute for the object type {1}.
<b>INMCLE0077</b>	<b>Failed to execute query {0}.</b>
<b>Explanation</b>	Could not execute the query {0}, possibly because the query syntax is incorrect.
<b>Action</b>	Correct the query syntax.
<b>INMCLE0078</b>	<b>Failed to execute query {0}.</b>
<b>Explanation</b>	Could not execute the query {0}, possibly because the query syntax is incorrect.
<b>Action</b>	Correct the query syntax.
<b>INMCLE0079</b>	<b>Failed to get objectTypeValue from given ObjectType.</b>
<b>Explanation</b>	Could not get the objectTypeValue from ObjectType, possibly because the given ObjectType is invalid.
<b>Action</b>	Check to make sure that the given ObjectType is valid.

<b>INMCLE0080</b>	<b>Failed to construct search query.</b>
<b>Explanation</b>	Could not construct the search query. The cause is not immediately known.
<b>Action</b>	If the problem persists, contact the CentraSite administrator.
<b>INMCLE0081</b>	<b>Caught an exception while getting iterator from CSOSearchResult.</b>
<b>Explanation</b>	This is an unexpected exception. The cause is not immediately known.
<b>Action</b>	If the problem persists, contact the CentraSite administrator.
<b>INMCLE0082</b>	<b>Failed to get search result count.</b>
<b>Explanation</b>	Could not get the number of results displayed on the Search Results page. The cause is not immediately known.
<b>Action</b>	If the problem persists, contact the CentraSite administrator.
<b>INMCLE0083</b>	<b>Unable to fetch next object for id {0}.</b>
<b>Explanation</b>	An unexpected exception occurred while trying to fetch the next object for above id.
<b>Action</b>	If the problem persists, contact the CentraSite administrator.
<b>INMCLE0084</b>	<b>The configuration file is invalid; attribute {0} is mandatory for multi-valued elements.</b>
<b>Explanation</b>	The required attribute for multi-valued elements is not specified in the XML configuration file.
<b>Action</b>	Before you save the configuration file, check to make sure that all the required attributes are specified.
<b>INMCLE0085</b>	<b>The configuration file is invalid; attribute {0} is mandatory for multi-valued elements.</b>
<b>Explanation</b>	The required attribute for multi-valued elements is not specified in the XML configuration file.
<b>Action</b>	Before you save the configuration file, check to make sure that all the required attributes are specified.
<b>INMCLE0086</b>	<b>Failed to fetch common attribute {0}.</b>
<b>Explanation</b>	Could not fetch the common attribute {0}, possibly because the attribute does not exist.
<b>Action</b>	Verify that the common attribute {0} is valid.

<b>INMCLE0087</b>	<b>Caught an exception while trying to set value for attribute {0}.</b>
<b>Explanation</b>	Could not set a value for attribute {0}. It is probably because of the following reasons: 1) attribute does not exist 2) attribute is read-only.
<b>Action</b>	Check for the above possible reasons and execute again. If the problem persists, contact the CentraSite administrator.
<b>INMCLE0088</b>	<b>Failed to retrieve attribute {0}.</b>
<b>Explanation</b>	Could not retrieve attribute {0}, possibly because the attribute does not exist.
<b>Action</b>	Verify that the attribute is valid.
<b>INMCLE0089</b>	<b>{0} based search has null or empty value.</b>
<b>Explanation</b>	Could not execute {0} based search, possibly because of a null or empty value in the search criteria.
<b>Action</b>	Check to make sure that the search criteria is valid.
<b>INMCLE0090</b>	<b>Data type {0} in search criteria is invalid.</b>
<b>Explanation</b>	The specified data type {0} in search criteria is not supported.
<b>Action</b>	Specify a valid data type. Refer to the CentraSite online documentation's section "Attribute Data Types" for a list of the supported data types.
<b>INMCLE0091</b>	<b>The number of values provided in the search criteria does not match with the mandatory number allowed for the operator {0}.</b>
<b>Explanation</b>	Every operator will support only the specified number of values. This error occurs when the number of values entered is less than or greater than the specified number.
<b>Action</b>	Refer to the CentraSite online documentation's section "Searching the CentraSite Catalog".
<b>INMCLE0092</b>	<b>Failed to serialize search {0}.</b>
<b>Explanation</b>	Could not serialize the above search, possibly because of invalid parameters in the search criteria.
<b>Action</b>	Check to make sure that the mandatory parameters are specified in search criteria.

<b>INMCLE0093</b>	<b>Failed to create folder in WebDav.</b>
<b>Explanation</b>	Could not create folder in the WebDav, possibly because you do not have the necessary permission to create a folder or intermediate folder in WebDav.
<b>Action</b>	Verify that you have the required permission to create a folder or intermediate folder in WebDav.
<b>INMCLE0094</b>	<b>Failed to retrieve file from given URI {0}.</b>
<b>Explanation</b>	Could not retrieve file from the above URI. This is probably because of the following reasons: 1) file does not exist 2) insufficient permissions to read the file.
<b>Action</b>	Check for the above possible reasons and execute again. If the problem persists, contact your service provider.
<b>INMCLE0095</b>	<b>Search cannot be executed with given URI {0}.</b>
<b>Explanation</b>	Could not execute a search with URI {0}, possibly because the given URI is invalid.
<b>Action</b>	Verify that the specified URI is valid. If the problem persists, contact the CentraSite administrator.
<b>INMCLE0096</b>	<b>Failed to parse persisted search output {0}.</b>
<b>Explanation</b>	Could not parse the search output, possibly because of an invalid XML syntax.
<b>Action</b>	Verify that the XML syntax is correct.
<b>INMCLE0097</b>	<b>Failed to convert input {0} to bytes.</b>
<b>Explanation</b>	Could not convert the given input {0} to bytes. The cause is not immediately known.
<b>Action</b>	If the problem persists, contact the CentraSite administrator.
<b>INMCLE0098</b>	<b>Failed to read output.</b>
<b>Explanation</b>	Failed to read the output, possibly because the input or output stream is closed.
<b>Action</b>	Make sure that the input or output stream is open.
<b>INMCLE0099</b>	<b>Failed to initialize parser.</b>
<b>Explanation</b>	Error: could not initialize parser. The cause is not immediately known.
<b>Action</b>	If the problem persists, contact the CentraSite administrator.

<b>INMCLE0100</b>	<b>Failed to get search data stored in folder {0}.</b>
<b>Explanation</b>	Could not get search data files that were stored in the above folder, possibly because you do not have insufficient permission to access the files.
<b>Action</b>	Verify that you have required permissions to access the data files.
<b>INMCLE0101</b>	<b>Cannot instantiate class{0}.</b>
<b>Explanation</b>	Could not instantiate the above class, possibly because the class is incorrect.
<b>Action</b>	Check to make sure that the implementation class is correct and follows a specified syntax. Refer to the documentation reference for Action Implementation class.
<b>INMCLE0102</b>	<b>Failed to load actions from system configurations.</b>
<b>Explanation</b>	Could not load specific actions from the system configuration file because of the following reasons: 1) class name for action is incorrect 2) action is not configured.
<b>Action</b>	Check to make sure that the class name for actions is correct and is configured in your system.xml file.
<b>INMCLE0103</b>	<b>Unable to retrieve actions for null parameter.</b>
<b>Explanation</b>	Internal error. It is possibly because you are trying to pass parameter with null value.
<b>Action</b>	Check if the parameter contains a null value.
<b>INMCLE0104</b>	<b>Failed to get configurator {0}</b>
<b>Explanation</b>	Could not get the above configurator, possibly because you do not have the required permissions.
<b>Action</b>	Verify that you have the required permission to get configurator. Contact your administrator and request permission if necessary and try again.
<b>INMCLE0105</b>	<b>Failed to get owner from connection.</b>
<b>Explanation</b>	Could not get the owner from connection, possibly because you do not have the required permissions.
<b>Action</b>	Verify that you have the required permission to get owner from connection. Contact your administrator and request permission if necessary and try again.

<b>INMCLE0106</b>	<b>Login failed.</b>
<b>Explanation</b>	Failed to login to CentraSite. It is possibly because of the following reasons: 1) incorrect CentraSite URL 2) invalid authentication credentials.
<b>Action</b>	Check for the above possible reasons and execute again. If the problem persists, contact the CentraSite administrator.
<b>INMCLE0107</b>	<b>{0} object is null.</b>
<b>Explanation</b>	Error: given object is null.
<b>Action</b>	Check to make sure that the given object is not null.
<b>INMCLE0108</b>	<b>Failed to get an instance of component {0}.</b>
<b>Explanation</b>	Could not get an instance of the above component. The cause is not immediately known.
<b>Action</b>	If the problem persists, contact the CentraSite administrator.
<b>INMCLE0111</b>	<b>Failed to remove file {0} from WebDaV.</b>
<b>Explanation</b>	Could not create a folder in WebDav. It is probably because of the following reasons: 1) file does not exist in WebDav 2) insufficient permission to remove a file from WebDav.
<b>Action</b>	Check for the above possible reasons and execute again. If the problem persists, contact the CentraSite administrator.
<b>INMCLE0112</b>	<b>Failed to create a file in {0}.</b>
<b>Explanation</b>	Could not create a file in {0}, possibly because the parent directory does not exist in the given location.
<b>Action</b>	Verify that parent directory exists in the given location.
<b>INMCLE0113</b>	<b>Could not instantiate AccessControlElement.</b>
<b>Explanation</b>	Unable to instantiate the AccessControlElement. The cause is not immediately known.
<b>Action</b>	If the problem persists, contact the CentraSite administrator.
<b>INMCLE0114</b>	<b>Failed to find resource exists for given URL {0}.</b>
<b>Explanation</b>	Could not find the file for given URL. It is probably because the file does not exist in the given URL.
<b>Action</b>	Check to make sure that the file exists in given URL.

<b>INMCLE0115</b>	<b>Failed to purge older versions of CentraSite object.</b>
<b>Explanation</b>	Could not purge older versions of the CentraSite object. The cause is not immediately known.
<b>Action</b>	If the problem persists, contact the CentraSite administrator.
<b>INMCLE0116</b>	<b>Unable to version CentraSite object.</b>
<b>Explanation</b>	Could not create a new version of the CentraSite object. The cause is not immediately known.
<b>Action</b>	If the problem persists, contact the CentraSite administrator.
<b>INMCLE0117</b>	<b>Unable to obtain base type for {0}.</b>
<b>Explanation</b>	Could not obtain the base type for {0}. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information.
<b>INMCLE0118</b>	<b>Failed to retrieve profiles for {0}.</b>
<b>Explanation</b>	Could not retrieve profiles for {0} because of the following reasons: 1) failure in retrieving profiles from type 2) insufficient permission for accessing the profiles.
<b>Action</b>	Check for the above possible reasons and execute again. If the problem persists, contact the CentraSite administrator.
<b>INMCLE0119</b>	<b>Failed to retrieve information for profile {0}.</b>
<b>Explanation</b>	Could not retrieve the information for profile. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information.
<b>INMCLE0120</b>	<b>Failed to choose assets for {0}.</b>
<b>Explanation</b>	Could not choose the assets for executing above action, possibly because the action is not in the 'initial' state.
<b>Action</b>	Verify that the action is in 'initial' state.
<b>INMCLE0122</b>	<b>Failed to retrieve immediate allowed states.</b>
<b>Explanation</b>	This is an unexpected exception. It is probably because the current lifecycle state does not have at least one immediate state.
<b>Action</b>	Check to make sure that the current lifecycle state has at least one immediate state.

<b>INMCLE0123</b>	<b>Failed to retrieve immediate preferred state</b>
<b>Explanation</b>	This is an unexpected exception. It is probably because the current lifecycle state does not have at least one immediate state.
<b>Action</b>	Check to make sure that the current lifecycle state has at least one immediate state.
<b>INMCLE0124</b>	<b>Failed to retrieve current state.</b>
<b>Explanation</b>	This is an unexpected exception. It is probably because the object is not associated with any of the lifecycle model.
<b>Action</b>	Check to make sure that the object type is associated with at least one lifecycle model.
<b>INMCLE0125</b>	<b>Failed to retrieve pending state.</b>
<b>Explanation</b>	This is an unexpected exception. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information. If the problem persists, contact your system administrator.
<b>INMCLE0126</b>	<b>Failed to identify if state of object is pending or not.</b>
<b>Explanation</b>	Could not identify if state of the object is in pending or not. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information. If the problem persists, contact your system administrator.
<b>INMCLE0127</b>	<b>Failed to get lifecycle model assigned types.</b>
<b>Explanation</b>	Could not get the lifecycle model assigned types. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information. If the problem persists, contact your system administrator.
<b>INMCLE0128</b>	<b>Failed to identify initial state of lifecycle model.</b>
<b>Explanation</b>	Could not identify initial state of the lifecycle model. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information. If the problem persists, contact your system administrator.

<b>INMCLE0129</b>	<b>Failed to get applicable states of lifecycle model.</b>
<b>Explanation</b>	Could not get applicable states of the lifecycle model. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information. If the problem persists, contact your system administrator.
<b>INMCLE0130</b>	<b>Failed to identify if given lifecycle model is global or not.</b>
<b>Explanation</b>	Could not identify if the given lifecycle model belongs to the global category. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information. If the problem persists, contact your system administrator.
<b>INMCLE0131</b>	<b>Mandatory parameters to identify applicable lifecycle models are empty.</b>
<b>Explanation</b>	An attempt is made to pass one or more of the mandatory parameters (CentraSiteObjectType or Organization) empty.
<b>Action</b>	Enter valid value for the mandatory parameters.
<b>INMCLE0132</b>	<b>Mandatory parameters to identify applicable lifecycle models are empty.</b>
<b>Explanation</b>	An attempt is made to pass one or more of the mandatory parameters (Keyword, CentraSiteObjectType or Organization) empty.
<b>Action</b>	Enter valid value for the mandatory parameters.
<b>INMCLE0133</b>	<b>setParameter value for a CSOSearch is empty.</b>
<b>Explanation</b>	An attempt is made to pass an empty list of values for the setParameter of CSOSearch.
<b>Action</b>	Enter a valid list of values for the CSOSearch.
<b>INMCLE0134</b>	<b>Invalid authentication credentials.</b>
<b>Explanation</b>	You have entered invalid authentication credentials.
<b>Action</b>	Enter valid authentication credentials.
<b>INMCLE0135</b>	<b>Folder {0} does not exist.</b>
<b>Explanation</b>	The specified folder does not exist in WebDav.
<b>Action</b>	Create the folder in WebDav and try again.

<b>INMCLE0136</b>	<b>Choose the CentraSite Object(s) to perform this action.</b>
<b>Explanation</b>	You have not chosen the CentraSite Object(s) for performing this action.
<b>Action</b>	Choose the CentraSite Object(s) to perform this action.
<b>INMCLE0137</b>	<b>Failed to perform {0} on multiple CentraSite objects.</b>
<b>Explanation</b>	You cannot perform {0} on multiple CentraSite objects at a time.
<b>Action</b>	Ensure you choose only one CentraSite object for performing {0}.
<b>INMCLE0138</b>	<b>Failed to check if {0} is applicable or not.</b>
<b>Explanation</b>	This is an unexpected exception. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information.
<b>INMCLE0139</b>	<b>Failed to perform {0} on specified CentraSite object(s).</b>
<b>Explanation</b>	Could not perform {0} on the specified CentraSite object(s) due to one or more of the following reasons: (1) insufficient permission (2) CentraSite object is in 'Pending' state (3) CentraSite object is locked for editing by another user.
<b>Action</b>	Check for the above possible reasons and execute again. Else, contact the CentraSite administrator.
<b>INMCLE0140</b>	<b>Failed to verify if current user has Edit permission on {0}.</b>
<b>Explanation</b>	This is an unexpected exception. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information.
<b>INMCLE0141</b>	<b>You are trying to modify an outdated asset.</b>
<b>Explanation</b>	You are trying to modify an asset which is outdated.
<b>Action</b>	Before you start to edit an asset, refresh the details page.
<b>INMCLE0142</b>	<b>Failed to verify if user has Move permission on CentraSite object.</b>
<b>Explanation</b>	This is an unexpected exception. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information.

<b>INMCLE0143</b>	<b>Failed to cancel {0}.</b>
<b>Explanation</b>	This is an unexpected exception. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information.
<b>INMCLE0144</b>	<b>Error loading saved search with name {0}.</b>
<b>Explanation</b>	This is an unexpected exception. The cause is not immediately known.
<b>Action</b>	If the problem persists, contact our technical support.
<b>INMCLE0145</b>	<b>{0} is required for CSOSearch.</b>
<b>Explanation</b>	Mandatory property {0} for executing a CSOSearch is missing.
<b>Action</b>	Check to make sure that the mandatory property is specified.
<b>INMCLE0146</b>	<b>Mismatch of attribute {0} specified in {1} with {2}.</b>
<b>Explanation</b>	The attribute in {1} does not match with the given {2}.
<b>Action</b>	Remove the faulty {1} and execute again.
<b>INMCLE0147</b>	<b>Caught an exception while getting profile id for {0}.</b>
<b>Explanation</b>	Could not retrieve the profile id for {0}. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information.
<b>INMCLE0148</b>	<b>{0} with name {1} used in {2} does not exist.</b>
<b>Explanation</b>	{0} with name {1} used in {2} does not exist.
<b>Action</b>	Contact the CentraSite administrator.
<b>INMCLE0149</b>	<b>Object {0} is null.</b>
<b>Explanation</b>	Could not get the object {0}.
<b>Action</b>	The object should be initialized before executing this operation.
<b>INMCLE0150</b>	<b>Caught an exception while trying to fetch pending approval requests.</b>
<b>Explanation</b>	Could not fetch pending approval requests for the logged in user. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information.

<b>INMCLE0151</b>	<b>Caught an exception while trying to verify if the logged in user has CentraSite Administrator role.</b>
<b>Explanation</b>	Could not verify if the logged in user has CentraSite Administrator role. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information.
<b>INMCLE0152</b>	<b>Wrong usage of {0} method.</b>
<b>Explanation</b>	Wrong usage of {0} method. This method is allowed only in the following scenarios: (1) if the action is in {1} state (2) before triggering the finishAllSteps() execution.
<b>Action</b>	Make sure that the method is used in one of the above scenarios. If the problem persists, contact the CentraSite administrator.
<b>INMCLE0153</b>	<b>{0} execution without comments is invalid.</b>
<b>Explanation</b>	{0} execution without comments is invalid. The approver has not specified his/her comments for {0}.
<b>Action</b>	Enter the comments for {0} using {1} API.
<b>INMCLE0154</b>	<b>Failed to execute {0}.</b>
<b>Explanation</b>	Could not execute {0}. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information.
<b>INMCLE0155</b>	<b>Failed to execute {0}</b>
<b>Explanation</b>	Could not execute {0} due to one or more of the following reasons: (1) {0} is not allowed at the time of execution (2) assets for {0} are in 'Completed' state (3) for a Revert action, the you should have the CentraSite administrator role (4) you do not have a pending approval flow to proceed with {0}.
<b>Action</b>	Check for the above possible reasons and execute again. Else, contact the CentraSite administrator.
<b>INMCLE0157</b>	<b>Invalid state transition from {0} by invoking {1} operation.</b>
<b>Explanation</b>	The state transition from {0} by invoking the {1} operation is not valid.
<b>Action</b>	See the Action Java API documentation for more details.

<b>INMCLE0158</b>	<b>One or more assets you have selected is not the most recent version of the asset.</b>
<b>Explanation</b>	One or more selected assets is not the most recent version of the asset. The New Version action does not apply to assets with intermediate version.
<b>Action</b>	Check to make sure that the selected assets for versioning are in their most recent version.
<b>INMCLE0159</b>	<b>Failed to create new version assets.</b>
<b>Explanation</b>	Error occurred when trying to create new version assets. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information.
<b>INMCLE0160</b>	<b>Caught an exception while invoking {0} operation.</b>
<b>Explanation</b>	An unexpected exception occurred while trying to execute the {0} operation.
<b>Action</b>	Check the stack trace for detailed information.
<b>INMCLE0161</b>	<b>Could not exclude a CentraSite object in {0} state from export. The object should be in "Export Preview" state.</b>
<b>Explanation</b>	CentraSite object in a state other than "Export Preview" cannot be excluded from export. The CentraSite object in "Export Preview" state will only have the option to preview and modify the export list.
<b>Action</b>	Verify that the CentraSite object is in "Export Preview" state. Read the usage instructions of Export action before use.
<b>INMCLE0162</b>	<b>Could not obtain export archive of a CentraSite object in {0} state. The object should be in "Completed" state.</b>
<b>Explanation</b>	You cannot obtain an export archive of the CentraSite object, if the object is in a state other than "Completed".
<b>Action</b>	Verify that the CentraSite object is in "Completed" state. Read the usage instructions of Export action before use.
<b>INMCLE0163</b>	<b>Failed to execute Consume action.</b>
<b>Explanation</b>	Could not execute a Consume action, possibly because of one or more of the following reasons: 1) username is invalid 2) password is invalid 3) connection URL is incorrect.
<b>Action</b>	Check for the above possible reasons and execute again. Else, contact the CentraSite administrator.

<b>INMCLE0164</b>	<b>An action in {0} state will not have Export List viewable. The action should be in "Export Preview" state.</b>
<b>Explanation</b>	You cannot view an export list if the action is in a state other than "Export Preview".
<b>Action</b>	Verify that the action is in "Export Preview" state. Read the usage instructions of Export action before use.
<b>INMCLE0165</b>	<b>Failed to execute Consume action.</b>
<b>Explanation</b>	{0} execution can fail due to one or more of the following reasons: (1) consumers are not selected (2) consumer requests are not registered.
<b>Action</b>	Check for the above possible reasons and execute again. Else, contact the CentraSite administrator.
<b>INMCLE0166</b>	<b>CentraSiteObject type list is empty.</b>
<b>Explanation</b>	You have not entered a CentraSiteObject type list.
<b>Action</b>	Enter a valid CentraSiteObject type list.
<b>INMCLE0167</b>	<b>Invalid object {1} for object type {2}.</b>
<b>Explanation</b>	The specified CentraSite object {1} does not belong to CentraSiteObject type {2}.
<b>Action</b>	Enter a valid CentraSite object of type {2}.
<b>INMCLE0168</b>	<b>Caught an exception while trying to convert CentraSite objects.</b>
<b>Explanation</b>	This is an unexpected exception. This is probably because an attempt is made to convert RegistryObjects to CentraSiteObjects, and vice versa.
<b>Action</b>	Check the stack trace for detailed information.
<b>INMCLE0169</b>	<b>Invalid value set for {0}. Expected value : {1} Current value : {2}.</b>
<b>Explanation</b>	The specified values for search condition does not match with the expected value.
<b>Action</b>	See the CentraSite online documentation's section "Searching the CentraSite Catalog" for details.
<b>INMCLE0170</b>	<b>Failed to verify if user {0} is watching asset {0}.</b>
<b>Explanation</b>	Could not verify if the user {0} is watching the given asset. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information.

<b>INMCLE0171</b>	<b>Invalid operator set for {0}. Current operator: {1}. Supported operators for {2} type are {3}.</b>
<b>Explanation</b>	The specified operator for search does not match with the attribute's applicable operators.
<b>Action</b>	See the CentraSite online documentation's section "Searching the CentraSite Catalog" for details.
<b>INMCLE0172</b>	<b>Failed to get existing lists.</b>
<b>Explanation</b>	This is an unexpected exception. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information.
<b>INMCLE0173</b>	<b>List {0} does not exist.</b>
<b>Explanation</b>	An attempt is made to pass the list {0} that is not available for the current user.
<b>Action</b>	Check to make sure that the list you pass for setExistingList(..) is available for the current user.
<b>INMCLE0174</b>	<b>Wrong usage of Add to List action API.</b>
<b>Explanation</b>	Incorrect usage of the Add to List action API. This problem occurs, when the '{0}' method is triggered with action in a state other than 'Show Available Lists'.
<b>Action</b>	Before you execute the {0} method, verify that the Add to List action is in 'Show Available Lists' state.
<b>INMCLE0175</b>	<b>List to add selected assets is not set.</b>
<b>Explanation</b>	List to add the selected set of assets is not set. Use the {0} method to set this list.
<b>Action</b>	Make sure that you use the {0} method to set the list to add selected assets.
<b>INMCLE0176</b>	<b>Failed to execute {0}.</b>
<b>Explanation</b>	{0} execution can fail for a number of reasons: (1) action is not allowed (2) action is not applicable at the time of execution (3) action is in 'Completed' state.
<b>Action</b>	Check for the above possible reasons and execute again. Else, contact the CentraSite administrator.

<b>INMCLE0177</b>	<b>Failed to create a new list {0}.</b>
<b>Explanation</b>	This is an unexpected exception. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information.
<b>INMCLE0178</b>	<b>Failed to add selected assets to the list.</b>
<b>Explanation</b>	This is an unexpected exception. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information.
<b>INMCLE0179</b>	<b>Choose a document to attach to asset.</b>
<b>Explanation</b>	The document to attach to the asset is not specified.
<b>Action</b>	Call the setDocument method before invoking the execute method in Attach Document action.
<b>INMCLE0180</b>	<b>Failed to create {0}</b>
<b>Explanation</b>	Failed to create resources or asset. The cause is not immediately known.
<b>Action</b>	If the problem persists, contact the CentraSite administrator.
<b>INMCLE0182</b>	<b>Data of type {0} is ignored.</b>
<b>Explanation</b>	Data of the above type defined for a CSOParameter is not supported.
<b>Action</b>	Use the supported data types for CSOParameter. See the CentraSite online documentation's section "Searching the CentraSite Catalog" for details.
<b>INMCLE0183</b>	<b>Current CSOSearch has unresolved parameters: {0}.</b>
<b>Explanation</b>	Current CSOSearch holds parameters that have a null value.
<b>Action</b>	Enter values for the unresolved parameters.
<b>INMCLE0184</b>	<b>Number of parameters defined in CSOSearch differs from parameters defined for the XQuery module.</b>
<b>Explanation</b>	Number of Parameters defined in the XQuery: {0} Number of Parameters defined in the CSOSearch: {1}.
<b>Action</b>	Validate your CSOSearch against the XQuery module.

<b>INMCLE0185</b>	<b>Missing parameters</b>
<b>Explanation</b>	The XQuery module used by the current CSOSearch requires {0} parameters.
<b>Action</b>	Validate the CSOSearch definition against the XQuery module that is being used.
<b>INMCLE0186</b>	<b>Cannot find Xquery module {1} in namespace {0}.</b>
<b>Explanation</b>	Could not find or load the XQuery module({0}:{1}) used by CSOSearch.
<b>Action</b>	Load the module / correct the CSOSearch definition.
<b>INMCLE0187</b>	<b>No CentraSite object is available for Export action.</b>
<b>Explanation</b>	You have not chosen the CentraSite objects for Export action.
<b>Action</b>	Choose the CentraSite objects for Export action.
<b>INMCLE0188</b>	<b>Configuration base directory is not set.</b>
<b>Explanation</b>	The configuration base directory specified by the path "com.softwareag.centrasite.api.configuration.basedir" is not set.
<b>Action</b>	Set the configuration base directory correctly. See the CentraSite online documentation for more details.
<b>INMCLE0189</b>	<b>Type {0} not valid for Attach Document action.</b>
<b>Explanation</b>	Could not perform the Attach Document action on selected type {0}.
<b>Action</b>	Enter a valid file. If the problem persists, contact the CentraSite administrator.
<b>INMCLE0190</b>	<b>Failed to attach given document.</b>
<b>Explanation</b>	Could not attach the given document, possibly because the document is invalid.
<b>Action</b>	Enter a valid document.
<b>INMCLE0191</b>	<b>CentraSite object {0} does not belong to any of the given types {1}.</b>
<b>Explanation</b>	The specified CentraSite object {0} does not belong to any of the given types {1}. Only objects that belong to the given types {1} are applicable for the Consume action.
<b>Action</b>	Choose a CentraSite object that belongs to one of the types {1}.

<b>INMCLE0192</b>	<b>Could not choose consumer object in current state {0}.</b>
<b>Explanation</b>	You cannot choose a consumer object in the current state {0}. The object should be in state {1}.
<b>Action</b>	Make sure that the consumer is in state {1}. Read the usage instructions of Consume action before use.
<b>INMCLE0193</b>	<b>List of consumers is empty.</b>
<b>Explanation</b>	An attempt is made to add an empty list of consumers for the Consume action.
<b>Action</b>	Choose a valid list of consumers. Read the usage instructions of Consume action before use.
<b>INMCLE0194</b>	<b>Error: Timeout - The Document Processor Thread timed out waiting for the required inputs.</b>
<b>Explanation</b>	You have not entered the required inputs within the time that the Document Processor was prepared to wait.
<b>Action</b>	Enter the required inputs as soon as prompted.
<b>INMCLE0195</b>	<b>Failed to process missing resources, {0}.</b>
<b>Explanation</b>	Could not process because the following resources are missing: {0}.
<b>Action</b>	Check to make sure that the required resources are specified.
<b>INMCLE0196</b>	<b>Failed to initialize AttachDocumentProcessorThread.</b>
<b>Explanation</b>	This is an internal error. The cause is not immediately known.
<b>Action</b>	Check to make sure that the mandatory inputs are specified.
<b>INMCLE0198</b>	<b>Failed to attach given document(s), Reason : {0}.</b>
<b>Explanation</b>	An exception occurred while trying to attach the document(s). This is probably because of the following reasons: 1) document is invalid 2) network failure.
<b>Action</b>	Check for the above possible reasons and execute again. If the problem persists, contact the CentraSite administrator.
<b>INMCLE0199</b>	<b>Failed to get applicable reports for object {0}.</b>
<b>Explanation</b>	An unexpected exception occurred while trying to get applicable reports for {0}. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information.

<b>INMCLE0200</b>	<b>Wrong usage of the View Report action API {0}.</b>
<b>Explanation</b>	Incorrect usage of the View Report action API. This problem occurs, when the '{0}' method is triggered with action in a state other than '{1}'.
<b>Action</b>	Before you execute the '{0}' method, verify that the action is in '{1}' state.
<b>INMCLE0201</b>	<b>Could not get selected report.</b>
<b>Explanation</b>	Failed to get the selected report, possibly because the report is not implicitly set for retrieval.
<b>Action</b>	Use the 'setSelectedReport(..)' to set a report for this action.
<b>INMCLE0202</b>	<b>Could not generate the selected report {0}.</b>
<b>Explanation</b>	An unexpected exception occurred while trying to generate the selected report {0}. The cause is not immediately known.
<b>Action</b>	Check the log file for detailed information.
<b>INMCLE0203</b>	<b>Failed to execute {0}.</b>
<b>Explanation</b>	You do not have permission to perform this action.
<b>Action</b>	Before executing {0} make sure that you have the 'Use the Reports UI' permission. Contact your CentraSite administrator and if necessary request access and then try again.
<b>INMCLE0204</b>	<b>Failed to close Centrasite ResourceAccessManager.</b>
<b>Explanation</b>	Caught an exception while trying to close the ResourceAccessManager. This is a system error.
<b>Action</b>	Check the stack trace for detailed information. If the problem persists, contact the CentraSite administrator.
<b>INMCLE0205</b>	<b>CentraSite cannot create a gateway because the gateway already exists. Gateway type: {0}, gateway name: {1}. Specify another name for the gateway.</b>
<b>Explanation</b>	You are trying to create a gateway in CentraSite with an existing name and gateway type.
<b>Action</b>	Provide another name for the gateway and try the "set gateway" command again.

<b>INMCLE0206</b>	<b>Failed to export {0}.</b>
<b>Explanation</b>	Could not export the asset (s). This is probably because of the following reasons: 1) mandatory input is missing 2) prerequisite not satisfied.
<b>Action</b>	Check for the above possible reasons. If the problem persists, contact the CentraSite administrator.
<b>INMCLE0207</b>	<b>Exception in Export Processor Thread</b>
<b>Explanation</b>	Export Processor Thread caught an unhandled exception. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information.
<b>INMCLE0208</b>	<b>Specify mandatory {0}s for performing operation {1}.</b>
<b>Explanation</b>	To perform this operation you should set the mandatory inputs.
<b>Action</b>	Check to make sure that the mandatory inputs are specified.
<b>INMCLE0209</b>	<b>List to remove the selected assets is not set.</b>
<b>Explanation</b>	The list to remove the selected assets is not set. Use the {0} method to set this list.
<b>Action</b>	Make sure that you use the {0} method to set the list to remove the selected assets.
<b>INMCLE0210</b>	<b>Caught an unexpected exception when setting notification options for user {0}.</b>
<b>Explanation</b>	This exception is unexpected. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information.
<b>INMCLE0211</b>	<b>Invalid file; specify a valid path to external file {0}.</b>
<b>Explanation</b>	You have entered an invalid file path.
<b>Action</b>	Enter a valid file path.
<b>INMCLE0212</b>	<b>Exception occurred when setting the specified email addresses for user {0}.</b>
<b>Explanation</b>	This exception is unexpected. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information.

<b>INMCLE0213</b>	<b>Exception occurred when adding the specified telephone number for user {0}.</b>
<b>Explanation</b>	This exception is unexpected. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information.
<b>INMCLE0214</b>	<b>Exception occurred when setting the specified name for user {0}.</b>
<b>Explanation</b>	An unexpected exception occurred when trying to set one of the specified name (First Name, Middle Name or Last Name) for the user {0}.
<b>Action</b>	Check the stack trace for detailed information.
<b>INMCLE0215</b>	<b>Parameter passed for {0} is null.</b>
<b>Explanation</b>	An attempt is made to specify the mandatory parameter {0} with a null value.
<b>Action</b>	Check to make sure that the {0} has a valid value.
<b>INMCLE0216</b>	<b>Exception occurred when trying to store the given profile picture in WEBDAV for user {0}.</b>
<b>Explanation</b>	This exception is unexpected. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information. If the problem persists, contact the CentraSite administrator.
<b>INMCLE0217</b>	<b>Exception occurred when trying to check for pending consumer registrations for user {0}.</b>
<b>Explanation</b>	This exception is unexpected. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information. If the problem persists, contact the CentraSite administrator.
<b>INMCLE0218</b>	<b>Exception occurred when trying to get Approval Request Reason for {0}.</b>
<b>Explanation</b>	This exception is unexpected. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information. If the problem persists, contact the CentraSite administrator.
<b>INMCLE0219</b>	<b>Exception occurred when trying to get Approval Workflow Name for {0}.</b>
<b>Explanation</b>	This exception is unexpected. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information. If the problem persists, contact the CentraSite administrator.

<b>INMCLE0220</b>	<b>{0} is triggered for consumer registration approval / rejection process; accessing {1} is invalid.</b>
<b>Explanation</b>	The {0} is triggered for consumer registration approval / rejection; accessing {1} is not valid.
<b>Action</b>	Accessing the {1} method for this kind of {0} is not valid. Ensure that you do not call this method here.
<b>INMCLE0221</b>	<b>Could not create/update a gateway because the gateway type is not specified. Specify the gateway type and try again.</b>
<b>Explanation</b>	The gateway type attribute is required to identify a gateway along with the gateway name. You have not specified the gateway type for the "set gateway" command in CentraSite.
<b>Action</b>	Specify the gateway type along with the name and other mandatory parameters, and try the "set gateway" command again.
<b>INMCLE0222</b>	<b>Exception occurred when trying to get Consumer Registration Requestor for {0}.</b>
<b>Explanation</b>	This exception is unexpected. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information. If the problem persists, contact the CentraSite administrator.
<b>INMCLE0223</b>	<b>Exception occurred when trying to get profile picture for user {0}.</b>
<b>Explanation</b>	This exception is unexpected. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information. If the problem persists, contact the CentraSite administrator.
<b>INMCLE0224</b>	<b>Exception occurred when getting the notification options for user {0}.</b>
<b>Explanation</b>	This exception is unexpected. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information. If the problem persists, contact the CentraSite administrator.
<b>INMCLE0225</b>	<b>Error loading predefined notification concepts</b>
<b>Explanation</b>	This exception is unexpected. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information. If the problem persists, contact the CentraSite administrator.

<b>INMCLE0226</b>	<b>Invalid phone type {0}.</b>
<b>Explanation</b>	You have entered an invalid phone type. The phone type should match one of the predefined types.
<b>Action</b>	Refer to CLL API documentation for details on predefined phone types.
<b>INMCLE0228</b>	<b>Invalid name {0}.</b>
<b>Explanation</b>	You have entered an invalid name.
<b>Action</b>	Enter a valid name without special characters.
<b>INMCLE0229</b>	<b>CentraSite could not create the gateway. You might not have permission to create a Mediator gateway.</b>
<b>Explanation</b>	User is not authorized to create a Mediator gateway in CentraSite.
<b>Action</b>	Contact your CentraSite administrator.
<b>INMCLE0230</b>	<b>Failed to create {0} for given URI {1}.</b>
<b>Explanation</b>	Failed to create a {0} for the given URI {1}, possibly because the Save operation is applicable only for WebDav resources.
<b>Action</b>	Save is applicable only for WebDav resources.
<b>INMCLE0231</b>	<b>Failed to get content type for given URI {0}.</b>
<b>Explanation</b>	Failed to get content type for given URI {0}, possibly because the content type could not find the external URI.
<b>Action</b>	Failed to get content type for given URI {0}, possibly because the content type could not find the external URI.
<b>INMCLE0232</b>	<b>Unable to fetch folders from external URL {0}.</b>
<b>Explanation</b>	Could not get folders from an external URL, because this operation is only supported for a WebDav URL.
<b>Action</b>	Enter a valid WebDav URL.
<b>INMCLE0233</b>	<b>Unable to fetch files from external URL {0}.</b>
<b>Explanation</b>	Could not fetch files from an external URL, because this operation is only supported for a WebDav URL.
<b>Action</b>	Enter a valid a WebDav URL.

<b>INMCLE0234</b>	<b>Failed to read XQuery from file {0}.</b>
<b>Explanation</b>	Could not read the XQuery from file, possibly because the file does not exist.
<b>Action</b>	Enter a valid file path.
<b>INMCLE0235</b>	<b>Parameter passed to the method {0} is null.</b>
<b>Explanation</b>	The parameter passed to the method {0} is null.
<b>Action</b>	Pass a valid parameter to the method {0}.
<b>INMCLE0236</b>	<b>Invalid values for keyword condition</b>
<b>Explanation</b>	Keyword condition takes only one string value as input. The value should be put in the collection and then set to keyword condition.
<b>Action</b>	Check to make sure that valid values are set as input to the keyword condition.
<b>INMCLE0237</b>	<b>Failed to get TransformedContent {0}.</b>
<b>Explanation</b>	Failed to get the TransformedContent, possibly because of a connection failure.
<b>Action</b>	Check the network connection. If the problem persists, contact CentraSite administrator.
<b>INMCLE0240</b>	<b>{0} cannot be reset.</b>
<b>Explanation</b>	An attempt is made to reset the {0} that already has a value specified and that is read-only.
<b>Action</b>	{0} is read-only.
<b>INMCLE0241</b>	<b>Exception occurred while trying to get the webdav location of computed profile template.</b>
<b>Explanation</b>	An unexpected exception occurred while trying to get the webdav location of computed profile template, possibly because the template does not exist.
<b>Action</b>	Check to make sure that the uploaded archive contains the computed profile template.
<b>INMCLE0242</b>	<b>Exception occurred while loading the implementation class of computed profile.</b>
<b>Explanation</b>	An unexpected exception occurred while loading the implementation class of computed profile, possibly because the class does not exist.
<b>Action</b>	Check to make sure that the uploaded archive contains the implementation class.

<b>INMCLE0243</b>	<b>Database access is denied.</b>
<b>Explanation</b>	Access to the database is denied.
<b>Action</b>	Login again.
<b>INMCLE0244</b>	<b>Exception while trying to retrieve the computed profile data.</b>
<b>Explanation</b>	This is an unexpected exception. The cause is not immediately known.
<b>Action</b>	Make sure that the getProfileDataAsJson() implementation is correct.
<b>INMCLE0245</b>	<b>Exception while trying to compute the profile data.</b>
<b>Explanation</b>	This is an unexpected exception. The cause is not immediately known.
<b>Action</b>	Make sure that the computeProfileData implementation is correct.
<b>INMCLE0246</b>	<b>Required input is missing.</b>
<b>Explanation</b>	The required input is missing.
<b>Action</b>	Enter a valid input.
<b>INMCLE0247</b>	<b>Error loading profile data.</b>
<b>Explanation</b>	An unexpected error occurred while trying to load the profile data, possibly because of the following reasons: {0}.
<b>Action</b>	Check for the above possible reasons. If the problem persists, contact the CentraSite administrator.
<b>INMCLE0248</b>	<b>Search cannot be saved.</b>
<b>Explanation</b>	The current search contains validation errors.
<b>Action</b>	Correct the validation errors and try again.
<b>INMCLE0249</b>	<b>Error establishing a database connection.</b>
<b>Explanation</b>	Unable to connect the database, possibly because the database server is down.
<b>Action</b>	Start the database server.
<b>INMCLE0250</b>	<b>Failed to convert the given duration {0} to date.</b>
<b>Explanation</b>	Exception occurred while trying to convert the given duration to date; possibly because the duration string is invalid.
<b>Action</b>	Enter a valid duration.

<b>INMCLE0251</b>	<b>Failed to covert the given string {0} to date.</b>
<b>Explanation</b>	Exception occurred while trying to convert the given string to date; possibly because the string is invalid.
<b>Action</b>	Check to make sure that the string is valid and it supports the date format like "E MMM dd HH:mm:ss Z yyyy".
<b>INMCLE0252</b>	<b>Failed to create a new {0}.</b>
<b>Explanation</b>	The {0} could not be created; possibly because the inputs were invalid.
<b>Action</b>	Make sure the inputs are valid.
<b>INMCLE0253</b>	<b>Failed to save an asset with the given permissions.</b>
<b>Explanation</b>	Failed to save an asset with the given permissions; possibly because the asset is unlocked.
<b>Action</b>	Make sure the asset is locked and available for editing.
<b>INMCLE0254</b>	<b>Exception fetching the asset's instace-level and profile-level permissions.</b>
<b>Explanation</b>	This exception is unexpected. The cause is not immediately known.
<b>Action</b>	Contact your system administrator if the problem persists.
<b>INMCLE0255</b>	<b>Display Interval {0} is invalid.</b>
<b>Explanation</b>	Specify the time interval how frequently you want to collect metrics for the service. The expected format is 3m 2d 6h; where m indicates the month, d indicates the day and h indicates the hour.
<b>Action</b>	Check to make sure that the time interval is specified in exactly the above format.
<b>INMCLE0256</b>	<b>Exception {0} occurred while trying to fetch the list of targets.</b>
<b>Explanation</b>	This exception is unexpected. The cause is not immediately known.
<b>Action</b>	Check the exception stack trace information.
<b>INMCLE0257</b>	<b>Target {0} is not active.</b>
<b>Explanation</b>	The target {0} is not active. The cause is not immediately known.
<b>Action</b>	Check the stack trace information for details.

<b>INMCLE0258</b>	<b>Failed to deploy the asset {0} on target {1}.</b>
<b>Explanation</b>	Could not deploy the asset {0} on given target {1}. Possible reason: {2}
<b>Action</b>	Check the stack trace information for details.
<b>INMCLE0259</b>	<b>Unable to fetch policy with UUID '{0}'.</b>
<b>Explanation</b>	Could not fetch policies with the given UUID '{0}'; possibly because of the following reasons: 1. A policy with a UUID '{0}' does not exist. 2. Logged in user does not have the required permission on policy.
<b>Action</b>	Ensure that at least one policy exists with the given UUID and the logged in user has the required permissions on the policy.
<b>INMCLE0260</b>	<b>Unable to fetch policies with name pattern '{0}'.</b>
<b>Explanation</b>	Could not fetch policies with the given name pattern '{0}'; possibly because of the following reasons: 1. A policy with a name pattern '{0}' does not exist. 2. Logged in user does not have the required permission on policy.
<b>Action</b>	Ensure that at least one policy exists with the given name pattern and the logged in user has the required permissions on the policy.
<b>INMCLE0261</b>	<b>The policy action template is invalid.</b>
<b>Explanation</b>	Invalid action template; possibly because one or more vital parameters are null or not available.
<b>Action</b>	Enter valid parameters for the action template.
<b>INMCLE0262</b>	<b>Unable to fetch policy actions with UUID '{0}'.</b>
<b>Explanation</b>	Could not fetch policy actions with the given UUID '{0}'; possibly because of the following reasons: 1. A policy action with a UUID '{0}' does not exist. 2. Logged in user does not have the required permission on action.
<b>Action</b>	Ensure that at least one policy action exists with the given UUID and the logged in user has the required permissions on the action.
<b>INMCLE0263</b>	<b>Unable to fetch policy actions with name pattern '{0}'.</b>
<b>Explanation</b>	Could not fetch policy actions with the given name pattern '{0}'; possibly because of the following reasons: 1. A policy action with a name pattern '{0}' does not exist. 2. Logged in user does not have the required permission on policy action.
<b>Action</b>	Ensure that at least one policy action exists with the given name pattern and the logged in user has the required permissions on the policy action.

<b>INMCLE0264</b>	<b>Unable to fetch {0}.</b>
<b>Explanation</b>	Could not fetch the {0}. The cause is not immediately known.
<b>Action</b>	Check the exception stack trace information.
<b>INMCLE0266</b>	<b>Failed to identify the consumers for the asset {0}.</b>
<b>Explanation</b>	Could not identify the consumers for the given asset {0}
<b>Action</b>	This is an internal error. If the problem persists, contact the system administrator.
<b>INMCLE0267</b>	<b>Failed to identify the targets to which the asset {0} is deployed.</b>
<b>Explanation</b>	Exception occurred when populating the targets to which the asset {0} is deployed.
<b>Action</b>	This is an internal error. If the problem persists, consult the system administrator.
<b>INMCLE0268</b>	<b>Failed to identify the events for the given search filter.</b>
<b>Explanation</b>	Exception occurred when populating events for the given search filter.
<b>Action</b>	This is an internal error. If the problem persists, consult the system administrator.
<b>INMCLE0269</b>	<b>Failed to revoke profile permissions.</b>
<b>Explanation</b>	Caught an exception when trying to revoke the profile permissions.
<b>Action</b>	This is an internal error. If the problem persists, consult the system administrator.
<b>INMCLE0270</b>	<b>Failed to set profile permissions.</b>
<b>Explanation</b>	Caught an exception when trying to set the profile permissions.
<b>Action</b>	This is an internal error. If the problem persists, consult the system administrator.
<b>INMCLE0271</b>	
<b>INMCLE0272</b>	<b>Error obtaining the classifications for object {0}.</b>
<b>Explanation</b>	Caught an unexpected exception occurred while trying to obtain the classifications of object {0} and which prevented the application from proceeding further.
<b>Action</b>	Check the stack trace information for details.

<b>INMCLE0273</b>	<b>Missing attribute in virtualization.</b>
<b>Explanation</b>	Mandatory attribute (Virtual Alias or Endpoint) is missing. Virtual Alias and Endpoint attributes are mandatory for virtualizing an API.
<b>Action</b>	Set the Virtual Alias and Endpoint attributes.
<b>INMCLE0274</b>	<b>Invalid Display Interval {0}.</b>
<b>Explanation</b>	The display interval specified is invalid.
<b>Action</b>	Specify a valid interval (ex. 1m 1d 1h) and try again.
<b>INMCLE0275</b>	<b>Failed to configure the API Key.</b>
<b>Explanation</b>	Could not configure the API Key for the given asset; possibly because of missing parameters.
<b>Action</b>	Check to make sure all the required parameters are set.
<b>INMCLE0276</b>	<b>Failed to load approval groups from the CentraSite registry.</b>
<b>Explanation</b>	One or more approval groups could not be loaded from the CentraSite registry.
<b>Action</b>	Make sure that an approval group exists and try again.
<b>INMCLE0277</b>	<b>Error checking permissions or validity over objects.</b>
<b>Explanation</b>	Could not check permissions or validity over the specified objects.
<b>Action</b>	Verify the user and asset type are valid in the CentraSite registry.
<b>INMCLE0278</b>	<b>Failed to check if the current user has Manage Organizations permission.</b>
<b>Explanation</b>	This is an unexpected exception. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information.
<b>INMCLE0279</b>	<b>Unable to delete/remove the selected {0} {1}</b>
<b>Explanation</b>	You cannot delete the {0} {1}, because you do not have the required permission to delete/remove the {0}.
<b>Action</b>	Verify that you have the required permission to delete/remove the {0}. Contact your administrator, request permission if necessary and try again.

<b>INMCLE0280</b>	<b>Unable to delete the selected user {0}.</b>
<b>Explanation</b>	{1}. A user cannot be deleted if the user owns/modifies object(s), or if the user has any pending actions or if the user is the sole administrator for an organization. Also, if the user modified some object, and the corresponding audit trail entry is still present, deletion is rejected.{0} - The user that was attempted to be deleted.
<b>Action</b>	Delete all of the objects owned by the user, complete all pending actions, ensure another user is appointed as administrator for the corresponding organization and after all modification audit trail entries are purged (if any), user deletion will be allowed.
<b>INMCLE0281</b>	<b>Unable to delete the selected group {0}</b>
<b>Explanation</b>	{1}. You cannot delete the selected group either because you do not have the required permission or the group is associated with another object which creates a dependency to the group.
<b>Action</b>	Verify that you have the required permission to delete the user. Ensure that the group does not have any associations to other objects and try deleting the associations (if any) before attempting to delete the group again.
<b>INMCLE0282</b>	<b>Unable to delete the selected role {0}</b>
<b>Explanation</b>	{1}. You cannot delete the selected role either because you do not have the required permission, or the role is a pre-defined system role which cannot be deleted, or the role is associated with another object which is dependent on it.
<b>Action</b>	Verify that you have the required permission to delete the role. Ensure that you are not attempting to delete a pre-defined role.
<b>INMCLE0283</b>	<b>Unable to delete the selected Child Organization</b>
<b>Explanation</b>	{0}. You cannot delete the selected Child Organization either because you do not have the required permission, or the organization has policies which are active, or other objects are associated with the organization.
<b>Action</b>	Verify that you have the required permission to delete the Child Organization. Ensure that organization dependencies are resolved before attempting to delete again.
<b>INMCLE0284</b>	<b>Unable to delete/modify the selected group {0}</b>
<b>Explanation</b>	You cannot modify the users of/delete pre-defined groups of CentraSite such as "Users" and "Members". Since the group {0} is a pre-defined object, the deletion/modification of the group has been rejected.
<b>Action</b>	Ensure that the group that you are trying to delete/modify is not a pre-defined object.

<b>INMCLE0285</b>	<b>Unable to delete the selected role {0}</b>
<b>Explanation</b>	You cannot delete the OrganizationAdministrator role of an organization. This is because this role indicates the Administrator(s) of an organization.
<b>Action</b>	Ensure that the role you are trying to delete is not that of the OrganizationAdministrator.
<b>INMCLE0286</b>	<b>Caught an Exception while creating the VSProcessingStepsAdapter instance</b>
<b>Explanation</b>	This is an internal error. It is probably because of an invalid connection.
<b>Action</b>	Verify that the user session is valid.
<b>INMCLE0287</b>	<b>Invalid Native service.</b>
<b>Explanation</b>	This is an internal error. It is probably because the native service Registry Object is null.
<b>Action</b>	Verify that the native service is valid.
<b>INMCLE0288</b>	<b>Unable to virtualize the native service</b>
<b>Explanation</b>	This is an internal error. It is probably because of an invalid MessageFlow.
<b>Action</b>	Verify that the MessageFlow is valid.
<b>INMCLE0289</b>	<b>Cannot Construct MessageFlow from VirtualService.</b>
<b>Explanation</b>	This is an internal error. It is probably because of an invalid VirtualService.
<b>Action</b>	Verify that the VirtualService is valid.
<b>INMCLE0290</b>	<b>Invalid Virtual service.</b>
<b>Explanation</b>	This is an internal error. It is probably because the virtual service Registry Object is null.
<b>Action</b>	Verify that the virtual service is valid.
<b>INMCLE0291</b>	<b>Falied to edit the VirtualService .</b>
<b>Explanation</b>	Cannot edit the VirtualService. It is probably because of an invalid MessageFlow.
<b>Action</b>	Verify the MessageFlow for the virtual service.

<b>INMCLE0292</b>	<b>Caught an Exception while creating Default StraightThrough routing for the Virtual Service</b>
<b>Explanation</b>	This is an internal error. It is probably because of an invalid route-to.
<b>Action</b>	Verify the endpoints for the virtualization
<b>INMCLE0293</b>	<b>Caught an Exception while creating Default Routing Endpoints for the Virtual Service.</b>
<b>Explanation</b>	This is an internal error. It is probably because of an invalid route-to.
<b>Action</b>	Verify the endpoint properties for the virtualization.
<b>INMCLE0294</b>	<b>Cannot build Processing steps with Empty MessageFlow.</b>
<b>Explanation</b>	This is an internal error. It is because the MessageFlow is empty.
<b>Action</b>	Verify the MessageFlow for the virtual service.
<b>INMCLE0295</b>	<b>Caught an Exception while building Processing steps for the VirtualService.</b>
<b>Explanation</b>	This is an internal error. It is probably because of an invalid MessageFlow.
<b>Action</b>	Verify that the MessageFlow is valid.
<b>INMCLE0296</b>	<b>Cannot add the PolicyActionInstance with templateId {0} to Routing Step</b>
<b>Explanation</b>	This probably occurs because the PolicyActionInstance does not belong to the routing step.
<b>Action</b>	Verify that the PolicyActionInstance is valid.
<b>INMCLE0297</b>	<b>Cannot add empty Default StraightThrough routing and empty Default Routing Endpoints for a Virtual Service.</b>
<b>Explanation</b>	Default routing and endpoint properties are mandatory for a virtual service and cannot be deleted.
<b>Action</b>	Verify that the default routing and endpoint properties are not deleted.
<b>INMCLE0298</b>	<b>Cannot add the PolicyActionInstance with templateId {0} to Enforce Step.</b>
<b>Explanation</b>	This probably occurs because the policy action instance does not belong to the enforce step.
<b>Action</b>	Verify that the policy action instance is valid.

<b>INMCLE0299</b>	<b>Virtualization is not supported for type {0}</b>
<b>Explanation</b>	The asset passed to the virtualization action is not supported for virtualization.
<b>Action</b>	Verify that the asset is suitable for virtualization.
<b>INMCLE0300</b>	<b>Unable to delete the selected asset.</b>
<b>Explanation</b>	{0}. You cannot delete the selected asset either because you do not have the required permission or the asset has dependencies/associations with other objects (Example: pending approval of assets).
<b>Action</b>	Verify that you have the required permission to delete the asset. Also delete all dependencies with the asset and then attempt the deletion again.
<b>INMCLE0301</b>	<b>Unable to remove the selected role(s) for the user {0}</b>
<b>Explanation</b>	{1} Removal of role(s) for the user may have failed if you are trying to delete role(s) inherited through group membership, or if there are dependencies/associations between the objects.
<b>Action</b>	Ensure that all dependencies are resolved, and do not attempt to delete roles inherited through group memberships.
<b>INMCLE0302</b>	<b>Unable to remove the selected role(s) for the group {0}</b>
<b>Explanation</b>	{1}. Removal of role(s) from the group may have failed if a role has dependencies/associations and hence the role removal for the group may fail.
<b>Action</b>	Ensure that the roles do not have any dependencies and then try again.
<b>INMCLE0303</b>	<b>Unable to remove the group membership {0} for the user</b>
<b>Explanation</b>	{1}. You may not be able to remove a user's group membership if the user has dependencies/associations with the group (example: due to an approval policy). In such cases, membership removal for a user will be rejected.
<b>Action</b>	Ensure that all dependencies are resolved between the user and the group, then try again.
<b>INMCLE0304</b>	<b>Unable to retrieve {0} of a {1}</b>
<b>Explanation</b>	{2}. The retrieval may have failed because you do not have required permission, or due to database access error.
<b>Action</b>	Verify that you have required permissions and also ensure that the database is running, then try again.

<b>INMCLE0305</b>	<b>Failed to instantiate class {0}</b>
<b>Explanation</b>	Could not instantiate the given class {0}, possibly because of the following reasons: 1) class file does not exist 2) classpath is incorrect.
<b>Action</b>	Check for the above possible reasons. If the problem persists, contact the CentraSite administrator.
<b>INMCLE0306</b>	<b>Failed to check User {0} has Role {1}</b>
<b>Explanation</b>	An exception occurred while checking the role {1} for the user {0}.
<b>Action</b>	This is an internal error. Please contact the system administrator.
<b>INMCLE0307</b>	<b>Invalid Super User</b>
<b>Explanation</b>	The given super user configuration in CentraSite web.xml is invalid.
<b>Action</b>	Please provide a valid super user ID for the com.softwareag.centrasite.service.privilege.user.id Init-Param property under CentraSite web.xml.
<b>INMCLE0308</b>	<b>Invalid Super User Role</b>
<b>Explanation</b>	The super user configured under CentraSite web.xml does not have the required role to perform the privileged service.
<b>Action</b>	Please assign the CentraSite Administrator role for the super user or provide a user ID that has the CentraSite Administrator role.
<b>INMCLE0309</b>	<b>Invalid Calling User Role</b>
<b>Explanation</b>	The calling user does not have the appropriate role to execute a privileged service.
<b>Action</b>	Please assign an appropriate role to the user in order to perform the privileged service.
<b>INMCLE0310</b>	<b>API Key settings cannot be updated or deleted</b>
<b>Explanation</b>	A policy related to API Key settings is in the pending state, hence the settings cannot be updated.
<b>Action</b>	Ask the approvers to process the pending approval request pertaining to this asset.
<b>INMCLE0311</b>	<b>Cannot find a category for the policy.</b>
<b>Explanation</b>	This is an internal error. The category type cannot be found.
<b>Action</b>	Please verify the message flow.

<b>INMCLE0312</b>	<b>Caught an Exception while retrieving Default StraightThrough routing endpoint for the Virtual Service</b>
<b>Explanation</b>	This is an internal error. It is probably because of an invalid route-to.
<b>Action</b>	Verify the endpoints for the virtualization
<b>INMCLE0313</b>	<b>Caught an Exception while creating Default HTTP Authentication for the Virtual Service.</b>
<b>Explanation</b>	This is an internal error. It is probably because of an invalid policy instance.
<b>Action</b>	Verify the policy instance.
<b>INMCLE0314</b>	<b>Unable to create/edit the selected {0}.</b>
<b>Explanation</b>	You cannot create the {0} {1}, because you do not have the required permission to create/edit the {0}.
<b>Action</b>	Verify that you have the required permission to create/edit the {0}. Contact your administrator, request permission if necessary and try again.
<b>INMCLE0315</b>	<b>Unable to modify the selected group {0}</b>
<b>Explanation</b>	Since the group you are trying to modify is associated with an external repository, you will not be able to modify the external group.
<b>Action</b>	Ensure that the group that you are trying to modify is not an external group.
<b>INMCLE0316</b>	<b>Unable to remove the selected role</b>
<b>Explanation</b>	The logged in user and the user for whom roles are attempted to be removed are the same. This is not allowed.
<b>Action</b>	Please make sure that you are not trying to remove roles assigned to you. It can only be done by the CentraSite Administrator or your Organization Administrator.
<b>INMCLE0317</b>	<b>Failed to find the alias which exists with the given name {0}</b>
<b>Explanation</b>	An exception occurred while trying to find the asset which already exists with the given name {0}.
<b>Action</b>	Please make sure the given asset name does not have any special characters.

<b>INMCLE0319</b>	<b>Email address already registered in CentraSite</b>
<b>Explanation</b>	This email address is already registered to a user in CentraSite.
<b>Action</b>	Enter a different email address.
<b>INMCLE0320</b>	<b>Please wait while we process your registration.</b>
<b>Explanation</b>	User registration with the given email address is being processed by the administrator.
<b>Action</b>	Please wait while we process your registration.
<b>INMCLE0321</b>	<b>Configure parameters for the New Account Registration policy</b>
<b>Explanation</b>	The parameters required for the New Account Registration Policy are missing.
<b>Action</b>	Configure parameters (such as, Approver Group, Approval Mode) for the New Account Registration policy.
<b>INMCLE0322</b>	<b>Failed to publish the asset</b>
<b>Explanation</b>	Unable to publish the asset; possibly because of an incorrect attribute.
<b>Action</b>	Check to make sure that the specified input parameters are correct.
<b>INMCLE0323</b>	<b>Failed to get the publish progress</b>
<b>Explanation</b>	An exception occurred while getting the publish progress information.
<b>Action</b>	Please make sure that the request end point, request and header parameters are correct.
<b>INMCLE0324</b>	<b>Failed to get the publish failed targets</b>
<b>Explanation</b>	An exception occurred while getting the deployment failed targets information.
<b>Action</b>	Please make sure that the request end point, request and header parameters are correct
<b>INMCLE0325</b>	<b>Failed to cancel publish operation</b>
<b>Explanation</b>	An exception occurred while canceling the publish operation.
<b>Action</b>	Please make sure that the request end point, request and header parameters are correct.
<b>INMCLE0326</b>	<b>Privileged user credentials are not configured.</b>
<b>Explanation</b>	The expected privileged user credentials are not configured in {0}.
<b>Action</b>	Check to make sure that the privilege user credentials are configured in {0}.

<b>INMCLE0327</b>	<b>Required roles to perform the publish are missing</b>
<b>Explanation</b>	One or more roles that are required to perform the publish are missing.
<b>Action</b>	Please contact the administrator to add roles required to perform the publish.
<b>INMCLE0328</b>	<b>Aliases or Targets input is empty</b>
<b>Explanation</b>	The publish request does not contains aliases or tagets information.
<b>Action</b>	Please make the you have provided the aliases and targets required to perform the publish operation.
<b>INMCLE0329</b>	<b>You do not have sufficient permissions to execute {0}.</b>
<b>Explanation</b>	You do not have sufficient permissions to execute {0}.
<b>Action</b>	Verify that you have the "Manage Organizations" permission. Contact your administrator and request permission if necessary and then try again.
<b>INMCLE0330</b>	<b>Unauthorized: Access is denied.</b>
<b>Explanation</b>	Access to the service is denied possibly because of insufficient permissions.
<b>Action</b>	Check to make sure that you have the required permissions for accessing the service.
<b>INMCLE0331</b>	<b>Forbidden: Access is denied.</b>
<b>Explanation</b>	Request is forbidden at the moment; possibly because the API key is pending for a renewal request.
<b>Action</b>	Kindly retry after sometime.
<b>INMCLE0332</b>	<b>Required policies to execute the API key renewal and/or revocation are not found.</b>
<b>Explanation</b>	Could not process the renewal and/or revocation requests for the API key; possibly because the requiried policies are not found.
<b>Action</b>	Check to make sure that the API key settings are configured for renewal and/or reovcation. If the problem persists, contact your system administrator.
<b>INMCLE0333</b>	<b>The Message Flow stage {0} that includes the action {1} must include at least one of the following dependent actions: Require Signing, Require Encryption, Require SLL, Require WSS X.509 Token.</b>
<b>Explanation</b>	This action {1} depends on the following actions: Require Signing, Require Encryption, Require SLL, Require WSS X.509 Token.
<b>Action</b>	Choose at least one of the dependent actions for {1}.

<b>INMCLE0339</b>	<b>The Message Flow stage {0} that includes the action {1} must also include {2} of the following dependent action(s): {3}.</b>
<b>Explanation</b>	This action {1} mandate that at least one of the dependent actions {3} be included in the message flow.
<b>Action</b>	Choose at least one of the dependent actions for {1}.
<b>INMCLE0340</b>	<b>Required field is missing</b>
<b>Explanation</b>	Required field {0} for the policy action {1} cannot be empty.
<b>Action</b>	Enter a value for the required field {0}.
<b>INMCLE0341</b>	<b>No action is defined for policy.</b>
<b>Explanation</b>	The Message Flow area in the indicated policy does not contain any actions.
<b>Action</b>	Add one or more actions to the Message Flow area in the indicated policy.
<b>INMCLE0342</b>	<b>Value set of Message Flow is null.</b>
<b>Explanation</b>	Value returned by Message Flow is null.
<b>Action</b>	Set a value for the Message Flow.
<b>INMCLE0343</b>	<b>{0} attribute not valid.</b>
<b>Explanation</b>	The specified attribute {0} is not a valid policy constraint.
<b>Action</b>	Specify a valid attribute.
<b>INMCLE0344</b>	<b>One or more dependent actions or action parameters are not configured.</b>
<b>Explanation</b>	There are no dependent actions or action parameters configured for the Message Flow.
<b>Action</b>	Configure the dependent actions and action parameters in the Message Flow area.
<b>INMCLE0345</b>	<b>Failed to change lifecycle state of {0}.</b>
<b>Explanation</b>	Could not change lifecycle state of this {0}, possibly because it has been implicitly locked by the server for an ongoing modification.
<b>Action</b>	Please try after some time.

<b>INMCLE0346</b>	<b>Failed to change lifecycle state of {0}.</b>
<b>Explanation</b>	Could not change lifecycle of this {0}, possibly because you do not have the required permissions.
<b>Action</b>	Check to make sure that you have the required permissions to change state of this{0}.
<b>INMCLE0347</b>	<b>Failed to delete {0}.</b>
<b>Explanation</b>	Could not delete this {0}, possibly because you do not have the required permissions.
<b>Action</b>	Check to make sure that you have the required permissions to delete this {0}.
<b>INMCLE0348</b>	<b>Failed to delete {0}.</b>
<b>Explanation</b>	Could not delete this {0}, possibly because it has been implicitly locked by the server for an ongoing modification.
<b>Action</b>	Please try after some time.
<b>INMCLE0349Error</b>	<b>CentraSite could not create the runtime alias. {0}</b>
<b>Explanation</b>	Error while creating a runtime alias in CentraSite.
<b>Action</b>	Check if a runtime alias with the same name already exists and if the parameters specified for the runtime alias are correct.
<b>INMCLE0350Error</b>	<b>CentraSite failed to publish the runtime alias to targets. {0}</b>
<b>Explanation</b>	Error while publishing runtime alias from CentraSite to target(s).
<b>Action</b>	Check the log file for more information.
<b>INMCLE0351</b>	<b>{0} action failed because the required objects {1} are not set.</b>
<b>Explanation</b>	Action {0} requires that the objects be set before it can execute.
<b>Action</b>	Ensure that the required objects {1} are set accordingly for the action.
<b>INMCLE0352</b>	<b>You must select valid objects for publishing/unpublishing to/from API Portals.</b>
<b>Explanation</b>	One or more of the selected registry objects cannot be published/unpublished to/from the specified API Portals. This is possibly because, one or more of the selected objects does not belong to the asset type "Service" or its variants.
<b>Action</b>	Make sure that the objects selected for publishing/unpublishing are of the asset type "Service" or any of its variants.

<b>INMCLE0353</b>	<b>{0} ERROR: Could not publish/unpublish APIs to API Portals.</b>
<b>Explanation</b>	An error {0} occurred while trying to publish/unpublish APIs to/from API Portals, possibly because one or more of the API Portal servers were unavailable.
<b>Action</b>	Make sure the API Portal servers are up and running. If the problem persists, contact your administrator.
<b>INMCLE0354</b>	<b>Category {0} does not belong to the taxonomy "Sandbox".</b>
<b>Explanation</b>	An attempt was made to classify an endpoint with the taxonomy "Sandbox", but the specified category {0} does not exist in the taxonomy "Sandbox".
<b>Action</b>	Make sure the category exists in the taxonomy "Sandbox".
<b>INMCLE0355</b>	<b>Failed to publish asset {0} to target.</b>
<b>Explanation</b>	Could not publish the specified asset {0} to the target, possibly because the specified asset is under the control of a lifecycle model (LCM), and is in a non-deployable state.
<b>Action</b>	Make sure you switch the asset to an active, ready-to-deploy state, before trying to publish asset to the target.
<b>INMCLE0356Error</b>	<b>Error while deploying runtime aliases. {0}</b>
<b>Explanation</b>	CentraSite could not deploy runtime aliases.
<b>Action</b>	Check the stack trace information in the log file for more information.
<b>INMCLE0357Error</b>	<b>Error while undeploying runtime aliases. {0}</b>
<b>Explanation</b>	CentraSite cannot undeploy runtime aliases.
<b>Action</b>	Check the stack trace information in the log file for more information.
<b>INMCLE0358</b>	<b>Could not get information from API Portal {0}, because of invalid user credentials.</b>
<b>Explanation</b>	An error occurred while getting an information from the specified API Portal {0}, possibly because of invalid username and/or password.
<b>Action</b>	Enter a valid username and/or password, and then try again.
<b>INMCLE0359</b>	<b>Could not get information from API Portal {0}.</b>
<b>Explanation</b>	An error occurred while getting an information from the specified API Portal {0}. There could be multiple reasons why this might have occurred: (1) API Portal server is down or inaccessible (2) invalid user credentials (3) application error on the CentraSite or API Portal server.
<b>Action</b>	Make sure the API Portal server is up and running, and the user credentials are correct.

<b>INMCLE0360</b>	<b>The API is published successfully but cannot be associated with API Portal.</b>
<b>Explanation</b>	The API was successfully published to the API Portal server, but could not be associated with it. This could be caused by an application error.
<b>Action</b>	Make sure the API Portal server is up and running. If the problem persists, contact your administrator.
<b>INMCLE0361</b>	<b>The API is unpublished successfully, but existing association with API Portal cannot be revoked.</b>
<b>Explanation</b>	The API was successfully unpublished from the API Portal server, but its existing association with API Portal could not be revoked. This could be caused by an application error.
<b>Action</b>	Make sure the API Portal server is up and running. If the problem persists, contact your administrator.
<b>INMCLE0362</b>	<b>Could not find API id {0} in the CentraSite registry.</b>
<b>Explanation</b>	An attempt was made to publish or unpublish the specified API which is not found in the CentraSite registry.
<b>Action</b>	Verify the API id is correct. If the API id is correct and the error persists, contact your administrator.
<b>INMCLE0363</b>	<b>Could not find API Portal id {0} in the CentraSite registry.</b>
<b>Explanation</b>	An attempt was made to publish or unpublish an API to the specified API Portal which is not found in the CentraSite registry.
<b>Action</b>	Verify the API Portal id is correct. If the API Portal id is correct and the error persists, contact your administrator.
<b>INMCLE0364</b>	<b>Could not find status id {0} of the publish/unpublish action in the CentraSite registry.</b>
<b>Explanation</b>	The publish or unpublish status could not be determined. The identifier used to get the status of the action is no longer valid, possibly because the action has already been completed.
<b>Action</b>	Verify the status id is correct. If the status id is correct and the error persists, contact your administrator.

<b>INMCLE0365</b>	<b>Database access error. Could not connect to the CentraSite Registry Repository.</b>
<b>Explanation</b>	The CentraSite Registry Repository is unavailable.
<b>Action</b>	Restart the Software AG CentraSite Registry Repository and Software AG Runtime. If the problem persists, contact your administrator.
<b>INMCLE0366</b>	<b>One or more of the selected resources have HTTP methods that are not supported for virtualization.</b>
<b>Explanation</b>	Resources with GET, POST, PUT, PATCH and DELETE methods are only allowed for virtualization. The following resource(s) have been found to have unsupported HTTP methods: {0}
<b>Action</b>	Select the resources that have supported HTTP methods.
<b>INMCLE0367</b>	<b>Could not set attribute {0} of the REST/XML service.</b>
<b>Explanation</b>	{1}: An error occurred while trying to set the attribute {0} of the REST/XML service. There could be multiple reasons why this might have occurred: (1) insufficient permissions (2) transaction timeouts (3) trying to modify an outdated service (4) invalid value for the attribute.
<b>Action</b>	Ensure that you have sufficient permissions to modify the service. If the underlying error is a transaction timeout or an outdated service, try setting the attribute again.
<b>INMCLE0368</b>	<b>Could not save the web service "{0}".</b>
<b>Explanation</b>	{1}: An error occurred while trying to save the specified REST/XML service {0}. There could be multiple reasons why this might have occurred: (1) insufficient permissions (2) transaction timeouts (3) trying to modify an outdated service (4) invalid property values for the service (5) a policy denies the save.
<b>Action</b>	Ensure that you have sufficient permissions to modify and save the service. Check for enabled policies denying the save. If the underlying error is a transaction timeout or an outdated service, try saving the service again.
<b>INMCLE0369</b>	<b>Failed to virtualize web service.</b>
<b>Explanation</b>	Could not virtualize the web service, possibly because the specified service doesn't reference any WSDL:binding element.
<b>Action</b>	Make sure that the WSDL contains a binding element.

<b>INMCLE0370</b>	<b>Failed to register CentraSite in the following API Portals: {0}</b>
<b>Explanation</b>	An error occurred while registering CentraSite in the indicated API Portals {0}. There could be multiple reasons why this might have occurred: (1) API Portal server is down or inaccessible (2) invalid user credentials (3) application error on the API Portal server.
<b>Action</b>	Make sure the API Portal server is up and running, and the user credentials are correct.
<b>INMCLE0371</b>	<b>Failed to delete the API {0}.</b>
<b>Explanation</b>	The selected API {0} cannot be deleted, because it is published to one or more API Portals.
<b>Action</b>	To delete the selected API first unpublish it from all the API Portals and then try again.
<b>INMCLE0373</b>	<b>Trying to access a resource {0} in API Portal {1} is forbidden.</b>
<b>Explanation</b>	A HTTP 403 error occurred while trying to access the resource {0} in API Portal {1} , possibly because you do not have sufficient access rights to access the specified resource in API Portal.
<b>Action</b>	Verify that you have the appropriate access rights. Contact your administrator and request access if necessary and then try again.
<b>INMCLE0374</b>	<b>Resource {0} is not found in API Portal {1}.</b>
<b>Explanation</b>	A HTTP 404 error occurred while trying to access the resource {0} in API Portal {1}. There could be multiple reasons why this might have occurred: (1) API Portal server is down or inaccessible (2) invalid resource endpoint.
<b>Action</b>	Make sure the API Portal server is up and running, and the resource endpoint is correct. If the problem persists, contact your administrator.
<b>INMCLE0375</b>	<b>Technical error encountered in API Portal {0}.</b>
<b>Explanation</b>	This exception is unexpected. The cause is not immediately known.
<b>Action</b>	Contact your system administrator with exception stack trace information present in the error log.
<b>INMCLE0376</b>	<b>An error occurred while creating a gateway in CentraSite.</b>
<b>Explanation</b>	One or more gateway configuration parameters are null.
<b>Action</b>	Specify the mandatory gateway parameters, and try again.

<b>INMCLE0377</b>	<b>An error occurred while creating a gateway in CentraSite. {0}</b>
<b>Explanation</b>	An error occurred while creating a gateway in CentraSite. Check the CentraSite logs for details.
<b>Action</b>	Fix the error(s) and retry the "set gateway" command. If the issue persists, contact Software AG support with the log information.
<b>INMCLE0379</b>	<b>Unable to find a gateway in CentraSite with the ID, "{0}".</b>
<b>Explanation</b>	A gateway with the specified identifier does not exist in CentraSite.
<b>Action</b>	Specify a valid gateway ID, and try again.
<b>INMCLE0380</b>	<b>CentraSite cannot retrieve the gateway details because the mandatory attribute, gateway ID is not available.</b>
<b>Explanation</b>	Gateway ID for the gateway is not available in CentraSite.
<b>Action</b>	Check if the gateway ID set in CentraSite is valid.
<b>INMCLE0381</b>	<b>CentraSite could not delete the gateway because the gateway ID is not specified.</b>
<b>Explanation</b>	The mandatory gateway ID parameter is not specified for the "remove gateway" command in CentraSite.
<b>Action</b>	Specify the gateway ID parameter and try and command again.
<b>INMCLE0382</b>	<b>CentraSite could not create/update a gateway because a mandatory attribute for the command is not specified. Attribute not specified: {0}, gateway: {1}</b>
<b>Explanation</b>	A mandatory attribute is not specified for the set gateway command in CentraSite.
<b>Action</b>	Specify the mandatory parameter and try the "set gateway" command again.
<b>INMCLE0383</b>	<b>Error in synchronizing consumers with Mediator gateway.</b>
<b>Explanation</b>	An error occurred while synchronizing consumers with the Mediator gateway. There could be multiple reasons why this might have occurred: (1) Mediator is down or inaccessible. (2) At least one consumer application is not available for synchronizing.
<b>Action</b>	Make sure that Mediator is up and running, and at least one consumer application is available for synchronizing with the gateway.

<b>INMCLE0384</b>	<b>You do not have permission in CentraSite to publish/unpublish the API Portal, {0}.</b>
<b>Explanation</b>	To perform publish/unpublish operation on an API Portal, you must have either API Portal Administrator role or the modify permission on the selected API Portal(s).
<b>Action</b>	Contact the CentraSite administrator to add roles/permissions required to perform the publish or unpublish APIs.
<b>INMCLE0385</b>	<b>Error publishing CentraSite communication details to Mediator.</b>
<b>Explanation</b>	CentraSite cannot publish communication details to Mediator. Possible reasons could be: (1) Mediator is down or inaccessible (2) invalid user credentials or (3) Error in Mediator when you publish information from CentraSite to Mediator.
<b>Action</b>	Check Mediator and CentraSite log files and take corrective actions.
<b>INMCLE0386</b>	<b>Could not publish CentraSite Communication Details to Mediator.</b>
<b>Explanation</b>	An error occurred while trying to publish CentraSite Communication Details to Mediator. There could be multiple reasons why this might have occurred: (1) Integration Server on which Mediator is running is down or inaccessible (2) invalid user credentials (3) application error on the CentraSite server or Integration Server.
<b>Action</b>	Make sure the Integration Server is up and running, and the user credentials are correct. If the problem persists, contact your administrator.
<b>INMCLE0387</b>	<b>Could not deploy 'CentraSite Communication Details' to Mediator due to HTTP connection failure.</b>
<b>Explanation</b>	Failure of HTTP connection between CentraSite and Mediator.
<b>Action</b>	Check if the Mediator credentials and endpoint URL specified are valid and try again.
<b>INMCLE0388</b>	<b>Mediator endpoint URL format is not correct. Format:</b> <PROTOCOL>://<HOSTNAME>:<PORT>or <PROTOCOL>://<HOSTNAME>
<b>Explanation</b>	The Mediator endpoint URL should be specified in one of the following formats:(1) <PROTOCOL>://<HOSTNAME>:<PORT>(2) <PROTOCOL>://<HOSTNAME>
<b>Action</b>	Enter the Mediator endpoint URL in the correct format and try again.
<b>INMCLE0389</b>	<b>Could not unpublish instances of API Portal.</b>
<b>Explanation</b>	An error occurred while unpublishing the selected instances of API Portal. There could be multiple reasons why this might have occurred: (1) API Portal server was down or inaccessible (2) instances of API Portal was successfully unpublished, but its existing association with published APIs and access tokens could not be revoked, possibly because of an application error.
<b>Action</b>	Make sure the API Portal server is up and running. Try unpublishing the selected instances of API Portal using the "Force Unpublish" action. If the problem persists, contact your administrator.

<b>INMCLE0390</b>	<b>Path parameters can only be defined at the Resource level.</b>
<b>Explanation</b>	Path parameters can be defined at the Resource level; but cannot be defined at the API level or Method level.
<b>Action</b>	Specify a path parameter at the Resource level.
<b>INMCLE0391</b>	<b>Error while publishing/un-publishing to/from the gateways selected.</b>
<b>Explanation</b>	You do not have permission to publish/un-publish to/from one or more of the selected gateways.
<b>Action</b>	Check if you have permission to publish/un-publish to/from the selected targets, and try again.
<b>INMCLE0392</b>	<b>Download Documents action failed.</b>
<b>Explanation</b>	An attempt was made to execute the Download Documents action without selecting an asset of the type Service.
<b>Action</b>	Select an asset of the type Service to execute this action.
<b>INMCLE0393</b>	<b>No document(s) to download.</b>
<b>Explanation</b>	Service doesn't have any documents to download.
<b>Action</b>	Ensure there is at least one document to download. Service owner has to first upload documents which can be downloaded later.
<b>INMCLE0394</b>	<b>Organization field cannot be empty.</b>
<b>Explanation</b>	You have not entered the name of the submitting organization when creating an asset in CentraSite.
<b>Action</b>	Enter the organization name.
<b>INMCLE0395</b>	<b>Failed to create an asset because the required specification file is invalid.</b>
<b>Explanation</b>	Could not create an asset, possibly because the given {0} specification file is invalid.
<b>Action</b>	Upload a valid {0} specification file. If the problem persists, contact your administrator.
<b>INMCLE0396</b>	<b>Unable to initialize and load {0} importer implementation.</b>
<b>Explanation</b>	{1}: An error occurred while initializing the {0} importer implementation. There could be multiple reasons why this might have occurred: (1) incorrec importer implementation class is incorrect (2) importer implementation class could not be identified (3) importer implementation class failed to instantiate.
<b>Action</b>	Make sure that the importer implementation and specifications are correct. For more information about importer specifications, see the document Working with REST-based APIs. Contact your administrator if the problem persists.

<b>INMCLE0397</b>	<b>Failed to create an asset of type {0} from the specification type {1}.</b>
<b>Explanation</b>	In CentraSite, certain asset types require a particular type of specification file for creating asset instances of that type. An asset could not be created if the given type of specification file is not supported for that asset type.
<b>Action</b>	For a list of the asset types and their supported specification files, see the document Working with REST-based APIs. Contact your administrator if the problem persists.
<b>INMCLE0398</b>	<b>Could not create or modify {1} asset from the {0} specification file.</b>
<b>Explanation</b>	{2}: An error occurred while trying to import the specification file. There could be multiple reasons why this might have occurred: (1) specification file is invalid (2) data type or specification type is not supported in CentraSite (3) an internal error in saving the asset.
<b>Action</b>	Make sure the specification file is valid. For information on the mappings between the specification file and asset in CentraSite, see the document Working with REST-based APIs. Contact your administrator if the problem persists.
<b>INMCLE0399</b>	<b>Error occurred while importing the archive file: {0}</b>
<b>Explanation</b>	An error occurred while importing the archive file.
<b>Action</b>	Check the stack trace for the cause of the failure and if required, contact your system administrator.
<b>INMCLE0400</b>	<b>{0} ERROR: Could not unpublish APIs from API Portals.</b>
<b>Explanation</b>	An error {0} occurred while trying to unpublish APIs from API Portals, possibly because one or more of the API Portal servers were unavailable.
<b>Action</b>	Make sure the API(s) are already published and API Portal servers are up and running. If the problem persists, contact your administrator.
<b>INMCLE0401</b>	<b>Could not generate access token for API Portal.</b>
<b>Explanation</b>	An attempt was made to request access token through an API Portal, but the specified API Portal UUID {0} does not exist in the CentraSite registry.
<b>Action</b>	Make sure the API Portal UUID exists in the CentraSite registry.
<b>INMCLE0402</b>	<b>Could not generate access token for API Portal user, possibly because the user does not have an E-mail address.</b>
<b>Explanation</b>	A request for the access token triggered by an API Portal user could not be processed, possibly because the specified user does not have an E-mail address.
<b>Action</b>	Enter a valid E-mail address.

<b>INMCLE0403</b>	<b>CentraSite cannot update the gateway. {0}</b>
<b>Explanation</b>	An error occurred while updating a gateway in CentraSite.
<b>Action</b>	Contact your system administrator with exception stack trace information in the CentraSite log.
<b>INMCLE0407</b>	<b>Failed to undeploy the asset {0} on target {1}.</b>
<b>Explanation</b>	Could not undeploy the asset {0} on given target {1}. Possible reason: {2}
<b>Action</b>	Check the stack trace information for details.
<b>INMCLE0409</b>	<b>Could not find user with email address {0}</b>
<b>Explanation</b>	No user with the specified email address was found.
<b>Action</b>	Correct the parameter value of ' __consumerEmailAddress' in the configuration file and try again.
<b>INMCLE0410</b>	<b>Could not find CentraSite object with id {0}</b>
<b>Explanation</b>	A CentraSite object with the specified id was not found.
<b>Action</b>	Correct the CentraSite object id and try again.
<b>INMCLE0411</b>	<b>User is not a CentraSite Administrator.</b>
<b>Explanation</b>	The user does not have necessary permission to perform the service.
<b>Action</b>	Log in with a CentraSite Administrator role.
<b>INMCLE0412</b>	<b>Value for parameter '{0}' is missing.</b>
<b>Explanation</b>	The value for the mandatory parameter {0} is missing.
<b>Action</b>	Provide a value for the mandatory parameter {0}.
<b>INMCLE0413</b>	<b>Failed to remove consumer/s {0} from asset/s {1}. Possible reason for failure: {2}</b>
<b>Explanation</b>	You may encounter an error while trying to remove a consumer from an asset. It could be due to one of the following reasons: (1) Insufficient permissions (2) The consumer is not properly associated (3) The consumed asset is in Pending state (4) Internal error occurred while removing the consumer.
<b>Action</b>	Ensure that you have modify permission on the asset whose consumer or consumed assets you are trying to remove. If it is an internal error, please retry the operation after sometime.

<b>INMCLE0414</b>	<b>API does not have a valid end point.</b>
<b>Explanation</b>	The API to be published to API Portal does not have a valid end point.
<b>Action</b>	Ensure that the API has valid endpoint. If there is an endpoint available, ensure that the endpoint is categorized with the category which is chosen during the API publish. For example, if the API endpoint is categorized as "production" endpoint and the publisher chooses to publish only "Test" endpoint, then technically API has no endpoint to publish.
<b>INMCLE0415</b>	<b>Failed to get applicable usecases for object {0}.</b>
<b>Explanation</b>	An unexpected exception occurred while trying to get applicable usecases for {0}. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information.
<b>INMCLE0416</b>	<b>Wrong usage of the Impact Analysis action API {0}.</b>
<b>Explanation</b>	Incorrect usage of the Impact Analysis action API. This problem occurs, when the '{0}' method is triggered with action in a state other than '{1}'.
<b>Action</b>	Before you execute the '{0}' method, verify that the action is in '{1}' state.
<b>INMCLE0417</b>	<b>Could not retrieve the selected usecase.</b>
<b>Explanation</b>	Failed to retrieve the selected usecase, possibly because the report is not implicitly set for retrieval.
<b>Action</b>	Use the 'setSelectedUseCase(..)' to set a report for this action.
<b>INMCLE0418</b>	<b>Failed to execute {0}.</b>
<b>Explanation</b>	You do not have necessary permission to perform this action.
<b>Action</b>	Before executing {0} make sure that you have the permission. Contact your CentraSite administrator and if necessary request access and then try again.
<b>INMCLE0419</b>	<b>CentraSite could not create/update the gateway because a gateway with the gateway name specified in the command already exists.</b>
<b>Explanation</b>	A gateway already exists with the gateway name given in the command.
<b>Action</b>	Modify the gateway name and try the "set gateway" command again.

<b>INMCLE0420</b>	<b>Could not retrieve the parameters of the selected report {0}.</b>
<b>Explanation</b>	An unexpected exception occurred while trying to retrieve the parameters of the selected report {0}. The cause is not immediately known.
<b>Action</b>	Check the log file for detailed information.
<b>INMCLE0421</b>	<b>Error while fetching action for template-id {0} from enforce-actions.</b>
<b>Explanation</b>	Invalid Template Id found while fetching action for template-id {0} from enforce-actions.
<b>Action</b>	Contact your CentraSite Administrator.
<b>INMCLE0422</b>	<b>Cannot register consumers since there are no consumable types defined for {0} type.</b>
<b>Explanation</b>	You cannot register consumers for this asset since the asset type {0} does not have any consumable types defined for it. Asset instances of the defined consumable types can only be registered as consumers.
<b>Action</b>	Ensure that the type {0} has consumable types defined for it. Refer to the documentation to define consumable types for an asset type.
<b>INMCLE0423</b>	<b>Could not save a scheduled report.</b>
<b>Explanation</b>	An unexpected exception occurred while trying to save a scheduled report. The cause is not immediately known.
<b>Action</b>	Check the log file for detailed information.
<b>INMCLE0424</b>	<b>Invalid parameter name {0}.</b>
<b>Explanation</b>	You have entered an invalid parameter name.
<b>Action</b>	Provide a valid parameter name without special characters and try again.
<b>INMCLE0425</b>	<b>Invalid parameter type {0}.</b>
<b>Explanation</b>	You have entered an invalid parameter type.
<b>Action</b>	Provide a valid parameter type and try again.
<b>INMCLE0426</b>	<b>Failed to delete the asset {0}.</b>
<b>Explanation</b>	The selected asset {0} cannot be deleted because it is consumed by one or more assets.
<b>Action</b>	Make sure you unconsume all consumers from the asset, before trying to delete it.

<b>INMCLE0428</b>	<b>Exception occurred while searching for Gateways.</b>
<b>Explanation</b>	An exception occurred while searching for Gateways.
<b>Action</b>	Contact your System Administrator.
<b>INMCLE0429</b>	<b>Failure in performing resource synchronization for virtual alias {0} during virtualization.</b>
<b>Explanation</b>	An error occurred while performing resource synchronization for the virtual alias {0}. This may be due to improper resource selection during synchronization or an invalid message flow.
<b>Action</b>	Verify the resources that you have selected for synchronization with the native service and verify the message flow for the virtual service.
<b>INMCLE0430</b>	<b>Error while fetching saved search {0}.xml</b>
<b>Explanation</b>	An error occurred because the specified saved search resource cannot be found.
<b>Action</b>	Make sure the specified saved search is available.
<b>INMCLE0431</b>	<b>Invalid Consumer Certificate {0}.</b>
<b>Explanation</b>	The attached consumer certificate is invalid.
<b>Action</b>	Attach a valid consumer certificate and try again.
<b>INMCLE0432</b>	<b>Failed to create an OData service due to unsupported version {0} of OData.</b>
<b>Explanation</b>	Could not create OData service in the CentraSite registry. This is because the specified OData version {0} is not supported in CentraSite.
<b>Action</b>	For a list of supported OData versions, see the CentraSite documentation.
<b>INMCLE0433</b>	<b>Failed to publish CentraSite details to the following Mediators: {0}</b>
<b>Explanation</b>	An error occurred while publishing CentraSite details in the indicated Mediators {0}. There could be multiple reasons why this might have occurred: (1) Mediator server is down or inaccessible (2) invalid user credentials (3) application error on the Mediator server.
<b>Action</b>	Make sure the Mediator server is up and running, and the user credentials are correct.

<b>INMCLE0434</b>	<b>Failed to execute {0}.</b>
<b>Explanation</b>	Could not execute {0}. This is possibly because you do not have the sufficient permissions to execute {0}.
<b>Action</b>	Verify that you have the sufficient permissions. Contact your administrator and request permission if necessary and then try again.
<b>INMCLE0435</b>	<b>Failed to create an OData service due to unexpected metadata at {0}.</b>
<b>Explanation</b>	The metadata of the specified OData service has unexpected content. One or more of the required elements are missing.
<b>Action</b>	Check the metadata of the given OData service.
<b>INMCLE0436</b>	<b>An error occurred while executing an extension enabled for the CentraSite Business UI.\nError Message: {0}</b>
<b>Explanation</b>	A detailed explanation of the error thrown by the extension can be found here. Explanation: {1}
<b>Action</b>	Possible action steps to take: {2} \nIf the information provided by this error message is insufficient, please refer to the logs or contact your Administrator.
<b>INMCLE0437</b>	<b>Failed to check the permissions of the current user.</b>
<b>Explanation</b>	This is an unexpected exception. The cause is not immediately known.
<b>Action</b>	Check the stack trace for detailed information.
<b>INMCLE0438</b>	<b>Error publishing CentraSite communication details to Mediator.</b>
<b>Explanation</b>	CentraSite cannot publish communication details to Mediator version older than 9.8.
<b>Action</b>	Configure a supported version of Mediator.
<b>INMCLE0439</b>	<b>Could not remove API Key configuration because one or more API Key consumers are associated to the virtual service.</b>
<b>Explanation</b>	All API Key consumers associated to the virtual service must be deleted before revoking the API Key option in API Consumption Settings.
<b>Action</b>	Delete all associations between the virtual service and API Key consumers and try again.

<b>INMCLE0440</b>	<b>Could not remove OAuth configuration because one or more OAuth consumers are associated to the virtual service.</b>
<b>Explanation</b>	All OAuth consumers associated to the virtual service must be deleted before revoking the OAuth option in API Consumption Settings.
<b>Action</b>	Delete all associations between the virtual service and OAuth consumers and try again.
<b>INMCLE0441</b>	<b>Failed to initialize an action class.</b>
<b>Explanation</b>	Could not initialize the action class. Check the CentraSite logs for the action class name and for more details.
<b>Action</b>	Check to make sure that the implementation class is correct and follows a specified syntax. Refer to the documentation reference for Action Implementation class.
<b>INMCLE0445</b>	<b>Could not publish CentraSite communication details to {0}.</b>
<b>Explanation</b>	An error occurred while trying to publish the CentraSite communication details to {0}. There could be multiple reasons why this might have occurred: (1) {0} is down or inaccessible (2) invalid user credentials (3) application error in {0}.
<b>Action</b>	Make sure {0} is up and running, user credentials are correct, and then try again.
<b>INMCLE0446</b>	<b>Failed to publish CentraSite communication details to {0}.</b>
<b>Explanation</b>	Could not publish the CentraSite communication details to {0}, possibly because of a HTTP connection failure between CentraSite and {0}.
<b>Action</b>	Make sure the endpoint URL is valid, user credentials are correct, and then try again.
<b>INMCLE0447</b>	<b>{0} endpoint URL is invalid.</b>
<b>Explanation</b>	The specified {0} endpoint URL is invalid, possibly because it does not comply to the following formats:(1) <PROTOCOL>://<HOSTNAME>:<PORT>(2) <PROTOCOL>://<HOSTNAME>
<b>Action</b>	Enter a valid {0} endpoint URL and try again.
<b>INMCLE0448</b>	<b>Failed to publish CentraSite communication details to {0}.</b>
<b>Explanation</b>	Could not publish the CentraSite communication details to {0}, possibly because the SNMP configuration is not accessible.
<b>Action</b>	Please contact your administrator.

<b>INMCLE0449</b>	<b>Failed to register CentraSite in {0}.</b>
<b>Explanation</b>	An error occurred while registering CentraSite in {0}, possibly because {0} is already registered with another instance of CentraSite.
<b>Action</b>	Deregister the existing CentraSite instance from {0}, and then register CentraSite again.
<b>INMCLE0450</b>	<b>Failed to deregister CentraSite from {0}.</b>
<b>Explanation</b>	An error occurred while deregistering CentraSite from {0}. There could be multiple reasons why this might have occurred: (1) {0} is down or inaccessible (2) invalid user credentials (3) application error in {0}.
<b>Action</b>	Make sure {0} is up and running, user credentials are correct, and then try again.
<b>INMCLE0451</b>	<b>Failed to load SNMP configuration file.</b>
<b>Explanation</b>	Could not load the SNMP configuration file, possibly because the configuration file is missing or the file path is incorrect.
<b>Action</b>	Please contact your administrator.
<b>INMCLE0452</b>	<b>Failed to parse SNMP configuration file.</b>
<b>Explanation</b>	Could not parse the SNMP configuration file, possibly because the configuration file structure is not as expected.
<b>Action</b>	Please contact your administrator.
<b>INMCLE0453</b>	<b>Could not update the publish or unpublish status of API Gateway asset.</b>
<b>Explanation</b>	An error occurred while trying to update the publish or unpublish status of API Gateway asset.
<b>Action</b>	Please contact your administrator.
<b>INMCLE0454</b>	<b>Could not update the publish or unpublish status of API Gateway asset.</b>
<b>Explanation</b>	An error occurred while trying to update the publish or unpublish status of API Gateway asset, possibly because the update gateway status call does not have a valid value for the gateway ID.
<b>Action</b>	Please contact your administrator.

<b>INMCLE0455</b>	<b>Could not update the publish or unpublish status of API Gateway asset.</b>
<b>Explanation</b>	An error occurred while trying to update the publish or unpublish status of API Gateway asset, possibly because the update gateway status call does not have a valid value for the status parameter.
<b>Action</b>	Please contact your administrator.
<b>INMCLE0457</b>	<b>Asset type with the namespace URI {0} already exists.</b>
<b>Explanation</b>	An asset type with the given namespace URI {0} already exists.
<b>Action</b>	Change the name of the asset type and try it again.
<b>INMCLE0458</b>	<b>Failed to add a new asset type.</b>
<b>Explanation</b>	Could not add the new asset type.
<b>Action</b>	Check the stack trace information in the log file for more information.
<b>INMCLE0459</b>	<b>Failed to get the relationship types.</b>
<b>Explanation</b>	Could not fetch the relationship types.
<b>Action</b>	Check the stack trace information in the log file for more information.
<b>INMCLE0460</b>	<b>Failed to get the association types.</b>
<b>Explanation</b>	Could not fetch the association types.
<b>Action</b>	Check the stack trace information in the log file for more information.
<b>INMCLE0461</b>	<b>Failed to get the object types.</b>
<b>Explanation</b>	Could not fetch the object types.
<b>Action</b>	Check the stack trace information in the log file for more information.
<b>INMCLE0462</b>	<b>Failed to get the consumable types.</b>
<b>Explanation</b>	Could not fetch the consumable types.
<b>Action</b>	Check the stack trace information in the log file for more information.
<b>INMCLE0463</b>	<b>Failed to set the consumable types.</b>
<b>Explanation</b>	Could not set the consumable types.
<b>Action</b>	Check the stack trace information in the log file for more information.

---

<b>INMCLE0464</b>	<b>Unable to get the option {0} for asset type {1}.</b>
<b>Explanation</b>	Could not fetch the option {0} for asset type {1}.
<b>Action</b>	Check the stack trace information in the log file for more information.
<b>INMCLE0465</b>	<b>Unable to update option {0} for asset type {1}.</b>
<b>Explanation</b>	Could not update the option {0} for asset type {1}.
<b>Action</b>	Check the stack trace information in the log file for more information.
<b>INMCLE0466</b>	<b>Failed to add attribute {0} to asset type {1}.</b>
<b>Explanation</b>	Could not add the attribute {0} to asset type {1}.
<b>Action</b>	Check the stack trace information in the log file for more information.
<b>INMCLE0467</b>	<b>Failed to modify attribute {0} of asset type {1}.</b>
<b>Explanation</b>	Could not modify the attribute {0} of asset type {1}.
<b>Action</b>	Check the stack trace information in the log file for more information.
<b>INMCLE0468</b>	<b>Failed to delete attribute {0} from asset type {1}.</b>
<b>Explanation</b>	Could not delete the attribute {0} from asset type {1}.
<b>Action</b>	Check the stack trace information in the log file for more information.
<b>INMCLE0469</b>	<b>Failed to set the profile sequence for asset type {0}.</b>
<b>Explanation</b>	Could not set the profile sequence for asset type {0}.
<b>Action</b>	Check the stack trace information in the log file for more information.
<b>INMCLE0470</b>	<b>Failed to get the profiles of asset type {0}.</b>
<b>Explanation</b>	Could not fetch the profiles of asset type {0}.
<b>Action</b>	Check the stack trace information in the log file for more information.
<b>INMCLE0471</b>	<b>Failed to add profile {0} to asset type {1}.</b>
<b>Explanation</b>	Could not add the profile {0} to asset type {1}.
<b>Action</b>	Check the stack trace information in the log file for more information.

<b>INMCLE0472</b>	<b>Failed to modify profile {0} of asset type {1}.</b>
<b>Explanation</b>	Could not modify the profile {0} of asset type {1}.
<b>Action</b>	Check the stack trace information in the log file for more information.
<b>INMCLE0473</b>	<b>Failed to delete profile {0} from asset type {1}.</b>
<b>Explanation</b>	Could not delete the profile {0} from asset type {1}.
<b>Action</b>	Check the stack trace information in the log file for more information.
<b>INMCLE0474</b>	<b>Failed to create a template for computed attribute or profile {0}.</b>
<b>Explanation</b>	Could not create a template for computed attribute or profile {0}.
<b>Action</b>	Check the stack trace information in the log file for more information.
<b>INMCLE0475</b>	<b>Failed to update the template for computed attribute or profile {0}.</b>
<b>Explanation</b>	Could not update the template for computed attribute or profile {0}.
<b>Action</b>	Check the stack trace information in the log file for more information.
<b>INMCLE0476</b>	<b>Failed to save asset type {0}.</b>
<b>Explanation</b>	An error occurred while trying to save the asset type {0}.
<b>Action</b>	Check the stack trace information in the log file for more information.
<b>INMCLI0001</b>	<b>Parsing failed. Make sure the configuration file syntax (or) path is correct.</b>
<b>Explanation</b>	This is probably because of the following reasons: 1) syntax of the configuration file is invalid 2) specified configuration file path is incorrect.
<b>Action</b>	Check for the above possible reasons and execute again. Refer to the CentraSite documentation for creating a valid configuration file.
<b>INMCLI0002</b>	<b>Internal error.</b>
<b>Explanation</b>	An unexpected error occurred due to failure in the system execution.
<b>Action</b>	Contact the CentraSite administrator.
<b>INMCLI0003</b>	<b>Error while executing command \${0}.</b>
<b>Explanation</b>	Unexpected error occurred while executing the command.
<b>Action</b>	Check the error message for details.

<b>INMCLI0004</b>	<b> \${0} is an invalid log unit; possible values are \${1}.</b>
<b>Explanation</b>	The specified log unit is not supported. Possible values are \${1}.
<b>Action</b>	Refer to the error message for a list of possible values.
<b>INMCLI0006</b>	<b> Purger is unavailable for \${0}.</b>
<b>Explanation</b>	Purger is not available for the specified log unit.
<b>Action</b>	Check to make sure that the log units specified in the XML configuration file are valid. Else, contact the CentraSite administrator.
<b>INMCLI0007</b>	<b> Purging stopped for \${0} as there is no write permission for export location \${1}.</b>
<b>Explanation</b>	Purging stopped for the log unit, possibly because you do not have the explicit permission to write to the export location.
<b>Action</b>	Verify if the user has required permissions for purging to the export location.
<b>INMCLI0008</b>	<b> Insufficient disk space in \${0}. Required space \${1}. Available space \${2}.</b>
<b>Explanation</b>	The specified export location does not contain enough space for the exported logs. Refer to error message for the available space and required space.
<b>Action</b>	Choose a different export location.
<b>INMCLI0009</b>	<b> Purging Failed. Following error occurred \${0}.</b>
<b>Explanation</b>	Purging failed for the log unit due to a network connection timeout.
<b>Action</b>	Try again later or contact CentraSite administrator.
<b>INMCLI0010</b>	<b> Unable to archive export directory \${0}.</b>
<b>Explanation</b>	An unexpected exception occurred while trying to archive the exported logs. This is probably because the files may be accessed by another application.
<b>Action</b>	Close the application and retry the operation.
<b>INMCLI0011</b>	<b> Unable to create export directory \${0}.</b>
<b>Explanation</b>	An unexpected exception occurred while trying to create the export directory. This is probably because of the following reasons: 1) you do not have the explicit permission to write to the export location 2) export location is invalid.
<b>Action</b>	Check for the above possible reasons and execute again. If the problem persists, contact the CentraSite administrator.

<b>INMCLI0012</b>	<b>Command \${0} is invalid.</b>
<b>Explanation</b>	The specified command is not supported. For example, to purge logs you must specify -command purge_logs.
<b>Action</b>	Refer to CentraSite documentation for a list of the supported commands and their usage.
<b>INMCLI0016</b>	<b>Attribute {0} does not exist for specified path {1}.</b>
<b>Explanation</b>	The given attribute does not exist for the specified path.
<b>Action</b>	Verify that the attribute and path values are configured properly.
<b>INMCLI0121</b>	<b>Error: Invalid session.</b>
<b>Explanation</b>	CentraSite session has expired (or) already closed.
<b>Action</b>	Close your browser and log in again.
<b>INMCLI0156</b>	<b>Parameters for New Version action can only be set in "Show Params" state. Current state of action is {0}.</b>
<b>Explanation</b>	Parameters for versioning an asset can only be set in "Show Params" state. Current state of the action is {0}.
<b>Action</b>	Refer to the CSOAction related java document.
<b>INMCLI0181</b>	<b>Current search criteria is invalid.</b>
<b>Explanation</b>	The current search criteria is invalid. Validate the search criteria before you run.
<b>Action</b>	Check to make sure that the current search criteria is valid.
<b>INMCLI0239</b>	<b>No list available to perform {0}.</b>
<b>Explanation</b>	List is not available to perform {0}.
<b>Action</b>	Make sure that at least one of the selected items is added to the logged in user's list already.
<b>INMCLI0265</b>	<b>Failed to create the custom activity {0}.</b>
<b>Explanation</b>	The custom activity syntax in the configuration file was invalid.
<b>Action</b>	Check the activity syntax in the configuration file.

<b>INMCLI0334</b>	<b>This action cannot be added to the Message Flow more than {0} time(s).</b>
<b>Explanation</b>	You cannot include this action more than the allowed number of time(s) in the Message Flow.
<b>Action</b>	Do not include this action more than the allowed number of time(s) in the Message Flow.
<b>INMCLI0335</b>	<b>This action cannot co-exist with {0}.</b>
<b>Explanation</b>	This action cannot co-exist with the existing {0} in the Message Flow. This is possibly because, the two actions are mutually exclusive.
<b>Action</b>	Check to make sure that there are no mutually exclusive actions in the Message Flow.
<b>INMCLI0336</b>	<b>{0} of the dependent actions {1} should be configured in the Message Flow.</b>
<b>Explanation</b>	This action mandates that at least one of the dependent actions {1} be included in the Message Flow.
<b>Action</b>	Choose at least one of the dependent actions for {1}.
<b>INMCLI0337</b>	<b>This action cannot be added to the Message Flow more than once.</b>
<b>Explanation</b>	You cannot include this action more than once in the Message Flow.
<b>Action</b>	Do not include this action more than once in the Message Flow.
<b>INMCLI0338</b>	<b>This action is not applicable to the {0} Message Flow stage.</b>
<b>Explanation</b>	You cannot include this action in the {0} Message Flow stage.
<b>Action</b>	Ensure that you include the action in the applicable Message Flow stage.
<b>INMCLI0442</b>	<b>Provide a valid IP address range.</b>
<b>Explanation</b>	You cannot specify only one IP address for a type.
<b>Action</b>	Ensure you have provided both the From and To IP address values.
<b>INMCLW0032</b>	<b>Activity {0} is not applicable for given user.</b>
<b>Explanation</b>	Activity {0} is not applicable for the given user.
<b>Action</b>	Assign the activity to given user.

<b>INMCLW0047</b>	<b>Failed to synchronize configurator items with other configurators.</b>
<b>Explanation</b>	Could not synchronize or update the configurator item changes with other configurators.
<b>Action</b>	Reset the configurator items. If the problem persists, contact the CentraSite administrator.
<b>INMCLW0109</b>	<b>Failed to retrieve guest locale. Instead, returns the default locale {0}.</b>
<b>Explanation</b>	An unexpected exception occurred while trying to retrieve the locale for logged in user. The cause is not immediately known.
<b>Action</b>	If the problem persists, contact the CentraSite administrator.
<b>INMCLW0110</b>	<b>Exception occurred when closing connection.</b>
<b>Explanation</b>	An unexpected exception occurred when trying to close the underlying connection.
<b>Action</b>	Initialize before opening a connection.
<b>INMCLW0197</b>	<b>Duplicate search condition.</b>
<b>Explanation</b>	An attempt is made to specify a duplicate condition in the search recipe.
<b>Action</b>	Remove the duplicate condition from search recipe.
<b>INMCLW0227</b>	<b>Search name '{0}' already exists.</b>
<b>Explanation</b>	The same name is not allowed for two different searches. This error occurs when an attempt is made to save a search with a name that already exists.
<b>Action</b>	Enter a different search name.
<b>INMCLW0238</b>	<b>Enable at least one notification option in User Preferences.</b>
<b>Explanation</b>	At least one notification options in the User Preferences page should be selected to allow the current user to receive notifications through email and/or Inbox.
<b>Action</b>	Enable at least one notification option in the User Preferences page before subscribing to an asset.
<b>INMCLW0318</b>	<b>Action {0} is not applicable for the message flow step {1}.</b>
<b>Explanation</b>	The chosen action {0} is not applicable for the message flow step {1}.
<b>Action</b>	Choose a valid action for the message flow.

**INMCLW0456**      **The service published to API Gateway could not be activated in API Gateway.**  
**Explanation**      The service published to API Gateway could not be activated in API Gateway. Reason: {0}  
**Action**              Check for reasons and solve the problem in API Gateway.

**INMCL\_COMMON\_ATTR\_PENDING\_APPROVALS – Pending Approvals**

**INMCL\_COMMON\_ATTR\_PENDING\_APPROVALS\_DEC – Pending approvals for the asset**

**INMCL\_USECASE\_ASSETDEPENDENCY – Asset Dependency**

**Explanation**      Displays the list of assets which the selected asset is depending upon.

**INMCL\_USECASE\_ASSETUSAGE – Asset Usage**

**Explanation**      Displays the list of assets which make use of the selected asset.

**INMCL\_USECASE\_ASSET\_VERSIONING\_AND\_CONSUMERS – Asset Versioning And Consumers**

**Explanation**      Displays the different versions of the selected asset and the consumers for each of the versions.

**INMCL\_USECASE\_DEPLOYMENT – Deployment Overview**

**Explanation**      Displays the list of gateways to which the selected asset is deployed.

**INMCL\_USECASE\_ORG Organization Structure**

**Explanation**      Displays the list of organizations and their related objects.

**INMCL\_USECASE\_RUNTIMELANDSCAPEVIEW – Runtime Landscape View**

**Explanation**      Displays the list of gateways and the assets deployed to them.

**INMCL\_USER\_ATTR\_AVATAR\_URL\_DESC – The WebDAV URL of the Avatar for the User**

**INMCL\_USER\_ATTR\_AVATAR\_URL\_NAME – Avatar URL Location**

**INMCL\_USER\_ATTR\_EMAIL\_DESC – The email address for the user**

**INMCL\_USER\_ATTR\_EMAIL\_NAME – Email Address**

**INMCL\_USER\_ATTR\_FIRSTNAME\_DESC – The details of the user's first name**

**INMCL\_USER\_ATTR\_FIRSTNAME\_NAME – First Name**

**INMCL\_USER\_ATTR\_LASTNAME\_DESC – The details of the user's last name**

**INMCL\_USER\_ATTR\_LASTNAME\_NAME – Last Name**

**INMCL\_USER\_ATTR\_PHONE\_DESC – The user's telephone number details**

**INMCL\_USER\_ATTR\_PHONE\_NAME – Telephone Number**

**INMCSE0006      Select a taxonomy to delete**  
**Explanation**      Attempting to execute the delete action without selecting a taxonomy.  
**Action**              Select a taxonomy to be deleted.

**INMCSE0007      Select JPG, GIF or PNG image format**  
**Explanation**      Adding files other than JPG, GIF or PNG formats into a taxonomy or concept object.  
**Action**              Add only files with JPG, GIF or PNG formats into a taxonomy or concept object.

**INMCSE0008      The given URL is not a proper WebDAV URL.**  
**Explanation**      Wrong WebDAV URL or resource added into the taxonomy.  
**Action**              Enter a correct WebDAV URL or resource.

<b>INMCSE0011</b>	<b>Select at least one user</b>
<b>Explanation</b>	At least one user should be selected.
<b>Action</b>	Select at least one user.
<b>INMCSE0012</b>	<b>Select at least one permission</b>
<b>Explanation</b>	At least one permission should be selected.
<b>Action</b>	Select at least one permission.
<b>INMCSE0013</b>	<b>Select an organization to delete</b>
<b>Explanation</b>	An attempt was made to delete an organization without selecting an organization object.
<b>Action</b>	Select an organization object to delete.
<b>INMCSE0014</b>	<b>Select the property to delete</b>
<b>Explanation</b>	An attempt was made to delete a property without selecting a property.
<b>Action</b>	Select the property to delete.
<b>INMCSE0015</b>	<b>Select at least one administrator</b>
<b>Explanation</b>	At least one administrator should be selected.
<b>Action</b>	Select at least one administrator.
<b>INMCSE0018</b>	<b>Organization {0} already exists</b>
<b>Explanation</b>	The same name is not allowed for two different organizations. This error occurs when an attempt is made to create an organization with a name that already exists.
<b>Action</b>	Enter a different organization name.
<b>INMCSE0019</b>	<b>Select a user to delete</b>
<b>Explanation</b>	An attempt was made to delete a user without selecting the user object.
<b>Action</b>	Select the user object to delete.
<b>INMCSE0020</b>	<b>Enter a valid user</b>
<b>Explanation</b>	A valid user is required.
<b>Action</b>	Enter a valid user.

<b>INMCSE0033</b>	<b>Enter the mandatory fields</b>
<b>Explanation</b>	Some mandatory fields were not entered.
<b>Action</b>	Enter the mandatory fields.
<b>INMCSE0038</b>	<b>Enter a valid user</b>
<b>Explanation</b>	A valid user has not been entered.
<b>Action</b>	Enter a valid user.
<b>INMCSE0042</b>	<b>Select permission to remove</b>
<b>Explanation</b>	At least one permission should be selected.
<b>Action</b>	Select at least one permission.
<b>INMCSE0044</b>	<b>E-mail address is not valid</b>
<b>Explanation</b>	An invalid E-mail address has been specified.
<b>Action</b>	Enter a valid E-mail address.
<b>INMCSE0045</b>	<b>Check the length of the contact input</b>
<b>Explanation</b>	The length of the contact input exceeds the limit.
<b>Action</b>	Check the length of the contact input.
<b>INMCSE0046</b>	<b>Enter valid contact input</b>
<b>Explanation</b>	A wrong value was entered in the contact input.
<b>Action</b>	Enter valid contact input.
<b>INMCSE0047</b>	<b>First name should not be empty</b>
<b>Explanation</b>	An empty first name was entered.
<b>Action</b>	Enter a value for the first name.
<b>INMCSE0051</b>	<b>A request with status 'Pending' can't be deleted.</b>
<b>Explanation</b>	It is not possible to perform an unregister if a selected request has 'InProgress' as its status.
<b>Action</b>	Ensure that none of the selected requests has the status 'InProgress'.

<b>INMCSE0052</b>	<b>Enter valid IP values</b>
<b>Explanation</b>	Valid IP values are required.
<b>Action</b>	Enter valid IP values.
<b>INMCSE0062</b>	<b>{0} is the current logged in user</b>
<b>Explanation</b>	An attempt was made to delete the logged in user.
<b>Action</b>	Ensure that selected user is not the current logged in user.
<b>INMCSE0063</b>	<b>{0} is the primary contact of {1}</b>
<b>Explanation</b>	The logged in user tried to delete the primary contact of an organization.
<b>Action</b>	Ensure that the selected user-{0} is not the primary contact of an organization-{1}.
<b>INMCSE0064</b>	<b>{0} is the CentraSite Administrator</b>
<b>Explanation</b>	The logged in user tried to delete the user who is the CentraSite Administrator.
<b>Action</b>	Ensure that the selected user to delete is not the CentraSite Administrator.
<b>INMCSE0068</b>	<b>Group {0} already exists in this organization</b>
<b>Explanation</b>	An attempt was made to create a group with the same name as an existing group in the same organization.
<b>Action</b>	Use a new group name which is not already in use in the organization.
<b>INMCSE0074</b>	<b>At least one {0} should be present</b>
<b>Explanation</b>	When there is only one user with the role CentraSite Administrator or Organization Administrator, and if that user is deleted, this error will be thrown.
<b>Action</b>	There should be at least one CentraSite Administrator or Organization Administrator user. Make sure that another user with the same role is available in CentraSite.
<b>INMCSE0075</b>	<b>Database access error. Can't connect to server CentraSite.</b>
<b>Explanation</b>	The CentraSite Server is not running.
<b>Action</b>	Start the CentraSite Server.

<b>INMCSE0076</b>	<b>There are no results matching your search criteria</b>
<b>Explanation</b>	No results were found that match the search criteria.
<b>Action</b>	No action required.
<b>INMCSE0077</b>	<b>The WSDL file is unreachable. Make sure the input information is correct.</b>
<b>Explanation</b>	The URL for the given WSDL is wrong.
<b>Action</b>	Verify the URL given for this WSDL file.
<b>INMCSE0084</b>	<b>{0} has child organization(s) and cannot be deleted.</b>
<b>Explanation</b>	An organization cannot be deleted if there is at least one child organization associated to it.
<b>Action</b>	Make sure that the parent organization is not associated with any child organization, and then the parent organization can be deleted.
<b>INMCSE0085</b>	<b>Select an attribute to move</b>
<b>Explanation</b>	If a user tries to re-order the attribute without selecting anything, this error will be thrown. For this the user has to first select any attribute and then do the re-ordering.
<b>Action</b>	Select an attribute to move.
<b>INMCSE0086</b>	<b>Reordering multiple attributes is not allowed</b>
<b>Explanation</b>	While assigning attributes to the profile, a user can re-order the attributes. If the user tries to re-order multiple attributes simultaneously, this error will be thrown.
<b>Action</b>	Ensure that you do not select multiple attributes for reordering.
<b>INMCSE0087</b>	<b>HTTP Methods cannot be empty</b>
<b>Explanation</b>	HTTP methods for an XML / REST service cannot be empty during import.
<b>Action</b>	Please select any one of the HTTP methods for the XML / REST service.
<b>INMCSE0090</b>	<b>User {0} not found in external user store</b>
<b>Explanation</b>	The synchronization of users can be done only with users who belong to the current default external user store.
<b>Action</b>	Deselect the users who do not belong to the default external user store.

<b>INMCSE0091</b>	<b>Users not found in external user store</b>
<b>Explanation</b>	The sychronization of users can be done only with users who belong to the current default external user store.
<b>Action</b>	Deselect the users who do not belong to the default external user store.
<b>INMCSE0092</b>	<b>No endpoint defined</b>
<b>Explanation</b>	For the namespace to be defined, declare the endpoint of the service.
<b>Action</b>	Provide the endpoint information for the service before giving the namespace.
<b>INMCSE0093</b>	<b>Only CentraSite Administrator can change the ownership</b>
<b>Explanation</b>	Only a CentraSite Administrator can change the ownership or the organization.
<b>Action</b>	If you want to change the ownership or the organization, ensure that you are a CentraSite Administrator.
<b>INMCSI0071</b>	<b>It is not allowed to add multiple associations if Relationship attribute is not multi-value</b>
<b>Explanation</b>	For any single value relationship attribute, multiple value is not possible.
<b>Action</b>	Verify the given value for the single value relationship attribute.
<b>INMCSW0053</b>	<b>Define the primary contact</b>
<b>Explanation</b>	A primary contact is required when creating the organization.
<b>Action</b>	Define the primary contact.
<b>INMCSW0060</b>	<b>{0} cannot be deleted</b>
<b>Explanation</b>	You can only delete an organization if you have the necessary permissions.
<b>Action</b>	Ensure that you have the necessary permissions to delete an organization.
<b>INMCSW0061</b>	<b>Default organization cannot be deleted</b>
<b>Explanation</b>	The default organization cannot be deleted by any user.
<b>Action</b>	It is not possible to delete the default organization.

<b>INMEUE0001</b>	<b>A connection with the same name already exists.</b>
<b>Explanation</b>	A CentraSite connection name should be unique.
<b>Action</b>	Enter another connection name.
<b>INMEUE0002</b>	<b>Could not connect to host.</b>
<b>Explanation</b>	The specified host could not be connected. But the connection can be saved in the workspace.
<b>Action</b>	Enter a reachable host name.
<b>INMEUE0003</b>	<b>Could not resolve host address.</b>
<b>Explanation</b>	The specified host could not be reached. But the connection can be saved in the workspace.
<b>Action</b>	Enter a reachable host name.
<b>INMEUE0004</b>	<b>Log on failed. Make sure your user name and password are correct.</b>
<b>Explanation</b>	A logon failed due to invalid credentials.
<b>Action</b>	Make sure your user name and password are correct.
<b>INMEUE0005</b>	<b>Connection Name should not be empty</b>
<b>Explanation</b>	The required name for the connection is missing.
<b>Action</b>	Enter a name for the connection.
<b>INMEUE0006</b>	<b>An error has occurred. See error log for more details.</b>
<b>Explanation</b>	An internal error has been occurred. Refer to the log files for more details.
<b>Action</b>	Refer to the log files for more details.
<b>INMEUE0007</b>	<b>Cannot connect to server. Verify the specified connection information!\nMaybe the application server or the registry is currently not available.</b>
<b>Explanation</b>	Maybe the application server or the registry is currently not available.
<b>Action</b>	Check whether the application server and CentraSite are available and accessible.

<b>INMEUE0008</b>	<b>Cannot initialize predicate editors.</b>
<b>Explanation</b>	Due to non-compliance with the Eclipse UI, the UI rendering failed.
<b>Action</b>	Check your implementation and make sure it handles the predicate properly.
<b>INMEUE0009</b>	<b>No editor found for predicate class {0}</b>
<b>Explanation</b>	No editors are associated with the predicate.
<b>Action</b>	Check whether the implementation of IPredicateEditor is associated in your plugin description.
<b>INMEUE0010</b>	<b>Profile already exists</b>
<b>Explanation</b>	The specified profile already exists with the asset type.
<b>Action</b>	Create another profile if required.
<b>INMEUE0011</b>	<b>Attribute already exists</b>
<b>Explanation</b>	An attribute with the same name already exists.
<b>Action</b>	Enter another name for the attribute if required.
<b>INMEUE0012</b>	<b>You cannot modify this predicate. Delete it and create a new one instead.</b>
<b>Explanation</b>	Predefined profiles are not modifiable.
<b>Action</b>	Delete it and/or create a new one instead.
<b>INMEUE0013</b>	<b>Could not save. Correct the input errors first!</b>
<b>Explanation</b>	The input value is not compatible with the selected type.
<b>Action</b>	Enter an input value that is compatible with the selected type.
<b>INMEUE0014</b>	<b>The object cannot be deleted because it still has incoming associations.</b>
<b>Explanation</b>	An object with incoming/outgoing association cannot be deleted.
<b>Action</b>	If you want to delete this object, first delete the associations.
<b>INMEUE0015</b>	<b>{0} cannot be renamed as it is the target of one or more ExternalLink objects.</b>
<b>Explanation</b>	If this object is the target of any ExternalLink object, the name cannot be modified.
<b>Action</b>	No action required.

<b>INMEUE0016</b>	<b>{0} cannot be deleted as it is the target of one or more ExternalLink objects.</b>
<b>Explanation</b>	If this object is the target of any ExternalLink object, the object cannot be deleted.
<b>Action</b>	No action required.
<b>INMEUI0001</b>	<b>You do not have the required authority.</b>
<b>Explanation</b>	The permission required to do this operation has not been granted.
<b>Action</b>	Contact the CentraSite administrator to get sufficient permission to do this operation if required.
<b>INMFEE0011</b>	<b>Error occurred while trying to publish UDDI object(s) : {0}</b>
<b>Explanation</b>	While trying to publish UDDI object(s), if the program encounters any errors, it displays this message. {0} - The Disposition Report Fault Message exception.
<b>Action</b>	Ensure that the object in question is valid and any dependency required by the object is already federated to the target registry. For example, key generators specific to the source registry might not be recognized by the target.
<b>INMFEE0012</b>	<b>Cannot find the taxonomy object : {0}, {1}</b>
<b>Explanation</b>	The taxonomy processor is looking for the taxonomy object in the target registry and cannot find it. {0} - Object name {1} - Object key
<b>Action</b>	This error occurs very rarely. So make sure that a connection to the target registry can be obtained and re-execute the program.
<b>INMFEE0013</b>	<b>Concept publish failed</b>
<b>Explanation</b>	If you are using the taxonomy processor, then it will attempt to publish concepts and classification schemes to the target registry. If not all the concepts can be published, then this error occurs.
<b>Action</b>	Make sure that the concepts have valid values and try to re-execute the program.
<b>INMFEE0014</b>	<b>The TModel for the key {0} is not available in the federated data.</b>
<b>Explanation</b>	This message is displayed by the taxonomy processor. While trying to federate the data, if a particular TModel is identified as a taxonomy, then it looks for the TModel in the federated data. If the data is not available, then this error occurs. {0} - TModel key
<b>Action</b>	Provide the TModel name for federation in the configuration file and re-execute the program.

<b>INMFEE0018</b>	<b>The given default Business Entity name "{0}" is not available in the target registry.</b>
<b>Explanation</b>	In the configuration file, you will provide a default business entity name for the target, so that services can be associated with this business. If this business entity name does not have any businesses in the target registry, then this error occurs. {0} Business entity name.
<b>Action</b>	Provide the right business entity name after ensuring that it exists in the target registry.
<b>INMFEE0022</b>	<b>The {0} registry details are not configured properly</b>
<b>Explanation</b>	The federation takes the data specification from the provided configuration file. If the {0} registry details are not configured in the configuration file, you will get this error. {0} source / target.
<b>Action</b>	Make sure the {0} registry details are provided with the proper syntax in the configuration file. To get more details, please refer to the product documentation.
<b>INMFEE0023</b>	<b>The provided configFile is not configured properly.</b>
<b>Explanation</b>	The configuration file provided does not have the required elements eventTypeStoreLoc and nervAssetsLoc. These elements should be present in the configFile.
<b>Action</b>	Ensure that these two elements are provided in the configuration XML file. Also ensure that you provide a valid path.
<b>INMFEE0026</b>	<b>Cannot obtain OSGi instance for federation process.</b>
<b>Explanation</b>	The OSGi instance is required to emit events across the event bus for federation. It could be that the OSGi container initialization is aborted.
<b>Action</b>	Restart your default OSGi container. Wait until the OSGi container is initialized before you begin the federation process.
<b>INMFEI0001</b>	<b>No data available for federation. Terminating program execution.</b>
<b>Explanation</b>	The configuration file specifies the data that has to be inquired from the source registry. If the result of the inquiry does not have any data, then the federation cannot proceed and the program will terminate.
<b>Action</b>	Make sure that the configuration file specifies the correct data that is needed for federation.

<b>INMFEI0002</b>	<b>Results of inquiring the source registry :</b>
<b>Explanation</b>	CentraSite is currently inquiring the source registry and will display the results of the inquiry.
<b>Action</b>	No action required.
<b>INMFEI0003</b>	<b>Obtained number of {0} : {1}</b>
<b>Explanation</b>	This message displays the number of business objects obtained from inquiring the source registry {0} - Business(es) {1} - Number
<b>Action</b>	No action required.
<b>INMFEI0004</b>	<b>Timestamp based update will be performed</b>
<b>Explanation</b>	The federated objects will be compared with the modification timestamp and the update will be performed based on that.
<b>Action</b>	No action required.
<b>INMFEI0005</b>	<b>Timestamp based update will not be performed</b>
<b>Explanation</b>	The federated objects will be published, irrespective of whether the object to be published is the same or modified.
<b>Action</b>	No action required.
<b>INMFEI0006</b>	<b>Key generator processor : Modifying the keys to belong to the domain {0}</b>
<b>Explanation</b>	The UDDI keys of the federated objects will go through the key generator processor which will modify the UDDI keys such that they belong to the provided domain {DomainKey} {0} - Domain Key
<b>Action</b>	No action required.
<b>INMFEI0007</b>	<b>The federated data is received as the following event :</b>
<b>Explanation</b>	The Federation framework enables event emission. So the data is federated as events. This message informs that the emitted event is received for publishing to the target registry.
<b>Action</b>	No action required.

<b>INMFEI0008</b>	<b>Time taken for publishing the data : {0} seconds</b>
<b>Explanation</b>	The time taken for publishing the UDDI objects to the target registry is displayed by this message {0} - Time taken.
<b>Action</b>	No action required.
<b>INMFEI0009</b>	<b>The given UDDI object(s) were federated to this target registry.</b>
<b>Explanation</b>	The federation operation has completed and the required UDDI objects were published to this target registry.
<b>Action</b>	No action required.
<b>INMFEI0010</b>	<b>Trying to update/publish {0} : {1}, {2}</b>
<b>Explanation</b>	This message is displayed when an attempt is made to publish a UDDI object. The object can be identified by the object name and the UDDI key which will be displayed in the message. {0} Business / Service / TModel {1} Name of the UDDI object {2} UDDI key.
<b>Action</b>	No action required.
<b>INMFEI0015</b>	<b>Taxonomy processor : Categories (Concepts) and Taxonomies (Classification Schemes) were identified and published to the target registry</b>
<b>Explanation</b>	The taxonomies and categories were identified from the provided data and published to the target registry.
<b>Action</b>	No action required.
<b>INMFEI0016</b>	<b>No {0} were found with the provided UDDIv3 Inquiry API parameters</b>
<b>Explanation</b>	The UDDI object to be inquired should be specified in the configuration file for federation. It is provided as UDDI v3 Inquiry API calls, find_business, find_service, find_tModel. If no UDDI object could be inquired with the provided Inquiry API, then this message is displayed. {0} - Business(es) / Service(s) / TModel(s).
<b>Action</b>	Make sure that the Inquiry API adheres to the UDDI standards and that the inquiry parameters can inquire the data from the registry.
<b>INMFEI0017</b>	<b>UDDI registry configured for {0} with the following properties: user {1}, {2} Authentication.</b>
<b>Explanation</b>	This message is displayed if a connection could be established to the UDDI registry with the provided details. {0} - host {1} - user {2} - AuthToken, Basic
<b>Action</b>	No action required.

<b>INMFIEI0019</b>	<b>The above mentioned {0} is published to the target registry</b>
<b>Explanation</b>	The UDDI object identified by the given name and the UDDI key has been updated/published in the target registry. {0} Business / Service / TModel.
<b>Action</b>	No action required.
<b>INMFIEI0020</b>	<b>Not updating {0} : {1}, {2} in the target registry</b>
<b>Explanation</b>	While the program was performing timestamp based updates in the target registry, the UDDI object identified by the given name and the UDDI key was not updated/published in the target registry because it is already available in the target. {0} - Business, Service, TModel {1} - Name of the UDDI object {2} - UDDI key.
<b>Action</b>	No action required.
<b>INMFIEI0021</b>	<b>Number of {0} received for publishing : {1} , number published : {2}</b>
<b>Explanation</b>	This message displays the number of {0} that were published to the target registry. {0} - Business(es) / Service(s) / TModel(s) {1} - Number of objects received {2} - Number published.
<b>Action</b>	No action required.
<b>INMFIEI0024</b>	<b>The federated data has reached the target : {0}</b>
<b>Explanation</b>	There can be multiple targets configured for federation. This message displays the details of the target which has received the federated data through the federation ID {0}.
<b>Action</b>	No action required.
<b>INMFIEW0025</b>	<b>An error occurred while trying to close a resource - {0}</b>
<b>Explanation</b>	Occasionally an error might be encountered while trying to close open connections, streams, etc. This is just a warning that an error was encountered and can be ignored.
<b>Action</b>	Make sure that the resource in question is not opened and/or modified by another program/application.
<b>INMIEE0001</b>	<b>The call to the registry layer of CentraSite has failed.</b>
<b>Explanation</b>	During export and import, access to the registry layer of CentraSite is required. The call to the registry layer of CentraSite has failed.
<b>Action</b>	Please contact your software supplier.

<b>INMIEE0002</b>	<b>The archive file {0} could not be opened.</b>
<b>Explanation</b>	The archive file is used to store the registry objects for export and import. The access to this archive file has failed.
<b>Action</b>	Please make sure that the archive file name is correct and you have sufficient access rights to access this file.
<b>INMIEE0003</b>	<b>The archive file {0} could not be closed.</b>
<b>Explanation</b>	The archive file is used to store the registry objects for export and import. The closing of this archive file has failed.
<b>Action</b>	Please make sure that the archive file has not been removed meanwhile.
<b>INMIEE0005</b>	<b>The object with name {0}, type {1} and key {2} references another object in the context {3}. The referenced object has the key {4}, but it does not exist in the registry.</b>
<b>Explanation</b>	Referenced object cannot be resolved, neither from the import set nor by existing objects.
<b>Action</b>	Add the referenced object.
<b>INMIEE0006</b>	<b>The registry object cannot be imported, because it is older than the existing registry object.</b>
<b>Explanation</b>	The import of the registry object has been rejected, because the timestamp of the existing registry object is newer than the timestamp of the import registry object. You can set the replace option of the import operation to overwrite the existing registry object with an older import object.
<b>Action</b>	You can set the replace option of the import operation to overwrite the existing registry object with an older import object.
<b>INMIEE0007</b>	<b>The import object refers to the invalid object "{0}" and thus cannot be imported either.</b>
<b>Explanation</b>	The import object refers to the specified invalid object, and thus cannot be imported either.
<b>Action</b>	Check why the referenced object is invalid by analyzing its error message.
<b>INMIEE0013</b>	<b>The object cannot be imported because the embedded object {0} which is embedded in the existing object does not exist and is referenced by object {1}.</b>
<b>Explanation</b>	The existing object contains an embedded object which is not defined in the object to be imported. This embedded object is referenced by another object either directly or through one of its embedded objects.
<b>Action</b>	Please add the missing object and try importing the object.

<b>INMIEE0014</b>	<b>The external link with URI {0} could not be found.</b>
<b>Explanation</b>	Specified resource could not be found. It may have been previously deleted.
<b>Action</b>	No action required.
<b>INMIEE0016</b>	<b>The user has no read/write privilege to access/modify already existing registry objects</b>
<b>Explanation</b>	The user wants to access or write an object for which the user has no privileges.
<b>Action</b>	The action must be performed by a more privileged user.
<b>INMIEE0017</b>	<b>The user has no write privilege to modify existing registry objects</b>
<b>Explanation</b>	The user wants to modify an object for which the user has no modify privileges.
<b>Action</b>	The action must be performed by a more privileged user.
<b>INMIEE0018</b>	<b>The database with the URL {0} cannot be accessed.</b>
<b>Explanation</b>	A connection to the database cannot be established.
<b>Action</b>	Check whether the URL is correct.
<b>INMIEE0019</b>	<b>The connection to database {0} cannot be closed.</b>
<b>Explanation</b>	The database connection has been lost and cannot be closed.
<b>Action</b>	Please contact your software supplier.
<b>INMIEE0021</b>	<b>The registry object could not be deleted.</b>
<b>Explanation</b>	The registry object should have been deleted after the export, but the deletion has failed.
<b>Action</b>	Please contact your software supplier.
<b>INMIEE0022</b>	<b>The lifecycle stage URL of the registry object does not match the URL of the import registry, which is {0}</b>
<b>Explanation</b>	The registry object carries information about valid target registries. This information is called the lifecycle stages of the particular lifecycle state of this registry object. This registry object thus can only be imported into matching target registries.
<b>Action</b>	The registry object can be imported into matching target registries only.

<b>INMIEE0025</b>	<b>The import of a user registry object has failed, because a user with identical name and key {0} already exists.</b>
<b>Explanation</b>	The user registry object already exists.
<b>Action</b>	No action required.
<b>INMIEE0026</b>	<b>The import of a group registry object has failed, because a group with identical name and key {0} already exists.</b>
<b>Explanation</b>	The group registry object already exists.
<b>Action</b>	No action required.
<b>INMIEE0027</b>	<b>The import operation has failed, because the update of the security information has failed, object "{0}" ({1}).</b>
<b>Explanation</b>	The update of the security information has failed.
<b>Action</b>	Please contact your software supplier.
<b>INMIEE0028</b>	<b>The import archive does not have the expected compatibility level of {0}.</b>
<b>Explanation</b>	The import archive must contain a file named MANIFEST.TXT which contains the compatibility level of the import archive. The compatibility level of the import archive must be the same as the compatibility level of the CentraSite version used.
<b>Action</b>	Use the same CentraSite version for exporting and importing.
<b>INMIEE0030</b>	<b>The provided import organization key {0} does not exist in the registry.</b>
<b>Explanation</b>	The lookup of this key in the registry was not successful.
<b>Action</b>	Please provide a valid import organization key.
<b>INMIEE0031</b>	<b>The provided import organization key {0} does not refer to an organization.</b>
<b>Explanation</b>	The provided key exists in the registry, but the referred object is not an organization object.
<b>Action</b>	Please provide a valid import organization key.
<b>INMIEE0032</b>	<b>The setting of the import organization {0} has failed.</b>
<b>Explanation</b>	During import, the setting of the import organization has failed.
<b>Action</b>	Please contact your software supplier.

<b>INMIEE0034</b>	<b>The deletion of the repository resource {0} has failed.</b>
<b>Explanation</b>	The option delete after export has been set and the deletion of a repository resource has failed.
<b>Action</b>	Please contact your software supplier.
<b>INMIEE0035</b>	<b>The query to find all external links with the external URI {0} has failed.</b>
<b>Explanation</b>	The option delete after export has been set and the query to find all external links with the same URI has failed.
<b>Action</b>	Please contact your software supplier.
<b>INMIEE0036</b>	<b>The collection of the registry objects of the policy {0} has failed.</b>
<b>Explanation</b>	The delete after export option is active and the policy is to be deleted after export. The collection of the registry objects belonging to the policy has failed.
<b>Action</b>	Please contact your software supplier.
<b>INMIEE0040</b>	<b>The import of a role registry object has failed, because a role with identical name and key {0} already exists.</b>
<b>Explanation</b>	Role objects cannot be replaced.
<b>Action</b>	Re-establish the organization's roles.
<b>INMIEE0041</b>	<b>The import of a permission registry object has failed, because a permission with identical name and key {0} already exists.</b>
<b>Explanation</b>	Permission objects cannot be replaced.
<b>Action</b>	Re-establish the organization's permission.
<b>INMIEE0044</b>	<b>The user has no privilege to create/update an asset type ({0})</b>
<b>Explanation</b>	The user has not enough permission to create or update an asset type.
<b>Action</b>	Check the roles of the user.
<b>INMIEE0046</b>	<b>The import of the organization with key {0} has failed, because the organization has not been exported with the option to include users, groups, roles and permissions.</b>
<b>Explanation</b>	You can only import an organization together with its users, groups, roles and permissions. However, if the organization already exists, then it is possible to just import an organization without its users, groups, roles and permissions.
<b>Action</b>	Export the organization with the option to include users, groups, roles and permissions.

---

<b>INMIEE0048</b>	<b>Creating/updating of asset type "{0}" failed with internal error: {1}</b>
<b>Explanation</b>	An asset type cannot be imported or updated because of an internal registry problem.
<b>Action</b>	View the internal error reason and the stack trace in the log.
<b>INMIEE0049</b>	<b>Replacement of asset type "{0}" failed due to layout mismatch</b>
<b>Explanation</b>	The asset type cannot be replaced because the layout of the importing type is incompatible with the existing one.
<b>Action</b>	View the stack trace for the details.
<b>INMIEE0050</b>	<b>The asset type "{0}" references another object with key {1}, but it does not exist in the registry.</b>
<b>Explanation</b>	A reference from the asset type to be imported is not in the registry. This is usually a referenced asset type and must be present. Due to internal reasons the import cannot continue.
<b>Action</b>	Check that the referenced object (asset type) is present in the target registry.
<b>INMIEE0055</b>	<b>Asset to be imported does not fit to Asset type definition with attribute mismatch, attribute: {0}</b>
<b>Explanation</b>	The asset does not match the asset type. Possibly the asset has an attribute which is not defined for the given asset type.
<b>Action</b>	Check the asset type for missing attributes. Import the asset type which matches the asset.
<b>INMIEE0057</b>	<b>Selective import not supported with old export archives</b>
<b>Explanation</b>	No selective import is possible, only importing the whole archive is supported.
<b>Action</b>	Do not select particular keys.
<b>INMIEE0061</b>	<b>User {0} not found</b>
<b>Explanation</b>	The requested user name was not found in the registry.
<b>Action</b>	Use a valid user name.
<b>INMIEE0063</b>	<b>The document cannot be imported, because the associated asset type will be rejected</b>
<b>Explanation</b>	The schema file of an asset type cannot be imported because the asset type itself will be rejected for another reason.
<b>Action</b>	Analyze the existing asset type.

<b>INMIEE0064</b>	<b>Replacement of asset type {0} failed due to layout mismatch, reason: {1}</b>
<b>Explanation</b>	The given asset type cannot be replaced because it would change or remove used information, e.g. attributes.
<b>Action</b>	Check the attributes of the existing asset type. There are assets with attributes which would be removed by the import.
<b>INMIEE0066</b>	<b>The document cannot be imported, because its parent was rejected</b>
<b>Explanation</b>	The repository document will not be imported because its parent object (e.g. an ExternalLink object) was rejected.
<b>Action</b>	Check why the parent object was rejected.
<b>INMIEE0067</b>	<b>The object cannot be replaced, because it would lose its attribute {0}, which is referenced within registry by: {1}</b>
<b>Explanation</b>	The given object cannot be replaced, because the object that is already present has an attribute which would disappear as a result of the replacement. This attribute is referenced by others, therefore the attribute must be kept.
<b>Action</b>	Check the existing object and its references.
<b>INMIEE0068</b>	<b>No privilege to update object</b>
<b>Explanation</b>	The user has no privilege to update an object, present in the archive, to the registry. This could happen when updating asset types or taxonomies.
<b>Action</b>	Check if you can import the archive as a user with more privileges.
<b>INMIEE0072</b>	<b>Cannot update asset type because of version mismatch ("{0}" / "{1}")</b>
<b>Explanation</b>	The asset type to be imported has a lower version number than the one in the registry. The type is incompatible to the registry and therefore a replacement would destroy relevant information.
<b>Action</b>	The asset type from a previous version cannot be imported.
<b>INMIEE0074</b>	<b>Insufficient permissions to access CentraSite's webdav for user {0} at resource {1}.</b>
<b>Explanation</b>	The user {0} tries to access the CentraSite webdav resource without insufficient permissions.
<b>Action</b>	Make sure the user has insufficient permissions to access the CentraSite webdav resource.

<b>INMIEE0075</b>	<b>Invalid credentials for promotion user {0}.</b>
<b>Explanation</b>	The promotion user defined in the asset promotion policy does not have the sufficient permissions to access the target CentraSite.
<b>Action</b>	Make sure the user has insufficient permissions to access the target CentraSite.
<b>INMIEI0010</b>	<b>The registry object is not imported, because it has the same timestamp as the existing object.</b>
<b>Explanation</b>	The object to be imported already exists with the same timestamp.
<b>Action</b>	No action required.
<b>INMIEI0011</b>	<b>The imported registry object has replaced the existing object.</b>
<b>Explanation</b>	The registry object to be imported already exists and has been replaced.
<b>Action</b>	No action required.
<b>INMIEI0012</b>	<b>The imported registry object has been created.</b>
<b>Explanation</b>	The registry object to be imported has been created.
<b>Action</b>	No action required.
<b>INMIEI0020</b>	<b>The registry object with key {0} was deleted after it has been exported.</b>
<b>Explanation</b>	The option delete after export has been set and the registry object has been deleted after the export.
<b>Action</b>	Please contact your software supplier.
<b>INMIEI0023</b>	<b>The document cannot be imported, because it is older than the existing document.</b>
<b>Explanation</b>	The import of the document has been rejected, because the timestamp of the existing document is newer than the timestamp of the import document. You can set the replace option of the import operation to overwrite the existing document with an older import document.
<b>Action</b>	You can set the replace option of the import operation to overwrite the existing document with an older import document.
<b>INMIEI0024</b>	<b>The document was not imported, because it has the same timestamp as the existing document.</b>
<b>Explanation</b>	The import document and the existing document have the same timestamp. No import is necessary.
<b>Action</b>	No action required.

<b>INMIEI0033</b>	<b>The repository resource was deleted after it has been exported.</b>
<b>Explanation</b>	The option delete after export has been set and the registry object has been deleted after the export.
<b>Action</b>	No action required.
<b>INMIEI0039</b>	<b>Referenced object not in export set: {0} --&gt; {1}</b>
<b>Explanation</b>	The target object is not in the export set.
<b>Action</b>	Before importing, the referenced (target) objects must be present in the registry.
<b>INMIEI0065</b>	
<b>INMIEI0069</b>	<b>The document cannot be imported because it is already present</b>
<b>Explanation</b>	The document, which contains executable code, is not imported because it is already present.
<b>Action</b>	No action required.
<b>INMIEI0070</b>	<b>The registry object is not imported, because it is already present</b>
<b>Explanation</b>	The object cannot be replaced because the root object was not imported.
<b>Action</b>	No action required.
<b>INMIEW0008</b>	<b>Embedded objects cannot be exported.</b>
<b>Explanation</b>	Embedded objects like Classification, AuditableEvent, ExternalIdentifier, ServiceBinding, SpecificationLink and Association cannot be exported.
<b>Action</b>	Deselect object from list of objects to be exported.
<b>INMIEW0009</b>	<b>Export of selected object does not find any objects to be exported.</b>
<b>Explanation</b>	Export of selected object does not find any objects to be exported.
<b>Action</b>	Remove object from list of objects to be exported.
<b>INMIEW0029</b>	<b>The referenced registry object with key {0} is not part of the export archive.</b>
<b>Explanation</b>	A referenced object is not selected for export. Therefore there might be problems at import.
<b>Action</b>	Check your associated objects and decide whether to add them to the export.

<b>INMIEW0037</b>	<b>Delete of registry objects failed, reason: {0}</b>
<b>Explanation</b>	The deletion of one or more registry objects has failed during the export with delete option. The export archive however is complete.
<b>Action</b>	See the reason for the rejection within the message.
<b>INMIEW0038</b>	<b>The referenced registry object with key {0} is not part of the export archive. It is referenced from object: "{1}"</b>
<b>Explanation</b>	A referenced object is not selected for export. Therefore there might be problems later when you try to import the archive.
<b>Action</b>	Check your associated objects and decide whether to add them to the export.
<b>INMIEW0042</b>	<b>Delete after export of object "{0}" is not supported</b>
<b>Explanation</b>	It is currently not supported to delete specified object with the delete-after-export function.
<b>Action</b>	Delete the object manually.
<b>INMIEW0043</b>	<b>User "{0}" could not be deleted from organization</b>
<b>Explanation</b>	The user cannot be deleted from an organization after import because this user is already in use.
<b>Action</b>	Clean up the user manually with the imported organization.
<b>INMIEW0047</b>	<b>Object {0} modified due to unreferenced association</b>
<b>Explanation</b>	The association to an unreferenced target object was removed from the object.
<b>Action</b>	Check the object and repair it if necessary.
<b>INMIEW0051</b>	<b>Unprivileged reference to key: {0}</b>
<b>Explanation</b>	An exported object has a reference to an object that the user has no privilege to access. This means for import that the referenced object must be present and the importing user must have privileges to access this object.
<b>Action</b>	Keep this situation in mind for a later import.
<b>INMIEW0052</b>	<b>One ore more asset types may be corrupted, key: {0}</b>
<b>Explanation</b>	Due to resolving an access violation situation, it may happen that asset types may be corrupted.
<b>Action</b>	Import the archive as CentraSite Administrator.

<b>INMIEW0053</b>	<b>{0} association to object "{1}" removed</b>
<b>Explanation</b>	The association to the given object has been removed during import because the target object is not present.
<b>Action</b>	Re-establish the removed association if possible.
<b>INMIEW0054</b>	<b>Classification "{0}" removed because of unreferenced category</b>
<b>Explanation</b>	The classification has been removed from the object because its concept is not present in the registry.
<b>Action</b>	Re-establish the classification if possible.
<b>INMIEW0058</b>	<b>External link reference removed from object "{0}"</b>
<b>Explanation</b>	An external link reference which does not exist for the object has been removed.
<b>Action</b>	Check if the external link can be re-inserted manually.
<b>INMIEW0059</b>	<b>Lifecycle state removed because of missing model</b>
<b>Explanation</b>	The object has a lifecycle state at import, however the associated lifecycle model is not present in the target registry.
<b>Action</b>	Import the lifecycle model first.
<b>INMIEW0060</b>	<b>User object cannot be imported because of a missing name, key: {0}</b>
<b>Explanation</b>	The import processing detected an invalid user element and ignored the import.
<b>Action</b>	Verify the user entry in the archive.
<b>INMIEW0062</b>	<b>contains unprivileged reference</b>
<b>Explanation</b>	The object given contains a reference to an object which cannot be exported because the user has no privilege of that object. Only the reference gets exported. At import, this reference is checked and possibly removed from the object if the referenced object is not present.
<b>Action</b>	Check if a more privileged user should export the object.
<b>INMIEW0071</b>	<b>ServiceBinding "{0}" removed because of unreferenced specificationObject</b>
<b>Explanation</b>	A service binding points to a specification object, which is not present in the archive or registry. Therefore the service binding gets removed from the service.
<b>Action</b>	Check the service and its specification objects.

<b>INMIEW0073</b>	<b>Asset type is replaced with a lower version number.</b>
<b>Explanation</b>	An older version of the asset type has been replaced in the registry.
<b>Action</b>	Consider that some values are changed in the type, for example, attributes no longer there.
<b>INMIME0001</b>	<b>ObjectType {0} does not exist.</b>
<b>Explanation</b>	The required object type does not exist in CentraSite.
<b>Action</b>	Make sure the required object type is available in CentraSite and create an instance of it.
<b>INMIME0002</b>	<b>Asset {0} not found.</b>
<b>Explanation</b>	A required asset is not available in CentraSite.
<b>Action</b>	Create the required asset.
<b>INMIME0003</b>	<b>Error while executing JAXR operation.</b>
<b>Explanation</b>	An internal JAXR operation failed.
<b>Action</b>	Retry your request.
<b>INMIME0004</b>	<b>XPDL file {0} not found.</b>
<b>Explanation</b>	An XPDL file does not exist in the location specified.
<b>Action</b>	Make sure the given XPDL file is in the specified location.
<b>INMIME0005</b>	<b>Error while parsing the XPDL file.</b>
<b>Explanation</b>	The XPDL file does not match the XPDL format.
<b>Action</b>	Make sure the given XPDL format is valid.
<b>INMIME0006</b>	<b>Error while connecting to CentraSite.</b>
<b>Explanation</b>	It is not possible to establish a connection to the CentraSite database.
<b>Action</b>	Make sure the CentraSite database URL and CentraSite user credentials are valid.
<b>INMIME0007</b>	<b>Given XPDL File not supported.</b>
<b>Explanation</b>	The given XPDL file is not supported by CentraSite. CentraSite supports only XPDL 2.x.
<b>Action</b>	Make sure the given XPDL version is 2.x.

<b>INMIME0008</b>	<b>Specified process {0} is not available</b>
<b>Explanation</b>	There is no process with the specified asset ID
<b>Action</b>	Check the asset ID provided in the request
<b>INMIME0009</b>	<b>Required id is missing in Pool</b>
<b>Explanation</b>	While parsing the XPDL file, a pool element has been found but the attribute "id" is missing.
<b>Action</b>	Please make sure the specified XPDL file is valid.
<b>INMIME0010</b>	<b>From reference is missing in Transition</b>
<b>Explanation</b>	While parsing the XPDL, a transition element has been found but the "from reference" is missing in the transition element.
<b>Action</b>	Please make sure the "from reference" element contains a proper value.
<b>INMIME0011</b>	<b>To reference is missing in Transition</b>
<b>Explanation</b>	While parsing the XPDL, a transition element has been found but the "to reference" is missing in the transition element.
<b>Action</b>	Please make sure the "to reference" element contains a proper value.
<b>INMIME0012</b>	<b>Id is missing in Transition</b>
<b>Explanation</b>	While parsing the XPDL, a transition element has been found but the "id" is missing in the transition element.
<b>Action</b>	Please make sure "id" is present in the transition element and contains a proper value.
<b>INMIME0013</b>	<b>Id is missing in lane element</b>
<b>Explanation</b>	While parsing the XPDL, a lane element has been found but the "id" is missing in the transition element.
<b>Action</b>	Please make sure the "id" is present in the lane element and contains a proper value.
<b>INMIME0014</b>	<b>Id is missing in activity element</b>
<b>Explanation</b>	While parsing the XPDL, a lane element has been found but the "id" is missing in the activity element.
<b>Action</b>	Please make sure "id" is present in the activity element and contains a proper value.

<b>INMJRE0001</b>	<b>Database access error: {0}</b>
<b>Explanation</b>	An error occurred while accessing the database. The corresponding stack trace contains a "caused by" message with the reason of the failure.
<b>Action</b>	Please contact your software supplier if you can't analyze the reason of the database access error.
<b>INMJRE0002</b>	<b>Expected {0} objects</b>
<b>Explanation</b>	Certain operations that accept a collection of input objects (such as for example <code>LifeCycleManager.saveOrganizations()</code> ) expect certain object types ("Organization" in this example). The affected operation can be found in the stack trace.
<b>Action</b>	Correct the client program.
<b>INMJRE0003</b>	<b>Invalid property name "{0}"</b>
<b>Explanation</b>	The name of a property must be a valid NCName as in XML schema, e.g. it must not contain colon or whitespace.
<b>Action</b>	Correct the name.
<b>INMJRE0004</b>	<b>Invalid object in {0} parameter</b>
<b>Explanation</b>	Certain operations that accept a collection of input objects expect certain object types. The affected operation can be found in the stack trace.
<b>Action</b>	Correct the client program.
<b>INMJRE0005</b>	<b>Mutually exclusive find qualifiers: {0}, {1}</b>
<b>Explanation</b>	The listed find qualifiers are mutually exclusive with respect to the performed operation.
<b>Action</b>	Correct the client program.
<b>INMJRE0006</b>	<b>Found multiple matches</b>
<b>Explanation</b>	The performed query method is supposed to return zero or one result object, however the database contains multiple matches.
<b>Action</b>	Please contact your software supplier.

<b>INMJRE0007</b>	<b>The javax.xml.registry.queryManagerURL property is not set</b>
<b>Explanation</b>	Before creating a new Connection, the javax.xml.registry.queryManagerURL property has to be set to a non-null value.
<b>Action</b>	Correct the client program.
<b>INMJRE0008</b>	<b>The credentials parameter must not be null</b>
<b>Explanation</b>	The setCredentials() method was called with a null value for the credentials parameter.
<b>Action</b>	Correct the client program.
<b>INMJRE0009</b>	<b>Re-connect failed</b>
<b>Explanation</b>	An error occurred while recreating the database connection according to the given credentials. The stack trace contains a "caused by" message with the reason of the failure.
<b>Action</b>	Please contact your software supplier.
<b>INMJRE0010</b>	<b>Invalid credentials: expected PasswordAuthentication</b>
<b>Explanation</b>	The credentials have to be passed as an instance of java.net.PasswordAuthentication.
<b>Action</b>	Correct the client program.
<b>INMJRE0011</b>	<b>User name is not unique: {0}, only readonly access granted</b>
<b>Explanation</b>	For each user, there should be only one user object in the database. For the given user however, several objects with the same name were found. When the user tries to log in he is granted readonly access.
<b>Action</b>	Log in using a different user (probably an administrator) and delete or rename the duplicate user objects.
<b>INMJRE0012</b>	<b>The declarative query manager is not supported by this implementation</b>
<b>Explanation</b>	The declarative query manager is not supported by this implementation.
<b>Action</b>	See the documentation for the available query functionality.
<b>INMJRE0013</b>	<b>Invalid interface name parameter: {0}</b>
<b>Explanation</b>	The method LifecycleManager.createObject() was called with an illegal interface name.
<b>Action</b>	Correct the client program.

<b>INMJRE0014</b>	<b>Invalid XML response when saving documents</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INMJRE0015</b>	<b>The object to be undeprecated ({0}) is not in deprecated state</b>
<b>Explanation</b>	Only deprecated objects may be undeprecated.
<b>Action</b>	Select only deprecated objects for undeprecation.
<b>INMJRE0016</b>	<b>Illegal object type: {0}</b>
<b>Explanation</b>	A delete operation was called with an illegal object type.
<b>Action</b>	Correct the client program.
<b>INMJRE0017</b>	<b>Internal error: object with key "{0}" lost from cache</b>
<b>Explanation</b>	This internal error indicates an inconsistency in the object cache.
<b>Action</b>	Please contact your software supplier.
<b>INMJRE0018</b>	<b>Invalid null value in {0} parameter</b>
<b>Explanation</b>	The method QueryManager.getRegistryObjects() was called with a null value.
<b>Action</b>	Correct the client program.
<b>INMJRE0019</b>	<b>The object identified by the ConnectionFactory property {0}="{1}" is not a classification scheme</b>
<b>Explanation</b>	The default postal scheme was not specified correctly.
<b>Action</b>	Specify a correct default postal scheme.
<b>INMJRE0020</b>	<b>This implementation does not support makeRegistrySpecificRequest()</b>
<b>Explanation</b>	This implementation does not support makeRegistrySpecificRequest().
<b>Action</b>	See the documentation for the available query functionality.
<b>INMJRE0021</b>	<b>Invalid schema name "{0}", please consult the documentation for correct syntax</b>
<b>Explanation</b>	The schema name of a type must be a valid NCName as in XML schema, e.g. it must not contain colon or whitespace.
<b>Action</b>	Correct the name.

<b>INMJRE0022</b>	<b>An association cannot have itself as source object</b>
<b>Explanation</b>	An association cannot have itself as source object.
<b>Action</b>	Specify a correct association.
<b>INMJRE0023</b>	<b>An association cannot have itself as target object</b>
<b>Explanation</b>	An association cannot have itself as target object.
<b>Action</b>	Specify a correct association.
<b>INMJRE0024</b>	<b>Association type must not be null</b>
<b>Explanation</b>	When creating a new association the association type must not be null.
<b>Action</b>	Specify a correct association.
<b>INMJRE0025</b>	<b>The object to be deleted is not of type {0}</b>
<b>Explanation</b>	The delete operation specified that only objects of a particular type should be deleted, however at least one of the given keys points to a different object.
<b>Action</b>	Specify only keys of the requested type.
<b>INMJRE0026</b>	<b>An auditable event object cannot be deleted</b>
<b>Explanation</b>	It is not allowed to delete an auditable event.
<b>Action</b>	Correct the client program.
<b>INMJRE0027</b>	<b>Concept must have a classification scheme ancestor</b>
<b>Explanation</b>	The concept used for an internal classification has to belong to a classification scheme.
<b>Action</b>	Supply a correct concept for an internal classification.
<b>INMJRE0028</b>	<b>{0} parameter must not be null</b>
<b>Explanation</b>	The function shown on the call stack must not be called with a null value.
<b>Action</b>	Correct the client program.
<b>INMJRE0029</b>	<b>Concept must not have a parent</b>
<b>Explanation</b>	If a ClassificationScheme is created from a concept, then this concept must not have a parent.
<b>Action</b>	Supply a correct concept.

<b>INMJRE0030</b>	<b>Invalid value type: {0}</b>
<b>Explanation</b>	ClassificationScheme.setValueType() was called with an invalid value type.
<b>Action</b>	Supply a valid value type.
<b>INMJRE0031</b>	<b>The classification scheme to be deleted still has children</b>
<b>Explanation</b>	A classification scheme cannot be deleted if it has child concepts.
<b>Action</b>	Delete the child concepts before deleting the classification scheme.
<b>INMJRE0032</b>	<b>Parent not allowed for concept</b>
<b>Explanation</b>	The parent of a concept has to be a classification scheme or another concept.
<b>Action</b>	Supply a valid parent.
<b>INMJRE0034</b>	<b>The concept to be deleted still has children</b>
<b>Explanation</b>	A concept cannot be deleted if it has child concepts.
<b>Action</b>	Delete the child concepts before deleting the concept.
<b>INMJRE0035</b>	<b>Invalid value for {0} ({1})</b>
<b>Explanation</b>	An internal error occurred during the XML serialization of Java objects.
<b>Action</b>	Please contact your software supplier.
<b>INMJRE0036</b>	<b>Invalid string value for {0} ({1})</b>
<b>Explanation</b>	An internal error occurred while deserializing an XML document to a Java object.
<b>Action</b>	Please contact your software supplier.
<b>INMJRE0037</b>	<b>The external link to be deleted still has linked objects</b>
<b>Explanation</b>	An external link cannot be deleted if it has linked objects.
<b>Action</b>	Remove the external link from its linked objects before deleting it.
<b>INMJRE0039</b>	<b>Cannot add a non-KeyRef to a KeyRefList</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Please contact your software supplier.

**INMJRE0040      toArray failed with attached JAXRException while resolving an object reference**

**Explanation**      An exception occurred while copying a collection to an array. See the "caused by" message in the stack trace for the cause of the problem.

**Action**              Please contact your software supplier.

**INMJRE0041      RegistryObjectIterator failed with attached JAXRException while resolving an object reference**

**Explanation**      An exception occurred while iterating a query result. See the "caused by" message of the stack trace for the cause of the problem.

**Action**              Please contact your software supplier.

**INMJRE0042      Invalid locale**

**Explanation**      An internal error occurred while deserializing an XML document to a Java object.

**Action**              Please contact your software supplier.

**INMJRE0043      The organization to be deleted still has child organizations**

**Explanation**      An organization cannot be deleted if it has child organizations.

**Action**              Delete the child organizations before deleting the organization.

**INMJRE0044      The organization to be deleted still has services**

**Explanation**      An organization cannot be deleted if it has child services.

**Action**              Remove the services before deleting the organization.

**INMJRE0045      The organization to be deleted still has users**

**Explanation**      An organization cannot be deleted if it has users.

**Action**              Remove the users before deleting the organization.

**INMJRE0046      Invalid stability value: {0}**

**Explanation**      The setStability() method was called with an invalid stability value.

**Action**              Supply a valid stability value.

<b>INMJRE0047</b>	<b>This registry provider does not support client supplied keys</b>
<b>Explanation</b>	This registry provider does not support client supplied keys.
<b>Action</b>	Do not call the setKey() method.
<b>INMJRE0048</b>	<b>Internal error: duplicate key in object cache "{0}"</b>
<b>Explanation</b>	This internal error indicates an inconsistency in the object cache.
<b>Action</b>	Please contact your software supplier.
<b>INMJRE0049</b>	<b>Cannot modify object type classification</b>
<b>Explanation</b>	An instance of a user-defined type cannot be assigned another object type classification.
<b>Action</b>	Correct the client program.
<b>INMJRE0050</b>	<b>Duplicate object type classification</b>
<b>Explanation</b>	An instance of a user-defined type can only be classified with one concept from the "ObjectType" classification scheme.
<b>Action</b>	Correct the client program.
<b>INMJRE0051</b>	<b>Cannot remove object type classification</b>
<b>Explanation</b>	For instances of user-defined types it is not allowed to remove the classification that represents the object type.
<b>Action</b>	Correct the client program.
<b>INMJRE0052</b>	<b>This object ({0}) is deprecated and must not be referenced</b>
<b>Explanation</b>	A deprecated object must not be referenced in any way by another object.
<b>Action</b>	Do not create references to deprecated objects.
<b>INMJRE0053</b>	<b>An object to be deleted has not been previously saved</b>
<b>Explanation</b>	Only objects that have been previously saved can be deleted.
<b>Action</b>	Correct the client program.
<b>INMJRE0054</b>	<b>The "{0}" object to be deleted ({1}) is the target of the "{2}" association "{3}". The source of the association is the {4} object "{5}" with key "{6}".</b>
<b>Explanation</b>	An object cannot be deleted if it is still the target of an association.
<b>Action</b>	Delete the association before deleting the object.

<b>INMJRE0055</b>	<b>The registry package to be deleted still has members</b>
<b>Explanation</b>	A registry package cannot be deleted if it has member objects.
<b>Action</b>	Remove the member objects from the package before deleting it.
<b>INMJRE0056</b>	<b>Cannot modify the name of a slot after it was added to a registry object</b>
<b>Explanation</b>	The name of a slot cannot be changed after the slot was added to a registry object.
<b>Action</b>	Correct the client program.
<b>INMJRE0057</b>	<b>Invalid namespace "{0}" of type</b>
<b>Explanation</b>	The namespace of a type must be a valid URI.
<b>Action</b>	Correct the namespace.
<b>INMJRE0058</b>	<b>Invalid XML stream</b>
<b>Explanation</b>	An internal error occurred while deserializing an XML document to a Java object.
<b>Action</b>	Please contact your software supplier.
<b>INMJRE0059</b>	<b>XML parsing error</b>
<b>Explanation</b>	An internal error occurred while deserializing an XML document to a Java object.
<b>Action</b>	Please contact your software supplier.
<b>INMJRE0060</b>	<b>STAX configuration error</b>
<b>Explanation</b>	An internal error occurred while deserializing an XML document to a Java object.
<b>Action</b>	Please contact your software supplier.
<b>INMJRE0061</b>	<b>Invalid URL value</b>
<b>Explanation</b>	An internal error occurred while deserializing an XML document to a Java object.
<b>Action</b>	Please contact your software supplier.
<b>INMJRE0062</b>	<b>Invalid boolean value for attribute {0}</b>
<b>Explanation</b>	An internal error occurred while deserializing an XML document to a Java object.
<b>Action</b>	Please contact your software supplier.

<b>INMJRE0063</b>	<b>Incomplete object ({0} is missing or does not have a value)</b>
<b>Explanation</b>	The indicated required part of an object was missing when an object was to be saved.
<b>Action</b>	Correct the client program.
<b>INMJRE0064</b>	<b>Cannot add an existing association to another object</b>
<b>Explanation</b>	It is not possible to add the same association object to several separate registry objects.
<b>Action</b>	Create a new association object.
<b>INMJRE0065</b>	<b>Cannot add an existing classification to another object</b>
<b>Explanation</b>	It is not possible to add the same classification object to several separate registry objects.
<b>Action</b>	Create a new classification object.
<b>INMJRE0066</b>	<b>Cannot add an existing external identifier to another object</b>
<b>Explanation</b>	It is not possible to add the same external identifier object to several separate registry objects.
<b>Action</b>	Create a new external identifier object.
<b>INMJRE0067</b>	<b>Unexpected owner type</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INMJRE0068</b>	<b>Cannot delete the pre-defined object with key "{0}"</b>
<b>Explanation</b>	The CentraSite Registry/Repository database is installed with some pre-defined JAXR objects that are required for CentraSite operation. These objects must not be deleted.
<b>Action</b>	Do not delete pre-defined objects.
<b>INMJRE0069</b>	<b>Incomplete principal</b>
<b>Explanation</b>	A CentraSitePrincipal has to be either an href representing a user or a group, or an "all" indicator, or an "authenticated" indicator, or an "unauthenticated" indicator. None of these were set.
<b>Action</b>	Create a correct CentraSitePrincipal object.

<b>INMJRE0070</b>	<b>Cannot set instance based security for objects of type {0}</b>
<b>Explanation</b>	Instance based security cannot be set for the following object types: AuditableEvent, Association, Classification, ExternalIdentifier, ServiceBinding and SpecificationLink.
<b>Action</b>	Do not try to set instance based security for these object types.
<b>INMJRE0071</b>	<b>Failed with attached JAXRException</b>
<b>Explanation</b>	Comparison of two key references failed. See the "caused by" message in the stack trace for the cause of the failure.
<b>Action</b>	Please contact your software supplier.
<b>INMJRE0072</b>	<b>A ServiceBinding cannot have both a TargetBinding and an AccessURI</b>
<b>Explanation</b>	For a ServiceBinding object, TargetBinding and AccessURI are mutually exclusive.
<b>Action</b>	Choose either TargetBinding or AccessURI.
<b>INMJRE0073</b>	<b>Expected empty XML element {0}, but found content "{1}"</b>
<b>Explanation</b>	An internal error occurred while deserializing instance based security information to a Java object.
<b>Action</b>	Please contact your software supplier.
<b>INMJRE0074</b>	<b>Trying to use a closed connection (created by {0} at "{1}", closed at "{2}")</b>
<b>Explanation</b>	A previously closed connection must not be used any more.
<b>Action</b>	Open a new connection.
<b>INMJRE0075</b>	<b>A concept object must not have a HasParent association</b>
<b>Explanation</b>	In order to allow for a proper mapping between JAXR and UDDI, a concept object must not have a HasParent association.
<b>Action</b>	Do not create HasParent associations for concept objects.
<b>INMJRE0076</b>	<b>Internal error: object type concept not found</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Please contact your software supplier.

<b>INMJRE0077</b>	<b>The operation "{0}" can only be called for objects of type "{1}"</b>
<b>Explanation</b>	Each operation belongs to one object type, and it can only be executed on objects of that type.
<b>Action</b>	Call the operation only for objects of the correct type.
<b>INMJRE0078</b>	<b>Internal error: method should not be called</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Do not call this method.
<b>INMJRE0079</b>	<b>Invalid status value: {0}</b>
<b>Explanation</b>	An invalid status value was specified.
<b>Action</b>	See the JAXR javadoc for correct status values.
<b>INMJRE0080</b>	<b>The status of the deprecated object ({0}) cannot be modified</b>
<b>Explanation</b>	The status of a deprecated object cannot be modified.
<b>Action</b>	Undeprecate the object before modifying its status.
<b>INMJRE0082</b>	<b>A concept ({0}) in the ObjectType classification scheme is to be saved without an external link to an XML schema file</b>
<b>Explanation</b>	Concepts in the ObjectType classification scheme represent JAXR object types. These concepts have to have an external link to an XML schema file (XSD).
<b>Action</b>	Supply an XSD file for this concept.
<b>INMJRE0087</b>	<b>Invalid value "{0}" of property "{1}"</b>
<b>Explanation</b>	The given value does not match the declared datatype of the property.
<b>Action</b>	Correct the value.
<b>INMJRE0088</b>	<b>The concept to be deleted ({0}) is used by a classification ({1}). The classification belongs to the {2} object with key "{3}".</b>
<b>Explanation</b>	A concept must not be deleted if it is used by a classification.
<b>Action</b>	Remove the classification before deleting the concept.

<b>INMJRE0089</b>	<b>Trying to add a concept with the already existing value "{0}" under the parent object with key "{1}".</b>
<b>Explanation</b>	Concepts under the same parent object must have unique values.
<b>Action</b>	Choose a different value for the new concept.
<b>INMJRE0090</b>	<b>Invalid slot name: "{0}"</b>
<b>Explanation</b>	In the CentraSite JAXR implementation a JAXR slot name has to have the format {uri}localname, where the {uri} part is optional. The localname has to be a valid NCName according to the XML specification. Basically this means it may start with a letter or an '_' character, followed by letters, digits, or the characters '_', '.', '-'. In particular, the localname must not contain any whitespace characters.
<b>Action</b>	Supply a valid slot name.
<b>INMJRE0091</b>	<b>Invalid concept used as association type: "{0}"</b>
<b>Explanation</b>	Only concepts from the classification scheme "AssociationType" may be used as association types.
<b>Action</b>	Choose a valid concept.
<b>INMJRE0092</b>	<b>Commit or rollback not allowed if connection does not have client controlled transactions</b>
<b>Explanation</b>	Only JAXR connections that were created with com.centrasite.jaxr.ClientTransaction=yes support commit and rollback operations.
<b>Action</b>	Correct the JAXR client program.
<b>INMJRE0093</b>	<b>The value "{0}" of slot "{1}" is not a valid "{2}".</b>
<b>Explanation</b>	The given value does not conform to the datatype as specified in the type definition.
<b>Action</b>	Specify a valid value.
<b>INMJRE0094</b>	<b>Trying to modify the value of the ObjectType concept "{0}".</b>
<b>Explanation</b>	It is not allowed to modify the value of a concept in the classification scheme ObjectType.
<b>Action</b>	Correct the client program.

<b>INMJRE0095</b>	<b>Invalid concept value: {0}</b>
<b>Explanation</b>	As described in the JAXR standard, a concept value has to be a valid NCName.
<b>Action</b>	Provide a valid concept value.
<b>INMJRE0096</b>	<b>Trying to use an internal classification scheme ({0}) for an external classification.</b>
<b>Explanation</b>	An external classification requires an external classification scheme.
<b>Action</b>	Supply a correct classification scheme.
<b>INMJRE0097</b>	<b>Trying to save object "{0}" which is marked to be modified without lock.</b>
<b>Explanation</b>	Objects which are marked to be modified without lock cannot be saved.
<b>Action</b>	Correct the client program.
<b>INMJRE0098</b>	<b>Trying to modify an outdated object ("{0}")</b>
<b>Explanation</b>	The application tried to modify a registry object which has been modified by someone else in the meantime.
<b>Action</b>	Make sure to modify only the latest version of a registry object.
<b>INMJRE0099</b>	<b>Repository access error.</b>
<b>Explanation</b>	An error occurred accessing the repository.
<b>Action</b>	Ensure the repository is available. Check there are no resource issues (e.g. lack of disk space).
<b>INMJRE0100</b>	<b>Lock not available for object "{0}"</b>
<b>Explanation</b>	The requested lock could not be granted.
<b>Action</b>	Wait until the lock is available.
<b>INMJRE0103</b>	<b>Cannot handle a collection of values with a simple ParameterInstance</b>
<b>Explanation</b>	A simple non-array ParameterInstance is associated with a single value.
<b>Action</b>	Use a single value.
<b>INMJRE0104</b>	<b>ParameterType mismatch: requested {0}, present {1}</b>
<b>Explanation</b>	The value(s) of a ParameterInstance have to correspond to the type of the respective ParameterTemplate.
<b>Action</b>	Read / set values according to the ParameterType.

<b>INMJRE0105</b>	<b>The readonly property "{0}" must not be modified.</b>
<b>Explanation</b>	Readonly properties can only be added to new objects. Existing property values must not be changed.
<b>Action</b>	Do not modify readonly properties. Do not add readonly properties to existing objects.
<b>INMJRE0106</b>	<b>Login rejected, user "{0}" not registered</b>
<b>Explanation</b>	Each user has to be registered before being used for login.
<b>Action</b>	Register the user.
<b>INMJRE0107</b>	<b>The "login user" option must not be modified for existing users.</b>
<b>Explanation</b>	The "login user" option can only be assigned to new users.
<b>Action</b>	Do not modify an existing user's "login user" option.
<b>INMJRE0108</b>	<b>For an existing user with "login user" option, the name must not be changed.</b>
<b>Explanation</b>	A user with "login user" option has to keep his name.
<b>Action</b>	Do not modify the name of a user with "login user" option.
<b>INMJRE0109</b>	<b>Invalid URI specified for principal: {0}.</b>
<b>Explanation</b>	The URI specified for the principal is not valid. It must be an absolute URI or one with an absolute path. The scheme of "ino:" is not a valid scheme.
<b>Action</b>	Ensure that the URI is valid.
<b>INMJRE0110</b>	<b>"post insert" policy event failed for RegistryObject ("{0}")</b>
<b>Explanation</b>	The enclosed exception explains the reason of the failure.
<b>Action</b>	Analyze the enclosed exception.
<b>INMJRE0111</b>	<b>"post update" policy event failed for RegistryObject ("{0}")</b>
<b>Explanation</b>	The enclosed exception explains the reason of the failure.
<b>Action</b>	Analyze the enclosed exception.
<b>INMJRE0112</b>	<b>"post delete" policy event failed for RegistryObject ("{0}")</b>
<b>Explanation</b>	The enclosed exception explains the reason of the failure.
<b>Action</b>	Analyze the enclosed exception.

<b>INMJRE0113</b>	<b>Please set the mandatory parameter {0} before activating the policy</b>
<b>Explanation</b>	The policy activation verifies whether all mandatory parameters are set. 0 - Name of the mandatory parameter which was not set.
<b>Action</b>	Please set all the mandatory parameters before activating the policy
<b>INMJRE0114</b>	<b>Action {0} does not match the scope of the policy {1}</b>
<b>Explanation</b>	The selected action does not match the scope of the policy 0 - Name of the action 1 - Name of the policy.
<b>Action</b>	Please ensure that the selected action matches the scope of the policy.
<b>INMJRE0115</b>	<b>The name of the default organization must not be changed.</b>
<b>Explanation</b>	The name of the default organization must not be changed.
<b>Action</b>	None
<b>INMJRE0117</b>	<b>Name not specified for user with "login user" option</b>
<b>Explanation</b>	A user without a name cannot have the "login user" option.
<b>Action</b>	Specify a user name.
<b>INMJRE0119</b>	<b>Enumeration not allowed for data type {0}</b>
<b>Explanation</b>	Enumerations are not allowed for data types InternationalString and InternationalRichText.
<b>Action</b>	Do not specify the enumeration option for these data types.
<b>INMJRE0120</b>	<b>Internal error: missing ExternalLink to schema document</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INMJRE0121</b>	<b>Internal error: target of {0} external link does not exist.</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.

<b>INMJRE0122</b>	<b>Duplicate type name {0}</b>
<b>Explanation</b>	Each object type is identified by a name consisting of a namespace and a schema name. This name has to be unique.
<b>Action</b>	Provide a unique type name.
<b>INMJRE0123</b>	<b>Trying to remove the primary contact from organization {0} ({1}).</b>
<b>Explanation</b>	Each organization has to have a primary contact. It is not allowed to remove the primary contact.
<b>Action</b>	Do not remove the primary contact from an organization.
<b>INMJRE0124</b>	<b>Cannot delete an ObjectType concept ({0})</b>
<b>Explanation</b>	The taxonomy "ObjectType" contains concepts that represent object types. It is not allowed to delete these concepts.
<b>Action</b>	Do not delete ObjectType concepts.
<b>INMJRE0125</b>	<b>The user "{0}" ({1}) is the owner of, or modified the "{2}" object "{3}" ({4})</b>
<b>Explanation</b>	A user who still owns an object cannot be deleted. Also, if the user modified some object, and the corresponding audit trail entry is still present, deletion is rejected. However, the audit trail can be purged, and after all modification audit trail entries are purged, user deletion will be allowed.
<b>Action</b>	Delete all of the user's objects before deleting the user.
<b>INMJRE0126</b>	<b>Attempt to modify a readonly privilege</b>
<b>Explanation</b>	Readonly privileges must not be modified.
<b>Action</b>	Do not modify a readonly privilege.
<b>INMJRE0127</b>	<b>Unsupported data type '{0}'</b>
<b>Explanation</b>	The requested datatype is not supported.
<b>Action</b>	This is an internal error. Please contact your software supplier.
<b>INMJRE0128</b>	<b>Illegal usage of deny ACE</b>
<b>Explanation</b>	An ACE with deny can only be used with principal ALL and privilege ALL.
<b>Action</b>	Correct the ACE.

<b>INMJRE0129</b>	<b>Not a valid revision object</b>
<b>Explanation</b>	The object specified is not a object from the revision part.
<b>Action</b>	Check objects for the revision restore.
<b>INMJRE0130</b>	<b>Expected revision object not present</b>
<b>Explanation</b>	Unexpectedly a revision object could not be located. Obviously there is no version present of the actual object.
<b>Action</b>	Contact your software supplier because there is a structural problem with the revision part.
<b>INMJRE0131</b>	<b>Revision object must not be modified ("{0}")</b>
<b>Explanation</b>	Revision object must not be modified, these objects are readonly.
<b>Action</b>	Check your objects.
<b>INMJRE0132</b>	<b>Invalid revision object encountered ("{0}")</b>
<b>Explanation</b>	Invalid revision object encountered. The keys must be the same but are different.
<b>Action</b>	Check registry objects.
<b>INMJRE0133</b>	<b>The "{0}" to be deleted ({1}) is an intermediate version object</b>
<b>Explanation</b>	The object to be deleted is a target of a version association and must not be explicitly deleted.
<b>Action</b>	To delete objects of old versions use the purge() methods of the VersionManager interface.
<b>INMJRE0134</b>	<b>Login rejected, user "{0}" not active</b>
<b>Explanation</b>	Deactivated users cannot log in.
<b>Action</b>	Activate the user.
<b>INMJRE0135</b>	<b>Association type "{0}" already used in this asset type</b>
<b>Explanation</b>	There can be only one association of type "Implements" per asset type. You attempted to create such an attribute, but one exists already.
<b>Action</b>	Use a different association type.

<b>INMJRE0136</b>	<b>Uploaded computed profile zip does't contain computed implementation</b>
<b>Explanation</b>	the zip does not the class which implements the interfaces like {0}
<b>Action</b>	Make sure the computed profile implementation bundled in zip
<b>INMJRE0138</b>	<b>User "{0}" is still the primary contact of organization "{1}"</b>
<b>Explanation</b>	A user cannot be deleted if this user is still the primary contact of an organization.
<b>Action</b>	Do not delete primary contact users.
<b>INMJRE0139</b>	<b>Taxonomy "{0}" still used to classify object "{1}"</b>
<b>Explanation</b>	An external taxonomy cannot be deleted as long as it is referenced by classifications.
<b>Action</b>	Remove the classifications before deleting the taxonomy.
<b>INMJRE0140</b>	<b>The association type to be deleted ({0}) is used by an association ({1}). The association belongs to the {2} object "{3}".</b>
<b>Explanation</b>	An association type cannot be deleted if there are still associations of that type.
<b>Action</b>	Delete all associations of that type before deleting the association type.
<b>INMJRE0141</b>	<b>Untyped RegistryEntry "{0}" must not be saved</b>
<b>Explanation</b>	Java RegistryEntry objects are used to represent instances of user-defined types. In order to make a RegistryEntry an instance of a type, it has to be classified with the corresponding type concept.
<b>Action</b>	Save only typed RegistryEntries.
<b>INMJRE0142</b>	<b>must not replace existing type concept</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INMJRE0143</b>	<b>duplicate target type "{0}"</b>
<b>Explanation</b>	For a Relationship attribute the same target type was specified twice.
<b>Action</b>	Specify each target type only once.

---

<b>INMJRE0144</b>	<b>invalid maxOccurs value "{0}"</b>
<b>Explanation</b>	Allowed values for maxOccurs are "1" and "unbounded".
<b>Action</b>	Specify a valid value.
<b>INMJRE0145</b>	<b>invalid minOccurs value "{0}"</b>
<b>Explanation</b>	Allowed values for minOccurs are "0" and "1".
<b>Action</b>	Specify a valid value.
<b>INMJRE0146</b>	<b>Missing taxonomy for classification attribute "{0}"</b>
<b>Explanation</b>	Each classification attribute needs a taxonomy.
<b>Action</b>	Specify a taxonomy.
<b>INMJRE0147</b>	<b>For the classification attribute "{0}", the default value "{1}" does not belong to the taxonomy "{2}".</b>
<b>Explanation</b>	The default value needs to belong to the taxonomy.
<b>Action</b>	Select a concept from the taxonomy as the default value.
<b>INMJRE0148</b>	<b>Missing association type for relationship attribute "{0}"</b>
<b>Explanation</b>	Each relationship attribute needs an association type.
<b>Action</b>	Specify an association type.
<b>INMJRE0149</b>	<b>duplicate attribute name "{0}"</b>
<b>Explanation</b>	Attribute names have to be unique within classification, relationship, and file attributes.
<b>Action</b>	Choose a unique attribute name.
<b>INMJRE0150</b>	<b>trying to access a deleted type</b>
<b>Explanation</b>	After a type was deleted, the corresponding Java instance must no longer be used.
<b>Action</b>	Correct the client program.
<b>INMJRE0151</b>	<b>must not rename existing type's schema name</b>
<b>Explanation</b>	The schema name uniquely identifies a type, it must not be modified.
<b>Action</b>	Do not rename an existing schema name.

<b>INMJRE0152</b>	<b>Cannot save object due to missing lifecycle state. The object "{0}" is classified with lifecycle state "{1}" which does not exist.</b>
<b>Explanation</b>	A call to saveObjects fails, when a saved object contains a lifecycle state classification which does not exist. This can occur after importing objects, when the lifecycle model data has not been imported beforehand.
<b>Action</b>	Make sure that any referenced lifecycle models are available in the registry before importing objects that refer to them.
<b>INMJRE0153</b>	<b>Invalid attribute "{0}" applied to object of type "{1}"</b>
<b>Explanation</b>	A setAttributeValue() or getAttributeValue() operation was issued against a registry object whose type does not contain the specified attribute.
<b>Action</b>	Correct the application.
<b>INMJRE0154</b>	<b>Conflicting aggregation settings</b>
<b>Explanation</b>	A relationship attribute can be aggregating, or reversely aggregating, but not both.
<b>Action</b>	Choose a correct aggregation setting.
<b>INMJRE0155</b>	<b>"{0}" is not a virtual type</b>
<b>Explanation</b>	The given type concept is not a virtual type.
<b>Action</b>	Please supply a virtual type.
<b>INMJRE0156</b>	<b>The delete operation failed due to a hidden association.</b>
<b>Explanation</b>	The object to be deleted is still the target of an association. However, the user that tries to delete the object does not have view permissions on the association and its source object. Probably a CentraSite administrator with full permissions is required to perform the delete operation.
<b>Action</b>	Please contact your CentraSite administrator.
<b>INMJRE0158</b>	<b>The locale {0} is not contained in the set of restricted locales.</b>
<b>Explanation</b>	The set of restricted locales defines which locales may be used when creating a value for an InternationalString.
<b>Action</b>	Choose a different locale.

<b>INMJRE0159</b>	<b>Invalid or missing default locale</b>
<b>Explanation</b>	When defining the set of restricted locales, exactly one locale needs to be marked as the default locale.
<b>Action</b>	Specify a proper default locale.
<b>INMJRE0160</b>	<b>The "{0}" package to be deleted ({1}) still has members, e.g. the {2} object "{3}" with key "{4}".</b>
<b>Explanation</b>	A registry package cannot be deleted if it still has members.
<b>Action</b>	Delete the members before deleting the registry package.
<b>INMJRE0161</b>	<b>no value provided for required attribute {0} of {1} "{2}"</b>
<b>Explanation</b>	The attribute is defined with the "required" option, but the attribute value was not supplied when storing the object.
<b>Action</b>	Provide a value for the attribute.
<b>INMJRE0162</b>	<b>too many values provided for single-value attribute {0} of {1} "{2}"</b>
<b>Explanation</b>	For single-value attributes, at most one value may be provided.
<b>Action</b>	Provide a correct attribute value.
<b>INMJRE0163</b>	<b>Internal error: cannot construct a RegistryObject from {0}.</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Contact your software provider.
<b>INMJRE0164</b>	<b>Internal error: missing object id for {0}</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Contact your software provider.
<b>INMJRE0165</b>	<b>Cannot modify attribute {0} of type {1} to be required, because it does not exist in the object with key "{2}"</b>
<b>Explanation</b>	While updating a type description, an attribute was modified to be a required attribute. This modification however can only be done when the attribute is already present in all existing objects of the type (which is trivially true if there are no existing objects), or it has been equipped at the same time with a default value.
<b>Action</b>	Define a default value for the attribute, or refrain from setting the attribute to "required", then retry the modification only after the attribute has been added to all existing objects of the given type.

<b>INMJRE0166</b>	<b>Failed to check that the given profile is a computed profile</b>
<b>Explanation</b>	While parsing the uploaded zip file, an unexpected exception occurred.
<b>Action</b>	Please make sure the uploaded zip file is not corrupted.
<b>INMJRE0167</b>	<b>Uploaded computed profile implementation zip file does not contain profile implementation class, which implements the interface like {0}</b>
<b>Explanation</b>	The uploaded computed profile implementation zip file does not contain the class that implements the interface like {0}.
<b>Action</b>	Please make sure the zip file contains the computed profile implementation.
<b>INMJRE0168</b>	<b>Default value should be given for all required attributes when the types have instances. Please provide the default value for the required attribute "{0}".</b>
<b>Explanation</b>	When updating an asset type which already has instances, all the required attributes of that type should be provided with default values.
<b>Action</b>	Ensure that all the required attributes of the edited asset type have default values.
<b>INMJRE0169</b>	<b>The predefined attribute cannot be deleted</b>
<b>Explanation</b>	You cannot delete the predefined attributes.
<b>Action</b>	You cannot delete the predefined attribute.
<b>INMJUE0001</b>	<b>Check your access rights and the proxy settings</b>
<b>Explanation</b>	The accessing user does not have sufficient privileges for the target object.
<b>Action</b>	Do the action as a more privileged user.
<b>INMJUE0005</b>	<b>No privilege to access target object from object: {0}</b>
<b>Explanation</b>	The accessing user does not have sufficient privileges for the target object.
<b>Action</b>	Do the action with a more privileged user.
<b>INMJUE0006</b>	<b>Uploaded computed profile implementation zip doesn't contain profile implementation class, which implements the interface like {0}</b>
<b>Explanation</b>	The uploaded computed profile implementation zip file does not contain the class that implements the interface like the one shown.
<b>Action</b>	Make sure the zip file contains the computed profile implementation.

<b>INMJUE0007</b>	<b>Failed to check that a given profile is a computed profile</b>
<b>Explanation</b>	While parsing the uploaded zip file an unexpected exception occurred.
<b>Action</b>	Make sure that the uploaded zip file is not corrupted.
<b>INMJUW0002</b>	<b>The associated object of type "External Link" could not be deleted</b>
<b>Explanation</b>	This can happen while deleting virtual services.
<b>Action</b>	No action required.
<b>INMJUW0003</b>	<b>The associated object of type "WS-Policy attachment" could not be deleted</b>
<b>Explanation</b>	This can happen when deleting virtual services.
<b>Action</b>	No action required.
<b>INMJUW0004</b>	<b>The associated object of type "Associated with" could not be deleted</b>
<b>Explanation</b>	This can happen when deleting virtual services.
<b>Action</b>	No action required.
<b>INMLFE0001</b>	<b>Provider not set for {0}</b>
<b>Explanation</b>	The LCM factory could not be initialized since the property for the provider class is not set appropriately.
<b>Action</b>	Please check the javadoc of the LCM API to set the appropriate property.
<b>INMLFE0002</b>	<b>Provider {0} not found</b>
<b>Explanation</b>	The LCM provider class could not be loaded.
<b>Action</b>	Please check that the name of provider class is appropriately set and is available for class loading.
<b>INMLFE0003</b>	<b>Provider {0} could not be instantiated</b>
<b>Explanation</b>	An exception occurred while trying to load the provider class.
<b>Action</b>	Please check that the name of provider class is appropriately set and is available for class loading

<b>INMLFE0004</b>	<b>No initial state defined</b>
<b>Explanation</b>	There should be an initial state defined for any lifecycle model.
<b>Action</b>	Please make sure that there is an initial state defined for the lifecycle model.
<b>INMLFE0005</b>	<b>The state(s) {0} are unreachable</b>
<b>Explanation</b>	It should be possible to traverse to each state within a lifecycle model from the initial state 0 - name(s) of the state(s) unreachable from the initial state.
<b>Action</b>	Please make sure that each state is reachable from the initial state in the lifecycle model.
<b>INMLFE0006</b>	<b>A lifecycle model should have at least one end state</b>
<b>Explanation</b>	Any lifecycle model should have at least one state that does not have a next state.
<b>Action</b>	Please make sure that the lifecycle model has at least one end state.
<b>INMLFE0007</b>	<b>The given object type {0} cannot be LCM enabled</b>
<b>Explanation</b>	Only asset types, policies and lifecycle models can be LCM enabled 0 - name of the invalid object type
<b>Action</b>	Please make sure that an appropriate object type that can be LCM enabled is used.
<b>INMLFE0008</b>	<b>The state {0} cannot be set as an initial state. The state is currently not present in the lifecycle model.</b>
<b>Explanation</b>	Only states which are already part of the lifecycle model can be set as an initial state.
<b>Action</b>	Please make sure that you add the state to the lifecycle model before setting it as the initial state.
<b>INMLFE0009</b>	<b>The state {0} cannot be set as a preferred next state. The state is currently not a next state.</b>
<b>Explanation</b>	Only states which are part of the next states can be set as preferred next state 0 - name of the invalid preferred next state.
<b>Action</b>	Please ensure that the state is part of the next states before setting it as the preferred next state.

<b>INMLFE0010</b>	<b>Each lifecycle model should belong to an organization</b>
<b>Explanation</b>	Each LCM should belong to one organization.
<b>Action</b>	Please assign an organization to which the lifecycle model belongs.
<b>INMLFE0011</b>	<b>It is only possible to define a lifecycle model for lifecycle models in CentraSite Active SOA version</b>
<b>Explanation</b>	A lifecycle model for lifecycle models can only be defined in the CentraSite Active SOA edition.
<b>Action</b>	No action required.
<b>INMLFE0012</b>	<b>{0} is not a type in CentraSiteRegistryTypes taxonomy</b>
<b>Explanation</b>	The concept used for the registry type should belong to the predefined CentraSiteRegistryTypes taxonomy 0 - key of the invalid concept.
<b>Action</b>	Please use a concept that belongs to the predefined CentraSiteRegistryTypes taxonomy.
<b>INMLFE0014</b>	<b>A type with the given name {0} was not found</b>
<b>Explanation</b>	No object type was found with the given name 0 - name of the given object type.
<b>Action</b>	Please specify a valid type name.
<b>INMLFE0015</b>	<b>No active lifecycle model for the given registry object found</b>
<b>Explanation</b>	The given registry object is not associated with any active lifecycle model.
<b>Action</b>	No action required.
<b>INMLFE0016</b>	<b>The given state {0} is not a valid follow up state of {1} for the given registry object {2}</b>
<b>Explanation</b>	The current state of the registry object does not have a state transition to the specified target state. 0 - specified target state 1 - current state of the registry object 2 - name of the registry object.
<b>Action</b>	Please ensure that there is a valid state transition from the current state of the registry object to the specified target state.
<b>INMLFE0017</b>	<b>The given registry object is never in a work flow to change its state</b>
<b>Explanation</b>	The given registry object cannot be approved or rejected since it was never in a work flow to change its state.
<b>Action</b>	No action required.

<b>INMLFE0018</b>	<b>For each object type, only one lifecycle model can be active per organization</b>
<b>Explanation</b>	For any object type and organization, there can be at most one active LCM.
<b>Action</b>	Please make sure that there are no active LCMs associated with the given object type and organization, before trying to activate this LCM.
<b>INMLFE0019</b>	<b>A promotion node can be set only on the final states of the lifecycle model</b>
<b>Explanation</b>	Promotion nodes be only be set for final states of a lifecycle model.
<b>Action</b>	Please make sure that promotion nodes are set only for final states.
<b>INMLFE0020</b>	<b>The registry object is in a workflow to change its state</b>
<b>Explanation</b>	Next states cannot be determined for a registry object with a pending state change.
<b>Action</b>	No action required.
<b>INMLFE0021</b>	<b>The given registry object is not a user or a role or a group that could be used to restrict transitions to the state</b>
<b>Explanation</b>	The registry object used to restrict transitions to the state should be either a user or group or role. No other type of registry object can be used.
<b>Action</b>	Please make sure that the registry object used to restrict transitions to the state is either a user or a group or a role.
<b>INMLFE0022</b>	<b>The current user is not allowed to perform the state transition</b>
<b>Explanation</b>	The current user does not have the necessary permissions to perform the requested state transition.
<b>Action</b>	Please make sure that the current user has the necessary permissions to perform the requested state transition.
<b>INMLFE0024</b>	<b>Failed to set the initial state for the registry object {0}</b>
<b>Explanation</b>	The registry object could not be set to the initial state of the life cycle model since there is an approval work flow.
<b>Action</b>	Please make sure that there are no approval work flows triggered for the initial state of the LCM.

<b>INMLFE0026</b>	<b>The lifecycle model is deleted!</b>
<b>Explanation</b>	Deleted lifecycle models cannot be reused.
<b>Action</b>	Please use an existing lifecycle model and do not refer to deleted lifecycle models.
<b>INMLFE0027</b>	<b>The lifecycle model is not associated with any types</b>
<b>Explanation</b>	Each lifecycle model should be associated with at least one object type.
<b>Action</b>	Please choose at least one object type which will be associated with the lifecycle model.
<b>INMLFE0028</b>	<b>Internal error: User {0}/{1} does not belong to any organization</b>
<b>Explanation</b>	The logged in user does not belong to any organization 0 - Name of the user 1 - Key of the user.
<b>Action</b>	Please make sure that the logged in user belongs to some organization.
<b>INMLFE0029</b>	<b>Internal error: please specify the organization for which the lifecycle model has to be found</b>
<b>Explanation</b>	A lifecycle model can be found only in the context of an organization for which the registry object is to be created.
<b>Action</b>	Please specify the organization for which the lifecycle model has to be found.
<b>INMLFE0030</b>	<b>{0} lifecycle model cannot be modified</b>
<b>Explanation</b>	A lifecycle model which is active or in a state after active cannot be modified.
<b>Action</b>	Please ensure that the lifecycle model is in a state before active so that it can be modified.
<b>INMLFE0031</b>	<b>The lifecycle model cannot be deleted!</b>
<b>Explanation</b>	The lifecycle model could not be deleted because of an internal exception.
<b>Action</b>	Please look at the exception for more details.
<b>INMLFE0032</b>	<b>The model cannot be set to state {0}</b>
<b>Explanation</b>	The lifecycle model could not be set to the given state since it is not a valid transition from the current state of the model 0 - name of the invalid state.
<b>Action</b>	Please make sure that the model is set to a state that is a valid transition from its current state.

<b>INMLFE0033</b>	<b>Transition from any state to initial state is not allowed</b>
<b>Explanation</b>	Transition from any state to initial state is not allowed.
<b>Action</b>	Transition from any state to initial state is not allowed.
<b>INMLFE0034</b>	<b>The lifecycle model cannot be activated since the older version of this model could not be superseded</b>
<b>Explanation</b>	The lifecycle model which is a newer version of some other model could not be activated since the older version model could not be marked as superseded.
<b>Action</b>	Please ensure that the older version model can be marked as superseded before activating the newer lifecycle model.
<b>INMLFE0035</b>	<b>An active lifecycle model cannot be deleted</b>
<b>Explanation</b>	An attempt was made to delete an active lifecycle model.
<b>Action</b>	An active lifecycle model cannot be deleted.
<b>INMLFE0036</b>	<b>State transition can only be made between states which belong to the same lifecycle model</b>
<b>Explanation</b>	There are state transitions which have been made between states which belong to different lifecycle models.
<b>Action</b>	Please ensure that the state transitions are not made between states of two different lifecycle models.
<b>INMLFE0037</b>	<b>Lifecycle Model for Lifecycles cannot be deleted</b>
<b>Explanation</b>	The predefined lifecycle model for lifecycles cannot be deleted.
<b>Action</b>	No action required.
<b>INMLFE0038</b>	<b>Policy Lifecycle cannot be deleted</b>
<b>Explanation</b>	The predefined lifecycle model for policies cannot be deleted.
<b>Action</b>	No action required.
<b>INMLFE0041</b>	<b>Intermediate versions of a Lifecycle cannot be deleted using 'Delete' option</b>
<b>Explanation</b>	There are two options to delete a lifecycle and its version objects, namely 'Delete' and 'Purge'. The 'Delete' option can be used only for the latest version of the lifecycle.
<b>Action</b>	Deletion will not be allowed.

<b>INMLYE0002</b>	<b>Lifecycle Model Name should not be empty</b>
<b>Explanation</b>	The model name is mandatory.
<b>Action</b>	Enter the model name.
<b>INMLYE0003</b>	<b>Stage Name should not be empty</b>
<b>Explanation</b>	The stage name is mandatory.
<b>Action</b>	Enter the stage name.
<b>INMLYE0005</b>	<b>Only one row can be moved down</b>
<b>Explanation</b>	For the order of the lifecycle state, only one row can be moved up or down.
<b>Action</b>	While moving down any lifecycle state, please ensure that only one state is selected.
<b>INMLYE0007</b>	<b>Only one row can be moved up</b>
<b>Explanation</b>	To order the LC State, only one row can be moved up.
<b>Action</b>	Lifecycle state order.
<b>INMLYE0008</b>	<b>Lifecycle model(s) should be selected for saving report</b>
<b>Explanation</b>	Saving a report should have one LCM object.
<b>Action</b>	Saving a report should have one LCM object.
<b>INMLYE0009</b>	<b>Two state names cannot have the same name</b>
<b>Explanation</b>	There is a duplicate state name.
<b>Action</b>	Choose a unique state name.
<b>INMPPEE0003</b>	<b>Namespace {0} does not match any of the possible namespaces {1}</b>
<b>Explanation</b>	Service namespace is validated against the set of possible namespaces as specified by the policy. 0 - Namespace of the service 1 - Allowed namespaces from policy.
<b>Action</b>	Please ensure that the namespace of the service matches at least one of the allowed namespaces.
<b>INMPPEE0009</b>	<b>Policy {0} cannot be deactivated since an approval triggered by the policy for {1} {2} is in progress</b>
<b>Explanation</b>	Since there is an approval which is in progress, this policy cannot be deactivated. 0 - Name of the policy 1 - Type of the object which is pending 2 - Name of the object which is pending.
<b>Action</b>	Please complete the approval flow for the specific object and then deactivate the policy.

<b>INMP EE0013</b>	<b>Organization {0} should have Administrator</b>
<b>Explanation</b>	Every organization should have an administrator assigned 0 - Name of the organization
<b>Action</b>	Please ensure that the organization has an administrator assigned to it.
<b>INMP EE0016</b>	<b>{0} {1} must be classified by taxonomy {2}</b>
<b>Explanation</b>	The given registry object is validated to be classified by the given taxonomy. 0 - Type name of the object 1 - Registry Object name 2 - Taxonomy node name.
<b>Action</b>	Please ensure that the registry object is classified by the given taxonomy.
<b>INMP EE0021</b>	<b>Policy without any actions cannot be executed</b>
<b>Explanation</b>	A policy without any actions cannot be executed.
<b>Action</b>	Please assign some actions to this policy.
<b>INMP EE0030</b>	<b>Service WSDL size {0} does not conform with the specified size {1}</b>
<b>Explanation</b>	The service WSDL size does not match the size specified by the policy. 0 - WSDL size of the service 1 - WSDL size specified in the policy.
<b>Action</b>	Please ensure that the WSDL size of the service conforms with the specified size.
<b>INMP EE0031</b>	<b>{0} name {1} does not conform with the pattern {2}</b>
<b>Explanation</b>	The registry object name does not match the specified pattern. 0 - Type of the registry object 1 - Name of the registry object 2 - Name pattern specified in the policy.
<b>Action</b>	Please ensure that the name of registry object conforms to the specified pattern.
<b>INMP EE0039</b>	<b>Service Binding Type(s) {0} are missing in the WSDL. The mandatory bindings specified in the policy are {1}</b>
<b>Explanation</b>	The binding types of the service are validated against the specified bindings. 0 - Violating binding types of the service 1 - Binding types specified by the policy.
<b>Action</b>	Please ensure that the service binding types conform to the specified binding types.
<b>INMP EE0043</b>	<b>User does not have the permission to create {0}</b>
<b>Explanation</b>	The user does not have the required permission to create an object of the given type. {0} refers to the object type for which the user is creating an instance.
<b>Action</b>	Please assign the necessary permissions to the user before trying to create an object of the type.

<b>INMP0045</b>	<b>Namespace cannot be empty for {0} {1}</b>
<b>Explanation</b>	The namespace of the applied object is empty. {0} - type of the applied object {1} - name of the applied object.
<b>Action</b>	Please ensure that the namespace is provided for the object.
<b>INMP0046</b>	<b>Description is empty for {0} {1}</b>
<b>Explanation</b>	The description of the registry object is empty. 0 - Type of the registry object 1 - Name of the registry object.
<b>Action</b>	Please make sure that the registry object has a non-empty and valid description.
<b>INMP0047</b>	<b>Name is empty for {0}</b>
<b>Explanation</b>	The name of the registry object is empty 0. - Type of the registry object.
<b>Action</b>	Please make sure that the registry object has a non-empty and valid name.
<b>INMP0048</b>	<b>Policy {0} cannot be activated since there is a newer active version of this policy</b>
<b>Explanation</b>	Since there is a newer version of this policy which is active, the policy cannot be activated.
<b>Action</b>	Please use the newest active version of the policy for enforcement.
<b>INMP0049</b>	<b>Policy {0} cannot be activated since the older version of the policy could not be superseded</b>
<b>Explanation</b>	The policy which is a newer version of some other policy could not be activated since the older version could not be marked as superseded.
<b>Action</b>	Please ensure that the older version policy can be marked as superseded before activating the newer policy.
<b>INMP0052</b>	<b>{0} description {1} does not conform with the pattern {2}</b>
<b>Explanation</b>	The registry object description does not conform to the pattern specified in the policy. 0 - Type of the registry object 1 - Description of the registry object 2 - Description pattern specified in the policy.
<b>Action</b>	Please ensure that the description of the registry object conforms to the specified pattern.

<b>INMP EE0057</b>	<b>{0} {1} does not belong to an LCM state</b>
<b>Explanation</b>	The registry object does not belong to an LCM state. 0 - Type name of the object 1 - Name of the object.
<b>Action</b>	Please ensure that the registry object is set to an appropriate LCM state.
<b>INMP EE0059</b>	<b>{0} {1} belongs to state {2} which does not conform to the allowed states {3}</b>
<b>Explanation</b>	The LCM state of the registry object is validated against the allowed states specified in the policy. 0 - Type name of the registry object 1 - Name of the registry object 2 - Current state name of the registry object 3 - Allowed states specified in the policy.
<b>Action</b>	Please ensure that the registry object is set to an appropriate LCM state.
<b>INMP EE0064</b>	<b>{0} {1} does not have a value set for attribute {2}</b>
<b>Explanation</b>	The registry object does not have a value set of the specified attribute. 0 - Type of the registry object 1 - Name of the registry object 2 - Attribute name specified in the policy.
<b>Action</b>	Please ensure that the object has a value set for the specific attribute.
<b>INMP EE0066</b>	<b>{0} {1} has value {2} set for attribute {3} which does not conform to the allowed values {4}</b>
<b>Explanation</b>	The registry object has a value set of the specified attribute which does not conform to the allowed values. 0 - Type of the registry object 1 - Name of the registry object 2 - Attribute value of the registry object 3 - Attribute name specified in the policy 4 - Allowed attribute values specified in the policy.
<b>Action</b>	Please ensure that the object has an appropriate value set for the specific attribute.
<b>INMP EE0069</b>	<b>Policy {0} cannot be activated as some mandatory action parameters are not set</b>
<b>Explanation</b>	The policy has some mandatory parameters which are not set, so the policy cannot be activated. 0 - Name of the policy.
<b>Action</b>	Please ensure that all mandatory parameters of the policy are set before activation.
<b>INMP EE0071</b>	<b>Priority for a policy should be between {0} and {1}</b>
<b>Explanation</b>	The priority for a policy should be within the specified limits.
<b>Action</b>	Please enter a priority within the specified limits.

<b>INMP0072</b>	<b>Policy action rule {0} is invalid</b>
<b>Explanation</b>	The action.properties file is not accessible for this policy action rule. 0- name of the policy action.
<b>Action</b>	Please enter the correct rule file for the policy action.
<b>INMP0073</b>	<b>{0} is not a valid Groovy script</b>
<b>Explanation</b>	The action file is not a valid Groovy script. 0 – name of the Groovy script.
<b>Action</b>	Please upload a valid Groovy script.
<b>INMP0074</b>	<b>Result message not set for Groovy action {0}</b>
<b>Explanation</b>	The Groovy script did not set the result object. 0 – name of the Groovy action.
<b>Action</b>	Set the result inside the Groovy action.
<b>INMP0087</b>	<b>Active user {0} cannot be deleted.</b>
<b>Explanation</b>	Only deactivated users can be deleted in CentraSite. {0} specifies the user name.
<b>Action</b>	Deactivate the user before deletion.
<b>INMP0089</b>	<b>Organization level permission for {0} is not created yet for organization {1}</b>
<b>Explanation</b>	Firstly we have to create an organization before creating any registry object for an organization. This is because organization level permissions of that organization are used in instance level permission for those registry objects. 0 – name of the registry object 1 – name of the organization.
<b>Action</b>	Create the organization first.
<b>INMP0091</b>	<b>User cannot update the role {0} with permissions that he does not have</b>
<b>Explanation</b>	A user can assign permissions that he has to a role. If a user tries to update a role with a permission that he does not have, then this error will be thrown. 0 – name of the role.
<b>Action</b>	Please ensure that the user has the permissions that he is assigning to a role.
<b>INMP0092</b>	<b>{0} cannot be deleted</b>
<b>Explanation</b>	The default organization cannot be deleted.
<b>Action</b>	Do not try to delete the default organization.

<b>INMPEE0094</b>	<b>Policy {0} cannot be activated since an active older version of the policy has a pending approval</b>
<b>Explanation</b>	Since there is an older version of this policy which is active and has a pending approval, this newer policy version cannot be activated. 0 – name of the policy.
<b>Action</b>	Please ensure that any approval triggered by the older active version of this policy gets completed before activating the newer version.
<b>INMPEE0102</b>	<b>Organization Primary Contact has to be an active user</b>
<b>Explanation</b>	A deactivated user cannot become the primary contact of an organization.
<b>Action</b>	Please assign an active user as the primary contact of an organization.
<b>INMPEE0104</b>	<b>User cannot assign the role {0} to a user/group that he cannot manage</b>
<b>Explanation</b>	If a user with "Manage Users" permission in one organization tries to assign a role from another organization or a system level role to his own organization's user, then this error message will be thrown.
<b>Action</b>	The user needs to have the "Manage Users" permission of the role's organization (if it is an organization level role) or the user should have the "Manage System-wide Roles" permission if it is a system level role. Only then can the user assign that role to a user.
<b>INMPEE0105</b>	<b>User cannot create the Role {0} with permissions that the user does not have</b>
<b>Explanation</b>	A user can update the role only with the permissions that he possesses. If a user with Organization level "Manage Users" permission or "Manage System-wide Roles" permission tries to update a role then this user can assign only the permission that he/she already has, otherwise this error message will be thrown.
<b>Action</b>	Please ensure that the user has the permissions that he/she is assigning to a role.
<b>INMPEE0106</b>	<b>Action class {0} not found in {1}</b>
<b>Explanation</b>	The action class mentioned in the properties file should be present in the action rule archive. 0 – name of the executable class, 1 – name of the action rule archive.
<b>Action</b>	The action class mentioned in the properties file is not present in the action rule archive. Please make sure the class mentioned in the property file is present in the archive.

<b>INMP00110</b>	<b>WS-I actions should not be combined with other actions in a single policy</b>
<b>Explanation</b>	A policy containing WS-I actions cannot contain any actions other than WS-I policy actions
<b>Action</b>	Make sure WS-I actions are not combined with other actions in a single policy.
<b>INMP00111</b>	<b>Dependent actions {0} for {1} is not included</b>
<b>Explanation</b>	Dependent actions of a WS-I action are not included. 0 – name of the missing dependent WS-I action, 1 - name of the included WS-I action.
<b>Action</b>	Dependent actions of a WS-I action should be included in a policy.
<b>INMP00113</b>	<b>There are no lifecycle states associated with the {0} event for the policy {1} and hence this policy cannot be activated</b>
<b>Explanation</b>	The pre/post state change policy does not have any lifecycle states associated with it and hence the policy will not be executed for any state transition. Hence this policy cannot be activated. 0 - Pre/Post State Change event, 1 - Name of the policy.
<b>Action</b>	Please ensure that the policy is associated with the appropriate lifecycle states for the pre/post state change events
<b>INMP00114</b>	<b>Lifecycle state {0} from {1} does not match the scope of the policy {2}</b>
<b>Explanation</b>	The lifecycle state associated with the policy does not correspond to the object types specified in the scope of the policy. 0 - Name of the lifecycle state associated with this policy, 1 - Name of the lifecycle model to which this state belongs, 2 - Name of the policy.
<b>Action</b>	Please ensure that the lifecycle states associated to the policy belong to a lifecycle model whose object type conform to the object types specified in the policy scope
<b>INMP00115</b>	<b>Consumer Registration Request {0} is not associated with any asset</b>
<b>Explanation</b>	A consumer registration request object must be associated with an asset. 0 – Name of the consumer registration request.
<b>Action</b>	Associate the consumer registration request object with an asset using an association with the association type "relatedTo". The source object of the association is the consumer registration request. The target object of the association is the asset.
<b>INMP00118</b>	<b>{0} {1} is pending on state change. So it cannot be modified or deleted.</b>
<b>Explanation</b>	The object has a pending state change. So this object cannot be modified or deleted. 0 - Type of the object 1 - Name of the object.
<b>Action</b>	If you want to modify or delete the object, release the object from the pending state. If there are pending approvals, get them completed.

<b>INMP EE0120</b>	<b>Attribute {0} is read only and hence cannot be set for {1} {2}</b>
<b>Explanation</b>	Since the attribute is read only, the given attribute value cannot be set for the registry object. 0 - Name of the read only attribute, 1 - Type of the registry object, 2 - Name of the registry object.
<b>Action</b>	Please ensure that the chosen attribute is not a read only attribute.
<b>INMP EE0129</b>	<b>Initial State {0} cannot be used to define policy on Pre-State Change event</b>
<b>Explanation</b>	Pre-state change policies cannot be defined on initial states of any lifecycle model. 0 - Name of the initial state associated with the policy.
<b>Action</b>	Please use a lifecycle state other than the initial state to define the pre-state change policy.
<b>INMP EE0136</b>	<b>Policy action {0} is used, so it cannot be edited or deleted</b>
<b>Explanation</b>	If the policy action is used by any other policy, the policy action can't be edited or deleted.
<b>Action</b>	Before editing or deleting any policy action, the user has to verify whether any policy is using this action or not.
<b>INMP EE0142</b>	<b>{0} {1} has a pending approval and hence cannot be moved</b>
<b>Explanation</b>	The registry object has an approval in pending state. So it cannot be moved to a new owner and/or organization. 0 - Type of the registry object 1 - Name of the registry object.
<b>Action</b>	Please complete the pending approval for the registry object before moving it.
<b>INMP EE0143</b>	<b>{0} {1} has a pending consumer registration request and hence cannot be moved</b>
<b>Explanation</b>	The registry object has a pending consumer registration, so it cannot be moved to a new owner and/or organization. 0 - Type of the registry object 1 - Name of the registry object.
<b>Action</b>	Please complete the consumer registration request for the registry object before moving it.
<b>INMP EE0144</b>	<b>{0} {1} is an internal object of CentraSite and hence cannot be moved</b>
<b>Explanation</b>	Internal objects of CentraSite cannot be moved.
<b>Action</b>	Internal objects of CentraSite cannot be moved.

<b>INMP EE0145</b>	<b>{0} {1} cannot be moved to inactive or internal users of CentraSite</b>
<b>Explanation</b>	Ownership of the registry object cannot be transferred to inactive or internal users of CentraSite. 0 - Type of the registry object 1 - Name of the registry object.
<b>Action</b>	Please ensure that the new owner for the registry object is an active and non-internal user of CentraSite.
<b>INMP EE0146</b>	<b>The mandatory attribute {0} does not have value for this object</b>
<b>Explanation</b>	An attribute should have a value for a registry object if it is marked as required.
<b>Action</b>	Provide appropriate value(s).
<b>INMP EE0148</b>	<b>Only user with CentraSite Administrator role can do the change ownership action</b>
<b>Explanation</b>	Only a user with the CentraSite Administrator role can do the change ownership action.
<b>Action</b>	Please make sure that you log in as a user who has CentraSite Administrator role to perform the ownership change.
<b>INMP EE0149</b>	<b>Only user with CentraSite Administrator role can do the change organization action</b>
<b>Explanation</b>	Only a user with the CentraSite Administrator role can do the change organization action for assets.
<b>Action</b>	Please make sure that you log in as a user who has the CentraSite Administrator role to perform the organization change.
<b>INMP EE0150</b>	<b>Internal users cannot be moved across organizations.</b>
<b>Explanation</b>	If the user is trying to move any of the predefined or internal users from one organization to another organization, this error message will be displayed.
<b>Action</b>	Remove the predefined/internal users from the list for moving users across organizations.
<b>INMP EE0151</b>	<b>Owner for the object {0} of type {1} is not present in CentraSite</b>
<b>Explanation</b>	The owner for the object is not present in CentraSite. {0} - Name of the object {1} - Type of the object.
<b>Action</b>	The owner should not be allowed to be removed from CentraSite while owning some objects. So, identify how the owner was removed from CentraSite with this object dependency and report a bug.

<b>INMP EE0153</b>	<b>View permission on {0} {1} is not available for {2} {3}</b>
<b>Explanation</b>	The view permission on the registry object is not available for the specific user or group. 0 - Type of the registry object for which the profile permissions are being set 1 - Name of the registry object 2 - User or Group 3 - Name of the user or group.
<b>Action</b>	Please set the view permission on the registry object for the specific user or group before setting the profile permissions.
<b>INMP EE0154</b>	<b>Modify permission on {0} {1} is not available for {2} {3}</b>
<b>Explanation</b>	The modify permission on the registry object is not available for the specific user or group. 0 - Type of the registry object for which the profile permissions are being set 1 - Name of the registry object 2 - User or Group 3 - Name of the user or group.
<b>Action</b>	Please set the modify permission on the registry object for the specific user or group before setting the profile permissions.
<b>INMP EE0156</b>	<b>The new owner {0} does not have create asset permission in organization {1}</b>
<b>Explanation</b>	An attempt was made to move an asset to a user who does not have "create assets" permission in the asset's organization.
<b>Action</b>	Assign the Asset Provider role or any custom role which contains the "create assets" permission in the asset' organization to the target user.
<b>INMP EE0167</b>	<b>The RejectHandler policy prohibited the operation for {0} {1}</b>
<b>Explanation</b>	Operations like "move", "delete", etc. are only allowed for specific object types.
<b>Action</b>	Correct the application program.
<b>INMP EE0175</b>	<b>Virtual Service {0} cannot be deleted because it has been deployed to the target.</b>
<b>Explanation</b>	This error message is thrown when you are attempting to delete the virtual service which is deployed to a target.
<b>Action</b>	Undeploy the virtual service before attempting to delete.
<b>INMP EE0176</b>	<b>Target information not available for the deployment operation.</b>
<b>Explanation</b>	A target is mandatory for deployment operations of Virtual Service/Virtual XML service/Virtual REST service/Consumer Application/Aliases.
<b>Action</b>	Trigger deployment from the deployment profile.

<b>INMP EE0180</b>	<b>IS Service Interface {0} should have at least one associated IS Service Object, hence the corresponding REST service is not created.</b>
<b>Explanation</b>	The IS Service Interface object should have at least one associated IS Service Object.
<b>Action</b>	Make sure at least one IS Service Object (HTTP methods get, put, post and delete) is associated to the IS Service Interface and also make sure the name of the IS Service Object should contain the following strings (get, put, post and delete) appropriate to the method definition.
<b>INMP EE0181</b>	<b>REST Service {0} should have at least one native endpoint, hence the corresponding REST service is not created.</b>
<b>Explanation</b>	The REST service published from the webMethods product suite should have at least one native endpoint.
<b>Action</b>	Make sure the port attribute (IS Server object) has a value defined.
<b>INMP EE0184</b>	<b>Cannot remove the existing life cycle state from the object {0}</b>
<b>Explanation</b>	It is not possible to remove the existing life cycle state from the given object
<b>Action</b>	No action required.
<b>INMP EE0185</b>	<b>{0} {1} must be classified by at least one of {2}</b>
<b>Explanation</b>	The given registry object is validated to be classified by the given taxonomy or category. 0 - Type name of the object 1 - Registry Object name 2 - Taxonomy node name or category node name.
<b>Action</b>	Please ensure that the registry object is classified by the given taxonomy or category.
<b>INMP EE0190</b>	<b>Unable to delete the exported archive file</b>
<b>Explanation</b>	The intermediate archive file created for asset promotion could not be deleted.
<b>Action</b>	No action required.
<b>INMP EE0204</b>	<b>The mandatory attribute {0}, of {1} "{2}" does not have a value</b>
<b>Explanation</b>	The mandatory attribute {0} of {2} created from type {1} does not have a value. Attribute {0} has been marked "required" in the definition of type {2} and hence should have a value.
<b>Action</b>	Provide a value for the attribute {0} or provide a default value for the attribute in the definition of type {2}.

<b>INMP EE0206</b>	<b>The validation pattern "{0}" is invalid for policy "{1} at {2}". Repair the regular expression pattern.</b>
<b>Explanation</b>	The validation policy action of the specified policy contains an invalid/unsupported regular expression pattern.
<b>Action</b>	Specify a syntactically correct regular expression for the policy action.
<b>INMP EE0210</b>	<b>Key Generator Policy is not enabled for the API {0}</b>
<b>Explanation</b>	The Key Generator Policy for the given API is not generated.
<b>Action</b>	Contact the API provider.
<b>INMP EE0211</b>	<b>Onboarding Organization {0} with Administrator User {1} has failed</b>
<b>Explanation</b>	Onboarding the given organization with the given administrator user of that organization has failed.
<b>Action</b>	Contact the CentraSite administrator.
<b>INMP EE0212</b>	<b>Onboarding User {0} in Organization {1} has failed</b>
<b>Explanation</b>	Onboarding of the given user has failed in the given organization.
<b>Action</b>	Contact the organization administrator.
<b>INMP EE0218</b>	<b>API key revocation failed.</b>
<b>Explanation</b>	The specified API key could not be revoked. This problem can occur because the requestor does not have the required permission to revoke API key.
<b>Action</b>	Only a user with Administrator or Asset Provider role can revoke API keys.
<b>INMP EE0225Error</b>	<b>CentraSite cannot delete the alias because it is already deployed to the target. Alias: {0}</b>
<b>Explanation</b>	You are trying to delete an alias which is already deployed to a target.
<b>Action</b>	You must undeploy an alias before you delete it.
<b>INMP EE0226</b>	<b>The user {0} of the API Portal cannot be deleted.</b>
<b>Explanation</b>	You do not have sufficient access rights to delete the specified user {0} of API Portal, who has onboarded in the CentraSite registry. To delete the specified user, you must belong to the CentraSite Administrator role.
<b>Action</b>	Verify that you have the appropriate access rights. Contact your administrator and request access if necessary and then try again.

<b>INMP EE0227</b>	<b>Could not send key revocation notice to the user configured in the API consumption settings.</b>
<b>Explanation</b>	An email notification for the key revocation status could not be sent to the user configured in the API consumption settings, possibly because the user specified has been deleted from the CentraSite registry.
<b>Action</b>	Verify that the specified user exists in the CentraSite registry. If the user exists and the error persists, contact your administrator. If the user does not exist, remove the user from the API consumption settings.
<b>INMP EE0228</b>	<b>API Portal user {0} was off-boarded.</b>
<b>Explanation</b>	The API Portal user {0} has been off-boarded prior to the key generation/renewal operation.
<b>Action</b>	Onboard the API Portal user and try again.
<b>INMP EE0229</b>	<b>Key revocation policy must be enabled for the API.</b>
<b>Explanation</b>	The key revocation policy required for revoking an API's key has not been enabled for the API.
<b>Action</b>	Contact the API provider.
<b>INMP EE0230</b>	<b>Failed to delete the API {0}.</b>
<b>Explanation</b>	Could not delete the specified API {0} from CentraSite registry, possibly because the specified API is published to one or more API Portals.
<b>Action</b>	Make sure you unpublish the API from all of the API Portals, before trying to delete it.
<b>INMP EE0231</b>	<b>Failed to create object {0} in organization {1}.</b>
<b>Explanation</b>	Could not create the object {0} in the organization {1}, possibly because of insufficient permissions.
<b>Action</b>	Ensure that you have sufficient permissions to create the object in the selected organization.
<b>INMP EE0234</b>	<b>The asset {0} cannot be deleted, because it is consumed by one or more assets.</b>
<b>Explanation</b>	The asset {0} cannot be deleted, because it is consumed by one or more assets.
<b>Action</b>	Make sure you unconsume all consumers from the asset, before trying to delete it.

<b>INMP EE0236</b>	<b>The WSDL does not have any service element for {0}.</b>
<b>Explanation</b>	The WSDL cannot be validated if there are no service elements in it.
<b>Action</b>	If the service {0} is a Virtual type, the service element will be available only after it is deployed to a Mediator gateway.
<b>INMP EI0002</b>	<b>Namespace {0} matches one of the possible namespaces {1}</b>
<b>Explanation</b>	The service namespace validated against the set of possible namespaces as specified by the policy. 0 - Namespace of the service 1 - Allowed namespaces from policy.
<b>Action</b>	No action required.
<b>INMP EI0004</b>	<b>User {0} does not have the role specified in the policy</b>
<b>Explanation</b>	Since the user does not have the role specified in the policy, the role group policy is not applicable for the user 0 - Name of the user.
<b>Action</b>	No action required.
<b>INMP EI0005</b>	<b>Attribute {0} is not applicable for {1} {2}</b>
<b>Explanation</b>	The specified attribute is not applicable for the given object. 0 - Name of the attribute 1 - Type of the object 2 - Name of the object.
<b>Action</b>	No action required.
<b>INMP EI0006</b>	<b>Policy {0} was successfully validated for activation</b>
<b>Explanation</b>	The policy was successfully validated for activation. 0 - Name of the policy.
<b>Action</b>	No action required.
<b>INMP EI0007</b>	<b>LC Model {0} was successfully validated for activation</b>
<b>Explanation</b>	The lifecycle was successfully validated for activation. 0 - Name of the lifecycle model.
<b>Action</b>	No action required.
<b>INMP EI0008</b>	<b>Policy {0} was successfully validated for deactivation</b>
<b>Explanation</b>	The policy was successfully validated for deactivation. 0 - Name of the policy.
<b>Action</b>	No action required.

<b>INMPEI0010</b>	<b>Permissions assigned successfully for {0} {1}</b>
<b>Explanation</b>	Default permissions were assigned successfully for the given registry object. 0 - Type of the object 1 - Name of the object.
<b>Action</b>	No action required.
<b>INMPEI0012</b>	<b>User {0} was assigned to organization groups successfully</b>
<b>Explanation</b>	The user was assigned to organization groups successfully. 0 - Name of the user.
<b>Action</b>	No action required.
<b>INMPEI0014</b>	<b>Organization {0} has Administrator</b>
<b>Explanation</b>	The given organization has an administrator assigned to it. 0 - Name of the organization.
<b>Action</b>	No action required.
<b>INMPEI0015</b>	<b>{0} {1} is classified by taxonomy {2}</b>
<b>Explanation</b>	The given registry object is validated to be classified by the given taxonomy. 0 - Type name of the object 1 - Registry object name 2 - Taxonomy node name.
<b>Action</b>	No action required.
<b>INMPEI0017</b>	<b>Default Roles, Permissions and Groups created successfully for Organization {0}</b>
<b>Explanation</b>	Default roles, permissions and groups were created successfully for the given organization. 0 - Name of the organization.
<b>Action</b>	No action required.
<b>INMPEI0018</b>	<b>Default Roles, Permissions and Groups deleted successfully for Organization {0}</b>
<b>Explanation</b>	Default roles, permissions and groups were deleted successfully for the given organization. 0 - Name of the organization.
<b>Action</b>	No action required.
<b>INMPEI0019</b>	<b>Adding {0} privilege for {1} {2} on {3} {4}</b>
<b>Explanation</b>	The chosen privilege on the given registry object was successfully added for the particular user/group. 0 - View/Modify 1 - User/Group 2 - Name of the user/group 3 - Type of the registry object 4 - Name of the registry object.
<b>Action</b>	No action required.

<b>INMPEI0022</b>	<b>Default roles, groups, permissions and SDL for organization {0} created successfully</b>
<b>Explanation</b>	Default roles, groups, permissions and SDL were created successfully for the given organization. 0 - Name of the organization.
<b>Action</b>	No action required.
<b>INMPEI0023</b>	<b>Default roles, groups, permissions for organization {0} removed successfully</b>
<b>Explanation</b>	Default roles, permissions and groups were removed successfully for the given organization. 0 - Name of the organization.
<b>Action</b>	No action required.
<b>INMPEI0024</b>	<b>User creation policy for User {0} was successful</b>
<b>Explanation</b>	The user was successfully added to the default groups of the organization to which the user belongs. 0 - Name of the user.
<b>Action</b>	No action required.
<b>INMPEI0025</b>	<b>Request Approval Flow {0} for {1} created successfully</b>
<b>Explanation</b>	Request approval flow with the specified name was created successfully for the object. 0 - Approval Flow Name 1 - Name of the object for which approval is triggered.
<b>Action</b>	No action required.
<b>INMPEI0026</b>	<b>Default instance level permissions for Asset {0} were assigned successfully</b>
<b>Explanation</b>	Default instance level permissions were successfully assigned for the given asset. 0 - Name of the asset.
<b>Action</b>	No action required.
<b>INMPEI0027</b>	<b>Email with subject {0} successfully sent to {1}</b>
<b>Explanation</b>	An email with the given subject was successfully sent to the recipients. 0 - Subject of the sent email 1 - email address of the recipient(s).
<b>Action</b>	No action required.
<b>INMPEI0029</b>	<b>Service WSDL size {0} conforms with the specified size {1}</b>
<b>Explanation</b>	The service WSDL size validated against the size specified by the policy. 0 - WSDL size of the service 1 - WSDL size specified in the policy.
<b>Action</b>	No action required.

<b>INMPEI0032</b>	<b>{0} name {1} conforms with the pattern {2}</b>
<b>Explanation</b>	The registry object name matches the specified pattern. 0 - Type of the registry object 1 - Name of the registry object 2 - Name pattern specified in the policy.
<b>Action</b>	No action required.
<b>INMPEI0033</b>	<b>Default instance level permissions for Group {0} were assigned successfully</b>
<b>Explanation</b>	Default instance level permissions were successfully assigned for the given group. 0 - Name of the group.
<b>Action</b>	No action required.
<b>INMPEI0034</b>	<b>Default instance level permissions for Lifecycle Model {0} were assigned successfully</b>
<b>Explanation</b>	Default instance level permissions were successfully assigned for the given lifecycle model. 0 - Name of the lifecycle model.
<b>Action</b>	No action required.
<b>INMPEI0035</b>	<b>Default instance level permissions for Policy {0} were assigned successfully</b>
<b>Explanation</b>	Default instance level permissions were successfully assigned for the given policy. 0 - Name of the policy.
<b>Action</b>	No action required.
<b>INMPEI0036</b>	<b>Default instance level permissions for Report Template {0} were assigned successfully</b>
<b>Explanation</b>	Default instance level permissions were successfully assigned for the given report template. 0 - Name of the report template.
<b>Action</b>	No action required.
<b>INMPEI0037</b>	<b>Default instance level permissions for Role {0} were assigned successfully</b>
<b>Explanation</b>	Default instance level permissions were successfully assigned for the given role. 0 - Name of the role.
<b>Action</b>	No action required.
<b>INMPEI0038</b>	<b>Default instance level permissions for Taxonomy {0} were assigned successfully</b>
<b>Explanation</b>	Default instance level permissions were successfully assigned for the given taxonomy. 0 - Name of the taxonomy.
<b>Action</b>	No action required.

<b>INMPEI0040</b>	<b>Service Binding Type(s) conform with the specified bindings {0}</b>
<b>Explanation</b>	The binding types of the service validated against the specified bindings. 0 - Binding types specified by the policy.
<b>Action</b>	No action required.
<b>INMPEI0041</b>	<b>Default instance level permissions for User {0} were assigned successfully</b>
<b>Explanation</b>	Default instance level permissions were successfully assigned for the given user 0 - Name of the User
<b>Action</b>	No action required
<b>INMPEI0042</b>	<b>Default instance level permissions for Policy Action {0} were assigned successfully</b>
<b>Explanation</b>	Default instance level permissions were successfully assigned for the given policy action. 0 - Name of the policy action.
<b>Action</b>	No action required.
<b>INMPEI0050</b>	<b>{0} {1} successfully classified by specified taxonomies {2}</b>
<b>Explanation</b>	The given registry object has been classified with the specified taxonomy nodes. 0 - Type name of the registry object 1 - Name of the registry object 2 - Name(s) of the taxonomy nodes.
<b>Action</b>	No action required.
<b>INMPEI0051</b>	<b>{0} {1} successfully unclassified from specified taxonomies {2}</b>
<b>Explanation</b>	The given registry object has been unclassified from the specified taxonomies. 0 - Type name of the registry object 1 - Name of the registry object 2 - Name(s) of the taxonomies.
<b>Action</b>	No action required.
<b>INMPEI0053</b>	<b>{0} description {1} conforms with the pattern {2}</b>
<b>Explanation</b>	The registry object description validated with the specified pattern. 0 - Type of the registry object 1 - Description of the registry object 2 - Description pattern specified in the policy.
<b>Action</b>	No action required.

<b>INMPEI0054</b>	<b>{0} {1} was triggered to change to initial state {2}</b>
<b>Explanation</b>	The registry object has been triggered to change to initial state of the corresponding lifecycle model. 0 - Type name of the object 1 - Name of the registry object 2 - Name of the initial state of the corresponding lifecycle model.
<b>Action</b>	No action required.
<b>INMPEI0055</b>	<b>Object type of {0} - {1} is not LCM-enabled</b>
<b>Explanation</b>	The type of the registry object is not lifecycle-enabled. 0 - Name of the object 1 - Type name of the object.
<b>Action</b>	No action required.
<b>INMPEI0056</b>	<b>{0} {1} was triggered to change activation to {2}</b>
<b>Explanation</b>	The registry object has been triggered to change activation to Active/Inactive. 0 - Type name of the object 1 - Name of the object 2 - Change activation to Active/Inactive.
<b>Action</b>	No action required.
<b>INMPEI0058</b>	<b>{0} {1} belongs to state {2} which conforms to the allowed states {3}</b>
<b>Explanation</b>	The lifecycle state of the registry object is validated against the allowed states specified in the policy. 0 - Type name of the registry object 1 - Name of the registry object 2 - Current state name of the registry object 3 - Allowed states specified in the policy.
<b>Action</b>	No action required.
<b>INMPEI0060</b>	<b>State change to {0} is not applicable for {1} {2}</b>
<b>Explanation</b>	The state change to the specified state is not applicable for the given object. 0 - Change to state name specified in the policy 1 - Type of the registry object 2 - Name of the registry object.
<b>Action</b>	No action required.
<b>INMPEI0061</b>	<b>State change to {0} is initiated for {1} {2}</b>
<b>Explanation</b>	The state change to the specified state has been initiated for the given object. 0 - Change to state name specified in the policy 1 - Type of the registry object 2 - Name of the registry object.
<b>Action</b>	No action required.

<b>INMPEI0062</b>	<b>{0} {1} cannot be applied role groups policy</b>
<b>Explanation</b>	Role groups policy can be applied only to user objects. 0 - Type of the registry object 1 - Name of the registry object.
<b>Action</b>	No action required
<b>INMPEI0063</b>	<b>User {0} was added or removed from group {1}</b>
<b>Explanation</b>	The given user was added or removed from the specified group. 0 - Name of the user 1 - Name of the group where the user was added or removed.
<b>Action</b>	No action required.
<b>INMPEI0065</b>	<b>{0} {1} has value {2} set for attribute {3} which conforms to the allowed values {4}</b>
<b>Explanation</b>	For the specified attribute of the given registry object, a value has been set which conforms to the allowed values. 0 - Type of the registry object 1 - Name of the registry object 2 - Attribute value of the registry object 3 - Attribute name specified in the policy 4 - Allowed attribute values specified in the policy.
<b>Action</b>	No action required.
<b>INMPEI0067</b>	<b>Attribute {2} of {0} {1} was set to value {3}</b>
<b>Explanation</b>	The specified attribute of the registry object was set to the specified value. 0 - Type of the registry object 1 - Name of the registry object 2 - Attribute name specified in the policy 3 - Attribute value specified in the policy.
<b>Action</b>	No action required
<b>INMPEI0068</b>	<b>LC Model {0}'s enabled object type instances were initiated into initial state {1}</b>
<b>Explanation</b>	The instances of the object types which are LCM enabled by the given LC Model have been triggered to change to the initial state of the LC Model. 0 - Name of the LC Model 1 - Name of the initial state of the LC Model.
<b>Action</b>	No action required
<b>INMPEI0076</b>	<b>Default instance level permissions for Target {0} were assigned successfully</b>
<b>Explanation</b>	Default instance level permissions were successfully assigned for the given target. 0 - Name of the target
<b>Action</b>	No action required.

<b>INMPEI0077</b>	<b>Default instance level permissions for Lifecycle State {0} were assigned successfully</b>
<b>Explanation</b>	Default instance level permissions were successfully assigned for the given lifecycle state. 0 - Name of the lifecycle state.
<b>Action</b>	No action required.
<b>INMPEI0078</b>	<b>Default instance level permissions for Asset Type {0} were assigned successfully</b>
<b>Explanation</b>	Default instance level permissions were successfully assigned for the given asset type. 0 - Name of the asset type.
<b>Action</b>	No action required.
<b>INMPEI0079</b>	<b>Default instance level permissions for Taxonomy {0} were assigned successfully</b>
<b>Explanation</b>	Default instance level permissions were successfully assigned for the given taxonomy. 0 - Name of the taxonomy.
<b>Action</b>	No action required.
<b>INMPEI0080</b>	<b>Default instance level permissions for Event Type {0} were assigned successfully</b>
<b>Explanation</b>	Default instance level permissions were successfully assigned for the given event type. 0 - Name of the event type
<b>Action</b>	No action required.
<b>INMPEI0081</b>	<b>Default instance level permissions for Profile {0} were assigned successfully</b>
<b>Explanation</b>	Default instance level permissions were successfully assigned for the given profile. 0 - Name of the profile
<b>Action</b>	No action required.
<b>INMPEI0082</b>	<b>Default instance level permissions for UDDI Subscription {0} were assigned successfully</b>
<b>Explanation</b>	Default instance level permissions were successfully assigned for the given UDDI subscription. 0 - Name of the UDDI subscription
<b>Action</b>	No action required.
<b>INMPEI0083</b>	<b>Default instance level permissions for Federation {0} were assigned successfully</b>
<b>Explanation</b>	Default instance level permissions were successfully assigned for the given federation. 0 - Name of the federation.
<b>Action</b>	No action required.

<b>INMPEI0084</b>	<b>Default instance level permissions for Concept {0} were assigned successfully</b>
<b>Explanation</b>	Default instance level permissions were successfully assigned for the given concept. 0 - Name of the concept.
<b>Action</b>	No action required.
<b>INMPEI0085</b>	<b>Taxonomy {0} instance level permissions were assigned successfully to its child objects</b>
<b>Explanation</b>	The instance level permissions of the taxonomy were successfully assigned to its children concepts. 0 - Name of the taxonomy.
<b>Action</b>	No action required.
<b>INMPEI0086</b>	<b>Policy {0} instance level permissions were assigned successfully to its child objects</b>
<b>Explanation</b>	Policy has child objects like Policy Condition and Policy Parameter. When we assign the instance level permission to a Policy, the permission should be assigned also to its child objects. The message states that this action was performed successfully.
<b>Action</b>	No action required.
<b>INMPEI0088</b>	<b>User {0} is not active</b>
<b>Explanation</b>	The user is not active and hence can be deleted. 0 - Name of the user.
<b>Action</b>	No action required.
<b>INMPEI0095</b>	<b>Pending state transition was terminated by CSA</b>
<b>Explanation</b>	The CentraSite administrator has terminated the pending state transition on the registry object.
<b>Action</b>	No action required.
<b>INMPEI0103</b>	<b>Organization Primary Contact is an active user</b>
<b>Explanation</b>	The primary contact of the organization is an active user and hence the validation for updating the organization is successful.
<b>Action</b>	No action required.
<b>INMPEI0119</b>	<b>Default instance level permissions for ConsumerRegistrationRequest {0} were assigned successfully</b>
<b>Explanation</b>	Default instance level permissions for the consumer registration request were assigned successfully. 0 – Name of the consumer registration request.
<b>Action</b>	No action required.

<b>INMPEI0134</b>	<b>Default instance level permissions for ExternalLink {0} were assigned successfully</b>
<b>Explanation</b>	Default instance level permissions were successfully assigned for the given external link. 0 - Name of the external link.
<b>Action</b>	No action required.
<b>INMPEI0135</b>	<b>Default instance level permissions for ExtrinsicObject {0} were assigned successfully</b>
<b>Explanation</b>	Default instance level permissions were successfully assigned for the given extrinsic object. 0 - Name of the extrinsic object.
<b>Action</b>	No action required.
<b>INMPEI0137</b>	<b>Collector was successfully executed for {0} {1}</b>
<b>Explanation</b>	The collector policy was executed successfully for the given object. 0 - Type of the object 1 - Name of the object.
<b>Action</b>	No action required.
<b>INMPEI0138</b>	<b>Default delete handler was successfully executed for {0} {1}</b>
<b>Explanation</b>	The default delete handler policy was executed successfully for the given object. 0 - Type of the object 1 - Name of the object.
<b>Action</b>	No action required.
<b>INMPEI0140</b>	<b>WSDL regeneration skipped for Service {0} since the service is not a VirtualService, VirtualXMLService or VirtualRESTService</b>
<b>Explanation</b>	WSDL regeneration can be performed only for a virtual service, virtual XML service or virtual REST service.
<b>Action</b>	Make sure the asset is a virtual service, virtual XML service or virtual REST service.
<b>INMPEI0141</b>	<b>{0} {1} moved successfully</b>
<b>Explanation</b>	The registry object has been moved successfully to the new owner and/or organization. 0 - Type of the registry object 1 - Name of the registry object.
<b>Action</b>	No action required.
<b>INMPEI0147</b>	<b>Registry Object {0} has been validated successfully against its mandatory attributes of type Classification, File and Relationship</b>
<b>Explanation</b>	All the mandatory classification, file and relationship attributes for the given registry object have been populated. 0 - Name of the registry object.
<b>Action</b>	No action required.

<b>INMPEI0155</b>	<b>Profile permissions for {0} {1} were assigned successfully</b>
<b>Explanation</b>	The profile level permissions for the given registry object were successfully assigned.
<b>Action</b>	No action required.
<b>INMPEI0158</b>	<b>Organization export handler was successfully executed for {0}</b>
<b>Explanation</b>	The organization export handler was executed successfully for the given organization.
<b>Action</b>	No action required.
<b>INMPEI0159</b>	<b>Taxonomy/Concept export handler was successfully executed for {0} {1}</b>
<b>Explanation</b>	The Taxonomy/Concept export handler was executed successfully for the given object.
<b>Action</b>	No action required.
<b>INMPEI0160</b>	<b>Default export handler was successfully executed for {0} {1}</b>
<b>Explanation</b>	The default export handler policy was executed successfully for the given object. 0 - Type of the object 1 - Name of the object.
<b>Action</b>	No action required.
<b>INMPEI0161</b>	<b>Asset type export handler was successfully executed for {0} {1}</b>
<b>Explanation</b>	The asset type export handler policy was executed successfully for the given object. 0 - Type of the object 1 - Name of the object.
<b>Action</b>	No action required.
<b>INMPEI0164</b>	<b>Metrics does not contain serviceKey hence will not be saved in Runtime Metrics Collection</b>
<b>Explanation</b>	Metrics must be saved against a service. But the user is trying to save a metrics object without classifying it with a proper service key. This metrics will be discarded.
<b>Action</b>	Please classify the metrics objects with the classificationScheme "uddi:centrasite.com:management:service.key". The value of the classification must be the key of the service to which the metrics belongs.
<b>INMPEI0168</b>	<b>The required permissions are already available for {0} {1}</b>
<b>Explanation</b>	The permissions to be set by the policy are already available in the registry object. 0 - Type of the registry object 1 - Name of the registry object.
<b>Action</b>	No action required.

<b>INMPEI0169</b>	<b>Request Approval Flow {0} for {1} was automatically approved</b>
<b>Explanation</b>	The approval flow for the registry object was automatically approved since the triggering user is part of the approver group.
<b>Action</b>	No action required.
<b>INMPEI0170</b>	<b>CentraSite does not contain an object of type {0} and with name {1}</b>
<b>Explanation</b>	The policy executed successfully, since CentraSite does not contain an object of the specified type and with specified name.
<b>Action</b>	No action required.
<b>INMPEI0171</b>	<b>CentraSite already contains an object of type {0} and with name {1}</b>
<b>Explanation</b>	This policy enforces uniqueness in names of the object. As the user tried to create an object using a name which already exists in CentraSite, this policy failed.
<b>Action</b>	Please use a different name
<b>INMPEI0173</b>	<b>Notified Webservice endpoint {0} hosted in application server {1} successfully.</b>
<b>Explanation</b>	A Webservice request has been published to the endpoint successfully.
<b>Action</b>	No action required.
<b>INMPEI0174</b>	<b>Failed to notify Webservice endpoint {0} hosted in application server {1}: Error Message {2}</b>
<b>Explanation</b>	The Webservice request could not be published to the specified endpoint.
<b>Action</b>	Provide a valid webservice endpoint which can accept the SOAP message configured in the notify policy.
<b>INMPEI0177</b>	<b>{0} {1} has kept the current LCM state</b>
<b>Explanation</b>	The LCM state has been retained during the import.
<b>Action</b>	No action required.
<b>INMPEI0178</b>	<b>Successfully deleted the rest service of IS Service Interface '{0}'</b>
<b>Explanation</b>	Rest service deletion has completed successfully while retracting the IS Service Interface from the Designer.
<b>Action</b>	No action required.

<b>INMPEI0179</b>	<b>Failed to delete the rest service '{0}' ({1}) used by IS Service Interface '{2}'</b>
<b>Explanation</b>	The deletion of the Rest Service failed while retracting the IS Service Interface from the Designer.
<b>Action</b>	No action required.
<b>INMPEI0182</b>	<b>IS Service Interface {0} object has been transformed successfully into REST service {1}.</b>
<b>Explanation</b>	The IS Service Interface object has been transformed successfully into a REST service in CentraSite.
<b>Action</b>	No action required.
<b>INMPEI0183</b>	<b>The given object {0} does not contain the state</b>
<b>Explanation</b>	The given object 0 does not contain the state.
<b>Action</b>	No action required.
<b>INMPEI0186</b>	<b>Target Group not applicable for the operation</b>
<b>Explanation</b>	The target group is not applicable for the operation.
<b>Action</b>	No action required.
<b>INMPEI0187</b>	<b>Target Group created for the Target</b>
<b>Explanation</b>	The target group was created for the target.
<b>Action</b>	No action required.
<b>INMPEI0188</b>	<b>Target Group not created for the Target</b>
<b>Explanation</b>	The target group was not created for the target.
<b>Action</b>	No action required.
<b>INMPEI0189</b>	<b>{0} {1} promoted successfully</b>
<b>Explanation</b>	The registry object has been promoted successfully to the specified target stage. 0 - Type of the registry object 1 - Name of the registry object.
<b>Action</b>	No action required.

<b>INMPEI0191</b>	<b>Not updating Consumer WSDL for VirtualService {0} as it does not contain WSDL or Consumer WSDL is already contains the proper WSDL file.</b>
<b>Explanation</b>	The Consumer WSDL attribute will not get updated if the Virtual Service does not have WSDL associated with it. Also the attribute will get updated if it contains the proper value in it.
<b>Action</b>	No Action Required, as this policy get triggered when WSDL is attached to the Virtual Service
<b>INMPEI0193</b>	<b>Consumer WSDL attribute is populated with proper WSDL</b>
<b>Explanation</b>	Policy Action successfully executed by populated the Consumer WSDL attribute with proper WSDL
<b>Action</b>	No action required
<b>INMPEI0194</b>	<b>Not updating Consumer WSDL for {0} since it is not a Service</b>
<b>Explanation</b>	Consumer WSDL attribute is applicable only for Virtual Service and hence it can't be updated for other objects
<b>Action</b>	Please make sure applicable object for "Consumer WSDL Generator" policy is set only to Virtual Service
<b>INMPEI0201</b>	,
<b>Explanation</b>	This is a user display name separator.
<b>Action</b>	No action required.
<b>INMPEI0202</b>	{0} {1} {2}
<b>Explanation</b>	This is a user display name.
<b>Action</b>	No action required.
<b>INMPEI0203</b>	<b>Ownership of {0} {1} was changed successfully to user {2}</b>
<b>Explanation</b>	The ownership of the given asset was changed successfully to the specified user. 0 - Type of the object; 1 - Name of the object; 2 - New owner of the object.
<b>Action</b>	No action required.

<b>INMPEI0205</b>	<b>{0} of type {1} has been validated for all mandatory Slot, Classification, File and Relationship attribute types.</b>
<b>Explanation</b>	The "required" attributes of the registry object {0} of type {1} have been identified and all such "required" attributes have been provided with values.
<b>Action</b>	No action required.
<b>INMPEI0207</b>	<b>The API Key is deployed successfully to target {0}</b>
<b>Explanation</b>	The specified API key was successfully deployed to the specified target.
<b>Action</b>	No action required.
<b>INMPEI0208</b>	<b>A new API Key is generated.</b>
<b>Explanation</b>	A new API key has been generated.
<b>Action</b>	No action required.
<b>INMPEI0209</b>	<b>Onboarded user {0} proceeds with consume API request for {1}</b>
<b>Explanation</b>	The onboarding of the user was successful, and the consume API request for the API has been triggered.
<b>Action</b>	User registration completion information will be sent as an email.
<b>INMPEI0213</b>	<b>Onboarding User {0} in Organization {1} is successful</b>
<b>Explanation</b>	Onboarding of the user in API Management solution was successful.
<b>Action</b>	The Consume API request will be generated automatically for the onboarded user.
<b>INMPEI0214</b>	<b>Onboarding Organization {0} with Administrator User {1} is successful</b>
<b>Explanation</b>	Onboarding of the given Organization with the given User in API Management solution was successful.
<b>Action</b>	The Consume API request will be generated automatically for the the onboarded administrator user.
<b>INMPEI0215</b>	<b>Congratulations from API management team</b>
<b>Explanation</b>	Email subject for successful onboarding of user.
<b>Action</b>	No action.

<b>INMPEI0216</b>	<b>API key deleted successfully from target {0}.</b>
<b>Explanation</b>	The API key is deleted successfully from the target {0}.
<b>Action</b>	None. Informational only.
<b>INMPEI0220</b>	<b>WSDL regeneration skipped for virtual service {0} as WSDL related objects are not modified.</b>
<b>Explanation</b>	WSDL regeneration is needed only if JAXR binding is updated, else WSDL update not required. CentraSite updates it only if it really required.
<b>Action</b>	No action required.
<b>INMPEI0221</b>	<b>API key has been renewed successfully.</b>
<b>Explanation</b>	API key has been renewed successfully.
<b>Action</b>	No action required
<b>INMPEI0232</b>	<b>OAuth2 Client is revoked successfully.</b>
<b>Explanation</b>	The OAuth2 Client was revoked successfully.
<b>Action</b>	No action required.
<b>INMPEI0235</b>	<b>Swagger2.0 file is generated successfully for the API {0}.</b>
<b>INMPEW0028</b>	<b>WSDL URL is empty for {0}</b>
<b>Explanation</b>	The service WSDL URL is empty. 0 - Name of the service.
<b>Action</b>	Please ensure that the service has a WSDL URL.
<b>INMPEW0172</b>	<b>Could not send notification to application server as it is not configured with APG_SERVICE_ENDPOINT</b>
<b>Explanation</b>	The notification will be send only if the application server is configured with APG_SERVICE_ENDPOINT in the object specific property.
<b>Action</b>	Configure a valid webservice endpoint to the application server which is associated to the registry object.

<b>INMPEW0192</b>	<b>Consumer WSDL attribute is not found Virtual Service type</b>
<b>Explanation</b>	This policy action will update the Consumer WSDL attribute with WSDL which may contain WS Policy in it. So this policy action requires Consumer WSDL attribute
<b>Action</b>	Please make sure Consumer WSDL file attribute exists for Service type
<b>INMPEW0217</b>	<b>Failed to delete API key from target {0} .</b>
<b>Explanation</b>	The specified API key could not be deleted from the target {0}. This problem can occur because the requestor does not have the required permisison to delete API key.
<b>Action</b>	Only a user with Administrator role can delete API key from targets.
<b>INMPEW0219</b>	<b>You can revoke an access token only once.</b>
<b>Explanation</b>	The access token is revoked twice.
<b>Action</b>	Revoke an access token only once.
<b>INMPEW0233</b>	<b>Failed to revoke OAuth2 Client from Mediator.</b>
<b>Explanation</b>	Could not revoke the OAuth2 Client from the specified Mediator. There could be multiple reasons why this might have occurred: (1) Integration Server on which Mediator is running is down or inaccessible (2) invalid user credentials (3) application error on the Integration Server.
<b>Action</b>	Make sure the Integration Server on which Mediator is up and running, and the user credentials are correct.
<b>INMPUE0003</b>	<b>Action category and action template types are mismatched</b>
<b>Explanation</b>	For a design time/ change time category, the action template type should be programmatic. If the action template type does not match the design time/ change time category, this causes an error.
<b>Action</b>	Ensure that the action category and action template types are matched.
<b>INMPUE0006</b>	<b>Action template name already exists</b>
<b>Explanation</b>	An action template name should be unique across the system, otherwise this will create confusion for the user. So this error occurs if a user tries to create an action template with a name that is already in use.
<b>Action</b>	Use a different action template name.

<b>INMPUE0015</b>	<b>WS-I actions cannot be combined with other actions</b>
<b>Explanation</b>	While creating a policy, WS-I actions should not be combined with other actions. If a user tries to do so, this problem will happen.
<b>Action</b>	WS-I actions cannot be combined with other actions.
<b>INMPUE0020</b>	<b>Reordering multiple actions is not allowed</b>
<b>Explanation</b>	While assigning actions to the policy, a user can re-order the actions. If the user tries to re-order multiple actions at a time, this error will be thrown.
<b>Action</b>	Reordering multiple actions is not allowed.
<b>INMPUE0028</b>	<b>Select an action to move</b>
<b>Explanation</b>	If a user tries to re-order the actions without selecting anything, this error will be thrown. For this the user has to first select any action and then do the re-ordering.
<b>Action</b>	Select an action to move.
<b>INMPUE0029</b>	<b>Action category with name {0} already available</b>
<b>Explanation</b>	Action category names are unique across the system. If a user tries to create an action category with a name that exists already, this error will be thrown.
<b>Action</b>	Enter a valid action category name.
<b>INMPUE0030</b>	<b>Provide the URL of ZIP file</b>
<b>Explanation</b>	When creating an action template with the selected rule type of Java, the user has to provide a valid zip file, otherwise this error will be thrown.
<b>Action</b>	Enter the URL of the ZIP file.
<b>INMPUE0032</b>	<b>Set Profile Permission action cannot be applied to multiple object types</b>
<b>Explanation</b>	If the policy applies to multiple object types, then the set profile permission action cannot be applied
<b>Action</b>	Change the object types or create a new policy with a single object type
<b>INMPUE0033</b>	<b>Provide the correct Attribute Values</b>
<b>Explanation</b>	The attribute value provided is incorrect for the chosen type.
<b>Action</b>	Provide the correct attribute value for the chosen type.

<b>INMPUE0034</b>	<b>You must specify a value for Attribute Name</b>
<b>Explanation</b>	The required value for the duration attribute name is missing.
<b>Action</b>	Supply a correct value for the duration attribute name.
<b>INMRAE0001</b>	<b>Cannot obtain {0} from closed Resource Access Manager.</b>
<b>Explanation</b>	The Resource Access Manager is closed and thus not yet initialized.
<b>Action</b>	Make sure that the Resource Access Manager is opened before using it.
<b>INMRAE0002</b>	<b>No configuration set.</b>
<b>Explanation</b>	No configuration info set was found.
<b>Action</b>	Please provide a configuration info set. Refer to the Resource Access javadoc for additional information.
<b>INMRAE0003</b>	<b>No valid credentials found.</b>
<b>Explanation</b>	No valid credentials were found.
<b>Action</b>	Please provide valid credentials.
<b>INMRAE0004</b>	<b>Found {0} while expecting instance of XmlServerRoleManager.</b>
<b>Explanation</b>	Failed authentication against CentraSite server or absence of XmlServerLoginModule from security configuration.
<b>Action</b>	Check logs and security configuration.
<b>INMRAE0005</b>	<b>SagRoleManagementPrincipal instance not available for the authenticated subject.</b>
<b>Explanation</b>	The SagRoleManagementPrincipal security artefact is missing.
<b>Action</b>	Check the security configuration.
<b>INMRAE0006</b>	<b>Authenticated Subject cannot be null.</b>
<b>Explanation</b>	After successful authentication, the Subject instance was not found.
<b>Action</b>	Contact your software supplier.
<b>INMRAE0007</b>	<b>No representation of the Group to be associated in external user repository.</b>
<b>Explanation</b>	The external group, to be associated with a local group, is no longer present in the external repository.
<b>Action</b>	External user repositories are managed outside of CentraSite.

<b>INMRAE0008</b>	<b>Error during System level permission copy.</b>
<b>Explanation</b>	Error during System level permission copy.
<b>Action</b>	Contact your software supplier.
<b>INMRAE0009</b>	<b>An organization must be set.</b>
<b>Explanation</b>	A permission has to belong to an organization.
<b>Action</b>	Assign an organization to the permission instance.
<b>INMRAE0010</b>	<b>Organization level permission needs to have a corresponding system level permission.</b>
<b>Explanation</b>	An organization level permission needs to have a corresponding system level permission.
<b>Action</b>	Assign the system level permission to the organization level permission instance.
<b>INMRAE0011</b>	<b>A Role needs to belong to an Organization.</b>
<b>Explanation</b>	A role needs to belong to an organization.
<b>Action</b>	Assign an organization to the role instance.
<b>INMRAE0012</b>	<b>The user does not have a working Organization set.</b>
<b>Explanation</b>	The user does not have a working organization set.
<b>Action</b>	Set the working organization of the user.
<b>INMRAE0013</b>	<b>Roles can be assigned only to registered users.</b>
<b>Explanation</b>	Roles can be assigned only to registered users associated with an external user repository.
<b>Action</b>	Register a user instance to CentraSite.
<b>INMRAE0014</b>	<b>Unsupported collection type.</b>
<b>Explanation</b>	The passed collection is of an unsupported type.
<b>Action</b>	The collection expected is a list-backed one.

<b>INMRAE0015</b>	<b>Got {0} while expecting {1}</b>
<b>Explanation</b>	Passed in Registry Object instance is not of group type.
<b>Action</b>	Make sure that passed in Registry Object instance is of group type.
<b>INMRAE0016</b>	<b>Cannot obtain external user repository type.</b>
<b>Explanation</b>	Cannot retrieve the currently effective external user repository type.
<b>Action</b>	Check the security configuration.
<b>INMRAE0017</b>	<b>Unsupported external user repository type {0}.</b>
<b>Explanation</b>	The currently effective external user repository type is unknown.
<b>Action</b>	Check the security configuration.
<b>INMRAE0018</b>	<b>Currently effective external user repository type {0} does not support custom predicate.</b>
<b>Explanation</b>	Currently effective external user repository type does not support custom predicate.
<b>Action</b>	Use predicates instead.
<b>INMRAE0019</b>	<b>Currently effective external user repository type {0} does not support predicates.</b>
<b>Explanation</b>	Currently effective external user repository type does not support predicates.
<b>Action</b>	Use custom predicate instead.
<b>INMRAE0020</b>	<b>SagUserPrincipal instance not available for the authenticated subject.</b>
<b>Explanation</b>	The SagUserPrincipal security artefact is missing. It is possible that authentication against the external user repository is not performed, for example internal user accounts such as the Guest user account.
<b>Action</b>	Check the security configuration.
<b>INMRAE0021</b>	<b>PersonName must be added</b>
<b>Explanation</b>	A user instance must have PersonName.
<b>Action</b>	When creating a User object, the first name, middle name and last name of the user object need to be provided.

<b>INMSOE0001</b>	<b>HTTP Routing Protocol not enabled</b>
<b>Explanation</b>	During configuration of routing protocol, if any of the routing types are StraightThrough/LoadBalance/ContentBased/ContextBased routing, then the transport of the routing should be HTTP enabled.
<b>Action</b>	Enable the HTTP transport for routing protocol.
<b>INMSOE0002</b>	<b>JMS Routing Protocol not enabled</b>
<b>Explanation</b>	During configuration of the routing protocol, if the routing type is JMS routing, then the transport of the routing should be JMS enabled.
<b>Action</b>	Enable the JMS transport for routing protocol.
<b>INMSOE0007</b>	<b>TargetType definition file missing</b>
<b>Explanation</b>	The input JAR file provided does not contain the relevant TargetType definition XML.
<b>Action</b>	Add the relevant TargetType definition XML to the input JAR file.
<b>INMSOE0008</b>	<b>Transformation definition file missing</b>
<b>Explanation</b>	The input JAR file provided does not contain the relevant transformation file.
<b>Action</b>	Add the relevant transformation file to the input JAR file.
<b>INMSOE0010</b>	<b>Target Type name should not be empty</b>
<b>Explanation</b>	The input JAR file provided does not contain the target type name in the Target Type Definition file.
<b>Action</b>	Provide the Target Type name.
<b>INMSOE0011</b>	<b>Event Type definition file missing</b>
<b>Explanation</b>	The input JAR file provided does not contain the relevant Event Type definition.
<b>Action</b>	Add the relevant Event Type definition to the input JAR file.
<b>INMSOE0012</b>	<b>Target Type name already exists</b>
<b>Explanation</b>	The Target Type already exists with the provided name in Target Type definition file.
<b>Action</b>	Change the Target Type name.

<b>INMSOE0013</b>	<b>Service WSDL does not contain the WSDL Service Element</b>
<b>Explanation</b>	The imported WSDL does not contain the service element.
<b>Action</b>	Make sure service element is present in the service WSDL.
<b>INMSOE0015</b>	<b>Service WSDL is mandatory for deployment operations</b>
<b>Explanation</b>	The WSDL is not present for the created virtual service.
<b>Action</b>	Make sure the created virtual service contains the WSDL.
<b>INMSOE0016</b>	<b>Deployment activity {0} is the current activity log for {1} {2}</b>
<b>Explanation</b>	An activity log which is the latest deployment log for a deployed asset cannot be deleted.
<b>Action</b>	Unselect the particular deployment log from the deployment history before deleting other old entries.
<b>INMSOE0019</b>	<b>The consumer application defined in the routing rule of the asset is no longer available in CentraSite. Specify a valid consumer application in the routing rule.</b>
<b>Explanation</b>	The consumer application used as part of the context based routing condition of the asset to be deployed is not available in the CentraSite Repository.
<b>Action</b>	Provide a valid consumer application in the routing rule.
<b>INMSOE0020</b>	<b>Data type mismatch during attribute mapping for RuntimeEventType: {0}. Expected data type for attribute {1} is {2}, while the supplied data type is {3}.</b>
<b>Explanation</b>	This exception is thrown when a data type mismatch is encountered when mapping SNMP Trap attributes from EventType.xml to RuntimeEventType attributes.
<b>Action</b>	Ensure the data type matches.
<b>INMSOE0021</b>	<b>Entry protocol not defined for asset {0}</b>
<b>Explanation</b>	The inbound transport information is not defined for the asset to be deployed to the Mediator.
<b>Action</b>	Configure the entry protocol in the processing steps profile of the asset to be deployed.
<b>INMSOE0022</b>	<b>WSDL not found for native service</b>
<b>Explanation</b>	A WSDL is not available for the native service to be virtualized.
<b>Action</b>	Attach the WSDL for the native service to be virtualized.

<b>INMSOE0023</b>	<b>Cannot virtualized this WebService since the service does not contain any wsdl:bindings</b>
<b>Explanation</b>	Service must contain at least one service binding, otherwise it cannot be virtualized
<b>Action</b>	Getting error while virtualizing the service without service binding
<b>INMSOE0027</b>	<b>TrapOID (Object Identifier) {0} is duplicated in the EventType.xml inside the provided Target Type definition jar file</b>
<b>Explanation</b>	During target type creation, if the SNMP Trap OID is duplicated in EventType.xml, this exception is thrown.
<b>Action</b>	SNMP Trap OIDs should be unique within and across target types.
<b>INMSOE0028</b>	<b>TrapOID {0} already defined in existing Target Type {1}</b>
<b>Explanation</b>	During target type creation, if the SNMP Trap OID is already present in an existing target type, this exception is thrown.
<b>Action</b>	SNMP Trap OIDs should be unique within and across target types.
<b>INMSOE0031</b>	<b>Scoped Virtual Service deployment will not be triggered since dependent assertion {0} does not exist</b>
<b>Explanation</b>	Scoped Virtual Service deployment will not be triggered since some of the dependent assertions are missing in the Runtime Policy.
<b>Action</b>	Ensure dependent assertions exist.
<b>INMSOE0033</b>	<b>Scoped Virtual Service deployment will not be triggered since dependent assertion {0} does not exist</b>
<b>Explanation</b>	Virtual Service will have policies associated with it. These policies may be dependent on other policies. If the dependent policies are not applied for the virtual service, this exception will arise.
<b>Action</b>	Please create the dependent runtime policy and make sure it is applicable for the virtual service to be deployed.
<b>INMSOE0036</b>	<b>Error in API Key Creation</b>
<b>Explanation</b>	An error occurred while creating an API Key instance.
<b>Action</b>	Check if there are any related messages in the log to determine the cause of the problem.

<b>INMSOE0037</b>	<b>Mandatory parameters are not present for creation of API Key instance</b>
<b>Explanation</b>	Mandatory parameters were not provided while creating API Key object
<b>Action</b>	Provide the mandatory parameters.
<b>INMSOE0039</b>	<b>Invalid parameter {0} is selected which is not supported in the version of Mediator installed</b>
<b>Explanation</b>	The version of mediator to which the asset is being deployed does not support the parameter {0}.
<b>Action</b>	Change the parameter to one that is supported in the mediator version installed.
<b>INMSOE0041</b>	<b>Error occurred during creation of OAuth2 Client asset</b>
<b>Explanation</b>	An error was encountered while creating the OAuth2 Client asset.
<b>Action</b>	Check if there are any related messages in the log to determine the cause of the problem.
<b>INMSOE0042</b>	<b>Mandatory parameters are missing for creation of OAuth2 client instance</b>
<b>Explanation</b>	Mandatory parameters were missing while creating OAuth2 client object.
<b>Action</b>	Check if the mandatory parameters 'Service' and 'Consumer' are missing.
<b>INMSOE0043</b>	<b>Cannot enforce evaluate actions ApiKey and OAuth2 for the service.</b>
<b>Explanation</b>	When both API Keys and OAuth2 are enforced for an API in AND condition, this exception is thrown.
<b>Action</b>	Change the enforce condition to OR.
<b>INMSOE0044</b>	<b>Deployment of the Virtual Service failed. Check the Integration Server log.</b>
<b>Explanation</b>	The deployment of the Virtual Service has failed.
<b>Action</b>	Check the Integration Server log.
<b>INMSOE0045Error</b>	<b>You might not be authorized to view the runtime alias type</b>
<b>Explanation</b>	Alias Key Name Map is not initialized.
<b>Action</b>	Check if you have permission to use the alias type.

<b>INMSOE0049Error</b>	<b>Default value not specified for the runtime alias. CentraSite cannot save the alias.</b>
<b>Explanation</b>	CentraSite cannot save the runtime alias because the default value for the alias is not specified.
<b>Action</b>	Retry after you specify a default value for the runtime alias.
<b>INMSOE0050Error</b>	<b>Provide values in the fields for the runtime target: {0}</b>
<b>Explanation</b>	You are trying to associate a target to a runtime alias which has no values specified in the fields.
<b>Action</b>	Retry after you have provided target-specific values for the runtime alias fields.
<b>INMSOE0053Error</b>	<b>CentraSite does not support alias deployment for runtime target Mediator version {0}. Runtime alias deployment is supported only for Mediator version {1} and above.</b>
<b>Explanation</b>	CentraSite cannot deploy runtime aliases because they are not support in the Mediator version installed.
<b>Action</b>	If you would like to create and deploy runtime aliases, upgrade to Mediator 9.7
<b>INMSOE0054</b>	<b>Alias with name {0} already exists. Provide a different name.</b>
<b>Explanation</b>	CentraSite cannot have aliases with same name as this will have issues when it is deployed to the same Mediator.
<b>Action</b>	Provide a different name for alias and save it.
<b>INMSOE0055Error</b>	<b>Runtime alias is already deployed to target(s). You must disassociate the alias from the services and undeploy it before you change the alias name.</b>
<b>Explanation</b>	You are trying to change the alias name of a runtime alias that is already deployed to its target(s).
<b>Action</b>	Disassociate the alias from the services and undeploy it before you change the alias name.
<b>INMSOE0056Error</b>	<b>Runtime alias not found. Alias name: {0}</b>
<b>Explanation</b>	You are trying to use a runtime alias that is not defined in CentraSite.
<b>Action</b>	Check if the alias is defined in CentraSite or use an alias that is already defined.

<b>INMSOE0057Error</b>	<b>The authentication type in the secure alias does not match the authentication type in the virtual service. Secure alias: {0}, virtual service: {1}. Check the authentication type of the secure alias that you published and change it to match the authentication type used in the virtual service</b>
<b>Explanation</b>	The authentication type specified in the secure alias does not match with the outbound authentication policy specified in CentraSite.
<b>Action</b>	Check the authentication type of the secure alias that you published and change it to match the authentication type used in the virtual service.
<b>INMSOE0058</b>	<b>Target does not support deployment of REST services with more than one resource and/or tokenized routing endpoints.</b>
<b>Explanation</b>	Older Mediators before version 9.7 do not support more than one REST resource and tokenized routing endpoints.
<b>Action</b>	Make sure that you deploy to a newer version of Mediator.
<b>INMSOE0059</b>	<b>Invalid deployment endpoint.</b>
<b>Explanation</b>	The deployment endpoint is not valid.
<b>Action</b>	Provide a valid deployment endpoint.
<b>INMSOE0061</b>	<b>HTTP protocol is not supported for Kerberos. Select HTTPS protocol only.</b>
<b>Explanation</b>	HTTP protocol is not supported for Kerberos. Only, HTTPS protocol is supported.
<b>Action</b>	Select HTTPS protocol only during virtualization.
<b>INMSOE0062</b>	<b>The Custom Error Variable name field must not be empty.</b>
<b>Explanation</b>	You have not entered a name while adding a Custom Error Variable in the Conditional Error Processing step.
<b>Action</b>	Enter a name for the Custom Error Variable.
<b>INMSOE0063</b>	<b>The Custom Error Variable Xpath expression cannot be empty.</b>
<b>Explanation</b>	You have not entered an Xpath expression while adding Custom Error Variable in the Conditional Error Processing step.
<b>Action</b>	Provide an Xpath expression for the Custom Error Variable.

<b>INMSOE0064</b>	<b>Gateway with version {0} does not support OData services.</b>
<b>Explanation</b>	The gateway is too old for deploying OData services.
<b>Action</b>	Use a newer gateway (>= 9.10)
<b>INMSOE0065</b>	<b>Service {0} is not of supported type for {1}.</b>
<b>Explanation</b>	The service is not supported for the give action. This is an internal problem.
<b>Action</b>	Check the type of service.
<b>INMSOE0066</b>	<b>VSD cannot be generated for virtual service {0}.</b>
<b>Explanation</b>	The VSD document of a virtual service cannot be generated due to internal problems.
<b>Action</b>	Check the details of the virtual service.
<b>INMSOE0067</b>	<b>Gateway with version {0} does not support the HTTP PATCH method for REST service {1}.</b>
<b>Explanation</b>	The deployed REST service exposes the HTTP PATCH method, which is not supported by this version of Mediator.
<b>Action</b>	Deploy the REST service with HTTP PATCH method to a newer version of Mediator.
<b>INMSOE0068</b>	<b>The REST service {0} uses the HTTP PATCH method, however the deployment mode is not set to "axis-free".</b>
<b>Explanation</b>	The REST service {0} uses the HTTP PATCH method, however the deployment mode is not set to "axis-free". This is because only the axis-free deployment mode supports the PATCH method.
<b>Action</b>	Check if you can activate the axis-free deployment mode in centrasite.xml.
<b>INMSOE0069</b>	<b>Incompatible gateway types.</b>
<b>Explanation</b>	The gateway types of the CentraSite registry object and the running instance are not the same type.
<b>Action</b>	Check your running target and the CentraSite gateway object.
<b>INMSOE0070</b>	<b>REST service deployment to API Gateway requires "axis-free" setting.</b>
<b>Explanation</b>	REST service deployment to API Gateway is only supported if the CentraSite deployment mode was set to axis-free.
<b>Action</b>	Configure the axis-free mode in CentraSite.

<b>INMSOE0072</b>	<b>Connection to deployment endpoint failed {0}.</b>
<b>Explanation</b>	This occurs if no connection can be established to the deployment endpoint defined in a target during deployment/undeployment/synconsumers operations. This could be because the deployment endpoint is down or the credentials used for accessing the deployment endpoint are incorrect.
<b>Action</b>	Check if the deployment endpoint is up and running. Also check if the credentials defined in the target for accessing the deployment endpoint are correct.
<b>INMSOE0073</b>	<b>Gateway not active or accessible.</b>
<b>Explanation</b>	The selected gateway is not active or accessible.
<b>Action</b>	Check the accessibility of gateway.
<b>INMSOE0074</b>	<b>Invalid credentials</b>
<b>Explanation</b>	Invalid username or password specified for accessing the gateway.
<b>Action</b>	Check the username and password for accessing the gateway.
<b>INMSOE0075</b>	<b>Unknown host: {0}</b>
<b>Explanation</b>	The host to be accessed is unknown.
<b>Action</b>	Check if the host is accessible.
<b>INMSOI0017</b>	<b>Connection to deployment endpoint failed</b>
<b>Explanation</b>	This occurs if no connection can be established to the deployment endpoint defined in a target during deployment/undeployment/synconsumers operations. This could be because the deployment endpoint is down or the credentials used for accessing the deployment endpoint are wrong.
<b>Action</b>	Check if the deployment endpoint is up and running. Also check if the credentials defined in the target for accessing the deployment endpoint are correct.
<b>INMSOI0035</b>	<b>API Key for {0} of {1}</b>
<b>Explanation</b>	This is how the name of the API key will be generated where the service name is passed as a parameter.
<b>Action</b>	No action required.

<b>INMSOI0040</b>	<b>OAuth2 Client for {0} of {1}</b>
<b>Explanation</b>	This is how the name of the OAuth2 Client is created when the service name and consumer name are passed as parameters.
<b>Action</b>	No action required.
<b>INMSOW0034</b>	<b>The parameter(s)/action(s) {0} were ignored as it is not supported by Mediator {1}</b>
<b>Explanation</b>	Virtual Service can be deployed from latest version of CentraSite to Mediator version 8.2.2 and above. If you deploy any service to older version of Mediator from latest version of CentraSite, some policy parameters or actions cannot be executed on older version of Mediator. Such policy parameters or actions will be ignored. This warning message will list those ignored parameter/actions.
<b>Action</b>	If the ignored parameters or actions need to be executed, then Mediator has to be upgraded to version in which CentraSite is running. If the ignored parameter or actions are not needed, then this warning message can be ignored.
<b>INMSOW0076</b>	<b>Service is published to API gateway but activation is denied.</b>
<b>Explanation</b>	Service was successfully published to API gateway but the service is still in deactivation state.
<b>Action</b>	Log into API Gateway and try to activate the service.
<b>INMSTE0001</b>	<b>Referenced service does not exist ("{0}")</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Please contact your software supplier.
<b>INMSTE0002</b>	<b>Dangling reference ("{0}")</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Please contact your software supplier.
<b>INMSTE0003</b>	<b>Conflicting state ({0})</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Please contact your software supplier.

<b>INMSTE0004</b>	<b>Invalid Reference ("{0}")</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Please contact your software supplier.
<b>INMSTE0005</b>	<b>Type concept is not found in ImportList</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Please contact your software supplier.
<b>INMSTE0006</b>	<b>No schema definition generated</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Please contact your software supplier.
<b>INMSTE0007</b>	<b>schemaName for selected concept is null</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Please contact your software supplier.
<b>INMSTE0008</b>	<b>At least one instance does not comply with the type modifications.</b>
<b>Explanation</b>	A type is being modified in a way that is not compliant with the existing instances of that type.
<b>Action</b>	Modify the type in a compliant way.
<b>INMSTE0009</b>	<b>Type concept not found for "{0}"</b>
<b>Explanation</b>	While updating or deleting a JAXR object type, the corresponding type concept was not found in the registry.
<b>Action</b>	This is an internal error. Please contact your software supplier.
<b>INMSUE0001</b>	<b>Reordering multiple actions is not allowed</b>
<b>Explanation</b>	Reordering multiple actions not allowed.
<b>Action</b>	Reordering multiple actions not allowed.
<b>INMSUE0002</b>	<b>You must select valid jar file</b>
<b>Explanation</b>	The selected jar file(s) are not valid.
<b>Action</b>	Select valid jar files.

<b>INMSUE0003</b>	<b>Enter unique name</b>
<b>Explanation</b>	The event type name already exists.
<b>Action</b>	Enter a unique name for the event type
<b>INMSUE0004</b>	<b>Target name should not be empty</b>
<b>Explanation</b>	An attempt was made to add a target object without a name.
<b>Action</b>	Supply a target name.
<b>INMSUE0005</b>	<b>Target type should not be empty</b>
<b>Explanation</b>	An attempt was made to add a target type object without a name.
<b>Action</b>	Supply a target type name.
<b>INMSUE0006</b>	<b>Policy name cannot be empty</b>
<b>Explanation</b>	An attempt was made to add a policy object without a name.
<b>Action</b>	Supply a policy name.
<b>INMSUE0007</b>	<b>Select an Asset Type for the policy</b>
<b>Explanation</b>	For creating a runtime policy object, the object needs an associated object type.
<b>Action</b>	Select an object type for the policy.
<b>INMSUE0008</b>	<b>Select a target type for the policy</b>
<b>Explanation</b>	The target type for the policy is missing.
<b>Action</b>	Select a target type for the policy.
<b>INMSUE0009</b>	<b>Default route cannot be empty</b>
<b>Explanation</b>	The default route is missing.
<b>Action</b>	Define a default route.
<b>INMSUE0010</b>	<b>XPath expression cannot be empty</b>
<b>Explanation</b>	An empty XPath expression was supplied.
<b>Action</b>	Supply an XPath expression.

<b>INMSUE0011</b>	<b>Enter the valid XPath to the 'Element Required to be Signed'</b>
<b>Explanation</b>	The correct XPath to the 'Element Required to be Signed' is required.
<b>Action</b>	Enter the valid XPath to the 'Element Required to be Signed'.
<b>INMSUE0012</b>	<b>Virtual Service name should not be empty</b>
<b>Explanation</b>	The required name is missing.
<b>Action</b>	Supply the name.
<b>INMSUE0013</b>	<b>Version cannot be empty</b>
<b>Explanation</b>	A version was not entered.
<b>Action</b>	Enter a version.
<b>INMSUE0014</b>	<b>No WSDL Found</b>
<b>Explanation</b>	For the given URL, there is no WSDL available.
<b>Action</b>	Supply a WSDL for the URL.
<b>INMSUE0015</b>	<b>Virtual service with name {0} already exists</b>
<b>Explanation</b>	A virtual service with the given name already exists.
<b>Action</b>	Supply a different name for the virtual service.
<b>INMSUE0016</b>	<b>Assign actions for the policy</b>
<b>Explanation</b>	The actions required for the runtime policy object are missing.
<b>Action</b>	Assign actions for the policy.
<b>INMSUE0017</b>	<b>Create target type before creating runtime policy</b>
<b>Explanation</b>	The target type required for creating the runtime policy is not available.
<b>Action</b>	Create the target type before creating the runtime policy.
<b>INMSUE0018</b>	<b>Create target type before creating target</b>
<b>Explanation</b>	The target type must be created before the target can be created.
<b>Action</b>	Create the target type before creating the target.

<b>INMSUE0019</b>	<b>Select at least one target to deploy</b>
<b>Explanation</b>	No target was selected to deploy.
<b>Action</b>	Select at least one target to deploy.
<b>INMSUE0020</b>	<b>Default route cannot be empty</b>
<b>Explanation</b>	The default route was not specified.
<b>Action</b>	Specify a default route
<b>INMSUE0022</b>	<b>JMS alert destination cannot be empty</b>
<b>Explanation</b>	The JMS alert destination was not specified.
<b>Action</b>	Specify the JMS alert destination.
<b>INMSUE0023</b>	<b>Select at least one consumer application</b>
<b>Explanation</b>	No consumer applications have been selected.
<b>Action</b>	Select at least one consumer application.
<b>INMSUE0024</b>	<b>Rule name already exists</b>
<b>Explanation</b>	The specified rule name already exists.
<b>Action</b>	Specify a different rule name.
<b>INMSUE0025</b>	<b>Endpoint URL cannot be empty</b>
<b>Explanation</b>	An empty endpoint URL was specified.
<b>Action</b>	Specify a value for the endpoint URL.
<b>INMSUE0026</b>	<b>Consumer application cannot be empty</b>
<b>Explanation</b>	The consumer application was not specified.
<b>Action</b>	Specify the consumer application.
<b>INMSUE0027</b>	<b>Invalid hour given</b>
<b>Explanation</b>	The input for hour is invalid.
<b>Action</b>	Enter a valid hour.

<b>INMSUE0028</b>	<b>Invalid minute given</b>
<b>Explanation</b>	The input for minute is invalid.
<b>Action</b>	Enter a valid minute.
<b>INMSUE0029</b>	<b>Date cannot be empty</b>
<b>Explanation</b>	A date was not entered.
<b>Action</b>	Enter a date.
<b>INMSUE0030</b>	<b>Assertion type not found</b>
<b>Explanation</b>	The assertion type was not found.
<b>Action</b>	Specify an assertion type.
<b>INMSUE0031</b>	<b>Virtual service name cannot be same as web service name</b>
<b>Explanation</b>	The virtual service name should not be the same as the web service name.
<b>Action</b>	Specify a different virtual service name.
<b>INMSUE0032</b>	<b>HTTP header value cannot be empty</b>
<b>Explanation</b>	An HTTP header value was not entered.
<b>Action</b>	Enter an HTTP header value.
<b>INMSUE0033</b>	<b>HTTP header name cannot be empty</b>
<b>Explanation</b>	The HTTP header name is empty.
<b>Action</b>	Enter an HTTP header name.
<b>INMSUE0034</b>	<b>JMS message property name cannot be empty</b>
<b>Explanation</b>	The JMS message property name is empty.
<b>Action</b>	Enter a JMS message property name.
<b>INMSUE0035</b>	<b>JMS message property value cannot be empty</b>
<b>Explanation</b>	The JMS message property value is empty.
<b>Action</b>	Enter a JMS message property value.

<b>INMSUE0036</b>	<b>Virtual service name cannot have # character</b>
<b>Explanation</b>	The virtual service name contains the "#" character.
<b>Action</b>	Ensure that the name of the virtual service does not contain the "#" character.
<b>INMSUE0037</b>	<b>JMS header name cannot be empty</b>
<b>Explanation</b>	The JMS header name is empty.
<b>Action</b>	Enter the JMS header name.
<b>INMSUE0038</b>	<b>JMS header value cannot be empty</b>
<b>Explanation</b>	The JMS header value is empty.
<b>Action</b>	Enter the JMS header value.
<b>INMSUE0039</b>	<b>Select a policy to delete</b>
<b>Explanation</b>	No policy has been selected for deletion.
<b>Action</b>	Select a policy to delete.
<b>INMSUE0062</b>	<b>Undeploy the Service(s) before deleting the Target</b>
<b>Explanation</b>	Before deleting the target, undeploy all virtual services from the target.
<b>Action</b>	Make sure that the target instance has no deployed virtual services before trying to delete the target.
<b>INMSUE0066</b>	<b>Virtual XML Service with name {0} already exists</b>
<b>Explanation</b>	A virtual XML service with the given name already exists.
<b>Action</b>	Supply a different name for the virtual XML service.
<b>INMSUE0067</b>	<b>HTTP Methods not declared for the native XML Service</b>
<b>Explanation</b>	HTTP methods required for the XML service being virtualized were not declared.
<b>Action</b>	Update the HTTP methods of the native XML service being virtualized.
<b>INMSUE0068</b>	<b>HTTP Methods are not declared for the XML Service</b>
<b>Explanation</b>	The HTTP methods cannot be empty when creating an XML service.
<b>Action</b>	Select any one of the HTTP methods provided to create an XML Service.

<b>INMSUE0069</b>	<b>Select an HTTP Method for Entry Protocol</b>
<b>Explanation</b>	HTTP Methods for an entry protocol policy of a virtual XML service cannot be empty
<b>Action</b>	Select any one of the options available for HTTP Methods for an Entry Protocol policy
<b>INMSUE0070</b>	<b>Select the data type for predefined context variable</b>
<b>Explanation</b>	The data type for the predefined context variable should be selected.
<b>Action</b>	Select either the String or Int data type for the predefined context variable.
<b>INMSUE0071</b>	<b>Select the name for predefined context variable</b>
<b>Explanation</b>	The context variable name cannot be empty.
<b>Action</b>	Select any of the available context variable names.
<b>INMSUE0072</b>	<b>Enter the value for predefined context variable</b>
<b>Explanation</b>	The context variable value cannot be empty.
<b>Action</b>	Enter the value of the selected context variable.
<b>INMSUE0073</b>	<b>Select the data type for custom context variable</b>
<b>Explanation</b>	The data type for the selected custom context variable is invalid.
<b>Action</b>	Select the data type of the custom context variable.
<b>INMSUE0074</b>	<b>Enter the name for custom context variable</b>
<b>Explanation</b>	The name of the custom context variable cannot be empty.
<b>Action</b>	Enter the custom context variable name.
<b>INMSUE0075</b>	<b>Enter the value for custom context variable</b>
<b>Explanation</b>	The value for the custom context variable cannot be empty.
<b>Action</b>	Enter the value for the custom context variable.
<b>INMSUE0076</b>	<b>Virtual REST Service with name {0} already exists</b>
<b>Explanation</b>	A virtual REST service with the given name already exists.
<b>Action</b>	Supply a different name for the virtual REST service.

<b>INMSUE0077</b>	<b>Select at least one asset to deploy</b>
<b>Explanation</b>	There are no assets selected for deployment
<b>Action</b>	Please select the assets to be deployed
<b>INMSUE0078</b>	<b>User does not have permission to create groups in the organization</b>
<b>Explanation</b>	When a target is created, a corresponding synchronization group is created in the organization selected with the given target name, but the user who is trying to create the target does not have permission to create a group in the organization he belongs to or the selected organization.
<b>Action</b>	Grant manage users permission to the user.
<b>INMSUE0079</b>	<b>Abstract WSDL services cannot be virtualized</b>
<b>Explanation</b>	The chosen service is an abstract service and hence cannot be virtualized
<b>Action</b>	Please choose a service which has concrete service definitions to virtualize
<b>INMSUE0080</b>	<b>Reserved characters except _ and - and non-ASCII characters are not allowed in the virtual service name.</b>
<b>Explanation</b>	The virtual service name can only contain the letters A-Z, a-z, numbers from 0-9, _ and - characters.
<b>Action</b>	Remove the special characters from the virtual service name.
<b>INMSUE0081</b>	<b>Logged in user {0} does not have permission to deploy the asset</b>
<b>Explanation</b>	To deploy an asset to the target, the user must have manage targets permission.
<b>Action</b>	Request the manage targets permission from the CentraSite administrator and try again.
<b>INMSUE0083</b>	<b>Hard Limit value should not be empty</b>
<b>Explanation</b>	Number. Required. Specifies the maximum number of invocations allowed per Interval before stopping the processing of further requests and issuing an alert. Typically, this limit should be higher than the soft limit.
<b>Action</b>	On Save of Throttling Policy

<b>INMSUE0085</b>	<b>Select Consumer Application to Limit traffic</b>
<b>Explanation</b>	Specifies the consumer application(s) that this action applies to. To specify multiple consumer applications, use the plus button to add rows, or select Any Consumer
<b>Action</b>	Specifies the consumer application(s) that this action applies to. To specify multiple consumer applications, use the plus button to add rows, or select Any Consumer
<b>INMSUE0086</b>	<b>Soft Limit value should not be empty</b>
<b>Explanation</b>	Number. Optional. Specifies the maximum number of invocations allowed per Interval before issuing an alert. Reaching the soft limit will not affect further processing of requests (until the Hard Limit is reached).
<b>Action</b>	On Save of Throttling Policy
<b>INMSUE0087</b>	<b>Soft Limit should not be higher than the Hard Limit</b>
<b>Explanation</b>	Hard limit should be higher than the soft limit
<b>Action</b>	On Save of Throttling Policy
<b>INMSUE0089</b>	<b>Reserved characters except _ and - and non-ASCII characters are not allowed in the target name.</b>
<b>Explanation</b>	The target name can only contain the letters A-Z, a-z, numbers from 0-9, _ and - characters.
<b>Action</b>	Remove the special characters from the target name.
<b>INMSUI0082</b>	<b>Service URL is invalid</b>
<b>Explanation</b>	Service URL should not contain characters like *
<b>Action</b>	Replace character ' * ' with a valid character.
<b>INMSUI0084</b>	<b>Interval should not be empty.</b>
<b>Explanation</b>	Specifies the amount of time for the soft limit and hard limit to be reached.
<b>Action</b>	Specifies the amount of time for the soft limit and hard limit to be reached.
<b>INMSUI0088</b>	<b>Please enter a valid URL or URI</b>
<b>Explanation</b>	A URL or URI was specified that is an invalid endpoint.
<b>Action</b>	Specify a valid URL or URI.

<b>INMUCE0001</b>	<b>Error while creating Axis2 SOAP Service Stub for UDDI Security API</b>
<b>Explanation</b>	This error may happen if the host or port specified in RegistryConfiguration is not valid or if there is an incorrect version of Axis jars in the classpath.
<b>Action</b>	Please make sure the host and port of the registry provided in RegistryConfiguration are valid. And also make sure that the classpath has the correct version of Axis2 jars.
<b>INMUCE0002</b>	<b>Error while creating Axis2 SOAP Service Stub for UDDI Inquiry API</b>
<b>Explanation</b>	This error may happen if the host or port specified in RegistryConfiguration is not valid or if there is an incorrect version of Axis jars in the classpath.
<b>Action</b>	Please make sure the host and port of the registry provided in RegistryConfiguration are valid. And also make sure the classpath has the correct version of Axis2 jars.
<b>INMUCE0003</b>	<b>Error while creating Axis2 SOAP Service Stub for UDDI Publish API</b>
<b>Explanation</b>	This error may happen if the host or port specified in RegistryConfiguration is not valid or if there is an incorrect version of Axis jars in the classpath.
<b>Action</b>	Please make sure the host and port of the registry provided in RegistryConfiguration are valid. And also make sure the classpath has the correct version of Axis2 jars.
<b>INMUCE0004</b>	<b>Error while creating Axis2 SOAP Service Stub for UDDI Subscription API</b>
<b>Explanation</b>	This error may happen if the host or port specified in RegistryConfiguration is not valid or if there is an incorrect version of Axis jars in the classpath.
<b>Action</b>	Please make sure the host and port of the registry provided in RegistryConfiguration are valid. And also make sure the classpath has the correct version of Axis2 jars.
<b>INMUCE0005</b>	<b>Error while creating Axis2 SOAP Service Stub for Taxonomy API</b>
<b>Explanation</b>	This error may happen if the host or port specified in RegistryConfiguration is not valid or if there is an incorrect version of Axis jars in the classpath.
<b>Action</b>	Please make sure the host and port of the registry provided in RegistryConfiguration are valid. And also make sure the classpath has the correct version of Axis2 jars.
<b>INMUCE0006</b>	<b>Not able to connect to the UDDI Registry. get_authToken call failed.</b>
<b>Explanation</b>	Remote exception thrown while connecting to UDDI registry.
<b>Action</b>	Please make sure the host and port provided in RegistryConfiguration are valid.

<b>INMUCE0007</b>	<b>Not able to connect to the UDDI Registry. discard_authToken call failed.</b>
<b>Explanation</b>	Remote exception thrown while connecting to UDDI registry.
<b>Action</b>	Please make sure the host and port provided in RegistryConfiguration are valid.
<b>INMUCE0008</b>	<b>Not able to fetch the modified date of service with key {0}. get_operationalInfo call failed due to RemoteException.</b>
<b>Explanation</b>	Remote exception was thrown while getting operational info for the given service.
<b>Action</b>	Please make sure the registry is running the host and port provided in RegistryConfiguration.
<b>INMUCE0009</b>	<b>Not to able to fetch the virtual services for the specified target {0}</b>
<b>Explanation</b>	Not to able to fetch the virtual services for the specified target {0}, as remote exception was caught in find_service call.
<b>Action</b>	Please make sure the registry is running the host and port provided in RegistryConfiguration.
<b>INMUCE0011</b>	<b>Not able to fetch the service with name {0}. find_service call failed due to RemoteException.</b>
<b>Explanation</b>	Remote exception was thrown while inquiring the registry for services.
<b>Action</b>	Please make sure the registry is running the host and port provided in RegistryConfiguration.
<b>INMUCE0012</b>	<b>Not able to fetch the details of the service {0}. get_serviceDetail call failed due to RemoteException.</b>
<b>Explanation</b>	Remote exception was thrown while inquiring the registry for service details.
<b>Action</b>	Please make sure the registry is running the host and port provided in RegistryConfiguration.
<b>INMUCE0013</b>	<b>Not able to fetch the details of the tModel {0}. get_tModelDetail call failed due to RemoteException.</b>
<b>Explanation</b>	Remote exception was thrown while inquiring the registry for tModel details.
<b>Action</b>	Please make sure the registry is running the host and port provided in RegistryConfiguration.

<b>INMUCW0010</b>	<b>Unable to find the virtual service with specified name {0}</b>
<b>Explanation</b>	There is not virtual service with the specified name in the UDDI registry.
<b>Action</b>	Please make sure the UDDI registry has a virtual service with the specified name. If it exists please make sure the user provided in RegistryConfiguration has the privilege to view the virtual service.
<b>INMVSE0001</b>	<b>Internal JAXR error happened</b>
<b>Explanation</b>	An exception inside JAXR occurred.
<b>Action</b>	Analyze the JAXR exception given by the stack.
<b>INMVSE0002</b>	<b>Invalid NULL parameter given</b>
<b>Explanation</b>	A version interface method was called with invalid parameters containing NULL.
<b>Action</b>	Correct the usage of the version management interface.
<b>INMVSE0003</b>	<b>Object of type {0} not supported for External Link versioning</b>
<b>Explanation</b>	This object must not be used for duplicating external links.
<b>Action</b>	Do not use this kind of object.
<b>INMVSE0004</b>	<b>Invalid external link for versioning, must be a WebDAV one. URI: {0}</b>
<b>Explanation</b>	The external link object provided for versioning is not supported. It must be an external link of a WebDAV resource.
<b>Action</b>	Do not use this kind of external link.
<b>INMVSE0005</b>	<b>Unexpected external link. URI: {0}</b>
<b>Explanation</b>	During external link versioning the external link handling was unexpected.
<b>Action</b>	Check your WebDAV resources of external links.
<b>INMVSE0006</b>	<b>Object of type {0} not supported for a versioning operation</b>
<b>Explanation</b>	A non-versionable object was found during a versioning operation.
<b>Action</b>	Check your registered objects.

<b>INMVSE0007</b>	<b>Unexpected: no new external link in duplication list</b>
<b>Explanation</b>	Internal error: an element was not properly duplicated during versioning.
<b>Action</b>	Contact your software supplier.
<b>INMVSE0008</b>	<b>Object to be versioned ({0}) does not have the highest version number</b>
<b>Explanation</b>	The registry object to be versioned is an intermediate one in the versioning hierarchy, which is not permitted.
<b>Action</b>	Use only the highest versioned object for a versioning action.
<b>INMVSE0009</b>	<b>Object ({0}) is not granted for a versioning operation.</b>
<b>Explanation</b>	A registered listener rejected the object for the given versioning operation.
<b>Action</b>	Check your registry entries and why the listener has denied the action.
<b>INMVSE0010</b>	<b>Invalid association ID specified: {0}</b>
<b>Explanation</b>	An invalid association type was specified by the user of the API.
<b>Action</b>	Correct the association type, e.g. for HasParent, Uses, etc.
<b>INMVSE0011</b>	<b>Invalid WebDAV URL: {0}</b>
<b>Explanation</b>	The WebDAV URL has an invalid format.
<b>Action</b>	Correct the format.
<b>INMVSE0012</b>	<b>WebDAV cannot be accessed</b>
<b>Explanation</b>	Failure on WebDAV access.
<b>Action</b>	Inspect the original exception.
<b>INMVSE0013</b>	<b>Resource cannot be stored to WebDAV</b>
<b>Explanation</b>	Internal error on storing a file to WebDAV.
<b>Action</b>	Inspect the original exception.
<b>INMVSE0014</b>	<b>Unexpected: copied object not found in list</b>
<b>Explanation</b>	An object which was duplicated was not found in the list holding those elements.
<b>Action</b>	No action required.

<b>INMVSE0015</b>	<b>Unsupported copy mode for a Package object</b>
<b>Explanation</b>	The copy mode for versioning a package is not supported.
<b>Action</b>	Use only supported copy modes.
<b>INMVSE0016</b>	<b>Error retrieving checkpoint objects for ID: {0}</b>
<b>Explanation</b>	The revision or checkpoint object cannot be determined.
<b>Action</b>	See the embedded exception description.
<b>INMVSE0017</b>	<b>Error finding checkpoint records</b>
<b>Explanation</b>	Checkpoint records couldn't be determined during a find with qualifiers.
<b>Action</b>	See the embedded exception description.
<b>INMVSE0018</b>	<b>The restore of revision objects failed</b>
<b>Explanation</b>	The replacement of the current object with an older revision of the object was not successful.
<b>Action</b>	See the embedded exception description.
<b>INMVSE0019</b>	<b>The method is not allowed if revision feature not enabled</b>
<b>Explanation</b>	The revision feature must be enabled in CentraSite before using certain methods.
<b>Action</b>	Enable CentraSite's revision feature.
<b>INMVSE0020</b>	<b>Checkpoint label {0} already in use</b>
<b>Explanation</b>	A checkpoint label must only be used once in the system.
<b>Action</b>	Use another label or delete the label first.
<b>INMVSE0021</b>	<b>Setting of checkpoint label '{0}' failed</b>
<b>Explanation</b>	Setting of checkpoint label to revision objects failed.
<b>Action</b>	See embedded exception description.
<b>INMVSE0022</b>	<b>Error reading checkpoint with label '{0}'</b>
<b>Explanation</b>	Reading revision objects failed due to an internal reason.
<b>Action</b>	See embedded exception description.

<b>INMVSE0023</b>	<b>Error on finding checkpoint label names</b>
<b>Explanation</b>	Retrieving all checkpoint label names was not successful.
<b>Action</b>	See embedded exception description.
<b>INMVSE0024</b>	<b>Error during deletion of checkpoint label '{0}'</b>
<b>Explanation</b>	Deleting checkpoint labels from objects was not successful.
<b>Action</b>	See embedded exception description.
<b>INMVSE0025</b>	<b>Checkpoint label count cannot be determined</b>
<b>Explanation</b>	The checkpoint label count cannot be determined due to internal problems.
<b>Action</b>	Please contact your software supplier.
<b>INMVSE0026</b>	<b>Error getting minor version of object: {0}</b>
<b>Explanation</b>	Error getting minor version of object.
<b>Action</b>	See embedded exception description.
<b>INMVSE0027</b>	<b>Error getting checkpoint label of object: {0}</b>
<b>Explanation</b>	Error getting checkpoint label of object.
<b>Action</b>	See embedded exception description.
<b>INMVSE0028</b>	<b>Invalid keepCount parameter</b>
<b>Explanation</b>	Invalid keepCount parameter.
<b>Action</b>	Correct the keepCount parameter.
<b>INMVSE0029</b>	<b>Error purging checkpoints of object: {0}</b>
<b>Explanation</b>	Error purging checkpoints of object.
<b>Action</b>	See embedded exception description.
<b>INMVSE0030</b>	<b>Revision and Checkpoint enablement failed</b>
<b>Explanation</b>	Revision and Checkpoint enablement failed.
<b>Action</b>	See embedded exception description.

<b>INMVSE0031</b>	<b>Disable of Revision and Checkpoint failed</b>
<b>Explanation</b>	Disable of Revision and Checkpoint failed.
<b>Action</b>	See embedded exception description.
<b>INMVSE0032</b>	<b>Base collection not present</b>
<b>Explanation</b>	The base CentraSite collection is not available. The registry seems to be inconsistent.
<b>Action</b>	Please contact your software supplier.
<b>INMVSE0033</b>	<b>The common CentraSite schema is not present.</b>
<b>Explanation</b>	Schema CentraSiteObjects is not present.
<b>Action</b>	Check the CentraSite environment.
<b>INMVSE0034</b>	<b>Asset Type ({0}) does not support the Versioning Capability</b>
<b>Explanation</b>	An instance of an asset type should get a new version, but the asset type does not support this.
<b>Action</b>	Check the properties of your asset type.
<b>INMWSE0001</b>	<b>Unable to connect to {0} using the provided username and password.</b>
<b>Explanation</b>	The service was unable to connect to the provided CentraSite address.
<b>Action</b>	Make sure the CentraSite address is valid and the username and password are correct.
<b>INMWSE0002</b>	<b>Error reading {0}.</b>
<b>Explanation</b>	The service was unable to read the document.
<b>Action</b>	Make sure that the document is accessible and valid.
<b>INMWSE0003</b>	<b>Unable to import service.</b>
<b>Explanation</b>	The application was unable to import the service in the CentraSite registry.
<b>Action</b>	Make sure the arguments are correct or manually check the CentraSite registry for problems.
<b>INMWSE0004</b>	<b>Error retrieving product with name {0}.</b>
<b>Explanation</b>	The service was unable to find the product with the provided product name.
<b>Action</b>	Make sure that the product name is correct and exists in the CentraSite registry.

<b>INMWSE0005</b>	<b>Unable to import {0} {1}.</b>
<b>Explanation</b>	The service was unable to import the file.
<b>Action</b>	Make sure the arguments are correct or manually check the CentraSite registry for problems.
<b>INMWSE0006</b>	<b>Failed to retrieve the imported service ID.</b>
<b>Explanation</b>	Unable to retrieve the UDDI key of the service which has been imported.
<b>Action</b>	Check connection to CentraSite server. Check the logs for errors.
<b>INMWSE0007</b>	<b>Unable to retrieve the registered BPEL process ID.</b>
<b>Explanation</b>	The application was unable to retrieve the imported BPEL process ID.
<b>Action</b>	Check connection to CentraSite server. Check the logs for errors.
<b>INMWSE0008</b>	<b>Unable to import BPEL process.</b>
<b>Explanation</b>	The application was unable to import the BPEL process in the CentraSite registry.
<b>Action</b>	Make sure the arguments are correct or manually check the CentraSite registry for problems.
<b>INMWSE0009</b>	<b>Unable to import XSD schema.</b>
<b>Explanation</b>	The service was unable to import the XSD schema in the CentraSite registry.
<b>Action</b>	Make sure the arguments are correct or manually check the CentraSite registry for problems.
<b>INMWSE0010</b>	<b>Missing attachment with content ID {0}.</b>
<b>Explanation</b>	The service was unable to retrieve the attachment.
<b>Action</b>	Make sure the content ID of the attachment is valid.
<b>INMWSE0011</b>	<b>Invalid file descriptor. Missing file type.</b>
<b>Explanation</b>	The value for file type was missing.
<b>Action</b>	Make sure the arguments are valid.

<b>INMWSE0012</b>	<b>Invalid file descriptor. Missing file name.</b>
<b>Explanation</b>	The value for the file name was missing.
<b>Action</b>	Make sure the arguments are valid.
<b>INMWSE0013</b>	<b>Invalid file descriptor. Missing content ID string.</b>
<b>Explanation</b>	The value for the content ID string was missing.
<b>Action</b>	Make sure the arguments are valid.
<b>INMWSE0014</b>	<b>Invalid file type. Must be XSD, WSDL, BPEL, XPDL, META_INFO, DOCUMENT or REFERENCED.</b>
<b>Explanation</b>	CentraSite web services will only accept the following file types: XSD, WSDL, BPEL, XPDL, META_INFO, DOCUMENT or REFERENCED.
<b>Action</b>	Please provide valid file type.
<b>INMWSE0015</b>	<b>Missing Authorization header.</b>
<b>Explanation</b>	Authorization header for HTTP basic authentication was not found in the request.
<b>Action</b>	Provide username and password to connect to the CentraSite server.
<b>INMWSE0016</b>	<b>The creation of a folder in the temp directory has failed.</b>
<b>Explanation</b>	The creation of a folder in the temp directory has failed. The folder could not be created in the temp directory which is determined by the system property java.io.tmpdir.
<b>Action</b>	Please make sure that the temp directory has enough free space.
<b>INMWSE0017</b>	<b>The creation of folder {0} has failed.</b>
<b>Explanation</b>	The specified folder could not be created.
<b>Action</b>	Please make sure that you have sufficient privileges to create the folder.
<b>INMWSE0018</b>	<b>Exception while importing XPDL</b>
<b>Explanation</b>	An exception occurred while importing the XPDL file.
<b>Action</b>	Please make sure the SOAP request has all required parameters filled with proper values.

<b>INMWSE0019</b>	<b>Referenced file {0} not found</b>
<b>Explanation</b>	The XPDL file to be imported has a reference to a web service. But the WSDL file for the referenced file was not passed to the XPDL importer service.
<b>Action</b>	Please create a file descriptor for the referenced WSDL file and send it to ImportXPDLService.
<b>INMWSE0020</b>	<b>Response from XPDL importer does not contain any registry objects</b>
<b>Explanation</b>	The XPDL Importer didn't report any error. Also it didn't return any response which needs to be filled for a web service response.
<b>Action</b>	Please make sure the XPDL file contains the Process element which will be created in CentraSite and returned in the web service response.
<b>INMWSE0021</b>	<b>Error while fetching LCM state for process</b>
<b>Explanation</b>	A system error has occurred while loading the LCM state of the process.
<b>Action</b>	Please check whether the Process object is in a valid state. If it is in a valid state, please retry the request.
<b>INMWSE0022</b>	<b>Parameter name (wild card) is mandatory input</b>
<b>Explanation</b>	This operation requires a keyword as a parameter. In the request, the keyword is not set.
<b>Action</b>	Please set the keyword in the SOAP request.
<b>INMWSE0023</b>	<b>Error while fetching processes from CentraSite</b>
<b>Explanation</b>	A system error has occurred while fetching process objects from CentraSite. Perhaps the connection to the CentraSite Server has been lost.
<b>Action</b>	Please check whether the CentraSite Server is up and running.
<b>INMWSE0024</b>	<b>Error while fetching services from CentraSite</b>
<b>Explanation</b>	A system error has occurred while fetching services from CentraSite. Perhaps the connection to the CentraSite Server has been lost.
<b>Action</b>	Please check whether the CentraSite Server is up and running.

<b>INMWSE0025</b>	<b>Error while fetching organizations from CentraSite</b>
<b>Explanation</b>	A system error has occurred while fetching organizations from CentraSite. Perhaps the connection to the CentraSite Server has been lost.
<b>Action</b>	Please check whether the CentraSite Server is up and running.
<b>INMWSE0026</b>	<b>Invalid LCM states {0} are used in search filters</b>
<b>Explanation</b>	At least one lifecycle state provided in the search filter is not valid.
<b>Action</b>	Please provide proper lifecycle states in the search filter.
<b>INMWSE0027</b>	<b>Invalid file descriptor.</b>
<b>Explanation</b>	The value for file type was missing.
<b>Action</b>	Make sure the arguments are valid.
<b>INMWSE0028</b>	<b>The XPDL is not passed as FileDescriptor in the request</b>
<b>Explanation</b>	The request does not contain a file descriptor.
<b>Action</b>	Please pass the XPDL content as the file descriptor in the request.
<b>INMWSE0029</b>	<b>Specified organization key {0} is not valid</b>
<b>Explanation</b>	CentraSite does not contain an organization with the provided key.
<b>Action</b>	Please make sure the organization key provided in the request is valid.
<b>INMWSE0030</b>	<b>Specified product {0} is not valid</b>
<b>Explanation</b>	CentraSite does not contain the product concept with the specified key.
<b>Action</b>	Please make sure the product specified in the request is valid.
<b>INMWSE0031</b>	<b>Exception while fetching the properties from META-INFO</b>
<b>Explanation</b>	The user can provide attributes with values in the request. CentraSite is not able to fetch the properties from the provided META-INFO file descriptor.
<b>Action</b>	Please provide the properties in the format which is supported by CentraSite. Please refer <a href="http://localhost:53307/wsstack/services/Property.xsd">http://localhost:53307/wsstack/services/Property.xsd</a> for the CentraSite supported format. Please replace the host and port in the above URL accordingly.

<b>INMWSE0032</b>	<b>Referenced file {0} not found</b>
<b>Explanation</b>	The WSDL file to be imported imports another WSDL/XSD. But the other imported WSDL/XSD file was not passed to the WSDL importer service.
<b>Action</b>	Please create a file descriptor for the referenced WSDL/XSD file and send it to ImportWSDLService.
<b>INMWSE0033</b>	<b>Exception occurred while executing getApprovalHistory operation</b>
<b>Explanation</b>	An internal issue occurred while performing the getApprovalHistory operation. It might be a CentraSite issue or the data provided to the CentraSite is not sufficient.
<b>Action</b>	Please make sure the web service operation is executed with right set of parameters.
<b>INMWSE0034</b>	<b>Exception occurred while executing getPendingApprovals operation</b>
<b>Explanation</b>	An internal issue occurred while performing the getPendingApprovals operation. It might be a CentraSite issue or the data provided to the CentraSite is not sufficient.
<b>Action</b>	Please make sure the web service operation is executed with right set of parameters.
<b>INMWSE0035</b>	<b>Exception occurred while approving the approval flow using approve operation</b>
<b>Explanation</b>	An internal issue occurred while performing the approve operation. It might be a CentraSite issue or the data provided to the CentraSite is not sufficient.
<b>Action</b>	Please make sure the web service operation is executed with right set of parameters.
<b>INMWSE0036</b>	<b>Exception occurred while executing getApprovalRequests operation</b>
<b>Explanation</b>	An internal issue occurred while performing the getApprovalRequests operation. It might be a CentraSite issue or the data provided to the CentraSite is not sufficient.
<b>Action</b>	Please make sure the web service operation is executed with right set of parameters.
<b>INMWSE0037</b>	<b>Exception occurred while executing getApprovalActions operation</b>
<b>Explanation</b>	An internal issue occurred while performing the getApprovalActions operation. It might be a CentraSite issue or the data provided to the CentraSite is not sufficient.
<b>Action</b>	Please make sure the web service operation is executed with right set of parameters.
<b>INMWSE0038</b>	<b>Revert Pending State operation can only be performed by CentraSite Administrator</b>
<b>Explanation</b>	Not all users have permission to revert the pending state of a registry object. The user should have the CentraSite Administrator role to perform a revert pending state operation.
<b>Action</b>	Please provide the user with CentraSite Administrator role for the revert pending state operation.

<b>INMWSE0039</b>	<b>CentraSite does not contain a registry object with the specified key {0}.</b>
<b>Explanation</b>	The revert pending state operation requires a key of the registry object which exists in CentraSite. The pending state change cannot be reverted for a registry object that does not exist in CentraSite.
<b>Action</b>	Please make sure a registry object exists in CentraSite with the specified key.
<b>INMWSE0040</b>	<b>Exception occurred while executing revertPendingStateChange operation</b>
<b>Explanation</b>	An internal issue occurred while reverting a pending state change. It might be a CentraSite issue or the data provided to the CentraSite is not sufficient.
<b>Action</b>	Please make sure the web service operation is executed with right set of parameters.
<b>INMWSE0041</b>	<b>Exception occurred while executing reject operation</b>
<b>Explanation</b>	An internal issue occurred while performing the reject operation. It might be a CentraSite issue or the data provided to the CentraSite is not sufficient.
<b>Action</b>	Please make sure the web service operation is executed with right set of parameters.
<b>INMWSE0042</b>	<b>applicationServeKeyOrName parameter is missing in the request</b>
<b>Explanation</b>	This error happens when the user does not set the applicationServerKeyOrName in the request parameter.
<b>Action</b>	Set the applicationServerKeyOrName in the request parameter.
<b>INMWSE0043</b>	<b>serviceKey parameter is missing in the request message</b>
<b>Explanation</b>	This error happens when the user does not set serviceKey in the request parameter.
<b>Action</b>	Set the serviceKey in the request parameter.
<b>INMWSE0044</b>	<b>Invalid product {0} has been specified in the request</b>
<b>Explanation</b>	The value given as product parameter is invalid.
<b>Action</b>	Give a valid product name in the product parameter.
<b>INMWSE0045</b>	<b>Found {0} {1} application server instances during search. Use application server key to find unique instance.</b>
<b>Explanation</b>	This error happens if the search result matches more than one application server instance.
<b>Action</b>	Use the key to find a unique application server instance in the web service request operation.

<b>INMWSE0046</b>	<b>Failed to associate the given application server {0} and service {1}</b>
<b>Explanation</b>	This error may happen if the given CentraSite location is wrong or because of invalid credentials.
<b>Action</b>	Check the CentraSite location and its credentials. Also check if the application server instance exists.
<b>INMWSE0047</b>	<b>Invalid application server {0}</b>
<b>Explanation</b>	The given application server key or name is not valid.
<b>Action</b>	Give the correct application server key in the request parameter.
<b>INMWSE0048</b>	<b>Parameter name (serviceKeys) is mandatory input</b>
<b>Explanation</b>	The serviceKeys element is mandatory for the GetServiceDetails request.
<b>Action</b>	Specify at least one service key for the GetServiceDetails request.
<b>INMWSE0049</b>	<b>Error while retrieving service detail</b>
<b>Explanation</b>	Verify that the given request parameters are appropriate for the getServiceDetails call.
<b>Action</b>	Validate the parameters supplied for the getServiceDetails operation.
<b>INMWSE0050</b>	<b>Error while retrieving associated type for Lifecycle model {0}</b>
<b>Explanation</b>	An error occurred while retrieving an associated type for a lifecycle model.
<b>Action</b>	Verify that the associated types for the lifecycle model are appropriate.
<b>INMWSE0051</b>	<b>Error while retrieving transition state for the Lifecycle model {0}</b>
<b>Explanation</b>	An error occurred while retrieving the transition state for the lifecycle state and lifecycle model.
<b>Action</b>	Verify that the transition states are appropriate for the retrieved lifecycle state.
<b>INMWSE0052</b>	<b>Error while retrieving LC State for the LC Model {0}</b>
<b>Explanation</b>	An error occurred while retrieving a lifecycle state for the lifecycle model.
<b>Action</b>	Verify that the lifecycle states are appropriate for the retrieved lifecycle model.

<b>INMWSE0053</b>	<b>Error while retrieving LC Model {0}</b>
<b>Explanation</b>	An error occurred while retrieving the lifecycle model.
<b>Action</b>	Verify that the retrieved lifecycle model is correct.
<b>INMWSE0054</b>	<b>Failed to process getLifecycleModels operation</b>
<b>Explanation</b>	The getLifecycleModels operation could not be processed.
<b>Action</b>	Verify that the parameters are appropriately specified in the request.
<b>INMWSE0055</b>	<b>Error while registering the application server {0}</b>
<b>Explanation</b>	An error occurred while registering the application server.
<b>Action</b>	Verify that the parameters are appropriately specified in the request.
<b>INMWSE0056</b>	<b>Error while deregistering the application server</b>
<b>Explanation</b>	An error occurred while deregistering the application server.
<b>Action</b>	Verify that the parameters are appropriately specified in the request.
<b>INMWSE0057</b>	<b>Error while reading product version information</b>
<b>Explanation</b>	An error occurred while getting the application server version.
<b>Action</b>	Verify that the parameters are specified in the request.
<b>INMWSE0058</b>	<b>Error while retrieving installed language information from CentraSite</b>
<b>Explanation</b>	Error while retrieving installed language information from CentraSite.
<b>Action</b>	Validate the web service request or contact the CentraSite administrator.
<b>INMWSE0059</b>	<b>Invalid owner key {0} specified in request</b>
<b>Explanation</b>	The request XML contains an invalid owner key.
<b>Action</b>	Specify the appropriate owner key in the request XML.
<b>INMWSE0060</b>	<b>Invalid organization key {0} specified in request</b>
<b>Explanation</b>	The request contains an invalid organization key.
<b>Action</b>	Specify an appropriate organization key in the request.

<b>INMWSE0061</b>	<b>Invalid object type {0} specified in request</b>
<b>Explanation</b>	The request contains an invalid object type.
<b>Action</b>	Specify an appropriate object type string in the request.
<b>INMWSE0062</b>	<b>Object Type is mandatory when Organization Key is specified in request</b>
<b>Explanation</b>	The object type is mandatory when the organization key is specified in the request.
<b>Action</b>	Specify a valid object type string in the request.
<b>INMWSE0063</b>	<b>Service {0} is not available in organization {1}</b>
<b>Explanation</b>	The organization key specified for this service is not correct.
<b>Action</b>	Provide the correct organization key of this service.
<b>INMWSE0064</b>	<b>Invalid asset key {0} passed in the request</b>
<b>Explanation</b>	The request contains an invalid asset key.
<b>Action</b>	Pass a valid asset key in the request.
<b>INMWSE0065</b>	<b>Error while processing getAssociatedServices request</b>
<b>Explanation</b>	An error occurred while processing a getAssociatedServices request.
<b>Action</b>	Check if the given request parameters are correct.
<b>INMWSE0066</b>	<b>Error while processing releaseProcesses request</b>
<b>Explanation</b>	It was not possible to process the releaseProcesses request.
<b>Action</b>	Check if the given request parameters are correct.
<b>INMWSE0067</b>	<b>CentraSite does not contain an Application Server with the specified key or name {0}.</b>
<b>Explanation</b>	A CentraSite web service received a RegisterApplicationServer request with a key or name specified. The web service tried to update the object with the specified key or name, but the web service was not able to find any Application Server object with the specified key or name.
<b>Action</b>	Please check whether an Application Server object exists in CentraSite with the specified key or name. If an object exists in CentraSite, please make sure the requested user has view/edit permission on the Application Server object.

<b>INMWSE0068</b>	<b>Specified application server {0} does not exist</b>
<b>Explanation</b>	The application server name or key given in the request is not valid.
<b>Action</b>	Check the given application server name or key and correct it.
<b>INMWSE0073</b>	<b>Invalid application server key {0}</b>
<b>Explanation</b>	The request contains an invalid application server key.
<b>Action</b>	Specify a valid application server key.
<b>INMWSE0074</b>	<b>Exception while parsing XPDL file {0}</b>
<b>Explanation</b>	CentraSite will parse the specified XPDL file to create corresponding objects in CentraSite. CentraSite is not able to parse the specified the XPDL file as the given XPDL file does not comply with the XML and XPDL specification.
<b>Action</b>	Please make sure the specified XPDL file is in accordance with the XML and XPDL specification.
<b>INMWSE0075</b>	<b>The given organization key {0} in the request does not match the key of the existing asset's organization {1}</b>
<b>Explanation</b>	The organization key given in the importWSDL request does not match the organization key of the existing asset's organization.
<b>Action</b>	Provide the existing asset's organization key in the request.
<b>INMWSE0077</b>	<b>Failed to find application server in given name {0}.</b>
<b>Explanation</b>	This exception is unexpected. The cause is not immediately known.
<b>Action</b>	If the problem persists, contact CentraSite administrator.
<b>INMWSE0078</b>	<b>Application Server name is empty</b>
<b>Explanation</b>	No name was supplied for the application server.
<b>Action</b>	Provide a valid application server name.
<b>INMWSE0079</b>	<b>Unsupported Association Type {0}</b>
<b>Explanation</b>	The specified association type is not supported.
<b>Action</b>	Correct the association type.

<b>INMWSE0080</b>	<b>Check your access rights and proxy settings.</b>
<b>Explanation</b>	You do not have sufficient privileges to access the target object.
<b>Action</b>	Execute the action with sufficient privileges.
<b>INMWSE0081</b>	<b>The {0} parameter value is null.</b>
<b>Explanation</b>	The function shown on the call stack is called with a null value.
<b>Action</b>	Correct the client program.
<b>INMWSE0082</b>	<b>The credentials parameter value is null.</b>
<b>Explanation</b>	The setCredentials() method is called with a null value for the credentials parameter.
<b>Action</b>	Correct the client program.
<b>INMWSE0083</b>	<b>Specified process {0} is unavailable.</b>
<b>Explanation</b>	Process with the specified asset ID is not available.
<b>Action</b>	Check the asset ID provided in the request.
<b>INMWSI0069</b>	<b>Asset {0} is already associated with the server {1}</b>
<b>Explanation</b>	The given asset key request is already associated with the specified application server.
<b>Action</b>	Remove the asset key from the request.
<b>INMWSI0070</b>	<b>Asset {0} has been associated with the server {1} successfully</b>
<b>Explanation</b>	The asset {0} has been associated with the server {1} successfully.
<b>Action</b>	The association between the asset key and the server was created successfully.
<b>INMWSI0071</b>	<b>The asset {0} has not been associated with the server {1}</b>
<b>Explanation</b>	The asset is not associated with the specified server.
<b>Action</b>	Associate the asset and the server first before disassociating.
<b>INMWSI0072</b>	<b>Asset {0} has been disassociated from the server {1} successfully</b>
<b>Explanation</b>	The given asset has been disassociated from the server successfully.
<b>Action</b>	The given asset has been disassociated from the server successfully.

<b>INMWSI0076</b>	<b>Application server does not exist for given name {0}.</b>
<b>Explanation</b>	An application server does not exist in the given name.
<b>Action</b>	Create an application server in the given name.
<b>INOQJE0001</b>	<b>XQConnection for {0} is closed!</b>
<b>Explanation</b>	The connection to the specified database is closed.
<b>Action</b>	Make sure that the connection in use is not closed prior to any later operation.
<b>INOQJE0002</b>	<b>XQExpression is closed!</b>
<b>Explanation</b>	The underlying expression is already closed.
<b>Action</b>	Make sure that the expression / connection in use is not closed prior to any later operation.
<b>INOQJE0003</b>	<b>XQItemType mismatch! Item is not of type {0}.</b>
<b>Explanation</b>	The specified item is not of the declared item type.
<b>Action</b>	Check for the compatibility of item types.
<b>INOQJE0004</b>	<b>No cursor handle given!</b>
<b>Explanation</b>	The cursor associated with the query handle was not found.
<b>Action</b>	This happens if there is no proper result set associated with the specified query.
<b>INOQJE0005</b>	<b>Error reading from file - {0}</b>
<b>Explanation</b>	This exception is thrown by the Java run-time architecture when an input error has occurred while reading from the specified file.
<b>Action</b>	Possible causes for this exception are an error reading from the specified file or the specified file is not found.
<b>INOQJE0006</b>	<b>Error while parsing the XMLStream - {0}</b>
<b>Explanation</b>	This is an error for unexpected errors during processing / XML handling, namely, to report well-formedness errors as well as unexpected processing conditions.
<b>Action</b>	The error message contains the explanation from the StAX parser. Modify the XML accordingly.

<b>INOQJE0007</b>	<b>Parser configuration error - {0}</b>
<b>Explanation</b>	Indicates a serious configuration error. An exception occurred during configuration of the XML parser being used.
<b>Action</b>	Add the corresponding XML parser jars in the CLASSPATH.
<b>INOQJE0008</b>	<b>Factory Configuration Error - {0}</b>
<b>Explanation</b>	A problem with configuration of the Parser Factories exists. This error will typically be thrown when the class of a parser factory specified in the system properties cannot be found or instantiated.
<b>Action</b>	Add the XML parser jars to the CLASSPATH and set the JAXP factory names.
<b>INOQJE0009</b>	<b>Cannot access the XQItem of type XQITEMTYPE_ATTRIBUTE</b>
<b>Explanation</b>	Indicates that the base item type of the current item is an attribute while writing the current item to a SAX stream.
<b>Action</b>	The current item should not be of type attribute.
<b>INOQJE0010</b>	<b>SAX Parse Error - {0}</b>
<b>Explanation</b>	Represents a general SAX error or warning.
<b>Action</b>	Possible causes for this error are if the value of the "org.xml.sax.driver" system property is null or the class cannot be loaded and instantiated.
<b>INOQJE0011</b>	<b>I/O Error - {0}</b>
<b>Explanation</b>	This exception is thrown by the Java run-time architecture when an input / output error of some kind has occurred while reading from the specified input source.
<b>Action</b>	Refer to the Java documentation for the error message.
<b>INOQJE0012</b>	<b>End of the sequence is reached</b>
<b>Explanation</b>	Execution of an XQuery returns a sequence of results. You can traverse the sequence of results using the XQResultSequence API.
<b>Action</b>	Reading or trying to modify items in the sequence after reaching the end of the sequence will result in this error.

---

<b>INOQJE0013</b>	<b>Positioned before the start of the sequence</b>
<b>Explanation</b>	Execution of an XQuery returns a sequence of results. You can traverse the sequence of results using the XQResultSequence API. Invoking the next() method for the first time will get to the first item in the sequence. If any operations are tried before this, this will result in this error.
<b>Action</b>	Invoke the next() method to get the first item.
<b>INOQJE0014</b>	<b>Server {0} unavailable</b>
<b>Explanation</b>	The specified database or server is not running.
<b>Action</b>	Provide the correct database URL, and check if the database is stopped.
<b>INOQJE0015</b>	<b>Error when attempting to change the transaction mode</b>
<b>Explanation</b>	The attempt to change the transaction mode failed.
<b>Action</b>	Check the Server documentation for the specified error code in the error message.
<b>INOQJE0016</b>	<b>Error closing the {0}</b>
<b>Explanation</b>	An attempt to close the underlying connection or result sequence that is specified along with the error failed.
<b>Action</b>	Make sure that the underlying connection is not closed before closing the result sequence.
<b>INOQJE0017</b>	<b>Transaction failed while committing the changes</b>
<b>Explanation</b>	Committing the changes failed.
<b>Action</b>	Check the Server documentation for the specified error code in the error message.
<b>INOQJE0018</b>	<b>Transaction failed while rolling back the changes</b>
<b>Explanation</b>	Rolling back the changes failed.
<b>Action</b>	Check the Server documentation for the specified error code in the error message.
<b>INOQJE0019</b>	<b>The scrollability type {0} is not supported</b>
<b>Explanation</b>	The mentioned scrollability type is not supported.
<b>Action</b>	Set a valid value for the scrollability type.

<b>INOQJE0020</b>	<b>The property {0} is not supported</b>
<b>Explanation</b>	The mentioned property is not supported.
<b>Action</b>	Provide a valid property.
<b>INOQJE0021</b>	<b>A property mentioned in the list is not supported</b>
<b>Explanation</b>	One of the mentioned properties in the property list is not supported.
<b>Action</b>	Check if all the properties in the property list are supported by the current implementation.
<b>INOQJE0022</b>	<b>Error executing the server command : {0}</b>
<b>Explanation</b>	An error occurred while executing the specified database command.
<b>Action</b>	Please refer to the documentation of the specified command.
<b>INOQJE0023</b>	<b>XQTypeException thrown - Error Code : {0} Message : {1}</b>
<b>Explanation</b>	External variable binding to XQuery failed.
<b>Action</b>	Check the server documentation for the error code displayed in the error.
<b>INOQJE0024</b>	<b>Error fetching cursor</b>
<b>Explanation</b>	Indicates a cursor based failure when fetching a number of documents from a cursor.
<b>Action</b>	Check the server documentation for the error code displayed in the error.
<b>INOQJE0025</b>	<b>XQuery exception: {0}</b>
<b>Explanation</b>	Error in the XQuery.
<b>Action</b>	Please check the XQuery for errors.
<b>INOQJE0026</b>	<b>Error while opening cursor</b>
<b>Explanation</b>	Indicates a failure when opening a cursor.
<b>Action</b>	Check the server documentation for the error code displayed in the error.
<b>INOQJE0027</b>	<b>Error executing XQuery {0}: {1}</b>
<b>Explanation</b>	Executing the XQuery failed. See the error code for more information.
<b>Action</b>	Check the server documentation for the error code displayed in the error.

<b>INOQJE0028</b>	<b>Sequence is non-scrollable</b>
<b>Explanation</b>	Cannot scroll on a non-scrollable sequence.
<b>Action</b>	Avoid scrolling, because the sequence is non-scrollable.
<b>INOQJE0029</b>	<b>Failed because of following exception</b>
<b>Explanation</b>	The cause of the exception is specified in the error message.
<b>Action</b>	Check the server documentation for the specified error code in the error message.
<b>INOQJE0030</b>	<b>Error creating the cached item</b>
<b>Explanation</b>	Creating a cached item failed.
<b>Action</b>	Check if the items are closed.
<b>INOQJE0031</b>	<b>Error binding the {0} Message - {1}</b>
<b>Explanation</b>	Binding the specified value to the expression / prepared expression failed.
<b>Action</b>	Check if the values declared and bound to the query are the same.
<b>INOQJE0032</b>	<b>Error executing the request with error [{0} {1} {2} {3}]</b>
<b>Explanation</b>	The message appears with the specific error code and information from the server.
<b>Action</b>	Refer to the server documentation for the specified error code.
<b>INOQJE0033</b>	<b>Sequence not scrollable</b>
<b>Explanation</b>	Cannot scroll a non scrollable sequence.
<b>Action</b>	Avoid scrolling, because the sequence is non-scrollable.
<b>INOQJE0034</b>	<b>Expected type {0} Current type {1} Location {2}</b>
<b>Explanation</b>	The expected type and the current type specified do not match.
<b>Action</b>	Check the types mentioned in the error at the specified location.
<b>INOQJE0035</b>	<b>Expected start or end tag {0}</b>
<b>Explanation</b>	When trying to move to the next tag in the resulting XML Stream, any white space , COMMENT, or PROCESSING_INSTRUCTION is skipped until a START_ELEMENT or END_ELEMENT is reached. If anything other than white space characters, COMMENT, PROCESSING_INSTRUCTION, START_ELEMENT, END_ELEMENT is encountered, this error is thrown along with the location number.
<b>Action</b>	Check the error message for the missing start or end in the XML.

<b>INOQJE0036</b>	<b>{0} cannot be null!</b>
<b>Explanation</b>	The underlying object specified is null.
<b>Action</b>	Make sure that the underlying object is properly initialized.
<b>INOQJE0037</b>	<b>The {0} method is not supported</b>
<b>Explanation</b>	The method specified in the error message is not supported.
<b>Action</b>	The specified method is not supported by the current XQJ implementation.
<b>INOQJE0038</b>	<b>XQPreparedExpression is closed!</b>
<b>Explanation</b>	The underlying prepared expression is already closed.
<b>Action</b>	Make sure that the XQPreparedExpression is not closed before any usage.
<b>INOQJE0039</b>	<b>XQSequence is closed!</b>
<b>Explanation</b>	The underlying sequence is already closed.
<b>Action</b>	Make sure that the XQSequence is not closed before any usage.
<b>INOQJE0040</b>	<b>XQItem is closed!</b>
<b>Explanation</b>	The underlying item is already closed.
<b>Action</b>	Make sure that the XQItem is not closed before any usage.
<b>INOQJE0041</b>	<b>The value for the property {0} cannot be null</b>
<b>Explanation</b>	The value for the specified property in the error message cannot be null.
<b>Action</b>	Mention a property value for the specified property name in the error message.
<b>INOQJE0042</b>	<b>Access Failure Exception - {0}</b>
<b>Explanation</b>	The cause for the exception is specified in the error message.
<b>Action</b>	Check the server documentation for the specified error code in the error message.
<b>INOQJE0043</b>	<b>Invalid user ID or password</b>
<b>Explanation</b>	The supplied user ID and password combination is invalid.
<b>Action</b>	Check the user ID and password.

<b>INOQJE0044</b>	<b>Cannot access the XQItem of type XQITEMKIND_ATTRIBUTE</b>
<b>Explanation</b>	This indicates that the item kind of the current item is an attribute while writing the current item to a SAX stream.
<b>Action</b>	The current item should not be of type attribute.
<b>INOQJE0045</b>	<b>Error creating the XQ item</b>
<b>Explanation</b>	An error occurred while creating an XQ item.
<b>Action</b>	Check if the items are closed.
<b>INOQJE0046</b>	<b>Binding to {0} not supported</b>
<b>Explanation</b>	While binding an external variable to an XQuery, the type specification was not valid. Either the type is not supported at all for binding external variables, or it was used with a binding method that does not support this specific type.
<b>Action</b>	Use one of the supported types with a proper binding method.
<b>UDDIE00002</b>	<b>No businessKey was defined</b>
<b>Explanation</b>	Keys have to be specified to fetch the details.
<b>Action</b>	Please provide keys in the UDDI request to fetch the details.
<b>UDDIE00005</b>	<b>At least keyBag or transferToken should be specified</b>
<b>Explanation</b>	The discard_transferToken request is not valid. It has to be according to the UDDI v3 specification.
<b>Action</b>	Please specify transferToken to discard it.
<b>UDDIE00006</b>	<b>The value of the attribute maxRows is not a valid number.</b>
<b>Explanation</b>	The value for the maxRows attribute in the UDDI request should be a number.
<b>Action</b>	Please specify an integer value for the maxRows attribute in the UDDI request.
<b>UDDIE00007</b>	<b>{0} is not a valid find qualifier value in version {1}.</b>
<b>Explanation</b>	The find qualifier is not supported in the specified version.
<b>Action</b>	Please specify find qualifiers corresponding to the UDDI version.

<b>UDDIE00008</b>	<b>No entityKey was defined</b>
<b>Explanation</b>	Keys have to be specified to fetch the operationa info.
<b>Action</b>	Please provide keys in the get_operationalInfo request to fetch the operational information.
<b>UDDIE00011</b>	<b>Publisher assertions are null</b>
<b>Explanation</b>	The add_publisherAssertions, delete_publisherAssertions and set_publisherAssertions requests should have publisher assertions in them.
<b>Action</b>	Please add the publisherAssertions element in add_publisherAssertions, delete_publisherAssertions and set_publisherAssertions requests.
<b>UDDIE00012</b>	<b>Exactly one BusinessKey must be defined.</b>
<b>Explanation</b>	Either fromKey, toKey or businessKey should be specified.
<b>Action</b>	Please specify a value for the toKey or fromKey or businessKey attribute of the find_relatedBusiness call.
<b>UDDIE00013</b>	<b>Only one keyedReference element may be defined in a find_relatedBusinesses message.</b>
<b>Explanation</b>	The publisher assertion should contain only one keyedReference element.
<b>Action</b>	Please provide one KeyedReference in the find_relatedBusiness call.
<b>UDDIE00014</b>	<b>{0} is not a valid UUID.</b>
<b>Explanation</b>	The specified key is not valid.
<b>Action</b>	Please make sure the key is valid according to the UDDI standard.
<b>UDDIE00015</b>	<b>The specified names are not valid for version</b>
<b>Explanation</b>	The names are not specified according to the UDDI specification.
<b>Action</b>	Please specify valid names.
<b>UDDIE00016</b>	<b>Only one key may be defined</b>
<b>Explanation</b>	Multiple keys are defined for the UDDI entity.
<b>Action</b>	Please specify a single key for the UDDI entity.

<b>UDDIE00017</b>	<b>The fromKey element is mandatory in a publisherAssertion document</b>
<b>Explanation</b>	The fromKey element does not contain a valid value.
<b>Action</b>	Please provide values for the fromKey element in the publisherAssertion element.
<b>UDDIE00018</b>	<b>The toKey element is mandatory in a publisherAssertion document</b>
<b>Explanation</b>	The toKey element does not contain valid value.
<b>Action</b>	Please provide values for the toKey element in the publisherAssertion element.
<b>UDDIE00019</b>	<b>The keyedReference element is mandatory in a publisherAssertion document</b>
<b>Explanation</b>	The keyedReference element does not contain valid value.
<b>Action</b>	Please provide values for the keyedReference element in the publisher assertion element.
<b>UDDIE00020</b>	<b>The keyedReference element in a publisherAssertion must be defined exactly one time</b>
<b>Explanation</b>	The publisher assertion should contain only one keyedReference element.
<b>Action</b>	Please provide one KeyedReference in the publisher assertion element.
<b>UDDIE00022</b>	<b>{0} is not a valid findQualifier value</b>
<b>Explanation</b>	Provided findQualifier is not valid. The valid qualifiers can be found in UDDI specification.
<b>Action</b>	Please provide findQualifiers according to the UDDI specification
<b>UDDIE00024</b>	<b>The string representation may not be empty.</b>
<b>Explanation</b>	A value for the element in the UDDI request is not according to the UDDI specification.
<b>Action</b>	Please make sure the UDDI request is valid according to UDDI specification.
<b>UDDIE00025</b>	<b>A tag of the language code must have at least one character and no more than eight characters.</b>
<b>Explanation</b>	A value for the language code in the UDDI request does not comply with the UDDI specification.
<b>Action</b>	Please make sure the UDDI request is valid according to UDDI specification.

<b>UDDIE00026</b>	<b>A language code may only contain ASCII alphanumerics.</b>
<b>Explanation</b>	A value for the language code in the UDDI request does not comply with the UDDI specification.
<b>Action</b>	Please make sure the UDDI request is valid according to UDDI specification.
<b>UDDIE00027</b>	<b>Could not authenticate the user {0}</b>
<b>Explanation</b>	The user specified in the UDDI request is not valid.
<b>Action</b>	Please specify a valid CentraSite user.
<b>UDDIE00042</b>	<b>{0} does not represent a businessKey.</b>
<b>Explanation</b>	CentraSite does not contain any business entity with the specified key.
<b>Action</b>	Please make sure the business key specified in the request is valid.
<b>UDDIE00043</b>	<b>No businessKey in the registry matches the key {0}.</b>
<b>Explanation</b>	CentraSite does not contain any business entity with the specified key.
<b>Action</b>	Please make sure the business key specified in the request is valid.
<b>UDDIE00045</b>	<b>No entity in the registry matches the key {0}.</b>
<b>Explanation</b>	CentraSite does not contain any UDDI entity with the specified key.
<b>Action</b>	Please make sure the key specified in the request is valid.
<b>UDDIE00047</b>	<b>The value of maxRows parameter is not a valid number.</b>
<b>Explanation</b>	The value for the maxRows attribute in the UDDI request should be a number.
<b>Action</b>	Please specify an integer value for the maxRows attribute in the UDDI request.
<b>UDDIE00049</b>	<b>The contact {0} already exists. Please specify a different contact.</b>
<b>Explanation</b>	The specified contact already exists in the CentraSite. A contact cannot be present in multiple businesses
<b>Action</b>	Please make sure the contact is not present in any other business
<b>UDDIE00050</b>	<b>The value of maxEntities parameter is not valid</b>
<b>Explanation</b>	The maxEntities attribute of the subscription should contain an valid non-negative number.
<b>Action</b>	Please provide valid non-negative number for the maxEntities attribute.

**uddi:107e04bd-bdf4-11e2-b6b3-c566c3aaf997 – Verify Required Attributes**

**Explanation**            During asset instance creation and modification, verifies whether the required attributes of that Asset Type are provided with values

**uddi:18bf0e3d-bdf4-11e2-b6b3-886f1ce73523 – Verify Required Attributes Policy**

**Explanation**            During asset instance creation and modification, this policy verifies whether the required attributes of that Asset Type are provided with values.

**uddi:44e3e2de-064c-432f-b67a-8fbca0fb04d6 – Invoke webMethods Integration Server**

**Explanation**            Processing steps calling an Integration Server (IS) Service which will be executed when the consumer invokes the Virtual Service.



# 7 CloudStreams Messages

---

<b>0010.0715E</b>	<b>CloudStreams Upgrade, did not complete successfully.</b>
<b>Explanation</b>	This log message may occur when the CloudStreams package loads during the Integration Server restart after an overinstall. This message indicates the upgrade was not successful. There should be a previous error message in the server log that indicates the problem.
<b>Action</b>	See actions for message ID '0010.0702'
<b>0030.0099</b>	<b>PublisherPropsObserver - Unknown wrapper factory data type ({0})</b>
<b>Explanation</b>	This message has incorrect text. It should indicate an invalid data type for UDDP publisher bean.
<b>Action</b>	Update the pg configuration file to use a proper UDDI publisher data type.
<b>0030.0100</b>	<b>PublisherPropsObserver - Unable to find wrapper factory</b>
<b>Explanation</b>	There is no UDDI publisher configured, but its properties are being changed.
<b>Action</b>	Update the configuration file. Either configure a UDDI publisher or unregister the UDDI properties observer.
<b>0030.0109</b>	<b>PublisherPropsObserver - Can't convert string ({0}) to integer for publishing interval, ignoring input</b>
<b>Explanation</b>	The value received for performance data reporting interval was not a valid numeric string.
<b>Action</b>	Make sure a numeric value is input.

<b>0030.0113</b>	<b>PublisherPropsObserver - Unknown pg service deployer data type {{0}}</b>
<b>Explanation</b>	The data type of the PG Service Deployer bean is invalid.
<b>Action</b>	Update the pg configuration file to use a proper PG Service Deployer data type.
<b>0030.0301</b>	<b>ConsumerApplicationManager.convert - cannot handle null request</b>
<b>Explanation</b>	Unable to create Consumer deployment object for update.
<b>Action</b>	Probably bad SOAP request to Deployer, fix request.
<b>0030.0302</b>	<b>ConsumerApplicationManager.convert - cannot convert consumer with null {0}</b>
<b>Explanation</b>	Invalid Consumer deployment object was found.
<b>Action</b>	Probably bad SOAP request to Deployer, fix request.
<b>0030.0303</b>	<b>VirtualServiceDeployer.{0} - cannot handle null {1}</b>
<b>Explanation</b>	A null reference was found during a deployment activity. The object and activity are identified in the message.
<b>Action</b>	Probably bad SOAP request for deployment, fix request.
<b>0030.0304</b>	<b>VirtualServiceDeployer.deploy - service {{0}} already deployed, undeploying</b>
<b>Action</b>	Info level message, no action required.
<b>0030.0306</b>	<b>VirtualServiceDeployer.{0} - caught this: type({1}) message({2})</b>
<b>Explanation</b>	Unable to deploy virtual service. See exception message for more details.
<b>Action</b>	Address the problem indicated by exception and try to deploy again.
<b>0030.0309</b>	<b>ClusteredServiceDeployer{0} - cannot handle null {1}</b>
<b>Explanation</b>	Unable to create VS deployment object for update.
<b>Action</b>	Probably bad SOAP request to Deployer, fix request.
<b>0030.0315</b>	<b>ClusteredConsumerManager.updateConsumer - cannot handle null consumer</b>
<b>Explanation</b>	Unable to create Consumer object for update.
<b>Action</b>	Probably bad SOAP request to Deployer, fix request.

---

<b>0030.0318</b>	<b>ClusteredServiceDeployer - cannot deploy null info to cache</b>
<b>Explanation</b>	A problem occurred while attempting to convert a PGService for deployment to shared cache. There should be another message describing the conversion or deployment issue.
<b>Action</b>	Fix the conversion or deployment problem.
<b>0030.0319</b>	<b>ClusteredServiceDeployer - cannot undeploy null service name from cache</b>
<b>Explanation</b>	Virtual service undeployment requires a non-empty service name. This is problem with undeployment request payload.
<b>Action</b>	Fix the undeployment request payload.
<b>0030.0328</b>	<b>ConsumerApplicationManager.{0} - cannot handle null update request</b>
<b>Explanation</b>	Invalid Consumer deployment request for update.
<b>Action</b>	Probably bad SOAP request to Deployer, fix request.
<b>0030.0330</b>	<b>ConsumerApplicationManager - not updating consumer ({0}), modification date, ({1}), is no more recent</b>
<b>Action</b>	Info level message, no action required.
<b>0030.0333</b>	<b>ConsumerApplicationManager.{0} - caught this: type({1}) message({2})</b>
<b>Explanation</b>	Unable to create and persist Consumer object for update.
<b>Action</b>	Either bad SOAP request to Deployer, fix Request. Or file system problem, check file system permissions. See logged message text for specific error details.
<b>0030.0336</b>	<b>Consumer Application Update Failed; requested update has invalid {0} field</b>
<b>Explanation</b>	Invalid consumer name or key in remove request.
<b>Action</b>	Probably bad SOAP request to Deployer, fix request.
<b>0030.0337</b>	<b>Consumer Application Remove Failed; consumer ({0}) does not exist</b>
<b>Explanation</b>	Attempt to remove consumer failed.
<b>Action</b>	Reply to CentraSite Deployment attemp should indicate error. Try redeploying this consumer or resynchronizing all consumers.

<b>0030.0343</b>	<b>RegisteredConsumerNamesManager.{0} - cannot handle null update request</b>
<b>Explanation</b>	Invalid RegisteredConsumerNames deployment request for update.
<b>Action</b>	Probably bad SOAP request to Deployer, fix request.
<b>0030.0344</b>	<b>Registered Consumer Names Update Failed; requested update has invalid {0} field</b>
<b>Explanation</b>	Invalid service name or consumer names in registered consumer names update request.
<b>Action</b>	Probably bad SOAP request to Deployer, fix request.
<b>0030.0346</b>	<b>RegisteredConsumerNamesManager - not updating consumer names registered to ({0}), modification date, ({1}), is no more recent</b>
<b>Action</b>	Info level message, no action required.
<b>0030.0347</b>	<b>RegisteredConsumerNamesManager.{0} - cannot handle null update request</b>
<b>Explanation</b>	Invalid RegisteredConsumerNames deployment request for remove.
<b>Action</b>	Probably bad SOAP request to Deployer, fix request.
<b>0030.0348</b>	<b>Registered Consumer Names Remove Failed; requested update has invalid {0} field</b>
<b>Explanation</b>	Invalid service consumer name in remove request.
<b>Action</b>	Probably bad SOAP request to Deployer, fix request.
<b>0030.0350</b>	<b>Registered Consumer Names Remove Failed; service ({0}) has no registered consumers</b>
<b>Explanation</b>	Invalid request to remove RegisteredConsumerNames, must include at least one consumer name.
<b>Action</b>	Probably bad SOAP request to Deployer, fix request.
<b>0030.0352</b>	<b>RegisteredConsumerNamesManager.{0} - caught this: type({1}) message({2})</b>
<b>Explanation</b>	Unable to create and persist RegisteredConsumerNames object for update.
<b>Action</b>	Either bad SOAP request to Deployer, fix Request. Or file system problem, check file system permissions. See logged message text for specific error details.

---

0030.0356	<b>VirtualServiceDeployer - unable to get endpoints for {0}, caught this: type({1}), msg({2})</b>
<b>Explanation</b>	Unable to obtain endpoint for deployed service.
<b>Action</b>	Probably bad SOAP request to Deployer or bad VSD, fix one or both.
0030.0357	<b>ClusteredRegisteredConsumerNamesDeployer.updateConsumerNames - cannot handle null reg names object</b>
<b>Explanation</b>	Unable to create RegisteredConsumerNames object for update.
<b>Action</b>	Probably bad SOAP request to Deployer, fix request.
0030.0358	<b>Consumer Application Remove Failed; requested update has invalid name and key fields, both are empty</b>
<b>Explanation</b>	Consumer remove request must have either name or key to identify consumer; both were null or empty.
<b>Action</b>	Probably bad SOAP request to Deployer, fix request.
0030.0359	<b>ConsumerApplicationManager - Consumer update request has invalid IP range; from ({0}) to ({1})</b>
<b>Explanation</b>	Consumer update request had invalid IP address range.
<b>Action</b>	Probably bad SOAP request to Deployer, fix request.
0030.0361	<b>VirtualServiceDeployer - redeploying undeployed service ({0}), deployment failed for newer version</b>
<b>Action</b>	Info level message, no action required.
0030.0362	<b>VirtualServiceDeployer - a problem was encountered during deployment, ({0}) will be undeployed and replaced if necessary</b>
<b>Action</b>	Info level message, no action required.
0030.0363	<b>VirtualServiceDeployer.{0} - service({1}) caught this: type({2}) message({3})</b>
<b>Explanation</b>	Message context encountered an exception while attempting to redeploy or undeploy a virtual service. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.

<b>0030.0364</b>	<b>Deployment request for service: {0}. Registered consumer name element was processed, but the existing modification date is the same as the request. {1}</b>
<b>Action</b>	Info level message, no action required.
<b>0030.0366</b>	<b>UddiPropertiesObserver - Password lookup failed; type ({0}), message ({1})</b>
<b>Explanation</b>	A problem was encountered by attempting to retrieve stored password. There should be an exception with more specific trouble description.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0030.0367</b>	<b>UddiPropertiesObserver - Unable to activate performance data policies; type ({0}), message ({1})</b>
<b>Explanation</b>	The performance data deployer was unable to run. This message should include more details regarding the reason.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0030.0370</b>	<b>UddiPropertiesObserver - Unable to connect to UDDI: ({0}); property updates saved, but data collection is OFF.</b>
<b>Explanation</b>	A problem was encountered during publisher test.
<b>Action</b>	This is probably a bad configuration parameter, fix it.
<b>0030.0371</b>	<b>UddiPropertiesObserver - Unable to convert port string ({0}) to integer, using default port {1}</b>
<b>Explanation</b>	The value input for 'UDDI port' number is non-numeric.
<b>Action</b>	Input an numeric port value.
<b>0050.0001</b>	<b>Unable to find Policy Element in the VSD:{0}</b>
<b>Explanation</b>	An exception was encountered while attempting to extract a policy element from VSD. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0002</b>	<b>Unable to create Rampart properties:{0}</b>
<b>Explanation</b>	An exception was encountered while attempting to assemble Rampart keystore properties. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.

---

<b>0050.0003</b>	<b>Unable to replace static Rampart configuration with configured properties:{0}</b>
<b>Explanation</b>	An exception was encountered while attempting to re-configure Rampart keystore properties. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0004</b>	<b>Unable to create Rampart Configuration Element:{0}</b>
<b>Explanation</b>	An exception was encountered while attempting to convert Rampart configuration string to XML. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0005</b>	<b>Unable to create XPath to select first Policy Alternative:{0}</b>
<b>Explanation</b>	An exception was encountered while attempting to create an Xpath object. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0006</b>	<b>Error while removing existing RampartConfig elements:{0}</b>
<b>Explanation</b>	An exception was encountered while attempting to remove configuration elements. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0007</b>	<b>Required configuration information to enable WS-Security processing is missing. Unable to process service: {0}. Please ensure Keystore/Truststore information is configured</b>
<b>Explanation</b>	Service could not be initialized due to a problem with keystore/trustore configuration.
<b>Action</b>	Fix the security configuration.
<b>0050.0011</b>	<b>Exception while determining hostname or IP address of the server:{0}</b>
<b>Explanation</b>	An exception was encountered while attempting to resolve a host name or IP address. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.

<b>0050.0013</b>	<b>CloudStreams needs the repository location of the SOAP stack</b>
<b>Explanation</b>	Configuration does not include a valid location for Axis2 repository configuration.
<b>Action</b>	Fix the axis2 configuration.
<b>0050.0016</b>	<b>ServerManager ready for processing</b>
<b>Action</b>	Info level message, no action required.
<b>0050.0017</b>	<b>CloudStreams encountered exception while starting ServerManager:{0}</b>
<b>Explanation</b>	An exception was encountered during configuration of Axis2 listeners. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0018</b>	<b>Invalid Port specified. Using default configuration: {0}</b>
<b>Explanation</b>	The 'port' property has a non-numeric string value, the value configured in Axis is used.
<b>Action</b>	Make sure the property value to numeric.
<b>0050.0019</b>	<b>Port {0} is already in use. Trying alternate</b>
<b>Explanation</b>	The port indicated in the message is not available to use with a new socket.
<b>Action</b>	Specify another port value in the system 'port' property or Axis configuration.
<b>0050.0020</b>	<b>Exception while creating "id" selection XPath: {0}</b>
<b>Explanation</b>	Message context encountered an exception while attempting to create an XPath object. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0021</b>	<b>Found Element within Resources element with id: {0}</b>
<b>Action</b>	Info level message, no action required.
<b>0050.0022</b>	<b>Exception while selecting element with id:{0} in Resources Element: {1}</b>
<b>Explanation</b>	Message context encountered an exception while attempting to extract the indicated element from XML. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.

---

<b>0050.0023</b>	<b>CloudStreams received a response for the request with message Id :{0} But a callback is not registered (anymore) to process this response</b>
<b>Explanation</b>	No callback was registered at the time this response was processed.
<b>Action</b>	This is probably a VS configuration problem.
<b>0050.0024</b>	<b>CloudStreams received a response message without a message Id</b>
<b>Explanation</b>	There was a problem relating the native service response to a virtual service request.
<b>Action</b>	Look for previously logged message indicating that message Id was not used.
<b>0050.0025</b>	<b>CloudStreams encountered an exception: {0}. No error handlers found - [Message Dropped]</b>
<b>Explanation</b>	This could be a configuration problem. An exception was encountered while attempting to handle a fault. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the configuration, or other problem identified by the exception message.
<b>0050.0026</b>	<b>Outbound client can't locate policy from the property :{0}</b>
<b>Explanation</b>	The Synapse message context does not contain an entry for theproperty key identified in the message.
<b>Action</b>	This is a policy configuration problem.
<b>0050.0027</b>	<b>CloudStreams outbound client encountered error:{0}</b>
<b>Explanation</b>	Client encountered an exception while attempting to send a message. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0029</b>	<b>VSD with incorrect Namespace:{0}. Unable to create PGService.</b>
<b>Explanation</b>	The namespace found in the VSD is unknown.
<b>Action</b>	This is a virtual service configuration problem.
<b>0050.0031</b>	<b>The {0} element is required for a CloudStreams service</b>
<b>Explanation</b>	Some element used during service deployment was found to be null. The specific element should be identified in the message text.
<b>Action</b>	This is a virtual service configuration problem.

<b>0050.0032</b>	<b>The {0} sequence element is required for a CloudStreams service</b>
<b>Explanation</b>	The VSD is missing the sequence element identified in the message.
<b>Action</b>	This is a virtual service configuration problem.
<b>0050.0033</b>	<b>The inSequence for VSD:{0} is invalid.</b>
<b>Explanation</b>	The sequence identified in the message failed validation. Look for recent error message with more validation failure details.
<b>Action</b>	This is a virtual service configuration problem.
<b>0050.0034</b>	<b>The outSequence for VSD:{0} is invalid.</b>
<b>Explanation</b>	The sequence identified in the message failed validation. Look for recent error message with more validation failure details.
<b>Action</b>	This is a virtual service configuration problem.
<b>0050.0035</b>	<b>Exception while parsing Virtual Service String Definition:{0}</b>
<b>Explanation</b>	An exception was encountered while attempting to parse the virtual service description. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0036</b>	<b>Unable to create Virtual Service Definition</b>
<b>Explanation</b>	Unable to create XML object from the VSD string.
<b>Action</b>	This is a virtual service configuration or deployment problem.
<b>0050.0037</b>	<b>PGServiceFactory encountered and exception while creating the PGService: {0}</b>
<b>Explanation</b>	An exception was encountered while attempting to validate input or output sequence or during WSDL URI processing. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0038</b>	<b>Invalid parameter specified for PGService: {0}</b>
<b>Explanation</b>	The attribute named in the message has no value in the VSD.
<b>Action</b>	This is a virtual service configuration problem.

---

<b>0050.0039</b>	<b>Exception {0} for PGService: {1}</b>
<b>Explanation</b>	An exception was encountered while attempting during service creation. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0040</b>	<b>No PGService found with name: {0}</b>
<b>Explanation</b>	Attempting to undeploy or get endpoints for a service that does not exist.
<b>Action</b>	Make sure the virtual service exists before operating on it.
<b>0050.0041</b>	<b>WSStack exception processing service: {0} Cause: {1}</b>
<b>Explanation</b>	An AxisFault was encountered while attempting to either undeploy or get endpoints for the virtual service named in the message. The associated fault message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the fault message.
<b>0050.0042</b>	<b>Unable to locate the WSStack configuration. Can't deploy Virtual Service:{0}</b>
<b>Explanation</b>	The Synapse configuration cannot supply an Axis configuration.
<b>Action</b>	This is an Axis2/Synapse/WS-Stack configuration problem.
<b>0050.0043</b>	<b>A Virtual Service with name:{0} already exists. Unable to deploy.</b>
<b>Explanation</b>	Cannot deploy an Axis service when one already exists with the same name.
<b>Action</b>	Undeploy the existing service before attempting to redeploy or use the same name.
<b>0050.0044</b>	<b>Unable to locate WSStack configuration. Please check if WSStack is enabled/correctly configured.</b>
<b>Explanation</b>	Unable to retrieve the configuration context supplier bean.
<b>Action</b>	This is a Spring bean configuration issue, the pg-config.xml file is missing or corrupted.
<b>0050.0045</b>	<b>Invalid parameter passed for Virtual Service creation:{0}</b>
<b>Explanation</b>	An attempt to persist the VSD for a service found a null element. The VSD is not allowed to be null.
<b>Action</b>	This may be the result of invalid deployment payload; fix the VSD.

<b>0050.0046</b>	<b>Unable to persist VSD:{0} to disk. Encountered error:{1}</b>
<b>Explanation</b>	An exception was encountered while attempting to serialize the VSD for the service identified in the message. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0047</b>	<b>Unable to {0} VSD:{1}. Error:{2}</b>
<b>Explanation</b>	This message is used in several different error conditions, as indicated by the object of 'unable to...'.
<b>Action</b>	Fix the 'unable to...' problem for the service identified by 'VSD:'.
<b>0050.0048</b>	<b>Error getting endpoints for service:{0}, Cause: {1}</b>
<b>Explanation</b>	An exception was encountered while attempting to get endpoints. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0049</b>	<b>Exception while creating PGService: {0}, Cause: {1}</b>
<b>Explanation</b>	An AxisFault was encountered while checking if deploying service already exists or while attempting to register service with Axis2. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0050</b>	<b>Error while engaging module: {0}</b>
<b>Explanation</b>	An AxisFault was encountered while attempting to engage the Axis2 module indicated in the message. The associated fault message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the fault message.
<b>0050.0052</b>	<b>Axis was unable to load module {0}</b>
<b>Explanation</b>	An exception was encountered while attempting to load and engage module identified in message. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.

---

<b>0050.0053</b>	<b>Loading the WSDL : {0}</b>
<b>Action</b>	Info level message, no action required.
<b>0050.0055</b>	<b>PGService {0} encountered error while converting wsdl element to a StreamSource:{0}</b>
<b>Explanation</b>	An exception was encountered while attempting to read WSDL from manifest. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0057</b>	<b>Unknown WSDL format for PGService:{0}, neither WSDL 1.1 nor WSDL 2.0</b>
<b>Explanation</b>	The current WSDL element has unknown or no namespace associated.
<b>Action</b>	This is a virtual service configuration problem.
<b>0050.0060</b>	<b>Populating SOAP service using WSDL</b>
<b>Action</b>	Info level message, no action required.
<b>0050.0061</b>	<b>Unable to find a WSDL for the PGService:{0}. Assuming a POX or Legacy service</b>
<b>Action</b>	Info level message, no action required.
<b>0050.0062</b>	<b>PGService: {0} is available on transports {1}</b>
<b>Action</b>	Info level message, no action required.
<b>0050.0063</b>	<b>Adding PGService:{0} to the SOAP Stack</b>
<b>Action</b>	Info level message, no action required.
<b>0050.0064</b>	<b>Removing PGService:{0} due to error: axisFault.getMessage()</b>
<b>Action</b>	Info level message, no action required.
<b>0050.0065</b>	<b>Exception while setting policy on PGService:{0}</b>
<b>Explanation</b>	An exception was encountered while attempting to engage WS-Policy module. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.

<b>0050.0066</b>	<b>Setting policy with id:{0} on CloudStreams service:{1}</b>
<b>Action</b>	Info level message, no action required.
<b>0050.0068</b>	<b>Successfully created service in SOAP Stack for PGService:{0} containing {1} endpoint(s).</b>
<b>Action</b>	Info level message, no action required.
<b>0050.0069</b>	<b>Error{1} on setting parameter :{0} on CloudStreams service</b>
<b>Explanation</b>	An exception was encountered while attempting to set a parameter into an Axis service. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0070</b>	<b>creating new CloudStreams service: {0}</b>
<b>Action</b>	Info level message, no action required.
<b>0050.0071</b>	<b>Unable to find service directory for service {0}</b>
<b>Explanation</b>	Unable to persist WSDL assets because the virtual service directory does not exist.
<b>Action</b>	Redeploying the virtual service should create the service directory.
<b>0050.0074</b>	<b>Error: {0} while reading from file {1}</b>
<b>Explanation</b>	An exception was encountered while attempting to read the proxy file identified in the message. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0076</b>	<b>Scheduled task[{0}] with startup delay of {1} ms and interval of {2} ms</b>
<b>Action</b>	Info level message, no action required.
<b>0050.0077</b>	<b>Error initializing JMS transport listener. Cause: {0}</b>
<b>Explanation</b>	An exception was encountered while attempting to register JMS listener. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.

---

<b>0050.0078</b>	<b>Unable to stop TransportListener called:{0}. Exception:{1}</b>
<b>Explanation</b>	An AxisFault was encountered while attempting to stop the JMS transport listener during bean initialization. The associated fault message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the fault message.
<b>0050.0083</b>	<b>Error {0} occurred while updating the load balancer properties</b>
<b>Explanation</b>	An AxisFault was encountered while attempting to add load balancer URL to an Axis transport description. The associated fault message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the fault message.
<b>0050.0084</b>	<b>Loadbalanced Endpoint: [{0}] failed!</b>
<b>Explanation</b>	A mediation operation to a load balanced endpoint has failed. The endpoint indicated in the message is not available. This usually indicates a communication problem with the targeted server.
<b>Action</b>	Fix the targeted server.
<b>0050.0086</b>	<b>Unable to get the IS keystore manager - please check your configuration!</b>
<b>Explanation</b>	Unable to retrieve the keystore manager bean.
<b>Action</b>	This is a Spring bean configuration issue, the pg-config.xml file is missing or corrupted.
<b>0050.0089</b>	<b>Unable to get the Rampart Configuration Handler - please check your configuration!</b>
<b>Explanation</b>	Unable to retrieve the Rampart creation handler bean.
<b>Action</b>	This is a Spring bean configuration issue, the pg-config.xml file is missing or corrupted.
<b>0050.0099</b>	<b>VSD proxy loader, Unable to delete file: {0}</b>
<b>Explanation</b>	The file or directory indicated in the message could not be deleted.
<b>Action</b>	Determine why the file or directory could not be deleted and make it deletable.
<b>0050.0100</b>	<b>VSD proxy loader, Unable to delete directory: {0}</b>
<b>Explanation</b>	The directory indicated in the message could not be deleted.
<b>Action</b>	Determine why the directory could not be deleted and make it deletable.

<b>0050.0105</b>	<b>Unable to determine the fault cause. Check the log file for more information.</b>
<b>Explanation</b>	This error indicates that CloudStreams could not determine the cause for the error when trying to extract the soap fault message from the response. Additional errors, if any, would be present in the Integration Server log file (server.log).
<b>0050.0208</b>	<b>Error resolving WSDL URI. Cause {0}</b>
<b>Explanation</b>	An exception was encountered while attempting to resolve URI elements into XML source. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0209</b>	<b>Error initializing virtual service factory. Cause: {0}</b>
<b>Explanation</b>	An exception was encountered while attempting to initialize XPath elements. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0210</b>	<b>Error setting location of virtual service proxies directory. Path: {0} Cause: {1}</b>
<b>Explanation</b>	An exception was encountered while attempting to use the directory identified in the message. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0211</b>	<b>Unable to determine service endpoint URI for this service: {0} No transport listener defined for the virtual service's transport protocol.</b>
<b>Explanation</b>	The configuration context's listener manager cannot find an endpoint for the current service. This may indicate that the hosting IS does not have an appropriate listener registered.
<b>Action</b>	This is a configuration problem, either in IS ports or VSD
<b>0050.0212</b>	<b>Unknown exception deploying virtual service: {0} Cause: {1}</b>
<b>Explanation</b>	An exception was encountered while attempting to get an endpoint reference from the context listener manager. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.

---

<b>0050.0214</b>	<b>Error {0} manifest from external resources associated with virtual service: {1}. Cause: {2}</b>
<b>Explanation</b>	An exception was encountered while attempting to read WSDL from manifest. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0215</b>	<b>Error initializing virtual service transformation bean with this xslt: {0} Cause: {1}</b>
<b>Explanation</b>	An exception was encountered while attempting to read the transformation file. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0221</b>	<b>CloudStreams has an internal configuration error. It's deploy-time xslt transformation file path does not exist. Path: {0}</b>
<b>Explanation</b>	An exception was encountered while attempting to read the file identified in the message. The associated exception message should include more details regarding the problem.
<b>Action</b>	This is a configuration problem; make sure the file identified in the message exists and contains the transformation.
<b>0050.0235</b>	<b>URI creation error: {0}</b>
<b>Explanation</b>	An exception was encountered while attempting to resolve an endpoint URI. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0250</b>	<b>Could not find user-specified value for HTTP method! Defaulting to inbound request HTTP method {0}</b>
<b>Explanation</b>	The 'routing method' context variable has an invalid value.
<b>Action</b>	If the value indicated in the message is acceptable, no action is required. Otherwise virtual service configuration must be changed.
<b>0050.0252</b>	<b>Could not set HTTP method for outgoing request for endpoint: {0}</b>
<b>Explanation</b>	The outgoing request's message context is null.
<b>Action</b>	This is a virtual service/policy configuration problem.

**0050.0300**            **Context variable name "{0}" is already declared. Multiple declarations in the same context is not allowed.**

**Explanation**        Context variable names must be unique for a service.

**Action**              This is a service configuration problem.

**0050.0303**            **Attempt to reference context variable without providing a message context. Custom context variables may only be declared with a 'session' scope at this time. Other scopes are not supported.**

**Explanation**        Attempting to get context variable or context variable map, but the message context (or session) is null.

**Action**              Earlier error messages should provide clues to help determine why a valid message context is null.

**0050.0306**            **Context variable name is required for variable declaration.**

**Explanation**        Variable name validation failed, QName is null or is missing a local part.

**Action**              This is a context variable configuration problem.

**0050.0307**            **Namespace URI and prefix is required for custom variable declaration. varName: {0}**

**Explanation**        Variable name validation failed, Namespace URI and prefix must both be neither null nor empty.

**Action**              This is a context variable configuration problem.

**0050.0308**            **Context variable name must be a valid identifier ( alpha-numeric, \$, or \_ permitted ) Found: {0}**

**Explanation**        Variable name validation failed, name has invalid characters.

**Action**              This is a context variable configuration problem.

**0050.0309**            **Core Context variables cannot have a namespace or prefix as part of its declaration. varName: {0}**

**Explanation**        Variable name validation failed, prefix for core variables must be empty.

**Action**              This is a context variable configuration problem.

---

<b>0050.0310</b>	<b>Either a Message context or axis service name is required when creating a custom context variable. varName: {0}</b>
<b>Explanation</b>	Both service name and Axis2 message context are null, this is not acceptable. This is probably the result of attempting to deploy a service with no service name.
<b>Action</b>	Verify that service configuration is correct.
<b>0050.0311</b>	<b>Attempt to create a custom variable using a message context with no AxisService. varName: {0}</b>
<b>Explanation</b>	The axis2 message context is corrupted, it should identify a service.
<b>Action</b>	Earlier error messages should provide clues to help determine why a valid message context could not be created.
<b>0050.0312</b>	<b>Unexpected error creating custom CloudStreams context variable. varName: {0} reason: {1}</b>
<b>Explanation</b>	An exception was encountered while attempting to create a custom context variable. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0313</b>	<b>Unexpected error removing custom CloudStreams context variable for service: {0} reason: {1}</b>
<b>Explanation</b>	An exception was encountered while attempting to remove or inject a custom context variable. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0314</b>	<b>Unexpected error initializing core CloudStreams context variables. reason: {0}</b>
<b>Explanation</b>	An exception was encountered while attempting to create a context variable. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0316</b>	<b>Unexpected error getting CloudStreams context variable value. varName: {0} reason: {1}</b>
<b>Explanation</b>	An exception was encountered while attempting to get the value of the context variable named in the message. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.

<b>0050.0317</b>	<b>Unexpected error setting CloudStreams context variable value. varName: {0}, value:{1}, reason: {2}</b>
<b>Explanation</b>	An exception was encountered while attempting to set the context variable value named in the message. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0318</b>	<b>Expected a virtual service name for this method operation, but none was provided.</b>
<b>Explanation</b>	Attempting to get context variable map for a null service name.
<b>Action</b>	Earlier error messages should provide clues to help determine why a valid service name is null.
<b>0050.0321</b>	<b>CloudStreams context variable adapter unable to locate this type: {0}</b>
<b>Explanation</b>	The context variable type indicated in the message is unknown.
<b>Action</b>	This is a context variable configuration problem.
<b>0050.0322</b>	<b>Unexpected error getting core CloudStreams context variable value from adapter. type: {0}</b>
<b>Explanation</b>	An exception was encountered while attempting to get the context variable value named in the message. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0323</b>	<b>Only string and int schema types are supported at this time. Type: {0}, declared with "{1}" context variable is not supported.</b>
<b>Explanation</b>	The context variable schema type is not among the accepted types.
<b>Action</b>	This is a service configuration problem.
<b>0050.0324</b>	<b>Context variable name declarations cannot contain \$ sign symbols in the name since that is used as a reference operator. varName: {0}</b>
<b>Explanation</b>	Variable name validation failed, name must include substitution character, (dollar sign).
<b>Action</b>	This is a context variable configuration problem.

---

<b>0050.0325</b>	<b>Unable to return list of context variables declared for this service: {0} Reason: {1}</b>
<b>Explanation</b>	An AxisFault was encountered while attempting to retrieve a list of context variable names. The associated fault message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the fault message.
<b>0050.0326</b>	<b>Unable to return list of context variables declared for this message context: {0} Reason: {1}</b>
<b>Explanation</b>	An AxisFault was encountered while attempting to get a list of context variables or list of variable keys. The associated fault message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the fault message.
<b>0050.0327</b>	<b>Context variable name deployed with virtual service {0} references an unknown namespace prefix. name attribute: {1}</b>
<b>Explanation</b>	Context variable identified in message has invalid namespace.
<b>Action</b>	This is a context variable configuration problem.
<b>0050.0328</b>	<b>Exception while copying context variables from request to response message context. Reason: {0}</b>
<b>Explanation</b>	An AxisFault was encountered while attempting to copy context variable names between contexts. The associated fault message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the fault message.
<b>0050.0329</b>	<b>Could not create backup directory for failed services! Dir tried = {0}</b>
<b>Explanation</b>	An attempt to create the 'failed services' directory has failed.
<b>Action</b>	Determine why the directory could not be created. Either fix the creation problem or specify a different directory.
<b>0050.0331</b>	<b>Error occurred when getting backup directory for path {0}</b>
<b>Explanation</b>	An exception was encountered while attempting to determine directory for backing up failed services. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.

<b>0050.0333</b>	<b>Error occurred while resolving URI; message = {0}</b>
<b>Explanation</b>	An exception was encountered during URI resolution. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0337</b>	<b>Previously selected {0} port {1} is no longer enabled or available!</b>
<b>Explanation</b>	The message indicates port number and type. The requested port is not available.
<b>Action</b>	Select a new port number for the indicated port type.
<b>0050.0343</b>	<b>Context variable API expected an IData object for ctx variable, {0}, but received this: {1}</b>
<b>Explanation</b>	The data element from which a context variable is to be extracted has an unknown data type.
<b>Action</b>	This is probably a flow configuration problem; where the pipeline was populated with an invalid value.
<b>0050.0344</b>	<b>Attempt to insert {0} core ctx variable with invalid value type: {1}. Expected a collection of this type: {2}</b>
<b>Explanation</b>	.The allowable data type for a core context variable is restricted, depending on variable type.
<b>Action</b>	.This is a context variable configuration problem.
<b>0050.0345</b>	<b>Unable to access array element [{0}] in SOAP_HEADERS core ctx variable. Cause: {1}</b>
<b>Explanation</b>	The index value indicated in the message must be numeric.
<b>Action</b>	This is a context variable configuration problem.
<b>0050.0346</b>	<b>Invalid array or key reference for core ctx variable. This substitution string has mismatched braces: {0}</b>
<b>Explanation</b>	The context variable substitution string is invalid, mismatched brace characters were found.
<b>Action</b>	This is a context variable configuration problem.

---

<b>0050.0347</b>	<b>Attempt to create an IData value for a ctx variable from an unsupported class type. CtxVar: {0} Bad type: {1}</b>
<b>Explanation</b>	The context variable to be converted to IData has an unknown data type.
<b>Action</b>	This is a context variable configuration problem.
<b>0050.0348</b>	<b>Unable to append header block to the end of the soap header. Cause: {0}, soapHeader element: {1}</b>
<b>Explanation</b>	An exception was encountered while attempting to add append new SOAP header block. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0349</b>	<b>Unable to prepend header block to the beginning of the soap header. Cause: {0}, soapHeader element: {1}</b>
<b>Explanation</b>	An exception was encountered while attempting to add prepend new SOAP header block. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0350</b>	<b>Unable to remove header block from the soap header. Cause: {0}, soapHeader: {1}</b>
<b>Explanation</b>	An exception was encountered while attempting to remove a SOAP header block. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0351</b>	<b>Unable to set header block at position {0} of the soap header. Cause: {1}, soapHeader element: {2}</b>
<b>Explanation</b>	An exception was encountered while attempting to replace a SOAP header block with a new one. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0357</b>	<b>Error occurred when getting STS configurations directory for path {0}</b>
<b>Explanation</b>	An exception was encountered while attempting to create the directory indicated in the message. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.

<b>0050.0362</b>	<b>Error occurred when creating STS client</b>
<b>Explanation</b>	An exception was encountered while attempting to create an STS client object. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0364</b>	<b>Error occurred when initializing default STS configuration store</b>
<b>Explanation</b>	An exception was encountered while attempting to create JAXB marshaller/unmarshaller pair. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0367</b>	<b>Error occurred when saving STS configuration to disk</b>
<b>Explanation</b>	An exception was encountered while attempting to marshal configuration object into file. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0368</b>	<b>Error occurred when reading STS configuration from file {0}</b>
<b>Explanation</b>	An exception was encountered while attempting to unmarshal configuration file indicated in the message into JAXB object. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0371</b>	<b>Error getting IS keystore manager instance!</b>
<b>Explanation</b>	An exception was encountered while attempting to get a reference to the keystore manager. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0373</b>	<b>Error occurred when adding rampart configuration to STS policy</b>
<b>Explanation</b>	An exception was encountered while attempting to configure the STS policy. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.

---

<b>0050.0379</b>	<b>Error occurred when adding assertion to STS policy</b>
<b>Explanation</b>	An exception was encountered while attempting to add an assertion to a WS-Policy artifact. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0382</b>	<b>Error occurred when adding OnBehalfOf element to WS-Trust request element</b>
<b>Explanation</b>	An exception was encountered while attempting to add the WS-Trust element to a request. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0383</b>	<b>Error occurred when sending WS-Trust request to STS to obtain SAML assertion</b>
<b>Explanation</b>	An exception was encountered while attempting to add SAML assertion to pipeline. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0389</b>	<b>Adding OnBehalfOf element in WS-Trust request for IS user {0}</b>
<b>Action</b>	Info level message, no action required.
<b>0050.0390</b>	<b>Could not find base STS policy file: {0} !</b>
<b>Explanation</b>	An exception was encountered while attempting to load a WS-Policy artifact from the file indicated in the message. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0391</b>	<b>Error occurred when getting STS configurations! Check to see if the ISTSClientConfigManager bean is configured!</b>
<b>Explanation</b>	The STS configuration manager bean could not be found.
<b>Action</b>	This is a Spring bean configuration issue, the pg-config.xml file is missing or corrupted.
<b>0050.0394</b>	<b>Error occurred when getting key aliases for keystore {0}: Error: {1}</b>
<b>Explanation</b>	An exception was encountered while attempting to add a list of certificate aliases to the pipeline. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.

<b>0050.0395</b>	<b>Error occurred when getting keystore handles {0}</b>
<b>Explanation</b>	An exception was encountered while attempting to add a list of keystore handles to the pipeline. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0396</b>	<b>Error when signing SAML assertion and SOAP request body</b>
<b>Explanation</b>	An exception was encountered while attempting to sign a SAML assertion and request body. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0397</b>	<b>Error occurred when adding ws-addressing headers to outbound soap request; Error: {0}</b>
<b>Explanation</b>	An exception was encountered while attempting to add WS-Addressing headers. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0400</b>	<b>Using default timestamp value of 300s, because input TTL {0} is invalid (-ve or too big)</b>
<b>Explanation</b>	The input value was not valid, a default was used.
<b>Action</b>	If the default is acceptable, no action is required. Otherwise update the configuration.
<b>0050.0404</b>	<b>Response content type was empty! Falling back to original request content-type [{0}]</b>
<b>Explanation</b>	The response message context contained an empty 'ContentType', so the type from the original request was used.
<b>Action</b>	This may be acceptable. If not, then configuration update will be required.
<b>0050.0507</b>	<b>ScaDeploymentPayload.extractParts found no virtual service requests</b>
<b>Action</b>	Info level message, no action required.
<b>0050.0508</b>	<b>Unexpected exception, attempting to {0}, caught: type({1}), msg({2})</b>
<b>Explanation</b>	An exception was encountered while attempting to process a deployment request. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.

---

<b>0050.0509</b>	<b>ScaDeploymentPayload.extractParts - Unable to find consumer file {0}, for component {1}</b>
<b>Explanation</b>	The SCA deployment package was expected to contain a file to define the consumer identified in the message. The file was not found.
<b>Action</b>	This is a deployment payload construction problem.
<b>0050.0510</b>	<b>Unexpected exception, attempting to process {0} request, caught: type({1}), msg({2})</b>
<b>Explanation</b>	An exception was encountered while attempting to process a deployment request. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0515</b>	<b>ScaCompositeConfiguration found component with implementation type ({0})</b>
<b>Action</b>	Info level message, no action required.
<b>0050.0516</b>	<b>{0} - unable to convert string ({1}) to XMLGregorianCalendar: exception message ({2})</b>
<b>Explanation</b>	The date element from the deployment payload has an unexpected format.
<b>Action</b>	This is problem with the contents of the deployment payload.
<b>0050.0517</b>	<b>DeploymentPayload.{0} - input pipeline does not contain expected key ({1})</b>
<b>Explanation</b>	The deployment payload must include an element with the key indicated in the message.
<b>Action</b>	This is problem with the contents of the deployment payload.
<b>0050.0519</b>	<b>ScaDeploymentPayload - unable to delete temporary zip file: ({0})</b>
<b>Explanation</b>	The file indicated in the message could not be deleted.
<b>Action</b>	Determine why the file could not be deleted and make it deletable.
<b>0050.0520</b>	<b>DeploymentPayload - invalid request type: {0}</b>
<b>Explanation</b>	The deployment payload type is unknown.
<b>Action</b>	This is a deployment payload construction problem.

<b>0050.0528</b>	<b>DeploymentPayload - found null/empty virtual service descriptor for service {0}</b>
<b>Explanation</b>	The deployment payload must contain a VSD. The VSD for the service identified in the message was not found.
<b>Action</b>	This is a deployment payload construction problem.
<b>0050.0603</b>	<b>Error occurred when adding UsernameToken to SOAP Envelope: {0}</b>
<b>Explanation</b>	An exception was encountered while attempting to add username token to the pipeline. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0605</b>	<b>Error occurred when adding X.509 token to SOAP Envelope: {0}</b>
<b>Explanation</b>	An exception was encountered while attempting to add X509 token to the pipeline. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0100.0001</b>	<b>The specified node {0} could not be found.</b>
<b>0100.0002</b>	<b>You have specified an invalid transformer service {0} for the cloud service node {1}.</b>
<b>0100.0003</b>	<b>Error occurred while handling the custom service signature for the cloud service node {0}. Error is {1}.</b>
<b>0100.0004</b>	<b>You have specified an invalid transformer service {0} for the cloud service node {1}. The transformer service should have a signature with Input/Output prefixes.</b>
<b>0100.0005</b>	<b>You have specified an invalid transformer service {0} for the cloud service node {1}. The root of the transformer service signature should be a document type only.</b>
<b>0101.0311</b>	<b>Error occurred while validating certificate "{0}". Error is "{1}"</b>
<b>Explanation</b>	An error occurred while validating a certificate. This can be due to an invalid certificate or a non-existent certificate.
<b>Action</b>	Ensure that the certificate specified is valid and exists in the filesystem.

0300.0048.description – Define any custom configurations specific to the SaaS provider.

0300.0049            OAuth Alias

0300.0049.description – Define the OAuth tokens alias to be used for the connection.

0300.0101.description – Define the required connection configurations to initiate communication with the SaaS provider.

0300.0102.description – Define configurations needed for the username and password based authentication to the SaaS provider.

0300.0103.description – Define the HTTP request header contents that will be used while making a request to a SaaS provider.

0300.0104.description – Define configurations needed for the HTTP protocol that the connection will use to connect to the SaaS provider.

0300.0126.description – Define configurations needed for Amazon web services requests requiring AWS Signature Version 2 authentication.

0300.0127.description – Indicates that the group is defined for the Amazon S3 authentication scheme and it uses the Access Key and the Secret Key of the client to authenticate the requests.

0300.0128.description – Define configurations needed for Amazon web services requests requiring AWS Signature Version 4 authentication.

0300.0129            Invalid proxy server alias specified "{0}". Ensure that proxy server alias "{0}" exists and is valid.

**Explanation**            Invalid proxy server alias is provided in the cloud connection.

**Action**                    Ensure that proxy server alias exists and is valid.

**0300.0130.description – Define the configurations needed for the OAuth version 1.0a authentication scheme.**

**0300.0131.description – Define configurations needed for the OAuth version 2.0 authentication scheme.**

**0300.0132            'Refresh Token' value is required when "{0}" is selected as 'Refresh Request Type' for refreshing the OAuth V2.0 access token**

**Explanation**        'Refresh Token' is a required field when 'Refresh Access Token' is 'true' and option selected for 'Refresh Request Type' is '{0}' in the OAuth V2.0 configuration screen

**Action**                Specify a value for the 'Refresh Token' field

**0300.0133            'Refresh URL' value is required when "{0}" is selected as 'Refresh Request Type' for refreshing the OAuth V2.0 access token**

**Explanation**        'Refresh URL' is a required field when 'Refresh Access Token' is 'true' and option selected for 'Refresh Request Type' is '{0}' in the OAuth V2.0 configuration screen

**Action**                Specify a value for the 'Refresh URL' field

**0300.0134            'Custom ESB Service Name' value is required when "Custom ESB Service" is selected as 'Refresh Request Type' for refreshing the OAuth V2.0 access token**

**Explanation**        'Custom ESB Service Name' value is required when "Custom ESB Service" is selected as 'Refresh Request Type' for refreshing the OAuth V2.0 access token

**Action**                Specify a value for the 'Custom ESB Service Name' field

**0501.0005Error       Error while initializing the connector "{0}". Details: {1}**

**Explanation**        An error occurred while trying to initialize the specified connection definition. The Details describe the exact cause of the error.

**Action**                For more information, see the Integration Server logs. Try to correct the error and reload the provider package.

**0501.0009Error       I/O exception, while trying to load manifest for connector: {0}. Details: {1}**

**Explanation**        An error occurred while reading the connector manifest file at the specified location. The error occurs if the manifest file is missing or corrupted, or the manifest file does not contain the required attribute definitions.

**Action**                Re-install the connector.

<b>0501.0025Warning</b>	<b>Duplicate definition found for operation: {0} in connector definition for: {1}. Ignoring!</b>
<b>Explanation</b>	The specified connector descriptor contains more than one operation definition against the specified name {0}. The duplicate definition will be ignored.
<b>Action</b>	Correct the connector descriptor and ensure that each operation name definition is unique.
<b>0501.0026Warning</b>	<b>No definition found for operation: {0} in connector definition for: {1}. Ignoring!</b>
<b>Explanation</b>	The WSDL contains an operation definition, but the connector definition does not include the corresponding operation definition and the operation is ignored.
<b>Action</b>	Consider including the operation definition, if required to be included, as part of the connector definition.
<b>0501.0028Warning</b>	<b>No operations defined in the connector definition: {0}, while the WSDL model contains {1} operation(s).</b>
<b>Explanation</b>	The connector descriptor does not include any valid operation definition, while the WSDL definition contains one or more operation definitions.
<b>Action</b>	Include one or more valid operation definitions in the connector descriptor.
<b>0501.0030Warning</b>	<b>No abstract type defined in service: {0}. Ignoring complex type check for interaction: {1}, connector: {2}</b>
<b>Explanation</b>	One or more interactions are marked as COMPLEX, but the connector descriptor does not define any 'abstractObject' definition. The interaction will be treated as a SIMPLE interaction.
<b>Action</b>	Consider either including an 'abstractObject' definition for the specified service or mark the interaction type as SIMPLE.
<b>0501.0031Warning</b>	<b>Exception while populating the abstract definition for operation: {0}. Details: {1}</b>
<b>Explanation</b>	Unable to populate the abstract definition for the specified operation. The operation will be treated as SIMPLE operation.
<b>Action</b>	For more information, see the Integration Server log. Correct the error based on the information from the log or mark the operation type as SIMPLE.
<b>0501.0052Error</b>	<b>Unable to {0} the document type package "{1}" for connector: {2}. Details: {3}</b>
<b>Explanation</b>	The error occurred while performing the specified operation on the connector.
<b>Action</b>	For more information, see the Integration Server log.

<b>0501.0080Error</b>	<b>Error loading the model for resource: {0}</b>
<b>Explanation</b>	A parsing error occurred while loading the connector descriptor for the specified resource.
<b>Action</b>	For more information, see the Integration Server log.
<b>0501.0082</b>	<b>Unable to load resource file {0}. Details: {1}</b>
<b>Explanation</b>	Error occurred while loading the resource file or no schema definition file found at {0}. No schema validation would be performed.
<b>Action</b>	Ensure that the necessary XML Schema file {0} exists at the location
<b>0501.0202Warning</b>	<b>At least one connection for the connector: {0} is enabled. Disable all the connections for this connector.</b>
<b>Explanation</b>	You tried to disable a connector that contains one or more enabled connections.
<b>Action</b>	You must disable all the connections created for the connector, before disabling the connector.
<b>0501.0218Warning</b>	<b>No provider registered with name: {0}</b>
<b>Explanation</b>	No provider with the specified name is registered with webMethods CloudStreams.
<b>Action</b>	Check the provider name. Typically, the provider name is the same as the provider package name for the package that contains the connector definitions.
<b>0501.0219Warning</b>	<b>No connector registered with name: {0}</b>
<b>Explanation</b>	No connector descriptor is registered with webMethods CloudStreams for the specified identifier.
<b>Action</b>	Check the connector identifier. See the 'connector-Key' in the manifest.cpd file for the connector unique identifier.
<b>0501.0224Warning</b>	<b>Unable to delete the connector: {0}, the connector is enabled.</b>
<b>Explanation</b>	The connector cannot be deleted, because it is currently enabled.
<b>Action</b>	When you want to delete the connector, you must first disable the connector. You cannot recover a connector after deleting it and you lose all the connector-related artifacts.

<b>0501.0227Error</b>	<b>Error initializing the provider registry and meta-data handler factory. Details: {0}</b>
<b>Explanation</b>	Unable to initialize and load the provider registry.
<b>Action</b>	For more information, see the Integration Server log.
<b>0501.0231Error</b>	<b>Error {0} provider: {1}. Details: {2}</b>
<b>Explanation</b>	The error occurred when registering or unregistering the provider.
<b>Action</b>	For more information, see the Integration Server log.
<b>0501.0262</b>	<b>Invalid mapping "{0}" found. Source type "{1}" and target type "{2}".</b>
<b>Explanation</b>	The specified mapping defined in the connector XML of a Provider is invalid.
<b>Action</b>	Correct the mapping and ensure that the source and target types are valid, and the source type supports the output to a given target type. See Administering webMethods CloudStreams guide for more details.
<b>0501.0265</b>	<b>An exception occurred while creating a connection for the connector: {0}. Details: {1}</b>
<b>0501.0266</b>	<b>Connection created successfully.</b>
<b>0501.0267</b>	<b>Connection updated successfully.</b>
<b>0501.0268</b>	<b>An exception occurred while updating the connection: {0}. Details: {1}</b>
<b>0501.0269</b>	<b>Connection deleted successfully.</b>
<b>0501.0270</b>	<b>An exception occurred while deleting the connection : {0}. Details: {1}</b>
<b>0502.0004Error</b>	<b>Error occurred while registering connection node: "{0}".</b>
<b>Explanation</b>	If the connection is enabled as per the node definition, Integration Server tries to enable the connection during restart or package reload. During this process, no connection is established with the SaaS provider and an exception occurs.
<b>Action</b>	Check if the connection parameters are valid and if a connection can be established using those parameters. Also, in the connector configuration file, check if the mappings and operation names/document types are configured correctly for the connection type.

<b>0502.0006Error</b>	<b>Error while unregistering connection alias: "{0}".</b>
<b>Explanation</b>	This error may occur under different circumstances. The Integration Server log contains the details of the error that explain the root cause for the error.
<b>Action</b>	For more information, see the Integration Server error log.
<b>0502.0007Error</b>	<b>Error while making a copy of connection alias: "{0}".</b>
<b>Explanation</b>	If you make a copy of a connection node using Designer, the copy of the source connection node might not be available in the file system.
<b>Action</b>	Check if the node.ndf file of the source connection node is available for read and that it is valid.
<b>0502.0017Error</b>	<b>Unable to create node "{0}" in the server namespace.</b>
<b>Explanation</b>	This error may occur under different circumstances. The Integration Server log contains the details of the error that explain the root cause for the error.
<b>Action</b>	For more information, see the Integration Server error log.
<b>0502.0047Error</b>	<b>Error occurred while destroying a connection instance of the alias: "{0}". Details: {1}</b>
<b>Explanation</b>	The error occurs when disabling a connection and 1/ The SaaS provider is not accessible. 2/ The logout request can not be created successfully, because of incorrect mappings or document types specified in the connector configuration file.
<b>Action</b>	For more information, see the Integration Server logs.
<b>0502.0056Error</b>	<b>Updating the connection alias {0} failed because the connection is enabled. Disable the connection and try updating again.</b>
<b>Explanation</b>	The error occurs when you attempt to delete or update a connection alias when the connection is enabled.
<b>Action</b>	Disable the connection alias and try updating or deleting the connection again.
<b>0502.0224</b>	<b>Error occurred while initializing the connection metadata builder for the given connection "{0}"</b>
<b>Explanation</b>	An error occurred while loading the connection metadata (connection attributes) associated with the specified connection.
<b>Action</b>	Ensure that all the connection attributes are valid for the specified connection. Check the server log for the Integration Server for more details.

---

<b>0502.0225</b>	<b>'Session Management' under 'Connection Management Properties' must be enabled when OAuth V2.0 'Refresh Access Token' is configured to 'true'</b>
<b>Explanation</b>	'Session Management' under 'Connection Management Properties' must be configured to 'idle' or 'fixed' when OAuth V2.0 'Refresh Access Token' is configured to 'true'
<b>Action</b>	Either configure 'Session Management' under 'Connection Management Properties' to 'idle' or 'fixed' or configure 'OAuth V2.0' 'Refresh Access Token' to 'false'
<b>0502.0226</b>	<b>'Refresh Access Token' under 'OAuth V2.0' configuration must be configured to 'true' when 'Session Management' under 'Connection Management Properties' is enabled</b>
<b>Explanation</b>	'Refresh Access Token' under 'OAuth V2.0' configuration must be configured to 'true' when 'Session Management' under 'Connection Management Properties' is configured to 'idle' or 'fixed'
<b>Action</b>	Either configure 'Refresh Access Token' under 'OAuth V2.0' configuration to 'true' or disable 'Session Management' under 'Connection Management Properties' by configuring it to 'none'
<b>0503.0101</b>	<b>Error while retrieving the service list from provider. Connection name "{0}". Details: {1}</b>
<b>Explanation</b>	The CloudStreams server cannot load the connector model for the specified connection name.
<b>Action</b>	Ensure that the associated connector model is valid or exists, and that the model loads without an error.
<b>0503.0106</b>	<b>Error creating CloudStreams connector service: "{0}". Details: {1}</b>
<b>Explanation</b>	The inputs provided or configured when creating the connector service are incomplete, invalid, or not supported. The error also occurs when the CloudStreams server is trying to load an existing CloudStreams service node that is corrupted.
<b>Action</b>	Ensure that the service is configured properly. If you are using a custom connector, ensure that it is valid and that the service node is not corrupted.
<b>0503.0108</b>	<b>Error occurred while registering the cloud connector service {0} with connector virtual service.</b>
<b>Explanation</b>	A CloudStreams connector service is registered with a connector virtual service whenever the cloud connector service is created or updated. The registration is required for generating Analytics information.
<b>Action</b>	Ensure that the connector virtual service that the CloudStreams connector service refers to is valid and available.

<b>0503.0109</b>	<b>Unable to invoke CloudStreams connector service "{0}". Details: {1}.</b>
<b>Explanation</b>	Internal error while executing the cloud connector service.
<b>Action</b>	Contact Software AG Global Support.
<b>0503.0112</b>	<b>Unable to invoke CloudStreams connector service "{0}" because the associated connection "{1}" is not found.</b>
<b>Explanation</b>	The connection associated with the specified CloudStreams connector service or the connection alias passed at runtime does not exist.
<b>Action</b>	Ensure that the associated or specified connection exists and that the connection is enabled.
<b>0503.0113</b>	<b>Unable to invoke CloudStreams connector service "{0}" because the associated connection "{1}" is disabled.</b>
<b>Explanation</b>	The connection associated with the CloudStreams connector service or the connection alias passed at runtime exists, but is disabled.
<b>Action</b>	Ensure that the associated or specified connection exists and that the connection is enabled.
<b>0503.0116</b>	<b>Unable to retrieve virtual service runtime instance while executing CloudStreams connector service "{0}"</b>
<b>Explanation</b>	Internal error while executing the cloud connector service.
<b>Action</b>	Contact Software AG Global Support.
<b>0503.0120</b>	<b>Error occurred while invoking CloudStreams connector service "{0}" using virtual service "{1}". Details: {2}</b>
<b>Explanation</b>	Internal error while executing the cloud connector service.
<b>Action</b>	Contact Software AG Global Support.
<b>0503.0121</b>	<b>Error occurred while registering CloudStreams connector service "{0}" with cloud virtual service "{1}".</b>
<b>Explanation</b>	A CloudStreams connector service is registered with a connector virtual service whenever the connector service is created or updated. The registration is required for generating Analytics information.
<b>Action</b>	Ensure that the connector virtual service that the CloudStreams connector service refers to is valid and available.

<b>0503.0122</b>	<b>Error occurred while unregistering CloudStreams connector service "{0}" with cloud virtual service "{1}".</b>
<b>Explanation</b>	A CloudStreams connector service is un-registered with a connector virtual service whenever the connector service is deleted. This is required for generating Analytics information.
<b>Action</b>	Ensure that the connector virtual service that the CloudStreams connector service refers to is valid and available.
<b>0503.0123</b>	<b>Error while retrieving the default virtual service name for "{0}" based connector service. Details: {1}</b>
<b>Explanation</b>	The error occurred while retrieving the connector virtual services list because of an internal error.
<b>Action</b>	Ensure that WmCloudStreams package is loaded without any warnings. If the problem persists, contact Software AG Global Support.
<b>0503.0124</b>	<b>Error retrieving business object list. Connection name "{0}". Details: {1}</b>
<b>Explanation</b>	The error occurs because of one of the following reasons: 1/ The connection does not exist or is disabled. 2/ The session ID for the connection has expired. 3/ The backend is not available or it cannot be reached to retrieve the metadata from the backend SaaS provider.
<b>Action</b>	To resolve this error, ensure that: 1/ The connection exists and is enabled. 2/ The connection is enabled and has a valid session ID. You can turn on the session management connection option. 3/ Ensure that the backend is reachable and metadata is retrieved successfully from the backend SaaS provider.
<b>0503.0125</b>	<b>Error retrieving business object description. Connection name "{0}". Details: {1}</b>
<b>Explanation</b>	The error occurs because of one of the following reasons: 1/ The connection does not exist or is disabled. 2/ The session ID for the connection has expired. 3/ The backend is not available or cannot be reached to retrieve metadata from the backend SaaS provider.
<b>Action</b>	To resolve the error, ensure that: 1/ The connection exists and is enabled. 2/ The connection is enabled and has a valid session ID. You can turn on the session management connection option. 3/ The backend is reachable and metadata is retrieved successfully from the backend SaaS provider.
<b>0503.0126</b>	<b>Invalid lookup service "{0}" specified.</b>
<b>Explanation</b>	Lookup services are invoked during the cloud connector service definition. The lookup services should exist in the Integration Server namespace.
<b>Action</b>	Ensure that the lookup service specified in the error message exists in the Integration Server namespace and it is accessible.

<b>0503.0127</b>	<b>Invalid service specification "{0}". The lookup service "{1}" must use the specification "{2}".</b>
<b>Explanation</b>	Every lookup service must implement the specified service specification.
<b>Action</b>	Ensure that the specified lookup service implements the required service specification.
<b>0503.0128</b>	<b>Unable to invoke CloudStreams connector service "{0}".</b>
<b>Explanation</b>	Cloud connector services access the connection from a connection pool during service invocation. The error occurs when the CloudStreams framework cannot obtain a connection from a connection pool.
<b>Action</b>	Analyze the cloud service usage and ensure that the connection is properly configured. Also, the connection pool should have a free available connection whenever a CloudStreams connector service is invoked.
<b>0503.0210</b>	<b>Unable to load the REST service node model for "{0}".</b>
<b>0503.0212</b>	<b>Invalid REST resource end point: "{0}"</b>
<b>Explanation</b>	The REST resource end point is not resolved correctly. It may have entries in brackets({}) that should be resolved.
<b>Action</b>	Check if the required Parameters are passed during the cloud connector service execution. You can also set any default values on the "Parameter" tab in Designer.
<b>0503.0213</b>	<b>Error in ServiceDispatcher, invalid input.</b>
<b>Explanation</b>	One of the key inputs for service execution is missing, such as a connection that is enabled or a virtual service.
<b>Action</b>	Check if the connection exists and is enabled. In Designer, check if the virtual service is available. Also, check that the values you specified for the inputs are correct.
<b>0503.0217</b>	<b>Unable to apply mapping on CloudStreams connector service "{0}", for operation "{1}". Details: "{2}"</b>
<b>Explanation</b>	Error while reading or applying the mappings.
<b>Action</b>	Check the mappings available in the Cloud Provider Descriptor.
<b>0503.0233</b>	<b>Could not execute the map service "{0}". Exception: {1}</b>
<b>Explanation</b>	The map service associated with the mapping could not be executed.
<b>Action</b>	Check the server log for more details.

---

0503.0297	<b>Parameter "{0}" is not supported for mapping because the Data Type is Record.</b>
0503.0513	<b>Unable to identify connectorID or none specified</b>
<b>Explanation</b>	ConnectorID is not specified or empty while creating cloud connector service
<b>Action</b>	Please provide a valid connectorID
0503.0514	<b>Unable to identify providerName or none specified</b>
<b>Explanation</b>	Provider Name is not specified or empty while creating cloud connector service
<b>Action</b>	Please provide a valid provider name
0503.0519	<b>Invalid InteractionHandler implementation {0} specified for the interaction name {1}. Note that if the interaction type is {2} then InteractionHandler must implements the abstract class {3}.</b>
<b>Explanation</b>	Interaction implementation can be externalised to Java based implementation. If the interaction is involved with multiple business objects then connector developer should leverage the built in abstract implementation class. This abstract implementation can generate the input and output cloud service based on various properties configurations. Internally CloudStreams server generates the signature based of various templates. These internal templates reads the multiple properties and generates the signatures.
<b>Action</b>	Make sure that the implementation class specified extends the mentioned abstract InteractionHandler class.
0550.0001	<b>Error while creating Connection "{0}".</b>
0550.0002	<b>Error while deleting Connection "{0}".</b>
0550.0003	<b>Error while retrieving details for Connection "{0}".</b>
0550.0004	<b>Error while updating Connection "{0}".</b>
0550.0005	<b>Error while checking for Connection "{0}".</b>

- 0550.0006      **Error while fetching list of Connections.**
  
- 0550.0007      **Error while creating Connector "{0}".**
  
- 0550.0008      **Error while deleting Connector "{0}".**
  
- 0550.0009      **Error while retrieving details for Connector "{0}".**
  
- 0550.0010      **Error while updating Connector "{0}".**
  
- 0550.0011      **Error while fetching manifest content for Connector "{0}".**
  
- 0550.0012      **Error while fetching list of Connectors.**
  
- 0550.0013      **Error while loading model for Connector "{0}".**
  
- 0550.0014      **Error while creating REST Resource "{0}".**
  
- 0550.0015      **Error while deleting REST Resource "{0}".**
  
- 0550.0016      **Error while updating REST Resource "{0}".**
  
- 0550.0017      **Error while retrieving details for REST Resource "{0}".**
  
- 0550.0018      **Error while checking for REST Resource "{0}".**
  
- 0550.0019      **Error while fetching list of REST Resources.**

---

0550.0020	Error while creating Provider "{0}".
0550.0021	Error while updating Provider "{0}".
0550.0022	Error while deleting Provider "{0}".
0550.0023	Error while retrieving details for Provider "{0}".
0550.0024	Error while fetching list of Providers.
0550.0025	Error while creating Service "{0}".
0550.0026	Error while deleting Service "{0}".
0550.0027	Error while retrieving details for Service "{0}".
0550.0028	Error while updating Service "{0}".
0550.0029	Error while checking for Service "{0}".
0550.0030	Error while fetching list of Services.
0550.0031	{0} "{1}" already exists.
0550.0032	{0} "{1}" not found.
0550.0033	Error during {0} operation for {1} "{2}".

- 0550.0034      **Error during {0} operation for {1}.**
  
- 0550.0035      **Error loading {0} "{1}".**
  
- 0550.0036      **"{0}" is a required input.**
  
- 0550.0037      **"{0}" is a required input when {1}.**
  
- 0550.0038      **Invalid input "{0}" for "{1}". Valid values are {2}.**
  
- 0550.0039      **Creating Connection "{0}".**
  
- 0550.0040      **Created Connection "{0}".**
  
- 0550.0041      **Deleting Connection "{0}".**
  
- 0550.0042      **Deleted Connection "{0}".**
  
- 0550.0043      **Retrieving details for Connection "{0}".**
  
- 0550.0044      **Updating Connection "{0}".**
  
- 0550.0045      **Updated Connection "{0}".**
  
- 0550.0046      **Checking for Connection "{0}".**
  
- 0550.0047      **Listing Connections.**

0550.0048	Creating Connector "{0}".
0550.0049	Created Connector "{0}".
0550.0050	Deleting Connector "{0}".
0550.0051	Deleted Connector "{0}".
0550.0052	Retrieving details for Connector "{0}".
0550.0053	Updating Connector "{0}".
0550.0054	Updated Connector "{0}".
0550.0055	Checking for Connector "{0}".
0550.0056	Listing Connectors.
0550.0057	Creating REST Resource "{0}".
0550.0058	Created REST Resource "{0}".
0550.0059	Deleting REST Resource "{0}".
0550.0060	Deleted REST Resource "{0}".
0550.0061	Retrieving details for REST Resource "{0}".

- 0550.0062      **Updating REST Resource "{0}".**
- 0550.0063      **Updated REST Resource "{0}".**
- 0550.0064      **Checking for REST Resource "{0}".**
- 0550.0065      **Listing REST Resources.**
- 0550.0066      **Creating Provider "{0}".**
- 0550.0067      **Created Provider "{0}".**
- 0550.0068      **Deleting Provider "{0}".**
- 0550.0069      **Deleted Provider "{0}".**
- 0550.0070      **Retrieving details for Provider "{0}".**
- 0550.0071      **Updating Provider "{0}".**
- 0550.0072      **Updated Provider "{0}".**
- 0550.0073      **Checking for Provider "{0}".**
- 0550.0074      **Listing Providers.**
- 0550.0075      **Creating Service "{0}".**

---

0550.0076	Created Service "{0}".
0550.0077	Deleting Service "{0}".
0550.0078	Deleted Service "{0}".
0550.0079	Retrieving details for Service "{0}".
0550.0080	Updating Service "{0}".
0550.0081	Updated Service "{0}".
0550.0082	Checking for Service "{0}".
0550.0083	Listing Services.
0550.0084	Unable to load connection manager factory: {0}.
0550.0085	"{0}" is not a supported Connector type.
0550.0086	Error while publishing provider "{0}".
0550.0087	Error while installing provider "{0}".
0550.0088	Enter a valid Package Name.
0550.0089	Development package for provider "{0}" does not exist.

0550.0090            **Could not create the Provider package under "{0}".**

0550.0091            **Publishing the package for Provider "{0}"...**

0550.0092            **Package published for Provider "{0}".**

0550.0093            **Installing Provider "{0}"...**

0550.0094            **Installed Provider "{0}".**

0550.0095            **Creating a temporary folder for provider "{0}" under "{1}"...**

0550.0096            **Moving the Provider artifacts under "{0}"...**

0550.0097            **Copying the file "{0}" under "{1}"...**

0550.0098            **Creating the package zip file for provider "{0}"...**

0550.0099            **Moving the provider package "{0}" to "{1}"...**

0601.0002            **Error:{0}**

**Explanation**        An exception occurred while parsing the fetched data from database

**Action**              Check whether CloudStreams 'JDBC Pool alias ' is configured properly

**Add\_Group**         **Add Group...**

**AuditLogger\_Editor\_Name – Logged Fields**

**Bundle-Name**      **CloudStreams Service Editors**

**Bundle-Vendor**    **Software AG**

**BusinessObjectPage\_Available\_Obj\_Label – Available Business Objects**

**BusinessObjectPage\_Filter\_Text – type filter text**

<b>CLS.0010.0014E</b>	<b>PolicyGateway.shutdownMyService - Unable to remove service:{0}. Error:{1}</b>
<b>Explanation</b>	A virtual service was not completely removed during CloudStreams package unload.
<b>Action</b>	No action is necessary if the error occurred while the Integration Server was shutting down.
<b>CLS.0010.0020W</b>	<b>Consumer file [{0}] could not be found! Could not load Consumer information into CloudStreams.</b>
<b>Explanation</b>	Consumer definitions defined in the CloudStreams admin are persisted in an XML file in a directory under the WmCloudStreams package.
<b>Action</b>	No action is necessary if no consumers have been defined; otherwise, please contact support.
<b>CLS.0010.0062E</b>	<b>Unable to get the password for callback identifier: {0}</b>
<b>Explanation</b>	Error while retrieving the cleartext password from the encrypted passman file store.
<b>Action</b>	Review the CloudStreams STS configuration, else this is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the Integration Server Administrator's package management menu > WmCloudStreams package's list of services, if available.
<b>CLS.0010.0083W</b>	<b>Non-fatal CloudStreams package initialization error. {0}, {1}</b>
<b>Explanation</b>	CloudStreams encountered an error during an upgrade processing step, after the package initialization has completed.
<b>Action</b>	Verify whether the overinstall upgrade steps were followed as defined in the documentation, else this is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.

<b>CLS.0010.0085E</b>	<b>CloudStreams - Unable to find ClusterStateCache</b>
<b>Explanation</b>	CloudStreams defines a cache for this information even when the product is not clustered.
<b>Action</b>	Contact support.
<b>CLS.0010.0190E</b>	<b>Error initializing CloudStreams keystore manager's keystore. Path:{0}, Cause: {1}</b>
<b>Action</b>	Verify whether a valid keystore file exists for this path and the file permissions allow for the Integration Server to read the file.
<b>CLS.0010.0212E</b>	<b>Endpoint connection timeout duration expected as a number but was not a number ({0})</b>
<b>Explanation</b>	A virtual service was deployed with an invalid connection timeout specified for its native provider endpoint.
<b>Action</b>	Review the advanced endpoint configuration in CentraSite and redeploy the service if necessary.
<b>CLS.0010.0214E</b>	<b>Either both keystore and key alias must be specified or none for the SSL configuration; KeyStore alias = [{0}]; Key alias = [{0}]</b>
<b>Explanation</b>	A virtual service with a native provider SSL endpoint was deployed with an invalid advanced endpoint configuration. The endpoint must have a valid alias for both the keystore file and the keystore entry aliases as defined in the Integration Server, or it can have no aliases defined at all.
<b>Action</b>	Update the advanced endpoint configuration and redeploy the virtual service to CloudStreams.
<b>CLS.0010.0217E</b>	<b>Error occurred while getting the password for handle {0} from the passman.</b>
<b>Explanation</b>	An attempt to retrieve a cleartext password from a passman encrypted file store failed.
<b>Action</b>	This is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.
<b>CLS.0010.0218E</b>	<b>Error occurred when storing the password for handle {0} in the passman.</b>
<b>Explanation</b>	An attempt to save a password in a passman encrypted file store failed during CloudStreams STS configuration.
<b>Action</b>	This is an internal error. Contact Support. Produce a diagnostic zip file by running the cloustreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.

---

<b>CLS.0010.0220E</b>	<b>Error while converting the given WS-Policy component to string.</b>
<b>Explanation</b>	Cloudstreams was unable to parse policy elements used in producing request security tokens (RST) to a configured security token service (STS).
<b>Action</b>	This is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.
<b>CLS.0010.0702E</b>	<b>CloudStreams upgrade/migration has been interrupted due to an error. Details: {0}</b>
<b>Explanation</b>	This log message may occur when the CloudStreams package loads during the Integration Server restart after an overinstall. It indicates that the upgrade was not successful and further actions are required.
<b>Action</b>	Depending on the error message, the following options are available: 1) Resolve the issue which is causing the upgrade to fail and then restart the Integration Server to see if the upgrade completes successfully. 2) Delete the cloudstreamsUpgrade.xml file from the installation path: \${IS_HOME}/packages/WmCloudStreams/ directory. This is the file that causes CloudStreams to perform its upgrade step. If this action is taken, the CloudStreams configuration will have to be re-entered manually through the Integration Server Administrator's UI. 3) Contact Support. Whenever the Integration Server is restarted, CloudStreams will attempt to perform an upgrade as long as its cloudstreamsUpgrade.xml file is present in the package directory.
<b>CLS.0010.0706E</b>	<b>CloudStreams Upgrade, unable to read required file. {0}</b>
<b>Explanation</b>	This log message may occur when the CloudStreams package loads during the Integration Server restart after an overinstall. This message implies that the OS user running the Integration Server does not have adequate permissions to read the file referenced in the error message.
<b>Action</b>	Review user and file permissions and make necessary adjustments to ensure the file can be read.
<b>CLS.0010.0707E</b>	<b>During CloudStreams upgrade, a configuration file is missing a required entry element key attribute. {0}, File path: {1}</b>
<b>Explanation</b>	This log message may occur when the CloudStreams package loads during the Integration Server restart after an overinstall. The cloudstreamsUpgrade.xml file used to control a CloudStreams overinstall upgrade is corrupted. It is missing a reference to an attribute containing a path to an archive of the previous CloudStreams version, prior to the overinstall.
<b>Action</b>	Contact Support.

<b>CLS.0010.0708E</b>	<b>During CloudStreams upgrade, a configuration file entry element key attribute is not as expected: {0}, expected this value: {1}, but found: {2}, File path: {3}</b>
<b>Explanation</b>	This log message may occur when the CloudStreams package loads during the Integration Server restart after an overinstall. The cloudstreamsUpgrade.xml file used to control a CloudStreams overinstall upgrade is corrupted.
<b>Action</b>	Contact Support.
<b>CLS.0010.0709E</b>	<b>CloudStreams Upgrade, unable to find the required file. Expected location: {0}</b>
<b>Explanation</b>	This log message may occur when the CloudStreams package loads during the Integration Server restart after an overinstall. The backup file archive containing the CloudStreams package prior to the overinstall upgrade cannot be found.
<b>Action</b>	Contact support.
<b>CLS.0010.0711E</b>	<b>CloudStreams Upgrade, unable to delete configuration file. CloudStreams upgrade task will continue to execute after each Integration Server startup until this file is removed. Path: {0}</b>
<b>Explanation</b>	This log message may occur when the CloudStreams package loads during the Integration Server restart after an overinstall. Verify that the OS user account running the Integration Server has the necessary permissions to delete the file.
<b>Action</b>	If the log messages suggest the upgrade ran successfully, this file can be deleted; otherwise, contact support.
<b>CLS.0010.0712E</b>	<b>During CloudStreams upgrade, a configuration file is not a valid xml. Unable to parse it. {0}, Details: {1}</b>
<b>Explanation</b>	This log message may occur when the CloudStreams package loads during the Integration Server restart after an overinstall. The cloudstreamsUpgrade.xml file is corrupted.
<b>Action</b>	Contact Support.
<b>CLS.0010.0717W</b>	<b>CloudStreams Upgrade, Could not find Default STS configuration file: {0} in archived zip file</b>
<b>Explanation</b>	The default STS configuration file was not found when performing an overinstall upgrade.
<b>Action</b>	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the CloudStreams package's list of services in IS Admin's package management menu if available.

---

<b>CLS.0010.0718E</b>	<b>During CloudStreams upgrade, a configuration file has an unexpected element key attribute, {0}, with value. {1}. The configuration file path is: {2}</b>
<b>Explanation</b>	This log message may occur when the CloudStreams package loads during the Integration Server restart after an overinstall. The cloudstreamsUpgrade.xml file is corrupted.
<b>Action</b>	Contact Support.
<b>CLS.0010.0719E</b>	<b>CloudStreams Upgrade, Could not find Default STS configuration file: {0} following upgrade; Skipping migrating configuration data!</b>
<b>Explanation</b>	CloudStreams was unable to locate the default STS configuration file during an overinstall upgrade.
<b>Action</b>	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in IS Admin's package management menu if available.
<b>CLS.0010.0720W</b>	<b>CloudStreams Upgrade, Could not load Default STS client configuration; Skipping migrating configuration data</b>
<b>Explanation</b>	The default STS configuration file was not found when performing an overinstall upgrade.
<b>Action</b>	This is an internal error. Contact Customer Care. Please produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in IS Admin's package management menu if available.
<b>CLS.0050.0279D</b>	<b>Callback not removed for message id, "{0}". Receiver: {1}, Properties: {2}</b>
<b>Explanation</b>	When a service is invoked, the state for the invocation is stored in a callbackStore map until the response is returned. The callback object was not found in the map for the given message id.
<b>Action</b>	No action is necessary unless memory runs low. In that event, please contact support.
<b>CLS.0050.0280D</b>	<b>Message receiver not found for message id: "{0}", Properties: {1}</b>
<b>Explanation</b>	Synapse callback receiver used to process the provider response is not found.
<b>Action</b>	Please contact support.

<b>CLS.0050.0281D</b>	<b>Outbound message id not found. "{0}", Properties: {1}</b>
<b>Explanation</b>	The message id used to correlate a native provider request was not found.
<b>Action</b>	Please contact support.
<b>CLS.0050.0408E</b>	<b>Authentication failed for user {0}</b>
<b>Explanation</b>	Invalid basic authentication credentials were included in the Authorization header sent to a virtual service that has a "Require HTTP Basic Authentication" runtime security policy.
<b>Action</b>	The web service consumer should include proper credentials and resend the service request.
<b>CLS.0050.0608E</b>	<b>Error occurred when adding Timestamp to SOAP Envelope: {0}</b>
<b>Explanation</b>	CloudStreams was unable to insert a WS security timestamp element to the request's security header sent to the native provider.
<b>Action</b>	Review the configured ESB "AddTimestamp" service call for virtual service and redeploy if incorrect, else this is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.
<b>CLS.0070.0010E</b>	<b>Incoming SOAP request does not contain the 'Authorization' header. This service requires the HTTP Basic Authentication token to be present!</b>
<b>Explanation</b>	No Authorization header was sent to a virtual service that has a "Require HTTP Basic Authentication" runtime security policy.
<b>Action</b>	The web service consumer should include proper credentials and resend the service request.
<b>CLS.0070.0032E</b>	<b>Unable to create Schema for this service "{0}". Schema validation may not succeed.</b>
<b>Explanation</b>	CloudStreams was unable to initialize the schema parser for a virtual service with a "Validate Schema" runtime policy. This error occurs when a consumer sends CloudStreams a service request.
<b>Action</b>	Review the schemas defined in the virtual service, make corrections, and then redeploy the virtual service if necessary; otherwise, this is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.

---

<b>CLS.0070.0071W</b>	<b>The ESB service name specified for InvokeESB cloudstreams cannot be empty.</b>
<b>Explanation</b>	A virtual service was deployed containing an ESB service invocation step containing an invalid or missing service name.
<b>Action</b>	Review all service invocations from the "Processing steps" configuration for the virtual service, and redeploy if necessary.
<b>CLS.0070.0072E</b>	<b>The 'service' attribute is required for the InvokeESB cloudstreams definition.</b>
<b>Explanation</b>	The deployed virtual service configuration is corrupted.
<b>Action</b>	This is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.
<b>CLS.0070.0073W</b>	<b>Did not invoke ESB service, because the service name was either empty or invalid (must be of the form folder1.folder2:service)</b>
<b>Explanation</b>	A virtual service was deployed containing an ESB service invocation step with an invalid or missing service name.
<b>Action</b>	This warning is logged when a virtual service request is executed. See the action defined for CLS.0070.0071.
<b>CLS.0070.0074E</b>	<b>Unknown mediator : {0}</b>
<b>Explanation</b>	Synapse mediators are used in the "In Sequence", "Out Sequence", and "Error Sequence" steps defined for virtual services. These Mediators are predefined and registered in CloudStreams.
<b>Action</b>	Contact Support.
<b>CLS.0101.0099D</b>	<b>Unable to remove session context for connector service with this session token. "{0}"</b>
<b>Explanation</b>	The CloudStreams transport listener should remove the session context for a connector service when it is no longer needed.
<b>Action</b>	Please contact support if available IS heap memory runs low.
<b>CLS.0102.0056E</b>	<b>Package name and service name must be specified for deploying service(s).</b>
<b>Action</b>	Verify whether the service has an associated package and then redeploy; otherwise, contact Support.

**CLS.0102.0057E**      **Unable to deploy. A virtual service with the name "{0}" already exists in the package "{1}".**

**Action**              Confirm whether the package association is correct and consider undeploying previous virtual services before deployment. Otherwise, contact Support.

**CLS.0200.0045E**      **Error saving EhCache configuration file: {0}**

**Explanation**        CloudStreams was unable to save its configuration file used for the Terracotta cache component.

**Action**              This is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.

**CLS.0200.0046E**      **Could not find the specified EhCache configuration file: {0}**

**Explanation**        The Terracotta cache configuration file for CloudStreams caches could not be found during package startup.

**Action**              This is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.

**CLS.0201.0003E**      **PgMen incoming handler found no sie event for {0}, mep: {1}**

**Explanation**        A service invoke event (sie) contains basic attributes of a service invocation. The sie should have been created by another Axis2 handler, but it was not or is no longer accessible from this handler.

**Action**              The service request will be permitted to execute, but the invocation may not be accurately tracked by the policy engine.

**CLS.0201.0004E**      **Exception in Outgoing fault handler while creating sie. serviceName: {0} cause: {1}**

**Explanation**        An error occurred while trying to create a service invoke event (sie) in a policy engine's Axis2 fault handler.

**Action**              The original service fault will be returned to the caller, but the service invocation may not be accurately tracked by the policy engine.

---

<b>CLS.0201.0005E</b>	<b>Unable to create an sie event in outgoing fault handler. serviceName: {0}</b>
<b>Explanation</b>	A service invoke event (sie) contains basic attributes of a service invocation. The sie should have been created by this or another Axis2 handler, but it was not or is no longer accessible.
<b>Action</b>	The original service fault will be returned to the caller, but the service invocation may not be accurately tracked by the policy engine.
<b>CLS.0201.0006E</b>	<b>PgMen incomingHandler found an event with unexpected state {0}</b>
<b>Explanation</b>	The policy engine relies on Axis2 handlers executing during specific phases in order to capture all the attributes of a service invocation. These attributes are stored in a service invoke event (sie) for each inbound or outbound phase.
<b>Action</b>	The sie data for this specific service invocation may be corrupted. The data contained in dependent policy engine events may be affected. Contact support.
<b>CLS.0201.0007E</b>	<b>Exception in incomingHandler. msgId: {0} details {1}</b>
<b>Explanation</b>	An error occurred while executing a policy engine Axis2 handler.
<b>Action</b>	A service fault will be returned to the caller, but the service invocation may not be accurately tracked by the policy engine.
<b>CLS.0201.0008E</b>	<b>PgMen incoming handler had no service name in message context for this msgId {0}</b>
<b>Explanation</b>	The inbound policy engine Axis2 handler did not find an Axis2 service registered in the message context; however, the service request will be permitted to execute and the response will be returned to the caller.
<b>Action</b>	Since the virtual service was not identified for this service request, the invocation will not be tracked by the policy engine.
<b>CLS.0201.0011E</b>	<b>PgMen incoming handler could not find service operation in axis2 message context. Service name: {0}</b>
<b>Explanation</b>	The inbound policy engine Axis2 handler did not find an Axis operation registered in the message context; however, the service request will be permitted to execute and the response will be returned to the caller.
<b>Action</b>	Since the virtual service operation was not identified for this service request, the invocation will not be tracked by the policy engine.

<b>CLS.0201.0013E</b>	<b>PgMen outgoing handler found an event with unexpected state {0}, sie Dump: {1}</b>
<b>Explanation</b>	The policy engine relies on Axis2 handlers executing during specific phases in order to capture all the attributes of a service invocation. These attributes are stored in a service invoke event (sie) for each inbound or outbound phase.
<b>Action</b>	The sie data for this specific service invocation may be corrupted. The data contained in dependent policy engine events may be affected. Contact support.
<b>CLS.0201.0015E</b>	<b>Policy {0} forbids invocation of service {1} for scope {2}</b>
<b>Explanation</b>	This service invocation was rejected because a policy rule was breached in the policy engine.
<b>Action</b>	No action is necessary.
<b>CLS.0201.0016E</b>	<b>PgMen outgoing handler expected service {0} and invokeId: {1}, but cached event had {2} and {3}</b>
<b>Explanation</b>	The invocation id for this execution thread's handler does not match the id that is stored on the current service invocation event (sie).
<b>Action</b>	This error suggests that data corruption may have occurred. Please contact support.
<b>CLS.0201.0017E</b>	<b>PgMen outgoing handler had no service name in message context for this msgId {0}</b>
<b>Explanation</b>	The inbound policy engine Axis2 handler did not find an Axis2 service registered in the message context; however, the service request will be permitted to execute and the response will be returned to the caller.
<b>Action</b>	Since the virtual service was not identified for this service request, the invocation will not be tracked by the policy engine.
<b>CLS.0201.0018E</b>	<b>Axis service object not found in message context.</b>
<b>Explanation</b>	The inbound policy engine Axis2 handler did not find an Axis2 service registered in the message context; however, the service request will be permitted to execute and the response will be returned to the caller.
<b>Action</b>	Since the virtual service was not identified for this service request, the invocation will not be tracked by the policy engine.
<b>CLS.0201.0023W</b>	<b>No native service provider endpoint for {0}.</b>
<b>Explanation</b>	The policy engine's Axis2 outbound handlers found no endpoint reference in message context.
<b>Action</b>	No further action is necessary if an endpoint was located at a later point during execution and the service was invoked.

---

<b>CLS.0201.0024E</b>	<b>Exception caught while constructing the reason expression: {0}</b>
<b>Explanation</b>	An error occurred while processing a virtual service's error sequence step.
<b>Action</b>	No further action is necessary. The soap fault will be returned without the fault's reason content.
<b>CLS.0201.0034W</b>	<b>BaseHandler - No PolicyViolationDetector found, skipping analysis</b>
<b>Explanation</b>	The spring component for detecting policy violations is missing.
<b>Action</b>	Verify the WmCloudStreams package loaded successfully; otherwise please contact support to verify the CloudStreams spring configuration is not corrupted.
<b>CLS.0201.0040E</b>	<b>PgMen incoming event handler encountered an error executing PgMen outgoing FAULT handler. Cause: {0}</b>
<b>Explanation</b>	An error occurred while processing one of the Axis2 fault handlers used by the policy engine during a service invocation.
<b>Action</b>	A service fault will be returned to the caller, but the service invocation may not be accurately tracked by the policy engine.
<b>CLS.0201.0041E</b>	<b>PgMen outgoing handler could not find service operation in axis2 message context. Service name: {0}</b>
<b>Explanation</b>	The outbound policy engine Axis2 handler did not find an Axis operation registered in the message context; however, the service request will be permitted to execute and the response will be returned to the caller.
<b>Action</b>	Since the virtual service operation was not identified for this service request, the invocation will not be tracked by the policy engine.
<b>CLS.0201.0042E</b>	<b>PgMen outgoing FAULT handler could not find service operation in axis2 message context. Service name: {0}</b>
<b>Explanation</b>	The outbound policy engine Axis2 fault handler did not find an Axis operation registered in the message context; however, the service request will be permitted to execute and the response will be returned to the caller.
<b>Action</b>	Since the virtual service operation was not identified for this service request, the invocation may not be accurately tracked by the policy engine.
<b>CLS.0201.0043E</b>	<b>PgMen outgoing handler encountered error publishing an event. Missing sie event.</b>
<b>Explanation</b>	A service invoke event (i.e. sie) contains basic attributes of a service invocation. The sie should have been created by another Axis2 handler, but it was not or is no longer accessible from this handler.
<b>Action</b>	The service request will be permitted to execute, but the invocation may not be accurately tracked by the policy engine.

<b>CLS.0201.0044E</b>	<b>PgMen outgoing handler encountered error publishing an event. sie event is missing service name.</b>
<b>Explanation</b>	A service invoke event (i.e. sie) contains basic attributes of a service invocation. The sie should have been created by another Axis2 handler, but it was not or is no longer accessible from this handler.
<b>Action</b>	The service request will be permitted to execute, but the invocation may not be accurately tracked by the policy engine.
<b>CLS.0201.0046E</b>	<b>No UUID generator bean (bean id={0}) configured, using java.util.UUID</b>
<b>Explanation</b>	The spring configuration is missing an expected component for UUID generation.
<b>Action</b>	CloudStreams is falling back to an alternate UUID factory; however, this error suggests the configuration may be corrupted. Verify the WmCloudStreams package loaded successfully; otherwise, please contact support to verify.
<b>CLS.0202.0003E</b>	<b>Cannot create a PolicyEnforcer using a null/empty service name {0}</b>
<b>Explanation</b>	A virtual service must be associated to a policy before it may be applied at runtime.
<b>Action</b>	Verify the policy configuration filter is correct, the policy is active, and redeploy the affected virtual services.
<b>CLS.0202.0004E</b>	<b>Cannot create a PolicyEnforcer using a null PolicyInfo reference</b>
<b>Explanation</b>	The policy enforcer is a runtime object that requires a policy info configuration element.
<b>Action</b>	This should not happen under normal circumstances. Please contact support.
<b>CLS.0203.0062E</b>	<b>ControllingNodeLocker.run, thread id({0}), expected Ehcache, found ({1})</b>
<b>Explanation</b>	Unexpected content was returned in the Terracotta cluster status cache.
<b>Action</b>	This is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.
<b>CLS.0203.0065E</b>	<b>ControllingNodeLocker.run, thread id({0}), caught ({1}/{2}) attempting to get a lock, thread dies.</b>
<b>Explanation</b>	CloudStreams encountered an error trying to obtain a lock on the controlling node in a Terracotta cluster.
<b>Action</b>	This is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.

<b>CLS.0203.0070I</b>	<b>ClusterStatusCache - cache manager for {0} returned null CacheCluster reference. Not clustered.</b>
<b>Explanation</b>	CloudStreams was unable to obtain a reference to the configured Terracotta cluster.
<b>Action</b>	This is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.
<b>CLS.0203.0071I</b>	<b>{0} - getCluster(ClusterScheme.TERRACOTTA) threw exception {1}, using schema NONE</b>
<b>Explanation</b>	An attempt to get Terracotta cluster configuration details failed.
<b>Action</b>	If CloudStreams is configured for a Terracotta cluster, this is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.
<b>CLS.0203.0072E</b>	<b>ClusterStatusCache - thread id({0}) attempts to release {1} lock, but does not hold it.</b>
<b>Explanation</b>	An attempt to release the lock on the node controller in a Terracotta cluster failed.
<b>Action</b>	This is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.
<b>CLS.0203.0073E</b>	<b>Error initializing JAXB Context: {0}</b>
<b>Explanation</b>	Initialization for the cached global or registered consumers deployed to CloudStreams has failed.
<b>Action</b>	This is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.
<b>CLS.0203.0075E</b>	<b>ControllingNodeLocker.run, thread id({0}), caught {1} attempting to ask about lock status, thread dies.</b>
<b>Explanation</b>	The thread defining the controlling node in a CloudStreams cluster encountered an error.
<b>Action</b>	This is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.

<b>CLS.0203.0076E</b>	<b>Unable to get the cache named {0} from the cache manager {1}</b>
<b>Explanation</b>	CloudStreams encountered an error while accessing one of the Terracotta caches.
<b>Action</b>	This is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.
<b>CLS.0203.0081E</b>	<b>{0}, thread id({1}), caught {2}/{3} attempting to release lock. Thread dies.</b>
<b>Explanation</b>	CloudStreams encountered an error while releasing the lock on the controlling node in the Terracotta cluster.
<b>Action</b>	This is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.
<b>CLS.0203.0082E</b>	<b>EhcacheClusterStatusCache, thread id({0}), caught {1}/{2} attempting to update the controlling lock in the cache.</b>
<b>Explanation</b>	CloudStreams encountered an error while updating the controlling node in a Terracotta cluster.
<b>Action</b>	This is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.
<b>CLS.0203.0100W</b>	<b>Thread interrupted when trying to obtain {0} lock for the cache {1}</b>
<b>Explanation</b>	While CloudStreams was attempting to obtain a lock on a cache entry key, its thread was interrupted.
<b>Action</b>	No action is necessary if CloudStreams is functioning normally.
<b>CLS.0203.0101E</b>	<b>Unable to {0} lock the {1} cache for key {2} after waiting {3} ms</b>
<b>Explanation</b>	CloudStreams failed to lock a cache key in the expected time period.
<b>Action</b>	No action is necessary if CloudStreams is functioning normally
<b>CLS.0203.0103E</b>	<b>{0} task in thread {1} threw this: {2}</b>
<b>Explanation</b>	During CloudStreams shutdown, an error occurred in the controlling node of a Terracotta cluster.
<b>Action</b>	Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.

<b>CLS.0204.0008E</b>	<b>Unable to access spring bean config bean : {0}. Is there a problem with CloudStreams spring config file?</b>
<b>Explanation</b>	The interval manager thread pool is missing from its spring configuration file.
<b>Action</b>	Contact support.
<b>CLS.0204.0013W</b>	<b>No value defined in {0} cache for this key: {1}</b>
<b>Explanation</b>	The policy engine's interval manager component creates and updates a global interval counter that is used for both clustered and non-clustered installations.
<b>Action</b>	It is normal for this warning to appear once or twice when the WmCloudStreams package is reloaded or during Integration Server startup. If this warning message continues to occur, verify the WmCloudStreams package loaded successfully; otherwise, please contact support.
<b>CLS.0205.0062E</b>	<b>UddiPerformanceMetricsSender - unable to publish metrics over UDDI for service: {0}, message: {1}</b>
<b>Explanation</b>	This log message is produced when CloudStreams is unable to publish performance metrics results to CloudStreams. When reviewing the content, note that some exception details may have originated from the CentraSite product hosting the UDDI server. Errors can range from improper CloudStreams configuration, OS resource issues, network connectivity, or issues with the CentraSite installation.
<b>Action</b>	Depending on the errors logged in the CloudStreams UI, one of the following actions may prove more relevant: (1) Verify whether the CentraSite configuration information regarding UDDI is correct for the CloudStreams UI. (2) Verify whether the hostname or IP address is reachable from the computer running the CloudStreams instance. (3) Verify whether the CentraSite instance and its repository is up and accessible.
<b>CLS.0205.0063E</b>	<b>Unable to initialize UddiClientAdapter due to a missing password for username: {0}.</b>
<b>Explanation</b>	This log message is produced when CloudStreams is unable to publish performance metrics results to CloudStreams. A password was not found in the encrypted store for the user, configured in the CentraSite panel of the CloudStreams UI.
<b>Action</b>	Verify whether the password is entered and the configuration was successfully saved for the CentraSite configuration screen in the CloudStreams UI.
<b>CLS.0205.0064E</b>	<b>Error connecting to the CentraSite UDDI registry running on {0}://{1}:{2}. Error: {3}</b>
<b>Explanation</b>	This log message may be produced under the following situations: (1) During CloudStreams package startup. (2) CentraSite configuration entered in the CloudStreams UI is saved, but a connection to the UDDI server fails for these settings. (3) CloudStreams attempts to publish performance metrics but fails during its regular scheduled interval.
<b>Action</b>	Verify whether CentraSite configuration values in the CloudStreams UI are correct and CentraSite is up and running.

<b>CLS.0205.0067E</b>	<b>Error disconnecting to CentraSite UDDI registry running on {0}://{1}:{2}. Error: {3}</b>
<b>Explanation</b>	This log message may be seen during the following situations: (1) During CloudStreams package shutdown. (2) While CloudStreams is initializing communications with the CentraSite UDDI server after encountering an error during runtime or saving configuration values in the CloudStreams UI.
<b>Action</b>	Refer the "Action" text for 0205.0064.
<b>CLS.0205.0602E</b>	<b>Missing "{0}" JDBC destination pool from spring configuration.</b>
<b>Explanation</b>	A CloudStreams configuration file may be corrupted and a necessary configuration element may be missing.
<b>Action</b>	Contact Support.
<b>CLS.0205.0603E</b>	<b>Jdbc destination sender expected a JdbcEvent object but received: "{0}"</b>
<b>Explanation</b>	The JDBC destination sender event component received an unexpected event type.
<b>Action</b>	Contact Support.
<b>CLS.0205.0604E</b>	<b>JDBC destination sender encountered an SQL Exception while generating "{0}" events. Error Code: {1} Cause: {2}</b>
<b>Explanation</b>	The CloudStreams JDBC destination sender component encountered an SQL exception while sending a runtime event.
<b>Action</b>	Verify whether the CloudStreams functional alias in the Integration Server Administrator is configured for a JDBC pool. Verify whether the database is operational and then restart the functional alias pool. Verify whether the CloudStreamsEvents database component tables installed using the Common Database Component are still defined, and the JDBC pool credentials and URL defined in the Integration Server are correct. If it still fails, contact Support.
<b>CLS.0205.0605D</b>	<b>JDBC destination sender took {0} ms to get a connection out of the data source.</b>
<b>Explanation</b>	If the '0205 MEN - Events' CloudStreams logging component is set to 'DEBUG', CloudStreams issues a log message if the time it takes to get a JDBC connection exceeds a predefined threshold as defined in the CloudStreams pg-jdbc.xml file. The current default is 50 milliseconds.
<b>Action</b>	No action is necessary.

---

<b>CLS.0205.0606D</b>	<b>JDBC destination sender took {0} ms to get a prepared statement out of connection with this SQL: {1}.</b>
<b>Explanation</b>	If the '0205 MEN - Events' CloudStreams logging component is set to 'DEBUG', then CloudStreams issues a log message if the time it takes to get a JDBC prepared statement exceeds a predefined threshold as defined in the CloudStreams pg-jdbc.xml file. The current default is 50 milliseconds.
<b>Action</b>	No action is necessary.
<b>CLS.0205.0609D</b>	<b>JDBC destination sender took {0} ms to close the prepared statement and connection.</b>
<b>Explanation</b>	If the '0205 MEN - Events' CloudStreams logging component is set to 'DEBUG', then CloudStreams issues a log message if the time it takes to close a JDBC connection exceeds a predefined threshold as defined in the CloudStreams pg-jdbc.xml file. The current default is 50 milliseconds.
<b>Action</b>	No action is necessary.
<b>CLS.0205.0610E</b>	<b>JDBC event requires at least one SQL clause to be valid.</b>
<b>Explanation</b>	The CloudStreams JDBC component is in an invalid state.
<b>Action</b>	Contact Support.
<b>CLS.0205.0611D</b>	<b>JDBC destination sender took {0} ms to insert a batch of {1} "{2}" events. AutoCommit enabled on driver? {3}, Transaction Isolation level? {4}</b>
<b>Explanation</b>	If the '0205 MEN - Events' CloudStreams logging component is set to 'DEBUG', then CloudStreams issues a log message if the time it takes to execute a batch of runtime event inserts into the database, exceeds a predefined threshold as defined in the CloudStreams pg-jdbc.xml file. The current default is 500 milliseconds.
<b>Action</b>	No action is necessary unless the time is extremely large. In that case, consider reducing the 'pg.jdbc.batchSize' property in the CloudStreams pg-config.properties file. This will cause the JDBC destination sender to send updates to the database server in smaller batches.
<b>CLS.0205.0612E</b>	<b>JDBC destination sender cannot use a read-only connection object to insert events.</b>
<b>Explanation</b>	The functional alias used by the CloudStreams JDBC destination sender is configured for a read-only transaction model in the Integration Server Administrator.
<b>Action</b>	Change the configured transaction model so that it supports updates to the database.

<b>CLS.0205.0614E</b>	<b>The JDBC event SQL range should be between 0 and {0}, {1} is out of range.</b>
<b>Explanation</b>	The CloudStreams JDBC component is in an invalid state.
<b>Action</b>	Contact Support.
<b>CLS.0205.0615E</b>	<b>The JDBC performance metrics processor expected only one return key, but "{0}" were found.</b>
<b>Explanation</b>	The CloudStreams JDBC component is in an invalid state.
<b>Action</b>	Contact Support.
<b>CLS.0205.0616E</b>	<b>The JDBC performance metrics processor expected two SQL statements, but "{0}" were found.</b>
<b>Explanation</b>	The CloudStreams JDBC component is in an invalid state.
<b>Action</b>	Contact Support.
<b>CLS.0205.0617E</b>	<b>The JDBC performance metrics processor is missing the returned primary key upon SQL insert.</b>
<b>Explanation</b>	The database did not return the 'event_pk' primary key column for the event inserted into the cloudstreams_metrics_event table.
<b>Action</b>	Verify whether the database is functioning properly; otherwise, contact Support.
<b>CLS.0205.0618E</b>	<b>Jdbc event is in a bad state. Data type count "{0}" does not equal column value count "{1}"</b>
<b>Explanation</b>	The Jdbc event destination component is in an invalid state.
<b>Action</b>	Contact Support.
<b>CLS.0205.0619W</b>	<b>Jdbc driver doesn't support returned named SQL columns from Insert statement. Trying "Statement.RETURN_GENERATED_KEYS" mode.</b>
<b>Explanation</b>	The Jdbc event destination component will attempt to use named columns for returning the database-generated primary key after inserting a row. If the database driver does not support this feature, this log message is raised, and the component will use another method to return the inserted primary key.
<b>Action</b>	No action required unless other SQLException errors are raised.

---

<b>CLS.0206.0035W</b>	<b>MAC cache update {0} operation took {1} ms to complete for {2} SIEs. This could cause lock attempts for tallying metrics statistics in MAC cache to fail.</b>
<b>Explanation</b>	An update to the policy engine metrics data took longer than expected. When the duration of this task is longer than the configured lock request timeout, tasks can be lost when they fail to obtain exclusive locks.
<b>Action</b>	Review the Integration Server performance, increase the advanced property for lock timeout <code>pg.PgMenSharedCacheManager.lockTimeOut</code> , and the restart Integration Server. Otherwise, if this happens very frequently, contact Support. Produce a diagnostic zip file by running the <code>cloudstreams.util:diagnosticZip</code> service from the <code>WmCloudStreams</code> package's list of services in the Integration Server Administrator's package management menu, if available.
<b>CLS.0207.0002E</b>	<b>DCPool spring configuration {0} missing a workQueue property? No workQueue was instantiated.</b>
<b>Explanation</b>	The referenced policy engine thread pool is missing its in-memory work queue configuration.
<b>Action</b>	Possibly the <code>*-pgmen.xml</code> spring configuration file is corrupted. Contact support.
<b>CLS.0207.0003E</b>	<b>Work queue capacity must be greater than 0. Value {0} is invalid.</b>
<b>Explanation</b>	One of the advanced configuration properties in the <code>*-config.properties</code> file has an invalid queue size.
<b>Action</b>	These values are not exposed in the admin UI. Review the values in the <code>pg-config.properties</code> or <code>wst-config.properties</code> file and verify the policy engine work queue sizes are greater than 0.
<b>CLS.0207.0009W</b>	<b>{0} thread pool shutdown - caught {1} while awaiting pool termination.</b>
<b>Explanation</b>	A policy engine pool's thread was interrupted while waiting for graceful shutdown to complete.
<b>Action</b>	No action is needed.
<b>CLS.0300.0001E</b>	<b>"{0}" is an unknown connection factory alias</b>
<b>Explanation</b>	The classname specified in <code>wst-core.xml</code> spring bean configuration for the implementation map of the <code>'clientConnectionFactoryManager'</code> bean is not in the classpath.
<b>Action</b>	Contact support.

<b>CLS.0300.0002E</b>	<b>Class "{0}" for alias "{1}" does not implement the IConnectionManager interface.</b>
<b>Action</b>	Contact Support.
<b>CLS.0300.0003E</b>	<b>"{0}" is an unknown connection pool alias.</b>
<b>Action</b>	Contact Support.
<b>CLS.0300.0004E</b>	<b>Unknown configuration group alias, "{0}"</b>
<b>Explanation</b>	A CloudStreams connector descriptor has a configurable group in its connection configuration that is not valid for the connection manager.
<b>Action</b>	Contact support.
<b>CLS.0300.0007E</b>	<b>Error creating connection alias "{0}".</b>
<b>Explanation</b>	A CloudStreams connection manager had an error during its initialization phase.
<b>Action</b>	Contact support.
<b>CLS.0300.0010E</b>	<b>Unknown field key "{0}" from connection factory alias "{1}"</b>
<b>Explanation</b>	All managed connection configuration fields must have a unique key name including custom configuration fields. 'cn.providerURL' is an example.
<b>Action</b>	Review CloudStreams connector configuration to locate source of the unknown field name.
<b>CLS.0300.0011E</b>	<b>Attempt to unregister an unregistered connection configuration instance, "{0}"</b>
<b>Action</b>	Contact Support.
<b>CLS.0300.0012E</b>	<b>Attempt to reference an unregistered connection configuration instance, "{0}"</b>
<b>Action</b>	Contact Support.
<b>CLS.0300.0013T</b>	<b>Duplicate field "{0}" exists in configurable group "{1}" of connection factory</b>
<b>Explanation</b>	Each managed connection configuration field may only exist once for the select configurable groups.
<b>Action</b>	In normal cases, some common fields are shared across groups intended to be mutually exclusive (e.g. Amazon Web Service groups) when used with service configurations.

---

<b>CLS.0300.0014E</b>	<b>Duplicate custom field "{0}" exists in configurable group "{1}" of connection factory</b>
<b>Explanation</b>	Each managed connection configuration custom field must have a unique key name associated with it.
<b>Action</b>	Review all custom configuration fields created in CloudStreams and verify each name is unique.
<b>CLS.0300.0016E</b>	<b>Unexpected connection configuration implementation type, {0}</b>
<b>Action</b>	Contact Support.
<b>CLS.0300.0017W</b>	<b>Error {0}, while releasing resources for connection configuration "{0}"</b>
<b>Explanation</b>	An error was encountered while releasing a managed connection pool instance during connection manager shutdown.
<b>Action</b>	No action is necessary.
<b>CLS.0300.0019E</b>	<b>Invalid HTTP method selected, "{0}"</b>
<b>Explanation</b>	An invalid HTTP method was referenced.
<b>Action</b>	Locate the source of the invalid method and change it to a valid HTTP method.
<b>CLS.0300.0020E</b>	<b>Unknown service method implementation: {0}</b>
<b>Action</b>	Contact Support.
<b>CLS.0300.0021E</b>	<b>Missing connection configuration alias is required.</b>
<b>Explanation</b>	CloudStreams connector services must have a configured managed connection alias.
<b>Action</b>	Configure or recreate the connector service so it has a managed connection pool alias.
<b>CLS.0300.0022E</b>	<b>Connection configuration alias "{0}" requires at least one configurable group.</b>
<b>Action</b>	Review CloudStreams connectors and locate the connector that does not have at least one configurable group for all of its connections.
<b>CLS.0300.0025E</b>	<b>Unknown service request implementation: {0}</b>
<b>Action</b>	Contact Support.

<b>CLS.0300.0026E</b>	<b>Error getting property value for "{0}" from class {1}, Error: {2}</b>
<b>Explanation</b>	CloudStreams was unable to access the value for one of its managed connection's configurable fields.
<b>Action</b>	Inspect the configuration value and verify it is valid for the specified field.
<b>CLS.0300.0027E</b>	<b>Error setting property value "{0}" for "{1}" from class {2}, Error: {3}</b>
<b>Explanation</b>	CloudStreams was unable to access the value for one of its managed connection's configurable fields.
<b>Action</b>	Inspect the configuration value and verify it is valid for the specified field.
<b>CLS.0300.0028E</b>	<b>Error introspecting class {0}, Error: {1}</b>
<b>Action</b>	Contact Support.
<b>CLS.0300.0029E</b>	<b>Custom config field "{0}" expected group alias "{1}" instead of "{2}"</b>
<b>Action</b>	Contact Support.
<b>CLS.0300.0030E</b>	<b>Custom config field is missing required key property.</b>
<b>Explanation</b>	All managed connection custom configuration fields must have a unique key name.
<b>Action</b>	Review CloudStreams connector configuration to locate source of the missing field key.
<b>CLS.0300.0031E</b>	<b>Illegal attempt to binding or register a connection configuration "{0}". It is already registered.</b>
<b>Explanation</b>	When a connection configuration (e.g. a managed connection pool) is enabled, its alias name must be unique.
<b>Action</b>	Change the connection configuration alias name so it will be unique.
<b>CLS.0300.0032E</b>	<b>Attempt to create a connection configuration instance "{0}" with missing required groups. Required groups: {1}</b>
<b>Action</b>	Review the affected CloudStreams connection configuration and ensure that it includes the required configurable group.

---

<b>CLS.0300.0033W</b>	<b>Error unloading connection manager alias "{0}" from factory. Details: {1}</b>
<b>Explanation</b>	An error was encountered while releasing a managed connection pool instance during connection manager shutdown.
<b>Action</b>	No action is necessary.
<b>CLS.0300.0034E</b>	<b>Connection factory manager overwrote key "{0}" for implementation. Old value: {1}, New value: {2}</b>
<b>Action</b>	Contact Support.
<b>CLS.0300.0035E</b>	<b>Missing connection configuration instance for the alias "{0}"</b>
<b>Explanation</b>	An error occurred while attempting to obtain a socket connection for an unknown connection configuration instance.
<b>Action</b>	Confirm a connection configuration exists and is enabled with this alias name.
<b>CLS.0300.0036E</b>	<b>The config value "{0}" for field "{1}" is not supported.</b>
<b>Action</b>	Contact Support.
<b>CLS.0300.0038E</b>	<b>Configuration value missing for required field "{0}" in connection configuration "{1}"</b>
<b>Action</b>	Provide a value for the connection configuration's required field and then enable it again.
<b>CLS.0300.0039E</b>	<b>Configuration value for field "{0}" is not serializable. Value: {1}</b>
<b>Action</b>	Contact Support.
<b>CLS.0300.0040E</b>	<b>Error creating native service provider endpoint, {0} with service context, {1} Error: {2}</b>
<b>Explanation</b>	The native provider endpoint could not be defined as a valid URI.
<b>Action</b>	Review the configured value and ensure it is properly formatted as a URI.
<b>CLS.0300.0041E</b>	<b>An IO or timeout exception is encountered for invoke "{0}" method for connection alias "{1}". Check the network connectivity/proxy setting. Details: {2}</b>
<b>Explanation</b>	A service invocation error occurred due to a network IO exception on the socket.
<b>Action</b>	Verify whether the connection configuration is correct, the endpoint is valid, the service is running, the connect and read timeouts are not too short, including the network connectivity and proxy settings.

<b>CLS.0300.0042E</b>	<b>Unexpected exception encountered for invoke "{0}" method for connection alias "{1}". Details: {2}</b>
<b>Explanation</b>	An unexpected service invocation error occurred that is not caused by an IO socket exception.
<b>Action</b>	Verify connection configuration is correct.
<b>CLS.0300.0044E</b>	<b>Error while activating Authentication scheme, "{0}" for connection alias, "{1}". Details: {2}</b>
<b>Explanation</b>	An error occurred activating an authentication scheme (e.g. OAuth, Basic Auth, etc.).
<b>Action</b>	Review configuration details if the authentication scheme has its own configuration; otherwise, please contact support.
<b>CLS.0300.0045E</b>	<b>HTTP version "{0}" is not supported. Must be HTTP/0.9, HTTP/1.0 or HTTP/1.1</b>
<b>Action</b>	Ensure that the connection configuration specifies the correct HTTP version.
<b>CLS.0300.0046E</b>	<b>Error in request headers configuration for "{0}" alias. Names: {1}, Values: {2}, Details: {3}</b>
<b>Explanation</b>	Error validating request headers encountered while enabling a connection configuration.
<b>Action</b>	Verify the comma-delimited list of request headers and values are valid.
<b>CLS.0300.0047E</b>	<b>Error in request headers configuration for "{0}" alias. Names: {1}, Values: {2}, Names and values are required.</b>
<b>Action</b>	Verify whether the comma-delimited list of header names and values have non-whitespace characters for each entry.
<b>CLS.0300.0051E</b>	<b>Error invoking connection from connection configuration instance "{0}". It is configured for an unknown web proxy alias "{1}"</b>
<b>Explanation</b>	A connection configuration has a configuration field for an unknown IS proxy server.
<b>Action</b>	Confirm the proxy alias entered for the connection configuration exists in the Integration Server 'Proxy Server' configuration.
<b>CLS.0300.0052W</b>	<b>Unable to register scheme for web proxy alias, "{0}", in connection configuration: "{1}"</b>
<b>Explanation</b>	A connection configuration's web proxy alias could not be initialized when it was enabled, so the configuration is enabled with no proxy server support.
<b>Action</b>	Verify the Integration Server proxy server configuration identified by the alias is valid.

---

<b>CLS.0300.0054E</b>	<b>Cannot create OAuthCredentials for OAuth version {0}</b>
<b>Action</b>	Contact Support.
<b>CLS.0300.0055E</b>	<b>Cannot create SchemeFactory for OAuth version {0}</b>
<b>Action</b>	Contact Support.
<b>CLS.0300.0056E</b>	<b>OAuthAliasHelperFactory cannot work with null token alias name</b>
<b>Explanation</b>	A connection configuration instance requires a valid OAuth alias.
<b>Action</b>	Verify the oauth token configuration in the CloudStreams admin has a proper alias.
<b>CLS.0300.0057E</b>	<b>OAuthAliasHelperFactory cannot find token alias name {0}</b>
<b>Explanation</b>	A connection configuration instance references an unknown OAuth token alias.
<b>Action</b>	Verify the connection configuration references the correct alias as defined in the oauth token configuration in the CloudStreams admin.
<b>CLS.0300.0058E</b>	<b>OAuthAliasHelperFactory cannot work with null OAuthAccessDetailsManager bean. Not configured.</b>
<b>Action</b>	Contact Support.
<b>CLS.0300.0059I</b>	<b>CloudStreams outbound connector "{0}" encountered an IO exception while reading the native provider response. Consider setting the advanced connection configuration, increasing timeout values for 'Connection Timeout' and 'Socket Read Timeout' properties. Also, optionally change 'Retry on Response Failure' to true while 'Connection Retry Count ' is greater than 0 if it is safe to send requests more than once.</b>
<b>Explanation</b>	The default timeout value for 'Connection Timeout' and 'Socket Read Timeout' property may not be enough. The default settings for the default connector outbound connection factory will not attempt to resend a request if it believes it was received by the provider. If there is no harm to send a request more than once to a provider, enable the 'Retry on Response Failure' advanced property (cn.retryIfRequestSentOk).
<b>Action</b>	In case the network is slow or the backend processing takes longer than usual, increase the 'Connection Timeout' and the 'Socket Read Timeout' values. Also, optionally change 'Retry on Response Failure' to true while 'Connection Retry Count ' is greater than 0 if it is safe to send requests more than once.

<b>CLS.0300.0061E</b>	<b>Error instantiating object for hostname verifier: "{0}", Details: {1}</b>
<b>Explanation</b>	This configuration field must be set to a fully qualified classname that implements the Apache HttpClient interface: org.apache.http.conn.ssl.X509HostnameVerifier. This field is used to perform validation checks between a native provider host and its server SSL certificate.
<b>Action</b>	Specify "org.apache.http.conn.ssl.AllowAllHostnameVerifier" to accept all hosts or "org.apache.http.conn.ssl.StrictHostnameVerifier" for strict enforcement. Leaving this field blank implies using the "AllowAllHostnameVerifier" option.
<b>CLS.0300.0062E</b>	<b>Hostname verifier class, "{0}", must implement org.apache.http.conn.ssl.X509HostnameVerifier interface.</b>
<b>Action</b>	Specify a valid fully qualified classname in the CloudStream package's java classpath that implements the interface or leave the field blank to disable hostname verification. See CLS.0300.0061 for more details.
<b>CLS.0300.0063E</b>	<b>Error initializing registered provider's SSL context for the "{0}" algorithm. Details: {1}</b>
<b>Action</b>	Contact Support.
<b>CLS.0300.0064E</b>	<b>Error reading a key store for this file: {0}, Details: {1}</b>
<b>Action</b>	Verify whether the file path exists, the file is a valid keystore file, and Integration Server has privileges to read the file.
<b>CLS.0300.0065E</b>	<b>Error reading a trust store for this file: {0}, Details: {1}</b>
<b>Action</b>	Verify whether the file path exists, is a valid trust store file, and the Integration Server has OS privileges to read the file; otherwise, contact Support.
<b>CLS.0300.0066E</b>	<b>Error initializing entrust security provider's socket factory "{0}" algorithm. Details: {1}</b>
<b>Action</b>	Unless this is a correctable error with one of the keystore files, contact Support.
<b>CLS.0300.0069E</b>	<b>Unable to verify hostname. unknown SSL socket type: {0}</b>
<b>Explanation</b>	Unable to perform hostname verification on a native provide endpoint.
<b>Action</b>	Contact support.

---

<b>CLS.0300.0070E</b>	<b>Unknown HCAdapter event type: {0}</b>
<b>Explanation</b>	An enabled connection configuration instance has received a notification event from an unknown origin. (These events are used to keep configuration instances in synch with related Integration Server configuration changes when possible.)
<b>Action</b>	Contact support.
<b>CLS.0300.0072E</b>	<b>Error creating socket factory, "{0}". Details: {1}</b>
<b>Explanation</b>	Unable to create the SSL socket factory for use with a connection configuration.
<b>Action</b>	Review the configuration and make corrections if possible; otherwise, please contact support.
<b>CLS.0300.0073D</b>	<b>Error during onCleanup for socket factory for "{0}". Details: {1}</b>
<b>Explanation</b>	Nonfatal error encountered while release resources associated with a connection configuration's SSL socket factory.
<b>Action</b>	No action should be necessary for this debug message.
<b>CLS.0300.0075E</b>	<b>Unable to initialize the key store for file: {0}, Details: {1}</b>
<b>Action</b>	Ensure that the file path exists, is a valid keystore file, and the Integration Server has OS privileges to read the file; otherwise, contact Support.
<b>CLS.0300.0076E</b>	<b>Unable to create key store object from this file. {0}, exists? {1}, readable? {2}</b>
<b>Action</b>	Ensure that the file path exists, is a valid keystore file, and the Integration Server has OS privileges to read the file; otherwise, contact Support.
<b>CLS.0300.0077E</b>	<b>Unable to access client's private key and certificate for this key alias: {0}, in this keystore file: {1}, Details: {2}</b>
<b>Action</b>	Ensure that the configuration alias used to access the client key is correct for the specified keystore; otherwise, contact Support.
<b>CLS.0300.0081E</b>	<b>Unable to register or unregister connfactory event subscriber instance, {0}. Event type: {1} Details: {2}</b>
<b>Explanation</b>	An error occurred while the connection factory registered its event listener used to receive notifications for some Integration Server configuration changes.
<b>Action</b>	Contact support.

<b>CLS.0300.0082E</b>	<b>Error during onInit for socket factory, "{0}". Details: {1}</b>
<b>Explanation</b>	Error during SSL socket factory initialization.
<b>Action</b>	Contact support.
<b>CLS.0300.0083E</b>	<b>Error initializing security provider's socket factory. Key store alias: {0}, trust store alias: {1}, details: {2}</b>
<b>Explanation</b>	Error during SSL socket factory initialization.
<b>Action</b>	Contact support.
<b>CLS.0300.0093E</b>	<b>Error initializing connfactory cert chain verifier for trust store file: {0}, Details: {1}</b>
<b>Explanation</b>	Error occurred while building the list of certificates that the connection configuration will trust.
<b>Action</b>	Contact support.
<b>CLS.0300.0096E</b>	<b>Error while attempting to verify trust for this cert: {0}, Cert will not be trusted. Details: {1}</b>
<b>Action</b>	No action is necessary unless this certificate is trusted; otherwise, contact Support.
<b>CLS.0300.0099E</b>	<b>Credentials configurable group failed to bind configuration field "{0}", with an illegal value "{1}".</b>
<b>Explanation</b>	The "cr.authSchemeType" configuration field is limited to a closed set of possible values.
<b>Action</b>	It should not be possible to specify an unknown value through the CloudStreams connection admin UI, so please contact support.
<b>CLS.0300.0100E</b>	<b>Protocol configurable group failed to bind configuration field "{0}", with an illegal value "{1}".</b>
<b>Explanation</b>	The "pr.protocolVersion" configuration field is limited to a closed set of possible values.
<b>Action</b>	It should not be possible to specify an unknown value through the CloudStreams connection admin UI, so please contact support.
<b>CLS.0300.0105E</b>	<b>Error creating buffered entity for request message. Details: {0}</b>
<b>Action</b>	If problem persists, contact Support.

---

<b>CLS.0300.0106E</b>	<b>Connection configuration instance "{0}" contains a custom key "{1}" with no prefix. Suggest "cx.{1}"</b>
<b>Explanation</b>	All connection fields including custom fields must have a key name that may be used to identify the field. A dot-separated prefix must be prepended to the field name's key. 'cx.' is the suggested convention for custom fields.
<b>Action</b>	Change the specified key for the custom configuration field so it contains a valid prefix.
<b>CLS.0300.0107E</b>	<b>AWS Activator called with wrong token instance. {0}</b>
<b>Explanation</b>	The Amazon web service auth scheme requires auth tokens to produce the content necessary to invoke an AWS service.
<b>Action</b>	Please contact support.
<b>CLS.0300.0108E</b>	<b>Missing auth token required field for Amazon Web Service authentication. {0}</b>
<b>Explanation</b>	The Amazon web services require auth tokens to build a proper service request that can be authenticated.
<b>Action</b>	Review configuration and ensure all token fields are provided.
<b>CLS.0300.0110E</b>	<b>AWS v2 signature auth scheme requires application/x-www-form-urlencoded content.</b>
<b>Explanation</b>	Amazon web service signature version 2 cannot be used unless request message is using the required Content-Type.
<b>Action</b>	Correct service configuration to use the appropriate content type for the request.
<b>CLS.0300.0111E</b>	<b>Unable to update native provider URI for AWS {0} signature auth scheme.</b>
<b>Explanation</b>	The Amazon signature auth scheme appends additional security tokens as query parameters on the native provider endpoint.
<b>Action</b>	Please contact support.
<b>CLS.0300.0112E</b>	<b>Unexpected request type received in AWS {0} auth scheme. {1}</b>
<b>Action</b>	Contact Support.
<b>CLS.0300.0114E</b>	<b>Unsupported algorithm. {0} AWS {1} signature scheme must be one of these. {2}</b>
<b>Explanation</b>	The service must be configured to use one of the valid algorithms for signing the request.
<b>Action</b>	Review connection configuration.

<b>CLS.0300.0115E</b>	<b>"{0}" header is missing from {1} AWS signature auth scheme.</b>
<b>Explanation</b>	The AWS authentication scheme requires this header.
<b>Action</b>	Verify the service configuration is correct.
<b>CLS.0300.0117D</b>	<b>Expected one value for AWS Param key: {0}, Found: {1}</b>
<b>Explanation</b>	This AWS auth scheme parameter was expected to have only one value.
<b>Action</b>	Please contact support.
<b>CLS.0300.0118T</b>	<b>Provider endpoint: {0}, AWS Canonical Request: {1}</b>
<b>Explanation</b>	AWS signature calculations require requests to be in a specific format.
<b>Action</b>	Use this message to debug AWS signature authentication failures.
<b>CLS.0300.0119T</b>	<b>Provider endpoint: {0}, AWS String to sign: {1}</b>
<b>Explanation</b>	AWS signature calculations create a specific string to sign when generating signatures for the request.
<b>Action</b>	Use this message to debug AWS signature authentication failures.
<b>CLS.0300.0120T</b>	<b>Provider endpoint: {0}, AWS Canonical Request: {1}</b>
<b>Explanation</b>	AWS v2 signatures calculations require requests to be in a specific format.
<b>Action</b>	Use this message to debug AWS signature authentication failures.
<b>CLS.0300.0122T</b>	<b>Added 'Host' header: {0}</b>
<b>Explanation</b>	Amazon v4 signature requests require a "Host" header be sent with request.
<b>Action</b>	Use this message to debug AWS signature authentication failures.
<b>CLS.0300.0123E</b>	<b>Unknown AWS auth scheme type.</b>
<b>Explanation</b>	The AuthSchemeActivatorFactory received auth tokens for an unsupported signature scheme. type: {0}
<b>Action</b>	Please contact support.
<b>CLS.0300.0124E</b>	<b>Unsupported AWS auth scheme type. {0}</b>
<b>Explanation</b>	An auth scheme must be declared for the service, so it can be properly authenticated by the AWS server.
<b>Action</b>	Verify the connector configuration is correct.

<b>CLS.0300.0125E</b>	<b>Unexpected error binding configuration authTokens to AWS configuration. Details: {1}</b>
<b>Explanation</b>	Unable to enable a connection configuration with AWS configuration group because of an unexpected error.
<b>Action</b>	Please contact support.
<b>CLS.0301.0001E</b>	<b>This IData request is missing NSRecord metadata. Namespace details may be impacted.</b>
<b>Explanation</b>	NSRecord metadata (document types) are used to marshal between IData and Axiom (XML) data models.
<b>Action</b>	Contact support.
<b>CLS.0301.0002E</b>	<b>IDataBuilder error translating IData message into an Axiom element. Details: {0}</b>
<b>Explanation</b>	An error occurred while translating a message from IData to the Axiom (XML) data model.
<b>Action</b>	Verify the IData content is valid.
<b>CLS.0301.0003E</b>	<b>IDataBuilder missing required parameters. Either an input stream or an IData object is needed to process a message.</b>
<b>Explanation</b>	The component that translates IData to Axiom (XML) data model is missing a required value.
<b>Action</b>	Review service that produced this error and verify a reference to either an input stream or IData content was provided.
<b>CLS.0301.0005E</b>	<b>IDataMessageFormatter error translating Axiom element to IData for service: {0} and operation: {1}. Details: {2}</b>
<b>Explanation</b>	An error occurred while translating a message from Axiom (XML) to the IData data model.
<b>Action</b>	Review service that produced this error and verify the message content is valid.
<b>CLS.0301.0006E</b>	<b>IDataMessageFormatter error encoding IData message to stream for service: {0} and operation: {1}. Details: {2}</b>
<b>Explanation</b>	An error occurred while serializing a message.
<b>Action</b>	Review service that produced this error and verify the message content is valid.

<b>CLS.0301.0008E</b>	<b>IDataMessageFormatter is unable to resolve provider targetAddress as a valid URL. {0}</b>
<b>Action</b>	Verify whether the target address endpoint is a valid URL.
<b>CLS.0301.0009E</b>	<b>CloudStreams message mappings for CloudStreams virtual service invocation "{0}" is invalid. Details: {1}</b>
<b>Explanation</b>	A CloudStreams service has one or more message mapping steps which are invalid.
<b>Action</b>	Review the errors and correct the message mapping statements for this connector.
<b>CLS.0301.0010D</b>	<b>CloudStreams mapping step, Error applying map step to message. Service invocation aborted? {0}. Source: {1}, Target: {2}, Details: {3}</b>
<b>Explanation</b>	Debug message showing an exception that occurred while executing a mapping step.
<b>Action</b>	If the mapping step is not required, then no additional action is necessary.
<b>CLS.0301.0011E</b>	<b>CloudStreams mapping step, Unknown map type "{0}"</b>
<b>Explanation</b>	There are various categories of mapping steps. (e.g. HEADER, COOKIE, XPATH, IDATA, etc.).
<b>Action</b>	Review the connector configuration and fix the invalid mapping step.
<b>CLS.0301.0012E</b>	<b>CloudStreams mapping step, Illegal attempt to set a value on a LITERAL mapping step named, "{0}"</b>
<b>Explanation</b>	A mapping step cannot have a 'LITERAL' target. In other words, a LITERAL cannot have a value assigned to it; it can only be used as a source value in mapping expressions.
<b>Action</b>	Review the connector configuration and fix the invalid mapping step.
<b>CLS.0301.0013E</b>	<b>CloudStreams mapping step, mapping step is missing "{0}" map value.</b>
<b>Explanation</b>	The mapping step is not properly configured. It is missing required elements.
<b>Action</b>	Review the connector configuration and fix the invalid mapping step.
<b>CLS.0301.0014E</b>	<b>CloudStreams mapping step, mapping step is missing "context" for map value. Must be IN or OUT.</b>
<b>Explanation</b>	A mapping step has a specific context depending on where it is used during service invocations. The 'IN' context implies the expression executes before the service invocation. The 'OUT' context implies the expression executes after the service invocation.
<b>Action</b>	Review the connector configuration and fix the invalid mapping step.

---

<b>CLS.0301.0016E</b>	<b>CloudStreams mapping step, XPath map value expression contains namespace prefix, but no namespaces were provided with map. {0}</b>
<b>Explanation</b>	An XPATH mapping step must include a namespace prefix and URI declaration(s) if the XPath expression contains a colon-delimited prefix reference.
<b>Action</b>	Review the connector configuration and fix the invalid mapping step.
<b>CLS.0301.0017E</b>	<b>CloudStreams mapping step, XPath map step unable to set value on node. "{0}" did not find any nodes in message.</b>
<b>Explanation</b>	An XPATH mapping step executed but the expression returned no matching nodes from the Axiom (XML) message.
<b>Action</b>	Review the connector configuration and verify the expression is valid if matches were expected.
<b>CLS.0301.0019E</b>	<b>CloudStreams mapping step, Error executing XPath map step to set value for this XPath: "{0}" and this value: {1}, Details: {2}</b>
<b>Explanation</b>	An error occurred while executing an XPath expression meant to set a value on an Axiom (XML) message.
<b>Action</b>	Review the connector configuration and fix the invalid mapping step if this error was unexpected.
<b>CLS.0301.0020E</b>	<b>CloudStreams mapping step, XPath map step unable to set value on node. "{0}" found {1} nodes in message.</b>
<b>Explanation</b>	An XPATH mapping step's XPath expression against an Axiom (XML) message did not resolve to a single node.
<b>Action</b>	Review the connector configuration and fix the invalid mapping step if this error was unexpected.
<b>CLS.0301.0021E</b>	<b>CloudStreams mapping step, Error executing XPath map step to get value for this XPath: "{0}", Details: {1}</b>
<b>Explanation</b>	An error occurred while executing an XPath expression meant to get a value from a message.
<b>Action</b>	Review the connector configuration and fix the invalid mapping step if this error was unexpected.

<b>CLS.0301.0023E</b>	<b>CloudStreams mapping step. Error executing validation for mappings. Details: {0}</b>
<b>Action</b>	Review the connector configuration and then fix the invalid mapping step(s).
<b>CLS.0301.0025E</b>	<b>CloudStreams mapping step, XPath "{0}" expression returned unsupported XML element type, "{1}". Expressions must resolve to a single element or attributes only.</b>
<b>Explanation</b>	CloudStreams XPATH mapping expressions may only reference text or attributes nodes in the XML message.
<b>Action</b>	Review the connector configuration and fix the invalid mapping step.
<b>CLS.0301.0031E</b>	<b>No validator instance to validate CloudStreams message content using IS doc type validation.</b>
<b>Explanation</b>	CloudStreams was unable to create a validator for a message against its associated doc type(s).
<b>Action</b>	Review the doctypes for the affected request or response message.
<b>CLS.0301.0032E</b>	<b>Error while validating CloudStreams message content using IS doc type validation. Details: {0}</b>
<b>Explanation</b>	An unexpected error occurred while validating a message against its associated doctype(s).
<b>Action</b>	Review the doctypes for the affected request or response message.
<b>CLS.0301.0033E</b>	<b>Cloudstreams message is not valid based on expected doc type. Details: {0}</b>
<b>Explanation</b>	A CloudStreams request or response message did not have the expected structure as defined by its associated doctype(s).
<b>Action</b>	Review the connector service configuration and state of the native provider to resolve the underlying error with the unexpected message structure.
<b>CLS.0301.0034E</b>	<b>The configured translator service "{0}" is missing "static" method declaration for its "translate" method.</b>
<b>Explanation</b>	A mapping statement may have an optional attribute that defines a fully qualified classname for a java class. This class must contain a public static method named 'translate'.
<b>Action</b>	Verify the connector configuration's mapping statement is correct and the class has the expected 'translate' public static method and is in the CloudStreams class loader.

---

<b>CLS.0301.0035E</b>	<b>Error resolving configured translate service "{0}", Details: {1}</b>
<b>Action</b>	Verify whether the connector configuration's mapping statement is correct and the class is in the CloudStreams class loader. See CLS.0301.0034 for more details.
<b>CLS.0301.0037E</b>	<b>Unknown builder type "{0}" for message data handler.</b>
<b>Explanation</b>	No Axis2 message Builder implementation is registered for this builder type (key).
<b>Action</b>	Contact support.
<b>CLS.0301.0038E</b>	<b>Unknown message formatter type "{0}" for message data handler.</b>
<b>Explanation</b>	No Axis2 MessageFormatter implementation is registered for this message type (key).
<b>Action</b>	Contact support.
<b>CLS.0301.0042E</b>	<b>No response code and method mapping found for connector "{0}" and response code "{1}" and httpMethod "{2}"</b>
<b>Explanation</b>	The invoked connector service has returned an unexpected response code for the httpMethod used to execute the request. So it is considered to be a fault condition regardless of the provider response code.
<b>Action</b>	A fault message will be returned to the pipeline. If the virtual service is configured to return the native provider fault, then this provider response will be included.
<b>CLS.0301.0045E</b>	<b>Unknown message handler phase. {0}</b>
<b>Explanation</b>	CloudStreams message handlers have predefined inbound and outbound phases for both request and response message processing.
<b>Action</b>	Contact support.
<b>CLS.0301.0046E</b>	<b>Unknown message builder content type, "{0}" for "{1}" message phase</b>
<b>Explanation</b>	The message mapping in CloudStreams wst-transport.xml configuration file is incorrect.
<b>Action</b>	Contact support.
<b>CLS.0301.0047E</b>	<b>Unknown message formatter content type, "{0}" for "{1}" message phase</b>
<b>Explanation</b>	The message mapping in CloudStreams wst-transport.xml configuration file is incorrect.
<b>Action</b>	Contact support.

**CLS.0301.0062E**      **Error instantiating builder class: {0} for content type: {1}. Details: {2}**  
**Explanation**      The message mapping in CloudStreams wst-transport.xml or Integration Server's axis2.xml configuration file is incorrect.  
**Action**              Contact support.

**CLS.0301.0063E**      **Error instantiating message formatter class: {0} for content type: {1}. Details: {2}**  
**Explanation**      The message mapping in CloudStreams wst-transport.xml or Integration Server's axis2.xml configuration file is incorrect.  
**Action**              Contact support.

**CSHeaderTreeTable\_Active\_Label – Active**

**CSHeaderTreeTable\_Add\_Header\_Label – Add Header**

**CSHeaderTreeTable\_Add\_Label – Add**

**CSHeaderTreeTable\_Add\_Row\_Label – Add Row**

**CSHeaderTreeTable\_Default\_Value\_Label – Default Value**

**CSHeaderTreeTable\_Delete\_Header\_Label – Delete Header**

**CSHeaderTreeTable\_Delete\_Row\_Label – Delete Row**

**CSHeaderTreeTable\_Headers\_Label – Header(s)**

**CSHeaderTreeTable\_Headers\_Not\_Available\_Message – No headers are available to select because no operation is selected on the Operation tab.**

**CSHeaderTreeTable\_Headers\_Not\_Available\_Title – Headers Not Available**

**CSHeaderTreeTable\_Headers\_Not\_Found\_Title – Headers Not Found**

**CSHeaderTreeTable\_Insert\_Row\_Label – Insert Row**

**CloudServiceCreationPage\_Error – Error**

**CloudServiceCreationPage\_Page\_Description – Specify the location and name for the new cloud connector service.**

**CloudServiceCreationPage\_Page\_Title – Create a New Cloud Connector Service**

**CloudServiceCreationPage\_Warning – Warning**

**CloudStreams\_Provider\_Project\_Label – CloudStreams Provider Project**

**Explanation**            Menu item label for creating a new CloudStreams Provider Project.

**ConnectionAliasSelectionPage\_No\_Connections\_Error\_Message – No connection pools have been created for the selected cloud application provider.**

**ConnectionAliasSelectionPage\_Page\_Description – Select the connection pool that the cloud connector service "{0}" will use to connect to the cloud provider.**

**ConnectionAliasSelectionPage\_Search\_Message\_Text – type connection name**

**ConnectionAliasSelectionPage\_Text\_Available\_Connection\_Pool – Available Connection Pools**

**ConnectionAliasSelectionPage\_Text\_Name – Name**

**ConnectorParameterTable\_6 – Add Parameter**

**ConnectorParameterTable\_8 – Delete Parameter**

**ConnectorParameterTable\_Add\_Parameter\_Label – Add Parameter**

**ConnectorParameterTable\_Data\_Type\_Label – Data Type**

**ConnectorParameterTable\_Default\_Value\_Label – Default Value**

**ConnectorParameterTable\_Delete\_Parameter\_Label – Delete Parameter**

**ConnectorParameterTable\_Name\_Label – Name**

**ConnectorParameterTable\_Shift\_Down – Shift Down**

**ConnectorParameterTable\_Shift\_Down\_Label – Shift Down**

**ConnectorParameterTable\_Shift\_Up – Shift Up**

**ConnectorParameterTable\_Shift\_Up\_Label – Shift Up**

**ConnectorParameterTable\_Type\_Label – Type**

**ConnectorServiceWizard\_Wizard\_Title – New Cloud Connector Service**

**Deploylog\_Table\_ServerHost – CloudStreams Server Host**

**Deploylog\_Table\_ServerVersion – CloudStreams Server Version**

**Deploylog\_table\_serverColumn – CloudStreams Server Alias**

<b>Description</b>	<b>Description:</b>
<b>ECLS.0300.0008</b>	<b>Connection configuration alias "{0}" already registered. Original config was replaced with alias "{1}"</b>
<b>Explanation</b>	Managed connection pool aliases must be unique across all CloudStreams connectors.
<b>Action</b>	Locate the duplicate alias name and change its name to ensure no two pool configurations share the same alias.

**Error\_Generic\_Message – Operation failed because of the following reason, please check the log files for more details.**

**Error\_Unable\_To\_Reach\_Destination – Unable to reach the Resource Destination. Check your Network connection and Hostname.**

**Group\_Column\_Connection\_Description – Connection Description**

**Group\_Column\_Connection\_Name – Connection Name**

**Group\_Column\_Connection\_Type – Connection Type**

**HeaderPage\_Page\_Name – Headers**

**HeaderPage\_Section\_Input – Input**

**HeaderPage\_Section\_Output – Output**

**HeaderSelectionPage\_Available\_Headers\_Label – Available Headers**

**HeaderSelectionPage\_Description – Select Header**

**HeaderSelectionPage\_Filter\_Text\_Message – type filter text**

**HeaderSelectionPage\_Header\_Label – Header**

**HeaderSelectionPage\_Title – Header**

**HeaderSelectionWizard\_Title – Select Header**

**IOEditor\_Editor\_Name – Input/Output**

**ISCloudConnectionNode\_Node\_Name – Cloud Connection**

**Info\_Configure\_Login\_Operation – Configure a Login Operation under Services.**

**Info\_Configure\_Logout\_Operation – Configure a Logout Operation under Services.**

**Is\_Hidden            Hide**

**Lookup\_SODescribe soDescribe**

**Lookup\_Selection\_Dialog – Lookup Selection Dialog**

**Lookup\_Selection\_Dialog\_Message – Select a Lookup.**

**Lookup\_Selection\_Dialog\_Title – Lookup Selection**

**New\_Group\_Wizard\_Description** – Select a group.

**New\_Group\_Wizard\_Title** – New Group

**OperationPage\_Business\_Object\_Label** – Business Object:

**OperationPage\_Con\_Pool\_Label** – Connection Pool:

**OperationPage\_Name** Operation

**OperationPage\_Operation\_Change\_Title** – Operation change confirmation

**OperationPage\_Provider\_Type\_Label** – Connector Type:

**OperationPage\_Virtual\_Svc\_Label** – Connector Virtual Service:

**OperationPage\_operation\_Label** – Operation:

**ParameterPage\_Form\_Text\_Parameters** – Parameters

**ParameterPage\_Page\_Name** – Parameters

**ParameterWizardPage\_Field\_Column** – Field

**ParameterWizardPage\_Field\_Label\_Column** – Field Label

**ParameterWizardPage\_Native\_Column** – Native

**ParameterWizardPage\_SOAP\_TYPE\_Column – SOAP Type**

**ProviderSelectionPage\_Name – Name**

**ProviderSelectionPage\_No\_Providers\_Error\_Message – No CloudStreams connectors are installed.**

**ProviderSelectionPage\_Page\_Description – Select a CloudStreams Connector instance to use for the cloud connector service "{0}".**

**ProviderSelectionPage\_Page\_title – Select the Connector**

**ProviderSelectionPage\_SearchLabel – Available Connectors**

**ProviderSelectionPage\_Search\_Message\_Text – type connector name**

**ProviderSelectionPage\_Type – Type**

**ProviderSelectionPage\_Version – Version**

**Publisher Publisher:**

**RetrieveBusinessObjs\_Operation\_Cancelled – Business Objects retrieval operation was canceled.**

**RetrieveBusinessObjs\_TaskName – Getting Business Objects...**

**ServiceSelectionPage\_No\_Services\_Error\_Message – No services exist for the selected cloud application provider.**

**ServiceSelectionPage\_Page\_Description – Select the service that will be used for the cloud connector service "{0}".**

**ServiceSelectionPage\_Page\_Title – Select the Service**

**ServiceSelectionPage\_Search\_Label – Available Services**

**ServiceSelectionPage\_Search\_Message\_Text – type service name**

**ServiceSelectionPage\_Text\_Name – Name**

**SummaryPage\_Business\_Object – Business Object:**

**SummaryPage\_ConnectionPool – Connection Pool:**

**SummaryPage\_Name Name:**

**SummaryPage\_Namespace – Namespace:**

**SummaryPage\_Operation – Operation:**

**SummaryPage\_Package\_Name – Package:**

**SummaryPage\_Page\_Name – Summary**

**SummaryPage\_Provider – Connector:**

**SummaryPage\_Provider\_Type – Connector Type:**

**SummaryPage\_Service\_Name – Service Name:**

**SummaryPage\_Version\_Number – Version Number:**

**TCLS.0300.0121**      **Added 'X-Amz-Date' header: {0}**  
**Explanation**      Amazon v4 signature requests require a 'Date' or 'X-Amz-Date' header be sent with request.  
**Action**              Use this message to debug AWS signature authentication failures.

**WST-2360**            **Updated CloudStreams Connector service "{0}" of package "{1}".**  
**Explanation**      Cloud connector service updation has failed. See the server/error logs for details.  
**Action**              Ensure that the cloud service which you are updating is not locked or in readonly mode. If the problem still persists, restart the Integration Server. If the problem still remains, contact Support.

**category.name**      **ESB**

**content-type.name** **CloudService**

**g11ndsp\_run\_as\_user** – **Run As User**

**service.editor.name** – **CloudStreams Service Multi-page Editor**

**wizard.name**        **Cloud Connector Service**

# 8 Command Central Messages

---

<b>CCEADME0000</b>	<b>Unknown node alias.</b>
<b>Explanation</b>	A node with the specified alias is not found.
<b>Action</b>	Provide a valid node alias.
<b>CCECAME0000</b>	<b>The specified flatfile location does not exist.</b>
<b>Explanation</b>	The flatfile repository was not located at the specified location on the file system.
<b>Action</b>	Specify a valid location for the flatfile repository.
<b>CCECAME0001</b>	<b>A repository already exists at the same location.</b>
<b>Explanation</b>	Two or more repositories cannot point to the same location.
<b>Action</b>	Specify a unique location for the new repository.
<b>CCECAME0002</b>	<b>A repository with this name already exists.</b>
<b>Explanation</b>	The name of the repository is not unique.
<b>Action</b>	Check the repository name and provide a unique name for the repository.
<b>CCECAME0003</b>	<b>Repository name, type and location cannot be empty or missing.</b>
<b>Explanation</b>	The name, type, and location are required parameters when creating asset type repositories.
<b>Action</b>	Specify values for all required parameters.

<b>CCECAME0004</b>	<b>Name and type cannot be empty or missing.</b>
<b>Explanation</b>	All parameters are required.
<b>Action</b>	Specify values for all parameters.
<b>CCECAME0005</b>	<b>Update failed. Trying to update {0} asset repository when the cached repository is of type {1}.</b>
<b>Explanation</b>	The specified asset repository type is incorrect.
<b>Action</b>	Specify the correct repository type.
<b>CCECCBE0000</b>	<b>File with path {} can not be deleted.</b>
<b>Explanation</b>	The file can not be deleted.
<b>Action</b>	Make sure the file is not used by any process.
<b>CCECCUI0143</b>	<b>No ports configured for the specified runtime.</b>
<b>Explanation</b>	There are no ports configured for the specified runtime.
<b>Action</b>	Configure a port.
<b>CCECCUI0288</b>	<b>No rows were selected. You are about to download all Log Sources.</b>
<b>Explanation</b>	No rows were selected in the Log Sources table before clicking the Download Selected Files menu option.
<b>Action</b>	No action required.
<b>CCECCUI0802</b>	<b>Chart shows summarized used {0}</b>
<b>Explanation</b>	Chart shows summarized used {0}
<b>CCECCUI0803</b>	<b>Total {0} above licensed capacity:</b>
<b>Explanation</b>	Total {0} above licensed capacity:
<b>CCECFRE0000</b>	<b>The content of the response is not acceptable according to the accept headers</b>
<b>Explanation</b>	The response content cannot be converted into the requested media type that is specified in the HTTP Accept header. For example, the response is in text format and cannot be converted into XML or JSON format.
<b>Action</b>	Try to load the configuration again and specify a supported media type.

<b>CCECFRE0001</b>	<b>The ConfigurationTypeId "{1}" does not exist for RuntimeComponentId "{0}".</b>
<b>Explanation</b>	One or more configuration types specified do not match or are not valid for the specified properties.
<b>Action</b>	Provide valid configuration types for the specified properties. You can determine the valid configuration types using the following command:cc list configuration types
<b>CCECFRE0002</b>	<b>The ConfigurationTypeId "{0}" does not exist for RuntimeComponentId "{1}".</b>
<b>Explanation</b>	There is no registered ConfigurationType with the provided ID for the specified runtime component.
<b>Action</b>	Provide a valid ConfigurationTypeId for the specified runtime component. You can determine the IDs for configuration types using the following command:cc list configuration types
<b>CCECFRE0005</b>	<b>LandscapeConfigurationUiBindingService is not available.</b>
<b>Explanation</b>	The LandscapeConfigurationUiBindingService is not registered.
<b>Action</b>	Ensure that the bundle that contains this service is active.
<b>CCECFRE0006</b>	<b>Configuration instance {0} cannot store license keys.</b>
<b>Explanation</b>	The specified configuration instance {0} cannot store license keys.
<b>Action</b>	Specify a configuration instances that is able to store license keys. Such configuration instances always start with the COMMON-LICENSE prefix.
<b>CCECFRE0007</b>	<b>Getting the content of an input stream as string fails</b>
<b>Explanation</b>	Command Central cannot convert the input stream as string.
<b>Action</b>	Check the logs for more information.
<b>CCECLTE0001</b>	<b>The expected values expression could not be parsed correctly.</b>
<b>Explanation</b>	The expected values expression could not be parsed correctly.
<b>Action</b>	Check the expected values expression for errors.
<b>CCECLTE0012</b>	<b>A resource was not specified.</b>
<b>Explanation</b>	The REST call failed because a remote resource location was not specified in the REST service.
<b>Action</b>	Specify a valid resource in the REST service, for example, spm/inventory/components.

<b>CCECLTE0013</b>	<b>A URL was not specified.</b>
<b>Explanation</b>	The REST call to the remote host failed because the URL was not specified.
<b>Action</b>	Specify a valid URL, for example, <code>http://localhost:8092</code> .
<b>CCECNFE0000</b>	<b>LandscapeDefinition service is not available.</b>
<b>Explanation</b>	The LandscapeDefinition service is not registered.
<b>Action</b>	Ensure that the bundle that contains this service is active and the service is properly configured.
<b>CCECNFE0001</b>	<b>Landscape inventory service not available.</b>
<b>Explanation</b>	The landscape inventory service was not configured.
<b>Action</b>	Ensure that the bundle that contains this service is active.
<b>CCECNFE0002</b>	<b>Configuration service factory not available.</b>
<b>Explanation</b>	A configuration service factory is not configured.
<b>Action</b>	Ensure that the bundle that contains the configuration service factory is active and that the component definition is correct.
<b>CCECNFE0003</b>	<b>The configuration service encountered a remote request failure.</b>
<b>Explanation</b>	The remote request for a configuration item failed.
<b>Action</b>	Ensure that the node in the request is active.
<b>CCECNFE0004</b>	<b>The remote request encountered a concurrency error.</b>
<b>Explanation</b>	The system could not execute parallel remote requests.
<b>Action</b>	Contact Software AG Global Support.
<b>CCECNFE0005</b>	<b>Can not update credentials.</b>
<b>Explanation</b>	The user credentials on Command Central can not be updated.
<b>Action</b>	Ensure that the <code>runtimeComponentId</code> and <code>nodeAlias</code> parameters are valid.
<b>CCECNFE0006</b>	<b>Can not process JSON configuration.</b>
<b>Explanation</b>	The JSON format of an old configuration is incorrect.
<b>Action</b>	Verify that the configuration uses proper JSON format.

---

<b>CCECNFE0008</b>	<b>Can not update configurations cache because of failure during retrieval of remote configurations.</b>
<b>Explanation</b>	The remote request for configuration items failed and the configurations cache can not be updated.
<b>Action</b>	Ensure that the node in the request is active.
<b>CCECNFE0009</b>	<b>The configuration service encountered a remote request failure while retrieving configuration data for runtime component {0}, configuration instance {1}.</b>
<b>Explanation</b>	The remote request for the specified configuration item failed.
<b>Action</b>	Ensure that the node in the request is active and check the Platform Manager logs.
<b>CCECOME0000</b>	<b>Cannot perform an operation on nodes that are not accessible. The offline nodes are {0}.</b>
<b>Explanation</b>	The specified nodes cannot be accessed because they are offline.
<b>Action</b>	Check the status of the specified nodes. Command Central can only access nodes that are online.
<b>CCECOME0002</b>	<b>{0} on {1} ({2}) became unresponsive. Component restart may help to resolve this quickly.</b>
<b>Explanation</b>	Specified components became unresponsive.
<b>Action</b>	Component restart may help to resolve this quickly.
<b>CCECOME0003</b>	<b>{0} on {1} ({2}) crashed. You will need to start it again and investigate the cause of the failure.</b>
<b>Explanation</b>	Specified components crashed.
<b>Action</b>	You will need to start it again and investigate the cause of the failure.
<b>CCECOME0007</b>	<b>{0} of {1} on {2} ({3}) spiked into critical zone. The component may become overloaded!</b>
<b>Explanation</b>	The specified component becomes overloaded.
<b>Action</b>	Try to release the load on the specified component.

<b>CCECOME0015</b>	<b>Node {0} was not found.</b>
<b>Explanation</b>	The specified node was not found.
<b>Action</b>	Check if the correct alias is used. If the node is not present in the landscape it can be added using the landscape service. If the node has been added but is still not accessible, contact Software AG Global Support.
<b>CCECOME0016</b>	<b>Node {0} could not be created.</b>
<b>Explanation</b>	A node with alias {0} could not be created because another node with alias {1} already exists.
<b>Action</b>	Provide a different alias for the new node.
<b>CCECOME0017</b>	<b>Environment {0} could not be created.</b>
<b>Explanation</b>	An environment with alias {0} could not be created because another environment with alias {1} already exists.
<b>Action</b>	Provide a different alias for the new environment.
<b>CCECOME0018</b>	<b>Generation of checksum for license metering report failed</b>
<b>Explanation</b>	The generation of the checksum for the license metering report failed.
<b>Action</b>	Contact Software AG Global Support.
<b>CCECOME0019</b>	<b>Generation of report id for license metering report failed</b>
<b>Explanation</b>	The generation of the report ID for the license metering report failed.
<b>Action</b>	Contact Software AG Global Support.
<b>CCECOME0020</b>	<b>Cannot convert XML report to string</b>
<b>Explanation</b>	The conversion of the XML report failed.
<b>Action</b>	Contact Software AG Global Support.
<b>CCECOME0025</b>	<b>Generation of XML string for object instance of class {0} failed</b>
<b>Explanation</b>	The generation of the XML string for object instance of class {0} failed.
<b>Action</b>	Provide a valid object instance.

---

<b>CCECOME0029</b>	<b>License key {0} not found.</b>
<b>Explanation</b>	The license key with the specified alias {0} is not found.
<b>Action</b>	Upload and assign a valid license key for this alias or use a different existing license key alias.
<b>CCECOME0030</b>	<b>Checksum verification of report {0} failed!</b>
<b>Explanation</b>	The checksum verification of report {0} failed.
<b>Action</b>	Contact Software AG Global Support.
<b>CCECOME0033</b>	<b>Unable to parse this date string({0}).</b>
<b>Explanation</b>	Unable to parse this date string({0}).
<b>Action</b>	Contact Software AG support.
<b>CCECOME0034</b>	<b>Unexpected exception occurred: {0}.</b>
<b>Explanation</b>	An unexpected exception occurred: {0}.
<b>Action</b>	Contact Software AG support.
<b>CCECOME0038</b>	<b>The remote Platform Manager job with id {0} was not found.</b>
<b>Explanation</b>	A job with the specified id was not found on Platform Manager.
<b>Action</b>	Specify an existing job id.
<b>CCECORE0001</b>	<b>Exceeded the maximum nodes allowed as per the configured license.</b>
<b>Explanation</b>	You have exceeded the nodes allowed to you as per the license configured for Command Central.
<b>Action</b>	Contact Software AG support to upgrade the license.
<b>CCECORE0002</b>	<b>Invalid License found. The system is going to shutdown in 30 minutes.</b>
<b>Explanation</b>	The configured license is invalid. You need to configure a valid license immediately else the system will shutdown in 30 mintures.
<b>Action</b>	Configure a valid license immediately. If you do not have one, contact your system dministrator or Software AG support.

<b>CCECORE0003</b>	<b>Invalid License found. The system is shutting down.</b>
<b>Explanation</b>	The system is shutting down as the configured license is invalid.
<b>Action</b>	Contact your Administrator or Software AG support.
<b>CCECORE0004</b>	<b>The license has expired.</b>
<b>Explanation</b>	The configured license has expired.
<b>Action</b>	Contact your system administrator or Software AG support.
<b>CCECORE0005</b>	<b>The license is not valid for the current operating system.</b>
<b>Explanation</b>	The configured license is not valid for the current operating system.
<b>Action</b>	Contact your Administrator or Software AG support.
<b>CCECORE0006</b>	<b>The number of nodes has exceeded as per the configured license.</b>
<b>Explanation</b>	As per the configured license, you are not allowed to add more nodes as you have exhausted the licensed number of nodes.
<b>Action</b>	Contact your system administrator or Software AG support to get the license upgraded to add more nodes.
<b>CCECORE0007</b>	<b>Failed to get the node count from the license.</b>
<b>Explanation</b>	This issue may occur when your license file is corrupt.
<b>Action</b>	Contact your system administrator or Software AG support.
<b>CCECORE0008</b>	<b>The configured license is not valid for this product.</b>
<b>Explanation</b>	Either the license file is not for Command Central or it may have be a corrupt file.
<b>Action</b>	Contact your system administrator or Software AG support.
<b>CCECORE0009</b>	<b>Failed to read the product code from the license.</b>
<b>Explanation</b>	This issue may occur when your license file is corrupt.
<b>Action</b>	Contact your system administrator or Software AG support.
<b>CCECORE0010</b>	<b>The configured license is not valid for this product version.</b>
<b>Explanation</b>	This issue may occur when your license file is corrupt.
<b>Action</b>	Contact your system administrator or Software AG support.

---

<b>CCECORE0011</b>	<b>Failed to read the product version from the license.</b>
<b>Explanation</b>	Either the license file is not for current version of Command Central or the license file may be corrupt.
<b>Action</b>	Contact your system administrator or Software AG support.
<b>CCECORE0012</b>	<b>Node with alias {0} is not found.</b>
<b>Explanation</b>	The specified node is not found in Command Central.
<b>Action</b>	Ensure that the node alias is spelled correctly. You can view a list of installations and their aliases using either the Command Central Web user interface, the cc list landscape nodes command, or the REST API.
<b>CCECORE0013</b>	<b>The specified search query is not valid. The supported search attributes are: {0}</b>
<b>Explanation</b>	One or more attributes are not supported for this type of search.
<b>Action</b>	Ensure that the search attributes are supported for the type of search you want to perform. Make sure that the attributes are spelled correctly. The supported search attributes are listed in the error message. Note that search attributes are case-sensitive.
<b>CCECORE0014</b>	<b>Task "{0}" for node "{1}" failed.</b>
<b>Explanation</b>	The specified task failed to execute for the specified node.
<b>Action</b>	Read through the details provided in the error message and the logs, then take corrective steps.
<b>CCECORE0015</b>	<b>Tasks execution has failed.</b>
<b>Explanation</b>	Some or all of the tasks failed to execute.
<b>Action</b>	Read through the details provided in the error message and the logs, then take corrective steps.
<b>CCECORE0016</b>	<b>The specified attribute name and the attribute name in the request are not the same.</b>
<b>Explanation</b>	The attribute name in the body and the attribute name in the path segment should be the same.
<b>Action</b>	Fix the request and try again.

<b>CCECORE0017</b>	<b>Specify attributes to created or updated.</b>
<b>Explanation</b>	The request does not contain search attributes to be created or updated.
<b>Action</b>	Fix the request and submit it again.
<b>CCECORE0018</b>	<b>{0} did not get {1} for {2} seconds!</b>
<b>Explanation</b>	The specified node did not reach the expected status in the given amount of time.
<b>Action</b>	Retry the operation or contact SoftwareAG Global Support.
<b>CCECORE0019</b>	<b>Key {0} is invalid.</b>
<b>Explanation</b>	The specified key {0} is invalid.
<b>Action</b>	Specify a valid key, followed by a valid contract item identifier (for example, item=<contractItemIdentifier>).
<b>CCECORE0020</b>	<b>Contract item identifier {0} is invalid.</b>
<b>Explanation</b>	The specified contract item identifier {0} is invalid.
<b>Action</b>	Specify a valid contract item identifier (for example, item=<contractItemIdentifier>). You can find the valid contract item identifiers using the following command: cc list license-tools manifests contracts basepeak <nodeAlias> <productId>
<b>CCECORE0021</b>	<b>One contract item identifier expected.</b>
<b>Explanation</b>	Command Central expects one contract item identifier.
<b>Action</b>	Specify one valid contract item identifier.
<b>CCECORE0022</b>	<b>Could not retrieve Version of node {0}.</b>
<b>Explanation</b>	The error usually occurs because of issues connecting to node {0}.
<b>Action</b>	Check the logs for details about the connectivity issues.
<b>CCECORE0023</b>	<b>Cannot add contract item identifier assignment for runtime components with base and peak license key.</b>
<b>Explanation</b>	Command Central cannot add the manual contract item identifier assignment if the runtime component has a base and peak license key.
<b>Action</b>	Specify contract item identifiers only for runtime components without base and peak license key.

---

<b>CCECORE0025</b>	<b>{0} did not get {1} for {2} seconds!</b>
<b>Explanation</b>	The specified node did not reach the expected status in the given amount of time.
<b>Action</b>	Retry the operation or contact SoftwareAG Global Support.
<b>CCECORE0026</b>	<b>{0} did not get {1} for {2} seconds!</b>
<b>Explanation</b>	The specified node did not reach the expected status in the given amount of time.
<b>Action</b>	Retry the operation or contact SoftwareAG Global Support.
<b>CCECORE0027</b>	<b>A node with the specified alias does not exist.</b>
<b>Explanation</b>	An installation (node) with the specified alias name does not exist.
<b>Action</b>	Specify a valid alias name for an existing installation (node).
<b>CCECORE0028</b>	<b>A runtime component with the specified id does not exist.</b>
<b>Explanation</b>	A runtime component with the specified ID does not exist on the node(s).
<b>Action</b>	Specify an ID of an existing runtime component.
<b>CCECORE0029</b>	<b>Cache update operation failed.</b>
<b>Explanation</b>	One of the automatic cache update operations failed to complete.
<b>Action</b>	Check the logs for details.
<b>CCECORE0030</b>	<b>Unknown cahce type: {0}. EventListener was not added because the required cache could not be created.</b>
<b>Explanation</b>	Ehcache is not configured properly.
<b>Action</b>	Contact Software AG global support.
<b>CCECORE0031</b>	<b>Unknown cahce type: {0}. EventListener was not removed because the required cache could not be created.</b>
<b>Explanation</b>	Ehcache is not configured properly.
<b>Action</b>	Contact Software AG global support.
<b>CCECORE0032</b>	<b>Invalid settings format: {0}</b>
<b>Explanation</b>	The format of the settings is as follows: key:value[;key:value]...
<b>Action</b>	Make sure that the settings comply with the specified format.

<b>CCECORE0033</b>	<b>Invalid value for period: {0}</b>
<b>Explanation</b>	The value for period must match the following pattern \d+h m. Examples: 9m, 3h, 45m, 12h
<b>Action</b>	Make sure the period value complies with the specified format.
<b>CCECPTE0000</b>	<b>Invalid composite template alias: {0}</b>
<b>Explanation</b>	The composite template alias is not present or contains special characters.
<b>Action</b>	Specify a composite template alias. The template alias can include the following characters: letters, digits, hyphen and dot.
<b>CCECPTE0001</b>	<b>A composite template with alias {0} already exists.</b>
<b>Explanation</b>	A composite template with the specified alias already exists.
<b>Action</b>	Change the alias of the composite template that is being imported or delete the existing composite template that has the same alias.
<b>CCECPTE0002</b>	<b>Missing property {0}.</b>
<b>Explanation</b>	A property is missing from the composite template definition.
<b>Action</b>	Add the missing property with a proper value.
<b>CCECPTE0003</b>	<b>Invalid value {0} for property {1}.</b>
<b>Explanation</b>	A property has an invalid value.
<b>Action</b>	Provide a proper value as described in the Command Central documentation.
<b>CCECPTE0004</b>	<b>A composite template with alias {0} does not exist.</b>
<b>Explanation</b>	A composite template with the specified alias does not exist.
<b>Action</b>	Import a composite template with the specified alias or use the alias of an existing composite template.
<b>CCECPTE0005</b>	<b>The requested repository version {0} was not found.</b>
<b>Explanation</b>	The requested repository version was not found.
<b>Action</b>	Provide an existing repository version or specify an image file location if the repository is of type image.

---

<b>CCECPTE0006</b>	<b>Invalid repository definition.</b>
<b>Explanation</b>	An invalid combination of properties was specified.
<b>Action</b>	See the Command Central documentation on how to define a repository.
<b>CCECPTE0007</b>	<b>The repository definition cannot have both version and location.</b>
<b>Explanation</b>	In the repository definition, the specified location defines that this is an image repository. However, a version cannot be specified for an image repository.
<b>Action</b>	Fix the repository definition. If it is an image repository, specify only a location. Otherwise, remove the location and specify proper credentials.
<b>CCECPTE0008</b>	<b>Cannot have both credentials and location in repository definition.</b>
<b>Explanation</b>	In the repository definition, location defines that this is an image repository. However, you cannot specify credentials for an image repository.
<b>Action</b>	Fix the repository definition. If the repository is an image repository, specify a location. If the repository is a master repository, remove the location and specify proper credentials.
<b>CCECPTE0015</b>	<b>The runtime status of runtime component {0} on node {1} is not online.</b>
<b>Explanation</b>	The runtime component has a status different than online.
<b>Action</b>	Check the logs on the node for issues which may cause the behavior.
<b>CCECPTE0016</b>	<b>The {0} lifecycle job of a runtime component on node {1} did not complete successfully.</b>
<b>Explanation</b>	The lifecycle job of a runtime component on a node did not complete successfully.
<b>Action</b>	Check the jobs on the node.
<b>CCECPTE0017</b>	<b>Define layers when there is a provisioning section.</b>
<b>Explanation</b>	Provisioning requires layers to be defined.
<b>Action</b>	Define a layers section.
<b>CCECPTE0018</b>	<b>Provisioning requires layer {0} however a layer is not defined.</b>
<b>Explanation</b>	All layers defined in the provisioning section should be defined in the layers section.
<b>Action</b>	Fix the layers section by adding the missing layers or change the provisioning section to not include layers.

<b>CCECPTE0019</b>	<b>Invalid layer alias: {0}</b>
<b>Explanation</b>	The layer alias is not present or contains special characters.
<b>Action</b>	Provide a layer alias. The layer alias can contain the following characters: letters, digits, hyphen and dot.
<b>CCECPTE0020</b>	<b>Invalid template alias: {0}</b>
<b>Explanation</b>	The template alias is not present or contains special characters.
<b>Action</b>	Provide a layer alias. The layer alias can contain the following characters: letters, digits, hyphen and dot.
<b>CCECPTE0021</b>	<b>Repository with name {0} is already defined.</b>
<b>Explanation</b>	A repository with the same name is already defined in the YAML document.
<b>Action</b>	Change the name of the repository, so that the name is unique in the scope of the document.
<b>CCECPTE0022</b>	<b>The maximum number of retries for applying template {0} on node {1} due to possible Platform Manager restarts is reached.</b>
<b>Explanation</b>	The maximum number of retries for applying a template on a node due to possible Platform Manager restarts is reached.
<b>Action</b>	Check the logs for details about previous attempts to apply the template to determine what the issues are.
<b>CCECPTE0023</b>	<b>{0} did not get {1} for {2} seconds!</b>
<b>Explanation</b>	The specified node did not reach the expected status in the given amount of time.
<b>Action</b>	Retry the operation or contact SoftwareAG Global Support.
<b>CCECPTE0024</b>	<b>Can not find any repository matching the provided host and name.</b>
<b>Explanation</b>	Command Central does not find a repository matching the specified host and name.
<b>Action</b>	Specify valid host and name.
<b>CCECPTE0025</b>	<b>Snapshot template {0} not found!</b>
<b>Explanation</b>	The snapshot template referred from the composite template cannot be found.
<b>Action</b>	Import a snapshot template with the specified alias and re-apply the composite template.

---

<b>CCECPTE0027</b>	<b>Server action {0} failed with a non-zero exit code: {1}</b>
<b>Explanation</b>	An action executing on the CommandCentral server failed.
<b>Action</b>	Make sure the action itself is correct and try again.
<b>CCECPTE0032</b>	<b>The jar command executable cannot be found on the source node installation.</b>
<b>Explanation</b>	The jar command executable cannot be found on the source node installation.
<b>Action</b>	Check the composite template logs.
<b>CCECPTE0038</b>	<b>Remote action {0} failed with a non-zero exit code: {1}</b>
<b>Explanation</b>	An action executing remotely failed.
<b>Action</b>	Make sure the action itself is correct and try again.
<b>CCECPTE0039</b>	<b>Neither script nor file exist for action: {0}!</b>
<b>Explanation</b>	An action must have either a script, or a file associated with it.
<b>Action</b>	Add a script or file and try again.
<b>CCECPTE0040</b>	<b>The runtime status of runtime component {0} on node {1} is not paused.</b>
<b>Explanation</b>	The runtime component has a status other than paused.
<b>Action</b>	Check the logs on the node for issues which may cause the behavior.
<b>CCECPTE0041</b>	<b>Environment {0} is not defined in 'provision'!</b>
<b>Explanation</b>	The environments in the 'provision' and 'migration' sections do not match.
<b>Action</b>	Make sure the same set of environments is present in both the 'provision' and 'migration' sections and try again.
<b>CCECPTE0042</b>	<b>Layer {0} referenced in 'migration' but not in 'provision'!</b>
<b>Explanation</b>	The layers referenced in the 'provision' and 'migration' sections do not match.
<b>Action</b>	Make sure the same set of layers are referenced from both the 'provision' and 'migration' sections and try again.
<b>CCECPTE0043</b>	<b>The number of nodes for layer {0} in 'migration' and 'provision' don't match!</b>
<b>Explanation</b>	The number of nodes for a given layer in the 'migration' section must match the number of nodes for the same layer in the 'provision' section.
<b>Action</b>	Make sure the number of nodes per layer is the same across the 'migration' and 'provision' sections and try again.

<b>CCECPTE0044</b>	<b>Executing more than one migration type in a single composite template is not supported: {0}, {1}. Check the source and target nodes hostnames and installation directories.</b>
<b>Explanation</b>	The composite template contains nodes that should be migrated using different migration type scenarios. This is not supported.
<b>Action</b>	Split or parameterize the template so that the migration is done using a single migration type.
<b>CCECPTE0045</b>	<b>Error during archiving the migration source node installation directory.</b>
<b>Explanation</b>	An error occurred during archiving the migration source node installation directory.
<b>Action</b>	Check the logs for the result of the executed remote archive command.
<b>CCECPTE0046</b>	<b>Runtime component with id {0} cannot be found.</b>
<b>Explanation</b>	Runtime component with the provided ID cannot be found.
<b>Action</b>	Check the Command Central logs for inventory service errors.
<b>CCECPTE0047</b>	<b>Cannot find node with alias {0} in the list of the bootstrapped migration source nodes: {1}.</b>
<b>Explanation</b>	Command Central cannot find the source node with the specified nodeAlias in the list of bootstrapped migration source nodes.
<b>Action</b>	Check the logs for previous errors.
<b>CCECPTE0048</b>	<b>Aborted because of a migration failure, see the logs for more details.</b>
<b>Explanation</b>	The entire composite template operation failed because of a migration error.
<b>Action</b>	Check the logs to identify the issue and try again.
<b>CCECPTE0049</b>	<b>Cannot skip run-time components stop operation when doing migration on the same host.</b>
<b>Explanation</b>	Skipping the run-time components stop operation when doing migration on the same host is not supported.
<b>Action</b>	To stop the run-time components, enable the migration/options/shutdown option in the composite template definition.

---

<b>CCECPTE0050</b>	<b>A {0} file could not be found in the imported composite template archive {1}.</b>
<b>Explanation</b>	The expected template yaml file could not be found in the imported composite template archive.
<b>Action</b>	Provide a valid template archive containing the expected template yaml file.
<b>CCECPTE0051</b>	<b>Source backup archive {0} was not found on the Command Central host.</b>
<b>Explanation</b>	The backup archive, created from the migration source node, was not found on the Command Central host.
<b>Action</b>	Check the logs for previous errors related to the backup archive creation or archive transfer from the source host to the Command Central host.
<b>CCECPTE0052</b>	<b>Source backup archive {0} was not found on host {1}.</b>
<b>Explanation</b>	The backup archive, created from the migration source node, was not found on the target host.
<b>Action</b>	Check the logs for previous errors related to backup archive transfer from the Command Central host to the target host. If the backup was transferred manually then check if its location is the expected by Command Central one.
<b>CCECPTE0053</b>	<b>Cygpah command returned empty result.</b>
<b>Explanation</b>	The Cygpah command returned empty result.
<b>Action</b>	Check the Command Central template logs.
<b>CCECPTE0054</b>	<b>Cannot skip run-time components stop operation for node {0} running on Windows when doing migration of type different hosts.</b>
<b>Explanation</b>	Skipping the run-time components stop operation when doing migration on different hosts running on Windows is not supported.
<b>Action</b>	To stop the run-time components, enable the migration/options/shutdown option in the composite template definition.
<b>CCECPTE0055</b>	<b>Unexpected YAML type {0} in field {1}! The correct type is integer.</b>
<b>Explanation</b>	Non-integer data was used in a field that requires integer.
<b>Action</b>	Use the correct integer value and try again.

<b>CCECPTE0078</b>	<b>Composite template validation for {0} completed: {1}</b>
<b>Explanation</b>	Validation detected that the composite template cannot be applied successfully.
<b>Action</b>	Study the validation report, fix the errors and try again.
<b>CCECPTI0026</b>	<b>The following runtime components are started but not ready to accept client requests: {0}</b>
<b>Explanation</b>	Some runtime components have started, but are not ready to accept client requests.
<b>Action</b>	The components might require additional configuration.
<b>CCECPTW0030</b>	<b>Source migration step {0} finished with error: {1}</b>
<b>Explanation</b>	The source node migration step finished with an error.
<b>Action</b>	Check the logs and identify the error root cause.
<b>CCECPTW0031</b>	<b>Skipping source node archive step. Source node installation directory is null.</b>
<b>Explanation</b>	Command Central will skip the source node archive step, because the source node installation directory is null.
<b>Action</b>	Start Platform Manager on the source node, retrieve the node information on Command Central when Platform Manager gets online.
<b>CCEIMPE0004</b>	<b>You cannot update the license location for the configuration type COMMON-LICLOC in Command Central.</b>
<b>Explanation</b>	You cannot update the license location for the configuration type COMMON-LICLOC in Command Central.
<b>Action</b>	Use the default license location.
<b>CCEIMPE0005</b>	<b>You cannot create a license location for the configuration type COMMON-LICLOC in Command Central.</b>
<b>Explanation</b>	You cannot create a license location for the configuration type COMMON-LICLOC in Command Central.
<b>Action</b>	Use the default license location.
<b>CCEIMPE0006</b>	<b>You cannot delete the license location for the configuration type COMMON-LICLOC in Command Central.</b>
<b>Explanation</b>	You cannot delete the license location for the configuration type COMMON-LICLOC in Command Central.
<b>Action</b>	Use the default license location.

---

<b>CCEIMPE0007</b>	<b>The product version is invalid.</b>
<b>Explanation</b>	In Command Central, when the license is created or updated for Command Central Engine, if the product version in license validation does not match the version of the product installed, this error is thrown.
<b>Action</b>	Provide a new license file with the product version matching the installed product.
<b>CCEIMPE0009</b>	<b>The product code is invalid.</b>
<b>Explanation</b>	In Command Central, when the license is created or updated for the Command Central Engine, if the product code does not match the Command Central Engine product code, this error is thrown.
<b>Action</b>	Provide a new license file with the product code matching with the Command Central Engine product code.
<b>CCEIMPE0021</b>	<b>A layer definition with the same name already exists.</b>
<b>Explanation</b>	A layer definition with the same name already exists.
<b>Action</b>	Specify a unique name for the layer type.
<b>CCEIMPE0022</b>	<b>A micro template with alias {0} does not exist.</b>
<b>Explanation</b>	A micro template with the specified alias does not exist.
<b>Action</b>	Specify the alias of an existing micro template.
<b>CCEIMPE0023</b>	<b>The provided configuration cannot be null.</b>
<b>Explanation</b>	The provided configuration cannot be null.
<b>Action</b>	Provide non-null layer definition configuration.
<b>CCEIMPE0024</b>	<b>Configuration of type CCE-LAYER-TYPES should have a name attribue with a valid id.</b>
<b>Explanation</b>	The name attribute of the specified configuration type should have an ID that contains only URL friendly symbols.
<b>Action</b>	Provide a URL-friendly ID for the name attribute.
<b>CCEIMPE0025</b>	<b>Providing micro template alias is required.</b>
<b>Explanation</b>	Specifying the micro template alias is required.
<b>Action</b>	Specify the alias of an existing micro template.

<b>CCEIMPE0026</b>	<b>Deleting default system layer definition {0} is not allowed.</b>
<b>Explanation</b>	Deleting default system layer definition is not allowed.
<b>Action</b>	Do not delete the default system layer definitions.
<b>CCEINME0000</b>	<b>Fix repository with Id {0} cannot be found.</b>
<b>Explanation</b>	The specified repository ID is not the ID of an existing repository.
<b>Action</b>	Check the input parameters and specify the ID of an existing repository.
<b>CCEINME0001</b>	<b>An error occurred while registering repository {0} on node {1}. Check the server logs for details.</b>
<b>Explanation</b>	The issue might occur because of a problem with the repository contents.
<b>Action</b>	Check the server logs for details.
<b>CCEINRE0001</b>	<b>A node with the specified alias does not exist.</b>
<b>Explanation</b>	An installation (node) with the specified alias name does not exist.
<b>Action</b>	Specify the valid alias name for an existing installation (node).
<b>CCEINRE0002</b>	<b>The specified runtime component is not a process!</b>
<b>Explanation</b>	The specified run-time component is not a PROCESS. Run-time components that are in the PROCESS category are components that function on their own. In contrast, run-time components that are in the ENGINE category cannot function on their own, but rather run within a PROCESS run-time component.
<b>Action</b>	Specify a PROCESS run-time component.
<b>CCEJMRE0000</b>	<b>A job with ID {0} cannot be found.</b>
<b>Explanation</b>	A job with the specified ID may have never existed or it may have completed long before this request.
<b>Action</b>	Use the following URI to list all jobs that are running or recently completed: <code>/cce/jobmanager/jobs</code>
<b>CCEJMRE0001</b>	<b>A node with alias {0} does not exist.</b>
<b>Explanation</b>	There is no node with the given alias in the landscape.
<b>Action</b>	Add the node to the landscape.

---

<b>CCEJMRE0002</b>	<b>A job with ID {0} on node {1} cannot be found.</b>
<b>Explanation</b>	A job with the specified ID may have never existed or it may have completed long before this request.
<b>Action</b>	Use the following URI to list all jobs that are running or recently completed: /cce/jobmanager/landscapejobs/local where "local" is the node alias
<b>CCELCRE0000</b>	<b>The lifecycle operation to execute is unknown.</b>
<b>Explanation</b>	You specified a lifecycle operation that is not valid. Valid lifecycle operations are start, stop, restart, pause, resume, start in debug mode, and start in safe mode. Note, however, that a run-time component might support only a subset of the valid lifecycle operations.
<b>Action</b>	Specify a valid lifecycle operation.
<b>CCELCYE0003</b>	<b>Error occured while executing lifecycle operation on a remote managed node with alias {0}. Remote task status is {1}</b>
<b>Explanation</b>	Error occured while executing lifecycle operation on a remote managed node.
<b>Action</b>	Check the Command Central and target node Platform Manager logs.
<b>CCELCYE0004</b>	<b>Error during lifecycle job execution.</b>
<b>Explanation</b>	An error occurred during the lifecycle job execution.
<b>Action</b>	Check the logs for details about the error.
<b>CCELCYE0005</b>	<b>At least one remote call has timed out.</b>
<b>Explanation</b>	At least one remote lifecycle execution call has timed out.
<b>Action</b>	Check the remote Platform Manager logs for related errors.
<b>CCELIRE0000</b>	<b>Error deleting license report with id: {0}</b>
<b>Explanation</b>	An unexpected error occurred when trying to delete the License Report with the given ID.
<b>Action</b>	Check the report id provided and if valid, check the server log for any exception messages.

<b>CCELIRE0001</b>	<b>Error deleting license reports.</b>
<b>Explanation</b>	At least one of the license reports was not deleted successfully.
<b>Action</b>	Retry the delete operation later or contact Software AG Global Support.
<b>CCELIRE0003</b>	<b>Exception while building license report Document, {0}: caught type({1}), msg({2})</b>
<b>Explanation</b>	A problem was encountered while attempting to build a License Report XML document from its string representation.
<b>Action</b>	Consult Software AG Global Support.
<b>CCELIRE0004</b>	<b>Invalid license manifest file.</b>
<b>Explanation</b>	The contents of the specified file is invalid for license manifest files.
<b>Action</b>	Specify a valid license manifest file.
<b>CCELIRW0002</b>	<b>Error deleting the following reports: {0}</b>
<b>Explanation</b>	The specified reports could not be deleted successfully.
<b>Action</b>	Check the server log for more details and try to delete the reports individually.
<b>CCELITE0000</b>	<b>Error generating license report id!</b>
<b>Explanation</b>	An error occurred when trying to generate a unique report ID for the license report snapshot.
<b>Action</b>	Retry the operation or contact Software AG Global Support.
<b>CCELITE0001</b>	<b>Could not find a report with id {0}</b>
<b>Explanation</b>	No license report with the specified report ID was found in the system.
<b>Action</b>	Check the report ID value and try again.
<b>CCELITE0002</b>	<b>Error creating license snapshots directory {0}</b>
<b>Explanation</b>	An error occurred when trying to create a filesystem directory to store the license snapshots.
<b>Action</b>	Check if there is enough disk space and/or contact Software AG Global Support.

---

<b>CCELITE0003</b>	<b>Unable to get runtime component {0}/{1} caught: {2}</b>
<b>Explanation</b>	During license data collection, an attempt to retrieve information about this runtime component failed. The issue may indicate a communication issue between Command Central and Platform Manager.
<b>Action</b>	This could be a temporary communications issue. If the problem persists, contact Software AG Global Support.
<b>CCELITE0004</b>	<b>Unable to get configuration types for {0}/{1} caught: {2}</b>
<b>Explanation</b>	During license data collection, an attempt to retrieve information about this runtime component failed. The issue may indicate a communication issue between Command Central and Platform Manager.
<b>Action</b>	This could be a temporary communications issue. If the problem persists, contact Software AG Global Support.
<b>CCELITE0005</b>	<b>Unable to get configuration instances for {0}/{1} caught: {2}</b>
<b>Explanation</b>	During license data collection, an attempt to retrieve information about this runtime component failed. The issue may indicate a communication issue between Command Central and Platform Manager.
<b>Action</b>	This could be a temporary communications issue. If the problem persists, contact Software AG Global Support.
<b>CCELITE0006</b>	<b>Unable to get configuration data for {0}/{1}/{2} caught: {3}</b>
<b>Explanation</b>	During license data collection, an attempt to retrieve information about this runtime component failed. The issue may indicate a communication issue between Command Central and Platform Manager.
<b>Action</b>	This could be a temporary communications issue. If the problem persists, contact Software AG Global Support.
<b>CCELITE0007</b>	<b>Found null value for license configuration data for {0}/{1}/{2}</b>
<b>Explanation</b>	During license data collection, an attempt to retrieve license information about this runtime component found an invalid license.
<b>Action</b>	Contact Software AG Global Support.
<b>CCELITE0008</b>	<b>Expected a String value for license configuration data for {0}/{1}/{2}, found type {3}</b>
<b>Explanation</b>	During license data collection, an attempt to retrieve license information about this runtime component found an invalid license.
<b>Action</b>	Contact Software AG Global Support.

<b>CCELITE0010</b>	<b>Checksum verification failed for License Report with id {0} {1}.</b>
<b>Explanation</b>	The license report file may be corrupted or been tampered with, which has resulted in an integrity check failure.
<b>Action</b>	Regenerate the license report and/or contact Software AG Global Support with the affected license report file.
<b>CCELITE0011</b>	<b>Unable to generate and store license snapshot report; caught type: {0}, msg: {1}</b>
<b>Explanation</b>	An issue was encountered either when generating, or saving the generated license report snapshot.
<b>Action</b>	Check the exception and message to identify the exact cause, or contact Software AG Global Support.
<b>CCELITE0012</b>	<b>Unable to generate report, no report generator configured</b>
<b>Explanation</b>	The issue occurred because of incorrect component configuration.
<b>Action</b>	Check the license report configuration or contact Software AG Global Support.
<b>CCELITE0013</b>	<b>Error getting license report!</b>
<b>Explanation</b>	An error occurred when trying to retrieve the requested license report.
<b>Action</b>	Check the cause and retry the operation.
<b>CCELITE0014</b>	<b>Unable to parse license XML for {0}/{1} from string that follows; except msg: {2}. XML: {3}</b>
<b>Explanation</b>	The license content retrieved from the Platform Manager could not be parsed.
<b>Action</b>	Check the exception message for the exact cause and/or contact Software AG Global Support. The error may occur if a license file is found that is not in a standard Software AG format.
<b>CCELITE0015</b>	<b>Error generating pdf report for this reportId "{0}". Cause: {1}</b>
<b>Explanation</b>	The attempt to transform the XML data failed to produce a PDF data stream.
<b>Action</b>	Generate another report and verify whether the XML response is well-formed.
<b>CCELITE0016</b>	<b>Error generating pdf license report. No XML data stream available for "{0}"</b>
<b>Explanation</b>	The license reports module cannot produce a pdf report unless its canonical data is provided.
<b>Action</b>	Verify that the pdf generation task was executed properly using an existing report ID.

---

<b>CCELITE0017</b>	<b>Error generating pdf license report. Unable to locate XSLT style sheet for pdf generation. "{0}"</b>
<b>Explanation</b>	The license tools bundle could not locate the XSLT style used to produce a pdf report.
<b>Action</b>	Contact Software AG Global Support.
<b>CCELITE0018</b>	<b>Error applying license pdf report stylesheet "{0}" to XML data "{1}". Cause: {2}</b>
<b>Explanation</b>	Unexpected errors were encountered while generating the license pdf report.
<b>Action</b>	Contact Software AG Global Support.
<b>CCELITE0019</b>	<b>Unable to serialize a license report data object for "{0}". Cause: {1}</b>
<b>Explanation</b>	The license report data object could not be serialized as input for pdf report generation.
<b>Action</b>	Contact Software AG Global Support.
<b>CCELITE0020</b>	<b>Error verifying license report checksum.</b>
<b>Explanation</b>	An error occurred when trying to verify the license report checksum when retrieving the report.
<b>Action</b>	Retry request later or contact Software AG Global Support.
<b>CCELITE0022</b>	<b>Unable to open extended rights table ({0})</b>
<b>Explanation</b>	The indicated value is not available.
<b>Action</b>	Contact Software AG Global Support.
<b>CCELITE0023</b>	<b>Unable to load extended rights properties from {0}; caught: type({1}). message({2})</b>
<b>Explanation</b>	A problem was encountered while loading the indicated file into memory.
<b>Action</b>	Contact Software AG Global Support.
<b>CCELITE0024</b>	<b>Unable to close input stream from {0}; caught: type({1}). message({2})</b>
<b>Explanation</b>	A problem was encountered while cleaning up after loading the indicated file into memory.
<b>Action</b>	Contact Software AG Global Support.

<b>CCELITE0026</b>	<b>License manifest is already stored.</b>
<b>Explanation</b>	The license manifest is already been stored with alias {0}.
<b>Action</b>	Specify a different license manifest.
<b>CCELITE0027</b>	<b>Unable to store license manifest "{0}"; caught type: {1}, msg: {2}</b>
<b>Explanation</b>	An issue was encountered when storing a license manifest.
<b>Action</b>	Check the exception and message to identify the exact cause, or contact Software AG Global Support.
<b>CCELITE0028</b>	<b>Error creating storage location {0} for license manifests.</b>
<b>Explanation</b>	An error occurred when trying to create a filesystem directory to store license manifests.
<b>Action</b>	Check access rights and disk space or contact Software AG Global Support.
<b>CCELITE0029</b>	<b>Error retrieving license manifests.</b>
<b>Explanation</b>	An error occurred when trying to retrieve the list of stored license manifests.
<b>Action</b>	Check the cause and retry the operation.
<b>CCELITE0030</b>	<b>Could not find a license manifest with alias {0}</b>
<b>Explanation</b>	No license manifest with the specified alias was found in the system.
<b>Action</b>	Check the license manifest alias value and try again.
<b>CCELITE0031</b>	<b>Invalid license manifest.</b>
<b>Explanation</b>	The specified file is not a valid license manifest.
<b>Action</b>	Specify a valid license manifest.
<b>CCELITE0032</b>	<b>Checksum verification failed for LicenseMeteringConfiguration.xml file.</b>
<b>Explanation</b>	The LicenseMeteringConfiguration.xml file which is delivered with the CCE installation is either corrupted, or modified.
<b>Action</b>	Contact Software AG Global Support to get a valid LicenseMeteringConfiguration.xml file.

---

<b>CCELITE0034</b>	<b>Alias "{0}" already exists.</b>
<b>Explanation</b>	A license manifest with the specified alias already exists.
<b>Action</b>	Specify a new alias for the license manifest.
<b>CCELITE0035</b>	<b>License manifest alias missing.</b>
<b>Explanation</b>	No license manifest alias has been specified.
<b>Action</b>	Specify a valid license manifest alias.
<b>CCELITE0036</b>	<b>Deleting license manifest with alias "{0}" failed.</b>
<b>Explanation</b>	An error occurred while trying to delete the license manifest with the specified alias.
<b>Action</b>	Check the exception and message to identify the exact cause, or contact Software AG Global Support.
<b>CCELITE0037</b>	<b>Deleting license manifests failed.</b>
<b>Explanation</b>	An error occurred while trying to delete the license manifests.
<b>Action</b>	Check the exception and message to identify the exact cause, or contact Software AG Global Support.
<b>CCELITE0042</b>	<b>Invalid processor core class {0}.</b>
<b>Explanation</b>	The specified processor core class is not valid.
<b>Action</b>	Specify a valid processor core class.
<b>CCELITE0046</b>	<b>Checksum verification failed for the given License Manifest.</b>
<b>Explanation</b>	The license manifest file is corrupted or been tampered with, which has resulted in an integrity check failure.
<b>Action</b>	Use original license manifest file from Software AG and/or contact Software AG Global Support with the affected license manifest file.
<b>CCELITE0047</b>	<b>Cannot open license metering configuration file.</b>
<b>Explanation</b>	The license metering configuration file could not be read.
<b>Action</b>	Contact Software AG support.

<b>CCELITE0048</b>	<b>Updating {0} cache for node {1} failed.</b>
<b>Explanation</b>	Updating the cache failed. The license metering report may contain invalid data.
<b>Action</b>	Contact Software AG support.
<b>CCELITE0049</b>	<b>Processor core class is not available. Product cannot be checked.</b>
<b>Explanation</b>	The Platform Manager where the product is installed did not provide the processor core class the node is running on.
<b>Action</b>	Contact Software AG Global Support.
<b>CCELITE0050</b>	<b>Cannot find runtime status: {0}</b>
<b>Explanation</b>	The run-time status of the current landscape XML file was not found.
<b>Action</b>	Provide a valid landscape XML file.
<b>CCELITE0051</b>	<b>Cannot store license metering configuration data to file.</b>
<b>Explanation</b>	An error occurred while writing the license metering configuration data to a new file.
<b>Action</b>	Contact Software AG Global Support.
<b>CCELITE0053</b>	<b>Platform Manager with version {0} is not sufficient for the license metering. Version 9.8 or higher is required.</b>
<b>Explanation</b>	The version of the Platform Manager is {0}. Platform Manager version of 9.8 or higher is required for the license metering.
<b>Action</b>	Update the Platform Manager with version 9.8 or higher.
<b>CCELITE0054</b>	<b>Consolidation of License Manifests failed.</b>
<b>Explanation</b>	An error occurred during the consolidation of the license manifests.
<b>Action</b>	Contact Software AG support.
<b>CCELITE0055</b>	<b>Collecting server details information failed.</b>
<b>Explanation</b>	An error occurred during the collection of server details information.
<b>Action</b>	Contact Software AG support.

---

<b>CCELITE0056</b>	<b>Generating license report compliance result failed.</b>
<b>Explanation</b>	An error occurred during the generation of the license report compliance result.
<b>Action</b>	Contact Software AG Global Support.
<b>CCELITE0057</b>	<b>License manifest for referenced location id {0} not found.</b>
<b>Explanation</b>	The license manifest for the location id {0} has been removed.
<b>Action</b>	Add the license manifest for the location id {0} to Command Central or assign a different location id to the installation details in the landscape overview tab.
<b>CCELITE0058</b>	<b>Unable to retrieve Command Central port number.</b>
<b>Explanation</b>	An error occurred while trying to retrieve the port number of Command Central.
<b>Action</b>	Ensure that the Platform Manager that belongs to this Command Central installation is running.
<b>CCELITE0059</b>	<b>The license metering cannot be stopped, because metering is required.</b>
<b>Explanation</b>	One of the active license manifests contains a product for which license metering is required, so that it is not possible to stop the metering.
<b>Action</b>	Remove the license manifest that requires metering or keep license metering running.
<b>CCELITE0060</b>	<b>No node alias specified.</b>
<b>Explanation</b>	The alias of a node was not specified.
<b>Action</b>	Specify a valid node alias. The available node aliases can be determined from the landscape configuration.
<b>CCELITE0061</b>	<b>No product id specified.</b>
<b>Explanation</b>	The ID of the product for which contracts are to be retrieved is not specified.
<b>Action</b>	Specify a valid product ID. The available product IDs can be determined from the landscape configuration.
<b>CCELITE0062</b>	<b>Node alias {0} is invalid.</b>
<b>Explanation</b>	A node with the specified alias {0} is not registered in Command Central.
<b>Action</b>	Specify a valid node alias. The available node aliases can be determined from the landscape configuration.

<b>CCELITE0063</b>	<b>No server details found for node with alias {0}.</b>
<b>Explanation</b>	The server details could not be determined for the node with the specified alias {0}.
<b>Action</b>	Make sure that the Platform Manager on the node with the specified alias is running.
<b>CCELITE0064</b>	<b>No product with id {0} found on node with alias {1}.</b>
<b>Explanation</b>	There is no product with the specified ID {0} installed on the node with the specified alias {1}.
<b>Action</b>	Specify the ID of a product that is installed on the node with the specified alias. The available product IDs can be determined from the landscape configuration.
<b>CCELITE0065</b>	<b>Platform Manager on node with alias {0} is not running.</b>
<b>Explanation</b>	The Platform Manager on the node with alias {0} is not running.
<b>Action</b>	Start Platform Manager on the node with alias {0} and execute the command again.
<b>CCELITE0068</b>	<b>Version {0} of license manifest is not supported. Highest supported version is {1}.</b>
<b>Explanation</b>	The version {0} of the specified license manifest is higher than the version {1} currently supported.
<b>Action</b>	Update Command Central to a version that supports the version of the specified license manifest.
<b>CCELITE0069</b>	<b>Version {0} of license report is not supported. Highest supported version is {1}.</b>
<b>Explanation</b>	The version {0} of the specified license report is higher than the version {1} currently supported.
<b>Action</b>	Update Command Central to a version that supports the version of the specified license report.
<b>CCELITE0070</b>	<b>Aggregated license report with alias {0} already exists.</b>
<b>Explanation</b>	An aggregated license report with the alias {0} already exists.
<b>Action</b>	Specify an aggregated license report with a different alias.
<b>CCELITE0071</b>	<b>Alias {0} already exists.</b>
<b>Explanation</b>	A license key with the specified alias {0} already exists.
<b>Action</b>	Specify a different alias.

---

<b>CCELITE0072</b>	<b>ProductCode and productId specified.</b>
<b>Explanation</b>	You must specify either productCode or productId.
<b>Action</b>	Remove either productCode or productId.
<b>CCELITE0073</b>	<b>Platform and OS specified.</b>
<b>Explanation</b>	You must specify either platform, or operating system.
<b>Action</b>	Remove either the platform or the operating system.
<b>CCELITE0074</b>	<b>Invalid platform(s) {0} specified.</b>
<b>Explanation</b>	The specified platform(s) {0} is invalid.
<b>Action</b>	Specify valid platform(s).
<b>CCELITE0075</b>	<b>Specified installationType {0} is invalid</b>
<b>Explanation</b>	The specified installationType {0} is invalid.
<b>Action</b>	Specify a valid installationType.
<b>CCELITE0076</b>	<b>Invalid productCode {0} specified.</b>
<b>Explanation</b>	The specified productCode {0} is invalid.
<b>Action</b>	Specify a valid productCode.
<b>CCELITE0077</b>	<b>Invalid productId {0} specified.</b>
<b>Explanation</b>	The specified productId {0} is invalid.
<b>Action</b>	Specify a valid productId.
<b>CCELITE0078</b>	<b>Invalid os {0} specified.</b>
<b>Explanation</b>	The specified OS {0} is invalid.
<b>Action</b>	Specify valid OS.
<b>CCELITE0080</b>	<b>Specified licenseKeyType {0} is invalid.</b>
<b>Explanation</b>	The specified licenseKeyType {0} is invalid.
<b>Action</b>	Specify a valid licenseKeyType.

<b>CCELITE0081</b>	<b>Error verifying landscape checksum.</b>
<b>Explanation</b>	An error occurred when trying to verify the landscape checksum.
<b>Action</b>	Contact Software AG Global Support.
<b>CCELITE0082</b>	<b>Invalid license key.</b>
<b>Explanation</b>	The specified file is not a valid license key. A valid license key must not contain binary data or be empty.
<b>Action</b>	Specify a valid license key.
<b>CCELITE0083</b>	<b>Invalid license key: {0}.</b>
<b>Explanation</b>	Specified file is not a valid license key.
<b>Action</b>	Specify a valid license key.
<b>CCELITE0084</b>	<b>A node with the specified alias does not exist.</b>
<b>Explanation</b>	An installation (node) with the specified alias name does not exist.
<b>Action</b>	Specify a valid alias name for an existing installation (node).
<b>CCELITE0085</b>	<b>A run-time component with the specified id does not exist.</b>
<b>Explanation</b>	A run-time component with the specified ID does not exist on the node(s).
<b>Action</b>	Specify an ID of an existing runtime component.
<b>CCELITE0090</b>	<b>Invalid productCode {0} and productId {1} specified.</b>
<b>Explanation</b>	The specified productCode {0} and productId {1} is invalid.
<b>Action</b>	Specify a valid productCode and productId.
<b>CCELITE0091</b>	<b>Unexpected exception occurred: {0}</b>
<b>Explanation</b>	An unexpected exception occurred: {0}
<b>Action</b>	Contact Software AG support.
<b>CCELITE0092</b>	<b>Failed to update server time stamp for server {0} : {1}</b>
<b>Explanation</b>	Failed to update server time stamp for server {0} : {1}
<b>Action</b>	Make sure the Platform Manager on server {0} is running.

---

<b>CCELITE0093</b>	<b>Error creating URL from urlString {0}.</b>
<b>Explanation</b>	Error creating URL from urlString {0}.
<b>Action</b>	Specify a valid URL.
<b>CCELITE0094</b>	<b>License key with specified alias {0} not found.</b>
<b>Explanation</b>	A license key with the specified alias {0} is not stored in the license key manager.
<b>Action</b>	Specify the alias of a stored license key.
<b>CCELITE0102</b>	<b>Alias must be specified for custom license keys.</b>
<b>Explanation</b>	You must specify an alias when adding a custom license key.
<b>Action</b>	Specify a license key alias.
<b>CCELITE0105</b>	<b>Invalid license key archive.</b>
<b>Explanation</b>	The specified file is not a valid license key archive. A valid license key archive must contain license keys.
<b>Action</b>	Specify a valid license key archive.
<b>CCELITE0106</b>	<b>License key already stored with alias {0}.</b>
<b>Explanation</b>	This license key is already stored with alias {0}.
<b>Action</b>	Specify another license key, or add the license key with a different alias.
<b>CCELITI0033</b>	<b>Type of installation is not defined. Product cannot be checked.</b>
<b>Explanation</b>	The Platform Manager where the product is installed does not have a type of installation (Development, Production, Test) defined.
<b>Action</b>	Define a type of installation for your Platform Manager.
<b>CCELITI0038</b>	<b>Product is not found in the license manifest(s).</b>
<b>Explanation</b>	You have no valid license for the installed product.
<b>Action</b>	Contact Software AG for licensing your product.
<b>CCELITI0039</b>	<b>Core class does not match: {0} is installed, {1} is licensed.</b>
<b>Explanation</b>	The core class of the Platform Manager server does not match the licensed core class.
<b>Action</b>	Contact Software AG Global Support for licensing a higher core class.

<b>CCELITI0040</b>	<b>License capacity does not match: {0} {1} used, {2} {1} licensed.</b>
<b>Explanation</b>	The number of units used does not match the licensed number of units.
<b>Action</b>	Contact Software AG Global Support for licensing a higher number of units.
<b>CCELITI0043</b>	<b>Installation type does not match: {0} is installed, {1} is licensed.</b>
<b>Explanation</b>	The installation type of the Platform Manager server does not match the licensed installation type.
<b>Action</b>	Contact Software AG Global Support for licensing the appropriate installation type.
<b>CCELITW0021</b>	<b>Unable to translate extended rights code ({0}), not found</b>
<b>Explanation</b>	The table used to look up license Extended Rights codes does not contain the indicated value.
<b>Action</b>	Contact Software AG Global Support.
<b>CCELITW0025</b>	<b>LicenseReportFactory - unable to determine runtime status for component ({0}) on node ({1}); caught this: type({2}), msg({3})</b>
<b>Explanation</b>	Command Central can not determine if the identified component is up or down.
<b>Action</b>	This behavior could occur when the Platform Manager node is down, or because of some other communication issue. If this problem persists when the Platform Manager node is up, contact Software AG Global support.
<b>CCELNDE0000</b>	<b>The node alias is invalid.</b>
<b>Explanation</b>	An installation (node) with the specified alias name does not exist.
<b>Action</b>	Specify the valid alias name for an existing installation (node).
<b>CCELNDE0001</b>	<b>"{0}" Run-time component is not found on node "{1}".</b>
<b>Explanation</b>	The Landscape Inventory cache does not contain run-time component "{0}" for node "{1}".
<b>Action</b>	Use a combination of an existing run-time component Id and node alias or refresh the Landscape Inventory run-time component cache and try again.
<b>CCELNDE0002</b>	<b>Invalid node alias or url.</b>
<b>Explanation</b>	The specified alias name or URL for an installation (node) is not valid.
<b>Action</b>	Specify a valid alias name or URL.

---

<b>CCELNDE0003</b>	<b>Specify a valid URL.</b>
<b>Explanation</b>	The URL field in NodeInfo contains an invalid value.
<b>Action</b>	Check if the URL syntax of the node is valid.
<b>CCELNDE0004</b>	<b>A node with a different alias for the same host:port already exist.</b>
<b>Explanation</b>	An installation (node) with a different alias name already exists for the installation with the specified host name and port number.
<b>Action</b>	None.
<b>CCELNDE0006</b>	<b>Node {0} could not be created.</b>
<b>Explanation</b>	A node with alias {0} could not be created because another node with alias {1} already exists.
<b>Action</b>	Provide a different alias for the new node.
<b>CCELNDE0008</b>	<b>Can not retrieve node's product information for {0}</b>
<b>Explanation</b>	Command Central can not connect to Platform Manager to retrieve Platform Manager product information.
<b>Action</b>	Make sure the node is online.
<b>CCELNDE0009</b>	<b>Can not update inventory cache because of failure during retrieval of remote inventory items.</b>
<b>Explanation</b>	The remote request for inventory items failed and the inventory cache can not be updated.
<b>Action</b>	Ensure that the node in the request is active or the target node inventory is responsive.
<b>CCELNDE0010</b>	<b>The node alias cannot be empty or longer than 100 characters.</b>
<b>Explanation</b>	The specified node alias is incorrect, either because the node alias is empty, or it exceeds 100 characters.
<b>Action</b>	Specify a correct node alias and try again.
<b>CCELNDE0011</b>	<b>The host name should be between 2 and 253 characters long.</b>
<b>Explanation</b>	The host name is incorrect, because it is shorter or longer than the specified character length limitations.
<b>Action</b>	Provide a correct host name and try again.

<b>CCELNDE0012</b>	<b>The node display name should not be longer than 100 characters.</b>
<b>Explanation</b>	The node display name is incorrect, because it is longer than 100 characters.
<b>Action</b>	Specify a correct node display name and try again.
<b>CCELNDE0013</b>	<b>Trying to use unavailable NodeInfo element.</b>
<b>Explanation</b>	The specified element of type NodeInfo does not exist.
<b>Action</b>	Specify a NodeInfo element that is available.
<b>CCELNDE0014</b>	<b>Node alias is not valid. Only letters, numbers, -, _ and . are allowed.</b>
<b>Explanation</b>	The specified node alias is incorrect, because it uses special characters that are not allowed.
<b>Action</b>	Specify a correct node alias and try again.
<b>CCELNDI0005</b>	<b>You have exhausted the number of licensed nodes that can be configured. To add more nodes, contact your system administrator or Software AG support to get the license upgraded.</b>
<b>Explanation</b>	You have exhausted the number of licensed nodes that can be configured.
<b>Action</b>	To add more nodes, contact your system administrator or Software AG support to get the license upgraded.
<b>CCELSRE0001</b>	<b>The node alias cannot be updated.</b>
<b>Explanation</b>	You cannot update the alias name for an installation (node).
<b>Action</b>	Create a new installation or update the existing installation without changing the alias name.
<b>CCELSRE0002</b>	<b>The environment alias cannot be updated.</b>
<b>Explanation</b>	You cannot change the alias name of an environment.
<b>Action</b>	Create a new environment or update the existing environment without changing the alias name.
<b>CCELSRE0004</b>	<b>Node Aliases not specified!</b>
<b>Explanation</b>	To add installations (nodes) to an environment, you must specify the alias names of the installations that you want to add.
<b>Action</b>	Try again, this time specifying the installation (node) alias names as query parameters.

---

<b>CCELSRE0005</b>	<b>Alias not specified or invalid.</b>
<b>Explanation</b>	The environment could not be created or updated because the alias is invalid.
<b>Action</b>	Specify a valid alias. You can view a list of installations and their aliases using the following command: <code>cc list landscape nodes</code>
<b>CCELSRE0006</b>	<b>Node {0} could not be created.</b>
<b>Explanation</b>	A node with alias {0} could not be created because another node with alias {1} already exists.
<b>Action</b>	Provide a different alias for the new node.
<b>CCELSRE0007</b>	<b>Environment {0} could not be created.</b>
<b>Explanation</b>	An environment with alias {0} could not be created because another environment with alias {1} already exists.
<b>Action</b>	Provide a different alias for the new environment.
<b>CCELSRE0008</b>	<b>Trying to use unavailable NodeInfo element.</b>
<b>Explanation</b>	Trying to use element of type NodeInfo that doesn't exist.
<b>Action</b>	Provide an available NodeInfo element.
<b>CCELSRE0012</b>	<b>Alias not specified.</b>
<b>Explanation</b>	The node could not be created because the alias is missing.
<b>Action</b>	Specify a valid alias.
<b>CCELSRE0013</b>	<b>Node {0} could not be created.</b>
<b>Explanation</b>	A node with alias {0} could not be created because the specified location id {1} does not exist.
<b>Action</b>	Provide an existing location id. Available location id(s): {2}
<b>CCELSRE0014</b>	<b>Node {0} could not be updated.</b>
<b>Explanation</b>	A node with alias {0} could not be updated because the specified location id {1} does not exist.
<b>Action</b>	Provide an existing location id. Available location id(s): {2}

<b>CCELSRE0015</b>	<b>Node {0} could not be created.</b>
<b>Explanation</b>	A node with alias {0} could not be created because the specified installation type {1} is invalid.
<b>Action</b>	Provide a valid installation type. Valid installation types are: {2}
<b>CCELSRE0016</b>	<b>Node {0} could not be updated.</b>
<b>Explanation</b>	A node with alias {0} could not be updated because the specified installation type {1} is invalid.
<b>Action</b>	Provide a valid installation type. Valid installation types are: {2}
<b>CCELSRI0000</b>	<b>A node with the specified alias does not exist.</b>
<b>Explanation</b>	No node alias matches {0}
<b>Action</b>	Provide a valid node alias.
<b>CCELSRI0003</b>	<b>The environment with the provided alias doesn't exist.</b>
<b>Explanation</b>	An environment with the specified alias name does not exist.
<b>Action</b>	Specify the valid alias name of an existing environment.
<b>CCEMIGE0019</b>	<b>Extracting source version failed.</b>
<b>Explanation</b>	Command Central failed to extract the source version from the bundles.info file.
<b>Action</b>	Ensure that the bundles.info file is at the correct location.
<b>CCEMONE0001</b>	<b>{0} on {1} ({2}) became unresponsive. Component restart may help to resolve this quickly.</b>
<b>Explanation</b>	{0} on {1} ({2}) became unresponsive.
<b>Action</b>	Component restart may help to resolve this quickly.
<b>CCEMONE0002</b>	<b>{0} on {1} ({2}) crashed. You will need to start it again and investigate the cause of the failure.</b>
<b>Explanation</b>	RuntimeStatus of {0} went from ONLINE to FAILED.
<b>Action</b>	Try to restart it. Have a look on {1} ({2}) for additional information on its status.

---

<b>CCEMONE0006</b>	<b>{0} of {1} on {2} ({3}) spiked into critical zone. The component may become overloaded!</b>
<b>Explanation</b>	The kpi {0} of {1} went from MARGINAL into CRITICAL status.
<b>Action</b>	Please have a look on {2} ({3}) to find out why this is happening.
<b>CCEMONE0011</b>	<b>Node with alias {0} does not exist.</b>
<b>Explanation</b>	There is no node with the specified alias registered with Command Central.
<b>Action</b>	Ensure that the node alias is spelled correctly and that it is registered with Command Central.
<b>CCEMONE0012</b>	<b>No runtime monitoring information could be found for component {0}.</b>
<b>Explanation</b>	The landscape nodes do not have monitoring information for the specified component.
<b>Action</b>	Check the landscape nodes for the for the specified component. Ensure that the specified component exists on the nodes and that it is spelled correctly.
<b>CCEMONE0013</b>	<b>Component {0} does not exist on node {1}.</b>
<b>Explanation</b>	The specified runtime component does not exist on the specified SPM node.
<b>Action</b>	Ensure that the specified component is spelled correctly and exists on the specified node.
<b>CCEMONE0014</b>	<b>Removing alert with id {0} failed.</b>
<b>Explanation</b>	The specified alert could not be found.
<b>Action</b>	Ensure that the alert with the specified ID exists in the Command Central landscape.
<b>CCEMONE0015</b>	<b>Error getting runtime component {0} for node {1}</b>
<b>Explanation</b>	Runtime component {0} is not available in cache.
<b>Action</b>	Try to update the inventory cache and make sure the node in the request is active and the target node inventory is responsive.
<b>CCEMONE0016</b>	<b>includeChildren parameter requires NodeAlias and RuntimeComponentId to be provided.</b>
<b>Explanation</b>	The <includeChildren> parameter requires the <nodeAlias> and <runtimeComponentId> parameters to be provided.
<b>Action</b>	Provide values for the <nodeAlias> and <runtimeComponentId> parameters.

<b>CCEMONE0017</b>	<b>Alerts filtering requires both NodeAlias and RuntimeComponentId.</b>
<b>Explanation</b>	The filtering of alerts requires both <NodeAlias> and <RuntimeComponentId> parameters to be provided.
<b>Action</b>	Provide values for both <NodeAlias> and <RuntimeComponentId> parameters.
<b>CCEMONE0018</b>	<b>Error while handling event [{0}].</b>
<b>Explanation</b>	There was an error while handling an event.
<b>Action</b>	Check the logs for previous errors.
<b>CCEMONE0019</b>	<b>Error polling SPM node [{0}].</b>
<b>Explanation</b>	The monitoring states for a runtime component on a target node could not be retrieved.
<b>Action</b>	Check the logs for previous errors.
<b>CCEMONE0020</b>	<b>Error during retrieving of monitoring state of {0} on node {1}.</b>
<b>Explanation</b>	The monitoring state for a runtime component on a target node could not be retrieved.
<b>Action</b>	Check the logs for previous errors.
<b>CCEMONE0021</b>	<b>Error polling SPM node [{0}]. Node Status will be set to {1} and the Runtime State for all instances of the node will be set to {2}.</b>
<b>Explanation</b>	The monitoring states on a target node could not be retrieved and as a result all states will be set to unknown.
<b>Action</b>	Check the logs for previous errors.
<b>CCEMONE0022</b>	<b>Could not retrieve Cache. Monitoring stopped.</b>
<b>Explanation</b>	The Command Central cache manager could not be retrieved.
<b>Action</b>	Contact Software AG Global Support.
<b>CCEPROE0000</b>	<b>No node with alias, {0}, exists in the environment.</b>
<b>Explanation</b>	The node alias specified in the request does not exist.
<b>Action</b>	Resubmit the request with an existing node alias.

---

<b>CCEPROE0001</b>	<b>No artifacts specified in uninstall request.</b>
<b>Explanation</b>	The uninstall request did not specify any artifacts.
<b>Action</b>	Resubmit the request with a list of valid artifacts.
<b>CCEPROE0002</b>	<b>{0} is an invalid/unsupported type for artifacts.</b>
<b>Explanation</b>	Only Product and Fix are valid artifact types.
<b>Action</b>	Resubmit the request with valid artifacts.
<b>CCEPROE0003</b>	<b>{0} MASTER repository configuration is invalid.</b>
<b>Explanation</b>	The repository configuration misses the location URL.
<b>Action</b>	Remove and add this repository again to ensure it has valid remote location URL.
<b>CCEPROE0004</b>	<b>{0} repository is not configured with user credentials.</b>
<b>Explanation</b>	The repository configuration misses username property value. Most likely the repository was not configured with the required user credentials after it was discovered.
<b>Action</b>	Configure the repository with valid user credentials.
<b>CCEPROE0005</b>	<b>{0} repository is not configured with user credentials.</b>
<b>Explanation</b>	The repository configuration misses the username property value. Most likely the repository was not configured with the required user credentials after it was discovered.
<b>Action</b>	Configure the repository with valid user credentials.
<b>CCEPROE0006</b>	<b>{0} IMAGE repository configuration is invalid.</b>
<b>Explanation</b>	The repository configuration misses the image file location.
<b>Action</b>	Edit this repository to ensure it has a valid image location.
<b>CCEPROE0007</b>	<b>Node {0} is already registred and reports ONLINE status.</b>
<b>Explanation</b>	The node that you are attempting to bootstrap already reports ONLINE status. Most likely you specified a node that is already setup and ready to use.
<b>Action</b>	Use a node alias for a Platform Manager that is not running yet. It can be a node that is already registered but does not have a backing Platform Manager, or a completely new node alias that will be added to the landscape when the Platform Manager bootstrap operation is finished.

<b>CCEPROE0008</b>	<b>Repository {0} type is not a MASTER repository.</b>
<b>Explanation</b>	Bootstrap images can be generated only from a MASTER PRODUCT repository. Other types are not supported.
<b>Action</b>	Specify a configured MASTER PRODUCT repository with valid user credentials and try again.
<b>CCEPROE0009</b>	<b>Repository {0} is not configured with a user password.</b>
<b>Explanation</b>	MASTER repositories require configuration of user credentials.
<b>Action</b>	Ensure that the selected repository is configured with a valid username and password.
<b>CCEPROE0010</b>	<b>Target machine platform is not specified.</b>
<b>Explanation</b>	The bootstrap operation requires the target platform to be explicitly defined.
<b>Action</b>	Select platform of the target machine that Platform Manager will be installed
<b>CCEPROE0011</b>	<b>Cannot match requested version {0} to any of the configured repositories.</b>
<b>Explanation</b>	The version you requested to install does not match the available repositories.
<b>Action</b>	Select a specific repository or add new repositories that will match the version you requested.
<b>CCEPROE0012</b>	<b>No PRODUCT repositories are defined to complete the operation.</b>
<b>Explanation</b>	You did not explicitly specify a repository or version to use and Command Central cannot automatically pick a repository.
<b>Action</b>	Ensure that you have configured a PRODUCT repository that contains the required version of Platform Manager.
<b>CCEPROE0013</b>	<b>Remote machine credentials are not provided.</b>
<b>Explanation</b>	Command Central cannot connect to a remote machine without valid user credentials.
<b>Action</b>	Provide user credentials for the remote machine on which you are installing Platform Manager.
<b>CCEPROE0014</b>	<b>Error while retrieving configuration.</b>
<b>Explanation</b>	Internal error while retrieving common proxy configuration.
<b>Action</b>	Make sure COMMON-PROXY configuration exists.

---

<b>CCEPROE0015</b>	<b>Remote access service returned {0} jobs while 1 was expected.</b>
<b>Explanation</b>	Only one remote operation was initiated but a different amount of jobs was returned.
<b>Action</b>	Contact Software AG Global Support.
<b>CCEPROE0016</b>	<b>Java not found on {0}.</b>
<b>Explanation</b>	The Java Runtime Environment is not available on the given node.
<b>Action</b>	Install Java Runtime Environment and try again.
<b>CCEPROE0017</b>	<b>Remote command returned a non-zero exit code: {0}</b>
<b>Explanation</b>	The remote installer command failed. Check the logs for more information.
<b>Action</b>	Re-try the operation. If the problem persists, contact Software AG Global Support.
<b>CCEPROE0018</b>	<b>Can not connect to Platform Manager running on host {0} and port {1} due to wrong credentials.</b>
<b>Explanation</b>	Can not connect to Platform Manager due to wrong credentials.
<b>Action</b>	Provide valid Platform Manager credentials.
<b>CCEPROE0026</b>	<b>The nodeAlias field is required for each node that is added.</b>
<b>Explanation</b>	Node alias is required field for each node that is added.
<b>Action</b>	Provide node alias.
<b>CCEPROE0027</b>	<b>The hostname field is required for each node that is added.</b>
<b>Explanation</b>	A hostname is required field for each node that is added.
<b>Action</b>	Provide a hostname.
<b>CCEPROE0028</b>	<b>Platform Manager port is required field for each node that is added.</b>
<b>Explanation</b>	A Platform Manager port is required field for each node that is added.
<b>Action</b>	Provide a port field value.
<b>CCEPROE0029</b>	<b>Platform Manager nodes are available, but the provided credentials for them are wrong: {0}</b>
<b>Explanation</b>	Platform Manager nodes are available, but the provided credentials for them are incorrect.
<b>Action</b>	Provide valid credentials for the Platform Manager nodes.

<b>CCEPROE0030</b>	<b>The Platform Managers are not remotely accessible: {0}</b>
<b>Explanation</b>	The specified Platform Managers are not remotely accessible.
<b>Action</b>	Check the connectivity and the remote accessibility to the Platform Managers.
<b>CCEPROE0034</b>	<b>Error occured while installing {2} on node {0}. Remote task status is {1}</b>
<b>Explanation</b>	The selected artifact was not installed on the remote managed node.
<b>Action</b>	See the error logs for more details about the error.
<b>CCEPROE0038</b>	<b>The maximum number of retries for installing artifacts from repository {0} on node {1} due to possible Platform Manager restarts is reached.</b>
<b>Explanation</b>	The maximum number of retries for installing artifacts from repository {0} on node {1} due to possible Platform Manager restarts is reached.
<b>Action</b>	Check the logs for details about previous attempts to install artifacts to determine what the issues are.
<b>CCEPROE0042</b>	<b>The maximum number of retries for uninstalling artifacts on node {0} due to possible Platform Manager restarts is reached.</b>
<b>Explanation</b>	The maximum number of retries for uninstalling artifacts on node {0} due to possible Platform Manager restarts is reached.
<b>Action</b>	Check the logs for details about previous attempts to install artifacts to determine what the issues are.
<b>CCEPROE0043</b>	<b>Creating an image with name {0} failed.</b>
<b>Explanation</b>	Creating an image from a mirror repository that is not on the local Platform Manager is not supported.
<b>Action</b>	Create a mirror repository on the local Platform Manager node and use it for bootstrapping.
<b>CCEPROE0044</b>	<b>Bootstrapping Platform Manager on installation with alias {0} failed.</b>
<b>Explanation</b>	The export of artifacts from a mirror repository with name {0} into image with name {1} failed.
<b>Action</b>	See the Platform Manager logs for more information.

---

<b>CCEPROE0046</b>	<b>Bootstrap installer {0} not found.</b>
<b>Explanation</b>	The bootstrap installer file was not found under install_dir/profiles/CCE/data/installers
<b>Action</b>	Make sure the specified bootstrap installer file is in the correct location.
<b>CCEPROE0047</b>	<b>unzip command not found on {0}</b>
<b>Explanation</b>	The unzip package is not present in your cygwin environment.
<b>Action</b>	Install unzip in your cygwin environment and try again.
<b>CCEPROE0048</b>	<b>Local bootstrap completed with exit code: {0}</b>
<b>Explanation</b>	The execution of the bootstrap operation failed unexpectedly.
<b>Action</b>	Check the bootstrap logs for more information.
<b>CCEPROE0049</b>	<b>The installers directory does not exist.</b>
<b>Explanation</b>	The directory containing the bootstrap installers does not exist.
<b>Action</b>	Create the install_dir/profiles/CCE/data/installers directory.
<b>CCEPROE0050</b>	<b>Installer platform mismatch! Expected W64 but found {0}.</b>
<b>Explanation</b>	The installation cannot be performed, because the incorrect platform is selected.
<b>Action</b>	Select an installer with the correct platform.
<b>CCEPROE0051</b>	<b>{0} is not a valid installer directory or it does not exist.</b>
<b>Explanation</b>	The bootstrap installer archive may not have been extracted correctly.
<b>Action</b>	Retry the operation or contact Software AG global support.
<b>CCEPROE0052</b>	<b>Invalid number of Windows scripts in the installer directory: {0}</b>
<b>Explanation</b>	The bootstrap installer archive must contain exactly one executable script (batch).
<b>Action</b>	Obtain the correct bootstrap installer.
<b>CCEPROE0055</b>	<b>Platform Manager nodes are available, but the installation directory is different than requested: {0}</b>
<b>Explanation</b>	The Platform Manager nodes are available, but the installation directory is different than requested.
<b>Action</b>	Change the installation directory or stop the available Platform Manager if you want to bootstrap a new instance on the same ports.

**CCEPROW0045**      **The SSH server did not return the exit code of the bootstrap operation. The operation has completed but it is not clear if it was successful or not.**

**Explanation**      In some cases the SSH server may not return the exit code of the executed operation. This makes it unclear if the operation was successful or not.

**Action**            Examine the installation logs on the remote node to make sure the installation was successful.

**CCERARE0000**      **Not all mandatory parameters are specified.**

**Explanation**      Some of the parameters required for this request are missing.

**Action**            Check the Command Central documentation for the required parameters.

**CCERARE0001**      **Nothing has been scheduled for execution for this request.**

**Explanation**      This request should start jobs for execution, but no jobs have started.

**Action**            Check the logs for errors why the request has not terminated properly.

**CCERARE0002**      **Remote Access Service is missing.**

**Explanation**      A required service is missing.

**Action**            Check whether the remote-access bundle is started and has registered any services.

**CCERARE0003**      **The private key must be specified when certificate is used for authentication.**

**Explanation**      The selected authorization method is "certificate", however, a path to the private key is not specified.

**Action**            Specify the path to the private key.

**CCEREAE0003**      **Authentication method {0} not supported.**

**Explanation**      The specified authentication method is not supported.

**Action**            Check the Command Central documentation for the supported authentication methods.

**CCEREAE0004**      **The provided private key does not exist: {0}**

**Explanation**      The specified file that contains the private key does not exist on the file system.

**Action**            Make sure the private key is available.

---

<b>CCEREA0005</b>	<b>Remote host should be specified.</b>
<b>Explanation</b>	Remote host is not specified and a connection cannot be established.
<b>Action</b>	Specify the remote host.
<b>CCEREA0007</b>	<b>{0} not found on {1}</b>
<b>Explanation</b>	The specified path cannot be found on the target host.
<b>Action</b>	Make sure the specified path exists and try again.
<b>CCEREA0008</b>	<b>Invalid output from df: {0}</b>
<b>Explanation</b>	The output of the df command does not match the POSIX standard.
<b>Action</b>	Make sure the target system has a POSIX compliant df command.
<b>CCEREA0009</b>	<b>The home directory of user {0} on host {1} could not be found.</b>
<b>Explanation</b>	The home directory of the specified user on the specified host could not be found.
<b>Action</b>	Check the configuration of the remote endpoint.
<b>CCEREA0010</b>	<b>Cannot close remote receive session.</b>
<b>Explanation</b>	The remote session for receiving files cannot be closed.
<b>Action</b>	Check the logs for previous errors.
<b>CCEREMW0000</b>	<b>Error producing zipped log source contents. Node alias: {0}, RuntimeComponent: {1}, Log Source Aliases: {2} Details: {3}</b>
<b>Explanation</b>	An error occurred while producing the zipped archive containing a collection of log source contents on the Command Central server.
<b>Action</b>	Try again. If the problem persists, contact Software AG Global Support.
<b>CCEREMW0001</b>	<b>Error attempting to close a file store used to produce zipped collection of log source contents.</b>
<b>Explanation</b>	An error occurred while closing the zip file system object containing a collection of log source file contents.
<b>Action</b>	No action required.

**CCEREMW0002**      **Error attempting to delete a temporary file used to create a zipped collection of log source contents. Filename: {0}**

**Explanation**      An attempt to delete the specified file has failed.

**Action**            Locate the file on the server hosting Command Central and delete the file if it still exists.

**CCEREMW0004**      **Error producing zipped log source contents. Node alias: {0} Details: {1}**

**Explanation**      An error occurred while producing the zipped archive containing a collection of log source contents on the Command Central server.

**Action**            Try again. If the problem persists, contact Software AG Global Support.

**CCEREPE0000**      **No repository with id, {0}, exists on managed node, {1}**

**Explanation**      The specified repository does not exist.

**Action**            Ensure the correct repository id is specified in the request, or add the desired repository to the managed node.

**CCEREPE0001**      **No repository with id, {0}, exists on managed node, {1}**

**Explanation**      The specified repository does not exist.

**Action**            Ensure the correct repository id is specified in the request, or add the desired repository to the managed node.

**CCEREPE0002**      **No such node, {0}**

**Explanation**      The node alias specified in the request does not exist.

**Action**            Specify the correct node alias, or add the relevant node to the environment.

**CCEREPE0003**      **The specified image location does not exist.**

**Explanation**      The specified location for an image repository was not found on the file system.

**Action**            Provide a valid location for the image repository.

**CCEREPE0004**      **The specified repository does not exist.**

**Explanation**      The specified repository was not found.

**Action**            Check the repository name and provide the name of an existing repository.

---

<b>CCEREPE0005</b>	<b>Parameters cannot be empty or missing.</b>
<b>Explanation</b>	All parameters are required.
<b>Action</b>	Specify values for all parameters.
<b>CCEREPE0006</b>	<b>A repository with this name already exists.</b>
<b>Explanation</b>	The name of the repository should be unique.
<b>Action</b>	Check the repository name and provide a unique name for the repository.
<b>CCEREPE0007</b>	<b>A repository at the same location already exists.</b>
<b>Explanation</b>	Two or more repositories cannot point to the same location.
<b>Action</b>	Provide a unique location for the new repository.
<b>CCEREPE0008</b>	<b>The specified repository points to an image file but the repository type is not image.</b>
<b>Explanation</b>	The specified repository cannot point to an image file, because the repository type is not image.
<b>Action</b>	Specify the correct repository type.
<b>CCEREPE0009</b>	<b>There is no repository to register.</b>
<b>Explanation</b>	No repository is found for the specified name.
<b>Action</b>	Check the repository and resubmit the request.
<b>CCEREPE0010</b>	<b>User credentials are missing.</b>
<b>Explanation</b>	No user credentials are specified for the repository.
<b>Action</b>	Add user credentials for the repository.
<b>CCEREPE0011</b>	<b>Connection to node {0} failed.</b>
<b>Explanation</b>	Could not connect to node {0}.
<b>Action</b>	Check if the node is online.
<b>CCEREPE0012</b>	<b>Repository with type {0} does not exist.</b>
<b>Explanation</b>	The repository with the specified type does not exist.
<b>Action</b>	Specify an existing repository type for the repository.

<b>CCEREPE0013</b>	<b>Repository content cache invalidate failed.</b>
<b>Explanation</b>	Invalidation of the content cache for repository {0} and nodeAlias {1} failed.
<b>Action</b>	See the Command Central logs for more details.
<b>CCEREPE0015</b>	<b>Repository with the specified name: {0} does not exist.</b>
<b>Explanation</b>	Importing content from the repository with name: {0} failed because a repository with the specified name was not found.
<b>Action</b>	Check the repository name and provide the name of an existing repository.
<b>CCEREPE0020</b>	<b>Error occurred while importing artifacts from repository with name: {0} to mirror repository with name: {1} for platforms: {2}</b>
<b>Explanation</b>	An error occurred while importing artifacts from repository with name: {0} to mirror repository with name: {1} for platforms: {2}
<b>Action</b>	See the corresponding Platform Manager logs for more details.
<b>CCEREPE0024</b>	<b>Mirror repository with name: {0} is not published or registered on Command Central.</b>
<b>Explanation</b>	Command Central cannot identify the specified mirror repository.
<b>Action</b>	Check if a mirror repository with name: {0} is published and registered on Command Central. Note that the Refresh operation refreshes a published mirror repository immediately after it is created or at a later point in time.
<b>CCEREPE0029</b>	<b>Local mirror repository with name {0} can not be removed on target node {1}</b>
<b>Explanation</b>	The local mirror repository with name {0} can not be removed on the target node {1}
<b>Action</b>	See the corresponding Platform Manager logs for more details.
<b>CCEREPE0035</b>	<b>Remote task failed: {0}</b>
<b>Explanation</b>	Remote task failed: {0}
<b>Action</b>	See the corresponding Platform Manager logs for more details.
<b>CCEREPE0036</b>	<b>Initiating mirror operation not from an image repository and without selecting "Product Repositories" is not supported.</b>
<b>Explanation</b>	This operation is not supported as it might be time consuming because of the size of the source repository.
<b>Action</b>	Either select a product repository, or change the source repository to an image repository.

---

<b>CCEREPE0038</b>	<b>Cannot delete Mirror repository with name: {0} because node with alias: {1} does not exist. Register node for host:{2} and port:{3}.</b>
<b>Explanation</b>	The mirror repository is physically stored on {1} node, which was deleted and is not now registered in Command Central.
<b>Action</b>	Add the node with alias: {1} , host: {2} and port: {3}
<b>CCEREPE0039</b>	<b>Cannot perform mirror operation because node with alias: {0} does not exist any more. Register again the node with alias: {0} for host: {1} and port: {2}.</b>
<b>Explanation</b>	The mirror repository is physically stored on {0} node, which was deleted and is not now registered in Command Central.
<b>Action</b>	Add the node with alias: {0} , host: {1} and port: {2}
<b>CCEREPE0041</b>	<b>Content of repository with displayName : {0} cannot be loaded.</b>
<b>Explanation</b>	The content of the repository with displayName : {0} cannot be listed.
<b>Action</b>	Use a different repository type or check all logs for details about the error.
<b>CCEREPE0042</b>	<b>Generation of repository status report for repository {0} will be skipped because connectivity validation failed.</b>
<b>Explanation</b>	Generating the Repository Status report will be skipped and the list content operation will not be triggered.
<b>Action</b>	Check if the proxy is available and if the Platform Manager proxy configuration is set correctly. Also, check if the user credentials are valid.
<b>CCEREPE0043</b>	<b>Creating a mirror repository failed because the source repository is not specified.</b>
<b>Explanation</b>	The source repository from which to create the mirror repository is not specified.
<b>Action</b>	Specify at least one source repository. You can specify a master, image, or another mirror repository.
<b>CCEREPE0044</b>	<b>Attempt to connect to {0} product repository from {1} installation timed out.</b>
<b>Explanation</b>	Internet access is required to connect to this repository. The error occurred either because the proxy for the local Platform Manager is not configured, or the metadata and the user credentials for the repository are not correct.
<b>Action</b>	Configure a proxy for the local Platform Manager and check the repository metadata.

<b>CCEREPE0048</b>	<b>Repository fix content cache update failed.</b>
<b>Explanation</b>	An explicit repository fix content cache update failed during the regular cache update.
<b>Action</b>	Check if the connection to the fix repository is successful.
<b>CCEREPE0049</b>	<b>Remote task failed: {0}</b>
<b>Explanation</b>	Remote task failed \ : {0}
<b>Action</b>	Check the corresponding Platform Manager logs for more details about the error.
<b>CCEREPE0052</b>	<b>Error while retrieveing credentials with alias {0}.</b>
<b>Explanation</b>	A credentials alias is not defined.
<b>Action</b>	Try again using an existing credentials alias.
<b>CCERPPE0000</b>	<b>The repository name is not specified.</b>
<b>Explanation</b>	The requested operation requires a repository name.
<b>Action</b>	Check the input and provide a repository name.
<b>CCERPPE0001</b>	<b>Repository with the specified name {0} already exists.</b>
<b>Explanation</b>	The repository name must be unique.
<b>Action</b>	Check the repository name and provide a unique name for the repository.
<b>CCERPPE0002</b>	<b>Repository with the specified name {0} does not exists.</b>
<b>Explanation</b>	Editing the repository failed, because a repository with the specified name was not found.
<b>Action</b>	Check the repository name and provide the name of an existing repository.
<b>CCERPPE0003</b>	<b>Unknown repository type. Use one of {0}</b>
<b>Explanation</b>	The specified repository type is not supported by Command Central.
<b>Action</b>	Use one of the suggested repository types.
<b>CCERPPE0004</b>	<b>Destination is not specified.</b>
<b>Explanation</b>	The destination parameter is missing.
<b>Action</b>	Specify a value for the destination parameter. For example, dest=myfixes.zip

---

<b>CCERP0005</b>	<b>Destination parameter contains invalid characters.</b>
<b>Explanation</b>	The destination parameter cannot contain file path manipulation characters.
<b>Action</b>	Specify a proper destination value. For example, dest=myfixes.zip
<b>CCERP0006</b>	<b>Export image job is not found.</b>
<b>Explanation</b>	The job responsible for creating an image is not found on the local Platform Manager.
<b>Action</b>	Check the logs for indication what went wrong.
<b>CCERP0007</b>	<b>The specified path for the image file is not valid.</b>
<b>Explanation</b>	The path specified for the image file is not valid.
<b>Action</b>	Provide a valid path for the image file.
<b>CCERP0008</b>	<b>The specified repository content type ( {0} ) did not match the actual content type of the repository ( {1} ).</b>
<b>Explanation</b>	The specified repository content type ( {0} ) did not match the actual content type of the repository ( {1} ).
<b>Action</b>	Verify that the specified repository content type is correct.
<b>CCERP0009</b>	<b>The specified repository image file location "{0}" is not valid.</b>
<b>Explanation</b>	The specified repository image file location "{0}" is not valid.
<b>Action</b>	Provide a valid repository image file location.
<b>CCERP0010</b>	<b>The artifact : {0} is not found in the repository : {1}</b>
<b>Explanation</b>	The identifier specified for the artifact is not valid or the artifact does not exist in the repository.
<b>Action</b>	Provide a valid identifier for the artifact: <id>_<version>.
<b>CCERP0011</b>	<b>Command Central cannot find the specified image file at the specified location "{0}".</b>
<b>Action</b>	Make sure the given path and file name are correct.

<b>CCERPRE0012</b>	<b>Repository with that name is not found.</b>
<b>Explanation</b>	There is no registered repository with that name.
<b>Action</b>	Provide a valid name of a registered repository.
<b>CCERPRE0013</b>	<b>Repository image location URI is not valid.</b>
<b>Explanation</b>	The location you provided is empty or not a valid URI.
<b>Action</b>	Ensure the provided location is not empty, does not include white spaces and points to a valid image file.
<b>CCESREE0000</b>	<b>Error occurred during retrieving user credentials</b>
<b>Explanation</b>	This error might occur due to the following reasons: - Users attempt to get credentials when the credentials data store is empty; - While setting credentials, the communication with the remote SPM failed; - While deleting credentials, the communication with the remote SPM failed.
<b>Action</b>	Ensure that: - If you are attempting to get the credentials, the credentials data store is not empty. - If you are setting the credentials, the remote SPM is accessible. - If you are deleting the credentials, the remote SPM is accessible.
<b>CCESREE0001</b>	<b>Specify the private key when certificate is used for authentication.</b>
<b>Explanation</b>	The selected authorization method is "certificate", however, the path to the private key is not specified or is invalid.
<b>Action</b>	Specify a valid path to the private key.
<b>CCETEME0000</b>	<b>A job with ID {0} cannot be found.</b>
<b>Explanation</b>	The job with the specified ID may have completed long before this request.
<b>Action</b>	Use the following URI to list all recently completed or running jobs: /cce/jobmanager/jobs
<b>CCETEME0001</b>	<b>The remote request encountered a concurrency error.</b>
<b>Explanation</b>	The system could not execute parallel remote requests.
<b>Action</b>	Contact Software AG Global Support.
<b>CCETEME0002</b>	<b>A job with ID {0} did not completed successfully in {1} seconds.</b>
<b>Explanation</b>	The job with the specified ID may require more time to complete.
<b>Action</b>	Use the following URI to list all recently completed or running jobs: /cce/jobmanager/jobs

---

<b>CCETEME0003</b>	<b>Template metadata cannot be empty.</b>
<b>Explanation</b>	The template metadata is required for creating a template.
<b>Action</b>	Ensure that you have provided metadata for the template. The metadata.Alias and nodeAlias fields are required.
<b>CCETEME0004</b>	<b>Template alias cannot be empty.</b>
<b>Explanation</b>	The template alias is a required attribute of the template metadata.
<b>Action</b>	Specify a value for the template alias attribute.
<b>CCETEME0005</b>	<b>Template nodeAlias cannot be empty.</b>
<b>Explanation</b>	The template nodeAlias is a required attribute of the template metadata.
<b>Action</b>	Specify a value for the nodeAlias attribute.
<b>CCETEME0006</b>	<b>Template options cannot be empty.</b>
<b>Explanation</b>	The template options attribute is required in the template metadata.
<b>Action</b>	Specify at least one option and retry.
<b>CCETEME0007</b>	<b>Error occurred during template creation {0}</b>
<b>Explanation</b>	Creating the template failed with an error.
<b>Action</b>	Check the error logs for more details.
<b>CCETEME0008</b>	<b>Error occurred during template creation on the remote managed node with alias : {0}. Remote task status is {1}</b>
<b>Explanation</b>	Creating a template on the remote managed node with the specified ID failed with an error.
<b>Action</b>	Check the job status.
<b>CCETEME0009</b>	<b>A template with alias: {0} already exists.</b>
<b>Explanation</b>	Another template with the same alias already exists.
<b>Action</b>	To overwrite the existing template, add the OVERWRITE_TEMPLATE option in the template metadata. To create a new template and keep the existing template, change the template alias.

<b>CCETEME0010</b>	<b>Node with alias : {0} does not exist.</b>
<b>Explanation</b>	A managed installation (node) with the specified alias name does not exist.
<b>Action</b>	Specify a valid alias name for an existing installation (node).
<b>CCETEME0011</b>	<b>A problem occurred while downloading template with alias {0} on Command Central.</b>
<b>Explanation</b>	Command Central could not create a folder for the template on the file system.
<b>Action</b>	Contact the Command Central Administrator.
<b>CCETEME0012</b>	<b>A template with alias {0} could not be found.</b>
<b>Explanation</b>	Command Central could not find a template with the specified alias.
<b>Action</b>	Check if the specified alias for the template you want to delete is correct.
<b>CCETEME0013</b>	<b>Error occurred while creating a template on the remote managed node with alias: {0}. Remote task status is {1}</b>
<b>Explanation</b>	Creating the template fails with a "Nothing to download on Command Central" error.
<b>Action</b>	See the error logs for the error details.
<b>CCETEME0014</b>	<b>Template with alias {0} was not found.</b>
<b>Explanation</b>	Command Central could not find a template with the specified alias.
<b>Action</b>	Verify that the alias is spelt correctly and that a template with this alias is already created. If the template is not created, execute a create template operation.
<b>CCETEME0015</b>	<b>Template already exists.</b>
<b>Explanation</b>	A template with the specified alias already exists.
<b>Action</b>	Change the alias of the imported template or delete the existing template with the same alias.
<b>CCETEME0016</b>	<b>A problem occurred while importing the template.</b>
<b>Explanation</b>	Command Central could not create a folder for the template on the file system.
<b>Action</b>	Contact the Command Central Administrator.

---

<b>CCETEME0017</b>	<b>Could not import template because a required file was not found.</b>
<b>Explanation</b>	Command Central could not find or access the file from which to import the template.
<b>Action</b>	Contact the Command Central Administrator.
<b>CCETEME0018</b>	<b>Template data is invalid.</b>
<b>Explanation</b>	The provided template data could not be deserialised.
<b>Action</b>	Check if the provided template data is corrupted.
<b>CCETEME0019</b>	<b>Template options cannot be empty.</b>
<b>Explanation</b>	The template options attribute is required in the template metadata.
<b>Action</b>	Specify at least one option and retry.
<b>CCETEME0020</b>	<b>The requested service temporarily not available.</b>
<b>Explanation</b>	The requested service temporarily not available. This may be due to Platform Manager (SPM) being in the process of shutting down or still loading at start up.
<b>Action</b>	Ensure that Platform Manager is running and Installation has ONLINE status.
<b>CCETEME0021</b>	<b>The Platform Manager (SPM) is shut down.</b>
<b>Explanation</b>	The Platform Manager (SPM) is shut down.
<b>Action</b>	Ensure that Platform Manager is running and Installation has ONLINE status
<b>CCETEME0022</b>	<b>Template metadata must be specified.</b>
<b>Explanation</b>	Specify metadata for the template.
<b>Action</b>	Check the input parameters.
<b>CCETEME0023</b>	<b>Node Alias must be specified.</b>
<b>Explanation</b>	The template input parameters must include Node Alias.
<b>Action</b>	Check the input parameters.
<b>CCETEME0024</b>	<b>Repository Id must be specified.</b>
<b>Explanation</b>	The template input parameters must include Repository Id.
<b>Action</b>	Check the input parameters.

<b>CCETEME0025</b>	<b>Repository with Id {0} cannot be found.</b>
<b>Explanation</b>	The template input parameters must include Repository Id of existing Repository.
<b>Action</b>	Check the input parameters.
<b>CCETEME0026</b>	<b>Template metadata in {0} cannot be unmarshalled.</b>
<b>Explanation</b>	The file containing the metadata for the template cannot be read.
<b>Action</b>	Make sure the file exists, can be read and contains valid XML.
<b>CCETEME0027</b>	<b>An error occurred while registering Repository {0} on Node {1}. Check the Server logs for details.</b>
<b>Explanation</b>	The issue might occur because of a problem with the Repository contents.
<b>Action</b>	Check the Server logs for details.
<b>CCETEME0028</b>	<b>Unable to obtain snapshot template job group id for node {0}.</b>
<b>Explanation</b>	Command Central was unable to obtain the snapshot template job group id for a node.
<b>Action</b>	Contact Software AG Global Support.
<b>CCETEME0029</b>	<b>Error during checking remote job status.</b>
<b>Explanation</b>	An error occurred while checking the remote job status.
<b>Action</b>	Check if Platform Manager is running.
<b>CCETMRE0000</b>	<b>Specify template alias, options, and target node.</b>
<b>Explanation</b>	Template alias, target node alias, and options are required parameters for this template.
<b>Action</b>	Specify values for all required parameters.
<b>CCETMRE0001</b>	<b>{0} option is specified but a repository for the option is not specified.</b>
<b>Explanation</b>	A repository for the option is not specified.
<b>Action</b>	Specify a repository for the option. For example, if the option is PRODUCTS, specify a product repository.

---

<b>CCETMRE0002</b>	<b>The specified repository is not applicable for this option {0}</b>
<b>Explanation</b>	The specified repository is not applicable for the specified option.
<b>Action</b>	Specify a proper repository. For example, if the option is PRODUCTS, specify a product repository.
<b>CCETMRE0003</b>	<b>There is no repository that supports the specified option {0}.</b>
<b>Explanation</b>	The specified option is not supported by the specified repositories. For example, the error occurs if the FIXES option is specified, but the repository for this option does not support fixes.
<b>Action</b>	Specify a proper repository. For example, if the specified option is FIXES, specify a repository that contains fixes.
<b>CCETMRE0004</b>	<b>No suitable option found for {0}.</b>
<b>Explanation</b>	No matching option found for the specified parameter.
<b>Action</b>	Specify a supported template option.
<b>CCEWCME0009</b>	<b>Display name cannot be empty.</b>
<b>Explanation</b>	Display name is required.
<b>Action</b>	Provide the display name.
<b>CCEWCME0010</b>	<b>Alias {0} cannot be empty.</b>
<b>Explanation</b>	Environment alias and node alias cannot be empty.
<b>Action</b>	Provide a valid alias name.
<b>CCEWCME0011</b>	<b>{0} cannot exceed {1} characters.</b>
<b>Explanation</b>	The specified field input is incorrect.
<b>Action</b>	Check the error message and provide the correct input to the specified field.
<b>CCEWCME0012</b>	<b>Environment name or alias cannot be {0}.</b>
<b>Explanation</b>	Incorrect environment name/alias provided.
<b>Action</b>	Check the error message and provide the correct input.

**CCEWCME0013**     **{0} alias cannot contain {1} non-ASCII characters.**

**Explanation**     Environment alias cannot contain non-ASCII characters.

**Action**            Make sure the value of the alias field is correct.

**CCEWCME0014**     **Alias {0} cannot contain spaces.**

**Explanation**     Environment alias cannot contain spaces.

**Action**            Make sure the value of the alias field is correct.

**CCEWCME0015**     **{0} already exists.**

**Explanation**     The specified node/environment already exists.

**Action**            Specify a correct node/environment.

**CCEWCME0017**     **Installation name cannot be empty. It must be less than 100 characters.**

**Explanation**     Node name cannot be empty or contain more than 100 characters.

**Action**            Enter a valid node name.

**CCEWCME0018**     **Alias cannot be empty. It should be no more than 100 characters long. It should not have spaces. Only ASCII characters, numbers, -, \_ and . are allowed.**

**Explanation**     The node alias cannot be empty. It should be no more than 100 characters long.

**Action**            Enter a valid node alias.

**CCEWCME0019**     **Host name cannot be empty. The host name should be between two and 253 characters characters long. Do not use any special characters, except period(.) and minus(-). Do not start or end the host name with a period(.) or minus(-).**

**Explanation**     The host name field cannot be empty.

**Action**            Provide a valid host name. The host name should be between two and 253 characters characters long. Do not use any special characters, except period(.) and minus(-). Do not start or end the host name with a period(.) or minus(-).

**CCEWCME0020**     **Port number cannot be empty. It must be a positive number.**

**Explanation**     Port number cannot be empty.

**Action**            Enter a valid port number.

---

<b>CCEWCME0028</b>	<b>Installation alias {0} already exists. Please provide a different alias for the installation.</b>
<b>Explanation</b>	Installation node already exists.
<b>Action</b>	Provide a different alias for the installation node you want to add.
<b>CCEWCME0039</b>	<b>Null returned while retrieving the configuration types for comparison.</b>
<b>Explanation</b>	This intermittent error occurs while retrieving the configuration types from Platform Manager.
<b>Action</b>	Retry configuration comparison.
<b>CCEWCME0047</b>	<b>Specify a name for the template. No spaces allowed. Use only ASCII characters, numbers, "-", "_", and "."</b>
<b>Explanation</b>	The alias field for the template cannot be empty.
<b>Action</b>	Provide a valid template alias. No spaces allowed. Use only ASCII characters, numbers, "-", "_", and "."
<b>CCEWCME0048</b>	<b>Shared secret cannot be empty.</b>
<b>Explanation</b>	The template shared secret cannot be empty.
<b>Action</b>	Provide a valid shared secret.
<b>CCEWCME0049</b>	<b>The shared secrets you entered do not match.</b>
<b>Explanation</b>	The shared secrets that you entered do not match.
<b>Action</b>	Re-enter the shared secrets.
<b>CCEWCME0050</b>	<b>Select at least one include option.</b>
<b>Explanation</b>	You cannot clear all include option check boxes.
<b>Action</b>	You must select at least one include option check box.
<b>CCEWCME0051</b>	<b>No license reports were selected for deletion.</b>
<b>Explanation</b>	At least one report must be selected in the view before clicking the delete button.
<b>Action</b>	Select one or more reports and click the delete button.

<b>CCEWCME0053</b>	<b>No repositories configured. Add at least one repository.</b>
<b>Explanation</b>	There are no central repositories configured in Command Central.
<b>Action</b>	Register at least one repository in Command Central.
<b>CCEWCME0069</b>	<b>Specify a name for the repository. No spaces allowed. Use only ASCII characters, numbers, "-", "_", and "."</b>
<b>Explanation</b>	The alias field for the repository cannot be empty.
<b>Action</b>	Provide a valid repository alias. No spaces allowed. Use only ASCII characters, numbers, "-", "_", and "."
<b>CCEWCME0072</b>	<b>Repository {0} creation failed.</b>
<b>Explanation</b>	Creating the repository failed.
<b>Action</b>	Check the server logs or contact your system administrator.
<b>CCEWCME0073</b>	<b>Repository {0} update failed.</b>
<b>Explanation</b>	Updating the specified repository failed.
<b>Action</b>	Check the server logs or contact your system administrator.
<b>CCEWCME0074</b>	<b>Version cannot be empty.</b>
<b>Explanation</b>	The Version field is a required field.
<b>Action</b>	Click the Advanced button and specify a valid server in the Enter server URL field. Leave this field empty to use the Software AG Download Center.
<b>CCEWCME0075</b>	<b>Image file path cannot be empty.</b>
<b>Explanation</b>	The Image file on server field is a required field.
<b>Action</b>	In the Image file on server field, provide a valid path to an image file on the Command Central server.
<b>CCEWCME0076</b>	<b>An image file should be selected.</b>
<b>Explanation</b>	Specifying an image file is required.
<b>Action</b>	In the Upload image file field, select an image file.

---

<b>CCEWCME0077</b>	<b>A repository with location {0} was not found in the Software AG Download Center.</b>
<b>Explanation</b>	The repository that you are trying to edit was not found in the Software AG Download Center.
<b>Action</b>	Contact your system administrator.
<b>CCEWCME0099</b>	<b>Applying template {0} on installation {1} failed.</b>
<b>Explanation</b>	The apply template operation on the target installation has failed.
<b>Action</b>	Check the logs and jobs on the target installation.
<b>CCEWCME0103</b>	<b>Error while creating a new license report. {0}</b>
<b>Explanation</b>	An error occurred while invoking the service action responsible for creating a new report.
<b>Action</b>	Check the Command Central server logs to determine the root cause for the error.
<b>CCEWCME0104</b>	<b>Error while deleting license report(s). {0}</b>
<b>Explanation</b>	An error occurred while invoking the service action responsible for deleting reports.
<b>Action</b>	Check the Command Central server logs to determine the root cause for the error.
<b>CCEWCME0105</b>	<b>Error while refreshing the license reports view. {0}</b>
<b>Explanation</b>	An error occurred while invoking the service action responsible for retrieving the reports from the Command Central server.
<b>Action</b>	Check the Command Central server logs to determine the root cause for the error.
<b>CCEWCME0114</b>	<b>Saving of template {0} from installation {1} failed.</b>
<b>Explanation</b>	The save template operation on the target installation has failed.
<b>Action</b>	Check the logs and jobs on the target installation.
<b>CCEWCME0119</b>	<b>You do not have enough access privileges to perform requested operation.</b>
<b>Explanation</b>	You do not have enough access privileges to perform requested operation.
<b>Action</b>	Contact your system administrator to help you get the required permissions.

<b>CCEWCME0124</b>	<b>Bootstrapping of Platform Manager on installation with alias {0} failed.</b>
<b>Explanation</b>	The bootstrap Platform Manager operation on the target installation has failed.
<b>Action</b>	Check the logs and jobs on Command Central.
<b>CCEWCME0125</b>	<b>Alias {0} already exists. Provide a unique alias.</b>
<b>Explanation</b>	Alias already exists.
<b>Action</b>	Provide a unique alias for the object you want to add.
<b>CCEWCME0126</b>	<b>Alias cannot be empty. It should not have spaces. Only ASCII characters, numbers, -, _ and . are allowed.</b>
<b>Explanation</b>	Alias cannot be empty.
<b>Action</b>	Enter a valid alias.
<b>CCEWCME0127</b>	<b>No file specified.</b>
<b>Explanation</b>	A valid file must be specified.
<b>Action</b>	Press the 'Browse' button and select a valid file.
<b>CCEWCME0129</b>	<b>Error while deleting license manifest(s). {0}</b>
<b>Explanation</b>	An error occurred while invoking the service action responsible for deleting license manifests.
<b>Action</b>	Check the Command Central server logs to determine the root cause for the error.
<b>CCEWCME0130</b>	<b>Error while refreshing the license manifests view. {0}</b>
<b>Explanation</b>	An error occurred while invoking the service action responsible for retrieving the license manifests from the Command Central server.
<b>Action</b>	Check the Command Central server logs to determine the root cause for the error.
<b>CCEWCME0132</b>	<b>No license manifests were selected for deletion.</b>
<b>Explanation</b>	At least one license manifest must be selected in the view before clicking the delete button.
<b>Action</b>	Select one or more license manifests and click the delete button.

---

<b>CCEWCME0135</b>	<b>The contents of the specified file has invalid format.</b>
<b>Explanation</b>	The contents of the specified file does not match the required format.
<b>Action</b>	Specify a file with valid format.
<b>CCEWCME0136</b>	<b>Select remote installation method.</b>
<b>Explanation</b>	A remote installation method is not selected in the web user interface.
<b>Action</b>	Select a remote installation method in the web user interface.
<b>CCEWCME0137</b>	<b>Distribution cannot be empty.</b>
<b>Explanation</b>	The Distribution field in the web user interface cannot be empty.
<b>Action</b>	Select a distribution in the Distribution field.
<b>CCEWCME0138</b>	<b>Repository cannot be empty.</b>
<b>Explanation</b>	The Repository field in the web user interface cannot be empty.
<b>Action</b>	Select a repository in the Repository field.
<b>CCEWCME0140</b>	<b>Installation directory cannot be empty.</b>
<b>Explanation</b>	The Installation directory field in the web user interface cannot be empty.
<b>Action</b>	Select an installation directory in the Installation directory field.
<b>CCEWCME0141</b>	<b>Operating System cannot be empty.</b>
<b>Explanation</b>	The Operating System field in the web user interface cannot be empty.
<b>Action</b>	Select an operating System in the Operating System field.
<b>CCEWCME0142</b>	<b>Bootstrapped node {0} startup timed out.</b>
<b>Explanation</b>	The status of the bootstrapped node is still OFFLINE after the required timeout.
<b>Action</b>	Check the Command Central bootstrap logs.
<b>CCEWCME0143</b>	<b>Bootstrap installer creation failed.</b>
<b>Explanation</b>	Bootstrap installer creation failed.
<b>Action</b>	Check the Command Central logs.

- CCEWCME0145**     **User name cannot be empty.**  
**Explanation**     The user name field cannot be empty.  
**Action**             Provide a value in the user name field.
- CCEWCME0146**     **Password cannot be empty for the selected authentication method.**  
**Explanation**     The Password cannot be empty for the selected authentication method.  
**Action**             Provide a value in the Password field for the selected authentication method.
- CCEWCME0147**     **Key file cannot be empty for the selected authentication method.**  
**Explanation**     The Key file field cannot be empty for the selected authentication method.  
**Action**             Provide a value in the Key file field for the selected authentication method.
- CCEWCME0148**     **Password cannot be empty.**  
**Explanation**     The Password field cannot be empty.  
**Action**             Provide a value in the Password field.
- CCEWCME0149**     **User name cannot be empty.**  
**Explanation**     The user name cannot be empty.  
**Action**             Provide a value in the user name field.
- CCEWCME0151**     **Navigation to the log(s) for node {0} can not be initiated.**  
**Explanation**     A node with alias {0} does not exist in the Command Central landscape.  
**Action**             Select an existing node different than {0}.
- CCEWCME0152**     **You do not have access to the requested operation(s).**  
**Explanation**     You do not have access to the requested operation(s).  
**Action**             Provide valid credentials to perform the requested operation(s).
- CCEWCME0154**     **Request to create a license report failed.**  
**Explanation**     An error occurred during the creation of the license report.  
**Action**             Contact Software AG Global Support.

---

<b>CCEWCME0155</b>	<b>Select fixes to be installed.</b>
<b>Explanation</b>	No fixes are selected for installation.
<b>Action</b>	Select at least one fix to be installed.
<b>CCEWCME0156</b>	<b>Duplicate fixes selected. Select only one of the fix versions to be installed.</b>
<b>Explanation</b>	Duplicate fixes with the same ID, but different versions were selected.
<b>Action</b>	Select only one of the possible versions.
<b>CCEWCME0157</b>	<b>The key should not be empty.</b>
<b>Explanation</b>	The Support Patch key should not be empty.
<b>Action</b>	Provide a Support Patch key.
<b>CCEWCME0158</b>	<b>The Platform Manager (SPM) on this installation is not online.</b>
<b>Explanation</b>	The selected fix and product installation functions are not supported when Platform Manager is not running.
<b>Action</b>	Start Platform Manager and try again.
<b>CCEWCME0159</b>	<b>Release 9.7 and higher supports fix installation.</b>
<b>Explanation</b>	Fix installation is supported for installations of release 9.7 and higher. See the actions suggested for your installation in the Action field.
<b>Action</b>	Use Software AG Update Manager to install fixes and support patches for this installation. Consider upgrading this installation to 9.10 or a later release, using Command Central.
<b>CCEWCME0162</b>	<b>This installation version ({0}) does not support this feature.</b>
<b>Explanation</b>	The selective fix uninstallation feature is supported beginning with Platform Manager 9.7.
<b>Action</b>	If it is not possible to upgrade the installation to the latest available release version, you should use Update Manager to uninstall fixes.
<b>CCEWCME0163</b>	<b>Select a support patch to be installed.</b>
<b>Explanation</b>	There is no support patch selected for installation.
<b>Action</b>	Select a support patch to install.

<b>CCEWCME0166</b>	<b>Select at least one source repository.</b>
<b>Explanation</b>	You must select at least one source repository from which to create a mirror repository.
<b>Action</b>	Select at least one source repository from which to create a mirror repository.
<b>CCEWCME0167</b>	<b>The provided configuration is not valid.</b>
<b>Explanation</b>	The server request can not be completed successfully.
<b>Action</b>	Expand this view for more details.
<b>CCEWCME0168</b>	<b>No license keys were selected for deletion.</b>
<b>Explanation</b>	You must select at least one license key in the view before clicking the delete button.
<b>Action</b>	Select one or more license keys and click the delete button.
<b>CCEWCME0171</b>	<b>Error while refreshing the license keys view. {0}</b>
<b>Explanation</b>	An error occurred while invoking the service action responsible for retrieving the license keys from the Command Central server.
<b>Action</b>	Check the Command Central server logs to determine the root cause for the error.
<b>CCEWCME0174</b>	<b>Adding/Updating a repository operation failed.</b>
<b>Explanation</b>	Adding a repository operation failed. The job status is Error.
<b>Action</b>	Check the logs and try again.
<b>CCEWCME0175</b>	<b>Error while deleting license key(s). {0}</b>
<b>Explanation</b>	An error occurred while invoking the service action responsible for deleting license keys.
<b>Action</b>	Check the Command Central server logs to determine the root cause for the error.
<b>CCEWCME0183</b>	<b>Invalid username or password.</b>
<b>Explanation</b>	Invalid username or credentials provided in the Command Central Login page.
<b>Action</b>	Provide valid username or credentials in the Command Central Login page.
<b>CCEWCME0184</b>	<b>To mirror from a MASTER repository, you need at least one product repository that will be used as a filter for the repository content.</b>
<b>Explanation</b>	To mirror from a MASTER repository, you need at least one product repository that will be used as a filter for the repository content.
<b>Action</b>	Select at least one product repository.

---

<b>CCEWCME0185</b>	<b>Specify a name that follows the webMethods-&lt;major.version&gt;.&lt;minor.version&gt;_&lt;name&gt; pattern.</b>
<b>Explanation</b>	The pattern allows to extract the version when constructing a bootstrap image for ALL SPM distribution.
<b>Action</b>	Name your product mirror repository after the pattern.
<b>CCEWCME0188</b>	<b>Insufficient permissions to access this resource.</b>
<b>Explanation</b>	You do not have sufficient permissions to access this resource.
<b>Action</b>	Contact your system administrator to get sufficient permissions.
<b>CCEWCME0209</b>	<b>Release 9.8 and higher supports product installation.</b>
<b>Explanation</b>	Product installation is supported for installations of release 9.8 and higher. See the actions suggested for your installation in the Action field.
<b>Action</b>	Use Software AG Installer to install products for this installation. Consider upgrading this installation to 9.10 or a later release, using Command Central.
<b>CCEWCME0210</b>	<b>Release 9.8 and higher supports support patch installation.</b>
<b>Explanation</b>	Support patch installation is supported for installations of release 9.8 and higher. See the actions suggested for your installation in the Action field.
<b>Action</b>	Use Software AG Update Manager to install support patches for this installation. Consider upgrading this installation to 9.10 or a later release, using Command Central.
<b>CCEWCME0214</b>	<b>Enter your user name for the Software AG Download Center.</b>
<b>Explanation</b>	The user name field cannot be empty.
<b>Action</b>	Enter a valid user name for the Software AG Download Center.
<b>CCEWCME0215</b>	<b>Enter your password for the Software AG Download Center.</b>
<b>Explanation</b>	The password field cannot be empty.
<b>Action</b>	Enter a valid password for the Software AG Download Center.
<b>CCEWCME0216</b>	<b>Enter your user name for the remote Platform Manager.</b>
<b>Explanation</b>	The user name field cannot be empty.
<b>Action</b>	Enter a valid user name for the Platform Manager, which is specified in the repository URL.

<b>CCEWCME0217</b>	<b>Enter your password for the remote Platform Manager.</b>
<b>Explanation</b>	The password field cannot be empty.
<b>Action</b>	Enter a valid password for the Platform Manager, which is specified in the repository URL.
<b>CCEWCME0220</b>	<b>Updating repository contents operation failed.</b>
<b>Explanation</b>	The repository update contents operation failed. The job status is Error.
<b>Action</b>	Check the logs and try again.
<b>CCEWCME0223</b>	<b>Could not transfer the file to the target destination {0}.</b>
<b>Explanation</b>	The file could not be transferred because of an error.
<b>Action</b>	Check if the target host has enough disk space or the specified file name is valid.
<b>CCEWCME0228</b>	<b>You are not allowed to perform the requested operation.</b>
<b>Explanation</b>	You are not allowed to perform the requested operation because of Cross Site Request Prevention.
<b>Action</b>	Ensure that you do not have several Command Central REST resources open in the same browser session. If you do, close all the instances of the browser and log into the Command Central web user interface again.
<b>CCEWCME0239</b>	<b>Source repositories with different versions are selected: {0}.</b>
<b>Explanation</b>	The selected source repositories have different versions.
<b>Action</b>	Select source repositories with the same version.
<b>CCEWCME0240</b>	<b>Connecting to asset repository {0} failed.</b>
<b>Explanation</b>	Connecting to an asset repository failed.
<b>Action</b>	Check the logs and try again.
<b>CCEWCME0243</b>	<b>Asset repository {0} could not be connected/edited.</b>
<b>CCEWCMI0021</b>	<b>Installation {0} already exists in environment {1}.</b>
<b>Explanation</b>	The selected node already exists in the environment. Drag and drop not possible.
<b>Action</b>	Verify if you have selected the correct nodes and the environment for drag and drop.

---

<b>CCEWCMI0040</b>	<b>{0} must be a non-negative integer.</b>
<b>Explanation</b>	Specified field must be a non-negative integer.
<b>Action</b>	Enter a valid field value.
<b>CCEWCMI0041</b>	<b>{0} cannot be empty.</b>
<b>Explanation</b>	Specified field cannot be empty.
<b>Action</b>	Enter a valid field value.
<b>CCEWCMI0046</b>	<b>Alias cannot be empty.</b>
<b>Explanation</b>	The port alias field cannot be empty.
<b>Action</b>	Provide a valid port alias name.
<b>CCEWCMI0057</b>	<b>User credentials saved successfully.</b>
<b>Explanation</b>	The provided user credentials are successfully saved.
<b>Action</b>	None.
<b>CCEWCMI0058</b>	<b>User credentials deleted successfully.</b>
<b>Explanation</b>	The provided user credentials are successfully deleted.
<b>Action</b>	None.
<b>CCEWCMI0098</b>	<b>Template {0} successfully saved from installation {1}.</b>
<b>Explanation</b>	The save template operation completed successfully.
<b>Action</b>	No action required.
<b>CCEWCMI0100</b>	<b>Type a keyword to display only the reports that contain the keyword in the report id, creator, create date or compliance status. The search is case-insensitive.</b>
<b>Explanation</b>	License report search filter help text.
<b>Action</b>	None.
<b>CCEWCMI0101</b>	<b>Do you wish to continue?</b>
<b>Explanation</b>	Part of the license report confirmation dialog for creating a new report.
<b>Action</b>	None.

<b>CCEWCMI0110</b>	<b>It may take a few moments to generate the report.</b>
<b>Explanation</b>	Part of the license report confirmation dialog for creating a new report.
<b>Action</b>	None.
<b>CCEWCMI0112</b>	<b>license report(s)</b>
<b>Explanation</b>	Part of 'delete license report(s)' confirmation dialog.
<b>Action</b>	None.
<b>CCEWCMI0113</b>	<b>Report Id(s): {0}</b>
<b>Explanation</b>	License report confirmation dialog for deleting one or more reports.
<b>Action</b>	None.
<b>CCEWCMI0115</b>	<b>Template {0} successfully applied on installation {1}.</b>
<b>Explanation</b>	The apply template operation completed successfully.
<b>Action</b>	No action required.
<b>CCEWCMI0117</b>	<b>Scheduled job did not complete within status checker's allotted time.</b>
<b>Explanation</b>	The client job status checker stopped polling for an executing job's status before it completed. This does not necessarily mean the job did not complete successfully.
<b>Action</b>	Confirm if job completed via other means.
<b>CCEWCMI0120</b>	<b>Attribute {0} successfully submitted.</b>
<b>Explanation</b>	The attribute was successfully added or updated.
<b>Action</b>	No action required.
<b>CCEWCMI0121</b>	<b>Attribute {0} successfully deleted.</b>
<b>Explanation</b>	The attribute was successfully deleted.
<b>Action</b>	No action required.
<b>CCEWCMI0123</b>	<b>Platform Manager successfully bootstrapped on installation with alias {0}.</b>
<b>Explanation</b>	The bootstrap of Platform Manager was successful.
<b>Action</b>	No action required.

---

<b>CCEWCMI0131</b>	<b>Type a keyword to display only the license manifests that contain the keyword in one of the columns. The search is case-insensitive.</b>
<b>Explanation</b>	License manifest search filter help text.
<b>Action</b>	None.
<b>CCEWCMI0144</b>	<b>Bootstrap installer created successfully.</b>
<b>Explanation</b>	A new bootstrap installer was successfully created.
<b>Action</b>	None.
<b>CCEWCMI0180</b>	<b>No licenses have been registered</b>
<b>Explanation</b>	No license key aliases have been registered so that it is not possible to select a license key alias.
<b>Action</b>	Register a license key alias.
<b>CCEWCMI0186</b>	<b>Provided configuration is valid.</b>
<b>Explanation</b>	The server request is completed successfully.
<b>Action</b>	Expand this view for more details.
<b>CCEWCMW0107</b>	<b>No data selected for delete.</b>
<b>Explanation</b>	You must select at least one object for deletion.
<b>Action</b>	Select at least one object from the object list.
<b>CCEWCMW0108</b>	<b>Delete request failed, but no ErrorInfo was found.</b>
<b>Explanation</b>	A problem occurred when executing a delete request, but the server did not provide details about the problem.
<b>Action</b>	Check the server-side log files for details. Contact Software AG Global Support.
<b>CCEWCMW0109</b>	<b>Request to delete license reports failed for these report IDs: {0}</b>
<b>Explanation</b>	The server was not able to delete the license reports identified here. The request may have included other report IDs for which deletion was successful.
<b>Action</b>	Refresh the display of license reports to see which were deleted. Check the server-side error log for details about why the attempt to delete failed.

**CCEWCMW0118**    **Unable to determine job status due to unexpected error while checking status. {0}**

**Explanation**    Job status checking encountered an error. This does not necessarily mean the job did not complete successfully.

**Action**    Confirm if job completed via other means.

**CCEWCMW0122**    **The provided attribute name {0} already exists.**

**Explanation**    The attribute name which you are trying to add already exists.

**Action**    Provide a unique attribute name.

**CCEWCMW0172**    **Delete request failed for this alias: {0}**

**Explanation**    The server was not able to delete the object with the given alias.

**Action**    Check the server-side error log for details about why the attempt to delete failed.

**CCEWCMW0187**    **Provided configuration is valid, but check the warnings.**

**Explanation**    The server request is completed, but check the warnings.

**Action**    Expand this view for more details.

**CCEWCMW0211**    **Not all products can be installed by Command Central.**

**Explanation**    The number of products that you can install using Command Central increases with each Software AG release.

**Action**    See the Command Central release readme for a list of products that you cannot install through Command Central for each Software AG release.

**CCEWCMW0212**    **There are artifacts which are either not applicable for the installation or not present in the selected repository.**

**Explanation**    The following artifacts are either not applicable, or not present in the selected repository: {0}

**Action**    Either continue without the missing artifacts, or use a source repository containing those artifacts.

**CCEWCMW0222**    **User credentials for repository {0} are missing or invalid.**

**Explanation**    The user credentials for repository {0} are missing or invalid.

**Action**    Specify valid user credentials for repository {0}.

# 9

## Common Monitoring Provider Messages

---

<b>CMPAPIE0000</b>	<b>{0}: The input parameter {1} is null or empty.</b>
<b>Explanation</b>	A required input parameter is null or empty.
<b>Action</b>	Please provide the required input parameter.
<b>CMPAPIE0001</b>	<b>{0}: The input parameter {1} is null.</b>
<b>Explanation</b>	A required input parameter is null.
<b>Action</b>	Please provide the required input parameter.
<b>CMPAPIE0003</b>	<b>{0}: Cannot load XSD file {1}</b>
<b>Explanation</b>	A required input parameter is null.
<b>Action</b>	Please provide the required input parameter.
<b>CMPBKRE0000</b>	<b>Error initializing Broker Attribute Values. Broker Monitoring Context cannot be null.</b>
<b>Explanation</b>	Broker Monitoring Context is required for initializing Broker Attribute Values.
<b>Action</b>	Verify Broker Connection parameters.
<b>CMPBKRE0001</b>	<b>Error while retrieving attribute value. MetaModel Type Name cannot be null or empty.</b>
<b>Explanation</b>	MetaModel Type Name is required for retrieving attribute value.
<b>Action</b>	Verify metadata model type name is provided.

<b>CMPBKRE0002</b>	<b>Error while retrieving attribute value. MetaModel instance name cannot be null or empty.</b>
<b>Explanation</b>	MetaModel instance name is required to retrieve attribute value.
<b>Action</b>	Verify metadata model instance name is provided.
<b>CMPBKRE0003</b>	<b>Error while retrieving attribute value. Attribute ID cannot be null or empty.</b>
<b>Explanation</b>	Attribute ID is required to retrieve attribute value.
<b>Action</b>	Verify Attribute ID is provided.
<b>CMPBKRE0004</b>	<b>Error while retrieving attribute values. Attribute query object cannot be null.</b>
<b>Explanation</b>	Attribute query object is required to retrieve attribute values.
<b>Action</b>	Verify attribute query object is provided.
<b>CMPBKRE0005</b>	<b>Error while retrieving attribute value due to invalid model type.</b>
<b>Explanation</b>	An invalid model type was provided while retrieving attribute values.
<b>Action</b>	Verify a valid model type is provided.
<b>CMPBKRE0006</b>	<b>Error while destroying Monitoring Context. Monitoring Context cannot be null.</b>
<b>Explanation</b>	Error while destroying Monitoring Context. Monitoring Context cannot be null.
<b>Action</b>	Verify Monitoring Context is provided
<b>CMPBKRE0007</b>	<b>Error while destroying Monitoring Context. Invalid Broker Monitoring Context provided.</b>
<b>Explanation</b>	Error while destroying Monitoring Context. Invalid Broker Monitoring Context provided.
<b>Action</b>	Verify valid Broker Monitoring Context is provided.
<b>CMPBKRE0008</b>	<b>Error while getting meta model. Model type name cannot be null.</b>
<b>Explanation</b>	Error while getting meta model. Model type name cannot be null.
<b>Action</b>	Verify Model type name is provided.

---

<b>CMPBKRE0009</b>	<b>Error while validating Broker Monitoring Context. Broker Monitoring Context cannot be null.</b>
<b>Explanation</b>	Error while validating Broker Monitoring Context. Broker Monitoring Context cannot be null.
<b>Action</b>	Verify Broker Monitoring Context is provided.
<b>CMPBKRE0010</b>	<b>Error while validating Broker Monitoring Context. Invalid Broker Monitoring Context provided.</b>
<b>Explanation</b>	Error while validating Broker Monitoring Context. Invalid Broker Monitoring Context provided.
<b>Action</b>	Verify a valid Broker Monitoring Context is provided.
<b>CMPBKRE0011</b>	<b>Error while validating Broker Monitoring Context. Context object is null.</b>
<b>Explanation</b>	Error while validating Broker Monitoring Context. Context object is null.
<b>Action</b>	Verify Broker Monitoring Context is provided.
<b>CMPBKRE0012</b>	<b>Error while validating Broker Monitoring Context. Context is invalid.</b>
<b>Explanation</b>	Error while validating Broker Monitoring Context. Context is invalid.
<b>Action</b>	Verify valid Broker Monitoring Context is provided.
<b>CMPBKRE0013</b>	<b>Error while validating Broker Monitoring Context. Context host attribute cannot be null or empty.</b>
<b>Explanation</b>	Error while validating Broker Monitoring Context. Context host attribute cannot be null or empty.
<b>Action</b>	Verify host attribute is provided in Broker Monitoring Context
<b>CMPBKRE0014</b>	<b>Error while validating Broker Monitoring Context. Context port attribute is invalid.</b>
<b>Explanation</b>	Error while validating Broker Monitoring Context. Context port attribute is invalid.
<b>Action</b>	Verify valid port attribute is provided in Broker Monitoring Context.
<b>CMPBKRE0015</b>	<b>Error while creating Broker Server client. Host name cannot be null or empty.</b>
<b>Explanation</b>	Error while creating Broker Server client. Host name cannot be null or empty.
<b>Action</b>	Verify host name is provided.

<b>CMPBKRE0016</b>	<b>Error while creating Broker Server client. Port cannot be null or empty.</b>
<b>Explanation</b>	Error while creating Broker Server client. Port cannot be null or empty.
<b>Action</b>	Verify port is provided.
<b>CMPBKRE0017</b>	<b>Error while destroying Broker Server client. Broker Name cannot be null or empty.</b>
<b>Explanation</b>	Error while destroying Broker Server client. Broker Name cannot be null or empty.
<b>Action</b>	Verify Broker Name is provided.
<b>CMPBKRE0018</b>	<b>Error while creating Broker Admin client. Broker Name cannot be null.</b>
<b>Explanation</b>	Error while creating Broker Admin client. Broker Name cannot be null.
<b>Action</b>	Verify Broker Name is provided.
<b>CMPBKRE0019</b>	<b>Error while setting Broker Admin client. Broker Name cannot be null.</b>
<b>Explanation</b>	Error while setting Broker Admin client. Broker Name cannot be null.
<b>Action</b>	Verify Broker Name is provided.
<b>CMPBKRE0020</b>	<b>Error while setting Broker Admin client. Broker Admin Client cannot be null.</b>
<b>Explanation</b>	Error while setting Broker Admin client. Broker Admin Client cannot be null.
<b>Action</b>	Verify Broker Admin Client is specified.
<b>CMPBKRE0021</b>	<b>Error while initializing Broker Client model. Broker Monitoring Context is null.</b>
<b>Explanation</b>	Error while initializing Broker Client model. Broker Monitoring Context is null.
<b>Action</b>	Verify Broker Monitoring Context is provided.
<b>CMPBKRE0022</b>	<b>Error while getting Broker Client attributes. Model Instance List cannot be null.</b>
<b>Explanation</b>	Error while getting Broker Client attributes. Model Instance List cannot be null.
<b>Action</b>	Verify Model Instance List is provided.
<b>CMPBKRE0023</b>	<b>Error while getting Broker Client attributes. Attribute List cannot be null.</b>
<b>Explanation</b>	Error while getting Broker Client attributes. Attribute List cannot be null.
<b>Action</b>	Verify Attribute List is provided.

---

<b>CMPBKRE0024</b>	<b>Error while getting Broker Client attribute. Attribute ID cannot be null.</b>
<b>Explanation</b>	Error while getting Broker Client attribute. Attribute ID cannot be null.
<b>Action</b>	Verify Attribute ID is provided.
<b>CMPBKRE0025</b>	<b>Error while initializing Broker Document Type model. Broker Monitoring Context is null.</b>
<b>Explanation</b>	Error while initializing Broker Document Type model. Broker Monitoring Context is null.
<b>Action</b>	Verify Broker Monitoring Context is provided.
<b>CMPBKRE0026</b>	<b>Error while getting Broker Document Type attributes. Model Instance List cannot be null.</b>
<b>Explanation</b>	Error while getting Broker Document Type attributes. Model Instance List cannot be null.
<b>Action</b>	Verify Model Instance List is provided.
<b>CMPBKRE0027</b>	<b>Error while getting Broker Document Type attributes. Attribute List cannot be null.</b>
<b>Explanation</b>	Error while getting Broker Document Type attributes. Attribute List cannot be null.
<b>Action</b>	Verify Attribute List is provided.
<b>CMPBKRE0028</b>	<b>Error while getting Broker Document Type attribute. Attribute ID cannot be null.</b>
<b>Explanation</b>	Error while getting Broker Document Type attribute. Attribute ID cannot be null.
<b>Action</b>	Verify Attribute ID is provided.
<b>CMPBKRE0029</b>	<b>Error while initializing Broker Gateway model. Broker Monitoring Context is null.</b>
<b>Explanation</b>	Error while initializing Broker Gateway model. Broker Monitoring Context is null.
<b>Action</b>	Verify Broker Monitoring Context is provided.
<b>CMPBKRE0030</b>	<b>Error while initializing Broker Gateway model. Broker Monitoring Context is null.</b>
<b>Explanation</b>	Error while initializing Broker Gateway model. Broker Monitoring Context is null.
<b>Action</b>	Verify Broker Monitoring Context is provided.

<b>CMPBKRE0031</b>	<b>Error while getting Broker Gateway attributes. Model Instance List cannot be null.</b>
<b>Explanation</b>	Error while getting Broker Gateway attributes. Model Instance List cannot be null.
<b>Action</b>	Verify Model Instance List is provided.
<b>CMPBKRE0032</b>	<b>Error while getting Broker Gateway attributes. Attribute List cannot be null.</b>
<b>Explanation</b>	Error while getting Broker Gateway attributes. Attribute List cannot be null.
<b>Action</b>	Verify Attribute List is provided.
<b>CMPBKRE0033</b>	<b>Error while getting Broker Gateway attribute. Attribute ID cannot be null.</b>
<b>Explanation</b>	Error while getting Broker Gateway attribute. Attribute ID cannot be null.
<b>Action</b>	Verify Attribute ID is provided.
<b>CMPBKRE0034</b>	<b>Error while initializing Broker model. Broker Monitoring Context is null.</b>
<b>Explanation</b>	Error while initializing Broker model. Broker Monitoring Context is null.
<b>Action</b>	Verify Broker Monitoring Context is provided.
<b>CMPBKRE0035</b>	<b>Error while getting Broker attributes. Model Instance List cannot be null.</b>
<b>Explanation</b>	Error while getting Broker attributes. Model Instance List cannot be null.
<b>Action</b>	Verify Model Instance List is provided.
<b>CMPBKRE0036</b>	<b>Error while getting Broker attributes. Attribute List cannot be null.</b>
<b>Explanation</b>	Error while getting Broker attributes. Attribute List cannot be null.
<b>Action</b>	Verify Attribute List is provided.
<b>CMPBKRE0037</b>	<b>Error while getting Broker attribute. Attribute ID cannot be null.</b>
<b>Explanation</b>	Error while getting Broker attribute. Attribute ID cannot be null.
<b>Action</b>	Verify Attribute ID is provided.
<b>CMPBKRE0038</b>	<b>Error while initializing Broker model instance. Broker Monitoring Context is null.</b>
<b>Explanation</b>	Error while initializing Broker model instance. Broker Monitoring Context is null.
<b>Action</b>	Verify Broker Monitoring Context is provided.

---

<b>CMPBKRE0039</b>	<b>Error while getting model instances. MetaModel Type name is null or empty.</b>
<b>Explanation</b>	Error while getting model instances. MetaModel Type name is null or empty.
<b>Action</b>	Verify MetaModel Type Name is provided.
<b>CMPBKRE0040</b>	<b>Error while getting model instances. Invalid MetaModel Type Name.</b>
<b>Explanation</b>	Error while getting model instances. Invalid MetaModel Type Name.
<b>Action</b>	Verify valid MetaModel Type Name is provided.
<b>CMPBKRE0041</b>	<b>Error while initializing Broker Server model. Broker Monitoring Context is null.</b>
<b>Explanation</b>	Error while initializing Broker Server model. Broker Monitoring Context is null.
<b>Action</b>	Verify Broker Monitoring Context is provided.
<b>CMPBKRE0042</b>	<b>Error while getting Broker Server attributes. Model Instance List cannot be null.</b>
<b>Explanation</b>	Error while getting Broker Server attributes. Model Instance List cannot be null.
<b>Action</b>	Verify Model Instance List is provided.
<b>CMPBKRE0043</b>	<b>Error while getting Broker Server attributes. Attribute List cannot be null.</b>
<b>Explanation</b>	Error while getting Broker Server attributes. Attribute List cannot be null.
<b>Action</b>	Verify Attribute List is provided.
<b>CMPBKRE0044</b>	<b>Error while getting Broker Server attribute. Attribute ID cannot be null.</b>
<b>Explanation</b>	Error while getting Broker Server attribute. Attribute ID cannot be null.
<b>Action</b>	Verify Attribute ID is provided.
<b>CMPBKRE0045</b>	<b>Error while getting Broker SSL Stats attributes. Attribute ID cannot be null.</b>
<b>Explanation</b>	Error while getting Broker SSL Stats attributes. Attribute ID cannot be null.
<b>Action</b>	Verify valid Attribute ID is provided.
<b>CMPBKRE0046</b>	<b>Error while initializing Broker Territory model. Broker Monitoring Context is null.</b>
<b>Explanation</b>	Error while initializing Broker Territory model. Broker Monitoring Context is null.
<b>Action</b>	Verify Broker Monitoring Context is provided.

**CMPBKRE0047**      **Error while getting Broker Territory attributes. Model Instance List cannot be null.**  
**Explanation**      Error while getting Broker Territory attributes. Model Instance List cannot be null.  
**Action**              Verify Model Instance List is provided.

**CMPBKRE0048**      **Error while getting Broker Territory attributes. Attribute List cannot be null.**  
**Explanation**      Error while getting Broker Territory attributes. Attribute List cannot be null.  
**Action**              Verify Attribute List is provided.

**CMPBKRE0049**      **Error while getting Broker Territory attribute. Attribute ID cannot be null.**  
**Explanation**      Error while getting Broker Territory attribute. Attribute ID cannot be null.  
**Action**              Verify Attribute ID is provided.

**CMPBKRE0050**      **Error while initializing Territory Broker model. Broker Monitoring Context is null.**  
**Explanation**      Error while initializing Territory Broker model. Broker Monitoring Context is null.  
**Action**              Verify Broker Monitoring Context is provided.

**CMPBKRE0051**      **Error while getting Territory Broker attributes. Model Instance List cannot be null.**  
**Explanation**      Error while getting Territory Broker attributes. Model Instance List cannot be null.  
**Action**              Verify Model Instance List is provided.

**CMPBKRE0052**      **Error while getting Territory Broker attributes. Attribute List cannot be null.**  
**Explanation**      Error while getting Territory Broker attributes. Attribute List cannot be null.  
**Action**              Verify Attribute List is provided.

**CMPBKRE0053**      **Error while getting Territory Broker attribute. Attribute ID cannot be null.**  
**Explanation**      Error while getting Territory Broker attribute. Attribute ID cannot be null.  
**Action**              Verify Attribute ID is provided.

**CMPBKRE0054**      **Error while getting Territory Broker Stats attribute. Could not retrieve attribute value.**  
**Explanation**      Error while getting Territory Broker Stats attribute. Could not retrieve attribute value.

---

<b>CMPBKRE0055</b>	<b>Error while getting Territory Broker Stats Event attribute. Could not retrieve attribute value.</b>
<b>Explanation</b>	Error while getting Territory Broker Stats Event attribute. Could not retrieve attribute value.
<b>CMPBKRE0056</b>	<b>Error during Broker ping. Invalid Ping Context.</b>
<b>Explanation</b>	Error during Broker ping. Invalid Ping Context.
<b>Action</b>	Verify valid Ping Context is provided.
<b>CMPBKRE0057</b>	<b>Error during Broker Client ping. Broker Name not set in Broker Monitoring Context.</b>
<b>Explanation</b>	Error during Broker Client ping. Broker Name not set in Broker Monitoring Context.
<b>Action</b>	Verify Broker Name is set in Broker Ping Context.
<b>CMPDESE0001</b>	<b>Error while validating DES Monitoring Context. DES Monitoring Context cannot be null.</b>
<b>CMPDESE0002</b>	<b>Error while validating DES Monitoring Context. DES Monitoring Context is not instance of DESMonitoringContext.</b>
<b>CMPDESE0003</b>	<b>Error while validating DES Monitoring Context. Context object is null.</b>
<b>CMPDESE0004</b>	<b>Error while validating DES Monitoring Context. Context is invalid.</b>
<b>CMPDESE0005</b>	<b>Error while validating DES Monitoring Context. Context host attribute cannot be null or empty.</b>
<b>CMPDESE0006</b>	<b>Error while validating DES Monitoring Context. Context port attribute is invalid.</b>
<b>CMPDESE0007</b>	<b>DES Monitoring Context cannot be null.</b>
<b>CMPDESE0008</b>	<b>Error while getting meta model. DES Meta model type ID cannot be null or empty.</b>

- CMPDESE0010**      **Input parameter mbean name cannot be null.**
  
- CMPDESE0012**      **Model instance list or attribute list cannot be null.**
  
- CMPDESE0034**      **Input parameter mbean name cannot be null.**
  
- CMPDESE0036**      **Invalid response from server: {0}**
  
- CMPDESE0037**      **Model instance list cannot be null.**
  
- CMPDESE0038**      **Attribute instance list cannot be null.**
  
- CMPDESE0039**      **Method Name cannot be empty or null.**
  
- CMPDESE0040**      **Attribute query string cannot be null.**
  
- CMPDESE0042**      **Attribute value is invalid or not available.**
  
- CMPDESE0043**      **DES Monitoring Context cannot be null.**
  
- CMPDESE0044**      **Input metaModelTypeID cannot be null or empty.**
  
- CMPDESE0045**      **Input modelInstanceID cannot be null or empty.**
  
- CMPDESE0046**      **Input attributeID cannot be null or empty.**
  
- CMPDESE0047**      **AttributeQuery cannot be null.**

---

<b>CMPDESE0048</b>	<b>unused</b>
<b>CMPDESE0049</b>	<b>Input context cannot be null</b>
<b>CMPDESE0050</b>	<b>Exception occurred while getting Object Status, {0}</b>
<b>CMPDESE0051</b>	<b>n/a</b>
<b>CMPDESE0052</b>	<b>Unknown model type: {0} During getting attribute values.</b>
<b>CMPDESE0053</b>	<b>Object is invalid or not available.</b>
<b>CMPDESE0054</b>	<b>Can't create DESMonitoringContext with null DESInputContext");</b>
<b>CMPERTE0001</b>	<b>Error while validating Event Routing Monitoring Context. Event Routing Monitoring Context cannot be null.</b>
<b>CMPERTE0002</b>	<b>Error while validating Event Routing Monitoring Context. Event Routing Monitoring Context is not instance of EventRoutingMonitoringContext.</b>
<b>CMPERTE0003</b>	<b>Error while validating Event Routing Monitoring Context. Context object is null.</b>
<b>CMPERTE0005</b>	<b>Error while validating Event Routing Monitoring Context. Context host attribute cannot be null or empty.</b>
<b>CMPERTE0006</b>	<b>Error while validating Event Routing Monitoring Context. Context port attribute is invalid.</b>
<b>CMPERTE0007</b>	<b>Event Routing Monitoring Context cannot be null.</b>

- CMPERTE0008**      **Error while getting meta model. Event Routing Meta model type ID cannot be null or empty.**
  
- CMPERTE0010**      **Input parameter mbean name cannot be null.**
  
- CMPERTE0012**      **Model instance list or attribute list cannot be null.**
  
- CMPERTE0034**      **Input parameter mbean name cannot be null.**
  
- CMPERTE0036**      **Invalid response from server: {0}**
  
- CMPERTE0037**      **Model instance list cannot be null.**
  
- CMPERTE0038**      **Attribute instance list cannot be null.**
  
- CMPERTE0039**      **Method Name cannot be empty or null.**
  
- CMPERTE0040**      **Attribute query string cannot be null.**
  
- CMPERTE0042**      **Attribute value is invalid or not available.**
  
- CMPERTE0043**      **Event Routing Monitoring Context cannot be null.**
  
- CMPERTE0044**      **Input metaModelTypeID cannot be null or empty.**
  
- CMPERTE0045**      **Input modelInstanceID cannot be null or empty.**
  
- CMPERTE0046**      **Input attributeID cannot be null or empty.**

<b>CMPERTE0047</b>	<b>AttributeQuery cannot be null.</b>
<b>CMPERTE0048</b>	<b>unused</b>
<b>CMPERTE0049</b>	<b>Input context cannot be null</b>
<b>CMPERTE0050</b>	<b>Exception occurred while getting Object Status, {0}</b>
<b>CMPERTE0051</b>	<b>n/a</b>
<b>CMPERTE0052</b>	<b>Unknown model type: {0} During getting attribute values.</b>
<b>CMPERTE0053</b>	<b>Object is invalid or not available.</b>
<b>CMPERTE0054</b>	<b>Can't create EventRoutingMonitoringContext with null EventRoutingInputContext");</b>
<b>CMPERTW0004</b>	<b>Error while validating Event Routing Monitoring Context. Context is invalid.</b>
<b>CMPJBPE0000</b>	<b>Presto HTTP URL Method Name cannot be empty or null.</b>
<b>Explanation</b>	Presto HTTP URL Method Name cannot be empty or null.
<b>Action</b>	Please provide Presto HTTP URL Method Name.
<b>CMPJBPE0001</b>	<b>Error while validating Presto Monitoring Context. Presto Monitoring Context cannot be null.</b>
<b>Explanation</b>	Presto Monitoring Context is required.
<b>Action</b>	Please provide Presto Monitoring Context.
<b>CMPJBPE0002</b>	<b>Error while validating Presto Monitoring Context. Presto Monitoring Context cannot be null.</b>
<b>Explanation</b>	Presto Monitoring Context is required.
<b>Action</b>	Please provide valid Presto Monitoring Context.

<b>CMPJBPE0003</b>	<b>Error while validating Presto Monitoring Context. Context object is null.</b>
<b>Explanation</b>	Presto Monitoring Context is required.
<b>Action</b>	Please provide Presto Monitoring Context.
<b>CMPJBPE0004</b>	<b>Error while validating Presto Monitoring Context. Context is invalid.</b>
<b>Explanation</b>	Presto Monitoring Context is required.
<b>Action</b>	Please provide valid Presto Monitoring Context.
<b>CMPJBPE0005</b>	<b>Error while validating Presto Monitoring Context. Context host attribute cannot be null or empty.</b>
<b>Explanation</b>	Presto Monitoring Context host attribute cannot be null or empty.
<b>Action</b>	Please provide host attribute for Presto Monitoring Context.
<b>CMPJBPE0006</b>	<b>Error while validating Presto Monitoring Context. Context port attribute is invalid.</b>
<b>Explanation</b>	Presto Monitoring Context port attribute cannot be null or empty.
<b>Action</b>	Please provide port attribute for Presto Monitoring Context.
<b>CMPJBPE0007</b>	<b>Presto Monitoring Context cannot be null.</b>
<b>Explanation</b>	Presto Monitoring Context is required for getting Presto model instances.
<b>Action</b>	Please provide Presto Monitoring Context.
<b>CMPJBPE0008</b>	<b>Error while getting meta model. Presto Meta model type ID cannot be null or empty.</b>
<b>Explanation</b>	Presto Meta model type ID cannot be null or empty.
<b>Action</b>	Please provide Presto meta model type ID.
<b>CMPJBPE0009</b>	<b>Presto Monitoring Context cannot be null.</b>
<b>Explanation</b>	Presto Monitoring Context cannot be null.
<b>Action</b>	Please provide Presto Monitoring Context.
<b>CMPJBPE0010</b>	<b>Input parameter mbean name cannot be null.</b>
<b>Explanation</b>	Input parameter mbean name is required.
<b>Action</b>	Please provide input parameter mbean name.

---

<b>CMPJBPE0011</b>	<b>Presto Monitoring Context cannot be null.</b>
<b>Explanation</b>	Presto Monitoring Context is required for getting Presto model instances.
<b>Action</b>	Please provide Presto Monitoring Context.
<b>CMPJBPE0012</b>	<b>Model instance list or attribute list cannot be null.</b>
<b>Explanation</b>	Model instance list or attribute list cannot be null.
<b>Action</b>	Please provide model instance list or attribute list.
<b>CMPJBPE0013</b>	<b>Presto Monitoring Context cannot be null.</b>
<b>Explanation</b>	Presto Monitoring Context is required for getting Presto model instances.
<b>Action</b>	Please provide Presto Monitoring Context.
<b>CMPJBPE0014</b>	<b>Model instance list or attribute list cannot be null.</b>
<b>Explanation</b>	Model instance list or attribute list cannot be null.
<b>Action</b>	Please provide model instance list or attribute list.
<b>CMPJBPE0015</b>	<b>Presto Monitoring Context cannot be null.</b>
<b>Explanation</b>	Presto Monitoring Context is required for getting Presto model instances.
<b>Action</b>	Please provide Presto Monitoring Context.
<b>CMPJBPE0016</b>	<b>Model instance list or attribute list cannot be null.</b>
<b>Explanation</b>	Model instance list or attribute list cannot be null.
<b>Action</b>	Please provide model instance list or attribute list.
<b>CMPJBPE0017</b>	<b>Presto Monitoring Context cannot be null.</b>
<b>Explanation</b>	Presto Monitoring Context is required.
<b>Action</b>	Please provide Presto Monitoring Context.
<b>CMPJBPE0018</b>	<b>Model instance list or attribute list cannot be null.</b>
<b>Explanation</b>	Model instance list or attribute list cannot be null.
<b>Action</b>	Please provide model instance list or attribute list.

<b>CMPJBPE0019</b>	<b>Presto Monitoring Context cannot be null.</b>
<b>Explanation</b>	Presto Monitoring Context is required.
<b>Action</b>	Please provide Presto Monitoring Context.
<b>CMPJBPE0020</b>	<b>Model instance list or attribute list cannot be null.</b>
<b>Explanation</b>	Model instance list or attribute list cannot be null.
<b>Action</b>	Please provide model instance list or attribute list.
<b>CMPJBPE0021</b>	<b>Presto Monitoring Context cannot be null.</b>
<b>Explanation</b>	Presto Monitoring Context is required.
<b>Action</b>	Please provide Presto Monitoring Context.
<b>CMPJBPE0022</b>	<b>Model instance list or attribute list cannot be null.</b>
<b>Explanation</b>	Model instance list or attribute list cannot be null.
<b>Action</b>	Please provide model instance list or attribute list.
<b>CMPJBPE0023</b>	<b>Presto Monitoring Context cannot be null.</b>
<b>Explanation</b>	Presto Monitoring Context is required.
<b>Action</b>	Please provide Presto Monitoring Context.
<b>CMPJBPE0024</b>	<b>Model instance list or attribute list cannot be null.</b>
<b>Explanation</b>	Model instance list or attribute list cannot be null.
<b>Action</b>	Please provide model instance list or attribute list.
<b>CMPJBPE0025</b>	<b>Presto Monitoring Context cannot be null.</b>
<b>Explanation</b>	Presto Monitoring Context is required.
<b>Action</b>	Please provide Presto Monitoring Context.
<b>CMPJBPE0026</b>	<b>Model instance list or attribute list cannot be null.</b>
<b>Explanation</b>	Model instance list or attribute list cannot be null.
<b>Action</b>	Please provide model instance list or attribute list.

---

<b>CMPJBPE0027</b>	<b>Presto Monitoring Context cannot be null.</b>
<b>Explanation</b>	Presto Monitoring Context is required.
<b>Action</b>	Please provide Presto Monitoring Context.
<b>CMPJBPE0028</b>	<b>Model instance list or attribute list cannot be null.</b>
<b>Explanation</b>	Model instance list or attribute list cannot be null.
<b>Action</b>	Please provide model instance list or attribute list.
<b>CMPJBPE0029</b>	<b>Presto Monitoring Context cannot be null.</b>
<b>Explanation</b>	Presto Monitoring Context is required.
<b>Action</b>	Please provide Presto Monitoring Context.
<b>CMPJBPE0030</b>	<b>Presto Monitoring Context cannot be null.</b>
<b>Explanation</b>	Presto Monitoring Context is required.
<b>Action</b>	Please provide Presto Monitoring Context.
<b>CMPJBPE0031</b>	<b>Model instance list or attribute list cannot be null.</b>
<b>Explanation</b>	Model instance list or attribute list cannot be null.
<b>Action</b>	Please provide model instance list or attribute list.
<b>CMPJBPE0032</b>	<b>Presto Monitoring Context cannot be null.</b>
<b>Explanation</b>	Presto Monitoring Context is required.
<b>Action</b>	Please provide Presto Monitoring Context.
<b>CMPJBPE0033</b>	<b>Model instance list or attribute list cannot be null.</b>
<b>Explanation</b>	Model instance list or attribute list cannot be null.
<b>Action</b>	Please provide model instance list or attribute list.
<b>CMPJBPE0034</b>	<b>Input parameter mbean name cannot be null.</b>
<b>Explanation</b>	Input parameter mbean name is required.
<b>Action</b>	Please provide input parameter mbean name.

**CMPJBPE0035**      **Model instance list or attribute list cannot be null.**

**Explanation**      Model instance list or attribute list cannot be null.

**Action**            Please provide model instance list or attribute list.

**CMPJBPE0036**      **Invalid response from server: {0}**

**Explanation**      Invalid response from server.

**Action**            Please resolve the issue with output.

**CMPJBPE0037**      **Model instance list cannot be null.**

**Explanation**      Model instance list cannot be null.

**Action**            Please provide model instance list.

**CMPJBPE0038**      **Attribute instance list cannot be null.**

**Explanation**      Attribute instance list cannot be null.

**Action**            Please provide attribute instance list.

**CMPJBPE0039**      **Method Name cannot be empty or null.**

**Explanation**      Method Name cannot be empty or null.

**Action**            Please provide method name.

**CMPJBPE0040**      **Attribute query string cannot be null.**

**Explanation**      Attribute query string cannot be null.

**Action**            Please provide attribute query string.

**CMPJBPE0041**      **Presto Monitoring Context cannot be null.**

**Explanation**      Presto Monitoring Context cannot be null.

**Action**            Please provide monitoring context.

**CMPJBPE0042**      **Attribute value is invalid or not available.**

**Explanation**      Attribute value is invalid or not available.

**Action**            Please provide valid attribute value.

---

<b>CMPJBPE0043</b>	<b>Presto Monitoring Context cannot be null.</b>
<b>Explanation</b>	Presto Monitoring Context is required.
<b>Action</b>	Please provide Presto Monitoring Context.
<b>CMPJBPE0044</b>	<b>Input metaModelTypeID cannot be null or empty.</b>
<b>Explanation</b>	Input metaModelTypeID cannot be null or empty.
<b>Action</b>	Please provide meta model type ID.
<b>CMPJBPE0045</b>	<b>Input modelInstanceID cannot be null or empty.</b>
<b>Explanation</b>	Input modelInstanceID cannot be null or empty.
<b>Action</b>	Please provide model instance ID.
<b>CMPJBPE0046</b>	<b>Input attributeID cannot be null or empty.</b>
<b>Explanation</b>	Input attributeID cannot be null or empty.
<b>Action</b>	Please provide attribute ID.
<b>CMPJBPE0047</b>	<b>AttributeQuery cannot be null.</b>
<b>Explanation</b>	AttributeQuery cannot be null.
<b>Action</b>	Please provide attribute query.
<b>CMPJBPE0048</b>	<b>unused</b>
<b>Explanation</b>	unused
<b>Action</b>	Report the error
<b>CMPJBPE0049</b>	<b>Input context cannot be null</b>
<b>Explanation</b>	Input context cannot be null
<b>CMPJBPE0050</b>	<b>Exception occurred while getting Object Status, {0}</b>
<b>Explanation</b>	Exception occurred while getting Object Status, Exception attached.
<b>Action</b>	Report the error

<b>CMPJBPE0051</b>	<b>n/a</b>
<b>Explanation</b>	n/a
<b>Action</b>	Report the error
<b>CMPJBPE0052</b>	<b>Unknown model type: {0} During getting attribute values.</b>
<b>Explanation</b>	Encountered an unknown model type when getting attribute values.
<b>Action</b>	Report the error
<b>CMPJBPE0053</b>	<b>Object is invalid or not available.</b>
<b>Explanation</b>	Object is invalid or not available is a default error message for a missing attribute.
<b>Action</b>	Report the error.
<b>CMPJBPE0054</b>	<b>Can't create PrestoMonitoringContext with null PrestoInputContext</b>
<b>Explanation</b>	There is code trying to create a PrestoMonitoringContext with null PrestoInputContext
<b>Action</b>	Report the error
<b>CMPJMXE0000</b>	<b>Jmx HTTP URL Method Name cannot be empty or null.</b>
<b>Explanation</b>	Jmx HTTP URL Method Name cannot be empty or null.
<b>Action</b>	Please provide Jmx HTTP URL Method Name.
<b>CMPJMXE0001</b>	<b>Error while validating Jmx Monitoring Context. Jmx Monitoring Context cannot be null.</b>
<b>Explanation</b>	Jmx Monitoring Context is required.
<b>Action</b>	Please provide Jmx Monitoring Context.
<b>CMPJMXE0003</b>	<b>Error while validating Jmx Monitoring Context. Context object is null.</b>
<b>Explanation</b>	Jmx Monitoring Context is required.
<b>Action</b>	Please provide Jmx Monitoring Context.
<b>CMPJMXE0004</b>	<b>Error while validating Jmx Monitoring Context. Context is invalid.</b>
<b>Explanation</b>	Jmx Monitoring Context is required.
<b>Action</b>	Please provide valid Jmx Monitoring Context.

---

<b>CMPJMXE0005</b>	<b>Error while validating Jmx Monitoring Context. Context host attribute cannot be null or empty.</b>
<b>Explanation</b>	Jmx Monitoring Context host attribute cannot be null or empty.
<b>Action</b>	Please provide host attribute for Jmx Monitoring Context.
<b>CMPJMXE0006</b>	<b>Error while validating Jmx Monitoring Context. Context port attribute is invalid.</b>
<b>Explanation</b>	Jmx Monitoring Context port attribute cannot be null or empty.
<b>Action</b>	Please provide port attribute for Jmx Monitoring Context.
<b>CMPJMXE0007</b>	<b>Jmx Monitoring Context cannot be null.</b>
<b>Explanation</b>	Jmx Monitoring Context is required for getting Jmx model instances.
<b>Action</b>	Please provide Jmx Monitoring Context.
<b>CMPJMXE0020</b>	<b>mBean filter can not be null or empty.</b>
<b>Explanation</b>	mBean filter can not be null or empty.
<b>Action</b>	Please provide mBean filter.
<b>CMPJMXE0037</b>	<b>Model instance list cannot be null.</b>
<b>Explanation</b>	Model instance list cannot be null.
<b>Action</b>	Please provide model instance list.
<b>CMPJMXE0038</b>	<b>Attribute instance list cannot be null.</b>
<b>Explanation</b>	Attribute instance list cannot be null.
<b>Action</b>	Please provide attribute instance list.
<b>CMPJMXE0060</b>	<b>SSL enabled, but there is no trustStore configured! The input context is invalid.</b>
<b>Explanation</b>	SSL enabled, but there is no trustStore configured! The input context is invalid.
<b>Action</b>	Please provide trustStore
<b>CMPJMXE0061</b>	<b>Jmx server is not reachable.</b>
<b>Explanation</b>	Jmx server is not reachable.
<b>Action</b>	Please make sure Jmx server is reachable

<b>CMPMNGE0000</b>	<b>Mashzone NextGen HTTP URL Method Name cannot be empty or null.</b>
<b>Explanation</b>	Mashzone NextGen HTTP URL Method Name cannot be empty or null.
<b>CMPMNGE0001</b>	<b>Error while validating Mashzone NextGen Monitoring Context. Mashzone NextGen Monitoring Context cannot be null.</b>
<b>Explanation</b>	Error while validating Mashzone NextGen Monitoring Context. Mashzone NextGen Monitoring Context cannot be null.
<b>CMPMNGE0002</b>	<b>Error while validating Mashzone NextGen Monitoring Context. Mashzone NextGen Monitoring Context is not instance of MZNGMonitoringContext.</b>
<b>Explanation</b>	Error while validating Mashzone NextGen Monitoring Context. Mashzone NextGen Monitoring Context is not instance of MZNGMonitoringContext.
<b>CMPMNGE0003</b>	<b>Error while validating Mashzone NextGen Monitoring Context. Context object is null.</b>
<b>Explanation</b>	Error while validating Mashzone NextGen Monitoring Context. Context object is null.
<b>CMPMNGE0004</b>	<b>Error while validating Mashzone NextGen Monitoring Context. Context is invalid.</b>
<b>Explanation</b>	Error while validating Mashzone NextGen Monitoring Context. Context is invalid.
<b>CMPMNGE0005</b>	<b>Error while validating Mashzone NextGen Monitoring Context. Context host attribute cannot be null or empty.</b>
<b>Explanation</b>	Error while validating Mashzone NextGen Monitoring Context. Context host attribute cannot be null or empty.
<b>CMPMNGE0006</b>	<b>Error while validating Mashzone NextGen Monitoring Context. Context port attribute is invalid.</b>
<b>Explanation</b>	Error while validating Mashzone NextGen Monitoring Context. Context port attribute is invalid.
<b>CMPMNGE0007</b>	<b>Mashzone NextGen Monitoring Context cannot be null.</b>
<b>Explanation</b>	Mashzone NextGen Monitoring Context cannot be null.

---

<b>CMPMNGE0008</b>	<b>Error while getting meta model. Mashzone NextGen Meta model type ID cannot be null or empty.</b>
<b>Explanation</b>	Error while getting meta model. Mashzone NextGen Meta model type ID cannot be null or empty.
<b>CMPMNGE0010</b>	<b>Input parameter mbean name cannot be null.</b>
<b>Explanation</b>	Input parameter mbean name cannot be null.
<b>CMPMNGE0012</b>	<b>Model instance list or attribute list cannot be null.</b>
<b>Explanation</b>	Model instance list or attribute list cannot be null.
<b>CMPMNGE0034</b>	<b>Input parameter mbean name cannot be null.</b>
<b>Explanation</b>	Input parameter mbean name cannot be null.
<b>CMPMNGE0036</b>	<b>Invalid response from server: {0}</b>
<b>Explanation</b>	Invalid response from server: {0}
<b>CMPMNGE0037</b>	<b>Model instance list cannot be null.</b>
<b>Explanation</b>	Model instance list cannot be null.
<b>CMPMNGE0038</b>	<b>Attribute instance list cannot be null.</b>
<b>Explanation</b>	Attribute instance list cannot be null.
<b>CMPMNGE0039</b>	<b>Method Name cannot be empty or null.</b>
<b>Explanation</b>	Method Name cannot be empty or null.
<b>CMPMNGE0040</b>	<b>Attribute query string cannot be null.</b>
<b>Explanation</b>	Attribute query string cannot be null.
<b>CMPMNGE0042</b>	<b>Attribute value is invalid or not available.</b>
<b>Explanation</b>	Attribute value is invalid or not available.

<b>CMPMNGE0043</b>	<b>Mashzone NextGen Monitoring Context cannot be null.</b>
<b>Explanation</b>	Mashzone NextGen Monitoring Context cannot be null.
<b>CMPMNGE0044</b>	<b>Input metaModelTypeID cannot be null or empty.</b>
<b>Explanation</b>	Input metaModelTypeID cannot be null or empty.
<b>CMPMNGE0045</b>	<b>Input modelInstanceID cannot be null or empty.</b>
<b>Explanation</b>	Input modelInstanceID cannot be null or empty.
<b>CMPMNGE0046</b>	<b>Input attributeID cannot be null or empty.</b>
<b>Explanation</b>	Input attributeID cannot be null or empty.
<b>CMPMNGE0047</b>	<b>AttributeQuery cannot be null.</b>
<b>Explanation</b>	AttributeQuery cannot be null.
<b>CMPMNGE0048</b>	<b>unused</b>
<b>Explanation</b>	unused
<b>CMPMNGE0049</b>	<b>Input context cannot be null</b>
<b>Explanation</b>	Input context cannot be null
<b>CMPMNGE0050</b>	<b>Exception occurred while getting Object Status, {0}</b>
<b>Explanation</b>	Exception occurred while getting Object Status, {0}
<b>CMPMNGE0051</b>	<b>n/a</b>
<b>Explanation</b>	n/a
<b>CMPMNGE0052</b>	<b>Unknown model type: {0} During getting attribute values.</b>
<b>Explanation</b>	Unknown model type: {0} During getting attribute values.

---

<b>CMPMNGE0053</b>	<b>Object is invalid or not available.</b>
<b>Explanation</b>	Object is invalid or not available.
<b>CMPMNGE0054</b>	<b>Can't create MZNGMonitoringContext with null MZNGInputContext</b>
<b>Explanation</b>	Can't create MZNGMonitoringContext with null MZNGInputContext
<b>CMPMWSE0000</b>	<b>MWS HTTP URL Method Name cannot be empty or null.</b>
<b>Explanation</b>	MWS HTTP URL Method Name cannot be empty or null.
<b>Action</b>	Please provide MWS HTTP URL Method Name.
<b>CMPMWSE0001</b>	<b>Error while validating MWS Monitoring Context. MWS Monitoring Context cannot be null.</b>
<b>Explanation</b>	MWS Monitoring Context is required.
<b>Action</b>	Please provide MWS Monitoring Context.
<b>CMPMWSE0002</b>	<b>Error while validating MWS Monitoring Context. MWS Monitoring Context cannot be null.</b>
<b>Explanation</b>	MWS Monitoring Context is required.
<b>Action</b>	Please provide valid MWS Monitoring Context.
<b>CMPMWSE0003</b>	<b>Error while validating Broker Monitoring Context. Context object is null.</b>
<b>Explanation</b>	MWS Monitoring Context is required.
<b>Action</b>	Please provide MWS Monitoring Context.
<b>CMPMWSE0004</b>	<b>Error while validating MWS Monitoring Context. Context is invalid.</b>
<b>Explanation</b>	MWS Monitoring Context is required.
<b>Action</b>	Please provide valid MWS Monitoring Context.
<b>CMPMWSE0005</b>	<b>Error while validating MWS Monitoring Context. Context host attribute cannot be null or empty.</b>
<b>Explanation</b>	MWS Monitoring Context host attribute cannot be null or empty.
<b>Action</b>	Please provide host attribute for MWS Monitoring Context.

**CMPMWSE0006**    **Error while validating Broker Monitoring Context. Context port attribute is invalid.**  
**Explanation**    MWS Monitoring Context port attribute cannot be null or empty.  
**Action**            Please provide port attribute for MWS Monitoring Context.

**CMPMWSE0007**    **MWS Monitoring Context cannot be null.**  
**Explanation**    MWS Monitoring Context is required for getting MWS model instances.  
**Action**            Please provide MWS Monitoring Context.

**CMPMWSE0008**    **Error while getting meta model. MWS Meta model type ID cannot be null or empty.**  
**Explanation**    MWS Meta model type ID cannot be null or empty.  
**Action**            Please provide MWS meta model type ID.

**CMPMWSE0009**    **MWS Monitoring Context cannot be null.**  
**Explanation**    MWS Monitoring Context cannot be null.  
**Action**            Please provide MWS Monitoring Context.

**CMPMWSE0010**    **Input parameter mbean name cannot be null.**  
**Explanation**    Input parameter mbean name is required.  
**Action**            Please provide input parameter mbean name.

**CMPMWSE0011**    **MWS Monitoring Context cannot be null.**  
**Explanation**    MWS Monitoring Context is required for getting MWS model instances.  
**Action**            Please provide MWS Monitoring Context.

**CMPMWSE0012**    **Model instance list or attribute list cannot be null.**  
**Explanation**    Model instance list or attribute list cannot be null.  
**Action**            Please provide model instance list or attribute list.

**CMPMWSE0013**    **MWS Monitoring Context cannot be null.**  
**Explanation**    MWS Monitoring Context is required for getting MWS model instances.  
**Action**            Please provide MWS Monitoring Context.

---

<b>CMPMWSE0014</b>	<b>Model instance list or attribute list cannot be null.</b>
<b>Explanation</b>	Model instance list or attribute list cannot be null.
<b>Action</b>	Please provide model instance list or attribute list.
<b>CMPMWSE0015</b>	<b>MWS Monitoring Context cannot be null.</b>
<b>Explanation</b>	MWS Monitoring Context is required for getting MWS model instances.
<b>Action</b>	Please provide MWS Monitoring Context.
<b>CMPMWSE0016</b>	<b>Model instance list or attribute list cannot be null.</b>
<b>Explanation</b>	Model instance list or attribute list cannot be null.
<b>Action</b>	Please provide model instance list or attribute list.
<b>CMPMWSE0017</b>	<b>MWS Monitoring Context cannot be null.</b>
<b>Explanation</b>	MWS Monitoring Context is required.
<b>Action</b>	Please provide MWS Monitoring Context.
<b>CMPMWSE0018</b>	<b>Model instance list or attribute list cannot be null.</b>
<b>Explanation</b>	Model instance list or attribute list cannot be null.
<b>Action</b>	Please provide model instance list or attribute list.
<b>CMPMWSE0019</b>	<b>MWS Monitoring Context cannot be null.</b>
<b>Explanation</b>	MWS Monitoring Context is required.
<b>Action</b>	Please provide MWS Monitoring Context.
<b>CMPMWSE0020</b>	<b>Model instance list or attribute list cannot be null.</b>
<b>Explanation</b>	Model instance list or attribute list cannot be null.
<b>Action</b>	Please provide model instance list or attribute list.
<b>CMPMWSE0021</b>	<b>MWS Monitoring Context cannot be null.</b>
<b>Explanation</b>	MWS Monitoring Context is required.
<b>Action</b>	Please provide MWS Monitoring Context.

**CMPMWSE0022    Model instance list or attribute list cannot be null.**

**Explanation**    Model instance list or attribute list cannot be null.

**Action**    Please provide model instance list or attribute list.

**CMPMWSE0023    MWS Monitoring Context cannot be null.**

**Explanation**    MWS Monitoring Context is required.

**Action**    Please provide MWS Monitoring Context.

**CMPMWSE0024    Model instance list or attribute list cannot be null.**

**Explanation**    Model instance list or attribute list cannot be null.

**Action**    Please provide model instance list or attribute list.

**CMPMWSE0025    MWS Monitoring Context cannot be null.**

**Explanation**    MWS Monitoring Context is required.

**Action**    Please provide MWS Monitoring Context.

**CMPMWSE0026    Model instance list or attribute list cannot be null.**

**Explanation**    Model instance list or attribute list cannot be null.

**Action**    Please provide model instance list or attribute list.

**CMPMWSE0027    MWS Monitoring Context cannot be null.**

**Explanation**    MWS Monitoring Context is required.

**Action**    Please provide MWS Monitoring Context.

**CMPMWSE0028    Model instance list or attribute list cannot be null.**

**Explanation**    Model instance list or attribute list cannot be null.

**Action**    Please provide model instance list or attribute list.

**CMPMWSE0029    MWS Monitoring Context cannot be null.**

**Explanation**    MWS Monitoring Context is required.

**Action**    Please provide MWS Monitoring Context.

---

<b>CMPMWSE0030</b>	<b>MWS Monitoring Context cannot be null.</b>
<b>Explanation</b>	MWS Monitoring Context is required.
<b>Action</b>	Please provide MWS Monitoring Context.
<b>CMPMWSE0031</b>	<b>Model instance list or attribute list cannot be null.</b>
<b>Explanation</b>	Model instance list or attribute list cannot be null.
<b>Action</b>	Please provide model instance list or attribute list.
<b>CMPMWSE0032</b>	<b>MWS Monitoring Context cannot be null.</b>
<b>Explanation</b>	MWS Monitoring Context is required.
<b>Action</b>	Please provide MWS Monitoring Context.
<b>CMPMWSE0033</b>	<b>Model instance list or attribute list cannot be null.</b>
<b>Explanation</b>	Model instance list or attribute list cannot be null.
<b>Action</b>	Please provide model instance list or attribute list.
<b>CMPMWSE0034</b>	<b>Input parameter mbean name cannot be null.</b>
<b>Explanation</b>	Input parameter mbean name is required.
<b>Action</b>	Please provide input parameter mbean name.
<b>CMPMWSE0035</b>	<b>Model instance list or attribute list cannot be null.</b>
<b>Explanation</b>	Model instance list or attribute list cannot be null.
<b>Action</b>	Please provide model instance list or attribute list.
<b>CMPMWSE0036</b>	<b>Invalid response from server: {0}</b>
<b>Explanation</b>	Invalid response from server.
<b>Action</b>	Please resolve the issue with output.
<b>CMPMWSE0037</b>	<b>Model instance list cannot be null.</b>
<b>Explanation</b>	Model instance list cannot be null.
<b>Action</b>	Please provide model instance list.

<b>CMPMWSE0038</b>	<b>Attribute instance list cannot be null.</b>
<b>Explanation</b>	Attribute instance list cannot be null.
<b>Action</b>	Please provide attribute instance list.
<b>CMPMWSE0039</b>	<b>Method Name cannot be empty or null.</b>
<b>Explanation</b>	Method Name cannot be empty or null.
<b>Action</b>	Please provide method name.
<b>CMPMWSE0040</b>	<b>Attribute query string cannot be null.</b>
<b>Explanation</b>	Attribute query string cannot be null.
<b>Action</b>	Please provide attribute query string.
<b>CMPMWSE0041</b>	<b>MWS Monitoring Context cannot be null.</b>
<b>Explanation</b>	MWS Monitoring Context cannot be null.
<b>Action</b>	Please provide monitoring context.
<b>CMPMWSE0042</b>	<b>Attribute value is invalid or not available.</b>
<b>Explanation</b>	Attribute value is invalid or not available.
<b>Action</b>	Please provide valid attribute value.
<b>CMPMWSE0043</b>	<b>MWS Monitoring Context cannot be null.</b>
<b>Explanation</b>	MWS Monitoring Context is required.
<b>Action</b>	Please provide MWS Monitoring Context.
<b>CMPMWSE0044</b>	<b>Input metaModelTypeID cannot be null or empty.</b>
<b>Explanation</b>	Input metaModelTypeID cannot be null or empty.
<b>Action</b>	Please provide meta model type ID.
<b>CMPMWSE0045</b>	<b>Input modelInstanceID cannot be null or empty.</b>
<b>Explanation</b>	Input modelInstanceID cannot be null or empty.
<b>Action</b>	Please provide model instance ID.

---

<b>CMPMWSE0046</b>	<b>Input attributeID cannot be null or empty.</b>
<b>Explanation</b>	Input attributeID cannot be null or empty.
<b>Action</b>	Please provide attribute ID.
<b>CMPMWSE0047</b>	<b>AttributeQuery cannot be null.</b>
<b>Explanation</b>	AttributeQuery cannot be null.
<b>Action</b>	Please provide attribute query.
<b>CMPTCME0001</b>	<b>Error while validating TC Monitoring Context. TC Monitoring Context cannot be null.</b>
<b>CMPTCME0002</b>	<b>Error while validating TC Monitoring Context. Context is not terracotta type.</b>
<b>CMPTCME0003</b>	<b>Error while validating TC Input Context. TC Input Context cannot be null.</b>
<b>CMPTCME0004</b>	<b>Error while validating TC Input Context. Context is not terracotta type.</b>
<b>CMPTCME0005</b>	<b>Error while validating TC Input Context. TMC host attribute cannot be null or empty.</b>
<b>CMPTCME0006</b>	<b>Error while validating TC Input Context. TMC port attribute is invalid.</b>
<b>CMPTCME0007</b>	<b>TC Input Monitoring Context cannot be null.</b>
<b>CMPTCME0008</b>	<b>Error while getting meta model. TC Meta model type ID cannot be null or empty.</b>
<b>CMPTCME0009</b>	<b>TC Monitoring Context cannot be null.</b>
<b>CMPTCME0010</b>	<b>Model instance list cannot be null.</b>

<b>CMPTCME0011</b>	<b>Attribute instance list cannot be null.</b>
<b>CMPTCME0012</b>	<b>Model instance list or attribute list cannot be null.</b>
<b>CMPTCME0013</b>	<b>Attribute query string cannot be null.</b>
<b>CMPTCME0014</b>	<b>Attribute value is invalid or not available.</b>
<b>CMPTCME0015</b>	<b>Input metaModelTypeID cannot be null or empty.</b>
<b>CMPTCME0016</b>	<b>Input modelInstanceID cannot be null or empty.</b>
<b>CMPTCME0017</b>	<b>Input attributeID cannot be null or empty.</b>
<b>CMPTCME0018</b>	<b>AttributeQuery cannot be null.</b>
<b>CMPTCME0019</b>	<b>Version not support.</b>
<b>CMPTCME0020</b>	<b>Could not connect to url {0}.</b>
<b>COMPUMIE0000</b>	<b>UM HTTP URL Method Name cannot be empty or null.</b>
<b>Explanation</b>	UM HTTP URL Method Name cannot be empty or null.
<b>Action</b>	Please provide UM HTTP URL Method Name.
<b>COMPUMIE0001</b>	<b>Error while validating UM Monitoring Context. UM Monitoring Context cannot be null.</b>
<b>Explanation</b>	UM Monitoring Context is required.
<b>Action</b>	Please provide UM Monitoring Context.

---

<b>CMPUMIE0002</b>	<b>Error while validating UM Monitoring Context. UM Monitoring Context cannot be null.</b>
<b>Explanation</b>	UM Monitoring Context is required.
<b>Action</b>	Please provide valid UM Monitoring Context.
<b>CMPUMIE0003</b>	<b>Error while validating UM Monitoring Context. Context object is null.</b>
<b>Explanation</b>	UM Monitoring Context is required.
<b>Action</b>	Please provide UM Monitoring Context.
<b>CMPUMIE0004</b>	<b>Error while validating UM Monitoring Context. Context is invalid.</b>
<b>Explanation</b>	UM Monitoring Context is required.
<b>Action</b>	Please provide valid UM Monitoring Context.
<b>CMPUMIE0005</b>	<b>Error while validating UM Monitoring Context. Context host attribute cannot be null or empty.</b>
<b>Explanation</b>	UM Monitoring Context host attribute cannot be null or empty.
<b>Action</b>	Please provide host attribute for UM Monitoring Context.
<b>CMPUMIE0006</b>	<b>Error while validating UM Monitoring Context. Context port attribute is invalid.</b>
<b>Explanation</b>	UM Monitoring Context port attribute cannot be null or empty.
<b>Action</b>	Please provide port attribute for UM Monitoring Context.
<b>CMPUMIE0007</b>	<b>UM Monitoring Context cannot be null.</b>
<b>Explanation</b>	UM Monitoring Context is required for getting UM model instances.
<b>Action</b>	Please provide UM Monitoring Context.
<b>CMPUMIE0008</b>	<b>Error while getting meta model. UM Meta model type ID cannot be null or empty.</b>
<b>Explanation</b>	UM Meta model type ID cannot be null or empty.
<b>Action</b>	Please provide UM meta model type ID.
<b>CMPUMIE0009</b>	<b>UM Monitoring Context cannot be null.</b>
<b>Explanation</b>	UM Monitoring Context cannot be null.
<b>Action</b>	Please provide UM Monitoring Context.

<b>CMPUMIE0010</b>	<b>Input parameter mbean name cannot be null.</b>
<b>Explanation</b>	Input parameter mbean name is required.
<b>Action</b>	Please provide input parameter mbean name.
<b>CMPUMIE0011</b>	<b>UM Monitoring Context cannot be null.</b>
<b>Explanation</b>	UM Monitoring Context is required for getting UM model instances.
<b>Action</b>	Please provide UM Monitoring Context.
<b>CMPUMIE0012</b>	<b>Model instance list or attribute list cannot be null.</b>
<b>Explanation</b>	Model instance list or attribute list cannot be null.
<b>Action</b>	Please provide model instance list or attribute list.
<b>CMPUMIE0013</b>	<b>UM Monitoring Context cannot be null.</b>
<b>Explanation</b>	UM Monitoring Context is required for getting UM model instances.
<b>Action</b>	Please provide UM Monitoring Context.
<b>CMPUMIE0014</b>	<b>Model instance list or attribute list cannot be null.</b>
<b>Explanation</b>	Model instance list or attribute list cannot be null.
<b>Action</b>	Please provide model instance list or attribute list.
<b>CMPUMIE0015</b>	<b>UM Monitoring Context cannot be null.</b>
<b>Explanation</b>	UM Monitoring Context is required for getting UM model instances.
<b>Action</b>	Please provide UM Monitoring Context.
<b>CMPUMIE0016</b>	<b>Model instance list or attribute list cannot be null.</b>
<b>Explanation</b>	Model instance list or attribute list cannot be null.
<b>Action</b>	Please provide model instance list or attribute list.
<b>CMPUMIE0017</b>	<b>UM Monitoring Context cannot be null.</b>
<b>Explanation</b>	UM Monitoring Context is required.
<b>Action</b>	Please provide UM Monitoring Context.

---

<b>CMPUMIE0018</b>	<b>Model instance list or attribute list cannot be null.</b>
<b>Explanation</b>	Model instance list or attribute list cannot be null.
<b>Action</b>	Please provide model instance list or attribute list.
<b>CMPUMIE0019</b>	<b>UM Monitoring Context cannot be null.</b>
<b>Explanation</b>	UM Monitoring Context is required.
<b>Action</b>	Please provide UM Monitoring Context.
<b>CMPUMIE0020</b>	<b>Model instance list or attribute list cannot be null.</b>
<b>Explanation</b>	Model instance list or attribute list cannot be null.
<b>Action</b>	Please provide model instance list or attribute list.
<b>CMPUMIE0021</b>	<b>UM Monitoring Context cannot be null.</b>
<b>Explanation</b>	UM Monitoring Context is required.
<b>Action</b>	Please provide UM Monitoring Context.
<b>CMPUMIE0022</b>	<b>Model instance list or attribute list cannot be null.</b>
<b>Explanation</b>	Model instance list or attribute list cannot be null.
<b>Action</b>	Please provide model instance list or attribute list.
<b>CMPUMIE0023</b>	<b>UM Monitoring Context cannot be null.</b>
<b>Explanation</b>	UM Monitoring Context is required.
<b>Action</b>	Please provide UM Monitoring Context.
<b>CMPUMIE0024</b>	<b>Model instance list or attribute list cannot be null.</b>
<b>Explanation</b>	Model instance list or attribute list cannot be null.
<b>Action</b>	Please provide model instance list or attribute list.
<b>CMPUMIE0025</b>	<b>UM Monitoring Context cannot be null.</b>
<b>Explanation</b>	UM Monitoring Context is required.
<b>Action</b>	Please provide UM Monitoring Context.

**CMPUMIE0026**      **Model instance list or attribute list cannot be null.**  
**Explanation**      Model instance list or attribute list cannot be null.  
**Action**              Please provide model instance list or attribute list.

**CMPUMIE0027**      **UM Monitoring Context cannot be null.**  
**Explanation**      UM Monitoring Context is required.  
**Action**              Please provide UM Monitoring Context.

**CMPUMIE0028**      **Model instance list or attribute list cannot be null.**  
**Explanation**      Model instance list or attribute list cannot be null.  
**Action**              Please provide model instance list or attribute list.

**CMPUMIE0029**      **UM Monitoring Context cannot be null.**  
**Explanation**      UM Monitoring Context is required.  
**Action**              Please provide UM Monitoring Context.

**CMPUMIE0030**      **UM Monitoring Context cannot be null.**  
**Explanation**      UM Monitoring Context is required.  
**Action**              Please provide UM Monitoring Context.

**CMPUMIE0031**      **Model instance list or attribute list cannot be null.**  
**Explanation**      Model instance list or attribute list cannot be null.  
**Action**              Please provide model instance list or attribute list.

**CMPUMIE0032**      **UM Monitoring Context cannot be null.**  
**Explanation**      UM Monitoring Context is required.  
**Action**              Please provide UM Monitoring Context.

**CMPUMIE0033**      **Model instance list or attribute list cannot be null.**  
**Explanation**      Model instance list or attribute list cannot be null.  
**Action**              Please provide model instance list or attribute list.

---

<b>CMPUMIE0034</b>	<b>Input parameter mbean name cannot be null.</b>
<b>Explanation</b>	Input parameter mbean name is required.
<b>Action</b>	Please provide input parameter mbean name.
<b>CMPUMIE0035</b>	<b>Model instance list or attribute list cannot be null.</b>
<b>Explanation</b>	Model instance list or attribute list cannot be null.
<b>Action</b>	Please provide model instance list or attribute list.
<b>CMPUMIE0036</b>	<b>Invalid response from server: {0}</b>
<b>Explanation</b>	Invalid response from server.
<b>Action</b>	Please resolve the issue with output.
<b>CMPUMIE0037</b>	<b>Model instance list cannot be null.</b>
<b>Explanation</b>	Model instance list cannot be null.
<b>Action</b>	Please provide model instance list.
<b>CMPUMIE0038</b>	<b>Attribute instance list cannot be null.</b>
<b>Explanation</b>	Attribute instance list cannot be null.
<b>Action</b>	Please provide attribute instance list.
<b>CMPUMIE0039</b>	<b>Method Name cannot be empty or null.</b>
<b>Explanation</b>	Method Name cannot be empty or null.
<b>Action</b>	Please provide method name.
<b>CMPUMIE0040</b>	<b>Attribute query string cannot be null.</b>
<b>Explanation</b>	Attribute query string cannot be null.
<b>Action</b>	Please provide attribute query string.
<b>CMPUMIE0041</b>	<b>UM Monitoring Context cannot be null.</b>
<b>Explanation</b>	UM Monitoring Context cannot be null.
<b>Action</b>	Please provide monitoring context.

<b>CMPUMIE0042</b>	<b>Attribute value is invalid or not available.</b>
<b>Explanation</b>	Attribute value is invalid or not available.
<b>Action</b>	Please provide valid attribute value.
<b>CMPUMIE0043</b>	<b>UM Monitoring Context cannot be null.</b>
<b>Explanation</b>	UM Monitoring Context is required.
<b>Action</b>	Please provide UM Monitoring Context.
<b>CMPUMIE0044</b>	<b>Input metaModelTypeID cannot be null or empty.</b>
<b>Explanation</b>	Input metaModelTypeID cannot be null or empty.
<b>Action</b>	Please provide meta model type ID.
<b>CMPUMIE0045</b>	<b>Input modelInstanceID cannot be null or empty.</b>
<b>Explanation</b>	Input modelInstanceID cannot be null or empty.
<b>Action</b>	Please provide model instance ID.
<b>CMPUMIE0046</b>	<b>Input attributeID cannot be null or empty.</b>
<b>Explanation</b>	Input attributeID cannot be null or empty.
<b>Action</b>	Please provide attribute ID.
<b>CMPUMIE0047</b>	<b>AttributeQuery cannot be null.</b>
<b>Explanation</b>	AttributeQuery cannot be null.
<b>Action</b>	Please provide attribute query.
<b>CMPUMIE0048</b>	<b>No such node with path {0}</b>
<b>Explanation</b>	No UM node has been found or stored with the path provided.
<b>Action</b>	Report the error
<b>CMPUMIE0049</b>	<b>Failed to get attribute values for instance {0}. No such node with path : {1}</b>
<b>Explanation</b>	Failed to get attribute values for instance {0}. No such node with path : {1}
<b>Action</b>	Report the error

---

<b>CMPUMIE0050</b>	<b>Failed for instance {0}. Exception message : {1}</b>
<b>Explanation</b>	Failed to get attribute values for an instance. Exception message attached.
<b>Action</b>	Report the error
<b>CMPUMIE0051</b>	<b>Failed for instance {0}. Can't parse path : {1}</b>
<b>Explanation</b>	Failed to get attribute values for an instance. Failed to parse the attached path.
<b>Action</b>	Report the error
<b>CMPUMIE0052</b>	<b>Unknown model type: {0} During getting attribute values.</b>
<b>Explanation</b>	Encountered an unknown model type when getting attribute values.
<b>Action</b>	Report the error
<b>CMPUMIE0053</b>	<b>Object is invalid or not available.</b>
<b>Explanation</b>	Object is invalid or not available is a default error message for a missing attribute.
<b>Action</b>	Report the error.
<b>CMPUMIE0054</b>	<b>Can't create UMMonitoringContext with null UMInputContext</b>
<b>Explanation</b>	There is code trying to create a UMMonitoringContext with null UMInputContext
<b>Action</b>	Report the error
<b>CMPUMIE0055</b>	<b>User not authorized on this node. user:{0}, sessionAttributes:{1}</b>
<b>Explanation</b>	The User specified to connect to the realm is not authorized for operations on this node. Attaches user and sessionAttributes
<b>Action</b>	report the error
<b>CMPUMIE0056</b>	<b>Input context cannot be null</b>
<b>Explanation</b>	Input context cannot be null
<b>CMPUMIE0057</b>	<b>Can't find interface status for {0}</b>
<b>Explanation</b>	Can't find interface status for an Interface
<b>Action</b>	Report the error

<b>CMPUMIE0058</b>	<b>Can't find interface name for {0}</b>
<b>Explanation</b>	Can't find interface name for a interface
<b>Action</b>	Report the error
<b>CMPUMIE0059</b>	<b>Not Authorized to use nRealmNode methods</b>
<b>Explanation</b>	This exception will be thrown if a user connecting to UM is Not Authorized to use nRealmNode methods
<b>Action</b>	Report the error
<b>CMPUMIE0060</b>	<b>Can't set node to null in UMNNodeModel</b>
<b>Explanation</b>	Can't set node to null in UMNNodeModel
<b>Action</b>	Report the error
<b>CMPUMIE0061</b>	<b>Node does not exist in NodeFactory, path:{0}</b>
<b>Explanation</b>	Node does not exist in NodeFactory, path attached.
<b>Action</b>	Report the error
<b>CMPUMIE0062</b>	<b>Realm Node Not connected, path:{0}</b>
<b>Explanation</b>	Realm Node Not connected, the connection has expired or couldn't be established. path attached.
<b>Action</b>	Report the error
<b>CMPUMIE0063</b>	<b>Realm Node Not connected</b>
<b>Explanation</b>	Realm Node Not connected
<b>Action</b>	Report the error
<b>CMPUMIE0064</b>	<b>Exception occurred while getting Object Status, {0}</b>
<b>Explanation</b>	Exception occurred while getting Object Status, Exception attached.
<b>Action</b>	Report the error
<b>CMPUMIE0065</b>	<b>Can't get realm for node, path: {0}</b>
<b>Explanation</b>	Can't get realm for node, path attached
<b>Action</b>	Report the error

<b>CMPUMIE0066</b>	<b>Node is null during isConnected call in class: {0}</b>
<b>Explanation</b>	Node is null during isConnected call in class: {0}
<b>Action</b>	Report the error



# 10 Database Component Configurator Messages

---

## **CAN\_NOT\_RUN\_MIGRATE\_MSG – Can not run migrate to version {0}**

**Explanation** The user tried to migrate a database component that does not exist.

**Action** Make sure the database component exists using the catalog action before trying to migrate it.

## **CMP\_STORE\_INIT\_ERROR – Error initializing definition store instance**

**Explanation** The Database Component Configurator could not initialize all database component definitions.

**Action** Contact Software AG Global Support.

## **DCI\_INFO\_ERROR\_MSG Error in getting DCI about information.**

**Explanation** The user displayed the About information, but build information is missing.

**Action** Contact Software AG Global Support.

## **ERROR\_ENCODING Error in checking database encoding**

**Explanation** The checkEncoding action failed.

**Action** Make sure the the RDBMS is running.



# 11

## Deployer Messages

---

<b>1232</b>	<b>Repository-based deployment does not support deployment of {0} assets when part of a project that also contains either MWS, Optimize, or Business Rules assets.</b>
<b>Explanation</b>	Deployer does not support deployment of Universal Messaging assets when part of a project that also contains MWS, Optimize, or Business Rules assets.
<b>Action</b>	Remove the the Universal Messaging assets from the deployment set and update the deployment map accordingly. To deploy Universal Messaging assets, you must create a separate project that contains the Universal Messaging assets.
<b>1234</b>	<b>Deployer issued the following exception while attempting to compile the package: "{0}"</b>
<b>Explanation</b>	Deployer invoked the <code>wm.server.packages:compilePackage</code> service, and the <code>compilePackage</code> service returned an error.
<b>Action</b>	Verify the network connectivity between the Deployer server and each target Integration Server. Also, verify that the target Integration Servers are up and running. For more information about the error that the <code>compilePackage</code> service returned, see the deploy or simulation report.
<b>1240</b>	<b>Error occurred while attempting to compile the package {0}. Error details : {1}</b>
<b>Explanation</b>	This error message is shown in case of compilation errors while compiling java sources present in Integration Server package.
<b>Action</b>	Fix the compilation issue.

<b>185I</b>	<b>Successfully stored the password entry.</b>
<b>186I</b>	<b>Successfully retrieved the password.</b>
<b>187I</b>	<b>Successfully deleted the password entry.</b>
<b>188I</b>	<b>Successfully retrieved the list of password handles.</b>
<b>189I</b>	<b>Successfully updated the password entry.</b>
<b>190E</b>	<b>Existing password does not match the specified old password.</b>
<b>Explanation</b>	The specified old password does not match the password handle.
<b>Action</b>	Supply the correct existing password.
<b>191E</b>	<b>Password handle {0} does not exist.</b>
<b>Explanation</b>	An error occurred while retrieving the password entry for the password handle.
<b>Action</b>	Supply a valid password handle.
<b>192E</b>	<b>An error occurred while listing password handles.</b>
<b>Explanation</b>	An error occurred while getting the list of available password handles from the password store.
<b>Action</b>	Check the Integration Server logs for more details.
<b>193E</b>	<b>An error occurred while storing the password entry for handle {0}.</b>
<b>Explanation</b>	An error occurred while storing the entry for the specified handle and password values.
<b>Action</b>	Check the Integration Server logs for more details.
<b>194</b>	<b>An error occurred while deleting the password entry for handle {0}.</b>
<b>Explanation</b>	An error occurred while deleting the password entry for the supplied password handle.
<b>Action</b>	Check the Integration Server logs for more details.

<b>195E</b>	<b>The current user is not authorized to access password store operations.</b>
<b>Explanation</b>	Only an authorized user can perform create/delete/update/fetch operations on password stores.
<b>Action</b>	Obtain the proper authorization.
<b>DEP.0000.1205E</b>	<b>Repository-based deployment does not support the simulate operation for the mapped target servers.</b>
<b>Explanation</b>	Repository-based projects do not support simulate operations for the mapped target servers.
<b>Action</b>	Perform Deploy operation.
<b>DEP.0001.0002E</b>	<b>Deployer could not connect to server aliases {0}. Make sure the server alias information is correct and the server is running.</b>
<b>Explanation</b>	Deployer could not connect to the specified server when executing the CreateBuild command-line script.
<b>Action</b>	Make sure the connection information specified to the script is correct and that the server is running.
<b>DEP.0001.0003E</b>	<b>You are not authorized to extract the {0} project. Ask an administrator or user that has build authorization for the project to perform this task, or ask an administrator to update the authorization for the specified project to give you build authorization.</b>
<b>Explanation</b>	You do not have build authority for the specified project.
<b>Action</b>	Ask an administrator or user that has build authorization for the project to perform this task or ask an administrator to update the authorization for the specified project to give you build authorization.
<b>DEP.0001.0005E</b>	<b>Error checking authorization: {0}. Make sure the service exists and the permissions for the service are adequate to allow execution of the service.</b>
<b>Explanation</b>	An error occurred while invoking the wm.deployer.authorization:isAuthorized service on the Integration Server that is running Deployer.
<b>Action</b>	Make sure the service exists and the permissions for the service are adequate to allow execution of the service.
<b>DEP.0001.0006E</b>	<b>Error writing project file into build file {0}. Make sure there is sufficient disk space, memory, and operating system privileges.</b>
<b>Explanation</b>	An error occurred while trying to write the project file in the build archive file.
<b>Action</b>	Make sure there is sufficient disk space, memory, and that you have the proper operating system privileges.

<b>DEP.0001.0007E</b>	<b>Error writing properties file into build file {0}. Ensure that the project name was correctly specified and that there is sufficient disk space, memory, and operating system privileges.</b>
<b>Explanation</b>	An error occurred while attempting to write the build properties file in the build archive file.
<b>Action</b>	Ensure there is sufficient disk space, memory, and operating system privileges.
<b>DEP.0001.0008E</b>	<b>Error closing build file {0}. Make sure there is sufficient disk space, memory, and operating system privileges to close the build file.</b>
<b>Explanation</b>	An error occurred while attempting to close the build file.
<b>Action</b>	Make sure there is sufficient disk space, memory, and operating system privileges to close the build file.
<b>DEP.0001.0009E</b>	<b>Error creating build report {0}. Make sure there is sufficient disk space, memory, and operating system privileges to create a build report.</b>
<b>Explanation</b>	An error occurred when attempting to create a build report.
<b>Action</b>	Make sure there is sufficient disk space, memory, and operating system privileges to create a build report.
<b>DEP.0001.0010E</b>	<b>Error during extraction: {0}</b>
<b>Explanation</b>	An error occurred while attempting to create a build for a project. The extraction error can be any error that occurred when attempting to create a build. This error can be caused by an object that is listed in the project, but does not exist on the source system.
<b>Action</b>	Ensure that all objects listed in the project exist on the source system.
<b>DEP.0001.0011E</b>	<b>Error extracting IS package {0}: {1}. Make sure the service exists and that the permissions are adequate to allow execution of the service.</b>
<b>Explanation</b>	An error occurred while invoking the <code>wm.deployer.resource.extractor.is:extractPackage</code> service.
<b>Action</b>	Make sure the service exists and that the permissions are adequate to allow execution of the service.
<b>DEP.0001.0012E</b>	<b>Error extracting IS ACL(s) on source system {0}: {1}. Make sure the service exists and the permissions are adequate to allow execution of the service.</b>
<b>Explanation</b>	An error occurred while invoking the <code>wm.deployer.resource.extractor.is:extractAcls</code> service on the specified source system.
<b>Action</b>	Make sure the service exists and that the permissions are adequate to allow execution of the service.

<b>DEP.0001.0013E</b>	<b>Integration Server ACL {0} does not exist on the source system.</b>
<b>Explanation</b>	The identified asset does not exist on the source system.
<b>Action</b>	Either remove the asset from the project or add it to the source system.
<b>DEP.0001.0014E</b>	<b>Deployer encountered the following error while extracting Integration Server users from source system {0}: {1}</b>
<b>Explanation</b>	An error occurred while invoking the wm.deployer.resource.extractor.is:extractUsers service on the specified source system.
<b>Action</b>	Make sure the service exists and that you have the proper permissions to execute the service.
<b>DEP.0001.0015E</b>	<b>The Integration Server user account {0} does not exist on the source system. Either remove the user account from the project or create it on the source system.</b>
<b>Explanation</b>	The identified IS user account does not exist on the source system.
<b>Action</b>	Either remove the user account from the project or create it on the source system.
<b>DEP.0001.0016E</b>	<b>Deployer encountered the following error while extracting Integration Server groups from source system {0}: {1}</b>
<b>Explanation</b>	An error occurred while invoking the wm.deployer.resource.extractor.is:extractGroups service on the specified source system.
<b>Action</b>	Make sure the service exists and that the permissions are adequate to allow execution of the service.
<b>DEP.0001.0017E</b>	<b>The Integration Server group {0} does not exist on the source system. Either remove the group from the project or create the group on the source system.</b>
<b>Explanation</b>	The identified Integration Server group does not exist on the source system.
<b>Action</b>	Either remove the group from the project or create the group on the source system.
<b>DEP.0001.0018E</b>	<b>Deployer encountered the following error while extracting Integration Server ports from source system {0}: {1}</b>
<b>Explanation</b>	An error occurred while invoking the wm.deployer.resource.extractor.is:extractPorts service on the specified source system.
<b>Action</b>	Make sure the service exists and the permissions are adequate to allow execution of the service.

<b>DEP.0001.0020E</b>	<b>Deployer encountered the following error while extracting Integration Server scheduled service {0} ({1}) from source system {2}: {3}</b>
<b>Explanation</b>	An error occurred while invoking the pub.scheduler:getTaskInfo service on the specified source system.
<b>Action</b>	Make sure the service exists and the permissions are adequate to allow execution of the service. If the error message indicates that the scheduled service is not on the source system, either remove the scheduled service from the project or add it to the source system.
<b>DEP.0001.0021E</b>	<b>Deployer encountered the following error while extracting assets from Trading Networks from source system {0}: {1}</b>
<b>Explanation</b>	An error occurred while invoking the wm.tn.admin:exportData service on the specified source Trading Networks system.
<b>Action</b>	Make sure the source Trading Networks system is running, the service exists, and the permissions are adequate to allow execution of the service.
<b>DEP.0001.0035E</b>	<b>Error invoking service "{0}".</b>
<b>Explanation</b>	An error occurred invoking a service on the Integration Server that is running Deployer.
<b>Action</b>	Verify that the service exists and that the permissions are adequate to execute the service. For more information, see the Integration Server error message in the Integration Server error log.
<b>DEP.0001.0036E</b>	<b>An error occurred while invoking service "{0}" on system "{1}".</b>
<b>Explanation</b>	An error occurred while invoking a service on a remote system.
<b>Action</b>	Verify that the service exists and that the permissions are adequate to execute the service. For more information, see the Integration Server error message in the Integration Server error log.
<b>DEP.0001.0038E</b>	<b>Project {0} is empty; it does not contain any assets to extract. Use the Deployer user interface to add assets to the project.</b>
<b>Explanation</b>	The specified project does not contain any assets to extract.
<b>Action</b>	Use the Deployer user interface to add assets to the project.

<b>DEP.0001.0039E</b>	<b>The following source servers are currently unavailable: {0}. Check your network connection and make sure the source servers are running.</b>
<b>Explanation</b>	The source servers are not responding to a ping. To ping a server, Deployer executes services as follows: <ul style="list-style-type: none"> <li>- For an Integration Server system, Deployer uses the wm.server:ping service.</li> <li>- For a Trading Networks system, Deployer uses the wm.tn:ping service.</li> <li>- For any other system, Deployer uses the ping plug-in Web service.</li> </ul>
<b>Action</b>	Check the network connection and make sure the source servers are running.
<b>DEP.0001.0041E</b>	<b>Deployment set {0} has unresolved dependencies and could result in an incomplete deployment. Use the Deployer user interface to resolve the dependencies</b>
<b>Explanation</b>	The deployment set has unresolved dependencies and could result in an incomplete deployment.
<b>Action</b>	Use the Deployer user interface to resolve the dependencies.
<b>DEP.0001.0042E</b>	<b>Integration Server package files {0} do not exist. Use the Deployer user interface to verify and edit the list of files for the package.</b>
<b>Explanation</b>	The list of files specified for the package do not exist.
<b>Action</b>	Use the Deployer user interface to verify and edit the list of files for the package.
<b>DEP.0001.0043E</b>	<b>Integration Server package {0} does not exist on the source system. Either remove the package from the project or add it to the source system.</b>
<b>Explanation</b>	The identified Integration Server package does not exist on the source system.
<b>Action</b>	Either remove the package from the project or add it to the source system.
<b>DEP.0001.0044E</b>	<b>Deployer encountered the following error while extracting assets from {0} on source system {1}: {2}</b>
<b>Explanation</b>	An error occurred while invoking the Deployer plug-in web service getObjects on the specified source system.
<b>Action</b>	Make sure the source system is running, the service exists, and the permissions are adequate to execute the service.

<b>DEP.0001.0045E</b>	<b>Build file {0} does not contain a properties file. Build cannot load because the file is incomplete. Make sure the build file is not corrupted and has not been manually updated.</b>
<b>Explanation</b>	Build cannot load because the file is incomplete.
<b>Action</b>	Make sure the build file is not corrupted and has not been manually updated.
<b>DEP.0001.0053E</b>	<b>Integration Server port {0} does not exist on the source system and was not extracted into the build. Make sure the port exists in the source system.</b>
<b>Explanation</b>	The Integration Server port was not extracted into the build.
<b>Action</b>	Make sure the port exists in the source system.
<b>DEP.0001.0054E</b>	<b>The Integration Server scheduled service does not exist on source system {0}: {1}</b>
<b>Explanation</b>	The scheduled service does not exist on the source server.
<b>Action</b>	Either remove the scheduled service from the project or add it to the source system.
<b>DEP.0001.0068E</b>	<b>Deployer encountered the following error while extracting Integration Server package {0} node ACLs: {1}</b>
<b>Explanation</b>	Error when executing the <code>wm.deployer.resource.gui.IS:getTypedPackageContents</code> service.
<b>Action</b>	Make sure the service exists on the Integration Server and the user has the necessary privileges to execute the service.
<b>DEP.0001.0069E</b>	<b>Error writing to the build file {0}. Make sure the build file exists, that it has read/write permission, and that the file system has adequate space.</b>
<b>Explanation</b>	An error occurred while trying to write to the build file.
<b>Action</b>	Read the error message to determine the possible causes. Make sure the build file exists, that it has read/write permission, and there is adequate space for it on the file system.
<b>DEP.0001.0070E</b>	<b>Trading Networks field group {0} does not exist on the specified source Trading Networks system. Either remove the profile field group from the project or add it to the source Trading Networks system.</b>
<b>Explanation</b>	The identified Trading Networks profile field group does not exist on the specified source Trading Networks system.
<b>Action</b>	Either remove the profile field group from the project or add it to the source Trading Networks system.

<b>DEP.0001.0071E</b>	<b>Trading Networks field definition {0} does not exist on the source Trading Networks system. Either remove the profile field definition from the project or add it to the source Trading Networks system.</b>
<b>Explanation</b>	The identified Trading Networks profile field definition does not exist on the source Trading Networks system.
<b>Action</b>	Either remove the profile field definition from the project or add it to the source Trading Networks system.
<b>DEP.0001.0072E</b>	<b>Trading Networks Profile {0} does not exist on the source Trading Networks system. Either remove the profile from the project or add it to the source Trading Networks system.</b>
<b>Explanation</b>	The identified Trading Networks profile does not exist on the source Trading Networks system.
<b>Action</b>	Either remove the profile from the project or add it to the source Trading Networks system.
<b>DEP.0001.0073E</b>	<b>Trading Networks TPA {0} does not exist on the source Trading Networks system. Either remove the TPA from the project or add it to the source Trading Networks system.</b>
<b>Explanation</b>	The identified Trading Networks trading partner agreement (TPA) does not exist on the source Trading Networks system.
<b>Action</b>	Either remove the TPA from the project or add it to the source Trading Networks system.
<b>DEP.0001.0074E</b>	<b>Trading Networks document attribute {0} does not exist on the source Trading Networks system. Either remove the document attribute from the project or add it to the source Trading Networks system.</b>
<b>Explanation</b>	The identified Trading Networks document attribute does not exist on the source Trading Networks system.
<b>Action</b>	Either remove the document attribute from the project or add it to the source Trading Networks system.
<b>DEP.0001.0075E</b>	<b>Trading Networks document type {0} does not exist on the source Trading Networks system. Either remove the Trading Networks document type from the project or add it to the source Trading Networks system.</b>
<b>Explanation</b>	The identified Trading Networks document type does not exist on the source Trading Networks system.
<b>Action</b>	Either remove the Trading Networks document type from the project or add it to the source Trading Networks system.

**DEP.0001.0076E**      **Trading Networks processing rule {0} does not exist on the Trading Networks source system. Either remove the processing rule from the project or add it to the source Trading Networks system.**

**Explanation**      The identified Trading Networks processing rule does not exist on the Trading Networks source system.

**Action**            Either remove the processing rule from the project or add it to the source Trading Networks system.

**DEP.0001.0077E**      **Trading Networks external ID type {0} does not exist on the source Trading Networks system. Either remove the external ID type from the project or add it to the source Trading Networks system.**

**Explanation**      The identified Trading Networks external ID type does not exist on the source Trading Networks system.

**Action**            Either remove the external ID type from the project or add it to the source Trading Networks system.

**DEP.0001.0078E**      **Trading Network contact type {0} does not exist on the source Trading Networks system. Either remove the contact type from the project or add it to the source Trading Networks system.**

**Explanation**      The identified Trading Networks contact type does not exist on the source Trading Networks system.

**Action**            Either remove the contact type from the project or add it to the source Trading Networks system.

**DEP.0001.0079E**      **Trading Networks binary type {0} does not exist on the source Trading Networks system. Either remove the binary type from the project or add it to the source Trading Networks system.**

**Explanation**      The identified Trading Networks binary type does not exist on the source Trading Networks system.

**Action**            Either remove the binary type from the project or add it to the source Trading Networks system.

**DEP.0001.0080E**      **Trading Networks profile group {0} does not exist on the source Trading Networks system. Either remove the profile group from the project or add it to the source Trading Networks system.**

**Explanation**      The identified Trading Networks profile group does not exist on the source Trading Networks system.

**Action**            Either remove the profile group from the project or add it to the source Trading Networks system.

---

<b>DEP.0001.0081E</b>	<b>Trading Networks extended field {0} for profile {1} does not exist on the source Trading Networks system for the specified profile. Either remove the extended field from the project or add it to the appropriate profile in the source Trading Networks system.</b>
<b>Explanation</b>	The identified Trading Networks extended field does not exist on the source Trading Networks system for the specified profile.
<b>Action</b>	Either remove the extended field from the project or add it to the appropriate profile in the source Trading Networks system.
<b>DEP.0001.0082E</b>	<b>Trading Networks security data item {0} does not exist on the source Trading Networks system. Either remove the security data item from the project or add it to the source Trading Networks system.</b>
<b>Explanation</b>	The identified Trading Networks security data item does not exist on the source Trading Networks system.
<b>Action</b>	Either remove the security data item from the project or add it to the source Trading Networks system.
<b>DEP.0001.0085W</b>	<b>Warning creating build {0}. See build report for details.</b>
<b>Explanation</b>	Deployer issued a warning while creating the build.
<b>Action</b>	Check the build report for details.
<b>DEP.0001.0087E</b>	<b>Deployer encountered the following error while extracting Integration Server extended settings from source system {0}: {1}</b>
<b>Explanation</b>	An error occurred while invoking the <code>wm.deployer.resource.extractor.is:extractExtendedSettings</code> service on the specified source system.
<b>Action</b>	Make sure the service exists and that the permissions are adequate to allow execution of the service.
<b>DEP.0001.0093</b>	<b>Trading Networks queue {0} does not exist on the source system. Either remove the asset from the project or add it to the source system.</b>
<b>Explanation</b>	The identified asset does not exist on the source system.
<b>Action</b>	Either remove the asset from the project or add it to the source system.

<b>DEP.0001.0094E</b>	<b>Integration Server extended setting {0} does not exist on the source server.</b>
<b>Explanation</b>	The indicated extended setting does not exist on the source server.
<b>Action</b>	Either remove the extended setting from the project or add the extended setting to the source server.
<b>DEP.0001.0109</b>	<b>TN processing rule {0} does not exist on the source system. Either remove the asset from the project or add it to the source system.</b>
<b>Explanation</b>	The identified asset does not exist on the source system.
<b>Action</b>	Either remove the asset from the project or add it to the source system.
<b>DEP.0001.0114</b>	<b>TN extended field {0} for profile {1} does not exist on the source system. Either remove the asset from the project or add it to the source system.</b>
<b>Explanation</b>	The identified asset does not exist on the source system.
<b>Action</b>	Either remove the asset from the project or add it to the source system.
<b>DEP.0001.0117</b>	<b>Cannot write to build directory: {0}. The Integration Server user does not have privileges to create or write to a file. Make sure the user has the correct privileges.</b>
<b>Explanation</b>	The Integration Server user does not have privileges to create or write to a file.
<b>Action</b>	Make sure the user has the correct privileges.
<b>DEP.0001.0118</b>	<b>Error writing checkpoint report: {0}. An error occurred while attempting to close the build file. Make sure there is sufficient disk space, memory, and operating system privileges.</b>
<b>Explanation</b>	An error occurred while attempting to close the build file.
<b>Action</b>	Make sure there is sufficient disk space, memory, and operating system privileges.
<b>DEP.0001.0119</b>	<b>IS scheduled service {0} ({1}) does not exist on the source server. Either remove the scheduled service from the project or add it to the source system.</b>
<b>Explanation</b>	The identified asset was not found on the source system.
<b>Action</b>	Either remove the asset from the project or add it to the source system.
<b>DEP.0001.0122</b>	<b>TN DIs {0} does not exist on the source server. Either remove the asset from the project or add it to the source system.</b>
<b>Explanation</b>	The identified asset does not exist on the source system.
<b>Action</b>	Either remove the asset from the project or add it to the source system.

<b>DEP.0001.0125</b>	<b>TN Fp {0} does not exist on the source system.</b>
<b>Explanation</b>	The identified asset does not exist on the source system.
<b>Action</b>	Either remove the asset from the project or add it to the source system.
<b>DEP.0001.0128</b>	<b>TN Archival Service {0} does not exist on the source system.</b>
<b>Explanation</b>	The identified asset does not exist on the source system.
<b>Action</b>	Either remove the asset from the project or add it to the source system.
<b>DEP.0001.0130</b>	<b>The Target Server/Group {0} is not currently available; skipping that Target Server/Group. Check your network connection, and verify that the Target Server/Group is running.</b>
<b>Explanation</b>	Deployer cannot ping a target server or some servers in a target group. This might occur because the servers in question are not running or because of network latency.
<b>Action</b>	Make sure that the servers in question are running.
<b>DEP.0001.0131</b>	<b>{0} {1} {2} does not exist on the source system.</b>
<b>Explanation</b>	The identified objects do not exist on the source system.
<b>Action</b>	Either remove the identified objects from the project or add them to the source system.
<b>DEP.0001.0133</b>	<b>Could not rebuild project {0} because the specific build in the project could not be rebuilt. See the Integration Server logs for more information.</b>
<b>Explanation</b>	Deployer could not migrate the project because the specific build in the project could not be rebuilt.
<b>Action</b>	See the Integration Server logs for more information.
<b>DEP.0001.0135</b>	<b>Deployer could not migrate project {0}. Make sure all source servers specified in project {0} are running. See the Integration Server logs for more information.</b>
<b>Explanation</b>	Deployer could not migrate the project.
<b>Action</b>	See the Integration Server logs for more information.
<b>DEP.0001.0136</b>	<b>Could not migrate projects data. See the Integration Server logs for more information.</b>
<b>Explanation</b>	Deployer was unable to migrate the project data.
<b>Action</b>	See the Integration Server logs for more information.

<b>DEP.0001.0139</b>	<b>Some of the projects could not be migrated. See the Integration Server logs for more information.</b>
<b>Explanation</b>	Deployer could not migrate all projects.
<b>Action</b>	See the Integration Server logs for more information.
<b>DEP.0001.0144E</b>	<b>The source servers hosting the deployment sets are from different releases. Make sure all source servers are from the same release.</b>
<b>Explanation</b>	Deployer issues this message and ends the build process when you modify the version of the source server alias for existing projects.
<b>Action</b>	Make sure all source servers are from the same release.
<b>DEP.0001.0145E</b>	<b>Deployer did not migrate the following target groups because the alias servers were not migrated to the correct version. Change the version of the server alias or target group so that the two match.</b>
<b>Explanation</b>	You migrated a target group to a different version than that of its server alias.
<b>Action</b>	Change the version of the server alias or target group so that the two match.
<b>DEP.0001.0153W</b>	<b>Marked {0} {1} for deletion. The indicated server, or the network connection to that server, is not available. Alternatively, the command-line values for user and password might not be valid on the indicated server. Confirm that the server is running and reachable, and that the user/password values are valid.</b>
<b>Explanation</b>	The indicated server, or the network connection to that server, is not available. Alternatively, the command-line values for user and password might not be valid on the indicated server.
<b>Action</b>	Confirm that the server is running and reachable, and that the user/password values are valid.
<b>DEP.0001.0154W</b>	<b>Streamed file {0} for file {1} in deployment set {3} not found. The Integration Server, or the network connection to that server, might be shut down. Confirm that the server is running and that the network connection is up.</b>
<b>Explanation</b>	The Integration Server, or the network connection to that server, might be shut down.
<b>Action</b>	Confirm that the server is running and that the network connection is up.
<b>DEP.0001.0155</b>	<b>Error while reading streamed file {0} for file {1} in deployment set {3}. See the Integration Server logs for more information.</b>
<b>Explanation</b>	An error occurred while reading the streamed file.
<b>Action</b>	See the Integration Server logs for more information.

<b>DEP.0001.0156</b>	<b>Deployer could not connect to the source server aliases specified in the project. Deployer could not rebuild and upgrade the project {0}. Make sure the server alias information is correct and the servers are running.</b>
<b>Explanation</b>	Deployer could not migrate the project because the specific build in the project could not be rebuilt.
<b>Action</b>	Make sure the source servers for the deployment set in the build are running.
<b>DEP.0001.0158E</b>	<b>Build name {0} contains one or more of the following invalid characters: # &amp; # ; @ ^ ! &amp; # 3 8 ; * : \$ / \ ` ' ; , ~ + = &amp; g t ; &amp; l t ; " Remove the invalid characters from the build name.</b>
<b>Explanation</b>	The build name contains one or more of the following invalid characters: # & @ ^ ! % * : \$ / \ ` ' ; , ~ + = > < \ "
<b>Action</b>	Remove the invalid characters from the build name.
<b>DEP.0001.0159E</b>	<b>Deployer could not migrate the Deployer settings. See the Integration Server logs for more information.</b>
<b>Explanation</b>	Deployer encountered an error while migrating the Deployer settings.
<b>Action</b>	Check the Integration Server logs for more information.
<b>DEP.0001.0161E</b>	<b>Deployer could not migrate settings.</b>
<b>Explanation</b>	Deployer did not receive the settings during migration.
<b>Action</b>	Reload the Deployer package.
<b>DEP.0002.0004E</b>	<b>Project {0} does not contain a deployment set named {1}.</b>
<b>Explanation</b>	The Deployer user interface referenced a deployment set name that is not recognized by the Deployer. Another Deployer session might have deleted this deployment set, or the project might be corrupted on the file system.
<b>Action</b>	Refresh the page and try again. If the same error occurs, this project might be corrupted on the file system and you might have to discard it.
<b>DEP.0002.0006E</b>	<b>Deployer did not find a dependency on component {0} was found.</b>
<b>Explanation</b>	The Deployer user interface attempted to delete a dependency that is not recognized by Deployer. Another Deployer session might have deleted the dependency, or the project might be corrupted on the file system.
<b>Action</b>	Refresh the page and try again. If the same error occurs, this project might be corrupted on the file system and you might have to discard it.

<b>DEP.0002.0007E</b>	<b>Deployer cannot access server alias {0} in deployment set {1}.</b>
<b>Explanation</b>	The Deployer user interface referenced a source server name that is not recognized by Deployer. Another Deployer session might have deleted the source server from the project, or the project might be corrupted on the file system.
<b>Action</b>	Refresh the page and try again. If the same error occurs, this project might be corrupted on the file system and you might have to discard it.
<b>DEP.0002.0008E</b>	<b>Package {0} from server alias {1} does not exist in deployment set {2}.</b>
<b>Explanation</b>	The Deployer user interface referenced a package or server name that is not recognized by Deployer. Another Deployer session might have deleted the package or server name from the project, or the project might be corrupted on the file system.
<b>Action</b>	Refresh the page and try again. If the same error occurs, this project might be corrupted on the file system and you might have to discard it.
<b>DEP.0002.0009E</b>	<b>Server {0} already exists in deployment set {1} as a non-Integration Server server. You cannot add Integration Server objects to it.</b>
<b>Explanation</b>	You passed an incorrect value for the parameter.
<b>Action</b>	Avoid executing the service outside of the Deployer user interface.
<b>DEP.0002.0010E</b>	<b>Package {0} already exists in deployment set {1} as a complete package. Cannot add package components or files to it.</b>
<b>Explanation</b>	You attempted to add package components to a deployment set that already exists on the deployment set.
<b>Action</b>	If you want to include the entire package in a deployment set, no action is necessary because it is already included. If you want the deployment set to contain only a partial package, first remove the entire package from the deployment set before trying to add specific package components.
<b>DEP.0002.0011E</b>	<b>Project {0} already contains a deployment set named {1}. Use a different name for the new deployment set.</b>
<b>Explanation</b>	You attempted to add a deployment set to the specified project, but the project already has a deployment set that uses the same name that you specified.
<b>Action</b>	Use a different name for the new deployment set.

<b>DEP.0002.0012E</b>	<b>Project name {0} contains illegal characters.</b>
<b>Explanation</b>	The project name contains spaces or one or more of the following invalid characters: # & @ ^ ! % * : \$ / \ \ ' ; , ~ + = > < \ "
<b>Action</b>	Specify another name for the project that does not include the illegal characters.
<b>DEP.0002.0013E</b>	<b>Could not complete project copy due to file system error. Check your Integration Server's disk space. If you believe there is sufficient space, try the copy again. As a final option, manually recreate the project.</b>
<b>Explanation</b>	Deployer encountered an error writing the project to disk.
<b>Action</b>	Check your Integration Server's disk space. If you believe there is sufficient space, try the copy again. As a final option, manually recreate the project.
<b>DEP.0002.0014E</b>	<b>Project {0} already exists. Use a different, unique name for the new project.</b>
<b>Explanation</b>	A project with the name you specified already exists.
<b>Action</b>	Use a different, unique name for the new project.
<b>DEP.0002.0015E</b>	<b>Deployer was unable to invoke service {0}.</b>
<b>Explanation</b>	Deployer was unable to find the specified Integration Server service.
<b>Action</b>	Determine whether a required Integration Server package is disabled, missing, or whether parts are missing. Check for the following packages: WmDeployer, WmAdmin, WmRoot, WmDeployerResource, and WmModeler.
<b>DEP.0002.0016E</b>	<b>Unable to delete build {0}. The build file is probably in use. This file exists in the &lt;serverDirectory&gt;/packages/WmDeployer/persist/projects/&lt;YourProjectName&gt;/builds directory. Locate the process that is accessing this file and stop it. Then try to delete the build again.</b>
<b>Explanation</b>	Deployer was unable to delete the specified build file.
<b>Action</b>	The build file is probably in use. This file exists in the <serverDirectory>/packages/WmDeployer/persist/projects/<YourProjectName>/builds directory. Locate the process that is accessing this file and stop it. Then try to delete the build again.
<b>DEP.0002.0017E</b>	<b>Project {0} does not contain a build named {1}.</b>
<b>Explanation</b>	The Deployer user interface referenced a build name that is not recognized by Deployer. Another Deployer session might have deleted this build, or the project might be corrupted on the file system.
<b>Action</b>	Refresh the page and try again. If the same error occurs, this project might be corrupted on the file system and you might have to discard it.

<b>DEP.0002.0018E</b>	<b>Deployer could not load build {0}.</b>
<b>Explanation</b>	The build file is corrupted.
<b>Action</b>	Use Windows Explorer to locate the <serverDirectory>\packages\WmDeployer\persist\projects\<YourProjectName>\builds directory and manually remove the corrupted build file. Then use Deployer to rebuild.
<b>DEP.0002.0019E</b>	<b>Deployment map {0} already exists in project {1}.</b>
<b>Explanation</b>	You attempted to create a deployment map with the same name as an existing deployment map.
<b>Action</b>	Use a different name for the new deployment map.
<b>DEP.0002.0020E</b>	<b>Deployment map {0} does not exist in project {1}.</b>
<b>Explanation</b>	The Deployer user interface referenced a deployment map name that is not recognized by the Deployer. Another Deployer session might have deleted this deployment map, or the project on the file system might be corrupted.
<b>Action</b>	Refresh the page and try again. If the same error occurs, this project might be corrupted on the file system and you might have to discard it.
<b>DEP.0002.0021E</b>	<b>Deployer could not load deployment map {0} from project {1}.</b>
<b>Explanation</b>	The deployment map file is corrupted.
<b>Action</b>	Use Windows Explorer to locate the <serverDirectory>\packages\WmDeployer\persist\projects\<YourProjectName>\targets directory and manually remove your deployment candidate file. Then use Deployer to recreate it.
<b>DEP.0002.0026E</b>	<b>Deployer could not save deployment map {0}.</b>
<b>Explanation</b>	Deployer encountered an error writing to disk.
<b>Action</b>	Check your Integration Server's disk space. If you believe there should be sufficient space, try to save again. If this is not successful, try one or both of the following:  Restart the server.  Recreate the deployment map.

---

<b>DEP.0002.0028E</b>	<b>Deployment set {0} is not mapped to target {1}.</b>
<b>Explanation</b>	The Deployer user interface referenced a deployment set name that is not recognized by the Deployer. Another Deployer session might have deleted this deployment set, or the project might be corrupted on the file system.
<b>Action</b>	Refresh the page and try again. If the same error occurs, this project might be corrupted on the file system and you might have to discard it.
<b>DEP.0002.0031</b>	<b>Could not invoke service {0} remotely.</b>
<b>Explanation</b>	An integration service invocation failed.
<b>Action</b>	Ensure that the Integration Server is running and that the service exists on that Integration Server. Also ensure that you have the proper privileges to execute the service.
<b>DEP.0002.0032E</b>	<b>Server Alias cannot be blank.</b>
<b>Explanation</b>	You left the required Server Alias field blank.
<b>Action</b>	Specify a value for the Server Alias field and try again.
<b>DEP.0002.0054E</b>	<b>The value specified for the task parameter is not valid.</b>
<b>Explanation</b>	You passed an incorrect value for the task parameter. The task must be either DEFINE, MAP, EXTRACT, DEPLOY, or VIEW.
<b>Action</b>	Avoid executing the service outside of the Deployer user interface.
<b>DEP.0002.0058E</b>	<b>Deployer cannot perform export operation because the file {0} already exists under WmDeployer/outbound</b>
<b>Explanation</b>	You attempted to export a build with the same name as an existing build.
<b>Action</b>	Use a different name when you export the build.
<b>DEP.0002.0059E</b>	<b>The Deployer import map file {0} is not accessible or does not exist.</b>
<b>Explanation</b>	You attempted to import a build that does not exist.
<b>Action</b>	Refresh the Import Build page and try again.
<b>DEP.0002.0060E</b>	<b>User is not authorized to export builds from project {0}.</b>
<b>Explanation</b>	You are not authorized to export builds for the specified project. You must have build authorization for the project.
<b>Action</b>	Ask an administrator or user that has build authorization for the project to perform this task or have an administrator assign you build authorization.

- DEP.0002.0061E**      **User is not authorized to import builds to project {0}.**  
**Explanation**      You are not authorized to import builds for the specified project. You must have build authorization for the project.  
**Action**              Ask an administrator or user that has build authorization for the project to perform this task or have an administrator assign you build authorization.
- DEP.0002.0064E**      **Deployment set {0} already exists in project {1}.**  
**Explanation**      You attempted to create a deployment set in a project that already contains a deployment set of the same name.  
**Action**              Use a different name for the new deployment set.
- DEP.0002.0065E**      **Deployer encountered an error and did not save deployment {0}.**  
**Explanation**      Deployer encountered an error while writing to disk.  
**Action**              Check your Integration Server's disk space. If you believe there should be sufficient space, try to save again. If Deployer still cannot save the deployment, restart the server or recreate the deployment candidate.
- DEP.0002.0067E**      **Deployment candidate {0} does not exist in project {1}.**  
**Explanation**      The Deployer user interface referenced a deployment candidate that is not recognized by Deployer. Another Deployer session might have deleted the deployment candidate, or the project might be corrupted on the file system.  
**Action**              Refresh the page and try again. If the same error occurs, this project might be corrupted on the file system and you might have to discard it.
- DEP.0002.0068E**      **Unable to delete deployment map {0}.**  
**Explanation**      Deployer was unable to delete the specified deployment map file.  
**Action**              The deployment map file is probably in use. This file exists in the <serverDirectory>\packages\WmDeployer\persist\projects\<YourProjectName>\targets directory. Locate the process that is accessing this file and stop it. Then try to delete the deployment candidate again.
- DEP.0002.0069E**      **Unable to delete deployment candidate {0}.**  
**Explanation**      Deployer was unable to delete the deployment candidate file.  
**Action**              The deployment candidate file is probably in use. This file exists in the <serverDirectory>\packages\WmDeployer\persist\projects\<YourProjectName>\deployments directory. Locate the process that is accessing this file and stop it. Then try to delete the deployment candidate again.

<p>DEP.0002.0072E</p> <p><b>Explanation</b></p> <p><b>Action</b></p>	<p><b>Deployer could not load deployment {0} from project {1}.</b></p> <p>The deployment candidate file is corrupted.</p> <p>Use Windows Explorer to locate to the &lt;serverDirectory&gt;\packages\WmDeployer\persist\projects\&lt;YourProjectName&gt;\deployments directory and manually remove the deployment candidate file. Then use Deployer to recreate it.</p>
<p>DEP.0002.0073E</p> <p><b>Explanation</b></p> <p><b>Action</b></p>	<p><b>Deployer could not add component {0} of type {1}.</b></p> <p>Deployer does not recognize the specified Integration Server component.</p> <p>Rather than attempting to add the component to the project, add the files that comprise the component (example, "ns" directory). You can also try adding the entire package rather than individual components of the package.</p>
<p>DEP.0002.0075E</p> <p><b>Explanation</b></p> <p><b>Action</b></p>	<p><b>When you specify "deploymentName", you cannot specify additional arguments .</b></p> <p>You specified incorrect arguments when running the deploy.bat or deploy.sh script.</p> <p>The deploy script can either reference an existing deployment candidate or create a new deployment candidate. When you specify the "deploymentName" argument to reference an existing deployment candidate do not supply other arguments.</p>
<p>DEP.0002.0076E</p> <p><b>Explanation</b></p> <p><b>Action</b></p>	<p><b>When you specify "newDeploymentName", "buildName" and "deploymentMapName" are required.</b></p> <p>You specified incorrect arguments for the deploy.bat or deploy.sh script.</p> <p>You can specify the deploy script to either reference an existing deployment candidate or to create a new deployment candidate. If you use the "newDeploymentName" argument to create a new deployment candidate, you must also specify the "buildName" and "deploymentMapName" arguments.</p>
<p>DEP.0002.0077E</p> <p><b>Explanation</b></p> <p><b>Action</b></p>	<p><b>You are not authorized to modify the project definition.</b></p> <p>You are not authorized to define a project.</p> <p>Ask an administrator or user that has define authorization to perform the action for you or have an administrator assign you define authorization.</p>
<p>DEP.0002.0078E</p> <p><b>Explanation</b></p> <p><b>Action</b></p>	<p><b>You are not authorized to modify the project target mapping.</b></p> <p>You are not authorized to map a project.</p> <p>Ask an administrator or user that has map authorization to perform the action for you or have an administrator assign you map authorization.</p>

- DEP.0002.0079E**      **You are not authorized to modify project deployments.**  
**Explanation**      You are not authorized to deploy a project.  
**Action**              Ask an administrator or user that has deploy authorization to perform the action for you or have an administrator assign you deploy authorization.
- DEP.0002.0080E**      **You are not authorized to remove project builds.**  
**Explanation**      You are not authorized to build a project.  
**Action**              Ask an administrator or user that has build authorization to perform the action for you or have an administrator assign you build authorization.
- DEP.0002.0081E**      **Deployer cannot delete build {0} because it is being used by deployment candidate {1}.**  
**Explanation**      You attempted to delete a build that is referenced by a deployment candidate.  
**Action**              Delete or modify the deployment candidate that references the build or do not delete this build.
- DEP.0002.0082E**      **Deployer cannot delete deployment map {0} because it is being used by deployment candidate {1}.**  
**Explanation**      You attempted to delete a deployment map that is referenced by another deployment candidate.  
**Action**              Delete or modify the deployment candidate that references the deployment map.
- DEP.0002.0083E**      **Deployer encountered the following exception while parsing project {0}: {1}**  
**Explanation**      An exception occurred while trying to load the project. The exception be due to an input/output error.  
**Action**              Review the exception message to determine the cause of the error.
- DEP.0002.0085E**      **Deployer could not add package {0} to the deployment set.**  
**Explanation**      Deployer was unable to determine which components in the package were available for variable substitution. The problem might be that the source Integration Server was temporarily unavailable.  
**Action**              Check the Integration Server Error log to determine the reason that Deployer was unable to access information about the package components.

<b>DEP.0002.0086E</b>	<b>Deployment map {0} in project {1} is corrupted and must be removed. It references deployment set {2} which does not exist.</b>
<b>Explanation</b>	The deployment map file is corrupted.
<b>Action</b>	Use Windows Explorer to locate the <serverDirectory>\packages\WmDeployer\persist\projects\<YourProjectName>\targets directory and manually remove the deployment map file. Then use Deployer to recreate it.
<b>DEP.0002.0087E</b>	<b>Deployer cannot remove deployment set {0}. It is referenced by deployment map {1}.</b>
<b>Explanation</b>	You attempted to delete a deployment set that is being referenced by a deployment map.
<b>Action</b>	Perform one of the following: <ul style="list-style-type: none"> <li>- Delete or modify the deployment map that references the deployment set.</li> <li>- Do not delete the deployment set.</li> </ul>
<b>DEP.0002.0089E</b>	<b>Deployer could not save adapter connection metadata for project {0}</b>
<b>Explanation</b>	The project is corrupted.
<b>Action</b>	Retry the last action taken on the deployment project. If the action is unsuccessful, create a new project.
<b>DEP.0002.0092E</b>	<b>Deployer cannot update package {0} version in the deployment set.</b>
<b>Explanation</b>	Deployer was unable to access the specified package on the server.
<b>Action</b>	Retry the action. If the action is unsuccessful, investigate why Deployer is unable to locate the specified package on the remote server. If the package appears to be available on the remote server, shut down the Deployer window (as well as the window that launched Deployer) and restart the browser.
<b>DEP.0002.0093E</b>	<b>Both the {0} and the {1} Deployer plug-ins contain the Deployer plug-in type {2}.</b>
<b>Explanation</b>	More than one plug-in for the same type of deployment asset has been detected. This indicates a problem with the configuration of the Deployer.
<b>Action</b>	Update the configuration of the Deployer to remove extraneous plug-ins for the same type of deployment asset. Alternatively, you can uninstall, then reinstall Deployer.

<b>DEP.0002.0096E</b>	<b>Deployer is currently unable to access Trading Networks system: {0}.</b>
<b>Explanation</b>	No data was returned from the specified Trading Networks server. This indicates that the Trading Networks server is not accessible.
<b>Action</b>	Ensure that the Trading Networks server is accessible over the network and that you have correctly configured the server alias.
<b>DEP.0002.0097E</b>	<b>Deployer is currently unable to access target system: {0}.</b>
<b>Explanation</b>	The target Trading Networks Server is not available. The server did not respond to a server ping.
<b>Action</b>	Ensure that the Trading Networks Server is accessible over the network and that you have correctly configured the server alias for the Trading Networks server.
<b>DEP.0002.0098E</b>	<b>Deployer cannot check target cluster configuration. The target is missing the Deployer resource package. This can be installed from the Servers &gt; IS &amp; TN screen.</b>
<b>Explanation</b>	An error occurred while Deployer attempted to access a service on the target WmDeployerResource package.
<b>Action</b>	Install the current version of WmDeployerResource package on the target server.
<b>DEP.0002.0099E</b>	<b>Cluster node details not available.</b>
<b>Explanation</b>	An error occurred when the Deployer attempted to access a service on the target WmDeployerResource package.
<b>Action</b>	Install the current version of the WmDeployerResource package on the target server. Also, ensure that the target server is running and that Deployer can access it over the network.
<b>DEP.0002.0101E</b>	<b>The source servers hosting the deployment sets are different versions.</b>
<b>Explanation</b>	The source servers hosting the deployment sets are different versions.
<b>Action</b>	Modify the source servers to use the same versions.
<b>DEP.0002.0102E</b>	<b>The target server or target group is a different version than the project source. Select servers that use the same version.</b>
<b>Explanation</b>	Deployer issues this error message when you add a target server or target group to a deployment map and the version of the target server or group is different than that of the project source server.
<b>Action</b>	Use a target server or target group that is the same version as the project source server.

<b>DEP.0002.0106E</b>	<b>Dependencies may not contain the \$ character.</b>
<b>Explanation</b>	You added a manual dependency that contains the \$ character.
<b>Action</b>	Remove the \$ character.
<b>DEP.0002.0109E</b>	<b>Failed to install resource package on Integration Server {0}: {1}</b>
<b>Explanation</b>	Deployer is trying to install the WmDeployerResource package on the IntegrationServer indicated by <serverName>, but the attempt failed. The <exceptionMessage> provides more information.
<b>Action</b>	Make sure the server is running and connected to the network, and that the system has sufficient disk space, memory, and necessary operating system privileges.
<b>DEP.0002.0110E</b>	<b>Deployer could not locate resource package {0}. Make sure the WmDeployerResource package has been installed on the Integration Server that hosts Deployer and that the system has sufficient disk space, memory, and the necessary operating system privileges.</b>
<b>Explanation</b>	An error occurred when the Deployer tried to locate the WmDeployerResource package. The <exceptionMessage> provides information about why that attempt failed. The resource package might not exist on your Integration Server or might require more memory.
<b>Action</b>	Make sure the WmDeployerResource package has been installed on the Integration Server that hosts Deployer and that the system has sufficient disk space, memory, and the necessary operating system privileges.
<b>DEP.0002.0112</b>	<b>Unable to import the XML document {0} nl{1}. The XML file you passed in either the import map or the import varsub flow is invalid. Correct the XML file as necessary.</b>
<b>Explanation</b>	The XML file you passed in either the import map or the import varsub flow is invalid.
<b>Action</b>	Correct the XML file as necessary.
<b>DEP.0002.0114</b>	<b>Input XML varsub information is not valid. It might contain an asset type for which varsub is not supported. Validate the XML file against the wm.deployer.flows:DeploymentMap_Definition or wm.deployer.flows:Varsub_Definition XSD.</b>
<b>Explanation</b>	The varsub XML file is not valid. It might contain an asset type for which varsub is not supported. The assets for which varsub is supported are AdapterConnection, ScheduledService, ExtendedSettings, Port, AdapterNotification, AdapterListener, eform, and webServiceDescriptor.
<b>Action</b>	Validate the XML file against the wm.deployer.flows:DeploymentMap_Definition or wm.deployer.flows:Varsub_Definition XSD.

<b>DEP.0002.0116</b>	<b>Exporting of map {0} failed; the exported map file already exists in the WmDeployer/replicate/inbound folder. Make a backup of the map file in another location, delete the map file from the inbound folder, and then export the map file again.</b>
<b>Explanation</b>	The exported map file already exists in the WmDeployer/replicate/inbound folder.
<b>Action</b>	Make a backup of the map file in another location, delete the map file from the inbound folder, and then export the map file again.
<b>DEP.0002.0118</b>	<b>Importing of map {0} failed. Make sure the <code>wm.deployer.gui.UITarget:addMapSetToProject</code> service exists and that the user has the necessary privileges for executing the service, and then try again.</b>
<b>Explanation</b>	This error might occur for no specific reason.
<b>Action</b>	Make sure the <code>wm.deployer.gui.UITarget:addMapSetToProject</code> service exists and that the user has the necessary privileges for executing the service, and then try again.
<b>DEP.0002.0119</b>	<b>Deployment map {0} already exists in project {1} and cannot be overwritten.</b>
<b>Explanation</b>	You attempted to import a map file for a map that already exists.
<b>Action</b>	Delete the existing map and then import the map. If you need a backup of the existing map export the map and store it in a different location.
<b>DEP.0002.0120</b>	<b>Unable to list remote server aliases.</b>
<b>Explanation</b>	This error might occur for no specific reason.
<b>Action</b>	Make sure the <code>wm.deployer.Util:listAliases</code> service exists and the user has the necessary privileges for executing the service. then try again.
<b>DEP.0002.0121</b>	<b>Unable to list target group aliases.</b>
<b>Explanation</b>	This error might occur for no specific reason.
<b>Action</b>	Make sure the <code>wm.deployer.gui.UITargetGroup:listTargetGroups</code> service exists and the user has the necessary privileges for executing the service. Then try again.
<b>DEP.0002.0124</b>	<b>Deployment set {0} is not valid for project {1}.</b>
<b>Explanation</b>	One or more deployment sets defined in the map file you are importing are not included in the project definition.
<b>Action</b>	Make sure the map file you are trying to import is consistent with the define step of the project.

<b>DEP.0002.0125</b>	<b>The target server {0} is not valid for plugin type {1}. Either define the target server alias on the Deployer where you are trying to import the map file or remove the target server alias from the exported map file.</b>
<b>Explanation</b>	This error is shown when you attempt to import a map file that contains a target server alias that is not defined on that Deployer.
<b>Action</b>	Either define the target server alias on the Deployer where you are trying to import the map file or remove the target server alias from the exported map file.
<b>DEP.0002.0126</b>	<b>The target group {0} is not valid for plugin type {1}. Define the target group on the Deployer where you are trying to import the map file or else remove the target group from the exported map file.</b>
<b>Explanation</b>	This error is shown when you try to import a map file that contains a target group not defined on that Deployer.
<b>Action</b>	Define the target group on the Deployer where you are trying to import the map file or else remove the target group from the exported map file.
<b>DEP.0002.0129</b>	<b>Either the number passed is not a number or is negative. Enter an integer value for the flag -id for the command --showReport.</b>
<b>Explanation</b>	This error is thrown by the Deployer command line interface for the --showReport command. The --showReport command requires an integer value for the flag -id. If an integer is not entered for this flag then the above error is thrown.
<b>Action</b>	Enter an integer value for the flag -id for the command --showReport.
<b>DEP.0002.0133</b>	<b>Error exporting properties for the project {0}.</b>
<b>Explanation</b>	This error might occur for no specific reason.
<b>Action</b>	Make sure the wm.deployer.gui.UIProject:getFormattedProjectInfo service exists and the user has the necessary privileges for executing the service.
<b>DEP.0002.0135</b>	<b>Error retrieving properties for the project {0}.</b>
<b>Explanation</b>	This error might occur for no specific reason.
<b>Action</b>	Make sure the wm.deployer.gui.UIProject:getFormattedProjectInfo service exists and the user has the necessary privileges for executing the service.
<b>DEP.0002.0136</b>	<b>Unable to import zip file; zip file might be corrupt. Copy the build file from the source Deployer again. If this does not fix the problem, rebuild the original project and export the build again.</b>
<b>Explanation</b>	The build file placed in the WmDeployer/replicate/inbound is corrupted. This can occur because of error while copying the build file.
<b>Action</b>	Copy the build file from the source Deployer again. If this does not fix the problem, rebuild the original project and export the build again.

**DEP.0002.0137**      **Install of WmDeployerResource package cannot proceed. All the nodes in this cluster are not online. The following nodes are offline: {0}. Installing the package on the local node only.**

**Explanation**      This error occurs when you try to install the WmDeployerResource package on a cluster node and some of the nodes of the cluster are offline.

**Action**             Make sure all the nodes in the cluster are online.

**DEP.0002.0138E**      **You tried to add a target server or a target group of the same name as one that already exists in the deployment map.**

**Explanation**      You tried to add a target server or a target group of the same name as one that already exists in the deployment map.

**Action**             Rename the target server or target group alias and add it to the map.

**DEP.0002.0139**      **Cannot import the deployment map. Make sure the field names, values and the structure of the XML file are valid.**

**Explanation**      The exported map does not have the expected structure.

**Action**             If you modified the XML, validate the exported XML with the service `wm.deployer.flows:validateXMLWithXSD`.

If you are exporting a map, pass the schema file as `wm.deployer.flows:DeploymentMap_Definition`.

If you are exporting a varsub, pass the schema file as `wm.deployer.flows:Varsub_Definition`.

**DEP.0002.0140**      **Cannot import variable substitution values. Make sure the field names and values and the structure of the XML file are valid.**

**Explanation**      This error occurs when the exported map does not have the expected structure.

**Action**             If you have modified the XML, validate the exported xml with the service `wm.deployer.flows:validateXMLWithXSD`.

If you are exporting a map then pass the schema file as `wm.deployer.flows:DeploymentMap_Definition`.

If you are exporting a varsub then pass the schema file as `wm.deployer.flows:Varsub_Definition`.

<b>DEP.0002.0142</b>	<b>Project {0} already contains a deletion set named {1}. Rename the deployment or deletion set you are trying to create or delete the existing deployment or deletion set from the project. Then retry your action.</b>
<b>Explanation</b>	You tried to add a deployment or deletion set of the same name as one of the deployment or deletion sets already in the project.
<b>Action</b>	Rename the deployment or deletion set you are trying to create or delete the existing deployment or deletion set from the project. Then retry your action.
<b>DEP.0002.0143</b>	<b>A project can have only one deletion set for each server type. Deletion set {0} already exists for {1}. You can add assets to existing deleting sets, or delete the existing deletion set before trying to create another deletion set.</b>
<b>Explanation</b>	You attempted to create a deletion set on a project that already contains one. Only one deletion set can be created for a project.
<b>Action</b>	You can add assets to existing deleting sets, or delete the existing deletion set before trying to create another deletion set.
<b>DEP.0002.0144E</b>	<b>Deployer encountered an error while trying to get dependent assets for deletion set {0}. See the Integration Server logs.</b>
<b>Explanation</b>	This error might occur for no specific reason.
<b>Action</b>	Ensure the <code>wm.deployer.gui.UITarget:checkTargetDependencies</code> service exists and the user has the necessary privileges for executing the service.
<b>DEP.0002.0146</b>	<b>Deletion sets definition file {0} already exists for this project. Make a back up of the existing file in another location and then delete the file. Then export the deletion set again.</b>
<b>Explanation</b>	The exported file already exists and another export for the same deletion set would cause this error.
<b>Action</b>	Make a back up of the existing file in another location and then delete the file. Then export the deletion set again.
<b>DEP.0002.0147</b>	<b>Rollback on deployment candidate {0} failed. Check the rollback report for more information.</b>
<b>Explanation</b>	This error might occur for no specific reason.
<b>Action</b>	Check the rollback report for further information.

DEP.0002.0148	<b>No such deployment candidate {0} found in project {1}. Delete and recreate the deployment candidate.</b>
<b>Explanation</b>	This error might occur for no specific reason.
<b>Action</b>	Delete and recreate the deployment candidate.
DEP.0002.0149	<b>Deployment candidate {0} in project {1} is not checkpointed. Use the Deployer command-line interface to create a checkpoint for the deployment candidate. If you want to deploy without creating a checkpoint, use the -force flag.</b>
<b>Explanation</b>	This error is shown when you attempt to deploy without creating a checkpoint from the Deployer command-line interface.
<b>Action</b>	Use the Deployer command-line interface to create a checkpoint for the deployment candidate. If you want to deploy without creating a checkpoint, use the -force flag.
DEP.0002.0150	<b>The WmDeployerResource package is not installed on the target Integration Server. Install the WmDeployerResource package on the target Integration Server from the Deployer user interface on the Integration Server alias page.</b>
<b>Explanation</b>	The WmDeployerResource package is not installed on the target Integration Server.
<b>Action</b>	Install the WmDeployerResource package on the target Integration Server from the Deployer user interface on the Integration Server alias page.
DEP.0002.0158E	<b>Deployer did not save the versions for the aliases {0} because the aliases do not exist. Make sure the alias for which you specified the version is valid.</b>
<b>Explanation</b>	The alias for which you tried to update the version does not exist.
<b>Action</b>	Make sure the alias for which you specified the version is valid.
DEP.0002.0159E	<b>The deployment set contains source servers of different versions. Source servers in a deployment set must be the same version. Remove the source servers with the wrong version from the deployment set or change the versions to match.</b>
<b>Explanation</b>	The source servers in the deployment set are different versions.
<b>Action</b>	Remove the source servers with the wrong version from the deployment set or change the versions to match.
DEP.0002.0160E	<b>The deployment maps contain target servers of different versions. Target servers in deployment maps must be the same version. Remove the target servers with the wrong version from the deployment maps or change the versions to match.</b>
<b>Explanation</b>	The target servers in the deployment maps are different versions.
<b>Action</b>	Remove the target servers with the wrong version from the deployment maps or change the versions to match.

<b>DEP.0002.0162E</b>	<b>Repository name {0} contains illegal characters.</b>
<b>Explanation</b>	The repository name contains one or more spaces or the following invalid characters: # & @ ^ ! % * : \$ / \ \ ` ' ; , ~ + = > < \ "
<b>Action</b>	Remove the invalid characters from the repository alias name.
<b>DEP.0002.0163E</b>	<b>Deployment set name {0} contains illegal characters.</b>
<b>Explanation</b>	The deployment set name contains one or more spaces or the following invalid characters: # & @ ^ ! % * : \$ / \ \ ` ' ; , ~ + = > < \ "
<b>Action</b>	Remove the invalid characters from the deployment set name.
<b>DEP.0002.0164E</b>	<b>Deployment map name {0} contains illegal characters.</b>
<b>Explanation</b>	The deployment map name contains one or more spaces or the following invalid characters: # & @ ^ ! % * : \$ / \ \ ` ' ; , ~ + = > < \ "
<b>Action</b>	Remove the invalid characters from the deployment map name.
<b>DEP.0002.0165E</b>	<b>Deployment candidate name {0} contains illegal characters.</b>
<b>Explanation</b>	The deployment candidate name contains one or more spaces or the following invalid characters: # & @ ^ ! % * : \$ / \ \ ` ' ; , ~ + = > < \ "
<b>Action</b>	Remove the invalid characters from the deployment candidate name.
<b>DEP.0002.0166E</b>	<b>Component {0} not found in composite {1} from repository source {2}.</b>
<b>Explanation</b>	The contents of the repository have been modified.
<b>Action</b>	Run the build script again or recreate the repository.
<b>DEP.0002.0167E</b>	<b>There is an error in deployment candidates(s) {0} from project {1}. See the Integration Server logs for more information.</b>
<b>Explanation</b>	Deployer displays this error for various reasons.
<b>Action</b>	See the Integration Server logs for an explanation of the exception.
<b>DEP.0002.0168E</b>	<b>Cannot save variable substitutions. There are no servers selected.</b>
<b>Explanation</b>	Deployer requires that you select at least one server for variable substitutions.
<b>Action</b>	Select at least one server from the list of selected servers.

**DEP.0002.0172W**      **When adding a new target server to the map, Deployer will remove any checkpoints created for the associated deployment candidates. You must recreate any checkpoints you want to use. Do you want to continue?**

**Explanation**      Adding new target servers to the map will cause Deployer to remove any checkpoints previously created for the deployment candidates associated with this map.

**Action**      If you continue with the change, you must recreate any checkpoints you want to use for the associated deployment candidates.

**DEP.0002.0173W**      **When modifying the deployment set, Deployer will remove any checkpoints created for the associated deployment candidates. You must recreate any checkpoints you want to use. Do you want to continue?**

**Explanation**      Modifying the deployment set will cause Deployer to remove any checkpoints previously created for the deployment candidates associated with this project.

**Action**      If you continue with the change, you must recreate any checkpoints you want to use for the project.

**DEP.0002.0180E**      **Repository {0} is not connected. The specified flat file directory does not exist.**

**Explanation**      The specified repository does not exist.

**Action**      Ensure that the repository exists in the specified location.

**DEP.0002.0183W**      **When modifying the deletion set, Deployer will remove any checkpoints created for the associated deployment candidates. You must recreate any checkpoints you want to use. Do you want to continue?**

**Explanation**      If you modify the deletion set, Deployer will remove any checkpoints previously created for the deployment candidates associated with this project.

**Action**      If you continue with the change, you must recreate any checkpoints you want to use for the project.

**DEP.0002.0201E**      **Checkpoint for Deployment Candidate {0} failed. For more information, see the checkpoint report.**

**Explanation**      Possible causes for this error:

- 1) The project file could not be found in, or loaded from, the build.
- 2) The target file or deployment candidate could not be loaded from disk.
- 3) The user is not authorized to create a checkpoint.
- 4) Another reason shown in the checkpoint report.

**Action**      Verify that the build is available and correct and that there is sufficient disk space and memory. Also review the checkpoint report and verify that the necessary operating system privileges are set and that the user has authorization to create a checkpoint.

<b>DEP.0002.0202W</b>	<b>Checkpoint for deployment candidate {0} completed with warnings. For more information, see the checkpoint report.</b>
<b>Explanation</b>	Deployer encountered a warning while extracting objects from source system.
<b>Action</b>	Review the checkpoint report to determine any further action to take. Most warnings require no action by the user.
<b>DEP.0002.0206E</b>	<b>Checkpoint for deployment candidate {0} failed: {1}</b>
<b>Explanation</b>	Deployer encountered an exception while extracting objects from the source system. The following are possible causes for the exception:  <ol style="list-style-type: none"> <li>1) Deployer could not find project file in, or load it from, the build.</li> <li>2) Deployer could not load the target file or deployment candidate from disk.</li> <li>3) The user is not authorized to create a checkpoint.</li> <li>4) Other reasons as shown in the checkpoint report.</li> </ol>
<b>Action</b>	Verify that the build is available and correct, and that there is sufficient disk space and memory. Also review the checkpoint report to verify that the necessary operating system privileges are set and that the user has authorization to create a checkpoint.
<b>DEP.0002.0300E</b>	<b>User is not authorized to create variable substitution file for project {0}.</b>
<b>Explanation</b>	You are not authorized to perform the action of variable substitution for the specified project. You must have map authorization for the project.
<b>Action</b>	Ask an administrator or user that has map authorization for the project to perform this task or have an administrator assign you map authorization.
<b>DEP.0002.0301E</b>	<b>Could not save variable substitution file {0}.</b>
<b>Explanation</b>	Deployer encountered an error writing to disk.
<b>Action</b>	Check your Integration Server's disk space. If you believe there should be sufficient space, try to save again. If saving again is not successful, perform one or both of the following and retry the action:  <p>Restart the server.</p> <p>Recreate the variable substitution information.</p>

- DEP.0002.0302E**      **Variable substitution object type {0} is invalid.**  
**Explanation**      Deployer attempted to create a variable substitution item that is not valid. This might occur if the service that is attempting to create the variable substitution item is invoked by something other than the Deployer user interface.  
**Action**              Contact Software AG Global Support to report this issue and request a fix.
- DEP.0002.0306E**      **Deployer cannot import the substitute configuration values into the deployment map. The .vs file does not exist.**  
**Explanation**      There are no .vs files in the WmDeployer/replicate/inbound folder.  
**Action**              Copy the variable substitution file to the WmDeployer/replicate/inbound folder and then import it into the deployment map.
- DEP.0002.0309E**      **Unable to export variable substitution information.**  
**Explanation**      This error occurs when the exported map already exists in the WmDeployer/replicate/inbound folder.  
**Action**              Backup the file to a different location and delete the original. Then export the map again.
- DEP.0002.0311E**      **The Deployer {0} file is not accessible or does not exist.**  
**Explanation**      The XML file name you passed for importing the varsub is not present in the WmDeployer/replicate/inbound folder.  
**Action**              Check and correct the file name you passed in the command-line.
- DEP.0004.0001E**      **Version Mismatch Error: The server alias is a different version number than the other source/target servers. Source and target servers must use the same version as the server alias.**  
**Explanation**      The versions of the source or target servers are different than the version selected for the alias version.  
**Action**              Remove the aliases with the wrong version from the deployment set or change the version to match the source servers.
- DEP.0004.0002W**      **The target Integration Server is part of a cluster, but is not properly configured to support clustered deployment. See the product documentation for instructions on proper cluster configuration.**  
**Explanation**      One of the target Integration Servers is not properly configured for clustering.  
**Action**              See the webMethods Integration Server documentation for a description of the proper configuration settings for clustering.

<b>DEP.0005.0105I</b>	<b>No publishable document types needed to be synchronized in the following package(s): "{0}"</b>
<b>Explanation</b>	The packages with document types are deployed. However, there are no unsynchronized document types.
<b>Action</b>	Make sure that no unsynchronized document types are used for process development.
<b>DEP.0005.0111E</b>	<b>The source user has no username. Deployer cannot deploy an undefined user.</b>
<b>Explanation</b>	This error occurs when Deployer cannot deploy or roll back a target server due to an undefined user.
<b>Action</b>	Verify that the user exists on the source server and that configuration details are correct.
<b>DEP.0005.0113E</b>	<b>The source user "{0}" has a non-ASCII password. Deployer cannot deploy assets to an undefined user.</b>
<b>Explanation</b>	Deployer is attempting to deploy an invalid user.
<b>Action</b>	Verify that the selected user is valid.
<b>DEP.0005.0115E</b>	<b>An error occurred while attempting to deploy user "{0}" with the following error message follows: &lt;p&gt;"{1}"&lt;/p&gt;</b>
<b>Explanation</b>	An error occurred while attempting to deploy a user.
<b>Action</b>	Check the Integration Server logs and error messages in the output report for more information.
<b>DEP.0005.0118E</b>	<b>Deployer encountered the following exception while attempting to put package "{0}" into the inbound directory: "{1}"</b>
<b>Explanation</b>	There might be network connectivity problems between Deployer and each target Integration Server. Alternatively, the target Integration Servers might not be currently running.
<b>Action</b>	Verify network connectivity between the Deployer server and each target server. Also, verify that the target Integration Servers are running.
<b>DEP.0005.0131E</b>	<b>Deployment completed with errors. Following is a path to the output report, followed by an error message: "{0}" &lt;p&gt;Error message: "{1}"&lt;/p&gt;</b>
<b>Explanation</b>	Deployment completed with errors.
<b>Action</b>	Check the Integration Server logs, as well as error messages in the output report.

<b>DEP.0005.0134E</b>	<b>Deployer encountered an error while synchronizing documents in the following packages: "{0}"</b>
<b>Explanation</b>	This error occurs when a Broker or UM mapped with an Integration Server is unavailable.
<b>Action</b>	Ensure that the mapped JMS Broker or UM is available.
<b>DEP.0005.0156E</b>	<b>Deployer encountered an error during deployment. Deployer did not find package "{0}" in the build zip file "{1}".</b>
<b>Explanation</b>	Deployer invoked the wm.server.util:putPackageFile service and the service returned an error.
<b>Action</b>	See the deployment or simulation report to determine which error putPackageField service returned.
<b>DEP.0005.0157E</b>	<b>Deployer encountered an error during deployment. "{0}" package was not found in the build zip file: "{1}".</b>
<b>Explanation</b>	The specified package was not found in the build. Typically, this indicates that the deployment set is not current with the build.
<b>Action</b>	Re-create your deployment set and build files.
<b>DEP.0005.0160E</b>	<b>While attempting to install package "{0}" an exception with the following error message occurred: &lt;p&gt;"{1}"&lt;/p&gt;</b>
<b>Explanation</b>	Deployer invoked the pub.packages:installPackage service, and the service returned an error.
<b>Action</b>	Verify network connectivity between the Deployer server and each target server. Verify that the target Integration Servers are running. For more information about the error returned by the installPackage service, see the deployment or simulation report. For more information about the installPackage service, see Integration Server Built-In Services Reference.
<b>DEP.0005.0161E</b>	<b>The number of bytes read from package "{0}" was not correct.</b>
<b>Explanation</b>	An I/O exception occurred while reading the specified package. As a result, all data from the package could not be read. This exception can occur for the following reasons: <ul style="list-style-type: none"> <li>- The I/O operation failed or was interrupted while accessing the build file.</li> <li>- A security violation has occurred, which typically means that the user running Deployer does not have correct privileges to access the files.</li> </ul>
<b>Action</b>	Verify that the file system and the build file that contains the source package are not corrupt. Verify that the user attempting this action has the proper authority to read files on the file system. You might need to re-create the build.

<b>DEP.0005.0164E</b>	<b>The scheduled service type "{0}" for service name "{1}" is unknown and could not be processed.</b>
<b>Explanation</b>	Your version of Deployer is out of date.
<b>Action</b>	Ensure that you have the latest version of the WmDeployer package.
<b>DEP.0005.0170E</b>	<b>Deployer encountered the following error while retrieving the scheduled service with service name "{0}" from target "{1}": "{2}".</b>
<b>Explanation</b>	This error occurs when Deployer fails to get details for a scheduled service for the variable substitution.
<b>Action</b>	Verify that the scheduled service exists under the specified name on the target server.
<b>DEP.0005.0187E</b>	<b>Deployer encountered the following exception while performing a remote invoke of the service "{0}": "{1}"</b>
<b>Explanation</b>	This error occurs when Deployer cannot invoke a service on a remote server, which indicates that the remote server might be offline.
<b>Action</b>	Verify that the remote server is running and available.
<b>DEP.0005.0190E</b>	<b>Deployer encountered the following error while attempting to deploy Group: "{0}": "{1}"</b>
<b>Explanation</b>	An error occurred while attempting to deploy the group.
<b>Action</b>	Recreate the build and deploy the group again.
<b>DEP.0005.0193E</b>	<b>Deployer encountered the following error while attempting to deploy ACL "{0}": "{1}"</b>
<b>Explanation</b>	An error occurred while attempting to deploy an ACL.
<b>Action</b>	Check Integration Server logs and error messages in the Deployment report.
<b>DEP.0005.0197E</b>	<b>Deployer encountered the following error while attempting to deploy Port "{0}" associated with package "{1}": "{2}".</b>
<b>Explanation</b>	An error occurred while attempting to deploy a port associated with a package.
<b>Action</b>	Check for error messages in the output report and Integration Server logs. Verify that the specified port is available on the target server. Recreate the build if problems persist.

<b>DEP.0005.0199E</b>	<b>Deployment failed.</b>
<b>Explanation</b>	The deployment failed.
<b>Action</b>	Review the deployment report and Integration Server logs to determine the cause of the failure, and take the appropriate action.
<b>DEP.0005.0204E</b>	<b>Deployer encountered the following Trading Networks error while attempting to import "{0}" with name "{1}": "{2}", message: "{3}"</b>
<b>Explanation</b>	An error occurred attempting to import one of the following Trading Network object types: Document Attributes, Document Types, Field Groups, ID Types, Contact Types, Binary Types, or Profile Groups. Possible causes include: <ul style="list-style-type: none"><li>- A network connection error occurred between the Deployer server and the target Integration Server.</li><li>- The target Integration Server is not running.</li><li>- The target WmTN package on the target Integration Server is not loaded or enabled.</li><li>- There could be problems with the Trading Networks object type being imported to the target.</li></ul>
<b>Action</b>	Verify the following: <ul style="list-style-type: none"><li>- There are no network connectivity errors between the Deployer server and each target Integration Server.</li><li>- All target Integration Servers are running.</li><li>- The WmTN package on each target Integration Server is loaded and enabled.</li><li>- The Trading Networks object type is allowed. See the webMethods Trading Networks documentation for details about permissible Trading Networks object types.</li></ul>
<b>DEP.0005.0231</b>	<b>There are no required patches specified for the target Integration Server.</b>
<b>Explanation</b>	This message occurs when a user deploys unrequired patches into a target.
<b>Action</b>	See the patch details for more information.
<b>DEP.0005.0234E</b>	<b>Deployer encountered the following error while pausing the listener "{0}" associated with package "{1}": "{2}"</b>
<b>Explanation</b>	Could not pause the listener associated with the package.
<b>Action</b>	Check the Integration Server logs and error messages in the output report for more information.

<b>DEP.0005.0235E</b>	<b>Deployer encountered an error while disabling of port "{0}" associated with package "{1}".</b>
<b>Explanation</b>	An exception occurred while disabling the port associated with the package.
<b>Action</b>	Check the Integration Server logs and error messages in the output report for more information.
<b>DEP.0005.0236E</b>	<b>Deployer encountered an error while enabling the listener "{0}" associated with package "{1}": "{2}"</b>
<b>Explanation</b>	Deployer could not enable the specified listener.
<b>Action</b>	See the webMethods Integration Server documentation for specific instructions on how to enable a listener.
<b>DEP.0005.0240E</b>	<b>Deployer encountered the following error while suspending the triggers: "{0}"</b>
<b>Explanation</b>	Deployer could not suspend the triggers on the target Integration Server. Deployer attempts to suspend all triggers by setting the maximum percentage of document retrieval threads and the maximum percentage of trigger execution threads to zero.
<b>Action</b>	Verify network connectivity between Deployer and each target Integration Server. Also, verify that the target Integration Servers are running. For more information about the configuration settings for document retrieval threads and trigger execution threads, see information about configuring the server in the webMethods Integration Server documentation.
<b>DEP.0005.0242E</b>	<b>Could not resume the Integration Server triggers. Error message follows: "{0}"</b>
<b>Explanation</b>	Deployer could not resume the triggers on the target Integration Server. Deployer attempts to resume all triggers by resetting the maximum percentage of document retrieval threads and the maximum percentage of trigger execution threads to the values they had before Deployer suspended the triggers.
<b>Action</b>	Verify network connectivity between the Deployer server and each target Integration Server. Verify that the target Integration Servers are running. For more information about configuration settings for document retrieval threads and trigger execution threads, see information about configuring the server in the webMethods Integration Server documentation.
<b>DEP.0005.0243E</b>	<b>Deployer did not deploy deployment set "{0}" because it contains the following unsatisfied dependencies: "{1}"</b>
<b>Explanation</b>	The dependencies required by the specified deployment set are missing on the target system.
<b>Action</b>	Either install the necessary components on the target system, or change the Deployer project so that it no longer requires the missing dependencies.

<b>DEP.0005.0244E</b>	<b>Deployer encountered the following exception while checking dependencies on target "{0}" for deployment set "{1}": "{2}"</b>
<b>Explanation</b>	An exception occurred while checking dependencies for the deployment set at the target.
<b>Action</b>	Check Integration Server logs and error messages in the output report for exception details.
<b>DEP.0005.0250E</b>	<b>Simulation failed.</b>
<b>Explanation</b>	The deployment simulation failed.
<b>Action</b>	Refer to the simulation report and Integration Server logs to determine the cause of the failure and take the appropriate action.
<b>DEP.0005.0256E</b>	<b>There are no targets mapped for the current deployment set.</b>
<b>Explanation</b>	There are no valid target servers mapped for the deployment set.
<b>Action</b>	Verify that the specified target servers are mapped appropriately for the current deployment set.
<b>DEP.0005.0257E</b>	<b>Deployer cannot deploy the deployment set because there are no source servers specified.</b>
<b>Explanation</b>	There are no source servers mapped for the deployment set to define assets for deployment.
<b>Action</b>	Verify that source servers are defined appropriately for assets to be deployed.
<b>DEP.0005.0263E</b>	<b>The following Trading Networks error occurred while attempting to import processing rules: class: "{0}", message: "{1}"</b>
<b>Explanation</b>	An error occurred when attempting to import processing rules into Trading Networks. Possible causes include: <ul style="list-style-type: none"> <li>- A network connection error between the Deployer server and the target Integration Server running Trading Networks.</li> <li>- The target Integration Server is not running.</li> <li>- The WmTN package is not loaded or enabled on the target Integration Server.</li> <li>- The Trading Networks object type being imported to the target might be in error.</li> </ul>
<b>Action</b>	Verify the following: <ul style="list-style-type: none"> <li>- There are no network connectivity errors between the Deployer server and each target Integration Server.</li> <li>- All target Integration Servers are running.</li> <li>- The WmTN package on each target Integration Server is loaded and enabled.</li> </ul>

- The Trading Networks object type is allowed. See the webMethods Trading Networks documentation for details about permissible processing rules.

**DEP.0005.0265E** **Deployer encountered the following Trading Networks error while attempting to import "{0}" with a group code "{1}" and name "{2}": class: "{3}", message: "{4}"**

**Explanation** An error occurred when attempting to import field groups into Trading Networks. Possible causes include:

- An error in the network connection between the Deployer server and the target Integration Server running Trading Networks.
- The target Integration Server is not running.
- The WmTN package is not loaded or enabled on the target Integration Server.
- The Trading Networks object type being imported to the target might be in error.

**Action** Verify the following:

- There are no network connectivity errors between the Deployer server and each target Integration Server.
- All target Integration Servers are running.
- The WmTN package on each target Integration Server is loaded and enabled.
- The Trading Networks object type is allowed. See the webMethods Trading Networks documentation for details about permissible field groups.

**DEP.0005.0266E** **Deployer encountered the following Trading Networks error while attempting to import field definitions: class: "{0}", message: "{1}"**

**Explanation** An error occurred when attempting to import field definitions into Trading Networks. Possible causes include:

- An error in the network connection between the Deployer server and the target Integration Server running Trading Networks.
- The target Integration Server is not running.
- The WmTN package is not loaded or enabled on the target Integration Server.
- The Trading Networks object type being imported to the target might be in error.

**Action** Verify the following:

- There are no network connectivity errors between the Deployer server and each target Integration Server.
- All target Integration Servers are running.
- The WmTN package on each target Integration Server is loaded and enabled.

- The Trading Networks object type is allowed. See the webMethods Trading Networks documentation for details about permissible field definitions.

**DEP.0005.0270E**     **Deployer encountered the following Trading Networks error while attempting to import partner profiles: class: "{0}", message: "{1}"**

**Explanation**     An error occurred when attempting to import partner profiles into Trading Networks. Possible causes include:

- A network connection error between the Deployer server and the target Integration Server running Trading Networks.
- The target Integration Server is not running.
- The WmTN package is not loaded or enabled on the target Integration Server.
- The Trading Networks object type being imported to the target might be in error.

**Action**     Verify the following:

- There are no network connectivity errors between the Deployer server and each target Integration Server.
- All target Integration Servers are running.
- The WmTN package on each target Integration Server is loaded and enabled.
- The Trading Networks object type is allowed. See the webMethods Trading Networks documentation for details about permissible partner profiles.

**DEP.0005.0274E**     **Deployer encountered the following Trading Networks error while attempting to import trading partner agreements: class: "{0}", message: "{1}"**

**Explanation**     An error occurred when attempting to import trading partner agreements (TPAs) into Trading Networks. Possible causes include:

- A network connection error between the Deployer server and the target Integration Server running Trading Networks.
- The target Integration Server is not running.
- The WmTN package is not loaded and/or enabled on the target Integration Server.
- The Trading Networks object type being imported to the target might be in error.

**Action**     Verify the following:

- There are no network connectivity errors between the Deployer server and each target Integration Server.
- All target Integration Servers are running.
- The WmTN package on each target Integration Server is loaded and enabled.

- The TN object type is allowed. See the webMethods Trading Networks documentation for details about permissible trading partner agreements (TPAs).

**DEP.0005.0277E** **Deployer encountered an error while attempting to import "{0}" with a type code "{1}" and a name "{2}". The following is the error information from Trading Networks: class: "{3}", message: "{4}"**

**Explanation** An error occurred when attempting to import external ID types, contact types, or binary types into Trading Networks. Possible causes include:

- A network connection error between the Deployer server and the target Integration Server running Trading Networks.
- The target Integration Server is not running.
- The WmTN package is not loaded or enabled on the target Integration Server.
- The Trading Networks object type being imported to the target might be in error.

**Action** Verify the following:

- There are no network connectivity errors between the Deployer server and each target Integration Server.
- All target Integration Servers are running.
- The WmTN package on each target Integration Server is loaded and enabled.
- The Trading Networks object type is allowed. See the webMethods Trading Networks documentation for details about permissible external ID types, contact types, and binary types.

**DEP.0005.0280E** **Triggers were not suspended prior to package deployment. Failure to suspend a trigger during deployment could cause problems on the target server.**

**Explanation** Triggers were not suspended prior to package deployment.

**Action** Not suspending a trigger during deployment can cause problems on the target. Check the Integration Server logs for more information.

**DEP.0005.0282E** **Scheduled services were not suspended prior to deployment. Failure to suspend scheduled services during deployment could cause problems on the target server.**

**Explanation** Scheduled services were not suspended prior to deployment. Failure to suspend scheduled services during deployment can cause problems at the target.

**Action** Check the Integration Server logs and error messages in the output report for more information.

<b>DEP.0005.0284E</b>	<b>Scheduled services were not started after deployment.</b>
<b>Explanation</b>	Scheduled services were not started after deployment. There might be an issue with a target server.
<b>Action</b>	For more information, check the Integration Server logs and error messages in the output report.
<b>DEP.0005.0286E</b>	<b>Listeners were not suspended prior to deployment. Failure to suspend listeners during deployment could cause problems on the target server.</b>
<b>Explanation</b>	Listeners were not suspended prior to deployment. Failure to suspend listeners during deployment could cause problems on the target server.
<b>Action</b>	Check the Integration Server logs for errors in suspending the listeners.
<b>DEP.0005.0288E</b>	<b>Listeners were not started after deployment.</b>
<b>Explanation</b>	Listeners were not started after deployment. It happens when the ports are disabled or if they will be used for the first time.
<b>Action</b>	Check the Integration Server logs and error messages in the output report.
<b>DEP.0005.0296E</b>	<b>Deployer did not deploy the {0}, which is required for source package "{1}" and it does not already exist at the target. Although the source package would be deployed to the target, some services in that package will not run correctly until that ACL is created at the target.</b>
<b>Explanation</b>	The Read, Write, List, or Execute ACLs required for the deployed package to run correctly are not being deployed to the target Integration Server, and that ACL does not already exist on the target Integration Server. Typically, this indicates that the ACLs associated with the package were not extracted.
<b>Action</b>	Repeat the extraction step using Deployer to ensure that all ACLs are included.
<b>DEP.0005.0297E</b>	<b>Deployer did not deploy the {0}, which is required for source package "{1}" and it does not already exist on the target. Some services in that source package will not run correctly until that ACL is created at the target.</b>
<b>Explanation</b>	The Read, Write, List, or Execute ACLs that are necessary for the deployed package to run correctly are not being deployed to the target Integration Server, and the specified ACL does not already exist on the target Integration Server. Typically, this problem indicates that the ACLs associated with the package were not extracted.
<b>Action</b>	Perform the extraction step again using Deployer to ensure that all ACLs are included.

<b>DEP.0005.0298E</b>	<b>Deployer encountered the following exception while invoking of the service "{0}": "{1}"</b>
<b>Explanation</b>	This exception occurs when Deployer invokes a service on a remote server.
<b>Action</b>	Verify that the source or target server is available.
<b>DEP.0005.0302E</b>	<b>Deployer encountered the following exception while creating the directory "{0}": "{1}"</b>
<b>Explanation</b>	An exception occurred while attempting to create a directory.
<b>Action</b>	Ensure that the appropriate write permissions exist to allow for the creation of the new directory and that adequate free space is available.
<b>DEP.0005.0303E</b>	<b>Deployer encountered an exception while creating one of the temporary jar files in "{0}": "{1}"</b>
<b>Explanation</b>	An exception occurred while attempting to create one of the temporary jar files.
<b>Action</b>	Ensure that the appropriate write permissions exist for the new file location and that adequate free space is available.
<b>DEP.0005.0304E</b>	<b>Target Server {0} is unavailable.</b>
<b>Explanation</b>	Deployer could not connect to the specified target server.
<b>Action</b>	Verify the following: <ul style="list-style-type: none"> <li>- Network connectivity between Deployer and each target Integration Server.</li> <li>- The target Integration Servers are running.</li> <li>- The target Integration Server alias is defined on the Deployer host server.</li> </ul>
<b>DEP.0005.0305E</b>	<b>An exception occurred while getting a Trading Networks docType object. This is most likely caused by a user-defined extension to the Trading Networks type BizDocType. Copy the jar files containing the extensions from the webM_install_dir/IntegrationServer/packages/WmTN/code/jars directory into the WmDeployer/code/jars directory.</b>
<b>Explanation</b>	There is a user-defined extension to a Trading Networks document type and Deployer does not have access to the associated jar files.
<b>Action</b>	To ensure Deployer has access to the associated jar files, copy the jar files containing the extensions from the webM_install_dir/IntegrationServer/packages/WmTN/code/jars directory into the WmDeployer/code/jars directory.

**DEP.0005.0306E**      **An error occurred while attempting to import extended field definitions; error information from Trading Networks: class: "{0}", message: "{1}"**

**Explanation**      An error occurred when attempting to import extended field definitions into Trading Networks. Possible causes include:

- An error in the network connection between the Deployer server and the target Integration Server that is running Trading Networks.
- The target Integration Server is not running.
- The WmTN package is not loaded and/or enabled on the target Integration Server.
- The Trading Networks object type being imported to the target might be in error.

**Action**      Verify the following:

- There are no network connectivity errors between the Deployer server and each target Integration Server.
- All target Integration Servers are running.
- The WmTN package on each target Integration Server is loaded and enabled.
- The Trading Networks object type is allowed. See the webMethods Trading Networks documentation for details about permissible extended field definitions.

**DEP.0005.0307E**      **Deployer encountered the following Trading Networks error while attempting to import security data for profile: "{0}": class: "{1}", message: "{2}"**

**Explanation**      Deployer encountered an error occurred while attempting to import the security data for the specified profile into Trading Networks. Possible causes include:

- A network connection error between the Deployer server and the target Integration Server running Trading Networks.
- The target Integration Server is not running.
- The WmTN package is not loaded or enabled on the target Integration Server.
- The Trading Networks object type being imported to the target might be in error.

**Action**      Verify the following:

- There are no network connectivity errors between the Deployer server and each target Integration Server.
- All target Integration Servers are running.
- The WmTN package on each target Integration Server is loaded and enabled.
- The Trading Networks object type is allowed. See the webMethods Trading Networks documentation for details about permissible Trading Networks Security Data.

<b>DEP.0005.0308E</b>	<b>An error occurred while attempting to import queues: class: "{0}", message: "{1}"</b>
<b>Explanation</b>	<p>An error occurred when attempting to import the public queues into Trading Networks. Possible causes include:</p> <ul style="list-style-type: none"> <li>- A network connection error between the Deployer server and the target Integration Server running Trading Networks.</li> <li>- The target Integration Server is not running.</li> <li>- The WmTN package is not loaded and/or enabled on the target Integration Server.</li> <li>- The Trading Networks object type being imported to the target might be in error.</li> </ul>
<b>Action</b>	<p>Verify the following:</p> <ul style="list-style-type: none"> <li>- There are no network connectivity errors between the Deployer server and each target Integration Server.</li> <li>- All target Integration Servers are running.</li> <li>- The WmTN package on each target Integration Server is loaded and enabled.</li> <li>- The Trading Networks object type is allowed. See the webMethods Trading Networks documentation for details about permissible public queues.</li> </ul>
<b>DEP.0005.0309E</b>	<b>An error occurred while attempting to import profile group "{0}" with value "{1}". class: "{2}", message: "{3}"</b>
<b>Explanation</b>	<p>An error occurred when attempting to import the profile groups into Trading Networks. Possible causes include:</p> <ul style="list-style-type: none"> <li>- A network connection error between the Deployer server and the target Integration Server running Trading Networks.</li> <li>- The target Integration Server is not running.</li> <li>- The WmTN package is not loaded and/or enabled on the target Integration Server.</li> <li>- The Trading Networks object type being imported to the target might be in error.</li> </ul>
<b>Action</b>	<p>Verify the following:</p> <ul style="list-style-type: none"> <li>- There are no network connectivity errors between the Deployer server and each target Integration Server.</li> <li>- All target Integration Servers are running.</li> <li>- The WmTN package on each target Integration Server is loaded and enabled.</li> <li>- The Trading Networks object type is allowed. See the webMethods Trading Networks documentation for details about permissible profile groups.</li> </ul>

**DEP.0005.0326E**      **An error occurred while deploying package "{0}". Item "{1}" could not be loaded because of reason "{2}". The package may have partially loaded; please check your target server.**

**Explanation**      The specified package did not load due to the reason returned from the target Integration Server.

**Action**            See the webMethods Integration Server documentation for the specific requirements for loading a package.

**DEP.0005.0328E**      **The JVM "{0}" on the target server is older than the "{1}" JVM recommended on the source for package "{2}".**

**Explanation**      The JVM version running on the target is older than the minimum JVM version property specified by the source.

**Action**            Change the minimum JVM property for the package being deployed and redeploy the package.

**DEP.0005.0329E**      **The "{0}" target JVM is older than the JVM recommended "{1}" on the source for package "{2}".**

**Explanation**      The JVM version running on the target is older than the minimum JVM version property required by the source.

**Action**            Change the minimum JVM property for the package being deployed, and then deploy again.

**DEP.0005.0330E**      **The target package version is null.**

**Explanation**      For partial deployment, Deployer requires that the package is present on the target server and that version of the package is not null and matches that of the source server.

**Action**            Verify that the package version defined on the target server is appropriate for partial package deployment.

**DEP.0005.0334E**      **Source package is of type Patch and package does not exist on target. The package: "{0}" will not be deployed. Re-define package to Full to deploy the package on target**

**Explanation**      This message indicates that the target partial mode package is undefined.

**Action**            Verify that the specified package exists on the target server and that it is valid for partial package deployment.

---

<b>DEP.0005.0337E</b>	<b>An error occurred while deploying package: "{0}"</b>
<b>Explanation</b>	Deployer invoked the pub.packages:installPackage service and the installPackage service returned an error.
<b>Action</b>	For more information about the error that the installPackage service returned, see the deployment or simulation report. For more information about the installPackage service and the requirements for installing packages, see the Integration Server Built-In Services Reference.
<b>DEP.0005.0338E</b>	<b>Deployer issued the following exception while attempting to activate the package: "{0}"</b>
<b>Explanation</b>	Deployer invoked the pub.packages:activatePackage service, and the activatePackage service returned an error.
<b>Action</b>	Verify the network connectivity between the Deployer server and each target Integration Server. Also, verify that the target Integration Servers are up and running. For more information about the error that the activatePackage service returned, see the deploy or simulation report. For more information about the activatePackage service, see the documentation for webMethods Integration Server documentation.
<b>DEP.0005.0352E</b>	<b>The package name "{0}" contains the invalid "{1}" character. For more information about illegal characters, see the webMethods Integration Server documentation.</b>
<b>Explanation</b>	The package name contains illegal characters.
<b>Action</b>	See the webMethods Integration Server documentation for information about how to name a package.
<b>DEP.0005.0353E</b>	<b>"{0}" is an invalid value for the Cleanup File Age parameter. Valid values are 1-9999.</b>
<b>Explanation</b>	The value specified for the Cleanup File Age parameter is invalid.
<b>Action</b>	Specify a valid value between 1 and 9999 for the Cleanup File Age parameter.
<b>DEP.0005.0354E</b>	<b>Invalid File Age parameter "{0}". Valid values are 0-9999.</b>
<b>Explanation</b>	The value specified for the File Age parameter is invalid.
<b>Action</b>	Specify a value between 0 and 9999 for the File Age parameter.
<b>DEP.0005.0355E</b>	<b>The Allow Recursive Polling parameter "{0}" is invalid. Valid values are "yes" and "no".</b>
<b>Explanation</b>	The specified Allow Recursive Polling parameter is neither "yes" nor "no".
<b>Action</b>	Specify either "yes" or "no" for the Allow Recursive Polling parameter.

**DEP.0005.0356E**      **The Run As User value "{0}" contains invalid character "{1}". For more information about illegal characters, see the webMethods Integration Server documentation.**

**Explanation**      The Run As User value contains illegal characters.

**Action**      For more information about illegal characters, see the webMethods Integration Server documentation.

**DEP.0005.0357E**      **No value was provided for the required Run services as user parameter.**

**Explanation**      The Run services as user parameter value is not specified.

**Action**      Specify a value for the Run services as user parameter. For more information, see the webMethods Integration Server documentation.

**DEP.0005.0358E**      **"{0}" is an invalid value for the File Polling Interval parameter. Valid values are 1-9999.**

**Explanation**      The value specified for the File Polling Interval parameter is invalid.

**Action**      Specify a valid value between 1 and 9999 for the File Polling Interval parameter.

**DEP.0005.0359E**      **No value is specified for the File Polling Interval parameter. Valid values are 1-9999.**

**Explanation**      No value is specified for the File Polling Interval parameter.

**Action**      Specify a value between 1 through 9999 for the File Polling Interval parameter.

**DEP.0005.0360E**      **"{0}" is an invalid value for the Cleanup Interval parameter. Valid values are 1-9999.**

**Explanation**      The value specified for the Cleanup Interval parameter is invalid.

**Action**      Specify a value between 1 and 9999 for the Cleanup Interval parameter.

**DEP.0005.0361E**      **"{0}" is an invalid value for the Maximum Number of Invocation Threads parameter. Valid values are 1-10.**

**Explanation**      The value specified for the Maximum Number of Invocation Threads parameter is invalid.

**Action**      Specify a value between 1 and 10 for the Maximum Number of Invocation Threads parameter.

**DEP.0005.0362E**      **No value provided for the required Maximum Number of Invocation Threads parameter.**

**Explanation**      No value was specified for the Maximum Number of Invocation Threads parameter.

**Action**      Specify a value between 1 and 10 for the Maximum Number of Invocation Threads parameter.

---

DEP.0005.0363E	<b>"{0}" is an invalid value for the Port parameter. The Port parameter requires an integer value.</b>
<b>Explanation</b>	The value specified for the Port parameter is not an integer.
<b>Action</b>	Specify a valid value for the Port parameter.
DEP.0005.0364E	<b>"{0}" is an invalid value for the Port parameter. The value for the Port parameter must be greater than -1.</b>
<b>Explanation</b>	The value for the Port parameter is not valid.
<b>Action</b>	Specify a valid value for the Port parameter.
DEP.0005.0365E	<b>No value was specified for the required Port parameter. Specify a value for the Port parameter.</b>
<b>Explanation</b>	No value was specified for the Port parameter.
<b>Action</b>	Specify a valid integer type value that is greater than -1 for the Port parameter.
DEP.0005.0366E	<b>The Client Authentication value: "{0}" is invalid. Valid values are 'true' and 'false'.</b>
<b>Explanation</b>	The specified Client Authentication value is neither "true" nor "false".
<b>Action</b>	Specify either "true" or "false" for the Client Authentication value.
DEP.0005.0367E	<b>The Host parameter requires a value.</b>
<b>Explanation</b>	The value for the Host parameter was not specified.
<b>Action</b>	Specify a value for the Host parameter.
DEP.0005.0368E	<b>"{0}" is an invalid value for the Type parameter. Valid values are "pop3" and "imap".</b>
<b>Explanation</b>	The value specified for the Type parameter is invalid.
<b>Action</b>	Specify either "pop3" or "imap" for the Type parameter.
DEP.0005.0369E	<b>Specify a value for the Type parameter. Valid values are "pop3" and "imap".</b>
<b>Explanation</b>	No value is specified for the required Port parameter.
<b>Action</b>	Specify either "pop3" or "imap" for the Port parameter.

- DEP.0005.0370E**      **The user name value: "{0}" contains an invalid character: "{1}". Refer to the Administering Integration Server guide for listed illegal characters.**
- Explanation**      The user name value contains illegal characters.
- Action**              For information about legal characters for user accounts, see the Administering Integration Server guide.
- 
- DEP.0005.0371E**      **No value provided for user name. This field is mandatory.**
- Explanation**      No value is provided for user name.
- Action**              Specify a value for the user name. For information about the legal characters for user accounts, see the Administering Integration Server guide.
- 
- DEP.0005.0372E**      **Invalid value provided for the "Log out after each mail check" parameter: "{0}". Valid values are "yes" and "no".**
- Explanation**      The specified value for the "Log out after each mail check" parameter is neither "yes" nor "no".
- Action**              Specify a valid value for the "Log out after each mail check" parameter. Valid values are "yes" and "no".
- 
- DEP.0005.0373E**      **The Authorize value "{0}" is invalid. Valid values are Yes and No.**
- Explanation**      The specified Authorize value is neither Yes and No.
- Action**              Specify either Yes or No for the Authorize value.
- 
- DEP.0005.0374E**      **"{0}" is an invalid value for the Time Interval parameter. Valid values are 1-9999.**
- Explanation**      The value specified for the Time Interval parameter is invalid.
- Action**              Specify a valid value between 1 and 9999 for the Time Interval parameter.
- 
- DEP.0005.0375E**      **Specify a value for the required Time Interval parameter. Valid values are 1-9999.**
- Explanation**      The required Time Interval parameter has not been specified.
- Action**              Specify a value from 1 through 9999 for the Time Interval parameter.
- 
- DEP.0005.0376E**      **The Reply value: "{0}" is invalid. Valid values are "yes" and "no".**
- Explanation**      The specified Reply value is neither "yes" nor "no".
- Action**              Specify either "yes" or "no" for the Reply value.

---

DEP.0005.0377E	<b>The Send reply e-mail on error value "{0}" is invalid. Valid values are Yes and No.</b>
<b>Explanation</b>	The Send reply e-mail on error value is set to a value other than Yes or No.
<b>Action</b>	Specify either Yes or No for the Send reply e-mail on error value.
DEP.0005.0378E	<b>The Remove value: "{0}" is invalid. Valid values are "yes" and "no".</b>
<b>Explanation</b>	The specified Remove value is neither "yes" nor "no".
<b>Action</b>	Specify either "yes" or "no" for the Remove value.
DEP.0005.0379E	<b>"{0}" is an invalid value for the Delete invalid messages parameter. Valid values are Yes and No.</b>
<b>Explanation</b>	The value specified for the Delete invalid messages parameter is invalid.
<b>Action</b>	Specify a valid value of Yes or No for the Delete invalid messages parameter.
DEP.0005.0380E	<b>The Multithread processing value "{0}" is invalid. Valid values are Yes and No.</b>
<b>Explanation</b>	The Multithread processing is set to a value other than Yes or No.
<b>Action</b>	Specify either Yes or No for the Multithread processing value.
DEP.0005.0381E	<b>"{0}" is an invalid value for the Number of threads if multithreading is turned on parameter. Valid values are 1-99.</b>
<b>Explanation</b>	The value specified for the Number of threads if multithreading is turned on field is invalid.
<b>Action</b>	Specify a value between 1 and 99 for the Number of threads if multithreading is turned on field.
DEP.0005.0382E	<b>Enter a value for the Number of threads if multithreading is turned on parameter. Valid values are 1-99.</b>
<b>Explanation</b>	There is no value set for the Number of threads if multithreading is turned on parameter.
<b>Action</b>	Specify a value between 1 and 99 for the Number of threads if multithreading is turned on parameter.
DEP.0005.0383E	<b>The Break Mmsg value: "{0}" is invalid. Valid values are "yes" and "no".</b>
<b>Explanation</b>	The specified Break Mmsg value is neither "yes" nor "no".
<b>Action</b>	Specify either "yes" or "no" for the Break Mmsg value.

<b>DEP.0005.0384E</b>	<b>The Include Headers value: "{0}" is invalid. Valid values are "yes" and "no".</b>
<b>Explanation</b>	The specified Include Headers value is neither "yes" nor "no".
<b>Action</b>	Specify either "yes" or "no" for the Include Headers value.
<b>DEP.0005.0421E</b>	<b>Unknown system type: "{0}".</b>
<b>Explanation</b>	The source system type is unknown, which indicates that your version of Deployer is out of date.
<b>Action</b>	Ensure that you have the latest version of the WmDeployer package.
<b>DEP.0005.0422E</b>	<b>Unable to invoke "{1}" because the connection object is of an unknown type. Its value is: "{0}".</b>
<b>Explanation</b>	The system type object is set to a value that is not recognized. This issue might occur if the user manually edits the project XML file.
<b>Action</b>	Rebuild the project file and map the steps again. Do not manually edit the project file.
<b>DEP.0005.0423E</b>	<b>Deployer encountered an exception while writing the bytes for package "{0}" to the output stream in preparation for deployment to the target "{1}".</b>
<b>Explanation</b>	An exception occurred when Deployer tried to write the package data to disk. That exception can occur for the following reasons:  - The I/O operation failed or was interrupted while accessing the build file.  - A security violation occurred, which typically means that the user running Deployer lacks the correct privileges to access the files.
<b>Action</b>	Verify that the file system is not corrupt and that adequate disk space is available for writing new files. Also verify that the user has appropriate privileges to write files on the file system.
<b>DEP.0005.0430</b>	<b>There is no logical server defined for the specified Server ID.</b>
<b>Explanation</b>	Either no logical server is defined in the WmDesigner service on the target Integration Server server, or the server is not up and running and available for process model deployment.
<b>Action</b>	Verify that the logical server is defined in the WmDesigner service on the target Integration Server server and that the server is available.

<b>DEP.0005.0431</b>	<b>The most-likely fix for that is to use webMethods Administrator on your target server to define a logical server with the name: "{0}".</b>
<b>Explanation</b>	This problem occurs when the logical server is not defined in the WmDesigner service on the target Integration Server server for process model deployment.
<b>Action</b>	Verify that the logical server is defined in the WmDesigner service on the target Integration Server server.
<b>DEP.0005.0433E</b>	<b>Cannot associate {0} ACL "{1}", with "{2}" because user "{3}" is not in the Write ACL: "{4}" .</b>
<b>Explanation</b>	Cannot associate the ACL because the user is not a member of the Write ACL.
<b>Action</b>	Add the user to the Write ACL.
<b>DEP.0005.0435E</b>	<b>Deployer cannot suspend selected triggers. You can suspend selected triggers only with Integration Server 6.0.1 Fix 144, Integration Server 6.1 Fix 22, or Integration Server 6.5 and later. Alternatively, you can suspend all triggers in the project properties.</b>
<b>Explanation</b>	Selected trigger suspension is supported only in the following releases: <ul style="list-style-type: none"> <li>- Integration Server 6.0.1 Fix 144</li> <li>- Integration Server 6.1 Fix 22.</li> <li>- Integration Server 6.5 and later</li> </ul>
<b>Action</b>	You can suspend all triggers in the project properties.
<b>DEP.0005.0447I</b>	<b>The "{0}" file was deployed.</b>
<b>Explanation</b>	This message occurs when a user deploys files.
<b>Action</b>	Check whether the files are deployed or not.
<b>DEP.0005.0449E</b>	<b>Deployer could not suspend the adapter notifications. Adapter suspension is supported only with Integration Server 6.5 and later.</b>
<b>Explanation</b>	Adapter notifications could not be suspended because this functionality is only supported for Integration Server 6.5 and later.
<b>Action</b>	None.

<b>DEP.0005.0457E</b>	<b>Suspend adapter notifications prior to deploying packages. Failure to suspend adapter notifications during deployment can cause problems on the target.</b>
<b>Explanation</b>	Adapter notifications were not suspended prior to package deployment.
<b>Action</b>	Check the Integration Server logs and error messages in the output report for more information.
<b>DEP.0005.0458E</b>	<b>Deployer suspended adapter notification "{0}" but could not verify status.</b>
<b>Explanation</b>	Deployer suspended the adapter notification but was unable to verify its status after the suspension.
<b>Action</b>	For more information, check the Integration Server logs and error messages in the output report.
<b>DEP.0005.0459E</b>	<b>Deployer resumed adapter notification "{0}" but could not verify status.</b>
<b>Explanation</b>	Deployer resumed adapter notification but could not verify the status.
<b>Action</b>	Check the Integration Server logs and error messages in the output report for more information.
<b>DEP.0005.0460E</b>	<b>Suspend trigger "{0}" failed: {1}</b>
<b>Explanation</b>	Deployer could not suspend the trigger.
<b>Action</b>	Check the Integration Server logs and error messages in the output report for more information.
<b>DEP.0005.0461E</b>	<b>Suspend adapter notification "{0}" failed: {1}</b>
<b>Explanation</b>	Suspension of adapter notification failed.
<b>Action</b>	Recreate the build and deploy again. If the problem persists, check the target server adapter settings.
<b>DEP.0005.0477E</b>	<b>The source group has no name. Deployer cannot deploy an undefined group.</b>
<b>Explanation</b>	This message occurs when Deployer attempts to roll back an undefined group.
<b>Action</b>	Verify that the specified group is defined on the source server.
<b>DEP.0005.0482E</b>	<b>The source ACL has no name. Deployer cannot deploy an undefined ACL.</b>
<b>Explanation</b>	Deployer attempted to roll back an undefined ACL.
<b>Action</b>	Verify that the specified ACL exists on the source server.

<b>DEP.0005.0492</b>	<b>The Extended Setting in the source has no name. Deployer cannot deploy an undefined Extended Setting.</b>
<b>Explanation</b>	This message occurs when Deployer attempts to roll back of an undefined Extended Setting.
<b>Action</b>	Verify that the specified Extended Setting exists on the target server.
<b>DEP.0005.0496E</b>	<b>The Trading Networks instance is not currently available on the target server "{0}". Please check your network connection and verify that the Trading Networks instance is installed, configured, and running.</b>
<b>Explanation</b>	The target Trading Networks server is not accessible due to a network connection problem.
<b>Action</b>	Check your network connection. Verify that the Trading Networks instance is installed, configured, and running.
<b>DEP.0005.0501E</b>	<b>Deployer issued the following exception after it failed to load the variable substitution object {0}.</b>
<b>Explanation</b>	The map file: <code>&lt;srcDir&gt;\&lt;pkg&gt;\&lt;winDir&gt;\&lt;path&gt;\&lt;projName&gt;\&lt;mapName&gt;\&lt;dynamicName&gt;\&lt;targetName&gt;.ml</code> is either corrupt or not present.
<b>Action</b>	Verify that the map file exists. If it does, you might need to use Deployer to recreate your map and variable substitution actions.
<b>DEP.0005.0505E</b>	<b>ERROR: Failed to generate IData for Port. The following exception was thrown: {0}</b>
<b>Explanation</b>	The port type is unknown. This indicates that your version of Deployer is out of date.
<b>Action</b>	See the error log of the Deployer server.
<b>DEP.0005.0506</b>	<b>Variable {2}, in {0} "{1}" will be changed from "{3}" to "{4}" on the target system.</b>
<b>Explanation</b>	This message is displayed in the deployment report when the variable is substituted during deployment.
<b>Action</b>	Verify that the displayed variables are substituted.
<b>DEP.0005.0600E</b>	<b>The target server is Integration Server {0}, which does not support this feature. Deployer cannot update the following adapter connections with the variable substitution values: {1}</b>
<b>Explanation</b>	The version of the target Integration Server is a version prior to version 6.1. Versions of the Integration Server prior to 6.1 do not support the APIs that are required to update the adapter connections.
<b>Action</b>	Either upgrade the target Integration Server to version 6.1 or later, or manually update the Adapter connections on the target system.

<b>DEP.0005.0615E</b>	<b>Deployer encountered an error while retrieving current values for adapter connection "{0}".</b>
<b>Explanation</b>	Deployer invoked the <code>wm.art.admin.connection:getResourceConfiguration</code> service but was unable to get current values for the adapter connection in the vars sub page.
<b>Action</b>	The <code>wm.art.admin.connection:getResourceConfiguration</code> service might not be operational or the WmART package is not installed on the target machine. Verify that both the service and the package are installed and operational.
<b>DEP.0005.0706</b>	<b>Rollback failed. For more information, see the rollback report and the Integration Server log.</b>
<b>Explanation</b>	This message occurs when a rollback operation fails.
<b>Action</b>	Review the rollback report and take appropriate action.
<b>DEP.0005.0850E</b>	<b>Deployer issued the following error while rolling back the contact type: "{0}"</b>
<b>Explanation</b>	Deployer issued an exception while rolling back the contact type.
<b>Action</b>	Contact the Trading Networks target administrator.
<b>DEP.0005.0851E</b>	<b>Deployer issued the following exception while deleting the document type during rollback: "{0}"</b>
<b>Explanation</b>	An exception occurred while deleting the document type.
<b>Action</b>	Contact the administrator of the target Trading Networks system for assistance.
<b>DEP.0005.0852E</b>	<b>Deployer issued the following exception while deleting the field group during rollback: "{0}"</b>
<b>Explanation</b>	An exception occurred while deleting the field group.
<b>Action</b>	Contact the administrator of the target server for assistance.
<b>DEP.0005.0854E</b>	<b>Deployer issued the following exception while deleting the external ID type during rollback: "{0}".</b>
<b>Explanation</b>	An exception occurred while deleting the external ID type during rollback.
<b>Action</b>	Verify that target server is running, then try the deleting the external ID type again.

DEP.0005.0856E	<b>Deployer issued the following exception while deleting the processing rule during rollback: "{0}"</b>
<b>Explanation</b>	An exception occurred while deleting the processing rule.
<b>Action</b>	Contact the administrator of the target server for assistance.
DEP.0005.0858E	<b>Deployer issued the following exception while deleting the profile during rollback: "{0}"</b>
<b>Explanation</b>	An exception occurred while deleting the profile.
<b>Action</b>	Verify that the target server is running. Then try the deletion again.
DEP.0005.0859E	<b>Deployer could not suspend the "{0}" scheduled service type with service name "{1}" because it was deployed to a clustered Integration Server.</b>
<b>Explanation</b>	The service was deployed to a clustered Integration Server and could not be suspended.
<b>Action</b>	Suspend the service manually at each target.
DEP.0005.0860E	<b>Deployer could not resume the scheduled service type "{0}" with service name "{1}". The service was deployed to a clustered Integration Server and could not be resumed. You must resume the service manually at each target.</b>
<b>Explanation</b>	The service was deployed to a clustered Integration Server and could not be resumed.
<b>Action</b>	Resume the service manually at each target.
DEP.0005.0861E	<b>Scheduled services are being deployed to a clustered Integration Server and cannot be started after deployment.</b>
<b>Explanation</b>	Scheduled services cannot be started on the clustered target.
<b>Action</b>	Start the services manually on each clustered target.
DEP.0005.0862E	<b>Scheduled services have been deployed to a clustered Integration Server and were not suspended after deployment. If suspension is required, then do so manually at each target.</b>
<b>Explanation</b>	Scheduled services could not be suspended at the clustered target after deployment
<b>Action</b>	Suspend the services manually at each target.

<b>DEP.0005.0864E</b>	<b>Deployer requires that scheduled services be updated at a clustered Integration Server, but this is not supported with this release. You can update the scheduled services by deploying them to each of the individual Integration Servers in the cluster.</b>
<b>Explanation</b>	This deployment candidate requires that scheduled services be updated at a clustered Integration Server, which is not supported with this release.
<b>Action</b>	Update the services by deploying to each of the individual Integration Servers in the cluster.
<b>DEP.0005.0869E</b>	<b>The deployment failed and Deployer is performing an automatic rollback. Please see the separate rollback report for more information about the failed deployment.</b>
<b>Explanation</b>	This message occurs when a deployment fails and an automatic rollback occurs.
<b>Action</b>	Please see the Rollback report and take appropriate action.
<b>DEP.0005.1003E</b>	<b>An IO exception occurred while attempting to access: "{0}". Exception details follow: "{1}".</b>
<b>Explanation</b>	An exception occurred when Deployer tried to create, write data to, or save a file. This exception can occur for the following reasons: <ul style="list-style-type: none"> <li>- The I/O operation failed or was interrupted while accessing the build file.</li> <li>- A security violation has occurred, which typically means that the user running Deployer lacks appropriate privileges to access the files.</li> </ul>
<b>Action</b>	Verify that the file system is not corrupt and that adequate disk space is available for creating, writing, and/or saving new files. Also verify that the user has proper privileges to create, write, and save files on the file system.
<b>DEP.0005.1004E</b>	<b>An exception occurred while attempting to access "{0}". Exception details follow: "{1}".</b>
<b>Explanation</b>	An exception occurred when Deployer tried to access (that is, create, save, read, or load) the indicated <object>, where <object> is one of the following: checkpoint, deployment, build, deployReport, targetFileName, or targetServer. Possible causes of the exception include the following: <ul style="list-style-type: none"> <li>- The deployment, reportFiles, or targetFile Object could not be loaded from the file system.</li> <li>- An I/O operation failed or was interrupted while accessing the build or checkpoint file.</li> <li>- A security violation has occurred, which typically means that the user running Deployer does not have privileges to access files necessary to perform the deploy operation.</li> <li>- A target Integration Server Adapter and/or Trigger could not be suspended/resumed.</li> </ul>

	<ul style="list-style-type: none"> <li>- A variable substitution failed.</li> <li>- Deployer could not obtain a connection to a target server.</li> </ul>
<b>Action</b>	<p>Verify the following:</p> <ul style="list-style-type: none"> <li>- The file system is not corrupt.</li> <li>- Adequate disk space is available for creating and/or saving new files.</li> <li>- The user attempting this action has the proper authority to create and save files on the file system.</li> <li>- The target server is running, and is reachable on the network.</li> </ul>
<b>DEP.0005.1005E</b>	<b>You are not authorized to deploy the "{0}" project.</b>
<b>Explanation</b>	The user does not have the authorization to deploy the specified project.
<b>Action</b>	Ask an administrator or user that has deploy authorization to perform the action for you. Alternatively, have an administrator update your authorization to assign you deploy authorization for the project.
<b>DEP.0005.1006E</b>	<b>You are not authorized to deploy the "{0}" project for the following reason: "{1}".</b>
<b>Explanation</b>	An error occurred when invoking the service on the host Integration Server. Integration Server cannot determine whether the user is authorized to deploy the specified project.
<b>Action</b>	Verify that the host Integration Server is still running. If you are running Deployer from a remote location, verify the network connectivity between the Deployer user interface and the server.
<b>DEP.0005.1007E</b>	<b>The following exception occurred while attempting to process "{0}": "{1}"</b>
<b>Explanation</b>	<p>In the message, &lt;subMessage&gt; is one of the following sub-messages that Deployer displays to provide additional information about the exception: -&lt;targetFileName&gt; - An exception occurred while performing a [remote] invoke of the service: &lt;ISServiceName&gt;. Exception details follow: &lt;exceptionInfo&gt; - An exception occurred while attempting to XMLDecode the file: &lt;buildFileName&gt;. Exception details follow: &lt;exceptionInfo&gt;. - &lt;errorMessageReturnedFromIS&gt; - An exception occurred getting a Trading Networks, TN, docType object. That is most likely caused by a user-defined extension to the TN type BizDocType. Copy the jar files, which should be found in the &lt;webM install dir&gt; \ \IntegrationServer \ \packages \ \WmTN \ \code \ \jars directory, containing those extensions into the WmDeployer/code/jars directory. - Source package is of type upgrade and required target package version is null. - Error: no Logical Server for Server ID" The most-likely fix for that is to use webMethods Administrator on your target server to define a logical server with the name: &lt;sourceSystemName&gt;. - An Exception occurred while attempting to IDataBinCoder the file: '&lt;buildFileName&gt;'. Exception details follow: &lt;exceptionInfo&gt; - Overwrite 'everything else' field is set to &lt;overwriteEverythingElseString&gt;, which is invalid. - The Port: &lt;sourcePortName&gt;, associated with Package: &lt;packageName&gt; - Disabling</p>

of the Port: <sourcePortName>, associated with Package: <packageName> - Enabling of the Port: <sourcePortName>, associated with Package: <packageName> - Resuming the scheduled-service: " + scheduledServiceName - Suspending the scheduled-service: " + scheduledServiceName - <serviceName> - A SOAP fault occurred while performing a remote invoke of the service: <ISServiceName>.The SOAP Fault string follows: <faultString> - Getting information about the Port: <sourcePortName>, associated with Package: <packageName> The reason for the exception can be one of the following:

- There is a problem with connectivity to the target Integration Server.
- The target Integration Server is not running.
- The target Integration Server requires a Broker Server, but no Broker Server is connected to it.
- There is a user-defined extension to a Trading Networks document type, and Deployer does not have access to the associated jar files.
- You specified a partial package for deployment; however, the package does not exist on the target.
- You specified a logical server that is not defined on the target.
- The overwrite flag is invalid, which can only occur if the build file was manually edited.

**Action**

Based on the reason for the exception, perform one of the following:

- Verify the network connectivity between the Deployer server and each target server.
- Verify that each target server is running.
- If the target Integration Server requires that a Broker be connected to it, ensure that a Broker is connected.
- If a user-defined Trading Networks document type is in use, ensure Deployer has access to the associated jar files. To do so copy the jar files located in the <serverDirectory>\packages\WmTN\code\jars directory (which contain the Trading Networks document type extensions) to the <serverDirectory>\packages\WmDeployer\code\jars directory.
- If you specified a partial package and the package does not exist on the target, either remove the package from the deployment or specify a full package for deployment.
- If the definition of a logical server is missing, use webMethods Administrator on your target server to define a logical server with the name indicated in the error message.
- If the overwrite flag is invalid, ensure that your build file has not been manually edited.

<b>DEP.0005.1008E</b>	<b>The deploy report: "{0}" already exists. Please move it to a different directory.</b>
<b>Explanation</b>	The deploy report already exists.
<b>Action</b>	Move the existing deploy report file to a different directory.
<b>DEP.0005.1010</b>	<b>An error occurred interacting with server: "{0}". Exception details follow: "{1}"</b>
<b>Explanation</b>	This error occurs if the servers in a cluster are not up and running or if the cluster is invalid for some reason.
<b>Action</b>	Verify that the cluster is configured correctly and that all servers are up and running.
<b>DEP.0005.1011E</b>	<b>Error invoking service wm.deployer.UIAuthorization. Contact Software AG support.</b>
<b>Explanation</b>	Error invoking service wm.deployer.UIAuthorization.
<b>Action</b>	Contact Software AG support.
<b>DEP.0005.1014E</b>	<b>An exception occurred while attempting to close the file "{0}". This will not affect deployment, but will keep a lock on the file. Exception details follow: "{1}"</b>
<b>Explanation</b>	The build file could not be closed because an I/O exception occurred. The exception can occur for the following reasons:  <ul style="list-style-type: none"> <li>- The I/O operation failed or was interrupted while accessing the build file.</li> <li>- A security violation has occurred, which typically means that the user running Deployer does not have correct privileges to access the files.</li> </ul>
<b>Action</b>	Verify that the file system is not corrupt and that adequate disk space is available for saving new files. Also verify that the user attempting this action has proper privileges to save files on the file system.
<b>DEP.0005.1015E</b>	<b>The Overwrite Existing field is set to {0}, which is invalid.</b>
<b>Explanation</b>	The overwrite flag was set to a value that the code did not recognize. This occurs when a user has manually edited the XML in the target file.
<b>Action</b>	Repeat the build and map steps. Do not manually edit the target file.
<b>DEP.0005.1018E</b>	<b>A null aliasValues IData was returned from the invocation of wm.server.remote:getAliasValue against remote host: {0} Cannot continue with deployment of Trading Networks. Make sure the WmTN package and the Trading Networks JDBC pool on the target server are enabled.</b>
<b>Explanation</b>	Deployer invoked the wm.server.remote:getAliasValue service while deploying Trading Networks assets, and a null value was returned.
<b>Action</b>	Make sure the WmTN package and the Trading Networks JDBC pool on the target server are enabled.

**DEP.0005.1024E**      **The target cluster {0} is not currently available. Deployer is skipping that cluster. Check your network connection and make sure all target servers ({1}) are running within the cluster.**

**Explanation**      Deployer cannot connect to the target cluster servers due to network connection problems.

**Action**            Check your network connection. You should be able to access the target server machines.

**DEP.0005.1025W**      **webMethods Deployer does not support deployment of certificates. Certificates for profile "{0}" will not be deployed.**

**Explanation**      Deployer does not support the deployment of certificates.

**Action**            Deployer does not support deployment of certificates. Certificates for profile "{0}" will not be deployed.

**DEP.0005.1026E**      **Deployer cannot enable adapter connection {0} on target {1}. Make sure the pub.art.connection:enableConnection service is operational and the WmART package is installed on the target server.**

**Explanation**      Deployer invoked the pub.art.connection:enableConnection service but could not enable adapter notification on the target server after deployment.

**Action**            Make sure the pub.art.connection:enableConnection service is operational and the WmART package is installed on the target server.

**DEP.0005.1027E**      **Adapter connection {0} on target {1} is not enabled. Make sure the pub.art.connection:queryConnectionState service is operational and the WmART package is installed on the target server.**

**Explanation**      Deployer invoked the pub.art.connection:queryConnectionState service but could not enable adapter connections on the target server after deployment.

**Action**            Make sure the pub.art.connection:queryConnectionState service is operational and the WmART package is installed on the target server.

**DEP.0005.1028E**      **Deployer cannot update adapter connection "{0}" on target "{1}".**

**Explanation**      Deployer invoked the wm.art.dev.connection:updateConnectionNode service but could not update adapter connections on the target server after deployment.

**Action**            Make sure the wm.art.dev.connection:updateConnectionNode service is operational and the WmART package is installed on the target server.

<b>DEP.0005.1029E</b>	<b>Unable to disable adapter connection {0} on target {1}. Check the Integration Server logs and error messages in the output report for more information.</b>
<b>Explanation</b>	Unable to disable adapter connection on target.
<b>Action</b>	Check the Integration Server logs and error messages in the output report for more information.
<b>DEP.0005.1030E</b>	<b>Deployer encountered an error retrieving current values for adapter connection {0} on target {1}. Make sure the <code>wm.art.admin.connection:getResourceConfiguration</code> service is operational and the WmART package is installed on the target server.</b>
<b>Explanation</b>	Deployer invoked the <code>wm.art.admin.connection:getResourceConfiguration</code> service but could not get current values for the adapter connection in the varsub page.
<b>Action</b>	Make sure the <code>wm.art.admin.connection:getResourceConfiguration</code> service is operational and the WmART package is installed on the target server.
<b>DEP.0005.1031E</b>	<b>Deployer cannot set the adapter notification for {0} on target {1}. The selected adapter notification might be active on the target server. Review the project settings.</b>
<b>Explanation</b>	Deployer could not set variable substitution values for adapter notification.
<b>Action</b>	The selected adapter notification might be active on the target server. Review project settings to make sure they are appropriate.
<b>DEP.0005.1032E</b>	<b>The adapter notification for {0} on target {1} is not enabled.</b>
<b>Explanation</b>	Deployer invoked the <code>pub.art.notification:queryPollingNotificationState</code> service but could not enable adapter notification on the target server after deployment.
<b>Action</b>	Make sure the <code>pub.art.notification:queryPollingNotificationState</code> service is operational and the WmART package is installed on the target server.
<b>DEP.0005.1033E</b>	<b>Deployer cannot enable adapter notification for {0} on target {1}.</b>
<b>Explanation</b>	Deployer invoked the <code>pub.art.notification:enablePollingNotification</code> service, but could not enable adapter notification on the target server after deployment.
<b>Action</b>	Make sure the <code>pub.art.notification:enablePollingNotification</code> service is operational and the WmART package is installed on the target server.
<b>DEP.0005.1034E</b>	<b>Deployer cannot disable the adapter notification for {0} on target {1}. Check the Integration Server logs for more information. Re-create the build and redeploy if necessary.</b>
<b>Explanation</b>	Deployer cannot disable adapter notification.
<b>Action</b>	Check the Integration Server logs for more information. Re-create the build and deploy again if necessary.

<b>DEP.0005.1039E</b>	<b>Deployer cannot find the deployment reports for deployment candidate {0}.</b>
<b>Explanation</b>	There are no reports for the deployment candidate.
<b>Action</b>	Try to view the reports using a simulate or deploy operation.
<b>DEP.0005.1040E</b>	<b>Invalid ID for deployment report. Please use the list command to verify your inputs.</b>
<b>Explanation</b>	This message occurs when a Deployer user attempts to view the deployment report through command line interface and the report ID does not exist.
<b>Action</b>	Perform simulate and deploy operations and refer to the report ID shown.
<b>DEP.0005.1041E</b>	<b>Deployer cannot read report {0}.</b>
<b>Explanation</b>	This message occurs when Deployer is unable to display reports in a browser.
<b>Action</b>	Ensure that the report HTML or XML files are valid and not corrupted.
<b>DEP.0005.1045E</b>	<b>An error occurred while attempting to import functional permissions: class: "{0}", message: "{1}"</b>
<b>Explanation</b>	This error occurs when Deployer is unable to deploy Trading Network functional permissions, and it indicates that there might be a problem with the build.
<b>Action</b>	Verify that the selected functional permissions are valid on the source server, and rebuild if necessary.
<b>DEP.0005.1049E</b>	<b>An exception occurred while deleting DLS "{0}"</b>
<b>Explanation</b>	An exception occurred while deleting DLS.
<b>Action</b>	Contact the administrator of the target Trading Networks system for assistance.
<b>DEP.0005.1050E</b>	<b>An exception occurred while deleting the "{0}" functional permission.</b>
<b>Explanation</b>	An exception occurred while deleting the functional permission.
<b>Action</b>	Verify that the target server is running and try the deletion again.
<b>DEP.0005.1055E</b>	<b>An error occurred while attempting to import DLSs. The following is the error information from Trading Networks: class: "{0}", message: "{1}"</b>
<b>Explanation</b>	Deployer displays this error when it cannot deploy Trading Network DLSs. It indicates that there might be a problem with the build.
<b>Action</b>	Verify that the selected DLSs are valid on the source server and rebuild if necessary.

---

DEP.0005.1057E	<b>Invalid ID for build report. Use the list command to verify your inputs.</b>
<b>Explanation</b>	Deployer displays this message when a Deployer user attempts to view the build report through the command line interface and the specified report ID does not exist.
<b>Action</b>	Perform a build operation on the deployment sets and refer to the build report ID shown.
DEP.0005.1058E	<b>Unable to read JMS trigger {0}.</b>
<b>Explanation</b>	Deployer is unable to read the JMS trigger files from the source server.
<b>Action</b>	Ensure that the JMS trigger was created properly on the source server.
DEP.0005.1059E	<b>Unable to read build zip file.</b>
<b>Explanation</b>	Deployer is unable to read the build zip file while deploying.
<b>Action</b>	Verify that the project build file is correct, and ensure that it has not been corrupted.
DEP.0005.1060E	<b>Error deploying to cluster. One or more of the nodes in the cluster are not running. Check the cluster configuration and the extended settings for further information.</b>
<b>Explanation</b>	Not all of the nodes in the cluster are running.
<b>Action</b>	Check the cluster configuration and the extended settings.
DEP.0005.1063	<b>Action failed: The target server is unavailable. See the Integration Server logs for more information.</b>
<b>Explanation</b>	The target server is not available.
<b>Action</b>	Check the Integration Server logs for any relevant errors or messages.
DEP.0005.1067E	<b>An error occurred while attempting to import archival services. The following is the error information from Trading Networks:&lt;p&gt;class: "{0}", message: "{1}"&lt;/p&gt;</b>
<b>Explanation</b>	This error occurs when Deployer is unable to deploy the Trading Networks archival services and indicates that there might be a problem with the build.
<b>Action</b>	Verify that the selected archival services are valid on the source server and rebuild if necessary.
DEP.0005.1068E	<b>Automatic rollback in logical cluster group {0} failed because the connection to target server {1} was refused.</b>
<b>Explanation</b>	Deployer displays this message when an automatic rollback fails.
<b>Action</b>	Ensure that the specified server is online and that the network connection works. For more information, see the rollback report and take appropriate action.

**DEP.0005.1069E**      **Deployment in logical cluster group {0} failed. Connection to target server {1} was refused. Deployer will perform rollback on logical group {2}.**

**Explanation**      This error occurs when Deployer is unable to deploy assets to a logical cluster group of target servers.

**Action**      Verify that the servers in the logical cluster group are online and available.

**DEP.0005.1074E**      **Deployer cannot import Trading Networks partner profiles without a My Enterprise profile.**

**Explanation**      Deployer was unable to deploy the Trading Networks partner profile.

**Action**      Verify that a My Enterprise profile exists on the target server. If not, you must deploy the My Enterprise profile first.

**DEP.0005.1076E**      **Deployer encountered an exception while trying to delete {0}. Exception details follow: "{1}"**

**Explanation**      An exception occurred while trying to delete the node.

**Action**      Refresh the node list and try deleting again.

**DEP.0005.1125E**      **Assets in deletion set {0} have unresolved dependencies. Either add the dependent assets or remove the existing assets from the deletion set.**

**Explanation**      Assets in the deletion set have unresolved dependencies.

**Action**      Add the dependent assets, or remove the existing assets from the deletion set.

**DEP.0005.1126E**      **Deployment to a logical cluster failed and Deployer performed a rollback. Refer to the deployment and rollback reports for more details.**

**Explanation**      Deployment to a logical cluster failed and rollback has occurred.

**Action**      See the deployment and rollback reports for more details.

**DEP.0005.1129E**      **Error occured when deploying file to a Target. Please check the target Integration Server logs for details. {0}**

**Explanation**      This error occurs when deploying large files. It indicates that the target server WmDeployerResource package is not operational.

**Action**      Verify that the WmDeployerResource package is installed on the target server. If it is already installed, try re-installing.

<b>DEP.0005.1130E</b>	<b>An error occurred while creating or reading the streaming file {0} corresponding to {1} in the build. Check the target Integration Server logs for details.</b>
<b>Explanation</b>	This error occurs when extracting large files from a source server. It indicates that the WmDeployerResource package is not operational.
<b>Action</b>	Verify that the WmDeployerResource package is installed on the target server. If it is already installed, try re-installing.
<b>DEP.0005.1135E</b>	<b>The deployment or deletion set "{0}" contains unresolved dependencies or references. Please resolve the unresolved dependencies to continue with deployment.</b>
<b>Explanation</b>	The deployment or deletion set contains unresolved dependencies or references.
<b>Action</b>	Resolve the unresolved dependencies or references for the deployment or deletion sets in your project.
<b>DEP.0005.1152E</b>	<b>The delivery of artifacts to the {0} target server failed. For details, check the logs of the target server.</b>
<b>Explanation</b>	The delivery of artifacts to the target server failed.
<b>Action</b>	For more information, check the deployment report and the Integration Server log.
<b>DEP.0005.1153E</b>	<b>The activation of artifacts on the {0} target server failed. For details, check the logs of the target server.</b>
<b>Explanation</b>	The activation of artifacts on the target server failed.
<b>Action</b>	For details, check the deployment report and the Integration Server log.
<b>DEP.0005.1161E</b>	<b>Deployer could not deliver artifacts to {0} because the server is unavailable.</b>
<b>Explanation</b>	The target server is unavailable.
<b>Action</b>	Ensure the target server is running.
<b>DEP.0005.1167E</b>	<b>Unable to delete artifacts previously delivered to {0} because the server is unavailable.</b>
<b>Explanation</b>	The target server is unavailable.
<b>Action</b>	Make sure the target server is running.

<b>DEP.0005.1173E</b>	<b>Skipping the activation of deployment on {0} because the target server is unavailable.</b>
<b>Explanation</b>	Target server is unavailable.
<b>Action</b>	Ensure target server is running.
<b>DEP.0005.1183E</b>	<b>A simulation initiated by user {0} for deployment candidate {1} of project {2} is in progress. Wait until the simulation in progress is complete.</b>
<b>Explanation</b>	Another user is running an operation for this project.
<b>Action</b>	Wait until the other operation finishes.
<b>DEP.0005.1184E</b>	<b>A deployment initiated by the user {0} for deployment candidate {1} of project {2} is in progress. Wait until the deployment in progress is complete.</b>
<b>Explanation</b>	Another user is running an operation for this project.
<b>Action</b>	Wait until the other operation finishes.
<b>DEP.0005.1185E</b>	<b>A rollback initiated by user {0} for deployment candidate {1} of project {2} is in progress. Wait until the rollback in progress is complete.</b>
<b>Explanation</b>	Another user is running an operation for this project.
<b>Action</b>	Wait until the other operation finishes.
<b>DEP.0005.1186E</b>	<b>A checkpoint initiated by user {0} for deployment candidate {1} of project {2} is in progress. Wait until the checkpoint in progress is complete.</b>
<b>Explanation</b>	Another user is running an operation for this project.
<b>Action</b>	Wait until the other operation finishes.
<b>DEP.0005.1187E</b>	<b>You cannot deploy the {0} project because it is not locked.</b>
<b>Explanation</b>	The project was not locked before deployment.
<b>Action</b>	Lock the project.
<b>DEP.0005.1188E</b>	<b>You cannot deploy the {0} project because it is locked by another user.</b>
<b>Explanation</b>	Another user has locked the project.
<b>Action</b>	Wait until the project is unlocked by the other user.

<b>DEP.0005.1189E</b>	<b>You cannot simulate the deployment for the {0} project because it is not locked.</b>
<b>Explanation</b>	The project was not locked before simulation.
<b>Action</b>	Lock the project.
<b>DEP.0005.1190E</b>	<b>You cannot simulate the deployment for the {0} project because it is locked by another user.</b>
<b>Explanation</b>	Another user has locked the project.
<b>Action</b>	Wait until the project is unlocked by the other user.
<b>DEP.0005.1191E</b>	<b>You cannot rollback the deployment for the {0} project because it is not locked.</b>
<b>Explanation</b>	The project was not locked before you attempted to roll back the deployment.
<b>Action</b>	Lock the project.
<b>DEP.0005.1192E</b>	<b>You cannot rollback the deployment for the {0} project because it is locked by another user.</b>
<b>Explanation</b>	Another user has locked the project.
<b>Action</b>	Wait until the project is unlocked by the other user.
<b>DEP.0005.1193E</b>	<b>You are not authorized to generate a checkpoint for the {0} project because it is not locked.</b>
<b>Explanation</b>	The project was not locked before you attempted to generate a checkpoint.
<b>Action</b>	Lock the project.
<b>DEP.0005.1194E</b>	<b>You are not authorized to generate a checkpoint for the {0} project because it is locked by a different user.</b>
<b>Explanation</b>	Another user has locked the project.
<b>Action</b>	Wait until the project is unlocked by the other user.
<b>DEP.0005.1195E</b>	<b>The deletion of delivered to the {0} target server artifacts failed. For details, check the logs of the target server.</b>
<b>Explanation</b>	The deletion of delivered to the target server artifacts failed.
<b>Action</b>	Check the deployment report for details. There might be additional information in the log of Integration Server.

<b>DEP.0005.1201E</b>	<b>Repository-based deployment does not support the rollback operation for the mapped target servers.</b>
<b>Explanation</b>	Repository-based projects do not support rollback operations for the mapped target servers.
<b>Action</b>	Only Deploy operation is supported.
<b>DEP.0005.1203E</b>	<b>There are no target servers or target groups mapped for deployment candidate {0}.</b>
<b>Explanation</b>	There are no target servers or target groups mapped to the deployment set in the map step.
<b>Action</b>	Map at least one deployment set to a target server or a target group in the map step.
<b>DEP.0005.1204E</b>	<b>The success flag does not match any messages returned by the target server {0}.</b>
<b>Explanation</b>	Either the target server returned the success flag of true and the messages from the target server contains error messages, or the target returned a success flag of false and the message from the target server does not contain an error message.
<b>Action</b>	Check the target server logs or contact Software AG Global Support.
<b>DEP.0005.1206E</b>	<b>An error occurred while saving deployment candidate {0}.</b>
<b>Explanation</b>	An error encountered while saving the deployment candidate.
<b>Action</b>	Contact Software AG Global Support.
<b>DEP.0005.1210E</b>	<b>Deployer did not delete the assets from {0} because the server is unavailable.</b>
<b>Explanation</b>	The target server is unavailable.
<b>Action</b>	Ensure target server is running.
<b>DEP.0005.1212E</b>	<b>Deployer failed to delete the assets on the target server {0}. For more information, see the target server's logs.</b>
<b>Explanation</b>	The deletion of assets on the target server failed.
<b>Action</b>	Check the deployment report and the Integration Server log for details.
<b>DEP.0005.1215E</b>	<b>Deployer failed to delete the assets on the target server {0}. For more information, see the target server's logs.</b>
<b>Explanation</b>	The deletion of assets on the target server failed.
<b>Action</b>	Check the deployment report for details. There might be additional information in the Integration Server log.

---

<b>DEP.0005.1216E</b>	<b>Target server {0} did not return any messages.</b>
<b>Explanation</b>	Deployer did not receive any messages from target server {0}.
<b>Action</b>	Check the target server log for details.
<b>DEP.0005.1217E</b>	<b>Deletion set {0} contains unresolved dependencies. Please resolve the dependencies to proceed with deployment.</b>
<b>Explanation</b>	The deletion set contains unresolved dependencies.
<b>Action</b>	Resolve the unresolved dependencies for the deletion set.
<b>DEP.0005.1218E</b>	<b>Repository-based deployment does not support the rollback operation for target servers of types {0}.</b>
<b>Explanation</b>	Repository-based deployment does not support rollback operation for target servers of the given type.
<b>Action</b>	Remove the assets of the unsupported runtimes from the deployment and deletion sets and update the deployment map accordingly.
<b>DEP.0005.1219E</b>	<b>Repository-based deployment does not support the simulate operation for target servers of types {0}.</b>
<b>Explanation</b>	Repository-based deployment does not support simulate operation for target servers of the given type.
<b>Action</b>	Remove the assets of the unsupported runtimes from the deployment and deletion sets and update the deployment map accordingly.
<b>DEP.0005.1220E</b>	<b>Repository-based deployment does not support deletion sets for target servers of types {0}.</b>
<b>Explanation</b>	Repository-based deployment does not support deletion sets for target servers of the given type.
<b>Action</b>	Remove the assets of the unsupported runtimes from the deletion set and update the deployment map accordingly.
<b>DEP.0005.1221E</b>	<b>Repository-based deployment does not support deletion sets for the selected target servers.</b>
<b>Explanation</b>	Repository-based deployment does not support deletion sets for the selected target servers.
<b>Action</b>	Remove the deletion set from the project.

**DEP.0005.1222E**      **The repository is corrupted. The binary file for composite {0} of type {1} is missing from repository {2}.**

**Explanation**      The binary file is missing from the repository.

**Action**            Rebuild the repository using Asset Build Environment.

**DEP.0005.1227E**      **Deployer issued the following exception while deleting the field definition during rollback: "{0}"**

**Explanation**      An exception occurred while deleting the field definition.

**Action**            Contact the administrator of the target server for assistance.

**DEP.0005.1230**      **No value was specified for the required package parameter. Specify a value for the package parameter.**

**Explanation**      No value was specified for the package parameter.

**Action**            Specify a valid package value for the package parameter.

**DEP.0006.0011E**      **Plugin {0} does not exist.**

**Explanation**      The specified plug-in is not correctly configured in the Deployer plugin configuration file. This indicates an incomplete or damaged installation, or possibly a modification to the plugin configuration file located in  
<serverDirectory>\packages\WmDeployer\config\plugin folder.

**Action**            Make sure a file named <pluginName>.cnf exists in the  
<serverDirectory>\packages\WmDeployer\config\plugin directory.

**DEP.0006.0025E**      **The versions for the aliases {0} were not persisted successfully. Verify that the specified version is valid.**

**Explanation**      The specified versions are not valid.

**Action**            Ensure that the specified versions are valid.

**DEP.0006.0026E**      **The version {0} reported by the {1} plugin for the server alias {2} does not match the version {3} set by the user.**

**Explanation**      The version reported by the plugin is different from the version set for the server alias.

**Action**            Set the correct version for the server alias.

<b>DEP.0006.0028E</b>	<b>Plugin server name {0} contains illegal characters.</b>
<b>Explanation</b>	The plugin server name contains one or more spaces or the following invalid characters: # & @ ^ ! % * : \$ / \ \ ` ' ; , ~ + = > < \ "
<b>Action</b>	Remove the invalid characters from the plugin server name.
<b>DEP.0006.0030E</b>	<b>Plugin server {0} of type {1} does not exist for the specified runtime type. Create a new plugin server or remove it from the project map.</b>
<b>Explanation</b>	The plugin server does not exist for the specified runtime type.
<b>Action</b>	Create a new plugin server or remove it from the project map.
<b>DEP.0007.0001E</b>	<b>A target group with the name {0} already exists.</b>
<b>Explanation</b>	You specified a name for a target group that already exists. Deployer requires that target groups be uniquely named.
<b>Action</b>	Specify a unique name for the target group.
<b>DEP.0007.0002E</b>	<b>Target group {0} does not exist.</b>
<b>Explanation</b>	The specified target group does not exist
<b>Action</b>	Verify that the target group exists in the Deployer server target groups.
<b>DEP.0007.0005E</b>	<b>Error invoking service {0}. This usually indicates a problem with the Integration Server installation. On the local Deployer server, determine whether the following Integration Server packages are disabled, missing, or missing parts: WmDeployer, WmAdmin, WmRoot, WmDeployerResource, WmModeler.</b>
<b>Explanation</b>	Deployer was unable to invoke a required Integration Server service. This usually indicates a problem with the Integration Server installation.
<b>Action</b>	On the local Deployer server, determine whether the following Integration Server packages are disabled, missing, or missing parts:
	WmDeployer
	WmAdmin
	WmRoot
	WmDeployerResource
	WmModeler

**DEP.0007.0006E**      **Deployer encountered the following error while invoking getConnectionInfo for system {0}: {1}**

**Explanation**      Deployer could not retrieve the logical server connection information from the source server. The source server might not be running or the logon credentials might be incorrect.

**Action**            Make sure the specified source server is running and that the logon credentials in the plug-in server configuration, including the Port value, are correct.

**DEP.0007.0007E**      **The call to getConnectionInfo for system {0} returned the following exception for host name {1}: {2}**

**Explanation**      Deployer was unable to retrieve the logical server connection information from the source server. The source server might not be running or the logon credentials might be incorrect.

**Action**            Make sure the specified source server is running and that the logon credentials in the plug-in server configuration, including the Port value, are correct.

**DEP.0007.0008E**      **The call to getConnectionInfo for system {0} returned the following missing data: {1} Make sure the specified source server is running and that the logon credentials in the plug-in server configuration, including the Port value, are correct.**

**Explanation**      Deployer was unable to retrieve the logical server connection information from the source server. The source server might not be running or the logon credentials might be incorrect.

**Action**            Make sure the specified source server is running and that the logon credentials in the plug-in server configuration, including the Port value, are correct.

**DEP.0007.0009E**      **Deployer encountered the following error while connecting to Integration Server {0}: {1}**

**Explanation**      Deployer was unable to connect to the specified remote Integration Server. The Integration Server might not be running, or the logon credentials might be incorrect.

**Action**            Make sure the Integration Server is running and that the logon credentials in the remote server configuration, including the Port value, are correct.

**DEP.0007.0010E**      **Deployer encountered the following error while invoking the required Integration Server service {0} on system {1}: {2} This usually indicates an incomplete or error with the installation of a plug-in on the remote server. On the specified remote server, determine whether the following required Integration Server packages are disabled, missing, or incomplete:**

**Explanation**      Deployer was unable to invoke a required Integration Server service. This usually indicates an incomplete or error with the installation of a plug-in on the remote server.

**Action**            On the specified remote server, determine whether the following required Integration Server packages are disabled, missing, or incomplete:

- WmDeployer
- WmAdmin
- WmRoot
- WmDeployerResource
- WmModeler

**DEP.0007.0011**     **A Target Server with name {0} already exists. Rename the target server alias or use a different name for the Target Group.**

**Explanation**     Target servers and target groups cannot have the same names.

**Action**     Rename the target server alias or use a different name for the Target Group.

**DEP.0007.0012E**     **Failed to load the plug-in server configuration file {0}. This indicates that the configuration file has been modified and Deployer can no longer parse the configuration file. Try to delete and then re-add the plug-in server. This should correctly recreate the configuration file. If this fails, send the contents of the server configuration file, located in "<serverDirectory>/packages/WmDeployer/config/pluginServer/<pluginName>" to Software AG Global Support.**

**Explanation**     When Deployer started, it could not successfully load the plug-in server configuration file. This indicates the configuration file has been modified and Deployer can no longer parse the configuration file.

**Action**     Try to delete and then re-add the plug-in server. This should correctly recreate the configuration file. If this fails, send the contents of the server configuration file, located in "<serverDirectory>/packages/WmDeployer/config/pluginServer/<pluginName>" to Software AG Global Support.

**DEP.0007.0013E**     **Failed to save plugin server config file {0}. The plug-in configuration file provided by Software AG does not contain the entry identifying the class necessary to remotely install the communication component. The configuration file may have been altered incorrectly. Reinstall Deployer. Your project data will remain unchanged.**

**Explanation**     The plug-in configuration file provided by Software AG does not contain the entry identifying the class necessary to remotely install the communication component. The configuration file might have been altered incorrectly.

**Action**     Reinstall Deployer. Your project data will remain unchanged.

<b>DEP.0007.0014E</b>	<b>{0} target group {1} dependencies have been resolved. See the Integration Server error log for details. Contact webMethods Global Support if the problem cannot be resolved locally.</b>
<b>Explanation</b>	The invocation of the Communication Component Installation class has failed.
<b>Action</b>	See the Integration Server error log for details. Contact Software AG Global Support if the problem cannot be resolved locally.
<b>DEP.0007.0015E</b>	<b>{0} Target Group {1} validation failed. Unable to resolve some servers within the group. Your installation could be damaged or corrupt. Reinstall Deployer. Your project data will remain unchanged.</b>
<b>Explanation</b>	The remote installation of the communication component was unable to locate the component file on the file system. Your installation could be damaged or corrupt.
<b>Action</b>	Reinstall Deployer. Your project data will remain unchanged.
<b>DEP.0007.0018E</b>	<b>Deployer encountered the following error while pinging plug-in server {0}: {1} Deployer cannot contact the remote server hosting the identified plug-in. The host could be down or the host name could be incorrect. Verify the host name (or IP address) and ensure that the system is available.</b>
<b>Explanation</b>	Deployer cannot contact the remote server hosting the identified plug-in. The host could be down or the host name could be incorrect.
<b>Action</b>	Verify the host name (or IP address) and ensure that the system is available.
<b>DEP.0007.0019E</b>	<b>Plug-in {0} on target group {1} does not contain any servers.</b>
<b>Explanation</b>	You have attempted to add a target group with no servers.
<b>Action</b>	Add target servers in that target group.
<b>DEP.0007.0029</b>	<b>Cannot create a Target Group with same name as that of a Target Server. Either rename the target group or delete the existing target group or target server with the same name.</b>
<b>Explanation</b>	You cannot create a target group with same name as one used by a target server.
<b>Action</b>	Either rename the target group or delete the existing target group or target server with the same name.
<b>DEP.0007.0030</b>	<b>{0} Target Group {1} validation failed. Unable to resolve some servers within the cluster {2} in the group {3}. Make sure all nodes in the cluster are running and the WmDeployerResource package is installed on all of these nodes. If the WmDeployerResource package is not installed, install it using the Deployer user interface.</b>
<b>Explanation</b>	Deployer cannot ping some of the cluster servers.

<b>Action</b>	Make sure all nodes in the cluster are running and the WmDeployerResource package is installed on all of these nodes. If the WmDeployerResource package is not installed, install it using the Deployer user interface.
<b>DEP.0007.0031E</b>	<b>Validation of plug-in {0} on target group {1} failed. Deployer cannot resolve server {2} which is a part of the cluster {3}. Remove this server manually from target group.</b>
<b>Explanation</b>	A server in the cluster could not be resolved.
<b>Action</b>	Manually remove the server from the tagret group.
<b>DEP.0007.0032E</b>	<b>Invalid version specified for the target group {0} of type {1}. The valid versions can be {2}.</b>
<b>Explanation</b>	The version specified for the target group is not valid.
<b>Action</b>	Specify the correct version.
<b>DEP.0007.0033E</b>	<b>The server aliases {0} version do not match the target group {1} version. Server aliases and target groups must be of the same version. Modify either the definition of the targets within the target group or modify the version of the target group.</b>
<b>Explanation</b>	The version of the targets in the target group do not match the version of the parent target group.
<b>Action</b>	Modify either the definition of the targets within the target group or modify the version of the target group.
<b>DEP.0007.0034E</b>	<b>Target group name {0} contains illegal characters.</b>
<b>Explanation</b>	The target group name contains one or more spaces or the following invalid characters: # & @ ^ ! % * : \$ / \ \ ` ' ; , ~ + = > < \ "
<b>Action</b>	Remove the invalid characters from the target group name.
<b>DEP.0007.0035</b>	<b>Target group {0} does not exist.</b>
<b>Explanation</b>	A target group was mapped for deployment but is either not defined or was deleted.
<b>Action</b>	Define the target group.
<b>DEP.0008.0001E</b>	<b>You are not authorized to checkpoint the {0} project. Use the Deployer user interface to grant the user the right to deploy the project.</b>
<b>Explanation</b>	The user is not authorized to generate a checkpoint for the project.
<b>Action</b>	Use the Deployer user interface to grant the user the right to deploy the project.

<b>DEP.0008.0003E</b>	<b>Error invoking service "{0}".</b>
<b>Explanation</b>	An exception occurred while invoking the wm.deployer.UIAuthorization:isAuthorized service. This could mean that Integration Server is either not running or that it cannot be reached on the network.
<b>Action</b>	Verify that the Integration Server is running and available on the network.
<b>DEP.0008.0004E</b>	<b>Error cloning source system "{0}": {1}</b>
<b>Explanation</b>	The project contains a source system of an unknown type.
<b>Action</b>	Rebuild the project.
<b>DEP.0008.0006E</b>	<b>Checkpoint summary file "{0}" does not exist.</b>
<b>Explanation</b>	The checkpoint file does not exist on the disk.
<b>Action</b>	Use Deployer to create a checkpoint.
<b>DEP.0008.0007E</b>	<b>Cannot write to checkpoint directory "{0}".</b>
<b>Explanation</b>	You cannot create or write to the specified directory.
<b>Action</b>	Ensure that you have the correct privileges to create and write to the directory and that the file system has enough space for the creation of a new directory.
<b>DEP.0008.0009E</b>	<b>Error creating checkpoint "{0}": {1}</b>
<b>Explanation</b>	An exception occurred while creating the checkpoint report.
<b>Action</b>	Ensure that you have the correct privileges to create and write to files and that the file system has enough space for the new file.
<b>DEP.0008.0010E</b>	<b>Error saving checkpoint project {0}: {1}. Make sure you have the correct privileges to create and write to files and that the file system has enough space for the new file</b>
<b>Explanation</b>	The specified file could not be saved to disk.
<b>Action</b>	Make sure you have the correct privileges to create and write to files and that the file system has enough space for the new file.
<b>DEP.0008.0013E</b>	<b>Deployer cannot generate a checkpoint at {0} because the target server is unavailable</b>
<b>Explanation</b>	The target server is unavailable.
<b>Action</b>	Ensure that the target server is running.

---

<b>DEP.0008.0015E</b>	<b>Checkpoint on the target server {0} failed. Please check the target server's logs for details.</b>
<b>Explanation</b>	The checkpoint operation failed due to the reason specified in the checkpoint report.
<b>Action</b>	Check the checkpoint report for details. There might also be additional information in the Integration Server log.
<b>DEP.0008.0018E</b>	<b>Skipping the delete checkpoint for {0} because the server is unavailable.</b>
<b>Explanation</b>	The target server is unavailable.
<b>Action</b>	Ensure that the target server is running.
<b>DEP.0008.0022E</b>	<b>Failed to delete checkpoint for target server {0}.</b>
<b>Explanation</b>	Deletion of checkpoint failed.
<b>Action</b>	Check Deployer and Integration Server logs.
<b>DEP.0008.0023E</b>	<b>Repository-based deployment does not support the checkpoint operation for the mapped target servers.</b>
<b>Explanation</b>	Repository-based projects do not support checkpoint operations for the mapped target servers
<b>Action</b>	Perform Deploy operation.
<b>DEP.0008.0024I</b>	<b>Deployer does not allow you to create checkpoints for transactional deployment.</b>
<b>Explanation</b>	You cannot create a checkpoint for projects that use transactional deployment. Deployer creates checkpoints automatically for transactional deployment.
<b>Action</b>	See the webMethods Deployer documentation for more information.
<b>DEP.0008.0025E</b>	<b>Repository-based deployment does not support checkpoint operation for target servers of type {0}.</b>
<b>Explanation</b>	Repository-based deployment does not support checkpoint operation for target servers of the given type.
<b>Action</b>	Remove the assets of the unsupported runtimes from the deployment and deletion sets and update the deployment map accordingly.

**DEP.0100.3.42E**      **The simulate, checkpoint, deploy, or rollback operation encountered an error while generating the report. Contact Software AG Global Support.**

**Explanation**      The simulate, checkpoint, deploy, or rollback operation encountered an error while generating the report.

**Action**              Contact Software AG Support.

**DEP.0100.5.37**      **Deployer cannot retrieve the project specified on the command. Make sure the user is authorized to view this information.**

**Explanation**      Deployer cannot retrieve the project specified on the command.

**Action**              Make sure the user is authorized to view this information.

**DEP.0100.5.38**      **Deployer cannot retrieve the build information specified on the command. Make sure the user is authorized to view this information.**

**Explanation**      Deployer cannot retrieve the build information specified on the command.

**Action**              Make sure the user is authorized to view this build information.

**DEP.0100.5.39**      **Deployer cannot retrieve the map specified on the command. Make sure the user is authorized to view this information.**

**Explanation**      Deployer cannot retrieve the map the user specified on the command.

**Action**              Make sure the user is authorized to view this information.

**DEP.0100.5.40**      **Deployer cannot retrieve the deployment candidates specified on the command. Make sure the user is authorized to view this information.**

**Explanation**      Deployer cannot retrieve the deployment candidates specified on the command.

**Action**              Make sure the user is authorized to view this information.

**DEP.0100.5.41**      **Deployer cannot retrieve the map for the user and project specified on the command. Make sure the user is authorized to view this information.**

**Explanation**      Deployer cannot retrieve the map for the user and project specified on the command.

**Action**              Make sure the user is authorized to view this information.

**DEP.0100.5.42**      **Deployer cannot retrieve the build information specified on the command. Make sure the user is authorized to view this information**

**Explanation**      Deployer cannot retrieve the build information specified on the command.

**Action**              Make sure the user is authorized to view this information.

**DEP.0100.5.43**      **There are no .map files in the IntegrationServer/packages/WmDeployer/replicate/inbound folder. Make sure the file you want to import exists in the specified folder.**

**Explanation**      There are no .map files in the IntegrationServer/packages/WmDeployer/replicate/inbound folder.

**Action**             Make sure the file you want to import exists in the specified folder.

**DEP.0100.5.63**      **The Integration Server to which you are trying to connect is configured to accept only secure connections on the UNIX platform. Use the correct digital certificates to establish the connection.**

**Explanation**      The Integration Server to which you are trying to connect is configured to accept only secure connections on the UNIX platform.

**Action**             Use the correct digital certificates to establish the connection.

**DEP.0100.5.64E**      **Deployer encountered an error while invoking the service. Make sure the Integration Server to which you are trying to connect is up and running and you have properly installed all required components.**

**Explanation**      This error is encountered when trying to invoke the service from CLI.

**Action**             Make sure the Integration Server to which you are trying to connect is up and running and you have properly installed all required components.

**InputValidationMessages.0001E – Parameter {0} cannot be null or empty**

**Explanation**      The specified parameter is either null or empty.

**Action**             Provide a valid value for the parameter.

**InputValidationMessages.0002E – Parameter {0} cannot be null.**

**Explanation**      The specified parameter is null.

**Action**             Provide a valid value for the parameter.

**InputValidationMessages.0003E – Parameter {0} cannot be a negative integer**

**Explanation**      The specified value is a negative integer.

**Action**             Provide a positive integer value for the parameter.

**InputValidationMessages.0004E – File {0} does not exist.**

**Explanation** The specified file does not exist in the specified location.  
**Action** Provide a valid file.

**InputValidationMessages.0005E – SSL-enabled connections require that either the TrustClientCertificatesByDefault parameter be set to true or that both TrustStoreFileName and TrustStorePassword are specified.**

**Explanation** Either the TrustClientCertificatesByDefault parameter is set to false or either the TrustStoreFileName, TrustStorePassword, or both are not specified.  
**Action** Set the TrustClientCertificatesByDefault parameter to true or provide valid values for both the TrustStoreFileName and TrustStorePassword parameters.

**OperationMessages.0002E – Failed to ping the target {0} of type {1} with following exception : {2}. Either the target is unavailable or the credentials provided are invalid.**

**Explanation** Either the target is unavailable or the credentials provided are invalid.  
**Action** Verify that the server is up and running, and that the specified parameters are valid.

**OperationMessages.0003E – An unexpected error occurred while pinging the target {0}. Error details : {1}**

**Explanation** An unexpected error occurred while pinging the target.  
**Action** Check the server logs for more details.

**OperationMessages.0011E – Deliver operation on the target server {0} of type {1} failed with following exception : {2}. Please check the target server's logs for details.**

**Explanation** The Deliver operation failed due to the reason specified in the Deliver report.  
**Action** Check the Deliver report for details. There might also be additional information in the Integration Server log.

**OperationMessages.0012E – An unexpected error occurred while performing variable substitutions for the asset with ACDL file name {0}. Error details : {1}**

**Explanation** An unexpected error occurred while substituting values.  
**Action** Check server logs for more details.

---

**OperationMessages.0021E – An unexpected error occurred while deleting the delivered assets for the deployment with ID {0} from target {1}. Error details : {2}**

**Explanation** An unexpected error occurred while deleting the delivered assets.

**Action** Check the server logs for more details.

**OperationMessages.0030E – An unexpected error occurred while activating the deployment with ID {0} for target {1}. Error details : {2}**

**Explanation** An unexpected error occurred while activating the delivered assets.

**Action** Check the server logs for more details.

**OperationMessages.0050E – Runtime type of the artifact {0} is different from the target runtime type {1}**

**Explanation** The runtime type of the specified artifact is different than the target runtime type.

**Action** Ensure that the runtime type of the asset to be deployed is same as the target server type.

**WDY-4460 The Package: "{0}" will not be activated. The dependent package "{1}" version "{2}" does not match the package version "{3}" present on the target server.**

**Explanation** The dependent package version does not match the package version present on the target server.

**Action** Ensure that the target server package version is the same as the dependent package version on the source server.



# 12 Designer Composite Application Framework

---

**restconnector.name** New REST UI

**restconnector.projectwizardpage.description** – Select a gadget from the listed projects

**restconnector.projectwizardpage.selectgadget** – Select a Gadget

**restconnector.projectwizardpage.swaggerurl** – Swagger URL

**restconnector.projectwizardpage.title** – Gadget Selection

**restconnector.restresourcespage.description** – Select the desired REST resources and their operations

**restconnector.restresourcespage.title** – REST Resources Selection

**restconnector.wizard.fieldpage.description** – Select the fields to be generated on UI and their configuration

**restconnector.wizard.fieldpage.displaylabel** – Display Label

**restconnector.wizard.fieldpage.formname – Form Name**

**restconnector.wizard.fieldpage.incolumncount – UI Layout column count for Input Parameters**

**Explanation**            The number of columns in which Business Console displays the input and output parameters in the generated form

**restconnector.wizard.fieldpage.inputparams – Input Parameters**

**restconnector.wizard.fieldpage.mandatory – Mandatory**

**restconnector.wizard.fieldpage.name – Name**

**restconnector.wizard.fieldpage.outcolumncount – UI Layout column count for Output Parameters**

**Explanation**            The number of columns in which Business Console displays the input and output parameters in the generated form

**restconnector.wizard.fieldpage.outputparams – Output Parameters**

**restconnector.wizard.fieldpage.pagenumber – PageNumber**

**restconnector.wizard.fieldpage.pagesize – PageSize**

**restconnector.wizard.fieldpage.title – Field Configuration**

**restconnector.wizard.fieldpage.totalrecords – TotalRecords**

**restconnector.wizard.fieldpage.type – Type**

**restconnector.wizard.fieldpage.uicontrol – UIControl**

**restconnector.wizard.fieldpage.validation – Validation**

**restconnector.wizard.title – New REST Connector Wizard**



# 13 Digital Event Services

---

<b>DEVABEE0000</b>	<b>The specified location "{0}" does not denote an existing directory.</b>
<b>Explanation</b>	A valid event type repository is needed.
<b>Action</b>	Check whether the specified location points to a DES event type repository.
<b>DEVABEE0002</b>	<b>Could not read content of file "{0}" in order to create zip archive "{1}"</b>
<b>Explanation</b>	The file content was not available while creating zip archive.
<b>Action</b>	See stacktrace for further explanations and actions.
<b>DEVABEE0003</b>	<b>Saving of acdl composite "{0}" failed.</b>
<b>Explanation</b>	See stacktrace for further information
<b>DEVABEE0004</b>	<b>Asset with path name "{0}" is duplicate in repository.</b>
<b>Explanation</b>	The path of an asset should always be unique.
<b>Action</b>	Check if the asset already exists and remove the wrong duplicate entry.
<b>DEVABEE0005</b>	<b>Not a valid repository "{0}".</b>
<b>Explanation</b>	The specified folder is not a valid repository folder.
<b>Action</b>	Specify a valid repository folder.

<b>DEVDECOE0040</b>	<b>Missing configuration location.</b>
<b>Explanation</b>	Required parameter for configuration location has not been set.
<b>Action</b>	Set an existing configuration location.
<b>DEVDECOE0041</b>	<b>Configuration location "{0}" does not exist.</b>
<b>Explanation</b>	The configuration location does not exist.
<b>Action</b>	Provide an existing configuration location.
<b>DEVDECOE0042</b>	<b>Configuration location "{0}" is not an absolute path.</b>
<b>Explanation</b>	Configuration location is not an absolute path.
<b>Action</b>	Provide an absolute path as configuration location.
<b>DEVDECOE0043</b>	<b>Configuration location "{0}" is not a directory.</b>
<b>Explanation</b>	The configuration location must be a directory.
<b>Action</b>	Provide a directory as configuration location.
<b>DEVDEEEE0000</b>	<b>Storing password for handle {0} failed</b>
<b>Explanation</b>	This is a failure of the Passman component.
<b>Action</b>	Contact your local support organization.
<b>DEVDEEEE0003</b>	<b>Failed to calculate passman config location: {0}</b>
<b>Explanation</b>	Malformed URL or invalid URI provided.
<b>Action</b>	Verify the correct URL / URI location.
<b>DEVDELIE0000</b>	<b>System property for license file path not specified</b>
<b>Explanation</b>	The system property that defines the location of the license file is not specified.
<b>Action</b>	Specify the system property.
<b>DEVDELIE0001</b>	<b>The specified license file path "{0}" does not exist</b>
<b>Explanation</b>	The specified license file path does not exist.
<b>Action</b>	Specify a valid license file.

---

<b>DEVDELIE0002</b>	<b>Invalid product code.</b>
<b>Explanation</b>	The product code is not valid.
<b>Action</b>	Provide a valid license.
<b>DEVDELIE0003</b>	<b>Invalid product version, expected major version "{0}", but found "{1}"</b>
<b>Explanation</b>	The major version in the license does not match the runtime version of the Digital Event Services product.
<b>Action</b>	Provide a valid license.
<b>DEVDELIE0004</b>	<b>Invalid OSGi installation directory</b>
<b>Explanation</b>	The specified value for the OSGi installation directory does not denote a valid directory.
<b>Action</b>	This is an internal error. Contact your support organization.
<b>DEVDELIE0005</b>	<b>The specified license file path "{0}" denotes a directory.</b>
<b>Explanation</b>	The location of the Digital Event Services license must point to the license file.
<b>Action</b>	Provide the proper license file location.
<b>DEVDERCE0030</b>	<b>Passed object of RunWatchdog is not valid</b>
<b>Explanation</b>	During instantiation of one of the RunWatchdog handlers, the RunWatchdog object itself is passed. However, this RunWatchdog object is not valid (null).
<b>Action</b>	Verify that the RunWatchdog object is valid before instantiating the handlers.
<b>DEVDERCE0042</b>	<b>A service group with the name "{0}" already exists.</b>
<b>Explanation</b>	Each service group must have a valid and unique name. The name must be unique in the namespace of all service groups. The service group name must follow the rule: <alpha character>+(<word character>   -   .)* where <word character> can be a digit, a lower or upper case character, and <alpha character> can be a lower or upper case character.
<b>Action</b>	Specify a unique service group name.
<b>DEVDERCE0045</b>	<b>The specified path "{0}" does not exist</b>
<b>Explanation</b>	The path must be a valid folder and it must exist on disk.
<b>Action</b>	Make sure the path location is an existing folder and create it if necessary.

<b>DEVDERCE0046</b>	<b>The specified path "{0}" is not a valid directory</b>
<b>Explanation</b>	The path is not an existing directory.
<b>Action</b>	Make sure that the specified directory exists.
<b>DEVDERCE0047</b>	<b>The specified path "{0}" is not an absolute path.</b>
<b>Explanation</b>	The path must be specified as an absolute path.
<b>Action</b>	Make sure that the path is specified as an absolute path.
<b>DEVDERCE0048</b>	<b>The service "{0}" is still used by the Service Group "{1}".</b>
<b>Explanation</b>	A service can only be deleted if it is not included in a service group.
<b>Action</b>	Remove all references to a service before deleting it.
<b>DEVDERCE0049</b>	<b>A service must not be renamed</b>
<b>Explanation</b>	A service name is used as a unique ID to reference the service.
<b>Action</b>	If a new name is required, delete the service and create a new one. Before deleting the service, make sure it is no longer referenced by any service group.
<b>DEVDERCE0050</b>	<b>The service name must not be empty</b>
<b>Explanation</b>	Each service must have a valid and unique name. A service name must follow the rule: <word character>+(<word character>   -   .)* where <word character> can be a digit, lower or upper case character.
<b>Action</b>	Specify a valid name for the service.
<b>DEVDERCE0051</b>	<b>Name "{0}" not unique considering the instance IDs. (Not allowed predefined ids: {1}).</b>
<b>Explanation</b>	Software AG Platform Manager allows only unique instance IDs to be used for the Event Routing runtime component.
<b>Action</b>	Change the name so that is is not identical to any other already existing service name, service group name, or the predefined {1}.
<b>DEVDERCE0052</b>	<b>A service with the name "{0}" already exists.</b>
<b>Explanation</b>	Each service must have a valid and unique name. A service name must follow the rule: <word character>+(<word character>   -   .)* where <word character> can be a digit, lower or upper case character.
<b>Action</b>	Specify a unique name for the service.

---

<b>DEVDERCE0053</b>	<b>Cannot use reserved service name "{0}"</b>
<b>Explanation</b>	This is the name of a predefined service.
<b>Action</b>	Choose a different service name.
<b>DEVDERCE0054</b>	<b>The service group name must not be empty</b>
<b>Explanation</b>	Each service group must have a valid and unique name. The name must be unique in the namespace of all service groups. The service group name must follow the rule: <alpha character>+(<word character>   -   . )* where <word character> can be a digit, a lower or upper case character, and <alpha character> can be a lower or upper case character.
<b>Action</b>	Specify a valid and unique name for the service group.
<b>DEVDERCE0057</b>	<b>The service group "{0}" contains duplicate service entries: "{1}"</b>
<b>Explanation</b>	Each service group must contain at least one service. The list of services within a service group must contain only unique services.
<b>Action</b>	Use only unique services within a service group.
<b>DEVDERCE0059</b>	<b>The referenced service "{0}" does not exist</b>
<b>Explanation</b>	The specified service does not exist and cannot be assigned to a service group.
<b>Action</b>	Choose a valid service in order to assign it to a service group.
<b>DEVDERCE0060</b>	<b>In the group "{0}" only one service can be marked as "source"</b>
<b>Explanation</b>	Only one service within a service group can be specified as "source".
<b>Action</b>	Mark only one service as "source".
<b>DEVDERCE0062</b>	<b>Service type name not found for service "{0}" in group "{1}"</b>
<b>Explanation</b>	A service with invalid service type has been specified within a certain service group.
<b>Action</b>	Use a service with a valid service type. Only valid services may be assigned to a service group.
<b>DEVDERCE0063</b>	<b>Service type not found for service "{0}" in group "{1}"</b>
<b>Explanation</b>	A service with invalid service type has been specified within a certain service group.
<b>Action</b>	Use a service with a valid service type. Only valid services may be assigned to a service group.

<b>DEVDERCE0064</b>	<b>The service "{0}" is marked as "source", however the corresponding service type "{1}" cannot act as source</b>
<b>Explanation</b>	The parameters of each service depend on its service type definition. If the service type is not configured to act as source, then the services of that type cannot be configured as "source" either.
<b>Action</b>	Remove the "source" marker from the service definition or change the configuration of the service type in order to allow the "source" marker.
<b>DEVDERCE0067</b>	<b>The "{0}" service has to be configured as source&amp;destination</b>
<b>Explanation</b>	This predefined service can only be used as "source and destination".
<b>Action</b>	Configure the service as "source and destination".
<b>DEVDERCE0068</b>	<b>A service group must not be renamed</b>
<b>Explanation</b>	A service group name is used as a unique ID to reference the service group.
<b>Action</b>	If a new name is required, delete the service group and create a new one. Before deleting the service group make sure that no event types are associated to it.
<b>DEVDERCE0069</b>	<b>The default service group must not be deleted</b>
<b>Explanation</b>	The default service group name is "Default". This group covers all event types which are not associated to other service groups, therefore the "Default" service group cannot be deleted.
<b>Action</b>	Do not delete the "Default" service group.
<b>DEVDERCE0070</b>	<b>The service group "{0}" is still referenced by an event type e.g. "{1}"</b>
<b>Explanation</b>	A service group can only be deleted if no event types are associated to it.
<b>Action</b>	Remove all event types associations to the service group before deleting it.
<b>DEVDERCE0078</b>	<b>Validation Error Message: {0}</b>
<b>DEVDERCE0079</b>	<b>Invalid name "{0}". It must follow the rule: &lt;alpha character&gt;+(&lt;word character&gt;   -   .)*</b>
<b>Explanation</b>	A name must follow the rule: <alpha character>+(<word character>   -   .)* where <word character> can be a digit, lower or upper case character.
<b>Action</b>	Do not use invalid URI characters.

<b>DEVDERCE0080</b>	<b>{0} must not be null or an empty string!</b>
<b>DEVDERCE0081</b>	<b>"{0}" is not a valid capacity value</b>
<b>Explanation</b>	The capacity must consist of digits only, optionally followed by one of [K, k, M, m, G, g]. The resulting value must not be larger than 9223372036854775807.
<b>Action</b>	Provide a valid capacity.
<b>DEVDERCE0082</b>	<b>Missing parameter "defaultCapacityValue" in order to return the valid capacity value.</b>
<b>DEVDERCE0083</b>	<b>Event Type not found in type repository: {0}</b>
<b>DEVDERCE0101</b>	<b>Cannot configure non-publishable event type: {0}</b>
<b>DEVDERCW0061</b>	<b>The predefined "{0}" service will be configured as source&amp;destination</b>
<b>Explanation</b>	This predefined service must always be configured as "source and destination".
<b>Action</b>	Configure this predefined service as "source and destination".
<b>DEVDERE0000</b>	<b>Failed to look-up {0} implementation of type "{1}".</b>
<b>Explanation</b>	No ServiceProvider implementation for the respective type name has been found. As a result, services of this type cannot be created. Most probably this indicates that the library containing the ServiceProvider implementation is not on the application's classpath.
<b>Action</b>	Make sure the library containing the ServiceProvider implementation for the respective type is on the application's classpath.
<b>DEVDERE0009</b>	<b>Caught and suppressed an exception thrown from notify() of observer {0}.</b>
<b>Explanation</b>	The observer of a subscription executed a notification which failed.
<b>DEVDERE0020</b>	<b>Failed to start a receiving route for event type {0} and subscriber ID {1}.</b>
<b>Explanation</b>	A subscriber cannot be created because of an unavailable source service, an invalid durable subscriber ID, or because the durable subscriber ID is already in use.
<b>Action</b>	Check if the service configured as a source is available. If you are creating a durable subscriber, make sure that its ID does not contain invalid characters, and that no durable subscriber with this ID for the same event type is currently active on the source service.

<b>DEVDERE0100</b>	<b>Cannot use non-publishable event type for pub-sub operations: {0}</b>
<b>Explanation</b>	Only event types marked as publishable can be used to emit events, or to set up a subscription.
<b>Action</b>	Choose a publishable event for sending/subscribing.
<b>DEVDERE0102</b>	<b>A nonpositive value of "{0}" has been specified for 'maxUnacknowledgedEvents' which is not allowed.</b>
<b>DEVDERE0107</b>	<b>Failed to read last data event key for subscriber "{0}" from file "{1}".</b>
<b>DEVDERUE0041</b>	<b>The event type name "{0}" could not be decomposed, probably the event sender did not use the correct protocol.</b>
<b>Explanation</b>	When receiving an event the accompanying type name has to follow a certain pattern , so that it can be decomposed into parts. This pattern changed between Digital Event Services 9.12 and 10.0, which means senders and receivers across these versions cannot talk to each other.
<b>Action</b>	Make sure all senders and receivers are either of version 9.12, or they are all of version 10.0 or greater.
<b>DEVDERUE0043</b>	<b>Failed to unsubscribe subscriber "{0}" for event type "{1}" from the Universal Messaging server, as the session is not connected. To avoid high number of events being stored for its named object, please delete the named object manually.</b>
<b>DEVDERUW0040</b>	<b>Timed out waiting to acquire the session lock in {0}. Probably the lock is held by a client event listener processing a received event or by a client subscriber observer processing a notification.</b>
<b>DEVDESCE0000</b>	<b>Internal error: the given "RuntimeComponent" parameter is not an instance of the "Instance" interface</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>DEVDESCE0001</b>	<b>It is not allowed to create new instances of Runtime Configuration</b>
<b>Explanation</b>	Only one built-in instance of Runtime Configuration exists.
<b>Action</b>	In order to apply your changes, edit the built-in instance of Runtime Configuration.

---

<b>DEVDESCE0002</b>	<b>It is not allowed to delete the instance of Runtime Configuration</b>
<b>Explanation</b>	There is only one built-in instance of Runtime Configuration, which must not be deleted.
<b>Action</b>	In order to apply changes, edit the built-in instance of Runtime Configuration.
<b>DEVDESCE0005</b>	<b>It is not possible to change storage location, while instance {0} is running</b>
<b>Explanation</b>	Please ensure that the component using Digital Event Services is restarted in order to start using the new storage location.
<b>Action</b>	Changing the storage location requires a restart of the components using Digital Event Services.
<b>DEVDESCE0007</b>	<b>"{0}" is not a valid number</b>
<b>Explanation</b>	The value to be configured needs to be a number.
<b>Action</b>	Provide a valid number.
<b>DEVDESCE0008</b>	<b>It is not allowed to create new instances of Event Types Configuration</b>
<b>Explanation</b>	Only one built-in instance of Event Types Configuration exists.
<b>Action</b>	In order to apply your changes, edit the built-in instance of Event Types Configuration.
<b>DEVDESCE0009</b>	<b>It is not allowed to delete the instance of Event Types Configuration</b>
<b>Explanation</b>	There is only one built-in instance of Event Types Configuration, which must not be deleted.
<b>Action</b>	In order to apply changes, edit the built-in instance of Event Types Configuration.
<b>DEVDESCE0010</b>	<b>Configured service group "{0}" does not exist</b>
<b>Explanation</b>	Event types can only be assigned to existing service groups.
<b>Action</b>	Create the service group before assigning an event type, or choose a different service group.
<b>DEVDESCE0011</b>	<b>Unknown reliability string "{0}" as configured value string e.g. on UI</b>
<b>Explanation</b>	The string of the reliability value is unknown to the system and cannot be assigned to an internal definition. This is an internal error and should never occur.
<b>Action</b>	Contact Software AG Global Support.

<b>DEVDESCE0012</b>	<b>Invalid EventTypeReliability value "{0}"</b>
<b>Explanation</b>	Invalid EventTypeReliability value used for conversion into string for output on UI e.g. This is an internal error and should not occur.
<b>Action</b>	Contact Software AG Global Support.
<b>DEVDESCE0013</b>	<b>Invalid EventType Delivery Mode Preference value "{0}"</b>
<b>Explanation</b>	Invalid EventType Delivery Mode Preference value used for conversion into string for output on UI e.g. This is an internal error and should not occur.
<b>Action</b>	Contact Software AG Global Support.
<b>DEVDESCI0006</b>	<b>The storage content is not automatically copied from {0} to the new destination {1}.</b>
<b>Explanation</b>	Before starting Digital Event Services the new storage location should be prepared by copying the necessary folder and files. Events may be lost if the storage is not available at runtime.
<b>Action</b>	Copy the storage from the old path into the new specified path before starting Digital Event Services.
<b>DEVDESCI0021</b>	<b>com.softwareag.event.routing.configuration bundle started.</b>
<b>Explanation</b>	The Digital Event Services (DES) configuration bundle for Command Central is started.
<b>Action</b>	(No action required)
<b>DEVDESCI0022</b>	<b>com.softwareag.event.routing.configuration bundle stopped.</b>
<b>Explanation</b>	The Digital Event Services (DES) configuration bundle for Command Central is stopped.
<b>Action</b>	(No action required)
<b>DEVDESCW0003</b>	<b>It is not possible to check whether product to be configured is online. The configuration modification will take effect only after the next restart of the product.</b>
<b>Explanation</b>	The status of Digital Event Services cannot be checked using SPM tools. Please ensure that the component using Digital Event Services is restarted to use the new storage location.
<b>Action</b>	Changing the storage location requires a restart of the product which is using Digital Event Services.

<b>DEVDESCW0004</b>	<b>Restart "{0}" to use the storage location "{1}"</b>
<b>Explanation</b>	The running instance must be restarted to use the new storage location. SPM must be active to change the storage location.
<b>Action</b>	Restart SPM, otherwise the old location will be used.
<b>DEVDTRE0000</b>	<b>Annotation type "{0}" contains duplicate field name "{1}"</b>
<b>Explanation</b>	Annotation type definitions must not contain duplicate field names.
<b>Action</b>	Correct the annotation type definition.
<b>DEVDTRE0001</b>	<b>System property "{0}" not set.</b>
<b>Explanation</b>	Digital Events Repositories location is defined by a system property.
<b>Action</b>	Define the system property.
<b>DEVDTRE0002</b>	<b>Repositories location "{0}" is not a directory.</b>
<b>Explanation</b>	The repositories location must be a directory.
<b>Action</b>	Define a directory as a repository location.
<b>DEVDTRE0003</b>	<b>Double field name "{0}" found.</b>
<b>Explanation</b>	Event type fields with the same name are not allowed within one event type definition. E.g. \nF1 : string;F1 : boolean; <-- duplicate field name - must be renamed or deleted.
<b>Action</b>	Rename or delete the corresponding field.
<b>DEVDTRE0007</b>	<b>Annotation type "{0}" not found in repository.</b>
<b>Explanation</b>	Each annotation specified inside the event type definition must be defined in the annotation type repository of the installation. Predefined annotation is e.g. "@Unique".
<b>Action</b>	Use only these annotations which are defined inside the annotation type repository of the installation.
<b>DEVDTRE0008</b>	<b>Field names of annotation type "{0}" must be specified explicitly.</b>
<b>Explanation</b>	If more than one annotation field is defined for a certain annotation type you have to specify <key>=<value> pairs in the annotation's parameter list. E.g. \n@multipfield_annotation(field1="value1", field2="value2")\n\nThe number of specified parameters is arbitrary: \n@multipfield_annotationOnly\n\nin case of one single defined annotation field you can specify only the "<value>" without the <key>= in front of it. E.g. \n@singlefield_annotation("value")
<b>Action</b>	Specify <key>=<value> pairs as annotation parameter list instead of just "<value>". E.g. \n@multipfield_annotation(field1="value1", field2="value2")

<b>DEV DRE0009</b>	<b>No field names defined for annotation type "{0}".</b>
<b>Explanation</b>	If there is no annotation field defined for a certain annotation type then it is not allowed to specify any <key>=<value> pair as parameter of the annotation.
<b>Action</b>	Remove the whole parameter list of the annotation. Only the annotation name may be specified e.g. "@Unique".
<b>DEV DRE0011</b>	<b>No annotation field "{0}" allowed because no fields defined for annotation type "{1}".</b>
<b>Explanation</b>	There is at least one annotation field specified in the annotation's parameter list. But because no field is defined it is not allowed to specify any annotation field.
<b>Action</b>	Remove the whole parameter list as no annotation field is defined for the annotation type e.g. "@Unique".
<b>DEV DRE0012</b>	<b>Annotation field "{0}" not defined for annotation type "{1}".</b>
<b>Explanation</b>	The specified annotation field is invalid because it is not defined for the corresponding annotation type.
<b>Action</b>	Specify the correct annotation field name in the annotation parameter list. E.g. correct the <key> inside of @annotation(<key>=<value>)
<b>DEV DRE0013</b>	<b>Value "{0}" cannot be converted into annotation field type "{1}".</b>
<b>Explanation</b>	A certain annotation field type is assigned to each annotation field. The value is specified as string but it must be convertible into the corresponding annotation field type. The annotation field types are defined for each annotation field definition of a certain annotation type. Valid types: \nSTRING: any string (corresponds to java "String" type) \nINT64: 64 bit integer value (corresponds to java "Long" type) \nFLOAT64: 64 bit floating point value (corresponds to java "Double" type) \nBOOLEAN: boolean value (corresponds to java "Boolean" type)
<b>Action</b>	Specify a correct value according to the correct annotation field type.
<b>DEV DRE0015</b>	<b>Event Type "{0}" is not unique.</b>
<b>Explanation</b>	Trying to access an event type as unique, that is not unique.
<b>Action</b>	Don't access a non unique event type with methods for unique types.
<b>DEV DRE0016</b>	<b>Event Type "{0}" is unique, but contains more than one entry in repository.</b>
<b>Explanation</b>	There is more than one file for an unique Event Type in the repository.
<b>Action</b>	The repository must be repaired to contain only one variant of the unique Event Type.

---

<b>DEVVDRE0017</b>	<b>Inconsistent file name: variant key "{0}" does not match filename "{1}"</b>
<b>Explanation</b>	The variant key, as computed based on the contents of the type definition file, does not match the type definition file name. Probably, the type definition file was manipulated directly with a text editor.
<b>Action</b>	Fix the type definition file.
<b>DEVVDRE0018</b>	<b>Inconsistent file name: event type name "{0}" does not match filename "{1}"</b>
<b>Explanation</b>	The event type name, as extracted from the contents of the type definition file, does not match the type definition file name. Probably, the type definition file was manipulated directly with a text editor.
<b>Action</b>	Fix the type definition file.
<b>DEVVDRE0019</b>	<b>Inconsistent file name: Annotation type name "{0}" does not match filename "{1}"</b>
<b>Explanation</b>	The annotation type name, as extracted from the contents of the type definition file, does not match the type definition file name. Probably, the type definition file was manipulated directly with a text editor.
<b>Action</b>	Fix the type definition file.
<b>DEVVDRE0022</b>	<b>Cannot change "unique" for {0} due to broken reference of an embedded type.</b>
<b>Explanation</b>	"unique" cannot be changed, if the event type is referenced by another event type.
<b>Action</b>	Insert a new variant for the referenced type, change or delete the referenced types.
<b>DEVVDRE0024</b>	<b>Event type info does not match for "{0}"</b>
<b>Explanation</b>	The event type info of the type being inserted does not match the existing event type info in the repository.
<b>Action</b>	Correct the event type info.
<b>DEVVDRE0036</b>	<b>Type name to be inserted ({0}) conflicts with existing type ({1})</b>
<b>Explanation</b>	The name of any type in the repository must not be the prefix of another type name. For example, "com.company" and "com.company.type" are not allowed.
<b>Action</b>	Supply a non-conflicting type name.

<b>DEVDRIO004</b>	<b>Referenced event type "{0}" is expected to be a {1} event type, but is not found in event type repository.</b>
<b>Explanation</b>	Event type fields may be of type 'event type reference'. The referenced type should be available in the repository of the installation. But if the referenced type is not available in the repository the reference is stored in the event type model internally just with the information of event type name and variant key name, if provided. \nUnique event type references must not have any variant key specified; non-unique event type references must have the variant key specified: E.g. \nF1 : event : unique_eventtype;F1 : event : nonunique_eventtype("<variant key>");
<b>Action</b>	Add the missing event type to the event type repository of the installation or remove/add the variant key depending on whether the event type is unique or non-unique.
<b>DEVDRW0010</b>	<b>Exception for input : {0} in file : {1}. Event type skipped.</b>
<b>Action</b>	(No action required)
<b>DEVDRW0014</b>	<b>EventTypeInfo skipped due to exception in file : {0}.</b>
<b>Action</b>	(No action required)
<b>DEVDTTE0000</b>	<b>Field name "{0}" has wrong format</b>
<b>Explanation</b>	The field name must follow this pattern: "[a-zA-Z][a-zA-Z0-9]*".
<b>Action</b>	Provide a valid field name.
<b>DEVDTTE0001</b>	<b>A field definition requires a name</b>
<b>Explanation</b>	Each field definition has to have a name.
<b>Action</b>	Provide a name for the field definition.
<b>DEVDTTE0002</b>	<b>A field definition requires a type</b>
<b>Explanation</b>	Each field definition has to have a type.
<b>Action</b>	Provide a type for the field definition.
<b>DEVDTTE0004</b>	<b>Invalid field annotation</b>
<b>Explanation</b>	For field definitions, only field-applicable annotations may be specified.
<b>Action</b>	Provide a valid field annotation.

---

<b>DEVDTTE0005</b>	<b>Type name "{0}" has wrong format</b>
<b>Explanation</b>	The event type name must follow this pattern: "[a-zA-Z_][a-zA-Z0-9_]*(\.[a-zA-Z_][a-zA-Z0-9_]*)".
<b>Action</b>	Provide a valid event type name.
<b>DEVDTTE0006</b>	<b>Invalid event annotation</b>
<b>Explanation</b>	For event types, only event-applicable annotations may be specified.
<b>Action</b>	Provide a valid event annotation.
<b>DEVDTTE0007</b>	<b>Field name "{0}" is not defined in annotation type "{1}".</b>
<b>Explanation</b>	The field name is not defined in the corresponding annotation type.
<b>Action</b>	Use a different field name or define the field name in annotation type.
<b>DEVDTTE0008</b>	<b>Field type for field "{0}" is "{1}" not matching "{2}".</b>
<b>Explanation</b>	The defined field type does not match the Java type used for an annotation value.
<b>Action</b>	Use a matching Java type.
<b>DEVDTTE0009</b>	<b>Field type for field "{0}" is "{1}" is not matching any allowed field value.</b>
<b>Explanation</b>	AnnotationTypeDefinition only allows certain field types.
<b>Action</b>	Use a type which is allowed.
<b>DEVDTTE0010</b>	<b>Duplicate annotation "{0}"</b>
<b>Explanation</b>	The same annotation can be applied multiple times only if the corresponding annotation type is marked as repeatable.
<b>Action</b>	Provide a valid annotation.
<b>DEVDTTE0011</b>	<b>Java object not supported for any: "{0}"</b>
<b>Explanation</b>	Only Java objects that are supported by any must be set as values for any. These value can only be scalars or EventTypes. An arrays must be defined as arrays.
<b>DEVDTTE0012</b>	<b>Missing annotation type name.</b>
<b>Explanation</b>	No annotation type name was provided for the building of an annotation type.
<b>Action</b>	Set a name for the annotation type on the annotation type builder.

<b>DEVDTE0013</b>	<b>Recursive reference to "{0}" not allowed</b>
<b>Explanation</b>	Digital Event Types do not allow recursive type references, neither directly, nor indirectly.
<b>Action</b>	Provide a valid type reference.
<b>DEVDTE0014</b>	<b>An array must not contain another array.</b>
<b>Explanation</b>	It is not possible to define an array of arrays.
<b>Action</b>	An array is specified by explicitly defining the dimension.
<b>DEVDTE0017</b>	<b>The array dimension has to be a positive integer.</b>
<b>Explanation</b>	Array dimensions have to be positive integers. For example, specify dimension = 2 in order to construct a string[[]].
<b>Action</b>	Provide a valid dimension.
<b>DEVDTE0019</b>	<b>Field "{0}" is not defined for type "{1}".</b>
<b>Explanation</b>	The type for the event does not contain the field. The type does not contain the field.
<b>Action</b>	Set or get a field that is defined for the type of the event.
<b>DEVDTE0020</b>	<b>Field "{0}" in event type "{1}" has field type "{2}" in event type variant "{3}", and field type "{4}" in event type variant "{5}".</b>
<b>Explanation</b>	The field types for a field are not matching.
<b>Action</b>	Consider using another event type variant for accessing the event.
<b>DEVDTE0021</b>	<b>The reserved package name "{0}" must not be used</b>
<b>Explanation</b>	The Digital Event Services system uses the reserved package name for internal purposes.
<b>Action</b>	Provide a valid package name.
<b>DEVDTE0022</b>	<b>Transmission event type "{0}" and subscribing event type "{1}" must be the same.</b>
<b>Explanation</b>	The event type used for transmission is different from the one that has been subscribed for.
<b>Action</b>	Contact Software AG support.

<b>DEVDTTE0024</b>	<b>The path for the "{0}" annotation "{1}" does not match any field definition.</b>
<b>Explanation</b>	The paths for the annotations like "EventTime" and "EventId" must point to an existing field.
<b>Action</b>	Correct the path value of the annotation.
<b>DEVDTTE0025</b>	<b>The field corresponding to event time path "{0}" is not a time field.</b>
<b>Explanation</b>	The event time path must point to an existing time field.
<b>Action</b>	Correct the path value of the EventTime annotation.
<b>DEVDTTE0028</b>	<b>Field "{0}" of event type "{1}" contains an unresolved reference to event type "{2}".</b>
<b>Explanation</b>	This should not happen because only valid event type models are stored to the repository. However, the referenced type is no longer available in the repository in the case that it has been deleted from it.
<b>Action</b>	Correct the invalid event type or add the referenced event type to the repository.
<b>DEVDTTE0030</b>	<b>The unique event type "{0}" has different variants.</b>
<b>Explanation</b>	A unique event type should only exist in one variant.
<b>Action</b>	Use only one variant of a unique event type.
<b>DEVDTTE0031</b>	<b>Variants of Event Type "{0}" differ in "unique" setting.</b>
<b>Explanation</b>	If an event type is "unique", there cannot exist another variant of the same event type which is not "unique".
<b>Action</b>	Define an event type as "unique" or use it with variants.
<b>DEVDTTE0032</b>	<b>The type name "{0}" does not have a package</b>
<b>Explanation</b>	Each event type name needs to be qualified with a package.
<b>Action</b>	Provide a valid type name.
<b>DEVDTTE0033</b>	<b>The event type "{0}" and the nested event type "{1}" should have the same uniqueness setting</b>
<b>Explanation</b>	If an event type is marked as "unique", it can only refer to other "unique" event types. Vice versa, a "non-unique" event type can only refer to other "non-unique" event types.
<b>Action</b>	Correct the uniqueness setting.

<b>DEVDTTE0035</b>	<b>Cannot access the field "{0}" of unknown type "{1}" in event type "{2}"</b>
<b>Explanation</b>	The data type of the field is not known to the current runtime, therefore the field value cannot be accessed.
<b>Action</b>	Specify a field with a known data type.
<b>DEVDTTE0049</b>	<b>No variant key allowed for unique referenced event type "{0}".</b>
<b>Explanation</b>	In case of a uniquely defined event type, variant keys must not be specified in an event type reference: Invalid field definition: "F1 : event : package.unique_eventtype("<variant key>");" Correct field definition: "F1 : event : package.unique_eventtype;" (* Uniquely defined event types contain a @Unique annotation on event level.) (* The variant key is a hexadecimal 16-digit value, which is automatically added to the file name in the repository.)
<b>Action</b>	Remove the variant key and just specify the fully qualified event type name: F1 : event : package.unique_eventtype;
<b>DEVDTTE0050</b>	<b>Variant key necessary for non-unique referenced event type "{0}".</b>
<b>Explanation</b>	In case of a non-uniquely defined event type, a variant key must be specified in an event type reference. Invalid field definition: "F1 : event : package.nonunique_eventtype;" Correct field definition: "F1 : event : package.nonunique_eventtype("<variant key>");" (* Non-uniquely defined event types don't contain a @Unique annotation on event level.) (* The <variant key> is a hexadecimal 16-digit value, which is automatically added to the file name in the repository.)
<b>Action</b>	Add the variant key behind the fully qualified event type name: F1 : event : package.nonunique_eventtype("<variant key>");"
<b>DEVDTTE0051</b>	<b>Unknown type found: {0}</b>
<b>Explanation</b>	The any field contains an unknown type or type id, that cannot be read. Maybe the event has been created in a later product version.
<b>DEVDTTE0052</b>	<b>Event type "{0}" cannot be resolved.</b>
<b>Explanation</b>	The event type cannot be resolved.
<b>DEVDTI0015</b>	<b>Annotation field name "{0}" has wrong format.</b>
<b>Explanation</b>	The annotation field name must follow this pattern: "[a-zA-Z][a-zA-Z0-9_]*".
<b>Action</b>	Provide a valid annotation field name.

<b>DEVDTI0016</b>	<b>Annotation type name "{0}" has wrong format.</b>
<b>Explanation</b>	The annotation type name must follow this pattern: "[a-zA-Z_][a-zA-Z0-9_]*(\.[a-zA-Z_][a-zA-Z0-9_]*)".
<b>Action</b>	Provide a valid annotation type name.

---

# 14 Event-Driven Architecture Tools Messages

---

<b>EDAERBCE0000</b>	<b>The service group name must not be empty</b>
<b>Explanation</b>	Each service group must have a valid and unique name. The name must be unique in the namespace of all service groups. The service group name must follow the rule: <alpha character>+(<word character>   -   . )* where <word character> can be a digit, a lower or upper case character, and <alpha character> can be a lower or upper case character.
<b>Action</b>	Specify a valid and unique name for the service group.
<b>EDAERBCE0001</b>	<b>A service group with the name "{0}" already exists.</b>
<b>Explanation</b>	Each service group must have a valid and unique name. The name must be unique in the namespace of all service groups. The service group name must follow the rule: <alpha character>+(<word character>   -   . )* where <word character> can be a digit, a lower or upper case character, and <alpha character> can be a lower or upper case character.
<b>Action</b>	Specify a unique service group name.
<b>EDAERBCE0002</b>	<b>Invalid service group name "{0}". It must follow the rule: &lt;alpha character&gt;+(&lt;word character&gt;   -   . )*</b>
<b>Explanation</b>	Each service group must have a valid and unique name. The name must be unique in the namespace of all service groups. The service group name must follow the rule: <alpha character>+(<word character>   -   . )* where <word character> can be a digit, a lower or upper case character, and <alpha character> can be a lower or upper case character.
<b>Action</b>	Specify a valid service group name which follows the rule of service group names.

- EDAERBCE0003**     **Invalid service group name "{0}" because it is different from the created unique instance name "{1}" which is used for the configuration persistence.**
- Explanation**     Each service group must have a valid and unique name. The name must be unique in the namespace of all service groups. The service group name must follow the rule: <word character>+(<word character> | - | . | \_)\* where <word character> can be a digit, a lower or upper case character.
- Action**     Specify a valid service group name where service group name must be the same as the unique instance name.
- 
- EDAERBCE0004**     **The default service group must not be deleted**
- Explanation**     The default service group name is "Default". This group covers all event types which are not associated to other service groups, therefore the "Default" service group cannot be deleted.
- Action**     Do not delete the "Default" service group.
- 
- EDAERBCE0006**     **The default service group must not be renamed**
- Explanation**     The default service group name is "Default". This group covers all event types which are not associated to other service groups, therefore the "Default" service group cannot be renamed.
- Action**     Do not rename the "Default" service group.
- 
- EDAERBCE0007**     **The service group "{0}" is still referenced by an event type e.g. "{1}"**
- Explanation**     A service group can only be deleted if no event types are associated to it.
- Action**     Remove all event types associations to the service group before deleting it.
- 
- EDAERBCE0008**     **The service group "{0}" contains duplicate service entries: "{1}"**
- Explanation**     Each service group must contain at least one service. The list of services within a service group must contain only unique services.
- Action**     Use only unique services within a service group.
- 
- EDAERBCE0009**     **The service group "{0}" must contain at least one service**
- Explanation**     Each service group must contain at least one service. The list of services within a service group must contain only unique services.
- Action**     Assign at least one service to the service group.

---

<b>EDAERBCE0010</b>	<b>The referenced service "{0}" does not exist</b>
<b>Explanation</b>	The specified service does not exist and cannot be assigned to a service group.
<b>Action</b>	Choose a valid service in order to assign it to a service group.
<b>EDAERBCE0011</b>	<b>In the group "{0}" only one service can be marked as "source"</b>
<b>Explanation</b>	Only one service within a service group can be specified as "source".
<b>Action</b>	Mark only one service as "source".
<b>EDAERBCE0012</b>	<b>Service type name not found for service "{0}" in group "{1}"</b>
<b>Explanation</b>	A service with invalid service type has been specified within a certain service group.
<b>Action</b>	Use a service with a valid service type. Only valid services may be assigned to a service group.
<b>EDAERBCE0013</b>	<b>Service type not found for service "{0}" in group "{1}"</b>
<b>Explanation</b>	A service with invalid service type has been specified within a certain service group.
<b>Action</b>	Use a service with a valid service type. Only valid services may be assigned to a service group.
<b>EDAERBCE0014</b>	<b>The service "{0}" is marked as "source", however the corresponding service type "{1}" cannot act as source</b>
<b>Explanation</b>	The parameters of each service depend on its service type definition. If the service type is not configured to act as source, then the services of that type cannot be configured as "source" either.
<b>Action</b>	Remove the "source" marker from the service definition or change the configuration of the service type in order to allow the "source" marker.
<b>EDAERBCE0015</b>	<b>The service "{0}" is marked as "reliable", however the corresponding service type "{1}" does not support reliable</b>
<b>Explanation</b>	The parameters of each service depend on its service type definition. If the service type is not configured to support reliable delivery, then the services of that type cannot be configured as "reliable" either.
<b>Action</b>	Remove the "reliable" marker from the service definition or change the configuration of the service type in order to allow the "reliable" marker.

<b>EDAERBCE0017</b>	<b>The service name must not be empty</b>
<b>Explanation</b>	Each service must have a valid and unique name. A service name must follow the rule: <word character>+(<word character>   -   . )* where <word character> can be a digit, lower or upper character.
<b>Action</b>	Specify a valid name for the service.
<b>EDAERBCE0018</b>	<b>A service with the name "{0}" already exists.</b>
<b>Explanation</b>	Each service must have a valid and unique name. A service name must follow the rule: <word character>+(<word character>   -   . )* where <word character> can be a digit, lower or upper character.
<b>Action</b>	Specify a unique name for the service.
<b>EDAERBCE0019</b>	<b>The service "{0}" is still used by the Service Group "{1}".</b>
<b>Explanation</b>	A service can only be deleted if it is not included in a service group.
<b>Action</b>	Remove all references to the service before deleting it.
<b>EDAERBCE0020</b>	<b>Invalid name "{0}". It must follow the rule: &lt;alpha character&gt;+(&lt;word character&gt;   -   . )*</b>
<b>Explanation</b>	A name must follow the rule: <alpha character>+(<word character>   -   . )* where <word character> can be a digit, lower or upper character.
<b>Action</b>	Do not use invalid URI characters.
<b>EDAERBCE0021</b>	<b>Name "{0}" not unique considering the instance IDs. (Not allowed predefined ids: {1}).</b>
<b>Explanation</b>	Software AG Platform Manager allows only unique instance IDs to be used for the Event Routing runtime component.
<b>Action</b>	Change the name so that is is not identical to any other already existing service names, service group names, or the predefined {1}.
<b>EDAERBCE0024</b>	<b>Event type "{0}" does not exist</b>
<b>Explanation</b>	The specified event type is not present in the Event Type Store, and therefore cannot be used in the Service Group Event Types configuration.
<b>Action</b>	Remove the event type from the Service Group Event Types.

---

<b>EDAERBCE0025</b>	<b>Duplicate event type "{0}"</b>
<b>Explanation</b>	The specified event type appears twice in the Service Group Event Types configuration.
<b>Action</b>	Remove the duplicate event type from the Service Group Event Types configuration.
<b>EDAERBCE0026</b>	<b>The service group "{0}" does not exist</b>
<b>Explanation</b>	The specified service group does not exist.
<b>Action</b>	Remove the service group from the Service Group Event Types configuration, or create the service group before updating the Service Group Event Types configuration.
<b>EDAERBCE0028</b>	<b>A service group must not be renamed</b>
<b>Explanation</b>	A service group name is used as a unique id to reference the service group.
<b>Action</b>	If a new name is required, delete the service group and create a new one. Before deleting the service group make sure that no event types are associated to it.
<b>EDAERBCE0029</b>	<b>A service must not be renamed</b>
<b>Explanation</b>	A service name is used as a unique id to reference the service.
<b>Action</b>	If a new name is required, delete the service and create a new one. Before deleting the service make sure it is no longer referenced by any service group.
<b>EDAERBCE0030</b>	<b>"{0}" is not a valid capacity value</b>
<b>Explanation</b>	The capacity must consist of digits only, optionally followed by one of [K, k, M, m, G, g]. The resulting value must not be larger than 9223372036854775807.
<b>Action</b>	Provide a valid capacity.
<b>EDAERBCE0032</b>	<b>The "{0}" service has to be configured as source&amp;destination</b>
<b>Explanation</b>	This predefined service can only be used as "source and destination".
<b>Action</b>	Configure the service as "source and destination".
<b>EDAERBCE0033</b>	<b>Cannot use reserved service name "{0}"</b>
<b>Explanation</b>	This is the name of a predefined service.
<b>Action</b>	Choose a different service name.

<b>EDAERBCE0038</b>	<b>It is not possible to change storage location, while instance {0} is running</b>
<b>Explanation</b>	Please ensure that the component using Event Routing is restarted in order to start using the new storage location.
<b>Action</b>	Changing the storage location requires a restart of the components using Event Routing.
<b>EDAERBCE0040</b>	<b>The specified path "{0}" is not a valid directory</b>
<b>Explanation</b>	The path is not an existing directory.
<b>Action</b>	Make sure that the specified directory exists.
<b>EDAERBCE0041</b>	<b>The specified path "{0}" is not an absolute path.</b>
<b>Explanation</b>	The path must be specified as an absolute path.
<b>Action</b>	Make sure that the path is specified as an absolute path.
<b>EDAERBCE0042</b>	<b>The specified path "{0}" does not exist</b>
<b>Explanation</b>	The path must be a valid folder and it must exist on disk.
<b>Action</b>	Make sure the path location is an existing folder and create it if necessary.
<b>EDAERCE0005</b>	<b>It is not allowed to create new instances of Runtime Configuration</b>
<b>Explanation</b>	Only one built-in instance of Runtime Configuration exists.
<b>Action</b>	In order to apply your changes, edit the built-in instance of Runtime Configuration.
<b>EDAERCE0021</b>	<b>Invalid name "{0}". It must follow the rule: &lt;alpha character&gt;+(&lt;word character&gt;   -   .)*</b>
<b>Explanation</b>	Each service must have a valid and unique name. A service name must follow the rule: <alpha character>+(<word character>   -   .)* where <word character> can be a digit, lower or upper character, and <alpha character> can be a lower or upper case character. The service name is the same as the corresponding instance ID, which is used to identify a service in the configuration persistence. This instance ID must be unique for all instances of Event Routing.
<b>Action</b>	Use a valid service name following the naming rules.

---

<b>EDAERCE0022</b>	<b>It is not allowed to create new instances of Service Group Event Types</b>
<b>Explanation</b>	Only one built-in instance of Service Group Event Types exists.
<b>Action</b>	In order to apply changes, edit the built-in instance of Service Group Event Types.
<b>EDAERCE0023</b>	<b>It is not allowed to delete the instance of Service Group Event Types</b>
<b>Explanation</b>	Only one built-in instance of Service Group Event Types exists, and it cannot be deleted.
<b>Action</b>	In order to apply changes, edit the built-in instance of Service Group Event Types.
<b>EDAERCE0027</b>	<b>Internal error: the given "RuntimeComponent" parameter is not an instance of the "Instance" interface</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Contact your support organization.
<b>EDAERCE0031</b>	<b>It is not allowed to delete the instance of Runtime Configuration</b>
<b>Explanation</b>	There is only one built-in instance of Runtime Configuration, which must not be deleted.
<b>Action</b>	In order to apply changes, edit the built-in instance of Runtime Configuration.
<b>EDAERCE0041</b>	<b>Exception from getRuntimeStatus.</b>
<b>EDAERCE0048</b>	<b>Registration failed for service type: {0}.</b>
<b>EDAERCI0043</b>	<b>ui binding for {0} setup.</b>
<b>EDAERCI0045</b>	<b>com.softwareag.event.routing.configuration bundle stopped.</b>
<b>EDAERCPE0028</b>	<b>Passed object of RunWatchdog is not valid</b>
<b>Explanation</b>	During instantiation of one of the RunWatchdog handlers, the RunWatchdog object itself is passed. However, this RunWatchdog object is not valid (null).
<b>Action</b>	Verify that the RunWatchdog object is valid before instantiating the handlers.

<b>EDAERCPE0029</b>	<b>Default configuration not found</b>
<b>Explanation</b>	If no event routing configuration is available, all default configuration files are copied to the place where the configuration is expected. However, the zip file containing all these files could not be found. This file is created by calling the "eclipse" task of the project.
<b>Action</b>	Execute the "eclipse" task of the gradle build script beforehand.
<b>EDAERCPE0030</b>	<b>File {0} is empty! Service {1} is not created and no events can be handled by {1}</b>
<b>Explanation</b>	The file has no content. A service cannot be created and no events can be sent or received.
<b>Action</b>	Provide a file containing the desired entry or use a graphical configuration such as Software AG Command Central user interface for creating a correct service.
<b>EDAERCPE0031</b>	<b>{0} contains invalid content {1}</b>
<b>Explanation</b>	The content is not correct.
<b>Action</b>	Correct the content or use a graphical configuration tool such as Software AG Command Central.
<b>EDAERCW0042</b>	<b>Service group {0}: IP service set to source&amp;destination.</b>
<b>EDAERE0002</b>	<b>Failed to start a subscriber route consuming from URI "{0}".</b>
<b>Explanation</b>	A subscriber cannot be created because of an unavailable source service or an invalid or an already used durable subscriber ID.
<b>Action</b>	Check if the service configured as a source is available. If you are creating a durable subscriber, make sure that its ID does not contain invalid characters, and that no durable subscriber with this ID for the same event type is currently active on the source service.
<b>EDAERE0003</b>	<b>Failed to start a subscriber route consuming from URI "{0}": a durable subscriber with ID "{1}" already exists on the IP service.</b>
<b>Explanation</b>	An IP service durable subscriber cannot be created because of an already used durable subscriber ID.
<b>Action</b>	Make sure that no durable subscriber with this ID for the same event type is currently active on the source IP service.

---

<b>EDAERE0058</b>	<b>Failed to delete the service implementation bundle for service name: "{0}".</b>
<b>Explanation</b>	Undeploying the service from the bundles folder of the configuration failed. Even if the service could not be deleted, this should not prevent the system from running normally.
<b>Action</b>	Delete the service jar file manually if desired.
<b>EDAESE0000</b>	<b>Failed to create an event parser.</b>
<b>Explanation</b>	The factory was not able to create an event parser.
<b>Action</b>	Check the log for exception stacktrace.
<b>EDAESIE0004</b>	<b>The selected Integration Server Document Type is recursive and its conversion results in a recursive Event Type which is not supported.</b>
<b>Explanation</b>	The Integration Server Document type which has been selected is recursive. After the conversion a recursive Event Type is produced. Recursive Event Types are not supported.
<b>Action</b>	Remove recursion from the Integration Server Document type prior to creating an event type from it.
<b>EDAESIE0006</b>	<b>Restrictions not supported for {0}</b>
<b>Explanation</b>	Union and List are not supported for restrictions.
<b>Action</b>	Please contact your software supplier.
<b>EDAESIE0007</b>	<b>Unsupported facet {0} with value {1}</b>
<b>Explanation</b>	The called restriction facet is not supported.
<b>Action</b>	Please contact your software supplier.
<b>EDAESIE0029</b>	<b>Event Types without a target namespace are not allowed outside the root "Event Types" directory.</b>
<b>Explanation</b>	An event type which does not define target namespace exists outside the root of the event types directory.
<b>Action</b>	Either move this event type in the "Event Types" directory or manually create a target namespace definition for it.

<b>EDAESIE0034</b>	<b>Node {0} is not filterable because node {1} is not of cardinality 0..1 or 1..1.</b>
<b>Explanation</b>	The node is not filterable, since the node path can have several values (and not only a unique one).
<b>Action</b>	Set the node to not filterable, or set the cardinality of all nodes on the node path to cardinality 1..1.
<b>EDAESIE0035</b>	<b>Node {0} is not filterable because nodes {1} are not of cardinality 0..1 or 1..1.</b>
<b>Explanation</b>	The node is not filterable, since the node path can have several values (and not only a unique one).
<b>Action</b>	Set the node to not filterable, or set the cardinality of all nodes on the node path to cardinality 1..1.
<b>EDAETE0211</b>	<b>Event Types without a target namespace are not allowed outside the root "Event Types" directory.</b>
<b>Explanation</b>	An event type which does not define target namespace exists outside the root of the event types directory.
<b>Action</b>	Either move this event type in the "Event Types" directory or manually create a target namespace definition for it.
<b>EDAETE0213</b>	<b>Cannot build editor tree.</b>
<b>Explanation</b>	A unexpected error occurred while building the editor tree.
<b>Action</b>	Make sure the event type schema is correctly defined.
<b>EDAETE0214</b>	<b>Cannot provide children in node tree.</b>
<b>Explanation</b>	Unexpected error while getting the child nodes in a node tree.
<b>Action</b>	Make sure the event type schema is correctly defined.
<b>EDAISE0012</b>	<b>The selected IS Document Type is recursive and its conversion results in a recursive Event Type which is not supported.</b>
<b>Explanation</b>	The IS Document type which has been selected is recursive. After the conversion a recursive Event Type is produced. Recursive Event Types are not supported.
<b>Action</b>	Remove recursion from the IS Document type prior to creating an event type from it.

---

<b>EDANCE0000</b>	<b>Failed to parse date string "{0}" within {1}</b>
<b>Explanation</b>	Failed to parse date string.
<b>Action</b>	Check the format of the supplied data.
<b>EDANCE0001</b>	<b>Failed to parse date string "{0}" within {1}</b>
<b>Explanation</b>	Failed to not parse date string.
<b>Action</b>	Check the format of the supplied data.
<b>EDANCE0003</b>	<b>Specified value "{0}" for property "{1}" is not of type integer.</b>
<b>Explanation</b>	Required property is not of required type.
<b>Action</b>	Check the format of the supplied data.
<b>EDANCE0004</b>	<b>Specified value "{0}" for property "{1}" is not of type long.</b>
<b>Explanation</b>	Specified value for a property is not of type long.
<b>Action</b>	Check whether the specified property is of the required type.
<b>EDANCE0005</b>	<b>Specified value "{0}" for property "{1}" is not of the supported types: "{2}", "{3}", "{4}", "{5}", "{6}", "{7}".</b>
<b>Explanation</b>	The specified guaranteed delivery level in your NERV configuration file is not of the supported ones.
<b>Action</b>	Go to the NERV configuration file and specify one of the valid values: NORMAL, HIGH, MAXIMUM_STRONG, MAXIMUM_EVENTUAL, SHARED for the com.softwareag.eda.nerv.guaranteed.delivery.level property.
<b>EDANCE0007</b>	<b>Failed to create JNDI entry for topic "{0}".</b>
<b>Explanation</b>	Failed to create JNDI entry.
<b>Action</b>	Check your JMS provider configuration.
<b>EDANCE0008</b>	<b>No {0} instance available - no attempts will be made for creating JNDI entry for topic "{1}".</b>
<b>Explanation</b>	Failed to create JNDI entry.
<b>Action</b>	Check your JMS provider configuration.

<b>EDANCE0009</b>	<b>Failed to create topic with name "{0}" on the JMS provider.</b>
<b>Explanation</b>	Failed to create topic on the JMS Provider.
<b>Action</b>	Check your JMS provider configuration.
<b>EDANCE0010</b>	<b>No {0} instance available - no attempts will be made for creating topic with name "{1}" on the JMS provider.</b>
<b>Explanation</b>	Failed to create topic on the JMS provider.
<b>Action</b>	Check your JMS provider configuration.
<b>EDANCE0012</b>	<b>{0} instance is not configured properly.</b>
<b>Explanation</b>	The JNDI settings of your NERV component configuration are not correct.
<b>Action</b>	Check the JNDI settings of your NERV component configuration.
<b>EDANCE0013</b>	<b>Failed to create topic with name "{0}" on Broker running at "{1}".</b>
<b>Explanation</b>	During emit and subscribe operations NERV creates the respective topics on the JMS provider if they are missing.
<b>Action</b>	Check your JMS provider and NERV configuration.
<b>EDANCE0014</b>	<b>Failed to bind topic "{0}" at "{1}".</b>
<b>Explanation</b>	Failed to bind topic.
<b>Action</b>	Check your JMS provider configuration.
<b>EDANCE0015</b>	<b>Failed to create topic "{0}" on Universal Messaging Realm server at "{1}".</b>
<b>Explanation</b>	Failed to create topic.
<b>Action</b>	Check your JMS provider configuration.
<b>EDANCE0016</b>	<b>Failed to process the specified JMS provider url: "{0}". The expected format is "{1}{broker.name}@{broker.host}:{broker.port}".</b>
<b>Explanation</b>	Failed to process the JMS provider URL.
<b>Action</b>	Check your NERV configuration.

<b>EDANCE0017</b>	<b>No connection factory found. Either the "{0}" instance is not available or the creation of the factory has failed.</b>
<b>Explanation</b>	No connection factory has been found. This might be due to the unavailability of the NERV destination support service or the failure of the factory creation. This service is available only for webMethods Broker and Universal Messaging components.
<b>Action</b>	Check your NERV configuration and make sure Universal Messaging or Broker are configured and running.
<b>EDANCE0028</b>	<b>Failed to create connection factory for Broker with name "{0}" and address "{1}".</b>
<b>Explanation</b>	During initialization NERV tries to create and bind a connection factory for the specified JMS provider if such does not exist.
<b>Action</b>	Please make sure the specified provider URL denotes a running webMethods Broker instance.
<b>EDANCE0029</b>	<b>Failed to create topic with name "{0}" on Broker running at "{1}".</b>
<b>Explanation</b>	During emit and subscribe operations NERV creates the respective topics on the JMS provider if they are missing.
<b>Action</b>	Check your JMS provider and NERV configuration.
<b>EDANCE0032</b>	<b>The JmsSupport utility supports Universal Messaging and Broker, but the specified JMS provider "{0}" is of a different type.</b>
<b>Explanation</b>	The JmsSupport utility does not support the specified JMS provider.
<b>Action</b>	Please specify a provider URL denoting a JMS provider of type Universal Messaging or Broker.
<b>EDANCW0002</b>	<b>Not a date: {0} {1}</b>
<b>Explanation</b>	The passed argument is not a date.
<b>Action</b>	Check whether the passed argument is of the required type.
<b>EDANCW0011</b>	<b>Unsupported JMS provider. No attempts will be made for configuring the JMS provider.</b>
<b>Explanation</b>	Unsupported JMS provider.
<b>Action</b>	Check documentation for the list of supported JMS providers.

<b>EDANCW0026</b>	<b>JMS provider URL is set to "{0}" and the hostname denotes a loopback address. Remote clients will not be able to establish a connection to the JMS server.</b>
<b>Explanation</b>	This property is used for creating a connection factory that clients can look up remotely.
<b>Action</b>	To use NERV to connect remotely to a JMS provider, you must change the value of the JMS provider URL property to the actual hostname of the JMS server.
<b>EDANIE0002</b>	<b>Failed to propagate NERV properties change to NERV errorhandler because the JMX helper is not initialized.</b>
<b>Explanation</b>	Failed to propagate NERV properties change to NERV errorhandler because the JMX helper is not initialized.
<b>Action</b>	Check that NERV is properly initialized.
<b>EDANIE0005</b>	<b>Failed to handle notification.</b>
<b>Explanation</b>	Failed to handle route changed notification or unrecognized notification type.
<b>Action</b>	Check that NERV is properly initialized.
<b>EDANIE0006</b>	<b>NERV could not close JMS connection factory successfully.</b>
<b>Explanation</b>	NERV could not close JMS connection factory successfully.
<b>Action</b>	Close JMS connection factory.
<b>EDANIE0011</b>	<b>Failed to register service "{0}"</b>
<b>Explanation</b>	Failed to register Destination Support Service
<b>Action</b>	Make sure that NERV is properly configured.
<b>EDANIE0013</b>	<b>Failed to propagate NERV properties change to NERV component updater because it is not available.</b>
<b>Explanation</b>	Failed to propagate NERV properties change to NERV component updater because it is not available.
<b>Action</b>	Check the log files for errors during Component Updater initialization.
<b>EDANIE0014</b>	<b>Failed to propagate NERV properties change to NERV errorhandler updater because it is not available.</b>
<b>Explanation</b>	Failed to propagate NERV properties change to NERV errorhandler updater because it is not available.
<b>Action</b>	Check the log files for errors during Error Handler initialization.

---

<b>EDANIE0015</b>	<b>Failed to restart file watcher for NERV deployment directory.</b>
<b>Explanation</b>	Failed to restart file watcher for NERV deployment directory.
<b>Action</b>	Check that NERV is properly configured.
<b>EDANIE0018</b>	<b>Failed to update NERV component "{0}" in "{1}".</b>
<b>Explanation</b>	Failed to update NERV Default JMS component Event Consumer Service.
<b>Action</b>	Make sure that NERV is properly configured.
<b>EDANIE0019</b>	<b>Failed to update NERV component "{0}" in "{1}".</b>
<b>Explanation</b>	Failed to update NERV Default JMS component Event Emitter Service.
<b>Action</b>	Make sure that NERV is properly configured.
<b>EDANIE0021</b>	<b>Failed to configure NERV Default Component "{0}" via properties because the property "{1}" is missing or has an empty value.</b>
<b>Explanation</b>	Failed to configure NERV Default Component via properties because com.softwareag.eda.nerv.default.jms.provider property is missing or has an empty value.
<b>Action</b>	Make sure that NERV is properly configured.
<b>EDANIE0022</b>	<b>Unsubscribe failed for endpoint: &lt;&lt;{0}&gt;&gt;. No such subscription found.</b>
<b>Explanation</b>	Unsubscribe failed for endpoint. No such subscription found.
<b>Action</b>	Check endpointURI.
<b>EDANIE0023</b>	<b>Failed to find any NERV errohandler MBeans.</b>
<b>Explanation</b>	Failed to find any NERV errohandler Services.
<b>Action</b>	Check that NERV error handling is properly configured.
<b>EDANIE0024</b>	<b>Failed to configure NERV errorhandlers.</b>
<b>Explanation</b>	Failed to configure NERV errorhandlers.
<b>Action</b>	Check that NERV error handling is properly configured.

<b>EDANIE0025</b>	<b>Failed to obtain pub/sub "toEndpoint" for: {0}</b>
<b>Explanation</b>	Failed to obtain pub/sub "toEndpoint" for specified url.
<b>Action</b>	Check that NERV Components are properly configured.
<b>EDANIE0026</b>	<b>Failed to set tracing for object name "{0}" to: {1}</b>
<b>Explanation</b>	Failed to set tracing for object name to value.
<b>Action</b>	Check that NERV Components are properly configured.
<b>EDANIE0027</b>	<b>Failed to find existing in-memory endpoint object name for: {0}</b>
<b>Explanation</b>	Failed to find existing in-memory endpoint object name for the specified url.
<b>Action</b>	Check that NERV Components are properly configured.
<b>EDANIE0028</b>	<b>Failed to resolve component: "{0}". NERVSingleton.loadAssets() method has to be invoked prior to obtaining EventEmitter or EventConsumer references.</b>
<b>Explanation</b>	Failed to resolve specified component. NERVSingleton.loadAssets() method has to be invoked prior to obtaining EventEmitter or EventConsumer references.
<b>Action</b>	Make sure NERVSingleton.loadAssets() has been invoked before obtaining Consumer/Emitter references.
<b>EDANIE0029</b>	<b>Failed to resolve component: "{0}". There is no such bean loaded by NERV.</b>
<b>Explanation</b>	Failed to resolve the specified component. No such bean is loaded by NERV.
<b>Action</b>	Check NERV configuration.
<b>EDANIE0030</b>	<b>Failed to resolve component: "{0}". The bean exists, but it is not a NERV component.</b>
<b>Explanation</b>	Failed to resolve specified component. The bean exists, but it is not a NERV component.
<b>Action</b>	Check that the bean is a NERV component.
<b>EDANIE0031</b>	<b>The event type is not specified in the headers of event: {0}</b>
<b>Explanation</b>	The event type is not specified in the event headers.
<b>Action</b>	Message headers map should contain an "\$Event\$Type" entry.

---

<b>EDANIE0032</b>	<b>No Event Type Store has been set.</b>
<b>Explanation</b>	No Event Type Store has been set.
<b>Action</b>	Check that the Event Type Store location is configured properly.
<b>EDANIE0033</b>	<b>The event type is not specified in the message headers.</b>
<b>Explanation</b>	The event type is not specified in the event headers.
<b>Action</b>	Message headers map should contain an "\$Event\$Type" entry.
<b>EDANIE0034</b>	<b>No OSGi bundle context is set.</b>
<b>Explanation</b>	No OSGi bundle context is set. The bundle has not been initialized correctly.
<b>Action</b>	Restart bundle/OSGi/Product instance.
<b>EDANIE0035</b>	<b>Failed to resolve component with id "{0}". The JMS provider might be down.</b>
<b>Explanation</b>	Failed to resolve specified component. Possible cause: the JMS provider is unreachable due to incorrectly set address in the NERV component configuration properties file or due to the JMS provider being down.
<b>Action</b>	Check NERV Component configuration. Check if the JMS provider is running and reachable.
<b>EDANIE0036</b>	<b>Failed to resolve component with id "{0}".</b>
<b>Explanation</b>	Failed to resolve the specified component.
<b>Action</b>	Check NERV Component configuration.
<b>EDANIE0037</b>	<b>Failed to create NERV default component "{0}": unknown JMS provider "{1}".</b>
<b>Explanation</b>	Failed to create NERV default component: NERVDefaultJms unknown JMS provider.
<b>Action</b>	Check the value of the com.softwareag.eda.nerv.default.jms.provider property in the NERV configuration file.
<b>EDANIE0038</b>	<b>No OSGi bundle context is set.</b>
<b>Explanation</b>	No OSGi bundle context is set. The bundle has not been initialized correctly.
<b>Action</b>	Restart bundle/OSGi/Product instance.

<b>EDANIE0039</b>	<b>Failed to get NERV default component status.</b>
<b>Explanation</b>	Failed to get NERV default component status.
<b>Action</b>	Check that NERV is properly configured.
<b>EDANIE0040</b>	<b>Failed to subscribe to an empty endpoint URI: &lt;&lt;{0}&gt;&gt;</b>
<b>Explanation</b>	Failed to subscribe to an empty endpoint URI.
<b>Action</b>	Check that endpointURI is not null or empty.
<b>EDANIE0041</b>	<b>Failed to subscribe to endpoint URI: &lt;&lt;{0}&gt;&gt;</b>
<b>Explanation</b>	Failed to subscribe to the specified endpoint URI.
<b>Action</b>	Check that the endpointURI is valid.
<b>EDANIE0042</b>	<b>Processor must not be null.</b>
<b>Explanation</b>	When making a subscription, the provided Processor must not be null.
<b>Action</b>	Make sure the processor is not null.
<b>EDANIE0043</b>	<b>End-Points must be more than zero.</b>
<b>Explanation</b>	When making a subscription, the list of the End-Points must contain at least one entry.
<b>Action</b>	Check endpointURIs.
<b>EDANIE0044</b>	<b>Processor must not be null.</b>
<b>Explanation</b>	When unsubscribing, the provided Processor must not be null.
<b>Action</b>	Make sure the processor is not null.
<b>EDANIE0045</b>	<b>No route with id:&lt;&lt;{0}&gt;&gt; found while trying to stop!</b>
<b>Explanation</b>	No route with the specified id is found while trying to stop!
<b>Action</b>	Make sure the route ID is correct.
<b>EDANIE0046</b>	<b>Event Type must be specified in the message headers.</b>
<b>Explanation</b>	The event type is not specified in the event headers.
<b>Action</b>	Message headers map should contain a valid "\$Event\$Type" entry.

---

<b>EDANIE0047</b>	<b>Message should not be null.</b>
<b>Explanation</b>	Message should not be null or empty.
<b>Action</b>	Make sure the message is not null or empty.
<b>EDANIE0048</b>	<b>Message should not be null and at least one endpoint should be specified.</b>
<b>Explanation</b>	Message should not be null and at least one endpoint should be specified.
<b>Action</b>	Check that the message is not null or empty and that the endpointURIs is not null or empty.
<b>EDANIE0049</b>	<b>&lt;&lt;{0}&gt;&gt; is mandatory header.</b>
<b>Explanation</b>	The "\$Event\$EventID" entry is not specified in the headers of the event.
<b>Action</b>	Message headers map should contain an "\$Event\$EventID" entry.
<b>EDANIE0050</b>	<b>Failed to set {0} header.</b>
<b>Explanation</b>	Failed to set "\$Event\$Start" header.
<b>Action</b>	Expect events with a missing start header.
<b>EDANIE0051</b>	<b>Error while emitting event to endpoint: {0}</b>
<b>Explanation</b>	Error while emitting event to endpoint.
<b>Action</b>	Check the log file for more details.
<b>EDANIE0052</b>	<b>Error while emitting event to endpoint: {0}</b>
<b>Explanation</b>	Error while emitting event to endpoint.
<b>Action</b>	Check the log file for more details.
<b>EDANIE0053</b>	<b>Error while emitting event to endpoint: {0}</b>
<b>Explanation</b>	Error while emitting event to endpoint.
<b>Action</b>	Check the log file for more details.
<b>EDANIE0054</b>	<b>Failed to create route from: {0} to: {1}.</b>
<b>Explanation</b>	Failed to create default routing.
<b>Action</b>	Check the log file for more details.

**EDANIE0055**      **NERV Default Error Handler "{0}" has not been set. Please make sure a valid instance of type "{0}" is provided during Event Emitter instantiation.**

**Explanation**      No ErrorHandlerBuilder instance has been provided during Event Emitter instantiation.

**Action**              Check that a service/bean of type ErrorHandlerBuilder is exposed/registered by NERV.

**EDANIE0056**      **Failed to remove default route for endpoint: {0}**

**Explanation**      Failed to remove default route for endpoint.

**Action**              Check the log file for more details.

**EDANIE0057**      **Component Resolver has not been set. Please make sure a valid instance of type "{0}" is provided during Event Emitter instantiation.**

**Explanation**      No Component Resolver instance has been provided during Event Emitter instantiation.

**Action**              Check that a service/bean of type ComponentResolver is exposed/registered by NERV.

**EDANIE0058**      **EDAEventTypeID must not be null.**

**Explanation**      EDAEventTypeID must not be null.

**Action**              When making a subscription, check that eventTypeID is not null.

**EDANIE0059**      **No route with id:<<{0}>> found while trying to stop.**

**Explanation**      No route with specified id found while trying to stop.

**Action**              Check the log file for more details.

**EDANIE0060**      **Message should not be null.**

**Explanation**      Message should not be null.

**Action**              Check that the message is not null.

**EDANIE0061**      **Message should not be null.**

**Explanation**      Message should not be null.

**Action**              Check that the message is not null.

---

<b>EDANIE0062</b>	<b>Event type is missing from the provided event envelope. It should be specified under the /Event/Header/Type element of the XML string. The following tag should exist &lt;Type&gt;...&lt;/Type&gt;. Provided event envelope: {0} {1}</b>
<b>Explanation</b>	Event type is missing from the provided event envelope. It should be specified under the /Event/Header/Type element of the XML string. The following tag should exist <Type>...</Type>.
<b>Action</b>	Check that the eventContent matches the specified pattern.
<b>EDANIE0063</b>	<b>Could not find body element in the following string: {0}</b>
<b>Explanation</b>	Could not find body element in the specified string.
<b>Action</b>	Check that eventAsXMLString matches the specified pattern.
<b>EDANIE0064</b>	<b>Event type is either missing or has incorrect format. Provided event type: {0}</b>
<b>Explanation</b>	Event type is either missing or has incorrect format.
<b>Action</b>	Check that eventType is not null or empty or invalid.
<b>EDANIE0065</b>	<b>Event helper is null. It must be set prior to using it.</b>
<b>Explanation</b>	Event helper is null. It must be set prior to using it.
<b>Action</b>	Message Creator service is not configured properly. Check the NERV configuration.
<b>EDANIE0066</b>	<b>Event type store has not been set. Please make sure a valid reference to the Event Type Store is provided during Message Creator instantiation.</b>
<b>Explanation</b>	Event type store has not been set. Please make sure a valid reference to the Event Type Store is provided during Message Creator instantiation.
<b>Action</b>	Check that the Event Type Store location is configured properly.
<b>EDANIE0067</b>	<b>Failed to marshal event.</b>
<b>Explanation</b>	Failed to marshal event.
<b>Action</b>	Check the log file for more details.
<b>EDANIE0068</b>	<b>Event type is either missing or has incorrect format. It should be specified in the message headers map using key {0}.</b>
<b>Explanation</b>	Event type is either missing or has an incorrect format.
<b>Action</b>	Message headers map should contain an "\$Event\$Type" entry.

<b>EDANIE0069</b>	<b>Event should not be null or empty.</b>
<b>Explanation</b>	Event should not be null or empty.
<b>Action</b>	Check that eventAsXMLString is not null or empty.
<b>EDANIE0070</b>	<b>Failed to extract headers and filterable properties from event: {0} {1}</b>
<b>Explanation</b>	Failed to extract headers and filterable properties from the spefied event.
<b>Action</b>	Check the log file for more details.
<b>EDANIE0071</b>	<b>Event headers cannot be null and should not be empty.</b>
<b>Explanation</b>	Invalid headers.
<b>Action</b>	Check that the headers are not null or empty.
<b>EDANIE0072</b>	<b>Event headers cannot be null and should not be empty.</b>
<b>Explanation</b>	Invalid headers.
<b>Action</b>	Check that the headers are not null or empty.
<b>EDANIE0073</b>	<b>Event body should not be null. This is allowed only if the event is of kind heartbeat.</b>
<b>Explanation</b>	Invalid body.
<b>Action</b>	Check that the body is not null or empty.
<b>EDANIE0077</b>	<b>Failed to resolve XSD parser.</b>
<b>Explanation</b>	An error has occurred while trying to provide an XSD parser instance.
<b>Action</b>	Please review the exception stacktrace for detailed explanation of the failure.
<b>EDANIE0078</b>	<b>Failed to resolve XSD parser due to missing Event Type Store bean with name "{0}".</b>
<b>Explanation</b>	The default Event Type Store bean has not been found.
<b>Action</b>	Please make sure that you have specified a correct Event Type Store location in the NERV configuration file.
<b>EDANIE0083</b>	<b>Error while emitting event to endpoint: {0}</b>
<b>Explanation</b>	Error while emitting event to endpoint.
<b>Action</b>	Check the log file for more details.

---

<b>EDANIE0088</b>	<b>Guaranteed delivery level is set to "{0}", but the configuration directory specified via property "{1}" at "{2}" does not contain a configuration file with name "{3}".</b>
<b>Explanation</b>	No configuration XML file with name equal to the selected guaranteed level is found at the specified configuration directory.
<b>Action</b>	Make sure that a file with name equal to the specified guaranteed mode exists in the configuration directory.
<b>EDANIE0090</b>	<b>Event Emitter has not been set. Please make sure a valid instance of type "0" is provided during Event Consumer instantiation.</b>
<b>Explanation</b>	No Event Emitter instance has been provided during Event Consumer instantiation.
<b>Action</b>	Check that a service/bean of type Event Emitter is exposed/registered by NERV.
<b>EDANIE0091</b>	<b>Failed to flush NERV caches.</b>
<b>Explanation</b>	During initialization NERV flushes all cached events.
<b>Action</b>	Check the exception stacktrace in the log file for more details. Restarting NERV would trigger another flush attempt.
<b>EDANIE0094</b>	<b>Failed to retrieve bindings of type "{0}" from JNDI context at "{1}".</b>
<b>Explanation</b>	Look-up of bindings from the JNDI context at the specified server failed.
<b>Action</b>	Make sure that the messaging provider denoted by the provider URL property is up and running. Check the log file for any preceding error logs that might be related to this issue.
<b>EDANIE0095</b>	<b>Failed to retrieve deployed destinations at "{0}" using connection factory "{1}".</b>
<b>Explanation</b>	A connection created with this connection factory could not be initialized.
<b>Action</b>	Check the log file for any preceding error logs that might be related to this issue.
<b>EDANIE0096</b>	<b>The event emitting failed. EventEmitter.emit() was called from the init() or start() method of a custom route bundle loaded by NERV.</b>
<b>Explanation</b>	EventEmitter.emit() was called from the init() or start() method of a custom route bundle loaded by NERV.
<b>Action</b>	If a custom route bundle needs to emit an event from its init() or start() method, it has to do it in a separate thread in order to avoid a deadlock.

**EDANIE0097**      **Failed to propagate NERV properties change to NERV text encryptor because it is not available.**

**Explanation**      Failed to propagate NERV properties change to NERV text encryptor because it is not available.

**Action**            Check the log files for errors during text encryptor initialization.

**EDANIW0000**      **{0} does not denote an existing directory.**

**Explanation**      Specified directory does not exist.

**Action**            Make sure that "com.softwareag.eda.nerv.dead.letter.channel.uri" property denotes a directory.

**EDANIW0001**      **Failed to initialize NERV JMX helper.**

**Explanation**      Failed to initialize NERV JMX helper.

**Action**            Check log file for more details.

**EDANIW0003**      **Failed to configure NERV Default Error Handler "{0}" with the specified configuration properties.**

**Explanation**      Failed to configure NERV Default Error Handler with the specified configuration properties.

**Action**            Check that NERV error handling is properly configured.

**EDANIW0004**      **Failed to add event headers to message body.**

**Explanation**      Failed to add event headers to message body.

**Action**            Check log file for more details.

**EDANIW0007**      **Failed to process NERV Default Component "{0}" change.**

**Explanation**      Failed to process NERV Default Component change.

**Action**            Check log file for more details.

**EDANIW0008**      **Failed to configure NERV Default Component "{0}" with specified configuration properties: {1}**

**Explanation**      Failed to configure NERV Default Component with the specified configuration properties.

**Action**            Check NERV configuration.

---

<b>EDANIW0009</b>	<b>Failed to configure NERV Default Component "{0}" with specified configuration properties: {1}</b>
<b>Explanation</b>	Failed to configure NERV Default Component with the specified configuration properties.
<b>Action</b>	Check NERV configuration.
<b>EDANIW0010</b>	<b>Failed to update NERV Default Component "{0}".</b>
<b>Explanation</b>	Failed to update NERV Default Component.
<b>Action</b>	Check NERV configuration and log file for more details.
<b>EDANIW0012</b>	<b>Failed to register service "{0}" because NERV component "{1}" does not configure a webMethods Broker or Universal Messaging connection.</b>
<b>Explanation</b>	Failed to register Destination Support service because the specified NERV component does not configure a webMethods Broker or Universal Messaging connection.
<b>Action</b>	If you are configuring a Broker or Universal Messaging connection, double check that the configuration is correct. Otherwise ignore this message.
<b>EDANIW0016</b>	<b>Failed to process a bundle lifecycle change because no bundle component updater has been set.</b>
<b>Explanation</b>	NERVService Listener has not been properly initialized. Failed to process a bundle lifecycle change because no bundle component updater has been set.
<b>Action</b>	Restart bundle/OSGi/Product instance.
<b>EDANIW0017</b>	<b>NERV component "{0}" is not properly configured. Shutting down all routes consuming from component "{1}". In order to restart the routes, please provide a valid configuration and restart your consume bundles or restart the whole OSGi instance.</b>
<b>Explanation</b>	NERV component is not properly configured.
<b>Action</b>	Shutting down all routes consuming from specified component. In order to restart the routes, please provide a valid configuration and restart your consume bundles or restart the whole OSGi instance.
<b>EDANIW0020</b>	<b>Failed to load NERV assets from "{0}". Reason: {1}</b>
<b>Explanation</b>	Failed to load NERV assets from NERV asset folder.
<b>Action</b>	Check nervAssetFolder and log file more details.

<b>EDANIW0098</b>	<b>Failed to configure NERV text encryptor "{0}" with the specified configuration properties.</b>
<b>Explanation</b>	Failed to configure NERV text encryptor with the specified configuration properties.
<b>Action</b>	Check that the NERV security file location is properly configured.
<b>EDANRBE0000</b>	<b>The XML generation failed.</b>
<b>Explanation</b>	Failed to write the route bundle to an output stream.
<b>Action</b>	Check the error log for exception details.
<b>EDANRBE0001</b>	<b>The replaceable value could not be encrypted.</b>
<b>Explanation</b>	The replaceable value could not be encrypted.
<b>Action</b>	Check if the NervTextEncryptor instance passed to the NervRouteBundle object has been correctly initialized.
<b>EDANRBE0002</b>	<b>NervTextEncryptor is not set.</b>
<b>Explanation</b>	NervTextEncryptor is not set.
<b>Action</b>	Before writing the bundle, invoke NervRouteBundle.setTextEncryptor() and pass a properly initialized NervTextEncryptor.
<b>EDANRBE0004</b>	<b>Unsupported Event Persistence endpoint type was specified: "{0}".</b>
<b>Explanation</b>	The supported Event Persistence types are hdfs and jdbc.
<b>Action</b>	Please specify either hdfs or jdbc as a type.
<b>EDANRBE0005</b>	<b>The mandatory configuration property "{0}" for Event Persistence endpoint of type "{1}" is not set.</b>
<b>Explanation</b>	A mandatory Event Persistence endpoint configuration property has not been set.
<b>Action</b>	Set all mandatory configuration properties to the Event Persistence endpoint before adding it to a route.
<b>EDANRBE0006</b>	<b>Cannot perform any operations on a route which has not been properly initialized with a from() invocation.</b>
<b>Explanation</b>	The to() or camel() method invocation is not allowed on a route which has not been initialized with from() invocation first.
<b>Action</b>	Prior to calling the to() or camel() methods on a NervRoute, invoke the from() method first.

---

<b>EDANRBE0007</b>	<b>Empty parameter found in user package import entry {0}.</b>
<b>Explanation</b>	The specified user package import entry contains an empty argument or directive - for example: package;;version=["1.0,2.0).
<b>Action</b>	Make sure the user package import entry does not contain any empty arguments or directives before adding it to the bundle manifest.
<b>EDANRBE0008</b>	<b>User package import entry "{0}" does not contain any packages.</b>
<b>Explanation</b>	A user-added package import entry must contain at least one import and can have optional arguments and directives.
<b>Action</b>	Make sure the user import package entry you want to add to the bundle manifest contains one or more semicolon-separated packages.
<b>EDANRBE0009</b>	<b>The NERV route bundle factory could not be created.</b>
<b>Explanation</b>	The NERV route bundle factory could not be created.
<b>Action</b>	Please check the log.
<b>EDANRBE0010</b>	<b>The XML generation failed.</b>
<b>Explanation</b>	Failed to write the route bundle to a directory.
<b>Action</b>	Check the error log for exception details.
<b>EDANRBE0011</b>	<b>The output path is not a directory.</b>
<b>Explanation</b>	The specified path does not denote a directory where the bundle can be persisted.
<b>Action</b>	Please specify a valid directory path.
<b>EDANRBE0012</b>	<b>The contents of the output directory cannot be deleted.</b>
<b>Explanation</b>	Failed to delete the files found in the output directory.
<b>Action</b>	Please make sure that any access permissions for the file systems are properly configured.
<b>EDANRBE0013</b>	<b>The output directory cannot be created.</b>
<b>Explanation</b>	Failed to create a directory in which to persist the route bundle.
<b>Action</b>	Please make sure that access permissions for the file systems are properly configured.

**EDANRBE0014**      **The following directory cannot be created: "{0}".**  
**Explanation**      Failed to create a directory while persisting the route bundle.  
**Action**              Please make sure that access permissions for the file system are properly configured.

# 15

## Event Persistence Messages

---

**EVSECM172E0000 Invalid Event Persistence Elasticsearch URI format: {0}**

**Explanation** The Elasticsearch URI was specified using an invalid or unexpected format.

**EVSECM172E0001 Error creating Elasticsearch transport client for URI: {0}**

**Explanation** There was an error creating the Elasticsearch client and connecting to the cluster using the specified URI.

**EVSECM172E0002 Error creating Elasticsearch transport client for cluster name {0} and host(s) {1}**

**Explanation** There was an error creating the Elasticsearch client and connecting to the cluster using the specified URI.

**EVSECM232E0000 Invalid Event Persistence Elasticsearch URI format: {0}**

**Explanation** The Elasticsearch URI was specified using an invalid or unexpected format.

**EVSECM232E0001 Error creating Elasticsearch transport client for URI: {0}**

**Explanation** There was an error creating the Elasticsearch client and connecting to the cluster using the specified URI.

**EVSECM232E0002 Error creating Elasticsearch transport client for cluster name {0} and host(s) {1}**

**Explanation** There was an error creating the Elasticsearch client and connecting to the cluster using the specified URI.

<b>EVSECME0000</b>	<b>Error creating Elasticsearch transport client for URI: {0}</b>
<b>EVSECME0001</b>	<b>Error creating Elasticsearch transport client for cluster name {0} and host(s) {1}</b>
<b>EVSECME0002</b>	<b>Invalid Event Persistence Elasticsearch URI format: {0}</b>
<b>EVSEDSE0000</b>	<b>Cannot get EDA event type schema parser.</b>
<b>Explanation</b>	Cannot get EDA event type schema parser.
<b>EVSEDSE0001</b>	<b>Cannot get event type store at location: {0}</b>
<b>Explanation</b>	Cannot get event type store at the given location.
<b>Action</b>	Please make sure that the event type store location is valid.
<b>EVSEDSE0002</b>	<b>Non-default ETS locations are not currently supported in OSGi {0}</b>
<b>EVSEDSE0003</b>	<b>Timeout waiting for blueprint injection of EDA interface provider</b>
<b>Explanation</b>	The timeout expired when waiting for EDA ETS/XSD services
<b>EVSEQI172E0000</b>	<b>Unsupported syntax found in aggregate function clause: {0}</b>
<b>Explanation</b>	The syntax of the aggregate expression is incorrect. This error should never occur because the grammar has already been validated. It's included for proper error handling.
<b>EVSEQI172E0001</b>	<b>Unsupported encoding exception encountered when formatting result</b>
<b>Explanation</b>	The default utf-8 encoding was not supported in this environment. The result body could not be added to the result set.
<b>EVSEQI172E0002</b>	<b>An error has occurred because the response reference has not been set in response handler</b>
<b>Explanation</b>	This is a programming class usage issue. This error shouldn't be experienced once the implementation is tested and verified.

---

<b>EVSEQI172E0003</b>	<b>Unexpected statement type found when trying to determine query builder implementation</b>
<b>Explanation</b>	The query builder examines the statement to determine if its an instance or aggregate query. In this case the implementation couldn't identify the statement type.
<b>EVSEQI172E0004</b>	<b>Error executing full text query due to invalid query filter</b>
<b>Explanation</b>	The query filter could not be transformed and used in the Elasticsearch query.
<b>EVSEQI172E0005</b>	<b>An unsupported encoding exception was thrown while generating query hit.</b>
<b>Explanation</b>	The default encoding of utf-8 was not available and the query hit document could not be processed.
<b>EVSEQI172E0006</b>	<b>An unsupported encoding exception was thrown while generating explain message</b>
<b>Explanation</b>	The default encoding of utf-8 was not available to format the explain plan message
<b>EVSEQI172E0007</b>	<b>Error creating full text query for explain plan due to invalid query filter.</b>
<b>Explanation</b>	The explain plan content could not be generated due to a parsing error in the filter syntax
<b>EVSEQI172E0010</b>	<b>Error transforming query to native Elasticsearch request!%n{0}</b>
<b>Explanation</b>	The query as specified in the Common Query Syntax could not be transformed into a native Elasticsearch query.
<b>EVSEQI172E0011</b>	<b>Error executing native Elasticsearch search request!%n{0}</b>
<b>Explanation</b>	An error occurred during execution of the Elastisearch query.
<b>EVSEQI172E0012</b>	<b>Error transforming query to native Elastisearch request for explain plan</b>
<b>Explanation</b>	The query as expressed in the Common Query Syntax could not be transformed into an Elasticsearch request when creating the explain plan.
<b>EVSEQI172E0013</b>	<b>An unsupported encoding exception was thrown while generating explain message</b>
<b>Explanation</b>	The default encoding of utf-8 is not availble and caused an exception when generating the explain plan text.

- EVSEQI172E0014**    **Query session has been created with invalid context for this implementation**  
**Explanation**        The context must include all of the required parameters for this query implementation.
- EVSEQI172E0015**    **Error creating a transport client connection to Elasticsearch cluster**  
**Explanation**        A connection to the Elasticsearch cluster could not be established.
- EVSEQI172E0016**    **Failed to position cursor at next event in the result stream**  
**Explanation**        An exception was thrown when trying to move the cursor to the next position in the result stream.
- EVSEQI172E0017**    **The method {0} is unsupported in this implementation of ResultStream**  
**Explanation**        The ResultStream interface only requires that all implementations provide a next operation.
- EVSEQI172E0018**    **Error getting result at current cursor position from handler**  
**Explanation**        An exception was thrown when attempting to get the event data from the current position in the result stream.
- EVSEQI172I0008**    **Inbound query in common syntax form:**
- EVSEQI172I0009**    **Outbound query in native form:**
- EVSEQI232E0000**    **Unsupported syntax found in aggregate function clause: {0}**  
**Explanation**        The syntax of the aggregate expression is incorrect. This error should never occur because the grammar has already been validated. It's included for proper error handling.
- EVSEQI232E0001**    **Unsupported encoding exception encountered when formatting result**  
**Explanation**        The default utf-8 encoding was not supported in this environment. The result body could not be added to the result set.

---

<b>EVSEQI232E0002</b>	<b>An error has occurred because the response reference has not been set in response handler</b>
<b>Explanation</b>	This is a programming class usage issue. This error shouldn't be experienced once the implementation is tested and verified.
<b>EVSEQI232E0003</b>	<b>Unexpected statement type found when trying to determine query builder implementation</b>
<b>Explanation</b>	The query builder examines the statement to determine if its an instance or aggregate query. In this case the implementation couldn't identify the statement type.
<b>EVSEQI232E0004</b>	<b>Error executing full text query due to invalid query filter</b>
<b>Explanation</b>	The query filter could not be transformed and used in the Elasticsearch query.
<b>EVSEQI232E0005</b>	<b>An unsupported encoding exception was thrown while generating query hit.</b>
<b>Explanation</b>	The default encoding of utf-8 was not available and the query hit document could not be processed.
<b>EVSEQI232E0006</b>	<b>An unsupported encoding exception was thrown while generating explain message</b>
<b>Explanation</b>	The default encoding of utf-8 was not available to format the explain plan message
<b>EVSEQI232E0007</b>	<b>Error creating full text query for explain plan due to invalid query filter.</b>
<b>Explanation</b>	The explain plan content could not be generated due to a parsing error in the filter syntax
<b>EVSEQI232E0010</b>	<b>Error transforming query to native Elasticsearch request:%n{0}</b>
<b>Explanation</b>	The query as specified in the Common Query Syntax could not be transformed into a native Elasticsearch query.
<b>EVSEQI232E0011</b>	<b>Error executing native Elasticsearch search request:%n{0}</b>
<b>Explanation</b>	An error occurred during execution of the Elastisearch query.
<b>EVSEQI232E0012</b>	<b>Error transforming query to native Elastisearch request for explain plan</b>
<b>Explanation</b>	The query as expressed in the Common Query Syntax could not be transformed into an Elasticsearch request when creating the explain plan.

- EVSEQI232E0013**    **An unsupported encoding exception was thrown while generating explain message**  
**Explanation**    The default encoding of utf-8 is not available and caused an exception when generating the explain plan text.
- EVSEQI232E0014**    **Query session has been created with invalid context for this implementation**  
**Explanation**    The context must include all of the required parameters for this query implementation.
- EVSEQI232E0015**    **Error creating a transport client connection to Elasticsearch cluster**  
**Explanation**    A connection to the Elasticsearch cluster could not be established.
- EVSEQI232E0016**    **Failed to position cursor at next event in the result stream**  
**Explanation**    An exception was thrown when trying to move the cursor to the next position in the result stream.
- EVSEQI232E0017**    **The method {0} is unsupported in this implementation of ResultStream**  
**Explanation**    The ResultStream interface only requires that all implementations provide a next operation.
- EVSEQI232E0018**    **Error getting result at current cursor position from handler**  
**Explanation**    An exception was thrown when attempting to get the event data from the current position in the result stream.
- EVSEQI232I0008**    **Inbound query in common syntax form:**
- EVSEQI232I0009**    **Outbound query in native form:**
- EVSEQIE0000**        **Query session has been created with invalid context for this implementation**
- EVSEQIE0001**        **Error creating a transport client connection to Elasticsearch cluster**

---

<b>EVSEQIE0002</b>	<b>Error transforming query into native Elasticsearch request!%c{0}</b>
<b>EVSEQIE0003</b>	<b>Error executing native Elasticsearch search request!%c{0}</b>
<b>EVSEQIE0004</b>	<b>Failed to position cursor at next event in the result stream</b>
<b>Explanation</b>	There was an error when moving the cursor position forward in the stream
<b>EVSEQIE0005</b>	<b>The method {0} is unsupported in this implementation of ResultStream</b>
<b>Explanation</b>	The only requirement on a ResultStream implementation is that they provide a forward cursor via the next method
<b>EVSEQIE0006</b>	<b>Error getting result at current cursor position from handler</b>
<b>Explanation</b>	There was an error retrieving or formatting the result at the cursor position
<b>EVSEQIE0007</b>	<b>Unexpected statement type found when trying to determine query builder implementation</b>
<b>Explanation</b>	The query transformation found an expression other than an instance, property list or aggregate query.
<b>EVSEQIE0008</b>	<b>Unsupported syntax found in aggregate function clause: {0}</b>
<b>Explanation</b>	When processing an aggregation other than count, sum, avg, min or max was found.
<b>EVSEQIE0009</b>	<b>Unsupported encoding exception encountered when formatting result</b>
<b>EVSEQIE0010</b>	<b>An error has occurred because the response reference has not been set in response handler</b>
<b>Explanation</b>	This is a fatal programming error; the Elasticsearch response reference was not set before invoking the handler methods.
<b>EVSEQIE0011</b>	<b>Cursor positioning error; No pending results on result stack</b>
<b>Explanation</b>	The getResult method was invoked but there is no pending result item on the cursor stack.

<b>EVSEQIE0013</b> <b>Explanation</b>	<b>An unsupported encoding exception was thrown while generating explain message</b> An error was encountered when creating a byte array with utf8 encoding
<b>EVSEQIE0016</b>	<b>Error executing full text query due to invalid query filter.</b>
<b>EVSEQIE0017</b>	<b>An unsupported encoding exception was thrown while generateing query hit.</b>
<b>EVSEQII0014</b>	<b>Inbound query in common syntax form:</b>
<b>EVSEQII0015</b>	<b>Outbound query in native form:</b>
<b>EVSEQIW0012</b> <b>Explanation</b>	<b>Error transforming query for explain plan</b> The query transformation failed during processing of the explain plan call.
<b>EVSEREE0001</b> <b>Explanation</b>	<b>Event Routing Consumers are not supported by this Endpoint implementation</b> Event Persistence components only support producers
<b>EVSEREE0002</b> <b>Explanation</b>	<b>Synchronous Event processing is not supported by this component.</b> This component only supports asynchronous processing.
<b>EVSEREE0003</b> <b>Explanation</b>	<b>Error initializing required internal resources</b> Internal resources such as the transformer or storage provider could not be initialized.
<b>EVSEREE0004</b> <b>Explanation</b>	<b>Error transforming event instance from native format to JSON format</b> An error occurred during transformation from XML to JSON
<b>EVSEREE0005</b> <b>Explanation</b>	<b>Fatal exception thrown from storage provider during event processing</b> An error occurred when trying to persist the current event

---

<b>EVSEREE0006</b>	<b>Error creating storage type definition for event type: {0}</b>
<b>Explanation</b>	The event type schema could not be transformed to the storage type definition required by the storage providers.
<b>EVSEREE0007</b>	<b>Error parsing event schema with namespace {0} and event type {1}</b>
<b>Explanation</b>	The EDA event type schema for the specified type could not be parsed.
<b>EVSEREE0008</b>	<b>Error creating schema parser with Event Type Store location: {0}</b>
<b>Explanation</b>	A reference to the EDA schema parser class or service could not be obtained.
<b>EVSERSE0000</b>	<b>Port {0} should be a non-negative and non-zero integer value.</b>
<b>Explanation</b>	Port should be a non-negative integer value.
<b>EVSERSE0001</b>	<b>Index Name {0} has to be all lower case.</b>
<b>Explanation</b>	Index Name has to be all lower case..
<b>EVSERSE0003</b>	<b>Thread Pool Keep Alive Time has to be a non-negative non-zero integer.</b>
<b>Explanation</b>	Thread Pool Keep Alive Time has to be a non-negative and non-zero integer.
<b>EVSERSE0006</b>	<b>Thread Pool Queue size has to be a non-negative integer.</b>
<b>Explanation</b>	Thread Pool Queue size has to be a non-negative integer.
<b>EVSERSE0009</b>	<b>Batch size has to be a non-negative and non-zero integer.</b>
<b>Explanation</b>	Batch size has to be a non-negative and non-zero integer.
<b>EVSERSE0010</b>	<b>Batch write time has to be a non-negative and non-zero integer.</b>
<b>Explanation</b>	Batch write time has to be a non-negative and non-zero integer.
<b>EVSERSE0011</b>	<b>Event Persistence does not support storage type: {0}.</b>
<b>Explanation</b>	This is not supported store type for event persistence.

<b>EVSERSE0012</b>	<b>Can't create service bundle for storage type: {0}.</b>
<b>Explanation</b>	The service bundle could not be created!
<b>EVSERSE0013</b>	<b>Core Thread Pool size has to be a non-negative integer.</b>
<b>Explanation</b>	Core Thread Pool size has to be a non-negative integer.
<b>EVSERSE0014</b>	<b>Not supported storage type {0}.</b>
<b>EVSERSE0015</b>	<b>Hdfs maximum file size has to be a non-negative and non-zero integer.</b>
<b>Explanation</b>	Hdfs maximum file size has to be a non-negative and non-zero integer.
<b>EVSERSE0016</b>	<b>Maximum Thread Pool Size has to be a non-negative and non-zero integer.</b>
<b>Explanation</b>	Maximum Thread Pool Size has to be a non-negative and non-zero integer.
<b>EVSERSE0017</b>	<b>Elasticsearch keystore filepath is not valid.</b>
<b>Explanation</b>	Elasticsearch keystore filepath is not valid.
<b>EVSERSE0018</b>	<b>Elasticsearch truststore filepath is not valid.</b>
<b>Explanation</b>	Elasticsearch truststore filepath is not valid.
<b>EVSERSE0019</b>	<b>Key store should not be blank</b>
<b>Explanation</b>	Key store should not be blank
<b>EVSERSE0020</b>	<b>Trust store should not be blank</b>
<b>Explanation</b>	Trust store should not be blank
<b>EVSERSE0025</b>	<b>{0} must be specified using the following format {1}.</b>
<b>Explanation</b>	URI must be specified using the given format.

---

<b>EVSE0028</b>	<b>Invalid Hive Warehouse Location: {0}</b>
<b>Explanation</b>	Hive Warehouse Location is invalid, please enter a valid location name.
<b>EVSERSI0017</b>	<b>Event Persistence Configuration Validation Information</b>
<b>Explanation</b>	Display Label used for Event Persistence Configuration Validation Information UI
<b>EVSERSI0018</b>	<b>Connection to Elasticsearch node succeeded:</b>
<b>Explanation</b>	Successfully connected to the specified Elasticsearch cluster, index, host and port.
<b>EVSERSI0026</b>	<b>Connection to HDFS succeeded.</b>
<b>Explanation</b>	Connection to HDFS succeeded.
<b>EVSERSI0029</b>	<b>Connection to Hive server succeeded.</b>
<b>Explanation</b>	Connection to Hive server succeeded.
<b>EVSERSW0019</b>	<b>Could not connect to Elasticsearch node:</b>
<b>Explanation</b>	Could not connect to the specified elasticsearch cluster node, index, host and port.
<b>EVSERSW0020</b>	<b>Could not connect to Hive server:</b>
<b>Explanation</b>	Could not connect to the specified Hive server.
<b>EVSERSW0021</b>	<b>Could not connect to HDFS:</b>
<b>Explanation</b>	Could not connect to the specified HDFS database, hive warehouse location,
<b>EVSERSW0022</b>	<b>Cannot get JMX MBeanServer Connector for Runtime Component {0}.</b>
<b>Explanation</b>	Cannot get JMX MBeanServer Connector to the runtime component.
<b>EVSERSW0023</b>	<b>JMX MBeanServer invocation exception to remote runtime component {0}.</b>
<b>Explanation</b>	JMX MBeanServer invocation exception to remote runtime component.

<b>EVSESW0024</b>	<b>Cannot get JMX Connector for remote runtime component {0}.</b>
<b>Explanation</b>	Cannot get JMX Connector for remote runtime component.
<b>EVSESW0025</b>	<b>Cannot ping single SSL enabled elasticsearch node</b>
<b>Explanation</b>	Cannot ping single SSL enabled elasticsearch node
<b>EVSESW0030</b>	<b>Unable to validate the parameter due to the occurrence of one or more dynamic service configuration variables.</b>
<b>Explanation</b>	Parameters that contain dynamic service configuration variables can't be validated because the value of the parameter is unknown at the time of configuration.
<b>Action</b>	This is simply a warning.
<b>EVSESEE0000</b>	<b>No onfiguration passed into this service.</b>
<b>EVSESEE0001</b>	<b>Synchronous Event processing is not supported by this component.</b>
<b>Explanation</b>	Synchronous Event processing is not supported by this component.
<b>EVSESEE0002</b>	<b>Error initializing required internal resources</b>
<b>Explanation</b>	Error initializing required internal resources
<b>EVSESEE0003</b>	<b>Error stopping internal resource {0}</b>
<b>EVSESEE0004</b>	<b>Error transforming event instance from native format to JSON format</b>
<b>Explanation</b>	Error transforming event instance from native format to JSON format
<b>EVSESEE0005</b>	<b>Cannot transforming event {0} instance from native format to JSON format and cannot persist the event into Event Persistence error table.</b>
<b>Explanation</b>	Cannot transforming event {0} instance from native format to JSON format and cannot persist the event into Event Persistence error table.
<b>EVSESEE0006</b>	<b>Fatal exception thrown from storage provider during processing event {0}.</b>
<b>Explanation</b>	Fatal exception thrown from storage provider during event processing.

---

<b>EVSESEE0007</b>	<b>Error creating storage type definition for event type: {0}</b>
<b>Explanation</b>	Error creating storage type definition for the given event type.
<b>EVSESEE0008</b>	<b>DES Event Type {0} has not been registered in Digital Event Type TypeRepository.</b>
<b>Explanation</b>	DES Event Type has not been registered in Digital Event Type TypeRepository.
<b>EVSESEE0009</b>	<b>Invalid Configuration class type '{0}'. : Expected type: '{1}'.</b>
<b>Explanation</b>	Invalid Configuration class type.
<b>EVSESEE0010</b>	<b>'{0}' Digital Event Data Type for event field '{1}' is not supported.</b>
<b>Explanation</b>	Given Digital Event Data Type is not supported.
<b>EVSESEE0011</b>	<b>Error initializing required internal resources; a restart may be required</b>
<b>Explanation</b>	The required resources could not be initialized. This could be due to a wiring or classpath issue.
<b>EVSESEE0012</b>	<b>A fatal and unexpected exception was thrown when creating the generic storage event instance.</b>
<b>Explanation</b>	A storage event implementation could not be instantiated from the DES event instance.
<b>EVSESEFE0000</b>	<b>Port {0} should be a non-negative and non-zero integer value.</b>
<b>Explanation</b>	Port should be a non-negative and non-zero integer value.
<b>EVSESEFE0001</b>	<b>Thread Pool Keep Alive Time has to be a non-negative integer.</b>
<b>Explanation</b>	Thread Pool Keep Alive Time has to be a non-negative integer.
<b>EVSESEFE0002</b>	<b>Batch size has to be a non-negative and non-zero integer.</b>
<b>Explanation</b>	Batch size has to be a non-negative and non-zero integer.
<b>EVSESEFE0003</b>	<b>Batch write time has to be a non-negative and non-zero integer.</b>
<b>Explanation</b>	Batch write time has to be a non-negative and non-zero integer.

<b>EVSESFE0004</b>	<b>Event Persistence does not support storage type: {0}.</b>
<b>Explanation</b>	This is not supported storage type for Event Persistence.
<b>EVSESFE0005</b>	<b>Thread Pool Queue size has to be a non-negative and non-zero integer.</b>
<b>Explanation</b>	Thread Pool Queue size has to be a non-negative and non-zero integer.
<b>EVSESFE0006</b>	<b>Core Thread Pool size has to be a non-negative integer.</b>
<b>Explanation</b>	Core Thread Pool size has to be a non-negative integer.
<b>EVSESFE0007</b>	<b>Hdfs maximum file size has to be a non-negative and non-zero integer.</b>
<b>Explanation</b>	Hdfs maximum file size has to be a non-negative and non-zero integer.
<b>EVSESFE0008</b>	<b>Maximum Thread Pool Size has to be a non-negative and non-zero integer.</b>
<b>Explanation</b>	Maximum Thread Pool Size has to be a non-negative and non-zero integer.
<b>EVSESFE0016</b>	<b>{0} must be specified using the following format {1}.</b>
<b>Explanation</b>	URI must be specified using the given format.
<b>EVSESFE0018</b>	<b>Index name {0} has to be all lower case.</b>
<b>Explanation</b>	Index name has to be in all lower case.
<b>EVSESFE0019</b>	<b>Elasticsearch keystore filepath is not valid.</b>
<b>Explanation</b>	Elasticsearch keystore filepath is not valid.
<b>EVSESFE0020</b>	<b>Elasticsearch truststore filepath is not valid.</b>
<b>Explanation</b>	Elasticsearch truststore filepath is not valid.
<b>EVSESFE0021</b>	<b>Invalid Hive Warehouse Location: {0}</b>
<b>Explanation</b>	Hive Warehouse Location is invalid, please enter a valid location name.

---

<b>EVSESEFI0009</b>	<b>Connection to HDFS succeeded.</b>
<b>Explanation</b>	Connection to HDFS succeeded.
<b>EVSESEFI0017</b>	<b>Connection to Hive server succeeded.</b>
<b>Explanation</b>	Connection to Hive server succeeded.
<b>EVSESEFI0022</b>	<b>Connection to Elasticsearch node succeeded:</b>
<b>Explanation</b>	Connection to specific Elasticsearch succeeded.
<b>EVSESEFW0010</b>	<b>Could not connect to Elasticsearch node:</b>
<b>Explanation</b>	Could not connect to the specified elasticsearch cluster node, index, host and port.
<b>EVSESEFW0011</b>	<b>Could not connect to Hive server:</b>
<b>Explanation</b>	Could not connect to the specified Hive server.
<b>EVSESEFW0012</b>	<b>Could not connect to HDFS:</b>
<b>Explanation</b>	Could not connect to the specified HDFS database, hive warehouse location.
<b>EVSESEFW0013</b>	<b>Cannot get JMX MBeanServer Connector for Runtime Component {0}.</b>
<b>Explanation</b>	Cannot get JMX MBeanServer Connector to the runtime component.
<b>EVSESEFW0014</b>	<b>JMX MBeanServer invocation exception to remote runtime component {0}.</b>
<b>Explanation</b>	JMX MBeanServer invocation exception to remote runtime component.
<b>EVSESEFW0015</b>	<b>Cannot get JMX Connector for remote runtime component</b>
<b>Explanation</b>	Cannot get JMX Connector for remote runtime component.
<b>EVSESEFW0023</b>	<b>Unable to validate the parameter due to the occurrence of one or more dynamic service configuration variables.</b>
<b>Explanation</b>	Parameters that contain dynamic service configuration variables can't be validated because the value of the parameter is unknown at the time of configuration.
<b>Action</b>	This is simply a warning.

<b>EVSESI172E0000</b>	<b>Process method called before provider has been started</b>
<b>Explanation</b>	This is a programatic initialization error. The storage providers start method was not called during initialization.
<b>EVSESI172E0001</b>	<b>Error initializing required internal resources</b>
<b>Explanation</b>	An error occurred during initialization of the various implementation classes for this storage provider.
<b>EVSESI172E0002</b>	<b>Error creating or accessing bulk indexer for event type: {0}</b>
<b>Explanation</b>	A bulk indexer instance could not be accessed or created for the specified event type.
<b>EVSESI172E0003</b>	<b>Error stopping resource {0} on provider shutdown</b>
<b>Explanation</b>	An internal resource threw an exception while stopping the storage provider.
<b>EVSESI172E0005</b>	<b>Failed to create Elasticsearch transport client connection to cluster {0}, index {1} on server {2} with user {3}.</b>
<b>Explanation</b>	The client could not establish a connection to the Elasticsearch cluster.
<b>EVSESI172E0006</b>	<b>Elasticsearch client manager not started for cluster {0}, index {1} on server {2} with user {3}</b>
<b>Explanation</b>	An attempt to get a connection was made before the client manager was started.
<b>EVSESI172E0007</b>	<b>Error stopping bulk indexer for type: {0}</b>
<b>Explanation</b>	The bulk indexer instance for the specified type threw an exception on shutdown.
<b>EVSESI172E0008</b>	<b>Error creating Elasticsearch bulk indexing request</b>
<b>Explanation</b>	An error occurred while formatting an Elasticsearch bulk indexing request for the current event batch
<b>EVSESI172E0009</b>	<b>Error executing Elasticsearch bulk indexing request</b>
<b>Explanation</b>	The Elasticsearch bulk indexing request for the specified event batch could not be executed.

---

<b>EVSESI172E0010</b>	<b>Error loading metadata for persistence error type; logging to local file</b>
<b>Explanation</b>	Metadata for the persistence error type couldn't be found or created. All messages will be logged to the local log file.
<b>EVSESI172E0011</b>	<b>Unable to write internal persistence error event; defaulting to log file:%n {0}</b>
<b>Explanation</b>	The logger could not persist the error event data to the data store. The error will be written to the default log file.
<b>EVSESI172E0012</b>	<b>Error storing internal persistence error event to Elasticsearch index.</b>
<b>Explanation</b>	The persistence error event could not be stored in elasticsearch due to an exception.
<b>EVSESI172E0013</b>	<b>Exception encountered during auto registration of event type: {0}</b>
<b>Explanation</b>	Storage could not be allocated for the specified event type due to an Elasticsearch error.
<b>EVSESI172E0014</b>	<b>Error getting Elasticsearch client for auto registration</b>
<b>Explanation</b>	An exception occurred when trying to access the Elasticsearch transport client
<b>EVSESI172E0015</b>	<b>An event type mapping already exists for the event type: {0}</b>
<b>Explanation</b>	Storage for the specified event type has already been allocated.
<b>EVSESI172E0016</b>	<b>Error checking for existing type in Elasticsearch index</b>
<b>Explanation</b>	An exception was thrown while checking Elasticsearch for a registered event type
<b>EVSESI172E0017</b>	<b>No acknowledgment received from Elasticsearch cluster after create index operation</b>
<b>Explanation</b>	The Elasticsearch node failed to acknowledge the status of the create index request.
<b>EVSESI172E0018</b>	<b>No acknowledgment received from Elasticsearch cluster after type mapping operation</b>
<b>Explanation</b>	The Elasticsearch node failed to acknowledge the status of the put type mapping request.

<b>EVSESI172E0019</b>	<b>An Elasticsearch exception occurred while creating the type mapping</b>
<b>Explanation</b>	The type mapping could not be added due to an exception thrown by the Elasticsearch client-server.
<b>EVSESI172E0020</b>	<b>Failed to initialize Elasticsearch schema parser implementation</b>
<b>Explanation</b>	The event type schema parser couldn't be initialized; no event type parsing is possible.
<b>EVSESI172E0021</b>	<b>Error creating schema parser with Event Type Store location: {0}</b>
<b>Explanation</b>	The EDA event type schema parser could not be initialized.
<b>EVSESI172E0022</b>	<b>Error parsing event schema with namespace {0} and event type {1}</b>
<b>Explanation</b>	The event type definition for the given namespace and event type could not be parsed.
<b>EVSESI172E0023</b>	<b>A valid namespace and event type are required to produce an Elasticsearch type mapping.</b>
<b>Explanation</b>	Event type information could not be found for the specified namespace and event type.
<b>EVSESI172E0024</b>	<b>The event persistence annotation is not recognized: {0}</b>
<b>Explanation</b>	An annotation specified in the event type definition is not known or supported.
<b>EVSESI172E0027</b>	<b>Error retrieving Elasticsearch client for metadata verification</b>
<b>Explanation</b>	A connection couldn't be established while trying to load metadata from index
<b>EVSESI172E0029</b>	<b>Error closing transport client connection to cluster {0}, index {1} on server {2} with user {3}</b>
<b>Explanation</b>	An error occurred disconnecting from the Elasticsearch cluster
<b>EVSESI172E0030</b>	<b>The event persistence annotation is not recognized: {0}</b>
<b>Explanation</b>	An annotation value was specified that is not supported by event persistence

---

<b>EVSESI172E0031</b>	<b>Error retrieving normalized type from component for event type: {0}</b>
<b>Explanation</b>	An exception was thrown by the component when generating the normalized type for the event type
<b>EVSESI172I0004</b>	<b>Elasticsearch transport client successfully connected to cluster {0}, index {1} on server {2} with user {3}</b>
<b>Explanation</b>	The connection to the Elasticsearch cluster was successful.
<b>EVSESI172I0028</b>	<b>Elasticsearch transport client successfully disconnected from cluster {0}, index {1} on server {2} with user {3}</b>
<b>Explanation</b>	The component has disconnected from the Elasticsearch cluster
<b>EVSESI172W0025</b>	<b>Task manager queue is full; The operation will be re-tried</b>
<b>Explanation</b>	The task queue is at it's maximum size. The operation is re-tried after a slight delay.
<b>EVSESI172W0026</b>	<b>Thread interrupted while waiting for task re-submission</b>
<b>Explanation</b>	The task manager thread was interrupted during re-submission delay. The operation will be re-tried immediately.
<b>EVSESI232E0000</b>	<b>Process method called before provider has been started</b>
<b>Explanation</b>	This is a programatic initialization error. The storage providers start method was not called during initialization.
<b>EVSESI232E0001</b>	<b>Error initializing required internal resources</b>
<b>Explanation</b>	An error occurred during initialization of the various implementation classes for this storage provider.
<b>EVSESI232E0002</b>	<b>Error creating or accessing bulk indexer for event type: {0}</b>
<b>Explanation</b>	A bulk indexer instance could not be accessed or created for the specified event type.
<b>EVSESI232E0003</b>	<b>Error stopping resource {0} on provider shutdown</b>
<b>Explanation</b>	An internal resource threw an exception while stopping the storage provider.

**EVSESI232E0005**    **Failed to create Elasticsearch transport client connection to cluster {0}, index {1} on server {2} with user {3}.**

**Explanation**        The client could not establish a connection to the Elasticsearch cluster.

**EVSESI232E0006**    **Elasticsearch client manager not started for cluster {0}, index {1} on server {2} with user {3}**

**Explanation**        An attempt to get a connection was made before the client manager was started.

**EVSESI232E0007**    **Error stopping bulk indexer for type: {0}**

**Explanation**        The bulk indexer instance for the specified type threw an exception on shutdown.

**EVSESI232E0008**    **Error creating Elasticsearch bulk indexing request**

**Explanation**        An error occurred while formatting an Elasticsearch bulk indexing request for the current event batch

**EVSESI232E0009**    **Error executing Elasticsearch bulk indexing request**

**Explanation**        The Elasticsearch bulk indexing request for the specified event batch could not be executed.

**EVSESI232E0010**    **Error loading metadata for persistence error type; logging to local file**

**Explanation**        Metadata for the persistence error type couldn't be found or created. All messages will be logged to the local log file.

**EVSESI232E0011**    **Unable to write internal persistence error event; defaulting to log file:%n {0}**

**Explanation**        The logger could not persist the error event data to the data store. The error will be written to the default log file.

**EVSESI232E0012**    **Error storing internal persistence error event to Elasticsearch index.**

**Explanation**        The persistence error event could not be stored in elasticsearch due to an exception.

**EVSESI232E0013**    **Exception encountered during auto registration of event type: {0}**

**Explanation**        Storage could not be allocated for the specified event type due to an Elasticsearch error.

---

<b>EVSESI232E0014</b>	<b>Error getting Elasticsearch client for auto registration</b>
<b>Explanation</b>	An exception occurred when trying to access the Elasticsearch transport client
<b>EVSESI232E0015</b>	<b>An event type mapping already exists for the event type: {0}</b>
<b>Explanation</b>	Storage for the specified event type has already been allocated.
<b>EVSESI232E0016</b>	<b>Error checking for existing type in Elasticsearch index</b>
<b>Explanation</b>	An exception was thrown while checking Elasticsearch for a registered event type
<b>EVSESI232E0017</b>	<b>No acknowledgment received from Elasticsearch cluster after create index operation</b>
<b>Explanation</b>	The Elasticsearch node failed to acknowledge the status of the create index request.
<b>EVSESI232E0018</b>	<b>No acknowledgment received from Elasticsearch cluster after type mapping operation</b>
<b>Explanation</b>	The Elasticsearch node failed to acknowledge the status of the put type mapping request.
<b>EVSESI232E0019</b>	<b>An Elasticsearch exception occurred while creating the type mapping</b>
<b>Explanation</b>	The type mapping could not be added due to an exception thrown by the Elasticsearch client-server.
<b>EVSESI232E0020</b>	<b>Failed to initialize Elasticsearch schema parser implementation</b>
<b>Explanation</b>	The event type definition for the given namespace and event type could not be parsed.
<b>EVSESI232E0021</b>	<b>Error creating schema parser with Event Type Store location: {0}</b>
<b>Explanation</b>	The EDA event type schema parser could not be initialized.
<b>EVSESI232E0022</b>	<b>Error parsing event schema with namespace {0} and event type {1}</b>
<b>Explanation</b>	Event type information could not be found for the specified namespace and event type.

**EVSESI232E0023**    **A valid namespace and event type are required to produce an Elasticsearch type mapping.**

**Explanation**    Event type information could not be found for the specified namespace and event type.

**EVSESI232E0024**    **The event persistence annotation is not recognized: {0}**

**Explanation**    An annotation specified in the event type definition is not known or supported.

**EVSESI232E0027**    **Error retrieving Elasticsearch client for metadata verification**

**Explanation**    A connection couldn't be established while trying to load metadata from index

**EVSESI232E0029**    **Error closing transport client connection to cluster {0}, index {1} on server {2} with user {3}**

**Explanation**    An error occurred when diconnecting from the Elasticsearch cluster

**EVSESI232E0030**    **The event persistence annotation is not recognized: {0}**

**Explanation**    An annotation value was specified that is not supported by event persistence

**EVSESI232E0031**    **Error retrieving normalized type from component for event type: {0}**

**Explanation**    An exception was thrown by the component when generating the normalized type for the event type

**EVSESI232E0032**    **Error generating cache key for resource**

**Explanation**    There was an error generating the cache key for the specified elasticsearch resource; verify variable values.

**EVSESI232E0033**    **Error creating and starting bulk indexer for event type: {0}**

**Explanation**    The bulk indexer for the stated type could not be created or started

**EVSESI232E0034**    **Validation of dynamic service configuration against provided values failed**

**Explanation**    A dynamic service configuration was provided but the variables are not present in the event.

---

<b>EVSESI232E0035</b>	<b>Validation of dynamic service configuration failed. Event can not be persisted: Header: {0} Body: {1}</b>
<b>Explanation</b>	The values required for using a dynamic configuration were not supplied in the event being processed.
<b>EVSESI232E0036</b>	<b>Error initialising internal resources for provider; operation will be re-tried. Exception repeated {0} times</b>
<b>Explanation</b>	Internal initialisation failed. The operation will be retried until successful or the component is restarted.
<b>EVSESI232E0037</b>	<b>Error creating bulk indexer for event type {0}; operation will be re-tried; Exception repeated {1} times</b>
<b>Explanation</b>	An indexer could not be created to process the specified event type. This could be due to a failure to connect to the cluster for the required metadata.
<b>EVSESI232E0038</b>	<b>Error creating Elasticsearch bulk indexing request; operation will be re-tried; Exception repeated {0} times</b>
<b>Explanation</b>	There was an error while creating the indexing request most likely due to a connectivity issue between the client and server
<b>EVSESI232E0039</b>	<b>Error executing Elasticsearch bulk indexing request; operation will be re-tried; Exception repeated {0} times</b>
<b>Explanation</b>	There was an error while creating the indexing request most likely due to a connectivity issue between the client and server
<b>EVSESI232E0040</b>	<b>An exception occurred while checking the cluster for the specified destination index: {0}</b>
<b>Explanation</b>	When the provider invoked the index exists call to Elasticsearch, the API threw an exception.
<b>Action</b>	Check the status of the Elasticsearch cluster.
<b>EVSESI232E0041</b>	<b>An Elasticsearch exception occurred while creating the specified destination index: {0}</b>
<b>Explanation</b>	When the provider invoked the create index call to Elasticsearch, the API threw an exception.
<b>Action</b>	Check the status of the Elasticsearch cluster

<b>EVSESI232E0042</b>	<b>An error occurred while attempting to determine if auto-registration is required for type: {0} in index: {1}</b>
<b>Explanation</b>	The service could not access or process the Elasticsearch type mapping in the given index.
<b>Action</b>	Check the health of the Elasticsearch cluster.
<b>EVSESI232I0004</b>	<b>Elasticsearch transport client successfully connected to cluster {0}, index {1} on server {2} with user {3}</b>
<b>Explanation</b>	The connection to the Elasticsearch cluster was successful.
<b>EVSESI232I0028</b>	<b>Elasticsearch transport client successfully disconnected from cluster {0}, index {1} on server {2} with user {3}</b>
<b>Explanation</b>	The component has disconnected from the Elasticsearch cluster
<b>EVSESI232W0025</b>	<b>Task manager queue is full; The operation will be re-tried</b>
<b>Explanation</b>	The task queue is at it's maximum size. The operation is re-tried after a slight delay.
<b>EVSESI232W0026</b>	<b>Thread interrupted while waiting for task re-submission</b>
<b>Explanation</b>	The task manager thread was interrupted during re-submission delay. The operation will be re-tried immediately.
<b>EVSEVCE0000</b>	<b>No transformer found for type: {0}</b>
<b>Explanation</b>	No transformer of the required type, for example XML could be found.
<b>EVSEVEE0000</b>	<b>Elasticsearch transport client successfully connected to cluser {0}, index {1} on server {2}, port {3} with user {4}</b>
<b>EVSEVEE0001</b>	<b>Failed creating Elasticsearch transport client to connect to cluser {0}, index {1} on server {2}, port {3} with user {4}</b>
<b>EVSEVEE0002</b>	<b>Elasticsearch transport client is not started to connect to cluser {0}, index {1} on server {2}, port {3} with user {4}.</b>

EVSEVVEE0003	Error retrieving Elasticsearch client from pool
EVSEVVEE0004	Error checking for existing type in Elasticsearch index
EVSEVVEE0005	Exception encountered auto registration of event type: {0}
EVSEVVEE0006	Event Routing Consumers are not supported by this Endpoint implementation
EVSEVVEE0007	Synchronous Event processing is not supported by this component.
EVSEVVEE0008	Error transforming event instance from native format to JSON format
EVSEVVEE0009	Error initializing required internal resources
EVSEVVEE0010	Error retrieving Elasticsearch client from pool during bulk indexing task
EVSEVVEE0011	Error creating Elasticsearch bulk indexing request
EVSEVVEE0012	Error executing Elasticsearch bulk indexing request
EVSEVVEE0013	Unable to write internal persistence error event defaulting to log file:%s {0}
EVSEVVEE0014	Error storing internal persistence error event to Elastisearch
EVSEVVEE0015	Error loading metadata for persistence error type; logging to local file
EVSEVVEE0017	Elasticsearch transport client not started for cluster {0}, index {1} on server {2} with user {3}.

EVSEVEE0019	<b>Elasticsearch transport client successfully connected to cluster {0}, index {1} on server {2} with user {3}</b>
EVSEVEE0020	<b>Failed to create Elasticsearch transport client connection to cluster {0}, index {1} on server {2} with user {3}</b>
EVSEVEE0021	<b>Not Compliant JMX MBean, cannot create MBean {0}.</b>
<b>Explanation</b>	Failed to create Elasticsearch JMX MBean
EVSEVEE0023	<b>An internal error occurred during schema processing operations</b>
<b>Explanation</b>	This error is most likely due to incorrect wiring of the ETS/XSD services
EVSEVEI0022	
EVSEVEW0016	<b>Task manager queue is full; The operation will be re-tried</b>
<b>Explanation</b>	The work queue has reached its maximum size.
EVSEVEW0018	<b>Thread interrupted while waiting for task re-submission</b>
EVSEVHE0000	<b>Hive table could not be found or created for Event Type {0}</b>
<b>Explanation</b>	Hive table could not be found or created in event store instance
EVSEVHE0001	<b>Error loading Hive table from event store instance</b>
<b>Explanation</b>	Error loading Hive table from event store instance
EVSEVHE0002	<b>Failed to generate HDFS URI ({0})</b>
<b>Explanation</b>	Failed to generate HDFS URI based on the configuration parameters.
<b>Action</b>	Inspect configuration parameters defined in Command Central's UI.
EVSEVHE0003	<b>Failed to generate Hive URI ({0})</b>
<b>Explanation</b>	Failed to generate Hive URI based on the configuration parameters set.
<b>Action</b>	Inspect the configuration parameters defined in Command Central's UI.

---

<b>EVSEVHE0004</b>	<b>Error creating HDFS Producer for Event Type: {0}</b>
<b>Explanation</b>	Error creating HDFS Producer
<b>EVSEVHE0005</b>	<b>Event could not be processed by HDFS producer</b>
<b>Explanation</b>	Event could not be processed by HDFS producer
<b>EVSEVHE0006</b>	<b>Unable to create or locate Hive persistence errors table; defaulting to log file</b>
<b>Explanation</b>	Unable to create or locate Hive persistence errors table
<b>EVSEVHE0007</b>	<b>Unable to write internal persistence error event; defaulting to log file</b>
<b>Explanation</b>	Unable to write internal persistence error event
<b>EVSEVHE0008</b>	<b>Synchronous Event processing is not supported by this component.</b>
<b>Explanation</b>	Event Persistence components only support asynchronous event processing.
<b>EVSEVHE0009</b>	<b>Consumers are not supported by the HDFS Endpoint</b>
<b>Explanation</b>	The EVP HDFS Component only supports producers for event persistence
<b>EVSEVHE0010</b>	<b>Error encountered during batch processing.</b>
<b>Explanation</b>	An error occurred during batch processing. Possible network connection failure.
<b>Action</b>	Check your network connection.
<b>EVSEVHE0011</b>	<b>Ping Hive Server {0} failed.</b>
<b>Explanation</b>	Hive Server is not available.
<b>EVSEVHE0012</b>	<b>Ping NameNode {0} failed.</b>
<b>Explanation</b>	Cannot access the NameNode.
<b>EVSEVHE0013</b>	<b>Not Compliant JMX MBean, cannot create MBean {0}.</b>
<b>Explanation</b>	Not Compliant JMX MBean.

<b>EVSEVHE0015</b>	<b>An internal error occurred during schema processing operations</b>
<b>Explanation</b>	This error is most likely due to incorrect wiring of the ETS/XSD services
<b>EVSEVHE0016</b>	<b>Error transforming event instance from native format to JSON format</b>
<b>Explanation</b>	The XML event could not be transformed to JSON possibly due to invalid content
<b>EVSEVHI0014</b>	<b>Successfully created Hadoop Connectivity JMX MBean {0}.</b>
<b>Explanation</b>	Hadoop Connectivity JMX MBean created.
<b>EVSEVJE0002</b>	<b>JDBC Database Type not supported: {0}</b>
<b>EVSEVJE0003</b>	<b>Error Starting JDBC Component ({0})</b>
<b>Explanation</b>	The EVP JDBC Component could not be started
<b>EVSEVJE0004</b>	<b>Error Stopping JDBC Component ({0})</b>
<b>Explanation</b>	An internal error occurred when stopping the JDBC Component
<b>EVSEVJE0005</b>	<b>Error creating JDBC Producer for event type: {0}</b>
<b>Explanation</b>	The EVP JDBC Endpoint could not create a Producer for the given event type.
<b>EVSEVJE0006</b>	<b>Consumers are not supported by the JDBC Endpoint</b>
<b>Explanation</b>	The EVP JDBC Component only supports producers for event persistence
<b>EVSEVJE0007</b>	<b>No metadata found for event type: {0}</b>
<b>Explanation</b>	No JDBC metadata was found for the given event type.
<b>EVSEVJE0008</b>	<b>Database exception while searching for event metadata!</b>
<b>Explanation</b>	The metadata lookup failed with a database exception.

<b>EVSEVJE0009</b>	<b>Unable to write internal persistence error event defaulting to log file %n%n{0}</b>
<b>Explanation</b>	The PersistenceError event could not be written to the store.
<b>EVSEVJE0011</b>	<b>Unexpected error during database rollback operation</b>
<b>Explanation</b>	The database system reported an exception while performing the rollback
<b>EVSEVJE0012</b>	<b>Error encountered during batch processing! Number of batched events: {0}</b>
<b>Explanation</b>	An error was reported while writing the events to the persistence store.
<b>EVSEVJE0013</b>	<b>Event could not be processed by producer</b>
<b>Explanation</b>	An error occurred during event processing by this producer.
<b>EVSEVJE0014</b>	<b>Synchronous Event processing is not supported by this component.</b>
<b>Explanation</b>	Event Persistence components only support asynchronous event processing.
<b>EVSEVJI0000</b>	<b>JDBC Connection Pool {0}{1} started with initial size of {2} and max size of {3}</b>
<b>EVSEVJI0001</b>	<b>JDBC Connection Pool closed</b>
<b>EVSEVJW0010</b>	<b>No metadata found for persistence error logger; defaulting to local log files!</b>
<b>Explanation</b>	The metadata for the internal persistence error event type was not found in the store.
<b>EVSEVPE0000</b>	<b>Error Connecting ParStream Server for host: {0}, port: {1} and user: {2}.</b>
<b>Explanation</b>	Error Connecting to ParStream Streaming Server.
<b>Action</b>	Please make sure that the database server is up and running.
<b>EVSEVPE0001</b>	<b>No metadata found for event type: {0}</b>
<b>EVSEVPE0002</b>	<b>AutoRegistration failed for Event Type with NameSpace {0} : EventType {1}</b>
<b>Explanation</b>	Check Database status and connection

<b>EVSEVPE0003</b>	<b>Database exception while searching for event metadata!</b>
<b>Explanation</b>	Database exception while searching for event metadata!
<b>EVSEVPE0004</b>	<b>Synchronous Event processing is not supported by this component.</b>
<b>Explanation</b>	Synchronous Event processing is not supported by this component.
<b>EVSEVPE0005</b>	<b>Error Starting ParStream Streaming Component for host: {0} and port: {1}</b>
<b>Explanation</b>	Error Starting ParStream Streaming Component for host: {0} and port: {1}
<b>EVSEVPE0006</b>	<b>Error Stopping ParStream Component for host: {0} and port: {1}</b>
<b>Explanation</b>	Error Stopping ParStream Component
<b>EVSEVPE0007</b>	<b>Unexpected error during database rollback operation</b>
<b>Explanation</b>	Unexpected error during database rollback operation
<b>EVSEVPE0008</b>	<b>Error encountered during batch processing! Number of batched events: {0}</b>
<b>Explanation</b>	Error encountered during batch processing!
<b>EVSEVPE0009</b>	<b>Unable to write internal persistence error event, defaulting to log file %n%n{0}</b>
<b>Explanation</b>	Unable to write internal persistence error event defaulting to log file.
<b>EVSEVPE0010</b>	<b>Cannot get metadata information for event namespace {0} and type {1}.</b>
<b>Explanation</b>	Cannot get metadata information for the event type.
<b>EVSEVPE0011</b>	<b>Error creating ParStream Producer for event type: {0}</b>
<b>Explanation</b>	Error creating ParStream Producer for event type.
<b>EVSEVPW0000</b>	<b>No metadata found for persistence error logger; defaulting to local log files!</b>
<b>Explanation</b>	No metadata found for persistence error logger; defaulting to local log files!

---

<b>EVSHQI530E0000</b>	<b>Hive query execution failed with unexpected exception</b>
<b>Explanation</b>	An unexpected exception occurred during the execution of the Hive query
<b>EVSHQI530E0001</b>	<b>Error transforming common query for explain plan</b>
<b>Explanation</b>	An error occurred when transforming the common query to native format for the explain plan
<b>EVSHQI530E0002</b>	<b>An unsupported encoding exception was thrown while generating explain message</b>
<b>Explanation</b>	The default encoding of utf-8 is required when creating the explain plan
<b>EVSHQI530E0003</b>	<b>Failed to close hive JDBC result set</b>
<b>Explanation</b>	An exception was thrown during the close method on the JDBC result set
<b>EVSHQI530E0004</b>	<b>Failed to close hive JDBC statement</b>
<b>Explanation</b>	An exception was thrown when closing the JDBC statement
<b>EVSHQI530E0007</b>	<b>The context did not contain the required parameters</b>
<b>Explanation</b>	The context parameters for the specified session were invalid.
<b>EVSHQI530E0008</b>	<b>Error creating Hive SQL query in the current session.</b>
<b>Explanation</b>	Could not create a JDBC connection and or Hive Query using the current session.
<b>EVSHQI530E0009</b>	<b>Full text query not supported by this implementation.</b>
<b>Explanation</b>	This query implementation does not support full text queries.
<b>EVSHQI530E0010</b>	<b>Error closing current Hive JDBC connection.</b>
<b>Explanation</b>	An exception was thrown when the close method of the connection was invoked.
<b>EVSHQI530E0011</b>	<b>Error initializing Hive JDBC connection.</b>
<b>Explanation</b>	An error occurred when creating the Hive JDBC connection

- EVSHQI530E0012 Error setting default database in Hive JDBC connection.**  
**Explanation** An exception was thrown when issuing the use database statement
- EVSHQI530E0013 Error closing active Hive JDBC statement.**  
**Explanation** An exception was thrown during the close invocation on the current JDBC statement.
- EVSHQI530E0014 Failed to position cursor at next event in the result stream**  
**Explanation** An error occurred when advancing the cursor in the result set.
- EVSHQI530E0015 The method {0} is unsupported in this implementation of ResultStream**  
**Explanation** Implementors of the result stream must implement the next method; the other positional methods are optional.
- EVSHQI530E0016 Error getting result at current cursor position from handler**  
**Explanation** An error occurred when retrieving the event data from the current cursor position.
- EVSHQI530E0017 Error closing Hive JDBC result set on close of result stream.**  
**Explanation** The JDBC result set could not be closed when closing the result stream.
- EVSHQI530E0018 Property '{0}' in group by expression must appear in select expression**  
**Explanation** A property specified in the group by clause is not present in the select list
- EVSHQI530E0019 Property '{0}' in select expression must appear in group by expression**  
**Explanation** A property in the select expression is not present in the group by clause
- EVSHQI530E0020 Property '{0}' in order by expression must appear in select and group by expression**  
**Explanation** A property specified in the order by expression is not present in the select expression
- EVSHQI530I0005 Inbound query in common syntax form:**  
**Explanation** Label for the explain plain

---

<b>EVSHQI530I0006</b>	<b>Outbound query in native form:</b>
<b>Explanation</b>	Explain plan label
<b>EVSHQIE0000</b>	<b>Unsupported date time format in string literal: {0}.</b>
<b>Explanation</b>	Unsupported date time format in string literal
<b>EVSHQIE0001</b>	<b>Hive query execution failed.</b>
<b>Explanation</b>	Hive query execution failed.
<b>EVSHQIE0002</b>	<b>Failed to close result set.</b>
<b>Explanation</b>	Failed to close result set.
<b>EVSHQIE0003</b>	<b>Failed to close statement.</b>
<b>Explanation</b>	Failed to close statement.
<b>EVSHQIE0004</b>	<b>HiveQuerySession initialize JDBC Connection failed.</b>
<b>Explanation</b>	HiveQuerySession initialize JDBC Connection failed.
<b>EVSHQIE0005</b>	<b>Close Connection failed.</b>
<b>Explanation</b>	Close Connection failed.
<b>EVSHQIE0007</b>	<b>Result cannot be formatted to JSON. format</b>
<b>Explanation</b>	Result cannot be formatted to JSON format.
<b>EVSHQIE0008</b>	<b>Failed get next result.</b>
<b>Explanation</b>	Failed get next result.
<b>EVSHQIE0009</b>	<b>Cannot create connection statement.</b>
<b>Explanation</b>	Cannot create connection statement.

<b>EVSHQIE0010</b>	<b>Failed to create {0}</b>
<b>EVSHQIE0011</b>	<b>Property "{0}" in group by expression must appear in select expression</b>
<b>Explanation</b>	Group by property is required to appear in select expression
<b>EVSHQIE0012</b>	<b>Property "{0}" in select expression must appear in group by expression</b>
<b>Explanation</b>	Property in select expression must appear in the group by expression
<b>EVSHQIE0013</b>	<b>Property "{0}" in order by expression must appear in select and group by expression</b>
<b>Explanation</b>	Property in order by expression must be included in the group by and select expression
<b>EVSHQIE0014</b>	<b>Full text query not supported by this implementation</b>
<b>Explanation</b>	This query implementation does provide full text search capabilities
<b>EVSHQIE0015</b>	<b>Error transforming query for explain plan</b>
<b>EVSHQIE0016</b>	<b>An unsupported encoding exception was thrown while generating explain message</b>
<b>EVSHQII0006</b>	<b>Method: {0} is not supported.</b>
<b>Explanation</b>	Method is not supported.
<b>EVSHQII0017</b>	<b>Inbound query in common syntax form:</b>
<b>EVSHQII0018</b>	<b>Outbound query in native form:</b>
<b>EVSHSI530E0000</b>	<b>Process method called before storage provider was started</b>
<b>Explanation</b>	The storage provider was not initialized and a call was made to process an event.
<b>EVSHSI530E0001</b>	<b>Error initializing required internal resources for provider</b>
<b>Explanation</b>	The required internal resources for the storage provider couldn't be initialized.

---

<b>EVSHSI530E0002</b>	<b>Error creating or accessing HDFS processor for event type: {0}</b>
<b>Explanation</b>	An HDFS processor for the given event type could not be accessed or instantiated.
<b>EVSHSI530E0003</b>	<b>Error stopping resource {0} on storage provider shutdown</b>
<b>Explanation</b>	An exception was through when stopping an internal resource on provider shutdown.
<b>EVSHSI530E0004</b>	<b>Error closing HDFS Writer instance on processor shutdown</b>
<b>Explanation</b>	The HDFS writer and stream threw an exception on close.
<b>EVSHSI530E0005</b>	<b>Unexpected error encountered during batch processing.</b>
<b>Explanation</b>	There was an HDFS or Hive error encountered during the processing of an event batch.
<b>EVSHSI530E0006</b>	<b>Error processing batch during execution of auto-write task.</b>
<b>Explanation</b>	An unexpected exception was thrown during batch processing.
<b>EVSHSI530E0007</b>	<b>Error processing batch during execution of on-demand task</b>
<b>Explanation</b>	An expected exception was thrown during batch processing
<b>EVSHSI530E0008</b>	<b>Error starting HDFS processor resource for event type: {0}</b>
<b>Explanation</b>	An error was thrown when initializing and starting the HDFS processor.
<b>EVSHSI530E0009</b>	<b>Error stopping HDFS processor for event type: {0}</b>
<b>Explanation</b>	An unexpected error occurred during the shutdown of the HDFS processor
<b>EVSHSI530E0010</b>	<b>Error creating HDFS processor for event type: '{0}'</b>
<b>Explanation</b>	An internal error occurred during the creation of the HDFS processor
<b>EVSHSI530E0011</b>	<b>Unsupported encoding error converting text event to byte stream</b>
<b>Explanation</b>	The event instance was formatted in an encoding other than the default of utf-8

- EVSHSI530E0012**    **Error streaming event data to HDFS output stream**  
**Explanation**        An error occurred while writing the event data to the HDFS file system.
- EVSHSI530E0013**    **Error flushing and closing the HDFS file stream**  
**Explanation**        The HDFS I/O stream could not be flushed and closed.
- EVSHSI530E0014**    **Error closing HDFS file system reference**  
**Explanation**        The HDFS file system reference throw an unexpected exception during the close method call
- EVSHSI530E0015**    **Error creating HDFS file system reference**  
**Explanation**        An unexpected exception was thrown when closing the HDFS file system.
- EVSHSI530E0016**    **Hive table could not be found or created for event type: {0}**  
**Explanation**        The Hive table does not exist and or could not be created by the Hive metadata manager
- EVSHSI530E0017**    **Error loading Hive table data or performing auto registration for event type: {0}**  
**Explanation**        An error accessing the Hive metadata or creating the Hive metadata for the specified event type occurred.
- EVSHSI530E0018**    **Unable to create or find Hive persistence error table; defaulting to log file:%n {0}**  
**Explanation**        The Hive metadata table for the event persistence error type could not be found or created. Errors will be logged to the error log.
- EVSHSI530E0019**    **Error retrieving root schema tree element children from parser**  
**Explanation**        The child nodes of the schema element tree root could not be accessed.
- EVSHSI530E0020**    **Error parsing schema for event type: {0} in namespace {1}**  
**Explanation**        The event type definition for the given event type and namespace could not be parsed by the schema parser.

---

<b>EVSHSI530E0021</b>	<b>Generated Hive event table name exceeds 255 character size limit: {0}</b>
<b>Explanation</b>	Table names in Hive are limited to 255 characters; The unique table name generated for the event type and namespace exceeded this limit.
<b>EVSHSI530E0022</b>	<b>Error creating Hive database table field definitions</b>
<b>Explanation</b>	An expected error occurred when parsing the schema tree and creating the database table and field definitions
<b>EVSHSI530E0023</b>	<b>Error creating Hive database table structure definition</b>
<b>Explanation</b>	An unexpected error occurred when generating the Hive table structure
<b>EVSHSI530E0024</b>	<b>Error creating Hive database table definition</b>
<b>Explanation</b>	An unexpected error occurred when generating the Hive metadata table definition.
<b>EVSHSI530E0025</b>	<b>Error filtering non-mappable nodes from root schema element tree</b>
<b>Explanation</b>	There are certain binary type properties supported in events; these are filtered out of the stored event. An unexpected error occurred when trying to filter these nodes.
<b>EVSHSI530E0027</b>	<b>Ping to Apache Hive Server {0} failed.</b>
<b>Explanation</b>	Could not ping an active hive server for metadata operations
<b>EVSHSI530E0028</b>	<b>Ping to Apache Hadoop Name Node {0} failed.</b>
<b>Explanation</b>	Failed to connect to primary name node for file system access.
<b>EVSHSI530E0031</b>	<b>Error disconnecting from Apache Hive database: {0} at host: {1} port: {2} and user: {3}</b>
<b>Explanation</b>	An error occurred when disconnecting from the hive database
<b>EVSHSI530E0034</b>	<b>Error retrieving normalized type from component for event type: {0}</b>
<b>Explanation</b>	An exception was thrown by the component when generating the normalized type for the event type

<b>EVSHSI530E0035</b>	<b>An exception was thrown whilst stopping an HDFS error event writer: {0}</b>
<b>Explanation</b>	During shutdown of the HDFS error logger an exception was thrown when closing the writer for the given target and event type.
<b>EVSHSI530E0036</b>	<b>Validation of dynamic service configuration against provided values failed</b>
<b>Explanation</b>	A dynamic service configuration was provided but the variables are not present in the event.
<b>EVSHSI530E0037</b>	<b>Unexpected exception encountered during batch processing; operation will be re-tried. Exception repeated {0} times</b>
<b>Explanation</b>	An exception occurred while writing the events to the HDFS file system. The operation will be re-tried until successful.
<b>EVSHSI530E0038</b>	<b>Unexpected exception on HDFS file system close call during hard reset</b>
<b>Explanation</b>	An exception was thrown when closing the file system reference after write exception.
<b>EVSHSI530E0039</b>	<b>Error initialising internal resources for provider; operation will be re-tried. Exception repeated {0} times</b>
<b>Explanation</b>	Internal initialisation failed. The operation will be retried until successful or the component is restarted.
<b>EVSHSI530E0040</b>	<b>Error creating processor for event type {0}; operation will be re-tried; Exception repeated {1} times</b>
<b>Explanation</b>	A processor could not be created to process the specified event type. This could be due to a failure to connect to Hive for the required metadata.
<b>EVSHSI530E0041</b>	<b>Validation of dynamic service configuration failed. Event can not be persisted: Header: {0} Body: {1}</b>
<b>Explanation</b>	The values required for using a dynamic configuration were not supplied in the event being processed.
<b>EVSHSI530I0026</b>	<b>Successfully created JMX MBean for Hadoop Connectivity: {0}</b>
<b>Explanation</b>	The monitoring MBean was successfully created

---

<b>EVSHSI530I0029</b>	<b>Connected to Apache Hive database: {0} at host: {1} port: {2} and user: {3}</b>
<b>Explanation</b>	Info message on connection to hive database
<b>EVSHSI530I0030</b>	<b>Disconnected from Apache Hive database: {0} at host: {1} port: {2} and user: {3}</b>
<b>Explanation</b>	Info message on database disconnect
<b>EVSHSI530I0032</b>	<b>Connected to Apache HDFS File System specified by URI: {0}</b>
<b>Explanation</b>	Info message logged on connect to HDFS file system
<b>EVSHSI530I0033</b>	<b>Disconnected from Apache HDFS File System specified by URI: {0}</b>
<b>Explanation</b>	Info message logged on disconnect from HDFS file system
<b>EVSJCOE0000</b>	<b>An invalid column index was passed into the accessor method: {0}</b>
<b>Explanation</b>	Column indices range from 1 to n. The client has passed an index into the accessor methods that is outside this range.
<b>EVSJCOE0001</b>	<b>An invalid column label was passed into the accessor method: {0}</b>
<b>Explanation</b>	The client has passed a column label into the accessor method that does not exist in this result set.
<b>EVSJCOE0002</b>	<b>The specified feature is not supported by this driver or data source: {0}</b>
<b>Explanation</b>	The invoked method is not supported by the driver or data source. Only a subset of the JDBC API are required to be supported.
<b>EVSJCOE0003</b>	<b>Column data at index or specified label is not integral: {0}</b>
<b>Explanation</b>	A numeric column accessor method was called but the value is not a numeric.
<b>EVSJCOE0004</b>	<b>Column data at index or for specified label is not a floating point number: {0}</b>
<b>Explanation</b>	A decimal column accessor method was called but the value is not a floating point number.

<b>EVSJDRE0000</b>	<b>No driver or data source implementation found for scheme: {0}</b>
<b>Explanation</b>	The driver implementation is dynamically loaded based on the scheme in the database URL. This message indicates that there is no implementation class for the specified schema.
<b>EVSJDRE0001</b>	<b>The specified feature is not supported by this driver or data source: {0}</b>
<b>Explanation</b>	The invoked method is not supported by the driver or data source. Only a subset of the JDBC API are required to be supported.
<b>EVSJDRE0002</b>	<b>Error loading dynamic library white list from resource: {0}</b>
<b>Explanation</b>	The resource containing a white list of dynamically loaded run-time libraries could not be loaded.
<b>EVSJDRE0003</b>	<b>Error creating class loader and loading white listed run-time libraries</b>
<b>Explanation</b>	There as an error when creating the classloader and loading the classes contained in the white listed libraries.
<b>EVSJDRE0004</b>	<b>Error creating instance of the driver or data source implementation class: {0}</b>
<b>Explanation</b>	The driver implementation class could not be instantiated using the custom class loader and dynamically loaded library classes.
<b>EVSJDRE0005</b>	<b>The driver or data source installation directory is a required property but has not been set.</b>
<b>Explanation</b>	The driver dynamically loads the implementation and run-time libraries based on the database URL. For this to function correctly the location of the driver installation must be provide.
<b>EVSJDRE0006</b>	<b>The databaseURL property has not been set for this data source</b>
<b>Explanation</b>	An attempt was made to retrieve a connection from the data source without setting the database location.
<b>EVSJDRE0007</b>	<b>No parameters found in JDBC URL query string: {0}</b>
<b>Explanation</b>	The JDBC URL contains a query string marker "?" but has no parameters.
<b>Action</b>	Correct the JDBC URL and ensure that the required parameters are specified correctly.

---

<b>EVSJDRE0008</b>	<b>The specified query parameter has no associated value: {0}</b>
<b>Explanation</b>	The JDBC URL contains a query string that includes one or more parameters with no associated values.
<b>Action</b>	Correct the JDBC URL and ensure that all query parameters have valid values.
<b>EVSJEDI232E0000</b>	<b>The specified feature is not supported by this driver or data source: {0}</b>
<b>Explanation</b>	The invoked method is not supported by the driver or data source. Only a subset of the JDBC API are required to be supported.
<b>EVSJEDI232E0001</b>	<b>This connection implementation provides no wrapper interfaces</b>
<b>Explanation</b>	The connection implementation does not support the unwrap feature declared in the Wrapper interface.
<b>EVSJEDI232E0002</b>	<b>The required properties for this data source have not be set prior to creating the connection</b>
<b>Explanation</b>	Prior to creating a connection through the data source the various setter methods should be invoked to initialize the data source.
<b>EVSJEDI232E0003</b>	<b>An error occurred when creating a connection to the Elasticsearch cluster.</b>
<b>Explanation</b>	The transport client could not be created during construction of the connection.
<b>Action</b>	Check the database URL and verify that the cluster is available
<b>EVSJEDI232E0004</b>	<b>Error converting Elasticsearch mapping metadata to JSON format</b>
<b>Explanation</b>	The Elasticsearch metadata response could not be marshalled into JSON format.
<b>EVSJEDI232E0005</b>	<b>An invalid column index was passed into the accessor method: {0}</b>
<b>Explanation</b>	Column indices range from 1 to n. The client has passed an index into the accessor methods that is outside this range.
<b>EVSJEDI232E0006</b>	<b>Column data at index or specified label is not integral: {0}</b>
<b>Explanation</b>	A numeric column accessor method was called but the value is not a numeric.

- EVSJEDI232E0007** **Column data at index or for specified label is not a floating point number: {0}**  
**Explanation** A decimal column accessor method was called but the value is not a floating point number.
- EVSJEDI232E0008** **An invalid column label was passed into the accessor method: {0}**  
**Explanation** The client has passed a column label into the accessor method that does not exist in this result set.
- EVSJEDI232E0009** **Column data at index or for specified label is not a valid timestamp: {0}**  
**Explanation** A timestamp column accessor method was called but the value is not a valid timestamp
- EVSJEDI232E0010** **Column data at index or for specified label is not a valid date: {0}**  
**Explanation** A date column accessor method was called but the value is not a valid date
- EVSJEDI232E0011** **Column data at index or for specified label is not a valid time field: {0}**  
**Explanation** A time column accessor method was called but the value is not a valid time field
- EVSJEDI232E0012** **No corresponding index exists for the specified catalog: {0}**  
**Explanation** There is a one to one relationship between the SQL catalog and Elasticsearch index in the persistence framework. A method taking a catalog parameter was called but no such index exists in the Elasticsearch cluster.
- EVSJEDI232E0013** **This driver or data source only supports SQL queries**  
**Explanation** The JDBC driver for Event Persistence is provided for basic queries against non-SQL data stores.
- EVSJEDI232E0014** **The specified column name "{0}" does not exist in table; available columns are: {1}**  
**Explanation** The SQL query specified an invalid column name in the column list, where clause, order by clause, or group by clause.  
**Action** Correct the SQL query statement.

---

<b>EVSJEDI232E0015</b>	<b>Error transforming SQL query into a native Elasticsearch request%n{0}</b>
<b>Explanation</b>	The SQL query could not be turned into an Elasticsearch search request.
<b>Action</b>	Verify the syntax of the issued query and revise as needed.
<b>EVSJEDI232E0016</b>	<b>Error executing native Elasticsearch search request%n{0}</b>
<b>Explanation</b>	An error occurred while executing the native Elasticsearch search request.
<b>Action</b>	Check that the cluster is available and in good health.
<b>EVSJEDI232E0017</b>	<b>The index represented by the specified catalog does not exist: {0}</b>
<b>Explanation</b>	An SQL query was issued but there is no corresponding index on the cluster
<b>Action</b>	Check your query and the available indices on the cluster.
<b>EVSJEDI232E0018</b>	<b>The type represented by the specified table does not exist: {0}</b>
<b>Explanation</b>	An SQL query was issued but there is no corresponding type available in the index.
<b>Action</b>	Check your query and the available indices on the cluster.
<b>EVSJEDI232E0019</b>	<b>Unexpected statement type found while trying to determine the appropriate query builder implementation</b>
<b>Explanation</b>	Different builder classes are used to transform the SQL query into various Elasticsearch search requests. The implementation is selected based on the presence of aggregate functions or column list expressions. In this case, neither was found.
<b>Action</b>	Check your SQL query syntax.
<b>EVSJEDI232E0020</b>	<b>Error incrementing result cursor or accessing query result data</b>
<b>Explanation</b>	The result cursor could not be advanced to the next position.
<b>Action</b>	This can occur if the cluster goes down and the client tries to access the next batch. Check the cluster health.
<b>EVSJEDI232E0021</b>	<b>Error setting fetch direction on forward only result set.</b>
<b>Explanation</b>	This jdbc driver provides forward only result sets. A client attempted to set a fetch direction other than forward.
<b>Action</b>	Correct the client logic.

**EVSJEDI232E0022** **An error has occurred because the response reference has not been set in response handler**

**Explanation** This is a programming error in the implementation logic; the response must be set before using the handler.

**Action** Correct the programming error.

**EVSJEDI232E0023** **No matching parameter marker found for given index: {0}**

**Explanation** The client invoked a set method on the prepared statement for which there was no marker. For example, setting parameter 2 on a statement with only one marker.

**Action** Correct the program logic.

**EVSJEDI232E0024** **No corresponding value found for the marker at parameter index: {0}**

**Explanation** A parameter marker was specified in the query but no value was set prior to executing the statement.

**Action** Correct the program logic by invoking the appropriate set method on the prepared statement.

**EVSJEDI232E0025** **The position {0} declared in the order by clause does not match a valid column or alias defined in the select statements column or aggregate list**

**Explanation** The order by clause specifies an integer position that does not match a value in the select expressions column list.

**Action** Review the statement and correct the column list expression or the order by clause.

**EVSJHDI530E0000** **The specified feature is not supported by this driver or data source: {0}**

**Explanation** The invoked method is not supported by the driver or data source. Only a subset of the JDBC API are required to be supported.

**EVSJHDI530E0001** **The required properties for this data source have not be set prior to creating the connection**

**Explanation** Prior to creating a connection through the data source the various setter methods should be invoked to initialize the data source.

**EVSJQIE0000** **Unsupported format in aggregation function: {0}.**

**Explanation** Unsupported format in aggregation function.

---

<b>EVSJQIE0001</b>	<b>Unsupported date time format in string literal: {0}.</b>
<b>Explanation</b>	Data and time format is invalid.
<b>EVSJQIE0002</b>	<b>Query execution failed.</b>
<b>Explanation</b>	Query execution failed.
<b>EVSJQIE0003</b>	<b>Failed close query result.</b>
<b>Explanation</b>	Failed close query result.
<b>EVSJQIE0004</b>	<b>Failed to close query statement.</b>
<b>Explanation</b>	Failed to close query statement.
<b>EVSJQIE0005</b>	<b>Failed to close query connection.</b>
<b>Explanation</b>	Failed to close query connection.
<b>EVSJQIE0006</b>	<b>Failed to close query result.</b>
<b>Explanation</b>	Failed to close query result.
<b>EVSJQIE0007</b>	<b>Failed to format the result to JSON.</b>
<b>Explanation</b>	Failed to format the result to JSON.
<b>EVSJQIE0008</b>	<b>Unsupported feature: {0}.</b>
<b>Explanation</b>	Feature is not supported.
<b>EVSJQIE0009</b>	<b>Failed to get next query result.</b>
<b>Explanation</b>	Failed to get next query result.
<b>EVSJQIE0010</b>	<b>Full text query not supported by this implementation</b>
<b>Explanation</b>	This query implementation does provide full text search capabilities

<b>EVSJQIE0011</b>	<b>Error transforming query for explain plan</b>
<b>EVSJQIE0012</b>	<b>An unsupported encoding exception was thrown while generating explain message</b>
<b>EVSJQII0013</b>	<b>Inbound query in common syntax form:</b>
<b>EVSJQII0014</b>	<b>Outbound query in native form:</b>
<b>EVSJQPE0000</b>	<b>Test Message</b>
<b>EVSJUTE0000</b>	<b>Invalid JDBC scheme: {0}</b>
<b>Explanation</b>	Invalid JDBC scheme.
<b>EVSPAIE0000</b>	<b>Failed to execute operations: {0}</b>
<b>Explanation</b>	Failed to execute operations: {0}
<b>EVSPAIE0001</b>	<b>ParStream Admin Session has not been started.</b>
<b>Explanation</b>	ParStream Admin Session has not been started.
<b>EVSPAIE0002</b>	<b>Failed to close JDBC connection statement.</b>
<b>Explanation</b>	Failed to close JDBC connection statement.
<b>EVSPAIE0003</b>	<b>Event type {0} with Namespace {1} has already registered.</b>
<b>Explanation</b>	Event type {0} with Namespace {1} has already registered.
<b>EVSPAIE0004</b>	<b>Not supported operation: {0}.</b>
<b>Explanation</b>	Not supported operation: {0}.
<b>EVSPAIE0005</b>	<b>Not Supported Encoding {0}.</b>
<b>Explanation</b>	Not Supported Encoding {0}.

---

<b>EVSPQIE0000</b>	<b>Metadata manager error encountered during create session call</b>
<b>Explanation</b>	Metadata manager couldn't be created; possibly due to invalid event type store location
<b>EVSPQIE0001</b>	<b>Error encountered when initializing metadata manager</b>
<b>Explanation</b>	Metadata manager couldn't be created; possibly due to invalid event type store location
<b>EVSPQIE0002</b>	<b>Unsupported date time format in string literal: {0}</b>
<b>Explanation</b>	Date and time format is invalid - See java.sql.Timestamp format
<b>EVSPQIE0003</b>	<b>Unsupported syntax in aggregate function clause: {0}</b>
<b>Explanation</b>	Unsupported syntax in aggregation function clause avg, min, max, sum or count
<b>EVSPQIE0004</b>	<b>Error creating the connection to the ParStream database</b>
<b>Explanation</b>	There was an error connecting to the ParStream server(s)
<b>EVSPQIE0005</b>	<b>An open query exists for this session</b>
<b>Explanation</b>	There is already a pending or active query for this session; execute or close the query
<b>EVSPQIE0006</b>	<b>Error closing the connection to the ParStream database</b>
<b>Explanation</b>	There was an error closing the connection to the database
<b>EVSPQIE0007</b>	<b>An open result stream exists for this query</b>
<b>Explanation</b>	There is an active result stream; process the results or close the result stream
<b>EVSPQIE0008</b>	<b>There was an error executing the current query</b>
<b>Explanation</b>	This could be due to a syntax error in the query or the ParStream database may be unavailable
<b>EVSPQIE0009</b>	<b>Unexpected exception when closing the query</b>
<b>Explanation</b>	An error was encountered when closing the query session

<b>EVSPQIE0010</b>	<b>Failed to position cursor at next event in the result stream</b>
<b>Explanation</b>	There was an error when moving the cursor position forward in the stream
<b>EVSPQIE0011</b>	<b>The method {0} is unsupported in this implementation of ResultStream</b>
<b>Explanation</b>	The only requirement on a ResultStream implementation is that they provide a forward cursor via the next method
<b>EVSPQIE0012</b>	<b>Failed to format the query result into a JSON document</b>
<b>Explanation</b>	There was an error when creating the JSON result from the database query
<b>EVSPQIE0013</b>	<b>Unexpected exception encountered when closing result stream</b>
<b>Explanation</b>	There was an error closing the result stream; this could be caused by a network or database issue
<b>EVSPQIE0014</b>	<b>Full text query not supported by this implementation</b>
<b>Explanation</b>	This query implementation does provide full text search capabilities
<b>EVSQUAE0000</b>	<b>No provider registered for scheme: {0}</b>
<b>Explanation</b>	No provider registered for scheme.
<b>EVSQUAE0001</b>	<b>EventStoreUser is not set.</b>
<b>Explanation</b>	EventStoreUser is not set.
<b>EVSQUAE0002</b>	<b>Where clause contains no valid expression</b>
<b>Explanation</b>	A where clause was added to the builder that contains no expression.
<b>EVSQUAE0003</b>	<b>Group by clause contains no valid properties</b>
<b>Explanation</b>	A group by was added to the builder but contains no event properties.
<b>EVSQUAE0004</b>	<b>Order by clause contains no valid properties</b>
<b>Explanation</b>	An order by clause was added to the builder but contains no properties

---

<b>EVSSAPE0000</b>	<b>No registered storage provider factory found for store type: {0} and version: {1}</b>
<b>Explanation</b>	As EVP storage implementation bundles are initialized they register their factories with the api. This indicates that there is no registered factory for the data store type and version.
<b>EVSSAPE0001</b>	<b>Error creating storage factory instance for store type: {0} and version: {1}</b>
<b>Explanation</b>	The implementation class for the storage provider could not be instantiated.
<b>EVSSAPE0002</b>	<b>Found variable {0} but no associated value was provided in the event</b>
<b>Explanation</b>	The service has been configured with variables but no value was included in the emitted event.
<b>EVSSAPE0003</b>	<b>Dynamic Service Configuration validation failed; no values found in map for the following variables: {0}</b>
<b>Explanation</b>	A variable was defined in the service configuration but no value was found in the event header.
<b>EVSSAPE0004</b>	<b>Error compiling regular expression for variable substitution on variable: {0}</b>
<b>Explanation</b>	The regular expression for substitution of the stated variable failed.
<b>EVSUTLE0000</b>	<b>Invalid JDBC scheme: {0}</b>
<b>Explanation</b>	Invalid JDBC scheme.
<b>EVSUTLE0001</b>	<b>Invalid or unexpected Event Store URI format: {0}</b>
<b>Explanation</b>	Invalid or unexpected Event Store URI format.



# 16

## Installer Messages

---

**CommandLineArgs.missingMaxLogSize** – You changed the default maximum log size using `-maxLogSize` but did not provide the new value for new log size. Provide the new value for the maximum log size, followed by either 'k' or 'm'.

**Explanation**            You changed the default maximum log size using `-maxLogSize` but did not provide the new value for log size.

**Action**                    Provide the new value for the maximum log size, followed by either 'k' or 'm'.

**DLInitFilesProgressPanel.cannotLoadJNI** – Unable to load resource {0}. Run the installer again with a 32-bit JDK instead of a 64-bit JDK.

**Explanation**            This message is displayed when the user uses 64-bit JDK to install an older version that did not support 64-bit JDK. The 64-bit library will be missing.

**Action**                    Run the installer again with a 32-bit JDK instead of a 64-bit JDK.

**DLInitFilesProgressPanel.unsupportedPlatformInternal** – The installer has requested files for {0} but no files are available for that operating system at {1}.

**DLInitFilesProgressPanel.unsupportedPlatformProduction** – The selected product release does not support the operating system {0} on which you are trying to install.

**Explanation**            The user is trying to install on a platform that not supported on the current install machine.

**Action**                    The user should select a different product suite that does support the current platform.

**DLJarsProgressPanel.errorImagePlatformAs400** – April 2011 and later Software AG Installers do not support creation of images for IBM AS/400 systems. The installer will now exit.

**DistManInstallMain.relaunchBadJavaHome** – The JDK located at {0} is version {1}, which only supports classes up to major.minor version {2}. You must execute the installer or uninstaller with a JDK that supports classes with a major.minor of at least {3}. You can use the `-javaHome` command line option to launch the uninstaller using a different JDK. The JDK located in {4} is not working; verify that the path is correct.

**Explanation** This message is displayed when the user gave the installer or uninstaller an alternate JDK to launch the installer or uninstaller, and the path was incorrect. See 'DistManInstallMain.relaunchNoJavaHome' for more details -- {4} is the location the user gave for the JDK installation.

**Action** The user should provide a proper JDK installation directory.

**DistManInstallMain.relaunchJavaHomeSetText** – The JDK located at {0} is version {1}, which only supports classes up to major.minor version {2}. However, you must execute the installer or uninstaller with a JDK that supports classes with a major.minor of at least {3}. Please provide a JDK installation directory that meets these requirements; the JDK located at {4} does not meet these requirements or does not exist.

**Explanation** This message displayed when the user provides an alternate JDK to execute the installer or uninstaller, and the given path is too old or is not a proper directory. {0} - the JDK that is running this client {1} - the current JDK version {2} the major.minor class version that this JDK supports {3} - the required major.minor {4} - the location the user gave as an alternate JDK to run the installer or uninstaller.

**Action** Supply a proper JDK directory.

**DistManInstallMain.relaunchJavaHomeText** – The JDK located at {0} is version {1}, which only supports classes up to major.minor version {2}. However, you must execute the installer or uninstaller with a JDK that supports classes with a major.minor of at least {3}. Download a JDK that meets these requirements. See the Using the Software AG Installer guide for details and instructions.

**Explanation** If the user tries to launch the installer or uninstaller with a JDK that is too old, this message will be shown. The user will be queried to supply an alternate location for a more recent JDK. {0} - location of the current JDK executing the installer or uninstaller {1} -- version of the current JDK {2} major.minor class version the current version of JDK supports, {3} -- the minimum that is required to execute the client classes.

**Action** Enter the newer JDK installation directory and the installer or uninstall will execute themselves again using that JDK.

---

**DistManInstallMain.relaunchNoJavaHome** – The JDK located at {0} is version {1}, which only supports classes up to major.minor version {2}. You must execute the installer or uninstaller with a JDK that supports classes with a major.minor of at least {3}. You can use the `-javaHome` command line option to launch the uninstaller using a different JDK.

**Explanation** This message is displayed when the user tries to execute the installer or uninstaller with a JDK version that is too old. This can happen, for example, if the user installs webMethods 6 (which includes JDK 1.3 or 1.3.1) and tries to run the uninstaller. The message parameters are {0} - Installation home directory for java, {2} major.minor version of the java the user used to run the installer or uninstaller {3} - the major.minor version that is required as an absolute minimum.

**Action** As long as the user is not using console mode and running the installer, the user can point the installer or uninstaller at a newer JDK installation; the installer or uninstaller will launch again using that JDK.

**InstallDirWizardPanel.cannotFindRegistryKeys** – The Software AG Uninstaller cannot find the proper registry keys for this installation and cannot continue.

**LockedFilesWizardPanel.explainText** – The installer has detected running processes that must be stopped before you can continue. First shut down the listed products; this might also automatically shut down other listed processes. Shut down products by stopping services or exiting applications. Do not use Task Manager. If you need shutdown instructions, see the product documentation.

**SAGEnvironmentManagerUnix.configFileNotReadable** – The installation user has no permissions to read the config file "{0}"! Change the permissions and try again or exit the current installation.

**Explanation** The message that pops up when the current installation user has no read permission for the config file '/etc/sagconf.xml' on Unix systems.

**ZipManager.errorLockedFile** – The process cannot access the file because another process has locked a portion of the file.



# 17

## Integration Server Messages

---

<b>0701.002E</b>	<b>Mobile application "{0}" version {1} is already registered.</b>
<b>Explanation</b>	A mobile application with this name and version already exists.
<b>Action</b>	Provide a different application name or version.
<b>0701.003E</b>	<b>Upload service "{0}" is not available.</b>
<b>Explanation</b>	The upload service supplied during mobile sync component creation does not exist in the specified namespace.
<b>Action</b>	Make sure the service exists within the specified namespace and that the namespace and service name are typed correctly.
<b>0701.004E</b>	<b>Download service "{0}" is not available.</b>
<b>Explanation</b>	The download service supplied during mobile sync component creation does not exist in the specified namespace.
<b>Action</b>	Make sure the service exists within the specified namespace and that the namespace and service name are typed correctly.
<b>0701.005E</b>	<b>Document type "{0}" is not available.</b>
<b>Explanation</b>	The business doc type supplied during mobile sync component creation does not exist in the specified namespace.
<b>Action</b>	Make sure the document type exists within the specified namespace and that the namespace and document type are typed correctly.

<b>0701.006E</b>	<b>Mobile sync component "{0}" is suspended and cannot be changed.</b>
<b>Explanation</b>	An attempt was made to edit the mobile sync component, but changes cannot be made to a mobile sync component when the component is suspended.
<b>Action</b>	Disable the mobile sync component and try to edit the component again.
<b>0701.007E</b>	<b>Mobile sync component "{0}" is associated with mobile application "{1}" version {2}. Remove association before deleting mobile sync component.</b>
<b>Explanation</b>	An attempt was made to delete a mobile sync component that is associated with a mobile application.
<b>Action</b>	Remove the association between the mobile sync component and the mobile application. In the Integration Server Administrator, navigate to the Solutions > Mobile Support > Mobile Apps screen, click the name of the application to edit its associations, and deselect the mobile sync component from the Mobile Sync Component Alias list. Then, try deleting the mobile sync component again.
<b>0701.008E</b>	<b>Error: {0}</b>
<b>Explanation</b>	Mobile Support encountered an error while validating the namespaces for the download service, upload service, or business doc type supplied during creation of a mobile sync component.
<b>Action</b>	Make sure that the service or doc type exists within the specified namespace and that the entry is typed correctly.
<b>0701.009E</b>	<b>Mobile application "{0}" version {1} was not found.</b>
<b>Explanation</b>	Mobile Support could not find the specified mobile application and version while retrieving, updating, or deleting the mobile application or processing a synchronization request.
<b>Action</b>	Specify a valid mobile application and version.
<b>0701.012E</b>	<b>Mobile sync component "{0}" could not be suspended. Error: {1}</b>
<b>Explanation</b>	Mobile Support could not suspend the mobile sync component for the reason indicated.
<b>Action</b>	Check the reason detailed in the message and take appropriate corrective action.
<b>0701.014E</b>	<b>Conflict resolution rule is not valid.</b>
<b>Explanation</b>	The conflict resolution rule specified during mobile sync component creation is not valid.
<b>Action</b>	Specify a conflict resolution rule of either "Client wins" or "Server wins".

---

<b>0701.015E</b>	<b>Mobile sync component "{0}" already exists.</b>
<b>Explanation</b>	Mobile Support could not create the mobile sync component because the specified alias already exists.
<b>Action</b>	Specify a different alias for the mobile sync component.
<b>0701.016E</b>	<b>Mobile sync component "{0}" was not found.</b>
<b>Explanation</b>	Mobile Support could not find the specified mobile sync component while retrieving, updating, enabling or disabling, or deleting the mobile sync component or associating a mobile application with the component.
<b>Action</b>	Specify the alias of an existing mobile sync component.
<b>0701.022E</b>	<b>Mobile sync component "{0}" could not be created. Error: {1}</b>
<b>Explanation</b>	Mobile Support could not create the mobile sync component for the reason indicated.
<b>Action</b>	Check the reason detailed in the message and take appropriate corrective action.
<b>0701.023E</b>	<b>Mobile sync component "{0}" could not be deleted. Error: {1}</b>
<b>Explanation</b>	Mobile Support could not delete the mobile sync component for the reason indicated.
<b>Action</b>	Check the reason detailed in the message and take appropriate corrective action.
<b>0701.024E</b>	<b>Mobile sync component "{0}" could not be updated. Error: {1}</b>
<b>Explanation</b>	Mobile Support could not update the mobile sync component for the reason indicated.
<b>Action</b>	Check the reason detailed in the message and take appropriate corrective action.
<b>0701.025E</b>	<b>Mobile sync component "{0}" could not be enabled. Error: {1}</b>
<b>Explanation</b>	Mobile Support could not enable the mobile sync component for the reason indicated.
<b>Action</b>	Check the reason detailed in the message and take appropriate corrective action.
<b>0701.026E</b>	<b>Mobile sync component "{0}" could not be disabled. Error: {1}</b>
<b>Explanation</b>	Mobile Support could not disable the mobile sync component for the reason indicated.
<b>Action</b>	Check the reason detailed in the message and take appropriate corrective action.

<b>0701.027E</b>	<b>Mobile sync components could not be retrieved.</b>
<b>Explanation</b>	Mobile Support could not retrieve the list of mobile sync components.
<b>Action</b>	Check the server log for details about this error.
<b>0701.028E</b>	<b>Mobile sync component "{0}" could not be retrieved. Error: {1}</b>
<b>Explanation</b>	Mobile Support could not retrieve the mobile sync component for the reason indicated.
<b>Action</b>	Check the reason detailed in the message and take appropriate corrective action.
<b>0701.029E</b>	<b>Mobile sync component "{0}" could not be deleted or edited.</b>
<b>Explanation</b>	The mobile sync component cannot be deleted or edited because the component is still enabled.
<b>Action</b>	Disable the mobile sync component and try to edit or delete the component again.
<b>0701.030E</b>	<b>Upload service "{0}" is not implementing the "{1}" specification.</b>
<b>Explanation</b>	The upload service provided during mobile sync component creation is not implementing the Mobile Support upload specification.
<b>Action</b>	Edit the upload service to include a reference to the <code>wm.mobile.datasync.specs:uploadSpec</code> specification.
<b>0701.031E</b>	<b>Download service "{0}" is not implementing the "{1}" specification.</b>
<b>Explanation</b>	The download service provided during mobile sync component creation is not implementing the Mobile Support download specification.
<b>Action</b>	Edit the download service to include a reference to the <code>wm.mobile.datasync.specs:downloadSpec</code> specification.
<b>0701.032E</b>	<b>"{0}" is not a valid Integration Server service node.</b>
<b>Explanation</b>	The download or upload service specified during mobile sync component creation is not a valid Integration Server service node.
<b>Action</b>	Ensure that element specified for the download or upload service is an Integration Server flow service (that is, a node type of <code>NSService</code> ) and not another type of element.
<b>0701.033E</b>	<b>Mobile sync component state "{0}" is not valid.</b>
<b>Explanation</b>	Mobile Support detected that an external attempt was made to invoke a mobile sync component that is in a state other than "enabled," "disabled," or "suspended." As a result, Mobile Support has rejected the request to invoke the mobile sync component.
<b>Action</b>	No action is necessary.

---

<b>0701.034E</b>	<b>Mobile application "{0}" version {1} could not be created. Error: {2}</b>
<b>Explanation</b>	Mobile Support encountered an error while associating the mobile application with a mobile sync component.
<b>Action</b>	Check the reason detailed in the message and take appropriate corrective action.
<b>0701.035E</b>	<b>Mobile application "{0}" version {1} could not be updated. Error: {2}</b>
<b>Explanation</b>	Mobile Support encountered an error while updating the mobile application.
<b>Action</b>	Check the reason detailed in the message and take appropriate corrective action.
<b>0701.036E</b>	<b>Mobile application "{0}" version {1} could not be retrieved. Error: {2}</b>
<b>Explanation</b>	Mobile Support encountered an error while retrieving details about the association between the mobile application and a mobile sync component.
<b>Action</b>	Check the reason detailed in the message and take appropriate corrective action.
<b>0701.037E</b>	<b>Mobile applications could not be retrieved. Error: {0}</b>
<b>Explanation</b>	Mobile Support encountered an error while retrieving details about the associations between mobile applications and mobile sync components.
<b>Action</b>	Check the server log for details and take appropriate corrective action.
<b>0701.038E</b>	<b>Mobile application "{0}" version {1} could not be removed. Error: {2}</b>
<b>Explanation</b>	Mobile Support encountered an error while removing the association between the mobile application and a mobile sync component.
<b>Action</b>	Check the reason detailed in the message and take appropriate corrective action.
<b>0701.041E</b>	<b>Row identifier "{0}" is not present in business doc type "{1}".</b>
<b>Explanation</b>	The business doc type does not contain the specified row identifier.
<b>Action</b>	When specifying row identifiers during mobile sync component creation, be sure the row identifiers are present in the specified business doc type.
<b>0701.042E</b>	<b>Row identifier "{0}" must be a string or an object.</b>
<b>Explanation</b>	A row identifier was provided that is not a string or an object.
<b>Action</b>	When specifying row identifiers during mobile sync component creation, be sure the row identifiers are strings or objects.

<b>0701.043E</b>	<b>"{0}" is not a document type node.</b>
<b>Explanation</b>	A business doc type was provided that is not of type NSRecord.
<b>Action</b>	When specifying a business doc type during mobile sync component creation, be sure the business doc type is of type NSRecord.
<b>0701.044E</b>	<b>Mobile application "{0}" version {1} is not associated with the mobile sync component "{2}".</b>
<b>Explanation</b>	Mobile Support could not complete the synchronization operation because the mobile application is not associated with the specified mobile sync component.
<b>Action</b>	In Integration Server Administrator, go to the Mobile Support > Mobile App page and associate the mobile application with the specified mobile sync component.
<b>0701.045E</b>	<b>Mobile sync component "{0}" could not be suspended. Only enabled mobile sync components can be suspended.</b>
<b>Explanation</b>	An attempt was made to suspend the mobile sync component, but the attempt failed because the mobile sync component was not enabled.
<b>Action</b>	Ensure that the mobile sync component is enabled before attempting to suspend it.
<b>0701.046E</b>	<b>Requested mobile sync component "{0}" is not enabled.</b>
<b>Explanation</b>	Mobile Support could not process the synchronization request because the specified mobile sync component is not enabled.
<b>Action</b>	In Integration Server Administrator, go to the Mobile Support > Mobile Sync Components page and enable the mobile sync component. Then, resubmit the synchronization request.
<b>0701.047E</b>	<b>No mobile sync component was specified.</b>
<b>Explanation</b>	Mobile Support could not process the synchronization request because no mobile sync component was specified.
<b>Action</b>	Ensure that the synchronization request includes a mobile sync component alias and a mobile application name and version.
<b>0701.048E</b>	<b>Mobile sync component "{0}" cannot be suspended because it was configured to not store business data in the sync store.</b>
<b>Explanation</b>	Mobile Support could not suspend the specified mobile sync component because the Store Business Data check box was not selected in Integration Server Administrator when the mobile sync component was configured. When business objects are not stored in the sync store, mobile sync components can be disabled but not suspended.
<b>Action</b>	In Integration Server Administrator, on the Solutions > Mobile Support > Mobile Sync Components screen, disable the mobile sync component.

---

<b>0701.049E</b>	<b>Mobile sync component "{0}" cannot be refreshed because it was configured to not store business data in the sync store.</b>
<b>Explanation</b>	Mobile Support could not refresh the specified mobile sync component because the Store Business Data check box was not selected when the mobile sync component was configured. When business objects are not stored in the sync store, mobile sync components cannot be refreshed.
<b>Action</b>	In Integration Server Administrator, on the Solutions > Mobile Support > Mobile Sync Components > Edit Mobile Sync Component screen, select the Store Business Data check box. Then, disable and enable the mobile sync component.
<b>0701.057E</b>	<b>Error occurred while processing record "{0}".</b>
<b>Explanation</b>	Mobile Support encountered an error while processing the specified record.
<b>Action</b>	Check the server log for details and take appropriate corrective action.
<b>0701.068E</b>	<b>"{0}" is not locked by thread "{1}".</b>
<b>Explanation</b>	The thread attempted to unlock the specified record, but the record is not owned by the thread.
<b>Action</b>	Try the request again. If the issue recurs, contact Software AG Global Support.
<b>0701.069E</b>	<b>Thread "{0}" could not unlock record "{1}" because record is already unlocked.</b>
<b>Explanation</b>	The thread attempted to unlock the specified record, but the record was not locked.
<b>Action</b>	Try the request again. If the issue recurs, contact Software AG Global Support.
<b>0701.080E</b>	<b>Could not refresh mobile sync component "{0}". Mobile sync component is in "{1}" state.</b>
<b>Explanation</b>	Mobile Support could not refresh the mobile sync component because the component is not suspended.
<b>Action</b>	Suspend the mobile sync component.
<b>0701.093E</b>	<b>Error occurred while initializing sync store.</b>
<b>Explanation</b>	Mobile Support experienced an error while initializing the sync store.
<b>Action</b>	Check the server log for details and take appropriate corrective action.

<b>0701.095E</b>	<b>Validation Error occurred: {0}.</b>
<b>Explanation</b>	Mobile Support could not process the data row because the data that was submitted was not valid.
<b>Action</b>	Correct the validation error.
<b>0701.096E</b>	<b>Message "{0}" skipped. Unique ID is missing.</b>
<b>Explanation</b>	Mobile Support could not process the data row because the data does not contain row identifier(s).
<b>Action</b>	Supply one or more row identifiers.
<b>0701.097E</b>	<b>Unable to synchronize the mobile device. Exception: {0}</b>
<b>Explanation</b>	Mobile Support could not synchronize the mobile device for the reason specified.
<b>Action</b>	Check the server log for details and take appropriate corrective action.
<b>0701.112E</b>	<b>Unable to save the record associated with unique ID and mobile sync component of "{0}". Exception: {1}</b>
<b>Explanation</b>	Mobile Support could not save the record for the reason indicated.
<b>Action</b>	Check the reason detailed in the message and take appropriate corrective action.
<b>0701.113E</b>	<b>Unable to save record data. Exception: {0}</b>
<b>Explanation</b>	Mobile Support could not save the record data for the reason indicated.
<b>Action</b>	Check the reason detailed in the message and take appropriate corrective action.
<b>0701.114E</b>	<b>Unable to write record data. Exception: {0}</b>
<b>Explanation</b>	Mobile Support could not write the record data for the reason indicated.
<b>Action</b>	Check the reason detailed in the message and take appropriate corrective action.
<b>0701.117E</b>	<b>Unable to delete record associated with unique ID "{0}" and mobile sync component "{1}". Reason: {2}</b>
<b>Explanation</b>	Mobile Support could not delete the record for the reason indicated.
<b>Action</b>	Check the reason detailed in the message and take appropriate corrective action.

<b>0701.118E</b>	<b>Unable to delete record associated with mobile sync component "{0}". Reason: {1}</b>
<b>Explanation</b>	Mobile Support could not delete the record for the reason indicated.
<b>Action</b>	Check the reason detailed in the message and take appropriate corrective action.
<b>0701.119E</b>	<b>Unable to get records from sync store. Reason: {0}</b>
<b>Explanation</b>	Mobile Support could not retrieve records from the sync store for the reason indicated.
<b>Action</b>	Check the reason detailed in the message and take appropriate corrective action.
<b>0701.121E</b>	<b>Unable to obtain connection from connection pool. Exception: {0}</b>
<b>Explanation</b>	Mobile Support could not obtain a connection from the connection pool for the reason indicated.
<b>Action</b>	In Integration Server Administrator, on the Settings > JDBC Pools screen, select the pool alias associated with the MobileSupport functional alias. On the Connection Aliases > Edit screen, increase the number of maximum connections.
<b>0701.122E</b>	<b>Unable to obtain database connection from connection pool for sync store.</b>
<b>Explanation</b>	Mobile Support could not obtain a connection to the database configured for the sync store.
<b>Action</b>	In Integration Server Administrator, on the Settings > JDBC Pools screen, test the connection from the MobileSupport functional alias to the database. Take appropriate corrective action to resolve any errors.
<b>0901.001E</b>	<b>Name cannot be null or empty.</b>
<b>Explanation</b>	While creating or updating an OData element, Name cannot be null or empty.
<b>Action</b>	Provide a valid Name for the OData element.
<b>0901.002E</b>	<b>The specified name is invalid. Ensure that the name does not exceed 480 characters, does not start with a number or "_" symbol, and that it contains no special characters other than "_".</b>
<b>Explanation</b>	Specified name is invalid because name can contain only alphanumeric characters and "\"_\" symbol. Name must start with an alphabet and not with a number or "\"_\" symbol.
<b>Action</b>	Provide a valid name that starts with an alphabet and contains only alphanumeric characters and "\"_\" symbol. For information about other supported unicode characters, see SimpleIdentifier in Common Schema Definition Language (CSDL) documentation.

<b>0901.003E</b>	<b>Length of the Name cannot exceed 480 characters.</b>
<b>Explanation</b>	The Name specified contains more than 480 characters.
<b>Action</b>	Ensure that the length of the Name does not exceed 480 characters.
<b>0901.004E</b>	<b>Cannot rename Complex Type name to "{0}". Complex Type name must be unique.</b>
<b>Explanation</b>	The Complex Type name could not be renamed because a Complex Type with the same name already exists.
<b>Action</b>	Enter a unique Name for the Complex Type.
<b>0901.005E</b>	<b>Cannot rename Entity Type name to "{0}". Entity Type name must be unique.</b>
<b>Explanation</b>	The Entity Type name could not be renamed because an Entity Type with the same name already exists.
<b>Action</b>	Enter a unique Name for the Entity Type.
<b>0901.006E</b>	<b>Cannot rename Property name to "{0}". Property name must be unique.</b>
<b>Explanation</b>	The Property name could not be renamed because a Property with the same name already exists.
<b>Action</b>	Enter a unique Name for the Complex Type.
<b>0901.007E</b>	<b>Cannot delete Complex Type because it is referred to by "{0}".</b>
<b>Explanation</b>	The Complex Type cannot be deleted because it is referred to by a Complex property.
<b>Action</b>	Ensure that all references to the Complex Type are removed before deleting it.
<b>0901.008E</b>	<b>A Property with the same name already exists in the Entity Type.</b>
<b>Explanation</b>	The new Property with the specified name cannot be added because another Property with the same name already exists in the Entity Type.
<b>Action</b>	Enter a unique Name for the new Property that you want to add.
<b>0901.009E</b>	<b>A Property with the same name already exists in the Complex Type.</b>
<b>Explanation</b>	The new Property with the specified name cannot be added because another Property with the same name already exists in the Complex Type.
<b>Action</b>	Enter a unique Name for the new Property that you want to add.

---

<b>0901.010E</b>	<b>An Entity Type with the same name already exists in the OData Service.</b>
<b>Explanation</b>	The new Entity Type cannot be created with the specified name because another Entity Type with the same name already exists in the OData Service.
<b>Action</b>	Enter a unique Name for the Entity Type that you want to add.
<b>0901.011E</b>	<b>A Complex Type with the same name already exists in the OData Service</b>
<b>Explanation</b>	The new Complex Type cannot be added with the specified name because another Complex Type with the same name already exists in the OData Service.
<b>Action</b>	Enter a unique Name for the Complex Type that you want to add.
<b>0901.012E</b>	<b>An Association with the same name already exists in the OData Service.</b>
<b>Explanation</b>	A new Association with the specified name cannot be created because another Association with the same name already exists in the OData Service.
<b>Action</b>	Enter a unique name for the Association that you want to add.
<b>0901.013E</b>	<b>Invalid index position "{0}"; Unable to move the OData element.</b>
<b>Explanation</b>	Unable to move the OData element to an invalid index position.
<b>Action</b>	Ensure that the element is moved to an index position within the same container.
<b>0901.014E</b>	<b>Invalid property. Property "{0}" does not exist and hence, cannot be moved.</b>
<b>Explanation</b>	The specified Property cannot be moved because it does not exist.
<b>Action</b>	Ensure that the Property you want to move is already added to the OData service.
<b>0901.015E</b>	<b>Cannot delete Entity Type because it is referred to by one of the Associations.</b>
<b>Explanation</b>	The Entity type cannot be deleted because it is referred to by one of the Associations.
<b>Action</b>	Ensure that all references to the Entity Type is removed before deleting it.
<b>0901.016E</b>	<b>Facet "{0}" is not applicable for Type "{1}"</b>
<b>Explanation</b>	The specified Facets property is not applicable for the selected Type.
<b>Action</b>	Ensure that only those Facets that apply to the selected Type are specified.

<b>1000.0042E</b>	<b>Error in parsing EDM simple type "{0}" while evaluating the filter query.</b>
<b>Explanation</b>	Error in parsing the literal value of the filter expression because the literal value is incorrect.
<b>Action</b>	Ensure that the correct literal value is given in the filter expression.
<b>1000.0043E</b>	<b>Error in parsing property "{0}" in the Entity Data Model (EDM) while evaluating the filter query.</b>
<b>Explanation</b>	Error in parsing the property value of the filter expression.
<b>Action</b>	Ensure that the correct property value is given in the Entity Data Model (EDM).
<b>1000.0044E</b>	<b>Error in evaluating the filter expression "{0}".</b>
<b>Explanation</b>	The syntax of the filter expression is incorrect.
<b>Action</b>	Ensure that the syntax of the filter expression is correct.
<b>1000.0047E</b>	<b>Internal server error for request "{0}" due to "{1}"</b>
<b>Explanation</b>	Validation error from Olingo.
<b>Action</b>	Refer to the error message text for more details and correct the URL specified.
<b>1000.0048E</b>	<b>OData request "{0}" failed with error code "{1}" reason "{2}"</b>
<b>Explanation</b>	Validation error from Olingo.
<b>Action</b>	Refer to the error message text for more details and correct the URL specified.
<b>1000.0049E</b>	<b>Entity type "{0}" not found in the entity data model.</b>
<b>Explanation</b>	The entity type specified in the OData request is incorrect, deleted, or not available in the entity type model.
<b>Action</b>	Ensure that the entity type that you specified exists in the entity data model.
<b>1000.0050E</b>	<b>Odata data request failed with the error "{0}"</b>
<b>Explanation</b>	Error in the OData handler because the request is malformed.
<b>Action</b>	See the information provided in the error message and correct the request URL.

---

<b>1000.0052E</b>	<b>Error in retrieving NSOdata service node from OData Context.</b>
<b>Explanation</b>	The OData service node in the OData context is null.
<b>Action</b>	Ensure that the path to the OData service node specified in the request URL is correct.
<b>12.31</b>	<b>Invalid SAML assertion. The trust/signature validation failed with exception: {0}</b>
<b>Explanation</b>	Integration Server received a SAML assertion that either failed during signature validation or it did not come from a trusted issuer.
<b>Action</b>	Review the request and work with the sender to correct the issues.
<b>12.45</b>	<b>Error in getting security token form SAML assertion. SAML Assertion is: {0}</b>
<b>12.46</b>	<b>No user mapped to this X509 certificate.</b>
<b>12.47</b>	<b>No X509 certificate chain found.</b>
<b>12.48</b>	<b>No PAM authentication module.</b>
<b>12.49</b>	<b>No PAM user found.</b>
<b>12.50</b>	<b>Basic authentication, no user found.</b>
<b>12.51</b>	<b>Digest authentication, no user found.</b>
<b>12.52</b>	<b>Default authentication, no user found.</b>
<b>12.53</b>	<b>Request {0} for subject {1} was rejected.</b>
<b>12.54</b>	<b>Using account {0} for {1} subject {2}.</b>

- 12.55            **Error initializing OpenID Provider: {0}: {1}**
  
- 12.56            **Error initializing OpenID Providers**
  
- 12.57            **Requesting delegatable kerberos token for user: {0}**
  
- 12.58            **Server logged in as user : {0} into KDC**
  
- 12.59            **Kerberos delegated credentials set for user: {0}**
  
- 12.60            **Found kerberos delegated credentials for user: {0} . Placed in Context**
  
- 12.61            **Logged in as {0} . Using delegated kerberos credentials of {1} to request for service principal**
  
- 12.62            **Obtained delegated kerberos token for user : {0}**
  
- 12.63            **Kerberos ticket is set in the HTTP header: {0}**
  
- 12.64            **Kerberos delegated credentials set for : {0}**
  
- 12.65            **Unable to initialize the set of external OAuth Authorization Servers**
  
- 12.9999...0    **{0}**
  
- 13.10            **Unable to register multipart coder {0} for service {1}. A coder is already registered with that service name.**
  
- 13.11            **Unable to deregister multipart coder for service {0}. There is no coder registered with that service name.**

---

13.5	Deregistering multipart content handler for service {0}.
13.6	Registering multipart coder {0} for service {1}.
13.7	Deregistering multipart coder for service {0}.
13.8	Unable to register multipart content handler {0} for service {1}. A content handler is already registered with that service name.
13.9	Unable to deregister multipart content handler for service {0}. There is no content handler registered with that service name.
14.59	OutboundPasswordManager could not find package: {2}
14.60	Master password updated for package: {0}
14.61	Package {2} is not enabled.
14.62	Package name cannot be null.
14.63	The value specified for the <code>watt.server.xml.encoding</code> parameter is not supported by your JVM. Integration Server might not be able to process the XML files.
147.4	Error while executing command {0}: {1}
149.25W	<b>Possible SQL injection threat for {0} database</b>
<b>Explanation</b>	Incoming request to Enterprise Gateway Server contains suspicious data (payload), which could possibly cause an SQL injection attack.
<b>Action</b>	Contact the Integration Server system administrator to inspect and validate the incoming request to avert an SQL injection attack.

<b>149.26W</b>	<b>Possible SQL injection threat detected with the incoming payload.</b>
<b>Explanation</b>	Incoming request to Enterprise Gateway Server contains suspicious payload, which could possibly cause an SQL injection attack.
<b>Action</b>	Contact the Integration Server system administrator to inspect and validate the incoming request to avert an SQL injection attack.
<b>154.1</b>	{0}
<b>155.9998</b>	Exception --> {0}
<b>163.1</b>	<b>JWT Token is not present. Send a Bearer token along with the request.</b>
<b>163.2</b>	<b>Unable to find user corresponding to the JWT Bearer token.</b>
<b>163.3</b>	<b>Verifying with truststore alias "{0}" and certificate alias "{1}".</b>
<b>163.4</b>	<b>Verified claim : "{0}".</b>
<b>163.5</b>	<b>User "{0}" found in the JWT Bearer token.</b>
<b>163.9999</b>	Exception --> {0}
<b>21.1001E</b>	<b>The on-premise service signature cannot be null or empty.</b>
<b>Explanation</b>	While creating an Integration Cloud connector service, the service signature cannot be null or empty.
<b>Action</b>	Ensure that service signature is not null or empty while invoking the service to generate an Integration Cloud connector.
<b>21.1002E</b>	<b>Package name cannot be null or empty.</b>
<b>Explanation</b>	While creating an Integration Live connector service, the package name cannot be null or empty.
<b>Action</b>	Ensure that you specify the package name while invoking the service to generate an Integration Live connector.

---

<b>21.1003E</b>	<b>The on-premise service name cannot be null or empty.</b>
<b>Explanation</b>	While creating an Integration Live connector service, the on-premise service name cannot be null or empty.
<b>Action</b>	Ensure that you specify an on-premise service name while invoking the service to generate an Integration Live connector.
<b>21.1004E</b>	<b>Connector service name cannot be null or empty.</b>
<b>Explanation</b>	While creating an Integration Live connector service, the connector service name cannot be null or empty.
<b>Action</b>	Ensure that the connector service name is not null or empty while invoking the service to generate an Integration Live connector.
<b>21.1005E</b>	<b>An error occurred while creating the webMethods Cloud connector service. Details: {0}</b>
<b>Explanation</b>	Unknown error occurred while creating the Integration Live connector service.
<b>Action</b>	Contact Software AG global support.
<b>21.1006E</b>	<b>Interface name cannot be null or empty.</b>
<b>Explanation</b>	While creating the Application folder structure, the Interface name cannot be null or empty.
<b>Action</b>	Ensure that you specify the Interface name while invoking the service to create the Application folder structure.
<b>21.1007E</b>	<b>Application name cannot be null or empty.</b>
<b>Explanation</b>	While creating the Application folder structure, the Application name cannot be null or empty.
<b>Action</b>	Ensure that you specify the application name while invoking the service to create the Application folder structure.
<b>21.1008E</b>	<b>An error occurred while creating the application interface. Details: {0}</b>
<b>Explanation</b>	Unknown error occurred while creating the application interface.
<b>Action</b>	Contact Software AG global support.

<b>21.2001E</b>	<b>An error occurred while connecting to the Universal Messaging Realm. Error: {0}</b>
<b>Explanation</b>	Integration Server encountered the specified error while connecting to the Universal Messaging Realm.
<b>Action</b>	Ensure that the Realm URL and that the port identified in the URL is active on the Universal Messaging Server. In addition, take the appropriate action based on the details shown in the message.
<b>21.2002E</b>	<b>User {0} is not authorized to perform administrative functions on the Universal Messaging Realm.</b>
<b>Explanation</b>	The specified user does not have the rights required to perform administrative functions.
<b>Action</b>	Log on with a user name that has the proper permissions to perform administrative functions.
<b>21.3E</b>	<b>No Git credentials were found for tenant {0} (user {1}). Cannot access the remote Git repository.</b>
<b>Explanation</b>	Integration Server is not provisioned with Git credentials for the tenant.
<b>Action</b>	Contact the system administrator.
<b>21.4E</b>	<b>Tenant {0} has no credentials. Cannot fetch tenant's package from repository.</b>
<b>Explanation</b>	Integration Server is not provisioned with GIT credentials for the tenant.
<b>Action</b>	Contact the system administrator.
<b>21.5E</b>	<b>The local Git repository does not exist for package {0}.</b>
<b>Explanation</b>	The specified package is not associated with a local Git repository.
<b>Action</b>	Contact the system administrator.
<b>21.6002E</b>	<b>Settings could not be saved because of the following error: {0}</b>
<b>Explanation</b>	The settings could not be saved because of the specified error.
<b>Action</b>	Take the appropriate action based on the details shown in the message.
<b>21.6003E</b>	<b>The following error occurred while saving settings: {0}. See the error log for the full stack trace.</b>
<b>Explanation</b>	Integration Server encountered the specified error while saving the settings.
<b>Action</b>	Review the server log for details and take appropriate corrective action.

---

<b>21.6004E</b>	<b>An error occurred while loading information from the webMethods Cloud environment.</b>
<b>Explanation</b>	Integration Server encountered an error while loading information from the webMethods Cloud environment.
<b>Action</b>	Review the server log for details and take appropriate corrective action.
<b>21.6005E</b>	<b>webMethods Cloud information was not loaded because the settings are not specified.</b>
<b>Explanation</b>	You must specify the settings on the Settings page to load webMethods Cloud information.
<b>Action</b>	Specify the settings on the Settings page.
<b>21.7E</b>	<b>An exception occurred during the Git operation for package {0}: {1}</b>
<b>Explanation</b>	Integration Server encountered the specified error during the Git operation.
<b>Action</b>	Contact the system administrator.
<b>21.7003E</b>	<b>Could not save application {0}. A service with Display Name {1} already exists</b>
<b>Explanation</b>	A service with the specified display name already exists within the application. The display name of each service in the application must be unique.
<b>Action</b>	Specify a unique display name for the service.
<b>21.7004E</b>	<b>Could not save application {0} because there are no services selected.</b>
<b>Explanation</b>	There are no services specified for the application. You must specify at least one service for an application to be valid.
<b>Action</b>	Specify one or more services for the application.
<b>21.7007E</b>	<b>The following error occurred while saving application {0}: {1}. See the error log for the full stack trace.</b>
<b>Explanation</b>	Integration Server encountered the specified error while saving the application.
<b>Action</b>	Review the error log and correct the error.
<b>21.7008E</b>	<b>The following error occurred while deleting application {0}: {1} See the error log for the full stack trace.</b>
<b>Explanation</b>	Integration Server encountered the specified error while deleting the application.
<b>Action</b>	Review the error log and correct the error.

<b>21.7009E</b>	<b>The application named {0} does not exist.</b>
<b>Explanation</b>	The application's name contains too many characters.
<b>Action</b>	Rename the application using no more than 32 characters.
<b>21.7009...0E</b>	<b>The application named {0} does not exist.</b>
<b>Explanation</b>	The application does not exist. It might have been deleted by another user.
<b>Action</b>	Retry the action. If the issue persists, contact your system administrator.
<b>21.7010E</b>	<b>An application named {0} already exists.</b>
<b>Explanation</b>	The application is not valid because another application with the specified name already exists.
<b>Action</b>	Specify a unique application name.
<b>21.7011E</b>	<b>Could not save application {0} because the Display Name field for one or more of the services is empty.</b>
<b>Explanation</b>	The Display Name field is not specified for one or more services selected for the application.
<b>Action</b>	Specify a valid Display Name for each service in the application.
<b>21.7012E</b>	<b>Application {0} could not be saved because the Name contains: {1}.</b>
<b>Explanation</b>	The application's name contains the specified illegal character, leading digit, or reserved word.
<b>Action</b>	Rename the application.
<b>21.7013E</b>	<b>Application {0} could not be saved because the service Display Name {1} contains: {2}</b>
<b>Explanation</b>	The Display Name field of a service in the application contains the specified illegal character, value, or reserved word.
<b>Action</b>	Remove the specified character, value, or word from the Display Name.
<b>21.7014E</b>	<b>The following error occurred while uploading application {0}: {1}. See the error log for the full stack trace.</b>
<b>Explanation</b>	The specified error occurred while uploading the application.
<b>Action</b>	Review the error log and correct the error.

---

<b>21.7016E</b>	<b>Application {0} could not be uploaded because of the following error: {1}</b>
<b>Explanation</b>	Integration Server encountered the specified error while uploading the application.
<b>Action</b>	Check the server log for details and take appropriate corrective action.
<b>21.7020E</b>	<b>Applications require that at least one account be selected before they can be uploaded.</b>
<b>Explanation</b>	Applications require that at least one connection be selected before it can be uploaded.
<b>Action</b>	Select a connection for the application.
<b>21.7021E</b>	<b>No accounts exist. Go to webMethods Cloud &gt; Accounts and create an account.</b>
<b>Explanation</b>	Applications require that at least one account be selected before being uploaded, but no accounts have been created.
<b>Action</b>	Go to webMethods Cloud > Accounts and create at least one account.
<b>21.7022E</b>	<b>The on-premise Integration Server could not upload the application because the service {0} does not exist.</b>
<b>Explanation</b>	The specified service does not exist.
<b>Action</b>	Confirm that the service exists on the system.
<b>21.8001E</b>	<b>Account with alias name {0} does not exist.</b>
<b>Explanation</b>	There is no account with the specified alias name on Integration Server.
<b>Action</b>	Check the alias name of the Integration Live account that you are attempting to use to ensure you have the correct name.
<b>21.8002E</b>	<b>Account with alias name {0} already exists.</b>
<b>Explanation</b>	The account is not valid because another account already uses the specified alias name.
<b>Action</b>	Specify an alias name for the account that is unique for the Integration Server.
<b>21.8003E</b>	<b>The Alias Name parameter is required.</b>
<b>Explanation</b>	The Alias Name parameter is required but is either missing or is null.
<b>Action</b>	Make sure the Alias Name parameter is specified and that the value is not null.

<b>21.8005E</b>	<b>The Tenant ID parameter is required.</b>
<b>Explanation</b>	The Tenant ID parameter is required but is either missing or is null.
<b>Action</b>	Make sure the Tenant ID parameter is specified and that the value is not null.
<b>21.8006E</b>	<b>The Run As User parameter is required.</b>
<b>Explanation</b>	The Run As User parameter is required but is either missing or is null.
<b>Action</b>	Make sure the Run As User parameter is specified and that the value is not null.
<b>21.8012E</b>	<b>Error while enabling the listener for account {0}.</b>
<b>Explanation</b>	Integration Server encountered an error while enabling the listener for the specified account.
<b>Action</b>	Check the server log for details and take appropriate corrective action.
<b>21.8013E</b>	<b>Error while disabling the listener for account {0}.</b>
<b>Explanation</b>	Integration Server encountered an error while disabling the listener for the specified account.
<b>Action</b>	Check the server log for details and take appropriate corrective action.
<b>21.8019E</b>	<b>Error sending response for request ID {1} to execute service {0}.</b>
<b>Explanation</b>	Integration Server encountered an error while sending a response to the request received from webMethods Cloud for the specified request ID.
<b>Action</b>	Check the server log for details and take appropriate corrective action.
<b>21.8021E</b>	<b>Error executing service {0} for request ID {1}.</b>
<b>Explanation</b>	Integration Server encountered an error while executing the specified service.
<b>Action</b>	Check the server log for details and take appropriate corrective action.
<b>21.8022E</b>	<b>Test of the account failed. Confirm that the parameters are correct and tenant is registered in webMethods Cloud.</b>
<b>Explanation</b>	The test of the account failed.
<b>Action</b>	Make sure that the information provided is correct and that the tenant is registered in webMethods Cloud.

---

<b>21.8024E</b>	<b>An error was encountered while executing service {0}. The response was not received within {1} milliseconds.</b>
<b>Explanation</b>	Integration Server did not receive a response from the service within the time allowed.
<b>Action</b>	Ensure that the on-premise Integration Server is connected to webMethods Cloud and that the account is enabled.
<b>21.8026E</b>	<b>The information for account {0} was not uploaded successfully on stage {1}. Check the Integration Server logs for more details. Error: {2}</b>
<b>Explanation</b>	Integration Server encountered the specified error while uploading the account.
<b>Action</b>	Check the server log for details and take appropriate corrective action.
<b>21.8027E</b>	<b>Service {0} is not shared by on-premise for application {1}.</b>
<b>Explanation</b>	The specified service is not shared by the on-premise Integration Server.
<b>Action</b>	Make sure that the service is assigned to the specified application.
<b>21.8029E</b>	<b>Invalid account {0} associated with the execution of service {1}.</b>
<b>Explanation</b>	The specified account is not associated with the application that shares the service.
<b>Action</b>	Ensure that the application that shares the service is associated with the specified account.
<b>21.8031E</b>	<b>Account {0} was not removed from stage {1}. Check the Integration Server logs for more details. Error: {2}</b>
<b>Explanation</b>	The specified account was not deleted from the stage.
<b>Action</b>	Check the server error log for more detailed information and take the appropriate corrective action.
<b>21.8032E</b>	<b>Invalid value {1} specified for the stage parameter of account {0}.</b>
<b>Explanation</b>	The account settings were not retrieved correctly from webMethods Cloud.
<b>Action</b>	Make sure that you obtained the correct account settings from webMethods Cloud.
<b>21.8033E</b>	<b>No account information is configured for webMethods Cloud.</b>
<b>Explanation</b>	You cannot upload or enable accounts or applications without first configuring the account settings.
<b>Action</b>	Specify the account settings and retry the operation.

<b>21.8034E</b>	<b>The webMethods Cloud account endpoint to which the on-premise Integration Server should send responses is not valid</b>
<b>Explanation</b>	You cannot upload or enable accounts or applications without first configuring the account settings.
<b>Action</b>	Specify the account settings and retry the operation.
<b>21.8035E</b>	<b>Invalid account settings. Make sure that webMethods Cloud settings are configured.</b>
<b>Explanation</b>	Integration Server cannot connect to webMethods Cloud because there are no settings configured for the webMethods Cloud.
<b>Action</b>	Configure a valid webMethods URL on the Settings screen of the Integration Server Administrator.
<b>21.8036E</b>	<b>Stage for the account is not configured on webMethods Cloud. Contact webMethods Cloud Administrator.</b>
<b>Explanation</b>	The stage specified for the account does not exist on Integration Cloud.
<b>Action</b>	Contact the webMethods Cloud administrator.
<b>21.8037E</b>	<b>Stage for the application is not configured on webMethods Cloud. Contact webMethods Cloud Administrator</b>
<b>Explanation</b>	The stage specified for the application does not exist on Integration Cloud.
<b>Action</b>	Contact the webMethods Cloud administrator.
<b>21.9003E</b>	<b>Cannot delete account {0} because it is in use by other applications.</b>
<b>Explanation</b>	The specified account is in use by other applications and cannot be deleted.
<b>Action</b>	Modify the application to use a different account, or leave the account active.
<b>21.9006E</b>	<b>Unable to connect to on-premise Integration Server for account {0}.</b>
<b>Explanation</b>	The specified account cannot be tested.
<b>Action</b>	Ensure that the specified account is enabled on the on-premise Integration Server.
<b>24.23</b>	<b>Central User Manager queried for group "{0}" of type {1} and returned "{2}".</b>

24.24	Central User Manager queried for user "{0}" and returned "{1}".
24.25	Central User Manager queried for membership. User "{0}" {1} a member of "{2}".
24.26	Central User Manager found user "{0}" in "{1}" of type {2}.
24.27	Central User Manager searched for group "{0}" and returned "{1}".
24.28	Central User Manager searched for user "{0}" and returned "{1}".
24.39E	<b>Error while creating Integration Live user groups, tenantID : {0}. Error message: {1}. Stack trace: {2}</b>
<b>Explanation</b>	An unexpected error occurred while creating Integration Live user groups.
<b>Action</b>	Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
24.41	<b>Integration Live Manager addUserInGroup(), --&gt; group "{0}" reterived from UserManager for group id "{1}".</b>
24.42	<b>Integration Live Manager addUserInGroup(), --&gt; user "{0}" added into group "{1}".</b>
24.43	<b>Integration Live Manager updateUserInGroup(), --&gt; before update user "{0}", saml security token "{1}".</b>
24.44	<b>Integration Live Manager updateUserInGroup(), --&gt; after update user "{0}", saml security token "{1}".</b>
24.45	<b>Integration Live Container UserManager addUser(), SagSecurityToken --&gt; {0}.</b>
24.46	<b>Integration Live Container UserManager addUser(), tenantID: {0}.</b>

- 24.47            **Integration Live Container UserManager addUser(), user already present--> {0} but it got updated using this Assertion.**
  
- 24.48            **Integration Live Container UserManager addUser(), user added--> {0}.**
  
- 24.49            **Integration Live Container UserManager removeUser(), user--> {0}.**
  
- 24.50            **Integration Live Container UserManager removeUser(), user removed successfully--> {0}.**
  
- 24.51            **Integration Live Container UserManager getUser(), user not found --> {0}.**
  
- 24.52            **Integration Live Container UserManager addUserInGroup(), --> group "{0}" retrieved from UserManager.**
  
- 24.53            **Integration Live Container UserManager addUserInGroup(), --> user "{0}" added into group "{1}".**
  
- 24.54            **Integration Live Container UserManager addUserInGroup(), --> group "{0}" is not found so not adding to user {1}.**
  
- 24.55            **Integration Live Container UserManager addUserInGroup(), --> role "{0}" retrieved from UserManager.**
  
- 24.56            **Integration Live Container UserManager addUserInGroup(), --> user "{0}" added into role "{1}".**
  
- 24.57            **Integration Live Container UserManager addUserInGroup(), --> role "{0}" is not found so not adding to user {1}**
  
- 24.58            **Integration Live Container UserManager getUser(), userID: {0}.**

24.59	Integration Live Container UserManager getUser(), user found --> {0}.
25.67	Integration Server could not initialize the cluster. Stopping Integration Server initialization. Use the server log and error log to diagnose and correct the problem.
28.62	Unable to load keystores and truststores for package {0}.
28.63	Error in un-loading keystores and truststores for package {0}
35.5	Number of lines to display must be a non negative number. {0}.
4.9998	Exception -> {0}
50.22	ForEach failed: {0}: out-array={1}, in-array={2}
50.23	ForEach failed: No source data available for in-array {0}
50.24	ForEach failed: in-array {0} is not an array type.
50.25	ForEach out-array {0} is not the same length as in-array {1}.
53.15	The listener for the port with alias "{0}" does not exist.
53.9999	{0}
64.32	HTTP Put {0}
64.33	HTTP Delete {0}

64.34	HTTP Head {0}
64.35	HTTP Options {0}
64.36	HTTP Trace {0}
68.29	{0}
68.30	{0}
7.5	Access Denied. User "{0}" in tenant {1} does not have permissions to access assets in package {2}.
71.12	EPRT command refused. The EPRT address {0} does not match the original host address {1}.
72.19	Using default html encoding for input: "{0}"
72.20	Exception occurred while initializing encoder {0}. Reason: {1}
72.21	Initialization of encoder "{0}" failed
72.22	Performing "{0}" encoding for input: "{1}". Output is: "{2}"
72.23	Failed to initialize the bundle for encoder "{0}"
72.24	Initialization of encoder "{0}" completed
75.9998	Unable to extract the password associated with the alias: {0}

- 76.35            A valid encoding is not available in the XML header {0}. Proceeding with the encoding value specified in `watt.server.xml.encoding = {1}`.
- 88.9443        One or more required Headers "{0}" are not present in the SOAP response.
- 95.27            The audit logging database does not populate the `CHAR_OCTET_LENGTH` field in its metadata. Integration Server cannot determine the maximum number of bytes for the `WMSERVICEACTIVITYLOG.FULLMESSAGE` and `WMSERVICECUSTOMFLDS.STRINGVALUE` columns. If the data inserted into these columns need to be truncated, they will be truncated based on the number of characters rather than the number of bytes. This may lead to `SQLExceptions` while writing to the audit log. To avoid this, use the `ALTER TABLE` command on your database to increase the size of these columns.
- 95.28            Audit Logging: The {0} has entered fail-fast mode.
- 95.29            Audit Logging: The {0} has exited fail-fast mode.
- 95.34            Audit Logging: Error occurred while reconnecting to session for messaging connection alias {0}; will retry after {1} seconds. Error message: {2}
- 95.35            Audit Logging: Starting monitor for creating session with messaging connection alias {0}; retry interval is {1} seconds.
- 95.36            Audit Logging: Attempting to reconnect to session for messaging connection alias {0}.
- 95.41            Skipping {0} audit log data. It is larger than {1} MB, the limit defined by `watt.server.diagnostic.logFiles.maxMB`.
- 96.11            The `DataStoreDBListener` has been notified of `SQLException`. The JDBC connection to {0} is still valid. Returning it to the pool.

- 96.20            creation of JDBC connection failed with exception : {0}
  
- 96.21            JDBC Connection pool is currently in Fail-Fast mode for pool {0}:{1}
  
- 96.22            {0} threads are waiting to get the JDBC Connection for pool {1}:{2}
  
- 96.23            Connection pool size is {0}, Available pool size is {1} for pool {2}:{3}. The Maximum connection is {4}
  
- 96.24            Created a new JDBC Connection for pool {0}:{1}. Connection pool size is {2}.
  
- 96.25            Got Exception for pool {0}:{1}. Exception details: {2}
  
- 96.26            Enter Fail-Fast mode for pool {0}:{1}.
  
- 96.27            Exit Fail-Fast mode for pool {0}:{1}.
  
- 96.28            Re-initializing the pool {0}:{1}.
  
- 96.29            Removed the connection from pool {0}:{1}. Connection pool size is {2}. Available pool size is {3}.
  
- 96.30            Released the connection to pool {0}:{1}. Connection pool size is {2}. Available pool size is {3}.
  
- 96.8             JDBC Connection pool threshold {0}, {1} available for pool {2}:{3}
  
- 96.9             JDBC Connection pool waiting threads threshold {0}, {1} threads waiting for connection for pool {2}:{3}

**ALREADY\_MARKED\_ROLLBACK** – tran was rolled back because tran was marked for rollback

**ANNOTATION\_FIELD\_DUPLICATE\_NAME** – {0} - {1} appears more than once in the document type

**ANNOTATION\_FIELD\_ENV** – {0} - {1} envelope field is not allowed as an annotation field

**ANNOTATION\_FIELD\_INVALID\_NAME** – {0} - {1} is not a valid Digital Event Services field name

**ANNOTATION\_FIELD\_NOT\_FOUND** – {0} - {1} field not found in document type

**ANNOTATION\_FIELD\_NOT\_VALID** – {0} - {1} field is invalid type

**ANNOTATION\_NSR\_NOT\_PUBLISHABLE** – Document type is not publishable

**ANNOTATION\_NSR\_NOT\_SPECIFIED** – Document type not specified

**APLog.string(APLog.AP\_CONNECTION\_TEST\_FAILED)** – Test of CentraSite connection failed.

**Explanation** An attempt was made to connect to CentraSite, but a connection could not be made.  
**Action** Check the connection parameters in Integration Server Administrator. Check the error log in both Integration Server and CentraSite.

**ART.0114.0002E** **Unable to get adapter type information. Internal error.**

**Explanation** An error occurred while fetching the list of supported services for a particular adapter.  
**Action** This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

**ART.0114.0003E** **Unable to get information about adapter type {0}.**

**Explanation** An error occurred while retrieving a service's localized deployment values (adapter name, adapter version, adapter JCA version) from the specified adapter's metadata.  
**Action** This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

<b>ART.0114.0004E</b>	<b>Error getting available packages.</b>
<b>Explanation</b>	An error occurred while retrieving a list of packages available for node creation.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0005E</b>	<b>Error(s) during Adapter Runtime startup.</b>
<b>Explanation</b>	An error occurred during the initialization of the com.wm.pkg.art.AdapterRuntimeGlobals class.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0006E</b>	<b>Unable to initialize transaction manager. Transaction manager already initialized.</b>
<b>Explanation</b>	WmART has attempted to initialize the Transaction Manager twice.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0007E</b>	<b>Unable to get managed connection factories for adapter type {0}.</b>
<b>Explanation</b>	WmART was unable to obtain a list of connection factories for the specified adapter.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0008E</b>	<b>Unable to get the description and display name for connection type "{0}" of adapter type "{1}".</b>
<b>Explanation</b>	An error occurred while getting the display name and description for the specified connection/listener in the specified adapter.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0009E</b>	<b>Error(s) while registering adapter type {0}.</b>
<b>Explanation</b>	An error occurred while loading the specified adapter.
<b>Action</b>	This might be due to a connection that failed to initialize properly. Ensure that the adapter's connections can communicate with their respective resources. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

---

<b>ART.0114.0010E</b>	<b>Error(s) while unregistering adapter type {0}.</b>
<b>Explanation</b>	An error occurred while shutting down the specified adapter's connection resources.
<b>Action</b>	This might be due to problems in one or more connections. Ensure that all adapter connections shut down properly when the adapter was unloaded.
<b>ART.0114.0011E</b>	<b>Error occurred while Adapter Runtime was loading an adapter type. Missing required input, "{0}".</b>
<b>Explanation</b>	The class name of an adapter was not present as the first item in the pipeline given to com.wm.pkg.art.deployment.Service.registerAdapterType.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0012E</b>	<b>Error occurred while Adapter Runtime was loading an adapter type. Unexpected adapter type object "{0}" for input "{1}".</b>
<b>Explanation</b>	The class name of the object passed to com.wm.pkg.art.deployment.Service.registerAdapterType is not derived from WmAdapter.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0013E</b>	<b>Error occurred while Adapter Runtime was loading adapter type "{0}".</b>
<b>Explanation</b>	An error occurred while loading the specified adapter.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0014E</b>	<b>Error occurred while Adapter Runtime was unloading an adapter type. Missing required input, "{0}".</b>
<b>Explanation</b>	The class name of an adapter was not present as the first item in the pipeline given to com.wm.pkg.art.deployment.Service.unregisterAdapterType.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

**ART.0114.0015E**      **Error occurred while Adapter Runtime was unloading an adapter type. Unexpected adapter type object "{0}" for input "{1}".**

**Explanation**      The class name of the specified object passed to com.wm.pkg.art.deployment.Service.unregisterAdapterType is not derived from WmAdapter.

**Action**              This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

**ART.0114.0016E**      **Error occurred while Adapter Runtime was unloading adapter type "{0}".**

**Explanation**      An error occurred while loading the specified adapter.

**Action**              This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

**ART.0114.0017E**      **Error occurred while registering XidFactory for adapter type "{0}".**

**Explanation**      WmART was unable to locate the Transaction Manager or Transaction ID Factory class for the specified adapter.

**Action**              This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

**ART.0114.0018E**      **Unable to get XidFactories for adapter type "{0}".**

**Explanation**      WmART was unable to locate the class loader while retrieving the Transaction ID Factory map for the specified adapter.

**Action**              This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

**ART.0114.0019E**      **Unable to get XidFactory {0} for XAResource {1} in adapter type "{2}".**

**Explanation**      WmART was unable to determine the corresponding XidFactory class for the specified XAResource class while loading the adapter.

**Action**              This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

---

<b>ART.0114.0020E</b>	<b>Error occurred while loading online help system for adapter type "{0}".</b>
<b>Explanation</b>	An error occurred while WmART was attempting to fetch the path to the specified adapter's online help file.
<b>Action</b>	Ensure that a help page key exists in your AdapterResourceBundle for ADKGLOBAL.RESOURCEBUNDLEKEY_LISTRESOURCES, ADKGLOBAL.RESOURCEBUNDLEKEY_LISTCONNECTIONTYPES, ADKGLOBAL.RESOURCEBUNDLEKEY_LISTPOLLINGNOTIFICATIONS, ADKGLOBAL.RESOURCEBUNDLEKEY_LISTPOLLINGNOTIFICATIONDETAILS, and ADKGLOBAL.RESOURCEBUNDLEKEY_ABOUT.
<b>ART.0114.0021E</b>	<b>Error occurred while loading copyright for adapter type "{0}".</b>
<b>Explanation</b>	Failed to read a third-party copyright file for the specified adapter.
<b>Action</b>	If you have explicitly specified ADKGLOBALS.RESOURCEBUNDLEKEY_THIRDPARTYCOPYRIGHTURL in the adapter's resource bundle, ensure that the file this key references is in the pub directory in the adapter's directory tree. Also ensure that this file is readable by Integration Server.
<b>ART.0114.0022E</b>	<b>Error in {0}. Missing or invalid parameter: {1}.</b>
<b>Explanation</b>	A value was not specified for the parameter of the specified method.
<b>Action</b>	If you explicitly invoked the specified method, check your parameter values and resubmit. Otherwise, look in the error log for related errors.
<b>ART.0114.0030E</b>	<b>Unable to create node {0} in the namespace.</b>
<b>Explanation</b>	WmART failed to create the specified connection or listener node in the namespace.
<b>Action</b>	The connection/listener information you provided in Integration Server Administrator is invalid, or perhaps duplicates an existing connection/listener in the same namespace. Refer to adjacent log entries for specifics.
<b>ART.0114.0031E</b>	<b>Unable to update node {0}. Package not found.</b>
<b>Explanation</b>	WmART attempted to save changes to the specified namespace node, but could not determine its package.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

- ART.0114.0032E**      **Unable to update resource {0}.**  
**Explanation**      An error occurred when updating a value in the specified namespace.  
**Action**              This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0114.0033E**      **Invalid folder name {0}.**  
**Explanation**      While creating a new connection node, a null folder name was passed to `com.wm.pkg.art.util.ServiceHelper.checkInterfaceName`.  
**Action**              This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0114.0034E**      **Unable to create folder {0}.**  
**Explanation**      WmART was unable to create the specified folder in the adapter's namespace.  
**Action**              Ensure that the folder name conforms to naming conventions in your server's local file system, and that Integration Server has permissions to create folders under the packages folder. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0114.0035E**      **Unable to create record for {0}.**  
**Explanation**      An error occurred in `ServiceHelper.createRecordFromBean` while creating an `NSRecord` from the specified object. Adjacent log messages might contain additional details.  
**Action**              This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0114.0036E**      **Unable to create folder for service {0}.**  
**Explanation**      An error occurred in `ServiceHelper.registerService` while creating the file system infrastructure for the specified adapter service. Adjacent log messages might contain additional details.  
**Action**              Ensure that the local operating system access permissions within the Integration Server packages folder will allow WmART to create folders and files dynamically.

---

<b>ART.0114.0037E</b>	<b>Unable to create service {0}.</b>
<b>Explanation</b>	An error occurred in ServiceHelper.registerService while registering the adapter service. Adjacent log messages might contain additional details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0038E</b>	<b>Unable to create flow {0}.</b>
<b>Explanation</b>	An error occurred in ServiceHelper.createFlowService. Adjacent log messages might contain additional details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0040E</b>	<b>Unable to create interaction input record.</b>
<b>Explanation</b>	An error occurred in RecordFactoryBridgeImpl.createInputRecord while creating a mapped Record. Adjacent log messages might contain additional details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0041E</b>	<b>Unable to create input record. createMappedRecord() returned {0}.</b>
<b>Explanation</b>	A call to RecordFactory.createMappedRecord returned an object of the specified class rather than a WmRecord or IDataCodable object.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0042E</b>	<b>Unable to convert interaction output record into IData. Output record is {0}.</b>
<b>Explanation</b>	RecordFactoryBridgeImpl.createOutputData was passed an instance of the specified class rather than a WmRecord, IData, or IDataCodable instance.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

**ART.0114.0050E**      **Unable to convert string to specific data type. The data type is not specified or the string value is null.**

**Explanation**      While configuring a new connection or listener, WmART detected that the type or value of one of the connection's properties is null.

**Action**              Ensure that you enter values for all required properties. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

**ART.0114.0051E**      **Unable to convert string to specific data type. Unsupported data type {0}.**

**Explanation**      You omitted a value when configuring a connection or listener property from Integration Server Administrator.

**Action**              Reconfigure the connection/listener, entering valid values for all properties on the Integration Server Administrator page.

**ART.0114.0053E**      **Unable to convert string array to specific data type array. The data type is not specified.**

**Explanation**      While configuring a new connection or listener, WmART detected that the type of a property array is null.

**Action**              This condition indicates a coding error in the adapter or the Adapter Runtime (WmART) itself. Ensure that the adapter is handling connection and listener properties correctly. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

**ART.0114.0054E**      **Unable to convert string array to specific data type array. Unsupported data type {0}.**

**Explanation**      The Adapter Runtime (WmART) has detected a property array in a connection or listener that has an unsupported data type.

**Action**              Change your connection/listener to use only supported data types for all properties.

**ART.0114.0055E**      **Unable to convert string array to data type {0} array.**

**Explanation**      An unexpected property array conversion error has occurred while configuring a connection or listener.

**Action**              This might be due to invalid data in a property array on the Integration Server Administrator page, such as non-numeric data in a numeric property. Reconfigure the connection/listener to ensure that the entered data matches the expected data types for all properties.

---

<b>ART.0114.0056E</b>	<b>Unable to convert string array to primitive int array.</b>
<b>Explanation</b>	A value has been entered in a connection or listener property array that cannot be converted to a Java int type.
<b>Action</b>	Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.
<b>ART.0114.0057E</b>	<b>Unable to convert string array to primitive long array.</b>
<b>Explanation</b>	A value has been entered in a connection or listener property array that cannot be converted to a Java long data type.
<b>Action</b>	Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.
<b>ART.0114.0058E</b>	<b>Unable to convert string array to primitive float array.</b>
<b>Explanation</b>	A value has been entered in a connection or listener property array that cannot be converted to a Java float type.
<b>Action</b>	Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.
<b>ART.0114.0059E</b>	<b>Unable to convert string array to primitive double array.</b>
<b>Explanation</b>	A value has been entered in a connection or listener property array that cannot be converted to a Java double type.
<b>Action</b>	Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.
<b>ART.0114.0060E</b>	<b>Unable to convert string array to primitive boolean array.</b>
<b>Explanation</b>	A value has been entered in a connection or listener property array that cannot be converted to a Java Boolean type.
<b>Action</b>	Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.
<b>ART.0114.0061E</b>	<b>Unable to convert string array to primitive short array.</b>
<b>Explanation</b>	A value has been entered in a connection or listener property array that cannot be converted to a Java short type.
<b>Action</b>	Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.

- ART.0114.0062E**      **Unable to convert string array to primitive char array.**  
**Explanation**      A value has been entered in a connection or listener property array that cannot be converted to a Java char type.  
**Action**              Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.
- ART.0114.0063E**      **Unable to convert string array to Integer array.**  
**Explanation**      A value has been entered in a connection or listener property array that cannot be converted to a Java integer instance.  
**Action**              Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.
- ART.0114.0064E**      **Unable to convert string array to Long array.**  
**Explanation**      A value has been entered in a connection or listener property array that cannot be converted to a Java long instance.  
**Action**              Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.
- ART.0114.0065E**      **Unable to convert string array to Float array.**  
**Explanation**      A value has been entered in a connection or listener property array that cannot be converted to a Java float instance.  
**Action**              Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.
- ART.0114.0066E**      **Unable to convert string array to Double array.**  
**Explanation**      A value has been entered in a connection or listener property array that cannot be converted to a Java double instance.  
**Action**              Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.
- ART.0114.0067E**      **Unable to convert string array to Boolean array.**  
**Explanation**      A value has been entered in a connection or listener property array that cannot be converted to a Java Boolean instance.  
**Action**              Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.

---

<b>ART.0114.0068E</b>	<b>Unable to convert string array to Short array.</b>
<b>Explanation</b>	A value has been entered in a connection or listener property array that cannot be converted to a Java short instance.
<b>Action</b>	Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.
<b>ART.0114.0069E</b>	<b>Unable to convert string array to Character array.</b>
<b>Explanation</b>	A value has been entered in a connection or listener property array that cannot be converted to a Java character instance.
<b>Action</b>	Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.
<b>ART.0114.0072E</b>	<b>Unable to set JavaBean properties.</b>
<b>Explanation</b>	WmART has detected an error while setting the properties on a listener or listener notification bean.
<b>Action</b>	Ensure that the adapter's listener and listener notification implementations adhere to the JavaBean standard.
<b>ART.0114.0073E</b>	<b>Unable to set property {0} to value {1} on class {1}.</b>
<b>Explanation</b>	WmART failed to set the specified property on the specified (bean) class because it could not introspect the class.
<b>Action</b>	Ensure that the adapter's service template implementations adhere to the JavaBean standard. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0074E</b>	<b>Property {0} not found in class {1}.</b>
<b>Explanation</b>	After introspecting the specified class, WmART failed to find the specified property in that class.
<b>Action</b>	Ensure that the adapter's service template implementations support the JavaBean standard. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

<b>ART.0114.0075U</b>	<b>Unable to set property descriptor.</b>
<b>Explanation</b>	WmART failed to introspect an unspecified bean.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0076E</b>	<b>Unable to set {0} to {1} because property is not writable.</b>
<b>Explanation</b>	WmART was unable to locate the "set" method for the specified property on a bean class. The property appears to be read only.
<b>Action</b>	Ensure that the adapter's service template implementations support the JavaBean standard. To make the specified property writable, implement a "set" method for it.
<b>ART.0114.0077E</b>	<b>Error while setting property {0} of class {1} to {2}.</b>
<b>Explanation</b>	An error occurred while setting the specified property on the specified class instance.
<b>Action</b>	Ensure that the adapter's service template implementations support the JavaBean standard. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0078E</b>	<b>Unable to get JavaBean properties for {0}.</b>
<b>Explanation</b>	An error occurred while reading the properties from the specified bean class.
<b>Action</b>	Ensure that the adapter's service template implementations support the JavaBean standard. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0081E</b>	<b>Unable to create instance of {0}.</b>
<b>Explanation</b>	WmART was unable to create a new instance of the specified class.
<b>Action</b>	Ensure that the adapter's service and notification template implementation classes expose a default public constructor and are not abstract. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0082E</b>	<b>Unable to get JavaBean property {0} of class {1}.</b>
<b>Explanation</b>	WmART failed to determine or invoke the "get" method for the property in the specified class.
<b>Action</b>	Ensure that the adapter's service template implementations support the JavaBean standard. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

---

<b>ART.0114.0083E</b>	<b>Exception encountered attempting to load fix information for adapter type {0}.</b>
<b>Explanation</b>	The Adapter Runtime (WmART) failed while attempting to load the installed update information for the adapter.
<b>Action</b>	This error is generated when an exception is caught during execution. Check the error logs for information on the original exception.
<b>ART.0114.0084E</b>	<b>Missing or invalid value. {0} is not a valid value for field {1}.</b>
<b>Explanation</b>	An error occurred while validating the common values for a connection pool. The common values are settings, such as, Minimum Pool Size, Maximum Pool Size, etc.
<b>Action</b>	Change the invalid value. Then attempt to save and enable your connection.
<b>ART.0114.0201E</b>	<b>Unable to introspect "{0}". This service introspects the parameters of connection only.</b>
<b>Explanation</b>	WmART failed to create a WmManagedConnectionFactory instance from the specified class name. The current WmART implementation does not allow this condition to occur.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0202E</b>	<b>Failure when introspecting the connection properties.</b>
<b>Explanation</b>	An error occurred while introspecting connection properties. Additional details are logged.
<b>Action</b>	Check adjacent log messages for specific error details. Correct any problems with your connection metadata. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0203E</b>	<b>Unable to introspect "{0}"</b>
<b>Explanation</b>	The Adapter Runtime (WmART) failed to create an instance of an adapter service, notification, or listener from the specified class name.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

<b>ART.0114.0204E</b>	<b>Unable to introspect the parameters of service template.</b>
<b>Explanation</b>	An error occurred while attempting to introspect a template or listener. Additional details are logged.
<b>Action</b>	Ensure that the adapter's implementation .class files are installed properly under the packages folder. If you modify the .class files for the adapter while the Integration Server is running, you must reload that adapter.
<b>ART.0114.0205E</b>	<b>Unable to lookup the resource domain values.</b>
<b>Explanation</b>	This is a general processing error message. Details should appear in adjacent log messages.
<b>Action</b>	Refer to the Action column for the accompanying messages.
<b>ART.0114.0206E</b>	<b>Connection alias was not specified in "{0}".</b>
<b>Explanation</b>	The connection, adapter, or listener could not be found in the request to the specified method.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0207E</b>	<b>The connection alias "{0}" does not support webMethods metadata extensions. The adapter could be a third-party adapter.</b>
<b>Explanation</b>	The specified connection alias is not derived from com.wm.adk.cci.connection.WmConnection.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0208E</b>	<b>The connection alias "{0}" isn't configured or failed.</b>
<b>Explanation</b>	WmART failed to create a ConnectionDataNode instance based on the specified connection alias.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

<b>ART.0114.0209E</b>	<b>Cannot get the connection instance of connectionAlias "{0}".</b>
<b>Explanation</b>	An error occurred while creating a WmConnection instance from the specified connection alias. Additional details are provided in adjacent log messages.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0213E</b>	<b>Cannot get the listener instance of listenerNode "{0}".</b>
<b>Explanation</b>	The method getListenerAdapterMetadata in com.wm.pkg.art.metadata.ConnectionMetadataService failed to locate and create a listener object for the specified listener node.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0216E</b>	<b>Unable to validate the resource domain value.</b>
<b>Explanation</b>	An error occurred while validating a resource domain. This is a general processing error message. Details should appear in adjacent log messages.
<b>Action</b>	Refer to the Action column for the accompanying messages.
<b>ART.0114.0218E</b>	<b>Failure when introspecting the parameters of the notification listener.</b>
<b>Explanation</b>	WmART failed to lookup a resource domain. Additional details should appear in adjacent log messages.
<b>Action</b>	Ensure that the adapter's implementation(s) of WmNotification.fillWmTemplateDescriptor sets resource domains correctly.
<b>ART.0114.0219E</b>	<b>Failure when validating the resource domain "{0}". Null checkValues returned.</b>
<b>Explanation</b>	WmART was unable to locate internal check values for the specified resource domain.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0220E</b>	<b>Error occurred when closing the connection handle.</b>
<b>Explanation</b>	An error occurred when closing a connection. Additional details are logged.
<b>Action</b>	Ensure that the connection is configured properly and is able to communicate with the back-end resource. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

- ART.0114.0221E**      **No adapter type name specified in "{0}".**  
**Explanation**      The specified method in com.wm.pkg.art.metadata.ConnectionMetadataService failed to retrieve connection metadata because no adapter name was provided.  
**Action**              This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0114.0222E**      **No class name of WmManagedConnectionFactory specified in "{0}".**  
**Explanation**      The specified method in com.wm.pkg.art.metadata.ConnectionMetadataService failed to retrieve connection metadata because no connection factory class name was provided.  
**Action**              This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0114.0225E**      **Cannot get the connection handle of "{0}".**  
**Explanation**      WmART failed to create a WmConnection instance based on the specified connection alias.  
**Action**              This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0114.0226E**      **No class name of service template specified in "{0}".**  
**Explanation**      The specified method failed to retrieve metadata from an adapter template, notification template, or listener because no service class was provided in the request.  
**Action**              This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0114.0227E**      **No resource domain name specified in "{0}".**  
**Explanation**      The specified method failed because no resource domain was provided in the request.  
**Action**              This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

---

<b>ART.0114.0228E</b>	<b>No statement specified in "{0}".</b>
<b>Explanation</b>	The specified method in <code>com.wm.pkg.art.metadata.InteractionMetadataService</code> failed because the <code>AdapterRuntimeGlobals.STATEMENT</code> value was not provided in the request.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0230E</b>	<b>Unable to get the list of service template metadata.</b>
<b>Explanation</b>	The method <code>getInteractionAdapterMetadataList</code> in <code>com.wm.pkg.art.metadata.InteractionMetadataService</code> failed because the list of service templates supported by a connection was not provided in the request.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0231E</b>	<b>Unable to get the list of notification template metadata.</b>
<b>Explanation</b>	An error occurred in <code>com.wm.pkg.art.metadata.InteractionMetadataService.getNotificationAdapterMetadataList</code> . This is a general processing error message. Details should appear in adjacent log messages.
<b>Action</b>	Refer to the Action column for the accompanying messages.
<b>ART.0114.0232E</b>	<b>Unable to get the adapter type "{0}".</b>
<b>Explanation</b>	The method <code>getConnectionAdapterMetadata</code> in <code>com.wm.pkg.art.metadata.ConnectionMetadataService</code> was unable to create a <code>WmAdapterType</code> instance using the specified adapter name.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0233E</b>	<b>Unable to get the connection type "{0}".</b>
<b>Explanation</b>	The method <code>getConnectionAdapterMetadata</code> in <code>com.wm.pkg.art.metadata.ConnectionMetadataService</code> was unable to create a connection factory using the specified class name.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

<b>ART.0114.0234E</b>	<b>Unable to get a connection for resource "{0}".</b>
<b>Explanation</b>	WmART failed to create a WmConnection instance based on the specified connection alias.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0235E</b>	<b>Error in {0}. Missing parameter: {1}.</b>
<b>Explanation</b>	The method in com.wm.pkg.art.metadata.InteractionMetadataService failed to retrieve notification metadata because the specified request parameter was missing.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0236E</b>	<b>The connectionAlias or listenerNodeName must be specified.</b>
<b>Explanation</b>	The method in com.wm.pkg.art.metadata.InteractionMetadataService failed to lookup/validate notification values because neither the connection node alias nor the listener node was provided in the request.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0237E</b>	<b>Value for parameter missing: {0}.</b>
<b>Explanation</b>	The operation input requires the metadata parameter listed in the message text, but the value was not provided.
<b>Action</b>	Add the metadata property and a value to the operation inputs and resubmit.
<b>ART.0114.0238E</b>	<b>Value for parameter {0} does not match data type {1}.</b>
<b>Explanation</b>	The value submitted with the operation input does not match the metadata parameter listed in the message text.
<b>Action</b>	Change the type of the value for the operation and resubmit.
<b>ART.0114.0239E</b>	<b>Number of fields does not match number of types in a record definition.</b>
<b>Explanation</b>	The operation input requires a field type and a field name for each output field specification.
<b>Action</b>	Ensure that the number of entries in the array of values for the field names and field types are equal and resubmit.

---

<b>ART.0114.0240E</b>	<b>Parameter missing: {0}.</b>
<b>Explanation</b>	The operation input is missing the required parameter listed in the message text.
<b>Action</b>	Ensure that the input contains an entry for the parameter and resubmit.
<b>ART.0114.0241E</b>	<b>Unrecognized parameter {0} specified.</b>
<b>Explanation</b>	The operation input contains the parameter listed in the message text, which is not defined for this template.
<b>Action</b>	Remove the parameter from the operation input and resubmit.
<b>ART.0114.0242E</b>	<b>Required parameter "{0}" is missing, or has no value.</b>
<b>Explanation</b>	The operation is missing a required parameter.
<b>Action</b>	Provide the missing parameter value, and resubmit the operation.
<b>ART.0114.0243E</b>	<b>Failed to run {0} service. Details provided in error log.</b>
<b>Explanation</b>	An exception was caught while executing the service.
<b>Action</b>	Look in the error log for details on the original exception.
<b>ART.0114.0244E</b>	<b>Resource domain "{0}" is not recognized by provider "{1}".</b>
<b>Explanation</b>	The specified resource domain is not registered for the template.
<b>Action</b>	This error should only be encountered while using the webMethods ADK for adapter development. If you are developing an adapter, ensure that the specified resource domain is registered for your template. If you are not developing an adapter, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0245E</b>	<b>Failed to update IO properties in template "{0}"</b>
<b>Explanation</b>	An exception was caught while updating IO properties in the specified template.
<b>Action</b>	Look in the error log for details on the original exception.
<b>ART.0114.0300</b>	<b>Unable to start transaction {0}.</b>
<b>Explanation</b>	An error occurred during the initiation of a transaction.
<b>Action</b>	Make sure that there is connectivity to the adapter backend, and that the connection associated with the transaction is enabled.

<b>ART.0114.0301E</b>	<b>Unable to commit transaction. A transaction name must be specified.</b>
<b>Explanation</b>	WmART failed to determine the name of a transaction.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0302E</b>	<b>Error while committing transaction {0}. The transaction in progress is {1}.</b>
<b>Explanation</b>	The transaction name does not match the specified connection state.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0303E</b>	<b>Unable to commit transaction.</b>
<b>Explanation</b>	An error occurred while committing a transaction.
<b>Action</b>	If the adapter uses a connection that supports LocalTransaction, ensure that it is implemented properly. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0304E</b>	<b>Unable to rollback transaction. A transaction name must be specified.</b>
<b>Explanation</b>	WmART failed to determine the name of a transaction.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0305E</b>	<b>Error while rolling back transaction {0}. The transaction in progress is {1}.</b>
<b>Explanation</b>	The specified transaction name does not match the specified connection state.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0306E</b>	<b>Unable to rollback transaction.</b>
<b>Explanation</b>	An error occurred while committing a transaction.
<b>Action</b>	If the adapter uses a connection that supports LocalTransaction, ensure that it is implemented properly. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

---

<b>ART.0114.0307E</b>	<b>Retryable Error during commit transaction.</b>
<b>Explanation</b>	An unexpected system error occurred while committing a transaction. The transaction can be re-tried.
<b>Action</b>	Ensure that the back-end resource for the transaction can be reached from the server and is in a valid state. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0350E</b>	<b>Unable to set transaction timeout to {0} seconds.</b>
<b>Explanation</b>	WmART has detected that an XAResource failed to set the transaction timeout to the specified number of seconds.
<b>Action</b>	Verify that the back-end resource for the transaction can be reached from the server and is in a valid state. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0351E</b>	<b>Unable to create Transaction Manager.</b>
<b>Explanation</b>	WmTransactionManagerFactory failed to create a TransactionManager.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0352E</b>	<b>Unable to create Transaction Manager with transaction timeout set to {0} seconds.</b>
<b>Explanation</b>	WmTransactionManagerFactory failed to create a TransactionManager with the specified number of timeout seconds.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0353E</b>	<b>Unable to set transaction timeout. Invalid timeout value {0}.</b>
<b>Explanation</b>	com.wm.pkg.art.transaction.Service.setTransactionTimeout could not cast the specified object to type Integer.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

<b>ART.0114.0700E</b>	<b>Errors occurred in cluster coordination repository access for {0}.</b>
<b>Explanation</b>	An exception was caught during processing.
<b>Action</b>	Look in the error log for details on the original exception.
<b>ART.0114.0701E</b>	<b>Unable to retrieve ART instance/session ID.</b>
<b>Explanation</b>	The Adapter Runtime (ART) session ID failed to initialize.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.0702E</b>	<b>Errors occurred attempting to stop {0}. See error log for details.</b>
<b>Explanation</b>	An exception was caught when attempting to stop the notification.
<b>Action</b>	Look in the error log for details on the original exception.
<b>ART.0114.0703E</b>	<b>Errors occurred attempting to confirm cluster member. See error log for details.</b>
<b>Explanation</b>	An exception was caught trying to validate Adapter Runtime (ART) cluster members.
<b>Action</b>	Look in the error log for details on the original exception.
<b>ART.0114.0704E</b>	<b>Internal Error-assert failed - node: {0}, detail:{1}.</b>
<b>Explanation</b>	An unexpected exception occurred during processing.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, error logs with the stack trace exposed, and the detail in this error message.
<b>ART.0114.0705E</b>	<b>Errors occurred attempting to start {0}. See error log for details.</b>
<b>Explanation</b>	An exception was caught when attempting to start the notification.
<b>Action</b>	Look in the error log for details on the original exception.
<b>ART.0114.0707E</b>	<b>"{0}" is an invalid setting for the cluster coordination mode of {1}. Valid values: {2}.</b>
<b>Explanation</b>	An unsupported mode was encountered.
<b>Action</b>	Change the mode to one of the supported settings, and restart the notification.

<b>ART.0114.0708E</b>	<b>{0} is an invalid setting for max process time of {1}. Value must be an number between {2} and {3}.</b>
<b>Explanation</b>	An invalid maximum process time was encountered for the notification.
<b>Action</b>	Change the maximum process time to a value within the specified range, and restart the notification.
<b>ART.0114.0709E</b>	<b>{0} is an invalid setting for max setup time of {1}. Value must be an number between {2} and {3}.</b>
<b>Explanation</b>	An invalid maximum setup time was encountered for the notification.
<b>Action</b>	Change the maximum setup time to a value within the specified range, and restart the notification.
<b>ART.0114.0710E</b>	<b>Adapter cluster properties files are not the same across the cluster. Please synchronize all cluster properties files and restart servers.</b>
<b>Explanation</b>	The Adapter Runtime encountered inconsistent cluster property files.
<b>Action</b>	Ensure the cluster property files are the same for the adapter on each clustered Integration Server.
<b>ART.0114.0711E</b>	<b>Notification {0} was unexpectedly removed from cluster.</b>
<b>Explanation</b>	Another instance of this notification erroneously determined that this current instance failed. The current instance was removed.
<b>Action</b>	Check the logs on other servers in the cluster. A log on one of the servers will include message 1405, which indicates that this instance was removed. Check clock synchronization and network connectivity between the two servers.
<b>ART.0114.0712E</b>	<b>Operation failed because notification {0} was unexpectedly removed from cluster.</b>
<b>Explanation</b>	Another instance of this notification erroneously determined that this current instance failed. The current instance was removed. Note that this error is similar to ART.0114.0711E; however, in this case the node was changing states.
<b>Action</b>	Check the logs on other servers in the cluster. A log on one of the servers will include message 1405, which indicates that this instance was removed. Check clock synchronization and network connectivity between the two servers.
<b>ART.0114.1004E</b>	<b>Parameter parsing error.</b>
<b>Explanation</b>	WmART attempted to encrypt or decrypt a null string value.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

<b>ART.0114.1005E</b>	<b>Parameter parsing error.</b>
<b>Explanation</b>	WmART failed to encrypt a string value.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.1006E</b>	<b>Parameter parsing error.</b>
<b>Explanation</b>	WmART failed to decrypt a string value.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.1008D</b>	<b>Jar file {0} is not an update jar file. Unable to read the {1} entry.</b>
<b>Explanation</b>	This message applies to adapters that use update jar files to deliver updates. The update.cnf file is not readable in the update jar file.
<b>Action</b>	No action is required.
<b>ART.0114.1009D</b>	<b>Jar file {0} is not an update jar file. It does not contain the {1} entry.</b>
<b>Explanation</b>	This message applies to adapters that use update jar files to deliver updates. The update.cnf file is missing from the update jar file.
<b>Action</b>	No action is required.
<b>ART.0114.1010D</b>	<b>File {0} is not an update file. It is not a jar file.</b>
<b>Explanation</b>	This message applies to adapters that use update jar files to deliver updates. A file was found in the adapters update directory that is not a jar file.
<b>Action</b>	No action is required.
<b>ART.0114.1011D</b>	<b>Error initializing UpdateFile. Missing required parameter.</b>
<b>Explanation</b>	This message applies to adapters that use update jar files to deliver updates. A null value was supplied for the file name parameter. A value is required.
<b>Action</b>	No action is required.

---

<b>ART.0114.1012D</b>	<b>No updates found for adapter: {0}.</b>
<b>Explanation</b>	No installed updates were found for the adapter.
<b>Action</b>	No action is required.
<b>ART.0114.1013E</b>	<b>Unable to locate the package name for adapter: {0}.</b>
<b>Explanation</b>	The Integration Server package name for the adapter could not be determined.
<b>Action</b>	Ensure the adapter package depends on the WmART package, and reload the adapter package.
<b>ART.0114.1014W</b>	<b>Adapter {0} is missing required fix {1}.</b>
<b>Explanation</b>	This message applies to adapters that use update jar files to deliver updates. A fix required by the adapter was not found.
<b>Action</b>	Install the required fix, and reload the adapter.
<b>ART.0114.1015E</b>	<b>Error loading update jar file {0}. An exception was encountered loading the {1} file.</b>
<b>Explanation</b>	This message applies to adapters that use update jar files to deliver updates. An exception occurred trying to load the update.cnf file in the update jar.
<b>Action</b>	Look in the error log for details on the original exception.
<b>ART.0114.1016E</b>	<b>Error loading update jar file {0}. The {1} file is missing the required property updateName.</b>
<b>Explanation</b>	This message applies to adapters that use update jar files to deliver updates. The update.cnf file associated with the fix is missing a required value.
<b>Action</b>	Re-apply the fix, and reload the adapter.
<b>ART.0114.1017E</b>	<b>Error loading update jar file {0}. The update name contains the illegal character ';'.</b>
<b>Explanation</b>	This message applies to adapters that use update jar files to deliver updates. The fix name in the update.cnf file contains an illegal semicolon (;) character.
<b>Action</b>	Re-apply the fix, and reload the adapter.
<b>ART.0114.1018E</b>	<b>Error loading update information. The '{0}' tag is missing.</b>
<b>Explanation</b>	The fix name is missing.
<b>Action</b>	Re-apply the fix, and reload the adapter.

<b>ART.0114.1019E</b>	<b>Illegal value is set for page size in watt.art.page.size - "{0}".</b>
<b>Explanation</b>	An invalid value was specified for the watt.art.page.size parameter. This parameter must be a positive integer greater than or equal to 1.
<b>Action</b>	Set the value of watt.art.page.size to an integer greater than or equal to 1.
<b>ART.0114.1020</b>	<b>Error while storing/retrieving/removing the password for the connection "{0}".</b>
<b>Explanation</b>	An error occurred while storing, retrieving or removing the password for the connection from the Integration Server passman store. The error can occur when creating, updating, or deleting an adapter connection respectively.
<b>Action</b>	Make sure that the latest fix is installed on Integration Server. Try to restart Integration Server and perform the operation again. Also, make sure that the package containing the connection is imported properly into Integration Server.
<b>ART.0114.1103E</b>	<b>Facility {0} - {1} error. Log handler not found.</b>
<b>Explanation</b>	WmART failed to get a Log Handler from the Integration Server for the specified facility.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.1105E</b>	<b>No LogProducer for facility {0} - {1}.</b>
<b>Explanation</b>	WmART attempted to log a message, but no Log Producer exists for the specified facility.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.1106E</b>	<b>Facility {0} - {1} error. No facilities registered.</b>
<b>Explanation</b>	WmART failed to get the list of facility codes from the Log Handler.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.1112E</b>	<b>Unable to instantiate class {1} in adapter {0}. See error log for details.</b>
<b>Explanation</b>	An exception occurred trying to instantiate a template for the adapter.
<b>Action</b>	Ensure package dependencies are set correctly, and reload the adapter

<b>ART.0114.1113E</b>	<b>Class {0} is not a Service or Notification template class.</b>
<b>Explanation</b>	An invalid class was registered as a template.
<b>Action</b>	If you are using the webMethods ADK to develop an adapter, ensure your class is properly registered and coded to be a template. If this message is being issued from a webMethods adapter, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0114.1401W</b>	<b>Coordination data for {0} is invalid. Coordination will revert to a default state.</b>
<b>Explanation</b>	Coordination data in the repository was not valid. If the server was recently upgraded, this might simply represent a change in record formats, and the operation you are performing will automatically correct the data for you. If you have not recently upgraded or the problem persists, it is likely that the repository is corrupted.
<b>Action</b>	If you recently performed a server upgrade, no action is required. If you have not recently upgraded or the problem persists, check repository logs for errors.
<b>ART.0114.1405W</b>	<b>Processing for {0} on server {1} has timed-out or failed. Local instance will take over.</b>
<b>Explanation</b>	Remote failure detected.
<b>Action</b>	Check logs on indicated server for messages ART.0114.0711E or ART.0114.0712E. If the messages are in the log, refer to those error messages for a resolution. If the messages do not appear in the logs, no action is required.
<b>ART.0114.1407W</b>	<b>Illegal overlap occurred in node {0}. Please verify clock synchronization with cluster member '{1}'</b>
<b>Explanation</b>	An illegal overlap exception was detected.
<b>Action</b>	Ensure the clocks are synchronized for all Integration Servers in the cluster.
<b>ART.0114.1411E</b>	<b>Unable to access {0} file for adapter "{1}". Please check the file permissions. Running with default configuration.</b>
<b>Explanation</b>	The cluster property file could not be read.
<b>Action</b>	Ensure the cluster property file exists and is readable for the specified adapter.
<b>ART.0114.1412E</b>	<b>Unable to parse {0} file for adapter "{1}". Please correct file format. Running with default configuration.</b>
<b>Explanation</b>	The cluster property file could not be parsed.
<b>Action</b>	Validate the cluster property file format for the specified adapter.

**ART.0114.1415E**      **An internal error occurred while rendering cluster settings for adapter {0}. Updated settings will not be persisted.**

**Explanation**      The settings could not be saved to the cluster property file.

**Action**             Ensure the directory and the cluster file are writable.

**ART.0114.1416E**      **Error attempting to save cluster settings for adapter {0}. Error {1}**

**Explanation**      An exception occurred trying to save the cluster settings.

**Action**             Look in the error log for details on the original exception.

**ART.0114.1418W**      **Illegal overlap occurred in node {0}. Please increase setup timeout. Current setting: {1}, actual time: {2} seconds**

**Explanation**      The requested operation took longer than the allotted time; the operation had no other errors.

**Action**             Increase the node's timeout value as indicated by the actual time.

**ART.0114.1419W**      **Illegal overlap occurred in node {0}. Please increase execute timeout. Current setting: {1}, actual time: {2} seconds**

**Explanation**      A polling operation took longer than the allotted time; the polling operation had no other errors.

**Action**             Increase the node's timeout value as indicated by the actual time.

**ART.0114.3139E**      **EventType Definition doesnt exists in the EventTypeStore for notification : {0}.**

**Explanation**      Event Type Definition is not present in the same namespace for the notification in the Event Type Store.

**Action**             Create an event type definition for the notification and manually copy it to the Event Type Store.

**ART.0115.3202E**      **Listener error releasing connection for {0}. Error: {1}.**

**Explanation**      An error occurred while closing the connection associated with the specified listener.

**Action**             This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

---

<b>ART.0115.3203E</b>	<b>Error creating listener object: Null argument on init call.</b>
<b>Explanation</b>	The method <code>WmNotificationListener.initListenerNodeProperties</code> was passed a null <code>ListenerNode</code> instance.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3204E</b>	<b>Error creating listener object: NSName null.</b>
<b>Explanation</b>	The method <code>WmNotificationListener.initListenerNodeProperties</code> was unable to derive the name of a listener node from the <code>ListenerNode</code> instance.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3207E</b>	<b>Illegal event type received: {0}.</b>
<b>Explanation</b>	The method <code>WmNotificationListener.doNotify</code> was passed the specified invalid event ID.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3208E</b>	<b>Error during listener event. Error: {0}.</b>
<b>Explanation</b>	An error occurred while processing a listener event. Refer to the error message text for more details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3209E</b>	<b>Error creating listener object {0}. Error: {1}.</b>
<b>Explanation</b>	An error occurred creating the specified listener or initializing its properties.
<b>Action</b>	Ensure that the listener and its properties are configured correctly. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

<b>ART.0115.3211E</b>	<b>Existing transaction rolled back before execution of {0}.</b>
<b>Explanation</b>	WmART detected an incomplete transaction for the specified listener prior to executing it. The transaction has been rolled back.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3212E</b>	<b>Listener error during execution of {0}. Error: {1} rolling back existing transaction.</b>
<b>Explanation</b>	WmART detected an incomplete transaction for the specified listener prior to executing it. WmART attempted to rollback the transaction, but failed. Refer to the error message text for more details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3213E</b>	<b>Listener error during execution of {0}. Error: {1} checking transaction.</b>
<b>Explanation</b>	WmART failed to determine whether the specified listener has an open transaction. Refer to the error message text for more details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3214E</b>	<b>Listener {0} not Found.</b>
<b>Explanation</b>	WmART failed to lookup the specified listener.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3215E</b>	<b>Unable to create listener {0}. Listener node already exists.</b>
<b>Explanation</b>	There was an attempt to create a duplicate listener node.
<b>Action</b>	Enter a new listener node name that is unique to its folder.
<b>ART.0115.3217E</b>	<b>Error creating listener object: {0}. Invalid package name: {1}.</b>
<b>Explanation</b>	ListenerManager.createListener failed to create an instance of the listener because it could not find the package name in the pipeline.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

---

<b>ART.0115.3218E</b>	<b>Error creating listener object: {0}. Invalid node name.</b>
<b>Explanation</b>	ListenerManager.createListener failed to create an instance of the listener because the specified node name is missing or invalid.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3219E</b>	<b>Error creating listener object: {0}. Error: {1}.</b>
<b>Explanation</b>	An error occurred while creating the listener. This might be due to an invalid listener node name. Refer to the error message text for more details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3220E</b>	<b>Unable to get list of listener types supported by node {0}.</b>
<b>Explanation</b>	An error occurred in ListenerManager.queryListenerTemplatesSupported for the specified adapter. See adjacent error messages for additional details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3221E</b>	<b>Unable to get listener node properties {0}.</b>
<b>Explanation</b>	An error occurred while querying the specified listener's properties. See adjacent error messages for additional details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3223E</b>	<b>Unable to update listener {0}: Error: {1}.</b>
<b>Explanation</b>	An error occurred while updating the specified listener's properties. See adjacent error messages for additional details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

<b>ART.0115.3225E</b>	<b>Unable to delete listener {0}: Error: {1}.</b>
<b>Explanation</b>	An error occurred while deleting the specified listener. See adjacent error messages for additional details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3226E</b>	<b>Unable to copy listener {0}: Error: {1}.</b>
<b>Explanation</b>	An error occurred while copying the specified listener. See adjacent error messages for additional details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3227E</b>	<b>Unable to copy listener. Error: Source nodeName is required.</b>
<b>Explanation</b>	The method ListenerManager.copyAdapterListener failed because the source listener node name was not present in the pipeline.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3228E</b>	<b>Unable to copy listener {0}. Error: newNodeName is required.</b>
<b>Explanation</b>	The method ListenerManager.copyAdapterListener failed because the destination listener node name was not present in the pipeline.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3229E</b>	<b>Unable to copy listener {0}. Error: publishableDocumentName is required.</b>
<b>Explanation</b>	The method ListenerManager.copyAdapterListener failed because the destination listener publishable document name was not present in the pipeline.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

---

<b>ART.0115.3230E</b>	<b>Unable to copy listener {0}. Error: newPkg is required.</b>
<b>Explanation</b>	The method ListenerManager.copyAdapterListener failed because the destination listener node package name was not present in the pipeline.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3231E</b>	<b>Unable to copy listener {0} to {1}. Error: Unable to get source listener node.</b>
<b>Explanation</b>	The method ListenerManager.copyAdapterListener failed because the source listener node name is invalid.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3232E</b>	<b>Unable to copy listener {0}. Error: New name already exists {1}.</b>
<b>Explanation</b>	The method ListenerManager.copyAdapterListener failed because the specified destination listener node name already exists in the package.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3235E</b>	<b>Unable to rename listener {0}. Error: {1}.</b>
<b>Explanation</b>	An error occurred while renaming the specified listener. See adjacent error messages for additional details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3236E</b>	<b>Unable to find listener {0}.</b>
<b>Explanation</b>	The method ListenerManager.queryListenerStatistics failed because it could not locate the specified listener node.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

<b>ART.0115.3237E</b>	<b>Unable to get listener {0}. Error: Listener class name is not specified.</b>
<b>Explanation</b>	The method ListenerNode.getListener failed because it could not locate the WmConnectedListener implementation class name.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3238E</b>	<b>Error in Listener Callback:{0} notification {1}.</b>
<b>Explanation</b>	An error occurred while processing a listener notification event for the specified listener. If there is a callback name in the error message, it corresponds to the notification event.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3239E</b>	<b>Missing required parameter on service: {0}</b>
<b>Explanation</b>	The specified parameter is not present in the pipeline. This is an internal error.
<b>Action</b>	Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3240E</b>	<b>Unable to retrieve listener data. No listener name specified.</b>
<b>Explanation</b>	The method ARTAdmin.retrieveListenerData failed because no listener was present in the pipeline.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3241E</b>	<b>Error retrieving listener: {0}. Error: {1}</b>
<b>Explanation</b>	An error occurred while retrieving information about the listener. Refer to the error text for more details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

---

<b>ART.0115.3242E</b>	<b>Unable to get listener properties for adapter: {0}, listener type: {1}.</b>
<b>Explanation</b>	An error occurred while retrieving properties of the listener in the specified adapter.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3243E</b>	<b>Error retrieving listeners. Missing parameter: {0}</b>
<b>Explanation</b>	The method ARTAdmin.retrieveListeners failed because the adapter name was not present in the pipeline.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3244E</b>	<b>Error setting listener status. Missing parameter: {0}</b>
<b>Explanation</b>	The method ARTAdmin.setListenerStatus failed because the listener name was not present in the pipeline.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3245E</b>	<b>Error retrieving listener types. Missing parameter: {0}</b>
<b>Explanation</b>	The method ARTAdmin.retrieveListenerTypes failed because the adapter name was not present in the pipeline.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3246E</b>	<b>Error retrieving listener types. Error: {0}</b>
<b>Explanation</b>	An error occurred while retrieving the listener types supported by an adapter. Refer to the error text for more details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

<b>ART.0115.3247E</b>	<b>Error deleting listener. Missing parameter: {0}</b>
<b>Explanation</b>	The method ARTAdmin.deleteListener failed because the listener name was not present in the pipeline.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3248E</b>	<b>Error deleting listener: {0}. Unable to find the node.</b>
<b>Explanation</b>	The method ARTAdmin.deleteListener failed because the specified listener node name is invalid.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3249E</b>	<b>Error deleting listener: {0}.</b>
<b>Explanation</b>	An error occurred while deleting the specified listener. See adjacent error messages for additional details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3250E</b>	<b>Error setting properties for listener: {0}.</b>
<b>Explanation</b>	An error occurred while setting the properties of the specified listener. See adjacent error messages for additional details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3251E</b>	<b>Invalid listener node name: {0}.</b>
<b>Explanation</b>	The specified listener name is missing or invalid.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

---

<b>ART.0115.3252E</b>	<b>Unable to commit transaction for listener {0}. Error: {1}.</b>
<b>Explanation</b>	WmNotificationListener failed to commit a transaction for the specified listener. Refer to the error text for more details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3253E</b>	<b>Listener {0} did not process notification.</b>
<b>Explanation</b>	The listener received a notification and was unable to find a listener notification to process it.
<b>Action</b>	Check to ensure that the listed listener has listener notifications registered with it and that at least one of them is enabled.
<b>ART.0115.3255E</b>	<b>Unable to start listener: {0}. Cannot retrieve connection from connection node: {1}</b>
<b>Explanation</b>	The listener requires a connection to start. The startup processing could not get a connection from the listed connection node.
<b>Action</b>	Check to ensure that the listed connection is enabled. If the connection is pooled, increase the maximum connections allowed in the pool.
<b>ART.0115.3256E</b>	<b>Unable to start listener: {0}. Error: {1}</b>
<b>Explanation</b>	An unexpected exception occurred while trying to enable a notification.
<b>Action</b>	Check the Integration Server error log for details on the unexpected exception.
<b>ART.0115.3257E</b>	<b>Exceeded max retries. Shutting down listener {0}. Error: {1}</b>
<b>Explanation</b>	A retryable error occurred while attempting to execute the listener. The maximum number of retries is exceeded.
<b>Action</b>	Check the Integration Server error log for details on the retryable exception. Correct the error and try to enable the listener.
<b>ART.0115.3258E</b>	<b>Fatal error in listener {0}. See error log for details</b>
<b>Explanation</b>	An unexpected exception occurred during listener operation.
<b>Action</b>	Check the Integration Server error log for details on the unexpected exception.

<b>ART.0115.3259E</b>	<b>Unable to enlist connection transactional resource</b>
<b>Explanation</b>	An unexpected exception occurred while trying to start a transaction within the listener.
<b>Action</b>	Check the Integration Server error log for details on the unexpected exception. If no related exceptions are found, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0115.3260E</b>	<b>Unable to commit transaction for listener {0}. Listener disabled</b>
<b>Explanation</b>	An unexpected exception occurred while trying to commit a transaction within the listener.
<b>Action</b>	Check the Integration Server error log for details on the unexpected exception.
<b>ART.0115.3261E</b>	<b>Connection Node {0} not enabled.</b>
<b>Explanation</b>	An error occurred while trying to retrieve a connection for the listener.
<b>Action</b>	Check to ensure the connection is enabled and restart the listener.
<b>ART.0115.3262E</b>	<b>Fatal error initiating transaction in listener {0}. See error log for details</b>
<b>Explanation</b>	An unexpected exception occurred while trying to start a transaction within the listener.
<b>Action</b>	Check the Integration Server error log for details on the unexpected exception.
<b>ART.0115.3263E</b>	<b>Connection error while retrieving metadata in listener {0}. See error log for details</b>
<b>Explanation</b>	An error occurred while trying to retrieve a connection for the listener.
<b>Action</b>	Check to ensure the connection is enabled. Check the Integration Server error log for more information about the connection error.
<b>ART.0115.3264E</b>	<b>Unable to stop listener: {0}. Error: {1}</b>
<b>Explanation</b>	An unexpected exception occurred while trying to stop the listener.
<b>Action</b>	Check the Integration Server error log for details on the unexpected exception.
<b>ART.0115.3265E</b>	<b>Errors occurred. {0} listeners were not suspended. See error log for details.</b>
<b>Explanation</b>	While attempting to suspend all listeners, some of the listeners reported errors.
<b>Action</b>	Look in the error log for details on the specific exceptions.

---

<b>ART.0115.3266E</b>	<b>Errors occurred. {0} listeners were not enabled. See error log for details.</b>
<b>Explanation</b>	While attempting to enable all suspended listeners, some of the listeners reported errors.
<b>Action</b>	Look in the error log for details on the specific exceptions.
<b>ART.0115.3267E</b>	<b>Cannot update adapter-defined settings in suspended listener {0}.</b>
<b>Explanation</b>	The user attempted to update adapter-defined settings for a listener; however, the listener is currently suspended.
<b>Action</b>	Disable the listener, and retry the operation.
<b>ART.0115.3268E</b>	<b>{0} is in an invalid state for requested operation.</b>
<b>Explanation</b>	The user attempted an operation on a listener; however, the listener was not in the proper state for the operation.
<b>Action</b>	Change the state of the listener to an acceptable state, and retry the operation.
<b>ART.0115.3269E</b>	<b>Unable to complete update. Setting connection for listener {0} is not supported.</b>
<b>Explanation</b>	The user attempted to change the connection associated with a listener; however, the listener does not require a connection.
<b>Action</b>	This operation is not supported.
<b>ART.0115.3270E</b>	<b>Unable to create listener. Setting connection for listener type {0} is not supported.</b>
<b>Explanation</b>	The user attempted to create a listener with a connection; however the listener does not require a connection.
<b>Action</b>	This operation is not supported.
<b>ART.0115.3271E</b>	<b>Unable to create listener. Must specify connection for listener type {0}.</b>
<b>Explanation</b>	A user attempted to create a listener that requires a connection; however no connection was specified.
<b>Action</b>	Specify a connection, and retry the operation.
<b>ART.0115.3272E</b>	<b>Unable to identify adapter for listener type {0}.</b>
<b>Explanation</b>	Integration Server cannot determine the adapter associated with the specified listener type.
<b>Action</b>	Ensure your package dependencies are set properly. Reload the adapter package, and retry the operation.

<b>ART.0115.3712E</b>	<b>Error during listener execution.</b>
<b>Explanation</b>	Either a fatal error has occurred while executing a listener, or the maximum number of non-fatal errors has been exceeded while executing a listener.
<b>Action</b>	Ensure that the connection from the listener to the back-end EIS is still valid, and that a communications path between them exists.
<b>ART.0115.3716W</b>	<b>Failed to retrieve connection for callback in listener {0}. Error: {1}</b>
<b>Explanation</b>	An error occurred while trying to retrieve a connection for the listener shutdown callback processing.
<b>Action</b>	Check to ensure the connection is enabled. Check the Integration Server error log for details on the unexpected exception.
<b>ART.0115.3717W</b>	<b>Failure in shutdown callback in listener {0}. Error: {1}</b>
<b>Explanation</b>	An error occurred during the listener shutdown callback processing.
<b>Action</b>	Details on the error are included in the message. The shutdown will attempt to continue.
<b>ART.0116.3001E</b>	<b>Notification error during execution of {0}. Error: {1}.</b>
<b>Explanation</b>	An error occurred while executing the specified notification. Refer to the text in the error message for additional details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3002E</b>	<b>Notification error releasing connection for {0}. Error: {1}.</b>
<b>Explanation</b>	WmART failed to release the specified notification's connection back to the connection pool.
<b>Action</b>	For custom adapters, check the connection's implementation for possible blocking situations. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3003E</b>	<b>Error creating notification object: Null argument on init call.</b>
<b>Explanation</b>	The method WmNotification.initNotificationNodeProperties failed because it was passed a null NotificationNode object.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

---

<b>ART.0116.3004E</b>	<b>Error creating notification object: NSName null.</b>
<b>Explanation</b>	The method WmNotification.initNotificationNodeProperties failed because it was unable to get the node name from the NotificationNode object.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3005E</b>	<b>Error creating notification object: {0}. Publishable Document name not set.</b>
<b>Explanation</b>	The method WmNotification.initNotificationNodeProperties failed because it was unable to get the publishable document node name for the specified notification.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3006E</b>	<b>Error creating notification object: {0}. UUID not set.</b>
<b>Explanation</b>	The method WmNotification.initNotificationNodeProperties failed because it was unable to get the specified notification's universal unique identifier (UUID) from the NotificationNode object.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3007E</b>	<b>Illegal event type received: {0}.</b>
<b>Explanation</b>	The method WmNotification.notifyEvent was passed the specified invalid event ID.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3008E</b>	<b>Error during notification event. Error: {0}.</b>
<b>Explanation</b>	An error occurred in the method WmNotification.notifyEvent. Refer to the error message text for more details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

<b>ART.0116.3009E</b>	<b>Error creating notification object {0}. Error: {1}.</b>
<b>Explanation</b>	An error occurred in the method NotificationNode.getNotification while creating the notification. Refer to the error message text for more details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3010E</b>	<b>Error publishing notification {0}. Error: {1}.</b>
<b>Explanation</b>	An error occurred in the method WmAsynchronousNotification.publishToDispatcher while publishing a non-duplicate document from the specified notification. Refer to the error message text for more details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3011E</b>	<b>Existing transaction rolled back before execution of {0}.</b>
<b>Explanation</b>	WmART detected an incomplete transaction for the notification prior to processing a notification event. The transaction has been rolled-back.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3012E</b>	<b>Notification error during execution of {0}. Error: {1} rolling back existing transaction.</b>
<b>Explanation</b>	WmART detected an incomplete transaction for the specified notification prior to processing a notification event. It attempted to rollback the transaction, but failed. Refer to the error message text for more details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3013E</b>	<b>Notification error during execution of {0}. Error: {1} checking transaction.</b>
<b>Explanation</b>	WmART failed to determine whether the specified notification has an open transaction. Refer to the error message text for more details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

---

<b>ART.0116.3014E</b>	<b>Notification {0} not Found.</b>
<b>Explanation</b>	WmART failed to locate the specified notification.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3015E</b>	<b>Unable to create notification {0}. Notification node already exists.</b>
<b>Explanation</b>	WmART failed to create the specified notification because a notification with this name already exists.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3016E</b>	<b>Unable to create publishable document {0}. Error: {1}.</b>
<b>Explanation</b>	The method NotificationFactory.createPublishableDocument failed to create a document for the specified notification. Refer to the error message text for more details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3018E</b>	<b>Error creating notification object: {0}. Invalid node name.</b>
<b>Explanation</b>	The specified notification node name is missing or improperly formatted.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3019E</b>	<b>Error creating notification object: {0}. Error: {1}.</b>
<b>Explanation</b>	An error occurred while creating the specified polling or listener notification. Refer to the error message text for more details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3020E</b>	<b>Unable to get list of notification types supported by node {0}.</b>
<b>Explanation</b>	An error occurred in NotificationManager.queryNotificationTemplatesSupported for the specified adapter. See adjacent error messages for additional details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

<b>ART.0116.3021E</b>	<b>Unable to get notification node properties {0}.</b>
<b>Explanation</b>	An error occurred while querying the specified notification's properties. See adjacent error messages for additional details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3022E</b>	<b>Unable to update notification {0}. Error: Notification must be disabled.</b>
<b>Explanation</b>	NotificationManager received a request to update the properties of an active notification.
<b>Action</b>	Disable the notification from Integration Server Administrator prior to updating it.
<b>ART.0116.3023E</b>	<b>Unable to update notification {0}.</b>
<b>Explanation</b>	An error occurred while updating the notification's properties. See adjacent error messages for additional details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3024E</b>	<b>Unable to delete notification {0}. Error: Notification must be disabled.</b>
<b>Explanation</b>	NotificationManager received a request to delete an active notification.
<b>Action</b>	Disable the notification from Integration Server Administrator prior to deleting it.
<b>ART.0116.3025E</b>	<b>Unable to delete notification {0}.</b>
<b>Explanation</b>	An error occurred while deleting the specified notification. See adjacent error messages for additional details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3026E</b>	<b>Unable to copy notification {0}.</b>
<b>Explanation</b>	An error occurred while copying the specified notification. See adjacent error messages for additional details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

---

<b>ART.0116.3027E</b>	<b>Unable to copy notification {0}. Error: nodeName is required.</b>
<b>Explanation</b>	The specified notification node name is missing or incorrectly formatted.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3031E</b>	<b>Unable to copy notification {0}. Error: Invalid node name {1}.</b>
<b>Explanation</b>	Notification Manager failed to validate the specified node name. Refer to the error message text for more details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3032E</b>	<b>Unable to copy notification {0}. Error: New name already exists {1}.</b>
<b>Explanation</b>	The method NotificationManager.copyAdapterNotification failed because the specified destination notification node name already exists in the package.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3033E</b>	<b>Unable to copy notification {0}. Error: New document name already exists {1}.</b>
<b>Explanation</b>	The method NotificationManager.copyAdapterNotification failed because the specified new publishable document name already exists in the package.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3034E</b>	<b>Unable to rename notification {0}. Error: Notification must be disabled.</b>
<b>Explanation</b>	NotificationManager received a request to rename an active notification.
<b>Action</b>	Disable the notification from Integration Server Administrator prior to renaming it.
<b>ART.0116.3035E</b>	<b>Unable to rename notification {0}. Error: {1}.</b>
<b>Explanation</b>	An error occurred while renaming the notification. Refer to the error message text for more details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

<b>ART.0116.3036E</b>	<b>Unable to find notification {0}.</b>
<b>Explanation</b>	The method NotificationManager.queryNotificationStatistics failed because the specified notification could not be located in the namespace.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3037E</b>	<b>Unable to get notification {0}. Error: Notification class name is not specified.</b>
<b>Explanation</b>	The method NotificationNode.getNotification failed to determine the implementation class name for the specified notification.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3038E</b>	<b>Error in Notification Callback:{0} notification {1}.</b>
<b>Explanation</b>	An error occurred in method WmNotification.notifyEvent while processing the specified callback.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3039E</b>	<b>Missing required parameter on service: {0}</b>
<b>Explanation</b>	The method NotificationManager.queryNotificationTemplatesSupported failed because the adapter name was not present in the pipeline.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3040E</b>	<b>Error creating notification object: {0}. Missing parameter: {1}.</b>
<b>Explanation</b>	NotificationManager failed to create the notification because the specified parameter was not in the pipeline.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

---

<b>ART.0116.3041E</b>	<b>Error creating notification object: {0}. Invalid Package Name {1}.</b>
<b>Explanation</b>	NotificationManager failed to create the notification because the specified package name is invalid.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3042E</b>	<b>Error creating notification object: {0}. Invalid Service Name {1}.</b>
<b>Explanation</b>	NotificationManager failed to create the notification because the service name is missing, improperly formatted, or otherwise invalid.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3043E</b>	<b>Error deleting notification object. Invalid node name: {0}.</b>
<b>Explanation</b>	The specified notification node name is missing or incorrectly formatted.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3044E</b>	<b>Error deleting notification object: {0}. Error: {1}.</b>
<b>Explanation</b>	NotificationManager failed to validate the specified node name. Refer to the error message text for more details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3045E</b>	<b>Error deleting notification object: {0}. The specified node is not a Listener Notification node.</b>
<b>Explanation</b>	NotificationManager.deleteListenerNotification was called to delete the specified notification, which is a polling notification, not a listener notification.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

<b>ART.0116.3046E</b>	<b>Unable to create document {0}. Error: {1}.</b>
<b>Explanation</b>	An error occurred while creating a document for the specified notification. Refer to the error message text for more details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3047E</b>	<b>Unable to create notification {0}. Error deleting an existing record: {1}.</b>
<b>Explanation</b>	NotificationFactory failed to create the notification because it could not delete existing document records. Refer to the error message text for more details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3048E</b>	<b>Unable to create notification {0}. The specified Listener does not exist: {1}.</b>
<b>Explanation</b>	NotificationManager.createListenerNotification failed to create the notification because it could not locate the corresponding listener node. Refer to the error message text for more details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3049E</b>	<b>Unable to create notification {0}. The specified notification template is not synchronous: {1}.</b>
<b>Explanation</b>	NotificationFactory failed to create the notification because the underlying specified implementation class is not derived from WmSynchronousNotification. Refer to the error message text for more details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3050E</b>	<b>Unable to create notification {0}. The specified notification template is not asynchronous: {1}.</b>
<b>Explanation</b>	NotificationFactory failed to create the specified notification because the underlying specified implementation class is not derived from WmAsynchronousNotification. Refer to the error message text for more details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

---

<b>ART.0116.3051E</b>	<b>Unable to query properties for {0}. Invalid node name.</b>
<b>Explanation</b>	The specified notification node name is missing or improperly formatted.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3052E</b>	<b>Unable to query properties for {0}. Error: {1}.</b>
<b>Explanation</b>	NotificationManager failed to validate the node name. Refer to the error message text for more details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3053E</b>	<b>Unable to update notification {0}. Invalid node name.</b>
<b>Explanation</b>	The specified notification node name is missing or incorrectly formatted.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3054E</b>	<b>Unable to update notification {0}. Error: {1}.</b>
<b>Explanation</b>	NotificationManager failed to validate the node name. Refer to the error message text for more details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3055E</b>	<b>Error copying notification: {0}. Missing parameter: {1}.</b>
<b>Explanation</b>	NotificationManager failed to copy the notification because the specified parameter was not in the pipeline.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3056E</b>	<b>Error copying notification: {0}. Invalid Package Name {1}.</b>
<b>Explanation</b>	NotificationManager failed to copy the notification because the specified package name is invalid.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

<b>ART.0116.3057E</b>	<b>Error updating notification object: {0}. Missing parameter: {1}.</b>
<b>Explanation</b>	NotificationManager failed to update the notification because the specified parameter was not in the pipeline.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3058</b>	<b>Unable to copy notification {0}. Error: New node name is invalid {1}.</b>
<b>Explanation</b>	Invalid connection name specified.
<b>Action</b>	Remove any unsupported special characters from the connection name.
<b>ART.0116.3059</b>	<b>Error trying to enable notification {0}. Error: Listener not found {1}.</b>
<b>Explanation</b>	The error occurs when trying to enable or disable a listener notification, and the associated listener is not available.
<b>Action</b>	Make sure that the associated listener is not deleted. If the associated listener is deleted, create the listener again with the same name.
<b>ART.0116.3060E</b>	<b>Error setting notification schedule property {0}</b>
<b>Explanation</b>	An unexpected exception occurred while trying to set the schedule parameter listed in the message.
<b>Action</b>	Check the Integration Server error log for details about the unexpected exception.
<b>ART.0116.3061E</b>	<b>Unable to move notification. Error: Invalid node name {0}.</b>
<b>Explanation</b>	The name of the notification you are trying to move is invalid.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3062E</b>	<b>Unable to move notification {0}. Error: Invalid Node Name Format.</b>
<b>Explanation</b>	The name of the notification listed in the message text is not in folder:nodename format.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

---

<b>ART.0116.3063E</b>	<b>Error moving notification: {0}. Error: Missing parameter: {1}.</b>
<b>Explanation</b>	The move operation is missing the required parameter listed in the message text.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3064E</b>	<b>Error moving notification: {0}. Error: Invalid Package Name {1}.</b>
<b>Explanation</b>	The name of the destination package for the move operation is invalid on Integration Server.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3065E</b>	<b>Unable to move notification {0}. Error: Src/Dest Node names not the same.{1}</b>
<b>Explanation</b>	The notification node name was changed during the move operation.
<b>Action</b>	Only the package name and folder are allowed to change during a move operation, while the actual node name is not allowed to change. This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3066E</b>	<b>Unable to move notification {0}. Error: Notification must be disabled.</b>
<b>Explanation</b>	This notification cannot be moved because it is enabled. To move a notification, it first must be disabled.
<b>Action</b>	In Integration Server Administrator, disable the notification and retry the move operation.
<b>ART.0116.3067E</b>	<b>Unable to move notification {0}.</b>
<b>Explanation</b>	An unexpected exception occurred while trying to move a notification.
<b>Action</b>	Check the Integration Server error log for details about the unexpected exception.
<b>ART.0116.3068E</b>	<b>Unable to move notification {0}. Error: nodeName is required.</b>
<b>Explanation</b>	The node name specified for the move operation is either missing or invalid.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

<b>ART.0116.3069E</b>	<b>Unable to move notification {0}. Error: New node name is invalid {1}.</b>
<b>Explanation</b>	The new node name specified for the move operation is either missing or invalid.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3100</b>	<b>Unable to obtain list of polling notifications for adapter type.</b>
<b>Explanation</b>	The adapter type passed is null or invalid while retrieving, suspending, or resuming the adapter notifications.
<b>Action</b>	Ensure that a valid adapter type is passed.
<b>ART.0116.3101E</b>	<b>Unable to obtain detailed information for polling notification.</b>
<b>Explanation</b>	The method ARTAdmin.retrievePollingNotificationData failed because the notification name was not present in the pipeline.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3102E</b>	<b>Unable to set status for polling notification.</b>
<b>Explanation</b>	The method ARTAdmin.forceNotificationDisable failed because the notification name was not present in the pipeline.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3103E</b>	<b>Unable to set schedule for polling notification.</b>
<b>Explanation</b>	The method ARTAdmin.setNotificationSchedule failed because the notification name was not present in the pipeline.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3104E</b>	<b>Unable to retrieve listener notification list. Missing parameter: {0}</b>
<b>Explanation</b>	The method ARTAdmin.retrieveListenerNotifications failed because the adapter name was not present in the pipeline.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

---

<b>ART.0116.3105E</b>	<b>Unable to set notification status. Missing parameter: {0}</b>
<b>Explanation</b>	The method ARTAdmin.setNotificationStatus failed because the notification name was not present in the pipeline.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3106E</b>	<b>Unable to set notification status. Notification not found: {0}</b>
<b>Explanation</b>	The method ARTAdmin.setNotificationStatus failed because it was unable to locate the node for the specified notification.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3107E</b>	<b>Unable to set notification status for {0}. Error: {1}</b>
<b>Explanation</b>	The method ARTAdmin.setNotificationStatus failed because it was unable to enable or disable the specified listener notification.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3108E</b>	<b>Unable to publish notification. Message ID {0} exceeds maximum length of {1}.</b>
<b>Explanation</b>	The message ID specified by the adapter is longer than the allowed maximum length.
<b>Action</b>	Integration Server restricts the length of the message ID for a published document. Contact Software AG Global Support to see how to increase this setting. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0116.3115E</b>	<b>Errors occurred. {0} notifications reported errors while attempting to suspend. See error log for details.</b>
<b>Explanation</b>	While attempting to suspend all notifications, some of the notifications reported errors.
<b>Action</b>	Look in the error log for details on the specific exceptions.
<b>ART.0116.3116E</b>	<b>Errors occurred. {0} notifications were not enabled. See error log for details.</b>
<b>Explanation</b>	While attempting to enable all suspended notifications, some of the notifications reported errors.
<b>Action</b>	Look in the error log for details on the specific exceptions.

<b>ART.0116.3117E</b>	<b>Non-fatal errors encounter while disabling notification {0}. Details recorded in error log.</b>
<b>Explanation</b>	An exception was encountered during the disable callback for a notification.
<b>Action</b>	Look in the error log for details on the specific exception.
<b>ART.0116.3118E</b>	<b>Non-fatal errors encounter while suspending notification {0}. Details recorded in error log.</b>
<b>Explanation</b>	An exception was encountered during the suspend callback for a notification.
<b>Action</b>	Look in the error log for details on the specific exception.
<b>ART.0116.3119E</b>	<b>Non-fatal errors encounter while stopping notification {0}. Details recorded in error log.</b>
<b>Explanation</b>	An exception was encountered during the shutdown callback for a notification.
<b>Action</b>	Look in the error log for details on the specific exception.
<b>ART.0116.3120E</b>	<b>{0} is not a valid node type for this operation.</b>
<b>Explanation</b>	An attempt was made to change the connection associated with a polling notification; however, the specified node is not a polling notification node.
<b>Action</b>	Select a polling notification node, and retry the operation.
<b>ART.0116.3121E</b>	<b>{0} is in an invalid state for the requested operation.</b>
<b>Explanation</b>	An attempt was made to perform an operation on a notification; however, the notification was not in the correct state. Typically this occurs when you attempt to perform an update type of operation when the notification is not in a disabled or suspended state.
<b>Action</b>	Change the state of the notification to disabled or suspended, and retry the operation.
<b>ART.0116.3533</b>	<b>Error while executing Polling Notification {0}. Check if the notification is present in all clusters.</b>
<b>Explanation</b>	The error occurs when a polling notification does not exist on all nodes in an Integration Server cluster.
<b>Action</b>	Make sure that all clustered Integration Server nodes have the same set of adapter polling notifications.

---

<b>ART.0117.4000E</b>	<b>Unable to invoke adapter service {0}. Unable to establish connection to connection {1}.</b>
<b>Explanation</b>	WmART failed to create or locate the connection object associated with the specified adapter service.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0117.4001E</b>	<b>Unable to invoke adapter service {0}. Connection.createInteraction() returned null.</b>
<b>Explanation</b>	WmART failed to create a new instance of WmInteraction for the specified adapter service.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0117.4002E</b>	<b>Unable to invoke adapter service {0}.</b>
<b>Explanation</b>	An error occurred while running the specified adapter service and processing its output. Additional information might appear in adjacent log messages.
<b>Action</b>	Determine whether the implementation of the adapter's WmAdapterService.execute method is throwing an exception at run time, and correct as needed.
<b>ART.0117.4005E</b>	<b>Connection not available.</b>
<b>Explanation</b>	WmART failed to locate the connection data node for the specified connection and adapter service. This message will always appear in conjunction with 117.4020.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0117.4006E</b>	<b>Invalid adapter type {0}.</b>
<b>Explanation</b>	WmART failed to create an instance of the specified adapter service. This message will always appear in conjunction with 117.4021.
<b>Action</b>	Ensure that the implementation class for the adapter service is installed correctly in the package. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

- ART.0117.4007E**      **Unable to get record factory bridge.**  
**Explanation**      WmART failed to create or locate an input/output record factory bridge object.  
**Action**              This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0117.4008E**      **Unable to get connection factory from connection.**  
**Explanation**      WmART failed to locate the connection factory associated with a ConnectionResource.  
**Action**              This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0117.4009E**      **Unable to get record factory required for interaction input.**  
**Explanation**      An error occurred while locating a RecordFactory associated with a ConnectionFactory. Additional details might appear in adjacent log messages.  
**Action**              This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0117.4010E**      **Unable to get adapter record factory. ConnectionFactory.getRecordFactory() returned null.**  
**Explanation**      WmART failed to locate a RecordFactory associated with a ConnectionFactory.  
**Action**              This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0117.4011E**      **Unable to connect to resource {0}. The resource is already being used in a parent transaction.**  
**Explanation**      WmART attempted to create a new connection to the specified resource, but detected that the resource is currently enrolled in an ongoing transaction.  
**Action**              This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

---

<b>ART.0117.4012E</b>	<b>Unable to run adapter service. Error occurred when connecting to resource {0}.</b>
<b>Explanation</b>	An error occurred while creating a new connection to the specified resource. Additional details might appear in adjacent log messages.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0117.4013E</b>	<b>Internal Error: Unable to nest connection states.</b>
<b>Explanation</b>	WmART attempted to start a new transaction, but detected that a parent transaction already exists.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0117.4014E</b>	<b>Error while starting nested transaction. The name {0} is already in use.</b>
<b>Explanation</b>	WmART attempted to start a new transaction, but detected that the specified transaction ID is already in use.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0117.4015E</b>	<b>Error(s) occurred while closing adapter connections.</b>
<b>Explanation</b>	Error(s) occurred while closing one or more connections involved in a transaction. Separate log messages are listed for each connection.
<b>Action</b>	Ensure that all EIS resources used in the transaction can communicate with the adapter. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0117.4018E</b>	<b>Error while closing transactions at service completion Error:{0}.</b>
<b>Explanation</b>	The specified error occurred while closing the connections involved in a successful transaction.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

<b>ART.0117.4019E</b>	<b>Error while rolling back transaction Error:{0}.</b>
<b>Explanation</b>	The specified error occurred while closing the connections involved in a failed transaction.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0117.4020E</b>	<b>Unable to invoke adapter service {0}. Connection resource {1} not found.</b>
<b>Explanation</b>	WmART failed to locate the connection data node for the specified connection and adapter service.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0117.4021E</b>	<b>Unable to invoke adapter service {0}. Unable to get adapter service template.</b>
<b>Explanation</b>	WmART failed to create an instance of the specified adapter service.
<b>Action</b>	Ensure that the implementation class for the adapter service is installed correctly in the package. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0117.4022E</b>	<b>Unable to invoke adapter service {0}. Unable to get connection state.</b>
<b>Explanation</b>	WmART failed to determine the connection state for the specified adapter service. This will prevent a resource connection from being created.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0117.4023E</b>	<b>Unable to properly handle adapter connection error for connection {0}.</b>
<b>Explanation</b>	WmART was unable to successfully handle an error that occurred on the specified connection while executing a service.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

---

<b>ART.0117.4024E</b>	<b>Unable to invoke adapter service {0}. An error occurred on connection {1}. Unable to recover from connection error.</b>
<b>Explanation</b>	An error occurred in the error handling logic while invoking the specified service. Additional details might appear in adjacent log messages.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0117.4026E</b>	<b>Unable to rollback transaction Error:{0}.</b>
<b>Explanation</b>	The specified error occurred while marking a failed transaction for rollback.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0117.4027E</b>	<b>Unable to create adapter service {0}. Invalid package name {1}.</b>
<b>Explanation</b>	WmART failed to create the specified adapter service because it could not locate the Package object for the specified package name.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0117.4028E</b>	<b>Unable to create adapter service {0}. Invalid service name.</b>
<b>Explanation</b>	WmART failed to create the specified adapter service because the service node name is missing or invalid.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0117.4029E</b>	<b>Unable to create adapter service {0} with connection {1}. Connection not found.</b>
<b>Explanation</b>	WmART AdapterServiceManager failed to create the adapter service because it could not locate the ConnectionDataNode object for the connection.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

- ART.0117.4030E      Unable to create adapter service {0}.**  
**Explanation**      An error occurred while creating the specified adapter service. Additional details should appear in adjacent log messages.  
**Action**              This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0117.4032E      Unable to find adapter service {0}.**  
**Explanation**      WmART failed to locate the namespace node (NSNode) for the adapter service.  
**Action**              This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0117.4033E      Retryable Error while closing transactions at service completion Error:{0}.**  
**Explanation**      The specified retryable run-time exception occurred while completing a successful service invocation.  
**Action**              Ensure that all EIS resources used in the transaction can communicate with the adapter. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0117.4034E      Retryable Error(s) occurred while closing adapter connections.**  
**Explanation**      One or more retryable errors have occurred while closing connections used in a transaction. Additional log messages might be listed.  
**Action**              Ensure that all EIS resources used in the transaction can communicate with the adapter. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0117.4035E      Error while completing service listener Error:{0}.**  
**Explanation**      An error occurred while calling method `com.wm.pkg.art.transaction.ServiceListener.listenComplete`.  
**Action**              This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

---

<b>ART.0117.4036E</b>	<b>Unable to commit transaction. Transaction state:{0} .</b>
<b>Explanation</b>	WmART was unable to commit a transaction because the transaction was in the specified, unexpected state.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0117.4037E</b>	<b>Unable to invoke adapter service {0}. Unable to create Input record.</b>
<b>Explanation</b>	An unexpected exception occurred during the adapter service execution.
<b>Action</b>	Check the Integration Server error log for details on the unexpected exception.
<b>ART.0117.4038E</b>	<b>Unable to delete adapter service {0}.</b>
<b>Explanation</b>	An unexpected exception occurred trying to delete the adapter service.
<b>Action</b>	Check the Integration Server error log for details on the unexpected exception.
<b>ART.0117.4039E</b>	<b>Unable to update adapter service {0}.</b>
<b>Explanation</b>	An unexpected exception occurred trying to update the adapter service.
<b>Action</b>	Check the Integration Server error log for details on the unexpected exception.
<b>ART.0117.4040E</b>	<b>Unable to create adapter service {0}. Adapter service node already exists.</b>
<b>Explanation</b>	It is illegal to create an adapter service with the same folder and node name.
<b>Action</b>	Use a different name for the adapter service and retry the create operation.
<b>ART.0117.4048E</b>	<b>Unable to update adapter service {0}.</b>
<b>Explanation</b>	An exception was encountered while attempting to update the adapter service.
<b>Action</b>	Check the Integration Server error log for details on the original exception.
<b>ART.0117.4049E</b>	<b>Unable to retrieve connection from resource {0}. See error log for details.</b>
<b>Explanation</b>	An exception was encountered while trying to retrieve a connection.
<b>Action</b>	Check the Integration Server error log for details on the original exception.

<b>ART.0118.5000E</b>	<b>Unable to retrieve and process connection properties from pipeline.</b>
<b>Explanation</b>	WmART failed to process a connection's properties. Additional log messages might be listed.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5001E</b>	<b>Error processing connection property {0}. Unable to get property name.</b>
<b>Explanation</b>	WmART failed to locate an expected connection property in the pipeline.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5002E</b>	<b>Error processing connection property {0}. Invalid value entered. The minimum string length is {1}.</b>
<b>Explanation</b>	The size of the specified connection property value is less than the specified minimum size.
<b>Action</b>	Reconfigure the connection from Integration Server Administrator using values that are within the constraints set by the connection.
<b>ART.0118.5003E</b>	<b>Error processing connection property {0}. Invalid value entered. The maximum string length is {1}.</b>
<b>Explanation</b>	The value of the specified property is not valid.
<b>Action</b>	Reconfigure the connection from Integration Server Administrator using values that are within the constraints set by the connection.
<b>ART.0118.5004E</b>	<b>Error processing connection property {0}.</b>
<b>Explanation</b>	An error occurred when converting a connection property value to its internal Java representation. Additional log messages might be listed.
<b>Action</b>	Reconfigure the connection from Integration Server Administrator ensuring that all data entered conforms to the underlying types in the connection class. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

---

<b>ART.0118.5005E</b>	<b>Unable to configure connection properties. Error occurred while processing connection properties.</b>
<b>Explanation</b>	This is a general processing error message. See adjacent log messages for details.
<b>Action</b>	Refer to the Action column for the accompanying messages.
<b>ART.0118.5006E</b>	<b>Unable to get list of connections for adapter type: {0}.</b>
<b>Explanation</b>	An error occurred while retrieving the list of configured connections for the specified adapter.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5007E</b>	<b>Unable to get list of connection types for adapter type: {0}.</b>
<b>Explanation</b>	An error occurred while retrieving the list of connection factories for the specified adapter.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5008E</b>	<b>Unable to get properties for connection {0}.</b>
<b>Explanation</b>	An error occurred while retrieving the configuration details for a specific connection.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5009E</b>	<b>Unable to get connection properties for adapter: {0}, connection type: {1}.</b>
<b>Explanation</b>	An error occurred while retrieving the connection properties for the specified connection factory and adapter.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5010E</b>	<b>Invalid connection name. The connection name must have a valid folder name and node name.</b>
<b>Explanation</b>	An invalid folder and/or connection name was entered on the Integration Server Administrator Configure Connection Type page.
<b>Action</b>	Re-enter the new connection type information making sure that the Folder Name and Connection Name fields have valid entries.

<b>ART.0118.5011E</b>	<b>Unable to create new connection {0}.</b>
<b>Explanation</b>	An error occurred while configuring a new connection type.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5012E</b>	<b>Unable to update connection {0}.</b>
<b>Explanation</b>	An error occurred while editing the connection type.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5013E</b>	<b>Unable to find connection {0}.</b>
<b>Explanation</b>	WmART was unable to locate the specified connection while deleting it.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5014E</b>	<b>Unable to delete connection {0}.</b>
<b>Explanation</b>	An error occurred while deleting a connection.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5015E</b>	<b>Unable to get connection manager properties.</b>
<b>Explanation</b>	An error occurred while getting a list of Connection Manager properties.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5016E</b>	<b>Unable to get configured values for connection manager.</b>
<b>Explanation</b>	An error occurred while processing Connection Manager property values.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

---

<b>ART.0118.5017E</b>	<b>Error occurred while getting connection manager properties.</b>
<b>Explanation</b>	This is a general processing error message. See adjacent log messages for details.
<b>Action</b>	Refer to the Action column for the accompanying messages.
<b>ART.0118.5018E</b>	<b>Error getting connection properties.</b>
<b>Explanation</b>	An error occurred while fetching connection property values.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5019E</b>	<b>Error getting connection metadata. Missing required parameter: adapterTypeName.</b>
<b>Explanation</b>	WmART was unable to determine the adapter type name while processing a connection's metadata.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5020E</b>	<b>Unable to process connection properties. Internal error.</b>
<b>Explanation</b>	WmART failed to set properties for a connection node. The expected connection form fields were not found in the pipeline.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5021E</b>	<b>Unable to process connection properties. Internal error.</b>
<b>Explanation</b>	WmART failed to get properties for a connection node. The expected connection form fields were not found in the pipeline.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5022E</b>	<b>Cannot create connection {0}. Adapter type {1} does not exist.</b>
<b>Explanation</b>	WmART failed to start the specified connection because it was unable to locate the specified adapter type.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

<b>ART.0118.5023E</b>	<b>Unable to configure connection manager. No connection manager properties provided.</b>
<b>Explanation</b>	WmART was unable to validate Connection Manager properties because they were null.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5024E</b>	<b>Unable set connection {0} state to {1}. Invalid state specified.</b>
<b>Explanation</b>	WmART was unable to modify the connection's state because the intended state is missing or invalid.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5025E</b>	<b>Unable to enable connection {0}.</b>
<b>Explanation</b>	This is a general processing error message. See adjacent log messages for details.
<b>Action</b>	Refer to the Action column for the accompanying messages.
<b>ART.0118.5026E</b>	<b>Unable to stop connection {0}.</b>
<b>Explanation</b>	This is a general processing error message. See adjacent log messages for details.
<b>Action</b>	Refer to the Action column for the accompanying messages.
<b>ART.0118.5027E</b>	<b>Unable to enable connection {0}. Connection is already enabled or is being shutdown.</b>
<b>Explanation</b>	WmART is enabling a connection that is not currently in a disabled state.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5028E</b>	<b>Unable to shutdown connection{0}. Connection is already disabled or in the process of being shutdown.</b>
<b>Explanation</b>	WmART is attempting to shut down a connection that is not currently in an enabled state.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

---

<b>ART.0118.5029E</b>	<b>Unable to disable connection {0}. Connection is already disabled.</b>
<b>Explanation</b>	WmART is attempting to disable a connection that is already disabled.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5030E</b>	<b>Unable to create connection {0}. Package {1} does not exist.</b>
<b>Explanation</b>	WmART was unable to create the connection node because it could not locate the specified package.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5031E</b>	<b>Unable to delete connection {0}. Internal error.</b>
<b>Explanation</b>	An error occurred while deleting the specified connection.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5032E</b>	<b>Unable to set connection resource properties. Internal error: ConnectionPropertiesBridge not found.</b>
<b>Explanation</b>	WmART failed to create a configured managed connection factory because it could not locate the WmConnectionPropertiesBridge instance needed to set its properties.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5033E</b>	<b>Error disabling connection resources.</b>
<b>Explanation</b>	An error occurred while stopping the connection resources. See adjacent log messages for more details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

<b>ART.0118.5034E</b>	<b>Connection type {0} does not exist in adapter {1}.</b>
<b>Explanation</b>	WmART was unable to locate the specified connection factory in the specified adapter.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5035E</b>	<b>Unable to create connection {0}. Internal error occurred while creating connection factory of type {1}.</b>
<b>Explanation</b>	WmART was unable to create the specified connection factory for the connection. See adjacent log messages for more details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5036E</b>	<b>Unable to configure connection manager.</b>
<b>Explanation</b>	WmART was unable to create a Connection Manager. See adjacent log messages for more details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5037E</b>	<b>Cannot create ResourceAdapterMetaData object. CCI Connection Factory is not an instance of WmConnectionFactory.</b>
<b>Explanation</b>	The method ConnectionDataNodeManager.createCCIConnectionFactory could not get the ResourceAdapterMetaData object for a connection factory.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5040E</b>	<b>Unable to get adapter service templates for connection {0}.</b>
<b>Explanation</b>	WmART failed to locate any adapter service templates for the specified connection.
<b>Action</b>	Do not configure an adapter service with a connection for which no adapter service templates exist. Try another connection.

---

<b>ART.0118.5041E</b>	<b>Unable to get connection status for connection resource {0}.</b>
<b>Explanation</b>	WmART was unable to obtain connection state information for the specified connection.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5042E</b>	<b>Unable to enable connection resource {0}.</b>
<b>Explanation</b>	This is a general processing error message. See adjacent log messages for details.
<b>Action</b>	Refer to the Action column for the accompanying messages.
<b>ART.0118.5043E</b>	<b>Unable to disable connection resource {0}.</b>
<b>Explanation</b>	This is a general processing error message. See adjacent log messages for details.
<b>Action</b>	Refer to the Action column for the accompanying messages.
<b>ART.0118.5044E</b>	<b>Unable to shutdown connection resource {0}.</b>
<b>Explanation</b>	This is a general processing error message. See adjacent log messages for details.
<b>Action</b>	Refer to the Action column for the accompanying messages.
<b>ART.0118.5046E</b>	<b>Unable to get a connection to resource {0}. Resource not available.</b>
<b>Explanation</b>	WmART could not locate a connection factory for the specified connection.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5047E</b>	<b>Unable to get a connection to resource {0}. Internal error occurred while restarting connection.</b>
<b>Explanation</b>	An error occurred while creating the connection.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

- ART.0118.5048E**      **Unable to get adapter service templates for connection resource {0}.**  
**Explanation**      WmART failed to locate any adapter service templates for the connection.  
**Action**              Do not configure an adapter service with a connection for which no adapter service templates exist. Try another connection.
- ART.0118.5049E**      **Unable to reset adapter connection {0}. Connection {1} is not supported.**  
**Explanation**      The method `ConnectionResource.handleAdapterConnectionException` reports that the specified connection class is not derived from `WmConnection`.  
**Action**              This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0118.5050E**      **Unable to reset adapter connection {0}. Unable to configure connection manager.**  
**Explanation**      The method `ConnectionResource.handleAdapterConnectionException` was unable to locate the `ConnectionManager` or `ConnectionManagerPropertiesBridge` for this connection.  
**Action**              This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0118.5051E**      **Unable to reset adapter connection {0}. Adapter type {1} does not exist.**  
**Explanation**      The method `ConnectionResource.handleAdapterConnectionException` was unable to determine the adapter type for this connection.  
**Action**              This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0118.5052E**      **Unable to create connection. Connection resource {0} is restarting.**  
**Explanation**      The method `ConnectionResource.createConnection` has been called against a connection resource in the restarting state.  
**Action**              This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

---

<b>ART.0118.5053E</b>	<b>Unable to get a connection to resource {0}.</b>
<b>Explanation</b>	WmART failed to create a connection because it could not communicate with the back-end connection resource.
<b>Action</b>	Check independently that the target resource is communicating and that it can be reached from the connection. If the condition persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5054E</b>	<b>Unable to reset adapter connection {0}.</b>
<b>Explanation</b>	An error occurred while trying to restart the specified connection. See adjacent log messages for additional details.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5055E</b>	<b>Unable to get adapter service templates for connection resource {0}.</b>
<b>Explanation</b>	The method ConnectionResourceState.getInteractionSpecsSupported failed to locate the ResourceAdapterMetaData associated with specified connection.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5056E</b>	<b>Unable to create connection for connection resource {0}, connection type {1}.</b>
<b>Explanation</b>	The method ConnectionResourceState.createConnection failed to get the Connection object for the specified connection.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5057E</b>	<b>Adapter Runtime was unable to initialize {0} connection resources for the adapter "{1}".</b>
<b>Explanation</b>	com.wm.pkg.art.ns.ConnectionDataNodeManager.startConnectionResources detected failures in starting connection nodes for the specified adapter.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

<b>ART.0118.5058E</b>	<b>Adapter Runtime was unable to stop {0} connection resources for the adapter "{1}".</b>
<b>Explanation</b>	com.wm.pkg.art.ns.ConnectionDataNodeManager.stopConnectionResources detected failures in shutting down connection nodes for the specified adapter.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5059E</b>	<b>Adapter Runtime was unable to stop connection resources for the {0} adapter types.</b>
<b>Explanation</b>	com.wm.pkg.art.ns.ConnectionDataNodeManager.stopAllConnectionResources detected failures in shutting down connection nodes.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5060E</b>	<b>Unable get properties for connection resource {0}.</b>
<b>Explanation</b>	An error occurred while fetching the specified connection's properties.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5061E</b>	<b>Unable to configure Connection Manager: Poolable property not set.</b>
<b>Explanation</b>	WmART failed to determine whether a connection should be pooled.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5062E</b>	<b>Unable to find connection {0}: error {1}.</b>
<b>Explanation</b>	An error was encountered while validating the specified connection.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5063E</b>	<b>Unable to start connection {0}: after {1} attempt(s).</b>
<b>Explanation</b>	The startup of a connection pool has exceeded the maximum number of retries.
<b>Action</b>	Check the Integration Server error log for details on the retryable exception.

---

<b>ART.0118.5064E</b>	<b>Cannot reconfigure connection {0}: it must be disabled first.</b>
<b>Explanation</b>	To update a connection, it must be disabled.
<b>Action</b>	Disable the connection and retry the update operation.
<b>ART.0118.5065E</b>	<b>Cannot delete connection {0}: it must be disabled first.</b>
<b>Explanation</b>	To delete a connection, it must be disabled.
<b>Action</b>	Disable the connection and retry the delete operation.
<b>ART.0118.5066E</b>	<b>Exception encountered processing {0} connection callback method. The {1} operation will proceed.</b>
<b>Explanation</b>	An exception was encountered while executing the specified connection callback method.
<b>Action</b>	Look in the error log for details on the original exception. The callback processing did proceed even though the error was encountered.
<b>ART.0118.5067E</b>	<b>Unknown callback event type received on connection node: {0}</b>
<b>Explanation</b>	An unknown connection callback was made.
<b>Action</b>	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
<b>ART.0118.5068E</b>	<b>Exception encountered processing {0} connection callback method.</b>
<b>Explanation</b>	An exception was encountered while executing the specified connection callback method.
<b>Action</b>	Look in the error log for details on the original exception. When this error is received, the callback processing does not continue.
<b>ART.0118.5069E</b>	<b>Cannot create connection factory for connection {0}. Adapter type {1} does not exist.</b>
<b>Explanation</b>	The adapter associated with this connection is not registered.
<b>Action</b>	Verify the package dependencies are set correctly. Reload the adapter package, and retry the operation.

<b>ART.0118.5070E</b>	<b>Exception encountered creating the connection factory for connection {0}.</b>
<b>Explanation</b>	An exception was encountered creating the connection factory.
<b>Action</b>	Look in the error log for details on the original exception.
<b>ART.0118.5071W</b>	<b>A non-fatal exception was encountered attempting to unregister {0}. The operation will proceed. See the error log for more details.</b>
<b>Explanation</b>	An exception was encountered trying to unregister the connection node.
<b>Action</b>	Look in the error log for details on the original exception. The unregister processing continued.
<b>ART.0118.5072E</b>	<b>Adapter service {0} cannot use connection {1}. The adapter service and connection are from different adapters.</b>
<b>Explanation</b>	The user attempted to set the connection associated with an adapter service; however, the adapter service and connection were not from the same adapter.
<b>Action</b>	Retry the operation using a connection from the same adapter.
<b>ART.0118.5073E</b>	<b>Adapter service {0} cannot use connection {1}. The connection is already being used by a listener.</b>
<b>Explanation</b>	The user attempted to use a connection in an adapter service; however, the connection is already being used by a listener.
<b>Action</b>	Retry the operation using a connection that is not already being used by a listener.
<b>ART.0118.5074E</b>	<b>"{0}" is not a valid connection name for adapter {1}</b>
<b>Explanation</b>	The user attempted to use a connection in a polling notification or listener; however, the connection was not part of the same adapter.
<b>Action</b>	Retry the operation using a connection from the same adapter.
<b>ART.0118.5075E</b>	<b>Listener {0} cannot use connection {1}. The connection is already being used by an adapter service or polling notification.</b>
<b>Explanation</b>	The specified listener cannot use the specified connection because the connection is already being used by a polling notification or an adapter service.
<b>Action</b>	Retry the operation using a connection that is not being used by a polling notification or adapter service.

---

<b>ART.0118.5076E</b>	<b>Polling notification {0} cannot use connection {1}. The connection is already being used by a listener.</b>
<b>Explanation</b>	The user attempted to use a connection in a polling notification; however, the connection is already being used by a listener.
<b>Action</b>	Retry the operation using a connection that is not already being used by a listener.
<b>ART.0118.5077E</b>	<b>Adapter service {0} cannot use connection {1}. The connection does not support this adapter service template.</b>
<b>Explanation</b>	The user attempted to use a connection for an adapter service; however, the connection does not support the adapter service.
<b>Action</b>	Retry the operation using a connection that supports the adapter service.
<b>ART.0118.5078E</b>	<b>Minimum pool size must not be greater than maximum pool size.</b>
<b>Explanation</b>	The user attempted to set the minimum pool size to a value that is greater than the maximum pool size.
<b>Action</b>	Retry the operation specifying a minimum pool size that is lower than the maximum pool size.
<b>ART.0118.5079</b>	<b>Exception encountered while removing {0} connection from Connection cache.</b>
<b>Explanation</b>	An error occurred while invalidating a failed XA transaction.
<b>Action</b>	Make sure that there is connectivity to the adapter backend, and that the connection associated with the transaction is enabled. Check the server logs for transaction details.
<b>ART.0118.5080</b>	<b>Exception encountered while updating connection {0}.</b>
<b>Explanation</b>	An error occurred while updating a connection node from an old version to a new one.
<b>Action</b>	Make sure that the connection parameters are valid. Make sure that the user updating the connection has been assigned the appropriate ACL.
<b>ART.0118.5083</b>	<b>Invalid value {0} specified for {1} property, hence using default value as {2}</b>
<b>Explanation</b>	The value of the watt.art.connection.nodeVersion watt property is invalid. Hence, when creating the connection node, the specified node version is ignored and the default value for node version is used instead.
<b>Action</b>	Make sure the watt.art.connection.nodeVersion property has a valid value. For details, see the Integration Server administration guide.

**AUTH055**            **Did not add user(s) {0}. Password was empty.**

**Explanation**        The Password field requires a value.

**Action**              Enter a valid password.

**BAB.0002.0000E**    **Wrapped Exception:**

**Explanation**        A communication failure occurred between Integration Server and a client resulting in the exception.

**Action**              Verify that the communication parameters are correct. Check the setup for any network issues.

**BAB.0006.0001E**    **CommException: LinkServer closed**

**Explanation**        A client sent a request to Integration Server after a previous connection between the client and Integration Server was closed.

**Action**              Make sure that the client is not designed to send new requests to Integration Server when communication with the server is closed.

**BAD\_AUDIT\_DIRE**    **The value supplied for watt.server.audit.logDir does not identify an existing directory that Integration Server can write to. watt.server.audit.logDir was not changed.**

**Explanation**        The audit log directory was not changed because the watt.server.audit.logDir parameter refers to a directory that either does not exist or Integration Server does not have permission to write to.

**Action**              Specify a directory that exists on the server and that Integration Server can write to. You can specify the full path name, or a relative path in relation to the Integration Server.

**BAD\_SESSION\_ID**    **Invalid or expired session identifier.**

**BAF.0000.0001E**    **No file or properties specified**

**Explanation**        Integration Server encountered an internal error.

**Action**              Contact Software AG Global Support.

**BAF.0000.0002E**    **Illegal set\_mode: {2}**

**Explanation**        Integration Server encountered an internal error.

**Action**              Contact Software AG Global Support.

---

<b>BAF.0000.0003E</b>	<b>FSDirCursor_encode exception</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0000.0004E</b>	<b>A minimum of three log segments required only {2} found</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0000.0005E</b>	<b>Unsupported BlockDevice specified: {2}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0000.0006E</b>	<b>BlockDevice Exception:</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0000.0007E</b>	<b>Unable to open FSData devices</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0000.0008E</b>	<b>Wrong number of Data Extents:{2} != {3}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0000.0009E</b>	<b>Invalid dataMaxExtents specified:{2}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0000.0010E</b>	<b>Invalid indexMaxExtents specified:{2}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.

**BAF.0000.0011E**      **Invalid dataMaxExtents:{2} must be between 1 and {3}**  
**Explanation**      Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support.

**BAF.0000.0012E**      **Invalid indexMaxExtents:{2} must be between 1 and {3}**  
**Explanation**      Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support.

**BAF.0000.0013E**      **Invalid dataThreshold specified:{2}**  
**Explanation**      Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support.

**BAF.0000.0014E**      **Invalid indexThreshold specified:{2}**  
**Explanation**      Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support.

**BAF.0000.0015E**      **Invalid dataThreshold:{2} must be between 50% and 99%**  
**Explanation**      Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support.

**BAF.0000.0016E**      **Invalid indexThreshold:{2} must be between 50% and 99%**  
**Explanation**      Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support.

**BAF.0000.0017E**      **Log offset:{2} inside Superblock**  
**Explanation**      Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support.

**BAF.0000.0018E**      **Log offset:{2} > Meta offset:{3}**  
**Explanation**      Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support.

---

<b>BAF.0000.0019E</b>	<b>Meta offset{2} &gt; Data offset:{3}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0000.0020E</b>	<b>Error during create - Data store already exists</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0000.0021E</b>	<b>Exception during checkDataDevices:</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0000.0022E</b>	<b>Exception during newHashCode:</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0000.0023E</b>	<b>Unknown log type:{2}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0000.0024E</b>	<b>NOT RETURNABLE in finalize:{2}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0000.0025E</b>	<b>Finalizing undestroyed cursor (p={2} d={3})</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0000.0026E</b>	<b>No more null entries after {2} in {3}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.

<b>BAF.0000.0027E</b>	<b>Filesystem full ({2} &lt; {3})</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0000.0028E</b>	<b>Block write failure</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0000.0029E</b>	<b>Unable to locate block of sufficient size</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0000.0030E</b>	<b>Cannot unlink last remaining empty</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0000.0031E</b>	<b>Data Expansion required but Maximum Data Exceeded</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0000.0032E</b>	<b>Index expansion requested but maximum are allocated</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0000.0033E</b>	<b>CreateIndexExtent, unable to alloc block</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0000.0034E</b>	<b>Mismatch:{2} {3} != {4}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.

---

<b>BAF.0000.0046E</b>	<b>Warning {2} failed</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0000.0047E</b>	<b>Notify() on null ref idx={2} hc={3} : {4}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0000.0048E</b>	<b>Transaction has no members:{2}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0000.0072E</b>	<b>Error during open - Log File does not exist</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0000.0073E</b>	<b>Error during create - Log File already exists</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0000.0074E</b>	<b>Error during create - Average Block Size or entries must be specified</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0000.0075E</b>	<b>Error during create - NumEntries exceeds size of integer</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0000.0076E</b>	<b>Error during open - data file segments do not match, input {2}, output {3}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.

**BAF.0000.0102E**      **The FSDData is damaged, see the journal log for details**  
**Explanation**      Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support.

**BAF.0000.0103E**      **FSDData checker. Bad NULL entry chain**  
**Explanation**      Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support.

**BAF.0001.0035E**      **Fatal Runtime Exception:{2}**  
**Explanation**      The Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support.

**BAF.0001.0036E**      **No open TXN for dirty entry**  
**Explanation**      The Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support.

**BAF.0001.0037E**      **Filesystem is in an invalid state**  
**Explanation**      The Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support.

**BAF.0001.0038E**      **Improper deleted type:{2}**  
**Explanation**      The Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support.

**BAF.0001.0039E**      **Can't unlink:{2}**  
**Explanation**      The Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support.

**BAF.0001.0040E**      **Can't add first empty back to empty list**  
**Explanation**      The Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support.

---

<b>BAF.0001.0041E</b>	<b>FreeBytes mismatch:{2} != {3}</b>
<b>Explanation</b>	The Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0001.0042E</b>	<b>Out of order merge:{2} &amp; {3}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0001.0043E</b>	<b>First null entry cannot be null</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0001.0044E</b>	<b>First empty entry cannot be null</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0001.0045E</b>	<b>Transaction has no members:{2}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0001.0049E</b>	<b>Cannot use destroyed cursor</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0001.0050E</b>	<b>EndTXN called outside of a transaction</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0001.0051E</b>	<b>AbortTXN called outside of a transaction:{2}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.

**BAF.0001.0052E**      **Log is not open**  
**Explanation**      Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support.

**BAF.0001.0053E**      **Log is not closed**  
**Explanation**      Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support.

**BAF.0001.0054E**      **Log is smaller than max block ({2} < {3})**  
**Explanation**      Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support.

**BAF.0001.0055E**      **Transaction larger than total log**  
**Explanation**      Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support.

**BAF.0001.0056E**      **Cursors already @ 0:{2}**  
**Explanation**      Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support.

**BAF.0001.0057E**      **References negative!:{2}**  
**Explanation**      Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support.

**BAF.0001.0058E**      **Entry is already unlinked!:{2}**  
**Explanation**      Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support.

**BAF.0001.0059E**      **No backup to revert to:{2}**  
**Explanation**      Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support.

---

<b>BAF.0001.0060E</b>	<b>Type mismatch: {2} != {3} on {4}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0001.0061E</b>	<b>Data length ({2}) != expected length:{3}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0001.0076E</b>	<b>Illegal state change from {2} to {3}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0002.0000E</b>	<b>Wrapped Exception:</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0003.0070E</b>	<b>TransactionException: Wait to start transaction interrupted</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0003.0071E</b>	<b>TransactionException: Resource already in a transaction</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0003.0072E</b>	<b>TransactionException: Wait to start transaction not allowed</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0004.0062E</b>	<b>Data: Unable to get cursor lock</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.

<b>BAF.0004.0063E</b>	<b>Data: Cannot get key, cursor is unpositioned</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0004.0064E</b>	<b>Data: Cannot get value, cursor is unpositioned</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0004.0065E</b>	<b>Data: Cannot get value reference, cursor is unpositioned</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0004.0066E</b>	<b>Data: Cursor is unpositioned</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0004.0067E</b>	<b>Data: Unable to delete: {2}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0004.0068E</b>	<b>Data: Can not clone a destroyed cursor</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0004.0069E</b>	<b>Data: Referenced object has been deleted</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0005.0077E</b>	<b>IOException: No Properties provied to JDBCBlockDev</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.

---

<b>BAF.0005.0078E</b>	<b>IOException: No JDBC Driver provided to JDBCBlockDev</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0005.0079E</b>	<b>IOException: No URL provided to JDBCBlockDev</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0005.0080E</b>	<b>IOException: Unable to create table:{2}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0005.0081E</b>	<b>IOException: {2} JDBCBlockDevice doesn't support Logical Devices - offset:{3}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0005.0082E</b>	<b>IOException: {2} Attempted to write past final segment: {3}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0005.0083E</b>	<b>IOException: {2} Attempted to read past final segment: {3}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0005.0084E</b>	<b>IOException: {2} Blob length: {3} != Segment size:{4}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0005.0085E</b>	<b>IOException: {2} Not Found:</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.

<b>BAF.0005.0086E</b>	<b>IOException: {2} Unable to Connect - Retries Exhausted</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0005.0087E</b>	<b>IOException: All component files must be the same length</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0005.0088E</b>	<b>IOException: Invalid logical position specified</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0005.0089E</b>	<b>IOException: Read error</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0005.0090E</b>	<b>IOException: Write error</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0005.0091E</b>	<b>IOException: Invalid Physical position</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0005.0092E</b>	<b>IOException: SplitExtent failed - Extent not found:{2}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0005.0093E</b>	<b>IOException: Unable to allocate new IBlockDevice in Device Group</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.

---

<b>BAF.0005.0094E</b>	<b>IOException: Invalid Log Region detected - Timestamp mismatch</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0005.0095E</b>	<b>IOException: CompositeBlockDevice read error</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0005.0096E</b>	<b>IOException: missing {2} properties file</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0005.0097E</b>	<b>IOException: Illegal mode {2}. Must be 'rw' or 'r'</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0005.0098E</b>	<b>IOException: block device has 0 length</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0005.0099E</b>	<b>IOException: Unable to read {2} bytes</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0005.0100E</b>	<b>IOException: Unable to allocate write buffer</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAF.0005.0101E</b>	<b>IOException: Native library unavailable</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.

- BAQ.0002.0000**      **Wrapped Exception:**
  
- BAQ.0003.0001**      **TransactionException: Resource already in a transaction**
  
- BAR.0001.1401**      **RuntimeException: unsupported cursor {2}**
  
- BAR.0002.0000**      **Wrapped Exception:**
  
- BAR.0005.1600**      **RepoDirCodec: DecodeParms must be called before decode**
  
- BAR.0005.1601**      **RepoDirCodec: Unserializable repo object**
  
- BAR.0005.1602**      **RepoDirCodec: Repo Must be Standalone**
  
- BAR.0006.1700**      **CommException: sendRequest() failed**
  
- BAR.0006.1701**      **CommException: ConnectionServer closed**
  
- BAR.0006.1702**      **CommException: Missing keyword:{2}**
  
- BAR.0010.0001**      **Directory: insert exception:**
  
- BAR.0010.0002**      **Directory: update exception:**
  
- BAR.0010.0003**      **Directory: rename exception:**
  
- BAR.0010.0004**      **Directory: get queue failed, invalid object type**

---

BAR.0010.0005	Directory: entry version "{2}" does not exist for entry "{3}"
BAR.0010.0007	Directory: delete exception:
BAR.0010.0008	Directory: "{2}" already exists
BAR.0010.0009	Directory: entry "{2}" is not a symbolic link
BAR.0010.0011	Directory: object has been destroyed
BAR.0010.0012	Directory: null not allowed in compound directory path expression
BAR.0010.0013	Directory; key "{2}" not found
BAR.0010.0014	Directory: key "{2}" is not a repository directory
BAR.0010.0015	Directory: "{2}" can not be versioned
BAR.0010.0016	Directory: illegal state, directory may have been destroyed
BAR.0010.0017	Directory: "{2}" is an invalid symbolic link target
BAR.0010.0018	Directory: "{2}" is a repository directory and an invalid symbolic link target
BAR.0010.0019	Directory: "{2}" is a repository IData object and an invalid symbolic link target
BAR.0010.0021	Directory: new key {2} can not be a compound key

- BAR.0010.0022      Directory: RepoQueue {2} can not be versioned**
  
- BAR.0010.0023      Directory: "{2}" is a symbolic link and is invalid as a symbolic link target**
  
- BAR.0010.0024      Directory: Entry {2} not versioned**
  
- BAR.0010.0025      Directory: reconnect attempt failed**
  
- BAR.0010.0026      Directory: get queue failed, object is null**
  
- BAR.0010.0027      Directory: can not be target of an update for entry {2}**
  
- BAR.0010.0028      Directory: invalid version number {2}**
  
- BAR.0010.0029      Directory: invalid relative version number {2}**
  
- BAR.0010.0030      Directory: cannot delete current version for entry {2}**
  
- BAR.0010.0031      Directory: illegal transaction state, {2} not allowed in active transaction**
  
- BAR.0010.0032      Directory: testAndSet failed for entry {2}:**
  
- BAR.0010.0033      Directory: testAndSet failed for entry {2} - Invalid Entry Type**
  
- BAR.0010.0034      Directory: key "{2}" is not a repository stream**
  
- BAR.0010.0035      Directory: internal error, unknown repository container type, {2}**

---

BAR.0011.0100	Queue: constructor failure:
BAR.0011.0101	Queue: enqueue failure:
BAR.0011.0102	Queue: dequeue failure:
BAR.0012.0200	Stream: Invalid length key type: {2}
BAR.0012.0201	Stream: DataException: {2}
BAR.0012.0202	Stream: Invalid Object: {2} missing {3}
BAR.0012.0203	Stream: Invalid Segments key type: {2}
BAR.0012.0204	Stream: Segment {2} not found in {3}
BAR.0012.0205	Stream: Invalid Status key type: {2}
BAR.0012.0206	Stream: EOF - Pending stream
BAR.0012.0207	Stream: {2} already open for output
BAR.0012.0208	Stream: {2} closed
BAR.0012.0209	Stream: Error Writing byte[] to OutputStream: {2}
BAR.0012.0210	Stream: Error Flushing OutputStream: {2}

- BAR.0012.0211**      **Stream: Error Closing OutputStream: {2}**
  
- BAR.0012.0212**      **Stream: Error Reading InputStream: {2}**
  
- BAR.0012.0213**      **Stream: Error Closing InputStream: {2}**
  
- BAR.0013.0300**      **NameParser: missing component key**
  
- BAR.0013.0301**      **NameParser: invalid key syntax: "{2}"**
  
- BAR.0013.0302**      **NameParser: index missing from key "{2}"**
  
- BAR.0013.0303**      **NameParser: index not numeric "{2}"**
  
- BAR.0013.0304**      **NameParser: bad array index syntax "{2}"**
  
- BAR.0014.0400**      **Illegal argument: Directory object cannot be stored**
  
- BAR.0014.0403**      **Illegal argument: Key must be specified**
  
- BAR.0014.0404**      **Illegal argument: Action must be ADD, DELETE, or CHANGE**
  
- BAR.0015.0500**      **Session: Logon required**
  
- BAR.0015.0505**      **Session: RepoStream object in use, RepoAPI calls not allowed**
  
- BAR.0015.0510**      **Session: Invalid logon URL "{2}" specified**

---

<b>BAR.0015.0511</b>	<b>Session: No default server specified</b>
<b>BAR.0015.0515</b>	<b>Session: Active repository session, logon not allowed</b>
<b>BAR.0015.0516</b>	<b>Session: Internal Error, invalid Transaction Resource object</b>
<b>BAR.0015.0518</b>	<b>Session: Duplicate logon not allowed</b>
<b>BAR.0015.0519</b>	<b>Session: Session not logged on</b>
<b>BAR.0015.0520</b>	<b>Session: Session disabled due to LUW timeout</b>
<b>BAR.0015.0521</b>	<b>Session: Previous LUW timeout still in progress, try again later</b>
<b>BAR.0016.0600</b>	<b>Internal Error: local server connection config invalid</b>
<b>BAR.0016.0601</b>	<b>Internal Error: during server initialization exception:</b>
<b>BAR.0016.0603</b>	<b>Internal Error: connection to repository server failed, missing remote refid</b>
<b>BAR.0016.0604</b>	<b>Internal Error: Repository server shutdown failed:</b>
<b>BAR.0016.0605</b>	<b>Internal Error: Repository server is not the primary server</b>
<b>BAR.0017.0700</b>	<b>RepoStore: Internal Error creating Repo Server object:</b>
<b>BAR.0017.0701</b>	<b>RepoStore: Unable to initialize Repository backing store</b>

- BAR.0017.0702      RepoStore: Repository server has been destroyed**
  
- BAR.0017.0703      RepoStore: Repository backing store not initialized**
  
- BAR.0017.0704      RepoStore: Missing 'persiststore' config parm**
  
- BAR.0018.0900      RepoConnection: Secondary server could not find primary repository server**
  
- BAR.0018.0901      RepoConnection: Could not find primary repository server: {2}**
  
- BAR.0018.0904      RepoConnection: Reconnect failed, no remote server cluster connection information available**
  
- BAR.0019.1100      Transaction: Resource already participating in a transaction**
  
- BAR.0019.1101      Transaction: Illegal transaction state, transaction destroyed**
  
- BAR.0019.1102      Transaction: Illegal transaction state, session mismatch**
  
- BAR.0019.1103      Transaction: Illegal transaction state, IDataSharedCuror Transactions not supported**
  
- BAR.0019.1104      Transaction: TransactionException: Cursor has been destroyed**
  
- BAR.0020.1200      SharedCursor: illegal state, cursor destroyed**
  
- BAR.0020.1201      SharedCursor: reconnect attempt failed**
  
- BAR.0020.1202      SharedCursor: invalid resource specified**

---

BAR.0020.1203	SharedCursor: Reconnect Exception detected
BAR.0020.1204	SharedCursor: Can not get key, cursor is unpositioned.
BAR.0020.1205	SharedCursor: Can not get value, cursor is unpositioned.
BAR.0021.1300	Queue: reconnect attempt failed
BAR.0021.1301	Queue: illegal state, queue destroyed
BAR.0021.1302	Queue: object has been destroyed
BAR.0021.1303	Queue: Repository Queue entry corrupted
BAR.0022.1400	Data: illegal state, IData destroyed
BAR.0023.1500	Migration: export not implemented in RepoMigrate, use Repov2Migrate or Repov3Migrate to export your specific Repo version
BAR.0023.1501	Migration: exception:{2}
BAR.0023.1502	Migration: Error During Import, probably Coder mismatch between Export and Import utilities: exception:{2}
BAR.0023.1503	Migration: import not implemented in {2}, use RepoMigrate to import
BAS.0123.0004E	FSDData checker repair attempted. Zero length file deleted. {0}
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.

- BAS.0123.0007E**      **FSDData checker. {0} entrys not in any chain.**  
**Explanation**      Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support.
- BAS.0123.0008E**      **FSDData checker repair attempted. Bad NULL list entry removed. {0}**  
**Explanation**      Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support.
- BAS.0123.0009E**      **FSDData checker. Entry in {0} list has bad prev pointer. {1}**  
**Explanation**      Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support.
- BAS.0123.0010E**      **FSDData checker. Entry in {0} list has wrong type. {1} != {2} {3}**  
**Explanation**      Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support.
- BAS.0123.0011E**      **FSDData checker. Duplicate entry in {0} list. {1}**  
**Explanation**      Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support.
- BAS.0123.0012E**      **FSDData checker. Entry in {0} list contains bad reference count. {1}**  
**Explanation**      Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support.
- BAS.0123.0013E**      **FSDData checker. Data node has wrong type. {0}**  
**Explanation**      Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support.
- BAS.0123.0014E**      **FSDData checker. Hash tree node has wrong type. {0}**  
**Explanation**      Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support.

---

<b>BAS.0123.0015E</b>	<b>FSDData checker. Free byte count is wrong. {0} != {1}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAS.0123.0016E</b>	<b>FSDData checker repair attempted. {0} orphaned NULLs recovered.</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAS.0123.0017E</b>	<b>FSDData checker. Entry is in multiple chains. {0}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAS.0123.0018E</b>	<b>FSDData checker. Repair attempted - full check will be run again.</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAS.0123.0019E</b>	<b>FSDData checker. Attempting to recover orphaned NULL and EMPTY entries.</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAS.0123.0021E</b>	<b>FSDData checker. Dir entry has bad last node pointer. {0}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAS.0123.0022E</b>	<b>FSDData checker repair attempted. Bad EMPTY list entry removed. {0}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>BAT.0000.0001</b>	<b>duplicate endpoint id {2}</b>

- BAT.0000.0002**      **endpoint {2} not found.**
  
- BAT.0000.0003**      **endpoint {2} can not be deleted it has producers/consumers with active or pending messages.**
  
- BAT.0000.0004**      **duplicate producer id {2}**
  
- BAT.0000.0005**      **producer {2} not found.**
  
- BAT.0000.0006**      **producer {2} can not deleted, it has active or pending messages.**
  
- BAT.0000.0007**      **duplicate consumer id {2}**
  
- BAT.0000.0008**      **consumer {2} not found.**
  
- BAT.0000.0009**      **consumer {2} can not deleted, it has active or pending messages.**
  
- BAT.0000.0010**      **duplicate message store id {2} for producer {3}**
  
- BAT.0000.0011**      **consumer {2} message store id {3} not found.**
  
- BAT.0000.0012**      **consumer {2} message store {3} can not deleted, it has active or pending messages.**
  
- BAT.0000.0013**      **no active transaction for message store id {2} for parent container id {3}**
  
- BAT.0000.0014**      **transactions not enabled for message store id {2} for parent container id {3}**
  
- BAT.0000.0015**      **method disabled because transactions are enabled for message store id {2} for parent container id {3}**

---

BAT.0000.0016	consumer {2} message store {3} this method requires transactions to be enabled.
BAT.0000.0017	duplicate sequence number {2} for message id {3} in store id {4} in parent container id {5}
BAT.0000.0018	message id {2} not found in message store id {3} for parent container id {4}
BAT.0000.0019	out of sequence message seq {2}, last seq {3} id {4} in store id {5} in parent container id {6}
BAT.0000.0020	argument arrays must be same length, message store id {2} for parent container id {3}
BAT.0000.0021	invalid timeout value {2}, must be > 0
BAT.0000.0022	invalid message sequence number {2}, must be >= 0
BAT.0000.0023	invalid message acknowledge mode {2}
BAT.0000.0024	message id can not be null, {2}
BAT.0000.0025	illegal state change request from {2} to {3}
BAT.0000.0026	{2} {3} has been closed
BAT.0000.0027	thread has been interrupted
BAT.0000.0028	method [{2}] is not allowed from a rejected message handler.

- BAT.0000.0029      the transient store type {2} specified could not be initialized.
  
- BAT.0000.0030      IData backing store is null, required
  
- BAT.0000.0031      IDATASTORE type requires a transacted IData implementation
  
- BAT.0000.0032      duplicate message for store id {2} in parent container id {3}
  
- BAT.0000.0033      {2} {3} is already started.
  
- BAT.0000.0034      {2} {3} has been stopped.
  
- BAT.0000.0035      Invalid reference: MessageStore[{2}] is null.
  
- BAT.0000.0036      A ISimpleQueueProducer has already been created for this SimpleQueue
  
- BAT.0000.0037      A ISimpleQueueConsumer has already been created for this SimpleQueue
  
- BAT.0000.0038      Cannot ack not allowed for a zero-or-more SimpleQueue
  
- BAT.0000.0039      Cannot nack not allowed for a zero-or-more SimpleQueue
  
- BAT.0000.0040      SimpleQueue {2} not found.
  
- BAT.0000.0041      SimpleQueue {2} can not be deleted it is not empty.
  
- BAT.0002.0000      Wrapped Exception:

---

BAT.0127.0001	Recoverable Error skipped because warnonopen = continue. Db:{0} Error:{1}
BAT.0127.0002	Recoverable Error encountered but warnonopen = fail. Db:{0} Error:{1}
BAT.0127.0003	Error deleting damaged data file. Db:{0} Error:{1}
BAT.0127.0004	Error renaming damaged data file. Db:{0} Error:{1}
BAT.0127.0005	Error re-creating damaged data file. Db:{0} Error:{1}
BAT.0127.0006	Damaged data file renamed. Db:{0} renamed:{1}
BAT.0127.0007	Damaged data file deleted. Db:{0}
BAT.0127.0008	Damaged data file re-created. Db:{0}
BAT.0127.0009	Error during checkDataDevice. Db:{0} Error:{1}
BAT.0127.0010	Damaged data file detected. Db:{0} Error:{1}
BAT.0127.0011	Data file resize required. Db:{0}
BAT.0127.0012	Error cleaning up resized Data file. Db:{0} Error:{1}
BAT.0127.0013	Error creating resized Data file. Db:{0} Error:{1}
BAT.0127.0014	Error copying resized Data file. Db:{0}

BAT.0127.0015      Error renaming original data file. Db:{0} Error:{1}

BAT.0127.0016      Error closing resized data file. Db:{0} Error:{1}

BAT.0127.0017      Error renaming resized data file. Db:{0} Error:{1}

BAT.0127.0018      Error restoring original data file. Db:{0} Error:{1}

BAT.0127.0019      Error cleaning up copied Data file. Db:{0} Error:{1}

BAT.0127.0020      Error closing original Data file. Db:{0} Error:{1}

BAT.0127.0021      Data file resize completed. Db:{0}

BAT.0127.0022      Resized Data file recovered. Db:{0}

**BEHAVIOUR\_IS\_INVALID** – Behaviour should be one of client or server

**BROKER\_NOT\_REACHABLE** – Broker not connected.

**CACHE\_CACHE\_MANAGER\_NOT\_INITIALIZED** – Cache manager {0} is not loaded or initialized.

**CACHE\_CACHE\_NOT\_FOUND** – Cache {1} for cache manager {0} not found.

**CACHE\_CANNOT\_ACQUIRE\_READ\_LOCK** – Could not acquire a read lock for key {0} in cache {1} contained within the cache manager {2}.

**CACHE\_CANNOT\_ACQUIRE\_WRITE\_LOCK** – Could not acquire a write lock for key {0} in cache {1} contained within the cache manager {2}.

**CACHE\_INVALID\_INPUT** – Invalid value for input parameter {0}. Error:{1}.

**CACHE\_MISSING\_PARAM\_NAME** – Missing required parameter: {0}

**CANNOT\_CREATE\_FOREACH** – Cannot make the For Each from: {0} to: {1}

**CAN\_NOT\_RESUME** can not resume due to state:

**CAN\_NOT\_SUSPEND** can not suspend due to state:

**CLIENT\_HTTP\_EXP3** do not use: data.string, data.stream or data.mimeStream on a DELETE

**CLIENT\_HTTP\_KERBEROS\_DELEGATION\_NO\_CREDENTIALS** – Kerberos delegatable credentials do not exist.

**Explanation**            Delegatable credentials do not exist. Delegation is set to Kerberos without requesting for a delegatable token in the previous (parent) pub.client:http call.

**Action**                 Ensure that the delegation input in the pub.client:http is set only after the requestDelegatableToken is set to true in the previous (parent) pub.client:http call.

**CLIENT\_HTTP\_KERBEROS\_PRINCIPALPASSWORD\_DELEGATION\_BOTHREQ** – Either both Kerberos clientPrincipal and clientPassword must be supplied or both should be left blank.

**CLIENT\_HTTP\_KERBEROS\_SPNFORM\_DELEGATION\_FORMAT** – Kerberos service principal name form must be either username or hostbased.

**CLIENT\_HTTP\_KERBEROS\_SPN\_FORM\_DELEGATION\_BOTHREQ** – Either both Kerberos service principal name and service principal name form must be supplied or both should be left blank.

**CLIENT\_INPUT\_NOT\_BYTE\_ARRAY** – Input {0} must be a byte array

**CLIENT\_WEBSOCKET\_MISSING\_INPUT – {0} is a required input**

**CLIENT\_WEBSOCKET\_WRONG\_URL – url is required and must begin with ws or wss**

**CURRENT\_EVENT\_IS\_NOT\_A\_START\_ELEMENT – Current event is not a START\_ELEMENT**

**CURRENT\_STATE\_NOT\_START\_ELEMENT – Current state not START\_ELEMENT**

**CURRENT\_STATE\_NOT\_START\_ELEMENT\_END\_ELEMENT\_OR\_ENTITY\_REFERENCE – Current state not START\_ELEMENT, END\_ELEMENT or ENTITY\_REFERENCE**

**CURRENT\_STATE\_NOT\_START\_ELEMENT\_OR\_END\_ELEMENT – Current state not START\_ELEMENT or END\_ELEMENT**

**DEFAULT\_ILIVE\_TRUSTSTORE\_DESCRIPTION – Default truststore alias for webMethods Cloud.**

**DEPLOYER\_PACKAGE\_DISALLOW\_INSTALL\_ON\_ENABLED – Package"{0}" will not be deployed because deploying to an enabled package is disallowed**

**DEPLOYER\_PACKAGE\_NOT\_ENABLED – The deployed package {0} is disabled. Check the Integration Server logs for any errors that may have occurred during deployment. If the package contains Adapter or .NET assets for which variable substitution parameters were specified, you must perform the variable substitutions manually on the Integration Server for the changes to take effect.**

**DEPLOYER\_PACKAGE\_SERVICE\_EXECUTION\_CHECK – Package"{0}" will not be deployed because at least one of the Package services is in execution**

<b>DISABLEDE</b>	<b>Messaging Synchronizer has been disabled</b>
<b>Explanation</b>	The Broker Synchronizer has been disabled.
<b>Action</b>	Check the status of the Broker and the Broker Settings in Integration Server Administrator.

**DUPE\_EVENT\_TYPE\_NAME** – Document type {0} has failed to load. Duplicate Broker document type name {1} is also referenced by {2}

**DUP\_XID\_RESOURCE\_UPDT** – Failed attempt to store resource status={0} for xid={1}, resource={2}. XID not found.

**DUP\_XID\_START** Transaction start for xid={0} failed. Transaction for this xid has already been started.

**EDA\_EID\_ROOT\_NODE** Parameter xmldata must be XML with a root node element named "Event {http://namespaces.softwareag.com/EDA/Event}".

**EGDOS002E** Error occurred while updating global Denial of Service options for Enterprise Gateway rules. Details: {0}.

**Explanation** Enterprise Gateway Server could not update the global Denial of Service options for Enterprise Gateway rules for the reason indicated.

**Action** Ensure that the correct input parameters are provided to the service. Then, try to update the global Denial of Service options again.

**EGDOS006E** Error occurred while updating Denial of Service by IP address options for Enterprise Gateway rules. Details: {0}.

**Explanation** Enterprise Gateway Server could not update DoS by IP address options for Enterprise Gateway rules for the reason indicated.

**Action** Check the reason detailed in the message and take appropriate corrective action.

**EGMAPP02E** Error occurred while updating device types. Details: {0}.

**Explanation** Enterprise Gateway Server could not update the list of device types. Possible reasons are: The device name is too long (exceeds 255 characters) or contains special characters; the device type was deleted by another user while the current user tried to update the list; the device type is specified in one or more Enterprise Gateway rules; or there was a problem saving the device types to the Enterprise Gateway rules configuration file.

**Action** If you are adding a device type, use the correct format. If you are deleting a device type and the device type is used in one or more Enterprise Gateway rules, remove or change the condition in the mobile application protection filter where the device type is specified.

<b>EGMAPP04E</b>	<b>Error occurred while updating mobile applications. Details: {0}.</b>
<b>Explanation</b>	Enterprise Gateway Server could not update the list of mobile applications. Possible reasons are: The application name is too long (exceeds 255 characters) or contains special characters; the application was deleted by another user while the current user tried to update the list; the application is specified in one or more rules; or there was a problem saving the application to the Enterprise Gateway rules configuration file.
<b>Action</b>	If you are adding a mobile application, use the correct format. If you are deleting a mobile application and the application is used in one or more Enterprise Gateway rules, remove or change the condition in the mobile application protection filter where the application is specified.
<b>EGRULE002E</b>	<b>Enterprise Gateway rule could not be created. Details: {0}.</b>
<b>Explanation</b>	Enterprise Gateway Server could not create the Enterprise Gateway rule for the reason indicated.
<b>Action</b>	Ensure that the correct input parameters are provided to the rule creation service.
<b>EGRULE004E</b>	<b>Enterprise Gateway rule could not be updated. Details: {0}.</b>
<b>Explanation</b>	Enterprise Gateway Server could not update the Enterprise Gateway rule for the reason indicated.
<b>Action</b>	Ensure that the correct input parameters are provided to the rule update service.
<b>EGRULE006E</b>	<b>Enterprise Gateway rule could not be deleted. Details: {0}.</b>
<b>Explanation</b>	Enterprise Gateway Server could not delete the Enterprise Gateway rule for the reason indicated.
<b>Action</b>	Ensure that the correct input parameters are provided to the rule deletion service.
<b>EGRULE007E</b>	<b>A rule violation occurred for Enterprise Gateway rule "{0}". Filter: "{1}", message: "{2}", request IP: {3}, request URL: {4}, request time: {5}.</b>
<b>Explanation</b>	Enterprise Gateway Server could not process the request because an Enterprise Gateway rule violation occurred.
<b>Action</b>	Either change the rule filter settings or modify the request so a rule violation does not occur.
<b>EGRULE008E</b>	<b>A rule violation occurred for Enterprise Gateway rule "{0}". Request IP: {1}, request URL: {2}, request time: {3}.</b>
<b>Explanation</b>	Enterprise Gateway Server could not process the request because an Enterprise Gateway rule violation occurred.
<b>Action</b>	Either change the rule settings or modify the request so a rule violation does not occur.

**ELEMENT\_IS\_NOT\_A\_TEXT\_ONLY\_ONE** – Element is not a text-only one

**ELEMENT\_TEXT\_CONTENT\_MAY\_NOT\_CONTAIN\_START\_ELEMENT** – element text content may not contain START\_ELEMENT

**EMPTY\_KEYSTORE\_ALIAS** – Alias is not specified

**EMPTY\_KEYSTORE\_LOCATION** – Location is not specified

**EMPTY\_KEYSTORE\_PROVIDER** – Provider is not specified

**EMPTY\_KEYSTORE\_TYPE** – Type is not specified

**ERROR\_DRIVER\_CONTAINS\_INVALID\_CHARSI** – Driver alias definition cannot be created. Driver alias name contains one or more invalid characters.

**ERROR\_POOL\_CONTAINS\_INVALID\_CHARSI** – Pool alias cannot contain any of these characters:  
{0}

**ER\_SEND\_MISSING\_EVENT\_PARAM** – Missing required parameter: {0}

**EXCEPTION\_PARSING\_HELP\_CONTEXT\_FILE** – Exception occurred while parsing the file doc/OnlineHelp/context.xml from WmRoot package: {0}

**EXPECTED\_LOCAL\_NAME\_NOT\_MATCHING** – Expected local name '{0}'; current local name '{1}'

**EXPECTED\_NON\_NULL\_LOCAL\_NAME** – Expected non-null local name, but current token not a START\_ELEMENT, END\_ELEMENT or ENTITY\_REFERENCE (was {0})

**FAC+."+AUTO\_CREATE\_CONNECTION\_FACTORY** – Automatically creating JMS Connection Factory {0} for JMS connection alias {1}.

**FAC+."."+AUTO\_CREATE\_DESTINATION – Automatically creating JMS Destination {0} for JMS connection alias {1}.**

**FAC+."."+ERROR\_READING\_SJO\_FILE\_FOR\_CONNECTIONFACTORY – Error occurred during lookup for SonicMQ ConnectionFactory object from "{0}".**

**FAC+."."+ERROR\_READING\_SJO\_FILE\_FOR\_DESTINATION – Error occurred during lookup for SonicMQ Destination object from "{0}".**

**FAC+."."+EXCEPTION\_DURING\_HOT\_DEPLOYMENT – Exception {0} occurred while handling Hot Deployment notification for trigger {1}**

**FAC+."."+JMS\_STARTING – JMS subsystem is starting.**

**FAC+."."+PRODUCER\_RETRY\_FAILED – Producer Retry for destination {0} alias {1} failed after {2} attempt(s): {3}**

**FAC+."."+PRODUCER\_RETRY\_FAILED\_ATTEMPT – Producer Retry for destination {0} alias {1} failed retry attempt {2}: {3}**

**FAC+."."+PRODUCER\_RETRY\_INTERRUPT\_DISABLED – Producer Retry for destination {0} alias {1} has been interrupted because the alias is now disabled.**

**FAC+."."+PRODUCER\_RETRY\_INTERRUPT\_DISCONNECTED – Producer Retry for destination {0} alias {1} has been interrupted because the connection is closed.**

**FAC+."."+PRODUCER\_RETRY\_INTERRUPT\_SHUTDOWN – Producer Retry for destination {0} alias {1} has been interrupted because the server is shutting down.**

**FAC+."."+PRODUCER\_RETRY\_NOTRUN\_DISABLED – Producer Retry not attempted for destination {0} alias {1} because the alias is disabled: {2}**

**FAC+."."+PRODUCER\_RETRY\_NOTRUN\_DISCONNECTED – Producer Retry not attempted for destination {0} alias {1} because the connection is closed: {2}**

**FAC+."."+PRODUCER\_RETRY\_NOTRUN\_SHUTDOWN – Producer Retry not attempted for destination {0} alias {1} because the server is shutting down: {2}**

**FAC+."."+PRODUCER\_RETRY\_STARTED – Attempting Producer Retry for destination {0} alias {1}. Max Retry Attempts: {2}, Retry Interval: {3}, Error: {4}**

**FAC+."."+PRODUCER\_RETRY\_SUCCESS – Producer Retry for destination {0} alias {1} was successful after {2} attempt(s).**

**FAC+."."+REGISTER\_TRIGGER\_FOR\_HOT\_DEPLOYMENT – Registering trigger {0} for updates on Hot Deployment of dependent package**

**FAC+."."+RESUMING\_TRIGGER\_ON\_HOT\_DEPLOYMENT\_CANCEL – Resuming trigger {0} as the Hot Deployment of dependent package ended**

**FAC+."."+RESUMING\_TRIGGER\_ON\_HOT\_DEPLOYMENT\_END – Resuming trigger {0} as the Hot Deployment of dependent package ended**

**FAC+."."+SUSPENDING\_TRIGGER\_ON\_HOT\_DEPLOYMENT\_START – Suspending trigger {0} as the dependent package is under Hot Deployment**

**FAC+."."+UNABLE\_TO\_RESTART\_TRIGGER – Unable to re-start JMS Trigger {0}: {1}**

**FAC+."."+UNABLE\_TO\_START\_TRIGGER\_FIRST\_TIME – Unable to start JMS Trigger {0}: {1}**

**FAC+."."+UN\_REGISTER\_TRIGGER\_FOR\_HOT\_DEPLOYMENT – Unregistering trigger {0} for updates on Hot Deployment of dependent package**

**FAC\_LISTENER+ALIS3300 – MSGPREFIX\_LISTENER+"Unable to handle the state change event of the listener {0} acrosss the cluster"**

**Explanation** An error occurred while processing a state change event for a listener in the cluster.

**Action** Check the details for the error in the Integration Server error log.

**FAC\_LISTENER+ALIS3311 – MSGPREFIX\_LISTENER+"The cluster event can't be acted upon since the listener {0} is not present"**

**Explanation** The error occurs when a listener is not available on a cluster node because of incorrect cluster setup. The correct cluster setup requires copying the same package on all cluster nodes.

**Action** Check if the package containing the listener is loaded properly. Verify if the WmART package dependency is set properly.

**FAC\_LISTENER+ALIS3312 – MSGPREFIX\_LISTENER+"unable to activate the listener {0}. "**

**Explanation** When a listener becomes disabled on an active node, another node becomes active. The system returns the exception if an unexpected error occurs during that process.

**Action** Check the error log and try enabling the listener manually later on the node on which the failure occurred.

**FAC\_LISTENER+ALIS3313 – MSGPREFIX\_LISTENER+"Unable to perform the listener failover since the listener node {0} is not available."**

**Explanation** The error occurs during failover handling of a node when the active node is down, if the corresponding listener node is not available.

**Action** Check whether the package with the corresponding listener node is enabled and active. If not, try enabling the package.

**FAC\_LISTENER+ALIS3314 – MSGPREFIX\_LISTENER+"Unable to perform the listener failover due to an error while accessing the listener state cache."**

**Explanation** This error occurs during failover handling of a node when the active node is down, if the listener state is not accessible from the Terracotta cache.

**Action** If all nodes throw the same exception, try enabling the listener manually on any of the nodes.

**FAC\_LISTENER+ALIS3315 – MSGPREFIX\_LISTENER+"Unable to synchronize the listener {0} across the cluster since the shared cache isn't available."**

**Explanation** In a clustered environment, shared cache is used to synchronize the state of the listeners. The error occurs when the shared cache is not available.

**Action** Check the connection of the shared cache server to the specified Integration Server node.

**FAC\_NOTIFICATION+ANOT3132 – MSGPREFIX\_NOTIFICATION+"Unable to set Publish Event status. Missing parameter: {0}"**

**Explanation** The Notification name input parameter is missing.

**Action** Specify the notification name for which you want to set the Publish Event status.

**FAC\_NOTIFICATION+ANOT3133 – MSGPREFIX\_NOTIFICATION+"Unable to set Publish Event status. Notification not found: {0}"**

**Explanation** The specified notification does not exist.

**Action** Check if the notification with the specified name exists in the system.

**FAC\_NOTIFICATION+ANOT3136 – MSGPREFIX\_NOTIFICATION+"Notification 'Disable' request is not initiated by any user explicitly."**

**Explanation** The polling notification is not disabled explicitly by any user. It was disabled automatically due to an error.

**Action** Check the stack trace in the error log to find out the point at which the notification 'disable' operation was triggered.

**FASHHASH\_NOSUCHELEMENT – FastHashEnumerator**

**FFP.0001.9001E Child at index [{0}] is cannot be added to this row.**

**Explanation** The Integration Server encountered an internal error.

**Action** Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.

**FFP.0001.9002E Cannot add child**

**Explanation** The Integration Server encountered an internal error.

**Action** Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.

<b>FFP.0001.9003E</b>	<b>Cannot add child</b>
<b>Explanation</b>	The Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.
<b>FFP.0001.9004E</b>	<b>Cannot put a record inside another record</b>
<b>Explanation</b>	The Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Information page from the Developer, and the contents of the packages\WmFlatFile\config directory.
<b>FFP.0001.9005E</b>	<b>Cannot add unknown type to a record</b>
<b>Explanation</b>	The Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.
<b>FFP.0001.9006E</b>	<b>Fields cannot have children</b>
<b>Explanation</b>	The Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Information page from the Developer, and the contents of the packages\WmFlatFile\config directory.
<b>FFP.0001.9007E</b>	<b>Composites cannot contain composites</b>
<b>Explanation</b>	The Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Information page from the Developer, and the contents of the packages\WmFlatFile\config directory.

---

<b>FFP.0001.9008E</b>	<b>Cannot add record to a composite</b>
<b>Explanation</b>	The Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Information page from the Developer, and the contents of the packages\WmFlatFile\config directory.
<b>FFP.0001.9009E</b>	<b>Cannot add unknown type to a composite</b>
<b>Explanation</b>	The Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.
<b>FFP.0001.9010E</b>	<b>Cannot add child</b>
<b>Explanation</b>	The Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.
<b>FFP.0001.9011E</b>	<b>Cannot add children to detail view</b>
<b>Explanation</b>	The Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Information page from the Developer, and the contents of the packages\WmFlatFile\config directory.
<b>FFP.0001.9012E</b>	<b>Cannot add children to detail view</b>
<b>Explanation</b>	The Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Information page from the Developer, and the contents of the packages\WmFlatFile\config directory.

- FFP.0001.9013E      Cannot add child of type: {0}**  
**Explanation**      The Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Information page from the Developer, and the contents of the packages\WmFlatFile\config directory.
- FFP.0001.9014E      The first child of the Record Usage must be the Record Definition**  
**Explanation**      The Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from the Developer, and the contents of the packages\WmFlatFile\config directory.
- FFP.0001.9015E      Cannot set the children of a usage node. The only child is the used node definition**  
**Explanation**      The Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.
- FFP.0001.9016E      Node is not editable**  
**Explanation**      The Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.
- FFP.0001.9017E      Cannot modify the children of a reference**  
**Explanation**      The Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.

---

<b>FFP.0001.9018E</b>	<b>Cannot add child. Child must be of type: {0}</b>
<b>Explanation</b>	The Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.
<b>FFP.0001.9019E</b>	<b>Cannot add node, node with name {0} already exists</b>
<b>Explanation</b>	The Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.
<b>FFP.0001.9020E</b>	<b>Cannot edit a broken link</b>
<b>Explanation</b>	The Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.
<b>FFP.0001.9021E</b>	<b>Server cannot be null</b>
<b>Explanation</b>	The Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.
<b>FFP.0018.0001</b>	<b>The mark method is not supported by the supplied InputStream.</b>
<b>FFP.0018.0002</b>	<b>The reset method is not supported by the supplied InputStream.</b>
<b>FFP.0018.0003</b>	<b>{0} must be greater than zero (0).</b>

- FFP.0018.0004      `{0}` is required and must be greater than zero (0).
- FFP.0018.0005      `{0}` is required and must be greater than one (1).
- FFP.0018.0006      `{0}` is required and must be zero (0) or greater.
- FFP.0018.0007      If `{0}` is supplied, it must be zero (0) or greater.
- FFP.0018.0008      `offset` + `length` cannot exceed the size of `buffer`.
- FFP.0018.0009      Input parameter ffData cannot be null.
- FFP.0018.0010      Cannot process ffData of type: {0}.
- FFP.0018.0011      Could not find flat file Schema: {0}.
- FFP.0018.0012      Not validating, not keeping results, invalid settings.
- FFP.0018.0013      Encoding not supported: {0}.
- FFP.0018.0014      Name and package are required.
- FFP.0018.0015      Could not find dictionary: {0}.
- FFP.0018.0016      Flat File Schema name must be specified.
- FFP.0018.0017      No input signature presented.

---

FFP.0018.0018	Document Type `{0}` already exists. Please delete it before re-creating.
FFP.0018.0019	Value specified for maxErrors must be an integer. Value specified: `{0}`.
FFP.0018.0020	Could not find record definition `{0}` in dictionary {1}.
FFP.0018.0021	Could not find composite definition `{0}` in dictionary {1}.
FFP.0018.0022	Could not find field definition `{0}` in dictionary {1}.
FFP.0018.0023	Please specify a valid value for entryType.
FFP.0018.0024	{0} is not a flat file dictionary.
FFP.0018.0025	{0} is not a flat file schema.
FFP.0018.0026	Could not find root tag <FFSchmea>
FFP.0018.0027	Could not find a valid value for input parameter `EntryType`
FFP.0018.0028	Could not find root tag <FFDictionary>
FFP.0018.0029	Flat file dictionary {0} already exists in package {1}, cannot create it in package {2}.
FFP.0018.0030	Flat file schema {0} already exists in package {1}, cannot create it in package {2}.
FFP.0018.0031	Values are required for input parameters `FFDictionaryName` and `PackageName`.

- FFP.0018.0032      Could not find entry `{0}` in dictionary `{1}`.
  
- FFP.0018.0033      Could not find record entry `{0}`, in dictionary `{1}`.
  
- FFP.0018.0034      Could not find composite entry `{0}` in dictionary `{1}`.
  
- FFP.0018.0035      Could not find field entry `{0}` in dictionary `{1}`.
  
- FFP.0018.0036      Document Type name `{0}` is not valid
  
- FFP.0018.0037      The following input parameters are required:{0}
  
- FFP.0018.0038      Cannot create document type. Referenced {0} {1} in flat file dictionary {2} could not be found
  
- FFP.0018.0042      Please specify a value for name
  
- FFP.0018.0043      Could not find {0}
  
- FFP.0018.0044      Specified value {0} must be a flat file dictionary or flat file schema.
  
- FFP.0018.0045      Could not find package: {0}
  
- FFP.0018.0046      Package {0}, is not enabled. Please enable the package, or specify a different package
  
- FFP.0018.0047      {0} was saved with the following warning(s):
  
- FFP.0018.0048      {0} was saved with the following error(s):

<b>FFP.0018.0049</b>	<b>{0} is not a flat file dictionary.</b>
<b>FFP.0018.0052</b>	<b>Cannot encode the delimiter character '{0}' (U+{1}) using specified encoding: {2}. Please select a different delimiter character.</b>
<b>FOUND_DUP_RECORD_NAME_UM – Cannot create field "{0}" in publishable document type "{1}"; field with duplicate names are not permitted with protocol buffer encoding.</b>	
<b>FPL.0001.0000E</b>	<b>Error processing Cleanup service: {0}</b>
<b>Explanation</b>	An error occurred during the execution of the user-specified cleanup service.
<b>Action</b>	Check the server error log for more detailed information. This error is most likely caused by an exception that occurred in the user-written, cleanup service, which is identified in the message.
<b>FPL.0001.0001E</b>	<b>Listener key not provided. Cleanup service not running</b>
<b>Explanation</b>	Internal Error
<b>Action</b>	Contact Software AG Global Support. Please have the following information available: server and error logs, a copy of the Support Information page from the Developer, and the contents of the packages\WmFlatFile\config directory.
<b>FPL.0001.0002E</b>	<b>Cleanup service access denied. User {0} not allowed to run service {1}</b>
<b>Explanation</b>	The user specified in the message attempted to run the service specified in the message, but the user does not have the privileges required to run the service.
<b>Action</b>	Modify the "Run services as user" parameter on the file polling listener configuration page to specify a user that has the appropriate privileges. Make certain that the user you specify has the permissions to execute the processing service.
<b>FPL.0001.0003E</b>	<b>Error processing service: {0}</b>
<b>Explanation</b>	An error occurred during the execution of the user-specified cleanup service.
<b>Action</b>	Check the server error log for more detailed information. This error is most likely caused by an exception that occurred in the user-written cleanup service, which is identified in the message.

<b>FPL.0001.0004E</b>	<b>Could not delete file: {0} - {1}</b>
<b>Explanation</b>	An error occurred while attempting to delete the specified file.
<b>Action</b>	Check the file system to determine why the specified file has not been deleted. It might be necessary to delete the file manually.
<b>FPL.0001.0012E</b>	<b>Could not move source file {0} to working directory {1}</b>
<b>Explanation</b>	The system was unable to move the file from the monitoring directory to the working directory.
<b>Action</b>	On a Windows operating system this can be normal behavior because the operating system will not allow a file to be moved while the file is being written to. For Windows, this is an error if the file listed is never processed. On a non-Windows operating system, this error might occur because the source and destination directories are on different file systems. Specify the source and destination directories to be on the same file system.
<b>FPL.0001.0013E</b>	<b>Error processing monitoring file. {0}.</b>
<b>Explanation</b>	An error occurred during the execution of the user-specified processing service.
<b>Action</b>	Check the server error log for more detailed information. This error is most likely caused by an exception that occurred in the user-written cleanup service, which is identified in the message.
<b>FPL.0001.0014E</b>	<b>Error processing cleanup. {0}.</b>
<b>Explanation</b>	An error occurred during the execution of the user-specified cleanup service.
<b>Action</b>	Check the server error log for more detailed information. This error is most likely caused by an exception that occurred in the user-written cleanup service, which is identified in the message.
<b>FPL.0001.0020E</b>	<b>Could not get canonical path for monitoring directory: {0} - {1}</b>
<b>Explanation</b>	The system could not obtain the canonical path for the monitoring directory, which is identified in the message. The message also displays the reason.
<b>Action</b>	Take the appropriate action based on the reason for the error shown in the message.
<b>FPL.0001.0030E</b>	<b>Error processing file: {0}</b>
<b>Explanation</b>	An error occurred during the execution of the user-specified processing service.
<b>Action</b>	Check the server error log for more detailed information. This error is most likely caused by an exception that occurred in the user-written cleanup service, which is identified in the message.

---

<b>FPL.0001.0031E</b>	<b>Listener key not provided. File polling listener not running</b>
<b>Explanation</b>	Internal Error
<b>Action</b>	Contact Software AG Global Support. Please have the following information available: server and error logs, a copy of the Support Information page from Developer, and the contents of the packages\WmFlatFile\config directory.
<b>FPL.0001.0032E</b>	<b>File polling processing service access denied. User {0} not allowed to run service {1}</b>
<b>Explanation</b>	The specified user does not have privileges to run the specified service.
<b>Action</b>	Modify the "Run services as user" parameter in the file polling listener configuration page to specify a user that has the appropriate privileges. Make certain that the user you specify has the permissions to execute the processing service.
<b>FPL.0001.0033E</b>	<b>Error processing service: {0}</b>
<b>Explanation</b>	An error occurred during the execution of the user-specified processing service.
<b>Action</b>	Check the server error log for more detailed information. This error is most likely caused by an exception that occurred in the user-written cleanup service, which is identified in the message.
<b>FPL.0001.0034E</b>	<b>Could not move file to finished directory. {0}</b>
<b>Explanation</b>	The system was unable to move the file from the working directory to the finished directory.
<b>Action</b>	On a Windows operating system this can be normal behavior because the operating system will not allow a file to be moved while the file is being written to. For Windows, this is an error if the file listed is never processed. On a non-Windows operating system, this error might occur because the source and destination directories are on different file systems. Specify the source and destination directories to be on the same file system.
<b>FPL.0001.0035</b>	<b>File polling processing service indicated error - [{0}]</b>
<b>Explanation</b>	The processing service flagged an error to indicate there is an error.
<b>Action</b>	No action is required.
<b>FPL.0001.0036</b>	<b>File polling processing file: {0}</b>
<b>Explanation</b>	The indicated file is being processed.
<b>Action</b>	No action is required.

<b>FPL.0001.0037E</b>	<b>Could not rename file {0} to {1}.</b>
<b>Explanation</b>	The system was unable to move the file from the monitoring directory to the working directory.
<b>Action</b>	On a Windows operating system this can be normal behavior because the operating system will not allow a file to be moved while the file is being written to. For Windows, this is an error if the file listed is never processed. On a non-Windows operating system, this error might occur because the source and destination directories are on different file systems. Specify the source and destination directories to be on the same file system.
<b>FPL.0002.0001E</b>	<b>Invalid processing service: {0}</b>
<b>Explanation</b>	The specified processing service does not exist.
<b>Action</b>	Specify a service name that exists on the Integration Server.
<b>FPL.0002.0002</b>	<b>No such service: {0}</b>
<b>FPL.0002.0003E</b>	<b>Unknown content type: {0}</b>
<b>Explanation</b>	No content handler is defined for the given content type.
<b>Action</b>	Specify a content type for which a content handler has been defined or define a content handler for the specified content type. For more details, see the Javadoc for the class <code>com.wm.app.b2b.server.ServerAPI</code> .
<b>FPL.0002.0004E</b>	<b>Server Error: {0}</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Contact Software AG Global Support. Please have the following information available: server and error logs, a copy of the Support Information page from the Developer, and the contents of the <code>packages\WmFlatFile\config</code> directory.
<b>FPL.0002.0005E</b>	<b>Invalid Cleanup service: {0}</b>
<b>Explanation</b>	The specified processing service does not exist.
<b>Action</b>	Specify a service name that exists on the Integration Server.
<b>FPL.0003.0001E</b>	<b>Must provide Monitoring Directory</b>
<b>Explanation</b>	No monitor directory was specified.
<b>Action</b>	Specify a monitor directory.

---

<b>FPL.0003.0004E</b>	<b>Monitoring Directory does not exist</b>
<b>Explanation</b>	The monitoring directory does not exist.
<b>Action</b>	Create the monitoring directory.
<b>FPL.0003.0005E</b>	<b>Working Directory does not exist</b>
<b>Explanation</b>	The working directory does not exist.
<b>Action</b>	Create the working directory.
<b>FPL.0003.0006E</b>	<b>Must provide User Name</b>
<b>Explanation</b>	The user did not specify a value for the input "Run services as user".
<b>Action</b>	Specify a user to run the service as.
<b>FPL.0003.0007E</b>	<b>Must provide Processing service</b>
<b>Explanation</b>	The processing service was not specified.
<b>Action</b>	Specify a processing service.
<b>FPL.0003.0008E</b>	<b>Invalid processing service {0}</b>
<b>Explanation</b>	The specified processing service does not exist.
<b>Action</b>	Specify a service name that exists on the webMethods Integration Server.
<b>FPL.0003.0009E</b>	<b>Monitor Directory {0} does not exist</b>
<b>Explanation</b>	The monitor directory does not exist.
<b>Action</b>	Create the monitor directory.
<b>FPL.0003.0010E</b>	<b>Completion Directory does not exist or can not be created</b>
<b>Explanation</b>	The completion directory does not exist or cannot be created.
<b>Action</b>	Determine whether the server has permissions to create the indicated directory, or create the directory manually.
<b>FPL.0003.0011E</b>	<b>Error Directory does not exist or can not be created</b>
<b>Explanation</b>	The error directory does not exist or cannot be created.
<b>Action</b>	Determine whether the server has permissions to create the indicated directory, or create the directory manually.

<b>FPL.0003.0012E</b>	<b>Invalid Cleanup service {0}</b>
<b>Explanation</b>	The specified clean up service does not exist.
<b>Action</b>	Specify a clean up service that exists on the webMethods Integration Server.
<b>FPL.0003.0013E</b>	<b>Invalid Working Directory</b>
<b>Explanation</b>	The specified working directory is the same as either the monitoring directory or the completion directory.
<b>Action</b>	Specify a working directory that is not the same as the completion or monitoring directories.
<b>FPL.0003.0015E</b>	<b>Invalid Error Directory</b>
<b>Explanation</b>	The specified error directory is the same as either the monitoring directory or the completion directory.
<b>Action</b>	Specify an error directory that is not the same as the completion or monitoring directories.
<b>FPP.0100.0001</b>	<b>No condition string defined for the conditional validator.</b>
<b>FPP.0100.0004</b>	<b>Internal Error: Unable to handle type: {0}.</b>
<b>FPP.0100.0005</b>	<b>Unable to handle recordIdentifier of type: {0}.</b>
<b>FPP.0100.0006</b>	<b>Code list validator contained no valid choices</b>
<b>FPP.0100.0007</b>	<b>Composite does not contain any subfields.</b>
<b>FPP.0100.0008</b>	<b>Cannot contain both a definition and a reference.</b>
<b>FPP.0100.0009</b>	<b>A &lt;RecordElement&gt; tag cannot have both a &lt;CompositeUsage&gt; and a &lt;FieldUsage&gt; tag</b>

---

FPP.0100.0010	A field can only have one validator
FPP.0100.0011	A field can only have one extractor
FPP.0100.0012	Too many record parsers defined. A <RecordParser> tag can only contain one record parser.
FPP.0100.0013	Too many record identifiers defined. A <RecordIdentifier> tag can only contain one record identifier.
FPP.0100.0014	Flat file schema must have a record identifier defined.
FPP.0100.0015	Flat file schema must have a record parser defined.
FPP.0100.0016	Value {0} must be integer greater than or equal to zero.
FPP.0100.0017	<MaxOccur> value must be either "Unlimited" or a positive integer greater than zero. `{0}` is not a valid value.
FPP.0100.0018	<Position> value must be either "NoPosition" or an integer. `{0}` is not a valid value.
FPP.0100.0019	<Area> must be either "NoArea" or a positive integer greater than zero. `{0}` is not a valid value.
FPP.0100.0020	Value {0} must be integer greater than or equal to one.
FPP.0100.0021	Either <{0}> or <{1}> is required.
FPP.0100.0022	The end position ({1}) must be greater than the start position ({0}).

- FPP.0100.0023**      **The flat file schema has no records defined.**
- FPP.0100.0024**      **This element contains a reference to the flat file dictionary {0}, which does not exist**
- FPP.0100.0025**      **The {0} entry called {1} in flat file dictionary {2} in package {3} could not be found**
- FPP.0100.0026**      **Record has no fields or composites defined**
- FPP.0100.0027**      **Must have a record delimiter defined when using delimited record parser**
- FPP.0100.0028**      **Must have a field delimiter defined when using Nth field extractors**
- FPP.0100.0029**      **Must have a subfield delimiter defined when using composite extractors**
- FPP.0100.0030**      **Element has no extractor defined**
- FPU.0002.0001**      **Unable to load resource bundle: {0}**
- FTP\_CMD\_ERR**      **Command {0} failed**
- IMPROPER\_URI\_AND\_XMLOBJECTID** – **The uri provided must be #{0} as [#idXmlObject] for an enveloping signature.**
- INCORRECT\_SIGNATURE\_TYPE** – **The signature cannot be both enveloped and detached.**
- INT\_XASTORE\_NULL** **The XA store could not be initialized.**
- INVALID\_ALLOW\_HOSTNAME** – **Invalid character/s found in host name, {0}, in IP Access Allow list.**

**INVALID\_CARDINALITY** – Invalid range "{0}" specified for cardinality.

**INVALID\_COPY\_MODE** Invalid Copy Mode "{0}".

**INVALID\_DES\_TRIGGER\_DUP\_DETECTION** – DES triggers do not support the duplicate document detection feature in this release.

**INVALID\_DES\_TRIGGER\_MULTI\_DEST** – DES triggers cannot specify more than one condition or more than one document type within a condition.

**INVALID\_DES\_TRIGGER\_SERIAL** – DES triggers do not support serial processing mode in this release.

**INVALID\_FIELD\_NAME\_UM** – Cannot create field "{0}" in publishable document type "{1}"; this field name is not valid for use with protocol buffer encoding. The Universal Messaging provider will transport the field contents, which will be visible to Integration Server clients only.

**INVALID\_FOR\_EACH\_COPY\_PATH** – Invalid Copy inside For Each.

**INVALID\_JOIN\_TYPE** Invalid Join type

**INVALID\_KEYSTORE\_ALIAS** – {0} alias is invalid. Only letters, numbers and underscores are allowed

**INVALID\_KEYSTORE\_LOCATION** – Location ({0}) does not exist

**INVALID\_KEYSTORE\_PROVIDER** – {0} is not a registered security provider

**INVALID\_KEYSTORE\_TYPE** – {0} is not a supported Keystore type

**INVALID\_TRIGGER\_MIXED\_ALIASES** – webMethods Messaging trigger {0} is invalid. All document types in the trigger must use the same alias.

**INVALID\_XML\_CHARACTER – The character {0} is not allowed in XML.**

**INVOKE\_IFCNAME\_MISSING – Service interface name required.**

**INVOKE\_SVCNAME\_MISSING – Service name required.**

**IS.0088.9446E      Access denied to use the web service endpoint alias {0}.**  
**Explanation**      User does not have permission to use the specified web service endpoint alias.  
**Action**              Using the Integration Server Administrator, examine the Execute ACL property of the web service endpoint alias. Make sure that the current user has the proper ACL to use the web service endpoint alias.

**ISC.0006.0004S      Error in SSL setup: {0}**  
**Explanation**      The server cannot configure SSL listener or SSL Sockets connections, most likely because of a problem with the SSL configuration settings.  
**Action**              Review the exception message in the log and correct the configuration.

**ISC.0006.0006I      SSL listener restricted to 128 bit or better encryption.**  
**Explanation**      Integration Server configuration properties watt.net.ssl.client.strongcipheronly or watt.net.ssl.server.strongcipheronly or both are set to "true".  
**Action**              No action is necessary. This message indicates that Integration Server is using strong encryption.

**ISC.0006.0013E      Peer certificate chain is not present**  
**Explanation**      Integration Server cannot retrieve the peer certificate chain from a client.  
**Action**              Update your client program so that it provides a valid peer certificate to Integration Server.

**ISC.0006.0014E      SSL handshake failed on port {0} because peer certificate is not in IS Certificate Map, transfer is terminated**  
**Explanation**      While trying to connect to Integration Server, a client presented a certificate that is not contained in the store of client certificates that are mapped to Integration Server users.  
**Action**              To import the client certificate to Integration Server and map it to a valid user, go to the Integration Server Administrator and click Security>Certificates>Configure Client Certificates. For additional information about certificate mapping, refer to the webMethods Integration Server documentation.

---

<b>ISC.0006.0015E</b>	<b>Peer certificate chain is not trusted</b>
<b>Explanation</b>	While trying to connect to Integration Server, a client presented a certificate that is not trusted by Integration Server.
<b>Action</b>	Add the certificate to the trusted certificates directory for Integration Server. The name of this directory is specified on the Integration Server Administrator under Security>Certificates. For more information about trusted certificates, refer to the webMethods Integration Server documentation.
<b>ISC.0006.0016E</b>	<b>SSL handshake failed on port {0}, transfer is terminated</b>
<b>Explanation</b>	An IOException occurred during the SSL handshake portion of a client's attempt to connect to Integration Server at the indicated port.
<b>Action</b>	Check the server log and error log for possible causes for the error.
<b>ISC.0006.0017S</b>	<b>Error in adding trusted certificates: {0}</b>
<b>Explanation</b>	The Integration Server failed to add the specified CA certificate because it is not in the correct format. The CA certificate must be DER or PEM encoded.
<b>Action</b>	Check the certificate format. Configure CA certificates in DER or PEM format.
<b>ISC.0006.0018S</b>	<b>Error in initializing certificate chain verifier: {0}</b>
<b>Explanation</b>	An error occurred when Integration Server initialized the certificate chain verifier while setting up the specified secure listener.
<b>Action</b>	Check the server log and error log to determine the cause of the error.
<b>ISC.0006.0019W</b>	<b>Not including Cipher {0} because it is not a strong Cipher.</b>
<b>Explanation</b>	Integration Server generates this warning when either the watt.net.ssl.server.strongcipheronly or watt.net.ssl.client.strongcipheronly property is set to "true", and if any of the ciphers identified in either the watt.net.ssl.client.cipherSuiteList or watt.net.ssl.server.cipherSuiteList property are weak.
<b>Action</b>	To stop receiving this warning, remove the specified cipher from the watt.net.ssl.server.cipherSuiteList or watt.net.ssl.client.cipherSuiteList property.
<b>ISC.0006.0020W</b>	<b>Cipher ({0}) is not a valid CipherSuiteList.</b>
<b>Explanation</b>	A CipherSuite specified as a value to either the watt.net.ssl.client.cipherSuiteList or watt.net.ssl.server.cipherSuiteList property is not valid. The invalid CipherSuite is shown in the log message.  One of the CipherSuite that is specified as a value to either watt.net.ssl.client.cipherSuiteList or watt.net.ssl.server.cipherSuiteList property is not a valid CipherSuite. The invalid CipherSuite is shown in the log message.

<b>Action</b>	Remove the invalid CipherSuite.
<b>ISC.0009.0012E</b>	<b>Failed to create certificate: {0}</b>
<b>Explanation</b>	The certificate specified in the Configure Client Certificates settings has a bad X509Certificate format.
<b>Action</b>	Make sure that the .der file specified in Configure Client Certificates settings is valid.
<b>ISC.0009.0014E</b>	<b>A certificate with the same issuer, serial number and usage is already mapped to user {0}.</b>
<b>Explanation</b>	For a given usage type, only one user can be mapped to a certificate with the same issuer and serial number.
<b>Action</b>	To reassign this certificate to different user, edit the previously mapped certificate and change the user.
<b>ISC.0009.0015E</b>	<b>The certificate is already mapped to user {0}.</b>
<b>Explanation</b>	Integration Server failed to map the client certificate to the user because the client certificate is already mapped to the user specified.
<b>Action</b>	To reassign this certificate to different user, edit the previously mapped certificate and change the user.
<b>ISC.0009.0016E</b>	<b>The ISInternal functional alias is not configured properly on the JDBC Pools page. Assign a valid database pool and restart the Integration Server.</b>
<b>Explanation</b>	Integration Server failed to initialize client certificate mappings because it could not access the ISInternal JDBC Pool.
<b>Action</b>	Assign a valid database pool to ISInternal JDBC functional alias and restart the Integration Server.
<b>ISC.0009.0017W</b>	<b>Certification chain trust verification failed.</b>
<b>Explanation</b>	At least one of the certificates present in the certificate chain is not trusted by Integration Server.
<b>Action</b>	Check the certificate chain presented to Integration Server for trust verification.
<b>ISC.0009.9001E</b>	<b>Certificate chain broken: not linked properly</b>
<b>Explanation</b>	The certificate chain is out of order.
<b>Action</b>	Obtain a valid certificate chain.

---

<b>ISC.0009.9003E</b>	<b>Certificate contains an unsupported critical extension</b>
<b>Explanation</b>	When <code>watt.security.cert.wmChainVerifier.enforceExtensionsChecks</code> property is set to "true", Integration Server checks the presented certificate for unsupported critical extensions. If Integration Server finds a certificate containing unsupported critical extensions, it will reject the certificate and fail the request.
<b>Action</b>	If you enabled Integration Server to perform a certificate extensions check, advise your clients to use certificates that do not contain unsupported critical extensions. Whether Integration Server enforces a certificate check is configured on the <code>watt.security.cert.wmChainVerifier.enforceExtensionsChecks</code> configuration property.
<b>ISC.0009.9004E</b>	<b>Certificate issued to {0} has expired</b>
<b>Explanation</b>	Unless configured to ignore expired certificates, Integration Server will reject any expired certificates. Whether Integration Server ignores expired certificates is configured on the <code>watt.security.ssl.ignoreExpiredChains</code> configuration property.
<b>Action</b>	Review the server log to see which client's certificate has expired. That client should renew their certificates and resubmit the request with the valid certificate.
<b>ISC.0009.9102E</b>	<b>User does not exist for certificate : {0}.</b>
<b>Explanation</b>	The user associated with the imported client certificate in Integration Server has been deleted.
<b>Action</b>	Ensure that all imported client certificates in Integration Server are associated with a user. If you have deleted the user associated with a client certificate, you can take one of the following actions:  1) Modify the certificate mapping using Security > Certificates > Client Certificates > Details > Change Mapping in the Integration Server Administrator.  2) Add a user with the same name as the deleted user that was associated with the imported client certificate.
<b>ISC.0012.0040E</b>	<b>OSGi service for SAML authentication not initialized.</b>
<b>Explanation</b>	There was a problem while attempting to access Integration Server from the Command Central user interface.
<b>Action</b>	Check the logs located in the <code>Software_AG_directory/profiles/IS/logs</code> directory and make sure that no errors were encountered during the initialization of the OSGi service specified in the error message.

- ISC.0012.0041E**      **Unable to initialize SAML authentication module. Cannot get reference of the OSGi service {0}.**
- Explanation**      There was a problem while attempting to access Integration Server from the Command Central user interface.
- Action**            Check the logs located in the Software\_AG\_directory/profiles/IS/logs directory and make sure that no errors were encountered during the initialization of the OSGi service specified in the error message.
- 
- ISC.0012.0042E**      **Error while adding Integration Live user: {0}. Error message: {1}. Stack trace: {2}**
- Explanation**      An unexpected error occurred while adding an Integration Live user.
- Action**            Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- 
- ISC.0012.0044E**      **Unable to get SAML assertion from REST URL {0} because of exception: {1}**
- Explanation**      An error occurred while retrieving the SAML assertion from REST URL. Refer to the error message text for more details.
- Action**            Verify the REST URL and ensure that the REST service exists to generate SAML assertion.
- 
- ISC.0018.0001U**      **Unable to read MIME types file**
- Explanation**      During startup, Integration Server was unable to read the MIME types from the file "mime.types", which is located on the <IntegrationServer\_dir>\lib directory. The most likely reason is that this file is corrupted.
- Action**            Contact Software AG Global Support for a copy of this file.
- 
- ISC.0018.0002**      **Deleted group {0} was removed from {1} ACL lists**
- 
- ISC.0018.9301E**      **Unlocking thread is not owner**
- 
- ISC.0018.9401E**      **target directory does not exist**
- Explanation**      Directory specified to make the tar (zip) file does not exist in the file system.
- Action**            Ensure that the directory exists in the file system.

---

<b>ISC.0018.9402E</b>	<b>target is not a directory</b>
<b>Explanation</b>	Only directories can be zipped. The File name field do not contain the path to a directory.
<b>Action</b>	Ensure that the File name field contains the path to a directory.
<b>ISC.0018.9403E</b>	<b>extraction target is not a directory</b>
<b>Explanation</b>	File name specified to extract a tar file is not a directory. A tar file can be extracted only to a directory.
<b>Action</b>	Enter the directory to which the tar file is to be extracted.
<b>ISC.0018.9404E</b>	<b>field length exceeded: {0} &gt; {1} ({2})</b>
<b>Explanation</b>	Integration Server encountered an internal error while adding a file to tar file.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0018.9405E</b>	<b>expected {0} bytes but got {1}</b>
<b>Explanation</b>	While adding a file to a tar archive, the number of bytes added to the archive is less than the actual size of the file.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0018.9406E</b>	<b>No Tar Entry specified</b>
<b>Explanation</b>	No directory is provided for zipping.
<b>Action</b>	Ensure that a directory is provided for zipping.
<b>ISC.0018.9407E</b>	<b>data length is greater than entry specification: {0}</b>
<b>Explanation</b>	Integration Server encountered an internal error while adding a file to the tar file.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0037.0001</b>	<b>Unable to Initialize {0}</b>
<b>ISC.0037.0002</b>	<b>Unable to Shutdown {0}</b>

ISC.0037.0005	<b>Unable to reset job manager {0}</b>
ISC.0037.0006	<b>Unable to reset logfile {0}</b>
ISC.0037.0007	<b>Unable to reset logstream {0}</b>
ISC.0037.0012	<b>Unable to accept requests</b>
ISC.0037.9101E	<b>Guaranteed Delivery Disabled - Please correct error and reinitialize</b>
ISC.0042.0002E	<b>Unsupported Encoding: {0}</b>
<b>Explanation</b>	Integration Server did not recognize the encoding of the document. Therefore, the default encoding will be used.
<b>Action</b>	If Integration Server successfully uses the default encoding, no action is necessary. Otherwise, change the supplied document so that it has a valid encoding.
ISC.0042.9001	<b>Cannot uniquely identify the root element : Every element may be contained in at least one other element -- Try loading the DTD from a sample XML document having a DOCTYPE declaration.</b>
ISC.0042.9002	<b>Cannot uniquely identify the root element : Multiple elements are topmost elements ({0}) -- Try loading the DTD from a sample XML document having a DOCTYPE declaration.</b>
ISC.0042.9003	<b>&lt;{ELEMENT {0} {1}&gt; contains the following error at character {2} of the contentspec: {3}</b>
ISC.0042.9005U	<b>URI {0} not declared at node {1}</b>
<b>Explanation</b>	webMethods Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.

---

<b>ISC.0042.9006U</b>	<b>Node reference is null</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0042.9007U</b>	<b>Node is not XML</b>
<b>Explanation</b>	The pub.xml:getXMLNodeIterator service failed to execute because the node object supplied was not an XML node.
<b>Action</b>	Examine the service input and make sure the "node" parameter represents an XML node, not an HTML node.
<b>ISC.0042.9008U</b>	<b>Moving window mode is only available when iterating over XML nodes</b>
<b>Explanation</b>	The pub.xml:getXMLNodeIterator service failed to execute because the XML node supplied did not represent a whole XML document.
<b>Action</b>	Examine the service input and make sure the "node" parameter represents an entire XML document, not an element of an XML document.
<b>ISC.0042.9009U</b>	<b>Moving window mode is not available with SAX parsers</b>
<b>Explanation</b>	The pub.xml:getXMLNodeIterator service failed to execute because the moving window mode is not available with SAX parsers.
<b>Action</b>	Switch to the webMethods parser instead of the SAX parser.
<b>ISC.0042.9011U</b>	<b>SAX parsers do not expose enough DTD info; try selecting the expandDTD option</b>
<b>Explanation</b>	The pub.xml:loadXMLNode service failed to execute because it used a SAX parser. Integration Server does not support SAX parsers because they do not expose enough DTD information.
<b>Action</b>	Switch to the webMethods parser instead of the SAX parser.
<b>ISC.0042.9012U</b>	<b>First node of region not found in node parameter</b>
<b>Explanation</b>	The pub.web:createRegions service failed to execute because the "regions" parameter did not correctly specify the first node of the region.
<b>Action</b>	Examine the service input for the "regions" parameter and check the query specified for identifying the first node. Make sure the query specified will correctly identify the first node.

<b>ISC.0042.9013U</b>	<b>Last node of region not found in node parameter</b>
<b>Explanation</b>	The pub.web:createRegions service failed to execute because the "regions" parameter did not correctly specify the last node of the region.
<b>Action</b>	Examine the service input for the "regions" parameter and check the query specified for identifying the ending node. Make sure the query specified will correctly identify the ending node.
<b>ISC.0049.0001</b>	<b>Branch {0}: child {1} not found, default child not found for switch {2}</b>
<b>ISC.0049.0002</b>	<b>Branch {0}: child {1} not found, invoking default child {2}</b>
<b>ISC.0049.0010</b>	<b>Loop {0}: in-array {1} is not an array type.</b>
<b>ISC.0049.0012</b>	<b>Set: invalid encoding: {0}</b>
<b>ISC.0049.0013E</b>	<b>Set: {0}</b>
<b>Explanation</b>	While saving or loading a flow service, Integration Server encountered a problem with the base64 encoding of a Map operation.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0049.0015</b>	<b>Loop {0}: out-array is not the same length as in-array.</b>
<b>ISC.0049.0016</b>	<b>Flow timed-out at {0}</b>
<b>ISC.0049.0018</b>	<b>Branch {0}: no expressions evaluated true and no default child found</b>
<b>ISC.0049.0019</b>	<b>Branch {0}: no expressions evaluated true, but default child found</b>
<b>ISC.0049.9001E</b>	<b>FlowExit "{0}" -- no valid ancestor to exit from \$loop</b>
<b>Explanation</b>	In a flow service, the Exit operation failed because an ancestor loop was not found.
<b>Action</b>	Move the Exit operation to be a child of a Loop or Repeat step. Alternatively, set the exit-on property for the Exit operation to a value other than \$loop.

---

<b>ISC.0049.9002E</b>	<b>get: complex path is not supported</b>
<b>Explanation</b>	A flow service tried to perform a get operation on a complex path, but Integration Server does not support complex path types. This is an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0049.9003E</b>	<b>put: complex path is not supported</b>
<b>Explanation</b>	A flow service tried to perform a put operation on a complex path type, but Integration Server does not support complex path types. This is an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0049.9004E</b>	<b>delete: complex path is not supported</b>
<b>Explanation</b>	A flow service tried to perform a delete operation on a complex path, but Integration Server does not support complex path types. This is an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0049.9005E</b>	<b>Input validation for service "{0}" failed: "{1}"</b>
<b>Explanation</b>	During service execution, Integration Server detected that the contents of the pipeline did not conform to the defined input signature of the service.
<b>Action</b>	Ensure that the inputs in the pipeline match the input signature of the flow service, or disable input validation for this service.
<b>ISC.0049.9006E</b>	<b>Output validation for service "{0}" failed: "{1}"</b>
<b>Explanation</b>	Upon completion of a service, Integration Server detected that the contents of the pipeline did not conform to the defined output signature .
<b>Action</b>	Ensure that the outputs in the pipeline match the defined output signature or disable output validation for this service.
<b>ISC.0049.9007E</b>	<b>Failure creating input validator for "{0}"</b>
<b>Explanation</b>	During execution of a flow service, Integration Server determined that it could not create an input Validator from the parameters provided.
<b>Action</b>	Contact Software AG Global Support.

<b>ISC.0049.9008E</b>	<b>Failure creating output validator for "{0}"</b>
<b>Explanation</b>	During execution of a Flow service, Integration Server determined that it could not create an output Validator from the parameters provided. This is an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0049.9009E</b>	<b>Missing required property 'switch' at "{0}"</b>
<b>Explanation</b>	The Branch step has no switch property value.
<b>Action</b>	Specify the name of an pipeline object that is to be used as the switch value for the Branch step.
<b>ISC.0049.9010E</b>	<b>Service "{2}" invoking unknown service "{1}" at "{0}". The service may have been renamed, moved or disabled.</b>
<b>Explanation</b>	The failing flow service attempted to execute another service that could not be located or could not be executed. The most likely cause is that the target service has been removed or renamed.
<b>Action</b>	Determine the new name or location of the target service and modify the failing flow service to correctly identify the target service.
<b>ISC.0049.9011E</b>	<b>Missing required property 'in-array' at "{0}"</b>
<b>Explanation</b>	The Loop step has no input array property.
<b>Action</b>	Specify the name of a pipeline object to use as the input array.
<b>ISC.0049.9012E</b>	<b>Cannot define 'switch' and use label conditions at "{0}"</b>
<b>Explanation</b>	Integration Server tried to execute a Branch step, but the Branch properties were specified incorrectly. Specifically, the "evaluate labels" property was set to "true" while the "switch" property specified an expression. This is not a valid combination.
<b>Action</b>	Change the Branch step properties to either specify a switch value and set "evaluate-labels" to false, or do not specify a switch value and set "evaluate-labels" to true.
<b>ISC.0049.9013E</b>	<b>Timeout at "{0}"</b>
<b>Explanation</b>	A step in a flow service exceeded its timeout value before returning.
<b>Action</b>	This is desired behavior. Examine the underlying services that did not return in time to determine the cause of the timeout.

---

<b>ISC.0049.9014E</b>	<b>Scope "{0}" not found or invalid</b>
<b>Explanation</b>	At run time, Integration Server could not resolve the scope of the pipeline in a flow step. The scope resolved to an object that was not an IData.
<b>Action</b>	Make sure that the path in the scope property resolves to an IData object at run time.
<b>ISC.0049.9015E</b>	<b>FlowExit "{0}" - label not found: "{1}"</b>
<b>Explanation</b>	In a flow service, the Exit operation failed because it could not locate the label anywhere in the ancestry of the Exit step.
<b>Action</b>	Make sure that an ancestor flow step has a label that matches the one in the Exit step.
<b>ISC.0049.9016E</b>	<b>Invalid scope path</b>
<b>Explanation</b>	At run time, Integration Server could not resolve the pipeline scope specified for a flow step because the syntax of the scope property is not valid.
<b>Action</b>	Make sure that the path syntax of the scope property is valid.
<b>ISC.0049.9017E</b>	<b>(1) Illegal path from: "{0}"</b>
<b>Explanation</b>	In the pipeline, the map path for the source or destination is empty.
<b>Action</b>	If this error occurs while editing a flow service, save the flow service and then reload it.
<b>ISC.0049.9018E</b>	<b>The path has been used: {0}</b>
<b>Explanation</b>	More than one mapping operation is being performed on a pipeline object.
<b>Action</b>	Only one operation may be performed on a pipeline object in a Map step. Remove all but one of the map operations for the pipeline object, or ensure that only one operation is attempted at run time.
<b>ISC.0049.9019I</b>	<b>More than one copy into the path with different common parent(s).</b>
<b>Explanation</b>	When mapping data in the pipeline, under a single Map step, you tried to map from documents to two different document fields under a common parent. However, the source documents have different dimensions.
<b>Action</b>	Separate the data mapping into two different Map steps.

<b>ISC.0049.9022E</b>	<b>Data type does not match the path.</b>
<b>Explanation</b>	A pipeline mapping operation specifies a target type that does not match the source type at run time.
<b>Action</b>	Ensure that the source type at run time matches the target type specified by the map operation.
<b>ISC.0049.9024E</b>	<b>Cannot make the copy from: {0} to: {1}</b>
<b>Explanation</b>	While executing mapping in a flow step, Integration Server determined that it could not copy one field to another because the elements were of incompatible types.
<b>Action</b>	Make sure that the field types are compatible and have the same dimensions.
<b>ISC.0049.9025E</b>	<b>Invalid source path.</b>
<b>Explanation</b>	While trying to execute a map between fields, Integration Server determined that no source field was specified.
<b>Action</b>	In the pipeline, make sure that a source field is specified.
<b>ISC.0049.9026E</b>	<b>Invalid target path.</b>
<b>Explanation</b>	While trying to execute a map between fields, Integration Server determined that no target path was specified.
<b>Action</b>	In the pipeline, make sure that the map specifies a target destination.
<b>ISC.0049.9027E</b>	<b>Error at {0} - Transformers cannot loop over list elements</b>
<b>Explanation</b>	A Map step includes a link from an array variable in Pipeline In to a scalar input variable for a transformer.
<b>Action</b>	Do one of the following: - Remove the mapping between the array variable in Pipeline in and the scalar input variable for the transformer. - Change the service invoked by the transformer to accept arrays as data. - Create a flow service in which a LOOP step loops over the array variable. Then, (in the same flow service) invoke the service you originally wanted to use as a transformer, and make that Invoke step a child of the Loop. Finally, insert the resulting flow service as a transformer in the Map step.
<b>ISC.0049.9031E</b>	<b>Global Variable {0} does not exist.</b>
<b>Explanation</b>	The global variable that you assigned to a variable in the flow service does not exist in Integration Server.
<b>Action</b>	Ensure that global variable exists in IS, if it does not exist then contact IS Admin to add this Global Variable.

---

ISC.0050.0002	<b>Invalid pipeline mapping: Cannot map two pipeline variables into the same field.</b>
ISC.0050.0003	<b>Pipeline variable sources have different dimensions.</b>
ISC.0050.0004	<b>Copy failed: {0}; to={1}, from={2}</b>
ISC.0050.0005	<b>Set failed: {0}; field={1}</b>
ISC.0050.0007	<b>Failed size check on path {0}</b>
ISC.0050.0008	<b>No valid value objects for path {0}</b>
ISC.0050.0009	<b>Data check: data type mismatch</b>
ISC.0050.0013	<b>Copy failed: No source data available from {0}</b>
ISC.0050.0014	<b>Field {0} incorrectly declared as array type</b>
ISC.0050.0015	<b>Incomplete path: null value for {0}</b>
ISC.0050.0016	<b>Cannot create object for the class: {0}</b>
ISC.0050.0017E	<b>Error encoding schema in FlowMap {0}</b>
<b>Explanation</b>	While saving a flow service, Integration Server encountered an error trying to encode the input or output of a Map step.
<b>Action</b>	Contact Software AG Global Support.
ISC.0050.0018E	<b>Error decoding schema in FlowMap {0}</b>
<b>Explanation</b>	While loading a flow service, Integration Server encountered an error trying to decode the input or output of a Map step.
<b>Action</b>	Contact Software AG Global Support.

ISC.0050.0019	<b>Copy failed: No source data available: to={0}, from={1}</b>
ISC.0050.0020	<b>Copy failed: Cannot create target data: to={0}, from={1}</b>
ISC.0050.0021	<b>Copy failed: Cannot support the required class name: to={0}, from={1}</b>
ISC.0062.0001	<b>CreateRegions createNsDecls type not supported</b>
ISC.0062.0002E	<b>CreateRegions createRegions type not supported</b>
<b>Explanation</b>	The pub.web:createRegions service failed to execute because the input provided for the "regions" parameter was not an instance of IData[ ].
<b>Action</b>	Examine the service input make sure the "regions" parameter specifies an instance of IData[ ].
ISC.0062.0003U	<b>GenerateQueryString {0} setValues {1}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
ISC.0062.0004E	<b>GenerateQueryStrings createFields type not supported</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
ISC.0062.0005E	<b>GenerateQueryStrings createNodeIDs type not supported</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
ISC.0062.0006E	<b>GenerateQueryStrings the bind failed</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.

---

ISC.0062.0007U	<b>GetDocAsTable nodeTypeToString: {0} unknown type</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
ISC.0062.0008	<b>MakeRules.makeNSRecordFromDTD root of doc:{0} sig:{1}</b>
ISC.0062.0009	<b>MakeRules.makeNSRecordFromDTD root of doc:null</b>
ISC.0062.0010	<b>MakeRules.findElementDef name {0} not found in DTD:{1}</b>
ISC.0062.0011E	<b>MakeRules.makeRecord ERROR ConnectParticleName:{0}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
ISC.0062.0012	<b>MakeRules.generateFlowFromDTD node parameter is null</b>
ISC.0062.0013	<b>MakeRules.generateFlowFromDTD no output signature</b>
ISC.0062.0014E	<b>QueryDocWithIdentity createFields type not supported:{0}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
ISC.0062.0015	<b>QueryDocWithIdentity createNsDecls type not supported:{0}</b>
ISC.0062.0016E	<b>queryXMLNode createFields type not supported:{0}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
ISC.0062.0017	<b>{0} createNsDecls type not supported:{1}</b>

<b>ISC.0062.0018U</b>	<b>DocumentToXMLString boundNode argument is null</b>
<b>Explanation</b>	The pub.xml:documentToXMLString service failed to execute because the required "document" parameter was missing. This parameter specifies the name of the document to be converted to XML.
<b>Action</b>	Examine the service input and make sure it specifies a value for the "document" parameter.
<b>ISC.0062.0019</b>	<b>ERROR unsupported type:{0} !!!!</b>
<b>ISC.0062.0022</b>	<b>Server encountered an unknown error: {0}</b>
<b>ISC.0062.0032</b>	<b>Invalid number format: {0}</b>
<b>ISC.0062.0033</b>	<b>Illegal parameter value. {0} is too many root elements in boundNode. Number attributes:{1}.</b>
<b>ISC.0062.0034</b>	<b>loadXMLNode called client.http pipe: {0}</b>
<b>ISC.0062.0036</b>	<b>Invalid port number {2} for {3}</b>
<b>ISC.0062.0037</b>	<b>loadXMLNode service encountered unsupported encoding: {0}</b>
<b>ISC.0062.9001U</b>	<b>boundNode parameter is null</b>
<b>Explanation</b>	The pub.xml:documentToXMLString service failed to execute because the required "document" parameter was missing.
<b>Action</b>	Examine the service input and make sure it contains the document to be converted in the form of an IData object.
<b>ISC.0062.9002U</b>	<b>Namespace prefix name "{0}" for uri {1} is not legal XML name</b>
<b>Explanation</b>	The pub.xml:documentToXMLString service failed to execute because it detected illegal characters in the namespace prefix of the document to be converted. Integration Server flags invalid characters in the namespace prefix only if the value for the "enforceLegalXML" parameter is set to "true".
<b>Action</b>	To resolve this error, do one of the following:  (1) Set the input for the "enforceLegalXML" parameter to "false". This causes the service to produce an XML fragment.

(2) Make sure the input for the "nsDecls" parameter specifies a namespace prefix that starts with a letter or the underscore "\_" character. In addition, it can only contain letters, digits, and the period ".", hyphen "-", and underscore "\_" characters.

<b>ISC.0062.9003U</b>	<b>Illegal parameter value. {0} is too many root elements in boundNode. Number attributes:{1}</b>
<b>Explanation</b>	The pub.xml:documentToXMLString service failed to execute because the document to be converted contains multiple root elements. Integration Server flags this condition only if the input for the "enforceLegalXML" parameter is set to true.
<b>Action</b>	Examine the service input and make sure the "enforceLegalXML" parameter is set to "false". This will cause the service to produce an XML fragment composed of the multiple elements that were not enclosed within a root element.
<b>ISC.0062.9004U</b>	<b>Attribute name "{0}" is not legal XML name</b>
<b>Explanation</b>	The pub.xml:documentToXMLString service failed to execute because the prefix that designates the keys that contain attributes contains illegal characters. Integration Server flags this condition only if the input for the "enforceLegalXML" parameter is set to true.
<b>Action</b>	To resolve this error, do one of the following:  (1) Set the input for the "enforceLegalXML" parameter to "false" . This will cause the service to produce an XML fragment.  (2) Make sure the input for the "attrPrefix" parameter starts with a letter or underscore "_" character. In addition, it can only contain letters, digits, and the period ".", hyphen "-", and underscore "_" characters.
<b>ISC.0062.9005U</b>	<b>Element name "{0}" is not legal XML name</b>
<b>Explanation</b>	The pub.xml:documentToXMLString service failed to execute because the document being converted contains illegal XML tag names. Integration Server flags this condition only if the input for the "enforceLegalXML" parameter is set to true.
<b>Action</b>	To resolve this error, do one of the following:  (1) Set the input for the "enforceLegalXML" parameter to "false". This causes the service to produce an XML fragment.  (2) Make sure the input for the "document" parameter starts with a letter or underscore "_" character. In addition, it can only contain letters, digits, and the period ".", hyphen "-", and underscore "_" characters.

<b>ISC.0062.9006U</b>	<b>Illegal parameter value. Document Type "{0}" not found.</b>
<b>Explanation</b>	The pub.xml:xmlNodeToDocument service failed to execute because the "documentTypeName" was specified, but the document it represents does not exist on the Integration Server namespace.
<b>Action</b>	Examine the service input and make sure the "documentTypeName" parameter specifies the fully qualified name of the document type. Remember that namespace element names are case-sensitive.
<b>ISC.0062.9007E</b>	<b>collect parameter must be null when using recordName parameter</b>
<b>ISC.0062.9008</b>	<b>MakeArrays parameter must be false when using recordName parameter</b>
<b>ISC.0062.9009</b>	<b>Arrays parameter must be null when using recordName parameter</b>
<b>ISC.0062.9010</b>	<b>Records parameter must be null when using recordName parameter</b>
<b>ISC.0062.9012</b>	<b>Internal error: no record generated by makeNSRecord</b>
<b>ISC.0062.9013</b>	<b>Internal error: no NSName generated</b>
<b>ISC.0062.9014</b>	<b>MakeRules.recursiveCollectRecordRefs found nested ContentParticleSet</b>
<b>ISC.0062.9015</b>	<b>MakeRules.findElementDef no element definitions found</b>
<b>ISC.0062.9016</b>	<b>MakeRules.findElementDef name "{0}" not found in DTD</b>
<b>ISC.0062.9017</b>	<b>XML node parameter is null</b>
<b>ISC.0062.9018</b>	<b>No NSRecord generated for package "{0}" Document Type "{1}"</b>

---

ISC.0062.9019	<b>XML node is null</b>
ISC.0062.9020	<b>Document Type "{0}" already exists.</b>
ISC.0062.9021U	<b>"object" is null</b>
<b>Explanation</b>	The object to be validated does not exist in the pipeline.
<b>Action</b>	Link an XML node or document variable to the object variable in Service In.
ISC.0062.9022U	<b>"{0}" - object does not exist</b>
<b>Explanation</b>	The document type or schema specified for the "conformsTo" parameter does not exist in the Integration Server namespace.
<b>Action</b>	Change the value of the "conformsTo" parameter to be a document type or schema that exists in the Integration Server namespace.
ISC.0062.9023U	<b>conformsTo parameter is null</b>
<b>Explanation</b>	While executing the pub.schema:validatePipeline service, the Integration Server determined that no value was specified for the "conformsTo" property, which is a required parameter. This parameter specifies the IS document or IS schema against which the Integration Server performs validation.
<b>Action</b>	Specify a value for the "conformsTo" parameter that is an IS document type or schema type that exists in the IS namespace.
ISC.0062.9024U	<b>Integration Server does not support this type of object in validation {0}</b>
<b>Explanation</b>	The object to be validated is not one of the types supported by validation.
<b>Action</b>	Currently, only XML, pipeline, and document (IData object) validation are supported.
ISC.0062.9025	<b>collect parameter must be null when using documentTypeName parameter</b>
ISC.0062.9026	<b>MakeArrays parameter must be false when using documentTypeName parameter</b>
ISC.0062.9027	<b>Arrays parameter must be null when using documentTypeName parameter</b>

- ISC.0062.9028** Documents parameter must be null when using documentTypeName parameter
- ISC.0062.9029** The schema domain of the conformsTo object must match the schemaDomain parameter
- ISC.0062.9137E** When node is an enhanced XML node, queryType must be XQL
- Explanation** The queryType input parameter is set to WQL but the node is an enhanced XML node. Only XQL can be used to query an enhanced XML node.
- Action** Set queryType to XQL and rewrite the query to use XQL instead of WQL.
- ISC.0063.0006** Generate Transaction Ids {0}
- ISC.0063.0017** Retrieve completed job tid={0}
- ISC.0063.0020** Error (see job log) tid={0}
- ISC.0063.0027** Error loading tid={0}; skipping ...
- ISC.0063.0036** Can Still Retry {0}
- ISC.0063.0042** Job Manager not initialized.
- ISC.0063.0045** Deregister - already 0
- ISC.0063.0046** Jobs still active on shutdown
- ISC.0063.0049** Start for Nonexistent Tid={0}
- ISC.0063.0050** Job Expired for Tid={0}

---

ISC.0063.0052	Retrieve on Nonexistent Tid={0}
ISC.0063.0053	Retrieve on new job
ISC.0063.0054	Retrieve on heuristic failure
ISC.0063.0055	Retrieve on expired job
ISC.0063.0056	Job Timed Out for Tid={0}
ISC.0063.0058	Restart for Nonexistent Tid={0}
ISC.0063.0059	Restart for Ended Tid={0}
ISC.0063.0060	Restart on active Tid={0}
ISC.0063.0061	Restart on non-pending Tid={0}
ISC.0063.0062	Status for non-existent Tid={0}
ISC.0063.0063	ChainedWait for non-existent Tid={0}
ISC.0063.0064	Get Remote TID for non-existent Tid={0}
ISC.0063.0069	Administrator email is not set.
ISC.0063.0070	Administrator email is {0}.

ISC.0063.0071	Logfile used:{0}. Jobdir used:{1}.
ISC.0063.0072	{0} broke lock for guaranteed job, tid={1}.
ISC.0063.0073E	<b>The IS Internal database pool is not configured properly. Assign a valid database pool for the "ISInternal" functional alias and restart the Integration Server.</b>
<b>Explanation</b>	The ISInternal functional alias on the Settings > JDBC Pools page in the Integration Server Administrator is not properly configured, or the database it refers to is unavailable.
<b>Action</b>	Configure the ISInternal functional alias on the Settings > JDBC Pools page in the Integration Server Administrator and use the "Test" button to verify that it can connect to the database. After configuring the ISInternal functional alias, restart the Integration Server.
ISC.0063.0074	End for Nonexistent Tid={0}
ISC.0063.0075	Failed to obtain repository context : {0}
ISC.0063.0078	Unable to accept requests
ISC.0063.0079	End: Invalid Transaction Id
ISC.0063.0080	Unable to accept requests
ISC.0063.0084	Unable to accept requests
ISC.0063.0086	Unable to accept requests
ISC.0063.0090	No Output Writer specified

---

ISC.0063.0098	<b>Not a custom stream</b>
ISC.0063.0100	<b>Not a custom Writer</b>
ISC.0063.0101	<b>Don't close user stream</b>
ISC.0063.0103	<b>{0} property is invalid. Using default value of {1}.</b>
ISC.0063.0104	<b>{0};{1} did not create remote tid</b>
ISC.0064.0001E	<b>HttpContext cannot clone self</b>
<b>Explanation</b>	The Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
ISC.0064.0011W	<b>Invalid maxRedirects setting {0}</b>
<b>Explanation</b>	The watt.net.maxRedirects property is not valid. It must be an integer.
<b>Action</b>	Change the value of the watt.net.maxRedirects property to an integer.
ISC.0064.0012E	<b>Class not found: {0}</b>
<b>Explanation</b>	Integration Server encountered an internal error because it could not find a class in the namespace.
<b>Action</b>	Contact Software AG Global Support.
ISC.0064.0018E	<b>Unable to instantiate class: {0}</b>
<b>Explanation</b>	Integration Server encountered an internal error because it could not instantiate a class in the namespace.
<b>Action</b>	Contact Software AG Global Support.
ISC.0064.0029D	<b>Could not open Socket connection to proxy={0} Exception:{1}</b>
<b>Explanation</b>	An exception was encountered while making an FTP connection through a proxy server. See the exception for details.
<b>Action</b>	Check that the FTP proxy you are using is correctly configured on the Settings > Proxy Servers page of Integration Server Administrator.

<b>ISC.0064.0030W</b>	<b>The {0} property is not a valid integer: {1}.</b>
<b>Explanation</b>	An invalid value was specified for the property identified in the message. The value for this property must be an integer.
<b>Action</b>	Change the value of the property to an integer.
<b>ISC.0064.0031E</b>	<b>Unexpected NTLM message sequence. The expected message type is not NTLM Type 1 Message.</b>
<b>Explanation</b>	The provided NTLM authentication credentials are not valid.
<b>Action</b>	Provide valid NTLM authentication credentials.
<b>ISC.0064.9001E</b>	<b>Could not connect to ftp server: {0}</b>
<b>Explanation</b>	FTP server is not accessible.
<b>Action</b>	Ensure that the FTP server and port are valid. If FTP proxy is configured in Integration Server, ensure that the proxy settings are correct.
<b>ISC.0064.9002E</b>	<b>FTP host name or port number is not specified</b>
<b>Explanation</b>	FTP hostname cannot be null and port cannot be zero.
<b>Action</b>	Ensure that you provide valid values for FTP host and port fields.
<b>ISC.0064.9003</b>	<b>Fail to connect to FTP proxy: {0}+ port: {1}</b>
<b>ISC.0064.9004E</b>	<b>Fail to connect to FTP server: {0} port: {1}</b>
<b>Explanation</b>	Integration server is unable to access the FTP server.
<b>Action</b>	Ensure that the FTP host and port fields contain valid values. If FTP host and port fields contain valid values and if Integration Server is still unable to access FTP server, contact Software AG Global Support.
<b>ISC.0064.9005E</b>	<b>{0}</b>
<b>Explanation</b>	Credentials of the FTP user are invalid.
<b>Action</b>	Ensure that the FTP user, password, and account fields have correct and valid values. Set the log level of Network Services component (64) to 'trace' to get more details.

---

<b>ISC.0064.9006E</b>	{0}
<b>Explanation</b>	FTP proxy server that you have configured does not support the SITE command.
<b>Action</b>	Check the FTP proxy server configuration to ensure that the FTP proxy server supports the SITE command. Set the log level of Network Services component (64) to 'trace' to get more details.
<b>ISC.0064.9007E</b>	{0}
<b>Explanation</b>	FTP proxy server that you have configured does not support the OPEN command.
<b>Action</b>	Check the FTP proxy server configuration to ensure that the FTP proxy server supports the OPEN command. Set the log level of Network Services component (64) to 'trace' to get more details.
<b>ISC.0064.9008E</b>	<b>FTP PORT command failed</b>
<b>Explanation</b>	FTP server encountered an error while sending the PORT command.
<b>Action</b>	The following lists the actions you can take:  <ol style="list-style-type: none"><li>1. Ensure that the FTP server implements the PORT command.</li><li>2. Ensure that the user has the permission to execute the command.</li><li>3. If the problem still persists, contact Software AG Global Support. Set the log level of Network Services component (64) to 'trace' to get more details.</li></ol>
<b>ISC.0064.9009E</b>	<b>Invalid Data Channel</b>
<b>Explanation</b>	FTP client is not able to create a data port for listening. In FTP Active mode, client creates a port for data connection and FTP server opens a connection to the client data port.
<b>Action</b>	Ensure that the data port specified in the FTP client is available.  -OR-  Use FTP passive transfer mode.  Set the log level of Network Services component (64) to 'trace' to get more details.
<b>ISC.0064.9010E</b>	{0}
<b>Explanation</b>	FTP server is not able to connect to the data port of the client. The possible cause for this is that the data port might be blocked by a firewall on the client side.
<b>Action</b>	The following lists the actions you can take:  <ol style="list-style-type: none"><li>1. Check whether the client is behind a firewall. If yes, make sure that the firewall allows the connection from the server.</li><li>2. Use FTP passive transfer mode.</li></ol>

3. Increase the connection timeout of data port using `watt.net.ftpClientDataConnTimeout` property.

<b>ISC.0064.9012E</b>	<b>Socket close err. {0}</b>
<b>Explanation</b>	FTP server encountered an error while closing the FTP client socket.
<b>Action</b>	Contact Software AG support team.
<b>ISC.0064.9013E</b>	<b>{0}</b>
<b>Explanation</b>	FTP server is not accessible.
<b>Action</b>	Contact Software AG support team. Set the log level of Network Services component(64) to trace to get more details.
<b>ISC.0064.9014E</b>	<b>Content must be of type byte[], String or InputStream</b>
<b>Explanation</b>	The content type of the data sent to the FTP server is not of type byte array, string, or InputStream.
<b>Action</b>	Make sure that the data sent to the FTP server is of type byte array, string, or InputStream.
<b>ISC.0064.9015E</b>	<b>FTP AUTH command failed with error code {0}</b>
<b>Explanation</b>	An FTP client sent an AUTH command to establish an FTPS connection with the Integration Server, but the command failed with the indicated return code.
<b>Action</b>	Check your FTP documentation for the possible causes of the FTP return code. In addition, check the server log and error log for possible causes for the error.
<b>ISC.0064.9016E</b>	<b>FTP AUTH command failed with error {0}</b>
<b>Explanation</b>	An FTP client sent an AUTH command to establish an FTPS connection with the Integration Server, but the command failed.
<b>Action</b>	Check your FTP documentation for the possible causes of the FTP error message. In addition, check the server log and error log for possible causes for the error.
<b>ISC.0064.9017E</b>	<b>FTP PBSZ command failed with error code {0}</b>
<b>Explanation</b>	An FTP client sent a PBSZ command to establish a secure connection between the client and Integration Server, but the command failed with the indicated return code.
<b>Action</b>	Check your FTP documentation for the possible causes of the FTP error message. In addition, check the server log and error log for possible causes for the error.

<b>ISC.0064.9018E</b>	<b>FTP PROT command failed with error code {0}</b>
<b>Explanation</b>	An FTP client sent a PROT command to establish a secure connection between the client and Integration Server, but the command failed with the indicated return code.
<b>Action</b>	Check your FTP documentation for the possible causes of the FTP error message. In addition, check the server log and error log for possible causes for the error.
<b>ISC.0064.9019E</b>	<b>FTP EPRT command failed with error {0}</b>
<b>Explanation</b>	The FTP server returned an error for the EPRT command sent by the Integration Server FTP client.
<b>Action</b>	Ensure that the FTP server implements the EPRT command. Ensure that the user has the permission to execute the command. Set the log level of Network Services facility (facility number 64) to 'trace' to get more details. If the problem persists, contact Software AG Global Support.
<b>ISC.0072.0010</b>	<b>Index {0} out of bounds for key {1}</b>
<b>ISC.0072.0011</b>	<b>value missing name. key={0}</b>
<b>ISC.0072.0014</b>	<b>LoopToken.evalArray unknown array type:{0}</b>
<b>ISC.0072.0016</b>	<b>Exception:{0} executing included template.</b>
<b>ISC.0072.0017</b>	<b>IfVarToken.processArgs value:{0} index:{1} ret:{2}</b>
<b>ISC.0072.9001E</b>	<b>Unknown service: {0}</b>
<b>Explanation</b>	Integration Server encountered an internal error because it could not find a requested service in the namespace.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0072.9002E</b>	<b>Reporter died from IOException: {0}</b>
<b>Explanation</b>	The Reporter.createTemplateFromFile() class issued an error because it could not read the template from the supplied file.
<b>Action</b>	Examine the use of the Reporter class in your application and make sure that the application has proper Read access to the template file.

<b>ISC.0076.0001</b>	<b>BinCoder decode error creating IData {0}, using {1} instead. Excpt:{2}</b>
<b>ISC.0076.0002</b>	<b>BinCoder decode error creating IDataCodable {0}, using {1} instead. Excpt:{2}</b>
<b>ISC.0076.0003</b>	<b>BinCoder decode error creating Codable {0}. Excpt:{1}</b>
<b>ISC.0076.0004</b>	<b>BinCoder decode error creating as String {0}, s={1}. Excpt:{2}</b>
<b>ISC.0076.0005E</b>	<b>BinCoder decode error creating Java serialized object. Excpt:{0}</b>
<b>Explanation</b>	The java.io.ObjectInputStream.readObject() service encountered an error while trying to decode a Java serialized object. For a ClassNotFoundException, the most likely cause is that a client performing a remote invoke placed a class definition into the pipeline, but the class definition does not exist on the receiving Integration Server. For an InvalidClassException, the most likely cause is that the class definition on the Integration Server does not match the class definition placed in the pipeline by the client.
<b>Action</b>	Make sure that the originating client and the receiving Integration Server have the same class definitions. For other I/O exceptions, there might be corruption in the input stream; therefore, you should try the request again.
<b>ISC.0076.0006</b>	<b>BinCoder decode error creating array {0}</b>
<b>ISC.0076.0007</b>	<b>XMLCoder decode invalid data type: {0}</b>
<b>ISC.0076.0008E</b>	<b>XMLCoder decode exception: {0}</b>
<b>Explanation</b>	Integration Server threw an exception while decoding an IDataXML encoded document.
<b>Action</b>	The document is corrupt. Contact Software AG Global Support.
<b>ISC.0076.0009E</b>	<b>RPCBinCoder2 decode error for array class: {0}</b>
<b>Explanation</b>	Integration Server encountered an error while trying to decode an array of remote objects. Class definitions might be out of sync.
<b>Action</b>	Contact Software AG Global Support.

---

<b>ISC.0076.0010E</b>	<b>RPCBinCoder2 decode error for Codable class: {0}</b>
<b>Explanation</b>	Integration Server encountered an error while trying to decode a codable class. Class definitions might be out of synch.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0076.0011E</b>	<b>RPCBinCoder2 decode error for as_String class: {0}</b>
<b>Explanation</b>	Integration Server encountered an error while trying to decode an object that was encoded as a String.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0076.0012E</b>	<b>SOAP Encoding Registrar cannot register schema type {0}; schema type already exists.</b>
<b>Explanation</b>	The SOAP Encoding Registrar could not register the indicated schema type. This is a serious internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0076.0013E</b>	<b>SOAP Message Coder cannot encode output data; pipeline does not match output signature</b>
<b>Explanation</b>	The SOAP message coder could not XML-encode the results of a SOAP remote procedure call because a variable appeared in the pipeline more than once.
<b>Action</b>	Examine the target service to determine why it is not producing output values that match the output signature. Correct the service's signature and/or logic after identifying the source of the problem.
<b>ISC.0076.0014U</b>	<b>SOAP Message Coder failure; a RuntimeException was thrown in the SOAP Coder</b>
<b>Explanation</b>	The message coder encountered a serious internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0076.0015E</b>	<b>SOAP Message Coder cannot encode variable {0}; variable does not have a valid XML name</b>
<b>Explanation</b>	The message coder could not XML-encode the SOAP RPC request or response because the pipeline contained the variable <varName>, whose name is not a valid name for an XML element.
<b>Action</b>	This error often occurs because the variable name contains a colon (:). Change the name of <varName> to one that is also valid as an XML element name (or map <varName> to a new variable, and use that variable as your SOAP RPC input or output parameter).

<b>ISC.0076.0016</b>	<b>Soap Message Coder warning; unregistered coder for variable {0}, using String</b>
<b>ISC.0076.0017E</b>	<b>SOAP Message Coder error; no coder is registered for encoding style {0}</b>
<b>Explanation</b>	The message coder encountered a serious internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0076.0018</b>	<b>Soap Message Coder warning; unregistered coder for variable {0}, using BasicData</b>
<b>ISC.0076.0019E</b>	<b>SOAP Message Coder cannot decode message; encoding style {0} is not a registered style</b>
<b>Explanation</b>	The message coder could not decode the submitted XML because it does not support the specified encoding style.
<b>Action</b>	Check the incoming XML and verify that the encodingStyle attribute is specified correctly and that it specifies a style that Integration Server supports.
<b>ISC.0076.0020E</b>	<b>Soap Message Coder warning; invalid HREF found {0}</b>
<b>Explanation</b>	The message coder could not resolve the href pointing to reference. A null value was produced instead.
<b>Action</b>	Examine the incoming XML and make sure that the specified reference points to an element that exists in the body of the message.
<b>ISC.0076.0021E</b>	<b>SOAP Message Coder cannot decode message; arrayType attribute value {0} is malformed</b>
<b>Explanation</b>	The message coder could not decode an XML-encoded array because it cannot understand the value of the "arrayType" attribute.
<b>Action</b>	Check the incoming XML and make sure that the "arrayType" attribute is using the correct syntax. For example, make sure that it is not missing a "[" symbol.
<b>ISC.0076.0022E</b>	<b>SOAP Message Coder cannot decode message; cannot determine type of element {0}</b>
<b>Explanation</b>	The message coder could not decode the XML-encoded parameters it has received, because the simple element <elementName> has an unknown data type (for example, xsi:type="myDataType").
<b>Action</b>	Check the incoming XML and make sure the data type has been specified correctly. Also make sure that it is using the correct namespace.

<b>ISC.0076.0023E</b>	<b>SOAP Message Coder cannot decode message; unable to create array for arrayType attribute value {0}</b>
<b>Explanation</b>	The message coder could not decode an XML-encoded array because it could not allocate an array of the specified dimensions.
<b>Action</b>	Check the incoming XML and make sure that the arrayType attribute is specified correctly. For example, make sure that it does not specify a negative dimension or an invalid array size (e.g., too many dimensions or dimensions that are unrealistically large). If the array is unusually large or the server is extremely very low on memory, the possibility also exists that this error was the result of an out-of-memory condition.
<b>ISC.0076.0026E</b>	<b>Broker Coder cannot encode document; the document, document type or both are null values</b>
<b>Explanation</b>	While attempting to process a document from the Broker, Integration Server determined that the document, the document type, or both are null values. This is an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0076.0027E</b>	<b>Broker Coder cannot encode document; Broker document type name is missing</b>
<b>Explanation</b>	The subscribing Integration Server received a document from the Broker or a publishing Integration Server, but was unable to encode the document because the document type name was missing from the event subscription. There are three possible reasons: (1) the document to be encoded is corrupted (2) the document type is out of sync with the corresponding document type on the Broker (3) an internal error occurred.
<b>Action</b>	Examine the document to be encoded and synchronize the document type with the Broker. If the error persists after the synchronization, contact Software AG Global Support.
<b>ISC.0076.0028</b>	<b>Broker Coder cannot decode document; byte[] is in wire format version {0}. Latest supported format is version {1}</b>
<b>ISC.0076.0029</b>	<b>Broker Coder warning; multi-reference with sequence id {0} does not exist; using null value</b>
<b>ISC.0076.0030E</b>	<b>Broker Coder warning; cannot parse value {0}; using {1} instead</b>
<b>Explanation</b>	Integration Server was not able to parse the document. There are two possible reasons: (1) the document might be corrupted (2) the document type is out of sync with the corresponding document type on the Broker.
<b>Action</b>	Examine the document and make sure that it is not corrupted. Also, synchronize the document type with the corresponding Broker document type.

<b>ISC.0076.0031E</b>	<b>Broker Coder warning; cannot create an instance of {0}</b>
<b>Explanation</b>	Integration Server could not create an instance of the indicated class. This is an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0076.0032</b>	<b>Broker Coder cannot decode document; the document, document type or both are null values</b>
<b>ISC.0076.0033E</b>	<b>Broker Coder cannot decode document; the document does not conform to the document type, {0}</b>
<b>Explanation</b>	The subscribing Integration Server was not able to decode the incoming document from either the Broker or the publishing Integration Server because the document type on the local Integration Server is out of sync with the corresponding document types on the publishing Integration Server and the Broker.
<b>Action</b>	Synchronize the publishable document type on the subscribing Integration Server with the corresponding Broker document type.
<b>ISC.0076.0034</b>	<b>Priority Classloader could not load the class while decoding.Trying Global classloader.</b>
<b>ISC.0076.9001U</b>	<b>Unsupported RPC type: {0}</b>
<b>Explanation</b>	Integration Server RPC Bin Coder does not support the version specified in the input stream to be decoded. This is an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0076.9002U</b>	<b>incorrect IDataXMLCoder file format: no element 'IDataXMLCoder' found</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0076.9003U</b>	<b>encoding {0}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.

---

<b>ISC.0076.9004U</b>	<b>decoding: {0} ex:{1}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0076.9005U</b>	<b>decoding: boolean ex:{0}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0076.9006U</b>	<b>decoding: {0}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0076.9007U</b>	<b>decoding: No null-arg create method in class: {0}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0076.9008U</b>	<b>Unsupported RPC type: {0}</b>
<b>Explanation</b>	Integration Server RPC Bin Coder does not support the version specified in the input stream to be decoded. This is an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0076.9009U</b>	<b>Root element is null</b>
<b>Explanation</b>	The flow.xml or node.ndf file is corrupt.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0076.9010U</b>	<b>Sibling root element is null rootTag:{0} localName:{1} root:{2}</b>
<b>Explanation</b>	The XMLCoder class issued an error because the supplied XML input stream cannot be decoded.
<b>Action</b>	Examine the use of the XMLCoder class in your application and make sure that the XML input stream has the correct format and it only contains supported object types. If the error still occurs, use the setIgnoreInvalid() class to set the flag to false so that XMLCoder ignores the unsupported object type that it decodes.

<b>ISC.0076.9011U</b>	<b>illegal file format</b>
<b>Explanation</b>	The service pub.flow:restorePipelineFromFile failed to execute because the file containing the saved pipeline was not encoded with XMLCoder or IDataXMLCoder.
<b>Action</b>	Examine the file containing the saved pipeline and make sure it is not corrupt. If the file was saved using the pub.flow:savePipelineToFile service, and it is not corrupt, contact Software AG Global Support.
<b>ISC.0076.9012E</b>	<b>Invalid state. JSON input stream does not start with the "{" character.</b>
<b>Explanation</b>	The input stream does not contain valid JSON content. JSON content must begin with the "{" character.
<b>Action</b>	Add a "{" character to the beginning of the JSON content.
<b>ISC.0076.9013E</b>	<b>Invalid state. JSON Object in the input stream does not end with "}" character.</b>
<b>Explanation</b>	The JSON object in the input stream does not contain valid JSON content. The JSON object content must end with the "\"}\" character.
<b>Action</b>	Add a "\"}\" character to the end of the JSON object.
<b>ISC.0076.9014E</b>	<b>Invalid state. JSON input stream contains incorrect syntax.</b>
<b>Explanation</b>	The JSON input stream contains incorrect JSON syntax.
<b>Action</b>	Correct the errors in the JSON input stream.
<b>ISC.0076.9015E</b>	<b>Invalid state. JSON Object in the input stream does not start with "{" character.</b>
<b>Explanation</b>	The JSON object in the input stream does not contain valid JSON content. The JSON object content must begin with the "{" character.
<b>Action</b>	Add a "{" character to the beginning of the JSON object in the input stream.
<b>ISC.0076.9016E</b>	<b>Invalid state. Array in the JSON input stream does not end with "]" character.</b>
<b>Explanation</b>	The JSON array in the input stream does not contain valid JSON content. The JSON array must end with the "]" character.
<b>Action</b>	Add the "]" character from the end of the JSON array.
<b>ISC.0076.9017E</b>	<b>Numeric value ({0}) for field {1} is outside the range for integer values. Integers must be within the range of -2147483648 to 2147483647. Error:{2}</b>
<b>Explanation</b>	Integration Server encountered an invalid integer value while parsing a JSON object.
<b>Action</b>	Correct the value before parsing the JSON object.

---

<b>ISC.0076.9018E</b>	<b>Numeric value ({0}) for field {1} is outside the range for long numbers. Long numbers must be within the range of -9223372036854775808 to 9223372036854775807. Error:{2}</b>
<b>Explanation</b>	Integration Server encountered an invalid long number value while parsing a JSON object.
<b>Action</b>	Correct the value before parsing the JSON object.
<b>ISC.0076.9019E</b>	<b>Numeric value ({0}) for field {1} is outside the range for float values. Error:{2}</b>
<b>Explanation</b>	Integration Server encountered an invalid float value while parsing a JSON object.
<b>Action</b>	Correct the value before parsing the JSON object.
<b>ISC.0076.9020E</b>	<b>Numeric value ({0}) for field {1} is outside of the range for double values. Error:{2}</b>
<b>Explanation</b>	Integration Server encountered an invalid double value while parsing a JSON object.
<b>Action</b>	Correct the value before parsing the JSON object.
<b>ISC.0076.9101E</b>	<b>SOAP Encoding Registrar cannot register encoding style {0}; encoding style already exists.</b>
<b>Explanation</b>	Integration Server cannot register the specified encoding style because the encoding style is already registered.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0076.9102E</b>	<b>SOAP Encoding Registrar cannot register Java type {0}; Java type already exists.</b>
<b>Explanation</b>	Integration Server cannot register the specified Java type because it already exists in the registry.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0076.9103E</b>	<b>SOAP Encoding Registrar cannot register Schema type {0}; Schema type already exists.</b>
<b>Explanation</b>	Integration Server cannot register the specified Schema type because it already exists in the registry.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0076.9104E</b>	<b>SOAP Encoding Registrar cannot unregister Java type {0}; doesn't exist in the registry</b>
<b>Explanation</b>	Integration Server cannot unregister the specified Java type because it does not exist in the registry.
<b>Action</b>	Contact Software AG Global Support.

<b>ISC.0076.9105E</b>	<b>SOAP Encoding Registrar cannot unregister Schema type {0}; doesn't exist in the registry</b>
<b>Explanation</b>	Integration Server cannot unregister the specified Schema type because it does not exist in the registry.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0076.9202E</b>	<b>SOAP Message Coder failure; a RuntimeException was thrown in the SOAP Coder</b>
<b>Explanation</b>	The SOAP message contains an element that does not have a valid QName.
<b>Action</b>	Make sure the elements in the SOAP message have valid QNames.
<b>ISC.0076.9203E</b>	<b>SOAP Message Coder cannot decode message; Invalid number {0}</b>
<b>Explanation</b>	The message coder could not decode an XML-encoded array because one of its dimensions is set to a nonnumeric value.
<b>Action</b>	Check the incoming XML and make sure that the arrayType attribute specifies a positive integer. For example, make sure it has not been inadvertently set to a nonnumeric value such as "A".
<b>ISC.0076.9204E</b>	<b>SOAP Message Coder cannot encode output data; pipeline does not match output signature, duplicate variable {0} in pipeline</b>
<b>Explanation</b>	The message coder could not XML-encode the results of a SOAP remote procedure call because the specified variable appeared in the pipeline more than once.
<b>Action</b>	On the Integration Server, examine the target service to determine why it is not producing output values that match the output signature. Correct the service's signature and/or logic after identifying the source of the problem.
<b>ISC.0076.9205E</b>	<b>SOAP Message Coder cannot encode variable {0}; variable does not have a valid XML name</b>
<b>Explanation</b>	The message coder could not XML-encode the SOAP RPC request or response because the pipeline contained the specified variable, whose name is not a valid name for an XML element.
<b>Action</b>	This error often occurs because the variable name contains a colon (:). Change the name of specified variable to one that is also valid as an XML element name (or map the variable to a new variable, and use the target variable as your SOAP RPC input or output parameter).

---

<b>ISC.0076.9206E</b>	<b>SOAP Message Coder error; no coder is registered for encoding style {0}</b>
<b>Explanation</b>	Integration Server encountered a serious internal error when encoding the SOAP message.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0076.9208E</b>	<b>SOAP Message Coder cannot decode message; cannot determine type of element {0}</b>
<b>Explanation</b>	The message coder could not decode the XML-encoded parameters it has received, because the specified element has an unknown data type (for example, <code>xsi:type="myDataType"</code> ).
<b>Action</b>	Check the incoming XML and make sure the data type has been specified correctly. Also make sure that it is using the correct namespace.
<b>ISC.0076.9209E</b>	<b>SOAP Message Coder cannot decode message; unable to create array for arrayType attribute value {0}</b>
<b>Explanation</b>	The message coder could not decode an XML-encoded array because it could not allocate an array of the specified dimensions.
<b>Action</b>	Check the incoming XML and make sure that the arrayType attribute is specified correctly. For example, make sure that it does not specify a negative dimension or an invalid array size (e.g., too many dimensions or dimensions that are unrealistically large). If the array is unusually large or the server is extremely very low on memory, the possibility also exists that this error was the result of an out-of-memory condition.
<b>ISC.0076.9210E</b>	<b>SOAP Message Coder cannot decode message; arrayType attribute value {0} is malformed</b>
<b>Explanation</b>	The message coder could not decode an XML-encoded array because it cannot understand the value of the arrayType attribute.
<b>Action</b>	Check the incoming XML and make sure that the arrayType attribute is using the correct syntax. For example, make sure that it is not missing a “[” symbol.
<b>ISC.0076.9211E</b>	<b>SOAP Message Coder cannot encode output data; pipeline does not match output signature, required variable {0} is missing</b>
<b>Explanation</b>	The message coder could not transform the results of a SOAP remote procedure call because the required variable varName was not in the pipeline.
<b>Action</b>	On Integration Server, examine the target service to determine why it is not producing the required output variables. Correct the service signature and/or logic after identifying the source of the problem.

**ISC.0076.9212E**      **SOAP Message Coder cannot encode output data; pipeline does not match output signature, extra variable {0} in pipeline**

**Explanation**      Integration Server encountered an error while processing an RPC/Encoded SOAP message. Either the SOAP message does not match the output signature of the service or the contents of the output pipeline produced by the service do not match the service signature.

**Action**            Do one or more of the following:

- Change the SOAP message response so that it matches the service output signature.
- Change the service output signature so that it matches the expected SOAP message response.
- Ensure that the service produces an output pipeline that matches the service signature.

**ISC.0076.9220E**      **{0} Coder: decoding error; illegal input parameter value(s)**

**Explanation**      One of the input parameters to the encode or decode method is null.

**Action**            Make sure that the input parameters passed to the encode or decode methods are not null.

**ISC.0076.9221E**      **{0} Coder: decoding error; can't get the SOAP Body from the SOAP Message**

**Explanation**      The SOAP body element cannot be retrieved from the SOAP message.

**Action**            Make sure that the SOAP message is valid and contains a SOAP body element.

**ISC.0076.9222E**      **{0} Coder: decoding error; can't convert SOAP Message to IS Document**

**Explanation**      Integration Server cannot convert a SOAP message to a document (IData) because of a decoding error.

**Action**            Contact Software AG Global Support.

**ISC.0076.9230E**      **{0} Coder: encoding error; can't create SOAP Message**

**Explanation**      Integration Server cannot create the SOAP message because an encoding error occurred.

**Action**            Contact Software AG Global Support.

<b>ISC.0076.9231E</b>	<b>{0} Coder: encoding error; can't add SOAP Body Element to SOAP Message</b>
<b>Explanation</b>	Integration Server cannot add the SOAP body element to the SOAP message because of an encoding error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0076.9234E</b>	<b>{0} Coder: encoding error; can't convert IS Document to XML String</b>
<b>Explanation</b>	Integration Server cannot convert the document (IData) to an XML String because of an encoding error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0076.9236E</b>	<b>SOAP Message Coder cannot decode message; value "{0}" doesn't match expected pattern yyyy-MM-dd</b>
<b>Explanation</b>	The date pattern is invalid.
<b>Action</b>	Make sure that the date value uses the pattern yyyy-MM-dd.
<b>ISC.0077.0001E</b>	<b>Config set local host error. Excppt:{0}</b>
<b>Explanation</b>	During startup, Integration Server was not able to set local host information from the values specified on the "watt.net.localhost" property.
<b>Action</b>	Examine the value specified for property "watt.net.localhost". The value can either be a machine host name or a string representing the machine's IP address, such as "localhost" or "127.0.0.1".
<b>ISC.0077.0002</b>	<b>Unsupported email encoding {0} specified. Defaulting to {1}</b>
<b>ISC.0077.0003S</b>	<b>Cannot initialize password store with null manager</b>
<b>Explanation</b>	Initialization of the code that manages outbound passwords failed. The most likely cause is a problem with the outbound password configuration files.
<b>Action</b>	Make sure that the following outbound password configuration files reside on the Integration Server:  config/txnPassStore.dat  config/empw.dat  config/configPassman.cnf  config/passman.cnf  See the webMethods Integration Server documentation for information about these files and to determine whether you can restore them. If you cannot determine the source of the problem, contact Software AG Global Support.

<b>ISC.0077.0004S</b>	<b>Exception during {0}, type: {1}, msg: {2}</b>
<b>Explanation</b>	A problem occurred when Integration Server tried to store or retrieve an outbound password or retrieve an encryption code from the outbound password store.
<b>Action</b>	The outbound password data store, config/txnPassStore.dat, is probably corrupted. See the webMethods Integration Server documentation for information about this file and how to restore it and other outbound password configuration files. If you cannot determine the source of the problem, contact Software AG Global Support.
<b>ISC.0077.0005</b>	<b>Unable to {0}, password mgr is null</b>
<b>ISC.0077.0006E</b>	<b>System property "{0}" equals "{1}". This value is not valid. The default value of "{2}" will be used instead.</b>
<b>Explanation</b>	Integration Server detected an invalid value on the indicated configuration file property.
<b>Action</b>	Refer to the webMethods Integration Server documentation for a description of the property and its required or allowed values.
<b>ISC.0077.9001</b>	<b>Stream is already closed</b>
<b>ISC.0077.9003</b>	<b>Source directory does not exist</b>
<b>ISC.0077.9004</b>	<b>Source File not a directory</b>
<b>ISC.0077.9006E</b>	<b>Could not determine encoding of file {0}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0077.9007E</b>	<b>Invalid encoding, {0}, specified for file {1}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0077.9009</b>	<b>Local name cannot be null</b>

---

ISC.0077.9010	<b>Local name cannot be an empty string.</b>
ISC.0077.9011	<b>Namespace name cannot be an empty string.</b>
ISC.0077.9012	<b>Invalid value {0} specified for local name.</b>
ISC.0077.9013U	<b>Document to XSD error: Field {0} cannot be represented in XML Schema. The field name contains a prefix but an XML Namespace property is not assigned to the field</b>
<b>Explanation</b>	The document type being used to generate a WSDL document contains a top-level variable whose name includes a prefix (that is, the name is in the format prefix:local name). This variable is not associated with an XML namespace.
<b>Action</b>	Do one of the following:  (1) Associate the variable with an XML namespace by specifying a value for the variable's XML Namespace property.  (2) Remove the prefix. Note that some protocols require the use of a prefix. Before removing the prefix, check the service signature's input and output requirements as documented for each protocol in the webMethods Integration Server documentation.
ISC.0077.9014U	<b>Document to XSD error: Field {0} cannot be represented in XML Schema. The field name does not conform to the XML NCName definition</b>
<b>Explanation</b>	The document type being used to generate a WSDL document contains field names that do not conform to the XML NCName definition.
<b>Action</b>	To resolve this error, rename the fields to conform to the QName lexical rules specified in <a href="http://www.w3.org/TR/REC-xml-names/#NT-QName">http://www.w3.org/TR/REC-xml-names/#NT-QName</a> and the XML namespace and local naming conventions specified in <a href="http://www.w3.org/TR/REC-xml-names/#NT-NCName">http://www.w3.org/TR/REC-xml-names/#NT-NCName</a> .
ISC.0077.9015E	<b>The amount of data needed is greater than the amount of data reserved.</b>
<b>Explanation</b>	A service needed to write a large amount of data to tspace, but the space the service reserved is not large enough to hold the data.
<b>Action</b>	Update your program to reserve more tspace. If your program does not reserve tspace directly, contact Software AG Global Support.

- ISC.0077.9016**      **Provided private key {0} is invalid.**
- ISC.0077.9017**      **Unable to read the key/certificate file(s) {0}.**
- ISC.0077.9018**      **Provided certificate(s) {0} is/are invalid.**
- ISC.0077.9022E**      **XOPObject content cannot be read more than once.**  
**Explanation**      You attempted to read the contents from an XOPObject. However, previous logic in either the same service or a previous service has already read the XOPObject. The XOPObject instance can only be read one time.  
**Action**              Update the service logic so that it reads an XOPObject only one time.
- ISC.0077.9023E**      **Error while parsing the "{0} {1}" XML string. Parser error: {2}; XML: {3}**  
**Explanation**      One of the reference parameters or metadata elements that you specified as message addressing property is not a valid XML string.  
**Action**              Ensure that the XML string that you specify as message addressing reference parameter or metadata element is correct.
- ISC.0077.9024E**      **Error while parsing the "{0} {1}" XML string. The XML that you specify should be namespace qualified. XML: {2}**  
**Explanation**      One of the reference parameters that you specified as the message addressing property is not a namespace qualified XML string.  
**Action**              Ensure that the XML string that you specify as message addressing reference parameter element is namespace qualified.
- ISC.0081.0002**      **Error registering universal name {0}, already registered to {1}**
- ISC.0081.0003**      **Registered universal name {0} on service {1}**
- ISC.0081.0004**      **Duplicate universalName {0} registered to a different service {1}, not this service {2}. Unregister failed.**

---

<b>ISC.0081.0005E</b>	<b>Could not create a unique ID for the trigger from the trigger's name.</b>
<b>Explanation</b>	Integration Server was unable to create a unique identifier for the trigger. This is an internal error.
<b>Action</b>	Try to recreate the trigger. If that fails, contact Software AG Global Support. Be prepared to provide logs and the version number and patch level for Integration Server and your operating system.
<b>ISC.0081.9001E</b>	<b>Node {0} does not exist</b>
<b>Explanation</b>	The specified element cannot be locked because it does not exist. The element might have already been deleted. Alternatively, another user might have been deleted the element at the same time an attempt to lock the element was made.
<b>Action</b>	Make sure that the element exists.
<b>ISC.0081.9002E</b>	<b>Cannot perform operation without Write ACL privileges on {0}</b>
<b>Explanation</b>	The specified element cannot be locked because the user attempting to lock the element does not have write permissions to the element. To lock an element, a user must be a member of the Write ACL assigned to the element.
<b>Action</b>	Make sure that the user has write access to the element before attempting to lock it
<b>ISC.0081.9003E</b>	<b>Unable to lock: {0}. It has been locked by user {1}.</b>
<b>Explanation</b>	The specified element cannot be locked because it is already locked by another user.
<b>Action</b>	Before locking an element, make sure it is not locked by another user.
<b>ISC.0081.9004E</b>	<b>universalName {0} is already registered</b>
<b>Explanation</b>	The specified universal name already exists and is assigned to another element.
<b>Action</b>	Specify a unique universal name that is not already used by another element.
<b>ISC.0081.9005E</b>	<b>Unknown content type: {0}</b>
<b>Explanation</b>	Integration Server cannot create an instance of the specified content type because Integration Server does not recognize or does not support the specified content type.
<b>Action</b>	Specify a content type supported by Integration Server.

<b>ISC.0081.9007E</b>	<b>Node exists</b>
<b>Explanation</b>	An element with this fully qualified name already exists on the Integration Server. Integration Server uses the following format for the fully qualified name: folder.subfolder1.subfolder2:element
<b>Action</b>	Specify an element name whose fully qualified name will be unique to the Integration Server.
<b>ISC.0081.9008E</b>	<b>Node '{0}' does not exist</b>
<b>Explanation</b>	A node (element) in the Integration Server namespace was not specified.
<b>Action</b>	Specify a node (element) in the Integration Server namespace.
<b>ISC.0081.9016E</b>	<b>Search expression {0} is not well-formed. Enter a valid regular expression or element name.</b>
<b>Explanation</b>	The regular expression syntax is not valid.
<b>Action</b>	Ensure that specified regular expression is valid and can be compiled into a valid pattern.
<b>ISC.0081.9164E</b>	<b>Exception occurred during generation of WSDL for service {0}: {1}</b>
<b>Explanation</b>	An error occurred while attempting to validate or generate WSDL for a Web service descriptor. The error text identifies the specific error details.
<b>Action</b>	Use the error details to correct the issue before attempting to save the Web service descriptor or request WSDL for the Web service descriptor.
<b>ISC.0081.9165E</b>	<b>Invalid WSDL. Attribute {0} must appear in element {1} at Operation: {2}, Binding: {3}</b>
<b>Explanation</b>	While creating a Web service descriptor from a WSDL document, Integration Server found an invalid WSDL attribute. Most likely it was a soap:fault definition that was missing the name attribute.
<b>Action</b>	Correct the WSDL document before attempting to create the Web service descriptor.
<b>ISC.0081.9166E</b>	<b>Invalid "use" detected in Operation {0} at Binding {1}</b>
<b>Explanation</b>	While consuming a WSDL document to create a Web service descriptor, Integration Server encountered an invalid value for the use= attribute. The only valid values for the use attribute are "literal" or "encoded".
<b>Action</b>	Correct the use attribute value in the WSDL document and then attempt to create the Web service descriptor.

---

<b>ISC.0081.9167E</b>	<b>Output signature of an RPC/Literal or a Document/Literal operation cannot have top-level fields that are named "*body" or that begin with the "@" symbol. Operation Name : {0}</b>
<b>Explanation</b>	The output signature of a service used as an operation in an RPC/Literal binder cannot have top-level fields named "*body" or top-level fields that begin with "@".
<b>Action</b>	Change the output signature of the service before attempting to use the service as an operation in an RPC/Literal binder.
<b>ISC.0081.9169e</b>	<b>Input signature of an RPC/Encoded operation cannot have fields named "*body" or that begin with the "@" symbol. Operation Name : {0}</b>
<b>Explanation</b>	A service used as an operation in an RPC/Encoded binder cannot contain fields named "*body" or fields with a name that starts with "@" symbol.
<b>Action</b>	Before using the service as an operation in an RPC/Encoded binder, change the service signature to remove or rename the fields named "*body" or fields with a name that start with "@" symbol.
<b>ISC.0081.9170</b>	<b>Output signature of an RPC/Encoded operation cannot have fields named "*body" or that begin with the "@" symbol. Operation Name : {0}</b>
<b>Explanation</b>	The output signature of a service used as an operation for an RPC/Encoded binder cannot contain a field named "*body" or a field with a name that starts with "@".
<b>Action</b>	Change the output signature of the service before using the service as an operation in an RPC/Encoded binder.
<b>ISC.0081.9171E</b>	<b>Request header of an RPC/Encoded operation cannot have fields named named "*body" or that begin with the "@" symbol. Operation Name : {0}, Header : {1}</b>
<b>Explanation</b>	An attempt was made to add a Request Header to an operation used in an RPC/Encoded binder but the document type being added either has a field named "*body" or a field name starting with "@". Neither is allowed in a Header for an operation in an RPC/Encoded binder.
<b>Action</b>	Remove the fields named "*body" and the fields that start with "a" from the document type. Or use a document type that meets the field name requirements to define the format of the Header.
<b>ISC.0081.9172E</b>	<b>Response header of an RPC/Encoded operation cannot have fields named "*body" or that begin with the "@" symbol. Operation Name : {0}, Header : {1}</b>
<b>Explanation</b>	An attempt was made to add a Response Header to an operation in an RPC/Encoded binder but the document type being added either has a field named "*body" or a field name starting with "@". Neither is allowed in a Header for an operation in an RPC/Encoded binder.
<b>Action</b>	Change the document type to meet the field name requirements or use a different document type that meets the requirements to define the format of the Header.

**ISC.0081.9173E      Fault for an RPC/Encoded operation cannot have fields named "\*body" or that begin with the "@" symbol. Operation Name : {0}, Fault : {1}**

**Explanation**      An attempt was made to add a Fault to an RPC/Encoded operation but the document type being added either has a field named \*body or a field name starting with @. Neither is allowed in a Fault for an RPC/Encoded operation.

**Action**             Edit the document type to remove the fields named \*body or those that begin with the "@" symbol and then add the Fault to the RPC/Encoded operation. Or, select a different document type to define the format of the Fault.

**ISC.0081.9174E      Input signature of an RPC/Literal operation cannot have a List field at the top level. Operation Name : {0} Field : {1}**

**Explanation**      The input signature of a service used as an operation in a RPC/Literal binder contains a List field at the top level. Services used as operations in RPC/Literal binders cannot have List fields at the top level of the service input signature.

**Action**             Remove the List field from the service input signature before attempting to use the service as an operation in a RPC Literal Binder.

**ISC.0081.9175E      Output signature of an RPC/Literal operation cannot have a List field at the top level. Operation Name : {0} Field : {1}**

**Explanation**      The output signature of a service used as an operation in an RPC/Literal binder contains a List field at the top level. Services used as operations in RPC/Literal binders cannot have signatures that use List fields at the top level.

**Action**             Correct the service output signature before attempting to use the service as an operation in a RPC/Literal binder

**ISC.0081.9176E      Input signature of an RPC/Literal or a Document/Literal operation cannot have a String Table field. Operation Name : {0} Field : {1}**

**Explanation**      A service with a String table in its service signature cannot be used as an operation for an RPC/Literal or Document/Literal binder.

**Action**             Change the service signature before attempting to use it as an operation in an RPC/Literal or Document/Literal binder.

**ISC.0081.9177E      Output signature of an RPC/Literal or a Document/Literal operation cannot have a String Table field. Operation Name : {0} Field : {1}**

**Explanation**      The output signature of a service used as an operation in an RPC/Literal or Document/Literal binder cannot contain a String table.

**Action**             Change the service output signature before attempting to use the service as an operation in an RPC/Literal or Document/Literal binder.

<b>ISC.0081.9178E</b>	<b>Input signature of an RPC/Literal operation cannot have identically named fields at the top level. Operation Name : {0} Field : {1}</b>
<b>Explanation</b>	A service used as an operation in a RPC/Literal binder has an input signature containing identically named fields at the top level. All top-level field names must be unique for services used as operations in an RPC/Literal binder.
<b>Action</b>	Change the service signature before attempting to use the service as an operation in an RPC/Literal binder.
<b>ISC.0081.9179E</b>	<b>Output signature of an RPC/Literal operation cannot have identically named fields at the top level. Operation Name : {0} Field : {1}</b>
<b>Explanation</b>	A service used as an operation in an RPC/Literal binder contains fields with duplicate names at the top level in the output signature. All top-level field names must be unique for operations in RPC/Literal binders.
<b>Action</b>	Change the output signature of the service before attempting to use the service as an operation in an RPC/Literal binder.
<b>ISC.0081.9180E</b>	<b>Unable to find {0}, needed to generate WSDL for operation {1}</b>
<b>Explanation</b>	A service first provider Web service descriptor uses an IS service as an operation, but that IS service no longer exists in the Integration Server namespace.
<b>Action</b>	Edit the Web service descriptor to use an existing IS service as the operation or recreate the missing IS service.
<b>ISC.0081.9181E</b>	<b>Cannot find document type {0} needed to generate WSDL</b>
<b>Explanation</b>	An internal error has occurred while attempting to validate a Web service descriptor or generate WSDL for the Web service descriptor. The specified document type is used within the definition of the Web service descriptor but it cannot be found in the Integration Server namespace.
<b>Action</b>	If the Web service descriptor was created from WSDL document, for example a consumer Web service descriptor or a WSDL first provider Web service descriptor, delete the Web service descriptor and recreate it. If the Web service descriptor is a service first provider Web service descriptor, manually create the missing document type, or correct the references to the document type from the Web service descriptor (for example update the signatures of service used as operations, update Header definitions, or update Fault definitions).
<b>ISC.0081.9182E</b>	<b>Invalid WSDL schema generated for the service signatures or the document types referred by the WSD "{0}". To view the generated WSDL change the logging level of Namespace(0081) to Trace. Error details: {1}</b>
<b>Explanation</b>	This is a generic message that Integration Server throws for all Xerces parser errors.
<b>Action</b>	If Xerces parser throws "Unique Particle Attribute" error, then a possible workaround for this issue is to set the value of the 'Allow unspecified fields' constraint of the variables in the IS doc type referred by the Web service descriptor to 'False'.

<b>ISC.0081.9194E</b>	<b>The header has a message part "{0}" defined by the type "{1}". Message parts in a header must be defined by the element attribute instead of the type attribute.</b>
<b>Explanation</b>	An attempt was made to set the Pre 8.2 compatibility mode property to false for a Web service descriptor, but the WSDL document used to create the Web service descriptor has Header parts defined using the type attribute. For the Web service descriptor to have the Pre 8.2 compatibility mode property set to false, the Header parts in the WSDL document must use the element attribute.
<b>Action</b>	If you want the Web service descriptor to have a Pre 8.2 compatibility mode property set to false, change the Header parts in WSDL document to use the element attribute and then use Designer recreate the Web service descriptor.
<b>ISC.0081.9195E, W</b>	<b>Invalid message part(s) defined in the wsdl: {0}</b>
<b>Explanation</b>	An invalid Message Part definition was found while consuming WSDL to create a Web service descriptor. The error message lists the specific error details .
<b>Action</b>	Use the error details in the message to correct the WSDL. Then, use the corrected WSDL document to create the Web service descriptor.
<b>ISC.0081.9197E</b>	<b>Cannot find SOAP-JMS trigger "{0}" specified in the provider Web service endpoint alias "{1}" assigned to binder "{2}" in the web service descriptor "{3}".</b>
<b>Explanation</b>	The Web service endpoint alias assigned to the provider Web service descriptor uses a SOAP-JMS trigger that cannot be found. The provider Web service endpoint alias for use with a JMS binder is not valid if the SOAP-JMS trigger specified in the alias cannot be found. The Web service descriptor cannot be saved if a valid Web service endpoint alias is not assigned to a binder that specifies JMS as the transport.
<b>Action</b>	Update the provider Web service endpoint alias to use a different SOAP-JMS trigger. Alternatively, assign a different valid provider Web service endpoint alias to the binder.
<b>ISC.0081.9198E</b>	<b>Cannot find provider Web service endpoint alias "{0}" assigned to binder "{1}" in the web service descriptor "{2}".</b>
<b>Explanation</b>	The Web service endpoint alias assigned to the provider Web service descriptor cannot be found. The Web service descriptor cannot be saved if a Web service endpoint alias is not assigned to a binder that specifies JMS as the transport.
<b>Action</b>	Assign a valid provider Web service endpoint alias to the binder.
<b>ISC.0081.9199W</b>	<b>MEP for operations {0} has changed from In-Only MEP to In-Out MEP. As a result, Integration Server will now execute the corresponding response handlers.</b>
<b>Explanation</b>	Changing the Pre-8.2 compatibility mode property of the Web service descriptor from false to true resulted in a change of the Message Exchange Pattern (MEP) for the specified operations to In-Out. At run time, Integration Server will execute response handler services for the specified operations.
<b>Action</b>	No action required.

---

<b>ISC.0081.9200W</b>	<b>MEP for operations {0} has changed from In-Out MEP to In-Only MEP. As a result, Integration Server will no longer execute the corresponding response handler services.</b>
<b>Explanation</b>	Because the specified operation has no defined output, changing the Pre-8.2 compatibility mode property of the Web service descriptor from true to false resulted in a change of the Message Exchange Pattern (MEP) for the specified operations to In-Only. At run time, Integration Server will no longer execute the response handler services for the specified operations.
<b>Action</b>	No action required.
<b>ISC.0081.9201W</b>	<b>MEP for operations {0} has changed from Robust In-Only MEP to In-Out MEP.</b>
<b>Explanation</b>	Changing the Pre-8.2 compatibility mode property of the Web service descriptor from false to true resulted in a change of the Message Exchange Pattern (MEP) for the specified operations to In-Out.
<b>Action</b>	No action required.
<b>ISC.0081.9203W</b>	<b>Invoke RefreshConnectors against the Web service descriptor to have the Web service connector's signature updated to reflect the change to the compatibility mode.</b>
<b>Explanation</b>	After changing the Pre-8.2 compatibility mode property for a consumer Web service descriptor, the Web service connectors need to be refreshed. If an operation does not have any defined output, refreshing the Web service connectors will update the output signature to reflect the compatibility mode change. If you changed the Pre-8.2 compatibility mode property to false, the Web service connector will no longer have any SOAP message-related output parameters. If you changed the Pre-8.2 compatibility mode property to true, the output signature will include an output parameter for a SOAP fault.
<b>Action</b>	Refresh the Web service connectors for this Web service descriptor.
<b>ISC.0081.9204E</b>	<b>Web service descriptor {0} is not available because the WS-Policy file with policy ID {1} attached to the WSD is not present in the policy repository.</b>
<b>Explanation</b>	The Web service descriptor is not available because the WS-Policy file attached to the Web service descriptor is deleted or moved from the policy repository.
<b>Action</b>	The following lists the actions you can take: 1) Ensure that the WS-Policy that is attached to the Web service descriptor resides in the policy repository. -OR- 2) Edit the Web service descriptor so that it no longer uses the deleted or moved WS-Policy file.

<b>ISC.0081.9207E</b>	<b>Invalid WSDL. wsdl:fault element named {0} must be present in operation {1} of port type {2}</b>
<b>Explanation</b>	The WSDL document used to create the WSDL first provider or consumer Web service descriptor does not contain wsdl:fault element in the wsdl:operation of the portType.
<b>Action</b>	Ensure that the WSDL contains the correct wsdl:fault element in the wsdl:operation of the portType. Contact Software AG Global Support for further assistance.
<b>ISC.0082.0001</b>	<b>Type {0} exists in schema {1}. Set {1} as owner schema.</b>
<b>ISC.0082.483E</b>	<b>"fractionDigits"+STR_BASE_FACET_FIXED</b>
<b>Explanation</b>	The fractionDigits facet is fixed for the type and cannot be changed
<b>Action</b>	Do not attempt to change the fractionDigits value for the type.
<b>ISC.0082.90007E</b>	<b>Missing Attribute Information Item</b>
<b>Explanation</b>	The attribute is declared as required but is missing from the instance document.
<b>Action</b>	Correct the instance document.
<b>ISC.0082.9001E</b>	<b>Error while parsing "{0}"</b>
<b>Explanation</b>	An unexpected error occurred while validating the instance document.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0082.9002E</b>	<b>Unable to retrieve root element</b>
<b>Explanation</b>	The instance document does not have a root element and cannot be validated.
<b>Action</b>	Correct the instance document.
<b>ISC.0082.9003E</b>	<b>Unable to locate a matching element declaration</b>
<b>Explanation</b>	The element in the instance document does not have an element declaration.
<b>Action</b>	Correct the instance document. Ensure that the element name is correctly spelled.
<b>ISC.0082.9004E</b>	<b>[attributes] property must be empty</b>
<b>Explanation</b>	The element is defined to be of simple type. No attributes may be present.
<b>Action</b>	Remove the attributes from the element in the instance document, or use an element that permits the attribute.

---

<b>ISC.0082.9005E</b>	<b>EII (s) are not allowed in [children] property</b>
<b>Explanation</b>	The element type does not allow child elements to be present in the content.
<b>Action</b>	Remove the child elements from the instance document, or use a type definition that permits the desired child elements.
<b>ISC.0082.9006E</b>	<b>Unable to locate a matching attribute declaration</b>
<b>Explanation</b>	Integration Server could not locate an attribute declaration for the attribute.
<b>Action</b>	Correct the instance document to reference an attribute for which there is a declaration or remove the attribute from the instance document.
<b>ISC.0082.9008E</b>	<b>Invalid value - does not match fixed value</b>
<b>Explanation</b>	The element declaration has a fixed value. Only that value may be present in the instance document.
<b>Action</b>	Correct the instance document.
<b>ISC.0082.9009E</b>	<b>Child element {0} at position {1} is unexpected</b>
<b>Explanation</b>	The instance document contains an element at the specified location that does not match what is expected.
<b>Action</b>	Correct the instance document.
<b>ISC.0082.9010E</b>	<b>Incomplete content - one or more child elements are expected</b>
<b>Explanation</b>	The instance element does not contain the expected child elements. Content is missing.
<b>Action</b>	Correct the instance document to contain the missing content.
<b>ISC.0082.9011E</b>	<b>Unable to locate attribute declaration</b>
<b>Explanation</b>	Integration Server could not locate a corresponding schema definition for the attribute.
<b>Action</b>	Ensure that a schema for the relevant namespace has been created and that it contains a declaration for the attribute.
<b>ISC.0082.9012E</b>	<b>Unable to locate type definition</b>
<b>Explanation</b>	Integration Server could not locate a corresponding schema definition for the type.
<b>Action</b>	Ensure that a schema for the relevant namespace has been created and that it contains a definition for the type.

<b>ISC.0082.9013E</b>	<b>Unable to locate type definition {0}</b>
<b>Explanation</b>	Integration Server could not locate a corresponding schema definition for the type.
<b>Action</b>	Ensure that a schema for the relevant namespace has been created and that it contains a definition for the type.
<b>ISC.0082.9014E</b>	<b>Unable to locate element declaration</b>
<b>Explanation</b>	Integration Server could not locate a corresponding schema definition for the element.
<b>Action</b>	Ensure that a schema for the relevant namespace has been created and that it contains a declaration for the element.
<b>ISC.0082.9015E</b>	<b>Ambiguous content model in schema - not LL(1)</b>
<b>Explanation</b>	The content model is ambiguous. The given set of particle can validate the same instance with more than one unique set of occurrence counts.
<b>Action</b>	A schema must not be ambiguous. It must be possible to validate an instance without looking ahead in the content model definition. Modify the schema so that the content model is not ambiguous.
<b>ISC.0082.9016E</b>	<b>Unable to resolve QName: {0}</b>
<b>Explanation</b>	The type reference cannot be resolved to a defined type.
<b>Action</b>	Specify a defined type.
<b>ISC.0082.9017E</b>	<b>{0} is not validly derived from {1}</b>
<b>Explanation</b>	The type specified in the instance document is not a valid subtype of the type specified in the schema element declaration.
<b>Action</b>	Correct the instance document by specifying a valid subtype.
<b>ISC.0082.9018E</b>	<b>{0} is an abstract type and cannot be used directly to validate content</b>
<b>Explanation</b>	An abstract type cannot be specified in an instance document.
<b>Action</b>	Specify a concrete type that has been derived from the abstract type.
<b>ISC.0082.9019E</b>	<b>{0} is an abstract element and cannot appear in an instance</b>
<b>Explanation</b>	The instance document contains an element that has been declared abstract in the schema. Abstract elements may not appear in an instance document.
<b>Action</b>	Remove the abstract designation rfrom the schema element definition or use a member of the abstract element's substitution group in the instance document.

---

<b>ISC.0082.9020E</b>	<b>{0} - xsi:type is used incorrectly (declared type is anonymous)</b>
<b>Explanation</b>	The element declaration does not reference a named type. It is not possible to specify a type in the instance document.
<b>Action</b>	Do not use a type specification for an element that has an anonymous type declaration.
<b>ISC.0082.9022E</b>	<b>The nillable value of {0} is false, hence xsi:nil cannot appear in an instance</b>
<b>Explanation</b>	The element declaration does not have the nillable attribute set to true. The element in the instance document may not have a nil attribute.
<b>Action</b>	Correct the instance document or modify the element declaration to have the nillable attribute set to true.
<b>ISC.0082.9023E</b>	<b>The value of xsi:nil is invalid</b>
<b>Explanation</b>	The instance document element contains a value for the nil attribute that is not valid. The nil attribute must have a value of true or false.
<b>Action</b>	Correct the instance document to specify a valid value for the nil attribute.
<b>ISC.0082.9024E</b>	<b>{0} cannot have content or child elements since xsi:nil is true</b>
<b>Explanation</b>	An element is marked nill in the instance document. The element cannot have any content.
<b>Action</b>	Correct the element in the instance document.
<b>ISC.0082.9026E</b>	<b>Undefined Object found</b>
<b>Explanation</b>	An unexpected object was found in the document.
<b>Action</b>	Correct the instance document by removing the unexpected object.
<b>ISC.0082.9027E</b>	<b>Dimension mismatch, List expected</b>
<b>Explanation</b>	The instance document contains a scalar value where an array is expected.
<b>Action</b>	Correct the input data.
<b>ISC.0082.9028E</b>	<b>Dimension mismatch, Single item expected</b>
<b>Explanation</b>	An array was encountered where a scalar item was expected.
<b>Action</b>	Correct the instance document to specify a scalar item instead of an array.

<b>ISC.0082.9029E</b>	<b>Dimension mismatch, Table expected</b>
<b>Explanation</b>	The instance document contained an object type other than String array of dimension two.
<b>Action</b>	Correct the instance document
<b>ISC.0082.9030E</b>	<b>Type mismatch, String expected</b>
<b>Explanation</b>	The instance document contained an object type other than String.
<b>Action</b>	Correct the instance document.
<b>ISC.0082.9031E</b>	<b>Type mismatch, Document expected</b>
<b>Explanation</b>	The document field was expected to reference another document but instead referenced some other data type.
<b>Action</b>	Correct the instance document.
<b>ISC.0082.9033E</b>	<b>Java type mismatch; expected {0}, got {1}</b>
<b>Explanation</b>	The field is declared to contain one of the supported Java wrapper types but the instance document contains some other data type.
<b>Action</b>	Correct the instance document.
<b>ISC.0082.9034E</b>	<b>Field is absent, field must exist</b>
<b>Explanation</b>	The specified element or attribute is required but is not present in the instance document.
<b>Action</b>	Correct the instance document to contain the required element or attribute.
<b>ISC.0082.9035E</b>	<b>Value cannot be null, allow null value is false</b>
<b>Explanation</b>	The field is declared to not contain nulls, but the instance document contains a null.
<b>Action</b>	Correct the instance document.
<b>ISC.0082.9036E</b>	<b>Duplicate root element {0} found</b>
<b>Explanation</b>	An instance document may contain only one root element.
<b>Action</b>	Correct the instance document so that it has only one root element.

---

<b>ISC.0082.9037E</b>	<b>Element [{0}] cannot have characters [{1}], because the type's content type is element-only</b>
<b>Explanation</b>	The element's type declaration does not permit text nodes to be present.
<b>Action</b>	Remove the embedded text from the instance document, or use an element type declaration that permits text.
<b>ISC.0082.9038E</b>	<b>Tag occurs too many times</b>
<b>Explanation</b>	The element occurs more times than permitted by the element declaration's maxOccurs attribute.
<b>Action</b>	Correct the instance document.
<b>ISC.0082.9039E</b>	<b>Tag occurs too few time</b>
<b>Explanation</b>	The element occurs fewer times than required by the element declaration's minOccurs attribute.
<b>Action</b>	Correct the instance document.
<b>ISC.0082.9101S</b>	<b>Document Type generation error: {0}</b>
<b>Explanation</b>	An internal failure has occurred.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0082.9102S</b>	<b>Integration Server says - {0}</b>
<b>Explanation</b>	An unexpected error has interrupted the conversion process.
<b>Action</b>	Retry the request. If the error recurs contact Software AG Global Support.
<b>ISC.0082.9104S</b>	<b>{0} - unable to locate the root element</b>
<b>Explanation</b>	An internal error has interrupted the conversion process.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0082.9105E</b>	<b>Cannot process multi-dimensional array {0}. The maximum supported dimensionality for arrays is 2.</b>
<b>Explanation</b>	Document types may not contain String arrays with dimension greater than two
<b>Action</b>	Do not use String arrays with dimension greater than two.

**ISC.0082.9106E**      **Complex type {0} is recursive. Recursive types are supported only when selecting the option "Generate complex types as document types"**

**Explanation**      It is not possible to expand a type inline if it has a recursive reference. The expansion become infinite.

**Action**             Use the Generate complex types as document types option.

**ISC.0082.9109E**      **Nested and repeating model groups are not yet supported by strict compliance for the {0} component**

**Explanation**      This version of Integration Server does not support strict conversion of schema content models that have nested or repeating model groups.

**Action**             Do not use the Strict conversion option. Use the Lax or None option instead.

**ISC.0082.9401E**      **Invalid: length**

**Explanation**      The length facet value must be a non-negative integer.

**Action**             Specify a valid value for the length facet.

**ISC.0082.9402E**      **Invalid: minLength**

**Explanation**      The minLength facet value must be a non-negative integer.

**Action**             Specify a valid facet value.

**ISC.0082.9403E**      **Invalid: maxLength**

**Explanation**      The maxLength facet value must be a non-negative integer.

**Action**             Specify a valid facet value.

**ISC.0082.9404E**      **Invalid: totalDigits**

**Explanation**      The totalDigits facet value must be a positive integer.

**Action**             Specify a valid facet value.

**ISC.0082.9405E**      **Invalid: fractionDigits**

**Explanation**      The fractionDigits facet value must be a non-negative integer.

**Action**             Specify a valid value for the fractionDigits facet.

---

<b>ISC.0082.9408E</b>	<b>maxLength is less than minLength</b>
<b>Explanation</b>	The maxLength facet value is less than the minLength facet value.
<b>Action</b>	Adjust the minLength or maxLength facet so that minLength is less than or equal to maxLength.
<b>ISC.0082.9410E</b>	<b>Invalid enumerated item: {0}. Length of value is not equal to specified length</b>
<b>Explanation</b>	The enumerated item length is not equal to the length required by its type.
<b>Action</b>	Specify a valid value for the type.
<b>ISC.0082.9411E</b>	<b>Invalid enumerated item: {0}. Value is shorter than minimum length</b>
<b>Explanation</b>	The enumerated item is shorter than the required length of its type.
<b>Action</b>	Specify a valid value for the type.
<b>ISC.0082.9412E</b>	<b>Invalid enumerated item: {0}. Value is longer than maximum length</b>
<b>Explanation</b>	The enumerated value is longer than the maximum length allowed by its type.
<b>Action</b>	Specify a valid value for the type.
<b>ISC.0082.9416E</b>	<b>Invalid: minExclusive</b>
<b>Explanation</b>	The minExclusive facet value exceeds the values permitted by the totalDigits or fractionDigits facets.
<b>Action</b>	Specify a valid facet value.
<b>ISC.0082.9417E</b>	<b>Invalid: maxInclusive</b>
<b>Explanation</b>	The maxInclusive facet value exceeds the values permitted by the totalDigits or fractionDigits facet.
<b>Action</b>	Specify a valid value for the maxInclusive facet.
<b>ISC.0082.9418E</b>	<b>Invalid: maxExclusive</b>
<b>Explanation</b>	The maxExclusive facet value exceeds the values permitted by the totalDigits or fractionDigits facets.
<b>Action</b>	Specify a valid value for the maxExclusive facet.

<b>ISC.0082.9425E</b>	<b>maxInclusive is less than minInclusive</b>
<b>Explanation</b>	The maxInclusive facet value is less than the minInclusive facet value.
<b>Action</b>	Change the value of the maxInclusive facet or the minInclusive facet.
<b>ISC.0082.9427E</b>	<b>maxExclusive is less than minExclusive</b>
<b>Explanation</b>	The maxExclusive facet value is less than the minExclusive facet value.
<b>Action</b>	Change the value of the maxExclusive facet or the minExclusive facet.
<b>ISC.0082.9428E</b>	<b>maxExclusive is less than minInclusive</b>
<b>Explanation</b>	The maxExclusive facet value is less than the minInclusive facet value.
<b>Action</b>	Change the value of the maxExclusive facet or the minInclusive facet.
<b>ISC.0082.9436E</b>	<b>maxInclusive is less than minExclusive</b>
<b>Explanation</b>	The maxInclusive facet value is less than the minExclusive facet value.
<b>Action</b>	Change the value of the maxInclusive facet or the minExclusive facet.
<b>ISC.0082.9438E</b>	<b>Invalid enumerated item: {0}</b>
<b>Explanation</b>	The enumeration is empty.
<b>Action</b>	Specify a value for the enumeration facet.
<b>ISC.0082.9440E</b>	<b>Invalid enumerated item ( Out of range ): {0}</b>
<b>Explanation</b>	The enumeration facet value is outside of the permitted value range of the type.
<b>Action</b>	Correct the enumeration facet value.
<b>ISC.0082.9441E</b>	<b>Invalid enumerated item ( Does not match pattern ): {0}</b>
<b>Explanation</b>	The enumeration value does not match the pattern facet for the type.
<b>Action</b>	Correct the enumeration value to match the pattern facet.
<b>ISC.0082.9442E</b>	<b>Invalid enumerated item. Length of value is not equal to specified length</b>
<b>Explanation</b>	The length of an enumeration value for a list must be equal to the length facet of the list.
<b>Action</b>	Specify a list enumeration facet with the correct length.

<b>ISC.0082.9443E</b>	<b>Invalid enumerated item. Value is shorter than minimum length</b>
<b>Explanation</b>	The length of an enumeration value for a list must be greater than or equal to the minLength facet of the list.
<b>Action</b>	Specify a list enumeration facet with the correct length.
<b>ISC.0082.9444E</b>	<b>Invalid enumerated item. Value is longer than maximum length</b>
<b>Explanation</b>	The length of an enumeration value for a list must be less than or equal to the maxLength facet of the list.
<b>Action</b>	Specify a list enumeration facet with the correct length.
<b>ISC.0082.9447E</b>	<b>Value does not conform to datatype</b>
<b>Explanation</b>	The value is not a valid instance of the type.
<b>Action</b>	If the error occurs during schema compilation, correct the value specification in the schema. If the error occurs during document validation, it indicates that validation successfully detected an invalid document.
<b>ISC.0082.9449E</b>	<b>"length"+STR_OUT_OF_BOUND</b>
<b>Explanation</b>	The length facet for the list is outside of the permissible range. It must not be less than the minLength facet and it must not be greater than the maxLength facet.
<b>Action</b>	Specify a valid length facet.
<b>ISC.0082.9450E</b>	<b>"minLength"+STR_OUT_OF_BOUND</b>
<b>Explanation</b>	The minLength facet value is either less than the minLength facet value or greater than the maxLength facet value of the base type
<b>Action</b>	Specify a minLength facet value that is within the range allowed by the base type.
<b>ISC.0082.9451E</b>	<b>"maxLength"+STR_OUT_OF_BOUND</b>
<b>Explanation</b>	The maxLength facet value is either greater than the maxLnegth facet value or less than the minLength facet value of the base type.
<b>Action</b>	Specify a maxLength facet value that is within the range allowed by the base type.
<b>ISC.0082.9452E</b>	<b>"minInclusive"+STR_OUT_OF_BOUND</b>
<b>Explanation</b>	The minInclusive facet value is either less than the minInclusive facet value or greater than the maxInclusive facet value of the base type.
<b>Action</b>	Specify a minInclusive facet value that is within the range allowed by the base type.

<b>ISC.0082.9453E</b>	<b>"minExclusive"+STR_OUT_OF_BOUND</b>
<b>Explanation</b>	The minExclusive facet value is either less than the minExclusive facet value or greater than the maxExclusive facet value of the base type.
<b>Action</b>	Specify a minExclusive facet value that is within the range allowed by the base type.
<b>ISC.0082.9454E</b>	<b>"maxInclusive"+STR_OUT_OF_BOUND</b>
<b>Explanation</b>	The maxInclusive facet value is less than the minInclusive facet value or greater than the maxInclusive facet value of the base type
<b>Action</b>	Specify a correct maxInclusive facet or remove it.
<b>ISC.0082.9455E</b>	<b>"maxExclusive"+STR_OUT_OF_BOUND</b>
<b>Explanation</b>	The maxExclusive facet value is less than the minInclusive facet value or greater than the maxInclusive facet value of the base type.
<b>Action</b>	Specify a correct maxExclusive facet or remove it.
<b>ISC.0082.9457E</b>	<b>"totalDigits"+STR_OUT_OF_BOUND</b>
<b>Explanation</b>	The totalDigits facet value is greater than the totalDigits facet value of the base type.
<b>Action</b>	Specify a totalDigits facet value that is within the range allowed by the base type.
<b>ISC.0082.9458E</b>	<b>"fractionDigits"+STR_OUT_OF_BOUND</b>
<b>Explanation</b>	The fractionDigits facet of a derived type may not exceed the fractionDigits facet of the base type
<b>Action</b>	Correct the fractionDigits facet value so that it does not exceed the fractionDigits facet value of the base type.
<b>ISC.0082.9459E</b>	<b>"whiteSpace"+STR_OUT_OF_BOUND</b>
<b>Explanation</b>	The whiteSpace facet value is incompatible with the whiteSpace facet value of the base type
<b>Action</b>	The whiteSpace facet value must specify white space handling that is more restrictive than the base type facet.
<b>ISC.0082.9460E</b>	<b>No matching enumeration value</b>
<b>Explanation</b>	The element value in the instance document contains a token that is not specified in the element type's enumeration facet.
<b>Action</b>	None. Validation successfully detected an invalid document.

---

<b>ISC.0082.9463E</b>	<b>Length of value is not equal to specified length</b>
<b>Explanation</b>	The length of the element value in the instance document does not match the length specified by the element type's length facet.
<b>Action</b>	None. Validation successfully detected an invalid document.
<b>ISC.0082.9464E</b>	<b>Value is shorter than minimum length</b>
<b>Explanation</b>	The instance document element value is shorter than the minLength facet for the element type, or the element contains a list with fewer items than the minLength facet of the list type.
<b>Action</b>	None. Validation successfully detected an invalid document.
<b>ISC.0082.9465E</b>	<b>Value is longer than maximum length</b>
<b>Explanation</b>	The instance document element value is longer than the maxLength facet for the element type, or the element contains a list with more items than the maxLength facet of the list type.
<b>Action</b>	None. Validation successfully detected an invalid document.
<b>ISC.0082.9466E</b>	<b>Datatype definition is missing</b>
<b>Explanation</b>	The list specification does not include a type definition for the items of the list.
<b>Action</b>	Specify an item type definition for the list.
<b>ISC.0082.9469E</b>	<b>Value does not match pattern(s)</b>
<b>Explanation</b>	The element value in the instance document does not match the element type's facet pattern.
<b>Action</b>	None. Validation successfully detected an invalid document.
<b>ISC.0082.9471E</b>	<b>The year 0000 is prohibited</b>
<b>Explanation</b>	The facet value may not contain a year value of 0000.
<b>Action</b>	Do not use 0000.
<b>ISC.0082.9472E</b>	<b>totalDigits is less than fractionDigits</b>
<b>Explanation</b>	The fractionDigits facet value must be less than or equal to the totalDigits facet value.
<b>Action</b>	Adjust the fractionDigits or the totalDigits facet value.

<b>ISC.0082.9473E</b>	<b>Invalid facet type</b>
<b>Explanation</b>	An invalid facet is specified.
<b>Action</b>	Specify a valid facet.
<b>ISC.0082.9474E</b>	<b>The input has invalid characters</b>
<b>Explanation</b>	An invalid whitespace character is present in the instance document.
<b>Action</b>	None. Validation successfully detected an invalid document.
<b>ISC.0082.9475E</b>	<b>"length"+STR_BASE_FACET_FIXED</b>
<b>Explanation</b>	The length of the list is fixed and cannot be changed.
<b>Action</b>	Remove the length facet.
<b>ISC.0082.9476E</b>	<b>"minLength"+STR_BASE_FACET_FIXED</b>
<b>Explanation</b>	The minLength facet of the base type is fixed; it cannot be customized.
<b>Action</b>	Remove the minLength facet from the type specification.
<b>ISC.0082.9477E</b>	<b>"maxLength"+STR_BASE_FACET_FIXED</b>
<b>Explanation</b>	The maxLength facet of the base type is fixed; it cannot be customized.
<b>Action</b>	Remove the maxLength facet from the type specification.
<b>ISC.0082.9478E</b>	<b>"minInclusive"+STR_BASE_FACET_FIXED</b>
<b>Explanation</b>	The minInclusive facet of the base type is fixed; it cannot be customized.
<b>Action</b>	Remove the minInclusive facet from the type specification.
<b>ISC.0082.9479E</b>	<b>"minExclusive"+STR_BASE_FACET_FIXED</b>
<b>Explanation</b>	The minExclusive facet of the base type is fixed; it cannot be customized.
<b>Action</b>	Remove the minExclusive facet from the type specification.
<b>ISC.0082.9480E</b>	<b>"maxInclusive"+STR_BASE_FACET_FIXED</b>
<b>Explanation</b>	The maxInclusive facet of the base type is fixed; it cannot be customized.
<b>Action</b>	Remove the maxInclusive facet from the type specification.

---

ISC.0082.9481E	<b>"maxExclusive"+STR_BASE_FACET_FIXED</b>
<b>Explanation</b>	The maxExclusive facet of the base type is fixed; it cannot be customized.
<b>Action</b>	Remove the maxExclusive facet from the type specification.
ISC.0082.9482E	<b>"totalDigits"+STR_BASE_FACET_FIXED</b>
<b>Explanation</b>	The totalDigits facet of the base type is fixed; it cannot be customized.
<b>Action</b>	Remove the totalDigits facet from the type specification.
ISC.0082.9484E	<b>"whiteSpace"+STR_BASE_FACET_FIXED</b>
<b>Explanation</b>	The whiteSpace facet of the base type is fixed; it cannot be customized.
<b>Action</b>	Remove the whiteSpace facet from the type specification.
ISC.0082.9485E	<b>This datatype cannot have this facet</b>
<b>Explanation</b>	The specified facet is not defined for the type on which it appears.
<b>Action</b>	Remove the facet from the type specification where it appears.
ISC.0082.9486E	<b>Cannot specify length with minLength or maxLength</b>
<b>Explanation</b>	The length facet cannot be specified along with the minLength or maxLength facets.
<b>Action</b>	Remove the length facet or the minLength and maxLength facets.
ISC.0082.9487E	<b>"Invalid enumerated item: {0}. "+STR_EXCEEDS_TOTAL_DIGIT</b>
<b>Explanation</b>	The enumerated item has more total digits than allowed by its type.
<b>Action</b>	Specify a valid value for the type.
ISC.0082.9488E	<b>"Invalid enumerated item: {0}. "+STR_EXCEEDS_FRACTION_DIGIT</b>
<b>Explanation</b>	The enumerated item has more fraction digits than allowed by its type.
<b>Action</b>	Specify a value that is valid for the type.
ISC.0082.9489E	<b>STR_EXCEEDS_TOTAL_DIGIT</b>
<b>Explanation</b>	The total digits in the instance item exceeds the total digits that is valid for the type.
<b>Action</b>	None. Validation has successfully detected an invalid document.

<b>ISC.0082.9490E</b>	<b>STR_EXCEEDS_FRACTION_DIGIT</b>
<b>Explanation</b>	The instance item exceeds the fraction digits allowed for its type
<b>Action</b>	None. Validation successfully detected an invalid document.
<b>ISC.0082.9491E</b>	<b>Value is less than minInclusive</b>
<b>Explanation</b>	The element value in the instance document is less than the minInclusive facet for the element type.
<b>Action</b>	None. Validation successfully detected an invalid document.
<b>ISC.0082.9492E</b>	<b>Value is less than or equal to minExclusive</b>
<b>Explanation</b>	The element value in the instance document is less than or equal to the minExclusive facet for the element type.
<b>Action</b>	None. Validation successfully detected an invalid document.
<b>ISC.0082.9493E</b>	<b>Value is greater than maxInclusive</b>
<b>Explanation</b>	The element value in the instance document exceeds the value of the maxExclusive facet for the element type
<b>Action</b>	None. Validation successfully detected an invalid document.
<b>ISC.0082.9494E</b>	<b>Value is greater than or equal to maxExclusive</b>
<b>Explanation</b>	The element value in the instance document exceeds or equals the value of the maxExclusive facet for the element type
<b>Action</b>	None. Validation successfully detected an invalid document.
<b>ISC.0082.9495E</b>	<b>"Length constraint cannot be customized." +STR_LENGTH_EXISTS</b>
<b>Explanation</b>	The base type already has a length facet; it is not possible to change the length facet.
<b>Action</b>	Remove the length facet from the type specification.
<b>ISC.0082.9496E</b>	<b>"Cannot specify minLength if length is specified." +STR_LENGTH_EXISTS</b>
<b>Explanation</b>	The length and minLength facets are mutually exclusive.
<b>Action</b>	Remove one of the facets from the type specification.

---

<b>ISC.0082.9497E</b>	<b>"Cannot specify maxLength if length is specified. "+STR_LENGTH_EXISTS</b>
<b>Explanation</b>	The maxLength and length facets are mutually exclusive.
<b>Action</b>	Remove one of the facets from the type specification.
<b>ISC.0082.9712E</b>	<b>Cannot specify both {0} and {1}</b>
<b>Explanation</b>	The schema properties are mutually exclusive. Only one can be specified.
<b>Action</b>	Decide which property is relevant and remove the other.
<b>ISC.0082.9723E</b>	<b>Xerces Java parser determined that the XML schema definition is invalid</b>
<b>Explanation</b>	<p>The Xerces Java parser determined that an XML schema definition is invalid. This can occur in the following situations:</p> <ul style="list-style-type: none"><li>- When creating an asset (IS schema, document type, or flow service) from an XML Schema definition.</li><li>- When creating a Web service descriptor from a WSDL document that contains a schema element or references an XML schema definition.</li><li>- When refreshing Web service connectors</li><li>- When executing a Web service connector</li><li>- When changing the IS schemas, document types, or service signatures associated with a Web service descriptor</li></ul>
<b>Action</b>	<p>Use the information returned by the Xerces Java parser to make the schema valid.</p> <p>Alternatively, if you do not want the Xerces Java parser to perform schema validation, do one of the following:</p> <ul style="list-style-type: none"><li>- When creating the asset, clear the Validate schema using Xerces check box</li><li>- For an existing Web service descriptor, set the Validate schema using Xerces property to False.</li></ul>
<b>ISC.0083.9001E</b>	<b>Requested type not available</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the Integration Server XQL query engine encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.

<b>ISC.0083.9002E</b>	<b>Tree type not supported</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the supplied query object supplied was not a valid XML Node object.
<b>Action</b>	Examine the service input and ensure it is a valid XML node object. You can invoke the pub.xml:xmlStringToXMLNode or pub.xml:loadXMLNode service to obtain the document and transform it to an XML node object before performing the query.
<b>ISC.0083.9003E</b>	<b>Expression is empty</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because no query expression was specified.
<b>Action</b>	Examine the logic and make sure that the query expression is not empty.
<b>ISC.0083.9004E</b>	<b>Node parameter is null</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the XML Node to be queried was empty or missing.
<b>Action</b>	Examine the XML node object submitted for query and make sure it is not null.
<b>ISC.0083.9005E</b>	<b>"{0}" object type not currently supported.</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the document submitted was not an instance of an XML Node object. This service can obtain information from XML nodes only. Note: An XML node is a special representation of an XML document that can be consumed by the Integration Server. Most webMethods services that operate on XML documents require an XML node as input.
<b>Action</b>	Examine the document submitted and make sure that you have used pub.xml:xmlStringToXMLNode or pub.xml:loadXMLNode service to convert the document to an XML Node object before performing the query.
<b>ISC.0083.9006E</b>	<b>Regions are not supported on IData objects</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because it tried to perform a region query on an IData object; the Integration Server does not support this type of query. Currently only XML node objects are supported for region queries. Note: An XML node is a special representation of an XML document that can be consumed by the Integration Server. Most webMethods services that operate on XML documents require an XML node as input.
<b>Action</b>	Do not attempt to query regions on IData objects.

<b>ISC.0083.9007E</b>	<b>Source not available for IData objects</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because it tried to obtain information from a Document (an IData object) instead of an XML Node. This service can obtain information from XML Nodes only. Note: An XML node is a special representation of an XML document that can be consumed by the Integration Server. Most webMethods services that operate on XML documents require an XML node as input.
<b>Action</b>	Do not attempt to query the source from Documents (IData objects).
<b>ISC.0083.9008E</b>	<b>Recursion detected in IData at {0}; can't have recursion when query contains   or //</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because it tried to perform a query on a recursive IData object, but the query contained " " (a union operator) or "/" (a path operator). These operators are not allowed when querying a recursive IData object.
<b>Action</b>	Do not attempt to query a recursive IData object when the query contains " " or "/".
<b>ISC.0083.9009</b>	<b>Illegal typecast in query expression</b>
<b>ISC.0083.9011</b>	<b>'true()' or 'false()' expected</b>
<b>ISC.0083.9012E</b>	<b>(' expected</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because it specified an incorrect syntax. Specifically, the left-hand parenthesis "(" was missing after the "true" or "false" Boolean function.
<b>Action</b>	Examine the query expression and make sure it uses the correct syntax. There must be matching parentheses after any "true" or "false" functions, e.g., true(), false().
<b>ISC.0083.9013E</b>	<b>)' expected</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the right-hand parenthesis ")" was missing after the "true" or "false" Boolean function.
<b>Action</b>	Examine the query expression and make sure it uses the correct syntax. There must be matching parentheses after any "true" or "false" functions, e.g., true(), false().
<b>ISC.0083.9014E</b>	<b>Invalid boolean method: {0}</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the Integration Server XQL query engine encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.

<b>ISC.0083.9015E</b>	<b>Comparison requires an rvalue</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the right-hand operand was not present in the query. Left- and right-hand operands are required for a comparison query.
<b>Action</b>	Examine the query expression and make sure that both the left- and right-hand operands are supplied.
<b>ISC.0083.9016E</b>	<b>Comparison righthand operand evaluates to more than one value</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute a comparison query because the value of the right-hand operand was not a scalar.
<b>Action</b>	Examine the query expression and make sure the value of the right-hand operand is a scalar or a value that can be cast at runtime to a scalar.
<b>ISC.0083.9017E</b>	<b>Comparison operator is missing.</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute a comparison query because the expression contained \$any\$ or \$all\$, but no comparison operator. A comparison operator must be specified in an expression that contains \$any\$ or \$all\$.
<b>Action</b>	Examine the query expression and make sure it contains a comparison operator.
<b>ISC.0083.9018E</b>	<b>Only relative queries allowed inside filters.</b>
<b>Explanation</b>	The XQL query expression contains an absolute path inside the filter. For example, "book[/author]".
<b>Action</b>	Make sure that the XQL query expression contains a relative path inside the filter. For example, "book[author]".
<b>ISC.0083.9019U</b>	<b>'[' is not matched by ']'</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the left-hand square bracket "[" was specified but the right-hand square "]" bracket was missing. An expression that uses a filter operator or a subscript operator must contain matching parentheses.
<b>Action</b>	Examine the query expression and make sure it contains matching brackets "[ ]" .
<b>ISC.0083.9020E</b>	<b>Filter brackets may only select nodes or attributes</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because a subquery within the "[ ]" was not a node or attribute. A subquery must be a node or an attribute when a filter operation is used.
<b>Action</b>	Examine the query expression and make sure that the subquery contained within the "[ ]" is a node or attribute.

<b>ISC.0083.9021E</b>	<b>Invalid or missing term</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because a query expression using a filter operator specified an invalid term or no terms at all.
<b>Action</b>	Examine the query expression and make sure it specifies a valid term. Valid terms are: dot('.'), left parenthesis('('), at('@'), and wildcard('*').
<b>ISC.0083.9022E</b>	<b>'(' is not matched by ')'. Token "{0}" found.</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the query expression contained a left parenthesis "(" that was not matched by a right parenthesis ")", but rather by another character. The query expression must specify matching parentheses when a filter operator is used.
<b>Action</b>	Examine the query expression and make sure it contains matching parentheses "()".
<b>ISC.0083.9023E</b>	<b>'(' is not matched by ')'. End of query found.</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the query expression contained a left parenthesis "(" but no right parenthesis ")". A query expression must specify matching parentheses when a filter operator is used.
<b>Action</b>	Examine the query expression and make sure it contains matching parentheses "()".
<b>ISC.0083.9024E</b>	<b>Invalid or misplaced term "{0}"</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because an invalid character was specified in a query expression that contains a filter operator. Valid characters are dot ".", left and right parentheses "(" and ")", at "@", and wildcard "*".
<b>Action</b>	Examine the query expression and ensure that only valid characters are specified.
<b>ISC.0083.9025E</b>	<b>Invalid attribute name "{0}:"</b>
<b>Explanation</b>	The XQL query expression contains an invalid attribute name. This attribute belongs to a namespace. For example, "//@prefix:123".
<b>Action</b>	Make sure that the XQL query expression contains a valid attribute name. For example, "//@prefix:a123".
<b>ISC.0083.9026E</b>	<b>Invalid or missing attribute name</b>
<b>Explanation</b>	The XQL query expression contains an invalid or undefined attribute name. For example, "//@123" or "//@".
<b>Action</b>	Make sure that the XQL query expression contains a valid attribute name. For example, "//@a123".

<b>ISC.0083.9027E</b>	<b>attribute() takes a quoted string</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the optional parameter passed to attribute() function was not a quoted string.
<b>Action</b>	Examine the query expression and make sure that it uses the correct syntax and passes a quoted string to the attribute() function.
<b>ISC.0083.9028E</b>	<b>attribute() incorrect attribute name "{0}"</b>
<b>Explanation</b>	The XQL query expression contains an invalid attribute name inside the attribute(). For example, "//book/attribute('123')".
<b>Action</b>	Make sure that the XQL query expression contains a valid attribute name inside the attribute(). For example, "//book/attribute('a')".
<b>ISC.0083.9029</b>	<b>Only nodes have attributes</b>
<b>ISC.0083.9030E</b>	<b>count() takes a query parameter</b>
<b>Explanation</b>	The XQL query expression contains a parameter in the count(), which is not allowed. For example, "//book/count(1)".
<b>Action</b>	Make sure that the XQL query expression does not contain a parameter in the count(). For example, "//book/count()".
<b>ISC.0083.9031E</b>	<b>Type {0} can't be cast to Date</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the query engine returned a value that could not be cast as a date.
<b>Action</b>	Examine the query expression and make sure it uses the correct syntax and specifies the correct query.
<b>ISC.0083.9032E</b>	<b>date({0}){1}</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the parameter passed to the XQL date() function was not in a format that could be converted to a date.
<b>Action</b>	Examine the detailed error message and make sure that the string parameter passed to the XQL date() function can be converted to a date.
<b>ISC.0083.9033E</b>	<b>date(){0} Error offset:{1}</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the parameter passed to the XQL date() function could not be parsed.
<b>Action</b>	Examine the detailed error message and the position provided in it and make sure that the string parameter passed to the date() function in the query expression can be parsed to a date.

---

<b>ISC.0083.9034E</b>	<b>Invalid element name "{0}:"</b>
<b>Explanation</b>	The XQL query expression contains an invalid element name. This element belongs to a namespace. For example, "//a:1".
<b>Action</b>	Make sure that the XQL query expression contains a valid element name. For example, "//a:b".
<b>ISC.0083.9035</b>	<b>Invalid or missing element name</b>
<b>ISC.0083.9036E</b>	<b>element() takes a quoted string</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the optional parameter passed to XQL element() function was not a quoted string.
<b>Action</b>	Examine the query expression and make sure it uses the correct syntax and passes a quoted string to the element() function.
<b>ISC.0083.9037E</b>	<b>element() incorrect attribute name "{0}"</b>
<b>Explanation</b>	The XQL query expression contains an invalid parameter in element(). For example, "/book/element("1")".
<b>Action</b>	Make sure that the XQL query expression contains a valid parameter name in element(). For example, "/book/element("a")".
<b>ISC.0083.9038</b>	<b>Only nodes have child elements</b>
<b>ISC.0083.9039E</b>	<b>Type {0} can't be cast to Float</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because it expected a float, but the value it received was not a float.
<b>Action</b>	Examine the query expression. Make sure it uses the correct syntax and specifies the query you intended.
<b>ISC.0083.9040E</b>	<b>id() takes a quoted string</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the optional parameter passed to XQL id() function was not a quoted string.
<b>Action</b>	Examine the query expression and make sure it uses the correct syntax and passes a quoted string to the XQL id() function.

- ISC.0083.9041E**      **Type {0} can't be cast to Integer**  
**Explanation**      The pub.xml:queryXMLNode service failed to execute because it expected an integer, but the value it received could not be cast as an integer.  
**Action**              Examine the query expression. Make sure it uses the correct syntax and specifies the query you intended.
- ISC.0083.9042E**      **name() takes a quoted string**  
**Explanation**      The pub.xml:queryXMLNode service failed to execute because the optional parameter passed to XQL name() function was not a quoted string.  
**Action**              Examine the query expression and make sure it uses the correct syntax and passes a quoted string to the XQL name() function.
- ISC.0083.9043E**      **name() requires a non-empty string**  
**Explanation**      The pub.xml:queryXMLNode service failed to execute because the parameter passed to the XQL name() function was empty.  
**Action**              Examine the query expression and make sure it uses the correct syntax and passes a non-empty quoted string to the name() function.
- ISC.0083.9044E**      **node() must be used relative to a node**  
**Explanation**      The pub.xml:queryXMLNode service failed to execute because it specified an incorrect syntax for the XQL node() function or tried to execute the function against a non-node object.  
**Action**              Examine the query expression and make sure it uses the correct syntax for the node() function and executes the function against a node.
- ISC.0083.9045E**      **region() must be used relative to a node**  
**Explanation**      The pub.xml:queryXMLNode service failed to execute because it specified an incorrect syntax for the XQL region() function or tried to execute the function against a non-node object.  
**Action**              Examine the query expression and make sure it uses the correct syntax for the region() function and executes the function against a node.
- ISC.0083.9046**      **Query parameters of region() must return nodes**

---

ISC.0083.9047	<b>region() can't have more than one region start node</b>
ISC.0083.9048	<b>region() can't have more than one region end node</b>
ISC.0083.9049E	<b>textnode() must be used relative to a node</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because it specified an incorrect syntax for the XQL textnode() function or tried to execute the function against a non-node object.
<b>Action</b>	Examine the query expression and make sure it uses the correct syntax for the textnode() function and executes the function against a node.
ISC.0083.9050	<b>Function or method name expected</b>
ISC.0083.9051E	<b>'(' missing after function or method name</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because a left-hand parenthesis "(" was missing after the function or method name. The correct syntax is functionname() or methodname() .
<b>Action</b>	Examine the query expression and make sure that it uses the correct syntax for the function or method.
ISC.0083.9052E	<b>Query contains truncated invocation</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because an incomplete expression was provided for a function call. Specifically, the expression contained a left parenthesis "(" but the invocation parameter or right parenthesis ")" was missing. Examples: function() function(parameter
<b>Action</b>	Examine the query expression and make sure it uses the correct syntax.
ISC.0083.9053E	<b>')' must terminate parameter list</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the right parenthesis ")" was missing from the parameter list that was passed to the XQL function.
<b>Action</b>	Examine the query expression and make sure it uses the correct syntax and includes the right parenthesis to terminate the parameter/parameter list.

<b>ISC.0083.9054E</b>	<b>missing function parameter</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the parameter required by the XQL function was not provided.
<b>Action</b>	Examine the query expression and make sure it uses the correct syntax and includes the required parameter.
<b>ISC.0083.9055E</b>	<b>Invalid number of parameters in function or method "{0}"</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because an invalid number of parameters were passed to the XQL function or method.
<b>Action</b>	Examine the query expression and make sure it uses the correct syntax and passes the correct number of parameters to the XQL function. See XQL Query Language at <a href="http://www.w3.org/TandS/QL/QL98/pp/xql.html">http://www.w3.org/TandS/QL/QL98/pp/xql.html</a> for method or function reference.
<b>ISC.0083.9056E</b>	<b>"{0}" is not a recognized function name</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because an invalid XQL function name was provided.
<b>Action</b>	Examine the query expression and make sure that it only uses the valid XQL functions. Integration Server currently supports the following pre-defined functions: attribute(), Boolean(), comment(), count(), date(), element(), float(), id(), integer(), name(), node(), not(), pi(), region(), textnode(), true(), false().
<b>ISC.0083.9057E</b>	<b>"{0}" is not a recognized method name</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because an invalid XQL method name was provided.
<b>Action</b>	Examine the query expression and make sure that it only uses the valid XQL methods. Integration Server currently supports the following pre-defined methods: basename(), count(), end(), index(), namespace(), nodename(), nodetype(), nodetypestring(), prefix(), regex(), regexinsensitive(), regexinsensitivematch(), regexmatch(), rawtext(), stringmatch(), source(), text(), value().
<b>ISC.0083.9058E</b>	<b>Methods may only be applied to nodes and attributes</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the Integration Server XQL query engine encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.

---

ISC.0083.9059	<b>regex() takes a quoted string</b>
ISC.0083.9060	<b>regexinsensitive() takes a quoted string</b>
ISC.0083.9061	<b>regexinsensitivematch() takes a quoted string</b>
ISC.0083.9062	<b>regexmatch() takes a quoted string</b>
ISC.0083.9063	<b>stringmatch() takes a quoted string</b>
ISC.0083.9064E	<b>Query contains extraneous terms</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because there was a syntax error in the expression. Specifically, there were extraneous terms in the expression.
<b>Action</b>	Examine the query expression and make sure it uses the correct syntax.
ISC.0083.9065E	<b>Cannot parse queries of type {0}</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
ISC.0083.9066E	<b>Left operand of / must be either a node or an attribute</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the query expression specified the unary child operator "/" but the value specified by the left-hand operand was not a node type or an attribute type.
<b>Action</b>	Examine the query expression and make sure the left-hand operand is a node or attribute.
ISC.0083.9067E	<b>Only relative queries allowed in relative paths.</b>
<b>Explanation</b>	The XQL query expression contains an absolute path inside another absolute path. For example, "/x/(/y)".
<b>Action</b>	Make sure that the XQL query expression does not contain an absolute path embedded inside another absolute path.

<b>ISC.0083.9068E</b>	<b>Left operand of // must be a node</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the query expression specified the unary child descendant operator "/" but the value specified by the left-hand operand was not a node.
<b>Action</b>	Examine the query expression and make sure the left-hand operand is a node.
<b>ISC.0083.9069E</b>	<b>Invalid subscript argument</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because no argument was supplied for the subscript operator or the argument supplied was not an integer.
<b>Action</b>	Examine the query expression and make sure that a valid integer is provided for the subscript operator.
<b>ISC.0083.9070E</b>	<b>Only values of the same type may be unioned</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute a union operation because the left-hand operand is not the same type as the right-hand operand.
<b>Action</b>	Examine the query expression and make sure that both operands are of the same type. Valid types are node, attribute, string, integer, float, and Boolean.
<b>ISC.0083.9071E</b>	<b>{0} and {1} types are not comparable</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute a comparison operation because the left-hand operand is not the same type as the right-hand operand.
<b>Action</b>	Examine the query expression and make sure that the left-hand operand and right-hand operand are of the same type. Valid types are node, attribute, string, integer, float, and Boolean.
<b>ISC.0083.9072E</b>	<b>The {0} relation is not defined on {1} types</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0083.9073E</b>	<b>Unrecognized expression type "{0}"</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.

ISC.0083.9074	<b>generateQueryString Node doc is a required parameter. Must not be null.</b>
ISC.0083.9075	<b>generateQueryString String queryType is a required parameter. Must not be null.</b>
ISC.0083.9076E	<b>generateQueryString only supports WQL, XQLVALUES and XQL types. Unsupported type "{0}"</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because an expression attempted to evaluate an unsupported type. Integration Server currently only supports WQL,XQLVALUES and XQL.
<b>Action</b>	Contact Software AG Global Support.
ISC.0083.9077E	<b>Unknown TreeExpression type</b>
<b>Explanation</b>	Integration Server tried to process an unsupported type. This is an internal error. Currently only the WQL, XQLVALUES and XQL types are supported.
<b>Action</b>	Contact Software AG Global Support.
ISC.0083.9078E	<b>Cannot cast "{0}" to boolean</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because it attempted to cast a string value to a Boolean type. The possible causes are: (1) the left-hand and right-hand operands specified with a comparison operator were not of the same type (2) the value returned by the query was of an unexpected type.
<b>Action</b>	Examine the query expression and make sure it specifies the correct syntax and performs the query you expected.
ISC.0083.9079E	<b>Cannot cast "{0}" to a float</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because it attempted to cast a string value to a float. The possible causes are: (1) the left-hand and right-hand operands specified with a comparison operator were not of the same type (2) the value returned by the query was of an unexpected type.
<b>Action</b>	Examine the query expression and make sure it specifies the correct syntax and performs the query you expected.
ISC.0083.9080E	<b>Cannot cast "{0}" to an integer</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because it attempted to cast a string value to an integer. The possible causes are: (1) The left-hand and right-hand operands specified with a comparison operator were not of the same type. (2) The value returned by the query was of an unexpected type.
<b>Action</b>	Examine the query expression and make sure it specifies the correct syntax and performs the query you expected.

<b>ISC.0083.9081E</b>	<b>Cannot cast "{0}" to a long</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because it attempted to cast a string value to a long type. The possible causes are: (1) the left-hand and right-hand operands specified with a comparison operator were not of the same type (2) the value returned by the query was of an unexpected type.
<b>Action</b>	Examine the query expression and make sure it specifies the correct syntax and performs the query you expected.
<b>ISC.0083.9082</b>	<b>IO error occurred while parsing a grove in a VARNAME expression: {0}</b>
<b>ISC.0083.9083E</b>	<b>XqlQuery.getStringWithIdentities: Query "{0}" does not yield strings:{1}</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0083.9084E</b>	<b>XqlQuery.getString: Query "{0}" does not yield strings:{1}</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0083.9085E</b>	<b>XqlQuery: Query yields unknown type</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0083.9086E</b>	<b>XqlQuery.getNodeWithIdentities: Query "{0}" does not yield nodes</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0083.9087E</b>	<b>XqlQuery.getNode: Query "{0}" does not yield nodes</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.

---

<b>ISC.0083.9088E</b>	<b>XqlQuery.getNodeArrayWithIdentities: Query "{0}" does not yield nodes</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0083.9089E</b>	<b>XqlQuery.getNodeArray: Query "{0}" does not yield nodes</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0083.9090E</b>	<b>XqlQuery.getIData: Query "{0}" does not yield nodes</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0083.9091E</b>	<b>Query does not yield an IData instance as expected</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0083.9092E</b>	<b>XqlQuery.getIDataArray: Query "{0}" does not yield nodes</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0083.9093E</b>	<b>Query "{0}" does not yield only IData instances as expected</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISC.0083.9094E</b>	<b>Floating point numbers must begin with a digit</b>
<b>Explanation</b>	The pub.xml:queryXMLNode service failed to execute because an invalid query expression was provided. Specifically, a floating point number was provided in an incorrect format. A digit must immediately precede and follow the dot "." term. Examples of the correct format are "1.23" and "-0.99.". Examples of incorrect formats are ".99" and "1.".
<b>Action</b>	Examine the query expression and make sure that it uses the correct format for floating point numbers.

- ISC.0083.9095E      Unrecognized operator '{0}'**  
**Explanation**      The pub.xml:queryXMLNode service failed to execute because an expression contained an unrecognized operator.  
**Action**              Examine the query expression and make sure it only uses the valid operators specified in the XQL specification. For more information, see XQL Query Language at <http://www.w3.org/TandS/QL/QL98/pp/xql.html>.
- ISC.0083.9096E      Invalid number: "{0}"**  
**Explanation**      The pub.xml:queryXMLNode service failed to execute because the XQL query engine could not parse a numberString to an integer or a float because the string does not represent an integer or float number.  
**Action**              Examine the query expression and make sure that it uses the correct syntax. See XQL Query Language at <http://www.w3.org/TandS/QL/QL98/pp/xql.html> for more information.
- ISC.0083.9097        Missing terminal quote: {0}{1}**
- ISC.0083.9098E      "{0}" is not a recognized function or method name**  
**Explanation**      The pub.xml:queryXMLNode service failed to execute because an invalid XQL function or method was specified in the query expression.  
**Action**              Examine the query expression and make sure that you only use a set of pre-defined XQL function names or method names in the query. For a list of pre-defined functions and methods in XQL, see The XML Query Language (XQL) at <http://www.w3.org/TandS/QL/QL98/pp/xql.html>.
- ISC.0083.9099E      Method requires Node tree for query "{0}".**  
**Explanation**      The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.  
**Action**              Contact Software AG Global Support.
- ISC.0083.9100        Queries on attributes are not supported by IData trees.**
- ISC.0083.9101        nsDecls and namespaces are not supported by IData trees.**

---

<b>ISC.0084.9004E</b>	<b>Access Denied</b>
<b>Explanation</b>	The user does not have permission to access an Integration Server resource. Review the server log to find the resource and the user who was denied access.
<b>Action</b>	If the user should have access to this resource, either add the user to the group that is in the Allowed list of the execute ACL of the resource, or add one of this user's groups to the Allowed list of the execute ACL of the resource.
<b>ISC.0084.9005E</b>	<b>Invalid Session ID or Session Expired</b>
<b>Explanation</b>	Whenever a client presents a Session ID that is no longer valid, Integration Server throws this exception and sets the 401 HTTP response code to force the client to re-authenticate.
<b>Action</b>	No action is necessary.
<b>ISC.0084.9006E</b>	<b>Server is not accepting new requests at this time</b>
<b>Explanation</b>	A client request was submitted during Integration Server shutdown. Integration Server does not accept requests during shutdown.
<b>Action</b>	Resubmit the request after Integration Server becomes available again.
<b>ISC.0084.9007E</b>	<b>Server has reached client limit</b>
<b>Explanation</b>	Integration Server was not able to create a session to service a client request. Integration Server sends this error with HTTP response code 503 to the client.
<b>Action</b>	Review the server log and error log to find possible causes of this error.
<b>ISC.0084.9102E</b>	<b>Resubmit data array cannot be null.</b>
<b>Explanation</b>	webMethods Monitor failed to resubmit the rejected document because the data array for resubmission was not supplied.
<b>Action</b>	Examine the document to be resubmitted and make sure that it is valid and not empty.
<b>ISC.0084.9103E</b>	<b>Resubmit data cannot be null.</b>
<b>Explanation</b>	webMethods Monitor failed to resubmit the rejected document because the data for resubmission was not supplied.
<b>Action</b>	Examine the document to be resubmitted and make sure that it is valid and not empty.

- ISC.0084.9104E      Auditcontexts cannot be null or empty.**  
**Explanation**      webMethods Monitor failed to resubmit the rejected document because the "auditContexts" field in the data was either null or empty.  
**Action**              Examine the document to be resubmitted and make sure that it is valid and that the "auditContexts " field is not missing.
- ISC.0084.9105E      Service name cannot be null or empty.**  
**Explanation**      webMethods Monitor failed to resubmit the rejected document because the "serviceName" field in the data was either null or empty.  
**Action**              Examine the document to be resubmitted and make sure that it is valid and that the "serviceName" field is not missing.
- ISC.0084.9106U      Service for resubmission does not exist on the server.**  
**Explanation**      webMethods Monitor failed to resubmit the rejected document because the service for resubmission does not exist on Integration Server.  
**Action**              Examine the document to be resubmitted and make sure that the name specified in the "serviceName" field is a valid service and exists on Integration Server.
- ISC.0084.9107E      Input pipeline cannot be null.**  
**Explanation**      webMethods Monitor failed to resubmit the rejected document because the "pipeline" field in the data was either null or empty.  
**Action**              Examine the document to be resubmitted and make sure that it is valid and that the "pipeline" field is not missing.
- ISC.0084.9108E      User name cannot be empty or null.**  
**Explanation**      webMethods Monitor failed to resubmit the rejected document because the "userName" field in the data was either null or empty.  
**Action**              Examine the document to be resubmitted and make sure that it is valid and that the "userName" field is not missing.
- ISC.0084.9109E      Access is denied to the user.**  
**Explanation**      The current user does not have permission to invoke the service that is being resubmitted.  
**Action**              To grant permission to the user, add the user to a group that is listed in the Execute ACL assigned to the service.

---

ISC.0084.9301E	Not Authorized to use Server
ISC.0086.9000	Recipient certificate at index {0} not in recognizable format
ISC.0086.9001	bytes must be byte[]
ISC.0086.9005	URL must begin with "http:" or "https:"
ISC.0086.9006	HTTP method is null
ISC.0086.9007	only use one of: data.stream, data.bytes or data.mimeStream on a POST
ISC.0086.9008	do not use: data.bytes, data.stream or data.mimeStream on a GET
ISC.0086.9009	{0}: input parameter required
ISC.0086.9010	invalid HTTP method: {0}
ISC.0086.9012	Invalid TO field: {0}
ISC.0086.9013	Invalid CC field: {0}
ISC.0086.9014	Invalid BCC field: {0}
ISC.0086.9015	files must be of type Values[]
ISC.0086.9016	No filename nor content included in the attachment!

- ISC.0086.9017 mimeStream must be an InputStream
- ISC.0086.9018 'pattern' is a required input
- ISC.0086.9020 {0} does not exist
- ISC.0086.9021 {0} cannot be read
- ISC.0086.9022 {0} is a directory
- ISC.0086.9023 Missing required parameter: '\$name'
- ISC.0086.9024 Missing required parameter: 'fileName'
- ISC.0086.9025 Saved pipeline {0} does not exist
- ISC.0086.9026 Missing required parameter: 'response'
- ISC.0086.9028 getLastError invoked outside of a Flow
- ISC.0086.9029 parameter 'key' is required when fromList is not null
- ISC.0086.9030 input must be an InputStream
- ISC.0086.9031 index must be a non-negative integer
- ISC.0086.9032 {0} input parameter required

---

ISC.0086.9033	<b>content input parameter required</b>
ISC.0086.9034	<b>Message content is not empty</b>
ISC.0086.9035	<b>Missing required value: {xmlvalues}</b>
ISC.0086.9036	<b>Missing required value: {record}</b>
ISC.0086.9037	<b>Missing one or more required values: {recordList,name}</b>
ISC.0086.9039	<b>Certificate not in recognizable format</b>
ISC.0086.9040	<b>Certificate at index {0} not in recognizable format</b>
ISC.0086.9041	<b>Invalid certificate input at index {0}</b>
ISC.0086.9042	<b>Could not create certs only SMIME object {0}</b>
ISC.0086.9043	<b>Not a valid InputStream</b>
ISC.0086.9044	<b>InputData not in recognizable format</b>
ISC.0086.9045	<b>Invalid recipient certificates information</b>
ISC.0086.9046	<b>Invalid recipient certificate input at index {0}</b>
ISC.0086.9047	<b>Incorrect keylength specified: {0}</b>

ISC.0086.9048	Unsupported encryption algorithm specified: {0}
ISC.0086.9049	Could not create SMIME Enveloped object {0}
ISC.0086.9050	Invalid private key information
ISC.0086.9052	Invalid signer certificate file information
ISC.0086.9053	Certificate file not in any recognizable format
ISC.0086.9054	Could not create signed SMIME object {0}
ISC.0086.9055	Could not retrieve content from input
ISC.0086.9056	Encrypted Content not in recognizable format
ISC.0086.9057	Recipient certificate not in any recognizable format
ISC.0086.9058	Supplied certificate cannot decrypt content
ISC.0086.9059	Not a valid privateKey
ISC.0086.9060	Unable to decrypt symmetric key
ISC.0086.9061	Certs-Only data not in recognizable format
ISC.0086.9062	Signed Content not in recognizable format

ISC.0086.9064	bytes must be type byte[]
ISC.0086.9065	already in exclusive wait
ISC.0086.9066	cannot obtain exclusive wait
ISC.0086.9068	No string table data supplied
ISC.0086.9069	No column names supplied
ISC.0086.9070	{0} Maybe the wrong number of column names
ISC.0086.9071	No row data supplied
ISC.0086.9072	Deprecated Service: table to documentList conversion is now automatic.
ISC.0086.9074	Cannot process null input
ISC.0086.9075	Input not a byte array
ISC.0086.9076	Input in incorrect format, certificate cannot be loaded
ISC.0086.9077	No algorithm has been specified
ISC.0086.9079	No keys provided to sign the provided data
ISC.0086.9080	Data to sign not in the expected format (byte[])

- ISC.0086.9081      An error occurred processing the signer information for {0}, {1}
  
- ISC.0086.9082      An error occurred creating the signature for the data: {0}
  
- ISC.0086.9083      No signature provided to verify
  
- ISC.0086.9084      No data provided to verify detached signature
  
- ISC.0086.9085      An error occurred attempting to reconstruct the signature: {0}
  
- ISC.0086.9086      Signature provided is not PKCS#7 SignedData
  
- ISC.0086.9087      Invalid data encountered when building the certificate chain, either an instance of a certificate or a byte[] expected
  
- ISC.0086.9088      Invalid data provided for certificate entry {0}, expecting a byte[]
  
- ISC.0086.9089      Parameter {0} is missing
  
- ISC.0086.9090      Parameter {0} is of incorrect type
  
- ISC.0086.9091      Parameters {0}, '\$filestream' and '\$filedata' are all missing. One of these must not be null.
  
- ISC.0086.9093      Http Error: {0} - {1}
  
- ISC.0086.9094      No LDAP URL specified
  
- ISC.0086.9095      No connection key provided

---

ISC.0086.9096	Bad connection key: {0}
ISC.0086.9097	No lookup name provided
ISC.0086.9098	No search filter provided
ISC.0086.9099	No target name provided
ISC.0086.9102	No schema information available
ISC.0086.9103	Required parameter 'packageName' is missing
ISC.0086.9104	Required parameter 'publisher' is missing
ISC.0086.9105	The 'fileList' or 'fileNamePattern' parameter is required
ISC.0086.9106	Required parameter 'package' is missing
ISC.0086.9107	Package "{0}" has already been released, select a different name instead
ISC.0086.9108	Required parameter 'package' is missing
ISC.0086.9109	Required parameter 'packageFile' is missing
ISC.0086.9113	No such user present : {0}
ISC.0086.9117	Task being updated is not a one-time task

- ISC.0086.9118      **Task being updated is not a repeating task**
  
- ISC.0086.9119      **Task being updated is not a complex task**
  
- ISC.0086.9120      **Inputs cannot be null**
  
- ISC.0086.9121      **Certificate file not found: {0}**
  
- ISC.0086.9122      **Certificate file {0} not in any recognizable format**
  
- ISC.0086.9123      **IO Exception encountered while reading file: {0}**
  
- ISC.0086.9125      **lockMode must be "{0}" or "{1}". Supplied value was {2}.**
  
- ISC.0086.9126      **key of entry to unlock can not be null**
  
- ISC.0086.9127      **key of value to add can not be null**
  
- ISC.0086.9128      **key of entry to insert or update can not be null**
  
- ISC.0086.9129      **key of entry to get can not be null**
  
- ISC.0086.9131      **key of entry to remove can not be null**
  
- ISC.0086.9132      **value to insert or update can not be null**
  
- ISC.0086.9133      **Cannot obtain entry lock for key**

---

ISC.0086.9134	Missing required parameter: tid
ISC.0086.9135	Missing required parameter: alias
ISC.0086.9136	Missing required parameter: service
ISC.0086.9138	Not allowed to activate package "{0}"
ISC.0086.9139	The target name specified by {0} is {1}, not allowed to install package or patch to {1}
ISC.0086.9140	Not allowed to enable package "{0}"
ISC.0086.9141	Not allowed to disable package "{0}"
ISC.0086.9142	Not allowed to recover package "{0}"
ISC.0086.9143	Package file "{0}" does not exist in Inbound directory
ISC.0086.9144	Exception occurred while checking target package name
ISC.0086.9145	Invalid or non-existing package name "{0}" provided
ISC.0086.9146	A required parameter {0} was not supplied
ISC.0086.9147	The Universal Name {0} is unknown
ISC.0086.9148	The Universal Name {0} is already defined for {1} in the registry

- ISC.0086.9149      **The Universal Name {0} is already defined as a Service**
  
- ISC.0086.9150      **The Universal Name {0} is not a valid QName**
  
- ISC.0086.9151      **Parameter {0} is the wrong data type**
  
- ISC.0086.9152      **Not allowed to reload package "{0}"**
  
- ISC.0086.9153      **Unknown package name "{0}" provided**
  
- ISC.0086.9154      **Package "{0}" is already active**
  
- ISC.0086.9155      **Package "{0}" is already enabled**
  
- ISC.0086.9156      **Package "{0}" is already disabled**
  
- ISC.0086.9157      **Not able to convert headerLines to byte array**
  
- ISC.0086.9158      **Missing required parameter: 'headerLines'**
  
- ISC.0086.9159      **Invalid input. 'headerLines' must be an instance of IData**
  
- ISC.0086.9160      **Missing required parameter: 'body'**
  
- ISC.0086.9161      **Invalid input. 'bytes' must be an instance of byte array**
  
- ISC.0086.9162      **Invalid input. 'stream' must be an instance of InputStream**

---

ISC.0086.9163	<b>Invalid input. 'body' must be an instance of IData</b>
ISC.0086.9164	<b>Error reading inputstream: 'stream'</b>
ISC.0086.9165	<b>Both 'bytes' and 'stream' cannot be absent</b>
ISC.0086.9166	<b>bytes is a required field</b>
ISC.0086.9167	<b>stream is a required field</b>
ISC.0086.9168	<b>Could not retrieve raw data from implicitly signed message</b>
ISC.0086.9169	<b>Alias for Enterprise Gateway Proxy not specified</b>
ISC.0086.9170	<b>No of Connections to Enterprise Gateway Proxy not specified</b>
ISC.0086.9171	<b>New threshold for outstanding Requests not specified</b>
ISC.0086.9172	<b>Connection ID not specific</b>
ISC.0086.9173	<b>Listener Type not specified</b>
ISC.0086.9174	<b>Invalid input. "{0}" is a required parameter of type IData</b>
ISC.0086.9175	<b>Invalid input. "{0}" is a required parameter of type String</b>
ISC.0086.9176E	<b>Invalid input. "{0}" must be of type String</b>
<b>Explanation</b>	The specified input parameter must have a value of type String, but does not.
<b>Action</b>	Set the specified input paramater to a value that is of type String.

<b>ISC.0086.9177</b>	<b>Invalid input. "{0}" must be a positive integer</b>
<b>Explanation</b>	The specified input parameter contains an invalid value.
<b>Action</b>	Set the value of the specified input parameter to a positive integer.
<b>ISC.0086.9178</b>	<b>Invalid input. "{0}" must be true or false</b>
<b>Explanation</b>	The specified parameter must be set to true or false.
<b>Action</b>	Set the specified parameter to true or false.
<b>ISC.0086.9179</b>	<b>Missing required parameter: {0}</b>
<b>ISC.0086.9180</b>	<b>Invalid value for parameter: {0}. {0} is not a recognized numeric type</b>
<b>ISC.0086.9181E</b>	<b>Missing required parameter: pattern</b>
<b>Explanation</b>	The pattern input parameter is required, but has not been provided.
<b>Action</b>	Supply a value for the pattern input parameter.
<b>ISC.0086.9182</b>	<b>Missing required value: {document}</b>
<b>ISC.0086.9183</b>	<b>Missing one or more required values: {documentList,name}</b>
<b>ISC.0086.9184</b>	<b>Invalid or non-existing package name "{0}" provided</b>
<b>ISC.0086.9185</b>	<b>Missing required parameter: version</b>
<b>ISC.0086.9186</b>	<b>Missing required parameter: JVMversion</b>
<b>ISC.0086.9187</b>	<b>Missing required parameter: targetPkgVersion</b>
<b>ISC.0086.9189</b>	<b>Invalid date pattern or input</b>

---

ISC.0086.9193	<b>FTP session key not specified</b>
ISC.0086.9198	<b>Missing content or filename</b>
ISC.0086.9199	<b>{0} is not a valid directory!</b>
ISC.0086.9200	<b>Private key data must be in a byte array (byte[]).</b>
ISC.0086.9201	<b>Certificate chain data must be an array of byte array (byte[][]).</b>
ISC.0086.9202	<b>Certificate at position {0} in array is not in any recognizable format</b>
ISC.0086.9203	<b>Not a valid long number</b>
ISC.0086.9204E	<b>"{0}" is required.</b>
<b>Explanation</b>	A required input value is missing.
<b>Action</b>	Supply the missing input value and re-execute the service.
ISC.0086.9205E	<b>If "{0}" is supplied, it must be zero (0) or greater.</b>
<b>Explanation</b>	The indicated input value is a negative number, but it must be zero or a positive number.
<b>Action</b>	For the specified parameter, enter a value of 0 or a positive integer. Alternatively, if the specified parameter is optional, delete the supplied value.
ISC.0086.9206E	<b>"offset" + "length" cannot exceed the size of "{0}".</b>
<b>Explanation</b>	The values specified for offset and length are invalid because they will cause Integration Server to write data from the stream past the end of the supplied buffer.
<b>Action</b>	Supply valid values for offset and length.
ISC.0086.9207E	<b>The mark method is not supported by the supplied InputStream.</b>
<b>Explanation</b>	A service invoked the pub.io:mark service to mark a location on a stream, but the supplied stream does not implement the mark and reset methods.
<b>Action</b>	If you are invoking a user-written service, either use a different kind of InputStream that implements the mark and reset methods, or do not invoke the pub.io:mark service. Otherwise, contact Software AG Global Support.

<b>ISC.0086.9208E</b>	<b>The reset method is not supported by the supplied InputStream.</b>
<b>Explanation</b>	A service invoked the pub.io:reset service to reset to a location on a stream, but the supplied stream does not implement the mark and reset methods.
<b>Action</b>	If you are invoking a user-written service, either use a different kind of InputStream that implements the mark and reset methods, or do not invoke the pub.io:reset service.
<b>ISC.0086.9209E</b>	<b>"{0}" must be greater than zero (0).</b>
<b>Explanation</b>	The input variable specified is negative or zero, but the value must be a positive number.
<b>Action</b>	Supply a value greater than zero for the indicated input parameter.
<b>ISC.0086.9210</b>	<b>User specified encoding "{0}" does not match content encoding received from remote server.</b>
<b>ISC.0086.9211</b>	<b>No LDAP credentials provided</b>
<b>ISC.0086.9212</b>	<b>{0} is a required input</b>
<b>ISC.0086.9213</b>	<b>Notification for {0} is already registered</b>
<b>ISC.0086.9214</b>	<b>Notification for {0} does not exist</b>
<b>ISC.0086.9215</b>	<b>Invalid private key provided</b>
<b>ISC.0086.9217</b>	<b>Invalid certificate chain provided</b>
<b>ISC.0086.9218</b>	<b>Invalid partner certificate provided</b>
<b>ISC.0086.9220</b>	<b>Access to internal passwords denied</b>

---

ISC.0086.9221	Password input is required
ISC.0086.9222	Password input must be WmSecureString
ISC.0086.9223	Old password input is required
ISC.0086.9224	New password input is required
ISC.0086.9225	Password must be of type WmSecureString
ISC.0086.9226	Password for key already exists
ISC.0086.9227	Password for key does not exist. Must add password as new entry
ISC.0086.9228	Key cannot be null
ISC.0086.9229	Key cannot be empty
ISC.0086.9230	Must input string, bytes, or chars
ISC.0086.9232	XML needs to be provided.
ISC.0086.9233	A set of values for nodeSelectors must be provided.
ISC.0086.9234	Either a recipientID or a recipientCert must be provided.
ISC.0086.9235	The XML could not be parsed.

- ISC.0086.9236      Unable to set up the XPath context.
  
- ISC.0086.9237      The keystore or key alias information is incorrect.
  
- ISC.0086.9238      A value for baseURI must be provided for an enveloping signature.
  
- ISC.0086.9239      The reference URI did not provide any content to sign.
  
- ISC.0086.9245      The signatureSelector parameter must contain a value.
  
- ISC.0086.9248      The signature could not be found.
  
- ISC.0086.9250      Parameter [{0}] is not of type: [{1}]
  
- ISC.0086.9251      Column [{0}] is missing for the parameter: [{1}]
  
- ISC.0086.9252      key[{0}] does not exist in the pipeline
  
- ISC.0086.9253      [{0}] could not be converted to a number
  
- ISC.0086.9254      [{0}] could not be converted to a date
  
- ISC.0086.9255      Invalid date pattern[{0}] specified.
  
- ISC.0086.9256      File [{0}] does not exist
  
- ISC.0086.9257      File [{0}] exists, but is a directory

---

ISC.0086.9258	Directory [{0}] cannot be created
ISC.0086.9259	File [{0}] exists, but is read-only
ISC.0086.9260	Directory [{0}] does not exist
ISC.0086.9261	[{0}] is not a directory
ISC.0086.9262	Failed to delete original file [{0}] after copying the [{1}]
ISC.0086.9264	Error reading properties file: [{0}]
ISC.0086.9265	originalObject parameter does not implement java.io.Serializable interface
ISC.0086.9266	File [{0}] already exists
ISC.0086.9268	PARAM_NUMLIST [{0}]: [{1}] could not be parsed
ISC.0086.9270	No PrivateKey entry found for key alias {0}.
ISC.0086.9271	Invalid index[{0}]. Value should be between {1} and {2}
ISC.0086.9272	{0} cannot be empty
ISC.0086.9273	Invalid holiday date pattern [{0}] specified in the holidays.cnf file
ISC.0086.9274	Could not parse the holiday date [{0}] specified in the holidays.cnf file using the pattern [{1}]

- ISC.0086.9275      **Invalid weekend [{0}]. Valid value should be one of the following: 'sunday', 'monday', 'tuesday', 'wednesday', 'thursday', 'friday', 'saturday'**
- ISC.0086.9276      **'itemList' parameter should be an array**
- ISC.0086.9277      **Specified command [{0}] is not on the allowedOSCommands list in the OSCCommands.cnf file**
- ISC.0086.9278      **[{0}] may not exist or it may not be a directory**
- ISC.0086.9279      **Specified working directory [{0}] is not on the 'allowedWorkingDirectories' list in the OSCCommands.cnf file**
- ISC.0086.9280      **Unable to find the node corresponding to the provided signature node selector xpath {0}.**
- ISC.0086.9281      **Unable to find the encryption certificate for recipient {0}.**
- ISC.0086.9282      **Unable to resolve the certificate to verify the signature.**
- ISC.0086.9283      **An invalid schema location pair was provided**
- ISC.0086.9284      **Folder{0} is not empty**  
**Explanation**      The specified folder must be empty.  
**Action**              Delete the contents of the specified folder or specify an empty folder.
- ISC.0086.9285      **Invalid folder name {0}. Error : {1}**  
**Explanation**      The specified folder name is invalid.  
**Action**              Specify a valid folder name.

---

<b>ISC.0086.9286</b>	<b>HSM based Keystore is not supported</b>
<b>ISC.0086.9289E</b>	<b>Applications cannot use an HTTP Status-Code of {0}</b>
<b>Explanation</b>	Only valid HTTP Status-Codes may be supplied.
<b>Action</b>	Supply a valid HTTP Status-Code.
<b>ISC.0086.9310E</b>	<b>Could not restore pipeline from file {0}.</b>
<b>Explanation</b>	The pub.flow:restorePipelineFromFile service failed because the specified pipeline file could not be found in the IntegrationServer_directory\pipeline directory.
<b>Action</b>	Make sure the specified pipeline file exists in the IntegrationServer_directory\pipeline directory, and then restore the pipeline.
<b>ISC.0086.9311E</b>	<b>Could not save pipeline to file {0}.</b>
<b>Explanation</b>	The pub.flow:savePipelineToFile service failed because the IntegrationServer_directory\pipeline directory could not be found or does not exist.
<b>Action</b>	Make sure the IntegrationServer_directory\pipeline directory exists, and then save the pipeline.
<b>ISC.0086.9318E</b>	<b>{0} must be "{1}" or "{2}".</b>
<b>Explanation</b>	The service failed because the specified input variable contains an invalid value. The values allowed for the input variable are listed in the message text.
<b>Action</b>	Enter a valid value for the input variable.
<b>ISC.0086.9319E</b>	<b>{0} must be "{1}", "{2}", "{3}" or "{4}".</b>
<b>Explanation</b>	The service failed because the specified input variable contains an invalid value. The values allowed for the input variable are listed in the message text.
<b>Action</b>	Enter a valid value for the input variable.
<b>ISC.0086.9320E</b>	<b>If {0} is supplied, {1} must also be supplied.</b>
<b>Explanation</b>	The service failed because the combination of input variables defined in the service is invalid. The message text lists the required input variable combinations.
<b>Action</b>	Provide a valid combination of input variables.

<b>ISC.0086.9321E</b>	<b>If {0} is "{1}", {2} must be supplied.</b>
<b>Explanation</b>	The service failed because the combination of input variables defined in the service is invalid. The message text lists the required input variable combinations.
<b>Action</b>	Provide a valid combination of input variables.
<b>ISC.0086.9322E</b>	<b>{0} must be "{1}", "{2}", "{3}" or "{4}" or "{5}".</b>
<b>Explanation</b>	The service failed because the specified input variable contains an invalid value. The values allowed for the input variable are listed in the message text.
<b>Action</b>	Enter a valid value for the input variable.
<b>ISC.0086.9323E</b>	<b>{0} must be "{1}", "{2}" or "{3}".</b>
<b>Explanation</b>	The service failed because the specified input variable contains an invalid value. The values allowed for the input variable are listed in the message text.
<b>Action</b>	Enter a valid value for the input variable.
<b>ISC.0086.9324E</b>	<b>If {0} is "{1}", {2} and {3} must be supplied.</b>
<b>Explanation</b>	The service failed because the combination of input variables defined in the service is invalid. The message text lists the required input variable combinations.
<b>Action</b>	Provide a valid combination of input variables.
<b>ISC.0088.0001U</b>	<b>SOAPException: {0}</b>
<b>Explanation</b>	The SOAP message handler could not process the message because an error occurred.
<b>Action</b>	Examine the details element in the SOAP exception message for information about the specific failure that occurred.
<b>ISC.0088.0002E</b>	<b>Failed registering SOAP Processor, missing parameter: {0}</b>
<b>Explanation</b>	Integration Server failed to add the specified SOAP processor to the processor registry using the pub.soap.processor:registerProcessor service.
<b>Action</b>	Examine the service input and make sure that the fully qualified service name is specified correctly for input parameter "svcName".
<b>ISC.0088.0003E</b>	<b>Failed registering SOAP Processor {0} as directive {1}; directive already registered</b>
<b>Explanation</b>	Integration Server failed to add the specified SOAP processor to the processor registry using the pub.soap.processor:registerProcessor service.
<b>Action</b>	Make sure that the "directive" parameter specifies the correct directive. (Directive names are case-sensitive.) In addition, make sure that the specified directive is not already registered in the SOAP Processor registry. Often, this error occurs because the registry already contains a processor registered to the specified directive.

---

<b>ISC.0088.0004E</b>	<b>Failed registering SOAP Processor {0} as directive {1}; unknown service {0}</b>
<b>Explanation</b>	Integration Server failed to add the specified SOAP processor to the processor registry using the pub.soap.processor:registerProcessor service.
<b>Action</b>	Examine the service input and make sure that the fully qualified service name is specified correctly for input parameter "svcName". (Service names are case-sensitive.) Often, this error occurs because the service does not exist on the Integration Server.
<b>ISC.0088.0005E</b>	<b>Failed unregistering SOAP Processor, missing parameter: {0}</b>
<b>Explanation</b>	The pub.soap.processor:unregisterProcessor service failed to execute because the "directive" parameter was not supplied.
<b>Action</b>	Examine the service input and make sure that the "directive" parameter specifies the correct directive. (Directive names are case-sensitive.) Often, this error occurs because the directive is not specified.
<b>ISC.0088.0006E</b>	<b>Failed unregistering SOAP Processor {0}; no such directive registered</b>
<b>Explanation</b>	Integration Server failed to remove the specified processor from the SOAP Processor registry using the pub.processor:unregisterProcessor service.
<b>Action</b>	Make sure that the "processorName" parameter specifies the correct directive. (Remember that directive names are case-sensitive.) In addition, make sure that the specified directive is currently registered in the SOAP Processor registry. It may have already been removed. Usually, this error occurs because the registry does not contain a processor registered to the specified directive.
<b>ISC.0088.0007E</b>	<b>Failed registering SOAP Processor {0} as directive {1}; invalid character(s) in directive</b>
<b>Explanation</b>	Integration Server failed to add the specified processor to the SOAP Processor registry using the pub.processor:registerProcessor service.
<b>Action</b>	Examine the service input and make sure that the value for the "directive" parameter only contains characters that are part of a Unicode identifier. See the description of the Java standard for the full range of Unicode values. Usually, this error occurs because the specified directive contains characters that are not part of a Unicode identifier.
<b>ISC.0088.0008</b>	<b>Failed registering JAX Handler {0}; Handler already registered</b>
<b>ISC.0088.0009</b>	<b>Failed initializing JAX Handler {0}; error {1}</b>

ISC.0088.0010	Failed destroying JAX Handler {0}; error {1}
ISC.0088.0011	Failed registering JAX Handler {0}, missing parameter {1}
ISC.0088.0012	Failed unregistering JAX Handler {0}; handler not registered
ISC.0088.0013	Failed unregistering JAX Handler {0}, missing parameter {1}
ISC.0088.0014	Failed listing JAX Handlers, missing parameter {0}
ISC.0088.0015	Failed finding JAX Handler {0}, missing parameter {1}
ISC.0088.0016	Failed finding JAX Handler {0}, handler not registered
ISC.0088.0017	Failed finding JAX Handler for header {0}:{1}
ISC.0088.0020	pub.client:soapClient SOAP request sent: {0}
ISC.0088.0022	pub.client:soapClient OutputValidationError - pipeline: {0} result: {1}
ISC.0088.0023	pub.client:soapClient InputValidationError - result: {0}
ISC.0088.0024	Encode input ({0}): {1}
ISC.0088.0026	Decode input ({0}): {1}
ISC.0088.0028E	<b>Service handler {0} could not be registered. A service handler by that name already exists</b>
<b>Explanation</b>	A service handler with the provided name already exists.
<b>Action</b>	Specify a unique name for the service handler.

---

<b>ISC.0088.0029E</b>	<b>Error initializing handler {0}. Error {1}</b>
<b>Explanation</b>	An error occurred while initializing the JAX-RPC header handler.
<b>Action</b>	The init() method of the JAX-RPC handler threw an error. Correct the error in init() method.
<b>ISC.0088.0030E</b>	<b>Error destroying service handler {0}. Error:{1}</b>
<b>Explanation</b>	An error occurred while destroying the JAX-RPC handler.
<b>Action</b>	The destroy() method of the JAX-RPC Handler has thrown an error. Correct the error in destroy() method.
<b>ISC.0088.0031E</b>	<b>Service handler {0} could not be registered. Missing required parameter {1}</b>
<b>Explanation</b>	A parameter required to register the service handler was not provided.
<b>Action</b>	Provide the missing parameter.
<b>ISC.0088.0032E</b>	<b>Service handler {0} could not be unregistered. A service handler by that name is not registered</b>
<b>Explanation</b>	The specified service handler is not registered.
<b>Action</b>	Provide the name of a registered service handler.
<b>ISC.0088.0033E</b>	<b>Service handler {0} could not be unregistered. Missing required parameter {1}</b>
<b>Explanation</b>	The service handler could not be unregistered because a required parameter is missing.
<b>Action</b>	Provide the missing parameter.
<b>ISC.0088.0034E</b>	<b>Registered service handlers could not be listed. Missing required parameter {0}</b>
<b>Explanation</b>	The list of registered service handlers could not be created because a required input parameter was not provided.
<b>Action</b>	Provide the missing input parameter.
<b>ISC.0088.0035E</b>	<b>Service handler {0} could not be found. Missing required parameter {1}</b>
<b>Explanation</b>	Service handler could not be found because a required input parameter was not provided.
<b>Action</b>	Provide the missing input parameter.

<b>ISC.0088.0036E</b>	<b>Service handler {0} could not be found. Service handler is not registered</b>
<b>Explanation</b>	A service handler with the provided name does not exist.
<b>Action</b>	Register a service handler with the provided name or specify the name of an existing registered service handler.
<b>ISC.0088.0037E</b>	<b>Could not find service handler for header {0}:{1}</b>
<b>Explanation</b>	The QName of the header does not correspond to a registered service handler.
<b>Action</b>	Verify that the QName of the header corresponds to a registered service handler or register a service handler for the provided universal name.
<b>ISC.0088.0038E</b>	<b>Error while processing asynchronous SOAP response received by the consumer Web service descriptor {0}. SOAP Message : {1}</b>
<b>Explanation</b>	Integration Server failed to process the asynchronous SOAP response directed to the consumer web service descriptor specified in the message.
<b>Action</b>	Check the server log and error log to find possible causes of this error and take corrective steps.
<b>ISC.0088.0039E</b>	<b>Error while processing asynchronous SOAP response received by the consumer Web service descriptor {0}.</b>
<b>Explanation</b>	Integration Server failed to process the asynchronous SOAP response directed to the consumer Web service descriptor specified in the message, possibly because the SOAP response is not well formed.
<b>Action</b>	Check the server log and error log to find possible causes of this error and take corrective steps.
<b>ISC.0088.0100</b>	<b>WS Security processing failed : Unable to convert SOAPMessage into a Document : {0}</b>
<b>ISC.0088.0101</b>	<b>WS Security processing failed : Unable to convert Document into a SOAPMessage : {0}</b>
<b>ISC.0088.0102</b>	<b>WS Security processing failed : A valid Document was not specified. Unable to create SOAPMessage</b>

---

ISC.0088.0103	WS Security processing failed : UsernameToken supported only with PasswordType as Text
ISC.0088.0104	WS Security processing failed : Invalid Credentials. User name {0}
ISC.0088.0105	WS Security processing failed : Authentication failed for user : {0}
ISC.0088.0106	WS Security processing failed : X509 Authentication failed with exception : {0}
ISC.0088.0107	WS Security processing failed : Unable to create Keystore
ISC.0088.0108	WS Security processing failed : Unable to create Crypto
ISC.0088.0109	WS Security processing failed : Invalid private key passed in to the Web service connector.
ISC.0088.0110	WS Security processing failed : Invalid certificate chain passed in to the Web service connector.
ISC.0088.0111	WS Security processing failed : Error while reading the private key/certificates from the Web service endpoint
ISC.0088.0112	WS Security processing failed : Error while operating on Keystore
ISC.0088.0113	WS Security processing failed : Unable to resolve partner certificate for encrypting the response
ISC.0088.0114	WS Security processing failed : Untrusted certificate chain
ISC.0088.0115	WS Security processing failed : Error during response encryption while retrieving partner certificate from the certificate mapper.

**ISC.0088.0116**      **WS Security processing failed : Invalid outbound security policy. Username token assertion not supported in the response**

**ISC.0088.0117**      **WS Security processing failed : Invalid outbound security policy. X509Authenticion token assertion not supported in the response**

**ISC.0088.0118**      **WS Security processing failed : Unable to resolve private key for signing or decrypting the message**

**ISC.0088.0119**      **WS Security processing failed : Unexepected error occurred while accessing the Keystore/Truststore**

**ISC.0088.0120**      **WS Security processing failed : Unable to resolve partner certificate for encrypting the request**

**ISC.0088.0200E**      **WS Security processing failed: Unable to retrieve {0} provider Web service endpoint alias named "{1}"**

**Explanation**      Integration server could not find the provider Web service endpoint alias with the type and name specified in the message.

**Action**              Create an appropriate provider Web service endpoint alias.

**ISC.0088.0201E**      **WS Security processing failed: Decryption of encrypted key failed because the key is encrypted with an unknown certificate.**

**Explanation**      Integration Server is unable to find a private key corresponding to the certificate used to encrypt the key.

**Action**              Configure an appropriate keystore in the WS Security Properties section of the appropriate consumer or provider Web service endpoint alias or by using the Decryption Key option under Security > Certificates in the Integration Server Administrator.

**ISC.0088.0202E**      **WS Security processing failed: Unable to resolve the private key required for signing the SOAP request.**

**Explanation**      Private key required for signing the SOAP request is not configured.

**Action**              Configure a keystore by adding the values in the WS Security Properties section of the appropriate consumer Web Service endpoint alias or by using the Signing Key option under Security > Certificates in the Integration Server Administrator.

---

<b>ISC.0088.0203E</b>	<b>WS Security processing failed: Unable to resolve the private key required for signing the SOAP response.</b>
<b>Explanation</b>	Private key required for signing the SOAP response is not configured.
<b>Action</b>	Configure a keystore by adding the values in the WS Security Properties section of the appropriate provider Web Service endpoint alias or by using the Signing Key option under Security > Certificates in the Integration Server Administrator.
<b>ISC.0088.0204E</b>	<b>WS Security processing failed: Invalid partner certificate passed into the Web service connector.</b>
<b>Explanation</b>	Value provided for auth/message/partnerCert field while executing the Web service connector is invalid.
<b>Action</b>	Provide a valid certificate for auth/message/partnerCert.
<b>ISC.0088.0205E</b>	<b>WS Security processing failed: Invalid partner certificate provided in the endpoint alias "{0}".</b>
<b>Explanation</b>	Partner certificate file provided in the endpoint alias mentioned in the message is invalid.
<b>Action</b>	Specify a valid partner certificate file in the endpoint alias mentioned in the message.
<b>ISC.0088.0206E</b>	<b>WS Security processing failed: Unable to resolve the private key required for decrypting the SOAP request.</b>
<b>Explanation</b>	Private key required for decrypting the SOAP request is not configured.
<b>Action</b>	Configure a keystore by adding the values in the WS Security Properties section of the appropriate provider Web service endpoint alias or by using the Decryption Key option under Security > Certificates in the Integration Server Administrator.
<b>ISC.0088.0207E</b>	<b>WS Security processing failed: Unable to resolve the private key required for decrypting the SOAP response.</b>
<b>Explanation</b>	Private key required for decrypting the SOAP response is not configured.
<b>Action</b>	Configure a keystore by adding the values in the WS Security Properties section of the appropriate consumer Web service endpoint alias or by using the Decryption Key option under Security > Certificates in the Integration Server Administrator.
<b>ISC.0088.0208E</b>	<b>WS Security processing failed: Decryption failed because the SOAP message is encrypted with an unknown certificate.</b>
<b>Explanation</b>	Integration server is unable to find a private key corresponding to the certificate used to encrypt the message.
<b>Action</b>	Configure an appropriate keystore in the WS Security Properties section of the appropriate consumer or provider Web service endpoint alias or by using the

Decryption Key option under Security > Certificates in the Integration Server Administrator.

**ISC.0088.0209E**      **WS Security processing failed: Signature verification failed because the certificate associated with the signing private key is unknown.**

**Explanation**      Integration server is unable to find a certificate corresponding to the private key used to sign the message.

**Action**      Ensure that the certificate corresponding to the private key used to sign the message is imported into the certificate mapper using Security > Certificates > Configure Client Certificates in the Integration Server Administrator.

**ISC.0088.0210E**      **WS Security processing failed: Error retrieving certificate from certificate mapper.**

**Explanation**      Integration Server failed to retrieve the certificate corresponding to the private key that was used to sign the message. Integration Server encountered an unexpected error when attempting to retrieve the certificate from the certificate mapper.

**Action**      Probable cause is that the embedded database of Integration Server that is used to store the certificates is corrupted. Contact Software AG Global Support.

**ISC.0088.0211W**      **WS Security processing failed: Binder for the SOAP action "{0}" in the Web service descriptor "{1}" not found. Integration Server will use server private keys and certificates for handling WS-Security.**

**Explanation**      Integration Server cannot find the binder for the specified SOAP action in the Web service descriptor. Integration Server is unable to use the private keys and certificates from the endpoint alias. As a result, Integration Server will use the server private keys and certificates.

**Action**      Ensure that the correct SOAP action is specified in the incoming SOAP request.

**ISC.0088.0212E**      **WS Security processing failed: HSM keystores are not supported.**

**Explanation**      The Integration Server WS-Security functionality does not support HSM keystores.

**Action**      Use a supported keystore type, for example, PKCS12 or JKS.

**ISC.0088.0213E**      **WS Security processing failed: Integration server only supports Username token with password type {0}, but received with password type {1}.**

**Explanation**      Incoming SOAP request has an unsupported password type in the Username token. Integration Server supports Username tokens with passwords of type:  
{<http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-username-token-profile-1.0>#PasswordText only.

**Action**      Ensure that the SOAP request the requester/client sends has a valid Username token.

---

<b>ISC.0088.0214E</b>	<b>WS Security processing failed: Unable to retrieve {0} consumer Web service endpoint alias named "{1}"</b>
<b>Explanation</b>	Integration server could not find the consumer Web service endpoint alias with the type and name specified in the message.
<b>Action</b>	Create an appropriate consumer Web service endpoint alias.
<b>ISC.0088.9129E</b>	<b>Invalid node: XML blocks must be in a container</b>
<b>ISC.0088.9131E</b>	<b>Invalid node: must be well-formed XML</b>
<b>ISC.0088.9142E</b>	<b>Invalid Body Entry. SOAP Body Entries must have a namespace name.</b>
<b>ISC.0088.9143E</b>	<b>Invalid Header Entry. SOAP Header Entries must have a namespace name.</b>
<b>ISC.0088.9165E</b>	<b>Soap Coder not found for a {0} SOAPMessage</b>
<b>ISC.0088.9167E</b>	<b>Service not found for soapAction = {0}</b>
<b>ISC.0088.9168E</b>	<b>SOAP Version Mismatch: SOAP Version "{0}" in request does not match the SOAP version "{1}" of the Web service.</b>
<b>ISC.0088.9169E</b>	<b>External WSDL URL does not exist for {0}, its a service first WSD.</b>
<b>ISC.0088.9170E</b>	<b>SOAP Version Mismatch: SOAP Version "{0}" in response does not match the SOAP version "{1}" of the Web service.</b>
<b>ISC.0088.9256E</b>	<b>Fault returned by invoked service</b>
<b>ISC.0088.9300E</b>	<b>Attachment Processing Failed: Can't get the size of the attachment due to an I/O Error</b>

**ISC.0088.9301E      Attachment Processing Failed: Can't retrieve the content due to an I/O Error**

**ISC.0088.9302E      Attachment Processing Failed: Attachment contains 'null' content**

**ISC.0088.9303E      Attachment Processing Failed: The value for Data Handler is 'null'**

**ISC.0088.9304E      Attachment Processing Failed: Data Handler contains 'null' Input Stream**

**ISC.0088.9320E      MTOM Attachments Processing Failed: Cannot convert SOAP Message to XOP Package; 'null' value for 'Web Service Descriptor'**

**Explanation**      The Web service descriptor identified by the part of request URL (for provider) or passed Web service descriptor name (for consumer) as parameter, does not exist.

**Action**             Correct the URL or correct the passed Web service descriptor name or create a proper Web service descriptor.

**ISC.0088.9321E      MTOM Attachments Processing Failed: Cannot convert SOAP Message to XOP Package; base64Binary encoded data is not in the Canonical Lexical form**

**Explanation**      Base64Binary encoded data is not in Canonical Lexical form; it contains line break characters or tabs.

**Action**             Convert the Base64Binary data into Canonical Lexical form.

**ISC.0088.9322E      MTOM Attachments Processing Failed: Cannot convert SOAP Message to XOP Package; invalid SOAP Message**

**Explanation**      The SOAP Message is invalid; either it is not well formed or it does not contain valid namespace declarations.

**Action**             Check the structure and content of the SOAP message.

**ISC.0088.9323      MTOM Attachments Processing Failed: Cannot convert SOAP Message to XOP Package; I/O Error occurred**

**Explanation**      Converting SOAP Message to XOP Package has been interrupted by another thread.

**Action**             Retry the action that caused it.

---

<b>ISC.0088.9324E</b>	<b>MTOM Attachments Processing Failed: Cannot convert XOP Package to SOAP Message; 'Content-Id' header field is missing in some of the attachments</b>
<b>Explanation</b>	One or more attachments does not contain the “Content-Id” field. This field is required to put the content of the attachment back into the SOAP message.
<b>Action</b>	Verify that the serialization of XOP Package to MIME stream had “Content-Id” present in the corresponding MIME part.
<b>ISC.0088.9325E</b>	<b>MTOM Attachments Processing Failed: Cannot serialize the XOP Message; unable to retrieve bytes from SOAP String using the SOAP Message Content Encoding</b>
<b>Explanation</b>	The conversion of SOAP String to byte array using the encoding specified for SOAP message has failed.
<b>Action</b>	Correct the content encoding specified for the SOAP message.
<b>ISC.0088.9326E</b>	<b>MTOM Attachments Processing Failed: Cannot serialize the XOP Message; MIME serialization has failed</b>
<b>Explanation</b>	Serialization of XOP Package to MIME Stream has failed.
<b>Action</b>	Verify the structure of SOAP Message is correct. Particularly the elements which contains base64Binary data.
<b>ISC.0088.9327E</b>	<b>MTOM Attachments Processing Failed: Cannot de-serialize the input MIME Stream; value of the 'Content-Type' header of the MIME message is not equal to 'multipart/related'</b>
<b>Explanation</b>	Value for the “Content-Type” header field of the MIME message is not equal to “multipart/related”.
<b>Action</b>	Verify that you have passed the correct value for “Content-Type” while serializing the MIME message.
<b>ISC.0088.9328E</b>	<b>MTOM Attachments Processing Failed: Cannot de-serialize the input MIME Stream; value of the 'type' parameter of the 'Content-Type' header of the MIME message is not equal to 'application/xop+xml'</b>
<b>Explanation</b>	Value for the “type parameter” of the “Content-type” header field of the MIME message is not equal to “application+xop+xml”.
<b>Action</b>	Verify that you have passed the correct value for “type” parameter while serializing the MIME message.

**ISC.0088.9329E**      **MTOM Attachments Processing Failed: Cannot de-serialize the input MIME Stream; value of the 'start-info' parameter of the 'Content-Type' header of the MIME message is not equal to 'application/soap+xml'**

**Explanation**      Value for the “start-info” parameter of the “Content-Type” header field of the MIME message is not equal to “application/soap+xml”.

**Action**            Check if you have passed the correct value for “start-info” parameter while serializing the MIME message otherwise pass the correct value for it.

**ISC.0088.9330E**      **MTOM Attachments Processing Failed: Cannot de-serialize the input MIME Stream; 'Content-Type' header of the Root MIME Part is invalid**

**Explanation**      Invalid content type for Root MIME part.

**Action**            Verify that you have passed the correct value for “Content-Type” header field of the Root MIME Part while serializing the MIME message.

**ISC.0088.9331E**      **MTOM Attachments Processing Failed: Cannot de-serialize the input MIME Stream; 'Content-Type' header of the Root MIME Part does not match with the 'type' parameter of the MIME message**

**Explanation**      The value of the “Content-Type” header of the Root MIME Part is not equal to the value of the “type” parameter of the “Content-Type” header of the MIME message.

**Action**            Verify that you have passed the correct value for these field(s)/parameter(s) while serializing the MIME message.

**ISC.0088.9332E**      **MTOM Attachments Processing Failed: Cannot de-serialize the input MIME Stream; value of 'type' parameter of the 'Content-Type' header of the Root MIME Part does not match with the value of the 'start-info' parameter of the MIME message**

**Explanation**      The value of the “type” parameter of the “Content-Type” header of the Root MIME Part is not equal to the value of the “start-info” parameter of the “Content-Type” header of the MIME Message.

**Action**            Verify that you have passed the correct value for these field(s)/parameter(s) while serializing the MIME.

**ISC.0088.9333E**      **MTOM Attachments Processing Failed: Cannot de-serialize the input MIME Stream; SOAP Message in the Root MIME part is not of version 1.2**

**Explanation**      The version of the SOAP Message not equal to 1.2.

**Action**            Send the SOAP 1.2 message.

---

<b>ISC.0088.9334E</b>	<b>MTOM Attachments Processing Failed: Cannot de-serialize the input MIME Stream; Root MIME Part contains invalid SOAP Message</b>
<b>Explanation</b>	The SOAP Message in the Root MIME Part is invalid; either it is not well formed or it does not contain valid namespace declarations.
<b>Action</b>	Check the structure and content of the SOAP message in the Root MIME Part.
<b>ISC.0088.9335E</b>	<b>MTOM Attachments Processing Failed: Cannot de-serialize the input MIME Stream; input stream is not a valid MIME stream</b>
<b>Explanation</b>	MIME Stream does not contain the valid data as per the MIME specifications.
<b>Action</b>	Verify that the MIME stream contains a valid MIME message.
<b>ISC.0088.9336E</b>	<b>Retrieving contents of the XOPObjct failed: "{0}"</b>
<b>Explanation</b>	You attempted to read the contents from an XOPObjct. However, previous logic in either the same service or a previous service has already read the XOPObjct. The XOPObjct instance can only be read one time.
<b>Action</b>	Update the service logic so that it reads an XOPObjct only one time.
<b>ISC.0088.9351E</b>	<b>Could not find Web Service Descriptor with name {0}</b>
<b>ISC.0088.9352E</b>	<b>Handler {1} not associated with Web Service Descriptor {0}</b>
<b>ISC.0088.9353E</b>	<b>Could not find policy with name {0}</b>
<b>ISC.0088.9354E</b>	<b>Missing required parameter : {0}</b>
<b>ISC.0088.9355E</b>	<b>First element of the SOAP-ENV:Body must have a QName</b>
<b>ISC.0088.9400E</b>	<b>Invalid BOOLEAN value {0} for variable {1}; must be true or false</b>
<b>ISC.0088.9432E</b>	<b>SOAP Header data does not conform to Header Record: {0}</b>

- ISC.0088.9433E**      **Access denied to Handler Service {0} in the Handler Chain**
- ISC.0088.9434E**      **Provided header data for the header named "{0}" exceeds the number of headers expected by Web Service Descriptor "{1}"**
- ISC.0088.9500E**      **Unable to determine SOAP version. Make sure that entry has a valid parent.**
- ISC.0088.9501E**      **Invalid namespace: {0}**
- ISC.0092.9117E**      **Invalid WSDL; URISyntaxException - Invalid URI found in the {0} attribute of the {1} element - BASE={2} URI={3}**
- Explanation**      The WSDL document used to create a WSDL first provider web service descriptor or a consumer web service descriptor contains a URI with invalid characters or syntax at the specified location.
- Action**      Correct the invalid URIs in the WSDL document and attempt to create the web service descriptor again.
- ISC.0092.9118E**      **Port "{0}" is not unique within service "{1}"**
- Explanation**      When creating a consumer Web service descriptor from a WSDL with the specified service, the service definition contains multiple ports that all have the same name.
- Action**      Update the WSDL so that the port name is unique within the service definition.
- ISC.0092.9119E**      **Schema definition not found for imported namespace(s):{0}**
- Explanation**      While creating a consumer Web service descriptor or a WSDL first provider Web service descriptor from a WSDL document, Integration Server determined that the WSDL document contained one or more `xsd:import` elements that did not specify the `schemaLocation` attribute. Consequently, the schema processor in Integration Server cannot locate the schema definition for the imported namespace and Web service descriptor creation fails. When this message appears at run time, the {0} in the message is replaced by the list of the imported namespaces for which a `schemaLocation` attribute is not specified.
- Action**      Correct the WSDL document by adding a valid `schemaLocation` attribute for each `xsd:import` element that did not specify a `schemaLocation`. The value of the `schemaLocation` attribute is a URI to the XML Schema definition for the imported namespace. Alternatively, modify the WSDL document by adding in inline schema definition for each namespace with a missing `schemaLocation` to the `wsdl:types` element in the WSDL document. Then attempt to create the Web service descriptor from the WSDL document.

---

<b>ISC.0107.9001E</b>	<b>Cannot create element "{0}"; a document type or schema with this name already exists on the Integration Server.</b>
<b>Explanation</b>	While trying to pull a document from the Broker, Integration Server determined that a record being referenced already existed on the Integration Server. As a result, synchronization could not continue.
<b>Action</b>	When synchronizing document types, clear the "Overwrite existing elements when importing referenced elements" check box.
<b>ISC.0107.9002</b>	<b>Cannot create field "{0}" in Broker document type for "{1}"; this field name is not valid on the Broker. The Broker will transport the field contents, which will be visible to Integration Server clients only.</b>
<b>ISC.0107.9003</b>	<b>Cannot retrieve "{0}"; document type with this name does not exist on the Integration Server.</b>
<b>ISC.0107.9004</b>	<b>Cannot make "{0}" unpublishable; it is not a publishable document type.</b>
<b>ISC.0107.9005</b>	<b>Cannot make "{0}" publishable; it is already a publishable document type.</b>
<b>ISC.0107.9006</b>	<b>Cannot create field "{0}" in Broker document type for "{1}"; recursive types cannot be represented on the Broker. The Broker will transport the field contents, which will be visible to Integration Server clients only.</b>
<b>ISC.0107.9007</b>	<b>Cannot make "{0}" publishable; it contains the field name '_env'.</b>
<b>ISC.0107.9008</b>	<b>Cannot make document type "{0}" publishable; this name is not valid.</b>
<b>ISC.0107.9009</b>	<b>Cannot make "{0}" publishable; the referenced document type "{1}" does not exist.</b>
<b>ISC.0107.9010</b>	<b>Cannot create field "{0}" in Broker document type for "{1}"; field with duplicate names are not permitted on the Broker.</b>

ISC.0107.9011	<b>SimpleType with the name "{0}" does not exist on the Integration Server.</b>
ISC.0107.9012	<b>Could not lock node "{0}"{1}</b>
ISC.0107.9013	<b>Could not create node "{0}". User "{1}" does not have write permission on folder "{2}".</b>
ISC.0124.9017E	<b>Document to XSD error: Field {0} cannot be represented in XML Schema. The field contains an XML Namespace property but the field name does not contain a prefix</b>
<b>Explanation</b>	A service for which a service first provider web service descriptor is being created uses an IS document type that contains a field with an assigned XML namespace property value. However, the field name does not include a prefix to associate with the XML namespace. That is, the field name is not in the format prefix:localName.
<b>Action</b>	Either add a prefix to the field name using the format prefix:localName or remove the value assigned to the XML namespace property. Important! Some protocols require the use of an XML namespace. Review the documentation for service signature requirements for service first provider web service descriptors.
ISC.0124.9019E	<b>Document to XSD error: Document type {0} cannot be represented in XML Schema. The document type is an XML document type.</b>
<b>Explanation</b>	Integration Server cannot create an XML Schema definition from an XML document type. Integration Server can create an XML Schema definition from an IS document type only. This error can appear whenever Integration Server creates an XML schema definition, such as when executing the pub.schema:createXSD service or when generating WSDL from a web service descriptor.
<b>Action</b>	Replace the XML document type with an IS document type.
ISC.0164.01Error	<b>Specified instance {0} is not a multiple of {1}.</b>
<b>Explanation</b>	The object instance in the JSON input is not a multiple of the value specified in the schema.
<b>Action</b>	Ensure that the object instance in the JSON input is a multiple of the value specified in the schema.
ISC.0164.02Error	<b>Specified numeric instance: {1} is greater than the allowed maximum value: {0}.</b>
<b>Explanation</b>	The value of the numeric instance in the JSON input is not less than or equal to the value specified in the schema.
<b>Action</b>	Reduce the specified value in the JSON input to be less than or equal to the maximum value allowed in the schema.

---

<b>ISC.0164.03Error</b>	<b>Specified numeric instance is not strictly less than the allowed maximum value: {0}.</b>
<b>Explanation</b>	The value of the numeric instance in the JSON input is greater than the value specified in the schema.
<b>Action</b>	Reduce the specified value in the JSON input to be strictly less than the maximum value allowed in the schema.
<b>ISC.0164.04Error</b>	<b>Specified numeric instance: {1} is less than the required minimum value: {0}.</b>
<b>Explanation</b>	The value of the numeric instance in the JSON input is not greater than or equal to the value specified in the schema.
<b>Action</b>	Change the specified value in the JSON input to be greater than or equal to the minimum value required in the schema.
<b>ISC.0164.05Error</b>	<b>Specified numeric instance is not strictly greater than the required minimum value: {0}.</b>
<b>Explanation</b>	The value of the numeric instance in the JSON input is less than the value specified in the schema.
<b>Action</b>	Change the specified value in the JSON input to be greater than the minimum value required in the schema.
<b>ISC.0164.06Error</b>	<b>Specified string: {0} of length: {1} is longer than the allowed maximum value: {2}.</b>
<b>Explanation</b>	The length of the string provided in the JSON input is greater than the value specified in the schema.
<b>Action</b>	Reduce the length of the string in the JSON input to be less than or equal to the maximum length specified in the schema.
<b>ISC.0164.07Error</b>	<b>Specified string: {0} of length: {1} is shorter than the required minimum value: {2}.</b>
<b>Explanation</b>	The length of the string provided in the JSON input is less than the value specified in the schema.
<b>Action</b>	Increase the length of the string in the JSON input to be greater than or equal to the minimum value specified in the schema.
<b>ISC.0164.08Error</b>	<b>Specified string: {0} does not match the ECMA 242 pattern: {1}.</b>
<b>Explanation</b>	The string provided in the JSON input does not match the pattern specified in the schema.
<b>Action</b>	Ensure that the input string matches the pattern specified in the schema.

<b>ISC.0164.10Error</b>	<b>Schema allows only {0} elements in an array, but the specified instance has {1} elements.</b>
<b>Explanation</b>	The array has elements other than those specified in the schema.
<b>Action</b>	Remove additional elements from the array to include only those that are specified in the schema.
<b>ISC.0164.11Error</b>	<b>Schema allows a maximum of {0} elements in an array, but the specified instance has {1} elements.</b>
<b>Explanation</b>	The specified array has more elements than the maximum allowed in the schema.
<b>Action</b>	Remove additional elements from the array to ensure that the total number of elements is less than or equal to the maximum allowed in the schema.
<b>ISC.0164.12Error</b>	<b>Schema requires a minimum of {0} elements in an array, but the specified instance has {1} elements.</b>
<b>Explanation</b>	The specified array has fewer elements than the minimum required in the schema.
<b>Action</b>	Add more elements to the array to ensure that the total number of elements is greater than or equal to the minimum required in the schema.
<b>ISC.0164.13Error</b>	<b>Array must not contain duplicate elements.</b>
<b>Explanation</b>	The specified array has duplicate elements.
<b>Action</b>	Remove duplicate elements from the array to ensure that it contains only unique elements.
<b>ISC.0164.15Error</b>	<b>Schema allows a maximum of {0} properties, but the specified object instance has {1} properties.</b>
<b>Explanation</b>	The specified object instance has more properties than the maximum allowed in the schema.
<b>Action</b>	Remove additional properties to ensure that the number of properties in the object instance is less than or equal to the maximum allowed value in the schema.
<b>ISC.0164.16Error</b>	<b>Schema requires a minimum of {0} properties, but the specified object instance has {1} properties.</b>
<b>Explanation</b>	The specified object instance has more properties than the minimum required in the schema.
<b>Action</b>	Add properties to ensure that the number of properties in the object instance is greater than or equal to the minimum required value in the schema.

---

<b>ISC.0164.17Error</b>	<b>Specified object instance must have the following required properties: {0}. The following properties are missing: {1}.</b>
<b>Explanation</b>	The object instance must have all the required properties specified in the schema.
<b>Action</b>	Add the required properties that are missing to the object instance.
<b>ISC.0164.20Error</b>	<b>Specified object instance has the following additional properties that the schema does not allow: {0}.</b>
<b>Explanation</b>	The object instance has properties other than those specified in the schema.
<b>Action</b>	Remove the additional properties from the object instance.
<b>ISC.0164.21Error</b>	<b>Property {0} is missing the following required property dependencies: {1}.</b>
<b>Explanation</b>	The JSON input does not contain dependency details for the specified property.
<b>Action</b>	Add the dependency for the specified property to the JSON input.
<b>ISC.0164.23Error</b>	<b>Specified instance value: {0} not found in enumeration with the following possible values: {1}.</b>
<b>Explanation</b>	The specified value is not among the possible enumeration values given in the schema.
<b>Action</b>	Make the required changes so that the specified values is among the possible enumeration values given in the schema.
<b>ISC.0164.25Error</b>	<b>Specified instance type: {0} does not match any of the allowed primitive types: {1}.</b>
<b>Explanation</b>	The specified input does not match any of the primitive types allowed in the schema.
<b>Action</b>	Change the input type to match the primitive types allowed in the schema.
<b>ISC.0164.26Error</b>	<b>Specified instance failed to match all the required schemas. Matched only {0} out of {1}.</b>
<b>Explanation</b>	The specified instance does not match all the schema instances.
<b>Action</b>	Change the input content so that it matches all the specified schema instances.
<b>ISC.0164.27Error</b>	<b>Specified instance failed to match at least one required schema out of {0}.</b>
<b>Explanation</b>	The specified instance does not match at least one of the schema instances.
<b>Action</b>	Change the input content so that it matches at least one of the specified schema instances.

<b>ISC.0164.28Error</b>	<b>Specified instance failed to match exactly one schema. Matched {0} out of {1}.</b>
<b>Explanation</b>	The specified instance matches more than one of the schema instances.
<b>Action</b>	Change the input content so that it matches exactly one of the specified schema instances.
<b>ISC.0164.29Error</b>	<b>Specified instance should not have matched the schema.</b>
<b>Explanation</b>	The specified instance matches the schema.
<b>Action</b>	Change the input content to not match the specified schema.
<b>ISC.81.9187W</b>	<b>JAX-RPC handlers are not supported when the Pre-8.2 compatibility mode is false. The following handlers will be ignored at run time: {0}</b>
<b>Explanation</b>	Integration Server only supports JAX-RPC handlers for use with Web service descriptors that run in pre-8.2 compatibility mode (i.e., when the Pre-8.2 compatibility mode property is true).
<b>Action</b>	To continue using the JAX-RPC handler, change the Web service descriptor to run in pre-8.2 compatibility mode. If you do not want to run the Web service descriptor in pre-8.2 compatibility mode, replace the JAX-RPC handler with a service handler that has the same behavior.
<b>ISC.81.9188W</b>	<b>Port type names of all the binders will be changed to "{0}". As a result, all bindings in the generated WSDL will use the same port type.</b>
<b>Explanation</b>	When a Web service descriptor's Pre-8.2 compatibility mode property is set to false, Integration Server generates WSDL with all the bindings referring to same port type. As a result, when you change the Pre-8.2 compatibility mode property from true to false, Integration Server changes the port type names of all the binders to (wsdName)_PortType, where (wsdName) is the Web service descriptor name.
<b>Action</b>	Depending on your web service client framework, you may need to regenerate or recreate existing Web service clients from the WSDL.
<b>ISC.81.9189E</b>	<b>All binders must have the same binding style and use when Pre-8.2 compatibility mode is false.</b>
<b>Explanation</b>	When a Web service descriptor's Pre-8.2 compatibility mode property is set to false, Integration Server does not allow the Web service descriptor to have binders that have different binding styles and use. Integration Server issues this message when either you are attempting to create a new binder for a Web service descriptor and the new binder has a different binding style or use from the existing binders, or when you are trying to consume a WSDL to create a Web service descriptor and WSDL has multiple bindings with different style and use.
<b>Action</b>	If you are trying to create a new binder for a Web service descriptor, use the same binding style and use as the existing binders. If you are trying to consume a WSDL that contains multiple bindings with different style and use, split the WSDL into multiple WSDLs that each use the same style and use.

<b>ISC.81.9190E</b>	<b>Multiple port types are not supported when Pre-8.2 compatibility mode is false.</b>
<b>Explanation</b>	The WSDL document used to create the Web service descriptor consists of multiple port types. When creating a Web service descriptor in Designer, Integration Server does not support multiple port types.
<b>Action</b>	Split the WSDL document that consists of multiple port types into multiple WSDL documents that each use a single port type. Then, create Web service descriptors from each WSDL document.
<b>ISC.81.9196W</b>	<b>MTOM streaming is not supported when the Pre-8.2 compatibility mode is true.</b>
<b>Explanation</b>	When the Pre-8.2 compatibility mode property of a Web service descriptor is set to true, Integration Server does not support MTOM streaming of attachments. Integration Server issues this message when you change the Pre-8.2 compatibility mode property from false to true and when at least one of the operation's input or output signature contains a field of type Object and the java wrapper type is set to com.wm.util.XOPObject.
<b>Action</b>	To continue using MTOM streaming, set the Pre-8.2 compatibility mode property of the Web service descriptor to false. If you want to run the Web service descriptor in pre-8.2 compatibility mode, ensure that the attachment size is not very large to avoid out of memory errors.
<b>ISC.88.9171E</b>	<b>Operation not found for soapAction = {0}</b>
<b>Explanation</b>	Integration Server could not find the operation for the SOAP action specified in the incoming SOAP request.
<b>Action</b>	Ensure that the correct SOAP action is specified in the incoming SOAP request. For a service first provider, if needed, you can edit the SOAP action to operation map present in the binder properties.
<b>ISC.88.9172E</b>	<b>Web service cannot be found for endpoint reference (EPR) = {0}</b>
<b>Explanation</b>	Integration Server could not find the Web service with the specified endpoint reference.
<b>Action</b>	Ensure that the Web service descriptor with the endpoint reference exists in the Integration Server.
<b>ISC.88.9173E</b>	<b>Operation can not be found for endpoint reference (EPR) = {0} and soapAction = {1}</b>
<b>Explanation</b>	Integration server could not find the operation in the Web service identified with the specified endpoint reference and SOAP action.
<b>Action</b>	Ensure that the operation with the specified SOAP action is present in the Web service descriptor identified by the endpoint reference.

<b>ISC.88.9357E</b>	<b>You cannot use this service against the specified Web service descriptor because its Pre-8.2 compatibility mode property is set to false.</b>
<b>Explanation</b>	Either pub.soap.utils.resetWSDEffectivePolicy or pub.soap.utils.setWSDEffectivePolicy services were specified with a Web service descriptor with Pre-8.2 compatibility mode property set to false. These services can only be used with Web service descriptors that are running in pre-8.2 compatibility mode (i.e., the Pre-8.2 compatibility mode property is set to true)
<b>Action</b>	Change the Web service descriptor's Pre-8.2 compatibility mode property to true.
<b>ISE.0093.9902E</b>	<b>Error occurred while invoking a service : {0}</b>
<b>Explanation</b>	The Integration Server encountered an internal error while invoking a service. More information about the error is provided in the error message.
<b>Action</b>	Contact Software AG Global Support.
<b>ISE.0093.9903E</b>	<b>Not implemented</b>
<b>Explanation</b>	The Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISE.0093.9904E</b>	<b>Unknown session: {0}</b>
<b>Explanation</b>	The Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISE.0093.9908E</b>	<b>Parameter {0} specified for method is invalid</b>
<b>Explanation</b>	The parameter that you specified is not valid.
<b>Action</b>	Specify a valid parameter.
<b>ISE.0093.9924E</b>	<b>FAILED</b>
<b>Explanation</b>	Integration Server is unable to retrieve the status of Repository Server V2.
<b>Action</b>	Ensure that the port and host information that you specified to retrieve the status of Repository Server V2 is correct.
<b>ISE.0093.9934E</b>	<b>Service {0} doesn't exist or was removed.</b>
<b>Explanation</b>	The service that you are trying to execute does not exist in Integration Server.
<b>Action</b>	Ensure that the service exists in Integration Server.

<b>ISE.0093.9935E</b>	<b>Package {0} doesn't exist or was removed.</b>
<b>Explanation</b>	The package that you are trying to access does not exist or is deleted.
<b>Action</b>	Ensure that the package you want to access exists in the IntegrationServer_directory\packages directory.
<b>ISE.0093.9936E</b>	<b>Port {0} doesn't exist or was removed.</b>
<b>Explanation</b>	The e-mail port that you are trying to access is not configured or enabled.
<b>Action</b>	Ensure that the e-mail port you want to access is configured and enabled.
<b>ISE.0093.9952E</b>	<b>Access was denied to resource {0}</b>
<b>Explanation</b>	The Integration Server encountered an internal error due to resource access.
<b>Action</b>	Contact Software AG Global Support.
<b>ISE.0093.9953E</b>	<b>A Java exception occurred {0}</b>
<b>Explanation</b>	Integration Server encountered an unexpected error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISE.0093.9954E</b>	<b>Resource {0} doesn't exist or was removed.</b>
<b>Explanation</b>	The Integration Server encountered an internal error due to resource access.
<b>Action</b>	Contact Software AG Global Support.
<b>ISKeyStoreBundle.getKeyForJournalLogger(DEFAULT_ILIVE_TRUSTSTORE_CREATION_ERROR)</b>	
<b>– Error: Truststore alias "DEFAULT_INTEGRATION_LIVE_TRUSTSTORE" cannot be created. Details: {0}</b>	
<b>ISP.0000.9101E</b>	<b>Unable to register NTLM Challenge Response Authentication handler</b>
<b>Explanation</b>	A handler was registered and then re-registered without first being unregistered.
<b>Action</b>	Register a handler only once. If you want to re-register a handler, first unregister it.
<b>ISP.0046.0001E</b>	<b>Could not initialize {0} Listener. Invalid port specified: {1}</b>
<b>Explanation</b>	While attempting to initialize a port, Integration Server detected that the port was improperly configured. Specifically, an invalid port number was specified for the port in the server.cnf, ports.cnf, or listeners.cnf file.
<b>Action</b>	Edit the appropriate configuration file and specify a port number from 1 through 65534 that is not already in use.

<b>ISP.0046.0006E</b>	<b>Cannot initialize {0} Listener on port {1}. No socket available.</b>
<b>Explanation</b>	While trying to initialize an HTTP listener, Integration Server determined that the socket associated with the requested port is already in use by another application. As a result, the requested port is unavailable.
<b>Action</b>	Specify a port that is not already in use, or disable the application that is using the requested port.
<b>ISP.0046.0007W</b>	<b>{0} Access denied. Connection disallowed {1}</b>
<b>ISP.0046.0019S</b>	<b>Unable to establish connection to Enterprise Gateway Server {0}:{1}. Exception: {2}.</b>
<b>Explanation</b>	The Internal Server could not establish a connection to Enterprise Gateway Server for the reason indicated.
<b>Action</b>	Ensure that the Enterprise Gateway registration port is enabled.
<b>ISP.0046.0020S</b>	<b>Unable to establish connection to Enterprise Gateway Server {0}:{1}. Internal Server was not authenticated on the Enterprise Gateway.</b>
<b>Explanation</b>	Internal Server authentication failed on the Enterprise Gateway.
<b>Action</b>	Ensure that the registration credentials specified during the creation of the Internal Server port are correct.
<b>ISP.0046.0024E</b>	<b>Unable to establish connection to Enterprise Gateway Server {0}:{1}. Internal Server version {2} does not support Enterprise Gateway version {3}</b>
<b>Explanation</b>	The version of Enterprise Gateway Server must be equal to or higher than the versions of Integration Servers acting as the Internal Server.
<b>Action</b>	Use the same or higher version of Enterprise Gateway Server.
<b>ISP.0046.0025E</b>	<b>Rejected a connection from Internal Server {0} on port {1}. Enterprise Gateway version {2} does not support Internal Server version {3}</b>
<b>Explanation</b>	The version of Enterprise Gateway Server must be equal to or higher than the versions of Integration Servers acting as the Internal Server.
<b>Action</b>	Use the same or higher version of Enterprise Gateway Server.
<b>ISP.0047.0001E</b>	<b>47.1 obsolete</b>
<b>Explanation</b>	While attempting to initialize a port, Integration Server detected that the port was improperly configured. Specifically, an invalid port number was specified for the port in the server.cnf, ports.cnf, or listeners.cnf file.
<b>Action</b>	Edit the appropriate configuration file and specify a port number from 1 through 65534 that is not already in use.

---

ISP.0047.0002	Resuming HTTPS Listener on port {0}
ISP.0047.0003	Starting HTTPS Listener on port {0}
ISP.0047.0005	Stopping HTTPS Listener on port {0}
ISP.0047.0008	Could not start HTTPS Listener on port {0}. No SSL support available.
ISP.0047.0009	Error in SSL setup: {0}
ISP.0047.0010	Certificate Authority was recognized
ISP.0047.0011	Certificate Authority was not recognized {0}
ISP.0047.0012	Client does not have a digital certificate
ISP.0047.0013	Access denied to host {0}
ISP.0047.0014	Error in SSL Setup: {0}
ISP.0047.0015	Error in SSL setup: Not all certificate fingerprints were loaded
ISP.0047.0016	The required client certificate was not provided by {0}
ISP.0047.0017	Could not start HTTPS listener on port {0}
ISP.0047.0018E	Aborting connection from {0}: {1}
<b>Explanation</b>	Integration Server encountered a problem while trying to establish a secure connection with the client at the indicated address.
<b>Action</b>	Make sure the client properly supports SSL connections.

<b>ISP.0047.0019E</b>	<b>SSL listener restricted to 128 bit or better encryption:</b>
<b>Explanation</b>	Integration Server configuration property <code>watt.net.ssl.server.strongcipheronly</code> is set to "true", but the list of ciphers includes weak ciphers. Integration Server displays these weak ciphers in subsequent messages.
<b>Action</b>	Either use only strong ciphers, or set <code>watt.net.ssl.server.strongcipheronly</code> to "false".
<b>ISP.0047.0020E</b>	<b>cipher {0} = {1} ({2} bit)</b>
<b>Explanation</b>	Integration Server configuration property <code>watt.net.ssl.server.strongcipheronly</code> is set to "true", but the list of ciphers includes the weak ciphers displayed by this message.
<b>Action</b>	Either use only strong ciphers, or set <code>watt.net.ssl.server.strongcipheronly</code> to "false".
<b>ISP.0047.0021E</b>	<b>Aborting connection request on {0} port {1}, a certificate map does not exist for {2}</b>
<b>Explanation</b>	A client presented a certificate to Integration Server, but the certificate has not been mapped to a user on Integration Server. For a certificate to be mapped to a user, the certificate must have been previously stored on Integration Server and associated with that user.
<b>Action</b>	Use the Server Administrator interface to import the certificate to Integration Server and map it to the appropriate user.
<b>ISP.0047.0022</b>	<b>Access denied to host: Hostname verification failed. The CN "{0}" in the subject DN of the certificate does not match the hostname "{1}".</b>
<b>ISP.0047.0023</b>	<b>Aborting connection, Server Certificate purpose verification failed</b>
<b>ISP.0047.9998U</b>	<b>Exception --&gt; {0}</b>
<b>Explanation</b>	Integration Server encountered an error. This message contains the exception produced by the server.
<b>Action</b>	Examine the error message to determine the problem.
<b>ISP.0057.0001I</b>	<b>Delete operation completed</b>
<b>ISP.0061.0001</b>	<b>Access denied to remote server {0} for user {1}</b>

---

ISP.0061.0002	Expired remote connection to {0} for user {1}
ISP.0061.0003	Established new remote connection to {0} for user {1}
ISP.0061.0004	Established new remote connection to {0}
ISP.0061.0005	Error expiring remote connection: {0}
ISP.0061.0006	Error expiring remote connection for user {0}: {1}
ISP.0061.0007	Expired remote connection to {0}
ISP.0061.0008	Could not create default Remote Server Alias: {0}
ISP.0061.0009	The default Remote Server Alias was created.
ISP.0068.0001	Successfully logged in as user {0} on host {1}
ISP.0068.0002	Login attempt as user {0} on host {1} failed
ISP.0068.0004	Processed {0} new message(s)
ISP.0068.0005	Error processing email message. {0}.
ISP.0068.0006	EMAIL Access denied. Connection disallowed from host {0}
ISP.0068.0007	EMAIL Access denied. Invalid host in senders address: {0}

- ISP.0068.0008      EMAIL Access denied. Could not figure out senders email address.
- ISP.0068.0009      EMAIL Access denied. User {0} not allowed to run service {1}
- ISP.0068.0010      Could not decode body part of email message
- ISP.0068.0011      Could not decode message body into input parameters
- ISP.0068.0012      Listener key not provided. Not running email listener
- ISP.0068.0013      Error processing service: {0}
- ISP.0068.0014      Could not get message content: {0}
- ISP.0068.0015      Could not get body part of message: {0}
- ISP.0068.0016      Error parsing message: {0}
- ISP.0068.0017      Could not get message UID: {0}
- ISP.0068.0018      Could not start listener threads: {0}
- ISP.0068.0020      Could not get message with uid {0}
- ISP.0068.0021      Could not process message with uid {0}
- ISP.0068.0022      Could not send reply message to {0}. Check email address and smtp settings.

<b>ISP.0068.0023</b>	<b>Received reply message. Not processing</b>
<b>ISP.0068.0024</b>	<b>The connection to the IMAP server {0} for user {1} was temporarily lost. Some messages may not have been processed.</b>
<b>ISP.0068.0025</b>	<b>No content handler for content type {0}. Service {1} called without content handler.</b>
<b>ISP.0068.0026</b>	<b>Content type: {0} Subject: {1}</b>
<b>ISP.0068.0027</b>	<b>{0} lost connection to {1} server {2}</b>
<b>ISP.0068.0028</b>	<b>{0} reconnected to {1} server {2}</b>
<b>ISP.0068.9001E</b>	<b>Skipping processing reply email message</b>
<b>Explanation</b>	The subject line of the e-mail received on the e-mail port starts with "Re:". Hence, it is treated as a reply message and its processing is skipped.
<b>Action</b>	Investigate why the subject line of the e-mail starts with "Re:". Usually, this is an indicator of a reply message.
<b>ISP.0068.9002E</b>	<b>Skipping processing returned email message</b>
<b>Explanation</b>	The subject line of the e-mail received on the e-mail port starts with "Returned". Hence, it is treated as a message that is returned by the recipient and its processing is skipped.
<b>Action</b>	Avoid the error and process the returned messages by setting the extended property "watt.server.email.processReturnedEmails" to true.
<b>ISP.0068.9003E</b>	<b>Invalid service: {0}</b>
<b>Explanation</b>	Integration Server received a message on the e-mail port listener, but the service specified to perform the message processing is invalid. The service that Integration Server selects to execute message processing depends on how the server is configured. Integration Server searches for the value in the locations listed below in order of precedence:
	- The Global Service field on the Email Client Configuration screen on the Server Administrator.
	- The e-mail message from the e-mail client.
	- The Default Service field on the Email Client Configuration screen on the Server Administrator.

The problem is often that the service name is specified in the wrong case (service names are case sensitive). Other causes could be that no service was specified at all or the service is not in its specified location.

**Action** Make sure the service name is specified correctly and exists in the location specified.

**ISP.0068.9004E** **No such service: {0}**

**Explanation** The Integration Server FTP listener encountered an internal error.

**Action** Contact Software AG Global Support.

**ISP.0068.9005E** **Unknown content type: {0}**

**Explanation** The Integration Server does not support the MIME type specified.

**Action** Only use the MIME types supported by the Integration Server.

**ISP.0068.9006E** **Server Error: {0}**

**Explanation** An unexpected error occurred when invoking the service.

**Action** If the exception details provided as part of the message does not give any hint, contact Software AG Global Support.

**ISP.0068.9101E** **Invalid header {0}**

**Explanation** The header specified is invalid.

**Action** Ensure that a valid header is provided. Keep the following points in mind when specifying a header:

1. Header name should not contain spaces.
2. Header value should not be empty.
3. Header name and value should not be the same.

**ISP.0068.9102E** **Invalid TO field: {0}**

**Explanation** Either the recipient e-mail address is not provided in the "to" field or the address provided is invalid.

**Action** Enter a valid e-mail address in the "to" field. Refer to "pub.client:smtp" service in webMethods Integration Server documentation for further details.

---

<b>ISP.0068.9103E</b>	<b>Invalid CC field: {0}</b>
<b>Explanation</b>	The e-mail address entered in the "cc" field is invalid.
<b>Action</b>	Enter a valid e-mail address in the "cc" field. Refer to "pub.client:smtp" service in webMethods Integration Server documentation for further details.
<b>ISP.0068.9104E</b>	<b>Invalid BCC field: {0}</b>
<b>Explanation</b>	The e-mail address entered in the "bcc" field is invalid.
<b>Action</b>	Enter a valid e-mail address in the "bcc" field. Refer to "pub.client:smtp" service in webMethods Integration Server documentation for further details.
<b>ISP.0068.9106E</b>	<b>No filename nor content included in the attachment!</b>
<b>Explanation</b>	Content or filename is not provided in the attachments field.
<b>Action</b>	Provide either the content or the filename in the attachments field. Refer to "pub.client:smtp" service in webMethods Integration Server documentation for further details.
<b>ISP.0068.9108E</b>	<b>charset {0} is not valid</b>
<b>Explanation</b>	Character set encoding specified for the body or attachment is invalid.
<b>Action</b>	Ensure that the Character set encoding specified is valid. Refer to "pub.client:smtp" service in webMethods Integration Server documentation for further details.
<b>ISP.0068.9110E</b>	<b>Invalid MAILHOST field: {0}</b>
<b>Explanation</b>	No value is provided for the mailhost parameter of the pub.client:smtp service.
<b>Action</b>	Provide a valid value for the mailhost parameter of the pub.client:smtp service. Refer to "pub.client:smtp" service in webMethods Integration Server documentation for further details.
<b>ISP.0068.9111E</b>	<b>Invalid Message Recipient: {0}</b>
<b>Explanation</b>	Either the recipient e-mail address is not provided in the "to" field or the address provided is invalid.
<b>Action</b>	Enter a valid e-mail address in the "to" field. Refer to "pub.client:smtp" service in webMethods Integration Server documentation for further details.

ISP.0071.0001	Could not initialize FTP Listener. Invalid port specified: {0}
ISP.0071.0002	Suspending FTP(S) Listener on port {0}
ISP.0071.0003	Can not build data channel, the exception is {0}, the message is {1}
ISP.0071.0004	The port range specified for passive data connections to FTP(S) listeners is invalid: please specify both "watt.net.ftpPassivePort.min" and "watt.net.ftpPassivePort.max" values
ISP.0071.0005	The port range specified for passive data connections to FTP(S) listeners is invalid: "watt.net.ftpPassivePort.min" value is not a number
ISP.0071.0006	The port range specified for passive data connections to FTP(S) listeners is invalid: "watt.net.ftpPassivePort.max" value is not a number
ISP.0071.0007	The port range specified for passive data connections to FTP(S) listeners is invalid: "watt.net.ftpPassivePort.min" and "watt.net.ftpPassivePort.max" values are not within 1-65534 range
ISP.0071.0008	The port range specified for passive data connections to FTP(S) listeners is invalid: "watt.net.ftpPassivePort.min" value is greater than "watt.net.ftpPassivePort.max" value
ISP.0071.0009	All ports within the port range specified for passive data connections to FTP(S) listeners are in use
ISP.0071.0010E	PORT command refused. The PORT address {0} does not match the original host address {1}.
<b>Explanation</b>	In FTP active mode, the PORT command specifying the IP address does not match the client IP address in the control connection. Possible reason for this could be that your FTP client is compromised.
<b>Action</b>	Contact your network security team to take necessary action in case your FTP client is compromised.

---

<b>ISP.0071.0011E</b>	<b>Cannot build data connection: client address {0} does not match the original host address {1}.</b>
<b>Explanation</b>	In FTP passive mode, the client address associated with the control port does not match the client address in the data port connection. Possible reason for this could be that your FTP client is compromised.
<b>Action</b>	Contact your network security team to take necessary actions in case your FTP client is compromised.
<b>ISP.0071.9001E</b>	<b>Cannot build data connection: use PORT or PASV first</b>
<b>Explanation</b>	The Integration Server failed to connect to a port on the FTP client because the FTP client did not provide valid port information.
<b>Action</b>	Check the Integration Server configuration and restart the server. If the problem persists, contact Software AG Global Support.
<b>ISP.0071.9002E</b>	<b>{0}: cannot create</b>
<b>Explanation</b>	An FTP client application connected to an FTP port on the Integration Server and tried to create a remote directory on the FTP server, but the "mkdir" command failed.
<b>Action</b>	Make sure the directory name was specified correctly. Also, examine the remote file system and make sure that you have permission to create the directory there.
<b>ISP.0071.9003E</b>	<b>{0}: cannot delete</b>
<b>Explanation</b>	An FTP client application connected to an FTP port on the Integration Server and tried to delete a file on the FTP server, but the "delete" command failed.
<b>Action</b>	Make sure the file name was specified correctly and that the file exists on the remote server. Also, examine the remote file system and make sure that you have permission to delete the file from the remote file system.
<b>ISP.0071.9004E</b>	<b>Cannot rename File to {0}</b>
<b>Explanation</b>	An FTP client application connected to an FTP port on the Integration Server and tried to rename a file on the FTP server, but the "rename" command failed.
<b>Action</b>	Make sure the old and new file names were specified correctly. Also, examine the remote file system and make sure that you have write permission to both the old and new file names.

<b>ISP.0071.9005U</b>	<b>Unable to make dir {0}</b>
<b>Explanation</b>	An FTP client application connected to an FTP port on the Integration Server and tried to create a remote directory on the FTP server, but the "mkdir" command failed.
<b>Action</b>	Make sure the directory name is specified correctly. Also, examine the remote file system and make sure that you have the appropriate permissions to create the directory there.
<b>ISP.0071.9006U</b>	<b>Unable to delete {0}</b>
<b>Explanation</b>	An FTP client application connected to an FTP port on the Integration Server and tried to delete a file on the FTP server, but the "delete" command failed.
<b>Action</b>	Make sure the file name is specified correctly and that the file exists. Also, examine the remote file system and make sure that you have permission to delete the file.
<b>ISP.0071.9007U</b>	<b>Unable to rename to {0}</b>
<b>Explanation</b>	An FTP client application connected to an FTP port on the Integration Server and tried to rename a file on the FTP server, but the "rename" command failed.
<b>Action</b>	Make sure the old and new file names are specified correctly. Also, examine the remote file system and make sure that you have write permission to both the old and new file names.
<b>ISP.0071.9008E</b>	<b>Cannot write</b>
<b>Explanation</b>	Integration Server failed to put the file in the folder directory. The file must be in the service directory for processing.
<b>Action</b>	Put the file in the service directory.
<b>ISP.0071.9009E</b>	<b>Invalid transaction name. Not in the form 'tid[;mime.type][;encoding]'.</b>
<b>Explanation</b>	The MIME type specified in the FTP request is incorrect. It should be in the form of 'tid[;mime.type][;encoding]'.
<b>Action</b>	Make sure to provide the name in the correct format.
<b>ISP.0071.9010U</b>	<b>Unable to determine mime type</b>
<b>Explanation</b>	Integration Server does not support the MIME type specified.
<b>Action</b>	Only use the MIME types supported by Integration Server. Refer to the webMethods Integration Server documentation for more information.

---

<b>ISP.0071.9011E</b>	<b>Cannot read</b>
<b>Explanation</b>	Ensure that the specified file exists in the FTP server.
<b>Action</b>	The Integration Server failed to read the specified file from the FTP server.
<b>ISP.0071.9012U</b>	<b>No such service: {0}</b>
<b>Explanation</b>	The Integration Server FTP listener encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISP.0071.9013U</b>	<b>Unknown content type: {0}</b>
<b>Explanation</b>	The Integration Server does not support the MIME type specified.
<b>Action</b>	Only use the MIME types supported by the Integration Server. Refer to the webMethods Integration Server documentation for more information.
<b>ISP.0071.9014U</b>	<b>Server Error: {0}</b>
<b>Explanation</b>	The Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISP.0071.9015E</b>	<b>Cannot publish STOR complete event</b>
<b>Explanation</b>	The Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISP.0071.9016E</b>	<b>Cannot build data connection: client address {0} does not match the original host address {1}.</b>
<b>Explanation</b>	In FTP passive mode, the client address associated with the control port does not match the client address in the data port connection. Possible reason for this could be that your FTP client is compromised.
<b>Action</b>	Contact your network security team to take necessary action in case your FTP client is compromised.
<b>ISP.0085.9001E</b>	<b>Issuer DN must be provided</b>
<b>Explanation</b>	The certificate is incomplete. It must include an Issuer DN.
<b>Action</b>	Supply a certificate that includes an Issuer DN.

<b>ISP.0085.9002E</b>	<b>Serial number must be provided</b>
<b>Explanation</b>	The certificate is incomplete. It must contain a serial number.
<b>Action</b>	Supply a certificate that includes a serial number.
<b>ISP.0085.9004E</b>	<b>data provided for certificate not in expected format</b>
<b>Explanation</b>	Only X509Certificates may be used to identify Integration Server clients.
<b>Action</b>	Supply a valid X509Certificate.
<b>ISP.0085.9005E</b>	<b>No map entry exists for the specified information</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISP.0085.9006E</b>	<b>Certificate's file name is required</b>
<b>Explanation</b>	Certificate Path is empty.
<b>Action</b>	Supply the fully qualified file name for a certificate file.
<b>ISP.0085.9007E</b>	<b>Specified certificate file does not exist</b>
<b>Explanation</b>	The Certificate Path field refers to a non-existent file.
<b>Action</b>	Supply the fully qualified file name of a certificate file.
<b>ISP.0085.9008E</b>	<b>Specified certificate file is empty</b>
<b>Explanation</b>	The Certificate Path field refers to an empty file.
<b>Action</b>	Supply the fully qualified file name of a certificate file.
<b>ISP.0085.9009E</b>	<b>Attempted to update a non-existent entry</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISP.0085.9010E</b>	<b>{0} is not a valid user</b>
<b>Explanation</b>	The supplied user name does not identify a user on this Integration Server.
<b>Action</b>	Supply a valid user.

---

<b>ISP.0085.9011E</b>	<b>Missing input for the parameter 'oldName'</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISP.0085.9012E</b>	<b>No service/Document Type exist for: {0}</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISP.0085.9013E</b>	<b>Missing input for the parameter 'newName'</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISP.0085.9014E</b>	<b>Not a Document Type: {0}</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISP.0085.9015E</b>	<b>Not a flow service: {0}</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISP.0085.9016E</b>	<b>Missing input parameter: path</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISP.0085.9017E</b>	<b>No input for the parameter {0}</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISP.0085.9018E</b>	<b>Specified node {0} not found</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Contact Software AG Global Support.

ISP.0085.9019	Missing required parameter: 'fileName'
ISP.0085.9020	Missing required parameter: 'pipeline'
ISP.0085.9030	No such folder: {0}
ISP.0085.9032	Invalid folder type: {0}
ISP.0085.9033	Provided folder name is null
ISP.0085.9034	Provided source is null
ISP.0085.9035	Provided package name is null
ISP.0085.9038	No such folder: {0}
ISP.0085.9041U	No such service: {0}
<b>Explanation</b>	Integration Server FTP listener encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
ISP.0085.9043	Must specify either Specification or Signature
ISP.0085.9047	Failed to register {0}
ISP.0085.9050	no such service {0}
ISP.0085.9051	service {0} is not a Java IM

---

ISP.0085.9052	<b>node is missing a name</b>
ISP.0085.9053E	<b>invalid package</b>
<b>Explanation</b>	An application tried to delete a service, but the package specified does not exist on the Integration Server.
<b>Action</b>	Examine the service input and verify that a valid package name is specified.
ISP.0085.9054	<b>Node name was not provided</b>
ISP.0085.9055	<b>Node {0} does not exist</b>
ISP.0085.9057	<b>Target name was not provided</b>
ISP.0085.9059	<b>Target package does not exist. Create it first</b>
ISP.0085.9060	<b>IOException occurred file={0}: {1}</b>
ISP.0085.9061	<b>Similarly-named node already in use</b>
ISP.0085.9062E	<b>Package name was not provided</b>
<b>Explanation</b>	An application tried to export a package, but the package name was not provided.
<b>Action</b>	Examine the service input make sure it provides a valid package name.
ISP.0085.9063	<b>{0} package does not exist</b>
ISP.0085.9064	<b>Node directory does not exist</b>
ISP.0085.9065	<b>IOException occurred creating zip for {0} node</b>

ISP.0085.9066	<b>{0} package not found</b>
ISP.0085.9067	<b>{0} package directory not found</b>
ISP.0085.9068	<b>IOException occurred creating zip for {0} package</b>
ISP.0085.9074	<b>no such class {0}</b>
ISP.0085.9075	<b>Package {0} is not enabled</b>
ISP.0085.9076	<b>class not in package</b>
ISP.0085.9077	<b>node is not in a package</b>
ISP.0085.9078E	<b>node belongs to invalid package</b>
<b>Explanation</b>	An application tried to create a service, but the package name specified to contain the service was missing or invalid.
<b>Action</b>	Examine the service input and make sure a valid package name is provided.
ISP.0085.9079E	<b>not a valid folder name</b>
<b>Explanation</b>	An application tried to create a new service, but the folder name was missing or invalid.
<b>Action</b>	Examine the service input and verify that a valid folder name is provided.
ISP.0085.9080	<b>node name already in use</b>
ISP.0085.9081	<b>folder node "{0}" in path "{1}" doesn't exist</b>
ISP.0085.9082	<b>folder node "{0}" exists in package</b>

---

ISP.0085.9083	<b>unsupported node type: {0}</b>
ISP.0085.9084	<b>Unable to lock: {0}. It has been locked by user {1}.</b>
ISP.0085.9085	<b>Unable to modify; node {0} is locked by another user.</b>
ISP.0085.9086	<b>Unable to perform the required operation. The destination folder has locked services which share a common Java source file.</b>
ISP.0085.9087	<b>Required parameter 'package' is missing</b>
ISP.0085.9088E	<b>Invalid package version {0}, the accepted format is #.#.#.###</b>
<b>Explanation</b>	The supplied package version is an invalid version number. The correct format is "x.y" or "x.y.z" (x, y, z all must be digits from 0-9, e.g. 2.0, 4.0.1 etc.).
<b>Action</b>	Examine the service input and make sure a valid package version is provided.
ISP.0085.9089E	<b>Not allowed to add unknown package(s) {0} to dependency list</b>
<b>Explanation</b>	The package that was added to another package's dependency list does not exist on Integration Server.
<b>Action</b>	Specify the package name again, this time specifying a package that exists on Integration Server and is enabled.
ISP.0085.9093	<b>Port must be numeric</b>
ISP.0085.9094E	<b>Invalid Folder/Service Name</b>
<b>Explanation</b>	The service, folder, or provider Web service descriptor that was added to a port's access list does not exist on Integration Server.
<b>Action</b>	Enter the name of the service, folder, or Web service descriptor again, making sure to specify one that exists on Integration Server.
ISP.0085.9095	<b>Unable to add service to this port</b>

<b>ISP.0085.9100E</b>	<b>No password specified</b>
<b>Explanation</b>	The alias created for a remote server omitted the remote server's password.
<b>Action</b>	Enter a valid password in the password field.
<b>ISP.0085.9101E</b>	<b>Missing one or more required parameters: \$alias, \$service</b>
<b>Explanation</b>	The pub.remote:invoke service failed to execute because one or both of the required "\$alias" or "\$service" parameters were not supplied.
<b>Action</b>	Examine the service input and ensure that both the parameters are specified.
<b>ISP.0085.9102E</b>	<b>No such remote server: {0}</b>
<b>Explanation</b>	The pub.remote:invoke service failed to execute because an invalid server alias was provided.
<b>Action</b>	From the Settings>Remote Servers page of the Server Administrator examine the Remote Servers List and make sure an alias exists for the remote server. If not, create one before invoking the pub.remote:invoke service again.
<b>ISP.0085.9103E</b>	<b>User session required to invoke a protected remote server</b>
<b>Explanation</b>	Integration Server encountered a serious internal error because the user session object that invokes the service on the remote server is null.
<b>Action</b>	Contact Software AG Global Support.
<b>ISP.0085.9104E</b>	<b>Access denied to invoke on remote server {0}</b>
<b>Explanation</b>	The pub.remote:invoke service failed to invoke the service on the remote server because the current user does not have the proper ACL.
<b>Action</b>	Using the Integration Server Administrator, examine the remote server alias properties as well as the service's Execute ACL setting on the remote server. Make sure that the current user has the proper ACL to invoke the service.
<b>ISP.0085.9105E</b>	<b>User session required to invoke a remote server with SESSION scope</b>
<b>Explanation</b>	Integration Server encountered a serious internal error because the user session object that invokes the service on the remote server is null.
<b>Action</b>	Contact Software AG Global Support.

---

ISP.0085.9106	<b>Missing required parameter: \$jobID</b>
ISP.0085.9108	<b>No such job: {0}</b>
ISP.0085.9110	<b>No such service is currently loaded {0}</b>
ISP.0085.9113E	<b>Invalid Date format.Date must be in YYYY/MM/DD format.</b>
<b>Explanation</b>	When attempting to schedule a one-time task, an invalid date or time format was specified.
<b>Action</b>	Enter the date and/or time again, this time using the correct format.
ISP.0085.9114	<b>You specified a date/time in the past</b>
ISP.0085.9115	<b>Invalid Time format.Time must be in HH:MM:SS format</b>
ISP.0085.9116E	<b>Interval must be a positive integer {0}</b>
<b>Explanation</b>	A repeating task could not be scheduled because the specified interval is not valid.
<b>Action</b>	Specify the interval again, this time specifying a positive integer.
ISP.0085.9117E	<b>Invalid task type: {0}</b>
<b>Explanation</b>	The WmRoot service wm.server.schedule:createUserTask failed to execute because an invalid task type was supplied. Valid task types are: "once", "repeat", and "complex".
<b>Action</b>	Examine the service input and ensure that the "type" parameter specifies a valid task type.
ISP.0085.9118	<b>Unknown service type: {0}</b>
ISP.0085.9119	<b>{0} is missing or package is disabled</b>
ISP.0085.9120	<b>Templates directory for package {0} could not be created</b>

- ISP.0085.9121**      **Template file exists but is not writable**
- ISP.0085.9123U**      **nobody to send message to**  
**Explanation**      Integration Server failed to invoke a service on the remote server using the e-mail port because the "to" parameter was not supplied.  
**Action**              Examine the logic to make sure that it passes the correct input to the "to" parameter when invoking services remotely using the e-mail listener.
- ISP.0085.9124U**      **no attachment**  
**Explanation**      Integration Server failed to invoke a service on the remote server using the e-mail port because the "attachments" parameter was not supplied.  
**Action**              Examine the logic to make sure that it passes the correct input to the "attachments" parameter when invoking services remotely using the e-mail listener.
- ISP.0085.9125U**      **attachments must be of type Values[]**  
**Explanation**      Integration Server failed to invoke a service on the remote server using the e-mail port because the input for the "attachments" parameter was not of Values[] type.  
**Action**              Examine the logic to make sure that it passes the correct Values[] input to the "attachments" parameter when invoking services remotely using the e-mail listener.
- ISP.0085.9126E**      **Invalid attachment file {0}**  
**Explanation**      Integration Server failed to invoke a service on the remote server using the e-mail port because the file attachment specified in the "filename" parameter does not exist in the system.  
**Action**              Examine the logic to make sure that it passes a valid file to the "filename" parameter and make sure that it exists in the file system.
- ISP.0085.9127**      **No filename nor content included in the attachment!**
- ISP.0085.9129**      **An error was encountered removing {0}**
- ISP.0085.9131E**      **Not allowed to add empty package version, the accepted format is \*.\***  
**Explanation**      The package dependency list does not specify a version for the package.  
**Action**              Enter a valid package version in the format "x.y" or "x.y.z" (x, y, z all must be digits from 0-9, e.g. 2.0, 4.0.1 etc.).

---

ISP.0085.9132	<b>Unable to perform operation. {0} has entities locked by another user. Please unlock these entities before performing this operation</b>
ISP.0085.9133	<b>A required parameter {0} was not supplied</b>
ISP.0085.9135	<b>The Universal Name {0} is already defined for {1} in the registry</b>
ISP.0085.9136	<b>The Universal Name {0} is already defined as a Service or Document</b>
ISP.0085.9139E	<b>Cannot {0} changes because the file(s) representing {1} may have been changed to 'Read-Only'. To {0} changes, change the following file(s) from 'Read-Only' to 'Read/Write' either manually or through a source control system: {2}</b>
<b>Explanation</b>	Integration Server could not compile the Java or C service, possibly because the files have changed to Read-Only.
<b>Action</b>	Examine the file permissions and change the file permission from Read-Only to Read/Write, either manually or through a source control system.
ISP.0085.9140	<b>Unable to lock: {0}. It might be locked by another user.</b>
ISP.0085.9141E	<b>The Universal Name {0} contains an invalid character</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Contact Software AG Global Support.
ISP.0085.9145E	<b>Invalid input</b>
<b>Explanation</b>	A WmRoot service failed to execute because the service input is not of the type required by the service.
<b>Action</b>	Examine the error stack trace to determine the exception that was thrown and the service that threw it. For example, the service may require an IData object, but the supplied input was not an instance of IData.
ISP.0085.9146	<b>Cannot schedule service. Input has unsupported datatypes</b>

<b>ISP.0085.9147E</b>	<b>Missing required parameter: 'header'</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact wSoftware AG Global Support.
<b>ISP.0085.9148E</b>	<b>'header' must be of type IData</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISP.0085.9149</b>	<b>Cannot perform operation without Read ACL privileges on {0}</b>
<b>ISP.0085.9150</b>	<b>Cannot perform operation without List ACL on package {0}</b>
<b>ISP.0085.9151</b>	<b>Cannot set Execute ACL {1} on {0}. You do not have permission to access the {1} ACL.</b>
<b>ISP.0085.9152</b>	<b>Cannot set List ACL {1} on {0}. You do not have permission to access the {1} ACL.</b>
<b>ISP.0085.9153</b>	<b>Cannot set Read ACL {1} on {0}. You do not have permission to access the {1} ACL.</b>
<b>ISP.0085.9154</b>	<b>Cannot set Write ACL {1} on {0}. You do not have permission to access the {1} ACL.</b>
<b>ISP.0085.9155</b>	<b>Cannot set List ACL {1} on package {0}. You do not have permission to access the {1} ACL.</b>
<b>ISP.0085.9156E</b>	<b>Cannot perform operation without List ACL privileges on {0}</b>
<b>Explanation</b>	You do not have List access to the element that you tried to lock for editing or the service you attempted to view.
<b>Action</b>	Contact the Administrator of the Integration Server to request List ACL permission for the service or element.
<b>ISP.0085.9157</b>	<b>Cannot perform operation without Write ACL privileges on {0}</b>

---

ISP.0085.9158	<b>Required parameter "{0}" is missing in invoke of {1}</b>
ISP.0085.9159	<b>Invalid input. "{0}" is a required parameter of type IData</b>
ISP.0085.9160	<b>Invalid input. "{0}" is a required parameter of type String</b>
ISP.0085.9161	<b>Invalid input. "{0}" must be of type String</b>
ISP.0085.9162	<b>Invalid input. "{0}" must be a positive integer</b>
ISP.0085.9163	<b>Invalid input. "{0}" must be true or false</b>
ISP.0085.9164	<b>Folder {0} not found</b>
ISP.0085.9165	<b>Unable perform the operation because Broker reports: {0}</b>
ISP.0085.9166E	<b>Not a valid condition type</b>
<b>Explanation</b>	An invalid condition type was provided. The condition type must be "simple" or "join."
<b>Action</b>	Examine the service input and ensure that the condition type provided is "simple" or "join."
ISP.0085.9167E	<b>Not a valid trigger name. Trigger name must be of type String</b>
<b>Explanation</b>	An invalid trigger name was provided. The trigger name must be of type String.
<b>Action</b>	Examine the service input and ensure that the trigger name is of type String.
ISP.0085.9168	<b>Specified trigger name does not exist: {0}</b>
ISP.0085.9169	<b>Could not validate data corresponding to publishable document: {0}</b>

ISP.0085.9170	<b>Trigger condition not satisfied by this document: {0}</b>
ISP.0085.9171E	<b>Not a valid condition name. Condition name must be of type String</b>
<b>Explanation</b>	During a trigger test, Integration Server encountered an invalid condition name. The condition name must be of type String.
<b>Action</b>	Examine the service input and ensure that the condition name is of type String.
ISP.0085.9172E	<b>Specified condition name does not exist: {0}</b>
ISP.0085.9173	<b>Trigger condition not satisfied. All documents must be submitted incase of "AND" join type</b>
ISP.0085.9174	<b>Package "{0}" does not exist.</b>
ISP.0085.9175	<b>Trigger condition "{0}" does not have a service</b>
ISP.0085.9176	<b>Trigger condition "{0}" does not have a document type; A trigger condition must have at least one document type</b>
<b>Explanation</b>	To be considered valid, a trigger condition must identify at least one document type.
<b>Action</b>	Edit the trigger condition to specify a document type.
ISP.0085.9177	<b>"{0}" does not exist or it is not a service</b>
ISP.0085.9178	<b>Document type "{0}" does not exist</b>
ISP.0085.9179	<b>"{0}" is not a publishable document type.</b>
ISP.0085.9184	<b>Node "{0}" is not writable.</b>
ISP.0085.9185	<b>Invalid filter "{0}" for document type "{1}": {2}</b>

ISP.0085.9186	Multiple join conditions are not allowed in a single trigger.
ISP.0085.9187	Could not copy folder completely: {0}
ISP.0085.9188	Could not delete folder completely: {0}
ISP.0085.9189	Could not move folder completely: {0}
ISP.0085.9200	Reference(s) for "{0}" could not be automatically updated, because the element(s) are currently locked.
ISP.0085.9201	Internal reference(s) could not be automatically updated.
ISP.0085.9202	Target node "{0}" already exists.
ISP.0085.9203	Errors occurred while updating remote aliases ({0} of {1} updates failed). See server logs for more details.
ISP.0085.9204	Local update failed: {0} (Note: The cluster synchronization will not run until all local errors are resolved.)
ISP.0085.9205	Password input is required
ISP.0085.9206	Password input must be WmSecureString
ISP.0085.9207	Old password input is required
ISP.0085.9208	New password input is required

ISP.0085.9210	Host Name not specified
ISP.0085.9211	No WSDL specified: wsdlURL or wsdlString input is required
ISP.0085.9212	Provided package name is null
ISP.0085.9213	Provided name is null
ISP.0085.9215	Invalid SOAPBinding found: {0}
ISP.0085.9216	Cannot schedule service. Error is : {0}
ISP.0085.9217	Cannot schedule service. Please contact your System Administrator
ISP.0085.9218	The Lateness Action option that you have selected is invalid for this Schedule Type
ISP.0085.9219	This One time task was suspended since it was overdue. It cannot be resumed
ISP.0085.9220	The lateness time that you have selected is invalid for this Lateness Action. Overdue time must be 0 minutes for 'Run the task immediately' Overdue option and must be greater than 0 minutes for 'Suspend and wait for administrator action' and 'Skip and run at next scheduled time' Overdue options.
ISP.0085.9232	No such user present: {0}
ISP.0085.9233	Cannot update child task
ISP.0085.9235	Interval time is greater than or equal to the difference between the start time and end time.

---

ISP.0085.9258	<b>Web Services Descriptor name not specified, or Web Services Descriptor not found</b>
ISP.0085.9259	<b>Web Services Descriptor is not a Consumer, no WSConnectors exist.</b>
ISP.0085.9260	<b>Web Services Connector {0} was not deleted. Reason= {1}.</b>
ISP.0085.9261	<b>Implicit and Explicit Universal names of the node are identical. The Universal name is registered for the node {1}</b>
ISP.0085.9263E	<b>Unable to get information for user/certificate mapping: {0}</b>
<b>Explanation</b>	An error was encountered while getting details for a certificate. The error may have occurred while reading from the database or while constructing an X509Certificate object. See the error message for details.
<b>Action</b>	If it is a database error, go to the Settings > JDBC Pools page and use the Test button for the ISInternal functional alias to verify that you can still connect to the database. If you can, it may have been a transient error. Try displaying or importing this certificate again. If you cannot, contact your DBA to troubleshoot your database connection problem. If it is not a database error, contact Software AG Global Support.
ISP.0085.9264	<b>Cannot resume the task as the User {0} is disabled.</b>
ISP.0085.9265	<b>Cannot resume the task as the User {0} is removed.</b>
ISP.0085.9268E	<b>A positive integer must be provided for the port</b>
ISP.0085.9269	<b>User Name for Transport not specified</b>
ISP.0085.9270	<b>User Name for WS Security not specified</b>
ISP.0085.9273	<b>URL must begin with "http:" or "https:"</b>

ISP.0085.9274	HTTP method is null
ISP.0085.9275	only use one of: data.stream, data.bytes or data.mimeStream on a POST
ISP.0085.9276	do not use: data.stream, data.bytes or data.mimeStream on a GET
ISP.0085.9277	Invalid private key provided
ISP.0085.9278	Invalid certificate chain provided
ISP.0085.9279	Invalid partner certificate provided
ISP.0085.9280	invalid HTTP method: {0}
ISP.0085.9281	Http Error: {0} - {1}
ISP.0085.9282	Unable to modify; node {0} is system locked.
ISP.0085.9284	Invalid Date or Time.
ISP.0085.9285	Found unresolved dependent services: {0}
ISP.0085.9289	Remote Invoke not licensed.
ISP.0085.9290	Transport Type not specified
ISP.0085.9291	<b>Binding with style="rpc" and use="encoded" is not supported for SOAP version 1.2. Binding {0} ignored.</b>
<b>Explanation</b>	Integration Server does not support RPC/Encoded for SOAP version 1.2. Integration Server ignores bindings that specify this style/use.
<b>Action</b>	No action is required.

---

ISP.0085.9292	Bindings or operations with mixed "use" are not supported
ISP.0085.9293	Host Name must be ASCII characters
ISP.0085.9294	User Name for Transport must be ASCII characters
ISP.0085.9295	Password for Transport must be ASCII characters
ISP.0085.9296	User Name for WS Security must be ASCII characters
ISP.0085.9297	Password for WS Security must be ASCII characters
ISP.0085.9299W	Binding with style="document" and use="encoded" is not supported. Binding {0} ignored.
ISP.0085.9300	The HTTP URL alias "{0}" is already registered for the path: {1}
ISP.0085.9301	A required parameter {0} was not supplied
ISP.0085.9302	No valid bindings found in the WSDL.
ISP.0085.9303	No Valid services found in the WSDL. The WsConnector may not work until a valid _url is given as input.
ISP.0085.9304	HSM based Keystore is not supported
ISP.0085.9305	Unsupported ExtensibleElement "{0}" found in Operation "{1}" and SOAPBinding "{2}"

ISP.0085.9306 SOAP Action "{0}" already found in Operation "{1}" and Binding "{2}". SOAP Action must be unique for Operation and or Binding for a specified SOAP Version.

ISP.0085.9307 "{0}" is not a valid HTTP URL Alias name. "{1}" leading character prohibited.

ISP.0085.9308 "{0}" is not a valid HTTP URL Alias target path. "{1}" leading character prohibited.

ISP.0085.9309 "{0}" is not a valid HTTP URL Alias name. "{1}" character prohibited.

ISP.0085.9310 "{0}" is not a valid HTTP URL Alias target path. "{1}" character prohibited.

ISP.0085.9311 "{0}" is not a valid HTTP URL Alias name. Space character prohibited.

ISP.0085.9312 "{0}" is not a valid HTTP URL Alias target path. Space character prohibited.

ISP.0085.9313 "{0}" is not a valid alias name. HTTP URL Alias must not start with "{1}".

ISP.0085.9314 "{0}" is not a valid HTTP URL Alias target path. URL path must not start with "{1}".

ISP.0085.9343E **Deployment activation for deployment ID {0} failed with an exception. For more information, see the Integration Server logs.**

**Explanation** The deployment was not activated due to the reason specified in the Integration Server logs.

**Action** See the Integration Server logs for more information.

ISP.0085.9344E **Artifact delivery for deployment ID {0} failed with an exception. For more information, see the Integration Server logs.**

**Explanation** The artifacts relating to the specified deployment ID were not delivered due to the reason specified in the Integration Server logs.

**Action** See the Integration Server logs for more information.

---

<b>ISP.0085.9345E</b>	<b>Deletion of artifacts delivered for deployment ID {0} failed with an exception. For more information, see the Integration Server logs.</b>
<b>Explanation</b>	The artifacts relating to the specified deployment ID were not deleted due to the reason specified in the Integration Server log.
<b>Action</b>	See the Integration Server logs for more information.
<b>ISP.0085.9346E</b>	<b>The deletion of artifacts for checkpoint ID {0} failed with an exception. For more information, see the Integration Server logs.</b>
<b>Explanation</b>	The artifacts associated with the specified checkpoint ID could not be deleted due to the reason specified in the Integration Server log.
<b>Action</b>	Check the Integration Server log for details.
<b>ISP.0085.9364I</b>	<b>There are no assets for the specified checkpoint ID: {0}. Deployer cannot activate checkpoint.</b>
<b>ISP.0085.9365E</b>	<b>Extraction of assets for checkpoint ID {0} failed for the composite {1}. For more information, see the Integration Server logs.</b>
<b>Explanation</b>	Assets for the specified checkpoint ID could not be extracted due to the reason specified in the Integration Server log.
<b>Action</b>	Check the Integration Server log for details.
<b>ISP.0085.9370I</b>	<b>There are no assets for the specified deployment ID: {0}. Deployer cannot activate deployment.</b>
<b>ISP.0085.9372E</b>	<b>Checkpoint operation for the checkpoint ID {0} was not successful. For more information, see the Integration Server logs.</b>
<b>Explanation</b>	The checkpoint operation failed due to the reason specified in the Integration Server log.
<b>Action</b>	Check the Integration Server log for details.
<b>ISP.0085.9375E</b>	<b>Checkpoint activation for the checkpoint ID {0} was not successful. For more information, see the Integration Server logs.</b>
<b>Explanation</b>	The checkpoint could not be created due to the reason specified in the Integration Server log.
<b>Action</b>	Check the Integration Server log for details.

**ISP.0085.9376E**      **Checkpoint activation for the checkpoint ID {0} failed with an exception. For more information, see the Integration Server logs.**

**Explanation**      The checkpoint activation failed due to the reason specified in the Integration Server logs.

**Action**              See the Integration Server logs for more information.

**ISP.0085.9384E**      **Missing required parameter: {0}**

**Explanation**      A required parameter was not supplied.

**Action**              Supply a value for the missing parameter and execute the service again.

**ISP.0090.0006**      **recursive IData reference key:'{0}'**

**ISP.0090.0007**      **{0} recursive IDataCodable reference key:'{1}'**

**ISP.0091.0001**      **{0} in {1} minutes or as soon as idle**

**ISP.0091.0002**      **Pending shutdown/restart request has been canceled**

**ISP.0091.0003**      **Grace period has expired. Server is shutting down.**

**ISP.0091.0004**      **Grace period has expired. Server is restarting.**

**ISP.0108.0008W**      **Encryption and Signing key pairs have been updated: {0}**

**Explanation**      The encryption certificate in the user's profile is not synchronized with the one in the JNDI directory. In this case, the signing and encryption key pairs are updated and this warning message is displayed.

**Action**              Ensure that the encryption certificates are synchronized with those available in the JNDI directory.

**ISP.0108.0009W**      **Could not check profile "{0}" for key pair update: {1}**

**Explanation**      When the encryption certificates in the user's profile are not synchronized with those available in the JNDI directory, the signing and encryption key pairs are updated. This warning message is displayed when there are errors when accessing the LDAP directory while updating the key value pairs.

**Action**              Contact Software AG Global Support.

---

<b>ISP.0147.0006E</b>	<b>Error while closing sftp session: Details: {0}</b>
<b>Explanation</b>	The session key that you specified has expired.
<b>Action</b>	Ensure that the session corresponding to this session key exists and has not expired.
<b>ISP.0147.0007E</b>	<b>Error in sftp session sweeper thread. Details: {0}</b>
<b>Explanation</b>	Integration Server encountered an error in the SFTP session sweeper thread.
<b>Action</b>	Read through the details provided in the error message and take corrective steps.
<b>ISS.0001.0001</b>	<b>All licenses have been consumed.</b>
<b>ISS.0001.0002</b>	<b>{0} License key expired or invalid.</b>
<b>ISS.0001.0003</b>	<b>{0} License will expire in {1} days.</b>
<b>ISS.0001.0004</b>	<b>Integration Server will shutdown in 30 minutes, unless a valid license key is provided.</b>
<b>ISS.0001.0005</b>	<b>Unable to load package {0} due to invalid license for package {1}.</b>
<b>ISS.0001.0006</b>	<b>Could not add {0} as dependent package due to invalid license.</b>
<b>ISS.0001.0007</b>	<b>Could not load {0} because one of the dependent package is not loaded.</b>
<b>ISS.0001.0008</b>	<b>{0} Functionality disabled due to license restrictions.</b>
<b>ISS.0001.0009</b>	<b>License key file is read-only. License settings cannot take effect until you make the file read/write.</b>
<b>ISS.0001.0010</b>	<b>The license key is not valid with this version of Integration Server. License key is version {0} and Integration Server is version {1}.</b>

<b>ISS.0001.0011U</b>	<b>The Integration Server is not licensed by the current license key.</b>
<b>Explanation</b>	Integration Server has reached its client limit. Your license for Integration Server allows only a certain number of sessions to be used at a time. Integration Server issues this message when the number of users trying to use the server exceeds the number specified in the license.
<b>Action</b>	Check the number of licensed sessions specified in your Integration Server license. Consider upgrading the license to obtain more user "seats" if the number of users requiring access to your Integration Server has increased.
<b>ISS.0002.0002E</b>	<b>Error loading LDAP settings: {0}</b>
<b>Explanation</b>	Integration Server encountered an IOException while reading the ldap.cnf file.
<b>Action</b>	Check to make sure that the operating system user that is running Integration Server has permission to read and write to the ldap.cnf file. In addition, make sure that the ldap.cnf file is a valid XML file and has not been corrupted in some way. As a last resort, delete the ldap.cnf file and reconfigure the LDAP settings from the Server Administrator.
<b>ISS.0002.0003E</b>	<b>Error saving LDAP settings: {0}</b>
<b>Explanation</b>	An IOException occurred while Integration Server was writing the ldap.cnf file.
<b>Action</b>	Check to make sure that the operating system user that is running Integration Server has permission to read and write to the ldap.cnf file and to the server config directory. In addition, make sure that there is sufficient disk space and quota space for creating and writing a new file.
<b>ISS.0002.0005W</b>	<b>LDAP User Manager enabled, but no LDAP directories are configured</b>
<b>Explanation</b>	The Integration Server is attempting to perform operations that require a connection to an LDAP server, but the Integration Server is only partially configured to use LDAP. Specifically, the configuration does not include a list of LDAP directories to which the Integration Server can connect.
<b>Action</b>	Use the Integration Server Administrator to configure the Integration Server to connect to one or more LDAP directories. For more information about working with LDAP, refer to the webMethods Integration Server documentation.
<b>ISS.0002.0007W</b>	<b>Query returned multiple DN's for a single user with filter ({0}={1})</b>
<b>Explanation</b>	The values specified in the Query DN field on the LDAP directory settings screen are not sufficient to uniquely identify a user. Integration Server uses this field to build a query to send to the LDAP server so that the LDAP server can authenticate the user.
<b>Action</b>	Make sure that the user root, user property, and user names specified on the Query DN field are not ambiguous.

---

<b>ISS.0002.0008E</b>	<b>Could not get a connection from the pool in the time allowed</b>
<b>Explanation</b>	Integration Server was unable to connect to the LDAP server because the request to obtain a connection timed out. This error can occur if the LDAP directory server is slow, is under high load, or is experiencing high latency, and there are insufficient connections in the connection pool to meet demand.
<b>Action</b>	This error is probably transient. It is usually sufficient to wait a few seconds and try the operation again (for example logging in, executing a service) when the load has decreased and resources have become available. If the problem persists, then from the LDAP Directory Settings page of the Server Administrator, try increasing the size of the LDAP connection pool. Also check to make sure the LDAP directory server is properly configured and that the network is able to handle the load being placed on it by the application.
<b>ISS.0002.0009E</b>	<b>Unable to open a connection to {0}</b>
<b>Explanation</b>	The Integration Server was unable to open a connection to the indicated LDAP directory server.
<b>Action</b>	To resolve this issue, do the following: <ul style="list-style-type: none"><li>- Make sure the LDAP server is running and that the Integration Server has permission to connect to it.</li><li>- Make sure that the connection parameters specified on the LDAP Settings screen of the Server Administrator are properly configured.</li><li>- If you are using SSL, make sure that the directory URL specified on the LDAP Settings screen specifies an SSL port on the LDAP server and that both the Integration Server and LDAP server support SSL.</li><li>- If you are specifying credentials, make sure the principal specified on the LDAP Settings screen of the Server Administrator is correct and that the password matches. This error can also occur if the Integration Server cannot establish a connection to the LDAP server within the configured time limit because of a problem such as network latency. For more information about connecting the Integration Server to an LDAP server, see the webMethods Integration Server documentation.</li></ul>
<b>ISS.0002.0010E</b>	<b>Error querying for user {0}: {1}</b>
<b>Explanation</b>	During a user log in, the Integration Server encountered an error while performing a query to obtain the user's Distinguished Name.
<b>Action</b>	In the Server Administrator, on the LDAP Settings screen for the LDAP directory, ensure that the user root and user properties are set correctly.

<b>ISS.0002.0013W</b>	<b>Found group {0}, but it contained no attribute {1}</b>
<b>Explanation</b>	During ACL mapping, Integration Server determined that the value specified in the group attribute field does match the attribute values of the group that Integration Server found.
<b>Action</b>	Make sure the group name attribute field contains a valid group name attribute.
<b>ISS.0002.0014E</b>	<b>Error querying for groups on {0} with root {1} and filter {2}: {3}</b>
<b>Explanation</b>	Integration Server encountered an error when looking for LDAP groups to map to an Integration Server ACL.
<b>Action</b>	If the text of the exception indicates a connection issue, try performing the mapping later. Otherwise, check the values specified for group name, filter, and group name attribute on the Map Groups to ACLs screen.
<b>ISS.0002.0015E</b>	<b>Unable to create ACL mapping: LDAP User Manager not initialized</b>
<b>Explanation</b>	An attempt to map an LDAP group to an ACL failed because the LDAP User Manager function of the Integration Server is not running. This error occurs when one user disables LDAP while another user is trying to perform ACL mapping.
<b>Action</b>	Use the Integration Server Administrator to check the External User Management Configuration screens for possible configuration problems. In addition, try checking the server and error logs for messages about problems with the LDAP manager. For information about using the Integration Server with an external directory, refer to the webMethods Integration Server documentation.
<b>ISS.0002.0016E</b>	<b>Unable to create ACL mapping: ACL {0} not found</b>
<b>Explanation</b>	An attempt to map an LDAP group to an ACL failed because the ACL specified on the Map Groups to ACLs screen does not exist. This error occurs if one user deletes the ACL in question when another user is trying to map an LDAP group to it.
<b>Action</b>	Determine why the other user changed the Integration Server configuration then reconfigure the Integration Server to use LDAP, if appropriate. For information about using the Integration Server with an external directory, refer to the webMethods Integration Server documentation.
<b>ISS.0002.0017E</b>	<b>Unable to retrieve password for handle {0}: {1}</b>
<b>Explanation</b>	The Integration Server is trying to connect to an LDAP server. As part of connecting, the Integration Server needs to send a password to the LDAP server. This error occurs when the Integration Server cannot find the password it stored for this purpose. A likely cause is that the ldap.cnf file was moved from one system to another, but the stored outbound passwords were not.
<b>Action</b>	Make sure the Outbound Password Manager is properly configured, and that its files are readable by the Integration Server process. If the Outbound Password Manager is set up correctly, and the error still occurs, go to the LDAP Configuration screen of the Server Administrator and reenter the existing password.

---

<b>ISS.0002.0018E</b>	<b>Unable to store password for handle {0}: {1}</b>
<b>Explanation</b>	The Integration Server was unable to store the password needed to connect to an LDAP server. The Integration Server must supply passwords to many of the applications it connects to. It stores these outbound passwords in encrypted form on the Integration Server. This error occurs when an administrator enters or changes the password, but the Integration Server cannot subsequently store it.
<b>Action</b>	Check to see if the Integration Server is properly configured to handle outbound passwords. Make sure that the following outbound password configuration files reside on the Integration Server and are readable and writable: config/txnPassStore.dat, config/empw.dat, config/configPassman.cnf and config/passman.cnf. Refer to the webMethods Integration Server documentation for more information.
<b>ISS.0002.0019E</b>	<b>Unable to delete password for handle {0}: {1}</b>
<b>Explanation</b>	An administrator updated the Integration Server configuration so that it no longer connects to an LDAP server. As part of this process, the Integration Server tried to delete the password it uses to connect to the LDAP server, but was unable to. The Integration Server deletes the LDAP server from the configuration, but the password remains, in encrypted form, on the Integration Server. The most likely cause is that the files used to store outbound passwords on the Integration Server are read-only.
<b>Action</b>	Refer to the webMethods Integration Server documentation for more information about outbound passwords and the files used to store them. Then try to determine why the files are in read-only mode.
<b>ISS.0002.0020E</b>	<b>Unable to check password: LDAP User Manager not initialized</b>
<b>Explanation</b>	The Integration Server tried to check the password of an LDAP user but could not because the LDAP user manager is not running. This error occurs when one user updates the Integration Server configuration to disable LDAP directory use while another user is trying to perform an LDAP operation.
<b>Action</b>	Determine why the other user changed the Integration Server configuration. Then, reconfigure the Integration Server to use LDAP, if appropriate. For information about using the Integration Server with an external directory, refer to the webMethods Integration Server documentation.
<b>ISS.0002.0021E</b>	<b>Unable to check group membership: LDAP User Manager not initialized</b>
<b>Explanation</b>	The Integration Server tried to find members of an LDAP group but could not because the LDAP user manager is not running. This error occurs when one user updates the Integration Server configuration to disable LDAP directory use while another user is trying to perform an LDAP operation.
<b>Action</b>	Determine why the other user changed the Integration Server configuration. Then, reconfigure the Integration Server to use LDAP, if appropriate. For information about using the Integration Server with an external directory, refer to the webMethods Integration Server documentation.

<b>ISS.0002.0023E</b>	<b>Error initializing a connection to {0}: {1}</b>
<b>Explanation</b>	The Integration Server encountered an exception while trying to connect to the indicated LDAP server.
<b>Action</b>	Check the following:  - Make sure the LDAP directory server is running and that the Integration Server has permission to access it.  - Make sure the parameters on the External User Management Configuration screens of the Server Administrator have been properly set.
<b>ISS.0002.0024W</b>	<b>Error closing connection to {0}: {1}</b>
<b>Explanation</b>	Integration Server encountered an exception while trying to connect to the indicated LDAP server. Integration Server will clean up the connection.
<b>Action</b>	No action is required.
<b>ISS.0002.0030E</b>	<b>While attempting automatic LDAP configuration, some invalid settings were found. It is necessary to complete the configuration manually.</b>
<b>Explanation</b>	When you upgrade from Integration Server release 6.1 or earlier to Integration Server release 6.5 or later, the upgrade process tries to automatically configure the external user management facilities in your new Integration Server based on these settings in your old Integration Server. To determine the old configuration settings, the upgrade process looks for the following properties:  watt.server.ldap.server  watt.server.ldap.attr.userId  watt.server.ldap.attr.member  This error indicates that the upgrade process was unable to find one of these properties. The automatic configuration does not continue.
<b>Action</b>	Go to the Security > Users and Groups > External User Management Configuration screen of the Server Administrator and configure the Integration Server to use an external LDAP directory. For additional information, refer to the webMethods Integration Server documentation.
<b>ISS.0002.0034E</b>	<b>Invalid credentials connecting to {0} as {1}</b>
<b>Explanation</b>	The Integration Server encountered an Authentication Exception because the indicated user could not log in to the indicated LDAP server.
<b>Action</b>	This error can occur for a number of reasons. Make sure that the DN of the user is valid, the credentials (i.e. password) specified are valid, and the user account is enabled.

---

<b>ISS.0002.0035E</b>	<b>Invalid credentials connecting to {0} as {1}: {2}</b>
<b>Explanation</b>	The Integration Server encountered an Authentication Exception because the indicated user could not log in to the indicated LDAP server. The last part of the message <errorMessage> includes extra information provided by the LDAP server about the error. You can use this data to audit authentication errors when the Integration Server connects to Microsoft Active Directory.
<b>Action</b>	This error can occur for a number of reasons. Check to make sure that the DN of the user is valid, the credentials (i.e. password) specified are valid, and the user account is enabled. Note: The errorMessage portion of this error displays only if the watt.server.ldap.extendedMessages property in the server.cnf file is set to true. If you do not find the extended message useful, you can disable extended messaging by setting this property to false.
<b>ISS.0002.0040E</b>	<b>Error querying for users : {0}</b>
<b>Explanation</b>	Error while listing users from the LDAP server, a runtime exception occurred while querying users for the provided search criteria.
<b>Action</b>	Ensure that the search criteria is defined properly, the LDAP server is configured properly, and it is running.
<b>ISS.0002.0041E</b>	<b>Error querying for users : {0}</b>
<b>Explanation</b>	Some errors occurred while searching for a particular group, or a search string in the LDAP Server.
<b>Action</b>	Ensure that the search criteria is defined properly, the LDAP server is configured properly, and it is running.
<b>ISS.0002.0042W</b>	<b>Bailing out query as {0} is null or empty.</b>
<b>Explanation</b>	While listing users from the LDAP server, either the directory name suffix or directory name prefix returned from the server is null or empty.
<b>Action</b>	Ensure that the LDAP configuration is correct and the LDAP server is not disconnected.
<b>ISS.0002.0044E</b>	<b>Error querying for user(s) on {0} with search root {2}: {3}</b>
<b>Explanation</b>	Error while listing users from the LDAP server, a runtime exception occurred while querying users for the provided search criteria.
<b>Action</b>	Ensure that the search criteria is defined properly, the LDAP server is configured properly, and it is running.

<b>ISS.0002.0045W</b>	<b>Found No Group on quering on {0} with root {1} and filter {2}</b>
<b>Explanation</b>	No group is found in the LDAP server for the search criteria.
<b>Action</b>	Refine the search query to get the required result.
<b>ISS.0002.0046E</b>	<b>Selected group {0} does not exist.</b>
<b>Explanation</b>	The Integration Server group associated with the LDAP configuration is deleted.
<b>Action</b>	Ensure that the group selected while configuring LDAP exists. If the group does not exist, you can take one of the following actions:  1) Modify the LDAP configuration to specify another group.  2) Add a group with the same name as the deleted group that was associated with the LDAP configuration.
<b>ISS.0002.9001E</b>	<b>LDAP User Manager not initialized</b>
<b>Explanation</b>	A user is trying to execute an operation on the LDAP server but LDAP user manager is not initialized.
<b>Action</b>	Check the LDAP settings.
<b>ISS.0002.9002E</b>	<b>Error saving new ACL Mappings: {0}</b>
<b>Explanation</b>	A runtime exception occurred while adding new mappings to the LDAP Server.
<b>Action</b>	Ensure that the mapping strings are correct (they should be in the following format - name; dn), the LDAP server is configured properly and it is running.
<b>ISS.0003.9001</b>	<b>Transformation: Required argument "{0}" missing.</b>
<b>ISS.0003.9002</b>	<b>Transformation: No XML source provided</b>
<b>ISS.0003.9003</b>	<b>Transformation: No result type specified</b>
<b>ISS.0003.9004</b>	<b>Transformation: No result filename specified</b>

<b>ISS.0003.9005</b>	<b>Transformation: No result system ID specified</b>
<b>ISS.0003.9006</b>	<b>Transformation: PipedInputStreamException - {0}</b>
<b>ISS.0003.9007</b>	<b>Transformation: HTTPS URL error - {0}</b>
<b>ISS.0003.9008</b>	<b>Transformation: HTTPS URL error - Response returned with HTTP protocol error {0}.</b>
<b>ISS.0003.9009</b>	<b>XSLT Samples: No XSLT input paramters provided</b>
<b>ISS.0003.9010</b>	<b>XSLT Service: No valid input provided</b>
<b>ISS.0003.9011</b>	<b>XSLT Service: No associated .xsl file for this service</b>
<b>ISS.0006.0030E</b>	<b>Unable to set javax.net.ssl.keyStore: Keystore location could not be retrieved from {0}.</b>
<b>Explanation</b>	Integration Server could not set the javax.net.ssl.keyStore system property because Integration Sever could not retrieve the keystore location from the keystore file. Integration Server looks in the keystore file associated with the specified keystore alias. At run time, the {0} in the error message is replaced with the name of the keystore alias assigned to the watt.sever.ssl.keyStoreAlias parameter.
<b>Action</b>	Make sure the keystore alias assigned to the watt.server.ssl.keyStoreAlias parameter contains the correct keystore details including the correct location of the keystore file.
<b>ISS.0006.0031E</b>	<b>Unable to set javax.net.ssl.keyStorePassword: Keystore password could not be retrieved from {0}.</b>
<b>Explanation</b>	Integration Server could not set the javax.net.ssl.keyStorePassword system property because Integration Server could not retrieve the password from the keystore file. Integration Server looks in the keystore file associated with the specified keystore alias. At run time, the {0} in the error message is replaced with the name of the keystore alias assigned to the watt.server.ssl.keyStoreAlias parameter.
<b>Action</b>	Make sure the keystore alias assigned to the watt.server.ssl.keyStoreAlias parameter contains the correct keystore details including the correct password for accessing the keystore file.

<b>ISS.0006.0032E</b>	<b>Unable to set javax.net.ssl.trustStore: Truststore location could not be retrieved from {0}.</b>
<b>Explanation</b>	Integration Server could not set the value of the javax.net.ssl.trustStore system property because Integration Server could not retrieve the truststore location from the truststore file. Integration Server looks in the truststore file associated with the specified truststore alias. At run time, the {0} in the error message is replaced with the name of the truststore alias assigned to the watt.server.ssl.trustStoreAlias parameter.
<b>Action</b>	Make sure the truststore alias assigned to the watt.server.ssl.trustStoreAlias parameter contains the correct truststore details including the correct location of the truststore file.
<b>ISS.0006.0033E</b>	<b>Unable to set javax.net.ssl.trustStorePassword: Truststore password could not be retrieved from {0}.</b>
<b>Explanation</b>	Integration Server could not set the javax.net.ssl.trustStorePassword system property because Integration Server could not retrieve the password for the truststore. Integration Server looks in the truststore file associated with the specified truststore alias. At run time, the {0} in the error message is replaced with the name of the truststore alias assigned to the watt.server.ssl.keyStoreAlias parameter.
<b>Action</b>	Make sure the truststore alias assigned to the watt.server.ssl.trustStoreAlias parameter contains the correct truststore details including the correct password for accessing the truststore file.
<b>ISS.0006.0034E</b>	<b>Error setting javax.net.ssl properties: {0}</b>
<b>Explanation</b>	The javax.net.ssl system properties cannot be set because the keystore and/or truststore is invalid.
<b>Action</b>	Use the exception included in the error message to determine why the javax.net.ssl properties could not be set. Actions to be taken might include the following:- Making sure the keystore or truststore file is valid and contains the correct information. - Making sure that the keystore alias assigned to watt.server.ssl.keyStoreAlias contains the correct details for the keystore. - Making sure that the truststore alias assigned to watt.server.ssl.trustStoreAlias contains the correct details for the truststore.If the keystore file is invalid, create a new keystore, keystore alias, truststore, and truststore alias. Use the new keystore alias as the value of watt.server.ssl.keyStoreAlias. Use the new truststore alias as the value of watt.server.ssl.trustStoreAlias.If the truststore file is invalid, create a new truststore and truststore alias and use the new alias as the value of watt.server.ssl.trustStoreAlias.

<b>ISS.0007.0001E</b>	<b>Access Denied. User "{0}" does not have permissions to invoke service: {1}.</b>
<b>Explanation</b>	The user does not have permission to invoke an Integration Server resource. Read through the details provided in the server log to find the user name and the name of the service.
<b>Action</b>	To grant permission to the user, either add the user to a group that is listed in the Execute ACL assigned to the service, or add one of this user's groups to the Execute ACL assigned to the service.
<b>ISS.0007.0002E</b>	<b>Access Denied. No permissions to invoke service ({0}) on port "{1}".</b>
<b>Explanation</b>	The Access Mode for the specified port is configured to Deny by Default. With this configuration, the port only allows the services explicitly listed in the Allow List. The identified service is not in the Allow List of the identified port.
<b>Action</b>	If this service should be allowed on this port, add the service to the Allowed Services list of the port.
<b>ISS.0010.8050</b>	<b>Error while connecting to the remote authorization server using the remote server alias "{0}". Error details: {1}</b>
<b>Explanation</b>	Integration Server cannot connect to the specified remote OAuth authorization server.
<b>Action</b>	Edit the remote server alias and ensure that all the parameters are specified correctly. If needed, run a test of the remote server alias.
<b>ISS.0010.9016E</b>	<b>The cache manager required for OAuth operations is not available. Verify that the cache manager initialized successfully and then restart Integration Server</b>
<b>Explanation</b>	During the initialization of Cache Managers an error was encountered.
<b>Action</b>	Examine the Integration Server Error logs and Server logs for details about the error. Use the information in the logs to correct the error and then restart Integration Server.
<b>ISS.0012.0014E</b>	<b>Unable to initialize JAAS login context. JAAS configuration file in use: {0}. Error message: {1}. Stack trace: {2}</b>
<b>Explanation</b>	Integration Server uses IntegrationServer/config/is_jaas.cnf file for its JAAS configuration. If there is any problem loading this file, Integration Server throws this exception.
<b>Action</b>	The entries found in a JAAS configuration file should follow the JAAS syntax. If you made any changes to the IntegrationServer/config/is_jaas.cnf, review your changes and make sure there are no syntax errors in the file.

<b>ISS.0012.0016E</b>	<b>Initialization of X509ValidatorModule failed with exception: {0}.</b>
<b>Explanation</b>	The X509ValidatorModule defined in the IntegrationServer/config/is_jaas.cnf file is incorrect.
<b>Action</b>	Review the Integration Server error log for the actual exception. Refer to the webMethods Integration Server documentation for information about how to use this module and correct any errors found.
<b>ISS.0012.0017E</b>	<b>Authentication failed because the X.509 certificate path validation has failed.</b>
<b>Explanation</b>	The X509ValidatorModule is enabled in the IntegrationServer/config/is_jaas.cnf file. As a result, Integration Server performed certificate path validation using the information provided, but the client certificates failed the certificate path validation.
<b>Action</b>	Make sure that the truststore used by the X509ValidatorModule contains the intermediary certificates as well.
<b>ISS.0012.0020E</b>	<b>Authentication failed because the X.509 certificate has been revoked.</b>
<b>Explanation</b>	The X509ValidatorModule is enabled in the IntegrationServer/config/is_jaas.cnf file. As a result, Integration Server checked the client certificate against the Certificate Revocation List (CRL) and the client certificate was found to be revoked.
<b>Action</b>	Advise the client to resubmit the request using a valid certificate.
<b>ISS.0012.0022E</b>	<b>Access Denied. Authentication resolved to user "{0}". User is not defined in any of the available user stores.</b>
<b>Explanation</b>	Integration Server JAAS authentication modules return the username in the Subject. Integration Server then tries to retrieve the definition of this user either locally in its user store, or in Central Users (if configured), or LDAP (if configured). If Integration Server is not able to find the user anywhere, it rejects the client request with this error.
<b>Action</b>	If this user should be allowed accessing Integration Server resources, make sure this user is defined in any of the user stores accessible to Integration Server.
<b>ISS.0012.0023E</b>	<b>SAML assertion verification failed. The current time {0} violates the "Not Before" setting {1} specified in the SAML assertion.</b>
<b>Explanation</b>	Integration Server received a SAML assertion that arrived before the "Not Before" setting.
<b>Action</b>	Check the clock time of the issuer. If it is significantly different from the clock time on the Integration Server machine, adjust the Clock Skew value on the Security -> SAML screen.

---

<b>ISS.0012.0024</b>	<b>SAML assertion verification failed. The current time {0} violates the "Not On Or After" setting {1} specified in the SAML assertion.</b>
<b>Explanation</b>	Integration Server received a SAML assertion that arrived later than the "Not On Or After" setting.
<b>Action</b>	Check the clock time of the issuer. If it is significantly different from the clock time on the Integration Server machine, adjust the Clock Skew value on the Security -> SAML screen.
<b>ISS.0012.0025E</b>	<b>Rejecting SAML assertion from issuer "{0}" because issuer is not configured on the Security &gt; SAML screen.</b>
<b>Explanation</b>	Integration Server received a SAML assertion from an issuer that has not been configured on the Security -> SAML screen.
<b>Action</b>	Configure the issuer on the Security -> SAML screen.
<b>ISS.0012.0027W</b>	<b>{0}% or more of maximum number of concurrent stateful sessions are in use. {1} sessions are available.</b>
<b>Explanation</b>	Integration Server is approaching the threshold for concurrent stateful sessions.
<b>Action</b>	No immediate action is required. Once the limit is reached, all new requests to create stateful sessions will be rejected. You can increase the limit using the Resources screen in the Integration Server Administrator; however, doing so could increase the server's resource requirement.
<b>ISS.0012.0030E</b>	<b>Rejecting SAML assertion because the subject identified in the SAML assertion is not the one who signed the request.</b>
<b>Explanation</b>	For security reasons, Integration Server cannot accept requests that are not signed by the subject identified in the SAML assertion.
<b>Action</b>	Sign the message using the subject identified in the SAML assertion.
<b>ISS.0013.0001</b>	<b>Binding XML. Service {0} was unable to bind incoming XML data</b>
<b>ISS.0013.0004E</b>	<b>Registering multipart content handler {0} for service {1}.</b>
<b>Explanation</b>	The syntax for the watt.server.content.type.mappings parameter is invalid.
<b>Action</b>	Use the correct syntax for this parameter. See Administering webMethods Integration Server for more information about using watt.server.content.type.mappings.

<b>ISS.0014.0001E</b>	<b>Encountered fatal errors while starting License Manager. Shutting down server.</b>
<b>Explanation</b>	Integration Server encountered a serious internal error while validating the license.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0014.0004</b>	<b>No listening ports were available. Shutting down server.</b>
<b>ISS.0014.0009</b>	<b>Server is unable to determine its own name.</b>
<b>ISS.0014.0012</b>	<b>watt.server.fileEncoding unsupported by JVM. Server may be unable to continue.</b>
<b>ISS.0014.0013</b>	<b>watt.server.netEncoding unsupported by JVM. Text may not process properly.</b>
<b>ISS.0014.0014</b>	<b>watt.server.logEncoding unsupported by JVM. Logging in default encoding.</b>
<b>ISS.0014.0017</b>	<b>Warning: {0} when initializing ACL Manager file {1}</b>
<b>ISS.0014.0021E</b>	<b>Failed to invoke notification callback {0}: {1}</b>
<b>Explanation</b>	Integration Server encountered an error while updating ACLs. Specifically, an error occurred when Integration Server invoked a service that is registered as a notification callback.
<b>Action</b>	Make sure that the service being invoked exists and can be executed.
<b>ISS.0014.0022E</b>	<b>Retrying service {0}. Retry count is {1}</b>
<b>Explanation</b>	Integration Server is retrying a service that was previously unsuccessful.
<b>Action</b>	No action is required.
<b>ISS.0014.0023E</b>	<b>Available Thread Pool Threshold No Longer Exceeded: {0}% available</b>
<b>Explanation</b>	Integration Server is no longer exceeding the specified threshold for thread pool usage.
<b>Action</b>	No action is required.

---

<b>ISS.0014.0024E</b>	<b>Server Initialization Aborted. See log messages.</b>
<b>Explanation</b>	During start up, Integration Server encountered a serious internal error that caused it to shut down immediately.
<b>Action</b>	Make sure that the machine on which Integration Server runs has sufficient disk space. In addition, make sure the operating system user that is trying to start Integration Server has a sufficient space allowance and has read/write permission to the directory on which Integration Server resides.
<b>ISS.0014.0025</b>	<b>Master password for outbound password encryption has expired. Password was last changed on {0}. The current expiration interval is {1} days</b>
<b>ISS.0014.0026</b>	<b>Master password for outbound password encryption expires in {0} days</b>
<b>ISS.0014.0027</b>	<b>Unable to remove outbound password handle {0}</b>
<b>ISS.0014.0028</b>	<b>Cannot initialize OutboundPasswordManager with null Password Manager</b>
<b>ISS.0014.0029S</b>	<b>Master password failed a sanity check</b>
<b>Explanation</b>	During Integration Server initialization, the sanity check of the master password for outbound passwords failed. Integration Server uses the master password to encrypt outbound passwords, which the Integration Server uses to connect to applications or systems such as remote Integration Servers, proxy servers, or databases. The outbound passwords are stored in files on Integration Server and encrypted for security purposes. During initialization, Integration Server performs a sanity check of the master password by attempting to use it to decrypt a special, internal string that it previously encrypted using the master password. If the decrypted internal string matches the clear text version of the string, Integration Server knows the correct master password was provided. This error is issued when the decrypted and clear text versions of the string do not match.
<b>Action</b>	The sanity check of the master password can fail for a number of reasons: <ul style="list-style-type: none"><li>- The outbound password file is corrupted.</li><li>- The master password file is corrupted.</li><li>- You mistyped the master password when you were prompted for it.</li></ul> If you suspect you have mistyped the password, shut down the server and restart it, this time entering the correct password. If this does not correct the problem, refer to the webMethods Integration Server documentation.

<b>ISS.0014.0030S</b>	<b>Master password updated</b>
<b>Explanation</b>	The master password, which Integration Server uses to encrypt outbound passwords, has been successfully updated.
<b>Action</b>	No action is required.
<b>ISS.0014.0035S</b>	<b>OutboundPasswordManager configuration directory cannot be null</b>
<b>Explanation</b>	Integration Server cannot locate the configuration directory it uses for managing outbound passwords.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0014.0039S</b>	<b>OutboundPasswordManager, {0} caught this: type {1}, msg {2}</b>
<b>Explanation</b>	The code that Integration Server uses to manage outbound passwords encountered a problem while trying to perform the indicated operation.
<b>Action</b>	If the exception message text does not suggest a solution, contact Software AG Global Support.
<b>ISS.0014.0047</b>	<b>com.wm.app.b2b.server.DataStore must be initialized before it can be used.</b>
<b>ISS.0014.0048</b>	<b>The ISInternal functional alias is not configured properly on the JDBC Pools page. Assign a valid database pool and restart the Integration Server.</b>
<b>ISS.0014.0051</b>	<b>Cannot acquire the lock.</b>
<b>ISS.0014.0054</b>	<b>Error occurred while initializing server: {0}</b>
<b>ISS.0014.0055</b>	<b>Cannot acquire an exclusive lock. Another session is holding a shared lock on the requested item.</b>
<b>ISS.0014.0056</b>	<b>Cannot acquire an exclusive lock on the requested context. Another session has locked it.</b>

ISS.0014.0057	Integration Server is quiesced and is not accepting new requests at this time.
ISS.0014.0058	Integration Server has reached the license limit for concurrent sessions.
ISS.0014.9101	User does not exist: {0}
ISS.0014.9102	No package name specified
ISS.0014.9104	A listener must be provided
ISS.0014.9105	A listener factory must be provided
ISS.0014.9106	A listener factory with {0} is already registered in the {1} package
ISS.0014.9107	Attempted to register a factory with an invalid identifying key
ISS.0014.9108	Attempted to register a listener with an invalid identifying key
ISS.0014.9109	A listener is already registered with the key {0}. The existing listener must be unregistered first
ISS.0014.9110	Failed to update listener configuration information
ISS.0014.9111	Unregistration failed, could not update the configuration
ISS.0014.9112	Service {0} unable to bind incoming XML data
ISS.0014.9113	No Valid Active Packages

**ISS.0014.9114      Package directory for {0} does not exist**

**ISS.0014.9115      Package {0} does not exist**

**ISS.0014.9116      Unable to locate or start compiler**

**ISS.0014.9117      Unable to save file {0} for {1}**

**ISS.0014.9118U      ServerReferenceManager can't get session to access object cache**

**Explanation**      Integration Server encountered an internal error with the object cache.

**Action**              Contact Software AG Global Support.

**ISS.0014.9119U      Unable to allocate a new thread in the time specified**

**Explanation**      Integration Server has reached the configured limit for the number of new threads it can create. After waiting unsuccessfully for resources to become available, Integration Server issued this ISRuntime exception. This exception usually indicates a transient condition in which resources are temporarily unavailable. If this error occurs during execution of a trigger, and retry is enabled, Integration Server will automatically retry the service. If, after a configured amount of time, the resources are still unavailable, Integration Server throws this exception.

**Action**              If the problem persists, use the Resource Settings page of the Server Administrator to specify thread pool settings that are more appropriate for your environment.

**ISS.0014.9120      Can not set thread pool max to zero or less than min, max={0}, min={1}**

**ISS.0014.9121      Repository config file repository4.cnf not found.**

**ISS.0014.9123E      {0} package not reloaded; missing the following assets: {1}**

**Explanation**      An internal error occurred while using the local service development feature in Software AG Designer. An attempt to reload an updated IS asset (flow service, Java service, document type, etc. ) failed because the specified IS asset does not exist in the IS namespace. At run time, the {0} in the error message is replaced with the package name and the {1} is replaced with the IS assets that do not exist in the namespace.

**Action**              Contact Software AG Global Support.

---

<b>ISS.0014.9124E</b>	<b>{0} package not reloaded. {1} already registered in {2}</b>
<b>Explanation</b>	While using the local service development feature in Software AG Designer, an attempt to reload an updated IS asset (flow service, Java service, document type, etc. ) failed because Integration Server determined that another package contains an asset with the same name. At run time, the {0} in the error message is replaced with the package name, the {1} is replaced with the IS asset name for which a reload was attempted, and the {2} is replaced with the name of the package that contains the already loaded, identically named asset.
<b>Action</b>	Ensure that each IS asset uses a name that is unique across the Integration Server namespace. To rename one of the assets, you might need to disable the package that contains the asset whose name you do not want to change. Change the name of the IS asset in the package that you want to change. Then, re-enable both packages.
<b>ISS.0014.9125E</b>	<b>Primary port change failed. The primary port must be a port associated with the WmRoot package.</b>
<b>Explanation</b>	An attempt to change the primary port failed because the chosen port is associated with a package other than WmRoot.
<b>Action</b>	Select a port associated with the WmRoot package as the primary port. Alternatively, change the chosen port to associate it with the WmRoot package and then designate the port as the primary port.
<b>ISS.0014.9126E</b>	<b>Primary port change failed. The primary port must be an enabled port.</b>
<b>Explanation</b>	An attempt to change the primary port failed because the chosen port is not enabled.
<b>Action</b>	Select an enabled port as the primary port. Alternatively, enable the chosen port and then designate the port as the primary port.
<b>ISS.0014.9127E</b>	<b>Primary port change failed. The primary port must be an HTTP or HTTPS port.</b>
<b>Explanation</b>	An attempt to change the primary port failed because the chosen port is not an HTTP or HTTPS port.
<b>Action</b>	Select an HTTP or HTTPS port to use as the primary port.
<b>ISS.0014.9128E</b>	<b>Primary port change failed. The primary port must be a standard port.</b>
<b>Explanation</b>	An attempt to change the primary port failed because the chosen port was not a standard port. Currently, the only non-standard port type is the diagnostic port.
<b>Action</b>	Select a standard HTTP or HTTPS port to use as the primary port. Do not select a diagnostic port to be the primary port.

<b>ISS.0015.0002E</b>	<b>Error {0} initializing Invoke Manager class {1} from {2}</b>
<b>Explanation</b>	Integration Server failed to initialize InvokeManager from the configuration file located at <IntegrationServer_dir>/config/invokeManager.cnf file at startup.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0015.0003E</b>	<b>Error {0} initializing Invoke Manager with {2}</b>
<b>Explanation</b>	Integration Server failed to initialize InvokeManager from the configuration file located at <IntegrationServer_dir>/config/invokeManager.cnf file at startup.
<b>Action</b>	Using a text editor, open the <IntegrationServer_dir>/config/invokeManager.cnf file and make sure that the content is not corrupt. If the error still occurs, consider removing the invokeManager.cnf file and restarting Integration Server.
<b>ISS.0015.0004E</b>	<b>Service {0} failed ACL access checking for user {1}</b>
<b>Explanation</b>	The client application failed to invoke the service because the current user did not have the Execute ACL privileges to execute the service.
<b>Action</b>	Using the Integration Server Administrator, examine the ACL settings of the service as well as the ACL group to which the current user belongs. Make sure that the user has the proper ACL settings.
<b>ISS.0016.0006EE</b>	<b>Cannot cache {0} service. The cache manager {1} is not initialized.</b>
<b>Explanation</b>	The cache manager SoftwareAG.IS.Services is not initialized.
<b>Action</b>	Check the configuration of the SoftwareAG.IS.Services cache manager.
<b>ISS.0017.0001E</b>	<b>An error was encountered parsing {0}: {1}. See the Integration Server error log for the full stack trace.</b>
<b>Explanation</b>	Either the format of XML in the configuration file is invalid, or a specific setting is not allowed.
<b>Action</b>	Read through the details provided in the error message and edit the configuration file to correct the problem.
<b>ISS.0017.0002I</b>	<b>Cache manager {0} created.</b>
<b>ISS.0017.0003E</b>	<b>{0} is required.</b>
<b>Explanation</b>	A value is required for the indicated parameter.
<b>Action</b>	Supply a value for the parameter.

---

<b>ISS.0017.0004E</b>	<b>There is no cache manager named {0}.</b>
<b>Explanation</b>	There is no cache manager with this name on Integration Server.
<b>Action</b>	Make sure the cache manager name is typed correctly and that it exists on the Integration Server.
<b>ISS.0017.0005E</b>	<b>There is no cache named {0} in the {1} cache manager.</b>
<b>Explanation</b>	Integration Server tried to connect to the indicated cache, but there is no cache with this name associated with the cache manager.
<b>Action</b>	Provide the name of a cache that is managed by the supplied cache manager.
<b>ISS.0017.0006I</b>	<b>Cache {0} created.</b>
<b>ISS.0017.0007E</b>	<b>Cache manager names starting with "SoftwareAG" are reserved.</b>
<b>Explanation</b>	The cache manager could not be created because the name is invalid.
<b>Action</b>	Choose a different name for the cache manager.
<b>ISS.0017.0008I</b>	<b>Successfully deleted cache manager {0}.</b>
<b>ISS.0017.0009I</b>	<b>All elements have been removed from cache {1} of cache manager {0}.</b>
<b>ISS.0017.0010I</b>	<b>Disabled cache {1} of cache manager {0}.</b>
<b>ISS.0017.0011I</b>	<b>Enabled cache {1} of cache manager {0}.</b>
<b>ISS.0017.0012E</b>	<b>Cache manager {0} is not started.</b>
<b>Explanation</b>	The service failed to execute because the specified cache manager is not available.
<b>Action</b>	Open Integration Server Administrator and go to the Settings > Caching page to verify that the cache manager is started and the cache the service wants to use is enabled.
<b>ISS.0017.0013E</b>	<b>Cache {1} for cache manager {0} not enabled.</b>
<b>Explanation</b>	The operation could not be completed because the indicated cache could not be found in the indicated cache manager.
<b>Action</b>	Make sure the cache name is typed correctly and that it is contained in the indicated cache manager.

- ISS.0017.0014E**      **Cache manager {0} already exists.**  
**Explanation**      The cache manager could not be created because a cache manager with the indicated name already exists on the Integration Server. The name you specify must be unique on the Integration Server.  
**Action**              Enter a new name for the cache manager that is unique to the Integration Server.
- ISS.0017.0015E**      **The {0} cache manager attempted to connect to a Terracotta Server Array, but the Integration Server license does not allow it. This cache manager will not be usable.**  
**Explanation**      To use this feature, Integration Server must have a license that allows distributed caching.  
**Action**              Obtain the appropriate license from Software AG Global Support and add it to the Integration Server.
- ISS.0017.0016E**      **If rejoin is enabled, a Terracotta Server Array URL must be supplied.**  
**Explanation**      You selected the Rejoin check box, but did not configure the cache manager to connect to a Terracotta Server Array.  
**Action**              Specify a Terracotta Server Array URL or clear the Rejoin check box.
- ISS.0017.0017E**      **Cannot use the administrative services to change a system cache manager: {0}.**  
**Explanation**      The cache could not be created because a cache with that name already exists in the cache manager. The name you specify must be unique within the cache manager.  
**Action**              See Administering webMethods Integration Server for more information about system cache managers.
- ISS.0017.0018E**      **The {0} cache already exists.**  
**Explanation**      The cache could not be created because a cache with that name already exists in the cache manager. The name you specify must be unique within the cache manager.  
**Action**              Enter a name for the cache that is unique within the cache manager.
- ISS.0017.0019E**      **Cannot delete a system cache manager: {0}.**  
**Explanation**      The cache manager you attempted to delete is a system cache manager and cannot be deleted.  
**Action**              See Administering webMethods Integration Server for more information about system cache managers.

<b>ISS.0017.0020E</b>	<b>Cache manager name cannot contain any of these characters: ? [ ] / = + &lt; &gt; : ; " , *   ^ @</b>
<b>Explanation</b>	The cache manager could not be created because the name you specified contains invalid characters.
<b>Action</b>	Specify a new name using valid characters.
<b>ISS.0017.0021E</b>	<b>Cache manager name cannot start with a ' ' or end with a space.</b>
<b>Explanation</b>	The cache manager could not be created because the name you specified contains invalid characters.
<b>Action</b>	Specify a new name using valid characters.
<b>ISS.0017.0022E</b>	<b>Cache manager name cannot be an operating system device name.</b>
<b>Explanation</b>	The cache manager could not be created because the name you specified is a reserved word as specified by your operating system.
<b>Action</b>	Specify a new name for the cache manager. Refer to your operating system's documentation for a list of reserved words.
<b>ISS.0017.0023E</b>	<b>An error was encountered updating {0}: {1}. See the Integration Server error log for the full stack trace.</b>
<b>Explanation</b>	While attempting to enable or disable clustering for the Integration Server, an error occurred while updating the Terracotta Cache Manager configuration files.
<b>Action</b>	Review the error details provided in the message and in the Integration Server error log. After correcting the issue that caused the error, use Integration Server Administrator to enable or disable clustering for the Integration Server.
<b>ISS.0017.0024E</b>	<b>When a cache is distributed, Overflow to Disk, Overflow to Off-heap and Persist to Disk cannot be selected.</b>
<b>Explanation</b>	The Overflow to Disk, Overflow to Off-heap and Persist to Disk options are not allowed with distributed caches.
<b>Action</b>	If you are creating a distributed cache, remove the values from the Overflow to Disk, Overflow to Off-heap and Persist to Disk fields.
<b>ISS.0017.0026E</b>	<b>Cache manager name is null in {0}. The cache manager will not be used</b>
<b>Explanation</b>	A cache manager configuration file was supplied with a null cache manager name.
<b>Action</b>	Edit the configuration file and provide a name for the cache manager.

- ISS.0017.0027E**      **A cache manager named "{0}" has already been loaded from {1}. The name cannot also be used in {2}. The cache manager in {2} will be ignored.**
- Explanation**      More than one configuration file in the Integration Server\_directory\config\Caching directory contains the specified cache manager. Integration Server cannot load two instances of the same cache manager. The cache manager that is already loaded is being used. The cache manager in the second configuration file will be ignored.
- Action**            Either remove one of the configuration files or change the cache manager name in one of the configuration files.
- 
- ISS.0017.0029I**      **Cache manager {0} successfully started.**
- 
- ISS.0017.0030E**      **Cache manager {0} successfully reloaded.**
- Explanation**      A value is required for the indicated parameter.
- Action**            Supply a value for the parameter.
- 
- ISS.0017.0031I**      **Cache manager {0} is already running.**
- 
- ISS.0017.0032I**      **Cache manager {0} is not running.**
- 
- ISS.0017.0033E**      **Cannot enable a system cache.**
- Explanation**      The cache you attempted to enable is a system cache. System caches are used by internal processes and cannot be modified.
- Action**            See Administering webMethods Integration Server for more information about system caches.
- 
- ISS.0017.0034E**      **Cannot disable a system cache.**
- Explanation**      The cache you attempted to disable is a system cache. System caches are used by internal processes and cannot be modified.
- Action**            See Administering webMethods Integration Server for more information about system caches.
- 
- ISS.0017.0035E**      **Cannot clear the contents of a system cache.**
- Explanation**      The cache you attempted to clear is a system cache. System caches are used by internal processes and cannot be modified.
- Action**            See Administering webMethods Integration Server for more information about system caches.

---

<b>ISS.0017.0036E</b>	<b>Cannot start a system cache manager.</b>
<b>Explanation</b>	The cache manager you attempted to start is a system cache manager. System cache managers are used by internal processes and cannot be modified.
<b>Action</b>	See Administering webMethods Integration Server for more information about system cache managers.
<b>ISS.0017.0037E</b>	<b>Cannot shutdown a system cache manager.</b>
<b>Explanation</b>	The cache manager you attempted to shutdown is a system cache manager. System cache managers are used by internal processes and cannot be modified.
<b>Action</b>	See Administering webMethods Integration Server for more information about system cache managers.
<b>ISS.0017.0038E</b>	<b>Cannot reload a system cache manager.</b>
<b>Explanation</b>	The cache manager you attempted to reload is a system cache manager. System cache managers are used by internal processes and cannot be modified.
<b>Action</b>	See Administering webMethods Integration Server for more information about system caches.
<b>ISS.0017.0039E</b>	<b>Attempted to create cache manager {0} that connects to a Terracotta Server Array, but the Integration Server license does not allow it. Cannot save cache manager configuration.</b>
<b>Explanation</b>	To use this feature, Integration Server must have a license that allows distributed caching.
<b>Action</b>	Obtain the appropriate license from Software AG Global Support and add it to Integration Server.
<b>ISS.0017.0040I</b>	<b>Successfully evicted expired elements from the cache {0} contained in cache manager {1}.</b>
<b>ISS.0017.0041I</b>	<b>Cleared all caches starting with name {0} contained within the cache manager {1}.</b>
<b>ISS.0017.0042I</b>	<b>Cleared all caches contained within the cache manager {0}.</b>

<b>ISS.0017.0043E</b>	<b>Error occurred while clearing caches starting with name {0} contained within the cache manager {1}. Details:{2}</b>
<b>Explanation</b>	The service cannot remove the element from the cache for the reason indicated in the message.
<b>Action</b>	Take the appropriate action based on the details shown in the message.
<b>ISS.0017.0044E</b>	<b>Error occurred while clearing caches contained within the cache manager {0}. Details:{1}</b>
<b>Explanation</b>	The service did not clear the caches in the specified cache manager because of the specified error.
<b>Action</b>	Take the appropriate action based on the details shown in the message.
<b>ISS.0017.0045I</b>	<b>Added cache {0}.</b>
<b>ISS.0017.0046I</b>	<b>Updated cache {0}.</b>
<b>ISS.0017.0047I</b>	<b>Deleted cache {0}.</b>
<b>ISS.0017.0048E</b>	<b>{0} is not a distributed cache. Integration Server cannot synchronize with the Terracotta Server Array.</b>
<b>Explanation</b>	You can only synchronize distributed caches with a Terracotta Server Arrays.
<b>Action</b>	Set the Distributed option on all the caches you want to synchronize with the Terracotta Server Array.
<b>ISS.0017.0049E</b>	<b>The {0} cache manager is not running. Start the cache manager to synchronize the cache with the Terracotta Server Array.</b>
<b>Explanation</b>	You cannot synchronize caches against the Terracotta Server Array when the cache manager is not running.
<b>Action</b>	Start the cache manager and then synchronize the cache with the Terracotta Server Array.
<b>ISS.0017.0050I</b>	<b>The configuration for the {0} cache has been synchronized with the Terracotta Server Array.</b>

<b>ISS.0017.0051I</b>	<b>Integration Server cannot evict expired elements for caches contained in a system cache manager.</b>
<b>ISS.0017.0052I</b>	<b>Integration Server cannot reload the {0} cache manager because it is not running.</b>
<b>ISS.0017.0053E</b>	<b>The {0} cache in {1} has a different local configuration than the configuration on the Terracotta Server Array. Integration Server is using the configuration from the Terracotta Server Array.</b>
<b>Explanation</b>	The configuration of the local cache should match that of the associated Terracotta Server Array. If the local cache configuration does not match the configuration of the Terracotta Server Array, Integration Server ignores the local cache configuration and uses the configuration of the Terracotta Server Array.
<b>Action</b>	Configure the local cache to match the configuration of the Terracotta Server Array.
<b>ISS.0017.0054I</b>	<b>Use Integration Server Administrator to synchronize mismatched cache configurations with the Terracotta Server Array.</b>
<b>ISS.0017.0055E</b>	<b>Integration Server has registered a cache manager, but the configuration file is not in the config/Caching directory. Integration Server cannot manage this configuration.</b>
<b>Explanation</b>	Integration Server saved the configuration for a cache manager, but the configuration file is not in the IntegrationServer/config/Caching directory. If the configuration is valid, you can still use the cache manager, but you cannot use Integration Server Administrator to stop or start the cache manager or edit its configuration.
<b>Action</b>	Copy the configuration file to the IntegrationServer/config/Caching directory and restart Integration Server.
<b>ISS.0017.0056E</b>	<b>The {0} cache manager is shut down but there is no configuration file associated with it. Integration Server cannot restart this cache manager.</b>
<b>Explanation</b>	The cache manager configuration file is not in the IntegrationServer/config/Caching directory.
<b>Action</b>	Restore the missing configuration file to the IntegrationServer/config/Caching directory.
<b>ISS.0017.0057E</b>	<b>The {0} cache manager is shut down but its corresponding configuration file ({1}) no longer exists. Integration Server cannot restart this cache manager.</b>
<b>Explanation</b>	The cache manager configuration file is not in the IntegrationServer/config/Caching directory.
<b>Action</b>	Restore the missing configuration file to the IntegrationServer/config/Caching directory.

- ISS.0017.0058E**      **Integration Server cannot remove the Terracotta Server Array URLs for this cache manager because one or more of its caches are distributed. Clear the Distributed option on all the caches.**
- Explanation**      Integration Server cannot remove Terracotta Server Array URLs if any of the caches contained in the cache manager are distributed.
- Action**             Shut down the cache manager and then change the Terracotta Server Array URLs.
- 
- ISS.0017.0059E**      **Integration Server cannot modify the Terracotta Server Array URLs for a cache manager while it is running. Shut down the cache manager, then change the Terracotta Server Array URLs.**
- Explanation**      Integration Server cannot modify the Terracotta Server Array URLs for a cache manager while it is running.
- Action**             Shut down the cache manager and then change the Terracotta Server Array URLs.
- 
- ISS.0017.0060I**      **Updated cache manager {0}.**
- 
- ISS.0017.0061I**      **Added cache manager {0}.**
- 
- ISS.0017.0062E**      **Integration Server encountered an error while parsing {0}: {1}.**
- Explanation**      The cache manager configuration file contains invalid syntax.
- Action**             Manually edit the cache manager configuration file so that it is syntactically correct.
- 
- ISS.0017.0063I**      **The current Terracotta license is not valid for the BigMemory settings configured for the {0} cache manager. To use the cache manager, either remove the BigMemory settings from the configuration file or obtain a valid Terracotta license for BigMemory.**
- 
- ISS.0017.0064E**      **Deployment of cache manager {0} failed because of invalid license. Check the Integration Server log for details.**
- Explanation**      Integration Server could not deploy the cache manager because the license for Integration Server or Terracotta is invalid.
- Action**             Acquire the correct license file for Terracotta, Integration Server, or both and then redeploy the cache manager.

---

ISS.0017.0065I	Reading cache manager configuration from file {0}.
ISS.0017.0066I	{0} is a system cache manager.
ISS.0017.0067I	Read cache manager {0} from file {1}.
ISS.0017.0068I	Integration Server is running in safe mode. Cache manager {0} not initialized.
ISS.0017.0069I	Initializing cache manager {0}.
ISS.0017.0070I	Cache manager {0} initialized.
ISS.0017.0072I	Shutting down cache manager {0}.
ISS.0017.0073I	Cache manager {0} is shut down.
ISS.0017.0074I	Shutting down cache managers.
ISS.0017.0075I	Finished shutting down cache managers.
ISS.0017.0076E	<b>The value specified in the "Maximum Elements in Memory" field must be an integer no larger than 2147483647.</b>
<b>Explanation</b>	An invalid value was specified in the Maximum Elements in Memory field.
<b>Action</b>	Change the value to an integer no larger than 2147483647.
ISS.0017.0077E	<b>Field cannot be changed while the cache manager is running: {0}</b>
<b>Explanation</b>	The specified field cannot be modified while the cache manager is running.
<b>Action</b>	Shut down the cache manager, and then update the field. To shut down the cache manager, open Integration Server Administrator and go to the Settings > Caching page, then click the "Shutdown" link for the cache's cache manager.

**ISS.0019.7005E**      **Unable to retrieve client\_secret for {0} from the secure password store. See the error log for a full stack trace.**

**Explanation**      Integration Server cannot retrieve the client secret for the specified OpenID Provider.

**Action**              Re-enter the client\_secret value in the OpenID Provider's configuration file and click the Reload OpenID Providers link on the Security > OpenID page. If none of the passwords work, the password store might be corrupt. Contact Software AG Global Support.

**ISS.0019.7007E**      **ID Token's issuer claim {0} is invalid. It does not match the application's OpenID Provider issuer ID.**

**Explanation**      Integration Server expected the iss field in the token to match the issuer value in the OpenID Provider's configuration file; however, the iss and issuer values do not match.

**Action**              Check that the issuer value in the OpenID Provider's configuration file is correct. If it is not, edit the OpenID Provider configuration file to include the correct issuer value. Then, click the Reload OpenID Providers link on the Security > OpenID page.

**ISS.0019.7008E**      **ID Token's audience claim {0} does not match the application's OpenID Provider client ID.**

**Explanation**      Integration Server expected the aud field in the token to match the client\_id value in the OpenID Provider's configuration file.

**Action**              Check that the client\_id value in the OpenID Provider's configuration file is correct. If it is not, edit the OpenID Provider configuration file to include the correct client\_id value. Then, click the Reload OpenID Providers link on the Security > OpenID page.

**ISS.0019.7009E**      **ID Token's audience claim has multiple values "{0}" but the required authorized party claim is not present.**

**Explanation**      The audience for an ID Token must contain the OAuth 2.0 client\_id of the Relying Party as an audience value but the required client\_id is missing.

**Action**              No action required.

**ISS.0019.7010E**      **ID Token's authorized party claim {0} does not match the OpenID Provider client ID {1}.**

**Explanation**      The authorized party claim in the ID Token either does not contain or does not match the OAuth 2.0 client\_id for the Authorized Party. The ID token must contain the authorized party claim when the ID Token has a single audience value and the audience is not the Authorized Party.

**Action**              No action required.

<b>ISS.0019.7011E</b>	<b>ID Token has expired. Expiration claim value is {0}, current time is {1}.</b>
<b>Explanation</b>	The ID Token issued by the OpenID Provider has expired and cannot be used for authentication.
<b>Action</b>	Set the prompt value in the OpenID Provider's configuration file to "login", which instructs the OpenID Provider to require the end user to log in using their credentials. Then, click the Reload OpenID Provider link on the Security > OpenID page. Have the user reissue the original request.
<b>ISS.0019.7012E</b>	<b>ID Token has expired. Issued at time value is {0}, current time is {1}, provider's max_age limit is {2}.</b>
<b>Explanation</b>	The age of the ID Token issued by the OpenID Provider exceeds the max_age value in the OpenID Provider's configuration file. The token cannot be used for authentication.
<b>Action</b>	Increase the max_age value in the OpenID Provider's configuration file and click the Reload OpenID Provider link on the Security > OpenID page. Have the user reissue the original request.
<b>ISS.0019.7013E</b>	<b>ID Token's asserted claim value(s) "{0}" do not match any of the provider's asserted claim values "{1}".</b>
<b>Explanation</b>	The claim values in the token do not match any of the claim values for the OpenID Provider.
<b>Action</b>	No action required.
<b>ISS.0019.7015E</b>	<b>ID Token requires re-authentication, Maximum Authentication Age {0} has expired. Authentication time was {1}, current time is {2}</b>
<b>Explanation</b>	The user must be re-authenticated because the time elapsed since the token authentication time exceed the Maximum Authentication Age.
<b>Action</b>	Re-authenticate the token. Set the prompt value in the OpenID Provider's configuration file to "login" and click the Reload OpenID Provider link on the Security > OpenID page. Have the user reissue the request.
<b>ISS.0019.7016E</b>	<b>{0} is null.</b>
<b>Explanation</b>	The OpenID Provider's token endpoint or userinfo endpoint did not return a token.
<b>Action</b>	Check the error log for an exception related to the request. Set watt.server.oauth.custom.responseHeader to true and the server logging facility "0040 HTTP Response" to TRACE. Recreate the problem and check the server log for a response header of X-OAuth-Error. If no error is reported, contact the OpenID Provider.

- ISS.0024.0001**      **Could not initialize User Manager.**
- ISS.0024.0002**      **Error occurred while initializing User Manager: Class {0} was not found in CLASSPATH.**
- ISS.0024.0003**      **Error occurred while initializing User Manager: {0}**
- ISS.0024.0004**      **Could not access User Manager**
- ISS.0024.0005E**      **Could not read users.cnf (the file may be corrupt)**  
**Explanation**      Integration Server could not read user and group configuration information from the users.cnf file. The file might be corrupt.  
**Action**            Examine this file in the Integration Server /config directory. Ensure that the server has read access to it. If the file is corrupted, you might need to set up the users and/or groups again through the Integration Server Administrator.
- ISS.0024.0006E**      **Could not write users.cnf (the file may be corrupt)**  
**Explanation**      Integration Server could not write user and group configuration information to the users.cnf file. The file might be corrupt.  
**Action**            Examine this file in the Integration Server /config directory. Ensure that the server has write access to it. If the file is corrupted, you might need to set up the users and/or groups again through the Integration Server Administrator.
- ISS.0024.0007**      **The JDBC Pool {0} associated with Central Users JDBC function is not defined so the Central User Manager is not enabled**
- ISS.0024.0010**      **Central User Manager initialization failed with error : {0}**
- ISS.0024.0011**      **Not able to load the {0} Role/Group.**
- ISS.0024.0013**      **Integration Server cannot add group to ACL because the required parameter "{0}" is not supplied.**

<b>ISS.0024.0014</b>	<b>Integration Server cannot add group "{0}" to ACL "{1}" because ACL "{1}" is not defined.</b>
<b>ISS.0024.0015</b>	<b>Integration Server cannot add group "{0}" to ACL "{1}" because group "{0}" is not found.</b>
<b>ISS.0024.0018</b>	<b>Integration Server failed to add group "{0}" to ACL "{1}" because of exception: {2}.</b>
<b>ISS.0025.0009E</b>	<b>Integration Server could not initialize the cache manager. Stopping Integration Server initialization. Use the server log and error log to diagnose and correct the problem.</b>
<b>Explanation</b>	This error occurs when Integration Server is configured to be in a cluster and cannot connect to the Terracotta Server Array (TSA). This could happen because the TSA URL in your cluster configuration is incorrect, the TSA is offline, or because there is a network problem.
<b>Action</b>	(1) Verify that the Terracotta Server Array is available and accepting connections. (2) If it is, start the server in safe mode by including the "-safeboot" argument in the command line. On the Settings > Clustering page of Integration Server Administrator, check that the Terracotta Server Array URL value is correct. (3) Make sure the network configuration of the host is correct and there are no problems with your network.
<b>ISS.0025.0034U</b>	<b>Dispatcher could not be shutdown: {0}</b>
<b>Explanation</b>	Integration Server encountered a serious internal error while shutting down.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0025.0035</b>	<b>Dispatcher could not be started: {0}</b>
<b>ISS.0025.0040I</b>	<b>FIPS mode initialized</b>
<b>Explanation</b>	Integration Server is operating under Federal Information Processing Standards.
<b>Action</b>	No action is required.
<b>ISS.0025.0041I</b>	<b>FIPS mode not initialized</b>
<b>Explanation</b>	Integration Server is not operating under Federal Information Processing Standards.
<b>Action</b>	No action is required.

- ISS.0025.0042S**      **FIPS mode could not be initialized. Shutting down server: {0}**  
**Explanation**      An error was encountered during initialization of FIPS mode operation.  
**Action**              Contact Software AG Global Support. Be prepared to provide configuration information related to security provider and FIPS mode.
- ISS.0025.0043S**      **Integration Server started in Safe Mode**  
**Explanation**      Integration Server is operating in safe mode either because it was started using the safeboot switch or because there were problems with the master password. When running in safe mode, Integration Server is not connected to any external resources, except the server's own external repository, and you cannot update any passwords. If it is a master password problem, there will be other messages logged that indicate that there was a master password problem.  
**Action**              If you intended to start the Integration Server in safe mode, then no action is required. If the Integration Server automatically started in safe mode due to a master password problem, see the webMethods Integration Server Administrator documentation.
- ISS.0025.0046**      **Monitoring API could not be initialized. JmsUrl = {0}. Value must be supplied for JmsUrl.**
- ISS.0025.0047**      **Monitoring API could not be initialized because of following exception. Check JMS Provider. {0}**
- ISS.0025.0048**      **Monitoring API could not be initialized. Check JMS Provider.**
- ISS.0025.0050**      **The JCE Unlimited Strength Jurisdiction Policy File was not found. Please install it.**
- ISS.0025.0053**      **Error encountered while disabling Monitoring API.**
- ISS.0025.0054**      **Fabric Agent initialization failed.**
- ISS.0025.0056**      **FIPS could not be initialized because the JCE Unlimited Strength Jurisdiction Policy File was not found. Shutting down Integration Server.**

---

<b>ISS.0025.0058</b>	<b>Error reading system level information: {0}</b>
<b>ISS.0025.0059W</b>	<b>Error initializing cluster node name: {0}</b>
<b>Explanation</b>	The specified cluster node name is an empty node name.
<b>Action</b>	Specify a non-empty cluster node name.
<b>ISS.0025.0060W</b>	<b>Falling back on the fully qualified domain name as the cluster node name, cluster node name is :{0}</b>
<b>Explanation</b>	Integration Server is using the default cluster node name for the machine because the cluster node name is empty or not provided.
<b>Action</b>	No action is required.
<b>ISS.0025.0061E</b>	<b>The logical name for the cluster node is not correct: {0}</b>
<b>Explanation</b>	The name for the cluster node is not valid. The logical host name you specify must be unique within the cluster and cannot contain a semicolon (;).
<b>Action</b>	Specify a unique logical name to identify the Integration Server instance in the cluster.
<b>ISS.0025.0062CC</b>	<b>Web services stack could not be initialized. Shutting down server: {0}</b>
<b>Explanation</b>	Integration Server encountered an error while initializing the Web services stack. Typical reasons are:  1) Loading of axis2.xml file located in Integration Server_directory/config/wss or Integration Server_directory/config/wssClient/conf folders failed because the file has been modified.  2) Integration Server failed to initialize the policy manager for the Web service.
<b>Action</b>	If you have modified the axis2.xml file located in Integration Server_directory/config/wss or Integration Server_directory/config/wssClient/conf folders, make sure that the changes made are correct. For all other reasons, refer to the details listed in the error message and respond accordingly.
<b>ISS.0025.0063E</b>	<b>EDA Manager initialization failed: {0}</b>
<b>Explanation</b>	The EDA Manager did not initialize during Integration Server start up.
<b>Action</b>	Review the exception returned with the error message to determine why the EDA Manager did not initialize.

<b>ISS.0025.0064E</b>	<b>EDA Manager initialized.</b>
<b>Explanation</b>	The EDA Manager initialized successfully.
<b>Action</b>	No action required.
<b>ISS.0025.0065W</b>	<b>Encountered an error while disabling listeners. Proceeding with server shutdown.</b>
<b>Explanation</b>	An error occurred while shutting down Integration Server. If the logging level for logging facility 0025, Initialization, is set to Debug or higher, the server log will include a stack trace with more details about the error.
<b>Action</b>	No action is required. Integration Server will shut down as requested.
<b>ISS.0025.0066W</b>	<b>Encountered an error while suspending triggers. Proceeding with server shutdown.</b>
<b>Explanation</b>	An error occurred while shutting down Integration Server. If the logging level for logging facility "0025 Initialization" is set to Debug or higher, the server log will include a stack trace with more details about the error.
<b>Action</b>	No action is required. Integration Server will shut down as requested.
<b>ISS.0025.0070C</b>	<b>Integration Server detected files in config/work directory which suggests unapplied configuration changes.</b>
<b>Explanation</b>	When saving changes to configuration files, Integration Server first saves the configuration changes in a temporary file in the IntegrationServer_directory/instances/instanceName/config/work directory. After saving the changes in a temporary file, Integration Server moves the temporary file to the actual configuration file. This ensures that if unexpected behavior occurs before the configuration changes are initially saved to the temporary file, only the temporary file is impacted. The actual configuration file is not corrupted. If Integration Server detects files in in the IntegrationServer_directory/instances/instanceName/config/work, it suggests that changes to a configuration file were not saved to the temporary file and that, therefore, the changes were not made to the actual configuration file.
<b>Action</b>	Use the contents of the IntegrationServer_directory/instances/instanceName/config/work directory to determine which configuration files were in the process of being changed. Decide whether or not you want to redo the changes to the configuration files. Delete the files under the directory and redo the configuration change if you so choose.
<b>ISS.0026.0002E</b>	<b>Failure while loading service {0}: {1}</b>
<b>Explanation</b>	Integration Server failed to install, enable, or reload the package because it could not load a service in the package into its namespace.
<b>Action</b>	Examine the error message to determine the problem service. Usually this error occurs when a Java service was not compiled before loading the package.

---

ISS.0026.0005	<b>Flow service could not be registered with the server: folder.servicename may already exist.</b>
ISS.0026.0006	<b>Warning missing type name while loading service {0}</b>
ISS.0026.0007	<b>Warning missing type name in operation {0} while loading service {1}</b>
ISS.0026.0008E	<b>Error: Exception serializing Flow Service {0}</b>
<b>Explanation</b>	Integration Server encountered an internal error with a flow service.
<b>Action</b>	Contact Software AG Global Support.
ISS.0026.0009E	<b>Error: unknown flow operation type for node:{0} in file:{1}</b>
<b>Explanation</b>	Integration Server encountered an internal error with a flow service.
<b>Action</b>	Contact Software AG Global Support.
ISS.0026.0010	<b>Warning: {0} Operation with no body in service {1}</b>
ISS.0026.0011	<b>Warning: {0} Operation missing service name in {1}</b>
ISS.0026.0012W	<b>Warning: Flow Branch Operation must have switch name or use conditional labels in {0}</b>
ISS.0026.0013	<b>Warning: Flow Branch Operation cannot have switch name and use conditional labels in {0}</b>
ISS.0026.0014	<b>Warning: {0} Operation missing target path in {1}</b>
ISS.0026.0015	<b>Warning: {0} Operation missing source path name in {1}</b>
ISS.0026.0016	<b>Warning: Flow Map Delete Operation missing field name in {0}</b>

<b>ISS.0026.0017</b>	<b>The HTTP URL alias could not be registered by the service {0}. "{1}" is already registered as an alias for the path: {2}</b>
<b>ISS.0026.9101E</b>	<b>Missing flow.xml</b>
<b>Explanation</b>	The flow.xml file does not exist. When a flow service is created, Integration Server creates a flow.xml file and a node.ndf file in the IntegrationServer\packages\packageName\ns\folderName directory that corresponds to the package and folder in which the flow service was created.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0026.9102E</b>	<b>Read only {0}</b>
<b>Explanation</b>	The flow.xml file cannot be updated because it is read-only.
<b>Action</b>	Navigate to the directory of the flow.xml file and make it a writable file.
<b>ISS.0026.9103E</b>	<b>Unable to write to flow.xml</b>
<b>Explanation</b>	An exception occurred while writing to the flow.xml file.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0026.9104E</b>	<b>Missing class {0}</b>
<b>Explanation</b>	The specified Java class cannot be found. This error is returned by the JVM.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0026.9105E</b>	<b>Method {0} is not defined with the proper signature</b>
<b>Explanation</b>	The signature of the Java service does not have a return type of void.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0026.9106E</b>	<b>No method {0} in class {1}</b>
<b>Explanation</b>	The service is to be supported by a specific method in a class. However, the loaded class does not contain the specified method.
<b>Action</b>	Make sure the class contains the method that you want to use to support the service.

---

<b>ISS.0026.9107E</b>	<b>Method {0} is unexpectedly null</b>
<b>Explanation</b>	Method defined to support the invoked service is null.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0026.9108E</b>	<b>Unable to create service; Service name missing</b>
<b>Explanation</b>	The service cannot be created because the service name is missing. Integration Server can only create and register services that have a name.
<b>Action</b>	Make sure to specify a name for the service.
<b>ISS.0026.9109E</b>	<b>Already registered in {0}</b>
<b>Explanation</b>	An identically named element already exists in another package. The fully qualified element name must be unique across Integration Server. Fully qualified element names use the format: folder.subfolder.subfolder:elementName
<b>Action</b>	Provide a different name for the element.
<b>ISS.0026.9110E</b>	<b>{0} : Name already used by another service type in {1} package</b>
<b>Explanation</b>	Integration Server cannot save or register the service because a service with that name already exists in the package.
<b>Action</b>	Specify a different name for the service.
<b>ISS.0026.9111E</b>	<b>Unable to register service; Package {0} is not enabled</b>
<b>Explanation</b>	An attempt was made to register a service in a disabled package. A service can be registered in an enabled package only.
<b>Action</b>	Enable the package and then attempt to register the service.
<b>ISS.0026.9201E</b>	<b>Unknown service: {0}</b>
<b>ISS.0027.0001W</b>	<b>nCipher Hardware accelerator not available</b>
<b>Explanation</b>	An error occurred while accessing the nCipher hardware.
<b>Action</b>	Turn the "0027 Server Configuration" logging facility up to TRACE on the Settings > Logging > Server Logger page of the Integration Server Administrator and try again. See the details of the error in the server log.

- ISS.0028.0002 Packages directory missing or corrupted
- ISS.0028.0003 Unable to copy the original package manifest file: {0}
- ISS.0028.0006 Unable to load {0} package (possibly due to circular dependencies)
- ISS.0028.0007 This package requires {0} package (Version {1}) to load
- ISS.0028.0008 Warning! Loading package from backup manifest file
- ISS.0028.0009 Unable to read manifest file for {0} package
- ISS.0028.0010 Unknown service type ({0}) in {1} package
- ISS.0028.0011 Unable to write package manifest file: {0}
- ISS.0028.0013 Startup service exited with the following error: {0}
- ISS.0028.0014 Startup service {1} was not found in {0} package
- ISS.0028.0016 Shutdown service exited with the following error: {0}
- ISS.0028.0017 Shutdown service {1} was not found in {0} package
- ISS.0028.0018 Server could not update the node definition file. Changes to the package were not saved.
- ISS.0028.0020 Unable to read node definition file

---

ISS.0028.0021	Server could not update the node subdirectory. Changes to the package were not saved.
ISS.0028.0022	Unable to locate class: {0}
ISS.0028.0023	Could not delete service
ISS.0028.0024	Invalid Package License key for Package: {0}
ISS.0028.0025	Unable to save Package Key for Package: {0}
ISS.0028.0026E	<b>Invalid or corrupt namespace plug-in configuration found in {0} package</b>
<b>Explanation</b>	Integration Server could not read plug-in configuration information from the nsplugins.cnf file associated with the indicated package.
<b>Action</b>	Contact Software AG Global Support.
ISS.0028.0027	Namespace plug-in type name {0} in package {1} conflicts with existing type
ISS.0028.0028	Cannot create namespace factory class {0} in package {1}: {2}
ISS.0028.0029	Namespace factory class invalid type {0} in package {1}
ISS.0028.0030	Error: Will not load deprecated service type ({0}) in service {1} in package {2}
ISS.0028.0035	Package {0} has failed to load.
ISS.0028.0036	Document type {0} has failed to load. Duplicate Broker document type name {1} is also referenced by {2}

- ISS.0028.0038**      **Error loading {0} : Name already used by another item in package {1}**
- ISS.0028.0039E**      **Failure while loading document type {0}: {1}**  
**Explanation**      Integration Server failed to load the document type into the namespace because another document type with the same name was already being loaded into the Integration Server namespace.  
**Action**              Examine the error message to determine the problem document types. Check both document types to make sure they have different names. If they have the same name and both need to be loaded into the namespace, rename one and try again.
- ISS.0028.0040E**      **Failure while loading schema {0}: {1}**  
**Explanation**      Integration Server failed to load the schema into the namespace because another schema with the same name was already being loaded into the Integration Server namespace.  
**Action**              Examine the error message to determine the problem schemas. Check both schemas to make sure they have different names. If both need to be loaded into the namespace, rename one and try again.
- ISS.0028.0041E**      **Failure while loading element {0}: {1}**  
**Explanation**      Integration Server failed to load the element into the namespace because another element with the same name was already being loaded into the Integration Server namespace.  
**Action**              Examine the error message to determine the problem elements. Check both elements to make sure they have different names. If both need to be loaded into the namespace, rename one and try again.
- ISS.0028.0043**      **Error unregistering node {0}: {1}**
- ISS.0028.0044W**      **Invalid classpath entry: {0}**  
**Explanation**      An I/O error occurred when Integration Server tried to access the file system to resolve the canonical name of the directory in which the file exists.  
**Action**              Check the file system for errors, such as problems with permissions and cyclical links.
- ISS.0028.0045E**      **Failed to install package {0}. Another package exists with the name {1}**  
**Explanation**      Integration Server was unable to install a package because a package with the same name already exists on the Integration Server.  
**Action**              Rename one of the packages, either the existing package or the one you are trying to install. Note that case does not matter; Integration Server considers "ABC" the same name as "abc".

---

<b>ISS.0028.0046E</b>	<b>Unable to load package replication passwords from {0}</b>
<b>Explanation</b>	Integration Server encountered an error while loading the indicated class.
<b>Action</b>	Check the audit log for messages about the underlying cause of the exception.
<b>ISS.0028.0047E</b>	<b>Unable to save package replication passwords to {0}</b>
<b>Explanation</b>	Integration Server encountered an error while loading the indicated resource.
<b>Action</b>	Check the Audit log for messages about the underlying cause of the exception.
<b>ISS.0028.0048</b>	<b>Failed to read class {0} from input stream</b>
<b>ISS.0028.0049</b>	<b>Unable to locate resource {0}</b>
<b>ISS.0028.0051E</b>	<b>Task Scheduler startup service exited with the following error: {0}</b>
<b>Explanation</b>	Integration Server encountered an error while executing the scheduler startup service task.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0028.0052E</b>	<b>Task Scheduler startup service {1} was not found in {0} package</b>
<b>Explanation</b>	The package startup process could not locate the service named in the message.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0028.0055</b>	<b>Caching of package classes is disabled due to the following error for file [{0}]: {1}</b>
<b>ISS.0028.0056</b>	<b>The post-initialization startup service {0} threw an exception: {1}. See the error log for the full stack trace.</b>
<b>ISS.0028.0057</b>	<b>Failure while registering HTTP URL alias "{0}" for the package {1}. Already registered as an alias for the path: {2}</b>
<b>ISS.0028.0058</b>	<b>Failure while registering HTTP URL alias "{0}" for the package {1}. Already registered by package {2} as an alias for the path: {3}</b>

- ISS.0028.0059**      **Failure while registering HTTP URL alias "{0}". Already registered as an alias for the path: {1}**
- ISS.0028.0060**      **Failure while registering HTTP URL alias "{0}". Already registered by package {1} as an alias for the path: {2}**
- ISS.0028.0061E**      **Unable to load system package {0} due to dependency on non-system packages.**  
**Explanation**      Integration Server cannot load the specified system package because it depends on a non-system package. System packages are pre-defined packages that are part of the Integration Server product (for example, WmPublic). A system package can have dependencies on other system package(s) only.  
**Action**              Using Designer, edit the package dependencies for the specified system package to remove the dependency on the non-system package.
- ISS.0028.9999W** **Error message – Unable to load the REST resource with URL template {0}, HTTP method(s) {1}, and service {2} because the URL template contains either illegal or unsupported characters.**  
**Explanation**      The information you have specified for configuring the REST resource contains either illegal or unsupported characters.  
**Action**              Update the REST resource configuration to not include illegal or unsupported characters.
- ISS.0033.0001**      **Inactive server {0} was removed from cluster {1}**
- ISS.0033.0100**      **If any multicast setting is supplied (Discovery Address, Discovery Port, Time To Live), they must all be supplied.**
- ISS.0033.0103E**      **Could not open the session cache. {0}**  
**Explanation**      Integration Server encountered an internal error.  
**Action**              Contact Software AG Global Support.
- ISS.0033.0104E**      **Could not add server to the cluster. {0}**  
**Explanation**      Integration Server failed to add a server to the cluster.  
**Action**              Make sure that the server repository is running and that the connection to other servers is valid.

---

ISS.0033.0108	<b>Could not remove server from cluster. {0}</b>
ISS.0033.0114E	<b>Failed to add server statistics to the cluster cache. {0}.</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
ISS.0033.0124E	<b>Local Address</b>
<b>Explanation</b>	Integration Server failed to remove expired sessions from the Repository. This is an internal error.
<b>Action</b>	Contact Software AG Global Support.
ISS.0033.0128	<b>Unable to save settings to the server's configuration file.</b>
ISS.0033.0143	<b>Please restart the server to make the new settings take effect.</b>
ISS.0033.0144	<b>Changes not saved: {0} is required.</b>
ISS.0033.0146	<b>Evaluating host {0} to receive Session Document.</b>
ISS.0033.0147	<b>Register Session Document handler with host {0}.</b>
ISS.0033.0148	<b>Received unknown special document. Body = &lt;&lt;{0}&gt;&gt;.</b>
ISS.0033.0149	<b>Changes not saved. Invalid value. {0} must be an integer.</b>
ISS.0033.0150	<b>Changes not saved. Invalid Well Known Address. If either host or port is supplied, both must be supplied. host={0}, port={1}.</b>
ISS.0033.0151U	<b>Communication with Terracotta Server Array has been lost.</b>
<b>Explanation</b>	During server startup, Integration Server detected a problem with its configuration that will prevent it from being part of a cluster.
<b>Action</b>	Check the Clustering and Repository settings for your Integration Server. Refer to the webMethods Integration Server documentation for more information about clustering. If you cannot determine the cause of the problem, contact Software AG Global Support.

<b>ISS.0033.0153E</b>	<b>Could not obtain a handle to ConnectionManager.</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0033.0154E</b>	<b>Could not save session {0} to the session cache. {1}.</b>
<b>Explanation</b>	Integration Server failed to persist the indicated session to the Repository. This is an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0033.0155E</b>	<b>Could not create local session {0} from the cached session values. {1}.</b>
<b>Explanation</b>	An Integration Server in a cluster tried to update a session object, but was unable to find it. This in an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0033.0156E</b>	<b>Cluster Invoke did not complete successfully. Cluster Synchronization feature is not configured.</b>
<b>Explanation</b>	After a trigger configuration update, Integration Server attempted to apply the change to other Integration Servers in the cluster, but was unable to. The most likely reason is that the Cluster Synchronization feature has not been properly configured.
<b>Action</b>	Review the cluster synchronization for rigger management text in the webMethods Integration Server documentation for instructions on configuring your cluster to propagate trigger changes to other Integration Servers in the cluster.
<b>ISS.0033.0159</b>	<b>The TSA URL must be specified on the Settings &gt; Clustering page in order to join a cluster. Clustering has been disabled. This server is running in stand-alone mode.</b>
<b>ISS.0033.0161</b>	<b>CLUSTERING DISABLED: Could not create or join distributed clustering cache "{0}". This server is NOT a member of a cluster.</b>
<b>ISS.0033.0162</b>	<b>The Cluster Name can contain only the following characters: alphanumeric, dashes, underscores, and colons.</b>
<b>ISS.0033.0163</b>	<b>Cache configuration is invalid. Settings were not saved: {0}</b>

<b>ISS.0033.0164</b>	<b>The ISInternal functional alias on the JDBC Pools page must be configured to use an external database in order to enable clustering.</b>
<b>ISS.0033.0167</b>	<b>The ISInternal functional alias on the JDBC Pools page must be configured to use an external database in order to join a cluster. Clustering has been disabled. This server is running in stand-alone mode.</b>
<b>ISS.0033.0169</b>	<b>Logical cluster node name, {0}, is not valid.</b>
<b>Explanation</b>	A cluster node name is either empty or null. Integration Server detects invalid cluster node names at server initialization or when someone attempts to pin a scheduled task to cluster node with an invalid name.
<b>Action</b>	Provide a non-empty cluster node name for the cluster node.
<b>ISS.0033.0181I</b>	<b>Cluster name cannot contain any of these characters: ? [ ] / = + &lt; &gt; ; " , *   ^ @</b>
<b>ISS.0033.0182I</b>	<b>Cluster name cannot start with a '.' or end with a space.</b>
<b>ISS.0033.0183I</b>	<b>Cluster name cannot be an operating system device name.</b>
<b>ISS.0033.0184I</b>	<b>Cluster name cannot be null or empty.</b>
<b>ISS.0033.0186W</b>	<b>Statistics polling time set to 60 seconds because clustering is configured.</b>
<b>Explanation</b>	Integration Server uses a value of 60 for the statistics polling time because the <code>watt.server.stats.pollTime</code> server configuration parameter is set to a value less than or equal to 0 (zero) or greater than 60. When clustering is configured, <code>watt.server.stats.pollTime</code> must be greater than 0 and less than or equal to 60.
<b>Action</b>	Set <code>watt.server.stats.pollTime</code> to value greater than 0 (zero) but less than or equal to 60.
<b>ISS.0035.0002</b>	<b>Initial log rotation interval could not be set: {0} ms in not valid</b>
<b>ISS.0035.0004</b>	<b>Returned {0} lines while requested for {1} number of lines for error logs.</b>

<b>ISS.0036.0002E</b>	<b>Errors occurred invoking URL {0}</b>
<b>Explanation</b>	A client application using the Java API did one of the following:  1) Tried to invoke the indicated folder or service name, but specified the wrong folder/service name.  2) Specified invalid certificates when setting up the SSL connection to the Integration Server.
<b>Action</b>	Examine the error stack trace to determine which exception was thrown. If it is a MalformedURLException, check the folder/service name provided in the API call and make sure that you specified the fully qualified service name. If it is a CertificateException, an IOException, or an InvalidKeyException, check the certificates provided and make sure that they are valid.
<b>ISS.0036.0004</b>	<b>Error occurred while pinging server: {0}</b>
<b>ISS.0036.0005</b>	<b>Error occurred while disconnecting from server: {0}</b>
<b>ISS.0036.0009E</b>	<b>Ping Failed to server: {0}</b>
<b>Explanation</b>	A client application performed a periodic ping of a remote Integration Server. The ping resulted in an exception.
<b>Action</b>	Verify that the remote Integration Server is up and running. In addition, verify that there is network connectivity between the two servers.
<b>ISS.0051.0002E</b>	<b>Error: {0}</b>
<b>Explanation</b>	Integration Server failed to add a port, remove a port, or edit an existing port because it could not save ports properties to <IntegrationServer_dir>/config/port.cnf.
<b>Action</b>	Examine the port.cnf file to make sure that it is not corrupt and not Read-Only. If the file is corrupt, you may need to remove the file and restart Integration Server. After you do this, you can re-add ports to the Integration Server.
<b>ISS.0051.0003</b>	<b>Port {0} already registered</b>
<b>ISS.0051.0005</b>	<b>Unable to unregister port {0}</b>

---

ISS.0051.0008	<b>Listener {0} was denied access to service {1}</b>
ISS.0053.0002	<b>Access denied for user {0} on port {1} from {2}.</b>
ISS.0053.0003	<b>Dispatch caught exception in run loop: {0}</b>
ISS.0053.0005	<b>Dispatch caught exception while trying to send response: {0}</b>
ISS.0053.0006S	<b>(tid={0}) Enterprise Gateway Server encountered the error "{1}" while handling a request from client "{2}" at request URL "{3}".</b>
<b>Explanation</b>	Enterprise Gateway Server experienced an internal error while handling the request.
<b>Action</b>	If the issue persists, contact the system administrator.
ISS.0053.0008I	<b>(tid={0}) Attempting to forward the request to the Internal Server again because the original attempt failed with exception "{1}". The retry count is {2} and the request URL is "{3}".</b>
<b>Explanation</b>	Enterprise Gateway Server failed to transmit the client request to the Internal Server due to the indicated network exception. The server will automatically try to send the request again. If the retry attempts fail, the server will log a message and fail the client request.
<b>Action</b>	The action you take depends on the exception issued. Look at the exception message for specific information.
ISS.0053.0009W	<b>(tid={0}) Enterprise Gateway Server encountered an I/O error while writing the Internal Server's response back to the client at "{1}". The request URL is "{2}".</b>
<b>Explanation</b>	An input/output error occurred between Enterprise Gateway Server and the Internal Server.
<b>Action</b>	If the issue persists, contact the system administrator.
ISS.0053.0010E	<b>(tid={0}) Enterprise Gateway Server encountered error "{1}" while handling the request. The server is unable to retry the request at this time. The retry count is {2}.</b>
<b>Explanation</b>	Enterprise Gateway Server experienced an internal error while handling the request.
<b>Action</b>	If the issue persists, contact the system administrator.

**ISS.0053.0011W** (tid={0}) Enterprise Gateway Server is stopping attempts to retry the request because the content length "{1}" of the retry request does not match the content length "{2}" of the original request. The retry count is {3}.

**Explanation** Enterprise Gateway Server could not complete the request for the reason indicated.

**Action** If the issue persists, contact the system administrator.

**ISS.0053.0012S** Access is denied for user "{0}" on port {1} from client "{2}" through Enterprise Gateway "{3}".

**Explanation** Incorrect credentials were specified while connecting to the Internal Server through the Enterprise Gateway.

**Action** Supply valid credentials.

**ISS.0053.0013** (tid={0}) API Gateway encountered an I/O error while responding to a request from the client at "{1}". The request URL is "{2}".

**Explanation** API Gateway cannot respond to the specified client request because of an I/O error.

**Action** Retry the request. If the issue persists, contact your system administrator.

**ISS.0053.0014** (tid={0}) API Gateway encountered the error "{1}" while handling a request from the client. The server is unable to retry the request at this time. The retry count is {2}.

**Explanation** The server is unable to retry the request after the retry count exceeded the predefined threshold.

**Action** Contact your system administrator.

**ISS.0053.0016** (tid={0}) API Gateway encountered an error while handling a request from client "{1}" at the request URL "{2}".

**Explanation** API Gateway encountered an error while handling the specified client request.

**Action** Retry the request. If the issue persists, contact your system administrator.

**ISS.0053.0017** Access denied for user "{0}" on port {1} from client "{2}" through API Gateway "{3}".

**Explanation** The current user cannot access API Gateway on the specified port because of not having the proper ACLs.

**Action** Check the ACLs for the current user. Ensure that the user has the correct ACLs to access API Gateway on the specified port.

---

<b>ISS.0054.0002E</b>	<b>CSRF attack detected. CSRF token is not present in the request URL: {0}</b>
<b>Explanation</b>	CSRF secure token is missing in the request URL, possibly due to a CSRF attack.
<b>Action</b>	If the request is valid, provide a valid CSRF secure token for the request.
<b>ISS.0055.0001E</b>	<b>Critical Java Service error</b>
<b>Explanation</b>	Integration Server encountered a serious internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0055.0002</b>	<b>Service setup {0} uses old-style signature</b>
<b>ISS.0055.0003</b>	<b>Initialization of Java Service {0} failed due to error: {1}</b>
<b>ISS.0056.0001</b>	<b>No SMTP server set. Cannot deliver mail</b>
<b>ISS.0056.0002</b>	<b>No recipient specified. Cannot deliver mail</b>
<b>ISS.0056.0003</b>	<b>Unable to send mail. *{0}</b> *
<b>ISS.0056.0004</b>	<b>Invalid SMTP port specified {0}. SMTP logging turned off</b>
<b>ISS.0059.0001U</b>	<b>Interrupted {0}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0070.0003W</b>	<b>Error encountered creating {0} listener on port {1}: {2}</b>
<b>Explanation</b>	An error was encountered while creating a listener.
<b>Action</b>	See the exception message for details about the error. Use the exception message to correct the error.
<b>ISS.0070.0004E</b>	<b>Failed to load configuration information</b>
<b>Explanation</b>	An error occurred while creating a listener from the settings in a package's listeners.cnf file.
<b>Action</b>	Go to the Settings > Logging > Server Log page in the Integration Server Administrator and increase the logging level for the "0070 Listeners" logging facility to TRACE. Reload the package that has the affected port or restart Integration Server. If the problem recurs, capture the exception written to the server log and send it to Software

AG Global Support. If you cannot connect to Integration Server because all ports are affected, contact Software AG Global Support and provide them with the listener.cnf file from the WmRoot package.

- ISS.0070.0006E**      **Failed to save configuration information**  
**Explanation**      An error occurred while saving listener settings.  
**Action**              Increase the logging level for the "0070 Listeners" logging facility to TRACE and try to save the listener settings again. If the problem recurs, capture the exception written to the server log and send it to Software AG Global Support.
- ISS.0070.0008W**      **Failed to bootstrap listener {0}**  
**Explanation**      The listener could not be started from the settings in the listeners.cnf file in a package's config directory. This file may have been manually edited or corrupted.  
**Action**              If you have a backup of the listeners.cnf file, restore it and reload the package or restart Integration Server.
- ISS.0070.0013W**      **Failed to start listener {0}. The following error was encountered: {1}**  
**Explanation**      Could not start the listener.  
**Action**              See error details in the message.
- ISS.0070.0025I**      **Access to {0} from host {1} was denied.**  
**Explanation**      The host with the specified IP address is unable to invoke services through the specified port. Possible reason for this could be the following:- The host with the specified IP address is in the deny list of the port. - In case of an Enterprise Gateway, the host is in the Enterprise Gateway deny list.  
**Action**              The following lists the actions you can take:- If the host with the specified IP address is in the deny list of the port, delete the host from the Deny List table in the Security > Ports > IP Access > <port> page in the Integration Server Administrator.- If the host with the specified IP address is in the Enterprise Gateway deny list, delete the IP address of the host from the Denied IP Address List table in the Security > Enterprise Gateway Rules > Denial of Service Options page in the Integration Server Administrator.
- ISS.0070.0027E**      **An I/O or Socket exception has occurred on {0}**  
**Explanation**      An error occurred while listening on a port.  
**Action**              See the exception message for details about the error.

---

<b>ISS.0070.0030W</b>	<b>Duplicate alias {2} encountered creating {0} listener on port {1}</b>
<b>Explanation</b>	When loading a package, Integration Server encountered a port alias that is the same as an existing port alias on Integration Server. The alias for a port must be unique across the Integration Server. Integration Server loads and enables the package but will not create the port with the duplicate alias.
<b>Action</b>	If you do not want the port created, you do not need to do anything. However, if you want the port to be created when the package is loaded, delete the existing port with that alias, create a new port that has the same properties as the just deleted port, and then reload the package containing the duplicate alias. Integration Server creates the port when the package is reloaded.
<b>ISS.0070.9001E</b>	<b>Invalid global service {0}</b>
<b>Explanation</b>	Invalid global service name provided for message processing. An e-mail listener was started. When the Integration Server tried to determine which service to use for message processing for this listener, the Integration Server detected a problem with the name of the service specified as the Global Service. The Global Service overrides the setting for the Default Service or the service specified in the e-mail message from the e-mail client. The problem could be that the service name is specified in the wrong case (service names are case sensitive) or that the specified service does not exist in the Integration Server's namespace.
<b>Action</b>	Examine the Global Service name provided. Make sure the name is in the correct case and that the service exists in the Integration Server's namespace.
<b>ISS.0070.9002E</b>	<b>Invalid default service {0}</b>
<b>Explanation</b>	An e-mail listener was started. When the Integration Server tried to determine which service to use for message processing for this listener, the Integration Server detected a problem with the name of the service specified as the Default Service. The Integration Server executes the Default Service if no service is specified in the e-mail message and no service is specified for the Global Service in the Email Client Configuration screen on the Integration Server Administrator. The problem could be that the service name is specified in the wrong case (service names are case-sensitive) or that the specified service does not exist in the Integration Server's namespace.
<b>Action</b>	Examine the Default Service name provided. Make sure the name is in the correct case and that the service exists in the Integration Server's namespace.
<b>ISS.0070.9003</b>	<b>Enable failed: Could not log into account {0}@{1}</b>

ISS.0070.9005	<b>Must provide Server Host</b>
ISS.0070.9006	<b>Must provide Server Type</b>
ISS.0070.9007	<b>Must provide User Name</b>
ISS.0070.9009	<b>Error starting to listen: {0}</b>
ISS.0070.9010	<b>A number must be provided for the port</b>
ISS.0070.9011E	<b>An invalid port number was provided</b>
<b>Explanation</b>	An administrator entered an invalid port number on a port configuration screen in the Integration Server Administrator.
<b>Action</b>	Specify a positive integer from 1 through 65534 for the port number.
ISS.0070.9012	<b>A port number must be provided</b>
ISS.0070.9013	<b>Private key not specified</b>
ISS.0070.9014	<b>Private key file does not exist</b>
ISS.0070.9015	<b>Listener is not enabled</b>
ISS.0070.9016	<b>A listener must be provided</b>
ISS.0070.9017	<b>Could not process certificate {0}</b>
ISS.0070.9018	<b>Peer certificate chain is not present</b>

---

ISS.0070.9019	Peer certificate is not in IS Certificate map
ISS.0070.9020	Peer certificate chain is not trusted
ISS.0070.9021	Invalid/unsupported listener type found, {0}
ISS.0070.9022	Invalid value for minimum threads, {0}
ISS.0070.9023	Invalid value for maximum threads, {0}
ISS.0070.9024	Invalid value for thread priority, {0}
ISS.0070.9025	Invalid min/max threads min={0} is greater than max={1}
ISS.0070.9026	Invalid thread priority {0}, minimum priority={1} and maximum priority={2}
ISS.0070.9027	Invalid port backlog queue value={0}
ISS.0070.9028	Invalid keep alive timeout value={0}
ISS.0070.9029	Invalid Enterprise Gateway internal port number {0}
ISS.0070.9030	Invalid port number {0}
ISS.0070.9031	Invalid maximum number of connections value {0}
ISS.0070.9039	Access denied to host: Hostname verification failed. The CN "{0}" in the subject DN of the certificate does not match the hostname "{1}".

- ISS.0070.9040**      **Aborting connection, Server Certificate purpose verification failed**
- ISS.0070.9041**      **Key alias is empty. Specify a key alias for the port or a global SSL key alias on the Security > Certificates > Edit page.**
- Explanation**      The port cannot be enabled because a key alias was not specified and there is not a default SSL key alias for the Integration Server.
- Action**            Before enabling the port, either define a key alias or specify a default SSL key alias for the Integration Server. The default SSL key alias is the keys alias specified during configuration of the SSL authentication credentials for the Integration Server. To use a defined key alias with the HTTPS port, specify that keystore alias in the create or update operation. To use the Integration Server's default SSL key alias with the HTTPS port, do not supply key alias information for the create or update operations.
- ISS.0070.9042**      **Keystore alias is empty. Specify a keystore alias for the port or a global SSL keystore alias on the Security > Certificates > Edit page.**
- Explanation**      The port cannot be enabled because a keystore alias was not specified and there is not a default SSL keystore alias for the Integration Server.
- Action**            Before enabling the port, either define a keystore alias or specify a default SSL keystore alias for the Integration Server. The default SSL keystore alias is the keystore alias specified during configuration of the SSL authentication credentials for the Integration Server. To use a defined keystore alias with a port, specify that keystore alias when creating or updating the port. To use the Integration Server's default SSL keystore alias with the port, do not supply keystore alias information when creating or updating the port.
- ISS.0070.9043**      **Invalid keypair specified. Public and private keypair moduli don't match**
- ISS.0070.9044E**      **Unsupported key type: {0}. The HTTPS/FTPS listener supports RSA keys only. Specify a key store that contains the appropriate RSA private key.**
- Explanation**      HTTPS or FTPS listener is configured with a keystore having DSA or EC key types. The HTTPS/ FTPS listener currently supports only RSA keys.
- Action**            Configure the HTTPS or FTPS listener to use a keystore that contains the RSA key.
- ISS.0070.9046E**      **Invalid character/s found in host name, {0}, in IP Access Deny list.**
- Explanation**      The specified host in the deny list contains one or more invalid characters.
- Action**            Correct the host name to remove the invalid characters. The host names or IP addresses can include upper and lower case alphabetic characters, digits (0-9), hyphens (-), and periods (.) and cannot include spaces. For IPv6, IP addresses can also include colons (:) and brackets ([])

---

<b>ISS.0070.9048E</b>	<b>Integration Server cannot find the file {0} specified for the server configuration parameter {1}.</b>
<b>Explanation</b>	The specified server configuration parameter uses a file to identify the allowed cipher suites; however, Integration Server cannot find the file.
<b>Action</b>	Make sure the server configuration parameter specifies the correct location of an existing file.
<b>ISS.0076.9021E</b>	<b>Error invoking the protocol buffer compiler. Error: {0}</b>
<b>Explanation</b>	An error has occurred while trying to compile a message descriptor for a publishable document type. At run time, the error text from the compiler replaces the {0} placeholder in the message. This error could occur under several circumstances including: when an IS document type is made publishable for the first time, when a publishable document type is edited and then saved, or when the publishable document type is synchronized with the Universal Messaging server.
<b>Action</b>	Use the error message to identify and correct the error. Then, repeat the action that led to the error. For example, if the error occurred when saving changes to a publishable document type, retry saving the publishable document type.
<b>ISS.0076.9022E</b>	<b>Protocol buffer coder cannot find descriptor in document type: {0}</b>
<b>Explanation</b>	An error occurred while encoding or decoding an instance of the specified publishable document type. Integration Server cannot find the message descriptor for the publishable document type. Integration Server creates a message descriptor for a publishable document type with an encoding type set to protocol buffers.
<b>Action</b>	Make sure the publishable document type is synchronized with the messaging provider.
<b>ISS.0081.9183E</b>	<b>All binders must contain the same operations</b>
<b>Explanation</b>	The binders in the Web service descriptor do not contain the same operations. In a service first provider Web service descriptor with multiple binders, the binders must contain the same operations.
<b>Action</b>	Modify the binders to contain the same operations.
<b>ISS.0081.9184W</b>	<b>The web service descriptor does not contain any operations</b>
<b>Explanation</b>	A provider Web service descriptor cannot be saved if it does not contain any operations.
<b>Action</b>	Add operations to the provider Web service descriptor.

<b>ISS.0081.9185E</b>	<b>Cannot resolve operation {0} in binding {1}; operation does not have a unique SOAPAction or a unique first element name.</b>
<b>Explanation</b>	The provider Web service descriptor could not be created because the operation in the specified binding does not have a unique SOAPAction value or the first part element in the operation's input message is not unique. If neither of these values are unique, Integration Server cannot match an incoming web service request with an operation.
<b>Action</b>	Modify the WSDL document so that operations within a binding have unique SOAPAction values or make sure operations with duplicate SOAPAction values have an input message in which the first part element is unique.
<b>ISS.0081.9186W</b>	<b>Web service name will change from: {0} to: {1}</b>
<b>Explanation</b>	<p>Changing the value of the Pre-8.2 compatibility mode property for a provider Web service descriptor results in a change to the value of the name attribute in the wsdl:service element in the associated WSDL document. Web service descriptors that run in pre-8.2 compatibility mode use the local name of the Web service descriptor as the service name. Web service descriptors that do not run in pre-8.2 compatibility mode use the fully qualified name of the Web service descriptor as the service name.</p> <p>For example, suppose that a Web service descriptor has the fully qualified name folder.myFolder:myWebService. If the Web service descriptor runs in pre-8.2 compatibility mode, in the WSDL document, the value of the name attribute in the wsdl:service element is "myWebService". If the Web service descriptor does not run in pre-8.2 compatibility mode, in the WSDL document, the value of the name attribute in the wsdl:service element is "folder.myFolder:myWebService".</p>
<b>Action</b>	Existing consumer Web service descriptors and Web service connectors created from an earlier version of the WSDL document are not affected by the service name change and will execute as expected. However, web service clients created on other platforms might be affected. If a web service client is affected by the name change, regenerate the client using the updated WSDL document.
<b>ISS.0081.9191W</b>	<b>The fault has a message part "{0}" defined by the type "{1}". Message parts in a fault must be defined by the element attribute instead of the type attribute.</b>
<b>Explanation</b>	The WSDL for the Web service descriptor contains a fault message part defined by the type attribute. To be deployed to the Web services stack in version 8.2 or later of Integration Server, the fault message part must be defined using the element attribute.
<b>Action</b>	To enable the WSDL for the Web service descriptor to be deployed to the Web services stack, modify the fault message part in the source WSDL used to create the Web service descriptor.

---

<b>ISS.0081.9192W</b>	<b>WS Security Handler has no effect when the Pre-8.2 compatibility mode property is false. To enforce WS Security attach WS Policies.</b>
<b>Explanation</b>	When a Web service descriptor is not running in pre-8.2 compatibility mode (i.e., the Pre-8.2 compatibility mode property is set to false), Integration Server does not execute the WS Security Handler. As a result, the WS Security Handler has no effect and WS Security will not be enforced.
<b>Action</b>	If you want to enforce WS Security, create the appropriate WS Policies and attach the WS Policies to the Web service descriptor.
<b>ISS.0081.9193W</b>	<b>WS Policies has no effect when the Pre-8.2 compatibility mode property is true.</b>
<b>Explanation</b>	When a Web service descriptor is running in pre-8.2 compatibility mode (i.e., the Pre-8.2 compatibility mode property is set to true), Integration Server does not enforce WS Policies attached to the Web service descriptor.
<b>Action</b>	If you want to enforce WS Policies (including those with WS-Security assertions), set the Pre-8.2 compatibility mode property to false. As an alternative, if you want to keep the Pre-8.2 compatibility mode property is set to true and still enforce WS Security policies, you can use the Integration Server WS Security facility. In this case, remove all WS Policies that you have attached to the Web service descriptor and attach the WS Security Handler. For more information about the WS Security Handler, see the Designer online help.
<b>ISS.0081.9205E</b>	<b>JMS Binders are not supported when Pre-8.2 compatibility mode is true.</b>
<b>Explanation</b>	One of the following situations occurred: the Pre-8.2 compatibility mode property was changed from false to true for a Web service descriptor that contains a binder with a Transport property set to JMS, a binder that specifies the JMS transport was added to a Web service descriptor that runs in compatibility mode (the Pre-8.2 compatibility mode property is set to true), or the Transport property for an existing binder was changed to JMS for a Web service descriptor that runs in compatibility mode. A Web service descriptor for which the Pre-8.2 compatibility mode property is set to true does not support binders with a JMS transport.
<b>Action</b>	If you want to keep the JMS binder, change the Pre 8.2 compatibility mode property from true to false. If you want to keep the Web Service descriptor in Pre 8.2 compatibility mode, delete any binders using the JMS transport or change the binder Transport property to a supported transport (HTTP or HTTPS). Then, save the modified Web service descriptor.
<b>ISS.0084.0001E</b>	<b>Invalid credentials</b>
<b>Explanation</b>	Integration Server validates any credentials (username/password or certificates) that are supplied by the client, and if those credentials fail to match any user known to Integration Server, Integration Server will return this exception back to the client.
<b>Action</b>	Supply the correct credentials.

<b>ISS.0084.9009W</b>	<b>Warning: CSRF secure token is not present in the request. If you still want to complete this request, click Continue.</b>
<b>Explanation</b>	CSRF token is missing in the request URL, possibly due to a CSRF attack.
<b>Action</b>	If the request is valid, click Continue to complete the request.
<b>ISS.0084.9010E</b>	<b>CSRF secure token is not present in the request.</b>
<b>Explanation</b>	CSRF token is missing in the request URL, possibly due to a CSRF attack.
<b>Action</b>	If the request is valid, provide a valid CSRF token for the request.
<b>ISS.0084.9101E</b>	<b>Access Denied</b>
<b>ISS.0085.9208E</b>	<b>Service first provider Web service descriptors cannot be refreshed.</b>
<b>Explanation</b>	An attempt was made to refresh a service first provider Web service descriptor. Only WSDL first provider Web service descriptors and consumer Web service descriptors can be refreshed.
<b>Action</b>	None.
<b>ISS.0085.9209E</b>	<b>Cannot refresh Web service descriptor. The Web service descriptor cannot be found in the Integration Server namespace.</b>
<b>Explanation</b>	A Web service descriptor cannot be refreshed because it does not exist in the Integration Server namespace.
<b>Action</b>	None.
<b>ISS.0085.9211E</b>	<b>Cannot roll back Web service descriptor to previously saved version.</b>
<b>Explanation</b>	An attempt to refresh a Web service descriptor failed. However, Integration Server could not roll back to the most recently saved version of the Web service descriptor and its associated assets. This can happen if Integration Server becomes unresponsive when rolling back the Web service descriptor.
<b>Action</b>	Delete the Web service descriptor and recreate it using the updated WSDL document. Note that any changes made to the Web service descriptor, such as new headers or faults, will be lost. Alternatively, if the Web service descriptor was checked into a version control system, check out the last checked in version of the Web service descriptor and then refresh the Web service descriptor

---

<b>ISS.0085.9212E</b>	<b>Cannot Save the refreshed Web service descriptor. Integration Server will rollback to the most recently saved versions of the Web service descriptor and its associated assets.</b>
<b>Explanation</b>	The WSDL file used to refresh the Web service descriptor contains or references an invalid schema.
<b>Action</b>	Use the information in the server log to determine why the schema is invalid. Correct the WSDL file or the associated XML Schema definition. Then, refresh the Web service descriptor.
<b>ISS.0085.9213E</b>	<b>Cannot refresh Web service descriptor. One or more operations cannot be merged. Integration Server will roll back to the most recently saved versions of the Web service descriptor and its associated assets.</b>
<b>Explanation</b>	As part of refreshing a Web service descriptor, Integration Server merges in changes made to existing services used as operations. One of the following can prevent Integration Server from merging the changes in successfully: - The contents or properties of an existing service could not be merged into the refreshed version of the service. - The ACL information could not be set for the refreshed service. - An existing service could not be locked. Integration Server will roll back to the most recently saved versions of the Web service descriptor and its associated assets.
<b>Action</b>	Contact Software AG Global Support. Obtain a copy of the server log before contacting support.
<b>ISS.0085.9214W</b>	<b>The {0} docTypes folder contained one or more user-defined document types used for headers. These document types were deleted when the Web service descriptor was refreshed.</b>
<b>Explanation</b>	The specified docTypes folder contains a document type used for a header in the Web service descriptor. This document type will be deleted upon refresh. When refreshing a Web service descriptor, Integration Server deletes the WSDName_docTypes folder and all elements contained in that folder and its subfolders. Integration Server will not recreate any assets manually added to the folder or its subfolders.
<b>Action</b>	Do not add any assets to any of the folders created automatically by Integration Server for a Web service descriptor including the WSDName_doctypes folder. If you added any assets to the folders, move the assets to another folder before refreshing the Web service descriptor.
<b>ISS.0085.9215W</b>	<b>The {0} docTypes folder contained one or more user-defined document types used for faults. These document types were deleted when the Web service descriptor was refreshed.</b>
<b>Explanation</b>	The specified docTypes folder contained a document type used for a fault in the Web service descriptor. This document type will be deleted upon refresh. When refreshing a Web service descriptor, Integration Server deletes the WSDName_docTypes folder and all elements contained in that folder and its subfolders. Integration Server will not recreate any assets manually added to the folder or its subfolders.

**Action** Do not add any assets to any of the folders created automatically by Integration Server for a Web service descriptor including the WSDName\_doctypes folder. If you added any assets to the folders, move the assets to another folder before refreshing the Web service descriptor.

**ISS.0085.9262** **No registered handler found for Header QName:{0}**

**Explanation** The WSDL you are using to create the Web service connector has a header defined, but a matching header handler is not registered in Integration Server.

**Action** Add a header handler with a QNAME matching the Document Universal Name to Integration Server, then create the Web service connector. If you do not have the appropriate header handler, you can continue the process and Developer will create the Web service connector without the header information.

**ISS.0085.9283** **Unknown ExtensibleElement "{0}" found in SOAPBinding "{1}"**

**Explanation** The WSDL used to create the Web service descriptor contains a binding element with a child other than SOAP 1.1 or SOAP 1.2. Integration Server does not support extensions to SOAP, such as sdk:binding (Microsoft SOAP-Toolkit extensions). Integration Server will process the valid portions of the SOAP 1.1 or SOAP 1.2 binding, but will skip processing of the unsupported extension.

**Action** Verify that the WSDL contains a valid SOAP 1.1 or SOAP 1.2 binding, and is usable without the extension.

**ISS.0085.9315E** **Binding {0} contains duplicate operation names {1}**

**Explanation** Web service descriptor cannot be generated. A binding in the WSDL document contains more than one operation with the same name.

**Action** Modify the WSDL document so that operation names are unique within a binding.

**ISS.0085.9317E** **Error occurred during export of the package {0}. Details : {1}**

**Explanation** Integration Server could not export the package because an error occurred during export.

**Action** Read through the details provided in the error message and take corrective steps.

**ISS.0085.9318E** **Invalid parameters passed. Make sure each required parameter is passed as an input to the service.**

**Explanation** Integration Server cannot export the assets because the required input parameters are not specified.

**Action** Specify all the required parameters.

---

<b>ISS.0085.9319E</b>	<b>Archive name passed "{0}" is invalid</b>
<b>Explanation</b>	The name of the archive contains illegal characters.
<b>Action</b>	Remove all illegal characters from the archive name.
<b>ISS.0085.9320E</b>	<b>Invalid service found; service {0} does not define any ports</b>
<b>Explanation</b>	The WSDL document contains a wsdl:service element that does not define any ports. A Web service descriptor cannot be created.
<b>Action</b>	Modify the WSDL document to include ports in the wsdl:service element.
<b>ISS.0085.9321E</b>	<b>Invalid port found; port {0} does not specify a binding</b>
<b>Explanation</b>	The WSDL document contains a wsdl:port element that does not specify a binding. A Web service descriptor cannot be created.
<b>Action</b>	Modify the WSDL document to include a binding for the port.
<b>ISS.0085.9322E</b>	<b>Invalid SOAP binding found; binding {0} does not contain all operations for corresponding portType {1}</b>
<b>Explanation</b>	The specified binding does not contain all of the operations declared in the specified portType.
<b>Action</b>	Modify the WSDL document so that the binding contains all of the operations declared in the specified portType.
<b>ISS.0085.9323W</b>	<b>Port alias for JMS Binder "{0}" set to "{1}". Ensure that this is the correct port alias.</b>
<b>Explanation</b>	When creating a WSDL first provider Web service descriptor, Integration Server uses the first JMS provider web service endpoint alias listed on the Settings > Web Service Endpoints page in Integration Server Administrator as the port alias.
<b>Action</b>	If you want to use a different JMS provider web service endpoint alias as the port alias, select the JMS binder and assign a different port alias.
<b>ISS.0085.9324E</b>	<b>Unable to create JMS Binder for binding {0}. There is not a defined JMS provider web service endpoint alias.</b>
<b>Explanation</b>	When creating a WSDL first provider Web service descriptor, Integration Server uses the first JMS provider web service endpoint alias listed on the Settings > Web Service Endpoints page in Integration Server Administrator as the port alias. If there is no defined JMS provider web service endpoint alias, Integration Server does not create the Web service descriptor.
<b>Action</b>	Create a JMS provider web service endpoint alias. Then create the WSDL first provider Web service descriptor.

- ISS.0085.9325E**      **Invalid parameter passed. {0} is a required parameter.**
- Explanation**      Integration Server cannot export the assets because the required input parameters are not specified.
- Action**              Specify all of the required parameters.
- 
- ISS.0085.9326E**      **Error occurred while exporting runtime configurations: {0}. For more information, see the Integration Server logs.**
- Explanation**      Deployer encountered an error while exporting runtime configurations: {0}.
- Action**              Check Integration Server log for more information.
- 
- ISS.0085.9327E,W**    **Unknown transport found in binding {0}. {1} is not a valid transport value.**
- Explanation**      The WSDL document used as the source for the Web service descriptor contains a binding with an invalid transport attribute. Integration Server will not create a WSDL first provider Web service descriptor when a binding transport is invalid. Integration Server will create a consumer Web service descriptor when a binding transport is invalid if the WSDL document contains other valid bindings.
- Action**              No action is required.
- 
- ISS.0085.9328E,W**    **No transport found in binding {0}. Valid transport value is required.**
- Explanation**      The WSDL document used as the source for the Web service descriptor contains a binding that does not specify a transport. Integration Server will not create a WSDL first provider Web service descriptor when a binding transport is missing. Integration Server will create a consumer Web service descriptor when a binding transport is missing if the WSDL document contains other valid bindings.
- Action**              If possible, determine the actual transport type and then edit the WSDL document to specify that transport for the specified binding.
- 
- ISS.0085.9329E,W**    **Unable to create JMS Binder for binding {0}. JMS Binders can be created using Designer only.**
- Explanation**      The source WSDL document for the Web service descriptor contains a SOAP JMS binding. Developer cannot be used to create a WSDL first provider Web service descriptor from a WSDL document with a SOAP JMS binding. Developer can be used create a consumer Web service descriptor from a WSDL document with a SOAP JMS binding if the WSDL document contains other valid SOAP HTTP bindings, but the resulting consumer Web service descriptor will not have a JMS binder.
- Action**              Use Designer to create the Web service descriptor.

---

<b>ISS.0085.9331E</b>	<b>Error occurred while deploying the asset: {0}. For more information, see the Integration Server logs.</b>
<b>Explanation</b>	Integration Server encountered an error while deploying the asset. Typical reasons for this error are: 1) Stream is already read. 2) An I/O error occurred. 3) Value for aclData input parameter is not provided. 4) Any other error that occurred during deployment.
<b>Action</b>	Read through the details provided in the error message and take corrective steps.
<b>ISS.0085.9333W</b>	<b>JVM "{0}" of the target Integration Server for installing package "{2}" is older than the recommended JVM "{1}".</b>
<b>Explanation</b>	The target Integration Server is running a JVM version that is older than the version recommended by the source package.
<b>Action</b>	Ensure that the target Integration Server is running the same or a later version of the JVM specified during release creation.
<b>ISS.0085.9334E</b>	<b>The version of target package cannot be null for a patch release.</b>
<b>Explanation</b>	The source package being installed is a patch release, but when the patch release was created, no version was specified for the target package.
<b>Action</b>	Specify a version for the target package when creating the patch release.
<b>ISS.0085.9335W</b>	<b>The target Integration Server version "{2}" and the Integration Server version "{1}" recommended by source package "{0}" are incompatible.</b>
<b>Explanation</b>	The target Integration Server version does not match the Integration Server version recommended by the source package.
<b>Action</b>	Ensure that the version of the target and source Integration Servers are the same.
<b>ISS.0085.9336W</b>	<b>Package "{2}" will not be deployed because the source package is a patch release and target package version: "{0}" does not match the required target package version: "{1}".</b>
<b>Explanation</b>	During installation of a patch release, Integration Server detected that the version of the target package is not the version required by the patch release.
<b>Action</b>	Install the correct version of the target package before applying the patch.
<b>ISS.0085.9337W</b>	<b>Package "{0}" will not be deployed because the source package is a patch release and the target package does not exist.</b>
<b>Explanation</b>	Integration Server could not install the package because the source package being installed is a patch release and the required package does not exist on the target server.
<b>Action</b>	The following lists the actions you can take: 1) Install the package in the target server before applying the patch. -OR- 2) Redefine the source package to a full release before deploying the package on the target server.

<b>ISS.0085.9338W</b>	<b>Package "{2}" will not be deployed because the version of source package: "{0}" is older than the version of target package: "{1}".</b>
<b>Explanation</b>	The package installed in the target server is of a later version than the source package being installed.
<b>Action</b>	Ensure that the version of the package on the target server is earlier than or the same as the package being installed.
<b>ISS.0085.9341E</b>	<b>Recursive invoke of wm.server.util:remoteInvoke service on a local server is not allowed.</b>
<b>Explanation</b>	You cannot invoke the wm.server.util:remoteInvoke service using the wm.server.util:remoteInvoke service recursively on a local server. Recursive invoke of wm.server.util:remoteInvoke service on a local server results in reduced thread availability and after sometime, Integration Server stops responding.
<b>Action</b>	Make sure that you are not invoking the wm.server.util:remoteInvoke service recursively on a local server.
<b>ISS.0085.9377E</b>	<b>Internal Error - Asset {0} does not exist</b>
<b>Explanation</b>	While using the local service development feature in Software AG Designer, an attempt to move, copy, or rename an IS asset, such as a flow service, java service, document type, or trigger, resulted in an internal error occurred. At run time, the {0} in the message is replaced with the name of the IS asset being moved, copied, or renamed.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0085.9380E</b>	<b>Invalid folder name {0}. Error : {1}</b>
<b>Explanation</b>	The specified folder name is invalid.
<b>Action</b>	Specify a valid folder name.
<b>ISS.0085.9381E</b>	<b>Folder {0} is not empty</b>
<b>Explanation</b>	The specified folder must be empty.
<b>Action</b>	Delete the contents of the specified folder or specify an empty folder.
<b>ISS.0085.9382E</b>	<b>Message addressing endpoint alias "{0}" of type "{1}" does not exist.</b>
<b>Explanation</b>	The specified message addressing endpoint alias does not exist.
<b>Action</b>	Ensure that the message addressing endpoint alias name that you specified is correct and that this endpoint alias exists.

---

<b>ISS.0085.9383E</b>	<b>Cannot delete message addressing endpoint alias "{0}" because it is referred to by the following provider endpoint aliases {1}</b>
<b>Explanation</b>	A Web service endpoint alias for a provider Web service descriptor is using the message addressing endpoint alias that you attempted to delete as a part of the Response Map. Integration Server can only delete a message addressing endpoint alias if it is not in use.
<b>Action</b>	Before deleting a message addressing endpoint alias, ensure that the endpoint alias is not associated with the Response Map of any provider Web service endpoint alias.
<b>ISS.0085.9385E</b>	<b>Reliable messaging sequence {0} not found.</b>
<b>Explanation</b>	No reliable messaging sequence for the specified internal Sequence Id was not found.
<b>Action</b>	Ensure that a valid Internal Sequence Id is specified.
<b>ISS.0085.9389E</b>	<b>Host Name must be only ASCII characters.</b>
<b>Explanation</b>	Host Name contains non-ASCII characters. Host Name must consist of only ASCII characters.
<b>Action</b>	Specify a valid host name consisting of only ASCII characters.
<b>ISS.0085.9390E</b>	<b>User Name must be only ASCII characters.</b>
<b>Explanation</b>	User Name contains non-ASCII characters. Host Name must consist of only ASCII characters.
<b>Action</b>	Specify a valid User Name consisting of only ASCII characters.
<b>ISS.0085.9391E</b>	<b>Port Number must be positive integer between 0 and 65535 (inclusive).</b>
<b>Explanation</b>	Port must be a positive integer.
<b>Action</b>	Specify a valid integer between 0 and 65535 (inclusive) for Port.
<b>ISS.0085.9392E</b>	<b>Password must be only ASCII characters.</b>
<b>Explanation</b>	Password contains non-ASCII characters. Password must consist of only ASCII characters.
<b>Action</b>	Specify a valid password consisting of only ASCII characters.

<b>ISS.0085.9393E</b>	<b>Proxy server alias {0} does not exist.</b>
<b>Explanation</b>	Proxy server alias does not exist.
<b>Action</b>	Specify a valid configured proxy server alias.
<b>ISS.0085.9394E</b>	<b>Protocol must be either HTTP or HTTPS or FTP or SOCKS.</b>
<b>Explanation</b>	The specified protocol is not valid. Protocol must be HTTP, HTTPS, FTP or SOCKS.
<b>Action</b>	Specify one of the following as the protocol: HTTP, HTTPS, FTP, or SOCKS.
<b>ISS.0085.9395E</b>	<b>Invalid FTP proxy type.</b>
<b>Explanation</b>	Invalid FTP proxy type. The FTP proxy type must be an integer within the range of 0 and 7 (inclusive).
<b>Action</b>	Specify an interger within the range of 0 to 7 (inclusive).
<b>ISS.0085.9396E</b>	<b>Proxy server alias contains illegal characters.</b>
<b>Explanation</b>	The Proxy server alias name is invalid because it contains invalid characters such as #&@^!%*:.\$/ \ \~;~+=)( ).{\><.
<b>Action</b>	Specify a proxy server alias name that does not contain the following characters: #&@^!%*:.\$/ \ \~;~+=)( ).
<b>ISS.0086.9063E</b>	<b>Missing required value: string</b>
<b>Explanation</b>	The string parameter is required but is either missing from the pipeline or is null.
<b>Action</b>	Make sure the string parameter is being supplied to the service and that the value of string is not null.
<b>ISS.0086.9263E</b>	<b>Specified path [{0}] is not on the [{1}] allowed list in the fileAccessControl configuration file</b>
<b>Explanation</b>	The specified path is not in the list of allowed directories and/or files for the specified parameter in the fileAccessControl.cnf file. For the pub.file services, Integration Server provides additional validation checks by ensuring that the paths supplied to the pub.file services are listed in the relevant parameter (allowedReadPath, allowedWritePath, or allowedDeletePath) in the fileAccessControl.cnf file. At run time, the {0} is replaced by the supplied path and the {1} is replaced with the parameter that is being checked in the fileAccessControl.cnf file.
<b>Action</b>	If the supplied path is listed for the specified parameter in the fileAccessControl.cnf, make sure that the supplied path does not contain any errors such as misspellings, misplaced punctuation, and so forth. Keep in mind that path names are case-sensitive on a UNIX-based system. Additionally, note that if the path includes a semicolon, the two backslashes that must precede the semicolon for a parameter in the fileAccessControl.cnf file do not need to be included in the path supplied to the input parameter of a pub.file service. If the specified path should be in the allowed list for

the specified parameter but is not, edit the parameter in the fileAccessControl.cnf file to include the path.

<b>ISS.0086.9287E</b>	<b>Applications cannot set the "{0}" field in the HTTP response header.</b>
<b>Explanation</b>	The input to the pub.flow:setResponseHeader service specifies a header field that cannot be set by an application.
<b>Action</b>	Change the input to the pub.flow:setResponseHeader service so that it does not specify a header field that cannot be set by an application.
<b>ISS.0086.9288E</b>	<b>Either "{0}" or "{1}" must be supplied</b>
<b>Explanation</b>	A value is required for one of the two indicated parameters.
<b>Action</b>	Supply the missing value.
<b>ISS.0086.9290E</b>	<b>Invalid JMS property name "{0}"; property name must contain only Java identifier part characters.</b>
<b>Explanation</b>	The property name specified as input to pub.flow:setResponseHeaders does not meet the syntax requirement for JMS properties as described in the Java Message Service standard.
<b>Action</b>	Modify the property name to meet the syntax requirements for JMS properties. Refer to the Java Message Service standard for information about syntax requirements for message properties.
<b>ISS.0086.9291E</b>	<b>Invalid JMS property name "{0}"; reserved word.</b>
<b>Explanation</b>	The property name specified as input to pub.flow:setResponseHeaders contains a reserved word as described in the Java Message Service standard.
<b>Action</b>	Modify the property name by removing the reserved word. Refer to the Java Message Service standard for information about reserved words for message properties.
<b>ISS.0086.9292E</b>	<b>Applications cannot set the "{0}" field in the JMS response header.</b>
<b>Explanation</b>	The input to the pub.flow:setResponseHeader service specifies a message header field that cannot be set by an application.
<b>Action</b>	Change the input to the pub.flow:setResponseHeader service so that it does not specify a header field that cannot be set by an application.

**ISS.0086.9293E**      **At least one of the parameters, "generateHeaderDocumentTypes", "generateBodyDocumentTypes" or "generateFaultDocumentTypes", must be set to true.**

**Explanation**      The "generateHeaderDocumentTypes", "generateBodyDocumentTypes", and "generateFaultDocumentTypes" parameters are all set to false while executing the pub.soap.handler:generateDocumentTypesFromWSDL service.

**Action**             Set the value of any one of these parameters to true.

**ISS.0086.9294E**      **If convertAllPackages is set to true, packageNames cannot be specified.**

**Explanation**      When convertAllPackages is set to true, the pub.ws.utils:setCompatibilityModeFalse service sets the Pre-8.2 compatibility mode property to false for each Web service descriptor in an enabled package. It is invalid to specify individual packages in packageNames as well.

**Action**             Either remove the specified value for packageNames or set convertAllPackages to false.

**ISS.0086.9295E**      **If convertAllPackages is set to false, packageNames must be specified.**

**Explanation**      When convertAllPackages is set to false, the packageNames parameter must specify the names of the packages that contain the Web service descriptors for which to change the Pre-8.2 compatibility mode value.

**Action**             Either specify packages in packageNames or set convertAllPackages to true.

**ISS.0086.9296E**      **Package {0} not enabled.**

**Explanation**      The specified package is not enabled. The pub.ws.utils:setCompatibilityModeFalse service can change Web service descriptors in enabled packages only.

**Action**             Enable the package.

**ISS.0086.9297E**      **Package {0} not found.**

**Explanation**      The packageNames parameter specifies a package that does not exist.

**Action**             Ensure that the package name is spelled correctly. Additionally, verify that package exists on the Integration Server.

**ISS.0086.9298E**      **Unable to lock Web service descriptor for editing.**

**Explanation**      The Pre-8.2 compatibility mode property cannot be changed because an error occurred while attempting to lock the Web service descriptor for editing.

**Action**             Determine what error prevents locking of the Web service descriptor by examining the lock properties of the Web service descriptor or by attempting to lock (or check out) the Web service descriptor. Either action should provide a detailed error message that you can use to resolve the error. Then either run the pub.utils.ws:setCompatibilityModeFalse service again or lock (check out) the Web

service descriptor and change the value of the Pre-8.2 compatibility mode property manually.

<b>ISS.0086.9299E</b>	<b>Web service descriptor is locked by another user.</b>
<b>Explanation</b>	The Pre-8.2 compatibility mode property cannot be changed because another user has the Web service descriptor checked out or locked for editing.
<b>Action</b>	Review the lock properties of the Web service descriptor to determine which user has it checked out or locked for editing. After the user unlocks (or checks in) the Web service descriptor, either run the <code>pub.utils.ws:setCompatibilityModeFalse</code> service again or lock (check out) the Web service descriptor and change the value of the Pre-8.2 compatibility mode property manually.
<b>ISS.0086.9309E</b>	<b>Could not release a lock of type {0} for key {1} in cache {2} contained within the cache manager {3}. Error:{4}</b>
<b>Explanation</b>	The specified lock type for the specified key, cache, and cache manager does not match the actual lock type held. This error also occurs if a release lock is called from a thread that did not lock the key.
<b>Action</b>	Specify the correct lock type or invoke the service from the same thread that acquired the lock.
<b>ISS.0086.9312E</b>	<b>Error while executing command {0}: {1}</b>
<b>Explanation</b>	Integration Server encountered an error while executing the command. Typical reasons are: 1) The session is invalid. 2) The command parameter is invalid. 3) The SFTP server is not reachable.
<b>Action</b>	Read through the details provided in the error message and take corrective steps.
<b>ISS.0086.9313E</b>	<b>Invalid session {0}</b>
<b>Explanation</b>	The session key that you specified is invalid.
<b>Action</b>	Ensure that session key is correct and that the session corresponding to this session key exists.
<b>ISS.0086.9314E</b>	<b>Session {0} expired.</b>
<b>Explanation</b>	The session key that you specified has expired.
<b>Action</b>	Adjust the session timeout value for this SFTP user alias according to your requirements. Once a session expires, you must create a new session.

<b>ISS.0086.9315E</b>	<b>Session {0} is in use. Integration Server does not support parallel command execution on a session.</b>
<b>Explanation</b>	You attempted to execute commands in parallel.
<b>Action</b>	Integration Server does not support parallel command execution on a session. Ensure that you execute the commands sequentially.
<b>ISS.0086.9316E</b>	<b>One or more required values are missing: {0}.</b>
<b>Explanation</b>	You have not provided all the mandatory input parameters that Integration Server requires to execute the SFTP put command.
<b>Action</b>	Ensure that you provide all the input parameters to execute the SFTP put command. For example, to execute the put command, you have the option to provide a combination of contentStream and remote file name. Integration Server throws this error if you do not provide both the input parameters in this combination.
<b>ISS.0086.9317E</b>	<b>Invalid mode: {0}.</b>
<b>Explanation</b>	The mode that you specified to execute an SFTP command is invalid.
<b>Action</b>	Ensure that you specify a valid value for mode. Valid values are "OVERWRITE", "RESUME", and "APPEND".
<b>ISS.0086.9334E</b>	<b>The packageNames and documentTypeNames input parameters are mutually exclusive.</b>
<b>Explanation</b>	Values cannot be specified for both the packageNames and documentTypeNames input parameters.
<b>Action</b>	Specify either packageNames or documentTypeNames or neither. If you specify neither, Integration Server searches through all the pub.utils.messaging:migrateDocTypesTriggersToUM attempts to migrate all publishable document types contained in packages that do not start with the letters "wm" in any case combination.
<b>ISS.0086.9335E</b>	<b>Error creating package archive:{0}.</b>
<b>Explanation</b>	Integration Server could not create an archive for a package. At run time, the {0} is replaced by the error message that caused package archiving to fail.
<b>Action</b>	Use the error message to correct the cause of the error, then , execute the pub.utils.messaging:migrateDocTypesTriggersToUM service. Note that when using the service to migrate the contents of multiple packages, it might be hard to determine for which package Integration Server could not create an archive. If the server log facility 0153 Dispatcher (Universal Messaging) is set to the Debug level, when the pub.utils.messaging:migrateDocTypesTriggersToUM service executes, the server log will indicate which package Integration Server attempted to archive when the error occurred.

---

<b>ISS.0086.9336E</b>	<b>Unable to lock for editing. Lock status:{0}.</b>
<b>Explanation</b>	The publishable document type could not be locked and therefore cannot be updated.
<b>Action</b>	Use the lock status to determine why the publishable document type is locked. Once the publishable document type is unlocked, execute the <code>pub.utils.messaging:migrateDocTypesTriggersToUM</code> service.
<b>ISS.0086.9337E</b>	<b>Locked by another user:{0}.</b>
<b>Explanation</b>	The publishable document type could not be locked because it is already locked by the specified user. For the publishable document type to be updated, it must be unlocked or locked by the user executing the <code>pub.utils.messaging:migrateDocTypesTriggresToUM</code> service.
<b>Action</b>	Ask the user who has the publishable document type locked to unlock it. Once the publishable document type is unlocked, execute the <code>pub.utils.messaging:migrateDocTypesTriggersToUM</code> service.
<b>ISS.0086.9339E</b>	<b>Could not find newConnectionAlias {0}.</b>
<b>Explanation</b>	Integration Server cannot find the Universal Messaging connection alias specified for the <code>newConnectionAlias</code> parameter. It is possible the alias does not exist or there is an error in the supplied alias name.
<b>Action</b>	Specify an Universal Messaging connection alias that exists on Integration Server as the value for <code>newConnectionAlias</code> . Make sure you spell the alias name properly. Universal Messaging connection alias names are case sensitive. Then, re-execute the <code>pub.utils.messaging.migrateDocTypesTriggersToUM</code> service.
<b>ISS.0086.9340E</b>	<b>Cannot find document type:{0}.</b>
<b>Explanation</b>	Integration Server cannot locate the document type.
<b>Action</b>	Make sure the document type exists on Integration Server. Then, re-execute the <code>pub.utils.messaging.migrateDocTypesTriggersToUM</code> service.
<b>ISS.0086.9341E</b>	<b>The specified element is not a document type.</b>
<b>Explanation</b>	An element specified for the <code>documentTypeNames</code> parameter is not a document type. Valid values for the <code>documentTypeNames</code> parameter are names of publishable document types that exist on Integration Server.
<b>Action</b>	Make sure the <code>documentTypeNames</code> parameter specifies only publishable document types that exist on Integration Server. Then, re-execute the <code>pub.utils.messaging.migrateDocTypesTriggersToUM</code> service.

- ISS.0086.9342E**      **The specified element is not a publishable document type.**
- Explanation**      An element specified for the documentTypeNames parameter is not a publishable document type. Valid values for the documentTypeNames parameter are names of publishable document types that exist on Integration Server.
- Action**              Make sure the documentTypeNames parameter specifies only publishable document types that exist on Integration Server. Then, re-execute the pub.utils.messaging.migrateDocTypesTriggersToUM service.
- 
- ISS.0086.9343E**      **Package not found**
- Explanation**      The contents of the package could not be migrated because Integration Server cannot find the package. The packageNames input parameter specifies a package that does not exist on Integration Server.
- Action**              Make sure the packageNames parameter specifies only packages that exist on Integration Server. Then re-execute the pub.utils.messaging.migrateDocTypesTriggersToUM service.
- 
- ISS.0086.9344E**      **Package disabled**
- Explanation**      The contents of the package could not be migrated because the package is disabled. Only the contents of enabled packages can be migrated.
- Action**              Enable the package and re-execute the pub.utils.messaging.migrateDocTypesTriggersToUM service.
- 
- ISS.0086.9345W**      **Document type does not belong to a package or belongs to a system package.**
- Explanation**      The pub.utils.messaging.migrateDocTypesTriggersToUM service skipped migration for a publishable document type because the publishable document type did not belong to a package or belongs to a system package. A system package begins with the letters “wm” in an case combination. The service modifies publishable document types or webMethods messaging triggers in a system package only when the system package is specified in the packageNames input parameter or the publishable document type was specified in the documentTypeNames input parameter.
- Action**              To migrate the skipped publishable document type, re-execute the pub.utils.messaging.migrateDocTypesTriggersToUM service and specify the publishable document type name in the documentTypeNames input parameter. Alternatively, to migrate multiple publishable document types in a system package, re-execute the pub.utils.messaging.migrateDocTypesTriggersToUM service and specify the system package in the packageNames input parameter.

---

<b>ISS.0086.9346I</b>	<b>Document type not changed.</b>
<b>Explanation</b>	Integration Server skipped migration for the document type because the <code>pub.utils.messaging.migrateDocTypesTriggersToUM</code> service did not make any changes to the publishable document type.
<b>Action</b>	No action required.
<b>ISS.0086.9347I</b>	<b>Package does not contain publishable document types.</b>
<b>Explanation</b>	Migration failed for the package because it does not contain any publishable document types that can be migrated.
<b>Action</b>	No action required.
<b>ISS.0086.9348E</b>	<b>The "serviceName" input parameter is required.</b>
<b>Explanation</b>	There is no service name specified for the <code>serviceName</code> input parameter.
<b>Action</b>	Specify a service name for the <code>serviceName</code> input parameter.
<b>ISS.0086.9350E</b>	<b>The "resultSetKey" input parameter is optional.</b>
<b>Explanation</b>	The pipeline key name specified for the <code>resultSetKey</code> input parameter does not exist in the pipeline.
<b>Action</b>	Specify the correct pipeline key name for the <code>servicePipeline</code> input parameter.
<b>ISS.0086.9351E</b>	<b>The pipeline key name "{0}" does not exist in the wrapped service pipeline.</b>
<b>Explanation</b>	The specified pipeline key name does not exist in the wrapped service.
<b>Action</b>	Verify the resultset key value returned by the wrapped service.
<b>ISS.0086.9352E</b>	<b>The \$internal service input parameter is required.</b>
<b>Explanation</b>	The calling service must create the <code>\$internal</code> service input parameter before calling iterator.
<b>Action</b>	Create the required <code>\$internal</code> input parameter for the iterator service and rerun.
<b>ISS.0086.9353E</b>	<b>The timeToLive input parameter must be greater than 0.</b>
<b>Explanation</b>	The <code>timeToLive</code> input parameter must have a value of greater than 0.
<b>Action</b>	Specify a value that is greater than 0 for the <code>timeToLive</code> input parameter.

<b>ISS.0086.9354E</b>	<b>The batchSize input parameter must be greater than 0.</b>
<b>Explanation</b>	The batchSize input parameter requires a value greater than 0.
<b>Action</b>	Set the batchSize input parameter to a value greater than 0 and rerun the service.
<b>ISS.0086.9355E</b>	<b>The service request has expired.</b>
<b>Explanation</b>	The value specified in the timeToLive input parameter has expired and the result set has been removed from the cache.
<b>Action</b>	Increase the value for timeToLive and rerun the service.
<b>ISS.0086.9356W</b>	<b>Document type is not assigned to a UM connection alias.</b>
<b>Explanation</b>	Integration Server skipped the document type during migration because a value was not specified for newConnectionAlias or a newConnectionAlias specified a Broker connection alias and the document type is either associated with a Broker connection alias or is publishable locally.
<b>Action</b>	Specify a value for newConnectionAlias and re-execute the pub.utils.messaging:migrateDocTypesTriggersToUM service. Alternatively, use Designer to assign the document type a Universal Messaging connection alias and then re-execute the pub.utils.messaging:migrateDocTypesTriggersToUM service.
<b>ISS.0086.9361E</b>	<b>newConnectionAlias:{0} must be an existing UM connection alias.</b>
<b>Explanation</b>	The newConnectionAlias input parameter specifies an alias that does not exist or specifies a Broker connection alias. The pub.utils.messaging:migrateDocTypesTriggersToUM service can be used to migrate publishable document types to a UM connection alias only
<b>Action</b>	Specify the name of a Universal Messaging connection alias that exists on Integration Server and then re-execute the pub.utils.messaging:migrateDocTypesTriggersToUM service.
<b>ISS.0086.9362I</b>	<b>Trigger does not contain any filters.</b>
<b>Explanation</b>	Integration Server skipped the trigger during migration because the trigger does not contain any filters.
<b>Action</b>	No action required.
<b>ISS.0086.9363W</b>	<b>Trigger already specifies a value for Provider Filter (UM).</b>
<b>Explanation</b>	Migration of the filters in the trigger failed because one or more of the trigger conditions already contains a value for Provider Filter (UM). A trigger filter cannot be migrated if a value already exists in Provider Filter (UM).
<b>Action</b>	Manually create the needed Provider Filter. For information about creating trigger filters for use with Universal Messaging, see the documentation.

<b>ISS.0086.9365E</b>	<b>Error retrieving Broker Transport Factory.</b>
<b>Explanation</b>	Integration Server cannot connect to the Broker. Specifically, the Broker Transport Factory cannot be located. Either the connection to the Broker is unavailable or the connection to the Broker is not configured correctly. A Broker connection is required for the <code>pub.utils.messaging:migrateDocTypesTriggersToUM</code> service to execute successfully.
<b>Action</b>	Make sure the Broker connection alias is properly configured, the Broker is installed and properly configured, and that the Broker is available.
<b>ISS.0086.9366E</b>	<b>Error retrieving Broker Transport.</b>
<b>Explanation</b>	Integration Server cannot connect to the Broker. Either the connection to the Broker is unavailable or the connection to the Broker is not configured correctly. A Broker connection is required for the <code>pub.utils.messaging:migrateDocTypesTriggersToUM</code> service to execute successfully.
<b>Action</b>	Make sure the Broker connection alias is properly configured, the Broker is installed and properly configured, and that the Broker is available
<b>ISS.0086.9367E</b>	<b>Error retrieving Broker Admin Client.</b>
<b>Explanation</b>	Integration Server cannot connect to the Broker. Either the connection to the Broker is unavailable or the connection to the Broker is not configured correctly. A Broker connection is required for the <code>pub.utils.messaging:migrateDocTypesTriggersToUM</code> service to execute successfully.
<b>Action</b>	Make sure the Broker connection alias is properly configured, the Broker is installed and properly configured, and that the Broker is available.
<b>ISS.0086.9368I</b>	<b>Converted Filter:{0} to Provider Filter (UM):{1}.</b>
<b>Explanation</b>	Integration Server converted the expression in Filter to the expression in Provider Filter (UM).
<b>Action</b>	No action required.
<b>ISS.0086.9369W</b>	<b>Partial filter conversion - Dropped:{0}.</b>
<b>Explanation</b>	The complete filter in the Filter field could not be migrated to the Provider Filter (UM) field. Integration Server migrated some expressions in the filter successfully, but could not migrate one or more expressions in the original filter. The <code>pub.utils.messaging:migrateDocTypesTriggersToUM</code> service returns this message for each expression that could not be migrated. At run time, the portion of the expression that could not be migrated replaces the {0} in the message. The contents of the Filter field will not change. That is, Integration Server does not remove the filter expressions that it migrated to Provider Filter (UM) field from the Filter field.
<b>Action</b>	No action is required. However, you might want to edit the contents of the Filter field by removing the expressions that were migrated to Provider Filter (UM). This will eliminate duplicate filter processing.

**ISS.0086.9371E      The node specified as input for the node parameter does not exist or is not a DOM node**

**Explanation**      The node specified as input to the node parameter for the pub.xmldata:domNodeToXMLData service does not exist or is not a DOM node.

**Action**            Make sure the node specified as input for the node parameter for the pub.xmldata:domNodeToXMLData service exists and is a DOM node.

**ISS.0086.9372E      The document type specified for the conformsTo input parameter does not exist or is not an XML document type.**

**Explanation**      The document type specified for the conformsTo input parameter for the pub.xmldata:domNodeToXMLData service either does not exist or is not an XML document type.

**Action**            Make sure that the document types specified as input to the conformsTo parameter exists and is an XML document type..

**ISS.0086.9373E      The document specified as input for the xmlDataDocument parameter does not exist or is not of type XMLData.**

**Explanation**      Either the specified document as input for the xmlDataDocument parameter does not exist or it is not of type XMLData. The pub.xmldata.xmlDataToXMLString service requires that the input document be of type XMLData.

**Action**            Make sure the document specified as input for xmlDataDocument exists and is of type XMLData. Use the Document data type property for the specified document to determine if it is of type XML Data.

**ISS.0086.9380E      The servicePrincipal input parameter is required if a jaasContext is specified.**

**Explanation**      If the pub.client:http service specifies a value for the auth/kerberos/jaasContext input parameter, the auth/keberos/servicePrincipal input parameter must be specified as well.

**Action**            Specify a value for the auth/Kerberos/servicePrincipal input parameter.

**ISS.0086.9381E      A value is not supplied for the Kerberos clientPassword input parameter. The Keberos clientPassword must be specified if the Kerberos clientPrincipal is supplied.**

**Explanation**      The pub.client:http service specifies a value for the auth/kerberos/clientPrincipal input parameter but does not specify a value for the auth/kerberos/clientPassword input parameter. If clientPrincipal is specified, then clientPassword must be specified.

**Action**            Specfiy a value for the auth/kerberos/clientPassword field.

---

<b>ISS.0086.9382E</b>	<b>Input to {0} must be an inputstream.</b>
<b>Explanation</b>	The input must be an input stream.
<b>Action</b>	Specify an inputstream.
<b>ISS.0086.9383E</b>	<b>Input must be a byte array or an inputstream.</b>
<b>Explanation</b>	The input must be a byte array or an input stream.
<b>Action</b>	Specify a byte array or input stream.
<b>ISS.0086.9384E</b>	<b>Input to {0} must be a (byte[]).</b>
<b>Explanation</b>	If the user does not provide a byte[] type
<b>Action</b>	User should provide a byte[].
<b>ISS.0086.9385E</b>	<b>Error while processing the signature stream:</b>
<b>Explanation</b>	User encounters problem while reading the stream
<b>Action</b>	To inform the user that there is a problem in processing the stream.
<b>ISS.0088.9108E</b>	<b>SOAP Handler {0} already registered</b>
<b>Explanation</b>	While executing pub.soap.processor:registerProcessor, Integration Server could not register the custom SOAP message processor because the registry already has a SOAP message processor registered for the supplied directive.
<b>Action</b>	When registering a custom SOAP message processor using pub.soap.processor:registerProcessor, specify a directive for which there is not already a custom SOAP message processor. Alternatively, use pub.soap.processor:unregisterProcessor to unregister the custom SOAP message processor that is currently registered to the specified directive and then register the new SOAP message processor with that directive.
<b>ISS.0088.9109</b>	<b>SOAP is only supported using HTTP POST protocol</b>
<b>Explanation</b>	The SOAP message handler was not able to accept the request because the SOAP message was submitted to Integration Server using the HTTP GET method. The SOAP message handler only accepts requests via the POST method (per W3C specification).
<b>Action</b>	Modify the client to use HTTP POST to submit SOAP messages to Integration Server.

<b>ISS.0088.9110E</b>	<b>Invalid BOOLEAN value {0} for variable {1}; must be 0 or 1</b>
<b>Explanation</b>	The addHeaderEntry service failed because the mustUnderstand attribute was not set correctly.
<b>Action</b>	Check the logic in the process that failed to make sure that it sets the value of the specified variable to either 0 or 1. No other values are permitted when setting the mustUnderstand attribute.
<b>ISS.0088.9111E</b>	<b>Cannot load or execute the SOAP processor {0}</b>
<b>Explanation</b>	The SOAP message handler cannot process the SOAP message because the requested SOAP processor is non-operational.
<b>Action</b>	On the server, check the status of the service that is registered to directiveName. Make sure this service is loaded and operating successfully. (Frequently this error occurs because the processor was modified and then did not recompile successfully.)
<b>ISS.0088.9112E</b>	<b>An Exception was thrown in the server:{0}</b>
<b>Explanation</b>	Integration Server, the SOAP processor, or one of the services processing the message has thrown an exception.
<b>Action</b>	See the detail element in the SOAP fault to determine the exception that was thrown and which process it was thrown by.
<b>ISS.0088.9113E</b>	<b>The SOAP Envelope does not have a Body block</b>
<b>Explanation</b>	The SOAP client was given a soapRequestData that did not contain a body element.
<b>Action</b>	Examine the logic in the client to see whether it uses the stringToSoapData or streamToSoapData service to generate their SOAP objects. If so, determine whether the String or stream from which the SOAP object was generated represented a valid SOAP message. Also check whether the SOAP processor or client used any of the data removal utilities (such as removeHeaderEntry or removeBodyEntry) and might have inadvertently removed the entire Body element.
<b>ISS.0088.9116]E</b>	<b>The server cannot execute the requested SOAP utility; required parameter {0} is missing or invalid</b>
<b>Explanation</b>	The requested SOAP utility service failed to execute because a required parameter was not supplied.
<b>Action</b>	Check the logic in the SOAP processor or client to make sure that it passes the correct parameters to each SOAP utility service that it invokes.

---

<b>ISS.0088.9117E</b>	<b>One or more header entries were not understood by the SOAP processor</b>
<b>Explanation</b>	The SOAP processor has rejected the SOAP message because it cannot obey a mandatory header entry (a header entry whose mustUnderstand attribute is enabled).
<b>ISS.0088.9118E</b>	<b>Parameter {0} must be a valid soapData</b>
<b>Explanation</b>	The requested SOAP utility service failed to execute because the value supplied to the specified parameter s not a SOAP object.
<b>Action</b>	Examine the logic in the SOAP processor or client and make sure that it passes a SOAP object to the specified parameter.
<b>ISS.0088.9119E</b>	<b>SOAP Processor did NOT return a valid SOAP Response</b>
<b>Explanation</b>	The message handler did not receive a valid SOAP message from the SOAP processor.
<b>Action</b>	Examine the logic in the SOAP processor to make sure that it composes the SOAP response message correctly. For example, check to see whether it the processor uses the stringToSoapData or streamToSoapData services to generate soapResponseData. If so, determine whether the original String or stream represents a valid SOAP message. If the SOAP processor logic seems correct, contact Software AG Global Support. This would indicate a serious internal error.
<b>ISS.0088.9120E</b>	<b>Parameter {0} is not one of the valid data types: {1}</b>
<b>Explanation</b>	The requested SOAP utility failed to execute because the specified parameter did not have the correct data type. The exception message identifies the data type that is expected.
<b>Action</b>	Examine the logic in the SOAP processor or client and make sure that it passes an object of the specified data type to the specified parameter.
<b>ISS.0088.9122E</b>	<b>Service {0} does not exist</b>
<b>Explanation</b>	The SOAP facility could not complete the requested operation because it could not find the specified service. This error is issued by various SOAP processes (e.g., registering a SOAP processor, invoking a SOAP processor, invoking a target service).
<b>Action</b>	Examine the process that failed and make sure that it specifies the name of the requested service correctly. For example, if you receive this error when registering a SOAP processor, check that you have specified the svcName parameter correctly. Remember that service names are case-sensitive.

- ISS.0088.9123E      Requested SOAP processor {0} is not registered on this server**
- Explanation**      The Integration Server could not process the SOAP message because it does not have the SOAP processor requested by the client.
- Action**              On the client side, verify that the correct process directive is specified in the URL (remember that the directive is case-sensitive). If the client has specified the process directive correctly, then use `pub.soap.processor:list` to verify that the requested processor is registered on the Integration Server.
- 
- ISS.0088.9124E      SOAP Message does not conform to the SOAP message model**
- Explanation**      The SOAP message passed to the `validateSoapData` utility failed validation (for example, it is missing the Body element or the Header element follows the body).
- Action**              Examine the logic that produced the message and see whether it uses the `stringToSoapData` or `streamToSoapData` service to manually generate a SOAP object instead of using the message composition services (e.g., `createSoapData`, `addHeaderEntry`, `addBodyEntry`). If so, determine whether the String or stream from which the SOAP object is generated represents a valid SOAP message. Also check whether the SOAP processor or client used any of the data removal utilities (such as `removeHeaderEntry` or `removeBodyEntry`) and might have inadvertently removed required portions of the SOAP object (for example, the entire Body element).
- 
- ISS.0088.9125E      SOAP request does not conform to the SOAP message model**
- Explanation**      The SOAP message handler could not process the SOAP request because it violates the SOAP message schema (for example, it is missing the Body element or the Header element follows the body).
- Action**              On the client side, correct the logic that builds the message to ensure that it produces a valid SOAP message.
- 
- ISS.0088.9126E      SOAP response does not conform to the SOAP message model**
- Explanation**      The SOAP message handler could not return the SOAP response generated by a SOAP processor on the Integration Server because the message violates the SOAP message schema.
- Action**              Examine the logic in the SOAP processor and see whether it uses the `stringToSoapData` or `streamToSoapData` service to generate a SOAP object. If so, determine whether the String or stream from which the SOAP object is generated represents a valid SOAP message. Examine the logic that produced the message and see whether it uses the `stringToSoapData` or `streamToSoapData` service to manually generate a SOAP object instead of using the message composition services (e.g., `createSoapData`, `addHeaderEntry`, `addBodyEntry`). If so, determine whether the String or stream from which the SOAP object is generated represents a valid SOAP message. Also check whether the SOAP processor or client used any of the data removal utilities (such as `removeHeaderEntry` or `removeBodyEntry`) and might have inadvertently removed required portions of the SOAP object (for example, the entire Body element).

---

<b>ISS.0088.9127E</b>	<b>The server could not load the SOAP XML Validator</b>
<b>Explanation</b>	The SOAP message handler encountered a serious internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0088.9128E</b>	<b>Request is from namespace {0}, server requires namespace {1}</b>
<b>Explanation</b>	The SOAP message handler could not process the message because the message is not from a version of SOAP that the Integration Server supports. Integration Server supports the version indicated in the exception message.
<b>Action</b>	From the client side, resubmit the message using a version of SOAP that Integration Server supports.
<b>ISS.0088.9132E</b>	<b>Failed to register SOAP Handler {0}, illegal characters in directive name.</b>
<b>Explanation</b>	Integration Server was not able to successfully register the SOAP processor, because directiveName contains characters that are not allowed in a directive name.
<b>Action</b>	Register the SOAP processor under a name that is composed only of letters, digits, or the characters <code>-.!~*'()</code> .
<b>ISS.0088.9133E</b>	<b>Error while encoding RPC output</b>
<b>Explanation</b>	While encoding RPC output, an exception occurred which resulted in an Integration Server error.
<b>Action</b>	Use the underlying exception to help determine what caused the error.
<b>ISS.0088.9134E</b>	<b>Exception occurred while processing the body of the message</b>
<b>Explanation</b>	Integration Server, the SOAP processor, or one of the services processing the SOAP message has thrown an exception.
<b>Action</b>	See the detail element in the SOAP fault to determine the exception that was thrown and by which process it was thrown.
<b>ISS.0088.9135E</b>	<b>A WMDocument Exception was thrown in the server, usually because an XML block was not well-formed</b>
<b>Explanation</b>	The SOAP message handler, the soapHTTP service, or the soapRPC service has received a SOAP message that contains invalid XML.
<b>Action</b>	Check the process that submitted the SOAP message to the Integration Server and make sure that it is producing valid XML. This error usually occurs because of a basic error in the XML document, such as missing tags or overlapping elements.

<b>ISS.0088.9137E</b>	<b>Invalid input parameter; {0} must be a Document (IData)</b>
<b>Explanation</b>	The requested SOAP service failed to execute because the object passed into the specified parameter is not an IData object.
<b>Action</b>	Check the logic in the SOAP processor or client to make sure that it passes an IData into the specified parameter.
<b>ISS.0088.9138E</b>	<b>Input parameters do not conform to targetInputSignature: {0}</b>
<b>Explanation</b>	The pub.client:soapRPC service could not submit the remote procedure call because the input parameters did not pass the data-validation process.
<b>Action</b>	This error is thrown when a client supplies an invalid set of input parameters for a SOAP remote procedure call. Specifically, it indicates that the parameters submitted to pub.client:soapRPC in reqParms do not match the structure and constraints of the document type specified in targetInputSignature. Generally, you will want to code your client to detect this kind of error and take some type of corrective action when it occurs.
<b>ISS.0088.9139E</b>	<b>Output parameters do not conform to targetOutputSignature: {0}</b>
<b>Explanation</b>	The SOAP RPC client could not submit the remote procedure call because the output parameters returned by the remote server did not pass the data-validation process.
<b>Action</b>	This error is thrown when a client receives an invalid set of output parameters (results) from a SOAP remote procedure call. Specifically, it indicates that the parameters returned to pub.client:soapRPC in respParms do not match the structure and constraints of the document type specified in targetOutputSignature. Generally, you will want to code your client to detect this kind of error and take some type of corrective action when it occurs.
<b>ISS.0088.9140E</b>	<b>Invalid target signature {0}, must be a Document Type</b>
<b>Explanation</b>	The SOAP RPC client could not process the remote procedure call because it was not able to validate the input or output parameters associated with the request. The signature it was given for validation is not a document type.
<b>Action</b>	Examine the logic in the SOAP RPC client and make sure that the object it specifies in targetInputSignature and/or targetOutputSignature is a document type. That is, these parameters, if used, specify the fully qualified name of a document type that exists on Integration Server.
<b>ISS.0088.9141E</b>	<b>Invalid target signature {0}, Document Type does not exist</b>
<b>Explanation</b>	The SOAP RPC client could not process the remote procedure call because it was not able to validate the input or output parameters associated with the request. The specified document type does not exist on the Integration Server.
<b>Action</b>	Examine the logic in the SOAP RPC client and make sure that targetOutputSignature and/or targetOutputSignature are correctly specified. (Remember that the names of

document types are case sensitive.). Also verify that the specified document type exists on the server and the package in which it resides is loaded and enabled.

<b>ISS.0088.9144</b>	<b>this SOAPEnvelope object already contains a valid SOAPHeader object</b>
<b>Explanation</b>	An attempt was made to add a SOAPHeader object to the SOAPEnvelope of a SOAPMessage that already contains a SOAPHeader object.
<b>Action</b>	The SOAPEnvelope object may contain a maximum of one SOAP Header.
<b>ISS.0088.9145E</b>	<b>this SOAPEnvelope object does not contain a valid SOAPHeader object</b>
<b>Explanation</b>	An attempt was made to access the SOAPHeader object, but the SOAPEnvelope of the SOAPMessage does not contain a SOAPHeader object.
<b>Action</b>	Add a SOAPHeader object to the SOAPEnvelope before accessing it.
<b>ISS.0088.9147E</b>	<b>this SOAPEnvelope object does not contain a valid SOAPBody object</b>
<b>Explanation</b>	An attempt was made to access the SOAPBody object, but the SOAPEnvelope of the SOAPMessage does not contain a SOAPBody object.
<b>Action</b>	Add a SOAPBody object to the SOAPEnvelope before accessing it.
<b>ISS.0088.9148E</b>	<b>Exception occurred while retrieving SOAPHeader object</b>
<b>Explanation</b>	The specified exception occurred while attempting to access the SOAPHeader object.
<b>Action</b>	Correct the error and retry.
<b>ISS.0088.9149E</b>	<b>Exception occurred while retrieving SOAPBody object</b>
<b>Explanation</b>	The specified exception occurred while attempting to access the SOAPBody object.
<b>Action</b>	Correct the error and retry.
<b>ISS.0088.9150E</b>	<b>Exception occurred while retrieving SOAPHeaderElement objects</b>
<b>Explanation</b>	The specified exception occurred while attempting to access the SOAPHeaderElement object.
<b>Action</b>	Correct the error and retry.

<b>ISS.0088.9151E</b>	<b>Exception occurred while retrieving SOAPBodyElement objects</b>
<b>Explanation</b>	The specified exception occurred while attempting to access the SOAPBodyElement object.
<b>Action</b>	Correct the error and retry.
<b>ISS.0088.9152E</b>	<b>The property {0} is unknown</b>
<b>Explanation</b>	An attempt was made to either get or set a property of the specified SOAPMessage, but the property name is unknown. The only valid SOAPMessage property names are javax.xml.soap.WRITE_XML_DECLARATION and javax.xml.soap.CHARACTER_SET_ENCODING.
<b>Action</b>	Specify the name of a valid property.
<b>ISS.0088.9153E</b>	<b>this SOAPMessage object already contains a valid Detail object</b>
<b>Explanation</b>	An attempt was made to add a Detail object to the SOAPBody of this SOAPMessage, but the SOAPBody already contains a Detail object. The SOAPBody can contain one and only one Detail object.
<b>Action</b>	Remove the existing Detail object before adding the new one.
<b>ISS.0088.9154</b>	<b>this SOAPMessage object already contains a valid Fault object</b>
<b>Explanation</b>	An attempt was made to add a Fault object to the SOAPBody of this SOAPMessage, but the SOAPBody already contains a Fault object. The SOAPBody can contain one and only one Fault object.
<b>Action</b>	Remove the existing Fault object before adding the new one.
<b>ISS.0088.9155E</b>	<b>this SOAPMessage does not contain a valid Envelope object</b>
<b>Explanation</b>	The specified SOAPMessage does not contain a valid SOAPEnvelope object.
<b>Action</b>	Create a new SOAPMessage that contains a valid SOAPEnvelope object.
<b>ISS.0088.9163E</b>	<b>Could not retrieve WSDL for service {0}, WSD not found.</b>
<b>Explanation</b>	Integration Server could not retrieve the WSDL for the specified Web service descriptor because the specified Web service descriptor does not exist on Integration Server.
<b>Action</b>	Ensure that the specified Web service descriptor exists on Integration Server.

<b>ISS.0088.9164E</b>	<b>Access to WSDescriptor {0} denied.</b>
<b>Explanation</b>	The user is not authorized to access the specified Web service descriptor.
<b>Action</b>	Specify a username that is authorized to access the specified Web service descriptor.
<b>ISS.0088.9166E</b>	<b>Binder not found for soapAction = {0}</b>
<b>Explanation</b>	The Web service descriptor has more than one binder, with the same operation name. Developer cannot calculate a default soapAction attribute to identify the correct operation.
<b>Action</b>	Include a unique soapAction attribute in the SOAPAction HTTP Header for every request.
<b>ISS.0088.9251E</b>	<b>JAX-RPC Handler failed to process the message</b>
<b>Explanation</b>	The JAX-RPC handler was invoked to process the message. Either the handleRequest() or handleResponse() method returns false, indicating a failure.
<b>Action</b>	Check the webMethods Integration Server log for error messages generated by the JAX-RPC handler.
<b>ISS.0088.9252E</b>	<b>An Exception has been caught: {0}</b>
<b>Explanation</b>	An exception was caught while attempting to process a SOAP message.
<b>Action</b>	Correct the problem indicated by the exception message.
<b>ISS.0088.9253E</b>	<b>Could not add "Text" element to "Reason" element, locale is null</b>
<b>Explanation</b>	An attempt to add a Text element to the existing Reason element failed because the locale was not specified.
<b>Action</b>	Specify the locale when adding the Text element.
<b>ISS.0088.9255I</b>	<b>This element's QName cannot be changed</b>
<b>Explanation</b>	An attempt to change the QName of a SOAPEnvelope, SOAPBody, or SOAPHeader failed, because the QName cannot be changed.
<b>Action</b>	No action is required.
<b>ISS.0088.9356E</b>	<b>One or more required Headers "{0}" are not present in the SOAP request.</b>
<b>Explanation</b>	The SOAP request received by the provider does not contain one or more required headers. Note that Integration Server considers all headers defined in a Web service descriptor to be required.
<b>Action</b>	Determine why the SOAP request does not contain the required headers, which might involve contacting the client to determine why the client did not include the required headers in the request.

<b>ISS.0088.9420E</b>	<b>Required parameter {0} is missing</b>
<b>Explanation</b>	A required input parameter was not provided.
<b>Action</b>	Provide the required input parameter.
<b>ISS.0088.9421E</b>	<b>The service {0} does not exist</b>
<b>Explanation</b>	The specified service does not exist.
<b>Action</b>	Specify an existing service.
<b>ISS.0088.9422E</b>	<b>Either parameter {0} or {1} must be provided</b>
<b>Explanation</b>	The service requires either one of the specified parameters, but neither was provided.
<b>Action</b>	Provide one of the required parameters.
<b>ISS.0088.9423E</b>	<b>Service handler {0} is already registered</b>
<b>Explanation</b>	A service handler with that name is already registered.
<b>Action</b>	Specify a different name when registering the service handler.
<b>ISS.0088.9425E</b>	<b>Error destroying service handler {0}. Error:{1}</b>
<b>Explanation</b>	An error occurred while destroying the JAX-RPC handler.
<b>Action</b>	The destroy() method of the JAX-RPC Handler has thrown an error. Correct the error in destroy() method.
<b>ISS.0088.9427E</b>	<b>Service handler {0} could not be unregistered. A service handler by that name is not registered</b>
<b>Explanation</b>	A service handler with the provided name is not registered.
<b>Action</b>	Specify the name of a registered service handler.
<b>ISS.0088.9428E</b>	<b>Service handler {0} could not be found. A service handler by that name is not registered</b>
<b>Explanation</b>	The specified service handler could not be found because it is not registered.
<b>Action</b>	Provide the name of a registered service handler.

<b>ISS.0088.9429E</b>	<b>Could not find service handler for header {0}:{1}</b>
<b>Explanation</b>	The header QName does not correspond to a registered service handler.
<b>Action</b>	Verify that the QName of the header corresponds to a registered service handler or register a service handler for the provided QName.
<b>ISS.0088.9430E</b>	<b>Handler processing failed on the provider</b>
<b>Explanation</b>	A handler service failed on the provider.
<b>Action</b>	Examine the handler services for errors and correct any errors that are found.
<b>ISS.0088.9431E</b>	<b>Handler processing failed on the consumer: {0}</b>
<b>Explanation</b>	A handler service failed on the consumer.
<b>Action</b>	Examine the handler services for errors and correct any errors that are found.
<b>ISS.0088.9443E</b>	<b>One or more required Headers "{0}" are not present in the SOAP response.</b>
<b>Explanation</b>	The SOAP response received by the Web service connector does not contain one or more required headers. That is, the SOAP response does not contain a header with a QName that matches the QName of a header defined in the consumer Web service descriptor. Note that Integration Server consider all headers defined in a Web service descriptor to be required.
<b>Action</b>	Determine why the SOAP response does not contain the required headers, which might involve contacting the provider to determine why the provider did not include the required headers in the response.
<b>ISS.0088.9448E</b>	<b>Handler services do not support XML document type usage</b>
<b>Explanation</b>	The name of the document type supplied to the pub.soap.handler* service is an XML document type. Integration Server does not support the use of XML document types with web services. As a result, the pub.soap.handler* services will not accept the name of XML document type as input for the documentType or documentTypes names input parameters.
<b>Action</b>	Modify the documentType or documentTypes input parameter to specify an IS document type name instead of an XML document type name.
<b>ISS.0092.9045E</b>	<b>A WS-I compliant Web Service Descriptor cannot contain a header or fault with a different namespace. Source: {0}</b>
<b>Explanation</b>	The supplied WSDL document is not WS-I compliant because it contains a header or a fault with a different namespace.
<b>Action</b>	Edit the WSDL document to be WS-I compliant.

<b>ISS.0092.9101E</b>	<b>Cannot specify both 'element' and 'type'.</b>
<b>Explanation</b>	The supplied WSDL document is invalid because element and type are both used to define a message part.
<b>Action</b>	Edit the WSDL document so that either element or type is used to define the message part.
<b>ISS.0092.9102E</b>	<b>{0}: not a valid web service description document</b>
<b>Explanation</b>	The file identified as the source for creating the Web service descriptor is not a .wsdl or .wsd file. A consumer Web service descriptor or a WSDL first provider Web service descriptor can be generated from a .wsdl or .wsd file only.
<b>Action</b>	Provide a .wsdl or .wsd file to use as the source for the Web service descriptor.
<b>ISS.0092.9103E</b>	<b>{0}: invalid file, unable to parse root element</b>
<b>Explanation</b>	The WSDL document does not contain a proper root element. Integration Server is unable to determine which element is the root element and cannot parse the root element.
<b>Action</b>	Ensure that the WSDL document contains a proper root element.
<b>ISS.0092.9105E</b>	<b>Cannot find the specified Document Type or input/output parameter.</b>
<b>Explanation</b>	While creating an XML Schema definition, Integration Server cannot find the specified document type or the Input/Output parameters are not mentioned.
<b>Action</b>	When creating an XML Schema definition from an document type, service (input/output parameters), or specification, ensure that the chosen source exists and is not null.
<b>ISS.0092.9106E</b>	<b>Field {0} is multi-dimensional which cannot be converted to xsd without using SOAP_ARRAY</b>
<b>Explanation</b>	The specified field is a table (multi-dimensional) and cannot be represented in XML Schema.
<b>Action</b>	A multi-dimensional field such as a table can be represented as a nested fields in an array.
<b>ISS.0092.9107E</b>	<b>Port {0} is missing required extended element.</b>
<b>Explanation</b>	The WSDL document is invalid because the specified port is missing a required element. Integration Server cannot create a Web service descriptor.
<b>Action</b>	Edit the WSDL document to include a valid port.

---

<b>ISS.0092.9108E</b>	<b>SimpleType {0} does not have base type.</b>
<b>Explanation</b>	In the WSDL or WSD document the specified simple type definition does not have a base type.
<b>Action</b>	Edit the simple type definition in the WSDL document to include a base data type.
<b>ISS.0092.9109E</b>	<b>The system cannot find {0}</b>
<b>Explanation</b>	The Web service descriptor cannot be created because the specified WSDL file cannot be found on the file system.
<b>Action</b>	Make sure that the specified WSDL file exists on the file system or that the provided URL for the WSDL file is correct.
<b>ISS.0092.9111E</b>	<b>Element must be a document type, service, or specification</b>
<b>Explanation</b>	The specified source from which Integration Server is to create an XML Schema definition is not a document type, service, or specification.
<b>Action</b>	Make sure the specified source is a document type, service, or specification.
<b>ISS.0092.9112E</b>	<b>The service does not have a valid signature</b>
<b>Explanation</b>	The service signature from which Integration Server is to create the XML Schema definition is not valid.
<b>Action</b>	Make sure the specified service has a valid signature that describes the expected names and data types for the inputs and outputs to the service.
<b>ISS.0092.9113E</b>	<b>Unknown ExtensibleElement "{0}"</b>
<b>Explanation</b>	The portType element in the WSDL document is missing required extensions (document OR operation).
<b>Action</b>	Edit the WSDL document to include the required extension in the that the portType element.
<b>ISS.0092.9114E</b>	<b>Invalid WSDL; 'arrayType' attribute value {0} is malformed. Invalid QName {1}</b>
<b>Explanation</b>	The supplied WSDL document is invalid because the specified arrayType attribute value contains the specified invalid QName.
<b>Action</b>	Edit the WSDL document to supply a valid QName for the arrayType attribute value.

<b>ISS.0092.9115E</b>	<b>Invalid WSDL; 'arrayType' attribute value {0} is malformed. It should contain characters '[' and ']'</b>
<b>Explanation</b>	The supplied WSDL document is invalid because the specified arrayType attribute value does not contain the opening and/or closing bracket characters '[' and ']'.
<b>Action</b>	Edit the WSDL by correcting the arrayType attribute value so that it includes the opening and closing bracket characters '[' and ']'.
<b>ISS.0092.9116E</b>	<b>Invalid WSDL; 'arrayType' attribute value {0} is malformed. Invalid rank size {1}</b>
<b>Explanation</b>	The supplied WSDL document is invalid because the specified arrayType attribute value contains an invalid rank size. The rank size should follow the pattern: "(\[\[,*\]\])*\[\(((\d+)*\d+)?\]\]" OR "(\[\[,*\]\])*" OR "(\[\[\(((\d+)*\d+)?\]\])*" )
<b>Action</b>	Edit the WSDL document to specify a valid rank size for the attribute. A valid rank size follows this pattern: "(\[\[,*\]\])*\[\(((\d+)*\d+)?\]\]" OR "(\[\[,*\]\])*" OR "(\[\[\(((\d+)*\d+)?\]\])*" )
<b>ISS.0094.0001E</b>	<b>Repository Exception: {0}</b>
<b>Explanation</b>	During initialization, Integration Server could not initialize the Repository Manager. The most likely reason is that the repository4.cnf file is corrupted.
<b>Action</b>	Check the directory that contains the repository files. By default, they are located at <IntegrationServer_dir>\WmRepository4\ directory. Try renaming the repository4.cnf file manually (to something like "damagedrepository4.cnf") or deleting it, then try re-initializing Integration Server. If that does not work, contact Software AG Global Support.
<b>ISS.0094.0003E</b>	<b>RepositoryManager detected damaged data files : {0}</b>
<b>Explanation</b>	During initialization, Integration Server detected that some of the data files that make up the repository were corrupted. In a recovery attempt, Integration Server tried to open the files, but was unable to.
<b>Action</b>	Check the directory that contains the data files. By default, the data files are located at <IntegrationServer_dir>\WmRepository4\ directory. You can also look in the repository4.cnf file for the location of the data files. Try manually renaming the files (to something like "damagedFSDData00000000") or deleting them, then try re-initializing Integration Server. If that does not work, contact Software AG Global Support.
<b>ISS.0094.0004E</b>	<b>RepositoryManager Exception renaming damaged data files : {0}</b>
<b>Explanation</b>	During initialization, Integration Server detected that some of the data files that make up the repository were corrupted. In an attempt to correct the problem, Integration Server tried to rename the damaged files before creating new ones but encountered an exception when trying to rename the damaged files.
<b>Action</b>	Check the directory that contains the data files. By default, the data files are located at <IntegrationServer_dir>\WmRepository4\ directory. You can also look in the repository4.cnf file for the location of the data files. Try manually renaming the files

(to something like "damagedFSDData00000000") or deleting them, then try re-initializing Integration Server. If that does not work, contact Software AG Global Support.

<b>ISS.0094.0006E</b>	<b>RepositoryManager Exception creating new data files : {0}</b>
<b>Explanation</b>	During initialization, Integration Server detected that some of the data files that make up the repository were corrupted. In an attempt to correct the problem, Integration Server renamed the damaged files and tried to create new ones but encountered an exception when trying to create new files. Possible reasons for the problem are that the file system does not have enough space for the data files or that Integration Server does not have write access to the directory that contains the files.
<b>Action</b>	Check the directory that contains the data files. By default, the data files are located at <IntegrationServer_dir>\WmRepository4\ directory. You can also look in the repository4.cnf file for the location of the data files. Make sure the file system has space for the files and that Integration Server has write access to the directory.
<b>ISS.0095.0006E</b>	<b>AuditLogManager: Exception auditing start of service {0}: {1}</b>
<b>Explanation</b>	An error was encountered while audit logging the start of a service invocation.
<b>Action</b>	Set the logging level of the "0095 Audit Log Manager" logging facility to TRACE on the Settings > Logging > Server Logger page of the Integration Server Administrator. If the error recurs, see the error details in the server log.
<b>ISS.0095.0007E</b>	<b>AuditLogManager: Exception auditing end of service {0}: {1}</b>
<b>Explanation</b>	An error was encountered while audit logging the start of a service invocation.
<b>Action</b>	Set the logging level of the "0095 Audit Log Manager" logging facility to TRACE on the Settings > Logging > Server Logger page of the Integration Server Administrator. If the error recurs, see the error details in the server log.
<b>ISS.0095.0008E</b>	<b>AuditLogManager: Exception auditing error for service {0}: {1}</b>
<b>Explanation</b>	An error was encountered while audit logging a service invocation.
<b>Action</b>	Set the logging level of the "0095 Audit Log Manager" logging facility to TRACE on the Settings > Logging > Server Logger page of the Integration Server Administrator. If the error recurs, see the error details in the server log.
<b>ISS.0095.0009E</b>	<b>AuditLogManager: Audit runtime interface object cannot be initialized: {0}</b>
<b>Explanation</b>	The Integration Server Audit Log Manager encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.

- ISS.0095.0010E      AuditLogManager Runtime Exception: {0} publishing log entry {1}. {2}**  
**Explanation**      An error was encountered while audit logging a service error.  
**Action**              See the detailed error message and stack trace that follow. If audit logging to a database, you may have to work with your DBA to diagnose a database problem.
- ISS.0095.0014E      Audit Logging initialized with errors.**  
**Explanation**      An error was encountered while starting the audit logging facility.  
**Action**              Set the logging level of the "0095 Audit Log Manager" logging facility to TRACE on the Settings > Logging > Server Logger page of the Integration Server Administrator. If the error recurs, contact Software AG Global Support and provide them with the server log.
- ISS.0095.0015W      Database at URI {0} is not available.**  
**Explanation**      An audit logger is configured to write log messages to a database, but the database is not available.  
**Action**              Go to the Settings > JDBC Pools page of the Integration Server Administrator and verify that the ISCoreAudit functional alias is correct. For process auditing, check the ProcessAudit functional alias. Use the Test button to check that Integration Server can reach the configured database.
- ISS.0095.0016W      Changing destination of queue {0} from database {1} to file system {2}.**  
**Explanation**      An asynchronous audit logger is configured to write log messages to a database, but the database is not available. The audit logger is being reconfigured to write audit messages to the file system.  
**Action**              Go to the Settings > JDBC Pools page of the Integration Server Administrator and verify that the ISCoreAudit functional alias is correct. For process auditing, check the ProcessAudit functional alias. Use the Test button to check that Integration Server can reach the configured database.
- ISS.0095.0017W      Changing destination of logger {0} from database {1} to file system {2}.**  
**Explanation**      A synchronous audit logger is configured to write log messages to a database, but the database is not available. The audit logger is being reconfigured to write audit messages to the file system.  
**Action**              Go to the Settings > JDBC Pools page of the Integration Server Administrator and verify that the ISCoreAudit functional alias is correct. For process auditing, check the ProcessAudit functional alias. Use the Test button to check that Integration Server can reach the configured database.

---

<b>ISS.0095.0018W</b>	<b>Cannot change destination of logger {0} to file system.</b>
<b>Explanation</b>	An audit logger is configured to write log messages to a database, but the database is not available. It is not possible to write messages for this audit logger to the file system because the messages contain binary data. This audit logger is being disabled.
<b>Action</b>	Go to the Settings > JDBC Pools page of the Integration Server Administrator and verify that the ISCoreAudit functional alias is correct. For process auditing, check the ProcessAudit functional alias. Use the Test button to check that Integration Server can reach the configured database.
<b>ISS.0095.0019W</b>	<b>Disabling the logger {0}.</b>
<b>Explanation</b>	The audit logger is being disabled. This is probably happening because the logger's database is not available.
<b>Action</b>	Go to the Settings > JDBC Pools page of the Integration Server Administrator and verify that the ISCoreAudit functional alias is correct. For process auditing, check the ProcessAudit functional alias. Use the Test button to check that Integration Server can reach the configured database.
<b>ISS.0095.0020W</b>	<b>Audit Logging Initialization: The {0} JDBC Pool Alias was not configured with enough connections. The Maximum Connections have been increased to {1}.</b>
<b>Explanation</b>	The auditing system needed more database connections than were provided in the JDBC Pools configuration. The configuration was changed as needed.
<b>Action</b>	No action is required.
<b>ISS.0095.0021E</b>	<b>ERROR: Audit Logging Initialization: The {0} JDBC Pool Alias was not configured with enough connections. Unable to automatically increase the Maximum Connections setting.</b>
<b>Explanation</b>	The auditing system needed more database connections than were provided in the JDBC Pools configuration. An attempt was made to automatically increase the number of connections, but it failed.
<b>Action</b>	Go to the Settings > JDBC Pools page of the Integration Server Administrator and increase the Max Connections setting for the ISCoreAudit functional alias. Restart Integration Server.
<b>ISS.0095.0022W</b>	<b>Audit Logging Initialization: Unable to verify the Max Connections setting for the Audit Logging database.</b>
<b>Explanation</b>	Integration Server encountered an error while checking the Max Connection setting for the ISCoreAudit functional alias.
<b>Action</b>	If the auditing system is slow or unresponsive, go to the Settings > JDBC Pools page of the Integration Server Administrator and increase the Max Connections setting for the ISCoreAudit functional alias.

**ISS.0095.0024W**      **The value for watt.server.audit.logDir has been changed and does not identify an existing directory that Integration Server can write to. File-based audit logs will continue to be written to the {0} directory.**

**Explanation**      The audit log directory was not changed because the watt.server.audit.logDir parameter refers to a directory that either does not exist or Integration Server does not have permission to write to. As a result, Integration Server will write file-based audit logs to the last valid directory specified.

**Action**      Go to the Settings > Extended page in the Integration Server Administrator and change the value for the watt.server.audit.logDir parameter. Specify a directory that exists on the server and that Integration Server can write to. You can specify the full path name, or a relative path in relation to the Integration Server.

**ISS.0095.0025W**      **The {0} file was not found and is being created.**

**Explanation**      Upon start up, Integration Server could not find the specified file, for which {0} is a placeholder, in the following directory:  
IntegrationServer/instances/instanceName/config/auditing where instanceName is the Integration Server instance that was started. Integration Server will create the file. The file specifies which database errors are considered transient.

**Action**      If the specified file has been modified, restore the file from a backup, if possible. If the file has not been modified, no action is necessary.

**ISS.0095.0026W**      **The {0} file was not found and is being created. The audit logging system is using default settings.**

**Explanation**      Upon start up, Integration Server could not find the specified file, for which {0} is a placeholder, in the following directory:  
IntegrationServer/instances/instanceName/config/auditing where instanceName is the Integration Server instance that was started. The specified file contains the configured auditing logging settings. Integration Server will create the file, which will contain the default auditing logging settings.

**Action**      If the specified file has been modified, restore the file from a backup or use Integration Server Administrator to restore the configured audit logging settings . If the file has not been modified (that is, you have not modified the audit logging configuration), no action is necessary.

**ISS.0095.0030I**      **Audit Logging: The {0} has entered fail-fast mode for messaging connection alias {1}.**

**Explanation**      The specified audit logger has entered queue fail-fast mode lost the connection to the Universal Messaging server established through indicated messaging connection alias. The audit logger will write log entries to the internal audit logging queue instead of the Universal Messaging

**Action**      Make sure that Universal Messaging server is up and running and that there are no network related problems between Integration Server and Universal Messaging server.

<b>ISS.0095.0031I</b>	<b>Audit Logging: The {0} has exited fail-fast mode for the messaging connection alias {1}.</b>
<b>Explanation</b>	The specified audit logger has exited queue fail-fast mode because connectivity to the Universal Messaging server has been restored. The audit logger writes new log entries to the Universal Messaging queue.
<b>Action</b>	None.
<b>ISS.0095.0032I</b>	<b>Audit Logging: Session for messaging connection alias {0} disconnected.</b>
<b>Explanation</b>	The session on a Universal Messaging server created using the specified messaging connection alias has disconnected. Any audit loggers that use the specified messaging connection alias to write log entries to a Universal Messaging queue will enter queue fail-fast mode and begin writing log entries to the internal audit logging queue.
<b>Action</b>	Make sure that Universal Messaging server is up and running and that there are no network related problems between Integration Server and Universal Messaging server.
<b>ISS.0095.0033I</b>	<b>Audit Logging: Reestablished connection with session for messaging connection alias {0}.</b>
<b>Explanation</b>	The session on a Universal Messaging server created using the specified messaging connection alias has been re-established. Any audit loggers that use the specified messaging connection alias will exit queue fail-fast mode and resume writing new log entries to the Universal Messaging queue
<b>Action</b>	None.
<b>ISS.0095.0037E</b>	<b>Pool with messaging connection alias name {0} does not exist.</b>
<b>Explanation</b>	For an audit logger configured to use Universal Messaging as the queue provider, Integration Server requested a session from a pool for a Universal Messaging connection alias that does not exist. The Universal Messaging connection alias specified in the Connection Alias field for the logger does not exist.
<b>Action</b>	Make sure the logger specifies an existing Universal Messaging connection alias for the Connection Alias field.
<b>ISS.0095.0038W</b>	<b>watt.server.audit.um.sessionPool.min.value is invalid {0}. Value must be an integer greater than zero. Integration Server will use default value of 2.</b>
<b>Explanation</b>	The watt.server.audit.um.sessionPool.min value is invalid because it is not an integer greater than zero. Integration Server will use the default value of 2 until a valid value is specified.
<b>Action</b>	Set watt.server.audit.um.sessionPool.min to an integer greater than 0 (zero) but less than or equal to the value of watt.server.audit.um.sessionPool.max.

**ISS.0095.0039W**      **watt.server.audit.um.sessionPool.max.value is invalid {0}. Value must be an integer greater than zero. Integration Server will use default value of 10.**

**Explanation**      The watt.server.audit.um.sessionPool.max value is invalid because it is not an integer greater than zero. Integration Server will use the default value of 10 until a valid value is specified.

**Action**      Set watt.server.audit.um.sessionPool.max to an integer greater than 0 (zero) but greater than or equal to watt.server.audit.um.sessionPool.min.

**ISS.0095.0040W**      **Invalid watt.server.audit.um.sessionPool.min value {0} and watt.server.audit.um.sessionPool.max value {1}. watt.server.audit.um.sessionPool.min must be less than or equal to watt.server.audit.um.sessionPool.max. Integration Server will use the default values of 2 and 10, respectively.**

**Explanation**      The watt.server.audit.um.sessionPool.min value and watt.server.audit.um.sessionPool.max value are invalid because the watt.server.audit.um.sessionPool.min value is greater than the watt.server.audit.um.sessionPool.max value. Integration Server will use the default values of 2 and 10, respectively, until valid values are specified

**Action**      Set watt.server.audit.um.sessionPool.mim and watt.server.audit.um.sessionPool so that both are integers greater than 0 (zero) and watt.server.audit.um.sessionPool.min value is less than or equal to the watt.server.audit.um.sessionPool.max value.

**ISS.0095.9998E**      **AuditLogManager Exception: {0}**

**Explanation**      An error was encountered using the audit logging database.

**Action**      Try logging again. It may be a transient error. If the error persists, examine the detailed message and stack trace that follow. You may need to work with your DBA to diagnose a problem with the audit logging database.

**ISS.0096.0001E**      **JDBCConnectionManager: initialization failed for {0} functional alias, check configuration.**

**Explanation**      Unable to initialize the functional alias. Integation Server will not be able to connect to the database for this functional alias.

**Action**      Go to the Settings > JDBC Pools page of the Integration Server Administrator and verify that the functional alias settings are correct. Use the Test button to check that Integration Server can reach the configured database.

<b>ISS.0096.0002W</b>	<b>JDBCConnectionManager: creating Embedded Pool Alias for {0}.</b>
<b>Explanation</b>	The connection pool for the embedded database is being created.
<b>Action</b>	No action is required.
<b>ISS.0096.0004E</b>	<b>JDBCConnectionManager: embedded database objects not created: {0}</b>
<b>Explanation</b>	Unable to create tables, keys, or other database objects while initializing the embedded database.
<b>Action</b>	Verify that Integration Server has write access to the file system. If the problem persists, contact Software AG Global Support.
<b>ISS.0096.0005E</b>	<b>JDBCConnectionManager: initialization failed with exception {0}</b>
<b>Explanation</b>	Initialization of the JDBC Connection Manager failed.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0096.0010E</b>	<b>The DataStoreDBListener has detected a bad connection for the {0} JDBC functional alias. The JDBC connection pool is being reinitialized</b>
<b>Explanation</b>	A database connection being used by the pub.storage services is no longer functional. This often indicates a network interruption has broken all existing database connections. Integration Server is reinitializing the pool of connections for the JDBC functional alias. If network connectivity has been restored, the pub.storage services may continue to be used without interruption. If network connectivity has not been restored, the pub.storage services will continue to fail until it is restored.
<b>Action</b>	If the network interruption is transient and connectivity to the database is restored quickly, no immediate action is required. If the network interruption persists, or if transient network interruptions continue to occur, this indicates a problem in the network or in the networking implementation of the host that Integration Server is running on. Seek assistance from a networking expert in your company to investigate and resolve this problem.
<b>ISS.0097.0004E</b>	<b>Failed to lock Repository entry {0}</b>
<b>Explanation</b>	Integration Server encountered an internal error when trying to lock the repository.
<b>Action</b>	If the error continues, contact Software AG Global Support.
<b>ISS.0097.0006I</b>	<b>Messaging synchronizer shutdown</b>
<b>Explanation</b>	The Broker Synchronizer has shut down.
<b>Action</b>	No action is required. This message is displayed when Integration Server is shutting down.

<b>ISS.0097.0012E</b>	<b>Messaging Synchronizer cannot open repository for sync-state storage</b>
<b>Explanation</b>	An error was encountered while trying to open WmRepository4.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0097.0013E</b>	<b>Messaging Synchronizer cannot update sync state; cannot remove sync data from repository: {0}</b>
<b>Explanation</b>	An error occurred while removing sync state data from WmRepository4.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0097.0014E</b>	<b>Messaging Synchronizer cannot update sync state; document type not specified</b>
<b>Explanation</b>	The document type to be synchronized was not specified; the nsName input variable is null.
<b>Action</b>	Specify a document type name for nsName.
<b>ISS.0097.0015D</b>	<b>Messaging Synchronizer cannot update sync state; document type {0} has no sync state</b>
<b>Explanation</b>	The requested document type has no sync state.
<b>Action</b>	No action is required.
<b>ISS.0097.0016E</b>	<b>Messaging Synchronizer cannot perform sync; Integration Server cannot connect to provider</b>
<b>Explanation</b>	Synchronization cannot occur because Integration Server cannot connect to the message provider.
<b>Action</b>	Make sure the message provider is running and that the message connection alias is enabled in Integration Server Administrator.
<b>ISS.0098.0003U</b>	<b>Exception occurred while decoding Broker Document {0} : {1}</b>
<b>Explanation</b>	Integration Server failed to decode the document received from the Broker. The document may be corrupt.
<b>Action</b>	Check the publisher of the document. Consider redelivering the document from the Broker.

---

<b>ISS.0098.0010U</b>	<b>Exception initializing Dispatcher configuration from file: {0}</b>
<b>Explanation</b>	Integration Server encountered the indicated exception while trying to initialize the Dispatcher. This is a serious internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0098.0023E</b>	<b>Document Router for Consumer Queue:{0} encountered error: {1}</b>
<b>Explanation</b>	Integration Server encountered an error while routing a document to a Broker.
<b>Action</b>	The action to take depends on the exception that occurred. Review the returned exception for more guidance.
<b>ISS.0098.0024U</b>	<b>No Trigger available for incoming Document {0}. Rejecting Document</b>
<b>Explanation</b>	Integration Server failed to deliver the incoming document to the trigger because there is not a trigger that subscribes to the document. The intended trigger may be disabled or deleted.
<b>Action</b>	Examine the existing triggers. If a trigger that subscribes to the document is disabled, enable it and ask the publisher to re-publish or deliver the document.
<b>ISS.0098.0025E</b>	<b>Document {0} from store {1} exceeded Redelivery Count.</b>
<b>ISS.0098.0029U</b>	<b>Exception while doing Request Reply: {0}</b>
<b>Explanation</b>	Integration Server encountered an internal error while executing a request reply.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0098.0030E</b>	<b>{0} received duplicate document(s). Error {1}</b>
<b>Explanation</b>	Integration Server determined that it received duplicate documents from a publisher.
<b>Action</b>	If you determine that the Integration Server did receive duplicate messages, check the publishing source to learn the source of the problem.  In some cases, Integration Server did not really receive duplicates. For example, two documents might use the same tracking ID but have different content. If Integration Server did not receive a duplicate document, try resubmitting the document using webMethods Monitor.

<b>ISS.0098.0031E</b>	<b>Consumer:{0} unable to persist Document(s) to Document Store. Error: {1}</b>
<b>Explanation</b>	Integration Server failed to write a document to the transient store. A likely cause is that the Integration Server JVM has run out of memory.
<b>Action</b>	Try increasing the heap size of the JVM. The heap size indicates how much memory is allotted for server processes.
<b>ISS.0098.0033E</b>	<b>Error while shutting down Dispatcher: {0}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0098.0036U</b>	<b>{0} encountered Transport Exception: {1}</b>
<b>Explanation</b>	Integration Server failed to publish the document because of one of the following:  1) The Broker is temporarily unavailable.  2) The client does not have the canPublish permission for its associate Broker document.  3) The document being published does not conform to the Broker document on the Broker. This may be because the document was not synchronized with the one on the Broker.  4) An internal error occurred.
<b>Action</b>	Do one of the following:  1) Check the Broker status. If the Broker or network connection is temporarily down, wait until they are up to re-publish the document.  2) Using the Broker administration tool, check the publication permissions of the client group to which the trigger client belongs. Make sure that the client is allowed to publish the document.  3)Synchronize the document and make sure that the document being published matches its associate Broker document type.  4) If the previous actions fail to correct the problem, contact Software AG Global Support.
<b>ISS.0098.0038E</b>	<b>{0} handling invalid Document. Exception: {1}</b>
<b>Explanation</b>	Integration Server encountered an error while processing a document. Specifically, the document does not have a corresponding publishable document type on the Integration Server or the publishable document type does not have a matching schema.
<b>Action</b>	Make sure that the appropriate document types and schemas for the document exist on the Integration Server.

---

<b>ISS.0098.0041E</b>	<b>Unable to connect to Broker. Starting to poll</b>
<b>ISS.0098.0044U</b>	<b>Exception while interacting with the Document Store name:{0} Problem:{1}</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0098.0045U</b>	<b>Unrecoverable Exception while initializing the Dispatcher: {0}</b>
<b>Explanation</b>	Integration Server encountered the indicated exception while trying to initialize the Dispatcher. This is an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0098.0047E</b>	<b>Connection to Broker unavailable. Unable to create transport for Trigger:{0}.</b>
<b>ISS.0098.0048U</b>	<b>Unable to remove subscription for Publishable Document {0} from transport:{1}. If connected, please remove subscription from {2} manually.</b>
<b>Explanation</b>	Integration Server failed to remove the document type subscription before unregistering the trigger. The Broker may be unavailable.
<b>Action</b>	In the Broker Administrator, check the status of the Broker and the network connection. If one or both are down, then you will need to manually remove the stale subscriptions for the trigger when they are back up.
<b>ISS.0098.0049U</b>	<b>Exception:{0} while executing trigger. {1} Document for TriggerStore:{2}.</b>
<b>Explanation</b>	Integration Server failed to execute the trigger. This indicates an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0098.0055U</b>	<b>Exception during attempt to register Trigger: {0}</b>
<b>Explanation</b>	Integration Server failed to register the trigger. This indicates an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0098.0056U</b>	<b>Unable to acknowledge Document {0} to transport for Trigger {1}. Exception:{2}</b>
<b>Explanation</b>	Integration Server encountered an internal error while acknowledging the document to the transport for the trigger.
<b>Action</b>	Contact Software AG Global Support.

<b>ISS.0098.0057U</b>	<b>Unable to delete Document Store for Trigger:{0}. Exception:{1}</b>
<b>Explanation</b>	Integration Server encountered an internal error while deleting the document store associated with the trigger.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0098.0058E</b>	<b>Stopping delivery of {1} to trigger {0} to prevent infinite loop.</b>
<b>ISS.0098.0059U</b>	<b>Exception while shutting down the Document Stores:{0}.</b>
<b>Explanation</b>	Integration Server encountered a serious internal error while shutting down.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0098.0060U</b>	<b>Exception while saving Dispatcher configuration :{0}.</b>
<b>Explanation</b>	Integration Server encountered an exception while trying to save Dispatcher configuration information to the dispatch.cnf file in the <IntegrationServer_dir>/config directory.
<b>Action</b>	If the dispatch.cnf file is set to read-only, change it to read/write. If the file is not set to read-only, this error indicates a serious internal error and you should contact Software AG Global Support.
<b>ISS.0098.0062E</b>	<b>{0} encountered Exception: {1}</b>
<b>ISS.0098.0073U</b>	<b>ControlledPublishOnSuccess max exceeded while processing {0}</b>
<b>Explanation</b>	Integration Server failed to publish a document because the maximum concurrent publish-on-success value was exceeded.
<b>Action</b>	Do one of the following:  1) On the Integration Server, increase the "concurrent publish on success" setting by editing the "watt.server.control.maxPublishOnSuccess" property.  2) Decrease the number of concurrent publish operations in the service.
<b>ISS.0098.0074E</b>	<b>Outbound msg store max exceeded, services blocking. Start broker to drain store.</b>

---

<b>ISS.0098.0075E</b>	<b>Insufficient memory while decoding event:{0} for {1}.</b>
<b>Explanation</b>	Integration Server does not have sufficient memory to decode the documents being retrieved from the Broker. Integration Server will attempt to decode the documents one more time.
<b>Action</b>	Check the size of the documents sent by the Broker and consider increasing the heap size of the Integration Server's JVM.
<b>ISS.0098.0076U</b>	<b>Unable to decode events for {0}. Please check JVM Heap size and/or size of Documents on the Broker.</b>
<b>Explanation</b>	Integration Server does not have sufficient memory to decode the documents from the Broker.
<b>Action</b>	Check the document size sent by the Broker and consider increasing the heap size of the JVM used by Integration Server.
<b>ISS.0098.0077E</b>	<b>Dispatcher out of memory. Retrying operation.</b>
<b>Explanation</b>	Integration Server does not have sufficient memory to continue its document publishing operations. Integration Server will attempt to process this message again.
<b>Action</b>	Consider increasing the heap size of the JVM used by Integration Server.
<b>ISS.0098.0078E</b>	<b>Dispatcher out of memory. Operation failed. Check error log.</b>
<b>Explanation</b>	Integration Server does not have sufficient memory to continue its document publishing operations. Integration Server has exceeded its retry count, and an exception will be thrown.
<b>Action</b>	Consider increasing the heap size of the JVM used by Integration Server.
<b>ISS.0098.0079E</b>	<b>Dispatcher out of memory. Retry succeeded.</b>
<b>Explanation</b>	Integration Server successfully retried a publishing operation after an OutOfMemory error prevented the operation from working the first time.
<b>Action</b>	If the Integration Server continues to issue this message, check the JVM Heap size and/or size of Documents on the Broker. The Trigger configuration (possibly the acknowledgment queue size) may need to be adjusted.
<b>ISS.0098.0080U</b>	<b>Insufficient memory while persisting messages for Trigger: {0}.</b>
<b>Explanation</b>	Integration Server does not have sufficient memory to persist the documents to the document store for the trigger.
<b>Action</b>	Check the size of the documents being persisted and consider increasing the heap size of the JVM used by Integration Server.

<b>ISS.0098.0081U</b>	<b>Insufficient memory while persisting message: {1} for Trigger: {0}.</b>
<b>Explanation</b>	Integration Server does not have sufficient memory to persist a single document to the document store for the trigger.
<b>Action</b>	Check the size of the document being persisted and consider increasing the heap size of the JVM used by Integration Server.
<b>ISS.0098.0082U</b>	<b>Unable to persist Document: {0} to Document Store: {1}. Exception: {2}</b>
<b>Explanation</b>	Integration Server failed to persist the document to the document store. This indicates a serious internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0098.0083U</b>	<b>Unable to acknowledge Document: {0} for Trigger Store: {1}. Insufficient memory.</b>
<b>Explanation</b>	Integration Server does not have sufficient memory to acknowledge the document to the document store.
<b>Action</b>	Check the size of the document being persisted and consider increasing the heap size of the JVM used by Integration Server.
<b>ISS.0098.0084U</b>	<b>Exception:{0} during Trigger dispatching.</b>
<b>Explanation</b>	Integration Server encountered an internal error while which processing a document destined for an individual trigger.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0098.0085U</b>	<b>Unable to remove all subscriptions for transport:{0} while unregistering trigger. If connected, please remove subscription from {1} manually.</b>
<b>Explanation</b>	Integration Server failed to remove all stale subscriptions before unregistering the trigger. The Broker may be unavailable.
<b>Action</b>	In the Broker Administrator, check the status of the Broker and the network connection. If one or both are down, then you will need to manually remove the stale subscriptions for the trigger when they are back up.
<b>ISS.0098.0086U</b>	<b>Unable to remove all subscriptions for transport:{0} before registering trigger. If connected, please remove stale subscriptions from {1} manually.</b>
<b>Explanation</b>	Integration Server failed to remove all stale subscriptions before registering the trigger. The Broker may be unavailable.
<b>Action</b>	In the Broker Administrator, check the status of the Broker and the network connection. If one or both are down, then you will need to manually remove the stale subscriptions for the trigger when the Broker and network are back up.

<b>ISS.0098.0087E</b>	<b>Duplicate document of type:{0} with Id:{1} received for trigger:{2}.</b>
<b>ISS.0098.0089U</b>	<b>Transaction size (no of documents * size of documents) is too large for Document Store: {0}. Please reduce capacity of Trigger and /or increase initial size of Document Stores.</b>
<b>Explanation</b>	The Integration Server failed to persist documents because the document store did not contain enough space. Documents received from the Broker are persisted in the triggers' persistent stores.
<b>Action</b>	In the Integration Server Administrator, click Settings>Resources>Document Stores. On this page, consider increasing the initial size of the document store. Also, consider reducing the number of triggers that subscribe to the document.
<b>ISS.0098.0090U</b>	<b>Size of Document: {0} for Document Store: {1} is too large. Server is unable to persist. Audit logging the document.</b>
<b>Explanation</b>	Integration Server failed to persist a document because the document store did not contain enough space.
<b>Action</b>	In the Integration Server Administrator, click Settings>Resources>Document Stores. On this page, consider increasing the initial size of the document store.
<b>ISS.0098.0096I</b>	<b>Integration Server is now connected to a Broker that tracks document redelivery counts. Restart the Integration Server to make use of redelivery counts in duplicate detection.</b>
<b>Explanation</b>	Integration Server connects to a version of the Broker that supports redelivery count. Previously it was connected to a Broker that did not support this feature.
<b>Action</b>	Restart Integration Server so that it can take advantage of the redelivery count feature supported by the Broker.
<b>ISS.0098.0100</b>	<b>Copying of documents to trigger store started.</b>
<b>ISS.0098.0103S</b>	<b>{0} not initialized. Adjust document store settings and restart server.</b>
<b>Explanation</b>	Integration Server was unable to create the Document Store on disk. The Document Store is essential for Integration Server functioning, therefore startup terminates.
<b>Action</b>	Check to see if there is enough disk space on the drive where the Document Store is being created (usually under <IS_SERVER_ROOT>\DocumentStore directory). If there is sufficient disk space, then check to see if the dispatch.cnf file under <IS_SERVER_ROOT>\config directory is corrupted. If the problem persists despite a re-start, contact Software AG Global Support.

**ISS.0098.0104I**      **Integration Server is now connected to a Broker that does not track document redelivery counts. Restart the Integration Server so that duplicate detection does not expect document redelivery counts.**

**Explanation**      Integration Server connects to a version of the Broker that does not support the redelivery count. Previously it was connected to a Broker that does support this feature.

**Action**              Restart the Integration Server so that its duplicate detection mechanism does not expect redelivery counts to be present in documents delivered by the Broker.

**ISS.0098.0105E**      **Unable to fully build comparable trigger: {0}**

**Explanation**      During Cluster Synchronization, Integration Server was unable to compare trigger nodes across all the nodes in the cluster. The most likely cause is that one or more triggers are not completely configured. Cluster Synchronization makes sure that changes made to a trigger's configuration on one Integration Server are propagated to other servers in the cluster. If an Integration Server is configured for Cluster Synchronization, this process runs when an administrator makes a trigger configuration change through the Integration Server Administrator or when a user-written service calls one of the pub.trigger:\* services.

**Action**              Using the development tool, check the trigger configuration. After correcting the problem, retry the task you were performing when the error occurred.

**ISS.0098.0106**      **Trigger comparison failed: trigger = {0}; parameter = {1}; local value = {2}; remote value = {3}.**

**ISS.0098.0107E**      **Error occurred during cluster invoke: Alias = {0}; Service = {1}; Exception = {2}.**

**Explanation**      During Cluster Synchronization, Integration Server threw an exception while invoking a service on a remote node in the cluster. Cluster Synchronization makes sure that changes made to a trigger's configuration on one Integration Server are propagated to other servers in the cluster. If an Integration Server is configured for Cluster Synchronization, this process runs when an administrator makes a trigger configuration change through the Server Administrator or when a user-written service calls one of the pub.trigger:\* services.

**Action**              The action you take depends on the exception issued. Look at the exceptionMessage for specific information.

**ISS.0098.0108**      **Serial trigger {0} has been automatically suspended due to an exception: {1}.**

---

ISS.0098.0109	Unable to establish secure connection to Broker. Password needed for SSL connection to Broker:{0}.
ISS.0098.0112	Trigger Resource Monitor now monitoring resource availability for trigger "{0}".
ISS.0098.0113	Trigger Resource Monitor invoked "{0}". Status of resource is "available".
ISS.0098.0114	Trigger Resource Monitor invoked "{0}". Status of resource is "not available".
ISS.0098.0115	Trigger Resource Monitor has resumed trigger "{0}".
ISS.0098.0116	Trigger Resource Monitor encountered an exception while attempting to resume trigger "{0}": {1}
ISS.0098.0117	The ISInternal functional alias is not configured properly on the JDBC Pools page. It is required in order to create and manage AND and XOR trigger joins. Assign a valid database pool and restart the Integration Server.
ISS.0098.0118	The ISInternal functional alias on the JDBC Pools page must be configured to use an external database in order to create and manage AND and XOR trigger joins.
ISS.0098.0119	Trigger Retry Failure occurred for trigger "{0}" : "{1}" . This trigger is being suspended and the message is being rolled back to the Broker because the Audit Logging subsystem also failed: "{2}"
ISS.0098.0120	The default Broker was detected while initializing the dispatch.cnf file. Broker Settings will automatically be enabled.
ISS.0098.0121	The default Broker was not detected while initializing the dispatch.cnf file. Broker Settings will automatically be disabled.

- ISS.0098.0122**      **The subscription for publishable document {0} will not be removed or recreated because the client prefix {1} used by the Broker connection for trigger {2} may be shared by multiple clients. If required, please remove subscription from Broker manually.**
- ISS.0098.0123**      **The subscription for publishable document {0} will not be removed or recreated because the client prefix {1} used by the Broker connection for trigger {2} may be shared by multiple clients. If required, please remove subscription from Broker manually.**
- ISS.0098.0124E**      **A username and password are required for Username/Password authentication.**  
**Explanation**      Authentication credentials were not specified.  
**Action**              Provide a username and password.
- ISS.0098.9002U**      **Required property missing for creating {0} transport: {1}**  
**Explanation**      Integration Server could not read properties from the  
 <IntegrationServer\_dir>\config\dispatch.cnf file. The file may be corrupt.  
**Action**              Examine the dispatch.cnf file to make sure that it is not corrupt and that the  
 "clientGroupName" and "brokerHost" fields exist. If the file is corrupt, rename it and  
 restart Integration Server. After you do this, you can re-configure the Broker Settings  
 using the Integration Server Administrator.
- ISS.0098.9005**      **Invalid connections properties for creating {0}**
- ISS.0098.9006U**      **No matching Document Type exists for {0}**  
**Explanation**      A pub.publish\* service returned an error because the document specified in the  
 "documentTypeName" parameter does not exist on the Integration Server.  
**Action**              Examine the input for the "documentTypeName" parameter. Make sure that the  
 parameter specifies the fully qualified name of the document type for which you want  
 to publish or deliver an instance. Keep in mind that document type names are  
 case-sensitive. Additionally, ensure that the specified document type exists on  
 Integration Server.
- ISS.0098.9007E**      **Data does not conform to the Publishable Document Type {0} errors: {1}**  
**Explanation**      A pub.publish\* service issued an error because the IData input for the "document"  
 parameter does not conform to the document type specified in the  
 "documentTypeName" parameter.  
**Action**              Examine the validation error message and the IData object passed to the "document"  
 parameter. Make sure that it conforms to the document type specified in the  
 "documentTypeName" parameter.

---

<b>ISS.0098.9008U</b>	<b>No registered Transport for the given id: {0}</b>
<b>Explanation</b>	Integration Server failed to create a subscription to the publishable document type specified in a trigger. The transport information does not exist, which indicates an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0098.9009</b>	<b>Certificate file require for using SSL encryption</b>
<b>ISS.0098.9010E</b>	<b>No waiting thread for Document Id: {0}. Requestor might have timed out.</b>
<b>Explanation</b>	Integration Server encountered an internal error while publishing the document and waiting for a reply.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0098.9011U</b>	<b>{0} is not a Publishable Document Type.</b>
<b>Explanation</b>	A pub.publish* service returned an error because the document type specified in the "documentTypeName" parameter was not publishable.
<b>Action</b>	Ensure that the Publishable property is set to "true" for the document type."
<b>ISS.0098.9013U</b>	<b>Dispatcher is not initialized</b>
<b>Explanation</b>	Integration Server was not able to publish, deliver, or reply to a document because the dispatcher that is responsible for performing these operations was not initialized.
<b>Action</b>	Log on to the Integration Server Administrator and make sure that you have correctly configured Integration Server for document publishing.
<b>ISS.0098.9014U</b>	<b>BrokerException: {0}</b>
<b>Explanation</b>	Integration Server was unable to publish or retrieve documents from the Broker because the operation failed on the Broker.
<b>Action</b>	Examine the error message provided by the Broker. Refer to the webMethods Broker API documentation for the Java Client for a detailed description of the error.
<b>ISS.0098.9015</b>	<b>Rejected document because Dispatcher was unable to deliver document after {0} attempts</b>

**ISS.0098.9016U**      **Broker Transport unable to subscribe to Publishable Document Type:{0} BrokerEvent Type:{1}**

**Explanation**      Integration Server failed to create a subscription to the publishable document type specified in a trigger. The client is not allowed to subscribe to the Broker document type associated with the publishable document type.

**Action**              In the Broker Administrator, check the subscription permissions of the client group to which the trigger belongs. Make sure that the client is allowed to subscribe to the Broker document type associated with the publishable document type.

**ISS.0098.9017**      **Rejecting document as there is no enabled Trigger registered:**

**ISS.0098.9018E**      **Unrecoverable Error while initializing the webMethods Messaging Subsystem (Dispatcher): {0}. No webMethods Messaging features will be available until this issue is resolved and the server is restarted.**

**Explanation**      Integration Server encountered an internal error.

**Action**              Contact Software AG Global Support.

**ISS.0098.9019U**      **Request timed out while waiting for reply**

**Explanation**      Integration Server encountered an internal error while publishing or delivering the document and waiting for a reply.

**Action**              Contact Software AG Global Support.

**ISS.0098.9021U**      **Received incorrect document as Reply. Expecting {0} and received {1}**

**Explanation**      Integration Server failed to receive the expected reply document while publishing or delivering the document and waiting for a reply.

**Action**              Check the subscriber of the publisher document. Make sure that the subscriber delivers a correct reply document.

**ISS.0098.9022E**      **Invalid DispatcherMessage {0}**

**Explanation**      Integration Server failed to deliver the document to the subscribing triggers. The document is null, which indicates an internal error.

**Action**              Contact Software AG Global Support.

<b>ISS.0098.9023U</b>	<b>Transport Factory: {0} not found.</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0098.9024U</b>	<b>{0} Unknown Transport Type specified. Unable to create transport.</b>
<b>Explanation</b>	Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0098.9025U</b>	<b>{0} not configured. {1} operation can only be done after a {0} is configured.</b>
<b>Explanation</b>	The pub.publish:deliver or pub.publish:deliverAndWait service failed to execute because Integration Server is not configured to connect to the Broker.
<b>Action</b>	Use Integration Server Administrator to configure the server to connect to a Broker.
<b>ISS.0098.9027U</b>	<b>Unknown broker version.</b>
<b>Explanation</b>	Integration Server failed to connect to the Broker because the version of the Broker is not supported.
<b>Action</b>	Do not attempt to set up such an environment. See the "Installing webMethods Products" for supported configurations.
<b>ISS.0098.9028</b>	<b>Incompatible Broker version. The minimum Broker version required is 6.0.</b>
<b>ISS.0098.9033E</b>	<b>Duplicate condition name "{1}" in Trigger "{0}"</b>
<b>Explanation</b>	Integration Server could not save the condition settings of a trigger because the trigger has duplicate condition names.
<b>Action</b>	Edit the trigger so that each condition has a unique name.
<b>ISS.0098.9034E</b>	<b>Condition name "{0}" - Cannot have duplicate document types in AND join.</b>
<b>Explanation</b>	Integration Server could not save a trigger because a condition has duplicate document types in an "AND" join.
<b>Action</b>	Edit the trigger condition to make sure that unique document types are specified in the "AND" join.

<b>ISS.0098.9035E</b>	<b>Cannot specify different filters for document type "{0}" within a single trigger</b>
<b>Explanation</b>	Integration Server could not save the condition settings of a trigger because more than one filter is specified for a document type in the trigger.
<b>Action</b>	If multiple conditions in the trigger specify the same document type, make sure that the filter applied to the document type is the same for each condition.
<b>ISS.0098.9036U</b>	<b>Unable to ack</b>
<b>Explanation</b>	Integration Server failed to acknowledge the document to the trigger document store. This indicates an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0098.9050U</b>	<b>Unable to publish volatile Document: {0}. Broker not connected.</b>
<b>Explanation</b>	Integration Server published a volatile document while the Broker was down. A service exception occurred for the publishing service and the volatile document was lost.
<b>Action</b>	Make sure the Broker is available and re-publish the document.
<b>ISS.0098.9051U</b>	<b>No activation specified for Join Document:{0}.</b>
<b>Explanation</b>	The published document cannot be processed in a join because it is missing an activation ID.
<b>Action</b>	The publisher of the document needs to set an activation ID for the document.
<b>ISS.0098.9056U</b>	<b>cmd for msgs all not the same or null</b>
<b>Explanation</b>	A flow service mixed the pub.publish:deliver and pub.publish:publish steps when the "delayUntilServiceSuccess" parameter is set to "true".
<b>Action</b>	Use separate flow services to deliver and publish a message when the "delayUntilServiceSuccess" parameter is set to "true".
<b>ISS.0098.9057U</b>	<b>destination for msgs all not the same or null</b>
<b>Explanation</b>	A flow service contains multiple pub.publish:deliver steps where the "delayUntilServiceSuccess" parameter is set to "true", but the destination IDs are not identical.
<b>Action</b>	Use separate flow services to deliver a message to different destination IDs when the "delayUntilServiceSuccess" parameter is set to "true".

<b>ISS.0098.9058E</b>	<b>publish-on-success is suspended</b>
<b>Explanation</b>	The publish-on-success facility has been programmatically suspended. Therefore, the publish-on-success operation will not work.
<b>Action</b>	Restart the Integration Server.
<b>ISS.0098.9059E</b>	<b>max concurrent publish-on-success is exceeded</b>
<b>Explanation</b>	The watt.server.control.maxPublishOnSuccess parameter was exceeded by a publishing flow. The maxPublishOnSuccess parameter controls the maximum number of documents that Integration Server publishes on success at one time.
<b>Action</b>	Decrease the number of documents published by a flow service that uses publish-on-success, or increase the value of the maxPublishOnSuccess parameter.
<b>ISS.0098.9061</b>	<b>Document store runtime capacity</b>
<b>ISS.0098.9062U</b>	<b>Document store is missing for {2}</b>
<b>Explanation</b>	Integration Server encountered an internal error in the document store.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0098.9063</b>	<b>Step size for {2} must be positive and no greater than 100: {3}</b>
<b>ISS.0098.9064</b>	<b>Unable to mark as complete to the Document History</b>
<b>ISS.0098.9065E</b>	<b>Error reply {0} received. adapterType:{1}, errorCategory:{2},errorText:{3},eventId:{4}</b>
<b>Explanation</b>	A client, typically an Integration Server but possibly a Broker client or Adapter, sent a request document to an Integration Server, but received an error reply (a document of type pub.publish.notification:error ) in response. This happens when the service executing the request document on the target server encounters an error. Instead of sending the expected reply document type, it sends an error document indicating it could not process the request document correctly.
<b>Action</b>	Check the Error log of the target Integration Server, that is, the Integration Server to which the request document was sent. If the error occurred when a document was being published to a single subscriber, you will know which target server issued the error reply. However, if the error occurred during a publish to multiple Integration Servers, you will have to determine which target server issued the error.

<b>ISS.0098.9066E</b>	<b>Missing required parameter: "{0}".</b>
<b>Explanation</b>	A client tried to invoke a service, but did not specify a required parameter.
<b>Action</b>	Supply the missing required parameter.
<b>ISS.0098.9067E</b>	<b>Trigger not found for triggerName: "{0}".</b>
<b>Explanation</b>	Integration Server tried to suspend or fetch metadata for the indicated trigger, but there is no trigger with this name enabled on Integration Server.
<b>Action</b>	Make sure the trigger name is typed correctly and that the trigger is enabled.
<b>ISS.0098.9068E</b>	<b>Unable to get status for Trigger "{0}": No IControlObject found.</b>
<b>Explanation</b>	Integration Server encountered an error while trying to perform an action against a trigger, but the trigger was not completely configured, and as a result, not fully initialized.
<b>Action</b>	Verify that the trigger is properly configured and is considered to be valid. After correcting the problem, retry the task you were performing when the error occurred.
<b>ISS.0098.9069E</b>	<b>Unable to get status for Trigger "{0}": {1}</b>
<b>Explanation</b>	Integration Server encountered an error while trying to perform an action against a trigger.  - For trigger retrieval, the status indicates whether the trigger is active or suspended.  - For trigger processing, the status indicates whether the trigger is active or suspended and shows the current threads being used, the current volatile queue size, and the current persisted queue size.
<b>Action</b>	The action you take depends on the exception issued. Look at the exception message and the server log for additional details.
<b>ISS.0098.9072E</b>	<b>Trigger "{0}" is locked. Change not permitted.</b>
<b>Explanation</b>	A user tried to modify the indicated trigger using the Trigger Management screens in Integration Server Administrator or the built-in services, but the trigger is locked.
<b>Action</b>	Unlock the trigger and try again.
<b>ISS.0098.9073E</b>	<b>Unable to suspend document {0} for Trigger "{1}": No IControlObject found.</b>
<b>Explanation</b>	A request to suspend document processing failed. The most likely cause is that the trigger was not completely configured, and as a result, not fully initialized.
<b>Action</b>	Make sure the trigger is configured properly and is considered to be valid. After correcting the problem, retry the task you were performing when the error occurred.

---

<b>ISS.0098.9074E</b>	<b>Unable to suspend document {0} for Trigger "{1}": {2}</b>
<b>Explanation</b>	A request to suspend document processing failed due to the indicated exception.
<b>Action</b>	The action you take depends on the exception issued. Look at the exception message value in the message for specific information.
<b>ISS.0098.9075E</b>	<b>Unable to resume document {0} for Trigger "{1}": No IControlObject found.</b>
<b>Explanation</b>	A request to resume document processing failed. The most likely cause is that the trigger was not completely configured, and as a result, not fully initialized.
<b>Action</b>	Make sure the trigger is properly configured and is considered to be valid. After correcting the problem, retry the task you were performing when the error occurred.
<b>ISS.0098.9076E</b>	<b>Unable to resume document {0} for Trigger "{1}": {2}</b>
<b>Explanation</b>	A request to resume document processing failed due to an exception.
<b>Action</b>	The action you take depends on the exception issued. Look at the exception message value in the message for specific information.
<b>ISS.0098.9077E</b>	<b>Unable to persist the change made to Trigger "{0}": {1}</b>
<b>Explanation</b>	The configuration change for a trigger was not saved to file. As a result, the change will revert back to its original value after Integration Server restarts or someone reloads the package.
<b>Action</b>	The action you take depends on the exception issued. Look at the exception message value in the message for specific information.
<b>ISS.0098.9078E</b>	<b>maxExecutionThreads cannot exceed queueCapacity</b>
<b>Explanation</b>	The value specified for the number of maximum execution threads exceeds the queue capacity. This is not permitted because the number of documents the Integration Server can process concurrently (maxExecutionThreads) cannot exceed the maximum number of documents that can be in the trigger's queue (queueCapacity).
<b>Action</b>	Change the maximum execution threads value to be less than or equal to the queue capacity. Alternatively, change the queue capacity value so that it is greater than or equal to the maximum execution threads.
<b>ISS.0098.9079E</b>	<b>queueRefillLevel cannot exceed queueCapacity</b>
<b>Explanation</b>	The value specified for the queue refill level exceeds the queue capacity. The queue refill level is the number of unprocessed documents that must remain in the trigger queue before Integration Server retrieves more documents for the queue from the Broker. This level cannot exceed the maximum number of documents that can be in the trigger's queue (queueCapacity).

**Action** Change the queue refill level value so that it is less than or equal to the queue capacity. Alternatively, change the queue capacity value so that it is greater than or equal to the queue refill level.

**ISS.0098.9080E** **{0} must be a positive number.**  
**Explanation** The value specified for the indicated parameter was zero or a negative number. This value must be positive number.  
**Action** Supply a positive number for the indicated parameter.

**ISS.0098.9081** **Unable to publish Document: {0}. Broker not connected.**

**ISS.0098.9082** **Unable to create trigger "{0}": {1}**

**ISS.0098.9083** **Unable to create trigger "{0}". Invalid Trigger Name.**

**ISS.0098.9084** **Unable to create trigger "{0}". Invalid NSName.**

**ISS.0098.9085** **Unable to create trigger "{0}". Package "{1}" does not exist.**

**ISS.0098.9086** **Unable to create trigger "{0}": Insufficient Write ACL privileges.**

**ISS.0098.9087** **Unable to create trigger "{0}". A trigger with this name already exists.**

**ISS.0098.9088** **{0} must me greater than 0 or -1.**

**ISS.0098.9089** **{0} must me greater than or equal to 0.**

**ISS.0098.9090** **Unable to publish to the broker the Document: {0}. Sync the document with the broker.**

---

<b>ISS.0098.9092W</b>	<b>Filter cannot be migrated to UM Provider Filter, it uses an unsupported construct:{0}.</b>
<b>Explanation</b>	The contents of the Filter field could not be migrated to the Provider Filter (UM) field because the filter contains the specified unsupported constructs. At run time, the unsupported constructs replace {0}, {1}, and {2}.
<b>Action</b>	No action is required. The contents of the Filter field will not change. The trigger will apply the filter to any messages that it receives. Note that while Broker might have applied portions of the filter to received messages before routing the message to the trigger, once the trigger and its document types have been updated to work with Universal Messaging, the contents of the Filter field become a local filter only. If you want the filter to become a provider filter applied by Universal Messaging, you must specify a filter in the Provider Filter (UM) field.
<b>ISS.0098.9093W</b>	<b>Filter cannot be completely migrated to Provider Filter (UM). Contains duplicate field name:{0}.</b>
<b>Explanation</b>	The contents of Filter could not be migrated to Provider Filter (UM) because the filter contains the specified duplicate field name. Universal Messaging cannot filter on duplicate field names because duplicate field names cannot be encoded as protocol buffers.
<b>Action</b>	No action is required. The contents of the Filter field will not change. The trigger will apply the filter to any messages that it receives. Note that while Broker might have applied portions of the filter to received messages before routing the message to the trigger, once the trigger and its document types have been updated to work with Universal Messaging, the contents of the Filter field become a local filter only. If you want the filter to become a provider filter applied by Universal Messaging, you must specify a filter in the Provider Filter (UM) field.
<b>ISS.0098.9094W</b>	<b>Filter cannot be completely migrated to Provider Filter (UM). Contains field with an invalid name:{0}.</b>
<b>Explanation</b>	The contents of Filter could not be migrated to Provider Filter (UM) because the filter contains a name considered to be invalid by Universal Messaging or a field name that cannot be encoded as protocol buffers.
<b>Action</b>	No action is required. The contents of the Filter field will not change. The trigger will apply the filter to any messages that it receives. Note that while Broker might have applied portions of the filter to received messages before routing the message to the trigger, once the trigger and its document types have been updated to work with Universal Messaging, the contents of the Filter field become a local filter only. If you want the filter to become a provider filter applied by Universal Messaging, you must specify a filter in the Provider Filter (UM) field.

**ISS.0098.9095W**      **Filter cannot be completely migrated to Provider Filter (UM). Contains an Object or Object List field:{0}.**

**Explanation**      The contents of Filter could not be migrated to Provider Filter (UM) because the filter contains a field of type Objects and Object Lists which is defined to be an unknown Java wrapper type. Object and Object Lists defined to be an unknown Java wrapper type cannot be encoded with protocol buffers.

**Action**      No action is required. The contents of the Filter field will not change. The trigger will apply the filter to any messages that it receives. Note that while Broker might have applied portions of the filter to received messages before routing the message to the trigger, once the trigger and it's document types have been updated to work with Universal Messaging, the contents of the Filter field become a local filter only. If you want the filter to become a provider filter applied by Universal Messaging, you must specify a filter in the Provider Filter (UM) field.

**ISS.0098.9096W**      **Filter cannot be completely migrated to Provider Filter (UM). Contains an invalid AND condition:{0} - {1}.**

**Explanation**      The contents of Filter could not be migrated to Provider Filter (UM) because the filter contains an AND condition that specifies a null value. Because a null value cannot be included in a protocol buffer message, a filter that checks for a null value is invalid.

**Action**      No action is required. The contents of the Filter field will not change. The trigger will apply the filter to any messages that it receives. Note that while Broker might have applied portions of the filter to received messages before routing the message to the trigger, once the trigger and it's document types have been updated to work with Universal Messaging, the contents of the Filter field become a local filter only. If you want the filter to become a provider filter applied by Universal Messaging, you must specify a filter in the Provider Filter (UM) field.

**ISS.0098.9097W**      **Filter cannot be completely migrated to Provider Filter (UM). Contains an invalid FUNCTION.**

**Explanation**      The contents of Filter could not be migrated to Provider Filter (UM) because the filter contains an invalid FUNCTION.

**Action**      No action is required. The contents of the Filter field will not change. The trigger will apply the filter to any messages that it receives. Note that while Broker might have applied portions of the filter to received messages before routing the message to the trigger, once the trigger and it's document types have been updated to work with Universal Messaging, the contents of the Filter field become a local filter only. If you want the filter to become a provider filter applied by Universal Messaging, you must specify a filter in the Provider Filter (UM) field.

---

<b>ISS.0098.9098W</b>	<b>Filter cannot be completely migrated to Provider Filter (UM). Contains an invalid comparator value:{0} - {1}.</b>
<b>Explanation</b>	The contents of Filter could not be migrated to Provider Filter (UM) because the filter contains a comparison considered invalid by Universal Messaging or protocol buffers. At run time, the {0} in the message is replaced the contents of the left side of the expression and {1} is replaced by the contents of the right side of the expression.
<b>Action</b>	No action is required. The contents of the Filter field will not change. The trigger will apply the filter to any messages that it receives. Note that while Broker might have applied portions of the filter to received messages before routing the message to the trigger, once the trigger and it's document types have been updated to work with Universal Messaging, the contents of the Filter field become a local filter only. If you want the filter to become a provider filter applied by Universal Messaging, you must specify a filter in the Provider Filter (UM) field.
<b>ISS.0098.9099W</b>	<b>Filter cannot be completely migrated to Provider Filter (UM). Contains a NULL comparator value:{0} - {1}.</b>
<b>Explanation</b>	The contents of Filter could not be migrated to Provider Filter (UM) because the filter compares a field to a NULL value. Because a null value cannot be included in a protocol buffer message, a filter that checks for a null value is invalid.
<b>Action</b>	No action is required. The contents of the Filter field will not change. The trigger will apply the filter to any messages that it receives. Note that while Broker might have applied portions of the filter to received messages before routing the message to the trigger, once the trigger and it's document types have been updated to work with Universal Messaging, the contents of the Filter field become a local filter only. If you want the filter to become a provider filter applied by Universal Messaging, you must specify a filter in the Provider Filter (UM) field.
<b>ISS.0098.9100W</b>	<b>Filter cannot be completely migrated to Provider Filter (UM). Contains a REGEX value:{0} {1}.</b>
<b>Explanation</b>	The contents of Filter could not be migrated to Provider Filter (UM) because the filter contains a regular expression. Universal Messaging filtering syntax does not support the use of regular expressions.
<b>Action</b>	No action is required. The contents of the Filter field will not change. The trigger will apply the filter to any messages that it receives. Note that while Broker might have applied portions of the filter to received messages before routing the message to the trigger, once the trigger and it's document types have been updated to work with Universal Messaging, the contents of the Filter field become a local filter only. If you want the filter to become a provider filter applied by Universal Messaging, you must specify a filter in the Provider Filter (UM) field.

**ISS.0098.9101W**      **Filter cannot be completely migrated to Provider Filter (UM). Contains an invalid Boolean value:{0}.**

**Explanation**      The contents of Filter could not be migrated to Provider Filter (UM) because the filter contains an invalid value for a field or type Boolean.

**Action**      No action is required. The contents of the Filter field will not change. The trigger will apply the filter to any messages that it receives. Note that while Broker might have applied portions of the filter to received messages before routing the message to the trigger, once the trigger and it's document types have been updated to work with Universal Messaging, the contents of the Filter field become a local filter only. If you want the filter to become a provider filter applied by Universal Messaging, you must specify a filter in the Provider Filter (UM) field.

**ISS.0098.9102W**      **Filter cannot be completely migrated to Provider Filter (UM). Contains an invalid OR condition:{0} - {1}.**

**Explanation**      The contents of Filter could not be migrated to Provider Filter (UM) because the filter contains an OR condition that specifies a null value. Because a null value cannot be included in a protocol buffer message, a filter that checks for a null value is invalid. At run time, the {0} in the message is replaced the contents of the left side of the expression and {1} is replaced by the contents of the right side of the expression.

**Action**      No action is required. The contents of the Filter field will not change. The trigger will apply the filter to any messages that it receives. Note that while Broker might have applied portions of the filter to received messages before routing the message to the trigger, once the trigger and it's document types have been updated to work with Universal Messaging, the contents of the Filter field become a local filter only. If you want the filter to become a provider filter applied by Universal Messaging, you must specify a filter in the Provider Filter (UM) field.

**ISS.0098.9103W**      **Filter cannot be completely migrated to Provider Filter (UM). Contains an invalid NOT condition:{0}.**

**Explanation**      The contents of Filter could not be migrated to Provider Filter (UM) because the filter contains an invalid value in a NOT condition.

**Action**      No action is required. The contents of the Filter field will not change. The trigger will apply the filter to any messages that it receives. Note that while Broker might have applied portions of the filter to received messages before routing the message to the trigger, once the trigger and it's document types have been updated to work with Universal Messaging, the contents of the Filter field become a local filter only. If you want the filter to become a provider filter applied by Universal Messaging, you must specify a filter in the Provider Filter (UM) field.

---

<b>ISS.0098.9104E</b>	<b>{0} operation is not supported when connection alias type is Local.</b>
<b>Explanation</b>	The documentTypeName input parameter specifies a publishable document type that uses the IS_LOCAL_CONNECTION alias. Instances of publishable document types that use the IS_LOCAL_CONNECTION messaging connection alias cannot be delivered.
<b>Action</b>	Change the documentTypeName input parameter value to be a publishable document type associated with a Universal Messaging connection alias or a Broker connection alias and then re-execute the service. If you want to publish a document locally, use the pub.publish:publish service or the pub.publish:publishAndWait service.
<b>ISS.0098.9105E</b>	<b>Cannot specify different provider filters for document type "{0}" within a single UM trigger</b>
<b>Explanation</b>	If a webMethods messaging trigger that receives messages from Universal Messaging specifies the same publishable document type in more than one condition, the conditions must specify the same provider filter. That is, the contents of the Provide Filter (UM) column must be the same for each condition that subscribes to the same publishable document type.
<b>Action</b>	Revise the contents of the Provider Filter (UM) column to be the same for each condition that subscribes to the same publishable document type.
<b>ISS.0099.0001U</b>	<b>Broker Transport:{0} unable to subscribe to Broker Document {1}. Exception {2}</b>
<b>Explanation</b>	The Integration Server failed to create the subscription for the trigger on the Broker. The Broker may be unavailable.
<b>Action</b>	In the Broker Administrator, check the status of the Broker and the network connection. If all are correct, then this is an internal error. Contact Software AG Global Support.
<b>ISS.0099.0002U</b>	<b>Broker Transport:{0} unable to unsubscribe to Broker Document {1}. Exception {2}</b>
<b>Explanation</b>	The Integration Server failed to cancel the subscription for the trigger from the Broker after removing the trigger from the Integration Server. The Broker might be unavailable.
<b>Action</b>	In the Broker Administrator, check the status of the Broker and the network connection. If all are correct, then this is an internal error. Contact Software AG Global Support.
<b>ISS.0099.0003U</b>	<b>Unable to create Broker Transport {0}. Exception {1}</b>
<b>Explanation</b>	The Integration Server failed to create the Broker transport for the Broker client because the client could not reconnect to the Broker. The Broker might be temporarily unavailable.
<b>Action</b>	In the Broker Administrator, check the status of the Broker and the network connection. If all are correct, then this is an internal error. Contact Software AG Global Support.

<b>ISS.0099.0005E</b>	<b>Creating subscription on Broker without invalid filter: {0}</b>
<b>Explanation</b>	A trigger contains an invalid filter. The subscription was created on the Broker without the invalid filter.
<b>Action</b>	Change the filter in the trigger to a valid trigger.
<b>ISS.0099.0006U</b>	<b>Unable to disconnect Broker Transport. Exception: {0}</b>
<b>Explanation</b>	Integration Server failed to disconnect from the Broker during shutdown. This indicates an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0099.0007U</b>	<b>BrokerTransport:{0} got Exception: {1}</b>
<b>Explanation</b>	The Integration Server encountered an internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0099.0008U</b>	<b>Insufficient memory while retrieving events for BrokerTransport:{0}</b>
<b>Explanation</b>	The Integration Server does not have sufficient memory to retrieve even one document from the Broker.
<b>Action</b>	From the Broker, check the size of the document. Consider increasing the heap size of the JVM used by Integration Server.
<b>ISS.0099.0009U</b>	<b>Unable to retrieve events from the Broker for BrokerTransport:{0}. Insufficient JVM memory. Please check Heap size/ size of Documents on the Broker.</b>
<b>Explanation</b>	The Integration Server does not have sufficient memory to retrieve documents from the Broker.
<b>Action</b>	From the Broker, check the size of the documents. Consider increasing the heap size of the JVM used by Integration Server.
<b>ISS.0099.0010U</b>	<b>Broker Transport:{0} failed to unsubscribe to all Broker Documents. Exception {1}</b>
<b>Explanation</b>	The Integration Server failed to cancel the subscriptions from the Broker while removing the trigger from the Integration Server. The Broker might be unavailable.
<b>Action</b>	In the Broker Administrator, check the status of the Broker and the network connection. If all are correct, then this is an internal error. Contact Software AG Global Support.

<b>ISS.0099.0011E</b>	<b>Broker Transport Factory unable to retrieve password for handle {0}</b>
<b>Explanation</b>	An internal error occurred.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0099.0012E</b>	<b>{0} failed to retrieve password for handle {1}. Exception {2}</b>
<b>Explanation</b>	An internal error occurred.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0099.0013E</b>	<b>{0} failed to save password for handle {1}. Exception {2}</b>
<b>Explanation</b>	An internal error occurred.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0099.0014E</b>	<b>{0} failed to refresh broker settings. Exception type {1}, msg {2}</b>
<b>Explanation</b>	An error occurred while saving broker settings to disk.
<b>Action</b>	Read through the details provided in the exception and take corrective steps. If you are not able to resolve the problem, contact Software AG Global Support.
<b>ISS.0099.0015E</b>	<b>BrokerTransport : Broker Timing out repetitively. New subscriptions won't get created and if subscriptions are already existing,this might lead to the client queue growing on the broker</b>
<b>Explanation</b>	An attempt to create a new subscription has timed out multiple times.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0100.0036E</b>	<b>{0} getReader() has already been called for this request</b>
<b>Explanation</b>	A servlet or JSP called the ServletRequest.getInputStream() method after it had already called the ServletRequest.getReader() method. The servlet or JSP can call one method or the other, not both.
<b>Action</b>	Check the servlet or JSP and ensure that only one of these methods is called.
<b>ISS.0100.9900U</b>	<b>The {0} action is not enclosed by a {1} action.</b>
<b>Explanation</b>	Integration Server was not able to execute a Web application because there are syntax errors in the JSP file.
<b>Action</b>	Examine the error message to determine which tag name caused the exception to be thrown. Then check the JSP file that contains the tags and look for syntax errors. See the "Web Applications Developer's Guide" for the correct usage. After you fix the problem, re-deploy the Web application on Integration Server.

<b>ISS.0100.9901U</b>	<b>The {0} action is not enclosed by a {1} action at {2}.</b>
<b>Explanation</b>	Integration Server was not able to execute a web application because there was a syntax error in the <webm:ifvar> and <webm:else> tags in the JSP file.
<b>Action</b>	Examine the JSP file that contains the <webm:ifvar> and <webm:else> tags. See the "webMethods Applications Developer's Guide" for the correct usage of these tags. After you fix the problem, re-deploy the Web application on Integration Server.
<b>ISS.0105.0003E</b>	<b>Cannot get canonicalKey: {0}</b>
<b>Explanation</b>	The pub.synchronization.xref:getCanonicalKey service failed to execute because an exception was thrown when Integration Server tried to retrieve the corresponding canonical key for the specified native ID from the repository.
<b>Action</b>	Examine the exception message and stack trace for details. Verify that you have provided correct input for the "appID", "nativeID", and "objectID" parameters. If you cannot find the cause for the problem, contact Software AG Global Support.
<b>ISS.0105.0005E</b>	<b>Cannot insert into database this record, appId="{0}", nativeId="{1}", canonicalKey="{2}", objId="{3}", error: {4}</b>
<b>Explanation</b>	The pub.synchronization.xref:createXReference service or pub.synchronization.xref:insertXReference service failed to execute because an exception was thrown when Integration Server tried to insert or create the cross-reference record in the repository.
<b>Action</b>	Examine the error stack trace to determine which exception was thrown. If it was a SQLException, check the webMethods Integration Server documentation to make sure that you have set up your JDBC Pool configurations correctly. If you cannot determine the cause of the problem, contact Software AG Global Support.
<b>ISS.0105.0006E</b>	<b>Cannot close latch: {0}</b>
<b>Explanation</b>	The "pub.synchronization.latch:closeLatch" service failed to execute because an exception was thrown when Integration Server tried to close the latch for a given application ID, canonical Key, and object ID.
<b>Action</b>	Examine the error stack trace to determine which exception was thrown. If it was a SQLException, check the webMethods Integration Server documentation to make sure you have set up your JDBC Pool configurations correctly. If you cannot determine the cause of the problem, contact Software AG Global Support.
<b>ISS.0105.0007E</b>	<b>Cannot open latch: {0}</b>
<b>Explanation</b>	The "pub.synchronization.latch:closeLatch" service failed to execute because an exception was thrown when the Integration Server tried to open the latch for a given application ID, canonical Key, and object ID.
<b>Action</b>	Examine the error stack trace to determine which exception was thrown. If it was a SQLException, check "Installing webMethods Products" to make sure you have set

up your JDBC Pool correctly. If you cannot determine the cause of the problem, contact Software AG Global Support.

<b>ISS.0105.0008E</b>	<b>Cannot get nativeId: {0}</b>
<b>Explanation</b>	The "pub.synchronization.xref:getNativeId" service failed to execute because an exception was thrown when the Integration Server tried to retrieve the native ID for a given canonical key, application ID, and object ID.
<b>Action</b>	Examine the error stack trace to determine which exception was thrown. If it was a SQLException, check "Installing webMethods Products" to make sure you have set up your JDBC Pool configurations correctly. If you cannot determine the cause of the problem, contact Software AG Global Support.
<b>ISS.0105.0009E</b>	<b>Cannot obtain a JDBC connection: {0}</b>
<b>Explanation</b>	The Integration Server was not able to obtain a connection to the JDBC database where cross-reference keys and echo suppression status are stored. A likely cause is that the pool alias for this database was specified incorrectly on the Settings>JDBC Pools page of the Server Administrator.
<b>Action</b>	From the Settings>JDBC Pools page of the Server Administrator, examine the pool alias properties for the Xref and make sure it specifies the correct Database URL, User Id, Password, and Database driver. Then, restart the Integration Server.
<b>ISS.0105.0010E</b>	<b>No JDBC connection available</b>
<b>Explanation</b>	The Integration Server was not able to obtain a connection to the JDBC database where the cross-reference keys and echo suppression status are stored. A likely cause is that no JDBC pool connections are available.
<b>Action</b>	From the Settings > JDBC Pools page of the Integration Server Administrator, examine the pool alias properties for the Xref and consider increasing the number of connections. Then, restart Integration Server.
<b>ISS.0105.0011E</b>	<b>Release JDBC connection error: {0}</b>
<b>Explanation</b>	Integration Server tried to perform a database operation, but the "pub.synchronization*" service failed to release its connection to the database. This indicates an internal error.
<b>Action</b>	Contact Software AG Global Support.

<b>ISS.0105.0012E</b>	<b>Get preparedStatement error: {0}</b>
<b>Explanation</b>	While trying to perform a database operation, a "pub.synchronization*" service encountered an SQLException.
<b>Action</b>	Examine the error stack trace to determine which SQL exception was thrown. Make sure you followed the instructions in the "webMethods Integration Server documentation and set up the Database correctly. If you cannot determine the cause of the error, contact the database vendor.
<b>ISS.0105.0013E</b>	<b>Check isLatchClosed error: {0}</b>
<b>Explanation</b>	The pub.synchronization.latch:isLatchClosed service threw an exception when it tried to check the latch status for a given canonical key, application ID, and object ID.
<b>Action</b>	Examine the error stack trace to determine which exception was thrown. If it was a SQLException, check "Installing webMethods Products" to make sure you have set up your JDBC Pool correctly. If you cannot determine the cause of the problem, contact Software AG Global Support.
<b>ISS.0105.0014E</b>	<b>Drop all records with objId="{0}", error: {1}</b>
<b>Explanation</b>	The "pub.synchronization.xref:deleteByObjectId" service threw an exception when it tried to remove all cross-reference records associated with a particular process or synchronization.
<b>Action</b>	Examine the error stack trace to determine which exception was thrown. If it was a SQLException, check the webMethods Integration Server documentation to make sure that you have set up your JDBC Pool configurations correctly. If you cannot determine the cause of the problem, contact Software AG Global Support.
<b>ISS.0105.0024E</b>	<b>Delete xref record: appId="{0}", canonicalKey="{1}", objId="{2}", error: {3}</b>
<b>Explanation</b>	The pub.synchronization.xref:deleteXReference service threw an exception when it tried to remove all cross-reference records associated with a particular process or synchronization.
<b>Action</b>	Examine the error stack trace to determine which exception was thrown. If it was a SQLException, check the webMethods Integration Server documentation to make sure that you have set up your JDBC Pool configurations correctly. If you cannot determine the cause of the problem, contact Software AG Global Support.
<b>ISS.012.0026E</b>	<b>The certificate in the SAML assertion signature does not match the certificate on file for the issuer; Rejecting SAML assertion.</b>
<b>Explanation</b>	The certificate in the SAML assertion signature does not match the certificate on file for the issuer.
<b>Action</b>	Check the issuer configuration on Security -> SAML screen and make sure that the identified truststore contains the correct certificate for the issuer.

<b>ISS.0125.0015W</b>	<b>The trigger input control parameters, <code>watt.server.control.triggerInputControl.delaysIncrementInterval</code> and <code>watt.server.control.triggerInputControl.delays</code>, were set to their default values because an exception occurred when parsing the supplied values.</b>
<b>Explanation</b>	Integration Server could not set the trigger input control configuration parameter <code>watt.server.control.triggerInputControl.delaysIncrementInterval</code> and/or <code>watt.server.control.triggerInputControl.delays</code> to the new value because an exception occurred when parsing a new value for one of the parameters. Integration Server reset both configuration parameters to the default values.
<b>Action</b>	Use a valid value for the <code>watt.server.control.triggerInputControl.delaysIncrementInterval</code> or <code>watt.server.control.triggerInputControl.delays</code> parameter.
<b>ISS.0128.0001E</b>	<b>Unable to get JDBC connection. Exception:{0}</b>
<b>Explanation</b>	Integration Server was unable to connect to the database defined by the DocumentHistory functional alias. This alias defines the database that the Integration Server uses to detect duplicate documents.
<b>Action</b>	From the Settings>JDBC Pools> page of the Integration Server Administrator, make sure that a Functional Alias called DocumentHistory exists and is associated with a valid Pool Alias. Click the Test button. If the alias exists, but there are errors when you hit the Test button, then there is a problem with the connection. Review the Journal log for messages about the operation being performed. If the problem persists, contact your Database Administrator.
<b>ISS.0128.0002E</b>	<b>Exception while {1}: {0}</b>
<b>Explanation</b>	An exception occurred when Integration Server tried to perform a task using the In Doubt Resolver component.
<b>Action</b>	From the Settings>JDBC Pools> page of the Integration Server Administrator, make sure that a Functional Alias called DocumentHistory exists and is associated with a valid Pool Alias. Click the Test button. If the alias exists, but there are errors when you hit the Test button, then there is a problem with the connection. If the problem persists, contact your Database Administrator.
<b>ISS.0128.0003E</b>	<b>SQLException:{0} while {1}</b>
<b>Explanation</b>	An exception occurred when Integration Server tried to perform a SQL operation using the JDBC connection pool for the functional alias DocumentHistory.
<b>Action</b>	From the Settings>JDBC Pools> page of the Integration Server Administrator, make sure that a Functional Alias called DocumentHistory exists and is associated with a valid Pool Alias. Click the Test button. If the alias exists, but there are errors when you hit the Test button, then there is a problem with the connection. Review the Journal log for messages about the operation being performed. If the problem persists, contact your Database Administrator.

<b>ISS.0128.0004E</b>	<b>Exception while loading the Decision Tree: {0}</b>
<b>Explanation</b>	An exception occurred when Integration Server tried to create the decision tree for resolving duplicate documents. The decision is based on multiple criteria, but Integration Server was not able to load these criteria into memory.
<b>Action</b>	Contact webMethods Customer Care. Be prepared to provide logs and the version number and patch level for Integration Server and your operating system.
<b>ISS.0128.0005E</b>	<b>Exception:{0} while resolving Document of type: {1} and Id: {2} for trigger: {3}. Document is being deemed as In Doubt.</b>
<b>Explanation</b>	An exception occurred when Integration Server tried to resolve a document it received. The exception might be due to a problem with the database connection for the alias DocumentHistory or with the Resolver Service associated with the trigger.
<b>Action</b>	Examine the Server log for error messages that indicate the cause of the problem. If the error was a database/SQL exception, check to see if the functional alias DocumentHistory is working properly. If a problem occurred with the Resolver Service, verify that the service is properly coded.
<b>ISS.0128.0006E</b>	<b>Trigger: {0} encountered exception while executing resolver service: {1}. Exception: {2}</b>
<b>Explanation</b>	Integration Server received a document, but the document resolver service associated with the trigger encountered an exception.
<b>Action</b>	Check the Error log to see if the Document Resolver Service associated with the trigger has logged any error messages. If no messages have been logged, change the auditing properties for the service to enable the Log on Error property. In addition, because this is a user-written service, check it to make sure it has been coded properly.
<b>ISS.0128.0007E</b>	<b>In Doubt document of type:{0} with Id:{1} received for trigger:{2}. Document is being Audit Logged.</b>
<b>Explanation</b>	Integration Server received a document, but the document resolver service associated with the trigger could not resolve the document and therefore considers it to be "In Doubt".
<b>Action</b>	Check the document's id to see if it is a duplicate. If there is a document resolver service associated with the trigger, determine why the service was not able to resolve the document. Integration Server records occurrences of In Doubt Documents in the Audit log. You can view In Doubt documents through WmMonitor.

<b>ISS.0128.0008E</b>	<b>Unable to Audit Log document of type:{0} with id:{1} as it can't be decoded. Exception:{2}.</b>
<b>Explanation</b>	An error occurred when Integration Server tried to resolve a document. As part of the resolution process, a document first goes to the In Doubt Resolver component. If that component successfully resolves the document, Integration Server decodes the document and sends it to the trigger. However, if the In Doubt Resolver cannot resolve the document, the Integration Server decodes the document and sends it to the In Doubt Resolver service associated with the trigger. This error is issued if there is an error when decoding the document before sending it to the In Doubt Resolver service associated with the trigger.
<b>Action</b>	Make sure the document type on Integration Server matches the associated Broker document type on the Broker. Re-sync the document types by pushing the IS document type to the Broker ("Push to Broker"). If all the document type fields and data types match and the problem still persists, contact webMethods Customer Care.
<b>ISS.0128.0009E</b>	<b>Unable to get JDBC Connection to the database.</b>
<b>Explanation</b>	As part of storing history for the document being processed, the Integration Server's In Doubt Resolver component add/deletes rows to a database. While performing one of these actions, the connection to the database was lost.
<b>Action</b>	From the Settings>JDBC Pools> page of the Integration Server Administrator, make sure that a functional alias called DocumentHistory exists and is associated with a valid Pool Alias. Click the Test button. If the alias exists, but there are errors when you hit the Test button, then there is a problem with the connection. If the problem persists, contact your Database Administrator. Review the Journal log for messages about the operation being performed. If the problem persists, contact your Database Administrator.
<b>ISS.0128.0010</b>	<b>Detected expired UUID:{0} for trigger:{1}. Deleting all expired UUIDs.</b>
<b>ISS.0128.0011</b>	<b>Unable to resolve processing state for UUID:{0} for trigger:{1}. Exception:{2}</b>
<b>ISS.0128.0012</b>	<b>Unable to mark UUID:{0} for trigger:{1} as complete in the database. A non-expired UUID already exists.</b>
<b>ISS.0128.0014E</b>	<b>Unable to insert UUID:{0}. Exception:{1}</b>
<b>Explanation</b>	As part of storing history for the document or message being processed, Integration Server's In Doubt Resolver component stores the UUID (universally unique ID) of the document (message) in a database. An exception occurred during this process.
<b>Action</b>	From the Settings>JDBC Pools> page of the Integration Server Administrator, make sure that a Functional Alias called DocumentHistory exists and is associated with a valid Pool Alias. Click the Test button. If the alias exists, but there are errors when

you hit the Test button, then there is a problem with the connection. If the problem persists, contact your Database Administrator.

**ISS.0128.0015E Document history initialization failed. Please verify database connection is available.Exception {0}.**

**Explanation** No valid JDBC connection Pool is available for the In Doubt Resolver Alias "DocumentHistory". Detection of duplicate documents depends on the availability of a database where document history is defined.

**Action** From the Settings>JDBC Pools> page of the Integration Server Administrator, make sure that a Functional Alias called DocumentHistory exists and is associated with a valid Pool Alias. Click the Test button. If the alias exists, but there are errors when you hit the Test button, then there is a problem with the connection. If the problem persists, contact your Database Administrator.

**ISS.0128.9002E Unable to get Connection**

**Explanation** No valid JDBC connection Pool is available for the In Doubt Resolver Alias "DocumentHistory".

**Action** From the Settings>JDBC Pools> page of the Integration Server Administrator, make sure that a Functional Alias called DocumentHistory exists and is associated with a valid Pool Alias. Click the Test button. If the alias exists, but there are errors when you hit the test button, then there is a problem with the connection. Review the Journal log for messages about the operation being performed. If the problem persists, contact your Database Administrator.

**ISS.0128.9006E Invalid argument supplied for:{0}**

**Explanation** Integration Server stores document history information in a database so that it can detect when duplicate documents are received. This error occurs when a process tries to insert an entry that specifies an invalid argument into the database.

**Action** Check to see if the name of the trigger and the UUID of the document satisfy the constraints specified on the columns of the Table WM\_IDR\_MSG\_HST in your database. This error can occur if the Trigger Name or UUID exceeds the column length of the database column.

**ISS.0128.9013E Exception while executing in doubt resolver service:{0}**

**Explanation** Integration Server received a document, but an exception occurred during execution of the document resolver service associated with the trigger.

**Action** Check the Integration Server error log to see if the document resolver service has logged any error messages. If no errors were logged, configure the document resolver service's auditing properties to Log on Error. In addition, verify that the document resolver service has been coded properly.

---

<b>ISS.0128.9015E</b>	<b>The DocumentHistory functional alias is not configured properly on the JDBC Pools page. Assign a valid database pool and restart the Integration Server.</b>
<b>Explanation</b>	Integration Server stores document history information in a Document History database so that it can detect when duplicate documents are received. Integration Server throws this exception whenever it does not find a JDBC Pool for the Document History functional alias.
<b>Action</b>	Configure a JDBC Pool for Document History functional alias.
<b>ISS.0131.0001E</b>	<b>No threads available. All diagnostic listener threads are in use.</b>
<b>Explanation</b>	Integration Server has detected that all threads allocated to the diagnostic thread pool are in use.
<b>Action</b>	Wait for one or more of these threads to finish. If this problem persists, contact webMethods Customer Care.
<b>ISS.0131.0002</b>	<b>DOMString size error. Details:{0}</b>
<b>ISS.0131.0003</b>	<b>Hierarchy request error. Details:{0}</b>
<b>ISS.0131.0004</b>	<b>Wrong document error. Details:{0}</b>
<b>ISS.0131.0005</b>	<b>Invalid character error. Details:{0}</b>
<b>ISS.0131.0006</b>	<b>No data allowed error. Details:{0}</b>
<b>ISS.0131.0007</b>	<b>No modification allowed error. Details:{0}</b>
<b>ISS.0131.0008</b>	<b>Not found error. Details:{0}</b>
<b>ISS.0131.0009</b>	<b>Not supported error. Details:{0}</b>
<b>ISS.0131.0010</b>	<b>Inuse attribute error. Details:{0}</b>

ISS.0131.0011	Invalid state error. Details:{0}
ISS.0131.0013	Invalid modification error. Details:{0}
ISS.0131.0015	Invalid access error. Details:{0}
ISS.0131.0017	Type mismatch error. Details:{0}
ISS.0131.9998	Cannot set attribute name or value to null
ISS.0131.9999	Cannot get null attribute
ISS.0134.0002	JMS Runtime Configuration Internal Error. Unable to set thread pool max: {0}
ISS.0134.0003	An error occurred while loading JMS configuration file: {0}
ISS.0134.0004	Unable to start JMS connection alias "{0}": {1}
ISS.0134.0005E	Unable to start JMS connection alias "{0}". The alias is now disabled: {1}
Explanation	The specified JMS connection alias could not be started because it is disabled. Only enabled JMS connection aliases can be started.
Action	Enable the JMS connection alias.
ISS.0134.0006	JNDI Property "{0}" not found. Setting JMS connection alias "{1}" to disabled.
ISS.0134.0009	JMS configuration file not found: {0}
ISS.0134.0010	JMS subsystem is not configured. The default JMS connection alias is being created.

---

ISS.0134.0011	Unable to load JMS configuration file "{0}": {1}
ISS.0134.0012	Unable to load JMS configuration file "{0}": File not found.
ISS.0134.0014	"jms.cnf" file contains no configuration data.
ISS.0134.0015	Unable to load configuration for JMS connection alias "{0}": {1}
ISS.0134.0016	JMS Connection Error on connection "{0}": {1}
ISS.0134.0017	Unable to destroy CSQ for connection "{0}": {1}
ISS.0134.0018	Unable to ping JNDI provider "{0}": {1}
ISS.0134.0019	Unable to start CSQ Factory. The CSQ feature will not be functional for any JMS connection aliases: {0}
ISS.0134.0020	Exception occurred while pinging JMS provider "{0}": {1}
ISS.0134.0021	Error delisting resource from transaction: {0}
ISS.0134.0022	Error closing JMS Session: {0}
ISS.0134.0023	Error shutting down CSQ Factory: {0}
ISS.0134.0024	CSQ Dispatcher "{0}" unable to retrieve producer. CSQ Dispatcher is now stopping: {1}
ISS.0134.0025	CSQ Dispatcher "{0}" is stopping because of exception: {1}

- ISS.0134.0026 CSQ Dispatcher "{0}" was unable to send message to "{1}" after {2} retries: {3}
  
- ISS.0134.0027 CSQ Dispatcher "{0}" was unable to send message to "{1}": {2}
  
- ISS.0134.0028 Out of memory error while acking message from CSQ "{0}". Attempting two retries
  
- ISS.0134.0030 CSQ Dispatcher "{0}" was unable to acknowledge message: {1}
  
- ISS.0134.0031 Out of memory error while sending message from CSQ. Attempting two retries
  
- ISS.0134.0033 No metadata found for JMS connection alias {0}
  
- ISS.0134.0034 No metadata found for JMS connection alias {0}: {1}
  
- ISS.0134.0035 The JMS provider and version associated with JMS connection alias {0} is not officially supported.
  
- ISS.0134.0039 IllegalStateException occured in Consumer {0}: {1}
  
- ISS.0134.0040 OutOfMemoryError occured in Consumer {0}
  
- ISS.0134.0041 JMS Trigger {0} failed preprocessing: {1}
  
- ISS.0134.0042 JMS Trigger {0} failed: {1}
  
- ISS.0134.0043 JMS Trigger {0} failed post-processing: {1}
  
- ISS.0134.0044 JMS Trigger {0} was unable to set JMS Reply To Context: {1}

---

<b>ISS.0134.0045I</b>	<b>JMS Trigger {0} has acknowledged the message(s).</b>
<b>Explanation</b>	The specified JMS trigger has acknowledged the message(s) to the JMS provider.
<b>Action</b>	No action required.
<b>ISS.0134.0046</b>	<b>JMS Trigger {0} has recovered the message(s).</b>
<b>ISS.0134.0051</b>	<b>Created JMS Trigger Thread Pool with a maximum of {0} threads.</b>
<b>ISS.0134.0053</b>	<b>Unable to start JMS Trigger {0}: {1}</b>
<b>ISS.0134.0056</b>	<b>Error closing Connection Handle: {0}.</b>
<b>ISS.0134.0057</b>	<b>JMS Trigger {0} did not shutdown in the allotted time ({1} seconds). It is now being forced to shutdown.</b>
<b>ISS.0134.0058</b>	<b>JMS Trigger {0} is shutting down because of exception: {1}</b>
<b>ISS.0134.0059</b>	<b>Error destroying Consumer Context: {0}.</b>
<b>ISS.0134.0060</b>	<b>Unable to refill Shared Session Pool after release: {0}</b>
<b>ISS.0134.0061</b>	<b>Consumer Context Pool shutdown timeout: Freeing up active entries.</b>
<b>ISS.0134.0062</b>	<b>Internal Error: returning unused object to Consumer Context Pool!</b>
<b>ISS.0134.0063</b>	<b>JMS transaction failed with \$errorType {0}.</b>
<b>ISS.0134.0064</b>	<b>Unable to register JMS Trigger {0}: {1}</b>

- ISS.0134.0065      Unable to unregister JMS Trigger {0}: {1}
  
- ISS.0134.0066      JMSTrigger {0} has started.
  
- ISS.0134.0072      JMS Trigger Resource Monitor scheduled new system task.
  
- ISS.0134.0073      JMS Trigger Resource Monitor has resumed the last trigger. Its system task will now be canceled.
  
- ISS.0134.0074      JMS Trigger Resource Monitor is now monitoring the resource availability of trigger {0}.
  
- ISS.0134.0075      JMS Trigger Resource Monitor invoked service {0}. Status of resource is "{1}".
  
- ISS.0134.0076      JMS Trigger Resource Monitor received an exception while invoking service {0}: {1}
  
- ISS.0134.0077      JMSTrigger Resource Monitor has resumed trigger {0}.
  
- ISS.0134.0078      JMS Trigger Resource Monitor received an exception while attempting to resume trigger {0}: {1}
  
- ISS.0134.0081      No suitable data type was found in the message body so an empty Message is being created.
  
- ISS.0134.0082      Not starting JMS connection alias {0} because package {1} is not loaded/enabled yet.
  
- ISS.0134.0083      Trigger {0} cannot receive messages in a batch while using a transacted connection. The "max batch messages" size will be set to 1.

---

ISS.0134.0084	Unable to acknowledge InDoubtResolver: {0}
ISS.0134.0085	Unable to remove InDoubtResolver entry: {0}
ISS.0134.0086	Trigger Preprocessing Failure occurred for trigger {0}: {1}. The DocumentHistory JDBC alias may not be configured correctly. The trigger will be automatically suspended. You must restart it manually.
ISS.0134.0087	Trigger Preprocessing Failure occurred for trigger {0}: {1}. The trigger will be automatically suspended and IS will monitor the DocumentHistory JDBC resource.
ISS.0134.0088	Rejecting incoming message for trigger: {0}, documentID: {1}. Delivery Count has exceeded {2} attempts.
ISS.0134.0089	JMS Trigger {0} failed decoding: {1}
ISS.0134.0090	Unable to retrieve password from Password Manager with key {0}: {1}
ISS.0134.0091	Unable to set password in Password Manager with key {0}: {1}
ISS.0134.0094	Unable to start JMS connection alias "{0}". The server will attempt to reconnect every {1} seconds: {2}
ISS.0134.0096	Could not create Destination to Ping Connection Alias :{0}.
ISS.0134.0098	JMS connection alias "{0}" is unable to check the JNDI namespace for updates to the ConnectionFactory "{1}": {2}
ISS.0134.0099	JMS connection alias "{0}" is updating because of changes made to ConnectionFactory "{1}" in the JNDI namespace.

<b>ISS.0134.0100</b>	<b>Unable to restart JMS connection alias "{0}" after updating ConnectionFactory "{1}": {2}</b>
<b>ISS.0134.0102</b>	<b>Unable to register event listener. Update functionality not available for this JNDI provider: {0}</b>
<b>ISS.0134.0103</b>	<b>The JNDI event listener for JMS connection alias "{0}" has been disconnected. The system will try to reconnect.</b>
<b>ISS.0134.0104</b>	<b>JMS connection alias "{0}" is dynamically setting polling interval to {1} milliseconds.</b>
<b>ISS.0134.0105</b>	<b>JMS connection alias "{0}" is unable to retrieve polling interval, so the default value of {1} minutes will be used instead: {2}</b>
<b>ISS.0134.0106</b>	<b>Starting JMS connection alias with Guaranteed Multisend policy. Broker list = {0}; Multisend Broker count = {1}.</b>
<b>ISS.0134.0114D</b>	<b>Refreshed session for consumer: {0}</b>
<b>Explanation</b>	Integration Server refreshed the session for the specified message consumer.
<b>Action</b>	None.
<b>ISS.0134.0115D</b>	<b>Initialized default Session pool for alias "{0}"; max size "{1}"</b>
<b>Explanation</b>	Integration Server created a default Session Pool for the specified JMS connection alias.
<b>Action</b>	No action required.
<b>ISS.0134.0116D</b>	<b>Initialized MessageProducer pool for alias "{0}"; destination "{1}"; max size "{2}"</b>
<b>Explanation</b>	For the specified JMS connection alias, Integration Server created a MessageProducer Pool for the specified destination.
<b>Action</b>	No action required.

<b>ISS.0134.0117E</b>	<b>Unable to initialize MessageProducer pool for alias "{0}"; destination "{1}": {2}</b>
<b>Explanation</b>	An error occurred while initializing the MessageProducer Pool for the specified JMS connection alias and destination. The error most likely occurred because the destination does not exist or cannot be accessed.
<b>Action</b>	Verify that the specified destination exists and that you have sufficient privileges to access the destination. If the JMS connection alias uses a JNDI provider for administered objects, verify that the JNDI provider is available.
<b>ISS.0134.0999</b>	<b>JMS subsystem unexpected error: {0}</b>
<b>ISS.0134.9045E</b>	<b>Unable to create trigger "{0}". Invalid or non-ascii characters in NSName.</b>
<b>Explanation</b>	The WS endpoint trigger could not be created because the Web service endpoint alias name includes characters that are not valid for an element name.
<b>Action</b>	Change the name of the alias so that it does not include any characters that Integration Server considers to be reserved or invalid for element names. Refer to the Designer or webMethods Developer documentation for a list of reserved or invalid characters.
<b>ISS.0134.9082E</b>	<b>The client side queue cannot be used with a send and wait request if the reply destination is a temporary queue.</b>
<b>Explanation</b>	The useCSQ parameter is set to true and the replyToDestinationName is blank or specifies a temporary queue.
<b>Action</b>	If you want Integration Server to route messages to the client side queue when the JMS provider is not available leave useCSQ set to true and specify a queue that is not temporary. That is, specify values for the destinationNameReplyTo and destinationTypeReplyTo input parameters.
<b>ISS.0134.9083E</b>	<b>The pub.jms:sendBatch service is not supported with this provider.</b>
<b>Explanation</b>	The connectionAliasName parameter specifies a JMS connection alias that uses a JMS provider that is not supported with the pub.jms:sendBatch service.
<b>Action</b>	Change the value of the connectionAliasName parameter to specify a JMS connection alias that uses a supported JMS provider.
<b>ISS.0134.9084E</b>	<b>The pub.jms:sendBatch service is not supported with connection factories that use the multisend guaranteed or multisend best effort Broker cluster policies.</b>
<b>Explanation</b>	The connectionAliasName parameter specifies a JMS connection alias that uses a connection factory to which the multisend guaranteed or multisend best effort Broker cluster policy is applied. The pub.jms:sendBatch service cannot be used with connection factories that have these policies.
<b>Action</b>	Change the value of the connectionAliasName parameter to specify a JMS connection alias that does not use a connection factory to which the multisend guaranteed or multisend best effort Broker cluster policy is applied.

<b>ISS.0134.9350E</b>	<b>UM admin operation failed [{0}]: {1}</b>
<b>Explanation</b>	The specified admin operation could not be completed on Universal Messaging due to the listed error. Integration Server will perform admin operations on Universal Messaging when Designer is being used to manage destinations and durable subscribers on Universal Messaging.
<b>Action</b>	Use the provided error message to determine why the admin operation could not be completed.
<b>ISS.0135.0001E</b>	<b>No properties found for JNDI alias {0}</b>
<b>Explanation</b>	Integration Server could not find the JNDI properties file for the specified JNDI provider alias.
<b>Action</b>	Ensure that the properties file associated with the JNDI provider alias exists and is not empty. The JNDI properties file is stored in the following directory: IntegrationServer_directory\instances\instanceName\config\jndi
<b>ISS.0135.0002E</b>	<b>JNDI configuration file already exists: {0}</b>
<b>Explanation</b>	Integration Server cannot create the JNDI provider alias because a JNDI properties file already exists for an alias with that name.
<b>Action</b>	Ensure that the JNDI provider alias is not a duplicate of one that already exists. Specify a different name for the JNDI provider alias.
<b>ISS.0135.0003E</b>	<b>JNDI configuration file does not exist: {0}</b>
<b>Explanation</b>	When deleting the JNDI provider alias, Integration Server encountered an error when attempting to delete the associated properties file as the associated JNDI properties file does not exist.
<b>Action</b>	Ensure that the properties file associated with the JNDI provider alias exists in the following directory: IntegrationServer_directory\instances\instanceName\config\jndi
<b>ISS.0135.0004E</b>	<b>Unable to delete JNDI configuration file: {0}</b>
<b>Explanation</b>	When deleting the JNDI provider alias, Integration Server could not delete the associated JNDI properties file.
<b>Action</b>	Ensure that another user is not currently accessing the properties file for the JNDI provider alias that you are attempting to delete. The JNDI properties files are located in the following directory IntegrationServer_directory\instances\instanceName\config\jndi

---

<b>ISS.0135.0005E</b>	<b>Unable to load JNDI Properties. File not found: {0}</b>
<b>Explanation</b>	Integration Server cannot load the properties file associated with the JNDI provider alias.
<b>Action</b>	Ensure that a valid properties file exists for the JNDI provider alias in the following directory: IntegrationServer_directory\instances\instanceName\config\jndi
<b>ISS.0135.0006E</b>	<b>Unable to load JNDI Properties. Invalid properties file: {0}</b>
<b>Explanation</b>	Integration Server could not load the properties file for the JNDI provider alias because the file is invalid.
<b>Action</b>	Ensure that the properties file associated with the JNDI provider alias exists and is not empty. The JNDI properties file is stored in the following directory: IntegrationServer_directory\instances\instanceName\config\jndi
<b>ISS.0137.0002W</b>	<b>Scheduler: Unable to get pool for ISInternal</b>
<b>Explanation</b>	Integration Server was unable to get the ISInternal JDBC connection pool.
<b>Action</b>	Configure the ISInternal functional alias (specified on the Settings > JDBC Pools screen in Integration Server Administrator) and assign a valid JDBC connection pool to it.
<b>ISS.0137.0006E</b>	<b>Scheduler: Error initializing scheduler: {0}</b>
<b>Explanation</b>	Integration Server encountered an error while initializing the database in which information about scheduled jobs is stored.
<b>Action</b>	Read through the contents of the error logs and take corrective steps. If you are unable to resolve the issue, contact Software AG Global Support.
<b>ISS.0137.0007E</b>	<b>Scheduler: Unable to get a connection to the database.</b>
<b>Explanation</b>	Integration Server was unable to get a connection from the JDBC connection pool.
<b>Action</b>	Use Integration Server Administrator to increase the maximum number of connections available in the JDBC connection pool that is assigned to the ISInternal functional alias.
<b>ISS.0137.0010E</b>	<b>Scheduler: Resources unavailable: {0}</b>
<b>Explanation</b>	Scheduler thread throttle, which is the percentage of server threads the scheduler function is permitted to use, is reached. Integration Server cannot execute a scheduled task because there are no threads available.
<b>Action</b>	Use Server Administrator to increase the maximum number of connections available in the JDBC pool that is assigned to the ISInternal functional alias.

<b>ISS.0137.0011E</b>	<b>Scheduler: Exception: {0}</b>
<b>Explanation</b>	Integration Server encountered an error while retrieving a scheduled task from the database and executing it.
<b>Action</b>	Read through the contents of the error logs and take corrective steps. If you are unable to resolve the issue, contact Software AG Global Support.
<b>ISS.0137.0012E</b>	<b>Scheduler: Error inserting task into database: {0}</b>
<b>Explanation</b>	Integration Server encountered an error while adding a new scheduled task to the database.
<b>Action</b>	Read through the contents of the error logs and take corrective steps. If you are unable to resolve the issue, contact Software AG Global Support.
<b>ISS.0137.0013E</b>	<b>Scheduler: Error updating task in database: {0}</b>
<b>Explanation</b>	Integration Server encountered an error while updating the information of a scheduled task in the database.
<b>Action</b>	Read through the contents of the error logs and take corrective steps. If you are unable to resolve the issue, contact Software AG Global Support.
<b>ISS.0137.0014E</b>	<b>Scheduler: Error updating status in database: {0}</b>
<b>Explanation</b>	Integration Server encountered an error while updating the status of a scheduled task in the database.
<b>Action</b>	Read through the contents of the error logs and take corrective steps. If you are unable to resolve the issue, contact Software AG Global Support.
<b>ISS.0137.0016E</b>	<b>Scheduler: Exception getting task IDs from database: {0}</b>
<b>Explanation</b>	Integration Server encountered an error while retrieving the IDs of scheduled tasks associated with a user.
<b>Action</b>	Read through the contents of the error logs and take corrective steps. If you are unable to resolve the issue, contact Software AG Global Support.
<b>ISS.0137.0017E</b>	<b>Scheduler: Exception getting tasks from database: {0}</b>
<b>Explanation</b>	Integration Server encountered an unexpected SQLException while retrieving the scheduled tasks from the database.
<b>Action</b>	Ensure that the database is available and configured to execute scheduled tasks.

---

<b>ISS.0137.0018E</b>	<b>Scheduler: Exception while invoking "{0}": {1}</b>
<b>Explanation</b>	Integration Server encountered a runtime exception while invoking a scheduled task.
<b>Action</b>	Read through the contents of the error logs and take corrective steps. If you are unable to resolve the issue, contact Software AG Global Support.
<b>ISS.0137.0021E</b>	<b>Invalid database vendor type: {0}</b>
<b>Explanation</b>	The database driver for the ISInternal functional alias is not valid.
<b>Action</b>	Go to the Settings > JDBC Pools page in Integration Server Administrator and set ISInternal's pool alias to use one of the listed database drivers.
<b>ISS.0137.0022E</b>	<b>No ISInternal JDBC Pool</b>
<b>Explanation</b>	The ISInternal functional alias is not configured.
<b>Action</b>	Configure the ISInternal functional alias (specified on the Settings > JDBC Pools screen in Integration Server Administrator) and assign a valid JDBC connection pool to it.
<b>ISS.0137.0023E</b>	<b>Could not get connection for pool {0}</b>
<b>Explanation</b>	Integration Server attempted to acquire a JDBC connection, but no connections are available in the pool assigned to the ISInternal functional alias.
<b>Action</b>	Use Server Administrator to increase the maximum number of connections available in the JDBC pool that is assigned to the ISInternal functional alias.
<b>ISS.0137.0024E</b>	<b>Namespace Dependency Manager is disabled</b>
<b>Explanation</b>	Unable to determine if the service executed by a scheduled task refers to other services that are unavailable.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0137.0025E</b>	<b>Found unresolved dependent services: {0}</b>
<b>Explanation</b>	Integration Server was unable to create or run the scheduled task because the service scheduled to run contains a reference to a service that cannot be located.
<b>Action</b>	Update the scheduled task to specify a correct reference to the dependent service. Note: Integration Server performs reference validation for services only when the <code>watt.server.scheduler.ignoreReferenceValidation</code> configuration parameter is set to true. The default is false.

<b>ISS.0137.0026E</b>	<b>User {0} is disabled</b>
<b>Explanation</b>	The user a scheduled task is set to run as is disabled. The task will not run.
<b>Action</b>	Enable the user or modify the task to run as a different user.
<b>ISS.0137.0027E</b>	<b>User {0} is removed</b>
<b>Explanation</b>	The user associated with a scheduled task has been removed.
<b>Action</b>	Add the user or change the scheduled task to execute with an enabled user.
<b>ISS.0137.0028W</b>	<b>Could not complete last run at node {0}</b>
<b>ISS.0137.0029E</b>	<b>Rolling back due to scheduler thread throttle reached: {0}</b>
<b>Explanation</b>	A scheduled task attempted to use more threads than the maximum number allowed by the Scheduler thread throttle limit. Any scheduled tasks that attempt to execute under these circumstances will fail.
<b>Action</b>	Use Integration Server Administrator to increase the Scheduler thread throttle under Settings > Resources > Edit Resource Settings > Server Thread Pool.
<b>ISS.0137.0030E</b>	<b>...&lt;truncated&gt;</b>
<b>Explanation</b>	Integration Server encountered an error during the execution of a scheduled task.
<b>Action</b>	Read through the contents of the error logs and take corrective steps. If you are unable to resolve the issue, contact Software AG Global Support.
<b>ISS.0137.0031E</b>	<b>Invalid Target {0}</b>
<b>Explanation</b>	A scheduled task is set to run on a host that is not currently a member of the Integration Server cluster.
<b>Action</b>	Modify the scheduled task to run on a member of the cluster.
<b>ISS.0137.0032E</b>	<b>Invalid task ID {0}</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Contact Software AG Global Support.

---

<b>ISS.0137.0033E</b>	<b>Errors encountered while initializing Scheduler. Scheduled tasks will not run. Check the logs for more information.</b>
<b>Explanation</b>	Integration Server encountered an error either while initializing the scheduler or while connecting to the database in which information about scheduled jobs is stored. As a result, scheduled tasks will not run.
<b>Action</b>	Read through the contents of the error logs and take corrective steps. After correcting the issue that caused the error, restart the Integration Server.
<b>ISS.0137.0034E</b>	<b>Unknown Service: {0}. Scheduled task will not run.</b>
<b>Explanation</b>	The service configured to execute for a scheduler does not exist in the Integration Server.
<b>Action</b>	Ensure that the service is available in the Integration Server.
<b>ISS.0138.0350E</b>	<b>Test of CentraSite connection failed.</b>
<b>Explanation</b>	Integration Server encountered an exception while connecting to CentraSite.
<b>Action</b>	Ensure the parameters that Integration Server uses to connect to CentraSite are correct. Specifically, check the URL pointing to CentraSite (including the port), the user name, and password.
<b>ISS.0139.0056W</b>	<b>Error: Default keystore alias "DEFAULT_IS_KEYSTORE" cannot be created. Details: {0}</b>
<b>Explanation</b>	Error while creating DEFAULT_IS_KEYSTORE alias at the first startup of Integration Server.
<b>Action</b>	<p>&lt;p&gt;The following lists the actions you can take:&lt;/p&gt;&lt;p&gt;1. Ensure that the keystore file 'keystore.jks' is present in the Integration Server_directory\common\conf directory.&lt;/p&gt;&lt;p&gt;2. Ensure that the keystore has not expired.&lt;/p&gt;&lt;p&gt;3. Contact Software AG Global Support.&lt;/p&gt;</p>
<b>ISS.0139.0057W</b>	<b>Error: Default truststore alias "DEFAULT_IS_TRUSTSTORE" cannot be created. Details: {0}</b>
<b>Explanation</b>	Error while creating DEFAULT_IS_TRUSTSTORE alias at the first start up of Integration Server.
<b>Action</b>	<p>&lt;p&gt;The following lists the actions you can take:&lt;/p&gt;&lt;p&gt;1. Ensure that the truststore file platform_truststore.jks is present in the Integration Server_directory\common\conf\ directory.&lt;/p&gt;&lt;p&gt;2. Ensure that the truststore has not expired.&lt;/p&gt;&lt;p&gt;3. Contact Software AG Global Support.&lt;/p&gt;</p>

<b>ISS.0139.9002E</b>	<b>Error: invalid keystore or truststore configuration file "{0}".</b>
<b>Explanation</b>	Configuration file related to keystore is corrupted.
<b>Action</b>	Create a keystore alias.
<b>ISS.0139.9003I</b>	<b>Keystore alias "{0}" saved successfully.</b>
<b>ISS.0139.9004W</b>	<b>Keystore alias "{0}" saved successfully. Warning: before using the keystore, you must create a password for at least one of its key aliases. Please edit the keystore alias configuration and add one or more valid key alias passwords.</b>
<b>Explanation</b>	The key aliases are not configured. Before using the keystore, you must create a password for at least one of its key aliases.
<b>Action</b>	Edit the keystore alias configuration and add at least one valid key alias passwords.
<b>ISS.0139.9005E</b>	<b>Keystore alias "{0}" saved successfully. An error occurred while loading the keystore in memory, please edit the keystore alias configuration. Details: {1}</b>
<b>Explanation</b>	An error occurred while loading the keystore in memory.
<b>Action</b>	Edit the keystore alias configuration. Make sure that the keystore location is correct and keystore exists on the file system. Then, make sure that the configuration file related to the keystore is valid.
<b>ISS.0139.9006W</b>	<b>Keystore alias "{0}" saved successfully. Warning: the following key aliases "{1}" cannot be used because they do not have passwords. Please edit the keystore alias configuration and add password(s) for the appropriate key alias(es).</b>
<b>Explanation</b>	Some key aliases are not configured.
<b>Action</b>	Edit the keystore alias configuration and add passwords for the corresponding key aliases.
<b>ISS.0139.9007W</b>	<b>Keystore alias "{0}" saved successfully. Warning: the following key aliases "{1}" have been removed from the keystore alias configuration.</b>
<b>Explanation</b>	Few key aliases were removed from the keystore alias configuration.
<b>Action</b>	Refresh the keystore alias.
<b>ISS.0139.9012E</b>	<b>Error: cannot save the keystore alias "{0}".</b>
<b>Explanation</b>	Either the keystore location is invalid, or the key aliases passwords do not consist of ASCII characters.
<b>Action</b>	Make sure that the keystore location is valid and the key aliases passwords consist of valid ASCII characters.

---

<b>ISS.0139.9013E</b>	<b>Error: keystore "{0}" not found.</b>
<b>Explanation</b>	The configuration file related to keystore alias is unavailable.
<b>Action</b>	Make sure that the configuration file related to the keystore alias exists in the directory ../config/security/keystore.
<b>ISS.0139.9014E</b>	<b>Error: keystore "{0}" not found. Details: {1}.</b>
<b>Explanation</b>	Invalid keystore location.
<b>Action</b>	Make sure that the location of the keystore is correct; the key aliases passwords are valid; and the configuration file exists, and it is not corrupted.
<b>ISS.0139.9016W</b>	<b>Keystore "{0}" was reloaded successfully. Warning: you must provide the password for at least one key alias in the keystore before using it. Please edit the keystore alias configuration and add at least one valid key alias password.</b>
<b>Explanation</b>	Either the keystore does not contain any key aliases, or a key alias password is not provided. You must provide the password for at least one key alias in the keystore before using it.
<b>Action</b>	Check whether the keystore has any key aliases. If not, then add key alias in the keystore. If there are key aliases in the keystore, then edit the keystore alias configuration and add at least one valid key alias password.
<b>ISS.0139.9017W</b>	<b>Keystore "{0}" reloaded successfully. Warning: the following key aliases "{1}" cannot be used because they do not have a password. Please edit the keystore alias configuration and add one or more valid key alias passwords.</b>
<b>Explanation</b>	Key alias must be configured in advance.
<b>Action</b>	Edit the keystore alias configuration and add one or more valid key alias passwords.
<b>ISS.0139.9018W</b>	<b>Keystore "{0}" reloaded successfully. Warning: the following key aliases "{1}" have been removed from the alias configuration.</b>
<b>Explanation</b>	Key alias must be configured in advance.
<b>Action</b>	Edit the keystore alias configuration and add one or more valid key alias passwords.
<b>ISS.0139.9019E</b>	<b>Error: cannot reload keystore "{0}". Details: {1}.</b>
<b>Explanation</b>	Keystore alias does not map to a valid keystore.
<b>Action</b>	Make sure that the keystore location is correct and keystore exists on the file system. Make sure that the configuration file related to the keystore is valid.

<b>ISS.0139.9020E</b>	<b>Error: cannot reload keystore "{0}".</b>
<b>Explanation</b>	Configuration file does not exist.
<b>Action</b>	Make sure that the configuration file, which corresponds to the truststore alias, exists in the directory ../config/security/keystore.
<b>ISS.0139.9022E</b>	<b>Error: unable to delete the keystore alias "{0}".</b>
<b>Explanation</b>	Keystore does not exist.
<b>Action</b>	Make sure that the keystore location is correct and the keystore exists on the file system.
<b>ISS.0139.9023E</b>	<b>Error: invalid keystore alias name "{0}".</b>
<b>Explanation</b>	Keystore alias is null or empty.
<b>Action</b>	Make sure that the keystore alias is not null or empty.
<b>ISS.0139.9024E</b>	<b>Error: cannot load the keystore pointed to by keystore alias "{0}", because of invalid password(s) for key alias(es) "{1}".</b>
<b>Explanation</b>	Invalid key alias password.
<b>Action</b>	Make sure that the key aliases passwords are correct.
<b>ISS.0139.9025E</b>	<b>Error: invalid key alias "{0}".</b>
<b>Explanation</b>	The key alias is invalid.
<b>Action</b>	Make sure that the key alias exists in the keystore.
<b>ISS.0139.9026E</b>	<b>Error: unable to look up the password for the key alias "{1}" in the keystore '{0}'.</b>
<b>Explanation</b>	Invalid key alias password.
<b>Action</b>	Make sure that the key alias password is correct.
<b>ISS.0139.9028E</b>	<b>Truststore alias "{0}" saved successfully. An error occurred while loading the truststore in memory, please edit the truststore alias configuration. Details: {1}.</b>
<b>Explanation</b>	Configuration file is corrupted.
<b>Action</b>	Make sure that the configuration file, which corresponds to the truststore alias is valid.

---

<b>ISS.0139.9029E</b>	<b>Error: cannot save the truststore alias "{0}".</b>
<b>Explanation</b>	Truststore location is invalid.
<b>Action</b>	Make sure that the truststore location is valid.
<b>ISS.0139.9030E</b>	<b>Error: truststore "{0}" not found.</b>
<b>Explanation</b>	The configuration file related to truststore alias is unavailable.
<b>Action</b>	Make sure that the configuration file related to the truststore alias exists in the directory <code>../config/security/keystore</code> .
<b>ISS.0139.9031E</b>	<b>Error: truststore "{0}" not found. Error: {1}.</b>
<b>Explanation</b>	Either the truststore location, or the configuration file is invalid.
<b>Action</b>	Make sure that the location of the truststore is correct; the truststore alias password is correct; and the configuration file exists, and it is not corrupted.
<b>ISS.0139.9033E</b>	<b>Error: cannot reload truststore "{0}". Details: {1}.</b>
<b>Explanation</b>	Either the keystore location is invalid, or the key aliases are modified.
<b>Action</b>	Make sure that the keystore location is valid and the key alias is not modified.
<b>ISS.0139.9034E</b>	<b>Error: cannot reload truststore "{0}".</b>
<b>Explanation</b>	Configuration file does not exist.
<b>Action</b>	Make sure that the configuration file, which corresponds to the truststore alias, exists in the directory <code>../config/security/keystore</code> .
<b>ISS.0139.9036E</b>	<b>Error: unable to delete the truststore alias "{0}".</b>
<b>Explanation</b>	Configuration file does not exist.
<b>Action</b>	Make sure that the configuration file for the truststore alias exists in the directory <code>../config/security/keystore</code> .
<b>ISS.0139.9037E</b>	<b>Error: invalid truststore alias name "{0}".</b>
<b>Explanation</b>	Invalid truststore name.
<b>Action</b>	Make sure that the truststore name is not null or empty.

<b>ISS.0139.9038E</b>	<b>Error: cannot retrieve data for the truststore "{0}".</b>
<b>Explanation</b>	Keystore is not loaded or initialized properly.
<b>Action</b>	Make sure that keystore is valid and the alias refers to the valid keystore location.
<b>ISS.0139.9039E</b>	<b>Error: cannot retrieve trusted certificates from the truststore pointed to by truststore alias "{0}". Details: {1}.</b>
<b>Explanation</b>	Truststore is not initialized or loaded properly.
<b>Action</b>	Reload the truststore alias and then make sure that the configuration file exists for the truststore alias.
<b>ISS.0139.9041E</b>	<b>Error: cannot retrieve the key for alias "{0}" from the keystore pointed to by keystore alias "{1}". Details: {2}.</b>
<b>Explanation</b>	Key alias entry in the keystore is not valid.
<b>Action</b>	Make sure that the key alias entry in the keystore is valid. For example, the certificate chain is available or the algorithm of the private key matches to the algorithm of the PublicKey in the end entity Certificate (at index 0).
<b>ISS.0139.9043E</b>	<b>Error: cannot retrieve the certificate for alias "{0}" from the truststore pointed to by truststore alias "{1}". Unsupported certificate type "{2}".</b>
<b>Explanation</b>	Invalid certificate type.
<b>Action</b>	Make sure that the certificate configured by the key alias is X509 Certificate.
<b>ISS.0139.9044E</b>	<b>Error: the alias has been modified from "{0}" to "{1}".</b>
<b>Explanation</b>	Keystore alias does not map to a valid keystore.
<b>Action</b>	Make sure that the keystore alias refers to a valid keystore.
<b>ISS.0139.9045E</b>	<b>Error: either the alias name "{0}" or the configuration file name "{1}" is incorrect.</b>
<b>Explanation</b>	Configuration file does not exist.
<b>Action</b>	Make sure that the configuration file exists for the alias in the directory ../config/security/keystore.
<b>ISS.0139.9047E</b>	<b>Password for following key aliases must be ASCII characters: {0}</b>
<b>Explanation</b>	The key alias password consists of non-ASCII characters.
<b>Action</b>	Make sure that the key alias password consists of valid ASCII characters.

<b>ISS.0139.9051E</b>	<b>Error: cannot load the keystore/truststore configuration file "{0}". Details:{1}.</b>
<b>Explanation</b>	Keystore alias does not map to a valid keystore.
<b>Action</b>	Make sure that the keystore alias refers to a valid keystore. In addition, verify that the configuration file related to the keystore alias is valid. Make sure that the security provider is installed and registered with Integration Server if you use a security provider.
<b>ISS.0139.9052E</b>	<b>Error: invalid keystore/truststore configuration file "{0}".</b>
<b>Explanation</b>	Configuration file does not exist.
<b>Action</b>	Make sure that the configuration file, which corresponds to the truststore alias, exists in the directory ../config/security/keystore.
<b>ISS.0139.9053E</b>	<b>Error: ISKeyStoreManager initialization failed. Cannot create the keystore configuration directory "{1}".</b>
<b>Explanation</b>	Keystore directory does not exist.
<b>Action</b>	Keystore location is invalid. Make sure that the keystore directory exists.
<b>ISS.0139.9054E</b>	<b>Error: alias has been modified from "{0}" to "{1}".</b>
<b>Explanation</b>	Keystore alias does not map to a valid keystore .
<b>Action</b>	Make sure that the keystore alias refers to a valid keystore.
<b>ISS.0139.9055E</b>	<b>Error: either the alias name "{0}" or the configuration file name "{1}" is incorrect.</b>
<b>Explanation</b>	Configuration file is corrupted.
<b>Action</b>	Make sure that the configuration file, which corresponds to the truststore alias, exists in the directory ../config/security/keystore.
<b>ISS.0139.9058I</b>	<b>Default keystore alias for Integration Server.</b>
<b>ISS.0139.9059I</b>	<b>Default truststore alias for Integration Server.</b>
<b>ISS.0141.0001E</b>	<b>Unable to create JMS URI for WS Endpoint Alias "{0}": {1}</b>
<b>Explanation</b>	The Web service endpoint alias does not contain the information needed to construct a JMS URI.
<b>Action</b>	Use the information in the exception to update the alias. For example, you may need to make changes to the provider Web service endpoint alias or edit the SOAP-JMS trigger used with the alias.

- ISS.0141.0002E**      **Unable to create WS Endpoint Trigger: {0}**
- Explanation**      Integration Server could not create a WS endpoint trigger using the information in the provider Web service endpoint alias.
- Action**              In Integration Server Administrator, use the information provided in the exception to edit the provider Web service endpoint alias
- 
- ISS.0141.0101W**      **WS-Policy file {0} with policy ID {1} is invalid. Details: {2}**
- Explanation**      The WS-Policy file added to the policy repository is not valid. Integration Server has moved the policy file to the IntegrationServer/config/wss/policies/invalid folder.
- Action**              Correct the invalid WS-Policy file in the IntegrationServer/config/wss/policies/invalid folder to make it valid and move it back into the main policy repository directory.
- 
- ISS.0141.0103W**      **Web service descriptor {0} is not available because the WS-Policy file {1} with policy ID {2} attached to the WSD is deleted.**
- Explanation**      The Web service descriptor is not available because the WS-Policy file attached to the Web service descriptor is deleted or moved from the policy repository.
- Action**              The following lists the actions you can take:
- 1) Ensure that the WS-Policy that is attached to the Web service descriptor resides in the policy repository.
  - OR-
  - 2) Edit the Web service descriptor so that it no longer uses the deleted WS-Policy file.
- 
- ISS.0141.0107W**      **Web service descriptor {0} is not available because the policy ID in WS-Policy file {1} is changed from {2} to {3}.**
- Explanation**      The Web service descriptor is not available because the policy ID of the WS-Policy file attached to the Web service descriptor has changed.
- Action**              The following lists the actions you can take:
- 1) Change the policy id of the WS-Policy that is attached to the Web service descriptor to what it was previously.
  - 2) Edit the Web service descriptor by re-attaching the WS-Policy file with the updated policy ID.

---

<b>ISS.0141.0108E</b>	<b>Transport header "{0}" is invalid and will not be added to the message. Transport headers must be Strings.</b>
<b>Explanation</b>	In the name/value pair supplied as a transport header, the name and the value must be of type String. If a transport header has a name or value that is not of type String, the header will not be included in the message.
<b>Action</b>	Change the transport header so that the name and value are both of type String.
<b>ISS.0141.0109W</b>	<b>Could not deploy consumer Web service descriptor {0} for handling asynchronous responses. Connectors generated for this consumer Web service descriptor can only be used for handling responses synchronously. Cause: {1}.</b>
<b>Explanation</b>	The consumer Web service descriptor specified in the message could not be deployed to handle asynchronous responses. See the error message for more details about the cause of the failure.
<b>Action</b>	If the error message indicates that the error can be resolved by changing the WSDL, change or correct the WSDL used for creating the consumer Web service descriptor and recreate the consumer. If the error still occurs, contact Software AG Global Support.
<b>ISS.0141.9106E</b>	<b>Received a null response.</b>
<b>Explanation</b>	An internal error occurred while processing the Web service request.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0141.9107E</b>	<b>Received unsupported content-encoding: {0}</b>
<b>Explanation</b>	The Web service response used the specified content-encoding, which is not supported.
<b>Action</b>	Ensure that the Web service request specifies a supported content-encoding for the response.
<b>ISS.0141.9108E</b>	<b>An HTTP transport error occurred. Error Code: {0}, Error Message: {1}</b>
<b>Explanation</b>	An error occurred while sending a Web service response. The error code and message portions of the error contain details about the error.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0141.9109E</b>	<b>Access Denied</b>
<b>Explanation</b>	A Web service request has arrived over an HTTP or HTTPS port, but the port access check has failed for the Web service descriptor. This means that the provider Web service descriptor name is either missing from the Allow list or is present in the Deny List, depending on how access to the port is defined.
<b>Action</b>	If access to this Web service is to be allowed over this port, ensure that the provider Web service descriptor name is either removed from the port's deny list or added to the port's allow list.

<b>ISS.0141.9208E</b>	<b>Could not deploy the Web service descriptor {0}. Cause: {1}</b>
<b>Explanation</b>	Integration Server could not deploy the Web service descriptor. Typical reasons are:  1) The WS-Policy that is attached to the provider Web service descriptor does not exist.  2) The module required to handle the attached WS-Policy does not exist.  3) The "rampartConfigProperties" parameter, which is in the axis2.xml file, is locked. If it is not one of these reasons, refer to the error message, which lists the cause.
<b>Action</b>	The following lists the actions you can take for one of the typical causes:  1) Ensure the WS-Policy that is attached to the Web service descriptor resides in the policy repository: (webMethods_directory)/IntegrationServer/config/wss  2) Ensure the module required to handle the attached WS-Policy resides in the (webMethods_directory)/IntegrationServer/config/wss/modules subdirectory.  3) Ensure the "rampartConfigProperties" parameter in the axis2.xml file is not locked. The axis2.xml file resides (webMethods_directory)/IntegrationServer/config/wss/modules subdirectory. For all other reasons, refer to the cause listed in the error message and respond accordingly.
<b>ISS.0141.9211E</b>	<b>Received a plain text response: {0}</b>
<b>Explanation</b>	A Web service call expected a SOAP Response but instead received a plain text response. The actual responseText is returned within a SOAP fault.
<b>Action</b>	Determine why the Web service provider did not return a SOAP response. It is possible that an incorrect endpoint address was used or an error occurred on the Web service provider.
<b>ISS.0141.9213E</b>	<b>Unknown web services reliable messaging sequence {0} specified for endpoint URI {1}.</b>
<b>Explanation</b>	A reliable messaging sequence with the specified sequence key corresponding to the specified endpoint URI does not exist.
<b>Action</b>	Specify a valid sequence key for the specified endpoint URI.
<b>ISS.0141.9214E</b>	<b>A duplicate web services reliable messaging sequence {0} specified for endpoint URI {1}.</b>
<b>Explanation</b>	A reliable messaging sequence with the specified sequence key and endpoint URI already exists.
<b>Action</b>	Specify a valid sequence key for the specified endpoint URI.

---

<b>ISS.0141.9215E</b>	<b>A closed web services reliable messaging sequence {0} specified for endpoint URI {1}.</b>
<b>Explanation</b>	The reliable messaging sequence with the specified sequence key and endpoint URI is closed.
<b>Action</b>	Specify a valid sequence key for the specified endpoint URI.
<b>ISS.0141.9216E</b>	<b>A terminated web services reliable messaging sequence {0} specified for endpoint URI {1}.</b>
<b>Explanation</b>	The reliable messaging sequence with the specified key and endpoint URI is terminated.
<b>Action</b>	Specify a valid sequence key for the specified endpoint URI.
<b>ISS.0141.9217E</b>	<b>Web services reliable messaging is not enabled for consumer web Services Descriptor {0}.</b>
<b>Explanation</b>	Reliable messaging is not enabled for the specified consumer web service descriptor.
<b>Action</b>	Specify a valid consumer web service descriptor for which reliable messaging is enabled or enable reliable messaging for the specified consumer web service descriptor.
<b>ISS.0142.0003W</b>	<b>User {0} issued request to cancel the thread. Thread id - {1}</b>
<b>Explanation</b>	Integration Server received a request to cancel an executing thread.
<b>Action</b>	No action is required.
<b>ISS.0142.0004W</b>	<b>User {0} issued request to kill the thread. Thread id - {1}</b>
<b>Explanation</b>	Integration Server received a request to kill an executing thread.
<b>Action</b>	No action is required.
<b>ISS.0142.0018E</b>	<b>The <code>watt.server.threadKill.timeout.enabled</code> parameter is set to true; however, the property that enables the thread kill facility, <code>watt.server.threadKill.enabled</code>, is set to false.</b>
<b>Explanation</b>	The ability to cancel or kill service threads is controlled by the <code>watt.server.threadKill.enabled</code> property. If you want to be able to cancel or kill threads, this property must be set to true, which is the default setting.
<b>Action</b>	Set <code>watt.server.threadKill.enabled</code> to true so that a flow step will not run beyond its specified timeout period.

**ISS.0145.0000E      Unable to start Integration Server in quiesce mode. No quiesce port was specified.**

**Explanation**      Integration Server cannot be started from the command line with the -quiesce switch unless a quiesce port is specified.

**Action**            Start Integration Server using either the Start menu (on Windows) or the startup.sh script (on UNIX). Then, specify the quiesce port that Integration Server should use to enter and exit quiesce mode.

**ISS.0145.0009E      Unable to quiesce this Integration Server. Exception: {0}**

**Explanation**      An error occurred while switching this server to quiesce mode.

**Action**            Check the Integration Server server and error logs. Take appropriate corrective action for the reported asset type. Then, try switching to quiesce mode again.

**ISS.0145.0012W      Handler "{0}" cannot disable asset type "{1}". Exception: {2}**

**Explanation**      While entering quiesce mode, Integration Server encountered an error when attempting to disable the specified asset type.

**Action**            In the Integration Server Administrator, manually disable the assets of the reported asset type.

**ISS.0145.0015E      Unable to return Integration Server to active mode. Exception: {0}**

**Explanation**      An error occurred while switching this Integration Server to active mode.

**Action**            Check the Integration Server server and error logs. Then, take the appropriate corrective action.

**ISS.0145.0018W      Handler "{0}" was unable to restore state of "{1}" asset type. Exception: {2}**

**Explanation**      While exiting quiesce mode, Integration Server could not restore the state of the specified asset type.

**Action**            In the Integration Server Administrator, manually enable the assets of the reported asset type.

**ISS.0145.0020W      Unable to shut down the quiesce mode manager. Exception: {0}.**

**Explanation**      Integration Server could not save the quiesce properties in the quiesce configuration file. The quiesce.cnf file either does not exist or is corrupt.

**Action**            Delete the quiesce.cnf file from the Integration Server\_directory\config directory. Then, restart the server and specify the quiesce port again.

---

<b>ISS.0145.0022E</b>	<b>Unable to save the configuration after setting quiesce port to {0}. Exception: {1}</b>
<b>Explanation</b>	An error occurred when the quiesce port was changed and Integration Server attempted to save the changes.
<b>Action</b>	Set the quiesce port to a valid port. If the error recurs, contact Software AG Global Support.
<b>ISS.0145.0023E</b>	<b>Unable to validate quiesce port {0}. Port does not exist.</b>
<b>Explanation</b>	The quiesce port has been deleted.
<b>Action</b>	Specify the port alias of an existing valid port.
<b>ISS.0145.0024E</b>	<b>Unable to validate quiesce port {0}. Port is not enabled.</b>
<b>Explanation</b>	The quiesce port is disabled.
<b>Action</b>	Enable the quiesce port.
<b>ISS.0145.0025E</b>	<b>Unable to validate quiesce port {0}. Port is not associated with WmRoot or WmPublic package.</b>
<b>Explanation</b>	The quiesce port does not reside in either the WmRoot or the WmPublic package.
<b>Action</b>	Specify the port alias of a valid quiesce port that resides in either the WmRoot package or the WmPublic package.
<b>ISS.0145.0027E</b>	<b>Unable to validate quiesce port {0}. Port type is incorrect.</b>
<b>Explanation</b>	The specified quiesce port does not belong to the HTTP or HTTPS protocol.
<b>Action</b>	Specify the port alias of a valid quiesce port of type HTTP or HTTPS.
<b>ISS.0145.0028E</b>	<b>Unable to validate quiesce port {0}. Port is suspended.</b>
<b>Explanation</b>	The quiesce port is suspended.
<b>Action</b>	Resume the quiesce port.
<b>ISS.0145.0029E</b>	<b>Unable to validate quiesce port {0}. Port does not have the necessary access mode.</b>
<b>Explanation</b>	The quiesce port's access mode is set to Deny+.
<b>Action</b>	Change the quiesce port's access mode to Allow.

<b>ISS.0145.0202E</b>	<b>Integration Server that is configured to be a member of a cluster did not join the cluster when exiting quiesce mode.</b>
<b>Explanation</b>	When exiting quiesce mode, Integration Server did not join the cluster.
<b>Action</b>	Use the Integration Server server log and error log to determine why Integration Server did not join the cluster and take the necessary actions to correct the error. Then, do one of the following for Integration Server to join the cluster: either restart Integration Server or enter and exit quiesce mode.
<b>ISS.0145.0206E</b>	<b>Integration Server is not configured for clustering. Errors occurred during initialization of cache managers. Exception: {0}</b>
<b>Explanation</b>	When exiting quiesce mode, Integration Server failed to initialize cache managers.
<b>Action</b>	Check Integration Server Server and Error logs and take required actions to correct the clustering error. Once this is done, you can either restart Integration Server or Enter and Exit Quiesce Mode to enable the cluster.
<b>ISS.0145.0207E</b>	<b>Integration Server is not configured for clustering. Errors occurred during initialization of cache managers.</b>
<b>Explanation</b>	When exiting quiesce mode, Integration Server failed to initialize cache managers.
<b>Action</b>	Check Integration Server Server and Error logs and take required actions to correct the clustering error. Once this is done, you can either restart Integration Server or Enter and Exit Quiesce Mode.
<b>ISS.0145.0302W</b>	<b>Unable to suspend {0}. Reason: {1}</b>
<b>Explanation</b>	While entering quiesce mode, Integration Server could not suspend the specified trigger.
<b>Action</b>	Check the server log for details and manually suspend the trigger.
<b>ISS.0145.0306W</b>	<b>Unable to resume {0}. Reason: {1}</b>
<b>Explanation</b>	While entering quiesce mode, Integration Server could not resume the specified trigger, even though the package containing trigger is enabled.
<b>Action</b>	Check the server log for details and manually enable the trigger.
<b>ISS.0145.0315W</b>	<b>Quiesce timeout limit of {0} minutes has expired. {1} services are running. Proceeding with disabling the packages.</b>
<b>Explanation</b>	Integration Server is proceeding with disabling packages even though some long-running services are still running. One or more of these services might fail.
<b>Action</b>	In the Integration Server Administrator, check which services are still running and make sure those services have completed before attempting to quiesce this server again. Alternatively, increase the quiesce timeout limit.

---

<b>ISS.0145.0504E</b>	<b>Cannot disable packages. Exception: {0}</b>
<b>Explanation</b>	While entering quiesce mode, Integration Server could not disable packages.
<b>Action</b>	Check the Integration Server server log for details. Then, in the Integration Server Administrator, manually disable the packages.
<b>ISS.0145.0506E</b>	<b>Package "{0}" is not loaded.</b>
<b>Explanation</b>	While starting in quiesce mode, Integration Server could not load the WmRoot or WmPublic package.
<b>Action</b>	Start the server in active mode, and then enter quiesce mode.
<b>ISS.0145.0509E</b>	<b>Unable to restore state of packages. Exception: {0}</b>
<b>Explanation</b>	While exiting quiesce mode, Integration Server could not restore the state of packages.
<b>Action</b>	Check the Integration Server server log for details. Then, in the Integration Server Administrator, manually enable or disable the packages as necessary.
<b>ISS.0145.0511E</b>	<b>Cannot enable package "{0}".</b>
<b>Explanation</b>	While exiting quiesce mode, Integration Server could not enable the specified package.
<b>Action</b>	In the Integration Server Administrator, manually enable the specified package.
<b>ISS.0145.0603E</b>	<b>Cannot enable listener "{0}" in quiesce mode. Exception: {1}</b>
<b>Explanation</b>	Integration Server could not start the quiesce listener.
<b>Action</b>	Ensure that the listener is enabled in the listener.cnf configuration file.
<b>ISS.0145.0604E</b>	<b>Cannot disable listener "{0}" in quiesce mode. Exception: {1}</b>
<b>Explanation</b>	Integration Server could not stop the quiesce listener.
<b>Action</b>	Ensure that the listener is disabled in the listener.cnf configuration file.
<b>ISS.0145.0700E</b>	<b>Unable to process scheduled task. Exception: {0}</b>
<b>Explanation</b>	Integration Server encountered a runtime error of unknown cause while attempting to quiesce a scheduled task.
<b>Action</b>	Check the server log for details and take the appropriate corrective steps.

<b>ISS.0145.0701E</b>	<b>Unable to retrieve scheduled task "{0}" from database. Exception: {1}</b>
<b>Explanation</b>	Either the database server is down or Integration Server is no longer connected to the database.
<b>Action</b>	Make sure the connection between Integration Server and the database is active.
<b>ISS.0145.0702E</b>	<b>Unable to retrieve scheduled task from database. Exception: {0}</b>
<b>Explanation</b>	Either the database server is down or Integration Server is no longer connected to the database.
<b>Action</b>	Make sure the connection between Integration Server and the database is active.
<b>ISS.0145.0705E</b>	<b>Unable to resume scheduled task "{0}" in quiesce mode. Exception: {1}</b>
<b>Explanation</b>	The state of the scheduled task may be inconsistent between the database and Integration Server. This can occur when changes are made to the database outside of Integration Server.
<b>Action</b>	Check the state of the task in the database. In the Integration Server Administrator, change the state of the task to match the state reported in the database.
<b>ISS.0145.0711E</b>	<b>Unable to retrieve host name. Exception: {0}</b>
<b>Explanation</b>	The Integration Server you are attempting to quiesce is part of a cluster, and there is an issue with the cluster's configuration.
<b>Action</b>	Verify your clustering environment and cache configuration according to the guidelines in the webMethods Integration Server documentation.
<b>ISS.0145.0803W</b>	<b>Cannot disable JMS connection alias "{0}". Reason: {1}</b>
<b>Explanation</b>	While entering quiesce mode, Integration Server could not disable the specified JMS connection alias.
<b>Action</b>	In the Integration Server Administrator, manually disable the JMS connection alias.
<b>ISS.0145.0805W</b>	<b>Cannot enable JMS connection alias "{0}". Reason: {1}</b>
<b>Explanation</b>	While exiting quiesce mode, Integration Server could not enable the specified JMS connection alias.
<b>Action</b>	In the Integration Server Administrator, manually enable the JMS connection alias.

---

<b>ISS.0145.0902E</b>	<b>Unable to shut down the guaranteed delivery outbound Job Manager. Exception: {0}</b>
<b>Explanation</b>	While entering quiesce mode, Integration Server could not shut down the outbound Job Manager.
<b>Action</b>	In the Integration Server Administrator, manually disable the guaranteed delivery outbound Job Manager.
<b>ISS.0145.0905E</b>	<b>Unable to initialize the guaranteed delivery inbound Job Manager. Exception: {0}</b>
<b>Explanation</b>	While exiting quiesce mode, Integration Server could not initialize the guaranteed delivery inbound Job Manager.
<b>Action</b>	In the Integration Server Administrator, manually enable the guaranteed delivery inbound Job Manager.
<b>ISS.0145.0906E</b>	<b>Unable to initialize the guaranteed delivery outbound Job Manager. Exception: {0}</b>
<b>Explanation</b>	While exiting quiesce mode, Integration Server could not initialize the guaranteed delivery outbound Job Manager.
<b>Action</b>	In the Integration Server Administrator, manually enable the guaranteed delivery outbound Job Manager.
<b>ISS.0146.9001E</b>	<b>Key cannot be empty.</b>
<b>Explanation</b>	The Key field must not be empty while adding a global variable.
<b>Action</b>	Provide a valid Key for the global variable.
<b>ISS.0146.9002E</b>	<b>Value cannot be empty.</b>
<b>Explanation</b>	The Value field must not be empty while adding a global variable.
<b>Action</b>	Provide a valid value for global variable.
<b>ISS.0146.9003E</b>	<b>Global variable {0} already exists.</b>
<b>Explanation</b>	Global variable key must be unique.
<b>Action</b>	Provide a unique key for the global variable.
<b>ISS.0146.9004E</b>	<b>Global variable {0} does not exist.</b>
<b>Explanation</b>	You attempted to delete or edit a global variable that does not exist.
<b>Action</b>	Ensure that the global variable exists before attempting to edit or delete it.

<b>ISS.0146.9005</b>	<b>Global Variable key cannot contain any of these characters:{0}</b>
<b>Explanation</b>	The global variable key that you specified contains special characters other than period (.) or underscore(_).
<b>Action</b>	Ensure that the global variable key does not contain any special characters other than period or underscore(_).
<b>ISS.0146.9006E</b>	<b>Global variable key cannot exceed 255 characters.</b>
<b>Explanation</b>	The global variable key that you specified contains more than 255 characters.
<b>Action</b>	Ensure that length of the global variable key is less than or equal to 255.
<b>ISS.0146.9007E</b>	<b>Global variable value cannot exceed 255 characters.</b>
<b>Explanation</b>	The global variable value that you specified contains more than 255 characters.
<b>Action</b>	Ensure that length of the global variable value is less than or equal to 255.
<b>ISS.0146.9008E</b>	<b>The value of the 'isSecure' field of a global variable cannot be edited.</b>
<b>Explanation</b>	You attempted to edit the value of the 'isSecure' field of a global variable.
<b>Action</b>	Ensure that you do not edit the value of the 'isSecure' field of a global variable.
<b>ISS.0147.9001E</b>	<b>SFTP server alias {0} already exists.</b>
<b>Explanation</b>	The SFTP server alias name that you specified already exists in Integration Server.
<b>Action</b>	Specify an SFTP server alias name that does not exist in Integration Server.
<b>ISS.0147.9002E</b>	<b>SFTP server alias {0} does not exist.</b>
<b>Explanation</b>	The specified SFTP server alias does not exist in Integration Server.
<b>Action</b>	Ensure that the SFTP server alias name you specified is correct and that this SFTP server alias exists in Integration Server.
<b>ISS.0147.9003E</b>	<b>Cannot retrieve the host key from location {0}. Details: Corrupt or unknown public key file format.</b>
<b>Explanation</b>	The specified host key file contains the public key of the SFTP server in an unsupported format.
<b>Action</b>	Ensure that the host key file contains the public key in the supported (openssh) format.

---

<b>ISS.0147.9004E</b>	<b>Cannot find the private key file {0}.</b>
<b>Explanation</b>	Integration Server is unable to find the private key file at specified location.
<b>Action</b>	Ensure that the private key file exists at the specified location.
<b>ISS.0147.9005E</b>	<b>Private key file {0} already exists in Integration Server.</b>
<b>Explanation</b>	The specified private key file already exists in Integration Server.
<b>Action</b>	Specify a different private key file.
<b>ISS.0147.9006E</b>	<b>User alias {0} does not exist.</b>
<b>Explanation</b>	The specified SFTP user alias does not exist in Integration Server.
<b>Action</b>	Ensure that the SFTP user alias name you specified is correct and that this SFTP user alias exists in Integration Server.
<b>ISS.0147.9007E</b>	<b>User alias {0} already exists.</b>
<b>Explanation</b>	The SFTP user alias name that you specified already exists in Integration Server.
<b>Action</b>	Specify an SFTP user alias name that does not exist in Integration Server.
<b>ISS.0147.9008E</b>	<b>Cannot read host key from location {0}.</b>
<b>Explanation</b>	Integration Server is unable to read the host key file from the location you specified.
<b>Action</b>	Specify a valid host key file location to which Integration Server has the required permission for reading.
<b>ISS.0147.9009E</b>	<b>Cannot write the public key to file {0}.</b>
<b>Explanation</b>	Integration Server is unable to write the host key file to the specified location.
<b>Action</b>	Ensure that Integration Server has the required permission and enough disk space to write the host key to the specified location.
<b>ISS.0147.9010E</b>	<b>Cannot get host key from server {0}. Details: {1}</b>
<b>Explanation</b>	Integration Server is unable to retrieve the host key from the specified (arg0) SFTP server.
<b>Action</b>	Ensure that the SFTP server is configured and running on the specified host-port.

<b>ISS.0147.9011E</b>	<b>Test of user alias {0} Fail. Details: {1}</b>
<b>Explanation</b>	Testing of SFTP user alias (arg0) failed due to error (arg1).
<b>Action</b>	Ensure that the SFTP user alias information is correct and that the SFTP server is running on the specified host and port.
<b>ISS.0147.9012E</b>	<b>Cannot delete SFTP server alias {0} because the following SFTP user alias(es) are using it : {1}.</b>
<b>Explanation</b>	Integration Server cannot delete the SFTP server alias (arg0) because the SFTP user alias(es) [arg1] are using it.
<b>Action</b>	Ensure that the SFTP server alias that you want to delete is not included in any SFTP user alias definition.
<b>ISS.0148.9010E</b>	<b>A valid short value must be specified for "{0}".</b>
<b>Explanation</b>	The value of short data type that you entered for field {0} while calling the service is invalid.
<b>Action</b>	Ensure that the value specified for the field {0} is a valid short value.
<b>ISS.0148.9011E</b>	<b>A valid boolean value must be specified for "{0}".</b>
<b>Explanation</b>	The value of boolean data type that you entered for field {0} while calling the service is invalid.
<b>Action</b>	Ensure that the value specified for the field {0} is a valid boolean value.
<b>ISS.0148.9012E</b>	<b>A valid double value must be specified for "{0}".</b>
<b>Explanation</b>	The value of double data type that you entered for field {0} while calling the service is invalid.
<b>Action</b>	Ensure that the value specified for the field {0} is a valid double value.
<b>ISS.0148.9013E</b>	<b>A valid float value must be specified for "{0}".</b>
<b>Explanation</b>	The value of float data type that you entered for field {0} while calling the service is invalid.
<b>Action</b>	Ensure that the value specified for the field {0} is a valid float value.

---

<b>ISS.0148.9014E</b>	<b>A valid character value must be specified for "{0}".</b>
<b>Explanation</b>	The value of character data type that you entered for field {0} while calling the service is invalid.
<b>Action</b>	Ensure that the value specified for the field {0} is a valid character value.
<b>ISS.0148.9015E</b>	<b>A valid byte value must be specified for "{0}".</b>
<b>Explanation</b>	The value of byte data type that you entered for field {0} while calling the service is invalid.
<b>Action</b>	Ensure that the value specified for the field {0} is a valid byte value.
<b>ISS.0148.9016E</b>	<b>A valid long value must be specified for "{0}".</b>
<b>Explanation</b>	The value of long data type that you entered for field {0} while calling the service is invalid.
<b>Action</b>	Ensure that the value specified for the field {0} is a valid long value.
<b>ISS.0148.9017E</b>	<b>{1} is not a valid value for {0}. Allowed values are {2}</b>
<b>Explanation</b>	The value {1} specified for field {0} while calling a service is not available in the pick list {2}.
<b>Action</b>	Ensure that the value specified for the field {0} is in the pick list {2}.
<b>ISS.0149.0001E</b>	<b>Message size exceeded the limit of {0} MB.</b>
<b>Explanation</b>	Enterprise Gateway Server could not process the request because the message associated with the request is larger than the size allowed in the Enterprise Gateway rule.
<b>Action</b>	Either reduce the message size of the request or increase the message size limit in the filter for the rule.
<b>ISS.0149.0002D</b>	<b>Enterprise Gateway rules processing has started on URL {0} and IP address {1} at time {2}.</b>
<b>Explanation</b>	Enterprise Gateway Server has started processing rules.
<b>Action</b>	No action is needed.

<b>ISS.0149.0003D</b>	<b>Processing Enterprise Gateway rule "{0}".</b>
<b>Explanation</b>	Enterprise Gateway Server has started processing the specified rule.
<b>Action</b>	No action is needed.
<b>ISS.0149.0004D</b>	<b>Processing Enterprise Gateway rule filter "{0}".</b>
<b>Explanation</b>	Enterprise Gateway Server has started processing the specified rule filter.
<b>Action</b>	No action is needed.
<b>ISS.0149.0005E</b>	<b>A rule violation occurred for Enterprise Gateway rule "{0}" for filter "{1}": {2}.</b>
<b>Explanation</b>	Enterprise Gateway Server could not process the request because the request met a filter condition defined in the Enterprise Gateway rule.
<b>Action</b>	Check the filter conditions for the specified rule and either change the conditions or modify the request so a rule violation does not occur.
<b>ISS.0149.0006E</b>	<b>A rule violation occurred for Enterprise Gateway rule "{0}".</b>
<b>Explanation</b>	Enterprise Gateway Server could not process the request because its type did not match the request type configured in the Enterprise Gateway rule.
<b>Action</b>	Modify the request so it matches one of the configured request types.
<b>ISS.0149.0007E</b>	<b>Denial of Service by IP address limit was reached for IP address {0}.</b>
<b>Explanation</b>	Enterprise Gateway Server could not process the request because an Enterprise Gateway Denial of Service limit was reached for this IP address.
<b>Action</b>	Delete the IP address from the Enterprise Gateway deny list.
<b>ISS.0149.0008W</b>	<b>IP address {0} is unblocked.</b>
<b>Explanation</b>	Enterprise Gateway Server is again accepting requests from this IP address because the Enterprise Gateway Denial of Service block interval has elapsed.
<b>Action</b>	No action is needed.
<b>ISS.0149.0009W</b>	<b>IP address {0} is blocked for a duration of {1} minutes.</b>
<b>Explanation</b>	Enterprise Gateway Server has blocked incoming requests from this IP address because the number of requests from this address has exceeded the specified Enterprise Gateway Denial of Service limits.
<b>Action</b>	Wait for the IP address to become unblocked when the block interval elapses. If an IP address is blocked too often, reevaluate the "maximum requests" and "maximum requests in progress" limits.

---

<b>ISS.0149.0011E</b>	<b>Requests from IP address {0} have exceeded the maximum in-progress limit of {1}.</b>
<b>Explanation</b>	Enterprise Gateway Server will deny or block incoming requests from this IP address because the number of requests from this address has exceeded the specified Enterprise Gateway Denial of Service limit for in-progress requests.
<b>Action</b>	Delete the IP address from the Enterprise Gateway deny list.
<b>ISS.0149.0012D</b>	<b>Denial of Service clean-up task has executed.</b>
<b>Explanation</b>	Periodically, Enterprise Gateway Server starts a task to clear old Denial of Service entries from the queue.
<b>Action</b>	No action is needed.
<b>ISS.0149.0013E</b>	<b>Global Denial of Service limits were reached: {0}.</b>
<b>Explanation</b>	Enterprise Gateway Server will block incoming requests received from all IP addresses because the number of requests has exceeded the specified Enterprise Gateway global Denial of Service limits.
<b>Action</b>	Wait for the block interval to elapse.
<b>ISS.0149.0014E</b>	<b>Requests from IP address {0} have exceeded the maximum request limit of {1} in {2} seconds.</b>
<b>Explanation</b>	Enterprise Gateway Server will deny or block incoming requests from this IP address because the number of requests from this address has exceeded the specified Enterprise Gateway Denial of Service limit for requests allowed in a specified time period.
<b>Action</b>	Delete the IP address from the Enterprise Gateway deny list.
<b>ISS.0149.0015S</b>	<b>Requests from all IP addresses will be blocked for a duration of {0} minutes.</b>
<b>Explanation</b>	Enterprise Gateway Server will block incoming requests received from all IP addresses for the indicated interval because the number of requests has exceeded the specified Enterprise Gateway global Denial of Service limits.
<b>Action</b>	Wait for the block interval to elapse.
<b>ISS.0149.0016E</b>	<b>OAuth token is not present in the request header.</b>
<b>Explanation</b>	Enterprise Gateway Server could not process the request because the OAuth token is not present in the request header.
<b>Action</b>	Either disable the OAuth filter or ensure that the request contains the OAuth token.

<b>ISS.0149.0017E</b>	<b>Maximum in-progress limit of {0} has been exceeded.</b>
<b>Explanation</b>	Enterprise Gateway Server will block incoming requests received from all IP addresses because the number of requests has exceeded the specified Enterprise Gateway global Denial of Service limit for in-progress requests.
<b>Action</b>	Wait for the block interval to elapse.
<b>ISS.0149.0018E</b>	<b>Maximum requests limit of {0} in {1} seconds has been exceeded.</b>
<b>Explanation</b>	Enterprise Gateway Server will block incoming requests received from all IP addresses because the number of requests has exceeded the specified Enterprise Gateway global Denial of Service limit for requests allowed in a specified time period.
<b>Action</b>	Wait for the block interval to elapse.
<b>ISS.0149.0019E</b>	<b>The header "{0}" is not present in the request header.</b>
<b>Explanation</b>	Enterprise Gateway Server could not process the request because the indicated header is not present in the request header.
<b>Action</b>	Either disable the mobile application protection filter or ensure that the request has the required mobile device type, application name, and application version request headers.
<b>ISS.0149.0020E</b>	<b>Mobile application version {0} is {1} {2} for application "{3}" and device type "{4}".</b>
<b>Explanation</b>	Enterprise Gateway Server could not process the request because the request matches the indicated mobile application protection filter condition. As a result, the request is in violation of the Enterprise Gateway rule.
<b>Action</b>	Reevaluate the mobile application protection filter conditions if desired.
<b>ISS.0149.0501CS</b>	<b>Exception occurred while sending a notification for Enterprise Gateway rule "{0}": {1}.</b>
<b>Explanation</b>	Enterprise Gateway Server could not send an alert notification indicating that a rule violation occurred for the reason indicated in the exception.
<b>Action</b>	Check the server error logs and take corrective steps.
<b>ISS.0149.0502CS</b>	<b>Exception occurred while invoking "{0}": {1}.</b>
<b>Explanation</b>	Enterprise Gateway Server could not invoke the flow service to notify users that a rule violation occurred for the reason indicated in the exception.
<b>Action</b>	Check the server error logs and take corrective steps.

---

<b>ISS.0149.0503W</b>	<b>Alert notification for Enterprise Gateway rule "{0}" was not sent. No alert options were found for the rule.</b>
<b>Explanation</b>	Enterprise Gateway Server could not send an alert notification indicating that a rule violation occurred because no alert options were specified for the rule to indicate how to handle the alert.
<b>Action</b>	Check the server error logs and take corrective steps.
<b>ISS.0149.0504W</b>	<b>Alert notification for Enterprise Gateway rule "{0}" was not sent. SMTP server configuration is not valid.</b>
<b>Explanation</b>	Enterprise Gateway Server could not send an alert notification for the Enterprise Gateway rule because the server is not configured to send emails.
<b>Action</b>	Check the settings on the Settings > Resources screen under Email Notification. If your server is not configured to send emails, use Integration Server Administrator to configure an SMTP port.
<b>ISS.0149.9001E</b>	<b>Enterprise Gateway rule "{0}" already exists.</b>
<b>Explanation</b>	Enterprise Gateway Server could not create the rule because an Enterprise Gateway rule with this name already exists.
<b>Action</b>	Specify a unique name for the Enterprise Gateway rule.
<b>ISS.0149.9002E</b>	<b>Enterprise Gateway rule "{0}" was not found</b>
<b>Explanation</b>	Enterprise Gateway Server could not find the specified Enterprise Gateway rule. Either the rule does not exist on this server or the specified rule name is incorrect.
<b>Action</b>	Ensure that the Enterprise Gateway rule exists on this Enterprise Gateway Server and that the name specified for the rule is correct.
<b>ISS.0149.9003E</b>	<b>Mobile application protection filter conditions were not specified.</b>
<b>Explanation</b>	Enterprise Gateway Server failed to create or update an Enterprise Gateway rule that has a mobile application protection filter enabled because no filter conditions were specified.
<b>Action</b>	Either specify one or more conditions or disable this filter.
<b>ISS.0149.9004E</b>	<b>Mobile application "{0}" was not found.</b>
<b>Explanation</b>	Enterprise Gateway Server did not recognize the application name provided in the mobile application protection filter because the application is not in the Mobile Applications list.
<b>Action</b>	Either specify a different mobile application or use the Mobile Application Protection Options screen in Integration Server Administrator to add the application.

- ISS.0149.9005E**      **Mobile device type "{0}" was not found.**  
**Explanation**      Enterprise Gateway Server did not recognize the device type provided in the mobile application protection filter because the device is not in the Device Types list.  
**Action**              Specify a different device type or use the Mobile Application Protection Options screen in Integration Server Administrator to add the device type.
- ISS.0149.9006E**      **Condition "{0}" is not supported.**  
**Explanation**      Enterprise Gateway Server failed to apply the condition to this Enterprise Gateway rule because the condition character specified in the mobile application protection filter is not valid.  
**Action**              Ensure that the condition is one of the following characters: =,<,>,<=,>=,<>
- ISS.0149.9007E**      **Mobile application version "{0}" is not valid.**  
**Explanation**      Enterprise Gateway Server failed to apply the condition to this Enterprise Gateway rule because the application version specified in the mobile application protection filter is not formatted correctly.  
**Action**              Ensure that the application version is in the following format:  
<major-version>.<minor-version>.<sub-minor-version>.<patch>
- ISS.0149.9008E**      **Mobile applications list was not updated. The following applications are specified in one or more rules: {0}.**  
**Explanation**      Enterprise Gateway Server failed to remove mobile applications from the application list because the applications are specified in a filter condition for one or more rules.  
**Action**              Before you attempt to remove a mobile application from the list, make sure the application is not specified in a filter condition in any rules.
- ISS.0149.9009E**      **Device types list was not updated. The following device types are specified in one or more rules: {0}.**  
**Explanation**      Enterprise Gateway Server failed to remove device types from the device types list because the device types are specified in a filter condition for one or more rules.  
**Action**              Before you attempt to remove a device type from the list, make sure the device type is not specified in a filter condition in any rules.
- ISS.0149.9010E**      **Service name "{0}" is not valid.**  
**Explanation**      A flow service was specified for Enterprise Gateway Server to invoke when an Enterprise Gateway rule violation occurs, but the service name is not valid.  
**Action**              Specify a valid, fully qualified service name.

---

<b>ISS.0150.9001</b>	<b>Missing required parameter: "{0}".</b>
<b>Explanation</b>	A required parameter was not supplied.
<b>Action</b>	Supply the specified required parameter.
<b>ISS.0150.9002</b>	<b>Unable to create port: "{0}".</b>
<b>Explanation</b>	Integration Server cannot create the port because an exception occurred.
<b>Action</b>	Use the specified exception to determine why the port could not be created.
<b>ISS.0150.9003</b>	<b>Unable to set the IP access mode for the port: {0}</b>
<b>Explanation</b>	An error occurred during an attempt to set the IP access mode for the port.
<b>Action</b>	Use the exception returned by the error message to determine the cause of the error.
<b>ISS.0150.9004</b>	<b>Unable to set the IP access list for the port: {0}</b>
<b>Explanation</b>	An error occurred while attempting to set the IP access list for the port.
<b>Action</b>	Use the exception returned by the error message to determine the cause of the error.
<b>ISS.0150.9005</b>	<b>Unable to set the URL access mode for the port: {0}</b>
<b>Explanation</b>	An error occurred during an attempt to set the URL access mode for the port.
<b>Action</b>	Use the exception returned by the error message to determine the cause of the error.
<b>ISS.0150.9006</b>	<b>Unable to set the URL access list for the port: {0}</b>
<b>Explanation</b>	An error occurred during an attempt to set the URL access list for the port.
<b>Action</b>	Use the exception returned by the error message to determine the cause of the error.
<b>ISS.0150.9008</b>	<b>The primary port cannot be changed.</b>
<b>Explanation</b>	An update operation attempted to make changes to the primary port of the Integration Server. The primary port cannot be updated.
<b>Action</b>	To make changes to the port that is assigned to be the primary port, specify another port as the primary port. Then make changes to the port that was previously the primary port.

**ISS.0150.9009**      **Invalid protocol. The webMethods Platform Manager subsystem does not support the protocol "{0}".**

**Explanation**      A create or update operation for port settings specified an protocol that is not supported by the webMethods Platform Manager subsystem in Integration Server.

**Action**            Specify a protocol supported by the webMethods Platform Manager subsystem in Integration Server.

**ISS.0150.9010**      **Cannot change port protocol [from {0} to {1}].**

**Explanation**      An update operation attempted to change the protocol for the port. Once a port is created, the protocol cannot be changed.

**Action**            To change the protocol used with a particular port, first delete the port. Then, recreate the port with the new protocol.

**ISS.0150.9011**      **Package "{0}" is not loaded or is not enabled.**

**Explanation**      A create or update port operation attempted to create or change a port in a package that either does not exist or is not enabled.

**Action**            Make sure the package exists and is enabled before performing the create or update port operation.

**ISS.0150.9012**      **Unable to disable port: {0}**

**Explanation**      An exception occurred during an attempt to disable the port

**Action**            Review the exception to determine why the port could not be disabled.

**ISS.0150.9013**      **No port found with unique ID {0}.**

**Explanation**      A read, update, or delete port operation supplied a port ID that does not exist.

**Action**            Verify the instance ID that the Software AG Platform Manager associates with the port. To do this, refresh the port list on the Software AG Platform Manager.

**ISS.0150.9014**      **The port was created. However, the access configuration was not set: {0}**

**Explanation**      A create port operation was partially successful. The port was created and some configuration settings were established. However, establishing some or all of the access configuration settings failed. The port will be disabled if it is not already.

**Action**            Review the exception to determine why the access configuration could not be set.

---

<b>ISS.0150.9015</b>	<b>The port was partially updated. However, the access configuration was not set: {0}</b>
<b>Explanation</b>	An update port operation was partially successful. Some settings were updated. However, updates to some or all of the access configuration settings failed. The port will be disabled if it is not already.
<b>Action</b>	Review the exception to determine why the access configuration settings could not be updated.
<b>ISS.0150.9020</b>	<b>The diagnostic port must be associated with the WmRoot package. Package {0} is invalid.</b>
<b>Explanation</b>	A create or update operation for the diagnostic port attempted to assign a package other than WmRoot to the diagnostic port. This is not allowed. The diagnostic port must be associated with the WmRoot package.
<b>Action</b>	Specify the WmRoot package when creating or updating the diagnostic port.
<b>ISS.0150.9021</b>	<b>Cannot create diagnostic port. A diagnostic port with port number {0} and ID {1} already exists. Each Integration Server can have one diagnostic port only.</b>
<b>Explanation</b>	An operation attempted to create a diagnostic port. However, the Integration Server already has a diagnostic port. Each Integration Server can have one diagnostic port only.
<b>Action</b>	To create a new diagnostic port, delete the existing diagnostic port first.
<b>ISS.0150.9022</b>	<b>Unable to update port. The diagnostic port cannot be changed to a standard port.</b>
<b>Explanation</b>	An operation attempted to change a diagnostic port to a standard port. A diagnostic port cannot be created in this way because the type of port may not be changed.
<b>Action</b>	To create a standard port on an assigned diagnostic port, first delete the existing diagnostic port and then create a standard port.
<b>ISS.0150.9023</b>	<b>Unable to update port. The standard port cannot be changed to a diagnostic port.</b>
<b>Explanation</b>	An operation attempted to change a standard port to a diagnostic port. A diagnostic port cannot be created in this way because the type of port may not be changed.
<b>Action</b>	To create a diagnostic port on an assigned port, first delete the existing port and then create a diagnostic port.
<b>ISS.0150.9024</b>	<b>Invalid keystore alias {0}</b>
<b>Explanation</b>	A create or update port operation specified a keystore alias that does not exist.
<b>Action</b>	Make sure to specify the name of an existing keystore alias. Verify that the name of the keystore alias is spelled correctly.

<b>ISS.0150.9025</b>	<b>Invalid key alias {0}</b>
<b>Explanation</b>	A create or update port operation specified a key alias that does not exist.
<b>Action</b>	Make sure to specify the name of an existing key alias. Verify that the name of the key alias is spelled correctly
<b>ISS.0150.9026</b>	<b>Invalid truststore alias {0}</b>
<b>Explanation</b>	A create or update port operation specified a truststore alias that does not exist.
<b>Action</b>	Make sure to specify the name of an existing truststore alias. Verify that the name of the truststorealias is spelled correctly.
<b>ISS.0150.9027</b>	<b>Cannot enable port. Keystore alias is empty. Specify a keystore alias for the port or a define a default SSL keystore alias for the Integration Server.</b>
<b>Explanation</b>	A create or update port operation did not specify a keystore alias and there is not a default SSL keystore alias for the Integration Server. An HTTPS port requires a keystore alias.
<b>Action</b>	Either define a keystore alias or specify a default SSL keystore alias for the Integration Server. The default SSL keystore alias is the keystore alias specified during configuration of the SSL authentication credentials for the Integration Server. To use a defined keystore alias with the HTTPS port, specify that keystore alias in the create or update operation. To use the Integration Server's default SSL keystore alias with the HTTPS port, do not supply keystore alias information for the create or update operations.
<b>ISS.0150.9028</b>	<b>Cannot enable port. Keystore alias is empty. Specify a key alias for the port or a define a default SSL key alias for the Integration Server.</b>
<b>Explanation</b>	A create or update port operation did not specify a key alias and there is not a default SSL key alias for the Integration Server. An HTTPS port requires a key alias.
<b>Action</b>	Either define a key alias or specify a default SSL key alias for the Integration Server. The default SSL key alias is the keys alias specified during configuration of the SSL authentication credentials for the Integration Server. To use a defined key alias with the HTTPS port, specify that keystore alias in the create or update operation. To use the Integration Server's default SSL key alias with the HTTPS port, do not supply key alias information for the create or update operations.
<b>ISS.0150.9030</b>	<b>Unable to assign primary port: "{0}".</b>
<b>Explanation</b>	An attempt to change the primary port failed because the selected port does not meet the primary port criteria mentioned in the wrapped exception.
<b>Action</b>	Select a port that meets the primary port requirements. Alternatively, change the chosen port to meet the primary port requirements mentioned in the wrapped exception.

---

<b>ISS.0150.9037E</b>	<b>Unable to assign quiesce port: "{0}".</b>
<b>Explanation</b>	An attempt to change the quiesce port failed because the selected port does not meet the quiesce port criteria mentioned in the wrapped exception.
<b>Action</b>	Select a port that meets the quiesce port requirements. Alternatively, change the chosen port to meet the quiesce port requirements mentioned in the wrapped exception.
<b>ISS.0150.9999</b>	<b>The webMethods Platform Manager subsystem experienced an unexpected error: {0}</b>
<b>Explanation</b>	An error occurred in the webMethods Platform Manager subsystem that runs in Integration Server.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0151.9001</b>	<b>Missing required parameter: "{0}".</b>
<b>Explanation</b>	A required parameter is missing.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.0153.0089C</b>	<b>Trigger {0} failed decoding: {1}</b>
<b>Explanation</b>	The specified trigger could not decode a received document.
<b>Action</b>	Review the provided exception to determine why decoding failed.
<b>ISS.0153.0401EE</b>	<b>{0} failed to save password for handle {1}. Exception: {2}</b>
<b>Explanation</b>	Integration Server was unable to save the password in the password store. This can occur if there is an issue with either the messaging.cnf file, which contains details about the connection alias, or the password store.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>ISS.0153.0402EE</b>	<b>{0} failed to retrieve password for handle {1}. Exception: {2}</b>
<b>Explanation</b>	Integration Server was unable to retrieve the password from the password store. This can occur if there is an issue with either the messaging.cnf file, which contains details about the connection alias, or the password store.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.

**ISS.0153.0404WW**    **Client authentication type for Universal Messaging connection alias {0} is not valid. Therefore, no authentication will be performed for this connection. Supported types: basic, none.**

**Explanation**        The client authentication type provided for the specified Universal Messaging connection alias is not valid. As a result, Universal Messaging will use the default authentication type (“none”) and no authentication will be performed.

**Action**              Supply a valid authentication type (“none” or “basic”).

**ISS.0155.0003E**    **Unable to perform hot deployment of packages. Hot deployment timeout limit has expired while waiting for in-flight tasks to complete.**

**Explanation**        Hot deployment of packages can happen only if the in-flight tasks are complete within the specified hot deployment timeout period.

**Action**              Increase the hot deployment timeout limit in the Settings > Hot Deployment page of the Integration Server Administrator. Alternatively, ensure that Integration Server is handling less load or requests.

**ISS.0155.0005E**    **Hot deployment of the system package {0} is not supported.**

**Explanation**        You attempted to hot deploy a system package. Hot deployment can be performed only for custom packages.

**Action**              Ensure that the packages that you are attempting to hot deploy are not system packages.

**ISS.0155.0008E**    **Invalid input. Provide a valid positive integer as the hot deployment timeout value.**

**Explanation**        The hot deployment timeout value must be a positive integer.

**Action**              Provide a valid positive integer as the hot deployment timeout value.

**ISS.0155.0010E**    **Cannot cancel the hot deployment operation. The installation of package has already started.**

**Explanation**        You attempted to cancel the hot deployment operation after the installation of the package started. You can cancel the hot deployment operation only before the package installation starts.

**Action**              If you attempted to cancel the hot deployment because of the delay in the completion of in-flight tasks, this message indicates that the in-flight processes are now complete and Integration Server has started the hot deployment operation. No action required.<p>If the hot deployment operation is canceled because the new version of the package has issues, perform hot deployment of the previous version of the package from the salvage directory or perform hot deployment of a newer version of the package after correcting the issues.</p>

---

<b>ISS.0157.0001E</b>	<b>Package "{0}" is not loaded</b>
<b>Explanation</b>	The specified package exists on Integration Server but is not enabled.
<b>Action</b>	Make sure the specified package is enabled. Then, re-execute the pub.assets:getChecksums service. Note that the service gets checksums only for assets that are loaded. If the specified package is partially loaded, the service gets checksums for the loaded assets only.
<b>ISS.0157.0002E</b>	<b>Package "{0}" does not exist</b>
<b>Explanation</b>	The specified package does not exist on Integration Server .
<b>Action</b>	Make sure the specified package exists and is loaded. Then, re-execute the pub.assets:getChecksums service.
<b>ISS.0157.0003E</b>	<b>A value must be specified for either 'packages' or 'assets'</b>
<b>Explanation</b>	A value was not specified for either the packages or assets input parameters. The pub.assets:getChecksums service requires a value for either packages or assets.
<b>Action</b>	Specify a value for the packages input parameter or the assets input parameter. Then, re-execute the pub.assets:getChecksums service.
<b>ISS.134.9215E</b>	<b>Connection Count must be a positive integer, and it must not exceed {0}.</b>
<b>Explanation</b>	The value of the Maximum execution threads property is less than the value of the Connection count property. The Maximum execution threads value must be greater than or equal to the Connection count value.
<b>Action</b>	Change the value of the Maximum execution threads property to be greater than or equal to the Connection count property. Alternatively, change the value of the Connection count property to be less than or equal to the Maximum execution threads property.
<b>ISS.134.9216E</b>	<b>The Multiple Connection feature is not supported when using non-durable Topics.</b>
<b>Explanation</b>	Only JMS triggers that subscribe to queues and/or topics (durable subscribers) can use multiple connections to receive messages from the JMS provider. A JMS trigger that subscribes to a topic that is a non-durable subscriber cannot use multiple connections to receive messages from the JMS provider. That is, only a JMS trigger that subscribes to queues and/or topics that are durable subscribers can have a connection count greater than 1.
<b>Action</b>	Set Connection count to 1. Alternatively, remove any topics that are non-durable subscribers from the list of destinations to which the JMS trigger subscribes.

<b>ISS.141.9102E</b>	<b>No transport info in MessageContext</b>
<b>Explanation</b>	An internal error occurred while processing the Web service request.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.141.9103E</b>	<b>No MessageFormatter in MessageContext</b>
<b>Explanation</b>	An internal error has occurred while processing the Web service request.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.141.9209E</b>	<b>Could not deploy the Web service descriptor {0} as policy with id {1} is not found.</b>
<b>Explanation</b>	Integration Server was unable to execute the Web service connector because the WS-Policy attached to the Web service connector is either missing or invalid. Valid policies should be in the policy repository, that is, saved in the following directory: (webMethods_directory)/IntegrationServer/config/wss
<b>Action</b>	<p>If you want to secure the Web service with the policy, locate the WS-Policy and add it to the policy repository. You can check the policy repository's invalid subdirectory to see whether the policy was moved because it is invalid. If the policy is in the invalid directory, correct it to make it valid, and move it back into the main policy repository directory.</p> <p>If the WS-Policy does not exist, detach the WS-Policy from the Web service descriptor. If you still need to secure the Web service, create a WS-Policy that provides the security you want, add it to the policy repository, and attach it to the Web service descriptor.</p>
<b>ISS.150.9036E</b>	<b>Port Alias cannot be edited.</b>
<b>Explanation</b>	Once a port is created, the port alias cannot be changed.
<b>Action</b>	None. However, if you want an existing port to use a different port alias, you must delete the port and then recreate it using the new port alias.
<b>ISS.153.9302E</b>	<b>Protocol buffer coder cannot find descriptor in document type: {0}</b>
<b>Explanation</b>	An error occurred while encoding or decoding an instance of the specified publishable document type. Integration Server cannot find the message descriptor for the publishable document type. Integration Server creates a message descriptor for a publishable document type with an encoding type set to protocol buffers.
<b>Action</b>	Make sure the publishable document type is synchronized with the messaging provider.

---

<b>ISS.156.10E</b>	<b>Failed to unsubscribe because subscription does not exist for unique key "{0}".</b>
<b>Explanation</b>	Subscription not found for the unique key \"{0}\".
<b>ISS.156.11E</b>	<b>Provided options "{0}" are not valid.</b>
<b>Action</b>	Provide valid options.
<b>ISS.156.13E</b>	<b>Unable to invoke service "{0}" because of the exception: "{1}" .</b>
<b>Explanation</b>	The exception message describes the cause.
<b>Action</b>	Check the exception message and take appropriate action.
<b>ISS.156.14E</b>	<b>An error occurred because the service name is not provided when the isAsync flag is set to true.</b>
<b>Explanation</b>	An error occurs when service name is not provided and the isAsync flag is set to true.
<b>Action</b>	Provide a service name when isAsync flag is set to true.
<b>ISS.156.15E</b>	<b>An error occurred because the user "{0}" is invalid or does not have the ACL permission to execute the service: "{1}".</b>
<b>Explanation</b>	You have entered an invalid username or the user does not have necessary permissions to invoke the callback service.
<b>Action</b>	Enter a valid user name and check if the user has the necessary permissions to invoke the callback service.
<b>ISS.156.16E</b>	<b>An error occurred because the service name is provided and the isAsync flag is set to false.</b>
<b>Explanation</b>	An error occurs when service name is provided and the isAsync flag is set to false.
<b>Action</b>	Do not provide a service name when isAsync is set to false.
<b>ISS.156.6E</b>	<b>Could not unsubscribe the subscription. The exception message is: "{0}".</b>
<b>Explanation</b>	The exception message describes the cause.
<b>Action</b>	Check the exception message and take appropriate action.

<b>ISS.156.7E</b>	<b>Event routing service is unavailable.</b>
<b>Explanation</b>	An error occurred when initializing event routing service.
<b>ISS.156.8E</b>	<b>Invalid Callback Service "{0}". Service should be invocable and should have reference to "{1}" document type as the only input.</b>
<b>Explanation</b>	Callback service cannot be invoked and does not have reference to \"{1}\" document type.
<b>Action</b>	Ensure that the callback service can be invoked and has reference to \"{1}\" document type as the only input.
<b>ISS.156.9E</b>	<b>Subscription failed because subscription already exists for unique key "{0}"</b>
<b>ISS.88.9435E</b>	<b>The specified document type {0} does not exist.</b>
<b>Explanation</b>	The document type that you supplied as input to the service does not exist.
<b>Action</b>	Check the name of the document type that you are attempting to use to ensure you have the correct name. Then, specify a document type name that exists and re-invoke the service.
<b>ISS.88.9436E</b>	<b>The structure of the document instance does not match the specified document type, {0}; validation failed.</b>
<b>Explanation</b>	The service validates a document instance using the IS document type you supplied. However, the document instance does not have the structure specified by the IS document type. Validation of the document instance failed.
<b>Action</b>	Check the IS document type you are attempting to use to ensure you specifying the correct one. Then, re-invoke the service specifying the correct IS document type for the document instance.
<b>ISS.88.9437E</b>	<b>Unexpected exception occurred: {0}</b>
<b>Explanation</b>	The Web services stack, which is Integration Server code that performs Web service functionality, encountered an unexpected error.
<b>Action</b>	Read through the contents of the messages, and take corrective steps. If you are unable to resolve the issue, contact Software AG Global Support.

<b>ISS.88.9438E</b>	<b>Unexpected exception occurred while creating a fault message.</b>
<b>Explanation</b>	Integration Server encountered an unexpected error. It was attempting to add a child fault element to a non-existing parent fault element.
<b>Action</b>	Contact Software AG Global Support.
<b>ISS.88.9439E</b>	<b>The query for the fault element failed because its corresponding parent element is absent from the SOAP message.</b>
<b>Explanation</b>	You attempted to query a SOAP message for SOAPFault elements. However, there is no parent element in the SOAP message for the queried item. For example, Integration Server will issue this error if you attempt to query for a fault code when there is no SOAPFault in the SOAP message.
<b>Action</b>	Ensure the SOAP message that you are attempting to process is valid. If the SOAP message is valid, contact Software AG Global Support.
<b>ISS.88.9440E</b>	<b>The structure of the SOAP fault detail Document is not valid, resulting in the invalid attribute name: {0}; validation failed.</b>
<b>Explanation</b>	A document representing the SOAP fault detail was passed to a service that handles SOAP faults, for example, the pub.soap.handler:addFaultBlock. The fault detail Document that was passed to the service has an invalid structure. An example of an invalid structure would be if the name in the Document instance that corresponds to an attribute is "@ns1:", but there is no local name for the attribute. In this example, there should have been additional text after the ":" that corresponds to a valid local name.
<b>Action</b>	Ensure that IS document instance for the SOAP fault detail is a proper representation of valid XML structure. Correct the SOAP fault detail Document and execute the service again.
<b>ISS.88.9441E</b>	<b>Validation requested, but no IS document type specified; validation failed.</b>
<b>Explanation</b>	You specified that you want an input Document to be validated. However, you have not provided the document type that the service should use for validation. As a result, the validation failed.
<b>Action</b>	Invoke the service again. This time pass the document type to use for validation in the appropriate input parameter.
<b>ISS.88.9442E</b>	<b>Service executed with invalid input parameter {0} : {1}</b>
<b>Explanation</b>	Execution of the service failed because the specified input parameter was passed an invalid value. The invalid value is displayed in the message.
<b>Action</b>	Invoke the service again, this time specifying a valid value for the input parameter.

**IS\_RUNTIME\_EXCEPTION** – runtime exception occurred. see error log for details.

**JBS.0122.0006**      Package "{0}" has deploy directory contents, but does not have a dependency on 'WmJBoss'

**JNDI\_CONTEXT\_NOT\_INITIALIZED** – Cannot perform JNDI operation: JNDI context is not initialized.

**JSONCODER\_INVALID\_DECODE\_FOR\_REAL** – Both `decodeRealAsString` and `decodeRealAsDouble` cannot be set to true.

**JSONCODER\_UNSUPPORTED\_TOKEN** – Invalid state. Unsupported token found in the JSON input stream.

**Explanation**      The input stream does not contain valid JSON content.

**Action**              Provide valid JSON content in the input stream.

**JSON\_INVALID\_INPUTS\_REAL\_AS\_STRING\_AND\_DOUBLE** – Both `decodeRealAsString` and `decodeRealAsDouble` cannot be set to true.

**JSON\_INVALID\_INPUT\_REAL\_AS\_STRING** – Field `decodeRealAsString` if set , can only be true or false.

**JournalLogger.FAC\_SCHED+"."+DATABASE\_VERSION\_CHECK\_FAILED** – Check of internal database failed: the current version {0} should be at least {1}

**LDAP\_URL\_INVALID\_CHAR** – Directory url contain invalid charactors. {0}

**LVLCHNG\_COMP\_CODE\_INVALID** – Supplied "componentCode" is not valid.

**LVLCHNG\_COMP\_CODE\_NULL** – Parameter "componentCode" is required and it cannot be null.

**LVLCHNG\_LISTENER\_NULL** – Parameter "listener" is required and it cannot be null.

**NESTED\_TRANS\_NOT\_SUPPORTED** – another tran active. nested tran disabled in settings

**NODE\_NS\_NAME\_EXISTS** – node\_nsName already exists

**NODE\_NS\_NAME\_IS\_INVALID** – node\_nsName "{0}" is invalid

**NODE\_NS\_NAME\_IS\_REQUIRED** – node\_nsName is required

**NODE\_PKG\_IS\_INVALID** – node\_pkg "{0}" is invalid

**NODE\_PKG\_IS\_REQUIRED** – node\_pkg is required

**NODE\_TYPE\_IS\_INVALID** – Node "{0}" is not of type 'webMethods/WebSocket'

**NOT\_NSWEBSOCKETENDPOINTCLIENT\_TYPE** – Provided NSWebSocketEndpointDescriptor is not of type Client

**NOT\_NSWEBSOCKETENDPOINTDESC\_TYPE** – Provided NSName {0} is not a type of NSWebSocketEndpointDescriptor. Please provide the NSWebSocketEndpointDescriptor NSName

**NO\_LOADERS\_FOUND** Loader is not configured for the cache {1} contained within the cache manager {0}.

**NO\_MORE\_EVENTS\_AVAILABLE** – No more xml events available

**NO\_OUTPUT\_SIGNATURE** – no output signature

**NO\_TRANS\_FOR\_THREAD** – current thread not with any transaction

**NO\_WRITERS\_FOUND** Writer is not configured for the cache {1} contained within the cache manager {0}.

**OAUTH\_ONE\_PREVENTS\_OTHERS** – {0} may not be specified if {1} is "{2}".

**Explanation** The service failed because the specified input variable contains an invalid value combination. The invalid combination is listed in the message text.

**Action** Enter a valid value combination for the input variable.

**ON\_BINARY\_IS\_INVALID** – onBinary "{0}" is invalid

**ON\_CLOSE\_IS\_INVALID** – onClose "{0}" is invalid

**ON\_CONNECT\_IS\_INVALID** – onConnect "{0}" is invalid

**ON\_ERROR\_IS\_INVALID** – onError "{0}" is invalid

**ON\_TEXT\_IS\_INVALID** onText "{0}" is invalid

**OPERATION\_NOT\_SUPPORTED\_WITH\_DES\_ALIAS** – {0} operation is not supported when connection alias type is DES.

**OTHER\_THAN\_SPACE\_CHARACTERS\_ENCOUNTERED** – Other than space characters encountered

**PACKAGE\_HOTDEPLOY\_ACTIVATION\_FAILED\_ON\_RECOVERYE** – Package recovered but not activated.

**Explanation** Hot deployment of the specified package failed. Integration Server recovered the package from the salvage directory, but was unable to activate the package.

**Action** Check the logs for hot deployment failure messages or contact Software AG Global Support.

**PACKAGE\_HOTDEPLOY\_AUTORECOVER\_ERROR** – Package cannot be recovered, check server logs for details.

**Explanation** Hot deployment of the specified package failed.

**Action** Check the logs for hot deployment failure messages or contact Software AG Global Support.

---

**PACKAGE\_HOTDEPLOY\_AUTORECOVER\_FAILEDE – Error during hot deployment of package {0}. Package cannot be recovered.**

<b>Explanation</b>	Hot deployment of the specified package failed. Integration Server attempted to recover the package from the salvage directory but was unable to do so.
<b>Action</b>	Check the logs for hot deployment failure messages or contact Software AG Global Support.

**PACKAGE\_HOTDEPLOY\_AUTORECOVER\_SUCCESSEI – Package recovered and activated.****PACKAGE\_HOTDEPLOY\_IN\_PROGRESSE – Cannot hot deploy package {0}. Hot deployment of package {1} is already in progress.**

<b>Explanation</b>	You attempted to hot deploy multiple packages in parallel. Integration Server does not support parallel hot deployment of packages.
<b>Action</b>	Integration Server does not support parallel hot deployment of packages. Ensure that you perform hot deployment of packages sequentially.

**PACKAGE\_HOTDEPLOY\_TIMEOUTE – Cannot hot deploy package {0} due to error: {1}**

<b>Explanation</b>	Hot deployment of the package failed due to the listed error.
<b>Action</b>	Review the error details provided in the message to determine the cause of the failure and take appropriate action, and then retry hot deploying the packages.

**PARSER\_MUST\_BE\_ON\_START\_ELEMENT\_TO\_READ\_NEXT\_TEXT – parser must be on START\_ELEMENT to read next text****PASSWORDBADOLDPASSWORDE – Invalid user name or password.**

<b>Explanation</b>	The specified user credentials are not valid.
<b>Action</b>	Provide a valid user name and password.

**PASSWORD\_EMPTY Password is empty. User(s) {0} not added.**

<b>Explanation</b>	The Password field requires a value.
<b>Action</b>	Enter a valid password.

**PASSWORD\_UPDT\_EMPTY – Password is empty. Password was not changed.**

**Explanation** The Password field requires a value.  
**Action** Enter a valid password.

**PDT\_OUT\_OF\_SYNC Document type "{0}" is out of sync with Provider**

**PIECMNE0000 Error initializing ISAttributeValues. ISMonitoringContext cannot be null.**  
**Explanation** The ISAttributeValues cannot be initialized because ISMonitoringContext is null.  
**Action** This is an internal error. Contact Software AG Global Support.

**PIECMNE0001 Error retrieving AttributeValue. The metaModelTypeID cannot be null or empty.**  
**Explanation** The AttributeValue cannot be retrieved because metaModelTypeID is null or empty.  
**Action** This is an internal error. Contact Software AG Global Support.

**PIECMNE0002 Error retrieving AttributeValue. The attributeID cannot be null or empty.**  
**Explanation** The AttributeValue cannot be retrieved because metaModelTypeID is null or empty.  
**Action** This is an internal error. Contact Software AG Global Support.

**PIECMNE0003 Error retrieving AttributeValue. The attributeID cannot be null or empty.**  
**Explanation** The AttributeValue cannot be retrieved because attributeID is null or empty.  
**Action** This is an internal error. Contact Software AG Global Support.

**PIECMNE0004 Error retrieving attribute values. The attributeQuery object cannot be null.**  
**Explanation** The attribute values cannot be retrieved because the attributeQuery object is null.  
**Action** This is an internal error. Contact Software AG Global Support.

**PIECMNE0005 Error retrieving attribute values. The modelType is invalid.**  
**Explanation** The attribute values cannot be retrieved because the modelType is invalid.  
**Action** This is an internal error. Contact Software AG Global Support.

---

<b>PIECMNE0006</b>	<b>Error while destroying ISMonitoringContext. The ISMonitoringContext cannot be null.</b>
<b>Explanation</b>	The ISMonitoringContext could not be destroyed because it is null.
<b>Action</b>	This is an internal error. Contact Software AG Global Support.
<b>PIECMNE0007</b>	<b>Error destroying ISMonitoringContext. Invalid ISMonitoringContext provided.</b>
<b>Explanation</b>	The ISMonitoringContext could not be destroyed because it is not a valid instance of ISMonitoringContext.
<b>Action</b>	This is an internal error. Contact Software AG Global Support.
<b>PIECMNE0008</b>	<b>Error getting meta model. The metaModelTypeId cannot be null.</b>
<b>Explanation</b>	The meta model could not be retrieved because the metaModelTypeId is null or empty.
<b>Action</b>	This is an internal error. Contact Software AG Global Support.
<b>PIECMNE0009</b>	<b>Error validating ISMonitoringContext. ISMonitoringContext cannot be null.</b>
<b>Explanation</b>	The ISMonitoringContext could not be validated because it is null.
<b>Action</b>	This is an internal error. Contact Software AG Global Support.
<b>PIECMNE0010</b>	<b>Error validating ISMonitoring Context. Invalid ISMonitoringContext provided.</b>
<b>Explanation</b>	The ISMonitoringContext could not be validated because it is not an instance of MonitoringContext.
<b>Action</b>	This is an internal error. Contact Software AG Global Support.
<b>PIECMNE0011</b>	<b>Error validating ISMonitoringContext. ISInputContext object is null.</b>
<b>Explanation</b>	The ISMonitoringContext cannot be validated because the supplied ISInputContext object is null.
<b>Action</b>	This is an internal error. Contact Software AG Global Support.
<b>PIECMNE0012</b>	<b>Error validating ISMonitoringContext. ISInputContext is invalid.</b>
<b>Explanation</b>	The ISMonitoringContext cannot be validated because the supplied ISInputContext object is invalid.
<b>Action</b>	This is an internal error. Contact Software AG Global Support.

<b>PIECMNE0013</b>	<b>Error validating ISMonitoringContext. Context host attribute cannot be null or empty.</b>
<b>Explanation</b>	The ISMonitoringContext cannot be validated because the context has a host attribute that is null or empty.
<b>Action</b>	This is an internal error. Contact Software AG Global Support.
<b>PIECMNE0014</b>	<b>Error validating ISMonitoringContext. Context port attribute is invalid.</b>
<b>Explanation</b>	The ISMonitoringContext cannot be validated because the context has an invalid port attribute.
<b>Action</b>	This is an internal error. Contact Software AG Global Support.
<b>PIECMNE0015</b>	<b>Error initializing ISModelInstance. ISMonitoringContext is null.</b>
<b>Explanation</b>	An ISModelInstance cannot be initialized because the ISMonitoringContext is null.
<b>Action</b>	This is an internal error. Contact Software AG Global Support.
<b>PIECMNE0016</b>	<b>Error getting model instances. The metaModelTypeName is null or empty.</b>
<b>Explanation</b>	The model instances cannot be retrieved because a metaModelTypeName is null or empty.
<b>Action</b>	This is an internal error. Contact Software AG Global Support.
<b>PIECMNE0017</b>	<b>Error getting model instances. Invalid metaModelTypeName.</b>
<b>Explanation</b>	The model instances cannot be retrieved because a valid metaModelTypeName was not supplied.
<b>Action</b>	This is an internal error. Contact Software AG Global Support.
<b>PIECMNE0018</b>	<b>Error while initializing ISServerModel. ISMonitoringContext is null.</b>
<b>Explanation</b>	The ISServerModel cannot be initialized because ISMonitoringContext is null.
<b>Action</b>	This is an internal error. Contact Software AG Global Support.
<b>PIECMNE0019</b>	<b>Error getting attributes for Integration Server. The modelInstanceListToQuery cannot be null.</b>
<b>Explanation</b>	Integration Server attributes cannot be retrieved because the modelInstanceListToQuery was null .
<b>Action</b>	This is an internal error. Contact Software AG Global Support.

---

<b>PIECMNE0020</b>	<b>Error getting Integration Server attributes. The attributeListToQuery cannot be null.</b>
<b>Explanation</b>	The Integration Server attributes cannot be retrieved because the attributeListToQuery was null.
<b>Action</b>	This is an internal error. Contact Software AG Global Support.
<b>PIECMNE0021</b>	<b>Error getting attributeID. The attributeID cannot be null.</b>
<b>Explanation</b>	The Integration Server attribute cannot be retrieved because the attributeID was null.
<b>Action</b>	This is an internal error. Contact Software AG Global Support.
<b>PIECMNE0022</b>	<b>Error while pinging Integration Server. Invalid ISMonitoringContext.</b>
<b>Explanation</b>	The ping of Integration Server failed because the provided ISMonitoringContext is invalid.
<b>Action</b>	This is an internal error. Contact Software AG Global Support.
<b>PIESIME0000</b>	<b>Unable to access Integration Server:{0}</b>
<b>Explanation</b>	An error occurred while attempting to access Integration Server. The details of the error will replace the {0} in the message text.
<b>Action</b>	Use the details of the error to resolve the error preventing a connection to Integration Server.
<b>PIESIME0001</b>	<b>Integration Server is unavailable:{0}</b>
<b>Explanation</b>	An error occurred while attempting to access Integration Server. The details of the error will replace the {0} in the message text.
<b>Action</b>	Use the provided error information to correct the issue and try again.
<b>PIESIME0002</b>	<b>An error occurred while invoking a service on Integration Server:{0}</b>
<b>Explanation</b>	An error occurred while invoking a service on Integration Server. The details of the error will replace the {0} in the message text.
<b>Action</b>	Use the supplied error information to correct the condition causing the error. Then, reissue the service request.

<b>PIESIME0004</b>	<b>Port object cannot be null.</b>
<b>Explanation</b>	ISContext cannot be created because the Port object is null.
<b>Action</b>	Provide a valid Port object that is not null.
<b>PIESIME0005</b>	<b>UserCredentials username/password cannot be null.</b>
<b>Explanation</b>	ISContext cannot be created because the username/password is null.
<b>Action</b>	Make sure that the username/password has a valid value and is not null.
<b>PIESIME0006</b>	<b>Missing required ClientAuthType for SSL.</b>
<b>Explanation</b>	ISContext cannot be created because the ClientAuthType required for SSL is null.
<b>Action</b>	Make sure the ClientAuthType has a valid value and is not null.
<b>PIESIME0007</b>	<b>Invalid protocol. The webMethods Platform Manager subsystem does not support the protocol "{0}".</b>
<b>Explanation</b>	A create or update operation for port settings specified a protocol that is not supported by the webMethods Platform Manager subsystem in Integration Server.
<b>Action</b>	Specify a protocol supported by the webMethods Platform Manager subsystem in Integration Server.
<b>PIESIME0008</b>	<b>Unable to connect Integration Server:{0}</b>
<b>Explanation</b>	An error occurred while attempting to connect Integration Server. The details of the error will replace the {0} in the message text.
<b>Action</b>	Use the error details to resolve the error that is preventing a connection to Integration Server.
<b>PIESIME0009E</b>	<b>Port Validation Error :{0}</b>
<b>Explanation</b>	The port configuration is not valid.
<b>Action</b>	Make sure the port configuration is valid.
<b>PIESIME0010</b>	<b>Port Validation Error, Invalid URLAccess Service :{0}</b>
<b>Explanation</b>	The port is not valid because the supplied URLAccess does not have a valid service name.
<b>Action</b>	Specify a valid service name for URLAccess.

---

<b>PIESIME0011</b>	<b>Port Validation Error, Invalid IPAccess Hostname :{0}</b>
<b>Explanation</b>	The port is not valid because the IPAccess Hostname is not valid.
<b>Action</b>	Specify a valid value for the IPAccess Hostname.
<b>PIESIME0012</b>	<b>Port Validation Error, Port Alias already exists : {0}</b>
<b>Explanation</b>	The port is not valid because the port alias is used by another port on Integration Server.
<b>Action</b>	Specify a port alias that is unique for the Integration Server.
<b>PIESIME0013</b>	<b>Port Validation Error, Primary port may not be disabled in an update.</b>
<b>Explanation</b>	A primary port cannot be disabled as part of an update.
<b>Action</b>	Do not attempt to disable the primary port as part of updating a port. If you want to disable the port acting as the primary port, you must first designate another port as the primary port. Then you can disable the port that was previously the primary port.
<b>PIESIME0014</b>	<b>Port Validation Error, Primary port package name must be WmRoot. Invalid Package Name : {0}</b>
<b>Explanation</b>	The primary port must be associated with the WmRoot package.
<b>Action</b>	Make sure the primary port is associated with the WmRoot package.
<b>PIESIME0015</b>	<b>Invalid server configuration parameter names: {0}</b>
<b>Explanation</b>	The server configuration parameter names must begin with "watt."
<b>Action</b>	Rename the server configuration parameter names so that they begin with "watt."
<b>PIESIME0016</b>	<b>A required configuration parameter is missing: {0}</b>
<b>Explanation</b>	A required configuration parameter is missing.
<b>Action</b>	Check the logs.
<b>PIESIME0017</b>	<b>Configuration details for COMMON-JDBC cannot be null.</b>
<b>Explanation</b>	While creating a JDBC pool alias, the configuration details for COMMON-JDBC cannot be null.
<b>Action</b>	Provide valid JDBC pool alias configuration details.

<b>PIESIME0018</b>	<b>JDBC pool alias cannot be null or empty.</b>
<b>Explanation</b>	While creating or updating a JDBC pool, the pool alias cannot be null or empty.
<b>Action</b>	Provide a valid value for the JDBC pool alias.
<b>PIESIME0019</b>	<b>Invalid configuration type.</b>
<b>Explanation</b>	The configuration type provided while creating the JDBC pool alias must be of type COMMON-JDBC.
<b>Action</b>	Provide a valid configuration of type COMMON-JDBC.
<b>PIESIME0020</b>	<b>Invalid configuration type.</b>
<b>Explanation</b>	The configuration type provided while updating the JDBC pool alias must be of type COMMON-JDBC.
<b>Action</b>	Provide a valid configuration of type COMMON-JDBC.
<b>PIESIME0021</b>	<b>JDBC pool cannot be null.</b>
<b>Explanation</b>	While creating a JDBC pool alias, the pool configuration details cannot be null.
<b>Action</b>	Provide valid configuration details while creating or updating a JDBC pool.
<b>PIESIME0022</b>	<b>{0} cannot be null or empty.</b>
<b>Explanation</b>	The specified value must not be null or empty
<b>Action</b>	Provide a valid value.
<b>PIESIME0023</b>	<b>Enter a positive number for {0}</b>
<b>Explanation</b>	The specified value must not be a negative number.
<b>Action</b>	Specify a positive number.
<b>PIESIME0024</b>	<b>JDBC configuration instance id is missing.</b>
<b>Explanation</b>	JDBC configuration instance id is required and must be specified.
<b>Action</b>	Provide a valid JDBC configuration instance id.
<b>PIESIME0025</b>	<b>MaxSize must be greater than 0.</b>
<b>Explanation</b>	The value provided for MaxSize must be greater than 0.
<b>Action</b>	Ensure that the value provided for MaxSize is greater than 0.

---

<b>PIESIME0026</b>	<b>Configuration details for COMMON-JDBC cannot be null.</b>
<b>Explanation</b>	While updating a JDBC pool alias, the configuration details for COMMON-JDBC cannot be null.
<b>Action</b>	Provide valid JDBC pool alias configuration details.
<b>PIESIME0027</b>	<b>JDBC pool cannot be null.</b>
<b>Explanation</b>	While updating a JDBC pool alias, the pool configuration details cannot be null.
<b>Action</b>	Provide valid configuration details while creating or updating a JDBC pool.
<b>PIESIME0028</b>	<b>MinSize must be less than or equal to MaxSize.</b>
<b>Explanation</b>	Minimum connections must be less than or equal to maximum connections.
<b>Action</b>	Ensure that the value provided for MinSize is less than or equal to MaxSize.
<b>PIESIME0029</b>	<b>Invalid SMTP port.</b>
<b>Explanation</b>	SMTP port should be greater than 0.
<b>Action</b>	Change the SMTP port to a valid value greater than 0.
<b>PIESIME0030</b>	<b>Unable to retrieve truststores.</b>
<b>Explanation</b>	Integration server is unable to retrieve the truststores.
<b>Action</b>	Ensure that there are truststores installed in Integration server.
<b>PIESIME0031</b>	<b>SMTP settings are already defined.</b>
<b>Explanation</b>	Unable to define new SMTP settings because the SMTP settings are already defined.
<b>Action</b>	To specify new SMTP settings, update the existing SMTP configuration.
<b>PIESIME0032</b>	<b>The truststore {0} does not exist.</b>
<b>Explanation</b>	The specified truststore alias cannot be found.
<b>Action</b>	Ensure that the specified truststore exists in Integration Server.
<b>PIESIME0033</b>	<b>Configuration details for COMMON-DBFUNCTION cannot be null.</b>
<b>Explanation</b>	While updating a functional alias, the configuration details for COMMON-DBFUNCTION cannot be null.
<b>Action</b>	Provide valid functional alias configuration details.

<b>PIESIME0034</b>	<b>Invalid configuration type.</b>
<b>Explanation</b>	The configuration type provided while updating the functional alias must be of type COMMON-DBFUNCTION.
<b>Action</b>	Provide a valid configuration of type COMMON-DBFUNCTION.
<b>PIESIME0035</b>	<b>Functional alias cannot be null</b>
<b>Explanation</b>	While updating a functional alias,the functional alias configuration details cannot be null.
<b>Action</b>	Provide valid configuration details while updating a functional alias.
<b>PIESIME0037</b>	<b>Configuration details for COMMON-JNDI cannot be null.</b>
<b>Explanation</b>	While configuring a JNDI provider alias, the configuration details for COMMON-JNDI cannot be null.
<b>Action</b>	Provide valid JNDI provider alias configuration details.
<b>PIESIME0038</b>	<b>Invalid configuration type.</b>
<b>Explanation</b>	The configuration type provided while configuring a JNDI provider alias must be of type COMMON-JNDI.
<b>Action</b>	Provide a valid configuration of type COMMON-JNDI.
<b>PIESIME0039</b>	<b>SMTP server not configured.</b>
<b>Explanation</b>	SMTP server is not configured in Integration Server.
<b>Action</b>	Configure SMTP server in Integration Server.
<b>PIESIME0040</b>	<b>Functional alias specified is not valid.</b>
<b>Explanation</b>	The functional alias specified in the input must be valid.
<b>Action</b>	Ensure that the functional alias specified in the input is valid.
<b>PIESIME0041</b>	<b>Functional alias description cannot be modified.</b>
<b>Explanation</b>	The functional alias description specified in the input cannot be modified.
<b>Action</b>	Ensure that the functional alias description specified in the input is not modified.

---

<b>PIESIME0042</b>	<b>The functional alias {0} cannot be associated with the embedded database pool.</b>
<b>Explanation</b>	The embedded database pool can only be used with IS Internal and Cross Reference database components.
<b>Action</b>	Associate the functional alias with any JDBC connection pool other than the embedded database pool.
<b>PIESIME0043</b>	<b>Invalid configuration details for COMMON-JMS. Invalid value for {0}.</b>
<b>Explanation</b>	The value specified for COMMON-JMS configuration {0} is not valid.
<b>Action</b>	Specify valid values for all the mandatory attributes in COMMON-JMS configuration.
<b>PIESIME0045</b>	<b>Configuration details for COMMON-JMS cannot be null.</b>
<b>Explanation</b>	The configuration details for COMMON-JMS cannot be null.
<b>Action</b>	Provide valid JMS configuration details.
<b>PIESIME0046</b>	<b>Invalid configuration provided while updating the COMMON-JMS configuration.</b>
<b>Explanation</b>	The JMS alias configuration provided while updating the COMMON-JMS configuration does not match the existing JMS alias configuration.
<b>Action</b>	Provide a valid JMS configuration that matches the JMS configuration to be updated.
<b>PIESIME0047</b>	<b>An error occurred while invoking a service in Integration Server : {0}</b>
<b>Explanation</b>	An error occurred while invoking a service in Integration Server. Error {0} occurred.
<b>Action</b>	Use the supplied error information to correct the condition causing the error. Then, reissue the service request.
<b>PIESIME0048</b>	<b>JMS alias {0} should be disabled before {1} operation.</b>
<b>Explanation</b>	The JMS alias {0} should be disabled before performing the {1} operation.
<b>Action</b>	Ensure that the JMS alias is disabled.
<b>PIESIME0049</b>	<b>Messaging connection alias {0} should be disabled before {1} operation.</b>
<b>Explanation</b>	The messaging connection alias {0} should be disabled before performing the {1} operation.
<b>Action</b>	Ensure that the messaging connection alias is disabled.

<b>PIESIME0050</b>	<b>Messaging connection alias description cannot be null or empty.</b>
<b>Explanation</b>	While creating a messaging connection alias, the description field cannot be null or empty.
<b>Action</b>	Provide a valid description for messaging connection alias.
<b>PIESIME0051</b>	<b>Messaging connection alias name cannot be updated.</b>
<b>Explanation</b>	You attempted to update the messaging connection alias. Messaging connection alias name is not editable.
<b>Action</b>	To change the name of a messaging connection alias, delete the existing messaging connection alias and create a new alias.
<b>PIESIME0052</b>	<b>Default messaging connection alias cannot be deleted.</b>
<b>Explanation</b>	The messaging connection alias that you attempted to delete is the default messaging connection alias, which cannot be deleted.
<b>Action</b>	To delete a default messaging connection alias, configure another messaging connection alias as the default.
<b>PIESIME0053</b>	<b>Cannot create a new messaging connection alias for Broker.</b>
<b>Explanation</b>	Only one messaging connection aliases for Broker can exist at a time in Integration Server.
<b>Action</b>	Delete the existing messaging connection aliases for Broker before creating a new messaging connection aliases for Broker.
<b>PIESIME0057</b>	<b>Logger name for COMMON-LOGGERS configuration type is invalid.</b>
<b>Explanation</b>	Valid values of logger name for COMMON-LOGGERS configuration type are {0}.
<b>Action</b>	Ensure that you specify a valid logger name when updating the COMMON-LOGGERS configuration type.
<b>PIESIME0058</b>	<b>Server logger cannot be disabled.</b>
<b>Explanation</b>	You attempted to disable the server logger. Server logger cannot be disabled.
<b>Action</b>	Ensure that the server logger is enabled.

---

<b>PIESIME0059</b>	<b>Destination for server log entries must be a file.</b>
<b>Explanation</b>	The destination for server log entries can only be a file.
<b>Action</b>	Ensure that you specify a file as the destination for server log entries.
<b>PIESIME0060</b>	<b>Mode for writing server log entries must be synchronous.</b>
<b>Explanation</b>	The server logger writes log entries synchronously to the specified destination file. Therefore, the mode for writing server log entries must be specified as synchronous.
<b>Action</b>	Ensure that the mode for writing server log entries is specified as synchronous.
<b>PIESIME0062</b>	<b>The destination for writing Integration Server log entries must be database or file.</b>
<b>Explanation</b>	Integration Server logger writes log entries to database or file only. You attempted to specify a destination other than database or file.
<b>Action</b>	Ensure that you specify database or file as the destination for writing Integration Server log entries.
<b>PIESIME0063</b>	<b>Configuration details for COMMON-VARS cannot be null.</b>
<b>Explanation</b>	While creating a global variable, the configuration details for COMMON-VARS cannot be null.
<b>Action</b>	Provide valid global variable configuration details.
<b>PIESIME0064</b>	<b>Invalid configuration type.</b>
<b>Explanation</b>	The configuration type provided while creating the global variable must be of type COMMON-VARS.
<b>Action</b>	Provide a valid configuration of type COMMON-VARS.
<b>PIESIME0065</b>	<b>Global variable validation error: Variable Setting cannot be empty.</b>
<b>Explanation</b>	The global variable configuration is not valid.
<b>Action</b>	Make sure that Variable Setting is not empty and that the global variable configuration is valid.
<b>PIESIME0066</b>	<b>Global variable validation error: Integration Server accepts only Strings as global variable values.</b>
<b>Explanation</b>	The global variable value specified is not of type String.
<b>Action</b>	Provide a valid value of type String for the global variable.

<b>PIESIME0067</b>	<b>Global variable validation error: Global variable value cannot be empty.</b>
<b>Explanation</b>	The global variable value must not be empty.
<b>Action</b>	Provide a valid value for the global variable.
<b>PIESIME0068</b>	<b>Global variable validation error: Global variable value cannot exceed 255 characters.</b>
<b>Explanation</b>	The global variable value that you specified contains more than 255 characters.
<b>Action</b>	Ensure that length of the global variable value is less than or equal to 255.
<b>PIESIME0069</b>	<b>Global variable validation error: Global variable key cannot be empty.</b>
<b>Explanation</b>	The global variable key must not be empty.
<b>Action</b>	Provide a valid key for the global variable.
<b>PIESIME0070</b>	<b>Global variable validation error: Global variable key cannot exceed 255 characters.</b>
<b>Explanation</b>	The global variable key that you specified contains more than 255 characters.
<b>Action</b>	Ensure that length of the global variable key is less than or equal to 255.
<b>PIESIME0071</b>	<b>Global variable validation error: Global variable key contains special characters other than "." and "_".</b>
<b>Explanation</b>	The global variable key that you specified contains special characters other than period (.) or underscore(_).
<b>Action</b>	Ensure that the global variable key does not contain any special characters other than period or underscore(_).
<b>PIESIME0072</b>	<b>Invalid value for ServiceLogLevel in Service Logger.</b>
<b>Explanation</b>	The value specified for ServiceLogLevel in Service Logger is not valid. Valid values for ServiceLogLevel are perSvc, brief, and verbose.
<b>Action</b>	Ensure that you specify a valid value for ServiceLogLevel in Service Logger.
<b>PIESIME0073</b>	<b>Invalid value for GenerateAuditingDataOnStartup in Security Logger.</b>
<b>Explanation</b>	The value specified for GenerateAuditingDataOnStartup in Security Logger is not valid. The GenerateAuditingDataOnStartup value must be a valid Boolean value (true/false).
<b>Action</b>	Ensure that you specify a valid value for GenerateAuditingDataOnStartup in Security Logger.

---

<b>PIESIME0074</b>	<b>Invalid value for GenerateAuditingDataOnEvent in Security Logger.</b>
<b>Explanation</b>	The value specified for GenerateAuditingDataOnEvent in Security Logger is not valid. Valid values for GenerateAuditingDataOnEvent are Success or Failure, Success, and Failure.
<b>Action</b>	Ensure that you specify a valid value for GenerateAuditingDataOnEvent in Security Logger.
<b>PIESIME0075</b>	<b>Invalid value for SecurityAreasToAudit in Security Logger.</b>
<b>Explanation</b>	The value specified for SecurityAreasToAudit in Security Logger is not valid. Valid values for SecurityAreasToAudit are {0}.
<b>Action</b>	Ensure that you specify a valid value for SecurityAreasToAudit in Security Logger.
<b>PIESIME0076</b>	<b>Unable to disable messaging connection alias.</b>
<b>Explanation</b>	An operation to disable messaging connection alias failed.
<b>Action</b>	Check the Integration Server logs for more information.
<b>PIESIME0077</b>	<b>Configuration details for COMMON-CLUSTER cannot be null.</b>
<b>Explanation</b>	When updating cluster settings, the configuration details for COMMON-CLUSTER cannot be null.
<b>Action</b>	Provide valid cluster configuration details.
<b>PIESIME0078</b>	<b>Invalid configuration type.</b>
<b>Explanation</b>	When updating the cluster settings, the provided configuration type must be COMMON-CLUSTER.
<b>Action</b>	Specify a configuration type of COMMON-CLUSTER when updating the cluster settings.
<b>PIESIME0079</b>	<b>{0} is required.</b>
<b>Explanation</b>	The required field value cannot be empty.
<b>Action</b>	Specify a value for the required field.
<b>PIESIME0082</b>	<b>Session timeout must be a positive integer.</b>
<b>Explanation</b>	The provided session timeout is not a positive integer.
<b>Action</b>	Specify a positive integer for session timeout.

<b>PIESIME0083E</b>	<b>Configuration details for {0} cannot be null.</b>
<b>Explanation</b>	While creating a {0} web service endpoint alias, the configuration details for {1} cannot be null.
<b>Action</b>	Provide valid web service endpoint alias configuration details.
<b>PIESIME0084</b>	<b>Invalid configuration type.</b>
<b>Explanation</b>	The configuration type provided while creating {0} web service endpoint alias must be of type {1}.
<b>Action</b>	Provide a valid configuration type.
<b>PIESIME0085</b>	<b>{0} Web service endpoint alias is not specified.</b>
<b>Explanation</b>	{0} Web service endpoint alias is not specified.
<b>Action</b>	Specify a valid web service endpoint alias configured in Integration Server.
<b>PIESIME0086</b>	<b>{0} Web service endpoint alias contains invalid characters.</b>
<b>Explanation</b>	{0} Web service endpoint alias contains invalid characters.
<b>Action</b>	Specify a valid web service endpoint alias.
<b>PIESIME0087</b>	<b>Host or port is not specified for {0} web service endpoint alias.</b>
<b>Explanation</b>	Host or port is not specified for {0} web service endpoint alias.
<b>Action</b>	Specify a valid host and port for the web service endpoint alias.
<b>PIESIME0088</b>	<b>Keystore alias or key alias is not valid.</b>
<b>Explanation</b>	Keystore alias or key alias must be a valid alias configured in Integration Server.
<b>Action</b>	Specify a valid configured keystore alias or key alias.
<b>PIESIME0089</b>	<b>Truststore alias is not valid.</b>
<b>Explanation</b>	Truststore alias must be a valid alias configured in Integration Server.
<b>Action</b>	Specify a valid configured truststore alias.
<b>PIESIME0090</b>	<b>{0} cannot be edited.</b>
<b>Explanation</b>	You attempted to edit {0}, which cannot be edited.
<b>Action</b>	Ensure that the specified field is not edited.

---

<b>PIESIME0092</b>	<b>Execute ACL is not valid.</b>
<b>Explanation</b>	The specified Execute ACL does not exist.
<b>Action</b>	Specify a valid ACL.
<b>PIESIME0093</b>	<b>Proxy server alias is not valid.</b>
<b>Explanation</b>	Proxy server alias must be a valid alias configured in Integration Server.
<b>Action</b>	Specify a valid proxy server alias.
<b>PIESIME0094E</b>	<b>The proxy-bypass alias cannot be deleted.</b>
<b>Explanation</b>	The default proxy alias, proxy-bypass, contains the proxy bypass addresses list and cannot be deleted.
<b>Action</b>	You cannot create or delete the proxy-bypass alias.
<b>PIESIME0095E</b>	<b>Invalid protocol specified. Protocol must be HTTP, HTTPS, FTP, or SOCKS.</b>
<b>Explanation</b>	Protocol must be HTTP, HTTPS, FTP, or SOCKS.
<b>Action</b>	Specify HTTP, HTTPS, FTP, or SOCKS as the protocol.
<b>PIESIME0096E</b>	<b>Invalid FTP proxy type. The FTP proxy type must be an integer within the range of 0 and 7 (inclusive).</b>
<b>Explanation</b>	FTP proxy type must be an integer within the range of 0 and 7 (inclusive).
<b>Action</b>	Specify an integer within the range of 0 and 7 (inclusive).
<b>PIESIME0097E</b>	<b>Only the NonProxyHosts field can be edited in the proxy-bypass alias.</b>
<b>Explanation</b>	You attempted to edit the fields other than the NonProxyHosts field in the proxy-bypass alias.
<b>Action</b>	Ensure that you edit only the NonProxyHosts field in the proxy-bypass alias.
<b>PIESIME0098E</b>	<b>License key location cannot be updated.</b>
<b>Explanation</b>	License key location cannot be updated.
<b>Action</b>	License key location cannot be updated.

<b>PIESIME0099E</b>	<b>The proxy server alias element for the existing configuration of type COMMON-PROXY cannot be updated.</b>
<b>Explanation</b>	You attempted to update the alias element for the existing configuration of type COMMON-PROXY.
<b>Action</b>	The proxy server alias element is not editable.
<b>PIESIME0102</b>	<b>File Access Permission configuration instance id cannot be null.</b>
<b>Explanation</b>	File Access Permission configuration instance id is required and must be specified.
<b>Action</b>	Provide a valid File Access Permission configuration instance id.
<b>PIESIME0103</b>	<b>Configuration details for IS-FILEPERMISSION cannot be null.</b>
<b>Explanation</b>	While updating a file permission instance, the configuration details for IS-FILEPERMISSION cannot be null.
<b>Action</b>	Provide valid file permission configuration details.
<b>PIESIME0104</b>	<b>Invalid configuration type.</b>
<b>Explanation</b>	The configuration type provided while updating the file permission configuration must be of type IS-FILEPERMISSION.
<b>Action</b>	Provide a valid configuration of type IS-FILEPERMISSION.
<b>PIESIME0105</b>	<b>Configuration details for IS-FILEPERMISSION cannot be null.</b>
<b>Explanation</b>	While updating the file access control configuration, the configuration details for IS-FILEPERMISSION cannot be null.
<b>Action</b>	Provide valid file access control configuration details.
<b>PIESIME0106</b>	<b>File permission type cannot be modified.</b>
<b>Explanation</b>	While updating file access control configuration, the file permission type cannot be modified.
<b>Action</b>	Provide valid configuration details while updating the file access control configuration.
<b>PIESIME0107</b>	<b>Logger Levels specified for Server Logger cannot be modified.</b>
<b>Explanation</b>	You attempted to add or delete the Logger Levels specified for Server Logger.
<b>Action</b>	You cannot add or delete the Logger Levels specified for Server Logger.

---

<b>PIESIME0108</b>	<b>Logger Level names and descriptions specified for Server Logger cannot be modified.</b>
<b>Explanation</b>	You attempted to modify the Logger Level names or descriptions specified for Server Logger.
<b>Action</b>	You can modify only the Logger Level value for Server Logger.
<b>PIESIME0109E</b>	<b>Specify an {0} proxy server alias.</b>
<b>Explanation</b>	Protocol of the proxy server alias that you specified and the transport type of the consumer web service endpoint alias must match.
<b>Action</b>	Specify an {0} proxy server alias.
<b>PIESIME0110</b>	<b>Value of {0} must be a positive integer between 0 and {1} (inclusive).</b>
<b>Explanation</b>	You specified an invalid value for {0}. Value of {1} must be a positive integer between 0 and {2} (inclusive).
<b>Action</b>	Ensure that you specify a positive integer between 0 and {1} (inclusive) as the value of {0}.
<b>PIESIME0111</b>	<b>Alias of an Integration Server logger cannot be modified.</b>
<b>Explanation</b>	You attempted to modify the alias of an Integration Server logger.
<b>Action</b>	You cannot modify the alias of an Integration Server logger.
<b>PIESIME0112</b>	<b>Invalid timestamp format.</b>
<b>Explanation</b>	The timestamp format must be supported by the Java class <code>java.text.SimpleDateFormat</code> .
<b>Action</b>	Specify any timestamp format that is supported by the Java class <code>java.text.SimpleDateFormat</code> .
<b>PIESIME0113</b>	<b>Alias of a {0} cannot be modified.</b>
<b>Explanation</b>	You attempted to modify the alias of a {0}.
<b>Action</b>	You cannot modify the alias of a {0}.
<b>PIESIME0114E</b>	<b>Remote server endpoint configuration details are not valid for {0}.</b>
<b>Explanation</b>	The value specified for remote server endpoint {0} is missing or is not valid.
<b>Action</b>	Specify valid values for all mandatory remote server endpoint attributes.

<b>PIESIME0115E</b>	<b>Remote server endpoint configuration details cannot be null.</b>
<b>Explanation</b>	Configuration details for a remote server endpoint cannot be null.
<b>Action</b>	Provide valid remote server endpoint details.
<b>PIESIME0116E</b>	<b>Remote server endpoint configuration could not be updated because the configuration details provided are not valid.</b>
<b>Explanation</b>	The remote server endpoint configuration could not be updated because the provided configuration details are not valid.
<b>Action</b>	Specify valid values for all mandatory remote server endpoint attributes.
<b>PIESIME0117E</b>	<b>An error occurred while invoking a service in Integration Server: {0}</b>
<b>Explanation</b>	Integration Server could not execute the service for the reason indicated.
<b>Action</b>	Check the reason detailed in the message, take appropriate corrective action, and reissue the service request.
<b>PIESIME0118E</b>	<b>Connection attempts to the remote server endpoint {0} failed.</b>
<b>Explanation</b>	A connection error occurred while trying to connect to the remote Integration Server from the target server on which the remote server endpoint was created. Either the remote server is not available or the provided host name, port, or authentication credentials are not valid.
<b>Action</b>	Check the status of the remote server and restart the server if necessary. Ensure the configuration of the remote server endpoint is valid.
<b>PIESIME0119E</b>	<b>Invalid SOCKS protocol version.</b>
<b>Explanation</b>	Supported SOCKS protocol versions are 4 and 5.
<b>Action</b>	Specify the SOCKS protocol version as either 4 or 5.
<b>PIESIME0120E</b>	<b>SOCKS protocol version 4 does not support authentication.</b>
<b>Explanation</b>	You specified authentication credentials (i.e. username and password) for SOCKS protocol version 4.
<b>Action</b>	Do not specify authentication credentials (i.e. username and password) for SOCKS protocol version 4.

---

<b>PIESIME0121</b>	<b>Messaging connection alias client prefix cannot be null or empty.</b>
<b>Explanation</b>	While creating a messaging connection alias, the client prefix field cannot be null or empty.
<b>Action</b>	Provide a valid client prefix for messaging connection alias.
<b>PIESIME0122</b>	<b>JAAS Context cannot be null or empty.</b>
<b>Explanation</b>	You did not specify a valid JAAS login context for Kerberos authentication. The JAAS Context field must not be null or empty.
<b>Action</b>	Provide a valid JAAS login context for Kerberos authentication.
<b>PIESIME0123</b>	<b>Service Principal Name Format cannot be null or empty.</b>
<b>Explanation</b>	You did not specify a valid Service Principal Name Format. Service Principal Name Format must not be null or empty.
<b>Action</b>	Provide a valid Service Principal Name Format.
<b>PIESIME0124</b>	<b>Proxy server alias contains invalid characters.</b>
<b>Explanation</b>	The Proxy server alias name can contain only alphanumeric characters.
<b>Action</b>	Specify a proxy server alias name that contains only alphanumeric characters.
<b>PIESIME0125</b>	<b>No LDAP server configuration is available in the target Integration Server or more than one LDAP servers are configured in the target Integration Server.</b>
<b>Explanation</b>	Only one LDAP server must be configured in the target Integration Server.
<b>Action</b>	Add or remove LDAP server configurations to ensure that there is only one LDAP server configured in the target Integration Server.
<b>PIESIME0126</b>	<b>An LDAP server is already configured in the target Integration Server.</b>
<b>Explanation</b>	Only one LDAP server must be configured in the target Integration Server. There is already one or more than one LDAP servers configured in the target Integration Server.
<b>Action</b>	Ensure that there is only one LDAP server configured in the target Integration Server. Retain one LDAP server configuration and delete the rest.

**PIESIME0127      The Maximum Connection Pool Size must be greater than the Minimum Connection Pool Size.**

**Explanation**      The value specified for Maximum Connection Pool Size is lesser than the Minimum Connection Pool Size.

**Action**              Ensure that you provide a Maximum Connection Pool Size greater than the Minimum Connection Pool Size.

**PIESIME0128      LDAP server configuration must contain either a default group or a group member attribute.**

**Explanation**      While configuring the LDAP server, either a default group or a group member attribute must be specified.

**Action**              Ensure that you specify a default group or a group member attribute while configuring the LDAP server.

**PIESIME0129      Invalid LDAP URL! Specify a LDAP URL that starts with ldap:// or ldaps:// and try again.**

**Explanation**      Invalid LDAP URL specified in the Server configuration type for LDAP.

**Action**              Specify a valid URL in the Server configuration type for LDAP.

**PIESIME0130      The Group Id attribute in the Server configuration type for LDAP cannot be null.**

**Explanation**      The Group Id attribute is not provided in the Server configuration type for LDAP.

**Action**              Specify a Group Id attribute in the Server configuration type for LDAP.

**PIESIMW0036      Unable to establish a connection using the specified JNDI provider alias.**

**Explanation**      Integration Server is unable to establish a connection using the specified JNDI provider alias. For possible causes, check the server logs.

**Action**              Ensure that the JNDI provider is running and that the JNDI provider-specific libraries are used in Integration server.

**PIESIMW0044      JMS alias {0} created successfully, but an error occurred while enabling the JMS alias.**

**Explanation**      An error occurred while enabling JMS alias {0}. Check logs of integration server.  
Exception : {1}

**Action**              Check the Integration Server log to handle the exception manually.

**PIESIMW0055**      **IS Resource settings updated successfully. If Broker is not configured, Broker-related settings will be ignored.**

**Explanation**      IS Resource settings updated successfully. If Broker is not configured on Integration Server, all the Broker-related settings that you specified will be ignored.

**Action**              Ensure that Broker is configured if you want the Broker-related settings to be updated.

**PIESIMW0056**      **Unable to read listeners.cnf file from package {0}.**

**Explanation**      Unable to read the listeners.cnf configuration file while attempting to locate the port number for the specified port alias.

**Action**              No action is required. If the issue persists, contact Software AG Global Support.

**PIPELINE\_SAVE\_ACCESSDENIED – Save pipeline to file {0}, Access denied**

**POOL\_NOT\_EXISTI** Pool alias {0} does not exist.

**PREFIX+String.valueOf(NEG\_TIMEOUT\_ERROR) – Pool {0} cannot be initialized. The pool timeouts must not be negative.**

**PROPERTIES\_CAN\_NOT\_BE\_NULL – properties can not be null**

**PROTOBUF\_CODER\_UNSUPPORTED\_DATATYPE – Protocol buffer coder cannot handle data type {0} for field {1} in document type: {2}. Error: {3}**

**PROXY\_INVALID SOCKS\_AUTH – SOCKS protocol version 4 does not support authentication.**

**PROXY\_INVALID SOCKS\_VERSION – Invalid SOCKS protocol version.**

**REMOTE\_NO\_REGISTRY\_TYPE – No Registry type specified**

**RESOURCE\_CAN\_NOT\_BE\_NULL – resource can not be null**

**RESPONSE\_ONE\_OF\_THREE\_REQD – "{0}" or "{1}" or "{2}" must be supplied**

**REVERSE\_GATEWAY\_NO\_LICENSE – Could not find a valid license for Enterprise Gateway.**

**Explanation** The Enterprise Gateway Server instance does not have a valid license for webMethods Enterprise Gateway.

**Action** Check the terms of the license file.

**ROLLBACK\_FAILED\_BAD\_STATE – Rollback failed due to status**

**RUN\_AS\_USER\_IS\_REQUIRED – runAsUser is required**

SCC.0121.0004 enlist failed: {0} xid = {1} rxid = {2}

SCC.0121.0007 delist failed: {0} xid = {1} rxid = {2}

SCC.0121.0010E commit failed: {0} xid = {1} resource = {2}

**Explanation** Integration Server transaction manager was unable to commit a two-phase commit (2PC) transaction to the backend XA resource.

**Action** Check to see if the backend resource is connected to Integration Server. Then, if necessary, re-initiate the transaction.

SCC.0121.0013 prepare failed: {0} xid = {1} rxid = {2} vote = {3}

SCC.0121.0017E rollback failed: {0} xid = {1} resource = {2}

**Explanation** The Integration Server transaction manager was unable to roll back a two-phase commit (2PC) transaction, most likely due to a resource issue.

**Action** Check to see if the backend resource is connected to Integration Server. Then, if necessary, re-initiate the transaction.

SCC.0121.0020 end failed: {0} xid = {1} rxid = {2}

SCC.0121.0026	<b>delisted transaction commit failed: {0} xid = {1}</b>
SCC.0121.0029	<b>one phase commit failed: {0} xid = {1} resource = {2}</b>
SCC.0121.0031	<b>sync beforeCompletion ran: {0} error: {1}</b>
SCC.0121.0033	<b>sync afterCompletion ran: {0} error: {1}</b>
SCC.0121.0034	<b>commit failed: more than 1 local trans enlisted. xid = {1} rxid = {2}</b>
SCC.0121.0035	<b>resource delisted with TMFAIL flag, transaction marked for rollback. xid = {0} rxid = {1}</b>
SCC.0121.0036	<b>transaction timeout. xid = {0}</b>
SCC.0121.0052E	<b>Unable to persist transaction status for xid = {0}: Exception: {1}</b>
<b>Explanation</b>	The transaction recovery manager in Integration Server was unable to write the status of a two-phase commit (2PC) transaction to the disk-based XA recovery store.
<b>Action</b>	Investigate the following possible causes for the problem: <ul style="list-style-type: none"> <li>1) The operating system userid under which the Integration Server is running does not have write privileges to the XAStore directory.</li> <li>2) There is not sufficient disk space for the directory.</li> <li>3) The XA recovery store is corrupt. If this is the case, archive the files stored in the XA recovery store directory, mail them to Software AG Global Support, move the files in the XA recovery store to a backup directory, and restart Integration Server.</li> </ul>
SCC.0121.0055E	<b>Unable to get unrecovered transactions from persistent store. Exception:{0}</b>
<b>Explanation</b>	The transaction recovery manager in Integration Server was unable to obtain a list of incomplete transactions from the XA recovery store. Integration Server uses this store to hold two-phase commit (2PC) transaction states for possible future recovery.
<b>Action</b>	Investigate the following possible causes for the problem: <ul style="list-style-type: none"> <li>1) The operating system userid under which Integration Server is running does not have write privileges to the XAStore directory.</li> <li>2) There is not sufficient disk space for the directory.</li> </ul>

3) The XA recovery store is corrupt. If this is the case, archive the files stored in the XA recovery store directory, mail them to Software AG Global Support, move the files in the XA recovery store to a backup directory, and restart the Integration Server.

**SCC.0121.0056      RecoveryManager found {0} unrecovered Transactions. Starting recovery.**

**SCC.0121.0057      Recovery process started for Transaction Xid:{0}, Status: {1}.**

**SCC.0121.0062E      Unable to rollback Xid:{0} during recovery for resource:{1}, transaction might be heuristically rolled back/committed by resource. Manual intervention might be required. Exception:{2}: Error Code:{3}.**

**Explanation**      The transaction recovery manager in Integration Server detected a transaction whose status in Integration Server is different from the status stored in the back-end resource (for example, a database). This situation occurs when the transaction recovery manager tries to rollback a transaction that the back-end XA resource has already rolled back or committed.

**Action**            Check to see if the back-end resource administrator (for example a database administrator ) manually issued a rollback/commit for the incomplete transaction. If so, ensure that the other back-end XA resources do the same.

**SCC.0121.0067E      Unable to commit Xid:{0} during recovery for resource:{1}, transaction might be heuristically rolled back/committed by resource. Manual intervention might be required. Exception:{2}.**

**Explanation**      The transaction recovery manager of the Integration Server detected a transaction whose status in the Integration Server is different from the status stored in the back-end resource (for example, a database). This situation occurs when the transaction recovery manager tries to commit a transaction that the back-end XA resource has already rolled back or committed.

**Action**            Check to see if the back-end resource administrator (for example a database administrator) manually issued a rollback/commit for the incomplete transaction. If so, ensure that the other back-end XA resources do the same.

**SCC.0121.0070      XARecoveryStore: Error during checkDataDevice. Db:{0} Error:{1}**

**SCC.0121.0071      XARecoveryStore: Resized Data file recovered. Db:{0}**

---

SCC.0121.0072	XARecoveryStore: Error restoring original data file. Db:{0} Error:{1}
SCC.0121.0073	XARecoveryStore: Recoverable Error Skipped - warnonopen = continue. Db:{0} Error:{1}
SCC.0121.0074	XARecoveryStore: Recoverable Error Encountered but warnonopen = fail. Db:{0} Error:{1}
SCC.0121.0075	XARecoveryStore: Damaged data file detected. Db:{0} Error:{1}
SCC.0121.0076	XARecoveryStore: Data file resize required. Db:{0}
SCC.0121.0077	XARecoveryStore: Error cleaning up resized Data file. Db:{0} Error:{1}
SCC.0121.0078	XARecoveryStore: Error creating resized Data file. Db:{0} Error:{1}
SCC.0121.0079	XARecoveryStore: Error closing original Data file. Db:{0} Error:{1}
SCC.0121.0080	XARecoveryStore: Error closing resized data file. Db:{0} Error:{1}
SCC.0121.0081	XARecoveryStore: Error cleaning up copied Data file. Db:{0} Error:{1}
SCC.0121.0082	XARecoveryStore: Error renaming original data file. Db:{0} Error:{1}
SCC.0121.0083	XARecoveryStore: Data file resize completed. Db:{0}
SCC.0121.0084	XARecoveryStore: Error renaming resized data file. Db:{0} Error:{1}
SCC.0121.0086	XARecoveryStore: Error copying resized Data file. Db:{0}

- SCC.0121.0087      XARecoveryStore: Damaged data file renamed. Db:{0} renamed:{1}
- SCC.0121.0088      XARecoveryStore: Error renaming damaged data file. Db:{0} Error:{1}
- SCC.0121.0089      XARecoveryStore: Damaged data file deleted. Db:{0}
- SCC.0121.0090      XARecoveryStore: Error deleting damaged data file. Db:{0} Error:{1}
- SCC.0121.0091      XARecoveryStore: Error re-creating damaged data file. Db:{0} Error:{1}
- SCC.0121.0092      XARecoveryStore: Damaged data file re-created. Db:{0}
- SCC.0121.0094S      **Unrecoverable Exception while initializing the XA Recovery Store: {0}**  
**Explanation**      Integration Server was unable to create a persistent XA recovery store on disk. Integration Server uses this store to hold two-phase commit (2PC) transaction states for possible future recovery.  
**Action**              Investigate the following possible causes for the problem:  
  
                            1) The operating system userid under which the Integration Server is running does not have write privileges to the XA recovery store directory.  
  
                            2) There is not sufficient disk space for the directory.  
  
                            3) The XA recovery store is corrupt. If this is the case, archive the files stored in the XAStore directory, mail them to Software AG Global Support, move the files in the XA recovery store to a backup directory, and restart the Integration Server.
- SCC.0121.0095      XA Recovery Store could not be created.
- SCC.0121.0104      Unable to gain access to resource:{0} Error:{1}. Please verify that the Connection exists and is correctly configured.
- SCC.0121.0106      No transaction record found for Xid:{0} in resource:{1}. Transaction might have been committed or erased on resource:{1}. Unable to resolve as transaction might be in mixed state, requires manual intervention.

---

SCC.0121.0107	<b>Invalid global transaction state for Xid:{0}. Unable to auto-resolve transaction, aborting recovery.</b>
SCC.0121.0108	<b>Transaction Xid:{0} exceeded abandon timeout setting, aborting recovery.</b>
SCC.0121.0112E	<b>Error while shutting down XA Recovery Store:{0}.</b>
<b>Explanation</b>	The Integration Server XA recovery store did not shut down cleanly. Integration Server uses this store to hold two-phase commit (2PC) transaction states for possible future recovery.
<b>Action</b>	Restart Integration Server and examine the Server log for any error messages regarding the XARecovery Store. If the problem is a file permission or out of storage issue, correct the problem and restart the Integration Server. If the problem is not a file permission or out of storage issue, archive the contents of the XAStore directory and contact Software AG Global Support.
SCC.0121.0113E	<b>Recover call on XAResource:{0} failed. Exception:{1}, Error Code:{2}</b>
<b>Explanation</b>	The transaction recovery manager on Integration Server encountered an error when it tried to obtain a list of all incomplete XIDs known to the back-end resource. The error occurred because the back-end resource threw an exception.
<b>Action</b>	Check to see if the back-end resource is available and connected to Integration Server. The name of the resource will be the name of the connection defined in the adapter for the resource.
SCC.0121.0116	<b>Active transaction detected while completing service {0}. Rolling back pending operations.</b>
SCC.0121.0118	<b>Active resource detected while cleaning Top Transaction for service {0}. Rolling back pending operations.</b>
SCC.0121.0120	<b>Active transaction found with the thread after cleanup while completing service {0}. Check the cleanup process.</b>
SCC.0121.0990	<b>XA Transaction Logging: {0}</b>

**SCC.0126.0100**      **An error occurred while attempting to clean up transaction resources on connection {0}**

**SCC.0126.0101**      **An error occurred while attempting to release connection {0}**

**SCC.0126.0102**      **An error occurred while attempting to close connection pool {0}**

**SCC.0126.0103E**      **Assertion error during creation of connection pool {0}**

**Explanation**      An error occurred while allocating the managed connection because either the connection pool does not exist or the connection pool is empty for the managed connection factory.

**Action**      Ensure that the connection pool settings contain valid values. If the values are valid and if Integration Server is still unable create the connection pool, contact Software AG Global Support.

**SCC.0126.0104**      **Assertion error during reset of connection pool {0}**

**SCC.0126.0105E**      **Assertion error during connection request from pool {0}**

**Explanation**      An error occurred while allocating a connection to a request from the connection pool. This can happen if there are no available connections in the pool, if the managed connection factory does not exist, or if the conditions provided by the basic connection pool properties (such as pool size, minimum number of connections or maximum number of connections) are not met.

**Action**      Ensure the connection pool settings are valid. If the connection pool settings are valid and Integration Server is still unable to allocate a connection from the connection pool, contact Software AG Global Support.

**SCC.0126.0106**      **An error occurred while attempting to retrieve a connection from {0}**

**SCC.0126.0107**      **A connection was not available for request in pool {0}**

**SCC.0126.0110**      **Failed to retrieve handle for connection {0}**

SCC.0126.0111	<b>A duplicate connection returned from managed connection factory {0}</b>
SCC.0126.0112	<b>A data level assertion occurred while managing connections for pool {0}</b>
SCC.0126.0113	<b>Pool {0} cannot be initialized. The pool sizes (min, max, increment) must not be negative.</b>
SCC.0126.0115E	<b>Pool {0} cannot be initialized. The minimum pool size must be &lt;= the maximum pool size.</b>
<b>Explanation</b>	An error occurred while initializing the connection pool because the minimum number of connections is greater than the maximum number of connections allowed or the maximum number of connections is set to zero.
<b>Action</b>	Check the adapter connection pool settings to ensure the values for the minimum number of connections and maximum number of connections are valid. If the adapter connection pool settings are valid and the pool is still unable to initialize, contact Software AG Global Support.
SCC.0126.0116E	<b>Pool {0} cannot be initialized. A valid ManagedConnectionFactory was not provided.</b>
<b>Explanation</b>	An error occurred while checking basic properties for a connection pool because the managed connection factory for this pool is null.
<b>Action</b>	Check the connection pool settings to ensure that a valid connection factory is provided. If the settings are valid and the problem still exists, contact Software AG Global Support.
SCC.0126.0117E	<b>An error occurred while attempting to destroy connection {0}</b>
<b>Explanation</b>	An error occurred while closing the database connection from the connection pool.
<b>Action</b>	This is an internal error. Contact Software AG Global Support.
SCC.0126.0118E	<b>Pool state error in {0}. Cannot process request.</b>
<b>Explanation</b>	The next available connection cannot be obtained from the connection pool because the connection pool is disabled.
<b>Action</b>	Check the connection pool settings to ensure that the connection pool is enabled. If the connection pool is enabled and if Integration Server is still unable to obtain the next available connection from the connection pool, contact Software AG Global Support.

**SCC.0126.0119E**     **An error occurred while attempting to create connections for {0}**  
**Explanation**     An error occurred while creating a new connection for the connection pool.  
**Action**            Ensure that the resource database is running and the connection pool settings are valid. If the resource database is running and the connection pool settings are valid, contact Software AG Global Support.

**SCC.0126.0120E**     **{0} Threads are already waiting to get connection. The pool {1} doesn't have a connection available for the request.**  
**Explanation**     This error occurs when a thread holds a connection and stops responding or is in an infinite loop. In either case, the connection pool management capabilities to grant, release, or close connections do not work. Meanwhile, if the pool is flooded with many connection requests, all of the requesting threads are held in a waiting state. Under a heavy load, Integration Server might stop responding. If there are a large number of threads already waiting for a connection, ResourceAllocationException will be thrown to the new threads.  
**Action**            Check the adapter connection pool settings to ensure the values for the minimum number of connections and maximum number of connections are valid. If the adapter connection pool settings are valid and the pool is still unable to initialize, contact Software AG Global Support.

**SESSION\_EXPIRED**   **Session has expired.**

**SS.0088.9424E**     **Error initializing service handler {0}. Error: {1}**  
**Explanation**     An error occurred while initializing the JAX-RPC header handler.  
**Action**            The init() method of JAX-RPC handler threw an error. Correct the error in init() method.

**STATUS\_ACTIVE**    **Transaction is active**

**STATUS\_COMMITTED** **Transaction is committed**

**STATUS\_COMMITTING** **Transaction is committing**

**STATUS\_MARKED\_ROLLBACK** – Transaction is marked for rollback

**STATUS\_NO\_TRANSACTION** – No Transaction

**STATUS\_PREPARED** Transaction is prepared

**STATUS\_PREPARING** Transaction is preparing

**STATUS\_ROLLEDBACK** Transaction is rolled back

**STATUS\_ROLLING\_BACK** – Transaction is rolling back

**STATUS\_TWO\_LOCAL\_TX** – commit failed. more than one local transaction enlisted.

**STATUS\_UNKNOWN** Transaction status is unknown

**STRINGSET\_NOSUCHELEMENT** – StringSetEnumerator

**TEST\_INVALID\_ALIASE** – Associated pool alias for the functional alias {0} does not exist.

**Explanation** Integration Server cannot establish a connection to the pool. A connection pool alias is not associated with the specified functional alias.

**Action** Make sure a connection pool is associated with the functional alias.

**THREAD\_ALREADY\_WITH\_THIS\_TX** – thread already associated with this transaction

**THREAD\_WITH\_ANOTHER\_TX** – thread already associated with another transaction

**TRAN\_NOT\_ACTIVE** transaction is not active

**TRAN\_NOT\_FOR\_THREAD** – transaction is not with current thread

**TRAN\_NOT\_WMIRAN** transaction not a Tran instance

**TRUST\_STORE\_EMPTY** Truststore alias is empty. Specify a Truststore alias for the port or a global truststore alias on the Security > Certificates > Edit page.

**UM\_MIGRATE\_CONNECTION\_ALIAS\_NOT\_FOUND...0** – conectionAlias was not found:{0}.

**UM\_MIGRATE\_CONNECTION\_ALIAS\_NOT\_UM...0** – conectionAlias:{0} MUST be a Universal Messaging Connection Alias.

**UM\_MIGRATE\_NOT\_MIGRATABLE\_FILTER** – Filter cannot be completely migrated to Provider Filter (UM). Contains an unsupported construct:{0} {1} {2}.

**UNABLE\_TO\_INIT\_XASTORE** – Unrecoverable Error while initializing XA Store: {0}

**UNEXPECTED\_END\_OF\_DOCUMENT\_WHEN\_READING\_ELEMENT\_TEXT\_CONTENT** – unexpected end of document when reading element text content

**UNEXPECTED\_EVENT\_TYPE** – Unexpected event type {0}

**UNSUPPORTED\_ACTION\_DELETE\_DEST\_NULL** – Cannot delete durable subscriber {0} for alias {1}. The durable subscriber cannot be accessed. You may need to delete the durable subscriber from the JMS provider manually.

**URI\_IS\_INVALID** URI "{0}" is invalid

**URI\_IS\_NOT\_UNIQUE** URI "{0}" is already being used

**URI\_IS\_REQUIRED** URI is required

**URLALIAS\_ALREADY\_REGISTERED** – The HTTP URL alias could not be registered by the service {0}. "{1}" is already registered as an alias for the path: {2}

**URLALIAS\_ALREADY\_REGISTERED2** – HTTP URL alias "{0}" could not be registered. It is already registered as an alias for the path: {1}

**URLALIAS\_ALREADY\_REGISTERED3** – HTTP URL alias "{0}" could not be registered. It is already registered by package {1} as an alias for the path: {2}

**URL\_IS\_INVALID** URL "{0}" is invalid

**URL\_IS\_NOT\_UNIQUE** URL "{0}" is already being used

**URL\_IS\_REQUIRED** URL is required

**VCS.0132.0051** VCS package shutting down

**VCS.0132.0052** loading configuration file: {0}

**VCS.0132.0054** error loading configuration file: {0}

**VCS.0132.0057** loading users file: {0}

**VCS.0132.0059** error loading users file: {0}

**VCS.0132.0060** saving users file: {0}

VCS.0132.0061	error saving users file: {0}
VCS.0132.0062	retrieving information from VCS server
VCS.0132.0063	no configuration file read for package: {0}; expecting: {1}
VCS.0132.0064	overwriting existing property: {0}; new value: {1}
VCS.0132.0100	file not checked out: {0}
VCS.0132.0101	file checked out: {0}
VCS.0132.0102	file out of date: {0}
VCS.0132.0103	file checked out by another user: {0}
VCS.0132.0150	setting VCS client as {0}
VCS.0132.0151	no current VCS client
VCS.0132.0152	invalid VCS client: {0}
VCS.0132.0153	no VCS client type set
VCS.0132.0202	files to delete: {0}
VCS.0132.0252	Deleted by %value dev_user% on %value is_host% at %value is_time%

---

VCS.0132.0253	<code>%value usercomment%%nl%dev_user : %value dev_user%%nl%is_host : %value is_host%%nl%dev_host: %value dev_host%%nl%is_time : %value is_time%</code>
VCS.0132.0254	delete failed; attempting to revert from opened list
VCS.0132.0302	not locking in build mode (no package specified)
VCS.0132.0303	not locking in delete mode
VCS.0132.0304	running checkout from VCS
VCS.0132.0353	Checked in by %value dev_user% on %value is_host% at %value is_time%
VCS.0132.0354	<code>%value usercomment%%nl%dev_user : %value dev_user%%nl%is_host : %value is_host%%nl%dev_host: %value dev_host%%nl%is_time : %value is_time%</code>
VCS.0132.0355	running checkin to VCS
VCS.0132.0502	not deleting files during preDelete
VCS.0132.0651	No entries to submit
VCS.0132.0700	loading directories: {0}; version: {1}
VCS.0132.0800	Perforce client not found
VCS.0132.0801	Perforce user not found
VCS.0132.0850	For {0}, command: {1}

VCS.0132.0951 Parent does not exist: {0}

VCS.0132.1000 Node not found for version

WEBSOCKET\_NO\_CALLBACK – Values for callback is required

WEBSOCKET\_NO\_VALUE Callback {0} is required

WEBSOCKET\_REQ\_FIELD – " {0} " is a required field.

WEBSOCKET\_REQ\_STR\_OR\_BYTE – message field should be either string or byte object

WEBSOCKET\_RUNASUSR runAsUser is a required field.

WEBSOCKET\_SESSION\_NOTFOUND – Couldn't find the session with sessionID: {0}

WS\_ALIAS\_EXISTING\_MESSAGE\_ADDRESSING – Could not add the Web service endpoint alias because the message addressing endpoint alias {0} for transport type {1} already exists. Provide a different alias name.

**Explanation** The message addressing endpoint alias name you specified already exists for a transport type (HTTP, HTTPS, JMS).

**Action** Specify a message addressing endpoint alias name that does not already exist.

WS\_INVALID\_ASC\_CLIENT\_KEYTAB\_FILE – Client Keytab Filename must be ASCII characters

WS\_INVALID\_ASC\_CLIENT\_PASSWORD – Password for Client Principal must be ASCII characters

WS\_INVALID\_ASC\_CLIENT\_PRINCIPAL – Client Principal name must be ASCII characters

**WS\_INVALID\_ASC\_CLIENT\_PWD\_INPUT\_MODE** – Client Password Input Mode must be ASCII characters

**WS\_INVALID\_ASC\_JAAS\_CONTEXT** – JAAS Context name must be ASCII characters

**WS\_INVALID\_ASC\_SERVICE\_PRINCIPAL** – Service Principal Name must be ASCII characters

**WS\_INVALID\_ASC\_SERVICE\_PRINCIPAL\_FORM** – Service Principal Name Form must be ASCII characters

**WS\_NO\_MSG\_KRB\_JAAS\_CONTEXT** – JAAS Context for WS Security not specified

**WS\_NO\_MSG\_KRB\_SERVICE\_PRINCIPAL** – Service Principal for WS Security not specified

**WS\_NO\_MSG\_KRB\_SERVICE\_PRINCIPAL\_FORM** – Service Principal Name Form for WS Security not specified

**XID\_NOT\_FOUND** Failed attempt to store global status={0} for xid={1}. XID not found.

**XML\_SOURCE\_SHOULD\_BE\_OF\_CORRECT\_TYPE** – xmlSource should be of type 'java.io.InputStream', 'java.io.Reader', 'org.w3c.dom.Node', 'javax.xml.stream.XMLStreamReader' or 'java.lang.String'

**XML\_TARGET\_SHOULD\_BE\_OF\_CORRECT\_TYPE** – xmlTarget should be of type 'java.io.OutputStream', 'java.io.Writer' or 'javax.xml.stream.XMLEventWriter'

**XSL.0002.0014E**      `new Object[][]{{Integer.valueOf(1),Integer.valueOf(2),"JAXP: Error - {0}"},{Integer.valueOf(2),Integer.valueOf(3),"JAXP: Warning - {0}"},{Integer.valueOf(3),Integer.valueOf(5),"JAXP: Properties file is {0}.",{Integer.valueOf(4),Integer.valueOf(5),"JAXP: DocumentBuilderFactory = {0}"},{Integer.valueOf(5),Integer.valueOf(5),"JAXP: SAXParserFactory = {0}"},{Integer.valueOf(6),Integer.valueOf(5),"JAXP: TransformerFactory = {0}"},{Integer.valueOf(7),Integer.valueOf(5),"JAXP: Stylesheet template {0} cached."},{Integer.valueOf(8),Integer.valueOf(5),"JAXP: Stylesheet templates cache cleared."},{Integer.valueOf(9),Integer.valueOf(3),"JAXP: Required argument 'stylesheet' not specified; no value removed from stylesheet cache."},{Integer.valueOf(10),Integer.valueOf(5),"JAXP: Stylesheet template {0} removed from cache."},{Integer.valueOf(11),Integer.valueOf(3),"JAXP: Stylesheet template {0} was not found in cache."},{Integer.valueOf(12),Integer.valueOf(5),"JAXP: Stylesheet {0} was successfully`

**compiled."},{Integer.valueOf(13),Integer.valueOf(5),"JAXP: Compiling TransformerFactory = {0}},{Integer.valueOf(14),Integer.valueOf(2),"JAXP: Error - External entity attack detected. Entity name is {0}"}},}**

**Explanation**

An external entity was detected in the XML that the pub.xslt.Transformations:transformSerialXML service received or in the XSLT stylesheet the service used to transform the XML.

**Action**

Check the XML file or the XSLT stylesheet for external entities. If the external entity is a trusted entity, add the entity to the server parameter watt.core.xml.allowedExternalEntities.

# 18 Mediator Messages

---

<b>0010.0345Debug</b>	<b>AliasesController.updateAliases - Deployment request for runtime alias is null</b>
<b>Explanation</b>	Mediator received an alias deployment request with null values.
<b>Action</b>	Check the deployment request and specify valid information in the request.
<b>0010.0715E</b>	<b>Mediator Upgrade, did not complete successfully.</b>
<b>Explanation</b>	This log message may occur when the Mediator package loads during the Integration Server restart after an overinstall. This message indicates the upgrade was not successful. There should be a previous error message in the server log that indicates the problem.
<b>Action</b>	See actions for message ID '0010.0702'
<b>0010.0753</b>	<b>Successfully migrated Mediator cache configuration file</b>
<b>0010.0786Error</b>	<b>Error initializing runtime aliases. {0}</b>
<b>Explanation</b>	Mediator could not initialize the XML data for the runtime alias.
<b>0010.0811Debug Error</b>	<b>AliasesController.removeAliases - Cannot delete alias. Null values found in the request field(s).</b>
<b>Explanation</b>	Mediator received an alias undeployment request with null values in one or more fields.
<b>Action</b>	Verify the request and resend the request with valid values in the fields.

<b>0010.0814Error</b>	<b>Error retrieving the secure alias: {0}. {1}</b>
<b>Explanation</b>	Error while retrieving the secure string for the alias from the Integration Server password manager.
<b>Action</b>	Check the Integration Server password manager for details on the secure alias string.
<b>0010.0815Error</b>	<b>Error saving the secure alias: {0}. {1}</b>
<b>Explanation</b>	Error while saving the secure string for the alias to the Integration Server password manager.
<b>Action</b>	Check the Integration Server password manager for the secure alias string.
<b>0010.0816Error</b>	<b>Secure alias does not contain a secure string. Secure alias: {0}</b>
<b>Explanation</b>	The secure alias does not have a secure string associated with it.
<b>Action</b>	Enter a valid secure string for the secure alias and try again.
<b>0010.0817Error</b>	<b>Secure alias has invalid secure string encoding. Secure alias: {0}</b>
<b>Explanation</b>	The secure string assigned to the secure alias is not valid.
<b>Action</b>	Check if the secure string is properly encoded.
<b>0010.0852</b>	<b>Mediator could not deploy the service, {0}. {1}</b>
<b>Explanation</b>	An error occurred while parsing the default content type values for the service. Hence, the service could not be deployed.
<b>Action</b>	Check the Integration server logs for more details.
<b>0010.0853</b>	<b>Service failed because of an incorrect value for the default content type. Service: {0}; default content type: {1}</b>
<b>Explanation</b>	The default content type you provided for the service is either not valid or not supported by Mediator.
<b>Action</b>	Check the default content type provided to the service. A list of the content types support by Mediator is available in the product documentation.
<b>0010.0855</b>	<b>Mediator cannot deploy the service because the SOAP action in the REST request received is not suitable.</b>
<b>Explanation</b>	Mediator could not find a suitable SOAP action for the REST request received from the consumer.
<b>Action</b>	Redeploy the service with the correct SOAP action.

---

<b>0010.0868</b>	<b>Mediator is performing start-up tasks, please wait ...</b>
<b>Explanation</b>	User trying to attempt deployment while loading service(s) from cache/disk at start-up.
<b>Action</b>	Please wait to trigger deployment task until complete the Mediator start-up tasks
<b>0030.0092</b>	<b>PublisherPropsObserver - Unknown sender data type ({0})</b>
<b>Explanation</b>	The properties observer received an invalid sender type.
<b>Action</b>	This indicates a coding error. Non-Mediator code should never call this method.
<b>0030.0094</b>	<b>PublisherPropsObserver - Unknown parameters data type ({0})</b>
<b>Explanation</b>	The properties observer received an invalid update object type.
<b>Action</b>	This indicates a coding error. Non-Mediator code should never call this method.
<b>0030.0099</b>	<b>PublisherPropsObserver - Unknown wrapper factory data type ({0})</b>
<b>Explanation</b>	This message has incorrect text. It should indicate an invalid data type for UDDP publisher bean.
<b>Action</b>	Update the pg configuration file to use a proper UDDI publisher data type.
<b>0030.0100</b>	<b>PublisherPropsObserver - Unable to find wrapper factory</b>
<b>Explanation</b>	There is no UDDI publisher configured, but its properties are being changed.
<b>Action</b>	Update the configuration file. Either configure a UDDI publisher or unregister the UDDI properties observer.
<b>0030.0104</b>	<b>Exception encountered initializing logging resource: {0}</b>
<b>Explanation</b>	A problem was encountered while setting up a logger for Mediator to use. There should be an exception message with more details.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0030.0109</b>	<b>PublisherPropsObserver - Can't convert string ({0}) to integer for publishing interval, ignoring input</b>
<b>Explanation</b>	The value received for performance data reporting interval was not a valid numeric string.
<b>Action</b>	Make sure a numeric value is input.

<b>0030.0113</b>	<b>PublisherPropsObserver - Unknown pg service deployer data type {{0}}</b>
<b>Explanation</b>	The data type of the PG Service Deployer bean is invalid.
<b>Action</b>	Update the pg configuration file to use a proper PG Service Deployer data type.
<b>0030.0301</b>	<b>ConsumerApplicationManager.convert - cannot handle null request</b>
<b>Explanation</b>	Unable to create Consumer deployment object for update.
<b>Action</b>	Probably bad SOAP request to Deployer, fix request.
<b>0030.0302</b>	<b>ConsumerApplicationManager.convert - cannot convert consumer with null {0}</b>
<b>Explanation</b>	Invalid Consumer deployment object was found.
<b>Action</b>	Probably bad SOAP request to Deployer, fix request.
<b>0030.0303</b>	<b>VirtualServiceDeployer.{0} - cannot handle null {1}</b>
<b>Explanation</b>	A null reference was found during a deployment activity. The object and activity are identified in the message.
<b>Action</b>	Probably bad SOAP request for deployment, fix request.
<b>0030.0304</b>	<b>VirtualServiceDeployer.deploy - service {{0}} already deployed, undeploying</b>
<b>Action</b>	Info level message, no action required.
<b>0030.0305</b>	<b>VirtualServiceDeployer.undeploy - cannot undeploy service {{0}}, not deployed</b>
<b>Explanation</b>	Attempt to undeploy virtual service failed.
<b>Action</b>	Verify that Mediator and CentraSite agree that the service is no longer deployed. If not, try undeploying this service again, or restarting Mediator/IS.
<b>0030.0306</b>	<b>VirtualServiceDeployer.{0} - caught this: type({1}) message({2})</b>
<b>Explanation</b>	Unable to deploy virtual service. See exception message for more details.
<b>Action</b>	Address the problem indicated by exception and try to deploy again.
<b>0030.0309</b>	<b>ClusteredServiceDeployer{0} - cannot handle null {1}</b>
<b>Explanation</b>	Unable to create VS deployment object for update.
<b>Action</b>	Probably bad SOAP request to Deployer, fix request.

---

<b>0030.0315</b>	<b>ClusteredConsumerManager.updateConsumer - cannot handle null consumer</b>
<b>Explanation</b>	Unable to create Consumer object for update.
<b>Action</b>	Probably bad SOAP request to Deployer, fix request.
<b>0030.0318</b>	<b>ClusteredServiceDeployer - cannot deploy null info to cache</b>
<b>Explanation</b>	A problem occurred while attempting to convert a PGService for deployment to shared cache. There should be another message describing the conversion or deployment issue.
<b>Action</b>	Fix the conversion or deployment problem.
<b>0030.0319</b>	<b>ClusteredServiceDeployer - cannot undeploy null service name from cache</b>
<b>Explanation</b>	Virtual service undeployment requires a non-empty service name. This is problem with undeployment request payload.
<b>Action</b>	Fix the undeployment request payload.
<b>0030.0328</b>	<b>ConsumerApplicationManager.{0} - cannot handle null update request</b>
<b>Explanation</b>	Invalid Consumer deployment request for update.
<b>Action</b>	Probably bad SOAP request to Deployer, fix request.
<b>0030.0330</b>	<b>ConsumerApplicationManager - not updating consumer ({0}), modification date, ({1}), is no more recent</b>
<b>Action</b>	Info level message, no action required.
<b>0030.0333</b>	<b>ConsumerApplicationManager.{0} - caught this: type({1}) message({2})</b>
<b>Explanation</b>	Unable to create and persist Consumer object for update.
<b>Action</b>	Either bad SOAP request to Deployer, fix Request. Or file system problem, check file system permissions. See logged message text for specific error details.
<b>0030.0336</b>	<b>Consumer Application Update Failed; requested update has invalid {0} field</b>
<b>Explanation</b>	Invalid consumer name or key in remove request.
<b>Action</b>	Probably bad SOAP request to Deployer, fix request.

- 0030.0337**            **Consumer Application Remove Failed; consumer ({0}) does not exist**  
**Explanation**        Attempt to remove consumer failed.  
**Action**                Reply to CentraSite Deployment attempt should indicate error. Try redeploying this consumer or resynchronizing all consumers.
- 0030.0343**            **RegisteredConsumerNamesManager.{0} - cannot handle null update request**  
**Explanation**        Invalid RegisteredConsumerNames deployment request for update.  
**Action**                Probably bad SOAP request to Deployer, fix request.
- 0030.0344**            **Registered Consumer Names Update Failed; requested update has invalid {0} field**  
**Explanation**        Invalid service name or consumer names in registered consumer names update request.  
**Action**                Probably bad SOAP request to Deployer, fix request.
- 0030.0346**            **RegisteredConsumerNamesManager - not updating consumer names registered to ({0}), modification date, ({1}), is no more recent**  
**Action**                Info level message, no action required.
- 0030.0347**            **RegisteredConsumerNamesManager.{0} - cannot handle null update request**  
**Explanation**        Invalid RegisteredConsumerNames deployment request for remove.  
**Action**                Probably bad SOAP request to Deployer, fix request.
- 0030.0348**            **Registered Consumer Names Remove Failed; requested update has invalid {0} field**  
**Explanation**        Invalid service consumer name in remove request.  
**Action**                Probably bad SOAP request to Deployer, fix request.
- 0030.0350**            **Registered Consumer Names Remove Failed; service ({0}) has no registered consumers**  
**Explanation**        Invalid request to remove RegisteredConsumerNames, must include at least one consumer name.  
**Action**                Probably bad SOAP request to Deployer, fix request.

---

0030.0352	<b>RegisteredConsumerNamesManager.{0} - caught this: type({1}) message({2})</b>
<b>Explanation</b>	Unable to create and persist RegisteredConsumerNames object for update.
<b>Action</b>	Either bad SOAP request to Deployer, fix Request. Or file system problem, check file system permissions. See logged message text for specific error details.
0030.0356	<b>VirtualServiceDeployer - unable to get endpoints for {0}, caught this: type({1}), msg({2})</b>
<b>Explanation</b>	Unable to obtain endpoint for deployed service.
<b>Action</b>	Probably bad SOAP request to Deployer or bad VSD, fix one or both.
0030.0357	<b>ClusteredRegisteredConsumerNamesDeployer.updateConsumerNames - cannot handle null reg names object</b>
<b>Explanation</b>	Unable to create RegisteredConsumerNames object for update.
<b>Action</b>	Probably bad SOAP request to Deployer, fix request.
0030.0358	<b>Consumer Application Remove Failed; requested update has invalid name and key fields, both are empty</b>
<b>Explanation</b>	Consumer remove request must have either name or key to identify consumer; both were null or empty.
<b>Action</b>	Probably bad SOAP request to Deployer, fix request.
0030.0359	<b>ConsumerApplicationManager - Consumer update request has invalid IP range; from ({0}) to ({1})</b>
<b>Explanation</b>	Consumer update request had invalid IP address range.
<b>Action</b>	Probably bad SOAP request to Deployer, fix request.
0030.0361	<b>VirtualServiceDeployer - redeploying undeployed service ({0}), deployment failed for newer version</b>
<b>Action</b>	Info level message, no action required.
0030.0362	<b>VirtualServiceDeployer - a problem was encountered during deployment, ({0}) will be undeployed and replaced if necessary</b>
<b>Action</b>	Info level message, no action required.

<b>0030.0363</b>	<b>VirtualServiceDeployer.{0} - service({1}) caught this: type({2}) message({3})</b>
<b>Explanation</b>	Message context encountered an exception while attempting to redeploy or undeploy a virtual service. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0030.0364</b>	<b>Deployment request for service: {0}. Registered consumer name element was processed, but the existing modification date is the same as the request. {1}</b>
<b>Action</b>	Info level message, no action required.
<b>0030.0366</b>	<b>UddiPropertiesObserver - Password lookup failed; type ({0}), message ({1})</b>
<b>Explanation</b>	A problem was encountered by attempting to retrieve stored password. There should be an exception with more specific trouble description.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0030.0367</b>	<b>UddiPropertiesObserver - Unable to activate performance data policies; type ({0}), message ({1})</b>
<b>Explanation</b>	The performance data deployer was unable to run. This message should include more details regarding the reason.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0030.0370</b>	<b>Unable to connect to UDDI: ({0}); property updates saved, but data collection is OFF.</b>
<b>Explanation</b>	A problem was encountered during publisher test.
<b>Action</b>	This is probably a bad configuration parameter, fix it.
<b>0030.0371</b>	<b>UddiPropertiesObserver - Unable to convert port string ({0}) to integer, using default port {1}</b>
<b>Explanation</b>	The value input for 'UDDI port' number is non-numeric.
<b>Action</b>	Input an numeric port value.
<b>0030.0396Debug</b>	<b>Exception in AliasesController.{0}. Alias type: {1}, message: {2}</b>
<b>Explanation</b>	Mediator is unable to create and persist an alias during an update.
<b>Action</b>	Verify the access permissions in the file system. See the Mediator error logs for details.

<b>0030.0398Error</b>	<b>Runtime alias update failed. The update request contains an invalid field: {0}</b>
<b>Explanation</b>	The SOAP request sent to the Deployer contains an invalid field.
<b>Action</b>	Resend the request with a valid value for the field.
<b>0030.0399Debug</b>	<b>SimpleAliasDeploymentManager.convert - Cannot deploy simple alias: {0}. Null value in field(s)</b>
<b>Explanation</b>	Mediator found an invalid simple alias during deployment.
<b>Action</b>	Resend the request with a valid value for the field(s).
<b>0030.0410Error</b>	<b>Error undeploying alias. Alias is associated with services. Alias: {0}, services: {1}</b>
<b>Explanation</b>	You are trying to undeploy an alias which is already deployed to a service. If you continue with undeploy, the associated services will not be usable.
<b>Action</b>	Remove the association between the alias and the service that you want to delete, or undeploy the associated services before you undeploy the alias.
<b>0030.0412Debug error</b>	<b>EndpointAliasDeploymentManager.convert - Cannot deploy endpoint alias: {0}. Null value in field(s)</b>
<b>Explanation</b>	Mediator found an invalid endpoint alias during deployment.
<b>Action</b>	Resend the request with a valid value for the field(s)
<b>0030.0419</b>	<b>AliasesDeploymentManager.convert - Cannot deploy alias: {0} of type {1}. Null value in field: {2}</b>
<b>Explanation</b>	Mediator found an invalid alias of type {1} during deployment. Alias Name: {0} Reason - Null value in field: {2}
<b>Action</b>	Resend the request with valid value for the field : {2}
<b>0030.0420</b>	<b>Deployment of webMethods IS Alias {0} failed because no webMethods IS service exists with the given service name {1} in Mediator.</b>
<b>Explanation</b>	Cannot deploy webMethods IS Alias with alias name : {0} and service name : {1}. No webMethods IS Service exists with given service name {1} in Mediator.
<b>Action</b>	Resend the deploy request with valid webMethods IS service name.

<b>0050.0001</b>	<b>Unable to find Policy Element in the VSD:{0}</b>
<b>Explanation</b>	An exception was encountered while attempting to extract a policy element from VSD. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0002</b>	<b>Unable to create Rampart properties:{0}</b>
<b>Explanation</b>	An exception was encountered while attempting to assemble Rampart keystore properties. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0003</b>	<b>Unable to replace static Rampart configuration with configured properties:{0}</b>
<b>Explanation</b>	An exception was encountered while attempting to re-configure Rampart keystore properties. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0004</b>	<b>Unable to create Rampart Configuration Element:{0}</b>
<b>Explanation</b>	An exception was encountered while attempting to convert Rampart configuration string to XML. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0005</b>	<b>Unable to create XPath to select first Policy Alternative:{0}</b>
<b>Explanation</b>	An exception was encountered while attempting to create an Xpath object. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0006</b>	<b>Error while removing existing RampartConfig elements:{0}</b>
<b>Explanation</b>	An exception was encountered while attempting to remove configuration elements. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.

---

<b>0050.0007</b>	<b>Required configuration information to enable WS-Security processing is missing. Unable to process service: {0}. Please ensure Keystore/Truststore information is configured</b>
<b>Explanation</b>	Service could not be initialized due to a problem with keystore/trustore configuration.
<b>Action</b>	Fix the security configuration.
<b>0050.0011</b>	<b>Exception while determining hostname or IP address of the server:{0}</b>
<b>Explanation</b>	An exception was encountered while attempting to resolve a host name or IP address. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0013</b>	<b>Mediator needs the repository location of the SOAP Stack</b>
<b>Explanation</b>	Configuration does not include a valid location for Axis2 repositoryconfiguration.
<b>Action</b>	Fix the axis2 configuration.
<b>0050.0016</b>	<b>ServerManager ready for processing</b>
<b>Action</b>	Info level message, no action required.
<b>0050.0017</b>	<b>Mediator encountered exception while starting ServerManager:{0}</b>
<b>Explanation</b>	An exception was encountered during configuration of Axis2 listeners. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0018</b>	<b>Invalid Port specified. Using default configuration: {0}</b>
<b>Explanation</b>	The 'port' property has a non-numeric string value, the value configured in Axis is used.
<b>Action</b>	Make sure the property value to numeric.
<b>0050.0019</b>	<b>Port {0} is already in use. Trying alternate</b>
<b>Explanation</b>	The port indicated in the message is not available to use with a new socket.
<b>Action</b>	Specify another port value in the system 'port' property or Axis configuration.

<b>0050.0020</b>	<b>Exception while creating "id" selection XPath: {0}</b>
<b>Explanation</b>	Message context encountered an exception while attempting to create an XPath object. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0021</b>	<b>Found Element within Resources element with id: {0}</b>
<b>Action</b>	Info level message, no action required.
<b>0050.0022</b>	<b>Exception while selecting element with id:{0} in Resources Element: {1}</b>
<b>Explanation</b>	Message context encountered an exception while attempting to extract the indicated element from XML. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0023</b>	<b>Mediator received a response for the request with message Id :{0} But a callback is not registered (anymore) to process this response</b>
<b>Explanation</b>	No callback was registered at the time this response was processed.
<b>Action</b>	This is probably a VS configuration problem.
<b>0050.0024</b>	<b>Mediator received a response message without a message Id</b>
<b>Explanation</b>	There was a problem relating the native service response to a virtual service request.
<b>Action</b>	Look for previously logged message indicating that message Id was not used.
<b>0050.0025</b>	<b>Mediator encountered an exception: {0}. No error handlers found - [Message Dropped]</b>
<b>Explanation</b>	This could be a configuration problem. An exception was encountered while attempting to handle a fault. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the configuration, or other problem identified by the exception message.
<b>0050.0029</b>	<b>VSD with incorrect Namespace:{0}. Unable to create PGService.</b>
<b>Explanation</b>	The namespace found in the VSD is unknown.
<b>Action</b>	This is a virtual service configuration problem.

---

<b>0050.0031</b>	<b>The {0} element is required for a Mediator Service</b>
<b>Explanation</b>	Some element used during service deployment was found to be null. The specific element should be identified in the message text.
<b>Action</b>	This is a virtual service configuration problem.
<b>0050.0032</b>	<b>The {0} sequence element is required for a Mediator Service</b>
<b>Explanation</b>	The VSD is missing the sequence element identified in the message.
<b>Action</b>	This is a virtual service configuration problem.
<b>0050.0033</b>	<b>The inSequence for VSD:{0} is invalid.</b>
<b>Explanation</b>	The sequence identified in the message failed validation. Look for recent error message with more validation failure details.
<b>Action</b>	This is a virtual service configuration problem.
<b>0050.0034</b>	<b>The outSequence for VSD:{0} is invalid.</b>
<b>Explanation</b>	The sequence identified in the message failed validation. Look for recent error message with more validation failure details.
<b>Action</b>	This is a virtual service configuration problem.
<b>0050.0035</b>	<b>Exception while parsing Virtual Service String Definition:{0}</b>
<b>Explanation</b>	An exception was encountered while attempting to parse the virtual service description. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0036</b>	<b>Unable to create Virtual Service Definition</b>
<b>Explanation</b>	Unable to create XML object from the VSD string.
<b>Action</b>	This is a virtual service configuration or deployment problem.
<b>0050.0037</b>	<b>PGServiceFactory encountered and exception while creating the PGService: {0}</b>
<b>Explanation</b>	An exception was encountered while attempting to validate input or output sequence or during WSDL URI processing. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.

<b>0050.0038</b>	<b>Invalid parameter specified for PGService: {0}</b>
<b>Explanation</b>	The attribute named in the message has no value in the VSD.
<b>Action</b>	This is a virtual service configuration problem.
<b>0050.0039</b>	<b>Exception {0} for PGService: {1}</b>
<b>Explanation</b>	An exception was encountered while attempting during service creation. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0040</b>	<b>No PGService found with name: {0}</b>
<b>Explanation</b>	Attempting to undeploy or get endpoints for a service that does not exist.
<b>Action</b>	Make sure the virtual service exists before operating on it.
<b>0050.0041</b>	<b>WSStack exception processing service: {0} Cause: {1}</b>
<b>Explanation</b>	An AxisFault was encountered while attempting to either undeploy or get endpoints for the virtual service named in the message. The associated fault message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the fault message.
<b>0050.0042</b>	<b>Unable to locate the WSStack configuration. Can't deploy Virtual Service:{0}</b>
<b>Explanation</b>	The Synapse configuration cannot supply an Axis configuration.
<b>Action</b>	This is an Axis2/Synapse/WS-Stack configuration problem.
<b>0050.0043</b>	<b>A Virtual Service with name:{0} already exists. Unable to deploy.</b>
<b>Explanation</b>	Cannot deploy an Axis service when one already exists with the same name.
<b>Action</b>	Undeploy the existing service before attempting to redeploy or use the same name.
<b>0050.0044</b>	<b>Unable to locate WSStack configuration. Please check if WSStack is enabled/correctly configured.</b>
<b>Explanation</b>	Unable to retrieve the configuration context supplier bean.
<b>Action</b>	This is a Spring bean configuration issue, the pg-config.xml file is missing or corrupted.

---

<b>0050.0045</b>	<b>Invalid parameter passed for Virtual Service creation:{0}</b>
<b>Explanation</b>	An attempt to persist the VSD for a service found a null element. The VSD is not allowed to be null.
<b>Action</b>	This may be the result of invalid deployment payload; fix the VSD.
<b>0050.0046</b>	<b>Unable to persist VSD:{0} to disk. Encountered error:{1}</b>
<b>Explanation</b>	An exception was encountered while attempting to serialize the VSD for the service identified in the message. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0047</b>	<b>Unable to {0} VSD:{1}. Error:{2}</b>
<b>Explanation</b>	This message is used in several different error conditions, as indicated by the object of 'unable to...'.
<b>Action</b>	Fix the 'unable to...' problem for the service identified by 'VSD:'.
<b>0050.0048</b>	<b>Error getting endpoints for service:{0}, Cause: {1}</b>
<b>Explanation</b>	An exception was encountered while attempting to get endpoints. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0049</b>	<b>Exception while creating PGService: {0}, Cause: {1}</b>
<b>Explanation</b>	An AxisFault was encountered while checking if deploying service already exists or while attempting to register service with Axis2. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0050</b>	<b>Error while engaging module: {0}</b>
<b>Explanation</b>	An AxisFault was encountered while attempting to engage the Axis2 module indicated in the message. The associated fault message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the fault message.

<b>0050.0052</b>	<b>Axis was unable to load module {0}</b>
<b>Explanation</b>	An exception was encountered while attempting to load and engage module identified in message. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0053</b>	<b>Loading the WSDL : {0}</b>
<b>Action</b>	Info level message, no action required.
<b>0050.0055</b>	<b>PGService {0} encountered error while converting wsdl element to a StreamSource:{0}</b>
<b>Explanation</b>	An exception was encountered while attempting to read WSDL from manifest. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0057</b>	<b>Unknown WSDL format for PGService:{0}, neither WSDL 1.1 nor WSDL 2.0</b>
<b>Explanation</b>	The current WSDL element has unknown or no namespace associated.
<b>Action</b>	This is a virtual service configuration problem.
<b>0050.0060</b>	<b>Populating SOAP service using WSDL</b>
<b>Action</b>	Info level message, no action required.
<b>0050.0061</b>	<b>Unable to find a WSDL for the PGService:{0}. Assuming a POX or Legacy service</b>
<b>Action</b>	Info level message, no action required.
<b>0050.0062</b>	<b>PGService: {0} is available on transports {1}</b>
<b>Action</b>	Info level message, no action required.
<b>0050.0063</b>	<b>Adding PGService:{0} to the SOAP Stack</b>
<b>Action</b>	Info level message, no action required.
<b>0050.0064</b>	<b>Removing PGService:{0} due to error: axisFault.getMessage()</b>
<b>Action</b>	Info level message, no action required.

---

<b>0050.0065</b>	<b>Exception while setting policy on PGService:{0}</b>
<b>Explanation</b>	An exception was encountered while attempting to engage WS-Policy module. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0066</b>	<b>Setting Policy with id:{0} on Mediator Service:{1}</b>
<b>Action</b>	Info level message, no action required.
<b>0050.0068</b>	<b>Successfully created service in SOAP Stack for PGService:{0} containing {1} endpoint(s).</b>
<b>Action</b>	Info level message, no action required.
<b>0050.0069</b>	<b>Error{1} on setting parameter :{0} on Mediator Service</b>
<b>Explanation</b>	An exception was encountered while attempting to set a parameter into an Axis service. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0070</b>	<b>creating new Mediator Service: {0}</b>
<b>Action</b>	Info level message, no action required.
<b>0050.0071</b>	<b>Unable to find service directory for service {0}</b>
<b>Explanation</b>	Unable to persist WSDL assets because the virtual service directory does not exist.
<b>Action</b>	Redeploying the virtual service should create the service directory.
<b>0050.0074</b>	<b>Error: {0} while reading from file {1}</b>
<b>Explanation</b>	An exception was encountered while attempting to read the proxy file identified in the message. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0076</b>	<b>Scheduled task[{0}] with startup delay of {1} ms and interval of {2} ms</b>
<b>Action</b>	Info level message, no action required.

- 0050.0077**      **Error initializing JMS transport listener. Cause: {0}**  
**Explanation**      An exception was encountered while attempting to register JMS listener. The associated exception message should include more details regarding the problem.  
**Action**              Fix the problem identified by the exception message.
- 0050.0078**      **Unable to stop TransportListener called:{0}. Exception:{1}**  
**Explanation**      An AxisFault was encountered while attempting to stop the JMS transport listener during bean initialization. The associated fault message should include more details regarding the problem.  
**Action**              Fix the problem identified by the fault message.
- 0050.0083**      **Error {0} occurred while updating the load balancer properties**  
**Explanation**      An AxisFault was encountered while attempting to add load balancer URL to an Axis transport description. The associated fault message should include more details regarding the problem.  
**Action**              Fix the problem identified by the fault message.
- 0050.0084**      **Loadbalanced Endpoint: [{0}] failed!**  
**Explanation**      A mediation operation to a load balanced endpoint has failed. The endpoint indicated in the message is not available. This usually indicates a communication problem with the targeted server.  
**Action**              Fix the targeted server.
- 0050.0086**      **Unable to get the IS keystore manager - please check your configuration!**  
**Explanation**      Unable to retrieve the keystore manager bean.  
**Action**              This is a Spring bean configuration issue, the pg-config.xml file is missing or corrupted.
- 0050.0087**      **Keystore initialization failed! Please check the server log for more details**  
**Explanation**      Unable to load the keystore file.  
**Action**              This is a Mediator security configuration problem.
- 0050.0088**      **Truststore initialization failed! Please check the server log for more details**  
**Explanation**      Unable to load the truststore file.  
**Action**              This is a Mediator security configuration problem.

---

<b>0050.0089</b>	<b>Unable to get the Rampart Configuration Handler - please check your configuration!</b>
<b>Explanation</b>	Unable to retrieve the Rampart creation handler bean.
<b>Action</b>	This is a Spring bean configuration issue, the pg-config.xml file is missing or corrupted.
<b>0050.0099</b>	<b>VSD proxy loader, Unable to delete file: {0}</b>
<b>Explanation</b>	The file or directory indicated in the message could not be deleted.
<b>Action</b>	Determine why the file or directory could not be deleted and make it deletable.
<b>0050.0100</b>	<b>VSD proxy loader, Unable to delete directory: {0}</b>
<b>Explanation</b>	The directory indicated in the message could not be deleted.
<b>Action</b>	Determine why the directory could not be deleted and make it deletable.
<b>0050.0101</b>	<b>VSD proxy loader, Unable to create directory: {0}</b>
<b>Explanation</b>	The file or directory indicated in the message could not be created.
<b>Action</b>	Delete the directory so that Mediator can create it again.
<b>0050.0105</b>	<b>Unable to determine fault cause. Please check the log file for more information!</b>
<b>Explanation</b>	This error indicates that Mediator could not determine the cause for the error when trying to extract the soap fault message from the response. Additional errors if any would be present in the IS log file (server.log)
<b>0050.0208</b>	<b>Error resolving WSDL URI. Cause {0}</b>
<b>Explanation</b>	An exception was encountered while attempting to resolve URI elements into XML source. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0209</b>	<b>Error initializing virtual service factory. Cause: {0}</b>
<b>Explanation</b>	An exception was encountered while attempting to initialize XPath elements. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.

<b>0050.0210</b>	<b>Error setting location of virtual service proxies directory. Path: {0} Cause: {1}</b>
<b>Explanation</b>	An exception was encountered while attempting to use the directory identified in the message. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0211</b>	<b>Unable to determine service endpoint URI for this service: {0} No transport listener defined for the virtual service's transport protocol.</b>
<b>Explanation</b>	The configuration context's listener manager cannot find an endpoint for the current service. This may indicate that the hosting IS does not have an appropriate listener registered.
<b>Action</b>	This is a configuration problem, either in IS ports or VSD
<b>0050.0212</b>	<b>Unknown exception deploying virtual service: {0} Cause: {1}</b>
<b>Explanation</b>	An exception was encountered while attempting to get an endpoint reference from the context listener manager. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0214</b>	<b>Error {0} manifest from external resources associated with virtual service: {1}. Cause: {2}</b>
<b>Explanation</b>	An exception was encountered while attempting to read WSDL from manifest. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0215</b>	<b>Error initializing virtual service transformation bean with this xslt: {0} Cause: {1}</b>
<b>Explanation</b>	An exception was encountered while attempting to read the transformation file. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0216</b>	<b>Error transforming raw virtual service string. Cause: {0} virtual service xml: {1}</b>
<b>Explanation</b>	An exception was encountered while attempting to read the Mediator's transformation file. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.

---

0050.0221	<b>Mediator has an internal configuration error. It's deploy-time xslt transformation file path does not exist. Path: {0}</b>
<b>Explanation</b>	An exception was encountered while attempting to read the file identified in the message. The associated exception message should include more details regarding the problem.
<b>Action</b>	This is a configuration problem; make sure the file identified in the message exists and contains the transformation.
0050.0250	<b>Could not find user-specified value for HTTP method! Defaulting to inbound request HTTP method {0}</b>
<b>Explanation</b>	The 'routing method' context variable has an invalid value.
<b>Action</b>	If the value indicated in the message is acceptable, no action is required. Otherwise virtual service configuration must be changed.
0050.0252	<b>Could not set HTTP method for outgoing request for endpoint: {0}</b>
<b>Explanation</b>	The outgoing request's message context is null.
<b>Action</b>	This is a virtual service/policy configuration problem.
0050.0300	<b>Context variable name "{0}" is already declared. Multiple declarations in the same context is not allowed.</b>
<b>Explanation</b>	Context variable names must be unique for a service.
<b>Action</b>	This is a service configuration problem.
0050.0303	<b>Attempt to reference context variable without providing a message context. Custom context variables may only be declared with a 'session' scope at this time. Other scopes are not supported.</b>
<b>Explanation</b>	Attempting to get context variable or context variable map, but the message context (or session) is null.
<b>Action</b>	Earlier error messages should provide clues to help determine why a valid message context is null.
0050.0306	<b>Context variable name is required for variable declaration.</b>
<b>Explanation</b>	Variable name validation failed, QName is null or is missing a local part.
<b>Action</b>	This is a context variable configuration problem.

<b>0050.0307</b>	<b>Namespace URI and prefix is required for custom variable declaration. varName: {0}</b>
<b>Explanation</b>	Variable name validation failed, Namespace URI and prefix must both be neither null nor empty.
<b>Action</b>	This is a context variable configuration problem.
<b>0050.0308</b>	<b>Context variable name must be a valid identifier ( alpha-numeric, \$, or _ permitted ) Found: {0}</b>
<b>Explanation</b>	Variable name validation failed, name has invalid characters.
<b>Action</b>	This is a context variable configuration problem.
<b>0050.0309</b>	<b>Core Context variables cannot have a namespace or prefix as part of its declaration. varName: {0}</b>
<b>Explanation</b>	Variable name validation failed, prefix for core variables must be empty.
<b>Action</b>	This is a context variable configuration problem.
<b>0050.0310</b>	<b>Either a Message context or axis service name is required when creating a custom context variable. varName: {0}</b>
<b>Explanation</b>	Both service name and Axis2 message context are null, this is not acceptable. This is probably the result of attempting to deploy a service with no service name.
<b>Action</b>	Verify that service configuration is correct.
<b>0050.0311</b>	<b>Attempt to create a custom variable using a message context with no AxisService. varName: {0}</b>
<b>Explanation</b>	The axis2 message context is corrupted, it should identify a service.
<b>Action</b>	Earlier error messages should provide clues to help determine why a valid message context could not be created.
<b>0050.0312</b>	<b>Unexpected error creating custom Mediator context variable. varName: {0} reason: {1}</b>
<b>Explanation</b>	An exception was encountered while attempting to create a custom context variable. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.

---

<b>0050.0313</b>	<b>Unexpected error removing custom Mediator context variable for service: {0} reason: {1}</b>
<b>Explanation</b>	An exception was encountered while attempting to remove or inject a custom context variable. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0314</b>	<b>Unexpected error initializing core Mediator context variables. reason: {0}</b>
<b>Explanation</b>	An exception was encountered while attempting to create a context variable. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0316</b>	<b>Unexpected error getting Mediator context variable value. varName: {0} reason: {1}</b>
<b>Explanation</b>	An exception was encountered while attempting to get the value of the context variable named in the message. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0317</b>	<b>Unexpected error setting Mediator context variable value. varName: {0}, value:{1}, reason: {2}</b>
<b>Explanation</b>	An exception was encountered while attempting to set the context variable value named in the message. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0318</b>	<b>Expected a virtual service name for this method operation, but none was provided.</b>
<b>Explanation</b>	Attempting to get context variable map for a null service name.
<b>Action</b>	Earlier error messages should provide clues to help determine why a valid service name is null.
<b>0050.0321</b>	<b>Mediator context variable adapter unable to locate this type: {0}</b>
<b>Explanation</b>	The context variable type indicated in the message is unknown.
<b>Action</b>	This is a context variable configuration problem.

**0050.0322**      **Unexpected error getting core Mediator context variable value from adapter. type: {0}**

**Explanation**      An exception was encountered while attempting to get the context variable value named in the message. The associated exception message should include more details regarding the problem.

**Action**      Fix the problem identified by the exception message.

**0050.0323**      **Only string and int schema types are supported at this time. Type: {0}, declared with "{1}" context variable is not supported.**

**Explanation**      The context variable schema type is not among the accepted types.

**Action**      This is a service configuration problem.

**0050.0324**      **Context variable name declarations cannot contain \$ sign symbols in the name since that is used as a reference operator. varName: {0}**

**Explanation**      Variable name validation failed, name must include substitution character, (dollar sign).

**Action**      This is a context variable configuration problem.

**0050.0325**      **Unable to return list of context variables declared for this service: {0} Reason: {1}**

**Explanation**      An AxisFault was encountered while attempting to retrieve a list of context variable names. The associated fault message should include more details regarding the problem.

**Action**      Fix the problem identified by the fault message.

**0050.0326**      **Unable to return list of context variables declared for this message context: {0} Reason: {1}**

**Explanation**      An AxisFault was encountered while attempting to get a list of context variables or list of variable keys. The associated fault message should include more details regarding the problem.

**Action**      Fix the problem identified by the fault message.

**0050.0327**      **Context variable name deployed with virtual service {0} references an unknown namespace prefix. name attribute: {1}**

**Explanation**      Context variable identified in message has invalid namespace.

**Action**      This is a context variable configuration problem.

---

<b>0050.0328</b>	<b>Exception while copying context variables from request to response message context. Reason: {0}</b>
<b>Explanation</b>	An AxisFault was encountered while attempting to copy context variable names between contexts. The associated fault message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the fault message.
<b>0050.0329</b>	<b>Could not create backup directory for failed services! Dir tried = {0}</b>
<b>Explanation</b>	An attempt to create the 'failed services' directory has failed.
<b>Action</b>	Determine why the directory could not be created. Either fix the creation problem or specify a different directory.
<b>0050.0331</b>	<b>Error occurred when getting backup directory for path {0}</b>
<b>Explanation</b>	An exception was encountered while attempting to determine directory for backing up failed services. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0333</b>	<b>Error occurred while resolving URI; message = {0}</b>
<b>Explanation</b>	An exception was encountered during URI resolution. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0337</b>	<b>Previously selected {0} port {1} is no longer enabled or available!</b>
<b>Explanation</b>	The message indicates port number and type. The requested port is not available.
<b>Action</b>	Select a new port number for the indicated port type.
<b>0050.0343</b>	<b>Context variable API expected an IData object for ctx variable, {0}, but received this: {1}</b>
<b>Explanation</b>	The data element from which a context variable is to be extracted has an unknown data type.
<b>Action</b>	This is probably a flow configuration problem; where the pipeline was populated with an invalid value.

<b>0050.0344</b>	<b>Attempt to insert {0} core ctx variable with invalid value type: {1}. Expected a collection of this type: {2}</b>
<b>Explanation</b>	.The allowable data type for a core context variable is restricted, depending on variable type.
<b>Action</b>	.This is a context variable configuration problem.
<b>0050.0345</b>	<b>Unable to access array element [{0}] in SOAP_HEADERS core ctx variable. Cause: {1}</b>
<b>Explanation</b>	The index value indicated in the message must be numeric.
<b>Action</b>	This is a context variable configuration problem.
<b>0050.0346</b>	<b>Invalid array or key reference for core ctx variable. This substitution string has mismatched braces: {0}</b>
<b>Explanation</b>	The context variable substitution string is invalid, mismatched brace characters were found.
<b>Action</b>	This is a context variable configuration problem.
<b>0050.0347</b>	<b>Attempt to create an IData value for a ctx variable from an unsupported class type. CtxVar: {0} Bad type: {1}</b>
<b>Explanation</b>	The context variable to be converted to IData has an unknown data type.
<b>Action</b>	This is a context variable configuration problem.
<b>0050.0348</b>	<b>Unable to append header block to the end of the soap header. Cause: {0}, soapHeader element: {1}</b>
<b>Explanation</b>	An exception was encountered while attempting to add append new SOAP header block. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0349</b>	<b>Unable to prepend header block to the beginning of the soap header. Cause: {0}, soapHeader element: {1}</b>
<b>Explanation</b>	An exception was encountered while attempting to add prepend new SOAP header block. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.

---

<b>0050.0350</b>	<b>Unable to remove header block from the soap header. Cause: {0}, soapHeader: {1}</b>
<b>Explanation</b>	An exception was encountered while attempting to remove a SOAP header block. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0351</b>	<b>Unable to set header block at position {0} of the soap header. Cause: {1}, soapHeader element: {2}</b>
<b>Explanation</b>	An exception was encountered while attempting to replace a SOAP header block with a new one. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0355</b>	<b>Could not create STS configuration directory! Dir tried = {0}</b>
<b>Explanation</b>	The file or directory indicated in the message could not be created.
<b>Action</b>	Delete the directory so that Mediator can create it next time it is required.
<b>0050.0357</b>	<b>Error occurred when getting STS configurations directory for path {0}</b>
<b>Explanation</b>	An exception was encountered while attempting to create the directory indicated in the message. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0362</b>	<b>Error occurred when creating STS client</b>
<b>Explanation</b>	An exception was encountered while attempting to create an STS client object. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0364</b>	<b>Error occurred when initializing default STS configuration store</b>
<b>Explanation</b>	An exception was encountered while attempting to create JAXB marshaller/unmarshaller pair. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.

<b>0050.0365</b>	<b>Could not find STS configuration file with path {0}</b>
<b>Explanation</b>	An attempt to delete the file indicated in the message failed because the file does not exist.
<b>Action</b>	Check this directory [IS_INSTALL_DIR\packages\WmMediator\config\resources\security\sts] to make sure there is an xml file with the STS config name being deleted. For e.g. if the STS config being deleted is MySTS, then there should be an XML file called MySTS.xml in the mentioned directory
<b>0050.0366</b>	<b>Could not delete STS configuration file with path {0}</b>
<b>Explanation</b>	An attempt to delete the file indicated in the message returned 'false'. The file was not deleted.
<b>Action</b>	Make sure the STS config file present under [IS_INSTALL_DIR\packages\WmMediator\config\resources\security\sts] is present and not locked by any other application (e.g. opened in an editor like Windows Notepad). Check the log file to see if there is any java IOException related to disk errors.
<b>0050.0367</b>	<b>Error occurred when saving STS configuration to disk</b>
<b>Explanation</b>	An exception was encountered while attempting to marshal configuration object into file. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0368</b>	<b>Error occurred when reading STS configuration from file {0}</b>
<b>Explanation</b>	An exception was encountered while attempting to unmarshal configuration file indicated in the message into JAXB object. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0371</b>	<b>Error getting IS keystore manager instance!</b>
<b>Explanation</b>	An exception was encountered while attempting to get a reference to the keystore manager. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.

---

<b>0050.0373</b>	<b>Error occurred when adding rampart configuration to STS policy</b>
<b>Explanation</b>	An exception was encountered while attempting to configure the STS policy. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0379</b>	<b>Error occurred when adding assertion to STS policy</b>
<b>Explanation</b>	An exception was encountered while attempting to add an assertion to a WS-Policy artifact. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0382</b>	<b>Error occurred when adding OnBehalfOf element to WS-Trust request element</b>
<b>Explanation</b>	An exception was encountered while attempting to add the WS-Trust element to a request. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0383</b>	<b>Error occurred when sending WS-Trust request to STS to obtain SAML assertion</b>
<b>Explanation</b>	An exception was encountered while attempting to add SAML assertion to pipeline. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0384</b>	<b>Could not find required property {0} for SAML sender-vouches action!</b>
<b>Explanation</b>	The pub.mediator.security.ws.AddSamlSenderVouchesToken ESB service is missing the required 'ConfigName' input value
<b>Action</b>	Make sure that the 'ConfigName' service input has a valid STS config name (must match one of the configured STS names)
<b>0050.0386</b>	<b>Could not find any STS client configuration with name {0}. Check to see if such an STS configuration exists!</b>
<b>Explanation</b>	This error occurs if the configured ESB service that calls the pub.mediator.security.ws.AddSamlSenderVouchesToken specifies the STS config name incorrectly.
<b>Action</b>	Check if the specified STS config name matches one of the configured STSs in Mediator. The "ConfigName" service input value should be the same name (case-sensitive) as the STS name specified in Mediator Admin configuration page

<b>0050.0388</b>	<b>Could not get SAML assertion from STS!</b>
<b>Explanation</b>	A null assertion element was found in the STS client.
<b>Action</b>	Mediator sent a request to the configured STS to obtain a SAML assertion, but no valid assertion was obtained by the client. Please check the log file for any errors related to sending the WS-Trust request to the STS to obtain the token.
<b>0050.0389</b>	<b>Adding OnBehalfOf element in WS-Trust request for IS user {0}</b>
<b>Action</b>	Info level message, no action required.
<b>0050.0390</b>	<b>Could not find base STS policy file: {0} !</b>
<b>Explanation</b>	An exception was encountered while attempting to load a WS-Policy artifact from the file indicated in the message. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0391</b>	<b>Error occurred when getting STS configurations! Check to see if the ISTSClientConfigManager bean is configured!</b>
<b>Explanation</b>	The STS configuration manager bean could not be found.
<b>Action</b>	This is a Spring bean configuration issue, the pg-config.xml file is missing or corrupted.
<b>0050.0392</b>	<b>Could not find any STS configuration with the name {0}</b>
<b>Explanation</b>	The STS client configuration identified in the message to be loaded or deleted could not be found.
<b>Action</b>	Verify that the STS configuration being loaded or deleted has an equivalent configuration file present under [IS_INSTALL_DIR\packages\WmMediator\config\resources\security\sts] directory. E.g. if the configuration being deleted is called MySTS, then there should be a file with name MySTS.xml in the mentioned directory
<b>0050.0394</b>	<b>Error occurred when getting key aliases for keystore {0}: Error: {1}</b>
<b>Explanation</b>	An exception was encountered while attempting to add a list of certificate aliases to the pipeline. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.

---

<b>0050.0395</b>	<b>Error occurred when getting keystore handles {0}</b>
<b>Explanation</b>	An exception was encountered while attempting to add a list of keystore handles to the pipeline. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0396</b>	<b>Error when signing SAML assertion and SOAP request body</b>
<b>Explanation</b>	An exception was encountered while attempting to sign a SAML assertion and request body. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0397</b>	<b>Error occurred when adding ws-addressing headers to outbound soap request; Error: {0}</b>
<b>Explanation</b>	An exception was encountered while attempting to add WS-Addressing headers. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0400</b>	<b>Using default timestamp value of 300s, because input TTL {0} is invalid (-ve or too big)</b>
<b>Explanation</b>	The input value was not valid, a default was used.
<b>Action</b>	If the default is acceptable, no action is required. Otherwise update the configuration.
<b>0050.0507</b>	<b>ScaDeploymentPayload.extractParts found no virtual service requests</b>
<b>Action</b>	Info level message, no action required.
<b>0050.0508</b>	<b>Unexpected exception, attempting to {0}, caught: type({1}), msg({2})</b>
<b>Explanation</b>	An exception was encountered while attempting to process a deployment request. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0509</b>	<b>ScaDeploymentPayload.extractParts - Unable to find consumer file {0}, for component {1}</b>
<b>Explanation</b>	The SCA deployment package was expected to contain a file to define the consumer identified in the message. The file was not found.
<b>Action</b>	This is a deployment payload construction problem.

<b>0050.0510</b>	<b>Unexpected exception, attempting to process {0} request, caught: type({1}), msg({2})</b>
<b>Explanation</b>	An exception was encountered while attempting to process a deployment request. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0515</b>	<b>ScaCompositeConfiguration found component with implementation type ({0})</b>
<b>Action</b>	Info level message, no action required.
<b>0050.0516</b>	<b>{0} - unable to convert string ({1}) to XMLGregorianCalendar: exception message ({2})</b>
<b>Explanation</b>	The date element from the deployment payload has an unexpected format.
<b>Action</b>	This is problem with the contents of the deployment payload.
<b>0050.0517</b>	<b>DeploymentPayload.{0} - input pipeline does not contain expected key ({1})</b>
<b>Explanation</b>	The deployment payload must include an element with the key indicated in the message.
<b>Action</b>	This is problem with the contents of the deployment payload.
<b>0050.0519</b>	<b>ScaDeploymentPayload - unable to delete temporary zip file: ({0})</b>
<b>Explanation</b>	The file indicated in the message could not be deleted.
<b>Action</b>	Determine why the file could not be deleted and make it deletable.
<b>0050.0520</b>	<b>DeploymentPayload - invalid request type: {0}</b>
<b>Explanation</b>	The deployment payload type is unknown.
<b>Action</b>	This is a deployment payload construction problem.
<b>0050.0528</b>	<b>DeploymentPayload - found null/empty virtual service descriptor for service {0}</b>
<b>Explanation</b>	The deployment payload must contain a VSD. The VSD for the service identified in the message was not found.
<b>Action</b>	This is a deployment payload construction problem.
<b>0050.0603</b>	<b>Error occurred when adding UsernameToken to SOAP Envelope: {0}</b>
<b>Explanation</b>	An exception was encountered while attempting to add username token to the pipeline. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.

---

<b>0050.0605</b>	<b>Error occurred when adding X.509 token to SOAP Envelope: {0}</b>
<b>Explanation</b>	An exception was encountered while attempting to add X509 token to the pipeline. The associated exception message should include more details regarding the problem.
<b>Action</b>	Fix the problem identified by the exception message.
<b>0050.0630Debug</b>	<b>DeploymentPayload - No update requests for the runtime aliases being deployed</b>
<b>Explanation</b>	Mediator did not receive any update requests for the runtime aliases being deployed.
<b>Action</b>	Check the update request for runtime aliases.
<b>0050.0632Error</b>	<b>Mediator does not support the runtime alias. Alias type: {0}</b>
<b>Explanation</b>	Mediator was not able to find a runtime alias of the specified type.
<b>Action</b>	Check the alias type assigned to the runtime alias.
<b>0050.0670Error</b>	<b>Resources for the endpoint URI not found. Endpoint URI: {0}</b>
<b>Explanation</b>	Mediator does not have REST resources configured with the specified URI.
<b>Action</b>	Check the configuration of the virtual REST service to ensure that the required resources are configured.
<b>0050.0677</b>	<b>Error while processing the REST to SOAP transformation in Mediator. The JSON string in the request is empty.</b>
<b>Explanation</b>	Mediator expects a non-empty JSON string in the request message.
<b>Action</b>	Check if the JSON request string is valid, and try again. Contact your system administrator for details if the issue persists.
<b>0050.0678</b>	<b>Mediator could not complete the transformation of a REST request received from the consumer to a SOAP request because of an error. JSON string:{0}. {1}</b>
<b>Explanation</b>	Mediator encountered an error while converting the JSON request to a SOAP request as part of the conversion of the REST request to a SOAP request.
<b>Action</b>	Check if the JSON request string is valid and try again. Contact your system administrator for details if the issue persists.
<b>0050.0679</b>	<b>Mediator could not complete the transformation of a REST request received from the consumer to a SOAP request because of an error. {0}</b>
<b>Explanation</b>	Mediator encountered an error while converting the multi-part REST request to SOAP request as part of the conversion of the REST request to SOAP request.
<b>Action</b>	Check if the attachments in the multi-part request are valid.

<b>0050.0680</b>	<b>Mediator could not complete the transformation of a REST request received from the consumer to a SOAP request because of an error. JSON string: {0}. {1}</b>
<b>Explanation</b>	Mediator encountered an error while converting the JSON string sent as an attachment to a SOAP request as part of the conversion of the REST request to a SOAP request.
<b>Action</b>	Check if the JSON string in the attachment to the SOAP request is valid.
<b>0050.0681</b>	<b>Mediator could not complete the transformation of a REST request received from the consumer to a SOAP request because of an error. {0}</b>
<b>Explanation</b>	Mediator encountered an error while parsing the schema in WSDL file, which leads to namespaces not being placed properly in the SOAP request when the REST to SOAP transformations are processed.
<b>Action</b>	Check the schema of the WSDL file provided in the native SOAP service.
<b>0070.0081</b>	<b>{{0}} Removing the Content-Encoding header in response as the Accept-encoding is null</b>
<b>0070.0094</b>	<b>{{0}} --&gt; Incoming Request Header does not contain a valid OAuth token.</b>
<b>Explanation</b>	User has configured OAuth authentication scheme but OAuth token is not present in the request.
<b>Action</b>	Ensure that the request has an authorization header with OAuth token in it.
<b>0070.0172</b>	<b>Found duplicate target namespace {{0}}, enabling namespace-growth for schema validation</b>
<b>Explanation</b>	This flag will be auto enabled when duplicate target namespaces found in the schema definition otherwise it will be false by default.
<b>Action</b>	User can enable/disable this flag by setting true/false to pg.schema.validation.namespacegrowth property.
<b>010.0787Error</b>	<b>Could not load information on runtime aliases to Mediator. File not found {0}</b>
<b>Explanation</b>	Mediator could not find the file containing information on the runtime aliases.
<b>Action</b>	Check if the file is present in the specified location.
<b>010.0788Error</b>	<b>Error loading aliases from file store :{0}, {1}</b>
<b>Explanation</b>	Mediator encountered an error while loading the aliases from the file store.
<b>Action</b>	Check if the file store exists in Mediator and is valid.

<b>010.0790</b>	<b>Error saving runtime aliases to the file store: {0}. {1}</b>
<b>Explanation</b>	Mediator encountered an error while saving the aliases from the file store.
<b>Action</b>	Check if the file store exists in Mediator and is a valid file store.
<b>010.0792Error</b>	<b>Runtime alias not added to the file store: {0}</b>
<b>Explanation</b>	Mediator is not able to add the runtime alias to the file store.
<b>Action</b>	Check the Integration Server log for more details
<b>0201.0049</b>	<b>No Certificate was sent over HTTPS transport</b>
<b>0203.0323Error</b>	<b>Error parsing alias service names file. {0}</b>
<b>Explanation</b>	Mediator cannot parse the alias service names file.
<b>Action</b>	Check the Integration Server log for details. Redeploy the aliases and the associated services after you have fixed the issues in the alias service names file.
<b>0203.0324Error</b>	<b>Error loading the service names associated with the alias to memory. {0}</b>
<b>Explanation</b>	Mediator cannot parse the alias service names file.
<b>Action</b>	Check the Integration Server log for details.
<b>0203.0325Error</b>	<b>Error saving the service names associated with the alias to the file store. {0}</b>
<b>Explanation</b>	User may not have permission to write to the file, or the file may not be in the disk.
<b>Action</b>	Check the Integration Server log for details.
<b>0203.0326Debug error – RuntimeAliasesCache - Null references to aliases found. Could not load the runtime alias cache.</b>	
<b>Explanation</b>	Mediator found null references to aliases.
<b>Action</b>	Check the cluster configuration in Integration Server and also ensure that there are no null elements in the cache.
<b>MED.0010.0062E</b>	<b>Unable to get password for callback identifier: {0}</b>
<b>Explanation</b>	Error while retrieving cleartext password from encrypted passman file store.
<b>Action</b>	Review Mediator STS configuration; otherwise, this is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

- MED.0010.0083W Non-fatal Mediator package initialization error. {0}, {1}**  
**Explanation** Mediator encountered an error during an upgrade processing step after the package initialization completed.  
**Action** Verify the overinstall upgrade steps were followed as defined in the documentation; otherwise, this is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
- MED.0010.0212E Endpoint connection timeout duration expected as a number but was not a number ({0})**  
**Explanation** A virtual service was deployed with an invalid connection timeout specified for its native provider endpoint.  
**Action** Review the advanced endpoint configuration in CentraSite and redeploy the service if necessary.
- MED.0010.0214E Both keystore and key alias must be specified or none at all for SSL configuration; KeyStore alias = [{0}]; Key alias = [{0}]**  
**Explanation** A virtual service with a native provider SSL endpoint was deployed with an invalid advanced endpoint configuration. The endpoint must have a valid alias for both the keystore file and the keystore entry aliases as defined in the Integration Server or it can have no aliases defined at all.  
**Action** Update the advanced endpoint configuration and redeploy the virtual service to Mediator.
- MED.0010.0217E Error occurred when getting the password for handle {0} from passman!**  
**Explanation** An attempt to retrieve a cleartext password from a passman encrypted file store failed.  
**Action** This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
- MED.0010.0218E Error occurred when storing the password for handle {0} in passman!**  
**Explanation** An attempt to save a password in a passman encrypted file store failed during Mediator STS configuration.  
**Action** This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

---

<b>MED.0010.0220E</b>	<b>Error converting given WS-Policy component to string</b>
<b>Explanation</b>	Mediator was unable to parse policy elements used in producing request security tokens (RST) to a configured security token service (STS).
<b>Action</b>	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
<b>MED.0010.0702E</b>	<b>Mediator Upgrade, Mediator migration interrupted due to error. Details: {0}</b>
<b>Explanation</b>	This log message may occur when the Mediator package loads during the Integration Server restart after an overinstall. It indicates the upgrade was not successful and further actions are required.
<b>Action</b>	Depending on the error message, one of the three options are available. 1) Resolve the issue causing the upgrade to fail, and restart the Integration Server again to see if the upgrade completes successfully. 2) Delete the mediatorUpgrade.xml file from installation path: \${IS_HOME}/packages/WmMediator/ directory. This is the file that causes Mediator to perform its upgrade step. If this action is taken, the Mediator configuration will have to be re-entered manually through the IS admin UI. 3) Contact support. Everytime the Integration Server is restarted, Mediator will attempt to perform an upgrade as long as its mediatorUpgrade.xml file is present in the package directory.
<b>MED.0010.0705E</b>	<b>Mediator Upgrade, mediatorUpgrade.xml file is corrupted. Expected 'properties' root element but none found.</b>
<b>Explanation</b>	This message indicates the mediatorUpgrade.xml file included after the installer completes a Mediator overinstall is corrupted. This file is normally installed into the \${IS_HOME}/packages/WmMediator/ directory path when the overinstall completes. Its presence causes Mediator to run its upgrade tasks during the next Integration Server restart. Once the upgrade task has completed, this file is removed ensuring the upgrade is run only once.
<b>Action</b>	Contact customer support or remove the mediatorUpgrade.xml file. The mediator package should load without error during the next Integration Server restart if this file is removed, but Mediator configuration must be set up manually through the IS admin UI.
<b>MED.0010.0706E</b>	<b>Mediator Upgrade, unable to read required file. {0}</b>
<b>Explanation</b>	This log message may occur when the Mediator package loads during the Integration Server restart after an overinstall. This message implies that the OS user running the Integration Server does not have adequate permissions to read the file referenced in the error message.
<b>Action</b>	Review user and file permissions and make necessary adjustments to ensure the file can be read.

<b>MED.0010.0707E</b>	<b>Mediator Upgrade, configuration file is missing a required entry element key attribute. {0}, File path: {1}</b>
<b>Explanation</b>	This log message may occur when the Mediator package loads during the Integration Server restart after an overinstall. The mediatorUpgrade.xml file used to control a Mediator overinstall upgrade is corrupted. It is missing a reference to an attribute containing a path to an archive of the previous Mediator version prior to the overinstall.
<b>Action</b>	Contact support.
<b>MED.0010.0708E</b>	<b>Mediator Upgrade, configuration file entry element key attribute: {0}, expected this value: {1}, but found: {2}, File path: {3}</b>
<b>Explanation</b>	This log message may occur when the Mediator package loads during the Integration Server restart after an overinstall. The mediatorUpgrade.xml file used to control a Mediator overinstall upgrade is corrupted.
<b>Action</b>	Contact support.
<b>MED.0010.0709E</b>	<b>Mediator Upgrade, unable to find the required file. Expected location: {0}</b>
<b>Explanation</b>	This log message may occur when the Mediator package loads during the Integration Server restart after an overinstall. The backup file archive containing the Mediator package prior to the overinstall upgrade cannot be found.
<b>Action</b>	Contact support.
<b>MED.0010.0711E</b>	<b>Mediator Upgrade, unable to delete configuration file. Mediator upgrade task will continue to execute after each Integration Server startup until this file is removed. Path: {0}</b>
<b>Explanation</b>	This log message may occur when the Mediator package loads during the Integration Server restart after an overinstall. Verify that the OS user account running the Integration Server has the necessary permissions to delete the file.
<b>Action</b>	If the log messages suggest the upgrade ran successfully, this file can be deleted; otherwise, contact support.
<b>MED.0010.0712E</b>	<b>Mediator Upgrade, configuration file is not valid xml. Unable to parse it. {0}, Details: {1}</b>
<b>Explanation</b>	This log message may occur when the Mediator package loads during the Integration Server restart after an overinstall. The mediatorUpgrade.xml file is corrupted.
<b>Action</b>	Contact support.

---

<b>MED.0010.0717W</b>	<b>Mediator Upgrade, Could not find Default STS configuration file: {0} in archived zip file</b>
<b>Explanation</b>	The default STS configuration file was not found when performing an overinstall upgrade.
<b>Action</b>	No action is necessary if migrating from Mediator 8.0; otherwise, this is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
<b>MED.0010.0718E</b>	<b>Mediator Upgrade, configuration file has unexpected element key attribute, {0}, with value. {1}, and configuration file path: {2}</b>
<b>Explanation</b>	This log message may occur when the Mediator package loads during the Integration Server restart after an overinstall. The mediatorUpgrade.xml file is corrupted.
<b>Action</b>	Contact support.
<b>MED.0010.0719E</b>	<b>Mediator Upgrade, Could not find Default STS configuration file: {0} following upgrade; Skipping migrating configuration data!</b>
<b>Explanation</b>	Mediator was unable to locate the default STS configuration file during an overinstall upgrade.
<b>Action</b>	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
<b>MED.0010.0720W</b>	<b>Mediator Upgrade, Could not load Default STS client configuration; Skipping migrating configuration data</b>
<b>Explanation</b>	The default STS configuration file was not found when performing an overinstall upgrade.
<b>Action</b>	No action is necessary if migrating from Mediator 8.0; otherwise, this is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
<b>MED.0050.0408E</b>	<b>Authentication failed for user {0}</b>
<b>Explanation</b>	Invalid basic authentication credentials were included in the Authorization header sent to a virtual service that has a "Require HTTP Basic Authentication" runtime security policy.
<b>Action</b>	The web service consumer should include proper credentials and resend the service request.

- MED.0050.0608E**    **Error occurred when adding Timestamp to SOAP Envelope: {0}**  
**Explanation**    Mediator was unable to insert a WS security timestamp element to the request's security header sent to the native provider.  
**Action**    Review the configured ESB "AddTimestamp" service call for virtual service and redeploy if incorrect. Otherwise, this is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
- MED.0070.0010E**    **Incoming request does not contain the 'Authorization' header. This service requires the HTTP Basic Authentication token to be present.**  
**Explanation**    Authorization header was not sent to a virtual service that has a "Require HTTP Basic Authentication" runtime security policy.  
**Action**    The web service consumer must include valid credentials and resend the service request.
- MED.0070.0032E**    **Unable to create Schema for this service "{0}" Schema validation may not succeed!**  
**Explanation**    Mediator was unable to initialize the schema parser for a virtual service with a "Validate Schema" runtime policy. This error occurs when a consumer sends Mediator a service request.  
**Action**    Review the schemas defined in the virtual service, make corrections, and redeploy the virtual service if necessary; otherwise, this is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
- MED.0070.0071W**    **The ESB service name specified for InvokeESB mediator cannot be empty!**  
**Explanation**    A virtual service was deployed containing an ESB service invocation step containing an invalid or missing service name.  
**Action**    Review all service invocations from the "Processing steps" configuration for the virtual service and redeploy if necessary.
- MED.0070.0072E**    **The 'service' attribute is required for the InvokeESB mediator definition**  
**Explanation**    The deployed virtual service configuration is corrupted.  
**Action**    This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

---

<b>MED.0200.0045E</b>	<b>Error saving EhCache configuration file: {0}</b>
<b>Explanation</b>	Mediator was unable to save its configuration file used for the Terracotta cache component.
<b>Action</b>	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
<b>MED.0200.0046E</b>	<b>Could not find specified EhCache configuration file: {0}</b>
<b>Explanation</b>	The Terracotta cache configuration file for Mediator's caches could not be found during package startup.
<b>Action</b>	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
<b>MED.0203.0062E</b>	<b>ControllingNodeLocker.run, thread id({0}), expected Ehcache, found ({1})</b>
<b>Explanation</b>	Unexpected content was returned in the Terracotta cluster status cache.
<b>Action</b>	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
<b>MED.0203.0065E</b>	<b>ControllingNodeLocker.run, thread id({0}), caught ({1}/{2}) attempting to get a lock, thread dies</b>
<b>Explanation</b>	Mediator encountered an error trying to obtain a lock on the controlling node in a Terracotta cluster.
<b>Action</b>	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
<b>MED.0203.0070I</b>	<b>ClusterStatusCache - cache manager for {0} returned null CacheCluster reference, not clustered?</b>
<b>Explanation</b>	Mediator was unable to obtain a reference to the configured Terracotta cluster.
<b>Action</b>	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

<b>MED.0203.0071I</b>	<b>{0} - getCluster(ClusterScheme.TERRACOTTA) threw exception {1}, using schema NONE</b>
<b>Explanation</b>	An attempt to get Terracotta cluster configuration details failed.
<b>Action</b>	If Mediator is configured for a Terracotta cluster, this is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
<b>MED.0203.0072E</b>	<b>ClusterStatusCache - thread id({0}) attempts to release {1} lock, but does not hold it</b>
<b>Explanation</b>	An attempt to release the lock on the node controller in a Terracotta cluster failed.
<b>Action</b>	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
<b>MED.0203.0073E</b>	<b>Error initializing JAXB Context: {0}</b>
<b>Explanation</b>	Initialization for the cached global or registered consumers deployed to Mediator has failed.
<b>Action</b>	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
<b>MED.0203.0075E</b>	<b>ControllingNodeLocker.run, thread id({0}), caught {1} attempting to ask about lock status, thread dies</b>
<b>Explanation</b>	The thread defining the controlling node in a Mediator cluster encountered an error.
<b>Action</b>	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
<b>MED.0203.0076E</b>	<b>Unable to get cache named {0} from cache manager {1}</b>
<b>Explanation</b>	Mediator encountered an error accessing one of the Terracotta caches.
<b>Action</b>	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

<b>MED.0203.0081E</b>	<b>{0}, thread id({1}), caught {2}/{3} attempting to release lock, thread dies</b>
<b>Explanation</b>	Mediator encountered an error releasing the lock on the controlling node in the Terracotta cluster.
<b>Action</b>	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
<b>MED.0203.0082E</b>	<b>EhcacheClusterStatusCache, thread id({0}), caught {1}/{2} attempting to update controlling lock in cache</b>
<b>Explanation</b>	Mediator encountered an error updating the controlling node in a Terracotta cluster.
<b>Action</b>	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
<b>MED.0203.0100W</b>	<b>Thread interrupted when trying to obtain {0} lock for cache {1}</b>
<b>Explanation</b>	While Mediator was attempting to obtain a lock on a cache entry key, its thread was interrupted.
<b>Action</b>	No action may be necessary if Mediator is functioning normally.
<b>MED.0203.0101E</b>	<b>Unable to {0} lock the {1} cache for key {2} after waiting {3} mSecs</b>
<b>Explanation</b>	Mediator failed to lock a cache key in the expected period of time.
<b>Action</b>	No action may be necessary if Mediator is functioning normally
<b>MED.0203.0103E</b>	<b>{0} task in thread {1} threw this: {2}</b>
<b>Explanation</b>	An error occurred in the controlling node of a Terracotta cluster during Mediator shutdown.
<b>Action</b>	Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
<b>MED.0205.0062E</b>	<b>UddiPerformanceMetricsSender - unable to publish metrics over UDDI for service: {0}, message: {1}</b>
<b>Explanation</b>	This log message is produced when Mediator is unable to publish performance metrics results to Mediator. When reviewing the content, please be aware that some exception details may have originated from the CentraSite product hosting the UDDI server. Errors can range from improper Mediator configuration, OS resource issues, network connectivity, or issues with the CentraSite installation.

**Action** Depending on the errors logged in the Mediator UI, one of the following actions may prove more relevant. Verify CentraSite configuration information regarding UDDI is correct for the Mediator UI. Verify the hostname or IP address is reachable from the computer running the Mediator instance. Verify the CentraSite instance and its repository is up and accessible.

**MED.0205.0063E** **Unable to initialize UddiClientAdapter due to a missing password for username: {0}.**

**Explanation** This log message is produced when Mediator is unable to publish performance metrics results to Mediator. A password was not found in the encrypted store for the user configured in the CentraSite panel of the Mediator UI.

**Action** Verify the password is entered and the configuration was successfully saved for the CentraSite configuration screen in the Mediator UI.

**MED.0205.0064E** **Error connecting to CentraSite UDDI registry running on {0}://{1}:{2}. Error: {3}**

**Explanation** This log message may be produced under the following situations: During Mediator package startup. CentraSite configuration entered in Mediator UI is saved, but a connection to the UDDI server fails for these settings. Mediator attempts to publish performance metrics but fails during its regularly scheduled interval.

**Action** Verify the CentraSite configuration values in the Mediator UI are correct and CentraSite is up and running.

**MED.0205.0067E** **Error disconnecting to CentraSite UDDI registry running on {0}://{1}:{2}. Error: {3}**

**Explanation** This log message may be produced during the following situations: During Mediator package shutdown. While Mediator is initializing communications with the CentraSite UDDI server after encountering an error during runtime or saving configuration values in the Mediator UI.

**Action** Please see the Action for 0205.0064

**MED.0205.0602E** **Missing "{0}" Jdbc destination pool from spring configuration**

**Explanation** One of the Mediator configuration files is corrupted and a necessary configuration element is missing.

**Action** Contact support.

**MED.0205.0603E** **Jdbc destination sender expected a JdbcEvent object but received: "{0}"**

**Explanation** The JDBC destination sender event component received an unexpected event type.

**Action** Contact Support.

---

<b>MED.0205.0604E</b>	<b>Jdbc destination sender encountered a Sql Exception while generating "{0}" events. Error Code: {1} Cause: {2}</b>
<b>Explanation</b>	The Mediator Jdbc destination sender component encountered a SQL exception while sending a runtime event.
<b>Action</b>	Verify the database is operational and restart the functional alias pool. Verify the MediatorEvents database component tables installed using the Common Database Component are still defined, and the Jdbc pool credentials defined in Integration Server are correct. If all else fails, please contact Support.
<b>MED.0205.0605D</b>	<b>Jdbc destination sender took {0} msec to get a connection out of data source.</b>
<b>Explanation</b>	If the '0205 MEN - Events' Mediator logging component is set to 'DEBUG', then Mediator will issue a log message if the time it takes to get a Jdbc connection exceeds a pre-defined threshold as defined in Mediator's pg-jdbc.xml file. The current default is 50 milliseconds.
<b>Action</b>	No action is necessary.
<b>MED.0205.0606D</b>	<b>Jdbc destination sender took {0} msec to get a prepared statement out of connection with this SQL: {1}.</b>
<b>Explanation</b>	If the '0205 MEN - Events' Mediator logging component is set to 'DEBUG', then Mediator will issue a log message if the time it takes to get a Jdbc prepared statement exceeds a pre-defined threshold as defined in Mediator's pg-jdbc.xml file. The current default is 50 milliseconds.
<b>Action</b>	No action is necessary.
<b>MED.0205.0609D</b>	<b>Jdbc destination sender took {0} msec to close the prepared statement and connection.</b>
<b>Explanation</b>	If the '0205 MEN - Events' Mediator logging component is set to 'DEBUG', then Mediator will issue a log message if the time it takes to close a Jdbc connection exceeds a pre-defined threshold as defined in Mediator's pg-jdbc.xml file. The current default is 50 milliseconds.
<b>Action</b>	No action is necessary.
<b>MED.0205.0610E</b>	<b>Jdbc event requires at least one sql clause to be valid.</b>
<b>Explanation</b>	The Mediator Jdbc component is in an invalid state.
<b>Action</b>	Contact Support.

<b>MED.0205.0611D</b>	<b>Jdbc destination sender took {0} msec to insert a batch of {1} "{2}" events. AutoCommit enabled on driver? {3}, Transaction Isolation level? {4}</b>
<b>Explanation</b>	If the '0205 MEN - Events' Mediator logging component is set to 'DEBUG', then Mediator will issue a log message if the time it takes to execute a batch of runtime event inserts into the database exceeds a pre-defined threshold as defined in Mediator's pg-jdbc.xml file. The current default is 500 milliseconds.
<b>Action</b>	No action is necessary unless the time is extremely large. In that case, consider reducing the 'pg.jdbc.batchSize' property in Mediator's pg-config.properties file. This will cause the Jdbc destination sender to send updates to the database server in smaller batches.
<b>MED.0205.0612E</b>	<b>Jdbc destination sender cannot use a read-only connection object to insert events.</b>
<b>Explanation</b>	The functional alias used by Mediator's Jdbc destination sender is configured for a read-only transaction model in the Integration Server admin.
<b>Action</b>	Change the configured transaction model so it supports updates to the database.
<b>MED.0205.0614E</b>	<b>Jdbc event sql range should be between 0 and {0}, {1} is out of range.</b>
<b>Explanation</b>	Mediator Jdbc component is in an invalid state.
<b>Action</b>	Contact Support.
<b>MED.0205.0615E</b>	<b>Jdbc performance metrics processor expected only one return key, but "{0}" were found.</b>
<b>Explanation</b>	The Mediator Jdbc component is in an invalid state.
<b>Action</b>	Contact Support.
<b>MED.0205.0616E</b>	<b>Jdbc performance metrics processor expected two SQL statements, but "{0}" were found.</b>
<b>Explanation</b>	The Mediator Jdbc component is in an invalid state.
<b>Action</b>	Contact Support.
<b>MED.0205.0617E</b>	<b>Jdbc performance metrics processor is missing returned primary key upon SQL insert</b>
<b>Explanation</b>	Database did not return the 'event_pk' primary key column for the event inserted into the mediator_metrics_event table.
<b>Action</b>	Verify database is functioning properly; otherwise, contact Support.

---

<b>MED.0205.0618E</b>	<b>Jdbc event is in a bad state. Data type count "{0}" does not equal column value count "{1}"</b>
<b>Explanation</b>	The Jdbc event destination component is in an invalid state.
<b>Action</b>	Contact Support.
<b>MED.0205.0619W</b>	<b>Jdbc driver doesn't support returned named SQL columns from Insert statement. Trying "Statement.RETURN_GENERATED_KEYS" mode.</b>
<b>Explanation</b>	The Jdbc event destination component will attempt to use named columns for returning the database-generated primary key after inserting a row. If the database driver does not support this feature, this log message is raised, and the component will use another method to return the inserted primary key.
<b>Action</b>	No action required unless other SQLException errors are raised.
<b>MED.0206.0035W</b>	<b>MAC cache update {0} operation took {1} milliseconds to complete for {2} SIEs. This could cause lock attempts for tallying metrics statistics in MAC cache to fail.</b>
<b>Explanation</b>	An update to the policy engine metrics data took longer than expected. When the duration of this task is longer than the configured lock request timeout, tasks can be lost when they fail to obtain exclusive locks.
<b>Action</b>	Review Integration Server performance and increase the advanced property for lock timeout <code>pg.PgMenSharedCacheManager.lockTimeOut</code> and restart IS. Otherwise, if this happens very frequently, contact webMethods Customer Care. Please produce a diagnostic zip file by running the <code>mediator.util:mediatorDiagnosticZip</code> service from the <code>WmMediator</code> package's list of services in IS Admin's package management menu if available.



# 19

## My webMethods Server Messages

---

### **ClassPathComponentsMapper.folder.cannot.read – Cannot read from folder.**

**Explanation**            Cannot read from file. The file was deleted with no read rights.

**Action**                    Check to see if the file exists and if you have read rights.

### **ClassPathComponentsMapper.folder.not.exists – The folder does not exist:**

**Explanation**            The provided folder does not exist.

**Action**                    You must specify an existing folder.

### **ClassPathComponentsMapper.folder.not.valid – The specified path is not a valid folder.**

**Explanation**            The specified path is not valid folder; it might be a file and not a folder.

**Action**                    Specify a valid folder path.

### **Error.POP.0.0.001    Error sending mail**

**Explanation**            When a forum message is retracted, an e-mail notification is sent to the configured forum administrator. This error occurs if there are any problems sending this e-mail to the administrator.

**Action**                    Check the My webMethods Server logs for additional information about the specific e-mail failure. It may be caused by the e-mail server not being available, or because of an invalid forum administrator e-mail address. See Check the My webMethods Server logs for more details. See ..\MWS\server\\logs

<b>POP.001.0002E</b>	<b>A "{0}" occurred with the Message "{1}"</b>
<b>Explanation</b>	An unexpected error occurred during deployment.
<b>Action</b>	Examine the install.log, and optionally try again. In the log file, look for any information specific to the deployed component.
<b>POP.002.0004E</b>	<b>Context is in an invalid state.</b>
<b>Explanation</b>	The server attempted to use an invalid context object. This error is the result of attempting to use a context object before it has been initialized or after it has been uninitialized.
<b>Action</b>	Always use the provider <code>com.webmethods.portal.bizPolicy.IContextProvider</code> (available through the <code>com.webmethods.portal.system.PortalSystem</code> ) to acquire a context object.
<b>POP.002.0005E</b>	<b>Unable to locate command: {0}</b>
<b>Explanation</b>	The requested command is not deployed on the server.
<b>Action</b>	Log in to My webMethods Server and use the Install Administration portlet to deploy the command to the server.
<b>POP.002.0006E</b>	<b>Unable to locate biz policy for resource: {0}</b>
<b>Explanation</b>	The server cannot resolve the business policy for the specified resource because no policy has been registered for the resource type.
<b>Action</b>	Create and register a business policy for the resource type. Consult the My webMethods Server documentation to learn more about business policies.
<b>POP.002.0007E</b>	<b>Unknown error encountered while trying to resolve business policy for uri {0}</b>
<b>Explanation</b>	The server cannot resolve a business policy for specified resource because of an internal error.
<b>Action</b>	Check the <code>_problems_.log</code> in the <code>..\MWS\server\default\logs</code> directory for more specific error information.
<b>POP.002.0008E</b>	<b>Uri is not a valid thingID: {0}</b>
<b>Explanation</b>	The server cannot invoke the <code>RemoveAccess</code> command on a resource that is not a metadata resource.
<b>Action</b>	Correct the command-invoking source code to specify a metadata resource using either the <code>'resourceURI'</code> parameter or the context's current resource.

---

<b>POP.002.0009</b>	<b>Invalid arguments to create Alias command</b>
<b>Explanation</b>	You cannot invoke this command without the required arguments: key and target.
<b>Action</b>	If you invoked this command programatically, review the Javadocs and make the required changes to the invoking code.
<b>POP.002.0010</b>	<b>The arguments are not valid</b>
<b>Explanation</b>	When invoking the alias commands you must supply valid arguments.
<b>Action</b>	If you invoked this command programatically, review the Javadocs and make the required changes to the invoking code.
<b>POP.002.0011</b>	<b>You cannot flush another user's cache</b>
<b>Explanation</b>	Only an Administrator can flush another user's cache.
<b>Action</b>	You must log in to My webMethods Server with Administrator credentials to be able to flush another user's cache.
<b>POP.002.0012E</b>	<b>Class group name is not specified</b>
<b>Explanation</b>	You must specify the groupName parameter when invoking the ReloadClasses command.
<b>Action</b>	Correct the command-invoking code to specify the 'groupName' parameter. The parameter value should be the name of the group's class-loader bundle.
<b>POP.002.0014E</b>	<b>Unable to authenticate user: {0}</b>
<b>Explanation</b>	The server cannot authenticate the user either because the user does not exist or because the user's password is incorrect.
<b>Action</b>	Try again with correct username and password. If necessary, log in to My webMethods or My webMethods Server and use the User Management feature to add the user to the server
<b>POP.002.0016E</b>	<b>Error listing directory groups</b>
<b>Explanation</b>	The server cannot list the groups of a particular directory service, most likely because of a problem connecting to the directory service.
<b>Action</b>	If the directory service is a newly configured directory service, log in to the My webMethods Server and double-check the configuration using the Folders > System > Portlets > Administration > Directory Services Administration portlet. If the directory service is an existing directory service for which groups could be listed previously, validate that the LDAP or ADSI server to which the directory service is connected is up and running properly. Also check that the machine which hosts My webMethods Server is able to connect to the LDAP or ADSI server using the hostname and port specified in the directory service's configuration.

- POP.002.0017E**      **Error retrieving template list**  
**Explanation**      The server cannot list directory service templates, because an error occurred loading the templates.  
**Action**              Check the ..\MWS\server\default\logs\\_problems\_.log file for more specific error information.
- POP.002.0018E**      **Error listing users**  
**Explanation**      The server cannot list the users of a particular directory service, most likely because of a problem connecting to the directory service.  
**Action**              If the directory service is a freshly configured directory service, go back to the Portal Admin Dashboard, and double-check the configuration using the Directory Service Administration portlet (in the Portal Configuration category). If the directory service is an existing directory service for which groups could be listed previously, validate that the LDAP or ADSI server to which the directory service is connected is up and running properly. Also check that the machine which hosts the Portal server is able to connect to the LDAP or ADSI server using the hostname and port specified in the directory service's configuration.
- POP.002.0019E**      **Error updating directory**  
**Explanation**      The server cannot update the directory service configuration because an error occurred in validating or storing the configuration settings.  
**Action**              Check the ..\MWS\server\default\logs\\_problems\_.log file for more specific error information.
- POP.002.0020**        **Invalid command ID: {0}**  
**Explanation**      The requested command is not found.  
**Action**              Verify that the command has been properly installed. This can be done by logging in to My webMethods Server as sysadmin and viewing the commands in the folder Folders > System > Manager > Commands directory.
- POP.002.0021E**      **Cannot resolve install mechanics for: {0}**  
**Explanation**      An error occurred during the installation of a server component.  
**Action**              Look in the ..\MWS\server\default\logs\\_problems\_.log file for the stack trace of the error. The stack trace may not provide enough detail to say why the error was thrown, but it will show where the error originated.

---

<b>POP.002.0022</b>	<b>Location is not a folder: {0}</b>
<b>Explanation</b>	When the Install Services commands are instructed to deploy all of the components of a folder, the resource must be a folder and cannot be a file.
<b>Action</b>	Ensure that either the Autodeploy folder is properly configured or that the object passed to the InstallComponents command is a folder.
<b>POP.002.0023</b>	<b>Cannot find folder: {0}</b>
<b>Explanation</b>	When the Install Services commands are instructed to deploy all of the components of a folder, the folder must be available.
<b>Action</b>	Ensure that either the Autodeploy folder is properly configured or that the object passed to the InstallComponents command is an available folder.
<b>POP.002.0025E</b>	<b>Command name is not specified</b>
<b>Explanation</b>	The Ant build file does not contain the command name needed to invoke the ExecuteCommand ant task.
<b>Action</b>	Correct the Ant build file to provide the command name with the 'name' attribute of the ExecuteCommand task.
<b>POP.002.0026E</b>	<b>Cannot resolve command [name, type] [{0}, {1}]</b>
<b>Explanation</b>	The server cannot execute the command by means of an Ant task because the specified command has not been deployed to the server.
<b>Action</b>	Deploy the command specified by the error message.
<b>POP.002.0027E</b>	<b>Attribute target is required</b>
<b>Explanation</b>	The target for invoking the ExecuteTargetLoop Ant task has not been specified.
<b>Action</b>	This error can occur if a developer modifies an Ant build file used to deploy components to the server. Correct the Ant build file to add a 'target' attribute to the ExecuteTargetLoop task invocation.
<b>POP.002.0028E</b>	<b>Cannot create IInitializableComponentData from: {0}</b>
<b>Explanation</b>	The component configuration data is not one of the following types: xml (serialized XML document), xmlLocation (URL specifying an XML document), properties (serialized properties map), propertiesLocation (URL specifying a properties file location).
<b>Action</b>	Correct the component configuration in the phaseProvider.xml configuration file to specify component configuration data as either xml, xmlLocation, properties, or propertiesLocation.

<b>POP.002.0029E</b>	<b>Attribute source is required</b>
<b>Explanation</b>	The server cannot execute an Ant task because the task requires a source attribute to be specified.
<b>Action</b>	Correct the Ant build file to add a 'src' attribute to RunJavaScript and RunSQLScript tasks. The 'src' attribute must specify the file path to the script to be run.
<b>POP.002.0030E</b>	<b>Cannot create IInitializableComponentData from {0} for provider {1}</b>
<b>Explanation</b>	The server cannot unregister the specified component. The component's configuration data has become corrupted.
<b>Action</b>	Reinstall the component with the Folders > Administrative Folders > Administration Dashboard > Configuration > Install Administration portlet, and then re-try uninstalling the component.
<b>POP.002.0031</b>	<b>Cannot find IComponent using IComponentData {0} in provider {1}</b>
<b>Explanation</b>	An attempt was made to unregister a component that is not currently registered.
<b>Action</b>	No further action is required.
<b>POP.002.0032E</b>	<b>Cannot get IComponentData for component {0} from provider {1}</b>
<b>Explanation</b>	An error occurred during the unregistration of a server component.
<b>Action</b>	Look in the ..\MWS\server\default\logs\_problems_.log file for the stack trace of the error. The stack trace may not provide enough detail to say why the error was thrown, but it will show where the error originated. It is likely that you need to restart the server.
<b>POP.002.0033E</b>	<b>Component Provider not found: {0}</b>
<b>Explanation</b>	The server cannot unregister the component because component data has become corrupted.
<b>Action</b>	Re-install the component with the Folders > Administrative Folders > Administration Dashboard > Configuration > Install Administration portlet, then re-try uninstalling.
<b>POP.002.0034E</b>	<b>Attribute descriptorSrc is required</b>
<b>Explanation</b>	The Ant task does not have skin descriptor content.
<b>Action</b>	Correct the Ant build file to provide skin descriptor content using the 'descriptorSrc' attribute to CreateSkinInstance, GetSkinInfo, and RemoveSkinInstance Ant tasks.

---

<b>POP.002.0035E</b>	<b>Skin name is empty</b>
<b>Explanation</b>	The server cannot determine the skin name because the skin descriptor does not contain the skin name or because the skin descriptor is improperly structured.
<b>Action</b>	Correct the skin descriptor to include the skin name in the 'name' attribute value of the 'wm_xt_skin' element.
<b>POP.002.0036E</b>	<b>Portlet info is not specified</b>
<b>Explanation</b>	Portlet descriptor content is not included in the GetPortletInfo Ant task.
<b>Action</b>	Correct the Ant build file to provide portlet descriptor content using the 'descriptorSrc' attribute.
<b>POP.002.0037E</b>	<b>Portlet name is empty</b>
<b>Explanation</b>	The server cannot determine the portlet name because the portlet descriptor does not contain the portlet name or because the portlet descriptor is improperly structured.
<b>Action</b>	Correct the portlet descriptor to include the portlet name as the content of the 'name' element.
<b>POP.002.0038E</b>	<b>Portlet is not available: {0}</b>
<b>Explanation</b>	The specified portlet is not deployed on the server.
<b>Action</b>	Use the Folders > Administrative Folders > Administration Dashboard > Configuration > Install Administration portlet to deploy the portlet specified by the error message.
<b>POP.002.0040E</b>	<b>Cannot find system folder for the portlet: {0}</b>
<b>Explanation</b>	An error occurred during installation of a portlet.
<b>Action</b>	Look in the ..\MWS\server\default\logs\_problems_.log file for the stack trace of the error. It may be necessary to reinstall the component.
<b>POP.002.0041</b>	<b>Page have to be a folder type</b>
<b>Explanation</b>	When cloning pages, the source of the cloning operation must be of the appropriate type
<b>Action</b>	Ensure that an appropriate source is used for the cloning operation.

<b>POP.002.0042E</b>	<b>Destination container is not a valid thing: {0}</b>
<b>Explanation</b>	The server cannot clone a remote resource; the resource must be cloned to a metadata destination container.
<b>Action</b>	Correct the command-invoking source code to specify a metadata destination container using the 'destContainerURI' parameter.
<b>POP.002.0043E</b>	<b>Source item container is not a valid thing: {0}</b>
<b>Explanation</b>	The server cannot clone the remote resource; only metadata resources can be cloned.
<b>Action</b>	Correct the command-invoking source code to specify a metadata resource using either the 'resourceURI' parameter or the server context's current resource.
<b>POP.002.0044E</b>	<b>Invalid XType: {0}</b>
<b>Explanation</b>	The server cannot resolve the DBO type of the remote item to be cloned. The most likely reason is that the DBO type has been uninstalled from the system.
<b>Action</b>	Normally, a DBO type cannot be uninstalled from the system until all instances of the type have been deleted. This message may also indicate that a damaged instance of the remote item is still present but cannot be cloned or recovered. No further action can be taken.
<b>POP.002.0046E</b>	<b>Item is not a valid thing: {0}</b>
<b>Explanation</b>	The server cannot invoke the metadata command because the command must be invoked against a metadata resource.
<b>Action</b>	Correct the command-invoking source code to specify a metadata resource using either the 'resourceURI' parameter or the server context's current resource.
<b>POP.002.0047</b>	<b>Can not create an item with an empty name</b>
<b>Explanation</b>	When creating a new resource, a 'name' property is required.
<b>Action</b>	When creating the resource, ensure that a name is supplied.
<b>POP.002.0048E</b>	<b>Delete operation failed</b>
<b>Explanation</b>	The container cannot be deleted because at least one of the items in the container cannot be deleted. Refer to the the list of contained items that cannot be deleted, displayed in the user interface along with this message.
<b>Action</b>	Manually delete the specified undeletable contained items individually. This may result in more detailed information as to why the items cannot be deleted.

---

<b>POP.002.0049E</b>	<b>Error obtaining owned folder</b>
<b>Explanation</b>	The server cannot obtain the owned folder because of an internal server error.
<b>Action</b>	Check the ..\MWS\server\default\logs\_problems_.log file for more specific error information.
<b>POP.002.0050E</b>	<b>Cannot get current resource uri</b>
<b>Explanation</b>	Cannot invoke the portlet command because a target portlet for the command is not specified.
<b>Action</b>	Correct the command-invoking code to specify the portlet with the 'resourceURI' parameter or with the server context's current resource.
<b>POP.002.0051E</b>	<b>ResourceURI is not specified</b>
<b>Explanation</b>	The server cannot invoke the portlet command because a target portlet for the command is not specified.
<b>Action</b>	Correct the command-invoking source code to specify the portlet with the 'resourceURI' parameter or with the server context's current resource.
<b>POP.002.0052E</b>	<b>PortletBean is not ICommandBean</b>
<b>Explanation</b>	The command cannot be invoked against the portlet because the portlet's portlet-bean does not implement the com.webmethods.portal.bizPolicy.command.ICommandBean interface.
<b>Action</b>	Modify portlet's portlet-bean source code to make the portlet-bean implement ICommandBean. Rebuild and redeploy the portlet.
<b>POP.002.0053E</b>	<b>UserID is not of type IThingID or String</b>
<b>Explanation</b>	The command was invoked using RMI with an inappropriate userID data type. This error is usually a result of a bug in the command-invoking code.
<b>Action</b>	Correct the command-invoking code to ensure it invokes the command with a userID specified either as a java.lang.String or a com.portal.webmethods.meta2.thing.IThingID object.
<b>POP.002.0054E</b>	<b>Search library not found: {0}.</b>
<b>Explanation</b>	An attempt was made to delete a search library that does not exist.
<b>Action</b>	Log in to My webMethods Server and use the Search Administration portlet to check the name of the search library against the available libraries.

<b>POP.002.0056E</b>	<b>Saved Searches folder not found.</b>
<b>Explanation</b>	The server cannot save a search because the user's saved-searches folder does not exist.
<b>Action</b>	User folders such as the user's saved-searches folder are created automatically for users when they login to My webMethods Server. Try logging out as the user, and then logging in again.
<b>POP.002.0057E</b>	<b>No name parameter found</b>
<b>Explanation</b>	The server cannot invoke the save-search command name; the command does not specify a name parameter.
<b>Action</b>	Correct the command-invoking source code to specify a 'name' parameter.
<b>POP.002.0058E</b>	<b>Not a valid skin: {0}</b>
<b>Explanation</b>	The server cannot invoke the ReloadSkin command; the specified skin identifier does not identify a valid skin.
<b>Action</b>	Correct the command-invoking source code to specify a valid skin resource using the 'skin' parameter.
<b>POP.002.0059E</b>	<b>Default xmlimport requires an IThingID for the parent: {0}</b>
<b>Explanation</b>	The server cannot import a metadata resource using xmlImport unless the parent of the resource is also a metadata resource.
<b>Action</b>	Correct the xmlImport file to move or remove elements contained by the element specified by the error message.
<b>POP.002.0060</b>	<b>Default xmlimport requires the parent to be a container: {0}</b>
<b>Explanation</b>	When executing an XML import script, every new child must be created within a valid container.
<b>Action</b>	Check the script to ensure that each created item has a valid parent.
<b>POP.002.0061E</b>	<b>Unable to locate acl for aclName: {0}</b>
<b>Explanation</b>	The server cannot modify the access control list (ACL) for a resource specified in xmlImport because the access control list was referenced by an alias that does not exist.
<b>Action</b>	Correct the xmlImport file to replace the 'aclName' attribute value specified by the error message with a valid value.

---

<b>POP.002.0062E</b>	<b>Unable to find value for acl</b>
<b>Explanation</b>	The server cannot create an access control entry using xmlImport because the ACL element requires a value attribute.
<b>Action</b>	Correct the xmlImport file to add a 'value' attribute to the 'acl' elements. The 'value' attribute values must contain one of the following My webMethods Server access right names (comma separated): READ, CREATE_ITEM, CREATE_CONTAINER, MODIFY, DELETE, PORTLET_MODIFY_PROPERTIES_INSTANCE, PORTLET_MODIFY_PROPERTIES_USER, ALL.
<b>POP.002.0063E</b>	<b>Unable to find ace value for: {0}</b>
<b>Explanation</b>	The server cannot create access an control entry using xmlImport because the xmlImport entry references an unknown right value.
<b>Action</b>	Correct the xmlImport file to add a 'value' attribute to the 'acl' elements. The 'value' attribute values must contain one of the following My webMethods Server access right names (comma separated): READ, CREATE_ITEM, CREATE_CONTAINER, MODIFY, DELETE, PORTLET_MODIFY_PROPERTIES_INSTANCE, PORTLET_MODIFY_PROPERTIES_USER, ALL.
<b>POP.002.0064</b>	<b>Unable to find alias name to set the acl</b>
<b>Explanation</b>	The required argument 'value' was not set on this xmlimport element.
<b>Action</b>	Ensure that the ACL element has a 'value' attribute
<b>POP.002.0065E</b>	<b>Alias attribute missing on context node</b>
<b>Explanation</b>	The server cannot establish the resource context during xmlImport because the context element requires an alias attribute.
<b>Action</b>	Correct the xmlImport file to add an 'alias' attribute to 'context' elements. The alias attribute value must contain the name of a valid alias; elements enclosed by the context apply to the resource identified by this alias.
<b>POP.002.0069S</b>	<b>Root users folder not found</b>
<b>Explanation</b>	The server cannot create the user's home folder because the server users folder does not exist.
<b>Action</b>	Create a new server folder, and set its alias to 'folder.users'.

- POP.002.0076E      The basic update properties requires a thingID: {0}**  
**Explanation**      The server cannot invoke the ImportFiles command because it does not specify a target folder for the import.  
**Action**              Correct the command-invoking source code to specify a folder using either the 'resourceURI' parameter or the server context's current resource.
- POP.002.0077E      Adding to version control requires a thingID: {0}**  
**Explanation**      The server cannot invoke the version-control command without specifying a versionable resource.  
**Action**              Correct the command-invoking source code to specify a versionable resource using either the 'resourceURI' parameter or the server context's current resource.
- POP.002.0078E      The resource does not support IVersionableMechanics: {0}**  
**Explanation**      The server cannot invoke the version-control command on the resource because the resource is not versionable.  
**Action**              Do not invoke the AddToVersion command against resources that are not versionable. Only server folders and server content items are versionable.
- POP.002.0079E      Command requires a thingID: {0}**  
**Explanation**      The server cannot invoke the version-control command without specifying a versionable resource.  
**Action**              Correct the command-invoking source code to specify a versionable resource using either the 'resourceURI' parameter or the server context's current resource.
- POP.002.0080E      Invalid version Uri: {0}**  
**Explanation**      The server cannot display the server version information of an item because the identifier used to specify the version is not a valid version identifier.  
**Action**              Correct the source code that invokes the ViewVersion command to provide a valid version identifier.
- POP.002.0081E      Invalid thing ID: {0}**  
**Explanation**      The server cannot display the server version information of an item because the identifier used to specify the item does not identify a valid resource  
**Action**              Correct the command-invoking source code to provide a valid versioned-item identifier for the 'targetURI' parameter.

---

<b>POP.002.0082</b>	<b>User {0} don't have rights to view {1}</b>
<b>Explanation</b>	The current user failed the permissions check to see a particular version of an item.
<b>Action</b>	Check the permissions on that item.
<b>POP.002.0083E</b>	<b>Could not acquire context, principal data not found on session</b>
<b>Explanation</b>	The server cannot create a server context for the specified javax.servlet.http.HttpSession because the HttpSession has not been initialized with the necessary server session data.
<b>Action</b>	Restart My webMethods Server.
<b>POP.002.0085E</b>	<b>Can't create subscription for non Thing: {0}</b>
<b>Explanation</b>	The server cannot create a subscription from xmlImport data because subscriptions are supported only for metadata resources.
<b>Action</b>	Correct the xmlImport file to remove 'subscription' elements from non-metadata resource contexts. The best way to determine specifically which subscription elements in the xmlImport file are causing this error is the trial-and-error approach: remove each subscription element in the xmlImport file one by one and then try re-importing from the xmlImport file.
<b>POP.002.0086E</b>	<b>Unable to import xml. No uid.</b>
<b>Explanation</b>	An attempt to create an access control entry or subscription using xmlimport did not specify the user ID of the My webMethods Server user or group.
<b>Action</b>	Correct the xmlImport file to add a 'uid' attribute to 'subscription' and 'ace' elements. The 'uid' attribute value must contain the user ID (LDAP user ID) of a valid My webMethods Server user or the cn (LDAP group ID) of a valid My webMethods Server group.
<b>POP.002.0087W</b>	<b>Unable to import xml. Could not acquire uri for uid: {0}</b>
<b>Explanation</b>	The user referenced in the xmlImport file does not exist on My webMethods Server.
<b>Action</b>	Log in to My webMethods or My webMethods Server with appropriate permissions and add the user, or change the xmlImport file.
<b>POP.002.0089E</b>	<b>Unable to import subscription. No value specified for 'deliveryMode'.</b>
<b>Explanation</b>	The server cannot create a subscription from xmlImport data because the subscription element requires a deliveryMode attribute. This error is caused by importing from an improperly constructed xmlImport file.
<b>Action</b>	Correct the xmlImport file by adding a 'deliveryMode' attribute to 'subscription' elements. The valid value for 'deliveryMode' attribute is "email", indicating notifications for this subscription are to be delivered to the user's e-mail address.

- POP.002.0090E**      **Unable to import subscription. No value specified for 'criteria'.**
- Explanation**      The server cannot create the subscription from xmlImport data because the subscription element requires a criteria attribute that contains the name of at least one criterion valid for the type of resource subscribed to.
- Action**            Correct the 'subscription' elements in the xmlImport file so that they all contain valid 'criteria' attribute values. Valid values are not empty; they must contain a comma-separated list of criterion names. The criterion names for basic folders are: 'added', 'removed', 'modified', 'deleted', and 'moved'. The criterion names for basic links, forms, portlets, and content items are 'modified', 'deleted', and 'moved'. Custom DBO types may have additional criteria.
- 
- POP.002.0091E**      **No matching criteria found for type: {0} and for criteria: {1}.**
- Explanation**      The server cannot create a subscription from xmlImport data because the subscription element requires a criteria attribute that contains the name of at least one criterion valid for the type of resource subscribed to.
- Action**            Correct the xmlImport file so that 'subscription' elements contained by any element of the type specified by the error message's resource-typeName have valid 'criteria' attribute values. Valid values are not empty; they must contain a comma-separated list of criterion names. The criterion names for basic folders are: 'added', 'removed', 'modified', 'deleted', and 'moved'. The criterion names for basic links, forms, portlets, and content items are 'modified', 'deleted', and 'moved'. Custom DBO types may have additional criteria.
- 
- POP.002.0092E**      **Can't set ace for non Thing: {0}**
- Explanation**      The server cannot modify the access control entry (ACE) for a resource specified in xmlImport because the resource does not support My webMethods Server access control entries.
- Action**            Correct the xmlImport file to remove the 'ace' element for the resource specified by the error message.
- 
- POP.002.0093E**      **Unable to locate alias for: {0}**
- Explanation**      The server cannot establish the resource context during xmlImport because the alias specified for the context does not exist.
- Action**            Log in to My webMethods Server and use the Alias Management portlet to create the alias specified by the error ,message or fix the xmlImport file to use an alias that does exist. To fix the xmlImport file, locate the alias attribute with the value specified by the error message and replace that value with the name of an existing alias.

---

<b>POP.002.0095</b>	<b>Unable to create alias: {0} because it already exists.</b>
<b>Explanation</b>	The command failed because an alias of the same name has already been registered.
<b>Action</b>	Either apply a different name to the new alias or modify the existing alias that uses the same name.
<b>POP.002.0096E</b>	<b>Mechanics is not an IBasicMechanics</b>
<b>Explanation</b>	The server cannot use xmlImport to update the properties of a resource that is not a metadata resource.
<b>Action</b>	Correct the xmlImport file to not update the properties of non-metadata resources. The best way to determine the element in the xmlImport file that is causing this error is the trial-and-error approach: remove each element in the xmlImport file one-by-one and then try re-importing from the xmlImport file.
<b>POP.002.0097E</b>	<b>Unable to complete import because type: {0} doesn't exist.</b>
<b>Explanation</b>	The server cannot import a resource specified in xmlImport because the resource is an instance of a DBO that is not currently deployed in My webMethods Server.
<b>Action</b>	Deploy the DBO specified by the error message and then rerun the xmlImport.
<b>POP.002.0098</b>	<b>Role xmlimport requires attributes of 'roleProvider' and 'name'</b>
<b>Explanation</b>	When creating a new role using an xmlImport script, the attributes must be available.
<b>Action</b>	Modify the xmlimport script to include the required 'roleProvider' and 'name' properties.
<b>POP.002.0099</b>	<b>Role xmlimport unable to locate roleProvider: {0}</b>
<b>Explanation</b>	The type of role is not registered on the current system.
<b>Action</b>	Check the 'roleProvider' attribute to make sure it is correct.
<b>POP.002.0103</b>	<b>Failed to set Alias {0} for resource {1}.</b>
<b>Explanation</b>	The system failed to correctly set an alias during the xmlimport.
<b>Action</b>	Check the server logs at ..\MWS\server\default\logs for any additional exceptions that occurred during the import.

<b>POP.002.0105</b>	<b>Failed to load xml document from {0}</b>
<b>Explanation</b>	The XML file specified for the xmlimport script is either not found or not well-formed.
<b>Action</b>	Verify that the XML file exists in the specified location and that the contents of the file are valid XML.
<b>POP.002.0107</b>	<b>Failed to invoke remote command: {0}. Original error message: {1}</b>
<b>Explanation</b>	A problem occurred when executing a command on a remote server.
<b>Action</b>	Check the logs on the remote server for additional information.
<b>POP.002.0108</b>	<b>User UID can not be found in MWS directories: {0}</b>
<b>Explanation</b>	No user is found with the specific user ID.
<b>Action</b>	Specify a valid user ID.
<b>POP.002.0110</b>	<b>You have insufficient privileges to impersonate other users.</b>
<b>Explanation</b>	You have insufficient privileges to impersonate other users.
<b>Action</b>	The log file indicates how to grant user impersonate privileges. Contact a system administrator if you need such privileges.
<b>POP.002.0111</b>	<b>Illegal Argument: Command result may not be serialized.</b>
<b>Explanation</b>	The command result cannot be serialized.
<b>Action</b>	Make sure the command result can be serialized.
<b>POP.002.0113</b>	<b>The parent of the task is already completed</b>
<b>Explanation</b>	You cannot create a new child task if its parent task has been completed.
<b>Action</b>	Contact the parent task owner to determine how to handle the additional work.
<b>POP.002.0114</b>	<b>User {0} does not have the functional privilege to delegate task {1}</b>
<b>Explanation</b>	The user has not been granted the functional privilege to delegate the task.
<b>Action</b>	Please contact the system administrator if you need such privileges.
<b>POP.002.0118</b>	<b>Thing with name "{0}" for locale "{1}" already exists in "{2}". Unable to rename "{3}"</b>

---

<b>POP.003.0003S</b>	<b>No access model specified in property "{0}".</b>
<b>Explanation</b>	The framework.access.model system property does not specify an access model.
<b>Action</b>	Update the portal.properties file to specify framework.access.model property value. The choices are permissive or restrictive.
<b>POP.003.0004S</b>	<b>Unable to register principal types: "{0}".</b>
<b>Explanation</b>	The system directory is corrupted.
<b>Action</b>	Restore the underlying system user directory content from a backup or manually restore the user directory. In the case of LDAPd, you can reinstall the LDAPd server using the webMethods Installer.
<b>POP.003.0005S</b>	<b>Unable to register search service: "{0}".</b>
<b>Explanation</b>	An error occurred in registering a new search service.
<b>Action</b>	You might need to reinstall My webMethods Server.
<b>POP.003.0006S</b>	<b>Error initializing content service: "{0}".</b>
<b>Explanation</b>	The content service cannot be initialized.
<b>Action</b>	Check the Content Service Administration portlet to verify that the content service is properly configured.
<b>POP.003.0007E</b>	<b>Cannot list roles, directory service "{0}" not found.</b>
<b>Explanation</b>	The directory service cannot be found.
<b>Action</b>	Check the Directory Service Administration portlet to verify that the directory service is properly configured and functional.
<b>POP.003.0008E</b>	<b>Could not locate system directory: "{0}".</b>
<b>Explanation</b>	The server cannot find the system user directory.
<b>Action</b>	Verify that the system directory is present in Directory Services Administration portlet, and that it is configured and functional.
<b>POP.003.0009E</b>	<b>Error setting system directory: "{0}".</b>
<b>Explanation</b>	The command failed to change the system directory service.
<b>Action</b>	Do not attempt to change the system directory.

<b>POP.003.0012W</b>	<b>"{0}" does not have permission to modify the Administrators group.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu to open the Permissions portlet to give the user access rights.
<b>POP.003.0013W</b>	<b>"{0}" does not have permission to modify the directory configuration.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu to open the Permissions portlet to give the user access rights.
<b>POP.003.0014E</b>	<b>Cannot update directory config, domain not found: "{0}".</b>
<b>Explanation</b>	An attempt was mademto update the config information for a directory service using an invalid domain name.
<b>Action</b>	Use a valid domain name.
<b>POP.003.0015S</b>	<b>Cannot update directory config, Administrator user not found: "{0}".</b>
<b>Explanation</b>	The system directory or the database is corrupted.
<b>Action</b>	Restore the underlying system user directory content from a backup or do so manually. If LDAPd, you can reinstall the LDAPd server using the webMethods Installer.
<b>POP.003.0016E</b>	<b>Cannot update directory config, Everyone group not found: "{0}".</b>
<b>Explanation</b>	The system directory does not have an everyone group or the directory is corrupted.
<b>Action</b>	Restore the underlying system user directory content from a backup or do so manually. In the case of LDAPd, you can reinstall the LDAPd server using the webMethods Installer.
<b>POP.003.0017S</b>	<b>Cannot update directory config, Guest user not found: "{0}".</b>
<b>Explanation</b>	The system directory is corrupted.
<b>Action</b>	Restore the underlying system user directory content from a backup or do so manually. In the case of LDAPd, you can reinstall the LDAPd server using the webMethods Installer.

---

<b>POP.003.0018E</b>	<b>Cannot remove the system directory.</b>
<b>Explanation</b>	The system directory services cannot be removed.
<b>Action</b>	Do not try to remove the system directory.
<b>POP.003.0021E</b>	<b>System directory does not have Administrator user.</b>
<b>Explanation</b>	The LDAP user store is missing the administrator user.
<b>Action</b>	Add a user to the system LDAP user store whose UID matches the Portal Administrator UID. This should only be necessary if the LDAP user store has become corrupted or the PortalAdmin user has been removed.
<b>POP.003.0022S</b>	<b>System directory does not have Everyone group. Everyone group access will not be available.</b>
<b>Explanation</b>	The system directory is corrupted.
<b>Action</b>	Restore or create the everyone group in the system directory. Use the directory's administration UI or tools for that purpose.
<b>POP.003.0023E</b>	<b>System directory does not have Guest user. Guest access will not be available.</b>
<b>Explanation</b>	The system directory does not have a guest user or it is corrupted.
<b>Action</b>	Restore the underlying system user directory content from a backup or do so manually. In the case of LDAPd, you can reinstall the LDAPd server using the webMethods Installer.
<b>POP.003.0024W</b>	<b>The type "{0}" is either 'disabled' or not deployed to this MWS cluster node. Please contact the My webMethods Server Administrator.</b>
<b>Explanation</b>	An attempt was made to view a portlet for which the status has been set to disabled.
<b>Action</b>	Use the Manage Components portlet in the Administration Dashboard to change the status of the portlet type.
<b>POP.003.0025W</b>	<b>{0} cannot view the content of {1}.</b>
<b>Explanation</b>	The user is denied access to view a portlet item
<b>Action</b>	Use the Permissions page to set the authentication scheme for the item to one of the installed authentication schemes.

<b>POP.003.0026W</b>	<b>{0} cannot list the shortcuts to {1}.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
<b>POP.003.0027W</b>	<b>{0} cannot list the notes for {1}.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
<b>POP.003.0028W</b>	<b>{0} cannot view the access list for {1}.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
<b>POP.003.0029W</b>	<b>{0} cannot view the authentication scheme for {1}.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
<b>POP.003.0030W</b>	<b>{0} cannot create an item of type {1}.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open up the Permissions portlet to give the user access rights.
<b>POP.003.0031W</b>	<b>{0} cannot update the content of {1}.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
<b>POP.003.0032W</b>	<b>{0} cannot add the note for {1}.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

---

<b>POP.003.0033W</b>	<b>{0} cannot remove the note for {1}.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
<b>POP.003.0034W</b>	<b>{0} cannot update the properties of {1}.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
<b>POP.003.0035W</b>	<b>{0} cannot delete {1}.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
<b>POP.003.0037W</b>	<b>{0} cannot destroy {1}.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
<b>POP.003.0038</b>	<b>{0} cannot store content {1}.</b>
<b>Explanation</b>	An attempt was made to store a document on a type that does not support document storage
<b>Action</b>	Ensure that content is stored on document types
<b>POP.003.0039W</b>	<b>{0} cannot contain a duplicate reference to {1}.</b>
<b>Explanation</b>	You cannot create items with the same name under the same folder.
<b>Action</b>	When naming items in a folder, make sure each item uses a name that is unique within the folder.
<b>POP.003.0040W</b>	<b>Cannot uninstall "{0}" because it has "{1}" published instances. Please delete them first and try again.</b>
<b>Explanation</b>	The DBO cannot be uninstalled because it has published instances.
<b>Action</b>	Manually delete all published instances of this DBO and try to uninstall it again. You can use Publish History portlet to help you find all published instances.

<b>POP.003.0044W</b>	<b>{0} is checked out.</b>
<b>Explanation</b>	The item cannot be checked out because it is already checked out.
<b>Action</b>	Wait until the item is checked in and try again.
<b>POP.003.0045W</b>	<b>{0} is not versioned.</b>
<b>Explanation</b>	The item is not versioned.
<b>Action</b>	Add the item to version control using the item's local menu.
<b>POP.003.0046</b>	<b>{0} cannot view version number of {1}.</b>
<b>Explanation</b>	An attempt was made to view a version of a document that failed a permissions check
<b>Action</b>	Verify that the current user has sufficient permissions
<b>POP.003.0047W</b>	<b>{0} cannot list the versions of {1}.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
<b>POP.003.0048W</b>	<b>{0} cannot add to versioning {1}.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
<b>POP.003.0049</b>	<b>{0} cannot remove from versioning {1}.</b>
<b>Explanation</b>	An attempt was made to remove a version from version control that failed a permissions check
<b>Action</b>	Verify that the current user has sufficient permissions
<b>POP.003.0050W</b>	<b>{0} is checked out by {1}.</b>
<b>Explanation</b>	The item is already checked out.
<b>Action</b>	Wait until the item is checked in and before trying to check out.

---

<b>POP.003.0051W</b>	<b>{0} cannot set the current version of {1}.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
<b>POP.003.0052W</b>	<b>{0} cannot publish a version of {1}.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
<b>POP.003.0053W</b>	<b>{0} cannot check out {1}.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
<b>POP.003.0054W</b>	<b>{0} is not checked out.</b>
<b>Explanation</b>	You cannot check the item in because it is not checked out.
<b>Action</b>	Do not attempt to check in an item that was not checked out.
<b>POP.003.0055W</b>	<b>{0} cannot check in {1}.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
<b>POP.003.0056W</b>	<b>{0} cannot undo the check out of {1}.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
<b>POP.003.0057E</b>	<b>Source branch is not found: "{0}".</b>
<b>Explanation</b>	The server cannot find a source version branch for this object.
<b>Action</b>	Do not try to add this object to version control.

<b>POP.003.0058</b>	<b>Destination branch is not found: "{0}".</b>
<b>Explanation</b>	Version control system was unable to create a new branch required to complete the add to versioning command.
<b>Action</b>	Check the logs for additional information such as out of disk space.
<b>POP.003.0059W</b>	<b>{0} cannot be added to versioning because parent is null.</b>
<b>Explanation</b>	The item is invalid because it does not have a parent.
<b>Action</b>	Use the local item menu to delete the item.
<b>POP.003.0060W</b>	<b>Not initialized: call init(PageData) first.</b>
<b>Explanation</b>	An internal error has occurred.
<b>Action</b>	Try the operation again.
<b>POP.003.0061W</b>	<b>Column must be contained by a row.</b>
<b>Explanation</b>	The page data xml is not valid. The column element must reside inside a row element.
<b>Action</b>	If you are using My webMethods Server when you got this message, the My webMethods Server page data has been corrupted. Try editing and then saving the page. If you cannot load the page into the page editor you need to delete the page and then recreate it.
<b>POP.003.0062E</b>	<b>Property must be contained by a portlet.</b>
<b>Explanation</b>	The page data xml is not valid. The property element must be inside portlet element.
<b>Action</b>	If you are using My webMethods Server when you got this message, the My webMethods Server page data has been corrupted. Try to edit and then save the page. If you cannot load the page into the page editor you need to delete the page and then recreate it.
<b>POP.003.0063E</b>	<b>Portlet must contain 'uri' attribute.</b>
<b>Explanation</b>	The page data xml file is not valid. The portlet definition does not have an URI attribute.
<b>Action</b>	If you are using My webMethods Server when you got this message, the My webMethods Server page data has been corrupted. Try to edit and then save the page. If you cannot load the page into the page editor you need to delete the page and then recreate it.

---

<b>POP.003.0064W</b>	<b>Property must contain 'name' attribute.</b>
<b>Explanation</b>	The page data xml is not valid. The property element must have a name attribute.
<b>Action</b>	If you are using My webMethods Server when you got this message, the My webMethods Server page data has been corrupted. Try to edit and then save the page. If you cannot load the page into the page editor you need to delete the page and then recreate it.
<b>POP.003.0065E</b>	<b>Wiring must be contained by a portlet.</b>
<b>Explanation</b>	The page data xml is not valid. The property element must reside inside the portlet element.
<b>Action</b>	If you are using My webMethods Server when you got this message, the My webMethods Server page data has been corrupted. Try to edit and then save the page. If you cannot load the page into the page editor you need to delete the page and then recreate it.
<b>POP.003.0066W</b>	<b>Wiring must contain 'name' attribute.</b>
<b>Explanation</b>	The page data xml is not valid. The wiring element must have a name attribute.
<b>Action</b>	If you are using My webMethods Server when you got this message, the My webMethods Server page data has been corrupted. Try to edit and then save the page. If you cannot load the page into the page editor you need to delete the page and then recreate it.
<b>POP.003.0067E</b>	<b>Wiring must contain 'portlet' attribute.</b>
<b>Explanation</b>	The page data xml file is not valid. The wiring definition does not have a portlet attribute.
<b>Action</b>	If you are using My webMethods Server when you got this message, the My webMethods Server page data has been corrupted. Try to edit and then save the page. If you cannot load the page into the page editor you need to delete the page and then recreate it.
<b>POP.003.0069E</b>	<b>The content service "{0}" is not available. Please contact the My webMethods Server Administrator.</b>
<b>Explanation</b>	The server failed to update the contents of a file that was saved to My webMethods Server.
<b>Action</b>	Verify that the location for the My webMethods Server content repository exists.

<b>POP.003.0070</b>	<b>"{0}" is not editable as it does not exist in a sandbox.</b>
<b>Explanation</b>	An invalid attempt to check in a versioned item was made.
<b>Action</b>	Check out a new version and the the item check in.
<b>POP.003.0071E</b>	<b>Cannot lookup install service: "{0}".</b>
<b>Explanation</b>	The server cannot find the install service for this component.
<b>Action</b>	The component is not supported.
<b>POP.003.0072E</b>	<b>ComponentUri is not a thingID: "{0}".</b>
<b>Explanation</b>	The server cannot determine the location of the installed component based on the passed URI.
<b>Action</b>	Correct the calling code to specify a thingID as the componentUri parameter of the uninstallComponent command.
<b>POP.003.0073E</b>	<b>{0} cannot install component.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
<b>POP.003.0074W</b>	<b>{0} cannot read search service.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
<b>POP.003.0075</b>	<b>{0} cannot set access entries on {1}.</b>
<b>Explanation</b>	An attempt was made to set permissions which failed a permissions check
<b>Action</b>	Ensure the current user has sufficient permissions to edit the permissions on the current object
<b>POP.003.0076W</b>	<b>{0} cannot remove access entries from {1}.</b>
<b>Explanation</b>	The specified user cannot remove entries from the access control list of the specified item.
<b>Action</b>	Grant the user the rights to perform the operation, or have the operation performed by a different user with permission to change the access control list of the target item.

---

<b>POP.003.0077W</b>	<b>{0} cannot set the authentication scheme of {1}.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
<b>POP.003.0078W</b>	<b>{0} cannot set the owner of {1}.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
<b>POP.003.0079E</b>	<b>Internal error. Access right lengths do not match.</b>
<b>Explanation</b>	Internal error. A database API inconsistency exists.
<b>Action</b>	Use the Manage Components portlet to edit permissions for this My webMethods Server object.
<b>POP.003.0080W</b>	<b>No auth scheme for auth Level: "{0}".</b>
<b>Explanation</b>	The authentication scheme might not be installed yet, or the specified authentication level is not valid.
<b>Action</b>	Install the missing authentication scheme <code>wm_&lt;schema&gt;Auth.cdp</code> component or correct the <code>authLevel</code> attribute value of your custom <code>xmlImport.xml</code> file.
<b>POP.003.0081E</b>	<b>No implementation for auth scheme: "{0}".</b>
<b>Explanation</b>	The authentication scheme for the target My webMethods Server item is invalid.
<b>Action</b>	Use the Permissions page to set the authentication scheme for the item to one of the installed authentication schemes.
<b>POP.003.0082W</b>	<b>{0} cannot list the contents of {1}.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
<b>POP.003.0083W</b>	<b>{0} cannot add an item to {1}.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

<b>POP.003.0084W</b>	<b>{0} cannot add a shortcut to {1}.</b>
<b>Explanation</b>	Most likely user does not have appropriate access rights.E145
<b>Action</b>	Give the user access rights.
<b>POP.003.0085W</b>	<b>{0} cannot remove an item from {1}.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open Permissions portlet to give the user access rights.
<b>POP.003.0086W</b>	<b>{0} cannot remove a shortcut from {1}.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
<b>POP.003.0087</b>	<b>You cannot copy this container into a descendant of itself.</b>
<b>Explanation</b>	A paste operation was attempted inside the source container.
<b>Action</b>	Paste the clipboard contents into an external container.
<b>POP.003.0088W</b>	<b>You cannot move this container into a descendant of itself.</b>
<b>Explanation</b>	The folder cannot move into one of its subfolders.
<b>Action</b>	If you need to move the folder, do not attempt to move it into a subfolder of itself.
<b>POP.003.0090W</b>	<b>{0} cannot contain a duplicate name.</b>
<b>Explanation</b>	The folder or page cannot have items with duplicate names.
<b>Action</b>	When naming items in a folder, make sure each item has a name that is unique within the folder.
<b>POP.003.0091E</b>	<b>Unable to create xtype with null name: "{0}".</b>
<b>Explanation</b>	The xtype id passed into the createChild command is not valid.
<b>Action</b>	Pass a valid xtype id parameter value. The valid values are listed in the tbIXTypes tables.

---

<b>POP.003.0092W</b>	<b>{0} is a reserved folder and cannot be modified.</b>
<b>Explanation</b>	The folder is a system folder and cannot be modified.
<b>Action</b>	Do not try to modify a system folder.
<b>POP.003.0093W</b>	<b>You cannot move a reserved item.</b>
<b>Explanation</b>	The item is reserved and cannot be moved.
<b>Action</b>	Do not attempt to move reserved items.
<b>POP.003.0094W</b>	<b>{0} is a reserved folder and can not be versioned.</b>
<b>Explanation</b>	The folder cannot be added to the version control because it is a special folder type.
<b>Action</b>	Do not try to add this folder to version control.
<b>POP.003.0095W</b>	<b>{0} cannot change the columns of {1}.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
<b>POP.003.0096</b>	<b>{0} cannot move portlet {1}.</b>
<b>Explanation</b>	An attempt to move a portlet failed a permissions check
<b>Action</b>	Verify that the current user has sufficient permissions
<b>POP.003.0097W</b>	<b>{0} cannot minimize portlet {1}.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
<b>POP.003.0099W</b>	<b>{0} cannot view this item.</b>
<b>Explanation</b>	The user attempted to view an item but does not have permission to see it.
<b>Action</b>	The My webMethods Server administrator should use the Manage Components portlet to edit permissions for this My webMethods Server object.

<b>POP.003.0102W</b>	<b>Unable to locate: "{0}".</b>
<b>Explanation</b>	The server cannot find the user in the directory.
<b>Action</b>	The user might have been removed from the directory. Determine if this user belongs in the directory.
<b>POP.003.0103W</b>	<b>Unable to locate: "{0}" invalid type.</b>
<b>Explanation</b>	The directory might be corrupted or improperly configured.
<b>Action</b>	Check the Directory Service Administration portlet to verify that the directory service is properly configured and functional.
<b>POP.003.0104W</b>	<b>{0} cannot modify user.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
<b>POP.003.0105W</b>	<b>Cannot modify attribute on principal, {0} not found.</b>
<b>Explanation</b>	The server cannot find the user in the directory.
<b>Action</b>	The user might have been removed from the directory. Determine if this user belongs in the directory.
<b>POP.003.0106W</b>	<b>Cannot set email address on principal, email address attribute not configured properly.</b>
<b>Explanation</b>	The email attribute is not configured for this user directory.
<b>Action</b>	Update the directory configuration in Directory Service Administration portlet to specify an email attribute name and try again.
<b>POP.003.0107W</b>	<b>{0} cannot create an alias.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
<b>POP.003.0108W</b>	<b>Alias not found: "{0}".</b>
<b>Explanation</b>	An attempt was made to remove an alias that does not exist.
<b>Action</b>	Verify that the remove alias call uses an existing alias name.

---

<b>POP.003.0109W</b>	<b>{0} cannot delete the "{2}" alias.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
<b>POP.003.0110E</b>	<b>Internal ScheduleMechanics error.</b>
<b>Explanation</b>	The paging cookie is invalid.
<b>Action</b>	Close the browser, then open it again, and retry the action.
<b>POP.003.0111W</b>	<b>{0} cannot view the subscription of {1}.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
<b>POP.003.0112W</b>	<b>{0} cannot list the subscriptions to {1}.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
<b>POP.003.0113W</b>	<b>{0} cannot edit the subscription to {1}.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
<b>POP.003.0115W</b>	<b>Cannot create cookie for URI: "{0}".</b>
<b>Explanation</b>	The system directory or the database is corrupted.
<b>Action</b>	Restore the underlying system user directory content from a backup or do so manually. In the case of LDAPd, you can reinstall the LDAPd server using the webMethods Installer.
<b>POP.003.0116W</b>	<b>User page size must be &gt;= 0 (zero indicates default).</b>
<b>Explanation</b>	The page size cannot be negative.
<b>Action</b>	Correct the calling code to pass the pageSize parameter as a positive number.

<b>POP.003.0117W</b>	<b>Cannot set password on user, user not found: "{0}".</b>
<b>Explanation</b>	The system directory or the database is corrupted.
<b>Action</b>	Restore the underlying system user directory content from a backup or do so manually. In the case of LDAPd, you can reinstall the LDAPd server using the webMethods Installer.
<b>POP.003.0118E</b>	<b>Cannot get roles for user, user not found: "{0}".</b>
<b>Explanation</b>	The server cannot find the user in the directory.
<b>Action</b>	The user might have been removed from the directory. Determine if this user belongs in the directory.
<b>POP.003.0119E</b>	<b>Unable to locate mechanics: "{0}".</b>
<b>Explanation</b>	Mechanics were not found for the given name or URI.
<b>Action</b>	If the error is related to a standard portlet, try to redeploy the portlet using the Install Administration portlet. If you have created a custom portlet, you need to correct the calling code in CAF and redeploy the portlet.
<b>POP.003.0120W</b>	<b>{0} cannot cut {1}.</b>
<b>Explanation</b>	The user does not have appropriate access rights.
<b>Action</b>	Use the item's Permissions local menu item to open the Permissions portlet to give the user access rights.
<b>POP.003.0121W</b>	<b>{0} cannot cut {1}.</b>
<b>Explanation</b>	The user does not have the appropriate access rights.
<b>Action</b>	Use the item's Permissions local menu item to open the Permissions portlet to give the user access rights.
<b>POP.003.0122W</b>	<b>A datasource named "{0}" already exists.</b>
<b>Explanation</b>	An attempt was made to register a SQL datasource with a datasource name that has already been used for another datasource.
<b>Action</b>	Use a different name for the new datasource.

---

<b>POP.003.0123W</b>	<b>You cannot copy a reserved item.</b>
<b>Explanation</b>	The item is reserved.
<b>Action</b>	Do not attempt to copy a reserved item.
<b>POP.003.0124</b>	<b>{0} cannot access datasource.</b>
<b>Explanation</b>	An attempt to issue a SQL statement was made with an invalid argument for the datasource
<b>Action</b>	Ensure that the datasource is registered
<b>POP.003.0126W</b>	<b>compression not allowed.</b>
<b>Explanation</b>	The presentation cache content cannot be compressed.
<b>Action</b>	Correct the calling code to not call PresentationCacheContent.setCompressed(true).
<b>POP.003.0129W</b>	<b>Cannot initialize principal, invalid type: "{0}".</b>
<b>Explanation</b>	The directory might be corrupted or improperly configured
<b>Action</b>	Check the Directory Service Administration portlet to verify that the directory service is properly configured and functional.
<b>POP.003.0130E</b>	<b>Error in thread resyncing group properties [domain]: "{0}".</b>
<b>Explanation</b>	The server failed to refresh the metadata for a Group from the LDAP server.
<b>Action</b>	Validate the connectivity to the LDAP server using an LDAP browser tool, the directory native Administration UI, or other tools.
<b>POP.003.0132</b>	<b>"{0}" depends on "{1}".</b>
<b>Explanation</b>	During the wiring resolution phase an error occurred
<b>Action</b>	Check the wiring configuration for the portlets on the current page.
<b>POP.003.0134W</b>	<b>{0}'s account has been disabled.</b>
<b>Explanation</b>	The user account has been disabled.
<b>Action</b>	Enable the user account in the underlying user directory. Use the directory Administration UI or other tools for that purpose.

**POP.003.0135W**      **Unable to find the content location for: "{0}". Content service is not available or out of sync with the database. Please try again. If the problem persists, contact the My webMethods Server Administrator.**

**Explanation**      The content store is corrupted.

**Action**      Delete the item and try again.

**POP.003.0136W**      **Cannot install component "{0}" because it requires "{1}" to be installed first.**

**Explanation**      The component being installed depends on another component that is not yet installed and not listed in the items to install list.

**Action**      Install the required components before attempting to install the component that raised the error.

**POP.003.0137W**      **Unable to create with unknown type: "{0}".**

**Explanation**      Cannot create an item because the xtype is invalid.

**Action**      Pass a valid xtype parameter to createChild command. All valid xtypes are found in the XTypes system folder in the My webMethods Server UI.

**POP.003.0139W**      **Component "{0}" installation failed. System state is recovered by uninstalling the component. Original error: {1}**

**Explanation**      The installation of the component failed.

**Action**      Uninstall the component to recover the system state. Look at the install.log file for details of why the installation failed.

**POP.003.0140E**      **Component "{0}" installation failed. System state is recovered by reinstalling the previous version of the component. Original error: {1}"**

**Explanation**      The installation of the component failed.

**Action**      Uninstall the component to recover the system state. Look at the install.log file for details of why the installation failed.

**POP.003.0141**      **The username/password you entered is invalid.**

**Explanation**      The login attempt failed.

**Action**      Verify that the username and password are correct.

---

<b>POP.003.0142</b>	<b>Invalid principal type: "{0}".</b>
<b>Explanation</b>	An attempt to modify a group's membership failed.
<b>Action</b>	Verify that the group exists prior to attempting to modify the group.
<b>POP.003.0143</b>	<b>{0} cannot set policy on {1}.</b>
<b>Explanation</b>	An attempt was made to add an item to a Security Realm failed a permissions check.
<b>Action</b>	Verify that the current user has sufficient permissions.
<b>POP.003.0144</b>	<b>{0} cannot remove policy from {1}.</b>
<b>Explanation</b>	An attempt to remove an item from a Security Realm failed a permissions check.
<b>Action</b>	Verify that the current user has sufficient permissions.
<b>POP.003.0146</b>	<b>{0} cannot modify the members of group: {1}</b>
<b>Explanation</b>	An attempt to modify the members of group failed a permissions check.
<b>Action</b>	Verify that the current user has sufficient permissions.
<b>POP.003.0147</b>	<b>{0} cannot modify the membership of principal: {1}</b>
<b>Explanation</b>	An attempt to modify the groups and roles a principal belongs to failed a permissions check.
<b>Action</b>	Verify that the current user has sufficient permissions.
<b>POP.003.0148</b>	<b>Command Error, Parent is not a container. Class= {0}</b>
<b>Explanation</b>	An attempt was made to create a new item inside a parent that is not a valid container.
<b>Action</b>	Ensure that the attempt is made to create a child inside a valid container.
<b>POP.003.0150</b>	<b>{0} cannot create users or groups in the "{1}" directory service."</b>
<b>Explanation</b>	An attempt was made to create a user or group failed a permissions check.
<b>Action</b>	Verify that the current user has sufficient permissions.
<b>POP.003.0151</b>	<b>{0} cannot modify the members of role: {1}</b>
<b>Explanation</b>	An attempt to modify the members of a role failed a permissions check.
<b>Action</b>	Verify that the current user has sufficient permissions.

<b>POP.003.0153</b>	<b>{0} cannot add a {2} to {1}.</b>
<b>Explanation</b>	An attempt to create a new child failed a permissions check.
<b>Action</b>	Verify that the current user has sufficient permissions.
<b>POP.003.0154</b>	<b>{0} cannot remove a {2} from {1}.</b>
<b>Explanation</b>	An attempt to remove a child from a folder failed a permissions check.
<b>Action</b>	Verify that the current user has sufficient permissions.
<b>POP.003.0155</b>	<b>My webMethods Server webspace {0} should have an valid alias</b>
<b>Explanation</b>	Webspaces must have a valid name in order to be created.
<b>Action</b>	Ensure that a valid alias name is supplied.
<b>POP.003.0156</b>	<b>Unclosed skin property: "{1}". Please close with "].</b>
<b>Explanation</b>	During the dynamic skin property resolution, a malformed skin property was referenced.
<b>Action</b>	Ensure that the javaScript file with the dynamic skin property is properly formed.
<b>POP.003.0160E</b>	<b>Failed to resolve wiring for property "{0}"</b>
<b>Explanation</b>	Wiring cannot be resolved for the <propertyName> property of a portlet instance.
<b>Action</b>	Open the Wiring settings for this portlet, make sure the source portlet and its property are still available. Adjust the wiring settings if necessary.
<b>POP.003.0162</b>	<b>A group cannot be a member of itself.</b>
<b>Explanation</b>	A malformed attempt to modify a group was made.
<b>Action</b>	Do not set a group as a member of itself.
<b>POP.003.0163</b>	<b>Invalid username or Password.</b>
<b>Explanation</b>	The username or password is invalid.
<b>Action</b>	Specify a valid username and password.
<b>POP.003.0164</b>	<b>{0} cannot copy {1}.</b>
<b>Explanation</b>	The user does not have the privilege to copy.
<b>Action</b>	Please contact the system administrator if you need this privilege.

---

<b>POP.003.0165</b>	<b>{0} cannot clone {1}.</b>
<b>Explanation</b>	The user does not have the privilege to clone.
<b>Action</b>	Please contact the system administrator if you need this privilege.
<b>POP.003.0166</b>	<b>{0} is a system component. And will not be uninstalled.</b>
<b>Explanation</b>	System components cannot be uninstalled.
<b>Action</b>	Do not attempt to uninstall a system component.
<b>POP.003.0167</b>	<b>Too many failed login attempts for: "{0}". You may try to login again in {1} minutes.</b>
<b>Explanation</b>	The user is not allowed to login because of too many failed login attempts. The user must wait a specified amount of time before trying again.
<b>Action</b>	Make sure you are using a valid username and password. Contact the system administrator if your existing credentials are not working.
<b>POP.003.0168</b>	<b>Password has expired for: "{0}". Please contact an administrator to reset your password.</b>
<b>Explanation</b>	The user's password has expired.
<b>Action</b>	Contact an administrator to reset your password.
<b>POP.003.0169</b>	<b>{0} is reserved and cannot be used for an alias.</b>
<b>Explanation</b>	The specified name is reserved by the system and cannot be used for an alias name.
<b>Action</b>	Specify a different name as an alias.
<b>POP.003.0171</b>	<b>The uploaded file type is not allowed. The allowed file extensions are: {0}</b>
<b>Explanation</b>	The uploaded file type is not supported by the system.
<b>Action</b>	Be sure to upload only supported file types.
<b>POP.004.0001E</b>	<b>The Resource Bundle for "{0}" was not found.</b>
<b>Explanation</b>	The server cannot load the specified resource bundle class. The bundle is a portlet class that has not been deployed or was deployed in a different portlet.
<b>Action</b>	Use the Portlet Developer to add the resource bundle class to the invoking portlet. Redeploy the portlet.

<b>POP.004.0002E</b>	<b>The Message Key "{0}" was not found in the Resource Bundle "{1}".</b>
<b>Explanation</b>	The resource bundle message key is missing.
<b>Action</b>	Correct the resource bundle to include a resource for the key specified by the error message.
<b>POP.004.0003</b>	<b>There was no Object found for Message Key "{0}".</b>
<b>Explanation</b>	No object was found for the specified message key.
<b>Action</b>	Specify a valid message key.
<b>POP.004.0004E</b>	<b>An error occurred while formatting the Message Key "{0}".</b>
<b>Explanation</b>	The resource bundle message key is missing or the message could not be formatted because its content is invalid.
<b>Action</b>	Correct the resource bundle to include the key specified by the error message, or correct the resource content identified by the key.
<b>POP.004.0005S</b>	<b>Error creating search pools "{0}".</b>
<b>Explanation</b>	The server cannot initialize some search service data structures because an internal portal error occurred.
<b>Action</b>	Use the specific error message details to diagnose the problem.
<b>POP.004.0006S</b>	<b>Invalid cache ID: "{0}".</b>
<b>Explanation</b>	The server cannot initialize an invalid cache.
<b>Action</b>	Correct the thing cache configuration in the cache.xml My webMethods Server configuration file. A valid entry is: <code>&lt;cache name="Thing Cache" class="com.webmethods.portal.service.cache.impl.TransientCache" maxSize="10000" isClustered="true" ID= "1" enabled="true"/&gt;</code>
<b>POP.004.0008E</b>	<b>Unable to initialize content service component: "{0}".</b>
<b>Explanation</b>	Cannot initialize the content service.
<b>Action</b>	If you cannot reconfigure the offending content service. Call Software AG Global Support for a reset directive.

<b>POP.004.0010E</b>	<b>No provider for directory [name, type] : [{0}, {1}]</b>
<b>Explanation</b>	The server cannot initialize the specified directory service because the directory service is an unknown type.
<b>Action</b>	Correct the directoryConfig.xml My webMethods Server configuration file to remove the Service element with the name attribute value specified by the error message.
<b>POP.004.0011E</b>	<b>Invalid XML for directory, no DirectoryConfig element found: "{0}".</b>
<b>Explanation</b>	The server cannot initialize the directory service because its configuration data is corrupt.
<b>Action</b>	Correct the directoryConfig.xml My webMethods Server configuration file to remove the Service element with the name attribute value specified by the error message.
<b>POP.004.0012S</b>	<b>Unable to construct component data for directory: "{0}".</b>
<b>Explanation</b>	The server cannot initialize the directory service.
<b>Action</b>	Use the Directory Services Administration portlet to create a new directory service and then delete the old one.
<b>POP.004.0013S</b>	<b>Alias Cache not found.</b>
<b>Explanation</b>	The server cannot initialize the alias service because the alias cache is not configured.
<b>Action</b>	Add the following entry to the cache.xml My webMethods Server configuration file: <pre>&lt;cache name="AliasCache" class="com.webmethods.portal.service.cache.impl.AliasCache" maxSize="5000" isClustered="true" ID="2" enabled="true"/&gt;</pre>
<b>POP.004.0014E</b>	<b>Can't create alias cache.</b>
<b>Explanation</b>	The server cannot initialize the metadata service because the required cache was not located.
<b>Action</b>	Correct the thing cache configuration in the cache.xml My webMethods Server configuration file. A valid entry is: <pre>&lt;cache name="Thing Cache" class="com.webmethods.portal.service.cache.impl.TransientCache" maxSize="10000" isClustered="true" ID= "1" enabled="true"/&gt;</pre>
<b>POP.004.0015E</b>	<b>Unable to create MetaContext: "{0}".</b>
<b>Explanation</b>	The server cannot create a connection to metadata datasource because the configuration information for the datasource was not retrieved.
<b>Action</b>	Correct the metaContext.xml My webMethods Server configuration file to remove the Context element with the connection attribute value specified by the error message.

<b>POP.004.0016S</b>	<b>Can't get schedule list: "{0}".</b>
<b>Explanation</b>	The server was unable to list all of the My webMethods Server schedules.
<b>Action</b>	Verify that the database has been properly configured and that the My webMethods Server schema was properly installed by paying close attention to the installation process.
<b>POP.004.0017S</b>	<b>Thing Cache not found.</b>
<b>Explanation</b>	The server cannot initialize the metadata service because the required cache was not located.
<b>Action</b>	Correct the thing cache configuration in the cache.xml My webMethods Server configuration file. A valid entry is: <code>&lt;cache name="Thing Cache" class="com.webmethods.portal.service.cache.impl.TransientCache" maxSize="10000" isClustered="true" ID= "1" enabled="true"/&gt;</code>
<b>POP.004.0018S</b>	<b>Can't create thing cache.</b>
<b>Explanation</b>	The server cannot initialize the metadata service because the thing cache configuration is invalid.
<b>Action</b>	Correct the thing cache configuration in the cache.xml My webMethods Server configuration file. A valid entry is: <code>&lt;cache name="Thing Cache" class="com.webmethods.portal.service.cache.impl.TransientCache" maxSize="10000" isClustered="true" ID= "1" enabled="true"/&gt;</code>
<b>POP.004.0019S</b>	<b>No queue specified.</b>
<b>Explanation</b>	The server cannot initialize the e-mail notification deliverer because the notification queue name was not specified in the deliverer's configuration.
<b>Action</b>	Specify the queue name in the queue attribute of the delivery initializers in the phaseProvider.xml My webMethods Server configuration file.
<b>POP.004.0020S</b>	<b>Unexpected exception: "{0}".</b>
<b>Explanation</b>	The server cannot initialize the e-mail notification deliverer because an unexpected error occurred.
<b>Action</b>	Check the <code>_problems_.log</code> in the My webMethods Server current logging directory for more specific error information.

---

<b>POP.004.0021S</b>	<b>Invalid ConnectionManager config file.</b>
<b>Explanation</b>	The server cannot initialize the datasource connection manager because it cannot acquire its configuration file.
<b>Action</b>	Validate that the portal.properties My webMethods Server configuration file contains the following entry: 'sled.connectionmanager.config=config;/db.xml'.
<b>POP.004.0022E</b>	<b>Could not acquire meta context : version service name: "{0}".</b>
<b>Explanation</b>	The server cannot acquire the metadata datasource by name because the specified name is unrecognized.
<b>Action</b>	Restart the server where My webMethods Server is installed.
<b>POP.004.0023E</b>	<b>Could not find root folder of version services.</b>
<b>Explanation</b>	The root folder of the version service does not exist.
<b>Action</b>	Reinstall the version service using the My webMethods Server Configurator.
<b>POP.004.0024S</b>	<b>Could not create service thing : version service name: "{0}".</b>
<b>Explanation</b>	The server cannot initialize the version service.
<b>Action</b>	Verify that all of the versioning components have been deployed. This includes the version service and version portlet which can be located in the system portal folders.
<b>POP.004.0027E</b>	<b>Ftp login failed for user [{0}] : {1}.</b>
<b>Explanation</b>	The server cannot login to the remote FTP server.
<b>Action</b>	Verify that the credentials are valid for the FTP connection service, and that the network connectivity is valid.
<b>POP.004.0028E</b>	<b>Ftp Connection Error: Access Denied</b>
<b>Explanation</b>	The server cannot connect to the remote FTP server.
<b>Action</b>	Validate that the credentials and configuration are valid for the FTP connection service, using the Content Service Admin portlet. Verify that the network connectivity is valid.
<b>POP.004.0029E</b>	<b>Ftp Connection Error: "{0}".</b>
<b>Explanation</b>	The server cannot connect to the remote FTP server.
<b>Action</b>	Validate that the credentials and configuration are valid for the FTP connection service, using the Content Service Admin portlet. Verify that the network connectivity is valid.

<b>POP.004.0032E</b>	<b>Invalid ID's in createThing.</b>
<b>Explanation</b>	The server was unable to publish a new My webMethods Server object.
<b>Action</b>	Correct the invoking method to pass in a valid owner and parent ID parameters.
<b>POP.004.0033E</b>	<b>Database is busy or unavailable.</b>
<b>Explanation</b>	The server cannot execute the SQL command because the database is not responding to My webMethods Server in a timely fashion. The database could be experiencing too much load preventing it from responding to My webMethods Server and the server might not be able to access the database's server or port. In addition, the database might not be running.
<b>Action</b>	Verify that the database is running, and is not experiencing heavy load. Verify that the database has an adequate number of connection threads available. Verify that the machine on which the My webMethods Server is running can access the datasource's configured host name and port.
<b>POP.004.0034E</b>	<b>Datasource Mismatch, passed ({0}) to API on ({1}).</b>
<b>Explanation</b>	The metadata datasource cannot operate on a resource from a different datasource.
<b>Action</b>	Correct the invoking source code to use a metadata service to operate on a resource that belongs to the service's datasource. Consult the API documentation for more information.
<b>POP.004.0035E</b>	<b>Invalid URI</b>
<b>Explanation</b>	The server cannot resolve the datasource for a metadata My webMethods Server identifier.
<b>Action</b>	The identifier that caused this error does not identify a resource, do not use it to identify a resource.
<b>POP.004.0036E</b>	<b>Invalid schedule info: interval "{0}", timeAt "{1}": Unable to parse 'timeAt' and/or 'interval'</b>
<b>Explanation</b>	An attempt to create or modify a schedule has failed because of invalid schedule parameters.
<b>Action</b>	Correct the invoking code to pass valid schedule parameters. Valid interval and timeAt parameter values are the time values formatted according to the ISO 8601 date/time format.

<b>POP.004.0037E</b>	<b>Invalid schedule info: interval "{0}", timeAt "{1}": 'timeAt' overlaps with 'interval'</b>
<b>Explanation</b>	The server cannot execute the scheduled event because the time to wait (timeAt), after the interval setting but before executing the event, is approximately as long as the interval itself.
<b>Action</b>	Edit the schedule using the Event Administration portlet, in the Portal Configuration category in the My webMethods Server Admin Dashboard, so the interval is longer than the On/At time-to-wait, such that weeks instead of days, hours instead of minutes.
<b>POP.004.0038E</b>	<b>Unknown thing type: {0}</b>
<b>Explanation</b>	The server was unable to identify the base type of the metadata service object.
<b>Action</b>	Verify that the portlet was built using the My webMethods Server.
<b>POP.004.0039E</b>	<b>Unable to unregister XType: {0}</b>
<b>Explanation</b>	The xtype was not registered or there are published instances of that xtype.
<b>Action</b>	Ensure that all instances of that xtype have been deleted prior to unregistering. These types are found by using the Publish History reporting portlet.
<b>POP.004.0040E</b>	<b>Can't convert to xtype of different base type</b>
<b>Explanation</b>	Xtype conversion is unsupported.
<b>Action</b>	Correct the invoking method and do not attempt to modify the xtype parameter.
<b>POP.004.0041E</b>	<b>Invalid Principal.</b>
<b>Explanation</b>	The server cannot modify the access control entry.
<b>Action</b>	Correct the invoking method to specify a principal parameter.
<b>POP.004.0042E</b>	<b>Invalid Ace. Cannot set both granted and denied on the same right.</b>
<b>Explanation</b>	The server cannot set a single access control entry to grant and deny the same access right.
<b>Action</b>	Correct the invoking source code. Consult the API documentation for more information.
<b>POP.004.0043E</b>	<b>Invalid Ace. Unknown right.</b>
<b>Explanation</b>	The server cannot set access control entry with the right bit outside of the defined right bit range, as defined by the access service API.
<b>Action</b>	Correct the invoking source code. Consult the API documentation for more information.

<b>POP.004.0045E</b>	<b>Invalid Ace. Cannot delegate a right not granted.</b>
<b>Explanation</b>	The server cannot modify the access control entry.
<b>Action</b>	Correct the invoking method to include the proper right set parameter.
<b>POP.004.0046</b>	<b>Setting user name is not supported.</b>
<b>Explanation</b>	Internal group and user objects cannot have their name set
<b>Action</b>	Check and correct directory API usage
<b>POP.004.0047E</b>	<b>Cookie is not set in this view.</b>
<b>Explanation</b>	The server cannot display the inbox notifications because a paging cookie was not set.
<b>Action</b>	Log out, log in, and try again.
<b>POP.004.0048E</b>	<b>Unable to load Subscription object. Subscription no longer exists.</b>
<b>Explanation</b>	The server cannot locate the subscription information that triggered the notification.
<b>Action</b>	Delete the notification by locating the offending notification in the My webMethods Server inbox and deleting it.
<b>POP.004.0049E</b>	<b>Unable to load Event.</b>
<b>Explanation</b>	The server cannot load event data because an error occurred in querying the database.
<b>Action</b>	Check the <code>_problems_.log</code> in My webMethods Server current logging directory for more specific error information.
<b>POP.004.0050E</b>	<b>Unable to remove Notification.</b>
<b>Explanation</b>	The server was unable to locate the notification in order to delete it.
<b>Action</b>	Correct the invoking method to specify a valid notification parameter.
<b>POP.004.0051E</b>	<b>Unable to remove Event.</b>
<b>Explanation</b>	The server cannot remove the event item from the database due to a SQL error while executing the stored procedure that performs the removal.
<b>Action</b>	Check the <code>_problems_.log</code> in My webMethods Server current logging directory for more specific error information.

---

<b>POP.004.0052E</b>	<b>Start index beyond end of list.</b>
<b>Explanation</b>	The server cannot list a page of metadata resources because the specified start index of the page is greater than the total number of resources in the list.
<b>Action</b>	Correct the source code that executes the query. Specify a start index that is less than the total number of resources in the list by modifying the start property of the <code>com.webmethods.portal.service.view.IPagingCookie</code> .
<b>POP.004.0053E</b>	<b>Paged before first item.</b>
<b>Explanation</b>	The server cannot list a page of metadata resources because the specified start or end index of the page is less than one.
<b>Action</b>	Correct the source code that executes the query. Specify a start index that is less than the total number of resources in the list by modifying the start or end properties of the <code>com.webmethods.portal.service.view.IPagingCookie</code> .
<b>POP.004.0054E</b>	<b>Invalid end index.</b>
<b>Explanation</b>	The server cannot execute a paged container query because the page-start index is greater than the page-end index.
<b>Action</b>	Correct the source code that executes the query. Specify a start index that is less than the end index by modifying the start and end properties of the <code>com.webmethods.portal.service.view.IPagingCookie</code> .
<b>POP.004.0055E</b>	<b>Invalid sort order for getTreeView.</b>
<b>Explanation</b>	The server cannot sort the tree view's results with the supplied sort parameter.
<b>Action</b>	Correct the invoking code to pass valid sort parameters.
<b>POP.004.0056E</b>	<b>Error saving subscription. No subscription or source information.</b>
<b>Explanation</b>	The server cannot add the subscription because the subscription information is corrupted.
<b>Action</b>	Correct the invoking method to specify a valid subscription parameter.
<b>POP.004.0057E</b>	<b>Error adding subscription. No subscription or source information.</b>
<b>Explanation</b>	The server cannot add the subscription because the subscription information is corrupted.
<b>Action</b>	Correct the invoking method and ensure that the proper parameters are passed.

<b>POP.004.0059</b>	<b>Can't create an archived thing, use deactivate or delete.</b>
<b>Explanation</b>	The archived thing type cannot be created directly. It is created automatically when object is deleted
<b>Action</b>	Check and correct MWS API used when creating new object instance
<b>POP.004.0060</b>	<b>Unable to save Role.</b>
<b>Explanation</b>	A database error occurred when saving role information
<b>Action</b>	Check logs for additional exception details
<b>POP.004.0061E</b>	<b>Unable to load Role.</b>
<b>Explanation</b>	The server cannot load the metadata information for a registered role.
<b>Action</b>	Using the Role Administration portlet, regenerate and configure the role.
<b>POP.004.0062E</b>	<b>Missing results from the database.</b>
<b>Explanation</b>	The server has received invalid results from a stored procedure.
<b>Action</b>	Verify that the database has been properly configured and that the schema was properly installed by paying close attention to the installation process.
<b>POP.004.0063E</b>	<b>Access model not set.</b>
<b>Explanation</b>	The access service cannot evaluate access rights for a user until its access model has been specified.
<b>Action</b>	Correct the portal.properties file in the My webMethods Server config directory so that it has the following line: framework.access.model=restrictive.
<b>POP.004.0064E</b>	<b>Access model is not valid.</b>
<b>Explanation</b>	The server cannot set the access model because the specified model is unknown. The valid model values are 1 (permissive) and 2 (restrictive).
<b>Action</b>	Correct the portal.properties file in the My webMethods Server config directory so that it has the following line: framework.access.model=restrictive.
<b>POP.004.0065E</b>	<b>Serialized object version is different then current version: [version, currentVersion] [{0},{1}]</b>
<b>Explanation</b>	The server cannot read the alias stored in the database because its serialized object version is out of date.
<b>Action</b>	Revert to the previous version of wm-caf-server.jar, and restart the My webMethods Server.

<b>POP.004.0066E</b>	<b>Unknown type: {0}</b>
<b>Explanation</b>	The server cannot initialize the directory search control because the specified query type is unknown.
<b>Action</b>	Correct the code invoking directory search to specify a type of 1 (users) or 2 (groups).
<b>POP.004.0067E</b>	<b>Attempted to set subkey on primary-key only key.</b>
<b>Explanation</b>	The server cannot create the cache key.
<b>Action</b>	Correct the invoking method to include appropriate cache key parameter.
<b>POP.004.0068E</b>	<b>Can't find or create valid cache.</b>
<b>Explanation</b>	The cache update stored procedure cannot resolve the cache identifier.
<b>Action</b>	Correct the invoking source code to provide a cache-key with a valid cacheID. Consult the API documentation for more information.
<b>POP.004.0069E</b>	<b>Cache error: data is not a serializable object</b>
<b>Explanation</b>	The server attempted to cache an object that is not serializable.
<b>Action</b>	Correct the source code that invokes the <code>com.webmethods.portal.service.cache.impl.DBCache.getBytesFromObject()</code> method to pass serializable object.
<b>POP.004.0070E</b>	<b>Invalid connection parameters.</b>
<b>Explanation</b>	The server cannot connect to the remote FTP server.
<b>Action</b>	Verify that the credentials and configuration are valid for the FTP connection service, using the Content Service Admin portlet. Verify that the network connectivity is valid.
<b>POP.004.0071E</b>	<b>Error persisting directory config.</b>
<b>Explanation</b>	The server cannot store the directory configuration modifications.
<b>Action</b>	Use the Directory Services Administration portlet to create a new directory service and then delete the old one.
<b>POP.004.0072E</b>	<b>Cannot lookup non user or group thing based objects : {0}</b>
<b>Explanation</b>	The server cannot look up directory service resources using metadata identifiers unless the resource is a user, group, or role.
<b>Action</b>	The identifier specified by the error message does not identify a directory resource, do not try to use it to identify a directory resource.

<b>POP.004.0073E</b>	<b>Invalid URI, no directory service specified for URI - "{0}"</b>
<b>Explanation</b>	The server cannot locate an invalid directory user.
<b>Action</b>	Use the Directory Service Administration portlet to verify that the directory service is properly configured.
<b>POP.004.0074E</b>	<b>Specified domain in URI not found [domain, uri] -- [{0}, {1}]. This can be due to directory service being disabled or removed</b>
<b>Explanation</b>	The server cannot look up the directory service based on a Portal identifier because the identified directory service does not exist.
<b>Action</b>	This error may have happened because the specified directory service configuration was deleted. Try re-adding the directory service using the Directory Services Administration portlet (in the Portal Configuration category of the Portal Admin Dashboard).
<b>POP.004.0075</b>	<b>Cannot add directory service, service already exists: {0}</b>
<b>Explanation</b>	Directory service name must be unique.
<b>Action</b>	Check and correct directory service name being created.
<b>POP.004.0076E</b>	<b>Error adding new directory service: {0}</b>
<b>Explanation</b>	The server cannot add or update a directory service because of an error in validating or storing the directory service configuration.
<b>Action</b>	Check the <code>_problems_.log</code> in the My webMethods Server current logging directory for more specific error information.
<b>POP.004.0077E</b>	<b>Cannot build URI, unknown type 0</b>
<b>Explanation</b>	The server cannot construct a My webMethods Server identifier for the directory service object because the specified type is not one of user, group, or role.
<b>Action</b>	Correct the source code that invokes the <code>com.webmethods.portal.server.directory.impl.DirectoryTools.constructDirectoryURI()</code> method to specify only either user, group, or role.
<b>POP.004.0078E</b>	<b>Invalid escape character in {0} at position {1}</b>
<b>Explanation</b>	The server was unable to normalize the LDAP DN.
<b>Action</b>	Investigate the original DN and try to remove offending characters if possible.

---

<b>POP.004.0079E</b>	<b>Cannot retrieve most significant attribute; invalid DN: "{0}"</b>
<b>Explanation</b>	The server cannot parse a directory service object DN (the object's LDAP ID), because the DN is invalid.
<b>Action</b>	Supply a valid DN to the <code>com.webmethods.portal.service.directory.impl.jndi.JNDITools</code> class's <code>getMostSignificantAttr()</code> and <code>getMostSignificantAttrSet()</code> methods.
<b>POP.004.0080E</b>	<b>Unable to connect to: {0}</b>
<b>Explanation</b>	The server cannot connect to the remote LDAP directory store.
<b>Action</b>	Verify that the Directory configuration is valid by using the Directory Service Administration portlet.
<b>POP.004.0081E</b>	<b>No user class specified in directory factory config</b>
<b>Explanation</b>	The server cannot store the directory configuration modifications.
<b>Action</b>	Use the Directory Services Administration portlet to create a new directory service and then delete the old one.
<b>POP.004.0082E</b>	<b>No group class specified in directory factory config</b>
<b>Explanation</b>	The server cannot initialize the directory service.
<b>Action</b>	Verify that the Directory service is properly configured by using the Directory Service Administration portlet.
<b>POP.004.0083E</b>	<b>Unable to wrap object. Unkown type: {0}</b>
<b>Explanation</b>	The server was unable to read an LDAP entry.
<b>Action</b>	Use the Directory Services Administration portlet to verify that the Directory configuration is valid.
<b>POP.004.0084</b>	<b>Unable to wrap LDAP object: {0}</b>
<b>Explanation</b>	There was an error fetching LDAP object properties
<b>Action</b>	Check MWS logs for additional exception details
<b>POP.004.0085E</b>	<b>Error setting attribute [name, value, action, message] - [{0}, {1}, {2}, {3}]</b>
<b>Explanation</b>	The server cannot modify the LDAP attribute.
<b>Action</b>	Verify that the connection to the LDAP directory store has adequate privileges to modify LDAP entries. Use your LDAP vendor's administration tool.

- POP.004.0086E**      **No response controls for directory: {0}**  
**Explanation**      The server cannot update the directory search control.  
**Action**              Start a new search.
- POP.004.0087E**      **Cannot page backward**  
**Explanation**      The server cannot page directory search control backwards because the control is at the first page of results.  
**Action**              Correct the source code invoking the directory search to check if the search has previous results before trying to page back to previous results. You can determine if a search has previous results by inspecting the value of the hasPrevious property of the com.webmethods.portal.service.view.IPagingCookie that you used to perform the search.
- POP.004.0088E**      **Cannot page forward**  
**Explanation**      The server cannot page the directory search control forward because the search has no more results.  
**Action**              Correct the source code invoking the directory search to check if the search has more results before trying to page forward. You can determine if a search has more results by inspecting the value of the hasNext property of the com.webmethods.portal.service.view.IPagingCookie that you used to perform the search.
- POP.004.0089E**      **Unable to retrieve user list**  
**Explanation**      The server cannot list the users of a directory service, there might be a problem connecting to the directory service.  
**Action**              If the directory service was recently configured directory service, go back to the My webMethods Server Admin Dashboard, and double-check the configuration using the Directory Service Administration portlet. Verify that the LDAP or ADSI server that connects to the directory service is up and running properly. Verify that the server the hosts My webMethods Server is able to connect to the LDAP or ADSI server using the hostname and port specified in the directory service's configuration.
- POP.004.0090E**      **Unable to lookup user {0}**  
**Explanation**      The server cannot locate the specified user.  
**Action**              Use the User and Group Management portlet to verify that the group exists in the LDAP directory store.

---

<b>POP.004.0091E</b>	<b>Invalid username or password</b>
<b>Explanation</b>	You have supplied invalid credentials.
<b>Action</b>	Try authenticating again with proper user name and password.
<b>POP.004.0092E</b>	<b>Could not lookup DN {0}</b>
<b>Explanation</b>	The server cannot look up a user or group by directory DN, the user or group's LDAP ID, because an error occurred while querying the directory store.
<b>Action</b>	Check the <code>_problems_.log</code> in My webMethods Server current logging directory for more specific error information.
<b>POP.004.0093E</b>	<b>Error looking up group {0}</b>
<b>Explanation</b>	The server cannot locate the specified group.
<b>Action</b>	Verify that the Directory service is configured by using the Directory Service Administration portlet.
<b>POP.004.0094E</b>	<b>Unable to perform search : {0}</b>
<b>Explanation</b>	An unknown error occurred while performing an LDAP directory search.
<b>Action</b>	Correct the invoking method to specify a valid query parameter.
<b>POP.004.0095E</b>	<b>Error getting memberships</b>
<b>Explanation</b>	The server cannot get membership information from the LDAP directory store.
<b>Action</b>	Verify that the Directory configuration is valid by using the Directory Service Administration portlet.
<b>POP.004.0096E</b>	<b>Unable to modify password of user {0} because the supplied old password is incorrect.</b>
<b>Explanation</b>	An attempt was made to change a user's password without supplying the user's existing password.
<b>Action</b>	Supply the correct existing password.
<b>POP.004.0097E</b>	<b>INSTALL is not supported operation for: {0}</b>
<b>Explanation</b>	Installation of the deployable object has failed.
<b>Action</b>	The deployable object does not have any installation code associated with its file extension. Do not attempt to deploy an unsupported type to the My webMethods Server.

<b>POP.004.0098E</b>	<b>UNINSTALL is not supported operation for: {0}</b>
<b>Explanation</b>	The server cannot uninstall the specified type of component.
<b>Action</b>	The specified component was not uninstalled; try again.
<b>POP.004.0100E</b>	<b>Component file not found: {0}</b>
<b>Explanation</b>	The server cannot install the component the component was not found at the specified location.
<b>Action</b>	Specify the correct location. If you are installing a component using the Install Administration portlet, select a valid location using the portlet's Browse button.
<b>POP.004.0101E</b>	<b>Cannot set properties for installer: {0}</b>
<b>Explanation</b>	The server cannot set install services because an internal error occurred.
<b>Action</b>	Check the <code>_problems_.log</code> in My webMethods Server current logging directory for more specific error information.
<b>POP.004.0102E</b>	<b>Script file not found: {0}</b>
<b>Explanation</b>	The server cannot execute a portlet deployment script.
<b>Action</b>	Using My webMethods Server, rebuild and redeploy the portlet.
<b>POP.004.0103E</b>	<b>Install script finished with {0} error(s). Please look at the install.log for details</b>
<b>Explanation</b>	An error occurred while installing or uninstalling a deployable component.
<b>Action</b>	Examine the logs, and try again. Look for the information specific to the deployed component in the <code>install.log</code> file.
<b>POP.004.0104E</b>	<b>Error installing/uninstalling component</b>
<b>Explanation</b>	An error occurred while installing or uninstalling a deployable component.
<b>Action</b>	Examine the logs, and optionally try again. Look for the information specific to the deployed component in the <code>install.log</code> file.
<b>POP.004.0105E</b>	<b>Failed to initialize LoggingCollector: {0}</b>
<b>Explanation</b>	The server cannot initialize logging over the JMS provider.
<b>Action</b>	Verify that the JMS server is running and configured.

---

<b>POP.004.0106E</b>	<b>PortletInfo is not available for uri [{0}]. Probably the portlet is not properly installed. Try to uninstall and then install it again.</b>
<b>Explanation</b>	Portlet is not currently available.
<b>Action</b>	Try to uninstall and then re-install the portlet again.
<b>POP.004.0107E</b>	<b>Invalid portlet descriptor. Portlet/DBO name is not defined</b>
<b>Explanation</b>	The server cannot load portlet information from the portlet descriptor because the portlet descriptor does not contain the portlet's name, or the portlet descriptor is incorrectly structured.
<b>Action</b>	Using the My webMethods Server to correct the portlet descriptor and redeploy it to the My webMethods Server.
<b>POP.004.0109E</b>	<b>Portlet URI is not published instance of the portlet or type. Unable to persist properties</b>
<b>Explanation</b>	The server cannot persist the properties of a portlet type without a valid portlet or portlet type identifier.
<b>Action</b>	Supply a valid portlet or portlet type identifier to the <code>com.webmethods.portal.service.portlet.impl.PortletType.setProperties()</code> method.
<b>POP.004.0110E</b>	<b>Portlet bean class is invalid: {0}</b>
<b>Explanation</b>	The server cannot initialize the portlet because the portlet does not implement the required interface.
<b>Action</b>	Using My webMethods Server to correct the portlet's deployment descriptor or regenerate the portlet, and then redeploy it.
<b>POP.004.0111E</b>	<b>Portlet bean is not poolable: {0}</b>
<b>Explanation</b>	The server cannot instantiate the portlet bean because the bean does not implement the <code>com.webmethods.portal.system.pool.IPooledObject</code> interface.
<b>Action</b>	Use My webMethods Server to correct the portlet bean source code to implement <code>IPooledObject</code> .
<b>POP.004.0112E</b>	<b>Portlet title bar class is invalid: {0}</b>
<b>Explanation</b>	The server cannot initialize portlet type information because the portlet titlebar class specified by the portlet's descriptor was not found.
<b>Action</b>	Using the Portlet Developer, remove the titlebar class specification from the portlet descriptor and then redeploy the portlet.

<b>POP.004.0113E</b>	<b>Invalid URI, no search service specified: {0}</b>
<b>Explanation</b>	The server cannot locate search provider because of an invalid URI.
<b>Action</b>	Correct the invoking code to use a valid URI.
<b>POP.004.0114E</b>	<b>Invalid datasource name: {0}</b>
<b>Explanation</b>	The server cannot execute a SQL statement against an invalid datasource.
<b>Action</b>	Correct the invoking method to pass the correct parameters. One of the critical parameters is the handle of the datasource, which can be obtained from the DataManager's API.
<b>POP.004.0115S</b>	<b>Can't find data service folder: {0}</b>
<b>Explanation</b>	The server cannot locate the system folder.
<b>Action</b>	It is possible that a system administrator has deleted a critical system folder. If so, you might need to reinstall My webMethods Server.
<b>POP.004.0116E</b>	<b>Cannot obtain database connection from pool: {0}</b>
<b>Explanation</b>	The server cannot obtain a database connection because all connections allocated for My webMethods Server are already in use or My webMethods Server cannot connect to the database.
<b>Action</b>	Verify that the database is running and is not experiencing a heavy load. Verify that the database has an adequate number of connection threads available. Verify that the machine on which the My webMethods Server is running can access the datasource's configured host name and port.
<b>POP.004.0117E</b>	<b>Database connection is closed.</b>
<b>Explanation</b>	The server cannot execute the SQL query because the database connection is closed.
<b>Action</b>	Execute the statement again. If problems persist, shut down and restart My webMethods Server.
<b>POP.004.0118E</b>	<b>Error updating Clob field</b>
<b>Explanation</b>	An error occurred while updating an unbounded size database field at the database level.
<b>Action</b>	Try the operation again.

---

<b>POP.004.0119E</b>	<b>Error updating Blob field</b>
<b>Explanation</b>	An error occurred in updating an unbounded size database field at the database level.
<b>Action</b>	Try the operation again.
<b>POP.004.0120E</b>	<b>Could not find content service for: {0}</b>
<b>Explanation</b>	The server cannot store versioned content for a resource because the content service for the resource was not found.
<b>Action</b>	Delete the resource.
<b>POP.004.0121E</b>	<b>Versioned content uri is null or empty: {0}</b>
<b>Explanation</b>	The server cannot access the versioning information.
<b>Action</b>	The version information is corrupted. Try to obtain a different version and recreate the changes.
<b>POP.004.0122E</b>	<b>Content doesn't exist: {0}</b>
<b>Explanation</b>	The server cannot read a resource's versioned content because the resource has no content.
<b>Action</b>	Delete the resource using the UI.
<b>POP.004.0123E</b>	<b>User ID is invalid: {0}</b>
<b>Explanation</b>	The server cannot locate the user's information about the versioned object.
<b>Action</b>	The version information is corrupted. Use the Publish portlet to publish a new instance of the item, and add the item to versioning. Consult the My webMethods Server documentation.
<b>POP.004.0124E</b>	<b>Could not find user: {0}</b>
<b>Explanation</b>	Cannot locate the user's information about the versioned object.
<b>Action</b>	The version information is corrupt. Publish a new instance of the item, and add the item to versioning.
<b>POP.004.0125E</b>	<b>Could not find thing: {0}</b>
<b>Explanation</b>	Cannot resolve metadata resource identifier from string.
<b>Action</b>	The resource specified by the identifier does not exist; do not use the identifier.

<b>POP.004.0126E</b>	<b>Cookie is not set on the List View</b>
<b>Explanation</b>	The server cannot sort or slice the list without a paging cookie.
<b>Action</b>	Correct the invoking source code to associate the paging cookie with the list by setting the cookie property of the list.
<b>POP.004.0127E</b>	<b>Unable to initialize directory service {0}: {1}</b>
<b>Explanation</b>	The server cannot initialize the directory service due to an error.
<b>Action</b>	Verify the connection information to the directory service using the Directory Service Administration portlet. Verify that the login credentials are accurate. Verify that there is network connectivity to the directory service from My webMethods Server.
<b>POP.004.0128E</b>	<b>Invalid directory Uri: "{0}"</b>
<b>Explanation</b>	The URI is malformed.
<b>Action</b>	Correct the invoking method to specify a valid URI parameter.
<b>POP.004.0129</b>	<b>Uri "{0}" should resolve to principal object, but was found: {1}</b>
<b>Explanation</b>	Attempting to look up a directory principal by a URL that does not resolve to a valid directory object.
<b>Action</b>	Check and correct directory API usage. Verify that the URI value used to look up directory object is valid.
<b>POP.004.0130E</b>	<b>Unidentified Clob implementation class: {0}</b>
<b>Explanation</b>	The server cannot retrieve an unbounded-length field from the database because the database driver is incompatible with My webMethods Server.
<b>Action</b>	Modify the datasource driver settings in the db.xml My webMethods Server configuration file to use approved driver.
<b>POP.004.0131S</b>	<b>Unidentified Blob implementation class: {0}</b>
<b>Explanation</b>	The server cannot retrieve result set data because of an incompatible database implementation.
<b>Action</b>	Verify that the correct version of Oracle is installed and that you are using the My webMethods Server supplied database drivers. You can consult your Oracle installation documentation to verify the version of Oracle and ensure that you have not added any custom Oracle drivers in the class path.

---

<b>POP.004.0132E</b>	<b>Xtype not found: {0}</b>
<b>Explanation</b>	The server cannot locate the portlet xtype in the metadata store.
<b>Action</b>	Most likely the portlet has been undeployed. Use the Install Administration portlet to redeploy the portlet.
<b>POP.004.0133</b>	<b>XType already registered: {0}</b>
<b>Explanation</b>	Every XType (Portlet Name, Dynamic Business Object) must have a unique name. An attempt was made to install a new portlet or application that contains a portlet or Dynamic Business Object which is already registered in MWS.
<b>Action</b>	Check to see if an application or portlet was renamed. It is also possible that a component un-install was not fully successful, in this case use <code>/component/development/tools/wm_remove_portlet</code> to clean up and delete component registration in MWS.
<b>POP.004.0134E</b>	<b>Error loading class group: {0}</b>
<b>Explanation</b>	The server cannot load all the classes for the specified class loader group.
<b>Action</b>	Check the <code>_problems_.log</code> in My webMethods Server current logging directory for more specific error information.
<b>POP.004.0135E</b>	<b>Error setting config on directory, rolling back to previous config.</b>
<b>Explanation</b>	The server cannot store the directory configuration modifications.
<b>Action</b>	Use the Directory Services Administration portlet to create a new directory service and then delete the old one.
<b>POP.004.0136E</b>	<b>Unable to retrieve group list.</b>
<b>Explanation</b>	The server cannot get group information from the LDAP directory store.
<b>Action</b>	Verify that the directory configuration is valid by using the Directory Service Administration portlet.
<b>POP.004.0141E</b>	<b>No configuration information found for content service, not initializing: {0}.</b>
<b>Explanation</b>	The server cannot initialize the content service.
<b>Action</b>	If you cannot reconfigure the offending content service by using the Content Service Admin portlet call Software AG Global Support for a reset directive.

<b>POP.004.0144I</b>	<b>FTPconnection connect to {0}.</b>
<b>Explanation</b>	A connection was initiated with the remote FTP server.
<b>Action</b>	This is an informative statement. No action is necessary.
<b>POP.004.0152E</b>	<b>No Query Parameters specified.</b>
<b>Explanation</b>	The server cannot execute the search because there is no search query.
<b>Action</b>	Navigate to the Search portlet and try again.
<b>POP.004.0153E</b>	<b>Search Server is unavailable or not properly configured</b>
<b>Explanation</b>	The server cannot access the search service.
<b>Action</b>	Verify that the search service is properly configured by using the Search Admin portlet.
<b>POP.004.0155E</b>	<b>Error adding file to search index: {0}</b>
<b>Explanation</b>	The server was unable to properly index a My webMethods Server component object.
<b>Action</b>	Determine if the document is in an unknown format or is malformed. Examine the Lucene Search Admin portlet for details on formats.
<b>POP.004.0156E</b>	<b>content stream is null</b>
<b>Explanation</b>	The server cannot locate the content file in the content repository.
<b>Action</b>	Verify that the existence of the content repository and network connectivity. The content repository has some configuration information in the storageConfig.xml. If a custom content service has been mounted, then verify that connectivity between the My webMethods Server process and the network file system is intact. Verify that you can browse to the content using My webMethods Server. Purge all items pending deletion with the Manage Deleted Items Admin Portlet.
<b>POP.004.0157E</b>	<b>Error getting resync list for library: {0}</b>
<b>Explanation</b>	The server cannot resynchronize the search library index because an error occurred in querying the database for the list of resources to index.
<b>Action</b>	Restart the My webMethods Server.

---

<b>POP.004.0158E</b>	<b>Malformed Language Pack: {0}</b>
<b>Explanation</b>	The server cannot use the language pack because its name is malformed. The name should be one of [language], [language]_[country], or [language]_[country]_[variant], where [language] is a language code such as en or ja, [country] is a country code such as US or JP, and [variant] is a variant code.
<b>Action</b>	Correct the language pack name and re-install language pack.
<b>POP.004.0187</b>	<b>Could not lookup URI {0}</b>
<b>Explanation</b>	If the URI points to an invalid directory object (user or group) an error occurs.
<b>Action</b>	Check and correct directory API usage. Check what URI value was used. This error might also occur if the user was deleted immediately before logging in. The error will go away when MWS caches are updated, usually within seconds.
<b>POP.004.0196</b>	<b>Role Modification is not supported for: {0}.</b>
<b>Explanation</b>	Only static roles support modification of role membership. This error is thrown when attempting to modify membership using the directory APIs for non-static roles
<b>Action</b>	Check and correct directory API usage. Check to see if the role being modified is static role
<b>POP.004.0197</b>	<b>Failed to set property "{0}". Reason: {1}</b>
<b>Explanation</b>	Error has occurred when setting the thing object properties. This might happen when attempting to set the property of a specific java type, but passing in an incompatible value.
<b>Action</b>	Check MWS logs for additional error information. Check the values the code attempted to update and determine if the actual property types are valid.
<b>POP.004.0198E</b>	<b>Cannot create a user with a duplicate id: {0}</b>
<b>Explanation</b>	An attempt was made to create a new user with a duplicate ID of an existing user.
<b>Action</b>	Use a unique identifier when creating a new user, group or role.
<b>POP.004.0199E</b>	<b>Cannot create a group with a duplicate id: {0}</b>
<b>Explanation</b>	An attempt was made to create a new user with a duplicate ID of an existing user.
<b>Action</b>	Use a unique identifier when creating a new user, group or role.

<b>POP.004.0200</b>	<b>Cannot create database connection to default MWS datasource.</b>
<b>Explanation</b>	Unable to create database connection to MWS database schema.
<b>Action</b>	Check MWS database connection configuration in MWS/server/default/config/mws.db.xml config file.
<b>POP.004.0201</b>	<b>Cannot initialize MWS, invalid database schema is specified</b>
<b>Explanation</b>	MWS validates if database schema contains correct tables and then throws this error if it is not configured.
<b>Action</b>	Check if MWS database schema was correctly created by dbConfigurator tool. You might need to drop and re-create MWS schema.
<b>POP.004.0202</b>	<b>Cannot create database connection to default MWS datasource. Please verify database connection parameters in the MWS/server/{0}/config/mws.db.xml configuration file</b>
<b>Explanation</b>	An issue has occurred with the database connection configuration file such as invalid XML or an incorrect JDBC driver name.
<b>Action</b>	Verify the database connection parameters in the MWS/server/default/config/mws.db.xml configuration file.
<b>POP.004.0203</b>	<b>User {0} can not set access on {1}</b>
<b>Explanation</b>	User does not have access rights to set or update permissions.
<b>Action</b>	See if the user or groups and roles, the user is a member of has access rights to set permissions on a given object.
<b>POP.004.0204</b>	<b>Failed to search business data with the "taskTypeID" query term specified.</b>
<b>Explanation</b>	The taskTypeID is not specified in task search term.
<b>Action</b>	Provide a valid taskTypeID as a task search term.
<b>POP.004.0205</b>	<b>Unable to locate whitelist storage object</b>
<b>Explanation</b>	The required whitelist storage object cannot be located.
<b>Action</b>	Contact the system administrator to make sure that whitelist storage has been configured.

---

<b>POP.004.0206</b>	<b>Failed to connect to database at {0}. Verify hostname/port and connection credentials.</b>
<b>Explanation</b>	Failed to connect to database.
<b>Action</b>	Make sure the database is running and has a network connection, and that the proper credentials are in use. Otherwise, contact the system administrator to make sure database has been configured correctly.
<b>POP.004.0207</b>	<b>Unable to update whitelist storage object</b>
<b>Explanation</b>	Your user account has not been granted the privilege for updating a whitelist storage object.
<b>Action</b>	Contact the system administrator if you need this privilege.
<b>POP.004.0209</b>	<b>Role name is empty.</b>
<b>POP.005.0002E</b>	<b>Can Not Re-initialize CDS library</b>
<b>Explanation</b>	An attempt was made to initialize the system twice.
<b>Action</b>	After My webMethods Server is initialized, do not attempt to do so again.
<b>POP.005.0003E</b>	<b>Error parsing segment urls: "{0}"</b>
<b>Explanation</b>	One of the My webMethods Servers in the cluster has an incorrect URL.
<b>Action</b>	Determine the correct URL for the My webMethods Server, then log in to My webMethods Server as sysadmin and use the Cluster Administration portlet to correct the error.
<b>POP.005.0004E</b>	<b>Unable to register component: "{0}" due to "{1}"</b>
<b>Explanation</b>	My webMethods Server could not register the specified component.
<b>Action</b>	Look in the _problems_.log file for the stack trace of the error. It might be necessary to reinstall the component.
<b>POP.005.0005</b>	<b>Unable to reload component: "{0}" due to "{1}"</b>
<b>Explanation</b>	During dynamic reloading of a component (for example, a portlet), an error occurred.
<b>Action</b>	Check the logs to investigate what component failed to be reloaded. If the component is a portlet, then try uninstalling the portlet and reinstalling it, or try to revert to a previous version of the portlet.

<b>POP.005.0006E</b>	<b>This server node is not defined in the MWS cluster configuration: "{0}"</b>
<b>Explanation</b>	The specified My webMethods Server is not included in the cluster configuration.
<b>Action</b>	Log in to My webMethods Server as sysadmin and use the Cluster Administration portlet to add the specified My webMethods Server to the cluster.
<b>POP.005.0007</b>	<b>Front End URL is not specified in the MWS cluster configuration</b>
<b>Explanation</b>	The cluster doesn't have a valid configuration.
<b>Action</b>	Log in to My webMethods Server as sysadmin and use the Cluster Administration portlet to check the cluster configuration.
<b>POP.005.0008E</b>	<b>internal cache error</b>
<b>Explanation</b>	An internal error occurred while removing an item from a cache.
<b>Action</b>	Inspect the <code>_problems_.log</code> for details of the failure. This error could indicate that there is invalid data in a cache. Restart My webMethods Server to address the problem.
<b>POP.005.0009E</b>	<b>Unable to loadComponent: "{0}"</b>
<b>Explanation</b>	A failure occurred while loading a My webMethods Server component.
<b>Action</b>	Look in the <code>_problems_.log</code> file for the stack trace of the error. It may be necessary to reinstall the component.
<b>POP.005.0010E</b>	<b>Unknown object: "{0}"</b>
<b>Explanation</b>	The ComponentData object for a component is of an unknown type.
<b>Action</b>	The componentData must be one of the handled object types. This error means that a My webMethods Server component could not initialize because it is invalid. Check the component for a valid configuration.
<b>POP.005.0013</b>	<b>Command not found: "{0}"</b>
<b>Explanation</b>	A request to obtain a registered command failed. The command does not exist.
<b>Action</b>	Check the custom portlet invoking the command and ensure that it is specifying a deployed command.
<b>POP.005.0014</b>	<b>Unbalanced "{1}" in value expression: "{0}"</b>
<b>Explanation</b>	A legacy portlet has created an illegal dynamic expression.
<b>Action</b>	Review the custom portlet for proper syntax of any dynamic expressions.

---

<b>POP.005.0021</b>	<b>Attempting to use non empty My webMethods Server database for fresh deployment. Please make sure to create new empty My webMethods Server database</b>
<b>Explanation</b>	A first time startup check determined that the configured database is not a new database. A new database is required for a new installation.
<b>Action</b>	You must create new (empty) My webMethods Server database and configure My webMethods Server to connect to it. Please refer to the Software AG documentation for installing webMethods products.
<b>POP.005.0022</b>	<b>Wrong version of My webMethods Server database: {0} but expected: {1}</b>
<b>Explanation</b>	A first time startup check determined that the configured database does not match the schema required by My webMethods Server.
<b>Action</b>	Verify that the specified database is properly configured. The database is likely configured with an old or incomplete schema. Please refer to the Software AG documentation for installing webMethods products.
<b>POP.005.0026</b>	<b>Must have at least one server node defined</b>
<b>Explanation</b>	The cluster does not have a valid configuration. No server nodes are defined.
<b>Action</b>	Log in to My webMethods Server as sysadmin and use the Cluster Administration portlet to check the cluster configuration.
<b>POP.005.0028</b>	<b>"{0}" server node must have at least one web stack listener enabled</b>
<b>Explanation</b>	Each node in the cluster is required to have at least one port enabled for accepting web requests.
<b>Action</b>	Log in to My webMethods Server as sysadmin and use the Cluster Administration portlet to check the cluster configuration.
<b>POP.005.0029</b>	<b>server node name must not be empty</b>
<b>Explanation</b>	The cluster does not have a valid configuration. A server node name is not defined.
<b>Action</b>	Log in to My webMethods Server as sysadmin and use the Cluster Administration portlet to check the cluster configuration.
<b>POP.005.0030</b>	<b>Credentials required.</b>
<b>Explanation</b>	Credentials of a valid My webMethods Server user are required.
<b>Action</b>	Provide the user name and password of a valid My webMethods Server user account.

<b>POP.005.0031</b>	<b>Credentials should be String[].</b>
<b>Explanation</b>	Credentials must be supplied in a string array format.
<b>Action</b>	Configure the JMX client to provide credentials in a string array format.
<b>POP.005.0032</b>	<b>Credentials should have 2 elements.</b>
<b>Explanation</b>	Two credential elements (user name and password) were expected, but a non-matching number of elements were provided.
<b>Action</b>	Provide only the user name and password.
<b>POP.005.0033</b>	<b>JMX Authentication failed!</b>
<b>Explanation</b>	The user cannot be authenticated within My webMethods Server.
<b>Action</b>	Provide a valid My webMethods Server user.
<b>POP.005.0034</b>	<b>JMX Authorization failed!</b>
<b>Explanation</b>	The provided user does not have sufficient privileges for connecting via JMX.
<b>Action</b>	Provide a user with the "Connect to JMX" privilege.
<b>POP.005.0035</b>	<b>Insufficient privileges for establishing JMX communication!</b>
<b>Explanation</b>	The provided user does not have sufficient privileges for connecting via JMX.
<b>Action</b>	Provide a user with the "Connect to JMX" privilege.
<b>POP.005.0036</b>	<b>JMX Server Port number cannot be parsed. Port parameter value "{0}".</b>
<b>Explanation</b>	The provided JMX port number is not an available port number.
<b>Action</b>	Change the JMX port configuration property to an available port number.
<b>POP.005.0037</b>	<b>JDK 1.6 or higher is required to run JMX over SSL.</b>
<b>Explanation</b>	My webMethods Server is currently started with JDK 1.5.
<b>Action</b>	Update the My webMethods Server JDK to JDK 1.6.
<b>POP.005.0039</b>	<b>Cannot start CDS library because MWS did not initialize yet</b>
<b>Explanation</b>	The CDS library cannot start because My webMethods Server has not initialized yet.
<b>Action</b>	Wait for My webMethods Server to initialize before starting the CDS library.

---

<b>POP.005.0040</b>	<b>Cannot start common directory service because IS was started before MWS. Complete the MWS upgrade, which includes starting MWS, before performing the IS upgrade, which includes starting IS. See the upgrade guide for correct order.</b>
<b>Explanation</b>	The CDS library cannot start because the My webMethods Server upgrade has not completed yet.
<b>Action</b>	Complete the My webMethods Server upgrade before starting the CDS library.
<b>POP.005.0041</b>	<b>Unable to start server at port number {0} on host {1} (for: {2}) , reason : {3}. Perhaps another MWS process is already running?</b>
<b>Explanation</b>	The server cannot be started at the specified port on the specified host due to the specified reason.
<b>Action</b>	Make sure that no other My webMethods Server instance is running on the same host using the same port.
<b>POP.005.0042</b>	<b>Unable to start. The server name {0} could not be found in the cluster definition</b>
<b>Explanation</b>	The server cannot start because the specified server name cannot be found in the cluster definition.
<b>Action</b>	Make sure that the server name matches the name specified in the cluster definition.
<b>POP.005.0043</b>	<b>The JMS communication layer for common directory services (CDS) failed to initialize, which causes CDS assets to be out of sync. To enable JMS communication, specify a valid JNDI Provider URL on the Cluster Administration page in My webMethods and restart Integration Server.</b>
<b>POP.006.0003E</b>	<b>portlet bean URI not specified</b>
<b>Explanation</b>	The portlet:bean JSP tag does not contain a uri attribute to identify a valid portlet instance.
<b>Action</b>	Ensure that all instances of the 'portlet:bean' JSP tag include a 'uri' attribute. The attribute value must identify a valid portlet instance. Also, ensure that the portlet type referenced by the 'uri' attribute has been deployed and that all instances referenced by the attribute exist.
<b>POP.006.0004E</b>	<b>cannot create portlet bean for the URI "{0}"</b>
<b>Explanation</b>	The portlet:bean JSP tag does not contain a uri attribute that identifies a valid portlet instance.
<b>Action</b>	Ensure that all instances of the 'portlet:bean' JSP tag include a 'uri' attribute. The attribute value must identify a valid portlet instance. Also, ensure that the portlet type referenced by the 'uri' attribute has been deployed, and that all instances referenced by the attribute exist.

<b>POP.006.0005</b>	<b>parent "{0}" not found</b>
<b>Explanation</b>	The JSP page is invalid, because a JSP tag that is only valid when it is inside of a parent JSP tag is not inside the expected parent.
<b>Action</b>	Locate the error in the JSP page and correct the problem.
<b>POP.006.0006E</b>	<b>cannot find portlet bean named "{0}" in the current page context</b>
<b>Explanation</b>	The portlet:portletController JSP tag does not contain a portlet attribute. The value of this attribute is the key to the pageContext entry in which a com.webmethods.portal.service.portlet.IPortletBean object is stored.
<b>Action</b>	Ensure that all instances of the 'portlet:portletController' JSP tag include a 'portlet' attribute that references a valid IPortletBean.
<b>POP.006.0007E</b>	<b>cannot obtain portlet info</b>
<b>Explanation</b>	The portlet:info JSP tag does not contain an info attribute. The value of this attribute is the key to the pageContext entry in which a com.webmethods.portal.service.portlet.info.IPortletInfo object is stored.
<b>Action</b>	Ensure that all instances of the 'portlet:info' JSP tag include an 'info' attribute that references a valid IPortletInfo object.
<b>POP.006.0008E</b>	<b>cannot find portlet info named "{0}" in the current page context</b>
<b>Explanation</b>	The portlet:propertyGroups, portlet:propertyGroup, or portlet:propertyLine JSP tag does not contain an info attribute. The value of this attribute is the key to the pageContext entry in which a com.webmethods.portal.service.portlet.info.IPortletInfo object is stored.
<b>Action</b>	Ensure that all instances of the 'portlet:propertyGroups', 'portlet:propertyGroup', and 'portlet:propertyLine' JSP tags include an 'info' attribute that references a valid IPortletInfo object.
<b>POP.006.0015</b>	<b>cannot obtain portlet property info</b>
<b>Explanation</b>	The portlet configuration information could not be found. This problem could result from an invalid JSP page or a portlet installation that has been corrupted.
<b>Action</b>	Review the JSP page and ensure the portlet:propertyLine JSP tag is contained within a portlet:bean tag. If the JSP is correct and the problem persists, try re-installing the broken portlet.

---

<b>POP.006.0016E</b>	<b>cannot find portlet property info named "{0}" in the current page context</b>
<b>Explanation</b>	The portlet:propertyLine JSP tag does not contain a propertyInfo attribute. The value of this attribute is the key to the pageContext entry in which a com.webmethods.portal.service.portlet.info.IPortletPropertyInfo object is stored.
<b>Action</b>	Ensure that all instances of the 'portlet:propertyLine' JSP tag include a 'propertyInfo' attribute that references a valid IPortletPropertyInfo.
<b>POP.006.0017</b>	<b>portlet property name not specified</b>
<b>Explanation</b>	The JSP page contains a portlet:propertyLine tag that is missing the required "name" property.
<b>Action</b>	Review the JSP page and correct any missing "name" properties.
<b>POP.006.0018E</b>	<b>cannot obtain portlet property bag</b>
<b>Explanation</b>	The portlet:propertyLine JSP tag does not contain a propertyInfo attribute. The value of this attribute is the key to the pageContext entry in which a com.webmethods.rtl.util.obj.IPropertyBag object is stored.
<b>Action</b>	Ensure that all instances of the 'portlet:bean' JSP tag include a 'propertyInfo' attribute that references a valid IPropertyBag.
<b>POP.006.0019E</b>	<b>cannot find portlet property bag named "{0}" in the current page context</b>
<b>Explanation</b>	The portlet:propertyLine JSP tag does not contain a propertyInfo attribute. The value of this attribute is the key to the pageContext entry in which a com.webmethods.rtl.util.obj.IPropertyBag object is stored.
<b>Action</b>	Ensure that all instances of the 'portlet:bean' JSP tag include a 'propertyInfo' attribute that references a valid IPropertyBag.
<b>POP.006.0020E</b>	<b>object named "{0}" in the current page context is not a portlet property bag</b>
<b>Explanation</b>	The portlet:propertyLine JSP tag does not contain a propertyInfo attribute. The value of this attribute is the key to the pageContext entry in which a com.webmethods.rtl.util.obj.IPropertyBag object is stored.
<b>Action</b>	Ensure that all instances of the 'portlet:bean' JSP tag include a 'propertyInfo' attribute that references a valid IPropertyBag.
<b>POP.006.0021</b>	<b>"{0}" requires body content</b>
<b>Explanation</b>	A JSP page contains an sql:query tag with missing SQL query text in the tag body.
<b>Action</b>	The JSP page must be edited to either remove the tag or add the SQL query text as the tag body.

<b>POP.006.0022</b>	<b>skin property not found</b>
<b>Explanation</b>	In a JSP page, the ui:img tag is trying to render an image from the skin, but the image was not defined in the skin.
<b>Action</b>	Edit the skin to add the missing image, or change the JSP page to reference an image that does exist.
<b>POP.006.0024E</b>	<b>'IterateTag' container is null</b>
<b>Explanation</b>	The util:iterate JSP tag does not contain a container attribute. The value of this attribute is the key to the pageContext entry in which a java.util.Collection, java.util.Iterator, or java.lang.Object[] object is stored.
<b>Action</b>	Ensure that all instances of the 'util:iterate' JSP tag include a 'container' attribute that references a valid container object.
<b>POP.006.0025</b>	<b>"{0}" class not supported as an 'IterateTag' container</b>
<b>Explanation</b>	A JSP page uses the util:iterate tag, but the value of the 'container' property is not one of the supported data types.
<b>Action</b>	The JSP page must be edited to correct the problem.
<b>POP.006.0026</b>	<b>"{0}" requires "{1}" attribute</b>
<b>Explanation</b>	A JSP page uses the util:iterate tag, but the "indexVar" tag attribute was not supplied.
<b>Action</b>	The JSP page must be edited to add the missing tag attribute.
<b>POP.006.0027</b>	<b>cannot find 'PerfStartTag' token named "{0}"</b>
<b>Explanation</b>	A JSP page uses the util:perfEnd tag, but the perf token supplied in the "name" tag attribute does not exist.
<b>Action</b>	This problem most likely results from a malformed JSP page. The JSP developer should review the JSP page for any mismatched util:perfStart/util:perfEnd pairs.
<b>POP.006.0028E</b>	<b>cannot find XML DOM node named "{0}" in the current page context</b>
<b>Explanation</b>	Use of the xml:valueOf JSP tag causes this exception.
<b>Action</b>	Remove all instances of the 'xml:valueOf' JSP tag.

---

<b>POP.006.0029E</b>	<b>cannot create XML DOM document from given XML stream</b>
<b>Explanation</b>	The XML stream specified for the xml:xml JSP tag does not contain well-formed XML.
<b>Action</b>	Check the _problems_.log in the Portal's current logging directory for more specific error information.
<b>POP.006.0030E</b>	<b>cannot load XML DOM document for the specified location "{0}"</b>
<b>Explanation</b>	The xml:xml JSP tag could not load a file from the location specified by the 'location' attribute.
<b>Action</b>	Edit instances of the 'xml:xml' JSP tag to include a 'location' attribute that correctly specifies the url to an XML document.
<b>POP.006.0031</b>	<b>Required Property Editor parameter "{0}" not specified.</b>
<b>Explanation</b>	A JSP page is rendering a property editor, but a required parameter has not been supplied.
<b>Action</b>	The JSP developer should edit the JSP page to supply the missing required parameter.
<b>POP.006.0032</b>	<b>Property Editor "{0}" not deployed.</b>
<b>Explanation</b>	A JSP page is trying to render a property editor that is not deployed to My webMethods Server.
<b>Action</b>	Deploy the missing property editor to My webMethods Server, or change the JSP page to use a property editor that is deployed to My webMethods Server.
<b>POP.006.0033</b>	<b>invalid portlet bean URI: {0}</b>
<b>Explanation</b>	A JSP page is using either the portlet:bean or the portlet:controller tag in which the supplied portlet URI does not match an existing portlet instance.
<b>Action</b>	Deploy the missing portlet instance. Or, edit the JSP page to change the URI to match an existing portlet instance.
<b>POP.007.0002</b>	<b>Error getting directory mechanics: "{0}"</b>
<b>Explanation</b>	The My webMethods Server instance was not properly installed.
<b>Action</b>	Re-create the My webMethods Server database schema and the My webMethods Server server instance.

<b>POP.007.0003</b>	<b>Error rendering layout "{0}" due to "{1}"</b>
<b>Explanation</b>	There was an error either compiling or executing the application *.JSP page.
<b>Action</b>	You may need to run My webMethods Server with a full JDK which includes the Java compiler. Or, if you have modified any system JSP or NBSF pages, there may have been a syntax error.
<b>POP.007.0006</b>	<b>Requested content was not found: "{0}"</b>
<b>Explanation</b>	An error occurred when attempting to browse to a page or file; the page or file does not exist in My webMethods Server.
<b>Action</b>	Verify that the URL being browsed to is correctly formed and specifies a valid URL.
<b>POP.007.0007E</b>	<b>Command not Found: "{0}"</b>
<b>Explanation</b>	An attempt was made to execute a server command that is not deployed.
<b>Action</b>	Log in to My webMethods Server and use the Install Administration portlet to deploy the missing portlet.
<b>POP.007.0008</b>	<b>The requested resource is not a webservice: "{0}"</b>
<b>Explanation</b>	An attempt was made to obtain a WSDL for a resource that is not a web service.
<b>Action</b>	Modify the request to specify a resource that is a web service.
<b>POP.007.0009</b>	<b>You are not authorized to view the resource.</b>
<b>Explanation</b>	The current user does not have permission to view the specified object or page.
<b>Action</b>	Check the permissions for the object or page to ensure that the user has read rights
<b>POP.007.0010E</b>	<b>This renderer is unable to render: "{0}"</b>
<b>Explanation</b>	An attempt was made to use the FolderRenderer to render an item that is not a folder.
<b>Action</b>	You cannot use the FolderRenderer for non-folders; specify a valid folder.
<b>POP.007.0011E</b>	<b>Unknown response: "{0}"</b>
<b>Explanation</b>	The dispatch handler returned an unknown return code.
<b>Action</b>	Correct the dispatch handler to return a valid return code.

---

<b>POP.007.0012</b>	<b>Cannot redirect to an invalid data type: "{0}"</b>
<b>Explanation</b>	An incorrect API was called when redirecting to new URL. This error is most likely to occur with a custom portlet.
<b>Action</b>	Verify that the portlet specifies the correct API for redirection.
<b>POP.007.0013</b>	<b>Unable to find adequate authentication information to instantiate an http session</b>
<b>Explanation</b>	My webMethods Server is unable to authenticate an HTTP session.
<b>Action</b>	This error can occur because of incorrect implementation of custom authentication (such as, agent based authentication). Review the custom authentication scheme and verify that it is correctly implemented.
<b>POP.007.0023</b>	<b>getWriter() has already been called on this response.</b>
<b>Explanation</b>	This error indicates an incorrect usage of the <code>HttpResponse.getWriter()</code> API and most likely occurred in a custom CAF application.
<b>Action</b>	Review the CAF application and check the implementation of the <code>HttpResponse</code> APIs.
<b>POP.007.0024</b>	<b>getOutputStream() has already been called on this response.</b>
<b>Explanation</b>	This error indicates an incorrect usage of the <code>HttpResponse.getOutputStream()</code> API and most likely occurred in a custom CAF application.
<b>Action</b>	Review the CAF application and check the implementation of the <code>HttpResponse</code> APIs.
<b>POP.007.0026</b>	<b>Response body content already written.</b>
<b>Explanation</b>	This error occurs when attempting to set the <code>HttpResponse</code> header when the response has been already partially or fully committed. This most likely occurred in a custom CAF application.
<b>Action</b>	Review the CAF application and check the implementation of the <code>HttpResponse</code> APIs.
<b>POP.007.0027</b>	<b>Internal Error! Portlet Controller Bean is null.</b>
<b>Explanation</b>	The system cannot serve as the internal controller bean for the portlet.
<b>Action</b>	This error occurs only for non-CAF portlets. Log out and log back in to resolve this problem.

<b>POP.007.0028</b>	<b>User not found: "{0}"</b>
<b>Explanation</b>	This error occurs when a user ID passed into My webMethods Server by a custom authentication handler cannot be matched.
<b>Action</b>	Verify that the specified user exists in the My webMethods Server directories, and check the custom authentication handler logic.
<b>POP.007.0029</b>	<b>No authentication information was found.</b>
<b>Explanation</b>	No user name was supplied to My webMethods Server when authenticating a user. This error can occur with a custom authentication handler.
<b>Action</b>	Check the implementation of the custom authentication handler. Verify the proper operation of any custom login forms.
<b>POP.007.0033</b>	<b>No portlet found to render "{0}" view.</b>
<b>Explanation</b>	This error can occur if there is a registered portlet renderer, but the portlet defined in the renderer is not found.
<b>Action</b>	Renderers are used internally by My webMethods Server to define certain system pages. If this error occurs, check to see if any of the My webMethods Server system components have been un-installed.
<b>POP.007.0035</b>	<b>The value {0} can not be changed</b>
<b>Explanation</b>	An attempt has been made to change the value of an invalid portlet preference.
<b>Action</b>	Verify that the correct portlet preference name is used.
<b>POP.007.0036</b>	<b>The store() method can not be called from a render method</b>
<b>Explanation</b>	An attempt was made to change and persist portlet preferences from the render() method.
<b>Action</b>	Portlet preferences can be changed only with the portlet action method. Correct the code which updates portlet preferences to use the proper method.
<b>POP.007.0037</b>	<b>The state of the portlet can not be changed</b>
<b>Explanation</b>	Portlet preferences can be updated only during the action() request.
<b>Action</b>	Correct the usage of the portlet preferences APIs to change preferences during the action() request.

<b>POP.007.0038</b>	<b>The key given is null.</b>
<b>Explanation</b>	An attempt was made to use the portlet preferences API with a NULL preference name.
<b>Action</b>	Correct the portlet preferences API implementation to specify a valid preference name.
<b>POP.007.0044</b>	<b>The map given is null</b>
<b>Explanation</b>	This error indicates an incorrect usage of the portlet URL APIs; the parameter map setting is NULL.
<b>Action</b>	Correct the portlet URL APIs implementation to specify a valid parameter map.
<b>POP.007.0045</b>	<b>The map given contains a null key</b>
<b>Explanation</b>	This error indicates an incorrect usage of the portlet URL APIs; the parameters map setting contains a NULL key.
<b>Action</b>	Correct the portlet URL APIs implementation to specify a valid parameter map key.
<b>POP.007.0046</b>	<b>The map contains a non String key</b>
<b>Explanation</b>	This error indicates an incorrect usage of the portlet URL APIs; the parameters map setting contains non-String values.
<b>Action</b>	Correct the portlet URL APIs implementation to pass in only String type parameters.
<b>POP.007.0047</b>	<b>Namespace prefix defined more than once for {0}</b>
<b>Explanation</b>	An incorrect URL was passed into My webMethods Server; more than one namespace prefix is provided.
<b>Action</b>	Check that the URL passed into My webMethods Server contains only one single value for the namespace prefix.
<b>POP.007.0048</b>	<b>Namespace prefix is not defined for {0} and the prefix id is not a valid thingID</b>
<b>Explanation</b>	An incorrect URL was passed into My webMethods Server; no namespace prefix is provided.
<b>Action</b>	Modify the URL passed into My webMethods Server to define the missing namespace prefix.

- POP.007.0049**      **The portlet mode {0} is not supported for the {1} markup language.**  
**Explanation**      The requested mode is not implemented in the portlet or is not supported.  
**Action**            Check the portlet URL API usage if attempting to set the mode with APIs. If this is a custom portlet, check to see if the portlet implements this mode.
- POP.007.0051**      **Output generated because of an exception**  
**Explanation**      An exception occurred while rendering portlet content.  
**Action**            Refer to the server logs at ..\MWS\server\default\logs for additional exception details.
- POP.007.0052**      **sendRedirect was already called**  
**Explanation**      An attempt was made to change the portlet window state, mode, or parameters after a redirect request was sent.  
**Action**            Examine and correct the usage of the redirect request in the portlet code.
- POP.007.0053**      **The portlet mode is null**  
**Explanation**      An attempt was made to set a NULL portlet mode.  
**Action**            Examine and correct the usage of the Portlet URL API.
- POP.007.0054**      **The window state {0} is not supported by the portlet container**  
**Explanation**      An attempt was made to set an invalid window state.  
**Action**            Examine and correct the window state being set by the Portlet URL APIs.
- POP.007.0055**      **The window state is null**  
**Explanation**      An attempt was made to set a NULL window state.  
**Action**            Examine and correct the window state being set by the Portlet URL APIs.
- POP.007.0056**      **The portlet mode {0} is not supported by the portlet container**  
**Explanation**      An attempt was made to set an invalid portlet mode.  
**Action**            Examine and correct the portlet mode being set by the Portlet URL APIs.

---

<b>POP.007.0057</b>	<b>The map contains a non String[] value</b>
<b>Explanation</b>	An attempt was made to set a parameter with a value that is not of the type String[].
<b>Action</b>	Examine and correct parameters being by the Portlet URL API; these values must be String or String[] types only.
<b>POP.007.0058</b>	<b>The key given is null</b>
<b>Explanation</b>	An attempt was made to pass in a NULL key value.
<b>Action</b>	Examine and correct the key value that is being passed in by the Portlet URL API.
<b>POP.007.0059</b>	<b>The value given is null</b>
<b>Explanation</b>	An attempt was made to pass in a NULL value.
<b>Action</b>	Examine and correct the value being passed in by the Portlet URL API.
<b>POP.007.0060</b>	<b>The sendRedirect method can not be invoked after any of the following methods of the ActionResponse interface has been called: setPortletMode, setWindowState, setRenderParameter, setRenderParameters</b>
<b>Explanation</b>	The sendRedirect method can not be invoked after any of the following methods of the ActionResponse interface has been called: setPortletMode, setWindowState, setRenderParameter, setRenderParameters
<b>Action</b>	Correct the code to ensure that the sendRedirect() method does not occur after these calls during the same action request.
<b>POP.007.0061</b>	<b>A relative or incorrect path URL is given</b>
<b>Explanation</b>	An attempt was made to redirect to an invalid URL.
<b>Action</b>	Check the URL that is the target of the redirect. It must start with "http://", "https://", or "/".
<b>POP.007.0062</b>	<b>You cannot have null as a parameter</b>
<b>Explanation</b>	An attempt was made to pass in a NULL parameter name.
<b>Action</b>	Examine and correct the parameter name used in the PortletContext and PortletRequest APIs.

<b>POP.007.0063</b>	<b>Content type cannot be application/x-www-form-urlencoded</b>
<b>Explanation</b>	Incorrect API usage. The ServletRequest.getReader() and getInputStream() methods are not available for requests where a form is submitted.
<b>Action</b>	Examine and correct the ServletRequest.getReader() and getInputStream() API usage.
<b>POP.007.0064</b>	<b>This method cannot be called, when getReader() method has been called</b>
<b>Explanation</b>	The ServletResponse method cannot be used when the getReader() method has been called.
<b>Action</b>	Examine and correct the ServletResponse API usage.
<b>POP.007.0065</b>	<b>The attribute name cannot be null</b>
<b>Explanation</b>	An attempt was made to get or set an attribute using a NULL name.
<b>Action</b>	Examine and correct the attribute name being passed to the API.
<b>POP.007.0066</b>	<b>Path must start with /</b>
<b>Explanation</b>	An attempt was made to get a resource using an invalid path. The path of the resource must start with "/".
<b>Action</b>	Examine and correct the path name set by the PortletContext API.
<b>POP.007.0069</b>	<b>The content type {0} is not supported.</b>
<b>Explanation</b>	An attempt was made to set an invalid content type.
<b>Action</b>	Check and correct the content type being set by the PortletResponse API.
<b>POP.007.0070</b>	<b>The content type has not been set before calling the getPortletOutputStream() method.</b>
<b>Explanation</b>	The response content type must be set before obtaining the output stream.
<b>Action</b>	Examine and correct the API calls.
<b>POP.007.0071</b>	<b>the output stream has already been called</b>
<b>Explanation</b>	A Writer cannot be obtained for the response after obtaining the output stream.
<b>Action</b>	Examine and correct the API usage.

---

<b>POP.007.0072</b>	<b>the PrintWriter object has already been called</b>
<b>Explanation</b>	A Writer cannot be obtained for the response because the output stream has already been obtained.
<b>Action</b>	Examine and correct the API usage.
<b>POP.007.0073</b>	<b>Can not serialize Portlet Preferences</b>
<b>Explanation</b>	There was error when serializing portlet preferences. Portlet preferences cannot contain non-serializable objects.
<b>Action</b>	Check the server log for more details. Examine and correct any portlet preferences being set to ensure only serializable objects are used.
<b>POP.007.0074</b>	<b>Portlet Application "{0}" is not properly installed or unavailable.</b>
<b>Explanation</b>	The system cannot load the specified portlet application. It is either not installed or is disabled in the cluster partition.
<b>Action</b>	Re-install the portlet application. Check the server logs for errors during installation. Verify that the application is enabled in the cluster partition.
<b>POP.007.0075</b>	<b>Portlet "{0}" is not found</b>
<b>Explanation</b>	The specified portlet is not installed or is disabled in the cluster partition.
<b>Action</b>	Verify that the portlet application is installed; install if necessary. Check the server logs for any installation errors. Verify that the portlet is enabled in the cluster partition.
<b>POP.007.0076</b>	<b>PortletContainer Servlet "{0}" is not found. Check default web application configuration file (defaultPortletAppWeb.xml)</b>
<b>Explanation</b>	System servlet is not found.
<b>Action</b>	Determine if any changes were made to system configuration files in ../MWS/server/default/deploy/portal.war. Re-install My webMethods Server.
<b>POP.007.0077</b>	<b>You are not authorized to view the resource. {0}</b>
<b>Explanation</b>	The current user does not have permission to read the specified object or resource.
<b>Action</b>	Examine and correct the user account permissions.

- POP.007.0078**      **This action requires an anti-cross-site-request-forgery token.**  
**Explanation**      The executed command or action did not specify an anti-cross-site-request-forgery token.  
**Action**              Check if the given command or action does require an AXRF token. If it does require a token, the token must be explicitly generated and passed in as a URL parameter. For example, when calling a CAF action from a portlet URL, the action must either be configured to not require a token (which lessens security), or a token must be generated when calling this action from a direct URL.
- POP.007.0101**      **Illegal Property Editor name: "{0}".**  
**Explanation**      A legacy portlet property uses an invalid property-editor name.  
**Action**              Examine and correct the property-editor name in the wm-portlet.xml file (this applies only to legacy non-CAF portlets).
- POP.007.0102**      **Illegal Property Editor parameter value for "{0}": "{1}".**  
**Explanation**      An incorrect parameter value was passed to the property editor.  
**Action**              Check the property editor configuration in the wm-portlet.xml file (this applies only to legacy non-CAF portlets).
- POP.007.0103**      **Property Editor requires DHTML.**  
**Explanation**      The property editor "dhtml" property configuration is invalid. The property editor requires DHTML to be enabled.  
**Action**              Examine the property editor configuration in the wm-portlet.xml file. Set dhtml=true (this applies only to legacy non-CAF portlets).
- POP.007.0105**      **Property editor "{0}" parameter "{1}" of type "choice" defined without choices.**  
**Explanation**      An invalid 'choice' parameter value was supplied to the property editor.  
**Action**              Examine the property editor configuration in the wm-portlet.xml file (this applies only to legacy non-CAF portlets).
- POP.007.0106**      **Illegal property editor "{0}" attribute: "{1}" value: "{2}".**  
**Explanation**      An invalid property editor attribute was encountered.  
**Action**              Examine the property editor configuration in the wm-portlet.xml file (this applies only to legacy non-CAF portlets).

---

<b>POP.007.0107</b>	<b>Illegal property editor "{0}" parameter "{1}" attribute "{2}" value: "{3}".</b>
<b>Explanation</b>	An invalid property editor attribute was encountered.
<b>Action</b>	Examine the property editor configuration in the wm-portlet.xml file (this applies only to legacy non-CAF portlets).
<b>POP.007.0108</b>	<b>Illegal property editor "{0}" parameter "{1}" choice "{2}" attribute "{3}" value: "{4}".</b>
<b>Explanation</b>	An invalid property editor attribute was encountered.
<b>Action</b>	Examine the property editor configuration in the wm-portlet.xml file (this applies only to legacy non-CAF portlets).
<b>POP.007.0109</b>	<b>Property Editor not deployed: "{0}".</b>
<b>Explanation</b>	An incorrect property editor was specified for use
<b>Action</b>	Examine the property editor configuration in the wm-portlet.xml file (this applies only to legacy non-CAF portlets).
<b>POP.007.0110</b>	<b>Illegal Redirect URL: "{0}".</b>
<b>Explanation</b>	An invalid redirect URL was provided.
<b>Action</b>	Check and correct the redirect URL used in the API calls.
<b>POP.009.0001</b>	<b>WebService invocation is disabled for the requested command</b>
<b>Explanation</b>	An attempt was made to invoke a My webMethods Server command as a web service, but the command does not allow invocation as a web service.
<b>Action</b>	1. Enable the command if it is disabled. 2. For some commands it is not possible to execute them with a web service. If this is one of those commands, no other action can be taken.
<b>POP.009.0002</b>	<b>No WebService type mapping found for java class: {0}</b>
<b>Explanation</b>	For a My webMethods Server command being invoked as a web service, one or more of the command bean (input) fields to the command does not have a SOAP serializer (or deserializer) defined. Therefore, the My webMethods Server framework cannot convert the data to a SOAP message.
<b>Action</b>	The command developer must either mark the command as not enabled for web service invocation, or write the custom serializer/deserializer code for the data type and register it in the type mapping registry by overriding the "initializeSOAPMappingRegistry" method of the command Java class.

<b>POP.009.0003</b>	<b>The CommandBean must implement ISoapComplexTypeBean to be used as a WebService</b>
<b>Explanation</b>	For a My webMethods Server command being invoked as a web service, the command bean Java class does not implement the interface that is required to be used as a web service.
<b>Action</b>	The command developer must either mark the command as not enabled for web service invocation, or change the command bean Java class to have it implement the interface.
<b>POP.009.0004</b>	<b>Error initializing ServiceDesc for WebService: {0}</b>
<b>Explanation</b>	An unexpected exception was detected while preparing a My webMethods Server command to be invoked as a web service.
<b>Action</b>	Inspect the stack trace in the My webMethods Server server log files to determine the cause of the exception.
<b>POP.009.0005</b>	<b>No WebService marshalling factories are defined for type {0}, and the type can not be treated as a javabean because it does not contain a public no-arg constructor</b>
<b>Explanation</b>	For a My webMethods Server command being invoked as web service, one of the inputs or outputs is a complex Java class that does not have a no-arg constructor. Therefore, it cannot be automatically marshalled into a SOAP message.
<b>Action</b>	The command developer must either mark the command as not enabled for web service invocation, or add a no-arg constructor to the Java class.
<b>POP.009.0006</b>	<b>SAML or Hybrid authentication can not be used. Please deploy SAML Security Service component or use Basic authentication instead</b>
<b>Explanation</b>	The SAML security service is not available.
<b>Action</b>	Deploy the SAML security service component or use basic authentication instead.
<b>POP.009.0007</b>	<b>Could not find a user context.</b>
<b>Explanation</b>	Cannot find UID for the user.
<b>Action</b>	Specify a correct UID.
<b>POP.009.0008</b>	<b>The SAML service you are trying to access is not available right now.</b>
<b>Explanation</b>	The SAML service is currently unavailable.
<b>Action</b>	Inspect the stack trace in the My webMethods Server log files to determine the cause of the exception.

---

<b>POP.009.0009</b>	<b>Failed to initialize WS-Stack clients within {0} milliseconds. They will be disabled.</b>
<b>Explanation</b>	The Web Services Stack client failed to initialize in the specified period.
<b>Action</b>	Check the OSGi configuration at com.softwareag.platform.config.propsloader or restart My webMethods Server to re-initialize Web Services Stack.
<b>POP.009.0102</b>	<b>{0}: {1} is not a IThingIDList</b>
<b>Explanation</b>	The SOAP serializer that is intended to marshall a IThingIDList object into a SOAP message was passed the wrong type of object.
<b>Action</b>	This is most likely a defect in the way the type mapping registry was initialized. Examine the related code to determine the problem and correct as required.
<b>POP.011.0001</b>	<b>The method "{0}" has not been implemented.</b>
<b>Explanation</b>	An attempt was made to improperly invoke a Dynamic API.
<b>Action</b>	Examine the logs for an indication of what component and user action caused this error.
<b>POP.011.0002</b>	<b>must specify both 'prefix' and 'uri' parameters for 'taglib' directive</b>
<b>Explanation</b>	A syntax error occurred while parsing a JSP page.
<b>Action</b>	Correct the syntax error on the JSP page.
<b>POP.011.0003</b>	<b>expected "{0}" end tag but found "{1}" end tag</b>
<b>Explanation</b>	A syntax error occurred while parsing a JSP page.
<b>Action</b>	Correct the syntax error on the JSP page.
<b>POP.011.0005</b>	<b>"{0}" tag declared invalid by TagExtraInfo</b>
<b>Explanation</b>	A syntax error occurred while parsing a JSP page.
<b>Action</b>	Correct the syntax error on the JSP page.
<b>POP.011.0006</b>	<b>"{0}" tag requires "{1}" attribute</b>
<b>Explanation</b>	A syntax error occurred while parsing a JSP page.
<b>Action</b>	Correct the syntax error on the JSP page.

<b>POP.011.0007</b>	<b>specified attribute "{0}" for "{1}" tag not declared in tld</b>
<b>Explanation</b>	A syntax error occurred while parsing a JSP page.
<b>Action</b>	Correct the syntax error on the JSP page.
<b>POP.011.0008</b>	<b>specified attribute "{0}" value for "{1}" tag cannot be request-time expression</b>
<b>Explanation</b>	A syntax error occurred while parsing a JSP page.
<b>Action</b>	Correct the syntax error on the JSP page.
<b>POP.011.0009</b>	<b>request cannot be null</b>
<b>Explanation</b>	An error occurred while uploading a file.
<b>Action</b>	Check the logs for additional information.
<b>POP.011.0010</b>	<b>saveDirectory cannot be null</b>
<b>Explanation</b>	An error occurred while uploading a file.
<b>Action</b>	Use the Content Service page to ensure that a directory is configured to store the uploaded files.
<b>POP.011.0011</b>	<b>maxPostSize must be positive</b>
<b>Explanation</b>	An error occurred while uploading a file.
<b>Action</b>	Use the Content Service page to ensure that a maximum size for uploaded files is configured.
<b>POP.011.0012E</b>	<b>"{0}" is not a directory.</b>
<b>Explanation</b>	The temporary location for for saving a file upload is not valid.
<b>Action</b>	Delete all files in the Portal/server/default/temp folder.
<b>POP.011.0013W</b>	<b>"{0}" is not writable directory.</b>
<b>Explanation</b>	The temporary location for saving a file upload is not writable.
<b>Action</b>	Make sure My webMethods Server was started by a user who has rights to the portal temp folder.

---

<b>POP.011.0014E</b>	<b>Posted content type "{0}" isn't multipart/form-data.</b>
<b>Explanation</b>	My webMethods Server expects to upload a multipart portlet, but the specified content type does not match.
<b>Action</b>	Check the source file for corruption. If the file is valid and correct, try uploading it again.
<b>POP.011.0015E</b>	<b>Posted content length of "{0}" MB exceeds limit of "{1}" MB.</b>
<b>Explanation</b>	An uploaded file is larger than the size allowed by the system administrator.
<b>Action</b>	Upload a smaller file or have the system administrator use the Content Service Administration portlet to increase the maximum allowed file size.
<b>POP.011.0016E</b>	<b>Separation boundary was not specified.</b>
<b>Explanation</b>	The specified file was corrupted before or during the upload process.
<b>Action</b>	Check the source file for corruption. If the file is valid and correct, try uploading it again.
<b>POP.011.0017E</b>	<b>Corrupt form data. No leading boundary was found.</b>
<b>Explanation</b>	The specified file was corrupted before or during the upload process.
<b>Action</b>	Check the source file for corruption. If the file is valid and correct, try uploading it again.
<b>POP.011.0018E</b>	<b>Malformed line after disposition "{0}"</b>
<b>Explanation</b>	The specified file was corrupted before or during the upload process.
<b>Action</b>	Check the source file for corruption. If the file is valid and correct, try uploading it again.
<b>POP.011.0019E</b>	<b>The published file was empty or invalid.</b>
<b>Explanation</b>	The specified file was corrupted before or during the upload process.
<b>Action</b>	Check the source file for corruption. If the file is valid and correct, try uploading it again.
<b>POP.011.0020E</b>	<b>Content disposition "{0}" is corrupt.</b>
<b>Explanation</b>	The specified file was corrupted before or during the upload process.
<b>Action</b>	Check the source file for corruption. If the file is valid and correct, try uploading it again.

<b>POP.011.0021</b>	<b>Invalid content disposition "{0}".</b>
<b>Explanation</b>	An error occurred while processing the uploaded file.
<b>Action</b>	Investigate the contents of the HTTP POST to see if the data was corrupted.
<b>POP.011.0022E</b>	<b>Content type corrupt "{0}".</b>
<b>Explanation</b>	The specified file was corrupted before or during the upload process.
<b>Action</b>	Check the source file for corruption. If the file is valid and correct, try uploading it again.
<b>POP.011.0023E</b>	<b>Malformed line after disposition "{0}".</b>
<b>Explanation</b>	The specified file was corrupted before or during the upload process.
<b>Action</b>	Check the source file for corruption. If the file is valid and correct, try uploading it again.
<b>POP.011.0024</b>	<b>No file name available.</b>
<b>Explanation</b>	An error occurred while uploading a file.
<b>Action</b>	Examine the contents of the HTTP POST to see if the data was corrupted.
<b>POP.011.0025E</b>	<b>Failed to create a DocumentBuilderFactory.</b>
<b>Explanation</b>	The XML parser appears to be missing.
<b>Action</b>	Check for the xercesImpl.jar file in the portal class path. If the file is missing, reinstall My webMethods Server.
<b>POP.011.0026E</b>	<b>Failed to create a TransformerFactory.</b>
<b>Explanation</b>	The Xalan XSTL processor could not be loaded.
<b>Action</b>	Check for the xalan.jar file in the portal classpath. If the file is missing, reinstall My webMethods Server.
<b>POP.011.0027</b>	<b>JMS already initialized with "{0}".</b>
<b>Explanation</b>	An error occurred during startup.
<b>Action</b>	Ensure that startup routines are invoked only once.

---

<b>POP.011.0028E</b>	<b>JMSProvider: failed to get configuration file.</b>
<b>Explanation</b>	The JMS provider appears to be disconnected.
<b>Action</b>	Verify that the Broker is running and that My webMethods Server can connect to the computer on which the Broker is running.
<b>POP.011.0029E</b>	<b>JMSProvider: failed to get configuration file "{0}", due to "{1}".</b>
<b>Explanation</b>	The JMS provider appears to be disconnected.
<b>Action</b>	Verify that the Broker is running and that My webMethods Server can connect to the computer on which the Broker is running.
<b>POP.011.0030E</b>	<b>JNDI name not found: "{0}".</b>
<b>Explanation</b>	The JMS provider appears to be disconnected.
<b>Action</b>	Verify that the Broker is running and that My webMethods Server can connect to the computer on which the Broker is running.
<b>POP.011.0031</b>	<b>Can't initialize perf service: "{0}".</b>
<b>Explanation</b>	The specified Performance Service failed to initialize.
<b>Action</b>	Check the perfUtils.properties configuration file for spelling errors.
<b>POP.011.0032</b>	<b>Perf Service Not Initialized.</b>
<b>Explanation</b>	An attempt was made to use the Performance Service before it was initialized.
<b>Action</b>	The Performance Service might be disabled. Check the contents of the perfUtils.properties configuration file.
<b>POP.011.0033</b>	<b>Cannot open stream. Location: "{0}".</b>
<b>Explanation</b>	An attempt to access a file failed.
<b>Action</b>	Ensure that the file exists at the specified location.
<b>POP.011.0034E</b>	<b>Size read mismatch "{0}" vs "{1}"</b>
<b>Explanation</b>	An InputStream corruption error occurred.
<b>Action</b>	Examine the _problems_.log file for the stack trace of the error. The stack trace may not provide enough detail to explain why the error was thrown, but it will show where the error originated.

<b>POP.011.0035</b>	<b>Cannot create temporary folder: "{0}"</b>
<b>Explanation</b>	Folder creation failed.
<b>Action</b>	Most likely, the current process lacks Write access to the configured temporary folder.
<b>POP.011.0036E</b>	<b>Unable to delete file: "{0}"</b>
<b>Explanation</b>	An error occurred while removing a temporary file.
<b>Action</b>	Find the specified file and remove it manually.
<b>POP.011.0037E</b>	<b>Unable to delete directory: "{0}"</b>
<b>Explanation</b>	An error occurred while cleaning up temporary files.
<b>Action</b>	Find the specified directory and manually remove the temporary files.
<b>POP.011.0039E</b>	<b>ObjectUtil: illegal arguments.</b>
<b>Explanation</b>	An error occurred while setting a property on an object, because the target object is null or the property name is null or empty.
<b>Action</b>	Examine the <code>_problems_.log</code> file for the stack trace of the error. The stack trace may not provide enough detail to explain why the error was thrown, but it will show where the error originated.
<b>POP.011.0044E</b>	<b>Error obtaining JMS topic for name: "{0}"</b>
<b>Explanation</b>	The requested JMS topic is not available.
<b>Action</b>	Verify that Broker is running and that My webMethods Server can connect to the computer on which Broker is running.
<b>POP.011.0045E</b>	<b>no JMS provider, requesting topic name: "{0}"</b>
<b>Explanation</b>	The JMS provider appears to be disconnected.
<b>Action</b>	Verify that Broker is running and that My webMethods Server can connect to the computer on which Broker is running.
<b>POP.011.0046E</b>	<b>JMSTopic.createTopicSession(), no JMS provider.</b>
<b>Explanation</b>	The JMS provider appears to be disconnected.
<b>Action</b>	Verify that Broker is running and that My webMethods Server can connect to the computer on which Broker is running.

---

<b>POP.011.0047E</b>	<b>Unable to connect to registry.</b>
<b>Explanation</b>	The My webMethods Server configuration registry is unavailable.
<b>Action</b>	In a cluster deployment, make sure the Master server is started before starting the other cluster nodes.
<b>POP.011.0048</b>	<b>no protocol defined for: "{0}"</b>
<b>Explanation</b>	The system tried to load a file from an unknown protocol.
<b>Action</b>	Check the protocol string spelling.
<b>POP.011.0053E</b>	<b>Error obtaining JMS queue for name: "{0}"</b>
<b>Explanation</b>	The requested JMS queue is unavailable.
<b>Action</b>	Verify that Broker is running and that My webMethods Server can connect to the computer on which Broker is running.
<b>POP.011.0054E</b>	<b>no JMS provider, requesting queue name: "{0}"</b>
<b>Explanation</b>	The JMS provider appears to be disconnected.
<b>Action</b>	Verify that Broker is running and that My webMethods Server can connect to the computer on which Broker is running.
<b>POP.011.0055E</b>	<b>JMSTopic.createQueueSession(), no JMS provider.</b>
<b>Explanation</b>	The JMS provider appears to be disconnected.
<b>Action</b>	Verify that Broker is running and that My webMethods Server can connect to the computer on which Broker is running.
<b>POP.011.0056E</b>	<b>Invalid line: "{0}"</b>
<b>Explanation</b>	An error occurred in parsing a .properties file.
<b>Action</b>	Look in the _problems_.log file for the stack trace of the error. The stack trace may not provide enough detail to explain why the error was thrown, but it will show where the error originated.
<b>POP.011.0057E</b>	<b>JMSDestination.Subscriber, unable to create consumer on: "{0}"</b>
<b>Explanation</b>	The JMS provider appears to be disconnected.
<b>Action</b>	Verify that Broker is running and that My webMethods Server can connect to the computer on which Broker is running.

- POP.011.0058E**      **JMSDestination.Subscriber, unable to create session for: "{0}"**  
**Explanation**      The JMS provider appears to be disconnected.  
**Action**              Verify that Broker is running and that My webMethods Server can connect to the computer on which Broker is running.
- POP.011.0062E**      **Stream exhausted.**  
**Explanation**      An error occurred in decoding a BASE64 String.  
**Action**              Examine the \_problems\_.log file for the error stack trace. The stack trace may not provide enough detail to explain why the error was thrown, but it will show where the error originated.
- POP.011.0063E**      **BASE64Encoder: Bad Padding byte.**  
**Explanation**      An error occurred in decoding a BASE64 String.  
**Action**              Examine the \_problems\_.log file for the error stack trace. The stack trace may not provide enough detail to explain why the error was thrown, but it will show where the error originated.
- POP.011.0065**      **There must be a default entry --> default=icon\_def.gif.**  
**Explanation**      The iconMap.properties file is corrupted.  
**Action**              Revert any changes made to this file.
- POP.011.0068**      **Output stream not set for: "{0}"**  
**Explanation**      An error occurred during page rendering.  
**Action**              Check the logs for problems that result in this situation.
- POP.011.0076**      **Unable to convert data type "{0}" to "{1}"**  
**Explanation**      The system failed in the attempted type coercion.  
**Action**              If possible, check the input value to ensure that it can be properly coerced to the target data type.
- POP.012.0001.tagname\_error – Not a valid value!Tag Name cannot contain spaces.**  
**Explanation**      The Tag Name cannot contain spaces.  
**Action**              Make sure the value of the Tag Name field is correct.

**POP.012.0001.wm\_axsrftconfig – This action requires a custom anti-cross-site-request-forgery token.**

**Explanation** An invalid custom token is provided during portlet configuration.  
**Action** Check and, if needed, re-configure the New Secret Interval and Oldest Secret preferences in wm\_axsrftconfig.

**POP.012.0001.wm\_caf\_task – Cannot upload this file as it is empty.Uploading empty files is not allowed.**

**Explanation** Content cannot contain an empty file, therefore uploading is not allowed  
**Action** Make sure that the file contains content.

**POP.012.0001.wm\_calendar – Illegal "{0}" parameter value: "{1}".**

**Explanation** The start date of an entry in the calendar is missing.  
**Action** Specify the start date of the entry in the calendar.

**POP.012.0001.wm\_cforms\_layout – Recursive use of Composite Form for "{0}".**

**Explanation** The composite form for "{0}" is attempting to display an item that displays the same composite form for "{0}". For instance, the composite form for "{0}" is displaying a form containing the same composite form for "{0}"  
**Action** Change the composite form for "{0}" "view" property to a different item.

**POP.012.0001.wm\_commonsearchbar – Search Context Portlet URI is not valid: {0}**

**Explanation** Search context portlet URI is not valid.  
**Action** Specify a valid search context portlet.

**POP.012.0001.wm\_commonsearchresults – Search Context Portlet URI is not valid: {0}**

**Explanation** The search context portlet URI is not valid.  
**Action** Specify a valid search context portlet.

**POP.012.0001.wm\_contentrendererE – Unable to parse regexps: {0}**

**Explanation** The My webMethods Server installation is missing RegEx support jars.  
**Action** Reinstall My webMethods Server.

**POP.012.0001.wm\_dirsearchcontext – This portlet is not intended to be viewed standalone**

**Explanation** This portlet is not intended to be viewed as standalone.  
**Action** Do not view this portlet as a standalone portlet.

**POP.012.0001.wm\_discotres\_forumview – Forum or category not specified.**

**Explanation** The forum or category should not be null.  
**Action** Specify the forum or category for the forum view.

**POP.012.0001.wm\_discotres\_forumwizard – Must specify "parent" property.**

**Explanation** The "parent" property must not be empty.  
**Action** Enter a valid "parent" property.

**POP.012.0001.wm\_discotres\_messageview – Forum message not specified.**

**Explanation** The forum requires some messages for proper notification.  
**Action** Provide the messages needed for the message view resources.

**POP.012.0001.wm\_discotres\_topicview – Forum topic not specified.**

**Explanation** Specify the correct forum topic.  
**Action** Specify a valid forum topic.

**POP.012.0001.wm\_fabric\_addtostart – You already have an instance of this portlet on the target page.**

**Explanation** You already have an instance of this portlet on the target page.  
**Action** Choose another portlet to add.

**POP.012.0001.wm\_formattedxml – No content available for {0}.**

**Explanation** No content can be retrieved from the specified style sheet.  
**Action** Make sure that the style sheet has content.

**POP.012.0001.wm\_inlinecontent – No content available for {0}.**

**Explanation** No content can be retrieved.  
**Action** Make sure the resource has content.

**POP.012.0001.wm\_jazzy – Not a valid dictionary identifier: "{0}".**

**Explanation** The dictionary ID provided is not valid.  
**Action** Provide a valid dictionary ID.

**POP.012.0001.wm\_mws\_diagnostics – No Performance Service is currently available. To enable the Service, please go to the properties page of this portlet.**

**Explanation** No performance service is currently enabled.  
**Action** To enable a service, go to the properties page of the Performance Analysis portlet.

**POP.012.0001.wm\_noodle – Cannot load page content.**

**Explanation** The page fails to load the content.  
**Action** Check if the file exists and if the path of the file is correct.

**POP.012.0001.wm\_noodle\_context\_wiring – This portlet has no UI.**

**Explanation** The specified portlet deployed on the server has no user interface.  
**Action** Go to Folders > Administrative Folders > Administration Dashboard > Configuration > Install Administration and re-install the portlet.

**POP.012.0001.wm\_ntlmv2authadmin – NTLM authentication failed because login has been disabled for the {0} user.**

**Explanation** The Directory Service reports that the 'Diisabled' attribute for the user record is set to true. This user cannot authenticate with My webMethods Server.  
**Action** To enable this user to authenticate with My webMethods Server, set the 'Diisabled' attribute to false in the appropriate directory server.

**POP.012.0001.wm\_portletinportletE – Recursive use of Portlet-in-Portlet for "{0}".**

**Explanation** Portlet-in-Portlet is attempting to display an item that displays the same Portlet-in-Portlet (for instance, the Portlet-in-Portlet is displaying a portal page containing the same Portlet-in-Portlet).  
**Action** Change the Portlet-in-Portlet's "Portal Page" property to a different item.

**POP.012.0001.wm\_principalprofileadmin – You don't have rights to modify the properties of this item.**

**Explanation** The current user does not have sufficient privileges to make changes to this portlet  
**Action** Contact a My webMethods Server system administrator to modify the current user's permissions.

**POP.012.0001.wm\_propertiesE – {0} is not specified.**

**Explanation** The Properties portlet could not locate the object to show its properties.  
**Action** Close and reopen the internet browser window.

**POP.012.0001.wm\_publish.NotLicensed – The "Publish" feature is disabled because this deployment is not licensed.**

**Explanation** The requested feature is not part of the used license.  
**Action** If you want to use this feature, you should buy and install the appropriate license.

**POP.012.0001.wm\_publish.ToEnable – To enable the "Publish" feature please contact webMethods to obtain a Portal license.**

**Explanation** The requested feature is not part of the used license. Contact Software AG to obtain the Portal license to enable the "Publish" feature.  
**Action** To use the "Publish" feature, you should buy and install the appropriate Portal license.

**POP.012.0001.wm\_sessionmonitor – The view "{0}" is not available.**

**Explanation** Unable to fetch the view context from the server.  
**Action** Try republishing the portlet to the server.

**POP.012.0001.wm\_shelladmin – A shell with the system name "{0}" already exists.**

**Explanation** The same system name is not allowed for two different shells. This error occurs when an attempt is made to save a shell with a system name that already exists.  
**Action** Specify a unique system name for the shell.

**POP.012.0001.wm\_shelleditorE – Cannot clone parent's shell section because it is not a Portal Page.**

**Explanation** Some legacy shells created before Portal 6.2 or customer-created shells may have a raw JSP page assigned to a shell section. Such shells cannot be cloned.  
**Action** Rework the legacy shell to use portal pages instead of JSP pages.

**POP.012.0001.wm\_skinadmin – A skin with the system name "{0}" already exists.**

**Explanation** The same system name is not allowed for two different skins. This error occurs when an attempt is made to save a skin with a system name that already exists.  
**Action** Specify a unique system name for the skin.

**POP.012.0001.wm\_skineditorE – {0} is not a valid skin.**

**Explanation** The specified skin object is not a valid portal skin.  
**Action** Log off from My webMethods and log back in.

**POP.012.0001.wm\_spm\_commandex – "{0}" does not identify a user or group.**

**Explanation** The supplied URI is not a valid user or group.  
**Action** Specify a correct URI.

**POP.012.0001.wm\_sysdirsvc – Unable to locate principal: {0}**

**Explanation** The principal cannot be retrieved using the provided principal URI.  
**Action** Check the server log for the principal URI that was used and make sure the principal URI is valid. Contact an administrator if the principal URI is valid but the issue persists.

**POP.012.0001.wm\_table – Illegal "{0}" property value: "{1}".**

**Explanation** An invalid value is specified for the property.  
**Action** Check the log for information about the value that was specified for the property. Specify a valid value for the property.

**POP.012.0001.wm\_tabs – Illegal "{0}" property value: "{1}".**

**Explanation** An invalid value is specified for the property.  
**Action** Check the log for information about the value that was specified for the property. Specify a valid value for the property.

**POP.012.0001.wm\_thumbnailagentE – Error executing external process**

**Explanation** The Thumbnail agent has failed to execute an external process to prepare thumbnails.  
**Action** Use the Install Administration portlet to reinstall the wm\_thumbnailagent portlet.

**POP.012.0001.wm\_tree – Illegal "{0}" property value: "{1}".**

**Explanation** An invalid value is used for the specified property.  
**Action** Check the server log for the value used for the property. Make sure a valid value is used.

**POP.012.0001.wm\_universalpicker – Cannot resolve portlet ID for "{0}".**

**Explanation** Cannot retrieve the thing using the specified ID.

**Action** Check the server log for the ID that cannot be retrieved and make sure that the ID is valid. Contact an administrator if you think that the ID is valid but the error persists.

**POP.012.0001.wm\_userhomefolderE – Empty "{0}" property.**

**Explanation** The user ID is either invalid or was not found.

**Action** Use the User Home folder portlet to refresh the page.

**POP.012.0001.wm\_userprofilewiring – This portlet has no UI.**

**Explanation** The specified portlet deployed on the server has no user interface.

**Action** Go to Folders > Administrative Folders > Administration Dashboard > Configuration > Install Administration and re-install the portlet.

**POP.012.0001.wm\_versionE – Unable to acquire publish portlet controller bean.**

**Explanation** An internal portlet error has occurred.

**Action** Log off from My webMethods and log back in.

**POP.012.0001.wm\_webclipE – Cannot clip from "{0}" because it is not an HTTP resource.**

**Explanation** The Webclip portlet has failed to connect to the specified URL and get its HTML content.

**Action** Check the URL specified for the Webclip portlet.

**POP.012.0001.wm\_wiringE – Can only wire portlets**

**Explanation** An attempt was made to wire a non-portlet.

**Action** You can only wire portlets.

**POP.012.0001.wm\_xt\_dbdirsvc – Directory could not authenticate this user**

**Explanation** The user cannot be authenticated with the specified credentials.

**Action** Make sure the user credentials are valid.

**POP.012.0001.wm\_xt\_dbrole – An error occurred executing the SQL query: "{0}". Please type a valid query and try again.**

**Explanation** The SQL query is invalid.

**Action** The server log contains the invalid SQL query. Use a valid SQL query.

**POP.012.0001.wm\_xt\_extdirsvc – Directory could not authenticate this user**

**Explanation** The user cannot be authenticated with the specified credentials.

**Action** Make sure the user credentials are valid.

**POP.012.0001.wm\_xt\_ldapdirsvc – This directory service does not support creating Users or Groups**

**Explanation** The LDAP directory service does not support creating users or groups.

**Action** Contact an administrator if you want to create users or groups.

**POP.012.0001.wm\_xt\_oauthsvc – Verification of the IdToken failed!**

**Explanation** Verification of the ID Token (security token) that contains claims about the authentication of a user by an authorization server failed. The failure may occur due to the following reasons: 1.The issuer identifier for the OpenID Provider obtained during discovery does not match the value of the iss (issuer) claim.2. The ID Token does not list the client (client\_id) as a valid audience (aud).

**Action** Check the OAuth configuration 'OAuth 2.0 Client Identifier' parameter.

**POP.012.0001.wm\_xt\_portalrules – Unknown rule thing: {0}**

**Explanation** The type of rule cannot be determined.

**Action** Check the server log for the rule ID that cannot be determined and make sure that the ID is valid. Contact an administrator if you think that the ID is valid but the error persists.

**POP.012.0001.wm\_xt\_rssfeed – age not found: {0}**

**Explanation** The specified RSS Feed Resource age "{0}" does not exist.

**Action** Examine the warning message and confirm that the age {0} exists.

**POP.012.0001.wm\_xt\_ruleE – The current IDirectoryUser is null.**

**Explanation** Rule matching has failed to load the user.

**Action** Log off from My webMethods and log back in.

**POP.012.0001.wm\_xt\_samlsecurityservice – The input document contains no elements.**

**Explanation** The input document contains no elements.  
**Action** Make sure that a valid document that is not empty is passed.

**POP.012.0001.wm\_xt\_shell – Cannot delete "{0}" because it is the default system shell.**

**Explanation** The default system shell cannot be deleted.  
**Action** Do not attempt to delete the default system shell.

**POP.012.0001.wm\_xt\_shortcutE – Unhandled object type found for the wm\_xt\_shortcut URL property: {0}**

**Explanation** An invalid object type was referenced by a shortcut.  
**Action** Delete the specified object and start over.

**POP.012.0001.wm\_xt\_skinE – Cannot delete "{0}" because it is the default system skin.**

**Explanation** The portal skin specified as the default skin cannot be deleted.  
**Action** Before deleting the skin, use the Skin Administration portlet to specify another skin as the default.

**POP.012.0001.wm\_xt\_ssolink – Failed to generate SAML artifact, artifact is null**

**Explanation** The SAML artifact cannot be generated.  
**Action** Make sure that the item thing ID and user ID are valid, and that the SAML service is running.

**POP.012.0001.wm\_xtypeviewE – You have not specified an object to display in this portlet.**

**Explanation** The Xtype View portlet does not have a valid target object to display.  
**Action** Update the Xtype View portlet properties and specify a valid DBO to display.

**POP.012.0002.wm\_caf\_task – Cannot connect to webMethods Content Service Platform Server on {0} : {1} . Please make sure the server is available.**

**Explanation** webMethods Content Service Platform is either not running, disconnected, or the environment configuration defined in My webMethods is incorrect.  
**Action** Make sure the CSP server is running; ensure that network connectivity is available; check the CSP environment configuration in My webMethods and verify the connection values.

**POP.012.0002.wm\_commonsearchbar – Search Context Portlet does not implement ISearchContext interface**

**Explanation** The search context portlet does not implement the ISearchContext interface.

**Action** Make sure the search context portlet implements the ISearchContext interface.

**POP.012.0002.wm\_commonsearchresults – Search Context Portlet does not implement ISearchContext interface**

**Explanation** The search context portlet does not implement the ISearchContext interface.

**Action** Make sure the search context portlet implements the ISearchContext interface.

**POP.012.0002.wm\_contentrenderere – Requested content was not found: "{0}"**

**Explanation** The server attempted to download invalid content.

**Action** Verify that valid content is present at the source location and can be downloaded.

**POP.012.0002.wm\_dirsearchcontext – Failed to move to next principal in directory services, service={0}, error={1}**

**Explanation** The directory search cannot continue because an exception was thrown when attempting to go to the next page search. No search results are returned.

**Action** Check the My webMethods Server log for the directory service used for the search and the exception that was thrown. Provide the log details to an administrator.

**POP.012.0002.wm\_discotres\_forumview – Can display listing for forum or category only.**

**Explanation** Only the listing for forum or category is displayed successfully.

**Action** No action required.

**POP.012.0002.wm\_discotres\_forumwizard – Must specify "target" property.**

**Explanation** The "target" property must not be empty.

**Action** Enter a valid "target" property.

**POP.012.0002.wm\_discotres\_messageview – Can display forum message only.**

**Explanation** Only forum messages are displayed successfully.

**Action** No action is required.

**POP.012.0002.wm\_discotres\_topicview – Can display listing for forum topic only.**

**Explanation** Only the listing for forum topic is displayed successfully.  
**Action** No action required.

**POP.012.0002.wm\_jazzy – Not a valid dictionary: "{0}".**

**Explanation** The dictionary specified is not valid.  
**Action** Provide a valid dictionary.

**POP.012.0002.wm\_publish – Please select a type to publish.**

**Explanation** The 'type' input parameter must be set to 'publish'.  
**Action** Provide an allowed value. The 'type' input parameter must be set to 'publish'.

**POP.012.0002.wm\_sessionmonitor – Use this portlet to monitor real-time user activity and send status messages to user(s) via e-mail. Click the appropriate column heading to sort by User Name, Location (Host ID), or Administrator status.**

**Explanation** Use this portlet to monitor real-time user activity and to send status messages to users by e-mail. Click the appropriate column heading to sort by User Name, Location (Host ID), or Administrator status.  
**Action** For more information, see the PDF publication, "My webMethods Server Portlet Reference."

**POP.012.0002.wm\_shelladmin – A shell with the display name "{0}" already exists.**

**Explanation** The same display name is not allowed for two different shells. This error occurs when an attempt is made to save a shell with a display name that already exists.  
**Action** Specify a unique system name for the shell.

**POP.012.0002.wm\_skinadmin – A skin with the display name "{0}" already exists.**

**Explanation** The same display name is not allowed for two different skins. This error occurs when an attempt is made to save a skin with a display name that already exists.  
**Action** Specify a unique display name for the skin.

**POP.012.0002.wm\_skineditor – feature not recognized: {0}**

**Explanation** The feature is not recognized.  
**Action** Contact Software AG Global Support. For contact information, log in to <https://empower.softwareag.com/>.

**POP.012.0002.wm\_spm\_commandex – Invalid argument supplied.**

**Explanation** An invalid argument was supplied as a parameter in the request map.  
**Action** Check the arguments for the command request.

**POP.012.0002.wm\_sysdirsvc – Password attribute is missing**

**Explanation** No password information is provided when creating a new principal.  
**Action** Provide a password attribute when creating a new principal.

**POP.012.0002.wm\_systemcontent – <div class="portlet-msg-error"><h3>Attempted redirect to a restricted host. </h3></div>**

**Explanation** My webMethods Server does not allow redirects to arbitrary URLs. In this case the URL was not configured as an acceptable redirect host.  
**Action** Ask the My webMethods Server administrator to modify the Server Redirect WhiteList to allow redirects to this foreign URL.

**POP.012.0002.wm\_userhomefolder – This user does not have a home folder. Note that the Portal typically does not create a home folder for a user until the user logs in for the first time.**

**Explanation** The user does not have a home folder.  
**Action** Note that the Portal typically does not create a home folder for a user until the user logs in for the first time. Contact an administrator if this problem persists after the user logs in.

**POP.012.0002.wm\_versionE – Unable to acquire target resource: {0}**

**Explanation** An internal portlet error has occurred.  
**Action** Log off from My webMethods and log back in.

**POP.012.0002.wm\_wiringE – {0} is not a normal thing**

**Explanation** An attempt was made to wire an invalid portlet instance.  
**Action** Delete the specified portlet and locate the correct portlet.

**POP.012.0002.wm\_xt\_extdirsvc – This directory service does not support creating Users or Groups**

**Explanation** This external directory service does not support creating users or groups.  
**Action** Create an administrator if you want to create users or groups.

**POP.012.0002.wm\_xt\_ldapdirsvc – This directory service does not support deleting Users or Groups**

**Explanation** The LDAP directory service does not support deleting users or groups.  
**Action** Contact an administrator if you want to delete users or groups.

**POP.012.0002.wm\_xt\_oauthsvc – The discovery document response is not valid.**

**Explanation** Unable to obtain configuration information about the OpenID provider, including information about all the necessary endpoints and public key location.  
**Action** Check the OAuth configuration 'Discovery Document URL' parameter.

**POP.012.0002.wm\_xt\_portalrules – Unable to resolve user id: {0}**

**Explanation** The principal information cannot be retrieved using the specified ID.  
**Action** Check the server log for the principal ID that cannot be retrieved and make sure that the ID is valid. Contact an administrator if you think that the ID is valid but the error persists.

**POP.012.0002.wm\_xt\_rssfeed – refresh interval not found: {0}**

**Explanation** The specified RSS Feed Resource refresh interval "{0}" does not exist.  
**Action** Provide a valid value for the input variable refresh interval :{0}.

**POP.012.0002.wm\_xt\_samlsecurityservice – The SAML artifact is invalid or has expired.**

**Explanation** The SAML artifact is invalid because it provides wrong information for the cluster index.  
**Action** Make sure the SAML artifact has the correct information.

**POP.012.0002.wm\_xt\_shell – Cannot delete "{0}" because it is the base system shell.**

**Explanation** The base system shell cannot be deleted.  
**Action** Do not attempt to delete the base system shell.

**POP.012.0002.wm\_xt\_skinE – Cannot delete "{0}" because it is the base system skin.**

**Explanation** The portal skin specified as the base system skin cannot be deleted.  
**Action** The base portal skin cannot be deleted because it is used as a parent for all other portal skins.

**POP.012.0002.wm\_xt\_wikiobject – Wiki with such name already exists**

**Explanation** A wiki with such a name already exists.  
**Action** Use a unique name for the wiki.

**POP.012.0003.wm\_commonsearchbar – None of the portlet tabs are visible**

**Explanation** None of the portlet tabs are visible for the search bar.  
**Action** Make sure that the search options are set.

**POP.012.0003.wm\_commonsearchresultsE – Failed to parse the max search results setting of "{0}", using default of "{1}"**

**Explanation** The common search code is attempting to build a search query object from a query string that was passed into it. The query string supplied contains an invalid value for the 'maxResults' setting. The warning message is written to the logs and the process continues with the default maxResults value.  
**Action** Make sure the portlet that invokes the API supplies a valid number for the 'maxResults' setting in the search query string. Typically, the end user would not cause this scenario because the wm\_commonsearchbar portlet that usually builds the query string validates the maxResults field before allowing the submission of the search form.

**POP.012.0003.wm\_contentseviceadmin – Cannot start a new content import process because another content import process is currently running.**

**Explanation** You cannot start a new content import process because another content import process is currently running.  
**Action** Wait until the content import in progress completes.

**POP.012.0003.wm\_dirsearchcontext – Failed to convert short move to next principal in directory services, service={0}, error={1}**

**Explanation** The internal ID is not a valid integer.  
**Action** Check the My webMethods Server log for the directory service used for the search and the exception that was thrown. Provide the log details to an administrator.

**POP.012.0003.wm\_discotres\_topicview – Must specify "target" property.**

**Explanation** The "target" property must not be empty.  
**Action** Enter a valid "target" property.

**POP.012.0003.wm\_jazzy – Cannot load dictionary "{0}" because an I/O error occurred.**

**Explanation** The specified dictionary cannot be loaded.  
**Action** Make sure that the dictionary is accessible.

**POP.012.0003.wm\_noodle – Cannot load portlet content.**

**Explanation** The portlet fails to load the content.  
**Action** Check if the portlet has content and if the path of the portlet is correct.

**POP.012.0003.wm\_ntlmv2authadmin – Field [{0}] is required.**

**Explanation** A necessary form field was not provided.  
**Action** Review the form and fill out all required fields, then resubmit.

**POP.012.0003.wm\_sessionmonitor – No sessions are available for this Portal Node.**

**Explanation** No sessions are available for this portal node.  
**Action** Try republishing the portlet to the server.

**POP.012.0003.wm\_shelladminE – The URI "{0}" does not identify a valid shell.**

**Explanation** The shell instance is not a valid portal shell object type.  
**Action** Restart the My webMethods Server to flush the internal caches.

**POP.012.0003.wm\_skinadminE – The URI "{0}" does not identify a valid skin.**

**Explanation** The skin instance is not a valid portal skin type.  
**Action** Restart My webMethods Server to flush the internal caches.

**POP.012.0003.wm\_skineditor – property not recognized: {0}**

**Explanation** The property is not recognized.  
**Action** Make sure this particular editor resource is declared correctly.

**POP.012.0003.wm\_spm\_commandex – Cannot create env entry. Entry already exists.**

**Explanation** There is a duplicate entry with that name.  
**Action** Specify a different name for the entry.

**POP.012.0003.wm\_tree – The "{0}" property value must begin with a '{' character.**

**Explanation** The property value should begin with a "{" character.  
**Action** Make sure that the property value begins with a "{" character.

**POP.012.0003.wm\_wiring – You don't have rights to modify the wiring of this item.**

**Explanation** The current user does not have sufficient permissions to modify the wiring properties of this portlet.  
**Action** Contact your My webMethods Server administrator to modify your user permissions.

**POP.012.0003.wm\_xt\_dbdirsvc – This directory service does not support deleting Users or Groups**

**Explanation** The database directory service does not support deleting users or groups.  
**Action** Contact an administrator if you want to delete users or groups.

**POP.012.0003.wm\_xt\_extdirsvc – This directory service does not support deleting Users or Groups**

**Explanation** This external directory service does not support deleting users or groups.  
**Action** Contact an administrator if you want to delete users or groups.

**POP.012.0003.wm\_xt\_ldapdirsvc – This directory service does not support modifying User or Group memberships**

**Explanation** The LDAP directory service does not support modifying users or groups.  
**Action** Contact an administrator if you want to modify users or groups.

**POP.012.0003.wm\_xt\_oauthsvc – Unable to obtain OSGI service reference: {0}**

**Explanation** The lookup for the OAuth user service failed.  
**Action** If a user service application is defined in the OAuth configuration, check if the user service application is deployed correctly.

**POP.012.0003.wm\_xt\_portalrules – Deprecated method {0} is not valid on wm\_xt\_portalrules**

**Explanation** The method is deprecated and should not be invoked.  
**Action** Use only supported methods.

**POP.012.0003.wm\_xt\_rssfeedE – Unable to find suitable factory for: {0}**

**Explanation** An RSS feed has failed to parse RSS content.

**Action** Choose another RSS feed.

**POP.012.0003.wm\_xt\_samlsecurityservice – Unable to locate principal "{0}".**

**Explanation** Directory principal information cannot be retrieved.

**Action** Make sure the SAML artifact contains correct directory principal information.

**POP.012.0004.wm\_commonsearchbar – Saved Search Name has already been used.**

**Explanation** The saved search name has already been used.

**Action** Specify a different search name.

**POP.012.0004.wm\_commonsearchresults – Failed to retrieve data from : {0} LDAPs**

**Explanation** The specified directory services failed to return a result due to an error.

**Action** Check the My webMethods Server logs for errors related to the specified directory services.

**POP.012.0004.wm\_contentseviceadminE – Content service not found: "{0}".**

**Explanation** The content service is no longer valid.

**Action** If you cannot reconfigure the offending content service by using the Content Service Admin portlet, contact Software AG Global Support for a reset directive.

**POP.012.0004.wm\_dirsearchcontext – Failed to evaluate expression for object, exp={0}, obj={1}, error={2}**

**Explanation** The expression cannot be evaluated.

**Action** Check the My webMethods Server log to determine the expression and the exception that was thrown. Provide the log details to an administrator.

**POP.012.0004.wm\_mws\_diagnostics – Performance Service does not support serialization.**

**Explanation** The currently running performance service does not support data serialization, therefore a snapshot cannot be exported.

**Action** Switch to a performance service that supports serialization.

**POP.012.0004.wm\_ntlmv2authadmin – Jespa library is required.**

**Explanation** NTLMV2 will not function without the Jespa library.

**Action** Contact Software AG Global Support for information about downloading the Jespa library from [jespa.org](http://jespa.org).

**POP.012.0004.wm\_portalaliassearchcontext – One or more of the requested aliases can not be removed**

**Explanation** One or more of the requested aliases can not be removed.

**Action** Before deleting an alias, verify that it exists and that it is not a system alias.

**POP.012.0004.wm\_shelladminE – Cannot delete "{0}" because it is the default system shell.**

**Explanation** The default portal shell cannot be deleted.

**Action** Use the Shell Administration portlet to specify another shell as the default, and then delete the first shell.

**POP.012.0004.wm\_skineditor – can't resolve input source: {0}**

**Explanation** The input resource provided is incorrect.

**Action** Provide the correct input resource.

**POP.012.0004.wm\_spm\_commandex – "{0}" argument not supplied.**

**Explanation** The required argument is not provided.

**Action** Check the provided arguments.

**POP.012.0004.wm\_tree – Cannot render resource as tree fragment.**

**Explanation** The resource content is empty.

**Action** Make sure that the resource has content.

**POP.012.0004.wm\_wiki\_createnew – Please provide the container for wiki**

**Explanation** The container is not provided for the wiki.

**Action** Provide the container for the wiki.

**POP.012.0004.wm\_xt\_dbdirsvc – This directory service does not support modifying User or Group memberships**

**Explanation** The database directory service does not support modifying users or groups.

**Action** Contact an administrator if you want to modify users or groups.

**POP.012.0004.wm\_xt\_extdirsvc – This directory service does not support modifying User or Group memberships**

**Explanation** This external directory service does not support modifying users or groups.

**Action** Contact an administrator if you want to modify users or groups.

**POP.012.0004.wm\_xt\_ldapdirsvc – No valid "{0}" found for the principal "{1}" from "{2}" directory service. Please check if ID attribute is valid in the Directory Services Configuration**

**Explanation** No principal is found in the LDAP directory service using the specified name.

**Action** Use a valid name when searching for the principal in the LDAP directory service.

**POP.012.0004.wm\_xt\_portalrules – Web application is not deployed or available {0}. Cannot evaluate {1}**

**Explanation** The specified web application is not deployed or available. As a result, My webMethods Server cannot evaluate the specified function.

**Action** Make sure that the specified web application is deployed and available.

**POP.012.0005.wm\_contentserviceadminE – Cannot remove default content service.**

**Explanation** The default content service cannot be deleted.

**Action** My webMethods Server disallows the deletion of the default content service.

**POP.012.0005.wm\_dirsearchcontext – Failed to create a directory service iterator, dirService={0}, error={1}**

**Explanation** A problem was encountered while trying to iterate through a directory service.

**Action** Check the server log for information about the directory service and the exception that was thrown. Provide the log details to an administrator.

**POP.012.0005.wm\_jazzy – Please specify text to check.**

**Explanation** The specified text is empty.

**Action** Specify the text to check.

**POP.012.0005.wm\_mws\_diagnostics – Wrong Import File format.**

**Explanation** The file you are trying to import was exported from a performance service that is different from the one currently running.

**Action** Check the portlet preferences and make sure the correct performance service is running.

---

**POP.012.0005.wm\_ntlmv2authadmin – Configuration test failed. Please double check all the required parameters.**

**Explanation** The specified configuration is not valid. NTLMv2 authentication will not succeed until the parameters are corrected.

**Action** Review the NTLMv2 configuration and modify parameters as required.

**POP.012.0005.wm\_portalaliassearchcontext – Unable to add alias "{0}" because an alias with that name already exists.**

**Explanation** Unable to add alias because an alias with that name already exists.

**Action** Create a unique alias name.

**POP.012.0005.wm\_shelladminE – Cannot delete "{0}" because it is the base system shell.**

**Explanation** The shell could not be deleted because it is a parent shell for other deployed shells.

**Action** My webMethods Server explicitly disallows deletion of the base shell.

**POP.012.0005.wm\_skineditor – cannot rename "{0}" to "{1}"**

**Explanation** The field name "{1}" already exists.

**Action** Specify a unique field name.

**POP.012.0005.wm\_spm\_commandex – Neither "{0}" or "{1}" arguments are supplied.**

**Explanation** Neither the first nor the second argument was provided.

**Action** Provide at least one argument.

**POP.012.0005.wm\_xt\_dbdirsvc – Directory could not load principal data, "{0}" attribute is missing**

**Explanation** The principal data cannot be loaded because the specified attribute is missing.

**Action** Check the log file for the missing attribute. Contact an administrator to make sure the specific principal is valid and has the specified attribute.

**POP.012.0005.wm\_xt\_extdirsvc – No data service defined**

**Explanation** The OSGi external directory service could not be found.

**Action** Check if the external directory service is defined correctly.

**POP.012.0005.wm\_xt\_ldapdirsvc – Unable to locate "{0}" directory service. It might have been disabled.**

**Explanation** The LDAP directory service cannot be located.  
**Action** Make sure the LDAP directory service is enabled.

**POP.012.0006.wm\_contentsserviceadmin – You do not have sufficient rights to modify content service "{1}".**

**Explanation** You do not have sufficient rights to modify this content service.  
**Action** An administrator must assign modify permission to the current user. Otherwise, modify the content service as an Administrator user.

**POP.012.0006.wm\_dirsearchcontext – Not a valid attribute filter string, string={0}**

**Explanation** The attribute filter string specified is not valid.  
**Action** Provide a valid attribute filter string. The server log file contains information about the invalid value.

**POP.012.0006.wm\_portalaliassearchcontext – Unable to update alias "{0}" because an existing alias with that name could not be found.**

**Explanation** Unable to update alias because an existing alias with that name could not be found.  
**Action** Select an existing alias to update, or create a new alias.

**POP.012.0006.wm\_shelladmin – "{0}" does not identify a legacy shell.**

**Explanation** The shell instance is not a valid legacy shell object type.  
**Action** Restart the My webMethods Server to flush the internal caches.

**POP.012.0006.wm\_spm\_commandex – Could not modify environment variable. Variable not found**

**Explanation** The variable was not found.  
**Action** Check and refresh the environment variables list.

**POP.012.0006.wm\_xt\_dbdirsvc – An error occurred executing the SQL query: "{0}". Please type a valid query and try again.**

**Explanation** The SQL query is invalid.  
**Action** Make sure that the SQL query is valid. Contact an administrator if you are sure your SQL is valid.

**POP.012.0006.wm\_xt\_extdirsvc – Unable to instantiate class: {0}**

**Explanation** The OSGi external directory service is not defined or exposed correctly.  
**Action** Check if the external directory service is defined correctly.

**POP.012.0006.wm\_xt\_samlsecurityservice – Unable to locate server within cluster to validate the SAML artifact, index={0}**

**Explanation** The server specified in the SAML artifact cannot be located within the cluster.  
**Action** Make sure the SAML artifact contains the correct server index information.

**POP.012.0007.wm\_contentserviceadmin – A content service with a name of "{0}" already exists.**

**Explanation** A content service with the same name already exists.  
**Action** Define a unique name when adding a new content service,

**POP.012.0007.wm\_dirsearchcontext – Not a valid attribute filter string, missing separator, string={0}**

**Explanation** The specified string does not have a valid attribute filter separator.  
**Action** Provide a valid attribute filter separator. You can find the invalid value in the server log file.

**POP.012.0007.wm\_mws\_diagnostics – Performance Service is not running. No data is available.**

**Explanation** No performance service currently is running, so there is no data to display.  
**Action** Enable a performance service and allow time for it to collect some data, then retry.

**POP.012.0007.wm\_portalaliassearchcontext – This portlet is not intended to be viewed standalone**

**Explanation** This portlet is not intended to be viewed as an individual portlet, outside of another portlet.  
**Action** Avoid using this portlet as a single stand-alone portlet.

**POP.012.0007.wm\_shelladmin – Cannot convert legacy shell because it uses JSP pages instead of Portal pages.**

**Explanation** My webMethods Server cannot convert a legacy shell because it uses JSP pages instead of Portal pages.  
**Action** Contact Software AG Global Support. For contact information, log in to <https://empower.softwareag.com/>.

**POP.012.0007.wm\_xt\_dbdirsvc – {0} is required**

**Explanation** The SQL query is invalid because the required property is missing.  
**Action** Make sure the SQL query includes the required property.

**POP.012.0007.wm\_xt\_extdirsvc – Unable to get the OSGI service: {0}**

**Explanation** The OSGi external directory service is not defined or exposed correctly.  
**Action** Check if the external directory service is defined correctly.

**POP.012.0008.wm\_contentserviceadmin – A content service with a root of "{0}" already exists.**

**Explanation** A content service with the same root already exists.  
**Action** Verify that no other service uses the same root location.

**POP.012.0008.wm\_dirsearchcontext – Unable to locate the attribute provider for URI={0}**

**Explanation** The principal attribute provider for the specific directory service cannot be found.  
**Action** Find the directory service in the server log and contact an administrator with the log information.

**POP.012.0008.wm\_migration – Your download should begin shortly.**

**Explanation** Informational message indicating that the download to begin shortly.  
**Action** No action required.

**POP.012.0008.wm\_portalaliassearchcontext – Unable to remove alias "{0}" because it is a system alias**

**Explanation** Unable to remove the alias because it is a system alias.  
**Action** No action available. You cannot delete a system alias.

**POP.012.0008.wm\_xt\_dbdirsvc – {0} "{1}" is invalid. It is missing required field "{2}"**

**Explanation** The SQL query is invalid because the required property is missing.  
**Action** Make sure the SQL query includes the required property.

**POP.012.0009.wm\_portalaliassearchcontext – Unable to remove alias "{0}" because it does not exist**

**Explanation** Unable to remove the alias because it does not exist.  
**Action** Before attempting to delete an alias, verify that it exists.

**POP.012.0009.wm\_xt\_dbdirsvc – {0} "{1}" is invalid. It does not implement case-insensitive lookup for uid attribute**

**Explanation** The database directory service does not support case-insensitive lookup for the UID attribute.

**Action** Check the server log for information about the UID attribute and the query. Contact an administrator to make sure that the database directory service supports case-insensitive lookup for the UID attribute.

**POP.012.0010.wm\_xt\_dbdirsvc – Directory could not load principal "{0}"**

**Explanation** No principal is found in the database directory service using the specified name.

**Action** Use a valid name when searching the principal in the database directory service.

**POP.012.0012.wm\_skineditor – You can not set skin parent to itself**

**Explanation** The skin parent cannot be set to itself.

**Action** The skin parent cannot be set to itself because it is used as a parent for all others.

**POP.012.0015.wm\_migration – May not export resource which does not have a parent**

**Explanation** You cannot export a resource that does not have a parent.

**Action** Ensure that the resource has a valid parent.

**POP.012.0019.wm\_migration – Export failed : Calender Id/Name Invalid**

**Explanation** An invalid Calendar ID or Name is specified for Task Definition export.

**Action** Specify a valid Calendar ID or Name for export. Consult the log file at ..\MWS\server\\logs for further information.

**POP.012.0020.wm\_migration – Export failed : Shell Id/Name Invalid**

**Explanation** An invalid Shell ID or Name is specified for Task Definition export.

**Action** Specify a valid Shell ID or Name for export. Consult the log file at ..\MWS\server\\logs for further information.

**POP.012.0020.wm\_securityrealmadmin – Warning: Selecting 'OK' will permanently remove the SecurityRealm from the system.**

**Explanation** Before proceeding, verify that permanent deletion of the security realm will not affect your application or solution.

**Action** Click OK to permanently remove the security realm from the system.

**POP.012.0021.wm\_migration – Export failed : Skin Id/Name Invalid**

**Explanation** An invalid Skin ID or Name is specified for Task Definition export.

**Action** Specify a valid Skin ID or Name for export. Consult the log file at ..\MWS\server\\logs for further information.

**POP.012.0021.wm\_securityrealmadmin – Warning: Selecting 'OK' will permanently remove this Container and all its contents from the system.**

**Explanation** Before proceeding, verify that permanent deletion of the container will not affect your application or solution.

**Action** Clcik OK to permanently remove this container and all its contents from the system.

**POP.012.0022.wm\_migration – Export failed : Security Realm Id/Name Invalid**

**Explanation** An invalid Security Realm ID or Name is specified for Task Definition export.

**Action** Specify a valid Security Realm ID or Name for export. Consult the log file at ..\MWS\server\\logs for further information.

**POP.012.0023.wm\_migration – Exception Closing Stream continuing with processing**

**Explanation** An exception occurred during resource migration.

**Action** Check the detailed error message and take appropriate action.

**POP.012.0024.wm\_migration – Export failed : Certificate Id/Name Invalid**

**Explanation** An invalid Shell ID or Name was specified for Task Definition export.

**Action** Specify a valid Shell ID or Name for export. Consult the log file at ..\MWS\server\\logs for further information.

**POP.012.0025.wm\_migration – Export failed : Invalid depth specified {0}**

**Explanation** An invalid depth is specified for Task Definition export.

**Action** Specify the valid path for Task Definition export. Consult the log file at ..\MWS\server\\logs for further information.

**POP.012.0026.wm\_migration – Export failed : Invalid URI/alias specified for Export**

**Explanation** An invalid URL or alias has been specified for Task Definition export.

**Action** Specify a valid URL or alias for export. Consult the log file at ..\MWS\server\\logs for further information.

**POP.012.0027.wm\_migration – Export did not containing any DLS Objects**

**Explanation** The DLS object specified for export is not found.  
**Action** Specify the correct object for export. Consult the logs at ..\MWS\server\\logs for more details.

**POP.012.0028.wm\_migration – Export failed : Invalid ID/URI/alias/Name specified for Task Definition Export**

**Explanation** An invalid ID, URL, alias, or Name is specified for Task Definition export.  
**Action** Specify a valid ID, URL, alias, or Name for export. Consult the log file at ..\MWS\server\\logs for further information.

**POP.012.0029.wm\_migration – Export failed : Unable to get the skin archive content for {0}**

**Explanation** Unable to get the field value using the specified path.  
**Action** Consult the log file at ..\MWS\server\\logs for further information.

**POP.012.0032.wm\_migration – The Descriptor file specified is invalid**

**Explanation** An invalid Descriptor file is specified.  
**Action** Specify a valid Descriptor file for export. See the log files in <Software AG\_directory>\MWS\server\\logs for further information.

**POP.012.0033.wm\_migration – Please specify valid target folder path**

**Explanation** An invalid target folder path was encountered while trying to execute migration.  
**Action** Specify a valid target folder path.

**POP.012.0034.wm\_migration – Import failed for entry :-> {0}**

**Explanation** An invalid entry is specified for Task Definition export.  
**Action** See the log files in <Software AG\_directory>\MWS\server\\logs for further information.

**POP.012.0035.wm\_migration – No Task Instances found for Task application name {0} and task\_type\_id {1}**

**Explanation** No task instances are found that match the specified search criteria.  
**Action** Verify that the task application name and task type ID specified for the task instance search are valid. Consult the log file at ..\MWS\server\\logs for further information.

**POP.012.0036.wm\_migration – Export failed : Invalid ID/URI/alias/Name specified for Task Rules Export**

**Explanation** An invalid ID, URL, alias, or Name is specified for Task Rules export.  
**Action** Consult the log file at ..\MWS\server\

**POP.012.0037.wm\_migration – Export successful for :--> {0}**

**Explanation** The specified export completed successfully.  
**Action** No action required.

**POP.012.0038.wm\_migration – Failed to get bizPolicy for :--> {0}**

**Explanation** An invalid bizpolicy is specified.  
**Action** Specify a valid bizPolicy. Consult the log file at ..\MWS\server\

**POP.012.0039.wm\_migration – Failed to get view details for thingID:--> {0}**

**Explanation** The view details for the specified object could not be retrieved.  
**Action** Consult the log file at ..\MWS\server\

**POP.012.0041.wm\_migration – Import functionality is not supported.**

**Explanation** The import function is not supported.  
**Action** No action required.

**POP.012.0055.wm\_migration – Import info file {0} is invalid**

**Explanation** The migration portlet was unable to find the control file that lists the My webMethods Server assets to be imported.  
**Action** The user has specified an invalid path and file for the import control file. Check that the specified file exists and has read permission for the current user.

**POP.012.0056.wm\_migration – Failed to list principals from directory service {0}**

**Explanation** My webMethods Server failed to build a list of principals from the specified directory service. This can happen if the directory service is non-functional and cannot access the underlying directory provider, such as an LDAP server or database.  
**Action** Check the Directory Services Administration portlet to verify that the directory service provider is correctly configured and is enabled. Also check the error logs for directory service provider connection failures.

**POP.012.0058.wm\_migration – WARNING:Command not found: {0}**

**Explanation** My webMethods Server was unable to locate an internal command by name.  
**Action** This is an internal failure and cannot be remedied by the end-user.

**POP.012.0059.wm\_migration – Error applying ACL for {0}**

**Explanation** A general error occurred applying an import ACL to a principal.  
**Action** This is a system error that cannot be remedied by the end-user.

**POP.012.0060.wm\_migration – WARNING: Profile Attribute Import failed: {0}**

**Explanation** A general error occurred when applying the profile attributes to a user during import. The details of the failure will be appended to the error message.  
**Action** This is a system error that cannot be remedied by the end-user.

**POP.012.0061.wm\_migration – Error importing skin {0}**

**Explanation** A general error occurred when importing a skin. The details of the failure are appended to this message.  
**Action** This is a general message meant to capture any errors that occur during skin import. Refer to the My webMethods Server logs or the additional error text to troubleshoot the specific problem.

**POP.012.0062.wm\_migration – Error occurred post-processing ACLs**

**Explanation** A general error occurred applying ACLs to imported users, groups, or roles.  
**Action** This is a general message meant to capture any errors that occur when applying ACLs. Refer to the My webMethods Server logs or the additional error text to troubleshoot the specific problem.

**POP.012.0063.wm\_migration – Rule target not found for {0}.**

**Explanation** The target of a My webMethods Server rule could not be resolved to a specific My webMethods Server object. For example, a shell rule would display this error if it referenced a shell that did not exist.  
**Action** Examine the rule that is reporting the warning to determine the rule target, then confirm that the rule target exists.

**POP.012.0065.wm\_migration – Unable to register datasource {0}**

**Explanation** A general failure occurred importing a datasource.

**Action** This is a general message meant to capture any errors that occur during datasource import. Refer to the My webMethods Server logs or the additional error text to troubleshoot the specific problem.

**POP.012.0067.wm\_migration – Unable to import saved search for {0}**

**Explanation** A general error occurred when importing a set of saved searches for the specified resource (for example, Task List Management or My Inbox).

**Action** This is a general message meant to capture any errors that occur during a saved search import. Refer to the My webMethods Server logs or the additional error text to troubleshoot the specific problem.

**POP.012.0068.wm\_migration – Unable to locate principal for applying saved searches to {0}**

**Explanation** The import includes private saved searches for a user that does not exist in the target My webMethods Server.

**Action** Import or create the missing user and then import the saved searches. Otherwise, this error can be ignored, and the private saved searches will not be imported.

**POP.012.0069.wm\_migration – Unable to locate principal for {0}**

**Explanation** A general warning message that the import references a user, group, or role that could not be located in the target My webMethods Server.

**Action** Make sure any users, groups, or roles used by the asset that generates this warning are imported or created prior to the import.

**POP.012.0070.wm\_migration – Unable to apply members to {0}**

**Explanation** A general error occurred importing the role or group membership.

**Action** This is a general message meant to capture any errors that occur during import. Refer to the My webMethods Server logs or the additional error text to troubleshoot the specific problem.

**POP.012.0073.wm\_migration – Attempting to import deprecated XType {0}**

**Explanation** The import contained a My webMethods Server asset that is no longer supported in My webMethods Server. For example, older versions of wm\_xt\_savedsearch are no longer supported in 8.0 and generate this warning.

**Action** Because the My webMethods Server asset that generated this error is no longer supported, the message is for informational purposes only.

**POP.012.0107.wm\_portalcontent – This is not meant to be viewed**

- Explanation** An attempt was made to view a portal content resource that does not have a user interface.
- Action** Do not attempt to view the portal content resource directly. If the resource must be viewed, you must create a renderer that is capable of displaying a user interface for the object.

**POP.012.1001.wm\_mws\_diagnostics – Cannot find file to parse.**

- Explanation** Unable to load the file for analysis.
- Action** Select a file to upload for analysis.

**POP.012.1002.wm\_mws\_diagnostics – Unable to parse the log file; possible wrong log file format.**

- Explanation** The selected log file cannot be parsed. It is possible that the log file is in an incorrect format.
- Action** Make sure the selected log file is in the appropriate format.

**POP.012.1003.wm\_mws\_diagnostics – Error during XML marshalling. Possible wrong log file format.**

- Explanation** My webMethods Server was unable to parse the xml log file.
- Action** Select a log file generated by My webMethods Server and upload again.

**POP.012.1004.wm\_mws\_diagnostics – Unable to locate default {0}**

- Explanation** Unable to locate default {0}
- Action** Check the My webMethods Server instance configuration.

**POP.012.1005.wm\_mws\_diagnostics – The given host: {0} does not exist**

- Explanation** My webMethods Server was not able to reach the remote host.
- Action** Check the connection settings for the remote host, verify that My webMethods Server has network access to the host, then try again.

**POP.012.1006.wm\_mws\_diagnostics – An error has occurred while downloading the file: {0}**

- Explanation** There was a problem when parsing the file.
- Action** Check the My webMethods Server logs for more details. See  
..\MWS\server\\logs

**POP.012.1007.wm\_mws\_diagnostics – An error has occurred while processing the downloaded file: {0}**

**Explanation** There was a problem processing the file.  
**Action** Check the My webMethods Server logs for more details. See  
..\MWS\server\\logs

**POP.012.wm\_httpheaderauth.userDisabled – HTTP header authentication failed because login has been disabled for the {0} user.**

**Explanation** A My webMethods Administrator disabled the user.  
**Action** Contact your My webMethods Administrator. If the user is not disabled, but this message still appears, contact Software AG.

**POP.013.0005E This item is either inactive or deleted and can not be viewed.**

**Explanation** The item is deleted but has not yet been purged.  
**Action** Use the Deleted Items Administration portlet to remove the deleted items completely from the user interface.

**POP.013.0096 This was not meant to be viewed**

**Explanation** An attempt was made to view a My webMethods DBO that does not have a user interface.  
**Action** Do not attempt to view the resource directly. If the resource must be viewed, you must create a renderer that is capable of displaying a user interface for the object.

**POP.013.0097 Datasource {0} not found**

**Explanation** A portlet is attempting to open a database connection to a data source that is not available on the My webMethods Server.  
**Action** The My webMethods Server administrator should add the missing database connection information using the "Data Sources" portlet.

**POP.013.0099 Unable to construct a secure URL because the MWS secure front end URL is not available**

**Explanation** Constructing a secure URL is not possible because the My webMethods Server secure front-end URL is not available.  
**Action** Make sure that the front-end URL has been specified.

---

<b>POP.013.0100</b>	<b>You must enable JavaScript to use this site.</b>
<b>Explanation</b>	You must enable JavaScript to use this site.
<b>Action</b>	Make sure that JavaScript is enabled.
<b>POP.015.0001</b>	<b>No constant was specified for {0}.</b>
<b>Explanation</b>	When the system attempted to parse a My webMethods Server rule, the syntax expected a number and none was found.
<b>Action</b>	Review the recently modified or uploaded rule to ensure that the syntax is valid.
<b>POP.015.0002</b>	<b>Incorrect number of children. Expected {0} and found {1}.</b>
<b>Explanation</b>	When the system attempted to parse a My webMethods Server rule, the parser expected to find another term and none was found. For instance, the rule might have been a comparison, and only one term was found to compare.
<b>Action</b>	Review the recently modified or uploaded rule to ensure that the syntax is valid.
<b>POP.015.0003</b>	<b>Both child terms must be numbers.</b>
<b>Explanation</b>	When the system attempted to parse a My webMethods Server rule, the parser expected to find a numeric value or a value that can be converted into a number. None was found.
<b>Action</b>	Review the recently modified or uploaded rule to ensure that the syntax is valid.
<b>POP.015.0006</b>	<b>Unknown types for comparison: {0} and {1}.</b>
<b>Explanation</b>	When the system attempted to parse a My webMethods Server rule, the parser expected to find valid terms that can be compared to each other but was unable to do so.
<b>Action</b>	Review the recently modified or uploaded rule to ensure that the syntax is valid.
<b>POP.015.0007</b>	<b>Unable to find object Reference: {0}.</b>
<b>Explanation</b>	When the system attempted to evaluate a My webMethods Server rule, the rule referred to an object reference which could not be located.
<b>Action</b>	Review the recently modified or uploaded rule to ensure that the syntax is valid.

<b>POP.015.0008</b>	<b>No object Reference name is set.</b>
<b>Explanation</b>	When the system attempted to parse a My webMethods Server rule, the parser expected to find an object identifier and none was found.
<b>Action</b>	Review the recently modified or uploaded rule to ensure that the syntax is valid.
<b>POP.015.0009</b>	<b>Incorrect number of children. Expected 0 or 1 and found {0}.</b>
<b>Explanation</b>	When the system attempted to parse a My webMethods Server rule, the parser found an unexpected term in the sequence.
<b>Action</b>	Review the recently modified or uploaded rule to ensure that the syntax is valid.
<b>POP.015.0010</b>	<b>Incorrect number of children. Expected 2 or more and found {0}.</b>
<b>Explanation</b>	When the system attempted to parse a My webMethods Server rule, the parser expected to find additional terms and no more were found. For instance, the rule might have been a comparison, and only one term was found to compare.
<b>Action</b>	Review the recently modified or uploaded rule to ensure that the syntax is valid.
<b>POP.015.0011</b>	<b>Unable to find method to invoke: {0}.</b>
<b>Explanation</b>	When the system attempted to evaluate a My webMethods Server rule, it was unable to invoke the specified method.
<b>Action</b>	Review the recently modified or uploaded rule to ensure that the syntax is valid.
<b>POP.015.0012</b>	<b>Incorrect number of children. Expected 1 or more and found {0}.</b>
<b>Explanation</b>	When the system attempted to parse a My webMethods Server rule, the parser expected to find additional terms and no more were found. For instance, the rule might have been a comparison, and only one term was found to compare.
<b>Action</b>	Review the recently modified or uploaded rule to ensure that the syntax is valid.
<b>POP.015.0013</b>	<b>XML Parse Exception. Expected {0} tag and found {1} tag.</b>
<b>Explanation</b>	When the system attempted to parse a My webMethods Server rule, the parser was unable to find the correct XML schema.
<b>Action</b>	Review the recently modified or uploaded rule to ensure that the syntax is valid.

---

<b>POP.015.0014</b>	<b>XML Parse Exception while parasing tag {0}.</b>
<b>Explanation</b>	When the system attempted to parse a My webMethods Server rule, the parser was unable to find the correct XML schema.
<b>Action</b>	Review the recently modified or uploaded rule to ensure that the syntax is valid.
<b>POP.015.0015</b>	<b>Parse Exception at char: {0} {1}.</b>
<b>Explanation</b>	When the system attempted to parse a My webMethods Server rule, the parser encountered a syntax error at the specified position.
<b>Action</b>	Review the recently modified or uploaded rule to ensure that the syntax is valid.
<b>POP.015.0029</b>	<b>Expected to find matching char "{0}"</b>
<b>Explanation</b>	When the system attempted to parse a My webMethods Server rule, the parser encountered a syntax error at the specified position.
<b>Action</b>	Review the recently modified or uploaded rule to ensure that the syntax is valid.
<b>POP.016.0001</b>	<b>unbalanced end element: expected "{0}" but was "{1}"</b>
<b>Explanation</b>	The optional PrettyPrintingResponseWriter that was enabled manually by the developer to tidy up the rendered html for a page in the web.xml of the webapp, has detected html that was not well-formed.
<b>Action</b>	This should never happen. If this happens a defect in one of the JSF component renderers has not properly closed one of the html tags that was written to the response writer.
<b>POP.016.0002</b>	<b>Portlet Preferences are only available inside the Portlet Context</b>
<b>Explanation</b>	This error message is not used in the current trunk code anymore.
<b>Action</b>	N/A
<b>POP.016.0003</b>	<b>Else control must be preceded directly by If control</b>
<b>Explanation</b>	The CAF view contains an "Else" control without a sibling "If" control.
<b>Action</b>	The developer should change the "Else" control to an "If" control or remove it from the CAF view.

<b>POP.016.0004</b>	<b>Duplicate component ID: {0} (IDs must be unique within naming-container)</b>
<b>Explanation</b>	In a CAF view two controls have the same ID value.
<b>Action</b>	The developer must change the ID of all the controls that are using the same ID to make the control's ID unique.
<b>POP.016.0005</b>	<b>Resource bundle is not available: {0}</b>
<b>Explanation</b>	The specified resource bundle could not be loaded.
<b>Action</b>	The developer should check the resource bundle name to make sure it is correct and make sure the resource bundle file is included in the war file.
<b>POP.016.0006</b>	<b>View source is not found: {0}</b>
<b>Explanation</b>	When attempting to load a CAF .view file, the file was not found.
<b>Action</b>	The developer should inspect the deployed war file to make sure the missing view file exists.
<b>POP.016.0007</b>	<b>Can only switch portlet modes within an action request</b>
<b>Explanation</b>	A portlet attempted to change the portlet mode outside of an action request which is not allowed per the JSR-168 specification.
<b>Action</b>	The developer should change the portlet source code and not attempt to change the portlet mode from a code path that does not originate in a portlet action handler.
<b>POP.016.0008</b>	<b>Unable to locate control ID {0} in view: {1}</b>
<b>Explanation</b>	There was no control in the view that had the specified control id.
<b>Action</b>	The developer should review their application code to make sure the correct control ID is used for the lookup.
<b>POP.016.0009</b>	<b>Connection failed to datasource {0}. Caused by: {1}</b>
<b>Explanation</b>	A SQLException was caught while retrieving the data for a RowSetTableContentProvider.
<b>Action</b>	Review the server log file to inspect the stack trace of the exception to try to determine the cause of the error.

---

<b>POP.016.0010</b>	<b>Search Results Table Control could not be located</b>
<b>Explanation</b>	The Export Table Button control could not find the table control to use for exporting data.
<b>Action</b>	The developer should check the Export For property of the Export Table Button control to make sure it matches the ID of the table control.
<b>POP.016.0011</b>	<b>DateInput component value must be a java.util.Date instance</b>
<b>Explanation</b>	The value bound to a Date Input control is not the expected data type.
<b>Action</b>	The developer should review the binding expression of the Date Input control to make sure it resolves to a java.util.Date object.
<b>POP.016.0012</b>	<b>DateRangeInput component value must be a com.webmethods.caf.faces.data.object.DateRange instance</b>
<b>Explanation</b>	The value bound to a Date Range Input control is not the expected data type.
<b>Action</b>	The developer should review the binding expression of the Date Range Input control to make sure it resolves to a com.webmethods.caf.faces.data.object.DateRange object.
<b>POP.016.0013</b>	<b>managed-bean-scope value "pageflow" should be changed to "session" for managed-bean "{0}" in application "{1}".</b>
<b>Explanation</b>	A managed-bean declaration in the faces-config.xml is using the deprecated pageflow managed-bean-scope.
<b>Action</b>	The application developer should change the managed-bean-scope value pageflow to session for the managed-bean and then rebuild and redeploy the application.
<b>POP.016.0014</b>	<b>ScheduleInput component value must be a com.webmethods.caf.faces.data.object.Schedule instance</b>
<b>Explanation</b>	The value bound to a Schedule Input control is not the expected data type.
<b>Action</b>	The developer should review the binding expression of the Schedule Input control to make sure it resolves to a com.webmethods.caf.faces.data.object.Schedule object.
<b>POP.016.0015</b>	<b>Interval must be set to calculate previous or next date</b>
<b>Explanation</b>	The Schedule.nextDate(..) or Schedule.previousDate(..) api was called but the schedule does not have an interval configured.
<b>Action</b>	Set the interval on the Schedule object before attempting to calculate the next or previous date.

<b>POP.016.0016</b>	<b>Source table provider does not expose currentRow data and thus cannot be used with PageableTableContentProvider.</b>
<b>Explanation</b>	Source table provider does not expose currentRow data and cannot be used with the PageableTableContentProvider.
<b>Action</b>	Review the configuration of the table content provider to ensure that it is configured properly.
<b>POP.016.0017</b>	<b>Cannot find value for script parameter: {0}</b>
<b>Explanation</b>	The value of a script parameter is null.
<b>Action</b>	The developer should review the source of the script parameter value to determine why it has no value.
<b>POP.016.0018</b>	<b>Cannot find control with id "{1}" for script parameter: {0}</b>
<b>Explanation</b>	The control id specified as the value of a script parameter did not match a control in the view.
<b>Action</b>	The developer should review the script parameter value to ensure it matches an existing control in the view.
<b>POP.016.0019</b>	<b>Cannot create null method binding.</b>
<b>Explanation</b>	An attempt was made to create a method binding object without supplying an expression string.
<b>Action</b>	The developer should review the application code to determine why the expression is null.
<b>POP.016.0020</b>	<b>Cannot create null value binding.</b>
<b>Explanation</b>	An attempt was made to create a value binding object without supplying an expression string.
<b>Action</b>	The developer should review the application code to determine why the expression is null.
<b>POP.016.0021</b>	<b>Cannot convert null locale string.</b>
<b>Explanation</b>	The com.webmethods.caf.faces.convert.ConvertUtils.getLocalFromToString API was called with a null string.
<b>Action</b>	The developer should review the application code to determine why the supplied locale string is null.

---

<b>POP.016.0022</b>	<b>Portlet control can only be used within a portlet request</b>
<b>Explanation</b>	The Portlet Include control is used in a non-portlet environment.
<b>Action</b>	Do not use the Portlet Include control in a standalone CAF web application.
<b>POP.016.0023</b>	<b>Cannot export from this context or phase</b>
<b>Explanation</b>	An attempt was made to export a file, but a compatible export handler was not found.
<b>Action</b>	You should not get this error.
<b>POP.016.0024</b>	<b>Cannot export control of specified type (id={0},type={1})</b>
<b>Explanation</b>	An attempt was made to export a control but the control specified was not an UIData based control so it cannot be exported.
<b>Action</b>	The developer should review the configuration of the export button to make sure the correct control is being exported.
<b>POP.016.0027</b>	<b>Cannot parse string "{0}" as date (using pattern "{1}").</b>
<b>Explanation</b>	A Date Import control value was a string but it could not be converted to a Date object.
<b>Action</b>	The developer should verify that the value pattern matches the format of the string bound to the control.
<b>POP.016.0029</b>	<b>The "rowVariable" property must be set to use BoundPropertiesSelectedItemGroupProvider.</b>
<b>Explanation</b>	The rowVariable property must be set to use BoundPropertiesSelectedItemGroupProvider.
<b>Action</b>	The developer should review the application code to ensure that the rowVariable property was set.
<b>POP.016.0030</b>	<b>The "rowType" property must be set to use as an IUpdateableTableContentProvider.</b>
<b>Explanation</b>	An attempt was made to add a new row to an updatable table content provider but the row type was not specified.
<b>Action</b>	The developer should review the application code to ensure that the rowType property was set.

<b>POP.016.0031</b>	<b>Cannot create response for {0}.</b>
<b>Explanation</b>	The CAF view handler was unable to get a response writer to render the output.
<b>Action</b>	This should not occur. If this error occurred, there is a catastrophic problem with the server instance. Other errors in the server logs might provide some guidance.
<b>POP.016.0032</b>	<b>AutoRefresh is not supported</b>
<b>Explanation</b>	An attempt was made to autorefresh a LazyNodeTreeContentProvider instance that does not support autorefresh.
<b>Action</b>	The developer should review the application code to remove any calls to the autorefresh API.
<b>POP.016.0033</b>	<b>NeedRefresh is not supported</b>
<b>Explanation</b>	An attempt was made to mark a LazyNodeTreeContentProvider instance as needing a refresh that does not support autorefresh.
<b>Action</b>	The developer should review the application code to remove any calls to the setNeedRefresh API.
<b>POP.016.0034</b>	<b>Child not in parent's children list</b>
<b>Explanation</b>	There is a problem building the structure of a LazyNodeTreeContentProvider instance.
<b>Action</b>	The developer should review the application code that is providing the values to the tree content provider to make sure that the parent/child relationships of the tree data are correct.
<b>POP.016.0035</b>	<b>The "rowIdBinding" property must be set to add or remove rows to or from a SelectableListTableContentProvider. If the table does not need to be selectable, try using a ListTableContentProvider instead.</b>
<b>Explanation</b>	The rowIdBinding property must be set to add or remove rows to or from a SelectableListTableContentProvider. If the table does not need to be selectable, try using a ListTableContentProvider instead.
<b>Action</b>	Set the rowIdBinding property for a SelectableListTableContentProvider. If the table does not need to be selectable, try using a ListTableContentProvider instead.
<b>POP.016.0036</b>	<b>The "rowIdBinding" property must be set to move rows within a SelectableListTableContentProvider.</b>
<b>Explanation</b>	The rowIdBinding property must be set to move rows within a SelectableListTableContentProvider.
<b>Action</b>	This error message is no longer used.

---

<b>POP.016.0037</b>	<b>Saved Search Not Found: {0}</b>
<b>Explanation</b>	An attempt was made to change the active saved search for a SearchBar control but the target saved search no longer exists.
<b>Action</b>	The end user should refresh the page and select a saved search.
<b>POP.016.0039</b>	<b>cannot load external resource: {0}</b>
<b>Explanation</b>	When loading an app-nav.xml file, there was a reference to an external resource which is not allowed.
<b>Action</b>	The developer should review the app-nav.xml and remove the references to external resources.
<b>POP.016.0040</b>	<b>cannot have more than one root page</b>
<b>Explanation</b>	When loading an app-nav.xml file more than one root page element was detected.
<b>Action</b>	The developer should review the app-nav.xml file to ensure that there is only one root page declared.
<b>POP.016.0042</b>	<b>Error updating control value ("{1}" property of "{0}" control).</b>
<b>Explanation</b>	An error was detected updating a control value. The cause of the error is contain within the message details displayed to the user.
<b>Action</b>	Review the error message details displayed to the user to determine the cause of the error.
<b>POP.016.0043</b>	<b>Toggle target control "{0}" could not be located.</b>
<b>Explanation</b>	The For property in a Toggle control does not resolve to a control.
<b>Action</b>	The application developer should review the application code to ensure that the For property of the toggle control matches the expected target control.
<b>POP.016.0043.details – Check the configuration of the control with this id: {0}</b>	
<b>Explanation</b>	Provides additional details for the "POP.016.0043" error.
<b>Action</b>	See action for the "POP.016.0043" error.
<b>POP.016.0044</b>	<b>Calendar StartDay is not set</b>
<b>Explanation</b>	A calendar control is being rendered but the start day has not been set.
<b>Action</b>	The developer should review the application code to ensure that the calendar has a start day.

- POP.016.0045**      **Invalid value for height property of the "{0}" control.**  
**Explanation**      The value of the height property of a Static Row or Static Cell control is not a valid height.  
**Action**              The developer should review the application code to ensure that the height value is a valid unit of measure.
- POP.016.0046**      **Invalid value for width property of the "{0}" control.**  
**Explanation**      The value of the width property of a Static Row or Static Cell control is not a valid width.  
**Action**              The developer should review the application code to ensure that the width value is a valid unit of unit of measure.
- POP.016.0047**      **Can only reset portlet navigation state within an action request**  
**Explanation**      Portlet navigation state such as if portlet maximized or minimized can only be changed from an ActionRequest  
**Action**              Do not attempt to change the portlet navigate state from the RenderRequest. Use ActionRequest.
- POP.016.0048**      **The target action was invalid**  
**Explanation**      Request portlet action in PortletUrl is invalid and cannot be found  
**Action**              Check the name action being requested and determine if it is defined in the portlet Java code
- POP.016.0048.detail – The target action was: {0}**  
**Explanation**      The request portlet action in PortletUrl is invalid and cannot be found  
**Action**              Check the name action being request and determine if it is defined in the portlet Java code
- POP.016.0049**      **The target action was invalid**  
**Explanation**      It is possible to invoke actions on the designated portlet via PortletURL. To prevent a malicious user from invoking an arbitrarily action on the portlet, each action defined must be annotated in Java code with @PortletAction annotation which instructs MWS runtime that a given action code is allowed when invoked from a url.  
**Action**              Check portlet action definition code, and determine if it has the @PortletAction annotation defined.

**POP.016.0049.detail – The target action requires a @PortletAction annotation: {0}**

**Explanation** It is possible to invoke actions on the designated portlet via PortletURL. To prevent malicious user to invoke an arbitrarily action on the portlet, each action defined must be annotated in Java code with @PortletAction annotation which instructs MWS runtime that a given action code is allowed from a url.

**Action** Check portlet action definition code if it has @PortletAction annotation defined

**POP.016.0050 The target action was invalid**

**Explanation** To prevent cross-site scripting attacks when malicious script might invoke a portlet action using a URL, the URL used to call a portlet action must obtain and use AXSRF token.

**Action** When producing a Portlet URL, make sure that the AXSRF token is included in the URL using com.webmethods.caf.portlet.IPortletUrl.setAXSRFT(true) API.

**POP.016.0050.detail – The target action "{0}" requires an anti-xsrft token.**

**Explanation** To prevent cross-site scripting attacks when malicious script might invoke a portlet action using an URL, the URL used to call a portlet action must obtain and use an AXSRF token.

**Action** When producing a Portlet URL, make sure that an AXSRF token is included in the URL using com.webmethods.caf.portlet.IPortletUrl.setAXSRFT(true) API.

**POP.016.0051 The target action was invalid**

**Explanation** To prevent cross-site scripting attacks when malicious script might invoke a portlet action using an URL, the URL used to call a portlet action must obtain and use a valid AXSRF token.

**Action** When producing a Portlet Url, make sure that AXSRF token is included in the URL using com.webmethods.caf.portlet.IPortletUrl.setAXSRFT(true) API.

**POP.016.0052 The target action was invalid**

**Explanation** The Portlet Url can invoke portlet actions from a URL. If the CAF application does not force use of Annotated Portlet Actions, see CAF documentation for more details, then it is possible to use a JSF binding expression to specify the action to invoke. This error is thrown if binding expression does not resolve to a valid method.

**Action** Check and correct the binding expression used for portlet action because it does not resolve to a valid action method.

**POP.016.0052.detail – The target action was: {0}**

**Explanation** The Portlet Url can invoke portlet actions from a URL. If the CAF application does not force the use of Annotated Portlet Actions, see the CAF documentation for more details, then it is possible to use a JSF binding expression to specify the action to invoke. This error is thrown if binding expression does not resolve to a valid action method.

**Action** Check and correct binding expression used for portlet action because it does not resolve to a valid action method.

**POP.016.0053 Invalid content type. The allowed content types are: {0}**

**Explanation** An attempt was made to upload a file of an unsupported type to an Attachment Panel control.

**Action** Upload a file of a supported type for attachments.

**POP.016.0054 Invalid file extension. The allowed file extensions are: {0}**

**Explanation** An attempt was made to upload a file of an unsupported type to an Attachment Panel control.

**Action** Upload a file type that is supported as an attachment.

**POP.016.0055 Invalid file size. The maximum file size is: {0}**

**Explanation** The file uploaded to an Attachment Panel control is larger than the allowed size of an attachment.

**Action** Upload a smaller file.

**POP.017.0001 Task is locked and you may not update it at this time. Please wait till task is unlocked**

**Explanation** Task instance is locked in following cases: when a task is being updated, or when task events and assignments are being processed. To ensure state consistency when a task is locked, no other updates to the task are possible (though the task can still be read and searched on). Typically lock time is very short (similar to database transaction).

**Action** Enable MWS "task" logging category Debug logging and investigate timing and duration of task locks.

**POP.017.0003 Task auditing level is not sufficient to rollback task state**

**Explanation** Task state should be kept in task audit in order for task rollback to function. If task state is not present in the audit, rollback is not possible

**Action** Make sure to audit full task state. Task audit options can be controlled as properties on task definition object. You must login as sysadmin, browse to /task.storage, navigate to "Task Definitions" and open properties of task type, then change audit settings.

---

<b>POP.017.0004</b>	<b>You don't have permissions to queue new task</b>
<b>Explanation</b>	User does not have a task functional privilege to queue task of specific task type.
<b>Action</b>	Configure Permissions on the user to enable "Queue Task" functional privilege.
<b>POP.017.0007</b>	<b>You don't have permissions to view this task</b>
<b>Explanation</b>	<p>The current user does not have permission to view task information.</p> <p>Prior to MWS_7.1.3_Fix9, the mechanism to determine if a user had permission to view a task required the user to hold "view task data" permission. With the introduction of MWS_7.1.3_Fix9, the user/role must have this permission and also must be present in the "assigned to" or "delegated to" lists. Under these conditions, if the user holds only "view task data" permission, permission to view the task is denied and this error occurs.</p> <p>A task client option, task.base.permission, is available to apply the simpler "view task data" permission even if MWS_7.1.3_Fix9 is applied. For more information, see the Task Engine Optional Settings section in the PDF publication, Task Engine User's Guide.</p>
<b>Action</b>	<p>If your system does not have MWS_7.1.3_Fix9 applied, make sure that the user holds "view task data" permission.</p> <p>If your system has MWS_7.1.3_Fix9 applied, make sure the user holds "view task data" permission and is also present on the "assigned to" or "delegated to" lists. Also, see the explanatory text above concerning the task.base.permission option.</p>
<b>POP.017.0008</b>	<b>You don't have permissions to view task data</b>
<b>Explanation</b>	Current User does not have permissions to view task business data.
<b>Action</b>	Configure Permissions on the user to enable "View Task Data" functional privilege.
<b>POP.017.0009</b>	<b>You don't have permissions to view audit log</b>
<b>Explanation</b>	Current user does not have permissions to view task audit.
<b>Action</b>	Configure Permissions on the user to enable "View Task Audit" functional privilege.
<b>POP.017.0010</b>	<b>You don't have permissions to accept this task</b>
<b>Explanation</b>	Current user does not have permissions to accept task instance.
<b>Action</b>	Configure Permissions on the user to enable "Accept Task" functional privilege.

<b>POP.017.0011</b>	<b>You don't have permissions to accept other users on this task</b>
<b>Explanation</b>	Current user does not have permissions to accept task instance.
<b>Action</b>	Configure Permissions on the user to enable "Accept Task" functional privilege.
<b>POP.017.0012</b>	<b>You don't have permissions to assign this task</b>
<b>Explanation</b>	Current user does not have permissions to assign task instance.
<b>Action</b>	Configure Permissions on the user to enable "Assign Task" functional privilege.
<b>POP.017.0013</b>	<b>You don't have permissions to rollback this task</b>
<b>Explanation</b>	Current user does not have permissions to rollback task instance.
<b>Action</b>	Configure Permissions on the user to enable "Rollback Task" functional privilege.
<b>POP.017.0014</b>	<b>You don't have permissions to modify task data</b>
<b>Explanation</b>	Current user does not have permissions to update task business data.
<b>Action</b>	Configure Permissions on the user to enable "Modify Task Data" functional privilege.
<b>POP.017.0015</b>	<b>You don't have permissions to modify task info</b>
<b>Explanation</b>	Current user does not have permissions to update generic task info properties.
<b>Action</b>	Configure Permissions on the user to enable "Modify Task Info" functional privilege.
<b>POP.017.0016</b>	<b>Task Type ID is not valid {0}</b>
<b>Explanation</b>	This error is reported when attempting to queue a task and specifying an invalid task type ID (from APIs).
<b>Action</b>	Check if the specified Task Type is deployed to MWS.
<b>POP.017.0017</b>	<b>Task ID is not valid {0}</b>
<b>Explanation</b>	This error is reported when attempting to operate on invalid task.
<b>Action</b>	Check if the specified task is still available in MWS, it may already be deleted.
<b>POP.017.0018</b>	<b>Unable to find task client bean: {0}</b>
<b>Explanation</b>	During task searches, assignments and events evaluation, Task Engine needs access to task generated beans which are part of task application. This error is reported when it fails to instantiate these beans.
<b>Action</b>	Check if task application was deployed properly, and if there are any errors in the install.log, re-install task application.

---

<b>POP.017.0020</b>	<b>Cannot obtain FacesContext for Task application: {0}</b>
<b>Explanation</b>	Indicates that task application was not properly deployed.
<b>Action</b>	Investigate any possible errors during task application installation. Re-install task application.
<b>POP.017.0022</b>	<b>You don't have permissions to delegate this task</b>
<b>Explanation</b>	Current user does not have permissions to delegate task instance.
<b>Action</b>	Configure Permissions on the user to enable "Delegate Task" functional privilege.
<b>POP.017.0024</b>	<b>You don't have permissions to complete this task</b>
<b>Explanation</b>	Current user does not have permissions to complete task instance.
<b>Action</b>	Configure Permissions on the user to enable "Complete Task" functional privilege.
<b>POP.017.0025</b>	<b>You don't have permissions to cancel this task</b>
<b>Explanation</b>	Current user does not have permissions to cancel task instance.
<b>Action</b>	Configure Permissions on the user to enable "Cancel Task" functional privilege.
<b>POP.017.0026</b>	<b>You don't have permissions to suspend this task</b>
<b>Explanation</b>	Current user does not have permissions to suspend task instance.
<b>Action</b>	Configure Permissions on the user to enable "Suspend Task" functional privilege.
<b>POP.017.0027</b>	<b>You don't have permissions to resume this task</b>
<b>Explanation</b>	Current user does not have permissions to resume task instance.
<b>Action</b>	Configure Permissions on the user to enable "Resume Task" functional privilege.
<b>POP.017.0028</b>	<b>User {0} not found</b>
<b>Explanation</b>	This error is reported when using Task Engine API from WmTaskClient IS package and "impersonated" user name is not valid.
<b>Action</b>	Check the name of the "impersonated" user in the Task Engine API calls.
<b>POP.017.0029</b>	<b>You can not rollback non-Active task</b>
<b>Explanation</b>	Only tasks in "Active" state can be rolled back.
<b>Action</b>	Set the status of the task to "Active".

<b>POP.017.0030</b>	<b>You can not queue new task. Task type is not enabled</b>
<b>Explanation</b>	Task Type, which the task is about to be queued for, is disabled.
<b>Action</b>	Enable the Task Type from the Task Engine Administration.
<b>POP.017.0032</b>	<b>Connecting user does not have Impersonate Users privilege</b>
<b>Explanation</b>	When using remote Task Engine API (from WmTaskClient IS package or web services), the API allows to impersonate user so task operations are performed on behalf of a different user. This is useful because typically passwords of end user are not known, so 'sysadmin' account should be used for remote APIs invocation. It is possible to connect to remote API using a non-sysadmin account, but in this case the user account needs to have "Impersonate Users for Remote Clients" Task Engine privilege.
<b>Action</b>	Grant the user the "Impersonate Users for Remote Clients" Task Engine privilege.
<b>POP.017.0033</b>	<b>You can not update non-Active task: {1}</b>
<b>Explanation</b>	Tasks whose status is "Completed", "Cancelled" or "Expired" cannot be updated.
<b>Action</b>	Administrator can set task status back to "Active".
<b>POP.017.0034</b>	<b>You can not rollback non-Active task</b>
<b>Explanation</b>	Tasks whose status is "Completed", "Cancelled" or "Expired" cannot be rolled back.
<b>Action</b>	Administrator can set task status back to "Active".
<b>POP.017.0037</b>	<b>Task is out of date, please refresh</b>
<b>Explanation</b>	Task Engine updates from UI or API implement "optimistic locking" to ensure that data being updated is up-to-date. This error is reported if task data being passed in from UI or API call is not the latest.
<b>Action</b>	UI needs to be refreshed to reload up-to-date task data. When using Task Engine APIs task data needs to be re-loaded.
<b>POP.017.0039</b>	<b>You don't have permissions to add task comments</b>
<b>Explanation</b>	Current user does not have permissions to add comments to task instance.
<b>Action</b>	Configure Permissions on the user to enable "Add Comment" functional privilege.

---

<b>POP.017.0040</b>	<b>You don't have permissions to delete task comments</b>
<b>Explanation</b>	Current user does not have permissions to delete comments from task instance.
<b>Action</b>	Configure Permissions on the user to enable "Delete Comments" functional privilege.
<b>POP.017.0041</b>	<b>You don't have permissions to delete other user's task comments</b>
<b>Explanation</b>	Current user does not have permissions to delete comments from task instance which were created by other people.
<b>Action</b>	Configure Permissions on the user to enable "Delete Other People's Comment" functional privilege.
<b>POP.017.0042</b>	<b>You don't have permissions to create new collaboration tasks</b>
<b>Explanation</b>	Current user does not have permissions to queue collaboration task of another task.
<b>Action</b>	Configure Permissions on the user to enable "Queue Collaboration Tasks" functional privilege.
<b>POP.017.0045</b>	<b>You can not update suspended task</b>
<b>Explanation</b>	If current task status is "Suspended", it can only be updated back to "Active" status. No other updates are allowed.
<b>Action</b>	Administrator can set task status back to "Active".
<b>POP.017.0051</b>	<b>You can not set the parent task ID using the self task ID</b>
<b>Explanation</b>	This error is reported when attempting to update an existing task via APIs and set its "parentTaskID" property to the ID of the task itself.
<b>Action</b>	Check "parentTaskID" being set.
<b>POP.017.0052</b>	<b>You can not set the parent task ID using non integer value</b>
<b>Explanation</b>	This error is reported when updating or queuing a new task via API and "parentTaskID" property is not a valid task ID value.
<b>Action</b>	Check value of "parentTaskID" being used.
<b>POP.017.0053</b>	<b>You can not set the parent task ID using invalid task ID</b>
<b>Explanation</b>	This error is reported when updating or queuing a new task via API and "parentTaskID" property is not a valid task ID value.
<b>Action</b>	Check "parentTaskID" value used.

**POP.017.0061      You can not set the delegated to or delegated from list if their size does not match**

**Explanation**      When updating task delegation via APIs both "delegatedFromList" and "delegatedToList" list values should contain the same number of items.

**Action**              Check "delegatedFromList" and "delegatedToList" values used.

**POP.017.0071      Task indexTableDis is null or emptys**

**Explanation**      Invalid task index configuration is provided from taskDefinition.xml file.

**Action**              Re-create task index configuration by re-configuring task index fields in Designer.

**POP.017.0072      Task indexTableDis format is invalid: {0}**

**Explanation**      Invalid task index configuration is supplied in taskDefinition.xml file.

**Action**              Re-create task index configuration by re-configuring task index fields in Designer.

**POP.017.0090      Failed to invoke IS service: {0}**

**Explanation**      Failed to invoke IS service when executing task decision table assignment. The reason could be that related rule project is not deployed on the corresponding IS server, or that IS service parameters, such as project name, rule set name, etc. are invalid.

**Action**              Please make sure the related rule project is deployed and correct IS service parameters are used when configuring task decision table assignment.

**POP.017.0091      You can not change status of scheduled task**

**Explanation**      If the current status of the task is "scheduled", no other status updates are allowed.

**POP.017.0092      You can not update task schedule date if task not in scheduled status**

**Explanation**      The task schedule date field cannot be updated if the task is not in a "scheduled" status.

**POP.017.0093      Task Schedule Date cannot be before current date**

**Explanation**      The Task Schedule Date attribute specifies the start time of the schedule. However, the value specified in the Task Schedule Date element is for a start time that is before the current time.

**Action**              Specify a date/time value for the Task Schedule Date attribute that is after the current time.

---

<b>POP.017.0094</b>	<b>Task Schedule Date cannot be after Expire date</b>
<b>Explanation</b>	The Task Schedule Date attribute specifies the start time of the schedule. However, the value specified in the Task Schedule Date element is for starting the schedule after the Expire date of the schedule.
<b>Action</b>	Specify a date/time value for the Task Schedule Date attribute that is before the Expire date.
<b>POP.017.0095</b>	<b>You can not change status of active/suspended task to scheduled</b>
<b>Explanation</b>	Tasks with an "active" or "suspended" status cannot be updated to "scheduled".
<b>POP.017.0096</b>	<b>You can not accept a scheduled task</b>
<b>Explanation</b>	Tasks with a "scheduled" status cannot be accepted.
<b>POP.017.0097</b>	<b>Child task schedule date cannot be before parent task schedule date</b>
<b>Explanation</b>	A child task should be scheduled to start after its parent task started.
<b>Action</b>	Reschedule the child task for a date after the parent task's start date. Alternatively, move back the parent task schedule date.
<b>POP.017.0098</b>	<b>Child task schedule date cannot be after parent task expiredate</b>
<b>Explanation</b>	A child task should be scheduled for a date before its parent task expires.
<b>Action</b>	Reschedule the child task for a date before the parent task's expiration date. Alternatively, extend the parent task's expiration date.
<b>POP.017.0100</b>	<b>Task has reached maximum number of modifications</b>
<b>Explanation</b>	The task has reached the maximum number of modifications set by the Infinite Loop task rule.
<b>Action</b>	Keep a smaller number of modifications to avoid such an error.
<b>POP.017.0101</b>	<b>Unhandled Exception during rule processing. Rule [{0}]</b>
<b>Explanation</b>	An exception was caught during processing Task Rules.
<b>Action</b>	Check the My webMethods Server logs at ..\MWS\server\ <instancename>\logs for additional exception details to determine the cause.</instancename>

<b>POP.017.0102</b>	<b>Unhandled Exception during task change processing</b>
<b>Explanation</b>	An exception was thrown while publishing a new notification or processing task events.
<b>Action</b>	Check the My webMethods Server logs at ... \MWS\server\<instanceName>\logs for additional exception details to determine the cause.
<b>POP.017.0103</b>	<b>Unable to deliver task completion to Process runtime (PRT)</b>
<b>Explanation</b>	Task completion cannot be delivered to the Process runtime.
<b>Action</b>	Check the My webMethods Server logs at .. \MWS\server\<instanceName>\logs for additional exception details to determine the cause.
<b>POP.017.0104</b>	<b>Process runtime (PRT) task step failed</b>
<b>Explanation</b>	An exception was thrown while processing the task completion. Most likely the time for redelivery was exceeded.
<b>Action</b>	Check the My webMethods Server logs at .. \MWS\server\<instanceName>\logs for additional exception details to determine the cause.
<b>POP.017.0106</b>	<b>Indexed task searches are not available in Preview Server. Please use standalone MWS server instead</b>
<b>Explanation</b>	Indexed task searches are not available when the portal system is running in a preview server mode.
<b>Action</b>	Use a standalone My webMethods Server instead.
<b>POP.017.0107</b>	<b>Cannot process rule [{0}] for Task [{1}] due to [{2}]</b>
<b>Explanation</b>	An exception was thrown while processing the task rule, which may mean that the task cannot be found.
<b>Action</b>	Check the My webMethods Server logs at .. \MWS\server\<instanceName>\logs for additional exception details to determine the cause.
<b>POP.017.0108</b>	<b>Failed to acquire lock for [{0}] in {1} milliseconds</b>
<b>Explanation</b>	The exception occurs when a timeout occurs while waiting to acquire a task lock in the task locking service.
<b>Action</b>	Internally used. Some handlers may re-send an event to be re-delivered later.

---

<b>POP.017.0120</b>	<b>RuleName is null or empty</b>
<b>Explanation</b>	The RuleName attribute of the schedule rule to be added or updated cannot be null.
<b>Action</b>	Specify a valid non-null RuleName attribute.
<b>POP.017.0121</b>	<b>TaskTypeID is null or empty</b>
<b>Explanation</b>	The TaskTypeID attribute of the schedule rule to be added or updated cannot be null.
<b>Action</b>	Specify a valid non-null TaskTypeID attribute.
<b>POP.017.0122</b>	<b>StartDate is null or empty</b>
<b>Explanation</b>	The StartDate attribute of the schedule rule to be added or updated cannot be null.
<b>Action</b>	Specify a valid non-null StartDate attribute.
<b>POP.017.0123</b>	<b>Failed to obtain a task index engine manager for: {0}.</b>
<b>Explanation</b>	Task Engine cannot obtain a task index engine manager of the specified type.
<b>Action</b>	Verify whether: 1. The specified task index manager is registered as an OSGi service. 2. The OSGi service id for the task index manager is correct. 3. The service is running without errors in the My webMethods Server OSGi runtime.
<b>POP.018.0001</b>	<b>IView object does not support indexed properties</b>
<b>Explanation</b>	A binding expression attempted to resolve a property of an IView object by index. This operation is not supported.
<b>Action</b>	The ViewPropertyResolver does not support lookup of a property by index. Change the application code so that it does not attempt an unsupported operation.
<b>POP.018.0002</b>	<b>IView object is readonly</b>
<b>Explanation</b>	A binding expression attempted to update a property of an IView object which is not supported.
<b>Action</b>	The ViewPropertyResolver does not support update of an IView property. Change the application code so that it does not attempt an unsupported operation.
<b>POP.018.0003.DirSearchProvider – Failed to move to next principal in directory services, service={0}, error={1}</b>	
<b>Explanation</b>	An unexpected exception occurred during the directory service search API call.
<b>Action</b>	Review the server log files for the stack trace of the cause.

**POP.018.0004.DirSearchProvider – Failed to evaluate expression for object, exp={0}, obj={1}, error={2}**

**Explanation** An unexpected error was caught while evaluating the value of the property used to sort the principal.

**Action** Review the server log files for the stack trace of the cause.

**POP.018.0005.DirSearchProvider – Failed to create a directory service iterator, dirService={0}, error={1}**

**Explanation** An unexpected error was caught while creating a directory service iterator.

**Action** Review the server log files for the stack trace of the cause.

**POP.018.0006.DirSearchProvider – Unable to locate the attribute provider for URI={0}**

**Explanation** While filtering a principal by an attribute, the provider of the attribute was not located.

**Action** Check the server to make sure the logged provider URI resolves to a attribute provider.

**POP.018.0007.AttachmentsProvider – Attachments container id is not valid: {0}**

**Explanation** The attachments provider for an Attachment Panel control does not have a valid container id for read/write of attachment files.

**Action** The developer should review the application code to ensure the attachment provider container id is a valid folder id or alias.

**POP.018.0008.AttachmentsProvider – Specified attachments container id is not a container: {0}**

**Explanation** The attachments provider for an Attachment Panel control does not have a valid container id for read/write of attachment files.

**Action** The developer should review the application code to verify that the attachment provider container id is a valid folder id or alias.

**POP.018.0009.AttachmentsProvider – Attachment id has not been specified**

**Explanation** The attachments provider updateAttachment or removeAttachment API was called but the attachment id parameter was null.

**Action** The developer should review the application code to verify that the API calls are passing an attachment id value that is not null.

**POP.018.0010.AttachmentsProvider – FileItem has not been specified**

**Explanation** The attachments provider addAttachment or updateAttachment API was called but the fileItem parameter was null.

**Action** The developer should review the application code to verify that the API calls are passing a fileItem value that is not null.

**POP.018.0011.AttachmentsProvider – The specified attachment id is not a child of the attachment container: {0}**

**Explanation** The attachments provider updateAttachment or removeAttachment API was called with an attachment id that is not a child of the attachments container.

**Action** The developer should review the application code to verify that the API calls are passing an attachment id value that is a child of the attachments folder.

**POP.019.0001 Unable to convert data type "{0}" to "{1}"**

**Explanation** The system failed to convert an object from the source data type to the destination data type.

**Action** Review the error stack trace in the My webMethods Server server logs to determine the cause.

**POP.019.0002 Cannot load "{0}" because it is not an HTTP resource**

**Explanation** The html parser failed to load the resource.

**Action** Inspect the error stack trace in the My webMethods Server server logs to determine the cause.

**POP.023.0001 Failed to start HPSTRA engine**

**Explanation** An error occurred and the HPSTRA engine failed to start.

**Action** Check the HPSTRA configuration and restart My webMethods Server.

**POP.023.0002 Failed to save HPSTRA configuration**

**Explanation** An internal error occurred when saving the specified HPSTRA configuration.

**Action** Gather error information from the logs and contact Software AG Global Support.

**POP.023.0003 Failed to configure HPSTRA engine**

**Explanation** An error occurred when configuring the HPSTRA engine.

**Action** Gather error information from the logs and contact Software AG Global Support.

**POP.023.0004 Error occurred while stopping HPSTRA**

**Explanation** An internal error occurred when stopping the HPSTRA engine.

**Action** Gather error information from the logs and contact Software AG Global Support.

- POP.023.0005**      **Invalid HPSTRA configuration specified. Details: {0}**  
**Explanation**      The specified HPSTRA congfiguration is invalid or incomplete.  
**Action**              Check the HPSTRA configuration and retry the previous operation.
- POP.023.0006**      **Failed to perform operation, HPSTRA engine is not enabled. Please configure it properly**  
**Explanation**      The HPSTRA engine is disabled and cannot perform the requested operation.  
**Action**              Enable the HPSTRA engine and retry the operation.
- POP.023.0007**      **HPSTRA action execution failed, Reason:**  
**Explanation**      An internal error occurred and the HPSTRA engine failed to execute the requested operation.  
**Action**              Gather error information from the server logs and contact Software AG Global Support.
- POP.023.0009**      **Failed to authenticate against an Elasticsearch instance, please check your credentials**  
**Explanation**      The user name and/or password, specified in the HPSTRA configuration are not valid.  
**Action**              Check your credentials in the Authentication section of the HPSTRA configuration and retry the operation.
- POP.023.0010**      **An Elasticsearch exception occurred. Details: {0}**  
**Explanation**      The Elasticsearch server returned an error message in response to the request from the HPSTRA engine.  
**Action**              Gather error information from the logs and contact Software AG Global Support.
- POP.101.0001.com.softwareag.caf.shared.diagnostics – The directory does not exist**  
**Explanation**      The specified directory is not found.  
**Action**              Provide a valid directory location as a parameter.
- POP.101.0002.com.softwareag.caf.shared.diagnostics – The specified path is not a valid directory**  
**Explanation**      The specified location is not a directory.  
**Action**              Provide a valid directory location as a parameter.

**POP.101.0006.com.softwareag.caf.shared.diagnostics – Unsupported report type**

**Explanation** A report was generated by an AeventProcessor which is not supported.  
**Action** Use an existing report or add the new one to the list of supported reports in LogAnalyzer.java

**POP.101.0007.com.softwareag.caf.shared.diagnostics – An error occurs while adding a root element to the analyzed log file**

**Explanation** A root element cannot be added to the analyzed log file.  
**Action** Check the log file for any discrepancies.

**POP.101.0010.com.softwareag.caf.shared.diagnostics – Either one or both of the provided documents are null**

**Explanation** The method load() was not invoked beforehand or it was invoked using incorrect parameters.  
**Action** You need to call the load() method before you continue using EnvDiff API.

**POP.101.0011.com.softwareag.caf.shared.diagnostics – At least one argument has to differ from null**

**Explanation** This invocation is not supported.  
**Action** Contact Software AG Global Support.

**POP.101.0012.com.softwareag.caf.shared.diagnostics – Cannot read the following file: {0}**

**Explanation** The file cannot be read.  
**Action** Check file and directory permissions; if the file is accessed over a network, check network connectivity.

**POP.101.0013.com.softwareag.caf.shared.diagnostics – No output channel found**

**Explanation** This behavior is not supported.  
**Action** Contact Software AG Global Support.

**POP.101.0014.com.softwareag.caf.shared.diagnostics – Input directory or file does not exist: {0}**

**Explanation** The specified directory or file does not exist.  
**Action** Specify an existing directory or file.

**POP.101.0015.com.softwareag.caf.shared.diagnostics – The system variable %1\$s and the %2\$s parameter are not set**

**Explanation** The required system properties are incorrect or are not set.

**Action** Set the system variables using proper values. For more information, see the product documentation.

**POP.101.0016.com.softwareag.caf.shared.diagnostics – Similarity level must be in the following range: 0-100**

**Explanation** Similarity level is not set to a valid value.

**Action** Set a similarity level between 0 and 100.

**POP.101.0017.com.softwareag.caf.shared.diagnostics – Java artifact mapping file does not exist in: {0}; cannot generate {1} report.**

**Explanation** A Java artifact mapping file cannot be found. The report cannot be generated.

**Action** Specify a valid Java artifact mapping XML file. Use the --java-artifact-mapping parameter to specify the path.

**POP.101.0018.com.softwareag.caf.shared.diagnostics – File not found in: {0}**

**Explanation** The specified file does not exist.

**Action** Specify an existing file.

**POP.101.0019.com.softwareag.caf.shared.diagnostics – File name is null**

**Explanation** The name of the file was not set in java artifact mapping XML file and this is a unsupported scenario.

**Action** Contact Software AG Global Support.

**POP.101.0020.com.softwareag.caf.shared.diagnostics – Product ID is null.**

**Explanation** The product ID was not set in a Java artifact mapping XML file; this is a unsupported scenario.

**Action** Contact Software AG Global Support.

**POP.101.0021.com.softwareag.caf.shared.diagnostics – Database configuration is not specified**

**Explanation** This error occurs when the file mws.db.xml is not specified or cannot be found.

**Action** Specify a valid mws.db.xml file.

**POP.102.0001.com.webmethods.caf.shared.bpm.common – This configuration is missing important parameters! Session and node id are mandatory!**

**Explanation** This error occurs: 1) when a node id is not provided when trying to search for a content type, or 2) when a session is not opened.

**Action** For 1), select a node that the searched content is associated with. For 2), verify that the CSP server is running, properly configured, and connected.

**POP.102.0002.com.webmethods.caf.shared.bpm.common – Illegal connection parameters**

**Explanation** An attempt has been made to connect to the CSP server without providing username/password values.

**Action** In My webMethods, check the Environment entries for the "wm\_csp\_task" portlet. If they are empty, next check the Global Environment entries. If no values are provided, specify a value for "csp/default/username" and "csp/default/password" entries. In general, the user name and password are specified in the Global Environment entries, except in cases when you have multiple CSP servers and want different portlets to connect to different servers. Otherwise, the Global Environment values are inherited by all portlets.

**POP.102.0003.com.webmethods.caf.shared.bpm.common – The provided session is null!**

**Explanation** The session which is the client primary access point to the CSP server is not instantiated.

**Action** Verify that the username and password are correct in the CSP configuration in My webMethods Server.

**POP.102.0005.com.webmethods.caf.shared.bpm.common – Error while marshalling!**

**Explanation** This error indicates that a low-level communication problem exists between Task Engine and webMethods Content Service Platform.

**Action** Stop and restart the Task Engine and the CSP server and try again. If the problem persists, contact Software AG Global Support.

**POP.102.0006.com.webmethods.caf.shared.bpm.common – Error while unmarshaling result!**

**Explanation** This error indicates that a low-level communication problem exists between Task Engine and webMethods Content Service Platform.

**Action** Stop and restart the Task Engine and the CSP server and try again. If the problem persists, contact Software AG Global Support.

**POP.102.0008.com.webmethods.caf.shared.bpm.common – This configuration is missing important parameters! Content id is mandatory!**

**Explanation** The Content ID value is not set.

**Action** Verify that a Content ID is set for this provider; ensure that the binding expression is correctly configured.

**POP.102.0009.com.webmethods.caf.shared.bpm.common – No retrieval module initiated! Please set proper session!**

**Explanation** The CSP session is not set for the provider; the retrieval module cannot be initiated.

**Action** Verify that a session is set for this provider; ensure that the binding expression is correctly configured.

**PerformanceMonitorDefaultviewView.errorMessage.unsupportedPerfServiceImpl – Currently enabled performance service implementation {0} does not support analysis. Cannot proceed.**

**Explanation** The performance service implementation specified for support analysis is not supported. Without these mandatory parameters, the execution cannot proceed.

**Action** Provide the supported parameters required for the currently enabled performance service.

**WSC.001.0002 Failed to bind to endPoint: {0} and interface: {1}**

**Explanation** The error occurs at binding to the WS-Stack registry.

**Action** Inspect the stack trace in the My webMethods Server log files to determine the cause of the exception.

**WSC.001.0004 Context instance does not allow access of inbound SOAP request interceptors**

**Explanation** An exception occurred while registering the interceptor with a context at the WS Server service provider.

**Action** Inspect the stack trace in the My webMethods Server log files to determine the cause of the exception.

**WSC.001.0005 Context instance does not allow access of outbound SOAP request interceptors**

**Explanation** An exception occurred while registering the request interceptor with the context.

**Action** Verify that the context is an instance of ProxyContext.

---

<b>WSC.001.0006</b>	<b>Exception occurred while invoking webservice: {0}. Details: {1}</b>
<b>Explanation</b>	An exception occurred while invoking the specified web service.
<b>Action</b>	Inspect the stack trace in the My webMethods Server log files to determine the cause of the exception.
<b>WSC.001.0007</b>	<b>Unable to connect to web service at {0}</b>
<b>Explanation</b>	The reason for the web service connection failure is specified in the error message.
<b>Action</b>	Check the detailed error message and take the appropriate action.
<b>WSC.002.0002</b>	<b>SAML artifact not found in request</b>
<b>Explanation</b>	The exception occurs when SAML authentication has to be performed, and indicates that the SAML artifact was not found within the SOAP headers of the incoming SOAP request.
<b>Action</b>	Check the SOAP request regarding the SAML artifact.
<b>WSC.002.0009</b>	<b>SAML Assertion is missing the subject name</b>
<b>Explanation</b>	An exception was thrown during the verification of the SAML Assertion showing that the subject name is missing.
<b>Action</b>	Check the subject name.
<b>WSC.002.0010</b>	<b>SAML Assertion has an invalid authentication method, method: {0}</b>
<b>Explanation</b>	The SAML Assertion passed is not valid.
<b>Action</b>	Specify a valid authentication method.
<b>WSC.002.0012</b>	<b>SAML Assertion has an invalid statement format</b>
<b>Explanation</b>	While validating the SAML Assertion the format of the statement is invalid.
<b>Action</b>	Specify a valid statement format.
<b>WSC.002.0013</b>	<b>SAML Assertion has an invalid assertion id.</b>
<b>Explanation</b>	The SAML Assertion has an invalid assertion ID.
<b>Action</b>	Check the assertion ID.

**WSC.002.0014      The credential type is not supported: {0}**  
**Explanation**      An exception occurred during realm authentication.  
**Action**              Supply a correct credential type.

**WSC.002.0015      User failed to authenticate with basic auth: {0}**  
**Explanation**      An exception occurred during realm authentication.  
**Action**              Check the username and password supplied.

**ascii.only.name.validation.msg – Name cannot contain non ASCII characters!**

**Explanation**      The Name field can contain only ASCII characters.  
**Action**              Remove the non-ASCII characters from the Name field.

**config.connection.authentication.password.value – 'Password' cannot be null or empty**

**Explanation**      My webMethods Server stores the configuration for the HPSTRA engine in the hpstra\_config.json file. This exception occurs when the configuration file was modified manually, and the "password" key under connection > authentication does not exist, or has a null or empty value.  
**Action**              Check the HPSTRA configuration file, supply a valid password for connecting to the Elasticsearch server, and restart My webMethods Server.

**config.connection.authentication.username.value – 'Username' cannot be null or empty**

**Explanation**      My webMethods Server stores the configuration for the HPSTRA engine in the hpstra\_config.json file. This exception occurs when the configuration file was modified manually, and the "username" key under connection > authentication does not exist, or has a null or empty value.  
**Action**              Check the HPSTRA configuration file, supply a valid user name for connecting to the Elasticsearch server, and restart My webMethods Server.

**config.connection.autoDiscovery.pollingInterval.value – Autodiscovery 'polling interval' parameter should be greater or equal to 1**

**Explanation**      My webMethods Server stores the configuration for the HPSTRA engine in the hpstra\_config.json file. This exception occurs when the configuration file was modified manually, and the "pollingInterval" key under connection > autoDiscovery has an invalid value.  
**Action**              Check the HPSTRA configuration file, supply a valid value for the "pollingInterval" key, and restart My webMethods Server. Valid values are positive integers from 1 to 2147483647.

**config.connection.connectTimeout.value – The 'connect timeout' parameter should be greater or equal to 1**

**Explanation** My webMethods Server stores the configuration for the HPSTRA engine in the hpstra\_config.json file. This exception occurs when the configuration file was modified manually, and the "connectTimeout" key under connection has an invalid value.

**Action** Check the HPSTRA configuration file, supply a valid value for the "connectTimeout" key, and restart My webMethods Server. Valid values are positive integers from 1 to 2147483647.

**config.connection.connectionPool.maxConnections.value – The 'maximum pool connections' parameter should be greater or equal to 1**

**Explanation** My webMethods Server stores the configuration for the HPSTRA engine in the hpstra\_config.json file. This exception occurs when the configuration file was modified manually, and the "maxConnections" key under connection has an invalid value.

**Action** Check the HPSTRA configuration file, supply a valid value for the "maxConnections" key, and restart My webMethods Server. Valid values are positive integers from 1 to 2147483647.

**config.connection.requestTimeout.value – The 'request timeout' parameter should be greater or equal to 1**

**Explanation** My webMethods Server stores the configuration for the HPSTRA engine in the hpstra\_config.json file. This exception occurs when the configuration file was modified manually, and the "requestTimeout" key under connection has an invalid value.

**Action** Check the HPSTRA configuration file, supply a valid value for the "requestTimeout" key, and restart My webMethods Server. Valid values are positive integers from 1 to 2147483647.

**config.connection.servers.size.value – The 'servers' parameter should contains at least one server URL (http, https)**

**Explanation** My webMethods Server stores the configuration for the HPSTRA engine in the hpstra\_config.json file. This exception occurs when the configuration file was modified manually, and the "servers" key under connection is empty, or has an invalid value.

**Action** Check the HPSTRA configuration file, supply a valid value for the "servers" key, and restart My webMethods Server. Valid values are unique http or https URLs.

**config.connection.servers.type.value – All entries of the 'servers' parameter should be unique and valid server URLs (http, https)**

**Explanation** My webMethods Server stores the configuration for the HPSTRA engine in the hpstra\_config.json file. This exception occurs when the configuration file was modified manually, and the "servers" key under connection has one or more invalid values.

**Action** Check the HPSTRA configuration file, supply valid values for the "servers" key, and restart My webMethods Server. Valid values are unique http or https URLs.

**config.connection.value – Configuration's connection information cannot be null**

**Explanation** My webMethods Server stores the configuration for the HPSTRA engine in the hpstra\_config.json file. This exception occurs when the configuration file was modified manually, and the "connection" key does not exist.

**Action** Check the HPSTRA configuration file, supply a valid configuration under the "connection" key, and restart My webMethods Server.

**config.persistence.consistency.value – Index operation 'consistency' parameter should be either null (use default settings) or one of the values: 'one' | 'quorum' | 'all'**

**Explanation** My webMethods Server stores the configuration for the HPSTRA engine in the hpstra\_config.json file. This exception occurs when the configuration file was modified manually, and the "consistency" key under "persistence" has an invalid value.

**Action** Check the HPSTRA configuration file, supply a valid value for the "consistency" key, and restart My webMethods Server. Valid values are null (default), "one", "quorum", and "all".

**config.persistence.createIndex.numberOfReplicas.value – The parameter 'number\_of\_replicas' for the index should be greater or equal to 1**

**Explanation** My webMethods Server stores the configuration for the HPSTRA engine in the hpstra\_config.json file. This exception occurs when the configuration file was modified manually, and the "numberOfReplicas" key under connection > createIndex has an invalid value.

**Action** Check the HPSTRA configuration file, supply a valid value for the "numberOfReplicas" key, and restart My webMethods Server. Valid values are positive integers from 1 to 2147483647.

**config.persistence.createIndex.numberOfShards.value – The parameter 'number\_of\_shards' for the index should be greater or equal to 1**

**Explanation** My webMethods Server stores the configuration for the HPSTRA engine in the hpstra\_config.json file. This exception occurs when the configuration file was modified manually, and the "numberOfShards" key under connection > createIndex has an invalid value.

**Action** Check the HPSTRA configuration file, supply a valid value for the "numberOfShards" key, and restart My webMethods Server. Valid values are positive integers from 1 to 2147483647.

**config.persistence.timeout.value – Index operation 'timeout' parameter should be greater or equal to 1**

**Explanation** My webMethods Server stores the configuration for the HPSTRA engine in the hpstra\_config.json file. This exception occurs when the configuration file was modified manually, and the "timeout" key under "persistence" has an invalid value.

**Action** Check the HPSTRA configuration file, supply a valid value for the "timeout" key, and restart My webMethods Server. Valid values are positive integers from 1 to 2147483647.

**config.search.searchType.value – Search operation 'search\_type' parameter should be either null (use default settings) or one of the values: 'query\_then\_fetch' | 'dfs\_query\_then\_fetch'**

**Explanation** My webMethods Server stores the configuration for the HPSTRA engine in the hpstra\_config.json file. This exception occurs when the configuration file was modified manually, and the "searchType" key under "search" has an invalid value.

**Action** Check the HPSTRA configuration file, supply a valid value for the "searchType" key, and restart My webMethods Server. Valid values are null (default), "query\_then\_fetch", and "dfs\_query\_then\_fetch".

**config.search.timeout.value – Search operation 'timeout' parameter should be greater or equal to 1**

**Explanation** My webMethods Server stores the configuration for the HPSTRA engine in the hpstra\_config.json file. This exception occurs when the configuration file was modified manually, and the "timeout" key under "search" has an invalid value.

**Action** Check the HPSTRA configuration file, supply a valid value for the "timeout" key, and restart My webMethods Server. Valid values are positive integers from 1 to 2147483647.

**config.synchronization.batchSize.value – Synchronization's 'batch size' parameter should be greater or equal to 1**

**Explanation** My webMethods Server stores the configuration for the HPSTRA engine in the hpstra\_config.json file. This exception occurs when the configuration file was modified manually, and the "batchSize" key under "synchronization" has an invalid value.

**Action** Check the HPSTRA configuration file, supply a valid value for the "batchSize" key, and restart My webMethods Server. Valid values are positive integers from 1 to 2147483647.

**config.synchronization.lockTimeout.value – Synchronization's 'lock timeout' parameter should be greater or equal to 1**

**Explanation** My webMethods Server stores the configuration for the HPSTRA engine in the hpstra\_config.json file. This exception occurs when the configuration file was modified manually, and the "lockTimeout" key under "synchronization" has an invalid value.

**Action** Check the HPSTRA configuration file, supply a valid value for the "lockTimeout" key, and restart My webMethods Server. Valid values are positive integers from 1 to 2147483647.

**config.synchronization.pollingInterval.value – Synchronization's 'polling interval' parameter should be greater or equal to 1**

**Explanation** My webMethods Server stores the configuration for the HPSTRA engine in the hpstra\_config.json file. This exception occurs when the configuration file was modified manually, and the "pollingInterval" key under "synchronization" has an invalid value.

**Action** Check the HPSTRA configuration file, supply a valid value for the "pollingInterval" key, and restart My webMethods Server. Valid values are positive integers from 1 to 2147483647.

**error.msg.noDebug The requested URL {0} resulted in an error.**

**Explanation** An error occurred while processing the URL.

**Action** Verify that the URL is correct.

**error.msg.withDebug – The requested URL {0} resulted in an error in {1}.**

**Explanation** An error occurred while processing the URL.

**Action** Verify that the URL is correct.

**g11n.Spregistration.propertygroup.customErrMsg6 – SAML Attribute Name cannot be empty**

**Explanation** You did not provide a value in the required field SAML Attribute Name.

**Action** Provide a valid value in the SAML Attribute Name field.

**g11n.Spregistration.propertyline.non-ascii – Only alphabet, numbers and underscores allowed and Length should not be more than 25**

**Explanation** The Attributes field can contain up to 25 symbols. Only alphanumerical characters and underscores are allowed.

**Action** Remove any illegal or excess characters from the field.

**g11n.UmConnectionConfiguration.service.unavailable – Configuration store service unavailable**

**Explanation** The OSGI service that stores the SSL configuration in the platform secure store is not available.

**Action** Retry saving the SSL configuration. If the issue persist, contact your system administrator.

**g11n.UmConnectionConfiguration.validation.path – Invalid path specified**

**Explanation** The location of the truststore/keystore for CA/client certificates is not a valid file path.  
**Action** Check the specified path and supply a valid entry.

**http.status.401 Unauthorized**

**Explanation** Invalid basic authentication credentials.  
**Action** Contact the security officer/web master for this resource and obtain the proper authorization for your credentials.

**http.status.403 Forbidden**

**Explanation** The action is prohibited.  
**Action** The owner of this resource does not allow access to the resource. Contact the security officer/web master for this resource and obtain the proper authorization for your credentials.

**http.status.404 Not Found**

**Explanation** The specified value was not found.  
**Action** Verify that the URL is correct. This error most often occurs when the resource has been removed from the server. It can also be caused by a DNS failure, if the server has been assigned a new IP address, or if the server no longer exists.

**http.status.405 Method Not Allowed**

**Explanation** This HTTP method (GET, PUT, etc.) is not allowed on this server for the specified URL.  
**Action** Use only supported methods. Contact the security officer/web master for this resource for more information.

**http.status.406 Not Acceptable**

**Explanation** The content returned from the server is not specified as acceptable by the client.  
**Action** Investigate the problem by looking at the Accept headers generated by the client system and the data stream returned by the web server.

<b>http.status.407</b>	<b>Proxy Authentication Required</b>
<b>Explanation</b>	Access to the URL resource requires the prior use of a proxy server that needs authentication which has not been provided.
<b>Action</b>	Log in to the proxy server with valid credentials and retry.
<b>http.status.408</b>	<b>Request Time-out</b>
<b>Explanation</b>	The interval of time between the establishment of an IP connection (socket) between the client and the server and the receipt of any data on that socket is too long. The server has dropped the connection.
<b>Action</b>	Attempt reconnecting to the resource. This error is typically caused by high server loads or network traffic. Contact the web master for this resource if the problem persists.
<b>http.status.409</b>	<b>Conflict</b>
<b>Explanation</b>	The request submitted by the client cannot be completed because it conflicts with an existing condition or rule. For example, a file on the server cannot be replaced with a file that has an older timestamp.
<b>Action</b>	Examine the client action and consult with the web master for this resource.
<b>http.status.413</b>	<b>Request Entity Too Large</b>
<b>Explanation</b>	The HTTP data stream sent by the client is too large to be accepted by the server.
<b>Action</b>	Attempt sending data in smaller batches. Otherwise, consult with the web master for this resource.
<b>http.status.415</b>	<b>Unsupported Media Type</b>
<b>Explanation</b>	The HTTP data stream sent by the client identifies a URL resource with a media type that does not agree with the media type specified on the request, is incompatible with the current data for the resource, or is incompatible with the HTTP method specified on the request.
<b>Action</b>	Examine the request and correct the media type if possible. Otherwise, consult with the web master for this resource.
<b>http.status.422</b>	<b>Unprocessable Entity (WebDAV)</b>
<b>Explanation</b>	The request was well-formed but was unable to be processed due to semantic errors.[
<b>Action</b>	Examine and correct the entity definition.

---

<b>http.status.423</b>	<b>Locked (WebDAV)</b>
<b>Explanation</b>	The resource that is being accessed is locked.
<b>Action</b>	Unlock the resource if possible. Otherwise, contact the web master for this resource.
<b>http.status.424</b>	<b>Failed Dependency (WebDAV)</b>
<b>Explanation</b>	The method could not be performed on the resource because the requested action depended on another action and that action failed (for example, a PROPPATCH).
<b>Action</b>	Examine the action request, correct as necessary, and perform again.
<b>http.status.500</b>	<b>Internal Server Error</b>
<b>Explanation</b>	The server encountered an unexpected condition that prevented it from fulfilling the request by the client.
<b>Action</b>	Make sure that the required services are running, communication channels are accessible, and parameters are valid. Examine the server logs for more information if possible. Otherwise, contact the server administrator.
<b>http.status.501</b>	<b>Not Implemented</b>
<b>Explanation</b>	The server does not understand or does not support the HTTP method it finds in the HTTP data stream sent to it by the client.
<b>Action</b>	Make sure the request contains a valid HTTP method.
<b>http.status.507</b>	<b>Insufficient Storage (WebDAV)</b>
<b>Explanation</b>	The method could not be performed on the resource because the server is unable to store the representation needed to successfully complete the request.
<b>Action</b>	This condition is usually temporary. If persistent, verify that sufficient storage is available on the server, or contact the system administrator. If the request that received this status code was the result of a user action, the request must not be repeated until it is requested by a separate user action.
<b>install.fixes.1</b>	<b>Installing update XML component {0}</b>
<b>Explanation</b>	The update XML file must be in the proper format and an installation location must be specified.
<b>Action</b>	Make sure the file contains the correct XML format and specify the correct location.

**install.fixes.2**      **Failed to install update XML component {0}**  
**Explanation**      Update manager has attempted to install the update XML component but the attempt has failed.  
**Action**              Make sure that My webMethods Server is running and is connected to the network, and that network connectivity exists to the server. Retry the installation. Otherwise, contact the system administrator.

**install.fixes.3**      **Failed to delete update XML component {0}**  
**Explanation**      Update Manager attempted to delete the XML component but was not successful.  
**Action**              Make sure that My webMethods Server is running and is connected to the network, and that network connectivity exists to the server. Retry the deletion. Check the server log file for more information. Otherwise, contact the system administrator.

**install.fixes.4**      **Failed to process all update XML components**  
**Explanation**      The update XML components operation could not be processed.  
**Action**              Verify that the parameters are appropriately specified in the request. Otherwise, contact the system administrator.

**install.fixes.5** **Not Used – Completed processing of update XML components**  
**Explanation**      XML components were updated successfully.  
**Action**              No action required.

**ldap.exceptions**    **Unable to retrieve data from {0} Idaps**  
**Explanation**      The specified directory services failed to return a result due to an error.  
**Action**              Check the My webMethods Server logs for errors related to the specified directory services.

**message.um.remoteupdate.fail** – **MWS node with name "{0}" failed to update with new Universal Messaging URL.**  
**Explanation**      During an update of the cluster configuration, the specified node failed to be updated.  
**Action**              Log into the specified node, and on the Cluster Administration page, click Reload to manually update the node.

**message.um.remoteupdate.fail.ctx – MWS failed to acquire user context, before notifying other nodes about UM URL change.**

**Explanation** During an update of the cluster configuration, the specified node failed to be updated.  
**Action** Log into the specified node, and on the Cluster Administration page, click Reload to manually update the node.

**message.um.update.fail – Current MWS node failed to update with new Universal Messaging URL.**

**Explanation** While updating the JNDI URL of the specified node, the JMS system of that node failed to reload.  
**Action** Restart the node. If My webMethods Server cannot connect to Universal Messaging, check the logs for errors. If the errors are not related to network connectivity, contact Software AG.

**message.um.url.invalid – The specified JNDI URL "{0}" is not valid.**

**Explanation** The specified JNDI URL does not conform to the Universal Messaging standards.  
**Action** The URL must start with a valid UM protocol, such as nsp, nsps, nhp, or nhps, for example: nsp://myurl:9000.



# 20 OSGi Messages

---

<b>OGICRE0003</b>	<b>Expected String [2] but its length is "{0}"</b>
<b>Explanation</b>	There is a problem with the user-defined credentials that are passed to the server in order to authenticate the user before creating MBeanServerConnection.
<b>Action</b>	The expected user-defined credentials are a username and password. Provide these security credentials only.
<b>OGICRE0004</b>	<b>Authentication fails with user "{0}"</b>
<b>Explanation</b>	There is a problem with authentication of the current user.
<b>Action</b>	Check the provided username and password.
<b>OGICRE0015</b>	<b>"{0}" property is not set, cannot proceed.</b>
<b>Explanation</b>	JMX authentication configuration property " <code>com.softwareag.platform.startup.jmx.auth.config</code> " is not set, cannot proceed.
<b>Action</b>	Set the JMX authentication configuration property " <code>com.softwareag.platform.startup.jmx.auth.config</code> " and provide a valid value to it.
<b>OGICRE0016</b>	<b>JAAS login configuration property "{0}" is not set, cannot proceed.</b>
<b>Explanation</b>	During the startup routine, the OSGi platform attempts to prepare JAAS configuration. The platform expects that the " <code>com.softwareag.platform.startup.jaas.login.config</code> " property is set and points to a valid JAAS configuration file. The error message is displayed when the property is not available at platform startup.
<b>Action</b>	Ensure that the " <code>com.softwareag.platform.startup.jaas.login.config</code> " is set and points to a valid JAAS configuration file.

<b>OGICRE0019</b>	<b>System property "java.io.tmpdir" is not set or empty, cannot ensure that the directory exists.</b>
<b>Explanation</b>	The 'java.io.tmpdir' property is expected to be set by the JVM. The platform startup cannot ensure that the directory pointed by this property is available if the property is empty or undefined.
<b>Action</b>	If you want to use a temporary file directory, make sure that it exists and is set to the JVM.
<b>OGICRE0021</b>	<b>Java temporary directory pointed by "java.io.tmpdir" system property: "{0}" does not exist and cannot be created.</b>
<b>Explanation</b>	The java temporary directory pointed by the "java.io.tmpdir" JVM property does not exist and automatic creation of this directory failed.
<b>Action</b>	Ensure that the directory pointed by the "java.io.tmpdir" JVM property exists.
<b>OGICRI0008</b>	<b>Standard JMX Management is used.</b>
<b>Explanation</b>	Custom authentication is not enabled. The standard JMX Management is used.
<b>Action</b>	If you want to enable custom authentication, set a System property with name "com.softwareag.jmx.noCustomAuthentication" and set it to "false".
<b>OGICRI0013</b>	<b>Using JMX authentication configuration: "{0}"</b>
<b>Explanation</b>	Information about the value of "com.softwareag.platform.startup.jmx.auth.config" JMX authentication configuration parameter.
<b>Action</b>	None.
<b>OGICRI0014</b>	<b>Using JAAS login configuration: "{0}".</b>
<b>Explanation</b>	Information about the value of "java.security.auth.login.config" JAAS configuration parameter.
<b>Action</b>	None.
<b>OGICRI0022</b>	<b>Successfully created Java temporary directory: {0}</b>
<b>Explanation</b>	Directory pointed by "java.io.tmpdir" system property did not exist and the OSGi platform startup bundle created it automatically.
<b>Action</b>	None.

<b>OGICRW0017</b>	<b>Configured JMX RMI Agent port: "{0}" is not valid; default port "{1}" will be used instead.</b>
<b>Explanation</b>	The platform startup routine is attempting to initialize the JMX RMI Agent using the port configured in the "com.softwareag.platform.startup.jmx.rmi.agent.port" key. The property is not a valid number.
<b>Action</b>	Set a valid port number in the "com.softwareag.platform.startup.jmx.rmi.agent.port" key.
<b>OGICRW0020</b>	<b>The parent directory of the Java temporary directory ({0}) is not write enabled.</b>
<b>Explanation</b>	Cannot write into the parent directory of the temporary directory pointed by the "java.io.tmpdir" system property. Automatic creation of the temporary directory will fail.
<b>Action</b>	Ensure that the user who started the platform has permissions to write into the parent directory of the temporary files directory.
<b>OGICRW0023</b>	<b>The parent directory of the Java temporary directory pointed by "java.io.tmpdir" system property: "{0}" does not exist and cannot be created.</b>
<b>Explanation</b>	When the OSGi platform is started it attempts to ensure that the temporary files directory (denoted by the "java.io.tmpdir" system property) exists. If the directory does not exist on the file system, the OSGi platform startup bundle attempts to create it. This message is displayed when the OSGi platform startup bundle fails to create the parent directory of the temporary files directory.
<b>Action</b>	Ensure that the directory pointed by the "java.io.tmpdir" JVM property exists.
<b>OGIMIGE0002</b>	<b>ERROR: Missing file in source installation - {0}</b>
<b>Explanation</b>	This message is displayed when no source file is found.
<b>Action</b>	Check if the file exists and is readable for the user.
<b>OGIMIGE0003</b>	<b>ERROR: Missing file in destination installation - {0}</b>
<b>Explanation</b>	This message is displayed when no destination file is found under path: <installdir_new_version>/profiles<some_profile>/configuration/com.softwareag.platform.config.propsloader/
<b>Action</b>	Check if the file exists and is readable for the user.
<b>OGIMIGE0004</b>	<b>ERROR: Backup failed for destination file - {0}</b>
<b>Explanation</b>	The file is backed up before merging . Losing this file might be crucial.
<b>Action</b>	Make sure that the file can be written in the parent directory.

<b>OGIMIGE0006</b>	<b>ERROR: Error while opening file - {0}</b>
<b>Explanation</b>	In order to migrate a file its content should be read. This error occurs because the file could not be opened properly.
<b>Action</b>	Make sure the file is not locked (for example, the file may be already opened by another program).
<b>OGIMIGE0007</b>	<b>ERROR: Result configuration file in destination installation was not found - {0}</b>
<b>Explanation</b>	After merging, the result is either a new file, or an updated overwritten destination file.
<b>Action</b>	Please make sure the file exists and is readable for the user.
<b>OGIMIGE0010</b>	<b>ERROR: More than one in the destination installation - {0} were found under {1}</b>
<b>Explanation</b>	This message is displayed when more than one destination file is found. This is not expected if a clean destination installation is done.
<b>Action</b>	Check the log file to see where are the files. Remove the unneeded files and leave only one file - the default one.
<b>OGIMIGE0013</b>	<b>ERROR: Loading source properties layout configuration failed. The source file is: from file {0}</b>
<b>Explanation</b>	When we load our properties we also load the comments and blank lines the file contains.
<b>Action</b>	Make sure that you source file is a valid java property file and it is not corrupted.
<b>OGIMIGE0014</b>	<b>ERROR: Cannot identify version of product {0}. Cannot find any locally installed products in the specified installation directory: {1}</b>
<b>Explanation</b>	The migration application attempted to identify the version of a locally installed product with the given product prop file name (without the .prop suffix), but no locally installed products were found in the specified installation directory.
<b>Action</b>	Specify the source version of the product when prompted to.
<b>OGIMIGE0015</b>	<b>ERROR: Cannot identify version of product {0}. Cannot find this product in the list of locally installed products in the specified installation directory: {1}</b>
<b>Explanation</b>	The migration application attempted to identify the version of a locally installed product with the given product prop file name (without the .prop suffix), but such locally installed product was not found in the specified installation directory.
<b>Action</b>	Specify the source version of the product when prompted to.

---

<b>OGIMIGE0018</b>	<b>ERROR: Storing result properties configuration layout failed.</b>
<b>Explanation</b>	The property file with all the properties and their comments failed on the saving step.
<b>Action</b>	Check the file access permissions of your target installation.
<b>OGIMIGE0019</b>	<b>ERROR: JAAS configuration {0} does not exist.</b>
<b>Explanation</b>	The JAAS configuration file is missing and the migration cannot proceed.
<b>Action</b>	Migration for JAAS configuration was not successful. Refer to the upgrade documentation and execute the required manual steps.
<b>OGIMIGE0020</b>	<b>ERROR: JAAS configuration {0} is not a file.</b>
<b>Explanation</b>	The JAAS configuration file is not a valid file and the migration cannot proceed.
<b>Action</b>	Migration for JAAS configuration was not successful. Refer to the upgrade documentation and execute the required manual steps.
<b>OGIMIGE0021</b>	<b>ERROR: Destination JAAS configuration {0} does not exist.</b>
<b>Explanation</b>	The JAAS configuration file is missing and the migration cannot proceed.
<b>Action</b>	Migration for JAAS configuration was not successful. Refer to the upgrade documentation and execute the required manual steps.
<b>OGIMIGE0022</b>	<b>ERROR: Destination JAAS configuration {0} is not a file.</b>
<b>Explanation</b>	The destination JAAS configuration file is not a valid file and the migration cannot proceed.
<b>Action</b>	Migration for JAAS configuration was not successful. Refer to the upgrade documentation and execute the required manual steps.
<b>OGIMIGE0023</b>	<b>ERROR: Backup failed for destination JAAS configuration file.</b>
<b>Explanation</b>	Creating a backup of the original file was not successful and it is unsafe for the migration to continue.
<b>Action</b>	Migration for JAAS configuration was not successful. Refer to the upgrade documentation and execute the required manual steps.
<b>OGIMIGE0024</b>	<b>ERROR: Error parsing source JAAS configuration</b>
<b>Explanation</b>	An error is found in the source JAAS configuration and the migration cannot proceed.
<b>Action</b>	Migration for JAAS configuration was not successful. Refer to the upgrade documentation and execute the required manual steps.

<b>OGIMIGE0025</b>	<b>ERROR: Error parsing destination JAAS configuration</b>
<b>Explanation</b>	Migration of the JAAS configuration was not successful. An error was found in the destination JAAS configuration and the migration cannot proceed.
<b>Action</b>	Refer to the upgrade documentation and execute the required manual steps.
<b>OGIMIGE0026</b>	<b>ERROR: Error saving destination JAAS configuration.</b>
<b>Explanation</b>	An error occurred while storing the migrated JAAS configuration and the migration cannot proceed.
<b>Action</b>	Migration for JAAS configuration was not successful. Refer to the upgrade documentation and execute the required manual steps.
<b>OGIMIGE0028</b>	<b>ERROR: Source server.xml configuration {0} does not exist.</b>
<b>Explanation</b>	The server.xml file could not be migrated because the file does not exist.
<b>Action</b>	Check if the source server.xml file exists and is readable for the user.
<b>OGIMIGE0029</b>	<b>ERROR: Source server.xml configuration {0} is not a file.</b>
<b>Explanation</b>	The server.xml is not a proper file.
<b>Action</b>	Check the server.xml file.
<b>OGIMIGE0030</b>	<b>ERROR: Parsing server.xml file {0}.</b>
<b>Explanation</b>	The server.xml file is not a valid XML file.
<b>Action</b>	Check the server.xml file.
<b>OGIMIGE0031</b>	<b>ERROR: Reading server.xml file {0}.</b>
<b>Explanation</b>	The server.xml file could not be read properly.
<b>Action</b>	Check the server.xml file.
<b>OGIMIGE0032</b>	<b>ERROR: Parser Configuration server.xml file {0}.</b>
<b>Explanation</b>	Parser error occurs when parsing the server.xml file.
<b>Action</b>	Check the server.xml file.

---

<b>OGIMIGE0033</b>	<b>ERROR: Backup file {0}.</b>
<b>Explanation</b>	The file could not be backed up successfully.
<b>Action</b>	Check the source location and target location paths and files.
<b>OGIMIGE0034</b>	<b>ERROR: Reading file {0}.</b>
<b>Explanation</b>	The error occurs because the file could not be read properly.
<b>Action</b>	Check the source location and target location paths,files, and permissions.
<b>OGIMIGE0035</b>	<b>ERROR: Writing file {0}.</b>
<b>Explanation</b>	The error occurs because the file could not be written properly.
<b>Action</b>	Check the source location and target location paths,files, and permissions.
<b>OGIMIGE0036</b>	<b>ERROR: Create/Update file {0}.</b>
<b>Explanation</b>	The error occurs because the file could not be created or updated properly.
<b>Action</b>	Check the source location and target location paths,files, and permissions.
<b>OGIMIGE0042</b>	<b>ERROR: Configuration migration finished with failure(s).</b>
<b>Explanation</b>	Migration failed for the server.xml, web.xml, and config.xml, *.jks files.
<b>Action</b>	Check the detailed error messages displayed by the migration tool.
<b>OGIMIGE0048</b>	<b>ERROR: Cannot identify version of product {0}. The product installation under {1} does not contain any build modules for the current installer platform: {0}</b>
<b>Explanation</b>	The migration application attempted to identify the version of a locally installed product, but the local product is targeting a different installer platform (operating system and architecture) and the product information could not be loaded.
<b>Action</b>	Specify the source version of the product when prompted to.
<b>OGIMIGE0049</b>	<b>ERROR: Cannot parse version of product {0}. The product version of {1} does not have valid syntax. Expecting a version in the format &lt;major&gt;.&lt;minor&gt;.&lt;micro&gt;.&lt;fixnum&gt;.&lt;buildnum&gt;.</b>
<b>Explanation</b>	The migration application attempted to identify the source version of a locally installed product but the product version did not have the expected format.
<b>Action</b>	Specify the source version of the product when prompted to.

<b>OGIMIGE0052</b>	<b>ERROR: User repository file does not exist in the expected location: {0}</b>
<b>Explanation</b>	Migration for common/conf entries was not successful. The users.txt file was not found in the expected location.
<b>Action</b>	Refer to the upgrade documentation and execute the required manual steps.
<b>OGIMIGE0053</b>	<b>ERROR: Error reading user repository file: {0}</b>
<b>Explanation</b>	Migration for common/conf entries was not successful. The users.txt file could not be read from the expected location.
<b>Action</b>	Refer to the upgrade documentation and execute the required manual steps.
<b>OGIMIGE0054</b>	<b>ERROR: User repository file version cannot be retrieved: {0}</b>
<b>Explanation</b>	Migration for common/conf entries was not successful. The users.txt file was not migrated. An unexpected error occurred during the retrieval of the users.txt file version.
<b>Action</b>	Refer to the upgrade documentation and execute the required manual steps.
<b>OGIMIGE0055</b>	<b>ERROR: User repository version is not compatible. Required minimal version is: {0}, found version is: {1}. Manual steps are required.</b>
<b>Explanation</b>	Migration for common/conf entries was not successful. The users.txt file cannot be migrated if the files in both locations are not with compatible versions.
<b>Action</b>	Refer to the upgrade documentation and execute the required manual steps.
<b>OGIMIGE0056</b>	<b>ERROR: User repository version could not be retrieved: {0}</b>
<b>Explanation</b>	Migration for common/conf entries was not successful. An unexpected error occurred during the compatibility check of the users.txt file. The users.txt file must be migrated manually.
<b>Action</b>	Refer to the upgrade documentation and execute the required manual steps.
<b>OGIMIGE0058</b>	<b>ERROR: Source user repository file does not exist: {0}</b>
<b>Explanation</b>	Migration for common/conf entries was not successful. The source user repository file users.txt cannot be found in the specified location.
<b>Action</b>	Refer to the upgrade documentation and execute the required manual steps.

---

<b>OGIMIGE0059</b>	<b>ERROR: Destination user repository file does not exist: {0}</b>
<b>Explanation</b>	Migration for common/conf entries was not successful. The destination user repository file users.txt cannot be found in the specified location.
<b>Action</b>	Refer to the upgrade documentation and execute the required manual steps.
<b>OGIMIGE0060</b>	<b>ERROR: Source user repository file could not be copied to destination.</b>
<b>Explanation</b>	Migration for common/conf entries was not successful. The source user repository file users.txt cannot be copied to destination due to an unexpected error.
<b>Action</b>	Refer to the upgrade documentation and execute the required manual steps.
<b>OGIMIGE0066</b>	<b>ERROR: Missing source SSH configuration file {0}</b>
<b>Explanation</b>	Migration of the SSH configuration was not successful. The source file with the SSH configuration is not found and the migration cannot proceed.
<b>Action</b>	Refer to the upgrade documentation and execute the required manual steps.
<b>OGIMIGE0067</b>	<b>ERROR: Error reading source SSH configuration file {0}</b>
<b>Explanation</b>	Migration of the SSH configuration was not successful. An error occurred while reading the source SSH configuration file and the migration cannot proceed.
<b>Action</b>	Refer to the upgrade documentation and execute the required manual steps.
<b>OGIMIGE0068</b>	<b>ERROR: Missing destination SSH configuration file {0}</b>
<b>Explanation</b>	Migration for SSH configuration was not successful. The destination configuration file for the SSH configuration cannot be found and the migration cannot proceed.
<b>Action</b>	Refer to the upgrade documentation and execute the required manual steps.
<b>OGIMIGE0069</b>	<b>ERROR: Error backing up destination SSH configuration file {0}</b>
<b>Explanation</b>	Migration of the SSH configuration was not successful. An error occurred while trying to backup the original destination SSH configuration file and the migration cannot proceed.
<b>Action</b>	Refer to the upgrade documentation and execute the required manual steps.
<b>OGIMIGE0071</b>	<b>ERROR: Destination SSH config file not found {0}</b>
<b>Explanation</b>	Migration for the SSH configuration was not successful. The destination SSH config file was not found and the migration cannot proceed.
<b>Action</b>	Refer to the upgrade documentation and execute the required manual steps.

<b>OGIMIGE0072</b>	<b>ERROR: Error storing migrated SSH configuration {0}</b>
<b>Explanation</b>	Migration of the SSH configuration was not successful. An error occurred while storing the migrated SSH configuration and the migration cannot proceed.
<b>Action</b>	Refer to the upgrade documentation and execute the required manual steps.
<b>OGIMIGE0073</b>	<b>Invalid source installation directory specified: {0}. No {1} subdirectory is present, this directory is required for the {2} migration to proceed.</b>
<b>Explanation</b>	The migration application requires the specified product subdirectory to be available in the source installation in order to proceed, but the directory was not found. This can happen if the product, for which the migration is executed is not available in the source installation directory.
<b>Action</b>	Make sure that the specified source installation contains the product that is being migrated.
<b>OGIMIGE0081</b>	<b>In file {0} Keystore/Truststore file referenced from HTTPS Connector in attribute {1} that can not be found, creating a valid HTTPS configuration not possible.</b>
<b>Explanation</b>	The server.xml file contains a Keystore/Truststore configuration (keystoreFile=truststoreFile=), pointing to a file that cannot be found. Migrating this would lead in an unusable HTTPS configuration.
<b>Action</b>	In your profile check the file /tomcat/conf/server.xml and the properties keystoreFile="TheKeystoreFilename" truststoreFile="TheTrustStoreFileName". Also check that the file(s) TheKeystoreFilename/TheTrustStoreFileName are existing and valid keystore/truststore files or reference the delivered default one: keystoreFile='C:\SAG32\profiles\CIP\configuration\tomcat\conf\localhost_dont_use_in_production.jks' and start the migration again.
<b>OGIMIGE0083</b>	<b>ERROR: Backup file cannot be created - invalid value for destination file passed.</b>
<b>Explanation</b>	While trying to create a backup of the original file, an invalid original file was passed.
<b>Action</b>	Check the log for more details.
<b>OGIMIGE0084</b>	<b>Cannot identify installer platform for specified installation directory: {0}. Reason: Cannot read installation metadata file: {1}</b>
<b>Explanation</b>	The migration application needs to verify that the source installation is created for the same operating system and architecture as the destination installation. This is done by inspecting the installation metadata located under install/products directory in the installation. If the installation metadata is missing or corrupt, or the process does not have read permissions for the specified file, the platform identification will fail and the migration cannot proceed.
<b>Action</b>	Make sure that the specified installation directory contains proper installation metadata (install/products directory containing installer property files for installed products) and the process has the correct privileges to read it.

---

<b>OGIMIGE0086</b>	<b>Failed to read file "{0}".</b>
<b>Explanation</b>	The platform migration utility could not read the specified file.
<b>Action</b>	Make sure the file exists and the user executing the migration is authorized to read it.
<b>OGIMIGE0087</b>	<b>Failed to close file stream "{0}".</b>
<b>Explanation</b>	An I/O error occurred while closing the file stream.
<b>Action</b>	Make sure the file exists and the user executing the migration is authorized to read it.
<b>OGIMIGE0089</b>	<b>An invalid path property "{0}" was found in file "{1}". Path should not be null or empty.</b>
<b>Explanation</b>	A path property sent for transformation has a null or empty value. Transformation cannot proceed with an invalid argument.
<b>Action</b>	Ensure that the property referenced in the given file has a valid path value.
<b>OGIMIGE0092</b>	<b>The path "{0}" is referenced in file "{1}"; it should be available as "{2}", but could not be found. Hence the path cannot be migrated.</b>
<b>Explanation</b>	The path transformer has discovered that a path referenced in a file in the source installation points to a file inside the source installation. The file does not exist and the configuration is invalid.
<b>Action</b>	Ensure that the path referenced in the specified file points to a valid file on the file system.
<b>OGIMIGE0095</b>	<b>The absolute path "{0}" referenced in file "{1}" does not exist on the file system.</b>
<b>Explanation</b>	The path transformer has discovered that a path referenced in a file in the source installation points to a file outside the source installation. The file does not exist and the configuration is invalid.
<b>Action</b>	Ensure that the path referenced in the specified file points to a valid file on the file system.
<b>OGIMIGE0097</b>	<b>Could not determine original installation location for "{0}".</b>
<b>Explanation</b>	The path transformer failed to determine the original source installation root directory, which is required in order for the transformer to function properly.
<b>Action</b>	Make sure the migration source directory contains a "profiles" folder with at least one valid profile inside.

**OGIMIGE0098**      **The original source directory "{0}" exists on this file system but the current migration is using "{1}" as a source. Path transformation is not supported.**

**Explanation**      Path transformer determined that the migration source directory is different from the original source installation root directory (which could be the case when you are migrating from a zip file or from a mapped/mounted directory). However, the original source installation root directory exists on this file system but it is not used as a migration source directory. This is not a supported path transformation scenario as the system may not reliably validate the transformed paths.

**Action**            If the original source installation directory is available on the same file system it should be used directly as a migration source directory.

**OGIMIGE0099**      **The target directory "{0}" must be the same as the installation root directory "{1}".**

**Explanation**      The target directory in the migrated profile config.ini file is different from the migration target directory. The target installation is corrupted.

**Action**            Make sure that the migration target directory is not moved or tampered with.

**OGIMIGE0102**      **Failed to copy transformed file path from "{0}" to "{1}".**

**Explanation**      Path transformer transformed a file path from the migration source directory to the migration target directory. The file copy operation failed.

**Action**            Make sure that the user executing the migration is able to physically copy the source file to the destination.

**OGIMIGE0103**      **An invalid URL property "{0}" was found in file "{1}". URL should not be null or empty.**

**Explanation**      A URL property sent for transformation has a null or empty value. Transformation cannot proceed with an invalid argument.

**Action**            Ensure that the property referenced in the given file has a valid URL value.

**OGIMIGE0107**      **Source installation directory ({0}) uses "{1}" platform, while destination installation directory ({2}) uses "{3}".**

**Explanation**      The migration cannot proceed if the source and destination installation platforms are different.

**Action**            Make sure the source and destination directories contain installations of one and the same platform.

---

<b>OGIMIGE0111</b>	<b>ERROR: copy file{0}.</b>
<b>Explanation</b>	Copy file operation failed.
<b>Action</b>	Make sure the file exists and is not used or opened by an application.
<b>OGIMIGE0113</b>	<b>Error occurred while merging the properties from '{0}' to '{1}'.</b>
<b>Explanation</b>	Merging the .properties files failed with an error.
<b>Action</b>	Check the logs for more information.
<b>OGIMIGE0115</b>	<b>ERROR: Error during finalization of the JAAS configuration.</b>
<b>Explanation</b>	An error occurred while finalizing the migrated JAAS configuration and the migration could not proceed.
<b>Action</b>	Contact Software AG Global support.
<b>OGIMIGE0116</b>	<b>Abort migration due to errors while evaluating source installation {0}</b>
<b>Explanation</b>	Migration of roles.txt entries was not successful due to problems with the source SAG product installation.
<b>Action</b>	Refer to the upgrade documentation and execute the required manual steps.
<b>OGIMIGE0117</b>	<b>Abort migration due to errors while evaluating destination installation {0}</b>
<b>Explanation</b>	Migration of roles.txt entries was not successful due to problems with the source SAG product installation.
<b>Action</b>	Refer to the upgrade documentation and execute the required manual steps.
<b>OGIMIGE0118</b>	<b>Error while reading source 'roles.txt': {0}</b>
<b>Explanation</b>	Unexpected error occurred while reading the 'roles.txt' file from the source SAG product installation.
<b>Action</b>	Refer to the upgrade documentation and execute the required manual steps.
<b>OGIMIGE0119</b>	<b>Error while reading destination 'roles.txt': {0}</b>
<b>Explanation</b>	Unexpected error occurred while reading the 'roles.txt' file from the destination SAG product installation.
<b>Action</b>	Refer to the upgrade documentation and execute the required manual steps.

<b>OGIMIGE0121</b>	<b>Cannot backup {0}. Migration is not safe. Proceeding with next migration.</b>
<b>Explanation</b>	Cannot create backup copy of the 'roles.txt' file. Migration might be successful but if it fails the previous content of the 'roles.txt' file can't be restored. Therefore, we skip the migration for this particular 'roles.txt' file.
<b>Action</b>	Refer to the upgrade documentation and execute the required manual steps.
<b>OGIMIGE0122</b>	<b>Error while merging {0} and {1}</b>
<b>Explanation</b>	Unexpected error occurred while merging the content of source and destination installation 'roles.txt' files. The current migration will be skipped and the original 'roles.txt' content will be restored.
<b>Action</b>	Refer to the upgrade documentation and execute the required manual steps.
<b>OGIMIGE0123</b>	<b>'config.ini' doesn't exist or is not file: {0}</b>
<b>Explanation</b>	Cannot proceed with the migration since the required configuration file 'config.ini' doesn't exist.
<b>Action</b>	Refer to the upgrade documentation and execute the required manual steps.
<b>OGIMIGE0126</b>	<b>Configuration location {0} doesn't exist or is not file.</b>
<b>Explanation</b>	The specified configuration location doesn't exist and therefore the migration process will be skipped.
<b>Action</b>	Refer to the upgrade documentation and execute the required manual steps.
<b>OGIMIGE0127</b>	<b>Configuration location {0} does not exist.</b>
<b>Explanation</b>	The specified configuration location doesn't exist and therefore the migration process will be skipped.
<b>Action</b>	Refer to the upgrade documentation and execute the required manual steps.
<b>OGIMIGE0128</b>	<b>Configuration location {0} is not a file.</b>
<b>Explanation</b>	The specified configuration location doesn't exist and therefore the migration process will be skipped.
<b>Action</b>	Refer to the upgrade documentation and execute the required manual steps.

---

<b>OGIMIGE0129</b>	<b>Cannot create backup file: {0}</b>
<b>Explanation</b>	The migration is not able to create a backup file for the JAAS configuration.
<b>Action</b>	Check the source location and target location paths, files, and permissions.
<b>OGIMIGE0130</b>	<b>This is not a valid destination backup file location: null</b>
<b>Explanation</b>	Missing destination backup file location.
<b>Action</b>	Check the source location and target location paths, files, and permissions.
<b>OGIMIGE0131</b>	<b>The destination backup file location '{0}' does not exist</b>
<b>Explanation</b>	The destination backup file location does not exist.
<b>Action</b>	Check the source location and target location paths, files, and permissions.
<b>OGIMIGE0134</b>	<b>JKS '{0}' with file {1} is missing mandatory property for password from the configuration file.</b>
<b>Explanation</b>	If truststoreFile property is present in configuration there should be truststorePass property. The same rule applies for keystoreFile and keystorePass.
<b>Action</b>	Check the properties of HTTPS connectors.
<b>OGIMIGE0135</b>	<b>The backup of '{0}' failed.</b>
<b>Explanation</b>	The problem might be that the pointed file cannot be copied or deleted after backup.
<b>Action</b>	Check for permissions on the file.
<b>OGIMIGE0136</b>	<b>The migration of key/certificates from '{0}' to '{1}' failed.</b>
<b>Explanation</b>	The migration of certificates and/or keys is failing for the pointed Java Key Stores. The following keystores are migrated as a part of the HTTPS configuration migration.
<b>Action</b>	Check if property files are pointing to the correct locations of trustore and keystore in the source installation. Check if password given in the configuration is correct. Check if the given configuration is actually operational.
<b>OGIMIGE0133</b>	<b>This login context is skipped by migration, because it contained SSX login module, but In version 10.x SSX is no longer available and migration is not possible</b>

<b>OGIMIGW0005</b>	<b>WARNING: File could not be deleted - {0}.</b>
<b>Explanation</b>	An error occurred while deleting incompatible destination file. This is a warning message because deleting this file should not be crucial for the functionality of the application.
<b>Action</b>	Delete this file manually as it may cause future conflicts.
<b>OGIMIGW0008</b>	<b>WARNING: Referenced file was found in the source installation but was not found in the destination installation: "{0}" . Check if the file was migrated and if not migrate it manually.</b>
<b>Explanation</b>	Configurations could have properties with values that contain paths to files. During migration these paths could become invalid. To prevent the migration of such paths that make the configurations unusable, a check is done if the file exists in the new installation. This warning shows that the file was successfully located in the source installation, but was missing from the destination.
<b>Action</b>	Check if the path from the configuration is valid after the migration. If the path is not valid, migrate the file manually and edit the path if needed.
<b>OGIMIGW0009</b>	<b>WARNING: Referenced file was not found in the destination system: "{0}"</b>
<b>Explanation</b>	Configurations could have properties with values that contain paths to files. During migration these paths could become invalid. To prevent the migration of such paths that make the configurations unusable, a check is done if the file exists in the new installation.
<b>Action</b>	Check if the path from the configuration is valid after the migration. If the path is not valid, migrate the file manually and edit the path if needed.
<b>OGIMIGW0011</b>	<b>WARNING: Property value could not be transformed properly.</b>
<b>Explanation</b>	When a migration is done, some properties require special transformation for their values. For this reason special transformer classes are used. This message is shown when there is a problem with finding the class, the class could not be instantiated or the class is not a valid Transformer class. This could lead to invalid property values.
<b>Action</b>	Check the value of the migrated property.
<b>OGIMIGW0012</b>	<b>WARNING: Installer client jar not available, falling back on custom installer metadata parser.</b>
<b>Explanation</b>	Migration framework did not find a required jar for reading the installation metadata, it will attempt to read the metadata by parsing the prop file instead.
<b>Action</b>	No action is required.

---

<b>OGIMIGW0016</b>	<b>WARNING: Properties for transformation were not loaded.This might make your configuration unusable.</b>
<b>Explanation</b>	We are using special files that map properties which need some kind of transformation for their value or key. In order to use them we have to load them from a file. This step has failed.
<b>Action</b>	Contact Software AG global support.
<b>OGIMIGW0017</b>	<b>WARNING: Transformer class was not found for the following property:</b>
<b>Explanation</b>	We allow custom property transformation which is done via a class. The loading of this class has failed. One or more properties were not transformed correctly.
<b>Action</b>	Contact Software AG global support.
<b>OGIMIGW0027</b>	<b>WARNING: Some runtime componets were not enabled in the source configuration - {0}. Migration exits successfully.</b>
<b>Explanation</b>	Some runtime componets like JMX, SSH are not enabled in the source configuration. The migartion will not migrate any data from these source configurations.
<b>Action</b>	If you want to disable the component explicitly please do so by changing the port property in the connector in the destination installation.
<b>OGIMIGW0037</b>	<b>WARNING: Error on read file {0}.</b>
<b>Explanation</b>	The error occurs because the file could not be read properly.
<b>Action</b>	Check the source location and target location paths,files, and permissions.
<b>OGIMIGW0038</b>	<b>WARNING: Error on write file {0}.</b>
<b>Explanation</b>	The error occurs because the file could not be written properly.
<b>Action</b>	Check the source location and target location paths,files, and permissions.
<b>OGIMIGW0051</b>	<b>WARNING: Using the default 'localhost_dont_use_in_production.jks' file in file {0} property name {1}, because the file referenced in the older version could not be found. Change the file specified in the property.</b>
<b>Explanation</b>	The specified property in the specified properties file points to the default .jks keystore file, because the keystore file referenced in the older version could not be found.
<b>Action</b>	Change the property to point to a valid existing production .jks keystore file.

<b>OGIMIGW0065</b>	<b>WARNING: SSH port is not set in source configuration {0}. Migration exits successfully.</b>
<b>Explanation</b>	SSH port is not set in source configuration so there is nothing to migrate.
<b>Action</b>	SSH port is not set in configuration and nothing is done. If this is not the case, refer to the upgrade documentation and execute the required manual steps.
<b>OGIMIGW0104</b>	<b>Value for JAAS configuration in config.ini could not be processed.</b>
<b>Explanation</b>	The JAAS configuration modifications will be made to the original JAAS configuration located in the profile folder.
<b>Action</b>	Define an absolute path to the current location of the JAAS configuration to be migrated or move it in the profile configuration folder.
<b>OGIMIGW0108</b>	<b>WARNING: source internal user repository file users.txt not present : "{0}" Skip the migration of users.txt; groups.txt, roles.txt.</b>
<b>Explanation</b>	The users.txt internal user repository file is not present in common/conf directory. The file(s) could not be migrated.
<b>Action</b>	Check the profiles/TheProfile/configuration/jaas.config for the following entry: internalRepository="ADirectory/users.txt" and check if this is migrated by the jaas config migration. Do the same for the groups.txt and roles.txt files. If there is no such entry, a migration of that file is not necessary, because no internal user repository for authentication is enabled or configured.
<b>OGIMIGW0112</b>	<b>WARNING: security configuration source file scPassMan.config.xml missing. File is mandatory! Skipping migration of all passman files.</b>
<b>Explanation</b>	Passman security configuration files are normally 3 files : scPassMan.config.xml ; defaultPassStore.dat and mpw.dat . The .dat files are optional, but the .xml is important and without it migration cannot be done.
<b>Action</b>	Check whether the scPassMan.config.xml file is present in the following location: installdir/profiles/TheProfile/configuration/security. With the xml file present, retry migration or migrate manually.
<b>OGIMIGW0132</b>	<b>Found SSX login module {2} in source {0}. SSX is removed in 10.0, so login context {1} will not be migrated.</b>
<b>Explanation</b>	SSX login module is found in source installation, but SSX is removed in version 10.0, so we can't migrate it properly
<b>Action</b>	Migrate login context by hand as it is not possible not migrate it automatically.

# 21 Platform Manager Messages

---

<b>SPMADME0000</b>	<b>Administration SPI for "{0}" and namespace "{1}" not found.</b>
<b>Explanation</b>	The Administration SPI for the specified entity and namespace should be registered beforehand.
<b>Action</b>	Check if the correct entity ID and namespace are provided or if the product plug-in is available.
<b>SPMADME0001</b>	<b>Error while invoking "{0}" Administration function with arguments "{2},{3}" of "{1}" and namespace "{4}".</b>
<b>Explanation</b>	The specified administration function is either not available, the arguments used to invoke the function are incorrect, or unchecked exception has been thrown.
<b>Action</b>	Check the functions supported by the Administration SPI.
<b>SPMADME0002</b>	<b>Administration function "{0}" with arguments "{2},{3}" of "{1}" and namespace "{4}" not found.</b>
<b>Explanation</b>	The specified administration function is not defined for the entity with the specified arguments.
<b>Action</b>	Check the functions supported by the Administration SPI.
<b>SPMADME0003</b>	<b>{0} process finished with error code {1}. Requested command: {2} Output: {3}</b>
<b>Explanation</b>	The requested command could not be executed successfully.
<b>Action</b>	Check the upgrade and migration help for the product.

**SPMCCPEMIE0001 An error occurred during a call to wm.monitor.util:configSettings. The error reported is: {}.**

**Explanation** An error occurred during the service call to write the configuration settings to WmMonitor. A probable cause for the error is failing to access the IntegrationServer\packages\WmMonitor\config\monitor.cnf file. The error could also occur when the monitor.cnf file is not present initially and the service call to write the configuration settings creates and populates the file with default values.

**Action** Ensure that the IntegrationServer\packages\WmMonitor\config\monitor.cnf file is present, contains name=value pairs, and the name=value pairs are valid. Also, ensure that the name-value pairs are acceptable for your configuration.

**SPMCCPEMIE0002 Only BASIC authentication is supported.**

**Explanation** The specified authentication is not supported.

**Action** Change authentication to BASIC.

**SPMCCPEMIE0003 The My webMethods Server URL is not valid.**

**Explanation** The URL for pingging My webMethods Server is not valid.

**Action** Check that your WmMonitor configuration values for host, port, username and password are valid.

**SPMCCPEMIE0009 No My webMethods Server credentials were provided.**

**Explanation** The connection to My webMethods Server cannot be validated without proper credentials.

**Action** Specify values for username and password.

**SPMCCPEMIE0014 The My webMethods Server host, port, and/or connection protocol were not provided.**

**Explanation** You must specify values for the My webMethods Server host, port, and connection protocol.

**Action** Specify values for host, port, and connection protocol.

**SPMCCPEMIE0015 The values are required.**

**Explanation** You must specify values in the fields.

**Action** Specify values for these fields.

**SPMCCPEMIW0000 My webMethods Server password was not provided.**

**Explanation** The password is a required field.

**Action** Provide a password for My webMethods Server.

**SPMCCPEMIW0004 The My webMethods Server URL is not accessible. Click Show Details for more information.**

**Explanation** The URL for pinging My webMethods Server is not accessible.

**Action** Check that your WmMonitor configuration values for host, port, username and password are valid, and also confirm that My webMethods Server is reachable on the network.

**SPMCCPEMIW0005 My webMethods Server credentials are not valid.**

**Explanation** The username or password are incorrect.

**Action** Check that the username and password are correct.

**SPMCCPEMIW0011 The password is required.**

**Explanation** You must specify a password.

**Action** Specify a password.

**SPMCCPEMIW0012 No value was provided for 'Data Level Security Administrator'**

**Explanation** A value for the Data Level Security, DLS, super user was not provided.

**Action** No action is required if the default value of '\Administrator\' is acceptable.

**SPMCCPEMIW0013 A default value of 'Administrator' was provided; it will be displayed upon Save.**

**Explanation** Because no value was provided for the Data Level Security super user, the default value of '\Administrator\' is used.

**Action** Set a value for Data Level Security Administrator.

**SPMCFCE0012 Properties serializer supports only instances of java.util.Properties**

**Explanation** The user is trying to use a Properties serializer on an inappropriate object type.

**Action** Use proper serializer for your object.

<b>SPMCFCE0023</b>	<b>There is no registered ConfigurationSerializer under runtimeComponentId {0} and configurationTypeId {1}</b>
<b>Explanation</b>	No registered ConfigurationSerializer exists under the entered runtimeComponentId and configurationTypeId.
<b>Action</b>	Register a ConfigurationSerializer under the entered runtimeComponentId and configurationTypeId.
<b>SPMCFCE0026</b>	<b>ConfigurationManager should be registered with the runtimeComponentId and configurationTypeId properties.</b>
<b>Explanation</b>	ConfigurationManager should be registered with the runtimeComponentId and configurationTypeId properties. They cannot be null.
<b>Action</b>	Register ConfigurationManager and set values for the runtimeComponentId and configurationTypeId properties.
<b>SPMCFCE0030</b>	<b>Error occurred during serialization/deserialization.</b>
<b>Explanation</b>	Error occurred during serialization/deserialization.
<b>Action</b>	Check for user permissions and hardware failures and try again.
<b>SPMCFCE0048</b>	<b>ConfigurationSerializer SPI could not be found for RuntimeComponentId "{0}" and ConfigurationTypeId "{1}" .</b>
<b>Explanation</b>	Platform Manager could not find a registered ConfigurationSerializer that can handle ConfigurationInstances with these properties.
<b>Action</b>	Register a ConfigurationSerializer SPI implementation that can handle ConfigurationInstances with these properties.
<b>SPMCFCE0049</b>	<b>Configuration is not available for this component.</b>
<b>Explanation</b>	The component requires a configuration to function properly.
<b>Action</b>	Set the configuration for this component.
<b>SPMCFCI0000</b>	<b>Port Settings</b>
<b>Explanation</b>	PortSettingsConfigurationType Display Name
<b>Action</b>	None.

---

<b>SPMCFCI0001</b>	<b>Listener ports configuration</b>
<b>Explanation</b>	PortSettingsConfigurationType description.
<b>Action</b>	None.
<b>SPMCFCI0019</b>	<b>The keystore truststore settings cannot be null.</b>
<b>Explanation</b>	The keystore truststore settings cannot be set to null.
<b>Action</b>	Provide a valid keystore truststore setting.
<b>SPMCFCI0028</b>	<b>There can be only one primary pool defined in the JDBC configuration.</b>
<b>Explanation</b>	There can be only one primary pool defined in the JDBC configuration.
<b>Action</b>	Specify only one pool with the primary as true.
<b>SPMCFGE0000</b>	<b>The configuration type argument is not set.</b>
<b>Explanation</b>	The configuration type argument is not set.
<b>Action</b>	Set the configuration type argument.
<b>SPMCFGE0001</b>	<b>Configuration type {0} cannot be found.</b>
<b>Explanation</b>	A Configuration Manager that can handle configuration type {0} cannot be found.
<b>Action</b>	Make sure that configuration type {0} is supported, for example check if there is a Configuration Manager registered for it.
<b>SPMCFGE0002</b>	<b>A Configuration instance with ID = {0} does not exist.</b>
<b>Explanation</b>	A Configuration instance with the provided ID does not exist.
<b>Action</b>	Use the ID of an existing Configuration instance.
<b>SPMCFGE0003</b>	<b>Loaded configuration cannot be null.</b>
<b>Explanation</b>	The requested configuration cannot be null.
<b>Action</b>	Provide valid runtimeComponent, configurationInstance, and configurationStatus.
<b>SPMCFGE0004</b>	<b>The Configuration Manager Service is not set.</b>
<b>Explanation</b>	The Configuration Manager Service is not set.
<b>Action</b>	Set the Configuration Manager Service.

<b>SPMCFGE0005</b>	<b>The component ID or configurationType ID is wrong.</b>
<b>Explanation</b>	The component ID or configurationType argument ID is wrong.
<b>Action</b>	Use an appropriate component ID or configurationType ID.
<b>SPMCFGE0006</b>	<b>Configuration is not available for this component.</b>
<b>Explanation</b>	This component needs configuration in order to function.
<b>Action</b>	Set the configuration for this component.
<b>SPMCFGE0007</b>	<b>ConfigurationSerializer SPI could not be found for RuntimeComponentId "{0}" and ConfigurationTypeId "{1}" .</b>
<b>Explanation</b>	Platform Manager did not find registered ConfigurationSerializer that can handle ConfigurationInstances with these properties.
<b>Action</b>	Register ConfigurationSerializer SPI implementation that can handle ConfigurationInstances with these properties.
<b>SPMCFGE0008</b>	<b>Id cannot be null.</b>
<b>Explanation</b>	When creating a configuration instance, the id argument cannot be null.
<b>Action</b>	Provide a non-null id argument.
<b>SPMCFGE0009</b>	<b>ConfigurationTypeId cannot be null.</b>
<b>Explanation</b>	When creating a configuration instance, the ConfigurationTypeId argument cannot be null.
<b>Action</b>	Provide a non-null id argument.
<b>SPMCFGE0010</b>	<b>DisplayName cannot be null.</b>
<b>Explanation</b>	When creating a configuration instance, the displayName argument cannot be null.
<b>Action</b>	Provide a non-null id argument.
<b>SPMCFGE0011</b>	<b>The component to be updated is null.</b>
<b>Explanation</b>	The runtime component to be updated cannot be null.
<b>Action</b>	Provide a non-null runtime component.

---

<b>SPMCFGE0012</b>	<b>Protocol value cannot be changed.</b>
<b>Explanation</b>	The protocol value for an existing port configuration cannot be changed.
<b>Action</b>	Retry the operation without changing the protocol.
<b>SPMCFGE0013</b>	<b>Create command is not supported.</b>
<b>Explanation</b>	Create configuration command is not supported by this configuration manager.
<b>Action</b>	Check the logs.
<b>SPMCFGE0020</b>	<b>ConfigurationService is not set.</b>
<b>Explanation</b>	ConfigurationService is not set.
<b>Action</b>	Register a ConfigurationService.
<b>SPMCFGE0021</b>	<b>New configuration is null.</b>
<b>Explanation</b>	The configuration sent for validation is null.
<b>Action</b>	Send a valid configuration that is not null.
<b>SPMCFGE0022</b>	<b>Delete command is not supported</b>
<b>Explanation</b>	Delete configuration command is not supported by this configuration manager.
<b>Action</b>	Check the logs.
<b>SPMCFGE0023</b>	<b>The new configuration to be validated can not be null.</b>
<b>Explanation</b>	The new configuration to be validated can not be null.
<b>Action</b>	Send a valid configuration that is not null for validation.
<b>SPMCFGE0024</b>	<b>Duplicate truststore aliases in the existing instances.</b>
<b>Explanation</b>	Duplicate truststore aliases are present in the existing instances.
<b>Action</b>	Use a unique truststore alias.
<b>SPMCFGE0025</b>	<b>Duplicate truststore aliases are present in the existing instances.</b>
<b>Explanation</b>	Duplicate truststore aliases are present in the existing instances.
<b>Action</b>	Use a unique truststore alias.

<b>SPMCFGE0026</b>	<b>Duplicate keystore aliases in existing instances.</b>
<b>Explanation</b>	Duplicate keystore alias is present in the existing instances.
<b>Action</b>	Use a unique keystore alias.
<b>SPMCFGE0027</b>	<b>Duplicate keystore alias is present in existing instances.</b>
<b>Explanation</b>	Duplicate keystore alias is present in the existing instances.
<b>Action</b>	Use a unique keystore alias.
<b>SPMCFGE0028</b>	<b>The file location provided in the keystore could not be found.</b>
<b>Explanation</b>	The file location provided in the keystore could not be found.
<b>Action</b>	The file location provided in the keystore configuration must point to an existing file. Use an existing file location.
<b>SPMCFGE0040</b>	<b>The keystore location information is missing.</b>
<b>Explanation</b>	The keystore location information is missing in the new configuration.
<b>Action</b>	Use a valid keystore location that points to an existing file.
<b>SPMCFGE0041</b>	<b>The keystore location information is either null or empty. It should point to an existing file.</b>
<b>Explanation</b>	The keystore location information is either null or empty. It should point to an existing file.
<b>Action</b>	The keystore location should point to an existing file.
<b>SPMCFGE0042</b>	<b>An exception occurred when trying to get the existing aliases.</b>
<b>Explanation</b>	The PlatformManagerException exception occurred when trying to get the existing aliases.
<b>Action</b>	You need to correct the existing configuration instances with valid aliases.
<b>SPMCFGE0043</b>	<b>An exception occurred when trying to get the existing aliases.</b>
<b>Explanation</b>	The IOException exception occurred when trying to get the existing aliases.
<b>Action</b>	Provide a valid runtime ID and configuration type ID to the validator.

---

<b>SPMCFGE0049</b>	<b>Configuration of type Common-JDBC is null.</b>
<b>Explanation</b>	Configuration object for Common-JDBC is null.
<b>Action</b>	Specify the valid configuration object for Common-JDBC.
<b>SPMCFGE0051</b>	<b>Duplicate alias for Jdbc Pool is found.</b>
<b>Explanation</b>	Alias for Jdbc Pool is not unique. This is not a valid configuration.
<b>Action</b>	Specify a unique Jdbc Pool alias.
<b>SPMCFGE0053</b>	<b>There can be only one pool with primary as true.</b>
<b>Explanation</b>	There is more than one pool defined as primary. This is not valid.
<b>Action</b>	Specify only one pool with primary as true.
<b>SPMCFGE0055</b>	<b>JDBC Pool information is not available. Specify valid JDBC Pool Settings.</b>
<b>Explanation</b>	JDBC Pool information is not available in the JDBC Settings Configuration Object. This is not valid.
<b>Action</b>	Specify valid JDBC Pool Settings.
<b>SPMCFGE0058</b>	<b>An exception occurred when trying to get the existing aliases.</b>
<b>Explanation</b>	The PlatformManagerException exception occurred when trying to get the existing aliases.
<b>Action</b>	You need to correct the existing configuration instances with valid JDBC pool aliases.
<b>SPMCFGE0059</b>	<b>The JDBC connection failed.</b>
<b>Explanation</b>	The JDBC connection failed because it was invalid.
<b>Action</b>	Specify valid JDBC connection data.
<b>SPMCFGE0060</b>	<b>Failed to close a valid JDBC connection.</b>
<b>Explanation</b>	Failed to close a valid JDBC connection.
<b>Action</b>	Contact your system administrator.
<b>SPMCFGE0061</b>	<b>Password verification failed.</b>
<b>Explanation</b>	The password provided to load the certificate is incorrect.
<b>Action</b>	You need to provide a valid password and try again.

<b>SPMCFGE0065</b>	<b>Configuration Instance "{0}" does not exist.</b>
<b>Explanation</b>	Configuration Instances should be backed up by existing source.
<b>Action</b>	Make sure this particular Configuration Instance is declared correctly.
<b>SPMCFGE0066</b>	<b>Configuration Instance "{0}" is not a valid URL.</b>
<b>Explanation</b>	Configuration Instance "{0}" should be backed up by valid URL source.
<b>Action</b>	Make sure this particular Configuration Instance is declared correctly.
<b>SPMCFGE0067</b>	<b>Unknown property name "{0}".</b>
<b>Explanation</b>	The property is not recognized.
<b>Action</b>	Make sure this particular Configuration Instance is declared correctly.
<b>SPMCFGE0068</b>	<b>The specified port number is already in use. The port number is bound to an application outside the current installation of Software AG Suite of products.</b>
<b>Explanation</b>	The specified port number is already in use. The port number is bound to an application outside the current installation of Software AG Suite of products.
<b>Action</b>	Specify a different port number or shut down the component that is running on this port.
<b>SPMCFGE0071</b>	<b>The value {0} cannot be used. A non-negative number is expected.</b>
<b>Explanation</b>	The specified value must not be a negative number.
<b>Action</b>	Specify a non-negative number.
<b>SPMCFGE0073</b>	<b>The value of the Threadpool Min parameter cannot be equal to or more than the value for the Threadpool Max parameter.</b>
<b>Explanation</b>	The value of the Threadpool Min parameter cannot be equal to or more than the value of the Threadpool Max parameter.
<b>Action</b>	Change the configuration to make the value of the Threadpool Max parameter more than the value of the Threadpool Min parameter.
<b>SPMCFGE0078</b>	<b>The configuration contains duplicate log file name entries.</b>
<b>Explanation</b>	Duplicate log file names exist in the log configuration appendices.
<b>Action</b>	Make sure each log file name in the log configuration is unique.

---

<b>SPMCFGE0079</b>	<b>Log file name {0} already exists.</b>
<b>Explanation</b>	The specified log file name exists in another runtime component's log configuration.
<b>Action</b>	Make sure each file name is unique across runtime components.
<b>SPMCFGE0080</b>	<b>Not enough disk space.</b>
<b>Explanation</b>	The disk partition free space is less than 10Mb.
<b>Action</b>	Make sure the disk partition has enough free space.
<b>SPMCFGE0081</b>	<b>The user does not have privileges to perform file operations. Check the current security policy.</b>
<b>Explanation</b>	The user performing the file operation does not have the proper privileges necessary to create or write to a log file.
<b>Action</b>	Make sure the user has adequate privileges to perform the operation.
<b>SPMCFGE0082</b>	<b>Error creating temp file in {0}. Make sure the specified directory is valid.</b>
<b>Explanation</b>	The log configuration validation failed because the specified log directory is not valid or does not exist.
<b>Action</b>	Make sure the specified log directory is valid.
<b>SPMCFGE0084</b>	<b>The "from" or "to" email address is not correct.</b>
<b>Explanation</b>	In Platform Manager, during validation of sending a test email, if the "from" or "to" email address is not correct, this error is thrown.
<b>Action</b>	Ensure that the "from" or "to" email address is correct, and try again.
<b>SPMCFGE0086</b>	<b>Not able to connect to the SMTP server {0}.</b>
<b>Explanation</b>	In Platform Manager, the socket connection is not able to connect to the SMTP server with the given credentials.
<b>Action</b>	Ensure the server is running and the specified credentials are correct.
<b>SPMCFGE0088</b>	<b>Unable to send a test mail to the recipient {1} using the SMTP server {0}.</b>
<b>Explanation</b>	In Platform Manager, an error occurs when sending an email to the recipient.
<b>Action</b>	The email ID is non-existent. Enter a valid email ID and try again.

<b>SPMCFGE0090</b>	<b>An exception occurred when trying to get the existing aliases.</b>
<b>Explanation</b>	The IOException exception occurred when trying to get the existing aliases.
<b>Action</b>	Provide a valid runtime ID and configuration type ID to the validator.
<b>SPMCFGE0091</b>	<b>An exception occurred when trying to get the existing JDBC pools defined as primary.</b>
<b>Explanation</b>	The PlatformManagerException exception occurred when trying to get the existing JDBC pools defined as primary.
<b>Action</b>	You need to correct the existing configuration instances with only one JDBC pool as primary.
<b>SPMCFGE0092</b>	<b>An exception occurred when trying to get the existing JDBC pools defined as primary.</b>
<b>Explanation</b>	The IOException exception occurred when trying to get the existing JDBC pools defined as primary.
<b>Action</b>	Provide a valid runtime ID and configuration type ID to the validator.
<b>SPMCFGE0093</b>	<b>No value was specified for the Protocol parameter.</b>
<b>Explanation</b>	No value was specified for the Protocol parameter.
<b>Action</b>	Specify a value for the Protocol parameter.
<b>SPMCFGE0094</b>	<b>The keystore truststore setting is empty.</b>
<b>Explanation</b>	The keystore truststore setting does not contain any fields.
<b>Action</b>	Provide either the keystore, truststore or extended properties.
<b>SPMCFGE0095</b>	<b>The keystore truststore setting does not contain any element.</b>
<b>Explanation</b>	The keystore truststore setting should either have the keystore, the truststore, or the extended properties, which is missing.
<b>Action</b>	Add the keystore, the truststore, or the extended properties to the keystore truststore setting.
<b>SPMCFGE0096</b>	<b>There can be only one primary pool defined in the JDBC configuration.</b>
<b>Explanation</b>	There can be only one primary pool defined in the JDBC configuration.
<b>Action</b>	Specify only one pool with the primary as true.

---

<b>SPMCFGE0097</b>	<b>The JDBC Pool name is not unique.</b>
<b>Explanation</b>	The JDBC Pool name is not unique.
<b>Action</b>	Specify a unique JDBC Pool name.
<b>SPMCFGE0098</b>	<b>The JDBC driver class should not be null when the database server type is Custom.</b>
<b>Explanation</b>	The JDBC driver class should not be null when the database server type is Custom.
<b>Action</b>	Specify the JDBC Driver class if the database server type is Custom.
<b>SPMCFGE0099</b>	<b>The database server host should not be null when the database server type is non-custom and the URL is not specified.</b>
<b>Explanation</b>	The database server host should not be null when the database server type is non-custom and the URL is not specified.
<b>Action</b>	Specify the hostname for the database server when the server type is non-custom and the database URL is not specified.
<b>SPMCFGE0100</b>	<b>The database server port number should not be null when the database server type is non-custom and the URL is not specified.</b>
<b>Explanation</b>	The database server port number should not be null when the database server type is non-custom and the URL is not specified.
<b>Action</b>	Specify the port number for the database server when the server type is non-custom and the database URL is not specified.
<b>SPMCFGE0101</b>	<b>The database server SID should not be null when the database server type is Oracle and the URL is not specified.</b>
<b>Explanation</b>	The database server SID should not be null when the database server type is Oracle and the URL is not specified.
<b>Action</b>	Specify the Oracle SID when the database server type is Oracle and the database URL is not specified.
<b>SPMCFGE0102</b>	<b>The database server's database name should not be null when the database server type is non-Oracle and the URL is not specified.</b>
<b>Explanation</b>	The database server's database name should not be null when the database server type is non-Oracle and the URL is not specified.
<b>Action</b>	Specify the database name when the database server type is non-Oracle and the URL is not specified.

<b>SPMCFGE0103</b>	<b>An error occurred while getting either the runtime components or configuration instances using the configuration or inventory service.</b>
<b>Explanation</b>	An error occurred while getting either the runtime components or configuration instances using the configuration or inventory service.
<b>Action</b>	Retry the action.
<b>SPMCFGE0105</b>	<b>Configuration instance and its configuration manager must have the same configuration type.</b>
<b>Explanation</b>	Configuration instance and its configuration manager must have the same configuration type.
<b>Action</b>	Check the type of the provided configuration instance.
<b>SPMCFGE0106</b>	<b>Not able to connect to the SMTP server(s) {0} with the given credentials and also not able to send a test mail to the recipient using the SMTP server(s) {1}.</b>
<b>Explanation</b>	In Platform Manager, the socket connection is not able to connect to the SMTP server with the given credentials (if provided). Also, a test mail to the recipient using the SMTP server is also not sent.
<b>Action</b>	Ensure the server is running and the server credentials entered are correct. Also, enter the correct email address and try again.
<b>SPMCFGE0109</b>	<b>The license file can not be empty.</b>
<b>Explanation</b>	In Platform Manager, when an empty license file is uploaded, this message is seen.
<b>Action</b>	You need to ensure to upload a license file that is not empty.
<b>SPMCFGE0110</b>	<b>The truststore location information is missing.</b>
<b>Explanation</b>	The truststore location information is missing in the new configuration.
<b>Action</b>	Use a valid truststore location that points to an existing file.
<b>SPMCFGE0111</b>	<b>The truststore location information is either null or empty. It should point to an existing file.</b>
<b>Explanation</b>	The truststore location information is either null or empty. It should point to an existing file.
<b>Action</b>	The truststore location should point to an existing file.

---

<b>SPMCFGE0112</b>	<b>The specified port is already bound by configuration instance {0} of runtime {1} and is enabled.</b>
<b>Explanation</b>	The specified port is already bound by configuration instance {0} of runtime {1} and is enabled.
<b>Action</b>	Change the port number and retry.
<b>SPMCFGE0114</b>	<b>The specified Bind Address value of {0} is invalid.</b>
<b>Explanation</b>	The value of {0} is invalid for Bind Address.
<b>Action</b>	Specify a valid bind address and retry.
<b>SPMCFGE0115</b>	<b>The specified port {0} is already in use by another configuration instance.</b>
<b>Explanation</b>	The specified port {0} is already in use by configuration instance {1} of runtime {2}.
<b>Action</b>	Change the port number and retry.
<b>SPMCFGE0117</b>	<b>The specified port number {0} is already in use.</b>
<b>Explanation</b>	The specified port number {0} is already in use. The port number is bound to an application outside the current installation of Software AG Suite of products.
<b>Action</b>	Specify a different port number or shut down the component that is running on this port.
<b>SPMCFGE0120</b>	<b>License file location is not specified in License Location Manager.</b>
<b>Explanation</b>	The location of the license file is not specified in the License Location Manager.
<b>Action</b>	Specify a valid license file location in License Location Manger before loading the License instance.
<b>SPMCFGE0121</b>	<b>The configured license is not valid for this product : {0}</b>
<b>Explanation</b>	The product code in the license file does not match with the product installed.
<b>Action</b>	Contact your system administrator or Software AG Global Support.
<b>SPMCFGE0122</b>	<b>The configured license is not valid for this version : {0}</b>
<b>Explanation</b>	The product version in the license file does not match with the product installed version.
<b>Action</b>	Contact your system administrator or Software AG Support.

<b>SPMCFGE0125</b>	<b>The provided port alias {0} already exists.</b>
<b>Explanation</b>	The provided port alias {0} already exists for this runtime component.
<b>Action</b>	Provide a unique port alias for the runtime component.
<b>SPMCFGE0126</b>	<b>The specified port alias {0} differs from the existing port alias {1}</b>
<b>Explanation</b>	The specified port alias {0} differs from the existing port alias {1}
<b>Action</b>	Do not change the port alias when you execute an update operation.
<b>SPMCFGE0127</b>	<b>The JDBC Pool alias cannot be changed once it is created.</b>
<b>Explanation</b>	While updating a JDBC Pool, the alias was modified. The alias for the JDBC Pool must not change after creating the pool.
<b>Action</b>	Specify the same JDBC Pool alias in the request, or remove it.
<b>SPMCFGE0128</b>	<b>Configuration of type COMMON-JNDI is null.</b>
<b>Explanation</b>	The configuration object for COMMON-JNDI is null.
<b>Action</b>	Specify the valid configuration object for COMMON-JNDI.
<b>SPMCFGE0129</b>	<b>Configuration of type COMMON-JNDI should have one JNDI element.</b>
<b>Explanation</b>	A configuration of type COMMON-JNDI should have one JNDI element.
<b>Action</b>	Provide one JNDI element for this configuration.
<b>SPMCFGE0130</b>	<b>Configuration of type COMMON-JNDI should have JNDI element with valid alias.</b>
<b>Explanation</b>	A configuration of type COMMON-JNDI should have a JNDI element with a valid alias.
<b>Action</b>	Provide URL friendly alias for the JNDI element.
<b>SPMCFGE0131</b>	<b>Configuration of type COMMON-JNDI should have JNDI element with unique alias.</b>
<b>Explanation</b>	A configuration of type COMMON-JNDI should have a JNDI element with a unique alias.
<b>Action</b>	Provide a unique alias for the JNDI element.

---

<b>SPMCFGE0132</b>	<b>Error occurred while retrieving the JNDI configuration instances.</b>
<b>Explanation</b>	An error occurred while retrieving the JNDI configuration instances.
<b>Action</b>	See the Platform Manager logs for more details.
<b>SPMCFGE0133</b>	<b>Provide a URL for the specified JNDI provider type.</b>
<b>Explanation</b>	The URL for the specified JNDI provider type is missing.
<b>Action</b>	Specify the URL for the specified JNDI provider type.
<b>SPMCFGE0134</b>	<b>Provide Initial Context Factory for the specified JNDI provider type.</b>
<b>Explanation</b>	The specified JNDI provider type does not have an Initial Context Factory.
<b>Action</b>	Specify the Initial Context Factory for the specified JNDI provider type.
<b>SPMCFGE0135</b>	<b>DbFunctional alias was not found.</b>
<b>Explanation</b>	A DbFunctional alias with the specified alias value could not be found.
<b>Action</b>	Check if a DbFunctional alias with the provided alias value is available.
<b>SPMCFGE0136</b>	<b>Element value is not set.</b>
<b>Explanation</b>	The value of an integral element has not been set.
<b>Action</b>	Ensure that the specified data contains valid values for all required elements.
<b>SPMCFGE0137</b>	<b>Invalid DbFunctional alias.</b>
<b>Explanation</b>	The provided DbFunctional alias is invalid.
<b>Action</b>	Check the provided DbFunctional alias for invalid characters.
<b>SPMCFGE0138</b>	<b>Duplicate DbFunctional alias.</b>
<b>Explanation</b>	The provided alias already exists.
<b>Action</b>	Provide a new alias.
<b>SPMCFGE0139</b>	<b>Invalid Pool alias.</b>
<b>Explanation</b>	The provided Pool alias is invalid.
<b>Action</b>	Provide a new Pool alias.

<b>SPMCFGE0140</b>	<b>Problem detected while trying to read/write DbFunctional alias data.</b>
<b>Explanation</b>	The read/write operation failed.
<b>Action</b>	Check if the DbFunctional alias data file is available.
<b>SPMCFGE0141</b>	<b>Configuration of type COMMON-JMS should have JMS element with valid alias.</b>
<b>Explanation</b>	A configuration of type COMMON-JMS should have a JMS element with a valid alias.
<b>Action</b>	Specify a URL friendly alias for the JMS element.
<b>SPMCFGE0142</b>	<b>Configuration of type COMMON-JMS is null.</b>
<b>Explanation</b>	Configuration object for COMMON-JMS is null.
<b>Action</b>	Specify the valid configuration object for COMMON-JMS.
<b>SPMCFGE0143</b>	<b>Configuration of type COMMON-JMS should have a JMS element.</b>
<b>Explanation</b>	A configuration of type COMMON-JMS should have a JMS element.
<b>Action</b>	Specify a JMS element for this configuration.
<b>SPMCFGE0144</b>	<b>Provide URL for the specified JMS provider type.</b>
<b>Explanation</b>	The URL for the specified JMS provider type is missing.
<b>Action</b>	Provide a URL for the specified JMS provider type.
<b>SPMCFGE0145</b>	<b>Provide an existing JNDI alias for the specified JMS provider type.</b>
<b>Explanation</b>	The JNDI alias provided for the specified JMS provider type does not exist.
<b>Action</b>	Provide an existing JNDI alias for the specified JMS provider type.
<b>SPMCFGE0146</b>	<b>The provided JNDI alias does not exist. Provide an existing JNDI alias for the specified JMS provider type.</b>
<b>Explanation</b>	The JNDI alias provided for the specified JMS provider type does not exist.
<b>Action</b>	Provide an existing JNDI alias for the specified JMS provider type.
<b>SPMCFGE0147</b>	<b>Configuration of type COMMON-JMS should have JMS element with unique alias.</b>
<b>Explanation</b>	A configuration of type COMMON-JMS should have a JMS element with a unique alias.
<b>Action</b>	Provide unique alias for the JMS element.

---

<b>SPMCFGE0148</b>	<b>Error occurred while retrieving the JMS configuration instances.</b>
<b>Explanation</b>	An error occurred while retrieving the JMS configuration instances.
<b>Action</b>	See the Platform Manager logs for mode details.
<b>SPMCFGE0149</b>	<b>ConfigurationUiBindingService is not set.</b>
<b>Explanation</b>	The ConfigurationUiBindingService is not set.
<b>Action</b>	Register the ConfigurationUiBindingService.
<b>SPMCFGE0150</b>	<b>Configuration ui binding for {0} runtimeComponent and {1} configurationType cannot be retrieved.</b>
<b>Explanation</b>	The configuration user interface binding cannot be retrieved because of incorrect search parameters or incorrect SPI implementation.
<b>Action</b>	Provide a valid runtimeComponent ID and configurationType ID or check the SPI implementation.
<b>SPMCFGE0151</b>	<b>Error occurred while trying to unmarshal ui binding XML data.</b>
<b>Explanation</b>	An error occurred while trying to unmarshal the user interface binding XML data.
<b>Action</b>	Check if the XML file is well-formed and valid.
<b>SPMCFGE0152</b>	<b>Error occurred while trying to parse XSD Schema.</b>
<b>Explanation</b>	An error occurred while trying to parse the XSD Schema.
<b>Action</b>	Check if the XSD schema is valid.
<b>SPMCFGE0153</b>	<b>Client group for webMethods Messaging alias is invalid or not specified.</b>
<b>Explanation</b>	While configuring webMethods Messaging alias, if provider type is Broker, Client Group cannot be empty.
<b>Action</b>	Provide a valid Client Group while configuring webMethods Messaging alias.
<b>SPMCFGE0154</b>	<b>Broker messaging alias must have valid authentication configuration.</b>
<b>Explanation</b>	If the webMethods Messaging alias provider is Broker, you must specify valid authentication configuration.
<b>Action</b>	Provide a valid authentication while configuring webMethods Messaging alias.

<b>SPMCFGE0155</b>	<b>Broker Messaging alias must have a valid user.</b>
<b>Explanation</b>	While configuring webMethods Messaging alias, if provider type is Broker, you must specify a valid user.
<b>Action</b>	Provide a valid user while configuring webMethods Messaging alias.
<b>SPMCFGE0156</b>	<b>Broker Messaging alias must have a valid password.</b>
<b>Explanation</b>	When the messaging alias provider is Broker, the alias should have a valid password.
<b>Action</b>	Provide a valid password for a messaging alias with provider type Broker.
<b>SPMCFGE0157</b>	<b>Broker Messaging alias must have a valid keystore definition.</b>
<b>Explanation</b>	When the messaging alias provider is Broker, it should have valid keystore definition.
<b>Action</b>	Provide a valid keystore for a messaging alias with provider type Broker.
<b>SPMCFGE0158</b>	<b>Broker Messaging alias must have a valid encryption definition.</b>
<b>Explanation</b>	When the messaging alias provider is Broker, the alias should have a valid encryption definition.
<b>Action</b>	Provide a valid encryption definition for a messaging alias with provider type Broker.
<b>SPMCFGE0159</b>	<b>Specify at least one server log facility to be updated.</b>
<b>Explanation</b>	When updating the server logger, you must specify at least one server log facility.
<b>Action</b>	Ensure that you specify a server log facility.
<b>SPMCFGE0160</b>	<b>While updating a global variable, you can modify only the value for the global variable.</b>
<b>Explanation</b>	You attempted to modify the key while updating a global variable. You can modify only the value for the global variable.
<b>Action</b>	Ensure that you modify only the value for the global variable.
<b>SPMCFGE0161</b>	<b>Configuration of type COMMON-LOCAL-USERS should have User element with a valid id.</b>
<b>Explanation</b>	The User element should have an ID that contains only URL friendly symbols.
<b>Action</b>	Provide URL friendly ID for the User element.

---

<b>SPMCFGE0162</b>	<b>Configuration of type COMMON-LOCAL-USERS should have one User instance.</b>
<b>Explanation</b>	Configuration of type COMMON-LOCAL-USERS should have one User instance.
<b>Action</b>	Provide one User element for this configuration.
<b>SPMCFGE0163</b>	<b>Configuration of type COMMON-LOCAL-USERS should have User element with unique id.</b>
<b>Explanation</b>	The ID should be unique among all configurations of type COMMON-LOCAL-USERS.
<b>Action</b>	Provide a unique ID for the User element.
<b>SPMCFGE0164</b>	<b>Retrieving COMMON-LOCAL-USERS configuration instances failed.</b>
<b>Explanation</b>	An error occurred while retrieving the configuration instances of type COMMON-LOCAL-USERS.
<b>Action</b>	Check the error logs for more information.
<b>SPMCFGE0165</b>	<b>Configuration of type COMMON-LOCAL-USERS should have password.</b>
<b>Explanation</b>	A password is required for the User element, but it is missing.
<b>Action</b>	Provide a password for the User.
<b>SPMCFGE0166</b>	<b>The User element id for existing configuration of type COMMON-LOCAL-USERS cannot be updated.</b>
<b>Explanation</b>	User ID cannot be changed on update operation.
<b>Action</b>	Use the the same User ID from the existing configuration.
<b>SPMCFGE0167</b>	<b>Configuration of type COMMON-CLUSTER is null.</b>
<b>Explanation</b>	The configuration object for COMMON-CLUSTER is null.
<b>Action</b>	Specify the valid configuration object for COMMON-CLUSTER.
<b>SPMCFGE0168</b>	<b>The provided server name should be unique within the landscape.</b>
<b>Explanation</b>	The provided server name already exists in the landscape.
<b>Action</b>	Provide a server name that is unique within the landscape.

<b>SPMCFGE0169</b>	<b>Error occurred while retrieving the COMMON-CLUSTER configuration instances.</b>
<b>Explanation</b>	An error occurred while retrieving the COMMON-CLUSTER configuration instances.
<b>Action</b>	See the Platform Manager logs for mode details.
<b>SPMCFGE0170</b>	<b>Path to the internal user repository file cannot be found.</b>
<b>Explanation</b>	File {0} does not exist.
<b>Action</b>	Specify a valid path to the user.txt file relative to profile or product suite directories.
<b>SPMCFGE0171</b>	<b>User does not exist.</b>
<b>Explanation</b>	User with id {0} is not found in the User repository file.
<b>Action</b>	Try to refresh the configuration metadata.
<b>SPMCFGE0172</b>	<b>One of the existing servers has changed name.</b>
<b>Explanation</b>	One of the existing servers has a changed name.
<b>Action</b>	The names of existing servers should not change.
<b>SPMCFGE0173</b>	<b>Invalid value of Init Size.</b>
<b>Explanation</b>	Only positive integers are allowed.
<b>Action</b>	Provide Init Size greater than zero.
<b>SPMCFGE0174</b>	<b>Path to users.txt not specified.</b>
<b>Explanation</b>	The path to the users.txt file is not specified in the component XML data.
<b>Action</b>	Specify a property named "usersRepoPath" with a value relative to profile or Software AG installation directories.
<b>SPMCFGE0175</b>	<b>Missing or invalid ProxyServer alias.</b>
<b>Explanation</b>	The ProxyServer alias is missing or invalid.
<b>Action</b>	Provide a valid ProxyServer alias.
<b>SPMCFGE0176</b>	<b>Protocol or Host value is not set.</b>
<b>Explanation</b>	The value of a required element (Host or Protocol) has not been set.
<b>Action</b>	Ensure that the specified data contains valid values for Host and Protocol.

---

<b>SPMCFGE0177</b>	<b>Duplicate ProxyServer alias.</b>
<b>Explanation</b>	The provided alias already exists.
<b>Action</b>	Provide a new alias.
<b>SPMCFGE0178</b>	<b>Invalid Protocol value.</b>
<b>Explanation</b>	The provided Protocol value is invalid.
<b>Action</b>	Provide a valid Protocol value.
<b>SPMCFGE0179</b>	<b>Invalid Host value.</b>
<b>Explanation</b>	The provided Host value is invalid.
<b>Action</b>	Provide a valid Host value.
<b>SPMCFGE0180</b>	<b>Problem detected while trying to read/write Proxy data.</b>
<b>Explanation</b>	The read/write operation failed.
<b>Action</b>	Check if the Proxy data file is available.
<b>SPMCFGE0181</b>	<b>Invalid value of Max Size.</b>
<b>Explanation</b>	Only positive integers greater than Init Size are allowed.
<b>Action</b>	Provide Max Size greater than zero and greater than Init Size.
<b>SPMCFGE0182</b>	<b>Error in configuration changed event handler for run-time component {0}.</b>
<b>Explanation</b>	An event was raised but most likely this run-time component does not exist anymore.
<b>Action</b>	Change the configuration for existing run-time components.
<b>SPMCFGE0183</b>	<b>Missing or invalid Component Endpoint alias.</b>
<b>Explanation</b>	The Component Endpoint alias is missing or invalid.
<b>Action</b>	Provide a valid Component Endpoint alias.
<b>SPMCFGE0184</b>	<b>Duplicate Component Endpoint alias.</b>
<b>Explanation</b>	The provided alias already exists.
<b>Action</b>	Provide a new unique alias.

<b>SPMCFGE0185</b>	<b>Problem detected while trying to read/write configuration data.</b>
<b>Explanation</b>	The read/write operation failed.
<b>Action</b>	Check if the configuration data file is available.
<b>SPMCFGE0186</b>	<b>There is no existing ProxySettings configuration instance with the provided ProxyAlias.</b>
<b>Explanation</b>	The provided ProxyAlias was not found in the existing ProxySettings aliases.
<b>Action</b>	Provide existing ProxyAlias.
<b>SPMCFGE0187</b>	<b>There is no existing Keystore configuration instance with the provided KeystoreAlias.</b>
<b>Explanation</b>	The provided KeystoreAlias was not found in the existing Keystore aliases.
<b>Action</b>	Provide existing KeystoreAlias.
<b>SPMCFGE0188</b>	<b>There is no existing Truststore configuration instance with the provided TruststoreAlias.</b>
<b>Explanation</b>	The provided TruststoreAlias was not found in the existing Truststore aliases.
<b>Action</b>	Provide existing TruststoreAlias.
<b>SPMCFGE0189</b>	<b>Missing or empty BASIC authentication user.</b>
<b>Explanation</b>	The BASIC authentication user is missing or empty.
<b>Action</b>	Provide BASIC authentication user.
<b>SPMCFGE0190</b>	<b>Either KeystoreAlias or KeystoreDefinition can be specified, but not both.</b>
<b>Explanation</b>	Either KeystoreAlias or KeystoreDefinition can be specified, but not both at the same time.
<b>Action</b>	Provide either KeystoreAlias or KeystoreDefinition.
<b>SPMCFGE0191</b>	<b>Either TruststoreDefinition or TruststoreAlias can be used, but not both.</b>
<b>Explanation</b>	Either TruststoreDefinition or TruststoreAlias can be used, but not both at the same time.
<b>Action</b>	Provide either TruststoreDefinition or TruststoreAlias.

---

<b>SPMCFGE0193</b>	<b>The "configuration" property is not set.</b>
<b>Explanation</b>	The "configuration" property defines where the proxy settings are stored.
<b>Action</b>	Set the "configuration" property.
<b>SPMCFGE0194</b>	<b>This configuration instance is not intended to be deleted.</b>
<b>Explanation</b>	This configuration can only be modified.
<b>Action</b>	Modify the configuration instead of deleting it.
<b>SPMCFGE0195</b>	<b>Configuration password decryption failed. The provided value for shared secret is incorrect.</b>
<b>Explanation</b>	Decrypting the configuration password has failed. The value specified for the shared secret is incorrect.
<b>Action</b>	Check if the values for shared secret on Command Central and Platform Manager are the same.
<b>SPMCFGE0196</b>	<b>The server cannot be null.</b>
<b>Explanation</b>	The creation of a cluster configuration requires servers.
<b>Action</b>	Specify at least one server.
<b>SPMCFGE0197</b>	<b>Wrong configuration ID.</b>
<b>Explanation</b>	The configuration ID is not recognized.
<b>Action</b>	Re-try using a valid configuration ID.
<b>SPMCFGE0198</b>	<b>LDAP configuration file not found.</b>
<b>Explanation</b>	An LDAP configuration file with the specified alias is not found.
<b>Action</b>	Specify a valid configuration instance ID.
<b>SPMCFGE0199</b>	<b>Configuration {0} can not be deleted.</b>
<b>Explanation</b>	The configuration file can not be deleted.
<b>Action</b>	Make sure that a configuration with the specified alias exists.

<b>SPMCFGE0201</b>	<b>Error while processing jaas.config entries.</b>
<b>Explanation</b>	Cannot store the JAAS configuration file.
<b>Action</b>	Check the wrapper log for details about the error.
<b>SPMCFGE0202</b>	<b>{0} process finished with error code "{1}".</b>
<b>Explanation</b>	CMD: {2}, OUTPUT: {3}
<b>Action</b>	Check the upgrade and migration help for the product.
<b>SPMCFGE0204</b>	<b>There is no existing Credentials configuration instance with the provided alias {0}.</b>
<b>Explanation</b>	The specified alias {0} was not found in the existing credentials configuration instances.
<b>Action</b>	Specify an existing credentials alias.
<b>SPMCFGE0205</b>	<b>Credentials configuration file not found.</b>
<b>Explanation</b>	A credentials configuration file with the specified alias is not found.
<b>Action</b>	Specify a valid configuration instance ID.
<b>SPMCFGE0206</b>	<b>Specified alias is reserved for default credentials and cannot be used.</b>
<b>Explanation</b>	The default credentials have reserved aliases, such as NONE, TRUSTED or DEFAULT_ADMINISTRATOR.
<b>Action</b>	Specify a valid alias.
<b>SPMCFGE0207</b>	<b>Configuration instance with alias {0} does not exist.</b>
<b>Explanation</b>	The specified configuration instance does not exist.
<b>Action</b>	Specify a valid alias of an existing configuration instance.
<b>SPMCFGE0209</b>	<b>Proxy configuration file not found.</b>
<b>Explanation</b>	The configuration instance ID is not valid.
<b>Action</b>	Specify a valid configuration instance ID.
<b>SPMCFGE0210</b>	<b>A realm with the same name already exists.</b>
<b>Explanation</b>	A JAAS realm with the same name already exists.
<b>Action</b>	Specify a unique realm name.

---

<b>SPMCFG10108</b>	<b>No primary or HTTPS ports are found for {0} component and its parent/child relations.</b>
<b>Explanation</b>	No primary or HTTPS ports were found for {0} component and its parent/child relations.
<b>Action</b>	Check configured and available ports for availability and collisions.
<b>SPMCFGW0029</b>	<b>The validator with the given type is not able to instantiate a KeyStore.</b>
<b>Explanation</b>	The validator with the given type is not able to instantiate a KeyStore.
<b>Action</b>	Provide the correct certificate information.
<b>SPMCFGW0030</b>	<b>An exception occurred when trying to load the keystore certificate.</b>
<b>Explanation</b>	The NoSuchAlgorithmException exception occurred when trying to load the keystore certificate.
<b>Action</b>	Provide the correct certificate information.
<b>SPMCFGW0031</b>	<b>An exception occurred while trying to load the keystore certificate.</b>
<b>Explanation</b>	The CertificateException exception occurred while trying to load the keystore certificate.
<b>Action</b>	Provide the correct certificate information.
<b>SPMCFGW0032</b>	<b>An exception occurred when trying to load the keystore certificate.</b>
<b>Explanation</b>	The IOException exception occurred when trying to load the keystore certificate.
<b>Action</b>	Provide the correct certificate information.
<b>SPMCFGW0033</b>	<b>An exception occurred when trying to load the keystore certificate.</b>
<b>Explanation</b>	The URISyntaxException exception occurred when trying to load the keystore certificate.
<b>Action</b>	Provide the correct certificate information.
<b>SPMCFGW0034</b>	<b>The file location provided in the truststore could not be found.</b>
<b>Explanation</b>	The file location provided in the truststore could not be found.
<b>Action</b>	Provide the correct certificate information.

<b>SPMCFGW0035</b>	<b>An exception occurred when trying to load the truststore certificate.</b>
<b>Explanation</b>	The KeyStoreException exception occurred when trying to load the truststore certificate.
<b>Action</b>	Provide the correct certificate information.
<b>SPMCFGW0036</b>	<b>An exception occurred when trying to load the certificate.</b>
<b>Explanation</b>	The NoSuchAlgorithmException exception occurred when trying to load the certificate.
<b>Action</b>	Provide the correct certificate information.
<b>SPMCFGW0037</b>	<b>An exception occurred when trying to load the certificate.</b>
<b>Explanation</b>	The CertificateException exception occurred when trying to load the certificate.
<b>Action</b>	Provide the correct certificate information.
<b>SPMCFGW0038</b>	<b>The validator could not load the certificate because of an exception.</b>
<b>Explanation</b>	The validator could not load the certificate when trying to load the certificate because of the IOException exception.
<b>Action</b>	Provide the correct certificate information.
<b>SPMCFGW0039</b>	<b>URI syntax provided is incorrect.</b>
<b>Explanation</b>	The URISyntaxException occurred when trying to load the certificate.
<b>Action</b>	Provide the correct certificate information.
<b>SPMCFGW0057</b>	<b>Platform Manager is unable to load JDBC driver class.</b>
<b>Explanation</b>	Platform Manager is unable to load JDBC driver class because the driver class is not specified in the classpath.
<b>Action</b>	Specify the driver class in the classpath.
<b>SPMCFGW0083</b>	<b>The path of the log file {0} is not fully qualified.</b>
<b>Explanation</b>	The specified log file path is not fully qualified.
<b>Action</b>	Provide the absolute path for the log file.

<b>SPMCFGW0104</b>	<b>Could not perform configuration validation for {0} because {1} error was encountered.</b>
<b>Explanation</b>	Could not perform configuration validation for {0} because {1} error was encountered.
<b>Action</b>	Retry the action.
<b>SPMCFGW0113</b>	<b>The specified port is already bound by configuration instance {0} of runtime {1} and is not enabled.</b>
<b>Explanation</b>	The specified port is already bound by configuration instance {0} of runtime {1} and is not enabled.
<b>Action</b>	Change the port number and retry.
<b>SPMCFGW0116</b>	<b>The specified port {0} is already in use by another configuration instance.</b>
<b>Explanation</b>	The specified port {0} is already in use by configuration instance {1} of runtime {2}, but is not enabled.
<b>Action</b>	Specify a different port number.
<b>SPMCFGW0203</b>	<b>Advanced Memory settings are deprecated.</b>
<b>Explanation</b>	Using the COMMON-MEMORY configuration type to set up advanced memory settings is deprecated.
<b>Action</b>	Use the COMMON-JVM-OPTIONS configuration type to configure the advanced memory settings.
<b>SPMCFRE0000</b>	<b>The content of the response is not acceptable according to the accept headers</b>
<b>Explanation</b>	The content of the response is not acceptable according to the accept headers.
<b>Action</b>	Check the response and the accept headers.
<b>SPMCFRE0001</b>	<b>Unexpected exception occurred.</b>
<b>Explanation</b>	Unexpected exception occurred.
<b>Action</b>	Check the logs.
<b>SPMCFRE0002</b>	<b>Configuration partial failure for runtime component: {0}, instance: {1} with type {2} - with linked exception:</b>
<b>Explanation</b>	Configuration partial failure for runtime component: {0}, instance: {1} with type {2} - with linked exception:
<b>Action</b>	Check the logs.

<b>SPMCFRE0003</b>	<b>ConfigurationSerializersRegistry is not available.</b>
<b>Explanation</b>	ConfigurationSerializersRegistry is not available.
<b>Action</b>	Contact Software AG Global Support.
<b>SPMCFRE0004</b>	<b>ConfigurationSerializer SPI could not be found for RuntimeComponentId "{0}" and ConfigurationTypeId "{1}" .</b>
<b>Explanation</b>	Platform Manager could not find a registered ConfigurationSerializer that can handle ConfigurationInstances with these properties.
<b>Action</b>	Register a ConfigurationSerializer SPI implementation that can handle ConfigurationInstances with these properties.
<b>SPMCFRE0005</b>	<b>A ConfigurationTypeId "{0}" doesn't exist for RuntimeComponentId "{1}" .</b>
<b>Explanation</b>	There is not registered ConfigurationType with the provided ID for the required RuntimeComponent.
<b>Action</b>	Provide valid ConfigurationTypeId for the required RuntimeComponent.
<b>SPMCFRE0006</b>	<b>Configuration Service cannot handle Configuration Model "{0}". Supported models are: {1}. Check Configuration Type "{2}" definition.</b>
<b>Explanation</b>	Most likely there is an error in the definition of the Configuration Type SPI in the respective product plug-in.
<b>Action</b>	Check the Configuration Type "{2}" definition.
<b>SPMCLTE0014</b>	<b>ConfigurationSerializer SPI could not be found for RuntimeComponentId "{0}" and ConfigurationTypeId "{1}" .</b>
<b>Explanation</b>	Platform Manager could not find a registered ConfigurationSerializer that can handle ConfigurationInstances with these properties.
<b>Action</b>	Register a ConfigurationSerializer SPI implementation that can handle ConfigurationInstances with these properties.
<b>SPMCLTE0015</b>	<b>Authentication call to SPM failed to execute.</b>
<b>Explanation</b>	Authentication call to SPM failed to execute.
<b>Action</b>	Make sure that the user has valid access rights to the service.

---

<b>SPMCLTE0016</b>	<b>Cannot retrieve the delegated assertion for the current user.</b>
<b>Explanation</b>	Cannot retrieve the delegated assertion for the current user.
<b>Action</b>	Check if the user has valid delegated rights.
<b>SPMCLTE0017</b>	<b>Internal Error processing Platform Manager request</b>
<b>Explanation</b>	The server encountered an error and it cannot complete the request.
<b>Action</b>	Contact your system administrator.
<b>SPMCLTE0018</b>	<b>The specified runtime component {0} could not be found on node {1}.</b>
<b>Explanation</b>	There is no component called {0} registered for node {1}. The data could not be retrieved.
<b>Action</b>	Check the components for Platform Manager node {1}.
<b>SPMCLTE0020</b>	<b>{0} is not a valid type for the runscript request</b>
<b>Explanation</b>	The type for the runscript request is not valid. Valid types are fix or product.
<b>Action</b>	Resubmit the request with a valid type.
<b>SPMCLTE0021</b>	<b>No artifacts specified in uninstall request</b>
<b>Explanation</b>	The uninstall request does not specify any products or fixes.
<b>Action</b>	Resubmit the request with a valid list of products and fixes.
<b>SPMCLTE0022</b>	<b>Invalid artifact type for uninstall</b>
<b>Explanation</b>	The artifact type must be product or fix.
<b>Action</b>	Specify valid artifacts in the request.
<b>SPMCLTE0023</b>	<b>Invalid repository type: {0}</b>
<b>Explanation</b>	The specified repository type is not supported.
<b>Action</b>	Use fix or product as the repository type.
<b>SPMCLTE0024</b>	<b>No such repository: {0}</b>
<b>Explanation</b>	The repository does not exist.
<b>Action</b>	Specify a valid repository.

<b>SPMCLTE0025</b>	<b>Unsupported repository type: {0}</b>
<b>Explanation</b>	Fix and product are the only supported repository types.
<b>Action</b>	Use fix or product as the repository type.
<b>SPMCLTE0026</b>	<b>Unsupported repository type: {0}</b>
<b>Explanation</b>	Fix and product are the only supported repository types.
<b>Action</b>	Specify a valid repository type.
<b>SPMCLTE0027</b>	<b>The response cannot be converted to java.util.Properties: {0}</b>
<b>Explanation</b>	The response does not comply with the java.util.Properties text or XML format.
<b>Action</b>	Make sure the format is correct or contact Software AG Global Support.
<b>SPMCLTE0028</b>	<b>{0} is not a valid type for the install request.</b>
<b>Explanation</b>	The type for the install request is not valid. Valid types are fix or product.
<b>Action</b>	Resubmit the request with a valid type.
<b>SPMCLTE0030</b>	<b>Failed to store license metering time stamp.</b>
<b>Explanation</b>	The products on the platform {0} were metered by the license metering tool of Command Central, but the time stamp when this metering was performed by node {1} could not be stored.
<b>Action</b>	Make sure that the harddisc on the specified server is not full or contact Software AG Global Support.
<b>SPMCLTE0031</b>	<b>Remote task failed: {0}</b>
<b>Explanation</b>	Remote task failed: {0}
<b>Action</b>	Check the corresponding Platform Manager logs for more details about the error.
<b>SPMCLTI0009</b>	<b>Internal Server Error</b>
<b>Explanation</b>	Internal server error.
<b>Action</b>	Make sure that the required services are running, communication channels are accessible, and parameters are valid.

---

<b>SPMCLTI0010</b>	<b>Unknown Error</b>
<b>Explanation</b>	An unspecified error occurred during communication.
<b>Action</b>	Make sure that the required services are running, communication channels are accessible, and parameters are valid.
<b>SPMCLTI0011</b>	<b>Error occurred during execution of the command!</b>
<b>Explanation</b>	An error occurred during communication.
<b>Action</b>	Make sure that the required services are running, communication channels are accessible, and parameters are valid.
<b>SPMCLTW0001</b>	<b>An exception has occurred while retrieving remotely RuntimeStatus from: {0}</b>
<b>Explanation</b>	This might be happening due to a number of reasons, such as missing monitoring implementation in the product plugin, network interference, and others.
<b>Action</b>	See detailed stack trace in order to define the actual reason for this exception.
<b>SPMCOME0000</b>	<b>{0} is unknown runtime component.</b>
<b>Explanation</b>	This component ID does not exist.
<b>Action</b>	Use runtimeComponentId that already exists.
<b>SPMCOME0001</b>	<b>{0} is an unknown product.</b>
<b>Explanation</b>	The required productId does not exist in the list of InventoryService.getInstalledProducts()
<b>Action</b>	Use a productId of a product that is already installed.
<b>SPMCOME0002</b>	<b>No available implementation for {0}.</b>
<b>Explanation</b>	Displayed status of a product plug-in after calling a specific operation that is not available.
<b>Action</b>	Use an available operation.
<b>SPMCOME0003</b>	<b>The PortSettings XML cannot be empty.</b>
<b>Explanation</b>	The PortSettings XML response cannot be empty.
<b>Action</b>	Add data in the PortSettings XML response.

<b>SPMCOME0004</b>	<b>PortSettings contains property keys that do not match properties in the config.ini file.</b>
<b>Explanation</b>	PortSettings contains property keys that do not match properties in the config.ini file.
<b>Action</b>	Check the property keys and try to find the matching one or fix the config.ini file.
<b>SPMCOME0005</b>	<b>Load configuration error.</b>
<b>Explanation</b>	Indicates issues with reading/writing a configuration.
<b>Action</b>	Fix any issues related to reading or writing the configuration.
<b>SPMCOME0006</b>	<b>Unexpected exception.</b>
<b>Explanation</b>	An unexpected exception occurred while reading/writing a configuration.
<b>Action</b>	Fix the unexpected exception.
<b>SPMCOME0007</b>	<b>Un-handled internal server error. {0}</b>
<b>Explanation</b>	A Platform Manager Exception occurred.
<b>Action</b>	Resolve the exception.
<b>SPMCOME0010</b>	<b>Error:</b>
<b>Explanation</b>	This is most likely an error that is not expected.
<b>Action</b>	None.
<b>SPMCOME0017</b>	<b>Provided configuration is not valid.</b>
<b>Explanation</b>	The provided configuration does not conform with the rules for the specified configuration type.
<b>Action</b>	Check the provided configuration for errors and rule breaches.
<b>SPMCOME0018</b>	<b>Unexpected component status: {0} but should have one of {1}</b>
<b>Explanation</b>	The requested operation cannot be completed because the component cannot do the operation in its current runtime status.
<b>Action</b>	Ensure that the component is in one of the expected statuses to complete this operation. For ONLINE status, start the parent runtime instance.

---

<b>SPMCOME0020</b>	<b>A Configuration instance with ID = {0} does not exist.</b>
<b>Explanation</b>	A Configuration instance with the provided ID does not exist.
<b>Action</b>	Use the ID of an existing Configuration instance.
<b>SPMCOME0029</b>	<b>Server did not find anything matching the request URI.</b>
<b>Explanation</b>	There is no resource for this URI.
<b>Action</b>	Check if the URI is correct. Check if the resource IDs are valid.
<b>SPMCOME0030</b>	<b>The request cannot be understood by the server.</b>
<b>Explanation</b>	Inconsistent or empty body.
<b>Action</b>	Do not retry without modifications of the request.
<b>SPMCOME0031</b>	<b>The request is not acceptable as stated in the accept headers.</b>
<b>Explanation</b>	Platform Manager cannot return the response in the desired format.
<b>Action</b>	Either change the accept headers, or the data format of the response.
<b>SPMCOME0033</b>	<b>The KPI {0} contains invalid data and cannot be created.</b>
<b>Explanation</b>	The error occurs when the RuntimeStateZone can not be calculated. Possible reasons for this issue are that the given values for max, marginal, and normal are null or in the wrong format.
<b>Action</b>	Check the content of the KPI and provide correct data.
<b>SPMCOME0043</b>	<b>Node version is not supported.</b>
<b>Explanation</b>	Command Central connects to an old Platform Manager node.
<b>Action</b>	Remove the old Platform Manager node.
<b>SPMCOME0045</b>	<b>Failed provisioning operation.</b>
<b>Explanation</b>	The failed status is {0}.
<b>Action</b>	Try to correct the situation. Retry the operation.
<b>SPMCOME0046</b>	<b>Operation failed due to unsatisfied dependencies: {0}</b>
<b>Explanation</b>	There are missing dependencies.
<b>Action</b>	Try to correct the situation. Retry the operation.

<b>SPMCOME0047</b>	<b>The specified repository does not exist.</b>
<b>Explanation</b>	The specified repository was not found.
<b>Action</b>	Check the repository name and provide the name of an existing repository.
<b>SPMCOME0048</b>	<b>Configuration password decryption failed. The provided value for shared secret is incorrect.</b>
<b>Explanation</b>	Decrypting the configuration password has failed. The value specified for the shared secret is incorrect.
<b>Action</b>	Check if the values for shared secret on Command Central and Platform Manager are the same.
<b>SPMCOME0049</b>	<b>Un-handled internal server error.</b>
<b>Explanation</b>	A Platform Manager Exception occurred.
<b>Action</b>	Resolve the exception.
<b>SPMCOME0051</b>	<b>Cannot connect to the repository due to {0}.</b>
<b>Explanation</b>	Internet access is required to connect to this repository. The error occurred either because the proxy for the local Platform Manager is not configured, or the metadata and the URL for the repository are not correct.
<b>Action</b>	Make sure the proxy for the local Platform Manager is configured and the given repository URL is valid. To find the URL, run 'sagcc list repository products properties=*'.
<b>SPMCOME0053</b>	<b>Service {0} is not available.</b>
<b>Explanation</b>	The service did not start in time.
<b>Action</b>	Retry the operation or refresh.
<b>SPMCOME0055</b>	<b>Cannot connect to the repository. {0}</b>
<b>Explanation</b>	The selected release is an innovation release to which you do not currently have access.
<b>Action</b>	For more information about the innovation release and how to get access, visit <a href="http://empower.softwareag.com/innovationrelease/">http://empower.softwareag.com/innovationrelease/</a>

---

<b>SPMCOME0057</b>	<b>Cannot connect to the repository.</b>
<b>Explanation</b>	The supplied credentials are not valid.
<b>Action</b>	See the Command Central documentation for information on troubleshooting credentials.
<b>SPMCOME0058</b>	<b>Cannot connect to the repository {0}.</b>
<b>Explanation</b>	The proxy for the local Platform Manager is not configured.
<b>Action</b>	See the Command Central documentation for information on configuring proxies.
<b>SPMCOME0061</b>	<b>Error reading metering data cache file.</b>
<b>Explanation</b>	The metering data cache file could not be read.
<b>Action</b>	Check the access rights to the metering folder.
<b>SPMCOME0062</b>	<b>Error writing to metering data cache file.</b>
<b>Explanation</b>	Writing to the metering data cache file failed.
<b>Action</b>	Check the access rights to the metering folder.
<b>SPMCOMI0008</b>	<b>The command is disabled.</b>
<b>Explanation</b>	Most probably an important OSGi service is not registered.
<b>Action</b>	None.
<b>SPMCOMI0009</b>	<b>No help available.</b>
<b>Explanation</b>	This command does not provide a help message.
<b>Action</b>	None.
<b>SPMCOMI0011</b>	<b>[DISABLED]</b>
<b>Explanation</b>	A command with this info line prefix cannot be executed.
<b>Action</b>	None.
<b>SPMCOMI0032</b>	<b>Unsupported operation.</b>
<b>Explanation</b>	The attempted operation is currently not supported by the Platform Manager server.
<b>Action</b>	Contact you administrator.

<b>SPMCONE0001</b>	<b>Error while loading configuration.</b>
<b>Explanation</b>	An error occurred while loading configuration.
<b>Action</b>	Provide valid arguments.
<b>SPMCONE0006</b>	<b>Error while getting a configuration type.</b>
<b>Explanation</b>	An error occurred while getting a configuration type.
<b>Action</b>	Resubmit the request.
<b>SPMCONE0007</b>	<b>Error during serialization</b>
<b>Explanation</b>	An error occurred during the serialization step.
<b>Action</b>	Resubmit the serialization step.
<b>SPMCONE0013</b>	<b>Error while updating configuration.</b>
<b>Explanation</b>	An error occurred while updating the configuration.
<b>Action</b>	Resubmit the configuration.
<b>SPMCONE0015</b>	<b>Error while getting configuration status.</b>
<b>Explanation</b>	Error while getting configuration status.
<b>Action</b>	Get the configuration status correctly.
<b>SPMCONE0024</b>	<b>Error while getting configuration instances.</b>
<b>Explanation</b>	An error occurred while getting configuration instances.
<b>Action</b>	Resubmit the configuration instances get operation.
<b>SPMCONI0000</b>	<b>The command is not recognized. Type {0} for help.</b>
<b>Explanation</b>	The typed command is not recognized.
<b>Action</b>	Type spm for help.
<b>SPMCONI0002</b>	<b>{0} - get configuration values for the given configuration type</b>
<b>Explanation</b>	Missing configuration values for the given configuration type.
<b>Action</b>	Get configuration values for the given configuration type.

---

<b>SPMCONI0003</b>	<b>Configuration (JavaModel): {0}</b>
<b>Explanation</b>	Configuration (JavaModel) information.
<b>Action</b>	None.
<b>SPMCONI0004</b>	<b>Configuration (Text): {0}</b>
<b>Explanation</b>	Configuration (Text) information.
<b>Action</b>	None.
<b>SPMCONI0005</b>	<b>No load configuration.</b>
<b>Explanation</b>	No load configuration.
<b>Action</b>	None.
<b>SPMCONI0008</b>	<b>Configuration status: {0}</b>
<b>Explanation</b>	Information about the configuration status.
<b>Action</b>	None.
<b>SPMCONI0009</b>	<b>No configuration status.</b>
<b>Explanation</b>	No configuration status.
<b>Action</b>	None.
<b>SPMCONI0010</b>	<b>The specified resource doesn't exist.</b>
<b>Explanation</b>	The specified resource doesn't exist.
<b>Action</b>	None.
<b>SPMCONI0011</b>	<b>There is no configuration type found for this runtime component.</b>
<b>Explanation</b>	There is no configuration type found for this runtime component.
<b>Action</b>	None.
<b>SPMCONI0012</b>	<b>{0} - Submit configuration and get the configuration status</b>
<b>Explanation</b>	The configuration status is missing or the configuration is not submitted.
<b>Action</b>	Submit the configuration and get the configuration status.

<b>SPMCONI0014</b>	<b>Bad URI - {0}</b>
<b>Explanation</b>	Bad URI is submitted.
<b>Action</b>	None.
<b>SPMCONI0016</b>	<b>Configuration status: {0}</b>
<b>Explanation</b>	Information about the configuration status.
<b>Action</b>	None.
<b>SPMCONI0017</b>	<b>No configuration status.</b>
<b>Explanation</b>	No configuration status.
<b>Action</b>	None.
<b>SPMCONI0018</b>	<b>{0} - query for the current configuration status.</b>
<b>Explanation</b>	A query for the current configuration status.
<b>Action</b>	None.
<b>SPMCONI0019</b>	<b>No configuration instance.</b>
<b>Explanation</b>	No configuration instance.
<b>Action</b>	None.
<b>SPMCONI0020</b>	<b>No configuration instances.</b>
<b>Explanation</b>	No configuration instances.
<b>Action</b>	None.
<b>SPMCONI0021</b>	<b>Configuration Instance description: {0}</b>
<b>Explanation</b>	Configuration Instance description.
<b>Action</b>	None.
<b>SPMCONI0022</b>	<b>Configuration Instance ID: {0}</b>
<b>Explanation</b>	Information about the Configuration Instance ID.
<b>Action</b>	None.

---

<b>SPMCONI0023</b>	<b>Configuration Instance name: {0}</b>
<b>Explanation</b>	Information about the Configuration Instance name.
<b>Action</b>	None.
<b>SPMCONI0025</b>	<b>{0} - list of the configuration instances for a given runtime component</b>
<b>Explanation</b>	List of the configuration instances for a given runtime component.
<b>Action</b>	None.
<b>SPMCONI0026</b>	<b>JobManagerService is not available.</b>
<b>Explanation</b>	JobManagerService is not available.
<b>Action</b>	None.
<b>SPMCONI0027</b>	<b>Invalid job ID: {0}</b>
<b>Explanation</b>	Information about an invalid job ID.
<b>Action</b>	None.
<b>SPMCONI0028</b>	<b>Number of jobs: {0}</b>
<b>Explanation</b>	Information about the number of jobs.
<b>Action</b>	None.
<b>SPMCONI0029</b>	<b>Job ID: {0}</b>
<b>Explanation</b>	Information about the job ID.
<b>Action</b>	None.
<b>SPMCONI0030</b>	<b>The status of the job with ID ({0}) is {1}.</b>
<b>Explanation</b>	Information about the job status.
<b>Action</b>	None.
<b>SPMCONI0031</b>	<b>The job started at {0}.</b>
<b>Explanation</b>	Information about when the job started.
<b>Action</b>	None.

**SPMCONI0032**      **The job ended at {0}.**  
**Explanation**      Information about when the job ended.  
**Action**            None.

**SPMCONI0033**      **The job is still running.**  
**Explanation**      The job is still running.  
**Action**            None.

**SPMCONI0034**      **The duration of the job so far is {0} seconds.**  
**Explanation**      Information about the duration of the job.  
**Action**            None.

**SPMCONI0035**      **{0} - lists all (not done) jobs or status of a specific job**  
**Explanation**      Lists all (not done) jobs or status of a specific job.  
**Action**            None.

**SPMCONI0036**      **{0} - runtime status of the component identified by this ID.**  
**Explanation**      Runtime status of the component identified by this ID.  
**Action**            None.

**SPMCONI0037**      **No RuntimeState found for {0}.**  
**Explanation**      No RuntimeState found.  
**Action**            None.

**SPMCONI0038**      **{0} - list of the runtime components**  
**Explanation**      List of the runtime components.  
**Action**            None.

**SPMCONI0039**      **{0} - list of the installed products**  
**Explanation**      List of the installed products.  
**Action**            None.

---

<b>SPMCONI0040</b>	<b>{0} - starts the runtime component with this ID with safe mode enabled.</b>
<b>Explanation</b>	Starts the runtime component with this ID with safe mode enabled.
<b>Action</b>	None.
<b>SPMCONI0041</b>	<b>{0} - starts the runtime component with this ID with debug mode enabled.</b>
<b>Explanation</b>	Starts the runtime component with this ID with debug mode enabled.
<b>Action</b>	None.
<b>SPMCONI0042</b>	<b>{0} - stops the runtime component with this ID.</b>
<b>Explanation</b>	Stops the runtime component with this ID.
<b>Action</b>	None.
<b>SPMCONI0043</b>	<b>{0} - starts the runtime component with this ID.</b>
<b>Explanation</b>	Starts the runtime component with this ID.
<b>Action</b>	None.
<b>SPMCONI0044</b>	<b>{0} - resumes the runtime component with this ID.</b>
<b>Explanation</b>	Resumes the runtime component with this ID.
<b>Action</b>	None.
<b>SPMCONI0045</b>	<b>{0} - restarts the runtime component with this ID.</b>
<b>Explanation</b>	Restarts the runtime component with this ID.
<b>Action</b>	None.
<b>SPMCONI0046</b>	<b>{0} - pauses the runtime component with this ID.</b>
<b>Explanation</b>	Pauses the runtime component with this ID.
<b>Action</b>	None.
<b>SPMCONI0047</b>	<b>{0} - creates a new configuration instance for a given runtime component and a given configuration type.</b>
<b>Explanation</b>	Creates a new configuration instance for a given runtime component and a given configuration type.
<b>Action</b>	None.

<b>SPMCONI0048</b>	<b>Error during creating configuration</b>
<b>Explanation</b>	Error during creating configuration
<b>Action</b>	None.
<b>SPMCONI0049</b>	<b>{0} - Delete configuration and get the configuration status.</b>
<b>Explanation</b>	Delete configuration and get the configuration status.
<b>Action</b>	Delete configuration and get the configuration status.
<b>SPMCONI0050</b>	<b>ConfigurationSerializer is not found for runtimeComponent with ID: {0} and configurationType with ID: {1}</b>
<b>Explanation</b>	ConfigurationSerializer is not found for runtimeComponent with ID: {0} and configurationType with ID: {1}.
<b>Action</b>	None.
<b>SPMCONI0051</b>	<b>{0} - runtime state of the comonent identified by this ID</b>
<b>Explanation</b>	Runtime state of the comonent identified by this ID
<b>Action</b>	None
<b>SPMCORE0001</b>	<b>Exception handling directory change events.</b>
<b>Explanation</b>	An exception occurred when handling directory change events.
<b>Action</b>	Contact your Command Central Administrator.
<b>SPMCORE0002</b>	<b>Exception processing directory change events.</b>
<b>Explanation</b>	An exception occurred when processing directory change events.
<b>Action</b>	Contact your Command Central Administrator.
<b>SPMCORE0003</b>	<b>The provided observer should not be null.</b>
<b>Explanation</b>	The provided observer should not be null.
<b>Action</b>	Provide a non-null observer to the Directory Watcher infrastructure.
<b>SPMCORE0004</b>	<b>The provided observed directory should not be null.</b>
<b>Explanation</b>	The provided observed directory should not be null.
<b>Action</b>	Provide a non-null observed directory to the Directory Watcher infrastructure.

<b>SPMCORE0005</b>	<b>The provided observed directory change types should not be null or empty.</b>
<b>Explanation</b>	The provided observed directory change types should not be null or empty.
<b>Action</b>	Provide valid observed directory change types to the Directory Watcher infrastructure.
<b>SPMCORI0000</b>	<b>TestMessage</b>
<b>Explanation</b>	Test message to be removed.
<b>Action</b>	None.
<b>SPMDBCE0000</b>	<b>Unsupported parameter name: {0}</b>
<b>Explanation</b>	The parameter name is not supported.
<b>Action</b>	See the Command Central documentation for a list of supported parameters.
<b>SPMDIAE0000</b>	<b>Log source not found: {0}</b>
<b>Explanation</b>	The requested log source does not exist.
<b>Action</b>	Use getLogSources() prior to retrieveLog().
<b>SPMDIAE0001</b>	<b>{0} does not exist or is not a directory.</b>
<b>Explanation</b>	The specified location does not exist or is not a directory.
<b>Action</b>	Provide a location that exists and is a directory.
<b>SPMDIAW0002</b>	<b>Missing 'logDirs' configuration property for DefaultLogAccess service component configuration.</b>
<b>Explanation</b>	An SPM bundle has a LogAccess service component that is missing its 'logDirs' configuraiton property.
<b>Action</b>	The OSGI service configuration must include this property if log files are to be collected.
<b>SPMDIAW0003</b>	<b>{0} cannot be evaluated.</b>
<b>Explanation</b>	The path expression {0} cannot be evaluated.
<b>Action</b>	Make sure the component definition has the correct path expression.

<b>SPMDIAW0004</b>	<b>The instance management service did not return a proper instance name.</b>
<b>Explanation</b>	The default log access component definition did not provide an instance name regular expression and the instance management service did not return a proper instance name.
<b>Action</b>	Provide an instance name regular expression or a proper implementation of the instance management service.
<b>SPMDIRE0000</b>	<b>{0} not found!</b>
<b>Explanation</b>	A runtime component or a log was not found.
<b>Action</b>	Verify the requested item is really present in the system.
<b>SPMIMGE0000</b>	<b>Product {0} does not support instance management.</b>
<b>Explanation</b>	The Platform Manager plugin for product {0} does not support instance management.
<b>Action</b>	See the Software AG Platform Manager documentation to double check if product {0} supports instance management. If the product supports instance management, contact Software AG Global Support.
<b>SPMIMGE0002</b>	<b>Properties for {0} cannot be returned.</b>
<b>Explanation</b>	A server error occurred during properties extraction.
<b>Action</b>	Contact Software AG Global Support.
<b>SPMIMGE0003</b>	<b>{0} cannot be matched against {1}</b>
<b>Explanation</b>	The specified regular expression in the component definition does not match the run-time component ID.
<b>Action</b>	Revise the regular expression in the component definition or contact Software AG Global Support.
<b>SPMIMGE0004</b>	<b>Mandatory property {0} is not specified.</b>
<b>Explanation</b>	A required property in the component definition is missing.
<b>Action</b>	Specify the required property in the component definition.
<b>SPMIMGE0005</b>	<b>Instance management script {0} cannot be resolved.</b>
<b>Explanation</b>	The instance management script was not found on the file system or there is another I\O error.
<b>Action</b>	Make sure the instance management script has the correct name and is in the correct location.

---

<b>SPMIMGE0007</b>	<b>This instance management command cannot be performed because the following input properties are missing: {0}</b>
<b>Explanation</b>	The input properties are insufficient for performing the requested instance management operation.
<b>Action</b>	Provide the input properties that are missing or contact Software AG Global Support.
<b>SPMIMGE0008</b>	<b>Instance management operation failed with exit code: {0}</b>
<b>Explanation</b>	The execution of the instance management operation failed.
<b>Action</b>	Check the logs for more details or contact SoftwareAG Global Support.
<b>SPMIMGE0009</b>	<b>Instance Management process finished with error code "{0}".</b>
<b>Explanation</b>	CMD: {1}, OUTPUT: {2}
<b>Action</b>	Check the administration documentation for the specified product instance.
<b>SPMIMGE0010</b>	<b>Property [{0}] has an invalid value [{1}].</b>
<b>Explanation</b>	Null or empty values are not allowed.
<b>Action</b>	Provide a valid value and try again.
<b>SPMIMPE0000</b>	<b>Unable to locate configuration source property for persistent ID: {0}; configuration properties for this PID are: {1}.</b>
<b>Explanation</b>	Most probably the persistent ID configuration is not provided by Dynamic Configurator.
<b>Action</b>	Provide the persistent ID using Dynamic Configurator.
<b>SPMIMPE0001</b>	<b>The configuration source location for the persistent ID {0} is not a valid URL: {1}</b>
<b>Explanation</b>	The configuration source location is not a valid URL.
<b>Action</b>	Dynamic Configurator should point to a valid URL for the given persistent ID.
<b>SPMINRI0000</b>	<b>Nothing found for ID = {0}</b>
<b>Explanation</b>	Nothing found for this ID.
<b>Action</b>	None.

<b>SPMINRI0001</b>	<b>Inventory Service is not set.</b>
<b>Explanation</b>	Inventory Service is not set.
<b>Action</b>	None.
<b>SPMINVI0000</b>	<b>Product cannot be null.</b>
<b>Explanation</b>	Product cannot be null.
<b>Action</b>	None.
<b>SPMINVI0001</b>	<b>Category cannot be null.</b>
<b>Explanation</b>	Category cannot be null.
<b>Action</b>	None.
<b>SPMINVI0002</b>	<b>ID must start with productId.</b>
<b>Explanation</b>	ID must start with productId.
<b>Action</b>	None.
<b>SPMJBRE0000</b>	<b>A job with ID {0} cannot be found.</b>
<b>Explanation</b>	A job with the specified ID may have never existed or it may have completed long before this request.
<b>Action</b>	Use the following URI to list all jobs that are running or recently completed: /spm/jobmanager/jobs
<b>SPMJOB0001</b>	<b>Maximum number of non-done jobs reached. Try again later or increase {2}. Current jobs: {0} max jobs: {1}.</b>
<b>Explanation</b>	The job manager queue is full and new jobs cannot be scheduled.
<b>Action</b>	Wait a few moments or increase com.softwareag.platform.management.jobmanager.impl.Configuration.SYS_PROP_MAX_JOBS.
<b>SPMJOB0002</b>	<b>Job sequence exhausted. Try again later or set a bigger {0}</b>
<b>Explanation</b>	All job sequence IDs have been consumed.
<b>Action</b>	Wait a few moments or set a bigger com.softwareag.platform.management.jobmanager.impl.Configuration.SYS_PROP_JOB_SEQUENCE_MAX_SIZE

---

<b>SPMJOB0003</b>	<b>Job {0} failed!</b>
<b>Explanation</b>	The task being carried out by this job has failed.
<b>Action</b>	Inspect the logs to troubleshoot the problem or contact SoftwareAG Global Support.
<b>SPMJOB0000</b>	<b>This job is done or not available due to a problem.</b>
<b>Explanation</b>	The Null Job status.
<b>Action</b>	None.
<b>SPMLCCE0000</b>	<b>runtimeComponentId for productId {0} is null.</b>
<b>Explanation</b>	The AdvancedLifecycleOperations service is registered in with productID that does not contain the given runtimeComponentId.
<b>Action</b>	Make sure that your product plugin has correct productId and runtimeComponentId IDs.
<b>SPMLCCE0001</b>	<b>Runtime component "{0}" does not support life cycle operation "{1}".</b>
<b>Explanation</b>	This Runtime component does not support the specified life cycle operation.
<b>Action</b>	Make sure you execute life cycle operations supported by this run-time component.
<b>SPMLCCE0015</b>	<b>The run-time status of runtimeComponent {0} is not {1}.</b>
<b>Explanation</b>	The lifecycle operation did not complete as expected.
<b>Action</b>	Check the logs for details about the error.
<b>SPMLCCE0016</b>	<b>Runtime status of component with id: {0} can not be retrieved or component is not stopped on time.</b>
<b>Explanation</b>	The run-time status of the component with id: {0} can not be retrieved on time.
<b>Action</b>	Check the logs for details about the error.
<b>SPMLCCE0032</b>	<b>The runtimeComponent with id: {0} does not have LifecycleOperations SPI registered.</b>
<b>Explanation</b>	A LifecycleOperations SPI has not been found for runtimeComponent : {0}
<b>Action</b>	Check the component definition, used for registering the SPI.

<b>SPMLCRE0000</b>	<b>The lifecycle operation to execute is unknown.</b>
<b>Explanation</b>	The operation is not a part of the predefined list of lifecycle operations that can be executed: start, stop, restart, pause, resume, start in debug, and start in safe mode.
<b>Action</b>	Specify an operation from the predefined list.
<b>SPMMICE0000</b>	<b>Extracting source version failed.</b>
<b>Explanation</b>	Failed to extract the source version from the bundles.info file.
<b>Action</b>	Ensure that the bundles.info file is at the correct location.
<b>SPMMONE0000</b>	<b>Could not get JMXConnector for runtime component with id {0} because JMX port configuration was not found.</b>
<b>Explanation</b>	This particular run-time component does not have a configured JMX port or there was a problem obtaining the configuration.
<b>Action</b>	Check if the run-time component is online and that at least one enabled JMX port configuration is available.
<b>SPMMWSE0000</b>	<b>Provide "sysadmin" credentials in CCE for "{0}"</b>
<b>Explanation</b>	When BASIC authentication is used, credentials for the "sysadmin" user must be supplied in Command Central for the My webMethods Server component.
<b>Action</b>	Verify that BASIC authentication for the My webMethods component uses credentials for "sysadmin" user.
<b>SPMMWSE0002</b>	<b>Primary port not set for {0}</b>
<b>Explanation</b>	A primary port is required to connect to My webMethods Server.
<b>Action</b>	Provide primary port value for {0}.
<b>SPMMWSE0003</b>	<b>Invalid URI</b>
<b>Explanation</b>	The supplied URI for connection to My webMethods Server does not have a valid syntax according to RFC 3986.
<b>Action</b>	Verify that the correct hostname and port are provided.
<b>SPMMWSE0004</b>	<b>An error occurred while constructing the URL</b>
<b>Explanation</b>	The connection URL to My webMethods Server is malformed.
<b>Action</b>	Verify that the correct hostname and port are provided.

---

<b>SPMMWSE0005</b>	<b>Root context path "{0}" is invalid.</b>
<b>Explanation</b>	The context path may start with a slash and can contain only the following characters: uppercase or lowercase letters, decimal digits, hyphen, period, and underscore.
<b>Action</b>	Verify that the root context path contains only valid characters.
<b>SPMMWSE0006</b>	<b>Invalid credentials set for user "sysadmin"</b>
<b>Explanation</b>	The password supplied for the "sysadmin" user is not correct.
<b>Action</b>	Provide the correct password for the "sysadmin" user in the authentication information in Command Central.
<b>SPMMWSE0007</b>	<b>First Name is required</b>
<b>Explanation</b>	The First Name field must not be empty.
<b>Action</b>	Enter a first name.
<b>SPMMWSE0008</b>	<b>Last Name is required</b>
<b>Explanation</b>	The Last Name field must not be empty.
<b>Action</b>	Enter a last name.
<b>SPMMWSE0009</b>	<b>Unable to find server log directory: {0}</b>
<b>Explanation</b>	Unable to read the server log directory path from systemPaths.properties
<b>Action</b>	Check if there is a connection to the My webMethods Server database.
<b>SPMMWSE0010</b>	<b>Encryption failed for: {0}</b>
<b>Explanation</b>	The encryption of a value failed.
<b>Action</b>	Contact Software AG Global Support. Provide the logs for Platform Manager and My webMethods Server and the reproduction steps for the issue.
<b>SPMMWSE0011</b>	<b>Decryption failed for: {0}</b>
<b>Explanation</b>	The decryption of a value failed.
<b>Action</b>	Contact Software AG Global Support. Provide the Platform Manager and My webMethods Server logs and the reproduction steps of the issue.

<b>SPMMWSE0012</b>	<b>Primary datasource cannot be deleted</b>
<b>Explanation</b>	You cannot delete the primary My webMethods Server database connection datasource.
<b>Action</b>	None required.
<b>SPMMWSE0013</b>	<b>Adding a Derby data source is not supported</b>
<b>Explanation</b>	My webMethods Server does not support additional Derby data sources.
<b>Action</b>	Add a datasource of one of the supported database types.
<b>SPMMWSE0014</b>	<b>Missing or invalid db.xml</b>
<b>Explanation</b>	A My webMethods Server system configuration file is either missing or invalid.
<b>Action</b>	Contact the My webMethods Server system administrator.
<b>SPMMWSE0015</b>	<b>Only TRUSTED and BASIC authentication are supported</b>
<b>Explanation</b>	The specified authentication is not supported.
<b>Action</b>	Change authentication to TRUSTED or BASIC.
<b>SPMOGIE0000</b>	<b>Could not obtain the runtime component id from "cplm" file: {0}</b>
<b>Explanation</b>	There was a problem obtaining metadata information about a specific profile.
<b>Action</b>	Check the profile folder structure and if cplm.xml contains any errors.
<b>SPMOGIE0002</b>	<b>Following exception occurred "{0}" while parsing "{1}".</b>
<b>Explanation</b>	One of the profiles contains wrong metadata.
<b>Action</b>	Check listed file for errors.
<b>SPMOGIE0003</b>	<b>The Common Platform Lifecycle Management (cplm-v.xml) file is malformed.</b>
<b>Explanation</b>	The profile metadata file contains errors.
<b>Action</b>	Try to check cplm.xml file for errors in the specific profile.
<b>SPMOGIE0005</b>	<b>Operation "{0}" is not defined in the "cplm" file.</b>
<b>Explanation</b>	There was lifecycle operation for the specific component that is not defined inside cplm.xml.
<b>Action</b>	Try to repair cplm.xml file in the component profile folder.

---

<b>SPMOGIE0008</b>	<b>Common Platform Lifecycle Management (cplm-v.xml) file not found!</b>
<b>Explanation</b>	A file called cplm.xml is expected inside the profile folder.
<b>Action</b>	Try to create cplm.xml file for the component.
<b>SPMOGIE0009</b>	<b>Configuration with version "{0}" was not found in the metadata file.</b>
<b>Explanation</b>	No configuration with the specified version exists inside the cplm.xml file.
<b>Action</b>	Check the profile folder for cplm.xml and make sure it is up to date.
<b>SPMOGIE0010</b>	<b>Recursive actions not allowed.</b>
<b>Explanation</b>	A recursive action exists inside cplm.xml file.
<b>Action</b>	Check the cplm.xml file in the profile and remove any recursive actions.
<b>SPMOGIE0011</b>	<b>Malformed action "{0}".</b>
<b>Explanation</b>	Wrong metadata information exists inside the profile cplm.xml file.
<b>Action</b>	Check the cplm.xml file for the profile and correct errors.
<b>SPMOGIE0012</b>	<b>Action "{0}" not found.</b>
<b>Explanation</b>	Unknown action defined inside cplm.xml.
<b>Action</b>	Correct the cplm.xml file for the profile.
<b>SPMOGIE0013</b>	<b>Script "{0}" does not exist.</b>
<b>Explanation</b>	The specified script cannot be found in cplm.xml.
<b>Action</b>	Specify valid script/path inside the profile cplm.xml file.
<b>SPMOGIE0014</b>	<b>Failed executing: {0}</b>
<b>Explanation</b>	A problem occurred while executing the specified script.
<b>Action</b>	Check the specified script for errors.
<b>SPMOGIE0015</b>	<b>Missing value data for element "argument".</b>
<b>Explanation</b>	Wrong data format inside the profile cplm.xml file.
<b>Action</b>	Provide valid data inside cplm.xml.

<b>SPMOGIE0016</b>	<b>More than one "action" element with the same name exist.</b>
<b>Explanation</b>	A naming conflict exists inside cplm.xml.
<b>Action</b>	Provide different action names.
<b>SPMOGIE0017</b>	<b>Two "configuration" elements have the same version.</b>
<b>Explanation</b>	A conflict exists inside cplm.xml file.
<b>Action</b>	Provide different versions for "configuration" elements.
<b>SPMOGIE0018</b>	<b>Missing attribue "path" or "actionReference" for element "execute".</b>
<b>Explanation</b>	Wrong data exists inside the profile cplm.xml.
<b>Action</b>	Provide the missing data.
<b>SPMOGIE0019</b>	<b>Cannot specify both "path" and "actionReference" attributes in one "execute" element.</b>
<b>Explanation</b>	Wrong data exists inside cplm.xml.
<b>Action</b>	Correct cplm.xml file inside the profile folder.
<b>SPMOGIE0026</b>	<b>Unable to find configuration instances for the runtime component with ID: "{0}". The "{1}" system property is not set.</b>
<b>Explanation</b>	Such a property should be available in the config.ini file located under the configuration folder of this runtime component.
<b>Action</b>	Add the property by hand. The value must be the absolute path to the folder that contains the configuration properties files.
<b>SPMOGIE0027</b>	<b>Unable to find configuration instances for the runtime component with ID: "{0}". "{1}" is either not existing or is not a directory.</b>
<b>Explanation</b>	This folder should contain the configuration properties files.
<b>Action</b>	Check if the location is configured properly in the config.ini file.
<b>SPMOGIE0029</b>	<b>Unable to load the configuration instance with ID "{0}" for the "{1}" runtime component.</b>
<b>Explanation</b>	None of the available configuration handlers can load the configuration instance. The configuration instance type might not be supported.
<b>Action</b>	Check the supported configuration instance types.

---

<b>SPMOGIE0030</b>	<b>Unable to update the configuration instance with ID "{0}" for the "{1}" runtime component.</b>
<b>Explanation</b>	None of the available configuration handlers can update the configuration instance. The configuration instance type might not be supported.
<b>Action</b>	Check the supported configuration instance types.
<b>SPMOGIE0031</b>	<b>Unable to load the configuration instance with ID: "{0}" for the "{1}" runtime component. The "{2}" property is not available but is required.</b>
<b>Explanation</b>	Unable to load the instance because of invalid set of configuration properties. The required properties must be available.
<b>Action</b>	Add the required property and report the invalid configuration instance.
<b>SPMOGIE0032</b>	<b>Unsupported protocol for configuration instance {0}.</b>
<b>Explanation</b>	Unknown protocol for the specified configuration instance.
<b>Action</b>	Check documentation for supported protocols.
<b>SPMOGIE0033</b>	<b>The update of the "{0}" configuration instance for the "{1}" runtime component failed. The port settings are empty.</b>
<b>Explanation</b>	The incoming configuration is empty. No port settings data is available.
<b>Action</b>	Port settings data should be present inside incoming configuration.
<b>SPMOGIE0034</b>	<b>No port available in configuration instance {0}.</b>
<b>Explanation</b>	Port number cannot be found inside the configuration instance.
<b>Action</b>	Provide port number inside the configuration instance.
<b>SPMOGIE0035</b>	<b>The update of the "{0}" configuration instance for the "{1}" runtime component failed. The available port configurations are more than one.</b>
<b>Explanation</b>	The configuration instance should contain only one port configuration.
<b>Action</b>	Remove obsolete port configurations.
<b>SPMOGIE0036</b>	<b>The update of the "{0}" configuration instance for the "{1}" runtime component failed. The port is null.</b>
<b>Explanation</b>	The port settings do not contain any port configuration.
<b>Action</b>	Provide port configuration.

<b>SPMOGIE0037</b>	<b>Invalid port number: "{0}"</b>
<b>Explanation</b>	The validation of the port number failed. The port number should be greater than 1024 and less than 65535.
<b>Action</b>	Check the source of the port number and provide a value in the specified range.
<b>SPMOGIE0038</b>	<b>Error writing the new configuration. An attempt was made to overwrite an existing configuration file "{0}" with the new configuration.</b>
<b>Explanation</b>	The port number is a part of the configuration file name. Therefore, if the user sets a port that is already used in another configuration, a collision in the file names occurs. In such case the write operation is aborted because configuration data might be lost.
<b>Action</b>	Check if the port number set in the configuration that is being written is not used in another configuration of the same type.
<b>SPMOGIE0039</b>	<b>The new configuration could not be written. Unable to delete the original configuration instance file: "{0}"</b>
<b>Explanation</b>	A problem occurred while deleting the configuration instance file.
<b>Action</b>	For more details, check the I/O exceptions in the log file.
<b>SPMOGIE0040</b>	<b>ConfigurationService not found!</b>
<b>Explanation</b>	Most probably spm configuration bundle was not started.
<b>Action</b>	Try to start spm the configuration bundle.
<b>SPMOGIE0042</b>	<b>No connector configurations or connector port found for component: {0}</b>
<b>Explanation</b>	Expected data is missing for the specified component.
<b>Action</b>	Provide configuration for the specified component.
<b>SPMOGIE0045</b>	<b>Cannot start "{0}" profile in debug mode without debug port configuration.</b>
<b>Explanation</b>	It is possible that wrong data exists inside the cplm.xml file.
<b>Action</b>	Escape single quote with another single quote.
<b>SPMOGIE0046</b>	<b>Cannot start "{0}" profile in debug mode because the debug port configuration is disabled.</b>
<b>Explanation</b>	It is possible that wrong data exists inside the cplm.xml file.
<b>Action</b>	Escape single quote with another single quote.

---

<b>SPMOGIE0048</b>	<b>Exception occurred while obtaining port configurations for profile "{0}".</b>
<b>Explanation</b>	A problem occurred while reading profile port configurations.
<b>Action</b>	Check profile port configurations for errors.
<b>SPMOGIE0050</b>	<b>{0} cannot be null.</b>
<b>Explanation</b>	{0} cannot be null.
<b>Action</b>	Make sure the parameter is not null.
<b>SPMOGIE0051</b>	<b>{0} must begin with {1}</b>
<b>Explanation</b>	{0} must begin with {1}
<b>Action</b>	Make sure {0} begins with {1}.
<b>SPMOGIE0055</b>	<b>A log configuration not found: {0}</b>
<b>Explanation</b>	A log configuration was not found.
<b>Action</b>	Check your configuration instance path.
<b>SPMOGIE0056</b>	<b>Could not retrieve parent runtime component with id {0} for child runtime component with id {1}.</b>
<b>Explanation</b>	An error occurred while obtaining information for the runtime component.
<b>Action</b>	Check if the runtime component is online and at least one enabled JMX port configuration is available.
<b>SPMOGIE0057</b>	<b>Could not get JMXConnector for a runtime component of category {0}. Runtime component id is {1}.</b>
<b>Explanation</b>	An error occurred while obtaining information for the runtime component.
<b>Action</b>	Check if the runtime component is online and at least one enabled JMX port configuration is available.
<b>SPMOGIE0058</b>	<b>Could not get JMXConnector because no JMX port configuration is available for runtime component with id {0}.</b>
<b>Explanation</b>	An error occurred while obtaining information for the runtime component.
<b>Action</b>	Check if the runtime component is online and at least one enabled JMX port configuration is available.

<b>SPMOGIE0059</b>	<b>Could not get JMXConnector for runtime component with id {0} because none of the configured JMX ports is open.</b>
<b>Explanation</b>	An error occurred while obtaining information for the runtime component.
<b>Action</b>	Check if the runtime component is online and at least one enabled JMX port configuration is available.
<b>SPMOGIE0060</b>	<b>Could not get SubsystemMBean for a runtime component of a type different than ENGINE. Category : {0}, runtime component id : {1}</b>
<b>Explanation</b>	An error occurred while obtaining information for the runtime component.
<b>Action</b>	Check if the runtime component is online and at least one enabled JMX port configuration is available.
<b>SPMOGIE0061</b>	<b>No subsystem with id {0} is found for runtime component with id {1}.</b>
<b>Explanation</b>	An error occurred while obtaining information for the runtime component.
<b>Action</b>	Check if the runtime component is online and at least one enabled JMX port configuration is available.
<b>SPMOGIE0062</b>	<b>Exactly one subsystem is expected for runtime component with id {0}.</b>
<b>Explanation</b>	Exactly one subsystem is expected for the given runtime component.
<b>Action</b>	Make sure there is exactly one subsystem specified for runtime component.
<b>SPMOGIE0064</b>	<b>Executing "{0}" lifecycle operation shell script "{1}" returned non-zero exit code: {2}.</b>
<b>Explanation</b>	Non-zero exit code indicates an error.
<b>Action</b>	Check the product and Platform Manager logs for more details. Try to execute the script from the command line.
<b>SPMOGIE0065</b>	<b>Cannot start "{0}" profile in debug mode because the configured debug port is already in use.</b>
<b>Explanation</b>	Another application is started using the same port number.
<b>Action</b>	Stop the other product using the same port for debug mode.
<b>SPMOGIE0066</b>	<b>Platform Manager is unable to find configuration instances for the runtime component with ID: "{0}". "{1}" is either not existing or is not a directory.</b>
<b>Explanation</b>	No configuration instances were found in the listed location.
<b>Action</b>	Check if the location is configured correctly in the config.ini file.

---

<b>SPMOGIE0067</b>	<b>Platform Manager is unable to find configuration instances for the runtime component with ID: "{0}". "{1}" is empty.</b>
<b>Explanation</b>	Platform Manager is unable to find configuration instances for the runtime component. This folder should contain the profile-related folders and files for the specified runtime component. The path is configured in the config.ini file.
<b>Action</b>	Check if this folder is empty.
<b>SPMOGIE0070</b>	<b>Error while getting runtime status.</b>
<b>Explanation</b>	A problem occurred while obtaining data from an Engine.
<b>Action</b>	Check if the connection and credentials are OK.
<b>SPMOGIE0081</b>	<b>"{0}" operation failed for runtime component with id {1}. Reason:{2}</b>
<b>Explanation</b>	Executing operation against engine failed.
<b>Action</b>	Check JMX credentials and properties for this engine.
<b>SPMOGIE0090</b>	<b>No alias provided for the port configuration.</b>
<b>Explanation</b>	Providing a value for the alias during the creation of the port configuration is required.
<b>Action</b>	Specify an alias for the port configuration.
<b>SPMOGIE0091</b>	<b>The provided port alias is not URL friendly.</b>
<b>Explanation</b>	The provided port alias contains symbols that are not URL friendly.
<b>Action</b>	Provide only URL friendly symbols for the port alias.
<b>SPMOGIE0092</b>	<b>Failed to construct the Configuration Instance ID.</b>
<b>Explanation</b>	Platform Manager failed to construct the Configuration Instance ID.
<b>Action</b>	Check the configuration file for this instance.
<b>SPMOGIE0093</b>	<b>Missing common port alias. This configuration will be ignored.</b>
<b>Explanation</b>	The common port alias is missing and the configuration will be ignored.
<b>Action</b>	Provide an alias for this port configuration.

<b>SPMOGIE0094</b>	<b>Failed to construct the configuration instance.</b>
<b>Explanation</b>	Platform Manager failed to construct the configuration instance.
<b>Action</b>	Provide valid configuration data.
<b>SPMOGIE0096</b>	<b>Cannot read config.ini file for RuntimeComponent with ID {0}. Fall back on default product: {1}.</b>
<b>Explanation</b>	Cannot retrieve the parent product for the specified run-time component because an error occurred while reading the corresponding config.ini file. The default product will be used instead.
<b>Action</b>	Check if the config.ini is a valid properties file.
<b>SPMOGIW0001</b>	<b>Could not pass the validating schema. The "cplm" file will not be validated.</b>
<b>Explanation</b>	File called cplm.xml does not contain expected metadata.
<b>Action</b>	Check profile folder files called cplm.xml for errors.
<b>SPMOGIW0028</b>	<b>Unable to find configuration instances for the runtime component with ID: "{0}". "{1}" is empty.</b>
<b>Explanation</b>	This folder should contain the configuration properties files for the specified runtime component. The path is configured in the config.ini file.
<b>Action</b>	Check if this folder should be empty.
<b>SPMOGIW0054</b>	<b>Could not retrieve engines for runtime component with id : {0}.</b>
<b>Explanation</b>	Most likely the component with the specified ID was offline.
<b>Action</b>	Check if the runtime component is online and at least one enabled JMX port configuration is available.
<b>SPMPROE0003</b>	<b>Script failed with status {0}</b>
<b>Explanation</b>	A fix script job failed with indicated status.
<b>Action</b>	Refer to the Software AG Update Manager log for more information.
<b>SPMPROE0004</b>	<b>Install fixes is not supported.</b>
<b>Explanation</b>	The requested feature is not supported yet.
<b>Action</b>	Use the runscript method to install fixes.

---

<b>SPMPROE0005</b>	<b>Nothing to install.</b>
<b>Explanation</b>	None of the artifacts exist in the specified repository.
<b>Action</b>	Use different artifacts or install from a different repository.
<b>SPMPROE0006</b>	<b>Install from local repository not supported.</b>
<b>Explanation</b>	The feature is not yet supported.
<b>Action</b>	Export artifacts from the repository into an image archive and install from the archive.
<b>SPMPROE0007</b>	<b>No repository found for {0}</b>
<b>Explanation</b>	The specified repository does not exist.
<b>Action</b>	Create the repository or use a different one.
<b>SPMPROE0008</b>	<b>Install from remote repository is not supported.</b>
<b>Explanation</b>	Installing from a remote repository is not supported.
<b>Action</b>	Create an image archive using installer client, and install from the archive.
<b>SPMPROE0009</b>	<b>Unable to process fix script.</b>
<b>Explanation</b>	Failures occurred processing a fix script.
<b>Action</b>	See the Software AG Update Manager logs and exception for failure details.
<b>SPMPROE0010</b>	<b>Invalid Type: {0}</b>
<b>Explanation</b>	The type of script is unrecognized. Valid types are either product, or fix.
<b>Action</b>	Use product or fix as the script type.
<b>SPMPROE0011</b>	<b>Uninstall of fixes is not supported by the uninstall method.</b>
<b>Explanation</b>	The operation is not supported.
<b>Action</b>	Use runscript to remove fixes.
<b>SPMPROE0012</b>	<b>Invalid artifact type: {0}</b>
<b>Explanation</b>	The artifact was not a product or fix artifact.
<b>Action</b>	Use a valid artifact.

<b>SPMPROE0013</b>	<b>Script failed with exit code {0}. See log at {1} for more information.</b>
<b>Explanation</b>	An installation script failed.
<b>Action</b>	Refer to the log for more details on the failure.
<b>SPMPROE0014</b>	<b>The provided configuration does not include the <code>com.softwareag.plm.spm.provisioning.pathtosum</code> property.</b>
<b>Explanation</b>	The property must be specified in the configuration.
<b>Action</b>	Include a <code>com.softwareag.plm.spm.provisioning.pathtosum</code> property setting that references the Software AG Update Manager installation directory.
<b>SPMPROE0016</b>	<b>The <code>com.softwareag.plm.spm.provisioning.pathtosum</code> property does not reference an existing directory.</b>
<b>Explanation</b>	The property must reference the installation directory of Software AG Update Manager.
<b>Action</b>	Specify a valid directory.
<b>SPMPROE0018</b>	<b>Removal of ProvisioningService configuration is not supported.</b>
<b>Explanation</b>	The ProvisioningService requires a configuration.
<b>Action</b>	None required.
<b>SPMPROE0020</b>	<b>No such repository, {0}</b>
<b>Explanation</b>	The install request specified a nonexistent repository.
<b>Action</b>	Specify a valid repository ID.
<b>SPMPROE0021</b>	<b>No matching products to uninstall.</b>
<b>Explanation</b>	The uninstall request specified products that are not installed.
<b>Action</b>	Ensure that the correct product list or managed node is included in the request.
<b>SPMPROE0022</b>	<b>{0} is not in repository {1} or the required products {2} are not installed.</b>
<b>Explanation</b>	The fix cannot be installed because it does not reside in the source repository or required products are not installed.
<b>Action</b>	Specify a different fix repository. Verify with Update Manager if the fix can be resolved.

---

<b>SPMPROE0023</b>	<b>Multiple fixes with id, {0}, reside in the repository {1}</b>
<b>Explanation</b>	Platform Manager cannot determine which fix version to install.
<b>Action</b>	Specify a complete version number for the fix (<fixname>_<version>).
<b>SPMPROE0024</b>	<b>Script failed with exit code {0};{1}. See log at {2} for more details.</b>
<b>Explanation</b>	The execution of the script failed.
<b>Action</b>	Rerun script after resolving the errors listed in the log.
<b>SPMPROE0025</b>	<b>Script failed with status {0}: {1}</b>
<b>Explanation</b>	The execution of the fix script failed.
<b>Action</b>	Rerun the script after resolving the errors.
<b>SPMPROE0026</b>	<b>Unrecognized repository type: {0}</b>
<b>Explanation</b>	The repository is not a supported type.
<b>Action</b>	Use a valid repository type.
<b>SPMPROE0027</b>	<b>Unsupported repository. Use P2 enabled repository for provisioning artifacts.</b>
<b>Explanation</b>	Only P2 enabled repositories are supported.
<b>Action</b>	Use a P2 enabled repository for provisioning artifacts.
<b>SPMPROE0028</b>	<b>Artifact with id "{0}" and version "{1}" not found in the repositories {2}</b>
<b>Explanation</b>	The repositories do not contain any of the desired artifacts.
<b>Action</b>	Check the template and repository definitions.
<b>SPMPROE0030</b>	<b>Platform Manager restart failed.</b>
<b>Explanation</b>	The attempt at restarting Platform Manager failed.
<b>Action</b>	Check the Platform Manager logs.
<b>SPMPROE0031</b>	<b>Failed detecting Platform Manager Components.</b>
<b>Explanation</b>	The attempt to identify whether Platform Manager components (for example, the product plug-ins) are about to be provisioned has failed.
<b>Action</b>	Check the Platform Manager logs.

<b>SPMPROE0032</b>	<b>Platform Manager will be restarted.</b>
<b>Explanation</b>	Platform Manager will be restarted because Platform Manager components have been installed.
<b>Action</b>	Wait for Platform Manager to start. Check the logs for more details.
<b>SPMPROI0000</b>	<b>Fix installation completed with exit code: {0}</b>
<b>Explanation</b>	The fix script has completed with the indicated exit status.
<b>Action</b>	If status is nonzero, review the Software AG Update Manager logs for possible problems.
<b>SPMPROI0001</b>	<b>Launching: {0}</b>
<b>Explanation</b>	A fix script is being started in a separate process. The specific shell command is included in the message.
<b>Action</b>	None required.
<b>SPMPROI0002</b>	<b>Failed to launch fix script.</b>
<b>Explanation</b>	A script could not be launched. The associated job will be given an error status.
<b>Action</b>	Refer to the exception included in the message to resolve the problem.
<b>SPMPROW0029</b>	<b>{0} is not in repository {1} or the required products are not installed.</b>
<b>Explanation</b>	The fix cannot be installed because it does not reside in the source repository or required products are not installed.
<b>Action</b>	Specify a different fix repository. Verify with Update Manager if the fix can be resolved.
<b>SPMREPE0000</b>	<b>Unsupported operation.</b>
<b>Explanation</b>	The getContent operation is not supported for fix images.
<b>Action</b>	Use UpdateManager to view fixes.
<b>SPMREPE0001</b>	<b>Unsupported operation.</b>
<b>Explanation</b>	The import operation is only supported on local product repositories.
<b>Action</b>	None required.

---

<b>SPMREPE0002</b>	<b>Invalid configuration detected for repository, {0}</b>
<b>Explanation</b>	The location property of the repository is invalid. The configuration refers to a fix image, which must be a local file.
<b>Action</b>	Delete the configuration.
<b>SPMREPE0003</b>	<b>Repository not found at {0} for configuration, {1}</b>
<b>Explanation</b>	A configuration was found for a fix image repository that does not exist.
<b>Action</b>	Remove the configuration.
<b>SPMREPE0004</b>	<b>Unsupported operation.</b>
<b>Explanation</b>	The export operation is not supported for this artifact type or repository.
<b>Action</b>	None required.
<b>SPMREPE0005</b>	<b>Unsupported operation.</b>
<b>Explanation</b>	The repository type does not support dependencies.
<b>Action</b>	None required.
<b>SPMREPE0006</b>	<b>Unsupported operations.</b>
<b>Explanation</b>	Publishing is not supported for this repository type.
<b>Action</b>	None required.
<b>SPMREPE0007</b>	<b>Unable to parse canonical in {1}: {0}</b>
<b>Explanation</b>	The product properties could not be processed. The file is not a valid image archive.
<b>Action</b>	Use a valid image archive.
<b>SPMREPE0008</b>	<b>Importing of artifacts into an image archive is not supported.</b>
<b>Explanation</b>	Importing artifacts into an image archive is not supported.
<b>Action</b>	To create an image archive, use the export feature.
<b>SPMREPE0009</b>	<b>URI scheme for image archive repository, {0}, must be file</b>
<b>Explanation</b>	The repository configuration is invalid.
<b>Action</b>	Specify a local file as the archive location.

<b>SPMREPE0010</b>	<b>Repository not found at {0}</b>
<b>Explanation</b>	There is no archive at the specified location.
<b>Action</b>	Specify a valid location for the archive.
<b>SPMREPE0011</b>	<b>Exporting from images is not supported.</b>
<b>Explanation</b>	The function is not supported.
<b>Action</b>	None required.
<b>SPMREPE0012</b>	<b>Dependencies not available for image archives.</b>
<b>Explanation</b>	The function is not supported.
<b>Action</b>	Non required.
<b>SPMREPE0013</b>	<b>Publish feature is not supported for image archives.</b>
<b>Explanation</b>	Only local repositories may be published.
<b>Action</b>	None required.
<b>SPMREPE0016</b>	<b>Platform Manager cannot list product or fix repositories of release 9.7 or earlier.</b>
<b>Explanation</b>	The listing of product or fix repositories is not supported for releases 9.7 or earlier.
<b>Action</b>	Start the Software AG Installer and select the release that includes the products you want to see, or start the Software AG Update Manager and select the release and products that include the fixes you want to see.
<b>SPMREPE0017</b>	<b>Sandboxes are not modifiable.</b>
<b>Explanation</b>	Importing into sandboxes is not supported.
<b>Action</b>	None required.
<b>SPMREPE0018</b>	<b>Exporting from sandboxes is not supported.</b>
<b>Explanation</b>	The function is not supported.
<b>Action</b>	Use the installer client to export images from legacy sandboxes.
<b>SPMREPE0019</b>	<b>Dependencies not available for sandboxes.</b>
<b>Explanation</b>	The function is not supported.
<b>Action</b>	Use installer client to interact with legacy sandboxes.

---

<b>SPMREPE0020</b>	<b>Only local repositories can be published.</b>
<b>Explanation</b>	Sandboxes cannot be published.
<b>Action</b>	None required.
<b>SPMREPE0021</b>	<b>Unable to load/create repository at {0}</b>
<b>Explanation</b>	Platform Manager was not able to read the repository content.
<b>Action</b>	See to logs for more information. The repository may have been corrupted.
<b>SPMREPE0024</b>	<b>Unable to verify archive: {0} due to {1}</b>
<b>Explanation</b>	The file could not be verified as a ZIP archive.
<b>Action</b>	Ensure the path to the archive is correct.
<b>SPMREPE0025</b>	<b>The specified file {0} is not a valid image file.</b>
<b>Action</b>	To validate a product image, open the Software AG Installer and go to Advanced Options > Images. If necessary, re-create the {product   fix} image using the instructions in Using the Software AG Installer (product image) or Using the Software AG Update Manager (fix image), and then try again.
<b>SPMREPE0026</b>	<b>Local repository, {0}, has an invalid location: {1}</b>
<b>Explanation</b>	The repository configuration is invalid.
<b>Action</b>	Delete the configuration.
<b>SPMREPE0027</b>	<b>Unable to create repository at {0}</b>
<b>Explanation</b>	The repository could not be created.
<b>Action</b>	See the logs for more information.
<b>SPMREPE0028</b>	<b>Exporting of fixes is not supported.</b>
<b>Explanation</b>	The function is not supported.
<b>Action</b>	Use Software AG Update Manager to export fixes.
<b>SPMREPE0037</b>	<b>Unsupported operation.</b>
<b>Explanation</b>	getContent is not supported for remote fix repositories.
<b>Action</b>	Use Software AG Update Manager to view repository content.

<b>SPMREPE0038</b>	<b>Unsupported operation.</b>
<b>Explanation</b>	Import is not supported for remote fix repositories.
<b>Action</b>	Use Software AG Update Manager to manage fix repositories.
<b>SPMREPE0039</b>	<b>Unsupported operation.</b>
<b>Explanation</b>	Export is not supported for remote fix repositories.
<b>Action</b>	Use Software AG Update Manager to manage fix repositories.
<b>SPMREPE0040</b>	<b>Unsupported operation.</b>
<b>Explanation</b>	Dependencies not supported for remote fix repositories.
<b>Action</b>	Use Software AG Update Manager to manage fix repositories.
<b>SPMREPE0041</b>	<b>Unsupported operation.</b>
<b>Explanation</b>	Publish is not supported for remote fix repositories.
<b>Action</b>	Use Software AG Update Manager to manage fix repositories.
<b>SPMREPE0042</b>	<b>Unable to access SD Security Service.</b>
<b>Explanation</b>	The security service used to access remote repositories is not available.
<b>Action</b>	Try to restart the security service.
<b>SPMREPE0043</b>	<b>Unable to obtain security token for user, {0}, for the {1} repository.</b>
<b>Explanation</b>	The attempt to login to the SD security service failed.
<b>Action</b>	Ensure correct credentials are set for the repository.
<b>SPMREPE0044</b>	<b>Unable to load remote repository, {0}, due to {1}</b>
<b>Explanation</b>	A failure was detected attempting to access the repository.
<b>Action</b>	See the logs for more information.
<b>SPMREPE0045</b>	<b>Unsupported operation.</b>
<b>Explanation</b>	Importing into a remote repository is not supported.
<b>Action</b>	None required.

---

<b>SPMREPE0047</b>	<b>Unsupported operation.</b>
<b>Explanation</b>	Exporting from a remote repository is not supported.
<b>Action</b>	Import the artifacts into a local repository, then export from the local repository.
<b>SPMREPE0048</b>	<b>Unsupported operation.</b>
<b>Explanation</b>	Publish is not supported for remote repositories. They are already published.
<b>Action</b>	None required.
<b>SPMREPE0049</b>	<b>{0} not found in repository.</b>
<b>Explanation</b>	The specified artifact does not exist in the repository.
<b>Action</b>	Verify that the correct artifact is used.
<b>SPMREPE0050</b>	<b>Unable to list repositories.</b>
<b>Explanation</b>	Failures occurred while reading repository configuration.
<b>Action</b>	Ensure read access is provided for repositories defined in the SPM profile.
<b>SPMREPE0051</b>	<b>Unable to list repositories.</b>
<b>Explanation</b>	Failures occurred while reading repository configuration.
<b>Action</b>	Ensure read access is provided for the repositories defined in the SPM profile.
<b>SPMREPE0053</b>	<b>Location can not be null.</b>
<b>Explanation</b>	When adding a new repository configuration, the location property must be provided.
<b>Action</b>	Provide a location for the repository being configured.
<b>SPMREPE0054</b>	<b>Invalid content type: {0}</b>
<b>Explanation</b>	The type of a repository must be either product or fix.
<b>Action</b>	Provide a valid repository type.
<b>SPMREPE0055</b>	<b>Repository already configured for {0}</b>
<b>Explanation</b>	A repository at this location is already configured.
<b>Action</b>	None required.

<b>SPMREPE0057</b>	<b>{0} is an invalid path.</b>
<b>Explanation</b>	The location cannot be represented as a valid URI.
<b>Action</b>	Use a valid path.
<b>SPMREPE0058</b>	<b>Location does not exist: {0}</b>
<b>Explanation</b>	There is no fix image archive at the specified location.
<b>Action</b>	Provide the location of an existing fix image archive.
<b>SPMREPE0062</b>	<b>Unable to delete configuration properties: {0}</b>
<b>Explanation</b>	The configuration properties for a repository could not be deleted.
<b>Action</b>	Manually delete the property file.
<b>SPMREPE0064</b>	<b>Must specify repository type.</b>
<b>Explanation</b>	The type argument for listing repositories cannot be null.
<b>Action</b>	Specify the repository type, either product or fix.
<b>SPMREPE0065</b>	<b>No such repository - {0}</b>
<b>Explanation</b>	There is no repository with the given ID.
<b>Action</b>	Use a known repository configuration.
<b>SPMREPE0066</b>	<b>Source and destination arguments cannot be null.</b>
<b>Explanation</b>	Both source and destination arguments must be specified for the import operation.
<b>Action</b>	Provide valid source and destination repository arguments.
<b>SPMREPE0067</b>	<b>No such repository registered, {0}</b>
<b>Explanation</b>	The source repository for the import operation does not exist.
<b>Action</b>	Provide a valid source repository argument.
<b>SPMREPE0068</b>	<b>No such repository registered, {0}</b>
<b>Explanation</b>	The destination repository for the import operation does not exist.
<b>Action</b>	Provide a valide destination repository.

---

<b>SPMREPE0069</b>	<b>Incompatible repositories.</b>
<b>Explanation</b>	The source and destination repositories must have the same content type.
<b>Action</b>	Ensure that both repositories are either product, or fix repositories.
<b>SPMREPE0070</b>	<b>Cannot import into remote repository, {0}</b>
<b>Explanation</b>	Importing into remote repositories is not supported.
<b>Action</b>	Specify a local repository as the destination.
<b>SPMREPE0071</b>	<b>Unable to create path to provisioning configuration: {0}</b>
<b>Explanation</b>	Unable to create provisioning configuration directory.
<b>Action</b>	Ensure that the Platform Manager configuration directory is writable.
<b>SPMREPE0072</b>	<b>Invalid repository type: {0}</b>
<b>Explanation</b>	The repository type must be product or fix.
<b>Action</b>	Specify a valid repository type.
<b>SPMREPE0073</b>	<b>No repository name provided.</b>
<b>Explanation</b>	A repository name must be provided for discovering fix repositories.
<b>Action</b>	Provide the repository name.
<b>SPMREPE0074</b>	<b>Invalid server or repository name: {0}</b>
<b>Explanation</b>	The server or name arguments contain invalid characters for a URL.
<b>Action</b>	Specify valid server and names for the fix repository.
<b>SPMREPE0075</b>	<b>Repository discovery failed: No ProductRepositoryManagementService available</b>
<b>Explanation</b>	Unable to discover product repositories as the necessary services are not active.
<b>Action</b>	See the logs to determine why the repository manager service is inactive.
<b>SPMREPE0076</b>	<b>Cannot connect to Software AG repository: {0}</b>
<b>Action</b>	Make sure the Platform Manager has Internet access and the proxy configuration is present and correct. You can also check the logs for the Platform Manager. Then try again to connect.

<b>SPMREPE0077</b>	<b>Source repository cannot be null.</b>
<b>Explanation</b>	A source repository must be specified for the export operation.
<b>Action</b>	Specify the local repository to use for export.
<b>SPMREPE0078</b>	<b>Path cannot be null.</b>
<b>Explanation</b>	The path to the destination archive must be specified for the export operation.
<b>Action</b>	Provide a path where the archive should be created.
<b>SPMREPE0079</b>	<b>No such repository registered, {0}</b>
<b>Explanation</b>	There is no repository with the given ID.
<b>Action</b>	Specify a valid source repository.
<b>SPMREPE0080</b>	<b>Unsupported operation.</b>
<b>Explanation</b>	Platform Manager cannot export from archive.
<b>Action</b>	Specify a local repository from which to export.
<b>SPMREPE0081</b>	<b>Cannot export into existing file: {0}</b>
<b>Explanation</b>	Exporting cannot be used to add to an existing archive.
<b>Action</b>	Specify the location to create a new archive.
<b>SPMREPE0082</b>	<b>Artifact must be specified.</b>
<b>Explanation</b>	An artifact argument for get dependencies was null.
<b>Action</b>	Specify the artifact for its list of dependencies.
<b>SPMREPE0083</b>	<b>Source repository cannot be null.</b>
<b>Explanation</b>	The source repository for get dependencies cannot be null.
<b>Action</b>	Specify a valid repository in which to search for dependencies.
<b>SPMREPE0084</b>	<b>No such repository registered, {0}</b>
<b>Explanation</b>	The specified repository does not exist.
<b>Action</b>	Specify a valid repository in which to search for dependencies.

---

<b>SPMREPE0085</b>	<b>No such repository: {0}</b>
<b>Explanation</b>	The specified repository does not exist.
<b>Action</b>	Specify a valid local repository to publish.
<b>SPMREPE0086</b>	<b>Source and destination repositories are the same.</b>
<b>Explanation</b>	The source and destination repositories must refer to different repositories.
<b>Action</b>	Specify valid repositories.
<b>SPMREPE0087</b>	<b>{0} not found in repository.</b>
<b>Explanation</b>	The specified artifact does not exist in the repository.
<b>Action</b>	Verify that the correct artifact is used.
<b>SPMREPE0088</b>	<b>Unsupported operation.</b>
<b>Explanation</b>	The publishing of local repositories is not supported in this release.
<b>Action</b>	None required.
<b>SPMREPE0089</b>	<b>Unsupported operation.</b>
<b>Explanation</b>	The unpublish operation is not supported for repository type.
<b>Action</b>	None required.
<b>SPMREPE0090</b>	<b>No such repository registered, {0}</b>
<b>Explanation</b>	The specified repository is not registered.
<b>Action</b>	Specify a valid repository, or add the repository.
<b>SPMREPE0091</b>	<b>Failures occurred attempting to publish a repository: {0}</b>
<b>Explanation</b>	Internal errors prevented the publish operation from completing.
<b>Action</b>	Depends on the specific error. Check the logs for the error details.
<b>SPMREPE0092</b>	<b>The repository, {0}, is already published with context, {1}</b>
<b>Explanation</b>	Specify the correct repository or republish to use a different context.
<b>Action</b>	To change context, unpublish, then republish with new context.

<b>SPMREPE0093</b>	<b>Web publishing service is unavailable.</b>
<b>Explanation</b>	The necessary service to publish repositories is not active.
<b>Action</b>	None required.
<b>SPMREPE0094</b>	<b>Invalid context: {0}</b>
<b>Explanation</b>	The context in the publish request may not be null and must start with /
<b>Action</b>	Check if the context of the publish request is null and verify that it starts with /
<b>SPMREPE0095</b>	<b>Invalid context: {0}</b>
<b>Explanation</b>	The context must not be null and start with /
<b>Action</b>	Use a valid context.
<b>SPMREPE0096</b>	<b>Repository {0}, is not published.</b>
<b>Explanation</b>	The request assumes the repository has been published.
<b>Action</b>	None required.
<b>SPMREPE0097</b>	<b>Failures detected while unpublishing repository: {0}</b>
<b>Explanation</b>	The unpublishing operation failed.
<b>Action</b>	Depends on the type of failure. Check the logs for the error details.
<b>SPMREPE0098</b>	<b>No credentials for accessing the remote fix repository, {0}, have been configured.</b>
<b>Explanation</b>	You must provide user credentials to access remote repositories.
<b>Action</b>	Specify the user and password properties for the repository.
<b>SPMREPE0099</b>	<b>The location of a repository is invalid: {0}</b>
<b>Explanation</b>	The URI of a repository does not have a valid path.
<b>Action</b>	Specify a valid location when registering repositories.
<b>SPMREPE0100</b>	<b>No repository found at the specified location: {0}</b>
<b>Explanation</b>	The location specified did not match any known repository.
<b>Action</b>	Specify a valid location.

---

<b>SPMREPE0101</b>	<b>No fix service available.</b>
<b>Explanation</b>	A required service for managing fix repositories is unavailable.
<b>Action</b>	Review the Platform Manager logs for indications of fix service failures.
<b>SPMREPE0103</b>	<b>{0} is an invalid path. It must be relative.</b>
<b>Explanation</b>	To create a new local repository, you must use only relative paths.
<b>Action</b>	Specify a relative path.
<b>SPMREPE0104</b>	<b>Login to repository, {1}, failed for user, {0},</b>
<b>Explanation</b>	Repository configured with incorrect credentials.
<b>Action</b>	Reconfigure the repository credentials.
<b>SPMREPE0105</b>	<b>Only one platform may be specified in the provided filter .</b>
<b>Explanation</b>	The repository operation included a filter with multiple platforms.
<b>Action</b>	Specify only one platform in the filter and retry the operation.
<b>SPMREPE0106</b>	<b>The repository, {0}, is currently in use.</b>
<b>Explanation</b>	The operation cannot be processed until the specified repository becomes available.
<b>Action</b>	Retry when all provisioning operations are completed.
<b>SPMREPE0107</b>	<b>Failed to load repository, {0}</b>
<b>Explanation</b>	An error occurred while attempting to access the repository.
<b>Action</b>	Check the logs for the error details.
<b>SPMREPE0108</b>	<b>Publish with non-default realm or roles is not supported.</b>
<b>Explanation</b>	The requested operation is not supported.
<b>Action</b>	Retry the request without specifying a realm or roles.
<b>SPMREPE0109</b>	<b>{0} is not in repository {1}</b>
<b>Explanation</b>	Unable to export the specified fix into the archive because the fix does not reside in the source repository.
<b>Action</b>	Specify a different fix or repository.

<b>SPMREPE0110</b>	<b>Invalid SDC installer properties.</b>
<b>Explanation</b>	The servers/production/versions property in the server.properties file is missing.
<b>Action</b>	This is an internal error and should be reported. Contact Software AG Global Support.
<b>SPMREPE0111</b>	<b>No such repository, {0}</b>
<b>Explanation</b>	The specified repository is not registered.
<b>Action</b>	Specify an valid repository, or create one.
<b>SPMREPE0112</b>	<b>Unsupported operation.</b>
<b>Explanation</b>	The getReadme operation is not supported by the repository.
<b>Action</b>	Specify an appropriate repository.
<b>SPMREPE0113</b>	<b>Unable to load remote repository {0}. The server returned null result.</b>
<b>Explanation</b>	The attempt to load to the specified remote repository failed.
<b>Action</b>	Ensure that the correct repository metadata is provided and try again.
<b>SPMREPE0114</b>	<b>Update Manager threw unexpected exception: {0}.</b>
<b>Explanation</b>	Update Manager threw unexpected exception: {0}.
<b>Action</b>	Check the Update Manager installation.
<b>SPMREPE0115</b>	<b>Login failed for user: {0} and location: {1}</b>
<b>Explanation</b>	The login operation failed for user: {0} and location: {1}
<b>Action</b>	Provide valid credentials and valid repository location.
<b>SPMREPE0116</b>	<b>The Repository Validation parameter should not be null.</b>
<b>Explanation</b>	The Repository Validation parameter should not be null.
<b>Action</b>	Provide a valid (not null) Repository Validation parameter.
<b>SPMREPE0117</b>	<b>The repository path should not be empty.</b>
<b>Explanation</b>	The repository path should not be empty.
<b>Action</b>	Provide a valid non-empty repository path.

---

<b>SPMREPE0118</b>	<b>The provided username or password should not be empty.</b>
<b>Explanation</b>	The username or password should not be empty.
<b>Action</b>	Provide non-empty valid username or password.
<b>SPMREPE0119</b>	<b>Fixes repository validation failed.</b>
<b>Explanation</b>	The fixes repository validation failed.
<b>Action</b>	Analyze the error and provide valid input.
<b>SPMREPE0120</b>	<b>Products repository validation failed.</b>
<b>Explanation</b>	The products repository validation failed.
<b>Action</b>	Analyze the error and provide valid input.
<b>SPMREPE0121</b>	<b>Trusted authentication failed while trying to log in {0} repository.</b>
<b>Explanation</b>	Connecting to the specified repository using trusted authentication failed.
<b>Action</b>	See the Platform Manager wrapper log for more details.
<b>SPMREPE0122</b>	<b>Repository {0} not found.</b>
<b>Explanation</b>	The specified repository is not registered.
<b>Action</b>	Check the repository name or register a repository with the same name.
<b>SPMREPI0014</b>	<b>Importing into {0}</b>
<b>Explanation</b>	Importing of artifacts is starting.
<b>Action</b>	None required.
<b>SPMREPI0015</b>	<b>Import failed: {0}</b>
<b>Explanation</b>	An import operation failed.
<b>Action</b>	See the installation log for more information.
<b>SPMREPI0023</b>	<b>Creating local repository at {0}</b>
<b>Explanation</b>	A new local repository is being created.
<b>Action</b>	None required.

<b>SPMREPI0029</b>	<b>No matching products found in {0} repository</b>
<b>Explanation</b>	The request to mirror a repository is ignored as none of the specified artifacts reside in the repository.
<b>Action</b>	None required.
<b>SPMREPI0030</b>	<b>Import from {0} to {1} failed.</b>
<b>Explanation</b>	The import operation failed.
<b>Action</b>	See the logs for more information.
<b>SPMREPI0031</b>	<b>Importing all products from {0} to {1}</b>
<b>Explanation</b>	All products in the source repository will be imported.
<b>Action</b>	None required.
<b>SPMREPI0032</b>	<b>Importing products fro {0} to {1}</b>
<b>Explanation</b>	A subset of products is being imported. The specific products are listed as subsequent log entries.
<b>Action</b>	None required.
<b>SPMREPI0033</b>	<b>{0}</b>
<b>Explanation</b>	The id of a product being imported.
<b>Action</b>	None required.
<b>SPMREPI0034</b>	<b>Import from {0} to {1} was successful.</b>
<b>Explanation</b>	The import operation completed successfully..
<b>Action</b>	None required.
<b>SPMREPI0035</b>	<b>Exporting artifacts from {0} to {1}</b>
<b>Explanation</b>	An export operation is starting.
<b>Action</b>	None required.
<b>SPMREPI0036</b>	<b>Export from {0} to {1} failed due to {2}</b>
<b>Explanation</b>	The export operation failed.
<b>Action</b>	See the logs for more information.

---

<b>SPMREPI0056</b>	<b>The configuration of repository {0} has an invalid location property: {0}</b>
<b>Explanation</b>	The location property is not a valid URL.
<b>Action</b>	Remove the repository.
<b>SPMREPI0059</b>	<b>Unable to add repository {0}.</b>
<b>Explanation</b>	The location is an invalid URL.
<b>Action</b>	Noe required.
<b>SPMREPI0060</b>	<b>Unable to add repository {0}.</b>
<b>Explanation</b>	The attempt to configure the remote repository failed.
<b>Action</b>	See the logs for more information.
<b>SPMREPI0061</b>	<b>Failures occurred during removal of repository {0}.</b>
<b>Explanation</b>	The repository configuration may not have been completely removed.
<b>Action</b>	See the logs for further information.
<b>SPMREPI0063</b>	<b>Removed repository configuration, {0}</b>
<b>Explanation</b>	The repository was successfully removed.
<b>Action</b>	None required.
<b>SPMREPW0022</b>	<b>Unable to delete {0}</b>
<b>Explanation</b>	The directory of the local repository to be created was not empty.
<b>Action</b>	None required.
<b>SPMREPW0046</b>	<b>Failed to remove password handle for repository, {0}</b>
<b>Explanation</b>	Cleanup of passman data was incomplete while removing the repository.
<b>Action</b>	None required.
<b>SPMREPW0052</b>	<b>Unable to initialize repository {0}.</b>
<b>Explanation</b>	The repository could not be validated.
<b>Action</b>	Remove the repository configuration.

<b>SPMREPW0102</b>	<b>Failed to remove password handle for repository, {0}</b>
<b>Explanation</b>	The passman cleanup was incomplete.
<b>Action</b>	None required.
<b>SPMRMCE0001</b>	<b>Invalid input data.</b>
<b>Explanation</b>	The submitted data failed to un-marshall or validate against the schema.
<b>Action</b>	Correct the reported problem in the input data and retry the request.
<b>SPMRMCE0002</b>	<b>Internal Error processing the request.</b>
<b>Explanation</b>	The server encountered an error and cannot execute the request.
<b>Action</b>	Contact your system administrator.
<b>SPMRMCE0003</b>	<b>Invalid client request.</b>
<b>Explanation</b>	The submitted client request is rejected by the server.
<b>Action</b>	Check the status code for more details or consult the Software AG Platform Manager documentation. Correct the problem and resubmit the request.
<b>SPMRMCE0005</b>	<b>The requested functionality is not supported.</b>
<b>Explanation</b>	Platform Manager does not support the requested functionality.
<b>Action</b>	See the Software AG Platform Manager documentation for the supported requests for this resource.
<b>SPMRMCI0000</b>	<b>Configuration partial failure for runtime component: {0}, instance: {1} with type {2} - with linked exception:</b>
<b>Explanation</b>	The configuration operation for the specified run-time component, instance, and type failed with the specified exception.
<b>Action</b>	Check the logs for the error details.
<b>SPMRPIE0000</b>	<b>Use RepositoryService to create new repository configurations.</b>
<b>Explanation</b>	The ConfigurationService cannot be used to add repository configurations.
<b>Action</b>	Use the RepositoryService to configure new repositories.

---

<b>SPMRPRE0000</b>	<b>Invalid filter specification.</b>
<b>Explanation</b>	A request was made that included a product filter and the useInventory option.
<b>Action</b>	Resubmit with the appropriate filter. Use either a product list or the useInventory option, not both at the same time.
<b>SPMRPRE0001</b>	<b>No repository with id, {0}, and type, {1} exists</b>
<b>Explanation</b>	The request references a non-existent repository.
<b>Action</b>	Specify the correct repository ID and/or type.
<b>SPMSCOE0000</b>	<b>No Credentials in Data Store for handle: {0}</b>
<b>Explanation</b>	Searching for exact credentials match does not return results.
<b>Action</b>	Search again for existing credentials.
<b>SPMSCOE0001</b>	<b>No Credentials available in Secured Store for handle: {0}</b>
<b>Explanation</b>	Searching for exact credentials match does not return results.
<b>Action</b>	Search again for existing credentials.
<b>SPMSURE0000</b>	<b>Some of the required properties for retrieving a UiBinding are not provided. Please provide values for {0} and a value for one of {1}.</b>
<b>Explanation</b>	Some of the required properties for retrieving a UiBinding are not provided.
<b>Action</b>	Provide the full set of required properties.
<b>SPMSURE0002</b>	<b>Could not transfer the file to the target destination {0}. Reason: {1}.</b>
<b>Explanation</b>	The file could not be transferred due to an error.
<b>Action</b>	Check if the target host has enough disk space or the provided file name is valid.
<b>SPMSURW0001</b>	<b>Some of the required properties for retrieving a UiBinding are not provided. Provide values for {0}.</b>
<b>Explanation</b>	Some of the properties required for retrieving a UiBinding are not provided.
<b>Action</b>	Provide the full set of required properties.

<b>SPMTEME0000</b>	<b>Error occurred while reading the configuration instances for {0}</b>
<b>Explanation</b>	The error occurred while creating a template that includes configuration information.
<b>Action</b>	Check whether the configuration instances for the specified runtime component are available by querying them explicitly. Check the logs for errors if the query fails.
<b>SPMTEME0001</b>	<b>Error occurred while applying template {0}</b>
<b>Explanation</b>	The error occurred when applying the specified template.
<b>Action</b>	Check the logs for more details.
<b>SPMTEME0006</b>	<b>Error occurred during template creation {0}</b>
<b>Explanation</b>	The error occurred when creating a template.
<b>Action</b>	Check the logs for more details about the error.
<b>SPMTEME0012</b>	<b>Error occurred while executing a task with id: {0} and status: {1}</b>
<b>Explanation</b>	Executing the specified task failed.
<b>Action</b>	Check the Platform Manager logs for more information.
<b>SPMTEME0014</b>	<b>Deleting configuration instance with type {0} is not supported operation.</b>
<b>Explanation</b>	Platform Manager does not support deleting the configuration instance with the specified type.
<b>Action</b>	Check the warning to determine if any damage to the system will occur.
<b>SPMTEME0015</b>	<b>Skipping deleting configuration instance ({0}) for runtime component - {1}. Reason: {2}</b>
<b>Explanation</b>	The error occurred because either the runtime component, or a configuration manager for the configuration instance is missing in the Platform Manager.
<b>Action</b>	Check if the specified runtime component is present or that the appropriate SPM plugin is installed. Check the warning to determine if any damage to the system will occur.
<b>SPMTEME0016</b>	<b>Skipping deleting configuration instance ({0}) for the missing runtime component - {1}</b>
<b>Explanation</b>	The specified runtime component is missing in the Platform Manager.
<b>Action</b>	Check if the specified runtime component is present in the Platform Manager. Check the warning to determine if any damage to the system will occur.

---

<b>SPMTEME0017</b>	<b>Task with id: {0} and status {1} did not finish in the expected period of time.</b>
<b>Explanation</b>	The timeout period, configured through a system property, is not sufficient to complete the task.
<b>Action</b>	Try to execute the operation again or increase the timeout value.
<b>SPMTEME0018</b>	<b>Task with id: {0} and status: {1} was canceled.</b>
<b>Explanation</b>	The execution of the operation is interrupted.
<b>Action</b>	Try to execute the operation again.
<b>SPMTEME0019</b>	<b>Error occurred during execution of operation {0} on template {1}</b>
<b>Explanation</b>	The error occurred when executing the specified operation.
<b>Action</b>	Check the logs for more details about the error.
<b>SPMTEME0020</b>	<b>The repository cannot be empty.</b>
<b>Explanation</b>	A repository should be specified in order to apply the template.
<b>Action</b>	Specify a repository to be used for applying the template.
<b>SPMTEME0021</b>	<b>The required services are not initialized.</b>
<b>Explanation</b>	The services required for applying are template are not initialized.
<b>Action</b>	Check whether all required bundles are started.
<b>SPMTEME0022</b>	<b>Template alias cannot be empty.</b>
<b>Explanation</b>	Template alias must be specified when creating or applying a template.
<b>Action</b>	Specify a template alias.
<b>SPMTEME0023</b>	<b>Template metadata cannot be empty.</b>
<b>Explanation</b>	Template metadata must be specified when creating or applying a template.
<b>Action</b>	Specify template metadata.
<b>SPMTEME0024</b>	<b>Template options cannot be empty.</b>
<b>Explanation</b>	Template options should be specified when creating or applying a template.
<b>Action</b>	Specify template options.

<b>SPMTEME0025</b>	<b>The provided template or template metadata does not contain any products.</b>
<b>Explanation</b>	A request to install products is made, however, the template or the template metadata does not contain any products.
<b>Action</b>	Check whether the template operation request is correct.
<b>SPMTEME0026</b>	<b>Fix Installation properties cannot be empty.</b>
<b>Explanation</b>	Fix Installation properties cannot be empty.
<b>Action</b>	Specify fix installation properties.
<b>SPMTEME0027</b>	<b>Arguments can not be null.</b>
<b>Explanation</b>	Neither of the arguments can be null.
<b>Action</b>	Specify proper arguments.
<b>SPMTEME0028</b>	<b>The script for this template is empty.</b>
<b>Explanation</b>	The script that is used for provisioning of this template is empty.
<b>Action</b>	Provide proper arguments to ensure successful generation of the script.
<b>SPMTEME0029</b>	<b>The provided template does not have a script for the specified type.</b>
<b>Explanation</b>	The template does not support the specified provisioning operation.
<b>Action</b>	Check the template metadata for discrepancy.
<b>SPMTEME0030</b>	<b>Job cannot be null.</b>
<b>Explanation</b>	An issue occurred during a template operation.
<b>Action</b>	Contact Software AG Global Support.
<b>SPMTEME0031</b>	<b>Configuration instance {0} threw unexpected exception during processing.</b>
<b>Explanation</b>	The composite template encountered an error while processing configuration instance {0}. This behavior is to be expected in some cases, for example when the run-time component on which the configuration is applied is not up and running.
<b>Action</b>	No action required. The composite template retries the configuration operation automatically. Check the final job log after the last retry.

---

<b>SPMTEME0032</b>	<b>The thread was interrupted while waiting for runtime status.</b>
<b>Explanation</b>	During the apply template configuration operation, the checking of the runtime status of a component was interrupted.
<b>Action</b>	Check the logs for JVM errors.
<b>SPMTEME0033</b>	<b>Exception occurred while getting runtime status.</b>
<b>Explanation</b>	An exception occurred during the apply template configuration operation, when checking the runtime status of a component.
<b>Action</b>	Check the SPM logs for system errors
<b>SPMTEME0034</b>	<b>The thread was interrupted while setting runtime status.</b>
<b>Explanation</b>	During the apply template configuration operation, the checking of the runtime status of a component was interrupted.
<b>Action</b>	Check the logs for JVM errors
<b>SPMTEME0035</b>	<b>Applying template was interrupted.</b>
<b>Explanation</b>	The thread applying the template was interrupted.
<b>Action</b>	Check the logs for more details.
<b>SPMTEME0036</b>	<b>Can not retrieve the imported template: {0}</b>
<b>Explanation</b>	Platform Manager can not retrieve the imported template: {0}
<b>Action</b>	Check the imported template metadata for inconsistent entries.
<b>SPMTEME0037</b>	<b>The template file can not be deleted.</b>
<b>Explanation</b>	The template file can not be deleted.
<b>Action</b>	Ensure that the template file is not locked on the file system.
<b>SPMTEME0038</b>	<b>The provided template alias should not be null.</b>
<b>Explanation</b>	The provided template alias should not be null.
<b>Action</b>	Provide a valid, non-null template alias.

<b>SPMTEME0039</b>	<b>Can not retrieve the imported template metadata: {0}</b>
<b>Explanation</b>	Can not retrieve the imported template metadata: {0}
<b>Action</b>	Check the imported template metadata for inconsistent entries.
<b>SPMTEME0040</b>	<b>Waiting for product with Id: {0} is interrupted.</b>
<b>Explanation</b>	Waiting for product with Id: {0} is interrupted.
<b>Action</b>	Double-check the logs for more details related to this error.
<b>SPMTEME0047</b>	<b>Configuration Type {0} does not support "text/plain" representation. Use JSON or XML.</b>
<b>Explanation</b>	The configuration data contained in the template is not in the expected format.
<b>Action</b>	Change the configuration definition in the template.
<b>SPMTEME0048</b>	<b>Could not deserialize Configuration Instance {0} for Runtime Component {1} having Configuration Type {2}.</b>
<b>Explanation</b>	The Configuration Data contained in the Template is not in the expected format.
<b>Action</b>	Change the Configuration definition in the Template.
<b>SPMTEMW0002</b>	<b>Applying the template completed with the following warnings: {0}</b>
<b>Explanation</b>	When applying a template, unexpected events occurred, but they did not prevent the process from executing.
<b>Action</b>	Check the warnings with extra caution to determine whether any damage to the system will occur.
<b>SPMTEMW0003</b>	<b>Skipping creating configuration instance ({0}) for the missing runtime component - {1}</b>
<b>Explanation</b>	The specified runtime component is missing in the specified Platform Manager.
<b>Action</b>	Check if the specified runtime component is present. Check the warning to determine if any damage to the system will occur.
<b>SPMTEMW0004</b>	<b>Skipping creating configuration instance ({0}) for runtime component - {1}. Reason: {2}</b>
<b>Explanation</b>	The error occurred because either the runtime component, or a configuration manager for the configuration instance is missing in the specified Platform Manager.
<b>Action</b>	Check if the specified runtime component is present and that the appropriate Platform Manager plugin is installed. Check the warning to determine if any damage to the system will occur.

---

<b>SPMTEMW0005</b>	<b>Creating configuration instance with type {0} is not supported operation.</b>
<b>Explanation</b>	Platform Manager does not support the create operation for the configuration instance with the specified type.
<b>Action</b>	Check the warning to determine if any damage to the system will occur.
<b>SPMTEMW0007</b>	<b>Skipping updating configuration instance ({0}) for the missing runtime component - {1}</b>
<b>Explanation</b>	The specified runtime component is missing in the Platform Manager.
<b>Action</b>	Check if the specified runtime component is present. Check the warning to determine if any damage to the system will occur.
<b>SPMTEMW0008</b>	<b>Template operation "{1}" completed with the following warnings: {0}</b>
<b>Explanation</b>	During template operation "{1}" unexpected events occurred but they did not prevent the operation from completing.
<b>Action</b>	Check the warnings to figure out what was successfully processed as part of operation "{1}".
<b>SPMTEMW0009</b>	<b>Skipping updating configuration instance ({0}) for runtime component - {1}. Reason: {2}</b>
<b>Explanation</b>	The error occurred because either the runtime component, or a configuration manager for the configuration instance is missing in the Platform Manager.
<b>Action</b>	Check if the specified runtime component is present or that the appropriate Platform Manager plugin is installed. Check the warning to determine if any damage to the system will occur.
<b>SPMTEMW0010</b>	<b>Skipping storage of item with id : {0} . Reason : {1}</b>
<b>Explanation</b>	The issue occurred during item serialization.
<b>Action</b>	Check the Platform Manager logs for more information about the error.
<b>SPMTEMW0011</b>	<b>Updating configuration instance with type {0} is not supported operation.</b>
<b>Explanation</b>	Platform Manager does not support updating the configuration instance with the specified type.
<b>Action</b>	Check the warning to determine if any damage to the system will occur.

**SPMTEMW0013**     **Skipping storage of configuration instance ({0}) for runtime component - {1}. Reason: {2}**

**Explanation**     An error occurred while loading the configuration instance and it will not be included in the template that will be created.

**Action**            Check the logs for more details about the error.

**SPMTEMW0046**     **Reserved instance name {0}.**

**Explanation**     Instance name {0} is reserved for internal use only.

**Action**            Use a different instance name.

**SPMTERE0000**     **Template log file not available.**

**Explanation**     The Platform Manager log access service was unable to locate the template log file.

**Action**            Contact Software AG Global Support.

**SPMTERE0001**     **Installer and Update Manager logs unavailable.**

**Explanation**     The Installer or Update Manager logs cannot be located.

**Action**            Contact Software AG Global Support.

**SPMUTLE0000**     **Invalid URL.**

**Explanation**     The URL does not fit the specification.

**Action**            Specify a valid URL.

**SPMUTLE0001**     **URL string cannot be parsed as a URI reference**

**Explanation**     The URL does not fit the specification.

**Action**            Specify a valid URL.

**SPMUTLE0002**     **Problem with saglicutil execution.**

**Explanation**     The saglicutil utility cannot be started.

**Action**            Contact Software AG Global Support.

**SPMUTLE0003**     **Error occurred: Saglicutil verifier tool is missing!**

**Explanation**     The saglicutil verifier tool is not found at the expected location.

**Action**            Contact Software AG Global Support.

---

<b>SPMUTLE0004</b>	<b>Unable to collect NetworkInterface details; caught this: type({0}), msg({1})</b>
<b>Explanation</b>	An attempt to use java.lang.NetworkInterface to collect MAC address information failed.
<b>Action</b>	Determine whether the current user has permission to collect this information.
<b>SPMUTLE0005</b>	<b>Collected {0} MAC addresses before failure.</b>
<b>Explanation</b>	This message will always be logged with SPMULTLE0004
<b>Action</b>	No action required.
<b>SPMUTLE0006</b>	<b>Error occurred: Execution of saglicutil verifier tool failed!</b>
<b>Explanation</b>	The execution of the saglicutil verifier tool may fail due to the latest Windows patches not being installed or due to a corrupted installation environment.
<b>Action</b>	Ensure that the latest Windows patches are installed or contact Software AG Global Support.
<b>SPMUTLE0007</b>	<b>Error occurred: Processor core type information is missing!</b>
<b>Explanation</b>	The saglicutil verifier tool does not provide the processor core type information.
<b>Action</b>	Contact Software AG Global Support.
<b>SPMUTLE0008</b>	<b>Error occurred: Processor core count information is missing!</b>
<b>Explanation</b>	The saglicutil verifier tool does not provide the processor core count information.
<b>Action</b>	Contact Software AG Global Support.
<b>SPMUTLW0009</b>	<b>Abnormal termination of command {0} with result {1}</b>
<b>Explanation</b>	The internal command execution returned non-zero exit code.
<b>Action</b>	No user action is required.
<b>SPMWTNE0000</b>	<b>Integration Server password was not provided</b>
<b>Explanation</b>	The password is a required field.
<b>Action</b>	Provide an Integration Server password.

- SPMWTNE0001    Integration Server URL is not valid**  
**Explanation**    The Integration Server URL is malformed  
**Action**    Check that your Task Engine configuration values for host, port, username and password are valid.
- SPMWTNE0002    Only BASIC authentication is supported**  
**Explanation**    The provided authentication is not supported.  
**Action**    Change authentication to BASIC.
- SPMWTNE0009    No Integration Server credentials were provided**  
**Explanation**    The connection to Integration Server cannot be validated without proper credentials.  
**Action**    Provide values for username and password.
- SPMWTNE0014    Integration Server host, port, and/or connection protocol were not provided**  
**Explanation**    The Integration Server host, port, and connection protocol are required values.  
**Action**    Provide values for host, port, and connection protocol.
- SPMWTNISE0000    My webMethods Server password was not provided.**  
**Explanation**    The password is a required field.  
**Action**    Provide a password for My webMethods Server.
- SPMWTNISE0001    An error occurred during a call to `wm.task.taskclient:getConfig`. The error reported is: `{0}`.**  
**Explanation**    An error occurred during the service call to write the configuration settings to `WmTaskClient`. The error might be caused by accessing the `IntegrationServer\packages\WmTaskClient\config\taskclient.properties` file. This message will also occur if the file was initially not present and the service call to write the configuration settings created the file and populated it with default values.  
**Action**    Make sure that the `IntegrationServer\packages\WmTaskClient\config\taskclient.properties` file is present, contains `name=value` pairs, and the `name=value` pairs are valid. Note: This message will also occur if the file was initially not present and the service call to write the configuration settings created the file and populated it with default values. Check that the name-value pairs are acceptable for your configuration.

**SPMWTNISE0002 Only BASIC authentication is supported**

**Explanation** The specified authentication is not supported.

**Action** Change authentication to BASIC.

**SPMWTNISE0003 The My webMethods Server URL is not valid.**

**Explanation** The URL for pinging My webMethods Server is not valid.

**Action** Check that your WmTaskClient configuration values for host, port, username and password are valid.

**SPMWTNISE0009 No My webMethods Server credentials were provided.**

**Explanation** The connection to My webMethods Server cannot be validated without proper credentials.

**Action** Specify values for username and password.

**SPMWTNISE0011 The password is required.**

**Explanation** You must specify a password.

**Action** Specify a password.

**SPMWTNISE0014 The My webMethods Server host, port, and/or connection protocol were not provided.**

**Explanation** You must specify values for the My webMethods Server host, port, and connection protocol.

**Action** Specify values for host, port, and connection protocol.



# 22 Presto Messages

---

**JBPCLICE0001**

**JBPCLICE0524** Unexpected error uploading thumbnail image: {0}

**JBPCLICE0529** Invalid zip export file. "app-export-details.xml" not found in ZIP.

**JBPCLICE0535** Dashboard with name :{0} and with guid: {1} already exists.

**JBPCLICI0002** Dashboard: {0} with guid: {1} already exists.

**JBPCLICI0003** Dashboard: {0} with guid: {1} could not be imported.

**JBPCLICI0004** Importing App...

**JBPCLICI0005** INFO: {0}

**JBPCLICI0006** Overwriting existing App...

JBPCLICI0007      **Overwriting existing App zip file...**

JBPCLICI0008      **Dashboard:{0} with guid: {1} successfully exported.**

JBPCLICI0009      **Dashboard {0} with guid {1} could not be exported. {2}**

JBPCLICI0010      **Dashboard: {0} with guid: {1} successfully imported.**

JBPCLICI0011      **Uploading App zip file...**

JBPCLICI0012      **Zip upload and/or overwrite completed : {0}**

JBPCLICI0013      **Failed to execute all test cases. Reason = {0}**

JBPCLICI0014      **Test case file not provided. Running default test data file from  
test/testcases\_public\_services.txt**

JBPCLICI0015      **Available subcommands:**

JBPCLICI0016      **{0}**

JBPCLICI0017      **-{0}**

JBPCLICI0018      **Failed to parse command line: {0}**

JBPCLICI0019      **Initialization failed. Cannot to real prestocli.propeties file.**

JBPCLICI0020      **Invalid Command: {0}**

---

JBPCLICI0021	Missing options: {0}
JBPCLICI0022	No command specified
JBPCLICI0023	padmin {0}
JBPCLICI0024	padmin command-line client, version {0}
JBPCLICI0025	Some command line values are invalid (see details below):
JBPCLICI0026	Type "{0} help <subcommand>" for help on a specific subcommand.
JBPCLICI0027	Type 'padmin help' for usage
JBPCLICI0028	usage: {0} <subcommand> [options]
JBPCLICI0029	Invalid URL format:{0}
JBPCLICI0030	(optional) server URL - default http://localhost:8080/mashzone/esd/api
JBPCLICI0031	use given password
JBPCLICI0032	use given user
JBPCLICI0033	verbose output
JBPCLICI0034	Cannot open input file:{0}

JBPCLICI0035	continue processing if one request fails
JBPCLICI0036	ERROR: {0}
JBPCLICI0037	Expecting app tag at document root, {0}
JBPCLICI0038	get path: {0}
JBPCLICI0039	INFO: {0}
JBPCLICI0040	input directory
JBPCLICI0041	overwrite existing entities
JBPCLICI0042	-- publishing App, id: {0}
JBPCLICI0043	-- publishing App {0}, {1}
JBPCLICI0044	-- publishing App, name: {0}
JBPCLICI0045	spec: {0}
JBPCLICI0046	Uploads and creates an App
JBPCLICI0047	ESD returned unrecognized response
JBPCLICI0048	Document Exception: {0}

---

JBPCLICI0049	getDbServiceDetail: {0}
JBPCLICI0050	getJdbcProviderInfo: {0}
JBPCLICI0051	Encrypt property value to be used in configuration property files
JBPCLICI0052	property value to encrypt
JBPCLICI0053	ERROR: {0}
JBPCLICI0054	INFO: {0}
JBPCLICI0055	WARN: {0}
JBPCLICI0056	Download App resources
JBPCLICI0057	Download completed
JBPCLICI0058	Exception creating output file: {0}
JBPCLICI0059	Exception creating output zip file: {0}
JBPCLICI0060	Exported {0} App{1}
JBPCLICI0061	Exported App {0}
JBPCLICI0062	Exported App unzipped to : {0}

JBPCLICI0063	Exported App written to : {0}
JBPCLICI0064	Exports Apps from Mashzone NextGen
JBPCLICI0065	Export details written to : {0}
JBPCLICI0066	Export file does not have expected elements ServiceExport_Array or ServiceExport__Array
JBPCLICI0067	export service details
JBPCLICI0068	Export written to : {0}
JBPCLICI0069	Export written to : {0}
JBPCLICI0070	Failed to export App {0} : {1}
JBPCLICI0071	Failed to export Service {0} : {1}
JBPCLICI0072	File {0} already exists. Please choose different file name
JBPCLICI0073	filter expression to select Apps to export. Where expression is a property followed by an optional comma separated list of one or more values for the given App property. Supported properties are : all, mine, ids, name, author, category, tag and provider. The expression should be enclosed in quotes. Examples: 1) -q "all" 1) -q "mine" 1) -q "author = dev, user" 2) -q "name = MyApp" 3) -q "tag = MyTag" 4) -q "ids = MyApp, MyOtherApp"
JBPCLICI0074	IO Exception creating output zip file: {0}

JBPCLICI0075	Named output directory is not a directory, absolute path : {0}
JBPCLICI0076	No Apps Exported
JBPCLICI0077	output file
JBPCLICI0078	overwrite any existing output file
JBPCLICI0079	Unknown reason
JBPCLICI0080	Destination directory not specified
JBPCLICI0081	Export query missing
JBPCLICI0082	username and password missing
JBPCLICI0083	username missing
JBPCLICI0084	user password missing
JBPCLICI0085	Cannot open output file:{0}
JBPCLICI0086	-d and -g options are mutually exclusive
JBPCLICI0087	Exports EMMML Macros
JBPCLICI0088	File {0} already exists. Please choose different file name

<b>JBPCLICI0089</b>	<b>global macros</b>
<b>JBPCLICI0090</b>	<b>macro domain name</b>
<b>JBPCLICI0091</b>	<b>macro name</b>
<b>JBPCLICI0092</b>	<b>ouput file</b>
<b>JBPCLICI0093</b>	<b>Cannot open output file:{0}</b>
<b>JBPCLICI0094</b>	<b>Exports Global attributes and attribute definitions</b>
<b>JBPCLICI0095</b>	<b>File {0} already exists. Please choose different file name</b>
<b>JBPCLICI0096</b>	<b>ouput file</b>
<b>JBPCLICI0097</b>	<b>Directory {0} already exists and is not empty. Please specify overwrite, -o, or empty the directory before exporting.</b>
<b>JBPCLICI0098</b>	<b>Download completed</b>
<b>JBPCLICI0099</b>	<b>Download Lib resources</b>
<b>JBPCLICI0100</b>	<b>Exception creating output file: {0}</b>
<b>JBPCLICI0101</b>	<b>Exception creating output zip file: {0}</b>
<b>JBPCLICI0102</b>	<b>Exported {0} {1}</b>

---

JBPCLICI0103	Exported Lib {0}
JBPCLICI0104	Exports user defined libraries
JBPCLICI0105	Export details written to : {0}
JBPCLICI0106	Export file does not have expected elements ServiceExport_Array or ServiceExport__Array
JBPCLICI0107	Export item not found {0}
JBPCLICI0108	Export unzipped to : {0}
JBPCLICI0109	Export written to : {0}
JBPCLICI0110	Export written to : {0}
JBPCLICI0111	Failed to export library {0} : {1}
JBPCLICI0112	Failed to export library : {0}
JBPCLICI0113	File {0} already exists. Please choose different file name
JBPCLICI0114	<b>filter expression to select libraries to export. Where expression is a comma separated list of one or more values for a given library property. Supported properties are: all, mine, user, ids, name, type, subtype. The expression should be enclosed in quotes. Examples: 1) -q "user=dev,user" 2) -q "name=My Lib" 2) -q "type=view" 4) -q "ids=MyLib, MyOtherLib"</b>
JBPCLICI0115	<b>include dependent libraries</b>

JBPCLICI0116	IO Exception creating output zip file: {0}
JBPCLICI0117	Named output directory is not a directory, absolute path : {0}
JBPCLICI0118	No libraries exported
JBPCLICI0119	output directory
JBPCLICI0120	output file
JBPCLICI0121	overwrite any existing output file
JBPCLICI0122	Unknown reason
JBPCLICI0123	Cannot open output file:{0}
JBPCLICI0124	Exports Apps
JBPCLICI0125	File {0} already exists. Please choose different file name
JBPCLICI0126	filter expression to select services to export. Where expression is all * [ids]=value Examples: 1) -q "ids = App1, App2"
JBPCLICI0127	ouput file
JBPCLICI0128	Cannot open output file:{0}
JBPCLICI0129	Exports XACML Policy

---

JBPCLICI0130	File {0} already exists. Please choose different file name
JBPCLICI0131	(optional) name of the policy to export, if no name provided default policy is exported
JBPCLICI0132	ouput file
JBPCLICI0133	Cannot open output file:{0}
JBPCLICI0134	Exports a Service
JBPCLICI0135	File {0} already exists. Please choose different file name
JBPCLICI0136	filter expression to select services to export. Where expression is all * [tag ids type name]=value Examples: 1) -q "type = WSDL" 2) -q "name = Yahoo*" 3) -q "tag = MyTag" 4) -q "ids = AmazonDocStyle, AmazonREST"
JBPCLICI0137	ouput file
JBPCLICI0138	Cannot open output file:{0}
JBPCLICI0139	Exports Global attributes and attribute definitions
JBPCLICI0140	File {0} already exists. Please choose different file name
JBPCLICI0141	ouput file
JBPCLICI0142	Cannot open output file:{0}

JBPCLICI0143	Exports Users and Roles
JBPCLICI0144	File {0} already exists. Please choose different file name
JBPCLICI0145	ouput file
JBPCLICI0146	Exception while processing template: {0} exception: {1}
JBPCLICI0147	getInstance: {0}
JBPCLICI0148	none found, creating new instance
JBPCLICI0149	processTemplateToString: templateName = {0}
JBPCLICI0150	Template Exception while processing template: {0} exception: {1}
JBPCLICI0151	template processing complete
JBPCLICI0152	Algorithm with name {0} is not supported
JBPCLICI0153	Cannot open output file:{0}
JBPCLICI0154	File {0} already exists. Please choose different file name
JBPCLICI0155	Generates a symmetric key
JBPCLICI0156	ouput file

---

JBPCLICI0157	use given key algorithm
JBPCLICI0158	Source directory not specified
JBPCLICI0159	App.spec not found. Expecting to find App spec at new File(dir, "App.xml").getAbsolutePath()
JBPCLICI0160	App Spec root document element incorrect
JBPCLICI0161	Cannot open input file:{0}
JBPCLICI0162	continue processing if one request fails
JBPCLICI0163	Empty App Spec
JBPCLICI0164	Exception retrying thumbnail upload: {0}
JBPCLICI0165	Expecting app tag at document root, {0}
JBPCLICI0166	Export file does not have either of the the expected elements ServiceExport_Array or ServiceExport__Array
JBPCLICI0167	Failed to create import zip file {0}
JBPCLICI0168	filter expression to select Apps to import. Where expression is a comma separated list of one or more values for a given App property. Supported properties are : ids, name, author, category, tag and provider. The expresssion should be enclosed in quotes. Examples: 1) -q "author = dev, user" 2) -q "name = MyApp" 3) -q "tag = MyTag" 4) -q "ids = MyApp, MyOtherApp"

- JBPCLICI0169 -- Importing App {0} ( {1} )
- JBPCLICI0170 -- App Import {0} ( {1} ) : completed on system {2}
- JBPCLICI0171 -- Importing App {0} ( {1} ) screenshot, {2}
- JBPCLICI0172 -- Importing App {0} ( {1} ) thumbnail, {2}
- JBPCLICI0173 -- Importing App {0} ( {1} ) zipfile, {2}
- JBPCLICI0174 Imports Apps
- JBPCLICI0175 Import of App {0} failed. {1} Continue importing remaining services
- JBPCLICI0176 import service details
- JBPCLICI0177 input file
- JBPCLICI0178 IOException during thumbnail upload: {0}
- JBPCLICI0179 Missing export or app spec details
- JBPCLICI0180 Named input directory does not exist, absolute path : {0}
- JBPCLICI0181 Named input directory is not a directory, absolute path : {0}
- JBPCLICI0182 No App spec found at zip entry '{0}', or 'App.xml'.

---

JBPCLICI0183	overwrite existing entities
JBPCLICI0184	-- publishing App {0}, {1}
JBPCLICI0185	thumbnail size {0}
JBPCLICI0186	thumbnail size {0}
JBPCLICI0187	Unexpected document exception handling import xml doc. {0}
JBPCLICI0188	Unexpected error importing services. {0}
JBPCLICI0189	Unexpected IOException creating import xml doc. {0}
JBPCLICI0190	username and password missing
JBPCLICI0191	username missing
JBPCLICI0192	user password missing
JBPCLICI0193	Cannot open input file:{0}
JBPCLICI0194	continue processing if one request fails
JBPCLICI0195	ERROR: {0}
JBPCLICI0196	Export file does not have expected element {0}

<b>JBPCLICI0197</b>	<b>Imports EMMML Macros</b>
<b>JBPCLICI0198</b>	<b>Import of macro failed. {0} Continue importing remaining macros</b>
<b>JBPCLICI0199</b>	<b>INFO: {0}</b>
<b>JBPCLICI0200</b>	<b>input file</b>
<b>JBPCLICI0201</b>	<b>overwrite existing entities</b>
<b>JBPCLICI0202</b>	<b>-- Processing {0} --</b>
<b>JBPCLICI0203</b>	<b>Cannot open input file:{0}</b>
<b>JBPCLICI0204</b>	<b>continue processing if one request fails</b>
<b>JBPCLICI0205</b>	<b>create global attribute failed</b>
<b>JBPCLICI0206</b>	<b>create global attribute failed - attribute already exists. Use -o to overwrite or remove attribute first.</b>
<b>JBPCLICI0207</b>	<b>ERROR: {0}</b>
<b>JBPCLICI0208</b>	<b>Export file does not have expected elements globalAttributes</b>
<b>JBPCLICI0209</b>	<b>Imports Global Attributes and definitions</b>
<b>JBPCLICI0210</b>	<b>INFO: {0}</b>

---

JBPCLICI0211	input file
JBPCLICI0212	inserting global attribute: {0}
JBPCLICI0213	overwrite existing entities
JBPCLICI0214	Received error: {0}. continuing ...
JBPCLICI0215	Received error: {0}. terminating..
JBPCLICI0216	Source directory not specified
JBPCLICI0217	Cannot open input file:{0}
JBPCLICI0218	check file {0}
JBPCLICI0219	continue processing if one request fails
JBPCLICI0220	create import zip file..
JBPCLICI0221	create input file..
JBPCLICI0222	create registration doc..
JBPCLICI0223	create tempory zip file..
JBPCLICI0224	Error reading file data : {0}

- JBPCLICI0225      Expecting LibExport tag at document root, {0}
- JBPCLICI0226      Export file does not have either of the the expected elements ServiceExport\_Array or ServiceExport\_\_Array
- JBPCLICI0227      Extracted view class as library loadConfirmation, {0}
- JBPCLICI0228      Extracted view description, {0}
- JBPCLICI0229      Extracted view name, {0}
- JBPCLICI0230      Failed to create import zip file {0}
- JBPCLICI0231      Failed to verify Lib {0}. {1} Continue importing remaining items.
- JBPCLICI0232      filter expression to select libraries to import. Where expression is a comma separated list of one or more values for a given library property. Supported properties are: all, mine, user, id, name, type, subtype. The expression should be enclosed in quotes. Examples: 1) -q "user=dev,user" 2) -q "name=My Lib" 2) -q "type=view" 4) -q "ids=MyLib, MyOtherLib"
- JBPCLICI0233      find xml file {0}
- JBPCLICI0234      found properties file, {0}
- JBPCLICI0235      -- Importing Lib {0} ( {1} )
- JBPCLICI0236      -- Importing Lib {0} ( {1} ) : completed
- JBPCLICI0237      -- Importing Lib {0} ( {1} ) {2}

---

JBPCLICI0238	-- Importing Lib {0} ( {1} ) {2} zipfile, {3}
JBPCLICI0239	Imports libraries
JBPCLICI0240	import details : {0}
JBPCLICI0241	Import of Lib {0} failed. {1} Continue importing remaining items
JBPCLICI0242	input directory
JBPCLICI0243	input file
JBPCLICI0244	{0}/{1}/library.zip
JBPCLICI0245	Library directory does not contain js or css directories.
JBPCLICI0246	Library directory is empty!
JBPCLICI0247	Library identified as a custom view
JBPCLICI0248	- loadConfirmation must be specified if library includes javascript.
JBPCLICI0249	Named input directory does not exist, absolute path : {0}
JBPCLICI0250	Named input directory is not a directory, absolute path : {0}
JBPCLICI0251	overwrite existing entities

JBPCLICI0252	overwriting if lib exists,
JBPCLICI0253	Unable to continue, no input file available.
JBPCLICI0254	Unexpectedly failed to read library details from file {0}
JBPCLICI0255	Unexpected document exception handling import xml doc. {0}
JBPCLICI0256	Unexpected IOException creating import xml doc. {0}
JBPCLICI0257	Cannot open input file:{0}
JBPCLICI0258	continue processing if one request fails
JBPCLICI0259	ERROR: {0}
JBPCLICI0260	Export file does not have niether of expected elements ServiceExport_Array or com.jackbe.jbp.sas.export.model.ServiceExport_Array or com.jackbe.jbp.sas.export.model.ServiceExport-array element
JBPCLICI0261	Imports Apps
JBPCLICI0262	Import of mashlet failed. {0} Continue importing remaining services
JBPCLICI0263	input file
JBPCLICI0264	overwrite existing entities
JBPCLICI0265	-- Processing {0}

---

JBPCLICI0266	Cannot open input file:{0}
JBPCLICI0267	ERROR: {0}
JBPCLICI0268	Imports an XACML Policy
JBPCLICI0269	input file
JBPCLICI0270	Cannot open input file:{0}
JBPCLICI0271	continue processing if one request fails
JBPCLICI0272	ERROR: {0}
JBPCLICI0273	Export file does not have niether of expected elements ServiceExport_Array or ServiceExport__Array or com.jackbe.jbp.sas.export.model.ServiceExport_Array or com.jackbe.jbp.sas.export.model.ServiceExport-array element
JBPCLICI0274	Failed to create category: {0}
JBPCLICI0275	Failed to create provider: {0}
JBPCLICI0276	Ignoring unexpected Element type: {0}
JBPCLICI0277	Imports a Service
JBPCLICI0278	Import of service failed. {0} Continue importing remaining services
JBPCLICI0279	INFO: {0}

JBPCLICI0280	input file
JBPCLICI0281	Software AG Mashzone NextGen Platform
JBPCLICI0282	overwrite existing entities
JBPCLICI0283	-- Processing {0} service of type {1} --
JBPCLICI0284	Service type "{0}" is not supported
JBPCLICI0285	Cannot open input file:{0}
JBPCLICI0286	continue processing if one request fails
JBPCLICI0287	create user profile failed
JBPCLICI0288	create user profile failed, attempting overwrite
JBPCLICI0289	ERROR: {0}
JBPCLICI0290	Export file does not have expected elements userProfiles
JBPCLICI0291	importing user profile for {0}
JBPCLICI0292	Imports User Profiles
JBPCLICI0293	INFO: {0}

---

JBPCLICI0294	input file
JBPCLICI0295	overwrite existing entities
JBPCLICI0296	Received error: {0}. continuing ...
JBPCLICI0297	Received error: {0}. terminating..
JBPCLICI0298	Cannot open input file:{0}
JBPCLICI0299	continue processing if one request fails
JBPCLICI0300	creating user: {0}
JBPCLICI0301	ERROR: {0}
JBPCLICI0302	Export file does not have expected elements roleNames
JBPCLICI0303	Export file does not have expected elements users
JBPCLICI0304	Imports Users and Roles
JBPCLICI0305	INFO: {0}
JBPCLICI0306	input file
JBPCLICI0307	<b>**NOTE: all imported users have had their passwords set to "welcome". **Please Notify each user to change their password.</b>

<b>JBPCLICI0308</b>	<b>overwrite existing entities</b>
<b>JBPCLICI0309</b>	<b>Received error: {0}. continuing ...</b>
<b>JBPCLICI0310</b>	<b>Received error: {0}. terminating..</b>
<b>JBPCLICI0311</b>	<b>skipping built-in role: {0}</b>
<b>JBPCLICI0312</b>	<b>user: {0} already exists</b>
<b>JBPCLICI0313</b>	<b>App File exists</b>
<b>JBPCLICI0314</b>	<b>Lib file exists</b>
<b>JBPCLICI0315</b>	<b>ERROR: {0}</b>
<b>JBPCLICI0316</b>	<b>Failed to create library, {0}</b>
<b>JBPCLICI0317</b>	<b>Importing library...</b>
<b>JBPCLICI0318</b>	<b>INFO: {0}</b>
<b>JBPCLICI0319</b>	<b>Invalid library id. Library id reserved for internal use.</b>
<b>JBPCLICI0320</b>	<b>Library import failed.</b>
<b>JBPCLICI0321</b>	<b>Library version exists..</b>

---

JBPCLICI0322	Library version exists. Use overwrite option to replace an existing library version.
JBPCLICI0323	Overwriting existing Library..
JBPCLICI0324	Overwriting existing library zip file...
JBPCLICI0325	Removing existing library..
JBPCLICI0326	Unexpected error importing library: {0}, {1}
JBPCLICI0327	Unexpected error uploading library zip file : {0}, {1}
JBPCLICI0328	Uploading library zip file...
JBPCLICI0329	Upload completed : {0}
JBPCLICI0330	Zip upload and overwrite completed : {0}
JBPCLICI0331	Failed to transmit app zip file. {0}
JBPCLICI0332	Failed to transmit resource file. {0}
JBPCLICI0333	Failed to upload app zip file. {0}
JBPCLICI0334	Failed to upload resource file. {0}
JBPCLICI0335	upload {0}, user: {1}, pw: {2}, path: {3}

<b>JBPCLICI0336</b>	<b>upload {0}, user: {1}, pw: {2}, path: {3}, overwrite {4}, content {5}</b>
<b>JBPCLICI0337</b>	<b>Cannot open input file:{0}</b>
<b>JBPCLICI0338</b>	<b>Comma separated list of RegistryObject Ids</b>
<b>JBPCLICI0339</b>	<b>Copy from URL. Used with COPY and MOVE</b>
<b>JBPCLICI0340</b>	<b>ERROR: {0}</b>
<b>JBPCLICI0341</b>	<b>Imports a resource file</b>
<b>JBPCLICI0342</b>	<b>INFO: {0}</b>
<b>JBPCLICI0343</b>	<b>input file</b>
<b>JBPCLICI0344</b>	<b>overwrite existing entities</b>
<b>JBPCLICI0345</b>	<b>Resource description</b>
<b>JBPCLICI0346</b>	<b>Resource mime type</b>
<b>JBPCLICI0347</b>	<b>Resource relative URL</b>
<b>JBPCLICI0348</b>	<b>Resource type</b>
<b>JBPCLICI0349</b>	<b>Failed to transmit app zip file. {0}</b>

---

JBPCLICI0350	Failed to transmit resource file. {0}
JBPCLICI0351	Failed to upload app zip file. {0}
JBPCLICI0352	Failed to upload resource file. {0}
JBPCLICI0353	Overwriting existing mashlet
JBPCLICI0354	allRoles: {0}
JBPCLICI0355	allUsers: {0}
JBPCLICI0356	Auth protocol: {0} not supported in migration tool. Please register this service manually.
JBPCLICI0357	categories and applications processing complete
JBPCLICI0358	categories complete, now processing applications
JBPCLICI0359	completed processing non-mashup services from 2.7 to 3.0
JBPCLICI0360	completed processing roles from 2.7 to 3.0
JBPCLICI0361	Create a migration file instead of actually doing the migration
JBPCLICI0363	database service: {0}
JBPCLICI0364	Datasource Name : dsDetail.getString("name")

- JBPCLICI0365**      **Dependency Check failed**
  
- JBPCLICI0366**      **Dependency check failed. Please correct the above errors and re-run migration**
  
- JBPCLICI0367**      **Dependency Error: The source system contains a Database service: {0} which is**
  
- JBPCLICI0368**      **dependent on the datasource: {0}. This datasource needs to be created in**
  
- JBPCLICI0369**      **DONE Migrating 2.7 Service Mashlets to 3.0 Apps**
  
- JBPCLICI0370**      **done registerSyndication**
  
- JBPCLICI0371**      **done WSDL registration**
  
- JBPCLICI0372**      **doUsers flag: {0}**
  
- JBPCLICI0373**      **Duplicate resource**
  
- JBPCLICI0374**      **Exception while migrating mashlets {0}**
  
- JBPCLICI0375**      **generateFileName: {0}**
  
- JBPCLICI0376**      **generateFile flag: {0}**
  
- JBPCLICI0377**      **ignoring system mashlet: {0}. It does not need to be migrated**
  
- JBPCLICI0378**      **jdbcDatasource is: {0}**

---

JBPCLICI0379	JDBC Driver Name : <code>dsDetail.getString("jdbcDriverName")</code>
JBPCLICI0380	JDBC Password : <code>dsDetail.getString("password")</code>
JBPCLICI0381	JDBC URL : <code>dsDetail.getString("jdbcUrl")</code>
JBPCLICI0382	JDBC User : <code>dsDetail.getString("userId")</code>
JBPCLICI0383	<code>{0}</code>
JBPCLICI0384	Log all progress to a file
JBPCLICI0386	migrated Auth Policy Roles : <code>{0}</code>
JBPCLICI0387	migrated from Presto 2.7
JBPCLICI0388	Migrates from Presto 2.7 to Presto 3.0
JBPCLICI0389	Migrate users source instance to target (not for use with LDAP)
JBPCLICI0390	Migrating 2.7 Service Mashlets to 3.0 Apps
JBPCLICI0391	Migrating mashlet: <code>{0}</code>
JBPCLICI0392	migrating role <code>{0}</code>
JBPCLICI0393	migrating service <code>[[{0}]]</code> :

JBPCLICI0394 Migration halted - error: {0}

JBPCLICI0395 MashZone NG 30 Url is invalid: {0}

JBPCLICI0396 Presto30 Pass: {0}

JBPCLICI0397 Presto30 URL: {0}

JBPCLICI0398 Presto30 User: {0}

JBPCLICI0399 MashZone NG Url is invalid: {0}

JBPCLICI0400 Mashzone NextGen Pass: {0}

JBPCLICI0401 Mashzone NextGen URL: {0}

JBPCLICI0402 Mashzone NextGen User: {0}

JBPCLICI0403 Processing Application: {0} into category {1}

JBPCLICI0404 processing categories and 2.7 applications to 3.0

JBPCLICI0405 Processing Category id : {0}, name : {1}, parent = {2}, desc: {3}

JBPCLICI0406 Processing {0} mashlets

JBPCLICI0407 processing mashup services from 2.7 to 3.0

---

JBPCLICI0408	processing non-mashup services from 2.7 to 3.0
JBPCLICI0409	processing providers from 2.7 to 3.0
JBPCLICI0410	processing provider: {0}
JBPCLICI0411	processing REST service{0}
JBPCLICI0412	processing service: {0} of type: {1}
JBPCLICI0413	processing Syndication service url: {0}
JBPCLICI0414	processing users and roles from 2.7 to 3.0
JBPCLICI0415	Processing user: {0}
JBPCLICI0416	processing WSDL service url: {0}
JBPCLICI0417	provider processing complete
JBPCLICI0420	****Reason: {0}
JBPCLICI0422	saving mashup service {0} for later
JBPCLICI0423	Existing App zip file detected without overwrite flag, skipping import of {0}
JBPCLICI0425	***Service: {0} encountered and error during registration. Please register this service manually.

<b>JBPCLICI0426</b>	<b>skipping root category</b>
<b>JBPCLICI0427</b>	<b>The service type: {0} is not supported by this utility.</b>
<b>JBPCLICI0428</b>	<b>the target system before migration can proceed. Datasouce details are:</b>
<b>JBPCLICI0430</b>	<b>URL to source Instance</b>
<b>JBPCLICI0431</b>	<b>URL to target Instance</b>
<b>JBPCLICI0432</b>	<b>User for source Instance</b>
<b>JBPCLICI0433</b>	<b>User for target instance</b>
<b>JBPCLICI0434</b>	<b>User password for source Instance</b>
<b>JBPCLICI0435</b>	<b>User password for target instance</b>
<b>JBPCLICI0437</b>	<b>getCommand: {0}</b>
<b>JBPCLICI0438</b>	<b>Invalid command name: {0}</b>
<b>JBPCLICI0439</b>	<b>Bad Argument: {0}</b>
<b>JBPCLICI0440</b>	<b>Begin MigrationMain</b>
<b>JBPCLICI0441</b>	<b>End MigrationMain</b>

---

JBPCLICI0442	migrate
JBPCLICI0443	Missing Argument: {0}
JBPCLICI0444	Missing Option: {0}
JBPCLICI0445	No command specified. Valid commands are:
JBPCLICI0446	Parse Exception: {0}
JBPCLICI0447	Unrecognized command: {0}. Valid commands are:
JBPCLICI0448	hold N seconds for response or "forever" to hold until successful ping
JBPCLICI0449	Pings Mashzone NextGen server
JBPCLICI0450	Server is down
JBPCLICI0451	Server is down after {0} seconds
JBPCLICI0452	Server is up
JBPCLICI0453	{0} is not valid. Either "forever" or a positive integer is required
JBPCLICI0454	findFeedbackForEntity: {0}
JBPCLICI0455	Not supported yet.

<b>JBPCLICI0456</b>	<b>continue processing if one request fails</b>
<b>JBPCLICI0457</b>	<b>Done</b>
<b>JBPCLICI0458</b>	<b>Error = {0}</b>
<b>JBPCLICI0459</b>	<b>error filename</b>
<b>JBPCLICI0460</b>	<b>Failed</b>
<b>JBPCLICI0461</b>	<b>Failed - {0}</b>
<b>JBPCLICI0462</b>	<b>Failed - {0}</b>
<b>JBPCLICI0463</b>	<b>Invalid URL:{0}</b>
<b>JBPCLICI0464</b>	<b>Reads JUMP Requests from file and send it to server over HTTP</b>
<b>JBPCLICI0465</b>	<b>----- RequestId= {0} -----</b>
<b>JBPCLICI0466</b>	<b>request filename</b>
<b>JBPCLICI0467</b>	<b>Stop because of failure</b>
<b>JBPCLICI0468</b>	<b>Cannot construct request.</b>
<b>JBPCLICI0469</b>	<b>doOperationInvocation: templateName = {0}</b>

---

JBPCLICI0470	{0}. Check if service with the same name already exists.
JBPCLICI0471	Failed to communicate with ESD at url::{0}
JBPCLICI0472	getting JSON array response
JBPCLICI0473	getting JSON object response
JBPCLICI0474	getting string response
JBPCLICI0475	Request:{0}
JBPCLICI0476	Response:{0}
JBPCLICI0478	already exists
JBPCLICI0479	category {0} already exists
JBPCLICI0480	Service already exists
JBPCLICI0481	Executing {0}
JBPCLICI0482	Failed - {0}
JBPCLICI0483	Failed - {0}
JBPCLICI0484	Invalid URL::{0}

JBPCLICI0485      Request ({0}) failed. Error -> {1}

JBPCLICI0486      Request ({0}) failed. Error -> {1}

JBPCLICI0487      INFO: Overwriting existing service

JBPCLICI0488      execute task..

JBPCLICI0489      input validation..

JBPCLICI0490      task completed

JBPCLICI0491      user name {0}

JBPCLICI0492      {0}. Check if service with the same name already exists.

JBPCLICI0493      Executing {0}

JBPCLICI0494      Failed - {0}

JBPCLICI0495      Failed - {0}

JBPCLICI0496      Invalid URL:{0}

JBPCLICI0497      Service registration for ({0}) failed. Error -> {1}

JBPCLICI0498      Error pretty printing xml: {0}

---

JBPCLICI0499	Invalid import. Service element {0} misses child element {1}
JBPCLICI0500	addToZip {0}, {1}, length {2}
JBPCLICI0501	could not rename the file {0} to {1}
JBPCLICI0502	Error saving data : {0}
JBPCLICI0503	Failed to create {0} zip file, {1} : {2}
JBPCLICI0504	Failed to create {0} zip file, {1} : {2}
JBPCLICI0505	file doesnt exist? {0}
JBPCLICI0506	[info] {0}
JBPCLICI0507	item : {0}
JBPCLICI0508	item : {0}
JBPCLICI0509	Output file exists, length : {0}, last modified{1}
JBPCLICI0510	Unable to create output file parent directory structure, {0}
JBPCLICI0511	Unable to create parent directory structure, {0}
JBPCLICI0512	Unexpected IOException creating zip file, {0} : {1}

JBPCLICI0513	zip directory {0}
JBPCLICI0514	Zip file does not exist. {0}
JBPCLICI0515	zip import items {0}, dir {1}
JBPCLICI0516	Could not export service: {0}. Error: {1}
JBPCLICI0517	Document Exception: {0}
JBPCLICI0518	exportService: {0}
JBPCLICI0519	specify Dashboards to export.Supported identifiers are: id, name or all. The expression should be enclosed in quotes.Examples:-i "id=3e0d34bf-299a-05b4f8a5"-i "name=MyDashboard" -i "all"
JBPCLICI0520	Dashboard with identifier {0} could not be found.
JBPCLICI0521	URL {0} seems to be invalid
JBPCLICI0522	Dashboard successfully exported to : {0}
JBPCLICI0523	Dashboard could not be exported to : {0}. Unknown reason.
JBPCLICI0524	overwrite existing resourcepolicy and permissions
JBPCLICI0525	Given import file could not be loaded. {0}.
JBPCLICI0530	Dashboard of the file {0} could not be imported, reason: {1}

---

JBPCLICI0531	Dashboard import failed. The content of the file {0} contains none or not all required information.
JBPCLICI0532	Dashboards imported from : {0}
JBPCLICI0533	Dashboard with name : {0} and guid: {1} successful imported
JBPCLICI0534	specify Feeds to export. Supported identifiers are: id, name or all. The expression should be enclosed in quotes. Examples: -i "id=3e0d34bf-299a-05b4f8a5" -i "name=MyFeed" -i "all"
JBPCLICI0536	Dashboards successfully exported to: {0}
JBPCLICI0537	(optional) output file
JBPCLICI0538	Dashboard with name : {0} and with guid: {1} successful exported.
JBPCLICI0539	Dashboard with name : {0} and with guid: {1} could not exported, reason: {2}
JBPCLICI0540	overwrite existing dashboards
JBPCLICI0541	User does not exist or is not authorized to import dashboards. Only user with admin privileges are able to import dashboards.
JBPCLICI0542	User does not exist or is not authorized to export dashboards. Only user with admin privileges are allowed to export dashboards.
JBPCLICI0543	File {0} already exists. Please add the overwrite option to the command to overwrite existing file name.

<b>JBPCLICI0544</b>	<b>overwrite existing data feeds</b>
<b>JBPCLICI0545</b>	<b>Data source export written to : {0}</b>
<b>JBPCLICI0546</b>	<b>Data sources imported from \: {0}</b>
<b>JBPCLICI0547</b>	<b>Data source import failed. The content of the file {0} contains none or not all required information.</b>
<b>JBPCLICI0548</b>	<b>Unexpected error uploading Data source information from zip file \: {0}</b>
<b>JBPCLICI0549</b>	<b>User doesn't exist or is not authorized to import data sources. Only user with admin privileges are able to import data sources.</b>
<b>JBPCLICI0550</b>	<b>Feed successfully exported to : {0}</b>
<b>JBPCLICI0551</b>	<b>Feeds successfully exported to: {0}</b>
<b>JBPCLICI0552</b>	<b>There are no dashboards to export.</b>
<b>JBPCLICI0553</b>	<b>There are no data feeds to export.</b>
<b>JBPCLICI0555</b>	<b>name of specify tenant (no tenant means default)</b>
<b>JBPCLICI0556</b>	<b>Only Administrators can export dashboards.</b>
<b>JBPCLICI0557</b>	<b>Only Administrators can export data feeds.</b>
<b>JBPCLICI0558</b>	<b>Only Administrators can import dashboards.</b>

---

JBPCLICI0559	Only Administrators can import data feeds
JBPCLICI0560	Exports dashboards
JBPCLICI0561	Exports data feeds
JBPCLICI0562	Exports aliases
JBPCLICI0563	specify aliases to export. Supported identifiers are: type, name or all Supported types: PPM, FILE, DATABASE, EVENT, URL, TERRACOTTA Examples: 1) -i "type=PPM" 2) -i "name=UMG_EN" 3) -i "all"
JBPCLICI0564	include jdbc driver jar files in export
JBPCLICI0565	Aliases successfully exported to: {0}
JBPCLICI0566	Aliases could not be exported to: {0}. Unknown reason.
JBPCLICI0567	Alias with identifier {0} could not be found.
JBPCLICI0568	Only administrators can export aliases.
JBPCLICI0569	There are no aliases to export.
JBPCLICI0570	Authorization failed, please check your username and password combination.
JBPCLICI0571	Alias: {0} with type: {1} successfully imported.
JBPCLICI0572	Overwrite existing aliases

JBPCLICI0573	Overwrite existing alias permissions
JBPCLICI0574	Aliases imported from : {0}
JBPCLICI0575	Imports Dashboards
JBPCLICI0576	Imports Feeds
JBPCLICI0578	Import aliases
JBPCLICI0610	Feed: {0} with guid: {1} successfully imported.
JBPCLICW0362	ERROR: {0}
JBPCLICW0385	Failed to create App, {0}
JBPCLICW0418	Role: {0} already exists. Skipping.
JBPCLICW0419	*** Mashlet {0} is a custom mashlet of type: {1}
JBPCLICW0421	*** Custom mashlet types need to be migrated separately
JBPCLICW0424	User: {0} already exists. Skipping.
JBPCLICW0429	*** Unrecognized service type :{0}. Skipping
JBPCLICW0436	****Service: {0} cannot be migrated. Please register this service manually

---

JBPLICW0477	****Reason: {0}
JBPLICW0519	Unexpected error importing App: {0}, {1}
JBPLICW0520	Provider: {0} already exists. Skipping.
JBPLICW0521	Service id: {0} - Unrecognized/unsupported authProtocol: {1}
JBPLICW0522	Unexpected error uploading App zip file : {0}, {1}
JBPLICW0523	Unrecognized responseFormat passed, returning raw response
JBPLICW0524	File name must end with .zip when exporting jdbc drivers (-j option).
JBPLICW0525	File name must end with .xml when exporting without jdbc drivers.
JBPLICW0577	Only administrators can import aliases.
JBPLICW5070	Authorization fails, please check your username and password combination.
JBPCOMMCE0062	unable to obtain license info {0}
JBPCOMMCE0069	Failed to load configuration data {0}
JBPCOMMCE0070	Failed to load config data from metadata database. Please make sure Mashzone NextGen repository is running. {0}
JBPCOMMCE0072	Failed to send mail. Please check mail server configuration in Administration area

- JBPCOMMCE0073** Data transformation error. Cause = {0}
  
- JBPCOMMCE0074** Data transformation error. No data to convert
  
- JBPCOMMCE0075** Data transformation error. Object cannot be null
  
- JBPCOMMCE0076** Data transformation error. Cause = Response object is null
  
- JBPCOMMCE0077** Failed to convert response to {0}
  
- JBPCOMMCE0079** Error removing all items from cache '{0}' : {1}
  
- JBPCOMMCE0080** Non serializable objects are not supported for Memcached CacheProvider. Use put/getFromCache instead.
  
- JBPCOMMCE0081** Cannot instantiate MemcachedProviderFactory
  
- JBPCOMMCE0082** No cache with name [{0}] has been configured in MemcachedCacheProviderFactory.
  
- JBPCOMMCE0083** Null host list
  
- JBPCOMMCE0084** No hosts in list: '{0}'
  
- JBPCOMMCE0085** Invalid server '{0}' in list: {1}
  
- JBPCOMMCE0086** Data serialization error
  
- JBPCOMMCE0087** Could not urlize value[{0}]

---

**JBPCOMMCE0088** Cannot initialize CommonServicesFactory

**JBPCOMMCE0089** Failed to parse JSON Request. JSON : {0}, error : {1}

**JBPCOMMCE0090** Couldn't find protocol version. version is a required field.

**JBPCOMMCE0091** Given protocol version is not currently supported. Version = {0}

**JBPCOMMCE0092** JUMP Protocol version cannot be empty. Please choose 1.0 or 1.1

**JBPCOMMCE0093** Parameters by name is not supported in protocol v1.0. Please use v1.1

**JBPCOMMCE0094** Error closing connection

**JBPCOMMCE0095** Keystore may not be null

**JBPCOMMCE0096** Keystore may not be null

**JBPCOMMCE0097** Unsupported algorithm exception: {0}

**JBPCOMMCE0098** Keystore exception: {0}

**JBPCOMMCE0099** Key management exception: {0}

**JBPCOMMCE0100** I/O error reading keystore/truststore file: {0}

**JBPCOMMCE0101** Parameters may not be null

**JBPCOMMCE0102 Trust manager may not be null**

**JBPCOMMCE0103 io error**

**JBPCOMMCE0104 error**

**JBPCOMMCE0105 no trust manager found**

**JBPCOMMCE0106 Parameters may not be null**

**JBPCOMMCE0107 Authentication scope may not be null**

**JBPCOMMCE0108 Authentication scope may not be null**

**JBPCOMMCE0109 Authentication scope may not be null**

**JBPCOMMCE0110 Authentication scope may not be null**

**JBPCOMMCE0111 No license found or provided license is not valid. Please apply a valid Mashzone NextGen License. Please apply a valid license <a href="/prest0/upgradelicense.jsp">here</a>**

**JBPCOMMCE0112 \*\*\*\*\* INVALID LICENSE \*\*\*\*\*  
\*\*\*\*\*: {0}**

**JBPCOMMCE0113 License key is empty. Please make sure you have applied the license.**

**JBPCOMMCE0114 ERROR: public and/or private keys were not generated!**

- 
- JBPCOMMCE0115 IO Exception while verifying: {0}
- JBPCOMMCE0116 Error verifying signature, error code: {0}, message: {1}
- JBPCOMMCE0117 license expired: {0}
- JBPCOMMCE0118 license error, operating system check: {0}
- JBPCOMMCE0119 License error: can't obtain productCode {0}
- JBPCOMMCE0120 License error: Product code expected JBP, license contains {0}
- JBPCOMMCE0121 License error: can't obtain version: {0}
- JBPCOMMCE0122 License error: version mismatch. Current product version is: {0}, but version in license is: {1}
- JBPCOMMCE0123 Checking license file: {0}
- JBPCOMMCE0124 check ok
- JBPCOMMCE0125 License error: {0}
- JBPCOMMCE0126 <h2>Reset your Mashzone NextGen password</h2>
- JBPCOMMCE0127 Cant remember your password? Dont worry about it - it happens. We can help.<br><br>
- JBPCOMMCE0128 Your username is: <b>%2%</b><br><br><b>Just click this link to reset your password</b>:<br>%3%/presto/hub/reset\_password.html?verify\_code=%4%<br><br>

JBPCOMMCE0129 **<b>Didnt ask to reset your password?</b><br>If you didnt ask for your password, its likely that another user entered your username or email address by mistake while trying to reset their password. If thats the case, you dont need to take any further action and can safely disregard this email.**

JBPCOMMCE0130 invalid BOM: null is not allowed

JBPCOMMCE0131 invalid description: null is not allowed

JBPCOMMCE0132 invalid description: empty string is not allowed

JBPCOMMCE0133 invalid input stream: null is not allowed

JBPCOMMCE0134 Could not read BOM from Stream

JBPCOMMCE0135 BOM read error

JBPCOMMCE0136 Match has more bytes than available!

JBPCOMMCE0137 Data was successful converted!

JBPCOMMCE0138 Syntax error! Usage: xml2csv-conv [-options] <source filename or url> <destination filename> Options -l <field name> Allows to set the name of the field that repeats in XML schema. -k <list of fields' names> Field' names that will be kept, separated by comma without space. -i <list of fields' names> Field' names that will be ignored, separated by comma without space. -d Returns not duplicated rows. -e <value> Value for empty data, e.g. "-" -s <value> Value for separator in CSV, e.g. "," Usage examples:

JBPCOMMCE0139 Negative values can't be set. Must be a positive number.

- 
- JBPCOMMCE0141** Minimum password length should always be a positive value less than the maximum password length.
- JBPCOMME0001** Failed to load configuration data : {0}
- JBPCOMME0002** Configuration key cannot be empty or null in - {0}.
- JBPCOMME0003** Configuration key cannot be empty or null in - {0}.
- JBPCOMME0004** Unsuppoted operation. If User Repository uses the same DB as RDS, use setRepositoryDBSetings. If not then modify userRepositoryJdbc.properties directly.
- JBPCOMME0005** Given configuration directory {0} is invalid.
- JBPCOMME0006** Please check read/write permissions on given config directory {0}.
- JBPCOMME0007** Given config path {0} is not a directory.
- JBPCOMME0008** Failed to load config data from file - {0} ...continuing to load remaining configuration data
- JBPCOMME0009** Failed to load config data from metadata database. Please make sure MashZone NextGen repository is running.
- JBPCOMME0010** Error loading configuration data : {0}
- JBPCOMME0011** Error loading configuration data : {0}
- JBPCOMME0012** HTTP error {0}

- JBPCOMME0013**    **io error {0}**
  
- JBPCOMME0014**    **error {0}**
  
- JBPCOMME0015**    **Failed to obtain PT, using PGT. Need to reauthenticate to MashZone NextGen to obtain new PGT**
  
- JBPCOMME0016**    **In order to call CAS protected services you must authenticate to MashZone NextGen using CAS.**
  
- JBPCOMME0017**    **Error getting HTTP proxy port value {0}**
  
- JBPCOMME0018**    **Authentication scope not set for HTTP proxy server {0}.**
  
- JBPCOMME0019**    **Invalid server URL...using given value as server host.**
  
- JBPCOMME0020**    **Keystore url may not be null.**
  
- JBPCOMME0021**    **HTTP error {0}**
  
- JBPCOMME0022**    **IO error {0}**
  
- JBPCOMME0023**    **error {0}**
  
- JBPCOMME0024**    **The endpoint reference is not valid: {0}.**
  
- JBPCOMME0025**    **No trust manager found**
  
- JBPCOMME0026**    **No SSO tokens are found in the request.**

---

<b>JBPCOMME0027</b>	<b>HTTP error {0}</b>
<b>JBPCOMME0028</b>	<b>IO error {0}</b>
<b>JBPCOMME0029</b>	<b>Error {0}</b>
<b>JBPCOMME0030</b>	<b>HttpClient must be an instance of AbstractHttpClient</b>
<b>JBPCOMME0031</b>	<b>No trust managers available</b>
<b>JBPCOMME0032</b>	<b>Send mail error {0}</b>
<b>JBPCOMME0033</b>	<b>Encyper is not implemented.</b>
<b>JBPCOMME0034</b>	<b>Failed to decrypt {0}</b>
<b>JBPCOMME0035</b>	<b>Unable to format date from: {0}</b>
<b>JBPCOMME0036</b>	<b>Unable to convert String to Long</b>
<b>JBPCOMME0037</b>	<b>ConfigMgr: setSessionAttribute : Cannot find HttpServletRequest object. Unable to store session attribute : {0}</b>
<b>JBPCOMME0038</b>	<b>Invalid driver jar url</b>
<b>JBPCOMME0039</b>	<b>Failed to parse service headers whitelist</b>
<b>JBPCOMME0040</b>	<b>Error in constructing RESTified URL</b>

- JBPCOMME0041**    **Error in getting server info**
  
- JBPCOMME0042**    **Failed to fill template. Returning template as it is.**
  
- JBPCOMME0043**    **Pruning xml failed... {0}**
  
- JBPCOMME0044**    **Processor does not support ADD operation.**
  
- JBPCOMME0045**    **Processor does not support REMOVE operation.**
  
- JBPCOMME0046**    **Processor does not support UPDATE operation.**
  
- JBPCOMME0047**    **Processor misconfigured. Current element is not the one that parser supports.**
  
- JBPCOMME0048**    **Not a number**
  
- JBPCOMME0049**    **Cannot convert object {0} to type {0}**
  
- JBPCOMME0050**    **Data transformation error**
  
- JBPCOMME0051**    **Error in converting XML -> JSON**
  
- JBPCOMME0052**    **Unable to convert the response to JSON format. Please retry with xml, native or soap format.**
  
- JBPCOMME0053**    **Unable to convert the response to XML format. Please retry with json or native format.**
  
- JBPCOMME0054**    **Error in converting POJO -> XML**

---

JBPCOMME0055	Error in converting POJO -> XML; {0}
JBPCOMME0056	( {0} ) is not a supported format. Sending response in service's native format
JBPCOMME0057	Data transformation error. No data to convert
JBPCOMME0058	Data transformation error. Cause = {0}
JBPCOMME0059	Unable to unmarshall dynabeans
JBPCOMME0060	Error shutting down cache: {0} : exception: {1}
JBPCOMME0061	Invalid license: {0}
JBPCOMME0062	test test
JBPCOMME0063	[RequestBuilderV1].....
JBPCOMME0064	[RequestBuilderV1].....Parameters by name is not supported in protocol v1.0. Please use v1.1.
JBPCOMME0065	Error in getting server side session expressions from request header
JBPCOMME0066	Data transformation error
JBPCOMME0067	Error removing item {0} from cache. {1}
JBPCOMME0068	Error removing item {0} from cache '{1}' : {2}

- JBPCOMME0069**    **The field {0} cannot be empty or null.**
- JBPCOMME0070**    **Exception occurred during CacheManager initialization.**  
**Explanation**    A runtime error has occurred during CacheManager initialization that prevents further usage of all Caches managed by the CacheManager.  
**Action**        See stack trace for further details and contact your administrator.
- JBPCOMME0071**    **Mail server configuration is not set. Please update mail server configuration in administration area.**
- JBPCOMME0091**    **An error occurred while bootstrapping the SAML2 library!**
- JBPCOMME0092**    **An error occurred while issuing a SAML2 assertion: Key store or key alias are not available.**
- JBPCOMME0093**    **An uncategorized error occurred while issuing a SAML2 assertion!**
- JBPCOMME0098**    **The alias {0} is reserved for internal storage.**
- JBPCOMME0099**    **The URI {0} is invalid. Expected format is terracotta://hostname:port.**
- JBPCOMME0100**    **The URI {0} is invalid. Expected format is terracotta://hostname[:port][,[hostname2[:port]],...].**
- JBPCOMMW0001**    **Invalid byproxy filter found...continuing with the remaining filters....{0}.**
- JBPCOMMW0002**    **Invalid byproxy filter found...continuing with the remaining filters...**
- JBPCOMMW0003**    **Given configuration directory has NO write permission. Updates to config files won't be possible thru Administration interface.**

- 
- JBPCOMMW0004** Cannot find SSLSocketFactory in Spring context.
- JBPCOMMW0005** Error while fixing xml, returning resulting xml as it is. Cause = {0}
- JBPCOMMW0006** Unable to flush memcached keys.
- JBPCOMMW0007** Caching failed
- JBPCOMMW0072** SUCCESS: Import of data feed {0} with guid = {1} was successful.
- JBPCOMMW0073** The following data transformations are not supported: {0}. Please adapt the data feed.
- JBPCOMMW0074** {0}. Please adapt the data feed.
- JBPCOMMW0075** XSLT preprocessing is not supported in XML data source. Please adapt the data feed.
- JBPCOMMW0076** Notes are not supported in data feeds and are discarded during migration.
- JBPCOMMW0077** FAILED: Data feed: {0} with guid: {1} can not be imported. The following data transformations are not supported: {2}. Please adapt the data feed.
- JBPCOMMW0078** FAILED: Data feed: {0} with guid: {1} can not be imported. {2} which is not supported. Please adapt the data feed.
- JBPCOMMW0079** The data feed was exported with a different edition as {0}.
- JBPCOMMW0080** FAILED: Data feed: {0} with guid: {1} can not be imported. The data feed was not exported with {2}.

- JBPCOMMW0081** FAILED: Dashboard: {0} with guid: {1} can not be imported. The dashboard was not exported with {2}.
  
- JBPCOMMW0082** FAILED: Dashboard: {0} with guid: {1} can not be imported. The widget(s) {2} is(are) not supported.
  
- JBPCOMMW0083** FAILED: Dashboard: {0} with guid: {1} can not be imported. {2} which is not supported.
  
- JBPCOMMW0084** The dashboard already exists.
  
- JBPCOMMW0085** The data feed already exists.
  
- JBPCOMMW0086** FAILED: Dashboard: {0} with guid: {1} can not be imported. The dashboard already exists.
  
- JBPCOMMW0087** FAILED: Data feed: {0} with guid: {1} can not be imported. The data feed already exists.
  
- JBPCOMMW0088** FAILED: Dashboard: {0} with guid: {1} can not be imported. The following data transformations are not supported: {2}.
  
- JBPCOMMW0089** The following data transformations are not supported: {0}. Please adapt the data feed.
  
- JBPCOMMW0090** {0} which is not supported. Please adapt the data feed.
  
- JBPCOMMW0094** SUCCESS: Import of alias {0} with type {1} was successful
  
- JBPCOMMW0095** FAILED: Import of alias {0} with type {1} already exists.

- 
- JBPCOMMW0096** There is no permission for user: {0} to access alias: {1} for type: {2}.
- JBPCOMMW0097**
- JBPEMMLCE0001** Internal Error
- JBPEMMLCE0003** Invalid Request : {0}
- JBPEMMLCE0007** Initialization error : {0}
- JBPEMMLCE0008** Schema of records to put in cache and schema registered at MetaCache do not match.
- JBPEMMLCE0009** Variable not found : {0}
- JBPEMMLCE0010** HTTP exception: {0} : {1}
- JBPEMMLCE0011** Parse Exception: {0}
- JBPEMMLCE0012** Unable to put schema to MetaCache.
- JBPEMMLCE0013** service
- JBPEMMLCE0014** inputvariable
- JBPEMMLCE0015** outputvariable
- JBPEMMLCE0016** input variables

**JBPEMMLCE0017**   **foreach**

**JBPEMMLCE0018**   **sort**

**JBPEMMLCE0019**   **group**

**JBPEMMLCE0020**   **toExpr**

**JBPEMMLCE0021**   **fromvariable**

**JBPEMMLCE0022**   **fromexpr**

**JBPEMMLCE0023**   **fromliteral**

**JBPEMMLCE0024**   **variable**

**JBPEMMLCE0025**   **annotation**

**JBPEMMLCE0026**   **expression**

**JBPEMMLCE0027**   **attribute**

**JBPEMMLCE0028**   **name**

**JBPEMMLCE0029**   **method**

**JBPEMMLCE0030**   **conditional**

---

JBPEMMLCE0031	script
JBPEMMLCE0032	keys
JBPEMMLCE0033	endpoint
JBPEMMLCE0034	missing or illegal {0}
JBPEMMLCE0035	missing or illegal {0} {1}
JBPEMMLCE0036	Error in {0} statement ( line # "{1}" ) : {2}
JBPEMMLCE0037	{0} should be a number greater or equal than 0
JBPEMMLCE0038	One of <code>actualexpr/actualvar</code> is required
JBPEMMLCE0039	<code>actualexpr</code> is required
JBPEMMLCE0040	One of <code>expectedexpr/expectedvar/literal/count/elementdepth</code> is required
JBPEMMLCE0041	Only Sequence commands can be in a Parallel command
JBPEMMLCE0042	Referenced JavaScript not found
JBPEMMLCE0043	spaces not allowed in {0}
JBPEMMLCE0044	parent

- JBPEMMLCE0045** name
  
- JBPEMMLCE0046** Assertion failed at line number [ {0} ].
  
- JBPEMMLCE0047** Unsupported source definition of type "{0}".
  
- JBPEMMLCE0048** Error, could not add URL to system classloader
  
- JBPEMMLCE0049** Key Field Not Found : {0}
  
- JBPEMMLCE0050** elem parameter must not be null!
  
- JBPEMMLCE0051** Cannot stringify null Node!
  
- JBPEMMLCE0052** XML PARSE ERROR (NO PARSERS!)
  
- JBPEMMLCE0053** null {0}
  
- JBPEMMLCE0054** IO Error in pretty print
  
- JBPEMMLCE0055** Invalid document in Throw statement. {0}
  
- JBPEMMLCE0056** {0} requires Saxon migration
  
- JBPEMMLCE0057** Error executing groovy script : {0}
  
- JBPEMMLCE0058** Illegal data type for Sort - must be Document or Element type

- 
- JBPEMMLCE0059** Error sorting data : {0}
- JBPEMMLCE0060** Error creating value of variable : {0} : {1}
- JBPEMMLCE0061** Data of subtype {0} must be processed using stream="true"
- JBPEMMLCE0062** for  
Explanation EMMML for loop
- JBPEMMLCE0063** Unable to declare variable in parent scope : {0}
- JBPEMMLCE0064** {0} to initialize variable : {1}
- JBPEMMLCE0065** Invalid cookie format
- JBPEMMLCE0066** Unable to convert document to XML
- JBPEMMLCE0067** Invalid Method
- JBPEMMLCE0068** Invalid Method in directinvoke: {0} for endpoint : {1}
- JBPEMMLCE0069** directinvoke parameter values must be of String type : {0}
- JBPEMMLCE0070** Error invoking syndication feed :: endpoint URL must be a valid RSS or Atom Feed
- JBPEMMLCE0071** Error invoking syndication feed : {0} : {1}
- JBPEMMLCE0072** Unable to find stylesheet : {0}

<b>JBPEMMLCE0073</b>	<b>startcountervalue</b>
<b>Explanation</b>	startcountervalue attribute in for loop
<b>JBPEMMLCE0074</b>	<b>Error initializing session variable : {0} - {1}</b>
<b>JBPEMMLCE0075</b>	<b>Error parsing date value : {0}; {1}</b>
<b>JBPEMMLCE0076</b>	<b>Variable not defined : {0}</b>
<b>JBPEMMLCE0077</b>	<b>Cannot find file [ {0} ]</b>
<b>JBPEMMLCE0078</b>	<b>Configuration not initialized</b>
<b>JBPEMMLCE0079</b>	<b>Unable to initialize configuration file : {0}</b>
<b>JBPEMMLCE0080</b>	<b>Error saving Config File : {0}</b>
<b>JBPEMMLCE0081</b>	<b>finalcountervalue</b>
<b>Explanation</b>	finalcountervalue attribute in for loop
<b>JBPEMMLCE0095</b>	<b>Data Transformation Error : {0}</b>
<b>JBPEMMLCE0096</b>	<b>Data Transformation Error. Cause = {0}</b>
<b>JBPEMMLCE0097</b>	<b>Data transformation error. Object cannot be null</b>
<b>JBPEMMLCE0098</b>	<b>XML format failed : {0}</b>

---

<b>JBPEMMLCE0099</b>	<b>Schema not found : {0}</b>
<b>Explanation</b>	Referenced RAQL Schema Not found in classpath
<b>Action</b>	Ensure RAQL Schema is available in JVM Classpath
<b>JBPEMMLCE0100</b>	<b><code>http://hostname:port/emml/&lt;serviceName&gt;/&lt;operationName&gt;?param1=value1&amp;param2=value2</code></b>
<b>JBPEMMLCE0101</b>	<b>Script submitted for Execution</b>
<b>JBPEMMLCE0102</b>	<b>Script not found : {0}</b>
<b>JBPEMMLCE0103</b>	<b>Refer to 'Self-Joins with a SingleDataset' in Mashzone NextGen documentation (<a href="http://www.jackbe.com/prestodocs">http://www.jackbe.com/prestodocs</a>) for performing joins using the same document.</b>
<b>JBPEMMLCE0105</b>	<b>type</b>
<b>Explanation</b>	missing type attribute in variable declaration
<b>Action</b>	specify valid type in variable declaration
<b>JBPEMMLCE0106</b>	<b>Missing mashup element in EMMML Script</b>
<b>JBPEMMLCE0107</b>	<b>Could not find macro with name [ {0} ] in namespace/file [ {1} ]</b>
<b>JBPEMMLCE0108</b>	<b>Unable to locate script file : {0}</b>
<b>JBPEMMLCE0109</b>	<b>Error parsing mashup script : {0}</b>
<b>JBPEMMLCE0110</b>	<b>Error parsing mashup script : {0} - file: {1}</b>
<b>JBPEMMLCE0111</b>	<b>Error parsing mashup script : {0} - file: {1} line: {2}</b>

- JBPEMMLCE0112** Unable to compile script : {0}
- JBPEMMLCE0113** Error : Illegal definition of operation. Operations are allowed only inside a EMMML Mashup
- JBPEMMLCE0114** Catch must be inside Try statement
- JBPEMMLCE0115** Invoke EMMML Statement is not supported in OMA version
- JBPEMMLCE0116** operation not found : {0}
- JBPEMMLCE0117** Error : Duplicate definition of Output Statement.
- JBPEMMLCE0118** Could not create a AST node for element
- JBPEMMLCE0119** Missing Mashup element in EMMML Script
- JBPEMMLCE0120** Illegal Mashup Service name : {0}
- JBPEMMLCE0121** Unable to locate Mashup service : {0}
- JBPEMMLCE0122** Error using reserved column names in user schema : {0} . Use RAQL select column aliasing or modify schema to rename these columns.
- Explanation** Certain column names like 'key' , 'value' are reserved names in Mashzone NextGen/BigMemory. Use alternate column names for these.
- Action** Use alternate column names to avoid conflicting with reserved column names.
- JBPEMMLCE0123** Could not initialize Listener registry or no Listeners found.

- 
- JBPEMMLCE0124 Unable to declare variable : {0}
- JBPEMMLCE0125 Mapping specification not found : {0}
- JBPEMMLCE0126 RAQL does not support querying JSON documents yet : {0}
- JBPEMMLCE0127 Error reading data from : {0} : {1}
- JBPEMMLCE0128 Type variable not found : {0}; Referenced in variable definition {1}
- JBPEMMLCE0129 Configuration error : {0}
- JBPEMMLCE0130 Error declaring variable : {0} : {1}
- JBPEMMLCE0131 Error converting to string : {0}
- JBPEMMLCE0132 Error filtering data : {0}
- JBPEMMLCE0133 Variable creation error : {0}
- JBPEMMLCE0134 Error creating variable : {0}
- JBPEMMLCE0135 Error evaluating expression : {0}
- JBPEMMLCE0136 Error initializing new mashup service : {0}
- JBPEMMLCE0137 Error accessing Variable names : {0}

**JBPEMMLCE0138**    **Error accessing Variable {0} : {1}**

**JBPEMMLCE0139**    **Error accessing Variables : {0}**

**JBPEMMLCE0140**    **Empty or Invalid Mashup Script**

**JBPEMMLCE0141**    **Mandatory EMMML <Output/> statement not found.**

**Explanation**        A EMMML <Output/> must be declared for every mashup.

**Action**                Declare EMMML Output statement for the mashup.

**JBPEMMLCE0142**    **Validation Error : {0}**

**JBPEMMLCE0143**    **stream variable '{0}' is not allowed in XPath/XQuery expression. To display 'stream' variables use type='stream' and previewcount='<int> or ALL' in display statement. Or else use stream='false' in raql command to serialize streams for further use in XPath/XQuery based EMMML commands or expressions.**

**Explanation**        'stream' variables are not allowed in XPath/XQuery expressions. To display 'stream' variables use type='stream' and previewcount='<int> or ALL' in display statement. Or else use stream='false' in raql command to serialize streams for further use in XPath/XQuery based EMMML commands or expressions.

**Action**                'stream' variables are not allowed in XPath/XQuery expressions. To display 'stream' variables use type='stream' and previewcount='<int> or ALL' in display statement. Or else use stream='false' in raql command to serialize streams for further use in XPath/XQuery based EMMML commands or expressions.

**JBPEMMLCE0144**    **Preview data option only available for 'stream' variables.**

**Explanation**        Preview data option only available for 'stream' variables.

**Action**                Either use 'stream' variable OR remove previewcount option from display statement.

**JBPEMMLCE0145**    **Error evaluating expression : {0}**

**JBPEMMLCE0146**    **Unauthorized to execute EMMML "{0}" statement (check with Administrator).**

---

**JBPEMMLCE0147** Annotation variable must be document or element; cannot be a NodeList

**JBPEMMLCE0148** Expected count {0} but was {1}

**JBPEMMLCE0149** Expected depth {0} but was {1}

**JBPEMMLCE0150** Unsupported comparison of return types.

**JBPEMMLCE0151** Expected {0} but was {1}

**JBPEMMLCE0152** Expected non equal values but got equal values.

**JBPEMMLCE0153** Expected a null value but got a non-null value

**JBPEMMLCE0154** Expected a non-null value but got a null value

**JBPEMMLCE0155** Destination variable not found : {0}

**JBPEMMLCE0156** Error assigning value : {0}

**JBPEMMLCE0157** Source variable not found : {0}

**JBPEMMLCE0158** Error in assignment : {0}

**JBPEMMLCE0159** Cache name not specified : cache='<cacheName>'.

**JBPEMMLCE0160** Cache not found: {0}

- JBPEMMLCE0161** Unknown Cache operation : {0}
- JBPEMMLCE0162** Illegal operation in cache : {0} ; must be 'store' or 'load'
- JBPEMMLCE0163** Scope={0} is invalid. Expected {1}|{2}
- JBPEMMLCE0164** Cannot use identical data source names with different properties : Conflict between ( {0} ) and ( {1} )
- JBPEMMLCE0165** Illegal 'type' value, display type attribute must be 'stream' or 'document' only.  
**Explanation** Illegal 'type' value, display type attribute must be 'stream' or 'document' only.  
**Action** use type='stream' or 'document'
- JBPEMMLCE0166** Unable to locate file : '{0}'
- JBPEMMLCE0167** No default Datasource defined. Use <datasource/> statement to define a SQL datasource.
- JBPEMMLCE0168** Data source not defined : {0}
- JBPEMMLCE0169** Illegal input variable in dbxml statement.
- JBPEMMLCE0170** Illegal input variable data type in dbxml statement.
- JBPEMMLCE0171** Service Invocation timed out.
- JBPEMMLCE0172** Error executing directinvoke : {0}
- JBPEMMLCE0173** Missing or empty previewcount.  
**Explanation** previewcount attribute must have a valid value.  
**Action** Specify valid count in previewcount attribute

---

JBPEMMLCE0174	<b>Error invoking external service : {0} : {1}</b>
JBPEMMLCE0175	<b>SOAP Exception : Status Code : {0}</b>
JBPEMMLCE0176	<b>REST Exception : Status Code : {0}</b>
JBPEMMLCE0177	<b>previewcount must not be negative number.</b>
Explanation	previewcount must not be negative number.
Action	Specify positive count or ALL for previewcount value.
JBPEMMLCE0178	<b>previewcount can only be used with stream variables (i.e., with type='stream')</b>
Explanation	previewcount can only be used with stream variables (i.e., with type='stream'), they cannot be used with Document types.
Action	Either remove type='stream' or use a stream variable for display
JBPEMMLCE0179	<b>Error executing statement : {0}</b>
JBPEMMLCE0180	<b>Error filtering data : {0}</b>
JBPEMMLCE0181	<b>Item expression in ForEach command is empty</b>
JBPEMMLCE0182	<b>{0} - no parent variable scope found</b>
JBPEMMLCE0183	<b>Macro Function table is empty</b>
JBPEMMLCE0184	<b>Macro definition not found : {0}</b>
JBPEMMLCE0185	<b>Use type="stream" and previewcount ="&lt;n&gt;" to display stream variable : {0}</b>
Explanation	Use type='stream' and previewcount ='<n>' to display stream variable
Action	Use type='stream' and previewcount ='<n>' to display stream variable

**JBPEMMLCE0186** Unable to access variable : {0} : {1}

**JBPEMMLCE0187** Application with name {0} not found

**JBPEMMLCE0188** Error executing script : {0}

**JBPEMMLCE0190** Snapshot datasource not found.

**JBPEMMLCE0191** Invalid input [{0}]. Input must be a document or a node list.

**JBPEMMLCE0192** Unable to access Cache. Internal Error. Try restarting server

**JBPEMMLCE0193** Invalid HTML parser specificaton : {0}

**JBPEMMLCE0195** Unsupported XML entity: {0}

**JBPEMMLCECE0001** Schema not found : {0}

**Explanation** Referenced RAQL Schema is not found

**Action** Ensure RAQL Schema file is in Classpath

**JBPEMMLCECE0002** {0} requires Saxon migration

**JBPEMMLCECE0003** Invalid Document

**JBPEMMLCECE0004** 'types' attribute must specify type for each parameter in 'params'

**Explanation** JDBC Types for each parameter in 'params' attribute must be specified in 'types' attribute.

**Action** Specify JDBC Type for each parameter in 'params'

---

**JBPEMMLCECE0005 Illegal or Unsupported Type : {0}**

**Explanation**        Illegal or Unsupported Type

**Action**                Specify valid data Type

**JBPEMMLCECE0006 Variable not found : {0}**

**JBPEMMLCECE0007 Variable not defined: {0}**

**JBPEMMLCECE0010 Error adding macro : {0} : {1}**

**JBPEMMLCECE0012 Unable to Invoke - {0}**

**JBPEMMLCECE0013 Missing script.**

**JBPEMMLCECE0014 Error saving service : {0}**

**JBPEMMLCECE0016 Error publishing service - {0}**

**JBPEMMLCECE0019 Error updating service details : {0}**

**JBPEMMLCECE0020 Cannot update service.**

**JBPEMMLCECE0021 Error updating script: {0}**

**JBPEMMLCECE0023 Error converting to string : {0}**

**JBPEMMLCECE0024 Error creating variable : {0}**

**JBPEMMLCECE0025 Variable creation error : {0}**

**JBPEMMLCECE0026 Configuration error : {0}**

**JBPEMMLCECE0027 Error declaring variable : {0}**

**JBPEMMLCECE0028 Validation Error : {0}**

**JBPEMMLCECE0029 Cannot access Mashzone NextGen Meta Repository**

**JBPEMMLCECE0033 Transaction already committed or rolled back**

**JBPEMMLCECE0034 Error in Mashzone NextGen Cache : {0}**

**JBPEMMLCECE0035 Configuration not initialized**

**JBPEMMLCECE0036 Error invoking external Service : {0} : {1}**

**JBPEMMLCECE0046 Invalid Command Specified (mapRequestToExpr): {0}**

**JBPEMMLCECE0047 Failed to transform request data.**

**JBPEMMLCECE0048 Unable to execute query: {0}**

**JBPEMMLCECE0049 DB Import failed.**

**JBPEMMLCECE0063 Unexpected parsing exception reading service data.**

**JBPEMMLCECE0064 Unexpected io exception reading service data.**

**JBPEMMLCECE0070 Failed to register service - {0}; Reason - {1}**

**JBPEMMLCECE0071 Pre-registration test failed: {0}**

**JBPEMMLCECE0072 Object with name [{0}] already exists.**

**JBPEMMLCECE0073 No object with name : {0} Exists**

**JBPEMMLCECE0074 Error saving object : {0}**

**JBPEMMLCECE0075 Could not fetch driver classpath**

**JBPEMMLCECE0081 no emml type found for: {0}**

**JBPEMMLCECE0082 No property file of name {0} found on classpath!**

**JBPEMMLCECE0084 Missing Service name.**

**JBPEMMLCECE0086 Empty or Invalid Mashup Script**

**JBPEMMLCECE0087 Type not found in Service {0} ({1})**

**JBPEMMLCECE0089 Error in {0} statement ( line # {1} ) : Only one {2} element is allowed**

**JBPEMMLCECE0090 'macros' library file must only be used with -lib option**

**JBPEMMLCECE0091** Illegal Macro definition -- root element must be 'macro'

**JBPEMMLCECE0093** Missing mashup service name.

**JBPEMMLCECE0096** Mashup Service not found : {0}

**JBPEMMLCECE0097** A service with name ({0}) is already registered. Please choose another name and try again.

**JBPEMMLCECE0098** Cannot update service with status '{0}' : {1}

**JBPEMMLCECE0099** Operation name may not be changed.

**JBPEMMLCECE0104** Error : Missing Mashup id

**JBPEMMLCECE0105** Error : Missing Mashup sample XML

**JBPEMMLCECE0106** Error registering mashup output type: {0}

**JBPEMMLCECE0108** Mashzone NextGen Service name not found : {0}

**JBPEMMLCECE0109** Transaction support is only available for Database Services

**JBPEMMLCECE0113** Application Context has not been initialized

**JBPEMMLCECE0114** BigMemory datasource : {0} not registered in Mashzone NextGen.

**JBPEMMLCECE0115** No Dynamic cache configuration (dynamiccache.xml) found in classpath

**JBPEMMLCECE0116 Security Profile {0} is not supported**

**JBPEMMLCECE0117 No default Datasource defined. Use <datasource/> statement to define a SQL datasource.**

**JBPEMMLCECE0118 Data source not defined : {0}**

**JBPEMMLCECE0120 Couldn't find service using ({0})**

**JBPEMMLCECE0121 Couldn't find operation using ({0})**

**JBPEMMLCECE0122 Reference to unknown Service Name : {0}**

**JBPEMMLCECE0124 Data source not found : {0}**

**JBPEMMLCECE0125 Cannot use identical datasource names with different Properties : Conflict between ( {0} ) and ( {1} )**

**JBPEMMLCECE0129 Login failed. Reason: {0}**

**JBPEMMLCEE0001 Parse Exception: {0}**

**JBPEMMLCEE0004 Initialization error : {0}**

**JBPEMMLCEE0005 Error in converting to JSON**

**JBPEMMLCEE0006 The argument 'date' may not be null.**

**JBPEMMLCEE0007 The argument 'days' may not be null.**

**JBPEMMLCEE0008** Error evaluating expression : {0}

**JBPEMMLCEE0009** Error executing Mashup Script [{0}.emml]: {1}

**JBPEMMLCEE0010** The argument 'seconds' may not be null.

**JBPEMMLCEE0011** Error saving macro: {0}

**JBPEMMLCEE0012** The first argument 'dateText' may not be null.

**JBPEMMLCEE0013** The second argument 'fromFormat' may not be null.

**JBPEMMLCEE0014** The third argument 'toFormat' may not be null.

**JBPEMMLCEE0015** Error registering mashup service : {0}

**JBPEMMLCEE0016** The first argument 'document' may not be null.

**JBPEMMLCEE0017** Error unregistering service : {0}

**JBPEMMLCEE0018** Error updating service : {0}

**JBPEMMLCEE0022** Error activating Mashup Service : {0}

**JBPEMMLCEE0030** Error in get Data/Value as String

**JBPEMMLCEE0031** Error in setValue

---

**JBPEMMLCEE0032** Response data is : {0}

**JBPEMMLCEE0037** Error generating Mashup Service Interface : {0}

**JBPEMMLCEE0038** Command Invocation Thread Interrupted : {0}

**JBPEMMLCEE0039** Error executing Join Service : {0}

**JBPEMMLCEE0040** Error mapping Parameters : {0}

**JBPEMMLCEE0041** Error invoking CompositeJoinService : {0}

**JBPEMMLCEE0042** Unable to perform data transformation : {0}

**JBPEMMLCEE0043** Unable to execute service : {0} : {1} : {2}

**JBPEMMLCEE0044** Failed to register Mashzone NextGen EMMML Service : {0} : {1}

**JBPEMMLCEE0045** Unable to create Field Ref : {0}

**JBPEMMLCEE0050** Exception retrieving catalogs : {0}

**JBPEMMLCEE0051** Exception retrieving schemas : {0}

**JBPEMMLCEE0052** Exception retrieving tables : {0}

**JBPEMMLCEE0053** Exception retrieving views : {0}

JBPEMMLCEE0054 Exception retrieving procedures : {0}

JBPEMMLCEE0055 Exception retrieving metadata : {0}

JBPEMMLCEE0056 Exception retrieving table names : {0}

JBPEMMLCEE0057 Exception retrieving view names : {0}

JBPEMMLCEE0058 Exception retrieving procedure names : {0}

JBPEMMLCEE0059 Failed to connect to data source.

JBPEMMLCEE0060 Exception importing data source: {0}

JBPEMMLCEE0061 SQL Exception thrown releasing db connection : {0}

JBPEMMLCEE0062 {0} Next Exception: {1}

JBPEMMLCEE0065 Unable to create project xml

JBPEMMLCEE0066 Unrecognized item name [{0}]

JBPEMMLCEE0067 Schema not recognized: [{0}]

JBPEMMLCEE0068 Catalog not recognized: [{0}]

JBPEMMLCEE0069 Failed To validate provider: [{0}]

**JBPEMMLCEE0076 Failed to upload file**

**JBPEMMLCEE0077 Error generating NSD for Mashup Service - {0}, Error: {1}**

**JBPEMMLCEE0078 Error resolving type : {0}**

**JBPEMMLCEE0079 Error generating NSD for Visual Service - {0}, Error: {1}**

**JBPEMMLCEE0080 Failed to register EMMML-SQL mashup service**

**JBPEMMLCEE0083 Script not found : {0}**

**JBPEMMLCEE0085 No service with name : {0} exists**

**JBPEMMLCEE0088 Service not found : {0}**

**JBPEMMLCEE0092 Specify a mashup service name.**

**JBPEMMLCEE0094 Empty mashup script for {0}**

**JBPEMMLCEE0095 Mashup not found: {0}**

**JBPEMMLCEE0100 Active service cannot be unregistered : {0}**

**JBPEMMLCEE0101 Empty mashup script for {0}**

**JBPEMMLCEE0102 Error retrieving mashup Script : {0}**

**JBPEMMLCEE0103 Error extracting Mashup Script : {0}**

**JBPEMMLCEE0107 Error retrieving Service info : {0}**

**JBPEMMLCEE0110 initializeFault failed : {0}**

**JBPEMMLCEE0111 Error Parsing Response data to xml: {0}.**

**JBPEMMLCEE0112 Error invoking service - {0} - {1}**

**JBPEMMLCEE0119 PrestoCache: Unable to locate emml-cache.xml - Cache configuration file.**

**JBPEMMLCEE0123 Error: Failed to locate Mashzone NextGen Service for registration : {0}**

**JBPEMMLCEE0126 No database driver file specified**

**JBPEMMLCEE0127 The following classpath entries are invalid: {0}**

**JBPEMMLCEE0128 Failed to load JDBC driver '{0}'. Please check that the class name and class path settings are correct.**

**JBPEMMLCEW0001 Unable to read configuration for profiler log file**

**JBPEMMLCEW0002 Was not allowed to read check file existence, file:[{0}].**

**JBPEMMLCEW0003 [ {0} ] does not exist.**

**JBPEMMLCEW0004 JSON to XML Conversion Failed : {0}**

---

**JBPEMMLCW0001** Exception in listener: {0}

**JBPEMMLCW0002** Unable to read configuration for profiler log file

**JBPEMMLCW0003** Profiler could not write to log file

**JBPEMMLCW0004** Was not allowed to read check file existence, file:[ {0} ].

**JBPEMMLCW0005** [{0}] does not exist.

**JBPEMMLCW0006** Invalid byproxy filter found...continuing with the remaining filters....{0}

**JBPEMMLCW0009** Error parsing return : using result as string. {0} ( {1} )

**JBPEMMLCW0010** warning : no outputvariable specified for sqlUpdate

**JBPEMMLCW0104** Illegal fetchSize value - must be positive count of rows to fetch

**Explanation** Must be positive count ( $\geq 0$ ) of rows to fetch

**JBPEMMLCW0194** Illegal period value - must not describe a negative time period

**Explanation** Must be positive period

**JBPEMMLE0001** Expected snapshot timestamp super-column ss\_ts. Found invalid super-column definition(s): {0}.

**JBPEMMLE0002** Internal Error : {0}

**JBPEMMLE0003** Unknown datasource type for variable {0}.

- JBPEMMLE0004**    **Error processing request : {0}**
  
- JBPEMMLE0005**    **Load Mashups failed : {0}**
  
- JBPEMMLE0006**    **Error Executing Mashup: {0}**
  
- JBPEMMLE0008**    **Error in converting to JSON**
  
- JBPEMMLE0009**    **Failed to load source-definition for var {0}.**
  
- JBPEMMLE0012**    **Unable to Parse XML : {0}**
  
- JBPEMMLE0047**    **addURL error**
  
- JBPEMMLE0060**    **Error reading Data: {0}**
  
- JBPEMMLE0061**    **Error reading data as binary stream : {0}**
  
- JBPEMMLE0062**    **Error reading data as char stream : {0}**
  
- JBPEMMLE0073**    **Error Initializing {0}**
  
- JBPEMMLE0081**    **Error getting HTTP proxy port value**
  
- JBPEMMLE0082**    **AuthenticationScope not set for HTTP proxy server**
  
- JBPEMMLE0104**    **Unable to locate EMMML Script : {0}**

---

JBPEMMLE0105	Unable to parse EMMML Script : {0}
JBPEMMLE0122	Error saving snapshot : {0}
JBPEMMLE0141	Unable to retrieve Content-Type : {0}
JBPEMMLE0143	Error in get Data/Value as String
JBPEMMLE0144	Error in setValue
JBPEMMLE0165	Illegal number format : {0}
JBPEMMLE0173	Could not parse as html : using result as string
JBPEMMLE0177	Error parsing html : {0}
JBPEMMLE0178	InitializeFault failed : {0}
JBPEMMLE0185	Parallel: Error executing command : {0}
JBPEMMLW0007	ConfigMgr: setSessionAttribute : Cannot find HttpServletRequest object. Unable to store session attribute : {0}
JBPEMMLW0008	error while fixing xml, returning resulting xml as it is. Cause = {0}
JBPEMMLW0011	Error closing database connection. {0}
JBPEMMLW0012	Unable to compile macro with name [{0}] in script [{1}]

- JBPMZCE0001**      **Failed to delete MashZone event source.**
  
- JBPMZCE0002**      **Import of administration settings failed. Details: {0}**
  
- JBPMZCE0003**      **Input parameter "{0}" is undefined**
  
- JBPMZCE0004**      **Unable to delete folder {0}.**
  
- JBPMZCE0006**      **Export of {0} "{1}" failed.**
  
- JBPMZCE0007**      **Unable to read archive "{0}".**
  
- JBPMZCE0009**      **Unable to add included data feed "{0}" to archive "{1}".**
  
- JBPMZCE0010**      **Alias definition "{0}" does not exist.**
  
- JBPMZCE0013**      **Export of administration settings failed.**
  
- JBPMZCE0014**      **Unable to write info file for "{0}".**
  
- JBPMZCE0018**      **Type "{0}" is not supported.**
  
- JBPMZCE0019**      **Archive "{0}" does not contain the entry "{1}".**
  
- JBPMZCE0020**      **The archive "{0}" does not contain any dashboards and data feeds.**
  
- JBPMZCE0021**      **Unable to import the {0} "{1}" due to incompatible license edition {2}.**

---

JBPMZCE0022	Cannot invoke MashZone until configured with proper mashzone.base.url
JBPMZCE0023	Failed to delete MashZone feed
JBPMZCE0024	reasonHeaderName must be specified
JBPMZCE0025	Error {0}
JBPMZCE0026	Error saving datafeed
JBPMZCE0027	ok {0}
JBPMZCE0028	no response
JBPMZCE0029	ok
JBPMZCE0030	ok
JBPMZCE0031	Response should not be null
JBPMZCE0032	Error: {0}
JBPMZCE0033	Error saving event source
JBPMZCE0034	ok:
JBPMZCE0035	The key {1} of the info file of the directory "{0}" has the invalid value "Dashboard".

- JBPMZCE0036**      **Import of data feed "{0}" failed.**
- JBPMZCE0037**      **The key {1} of the info file of the directory "{0}" has the invalid value "Data feed".**
- JBPMZCE0038**      **The key {1} of the info file of the directory "{0}" has the invalid value "Resource alias".**
- JBPMZCE0040**      **The key {1} of the info file of the directory "{0}" has the invalid value "unknown".**
- JBPMZCE0056**      **The archive "{0}" does not contain any alias definitions.**
- JBPMZCE0057**      **Import of dashboard "{0}" failed.**
- JBPMZCE0058**      **{0} "{1}" requires license edition "{2}". Reason: {3}**
- JBPMZCE0059**      **Import of the dashboard "{0}" is supported only from version {1}. Please update your installation, if required.**
- JBPMZCE0060**      **Import of the data feed "{0}" is supported only from version {1}. Please update your installation, if required.**
- JBPMZCE0061**      **Unable to extract dashboard info file "{0}".**
- JBPMZCE0062**      **Unable to extract data feed info file "{0}".**
- JBPMZCE0063**      **Import of data feed "{0}" as attachment failed. Therefore, the data feed is unable to return correct data.**
- JBPMZCE0064**      **Import of data feed "{0}" successful.**

---

JBPMZCE0065	The archive file does not contain any alias definitions of this type.
JBPMZCE0066	Alias definition "{0}" already exists.
JBPMZCE0067	Only a single EDA connection is supported. Please adapt the configuration to be imported accordingly.
JBPMZCE0072	Unable to process resource "{0}".
JBPMZCE0073	No write privileges assigned to resource {0}.
JBPMZCE0076	No execution privileges assigned to data feed "{0}".
JBPMZCE0077	No edit privileges assigned to data feed {0}.
JBPMZCE0078	You do not have the privilege required to edit a data feed.
JBPMZCE0079	Unable to find file "{0}".
JBPMZCE0080	Data query warning
JBPMZCE0081	Source system error
JBPMZCE0082	Favorite "{0}" is not supported.
JBPMZCE0083	PPM alias "{0}" is not supported.
JBPMZCE0084	The specified PPM authentication is not supported.

JBPMZCE0085	The specified PPM authentication is not supported.
JBPMZCE0086	Unable to find PPM configuration for GUID "{0}".
JBPMZCE0088	Error reading Castor mapping file. Details: {0}
JBPMZCE0089	Object type "{0}" is not supported.
JBPMZCE0090	Condition "{0}" insufficient.
JBPMZCE0091	Condition "guid or revision information missed" insufficient.
JBPMZCE0092	Condition "revision incomplete" insufficient.
JBPMZCE0093	The object with internal ID "{0}" does not exist.
JBPMZCE0094	For internal ID "{0}", the saved revision number ("{1}") is smaller than the one queried ("{2}"). Invalid query or system status.
JBPMZCE0095	Compression failed.
JBPMZCE0096	Decompression failed.
JBPMZCE0097	Access denied.
JBPMZCE0098	Permission to use method "{0}" denied.
JBPMZCE0099	The conditions "{0}" for running the interface "{1}" have not been met.

---

JBPMZCE0100	Unable to extract properties file "{0}".
JBPMZCE0101	Configuration key "{0}" exists multiple times.
JBPMZCE0102	The configuration "{0}" is addressed via JNDI and can therefore not be updated for technical reasons.
JBPMZCE0103	Error communicating with Mashzone NextGen's API ({0}).
JBPMZCE0104	Registration of registration object "{0}" in Mashzone NextGen failed.
JBPMZCE0105	Registration of registration object "{0}" in Mashzone NextGen failed. Details: {1}
JBPMZCE0106	Object type "{0}" is not supported.
JBPMZCE0109	Unable to create connection from connection pool.
JBPMZCE0110	The database result of the SQL query "{0}" on the database "{1}" did not return any meta data.
JBPMZCE0111	The following error occurred when converting the database result of the SQL query "{0}" on database "{1}": {2}
JBPMZCE0112	Error creating column information.
JBPMZCE0113	The following error occurred when connecting to database "{0}": {1}
JBPMZCE0115	The following error occurred when running SQL query "{0}" on database "{1}": {2}

- JBPMZCE0116**      **Unable to connect to database "{0}" because all database connections are in use. Please try again later.**
  
- JBPMZCE0117**      **Unable to connect to database because no database configuration with the name "{0}" exists.**
  
- JBPMZCE0118**      **Unable to determine database meta data connecting to database "{0}".**
  
- JBPMZCE0119**      **Unable to find JDBC driver class connecting to database "{0}".**
  
- JBPMZCE0120**      **Unable to determine valid JDBC driver class connecting to database "{0}".**
  
- JBPMZCE0121**      **Unable to register JDBC driver class connecting to database "{0}".**
  
- JBPMZCE0122**      **The database connection with the alias "{0}" is currently not active.**
  
- JBPMZCE0123**      **The instance of the database connection pool with the alias "{0}" is being terminated and cannot be used.**
  
- JBPMZCE0124**      **Internal error**
  
- JBPMZCE0125**      **Previous error:**
  
- JBPMZCE0126**      **Please specify a valid value or select a valid numerical column.**
  
- JBPMZCE0127**      **Data feed "{0}" contains a cycle.**
  
- JBPMZCE0128**      **The data feed contains invalid characters. Please check if all CSV and XML sources of the data feed are extracted with the appropriate character set.**

---

JBPMZCE0129	You do not have the read privilege for the data feed "{0}".
JBPMZCE0130	You do not have the read privilege for a data feed.
JBPMZCE0131	Unable to address event source "{0}". The event source addressed may no longer exist.
JBPMZCE0132	There are no columns for horizontal iteration.
JBPMZCE0133	Not supported data type "{0}"
JBPMZCE0134	The table already contains a column named "{0}".
JBPMZCE0135	A column named "{0}" does not exist in the table.
JBPMZCE0136	A column named "{0}" does not exist in data source "{1}".
JBPMZCE0137	Column "{0}" does not exist in the start table.
JBPMZCE0138	An unknown operator is used in operator "{0}" in data feed "{1}".
JBPMZCE0139	"{0}" is an invalid number.
JBPMZCE0140	Unable to determine value of input parameter "{0}".
JBPMZCE0141	"{0}" is an invalid date.
JBPMZCE0142	An input parameter is not numerical.

- JBPMZCE0143**      **Invalid input parameter type "{0}".**
  
- JBPMZCE0144**      **The new column name "{0}" already exists.**
  
- JBPMZCE0145**      **The column with the old name "{0}" was not assigned a new column name.**
  
- JBPMZCE0146**      **The copy of the column with the old name "{0}" was not assigned a new column name.**
  
- JBPMZCE0147**      **The start operator is not a single-value operator.**
  
- JBPMZCE0148**      **Data source "{0}" has no columns.**
  
- JBPMZCE0149**      **Data source "{0}" does not contain data.**
  
- JBPMZCE0150**      **Data source "{0}" has no column information in row {1}.**
  
- JBPMZCE0151**      **At least one column must be maintained.**
  
- JBPMZCE0152**      **The column "{0}" exists in the table, but is not of the 'Date' type.**
  
- JBPMZCE0153**      **The column "{0}" exists in the table, but is not of the 'Number' type.**
  
- JBPMZCE0154**      **Starting the event source "{0}" failed.**
  
- JBPMZCE0155**      **Event Service error**
  
- JBPMZCE0156**      **Unable to find event type "{0}".**

---

<b>JBPMZCE0157</b>	<b>Error retrieving existing event types.</b>
<b>JBPMZCE0158</b>	<b>Creating the event source "{0}" failed.</b>
<b>JBPMZCE0159</b>	<b>Unable to retrieve configuration for event source "{0}".</b>
<b>JBPMZCE0160</b>	<b>Initializing the event source "{0}" failed.</b>
<b>JBPMZCE0161</b>	<b>Unable to find EDA connection "{0}".</b>
<b>JBPMZCE0162</b>	<b>Unable to find EDA connections.</b>
<b>JBPMZCE0163</b>	<b>An event source with the alias "{0}" does not exist.</b>
<b>JBPMZCE0164</b>	<b>Starting the event source "{0}" failed. Reason: {1}</b>
<b>JBPMZCE0165</b>	<b>Stopping the event source "{0}" failed. Reason: {1}</b>
<b>JBPMZCE0166</b>	<b>Deleting the event source "{0}" failed. Reason: {1}</b>
<b>JBPMZCE0167</b>	<b>Initializing the event source "{0}" failed. Reason: {1}</b>
<b>JBPMZCE0168</b>	<b>JNDI connection test of the event source "{0}" failed. Reason: {1}</b>
<b>JBPMZCE0169</b>	<b>Stopping the event source "{0}" failed.</b>
<b>JBPMZCE0170</b>	<b>Deleting the event source "{0}" failed.</b>

- JBPMZCE0171**      **Castor mapping for the EDA connection failed.**
  
- JBPMZCE0172**      **JNDI connection test for EDA connection "{0}" failed.**
  
- JBPMZCE0173**      **Unable to parse event type name "{0}".**
  
- JBPMZCE0174**      **Unable to convert event type "{0}".**
  
- JBPMZCE0175**      **Unable to retrieve columns for event type "{0}".**
  
- JBPMZCE0176**      **Unable to find Connection Factories.**
  
- JBPMZCE0177**      **Unable to find topics for EDA connection "{0}".**
  
- JBPMZCE0178**      **Error checking Event Type Store path.**
  
- JBPMZCE0179**      **Unable to initialize EDA connection "{0}".**
  
- JBPMZCE0180**      **Invalid Event Type Store path.**
  
- JBPMZCE0181**      **Unable to load Event Type Store.**
  
- JBPMZCE0182**      **The maximum number of event sources ({0}) has been reached.**
  
- JBPMZCE0183**      **The column "{0}" exists in the table, but is not of the 'Text' type.**
  
- JBPMZCE0184**      **Both start tables are missing.**

---

JBPMZCE0185	The left start table is missing.
JBPMZCE0186	The right start table is missing.
JBPMZCE0187	Both key columns are missing.
JBPMZCE0188	The right key column is missing.
JBPMZCE0189	The left key column is missing.
JBPMZCE0190	The operator does not have a start operator.
JBPMZCE0191	Operator "{0}" does not have a start operator.
JBPMZCE0192	{0} text values are longer than {1} characters. They have to be shortened to {1} characters.
JBPMZCE0193	Data source "{0}" has less than {1} rows. Unable to determine column names from row {1}.
JBPMZCE0194	The initial text value has more than {0} characters. It has been shortened to {0} characters.
JBPMZCE0195	The input text value has more than {0} characters. It has been shortened to {0} characters.
JBPMZCE0196	{0} text values are too long and have been shortened in line with the restrictions stipulated by the license.
JBPMZCE0197	The operator result contains {0} rows. Only {1} rows can be processed. The rows in excess of that number will not be considered.

- JBPMZCE0198**      **The operator result contains more than {0} rows. Only {0} rows can be processed. The rows in excess of that number will not be considered.**
- JBPMZCE0199**      **The operator result contains {0} columns. Only {1} columns can be processed.**
- JBPMZCE0200**      **At least one column does not have a value.**
- JBPMZCE0201**      **The precision of operator "{0}" is not set or the associated single-value operator does not return any value.**
- JBPMZCE0202**      **The precision of operator "{0}" is supplied by a single-value operator that is not of the 'Number' type.**
- JBPMZCE0203**
- JBPMZCE0207**      **Error replacing values in column "{0}": The data type of the value to be set does not match the data type of the column.**
- JBPMZCE0208**      **Error comparing columns "{0}" and "{1}" The columns have different data types and therefore cannot be compared.**
- JBPMZCE0209**      **Invalid time unit for result cache time for data feed "{0}".**
- JBPMZCE0210**      **Invalid join mode "{0}".**
- JBPMZCE0211**      **"{0}" could not be compiled into css file.**
- JBPMZCE0212**      **"{0}" is not a directory.**
- JBPMZCE0213**      **The comparison criteria in the right table have the same value multiple times. Enable the option 'Allow multiple values' of the link operator to perform this operation.**

---

JBPMZCE0214	Key columns "{0}" and "{1}" are not of the same data type.
JBPMZCE0215	Error calculating data feed {0}.
JBPMZCE0216	Please specify a 100% value for data feed "{0}".
JBPMZCE0217	Please specify a 0% value for data feed "{0}".
JBPMZCE0218	Error inserting value in table column "{0}". Value "{1}" is not numerical.
JBPMZCE0228	Error inserting value in table column "{0}". Value "{1}" is not a date.
JBPMZCE0229	Error evaluating a condition. Column "{0}" is not of the data type "{1}" (current comparison value: "{2}").
JBPMZCE0230	Error evaluating a condition. The comparison value is not of the data type "{0}" (current comparison value: "{1}").
JBPMZCE0234	The data feed with the ID "{0}" does not exist.
JBPMZCE0235	The year "{0}" is BC and is not supported.
JBPMZCE0236	"{0}" is an invalid date format.
JBPMZCE0237	Data feed "{0}" does not have an output operator.
JBPMZCE0238	Unable to open data source "{0}".
JBPMZCE0239	Source "{0}" returns the following error: "{1}"

JBPMZCE0240	Source "{0}" returns the following warning: "{1}"
JBPMZCE0241	An error occurred during extraction of the data source {0}.
JBPMZCE0242	An error occurred during extraction of the data source.
JBPMZCE0243	URL "{0}" is invalid.
JBPMZCE0244	Unable to find sheet "{0}" in data source "{1}". Data is extracted from the first sheet of the workbook ("2").
JBPMZCE0245	Unable to find sheet "{0}" in data source "{1}".
JBPMZCE0246	Unable to find sheet "{0}" in data source "{1}". Data source does not contain sheets.
JBPMZCE0247	Data source does not contain sheets.
JBPMZCE0248	Data source "{0}" is not a valid Excel file.
JBPMZCE0249	Data source "{0}" is larger than {1} MB. It cannot be imported.
JBPMZCE0250	Data source "{0}" is password-protected or not a valid Excel file. Password-protected files cannot be opened.
JBPMZCE0251	The row from which the column names are to be determined was not specified or is outside the range of 1 to 65536.
JBPMZCE0252	The server does not support the character set "{0}".

---

JBPMZCE0253	Unable to convert specified file "{0}" to a document.
JBPMZCE0254	The PPM data source does not contain columns, the following error occurred: "{0}".
JBPMZCE0255	Unable to convert data of the PPM data source to a document.
JBPMZCE0256	An error occurred during preprocessing. Please check the XSLT file used.
JBPMZCE0257	Unable to parse resulting file to a document.
JBPMZCE0258	No valid aggregation type specified for column "{0}".
JBPMZCE0259	Unable to convert {0} of {1} rows from source column "{2}", they remain empty in target column "{3}".
JBPMZCE0260	Unable to convert value {0} to target format.
JBPMZCE0261	{0} of {1} rows do not contain a value in all columns used by the operation. The missing values were not included in the calculation.
JBPMZCE0262	The source column {0} is of the type "{1}". It cannot be converted to target type "{2}" and remains empty in the results table.
JBPMZCE0263	Index column "{0}" contains {1} empty cells. The corresponding rows of the feed table will not be included in the aggregation.
JBPMZCE0264	The index column "{0}" must not be one of the columns to be aggregated.
JBPMZCE0265	Google denied the coordinates request.

JBPMZCE0266	Invalid coordinate request.
JBPMZCE0267	No URL signing key was specified in for using the Google Geocoding service. Without this key, only {0} addresses can be retrieved per operator.
JBPMZCE0268	Unable to resolve {0} of {1} addresses from column "{2}".
JBPMZCE0269	The URL signing key specified for using the Google Geocoding service is too short (less than 4 characters).
JBPMZCE0270	An invalid URL signing key was specified in for using the Google Geocoding service.
JBPMZCE0271	Feed calculation canceled because Google did not deliver any results within "{0}" seconds. Possible reason: A URL signing key is missing. Without this key, you can only submit a certain number of requests per day.
JBPMZCE0272	Feed calculation canceled because Google did not deliver any results within "{0}" seconds.
JBPMZCE0273	The specified encoding "{0}" is not supported.
JBPMZCE0274	No address column specified. Please specify a valid address column.
JBPMZCE0275	The Geocoding operator does not execute because the Google Maps API terms were not accepted in the Administration module.
JBPMZCE0276	Source: Database
JBPMZCE0277	Source: PPM (URL-based)

---

<b>JBPMZCE0281</b>	<b>Source: PPM</b>
<b>JBPMZCE0282</b>	<b>Source: ARIS table</b>
<b>JBPMZCE0283</b>	
<b>JBPMZCE0287</b>	
<b>JBPMZCE0332</b>	<b>Error communicating with Event Service.</b>
<b>JBPMZCE0333</b>	<b>Object type "{0}" is not supported.</b>
<b>JBPMZCE0334</b>	<b>URI "{0}" is invalid.</b>
<b>JBPMZCE0335</b>	<b>URI "{0}" is locked.</b>
<b>JBPMZCE0336</b>	<b>URL "{0}" is invalid.</b>
<b>JBPMZCE0337</b>	<b>Unable to establish connection to URL "{0}". Please check the proxy settings.</b>
<b>JBPMZCE0338</b>	<b>Unable to establish connection to URL "{0}" within {1} seconds. Please check the proxy settings.</b>
<b>JBPMZCE0339</b>	<b>Unable to find PPM connection for alias "{0}".</b>
<b>JBPMZCE0340</b>	<b>Unable to establish connection to URL "{0}". Please check the proxy settings and whether the connection is available under the specified URL.</b>
<b>JBPMZCE0341</b>	<b>Invalid user/password combination.</b>

JBPMZCE0342	The query failed because PPM "{0}" does not support it.
JBPMZCE0343	Unable to load resource "{0}". The certificate used has expired.
JBPMZCE0344	Unable to load resource "{0}". The certificate used is not valid yet.
JBPMZCE0345	Unable to open input stream on resource "{0}".
JBPMZCE0346	Unable to extract directory "{0}".
JBPMZCE0347	Directory "{0}" does not exist.
JBPMZCE0348	Target "{0}" does not exist.
JBPMZCE0349	Target "{0}" is not a directory.
JBPMZCE0350	Unable to establish connection to resource "{0}". Status "{1}" is returned.
JBPMZCE0354	Error calculating data feed.
JBPMZCE0355	Access denied
JBPMZCE0356	Too many table columns.
JBPMZCE0357	Invalid column type.
JBPMZCE0358	Wrong value type.

---

JBPMZCE0359	Error calculating operator.
JBPMZCE0360	Error processing data.
JBPMZCE0361	Missing operator
JBPMZCE0362	Incorrect rows in the result of an operator.
JBPMZCE0363	Missing table column
JBPMZCE0364	The configuration of an operator is incorrect.
JBPMZCE0365	Name collision in table columns.
JBPMZCE0366	Missing operator
JBPMZCE0367	A column was not assigned a new name.
JBPMZCE0368	Internal error
JBPMZCE0369	Error determining input parameter.
JBPMZCE0370	Invalid input parameter type.
JBPMZCE0371	A source is not available.
JBPMZCE0372	A source does not return the expected data.

- JBPMZCE0373**      **Invalid URL.**
  
- JBPMZCE0374**      **Access denied**
  
- JBPMZCE0375**      **Error reading from CSV source.**
  
- JBPMZCE0376**      **The CSV source does not contain a column named "{0}". This may have been caused by changing options over an existing column configuration. Please recreate the CSV operator.**
  
- JBPMZCE0377**      **The CSV source contains a column with an invalid name. It is invalid, because it contains a double quote, which is not acceptable as part of the name. If the double quote was meant as a masking character, that must be specified accordingly. The invalid name is: {0}**
  
- JBPMZCE0378**      **No execution privileges assigned to dashboard "{0}".**
  
- JBPMZCE0379**      **No edit privileges assigned to dashboard "{0}".**
  
- JBPMZCE0380**      **Resource too large.**
  
- JBPMZCE0381**      **The feature "{0}" is not supported in the edition "{1}".**
  
- JBPMZCE0382**      **Resource "{0}" exceeds the maximum allowed data size of {1} KB and is therefore not being processed.**
  
- JBPMZCE0386**      **Invalid SSO authentication against PPM.**
  
- JBPMZCE0387**      **Error loading.**

---

JBPMZCE0388	Error determining alias URL.
JBPMZCE0389	Unable to load resource "{0}".
JBPMZCE0390	Error calling Web service at source "{0}". {1}
JBPMZCE0391	Alias should not be null or empty.
JBPMZCE0392	Path should not be null or empty.
JBPMZCE0393	The included feed doesn't have any result columns.
JBPMZCE0396	System error
JBPMZCE0399	You do not have the privilege required to edit a dashboard.
JBPMZCE0401	A required starting table is missing.
JBPMZCE0404	Undefined parameter: {0}
JBPMZCE0405	Ambiguous parameter: {0}
JBPMZCE0406	Syntax error in RAQL query.
JBPMZCE0407	Syntax error in line {0}.
JBPMZCE0408	Syntax error in line {0}, expected one of {1}

JBPMZCE0409	Semantic error in RAQL query.
JBPMZCE0410	Semantic error in line {0}: {1}
JBPMZCE0411	Error executing RAQL query.
JBPMZCE0418	<b>At least one required source data feed</b>
Explanation	Answer to the question "what is missing here?"
JBPMZCE0421	Error accessing Dataset "{0}"
JBPMZCE0423	Connection failed
JBPMZCE0424	URL alias definition "{0}" does not exist.
JBPMZCE0425	The Event Emitting Target "{0}" does not exist.
JBPMZCE0426	The event "{0}" is in an invalid format.
JBPMZCE0427	The Event Target "{0}" does not exist.
JBPMZCE0428	Event Types and/or their attributes could not be determined. The Apama system defined in alias [{0}] is not available.
JBPMZCE0429	Dataset identifier "{0}" does not observe required pattern [CONNECTION_ALIAS].[STORENAME].
JBPMZCE0430	Sample size for deriving schema of a Dataset must be either a positive integer or ALL.

---

JBPMZCE0431	Source: VA
JBPMZCE0432	Connection lost
JBPMZCE0433	Connection to Event Service lost
JBPMZCE0434	Error extracting cell definitions from Dataset "{0}".
JBPMZCE0435	Error running query on Dataset "{0}".
JBPMZCE0436	You do not have permission to send an event to Event Target "{0}".
JBPMZCE0437	No data found - could not derive any columns. Use the "Configure columns" dialog to configure manually.
JBPMZCE0438	The event could not be sent. The Apama instance "{0}" is not be reachable.
JBPMZCE0445	Column config contains multiple key columns: {0}, {1}.
JBPMZCE0446	Column config does not specify a key column.
JBPMZCI0005	Export to archive "{0}" successful.
JBPMZCI0008	Included data feed "{0}" was successfully added to archive "{1}".
JBPMZCI0011	Export of administration settings to archive "{0}" successful.
JBPMZCI0012	The following alias definitions were exported: {0}

- JBPMZCI0015**      **Empty archive "{0}" was not created.**
  
- JBPMZCI0016**      **Export of dashboard "{0}" into archive "{1}" successful.**
  
- JBPMZCI0017**      **Export of data feed "{0}" into archive "{1}" successful.**
  
- JBPMZCI0039**      **No conflicts for import of unknown "{0}" (Rev. {1}).**
  
- JBPMZCI0041**      **No conflicts for import of dashboard "{0}" (Rev. {1}).**
  
- JBPMZCI0042**      **No conflicts for import of data feed "{0}" (Rev. {1}).**
  
- JBPMZCI0043**      **No conflicts for import of resource alias "{0}" (Rev. {1}).**
  
- JBPMZCI0044**      **Import of unknown "{0}" (Rev. {1}) with last change date "{2}" updates the existing entry (Rev. {3}) of "{4}".**
  
- JBPMZCI0045**      **Import of dashboard "{0}" (Rev. {1}) with last change date "{2}" updates the existing entry (Rev. {3}) of "{4}".**
  
- JBPMZCI0046**      **Import of data feed "{0}" (Rev. {1}) with last change date "{2}" updates the existing entry (Rev. {3}) of "{4}".**
  
- JBPMZCI0047**      **Import of resource alias "{0}" (Rev. {1}) with last change date "{2}" updates the existing entry (Rev. {3}) of "{4}".**
  
- JBPMZCI0048**      **Import of unknown "{0}" (Rev. {1}) with last change date "{2}" collides with existing entry (Rev. {3}) with identical date "{4}".**
  
- JBPMZCI0049**      **Import of dashboard "{0}" (Rev. {1}) with last change date "{2}" collides with existing entry (Rev. {3}) with identical date "{4}".**

---

JBPMZCI0050	Import of data feed "{0}" (Rev. {1}) with last change date "{2}" collides with existing entry (Rev. {3}) with identical date "{4}".
JBPMZCI0051	Import of resource alias "{0}" (Rev. {1}) with last change date "{2}" collides with existing entry (Rev. {3}) with identical date "{4}".
JBPMZCI0052	Import of unknown "{0}" (Rev. {1}) with last change date "{2}" collides with existing entry (Rev. {3}) with more current date "{4}".
JBPMZCI0053	Import of dashboard "{0}" (Rev. {1}) with last change date "{2}" collides with existing entry (Rev. {3}) with more current date "{4}".
JBPMZCI0054	Import of data feed "{0}" (Rev. {1}) with last change date "{2}" collides with existing entry (Rev. {3}) with more current date "{4}".
JBPMZCI0055	Import of resource alias "{0}" (Rev. {1}) with last change date "{2}" collides with existing entry (Rev. {3}) with more current date "{4}".
JBPMZCI0068	Import of administration settings from archive "{0}" successful.
JBPMZCI0069	The following alias definitions were imported: {0}
JBPMZCI0070	
JBPMZCI0071	Revision "{0}" of internal ID "{1}" is obsolete. Please reload the object.
JBPMZCI0074	The data feed with internal ID "{0}" is locked by another user and cannot be edited.
JBPMZCI0075	Unable to save data feed "{0}" because embedded data feed "{1}" creates an infinite loop. Please resolve the infinite loop and save again.

JBPMZCI0087	Version before 5.1
JBPMZCI0107	Unable to import database column "{0}" due to its data type ({1}). The column is not included in the data feed.
JBPMZCI0108	Column "{0}" is empty and cannot be imported properly. Please use SQL/RAQL alias names (<column name> AS <new column name>) in order to uniquely identify columns that intentionally exist multiple times.
JBPMZCI0114	Connection test with database "{0}" successful.
JBPMZCI0204	Horizontal iteration
JBPMZCI0205	Vertical iteration
JBPMZCI0206	Values
JBPMZCI0219	Apama properties not set.
JBPMZCI0220	Apama connectivity was not initialized because of incorrect port specification.
JBPMZCI0221	Apama connection failed after {0} attempts.
JBPMZCI0222	Error initializing event source with alias "{0}".
JBPMZCI0223	Error starting event source with alias "{0}".
JBPMZCI0224	Error stopping event source with alias "{0}".

---

JBPMZCI0225	Unknown storage model"{0}".
JBPMZCI0226	Schema definition doesn't match buffer strategy. There is no group field defined.
JBPMZCI0227	Schema definition doesn't match buffer strategy. The specified column with key information "{0}" can't be found in the scenario.
JBPMZCI0231	Event Type Store not set, can't reinit EDA connections.
JBPMZCI0232	Event Type Store not set, can't reinit Event Type cache.
JBPMZCI0233	Error starting event source with alias "{0}": There is neither event type nor endpoint (topic) specified.
JBPMZCI0278	Source: MS Excel file
JBPMZCI0279	Retrieve geolocations
JBPMZCI0280	Source: CSV file
JBPMZCI0284	Source: PPM component
JBPMZCI0285	Source: wM Events
JBPMZCI0286	Source: BigMemory
JBPMZCI0288	wM Optimize
JBPMZCI0289	Source: XML file

<b>JBPMZCI0290</b>	<b>Source: BigMemory</b>
<b>JBPMZCI0291</b>	<b>Aggregate</b>
<b>JBPMZCI0292</b>	<b>Concatenate data feeds</b>
<b>JBPMZCI0293</b>	<b>Average</b>
<b>JBPMZCI0294</b>	<b>Change data type</b>
<b>JBPMZCI0295</b>	<b>Copy data feed</b>
<b>JBPMZCI0296</b>	<b>Concatenate texts</b>
<b>JBPMZCI0297</b>	<b>Round up/down date</b>
<b>JBPMZCI0298</b>	<b>Duplicate column</b>
<b>JBPMZCI0299</b>	<b>Insert column</b>
<b>JBPMZCI0300</b>	
<b>JBPMZCI0301</b>	<b>Delete column</b>
<b>JBPMZCI0302</b>	<b>Filter by date</b>
<b>JBPMZCI0303</b>	<b>Filter rows</b>

<b>JBPMZCI0304</b>	<b>Limit result</b>
<b>JBPMZCI0305</b>	<b>Find text index</b>
<b>JBPMZCI0306</b>	<b>Goal accomplishment</b>
<b>JBPMZCI0307</b>	<b>Source: Data feed</b>
<b>JBPMZCI0308</b>	<b>Combine data feeds</b>
<b>JBPMZCI0309</b>	<b>Source: Manual data</b>
<b>JBPMZCI0310</b>	<b>Arithmetic</b>
<b>JBPMZCI0311</b>	<b>Rename column</b>
<b>JBPMZCI0312</b>	<b>Conditional replace</b>
<b>JBPMZCI0313</b>	<b>Replace text</b>
<b>JBPMZCI0314</b>	<b>Round up/down</b>
<b>JBPMZCI0315</b>	<b>Replace date fields</b>
<b>JBPMZCI0316</b>	<b>Move date</b>
<b>JBPMZCI0317</b>	<b>Extract text</b>

<b>JBPMZCI0318</b>	<b>Convert text</b>
<b>JBPMZCI0319</b>	<b>Value to column</b>
<b>JBPMZCI0320</b>	<b>Create URL</b>
<b>JBPMZCI0321</b>	<b>Change data type</b>
<b>JBPMZCI0322</b>	<b>Copy single value</b>
<b>JBPMZCI0323</b>	<b>User input - Number</b>
<b>JBPMZCI0324</b>	<b>User input - Text</b>
<b>JBPMZCI0325</b>	<b>User input - Date</b>
<b>JBPMZCI0326</b>	<b>Column to value</b>
<b>JBPMZCI0327</b>	<b>Runtime info</b>
<b>JBPMZCI0328</b>	<b>Merge single texts</b>
<b>JBPMZCI0329</b>	<b>Aggregate geolocations</b>
<b>JBPMZCI0330</b>	<b>Move single date</b>
<b>JBPMZCI0331</b>	<b>Error starting event source with alias "{0}": There is neither event type nor endpoint (topic) specified.</b>

---

JBPMZCI0351	Unable to find included data feed "{0}".
JBPMZCI0352	The data feed "{0}" contains an incomplete or incorrect data feed operator.
JBPMZCI0400	RAQL
JBPMZCI0412	Possible loss of precision.
JBPMZCI0413	The values in column "{0}" of type {1} will be converted to type 'double'.
JBPMZCI0414	Text conversion.
JBPMZCI0415	The values in column "{0}" of type {1} will be converted to a text.
JBPMZCI0416	Possible truncation.
JBPMZCI0417	The values in column "{0}" will be truncated if they have more than {1} characters.
JBPMZCI0422	Source: TCStore
JBPMZCI0439	Source: JSON file
JBPMZCW0353	Encode single value
JBPMZCW0383	You are using default values.
JBPMZCW0384	Error processing data.

JBPMZCW0385	Unable to process all rows of the table.
JBPMZCW0394	Database column "{0}" is ignored
JBPMZCW0395	The database column "{0}" can not be read because of its datatype ({1}). Therefore the column is not contained in data feed.
JBPMZCW0397	Charset changed
JBPMZCW0398	The charset will be changed to the system's default charset because there was no charset configured for the CSV operator. In case of parsing errors, you can change the encoding in the UI.
JBPMZCW0402	Invalid results
JBPMZCW0403	The operation "{0}" leads to invalid results in {1} of {2} rows.
JBPMZCW0419	Warning occurred during execution
JBPMZCW0420	Warning {0}
JBPMZCW0440	Invalid precision value
JBPMZCW0441	Precision: Negative value is not supported
JBPMZCW0442	Precision: Decimal places will be ignored
JBPMZCW0443	The key column has been renamed to {0} as there already is a cell named {1}.

---

<b>JBPMZCW0444</b>	<b>Renamed key column.</b>
<b>JBPMZCW0447</b>	<b>Renamed column</b>
<b>JBPMZCW0448</b>	<b>The column name "{0}" was ambiguous and had to be renamed. Please see the "Configure columns" dialog for more details.</b>
<b>JBPMZE0001</b>	<b>Error while getting emml template</b>
<b>JBPMZE0002</b>	<b>IllegalState: No emml template!</b>
<b>JBPMZE0003</b>	<b>IllegalState: I dont have a rtbs emml template!</b>
<b>JBPMZE0004</b>	<b>Unable to transform current user to json, mz authn likely to fail</b>
<b>JBPMZE0005</b>	<b>Cannot invoke MashZone until configured with proper mashzone.base.url</b>
<b>JBPMZE0006</b>	<b>Got error response</b>
<b>JBPMZE0007</b>	<b>Cannot invoke MashZone until configured with proper mashzone.base.url</b>
<b>JBPMZE0008</b>	<b>Exception calling runFeed</b>
<b>JBPMZE0009</b>	<b>Feed returns error response.</b>
<b>JBPMZE0010</b>	<b>Cannot invoke MashZone until proper mashzone.base.url is set</b>
<b>JBPMZE0011</b>	<b>Cannot invoke MashZone until configured with proper mashzone.base.url</b>

<b>JBPMZE0012</b>	<b>Cannot invoke rtbs until rtbs.base.url is set</b>
<b>JBPMZE0013</b>	<b>Error calling rtbs {0}</b>
<b>JBPMZE0014</b>	<b>Cannot invoke rtbs until rtbs.base.url is set</b>
<b>JBPMZE0015</b>	<b>Unable to config parser</b>
<b>JBPMZE0016</b>	<b>Error parsing response</b>
<b>JBPMZE0017</b>	<b>Error parsing response</b>
<b>JBPMZE0018</b>	<b>Error testing connection to MashZone: {0}</b>
<b>JBPMZE0019</b>	<b>Error saving datafeed:</b>
<b>JBPMZE0020</b>	<b>Error testing connection to rtbs: {0}</b>
<b>JBPMZE0021</b>	<b>Error saving buffer:</b>
<b>JBPMZE0022</b>	<b>PPM connection could not be imported.</b>
<b>JBPMZE0023</b>	<b>PPM connection could not be delivered.</b>
<b>JBPMZE0024</b>	<b>PPM connection could not be updated.</b>
<b>JBPMZE0025</b>	<b>PPM connection could not be stored.</b>

---

<b>JBPMZE0026</b>	<b>PPM is currently not available. Please ensure that the PPM system is running.</b>
<b>JBPMZE0027</b>	<b>PPM connection could not be removed.</b>
<b>JBPMZE0028</b>	<b>PPM connection could not be exported.</b>
<b>JBPMZE0029</b>	<b>PPM connection could not be imported.</b>
<b>JBPMZE0030</b>	<b>Event service connection could not set alias name.</b>
<b>JBPMZE0031</b>	<b>Event service connection could not set configuration path.</b>
<b>JBPMZE0032</b>	<b>Event service connection could not check event source path.</b>
<b>JBPMZE0033</b>	<b>Event service connection could not deliver alias definitions.</b>
<b>JBPMZE0034</b>	<b>Event service connection could not delete alias definition.</b>
<b>JBPMZE0035</b>	<b>Event service connection could not restart Event Services.</b>
<b>JBPMZE0036</b>	<b>Event service connection could not import service.</b>
<b>JBPMZE0037</b>	<b>Event service connection could not deliver attributes.</b>
<b>JBPMZE0038</b>	<b>Event service connection could not set service definition.</b>
<b>JBPMZE0039</b>	<b>Event service connection could not restart all running services.</b>

<b>JBPMZE0040</b>	<b>Event service connection could not export service configuration.</b>
<b>JBPMZE0041</b>	<b>Event service connection could not stop service.</b>
<b>JBPMZE0042</b>	<b>Event service connection could not service.</b>
<b>JBPMZE0044</b>	<b>Could not retrieve a message from file. Please check if the desired language or at least the fallback language {0} is contained!</b>
<b>JBPMZE0045</b>	<b>Welcome text must not contain 'script' tags!</b>
<b>JBPMZE0046</b>	<b>Could not load welcome text file {0}.</b>
<b>JBPMZE0047</b>	<b>Event service configuration path could not be retrieved.</b>
<b>JBPMZE0048</b>	<b>DES repository path could not be retrieved.</b>
<b>JBPMZE0049</b>	<b>DES repository path could not be set.</b>
<b>JBPMZE0050</b>	<b>Wrong structure in analysis metaData</b>
<b>JBPMZE0051</b>	<b>Error during loading dashboard template</b>
<b>JBPMZE0052</b>	<b>Error during creation of json dashboard definition</b>
<b>JBPMZE0053</b>	<b>Internal Server error</b>
<b>JBPMZE0054</b>	<b>Dashboard properties missing</b>

---

<b>JBPMZE0055</b>	<b>In the used template the dashboard properties are missing!</b>
<b>JBPMZE0056</b>	<b>Chart type not available</b>
<b>JBPMZE0057</b>	<b>The chart type {0} does not exist in the template</b>
<b>JBPMZE0058</b>	<b>The Widget with the ID:{0} does not exist in the dashboard</b>
<b>JBPMZE0059</b>	<b>Widget not exists</b>
<b>JBPMZE0060</b>	<b>The template is not available</b>
<b>JBPMZE0061</b>	<b>The template for the dashboard creation is not available!</b>
<b>JBPMZE0062</b>	<b>Widget identifier missing</b>
<b>JBPMZE0063</b>	<b>Widget identifier is not set in the used template!</b>
<b>JBPMZE0064</b>	<b>Wrong column definition</b>
<b>JBPMZE0065</b>	<b>The column definition is not properly defined in the request. Name or type are empty.</b>
<b>JBPMZE0066</b>	<b>Wrong parameter definition</b>
<b>JBPMZE0067</b>	<b>Missing function right</b>
<b>JBPMZE0068</b>	<b>The parameter definition is not properly defined in the request. Name or type are empty.</b>

<b>JBPMZE0069</b>	<b>Error during argument validation</b>
<b>JBPMZE0070</b>	<b>The user has not the function right to create dashboards</b>
<b>JBPMZE0071</b>	<b>The value axis uses a column that is not available in the data set</b>
<b>JBPMZE0072</b>	<b>The category axis uses a column that is not available in the data set</b>
<b>JBPMZE0073</b>	<b>The partition axis uses a column that is not available in the data set</b>
<b>JBPMZE0074</b>	<b>One of the filter widgets in the parameter list uses a column that is not available in the data set</b>
<b>JBPMZE0075</b>	<b>A filter widget tries to establish a filter dependency to a not existing input</b>
<b>JBPMZE0076</b>	<b>Unsupported column type {0}</b>
<b>JBPMZE0077</b>	<b>Unsupported parameter list type {0}</b>
<b>JBPMZE0078</b>	<b>Multiple value axes are not supported in combination with a partition axis</b>
<b>JBPMZE0079</b>	<b>A category axis of type text can not have a format!</b>
<b>JBPMZE0080</b>	<b>A category axis of type date can not be sorted!</b>
<b>JBPMZE0081</b>	<b>A partition axis of type text can not have a format!</b>
<b>JBPMZE0082</b>	<b>Unsupported filter widget {0}</b>

---

<b>JBPMZE0083</b>	<b>Unsupported axis data type {0}</b>
<b>JBPMZE0084</b>	<b>Unsupported sort order {0}</b>
<b>JBPMZE0085</b>	<b>Unsupported partition type {0}</b>
<b>JBPMZE0086</b>	<b>Unsupported aggregation {0}</b>
<b>JBPMZE0087</b>	<b>Unsupported data point type {0}</b>
<b>JBPMZE0088</b>	<b>Unsupported legend position {0}</b>
<b>JBPMZE0089</b>	<b>Unsupported line type {0}</b>
<b>JBPMZE0090</b>	<b>Unsupported chart type</b>
<b>JBPMZW0001</b>	<b>MashZone integration will not work until 'mashzone.base.url' is configured.</b>
<b>JBPMZW0002</b>	<b>rtbs integration will not work until 'rtbs.base.url' is configured.</b>
<b>JBPMZW0003</b>	<b>Feed meta data api returns error.</b>
<b>JBPMZW0004</b>	<b>Got error: {0}, message {1}</b>
<b>JBPMZW0005</b>	<b>Got warning: {0}, message {1}</b>
<b>JBPMZW0006</b>	<b>Feed search api returns error.</b>

**JBPMZW0043** Only administrators are allowed to change the configuration.

**JBPMZW0091** In a bubble chart one one measure is allowed in the value axis.

**JBPRAQLCORECE0003** duplicate definition of column {0}

**JBPRAQLCORECE0004** Error when parsing the define dataset statement : {0}

**JBPRAQLCORECE0005** **JBPEMMLCECE0093** Unable to parse type : {0}

**JBPRAQLCORECE0006** Illegal column type : "{0}" for {1}

**JBPRAQLCORECE0007** Unable to locate file : {0}

**JBPRAQLCORECE0008** Error retrieving the schema information of an Apama Cache: {0}

**JBPRAQLCORECE0009** The source or query "{0}" to be de-registered is unknown.

**JBPRAQLCORECE0021** The mask "{0}" defining the temporal format is not valid.

**JBPRAQLCORECE0022** Date conversion error for value "{0}".

**JBPRAQLCORECE0023** Unsupported date field "{0}".

**JBPRAQLCORECE0024** Conversion to date failed for input string "{0}".

**JBPRAQLCORECE0025** The given window function does not accept a bounded frame given in the window specification.

**JBPRAQLCORECE0026** Measure must be either euclidean, manhattan, cosine, tanimoto, or squaredeuclidean.

**JBPRAQLCORECE0027** PN approach is not supported for geometric mean.

**JBPRAQLCORECE0028** Unable to create an aggregation factory instance for input types {0}.

**JBPRAQLCORECE0029** The parameter "k" needs to be an integer greater than 0.

**JBPRAQLCORECE0030** The parameter "iterations" needs to be an integer greater than 0.

**JBPRAQLCORECE0031** Number of clusters (k) has to be greater than 0.

**JBPRAQLCORECE0032** Number of iterations needs to be greater than 0.

**JBPRAQLCORECE0033** Unknown measure {0}. Valid measures are: {1}.

**JBPRAQLCORECE0034** Invalid or missing delimiter.

**JBPRAQLCORECE0035** Invalid or missing field index.

**JBPRAQLCORECE0036** Getting an adapter factory for {0} was not successful.

**JBPRAQLCORECE0037** Unknown RAQL window function type: {0}

**JBPRAQLCORECE0050** Error loading class from {0}.

**JBPRAQLCORECE0051** End index < start index.

**JBPRAQLCORECE0055** The function `decimal()` is deprecated. Please use the standard SQL CAST functions instead.

**JBPRAQLCORECE0056** The function `number()` is deprecated. Please use the standard SQL CAST functions instead.

**JBPRAQLCORECE0057** The function `round(Object, Object)` is deprecated. Please use the standard SQL functions `ROUND(Number)` or `ROUND(Number, INTEGER)` instead.

**JBPRAQLCORECE0058** Unknown function {0}

**JBPRAQLCORECE0059** Failed to add function

**JBPRAQLCORECE0060** Invalid dataFormat for reader based source:

**JBPRAQLCORECE0061** Illegal kmeans function Usage. Valid arguments are ( '`colname1, column_name2,...`', # of clusters, # of iterations, '`euclidean | manhattan | cosine | tanimoto | squaredeuclidean`' )

**JBPRAQLCORECE0062** column names(1st argument) missing

**JBPRAQLCORECE0063** # of clusters(2nd argument) must be greater than 0

**JBPRAQLCORECE0064** missing order by clause for rank().

**JBPRAQLCORECE0065** # of iterations (3rd argument) must be greater than 0

**JBPRAQLCORECE0066** missing order by clause for rank()

**JBPRAQLCORECE0067** Available commands:

JBPRAQLCORECE0068 Missing parameter <library-name>

JBPRAQLCORECE0069 Missing parameter <library-name>

JBPRAQLCORECE0070 - Artefact type

JBPRAQLCORECE0071 ---

JBPRAQLCORECE0072 Unknown command

JBPRAQLCORECE0073 The library directory {0} does not exist.

JBPRAQLCORECE0074 The library directory {0} is not readable.

JBPRAQLCORECE0075 The path {0} does not reference a directory.

JBPRAQLCORECE0076 Illegal column conversion to numeric : {0}

JBPRAQLCORECE0077 Illegal column conversion to decimal : {0}. {1}

JBPRAQLCORECE0078 rethrow QueryFallbackException

JBPRAQLCORECE0079 Column not indexed : {0}. Falling back to native RAQL processing.

JBPRAQLCORECE0080 Column '{0}' not found in cache.

JBPRAQLCORECE0081 Unimplemented relational operator : {0}

**JBPRAQLCORECE0082** Regex pattern must be String type

**JBPRAQLCORECE0083** Function reference : {0} - No pushdown to Search; fallback to native processing.

**JBPRAQLCORECE0084** Arithmetic expression - No pushdown to Search; fallback to native processing

**JBPRAQLCORECE0085** column not indexed : {0}. Falling back to native RAQL processing.

**JBPRAQLCORECE0086** Subquery expression - Pushdown not supported yet; fallback to native processing

**JBPRAQLCORECE0087** Illegal Column name : {0} - must be String type.

**JBPRAQLCORECE0088** Unknown Cache Value. All queried Attributes(columns) must be indexed

**JBPRAQLCORECE0089** Error closing connection

**JBPRAQLCORECE0090** Unsupported date field : {0}

**JBPRAQLCORECE0091** View not found :

**JBPRAQLCORECE0092** DBViews :

**JBPRAQLCORECE0093** DefaultAbstractBag.clear: failed to delete {0}

**JBPRAQLCORECE0094** Temporary directory doesn't exists. Trying to create: {0}

**JBPRAQLCORECE0095** Successfully created temporary directory: {0}

**JBPRAQLCORECE0096** Temporary directory already exists: {0}

**JBPRAQLCORECE0097** Unable to create temporary directory: {0}

**JBPRAQLCORECE0098** No such method found: {0} : {1}

**JBPRAQLCORECE0099** Error in function :

**JBPRAQLCORECE0100** {0} is not valid UDF libs directory.

**JBPRAQLCORECE0101** UDF libs directory {0} defined by system property {1}, is not valid.

**JBPRAQLCORECE0102** System property {0} is not defined. Attempted to use default UDF libs directory {1}, but is not valid directory. Either set system property {0} to valid UDF libs directory or insure that default UDF libs directory {1} exists.

**JBPRAQLCORECE0103** RaqlFunc annotation must specify not empty name, when used at class level.

**JBPRAQLCORECE0105** Failed to read library configuration

**JBPRAQLCORECE0106** Failed to create ClassLoader for lib directory {0}

**JBPRAQLCORECE0107** Failed to create library. Library directory does not exists. {0}

**JBPRAQLCORECE0110** Failed to read function's description from annotations.

**JBPRAQLCORECE0111** RaqlFunc annotation can only be applied to classes which implement AnalyticFunction interface.

**JBPRAQLCORECE0112** {0} is not a valid UDF library directory.

**JBPRAQLCORECE0113** UDF libs directory {0} defined by system property {1} is not valid.

**JBPRAQLCORECE0114** System property {0} is not defined. Attempted to use default UDF library directory {1}, but is not valid directory. Either set system property {0} to a valid UDF library directory or ensure that default UDF library directory {1} exists.

**JBPRAQLCORECE0115** Comparison method violates its general contract!

**JBPRAQLCORECE0116** Comparison method violates its general contract!

**JBPRAQLCORECE0117** fromIndex({0}) > toIndex({1})

**JBPRAQLCORECE0118** No such field index

**JBPRAQLCORECE0119** Not a field!

**JBPRAQLCORECE0120** No translation function specified for operator type: {0}

**JBPRAQLCORECE0121** No translation function specified for expression type: {0}

**JBPRAQLCORECE0122** Not implemented

**JBPRAQLCORECE0123** Error serializing Tuple : Unknown datatype :

**JBPRAQLCORECE0124** Illegal Tuple in SortFile

**JBPRAQLCORECE0125** Error deserializing Tuple : Unknown datatype :

JBPRAQLCORECE0126 Error reading data source :

JBPRAQLCORECE0127 Type conversion unavailable for : {0}

JBPRAQLCORECE0128 Unsupported conversion : str to {0}

JBPRAQLCORECE0129 Error converting to number : {0} : {1}

JBPRAQLCORECE0130 Date conversion error : {0} : {1}

JBPRAQLCORECE0131 Conversion to date not supported for :

JBPRAQLCORECE0132 No toInt conversion support for :

JBPRAQLCORECE0133 Decimal Type conversion unavailable for : {0}

JBPRAQLCORECE0134 Double Type conversion unavailable for : {0}

JBPRAQLCORECE0135 Error converting to number : {0}

JBPRAQLCORECE0136 Conversion Error :string to decimal : {0} : {1}

JBPRAQLCORECE0137 {0} does not provide a constructor with signature `String[]`, which is obligatory when passing a non-empty `String` array with parameters.

JBPRAQLCORECE0138 Unable to create instance of {0}.

JBPRAQLCORECE0139 {0} does not provide a constructor with signature `String[]`, which is obligatory.

**JBPRAQLCORECE0140** ScanIterator has been retired. Sorry!!

**JBPRAQLCORECE0141** File not found : {0}

**JBPRAQLCORECE0142** No data sources found for view : {0}

**JBPRAQLCORECE0143** Unable to extract schema information for identifier: {0}

**JBPRAQLCORECE0144** No Records found.

**JBPRAQLCORECE0145** Error fetching Tuple : {0}

**JBPRAQLCORECE0146** Error fetching Tuple : exception - {0}

**JBPRAQLCORECE0147** File not found : {0}

**JBPRAQLCORECE0148** No data sources found for Table : {0}

**JBPRAQLCORECE0149** spilling....

**JBPRAQLCORECE0150** Unable to create tmp file to spill to disk

**JBPRAQLCORECE0151** Unable to spill contents to disk

**JBPRAQLCORECE0152** Error closing spill

**JBPRAQLCORECE0153** The trim character for the TRIM function must have exactly one character.

**JBPRAQLCORECE0154** Failed to delete file: {0}

**JBPRAQLCORECE0155** Function {0} is not an analytical function

**JBPRAQLCORECE0156** Unable to initialize function : {0}. Check RAQL documentation for legal UDF interface contract.

**JBPRAQLCORECE0157** Function {0}, which resolves to {1} cannot be found

**JBPRAQLCORECE0158** Failed to resolve function name {0}

**JBPRAQLCORECE0159** function must have exactly one sub-expression.

**JBPRAQLCORECE0160** function must not have more than one sub-expression.

**JBPRAQLCORECE0161** Function could not be resolved:

**JBPRAQLCORECE0162** Repository error: the entry to retrieve is unknown.

**JBPRAQLCORECE0163** A {0} operation must not have more than two sub-expressions.

**JBPRAQLCORECE0164** A {0} operation must have exactly one sub-expression.

**JBPRAQLCORECE0165** A {0} operation must not have more than one sub-expression.

**JBPRAQLCORECE0166** A {0} operation must have exactly two sub-expressions.

**JBPRAQLCORECE0167** A {0} operation must not have more than two sub-expressions.

**JBPRAQLCORECE0168** Unknown operation expression type {0}.

**JBPRAQLCORECE0169** Unknown operation expression type {0}.

**JBPRAQLCORECE0170** Failed to create LibReloader

**JBPRAQLCORECE0171** Unrecognised watch key {0}

**JBPRAQLCORECE0172** Repository error: the entry to retrieve is unknown.

**JBPRAQLCORECE0173** A renamed field expression must have exactly one sub-expression.

**JBPRAQLCORECE0174** A renamed field expression must not have more than one sub-expression.

**JBPRAQLCORECE0175** Analytic function could not be resolved: {0}

**JBPRAQLCORECE0176** Unknown window function type {0}.

**JBPRAQLCORECE0177** Analytic function could not be resolved: {0}

**JBPRAQLCORECE0178** An aggregation operator must have exactly one input operator.

**JBPRAQLCORECE0179** An aggregation operator must not have more than one input operator.

**JBPRAQLCORECE0180** Overflow to BigNumber

**JBPRAQLCORECE0181** Error accessing {0} : {1}

**JBPRAQLCORECE0182** Error reading {0} : {1}

**JBPRAQLCORECE0183** Unable to determine schema of {0}.

**JBPRAQLCORECE0184** Not supported yet.

**JBPRAQLCORECE0185** Unknown join type {0}.

**JBPRAQLCORECE0186** A join operator must have at least two input operators.

**JBPRAQLCORECE0187** Implementations of multiway join are currently not supported, i.e., they must be transformed to join plans of binary joins using the query optimizer.

**JBPRAQLCORECE0188** Record Found!!!!!!!

**JBPRAQLCORECE0189** Error reading data source : {0}

**JBPRAQLCORECE0190** skipObject

**JBPRAQLCORECE0191** No record found.

**JBPRAQLCORECE0192** Unable to locate file : {0}

**JBPRAQLCORECE0193** No record found.

**JBPRAQLCORECE0194** Only operators can be used as child nodes of a limit operator.

**JBPRAQLCORECE0195** multiple window functions not yet supported

**JBPRAQLCORECE0196** Mapping operator is not expected to have more than one input!

**JBPRAQLCORECE0197** A mapping operator must have exactly one input operator.

**JBPRAQLCORECE0198** NULLS FIRST and NULLS LAST are not supported in RAQL query execution.

**JBPRAQLCORECE0199** Only operators can be used as child nodes of an order operator.

**JBPRAQLCORECE0200** ORDER BY should have at least one ordering criteria specified.

**JBPRAQLCORECE0201** A renaming operator must have exactly one input operator.

**JBPRAQLCORECE0202** A renaming operator must not have more than one input operator.

**JBPRAQLCORECE0203** prepared query successfully, query metadata:

**JBPRAQLCORECE0204** processing query: {0}

**JBPRAQLCORECE0205** {0} is not a valid UDF library directory.

**JBPRAQLCORECE0206** UDF libs directory {0} defined by system property {1} is not valid.

**JBPRAQLCORECE0207** System property {0} is not defined. Attempted to use default UDF library directory {1}, but is not valid directory. Either set system property {0} to a valid UDF library directory or ensure that default UDF library directory {1} exists.

**JBPRAQLCORECE0208** processing query: {0}

**JBPRAQLCORECE0209** prepared query successfully

**JBPRAQLCORECE0210** Unable to reset result-set.

**JBPRAQLCORECE0211** Resource not available: {0}

**JBPRAQLCORECE0212** startup RTM system

**JBPRAQLCORECE0213** Enter query or enter 'quit', 'q' or 'exit' to quit >

**JBPRAQLCORECE0214** Enter next query:

**JBPRAQLCORECE0215** Only operators can be used as child nodes of a limit operator.

**JBPRAQLCORECE0216** NULLS FIRST and NULLS LAST are not supported in RAQL query execution.

**JBPRAQLCORECE0217** WindowFunctions are expected to have at least one function

**JBPRAQLCORECE0218** An aggregation operator must have exactly one input operator.

**JBPRAQLCORECE0219** An aggregation operator must not have more than one input operator.

**JBPRAQLCORECE0220** update

**JBPRAQLCORECE0221** A boolean expression must not have any sub-predicates.

**JBPRAQLCORECE0222** A comparison predicate must not have any sub-predicates.

**JBPRAQLCORECE0223** Invalid operator [{0}].

**JBPRAQLCORECE0224** Unable to locate file : {0}

**JBPRAQLCORECE0225** No records in data source

**JBPRAQLCORECE0226** Unable to read header of data source

**JBPRAQLCORECE0227** No records in data source

**JBPRAQLCORECE0228** Error reading data source : {0}

**JBPRAQLCORECE0229** Illegal numeric types to '+' {0}

**JBPRAQLCORECE0230** Illegal numeric types to '-' {0}

**JBPRAQLCORECE0231** Illegal numeric types to '\*' {0}

**JBPRAQLCORECE0232** Illegal numeric types to '/' {0}

**JBPRAQLCORECE0233** LIKE operator requires String arguments

**JBPRAQLCORECE0234** Unsupported unary operator datatype : {0}

**JBPRAQLCORECE0235** match (~) operator requires String arguments

**JBPRAQLCORECE0236** Unable to evaluate expression : {0}

**JBPRAQLCORECE0237** operation not implemented

**JBPRAQLCORECE0238** Order By Not supported for {0}

**JBPRAQLCORECE0239** Not implemented {0}

**JBPRAQLCORECE0240** Unable to find our spill file.

**JBPRAQLCORECE0241** Unable to find our spill file.

**JBPRAQLCORECE0242** Unable to find our spill file.

**JBPRAQLCORECE0243** Failed to delete spill file: {0}

**JBPRAQLCORECE0244** InternalSortedBag is closed for adding new tuples

**JBPRAQLCORECE0245** Unable to find our spill file.

**JBPRAQLCORECE0246** The state of the logical constant is unknown.

**JBPRAQLCORECE0247** A logical constant must not have any sub-predicates.

**JBPRAQLCORECE0248** Unknown logical constant type {0}.

**JBPRAQLCORECE0249** The logical operation type {0} is currently not supported.

**JBPRAQLCORECE0250** A logical (boolean) NOT must have exactly one sub-predicate.

**JBPRAQLCORECE0251** A logical (boolean) NOT must not have more than one sub-predicate.

**JBPRAQLCORECE0252** Only operators can be used as sets of an in predicate.

**JBPRAQLCORECE0253** A logical (boolean) IN operator must not have any sub-predicates.

**JBPRAQLCORECE0254** Enumeration contains constants of different types.

**JBPRAQLCORECE0255** A logical (boolean) NOT must not have more than one sub-predicate.

**JBPRAQLCORECE0256** Error initializing log file : {0}

**JBPRAQLCORECE0257** Compile Error: Expected token: {0} or {1} : but, have {2} of type {3}

**JBPRAQLCORECE0258** Columns must be ',' separated

**JBPRAQLCORECE0259** Having not implemented yet. Sorry!

**JBPRAQLCORECE0260** Missing data source in from clause

**JBPRAQLCORECE0261** Compile Error: Expected token : {0} : but, have {1} of type {2}

**JBPRAQLCORECE0262** Unterminated quote

**JBPRAQLCORECE0263** Internal error : {0}

**JBPRAQLCORECE0264** Illegal Expression. {0}

**JBPRAQLCORECE0265** Invalid FrameBetween clause. Frame start must be lower than end.

---

JBPRAQLCORECE0266 Frame index may not be negative! Found: {0}

JBPRAQLCORECE0267 Parse error: expect NUMBER in frame clause

JBPRAQLCORECE0268 Illegal unary operator : {0}

JBPRAQLCORECE0269 Missing table reference in from clause

JBPRAQLCORECE0270 Unable to compare types : {0} : {1}

JBPRAQLCORECE0271 Unable to execute RAQL query as RAQL engine did not start up correctly.

JBPRAQLCORECW0001 The aggregation function alias "{0}" is deprecated. Please change your query to use "{1}" instead.

JBPRAQLCORECW0002 The window function alias "{0}" is deprecated. Please change your query to use "{1}" instead.

JBPRAQLCOREEE0001 Only directories will be loaded as library. Ignored file {0}.

JBPRAQLCOREEE0002 The library directory {0} is not readable.

JBPRAQLCOREEE0003 Loading library {0} failed.

JBPRAQLCOREEE0004 Parsing the library directory {0} failed.

JBPRAQLCOREEE0005 Not a valid library name: {0}

JBPRAQLCOREEE0006 Failed to create ClassLoader for lib directory {0}.

**JBPRAQLCOREE0007** Unresolved dependencies to {0}. Please check the library's classpath.

**JBPRAQLCOREE0008** Error retrieving classpath.

**JBPRAQLCOREE0009** Failed to register function {0}.

**JBPRAQLCOREE0010** The class {0} implements one of the UDX interfaces. All function level RaqlFunc annotations will be ignored.

**JBPRAQLCOREE0011** Class {0} has unresolved dependencies: {1}.

**JBPRAQLCOREE0012** Failed to read function descriptor(s) from annotations: {0}.

**JBPRAQLCOREE0013** Invalid RaqlFunc class {0}. Annotation @RaqlFunc may only be applied to classes which implement any of the following interfaces: {1}.

**JBPRAQLCOREE0014** There is already a function {0} defined by {1}.{2}. The function defined by {3}.{4} will be ignored.

**JBPRAQLCOREE0015** Failed to read library configuration: {0}

**JBPRAQLCOREE0016** Lib config does not exist: {0}.

**JBPRAQLCOREE0017** Failed to un-load library: {0}

**JBPRAQLCOREE0018** Failed to close ClassLoader for library {0}.

**JBPRAQLCOREE0019** Unhandled artefact type: {0}

JBPRAQLCOREE0020 De-registration failed for {0} {1}.

JBPRAQLCOREE0021 An error occurred during RAQL engine start-up.

JBPRAQLCOREE0022 Error retrieving the schema information of an Apama Cache: {0}

JBPRAQLCOREE0023 Unable to remove resources required for query execution from the RAQL engine after executing the query.

JBPRAQLCOREE0024 Unable to revert the failed source registration.

JBPRAQLCOREE0025 Unable to revert the failed query registration.

JBPRAQLCOREE0026 Unable to close a query that depends on the source or query '{0}' to be de-registered.

JBPRAQLCOREE0027 An error occurred in the RAQL engine.

JBPRAQLCOREE0038 LibraryLoader started.

JBPRAQLCOREE0039 Loading library: {0}.

JBPRAQLCOREE0040 Library loaded: {0}.

JBPRAQLCOREE0041 Library loaded with warnings: {0}. The following functions could not be registered: {1}.

JBPRAQLCOREE0042 Library did not provide any valid functions to register: {0}.

JBPRAQLCOREE0043 Classpath: {0}.

**JBPRAQLCOREE0044** Registered artifact of type: {0} {1}.

**JBPRAQLCOREE0045** The annotation {0} is deprecated. Please use {1} instead.

**JBPRAQLCOREE0046** Reading libConfig: {0}.

**JBPRAQLCOREE0047** LibraryLoader stopped.

**JBPRAQLCOREE0048** Unloading library: {0}.

**JBPRAQLCOREE0049** De-registered artifact of type {0}: {1}.

**JBPRAQLCOREE0052** Function `nv1()` expects exactly two arguments.

**JBPRAQLCOREE0053** Function `nv1()` does not accept arguments of type {0}.

**JBPRAQLCOREE0054** Both arguments of `nv1()` need to have the same type. Found {0} <> {1}.

**JBPRAQLCOREE0104** The function {0} is described by {1}.{2}. {3}.{4} will be ignored

**JBPRAQLCOREE0108** The function {0} is described in {1} and by annotations. Annotation description will be ignored.

**JBPRAQLCOREE0109** This class is an `AnaliticFunction`. All function level `RaqlFunc` annotations will be ignored.

**JBPRAQLCOREW0003** Overflow event on watched directory

**JBPRAQLCOREW0004** The interface, {0}, is deprecated and may not be supported in future versions. Please consider a migration to the new aggregation function interfaces (see documentation).

---

**JBPRAQLCOREW0005** Order-By expressions will not be available in FunctionContext.

**JBPRAQLCOREW0028** Deprecated folder-structure: A library's jar files should be contained in a '/lib' sub-folder, not in a '/libs' sub-folder.

**JBPRDSCE0027** No Cache Manager exists with the name: {0}

**JBPRDSCE0028** A BigMemory datasource with this name already exists. Please use a different name.

**JBPRDSCE0029** An attribute with name {0} already exists. Please specify a different name.

**JBPRDSCE0030** No attribute with name {0} can be found. Can't update.

**JBPRDSCE0031** Invalid username. Please only use letters, numbers, '-', '.', '\_'

**JBPRDSCI0001** Service - Run

**JBPRDSCI0002** Artifact - Created

**JBPRDSCI0003** Artifact - Removed

**JBPRDSCI0004** Service - Creation confirmed

**JBPRDSCI0005** Artifact - Turned on

**JBPRDSCI0006** Artifact - Turned off

**JBPRDSCI0007** Unknown Action

<b>JBPRDSCI0008</b>	<b>Artifact - Feedback added</b>
<b>JBPRDSCI0009</b>	<b>Service - Updated</b>
<b>JBPRDSCI0010</b>	<b>App - Updated</b>
<b>JBPRDSCI0011</b>	<b>Artifact - Permissions added</b>
<b>JBPRDSCI0012</b>	<b>Artifact - Permissions removed</b>
<b>JBPRDSCI0013</b>	<b>App - Run</b>
<b>JBPRDSCI0014</b>	<b>App - Approved by AppDepot manager</b>
<b>JBPRDSCI0015</b>	<b>App - Rejected by AppDepot manager</b>
<b>JBPRDSCI0016</b>	<b>App - Published to AppDepot</b>
<b>JBPRDSCI0017</b>	<b>App - Removed from AppDepot</b>
<b>JBPRDSCI0018</b>	<b>App - Submission to AppDepot cancelled</b>
<b>JBPRDSCI0019</b>	<b>User - Logged in</b>
<b>JBPRDSCI0020</b>	<b>User - Logged out</b>
<b>JBPRDSCI0021</b>	<b>HTTP Basic Authentication</b>

---

JBPRDSCI0022	Windows NTLM Authentication
JBPRDSCI0023	SSL Certificate Authentication
JBPRDSCI0024	Single Sign-On Authentication
JBPRDSCI0025	CAS2 Authentication
JBPRDSCI0026	OAuth Authentication
JBPRDSE0001	Please contact your JackBe Sales Representative.
JBPRDSE0002	You are exceeding the limit on SharePoint servers connected to Mashzone NextGen.  Your license allows
JBPRDSE0003	Your license does not include Mashzone NextGen features for Microsoft SharePoint.{0}
JBPRDSE0004	No server name specified
JBPRDSE0005	Error generating NSD info for Service : {0}
JBPRDSE0006	unexpected invocation exception: {0}
JBPRDSE0007	Invalid service Id : {0}
JBPRDSE0008	Service not found : {0}
JBPRDSE0009	Error Generating NSD info for Service : {0}

JBPRDSE0010	Couldn't get NSD for service = {0}
JBPRDSE0011	Couldn't get Service Description for service = {0}
JBPRDSE0012	Failed to generate input template
JBPRDSE0013	Unexpected error retrieving soap header: {0}_{1}_soapHeader
JBPRDSE0014	Unable to find repository item = {0}
JBPRDSE0015	Invalid repository item format!
JBPRDSE0016	SOAP Encode error
JBPRDSE0017	Error locating Mashup NSD Service Factory : {0}
JBPRDSE0018	Error generating XML String from DOM element
JBPRDSE0019	unable to parse xml: {0}
JBPRDSE0020	Unable to preprocess Schema : {0}
JBPRDSE0021	Error in schema repaire namespaces: {0}
JBPRDSE0022	Error generating NSD info for Service : {0}
JBPRDSE0023	Error generating NSD info for Service : {0}

---

JBPRDSE0024	Error generating NSD info for Service : {0}
JBPRDSE0025	Error Generating NSD info for Service : {0}
JBPRDSE0026	Error generating NSD: Invalid Service argument
JBPRDSE0027	NSDService.generateNSDForService: Error generating NSD Info for Service {0} : {1}
JBPRDSE0028	NSDService: Unable to locate WSDL file for {0}
JBPRDSE0029	Unable to process WSDL Schema Information :
JBPRDSE0030	Did not find a fallback repository item with key: {0}
JBPRDSE0031	Mashzone NextGen Server Error(NSD) : Unable to locate item : {0} with absolute url: {1}
JBPRDSE0032	Error Retrieving XSD from RDS : {0}
JBPRDSE0033	Given resource not found : {0}
JBPRDSE0034	Unable to get NSD for given Schema : {0} : {1}
JBPRDSE0035	ResourceSchema Error : Unable to proceprocess Imported Schema : {0} : {1}
JBPRDSE0036	Unable to access default SOAP schema files : {0}
JBPRDSE0037	Unable to proceprocess Imported Schema with systemId: {0} publicId {1} from Repository item with key: {2}

<b>JBPRDSE0038</b>	<b>Not supported yet.</b>
<b>JBPRDSE0039</b>	<b>Invalid expression: {0}</b>
<b>JBPRDSE0040</b>	<b>Action cannot be null</b>
<b>JBPRDSE0041</b>	<b>Indeterminate Decision</b>
<b>JBPRDSE0042</b>	<b>Unexpected response. Response has more then one results</b>
<b>JBPRDSE0043</b>	<b>Failed to evaluate authZ policy</b>
<b>JBPRDSE0044</b>	<b>Number of agrumets must be less then 4</b>
<b>JBPRDSE0045</b>	<b>Failed to initialize PDP</b>
<b>JBPRDSE0046</b>	<b>Cannot load permission configuration from {0}</b>
<b>JBPRDSE0047</b>	<b>Cannot load default policies</b>
<b>JBPRDSE0048</b>	<b>Permission element attributes fully define a permission. Thus Permission element cannot have content. Invalid element :{0}</b>
<b>JBPRDSE0049</b>	<b>Permission element invalid. {0}</b>
<b>JBPRDSE0050</b>	<b>Cannot load default policies</b>
<b>JBPRDSE0051</b>	<b>Failed to parse policy. Check if groupFilter is valid XACML</b>

---

JBPRDSE0052	Failed to read filter
JBPRDSE0053	Invalid format for a filter. Service element {0} misses child element {1}
JBPRDSE0054	Not supported yet.
JBPRDSE0055	Resource of type {0} has to be explicitly created before it can be used
JBPRDSE0056	Policy with id={0} Cannot be found
JBPRDSE0057	too many applicable top-level policies
JBPRDSE0058	Failed to load policies into cache
JBPRDSE0059	Initial load of default XACML policies into DB failed.
JBPRDSE0060	combiningAlg is an invalid URI
JBPRDSE0061	Invalid combiningAlg
JBPRDSE0062	Invalid combiningAlg or parentPolicyId
JBPRDSE0063	Cannot update group with id={0}
JBPRDSE0064	Cannot load default policies
JBPRDSE0065	too many applicable top-level policies

JBPRDSE0066	Filed to setup reader: {0}
JBPRDSE0067	Failed to read the file
JBPRDSE0068	Failed to parse the file
JBPRDSE0069	Failed to read the stream
JBPRDSE0070	Failed to parse the stream
JBPRDSE0071	Failed to resolve the URL: {0}
JBPRDSE0072	Unknown root document type: {0}
JBPRDSE0073	error parsing policy
JBPRDSE0074	fatal error parsing policy
JBPRDSE0075	Principal id is null
JBPRDSE0076	Not supported yet.
JBPRDSE0077	Cannot update entity {0} It does not exists.
JBPRDSE0078	When Depth is not equal SELF, Direction must be specified
JBPRDSE0079	Type is NULL or empty. You have to specify entity type to query for top rated entities

---

JBPRDSE0080	Cannot create DbAdapter. DB type cannot be found based on jdbcUrl = <{0}>. Please make sure that URL is correct. You can also force type by explicitly specifying "databaseType" property for DBAdapterFactory
JBPRDSE0081	Cannot create DbAdapter. Unsupported DB type <{0}>
JBPRDSE0082	{0} DB Type was guessed from jdbcUrl={1} If type is incorrect, you can force type by explicitly specifying "databaseType" property for DBAdapterFactory
JBPRDSE0083	User application with name={0} already exists for user {1}.Please choose different name
JBPRDSE0084	Not supported state {0} Onl approved and pending are supported
JBPRDSE0085	Cannot guess unquie in {0} attempts
JBPRDSE0086	ID [{0}] is invalid.
JBPRDSE0087	Name [{0}] is invalid.
JBPRDSE0088	Error retrieving security profile data. Cause -
JBPRDSE0089	Entities with following ids does not exist:
JBPRDSE0090	Entities with following ids have wrong type for dependencies:
JBPRDSE0091	Entity with id = {0} is not a Service or Mashup
JBPRDSE0092	Entity with id = {0} is not a OAuthProvider

JBPRDSE0093	Entity with id = {0} is not a Service
JBPRDSE0094	Entity with id = {0} is not a Mashup
JBPRDSE0095	Not supported yet.
JBPRDSE0096	QName Conversion Error : Unexpected type in unmarshal: {0}
JBPRDSE0097	Unable to convert value to a qname: {0}
JBPRDSE0098	Failed to set featured. Objects not found {0}
JBPRDSE0099	Error saving repository item: {0}
JBPRDSE0100	Cannot find file with id={0}
JBPRDSE0101	Error saving repository item: {0}
JBPRDSE0102	No entity for ID = null
JBPRDSE0103	Entity with id={0} does not exist
JBPRDSE0104	Not supported yet.
JBPRDSE0105	Cannot instantiate entity {0}
JBPRDSE0106	Expected BigDecimal or Long for version but got {0}

---

JBPRDSE0107	When <code>isAccessControlEnabled == true</code> <code>entityTypeId</code> cannot be null
JBPRDSE0108	Not implemented
JBPRDSE0109	Not supported yet.
JBPRDSE0110	===== Favorite Services Dump =====
JBPRDSE0111	Cannot add object with <code>id={0}</code> to featured. Object with this id does not exists
JBPRDSE0112	Duplicate Federation Partner
JBPRDSE0113	Not implemented yet
JBPRDSE0114	Cannot discover classloader to be used by JPOX PMF
JBPRDSE0115	Cannot delete special NONE provider
JBPRDSE0116	Type has to be either <code>{0}</code> or <code>{1}</code>
JBPRDSE0117	Type is NULL or empty. <code>{0}</code>
JBPRDSE0118	Type = <code>&lt;{0}&gt;</code> is unsupported. <code>{1}</code>
JBPRDSE0119	Not supported yet.
JBPRDSE0120	A <code>cacheManager</code> is required. Use <code>setCacheManager(QueryManagerCacheManager)</code> to provide one.

JBPRDSE0121	Update is only supported for Service and Mashlet, but this object is of type = {0}
JBPRDSE0122	Category with Id={0}already exists
JBPRDSE0123	Parent category does not exist. ParentId={0}
JBPRDSE0124	RegistryObject id is not unique. Id={0}
JBPRDSE0125	Failed to save RO:
JBPRDSE0126	messageSource cannot be NULL
JBPRDSE0127	Not yet implemented
JBPRDSE0128	List of serviceById methods is misconfigured in RdsQueryManager
JBPRDSE0129	List of serviceById method is misconfigured in RdsQueryManager
JBPRDSE0130	List of serviceById methods is misconfigured in RdsQueryManager
JBPRDSE0131	List of serviceById method is misconfigured in RdsQueryManager
JBPRDSE0132	File with id={0} does not exist.
JBPRDSE0133	Failed to get file.
JBPRDSE0134	Failed to find file

---

JBPRDSE0135	File with id={0} already exists.
JBPRDSE0136	Failed to create file.
JBPRDSE0137	Update Failed. File with id={0} does not exist.
JBPRDSE0138	Failed to update file.
JBPRDSE0139	Delete Failed. File with id={0} does not exist.
JBPRDSE0140	Copy failed. Source file with id={0} does not exist.
JBPRDSE0141	Failed to copy file.
JBPRDSE0142	Failed to associate File and RegistryObject. Either File or RegistryObject does not exist
JBPRDSE0143	Failed to associate File and RegistryObject
JBPRDSE0144	Failed to dissociate File from RegistryObject
JBPRDSE0145	Directory id should be shorter than resourceId
JBPRDSE0146	Directory don't contain resource.(dirId and resourceId have no common part)
JBPRDSE0147	Common part of directoryId and resourceId must end with directory separator {0}
JBPRDSE0148	Not supported yet.

JBPRDSE0149	IN opration is not supported in context of this expression
JBPRDSE0150	LIKE opration is not supported in context of this expression
JBPRDSE0151	LIKE_IN opration is not supported in context of this expression
JBPRDSE0152	Unknow operation
JBPRDSE0153	Unable to format date from: {0}
JBPRDSE0154	Unable to convert String to Long
JBPRDSE0155	A cache is required. Use setCache(Cache) to provide one.
JBPRDSE0156	Range fromat is from,to
JBPRDSE0157	fromIncl must be > 0. First element is 1
JBPRDSE0158	Invalid range. fromIncl must be less then toExcl
JBPRDSE0159	Transition workflow from state with type id {0} to state with type id {1} is not allowed
JBPRDSE0160	RegistryObject of type={0} and subtype={1} is not a valid entity
JBPRDSE0161	Cannot add category with id = {0} to RegistryObject because this category does not exists
JBPRDSE0162	Cannot set provider for entity. Provider with id={0} does not exists

---

JBPRDSE0163	Unrecognised UID ({0})
JBPRDSE0164	Name format should be parentEntityType/parentEntityName/resourceName
JBPRDSE0165	order field should have format fieldName:{{0}} {1}}
JBPRDSE0166	Cannot create RDS Spring Application Ctx
JBPRDSE0167	EQ operation is not supported in context of this expression
JBPRDSE0168	IN operation is not supported in context of this expression
JBPRDSE0169	LIKE operation is not supported in context of this expression
JBPRDSE0170	BETWEEN operation is not supported in context of this expression
JBPRDSE0171	There is no default processing defined. Operator has to be specified
JBPRDSE0172	Operator {0} is not supported
JBPRDSE0173	Operation must be overwritten by subclasses
JBPRDSE0174	Error during encrypting password, saving in plain format
JBPRDSE0175	Terracotta BigMemory client version {0}, does not match with server version {1}
JBPRDSE0176	fail to invoke TMC due to: {0}

JBPRDSE0177	fail to read TMC response due to: {0}
JBPRDSE0178	Error while retrieving Terracotta Server Array version: {0}
JBPRDSE0179	Unable to find class for internal service: {0}
JBPRDSE0180	Error saving repository item {0}
JBPRDSE0181	Error saving "feed" repository item: {0}
JBPRDSE0182	Expecting ServiceDescription, {0}
JBPRDSE0183	Invalid XACML policy document
JBPRDSE0184	Operation is not implemented
JBPRDSE0185	User or group name cannot be null!
JBPRDSE0186	User or group {0} does not exist!
JBPRDSE0187	Invalid users or groups, {0}
JBPRDSE0188	Cannot set field <{0}> when in VALID state
JBPRDSE0189	Invalid attribute index. Using default value of 0 as index
JBPRDSE0190	Unexpected parsing exception reading service data.

---

JBPRDSE0191	Unexpected io exception reading service data.
JBPRDSE0192	No project config data found for service : {0}
JBPRDSE0193	Failed to update project details
JBPRDSE0194	Failed to create connection : SQL Exception : {0}, {1}
JBPRDSE0195	Failed to create connection : {0}
JBPRDSE0196	Unable to establish connection for service {0}, transaction in progress.
JBPRDSE0197	Unable to find service using ({0})
JBPRDSE0198	Error finding registry object using uid = {0}
JBPRDSE0199	Error finding service artifacts. Internal repository error.
JBPRDSE0200	No jar files found in directory, {0}
JBPRDSE0201	Unexpected malformed url detected.
JBPRDSE0202	Failed to create class instance, {0}
JBPRDSE0203	App Ctx already set
JBPRDSE0204	Application Context has not been initialized

JBPRDSE0205	Not yet implemented
JBPRDSE0206	DB Import failed.
JBPRDSE0207	Failed to create connection to data source {0}
JBPRDSE0208	Exception retrieving catalogs and schemas : {0} NextException : {1}
JBPRDSE0209	Exception retrieving catalogs : {0}
JBPRDSE0210	Exception retrieving schemas : {0} NextException : {1}
JBPRDSE0211	Exception retrieving schemas : {0}
JBPRDSE0212	Exception retrieving tables : {0}
JBPRDSE0213	Exception retrieving views : {0}
JBPRDSE0214	Exception retrieving procedures : {0}
JBPRDSE0215	Exception retrieving metadata : {0} NextException : {1}
JBPRDSE0216	Exception retrieving metadata : {0}
JBPRDSE0217	SQLException retrieving table names : {0} NextException : {1}
JBPRDSE0218	Exception retrieving table names : {0}

---

JBPRDSE0219	SQLException retrieving view names : {0} NextException : {1}
JBPRDSE0220	Exception retrieving view names : {0}
JBPRDSE0221	SQLException retrieving procedure names : {0} NextException : {1}
JBPRDSE0222	Exception retrieving procedure names : {0}
JBPRDSE0223	Failed to connect to data source.
JBPRDSE0224	SQL Exception thrown releasing db connection : {0}
JBPRDSE0225	[dpi] {0}
JBPRDSE0226	Unexpectedly failed to initialise configuration.
JBPRDSE0227	Unexpected IOException saving config.
JBPRDSE0228	Failed to take copy of current config: {0}
JBPRDSE0229	Data Provider not recognised
JBPRDSE0230	Could not find configuration data for driver '{0}'
JBPRDSE0231	JDBC driver '{0}' is not configured correctly.
JBPRDSE0232	No suitable JDBC driver found for the following JDBC URL: {0} This probably means that the JDBC URL is in the wrong format or the wrong JDBC driver has been selected. Please check that driver '{1}' is configured correctly and that you have the correct JDBC URL format. No Suitable Driver

JBPRDSE0233	Could not connect to '{0}' due to a connection refused error. This normally means that the database is not running, a firewall is blocking access, or incorrect login details are being used. Connection Refused
JBPRDSE0234	Could not connect to '{0}' with User Id '{1}'. This probably means that the URL or login details are incorrect. The full error is: {2} SQL Exception : {3}
JBPRDSE0235	Throwable thrown validating data source, {0}
JBPRDSE0236	Unexpected exception thrown validating data source, {0}
JBPRDSE0237	Unexpected exception thrown closing connection, {0}
JBPRDSE0238	SQLException : {0}
JBPRDSE0239	Failed to take copy of current config: {0}
JBPRDSE0240	The following classpath entries are invalid: {0}
JBPRDSE0241	No database driver file specified
JBPRDSE0242	Failed to load JDBC driver '{0}'. Please check that the class name and class path settings are correct.
JBPRDSE0243	Invalid principal type<{0}>
JBPRDSE0244	Not supported yet.
JBPRDSE0245	User does not exists

---

JBPRDSE0246	Unable to get user details
JBPRDSE0247	Duplicate User Name
JBPRDSE0248	Role {0} is a built-in role and cannot be deleted
JBPRDSE0249	Password cannot be empty
JBPRDSE0250	Password length must be between {0} and {1} characters
JBPRDSE0251	Invalid password reset verification code. Please request a new code
JBPRDSE0252	Duplicate role
JBPRDSE0253	Cannot assign role={1} to userId={0}, because either role or user does not exists
JBPRDSE0254	Cannot Init DAO
JBPRDSE0255	User does not exist
JBPRDSE0256	Duplicate User Name
JBPRDSE0257	Attribute {0} cannot be modified
JBPRDSE0258	Attribute {0} is virtual attribute and cannot be deleted
JBPRDSE0259	Supported attribute list is generated dynamically. Thus setting attriubte names is unsupported.

<b>JBPRDSE0260</b>	<b>Bad credentials</b>
<b>JBPRDSE0261</b>	<b>Attribute map cannot be null</b>
<b>JBPRDSE0262</b>	<b>Regular expression must contain a single group</b>
<b>JBPRDSE0263</b>	<b>Malformed regular expression: {0}</b>
<b>JBPRDSE0264</b>	<b>contextSource must not be null</b>
<b>JBPRDSE0265</b>	<b>User with DN {0} not found in directory.</b>
<b>JBPRDSE0266</b>	<b>userSearch must not be null</b>
<b>JBPRDSE0267</b>	<b>authoritiesPopulator must not be null</b>
<b>JBPRDSE0268</b>	<b>User search failed:{0}</b>
<b>JBPRDSE0269</b>	<b>userDetailsMapper must not be null</b>
<b>JBPRDSE0270</b>	<b>searchAttributes array cannot be empty</b>
<b>JBPRDSE0271</b>	<b>Range should contain at least one element</b>
<b>JBPRDSE0272</b>	<b>Request Control operations require LDAPv3 - Context must be of type LdapContext</b>
<b>JBPRDSE0273</b>	<b>Error creating PagedResultsControl</b>

JBPRDSE0274	Ldap VLV paging failed. Error code:{0}
JBPRDSE0275	Ldap VLV paging failed. VLV response control had not been found in the response
JBPRDSE0276	Mashzone NextGen does not support modification to configured user repository
JBPRDSE0277	This operation is not supported in SSO mode. ( NullUserRepositoryAccessAdapter).
JBPRDSE0278	User details for userid={0} cannot be found
JBPRDSE0279	Snapshot failed : {0}
JBPRDSE0280	Error in getting created items list
JBPRDSE0281	not yet implemented
JBPRDSE0282	failed to add all..aborting
JBPRDSE0283	error saving message
JBPRDSE0284	failed to send private message to friends
JBPRDSE0285	failed to get messages
JBPRDSE0286	failed to delete message
JBPRDSE0287	Message status cannot be blank. Allowed are: read, flagged

<b>JBPRDSE0288</b>	<b>Invalid message status. Status can be: new, read, flagged</b>
<b>JBPRDSE0289</b>	<b>failed to update message status</b>
<b>JBPRDSE0290</b>	<b>not yet implemented</b>
<b>JBPRDSE0291</b>	<b>Message status cannot be blank. Allowed are: read, flagged</b>
<b>JBPRDSE0292</b>	<b>Invalid message status. Status can be: new, read, flagged</b>
<b>JBPRDSE0293</b>	<b>error in getting activities</b>
<b>JBPRDSE0294</b>	<b>error in getting commented items</b>
<b>JBPRDSE0295</b>	<b>error in getting created items</b>
<b>JBPRDSE0296</b>	<b>error in getting rated items</b>
<b>JBPRDSE0297</b>	<b>error in getting used items</b>
<b>JBPRDSE0298</b>	<b>failed to get all messages</b>
<b>JBPRDSE0299</b>	<b>failed to get messages for category</b>
<b>JBPRDSE0300</b>	<b>failed to get flagged messages</b>
<b>JBPRDSE0301</b>	<b>failed to get recent messages</b>

<b>JBPRDSE0302</b>	<b>failed to broadcast message</b>
<b>JBPRDSE0303</b>	<b>failed to send private message</b>
<b>JBPRDSE0304</b>	<b>failed to get broadcast messages</b>
<b>JBPRDSE0305</b>	<b>failed to get group messages</b>
<b>JBPRDSE0306</b>	<b>failed to get unread messages</b>
<b>JBPRDSE0307</b>	<b>failed to delete message</b>
<b>JBPRDSE0308</b>	<b>failed to get sent messages</b>
<b>JBPRDSE0309</b>	<b>not yet implemented</b>
<b>JBPRDSE0310</b>	<b>Failed to get info for given person Ids</b>
<b>JBPRDSE0311</b>	<b>Failed to get friends</b>
<b>JBPRDSE0312</b>	<b>Failed to get person</b>
<b>JBPRDSE0313</b>	<b>Failed to get friends ids</b>
<b>JBPRDSE0314</b>	<b>Given friend id is null</b>
<b>JBPRDSE0315</b>	<b>failed to add friend</b>

<b>JBPRDSE0316</b>	<b>failed to remove friend</b>
<b>JBPRDSE0317</b>	<b>Failed to get user's shared items</b>
<b>JBPRDSE0318</b>	<b>Failed to get friend's shared items</b>
<b>JBPRDSE0319</b>	<b>Failed to share artifact with your friend</b>
<b>JBPRDSE0320</b>	<b>not yet implemented</b>
<b>JBPRDSE0321</b>	<b>Failed to remove shared item</b>
<b>JBPRDSE0322</b>	<b>Failed to get top shared items</b>
<b>JBPRDSE0323</b>	<b>Failed to get top shared items summary</b>
<b>JBPRDSE0324</b>	<b>Failed to get recently shared items</b>
<b>JBPRDSE0325</b>	<b>Failed to get my shared items</b>
<b>JBPRDSE0326</b>	<b>Failed to get shared items from others</b>
<b>JBPRDSE0327</b>	<b>Policy Manager UI</b>
<b>JBPRDSE0328</b>	<b>Manage Permissions using PM UI</b>
<b>JBPRDSE0329</b>	<b>Manage Resource Groups using PM UI</b>

---

<b>JBPRDSE0330</b>	<b>Manage dynamic User Groups using PM UI</b>
<b>JBPRDSE0331</b>	<b>Manager Mashzone NextGen and custom UI objects using PM UI</b>
<b>JBPRDSE0332</b>	<b>Service Explorer UI</b>
<b>JBPRDSE0333</b>	<b>Name cannot be longer then 256</b>
<b>JBPRDSE0334</b>	<b>Id cannot be NULL or empty</b>
<b>JBPRDSE0335</b>	<b>Id cannot be longer then 2048</b>
<b>JBPRDSE0336</b>	<b>Id={0} is not unique</b>
<b>JBPRDSE0337</b>	<b>Valid characters for ID are [{0}]</b>
<b>JBPRDSE0338</b>	<b>Valid characters for Name are [{0}]</b>
<b>JBPRDSE0339</b>	<b>The defaultRole property cannot be set to null</b>
<b>JBPRDSE0340</b>	<b>groupRoleAttribute must not be null</b>
<b>JBPRDSE0341</b>	<b>groupSearchFilter must not be null</b>
<b>JBPRDSE0342</b>	<b>contextSource must not be null</b>
<b>JBPRDSE0343</b>	<b>The groupSearchBase (name to search under), must not be null.</b>

JBPRDSE0344	<b>groupNameTransformer must not be null</b>
JBPRDSE0345	<b>Cannot retrieve cache manager configuration: {0}</b>
JBPRDSE0346	<b>Invalid TMC address: {0}</b>
JBPRDSE0347	<b>The cache manager {0} was not found available on the management console at {1}</b>
JBPRDSE0348	<b>Authentication is not enabled on the management console!</b>
JBPRDSE0349	<b>There are multiple cache managers with the same name, this happens when multiple clients create the same cache manager. Please make sure all caches are under a single cache manager.</b>
JBPRDSE0350	<b>There are no cache managers with the name {0}</b>
JBPRDSE0351	<b>Fail while fetching cache manager configuration file: {0}</b>
JBPRDSE0352	<b>Invalid user name and/or password.</b>
JBPRDSE0353	<b>The cache manager {0} is already referenced in a configuration {1}</b>
JBPRDSE0354	<b>Multiple Cache Managers with the same name found. Please specify a TMS Connection name in your configuration {0}.</b>
<b>Explanation</b>	Two or more Cache Managers with the same name have been found. This could happen if there is no connection name specified in the configuration.
<b>Action</b>	Specifying a TMS connection name will point to a concrete TSA and prevent cache manager name clashes.
JBPRDSE0355	<b>Uninsufficient parameters for adding new BigMemory Configuration. Missing parameter: {0}</b>
<b>Explanation</b>	Some of the parameters are null or not provided at all.
<b>Action</b>	Add an entry for the required parameter in the request.

---

JBPRDSE0356	Attribute {0} does not exist. Cannot delete or update it.
JBPRDSE0357	Attribute {0} is a system attribute and may not be deleted
JBPRDSW0001	no target namespace found - exiting
JBPRDSW0002	getSchemaTargetNameSpace: no matching namespace for prefix: {0}
JBPRDSW0003	Did not find a repository item. Attempting fallback option repoKey: {0}
JBPRDSW0004	Returning NULL for for publicId={0} systemID={1}
JBPRDSW0005	processPolicyReferences: Missing Operation {0}
JBPRDSW0006	Warning on line {0}: {1}
JBPRDSW0007	Error on line {0}: {1} ... Policy will not be available
JBPRDSW0008	Fatal error on line {0}: {1} ... Policy will not be available
JBPRDSW0009	tried to load the same policy multiple times: {0}
JBPRDSW0010	Error reading policy: {0}
JBPRDSW0011	tried to load the same policy multiple times: {0}
JBPRDSW0012	Error reading policy: {0}

JBPRDSW0013	Caught exception looking up {0} from cache + {1} message = {2}
JBPRDSW0014	Exception results in cache-miss
JBPRDSW0015	Exception caught while storing {0}, message = {1}
JBPRDSW0016	subsequent lookups will result in cache-miss
JBPRDSW0017	Duplicate user name during user creation
JBPRDSW0018	Duplicate user name during user creation
JBPRDSW0019	createAuthority was passed a non-string object for a role. Its class is: {0}
JBPRDSW0020	proper authorities may not be correctly mapped
JBPRDSW0358	Attribute {0} already exists. Remove it first or use update.
JBPSASCE0001	invalid input feed format:
JBPSASCE0002	Malformed Syndication URL!
JBPSASCE0003	Internal Server Error
JBPSASCE0004	Failed to handle given request
JBPSASCE0005	Failed to handle given request for service [{0}]. Error = {1}

---

<b>JBPSASCE0006</b>	<b>Only simple XPath expression is allowed.</b>
<b>Explanation</b>	Only Simple XPath expressions are allowed i.e., advanced xpath expressions are not allowed in this context.
<b>Action</b>	Use simple XPath expression to refer to collection of records e.g. /response/records/record
<b>JBPSASCE0007</b>	<b>Failed to send mail. Please check mail server configuration in Administration area</b>
<b>JBPSASCE0008</b>	<b>SAML: core signature validation failure</b>
<b>JBPSASCE0009</b>	<b>SAML signature validation returns: {0}</b>
<b>JBPSASCE0010</b>	<b>SAML signature validation for reference [{0}] is: {1}</b>
<b>JBPSASCE0011</b>	<b>SAML Assertion: token signature invalid. Rejecting</b>
<b>JBPSASCE0012</b>	<b>SAML: unable to obtain certificate from assertion</b>
<b>JBPSASCE0013</b>	<b>The certificate in the SAML assertion does not match any trusted entries in the keystore file: {0}</b>
<b>JBPSASCE0014</b>	<b>Trusted Keystore file {0} not found</b>
<b>JBPSASCE0015</b>	<b>Problem loading trusted keystore file {0}</b>
<b>JBPSASCE0016</b>	<b>Invalid username. Please only use letters, numbers, '-', '.', '_'</b>
<b>JBPSASCE0017</b>	<b>Invalid log file location specified.</b>

<b>JBPSASCE0018</b>	<b>No logs found with specified criteria.</b>
<b>JBPSASCE0019</b>	<b>Failed to search logs. Error -&gt; {0}</b>
<b>JBPSASCE0020</b>	<b>Invalid input.</b>
<b>JBPSASCE0021</b>	<b>Invalid {0} [Help:{1}]</b>
<b>JBPSASCE0022</b>	<b>Only letters, numbers, underscores, periods and hyphens are allowed</b>
<b>JBPSASCE0023</b>	<b>Validation Errors: ({0})</b>
<b>JBPSASCE0024</b>	<b>Only positive numbers are allowed.</b>
<b>JBPSASCE0667</b>	<b>File with URL {0} cannot be found</b>
<b>JBPSASCE0668</b>	<b>Missing url</b>
<b>JBPSASCE0669</b>	<b>File was deleted</b>
<b>JBPSASCE0670</b>	<b>Operation is {0} , but source url is missing</b>
<b>JBPSASCE0671</b>	<b>Missing url</b>
<b>JBPSASCE0672</b>	<b>Unsupported HTTP Method {0}. Method should be {POST PUT DELETE}</b>
<b>JBPSASCE0673</b>	<b>Authentication failed.</b>

---

JBPSASCE0674	User ID was not provided in the request and there is no active user session
JBPSASCE0675	Password was not provided in the request and here is no active user session fore requested userid: {0}
JBPSASCE0676	Userid: {0}
JBPSASCE0677	The system has exceeded the maximum number of users licensed for this installation. Please try again later or contact your administrator.
JBPSASCE0678	Logout Success
JBPSASCE0679	This item is currently in use by:  
JBPSASCE0680	[App {0}] {1}
JBPSASCE0681	[Mashup {0}] {1}
JBPSASCE0682	No input provided
JBPSASCE0683	A valid input object is required
JBPSASCE0684	No Input
JBPSASCE0685	Request processing failed with one or more errors:
JBPSASCE0686	Invalid request. Please check service name, operation name, version and parameters.
JBPSASCE0687	Received empty request. Request cannot be empty.

<b>JBPSASCE0688</b>	<b>Cannot bootstrap saml2</b>
<b>JBPSASCE0689</b>	<b>Count : {0} Count by Minute :</b>
<b>JBPSASCE0690</b>	<b># Current requests in progress</b>
<b>JBPSASCE0691</b>	<b>Size of Current or most recent Request Payload</b>
<b>JBPSASCE0692</b>	<b>Size of Current or most recent Response Payload</b>
<b>JBPSASCE0693</b>	<b>Request Processing Time of Current or most recent Request</b>
<b>JBPSASCE0694</b>	<b>JVM Up Time</b>
<b>JBPSASCE0695</b>	<b>The length of time that the JVM has been running</b>
<b>JBPSASCE0696</b>	<b>JVM Heap Size</b>
<b>JBPSASCE0697</b>	<b>The memory usage of the JVM</b>
<b>JBPSASCE0698</b>	<b>UpTime</b>
<b>JBPSASCE0699</b>	<b>HeapSize</b>
<b>JBPSASCE0700</b>	<b>: # of Requests received</b>
<b>JBPSASCE0701</b>	<b>: # of Requests resulting in errors</b>

---

<b>JBPSASCE0702</b>	<b>: # of Requests processed successfully</b>
<b>JBPSASCE0703</b>	<b>: # of Requests results in Warnings</b>
<b>JBPSASCE0704</b>	<b>: # of Requests received</b>
<b>JBPSASCE0705</b>	<b>: # of Requests resulting in errors</b>
<b>JBPSASCE0706</b>	<b>: # of Requests processed successfully</b>
<b>JBPSASCE0707</b>	<b>: # of Requests results in Warnings</b>
<b>JBPSASCE0708</b>	
<b>JBPSASCE0709</b>	<b>: Total Request Processing time</b>
<b>JBPSASCE0710</b>	<b>: Total Time processing successful requests</b>
<b>JBPSASCE0711</b>	<b>: Total time Processing failed requests</b>
<b>JBPSASCE0712</b>	<b>: Total time Processing warning requests</b>
<b>JBPSASCE0713</b>	<b>Last Sample Time :</b>
<b>JBPSASCE0714</b>	<b>Failed to generate HMAC : {0}</b>
<b>JBPSASCE0715</b>	<b>Manages files such as images, xml files and others</b>

JBPSASCE0716	Date format should be
JBPSASCE0717	cannot contain *
JBPSASCE0718	Service testGeneralFindAll failed.
JBPSASCE0719	Unrecognised service type, {0}
JBPSASCE0720	Failed to instantiate ServiceAdapter
JBPSASCE0721	Failed to find ServiceAdapter
JBPSASCE0722	Failed to access ServiceAdapter
JBPSASCE0723	Service type not recognised, {0}
JBPSASCE0724	Error loading Schema '{0}' : {1}
JBPSASCE0725	Error loading Schema for URL '{0}' : {1}
JBPSASCE0726	Error generating XML instances: No schemas to process
JBPSASCE0727	Schema compilation errors:
JBPSASCE0728	could not find schema type: {{0}} {1}
JBPSASCE0729	fail to create XML instance document document: {0}

---

JBPSASCE0730	No schemas to process
JBPSASCE0731	Schema compilation errors:
JBPSASCE0732	could not find schema type: {{0}} {1}
JBPSASCE0733	fail to create XML instance document document: {0}
JBPSASCE0734	Token Lookup Strategy
JBPSASCE0735	Cannot find Signature element
JBPSASCE0736	Signature failed core validation
JBPSASCE0737	signature validation status: {0}
JBPSASCE0738	] validity status: {0}
JBPSASCE0739	No key found!
JBPSASCE0740	LogoutHandlers are required
JBPSASCE0741	Logout Success
JBPSASCE0742	Token is set as HTTP cookie
JBPSASCE0743	{0} attribute not found in request.

<b>JBPSASCE0744</b>	<b>Requested service didn't return any data</b>
<b>JBPSASCE0745</b>	<b>App {0} is not pending. Nothing to approve.</b>
<b>JBPSASCE0749</b>	<b>App {0} is already in AppDepot. Cannot reject an App already in AppDepot.</b>
<b>JBPSASCE0753</b>	<b>App {0} is not in AppDepot approval queue. Cannot cancel an App that is not waiting for approval.</b>
<b>JBPSASCE0758</b>	<b>App {0} is already pending approval in AppDepot. You have to cancel previous submission before submitting your App again.</b>
<b>JBPSASCE0762</b>	<b>Imported Pending AppDepot App</b>
<b>JBPSASCE0763</b>	<b>Imported Approved AppDepot App</b>
<b>JBPSASCE0764</b>	<b>Unexpected Exception importing AppDepot App: {0}</b>
<b>JBPSASCE0765</b>	<b>Manages dependency between entities</b>
<b>JBPSASCE0766</b>	<b>This service allows the configuration of supported languages by Mashzone NextGen Mashup Server</b>
<b>JBPSASCE0767</b>	<b>Enterprise Mashlet Hub</b>
<b>JBPSASCE0768</b>	<b>Job not found: {0}</b>
<b>JBPSASCE0769</b>	<b>All Jobs suspended</b>

---

<b>JBPSASCE0770</b>	<b>All Jobs resumed</b>
<b>JBPSASCE0771</b>	<b>Illegal from date format : {0}</b>
<b>JBPSASCE0772</b>	<b>Illegal to date format : {0}</b>
<b>JBPSASCE0773</b>	<b>EMML was not initialized</b>
<b>JBPSASCE0774</b>	<b>A cache is required. Use setCache(Cache) to provide one.</b>
<b>JBPSASCE0775</b>	<b>Content not supported for this mime type</b>
<b>JBPSASCE0776</b>	<b>Search Criteria Validation Error:</b>
<b>JBPSASCE0777</b>	<b>onDate cannot be used with beforeDate or afterDate</b>
<b>JBPSASE0001</b>	<b>Failed to create custom secure client</b>
<b>JBPSASE0002</b>	<b>Request data not set</b>
<b>JBPSASE0003</b>	<b>Service invocation context not set</b>
<b>JBPSASE0004</b>	<b>Failed to identify response type</b>
<b>JBPSASE0005</b>	<b>Unknown feed type. Supported types are rss/feed/rdf. Skipping sanitization</b>
<b>JBPSASE0006</b>	<b>Error sanitizing node</b>

<b>JBPSASE0007</b>	<b>Error getting security profile information for profile - {0}</b>
<b>JBPSASE0008</b>	<b>Failed to create SOAPFactory instance</b>
<b>JBPSASE0009</b>	<b>Input SOAP request is empty</b>
<b>JBPSASE0010</b>	<b>Failed to create SOAP message from input request</b>
<b>JBPSASE0011</b>	<b>Input SOAP request is empty</b>
<b>JBPSASE0012</b>	<b>Failed to create SOAP message from input request</b>
<b>JBPSASE0013</b>	<b>Failed to create SOAPFault object</b>
<b>JBPSASE0014</b>	<b>-----Failed to convert response xml,</b>
<b>JBPSASE0015</b>	<b>Couldn't convert String to OMElement</b>
<b>JBPSASE0016</b>	<b>Unable to read data from input stream</b>
<b>JBPSASE0017</b>	<b>Unable to send response to client</b>
<b>JBPSASE0018</b>	<b>Failed to get App {0}</b>
<b>JBPSASE0019</b>	<b>App cannot be found</b>
<b>JBPSASE0020</b>	<b>App cannot be found</b>

---

<b>JBPSASE0021</b>	<b>Failed to get Lib.</b>
<b>JBPSASE0022</b>	<b>Lib cannot be found</b>
<b>JBPSASE0023</b>	<b>App cannot be found</b>
<b>JBPSASE0024</b>	<b>Unsupported service type:</b>
<b>JBPSASE0025</b>	<b>SharePoint Service Export, failed to instantiate SharePoint Exporter</b>
<b>JBPSASE0026</b>	<b>SharePoint Service Export, unable to access SharePoint Exporter</b>
<b>JBPSASE0027</b>	<b>SharePoint Service Export, failed to find SharePoint Exporter</b>
<b>JBPSASE0028</b>	<b>EMML script is missing</b>
<b>JBPSASE0029</b>	<b>Cannot fetch Excel data</b>
<b>JBPSASE0030</b>	<b>Cannot find class for DBMashupExporter</b>
<b>JBPSASE0031</b>	<b>Cannot fetch XML data, exception: {0}</b>
<b>JBPSASE0032</b>	<b>Invalid query. Unexpected characters after {0}</b>
<b>JBPSASE0033</b>	<b>Invalid query. Query should start with (all mine user ids name type subtype). But found {0}</b>
<b>JBPSASE0034</b>	<b>Invalid query. Expected "=" after {0} but found {1}</b>

JBPSASE0035	Invalid query. Unexpected characters after {0}
JBPSASE0036	Invalid query. Query should start with (all mine user ids name provider category tag). But found {0}
JBPSASE0037	Invalid query. Expected "=" after {0} but found {1}
JBPSASE0038	Invalid query. Left side of "=" is empty
JBPSASE0039	Invalid query. Right side of "=" is empty
JBPSASE0040	Invalid query. Unexpected characters after {0}
JBPSASE0041	Invalid query. Query should start with (all ids name type tag). But found {0}
JBPSASE0042	Invalid query. Expected "=" after {0} but found {1}
JBPSASE0043	failed
JBPSASE0044	Illegal HourOfDay: {0}
JBPSASE0045	Illegal Minute argument: {0}
JBPSASE0046	Mashzone NextGen Platform Statistics :
JBPSASE0047	Service Name : {0}
JBPSASE0048	Statistics : {0}

---

<b>JBPSASE0049</b>	<b>StatsHolder : {0};</b>
<b>JBPSASE0050</b>	<b>lastSampledHour : {0}</b>
<b>JBPSASE0051</b>	<b>HourOfDay : {0}</b>
<b>JBPSASE0052</b>	<b>ServiceAdapterStats : {0}</b>
<b>JBPSASE0053</b>	<b>Cannot resize image</b>
<b>JBPSASE0054</b>	<b>Invalid format for orderBy</b>
<b>JBPSASE0055</b>	<b>Not implemented</b>
<b>JBPSASE0056</b>	<b>Not implemented</b>
<b>JBPSASE0057</b>	<b>Invalid search request</b>
<b>JBPSASE0058</b>	<b>Resource upload failed</b>
<b>JBPSASE0059</b>	<b>Keystore url may not be null</b>
<b>JBPSASE0060</b>	<b>Keystore may not be null</b>
<b>JBPSASE0061</b>	<b>Could not find CA Certificate nor Trust Certificate with aliases: {0}, {1}</b>
<b>JBPSASE0062</b>	<b>Unsupported algorithm exception {0}</b>

<b>JBPSASE0063</b>	<b>Keystore exception: {0}</b>
<b>JBPSASE0064</b>	<b>Key management exception: {0}</b>
<b>JBPSASE0065</b>	<b>I/O error reading keystore/truststore file: {0}</b>
<b>JBPSASE0066</b>	<b>Parameters may not be null</b>
<b>JBPSASE0067</b>	<b>Trust manager may not be null</b>
<b>JBPSASE0068</b>	<b>invalid endpoint url</b>
<b>JBPSASE0069</b>	<b>fail to open connection</b>
<b>JBPSASE0070</b>	<b>no trust manager found</b>
<b>JBPSASE0071</b>	<b>The endpoint reference is not valid: {0}</b>
<b>JBPSASE0072</b>	<b>Parameters may not be null</b>
<b>JBPSASE0073</b>	<b>Service with id = {0} does not exist</b>
<b>JBPSASE0074</b>	<b>Service with name = {0} does not exist</b>
<b>JBPSASE0075</b>	<b>fail retrieving resource file or metadata information associated to this service</b>
<b>JBPSASE0076</b>	<b>Error while reading CSV file data into java.io.Reader object</b>

---

<b>JBPSASE0077</b>	<b>Fail during data extraction: {0}</b>
<b>JBPSASE0078</b>	<b>Fail during data source as XML when parsing it: {0}</b>
<b>JBPSASE0079</b>	<b>IO error</b>
<b>JBPSASE0080</b>	<b>Error getting data</b>
<b>JBPSASE0081</b>	<b>Failed to read response on second try with ISO-8859-1. Bailing out...</b>
<b>JBPSASE0082</b>	<b>XmlException while parsing response</b>
<b>JBPSASE0083</b>	<b>{0} is not a valid operation name</b>
<b>JBPSASE0084</b>	<b>Class loader error.</b>
<b>JBPSASE0085</b>	<b>Data transformation error.</b>
<b>JBPSASE0086</b>	<b>Illegal access error.</b>
<b>JBPSASE0087</b>	<b>Service class loader error.</b>
<b>JBPSASE0088</b>	<b>Instantiation error.</b>
<b>JBPSASE0089</b>	<b>Invalid operation name.</b>
<b>JBPSASE0090</b>	<b>Service invocation error.</b>

<b>JBPSASE0091</b>	<b>&lt;{0}&gt; failed to instantiate factory method, {1}</b>
<b>JBPSASE0092</b>	<b>{{0}} Unexpected service class, {1} {2}</b>
<b>JBPSASE0093</b>	<b>{{0}} failed to match interface implementation, {1}, {2} - Service Instantiation Failed</b>
<b>JBPSASE0094</b>	<b>Class Not Found exception</b>
<b>JBPSASE0095</b>	<b>Illegal access exception</b>
<b>JBPSASE0096</b>	<b>Instantiation exception</b>
<b>JBPSASE0097</b>	<b>Invocation exception</b>
<b>JBPSASE0098</b>	<b>Failed to retrieve basic authentication password:</b>
<b>JBPSASE0099</b>	<b>Failed to retrieve NTLM authentication password:</b>
<b>JBPSASE0100</b>	<b>Error invoking SSO protected service</b>
<b>JBPSASE0101</b>	<b>Failed to invoke using security profile specific client</b>
<b>JBPSASE0102</b>	<b>HTTP exception:</b>
<b>JBPSASE0103</b>	<b>I/O exception:</b>
<b>JBPSASE0104</b>	<b>The NTLM credentials provided are invalid</b>

---

<b>JBPSASE0105</b>	<b>Failed to invoke via NTLM v2 connection:</b>
<b>JBPSASE0106</b>	<b>Failed to invoke service</b>
<b>JBPSASE0107</b>	<b>Currently only GET and POST methods are supported for REST services</b>
<b>JBPSASE0108</b>	<b>Unsupported REST operation. Currently only GET and POST are supported for REST services</b>
<b>JBPSASE0109</b>	<b>Error during REST service invocation</b>
<b>JBPSASE0110</b>	<b>Error during REST service invocation:</b>
<b>JBPSASE0111</b>	<b>Error during REST service invocation</b>
<b>JBPSASE0112</b>	<b>Error during REST service invocation:</b>
<b>JBPSASE0113</b>	<b>Invalid keystore file location for Syndication mutual SSL configuration settings, please review the spelling</b>
<b>JBPSASE0114</b>	<b>Invalid configuration for mutual SSL Syndication service, please check with your administrator</b>
<b>JBPSASE0115</b>	<b>Invalid HttpClient object instance</b>
<b>JBPSASE0116</b>	<b>Failed to establish connection with service</b>
<b>JBPSASE0117</b>	<b>The URL provided to retrieve the feed is not valid, please correct and try again</b>

<b>JBPSASE0118</b>	<b>Failed to fetch data for the feed due to bad URL or network connection problem</b>
<b>JBPSASE0119</b>	<b>A service was not provided to invoke</b>
<b>JBPSASE0120</b>	<b>Failed to invoke service using custom security profile {0}</b>
<b>JBPSASE0121</b>	<b>Invalid endpoint reference</b>
<b>JBPSASE0122</b>	<b>Failed reading from feed</b>
<b>JBPSASE0123</b>	<b>Failed to parse or generate feed</b>
<b>JBPSASE0124</b>	<b>Invalid response format</b>
<b>JBPSASE0125</b>	<b>Failed to process feed</b>
<b>JBPSASE0126</b>	<b>Failed to get service metadata for service {0}</b>
<b>JBPSASE0127</b>	<b>Couldn't find end point for service {0}</b>
<b>JBPSASE0128</b>	<b>Got empty SOAP request. Please check the log for errors</b>
<b>JBPSASE0129</b>	<b>Got empty SOAP request</b>
<b>JBPSASE0130</b>	<b>Failed to invoke SOAP service.</b>
<b>JBPSASE0131</b>	<b>Failed to send SOAP request to target service</b>

---

<b>JBPSASE0132</b>	<b>Fail encoding certificate:</b>
<b>JBPSASE0133</b>	<b>Xml parsing exception:</b>
<b>JBPSASE0134</b>	<b>soap client exception:</b>
<b>JBPSASE0135</b>	<b>SOAP Fault [code: {0} reason {1} : {2} detail {3} ]</b>
<b>JBPSASE0136</b>	<b>fail to decrypt Basic Auth password:</b>
<b>JBPSASE0137</b>	<b>The stored basic authentication information is corrupt or invalid</b>
<b>JBPSASE0138</b>	<b>The URL for keystore/truststore is not valid</b>
<b>JBPSASE0139</b>	<b>Error invoking SSO protected service</b>
<b>JBPSASE0140</b>	<b>Failed to invoke service using custom security profile {0}</b>
<b>JBPSASE0141</b>	<b>SOAP message contains multiRef nodes and cannot be converted to JSON. Please use resultFormat=soap header in the request to get native SOAP message</b>
<b>JBPSASE0142</b>	<b>SOAP Fault [code: {0} reason {1} : {2} detail {3} ]</b>
<b>JBPSASE0143</b>	<b>Failed to invoke SOAP service</b>
<b>JBPSASE0144</b>	<b>CAS2 Secure Client only supports GET or POST</b>
<b>JBPSASE0145</b>	<b>Cannot find OAuth Access Token to invoke this service</b>

<b>JBPSASE0146</b>	<b>Service profile definitions setup failed</b>
<b>JBPSASE0147</b>	<b>Cannot evaluate access rights. Unexpected operation payload</b>
<b>JBPSASE0148</b>	<b>Access is denied. User= {0} sid = {1} oid = {2}</b>
<b>JBPSASE0149</b>	<b>Not supported yet.</b>
<b>JBPSASE0150</b>	<b>Not supported yet.</b>
<b>JBPSASE0151</b>	<b>An AuthenticationManager is required</b>
<b>JBPSASE0152</b>	<b>A RememberMeService is required</b>
<b>JBPSASE0153</b>	<b>A SessionManager is required</b>
<b>JBPSASE0154</b>	<b>A SessionManager is required</b>
<b>JBPSASE0155</b>	<b>An AuthenticationManager is required</b>
<b>JBPSASE0156</b>	<b>A SessionIdPropagationStrategy is required</b>
<b>JBPSASE0157</b>	<b>This class was deprecated, you should not use it</b>
<b>JBPSASE0158</b>	<b>Authentication Failed</b>
<b>JBPSASE0159</b>	<b>Authentication Session Invalid</b>

---

<b>JBPSASE0160</b>	<b>Authentication Session Expired</b>
<b>JBPSASE0161</b>	<b>Authentication Failed</b>
<b>JBPSASE0162</b>	<b>AuthenticationEntryPointFilter is misconfigured. defaultAuthenticationModuleName does not point to authentication module</b>
<b>JBPSASE0163</b>	<b>Requested authentication module {0} does not exist</b>
<b>JBPSASE0164</b>	<b>Fail to create UserDetails. Expect CAS Assertion as principal, but found {0}</b>
<b>JBPSASE0165</b>	<b>Bean with name {0} expected to be of type HttpSessionContextIntegrationFilter</b>
<b>JBPSASE0166</b>	<b>Unsupported AuthN mode &lt;{0}&gt;</b>
<b>JBPSASE0167</b>	<b>Failed to resolve redirect URL</b>
<b>JBPSASE0168</b>	<b>An AuthenticationManager is required</b>
<b>JBPSASE0169</b>	<b>An AuthenticationEntryPoint is required</b>
<b>JBPSASE0170</b>	<b>Can only process HttpServletRequest</b>
<b>JBPSASE0171</b>	<b>Can only process HttpServletResponse</b>
<b>JBPSASE0172</b>	<b>Basic AuthN credentials not found</b>
<b>JBPSASE0173</b>	<b>AuthenticationDetailsSource required</b>

- JBPSASE0174** context must be defined and implement SecurityContext (typically use org.springframework.security.context.SecurityContextImpl; existing class is {0})
  
- JBPSASE0175** If using forceEagerSessionCreation, you must set allowSessionCreation to also be true
  
- JBPSASE0176** LogoutSuccessUrl required
  
- JBPSASE0177** LogoutHandlers are required
  
- JBPSASE0178** Can only process HttpServletRequest
  
- JBPSASE0179** Can only process HttpServletResponse
  
- JBPSASE0180** Please authenticate
  
- JBPSASE0181** FilterProcessesUrl required
  
- JBPSASE0182** An AuthenticationManager is required
  
- JBPSASE0183** An AuthenticationEntryPoint is required
  
- JBPSASE0184** Can only process HttpServletRequest
  
- JBPSASE0185** Can only process HttpServletResponse
  
- JBPSASE0186** An AuthenticationManager is required
  
- JBPSASE0187** Can only process HttpServletRequest

---

<b>JBPSASE0188</b>	<b>Can only process HttpServletResponse</b>
<b>JBPSASE0189</b>	<b>Failed to read SOAP message from request</b>
<b>JBPSASE0190</b>	<b>Failed to read SOAP message from request</b>
<b>JBPSASE0191</b>	<b>No SOAP message found in the input request</b>
<b>JBPSASE0192</b>	<b>No SOAP message found in the request</b>
<b>JBPSASE0193</b>	<b>Failed to create SOAP message from request</b>
<b>JBPSASE0194</b>	<b>Unable to extract credentials from SOAP request.</b>
<b>JBPSASE0195</b>	<b>Failed to extract security credentials from request</b>
<b>JBPSASE0196</b>	<b>Unable to extract credentials from SOAP request.</b>
<b>JBPSASE0197</b>	<b>Failed to extract security credentials from request</b>
<b>JBPSASE0198</b>	<b>Bad credentials. Please provide valid security credentials</b>
<b>JBPSASE0199</b>	<b>Authentication Failed</b>
<b>JBPSASE0200</b>	<b>The system has exceeded the maximum number of users licensed for this installation. Please try again later or contact your administrator.</b>
<b>JBPSASE0201</b>	<b>Authentication required. Please login</b>

- JBPSASE0202**      **Failed to generate JUMP response**
  
- JBPSASE0203**      **Cannot create ServiceRequest: {0}**
  
- JBPSASE0204**      **LogoutHandlers are required**
  
- JBPSASE0205**      **Missing required parameters. Service and operation names are required parameters.  
For example:  
http://host:port/presto/edge/api/rest/serviceName/operationName?arguments**
  
- JBPSASE0206**      **Error parsing REST request**
  
- JBPSASE0207**      **Error parsing REST request. Reason = {0}**
  
- JBPSASE0208**      **Invalid Rule in ResourceURL file. Syntax must be in form <HTTPVerb>  
<ResourcePath> <Service.Operation>. {0}**
  
- JBPSASE0209**      **Invalid Rule in ResourceURL file. Syntax must be in form <HTTPVerb>  
<ResourcePath> <Service.Operation>. {0}**
  
- JBPSASE0210**      **ERROR: Internal Error Loading Resource URLs.**
  
- JBPSASE0211**      **context must be defined and implement SecurityContext (typically use  
org.springframework.security.context.SecurityContextImpl; existing class is {0}**
  
- JBPSASE0212**      **Session is now null, but was not null at start of request; session was invalidated  
(most likely logout), so do not create a new session to store SecurityContext**
  
- JBPSASE0213**      **SecurityContextHolder set to new context, as request processing completed**

---

<b>JBPSASE0214</b>	<b>Authentication Session Invalid</b>
<b>JBPSASE0215</b>	<b>SSO token cannot be found in HttpRequest</b>
<b>JBPSASE0216</b>	<b>Validation response should start with {0}</b>
<b>JBPSASE0217</b>	<b>Validation response should end with {0}</b>
<b>JBPSASE0218</b>	<b>Validation response is blank</b>
<b>JBPSASE0219</b>	<b>SSO token string is blank</b>
<b>JBPSASE0220</b>	<b>First character is not '{'. SSO token should have format {endpointName}extrapath</b>
<b>JBPSASE0221</b>	<b>endpointName closing bracket '}' not found. SSO token should have format {endpointName}extrapath</b>
<b>JBPSASE0222</b>	<b>endpointName is blank. SSO token should have format {endpointName}extrapath</b>
<b>JBPSASE0223</b>	<b>SharepointSSOFilter is misconfigured. Cannot find description for http endpoint:&lt;{0}&gt;</b>
<b>JBPSASE0224</b>	<b>Cannot communicate with Sharepoint</b>
<b>JBPSASE0225</b>	<b>Sharepoint responded with HTTP error. HTTP error code:{0}</b>
<b>JBPSASE0226</b>	<b>Sharepoint SSO is misconfigured</b>
<b>JBPSASE0227</b>	<b>SSO server cannot validate token</b>

<b>JBPSASE0228</b>	<b>SSO server returned empty username</b>
<b>JBPSASE0229</b>	<b>An AuthenticationManager is required</b>
<b>JBPSASE0230</b>	<b>A name for http header which will have username required</b>
<b>JBPSASE0231</b>	<b>Can only process HttpServletRequest</b>
<b>JBPSASE0232</b>	<b>Can only process HttpServletResponse</b>
<b>JBPSASE0233</b>	<b>An authenticationDao must be set</b>
<b>JBPSASE0234</b>	<b>Malformed regular expression: {0}</b>
<b>JBPSASE0235</b>	<b>No matching pattern was found in subjectDN: {0}</b>
<b>JBPSASE0236</b>	<b>Regular expression must contain a single group</b>
<b>JBPSASE0237</b>	<b>An x509UserCache must be set</b>
<b>JBPSASE0238</b>	<b>An X509AuthoritiesPopulator must be set</b>
<b>JBPSASE0239</b>	<b>Certificate is null</b>
<b>JBPSASE0240</b>	<b>Invalid Certificate {0}</b>
<b>JBPSASE0241</b>	<b>Failed to unbundle mashlet,</b>

---

<b>JBPSASE0242</b>	<b>mashlet.json not found</b>
<b>JBPSASE0243</b>	<b>Failed to unbundle mashlet,</b>
<b>JBPSASE0244</b>	<b>Failed to unbundle mashlet,</b>
<b>JBPSASE0245</b>	<b>Failed to locate mashlet zip file, {0} , using id {1}</b>
<b>JBPSASE0246</b>	<b>missing name attribute {0}</b>
<b>JBPSASE0247</b>	<b>Malformed require tag, missing type or src attributes {1}</b>
<b>JBPSASE0248</b>	<b>Service operation not recognised {0} {1}</b>
<b>JBPSASE0249</b>	<b>Missing resource service id {0}</b>
<b>JBPSASE0250</b>	<b>Exception unzipping to {0}</b>
<b>JBPSASE0251</b>	<b>Exception unzipping to {0}</b>
<b>JBPSASE0252</b>	<b>Exception zipping {0}; message: {1}</b>
<b>JBPSASE0253</b>	<b>Error removing resources</b>
<b>JBPSASE0254</b>	<b>Failed to import zip file.</b>
<b>JBPSASE0255</b>	<b>Zip file not found, {0}</b>

<b>JBPSASE0256</b>	<b>Unable to generate identifier from name, {0}</b>
<b>JBPSASE0257</b>	<b>Identity already in use, {0}</b>
<b>JBPSASE0258</b>	<b>Existing identity not recognised, {0}</b>
<b>JBPSASE0259</b>	<b>Failed to save updates.</b>
<b>JBPSASE0260</b>	<b>Item must be deactivated</b>
<b>JBPSASE0261</b>	<b>Identity not recognised,</b>
<b>JBPSASE0262</b>	<b>Zip file not found</b>
<b>JBPSASE0263</b>	<b>Failed to save item.</b>
<b>JBPSASE0264</b>	<b>Item must be deactivated</b>
<b>JBPSASE0265</b>	<b>Failed to generate App Spec.</b>
<b>JBPSASE0266</b>	<b>Failed to migrate Mashlet.</b>
<b>JBPSASE0267</b>	<b>Identity already exists, {0}</b>
<b>JBPSASE0268</b>	<b>Erroring checking activate status of {0}</b>
<b>JBPSASE0269</b>	<b>Failed to generate Gadget Spec.</b>

---

JBPSASE0270	Identity not recognised, {0}
JBPSASE0271	failed to retrieve properties for app {0}
JBPSASE0272	failed to retrieve spec parts for {0}
JBPSASE0273	Failed to retrieve properties
JBPSASE0274	{0} : Publishing {1}
JBPSASE0275	{0} : Failed to publish : {1}
JBPSASE0276	{0} : Published successfully
JBPSASE0277	{0} : Failed to publish, exception thrown : {1}
JBPSASE0278	Samples path is not a directory, {0}
JBPSASE0279	Samples directory does not exist, {0}
JBPSASE0280	Existing Sample removed
JBPSASE0281	<p>Not authorized to update App : {0} </p>
JBPSASE0282	<p>Not all Mashzone NextGen Apps upgraded</p>
JBPSASE0283	<p>All Mashzone NextGen Apps upgraded</p>

JBPSASE0284	<p>No Mashzone NextGen Apps upgraded</p>
JBPSASE0285	Unable to generate unique identity with name, {0}
JBPSASE0286	No specification provided
JBPSASE0287	Failed to create App. Cause: {0}
JBPSASE0288	Identity already exists, {0}
JBPSASE0289	Failed to update compatibility attributes, {0}
JBPSASE0290	Failed to retrieve properties
JBPSASE0291	Failed to retrieve properties
JBPSASE0292	Category not recognised, {0}
JBPSASE0293	Tag not found, {0}
JBPSASE0294	Unable to locate presto/hub :
JBPSASE0295	Unexpected exception parsing app spec,
JBPSASE0296	Unexpected exception parsing app spec,
JBPSASE0297	failed to format spec,

---

JBPSASE0298	failed to convert to string,
JBPSASE0299	Failed to parse mashlet spec,
JBPSASE0300	Failed to update app spec,
JBPSASE0301	Failed to update app spec,
JBPSASE0302	Failed to create Document,
JBPSASE0303	Failed to parse spec,
JBPSASE0304	Missing app element
JBPSASE0305	Not recognised, {0}
JBPSASE0306	Not authorized to access App: {0}
JBPSASE0307	Not authorized to update App: {0}
JBPSASE0308	Not authorized to create Apps.
JBPSASE0309	Not authorized to run this App: {0}
JBPSASE0310	Tag not found, {0}
JBPSASE0311	A service with name '{0}' is already registered. Please choose another name and try again.

<b>JBPSASE0312</b>	<b>fail registering excel service:</b>
<b>JBPSASE0313</b>	<b>Not enough or invalid Excel Service information, cannot proceed with publication.</b>
<b>JBPSASE0314</b>	<b>Malformed REST URL: {0}</b>
<b>JBPSASE0315</b>	<b>Missing library id</b>
<b>JBPSASE0316</b>	<b>Failed to locate library zip file {0} version {1}</b>
<b>JBPSASE0317</b>	<b>Expected library zip file not found at path {0}</b>
<b>JBPSASE0318</b>	<b>Missing library id</b>
<b>JBPSASE0319</b>	<b>Library id already used by Mashzone NextGen {0}</b>
<b>JBPSASE0320</b>	<b>Unrecognised library path {0}</b>
<b>JBPSASE0321</b>	<b>No library javascript or stylesheets found.</b>
<b>JBPSASE0322</b>	<b>Library validation failed, {0}</b>
<b>JBPSASE0323</b>	<b>missing lib implementation? {0}</b>
<b>JBPSASE0324</b>	<b>Version not recognised, {0}</b>
<b>JBPSASE0325</b>	<b>Invalid library id given, {0}</b>

---

JBPSASE0326	Failed to initialise library json
JBPSASE0327	{0} not found.
JBPSASE0328	Hub jsapi directory not found.
JBPSASE0329	{0} not found.
JBPSASE0330	Unable to locate presto/hub : {0}
JBPSASE0331	Error reading file data : {0}
JBPSASE0332	Exception zipping lib {0}, message: {1}
JBPSASE0333	Exception unzipping to {0}, message {1}
JBPSASE0334	Error removing resource, {0}, message {1}
JBPSASE0335	logger is null
JBPSASE0336	level is null
JBPSASE0337	Refresh period must be > 0
JBPSASE0338	configurationFile is null
JBPSASE0339	configuration is null or an empty string

JBPSASE0340	Configuration file is null
JBPSASE0341	Could not create parent directory of log configuration file:
JBPSASE0342	Configuration file is not writable:
JBPSASE0343	Must specify a log file
JBPSASE0344	Not a valid log level
JBPSASE0345	Bad regular expression '{0}'
JBPSASE0346	Log file {0} does not exist
JBPSASE0347	Exception caught during logging of Runtime Information. Exception=
JBPSASE0348	Mashlet type directory not found, {0}
JBPSASE0349	type config differs from key : {0}, {1}
JBPSASE0350	Failed to read mashlets config json.
JBPSASE0351	Failed to init uwa page
JBPSASE0352	{0} not found.
JBPSASE0353	Mashlets directory not found.

---

<b>JBPSASE0354</b>	<b>Unable to access mashlet directory : {0}</b>
<b>JBPSASE0355</b>	<b>Unable to locate mashlet directory : {0}</b>
<b>JBPSASE0356</b>	<b>Error saving mashlet data : {0}</b>
<b>JBPSASE0357</b>	<b>Error reading file data : {0}</b>
<b>JBPSASE0358</b>	<b>Type already exists {0}</b>
<b>JBPSASE0359</b>	<b>Failed to convert dynabean</b>
<b>JBPSASE0360</b>	<b>Type not recognised, {0}</b>
<b>JBPSASE0361</b>	<b>error detected removing {0}</b>
<b>JBPSASE0362</b>	<b>Item already exists</b>
<b>JBPSASE0363</b>	<b>Failed to persist preferences.</b>
<b>JBPSASE0364</b>	<b>Type not recognised, {0}</b>
<b>JBPSASE0365</b>	<b>Item already exists, {0}</b>
<b>JBPSASE0366</b>	<b>Identity not recognised, {0}</b>
<b>JBPSASE0367</b>	<b>Identity already in use, {0}</b>

JBPSASE0368	Property is incompatible with existing datatype, {0}
JBPSASE0369	Failed to persist property.
JBPSASE0370	Property is readOnly, {0}
JBPSASE0371	Identity not recognised, {0}
JBPSASE0372	type mismatch : incorrect tag property datatype, {0}
JBPSASE0373	type mismatch : name, value = {0}, {1}, types = {2}, {3}
JBPSASE0374	failed to parse json
JBPSASE0375	Error unregistering service : Specify a Mashup Service name.
JBPSASE0376	Error unregistering service :
JBPSASE0377	Failed to parse token. Unknown token type: {0}
JBPSASE0378	There is no request token which can be approved
JBPSASE0379	Failed to get OAuth request token
JBPSASE0380	Failed to get OAuth Access token.
JBPSASE0381	RegistryObject with id={0} is not OAuthProvider

---

<b>JBPSASE0382</b>	<b>OAuth Provider with id {0} does not exist</b>
<b>JBPSASE0383</b>	<b>Invalid XACML policy document</b>
<b>JBPSASE0384</b>	<b>User or group name cannot be null!</b>
<b>JBPSASE0385</b>	<b>User or group {0} does not exist!</b>
<b>JBPSASE0386</b>	<b>Invalid users or groups, {0}</b>
<b>JBPSASE0387</b>	<b>Failed to create User Profile</b>
<b>JBPSASE0388</b>	<b>Failed to create Named User Profile</b>
<b>JBPSASE0389</b>	<b>Failed to update Named User Profile</b>
<b>JBPSASE0390</b>	<b>Failed to create User Profile</b>
<b>JBPSASE0391</b>	<b>Category Id should end with a '/', for example: '/cat/subCat/subSubCat/'</b>
<b>JBPSASE0392</b>	<b>Failed to get service details</b>
<b>JBPSASE0393</b>	<b>registration failed</b>
<b>JBPSASE0394</b>	<b>Service not found for id:{0}</b>
<b>JBPSASE0395</b>	<b>Failed to clone service</b>

<b>JBPSASE0396</b>	<b>DAO No longer supported</b>
<b>JBPSASE0397</b>	<b>Don't know how to unregister service of type: {0}</b>
<b>JBPSASE0398</b>	<b>Application with name= {0} already exists</b>
<b>JBPSASE0399</b>	<b>Failed to find template for given service and NSD type</b>
<b>JBPSASE0400</b>	<b>Cannot get Provider for id=null</b>
<b>JBPSASE0401</b>	<b>Invalid service Id = {0}</b>
<b>JBPSASE0402</b>	<b>REST access is not supported for this service {0}</b>
<b>JBPSASE0403</b>	<b>Couldn't get NSD for service {0}</b>
<b>JBPSASE0404</b>	<b>Error in construcing RESTified URL</b>
<b>JBPSASE0405</b>	<b>Failed to get certificate names from given trust store: {0} Cause: {1}</b>
<b>JBPSASE0406</b>	<b>Invalid keystore file location for REST mutual SSL configuration settings, please review the spelling</b>
<b>JBPSASE0407</b>	<b>Invalid configuration for mutual SSL REST service, please check with your administrator</b>
<b>JBPSASE0408</b>	<b>Failed to register service using custom client</b>
<b>JBPSASE0409</b>	<b>Is not possible to retrieve output sample/xml schema, probably a bad URL or a network connection problem.</b>

---

<b>JBPSASE0410</b>	<b>Invalid JSON document</b>
<b>JBPSASE0411</b>	<b>Malformed REST URL: {0}</b>
<b>JBPSASE0412</b>	<b>Cannot find operation:{0}</b>
<b>JBPSASE0413</b>	<b>Operation name is not provided and there is more then one operation to choose from</b>
<b>JBPSASE0414</b>	<b>A service with name {0} is already registered. Please choose another name and try again</b>
<b>JBPSASE0415</b>	<b>Malformed REST URL!</b>
<b>JBPSASE0416</b>	<b>Unrecognized output sample type, not an XML nor and Schema nor a URL to one of them</b>
<b>JBPSASE0417</b>	<b>Cannot find service registrar for service type:{0}</b>
<b>JBPSASE0418</b>	<b>Failed to retrieve shared item</b>
<b>JBPSASE0419</b>	<b>error translating json to string</b>
<b>JBPSASE0420</b>	<b>Cannot retrieve host't IP adress {0} using presto.config value: {1}</b>
<b>JBPSASE0421</b>	<b>Error in WSDL inspection during input message</b>
<b>JBPSASE0422</b>	<b>Error in WSDL inspection during output message</b>

- JBPSASE0423**      **The operation with name {0} is duplicated, Duplicate operation names are not supported**
  
- JBPSASE0424**      **Error registering Doc Style WSDL Service:**
  
- JBPSASE0425**      **Error registering WSDL Doc style service : WSDL inspection exception**
  
- JBPSASE0426**      **Error registering WSDL Doc style service :**
  
- JBPSASE0427**      **A service with name '{0}' is already registered. Please choose another name and try again.**
  
- JBPSASE0428**      **Incomplete HTTP Basic Authentication information, please make sure you provide user and password values**
  
- JBPSASE0429**      **Incomplete NTLM Authentication information received, please make sure you provide user/password and domain.**
  
- JBPSASE0430**      **WSDL SSL mutual authentication is not configured yet, please check with your administrator.**
  
- JBPSASE0431**      **Invalid keystore/truststore URL**
  
- JBPSASE0432**      **given client doesn't implement ServiceInvocationCustomClient interface for profile = {0}**
  
- JBPSASE0433**      **error getting security profile definition for profile = {0}**
  
- JBPSASE0434**      **error getting security profile definition for profile = {0}**

---

JBPSASE0435	error using custom client for security profile = {0}
JBPSASE0436	error invoking service client for profile = {0}
JBPSASE0437	There is no security profile set for this registration
JBPSASE0438	Error during WSDL inspection: {0}
JBPSASE0439	Failed to load WSDL: {0}
JBPSASE0440	the feed sample {0} is corrupted or not a valid XML.
JBPSASE0441	the feed sample {0} cannot be loaded
JBPSASE0442	feed type: {0} not supported, this is an error on the presto.config file in the property "syndication.type"
JBPSASE0443	Malformed URL: {0}
JBPSASE0444	A service with name '{0}' is already registered. Please choose another name and try again.
JBPSASE0445	Service returned an error response code: {0}
JBPSASE0446	fail parsing input feed:
JBPSASE0447	Incorrect current password.
JBPSASE0448	The output feed {0} configured on Mashzone NextGen server is not supported or misspelled.

JBPSASE0449	Invalid syndication feed type: {0}
JBPSASE0450	Error while registering the feed:
JBPSASE0451	Range should contain at least one element. If you want to get ALL, use [-1,-1) as a range
JBPSASE0452	User Id or Email cannot be empty. Need user id or email to retrieve password
JBPSASE0453	Sending password reset code email failed: Error =
JBPSASE0454	Error while creating password reset code. Error =
JBPSASE0455	Invalid user name
JBPSASE0456	{0} Id "{1}" already exists, please choose another id and retry
JBPSASE0457	Name already exists. Please choose another name and retry
JBPSASE0458	Data not available
JBPSASE0459	Failed to convert bean : {0}
JBPSASE0460	A service with name '{0}' is already registered. Please choose another name and try again.
JBPSASE0461	Failed to build payload for Excel service. Request details = {0}
JBPSASE0462	Error building Mashup Service request payload :

---

JBPSASE0463	Invalid JUMP protocol version: {0} . Supported versions are 1.0, 1.1 and 2.0
JBPSASE0464	Error building payload : {0}
JBPSASE0465	error during payload building
JBPSASE0466	Cannot find XML payload in request
JBPSASE0467	Failed to construct request. Value is null for parameter {0}
JBPSASE0468	Xstream error - converting xml to java object
JBPSASE0469	Failed to construct request. Invalid XML
JBPSASE0470	Failed to construct request
JBPSASE0471	Failed to serialize XML parameter value to string
JBPSASE0472	Error building payload :
JBPSASE0473	ERROR.....dyna bean is null. Param# {0}
JBPSASE0474	ERROR.....params is null. Param# {0}
JBPSASE0475	ERROR.....failed to create object hierarchy. Param# {0}
JBPSASE0476	Error building payload :

<b>JBPSASE0477</b>	<b>Error createObjectHierarchy :</b>
<b>JBPSASE0478</b>	<b>Error applyXPath :</b>
<b>JBPSASE0479</b>	<b>Unexpected NumberFormatException parsing long value,</b>
<b>JBPSASE0480</b>	<b>Couldn't parse given value for *date* field = {0}</b>
<b>JBPSASE0481</b>	<b>SOAPGatewayController initialization failed</b>
<b>JBPSASE0482</b>	<b>[SOAPGC] Failed to invoke service. Error =</b>
<b>JBPSASE0483</b>	<b>PrestoWS</b>
<b>JBPSASE0484</b>	<b>SOAP Request Error</b>
<b>JBPSASE0485</b>	<b>Service {0} ) is currently not active.</b>
<b>JBPSASE0486</b>	<b>PrestoWS</b>
<b>JBPSASE0487</b>	<b>SOAP Request Error</b>
<b>JBPSASE0488</b>	<b>Requested service is currently not active</b>
<b>JBPSASE0489</b>	<b>SOAP service invocation failed</b>
<b>JBPSASE0490</b>	<b>PrestoWS</b>

---

<b>JBPSASE0491</b>	<b>SOAP Request Error</b>
<b>JBPSASE0492</b>	<b>Error while handling Service response</b>
<b>JBPSASE0493</b>	<b>Got empty response from server. Please check the request.</b>
<b>JBPSASE0494</b>	<b>Error executing request. Reason = {0}</b>
<b>JBPSASE0495</b>	<b>Error while processing response. Reason =</b>
<b>JBPSASE0496</b>	<b>Failed to retrieve WSDL for service {0}</b>
<b>JBPSASE0497</b>	<b>Couldn't locate WSDL for given service</b>
<b>JBPSASE0498</b>	<b>Failed to remove Mashzone NextGen headers</b>
<b>JBPSASE0499</b>	<b>Couldn't process SOAP message</b>
<b>JBPSASE0500</b>	<b>Failed to remove Mashzone NextGen headers</b>
<b>JBPSASE0501</b>	<b>Unable to create SOAP message from input</b>
<b>JBPSASE0502</b>	<b>Unable to extract credentials from SOAP request.</b>
<b>JBPSASE0503</b>	<b>Unable to extract credentials from SOAP request.</b>
<b>JBPSASE0504</b>	<b>Error extracting user token credentials from given SOAP request</b>

<b>JBPSASE0505</b>	<b>Unable to extract BinarySecurityToken security credentials from the request</b>
<b>JBPSASE0506</b>	<b>Unable to extract BinarySecurityToken security credentials from the request</b>
<b>JBPSASE0507</b>	<b>Unable to extract UsernameToken security credentials from the request</b>
<b>JBPSASE0508</b>	<b>Failed to handle REST request</b>
<b>JBPSASE0509</b>	<b>Invalid JUMP protocol version: {0} . Supported versions are 1.0, 1.1 and 2.0</b>
<b>JBPSASE0510</b>	<b>Currently only GET and POST types are supported for REST services</b>
<b>JBPSASE0511</b>	<b>Currently only GET and POST types are supported for REST services</b>
<b>JBPSASE0512</b>	<b>Error in constructing input to REST service</b>
<b>JBPSASE0513</b>	<b>Error in constructing input to REST service</b>
<b>JBPSASE0514</b>	<b>Not yet implemented</b>
<b>JBPSASE0515</b>	<b>No Input Arguments found for operationId =</b>
<b>JBPSASE0516</b>	<b>Failed to build payload for REST service.</b>
<b>JBPSASE0517</b>	<b>Failed to serialize XML parameter value to string</b>
<b>JBPSASE0518</b>	<b>received empty request. Request cannot be empty</b>

---

<b>JBPSASE0519</b>	<b>Service ({0}) is not currently active</b>
<b>JBPSASE0520</b>	<b>Service invocation failed. Response is null</b>
<b>JBPSASE0521</b>	<b>Sorry! You are not authorized to access this resource or perform this action</b>
<b>JBPSASE0522</b>	<b>Authentication exception</b>
<b>JBPSASE0523</b>	<b>Authentication exception</b>
<b>JBPSASE0524</b>	<b>Bad Request</b>
<b>JBPSASE0525</b>	<b>Unable to parse input request</b>
<b>JBPSASE0526</b>	<b>Unable to parse request string. Please check the syntax. Error = {0}</b>
<b>JBPSASE0527</b>	<b>Bad Request -</b>
<b>JBPSASE0528</b>	<b>Unavailable</b>
<b>JBPSASE0529</b>	<b>Unable to connect to Mashzone NextGen repository. Please make sure it is running before you retry.</b>
<b>JBPSASE0530</b>	<b>Unable to connect to Mashzone NextGen Repository. Error = {0}</b>
<b>JBPSASE0531</b>	<b>Relogin to Mashzone NextGen is required</b>
<b>JBPSASE0532</b>	<b>Relogin to Mashzone NextGen is required</b>

<b>JBPSASE0533</b>	<b>Relogin to Mashzone NextGen is required. Error= {0}</b>
<b>JBPSASE0534</b>	<b>Relogin to Mashzone NextGen is rquired</b>
<b>JBPSASE0535</b>	<b>Internal Server Error</b>
<b>JBPSASE0536</b>	<b>Invalid request issued</b>
<b>JBPSASE0537</b>	<b>Invalid request</b>
<b>JBPSASE0538</b>	<b>Internal Server Error -</b>
<b>JBPSASE0539</b>	<b>License</b>
<b>JBPSASE0540</b>	<b>License</b>
<b>JBPSASE0541</b>	<b>No data found for session variables in response</b>
<b>JBPSASE0542</b>	<b>{0} service doesn't exist in the system</b>
<b>JBPSASE0543</b>	<b>{0} operation doesn't exist in service {1}</b>
<b>JBPSASE0544</b>	<b>Service (\${0}) is currently not active. Please activate the service and try again</b>
<b>JBPSASE0545</b>	<b>Operation ({0}) doesn't exist in service {1}</b>
<b>JBPSASE0546</b>	<b>{0} operation doesn't exist in service {1}</b>

---

<b>JBPSASE0547</b>	<b>Service Stopped - Unable to invoke service: {0} RequestPayload : {1}</b>
<b>JBPSASE0548</b>	<b>{0} Service Adapter is currently not running</b>
<b>JBPSASE0549</b>	<b>Service invocation failed.</b>
<b>JBPSASE0550</b>	<b>Service invocation failed.</b>
<b>JBPSASE0551</b>	<b>Unsupported Service Type:</b>
<b>JBPSASE0552</b>	<b>Session binding failed. Unable to determine response type</b>
<b>JBPSASE0553</b>	<b>Couldn't get value for binding expression = {0}</b>
<b>JBPSASE0554</b>	<b>server side binding error</b>
<b>JBPSASE0555</b>	<b>Invalid username or password</b>
<b>JBPSASE0556</b>	<b>Failed to build payload for WSDL service. Error = {0}</b>
<b>JBPSASE0557</b>	<b>Unable to extract values for SOAP body from input parameters</b>
<b>JBPSASE0558</b>	<b>Failed to build payload for WSDL service. Error = {0}</b>
<b>JBPSASE0559</b>	<b>Unable to find repository item = {0}</b>
<b>JBPSASE0560</b>	<b>Unable to find repository item with name {0}</b>

<b>JBPSASE0561</b>	<b>Failed to set data for certain elements in the request</b>
<b>JBPSASE0562</b>	<b>Error in applyXPath</b>
<b>JBPSASE0563</b>	<b>Invalid JUMP protocol version: {0} . Supported versions are 1.0, 1.1 and 2.0</b>
<b>JBPSASE0564</b>	<b>Request has no input</b>
<b>JBPSASE0565</b>	<b>error in constructing SOAP payload using inputFormat=xml</b>
<b>JBPSASE0566</b>	<b>Failed to build payload for WSDL service.</b>
<b>JBPSASE0567</b>	<b>Not yet implemented...</b>
<b>JBPSASE0568</b>	<b>Failed to build payload for WSDL service.</b>
<b>JBPSASE0569</b>	<b>Failed to serialize XML parameter value to string</b>
<b>JBPSASE0570</b>	<b>Unable to extract values for SOAP body from input parameters</b>
<b>JBPSASE0571</b>	<b>Unable to extract values for SOAP body from input parameters</b>
<b>JBPSASE0572</b>	<b>JDOM error in constructPayload</b>
<b>JBPSASE0573</b>	<b>IO error in constructPayload</b>
<b>JBPSASE0574</b>	<b>JDOM error in constructPayload</b>

---

JBPSASE0575	IO error in constructPayload
JBPSASE0576	Request template parse error in SOAP constructPayload:
JBPSASE0577	parameter {0} is expected to be of type string.
JBPSASE0578	parameter {0} is set to null, assuming empty.
JBPSASE0579	fail to append input value as an XML
JBPSASE0580	error in fillOutTemplate - NSME
JBPSASE0581	error in fillOutTemplate - IAE
JBPSASE0582	error in fillOutTemplate - ITE
JBPSASE0583	error in fillOutTemplate - parsing xml text
JBPSASE0584	error in fillOutTemplate - NSME
JBPSASE0585	error in fillOutTemplate - IAE
JBPSASE0586	error in fillOutTemplate - ITE
JBPSASE0587	Unable to find repository item = {0}
JBPSASE0588	Unable to find repository item with name {0}

<b>JBPSASE0589</b>	<b>Unable to paginate service : {0}</b>
<b>JBPSASE0590</b>	<b>Missing Mandatory Parameter in Service Request {0}</b>
<b>JBPSASE0591</b>	<b>Invalid Service Scheduler Request. Either 'repeatcount' or 'starttime' must be specified</b>
<b>JBPSASE0592</b>	<b>Service schedule failure :</b>
<b>JBPSASE0593</b>	<b>Missing Mandatory Parameter in Service Request</b>
<b>JBPSASE0594</b>	<b>Internal error: Missing Job Request in Scheduled Service Invocation</b>
<b>JBPSASE0595</b>	<b>Error Invoking Scheduled Service:</b>
<b>JBPSASE0596</b>	<b>Unknown Pagination Type (returning original response )</b>
<b>JBPSASE0597</b>	<b>Error converting pagination result to XML (returning complete response):</b>
<b>JBPSASE0598</b>	<b>Error converting pagination result to XML (returning complete response):</b>
<b>JBPSASE0599</b>	<b>Invalid username or password</b>
<b>JBPSASE0600</b>	<b>Data Transformer Error</b>
<b>JBPSASE0601</b>	<b>Unsupported content type/charset requested. Setting it to default (text/plain; charset=utf-8)</b>
<b>JBPSASE0602</b>	<b>Cant find default namespace</b>

---

<b>JBPSASE0603</b>	<b>Invalid folder: {0}</b>
<b>JBPSASE0604</b>	<b>This Provider or this folder does not support UIDs</b>
<b>JBPSASE0605</b>	<b>Authentication failed for user:&lt;{0}&gt;</b>
<b>JBPSASE0606</b>	<b>Unknown mail host:</b>
<b>JBPSASE0607</b>	<b>Unexpected error during mail search</b>
<b>JBPSASE0608</b>	<b>Host string should have format [host:port]. Got invalid host string {0}</b>
<b>JBPSASE0609</b>	<b>Invalid port {0}. Port should be numeric</b>
<b>JBPSASE0610</b>	<b>Got errors while sending email</b>
<b>JBPSASE0611</b>	<b>Invalid Unsent Addresses</b>
<b>JBPSASE0612</b>	<b>Valid Unsent Addresses</b>
<b>JBPSASE0613</b>	<b>Valid Sent Addresses</b>
<b>JBPSASE0614</b>	<b>Authentication to SMTP server failed</b>
<b>JBPSASE0615</b>	<b>{0} address {1} is invalid</b>
<b>JBPSASE0616</b>	<b>At least one from destination addresses (TO,CC,BCC) has to be specified</b>

<b>JBPSASE0617</b>	<b>SMTP host has to be specified</b>
<b>JBPSASE0618</b>	<b>Mail server configuration is not set. Please update mail server configuration in Administration area</b>
<b>JBPSASE0619</b>	<b>Mail server configuration is not set. Please update mail server configuration in Administration area</b>
<b>JBPSASE0620</b>	<b>Mail server configuration is not set. Please update mail server configuration in Administration area</b>
<b>JBPSASE0621</b>	<b>Mail server configuration is not set. Please update mail server configuration in Administration area</b>
<b>JBPSASE0622</b>	<b>Failed to send mail. Please check mail server configuration in Administration area</b>
<b>JBPSASE0623</b>	<b>Failed to send mail. Please check mail server configuration in Administration area</b>
<b>JBPSASE0624</b>	<b>Failed to send notification email. Invalid user id</b>
<b>JBPSASE0625</b>	<b>Failed to send notification email</b>
<b>JBPSASE0626</b>	<b>Failed to send notification email. Invalid user id</b>
<b>JBPSASE0627</b>	<b>Failed to send notification email</b>
<b>JBPSASE0628</b>	<b>fail retrieving output type:</b>
<b>JBPSASE0629</b>	<b>Error getting Mashup Output Schema :</b>

---

<b>JBPSASE0630</b>	<b>fail retrieving output type:</b>
<b>JBPSASE0631</b>	<b>Error getting Mashup Output Schema :</b>
<b>JBPSASE0632</b>	<b>Error: refElementName for this Mashup schema not found</b>
<b>JBPSASE0633</b>	<b>Error creating Mashup Output Schema :</b>
<b>JBPSASE0634</b>	<b>Error adding mashupOutputSchema :</b>
<b>JBPSASE0635</b>	<b>fail to generate schema from JSD</b>
<b>JBPSASE0636</b>	<b>fail to generate schema from NSD</b>
<b>JBPSASE0637</b>	<b>Service name cannot be empty</b>
<b>JBPSASE0638</b>	<b>WSDL access is not supported for given service type</b>
<b>JBPSASE0639</b>	<b>WSDL access is supported only for Mashup services</b>
<b>JBPSASE0640</b>	<b>The error occurs when invoking this service</b>
<b>JBPSASE0641</b>	<b>invalid request</b>
<b>JBPSASE0642</b>	<b>mashup service invocation fail</b>
<b>JBPSASE0643</b>	<b>Failed to get service details for sid= {0}</b>

<b>JBPSASE0644</b>	<b>fail building soap response:</b>
<b>JBPSASE0645</b>	<b>fail marshalling SOAP into JSON, due to the following XML processing error:</b>
<b>JBPSASE0646</b>	<b>fail marshalling SOAP into JSON, due to the following transformation error:</b>
<b>JBPSASE0647</b>	<b>Operation {0} Not Found</b>
<b>JBPSASE0648</b>	<b>Parameter {0} not found</b>
<b>JBPSASE0649</b>	<b>fail validating request</b>
<b>JBPSASE0650</b>	<b>fail to get inner XML document from request:</b>
<b>JBPSASE0651</b>	<b>type mismatch for parameter {0} should be of type {1}</b>
<b>JBPSASE0652</b>	<b>could not find message body</b>
<b>JBPSASE0653</b>	<b>fail marshalling SOAP into JSON, due to the following XML processing error:</b>
<b>JBPSASE0654</b>	<b>fail retrieving output type:</b>
<b>JBPSASE0655</b>	<b>invalid class type for request/response</b>
<b>JBPSASE0656</b>	<b>Fail to process request</b>
<b>JBPSASE0657</b>	<b>No credentials provided</b>

---

<b>JBPSASE0658</b>	<b>Fail to authenticate the user</b>
<b>JBPSASE0659</b>	<b>fail sending authentication error on soap fault message:</b>
<b>JBPSASE0660</b>	<b>invalid SOAP request</b>
<b>JBPSASE0661</b>	<b>AuthenticationManager is required</b>
<b>JBPSASE0662</b>	<b>fail to parser soap request:</b>
<b>JBPSASE0663</b>	<b>Fail to send response to client</b>
<b>JBPSASE0664</b>	<b>fail registering SOAP service {0} : {1}</b>
<b>JBPSASE0665</b>	<b>fail registering REST service {0} : {1}</b>
<b>JBPSASE0666</b>	<b>fail registering Syndication service {0} : {1}</b>
<b>JBPSASE0667</b>	<b>Unable to decrypt basic auth password for export: {0}</b>
<b>JBPSASE0668</b>	<b>Streaming service invocation not supported for this datasource type.</b>
<b>Explanation</b>	Streaming service invocation (with stream='true') not supported for this datasource type.
<b>Action</b>	use stream='false' to invoke this datasource.
<b>JBPSASW0001</b>	<b>Unable to get log file names</b>
<b>JBPSASW0002</b>	<b>CharacterCodingException while reading response encoded with: {0} - falling back to iso-8859-1</b>

- JBPSASW0003**      **no web proxy supported for NTLM v2 invocations.**
  
- JBPSASW0004**      **fail to parse SOAP header from payload**
  
- JBPSASW0005**      **fail to parse SOAP body from payload**
  
- JBPSASW0006**      **fail to parse the whole soap request from payload**
  
- JBPSASW0007**      **No soap version set on metadata database, assuming SOAP 1.1, probably this service fails to invoke**
  
- JBPSASW0008**      **no binding style for service: {0} operation {1} , invocation may fail, assuming 'document'**
  
- JBPSASW0009**      **Could not remove security profile: {0}**
  
- JBPSASW0010**      **Failed to extract credentials from JUMP Session**
  
- JBPSASW0011**      **ACEGI\_SECURITY\_CONTEXT did not contain a SecurityContext but contained: '{0}'; are you improperly modifying the HttpSession directly (you should always use SecurityContextHolder) or using the HttpSession attribute reserved for this class? - new SecurityContext instance associated with SecurityContextHolder**
  
- JBPSASW0012**      **Cannot create ServiceRequest**
  
- JBPSASW0013**      **Cannot create ServiceRequest**
  
- JBPSASW0014**      **JDK is reporting that UTF-8 is a bad encoding!? Falling back to default encoding**
  
- JBPSASW0015**      **Was not able to obtain session.**

---

JBPSASW0016	Cannot parse {0}. Should be in format propertyName:'propertyValue', but no : found
JBPSASW0017	no spec validation performed yet
JBPSASW0018	missing end, {0}
JBPSASW0019	missing start of config object {0}
JBPSASW0020	missing start of config statement, {0}
JBPSASW0021	missing end, {0}
JBPSASW0022	missing start, {0}
JBPSASW0023	null config
JBPSASW0024	Error during URL decoding given REST URL.Continuing using given URL as it is - {0}
JBPSASW0025	Failed to extract headers from WSDL
JBPSASW0026	Expected array type, but found <{0}>...continuing processing
JBPSASW0027	printHeader error
JBPSASW0028	empty request
JBPSASW0029	error in processing REST param - {0} = {1} ...using passed in value as it is

JBPSASW0030	Data for one or more session binding variables couldn't be retrieved.
JBPSASW0031	** the attribute: {0} is not a proper integer. Ignoring
JBPSASW0032	No data found for session binding expression. {0}
JBPSASW0033	Custom handler ({0}) is not of type ServiceInvocationCustomHandler interface. Skipping processing..
JBPSASW0034	Error while processing of custom service invocation handler: {0}
JBPSASW0035	Problem cleaning up resources
JBPSASW0036	Failed to get name for id = {0}. {1}
JBPSASW0037	Unable to send notification. {0}
JBPSASW0038	Failed to get name for id = {0}. {1}
JBPSASW0039	Unable to send notification. {0}
JBPSASW0040	Unable to find pending app owner. {0}
JBPSASW0041	saml2 exception
JBPSPCE0010	Failed to parse search query response.
JBPSPCE0011	Error processing response. {0}

---

JBPSPCE0012	Error invoking SSO protected service
JBPSPCE0013	SOAP message contains multiRef nodes and cannot be converted to JSON. Please use resultFormat=soap header in the request to get native SOAP message.
JBPSPCE0014	SOAP Fault [code: {0}], reason: {1}, detail: {2}
JBPSPCE0015	Detail: {0}
JBPSPCE0016	HTTP Error [ code: {0}, reason: {1} {2} ]
JBPSPCE0017	Unable to connect to SharePoint. {0}
JBPSPCE0018	Unable to connect to SharePoint. {0}
JBPSPCE0019	No server name provided. And failed to select SharePoint connection using url.
JBPSPCE0020	Unrecognized server name, {0}, provided. And failed to select SharePoint connection using url.
JBPSPCE0021	No server name provided. SharePoint connection selection using url not allowed.
JBPSPCE0022	Access credentials for server name, {0}, not found. SharePoint connection selection using url not allowed.
JBPSPCE0023	Unable to connect to SharePoint. {0}
JBPSPCE0024	SharePoint Service Id not recognized, {0}

JBPSPCE0025	Failed to retrieve mashup summary details, {0}
JBPSPCE0026	Service is not a Mashup, {0}
JBPSPCE0027	Mashup id not recognised, {0}
JBPSPCE0028	Failed to getSites for site, {0} : {1}
JBPSPCE0029	Failed to transform getSites response.
JBPSPCE0030	Failed to getSites: {0}
JBPSPCE0031	Failed to transform getSites response.
JBPSPCE0032	Malformed pageUrl, {0}
JBPSPCE0033	Failed to get WebPart Page, {0} : {1}
JBPSPCE0034	Unrecognised WebPart server URL. {0}
JBPSPCE0035	Failed to publish Mashlet WebPart. {0}
JBPSPCE0036	Unable to build WebPart, Server Info not available.
JBPSPCE0037	There are no lists at the selected site. Please select another site.
JBPSPCE0038	Failed to get Lists for site, {0}" : {1}

---

JBPSpCE0039	Failed to transform getLists response for site, {0}
JBPSpCE0040	Failed to get List, site: {0}, list: {1} : {2}
JBPSpCE0041	Failed to transform getList response for site, {0}
JBPSpCE0042	Failed to transform getLists response for site
JBPSpCE0043	Failed to getViews for site, {0} : {1}
JBPSpCE0044	Failed to transform getLists response for site, {0}
JBPSpCE0045	Failed to get list view, site: {0}, list: {1}, view: {2} : {3}
JBPSpCE0046	View contains no Field References
JBPSpCE0047	Failed to transform get list view, site: {0}, list: {1}, view: {2}
JBPSpCE0048	Failed to get List Items for site, {0} : {1}
JBPSpCE0049	Failed to get user info for site, {0}, user, {1} : {2}
JBPSpCE0050	Failed to retrieve list content. {0}
JBPSpCE0051	No Item ID property specified.
JBPSpCE0052	You are not authorized to use SharePoint Search Service.

JBPSPCE0053	Failed to search site: {0}, query: {1}. {2}
JBPSPCE0054	No Item ID property specified.
JBPSPCE0055	Unable to parse response for list item.
JBPSPCE0056	Failed to {0}. ListItem, site: {1}, list: {2}. {3}
JBPSPCE0057	SharePoint site URL not recognised, {0}
JBPSPCE0058	SharePoint Server not configured for user.
JBPSPCE0059	Server endpoint not recognised: {0}
JBPSPCE0060	Unable to identify server: {0}
JBPSPCE0061	Server name not found for server: {0}
JBPSPCE0062	Access failed: {0}
JBPSPCE0063	Failed: {0}
JBPSPCE0064	Invalid server name, {0}
JBPSPCE0065	Server Endpoint, {0} is not valid: {1}
JBPSPCE0066	Invalid site details, siteUrl not defined.

---

<b>JBPSPE0067</b>	<b>Invalid list details, listName not defined.</b>
<b>JBPSPE0068</b>	<b>Invalid page details, pageUrl not defined.</b>
<b>JBPSPE0069</b>	<b>Invalid view details, viewName not defined.</b>
<b>JBPSPE0070</b>	<b>Invalid user info details, username not defined.</b>
<b>JBPSPE0071</b>	<b>Mashzone NextGen Published SharePoint List</b>
<b>JBPSPE0072</b>	<b>Failed to publish SharePoint List as Mashup: {0}</b>
<b>JBPSPE0073</b>	<b>Ignoring unrecognised provider '{0}'</b>
<b>JBPSPE0074</b>	<b>Failed to retrieve List {0}. {1}</b>
<b>JBPSPE0075</b>	<b>Failed to update List {0} {1}</b>
<b>JBPSPE0001</b>	<b>field {0}</b>
<b>JBPSPE0002</b>	<b>Error generating NSD for Mashup Service : {0} - {1}</b>
<b>JBPSPE0003</b>	<b>missing global attr sp-ssoheaders</b>
<b>JBPSPE0004</b>	<b>Unable to retrieve Server Details</b>
<b>JBPSPE0005</b>	<b>Service script not found</b>

- JBPSPE0006**      **Failed to retrieve NSD for service, {0}**
  
- JBPSPE0007**      **failed to find suitable connection name for site url, {0}. {1}**
  
- JBPSPE0008**      **JEMSDesigner.registerService : {0} :: {1}**
  
- JBPSPE0009**      **Error registering Mashup Service : {0}**
  
- JBPSPSHCE0001**    **Unable to put schema to MetaCache.**
  
- JBPSPSHCE0028**    **error: {0}**
  
- JBPSPSHCE0029**    **Formula evaluates to no type: {0}**
  
- JBPSPSHCE0030**    **error: {0}**
  
- JBPSPSHCE0031**    **Formula evaluates to no type: {0}**
  
- JBPSPSHCE0033**    **Sheet name not found, please check spelling: {0}**
  
- JBPSPSHCE0034**    **fail to generate data set from range: {0}**
  
- JBPSPSHCE0039**    **The selected range is not valid: {0}**
  
- JBPSPSHCE0040**    **The page number falls out of the valid number of pages with is: {0}**
  
- JBPSPSHCE0045**    **Sheet name not found, please check spelling: {0}**

---

<b>JBPSPSHCE0050</b>	<b>The index value provided, is expected to be grater than 0: {0}</b>
<b>JBPSPSHCE0051</b>	<b>The index value provided, should be grater than 0 and with no decimal places in it: {0}</b>
<b>JBPSPSHCE0054</b>	<b>The excel file has not been loaded yet</b>
<b>JBPSPSHCE0058</b>	<b>Unable to load the specified content.</b>
<b>JBPSPSHCE0059</b>	<b>Cache with name {0} was not found in Cache Manager, please review the correct spelling of the cache name on the ehcache.xml configuration file.</b>
<b>JBPSPSHCE0061</b>	<b>LoaderGlobalContext singleton has already been created!!</b>
<b>JBPSPSHCE0062</b>	<b>Keystore url may not be null</b>
<b>JBPSPSHCE0063</b>	<b>Keystore may not be null</b>
<b>JBPSPSHCE0064</b>	<b>Unsupported algorithm exception: {0}</b>
<b>JBPSPSHCE0065</b>	<b>Keystore exception: {0}</b>
<b>JBPSPSHCE0066</b>	<b>Key management exception: {0}</b>
<b>JBPSPSHCE0067</b>	<b>I/O error reading keystore/truststore file: {0}</b>
<b>JBPSPSHCE0068</b>	<b>Parameters may not be null</b>
<b>JBPSPSHCE0069</b>	<b>Trust manager may not be null</b>

- JBPSPSHCE0070**    **Invalid excel file URL**
  
- JBPSPSHCE0071**    **no trust manager found**
  
- JBPSPSHCE0073**    **fail to delete file: {0}**
  
- JBPSPSHCE0074**    **The file already exists, try calling replace instead of save.**
  
- JBPSPSHCE0075**    **fail to save file**
  
- JBPSPSHCE0076**    **fail to update file state**
  
- JBPSPSHCE0077**    **Unknown date format**
  
- JBPSPSHCE0078**    **Cannot convert unknown int value**
  
- JBPSPSHCE0079**    **No repository set yet!**
  
- JBPSPSHCE0080**    **Fail to load workbook from excel file.**
  
- JBPSPSHCE0081**    **You cannot replace an unexisting file.**
  
- JBPSPSHCE0082**    **The replacing file and the original should be of the same type.**
  
- JBPSPSHCE0083**    **Column names must be of text type**
  
- JBPSPSHCE0084**    **fail to generate data set from range: {0}! {1}**

---

<b>JBPSPSHE0001</b>	<b>Sheet name not found, please check spelling: {0}</b>
<b>JBPSPSHE0004</b>	<b>fail to generate data set from CSV data: {0}</b>
<b>JBPSPSHE0005</b>	<b>fail parsing range for preview: {0}</b>
<b>JBPSPSHE0006</b>	<b>Sheet name not found, please check spelling: {0}</b>
<b>JBPSPSHE0009</b>	<b>For column with value: {0}</b>
<b>JBPSPSHE0010</b>	<b>fail loading worksheet of type XLS, due to the following exception: {0}</b>
<b>JBPSPSHE0011</b>	<b>fail loading worksheet of type XLSX due to the following exception: {0}</b>
<b>JBPSPSHE0012</b>	<b>fail to load workbook froa stream: {0}</b>
<b>JBPSPSHE0013</b>	<b>fail reading from workbook stream: {0}</b>
<b>JBPSPSHE0014</b>	<b>fail to generate data set from CSV data: {0}</b>
<b>JBPSPSHE0016</b>	<b>file location is not valid: {0}</b>
<b>JBPSPSHE0017</b>	<b>fail reading input file: {0}</b>
<b>JBPSPSHE0018</b>	<b>The file location provided is not valid:{0}</b>
<b>JBPSPSHE0019</b>	<b>fail reading from woorkbook stream: {0}</b>

<b>JBPSPSHE0020</b>	<b>could not find local excel file at {0}</b>
<b>JBPSPSHE0021</b>	<b>Fail selecting current loaded rows from cache due to the following reason: {0}</b>
<b>JBPSPSHE0022</b>	<b>Could not find loader with id: {0} the response is empty!</b>
<b>JBPSPSHE0024</b>	<b>too many files to split</b>
<b>JBPSPSHE0025</b>	<b>fail to loading service cache data: {0}</b>
<b>JBPSPSHE0026</b>	<b>I/O error when loading service cache data: {0}</b>
<b>JBPSPSHE0027</b>	<b>fail to retrieve file from data store</b>
<b>JBPSPSHW0001</b>	<b>while parsing XLSX file within range {0} \${1} : {2}</b>
<b>JBPWSDLCE0043</b>	<b>Keystore url may not be null</b>
<b>JBPWSDLCE0044</b>	<b>Keystore may not be null</b>
<b>JBPWSDLCE0045</b>	<b>Could not find CA Certificate nor Trust Certificate with aliases: {0}, {1}</b>
<b>JBPWSDLCE0046</b>	<b>Unsupported algorithm exception: {0}</b>
<b>JBPWSDLCE0047</b>	<b>Keystore exception: {0}</b>
<b>JBPWSDLCE0048</b>	<b>Key management exception: {0}</b>

---

**JBPWSDLCE0049** I/O error reading keystore/truststore file: {0}

**JBPWSDLCE0050** Paramaters may not be null

**JBPWSDLCE0051** Trust manager may not be null

**JBPWSDLCE0052** Parse XML exception: {0}

**JBPWSDLCE0053** The endpoint reference is not valid: {0}

**JBPWSDLCE0054** No trust manager found

**JBPWSDLCE0055** Parameters may not be null

**JBPWSDLCE0056** HTTP error: {0}

**JBPWSDLCE0057** Request failed.

**JBPWSDLCE0058** Failed to find element: {0}

**JBPWSDLCE0059** Could not find element {0} in part {1}

**JBPWSDLCE0060** Could not find type {0} in part {1}

**JBPWSDLCE0061** BEA X509 Certificate generation fail: {0}

**JBPWSDLCE0062** Invalid message type: {0}

- JBPWSDLCE0063 OASIS X509 Certificate generation fail: {0}
  
- JBPWSDLCE0064 Invalid service/port name, no null values are accepted
  
- JBPWSDLCE0065 The file: {0} was not loaded, ergo is not into the WSDL engine's cache
  
- JBPWSDLE0001 invalid SOAP request file location: {0}
  
- JBPWSDLE0002 fail loading SOAP request file: {0}
  
- JBPWSDLE0003 Http exception: {0}
  
- JBPWSDLE0004 Network exception: {0}
  
- JBPWSDLE0005 Self Signed SSL Http client exception: {0}
  
- JBPWSDLE0006 invalid endpoint reference {0} : {1}
  
- JBPWSDLE0007 Proxy server is not supported with NTLM
  
- JBPWSDLE0008 invalid target service reference {0}
  
- JBPWSDLE0009 Failed to invoke SOAP service
  
- JBPWSDLE0010 Failed to read response on second try with ISO-8859-1. Bailing out...
  
- JBPWSDLE0011 XmlException while parsing response

---

<b>JBPWSDLE0012</b>	<b>No WSDL file has been loaded yet!</b>
<b>JBPWSDLE0013</b>	<b>Error while resetting WSDL endpoint reference: {0}</b>
<b>JBPWSDLE0014</b>	<b>The WSDL at: {0}</b>
<b>JBPWSDLE0015</b>	<b>The WSDL at {0} is not well formed: There is a parser error: {1}</b>
<b>JBPWSDLE0016</b>	<b>The WSDL at: {0} is invalid: {1}</b>
<b>JBPWSDLE0017</b>	<b>The WSDL at: {0} is not recognizable: {1}</b>
<b>JBPWSDLE0018</b>	<b>service '{0}' not found!</b>
<b>JBPWSDLE0019</b>	<b>port '{0}' not found!</b>
<b>JBPWSDLE0020</b>	<b>Service name not found</b>
<b>JBPWSDLE0021</b>	<b>WSDL file: {0} does not have 'SOAP service defined' it lacks of 'Bind' section!</b>
<b>JBPWSDLE0022</b>	<b>No suitable binding/port for SOAP 1.1 or SOAP 1.2 could be found!</b>
<b>JBPWSDLE0023</b>	<b>Fail to retrieve service endpoint!</b>
<b>JBPWSDLE0024</b>	<b>Fail to invoke method 'getLocationURI' to retrieve service endpoint!</b>
<b>JBPWSDLE0025</b>	<b>Fail to access method 'getLocationURI' to retrieve service endpoint!</b>

- JBPWSDLE0026**      **Cannot add imported URL {0} to imported map, caused by {1}**
  
- JBPWSDLE0027**      **Fail loading wsdl through NTLM client: {0}**
  
- JBPWSDLE0028**      **No web proxy supported for NTLM v2 invocations.**
  
- JBPWSDLE0029**      **Fail parsing WSDL url.**
  
- JBPWSDLE0030**      **Fail to read from connection**
  
- JBPWSDLE0031**      **Error in registering service using custom client: {0}**
  
- JBPWSDLE0032**      **Fail reading file {0} caused by {1}**
  
- JBPWSDLE0033**      **Error invoking using secure clients for URL {0} caused by {1}**
  
- JBPWSDLE0034**      **A null Operation object has been provided**
  
- JBPWSDLE0035**      **A null Message Map has been provided**
  
- JBPWSDLE0036**      **No input parameters**
  
- JBPWSDLE0037**      **Fail reading soap fault:{0}**
  
- JBPWSDLE0038**      **Fail parsing soap fault: {0}**
  
- JBPWSDLE0039**      **Error in resolving multiRef links**

- JBPWSDLE0040      Error getting value for multiRef id={0}
- JBPWSDLE0041      Error in parsing given XML response
- JBPWSDLE0042      Error reading XML response
- JBPWSDLW0001      Charset {0} from Content-Type is not supported - using default
- JBPWSDLW0002      No charset detected, defaulting to UTF-8
- JBPWSDLW0004      enable.wSDL.doctype is 'true'. External XML Entity Injection attacks are possible with this option enabled. Use with caution.

MONTHS\_AGO\_COMMENTED – {createdBy} commented on [{artifactName}](#{link} "#{linktitle}") {0} {rating} {1} months ago

{comment}



# 23 Process Engine Messages

---

JL.execution(PRTMessageConstants.AA\_CASE\_CREATE) – {1}, {2}: Created Case with id {0}

JL.execution(PRTMessageConstants.AA\_CASE\_ERROR) – {1}, {2}: Failed to create case: {0}

JL.execution(PRTMessageConstants.AA\_CASE\_RESPONSE) – Received message from AgileApps: {0}

JL.execution(PRTMessageConstants.AA\_CASE\_UNK\_STATUS) – {1}, {2}: Received status from AgileApps: {0}

JL.execution(PRTMessageConstants.AA\_NO\_CASE\_RECORD\_ID) – {0}: Case creation was unsuccessful. AgileApps returned status: {1} and error message: {2}

JL.execution(PRTMessageConstants.AA\_PROCESS\_RESPONSE) – {1}: Sending message to AgileApps: {0}

JL.execution(PRTMessageConstants.AL\_ERRPUB\_OPTIMIZE) – {1}: exception publishing Optimize log event {2}: {0}

JL.execution(PRTMessageConstants.AL\_ERRPUB\_OPTIMIZE\_STEP) – {1}, {2}: exception publishing Optimize log event {3}: {0}

**JL.execution(PRTMessageConstants.AL\_ERR\_GET\_AUDIT\_RUNTIME) – {1}: exception getting audit runtime: {0}**

**JL.execution(PRTMessageConstants.AL\_ERR\_GET\_STACK) – {1}, {2}: exception retrieving process stack: {0}**

**JL.execution(PRTMessageConstants.AL\_NO\_MID\_FOR\_PID) – {1}: exception getting model identifier: {0}**

**JL.execution(PRTMessageConstants.AL\_PIPEERR\_STEP0) – {1}, {2}: exception trying to encode step pipeline: {0}**

**JL.execution(PRTMessageConstants.DUPLICATE\_TASK\_CALLBACK) – {0}, {1}: ignoring duplicate callback from Task Engine for TaskId {2}.**

**JL.execution(PRTMessageConstants.EP\_ERRPUB\_EDA) – {1}, {2}: exception publishing EDA Event: {0}**

**JL.execution(PRTMessageConstants.EP\_PIPEERR0) – {1}, {2}: exception encoding transition pipeline to {3}: {0}**

**JL.execution(PRTMessageConstants.EP\_SENDDTX0) – {0}, {1}: sending live transition to {2}**

**JL.execution(PRTMessageConstants.EP\_SENDDTX0\_DEADPATH) – {0}, {1}: sending dead transition to {2}**

**JL.execution(PRTMessageConstants.EP\_SEND\_PROCESS\_CASE\_CONTROL) – {0}: publishing case control event to AgileApps with control "{1}"**

**JL.execution(PRTMessageConstants.EP\_SEND\_PROCESS\_CHANGE) – {0}: sending process instance change EDA Event: {1}**

**JL.execution(PRTMessageConstants.EP\_SEND\_PROCESS\_ERROR) – {0}: sending process error EDA Event: {1}**

**JL.execution(PRTMessageConstants.EP\_SEND\_PROCESS\_LOG\_CUSTOM\_ID) – {0}: sending process log custom id EDA Event: {1}**

**JL.execution(PRTMessageConstants.EP\_SEND\_PROCESS\_LOG\_MESSAGE) – {0}: sending process log message EDA Event: {1}**

**JL.execution(PRTMessageConstants.EP\_SEND\_PROCESS\_STEP\_CHANGE) – {0}, {1}: sending process step instance change EDA Event: {2}**

**JL.execution(PRTMessageConstants.EP\_SEND\_PROCESS\_STEP\_ERROR) – {0}, {1}: sending process step error EDA Event: {2}**

**JL.execution(PRTMessageConstants.EP\_SEND\_PROCESS\_STEP\_LOOP\_CHANGE) – {0}, {1}: sending process step loop instance change EDA Event: {2}**

**JL.execution(PRTMessageConstants.EP\_SEND\_PROCESS\_STEP\_TRANSITION) – {0}, {1}: sending process step instance transition EDA Event: {2}**

**JL.execution(PRTMessageConstants.IL\_ERR\_CREATE\_LOGGER) – {1}: exception creating instance logger: {0}**

**JL.execution(PRTMessageConstants.IM\_CANCELLEDOK) – {0}, MID={1}, MVer={2}: process cancelled**

**JL.execution(PRTMessageConstants.IM\_CREATEOK) – {0}, MID={1}, MVer={2}: process started**

**JL.execution(PRTMessageConstants.IM\_FAILEDOK) – {0}, MID={1}, MVer={2}: process failed**

**JL.execution(PRTMessageConstants.IM\_FINISHOK) – {0}, MID={1}, MVer={2}: process completed**

JL.execution(PRTMessageConstants.IM\_RECREATE) – {0}, MID={1}, MVer={2}: process restarting

JL.execution(PRTMessageConstants.IM\_SVC\_CANCEL\_TX) – {0}, {1}: transitioning to cancel step

JL.execution(PRTMessageConstants.IM\_TRYCREATE0) – {0}, {1}: new process instance created on {2}

JL.execution(PRTMessageConstants.IM\_TRYCREATE2) – {0}, {1}: using existing pid on {2}

JL.execution(PRTMessageConstants.IM\_UPDATE\_TRACK) – {0}: updated track count by {1} to {2}

JL.execution(PRTMessageConstants.IS\_RETRYLIMIT) – {0}, {1}: step level retry count exceeded for service: {2}

JL.execution(PRTMessageConstants.IS\_SVC\_RETRY) – {1}, {2}: step level retry {3} of {4} in {5} ms: {0}

JL.execution(PRTMessageConstants.IS\_THRESHOLD) – {0}, {1}: thread threshold detected; retry abandoned

JL.execution(PRTMessageConstants.PRT\_EXCEPTION) – Exception: {0}

JL.execution(PRTMessageConstants.SDA\_AFTER\_STEP\_PIPE) – {0}, {1}: after step pipeline: {2}

JL.execution(PRTMessageConstants.SDA\_BEFORE\_STEP\_PIPE) – {0}, {1}: before step pipeline: {2}

JL.execution(PRTMessageConstants.SDA\_BEFORE\_STEP\_PIPE)...0 – {0}, {1}: before step pipeline: {2}

JL.execution(PRTMessageConstants.SDA\_CHANGE\_VERSION) – {0}, {1}: process version changed from {2} to {3}

JL.execution(PRTMessageConstants.SDA\_DEAD\_INGORED) – {0}, {1}: synchronization point ignoring dead path from {2}

JL.execution(PRTMessageConstants.SDA\_DYNAMIC\_CALL\_ACTIVITY\_STARTED) – {0}, {1}: Dynamic call activity step instantiated the following models:{2}

JL.execution(PRTMessageConstants.SDA\_DYNAMIC\_CALL\_ACTIVITY\_STARTED\_MODEL\_NOT\_WAITING) – {0} {1} instance(s) (not waiting for return)

JL.execution(PRTMessageConstants.SDA\_DYNAMIC\_CALL\_ACTIVITY\_STARTED\_MODEL\_WAITING) – {0} {1} instance(s) (waiting for return)

JL.execution(PRTMessageConstants.SDA\_DYNAMIC\_CALL\_ACTIVITY\_WAIT) – {0}, {1}: {2} of {3} callable instances completed

JL.execution(PRTMessageConstants.SDA\_ERR\_GENERAL) – {1}, {2}: exception executing step: {0}

JL.execution(PRTMessageConstants.SDA\_ERR\_HANDLEEVT\_CHANGE) – {1}: exception failing the process: {0}

JL.execution(PRTMessageConstants.SDA\_ERR\_OUT) – {1}, {2}: exception sending output {3} of {4}: {0}

JL.execution(PRTMessageConstants.SDA\_ERR\_SAVECTX) – {1}, {2}: exception saving step context: {0}

JL.execution(PRTMessageConstants.SDA\_ERR\_TX) – {1}, {2}: exception updating track count: {0}

JL.execution(PRTMessageConstants.SDA\_EVAL0) – {0}, {1}: transition condition {2} evaluated to {3}

JL.execution(PRTMessageConstants.SDA\_EVALF) – {0}, {1}: transition condition {2} is False

**JL.execution(PRTMessageConstants.SDA\_EVALT) – {0}, {1}: transition condition {2} is True**

**JL.execution(PRTMessageConstants.SDA\_EXC\_SEND\_DEAD\_PATH) – {1}, {2}: unable to send dead path transition with the following exception: {0}**

**JL.execution(PRTMessageConstants.SDA\_INVALID\_STEP) – {1}, {2}: deprecated step found: {0}**

**JL.execution(PRTMessageConstants.SDA\_LOGCUST) – {0}, {1}: logging custom audit data**

**JL.execution(PRTMessageConstants.SDA\_LOG\_STEP\_INPUT\_DATA) – {0}, {1}: logging step input data**

**JL.execution(PRTMessageConstants.SDA\_LOG\_STEP\_LOOP\_INPUT\_DATA) – {0}, {1}: logging step loop input data**

**JL.execution(PRTMessageConstants.SDA\_LOG\_STEP\_LOOP\_OUTPUT\_DATA) – {0}, {1}: logging step loop output data**

**JL.execution(PRTMessageConstants.SDA\_LOG\_STEP\_OUTPUT\_DATA) – {0}, {1}: logging step output data**

**JL.execution(PRTMessageConstants.SDA\_NOPIPE) – {0}, {1}: step not executed, enqueueing event**

**JL.execution(PRTMessageConstants.SDA\_PROCSTATS) – {0}, {1}: pushing step on suspended list**

**JL.execution(PRTMessageConstants.SDA\_PUBLISH1) – {0}, {1}: published output document {2}**

**JL.execution(PRTMessageConstants.SDA\_RETRIES) – {0}, {1}: step iteration count exceeded**

**JL.execution(PRTMessageConstants.SDA\_SVC) – {0}, {1}: executing {2} in package {3}**

JL.execution(PRTMessageConstants.SDA\_SVC\_ERR\_MSG) – {1}, {2}: exception invoking service {3}: {0}

JL.execution(PRTMessageConstants.SDA\_SVC\_ERR\_TX) – {0}, {1}: transitioning to error step {2}

JL.execution(PRTMessageConstants.SDA\_SVC\_SENDOUT) – {0}, {1}: sent {2} output events

JL.execution(PRTMessageConstants.SDA\_SYNCBEG) – {0}, {1}: start step execution

JL.execution(PRTMessageConstants.SDA\_SYNCEND) – {0}, {1}: end step execution

JL.execution(PRTMessageConstants.SDA\_TDELTA0) – {0}, {1}: no track count change

JL.execution(PRTMessageConstants.SDA\_TXASYNCH) – {0}, {1}: publishing transition to {2} on {3}

JL.execution(PRTMessageConstants.SDA\_TXASYNCH\_DEADPATH) – {0}, {1}: sending Dead Path PTE to {2} on {3}

JL.execution(PRTMessageConstants.SDA\_TXNOCOND) – {0}, {1}: sending dead transition to {2}

JL.execution(PRTMessageConstants.SDA\_TXSEND) – {0}, {1}: sending live transition to {2}

JL.execution(PRTMessageConstants.SDA\_UNABLE\_INVOKE\_ERROR\_STEP\_LOCALLY) – {1}, {2}: unable to invoke error step locally with the following exception: {0}

JL.execution(PRTMessageConstants.SDA\_UNSATISFIED\_JOIN) – {0}, {1}: taking unsatisfied join transition {2}

JL.execution(PRTMessageConstants.SDC\_ABSOLUTE\_TIME\_INVALID) – {0}, {1}: absolute timeout type is invalid

JL.execution(PRTMessageConstants.SDC\_DROPQ0) – {0}, {1}: dropping {2} events

JL.execution(PRTMessageConstants.SDC\_HANDLEJOINTIMER) – {0}, {1}: handling join timeout

JL.execution(PRTMessageConstants.SDC\_HANDLEPROCTIMER) – {0}: handling process timeout

JL.execution(PRTMessageConstants.SDC\_HANDLESTEPTIMER) – {0}, {1}: handling step timeout

JL.execution(PRTMessageConstants.SDC\_JOINTIME) – {0}, {1}: starting join timeout

JL.execution(PRTMessageConstants.SDC\_JOIN\_RSLT) – {0}, {1}: join evaluates to {2}

JL.execution(PRTMessageConstants.SDC\_PROCTIME) – {0}: starting process timeout

JL.execution(PRTMessageConstants.SDC\_QUEUE\_SZ) – {0}, {1}: {2} events in the queue. Event names: {3}. Join string: {4}. Join state: {5}

JL.execution(PRTMessageConstants.SDC\_STEPTIME) – {0}, {1}: starting step timeout

JL.execution(PRTMessageConstants.SDC\_TOHANDLE) – {0}, {1}: transitioning to timeout handler

JL.execution(PRTMessageConstants.SDC\_TOPIPEERR) – {1}, {2}: exception assembling pipeline: {0}

JL.execution(PRTMessageConstants.SD\_ACTIVITY\_NOT\_RUNNING) – {0}, {1}: boundary event {2} ignored because activity is not running

JL.execution(PRTMessageConstants.SD\_CORRELATE) – {0}, {1}: using correlation service {2}

JL.execution(PRTMessageConstants.SD\_CORRELATE\_DISABLED) – {0}, {1}: correlated to disabled model {2} version {3}

JL.execution(PRTMessageConstants.SD\_CORRELATE\_ERR) – {1}, {2}: exception invoking correlation svc {3}: {0}

JL.execution(PRTMessageConstants.SD\_CORRELATE\_FIELD) – {0}, {1}: using correlation field {2}

JL.execution(PRTMessageConstants.SD\_CORRELATE\_NEW) – {0}, {1}: correlated to process id

JL.execution(PRTMessageConstants.SD\_CORRELATE\_TN) – {0}, {1}: correlating to TN conversation id

JL.execution(PRTMessageConstants.SD\_CORRELBADMID) – {0}, {1}: correlated to {2}, expected {3}

JL.execution(PRTMessageConstants.SD\_ERR\_DISPATCH) – {1}, {2}: exception dispatching step: {0}

JL.execution(PRTMessageConstants.SD\_ERR\_HANDLEEVT) – {1}, {2}: exception handling transition event: {0}

JL.execution(PRTMessageConstants.SD\_INPUTMATCH) – {0}, {1}, document {3} is a valid published input

JL.execution(PRTMessageConstants.SD\_INVOKEDISPATCH) – {0}, {1}: dispatching step on new execution thread

JL.execution(PRTMessageConstants.SD\_NOINPUT1) – {0}, {1}: document {3} is NOT a valid published input

JL.execution(PRTMessageConstants.SD\_NOSTEPDEF) – {0}, {1}: no process fragment contains this step

JL.execution(PRTMessageConstants.SD\_PTE) – {0}, {1}: handling transition event from {2}

JL.execution(PRTMessageConstants.SD\_PUBLISH) – {0}, {1}: handling native document {3} on {2}

**JL.execution(PRTMessageConstants.SD\_STARTSTEP) – {0}, {1}: starting step execution**

**JL.execution(PRTMessageConstants.SD\_STEPSYNCH) – {0}, {1}: running step on same execution thread**

**JL.execution(PRTMessageConstants.SM\_ACTDONE) – {0}: process status changed to {1}**

**JL.execution(PRTMessageConstants.SM\_RESTARTPROC) – {0}: restarting process at step {1}**

**JL.execution(PRTMessageConstants.SM\_RESUMEPROC) – {0}: resuming process at {1}**

**JL.execution(PRTMessageConstants.SM\_START) – {0}: processing {1} request**

**JL.execution(PRTMessageConstants.ST\_DB\_CONNECT\_ERR1) – {1}: exception connecting to database: {0}**

**JL.execution(PRTMessageConstants.ST\_DB\_CONNECT\_ERR2) – {1}, {2}: exception connecting to database: {0}**

**JL.execution(PRTMessageConstants.ST\_LOCK\_FAIL) – {0}, {1}: step lock FAILED**

**JL.execution(PRTMessageConstants.ST\_LOCK\_SUCCESS) – {0}, {1}: step locked**

**JL.execution(PRTMessageConstants.ST\_LOCK\_TRY) – {0}, {1}: attempting step lock**

**JL.execution(PRTMessageConstants.TC\_INVOKE\_CONTROL\_TASKS) – {0}: invoking `wm.task.taskclient:controlTasks` with control "{1}"**

**JL.execution(PRTMessageConstants.TC\_INVOKE\_CONTROL\_TASKS\_ERR) – {1}: exception invoking `wm.task.taskclient:controlTasks` service: {0}**

JL.execution(PRTMessageConstants.TN\_ERR\_PROFIELD) – {1}: exception fetching data for field {2}: {0}

JL.execution(PRTMessageConstants.TN\_ERR\_PROSTORE) – {1}: exception fetching data from TN profile store: {0}

JL.execution(PRTMessageConstants.TO\_CANCEL\_JOIN) – {0}, {1}: cancelling join timeout

JL.execution(PRTMessageConstants.TO\_CANCEL\_PROCESS) – {0}: cancelling process timeout

JL.execution(PRTMessageConstants.TO\_CANCEL\_STEP) – {0}, {1}: cancelling step timeout

JL.execution(PRTMessageConstants.TO\_ERR\_INVOKE) – {1}, {2}: exception invoking timeout: {0}

JL.execution(PRTMessageConstants.TO\_KILLSTEPTHR) – {0}, {1}: killing step execution thread

JL.execution(PRTMessageConstants.TO\_MISSING\_JOIN\_TIMER\_TYPE) – {0}, {1}: cannot start Join timeout -- type not specified

JL.execution(PRTMessageConstants.TO\_MISSING\_PROCESS\_TIMER\_TYPE) – {0}: cannot start Process timeout -- type not specified

JL.execution(PRTMessageConstants.TO\_MISSING\_STEP\_TIMER\_TYPE) – {0}, {1}: cannot start Step timeout -- type not specified

JL.execution(PRTMessageConstants.TO\_NO\_TRANSITION) – {1}, {2}: no transition to handle timeout: {0}

JL.execution(PRTMessageConstants.TO\_STRT\_NO\_DURATION) – {0}, {1}: did not start timer, no end time specified.

JL.execution(PRTMessageConstants.TO\_STRT\_TIMER) – {0}, {1}: starting timeout: {2}

JL.execution(PRTMessageConstants.TO\_TIMEOUT\_JOIN) – {0}, {1}: join timer has expired

JL.execution(PRTMessageConstants.TO\_TIMEOUT\_PROCESS) – {0}: process timer has expired

JL.execution(PRTMessageConstants.TO\_TIMEOUT\_STEP) – {0}, {1}: step timer has expired

JL.general(PRTMessageConstants.ADM\_BPM\_ONLY\_USAGE) – This service cannot be invoked outside of an executing Business Process instance.

JL.general(PRTMessageConstants.ADM\_MWS\_INIT\_ERROR) – Unable to initialize MWS library. Business calendar based timeouts will not be able to be evaluated.

JL.general(PRTMessageConstants.ADM\_MWS\_INIT\_ERROR2) – Exception trying to initialize MWS library: {0}

JL.general(PRTMessageConstants.ADM\_MWS\_INIT\_ERROR\_GET\_POOL) – Error trying to get JDBC pool configuration using functional alias {0}. Business calendar based timeouts will not be able to be evaluated.

JL.general(PRTMessageConstants.ADM\_MWS\_INIT\_ERROR\_GET\_POOL2) – Exception trying to get JDBC pool configuration: {0}

JL.general(PRTMessageConstants.AL\_CANTPOP) – Exception trying to pop audit log context: {0}

JL.general(PRTMessageConstants.AL\_CANTPUSH) – Exception trying to push audit log context: {0}

JL.general(PRTMessageConstants.AL\_CUSTNOT) – Custom logging: cannot convert {0} to logging type {1} (value {2})

JL.general(PRTMessageConstants.AL\_CUSTNOU0) – Custom logging: cannot find value for {0}.{1} on path {2}

JL.general(PRTMessageConstants.AL\_ERRPUB1) – Exception publishing Audit Log Event {1}: {0}

JL.general(PRTMessageConstants.AL\_ERRPUB\_OPTIMIZE) – Exception publishing Optimize Log Event {1}: {0}

JL.general(PRTMessageConstants.AL\_ERR\_GET\_AUDIT\_RUNTIME2) – Exception getting audit runtime: {0}

JL.general(PRTMessageConstants.AL\_ERR\_LOG) – Exception logging audit entry: {0}

JL.general(PRTMessageConstants.AL\_ERR\_REG\_LOGGER) – Exception registering Process Logger: {0}

JL.general(PRTMessageConstants.AL\_FAILED\_AUDIT\_CACHE\_ADD) – Adding audit entry to failed process audit cache: {0}

JL.general(PRTMessageConstants.AL\_FAILED\_AUDIT\_CACHE\_ADD\_ERR) – Could not add audit entry to failed process audit cache: {0}

JL.general(PRTMessageConstants.AL\_FAILED\_AUDIT\_CACHE\_EMPTY) – All entries in the failed audit cache have been stored in the process audit database

JL.general(PRTMessageConstants.AL\_FAILED\_AUDIT\_CACHE\_STORED) – Stored {0} entries from the failed audit cache in the process audit database

JL.general(PRTMessageConstants.AL\_FAILED\_AUDIT\_CACHE\_STORE\_ERR) – Exception when trying to store entries from the failed audit cache in the process audit database: {0}

JL.general(PRTMessageConstants.AL\_NO\_MID\_FOR\_PID) – {1}: exception getting model identifier: {0}

**JL.general(PRTMessageConstants.AL\_PIPEERR\_STEP0) – Exception trying to encode step pipeline for {1}: {0}**

**JL.general(PRTMessageConstants.BT\_CFG\_ERROR) – [MID={1}] Problem reading BrainTribe config file: "{2}". {0}**

**JL.general(PRTMessageConstants.DASHBOARD) – Dashboard**

**JL.general(PRTMessageConstants.DASHBOARD\_DIAGNOSTIC) – Diagnostic**

**JL.general(PRTMessageConstants.DASHBOARD\_ENVIRONMENT) – Environment**

**JL.general(PRTMessageConstants.DASHBOARD\_ENV\_AUDIT\_SETTINGS) – Audit Logging Settings**

**JL.general(PRTMessageConstants.DASHBOARD\_ENV\_CONTROL\_TRIGGER) – Standard Control Triggers**

**JL.general(PRTMessageConstants.DASHBOARD\_ENV\_CR) – Content Repository View**

**JL.general(PRTMessageConstants.DASHBOARD\_ENV\_JDBC) – JDBC Connections**

**JL.general(PRTMessageConstants.DASHBOARD\_ENV\_JMS\_TRIGGER) – JMS Control Trigger**

**JL.general(PRTMessageConstants.DASHBOARD\_ENV\_SETTINGS) – Process Engine Settings**

**JL.general(PRTMessageConstants.DASHBOARD\_HEALTH\_AUDITLOG) – Audit Logging Status**

**JL.general(PRTMessageConstants.DASHBOARD\_HEALTH\_AUDIT\_LOGGING) – Audit Logging**

**JL.general(PRTMessageConstants.DASHBOARD\_HEALTH\_BROKER\_PUSH) – Broker Push**

**JL.general(PRTMessageConstants.DASHBOARD\_HEALTH\_BUSINESS\_CALENDAR) – Business Calendars**

**JL.general(PRTMessageConstants.DASHBOARD\_HEALTH\_BUSINESS\_CALENDARS) – Business Calendars**

**JL.general(PRTMessageConstants.DASHBOARD\_HEALTH\_CHECK) – Health Check**

**JL.general(PRTMessageConstants.DASHBOARD\_HEALTH\_CONTROL) – Control Triggers**

**JL.general(PRTMessageConstants.DASHBOARD\_HEALTH\_DBMS) – DBMS Status**

**JL.general(PRTMessageConstants.DASHBOARD\_HEALTH\_DB\_SCHEMA) – Database Schema Compatibility**

**JL.general(PRTMessageConstants.DASHBOARD\_HEALTH\_EFORM\_LISTENER) – E-form Listener**

**JL.general(PRTMessageConstants.DASHBOARD\_HEALTH\_JMS) – JMS Control Status**

**JL.general(PRTMessageConstants.DASHBOARD\_HEALTH\_JMS\_MSG) – JMS**

**JL.general(PRTMessageConstants.DASHBOARD\_HEALTH\_MESSAGING\_PUSH) – webMethods Messaging Push**

**JL.general(PRTMessageConstants.DASHBOARD\_HEALTH\_OPTIMIZE) – Optimize Subsystem**

**JL.general(PRTMessageConstants.DASHBOARD\_HEALTH\_OPTIMIZE\_MSG) – Optimize Logging**

JL.general(PRTMessageConstants.DASHBOARD\_HEALTH\_PA\_DB) – Process Auditing

JL.general(PRTMessageConstants.DASHBOARD\_HEALTH\_PE\_DB) – Process Engine Database

JL.general(PRTMessageConstants.DASHBOARD\_HEALTH\_RESTART\_TIMERS) – Restart Timers

JL.general(PRTMessageConstants.DASHBOARD\_HEALTH\_STARTUP\_MESSAGES) – Startup Messages

JL.general(PRTMessageConstants.DASHBOARD\_HEALTH\_STORAGE) – Storage

JL.general(PRTMessageConstants.DASHBOARD\_PROCESS) – Process

JL.general(PRTMessageConstants.DASHBOARD\_PROCESS)...0 – Process Engine

JL.general(PRTMessageConstants.DASHBOARD\_PROCESSLOG\_ALL\_EVENTS) – 5 - Process and All Events and Activities

JL.general(PRTMessageConstants.DASHBOARD\_PROCESSLOG\_ERRORS) – 2 - Errors only

JL.general(PRTMessageConstants.DASHBOARD\_PROCESSLOG\_NONE) – 1 - None

JL.general(PRTMessageConstants.DASHBOARD\_PROCESSLOG\_PROCESS) – 3 - Process only

JL.general(PRTMessageConstants.DASHBOARD\_PROCESSLOG\_START) – 4 - Process and Start Events

JL.general(PRTMessageConstants.DASHBOARD\_PROCESSLOG\_UNKNOWN) – Unknown

JL.general(PRTMessageConstants.DASHBOARD\_PROCESS\_AUDIT\_ASYNC) – Asynchronous

JL.general(PRTMessageConstants.DASHBOARD\_PROCESS\_AUDIT\_DB) – Database

JL.general(PRTMessageConstants.DASHBOARD\_PROCESS\_AUDIT\_FILE) – File

JL.general(PRTMessageConstants.DASHBOARD\_PROCESS\_AUDIT\_SYNC) – Synchronous

JL.general(PRTMessageConstants.DASHBOARD\_PROCESS\_SETTINGS) – Settings

JL.general(PRTMessageConstants.DASHBOARD\_RESTART\_EFORM\_FAIL) – Failed to restart e-form listener for {0}.

JL.general(PRTMessageConstants.DASHBOARD\_RESTART\_EFORM\_SUCCESS) – Restart of e-form listener: {0} successful.

JL.general(PRTMessageConstants.DASHBOARD\_STATUS\_NO) – No

JL.general(PRTMessageConstants.DASHBOARD\_STATUS\_SUSPENDED) – Suspended

JL.general(PRTMessageConstants.DASHBOARD\_STATUS\_YES) – Yes

JL.general(PRTMessageConstants.DUP\_CHK\_BEGIN) – CheckDuplicates processing {0}, uuid, {1}

JL.general(PRTMessageConstants.DUP\_CHK\_END) – CheckDuplicates processed {0}, uuid, {1}, status, {2}

JL.general(PRTMessageConstants.DUP\_CHK\_ISEXP) – CheckDuplicates throwing ISRuntimeException {0}, uuid, {1}

JL.general(PRTMessageConstants.EF\_CFG\_ERROR) – [MID={1}] Problem reading E-form config file: "{2}". {0}

JL.general(PRTMessageConstants.EF\_LISTENER\_ADDED) – [MID={0}] Now listening to path: "{1}" for e-Forms on jcr "{2}"

JL.general(PRTMessageConstants.EF\_LISTENER\_ADD\_ERROR) – [MID={1}] Error adding listener to Content Repository "{2}". {0}

JL.general(PRTMessageConstants.EF\_LISTENER\_ALREADY\_EXISTS) – [MID={0}] Content Repository currently has a listener listening in that location. No new listener added to listening path: "{1}" for e-Forms on jcr "{2}".

JL.general(PRTMessageConstants.EF\_LISTENER\_CHANGE\_NOTALLOWED) – [MID={0}] Unable to change listener please disable all other models currently using this listener: "{1}"

JL.general(PRTMessageConstants.EF\_LISTENER\_DOCNOTFOUND) – [MID={0}] Cannot start e-form process because doc type: "{1}" does not exist. For e-form instance at: "{2}". Please recreate the e-form doc or rebuild the model(s).

JL.general(PRTMessageConstants.EF\_LISTENER\_ERROR) – [MID={1}] Error with Content Repository "{2}". Check if the repo is running, login credentials and repo connection information is correct. {0}

JL.general(PRTMessageConstants.EF\_LISTENER\_FIRED) – [MID={0}] Trying to publish E-form instance "{1}" for template "{2}". With doc type of "{3}". If process does not start please check error log for any pub.publish errors. IData:{4}

JL.general(PRTMessageConstants.EF\_LISTENER\_FIRED)...0 – [MID={0}] Trying to publish E-form instance "{1}" for template "{2}". With doc type of "{3}". If process does not start please check error log for any pub.publish errors. IData:{4}

JL.general(PRTMessageConstants.EF\_LISTENER\_NOTCONFIGURED) – [MID={0}] Content Repository "{1}" not configured.

JL.general(PRTMessageConstants.EF\_LISTENER\_NO\_DOCS) – Content Repository currently has no models associated to it. No reason to restart the repository at this time.

JL.general(PRTMessageConstants.EF\_LISTENER\_PORTS\_NOTADDED) – [MID={0}] Cannot edit access for PORT 15006. Please ensure to manually add access for "wm.prt.eforms:update" "wm.server:connect" "wm.server:disconnect" "wm.server:ping".

JL.general(PRTMessageConstants.EF\_LISTENER\_REMOVED) – [MID={0}] Listener for e-Forms at path: "{1}" has been disabled from jcr "{2}"

JL.general(PRTMessageConstants.EF\_LISTENER\_REMOVE\_ERROR) – [MID={1}] Error disabling/removing listener from Content Repository "{2}". {0}

JL.general(PRTMessageConstants.EF\_LISTENER\_RESTART\_ERROR) – [MID={1}] Error restarting listener(s) to Content Repository "{2}". {0}

JL.general(PRTMessageConstants.EF\_LISTENER\_RESTART\_MODEL\_NOTENABLED) – No model(s) enabled using this listener "{0}". Listener will not be restarted.

JL.general(PRTMessageConstants.EF\_METHOD\_SUCCEEDED) – The method succeeded.

JL.general(PRTMessageConstants.EF\_PASS\_ERROR) – [MID={1}] Cannot retrieve password: "{2}". {0}

JL.general(PRTMessageConstants.EF\_PUBLISH\_COULD\_NOT\_CREATE\_DOC) – Could not create the IS document type "{0}" from e-form instance "{1}"; make sure the e-form instance contents matches the IS document type.

JL.general(PRTMessageConstants.EF\_PUBLISH\_DOCNOTFOUND) – Cannot publish the e-form as an IS document because the IS document type "{0}" does not exist. Please create the IS document type from your e-form template.

JL.general(PRTMessageConstants.EF\_PUBLISH\_DOC\_PUBLISH\_FAILED) – Error publishing e-form instance: {0}

JL.general(PRTMessageConstants.EF\_PUBLISH\_FILENOTFOUND) – Cannot publish the e-form as an IS document because the e-form instance file "{0}" does not exist.

**JL.general(PRTMessageConstants.EF\_PUBLISH\_INPUTS\_NOT\_PROVIDED)** – The required input values were not provided; for this service though some inputs are optional you must provide either (instanceName and instanceByteStream) or (instanceFilePath). If both sets are provided, then (instanceName and instanceByteStream), takes precedence.

**JL.general(PRTMessageConstants.EF\_PUBLISH\_PUBLISH\_ATTEMPT)** – Trying to publish e-form instance "{0}" as IS document type "{1}". If any associated processes do not start, then please check the error log for any pub.publish:publish errors.

**JL.general(PRTMessageConstants.EF\_PUBLISH\_TEMPLATE\_NOT\_PROVIDED)** – The required input value, templateName, was not provided.

**JL.general(PRTMessageConstants.EP\_PIPEERR0)** – Exception encoding transition pipeline: {0}

**JL.general(PRTMessageConstants.EP\_SENDERR)** – Exception during send: {0}

**JL.general(PRTMessageConstants.HEALTHCHECK\_AUDITLOG\_DB\_RED)** – Process audit database could not be accessed

**JL.general(PRTMessageConstants.HEALTHCHECK\_AUDITLOG\_INIT\_RED)** – Error initializing audit logging

**JL.general(PRTMessageConstants.HEALTHCHECK\_AUDITLOG\_RED)** – Process Logger is either not enabled or not configured for the database

**JL.general(PRTMessageConstants.HEALTHCHECK\_BC\_RED)** – MWS library is not initialized

**JL.general(PRTMessageConstants.HEALTHCHECK\_BC\_YELLOW)** – JDBC pool functional alias "CentralUsers" is not configured

**JL.general(PRTMessageConstants.HEALTHCHECK\_BROKER\_RED)** – ControlTrigger is not enabled

**JL.general(PRTMessageConstants.HEALTHCHECK\_BROKER\_YELLOW) – Broker is not configured**

**JL.general(PRTMessageConstants.HEALTHCHECK\_JMS\_RED) – JMSControlTrigger is not enabled**

**JL.general(PRTMessageConstants.HEALTHCHECK\_MESSAGING\_YELLOW) – webMethods Messaging is not configured**

**JL.general(PRTMessageConstants.HEALTHCHECK\_OPTIMIZE\_NOT\_CONFIGURED) – JMS Server URL is not configured**

**JL.general(PRTMessageConstants.HEALTHCHECK\_OPTIMIZE\_NOT\_INIT) – Unable to initialize Optimize interface**

**JL.general(PRTMessageConstants.HEALTHCHECK\_PADB\_RED) – Process audit database could not be accessed**

**JL.general(PRTMessageConstants.HEALTHCHECK\_PADB\_VERSION\_RED) – Process audit database schema version is incorrect. Minimum version expected is {0}, actual version is {1}.**

**JL.general(PRTMessageConstants.HEALTHCHECK\_PA\_FAILED\_AUDIT\_CACHE\_NOT\_EMPTY\_RED) – Failed process audit cache contains records that need to be inserted into the process audit database**

**JL.general(PRTMessageConstants.HEALTHCHECK\_PA\_FAILED\_AUDIT\_CACHE\_NO\_EXIST\_RED) – Failed process audit cache does not exist**

**JL.general(PRTMessageConstants.HEALTHCHECK\_PEDB\_RED) – Process engine database could not be accessed**

**JL.general(PRTMessageConstants.HEALTHCHECK\_PEDB\_VERSION\_RED) – Process engine database schema version is incorrect. Minimum version expected is {0}, actual version is {1}.**

JL.general(PRTMessageConstants.HEALTHCHECK\_TRIGGER\_RED) – Trigger {0} is not enabled.

JL.general(PRTMessageConstants.IL\_ERR\_CREATE\_LOGGER) – Exception creating instance logger: {0}

JL.general(PRTMessageConstants.IL\_ERR\_LOG\_ENABLED) – Exception determining if model is enabled for instance logging: {0}

JL.general(PRTMessageConstants.IM\_CLEANUPEVERY) – Cache cleanup running every {0} seconds and every {1} instances

JL.general(PRTMessageConstants.IM\_MODINACTIVE0) – Warning. Process model {0} is inactive

JL.general(PRTMessageConstants.IM\_MODINACTIVE1) – Cannot suspend/resume {0}. Fragment for model {1} is missing

JL.general(PRTMessageConstants.IM\_NOCLEANUP) – Instance cleanup disabled.

JL.general(PRTMessageConstants.IS\_RETRYLIMIT) – Step Level Retry count exceeded for service: {0}

JL.general(PRTMessageConstants.IS\_SVC\_RETRY) – Exception: {0}. Step Level Retry configured for service: {1}. Retry {2} of {3} in {4} ms

JL.general(PRTMessageConstants.IS\_THRESHOLD) – Thread Threshold detected. Retry abandoned for {0}.

JL.general(PRTMessageConstants.JMS\_ALIAS\_ERROR) – JMS Connection Alias for PE 'PE\_NONTRANSACTIONAL\_ALIAS' has not been configured.

JL.general(PRTMessageConstants.JMS\_CREATE\_CONNECTION\_ERROR) – Error creating JMS connection alias: {0}

**JL.general(PRTMessageConstants.JMS\_CREATE\_TOPIC\_ERROR) – Error creating PE internal JMS topic: {0}**

**JL.general(PRTMessageConstants.JMS\_UPDATE\_CG\_PERMISSIONS\_ERROR) – Error updating client group permissions: {0}**

**JL.general(PRTMessageConstants.MM\_BADFRAGERR) – Exception loading model fragment {1}: {0}**

**JL.general(PRTMessageConstants.MM\_CANTMAKEDIR) – Unable to create directory: {0}**

**JL.general(PRTMessageConstants.MM\_DELETING) – Deleting {0} old fragments from {1}**

**JL.general(PRTMessageConstants.MM\_DELFILE) – Deleting XML file {0}**

**JL.general(PRTMessageConstants.MM\_DELFRAG) – Deleting model fragment: {0}**

**JL.general(PRTMessageConstants.MM\_FILEERR) – Exception reading fragment file {1}: {0}**

**JL.general(PRTMessageConstants.MM\_NEWFRAG) – Adding new process fragment (pkg={0}, file={1})**

**JL.general(PRTMessageConstants.MM\_READMOD) – Loading model fragment {0}**

**JL.general(PRTMessageConstants.MM\_READPKG) – Loading process models in package {0}**

**JL.general(PRTMessageConstants.MON\_INVALID\_ENABLE\_RESUBMISSION) – Enable Resubmission value must be either "True" or "False"**

**JL.general(PRTMessageConstants.MON\_INVALID\_LOGGING\_LEVEL) – Invalid Logging Level**

**JL.general(PRTMessageConstants.MON\_INVALID\_LOG\_TRANSITIONS) – Log Transitions value must be either "True" or "False"**

**JL.general(PRTMessageConstants.MON\_INVALID\_MODEL) – [MID={0}, MVers={1}] Model does not exist.**

**JL.general(PRTMessageConstants.MON\_INVALID\_PID) – Process instance {0} is not running or does not exist.**

**JL.general(PRTMessageConstants.MON\_LOGGING\_LEVEL\_TOO\_LOW) – [MID={0}] Logging level for Model cannot be set below minimum value of {1}.**

**JL.general(PRTMessageConstants.MON\_OLD\_MODEL\_VERSION) – [MID={0}] QoS cannot be changed because it was generated from a pre-7.0 version of Modeler.**

**JL.general(PRTMessageConstants.OL\_OPTIMIZE\_INIT\_ERROR) – Unable to get Optimize process data collector. Tracking enabled models will not be logged to Optimize.**

**JL.general(PRTMessageConstants.OL\_OPTIMIZE\_INIT\_ERROR2) – Exception trying to get Optimize process data collector: {0}**

**JL.general(PRTMessageConstants.OL\_OPTIMIZE\_SHUTDOWN\_ERROR) – Exception trying to shut down Optimize data collector: {0}**

**JL.general(PRTMessageConstants.PRT\_EXCEPTION) – Exception: {0}**

**JL.general(PRTMessageConstants.PRT\_MESSAGE) – {0}**

**JL.general(PRTMessageConstants.REPO\_DEFAULT\_ROOT\_PATH) – (optional)**

**JL.general(PRTMessageConstants.REPO\_EXE) – A RepositoryException occurred while trying to read data from the Content Repository: "{0}"**

---

JL.general(PRTMessageConstants.REPO\_FILE\_DOES\_NOT\_EXIST) – File does not exist in repository

JL.general(PRTMessageConstants.REPO\_IO\_EXE) – An IOException occurred while trying to read data from the Content Repository: "{0}"

JL.general(PRTMessageConstants.REPO\_PATH\_NOT\_FOUND\_EXE) – A PathNotFoundException occurred while trying to read data from the Content Repository: "{0}"

JL.general(PRTMessageConstants.REPO\_READ\_NODE\_ERROR) – An exception occurred while trying to read data from the Content Repository at: "{0}". Please check log for details.

JL.general(PRTMessageConstants.SDA\_ERR\_GENERAL) – Exception executing step {1}, {2}: {0}

JL.general(PRTMessageConstants.SDA\_ERR\_HANDLEEVT\_CHANGE) – Exception trying to fail the process \*{1}: {0}

JL.general(PRTMessageConstants.SDA\_ERR\_OUT) – Exception sending output {1} of {2} for PID {3} SID {4}: {0}

JL.general(PRTMessageConstants.SDA\_ERR\_SAVECTX) – Exception saving step context {1}, {2}: {0}

JL.general(PRTMessageConstants.SDA\_ERR\_TX) – Exception updating track count {1}, {2}: {0}

JL.general(PRTMessageConstants.SDA\_INVALID\_STEP) – Exception: Deprecated step found {1}, {2}: {0}

JL.general(PRTMessageConstants.SDA\_SVC\_ERR\_MSG) – Exception invoking service {1}, {2}, Svc={3}: {0}

JL.general(PRTMessageConstants.SDC\_TOPIPEERR) – Exception assembling pipeline {1}, {2}: {0}

JL.general(PRTMessageConstants.SD\_CORRELATE\_ERR) – Error invoking correlation svc {1}: {0}

JL.general(PRTMessageConstants.SD\_ERR\_DISPATCH) – Exception dispatching step: {0}

JL.general(PRTMessageConstants.SD\_ERR\_HANDLEEVT) – Exception handling transition event: {0}

JL.general(PRTMessageConstants.SD\_INPUTMATCH) – Document {0} is a valid published input

JL.general(PRTMessageConstants.SD\_NOINPUT1) – Document {0} is NOT a valid published input

JL.general(PRTMessageConstants.SD\_NOSTEP1) – Document {2} does not match to any step in process {0} on {1}

JL.general(PRTMessageConstants.SD\_PUBLISH) – Handling native document {0} on {1}

JL.general(PRTMessageConstants.SD\_STEPMATCH) – Document {2} matches step in process {0} on {1}

JL.general(PRTMessageConstants.SM\_BAD\_ACTION) – {0} is not a valid Action.

JL.general(PRTMessageConstants.ST\_CACHE\_CONNECT\_ERR) – Exception: Unable to connect to cache!

JL.general(PRTMessageConstants.ST\_CACHE\_MGR\_NOT\_INITIALIZED) – Could not initialize cache manager

JL.general(PRTMessageConstants.ST\_CACHE\_NOT\_INITIALIZED) – Could not initialize cache: {0}

JL.general(PRTMessageConstants.ST\_CLEAN\_DURATION) – Storage cleaner: Duration {0} ms

**JL.general(PRTMessageConstants.ST\_CLEAN\_EVERY) – Storage cleaner: will run every {0} seconds**

**JL.general(PRTMessageConstants.ST\_CLEAN\_JDBC) – Storage cleaner: executing embedded SQL**

**JL.general(PRTMessageConstants.ST\_CLEAN\_PROC) – Storage cleaner: executing stored procedure**

**JL.general(PRTMessageConstants.ST\_DB\_CONNECT\_ERR) – Exception: Unable to connect to database!**

**JL.general(PRTMessageConstants.ST\_DB\_ERR) – Storage exception: {0}**

**JL.general(PRTMessageConstants.ST\_FAILED\_PROC\_EXPIRE) – Storage cleaner: expiration for failed processes: {0} seconds**

**JL.general(PRTMessageConstants.ST\_LOCK\_INSERT\_FAIL) – Failed to insert Lock ID: {0} -- attempt {1} of {2}**

**JL.general(PRTMessageConstants.ST\_NO\_CLEAN) – Storage cleaner: Disabled**

**JL.general(PRTMessageConstants.ST\_NO\_CLEAN\_FAILED\_PROC) – Storage cleaner: clean up for completed processes is disabled**

**JL.general(PRTMessageConstants.ST\_NO\_LOCK) – Storage cleaner: cannot acquire lock. Exception: {0}**

**JL.general(PRTMessageConstants.ST\_PROC\_EXPIRE) – Storage cleaner: expiration for completed processes: {0} seconds**

**JL.general(PRTMessageConstants.TM\_DFLTSPORT) – Default PE transport is {0}**

**JL.general(PRTMessageConstants.TM\_DFLTSPORT\_DEF) – Default PE transport is {0}; deferred**

**JL.general(PRTMessageConstants.TM\_PUSH\_ATTEMPT) – Pushing doctypes to webMethods Messaging**

**JL.general(PRTMessageConstants.TM\_PUSH\_ERROR) – webMethods Messaging push error: {0}**

**JL.general(PRTMessageConstants.TM\_PUSH\_NOCONN) – Not performing webMethods Messaging push (not connected)**

**JL.general(PRTMessageConstants.TM\_SEND) – Sending {2} over {0} to {1}**

**JL.general(PRTMessageConstants.TM\_SENDABBR) – Sending {1} over {0}**

**JL.general(PRTMessageConstants.TN\_DISPATCH0) – DocID={0}, DocType={1}, ConvId={2}: processing incoming TN document**

**JL.general(PRTMessageConstants.TN\_ERR\_BADFILTER) – Exception evaluating TN document filter: {0}**

**JL.general(PRTMessageConstants.TN\_ERR\_PROFIELD) – Exception fetching data for field {1}: {0}**

**JL.general(PRTMessageConstants.TN\_ERR\_PROSTORE) – Exception fetching data from TN profile store: {0}**

**JL.general(PRTMessageConstants.TN\_NOMATCH) – DocID={0}, DocType={1}, ConvId={2}: no Model match for TN document**

**JL.general(PRTMessageConstants.TN\_NOSTEPMATCH) – DocID={0}, DocType={1}, ConvId={2}, MID={3}: no Step match for TN document**

**JL.general(PRTMessageConstants.TN\_STARTORJOIN) – ConvId={0}, PID={1}: starting/joining TN process**

**JL.general(PRTMessageConstants.TOU\_INVALID\_BIZ\_CAL\_ALIAS) – Business calendar alias {0} does not exist**

**JL.general(PRTMessageConstants.TOU\_INVALID\_BIZ\_CAL\_EVALUATOR) – Business calendar evaluator does not exist**

**JL.general(PRTMessageConstants.TOU\_INVALID\_BIZ\_TIMEOUT) – Business timeout is invalid: {0}**

**JL.general(PRTMessageConstants.TO\_ERR\_INVOKE) – Exception invoking timeout for {1}, {2}: {0}**

**JL.general(PRTMessageConstants.TO\_TIMER\_THREAD\_INTERRUPTED) – Timer thread interrupted: {0}**

**JL.string(PRTMessageConstants.BT\_CFG\_ERROR) – [MID={1}] Problem reading BrainTribe config file: "{2}". {0}**

**JL.string(PRTMessageConstants.DASHBOARD\_PROCESSLOG\_ALL\_EVENTS) – 5 - Process and All Events and Activities**

**JL.string(PRTMessageConstants.EF\_METHOD\_SUCCEEDED) – The method succeeded.**

**JL.string(PRTMessageConstants.EF\_PUBLISH\_COULD\_NOT\_CREATE\_DOC) – Could not create the IS document type "{0}" from e-form instance "{1}"; make sure the e-form instance contents matches the IS document type.**

**JL.string(PRTMessageConstants.EF\_PUBLISH\_DOCNOTFOUND) – Cannot publish the e-form as an IS document because the IS document type "{0}" does not exist. Please create the IS document type from your e-form template.**

**JL.string(PRTMessageConstants.EF\_PUBLISH\_DOC\_PUBLISH\_FAILED) – Error publishing e-form instance: {0}**

**JL.string(PRTMessageConstants.EF\_PUBLISH\_FILENOTFOUND)** – Cannot publish the e-form as an IS document because the e-form instance file "{0}" does not exist.

**JL.string(PRTMessageConstants.EF\_PUBLISH\_INPUTS\_NOT\_PROVIDED)** – The required input values were not provided; for this service though some inputs are optional you must provide either (instanceName and instanceByteStream) or (instanceFilePath). If both sets are provided, then (instanceName and instanceByteStream), takes precedence.

**JL.string(PRTMessageConstants.EF\_PUBLISH\_PUBLISH\_ATTEMPT)** – Trying to publish e-form instance "{0}" as IS document type "{1}". If any associated processes do not start, then please check the error log for any pub.publish:publish errors.

**JL.string(PRTMessageConstants.EF\_PUBLISH\_TEMPLATE\_NOT\_PROVIDED)** – The required input value, templateName, was not provided.

**JL.string(PRTMessageConstants.HEALTHCHECK\_PADB\_VERSION\_RED)** – Process audit database schema version is incorrect. Minimum version expected is {0}, actual version is {1}.

**JL.string(PRTMessageConstants.HEALTHCHECK\_PEDB\_VERSION\_RED)** – Process engine database schema version is incorrect. Minimum version expected is {0}, actual version is {1}.

**JL.string(PRTMessageConstants.IM\_CANCELLEDOK)** – \*PID={0}, MID={1}, MVer={2}; process cancelled

**JL.string(PRTMessageConstants.IM\_FAILEDOK)** – \*PID={0}, MID={1}, MVer={2}; process failed

**JL.string(PRTMessageConstants.IM\_UPDATE\_TRACK)** – \*{0}, {1}: updated track count by {2} to {3}

**JL.string(PRTMessageConstants.REPO\_DEFAULT\_ROOT\_PATH)** – (optional)

**JL.string(PRTMessageConstants.REPO\_EXE)** – A RepositoryException occurred while trying to read data from the Content Repository: "{0}"

**JL.string(PRTMessageConstants.REPO\_FILE\_DOES\_NOT\_EXIST) – File does not exist in repository**

**JL.string(PRTMessageConstants.REPO\_IO\_EXE) – An IOException occurred while trying to read data from the Content Repository: "{0}"**

**JL.string(PRTMessageConstants.REPO\_PATH\_NOT\_FOUND\_EXE) – A PathNotFoundException occurred while trying to read data from the Content Repository: "{0}"**

**JL.string(PRTMessageConstants.REPO\_READ\_NODE\_ERROR) – An exception occurred while trying to read data from the Content Repository at: "{0}". Please check log for details.**

**JL.string(PRTMessageConstants.RULE\_SVC\_PIPEI) – Prepared pipeline to invoke Rule as: "{0}"**

**JL.string(PRTMessageConstants.SDA\_BEFORE\_STEP\_PIPE) – \*{0}, {1}: after step pipeline: {2}**

**JL.string(PRTMessageConstants.SDA\_BEFORE\_STEP\_PIPE)...0 – \*{0}, {1}: before step pipeline: {2}**

**JL.string(PRTMessageConstants.SDA\_DEAD\_INGORED) – \*{0}, {1}: synchronization point ignoring dead path from {2}**

**JL.string(PRTMessageConstants.SD\_ACTIVITY\_IN\_DEBUG) – Boundary event ignored because process was started in Debugger [PID={0}, ACTIVITY\_SID={1}, BOUNDARY\_SID={2}]**

**JL.string(PRTMessageConstants.SD\_ACTIVITY\_NOT\_RUNNING) – \*{0}, {1}: boundary event {2} ignored because activity is not running**

**JL.string(PRTMessageConstants.ST\_CACHE\_CONNECT\_ERR) – Exception: Unable to connect to cache!**

**JL.string(PRTMessageConstants.ST\_CACHE\_MGR\_NOT\_INITIALIZED) – Could not initialize cache manager**

**JL.string(PRTMessageConstants.ST\_CACHE\_NOT\_CONFIGURED) – Could not configure Shared Cache for Join locks**

**JL.string(PRTMessageConstants.ST\_CACHE\_NOT\_INITIALIZED) – Could not initialize cache: {0}**

**JL.string(PRTMessageConstants.ST\_LOCK\_INSERT\_FAIL) – Failed to insert Lock ID: {0} -- attempt {1} of {2}**

**JL.string(PRTMessageConstants.TU\_DELTHR\_CACHE) – Deleting thread from cluster cache, thread id={0}**

**JL.string(PRTMessageConstants.TU\_SETTHR\_CACHE\_ALIVE) – Marking thread alive in cluster cache, thread id={0}**

**JL.string(PRTMessageConstants.TU\_SETTHR\_CACHE\_KILLED) – Marking thread killed in cluster cache, thread id={0}**

**PRT.0101.0024E      Exception trying to encode step pipeline for {1}: {0}**

**Explanation**      Unable to encode the pipeline for audit logging.

**Action**            Check the exception message for details.

**PRT.0101.0025      Failed to encode pipeline for step {0}: {1}**

**PRT.0101.0026E      Custom logging: cannot find value for {0},{1} on path {2}**

**Explanation**      Unable to get the field value using the specified path.

**Action**            Make sure the field name and the path are correct.

**PRT.0101.0028E      Custom logging: cannot convert {0} to logging type {1} (value {2})**

**Explanation**      Failed to execute custom fields logging because the type of the field value cannot be determined.

**Action**            Verify that the custom field value is the correct field type.

---

<b>PRT.0101.0029E</b>	<b>Exception trying to push audit log context: {0}</b>
<b>Explanation</b>	Unable to add audit log context.
<b>Action</b>	Check the exception message for details.
<b>PRT.0101.0030E</b>	<b>Exception trying to pop audit log context: {0}</b>
<b>Explanation</b>	Unable to remove audit log context.
<b>Action</b>	Check the exception message for details.
<b>PRT.0101.0031E</b>	<b>Exception publishing Audit Log Event {1}: {0}</b>
<b>Explanation</b>	Unable to publish the log document for audit logging.
<b>Action</b>	Check the exception message for details.
<b>PRT.0101.0034E</b>	<b>Exception publishing Optimize Log Event {1}: {0}</b>
<b>Explanation</b>	Unable to perform the task because an audit runtime storage is not found.
<b>Action</b>	Make sure the audit runtime storage is properly set up and running.
<b>PRT.0101.0035</b>	<b>Exception registering Process Logger: {0}</b>
<b>PRT.0101.0055</b>	<b>*{0}, {1}: sending live transition to {2}</b>
<b>PRT.0101.0057E</b>	<b>Exception encoding transition pipeline: {0}</b>
<b>Explanation</b>	Unable to send an output transition using the specified transport.
<b>Action</b>	Check the exception message for details.
<b>PRT.0101.0059E</b>	<b>Exception during send: {0}</b>
<b>Explanation</b>	Cannot publish the document over the transport.
<b>Action</b>	Check the exception message in the Integration Server error logs for details.
<b>PRT.0101.0060</b>	<b>*{0}, {1}: sending dead transition to {2}</b>

<b>PRT.0101.0080</b>	<b>Loading process models in package {0}</b>
<b>PRT.0101.0082</b>	<b>Found PE model files in {0}</b>
<b>PRT.0101.0083</b>	<b>Loading model fragment {0}</b>
<b>PRT.0101.0084E</b>	<b>Exception loading model fragment {1}: {0}</b>
<b>Explanation</b>	Error while reading the process model file.
<b>Action</b>	Check the exception message for details.
<b>PRT.0101.0085</b>	<b>Skipping model fragment {0}</b>
<b>PRT.0101.0086</b>	<b>Deleting {0} old fragments from {1}</b>
<b>PRT.0101.0087E</b>	<b>Exception reading fragment file {1}: {0}</b>
<b>Explanation</b>	Error while reading the process model file.
<b>Action</b>	Check the process exception message in the Integration Server error logs for details.
<b>PRT.0101.0088</b>	<b>Deleting model fragment: {0}</b>
<b>PRT.0101.0089</b>	<b>Deleting XML file {0}</b>
<b>PRT.0101.0090</b>	<b>Adding new process fragment (pkg={0}, file={1})</b>
<b>PRT.0101.0091</b>	<b>Unable to create directory: {0}</b>
<b>PRT.0101.0118</b>	<b>[MID={0}, MVers={1}] has timed out</b>
<b>PRT.0101.0122E</b>	<b>Exception invoking timeout for {1}, {2}: {0}</b>
<b>Explanation</b>	Failed to invoke timeout.
<b>Action</b>	Check the exception message for details.

---

<b>PRT.0101.0124E</b>	<b>*{0}, {1}: starting timeout: {2}</b>
<b>Explanation</b>	Starting absolute timeout.
<b>Action</b>	This is an informative message only, indicating that an absolute timeout is being started for the process and step with the displayed IDs.
<b>PRT.0101.0140E</b>	<b>*{0}, {1}: killing step execution thread</b>
<b>Explanation</b>	Error while saving the process model file.
<b>Action</b>	Make sure you have write permission and network access to the file system.
<b>PRT.0101.0143I</b>	<b>{0} session</b>
<b>Explanation</b>	Timeout accessed an Integration Server service session to get the service thread.
<b>Action</b>	Informative message only: indicates that an IS service session has been accessed to get the service thread.
<b>PRT.0101.0145</b>	<b>[SID={0}] Creating timer entry for join timeout</b>
<b>PRT.0101.0147</b>	<b>*{0} cannot start Process timeout -- type not specified</b>
<b>PRT.0101.0148</b>	<b>*{0}, {1}: cannot start Join timeout -- type not specified</b>
<b>PRT.0101.0149</b>	<b>*{0}, {1}: cannot start Step timeout -- type not specified</b>
<b>PRT.0101.0150E</b>	<b>Registering PE transport {0}</b>
<b>Explanation</b>	Unable to sync documents with the Broker.
<b>Action</b>	Check the error message for details.
<b>PRT.0101.0151</b>	<b>Using new PE transport {0} as default</b>
<b>PRT.0101.0152</b>	<b>Removing PE transport {0}</b>

- PRT.0101.0153      **Default PE transport is {0}**
  
- PRT.0101.0154      **Default PE transport is {0}; deferred**
  
- PRT.0101.0155      **Not performing Broker push (not connected)**
  
- PRT.0101.0156      **Pushing doctypes to Broker**
  
- PRT.0101.0157      **Broker push error: {0}**
  
- PRT.0101.0158      **Sending {2} over {0} to {1}**
  
- PRT.0101.0160      **Broadcasting {1} over {0}**
  
- PRT.0101.0162      **Sending {1} over {0}**
  
- PRT.0101.0175      **\*{0}, {1}: new process instance created on {2}**
  
- PRT.0101.0178      **Warning. Process model {0} is inactive**
  
- PRT.0101.0180      **NON-START STEP. Step {1} of model {0} is a non-start step**
  
- PRT.0101.0182      **[MID={0}, MVer={1}, fragment={2}] using newly-created pid**
  
- PRT.0101.0183      **checking out process stack**
  
- PRT.0101.0184      **using pre-existing stack. Parent process ID = {0}**

---

PRT.0101.0186	creating brand new process stack
PRT.0101.0195	setting process status to RUNNING
PRT.0101.0196	*PID={0}, MID={1}, MVer={2}: process started
PRT.0101.0197	*{0}, MID={1}, MVer={2}: process restarting
PRT.0101.0199	[PID={0}, Delta={1}] updating Track Count
PRT.0101.0202	*PID={0}, MID={1}, MVer={2}: process completed
PRT.0101.0206	Cache cleanup running every {0} seconds and every {1} instances
PRT.0101.0207	*{0}, {1}: transitioning to cancel step
PRT.0101.0223	looking for PID for CID {0}
PRT.0101.0224	[MID={1}] matching bizdoc to model. Type name = {0}. Require start = {2}
PRT.0101.0228	{0} index entries found for doctype {1}
PRT.0101.0229	entry({0}) ==> {1}@{2}, filter={3}
PRT.0101.0230	evaluateFilter(): filter = {0}
PRT.0101.0231	evaluateFilter(): pipe = {0}

PRT.0101.0235	<b>DocID={0}, DocType={1}, ConvId={2}: processing incoming TN document</b>
PRT.0101.0236	<b>{{0}} doc internal ID: {1}</b>
PRT.0101.0237	<b>{{0}} doctype name: {1}</b>
PRT.0101.0238	<b>{{0}} conversation ID: {1}</b>
PRT.0101.0240	<b>joining existing conversation {1}</b>
PRT.0101.0241	<b>using model ID {0}</b>
PRT.0101.0242E	<b>DocID={0}, DocType={1}, ConvId={2}: no Model match for TN document</b>
<b>Explanation</b>	Not starting a process instance because no process model is found that matches the business document (bizdoc).
<b>Action</b>	Make sure there is a process model that subscribes to this business document (bizdoc).
PRT.0101.0243E	<b>DocID={0}, DocType={1}, ConvId={2}, MID={3}: no Step match for TN document</b>
<b>Explanation</b>	Unable to match a step to the business document (bizdoc).
<b>Action</b>	Make sure at least one step in the process model subscribes to this business document (bizdoc).
PRT.0101.0244	<b>ConvId={0}, PID={1}: starting/joining TN process</b>
PRT.0101.0247	<b>joining process (status {0})</b>
PRT.0101.0248	<b>PROCESS DONE, CANNOT JOIN</b>
PRT.0101.0249	<b>joining at step {1} (frag {0})</b>

---

<b>PRT.0101.0251E</b>	<b>IM failed: model is disabled or non-start step</b>
<b>Explanation</b>	Unable to create a process instance because it is a non-start step or the process model is inactive.
<b>Action</b>	If joining a running process, make sure it has the correct conversation ID. Otherwise, make sure the process model is enabled in webMethods Monitor.
<b>PRT.0101.0252</b>	<b>Attribute {0} = {1}</b>
<b>PRT.0101.0253</b>	<b>BizDocAttribute {0} is required in a process, but no definition is available on this server</b>
<b>PRT.0101.0254E</b>	<b>Exception fetching data from TN profile store: {0}</b>
<b>Explanation</b>	Unable to get the Trading Networks partner profile summary.
<b>Action</b>	Check the Trading Networks partner profile.
<b>PRT.0101.0255</b>	<b>Profile Field {0} = {1}</b>
<b>PRT.0101.0256E</b>	<b>Extended profile field {0} is required in a process, but no definition is available on this server</b>
<b>Explanation</b>	Unable to get the extended profile field.
<b>Action</b>	Make sure the extended profile field is populated.
<b>PRT.0101.0257E</b>	<b>Exception fetching data for field {1}: {0}</b>
<b>Explanation</b>	Unable to get the Trading Networks extended profile field.
<b>Action</b>	Check the Trading Networks extended profile field.
<b>PRT.0101.0258</b>	<b>Duplicate document: {0}. Document rejected</b>
<b>PRT.0101.0278</b>	<b>*{0}, {1}: handling transition event to {2}</b>
<b>PRT.0101.0284</b>	<b>*{0}, {1}: handling native document {3} on {2}</b>

<b>PRT.0101.0289E</b>	<b>NO MATCHING STEP</b>
<b>Explanation</b>	Unable to find the step that subscribes to this document.
<b>Action</b>	Make sure a step in the process model subscribes to this document.
<b>PRT.0101.0290E</b>	<b>Document {2} does not match to any step in process {0} on {1}</b>
<b>Explanation</b>	Unable to find the step that subscribes to this document.
<b>Action</b>	Make sure a step in the process model subscribes to this document.
<b>PRT.0101.0292</b>	<b>Document {2} matches step in process {0} on {1}</b>
<b>PRT.0101.0294E</b>	<b>NO MATCHING INPUT for pid</b>
<b>Explanation</b>	Unable to get the input definition for this document.
<b>Action</b>	Make sure the document exists and is synced to the Broker.
<b>PRT.0101.0295E</b>	<b>*{0}, {1}: document {3} is NOT a valid published input</b>
<b>Explanation</b>	Unable to get the input definition for this document.
<b>Action</b>	Make sure the document exists and is synced to the Broker.
<b>PRT.0101.0297</b>	<b>*{0}, {1}, document {3} is a valid published input</b>
<b>PRT.0101.0300E</b>	<b>*{0}, {1}: using correlation service {2}</b>
<b>Explanation</b>	An error occurred while accessing the ProcessAudit database.
<b>Action</b>	Make sure that the ProcessAudit pool alias is configured and functional, and that there are no connectivity problems.
<b>PRT.0101.0301E</b>	<b>pipe: {0}</b>
<b>Explanation</b>	An error occurred while accessing the ProcessAudit database.
<b>Action</b>	Make sure that the ProcessAudit pool alias is configured and functional, and that there are no connectivity problems.

---

<b>PRT.0101.0303</b>	<b>*{0}, {1}: correlating to TN conversation id</b>
<b>PRT.0101.0305E</b>	<b>*{0}, {1}: correlated to process id</b>
<b>Explanation</b>	An error occurred while accessing the ProcessAudit database.
<b>Action</b>	Make sure that the ProcessAudit pool alias is configured and functional, and that there are no connectivity problems.
<b>PRT.0101.0306</b>	<b>correlation ID mapped to existing PID</b>
<b>PRT.0101.0307E</b>	<b>Error invoking correlation svc {1}: {0}</b>
<b>Explanation</b>	Failed to invoke the specified correlation service.
<b>Action</b>	Check the process exception in the Integration Server error logs for details.
<b>PRT.0101.0309</b>	<b>dispatching event : {0}</b>
<b>PRT.0101.0310</b>	<b>*{0}, {1}: starting step execution</b>
<b>PRT.0101.0311E</b>	<b>*{0}, {1}: no process fragment contains this step</b>
<b>Explanation</b>	Unable to find the step in the process model fragment file.
<b>Action</b>	Make sure generated model fragment file contains this step.
<b>PRT.0101.0314</b>	<b>Exception dispatching step: {0}</b>
<b>PRT.0101.0315E</b>	<b>Exception handling transition event: {0}</b>
<b>Explanation</b>	Failed to handle a process transition document.
<b>Action</b>	Check the exception message for details.
<b>PRT.0101.0317W</b>	<b>Error joining because it is terminated already</b>
<b>Explanation</b>	Cannot join a process that is not running.
<b>Action</b>	Check the exception message for details.

PRT.0101.0318	*{0}, {1}: using correlation field {2}
PRT.0101.0319	*{0}, {1}: correlated to disabled model {2} version {3}
PRT.0101.0320	*{0}, {1}: correlated to {2}, expected {3}
PRT.0101.0335	*{0}, {1}: start step execution
PRT.0101.0336	*{0}, {1}: end step execution
PRT.0101.0337	continuing synchronous execution at step {0}
PRT.0101.0341	*{0}, {1}: executing step
PRT.0101.0343	fragment and step validated
PRT.0101.0347	*{0}, {1}: pushing step on suspended list
PRT.0101.0349	step iteration = {0}
PRT.0101.0356	*{0}, {1}: step not executed, enqueueing event
PRT.0101.0357	*{0}, {1}: step iteration count exceeded
PRT.0101.0358	*{0}, {1}: setting try count to {2}
PRT.0101.0359E	Exception executing step {1}, {2}: {0}
<b>Explanation</b>	The XPath expression cannot be parsed.
<b>Action</b>	Verify that the XPath expression is valid.

---

<b>PRT.0101.0360E</b>	<b>Exception saving step context {1}, {2}: {0}</b>
<b>Explanation</b>	Failed to save the context of the step.
<b>Action</b>	Check the exception message in the Integration Server error logs for details.
<b>PRT.0101.0361</b>	<b>done preparing step for execution</b>
<b>PRT.0101.0362</b>	<b>*{0}, {1}: logging custom audit data</b>
<b>PRT.0101.0366</b>	<b>no service to execute</b>
<b>PRT.0101.0370</b>	<b>merging pre-defined service inputs</b>
<b>PRT.0101.0372</b>	<b>service executed OK. After step invoke outPipe={0}</b>
<b>PRT.0101.0373</b>	<b>*{0}, {1}: sent {2} output events</b>
<b>PRT.0101.0374E</b>	<b>SERVICE EXECUTION FAILED ({0}) {1}</b>
<b>Explanation</b>	Caught a service exception. If an error handler is defined, the appropriate error action will be taken. Otherwise, the process will be marked as failed.
<b>Action</b>	Check webMethods Monitor for details about the failure.
<b>PRT.0101.0376E</b>	<b>Exception invoking service {1}, {2}, Svc={3}: {0}</b>
<b>Explanation</b>	Failed while executing the step. Service throws an error.
<b>Action</b>	If an error handler is defined, the appropriate error action will be taken. Otherwise, the process will be marked as failed.
<b>PRT.0101.0377</b>	<b>*{0}, {1}: transitioning to error step {2}</b>
<b>PRT.0101.0378E</b>	<b>*{0}, {1}: terminated abnormally</b>
<b>Explanation</b>	Failure during process execution. No error handler defined for the step.
<b>Action</b>	Define an error handler for the failed step so that appropriate error action can be taken.

PRT.0101.0383	<b>considering published output {0} (doctype {1})</b>
PRT.0101.0385	<b>document: {0}. Publishing with stack {1}</b>
PRT.0101.0387E	<b>missing content for document {0}</b>
<b>Explanation</b>	Unable to get the document from the publish output because of a missing or corrupted document object.
<b>Action</b>	Make sure the document is in the publish output pipeline.
PRT.0101.0388	<b>*{0}, {1}: published output document {2}</b>
PRT.0101.0389	<b>considering bizdoc output {0}</b>
PRT.0101.0390	<b>done with bizdoc output {0}</b>
PRT.0101.0391E	<b>Exception sending output {1} of {2} for PID {3} SID {4}: {0}</b>
<b>Explanation</b>	Error while sending output documents.
<b>Action</b>	Check the exception message for details.
PRT.0101.0392	<b>ERROR on output {0} of {1}. Output isa {2}. Output: {3}</b>
PRT.0101.0395	<b>considering transition to step {0} on {1}</b>
PRT.0101.0396	<b>*{0}, {1}: adding dead transition to {2}</b>
PRT.0101.0397	<b>*{0}, {1}: adding live transition to {2}</b>
PRT.0101.0398	<b>synchronously following transition to {0}</b>

---

<b>PRT.0101.0399</b>	<b>*{0}, {1}: publishing transition to {2} on {3}</b>
<b>PRT.0101.0400E</b>	<b>Exception updating track count {1}, {2}: {0}</b>
<b>Explanation</b>	Failed to evaluate the condition associated with this output, possibly because of an invalid condition parameter.
<b>Action</b>	Check the process exception message in the Integration Server error logs for details.
<b>PRT.0101.0401</b>	<b>*{0}, {1}: no track count change</b>
<b>PRT.0101.0402</b>	<b>*{0}, {1}: updated track count by {2} to {3}</b>
<b>PRT.0101.0403</b>	<b>*{0}, {1}: transition condition {2} evaluated to {3}</b>
<b>PRT.0101.0412W</b>	<b>Cannot execute step {0} because the process was terminated already</b>
<b>Explanation</b>	Cannot execute a step because the process was terminated.
<b>Action</b>	Check for incorrect use of the correlation service.
<b>PRT.0101.0428E</b>	<b>PE queue processing for step {0}</b>
<b>Explanation</b>	An error occurred while executing a step.
<b>Action</b>	See the detailed error message for specific information.
<b>PRT.0101.0430</b>	<b>event queue empty, nothing to do</b>
<b>PRT.0101.0432</b>	<b>*{0}, {1}: transitioning to timeout handler</b>
<b>PRT.0101.0434E</b>	<b>Exception assembling pipeline {1}, {2}: {0}</b>
<b>Explanation</b>	Cannot create a transition pipeline for the specified step.
<b>Action</b>	Check the exception in the Integration Server error logs for details.
<b>PRT.0101.0435</b>	<b>*{0}, {1}: {2} events in the queue. Join state: {3}</b>

<b>PRT.0101.0441</b>	<b>dropping {0} (id {1})</b>
<b>PRT.0101.0442</b>	<b>update track count ({0}) as a result of dropping events after the join</b>
<b>PRT.0101.0444</b>	<b>returning positive join result</b>
<b>PRT.0101.0445</b>	<b>these events will be in the pipeline:</b>
<b>PRT.0101.0447</b>	<b>applying thread count DELTA of {0}</b>
<b>PRT.0101.0448I</b>	<b>*{0}, {1}: starting join timeout</b>
<b>Explanation</b>	Starting join timeout.
<b>Action</b>	This is an informative message only, indicating that a join timeout has been started.
<b>PRT.0101.0449I</b>	<b>*{0}, {1}: starting step timeout</b>
<b>Explanation</b>	Starting step timeout.
<b>Action</b>	This is an informative message only, indicating that a step has been started.
<b>PRT.0101.0451</b>	<b>*{0}, {1}: absolute timeout type is invalid</b>
<b>PRT.0101.0452</b>	<b>Exception: Deprecated step found {1}, {2}: {0}</b>
<b>PRT.0101.0455</b>	<b>Error cloning IData {0}.</b>
<b>PRT.0101.0468E</b>	<b>Something just tried to dequeue an event with a null ID</b>
<b>Explanation</b>	Unable to remove metadata from the queue.
<b>Action</b>	Check the ArgumentException message in the Integration Server error logs for details.

---

<b>PRT.0101.0469E</b>	<b>Document with duplicate correlation ID submitted.</b>
<b>Explanation</b>	An error occurred when a document with a duplicate correlation ID was found.
<b>Action</b>	Make sure each correlation ID is unique.
<b>PRT.0101.0489</b>	<b>PRTX: INSERT {0},{1} --&gt; p.{2}</b>
<b>PRT.0101.0494</b>	<b>PRTX: mapping {0},{1} (insert={2})</b>
<b>PRT.0101.0509</b>	<b>Using Shared Cache for Join locks</b>
<b>PRT.0101.0511E</b>	<b>Can not initialize jdbc runtime storage for PE. Make sure ProcessAudit or ProcessEngine runtime pool is configured properly</b>
<b>Explanation</b>	Failed to establish a database for Process Engine storage; using repository instead.
<b>Action</b>	Check the Process Audit and PRT Associated Pool Alias configurations.
<b>PRT.0101.0512E</b>	<b>Storage exception: {0}</b>
<b>Explanation</b>	Exception executing an SQL statement.
<b>Action</b>	Check for incorrect database configuration.
<b>PRT.0101.0513</b>	<b>Storage cleaner: will run every {0} seconds</b>
<b>PRT.0101.0514E</b>	<b>Storage cleaner: executing stored procedure</b>
<b>Explanation</b>	An error occurred while saving the web service binding file. The user may not have the correct access to the directory.
<b>Action</b>	Make sure that the user has proper read/write access to the directory.
<b>PRT.0101.0515E</b>	<b>Storage cleaner: executing embedded SQL</b>
<b>Explanation</b>	An error occurred while saving the web service binding file. The user may not have the correct access to the directory.
<b>Action</b>	Make sure that the user has proper read/write access to the directory.

<b>PRT.0101.0517E</b>	<b>Storage cleaner: Duration {0} ms</b>
<b>Explanation</b>	An error occurred while saving the Web service binding file. The user may not have the correct access to the directory.
<b>Action</b>	Make sure that the user has proper read/write access to the directory.
<b>PRT.0101.0518E</b>	<b>Exception: Unable to connect to database!</b>
<b>Explanation</b>	The Web service binding file does not exist. The user may not have the correct access to the directory.
<b>Action</b>	Make sure that the user has proper read/write access to the directory.
<b>PRT.0101.0519</b>	<b>Storage cleaner: expiration for completed processes: {0} seconds</b>
<b>PRT.0101.0521</b>	<b>Storage cleaner: cannot acquire lock. Exception: {0}</b>
<b>PRT.0101.0522</b>	<b>Storage cleaner: expiration for failed processes: {0} seconds</b>
<b>PRT.0101.0523E</b>	<b>Storage cleaner: clean up for completed processes is disabled</b>
<b>Explanation</b>	The WSDL file for the web service could not be accessed. The file may not exist or it may be in the wrong directory location.
<b>Action</b>	Make sure that this file exists and has been deployed to the correct directory location.
<b>PRT.0101.0531</b>	<b>Exception: {0}. Step Level Retry configured for service: {1}. Retry {2} of {3} in {4} ms</b>
<b>PRT.0101.0532E</b>	<b>No Step Level Retry configured for step service: {0}</b>
<b>Explanation</b>	The WSDL file for the Web service could not be accessed.
<b>Action</b>	Make sure that the WSDL file exists and has been deployed to the generated package.
<b>PRT.0101.0533E</b>	<b>Step Level Retry count exceeded for service: {0}</b>
<b>Explanation</b>	An error occurred while accessing the process model package.
<b>Action</b>	Make sure that the process model has been generated and the corresponding namespace package has been created.

---

PRT.0101.0534	<b>Thread Threshold detected. Retry abandoned for {0}.</b>
PRT.0101.0535	<b>Error querying process {0} version {1} from {2}. Make sure the process is deployed for monitoring.</b>
PRT.0101.0550	<b>[MID={0}] StatusManager processing {1} request</b>
PRT.0101.0551	<b>*{0}: process status changed to {1}</b>
PRT.0101.0552	<b>*{0}: resuming process at {1}</b>
PRT.0101.0553	<b>*{0}: restarting process at step {0}</b>
PRT.0101.0554	<b>Running process at step {0}</b>
PRT.0101.0601I	<b>web service request/reply {0}</b>
<b>Explanation</b>	Performing Web service request/reply.
<b>Action</b>	Informative message only: indicates that the PRT dispatcher is processing a Web service request/reply.
PRT.0101.0700I	<b>Adding thread to thread table, thread id={0}</b>
<b>Explanation</b>	Added a thread with the following thread ID to the Process Engine's internal thread table.
<b>Action</b>	Informative message only: indicates the thread ID for a thread added to the Process Engine's internal table.
PRT.0101.0701I	<b>Getting thread from thread table, thread id={0}</b>
<b>Explanation</b>	Retrieved a thread with the following thread ID from the Process Engine's internal thread table.
<b>Action</b>	Informative message only: indicates the thread ID for a thread retrieved from the Process Engine's internal table.

PRT.0101.0702	<b>Deleting thread from thread table, thread id={0}</b>
PRT.0101.0830	<b>JMS Connection Alias for PE 'PE_NONTRANSACTIONAL_ALIAS' has not been configured.</b>
PRT.0101.0831	<b>Error creating JMS internal topic: {0}</b>
PRT.0101.0832	<b>Error updating client group permissions: {0}</b>
PRT.0101.0833	<b>Error creating JMS connection alias: {0}</b>
PRT.0101.0850E	<b>[MID={0}] Now listening to path: "{1}" for e-Forms on jcr "{2}"</b>
<b>Explanation</b>	This is an informative message. The e-form configuration is now listening for events.
<b>Action</b>	To generate an event, place an e-form into the My webMethods Server folder location that the listener is monitoring.
PRT.0101.0851	<b>[MID={1}] Error with Content Repository "{2}". Check if the repo is running, login credentials and repo connection information is correct. {0}</b>
PRT.0101.0852E	<b>[MID={1}] Error disabling/removing listener from Content Repository "{2}". {0}</b>
<b>Explanation</b>	Listener cannot be removed because the repository is down or does not exist.
<b>Action</b>	Make sure the repository is still running and connected, and that the listener is valid.
PRT.0101.0853	<b>[MID={0}] Content Repository "{1}" not configured.</b>
PRT.0101.0854	<b>[MID={0}] Listener for e-Forms at path: "{1}" has been disabled from jcr "{2}"</b>
PRT.0101.0855	<b>[MID={1}] Error adding listener to Content Repository "{2}". {0}</b>
PRT.0101.0856E	<b>[MID={1}] Problem reading E-form config file: "{2}". {0}</b>
<b>Explanation</b>	An invalid e-form configuration file or unknown file type using the CSP or JCR file name extension was found in WmPRT\config\.
<b>Action</b>	Log in to My webMethods and delete and then re-create the e-form configuration in the Define Environments application page.

<b>PRT.0101.0857E</b>	<b>[MID={0}] Unable to change listener please disable all other models currently using this listener: "{1}"</b>
<b>Explanation</b>	The SOAP processor aborted processing of the SOAP message because of a problem with the message header.
<b>Action</b>	Make sure the header entries of the SOAP message are valid.
<b>PRT.0101.0858E</b>	<b>[MID={0}] Cannot edit access for PORT 15006. Please ensure to manually add access for "wm.prt.eforms:update" "wm.server:connect" "wm.server:disconnect" "wm.server:ping".</b>
<b>Explanation</b>	E-forms requires the specified port to be open.
<b>Action</b>	Make sure that that port 15006 is open and has access for "wm.prt.eforms:update", "wm.server:connect", "wm.server:disconnect", and "wm.server:ping".
<b>PRT.0101.0859E</b>	<b>[MID={0}] Cannot start e-form process because doc type: "{1}" does not exist. For e-form instance at: "{2}". Please recreate the e-form doc or rebuild the model(s).</b>
<b>Explanation</b>	The document type related to this listener does not exist on the Integration Server.
<b>Action</b>	Re-create the e-form document type and rebuild the affected process model(s).
<b>PRT.0101.0860</b>	<b>[MID={0}] Trying to publish E-form instance "{1}" for template "{2}". With doc type of "{3}". If process does not start please check error log for any pub.publish errors. IData:{4}</b>
<b>PRT.0101.0861</b>	<b>[MID={1}] Error restarting listener(s) to Content Repository "{2}". {0}</b>
<b>PRT.0101.0862</b>	<b>Content Repository currently has no models associated to it. No reason to restart the repository at this time.</b>
<b>PRT.0101.0863</b>	<b>[MID={1}] Cannot retrieve password: "{2}". {0}</b>
<b>PRT.0101.0864</b>	<b>No model(s) enabled using this listener "{0}". Listener will not be restarted.</b>
<b>PRT.0101.0865</b>	<b>[MID={0}] Content Repository currently has a listener listening in that location. No new listener added to listening path: "{1}" for e-Forms on jcr "{2}".</b>

<b>PRT.0101.0900E</b>	<b>Monitor: {0}</b>
<b>Explanation</b>	Type mismatch in BPEL assign.
<b>Action</b>	Check that the mapping performed in the assign step is valid. Mapping is not typesafe.
<b>PRT.0101.0902E</b>	<b>Invalid Logging Level</b>
<b>Explanation</b>	Unable to find type of the field for the record using the specified part and XPath query.
<b>Action</b>	Check that the type used in the part and XPath query is defined in your Integration Server instance. This can occur when the field or record are not defined in the Integration Server instance to which the corresponding process has been deployed.
<b>PRT.0101.0903E</b>	<b>Log Transitions value must be either "True" or "False"</b>
<b>Explanation</b>	Unable to find type of the field for the record using the specified part and XPath query.
<b>Action</b>	Check that the type used in the part and XPath query is defined in your Integration Server instance. This can occur when the field or record are not defined in the Integration Server instance to which the corresponding process has been deployed.
<b>PRT.0101.0907</b>	<b>Enable Resubmission value must be either "True" or "False"</b>
<b>PRT.0101.0908</b>	<b>[MID={0}, MVers={1}] Model does not exist.</b>
<b>PRT.0101.0909</b>	<b>[MID={0}] QoS cannot be changed because it was generated from a pre-7.0 version of Modeler.</b>
<b>PRT.0101.0910</b>	<b>[MID={0}] Logging level for Model cannot be set below minimum value of {1}.</b>
<b>PRT.0101.1001</b>	<b>CheckDuplicates processing {0}, uuid, {1}</b>
<b>PRT.0101.1002</b>	<b>CheckDuplicates processed {0}, uuid, {1}, status, {2}</b>
<b>PRT.0101.1003</b>	<b>CheckDuplicates throwing ISRuntimeException {0}, uuid, {1}</b>

---

PRT.0101.1100	Error trying to get JDBC pool configuration using functional alias {0}. Business calendar based timeouts will not be able to be evaluated.
PRT.0101.1101	Exception trying to get JDBC pool configuration: {0}
PRT.0101.1102	Unable to initialize MWS library. Business calendar based timeouts will not be able to be evaluated.
PRT.0101.1103	Exception trying to initialize MWS library: {0}
PRT.0101.1200	Business timeout is invalid: {0}
PRT.0101.1201	Business calendar alias {0} does not exist
PRT.0101.1202	Business calendar evaluator does not exist
PRT.0101.1300	*{0}, {1}: did not start timer, no end time specified.
PRT.0101.1301	*{0}: executing Process Timeout
PRT.0101.1302	*{0}, {1}: executing Step Timeout
PRT.0101.1303	*{0}, {1}: executing Join Timeout
PRT.0101.1304	[MID={0}, SID={1}] Error killing step thread
PRT.0101.1305	[MID={0}] Constructing process timeout
PRT.0101.1306	[MID={0}, SID={1}] Constructing step timeout

- PRT.0101.1307 [MID={0}, SID={1}] Constructing join timeout
- PRT.0101.1309 \*{0}, {1}: cancelling step timeout
- PRT.0101.1310 \*{0}, {1}: cancelling join timeout
- PRT.0101.1400 Exception trying to fail the process \*{1}: {0}
- PRT.0101.1401 \*{0}, {1}: sending Dead Path PTE to {2} on {3}
- PRT.0101.1402 \*{0}, {1}: process version changed from {2} to {3}
- PRT.0101.1403 \*{0}, {1}: taking unsatisfied join transition {2}
- PRT.0101.1500 made input pipe from {0} events
- PRT.0101.1600 Unable to get Optimize process data collector. Tracking enabled models will not be logged to Optimize.
- PRT.0101.1601 Exception trying to get Optimize process data collector: {0}
- PRT.0101.1602 Exception trying to shut down Optimize data collector: {0}
- PRT.0101.1742 Failed to restart e-form listener for {0}.
- PRT.0101.1743 Restart of e-form listener: {0} successful.
- PRT.0101.9123E No value was supplied for the required parameter {0}.  
**Explanation** A parameter is missing or corrupted.  
**Action** Make sure that the parameter object exists.

---

<b>PRT.0101.9124E</b>	<b>An invalid value was supplied for the required parameter {0}. The bad value was {1}.</b>
<b>Explanation</b>	The value of the specified key is invalid.
<b>Action</b>	Make sure the value is the specified type.
<b>PRT.0101.9125E</b>	<b>Service {0} failed.</b>
<b>Explanation</b>	Caught a service exception.
<b>Action</b>	Check the service exception message in the Integration Server error logs for details.
<b>PRT.0101.9135E</b>	<b>Cannot read frag file {0}: the file does not exist.</b>
<b>Explanation</b>	An error occurred while reading the process model file: the file does not exist.
<b>Action</b>	Make sure the model has been generated correctly.
<b>PRT.0101.9136E</b>	<b>Cannot read frag file {0}: the file is not readable.</b>
<b>Explanation</b>	An error occurred while reading the process model file: the file is not readable.
<b>Action</b>	Check the file permissions.
<b>PRT.0101.9137E</b>	<b>Malformed frag file {0}: the file does not contain the 'fragment' key.</b>
<b>Explanation</b>	Unable to read the process model file; the file may be corrupted.
<b>Action</b>	Regenerate the process model.
<b>PRT.0101.9138E</b>	<b>IOException reading frag file {0}</b>
<b>Explanation</b>	An error occurred while reading the process model file.
<b>Action</b>	Refer to the process exception in the Integration Server error logs for details.
<b>PRT.0101.9139E</b>	<b>Cannot write frag file {0}: the file already exists and is not writeable.</b>
<b>Explanation</b>	An error occurred while saving the process model file: the file already exists.
<b>Action</b>	Check the file permissions.
<b>PRT.0101.9151E</b>	<b>Cannot rebind role {0} from partner ID {1} to partner ID {2}</b>
<b>Explanation</b>	Unable to add a TN sender or receiver role because the current public role information indicates a different partner ID.
<b>Action</b>	Make sure the sender or receiver matches the partner ID, then restart the process.

<b>PRT.0101.9195E</b>	<b>Could not enable model "{0}" version "{1}" for {2}</b>
<b>Explanation</b>	Cannot get a lock for global data.
<b>Action</b>	Determine whether another step in the process currently has a lock on global data.
<b>PRT.0101.9196E</b>	<b>Could not disable model "{0}" version "{1}" for {2}</b>
<b>Explanation</b>	Cannot get a lock for global data.
<b>Action</b>	Determine whether another step in the process currently has a lock on global data.
<b>PRT.0101.9197E</b>	<b>Could not acquire lock "{0}"</b>
<b>Explanation</b>	A field is not present in global data when using BPEL assign.
<b>Action</b>	Make sure the data exists.
<b>PRT.0101.9201</b>	<b>Correlated process ID {0} is incorrect; a process already exists with that process ID and a different model ID</b>
<b>PRT.0101.9204E</b>	<b>The CID returned from {0} is too long. CID length is {1}; maximum allowed is {2}</b>
<b>Explanation</b>	The conversation ID has exceeded the maximum allowed length.
<b>Action</b>	Shorten the conversation ID and rerun the process.
<b>PRT.0101.9205E</b>	<b>Correlation ID joins to a process instance that is no longer running. PID: {0}</b>
<b>Explanation</b>	Joins are not allowed on process instances that are not in running status.
<b>Action</b>	Change the state to running or start a new process instance.
<b>PRT.0101.9206</b>	<b>Intermediate Receive Step {2} of model {0} version {1} does not correlate to existing Process ID</b>
<b>PRT.0101.9215E</b>	<b>Cannot start process {0}; unable to determine the appropriate model</b>
<b>Explanation</b>	The process model ID has not been properly stored in the Process Engine DB.
<b>Action</b>	Check that the DB is working properly and rerun the process.

---

<b>PRT.0101.9216E</b>	<b>Cannot start process {0} with model {1} at step {2}: there is no fragment defined that contains that step</b>
<b>Explanation</b>	The process model fragment file does not contain the definition for the specified step.
<b>Action</b>	Check that the step is properly generated in the fragment file. If not, regenerate the process.
<b>PRT.0101.9217E</b>	<b>Cannot start process {0} at step {1}: there is no such step defined in fragment {2}</b>
<b>Explanation</b>	The process model fragment file does not contain the definition for the specified step.
<b>Action</b>	Check that the step is properly generated in the fragment file. If not, regenerate the process.
<b>PRT.0101.9218</b>	<b>Error changing version for process {0} with model {1} at step {2} from version {3} to {4}: there is no fragment defined that contains that step</b>
<b>PRT.0101.9228E</b>	<b>Missing ConversationID for call to getInstanceId()</b>
<b>Explanation</b>	Cannot start a process because a conversation ID was not present in the Trading Networks document envelope.
<b>Action</b>	Make sure that the conversation ID is properly defined and extracted.
<b>PRT.0101.9229E</b>	<b>Model {0} was specified, but there is no step in this model for a bizdoc of type {1}</b>
<b>Explanation</b>	Cannot find any step in the model that subscribes to this document.
<b>Action</b>	Make sure the model has a step that subscribes to this document.
<b>PRT.0101.9230E</b>	<b>Couldn't start process. Either the model is disabled or this document targets a non-start step.</b>
<b>Explanation</b>	The process cannot be started either because the model is disabled or the step subscribing to this document is not a start step.
<b>Action</b>	Make sure the model is enabled and that the step that subscribes to this document is a start step.
<b>PRT.0101.9231E</b>	<b>No ConversationID available; PE bizdoc processing fails</b>
<b>Explanation</b>	Cannot start a new process or join an existing process because a conversation ID was not present in the TN document envelope.
<b>Action</b>	Make sure that conversation ID is properly defined and extracted.

<b>PRT.0101.9244E</b>	<b>PID {0}: Cannot {1} process; status is {2}</b>
<b>Explanation</b>	The process instance has one of the following statuses: STAT_UNKNOWN, STAT_RUNNING, STAT_SUSPENDED, STAT_FAILED, STAT_CANCELLED, or STAT_DONE. Because the process instance is in one of these states, it cannot run the requested action. The requested action will be one of the following: START, SUSPEND, RESUME, CANCEL, FAIL, RESTART, QUIET, or DONE.
<b>Action</b>	Make sure the action is allowed on processes with the specified status.
<b>PRT.0101.9245E</b>	<b>PID {0}: Bad command RESTART; target step is missing</b>
<b>Explanation</b>	Unable to restart the process because of a missing or corrupted target step ID in the pipeline.
<b>Action</b>	Check the pipeline then restart the process.
<b>PRT.0101.9246E</b>	<b>PID {0}: Bad command RESTART; pipeline is missing</b>
<b>Explanation</b>	Unable to restart the process because of a missing or corrupted pipeline.
<b>Action</b>	Check the pipeline then restart the process.
<b>PRT.0101.9248E</b>	<b>PID {0}: Bad command RESTART; pipeline is missing /ProcessData</b>
<b>Explanation</b>	Unable to restart the process because of a missing or corrupted ProcessData object in pipeline.
<b>Action</b>	Check the pipeline then restart the process.
<b>PRT.0101.9249E</b>	<b>PID {0}: Bad command RESTART; pipeline is missing /ProcessData/LastEvents</b>
<b>Explanation</b>	The process instance was not restarted because the pipeline is missing.
<b>Action</b>	Make sure that the pipeline is properly logged.
<b>PRT.0101.9250E</b>	<b>PID {0}: Bad command RESTART; RestartParameters is missing</b>
<b>Explanation</b>	Cannot restart the process instance because some or all of the restart parameters are missing.
<b>Action</b>	Make sure that all of the restart parameters are present in the pipeline.
<b>PRT.0101.9251E</b>	<b>PID {0}: restart failed because the supplied pipeline contains an invalid ProcessInstanceID {1}</b>
<b>Explanation</b>	Unable to restart due to a invalid process instance ID.
<b>Action</b>	Check the pipeline then restart the process.

---

<b>PRT.0101.9253E</b>	<b>MID {0}: Cannot restart process; frag {1} step {2} does not define bizdoc {3} as input</b>
<b>Explanation</b>	Process cannot be restarted because the target step does not define the document as an input.
<b>Action</b>	Make sure that the target step specifies the document as an input.
<b>PRT.0101.9254E</b>	<b>PID {0}: failed to restart at step {1} because at least one valid event is needed in path /ProcessData/LastEvents/ of the supplied pipeline {2}</b>
<b>Explanation</b>	The process cannot be restarted because all documents in the pipeline have been removed.
<b>Action</b>	Start a new instance of the process.
<b>PRT.0101.9255E</b>	<b>MID {0} Failed to restart the process because Model {0} is not enabled</b>
<b>Explanation</b>	The process cannot be restarted because the model is disabled.
<b>Action</b>	Enable the model and restart again.
<b>PRT.0101.9256</b>	<b>PID {0} Failed to execute process instance status change</b>
<b>PRT.0101.9262E</b>	<b>PID {0}: Could not get a connection in {1}</b>
<b>Explanation</b>	An error occurred while trying to connect to Process Engine DB storage.
<b>Action</b>	Make sure that Process Engine DB storage is properly configured and running.
<b>PRT.0101.9263E</b>	<b>PID {0}: Update thread count failed</b>
<b>Explanation</b>	An error occurred while communicating with the Process Engine DB.
<b>Action</b>	Make sure that the Process Engine DB is properly configured and running.
<b>PRT.0101.9264</b>	<b>Cannot create new instance of model {0} version {1}, it is not enabled</b>
<b>PRT.0101.9265</b>	<b>Step {2} of model {0} version {1} is not a start step</b>
<b>PRT.0101.9285E</b>	<b>Could not create TN facade</b>
<b>Explanation</b>	Unable to create a Trading Networks implementation.
<b>Action</b>	Check the process exception message in the Integration Server error logs for details.

<b>PRT.0101.9286E</b>	<b>Could not handle doc output</b>
<b>Explanation</b>	Error while handling the output of a business document (bizdoc).
<b>Action</b>	Check the process exception message in the Integration Server error logs for details.
<b>PRT.0101.9287E</b>	<b>bizdoc_output() failed because pipeline object {0} is not a TN bizdoc object</b>
<b>Explanation</b>	The specified document is the wrong type.
<b>Action</b>	Make sure the document is a Trading Networks document.
<b>PRT.0101.9301E</b>	<b>Exception occurred during correlation or cross-reference operation</b>
<b>Explanation</b>	Unable to perform ID correlation because an error occurred while connecting to Process Engine DB storage.
<b>Action</b>	Refer to the process exception in the Integration Server error logs for details.
<b>PRT.0101.9306</b>	<b>Correlation field {0} does not exist in published document {1}</b>
<b>Explanation</b>	A correlation field is specified for the document starting this step, but the correlation field does not exist in the document at run time.
<b>Action</b>	Ensure that the correlation field is specified in the published document to establish correlation.
<b>PRT.0101.9316</b>	<b>Could not get process ID from conversation ID</b>
<b>PRT.0101.9321</b>	<b>Thread sleep wait interrupted: {0}</b>
<b>PRT.0101.9322</b>	<b>Variable "{0}" does not exist in the pipeline</b>
<b>PRT.0101.9340E</b>	<b>Bad join expression; invalid character {0}</b>
<b>Explanation</b>	The specified character is not allowed in the join expression.
<b>Action</b>	Verify that the join expression is valid.
<b>PRT.0101.9341E</b>	<b>Bad XOR join specification {0}; id required</b>
<b>Explanation</b>	The XOR join expression does not contain an unique ID.
<b>Action</b>	Make sure that a unique ID is present for the XOR join expression.

---

<b>PRT.0101.9342E</b>	<b>Bad XOR join specification; unparseable timeout {0}</b>
<b>Explanation</b>	The timeout value of the XOR join expression is not in a valid format.
<b>Action</b>	Make sure the timeout value for the XOR join expression is in milliseconds.
<b>PRT.0101.9343E</b>	<b>Bad join expression; one or more unmatched )</b>
<b>Explanation</b>	Missing parenthesis in a join expression.
<b>Action</b>	Make sure the join expression is valid.
<b>PRT.0101.9344E</b>	<b>Bad join expression; one or more unmatched (</b>
<b>Explanation</b>	Missing parenthesis in a join expression.
<b>Action</b>	Make sure the join expression is valid.
<b>PRT.0101.9345E</b>	<b>Bad join expression; bad standalone join spec {0}</b>
<b>Explanation</b>	Invalid standalone in a join expression.
<b>Action</b>	Make sure the join expression is valid.
<b>PRT.0101.9346</b>	<b>Global data is no longer supported. Model {0} : SID {1}</b>
<b>PRT.0101.9356E</b>	<b>Can not set track count to {0}; only 1 allowed for TransitionMetaData</b>
<b>Explanation</b>	The track count is not 0 or 1.
<b>Action</b>	Make sure the track count is 0 or 1.
<b>PRT.0101.9358E</b>	<b>Exception while executing SQL statement</b>
<b>Explanation</b>	The SQL processor failed to execute this statement because there is an error in the statement itself - a reference to a non-existent table, a non-existent (misspelled) field, or an incorrect SQL keyword.
<b>Action</b>	Check the process exception message in the Integration Server error logs for details.
<b>PRT.0101.9360</b>	<b>XPath data is no longer supported. Model {0} : SID {1}</b>

**PRT.0101.9412**      **PID {0}: Cannot execute step {1} because the process was terminated already**

**PRT.0101.9417E**      **Cannot publish {0}. Document is not in pipeline.**

**Explanation**      Cannot publish document; the document is not in the pipeline.

**Action**              Check for improper or missing mapping in the Integration Server flow service.

**PRT.0101.9432**      **Task execution was unsuccessful. The task engine returned status: {0} and error message: {1}**

**Explanation**      The Task Engine has returned an error to the Process Engine

**Action**              Check the My webMethods Server logs in  
.. \MWS\server\instances\\logs.

**PRT.0101.9467**      **Cannot enqueue an event with a null ID**

**PRT.0101.9469**      **Error encountered: Document with duplicate correlation ID submitted.**

**PRT.0101.9613**      **There are no enabled Processes matching this trigger: {0}**

**Explanation**      A document has arrived on a subscriptionTrigger but there are no enabled processes associated with this trigger. Therefore, the document is ignored.

**Action**              In most cases this means your process is not enabled. Log in to My webMethods and use webMethods Monitor to select the process and enable it for execution, then try again.

**PRT.0101.9862**      **This service has been deprecated and is no longer supported.**

**Explanation**      The service executed is no longer supported in the current release.

**Action**              Consult the release readme file and the Process Engine Administrator's guide for deprecated and removed services to determine if there is a replacement service.

**PRTEExceptionConstants.EXC\_AA\_CASE\_ERROR – AgileApps returned status: {0} and error message: {1}**

**PRTEExceptionConstants.EXC\_AA\_CASE\_NOCREATE – Case type {0} has circular dependency on Model {1}**

**PRTEExceptionConstants.EXC\_EFORM\_DUP\_FRIENDLYNAME** – Friendly name: {0} already in use please choose another.

**PRTEExceptionConstants.EXC\_FILE\_UTILS\_FILE\_EXISTS** – File "{0}" already exists.

**PRTEExceptionConstants.EXC\_FILE\_UTILS\_VALIDATE\_DIR** – File or directory "{0}" is not in the "{1}" directory.

**PRTEExceptionConstants.EXC\_PT\_JOINTIMEOUT** – The step "{2}" of model "{0}" with process id of "{1}" has join timed out, with no timeout step or error step to process.

**PRTEExceptionConstants.EXC\_SDA\_CA\_DYNAMIC\_DUPLICATE\_FIELD\_ERR** – Dynamic Call Activity document list contains duplicate values for {0} field.

**PRTEExceptionConstants.EXC\_SDA\_CA\_DYNAMIC\_MISSING\_FIELD\_ERR** – Dynamic Call Activity document does not contain {0} field.

**PRTEExceptionConstants.EXC\_SDA\_CA\_DYNAMIC\_MISSING\_ROOT\_DOC\_ERR** – Dynamic Call Activity CallActivityModels document list does not exist.

**PRTEExceptionConstants.EXC\_SD\_CIDLONG2** – The Correlation ID is too long. The length is {0}; maximum allowed is {1}

**PRTEExceptionConstants.EXC\_SM\_FORBID** – PID {0} Cannot restart process; It was initiated from AgileApps

**PRTEExceptionConstants.EXC\_SM\_NOACTFORSTAT...0** – PID {0}; Cannot {1} a process instance with a status of {2}.

**PRTEExceptionConstants.EXC\_TRANSITION\_NOT\_FOUND** – Transition Key {0} could not be found for Process ID {1}.



# 24

## Realtime Monitoring Messages

---

- WEPRME0001**      **The user name must not be null.**
- WEPRME0002**      **The SQL statement must not be null.**
- WEPRME0003**      **The temporal validity approach must not be null.**
- WEPRME0005**      **The class of the user-defined function must not be null.**
- WEPRME0007**      **The database source builder must not be null.**
- WEPRME0008**      **Persistency for a database source is currently not supported.**
- WEPRME0009**      **The class of the database source builder must not be null.**
- WEPRME0010**      **Persistency for tables is currently not supported.**
- WEPRME0011**      **The source adapter must not be null.**

- WEPRME0012**      **The authorization module does not currently support persistency.**
  
- WEPRME0013**      **The source adapter class must not be null.**
  
- WEPRME0014**      **The subscription mode must not be null.**
  
- WEPRME0015**      **The sink adapter must not be null.**
  
- WEPRME0016**      **The unsubscription mode must not be null.**
  
- WEPRME0017**      **The sink adapter class must not be null.**
  
- WEPRME0018**      **The authorization privilege must not be null.**
  
- WEPRME0019**      **{0} because the connection has already been closed.**
  
- WEPRME0020**      **{0} because the connection has been shut down by the server.**
  
- WEPRME0021**      **Unable to close the connection; it has already been shut down by the server.**
  
- WEPRME0022**      **The batch job cannot be started because the connection has been already closed.**
  
- WEPRME0023**      **The batch job is already active.**
  
- WEPRME0024**      **The temporal validity approach {0} requires the use of an instance of SourceAdapter.**
  
- WEPRME0025**      **Unsupported approach: {0}.**

---

WEPRME0026	The temporal validity approach {0} requires the use of an instance of SinkAdapter.
WEPRME0027	The temporal validity approach {0} requires the use of an instance of PnSinkAdapter.
WEPRME0028	The temporal validity approach {0} requires the use of a subclass of SourceAdapter.
WEPRME0029	The temporal validity approach {0} requires the use of a subclass of PnSourceAdapter.
WEPRME0030	The temporal validity approach {0} requires the use of a subclass of SinkAdapter.
WEPRME0031	The temporal validity approach {0} requires the use of a subclass of PnSinkAdapter.
WEPRME0032	The user {0} does not have the privilege to add the query.
WEPRME0033	A user can only add a query to his/her own schema.
WEPRME0034	The user {0} does not have the privilege to use the query.
WEPRME0035	The user {0} does not have the privilege to add the user-defined function.
WEPRME0036	Current system configuration does not support persistency.
WEPRME0037	The user {0} does not have the privilege to remove the user-defined function.
WEPRME0038	The user {0} does not have the privilege to add the database source.
WEPRME0039	The user {0} does not have the privilege to remove the database source.

- WEPRME0040**      **The user {0} does not have the privilege to use the database source.**
  
- WEPRME0041**      **The user {0} does not have the privilege to add the table.**
  
- WEPRME0042**      **The user {0} does not have the privilege to remove the table.**
  
- WEPRME0045**      **The user {0} does not have the privilege to remove the query.**
  
- WEPRME0046**      **The user {0} does not have the privilege to add the subscription.**
  
- WEPRME0047**      **A user can only add a subscription to his/her own schema.**
  
- WEPRME0048**      **The user {0} does not have the privilege to remove the subscription.**
  
- WEPRME0049**      **The user {0} does not have the privilege to use the subscription.**
  
- WEPRME0050**      **The user {0} does not have the privilege to grant the privilege.**
  
- WEPRME0051**      **The user {0} does not have the privilege to revoke the privilege.**
  
- WEPRME0052**      **The user {0} does not have the privilege to check the privilege.**
  
- WEPRME0053**      **The batch job cannot be executed because the connection has been closed.**
  
- WEPRME0054**      **The batch job cannot be executed because the connection has been shut down by the server.**
  
- WEPRME0055**      **No active batch job to execute.**

<b>WEPRME0056</b>	<b>The event engine has already been shut down.</b>
<b>WEPRME0057</b>	<b>An unexpected interrupt has occurred.</b>
<b>WEPRME0059</b>	<b>Calling the push method is not allowed after calling the done method.</b>
<b>WEPRME0060</b>	<b>Calling the heartBeat method is not allowed after calling the done method.</b>
<b>WEPRME0067</b>	<b>Init must be called before opening the adapter.</b>
<b>WEPRME0068</b>	<b>The following command is unknown: {0}.</b>
<b>WEPRME0069</b>	<b>The temporal validity approach {0} requires the use of an instance of PnSourceAdapter.</b>
<b>WEPRME0070</b>	<b>A user can only add a source to his/her own schema.</b>
<b>WEPRME0071</b>	<b>The artefact must not be null.</b>
<b>WEPRME0072</b>	<b>The query identifiers cannot be delivered.</b>
<b>WEPRME0073</b>	<b>The query cannot be prepared.</b>
<b>WEPRME0074</b>	<b>The query cannot be checked.</b>
<b>WEPRME0075</b>	<b>The query properties cannot be retrieved.</b>
<b>WEPRME0076</b>	<b>The server function cannot be registered.</b>

- WEPRME0077**      **The function cannot be deregistered.**
  
- WEPRME0078**      **The server data source cannot be registered.**
  
- WEPRME0079**      **The data source cannot be deregistered.**
  
- WEPRME0080**      **The server table cannot be registered.**
  
- WEPRME0081**      **The table cannot be deregistered.**
  
- WEPRME0082**      **The source cannot be prepared.**
  
- WEPRME0083**      **The query cannot be started.**
  
- WEPRME0084**      **The query cannot be stopped.**
  
- WEPRME0085**      **The sink cannot be subscribed.**
  
- WEPRME0086**      **The sink cannot be unsubscribed.**
  
- WEPRME0087**      **The earliest possible subscription time cannot be determined.**
  
- WEPRME0088**      **The earliest possible unsubscription time cannot be determined.**
  
- WEPRME0089**      **The server sink cannot be subscribed.**
  
- WEPRME0090**      **The server sink cannot be unsubscribed.**

---

<b>WEPRME0091</b>	<b>The privilege cannot be granted.</b>
<b>WEPRME0092</b>	<b>The privilege cannot be revoked.</b>
<b>WEPRME0093</b>	<b>The privilege cannot be checked.</b>
<b>WEPRME0094</b>	<b>The identifiers cannot be retrieved.</b>
<b>WEPRME0095</b>	<b>The registration cannot be checked.</b>
<b>WEPRME0096</b>	<b>The query metadata cannot be delivered.</b>
<b>WEPRME0097</b>	<b>Version mismatch between client and server. Cannot connect to server version {0} using client version {1}. Use a client version between {2} and {3} instead. Your current client version can only connect to server versions between {4} and {5}.</b>
<b>WEPRME0098</b>	<b>Unable to connect to any of the provided servers: {0}.</b>
<b>WEPRME0099</b>	<b>This operation is currently not supported in high availability mode.</b>
<b>WEPRME0100</b>	<b>The query head cannot be retrieved.</b>
<b>WEPRME0101</b>	<b>In high availability mode, this operation is currently only supported using a remote connection.</b>
<b>WEPRME0102</b>	<b>The SQL statement contains syntactical errors.</b>
<b>WEPRME0104</b>	<b>Unrecognized semantic exception. Please report the SQL statement to your software supplier.</b>

- WEPRME0105**      The {0} argument of the {1} aggregation must be numeric.
  
- WEPRME0106**      The types of the arguments of the aggregation do not match the required argument types.
  
- WEPRME0107**      The field {0} is unknown or not visible.
  
- WEPRME0108**      The argument of the ABS function must be numeric.
  
- WEPRME0109**      In the case function, the type of the {0} result expression does not match the types of the previous result expressions ({1}, {2}).
  
- WEPRME0110**      The signature of the user-defined function {0} does not match the specified types ({1}).
  
- WEPRME0111**      The user-defined function {0} is unknown or not visible.
  
- WEPRME0112**      The {0} argument of the {1} must be numeric.
  
- WEPRME0113**      The {0} argument of the {1} must be of character/string type.
  
- WEPRME0114**      The types of the arguments of the operation do not match the required argument types.
  
- WEPRME0115**      The arguments of the {0} comparison cannot be compared ({1}, {2}).
  
- WEPRME0116**      The expression list contains constants of different types.
  
- WEPRME0117**      The types of the expression and the constants in the expression list cannot be compared ({0}, {1}).

---

<b>WEPRME0118</b>	<b>Only expressions and star selections are permitted in a selection list.</b>
<b>WEPRME0119</b>	<b>An aggregate is not allowed inside a WHERE clause.</b>
<b>WEPRME0120</b>	<b>Only expressions are permitted in a GROUP BY clause.</b>
<b>Explanation</b>	The GROUP BY clause contains an entry that is not an expression.
<b>Action</b>	Replace the entry by a valid expression.
<b>WEPRME0121</b>	<b>The {0} constant listed in the set condition must have the same size as the specified field list.</b>
<b>WEPRME0122</b>	<b>The types of the field and the constants in the constant list cannot be compared ({0}, {1}).</b>
<b>WEPRME0123</b>	<b>The source {0} is unknown or not visible.</b>
<b>WEPRME0124</b>	<b>The size of a count-based window must be greater than zero.</b>
<b>Explanation</b>	The query contains an invalid size. This refers to the ROWS argument in an SQL query, or the size attribute of a window element in an XML query.
<b>Action</b>	Specify a valid size.
<b>WEPRME0125</b>	<b>The sliding size specification of a count-based window must be greater than zero.</b>
<b>Explanation</b>	The query contains an invalid sliding size. This refers to the SLIDE argument in an SQL query, or the increment attribute of a window element in an XML query.
<b>Action</b>	Specify a valid sliding size.
<b>WEPRME0126</b>	<b>The duration of a time-based window must be greater than zero.</b>
<b>Explanation</b>	The query contains an invalid duration. This refers to the RANGE argument in an SQL query, or the size attribute of a window element in an XML query.
<b>Action</b>	Specify a valid duration.

<b>WEPRME0127</b>	<b>The sliding size specification of a time-based window must be greater than zero.</b>
<b>Explanation</b>	The query contains an invalid sliding size. This refers to the SLIDE argument in an SQL query, or the increment attribute of a window element in an XML query.
<b>Action</b>	Specify a valid sliding size.
<b>WEPRME0128</b>	<b>The DURATION argument of a MATCHING clause must be greater than zero.</b>
<b>WEPRME0129</b>	<b>The WITHIN argument of a MATCHING clause must be greater than zero.</b>
<b>WEPRME0130</b>	<b>Duplicate definition for the pattern state "{0}".</b>
<b>WEPRME0131</b>	<b>The DEFINE clause does not define all the pattern states required by the specified pattern.</b>
<b>WEPRME0132</b>	<b>The field {0} is already defined by the input query.</b>
<b>WEPRME0133</b>	<b>The type of the defined field and the type of its default value do not match ({0}, {1}).</b>
<b>WEPRME0134</b>	<b>The type of the defined field and the type of the assigned value do not match ({0}, {1}).</b>
<b>WEPRME0135</b>	<b>The field names "START_TIMESTAMP" and "END_TIMESTAMP" are reserved for additional information provided by pattern matching.</b>
<b>WEPRME0136</b>	<b>The identifier for a pattern state must be a single character.</b>
<b>WEPRME0137</b>	<b>An aggregate is not allowed inside the condition in an action definition.</b>
<b>WEPRME0138</b>	<b>The condition of an action definition must be a predicate.</b>

- WEPRME0139**      **An aggregate is not allowed inside an action definition in a MATCHING clause.**
- WEPRME0140**      **The right-hand side of an action definition must be an expression.**
- WEPRME0143**      **Only predicates are permitted in the ON clause of a join.**
- WEPRME0144**      **Only predicates are permitted in a WHERE clause.**
- WEPRME0145**      **The {0} operation requires identical output format of the involved subqueries.**
- WEPRME0146**      **Only predicates are permitted in a disjunction.**
- WEPRME0147**      **Only predicates are permitted in a conjunction.**
- WEPRME0148**      **Only predicates are permitted in a negation.**
- WEPRME0149**      **The EXISTS clause is currently not supported.**
- WEPRME0150**      **An SQL expression list in a relational expression is currently not supported.**
- WEPRME0152**      **Only an expression is permitted as the first argument of a comparison.**
- WEPRME0153**      **Only an expression is permitted as the second argument of a comparison.**
- WEPRME0154**      **Only constants are allowed in the set of an IN clause.**
- WEPRME0155**      **A subquery in an IN clause is currently not supported.**

- WEPRME0156**      Only expressions are permitted as the first argument of a BETWEEN clause.
- WEPRME0157**      Only expressions are permitted as the second argument of a BETWEEN clause.
- WEPRME0158**      The arguments of the BETWEEN clause cannot be compared ({0}, {1}).
- WEPRME0159**      The first argument of the BETWEEN clause is greater than the second argument.
- WEPRME0160**      Only expressions are permitted in the IS NULL clause.
- WEPRME0161**      Only expressions are permitted in {0}.
- WEPRME0162**      Only expressions are permitted in an exponentiation.
- WEPRME0163**      Only expressions are permitted in a unary operation.
- WEPRME0164**      Only expressions are permitted in the WHEN clause of a simple CASE statement.
- WEPRME0165**      Only expressions are permitted in the THEN clause of a simple CASE statement.
- WEPRME0166**      Only expressions are permitted in the ELSE clause of a simple CASE statement.
- WEPRME0167**      Only predicates are permitted in the WHEN clause of a boolean CASE statement.
- WEPRME0168**      Only expressions are permitted in the THEN clause of a boolean CASE statement.
- WEPRME0169**      Only expressions are permitted in the ELSE clause of a boolean CASE statement.

<b>WEPRME0170</b>	<b>Duplicate field definition in recursive query.</b>
<b>WEPRME0171</b>	<b>The number of defined fields in the recursive query does not match the number of fields in the subquery.</b>
<b>WEPRME0172</b>	<b>The defined field name does not match the field name in the subquery.</b>
<b>WEPRME0173</b>	<b>The defined field type does not match the field type in the subquery.</b>
<b>WEPRME0174</b>	<b>Check the specified aggregation.</b>
<b>WEPRME0175</b>	<b>Check the specified SELECT item.</b>
<b>WEPRME0176</b>	<b>Check the specified DEFINE condition.</b>
<b>WEPRME0177</b>	<b>Check the specified action.</b>
<b>WEPRME0178</b>	<b>Check the specified part of the join predicate.</b>
<b>WEPRME0179</b>	<b>Check the specified part of the WHERE clause.</b>
<b>WEPRME0180</b>	<b>The operator type {0} is currently not allowed within a recursive query.</b>
<b>WEPRME0181</b>	<b>The operator type {0} is not allowed within a recursive query.</b>
<b>WEPRME0182</b>	<b>The type {0} is unexpected.</b>
<b>WEPRME0183</b>	<b>The defined field is not null but the field in the subquery is nullable.</b>

- WEPRME0184**      **The input of a window has to be a chronon stream.**
- WEPRME0185**      **The pattern of a MATCHING clause must not be empty.**
- WEPRME0189**      **The base time specification does not represent a valid date/time.**  
**Explanation**      The query contains an invalid base time. This refers to the RELATIVE TO clause in an SQL query, or the relative-to attribute of a window element in an XML query.  
**Action**              Specify a valid base time.
- WEPRME0191**      **The LIKE clause requires a constant string pattern.**
- WEPRME0192**      **Only predicates are permitted in a HAVING clause.**
- WEPRME0194**      **Arrays of type {0} are currently not supported.**
- WEPRME0195**      **Only expressions of type BOOLEAN are allowed in this context but the present type is {0}.**
- WEPRME0196**      **The {0} function only supports FLOAT and DOUBLE values as arguments.**
- WEPRME0197**      **The argument of the CHAR\_LENGTH function must be of string type.**
- WEPRME0198**      **Casting from {0} to {1} is currently not supported.**
- WEPRME0199**      **The argument of the {0} function must be numeric.**
- WEPRME0200**      **The {0} argument of the {1} function must be numeric.**
- WEPRME0201**      **Windows can only be applied to input streams or (sub)queries.**

<b>WEPRME0202</b>	<b>Tried to configure DataSource with unknown connection type {0} in RTM system.</b>
<b>WEPRME0203</b>	<b>Tried to configure unknown database table {0} in RTM system.</b>
<b>WEPRME0204</b>	<b>Cannot find builder class for DataSource configured in RTM system.</b>
<b>WEPRME0205</b>	<b>Cannot call builder class constructor for DataSource configured in RTM system.</b>
<b>WEPRME0206</b>	<b>Cannot access specified database table for DataSource configured in RTM system.</b>
<b>WEPRME0207</b>	<b>Initialization of CONNECT right failed.</b>
<b>WEPRME0208</b>	<b>Unable to initialize privileges for super user.</b>
<b>WEPRME0209</b>	<b>Unable to initialize privileges for monitoring user.</b>
<b>WEPRME0211</b>	<b>Unable to initialize privileges for pre-loaded data sources.</b>
<b>WEPRME0212</b>	<b>Unable to retrieve localhost name.</b>
<b>WEPRME0213</b>	<b>The system is already started.</b>
<b>WEPRME0214</b>	<b>Unable to prepare communication servers.</b>
<b>WEPRME0215</b>	<b>The user cannot be connected as direct connections to this system are currently not allowed.</b>
<b>WEPRME0216</b>	<b>The user cannot be connected as the system is not started.</b>

- WEPRME0217**      **The user cannot be connected as the system is already shut down.**
  
- WEPRME0218**      **The user cannot be connected as the username is unknown or the password is wrong.**
  
- WEPRME0219**      **The user cannot be connected as the connect right is missing.**
  
- WEPRME0220**      **The connection cannot be removed from the system as it is unknown.**
  
- WEPRME0221**      **The system was already shut down.**
  
- WEPRME0222**      **Setting the class loader is only allowed before system start.**
  
- WEPRME0223**      **System is not running in high availability mode.**
  
- WEPRME0224**      **The system does not allow remote connections.**
  
- WEPRME0225**      **Create database allowed only before the system start.**
  
- WEPRME0226**      **Drop database allowed only after system is already shut down.**
  
- WEPRME0228**      **Unable to send synchronous command.**
  
- WEPRME0229**      **Internal error: Callback of class {0} provided to {1} is not an instance of {2}.**
  
- WEPRME0230**      **Status of health check monitor of local system is not OK; shutting down!**
  
- WEPRME0231**      **Unexpected exception in HA ServerConnectionHandler.**

WEPRME0232	Unexpected error occurred when master was driving recovery of slave.
WEPRME0233	Unexpected error occurred when handling recovery request from master.
WEPRME0239	Exception when aborting connection process.
WEPRME0240	Unsupported protocol.
WEPRME0241	No handler registered for protocol {0}.
WEPRME0242	Handshake failed due to an exception.
WEPRME0243	Missing basic properties ({0}) needed to compute composed property.
WEPRME0246	Unexpected role {0}.
WEPRME0247	Received unknown command {0}.
WEPRME0248	The adapter must not be null.
WEPRME0249	The query {0} cannot be stopped as it is still in use by a subquery.
WEPRME0250	The query {0} cannot be stopped as it is still in use by a subscriber.
WEPRME0251	The subscription identifier {0} is already in use for user {1}.
WEPRME0252	The approach ({0}) does not match approach of the query ({1}).

- WEPRME0253**      **The sink cannot be subscribed as the query {0} has not been started.**
  
- WEPRME0254**      **Unable to compute starting point for snapshot-reducible results.**
  
- WEPRME0255**      **Unable to start subscription {0} from {1}.**
  
- WEPRME0256**      **The connection to all servers has been lost.**
  
- WEPRME0257**      **At least one server address has to be provided.**
  
- WEPRME0259**      **Unable to connect to {0} due to incompatible server version.**
  
- WEPRME0260**      **Authentication with remote system failed.**
  
- WEPRME0261**      **Inconsistent high availability mode of servers.**
  
- WEPRME0262**      **The source cannot be prepared as the query identifier {0}.{1} is already in use.**
  
- WEPRME0263**      **Unable to parse the given SQL statement: {0}.**
  
- WEPRME0264**      **Unable to compute property: {0}.**
  
- WEPRME0265**      **The query cannot be prepared as the query identifier {0} is already in use.**
  
- WEPRME0266**      **The query {0} cannot be started as it is already closed.**
  
- WEPRME0267**      **The query {0} cannot be started as it is not yet initialized.**

---

WEPRME0268	The mode {0} is not allowed for server subscriptions.
WEPRME0269	Persistent server subscriptions are only allowed with start time Long.MIN_VALUE.
WEPRME0270	Client subscription may not be unsubscribed using serverUnsubscribe - use unsubscribe.
WEPRME0271	Server subscription may not be unsubscribed using unsubscribe - use serverUnsubscribe.
WEPRME0272	Unable to stop subscription {0} from {1}.
WEPRME0273	A user-defined function factory is already registered for {0}.{1}.
WEPRME0274	No user-defined function is registered for {0}.{1}.
WEPRME0275	A data source is already registered for {0}.{1}.
WEPRME0276	A table is already registered for {0}.{1}.
WEPRME0277	No data source is registered for {0}.{1}.
WEPRME0278	No table is registered for {0}.{1}.
WEPRME0279	Subscription start point may only be computed for running queries.
WEPRME0280	The query identifier {0} is unknown.
WEPRME0281	Only numeric, string and date/time values can be used with {0} aggregation.

- WEPRME0282** Only numeric values can be used with {0} aggregation.
- WEPRME0285** Unknown aggregation type {0}.
- WEPRME0286** A {0} aggregate must have exactly one sub-expression.
- WEPRME0287** A {0} aggregate must not have more than one sub-expression.
- WEPRME0288** Only numeric, string and date/time values can be used with maximum/minimum aggregation.
- WEPRME0289** Only numeric values can be used with sum aggregation.
- WEPRME0292** An exception occurred during batch execution.
- WEPRME0293** Client did not provide valid number of supported stream protocols.
- WEPRME0294** No stream protocol requested by the client is supported.
- WEPRME0295** None of the proposed stream protocols is supported by the server.
- WEPRME0296** The stream protocol requested by the server is not supported.
- WEPRME0297** An exception occurred while sending a command.
- WEPRME0298** Registration of new protocol mappings is only allowed before starting.
- WEPRME0299** Starting may be done only once.

---

WEPRME0300	A yet unknown version.
WEPRME0301	An error occurred while parsing {0} and converting it to the target date format.
WEPRME0302	Unable to determine own address.
WEPRME0303	The protocol {0} requires a serializer for complex {1} which is not available at the server.
WEPRME0304	The protocol {0} requires a serializer for complex {1} which is not available at the client.
WEPRME0305	Unknown protocol {0}.
WEPRME0306	There is no handler registered under identifier {0} for protocol {1}.
WEPRME0307	A subscription to query {0} cannot be established as it has been configured to be non-subscribable.
WEPRME0308	The query with identifier {0}.{1} is not a connectable source.
WEPRME0309	Wrong approach: {0} (expected {1}).
WEPRME0310	Unknown command for system operation:{0}.
WEPRME0311	Unable to execute lock command on slave.
WEPRME0312	Execution of command on slave causes exception.

- WEPRME0313**      **Unable to sync command with slave.**
  
- WEPRME0314**      **Only the owner of a source may disconnect from it.**
  
- WEPRME0315**      **Only the owner of a source may connect to it.**
  
- WEPRME0316**      **The dynamic protocol handler could not be connected.**
  
- WEPRME0317**      **The dynamic protocol adapter must not be null.**
  
- WEPRME0318**      **Master result to slave communicators may only be added before the system is started.**
  
- WEPRME0319**      **Unable to grant rights to subscribe to HA difference to user.**
  
- WEPRME0320**      **Unable to execute recover command on slave.**
  
- WEPRME0321**      **Unable to retrieve health information from master.**
  
- WEPRME0322**      **Unable to retrieve health information from client.**
  
- WEPRME0323**      **Connection to HA partner system timed out.**
  
- WEPRME0324**      **There is already a class {0} bound.**
  
- WEPRME0325**      **This callback is already disconnected.**
  
- WEPRME0326**      **Unable to store entry of class {0} in repository.**

---

WEPRME0327	The repository already contains an artefact of type {0} for {1}.{2}.
WEPRME0328	Repository error: the entry to retrieve is unknown.
WEPRME0329	Repository error: the entry to remove is unknown.
WEPRME0330	Repository error: unknown subscription.
WEPRME0331	Repository does not contain an artefact of type {0} with owner {1} and identifier {2} or it might not be accessed.
WEPRME0332	Loading repository from database failed.
WEPRME0333	Unable to access notification dispatcher of underlying local connection as remote connection is not yet authenticated.
WEPRME0334	The user-defined aggregation function must not be null.
WEPRME0335	The class of the user-defined aggregation function adapter must not be null.
WEPRME0337	The server user-defined aggregation function cannot be registered.
WEPRME0338	The user-defined aggregation function cannot be registered.
WEPRME0339	The user-defined aggregation function cannot be deregistered.
WEPRME0340	The user-defined operator adapter factory must not be null.
WEPRME0341	The class of the user-defined operator adapter factory must not be null.

- WEPRME0342**      **Persistency for user-defined operators is currently not supported.**
  
- WEPRME0343**      **The server user-defined operator cannot be registered.**
  
- WEPRME0344**      **The user-defined operator cannot be registered.**
  
- WEPRME0345**      **The user-defined operator cannot be deregistered.**
  
- WEPRME0346**      **The user {0} does not have the privilege to add the user-defined aggregation function.**
  
- WEPRME0347**      **The user {0} does not have the privilege to remove the user-defined aggregation function.**
  
- WEPRME0348**      **The user {0} does not have the privilege to add the user-defined operator.**
  
- WEPRME0349**      **The user {0} does not have the privilege to remove the user-defined operator.**
  
- WEPRME0350**      **An user-defined aggregation function is already registered for {0}.{1}.**
  
- WEPRME0351**      **No user-defined aggregation function is registered for {0}.{1}.**
  
- WEPRME0352**      **A user-defined operator is already registered for {0}.{1}.**
  
- WEPRME0353**      **No user-defined operator is registered for {0}.{1}.**
  
- WEPRME0354**      **Only expressions are permitted as argument of {0} functions.**
  
- WEPRME0355**      **Only expressions are permitted as {0} argument of {1} functions.**

---

WEPRME0356	The connected system does not support the registration of user-defined aggregation functions.
WEPRME0357	The connected system does not support the deregistration of user-defined aggregation functions.
WEPRME0358	The connected system does not support the registration of user-defined operators.
WEPRME0359	The connected system does not support the deregistration of user-defined operators.
WEPRME0361	Unable to create instance of {0}.
WEPRME0367	The parameter type number {0} of a user-defined operator adapter factory for {1},{2} must not be null.
WEPRME0370	Unable to find class {0}.
WEPRME0371	The method name {0} is not unique in class {1}.
WEPRME0372	The method {0} is not declared in class {1}.
WEPRME0373	Methods using varargs are not supported.
WEPRME0374	The method {0} is not static.
WEPRME0375	The method {0} is not public.
WEPRME0376	The return type {0} of method {1} is not supported.

<b>WEPRME0377</b>	<b>The parameter type {0} of method {1} is not supported.</b>
<b>WEPRME0378</b>	<b>The method has been called with wrong parameters.</b>
<b>WEPRME0379</b>	<b>The method is not accessible.</b>
<b>WEPRME0380</b>	<b>The method cannot be invoked.</b>
<b>WEPRME0381</b>	<b>Wrong number of parameters.</b>
<b>WEPRME0383</b>	<b>Unable to invoke {0}.</b>
<b>WEPRME0385</b>	<b>Unable to determine parameter types.</b>
<b>WEPRME0386</b>	<b>Unable to determine output metadata.</b>
<b>WEPRME0387</b>	<b>Unable to access {0}.</b>
<b>WEPRME0388</b>	<b>No such method available: {0}.</b>
<b>WEPRME0389</b>	<b>Return type of method {0} must be StreamMetaData.</b>
<b>WEPRME0390</b>	<b>Return type of method {0} must be JavaTypes.Type.</b>
<b>WEPRME0391</b>	<b>Unable to access constructor.</b>
<b>WEPRME0392</b>	<b>No valid constructor available.</b>

<b>WEPRME0393</b>	<b>Wrong parameters: use class name and method names.</b>
<b>WEPRME0394</b>	<b>The {0} method must have at least two parameters.</b>
<b>WEPRME0400</b>	<b>The user-defined operator {0} is unknown or not visible.</b>
<b>WEPRME0401</b>	<b>The parameter type {0} must be the same as value parameter type of {1}.</b>
<b>WEPRME0406</b>	<b>The statements are not initialized.</b>
<b>WEPRME0407</b>	<b>The statements have to be initialized first.</b>
<b>WEPRME0408</b>	<b>This statement is not available.</b>
<b>WEPRME0409</b>	<b>The operation removeAll is not supported.</b>
<b>WEPRME0410</b>	<b>The operation removeAndReturn is currently not supported.</b>
<b>WEPRME0411</b>	<b>Elements are already removed by next.</b>
<b>WEPRME0412</b>	<b>{0} is not contained.</b>
<b>WEPRME0413</b>	<b>Calling the method getMinTimeStamp only supported in ordered remove mode.</b>
<b>WEPRME0414</b>	<b>Structure is empty.</b>
<b>WEPRME0415</b>	<b>The only supported key is key 0.</b>

- WEPRME0416**      **Not possible as heap is consuming.**
  
- WEPRME0417**      **Remove is always done.**
  
- WEPRME0418**      **The initial list has to be empty.**
  
- WEPRME0419**      **The length of the specified byte array does not match the length of the serialized byte array.**
  
- WEPRME0420**      **The given text node does not contain a single character.**
  
- WEPRME0421**      **The given node cannot be read.**
  
- WEPRME0422**      **The end of file has been reached before record metadata could be read completely.**
  
- WEPRME0423**      **The number of column names and column types differ.**
  
- WEPRME0424**      **The value contains more than one character.**
  
- WEPRME0425**      **The value is not in JDBC time escape format or null.**
  
- WEPRME0426**      **The value is not in JDBC date escape format or null.**
  
- WEPRME0427**      **The character encoding {0} is not supported.**
  
- WEPRME0428**      **The class of the serialized object was not found.**
  
- WEPRME0429**      **The class used by serialization is invalid.**

---

WEPRME0430	The input stream is corrupt.
WEPRME0431	The input stream consists of primitive data instead of objects.
WEPRME0432	An input/output error has occurred.
WEPRME0433	Writing a serializable object to a string failed due to I/O error.
WEPRME0434	Writing a serializable object to a string failed due to security problems.
WEPRME0435	Writing a serializable object to a string failed due to output stream being null.
WEPRME0436	NULL as null code is not allowed.
WEPRME0437	The end of file has been reached before record could be read completely.
WEPRME0438	The number of values differs from record metadata definition (expecting {0} but found {1}).
WEPRME0439	The index referring to the local error array is out of bounds.
WEPRME0440	The value for column {0} ({1}) must not be null.
WEPRME0442	No error at index {0} in the local error array.
WEPRME0443	The length of the specified byte array does not match the length of the serialized double array.
WEPRME0444	The length of the specified byte array does not match the length of the serialized long array.

- WEPRME0445**      **The class of the object to be read cannot be found ({0}).**
  
- WEPRME0446**      **The length of the specified byte array does not match the length of the serialized String array.**
  
- WEPRME0447**      **This serializer does not support the restoring of objects.**
  
- WEPRME0448**      **Unsupported type code: {0}.**
  
- WEPRME0449**      **Unsupported type name: {0}.**
  
- WEPRME0450**      **Unsupported type: {0}.**
  
- WEPRME0451**      **Types may not be null.**
  
- WEPRME0452**      **Unsupported Java type: {0} ({1}).**
  
- WEPRME0453**      **Unsupported SQL type: {0}.**
  
- WEPRME0454**      **Negative iterator only supported if negative counts are not.**
  
- WEPRME0455**      **Call to next while not hasNext.**
  
- WEPRME0456**      **The distinctIterator is not supported if negative counts are allowed.**
  
- WEPRME0457**      **Queue is empty.**
  
- WEPRME0458**      **Pos={0}, size={1}.**

---

WEPRME0459	Operation results in negative value.
WEPRME0460	Negative value.
WEPRME0461	The argument is not an array.
WEPRME0462	The argument is not a wrapper array.
WEPRME0463	SingleObjectList already contains an object.
WEPRME0464	SingleObjectList only supports index 0.
WEPRME0465	SingleObjectList already may only contain one object.
WEPRME0466	This list is empty.
WEPRME0467	SingleObjectList does not support subList.
WEPRME0468	A time period with non-constant time unit (day, week, month and year) must not be greater than {0}.
WEPRME0469	The size in milliseconds of the time period can only be calculated for constant time periods.
WEPRME0470	Composite metadata already contains specified metadata fragment "{0}".
WEPRME0471	Some metadata fragments cannot be added to composite metadata:{0}.
WEPRME0472	Composite metadata does not contain specified metadata "{0}".

- WEPRME0473**      **User {0} is already subscribed to {1}.**
  
- WEPRME0474**      **Identifier {0} is not supported.**
  
- WEPRME0475**      **Unable to subscribe to {0} due to failed subscription to dependent metadata: {1}.**
  
- WEPRME0476**      **User {0} is not subscribed to {1}.**
  
- WEPRME0477**      **Unexpected parameter {0}=>{1}.**
  
- WEPRME0478**      **Illegal parameter type! Expected {0}, found {1}.**
  
- WEPRME0479**      **Missing parameter(s): {0}.**
  
- WEPRME0480**      **Double metadata update - this should not appear in current update mechanism.**
  
- WEPRME0481**      **Transparent composite metadata does not contain specified metadata "{0}" as a direct fragment, hence it cannot be removed.**
  
- WEPRME0482**      **Requested point is not part of the domain.**
  
- WEPRME0483**      **Empty domain.**
  
- WEPRME0484**      **New domain ({0},{1}) has to be contained in old one ({2},{3}).**
  
- WEPRME0485**      **Range out of domain.**
  
- WEPRME0486**      **From==to but fromFactor != toFactor.**

<b>WEPRME0487</b>	<b>New domain has to be contained in old one.</b>
<b>WEPRME0488</b>	<b>Bound out of domain.</b>
<b>WEPRME0489</b>	<b>A weight has to be given for each function.</b>
<b>WEPRME0490</b>	<b>Functions do not have a common domain.</b>
<b>WEPRME0491</b>	<b>Parse error at position {0}, cause: {1}.</b>
<b>WEPRME0492</b>	<b>Syntax not supported.</b>
<b>WEPRME0493</b>	<b>Unexpected end of regular expression.</b>
<b>WEPRME0494</b>	<b>Missing number in count expression.</b>
<b>WEPRME0495</b>	<b>Non-digit in count expression.</b>
<b>WEPRME0496</b>	<b>Empty (sub) expression.</b>
<b>WEPRME0497</b>	<b>Range error.</b>
<b>WEPRME0498</b>	<b>Count value is 0.</b>
<b>WEPRME0499</b>	<b>Right parenthesis without matching left parenthesis.</b>
<b>WEPRME0500</b>	<b>Left parenthesis without matching right parenthesis.</b>

- WEPRME0501**      **Negative call on empty state.**
  
- WEPRME0502**      **Wrong number of parameters.**
  
- WEPRME0503**      **Empty state.**
  
- WEPRME0504**      **The switch function does not contain a function for the given identifier and no default function is specified.**
  
- WEPRME0505**      **Too many parameters fixed.**
  
- WEPRME0506**      **Inconsistent length of arguments.**
  
- WEPRME0507**      **Indices have to be in ascending order.**
  
- WEPRME0508**      **{0} cannot be used as result type for conversion.**
  
- WEPRME0509**      **This UserDefinedOperator has too many inputs. Maximum expected: {0}. Found: {1},{2}**
  
- WEPRME0510**      **This UserDefinedOperator is missing inputs. Minimum expected: {0}. Found: {1},{2}**
  
- WEPRME0511**      **TableName has to be provided.**
  
- WEPRME0512**      **Map has to be provided.**
  
- WEPRME0513**      **Error reading file.**
  
- WEPRME0514**      **Read line does not match the expected format (check number of rows and row delimiter).**

---

WEPRME0515	A method responsible for updating a structure was called in a class which does not support updates.
WEPRME0516	ResultSet does not provide row {0}.
WEPRME0517	File {0} cannot be written.
WEPRME0518	Row names must not be null.
WEPRME0519	Error parsing date {0}.
WEPRME0520	No update necessary after delete.
WEPRME0521	At least one row has to be mapped.
WEPRME0522	A required value is missing in the given line.
WEPRME0523	Between line {0} and {1} : {2}.
WEPRME0524	Line {0} : {1}.
WEPRME0525	Number of successful commands must not be negative.
WEPRME0526	At least one supported stream protocol has to be provided.
WEPRME0527	CreateArray only works for complex array types, not for {0}.
WEPRME0528	Unsupported type {0}.

- WEPRME0529**      **[This Error replaces a {0} which is not available to the class loader.] {1}.**
  
- WEPRME0530**      **[This RuntimeException replaces a {0} which is not available to the class loader.] {1}.**
  
- WEPRME0531**      **Unable to serialize Object.**
  
- WEPRME0532**      **Unsupported modifier.**
  
- WEPRME0533**      **Unable to deserialize Object.**
  
- WEPRME0534**      **Channel is already closed!**
  
- WEPRME0535**      **The null communication type should not be sent.**
  
- WEPRME0536**      **Java serialization is not supported. Use ObjectOutputStreamCommunication if needed.**
  
- WEPRME0537**      **Unsupported type {0}.**
  
- WEPRME0538**      **Unsupported type.**
  
- WEPRME0539**      **Exception while receiving {0}.**
  
- WEPRME0540**      **Communication type must not be null.**
  
- WEPRME0541**      **Factory parameters must not be null.**
  
- WEPRME0542**      **Unable to create server on address other than local address.**

---

WEPRME0543	Unable to resolve {0}.
WEPRME0544	Unsupported CommunicationType: {0}.
WEPRME0545	Could not receive answer as receiving was interrupted.
WEPRME0546	Could not receive answer as connection was closed due to an exception.
WEPRME0547	Requests must not use ResponseStatus.
WEPRME0548	Exception while handling async command ({0}).
WEPRME0549	More than one ID is not supported yet.
WEPRME0550	No command handler registered for ID {0}.
WEPRME0551	Command {0} sent by wrong side of communication.
WEPRME0552	Command {0} is asynchronous.
WEPRME0553	Command {0} is synchronous.
WEPRME0554	Wrong protocol, expected {0} but received unknown protocol ID {1}.
WEPRME0555	Wrong protocol, expected {0} but received {1}.
WEPRME0556	Wrong magic value for protocol {0}.

WEPRME0557	Protocol must not be null.
WEPRME0558	Uninitialized composite serializer for {0}.
WEPRME0559	Registration not possible after shutdown.
WEPRME0560	There is no address registered for handling protocol {0}.
WEPRME0561	There is already a handler registered for protocol {0}.
WEPRME0562	There is no handler registered for protocol {0}.
WEPRME0563	Unable to shut down server at {0}.
WEPRME0564	Unable to shut down {0} communication servers.
WEPRME0565	Compatibility matrix has to be provided.
WEPRME0566	Duplicate ID{0}.
WEPRME0567	No request types provided for {0}.
WEPRME0568	No respond types provided for {0}.
WEPRME0569	Unknown command ID: {0}.
WEPRME0570	Missing serializer for complex {0}.

---

<b>WEPRME0571</b>	<b>Parameter has to specify a directory.</b>
<b>WEPRME0572</b>	<b>Channel is already closed!</b>
<b>WEPRME0573</b>	<b>Unable to read communication server index file {0}.</b>
<b>WEPRME0574</b>	<b>Unable to start communication server on directory {0}.</b>
<b>WEPRME0575</b>	<b>Unable to create communication server index file {0}.</b>
<b>WEPRME0576</b>	<b>The stream protocol requested by the client is not supported.</b>
<b>WEPRME0577</b>	<b>The stream protocol {0} requested by the client is not supported.</b>
<b>WEPRME0578</b>	<b>Exception while closing streams.</b>
<b>WEPRME0579</b>	<b>Unable to accept a new connection in the specified time.</b>
<b>WEPRME0580</b>	<b>No server present at {0} .</b>
<b>WEPRME0581</b>	<b>File instead of directory found at server address {0}.</b>
<b>WEPRME0582</b>	<b>Unknown stream protocol: {0}.</b>
<b>WEPRME0583</b>	<b>Unable to connect to {0}.</b>
<b>WEPRME0584</b>	<b>Unable to close socket.</b>

- WEPRME0585**      **Protocol handler must not be null.**
  
- WEPRME0586**      **There was already a handler registered for protocol {0}.**
  
- WEPRME0587**      **There was already a handler registered.**
  
- WEPRME0588**      **The handler to register does not handle the correct protocol {0}.**
  
- WEPRME0589**      **This server does not support protocol type {0}.**
  
- WEPRME0590**      **Unable to start communication server on port {0}.**
  
- WEPRME0591**      **Unable to close server socket.**
  
- WEPRME0592**      **Unable to connect to {0};{1}.**
  
- WEPRME0593**      **Unable to initialize cache.**
  
- WEPRME0594**      **Cache already exists but with another end timestamp.**
  
- WEPRME0595**      **Unable to remove the specified cache.**
  
- WEPRME0596**      **New SerialBlob(..) threw SerialException.**
  
- WEPRME0597**      **New SerialBlob(..) threw SQLException.**
  
- WEPRME0598**      **Write(Element,Node) needs operator, expression or predicate.**

WEPRME0599	Node conversion not implemented for type {0} and sub-type {1}.
WEPRME0600	Unsupported constant type: {0}.
WEPRME0601	Outer semi join.
WEPRME0602	Non-constant unit in time shift.
WEPRME0603	Expression wrapped by this predicate is not of type BOOLEAN.
WEPRME0604	Only expressions can be used as boolean expressions.
WEPRME0605	A boolean expression must not have any sub-predicates.
WEPRME0606	Argument types cannot be compared with {0}.
WEPRME0607	Only expressions can be used as arguments of a comparison predicate.
WEPRME0608	Second parameter of LIKE has to be a constant.
WEPRME0609	Second parameter of LIKE has to be a String.
WEPRME0610	Invalid operator [{0}].
WEPRME0611	A comparison predicate must not have any sub-predicates.
WEPRME0612	The comparison predicate's arguments are not comparable.

- WEPRME0613**      **Incomparable Java type {0}.**
  
- WEPRME0614**      **The state of the logical constant is unknown.**
  
- WEPRME0615**      **A logical constant must not have any sub-predicates.**
  
- WEPRME0616**      **Unknown logical constant type {0}.**
  
- WEPRME0617**      **The logical operation type {0} is currently not supported.**
  
- WEPRME0618**      **Illegal member specification.**
  
- WEPRME0619**      **Illegal set specification.**
  
- WEPRME0620**      **Types of member and set are not comparable.**
  
- WEPRME0621**      **Illegal subpredicate.**
  
- WEPRME0622**      **Unknown logical operation type {0}.**
  
- WEPRME0623**      **Only predicates can be used as child nodes of a logical operation predicate.**
  
- WEPRME0624**      **Only operators can be used as sets of an exists predicate.**
  
- WEPRME0625**      **Only expressions can be used as expression of an in predicate.**
  
- WEPRME0626**      **Only operators can be used as sets of an in predicate.**

WEPRME0627	A logical (boolean) IN operator must not have any sub-predicates.
WEPRME0628	A logical (boolean) IN operator does not yet support subqueries.
WEPRME0629	A logical (boolean) NOT must have exactly one sub-predicate.
WEPRME0630	A logical (boolean) NOT must not have more than one sub-predicate.
WEPRME0631	Unknown logical operation type {0}.
WEPRME0632	Unknown aggregation operator mode {0}.
WEPRME0633	Only predicates can be used as filter predicate nodes of an aggregation operator.
WEPRME0634	Only operators can be used as child nodes of an aggregation operator.
WEPRME0635	An aggregation operator must have exactly one input operator.
WEPRME0636	An aggregation operator must not have more than one input operator.
WEPRME0637	Aggregation is currently not supported within recursive PN queries.
WEPRME0638	Unsupported target approach: {0}.
WEPRME0640	Unknown aggregation operator mode {0}.
WEPRME0641	A distinct operator must have exactly one operator.

- WEPRME0642**      **A distinct operator must not have more than one input operator.**
  
- WEPRME0643**      **Unknown distinct operator mode {0}.**
  
- WEPRME0644**      **Empty enumeration.**
  
- WEPRME0645**      **Enumeration contains constants of different types.**
  
- WEPRME0646**      **An enumeration operator must not have any input operators.**
  
- WEPRME0647**      **An enumeration operator provides a set of constants as subquery-replacement for the use in IN-predicates, hence no active enumeration operators are possible.**
  
- WEPRME0649**      **The specified object is not of the expected type; {0}.**
  
- WEPRME0650**      **ActionMapFormat.parseActionMap(String) failed.**
  
- WEPRME0651**      **Only operators can be used as child nodes of an equivalence operator.**
  
- WEPRME0652**      **The chosen query plan (operator at index {0}) does not exist.**
  
- WEPRME0653**      **The relational metadata of the operator node's children does not fit.**
  
- WEPRME0654**      **The operator node has no children.**
  
- WEPRME0655**      **Only operators can be used as child nodes of an except/minus operator.**
- Explanation**      An except/minus operator must have exactly two input operators, which provide the input events for the except operator. The except/minus operator returns all events of the first input stream that are not in the second input stream. This means that only the events that are different are returned.
- Action**            Connect exactly two operators as input of the except/minus operator.

---

<b>WEPRME0656</b>	<b>An except/minus operator must have exactly two input operators.</b>
<b>Explanation</b>	An except/minus operator must have exactly two input operators, which provide the input events for the except operator. The except/minus operator returns all events of the first input stream that are not in the second input stream. This means that only the events that are different are returned.
<b>Action</b>	Connect exactly two operators as input of the except/minus operator.
<b>WEPRME0657</b>	<b>An except/minus operator must not have more than two input operators.</b>
<b>Explanation</b>	An except/minus operator must have exactly two input operators, which provide the input events for the except operator. The except/minus operator returns all events of the first input stream that are not in the second input stream. This means that only the events that are different are returned.
<b>Action</b>	Connect exactly two operators as input of the except/minus operator.
<b>WEPRME0658</b>	<b>Unknown except/minus operator mode {0}.</b>
<b>WEPRME0659</b>	<b>Passive operators does not have chronon stream properties.</b>
<b>WEPRME0660</b>	<b>I/O exception occurred during metadata construction: "{0}".</b>
<b>WEPRME0661</b>	<b>Only column expressions specified by a single column name can be used as timestamp columns of a file operator.</b>
<b>WEPRME0662</b>	<b>Only operators can be used as child nodes of an output file operator.</b>
<b>WEPRME0663</b>	<b>An input-file operator must not have any input operators.</b>
<b>WEPRME0664</b>	<b>File not found: {0}.</b>
<b>WEPRME0665</b>	<b>Unable to read file header.</b>

- WEPRME0666**      **Time information must have a reference timestamp.**
  
- WEPRME0667**      **Time information must not have any additional timestamps.**
  
- WEPRME0668**      **Unknown file operator mode {0}.**
  
- WEPRME0669**      **An output-file operator must have exactly one input operator.**
  
- WEPRME0670**      **An output-file operator must not have more than one input operator.**
  
- WEPRME0671**      **For storing time intervals the names of the columns storing the start and an end timestamp are required.**
  
- WEPRME0672**      **File writing currently unsupported.**
  
- WEPRME0673**      **Unknown file operator type {0}.**
  
- WEPRME0674**      **Only operators can be used as child nodes of a selection operator.**
  
- WEPRME0675**      **A selection operator must have exactly one input operator.**
  
- WEPRME0676**      **A selection operator must not have more than one input operator.**
  
- WEPRME0677**      **Unknown identity operator mode {0}.**
  
- WEPRME0678**      **Only operators can be used as child nodes of an intersection operator.**
  
- WEPRME0679**      **An intersect operator must have exactly two input operators.**

---

<b>WEPRME0680</b>	<b>An intersect operator must not have more than two input operators.</b>
<b>WEPRME0681</b>	<b>Unknown target approach {0}.</b>
<b>WEPRME0682</b>	<b>Unknown intersect operator mode {0}.</b>
<b>WEPRME0683</b>	<b>Only operators can be used as child nodes of a join operator.</b>
<b>WEPRME0684</b>	<b>Only predicates can be used as condition of a theta join operator.</b>
<b>WEPRME0685</b>	<b>A join operator must have at least two input operators.</b>
<b>WEPRME0686</b>	<b>Implementations of multiway join are currently not supported, i.e., they must be transformed to join plans of binary joins using the query optimizer.</b>
<b>WEPRME0687</b>	<b>Implementations of outer joins are currently not supported.</b>
<b>WEPRME0688</b>	<b>Implementations of semi joins are currently not supported.</b>
<b>WEPRME0689</b>	<b>Implementations of joins between active and passive source are currently not supported.</b>
<b>WEPRME0690</b>	<b>Unknown join type {0}.</b>
<b>WEPRME0693</b>	<b>Unknown join mode {0}.</b>
<b>WEPRME0694</b>	<b>Implementations of natural joins without common attributes between active and passive sources are currently not supported.</b>

- WEPRME0695**      **Columns named by {0} cannot be unified because of different types.**
  
- WEPRME0696**      **Column failure.**
  
- WEPRME0697**      **Only operators can be used as child nodes of a mapping operator.**
  
- WEPRME0698**      **A mapping operator must have exactly one input operator.**
  
- WEPRME0699**      **A mapping operator must not have more than one input operator.**
  
- WEPRME0700**      **Unknown mapping operator mode {0}.**
  
- WEPRME0701**      **Some pattern variables are undefined.**
  
- WEPRME0702**      **Only constants can be used as initial values of a matching operator's MEASURE clause.**
  
- WEPRME0703**      **Only columns can be used in a matching operator's PARTITION BY part.**
  
- WEPRME0704**      **Only predicates can be used in the AS part of a matching operator's DEFINE clause.**
  
- WEPRME0705**      **Only columns can be used on the left side of a DO part of a matching operator's DEFINE clause.**
  
- WEPRME0706**      **Only expressions can be used on the right side of a DO part of a matching operator's DEFINE clause.**
  
- WEPRME0707**      **Only operators can be used as child nodes of a matching operator.**

WEPRME0708	A pattern matcher must have exactly one input operator.
WEPRME0709	A pattern matcher must have a synthetic input representing the underlying NFA's state.
WEPRME0710	A pattern matcher must not have more than two input operators.
WEPRME0712	{0} mode not supported.
WEPRME0713	Unknown selection operator mode {0}.
WEPRME0714	The relational metadata of the operator node's children does not fit.
WEPRME0715	The operator node has no children.
WEPRME0716	Only operators can be used as child nodes of a projection operator.
WEPRME0717	A projection operator must have exactly one input operator.
WEPRME0718	A projection operator must not have more than one input operator.
WEPRME0719	Unknown projection operator mode {0}.
WEPRME0720	Unsupported data type.
WEPRME0721	A random operator must not have any input operators.
WEPRME0722	Random sources are currently not supported for target approach: {0}.

- WEPRME0723**      **Unknown random operator mode {0}.**
  
- WEPRME0724**      **Unknown content.**
  
- WEPRME0725**      **Ambiguous content.**
  
- WEPRME0726**      **Only operators can be used as child nodes of a recursion operator.**
  
- WEPRME0727**      **A recursion operator must have exactly one input operator.**
  
- WEPRME0728**      **A recursion operator must not have more than one input operator.**
  
- WEPRME0729**      **The use of recursion operators inside the cursor algebra is currently not supported.**
  
- WEPRME0730**      **Unknown recursion operator mode {0}.**
  
- WEPRME0731**      **Only operators can be used as child nodes of a renaming operator.**
  
- WEPRME0732**      **A renaming operator must have exactly one input operator.**
  
- WEPRME0733**      **A renaming operator must not have more than one input operator.**
  
- WEPRME0734**      **Unknown renaming operator mode {0}.**
  
- WEPRME0735**      **A repository entry operator must not have any input operators.**
  
- WEPRME0736**      **A repository entry operator with name {0} for user {1} is unknown.**

<b>WEPRME0737</b>	<b>A subquery using the approach {0} cannot be used in a query compiled for the approach {1}.</b>
<b>WEPRME0738</b>	<b>Only predicates can be used as condition of a selection operator.</b>
<b>WEPRME0739</b>	<b>Only operators can be used as child nodes of a selection operator.</b>
<b>WEPRME0740</b>	<b>A selection operator must have exactly one input operator.</b>
<b>WEPRME0741</b>	<b>A selection operator must not have more than one input operator.</b>
<b>WEPRME0742</b>	<b>Unknown selection operator mode {0}.</b>
<b>WEPRME0743</b>	<b>No value columns specified.</b>
<b>WEPRME0744</b>	<b>Wrong number of fields in value {0} (expected {1}, found {2}).</b>
<b>WEPRME0745</b>	<b>For exact matches exactly one count argument must be specified.</b>
<b>WEPRME0746</b>	<b>For maximum matches exactly one count argument must be specified.</b>
<b>WEPRME0747</b>	<b>For minimum matches exactly one count argument must be specified.</b>
<b>WEPRME0748</b>	<b>For range matches exactly two count arguments must be specified.</b>
<b>WEPRME0749</b>	<b>Only operators can be used as child nodes of a set operator.</b>
<b>WEPRME0750</b>	<b>A set operator must have exactly one input operator.</b>

- WEPRME0751**      **A set operator must not have more than one input operator.**
- WEPRME0752**      **The defined field list and the specified values are not comparable.**
- WEPRME0753**      **Unknown mode {0}.**
- WEPRME0755**      **Unknown selection operator mode {0}.**
- WEPRME0756**      **Only operators can be used as child nodes of an output socket operator.**
- WEPRME0757**      **A input-socket operator must not have any input operators.**
- WEPRME0758**      **At this point a source reading its data from a socket channel to {0}@{1}:{2} should be returned.**
- WEPRME0759**      **An output-socket operator must have exactly one input operator.**
- WEPRME0760**      **An output-socket operator must not have more than one input operator.**
- WEPRME0761**      **At this point a sink writing the data received from {0} to a socket channel available at {1}@{2}:{3} should be returned.**
- WEPRME0762**      **Unknown socket type {0}.**
- WEPRME0763**      **The use of sockets inside the cursor algebra is currently not supported.**
- WEPRME0764**      **Unknown socket operator mode {0}.**
- WEPRME0765**      **Local metadata fragment identified by {0} cannot be created because of multiple fields matching the field name pattern.**

<b>WEPRME0766</b>	<b>Local metadata fragment identified by {0} cannot be created because no available field matches the field name pattern.</b>
<b>WEPRME0767</b>	<b>This exception is thrown to avoid the creation of a new metadata fragment.</b>
<b>WEPRME0768</b>	<b>Initialization is only available for source operators.</b>
<b>WEPRME0769</b>	<b>Recursive query not contained.</b>
<b>WEPRME0770</b>	<b>Source operators are internally used for identifying data sources, hence the occurrence of this exception is a signal of a misuse of a source operator.</b>
<b>WEPRME0771</b>	<b>Only operators can be used as child nodes of a stream operator.</b>
<b>WEPRME0772</b>	<b>A stream operator must have exactly one input operator.</b>
<b>WEPRME0773</b>	<b>A stream operator must not have more than one input operator.</b>
<b>WEPRME0774</b>	<b>The use of stream operators inside the pipes algebra is currently not supported.</b>
<b>WEPRME0775</b>	<b>The target of a stream operator is to transform a passive query into an active one, hence no passive stream operators are possible.</b>
<b>WEPRME0776</b>	<b>Unknown stream operator mode {0}.</b>
<b>WEPRME0777</b>	<b>Only operators can be used as child nodes of a time shift.</b>
<b>WEPRME0778</b>	<b>A time shifter must have exactly one input operator.</b>

- WEPRME0779**      **A time shifter must not have more than one input operator.**
  
- WEPRME0780**      **A time shifter must have a constant time shift.**
  
- WEPRME0781**      **Unknown selection operator mode {0}.**
  
- WEPRME0782**      **{0} mode not supported.**
  
- WEPRME0783**      **Only operators can be used as child nodes of an union operator.**
  
- WEPRME0784**      **A union operator must have at least two input operators.**
  
- WEPRME0785**      **A union operator must have at least two input operators.**
  
- WEPRME0786**      **Unknown union operator mode {0}.**
  
- WEPRME0787**      **Only an operator can be used as child node of a window operator.**
  
- WEPRME0788**      **A window operator must have exactly one input operator.**
  
- WEPRME0789**      **A window operator must not have more than one input operator.**
  
- WEPRME0790**      **A window operator on a non-chronon stream is currently not supported.**
  
- WEPRME0791**      **Unknown window operator type {0}.**
  
- WEPRME0792**      **The use of a window operator inside the cursor algebra is currently not supported.**

---

WEPRME0793	Unknown window operator mode: {0}.
WEPRME0794	Only expressions can be used as child nodes of an aggregate expression.
WEPRME0796	User-defined aggregation function does not support PN approach.
WEPRME0797	A constant expression must not have any sub-expressions.
WEPRME0798	Local metadata fragment identified by {0} cannot be created.
WEPRME0799	Local metadata fragment identified by {0} cannot be created because of multiple fields matching the field name pattern.
WEPRME0800	Local metadata fragment identified by {0} cannot be created because no available field matches the field name pattern.
WEPRME0801	A column expression must not have any sub-expressions.
WEPRME0802	Unable to identify field {0}.
WEPRME0803	Only numeric values can be used with ABS function.
WEPRME0804	The decimal place parameter has to be of type Integer.
WEPRME0805	Illegal condition.
WEPRME0806	Case does not provide FieldMetaData.
WEPRME0807	Inconsistent types in case.

- WEPRME0810**      **Only String values can be used with CHAR\_LENGTH function.**
  
- WEPRME0811**      **Casting from {0} to {1} is currently not supported.**
  
- WEPRME0812**      **Unknown function type {0}.**
  
- WEPRME0813**      **Only expressions can be used as child nodes of a function expression.**
  
- WEPRME0814**      **Initialization is only available for user-defined functions.**
  
- WEPRME0815**      **A {0} operation must have exactly two sub-expressions.**
  
- WEPRME0816**      **A {0} operation must not have more than two sub-expressions.**
  
- WEPRME0817**      **Only numeric values can be used with ABS function.**
  
- WEPRME0818**      **FLOOR function only supports Double and Float values.**
  
- WEPRME0819**      **CEILING function only supports Double and Float values.**
  
- WEPRME0820**      **The result type of a CHAR\_LENGTH function has to be Integer.**
  
- WEPRME0821**      **ROUND function only supports numeric values.**
  
- WEPRME0822**      **TRUNCATE function only supports numeric values.**
  
- WEPRME0823**      **Currently casting between these types is not allowed.**

---

WEPRME0824	Currently only casting between numeric types and casting to String type is supported.
WEPRME0825	A {0} function must not have any sub-expressions.
WEPRME0826	Unexpected undefined case.
WEPRME0827	Parameters missing for user-defined function {0}.
WEPRME0828	Too many parameters for user-defined function {0}.
WEPRME0829	Unknown function expression type {0}.
WEPRME0830	Only numeric values can be negated.
WEPRME0831	Only numeric values can be mathematically subsumed.
WEPRME0832	Exponentiation with base type {0} is only allowed for exponent types {1}, {2} and {3}.
WEPRME0833	Exponent type cannot be {0}.
WEPRME0834	Only textual values can be concatenated.
WEPRME0835	Unknown operation type {0}.
WEPRME0836	Recognized a numeric constant without a numeric data type.
WEPRME0837	Only expressions can be used as child nodes of an operation expression.

- WEPRME0838**      **A {0} operation must have exactly one sub-expression.**
  
- WEPRME0839**      **A {0} operation must not have more than one sub-expression.**
  
- WEPRME0840**      **A {0} operation must have exactly two sub-expressions.**
  
- WEPRME0841**      **A {0} operation must not have more than two sub-expressions.**
  
- WEPRME0842**      **Unknown operation expression type {0}.**
  
- WEPRME0843**      **Only numeric values can be negated.**
  
- WEPRME0844**      **Only numeric values can be mathematically subsumed.**
  
- WEPRME0845**      **Unknown operation expression type {0}.**
  
- WEPRME0847**      **Only expressions can be used as child nodes of a renamed field expression.**
  
- WEPRME0848**      **A renamed field expression must have exactly one sub-expression.**
  
- WEPRME0849**      **A renamed field expression must not have more than one sub-expression.**
  
- WEPRME0850**      **Child at index {0} cannot be accessed because the given index is not assigned so far.**
  
- WEPRME0851**      **Index {0} cannot be accessed ({1} children are allowed).**
  
- WEPRME0852**      **Index {0} cannot be accessed ({1} parents are allowed).**

---

WEPRME0853	New child has reached its maximum number of parents (number of allowed parents: {0}).
WEPRME0854	New parent has reached its maximum number of children (number of allowed children: {0}).
WEPRME0855	Node has reached its maximum number of children (number of allowed children: {0}).
WEPRME0856	Node has reached its maximum number of parents (number of allowed parents: {0}).
WEPRME0857	Only use this method on nodes without a fixed number of children.
WEPRME0858	Only use this method on nodes without a fixed number of parents.
WEPRME0859	Parent at index {0} cannot be accessed because the given index is not assigned so far.
WEPRME0860	A node of the specified iteration cannot be added to the given node's global metadata because it does not hold the specified precondition.
WEPRME0861	This exception is thrown to avoid the creation of a new metadata fragment after resetting.
WEPRME0862	Not contained.
WEPRME0863	Entry already contained.
WEPRME0864	Entry not contained.

- WEPRME0865**      **SpeedUp <0 is not allowed.**
  
- WEPRME0866**      **Unsupported SQL data type.**
  
- WEPRME0867**      **Period has to be equal to or greater than 0.**
  
- WEPRME0868**      **This period worker thread cannot be woken up, because wait time is zero.**
  
- WEPRME0869**      **For this factory, getSignature() may not be called with instantiation parameter types as the adapter is already instantiated.**
  
- WEPRME0870**      **For this factory, createInstance() may not be called with instantiation parameters as the adapter is already instantiated.**
  
- WEPRME0872**      **Class not found.**
  
- WEPRME0873**      **The function adapter class for the user-defined function must not be null.**
  
- WEPRME0877**      **Unable to create instance of {0}.**
  
- WEPRME0878**      **{0} does not provide a constructor with signature String[], which is obligatory.**
  
- WEPRME0884**      **Query already reconstructed.**
  
- WEPRME0885**      **Could not instantiate adapter class of sink adapter.**
  
- WEPRME0886**      **The {0} already exists in the database.**
  
- WEPRME0887**      **The removal of {0} from the database failed.**

---

WEPRME0889	Repository error: The query graph to be sorted must have at least one node without an input.
WEPRME0890	The input queries differ from the sorted output queries.
WEPRME0891	Query properties may only be retrieved after the query is built.
WEPRME0892	Unsupported approach.
WEPRME0893	Could not instantiate adapter class of source adapter.
WEPRME0896	Unable to access class {0}.
WEPRME0897	Unable to create instance of {0}.
WEPRME0898	Update in the database failed.
WEPRME0899	The given SQL statement {0} does not provide streaming data.
WEPRME0900	Unable to parse the given SQL statement: {0}.
WEPRME0901	Unable to translate the given SQL statement ({0}): {1}.
WEPRME0902	Unable to translate the given SQL statement (problem with at least one specified column name): {0}.
WEPRME0903	Configuration could not be loaded, check XML config URL.
WEPRME0904	Could not locate resource!

<b>WEPRME0905</b>	<b>Provided class not found!</b>
<b>WEPRME0906</b>	<b>Unable to read configuration file.</b>
<b>WEPRME0907</b>	<b>XML parsing problem.</b>
<b>WEPRME0908</b>	<b>BOT failed.</b>
<b>WEPRME0909</b>	<b>Check whether the persistent ID of the object is null!</b>
<b>WEPRME0910</b>	<b>COMMIT failed.</b>
<b>WEPRME0911</b>	<b>Initializing transaction failed.</b>
<b>WEPRME0912</b>	<b>Obtaining entity manager failed.</b>
<b>WEPRME0913</b>	<b>Persistence factory shutdown failed.</b>
<b>WEPRME0914</b>	<b>ROLLBACK failed.</b>
<b>WEPRME0915</b>	<b>The removal of {0} query from the database failed.</b>
<b>WEPRME0916</b>	<b>The saving of {0} to the database failed.</b>
<b>WEPRME0918</b>	<b>Unknown approach.</b>
<b>WEPRME0920</b>	<b>Unsupported approach {0}.</b>

<b>WEPRME0921</b>	<b>Unable to access database with given data source specification.</b>
<b>WEPRME0923</b>	<b>Unable to access database with given data source and table specification.</b>
<b>WEPRME0924</b>	<b>Unable to reconstruct refresh time.</b>
<b>WEPRME0925</b>	<b>Please provide connection URL property "rtmsystem.datasource.connection_url" in order to connect to database.</b>
<b>WEPRME0926</b>	<b>Please provide JDBC driver name property "rtmsystem.datasource.jdbc_drivename" in order to initialize the data source.</b>
<b>WEPRME0927</b>	<b>Problem with basic data source configuration.</b>
<b>WEPRME0928</b>	<b>Problem with JDBC driver, please verify that the library is attached, library classpath is correct and driver name is correct.</b>
<b>WEPRME0929</b>	<b>The classpath of the JDBC driver is malformed.</b>
<b>WEPRME0930</b>	<b>Obtaining Connection to JDBC Source {0} has failed!</b>
<b>WEPRME0931</b>	<b>This method is not supported by this version.</b>
<b>WEPRME0932</b>	<b>Could not instantiate builder class of ServerDataSourceEntry.</b>
<b>WEPRME0933</b>	<b>Load of tables failed!</b>
<b>WEPRME0934</b>	<b>The builder class for the data source must not be null.</b>

- WEPRME0938**      **Illegal HA state - slaves ({0}) are already locked before starting command execution.**
  
- WEPRME0939**      **Setting the remote ID is only allowed if the local connection is a remote stub.**
  
- WEPRME0940**      **Using High Availability, commands may only be given to the master.**
  
- WEPRME0941**      **An unexpected exception occurred while executing a remote command from the client.**
  
- WEPRME0942**      **No async commands supported yet.**
  
- WEPRME0943**      **No sync commands expected by {0}.**
  
- WEPRME0944**      **Only master can deliver list of active servers in HA cluster.**
  
- WEPRME0945**      **Only the master may broadcast update of cluster topology.**
  
- WEPRME0946**      **Remote connection handler is already removed or unknown.**
  
- WEPRME0947**      **Sink currently does not have to handle any commands.**
  
- WEPRME0948**      **System already shut down.**
  
- WEPRME0949**      **The class {0} cannot be instantiated on the server.**
  
- WEPRME0950**      **The system is already shut down.**
  
- WEPRME0951**      **This API is only to be used in HA mode.**

<b>WEPRME0952</b>	<b>Unable to close channel {0}.</b>
<b>WEPRME0953</b>	<b>Unexpected command {0}.</b>
<b>WEPRME0954</b>	<b>Unexpected command: {0}.</b>
<b>WEPRME0955</b>	<b>Unknown command: {0}.</b>
<b>WEPRME0956</b>	<b>Unsupported approach.</b>
<b>WEPRME0957</b>	<b>An exception occurred while connecting.</b>
<b>WEPRME0959</b>	<b>Connection to server has been lost.</b>
<b>WEPRME0960</b>	<b>Slave trying to initialize metadata after master failed to do so.</b>
<b>WEPRME0961</b>	<b>Unexpected approach {0}.</b>
<b>WEPRME0962</b>	<b>{0} does not provide a constructor with signature <code>String[]</code>, which is obligatory when passing a non-empty <code>String</code> array with parameters.</b>
<b>WEPRME0963</b>	<b>Builder class constructor not usable.</b>
<b>WEPRME0964</b>	<b>Builder class for <code>DataSource</code> not found.</b>
<b>WEPRME0965</b>	<b>Builder properties should contain at least one property e.g. connection URL.</b>
<b>WEPRME0966</b>	<b>Check if the schema file available.</b>

- WEPRME0967**      **Specified database table cannot be accessed.**
  
- WEPRME0968**      **System could not be configured, check XML config URL.**
  
- WEPRME0969**      **Unable to configure JPA Provider.**
  
- WEPRME0970**      **Unable to read configuration file.**
  
- WEPRME0971**      **Unable to read configuration file.**
  
- WEPRME0972**      **Unable to validate configuration file.**
  
- WEPRME0973**      **Unknown connection type purpose {0}.**
  
- WEPRME0974**      **Unknown database table {0}.**
  
- WEPRME0975**      **Unknown LoginModuleControlFlag: {0}.**
  
- WEPRME0976**      **Provided resource name is null!**
  
- WEPRME0977**      **Resource could not be located, please verify resource name ({0})!**
  
- WEPRME0978**      **Inconsistent stream metadata.**
  
- WEPRME0979**      **Unable to connect communication client.**
  
- WEPRME0980**      **Unable to connect due to incompatible protocols.**

<b>WEPRME0981</b>	<b>Unknown command.</b>
<b>WEPRME0982</b>	<b>Unsupported approach {0}.</b>
<b>WEPRME0983</b>	<b>Wrong command for being handled here: {0}.</b>
<b>WEPRME0984</b>	<b>Connection lost while not expecting a valid connection.</b>
<b>WEPRME0985</b>	<b>Disaster case, as other server has role {0}.</b>
<b>WEPRME0986</b>	<b>Inconsistent number of master result to slave communicators.</b>
<b>WEPRME0987</b>	<b>Master result to slave communicator which claims to support punctuations does not.</b>
<b>WEPRME0988</b>	<b>Multiple high availability partners are registered in cluster status ({0}).</b>
<b>WEPRME0989</b>	<b>No connection to slave which should be recovered.</b>
<b>WEPRME0990</b>	<b>No responsible master result sender found for query {0}.{1}.</b>
<b>WEPRME0991</b>	<b>Only the master can provide a list of active slaves.</b>
<b>WEPRME0992</b>	<b>Other server in unexpected role {0}.</b>
<b>WEPRME0993</b>	<b>PN approach currently not supported here.</b>
<b>WEPRME0994</b>	<b>Setting the cluster status provider is only allowed before start of high availability!</b>

- WEPRME0995**      **Setting the health check provider is only allowed before start of high availability!**
  
- WEPRME0996**      **Setting the system shutdown manager is only allowed before start of high availability!**
  
- WEPRME0997**      **Status of health check monitor of local system is not OK; shutting down!**
  
- WEPRME0998**      **Unable to connect to high availability partner due to incompatible versions.**
  
- WEPRME0999**      **Unable to create client connection handler because cluster status provider is not yet set.**
  
- WEPRME1000**      **Unable to do handshake with HA partner.**
  
- WEPRME1001**      **Unable to grant all artefact privileges to HA user.**
  
- WEPRME1002**      **Unable to initialize master mode because the cluster's master lock could not be acquired.**
  
- WEPRME1003**      **Unable to request communication parameters of master.**
  
- WEPRME1004**      **Unable to request role of HA partner.**
  
- WEPRME1005**      **Unable to retrieve high availability partner from cluster status.**
  
- WEPRME1006**      **Unable to shut down HA communication client of master.**
  
- WEPRME1007**      **Unable to take over master mode because the cluster's master lock could not be acquired.**

<b>WEPRME1008</b>	<b>Unsupported approach: {0}.</b>
<b>WEPRME1009</b>	<b>The specified HA server address {0} is not yet registered.</b>
<b>WEPRME1010</b>	<b>This command should not be used by the HA protocol.</b>
<b>WEPRME1012</b>	<b>No sync commands expected.</b>
<b>WEPRME1013</b>	<b>Break-off of input stream must only occur on input 1.</b>
<b>WEPRME1014</b>	<b>Action must not be null.</b>
<b>WEPRME1015</b>	<b>Add privilege on concrete and already existing artefact makes no sense.</b>
<b>WEPRME1016</b>	<b>Artefact must not be null.</b>
<b>WEPRME1017</b>	<b>Identifier must not be null.</b>
<b>WEPRME1018</b>	<b>Null argument.</b>
<b>WEPRME1019</b>	<b>Owner must not be null.</b>
<b>WEPRME1020</b>	<b>Wrong privilege type.</b>
<b>WEPRME1021</b>	<b>Grants load failed.</b>
<b>WEPRME1022</b>	<b>Grants remove failed.</b>

WEPRME1023	No actual artefact known.
WEPRME1024	Privilege {0} for user {1} granted by {2} not found.
WEPRME1025	Privilege {0} for user {1} not found.
WEPRME1026	Privilege cannot be persistent as the referenced artefact is not persistent.
WEPRME1027	The user {0} does not have the privilege {1}.
WEPRME1028	The user {0} does not have the privilege to grant the privilege {1}.
WEPRME1029	Privilege must not be null.
WEPRME1030	The delete failed.
WEPRME1031	The granted privilege to be serialized has no grants specified.
WEPRME1032	The remove of granter {0} to the database failed.
WEPRME1033	The saving of granter {0} to the database failed.
WEPRME1034	User must not be null.
WEPRME1035	Unsupported privilege type in serialization.
WEPRME1036	Unsupported privilege type.

<b>WEPRME1037</b>	<b>Wrong privilege type.</b>
<b>WEPRME1038</b>	<b>Granting privileges is not supported by this authorization module.</b>
<b>WEPRME1039</b>	<b>Persistence is not supported by this authorization module.</b>
<b>WEPRME1040</b>	<b>Revoking privileges is not supported by this authorization module.</b>
<b>WEPRME1041</b>	<b>Check argument, xmlConfig path is wrong, file could not be located.</b>
<b>WEPRME1042</b>	<b>Check argument, xmlSchema path is wrong, file could not be located.</b>
<b>WEPRME1043</b>	<b>Check arguments, either xmlConfig path or xmlSchema path is wrong, files could not be located.</b>
<b>WEPRME1044</b>	<b>Check arguments, either xmlConfig path or xmlSchema were null.</b>
<b>WEPRME1045</b>	<b>Clearing the system is only allowed before calling createSystem.</b>
<b>WEPRME1046</b>	<b>System could not be configured, check XML config URL.</b>
<b>WEPRME1047</b>	<b>Class for schema manager not found.</b>
<b>WEPRME1048</b>	<b>Current system configuration does not support persistence.</b>
<b>WEPRME1049</b>	<b>No schema manager provided!</b>
<b>WEPRME1050</b>	<b>Object of the schema manager cannot be instantiated!</b>

- WEPRME1051**      **Only client commands can be sent using this callback.**
  
- WEPRME1052**      **Problem with access to class of schema manager.**
  
- WEPRME1053**      **Registering protocol handlers is only allowed before system start!**
  
- WEPRME1054**      **Registering protocols is only allowed before system start!**
  
- WEPRME1055**      **Setting the cache provider is only allowed before system start!**
  
- WEPRME1056**      **The protocol handler must not be null.**
  
- WEPRME1057**      **The protocol must not be null.**
  
- WEPRME1058**      **There is already a protocol handler registered using identifier {0}.**
  
- WEPRME1059**      **There is already a protocol registered using identifier {0}.**
  
- WEPRME1060**      **Unknown protocol {0}.**
  
- WEPRME1061**      **The identifier "{0}" is not allowed for a {1}.**
  
- WEPRME1062**      **The identifier "{0}" is too long (maximum of {1} characters allowed).**
  
- WEPRME1063**      **The identifier of type {0} must not be null.**
  
- WEPRME1064**      **Unsupported artefact {0}.**

<b>WEPRME1065</b>	<b>Minimum supported client version must not be greater than maximum one.</b>
<b>WEPRME1066</b>	<b>Server must not support older maximum client versions than the previous one.</b>
<b>WEPRME1067</b>	<b>Server must not support older minimum client versions than the previous one.</b>
<b>WEPRME1068</b>	<b>Server must support clients with same version.</b>
<b>WEPRME1069</b>	<b>Server versions have to be provided in ascending order.</b>
<b>WEPRME1070</b>	<b>The operator is not processing.</b>
<b>WEPRME1071</b>	<b>The timestamps have to be provided in ascending order.</b>
<b>WEPRME1072</b>	<b>Sources must not have inputs.</b>
<b>WEPRME1073</b>	<b>The method (compute)Done must not be called on sources.</b>
<b>WEPRME1074</b>	<b>The method (compute)HeartBeat must not be called on sources.</b>
<b>WEPRME1075</b>	<b>The method (compute)Punctuate must not be called on sources.</b>
<b>WEPRME1076</b>	<b>The method (compute)Push must not be called on sources.</b>
<b>WEPRME1077</b>	<b>No additional outputs allowed.</b>
<b>WEPRME1078</b>	<b>A SourceAdapter providing a chronon stream must not use end timestamps other than start timestamp +1.</b>

- WEPRME1079**      **The operator is not processing ({0}).**
  
- WEPRME1080**      **The timestamps have to be provided in ascending order.**
  
- WEPRME1081**      **Source has to have at least one output.**
  
- WEPRME1082**      **Extra start time must be smaller than start time.**
  
- WEPRME1083**      **No extra work function specified for this source.**
  
- WEPRME1084**      **Sequence may not start before the logical start time.**
  
- WEPRME1085**      **Sequence produced wrong start timestamp.**
  
- WEPRME1086**      **HeartBeatPeriod has to be a divisor of elementPeriod.**
  
- WEPRME1087**      **Time {0} already past ({1}).**
  
- WEPRME1088**      **The specified label must not be null.**
  
- WEPRME1089**      **Lower bound of 1st range does not match with specified minimum.**
  
- WEPRME1090**      **Number of ranges and colors differ.**
  
- WEPRME1091**      **Upper bound of {0} range does not match with lower bound of {1} range.**
  
- WEPRME1092**      **Upper bound of last range does not match with specified maximum.**

<b>WEPRME1093</b>	<b>Legend for time series number {0} is not specified!</b>
<b>WEPRME1094</b>	<b>Sinks may not have outputs.</b>
<b>WEPRME1095</b>	<b>An ID has to be provided for each source.</b>
<b>WEPRME1096</b>	<b>Unable to provide metadata.</b>
<b>WEPRME1097</b>	<b>Illegal input index {0}.</b>
<b>WEPRME1098</b>	<b>Input data validity may not overlap more than one day.</b>
<b>WEPRME1099</b>	<b>Output already exists.</b>
<b>WEPRME1100</b>	<b>Output creation must take place before init.</b>
<b>WEPRME1101</b>	<b>Missing negative element for group {0}.</b>
<b>WEPRME1102</b>	<b>The length of minimal splits cannot be less than one millisecond.</b>
<b>WEPRME1103</b>	<b>An ID has to be provided for each cache input.</b>
<b>WEPRME1104</b>	<b>An ID has to be provided for each input.</b>
<b>WEPRME1105</b>	<b>Unexpected number of cache inputs!</b>
<b>WEPRME1106</b>	<b>Unexpected number of stream inputs!</b>

- WEPRME1107** Duplicate scope limited heartbeat for input {0}.
- WEPRME1108** Scope limited heartbeats with different timestamps.
- WEPRME1109** Window advance  $\leq 0$  not allowed.
- WEPRME1110** Window size  $\leq 0$  not allowed.
- WEPRME1111** Missing negative input elements.
- WEPRME1112** Not all positive elements matched.
- WEPRME1113** Negative call on empty state.
- WEPRME1115** The window advance must not be smaller than or equal to 0.
- WEPRME1116** Negative element not matching any previous positive one.
- WEPRME1117** An ID has to be provided for each input.
- WEPRME1118** Not all positive elements were matched by a negative one.
- WEPRME1119** Adding status is only allowed before open.
- WEPRME1120** Additional status elements have to be consecutive.
- WEPRME1121** The length of minimal splits cannot be less one millisecond.

WEPRME1125	Error on both streams !
WEPRME1126	Inconsistent streams.
WEPRME1127	No additional outputs allowed.
WEPRME1128	Minimum split length $\leq 0$ not allowed.
WEPRME1129	Ambiguous next edge.
WEPRME1130	Graph has to be packed before sequences can be generated.
WEPRME1131	Graph is already packed.
WEPRME1132	No node with ID {0}.
WEPRME1133	Reserved ID.
WEPRME1134	Wrong temporal event order.
WEPRME1135	The checked graph has the following errors: {0}
WEPRME1136	Duplicate scope limited heartbeat for input {0} (old: {1}, new: {2}).
WEPRME1137	Scope limited heartbeats with different timestamps.
WEPRME1138	Maximum size must only be given if blockIfFull is set.

- WEPRME1139** Duplicate scope limited heartbeat for input {0}.
- WEPRME1140** Start timestamp series is not monotonous.
- WEPRME1141** Scope limited heartbeat for recursive input {0} was not processed within the whole recursive query plan.
- WEPRME1142** Scope limited heartbeats are not supported for non-recursive inputs of recursion base.
- WEPRME1143** The window advance must not be smaller than or equal to 0.
- WEPRME1144** The window size must not be smaller than or equal to 0.
- WEPRME1145** Execution has already been assigned.
- WEPRME1146** Sink has to belong to this graph.
- WEPRME1147** Source has to belong to this graph.
- WEPRME1148** No corresponding connection found.
- WEPRME1149** Punctuation type {0} is not supported by default serializer.
- WEPRME1150** Data must not be null.
- WEPRME1151** Invalid element (empty time interval).
- WEPRME1152** Check internal queue resources/state.

<b>WEPRME1153</b>	<b>Operator won't produce any result in this state: {0}.</b>
<b>WEPRME1154</b>	<b>Method must not be called inside a connection's batch run.</b>
<b>WEPRME1155</b>	<b>Input record does not comply with the schema: expected {0}, but received {1}.</b>
<b>WEPRME1156</b>	<b>The record size ({0}) of {1} does not comply with metadata {2}.</b>
<b>WEPRME1157</b>	<b>The row {0} does not support null values.</b>
<b>WEPRME1158</b>	<b>RequiredDatabaseSources must not be null.</b>
<b>WEPRME1159</b>	<b>RequiredQueries must not be null.</b>
<b>WEPRME1160</b>	<b>RequiredUserDefinedFunctions must not be null.</b>
<b>WEPRME1161</b>	<b>Null properties are not allowed.</b>
<b>WEPRME1162</b>	<b>Property {0} has to be of type {1}.</b>
<b>WEPRME1163</b>	<b>RecordMetaData must not be null.</b>
<b>WEPRME1164</b>	<b>Subscriptions must not be null.</b>
<b>WEPRME1165</b>	<b>The given notification callback is already registered.</b>
<b>WEPRME1166</b>	<b>The given notification callback is not registered.</b>

- WEPRME1167**      **A timestamp for each input has to be specified.**
  
- WEPRME1168**      **All inputs have to be provided before init.**
  
- WEPRME1169**      **An operator may not publish elements in state {0}.**
  
- WEPRME1170**      **An operator may not publish punctuations in state {0}.**
  
- WEPRME1171**      **Cannot determine periodically updated metadata fragments! Execution is unavailable!**
  
- WEPRME1172**      **Cannot determine periodically updated metadata fragments!  
PeriodicMetaDataUpdateWorkerThread is unavailable!**
  
- WEPRME1173**      **Complete from is already set for output ID {0}.**
  
- WEPRME1174**      **Complete from must not change (Was {0} for output {1} and tried to change to {2}).**
  
- WEPRME1175**      **Graph must not be null!**
  
- WEPRME1176**      **Graph Wlock needed.**
  
- WEPRME1177**      **Identifier {0} is not supported.**
  
- WEPRME1178**      **Illegal Operator State: {0} (State.INITIALIZED or State.PROCESSING expected).**
  
- WEPRME1179**      **Index out of bounds.**
  
- WEPRME1180**      **Input {0} already set.**

---

<b>WEPRME1181</b>	<b>Input {0} not set.</b>
<b>WEPRME1182</b>	<b>Input {0} was not set.</b>
<b>WEPRME1183</b>	<b>MetaData-object must not be null!</b>
<b>WEPRME1184</b>	<b>Minimum heartbeat distance must not be smaller than one.</b>
<b>WEPRME1185</b>	<b>Not enough inputs provided.</b>
<b>WEPRME1186</b>	<b>Operator already closed.</b>
<b>WEPRME1187</b>	<b>Operator already closed.</b>
<b>WEPRME1188</b>	<b>Operator is already initialized.</b>
<b>WEPRME1189</b>	<b>Operator is already opened.</b>
<b>WEPRME1190</b>	<b>Operator is working.</b>
<b>WEPRME1192</b>	<b>Operator may not use tellDone method in state {0}.</b>
<b>Explanation</b>	The tellDone method of an operator announces to downstream operators that the operator will no longer send events. Calling this method is restricted to certain states of the lifecycle of the operator.
<b>Action</b>	Restrict the use of this method to the permitted lifecycle states.
<b>WEPRME1193</b>	<b>Operator was already closed.</b>
<b>WEPRME1194</b>	<b>Operator was already closed - use reset.</b>

<b>WEPRME1195</b>	<b>Output already exists.</b>
<b>WEPRME1196</b>	<b>Output already set.</b>
<b>WEPRME1197</b>	<b>Output creation must take place before init.</b>
<b>WEPRME1198</b>	<b>Output ID out of bounds.</b>
<b>WEPRME1199</b>	<b>Output not found.</b>
<b>WEPRME1200</b>	<b>Output not set.</b>
<b>WEPRME1201</b>	<b>Punctuations of type {0} are not supported by operator {1}.</b>
<b>WEPRME1202</b>	<b>Setting complete from for operators with optional inputs is only possible if no inputs present.</b>
<b>WEPRME1203</b>	<b>Setting complete from for operators with optional inputs is only possible when initialized.</b>
<b>WEPRME1204</b>	<b>Setting complete from is only possible for sources.</b>
<b>WEPRME1205</b>	<b>Too many inputs provided.</b>
<b>WEPRME1206</b>	<b>Nullary operators have no sources.</b>
<b>WEPRME1207</b>	<b>Input not set.</b>
<b>WEPRME1208</b>	<b>Unable to read from input.</b>

WEPRME1209	From must not be null.
WEPRME1210	Unable to close input stream.
WEPRME1211	Unable to read file.
WEPRME1212	Reset is not supported for a queue while it is consuming.
WEPRME1213	Min must not be greater than max.
WEPRME1214	Only positive numbers of elements are supported.
WEPRME1215	Times must not be negative.
WEPRME1216	Right input has to support reset.
WEPRME1217	Not enough sources provided.
WEPRME1218	Sources not yet provided.
WEPRME1219	Wrong input type.
WEPRME1220	Cannot determine supportsReset before init.
WEPRME1221	No source provided.
WEPRME1222	Source not yet provided.

- WEPRME1223**      **Wrong input type.**
  
- WEPRME1224**      **Initially empty map required.**
  
- WEPRME1225**      **This queue is limited.**
  
- WEPRME1226**      **Buffer must have a capacity of at least one element.**
  
- WEPRME1227**      **No additional run can be obtained before consuming the last one.**
  
- WEPRME1228**      **No new cursors can be requested after all previously requested cursors were closed.**
  
- WEPRME1229**      **Only one additional cursor supported due to consuming TeeBuffer.**
  
- WEPRME1230**      **This is a consuming TeeBuffer.**
  
- WEPRME1231**      **This is not a consuming TeeBuffer.**
  
- WEPRME1232**      **Iterator is empty.**
  
- WEPRME1233**      **Underlying iterator has to support remove.**
  
- WEPRME1234**      **Init not allowed after open{0}{1}.**
  
- WEPRME1235**      **Iterator is already closed.**
  
- WEPRME1236**      **Iterator is already initialized.**

<b>WEPRME1237</b>	<b>Iterator is already open.</b>
<b>WEPRME1238</b>	<b>Iterator is not initialized.</b>
<b>WEPRME1239</b>	<b>Iterator was already closed - use reset.</b>
<b>WEPRME1240</b>	<b>Iterator was not opened.</b>
<b>WEPRME1241</b>	<b>No more elements left.</b>
<b>WEPRME1242</b>	<b>Remove is not supported by this iterator.</b>
<b>WEPRME1243</b>	<b>Reset is only allowed after open and before close.</b>
<b>WEPRME1244</b>	<b>Update may only be used after next().</b>
<b>WEPRME1245</b>	<b>Not all required sources set.</b>
<b>WEPRME1246</b>	<b>Operator was already initialized.</b>
<b>WEPRME1247</b>	<b>Operators do not supported remove.</b>
<b>WEPRME1248</b>	<b>Sources {0} not set.</b>
<b>WEPRME1249</b>	<b>Update may only be used after next().</b>
<b>WEPRME1250</b>	<b>Exception during close.</b>

WEPRME1251	Exception during init.
WEPRME1252	Exception during query processing.
WEPRME1253	Unable to handle {0} due to {1}.
WEPRME1254	Unknown device.
WEPRME1255	Wrong data format: missing header element.
WEPRME1256	Wrong data format: missing header end.
WEPRME1257	Wrong data format: missing header start.
WEPRME1258	Wrong data format: missing packet end.
WEPRME1259	Wrong data format: unable to parse parameter.
WEPRME1260	Wrong data format: unable to parse parameter count.
WEPRME1261	Wrong data format: unable to parse timestamp.
WEPRME1262	Wrong data format: wrong number of parameters.
WEPRME1263	Wrong data format: wrong parameter format.
WEPRME1264	Bytes message cannot be read because of the following reason: {0}.

<b>WEPRME1265</b>	<b>Bytes messages do not support reading lines of data.</b>
<b>WEPRME1266</b>	<b>Bytes message cannot be written because of the following reason: {0}.</b>
<b>WEPRME1267</b>	<b>Connection cannot be created. Check associated properties (e.g. authentication properties)! {0}.</b>
<b>WEPRME1268</b>	<b>Connection cannot be listened to because of the following reason: {0}.</b>
<b>WEPRME1269</b>	<b>Connection factory cannot be retrieved via JNDI. Check associated ID! {0}.</b>
<b>WEPRME1270</b>	<b>Destination cannot be retrieved via JNDI. Check associated ID! {0}.</b>
<b>WEPRME1271</b>	<b>JNDI context cannot be created. Check connection properties! {0}.</b>
<b>WEPRME1272</b>	<b>Message cannot be sent because of the following reason: {0}.</b>
<b>WEPRME1273</b>	<b>Receiver cannot be created because of the following reason: {0}.</b>
<b>WEPRME1274</b>	<b>Sender cannot be created because of the following reason: {0}.</b>
<b>WEPRME1275</b>	<b>Session cannot be created because of the following reason: {0}.</b>
<b>WEPRME1276</b>	<b>Connection cannot be created because of the following reason: {0}.</b>
<b>WEPRME1277</b>	<b>Input has to support reset.</b>
<b>WEPRME1278</b>	<b>This class must not be reinitialized.</b>

- WEPRME1279**      **Unexpected reinitialization.**
  
- WEPRME1280**      **Only operators can be used as child nodes of a distinct operator.**
  
- WEPRME1281**      **Database sources using direct access cannot be used in user-defined operators.**
  
- WEPRME1282**      **Incompatible parameter type for user-defined operator {0} (expected {1}, found {2}).**
  
- WEPRME1283**      **Initialization is only available for user-defined operators.**
  
- WEPRME1284**      **Input of user-defined operator has unknown mode {0}.**
  
- WEPRME1285**      **Inputs of a user-defined operator have to be ordered (first input streams, second database sources).**
  
- WEPRME1286**      **Only user-defined operators and sources can be used as child nodes of a user-defined operator (found {0}).**
  
- WEPRME1288**      **Unable to compute stream metadata for user-defined operator.**
  
- WEPRME1289**      **Unable to retrieve specified source input.**
  
- WEPRME1290**      **Unknown user-defined operator mode {0}.**
  
- WEPRME1291**      **Wrong number of instantiation parameters for user-defined operator {0} (expected {1}, found {2}).**
  
- WEPRME1292**      **List caches cannot be indexed!**

WEPRME1293	Missing key indices!
WEPRME1294	Missing key!
WEPRME1295	Unsupported communication type.
WEPRME1296	Attempt to inconsistently initialize serializers for complex {0}.
WEPRME1297	Wrong serialization initialization - Missing: {0}, unused: {1}.
WEPRME1298	Wrong alternative.
WEPRME1299	File has to be empty.
WEPRME1300	Update ist not permitted.
WEPRME1301	Iterator always removes elements.
WEPRME1302	Remove is currently not supported.
WEPRME1303	Unsupported type code: {0}.
WEPRME1304	Unsupported RTM exception type.
WEPRME1305	Inputs of an user-defined operator have to be ordered (first input streams, second database sources).
WEPRME1306	Only user-defined operators and sources can be used as child nodes of an user-defined operator (found {0}).

- WEPRME1307**      **Wrong number of instantiation parameters for user-defined operator {0} (expected {1}, found {2}).**
  
- WEPRME1308**      **Incompatible parameter type for user-defined operator {0} (expected {1}, found {2}).**
  
- WEPRME1309**      **Input metadata mismatch for user-defined operator {0}. {1}**
  
- WEPRME1310**      **Missing inputs for user-defined operator {0}. {1}**
  
- WEPRME1311**      **Too may inputs for user-defined operator {0}. {1}**
  
- WEPRME1312**      **Unable to use user-defined operator {0}. {1}.**
  
- WEPRME1313**      **RequiredUserDefinedOperators must not be null.**
  
- WEPRME1314**      **An input stream is to be connected to an operator at index {0}, but the index must not be negative or exceed the maximum allowed number of inputs, which is {1}.**
  
- WEPRME1315**      **Inconsistent output stream metadata.**
  
- WEPRME1317**      **The entry to insert does not provide the list of required entries.**
  
- WEPRME1318**      **A list of required repository entries has to be provided.**
  
- WEPRME1319**      **An initialization reason has to be provided. Use other constructor if no reinitialization takes place.**
  
- WEPRME1320**      **JPA initialization is only allowed using the parameterless constructor.**

---

WEPRME1322	The entry is not yet initialized.
WEPRME1323	The timestamps have to be provided in increasing order.
WEPRME1324	The end timestamp has to be greater than the start timestamp.
WEPRME1325	First snapshot-reducible event has been sent for the following query: Owner: {0} Identifier: {1} Event: {2}
WEPRME1326	The entry {0} required by {1} is not in the repository.
WEPRME1327	The entry {0} can not be removed as it is still in use.
WEPRME1328	The left-hand side of an action must be a field declared in the measure clause.
WEPRME1335	This UserDefinedOperator is missing cache inputs. Minimum expected: {0}. Found: {1},{2}
WEPRME1336	This UserDefinedOperator is missing stream inputs. Minimum expected: {0}. Found: {1},{2}
WEPRME1337	This UserDefinedOperator has too many cache inputs. Maximum expected: {0}. Found: {1},{2}
WEPRME1338	This UserDefinedOperator has too many stream inputs. Maximum expected: {0}. Found: {1},{2}
WEPRME1340	Invalid range of exponent.
WEPRME1341	Error occurred when evaluating function {0}. {1}

- WEPRME1342**      **Error occurred when evaluating operation {0}. {1}**
  
- WEPRME1343**      **Cast to {0} is illegal due to precision loss.**
  
- WEPRME1344**      **Illegal real exponent for negative base. Integer required.**
  
- WEPRME1345**      **Invalid negative exponent for base zero.**
  
- WEPRME1346**      **Undefined for  $x \leq 0$ .**
  
- WEPRME1347**      **Undefined for negative values.**
  
- WEPRME1348**      **The query {0} cannot be stopped as it is still in use.**
  
- WEPRME1349**      **Unexpected problem caused by usage of a subscription.**
  
- WEPRME1350**      **The user-defined function {0}.{1} cannot be deregistered as it is still in use.**
  
- WEPRME1351**      **The user-defined aggregation function {0}.{1} cannot be deregistered as it is still in use.**
  
- WEPRME1352**      **The user-defined operator {0}.{1} cannot be deregistered as it is still in use.**
  
- WEPRME1353**      **The data source {0}.{1} cannot be deregistered as it is still in use.**
  
- WEPRME1354**      **The table {0}.{1} cannot be deregistered as it is still in use.**
  
- WEPRME1355**      **The number of inputs returned by the user-defined operator adapter's `getNumberOfInputs()` method ({0}) is not consistent with the the number of inputs the user-defined operator adapter factory is called with ({1}).**

---

WEPRME1356	The number of cache inputs returned by the user-defined operator adapter's <code>getNumberOfInputs()</code> method ( <code>{0}</code> ) is not consistent with the the number of cache inputs the user-defined operator adapter factory is called with ( <code>{1}</code> ).
WEPRME1357	Division by zero.
WEPRME1358	Column " <code>{0}</code> " not found in metadata object.
WEPRME1359	Unexpected number of field metadata entries. Found <code>{0}</code> , expected <code>{1}</code> .
WEPRME1360	Objects of type <code>{0}</code> do not match. <code>{1} &lt;&gt; {2}</code> .
WEPRME1361	Unexpected number of columns. Found <code>{0}</code> , expected <code>{1}</code> .
WEPRME1362	Argument may not be null!
WEPRME1363	Column <code>{0}</code> has an unexpected type. Found <code>{1}</code> , expected <code>{2}</code> .
WEPRME1365	Column is expected to be nullable: <code>{1}</code> .
WEPRME1366	Column is expected to be case sensitive: <code>{0}</code> .
WEPRME1368	Parameter is not within range [ <code>{0}</code> , <code>{1}</code> ]: <code>{2}</code> .
WEPRME1369	Stream is expected to be a chronon stream!
WEPRME1370	Stream is not expected to be a chronon stream!
WEPRME1371	Parameter does not match expected value. Found <code>{0}</code> , expected <code>{1}</code> .

- WEPRME1372**      **The address given in config parameter {0} must not be empty.**
- WEPRME1373**      **The deprecated property {0} is used although the new property {1} is present.**
- WEPRME1374**      **Wrong number of factory parameters (was {0} but expected {1}).**
- WEPRME1375**      **Invalid port number: {0}.**
- WEPRME1378**      **Error evaluating aggregate function {0}. {1}**
- WEPRME1379**      **Error occurred in method {0}.**
- WEPRME1380**      **The signature of the user-defined aggregation function {0} does not match the specified types ({1}).**
- WEPRME1381**      **The user-defined aggregation function {0} is unknown or not visible.**
- WEPRME1383**      **Error occurred when evaluating function {0}.**
- WEPRME1384**      **Error occurred when evaluating operation {0}.**
- WEPRME1385**      **The field {0} is ambiguous. Check if fields and sources are properly renamed and no duplicate aliases are introduced.**
- WEPRME1386**      **The provided source parameters should not be null.**  
**Explanation**      The input parameter source parameters is null. A valid source parameters object should be provided.
- WEPRME1387**      **The provided server source parameters should not be null.**  
**Explanation**      The input parameter server source parameters is null. A valid server source parameters object should be provided.

---

<b>WEPRME1388</b>	<b>The provided query parameters should not be null.</b>
<b>Explanation</b>	The input parameter query parameters is null. A valid query parameters object should be provided.
<b>WEPRME1389</b>	<b>The provided query language should not be null.</b>
<b>Explanation</b>	The input parameter query language is null. A valid query language object should be provided.
<b>WEPRME1390</b>	<b>The provided query string should not be null.</b>
<b>Explanation</b>	The input parameter query string is null. A valid query string object should be provided.
<b>WEPRME1391</b>	<b>The command prepareQuery2 is not supported by the server.</b>
<b>Explanation</b>	The client tried to send the command prepareQuery2 to the server. The current server version does not support handling of this command. There is a mismatch between client version and server version.
<b>WEPRME1392</b>	<b>The query {0} cannot be subscribed to using subscription mode {1} as subscriptions to this query were restricted to times when no element is valid.</b>
<b>Explanation</b>	The query was prepared using the query parameter 'isSubscribableOnlyWhenNoElementValid'. Subscriptions to such queries may not use other subscription modes than 'ALL'.
<b>Action</b>	Use subscription mode 'ALL'.
<b>WEPRME1393</b>	<b>The query {0} can currently not be subscribed to as subscriptions to this query were restricted to times when no element is valid.</b>
<b>WEPRME1394</b>	<b>The query {0} cannot be unsubscribed from using subscription mode {1} as subscriptions to this query were restricted to times when no element is valid.</b>
<b>Explanation</b>	The query was prepared using the query parameter 'isSubscribableOnlyWhenNoElementValid'. Unsubscriptions to such queries may not use other subscription modes than 'ALL'.
<b>Action</b>	Use subscription mode 'ALL'.

- WEPRME1395**      **An exception related to {0} occurred in the underlying connection.**
  
- WEPRME1396**      **Creation of empty arrays is not supported.**
  
- WEPRME1397**      **All values in an array value construction must have the same type.**
  
- WEPRME1398**      **Only field expressions can be used as child nodes of an array element reference expression.**
  
- WEPRME1399**      **Limiting subscriptions to times when no element is valid is currently not supported in HA mode.**
  
- WEPRME1400**      **The field {0} is not of type ARRAY.**
  
- WEPRME1401**      **The method {0} is not yet supported in class {1}.**
  
- WEPRME1402**      **The XML query is not a valid XML document.**
  
- WEPRME1404**      **The XML query contains semantical errors.**
  
- WEPRME1405**      **An operator providing a chronon stream must not use end timestamps other than start timestamp +1.**
  
- WEPRME1406**      **Unknown timezone: {0}.**
  
- WEPRME1407**      **The time unit "{0}" is unknown.**
  
- WEPRME1408**      **Connection to {0} system lost.**

<b>WEPRME1409</b>	<b>Client lost connection to server with address {0}.</b>
<b>WEPRME1425</b>	<b>The Positive-Negative approach is currently not supported when running in high availability mode.</b>
<b>WEPRME1427</b>	<b>NullPointerException occurred while accepting new connection on address {0}.</b>
<b>WEPRME1428</b>	<b>CommunicationException occurred while accepting new connection on address {0}.</b>
<b>WEPRME1429</b>	<b>Exception occurred while accepting new connection on address {0}.</b>
<b>WEPRME1431</b>	<b>The pattern contains illegal characters. Supported characters are letters and the meta characters '*', '+', '?', '.', ' ', '(', ')', '[, ]', '^', '{, }', " and digits.</b>
<b>WEPRME1432</b>	<b>An aggregate is not allowed in this context.</b>
<b>Explanation</b>	The query contains an aggregate, but in a context that does not permit aggregates. Aggregates are only allowed in the SELECT and HAVING clauses of an SQL query, or inside an aggregate operator of an XML query.
<b>Action</b>	Correct the query and resubmit.
<b>WEPRME1433</b>	<b>An Ehcache with the name {0} already exists.</b>
<b>Explanation</b>	The system has tried to create a new Ehcache but it already existed in the CacheManager.
<b>Action</b>	Make sure the existing Ehcache is removed from the CacheManager.
<b>WEPRME1434</b>	<b>Ehcache configuration error: {0}.</b>
<b>Explanation</b>	The provided ehcache configuration file is not valid.
<b>Action</b>	Make sure the provided ehcache configuration file is valid.
<b>WEPRME1435</b>	<b>Problem creating new Ehcache: {0}.</b>
<b>Explanation</b>	The system tried to create a new Ehcache but encountered problems.
<b>Action</b>	See detailed message for further information.

<b>WEPRME1436</b>	<b>Invalid value of join attribute "{0}".</b>
<b>Explanation</b>	Join attributes refer to the input operators of a join by specifying their 0-based index. They are thus composed of a list of indexes, where only 0 and 1 are valid indexes. As an additional constraint, the list must not contain duplicates.
<b>Action</b>	Correct the specified join attribute.
<b>WEPRME1437</b>	<b>The child nodes with the UIDs "{0}" and "{1}" are not equivalent in the equivalence node.</b>
<b>Explanation</b>	Two of the child nodes in the equivalence node have different record metadata. All direct children of an equivalence node in a query graph must have the same record metadata (resulting schema).
<b>Action</b>	Adapt the equivalence node so that all child nodes have the same record metadata.
<b>WEPRME1438</b>	<b>Regular expression is invalid at offset {0}.</b>
<b>Explanation</b>	The query contains a PATTERN clause, but its regular expression has invalid syntax. The offset contained in the message is the 0-based offset within the regular expression where the failure was detected.
<b>Action</b>	Correct the regular expression syntax and resubmit the query.
<b>WEPRME1439</b>	<b>Barrier can only await one single set of connections.</b>
<b>WEPRME1440</b>	<b>The connection barrier has not been passed yet.</b>
<b>WEPRME1441</b>	<b>Connection for ID {0} could not be used as it connected too late.</b>
<b>WEPRME1442</b>	<b>Unexpected incoming recovery connection for ID {0}.</b>
<b>WEPRME1443</b>	<b>Duplicate incoming recovery connection for ID {0}.</b>
<b>WEPRME1444</b>	<b>Wrong user or password for recovery connection for ID {0}.</b>

---

<b>WEPRME1445</b>	<b>The connection is already authenticated.</b>
<b>WEPRME1447</b>	<b>Unable to cast the {0} value {1} to {2}.</b>
<b>Explanation</b>	The specified CAST function tries to cast the specified value to the shown type, but this is not possible.
<b>Action</b>	Either change the value in a way that it can be casted to the specified type or change the type accordingly.
<b>WEPRME1449</b>	<b>Unable to read the given event.</b>
<b>WEPRME1450</b>	<b>Unable to write the given event.</b>
<b>WEPRME1451</b>	<b>Percentage of delays must be in [0,1].</b>
<b>Explanation</b>	Percentage of delays must be in [0,1].
<b>Action</b>	Configure delay to be in [0,1].
<b>WEPRME1452</b>	<b>Exclusion threshold for delays must be greater than or equal zero.</b>
<b>Explanation</b>	Exclusion threshold for delays must be greater than or equal zero.
<b>Action</b>	Set exclusion threshold for delays to be greater than or equal zero.
<b>WEPRME1453</b>	<b>The weighting factor alpha must be in [0,1].</b>
<b>Explanation</b>	The weighting factor alpha must be in [0,1].
<b>Action</b>	Set the weighting factor alpha to be in [0,1].
<b>WEPRME1454</b>	<b>Size for the queue must be greater 1.</b>
<b>Explanation</b>	Size for the queue must be greater 1.
<b>Action</b>	Set size for the queue to be greater 1.
<b>WEPRME1455</b>	<b>Missing Ehcache configuration.</b>
<b>Explanation</b>	The useEhcache query parameter was set, but there was no Ehcache configuration present in the RTM system configuration.
<b>Action</b>	Either remove the useEhcache query parameter, or extend the RTM system configuration to include an Ehcache configuration.

<b>WEPRME1456</b>	<b>Element must not be null.</b>
<b>Explanation</b>	Element must not be null.
<b>Action</b>	Insert only elements not being null.
<b>WEPRME1458</b>	<b>Only one overload detector can be registered at a time.</b>
<b>Explanation</b>	Only one overload detector can be registered at a time.
<b>Action</b>	Register only one overload detector.
<b>WEPRME1459</b>	<b>The DURATION expression of a MATCHING clause must be evaluable to a numeric type.</b>
<b>Explanation</b>	The specified DURATION expression evaluates to a type that is not numeric, e.g., STRING. But DURATION expressions must be numeric.
<b>Action</b>	Change the DURATION expression such taht is evaluates to a numeric type.
<b>WEPRME1460</b>	<b>The WITHIN expression of a MATCHING clause must be evaluable to a numeric type.</b>
<b>Explanation</b>	The specified WITHIN expression evaluates to a type that is not numeric, e.g., STRING. But WITHIN expressions must be numeric.
<b>Action</b>	Change the WITHIN expression such taht is evaluates to a numeric type.
<b>WEPRME1461</b>	<b>Check the DURATION expression.</b>
<b>Explanation</b>	The DURATION expression contains an unspecific error.
<b>Action</b>	Check the DURATION expression.
<b>WEPRME1462</b>	<b>Check the WITHIN expression.</b>
<b>Explanation</b>	The WITHIN expression contains an unspecific error.
<b>Action</b>	Check the WITHIN expression.
<b>WEPRME1469</b>	<b>The maximum window size must not be smaller than or equal to 0.</b>
<b>Explanation</b>	The maximum windo size specifies the maximum validity an event can get applied by the window operator. As validities are always greater than zero the maximum window size also has to be.
<b>Action</b>	Specify a maximum window size that is greater than 0.

---

<b>WEPRME1471</b>	<b>The size of a count-based window can only be specified using a numeric constant.</b>
<b>Explanation</b>	Count-based windows does not support window size specification using numeric expressions.
<b>Action</b>	Replace the window size expression by a numeric constant.
<b>WEPRME1472</b>	<b>Check the window size expression.</b>
<b>Explanation</b>	The window size expression contains an unspecific error.
<b>Action</b>	Check the window size expression.
<b>WEPRME1473</b>	<b>Only constant maximum windows sizes, i.e., milliseconds, seconds, minutes or hours, are allowed for time-based windows.</b>
<b>Explanation</b>	The maximum window size must be evaluable to a constant amount of milliseconds. For this reason only constant time units are supported.
<b>Action</b>	Use a constant unit, i.e., millisecond, second, minute or hour, when specifying a maximum window size.
<b>WEPRME1474</b>	<b>The size of a time-based window can't be specified using a non-numeric constant.</b>
<b>Explanation</b>	The window size is specified by a non-numeric constant.
<b>Action</b>	Replace the non-numeric constant window size specification by a numeric constant or an expression that can be evaluated to a numeric type.
<b>WEPRME1475</b>	<b>The window size must not be greater than the specified maximum window size.</b>
<b>Explanation</b>	The computed window size was greater than the specified maximum window size.
<b>Action</b>	Check the window size expression if it could be limited to results that are less than or equal to the specified maximum window size or adapt (or remove) the specified maximum window size.
<b>WEPRME1476</b>	<b>The user {0} does not have the privilege to refresh the table.</b>
<b>WEPRME1477</b>	<b>The table {0} does not support triggered cache refresh!</b>
<b>Explanation</b>	The table is configured with no support for a a-periodic, triggered cached refreshed.
<b>Action</b>	Change the AccessProperties of the table and enable supportsTriggeredRefresh option to enable a-periodic triggering of table refreshes.

<b>WEPRME1479</b>	<b>The required complete-from timestamp cannot be guaranteed by the source.</b>
<b>Explanation</b>	The source operator cannot guarantee the semantic subscription time requested when preparing the query.
<b>Action</b>	Change or remove the requested semantic subscription time when preparing the query.
<b>WEPRME1480</b>	<b>The required complete-from timestamp cannot be guaranteed by the source adapter (not an intra source adapter).</b>
<b>Explanation</b>	Only intra source adapters are able to guarantee semantic subscription time requests when preparing a query.
<b>Action</b>	Use registered intra source adapters or remove the requested semantic subscription time when preparing the query.
<b>WEPRME1481</b>	<b>The required complete-from timestamp cannot be guaranteed by the source adapter (intra source adapter does not support requesting semantic subscription times).</b>
<b>Explanation</b>	The used intra source adapter does not support guaranteed semantic subscription time requests when preparing a query.
<b>Action</b>	Use intra source adapters supporting this feature or remove the requested semantic subscription time when preparing the query.
<b>WEPRME1482</b>	<b>The required complete-from timestamp cannot be guaranteed by the source adapter (intra source adapter is not able to provide the requested semantic subscription time).</b>
<b>Explanation</b>	The used intra source adapter is not able to guarantee the semantic subscription time requested when preparing the query.
<b>Action</b>	Change or remove the semantic subscription time requested when preparing the query.
<b>WEPRME1483</b>	<b>The required complete-from timestamp cannot be guaranteed by the operator.</b>
<b>Explanation</b>	The operator is already opened and the requested semantic subscription time cannot be guaranteed anymore.
<b>Action</b>	Modify or remove the semantic subscription time requested when preparing the query.

---

<b>WEPRME1484</b>	<b>The required complete-from timestamp cannot be guaranteed by the count-based window.</b>
<b>Explanation</b>	Count-based windows does not support requesting semantic subscription times when preparing a query.
<b>Action</b>	Remove the count-based window from the query or remove the semantic subscription time request when preparing the query.
<b>WEPRME1485</b>	<b>The duration must not be NULL.</b>
<b>Explanation</b>	The duration expression was evaluated to NULL.
<b>Action</b>	The duration expression must not return NULL as it cannot be interpreted as a duration value. Modify the expression in such a way that it cannot return NULL when being evaluated using the incoming data.
<b>WEPRME1486</b>	<b>The within must not be NULL.</b>
<b>Explanation</b>	The within expression was evaluated to NULL.
<b>Action</b>	The within expression must not return NULL as it cannot be interpreted as a within value. Modify the expression in such a way that it cannot return NULL when being evaluated using the incoming data.
<b>WEPRME1487</b>	<b>The window size must not be NULL.</b>
<b>Explanation</b>	The window size expression was evaluated to NULL.
<b>Action</b>	The window size expression must not return NULL as it cannot be interpreted as a window size value. Modify the expression in such a way that it cannot return NULL when being evaluated using the incoming data.
<b>WEPRME1488</b>	<b>Execution is already started.</b>
<b>WEPRME1489</b>	<b>Execution is already stopped and may not be restarted.</b>
<b>WEPRME1490</b>	<b>Execution is not started, yet.</b>
<b>WEPRME1491</b>	<b>Execution is already stopped.</b>

- WEPRME1492**      **Error unregistering mBean "{0}".**
  
- WEPRME1493**      **Failed to invoke setter on class "{0}".**
  
- WEPRME1494**      **Failed to invoke action "{0}" on class "{1}".**
  
- WEPRME1495**      **Failed to invoke getter "{0}" on class "{1}".**
  
- WEPRME1496**      **Attribute name cannot be null.**
  
- WEPRME1498**      **Getter must not be invoked as long as metadata is not activated.**
  
- WEPRME1499**      **Attribute "{0}" not found in class "{1}".**
  
- WEPRME1500**      **Setters is not supported.**
  
- WEPRME1501**      **Action name cannot be null.**
  
- WEPRME1502**      **No parameters allowed.**
  
- WEPRME1503**      **No Signature allowed.**
  
- WEPRME1504**      **Action name has to start with either {0}, {1} or {2}.**
  
- WEPRME1505**      **No such metaDataIdentifier found: {0}.**
  
- WEPRME1506**      **Unsupported parameter type: {0}.**

---

<b>WEPRME1508</b>	<b>Aggregates are not allowed in the GROUP BY clause.</b>
<b>Explanation</b>	As the grouping is applied before the aggregates are computed on the groups it is not allowed to use aggregates in the GROUP BY clause.
<b>Action</b>	Remove the aggregate from the GROUP BY clause.
<b>WEPRME1509</b>	<b>Check the specified group expression.</b>
<b>Explanation</b>	The group expression contains an unspecific error.
<b>Action</b>	Check the group expression for errors.
<b>WEPRME1510</b>	<b>Check the specified predicate (having clause).</b>
<b>Explanation</b>	The predicate contains an unspecific error.
<b>Action</b>	Check the predicate for errors.
<b>WEPRME1511</b>	<b>Only operators can be used as child nodes of a limit operator.</b>
<b>Explanation</b>	A non-operator node was passed as the input node of a limit operator, where only an operator node is allowed.
<b>Action</b>	Supply an operator node as the child of a limit operator.
<b>WEPRME1512</b>	<b>Only operators can be used as child nodes of an order operator.</b>
<b>Explanation</b>	A non-operator node was passed as the input node of an order operator, where only an operator node is allowed.
<b>Action</b>	Supply an operator node as the child of an order operator.
<b>WEPRME1513</b>	<b>Translation mode does not support operators of type {0}.</b>
<b>Explanation</b>	An unsupported operator was found during the translation of an SQL statement. The operator may be invalid for the current mode , but valid in other translation mode.
<b>Action</b>	Avoid SQL statements using the offending operator, or use a translation mode that supports it.
<b>WEPRME1514</b>	<b>Invalid aggregate in ORDER BY clause.</b>
<b>Explanation</b>	An ORDER BY clause was found to contain an aggregate function, which was not specified earlier in the same query. This is not allowed, an ORDER BY clause must not introduce new aggregate functions.
<b>Action</b>	Correct SQL statement, e.g. by adding the aggregate in question to the SELECT list.

<b>WEPRME1515</b>	<b>Check the specified part of the ORDER BY clause.</b>
<b>Explanation</b>	The ORDER BY clause was found to contain some invalid construct.
<b>Action</b>	Inspect ORDER BY clause and remove any invalid expressions.
<b>WEPRME1516</b>	<b>Subquery not allowed in this context.</b>
<b>Explanation</b>	A subquery was found in a context, where it is not supported.
<b>Action</b>	Correct statement according to the language specification.
<b>WEPRME1517</b>	<b>Subquery results in more than one column, where it must be a single column.</b>
<b>Explanation</b>	A subquery in a comparison of the where clause must result in a single column.
<b>Action</b>	Correct SQL statement.
<b>WEPRME1518</b>	<b>Invalid frame bound.</b>
<b>Explanation</b>	A window definition contained an invalid frame bound. A frame bound of UNBOUNDED FOLLOWING is not allowed on the left hand side of a window frame BETWEEN definition, and a frame bound of UNBOUNDED PRECEDING is not allowed on the right hand side.
<b>Action</b>	Correct SQL statement.
<b>WEPRME1519</b>	<b>Window function not allowed in this context.</b>
<b>Explanation</b>	A window function was found in a context, where it is not supported.
<b>Action</b>	Correct statement according to the language specification.
<b>WEPRME1520</b>	<b>Check the specified part of the window specification.</b>
<b>Explanation</b>	A window specification was found to contain some invalid construct.
<b>Action</b>	Inspect window specification and remove any invalid expressions.
<b>WEPRME1521</b>	<b>Only operators can be used as child nodes of a window aggregation operator.</b>
<b>Explanation</b>	A non-operator node was passed as the input node of a window aggregation operator, where only an operator node is allowed.
<b>Action</b>	Supply an operator node as the child of a window aggregation operator.

---

<b>WEPRME1524</b>	<b>Invalid nested aggregate function reference.</b>
<b>Explanation</b>	The argument of a set function invocation cannot be another set function.
<b>Action</b>	Correct SQL statement.
<b>WEPRME1535</b>	<b>The 2nd argument of the ROUND function must be of type integer.</b>
<b>Explanation</b>	The 2nd argument of the given ROUND function call is not of type integer which is mandatory.
<b>Action</b>	Change the expression specifying the 2nd argument of ROUND function such that it is of type integer.
<b>WEPRME1536</b>	<b>Unable to parse long value due to wrong number format. {0}</b>
<b>Explanation</b>	The given literal does not comply with the structure of an integral number, i.e. it contains characters other than 0-9,+,-.
<b>Action</b>	Please remove any invalid characters from your integer literal.
<b>WEPRME1537</b>	<b>Unable to parse integer value due to wrong number format. {0}</b>
<b>Explanation</b>	The given literal does not comply with the structure of an integral number, i.e. it contains characters other than 0-9,+,-.
<b>Action</b>	Please remove any invalid characters from your integer literal.
<b>WEPRME1538</b>	<b>If FROM is specified in the TRIM function, either the trim specification (LEADING, TRAILING, or BOTH) or the trim character or both have to be specified.</b>
<b>Explanation</b>	If FROM is specified in the TRIM function, either the trim specification (LEADING, TRAILING, or BOTH) or the trim character or both have to be specified.
<b>Action</b>	Either add the trim specification, the trim character or both. Alternatively remove the FROM clause.
<b>WEPRME1539</b>	<b>Only expressions are permitted for the trim source argument of the TRIM function.</b>
<b>Explanation</b>	Only expressions are permitted for the trim source argument of the TRIM function.
<b>Action</b>	Use an expression for the trim source argument.
<b>WEPRME1540</b>	<b>Only expressions are permitted for the trim character argument of the TRIM function.</b>
<b>Explanation</b>	Only expressions are permitted for the trim character argument of the TRIM function.
<b>Action</b>	Use an expression for the trim character argument.

<b>WEPRME1541</b>	<b>The {1} function only supports STRING values as argument for the substring source.</b>
<b>Explanation</b>	The {1} function only supports STRING values as argument for the substring source.
<b>Action</b>	Use a STRING value as argument for the substring source.
<b>WEPRME1542</b>	<b>The {1} function only supports INTEGER values as argument for the start position.</b>
<b>Explanation</b>	The {1} function only supports INTEGER values as argument for the start position.
<b>Action</b>	Use an INTEGER value as argument for the start position.
<b>WEPRME1543</b>	<b>The {1} function only supports INTEGER values as argument for the string length.</b>
<b>Explanation</b>	The {1} function only supports INTEGER values as argument for the string length.
<b>Action</b>	Use and INTEGER value as argument for the string length.
<b>WEPRME1544</b>	<b>The {1} function only supports STRING values as argument for the trim character.</b>
<b>Explanation</b>	The {1} function only supports STRING values as argument for the trim character.
<b>Action</b>	Use a STRING value as argument for the trim character.
<b>WEPRME1545</b>	<b>The {1} function only supports STRING values as argument for the trim source.</b>
<b>Explanation</b>	The {1} function only supports STRING values as argument for the trim source.
<b>Action</b>	Use a STRING value as argument for the trim source.
<b>WEPRME1546</b>	<b>The argument of the {0} function must be of type STRING or CHARACTER.</b>
<b>Explanation</b>	The argument of the LOWER and the UPPER function must be of type STRING or CHARACTER.
<b>Action</b>	Use a STRING or CHARACTER value as argument for the LOWER and the UPPER function.
<b>WEPRME1547</b>	<b>For the SUBSTRING function the substring source must be of type STRING and the start position and string length must be of type INTEGER.</b>
<b>Explanation</b>	For the SUBSTRING function the substring source must be of type STRING and the start position and string length must be of type INTEGER.
<b>Action</b>	Use a STRING value for the substring source and an INTEGER value for the start position and the string length.

---

<b>WEPRME1548</b>	<b>For the TRIM function the trim source must be of type STRING and the trim character must be of type STRING or CHARACTER.</b>
<b>Explanation</b>	For the TRIM function the trim source must be of type STRING and the trim character must be of type STRING or CHARACTER.
<b>Action</b>	Use a STRING value for the trim source and a STRING or CHARACTER value for the trim character.
<b>WEPRME1549</b>	<b>A {0} operation must have exactly three sub-expressions.</b>
<b>Explanation</b>	A {0} operation must have exactly three sub-expressions.
<b>Action</b>	Ensure that the {0} operation has exactly three sub-expressions.
<b>WEPRME1550</b>	<b>The LOWER and the UPPER function only support STRING and CHARACTER values.</b>
<b>Explanation</b>	The LOWER and the UPPER function only support STRING and CHARACTER values.
<b>Action</b>	Ensure that only STRING and CHARACTER values are used.
<b>WEPRME1551</b>	<b>The trim character for the TRIM function must have exactly one character.</b>
<b>Explanation</b>	The trim character for the TRIM function must have exactly one character.
<b>Action</b>	Use a single character as trim character for the TRIM function.
<b>WEPRME1552</b>	<b>The values for start position and start length of the SUBSTRING function are not valid.</b>
<b>Explanation</b>	The values for start position and start length of the SUBSTRING function are not valid.
<b>Action</b>	Use correct values for start position and start length of the SUBSTRING function.
<b>WEPRME1555</b>	<b>The return type of method {0} needs to be assignable to {1}. Found: {2}.</b>
<b>WEPRME1556</b>	<b>The first parameter of method {0} needs to be the same class or a super-class of {1}. Found: {2}.</b>
<b>WEPRME1557</b>	<b>Mmethod {0} is expected to have return type {1}. Found: {2}.</b>

- WEPRME1558**      **Method {0} is expected to have {1,choice,0#no parameters | 1#exactly one parameter | 1<exactly {1,number} parameters}.**
  
- WEPRME1559**      **The function cannot be registered.**
  
- WEPRME1560**      **The function factory cannot be registered.**
  
- WEPRME1561**      **The class of the user-defined function adapter factory must not be null.**
  
- WEPRME1562**      **The class of the user-defined aggregation function adapter factory must not be null.**
  
- WEPRME1565**      **Receiver version is too old to handle serialized user defined aggregation function adapter factory.**
  
- WEPRME1567**      **Failed to instantiate user defined window function for call "{0}". {1}**
  
- WEPRME1568**      **The signature {0} of the retrieved user defined window function for call "{1}" is invalid. {2}**
  
- WEPRME1569**      **Failed to instantiate user defined aggregation function for call "{0}". {1}**
  
- WEPRME1570**      **The signature {0} of the retrieved user defined aggregation function for call "{1}" is invalid. {2}**
  
- WEPRME1571**      **Failed to instantiate user defined function for call "{0}". {1}**
  
- WEPRME1572**      **The signature {0} of the retrieved user defined function for call "{1}" is invalid. {2}**
  
- WEPRME1573**      **Unknown window function type {0}.**

---

<b>WEPRME1574</b>	<b>Parameter number {0} of method {1} is expected to be serializable.</b>
<b>WEPRME1575</b>	<b>The mask "{0}" defining the temporal format is not valid.</b>
<b>Explanation</b>	The mask "{0}" defining the temporal format is not valid.
<b>Action</b>	Select a valid temporal format.
<b>WEPRME1576</b>	<b>Date conversion error for value "{0}".</b>
<b>Explanation</b>	Date conversion error for value "{0}".
<b>Action</b>	Enter a valid date.
<b>WEPRME1577</b>	<b>Unsupported date field "{0}".</b>
<b>Explanation</b>	Unsupported date field "{0}".
<b>Action</b>	Select a valid date field.
<b>WEPRME1578</b>	<b>Conversion to date failed for input string "{0}".</b>
<b>Explanation</b>	Conversion to date failed for input string "{0}".
<b>Action</b>	Enter a valid input string.
<b>WEPRME1582</b>	<b>RequiredUserDefinedAggregationFunctions may not be null.</b>
<b>WEPRME1583</b>	<b>The aggregation function adapter may not be null.</b>
<b>WEPRME1584</b>	<b>The function adapter may not be null.</b>
<b>WEPRME1585</b>	<b>The window function adapter may not be null.</b>
<b>WEPRME1586</b>	<b>The connected system does not support the registration of user-defined window functions.</b>
<b>WEPRME1587</b>	<b>The connected system does not support the de-registration of user-defined window functions.</b>

- WEPRME1588**      **The class of the user-defined window function adapter must not be null.**
  
- WEPRME1589**      **The server user-defined window function cannot be registered.**
  
- WEPRME1590**      **The class of the user-defined window function adapter factory must not be null.**
  
- WEPRME1591**      **The class of the user-defined aggregation function adapter factory must not be null.**
  
- WEPRME1592**      **The user-defined window function cannot be deregistered.**
  
- WEPRME1593**      **The user-defined window function cannot be registered.**
  
- WEPRME1594**      **The user-defined window function adapter factory must not be null.**
  
- WEPRME1595**      **The user {0} does not have the privilege to add the user-defined window function.**
  
- WEPRME1596**      **A user-defined window function factory is already registered for {0}.{1}.**
  
- WEPRME1597**      **No user-defined window function is registered for {0}.{1}.**
  
- WEPRME1598**      **The user-defined window function {0}.{1} cannot be deregistered as it is still in use.**
  
- WEPRME1599**      **A window function is not allowed in this context.**
  
- WEPRME1600**      **The signature of the user-defined window function {0} does not match the specified types ({1}).**
  
- WEPRME1601**      **The user-defined window function {0} is unknown or not visible.**

WEPRME1602	<b>DISTINCT mode is not allowed for user-defined aggregates.</b>
WEPRME1603	<b>The window function {0} is expected to have exactly {1} sub-expression(s).</b>
WEPRME1604	<b>Unknown window function type {0}.</b>
WEPRME1605	<b>Window functions are not supported in ACTIVE mode.</b>
WEPRME1606	<b>Unknown window function operator mode {0}.</b>
WEPRME1607	<b>Unexpected sub-expression type {0}. Aggregate or window function expected.</b>
WEPRME1608	<b>Invalid aggregation function adapter factory: Resolved a valid signature for the call "{0}", but failed to instantiate an adapter.</b>
WEPRME1609	<b>Invalid usage of aggregation function adapter factory. The signature for the call "{0}" had not been resolved before attempting to instantiate the adapter.</b>
WEPRME1610	<b>Invalid function adapter factory: Resolved a valid signature for the call "{0}", but failed to instantiate an adapter.</b>
WEPRME1611	<b>Invalid usage of function adapter factory. The signature for the call "{0}" had not been resolved before attempting to instantiate the adapter.</b>
WEPRME1612	<b>Invalid window function adapter factory: Resolved a valid signature for the call "{0}", but failed to instantiate an adapter.</b>
WEPRME1613	<b>Invalid usage of window function adapter factory. The signature for the call "{0}" had not been resolved before attempting to instantiate the adapter.</b>

- WEPRME1614** Only expressions can be used as child nodes of a window function expression.
- WEPRME1615** Window function {0} is only applicable over ordered windows.
- WEPRME1616** Window function {0} is only applicable over unbounded windows.
- WEPRME1617** The user {0} does not have the privilege to remove the user-defined window function.
- WEPRME1618** The signature's return type may not be null.
- WEPRME1619** The signature's parameter types may not be null.
- WEPRME1620** Only expressions are permitted in a PARTITION BY clause.
- WEPRME1621** The {0,choice,0#parameter|1#instantiation parameter} types may not be null.
- WEPRME1622** Expected at least {1} {0,choice,0#parameter|1# instantiation parameter} type(s), found {2}.
- WEPRME1623** Expected at most {1} {0,choice,0#parameter|1# instantiation parameter} type(s), found {2}.
- WEPRME1624** The {1}-th {0,choice,0#parameter|1#instantiation parameter} type is expected to be numeric, but is {2}.
- WEPRME1625** {0,choice,0#Parameter|1#Instantiation parameter} types may not be null (found null at index {1}).
- WEPRME1626** {0,choice,0#Parameter|1#Instantiation parameter} type {1} is expected to be compatible with type {2}. Found {3}.

---

WEPRME1627	The number of input parameter types differs. Expected {0}, but was {1}.
WEPRME1628	The {0}-th input parameter type may not be null.
WEPRME1629	The {0}-th parameter type is expected to be assignable to type {1}. Was: {2}.
WEPRME1630	The Return type may not be null.
WEPRME1631	Incompatible return types. Expected {0}, but was {1}.
WEPRME1632	The number of instantiation parameter types differs. Expected {0}, but was {1}.
WEPRME1633	The {0}-th instantiation parameter may not be null.
WEPRME1634	The {0}-th instantiation parameter is expected to be equal to or a sub-type of {1}. Was: {2}.
WEPRME1635	No {0,choice,0#parameter 1#instantiation parameter} types expected. Found {1}.
WEPRME1636	The given window function requires an ORDER BY clause in the window specification.
WEPRME1637	The given window function does not accept a bounded frame given in the window specification.
WEPRME1638	Unable to cast the given object to the specified type "{0}".
WEPRME1639	Unable to convert the given date "{0}".

<b>WEPRME1640</b>	<b>Unable to convert the given date of class {0}.</b>
<b>WEPRME1641</b>	<b>Unable to read next record.</b>
<b>WEPRME1642</b>	<b>Unable to convert the next record.</b>
<b>WEPRME1643</b>	<b>Remove not supported.</b>
<b>WEPRME1644</b>	<b>Reset not supported.</b>
<b>WEPRME1645</b>	<b>Unable to initialize JSON parser on given reader.</b>
<b>WEPRME1646</b>	<b>The field {0} is neither a group column nor part of an exact match of a group expression or an aggregate call.</b>
<b>Explanation</b>	Queries including grouping and/or aggregates are only able to use group columns/expressions and aggregate calls in the select list.
<b>Action</b>	Either add the missing column to the group columns or remove the grouping/aggregation from the query.
<b>WEPRME1647</b>	<b>The combination of grouping and/or aggregation and (qualified) star expressions in the select list is not allowed.</b>
<b>Explanation</b>	Since (qualified) star expressions are matching input/subquery columns and these columns are usually not preserved by grouping/aggregation the combination of both is not allowed.
<b>Action</b>	Explicitly enumerate the columns in the select list that should be contained in the result.
<b>WEPRME1648</b>	<b>Unable to extract RecordMetaData. Reason: {0}.</b>
<b>Explanation</b>	The schema (RecordMetaData) extraction for a BigMemory Data Source terminated with an error.
<b>Action</b>	Investigate the 'Reason' specified in the message.

---

WEPRME1649	Measure must be either euclidean, manhattan, cosine, tanimoto, or squaredeuclidean.
WEPRME1650	Only operators can be used as child nodes of an external subquery operator.
WEPRME1651	An external subquery operator must have exactly one input operator.
WEPRME1652	Invalid record found in cache {0} while fetching value of {1}.
WEPRME1653	Unknown outer join type "{0}".
WEPRME1654	Unknown semi join type "{0}".
WEPRME1656	I/O exception while reading XML input.
WEPRME1657	Record conversion exception while reading XML input.
WEPRME1658	An exception occurred while processing XQuery: {0}
WEPRME1659	PN approach is not supported for geometric mean.
WEPRME1660	Unable to create an aggregation factory instance for input types {0}.
WEPRME1661	The parameter "k" needs to be an integer greater than 0.
WEPRME1662	The parameter "iterations" needs to be an integer greater than 0.
WEPRME1663	The parameter "measureId" needs to match one of: euclidean, manhattan, cosine, tanimoto or squaredeuclidean.

- WEPRME1664**      **Unknown cross join type "{0}".**
  
- WEPRME1665**      **The source this scalar has to provide exactly one result.**
  
- WEPRME1666**      **The source of scalar has to provide at most one result.**
  
- WEPRME1667**      **No matching adapter found for signature {0}.**
  
- WEPRME1668**      **Ambiguous adapters: {0}**
  
- WEPRME1669**      **Unable to create instance.**
  
- WEPRME1670**      **The given list of adapters contains adapters with identical parameter types.**
  
- WEPRME1671**      **The given adapter classes must not be null.**
  
- WEPRME1672**      **The given adapter parameters must not be null.**
  
- WEPRME1673**      **The number of given adapter classes and parameter type lists does not match.**
  
- WEPRME1674**      **Unable to instantiate adapter {0}.**
  
- WEPRME1675**      **Wrong parameters - use at least class name and method name and if ambiguous add parameter class names.**
  
- WEPRME1676**      **The method {0} is not declared in class {1} with the given parameter types {3}.**
  
- WEPRME1677**      **Wrapping given operator of approach {0} to approach {1} is not supported.**

WEPRME1678	Violation of push-scalar operator rules.
WEPRME1679	Left status structure has to support temporal queries.
WEPRME1680	Right status structure has to support temporal queries.
WEPRME1681	Unknown authentication type "{0}".
WEPRME1682	Requesting required complete-from is not supported by this intra source adapter.
WEPRME1683	Property {0} is unknown! Please check the property name.
WEPRME1684	Value {1} is not in defined domain ({2}) of property {0}! Please check the property value.
WEPRME1685	Value {1} of property {0} is not in the defined range! Please check the property value.
WEPRME1686	The mandatory property {0} is not provided (level {1})!
WEPRME1688	The given system properties must not be null.
WEPRME1689	The class of the pull source cannot be found.
WEPRME1690	The IS comparison is only allowed with a NULL constant as second argument.
WEPRME1691	Only established connections can be marked as broken.
WEPRME1692	Only established connections can be marked as shutting down.

- WEPRME1693**      **Unable to connect to cluster within {0} seconds.**
  
- WEPRME1696**      **An exception occurred while recovering connection to {0}.**
  
- WEPRME1702**      **The pull result is already closed.**
  
- WEPRME1703**      **The pull result has run out of data.**
  
- WEPRME1704**      **This handler is not handling any synchronous command.**
  
- WEPRME1705**      **This handler is not handling any asynchronous command.**
  
- WEPRME1706**      **The server user-defined aggregation function factory cannot be registered.**
  
- WEPRME1707**      **The pull source adapter must not be null.**
  
- WEPRME1708**      **The pull source cannot be prepared.**
  
- WEPRME1709**      **The parameters for the server pull source must not be null.**
  
- WEPRME1710**      **The class for the server pull source must not be null.**
  
- WEPRME1711**      **The server function factory cannot be registered.**
  
- WEPRME1712**      **The server user-defined window function factory cannot be registered.**
  
- WEPRME1713**      **The server pull source cannot be prepared.**

<b>WEPRME1714</b>	<b>The query parameters must not be null.</b>
<b>WEPRME1715</b>	<b>The query cannot be removed.</b>
<b>WEPRME1716</b>	<b>The query cannot be executed.</b>
<b>WEPRME1717</b>	<b>The batch job cannot be started because the connection has already been shut down by the server.</b>
<b>WEPRME1718</b>	<b>The data source cannot be registered.</b>
<b>WEPRME1719</b>	<b>The table cannot be registered.</b>
<b>WEPRME1720</b>	<b>The parameters for the pull source must not be null.</b>
<b>WEPRME1721</b>	<b>The pull source must not be null.</b>
<b>WEPRME1722</b>	<b>The pull source cannot be prepared.</b>
<b>WEPRME1723</b>	<b>Not supported in HA mode.</b>
<b>WEPRME1725</b>	<b>Unable to add a node that is not the root of a logical query graph.</b>
<b>WEPRME1726</b>	<b>Unable to remove a node that is not the root of a logical query graph.</b>
<b>WEPRME1727</b>	<b>Only operators can be used as child nodes of a scalar operator.</b>
<b>WEPRME1728</b>	<b>A scalar operator must have exactly one input operator.</b>

<b>WEPRME1729</b>	<b>A scalar operator must not have more than one input operator.</b>
<b>WEPRME1730</b>	<b>Scalar is not supported for BA approach.</b>
<b>WEPRME1731</b>	<b>Incompatible approach.</b>
<b>WEPRME1735</b>	<b>Server shutting down.</b>
<b>WEPRME1736</b>	<b>Unexpected type: Tried to receive {0} but got {1}.</b>
<b>WEPRME1737</b>	<b>There is no server running with id {0}, {1}.</b>
<b>WEPRME1738</b>	<b>There is already a server running with id {0}, {1}.</b>
<b>WEPRME1739</b>	<b>Invalid ID {0} (must be numeric).</b>
<b>WEPRME1740</b>	<b>IndexedStorage should be initialized with an empty cache.</b>
<b>WEPRME1741</b>	<b>Unable to create temporary file for buffering the content of the reader.</b>
<b>WEPRME1742</b>	<b>Unable to read from temporary file.</b>
<b>WEPRME1743</b>	<b>Error during execution of Pull Query {0}.</b>
<b>Explanation</b>	A severe runtime error has occurred.
<b>Action</b>	Analyze detailed log information and the cause of the exception.
<b>WEPRME1744</b>	<b>Window specification using ROWS requires frame bounds to be of type LONG.</b>

---

<b>WEPRME1745</b>	<b>Window specification using RANGE requires the order-by column to be of numeric type. Found: {0}.</b>
<b>WEPRME1746</b>	<b>Window specification using RANGE requires at least one numeric order-by expression.</b>
<b>WEPRME1747</b>	<b>Window specification using RANGE and custom frame bounds requires exactly one numeric order-by expression.</b>
<b>WEPRME1748</b>	<b>Unable to prefetch data.</b>
<b>WEPRME1749</b>	<b>An error occurred during subscription handling.</b>
<b>WEPRME1750</b>	<b>Partition/Window entries are not comparable as the OVER clause did not contain an order-by expression.</b>
<b>WEPRME1751</b>	<b>Only expressions can be used as child nodes of window function {0}.</b>
<b>WEPRME1752</b>	<b>The user-defined function {0} cannot be used as a window function.</b>
<b>Explanation</b>	Only (user-defined) window functions and (user-defined) aggregate functions can be used as window functions. But the specified function is an user-defined function.
<b>Action</b>	Either replace the user-defined function by a (user-defined) window function or by an (user-defined) aggregate function or remove the window specification.
<b>WEPRME1753</b>	<b>The source {0} is ambiguous. Check if sources are properly renamed and no duplicate aliases are introduced.</b>
<b>WEPRME1754</b>	<b>The given window function does not allow the specification of a window frame.</b>
<b>WEPRME1755</b>	<b>The subquery used in WHERE clause produced a non-scalar result.</b>
<b>Explanation</b>	When neither ALL or ANY is specified only scalar subqueries can be used with a relational operator in a WHERE clause.
<b>Action</b>	Change the subquery such that it produces a scalar result.

<b>WEPRME1756</b>	<b>Unsupported XML entity: {0}</b>
<b>WEPRME1757</b>	<b>Unable to handle the JSON token "{0}".</b>
<b>WEPRME1758</b>	<b>Unable to parse the given JSON input: {0}</b>
<b>WEPRME1759</b>	<b>Unable to read the given JSON input.</b>
<b>WEPRME1760</b>	<b>Error converting value "{0}" of column "{1}" to type {2} due to the following issue: {3}</b>
<b>WEPRME1761</b>	<b>The JSON input contains an unmatched END-ARRAY token.</b>
<b>Explanation</b>	The underlying JSON parser produced an END-ARRAY token without an according START-ARRAY token.
<b>Action</b>	Check the processed JSON input.
<b>WEPRME1762</b>	<b>The JSON input contains an unexpected {0} token.</b>
<b>Explanation</b>	The JSON parser produced an unexpected token.
<b>Action</b>	Check the processed JSON input.
<b>WEPRME1763</b>	<b>The JSON input contains an unmatched START-OBJECT token.</b>
<b>Explanation</b>	The JSON parser produced a START-OBJECT token without an according END-Object token.
<b>Action</b>	Check the processed JSON input.
<b>WEPRME1764</b>	<b>Unable to read JSON input.</b>
<b>Explanation</b>	An I/O exception occurred while reading the JSON input.
<b>Action</b>	Check the processed JSON input.
<b>WEPRME1765</b>	<b>The connection locale may not be null.</b>

---

WEPRME1766	Unable to open the specified file {0}.
WEPRME1767	Unable to reset buffered reader.
WEPRME1769	The following error has been reported {0} times and any recurrences will be suppressed: {1}
WEPRME1770	Unable to compute stream metadata for user-defined source factory.
WEPRME1771	Exception occurred while inferring schema.
WEPRME1772	Super column value is incompatible with defined type. Configured "{0}" but actually was "{1}".
WEPRME1773	Super column metadata differs among source factories for the same pull source. Expected "{0}", but was "{1}".
WEPRME1774	SearchAttribute name at index {0} must not be null.
WEPRME1775	The given search attribute {0} cannot be found.
WEPRME1776	Dynamic indexing is not supported for search attribute {0} as it is of type {1}.
WEPRME1778	Return type of UDX {0} does not comply with the schema: expected {1} but found {2}.
WEPRME1779	Null not allowed as return value of UDX {0}.
WEPRME1780	Method getComputedNext() may only be used after next().

<b>WEPRME1781</b>	<b>Could not find a source node in external subquery graph.</b>
<b>WEPRME1782</b>	<b>Error closing communication: {0}.</b>
<b>WEPRME1784</b>	<b>Failed to create directory {0}.</b>
<b>WEPRME1786</b>	<b>Repository contains an artefact of unexpected type {0} with owner {1} and identifier {2} that is using a pull query.</b>
<b>WEPRME1787</b>	<b>Unable to parse the given XML document: {0}.</b>
<b>Explanation</b>	An error occurred while parsing the given XML document.
<b>Action</b>	Check the underlying exception's message
<b>WEPRME1788</b>	<b>The query language {0} is not supported.</b>
<b>Explanation</b>	The specified query language parameter is not supported by this method.
<b>Action</b>	Change the query language parameter to one of the supported query languages, e.g., SQL or XML.
<b>WEPRME1789</b>	<b>The constructor of RemotePullSourceFactory requires two to four parameters ([host [port]] user password).</b>
<b>Explanation</b>	The constructor was called with the wrong number of String arguments.
<b>Action</b>	Call the constructor with the parameters (host, port, user, password) or (host, user, password) or (user, password).
<b>WEPRME1790</b>	<b>Unable to prepare the XML representation of the external subquery for the remote RTM system.</b>
<b>Explanation</b>	An error occurred when preparing the external subquery that should be executed by the remote RTM system.
<b>WEPRME1791</b>	<b>The external subquery does not have any registered source.</b>

---

<b>WEPRME1792</b>	<b>The external subquery does have more than one registered source.</b>
<b>WEPRME1793</b>	<b>Grouping set(s) not supported in this context.</b>
<b>Explanation</b>	A query contained a group by clause that specifies any of GROUPING SETS, ROLLUP, or CUBE, or an empty grouping set. This is not supported with either a SetCondition, nor with push processing mode.
<b>Action</b>	Modify query in order to obey the restriction on grouping sets.
<b>WEPRME1794</b>	<b>Grouping operation argument must be a group expression.</b>
<b>Explanation</b>	The query contains a grouping operation with an invalid argument. The arguments of a grouping operation must be grouping expressions.
<b>Action</b>	Modify query to contain only group expressions as arguments of a grouping operation.
<b>WEPRME1795</b>	<b>Grouping-set bit index may not be larger than number of group expressions. Was {0} &gt; {1}.</b>
<b>WEPRME1796</b>	<b>Grouping-set multiplicity may not be less than 1. Was {0}.</b>
<b>WEPRME1797</b>	<b>Grouping-sets do not cover all group expressions. Uncovered indices: {0}.</b>
<b>WEPRME1798</b>	<b>The GROUPING function currently supports only up to 64 arguments. Found {0}.</b>
<b>WEPRME1799</b>	<b>Parallel computation of GROUPING-SETS operator was interrupted.</b>
<b>WEPRME1800</b>	<b>Exactly one parameter expected.</b>
<b>WEPRME1801</b>	<b>Parameter type not supported by wrapped Aggregator.</b>
<b>WEPRME1802</b>	<b>The given node does not provide a field name.</b>

- WEPRME1803**      **The group expression does not provide a field name.**
  
- WEPRME1804**      **Unsupported aggregation type {0}.**
  
- WEPRME1805**      **The aggregates attribute does not provide a field name.**
  
- WEPRME1806**      **Predicate is neither a logical operation, comparison nor boolean expression.**
  
- WEPRME1807**      **Neither attribute of the comparison is a field.**
  
- WEPRME1808**      **The sort specification does not provide a field name.**
  
- WEPRME1809**      **Mapping has a Field with childIndex > 0**
  
- WEPRME1810**      **The given attribute {0} is not contained in search attributes.**
  
- WEPRME1811**      **The given node is no constant.**
  
- WEPRME1812**      **Unable to extract record metadata.**
  
- WEPRME1813**      **Number of clusters (k) has to be greater than 0.**
  
- WEPRME1814**      **Number of iterations needs to be greater than 0.**
  
- WEPRME1815**      **Unknown measure {0}. Valid measures are: {1}.**
  
- WEPRME1816**      **Invalid or missing delimiter.**

---

WEPRME1817	Invalid or missing field index.
WEPRME1818	Getting an adapter factory for {0} was not successful.
WEPRME1819	Unknown raql window function type: {0}
WEPRME1820	SupportsReset is only allowed after init.
WEPRME1821	SupportsPeek is only allowed after init.
WEPRME1822	SupportsRemove is only allowed after init.
WEPRME1823	The SinglePullSourcePullSourceFactory only supports parameterless usage.
WEPRME1824	Left bounds other than UNBOUNDED PRECEDING or CURRENT ROW are not supported in this context.
WEPRME1825	Right bounds other than UNBOUNDED FOLLOWING or CURRENT ROW are not supported in this context.
WEPRME1826	Illegal frame bounds: {0} > {1}.
WEPRME1827	Operation type is unknown or can not be processed.
WEPRME1828	At least three items have to be allowed.
WEPRME1829	Legend must not be null!
WEPRME1830	Number of legends must be equal to number of chart types!

- WEPRME1831**      **Start and/or end does not fit actual day.**
  
- WEPRME1832**      **Unsupported message type: {0}.**
  
- WEPRME1833**      **Unsupported callback type.**
  
- WEPRME1834**      **Login only allowed for initialized login module.**
  
- WEPRME1835**      **Commit only allowed for login module after successful login.**
  
- WEPRME1836**      **Could not create login context.**
  
- WEPRME1837**      **Unknown Callback.**
  
- WEPRME1838**      **The GROUPING-SET operator's search lattice is expected to have only one single entry with key 'null' on its root level.**
  
- WEPRME1839**      **Master and slave produce different results.**
  
- WEPRME1840**      **The buffer must not be smaller than 1: {0}**
  
- WEPRME1841**      **The pre-fetching number must not be smaller than 1: {0}.**
  
- WEPRME1842**      **The pre-computing number must not be smaller than 1: {0}.**
  
- WEPRME1843**      **The result block size number must not be smaller than 1: {0}.**
  
- WEPRME1844**      **The pull result adapter must not be null.**

<b>WEPRME1845</b>	<b>The pull query could not be executed.</b>
<b>WEPRME1846</b>	<b>A subscription to a pull query was not possible.</b>
<b>WEPRME1847</b>	<b>The pull result adapter class must not be null.</b>
<b>WEPRME1848</b>	<b>Could not unsubscribe from pull query.</b>
<b>WEPRME1849</b>	<b>Unable to subscribe to pull query.</b>
<b>WEPRME1850</b>	<b>Subscriptions to pull queries are currently not supported in HA mode.</b>
<b>WEPRME1851</b>	<b>Users may only remove subscriptions from their own schema.</b>
<b>WEPRME1852</b>	<b>The pull result could not be closed.</b>
<b>WEPRME1853</b>	<b>Cannot change to existing remote connection id {0}.</b>
<b>WEPRME1854</b>	<b>Remote connection id does not match the Id defined by the current master.</b>
<b>WEPRME1855</b>	<b>The class could not be found.</b>
<b>WEPRME1856</b>	<b>ServerConnectionHandler may not be null.</b>
<b>WEPRME1857</b>	<b>Detected second master: {0} &lt;-&gt; {1}</b>
<b>WEPRME1858</b>	<b>The result adapter was already closed.</b>

- WEPRME1859**      **No adapter found for handling.**
  
- WEPRME1860**      **Error in handling remote subscription.**
  
- WEPRME1861**      **Class {0} does not provide a default constructor, which is obligatory.**
  
- WEPRME1862**      **A subscription with this name exists already.**
  
- WEPRME1863**      **Cannot make a persistent subscription to a non-persistent query.**
  
- WEPRME1864**      **Cannot unsubscribe from a subscription, which does not exist.**
  
- WEPRME1865**      **The provided subscription parameter should not be null.**
  
- WEPRME1866**      **The execution time must not be null.**
  
- WEPRME1867**      **A non-server subscription cannot be made persistent.**
  
- WEPRME1868**      **Logical Constant is not a boolean.**
  
- WEPRME1869**      **Child does not have REFERENCED\_FIELDS metadata.**
  
- WEPRME1870**      **Not implemented.**
  
- WEPRME1871**      **Unknown Predicate Type.**
  
- WEPRME1872**      **Could not find source of expression: {0}.**

WEPRME1873	Mapping has a Field with childIndex > 0.
WEPRME1874	Parent grouping-set has not been set yet.
WEPRME1875	Rule broken: inverse map does not contain the source of a referenced field.
WEPRME1876	Mappings are not supposed to have ANCHOR->CHILD_INDEX != 0.
WEPRME1877	Query Graph broken: Found a Field with child != 0 at Order Node: ({0}, {1}).
WEPRME1878	Field does not contain field index.
WEPRME1879	Found EQUI-Join with 0 equi-fields.
WEPRME1880	Cannot handle multiway NATURAL JOIN.
WEPRME1881	Columns named by {0} cannot be unified because of different types.
WEPRME1882	Found NATURAL-Join with 0 join-candidates.
WEPRME1883	Optimizer cannot handle IN(subquery), yet.
WEPRME1884	Unknown Node type encountered: {0}.
WEPRME1885	Argument is not a predicate.
WEPRME1886	Found NOT with {0} child nodes.

- WEPRME1887** Found NOT with a child that's no predicate (is {0}).
  
- WEPRME1888** getAnd() called with less than 1 node.
  
- WEPRME1889** Argument is not an expression.
  
- WEPRME1890** Non-String Signature Key found: {0}.
  
- WEPRME1891** Unknown Node-Type: {0}.
  
- WEPRME1892** Unhandled enum entry: {0}.
  
- WEPRME1893** Aggregate is configured to have{0} arguments, but has actually {1} arguments.
  
- WEPRME1894** WindowFunction is configured to have {0} arguments, but has actually {1} arguments.
  
- WEPRME1895** Aggregate is configured to have {0} arguments, but has actually {1} arguments.
  
- WEPRME1896** UNEXPECTED.
  
- WEPRME1897** Function {0} only supports Double and Float values.
  
- WEPRME1898** Function {0} only supports numeric values.
  
- WEPRME1899** Offset must not be negative.
  
- WEPRME1900** Unknown frame unit: {0}.

---

WEPRME1901	Function {0} must have exactly one sub-expression.
WEPRME1902	Function {0} must not have more than one sub-expression.
WEPRME1903	Unsupported method.
WEPRME1904	Communication is already closed.
WEPRME1905	Unhandled communication type: {0}.
WEPRME1906	EhcacheBasedLinkedList should be initialized with an empty cache.
WEPRME1907	Index: {0}, Size: {1}.
WEPRME1908	Not feasible to copy the whole OffHeap list into the Java heap.
WEPRME1909	fromIndex = {0}
WEPRME1910	toIndex = {0}
WEPRME1911	fromIndex({0}) > toIndex({1})
WEPRME1912	next() has been called at all or after remove() has been called.
WEPRME1913	nextPos() has been called, or remove() has been called after the last call to nextPos().
WEPRME1914	At least one feature toggle did not satisfy the given assertions. {0}

- WEPRME1915**      **AttributeName unknown: {0}.**
  
- WEPRME1916**      **No standard filter: {0}.**
  
- WEPRME1917**      **Unknown type: {0}.**
  
- WEPRME1918**      **Failed to activate metadata handler for metadata identifier {0}.**
  
- WEPRME1919**      **The DynamicMetaDataManager is not registered.**
  
- WEPRME1920**      **This XmlPullSourceFactory accepts at most 2 instantiation parameters. Got {0}.**
  
- WEPRME1921**      **The number of instantiation parameters does not match the number of instantiation parameter types ({0} <> {1}).**
  
- WEPRME1922**      **Expected STRING instantiation parameter type at index {0}, found {1}.**
  
- WEPRME1923**      **Unhandled sink adapter type/approach: {0}.**
  
- WEPRME1924**      **Parent grouping-set has already been set and cannot be overridden.**
  
- WEPRME1925**      **Graph node is already defined: {0}.**
  
- WEPRME1926**      **Unknown graph node: {0}.**
  
- WEPRME1927**      **BigMemory does not support consecutive aggregations and applying criterias after aggregating.**
  
- WEPRME1928**      **BigMemory does not support limiting the number of elements that are aggregated, ordered and applied criterias to.**

---

WEPRME1929	This aggregation function does not support merging multiple aggregation states into one.
WEPRME1931	The value {0} cannot be rounded to a {1} value since it is greater than the maximum or less than the minimum {1} value.
WEPRME1932	Argument is not a field.
WEPRME1933	The parameter n must be greater than 0.
WEPRME1934	Target array is too short. Required array size is: {0}.
WEPRME1935	Chunksize must be greater than 0.
WEPRME1936	The parameter "times" must be greater than 0.
WEPRME1937	Unable to close JSON parser.
WEPRME1938	Namespace with index {0} does not exist.
WEPRME1941	Result of operation was not a number.
WEPRME1942	Result of operation was infinite.
WEPRME1943	An overflow occurred in aggregation {0} of type {1}.
WEPRME1944	An overflow occurred in function {0} of type {1}.
WEPRME1947	DISTINCT aggregates cannot be pushed-down: {0}.

- WEPRME1948      Aggregates on constant values cannot be pushed-down: {0}.
  
- WEPRME1949      Expressions on constant values cannot be pushed-down: {0}.
  
- WEPRME1950      Comparisons on two variables cannot be pushed-down: {0}.
  
- WEPRME1951      Comparisons of type {0} cannot be pushed-down.
  
- WEPRME1952      Cannot cast from {0} to {1}: {2}.
  
- WEPRME1953      The expression of type {0} cannot be pushed down: {1}.
  
- WEPRME1954      Unexpected data type {0} for expression {1}.
  
- WEPRME1955      Illegal constant expression '\*'.
  
- WEPRME1956      The aggregate of type {0} cannot be pushed-down: {1}.
  
- WEPRME1957      Unknown cell definition: {0} (type {1}).
  
- WEPRME1958      Operation {0} on two cells cannot be pushed-down.
  
- WEPRME1959      DIVISION with constant dividend is not supported in TC Store.
  
- WEPRME1960      Integer DIVISION cannot be pushed-down.
  
- WEPRME1961      Error parsing string {0} to XML document: {1}

---

WEPRME1962	Order expression cannot be pushed down to TC Store, as it may yield null values, which cannot be sorted properly.
WEPRME1963	AGGREGATION with HAVING predicate cannot be pushed down.
WEPRME1964	GROUP BY on constant expression cannot be pushed-down.
WEPRME1965	GROUP BY on complex {0} expression cannot be pushed down.
WEPRME1966	No aggregates to push-down.
WEPRME1967	OPERATOR of type {0} cannot be pushed-down.
WEPRME1968	ORDER BY on a constant expression cannot be pushed down.
WEPRME1969	The data type {0} is not supported: {1}.
WEPRME1970	The IN predicate's list may only contain constant expressions.
WEPRME1971	The IN predicate's 'member' expression may not be constant: {0}.
WEPRME1972	Operator {0} may not operate on a derived/non-record stream.
WEPRME1973	Unsupported predicate type {0}.
WEPRME1974	Wrong parameter type {0}. Expected STRING.
WEPRME1975	Unsupported type in ORDER BY clause: {0}.

- WEPRME1976**      **CellDefinition is expected to have type {0}. Found {1}.**
  
- WEPRME1977**      **Complex GROUPING SETS cannot be pushed down.**
  
- WEPRME1978**      **GROUPING expressions cannot be pushed down.**
  
- WEPRME1979**      **Unexpected number of child nodes. Expected {0}, but was {1}.**
  
- WEPRME1980**      **The MAPPING is not a plain projection and cannot be pushed down.**
  
- WEPRME1981**      **The projection mapping is a parent of non-schema preserving operator and cannot be pushed down.**
  
- WEPRME1982**      **The projection mapping is a child of a DISTINCT operator and cannot be pushed down.**
  
- WEPRME1983**      **Missing XML element: {0}.**
  
- WEPRME1984**      **The TCStore type {0} cannot be mapped to a corresponding RTM type.**
  
- WEPRME1985**      **RTM type {0} cannot be mapped to corresponding TC Store type.**
  
- WEPRME1986**      **Wrong parameter "{0}". Expected {1}.**
  
- WEPRME1987**      **Wrong number of instantiation parameters: Expected 0 or 1, but was {0}.**
  
- WEPRME1988**      **CellCollection has no value for field {0}, but field must not be nullable.**
  
- WEPRME1989**      **Conversion of RTM record to TC record failed, as value for not-nullable field {0} is NULL.**

---

WEPRME1990	RTM type {0} is not supported when converting RTM record to TC record using match mode {1}.
WEPRME1992	Column name "{0}" is not unique within the given schema and needs to be renamed.
WEPRME1993	Case insensitive String or Character comparisons are not supported by TC Store.
WEPRME1994	Cannot group on case insensitive STRING/CHARACTER in TC Store.
WEPRME1995	The user-defined data type {0} is not supported for serialization to a DES event.
WEPRME1996	The data type {0} is not supported for perfect serialization to a DES event.
WEPRME1997	The DES data type {0} is not supported for perfect serialization to a record.
WEPRME1998	The record's key cannot be referenced in arbitrary expressions.
WEPRME1999	The field to translate is not a key field: {0}.
WEPRME2000	Key column "{0}" could not found in schema.
WEPRME2001	Key column name "{0}" is not unique within the given schema.
WEPRME2002	The {0} data type cannot be compared or sorted.
WEPRMI0001	Initializing RTM system.
WEPRMI0002	Configuring persistent RTM system.

- WEPRMI0003**      **Initialization of RTM system finished.**
  
- WEPRMI0004**      **Starting RTM system.**
  
- WEPRMI0005**      **Start of RTM system finished.**
  
- WEPRMI0006**      **Shutting down RTM system.**
  
- WEPRMI0007**      **Shutdown of RTM system is finished.**
  
- WEPRMI0008**      **User {0} trying to locally connect to RTM system.**
  
- WEPRMI0009**      **User {0} connected to RTM system.**
  
- WEPRMI0010**      **Current HA role is {0}.**
  
- WEPRMI0013**      **HA role has been set to {0}.**
  
- WEPRMI0015**      **Slave is preparing recovery.**
  
- WEPRMI0016**      **Slave requesting recovery from master.**
  
- WEPRMI0017**      **Master has started sending recovery data to slave.**
  
- WEPRMI0018**      **Master finished sending recovery data to slave.**
  
- WEPRMI0019**      **Slave has started processing recovery request from master.**

<b>WEPRMI0020</b>	<b>Slave successfully finished processing recovery request from master.</b>
<b>WEPRMI0021</b>	<b>Server with newer build number {0} connected as slave.</b>
<b>WEPRMI0025</b>	<b>Aborted handshake due to shutdown.</b>
<b>WEPRMI0026</b>	<b>Handshake with remote RTM system successfully finished.</b>
<b>WEPRMI0027</b>	<b>Snapshot reducibility has been determined for the following query; Owner:{0}; Identifier:{1}; SQL:{2}; Snapshot reducible from:{3};</b>
<b>WEPRMI0028</b>	<b>Could not connect to a running high-availability peer, now attempting to acquire master lock.</b>
<b>WEPRMI1376</b>	<b>Properties of RTM system: {0}</b>
<b>WEPRMI1377</b>	<b>Properties of JPA : {0}</b>
<b>WEPRMI1412</b>	<b>Remote connection server is shutting down.</b>
<b>WEPRMI1413</b>	<b>Client starts close procedure.</b>
<b>WEPRMI1414</b>	<b>Client finishes close procedure.</b>
<b>WEPRMI1415</b>	<b>Client marks connection as broken for address {0}.</b>
<b>WEPRMI1416</b>	<b>Client shuts down broken connection to address {0}.</b>
<b>WEPRMI1417</b>	<b>Local connection is closed due to {0}.</b>

- WEPRMI1419**      **Closing HA result transmission query {0}.**
  
- WEPRMI1420**      **Shutting down remote connection handler with remote connection id {0}.**
  
- WEPRMI1426**      **Starting to accept new connections on address {0}.**
  
- WEPRMI1430**      **Stopped accepting new connections on address {0}.**
  
- WEPRMI1446**      **Re-authentication at remote RTM system finished successfully.**
  
- WEPRMI1697**      **Client marks connection as shutting down: {0}**
  
- WEPRMI1698**      **Client shuts down connection: {0}, isClosing={1}.**
  
- WEPRMI1699**      **Client starts recovering connection to {0}.**
  
- WEPRMI1700**      **Client is successfully connected to {0}.**
  
- WEPRMI1701**      **Ignored NPE when sending {0} to {1}.**
  
- WEPRMI1724**      **{0} (connectable source {1})**
  
- WEPRMI1733**      **Nested exceptions:**
  
- WEPRMI1734**      **Combined exceptions**
  
- WEPRMI1785**      **Starting RTM system (version={0} built at {1}).**

<b>WEPRMI1945</b>	<b>TCP/IP communication server is listening on local port {0}.</b>
<b>WEPRMW0001</b>	<b>Unable to shut down RTM system's persistence manager.</b>
<b>WEPRMW0002</b>	<b>Unable to shut down communication servers.</b>
<b>WEPRMW0003</b>	<b>Unable to stop communication server.</b>
<b>WEPRMW0004</b>	<b>Unable to stop communication client.</b>
<b>WEPRMW0005</b>	<b>Unable to shut down client connection handler.</b>
<b>WEPRMW0006</b>	<b>Unable to shut down server connection handler.</b>
<b>WEPRMW0007</b>	<b>Unable to connect to high availability partner.</b>
<b>WEPRMW0008</b>	<b>Unable to shut down master connection handler.</b>
<b>WEPRMW0009</b>	<b>Unable to send for slave health request.</b>
<b>WEPRMW0010</b>	<b>Server with older build number {0} connected as slave.</b>
<b>WEPRMW0011</b>	<b>Unable to shut down slave connection handler.</b>
<b>WEPRMW0012</b>	<b>Unable to send for master health request.</b>
<b>WEPRMW0017</b>	<b>Unable to call a task on the decoupled sink adapter.</b>

<b>WEPRMW0018</b>	<b>Authentication with remote RTM system contains illegal commands.</b>
<b>WEPRMW1329</b>	<b>Caught exception during operator initialization.</b>
<b>WEPRMW1330</b>	<b>Caught exception during heartbeat processing from input {0}.</b>
<b>WEPRMW1331</b>	<b>Caught exception while closing operator.</b>
<b>WEPRMW1332</b>	<b>Caught exception processing done signal from input {0}.</b>
<b>WEPRMW1333</b>	<b>Error processing element of index {0}.</b>
<b>WEPRMW1334</b>	<b>Caught exception while opening operator.</b>
<b>WEPRMW1410</b>	<b>Status of local system is not OK; shutting down!</b>
<b>WEPRMW1411</b>	<b>Status of cluster is not OK; shutting down!</b>
<b>WEPRMW1421</b>	<b>Received a shutdown notification from HA {0} with HA communication address {1}.</b>
<b>WEPRMW1422</b>	<b>Server ({0}) lost connection to HA partner system.</b>
<b>WEPRMW1423</b>	<b>Server is shutting down broken connection for address {0} as communication to master has been lost.</b>
<b>Explanation</b>	This message appears in the log of an HA slave when it loses its connection to a master that supports remote connections. It indicates why clients will lose their connection to that address.
<b>Action</b>	Check other messages to see if the reason for the lost connection can be found.

---

<b>WEPRMW1522</b>	<b>Aborting authentication with remote RTM system.</b>
<b>WEPRMW1687</b>	<b>Rule-based optimization failed due to: {0}</b>
<b>Explanation</b>	The optimizer has failed optimizing the query and failed back to a non-optimized query.
<b>WEPRMW1694</b>	<b>Master identifies himself with different address. Is {0}, not {1}.</b>
<b>WEPRMW1695</b>	<b>Still connected to old slave.</b>
<b>WEPRMW1768</b>	<b>External Subquery Translation failed. Reason was: {0}</b>
<b>Explanation</b>	The user query was optimized but the external subquery translation has failed to translate the logical query graph. This could under the circumstances result in a slower query performance.
<b>Action</b>	Try to rewrite the query or contact your local software supplier.
<b>WEPRMW1777</b>	<b>Search attribute {0} has been skipped as dynamic indexing is not supported for type {1}.</b>
<b>WEPRMW1783</b>	<b>Buffer file "{0}" could not be deleted: {1}.</b>
<b>WEPRMW1939</b>	<b>Unable to expand the explicit sub-query {0} for non-incremental query optimization.</b>
<b>WEPRMW1940</b>	<b>BigMemory was not able to execute the Search API query against a cache.</b>
<b>WEPRMW1946</b>	<b>Exact average value {0} is not accurately representable as a double. The BigDecimal representation is {1}.</b>
<b>WEPRMW1991</b>	<b>{0} push-down failed as there already is an Aggregation being pushed-down.</b>



# 25 Security Messages

---

<b>SINAZE0000</b>	<b>FileBasedAuthzStoreImpl: Storage cannot be loaded: {0}</b>
<b>Explanation</b>	Role storage (roles.txt) can not be loaded.
<b>Action</b>	Check the existance of the roles.txt file or the relevant storage.
<b>SINAZE0001</b>	<b>FileBasedAuthzStoreImpl: Storage location {0} is missing.</b>
<b>Explanation</b>	Role storage (roles.txt) is missing.
<b>Action</b>	The location passed to the service does not point to the existing file/storage. Check the availablity to the file.
<b>SINAZE0002</b>	<b>Cannot open storage file {0}</b>
<b>Explanation</b>	Role storage (roles.txt) cannot be opened.
<b>Action</b>	Check if the storage (file) is available and accessible.
<b>SINAZE0003</b>	<b>{0} is not readable!</b>
<b>Explanation</b>	Role storage (roles.txt) cannot be read.
<b>Action</b>	Check if the storage (file) has proper access rights, and whether it is not locked.
<b>SINAZE0004</b>	<b>Invalid entry in storage file. Invalid line in the storage file.</b>
<b>Explanation</b>	Role storage (roles.txt) syntax is not correct. Invalide entry is found.
<b>Action</b>	Check the storage (file) and validate the syntax.

<b>SINAZE0005</b>	<b>cannot open {0}</b>
<b>Explanation</b>	Role storage (roles.txt) cannot be opened/accessed.
<b>Action</b>	Check the storage (file).
<b>SINAZE0006</b>	<b>Cannot write to storage file {0}. File does not exist.</b>
<b>Explanation</b>	Cannot write to storage file. File does not exist.
<b>Action</b>	Check the availability of the storage/file.
<b>SINAZE0007</b>	<b>{0} is not writable!</b>
<b>Explanation</b>	Role storage (roles.txt) is not editable.
<b>Action</b>	Check access rights for the storage file.
<b>SINESE0000</b>	<b>/{0} not found.</b>
<b>Explanation</b>	Internal error. A file used by the product is missing.
<b>Action</b>	Contact SoftwareAG global support.
<b>SINESE0001</b>	<b>Error loading /{0}</b>
<b>Explanation</b>	Internal error. A file used by the product cannot be processed.
<b>Action</b>	Contact SoftwareAG global support.
<b>SINESE0002</b>	<b>/{0} not found.</b>
<b>Explanation</b>	Internal error. A validation properties file used by the product is missing.
<b>Action</b>	Contact SoftwareAG global support.
<b>SINESE0003</b>	<b>Error loading /{0}</b>
<b>Explanation</b>	Internal error. A validation properties file used by the product cannot be processed.
<b>Action</b>	Contact SoftwareAG global support.
<b>SINESE0004</b>	<b>Unknown System Type!</b>
<b>Explanation</b>	System type cannot be recognized.
<b>Action</b>	Contact SoftwareAG global support.

---

<b>SINESE0005</b>	<b>System property {0} is set, but file '{1}' doesn't exist</b>
<b>Explanation</b>	System property com.softwareag.sin.esapi.resources has a value that points to an invalid file or a file that doesn't have proper rights.
<b>Action</b>	Check the value of the system property com.softwareag.sin.esapi.resources and update it to point to a valid readable ESAPI.properties file.
<b>SINJCE0003</b>	<b>Initialize: JAAS property not set: {0}</b>
<b>Explanation</b>	The login module requires a 'DUMMY_USER_PROPERTY_URL' option representing a URL to the user properties file to load, but such option is not configured.
<b>Action</b>	Configure a 'DUMMY_USER_PROPERTY_URL' option for the DummyLoginModule. The option value must be a URL to a standard Java properties file containing users, groups and roles information.
<b>SINLDE0048</b>	<b>Authentication failed</b>
<b>Explanation</b>	LDAPLoginModule - authentication against LDAP failed. User name or password are wrong.
<b>Action</b>	Re-enter the user name and password. Check if their values are correct.
<b>SINLDE0056</b>	<b>No configured servers.</b>
<b>Explanation</b>	No configured servers were found.
<b>Action</b>	Ensure that the servers are configured properly.
<b>SINLDE0057</b>	<b>No configured servers.</b>
<b>Explanation</b>	No configured servers were found.
<b>Action</b>	Ensure that the servers are configured properly.
<b>SINLDE0058</b>	<b>No configured servers.</b>
<b>Explanation</b>	No configured servers were found.
<b>Action</b>	Ensure that the servers are configured properly.
<b>SINLDE0059</b>	<b>No configured servers.</b>
<b>Explanation</b>	No configured servers were found.
<b>Action</b>	Ensure that the servers are configured properly.

<b>SINLDE0060</b>	<b>LDAP keystore load error</b>
<b>Explanation</b>	An error occurred during extraction of a keystore. Possible causes are invalid URL, invalid algorithm, invalid certificate, invalid argument, etc.
<b>Action</b>	Ensure that the requested keystore and its URL are valid.
<b>SINLDE0061</b>	<b>LDAP truststore load error.</b>
<b>Explanation</b>	An error occurred during extraction of a truststore. Possible causes are invalid URL, invalid algorithm, invalid certificate, invalid argument, etc.
<b>Action</b>	Ensure that the requested truststore and its URL are valid.
<b>SINLDE0062</b>	<b>This principal {0} is with wrong type. Should be {1}</b>
<b>Explanation</b>	An error occurred while checking principal type. The principal type must be GROUP_TYPE.
<b>Action</b>	Change the principal type to GROUP_TYPE.
<b>SINLDW0063</b>	<b>More than one result returned uidprop: {0} uid: {1}</b>
<b>Explanation</b>	A single result is expected when getting DN from UID.
<b>Action</b>	Ensure that the UID contains a single DN corresponding to the search filter.
<b>SINLDW0064</b>	<b>More than one result returned gidprop: {0} gid: {1}</b>
<b>Explanation</b>	A single result is expected when getting DN from GID.
<b>Action</b>	Ensure that the GID contains a single DN corresponding to the search filter.
<b>SINLDW0066</b>	<b>Problem listing group properties.</b>
<b>Explanation</b>	An issue has occurred while listing group properties.
<b>Action</b>	Ensure that the group properties are valid.
<b>SINLDW0067</b>	<b>Empty [DN Prefix/Suffix]</b>
<b>Explanation</b>	Empty DN Prefix and DN Suffix were found when listing users during an LDAP configuration.
<b>Action</b>	Ensure that the DN Prefix and/or DN Suffix are present.

---

<b>SINLDW0070</b>	<b>Problem checking if DN is a group.</b>
<b>Explanation</b>	There was an issue while checking if the DN is a group when trying to get the group ID.
<b>Action</b>	Ensure that the DN is a group.
<b>SINLDW0071</b>	<b>Problem checking if dn is a user</b>
<b>Explanation</b>	There was an issue while checking if the DN is a user when trying to get the user ID
<b>Action</b>	Ensure that the DN is a user.
<b>SINLDW0081</b>	<b>Property {0} is unknown, but is found in server configuraion. Please check spelling of the properties.</b>
<b>Explanation</b>	A wrong property was found in the server configuration. Properties are case sensitive.
<b>Action</b>	Check the spelling and capitalization of the properties in the server configuration.
<b>SINLME0012</b>	<b>Initialize: failed to create X509CRL from the CRL URL: {0} {1}</b>
<b>Explanation</b>	CRLException was thrown during the initialization of the CRL. Possible reasons: the CRL file is broken or it is not in CRL format - <a href="http://docs.oracle.com/javase/7/docs/api/java/security/cert/X509CRL.html">http://docs.oracle.com/javase/7/docs/api/java/security/cert/X509CRL.html</a> .
<b>Action</b>	Double check in the JAAS configuration the value of the "crl_url" property and verify if the defined CRL file is a valid CRL file.
<b>SINLME0013</b>	<b>Initialize: failed to create URL or InputStream from the CRL URL: {0} {1}</b>
<b>Explanation</b>	IOException exception during initialization of the CRL. Possible reasons: the URL is broken or the file is not found.
<b>Action</b>	Double check in the JAAS configuration the value of the "crl_url" property and verify if this is a valid URL. If the CRL is on the file system, make sure the value for the "crl_url" begins with "file://".
<b>SINLME0014</b>	<b>Initialize: failed to create CRL - CRL location: {0} {1}</b>
<b>Explanation</b>	Unknown exception during initialization of the CRL.
<b>Action</b>	Double check the log files about the exception type and the explanation.

<b>SINLME0015</b>	<b>Initialize: CRL location is not specified.</b>
<b>Explanation</b>	The "check_crl_status" property is set to true but the "crl_url" property is not set up.
<b>Action</b>	1. Disable CRL check by setting up the "check_crl_status" property to false or by removing it; 2. Specify the "crl_url" property correctly.
<b>SINLME0190</b>	<b>login: unsupported callback {0}</b>
<b>Explanation</b>	Supplied Callback is not supported. Software AG Security Infrastructure supports only SagCredentialCallback, PasswordCallback and NameCallback.
<b>Action</b>	Check which Callback is used.
<b>SINLME0191</b>	<b>Engine failed to load with options: {0}</b>
<b>Explanation</b>	Authentication failed in RoleLoginModule. Storage is not loaded properly.
<b>Action</b>	Check logs for more details about the reasons.
<b>SINLME0192</b>	<b>Provider class cannot be found {0}</b>
<b>Explanation</b>	Role storage implementation provider is not found.
<b>Action</b>	Check the value of the "provider_class" property in the JAAS configuration file.
<b>SINLME0193</b>	<b>Provider class cannot be instantiated {0}</b>
<b>Explanation</b>	Role storage implementation provider cannot be instantiated.
<b>Action</b>	Check the value of the "provider_class" property in the JAAS configuration file.
<b>SINLME0194</b>	<b>Provider class cannot be accessible {0}</b>
<b>Explanation</b>	Role storage implementation provider class is not accessible.
<b>Action</b>	Check the value of the "provider_class" property in JAAS configuration file. Check classloaders, if the requested provider class is available.
<b>SINLME0195</b>	<b>resolveArtifact: ArtifactParseException {0}</b>
<b>Explanation</b>	An error occurred while parsing the artifact.
<b>Action</b>	Check the JAAS configuration.

---

<b>SINLME0197</b>	<b>resolveArtifact: ArtifactParserException {0}</b>
<b>Explanation</b>	An error occurred while parsing the artifact.
<b>Action</b>	Check the JAAS configuration.
<b>SINLME0198</b>	<b>resolveArtifact: Exception {0}</b>
<b>Explanation</b>	An error occurred while parsing the artifact.
<b>Action</b>	Check the JAAS configuration.
<b>SINLME0199</b>	<b>resolveArtifact: no name could be found in the SAML response. Returning NULL.</b>
<b>Explanation</b>	No name was found in the parsed artifact and the resolving failed.
<b>Action</b>	Check the JAAS configuration and the artifact creator.
<b>SINLME0204</b>	<b>authenticate() failed. Principal not available in the servlet request.</b>
<b>Explanation</b>	The configuration requires a principal, but the HTTP request does not contain one.
<b>Action</b>	Check the JAAS configuration.
<b>SINLME0205</b>	<b>authenticate() failed. X509Certificate Chain is not available in the servlet request.</b>
<b>Explanation</b>	The configuration requires a certificate, but the HTTP request does not contain one.
<b>Action</b>	Check the JAAS configuration.
<b>SINLME0206</b>	<b>authenticate() failed. SAML Artifact is not available in the servlet request.</b>
<b>Explanation</b>	The configuration requires a SAML artifact, but the HTTP request does not contain one.
<b>Action</b>	Check the JAAS configuration.
<b>SINLME0207</b>	<b>authenticate() failed. SAML Artifact header field name is not set in the JAAS configuration.</b>
<b>Explanation</b>	The configuration expects to find the HTTP header field used to search for a SAML Artifact, but the HTTP header is not set.
<b>Action</b>	Check the JAAS configuration.

<b>SINLME0208</b>	<b>authenticate() failed. Netegrity SiteMinder is not available in the servlet request.</b>
<b>Explanation</b>	The configuration requires a Netegrity SiteMinder, but the HTTP request does not contain one.
<b>Action</b>	Check the JAAS configuration.
<b>SINLME0209</b>	<b>authenticate() failed. Netegrity SiteMinder header field name is not set in the JAAS configuration.</b>
<b>Explanation</b>	The configuration expects to find the HTTP header field used to search for a Netegrity SiteMinder, but the HTTP header is not set.
<b>Action</b>	Check the JAAS configuration.
<b>SINLME0210</b>	<b>authenticate() failed. '{0}' custom header is not available in the servlet request.</b>
<b>Explanation</b>	The configuration requires a custom header name, but the HTTP request does not contain one.
<b>Action</b>	Check the JAAS configuration.
<b>SINLME0211</b>	<b>authenticate() failed. Custom header name property is not set in the JAAS configuration.</b>
<b>Explanation</b>	The configuration expects to find the HTTP header field used to search for a custom header, but the HTTP header is not set.
<b>Action</b>	Check the JAAS configuration.
<b>SINLME0212</b>	<b>authenticate: SAML Assertion identity provider key not available. Authentication failed.</b>
<b>Explanation</b>	The SAML Assertion identity provider key is not available.
<b>Action</b>	Check the JAAS configuration.
<b>SINLME0213</b>	<b>authenticate: SAML Assertion validation process failed. Authentication failed.</b>
<b>Explanation</b>	The SAML Assertion validation process failed.
<b>Action</b>	Check the JAAS configuration.
<b>SINLME0214</b>	<b>authenticate: no username returned. Authentication failed.</b>
<b>Explanation</b>	The SAML assertion does not contain a username.
<b>Action</b>	Check the JAAS configuration.

---

<b>SINLME0215</b>	<b>initConfiguration: failed!</b>
<b>Explanation</b>	An error was found in the LoginModule configuration.
<b>Action</b>	Check the JAAS configuration.
<b>SINLME0216</b>	<b>Initialize: trust store location is not specified. The default one will be used: {0}; trust store type: {1}</b>
<b>Explanation</b>	The trust store location is not specified and the default one will be used.
<b>Action</b>	Check the JAAS configuration.
<b>SINLME0217</b>	<b>Initialize: failed to create KeyStore from the trust store URL: {0}, keystore type: {1}</b>
<b>Explanation</b>	Failed to create a KeyStore from the trust store url.
<b>Action</b>	Check the JAAS configuration.
<b>SINLME0218</b>	<b>Failed to read certificate from trust store!</b>
<b>Explanation</b>	Failed to read the certificate from the trust store.
<b>Action</b>	Check the JAAS configuration.
<b>SINLME0219</b>	<b>validateAssertion: no name could be found in the SAML assertion</b>
<b>Explanation</b>	The SAML assertion does not contain a username.
<b>Action</b>	Check the JAAS configuration.
<b>SINLME0220</b>	<b>authenticate() failed. Basic authentication information is not available in the servlet request.</b>
<b>Explanation</b>	The configuration requires Basic authentication information, but the HTTP request does not contain it.
<b>Action</b>	Check the JAAS configuration.
<b>SINLME0221</b>	<b>authenticate() failed. The Authorization header required for Basic authentication is not available in the servlet request.</b>
<b>Explanation</b>	The configuration expects to find the Authorization HTTP header, but the HTTP header is not set.
<b>Action</b>	Check the JAAS configuration.

<b>SINLME0222</b>	<b>initConfiguration: failed! Can not load the key store {0}</b>
<b>Explanation</b>	Failed to initiate the configuration on the AppleDSLoginModule. Cannot load truststore.
<b>Action</b>	Verify that the location of the truststore is valid, the file is not corrupted and password is not missing or invalid.
<b>SINLME0223</b>	<b>Error in parsing the HTTP header cookie: {0}</b>
<b>Explanation</b>	An error occurred while authenticating with the AppleDSLoginModule.
<b>Action</b>	Make sure that the HTTP request is valid and contains all required headers.
<b>SINLME0224</b>	<b>authenticate: There is no cookie header in the HttpServletRequest.</b>
<b>Explanation</b>	While trying to authenticate with AppleDSLoginModule, the cookie header could not be found in the HttpServletRequest.
<b>Action</b>	Make sure that the HTTP request is valid and contains all required headers.
<b>SINLME0225</b>	<b>Cookie is not found in cookie header.</b>
<b>Explanation</b>	While trying to authenticate with AppleDSLoginModule, the cookie could not be found in the cookie header.
<b>Action</b>	Make sure that the HTTP request is valid and contains all required headers.
<b>SINLME0226</b>	<b>Cannot read response data</b>
<b>Explanation</b>	A read error occurred while trying to parse the input content.
<b>Action</b>	Make sure that the HTTP response does not contain corrupted data.
<b>SINLME0227</b>	<b>The personal id - {0}, is not returned by the server</b>
<b>Explanation</b>	The user principal does not contain a name attribute. The name attribute is expected from the HTTP response.
<b>Action</b>	Make sure that HTTP request is present and contains all necessary data. Check whether the login module is configured with the proper personal ID.
<b>SINLME0228</b>	<b>AppleUrlCreator could not be created. Invalid parameters.</b>
<b>Explanation</b>	An error has occurred while trying to create an instance of AppleUrlCreator. The input parameters are NULL.
<b>Action</b>	Make sure that HTTP request is present and contains all necessary data. Check whether the login module is configured with the proper cookie header.

---

<b>SINLME0229</b>	<b>constructURL: Neither URL ({0}), nor URL without query ({1}) is specified</b>
<b>Explanation</b>	An error occurred when trying to construct a URL, because the URL is not specified in the configuration.
<b>Action</b>	Make sure you correctly specify an URL in the configuration.
<b>SINLME0230</b>	<b>constructURL: Application admin password ({0}) is required!</b>
<b>Explanation</b>	An error occurred when trying to construct a URL, because the application administrator password is not specified in the configuration.
<b>Action</b>	Make sure you correctly specify the application administrator password in the configuration.
<b>SINLME0231</b>	<b>Application ID ({0}) is not specified as config property.</b>
<b>Explanation</b>	If the auth URL contains an <appId> placeholder, the application ID be must also be specified as a property.
<b>Action</b>	Set the application ID property.
<b>SINLME0232</b>	<b>Application ID ({0}) is not specified in the URL</b>
<b>Explanation</b>	The application ID must be contained in the authentication URL.
<b>Action</b>	Make sure that the application ID is contained in the URL.
<b>SINLME0233</b>	<b>The IP placeholder - {0}, could not be found in the URL</b>
<b>Explanation</b>	The auth URL must contain the IP placeholder.
<b>Action</b>	Make sure that the machine IP is contained in the URL.
<b>SINLME0234</b>	<b>The application admin password placeholder - {0}, could not be found in the URL</b>
<b>Explanation</b>	The auth URL must contain the application admin password placeholder.
<b>Action</b>	Make sure that the application admin password placeholder is contained in the URL.
<b>SINLME0235</b>	<b>The cookie placeholder - {0}, could not be found in the URL</b>
<b>Explanation</b>	The auth URL must contain the cookie placeholder.
<b>Action</b>	Make sure that the cookie placeholder is present in the URL.

<b>SINLME0236</b>	<b>Cannot create URL from {0}</b>
<b>Explanation</b>	An error occurred while trying to create a URL from the auth URL.
<b>Action</b>	Make sure that the authentication URL is valid and does not contain any restricted characters.
<b>SINLME0237</b>	<b>CookieValidator: Validation failed while reading URL data.</b>
<b>Explanation</b>	The URL validation failed while reading URL data.
<b>Action</b>	Make sure that the response from the URL does not contains corrupted data.
<b>SINLME0238</b>	<b>Validation failed! The URL is not specified.</b>
<b>Explanation</b>	The URL validation failed - the URL is NULL.
<b>Action</b>	Make sure that the provided authentication URL is valid.
<b>SINLME0241</b>	<b>Validation failed! Invalid line in the HTTP response.</b>
<b>Explanation</b>	Content validation failed due to an invalid line in the HTTP response.
<b>Action</b>	Make sure that the HTTP response does not contain invalid data.
<b>SINLME0242</b>	<b>Validation failed! Status code is {0}</b>
<b>Explanation</b>	Content validation has failed.
<b>Action</b>	Make sure that the HTTP response is successful and has SUCCESS status code.
<b>SINLME0243</b>	<b>Required func and returned values are different</b>
<b>Explanation</b>	The check of the required principal fails due to inconsistency between the required func and the returned values.
<b>Action</b>	Make sure that the property attributes of the principal are not null.
<b>SINLME0244</b>	<b>login: username not found: {0}</b>
<b>Explanation</b>	The configured properties file that represents the user store of the login module does not contain an entry for the specified user.
<b>Action</b>	The properties file that represents the user store of the login module must contain a 'userid's' property with a comma-separated list of user identifiers. For each identifier, a separate <identifier>.name property must be configured which represents the human-readable user name. If the username is not found, this means that respective configuration (user identifier and/or name) is not present in the properties file. If the user should be allowed to log in, then this user information must be added to the properties file.

---

<b>SINLME0245</b>	<b>login: passwords don't match for user {0}</b>
<b>Explanation</b>	The specified password does not match the configured password for the user.
<b>Action</b>	Double-check the specified password. The password for the user is configured via the "<userid>.passhash" property in the properties file configured for the login module. The value of the property is the SHA-1 digest of the plain text password encoded as a hexadecimal number.
<b>SINLME0246</b>	<b>login: SHA-1 hashing algorithm not found</b>
<b>Explanation</b>	The Java virtual machine does not contain a security provider which supports the SHA-1 hashing algorithm.
<b>Action</b>	Make sure you use a Java version which supports SHA-1 hashing algorithm or configure a Java security provider which supports this algorithm.
<b>SINLME0247</b>	<b>Resource not found: {0}</b>
<b>Explanation</b>	The specified resource file cannot be found in the classpath.
<b>Action</b>	Please check if the security infrastructure java archives are not corrupted and whether they contain the mentioned resource.
<b>SINRME0139</b>	<b>Wrong password format.</b>
<b>Explanation</b>	Password entry for the user is not correct. It must start with "\$6a\$" or "\$6\$".
<b>Action</b>	Check users.txt file.
<b>SINRME0140</b>	<b>Duplicates in user name.</b>
<b>Explanation</b>	User names are duplicated in the users.txt.
<b>Action</b>	Check the users.txt file that is used.
<b>SINRME0141</b>	<b>Duplicates in user name.</b>
<b>Explanation</b>	User names are duplicated in the users.txt.
<b>Action</b>	Check the users.txt file that is used.
<b>SINRME0142</b>	<b>Failed to initialize CipherUtil.</b>
<b>Explanation</b>	CipherUtil cannot be initialized due to some of following reasons: missing or invalid algorithm or key; invalid padding scheme; provider doesn't support a CipherSpi implementation for the specified algorithm; provider doesn't support a MacSpi implementation for the specified algorithm; provider doesn't support a SecretKeyFactorySpi implementation for the specified algorithm; the given key specification is inappropriate for this secret-key factory to produce a secret key; the given key is inappropriate for initializing MAC.
<b>Action</b>	General security error. Contact SoftwareAG global support.

<b>SINSCE0000</b>	<b>URL is missing in configuration!</b>
<b>Explanation</b>	Store cannot be added due to missing URL in the configuration.
<b>Action</b>	Ensure that a valid URL is specified.
<b>SINSOE0000</b>	<b>Cannot initialize Web SSO config context.</b>
<b>Explanation</b>	The Web SSO configuration could not be properly initialized.
<b>Action</b>	Make sure that your configuration is valid.
<b>SINSOE0001</b>	<b>Cannot initialize Web SSO config context.</b>
<b>Explanation</b>	The Web SSO configuration could not be properly initialized.
<b>Action</b>	Make sure that your configuration is valid.
<b>SINSOE0002</b>	<b>Failed to initialize Saml2 engine - all SAML operations will fail.</b>
<b>Explanation</b>	Internal error. The Saml2 engine failed to initialize properly. All SAML operations will fail.
<b>Action</b>	Contact SoftwareAG global support.
<b>SINSOE0003</b>	<b>Error initializing keystore.</b>
<b>Explanation</b>	Keystore cannot be found or the credentials are wrong.
<b>Action</b>	Ensure that the keystore exists and you have provided valid credentials.
<b>SINSOE0004</b>	<b>Error initializing keystore.</b>
<b>Explanation</b>	Keystore cannot be found or the credentials are wrong.
<b>Action</b>	Ensure that the keystore exists and you have provided valid credentials.
<b>SINSOE0005</b>	<b>Cannot load IDPSSODescriptor from metadata.</b>
<b>Explanation</b>	The error occurred because of invalid IDP metadata.
<b>Action</b>	Make sure that the provided IDP metadata is correct and has the SSO services defined.
<b>SINSOE0006</b>	<b>Cannot load SPSSODescriptor from metadata.</b>
<b>Explanation</b>	The error occurred because of invalid SP metadata.
<b>Action</b>	Make sure that the provided SP metadata is correct and has the consumer services defined.

---

<b>SINSOE0007</b>	<b>IDP cannot be determined.</b>
<b>Explanation</b>	IDP is missing in the metadata.
<b>Action</b>	Ensure that you have provided IDP metadata.
<b>SINSOE0008</b>	<b>Cannot get dynamic configuration.</b>
<b>Explanation</b>	Internal error. The service that provides configurations cannot be obtained.
<b>Action</b>	Contact SoftwareAG global support.
<b>SINSOE0009</b>	<b>The configuration could not be found.</b>
<b>Explanation</b>	Internal error. The service that provides configurations cannot be obtained.
<b>Action</b>	Contact SoftwareAG global support.
<b>SINSOE0010</b>	<b>The configuration could not be found.</b>
<b>Explanation</b>	Internal error. The service that provides configurations cannot be obtained.
<b>Action</b>	Contact SoftwareAG global support.
<b>SINSOE0011</b>	<b>Configuration Admin service is not available.</b>
<b>Explanation</b>	Internal error. The service that provides configurations cannot be obtained.
<b>Action</b>	Contact SoftwareAG global support.
<b>SINSOE0012</b>	<b>Can't obtain key from the keystore or generate key info for credential: {0}, {1}</b>
<b>Explanation</b>	A key cannot be obtained from the keystore with the provided credentials.
<b>Action</b>	Make sure the provided credentials are valid.
<b>SINSOW0013</b>	<b>Password for key alias: '{0}' is missing. This might lead to failure to load the respective key from key store</b>
<b>Explanation</b>	A password is not provided for the given alias.
<b>Action</b>	Check your configuration and add a password for the specified alias.
<b>SINSOW0014</b>	<b>Cannot obtain SPSSODescriptor. Default Web SSO profile will be used.</b>
<b>Explanation</b>	Cannot fetch metadata for the given provider (SPSSODescriptor).
<b>Action</b>	Check whether the Service Provider metadata contains the required data if the usage of the default value is not desired.

**SINSSE0022**      **SSOS properties could not be updated after sso properties file creation. Restart may be needed.**

**Explanation**      SSO Service properties could not be updated after sso properties file creation.

**Action**      Restart of the SSO service may be needed.

**SINSSE0023**      **CacheManager cannot be instantiated. {0}**

**Explanation**      CacheManager cannot be instantiated. The service will work without cache. This could cause some performance degradation.

**Action**      Check the value of the "com.softwareag.security.idp.ehcache.location" property in the com.softwareag.sso.pid.properties dynamic configuration file.

**SINSSE0024**      **Ehcache cannot be initialized. cacheManager = {0}**

**Explanation**      Ehcache cannot be initialized. The cachemanager in not available.

**Action**      Switch logging to debug and check the log file for more details.

**SINSSE0025**      **Ehcache in null**

**Explanation**      Ehcache in null.

**Action**      Switch logging to debug and check the log file for more details.

**SINSSE0026**      **Return NULL. Missing user ID in the assertion.**

**Explanation**      Wrong SAML assertion format. The required ID attribute is missing.

**Action**      Check the SAML assertion syntax.

**SINSSE0027**      **parseAssertion(String) throws SAMLException {0}**

**Explanation**      Parsing of the SAML assertion failed.

**Action**      Activate debug logging and check log file for more details.

**SINSSE0028**      **Return NULL. Missing user ID in the assertion.**

**Explanation**      Wrong SAML assertion format. The required ID attribute is missing.

**Action**      Check the SAML assertion syntax.

---

<b>SINSSE0029</b>	<b>{0}</b>
<b>Explanation</b>	Parsing of the SAML assertion failed.
<b>Action</b>	Activate debug logging and check log file for more details.
<b>SINSSE0030</b>	<b>generateAssertion() throws GeneralSecurityException {0}</b>
<b>Explanation</b>	Generation of the SAML assertion failed with GeneralSecurityException.
<b>Action</b>	Activate debug logging and check log file for more details.
<b>SINSSE0031</b>	<b>generateAssertion() throws XMLSignatureException {0}</b>
<b>Explanation</b>	Generation of the SAML assertion failed with XMLSignatureException.
<b>Action</b>	Activate debug logging and check log file for more details.
<b>SINSSE0032</b>	<b>generateAssertion() throws MarshalException {0}</b>
<b>Explanation</b>	Generation of the SAML assertion failed with MarshalException.
<b>Action</b>	Activate debug logging and check log file for more details.
<b>SINSSE0033</b>	<b>generateAssertion() throws MarshallingException {0}</b>
<b>Explanation</b>	Generation of the SAML assertion failed with MarshallingException.
<b>Action</b>	Activate debug logging and check log file for more details.
<b>SINSSE0034</b>	<b>Error loading truststore or keystore. Services will be unregistered.</b>
<b>Explanation</b>	Keystore or truststore cannot be found or the credentials are missing.
<b>Action</b>	Ensure that the keystore/truststore exists and you have provided valid credentials.
<b>SINSSE0035</b>	<b>Error loading truststore. Services will be unregistered.</b>
<b>Explanation</b>	Truststore cannot be found or the credentials are missing.
<b>Action</b>	Ensure that the truststore exists and you have provided valid credentials.
<b>SINSSE0036</b>	<b>Error during STS API initialization: {0}</b>
<b>Explanation</b>	An algorithm is not supported by the JVM.
<b>Action</b>	Ensure that unlimited strength JCE (Java Cryptographic Extension) is available on the system. If it is available, contact Software AG Global Support.

<b>SINSSE0037</b>	<b>Error during AuthResponse generation: {0}</b>
<b>Explanation</b>	A signature cannot be created or the element being signed cannot be marshalled.
<b>Action</b>	Ensure that the identity provider keystore is available and contains a signing key with the configured alias and credentials.
<b>SINSSE0038</b>	<b>Unsupported request type - expected AuthnRequest but was {0}</b>
<b>Explanation</b>	The received request is not a SAML AuthnRequest.
<b>Action</b>	Ensure the received SAML message is a valid SAML AuthnRequest.
<b>SINSSE0039</b>	<b>Error during request parsing: {0}</b>
<b>Explanation</b>	The received SAML AuthRequest cannot be parsed.
<b>Action</b>	Ensure the received XML message is a valid SAML AuthnRequest message.
<b>SINSSE0040</b>	<b>Missing signature in the request, ID: {0}</b>
<b>Explanation</b>	The received SAML AuthnRequest does not contain a signature.
<b>Action</b>	Ensure the received SAML AuthnRequest is signed by the respective relying party issuing the request.
<b>SINSSE0041</b>	<b>Insufficient input data: destination not provided!</b>
<b>Explanation</b>	A SAML response cannot be generated due to missing destination URL.
<b>Action</b>	Ensure a valid destination URL is provided when generating the SAML Response message.
<b>SINSSE0042</b>	<b>Insufficient input data: userId not provided!</b>
<b>Explanation</b>	A SAML response cannot be generated due to missing user ID.
<b>Action</b>	Ensure valid user ID is provided when generating SAML Response. The user ID is required to generate the SAML assertion's subject information.
<b>SINSSE0044</b>	<b>Missing request ID</b>
<b>Explanation</b>	Validation of SAML AuthRequest message is failing due to missing ID attribute.
<b>Action</b>	Ensure the SAML AuthnRequest message contains a valid ID attribute.

---

<b>SINSSE0045</b>	<b>Missing request issue instant</b>
<b>Explanation</b>	Validation of SAML AuthnRequest fails due to missing IssueInstant attribute.
<b>Action</b>	Ensure the SAML AuthnRequest message contains a valid IssueInstant attribute, which represents the time instant of issue for the request.
<b>SINSSE0046</b>	<b>SAML AuthnRequest version is not SAML 2.0</b>
<b>Explanation</b>	The SAML AuthnRequest has invalid Version attribute, the only supported version is SAML 2.0
<b>Action</b>	Ensure SAML AuthnRequest message uses SAML 2.0 version.
<b>SINSSE0047</b>	<b>Missing issuer in the request.</b>
<b>Explanation</b>	SAML AuthnRequest message does not specify an issuer.
<b>Action</b>	Ensure the SAML AuthnRequest message specifies an issuer, which identifies the entity that generated the request message.
<b>SINSSE0048</b>	<b>No relying party configuration found for entityId {0}</b>
<b>Explanation</b>	The identity provider is not configured with a relying party for the given entity identifier.
<b>Action</b>	Check if the relying party identified by the specified entityId is trusted, and if so, configure a relying party with this identifier in the identity provider configuration.
<b>SINSSE0049</b>	<b>Unexpected signature algorithm: {0}</b>
<b>Explanation</b>	The signature algorithm of the received SAML AuthnRequest message does not match the signature algorithm configured for the respective relying party in the identity provider configuration.
<b>Action</b>	The expected relying party signature algorithm must be specified in the relying party configuration. To disable checking the signature algorithm, do not configure a signature algorithm for the relying party.
<b>SINSXE0000</b>	<b>Initialize: keystore password is not specified.</b>
<b>Explanation</b>	Keystore password is missing.
<b>Action</b>	Make sure that the keystore password is specified.

<b>SINSXE0001</b>	<b>No token returned from IAF.</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Contact SoftwareAG global support.
<b>SINSXE0002</b>	<b>Signature creation failed.</b>
<b>Explanation</b>	Certificate cannot be found or error occurred during signing operation.
<b>Action</b>	Make sure that the provided certificate is valid.
<b>SINSXE0003</b>	<b>Unsupported encoding.</b>
<b>Explanation</b>	Internal error. Encoding with not supported charset.
<b>Action</b>	Contact SoftwareAG global support.
<b>SINSXE0004</b>	<b>verifySignature: Given certificate is NULL</b>
<b>Explanation</b>	Cannot verify given signature. The certificate is missing.
<b>Action</b>	Set certificate for verification of the signature.
<b>SINSXE0005</b>	<b>Utility path is not specified</b>
<b>Explanation</b>	The utility path is not specified in the JAAS configuration.
<b>Action</b>	Make sure that the utility path is specified in the JAAS configuration.
<b>SINSXE0006</b>	<b>RMI Port must be a valid integer.</b>
<b>Explanation</b>	The specified RMI port is invalid.
<b>Action</b>	Set a valid RMI port in the configuration.
<b>SINSXE0007</b>	<b>Remote classes are not currently bound</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Contact Software AG global support.
<b>SINSXE0008</b>	<b>Problem with clearing credentials</b>
<b>Explanation</b>	Internal error. User credentials cannot be cleared. Logout operation failed.
<b>Action</b>	Contact Software AG global support.

---

<b>SINSXE0009</b>	<b>Problem creating repository manager</b>
<b>Explanation</b>	Internal error. RMI registry function was not found or could not obtain remote reference to the repository.
<b>Action</b>	Contact Software AG global support.
<b>SINSXE0010</b>	<b>TEMPLATE_SECTION must not be null or empty.</b>
<b>Explanation</b>	Template section option is not specified in the JAAS configuration.
<b>Action</b>	Make sure that the template section option is specified in the JAAS configuration.
<b>SINSXE0011</b>	<b>Error opening SSX Repository</b>
<b>Explanation</b>	The error is thrown by the SSX repository during opening operation.
<b>Action</b>	Make sure that the provided SSX parameters are valid.
<b>SINSXE0012</b>	<b>Cannot obtain lock</b>
<b>Explanation</b>	Internal error. An interruption occurred when obtaining the remote registry.
<b>Action</b>	Contact Software AG global support.
<b>SINSXE0013</b>	<b>Cannot obtain lock</b>
<b>Explanation</b>	Internal error. An interruption occurred when obtaining the remote registry.
<b>Action</b>	Contact Software AG global support.
<b>SINSXE0014</b>	<b>Cannot obtain lock</b>
<b>Explanation</b>	Internal error. An interruption occurred when obtaining groups from the repository.
<b>Action</b>	Contact Software AG global support.
<b>SINSXE0015</b>	<b>Cannot obtain lock</b>
<b>Explanation</b>	Internal error. An interruption occurred when obtaining users from the repository.
<b>Action</b>	Contact Software AG global support.
<b>SINSXE0016</b>	<b>Cannot obtain lock</b>
<b>Explanation</b>	Internal error. An interruption occurred when obtaining user groups from the repository.
<b>Action</b>	Contact Software AG global support.

<b>SINSXE0017</b>	<b>Cannot obtain lock</b>
<b>Explanation</b>	Internal error. An interruption occurred when obtaining the users in a group from the repository.
<b>Action</b>	Contact Software AG global support.
<b>SINSXE0018</b>	<b>Cannot obtain lock</b>
<b>Explanation</b>	Internal error. An interruption occurred when obtaining the principles in a group from the repository.
<b>Action</b>	Contact Software AG global support.
<b>SINSXE0019</b>	<b>Cannot obtain lock</b>
<b>Explanation</b>	Internal error. An interruption occurred when checking if a group exists in the repository.
<b>Action</b>	Contact Software AG global support.
<b>SINSXE0020</b>	<b>Cannot obtain lock</b>
<b>Explanation</b>	Internal error. An interruption occurred when checking if a user exists in the repository.
<b>Action</b>	Contact Software AG global support.
<b>SINSXE0021</b>	<b>Cannot obtain lock</b>
<b>Explanation</b>	Internal error. An interruption occurred when obtaining user principals from the repository.
<b>Action</b>	Contact Software AG global support.
<b>SINSXE0022</b>	<b>Cannot obtain lock</b>
<b>Explanation</b>	Internal error. An interruption occurred when obtaining group principals from the repository.
<b>Action</b>	Contact Software AG global support.
<b>SINSXE0023</b>	<b>Cannot obtain lock</b>
<b>Explanation</b>	Internal error. An interruption occurred when obtaining the repository type.
<b>Action</b>	Contact Software AG global support.

---

<b>SINSXE0024</b>	<b>Cannot obtain lock</b>
<b>Explanation</b>	Internal error. An interruption occurred when specifying page size.
<b>Action</b>	Contact Software AG global support.
<b>SINSXE0025</b>	<b>Cannot obtain lock</b>
<b>Explanation</b>	Internal error. An interruption occurred when specifying principals data to IAF.
<b>Action</b>	Contact Software AG global support.
<b>SINSXE0026</b>	<b>LoadAccessList: Cannot read file {0} {1}</b>
<b>Explanation</b>	The URL of the load access list is not provided.
<b>Action</b>	Make sure that the "load access list" command line option is present.
<b>SINSXE0027</b>	<b>This client has no permissions for authentication. Please contact with your RMI server administrator.</b>
<b>Explanation</b>	The client has no permissions for authentication.
<b>Action</b>	Contact your RMI server administrator.
<b>SINSXE0028</b>	<b>authenticate: could not logout.</b>
<b>Explanation</b>	Internal error. Logout operation failed.
<b>Action</b>	Contact Software AG global support.
<b>SINSXE0029</b>	<b>authenticate: could not login the user with credentials: {0} {1}</b>
<b>Explanation</b>	Logon failed.
<b>Action</b>	Make sure the used credentials are valid.
<b>SINSXE0030</b>	<b>logout: user data parameter is null during the remote logout!</b>
<b>Explanation</b>	Internal error. Logout operaiton failed. User doesn't exist.
<b>Action</b>	Try again later, if that doesn't solve the issue, contact Software AG global support.
<b>SINSXE0031</b>	<b>logoutUser: could not logout the user: {0} {1}</b>
<b>Explanation</b>	Internal error. Logout operation failed.
<b>Action</b>	Contact Software AG global support.

<b>SINSXE0032</b>	<b>logoutUser: this context could not be fund in the cache. User data: {0}</b>
<b>Explanation</b>	Internal error. Context is missing from the cache.
<b>Action</b>	Contact Software AG global support.
<b>SINSXE0033</b>	<b>Could not obtain lock</b>
<b>Explanation</b>	Internal error. An interruption occured when obtaining the remote registry.
<b>Action</b>	Contact Software AG global support.
<b>SINSXE0034</b>	<b>Could not obtain lock</b>
<b>Explanation</b>	Internal error. An interruption occured when obtaining an access token frim the remote token manager.
<b>Action</b>	Contact Software AG global support.
<b>SINSXE0035</b>	<b>Invalid parameter!</b>
<b>Explanation</b>	Passed arguments during initialization of the remote SSX server are not registry port or configuration file.
<b>Action</b>	Make sure that either URL configuration or port number is present in the command line options.
<b>SINSXE0036</b>	<b>key store password parameter is missing</b>
<b>Explanation</b>	Keystore password is missing.
<b>Action</b>	Provide valid keystore password.
<b>SINSXE0037</b>	<b>Error starting the server</b>
<b>Explanation</b>	Error occurred during initialization/start of the server.
<b>Action</b>	Contact Software AG global support.
<b>SINSXE0038</b>	<b>Error running the server</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Contact global Software AG support.

---

<b>SINSXE0039</b>	<b>Error unbinding services</b>
<b>Explanation</b>	Error occurred during shutdown of the server.
<b>Action</b>	Contact Software AG global support.
<b>SINSXE0040</b>	<b>Can't get all groups: {0}</b>
<b>Explanation</b>	Groups cannot be obtained. The SSX repository cannot be opened.
<b>Action</b>	Make sure that the provided SSX repository parameters are valid. If the parameters are correct, contact global Software AG support.
<b>SINSXE0041</b>	<b>This principal {0} is with wrong.</b>
<b>Explanation</b>	Internal error. The principal has wrong user type.
<b>Action</b>	Contact global Software AG support.
<b>SINSXE0042</b>	<b>This {0} has wrong type</b>
<b>Explanation</b>	This {0} has wrong user type.
<b>Action</b>	Contact global Software AG support.
<b>SINSXE0043</b>	<b>This {0} is not user.</b>
<b>Explanation</b>	Error when verifying user.
<b>Action</b>	Contact global Software AG support.
<b>SINSXE0044</b>	<b>This principal: {0} has wrong type</b>
<b>Explanation</b>	Wrong principal type.
<b>Action</b>	Contact global Software AG support.
<b>SINSXE0045</b>	<b>This {0} is not group.</b>
<b>Explanation</b>	Error when verifying group.
<b>Action</b>	Contact global Software AG support.
<b>SINSXE0046</b>	<b>This method is not supported!</b>
<b>Explanation</b>	Specifying page size is not yet supported.
<b>Action</b>	Do not use this method.

<b>SINSXE0047</b>	<b>Input data cannot be null</b>
<b>Explanation</b>	Input data (password) is missing or incorrect.
<b>Action</b>	Make sure that the input data (password) is correct.
<b>SINSXE0048</b>	<b>Token type is not IAF token or artifact.</b>
<b>Explanation</b>	Access token is invalid, it does not contain a IAF token or artifact.
<b>Action</b>	Contact global Software AG support.
<b>SINSXE0049</b>	<b>Cannot retrieve access token {0}</b>
<b>Explanation</b>	Internal error. Repository cannot be opened.
<b>Action</b>	Contact global Software AG support.
<b>SINSXE0050</b>	<b>Can not get manifest file.</b>
<b>Explanation</b>	Cannot obtain the manifest of the SSX jar file.
<b>Action</b>	Contact Software AG global support.
<b>SINSXE0051</b>	<b>Can not receive user groups properties.</b>
<b>Explanation</b>	Internal error. Native code executed. Cannot receive user groups properties.
<b>Action</b>	Contact global Software AG support.
<b>SINSXE0052</b>	<b>Can not receive user properties.</b>
<b>Explanation</b>	Internal error. Native code executed. Cannot receive user properties.
<b>Action</b>	Contact global Software AG support.
<b>SINSXE0053</b>	<b>Can not receive group properties.</b>
<b>Explanation</b>	Internal error. Native code executed. Cannot receive group properties.
<b>Action</b>	Contact global Software AG support.
<b>SINSXE0054</b>	<b>Server not responding for a long time.</b>
<b>Explanation</b>	Connectivity issues.
<b>Action</b>	Contact global Software AG support.

<b>SINSXE0055</b>	<b>There is no SAG User Database Module in the manifest file.</b>
<b>Explanation</b>	The manifest file of the Software AG security extension java archive does not contain a 'SAG User Database Module' attribute section.
<b>Action</b>	Contact Software AG Global Support.



# 26 Tamino Messages

---

<b>INOAAE0001</b>	<b>Function not selected : name</b>
<b>Explanation</b>	The server extension function is not selected so that the parameter cannot be modified.
<b>Action</b>	Select the server extension function first.
<b>INOAAE0004</b>	<b>Cannot modify journal space</b>
<b>Explanation</b>	The journal space of the specified database cannot be modified.
<b>Action</b>	Check whether the data space is already in use. Check the database location for remaining disk space.
<b>INOAAE0018</b>	<b>Port number 'port' for 'name' indication</b>
<b>Explanation</b>	The port number cannot be used.
<b>Action</b>	Change the port parameter value.
<b>INOAAE0019</b>	<b>fail - delete database dbname read only parameter is set</b>
<b>Explanation</b>	The database parameter "read only" must be cleared before the database can be deleted.
<b>Action</b>	Remove the read only flag in the database parameters.
<b>INOAAE0020</b>	<b>Modify Email notification properties failed</b>
<b>Explanation</b>	The modification of Email notification properties failed.
<b>Action</b>	Look at the detailed error message and action.

<b>INOAAE0022</b>	<b>mvcount spaces successfully moved from oldloc to newloc, one or more spaces couldn't be moved because of errors/warnings</b>
<b>Explanation</b>	The given number of spaces were moved successfully but one or more spaces could not be moved because an error or a warning occurred during the execution of the command.
<b>Action</b>	Find out why spaces were not moved and try to move them via the 'Move' command of the database spaces entry.
<b>INOAAE0024</b>	<b>Change License file failed</b>
<b>Explanation</b>	Change license file failed.
<b>Action</b>	Check the license file.
<b>INOAAE0026</b>	<b>The parallel option is not supported for incremental backups</b>
<b>Explanation</b>	Options "parallel" and "incremental" are mutually exclusive.
<b>Action</b>	Select only one of the options.
<b>INOAAE0032</b>	<b>Cannot activate dynamic property 'name'</b>
<b>Explanation</b>	The property cannot be updated in the current server session, but will be active after a restart of the database.
<b>Action</b>	Restart the database to activate the property.
<b>INOAAE0038</b>	<b>Cannot open file path, file does not exist or is opened by another one or not enough access rights</b>
<b>Explanation</b>	The file does not exist or is already open.
<b>Action</b>	Check the filename.
<b>INOAAE0039</b>	<b>Unknown database space number</b>
<b>Explanation</b>	The database space number is not valid for this database.
<b>Action</b>	Use a valid database space number.
<b>INOAAE0040</b>	<b>This command is valid for journal space only</b>
<b>Explanation</b>	The database space type is not valid for this command.
<b>Action</b>	Use the journal space.

---

<b>INOAAE0042</b>	<b>CD database information file not found</b>
<b>Explanation</b>	The error message information file for the CD database not found.
<b>Action</b>	Check the path and filename.
<b>INOAAE0043</b>	<b>CD database information file doesn't contain all necessary data or was created on a different platform</b>
<b>Explanation</b>	The content of the information file is not complete or the file is not the required information file is from a different operating system.
<b>Action</b>	Check the content of the information file.
<b>INOAAE0044</b>	<b>CD database from different operating system cannot be registered</b>
<b>Explanation</b>	Only CD databases from the same operating system can be registered.
<b>Action</b>	Use a CD database that was created on the same operating system.
<b>INOAAE0045</b>	<b>Operation not allowed on CD database or read only database</b>
<b>Explanation</b>	The operation is not allowed on a CD database or read only database.
<b>Action</b>	No action required.
<b>INOAAE0054</b>	<b>The "Add database space" function has failed</b>
<b>Explanation</b>	The attempt to add one or more of the database spaces failed.
<b>Action</b>	Check the database locations for remaining disk space. The server property "read only" may be set to "yes".
<b>INOAAE0055</b>	<b>More than one replication database is not yet supported</b>
<b>Explanation</b>	Only one replication database is allowed.
<b>Action</b>	No action required.
<b>INOAAE0056</b>	<b>Re-invert of database dbName has failed</b>
<b>Explanation</b>	The re-invert operation failed. Possible reasons are that the database is not active or, if active, one or more indices could not be repaired.
<b>Action</b>	Check your database status.

<b>INOAAE0058</b>	<b>Invalid Access Control Element name</b>
<b>Explanation</b>	Function names cannot be part of paths.
<b>Action</b>	Use either a function name or a path but not both.
<b>INOAAE0059</b>	<b>Invalid master database name</b>
<b>Explanation</b>	The master database name specified is invalid.
<b>Action</b>	Specify another database name for the master database.
<b>INOAAE0060</b>	<b>Specification of key parameter is mandatory</b>
<b>Explanation</b>	The parameter must be specified.
<b>Action</b>	Specify the parameter and try again.
<b>INOAAE0065</b>	<b>Server extension 'name' not defined</b>
<b>Explanation</b>	The specified server extension does not exist.
<b>Action</b>	No action required.
<b>INOAAE0066</b>	<b>Internal configuration store key _default not found</b>
<b>Explanation</b>	The default internal configuration store key could not be found.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0067</b>	<b>File 'path' not found</b>
<b>Explanation</b>	The specified file could not be found.
<b>Action</b>	Specify a valid filename.
<b>INOAAE0068</b>	<b>Different server extension names: name1 is different from name2</b>
<b>Explanation</b>	The server extension names differ.
<b>Action</b>	No action required.
<b>INOAAE0069</b>	<b>File 'path' not extracted</b>
<b>Explanation</b>	The server extension installation file was not extracted.
<b>Action</b>	No action required.

---

<b>INOAAE0070</b>	<b>File 'path' already installed</b>
<b>Explanation</b>	The server extension installation file was previously installed.
<b>Action</b>	No action required.
<b>INOAAE0072</b>	<b>Document 'path' not installed</b>
<b>Explanation</b>	The server extension installation document was not installed.
<b>Action</b>	The action depends on previous error messages. Please check the previous messages for more information.
<b>INOAAE0073</b>	<b>File 'path' not created</b>
<b>Explanation</b>	The server extension installation file was not created.
<b>Action</b>	Correct the access rights for the directory and retry the operation.
<b>INOAAE0074</b>	<b>Server extension name 'name' not defined</b>
<b>Explanation</b>	The name of the server extension is not defined.
<b>Action</b>	Specify the name of the server extension and retry the operation.
<b>INOAAE0075</b>	<b>Server extension name 'name' already defined</b>
<b>Explanation</b>	The name of the server extension already exists.
<b>Action</b>	Change the name of the server extension and retry the operation.
<b>INOAAE0076</b>	<b>Directory 'path' already exists</b>
<b>Explanation</b>	The server extension installation directory already exists.
<b>Action</b>	Remove the directory and retry the operation.
<b>INOAAE0077</b>	<b>Document 'path' already installed</b>
<b>Explanation</b>	The server extension installation document is already installed.
<b>Action</b>	Remove the server extension installation document.
<b>INOAAE0078</b>	<b>Execution failed: command</b>
<b>Explanation</b>	The specified operating system command failed.
<b>Action</b>	The action depends on previous error messages. Please check the previous messages for more information.

<b>INOAAE0079</b>	<b>Database name not defined</b>
<b>Explanation</b>	The required database name was not specified.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0080</b>	<b>No functions defined: name</b>
<b>Explanation</b>	There are no functions defined in the server extension.
<b>Action</b>	Add functions to the server extension and retry the installation.
<b>INOAAE0081</b>	<b>The Tamino server returned an invalid server extension response document</b>
<b>Explanation</b>	The server extension response document does not correspond to the agreed protocol with the Tamino server.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0082</b>	<b>Server extension 'name' does not exist</b>
<b>Explanation</b>	The specified server extension does not exist.
<b>Action</b>	Correct the name of the server extension and retry the operation.
<b>INOAAE0083</b>	<b>File 'path' already open</b>
<b>Explanation</b>	The server extension installation package is already open.
<b>Action</b>	Wait until the package is not being used and retry the operation.
<b>INOAAE0084</b>	<b>File 'path' not open</b>
<b>Explanation</b>	The server extension installation package is not open.
<b>Action</b>	Wait until the package is not being used and retry the operation.
<b>INOAAE0085</b>	<b>File 'path' not previously closed</b>
<b>Explanation</b>	The server extension installation package is not closed.
<b>Action</b>	Wait until the package is not being used and retry the operation.
<b>INOAAE0086</b>	<b>Operation 'type' not implemented</b>
<b>Explanation</b>	The requested operation is not implemented.
<b>Action</b>	No action required.

---

<b>INOAAE0087</b>	<b>Command 'type' not allowed</b>
<b>Explanation</b>	This command is not allowed for the requested server extension.
<b>Action</b>	Ensure that you use one of the commands allowed for the server extension.
<b>INOAAE0088</b>	<b>message</b>
<b>Explanation</b>	This is a generic container for Tamino error messages.
<b>Action</b>	See the content of the message during online Tamino operation for further information.
<b>INOAAE0089</b>	<b>Not an installation package: path</b>
<b>Explanation</b>	The provided file is not a server extension installation package.
<b>Action</b>	Use a valid installation package.
<b>INOAAE0092</b>	<b>Error during write to inodmn, write interrupted or socket closed by inodmn</b>
<b>Explanation</b>	This is an internal error. It could be caused by not fully compatible versions of Tamino and System Management Hub.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0093</b>	<b>Error during read from inodmn, read interrupted or socket closed by inodmn</b>
<b>Explanation</b>	This is an internal error. It could be caused by not fully compatible versions of Tamino and System Management Hub.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0094</b>	<b>Command is an illegal number</b>
<b>Explanation</b>	This is an internal error in the event logging protocol.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0095</b>	<b>This command requires a different database state</b>
<b>Explanation</b>	An attempt was made to execute a command that either requires an active database, but the database is inactive, or the command can be executed only in inactive mode, but the database is active.
<b>Action</b>	Start or stop the database to bring it into the appropriate mode (active or inactive) and retry the command.

<b>INOAAE0096</b>	<b>The command requested cannot be executed because it is already running</b>
<b>Explanation</b>	The command you wish to execute is already being executed by someone else, but the command cannot be executed in parallel.
<b>Action</b>	Wait until the running command has completed. The argevsrv process keeps track of running commands. If the command is blocked although it is obviously not running, try restarting the argevsrv process.
<b>INOAAE0097</b>	<b>Insufficient resources to complete the command</b>
<b>Explanation</b>	This is an internal error in the event logging protocol. Some resource (usually disk or main storage) is exhausted and the function failed to complete.
<b>Action</b>	Check if there is enough free disk space. Delete temporary and otherwise expandable files, then try again.
<b>INOAAE0098</b>	<b>Path 'path/name' not created</b>
<b>Explanation</b>	The specified path name is too long.
<b>Action</b>	Choose another file structure with shorter path names.
<b>INOAAE0099</b>	<b>Path 'path' not converted</b>
<b>Explanation</b>	The specified path name was not converted to a URL or vice versa. Either the path name or the URL is too long.
<b>Action</b>	Choose another file structure with shorter path names.
<b>INOAAE0110</b>	<b>Internal error with database startup by changing replication database to a normal database</b>
<b>Explanation</b>	An internal error occurred when starting the database.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0111</b>	<b>No valid destination directory for backup files given.</b>
<b>Explanation</b>	No valid destination directory was given.
<b>Action</b>	Specify at least one valid directory with write access for Tamino and enough space for the backups.

---

<b>INOAAE0113</b>	<b>Path 'path' not extracted</b>
<b>Explanation</b>	The specified path was not extracted from the internal configuration store. This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0114</b>	<b>Execution mode 'name' not extracted</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0115</b>	<b>Execution mode not compatible: mode1 != mode2</b>
<b>Explanation</b>	The specified execution modes are not compatible.
<b>Action</b>	Select a compatible execution mode.
<b>INOAAE0116</b>	<b>GUID not extracted</b>
<b>Explanation</b>	The GUID was not extracted from the internal configuration store. This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0117</b>	<b>DLL 'path' is not registered</b>
<b>Explanation</b>	The specified DLL cannot be used.
<b>Action</b>	Specify another DLL.
<b>INOAAE0118</b>	<b>DLL 'path' not unregistered</b>
<b>Explanation</b>	The specified DLL cannot be used.
<b>Action</b>	Specify another DLL.
<b>INOAAE0119</b>	<b>Remove of all server extensions failed</b>
<b>Explanation</b>	The server extensions could not be removed.
<b>Action</b>	Check the extensions.
<b>INOAAE0120</b>	<b>XML port not defined for database 'name'</b>
<b>Explanation</b>	The XML port value is missing in the internal configuration store.
<b>Action</b>	Please contact your software supplier.

<b>INOAAE0121</b>	<b>Not enough memory</b>
<b>Explanation</b>	There is not enough memory for an http request.
<b>Action</b>	Close some of your applications.
<b>INOAAE0122</b>	<b>XML template processing failed, template template missing or incorrect</b>
<b>Explanation</b>	This is an internal error of the Tamino Manager browser interface.
<b>Action</b>	Check if the quoted template file exists and if it is intact. If not, either reinstall or contact your software supplier.
<b>INOAAE0123</b>	<b>No package name defined: name</b>
<b>Explanation</b>	For a server extension the Java package name is required.
<b>Action</b>	If you generated the Java package yourself, use a unique name for your Java package. If it is a third-party product, get a new package from your software vendor.
<b>INOAAE0124</b>	<b>Unknown database dbname : rename failed or no information from Software AG XTS Directory Server</b>
<b>Explanation</b>	The database to be renamed could not be found.
<b>Action</b>	Check if the specified database exists and if the Software AG XTS Directory Server is running.
<b>INOAAE0125</b>	<b>Directory 'path' not deleted</b>
<b>Explanation</b>	The directory is in use. Therefore it cannot be deleted.
<b>Action</b>	Wait until the directory is no longer in use and try again.
<b>INOAAE0126</b>	<b>No valid location type found</b>
<b>Explanation</b>	The location type parameter is missing.
<b>Action</b>	Specify the location type parameter.
<b>INOAAE0127</b>	<b>Location type 'type' is unknown</b>
<b>Explanation</b>	An unknown location type is specified.
<b>Action</b>	Specify a valid location type.

---

<b>INOAAE0128</b>	<b>File 'path' not copied</b>
<b>Explanation</b>	The specified file was not copied to the target file.
<b>Action</b>	Check your permissions or check your disk space.
<b>INOAAE0129</b>	<b>Please specify at least the location path</b>
<b>Explanation</b>	The path parameter is missing.
<b>Action</b>	Specify the path parameter.
<b>INOAAE0130</b>	<b>Path path exceeds the maximum path length of maxpathlen characters</b>
<b>Explanation</b>	The length of the specified path exceeds the allowed maximum length of a directory path.
<b>Action</b>	Specify a shorter directory path.
<b>INOAAE0131</b>	<b>Location path path includes no valid directory</b>
<b>Explanation</b>	The root of the specified directory path is invalid. A possible cause is that the specified directory path could be on a removable drive or RAM disk.
<b>Action</b>	Specify a valid directory path.
<b>INOAAE0132</b>	<b>Location path path is located on a remote drive. Please choose a local drive.</b>
<b>Explanation</b>	A remote drive is not allowed for a location path.
<b>Action</b>	Specify the location path on a local drive.
<b>INOAAE0133</b>	<b>Name name exceeds the maximum name length of maxnamelen characters</b>
<b>Explanation</b>	The length of the specified name exceeds the allowed maximum length.
<b>Action</b>	Specify a shorter name.
<b>INOAAE0134</b>	<b>Name name already exists as database location name</b>
<b>Explanation</b>	The specified location name is the name of an existing database location.
<b>Action</b>	Change the location name.
<b>INOAAE0135</b>	<b>Path path already exists as database location path</b>
<b>Explanation</b>	The specified location path is the path of an existing database location.
<b>Action</b>	Change the location path specification.

<b>INOAAE0136</b>	<b>Database location name not found</b>
<b>Explanation</b>	The specified location name was not found in the internal configuration store.
<b>Action</b>	Specify an existing location name.
<b>INOAAE0137</b>	<b>Location name is the current default location</b>
<b>Explanation</b>	Deleting the current default location is not allowed.
<b>Action</b>	Change the default location.
<b>INOAAE0138</b>	<b>Location name is the current default backup location</b>
<b>Explanation</b>	Deleting the current default backup location is not allowed.
<b>Action</b>	Change the default backup location.
<b>INOAAE0140</b>	<b>Database dbname uses database location name with location path path as 'category'. If you still want to delete the location, all spaces from that location must be moved to another location before you can delete it.</b>
<b>Explanation</b>	The specified location is defined as a category location for a database, so deleting is not allowed. Move the database spaces on that location to another one.
<b>Action</b>	Change the default database location category specification.
<b>INOAAE0141</b>	<b>No response document received</b>
<b>Explanation</b>	There was no response document received from the server.
<b>Action</b>	Check if the network communication is established.
<b>INOAAE0142</b>	<b>Value for property 'name' too small - minimum is minval</b>
<b>Explanation</b>	The value for the given property is smaller than the minimum allowed.
<b>Action</b>	Specify a larger value.
<b>INOAAE0143</b>	<b>Value for property 'name' too large - maximum is maxval</b>
<b>Explanation</b>	The value is larger than the maximum allowed.
<b>Action</b>	Specify a smaller value.

---

<b>INOAAE0144</b>	<b>Invalid numeric value for property 'name'</b>
<b>Explanation</b>	The property is a numeric property and the value has the wrong type.
<b>Action</b>	Change the property value to numeric.
<b>INOAAE0145</b>	<b>Property 'name' must be 'yes' or 'no'</b>
<b>Explanation</b>	The property is a boolean property and the value has the wrong type.
<b>Action</b>	Change the property value to 'yes' or 'no'.
<b>INOAAE0146</b>	<b>The sequence of backup spaces is not complete.</b>
<b>Explanation</b>	One or more streams or extents are missing in the selected backup spaces. Only complete backups can be restored. Spaces missing at the end of the sequence will be only detected at runtime when data is loaded into the new database.
<b>Action</b>	Check the stream or extent numbers of the selected backup spaces and add missing spaces. Check if the sequence of backup spaces (Extent 1, Extent 2, ..) is correct.
<b>INOAAE0149</b>	<b>Web server wsname already assigned</b>
<b>Explanation</b>	The web server is already assigned to the specified database.
<b>Action</b>	Check the specified web servers and the web server assignments.
<b>INOAAE0153</b>	<b>Web server wsname not assigned</b>
<b>Explanation</b>	The specified web server is not assigned to the specified database, therefore the assignment cannot be deleted.
<b>Action</b>	Check the web server assignments to the specified database.
<b>INOAAE0154</b>	<b>Error retrieving collection/doctype information: the requested document(s) could not be locked</b>
<b>Explanation</b>	The document is already locked or cannot be locked. A possible reason can also be an unclosed session.
<b>Action</b>	Wait for a short time and try this command again.
<b>INOAAE0155</b>	<b>Unknown location location name</b>
<b>Explanation</b>	The given location does not exist.
<b>Action</b>	Choose a valid location.

<b>INOAAE0157</b>	<b>Parameter parameter name missing</b>
<b>Explanation</b>	The parameter with the given name is not specified.
<b>Action</b>	Specify the required parameter.
<b>INOAAE0158</b>	<b>parameter name: invalid path, directory does not exist or is not writable</b>
<b>Explanation</b>	The given path does not exist or is not writeable.
<b>Action</b>	Use a path that exists and is writable.
<b>INOAAE0159</b>	<b>Database dbname already exists</b>
<b>Explanation</b>	The "rename database" command failed because the database name already exists.
<b>Action</b>	Use a different name or remove the database.
<b>INOAAE0162</b>	<b>Cannot delete database space spaceNo</b>
<b>Explanation</b>	The specified database space cannot be deleted from the location.
<b>Action</b>	Check whether the database space is already in use.
<b>INOAAE0165</b>	<b>Cannot expand database space spaceNo</b>
<b>Explanation</b>	The specified database space cannot be expanded.
<b>Action</b>	Check whether the database space is already in use. Check the database location for remaining disk space. If the database is read-only it cannot be expanded.
<b>INOAAE0169</b>	<b>Database database name exists</b>
<b>Explanation</b>	A database with the same name exists either on the local computer, or in the scope of XTS Directory Service (which may know databases on multiple computers).
<b>Action</b>	Choose a different name. On Windows platforms, it is not sufficient to have two names differ only in upper/lowercase.
<b>INOAAE0170</b>	<b>Configuration 'configuration' already exists for external backup method 'method'</b>
<b>Explanation</b>	The configuration name already exists for this external backup method.
<b>Action</b>	Specify a new configuration name which does not exist already.

---

<b>INOAAE0174</b>	<b>Could not initialize TCP stack</b>
<b>Explanation</b>	This is an internal error in the event logging protocol. The communication between a logging client and the logging server could not be established. Basic functions and commands may be unaffected by this failure but messages will not be stored permanently or displayed in the Tamino Manager browser interface.
<b>Action</b>	This failure is most likely due to extreme shortage of resources, or missing operating system components. Check the disk space. Check the integrity of the installation. Contact you software supplier to check if there is a software update.
<b>INOAAE0175</b>	<b>Error in inodmn conversation: unexpected response buffer</b>
<b>Explanation</b>	This is an internal error of the event logging protocol.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0177</b>	<b>Error in inodmn conversation: invalid number</b>
<b>Explanation</b>	This is an internal error in the event logging protocol.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0178</b>	<b>Function not implemented</b>
<b>Explanation</b>	This is an internal error of the event logging protocol, a feature is not implemented in the version installed. Basic functions and commands are probably not affected.
<b>Action</b>	No action necessary. Please contact your software supplier for a possible software update.
<b>INOAAE0179</b>	<b>Error in inodmn conversation: request failed</b>
<b>Explanation</b>	This is an internal error in the event logging protocol. It could be caused by not fully compatible Tamino and System Management Hub versions.
<b>Action</b>	Please contact your software supplier for a possible software update.
<b>INOAAE0180</b>	<b>Too many parameters</b>
<b>Explanation</b>	A parameter has been specified repeatedly, but is only allowed once.
<b>Action</b>	Change the command and retry.

<b>INOAAE0181</b>	<b>Database does not exist</b>
<b>Explanation</b>	There is no database with the given name.
<b>Action</b>	Choose a valid database name.
<b>INOAAE0182</b>	<b>Space space is not a valid backup space</b>
<b>Explanation</b>	The file or tape specified has not been recognized as a valid Tamino backup. The file or tape could be damaged or access to the medium could be denied.
<b>Action</b>	Use a valid backup space.
<b>INOAAE0183</b>	<b>Backup spaces have not been specified in the sequence determined by their extent or stream numbers</b>
<b>Explanation</b>	The spaces are not ordered by their extent or stream number. The first space does not have the extent number 1.
<b>Action</b>	Specify backup spaces in the order of the extent or stream number.
<b>INOAAE0184</b>	<b>Creation of directory path failed</b>
<b>Explanation</b>	The directory at the given path could not be created.
<b>Action</b>	Check the permissions for the given path.
<b>INOAAE0186</b>	<b>Unknown command</b>
<b>Explanation</b>	The command is unknown in this context.
<b>Action</b>	Specify a valid command for this context.
<b>INOAAE0187</b>	<b>Missing parameter</b>
<b>Explanation</b>	A parameter specification is missing.
<b>Action</b>	Specify the needed parameter.
<b>INOAAE0188</b>	<b>Not allowed to set a location of type 'type' as default location</b>
<b>Explanation</b>	The location represents a type which is not allowed to be set as the default location.
<b>Action</b>	Set another location as the default location.

---

<b>INOAAE0189</b>	<b>No valid location category specified</b>
<b>Explanation</b>	The specified category is not a valid location category.
<b>Action</b>	Specify a valid location category.
<b>INOAAE0190</b>	<b>Memory fault</b>
<b>Explanation</b>	An error has occurred while allocating memory storage.
<b>Action</b>	Reboot the system.
<b>INOAAE0191</b>	<b>database space spaceNo at location oldLoc not found</b>
<b>Explanation</b>	A database space cannot be moved from one location to another, because the space does not exist at the source location.
<b>Action</b>	Search for the space at another location.
<b>INOAAE0192</b>	<b>database space spaceNo at location newLoc already exists</b>
<b>Explanation</b>	The database space cannot be moved to the new location. The space already exists.
<b>Action</b>	Delete the space from the new location.
<b>INOAAE0193</b>	<b>Cannot remove database space spaceNo from location oldLoc</b>
<b>Explanation</b>	A database space cannot be removed from the source location.
<b>Action</b>	Check the permissions for the database space. The database space could be in use by a running database. Do a shutdown of the database and try again.
<b>INOAAE0194</b>	<b>Cannot write internal configuration store</b>
<b>Explanation</b>	The write operation into the internal configuration store failed.
<b>Action</b>	Check the permissions.
<b>INOAAE0195</b>	<b>Unknown database dbname or no information from Software AG XTS Directory Server</b>
<b>Explanation</b>	The database is unknown or there is no information from the Software AG XTS Directory Server.
<b>Action</b>	Check the database name, and check if the Software AG XTS Directory Server is running.

<b>INOAAE0196</b>	<b>Database dbname ID or port not found</b>
<b>Explanation</b>	The database ID or port was not found in the internal configuration store.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0197</b>	<b>Database dbname already active</b>
<b>Explanation</b>	The database is already active.
<b>Action</b>	Stop the database and re-execute the operation.
<b>INOAAE0198</b>	<b>Database dbname not active</b>
<b>Explanation</b>	The database is not active.
<b>Action</b>	Start the database and re-execute the operation.
<b>INOAAE0203</b>	<b>Function 'name' not found</b>
<b>Explanation</b>	The function was deleted, but the display has not been refreshed.
<b>Action</b>	Refresh your display.
<b>INOAAE0204</b>	<b>Invalid function type 'type'</b>
<b>Explanation</b>	The type of a server extension function was invalid. This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0205</b>	<b>File 'path' not added</b>
<b>Explanation</b>	The file was not added to the server extension package. This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0208</b>	<b>Not allowed to specify a recoverydate with recoveryoption=no</b>
<b>Explanation</b>	If a recoverydate is specified, recoveryoption=no is not allowed.
<b>Action</b>	Specify recoveryoption=yes or do not use the recoveryoption parameter.
<b>INOAAE0209</b>	<b>Access Violation - You are not allowed to access the requested database</b>
<b>Explanation</b>	You are not authorized to access the database.
<b>Action</b>	Get authorization from the database administrator.

---

<b>INOAAE0210</b>	<b>Min Port must be lower than Max Port and Port Ranges cannot overlap</b>
<b>Explanation</b>	An invalid port range was specified. Min Port must be lower than Max Port and Port Ranges cannot overlap.
<b>Action</b>	Change the ports and retry the operation.
<b>INOAAE0212</b>	<b>Error reading database locations</b>
<b>Explanation</b>	An error occurred while reading database locations from the internal configuration store.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0215</b>	<b>Unknown category</b>
<b>Explanation</b>	The agent was called with an invalid category.
<b>Action</b>	Use a valid category for this agent.
<b>INOAAE0216</b>	<b>Missing database name</b>
<b>Explanation</b>	The database name is missing in the object ID.
<b>Action</b>	Use a valid object ID.
<b>INOAAE0217</b>	<b>Missing Object ID</b>
<b>Explanation</b>	The object ID is missing in the agent call parameter.
<b>Action</b>	Use a valid object ID.
<b>INOAAE0218</b>	<b>Missing database space type</b>
<b>Explanation</b>	The database space type is missing in the agent call parameter.
<b>Action</b>	Use a valid database space type.
<b>INOAAE0219</b>	<b>Unknown database space category</b>
<b>Explanation</b>	The database space category in the agent call parameter is unknown.
<b>Action</b>	Use a valid database space category .
<b>INOAAE0220</b>	<b>The database dbname does not exist</b>
<b>Explanation</b>	One of the following errors may have occurred: - XTS not configured in the "hosts" file - the XTS service not running - the database is not specified in the XTS configuration file xturl.cfg.
<b>Action</b>	Choose another database name, check XTS configuration.

<b>INOAAE0222</b>	<b>The database dbname must be offline</b>
<b>Explanation</b>	The database must be stopped for this operation.
<b>Action</b>	Shut down the database.
<b>INOAAE0225</b>	<b>Leave command request on Event Service failed</b>
<b>Explanation</b>	This request is part of the command synchronization scheme. This scheme synchronizes the execution of commands that might interfere otherwise and it prevents parallel execution of commands that should be executed only once per database at a time (like a backup).
<b>Action</b>	Check if the Event Service is running. If it is running, stop and re-start the service to initialize command synchronization
<b>INOAAE0226</b>	<b>Database status request on event demon failed</b>
<b>Explanation</b>	The status of a database could not be received from the event demon.
<b>Action</b>	Check if the event demon is running.
<b>INOAAE0229</b>	<b>Tape path does not exist</b>
<b>Explanation</b>	The tape with the specified path does not exist.
<b>Action</b>	Specify an existing tape path.
<b>INOAAE0230</b>	<b>Device path does not exist</b>
<b>Explanation</b>	The device with the specified path does not exist.
<b>Action</b>	Specify an existing device path.
<b>INOAAE0231</b>	<b>Could not create location name at path</b>
<b>Explanation</b>	Creating the location failed because of an internal configuration store error.
<b>Action</b>	Check access rights (privileges) of the connected user; the user must be a power user (administrator).
<b>INOAAE0232</b>	<b>Could not delete location name</b>
<b>Explanation</b>	Deleting the location failed because of an internal configuration store error.
<b>Action</b>	Please contact your software supplier.

---

<b>INOAAE0233</b>	<b>Could not rename location name to newname</b>
<b>Explanation</b>	Renaming the location failed because of an internal configuration store error.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0234</b>	<b>Could not set location name as default database location</b>
<b>Explanation</b>	Setting the location as the default location failed because of an internal configuration store error.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0235</b>	<b>Could not set location name as default backup database location</b>
<b>Explanation</b>	Setting the location as the default backup location failed because of an internal configuration store error.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0236</b>	<b>Could not modify default of database location category 'category'</b>
<b>Explanation</b>	Modifying the default database location category failed because of an internal configuration store error.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0238</b>	<b>Archive path is empty</b>
<b>Explanation</b>	The archive is empty or corrupt. Try with a correct archive.
<b>Action</b>	Correct the archive you want to work with.
<b>INOAAE0242</b>	<b>No database name specified</b>
<b>Explanation</b>	The database name must be specified.
<b>Action</b>	Specify the database name.
<b>INOAAE0243</b>	<b>database registration failed</b>
<b>Explanation</b>	The registration of a read only database failed.
<b>Action</b>	Check the source file/path and database name.

<b>INOAAE0268</b>	<b>Move command for location type 'type' not supported</b>
<b>Explanation</b>	The move command is not supported for some location types, especially tape.
<b>Action</b>	Specify a valid location type as the target of the move command.
<b>INOAAE0272</b>	<b>Backup date 'bckDate' specifies no valid backup set for database dbName</b>
<b>Explanation</b>	The given date was not found as a savepoint entry in the internal configuration store.
<b>Action</b>	Specify a valid date which corresponds to a valid savepoint entry in the internal configuration store.
<b>INOAAE0274</b>	<b>No collection name specified</b>
<b>Explanation</b>	The collection name must be specified for this operation.
<b>Action</b>	Specify the collection name.
<b>INOAAE0284</b>	<b>Unregister is not allowed for normal databases; use "delete" command</b>
<b>Explanation</b>	Use the "delete" command to remove a normal database.
<b>Action</b>	Use the batch command "delete" instead of "unregister".
<b>INOAAE0285</b>	<b>Delete is not allowed for CD databases; use "unregister" command</b>
<b>Explanation</b>	Use the "unregister" command to remove a CD database.
<b>Action</b>	Use the batch command "unregister" instead of "delete".
<b>INOAAE0287</b>	<b>External function name exceeds 80 characters</b>
<b>Explanation</b>	The length of the external function name may not exceed 80 characters.
<b>Action</b>	Specify a shorter function name.
<b>INOAAE0294</b>	<b>No file restored : name</b>
<b>Explanation</b>	No file was restored. Maybe there are no server extensions installed.
<b>Action</b>	If there are server extensions installed check your database.
<b>INOAAE0295</b>	<b>Directory not created : path</b>
<b>Explanation</b>	The specified directory was not created.
<b>Action</b>	Check the permissions of your file system.

---

<b>INOAAE0296</b>	<b>Directory not found : path</b>
<b>Explanation</b>	The specified directory was not found.
<b>Action</b>	Check the permissions of your file system.
<b>INOAAE0297</b>	<b>Database not running : name</b>
<b>Explanation</b>	The specified database is not running.
<b>Action</b>	Start the database.
<b>INOAAE0298</b>	<b>Server returned error code : type</b>
<b>Explanation</b>	The Tamino server returned an error code.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0304</b>	<b>Fail - command log switch to mode buffers buffers</b>
<b>Explanation</b>	This is a result message for a batch command.
<b>Action</b>	Check the database.
<b>INOAAE0305</b>	<b>Parameter not defined : name</b>
<b>Explanation</b>	No value given for a mandatory parameter.
<b>Action</b>	Retry the command with the specified parameter value.
<b>INOAAE0306</b>	<b>Invalid object identification : name</b>
<b>Explanation</b>	The given object identification is invalid.
<b>Action</b>	Retry the command with a correct object identification.
<b>INOAAE0307</b>	<b>Update of settings failed : name</b>
<b>Explanation</b>	The update of the given settings parameter failed.
<b>Action</b>	Check the job log for further information.
<b>INOAAE0310</b>	<b>Path exists; please remove it or use another one</b>
<b>Explanation</b>	This is an error message for creating a CD database in batch mode. A specified pathname exists already, so a different pathname must be supplied or the existing path must be removed.
<b>Action</b>	Remove the path or use another one.

<b>INOAAE0311</b>	<b>Invalid character used in the specified location name at position position</b>
<b>Explanation</b>	An invalid character has been specified in the location name. This can be a non-ASCII character or one of the special characters " %&,;! \=#[ ] \ < > "".
<b>Action</b>	Change the character.
<b>INOAAE0312</b>	<b>Invalid character used in the specified path at position position</b>
<b>Explanation</b>	An invalid character has been specified in the given path. This can be a non-ASCII character or one of the special characters "\.:*?\"> &\"" for Windows or ".*? \> ,;&!\" for all other operating systems.
<b>Action</b>	Change the character.
<b>INOAAE0313</b>	<b>Mapped documents exist : name</b>
<b>Explanation</b>	Mapped XML documents exist for the server extension.
<b>Action</b>	Delete the XML documents before uninstalling the server extension.
<b>INOAAE0314</b>	<b>Command not allowed if no function is selected</b>
<b>Explanation</b>	The server extension must contain at least one selected function.
<b>Action</b>	Select some functions from the object being packed.
<b>INOAAE0315</b>	<b>Database name contains invalid character "&amp;" (ampersand)</b>
<b>Explanation</b>	A database name can't contain the "&" character.
<b>Action</b>	Remove the "&" from the database name.
<b>INOAAE0347</b>	<b>Database could not be connected</b>
<b>Explanation</b>	The security manager could not connect to Tamino.
<b>Action</b>	Check if the database has been started.
<b>INOAAE0355</b>	<b>The first and last character of a name should not be a blank</b>
<b>Explanation</b>	Blanks are not allowed at the beginning and end of a name.
<b>Action</b>	Change the first/last character.

---

<b>INOAAE0356</b>	<b>ACL name contains invalid character:</b>
<b>Explanation</b>	Special characters are not allowed.
<b>Action</b>	Remove special characters from ACL name.
<b>INOAAE0359</b>	<b>Group name contains invalid allowed character:</b>
<b>Explanation</b>	Special characters are not allowed.
<b>Action</b>	Remove special characters from the group name.
<b>INOAAE0361</b>	<b>User ID contains invalid character:</b>
<b>Explanation</b>	Special characters are not allowed.
<b>Action</b>	Remove special characters from the user ID.
<b>INOAAE0362</b>	<b>User created with escaped XML special characters in description</b>
<b>Explanation</b>	XML special characters are not allowed.
<b>Action</b>	Remove special characters from the description.
<b>INOAAE0363</b>	<b>Special characters are not allowed in an ACE name:</b>
<b>Explanation</b>	Special characters are not allowed in an ACE name.
<b>Action</b>	Remove special character from ACE name.
<b>INOAAE0370</b>	<b>TSM@DLL_PARSE_ERR</b>
<b>Explanation</b>	The retrieved XML-document is invalid or the XML parser could not retrieve data.
<b>Action</b>	Shut down the database and restart it.
<b>INOAAE0372</b>	<b>TSM@DLL_UNKNOWN_ACL_OR_ACL_NOT_RETRIEVABLE</b>
<b>Explanation</b>	The mentioned ACL is no longer available. Maybe another concurrent session deleted it.
<b>Action</b>	Refresh the data within the Tamino Manager and try again.
<b>INOAAE0373</b>	<b>TSM@DLL_UNKNOWN_GROUP</b>
<b>Explanation</b>	The mentioned GROUP is no longer available. Maybe another concurrent session deleted it.
<b>Action</b>	Refresh the data within the Tamino Manager and try again

<b>INOAAE0377</b>	<b>Access control element 'name' already exists in access control list</b>
<b>Explanation</b>	The access control element already exists in an access control list.
<b>Action</b>	Change the name of the access control element.
<b>INOAAE0378</b>	<b>Version with compatibility level level of Tamino not found</b>
<b>Explanation</b>	For reading the backup, a Tamino version of the same compatibility level is required.
<b>Action</b>	Install a Tamino version of the required compatibility level.
<b>INOAAE0381</b>	<b>No container size information in backup file filename found</b>
<b>Explanation</b>	The backup file does not contain important information for restoring.
<b>Action</b>	Check the backup file or generate a new one.
<b>INOAAE0382</b>	<b>Not enough free memory</b>
<b>Explanation</b>	Not enough free memory.
<b>Action</b>	try closing other applications to free memory.
<b>INOAAE0386</b>	<b>Access Control List 'name' already exists</b>
<b>Explanation</b>	An access control list with the specified name already exists.
<b>Action</b>	Change the name of the access control list.
<b>INOAAE0387</b>	<b>User 'name' already exists</b>
<b>Explanation</b>	The given user already exists in the ino:user doctype.
<b>Action</b>	Supply a new user ID.
<b>INOAAE0388</b>	<b>User 'name' does not exist</b>
<b>Explanation</b>	The user ID has not been found in the ino:user doctype.
<b>Action</b>	Create the required user ID.
<b>INOAAE0389</b>	<b>Access control list 'name' does not exist</b>
<b>Explanation</b>	The access control list has not been found in the ino:acl doctype.
<b>Action</b>	Create the required access control list.

---

<b>INOAAE0390</b>	<b>User group 'name' does not exist</b>
<b>Explanation</b>	A user group with the given name has not been found in the ino:group doctype.
<b>Action</b>	Create the required group.
<b>INOAAE0391</b>	<b>Acename has not been defined</b>
<b>Explanation</b>	The command line parameter "acename" has not been provided.
<b>Action</b>	Provide the "acename" parameter.
<b>INOAAE0392</b>	<b>Permission has not been defined</b>
<b>Explanation</b>	The command line parameter "permission" has not been provided.
<b>Action</b>	Provide the parameter "permission".
<b>INOAAE0393</b>	<b>Aclname has not been defined</b>
<b>Explanation</b>	The command line parameter "aclname" has not been provided.
<b>Action</b>	Provide the parameter "aclname".
<b>INOAAE0394</b>	<b>Database is readonly</b>
<b>Explanation</b>	The database is readonly, updates are not possible.
<b>Action</b>	No action required.
<b>INOAAE0395</b>	<b>UserID has not been defined</b>
<b>Explanation</b>	The command line parameter "userid" has not been provided.
<b>Action</b>	Provide the parameter "userid".
<b>INOAAE0396</b>	<b>Groupname has not been defined</b>
<b>Explanation</b>	The command line parameter "groupname" has not been provided.
<b>Action</b>	Provide the parameter "groupname".
<b>INOAAE0397</b>	<b>Ace permission is not defined</b>
<b>Explanation</b>	The permission for the access control element is not defined.
<b>Action</b>	Provide the permission for the access control element.

<b>INOAAE0398</b>	<b>Permission has to be set to an allowed value</b>
<b>Explanation</b>	Permission has not been set to an allowed value.
<b>Action</b>	Set permission to an allowed value.
<b>INOAAE0399</b>	<b>Description has not been defined</b>
<b>Explanation</b>	Description has not been provided.
<b>Action</b>	Provide description.
<b>INOAAE0400</b>	<b>User group 'name' already exists</b>
<b>Explanation</b>	The usr group already exists in the ino:group doctype.
<b>Action</b>	Change the group name to one that does not already exist.
<b>INOAAE0401</b>	<b>Missing compatibility level : type</b>
<b>Explanation</b>	The source or target compatibility level was not specified.
<b>Action</b>	Specify the compatibility level and execute the command again.
<b>INOAAE0402</b>	<b>Set database version failed</b>
<b>Explanation</b>	The "set database" action failed. Read the error messages to get more information.
<b>Action</b>	Check the error messages that are generated before this message at runtime to get the reason.
<b>INOAAE0408</b>	<b>Some databases may be still active at system shutdown</b>
<b>Explanation</b>	An error occurred while all active databases were stopped.
<b>Action</b>	Shut down manually all active databases prior to the system shutdown; get assistance from your software supplier to fix the problems that were reported.
<b>INOAAE0412</b>	<b>This request is in conflict with another request that is currently being executed</b>
<b>Explanation</b>	Some commands that access the same resources are mutually exclusive. This message can also appear if a process has been killed with operating system means or has crashed while the crash held the critical section locked.
<b>Action</b>	Retry later. If no other command is active and no one else is currently executing administrative commands, shut down and restart the System Management Hub Event Layer Service.

---

<b>INOAAE0413</b>	<b>The request cannot be executed because a condition is missing</b>
<b>Explanation</b>	The request requires another command to be active.
<b>Action</b>	No action possible. Please contact your software supplier.
<b>INOAAE0414</b>	<b>Restore of database dbName failed</b>
<b>Explanation</b>	An error occurred while restoring the specified database.
<b>Action</b>	Try to detect the error, otherwise contact your software supplier.
<b>INOAAE0417</b>	<b>Web server 'wsname' does not exist</b>
<b>Explanation</b>	The IP address and/or port of web server cannot be changed; the specified web server does not exist.
<b>Action</b>	Use an existing web server.
<b>INOAAE0418</b>	<b>IP address of web server 'wsname' is invalid</b>
<b>Explanation</b>	The IP address of the web server is invalid.
<b>Action</b>	Specify the IP address in a valid format.
<b>INOAAE0419</b>	<b>File 'path' already exists</b>
<b>Explanation</b>	The server extension installation file already exists.
<b>Action</b>	Select another path name.
<b>INOAAE0423</b>	<b>Unable to execute command with version 'argbatchversion' for database from version 'version'. Please use 'version=version' parameter for argbatch command, or change your environment : 'argbatch set environment version=version'.</b>
<b>Explanation</b>	A Tamino agent was called from the wrong version.
<b>Action</b>	Use the "version" parameter for the argbatch command or change your environment with: "argbatch set environment version=...".
<b>INOAAE0428</b>	<b>Web server 'wsname' not defined</b>
<b>Explanation</b>	The specified web server is not defined in the web server management.
<b>Action</b>	Add the specified web server in the web server management.

<b>INOAAE0439</b>	<b>Tamino plug-in for argevsrv not installed or not properly initialized</b>
<b>Explanation</b>	The Tamino plug-in was not installed, or the System Management Hub Event Service was unable to load it. Tamino will work without it but some administrative commands will not be be synchronized. This will cause problems only in rare conditions when multiple databases are created at the same time on the same computer.
<b>Action</b>	Avoid creating multiple databases at the same time on the same computer; please contact your software supplier to find out why the Tamino plug-in was not loaded by the System Management Hub Event Service.
<b>INOAAE0441</b>	<b>version of database not found</b>
<b>Explanation</b>	The database was found but not the version of Tamino that it requires.
<b>Action</b>	Check if the correct Tamino version for database is installed or set the version to one installed on the machine.
<b>INOAAE0442</b>	<b>Tamino version not found</b>
<b>Explanation</b>	The specified Tamino version was not found.
<b>Action</b>	Check if the Tamino version is installed on the machine.
<b>INOAAE0443</b>	<b>highest Tamino version not found</b>
<b>Explanation</b>	The highest Tamino version was not found.
<b>Action</b>	Check if Tamino is installed on the machine
<b>INOAAE0444</b>	<b>Max and/or Min port not found or RGS error</b>
<b>Explanation</b>	The Max and/or Min port was not found, or there was an RGS error.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0456</b>	<b>The "Move database space" function failed</b>
<b>Explanation</b>	An attempt to move a database space failed. Additional information is supplied in error messages that have occurred earlier.
<b>Action</b>	Please follow the actions of the error messages displayed earlier in the same job log.
<b>INOAAE0459</b>	<b>The "Create Database" function failed</b>
<b>Explanation</b>	An attempt to create a database failed. Additional information is supplied in error messages that have occurred earlier.
<b>Action</b>	Please follow the actions of the error messages displayed earlier in the same job log.

---

<b>INOAAE0462</b>	<b>The "Delete Database" function failed</b>
<b>Explanation</b>	An attempt to delete a database failed. Additional information is supplied in error messages that have occurred earlier.
<b>Action</b>	No action required. Please follow the actions of the error messages displayed earlier in the same job log.
<b>INOAAE0463</b>	<b>The database information is available in ONLINE mode only</b>
<b>Explanation</b>	The information can only be determined when the database is started.
<b>Action</b>	Start the database and call the information function again.
<b>INOAAE0472</b>	<b>Backup of database dbName failed</b>
<b>Explanation</b>	Errors occurred while backing up the specified database. A possible reason could be low system memory.
<b>Action</b>	Try to detect the error, otherwise contact your software supplier.
<b>INOAAE0474</b>	<b>Start of database dbName failed</b>
<b>Explanation</b>	Errors occurred while starting the database.
<b>Action</b>	Try to detect the error, otherwise contact your software supplier.
<b>INOAAE0475</b>	<b>Stop of database dbName failed</b>
<b>Explanation</b>	Errors occurred while stopping the specified database.
<b>Action</b>	If you cannot identify the error from a previous error message, please contact your software supplier.
<b>INOAAE0480</b>	<b>Add database space spaceNo to location newLoc failed</b>
<b>Explanation</b>	An attempt to add database spaces to the specified location failed.
<b>Action</b>	No action required.
<b>INOAAE0481</b>	<b>Not enough space on location newLoc</b>
<b>Explanation</b>	The new location to which the database space should be moved is not big enough.
<b>Action</b>	Choose a larger location for moving the database space.

<b>INOAAE0491</b>	<b>Error(s) occurred during modify of database properties</b>
<b>Explanation</b>	An error occurred while attempting to modify database properties. Only the properties with an error message or a warning were not modified. All other properties are changed.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0509</b>	<b>External function name already used : name</b>
<b>Explanation</b>	The external name of a server extension function is already in use.
<b>Action</b>	Change the external function name and retry the operation.
<b>INOAAE0510</b>	<b>Java classpath not modified : text</b>
<b>Explanation</b>	The Java classpath was not modified according to the modification rules.
<b>Action</b>	Correct the modification parameters and retry the operation.
<b>INOAAE0534</b>	<b>File 'path' not deleted</b>
<b>Explanation</b>	The server extension DLL file could not be deleted.
<b>Action</b>	Delete the DLL manually.
<b>INOAAE0547</b>	<b>Directory path does not exist</b>
<b>Explanation</b>	The directory with the specified path does not exist.
<b>Action</b>	Specify an existing path.
<b>INOAAE0548</b>	<b>No location name specified</b>
<b>Explanation</b>	No location name was specified.
<b>Action</b>	Specify a location name.
<b>INOAAE0549</b>	<b>Character " not allowed as part of location name</b>
<b>Explanation</b>	The character '\' is not allowed as part of the location name, because this name is used as internal configuration store key, and the '\' is the internal configuration store key delimiter.
<b>Action</b>	Replace this character by another one.

---

<b>INOAAE0567</b>	<b>There is currently only one location defined. Please create at least one more file system location using the Location Management 'Add' command.</b>
<b>Explanation</b>	No second location is defined that can be used as destination location for the move command .
<b>Action</b>	Create a second location and then start this command again.
<b>INOAAE0605</b>	<b>Wrong date or date format. Format 'datepattern' required.</b>
<b>Explanation</b>	An invalid date is specified or an invalid date format is used.
<b>Action</b>	Specify a valid date (use same format as used in 'argbatch show backups').
<b>INOAAE0608</b>	<b>No other Tamino version installed, set version not possible</b>
<b>Explanation</b>	Because there is no other Tamino version installed, it makes no sense to change the version.
<b>Action</b>	No action required.
<b>INOAAE0611</b>	<b>Named pipe path does not exist</b>
<b>Explanation</b>	The named pipe with the specified path does not exist.
<b>Action</b>	Specify an existing named pipe path.
<b>INOAAE0619</b>	<b>Device path is not a named pipe</b>
<b>Explanation</b>	The specified path is not a named pipe.
<b>Action</b>	Specify an existing named pipe path.
<b>INOAAE0637</b>	<b>Directory name 'path' not compatible with object identification 'name'</b>
<b>Explanation</b>	The directory name must consist of the first part of the object identification.
<b>Action</b>	Create a new server extension package with the correct directory name.
<b>INOAAE0638</b>	<b>Server extension function 'name' does not exist</b>
<b>Explanation</b>	The specified server extension function does not exist.
<b>Action</b>	Correct the function name.

<b>INOAAE0639</b>	<b>Server extension function parameter 'name' does not exist</b>
<b>Explanation</b>	The specified server extension function parameter does not exist.
<b>Action</b>	Correct the parameter name.
<b>INOAAE0641</b>	<b>Internal error from DSIF interface name returncode returncode error number errornr</b>
<b>Explanation</b>	This is an internal error message.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0645</b>	<b>Stop of XML session 'session' failed</b>
<b>Explanation</b>	Errors occurred while stopping the specified XML session.
<b>Action</b>	Try to detect the error, otherwise contact your software supplier.
<b>INOAAE0646</b>	<b>Error reading backup methods for database dbname</b>
<b>Explanation</b>	No backup methods were found in the internal configuration store for the database.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0648</b>	<b>Error reading parameters of backup method 'method'</b>
<b>Explanation</b>	No parameters were found for the backup method in the internal configuration store.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0651</b>	<b>Could not set global parameters for external backup method 'method' of database dbname</b>
<b>Explanation</b>	Setting of global parameters failed because of an internal configuration store error.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0653</b>	<b>Could not set configuration parameters for external backup method 'method' of database dbname</b>
<b>Explanation</b>	Setting of configuration parameters failed because of an internal configuration store error.
<b>Action</b>	Please contact your software supplier.

---

<b>INOAAE0656</b>	<b>Could not delete configuration 'configuration' of method 'method' of database dbname</b>
<b>Explanation</b>	The deletion of the configuration failed.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0658</b>	<b>Error reading configurations for database dbname of backup method 'method'</b>
<b>Explanation</b>	An error occurred while reading the configuration data.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0659</b>	<b>No configuration found for database dbname of backup method 'method'</b>
<b>Explanation</b>	No configuration data was specified for this method and database.
<b>Action</b>	Specify configuration data for this method and database using the 'External Backup Environment' dialog.
<b>INOAAE0660</b>	<b>Replication database name expected</b>
<b>Explanation</b>	The replication database name must be specified for this function.
<b>Action</b>	Specify the replication database name
<b>INOAAE0662</b>	<b>The database replication_db cannot be added into the permission list</b>
<b>Explanation</b>	An error occurred while adding the replication database name to the permission list.
<b>Action</b>	Check the subsequent error messages for more details.
<b>INOAAE0665</b>	<b>Database database cannot be set as replication database</b>
<b>Explanation</b>	An error occurred during the type change. The database cannot be set to a replication database. Possible reason: This database is a master database.
<b>Action</b>	Check for related additional messages.
<b>INOAAE0667</b>	<b>Replication database database cannot be reset to normal type</b>
<b>Explanation</b>	The database cannot be reset to a normal database.
<b>Action</b>	See the subsequent error messages.

<b>INOAAE0668</b>	<b>Database master_database is not active or is not a master database</b>
<b>Explanation</b>	The master database must be in the active state or permit this database to be replicated.
<b>Action</b>	Start up the master database and check the permission list for replication databases.
<b>INOAAE0669</b>	<b>Replication of master database master_database is not permitted</b>
<b>Explanation</b>	Permission to replicate the master database was denied.
<b>Action</b>	Ask the administrator to permit replication access to the master database.
<b>INOAAE0672</b>	<b>Not enough space at location newLoc for additional newsize MB - maximum free is freesize MB</b>
<b>Explanation</b>	The new location to which the database space should be moved or added is not big enough.
<b>Action</b>	Choose a larger location for the database space operation.
<b>INOAAE0680</b>	<b>Backup(s) not found wrongbackups please use one of the following backups</b>
<b>Explanation</b>	Wrong backups were specified.
<b>Action</b>	Use only valid backups of the database. You can see all backups with the command "argbatch show backups database=mydatabase".
<b>INOAAE0681</b>	<b>At least one backup must be given or don't use keepbackups</b>
<b>Explanation</b>	For the option keepbackups, at least one backup must be given/selected.
<b>Action</b>	Give/select at least one backup.
<b>INOAAE0683</b>	<b>Switching log space for database dbName has failed</b>
<b>Explanation</b>	Errors occurred while switching log space for the database.
<b>Action</b>	Try to detect the error, otherwise contact your software supplier.
<b>INOAAE0684</b>	<b>At least one destination directory must be given with parameter "destinationdirectory_0"</b>
<b>Explanation</b>	the option "keep backup files" needs at least one destination directory.
<b>Action</b>	Specify a destination directory with the parameter "destinationdirectory_0".

---

<b>INOAAE0685</b>	<b>For option "keepbackups=selected" at least one backup date and at least one destination directory must be given with parameter "destinationdirectory_0", "backupdate_0"</b>
<b>Explanation</b>	Give at least one backup date and one destination directory in the parameter list.
<b>Action</b>	Use the parameter "backupdate_0" to specify a backup to be kept and "destinationdirectory_0" for the destination directory.
<b>INOAAE0691</b>	<b>Could not add backup method 'method' for database dbname</b>
<b>Explanation</b>	Adding the backup method failed because of an internal configuration store error.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0694</b>	<b>Could not delete method 'method' of database dbname</b>
<b>Explanation</b>	Deleting the backup method failed because of an internal configuration store error.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0696</b>	<b>Internal error errno during modify property 'name' to 'value'</b>
<b>Explanation</b>	An error occurred while setting a new property value.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0699</b>	<b>Deletion of backup 'bckDate' of database dbName failed</b>
<b>Explanation</b>	An error occurred while deleting the specified backup.
<b>Action</b>	Check the additional messages.
<b>INOAAE0707</b>	<b>No permission to modify the type of the database</b>
<b>Explanation</b>	To change the type of a database to a replication database or to set it back to a normal one, the user needs to have administrator rights. Other possible reason: The database is not allowed to replicate the master database.
<b>Action</b>	Log in as administrator and try the operation again and check whether this database is in the permission list of the master database.
<b>INOAAE0708</b>	<b>Update server sessions exist</b>
<b>Explanation</b>	The database has already update sessions so that it cannot be used to replicate another database.
<b>Action</b>	Use a newly created database and retry this operation.

<b>INOAAE0709</b>	<b>Passwords not matched</b>
<b>Explanation</b>	The passwords entered do not match.
<b>Action</b>	Please ensure the passwords match.
<b>INOAAE0725</b>	<b>Error while changing port ranges</b>
<b>Explanation</b>	An error occurred while changing the port ranges.
<b>Action</b>	Please contact you software supplier.
<b>INOAAE0727</b>	<b>path is not a raw section</b>
<b>Explanation</b>	The specified path must be a raw section.
<b>Action</b>	Ensure that the path specifies a raw section.
<b>INOAAE0728</b>	<b>Unable to load data for CD databases</b>
<b>Explanation</b>	This database is a CD database. Data load not possible.
<b>Action</b>	No action required.
<b>INOAAE0731</b>	<b>Rename web server failed</b>
<b>Explanation</b>	The web server could not be renamed, the operation failed.
<b>Action</b>	The reason why the web server could not be renamed is in the job log. Check it and retry.
<b>INOAAE0733</b>	<b>Add web server failed</b>
<b>Explanation</b>	The web server could not be added, the operation failed.
<b>Action</b>	The reason why the web server could not be added is in the job log. Check it and retry.
<b>INOAAE0737</b>	<b>Delete web server failed</b>
<b>Explanation</b>	The web server could not be deleted, the operation failed.
<b>Action</b>	The reason why the web server could not be deleted is in the job log. Check it and retry.

---

<b>INOAAE0740</b>	<b>Modify web server failed</b>
<b>Explanation</b>	The web server could not be modified, the operation failed.
<b>Action</b>	The reason why the web server could not be modified is in the job log. Check it and retry.
<b>INOAAE0741</b>	<b>Domain 'name' does not exist</b>
<b>Explanation</b>	Domain has not been defined.
<b>Action</b>	Please check the defined domains list in Tamino and create the domain if necessary.
<b>INOAAE0744</b>	<b>parameter name: must not be a location on a raw section, is only allowed on DATA, INDEX, JOURNAL and RESERVED location</b>
<b>Explanation</b>	A location on raw section is only allowed as DATA, INDEX, JOURNAL and RESERVED location.
<b>Action</b>	Use a location that is not located on a raw section.
<b>INOAAE0745</b>	<b>All reserved locations are located on raw section(s), at least one location must not be located on a raw section</b>
<b>Explanation</b>	At least one reserved location for a database must not be on a raw section.
<b>Action</b>	Use at lease one location not located on a raw section.
<b>INOAAE0746</b>	<b>Location locname is of type type, this type is not allowed for loctype</b>
<b>Explanation</b>	Some location types are only allowed for special locations. For example locations on a tape are only allowed for backup locations.
<b>Action</b>	Use a location which is allowed for the current location type.
<b>INOAAE0747</b>	<b>Not allowed to set a location of type 'type' as default backup location</b>
<b>Explanation</b>	The default backup location cannot be in a location of type "raw".
<b>Action</b>	Use a location of a type that is allowed for a backup location.
<b>INOAAE0749</b>	<b>This command is deprecated. Please use the new command "show acs".</b>
<b>Explanation</b>	The command has been replaced by a new command.
<b>Action</b>	Please use the new command.

<b>INOAAE0750</b>	<b>This command is deprecated. Please use the new command "show groups".</b>
<b>Explanation</b>	The command is deprecated.
<b>Action</b>	Please use the new command.
<b>INOAAE0753</b>	<b>Query internal configuration store key key failed</b>
<b>Explanation</b>	An error occurred when querying the given internal configuration store key.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0754</b>	<b>This command is deprecated. Please use the new command "show users".</b>
<b>Explanation</b>	The command is deprecated.
<b>Action</b>	Please use the new command.
<b>INOAAE0755</b>	<b>Access to internal configuration store value value key key failed</b>
<b>Explanation</b>	An error occurred when getting the given internal configuration store key value.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0761</b>	<b>parameter name: must be the logical name of an existing location</b>
<b>Explanation</b>	The parameter must specify the short, "logical" name of a location (not its entire path), and the location must exist.
<b>Action</b>	Display the the "Locations" tree node in the System Management Hub (under the "Tamino" node) to display a list of existing locations or to add a new location.
<b>INOAAE0762</b>	<b>parameter name: must contain only digits 0 to 9</b>
<b>Explanation</b>	The value for this parameter must be an integer number with no fractional parts.
<b>Action</b>	Re-enter the parameter using only digits 0-9.
<b>INOAAE0763</b>	<b>parameter name: must be "yes" or "no"</b>
<b>Explanation</b>	This parameter must have either the value "yes" or "no", all lowercase characters.
<b>Action</b>	Re-enter either "yes" or "no" (without the double quotes).
<b>INOAAE0764</b>	<b>parameter name: must only contain digits 0-9, comma, dot, "E" or "e" for exponentiation</b>
<b>Explanation</b>	The value for this parameter must be a valid floating point number, or a number with an exponent.
<b>Action</b>	Re-enter he parameter value as floating point number, or with an exponent. Depending on the locale settings on the local computer, the decimal sign may be expected either as "," or as a ".".

<b>INOAAE0766</b>	<b>Size for space type extent extend is missing and no default size available</b>
<b>Explanation</b>	No default size could be obtained for this space type.
<b>Action</b>	A size must be specified, and it must be above the minimum value for this space type.
<b>INOAAE0767</b>	<b>The size specified for space type extent extend is under the minimum (minimum size Mb)</b>
<b>Explanation</b>	The given size for the extent is too small.
<b>Action</b>	A size of at least the given minimum must be specified.
<b>INOAAE0768</b>	<b>At least one backup location must be in the filesystem if no tape is supplied as initial backup</b>
<b>Explanation</b>	If no tape is supplied to create the database from (in the "Create From Backup" command) the initial backup is created at creation time as a file and requires a location that is in the file system. Before this message was issued, attempts were made to create it in one of the provided backup locations, in the default backup location and in the default location.
<b>Action</b>	Create a location in the file system using the "Add" command the System Management Hub browser interface, tree node Tamino/DB Locations and make it the default location (by clicking the new location and executing the "Set Default" command).
<b>INOAAE0769</b>	<b>At least one backup location is required for the initial backup of the new database</b>
<b>Explanation</b>	Specify one or more location where backups shall be created later on. This location is already required and used during the creation of the new database.
<b>Action</b>	Specify one or more writable, random accessible backup locations for the database to be created
<b>INOAAE0774</b>	<b>Database version with compatibility level of CD database not installed or found</b>
<b>Explanation</b>	A Tamino of the same compatibility level of CD database must be installed to use the CD database
<b>Action</b>	Install a database of the same compatibility level.
<b>INOAAE0775</b>	<b>Database name contains invalid character "*" (asterisk)</b>
<b>Explanation</b>	A database name cannot contain the "*" character.
<b>Action</b>	Remove the "*" from the database name.

<b>INOAAE0776</b>	<b>This command is deprecated. Please use the new command "show users".</b>
<b>Explanation</b>	This command is not supported as the user descriptions can be seen in the results of the new command.
<b>Action</b>	Please do not use this command and use the new one instead.
<b>INOAAE0778</b>	<b>Database name contains invalid character "/" (slash)</b>
<b>Explanation</b>	A database name cannot contain "/" character.
<b>Action</b>	Remove the "/" from database name.
<b>INOAAE0779</b>	<b>Port address 'buf' is invalid. Valid range is 0 - 65535.</b>
<b>Explanation</b>	The specified port address is not valid.
<b>Action</b>	Specify a valid port address in the range 0 to 65535.
<b>INOAAE0784</b>	<b>Database name contains invalid character "&lt;" (less than)</b>
<b>Explanation</b>	A database name cannot contain the "<" character.
<b>Action</b>	Remove the "<" from database name.
<b>INOAAE0785</b>	<b>Database name contains invalid character "&gt;" (greater than)</b>
<b>Explanation</b>	A database name cannot contain the ">" character.
<b>Action</b>	Remove the ">" from database name
<b>INOAAE0786</b>	<b>This command is deprecated. Please use the new command "show acesofacl".</b>
<b>Explanation</b>	The command is deprecated.
<b>Action</b>	Please use the new command.
<b>INOAAE0787</b>	<b>Domain parameters missing</b>
<b>Explanation</b>	Some or all of the necessary parameters for the domain creation/modification are missing.
<b>Action</b>	Please ensure that all necessary domain parameters are defined.
<b>INOAAE0788</b>	<b>Unrecognized domain parameters</b>
<b>Explanation</b>	The domain parameters defined are not valid for the domain type being created/modified.
<b>Action</b>	Please ensure that the correct domain parameters for the domain type being created/modified are defined.

---

<b>INOAAE0792</b>	<b>Namespace declarations required. Please check that all namespaces are defined.</b>
<b>Explanation</b>	There are some namespace prefixes for which no namespace declarations have been defined.
<b>Action</b>	Please ensure namespace declarations exist for all namespace prefixes.
<b>INOAAE0794</b>	<b>Internal error occurred</b>
<b>Explanation</b>	Internal error code 41 occurred.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0797</b>	<b>Domain 'name' already exists</b>
<b>Explanation</b>	A domain with the same name exists.
<b>Action</b>	Please choose another name.
<b>INOAAE0798</b>	<b>Failed to open input file filename for data load</b>
<b>Explanation</b>	The file cannot be opened or does not exist.
<b>Action</b>	Check the input and start the operation again.
<b>INOAAE0799</b>	<b>Parameter 'newname' or 'new_name' missing. The 'new_name' parameter is deprecated, please use the 'newname' parameter for the new name of the database.</b>
<b>Explanation</b>	No parameter with the new name of the database was given.
<b>Action</b>	Provide the database name using the parameter 'newname'.
<b>INOAAE0802</b>	<b>Could not connect to inodmn. Port number not found in internal configuration store, probably not installed.</b>
<b>Explanation</b>	The Software AG EventLayer Service is not installed correctly.
<b>Action</b>	Try re-installing the System Management Hub. Check for a fix or an update from your software supplier.
<b>INOAAE0803</b>	<b>Could not connect to inodmn, service not running</b>
<b>Explanation</b>	The "Software AG EventLayer Service" is not running, database functions and commands are probably unaffected.
<b>Action</b>	Restart the service. If the problem persists, contact your software supplier for an update or fix.

<b>INOAAE0807</b>	<b>Invalid parameter name 'name' specified.</b>
<b>Explanation</b>	The parameter name specified is not valid since it contains one or more space characters.
<b>Action</b>	Specify a parameter name that does not contain space characters.
<b>INOAAE0812</b>	<b>Web server IP address 'ipAddress' is invalid</b>
<b>Explanation</b>	The specified web server IP address is invalid.
<b>Action</b>	Specify a valid IP address. The valid range is 0 - 255.
<b>INOAAE0817</b>	<b>No license for raw section support</b>
<b>Explanation</b>	The use of raw sections requires an appropriate license option.
<b>Action</b>	Contact your software supplier for a license option to support raw sections.
<b>INOAAE0818</b>	<b>No raw section support for the used platform</b>
<b>Explanation</b>	There is no raw section support for the used platform.
<b>Action</b>	Do not use raw sections.
<b>INOAAE0819</b>	<b>Raw section support internal error</b>
<b>Explanation</b>	There was an internal error while processing a raw section.
<b>Action</b>	Please contact your software supplier.
<b>INOAAE0820</b>	<b>Raw section initialization failed</b>
<b>Explanation</b>	An error occurred while initializing a raw section.
<b>Action</b>	Check the raw section.
<b>INOAAE0825</b>	<b>Master database must be restarted before a replication database can be set up</b>
<b>Explanation</b>	A restart of the master database is necessary.
<b>Action</b>	Restart the master database and try to set up the replication database again.
<b>INOAAE0826</b>	<b>Inconsistency detected while setting the database to replication type</b>
<b>Explanation</b>	This database is not suitable to be set as the replication database of the specified master database. Perhaps the versions are not identical or this one was not created from the backup of the master. Also possible is that this database has its own updates after the creation.
<b>Action</b>	Use another database to replicate the master.

---

<b>INOAAE0831</b>	<b>Only one location specified for parallel backup</b>
<b>Explanation</b>	More than one location is required for parallel backup.
<b>Action</b>	Please specify more than one location for the parallel backup.
<b>INOAAE0832</b>	<b>Renaming a replication database master is not allowed.</b>
<b>Explanation</b>	Renaming a replication database master is not allowed, because the link between the master and replication databases would be lost.
<b>Action</b>	No action required.
<b>INOAAE0834</b>	<b>Database is a replication database master database. Deleting the replication database master is not allowed. No replication databases can be updated from this master database if this database is deleted.</b>
<b>Explanation</b>	Deleting this master database would mean that no replication databases could be updated from this master database. If you really want to delete this replication master database use the "force=yes" parameter for argbatch or check the "Force Delete of Replication Master Database" checkbox in the GUI.
<b>Action</b>	Use the "force=yes" parameter for argbatch or check the "Force Delete of Replication Master Database" checkbox in the GUI.
<b>INOAAE0835</b>	<b>Data load for database dbName failed</b>
<b>Explanation</b>	Load of data failed with error.
<b>Action</b>	Check the other related messages for more information.
<b>INOAAE0836</b>	<b>Unload data from database dbName failed</b>
<b>Explanation</b>	An error occurred while data was being unloaded from the database.
<b>Action</b>	Check for other messages related to this error for possible reasons.
<b>INOAAE0837</b>	<b>Location path path is read only</b>
<b>Explanation</b>	The location path specified is read only.
<b>Action</b>	Specify a location path with write access.
<b>INOAAE0838</b>	<b>Server extension does not contain a function</b>
<b>Explanation</b>	It was detected that no function has been defined for the server extension. Such a server extension is considered as invalid.
<b>Action</b>	Extend your server extension by at least one function.

<b>INOAAE0841</b>	<b>Uninstall of server extension name aborted</b>
<b>Explanation</b>	The uninstall operation for the server extension has not been completed due to functions that are used in some schema.
<b>Action</b>	Restart the uninstall operation with the parameter "force" set to "yes" (batch command).
<b>INOAAE0842</b>	<b>Uninstall of server extension 'name' failed</b>
<b>Explanation</b>	The uninstall operation failed.
<b>Action</b>	Check the job log to find the reason for the failure.
<b>INOAAE0843</b>	<b>Please specify either parameter IP address or node</b>
<b>Explanation</b>	The specification of the IP address or node is invalid.
<b>Action</b>	Please specify either the IP address or the node.
<b>INOAAE0844</b>	<b>Unable to find the replication database name from the permission list</b>
<b>Explanation</b>	The replication database name is not in the permission list.
<b>Action</b>	Check the parameter.
<b>INOAAE0845</b>	<b>Please specify either parameter IP address or node</b>
<b>Explanation</b>	Either the parameter IP address or node must be specified.
<b>Action</b>	Please specify either the parameter IP address or node.
<b>INOAAE0846</b>	<b>Upgrade from this database to Vversion not possible</b>
<b>Explanation</b>	This error occurs because the database cannot be upgraded directly to the target version.
<b>Action</b>	Upgrade to the next higher version and after that try a "set version" to the target version.
<b>INOAAE0847</b>	<b>Named pipe path not allowed for the specified location type</b>
<b>Explanation</b>	A named pipe is not allowed to set for the specified target location. Only the backup location type accepts named pipes.
<b>Action</b>	Specify another location for the target location.

---

<b>INOAAE0849</b>	<b>Cannot open event log session</b>
<b>Explanation</b>	Open event log session on argevsrv failed.
<b>Action</b>	Check that argevsrv is running.
<b>INOAAE0850</b>	<b>parameter name: must be of type FileSystem or RAW Section</b>
<b>Explanation</b>	Data, Index and Journal location must be of type FileSystem or RAW Section.
<b>Action</b>	Use a location of type FileSystem or RAW Section.
<b>INOAAE0852</b>	<b>This command is deprecated. Please use the new command "inoload".</b>
<b>Explanation</b>	This command is set to deprecated, use the new command instead.
<b>Action</b>	Use inoload to load or unload data in batch mode.
<b>INOAAE0855</b>	<b>Output directory directory does not exist</b>
<b>Explanation</b>	The output directory should exist.
<b>Action</b>	Create the output directory or check the permission if it already exists.
<b>INOAAE0868</b>	<b>Stop request requestid failed :errortext</b>
<b>Explanation</b>	Stop of a request failed.
<b>Action</b>	Check the error text for an explanation of why the operation failed.
<b>INOAAE0870</b>	<b>Query current active requests failed : message</b>
<b>Explanation</b>	A query of the current requests failed.
<b>Action</b>	Check the error message for more information.
<b>INOAAF0002</b>	<b>Version 'version' of Tamino not found. Please use 'set version' command to change the version to the installed version.</b>
<b>Explanation</b>	The specified Tamino version was not found.
<b>Action</b>	Use the "set version" command and change the version of the database.
<b>INOAAF0007</b>	<b>Cannot create database: reason</b>
<b>Explanation</b>	A database cannot be created with the parameters specified.
<b>Action</b>	Alter specified parameter value or provide missing parameter.

<b>INOAAF0253</b>	<b>Error reading savepoints for database dbname</b>
<b>Explanation</b>	An error occurred when reading database savepoint entries in the internal configuration store.
<b>Action</b>	Please contact your software supplier.
<b>INOAAF0254</b>	<b>Could not create XML document</b>
<b>Explanation</b>	An error occurred when creating an XML document.
<b>Action</b>	Reboot and restart the system.
<b>INOAAF0256</b>	<b>Open of event log failed</b>
<b>Explanation</b>	An error occurred when creating an event session.
<b>Action</b>	Check the event demon.
<b>INOAAF0262</b>	<b>Error reading database locations for savepoint 'savepoint'</b>
<b>Explanation</b>	No database locations were found in the internal configuration store for the savepoint.
<b>Action</b>	Please contact your software supplier.
<b>INOAAF0264</b>	<b>Duplicate parameter name parameter</b>
<b>Explanation</b>	The parameter appears more than once in the parameter list, but only a single value is allowed.
<b>Action</b>	Check where the parameter given is repeated and issue the command again without it.
<b>INOAAF0265</b>	<b>Job initialization failed</b>
<b>Explanation</b>	The job log could not be initialized because of insufficient resources. This could be memory or SMP resources like locks or threads.
<b>Action</b>	Free resources and retry.
<b>INOAAF0267</b>	<b>Rename database failed</b>
<b>Explanation</b>	The database could not be renamed.
<b>Action</b>	The reason why the database could not renamed is in the job log. Check it and retry.

---

<b>INOAAF0369</b>	<b>TSM@DLL *** FATAL ERROR NO ROLLBACK POSSIBLE (SESSION LOST) ***</b>
<b>Explanation</b>	Tamino reported an invalid session ID.
<b>Action</b>	Shut down the database and restart it.
<b>INOAAI0000</b>	<b>Change License file</b>
<b>Explanation</b>	Change license file.
<b>Action</b>	No action required.
<b>INOAAI0003</b>	<b>Modify journal space of database dbname</b>
<b>Explanation</b>	The size of the journal space is being modified.
<b>Action</b>	No action required.
<b>INOAAI0005</b>	<b>Modify journal space successfully finished</b>
<b>Explanation</b>	This message indicates that the "Modify journal space" function completed successfully.
<b>Action</b>	No action required.
<b>INOAAI0006</b>	<b>Modification and reorganization of journal space in location Location from oldsize MB to one journal space of newsize MB</b>
<b>Explanation</b>	The journal space size is being modified at the given location. If more the one journal space exists, the journal space is reorganized to one of the given size.
<b>Action</b>	No action required.
<b>INOAAI0008</b>	<b>Modify properties of Email notification</b>
<b>Explanation</b>	Email notification properties are being modified.
<b>Action</b>	No action required.
<b>INOAAI0009</b>	<b>Add location name at path</b>
<b>Explanation</b>	Start of the "add location" function.
<b>Action</b>	Information message, no action required.
<b>INOAAI0010</b>	<b>Delete location name</b>
<b>Explanation</b>	Start of the "delete location" function.
<b>Action</b>	Information message, no action required.

<b>INOAAI0011</b>	<b>Moving location oldloc to newloc</b>
<b>Explanation</b>	Start of the "move location" function.
<b>Action</b>	Information message, no action required.
<b>INOAAI0012</b>	<b>Rename location name to newname</b>
<b>Explanation</b>	Start of the "rename location" function.
<b>Action</b>	Information message, no action required.
<b>INOAAI0013</b>	<b>Set location name as default database location</b>
<b>Explanation</b>	Start of the "set default location" function.
<b>Action</b>	Information message, no action required.
<b>INOAAI0014</b>	<b>Set location name as default backup database location</b>
<b>Explanation</b>	Start of the "set default backup location" function.
<b>Action</b>	Information message, no action required.
<b>INOAAI0015</b>	<b>Modify default of database location category 'category'</b>
<b>Explanation</b>	Start of the "modify default of database location category" function.
<b>Action</b>	Information message, no action required.
<b>INOAAI0016</b>	<b>Database Version set to version</b>
<b>Explanation</b>	The database was set to the specified version.
<b>Action</b>	Information message, no action required.
<b>INOAAI0017</b>	<b>Modify Email notification properties successfully finished</b>
<b>Explanation</b>	Email notification properties have been modified successfully.
<b>Action</b>	No action required.
<b>INOAAI0021</b>	<b>Unregistering database dbName</b>
<b>Explanation</b>	This is a job log identification message.
<b>Action</b>	No action required.

---

<b>INOAAI0023</b>	<b>New license file successfully applied.</b>
<b>Explanation</b>	The license file was successfully applied.
<b>Action</b>	No action required.
<b>INOAAI0025</b>	<b>Please log in again to the web application in order to use the new product license!</b>
<b>Explanation</b>	The new functionality is available after you log in again.
<b>Action</b>	Log in again and restart your web applications.
<b>INOAAI0028</b>	<b>Confirmed all pending alerts</b>
<b>Explanation</b>	All warnings, errors and fatal errors of the job records specified have been acknowledged.
<b>Action</b>	No action required.
<b>INOAAI0033</b>	<b>New value of dynamic property 'name' is effective now</b>
<b>Explanation</b>	The property value has been updated and is active from now on.
<b>Action</b>	No action required.
<b>INOAAI0035</b>	<b>Database has been successfully unregistered</b>
<b>Explanation</b>	This message indicates, that the "Unregister Database" function is completed.
<b>Action</b>	No action required.
<b>INOAAI0037</b>	<b>Pending alerts of all jobs have been confirmed</b>
<b>Explanation</b>	All warnings, errors and fatal errors have been confirmed. The job records may be deleted now.
<b>Action</b>	No action required.
<b>INOAAI0048</b>	<b>Server extension command execution</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.
<b>INOAAI0049</b>	<b>Command Name : name</b>
<b>Explanation</b>	This message specifies the command name of a server extension.
<b>Action</b>	No action required.

<b>INOAAI0050</b>	<b>Collection Name : name</b>
<b>Explanation</b>	This message specifies the collection name of an XML document.
<b>Action</b>	No action required.
<b>INOAAI0051</b>	<b>Master database set to masterdb</b>
<b>Explanation</b>	The database named is the master database.
<b>Action</b>	No action required.
<b>INOAAI0063</b>	<b>Tamino will close the current log space extent and open a new one when the current log space block has been filled up</b>
<b>Explanation</b>	Tamino writes log information in blocks. When the currently used block has been filled up completely, Tamino will close the current log space extent and open a new one. As a consequence, you might encounter a minimal growth of the current log space before a new one is created.
<b>Action</b>	No action required.
<b>INOAAI0148</b>	<b>The name 'location_name' is not the name of an existing location; the default location is used instead</b>
<b>Explanation</b>	An invalid location name was specified or extracted from a backup. It could be a valid location on the host where the backup was created.
<b>Action</b>	No action required. The location defined as default in the location management will be used.
<b>INOAAI0152</b>	<b>No item selected for modification</b>
<b>Explanation</b>	No item was selected to be modified.
<b>Action</b>	Select an item and retry.
<b>INOAAI0160</b>	<b>Delete database space of database dbname</b>
<b>Explanation</b>	The database space with the highest extent is being deleted. The deletion will not proceed when the space is in use.
<b>Action</b>	No action required.

---

<b>INOAAI0161</b>	<b>Delete database space successfully finished</b>
<b>Explanation</b>	This message indicates that the "Delete database spaces" function completed successfully.
<b>Action</b>	No action required.
<b>INOAAI0163</b>	<b>Expand database space of database dbname</b>
<b>Explanation</b>	The last database space is being expanded.
<b>Action</b>	No action required.
<b>INOAAI0164</b>	<b>Expand database space successfully finished</b>
<b>Explanation</b>	This message indicates that the "Expand database spaces" function completed successfully.
<b>Action</b>	No action required.
<b>INOAAI0167</b>	<b>Deleting database space spaceNo from location Location</b>
<b>Explanation</b>	The specified database space is being deleted from the given location.
<b>Action</b>	No action required.
<b>INOAAI0168</b>	<b>Expanding database space spaceNo in location Location from oldsize MB to newsize MB</b>
<b>Explanation</b>	The specified database space is being expanded at the given location.
<b>Action</b>	No action required.
<b>INOAAI0176</b>	<b>Restoring of database dbName without further recovery successfully completed</b>
<b>Explanation</b>	The specified database has been restored successfully. Changes that occurred later than the backup time were not reapplied.
<b>Action</b>	No action required.
<b>INOAAI0211</b>	<b>Data load in collection collectionname</b>
<b>Explanation</b>	Data has been loaded into the named collection.
<b>Action</b>	No action required.

<b>INOAAI0227</b>	<b>Data unload from collection collectionname</b>
<b>Explanation</b>	Data will be unloaded into the named collection.
<b>Action</b>	No action required.
<b>INOAAI0237</b>	<b>mvcount spaces successfully moved from oldloc to newloc</b>
<b>Explanation</b>	The specified number of spaces were moved from one location to another one.
<b>Action</b>	Information message, no action required.
<b>INOAAI0248</b>	<b>Document path : path</b>
<b>Explanation</b>	This message specifies the path name of an XML document.
<b>Action</b>	No action required.
<b>INOAAI0249</b>	<b>Query string : text</b>
<b>Explanation</b>	This message specifies the query string to retrieve XML documents.
<b>Action</b>	No action required.
<b>INOAAI0250</b>	<b>Schema name : name</b>
<b>Explanation</b>	This message specifies the schema name of a XML Document.
<b>Action</b>	No action required.
<b>INOAAI0269</b>	<b>Execution of command 'name' successful</b>
<b>Explanation</b>	A server extension command was successfully executed.
<b>Action</b>	No action required.
<b>INOAAI0273</b>	<b>Location locCount : locName</b>
<b>Explanation</b>	This is an informational message for one default database location of the category.
<b>Action</b>	Information message, no action required.
<b>INOAAI0275</b>	<b>No pending alerts found</b>
<b>Explanation</b>	An attempt was made to confirm all pending alerts, but no job with pending alerts was found. Either there are no alerts in the display, or the alerts in the display have been confirmed meanwhile by someone else.
<b>Action</b>	No action required.

---

<b>INOAAI0276</b>	<b>When all pending alerts are confirmed, the "Pending Alerts" folder is cleared. Each individual job is still in the "Running Jobs" or in the "Completed Jobs" folder until it is deleted by automatic cleanup; up to that point, the warning, error and alert messages are still visible in the single job view.</b>
<b>Explanation</b>	No job or message is really removed when alerts are confirmed; they are just moved away from the Alerts folder.
<b>Action</b>	No action required
<b>INOAAI0277</b>	<b>When a job record is deleted, it is removed from the job log and its disk file is deleted. Jobs that are not completed (i.e. stopped or still running) and jobs that have unconfirmed alert messages are not deleted and remain in their respective folders.</b>
<b>Explanation</b>	Only finished jobs with no pending alerts are deleted.
<b>Action</b>	No action required
<b>INOAAI0280</b>	<b>Object Identification : text</b>
<b>Explanation</b>	The given text provides the object identification of the server extension.
<b>Action</b>	No action required.
<b>INOAAI0286</b>	<b>Execution type: type</b>
<b>Explanation</b>	The specified type is the selected server extension execution type.
<b>Action</b>	No action required.
<b>INOAAI0288</b>	<b>Backing up all server extensions for database 'name'</b>
<b>Explanation</b>	All server extensions in the specified database are being backed up.
<b>Action</b>	No action required.
<b>INOAAI0289</b>	<b>Backup of all server extensions successful</b>
<b>Explanation</b>	All server extensions have been backed up successfully.
<b>Action</b>	No action required.
<b>INOAAI0290</b>	<b>Restoring server extension for database 'name'</b>
<b>Explanation</b>	A server extension of the specified database is being restored.
<b>Action</b>	No action required.

<b>INOAAI0291</b>	<b>Restore of server extension 'name' successful</b>
<b>Explanation</b>	The specified server extension has been restored successfully.
<b>Action</b>	No action required.
<b>INOAAI0292</b>	<b>Restoring all server extensions for database 'name'</b>
<b>Explanation</b>	All server extensions of the specified database are being restored.
<b>Action</b>	No action required.
<b>INOAAI0293</b>	<b>Restore of all server extensions successful</b>
<b>Explanation</b>	All server extensions have been restored successfully.
<b>Action</b>	No action required.
<b>INOAAI0299</b>	<b>Storing binary file 'path'</b>
<b>Explanation</b>	A binary file is being stored in the database.
<b>Action</b>	No action required.
<b>INOAAI0300</b>	<b>Restoring binary file 'path'</b>
<b>Explanation</b>	A binary file is being restored from the database.
<b>Action</b>	No action required.
<b>INOAAI0301</b>	<b>Removing binary file 'path'</b>
<b>Explanation</b>	A binary file is being removed from the database.
<b>Action</b>	No action required.
<b>INOAAI0303</b>	<b>Command log switched mode buffers buffers</b>
<b>Explanation</b>	This is a result message for a batch command.
<b>Action</b>	No action required.
<b>INOAAI0308</b>	<b>Update of settings successful : name</b>
<b>Explanation</b>	The update of the given settings parameter value was successful.
<b>Action</b>	No action necessary.

---

<b>INOAAI0316</b>	<b>Backing up server extension for database 'name'</b>
<b>Explanation</b>	A server extension in the specified database is being backed up.
<b>Action</b>	No action required.
<b>INOAAI0317</b>	<b>Backup of server extension 'name' successful</b>
<b>Explanation</b>	The specified server extension has been backed up successfully.
<b>Action</b>	No action required.
<b>INOAAI0318</b>	<b>Deleting document : name</b>
<b>Explanation</b>	The XML document will be deleted.
<b>Action</b>	No action necessary.
<b>INOAAI0319</b>	<b>No mapped document : name</b>
<b>Explanation</b>	No XML document is mapped to the server extension.
<b>Action</b>	No action necessary.
<b>INOAAI0320</b>	<b>Trace server extensions in database 'name'</b>
<b>Explanation</b>	The server extension trace mode is changed in the specified database.
<b>Action</b>	No action required.
<b>INOAAI0321</b>	<b>Trace switched on successfully</b>
<b>Explanation</b>	The server extension trace is switched on.
<b>Action</b>	No action required.
<b>INOAAI0322</b>	<b>Trace switched off successfully</b>
<b>Explanation</b>	The server extension trace is switched off.
<b>Action</b>	No action required.
<b>INOAAI0323</b>	<b>Store server extensions in database 'name'</b>
<b>Explanation</b>	The storing of server extension files is changed to the specified database.
<b>Action</b>	No action required.

<b>INOAAI0324</b>	<b>Store server extension files switched on successfully</b>
<b>Explanation</b>	The storing of server extension files is switched on.
<b>Action</b>	No action required.
<b>INOAAI0325</b>	<b>Store server extension files switched off successfully</b>
<b>Explanation</b>	The storing of server extension files is switched off.
<b>Action</b>	No action required.
<b>INOAAI0326</b>	<b>Analyze object for a new server extension</b>
<b>Explanation</b>	The object for a new server extension will be analyzed.
<b>Action</b>	No action required.
<b>INOAAI0327</b>	<b>Object File : path</b>
<b>Explanation</b>	This specifies the object file for the new server extension.
<b>Action</b>	No action required.
<b>INOAAI0328</b>	<b>Analysis of new server extension object successful</b>
<b>Explanation</b>	The analysis of the object for the new server extension was successful.
<b>Action</b>	No action required.
<b>INOAAI0329</b>	<b>Remove server extension object</b>
<b>Explanation</b>	The object of a new server extension will be removed.
<b>Action</b>	No action required.
<b>INOAAI0330</b>	<b>Select function for a new server extension</b>
<b>Explanation</b>	The function for a new server extension will be selected.
<b>Action</b>	No action required.
<b>INOAAI0331</b>	<b>Select function for a new server extension successful</b>
<b>Explanation</b>	The function for a new server extension was successfully selected.
<b>Action</b>	No action required.

---

<b>INOAAI0332</b>	<b>Display trace state successful</b>
<b>Explanation</b>	The server extension trace state is displayed successfully.
<b>Action</b>	No action required.
<b>INOAAI0333</b>	<b>Create Database from Backup</b>
<b>Explanation</b>	Button Create Database from Backup
<b>Action</b>	none
<b>INOAAI0357</b>	<b>Access Control List 'name' created</b>
<b>Explanation</b>	A new access control list has been created. Details are generally provided in other messages.
<b>Action</b>	No action required.
<b>INOAAI0358</b>	<b>User group 'name' created</b>
<b>Explanation</b>	A new user group has been created.
<b>Action</b>	No action required.
<b>INOAAI0360</b>	<b>User 'name' created</b>
<b>Explanation</b>	A new user has been created. Details are generally provided in other messages.
<b>Action</b>	No action required.
<b>INOAAI0364</b>	<b>Access control list 'name' modified</b>
<b>Explanation</b>	The current ACL has been modified.
<b>Action</b>	No action required.
<b>INOAAI0365</b>	<b>User group 'name' modified</b>
<b>Explanation</b>	The user group has been modified.
<b>Action</b>	No action required.
<b>INOAAI0366</b>	<b>User 'name' modified</b>
<b>Explanation</b>	The user has been modified.
<b>Action</b>	No action required.

<b>INOAAI0368</b>	<b>Access control element 'name' added to the access control list</b>
<b>Explanation</b>	An ACE has been added successfully to an ACL.
<b>Action</b>	No action required.
<b>INOAAI0374</b>	<b>Access control list 'name' deleted</b>
<b>Explanation</b>	The access control list has been deleted.
<b>Action</b>	No action required.
<b>INOAAI0375</b>	<b>User 'name' deleted</b>
<b>Explanation</b>	The user has been deleted.
<b>Action</b>	No action required.
<b>INOAAI0376</b>	<b>User group 'name' deleted</b>
<b>Explanation</b>	The user group has been deleted.
<b>Action</b>	No action required.
<b>INOAAI0406</b>	<b>Shutdown of all active databases completed</b>
<b>Explanation</b>	All active databases are about to shut down, or they are already inactive.
<b>Action</b>	No action required.
<b>INOAAI0407</b>	<b>All autostart databases checked</b>
<b>Explanation</b>	All databases with autostart parameter set have been started.
<b>Action</b>	No action required.
<b>INOAAI0410</b>	<b>op of operation done</b>
<b>Explanation</b>	This message provides information about operation progress.
<b>Action</b>	No action required
<b>INOAAI0424</b>	<b>New value : text</b>
<b>Explanation</b>	This describes a new value for a Java public or private classpath.
<b>Action</b>	No action required.

---

<b>INOAAI0425</b>	<b>Starting autostart databases of version version</b>
<b>Explanation</b>	Databases with the autostart parameter set to 'yes' are being started.
<b>Action</b>	No action required.
<b>INOAAI0426</b>	<b>Stopping all active databases of version version</b>
<b>Explanation</b>	Active databases are being stopped
<b>Action</b>	No action required.
<b>INOAAI0429</b>	<b>Confirming all alerts</b>
<b>Explanation</b>	Fatal error, error and warning messages are being confirmed. Once all alerts are confirmed, a job will be scheduled for cleanup (will be removed later), or it can be delete explicitly as a single job or along with all completed jobs.
<b>Action</b>	No action required.
<b>INOAAI0431</b>	<b>Deleting all completed jobs</b>
<b>Explanation</b>	All jobs without unconfirmed alerts are being deleted.
<b>Action</b>	No action required.
<b>INOAAI0432</b>	<b>All job records of completed jobs successfully deleted by user (except jobs with pending alerts)</b>
<b>Explanation</b>	Deleted job records will not appear in the job monitor list any more; the corresponding files have been deleted on disk.
<b>Action</b>	No action required.
<b>INOAAI0445</b>	<b>Setting version for database 'dbName'</b>
<b>Explanation</b>	Set the version of a specific database.
<b>Action</b>	Data must be unloaded and loaded into a new database manually.
<b>INOAAI0446</b>	<b>No property has been modified. All properties already set to the given values.</b>
<b>Explanation</b>	A property will be changed when the new property value is different from the value stored in the internal configuration store.
<b>Action</b>	No action required.

<b>INOAAI0448</b>	<b>'param' has been changed from 'oldValue' to 'newValue'</b>
<b>Explanation</b>	A database property was changed successfully by the "modify property" command.
<b>Action</b>	No action required.
<b>INOAAI0451</b>	<b>Adding database space for database dbName</b>
<b>Explanation</b>	This message indicates the beginning of the execution of the "Add database spaces" function.
<b>Action</b>	No action required.
<b>INOAAI0452</b>	<b>Add database space successfully finished</b>
<b>Explanation</b>	This message indicates that the "Add database spaces" function completed successfully.
<b>Action</b>	No action required.
<b>INOAAI0454</b>	<b>Moving database space for database dbName</b>
<b>Explanation</b>	This message indicates the beginning of the execution of the "Move database spaces" function.
<b>Action</b>	No action required.
<b>INOAAI0455</b>	<b>Move database space successfully finished</b>
<b>Explanation</b>	This message indicates that the "Move database spaces" function completed successfully.
<b>Action</b>	No action required.
<b>INOAAI0457</b>	<b>Creating database dbName</b>
<b>Explanation</b>	This message indicates the beginning of the execution of the "Create Database" function.
<b>Action</b>	No action required.
<b>INOAAI0458</b>	<b>Create database successfully finished</b>
<b>Explanation</b>	This message indicates that the database was created successfully.
<b>Action</b>	No action required.

---

<b>INOAAI0460</b>	<b>Deleting database dbName</b>
<b>Explanation</b>	This message indicates the beginning of the execution of the "Delete Database" function.
<b>Action</b>	No action required.
<b>INOAAI0461</b>	<b>Database has been successfully deleted</b>
<b>Explanation</b>	This message indicates that the "Delete Database" function completed successfully.
<b>Action</b>	No action required.
<b>INOAAI0465</b>	<b>Start of database dbName successful</b>
<b>Explanation</b>	This message indicates that the specified database has been started successfully.
<b>Action</b>	No action required.
<b>INOAAI0467</b>	<b>Stop of database dbName successful</b>
<b>Explanation</b>	This message indicates that the specified database has been stopped successfully.
<b>Action</b>	No action required.
<b>INOAAI0468</b>	<b>Backup of database dbName</b>
<b>Explanation</b>	This message indicates that a backup of the specified database is being created.
<b>Action</b>	No action required.
<b>INOAAI0469</b>	<b>Restore database dbName using backup 'bckDate' with recovery</b>
<b>Explanation</b>	This message indicates the beginning of the execution of a database restore function with a database recovery based on the log spaces.
<b>Action</b>	No action required.
<b>INOAAI0470</b>	<b>Restore database dbName using backup 'bckDate' without recovery</b>
<b>Explanation</b>	This message indicates the beginning of the execution of a database restore function without a database recovery based on the log spaces.
<b>Action</b>	No action required.
<b>INOAAI0471</b>	<b>Backup of database dbName successfully completed</b>
<b>Explanation</b>	This message indicates that the specified database has been backed up successfully.
<b>Action</b>	No action required.

<b>INOAAI0476</b>	<b>Restoring and recovering of database dbName successfully completed</b>
<b>Explanation</b>	The specified database has been restored and recovered successfully.
<b>Action</b>	No action required.
<b>INOAAI0477</b>	<b>Moving database space spaceNo from location oldLoc to newLoc</b>
<b>Explanation</b>	A database space is being moved from one location to another.
<b>Action</b>	No action required.
<b>INOAAI0479</b>	<b>Adding size MB database space to location newLoc</b>
<b>Explanation</b>	The specified database space is being added to the given location.
<b>Action</b>	No action required.
<b>INOAAI0484</b>	<b>Uninstalling all server extensions in database 'name'</b>
<b>Explanation</b>	All server extensions in a database are being uninstalled from the specified database and the file system. If a restore is being performed the server extensions will be recovered from the backup database.
<b>Action</b>	No action required.
<b>INOAAI0490</b>	<b>Modify database properties successfully finished</b>
<b>Explanation</b>	Database properties have been modified successfully.
<b>Action</b>	No action required.
<b>INOAAI0492</b>	<b>Modify properties for database dbName</b>
<b>Explanation</b>	Database properties are being modified.
<b>Action</b>	No action required.
<b>INOAAI0493</b>	<b>Restore database dbName using backup 'bckDate' with partial recovery</b>
<b>Explanation</b>	A database restore function with partial recovery has been started.
<b>Action</b>	No action required.
<b>INOAAI0494</b>	<b>Checking and repairing database dbName</b>
<b>Explanation</b>	A function to check and repair the database has been started.
<b>Action</b>	No action required.

---

<b>INOAAI0495</b>	<b>Check and repair of database dbName finished successfully</b>
<b>Explanation</b>	The check and repair function was successfully applied to the specified database, i.e. the recreation of the indices was successful.
<b>Action</b>	No action required.
<b>INOAAI0497</b>	<b>help</b>
<b>Explanation</b>	This is a standard information message to show the server version in space and property commands.
<b>Action</b>	No action required.
<b>INOAAI0501</b>	<b>Uninstall of all server extensions successful</b>
<b>Explanation</b>	All server extensions in a database have been uninstalled successfully. This is an informational message.
<b>Action</b>	No action required.
<b>INOAAI0502</b>	<b>Registering Java class 'path'</b>
<b>Explanation</b>	The installation count for the Java class is added to the internal configuration. This is an informational message.
<b>Action</b>	No action required.
<b>INOAAI0505</b>	<b>Function name: 'name'</b>
<b>Explanation</b>	This is the name of a server extension function. This is an informational message.
<b>Action</b>	No action required.
<b>INOAAI0506</b>	<b>External name: 'name'</b>
<b>Explanation</b>	This is the external name of a server extension function. This is an informational message.
<b>Action</b>	No action required.
<b>INOAAI0511</b>	<b>Parameter 'para' not valid</b>
<b>Explanation</b>	The specified parameter is not valid for the current command.
<b>Action</b>	Check the spelling of the parameter. If the spelling is correct, check whether the parameter is valid in the current context.

<b>INOAAI0514</b>	<b>message</b>
<b>Explanation</b>	This is an informational message about a server extension document that has been returned from the Tamino server.
<b>Action</b>	No action required.
<b>INOAAI0515</b>	<b>Listing server extensions in database 'name'</b>
<b>Explanation</b>	A list of all installed server extensions for the specified database is being generated.
<b>Action</b>	No action required.
<b>INOAAI0516</b>	<b>Installing server extension in database 'name'</b>
<b>Explanation</b>	A new server extension is being installed in the specified database.
<b>Action</b>	No action required.
<b>INOAAI0517</b>	<b>Package file: path</b>
<b>Explanation</b>	The specified path is the pathname of the packed server extension file.
<b>Action</b>	No action required.
<b>INOAAI0518</b>	<b>Execution mode: mode</b>
<b>Explanation</b>	The specified mode is the selected server extension execution mode.
<b>Action</b>	No action required.
<b>INOAAI0519</b>	<b>Installation of server extension 'name' successful</b>
<b>Explanation</b>	The specified server extension was installed successfully.
<b>Action</b>	No action required.
<b>INOAAI0520</b>	<b>Uninstalling server extension from database 'name'</b>
<b>Explanation</b>	A server extension is being uninstalled from the specified database.
<b>Action</b>	No action required.
<b>INOAAI0521</b>	<b>Server extension name: 'name'</b>
<b>Explanation</b>	This message specifies the name of a server extension.
<b>Action</b>	No action required.

---

<b>INOAAI0522</b>	<b>Uninstall of server extension 'name' successful</b>
<b>Explanation</b>	The specified server extension has been uninstalled successfully.
<b>Action</b>	No action required.
<b>INOAAI0523</b>	<b>Modifying server extension in database 'name'</b>
<b>Explanation</b>	A server extension in the specified database is being modified.
<b>Action</b>	No action required.
<b>INOAAI0524</b>	<b>Modification of server extension 'name' successful</b>
<b>Explanation</b>	The specified server extension has been modified successfully.
<b>Action</b>	No action required.
<b>INOAAI0525</b>	<b>Deleting help URL 'path'</b>
<b>Explanation</b>	The specified help file for a server extension is being deleted.
<b>Action</b>	No action required.
<b>INOAAI0526</b>	<b>Executing command 'call'</b>
<b>Explanation</b>	The specified operating system command is being executed.
<b>Action</b>	No action required.
<b>INOAAI0527</b>	<b>De-registering server extension DLL 'path'</b>
<b>Explanation</b>	The specified server extension DLL file is being de-registered.
<b>Action</b>	No action required.
<b>INOAAI0528</b>	<b>Deleting server extension DLL 'path'</b>
<b>Explanation</b>	The specified server extension DLL file is being deleted.
<b>Action</b>	No action required.
<b>INOAAI0529</b>	<b>Deselect function of a new server extension</b>
<b>Explanation</b>	A selected function for a new server extension is being deselected. This is an informational message.
<b>Action</b>	No action required.

<b>INOAAI0530</b>	<b>Extracting entry 'name'</b>
<b>Explanation</b>	An entry is being extracted from a packed file.
<b>Action</b>	No action required.
<b>INOAAI0531</b>	<b>Inserting document 'path'</b>
<b>Explanation</b>	The URL of a help file for a server extension is being inserted into the server extension's installation document.
<b>Action</b>	No action required.
<b>INOAAI0532</b>	<b>Registering DLL 'path'</b>
<b>Explanation</b>	A server extension DLL file is being registered.
<b>Action</b>	No action required.
<b>INOAAI0533</b>	<b>DLL 'path' already registered</b>
<b>Explanation</b>	The specified server extension DLL file is already registered.
<b>Action</b>	No action required.
<b>INOAAI0535</b>	<b>Deleting file 'name'</b>
<b>Explanation</b>	The specified server extension installation file is being deleted.
<b>Action</b>	No action required.
<b>INOAAI0536</b>	<b>Deleting directory 'path'</b>
<b>Explanation</b>	The specified server extension installation directory is being deleted.
<b>Action</b>	No action required.
<b>INOAAI0537</b>	<b>Showing server extension attributes in database 'name'</b>
<b>Explanation</b>	The attributes of a server extension in the specified database are being listed.
<b>Action</b>	No action required.
<b>INOAAI0538</b>	<b>Setting access rights for server extension in database 'name'</b>
<b>Explanation</b>	The access rights of a server extension are being set in the specified database.
<b>Action</b>	No action required.

---

<b>INOAAI0543</b>	<b>Stopping database dbName in normal mode</b>
<b>Explanation</b>	This message indicates that the specified database is being stopped in normal mode.
<b>Action</b>	No action required.
<b>INOAAI0544</b>	<b>Stopping database dbName in abort mode</b>
<b>Explanation</b>	This message indicates that the specified database is being stopped in abort mode.
<b>Action</b>	No action required.
<b>INOAAI0545</b>	<b>Stopping database dbName in rollback mode</b>
<b>Explanation</b>	This message indicates that the specified database is being stopped in rollback mode.
<b>Action</b>	No action required.
<b>INOAAI0568</b>	<b>Unexpected messages received</b>
<b>Explanation</b>	This message is the header for subsequent messages.
<b>Action</b>	No action required.
<b>INOAAI0569</b>	<b>Edit details for a new server extension</b>
<b>Explanation</b>	Details for a new server extension will be edited.
<b>Action</b>	No action required.
<b>INOAAI0570</b>	<b>Description: text</b>
<b>Explanation</b>	This is a short description of the new server extension.
<b>Action</b>	No action required.
<b>INOAAI0571</b>	<b>Author name: name</b>
<b>Explanation</b>	This is the name of the new server extension author.
<b>Action</b>	No action required.
<b>INOAAI0572</b>	<b>Help file: name</b>
<b>Explanation</b>	This is the name of a help file for the new server extension.
<b>Action</b>	No action required.

<b>INOAAI0573</b>	<b>Editing of new server extension details successful</b>
<b>Explanation</b>	The editing of the new server extension details was successful.
<b>Action</b>	No action required.
<b>INOAAI0574</b>	<b>Starting database dbName</b>
<b>Explanation</b>	A Tamino database is being started.
<b>Action</b>	No action required.
<b>INOAAI0577</b>	<b>Unloading document 'path'</b>
<b>Explanation</b>	The server extension object information document is being unloaded.
<b>Action</b>	No action required.
<b>INOAAI0578</b>	<b>Edit details for a new server extension function</b>
<b>Explanation</b>	Details for a new server extension function will be edited.
<b>Action</b>	No action required.
<b>INOAAI0579</b>	<b>Function type: text</b>
<b>Explanation</b>	This message displays the type of a server extension function.
<b>Action</b>	No action required.
<b>INOAAI0580</b>	<b>Editing of new server extension function details successful</b>
<b>Explanation</b>	The editing of the new server extension function details was successful.
<b>Action</b>	No action required.
<b>INOAAI0581</b>	<b>Loading document 'path'</b>
<b>Explanation</b>	A server extension analyzer document is being loaded.
<b>Action</b>	No action required.
<b>INOAAI0582</b>	<b>Start Database</b>
<b>Explanation</b>	This is a command for the Tamino agent dbagent.
<b>Action</b>	No action required.

---

<b>INOAAI0583</b>	<b>Stop Database</b>
<b>Explanation</b>	This is a command for the Tamino agent dbagent.
<b>Action</b>	No action required.
<b>INOAAI0584</b>	<b>Delete Database</b>
<b>Explanation</b>	This is a command for the Tamino agent dbagent.
<b>Action</b>	No action required.
<b>INOAAI0587</b>	<b>Check and Repair</b>
<b>Explanation</b>	This is a command for the Tamino agent dbagent.
<b>Action</b>	No action required.
<b>INOAAI0589</b>	<b>Information</b>
<b>Explanation</b>	This is a command for the Tamino agent dbagent.
<b>Action</b>	No action required.
<b>INOAAI0591</b>	<b>Database Spaces</b>
<b>Explanation</b>	This is a command for the Tamino agent dbagent.
<b>Action</b>	No action required.
<b>INOAAI0592</b>	<b>Properties</b>
<b>Explanation</b>	This is a command for the Tamino agent dbagent.
<b>Action</b>	No action required.
<b>INOAAI0598</b>	<b>Register CD Database</b>
<b>Explanation</b>	This is a command button for the Tamino agent dblast.
<b>Action</b>	No action required.
<b>INOAAI0599</b>	<b>Prepare for CD</b>
<b>Explanation</b>	This is a command for the Tamino agent dblast.
<b>Action</b>	No action required.

<b>INOAAI0600</b>	<b>Unregister CD Database</b>
<b>Explanation</b>	This is a command button for the Tamino agent dbagent.
<b>Action</b>	No action required.
<b>INOAAI0601</b>	<b>Create a new server extension package</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.
<b>INOAAI0602</b>	<b>Package path: path</b>
<b>Explanation</b>	This is the pathname of the server extension package.
<b>Action</b>	No action required.
<b>INOAAI0603</b>	<b>Creation of package 'name' successful</b>
<b>Explanation</b>	A server extension package was created successfully.
<b>Action</b>	No action required.
<b>INOAAI0604</b>	<b>Port range successfully changed</b>
<b>Explanation</b>	The port range was successfully changed.
<b>Action</b>	none
<b>INOAAI0607</b>	<b>inodmp return erg</b>
<b>Explanation</b>	This message shows a return value of inodmp.
<b>Action</b>	No action required.
<b>INOAAI0612</b>	<b>Deselection of function 'name' successful</b>
<b>Explanation</b>	The server extension function was successfully deselected.
<b>Action</b>	No action required.
<b>INOAAI0613</b>	<b>Modify parameter of server extension function</b>
<b>Explanation</b>	The parameter name and XML type of a selected server extension function will be modified.
<b>Action</b>	Insert the corresponding values.

---

<b>INOAAI0614</b>	<b>Parameter name: name</b>
<b>Explanation</b>	This specifies the name of the parameter being modified.
<b>Action</b>	No action required.
<b>INOAAI0615</b>	<b>Modified name: name</b>
<b>Explanation</b>	This specifies the modified name of the parameter.
<b>Action</b>	No action required.
<b>INOAAI0616</b>	<b>XML type: type</b>
<b>Explanation</b>	This specifies the modified XML type of the parameter.
<b>Action</b>	No action required.
<b>INOAAI0617</b>	<b>Modification of parameter 'name' successful</b>
<b>Explanation</b>	A server extension function parameter was successfully modified.
<b>Action</b>	No action required.
<b>INOAAI0618</b>	<b>Preparation of CD database successful</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.
<b>INOAAI0625</b>	<b>Renaming database dbname to newdbname</b>
<b>Explanation</b>	The database is being renamed.
<b>Action</b>	No action required.
<b>INOAAI0626</b>	<b>Database successfully renamed</b>
<b>Explanation</b>	The database was renamed successfully.
<b>Action</b>	No action required.
<b>INOAAI0627</b>	<b>Server extension class 'name'</b>
<b>Explanation</b>	This message specifies the Java class name of a server extension.
<b>Action</b>	No action required.

<b>INOAAI0629</b>	<b>database successfully registered</b>
<b>Explanation</b>	A database has been successfully registered.
<b>Action</b>	No action required.
<b>INOAAI0630</b>	<b>Registering CD database dbname</b>
<b>Explanation</b>	The CD database is being registered.
<b>Action</b>	No action required.
<b>INOAAI0631</b>	<b>Location name at path successfully added</b>
<b>Explanation</b>	The location was successfully added.
<b>Action</b>	No action required.
<b>INOAAI0632</b>	<b>Location name successfully deleted</b>
<b>Explanation</b>	The location was successfully deleted.
<b>Action</b>	No action required.
<b>INOAAI0633</b>	<b>Location name successfully renamed to newname</b>
<b>Explanation</b>	The location was successfully renamed.
<b>Action</b>	No action required.
<b>INOAAI0634</b>	<b>Location name successfully set as default database location</b>
<b>Explanation</b>	The location was successfully set as the default database location.
<b>Action</b>	No action required.
<b>INOAAI0635</b>	<b>Location name successfully set as default backup database location</b>
<b>Explanation</b>	The location was successfully set as the default backup location.
<b>Action</b>	No action required.
<b>INOAAI0636</b>	<b>Default of database location category 'category' successfully modified</b>
<b>Explanation</b>	The default database location category was successfully modified.
<b>Action</b>	No action required.

---

<b>INOAAI0642</b>	<b>Stopping XML session</b>
<b>Explanation</b>	The XML session is being stopped.
<b>Action</b>	No action required.
<b>INOAAI0649</b>	<b>Setting global parameters for external backup method 'method' of database dbname</b>
<b>Explanation</b>	Global parameters for external backup method are being set.
<b>Action</b>	No action required, information message.
<b>INOAAI0650</b>	<b>Global parameters for external backup method 'method' of database dbname successfully set</b>
<b>Explanation</b>	The global parameters were successfully set.
<b>Action</b>	No action required, information message.
<b>INOAAI0652</b>	<b>Setting configuration parameters for external backup method 'method' of database dbname</b>
<b>Explanation</b>	The configuration parameters for the external backup method are being set.
<b>Action</b>	No action required, information message.
<b>INOAAI0654</b>	<b>Configuration parameters for external backup method 'method' of database dbname successfully set</b>
<b>Explanation</b>	The configuration parameters were successfully set.
<b>Action</b>	No action required, information message.
<b>INOAAI0655</b>	<b>Deleting configuration 'configuration' of method 'method' of database dbname</b>
<b>Explanation</b>	The "delete configuration" function was started.
<b>Action</b>	No action required, information message.
<b>INOAAI0657</b>	<b>Configuration 'configuration' of method 'method' of database dbname successfully deleted</b>
<b>Explanation</b>	The configuration parameters were successfully deleted.
<b>Action</b>	No action required, information message.

<b>INOAAI0661</b>	<b>Replication database name replication_db added into the permission list</b>
<b>Explanation</b>	This is a status report that the replication database name has been added into the permission list.
<b>Action</b>	No action required.
<b>INOAAI0663</b>	<b>Replication database name replication_db removed from the permission list</b>
<b>Explanation</b>	The replication database name has been removed from the permission list.
<b>Action</b>	No action required, this is an information message.
<b>INOAAI0664</b>	<b>Database database set to replication type</b>
<b>Explanation</b>	The database is set to the type "replication database".
<b>Action</b>	No action required, this is an information message.
<b>INOAAI0666</b>	<b>Replication database database has been reset to normal type</b>
<b>Explanation</b>	The replication database was reset so that it is a normal database.
<b>Action</b>	No action required, this is an information message.
<b>INOAAI0670</b>	<b>Private Classpath: path</b>
<b>Explanation</b>	The displayed path is the server extension private Java classpath.
<b>Action</b>	No action required.
<b>INOAAI0671</b>	<b>type Classpath: path</b>
<b>Explanation</b>	The specified operation type is performed with the server extension private Java classpath.
<b>Action</b>	No action required.
<b>INOAAI0673</b>	<b>Keep files from backup datetime</b>
<b>Explanation</b>	This indicates that the backup files will be saved.
<b>Action</b>	No action required, information message.
<b>INOAAI0674</b>	<b>Move backup space to "destination"</b>
<b>Explanation</b>	The backup space is being moved moved to new location.
<b>Action</b>	No action required, information message.

---

<b>INOAAI0682</b>	<b>Switching log space for database dbName</b>
<b>Explanation</b>	A switch of the log space is initiated.
<b>Action</b>	No action required.
<b>INOAAI0687</b>	<b>Nothing has changed: mode</b>
<b>Explanation</b>	The specified server extension attribute did not change.
<b>Action</b>	No action required.
<b>INOAAI0688</b>	<b>Attribute: mode</b>
<b>Explanation</b>	This specifies a new attribute of the parameter.
<b>Action</b>	No action required.
<b>INOAAI0689</b>	<b>Default value : text</b>
<b>Explanation</b>	This specifies the default value of the parameter.
<b>Action</b>	No action required.
<b>INOAAI0690</b>	<b>Adding backup method 'method' for database dbname</b>
<b>Explanation</b>	An external backup method of the database is being added.
<b>Action</b>	No action required, information message.
<b>INOAAI0692</b>	<b>Backup method 'method' successfully added for database dbname</b>
<b>Explanation</b>	The backup method has been successfully added.
<b>Action</b>	No action required, information message.
<b>INOAAI0693</b>	<b>Deleting method 'method' of database dbname</b>
<b>Explanation</b>	An external backup method of the database is being deleted.
<b>Action</b>	No action required, information message.
<b>INOAAI0695</b>	<b>Method 'method' of database dbname successfully deleted</b>
<b>Explanation</b>	The backup method has been successfully deleted.
<b>Action</b>	No action required, information message.

<b>INOAAI0697</b>	<b>Deleting backup 'bckDate' of database dbName</b>
<b>Explanation</b>	The backup of the database is being deleted.
<b>Action</b>	Information message, no action required.
<b>INOAAI0698</b>	<b>Deletion of backup 'bckDate' of database dbName successfully completed</b>
<b>Explanation</b>	The specified database backup has been deleted successfully.
<b>Action</b>	Information message, no action required.
<b>INOAAI0701</b>	<b>Remove permitted replication database name replicationdb from master database masterdb</b>
<b>Explanation</b>	This is a title for the messages for removing a database name from the permission list.
<b>Action</b>	No action required.
<b>INOAAI0702</b>	<b>Add permitted replication database name</b>
<b>Explanation</b>	This is a title for adding database name into the permission list.
<b>Action</b>	No action required.
<b>INOAAI0704</b>	<b>Set type to normal database</b>
<b>Explanation</b>	This is a title for setting the database type to a normal one.
<b>Action</b>	No action required.
<b>INOAAI0705</b>	<b>Create replication database list</b>
<b>Explanation</b>	This is a title for create replication database list.
<b>Action</b>	No action required.
<b>INOAAI0706</b>	<b>Retrieve replication database information</b>
<b>Explanation</b>	This is a title for retrieving the information of databases.
<b>Action</b>	No action required.
<b>INOAAI0711</b>	<b>Domain 'name' created</b>
<b>Explanation</b>	The domain has been created.
<b>Action</b>	No action required.

---

<b>INOAAI0713</b>	<b>Domain 'name' modified</b>
<b>Explanation</b>	The domain has been modified.
<b>Action</b>	No action required.
<b>INOAAI0715</b>	<b>Domain 'name' deleted</b>
<b>Explanation</b>	The domain has been deleted.
<b>Action</b>	No action required.
<b>INOAAI0718</b>	<b>Creating database dbName from backup dated timestamp</b>
<b>Explanation</b>	A new database is created with the content of a given backup. The log spaces belonging to the backup are not recovered.
<b>Action</b>	No action required.
<b>INOAAI0721</b>	<b>Web server assignments changed.</b>
<b>Explanation</b>	The web server assignments for this database have changed.
<b>Action</b>	No action required.
<b>INOAAI0722</b>	<b>Setting port ranges for Tamino databases</b>
<b>Explanation</b>	The static and dynamic port ranges are being set.
<b>Action</b>	No action required.
<b>INOAAI0726</b>	<b>Port ranges successfully changed</b>
<b>Explanation</b>	The port ranges were successfully changed.
<b>Action</b>	No action required.
<b>INOAAI0729</b>	<b>Renaming web server 'wbsname' to 'newwbsname'</b>
<b>Explanation</b>	The web server is being renamed.
<b>Action</b>	No action required.
<b>INOAAI0730</b>	<b>Web server successfully renamed</b>
<b>Explanation</b>	The web server was successfully renamed.
<b>Action</b>	No action required.

<b>INOAAI0732</b>	<b>Web server successfully added.</b>
<b>Explanation</b>	The web server was added successfully.
<b>Action</b>	No action required.
<b>INOAAI0734</b>	<b>Adding web server 'newwbsname'</b>
<b>Explanation</b>	The web server is being added.
<b>Action</b>	No action required.
<b>INOAAI0735</b>	<b>Deleting web server 'wbsname'</b>
<b>Explanation</b>	The web server is being deleted.
<b>Action</b>	No action required.
<b>INOAAI0736</b>	<b>Web server successfully deleted</b>
<b>Explanation</b>	The web server was deleted successfully.
<b>Action</b>	No action required.
<b>INOAAI0738</b>	<b>Modifying web server 'wbsname'. New IP address: 'ipaddress', new node: 'node', new port: 'port'.</b>
<b>Explanation</b>	The web server is being modified.
<b>Action</b>	No action required.
<b>INOAAI0739</b>	<b>Web server successfully modified</b>
<b>Explanation</b>	The web server was modified successfully.
<b>Action</b>	No action required.
<b>INOAAI0751</b>	<b>Preparing CD database dbname</b>
<b>Explanation</b>	A CD database is being prepared.
<b>Action</b>	No action required.
<b>INOAAI0770</b>	<b>Could not create database, cleaning up now</b>
<b>Explanation</b>	The "Create Database" or "Create Database From Backup" command has failed. Files, internal configuration store entries and XTS entries made during this process are deleted.
<b>Action</b>	No action required.

---

<b>INOAAI0771</b>	<b>Location location selected for initial backup</b>
<b>Explanation</b>	The initial backup could not be created in the first backup location specified. It has been created in the location indicated in the message text instead.
<b>Action</b>	No action required.
<b>INOAAI0781</b>	<b>The command requires an active database</b>
<b>Explanation</b>	An attempt was made to execute a command that requires an active database, but the the database is inactive.
<b>Action</b>	The database must be started before the command can be executed.
<b>INOAAI0782</b>	<b>The command requires an inactive database</b>
<b>Explanation</b>	An attempt was made to execute a command but the database is active and the command requires an inactive database.
<b>Action</b>	The database must be stopped before the command can be executed.
<b>INOAAI0789</b>	<b>Web server assignments changed. Please restart all databases which have this web server assigned to make your changes effective.</b>
<b>Explanation</b>	The web server assignments for this database have changed.
<b>Action</b>	Please restart all databases which have this web server assigned to make your changes effective.
<b>INOAAI0795</b>	<b>Set type to replication database with simultaneous query</b>
<b>Explanation</b>	The flag for simultaneous query for replication is set to 'enabled'.
<b>Action</b>	No action required.
<b>INOAAI0796</b>	<b>Set type to replication database without simultaneous query</b>
<b>Explanation</b>	The flag to allow simultaneous query for replication is disabled.
<b>Action</b>	No action required.
<b>INOAAI0821</b>	<b>Initialize raw section</b>
<b>Explanation</b>	This is an event log message while the raw section is being initialized.
<b>Action</b>	No action required.

<b>INOAAI0822</b>	<b>Raw section successfully initialized</b>
<b>Explanation</b>	The raw section has been successfully initialized.
<b>Action</b>	No action required.
<b>INOAAI0827</b>	<b>Set static min port min</b>
<b>Explanation</b>	The static minimum port is being set. All Tamino database static ports must be greater than or equal to this value.
<b>Action</b>	No action required.
<b>INOAAI0828</b>	<b>Set static max port max</b>
<b>Explanation</b>	The static maximum port is being set. All Tamino database static ports must be lower than or equal to this value.
<b>Action</b>	No action required.
<b>INOAAI0829</b>	<b>Set dynamic min port dmin</b>
<b>Explanation</b>	The dynamic minimum port is being set. Tamino databases use the port range for dynamically allocated ports. This port range should not be used by any other software.
<b>Action</b>	No action required.
<b>INOAAI0830</b>	<b>Set dynamic max port dmax</b>
<b>Explanation</b>	The dynamic maximum port is being set. Tamino databases use the port range for dynamically allocated ports. This port range should not be used by any other software.
<b>Action</b>	No action required.
<b>INOAAI0840</b>	<b>Function func is used in collection coll, schema schm, doc type doc</b>
<b>Explanation</b>	The server extension to be uninstalled contains a function that is still used in the given context.
<b>Action</b>	Typically no action is required but be aware that in the case of a forced uninstall the corresponding functions cannot be executed any longer.
<b>INOAAI0848</b>	<b>Restart parameter ignored, because only dynamic properties changed</b>
<b>Explanation</b>	A restart parameter was given, but a restart is only useful if a static property is changed.
<b>Action</b>	No action required.

<b>INOAAI0865</b>	<b>Moving database space spaceNo of database dbname from oldLoc to newLoc</b>
<b>Explanation</b>	The database space of the named database is being moved from one location to another location.
<b>Action</b>	No action required.
<b>INOAAI0866</b>	<b>Stop current request(s)</b>
<b>Explanation</b>	Stop a current running request.
<b>Action</b>	No action required.
<b>INOAAI0867</b>	<b>Request requestid successfully stopped</b>
<b>Explanation</b>	A request has been successfully stopped.
<b>Action</b>	No action required.
<b>INOAAI0869</b>	<b>No current active requests found</b>
<b>Explanation</b>	No requests are running on the XML Server.
<b>Action</b>	No action required.
<b>INOAAW0071</b>	<b>Higher server extension versions exist : name</b>
<b>Explanation</b>	In other databases, higher versions of this server extension exist.
<b>Action</b>	Back up the server extension.
<b>INOAAW0150</b>	<b>Backup spaces are copied because one or more spaces could still be part of an existing backup generation</b>
<b>Explanation</b>	To protect integrity of backup generations, spaces with the Tamino backup filename extension "1B0" are always copied because they could be part of a backup generation on the local host, or another remote host.
<b>Action</b>	Make sure that the selected backup spaces are not used in a backup generation by a local database or elsewhere, and then change their filename extension to something different from "1B0".
<b>INOAAW0166</b>	<b>Parameter 'para' unknown</b>
<b>Explanation</b>	The specified database parameter name is not known by the Tamino server.
<b>Action</b>	Check the spelling of the parameter. If the spelling is correct, check whether the parameter is valid in the current context.

**INOAAW0206**      **Required spacetype size could not be obtained from the backup, using minimum sizes where not specified otherwise**

**Explanation**      Minimum sizes will be used if not specified otherwise but the new database might refuse to start with these settings.

**Action**      Specify the effective spaces of the saved database if creating with the minimum sizes does not succeed.

**INOAAW0271**      **Cannot move space of database database, because the database is online**

**Explanation**      The database of the database space to move is in an active state.

**Action**      Stop the database.

**INOAAW0411**      **Show progress aborted**

**Explanation**      The progress information process is aborted because no more progress is determined, but operation is not finished.

**Action**      No action required.

**INOAAW0422**      **An error has occurred when user user attempted to remove the records of all completed jobs without pending alerts from the joblog**

**Explanation**      One or more job records may remain in the given job log after the attempt to delete all due records.

**Action**      Check if the service is running. If the problem persists, job records can be deleted "physically" by deleting the files with the extensions "OG0" and "OF0" in the directory where job records are stored (try the "log" directory in the Tamino or System Management Hub root directory) and restarting the service. This however will also delete records with pending alerts and records of active commands and should only be done as a last resort.

**INOAAW0433**      **File 'path' not deleted**

**Explanation**      The server extension file could not be deleted.

**Action**      No action necessary.

**INOAAW0434**      **File 'path' not found**

**Explanation**      The specified file could not be found.

**Action**      No action necessary.

---

<b>INOAAW0435</b>	<b>Directory 'path' not deleted</b>
<b>Explanation</b>	The directory is in use. Therefore it cannot be deleted.
<b>Action</b>	Wait until the directory is not in use, then retry the operation.
<b>INOAAW0436</b>	<b>Directory 'path' not found</b>
<b>Explanation</b>	The specified directory was not found.
<b>Action</b>	Check the permissions of your file system.
<b>INOAAW0440</b>	<b>Automatic assign of ports for the database failed, please assign the ports manually</b>
<b>Explanation</b>	The database is not usable until the ports are assigned manually.
<b>Action</b>	Assign the ports for the database manually.
<b>INOAAW0640</b>	<b>After restarting the Tamino server the server extension will be updated correctly</b>
<b>Explanation</b>	The Tamino server crashed. The server extension will be usable after restart.
<b>Action</b>	Restart the Tamino server to use this server extension .
<b>INOAAW0676</b>	<b>Please store the tape(s) from backup datetime in a safe place!</b>
<b>Explanation</b>	Tapes cannot be saved, the user must store them in a safe place.
<b>Action</b>	Keep the backup in a safe place.
<b>INOAAW0677</b>	<b>Please store the files from external backup datetime in a safe place!</b>
<b>Explanation</b>	External backups cannot be saved, the user must store them in a safe place.
<b>Action</b>	Keep the external backup in a safe place.
<b>INOAAW0700</b>	<b>Updating existing server extension 'name'</b>
<b>Explanation</b>	A previous version of the server extension is already installed in the database and will be updated.
<b>Action</b>	No action required.
<b>INOAAW0800</b>	<b>Disabling autostart for database dbName</b>
<b>Explanation</b>	The parameter "autostart" of the database has been set to "false".
<b>Action</b>	No action required.

<b>INOAAW0804</b>	<b>No property changed, property name and value is missing</b>
<b>Explanation</b>	There is no property name in the command.
<b>Action</b>	Supply the name of the property and the new value (propertyname=value) at the end of the batch command.
<b>INOAAW0815</b>	<b>Parameter 'name' is ignored for server extensions with execution type 'type'</b>
<b>Explanation</b>	The parameter cannot be used for server extensions of the given execution type.
<b>Action</b>	No action required.
<b>INOAAW0833</b>	<b>Force ignore replication database master status is set.</b>
<b>Explanation</b>	Normally it is not allowed to delete a replication database master, so force ignore replication master status is set. The database will be removed.
<b>Action</b>	No action required.
<b>INOAAW0839</b>	<b>Server extension name is used in schema</b>
<b>Explanation</b>	In some node of a schema a function of the server extension name is used.
<b>Action</b>	See the following messages for detailed information.
<b>INOAAW0851</b>	<b>No backups with user data found, please don't use option "Keep Backups"</b>
<b>Explanation</b>	No backups with user data found, please don't use option "Keep Backups".
<b>Action</b>	Do not use the option "Keep Backups".
<b>INOAAW0853</b>	<b>This command is deprecated. Please use the new command "inoload".</b>
<b>Explanation</b>	This command is set to the deprecated state and will be disabled in the next version
<b>Action</b>	Use the new command inoload instead of this command.
<b>INOAAW0854</b>	<b>COM server extension registration/deregistration suppressed</b>
<b>Explanation</b>	When packaging the COM server extension, the option to suppress the registration/deregistration commands has been used.
<b>Action</b>	It is the installer's responsibility to make sure the COM objects are correctly registered/deregistered using the methods provided by the underlying infrastructure.

---

<b>INOAAW0871</b>	<b>Can't connect to XTS directory server rc = xtsrc</b>
<b>Explanation</b>	Can't connect to XTS directory server. This server is necessary for Tamino databases.
<b>Action</b>	Check the XTS directory server.
<b>INOCVE8065</b>	<b>Collection collection contains non-migrated indexes</b>
<b>Explanation</b>	The upgrade was rejected because there are non-migrated indexes in Tamino 4.1.4.
<b>Action</b>	Please migrate the indexes. Refer to the migration documentation for details.
<b>INOCVE8067</b>	<b>Collection collection contains doctypes that are not namespace clean</b>
<b>Explanation</b>	The upgrade was rejected because at least one doctype in the database is not namespace clean.
<b>Action</b>	Please perform a namespace cleanup. Refer to the migration documentation for details.
<b>INOCVE8069</b>	<b>Conversion of data mapping to version version has failed with response response</b>
<b>Explanation</b>	An error occurred during the conversion of data mapping for standard index and collations.
<b>Action</b>	Please contact your software supplier.
<b>INOCVE8070</b>	<b>number TSD2 user collections exist</b>
<b>Explanation</b>	TSD2 user collections exist and must be migrated to TSD3.
<b>Action</b>	Please use the migration tool to migrate the TSD2 user collections.
<b>INOCVE8071</b>	<b>The count of existing user collections has failed with response response</b>
<b>Explanation</b>	The query to count existing user collections has failed.
<b>Action</b>	Please contact your software supplier.
<b>INOCVE8073</b>	<b>number installed COM server extensions found, conversion not allowed</b>
<b>Explanation</b>	It is not possible to convert a Tamino database to this version as COM server extensions are installed.
<b>Action</b>	Contact your software supplier for help with switching versions.

<b>INOCVE8074</b>	<b>Counting existing COM server extensions has failed with response response</b>
<b>Explanation</b>	The query to count existing COM server extensions has failed.
<b>Action</b>	Contact your software supplier for help with switching versions.
<b>INOCVE8075</b>	<b>Request to create indexes for doctype doctype in collection collection is pending</b>
<b>Explanation</b>	A request to create indexes is pending.
<b>Action</b>	Please correct the current status using the admin-command ino:repairIndex with option CONTINUE or DROP.
<b>INOCVE8077</b>	<b>The schema check for existing user collections has failed</b>
<b>Explanation</b>	The test define of existing user collection during "set version" has failed.
<b>Action</b>	Please contact your software supplier.
<b>INOCVE8078</b>	<b>The check for server extension installation has failed</b>
<b>Explanation</b>	The query to check whether a server extension is installed has failed.
<b>Action</b>	Please contact your software supplier.
<b>INOCVW8066</b>	<b>Schema "schema" in collection "collection" contains unknown attributes</b>
<b>Explanation</b>	The given schema in the given collection contains unknown attributes.
<b>Action</b>	Remove additional attributes before next schema update.
<b>INOCVW8076</b>	<b>The schema check for schema schema in collection collection has failed with response response</b>
<b>Explanation</b>	The test of defining all existing user collections during "set version" has failed.
<b>Action</b>	Please check the schema using the following admin-command ino:CheckSchema(collection-name, schema-name). Correct the schema and update it in Tamino.
<b>INODCE6507</b>	<b>Parameter structure mismatch</b>
<b>Explanation</b>	A parameter structure mismatch was detected.
<b>Action</b>	Please check and correct the given parameters and try again.

---

<b>INODCE6508</b>	<b>Not enough memory to create communication area</b>
<b>Explanation</b>	There was not enough memory to create the communication area.
<b>Action</b>	Please free some memory and try again.
<b>INODCE6509</b>	<b>Fatal error - unload aborted</b>
<b>Explanation</b>	A fatal error was detected and the unload was aborted.
<b>Action</b>	Please check for other error messages to obtain the cause of the abort.
<b>INODCE6510</b>	<b>Specify either the '-database' or the '-server' parameter, but do not specify both parameters together</b>
<b>Explanation</b>	Please specify either the '-database' or the '-server' parameter, but do not specify both parameters together.
<b>Action</b>	Please do not specify both parameters together.
<b>INODCE6511</b>	<b>Processing failed - cannot get server version</b>
<b>Explanation</b>	The processing failed because it was not possible to get the server version.
<b>Action</b>	Please check that you are using a version of the data loader client which is compatible with the server.
<b>INODCE6512</b>	<b>Path and/or file name too long</b>
<b>Explanation</b>	The path and/or file name is too long.
<b>Action</b>	Please change the file name and try again.
<b>INODCE6514</b>	<b>Cannot open log file 'file'</b>
<b>Explanation</b>	It was not possible to open the log file.
<b>Action</b>	Please make sure the log file can be written and try again.
<b>INODCE6515</b>	<b>Processing failed - corrupted response from server</b>
<b>Explanation</b>	Processing failed because a corrupted response was received from the server.
<b>Action</b>	Please contact your software supplier.

<b>INODCE6517</b>	<b>Server does not support mass loading of data</b>
<b>Explanation</b>	The server does not support mass loading of data.
<b>Action</b>	No action required.
<b>INODCE6518</b>	<b>Cannot retrieve information for input file 'file'</b>
<b>Explanation</b>	It was not possible to retrieve information for the input file.
<b>Action</b>	Please make sure the input file can be read and try again.
<b>INODCE6519</b>	<b>Cannot process an empty input file 'file'</b>
<b>Explanation</b>	It is not possible to process the input file because it is empty.
<b>Action</b>	Please make sure you specify the correct input file and try again.
<b>INODCE6520</b>	<b>Cannot open input file 'file'</b>
<b>Explanation</b>	It was not possible to open the input file.
<b>Action</b>	Please make sure the input file can be read and try again.
<b>INODCE6521</b>	<b>WSAStartup failed</b>
<b>Explanation</b>	WSAStartup failed.
<b>Action</b>	Please check the network configuration.
<b>INODCE6522</b>	<b>Winsock version mismatch</b>
<b>Explanation</b>	A Winsock version mismatch was detected.
<b>Action</b>	Please check the network configuration.
<b>INODCE6523</b>	<b>Not enough memory to create client host name</b>
<b>Explanation</b>	There was not enough memory to create client host name.
<b>Action</b>	Please free some memory and try again.
<b>INODCE6524</b>	<b>Invalid cursor handle delivered</b>
<b>Explanation</b>	An invalid cursor handle was delivered.
<b>Action</b>	Please contact your software supplier.

---

<b>INODCE6525</b>	<b>No cursor handle delivered</b>
<b>Explanation</b>	No cursor handle was delivered.
<b>Action</b>	Please contact your software supplier.
<b>INODCE6526</b>	<b>Not enough memory to create query object</b>
<b>Explanation</b>	There was not enough memory to create the query object.
<b>Action</b>	Please free some memory and try again.
<b>INODCE6527</b>	<b>Not enough memory to create query name buffer</b>
<b>Explanation</b>	There was not enough memory to create the query name buffer.
<b>Action</b>	Please free some memory and try again.
<b>INODCE6528</b>	<b>Cannot open output file 'file'</b>
<b>Explanation</b>	It was not possible to open the named output file.
<b>Action</b>	Please make sure the output file can be written and try again.
<b>INODCE6529</b>	<b>Invalid output format</b>
<b>Explanation</b>	An invalid output format was detected.
<b>Action</b>	Please contact your software supplier.
<b>INODCE6530</b>	<b>Cannot unload non-XML documents into a single file</b>
<b>Explanation</b>	It is not possible to unload non-XML documents into a single file.
<b>Action</b>	Please make sure you specified a valid output location for non-XML documents and try again.
<b>INODCE6531</b>	<b>Unload to a single file is not allowed</b>
<b>Explanation</b>	An unload to a single file is not allowed.
<b>Action</b>	Please make sure you specified a valid output location and try again.
<b>INODCE6532</b>	<b>Unload to a directory is not allowed</b>
<b>Explanation</b>	An unload to a directory is not allowed.
<b>Action</b>	Please make sure you specified a valid output location and try again.

<b>INODCE6534</b>	<b>Cannot read input file - I/O error code</b>
<b>Explanation</b>	The input file could not be read due to an I/O error.
<b>Action</b>	Please make sure the input file can be read and try again.
<b>INODCE6536</b>	<b>Not enough memory to create save area</b>
<b>Explanation</b>	There was not enough memory to create the save area.
<b>Action</b>	Please free some memory and try again.
<b>INODCE6538</b>	<b>Cannot initialize multi thread context</b>
<b>Explanation</b>	It was not possible to initialize a multi thread context.
<b>Action</b>	Please contact your software supplier.
<b>INODCE6539</b>	<b>Not enough memory to create request</b>
<b>Explanation</b>	The was not enough memory to create a request.
<b>Action</b>	Please free some memory and try again.
<b>INODCE6543</b>	<b>Not enough memory to create file offset area</b>
<b>Explanation</b>	There was not enough memory to create the file offset area.
<b>Action</b>	Please free some memory and try again.
<b>INODCE6544</b>	<b>Processing failed - no response from server</b>
<b>Explanation</b>	The processing failed because there was no response from the server.
<b>Action</b>	Please contact your software supplier.
<b>INODCE6545</b>	<b>Received empty answer from Tamino server</b>
<b>Explanation</b>	An empty reply was received from the Tamino server.
<b>Action</b>	Please contact your software supplier.
<b>INODCE6547</b>	<b>Invalid function code detected</b>
<b>Explanation</b>	An invalid function code was detected.
<b>Action</b>	Please enter either "load", "unload" or "define" for the parameter "-function"

---

<b>INODCE6548</b>	<b>Parameter 'parm' is only available with function code 'func'</b>
<b>Explanation</b>	The given parameter is only available with the given function code.
<b>Action</b>	Please correct your input and try again.
<b>INODCE6549</b>	<b>Argument for parameter 'arg' missing</b>
<b>Explanation</b>	An argument for the given parameter is missing.
<b>Action</b>	Please correct your input and try again.
<b>INODCE6550</b>	<b>Query filter must be enclosed in brackets: [...]</b>
<b>Explanation</b>	A query filter must be enclosed in brackets: [...].
<b>Action</b>	Please correct your input and try again.
<b>INODCE6551</b>	<b>Please specify the parameter 'parm' only once</b>
<b>Explanation</b>	The given parameter was specified more than once. Please specify the parameter only once.
<b>Action</b>	Please correct your input and try again.
<b>INODCE6552</b>	<b>Doctype is required</b>
<b>Explanation</b>	A doctype is required.
<b>Action</b>	Please correct your input and try again.
<b>INODCE6553</b>	<b>Server name is required</b>
<b>Explanation</b>	The server name is required.
<b>Action</b>	Please correct your input and try again.
<b>INODCE6554</b>	<b>Port number is required</b>
<b>Explanation</b>	A port number is required.
<b>Action</b>	Please correct your input and try again.
<b>INODCE6555</b>	<b>Parameter 'p1' not allowed in conjunction with parameter 'p2'</b>
<b>Explanation</b>	The first parameter cannot be used together with the second parameter.
<b>Action</b>	Please correct your input and try again.

<b>INODCE6556</b>	<b>Memory allocation failed during parsing</b>
<b>Explanation</b>	Memory allocation failed during the parsing phase.
<b>Action</b>	Please free some memory and try again.
<b>INODCE6557</b>	<b>Invalid hexBinary parameter detected</b>
<b>Explanation</b>	An invalid hexBinary parameter was detected.
<b>Action</b>	Please correct your input and try again.
<b>INODCE6558</b>	<b>Invalid parameter detected: 'parm'</b>
<b>Explanation</b>	An invalid parameter was detected.
<b>Action</b>	Please correct your input and try again.
<b>INODCE6559</b>	<b>Invalid argument for parameter -outputformat detected</b>
<b>Explanation</b>	An invalid argument for parameter -outputformat was detected.
<b>Action</b>	Please enter either "singlefile" or "multifiles".
<b>INODCE6560</b>	<b>Invalid argument for parameter -docname detected</b>
<b>Explanation</b>	An invalid argument for parameter -docname was detected.
<b>Action</b>	Please enter either "no", "full", "name" or "nameext".
<b>INODCE6561</b>	<b>Specify both '-sessionid' and '-sessionkey' or neither</b>
<b>Explanation</b>	You must specify either both '-sessionid' and '-sessionkey' or neither.
<b>Action</b>	Please correct your input and try again.
<b>INODCE6562</b>	<b>Mandatory parameter '-server' or '-database' missing</b>
<b>Explanation</b>	The mandatory parameter '-server' or '-database' is missing.
<b>Action</b>	Please correct your input and try again.
<b>INODCE6563</b>	<b>Mandatory parameter '-collection' missing</b>
<b>Explanation</b>	The mandatory parameter '-collection' is missing.
<b>Action</b>	Please correct your input and try again.

---

<b>INODCE6566</b>	<b>msg</b>
<b>Explanation</b>	This is a general placeholder for a message text.
<b>Action</b>	See the text of the message in the job log for more details.
<b>INODCE6567</b>	<b>Cannot open rejects file 'file'</b>
<b>Explanation</b>	The rejects file could not be opened.
<b>Action</b>	Please make sure the rejects file can be opened and try again.
<b>INODCE6568</b>	<b>Cannot write rejects file 'file'</b>
<b>Explanation</b>	It was not possible to write to the rejects file.
<b>Action</b>	Please make sure the rejects file can be written and try again.
<b>INODCE6570</b>	<b>Access to Tamino Server denied</b>
<b>Explanation</b>	Because of security definitions access to the Tamino server is denied.
<b>Action</b>	Please check your security definitions and try again.
<b>INODCE6575</b>	<b>Cannot write to output file - I/O error code</b>
<b>Explanation</b>	The output file could not be written due to an I/O error.
<b>Action</b>	Please make sure the output file can be written and try again.
<b>INODCE6578</b>	<b>Tamino Data Loader finished with errors</b>
<b>Explanation</b>	The Tamino Data Loader has finished its processing with some error messages.
<b>Action</b>	Check the log output, correct errors and try again.
<b>INODCE6579</b>	<b>libxni provided data buffer of bsize bytes, minimum of nsize bytes needed</b>
<b>Explanation</b>	Internal error in massload utility detected.
<b>Action</b>	Please contact your software supplier.
<b>INODCE6580</b>	<b>Memory allocation failed while loading data</b>
<b>Explanation</b>	An out of memory condition occurred.
<b>Action</b>	Restart the command when virtual memory is available.

<b>INODCE6581</b>	<b>Invalid media type specified for input file 'file'</b>
<b>Explanation</b>	An invalid media type was specified. You can load only documents of media type xml to a xml doctype.
<b>Action</b>	Please specify a legal xml media type and try again.
<b>INODCE6582</b>	<b>Error reading from input file 'file' while writing reject file</b>
<b>Explanation</b>	A file read error occurred while backing up rejected data.
<b>Action</b>	Check the file storage or contact your software supplier.
<b>INODCE6583</b>	<b>Cannot contact Tamino Server - HTTP status code code received</b>
<b>Explanation</b>	Cannot contact Tamino Server - HTTP status code received.
<b>Action</b>	Please contact your system administrator.
<b>INODCE6584</b>	<b>The operation was canceled by the user</b>
<b>Explanation</b>	The operation was canceled by the user.
<b>Action</b>	No action required.
<b>INODCE6585</b>	<b>Invalid argument for parameter -streaming detected</b>
<b>Explanation</b>	An invalid argument for parameter -streaming was detected.
<b>Action</b>	Please enter either "on" or "off".
<b>INODCE6590</b>	<b>Server does not support mass deleting of data</b>
<b>Explanation</b>	The server does not support mass deleting of data.
<b>Action</b>	No action required.
<b>INODCE6592</b>	<b>Disconnect from server failed due to a serious communication error</b>
<b>Explanation</b>	Disconnect from server failed due to a serious communication error.
<b>Action</b>	Please check your network settings.
<b>INODCI6500</b>	<b>Tamino Data Loader vvers - (c) Copyright Software AG 2002-year. All rights reserved.</b>
<b>Explanation</b>	This is the Tamino Data Loader start message.
<b>Action</b>	No action required.

---

<b>INODCI6501</b>	<b>Loading documents to database 'db', collection 'coll', doctype 'doctype'</b>
<b>Explanation</b>	Documents are being loaded into the database.
<b>Action</b>	No action required.
<b>INODCI6502</b>	<b>Loading documents to database on 'server:port', collection 'coll', doctype 'doctype'</b>
<b>Explanation</b>	Documents are being loaded into the database.
<b>Action</b>	No action required.
<b>INODCI6503</b>	<b>Unloading documents from database 'db', collection 'coll', doctype 'doctype'</b>
<b>Explanation</b>	Documents are being unloaded from database.
<b>Action</b>	No action required.
<b>INODCI6504</b>	<b>Unloading documents from database on 'server:port', collection 'coll', doctype 'doctype'</b>
<b>Explanation</b>	Documents are being unloaded from the database.
<b>Action</b>	No action required.
<b>INODCI6505</b>	<b>Defining schemas to database 'db'</b>
<b>Explanation</b>	Schemas are being defined in the database.
<b>Action</b>	No action required.
<b>INODCI6506</b>	<b>Defining schemas to database on 'server:port'</b>
<b>Explanation</b>	Schemas are being defined in the database.
<b>Action</b>	No action required.
<b>INODCI6513</b>	<b>Unloading file 'file'</b>
<b>Explanation</b>	The given file is being unloaded.
<b>Action</b>	No action required.
<b>INODCI6516</b>	<b>Loading file 'file'</b>
<b>Explanation</b>	The given file is being loaded.
<b>Action</b>	No action required.

<b>INODCI6533</b>	<b>No matching documents found</b>
<b>Explanation</b>	The query you specified returned no results.
<b>Action</b>	Please specify another query and try again.
<b>INODCI6535</b>	<b>start MB of end MB loaded</b>
<b>Explanation</b>	This shows the progress information.
<b>Action</b>	No action required.
<b>INODCI6537</b>	<b>Loading document id</b>
<b>Explanation</b>	The given document is being loaded.
<b>Action</b>	No action required.
<b>INODCI6540</b>	<b>Unloading documents start to end</b>
<b>Explanation</b>	The documents in the range from "start" to "end" are being unloaded.
<b>Action</b>	No action required.
<b>INODCI6541</b>	<b>Data unloading completed, number of documents processed: num</b>
<b>Explanation</b>	The unload of the data has completed.
<b>Action</b>	No action required.
<b>INODCI6542</b>	<b>Committing loaded documents - this may take a while</b>
<b>Explanation</b>	The loaded documents are being committed. This activity can last a while.
<b>Action</b>	No action required.
<b>INODCI6546</b>	<b>Elapsed time: elapse second(s), data processed: amount</b>
<b>Explanation</b>	The elapsed time and the amount of data processed are shown here.
<b>Action</b>	No action required.
<b>INODCI6564</b>	<b>msg</b>
<b>Explanation</b>	This is a general placeholder for a message text.
<b>Action</b>	See the text of the message in the job log for more details.

---

<b>INODCI6565</b>	<b>Data loading completed, number of documents processed docsproc, loaded docsload, rejected docsrejected</b>
<b>Explanation</b>	The data processing has completed with the given number of loaded and rejected documents.
<b>Action</b>	No action required.
<b>INODCI6569</b>	<b>Process id: id</b>
<b>Explanation</b>	The process has the given ID.
<b>Action</b>	No action required.
<b>INODCI6571</b>	<b>Unloading schemas from database 'db', collection 'coll'</b>
<b>Explanation</b>	Schemas are being unloaded from the database.
<b>Action</b>	No action required.
<b>INODCI6572</b>	<b>Unloading schemas from database on 'server:port', collection 'coll'</b>
<b>Explanation</b>	Schemas are being unloaded from the given collection of the database on the given server and port.
<b>Action</b>	No action required.
<b>INODCI6573</b>	<b>Unloading schemas start to end</b>
<b>Explanation</b>	Schemas in the range from "start" to "end" are being unloaded.
<b>Action</b>	No action required.
<b>INODCI6574</b>	<b>Data unloading completed, number of schema files written: num</b>
<b>Explanation</b>	The unloading of data has completed.
<b>Action</b>	No action required.
<b>INODCI6576</b>	<b>Tamino Data Loader successfully finished</b>
<b>Explanation</b>	The Tamino Data Loader has successfully completed its processing.
<b>Action</b>	No action required.

<b>INODCI6586</b>	<b>Undefining schemas from database 'db'</b>
<b>Explanation</b>	Schemas are being undefined from the database.
<b>Action</b>	No action required.
<b>INODCI6587</b>	<b>Undefining schemas from database on 'server:port'</b>
<b>Explanation</b>	Schemas are being undefined from the database.
<b>Action</b>	No action required.
<b>INODCI6588</b>	<b>Deleting documents from database 'db', collection 'coll', doctype 'doctype'</b>
<b>Explanation</b>	Documents are being deleted from database.
<b>Action</b>	No action required.
<b>INODCI6589</b>	<b>Deleting documents from database on 'server:port', collection 'coll', doctype 'doctype'</b>
<b>Explanation</b>	Documents are being deleted from the database.
<b>Action</b>	No action required.
<b>INODCI6591</b>	<b>Data deleting completed, docsdel documents deleted</b>
<b>Explanation</b>	The data deleting has completed with the given number of deleted documents.
<b>Action</b>	No action required.
<b>INODCW6577</b>	<b>Tamino Data Loader finished with warnings</b>
<b>Explanation</b>	The Tamino Data Loader has finished its processing with some warning messages.
<b>Action</b>	Check the log output, correct errors and try again.
<b>INODSA1000</b>	<b>Starting autorepair after abnormal termination</b>
<b>Explanation</b>	The last server session of the database was terminated abnormally. Before the database can be used, the data consistency will be re-established, changes which had not been written to disk will be redone, and transactions which were open at the time of the abnormal server session termination will be reset.
<b>Action</b>	Wait for the end of the autorepair processing before using your database.

---

<b>INODSA1001</b>	<b>Start writing crash dump of database, writing to file filename</b>
<b>Explanation</b>	The server has encountered an error situation which causes a crash. In order to enable error analysis, the server writes status information to a file in the reserved location.
<b>Action</b>	Report the crash to your software supplier, together with the dump files in the reserved location.
<b>INODSA1002</b>	<b>name modierversionmodifier2 on system info</b>
<b>Explanation</b>	This is a generic message that is used for identification of an activity.
<b>Action</b>	No action required.
<b>INODSA1003</b>	<b>Starting recovery</b>
<b>Explanation</b>	The database recovery processing is starting. After restoring a database, the recovery processing re-applies all updates that were done since the database backup was created.
<b>Action</b>	Wait for the end of the recovery processing before using your database.
<b>INODSA1006</b>	<b>Skipping database recovery during restore</b>
<b>Explanation</b>	The database restore is being performed without recovery processing. Log space information will be marked as skipped.
<b>Action</b>	Wait for the end of the recovery skipping before using your database.
<b>INODSA1007</b>	<b>Starting recovery until time</b>
<b>Explanation</b>	The database recovery processing is starting. After restoring a database, the recovery processing re-applies all updates that were done between the database backup creation and the specified time.
<b>Action</b>	Wait for the end of the recovery processing before using your database.
<b>INODSA1249</b>	<b>Starting recovery until time</b>
<b>Explanation</b>	The database recovery processing is starting. After restoring a database, the recovery processing re-applies all updates that were done between the database backup creation and the specified time.
<b>Action</b>	Wait for the end of the recovery processing before using your database.

<b>INODSA2278</b>	<b>Tamino name modifierversionmodifier2 on system info</b>
<b>Explanation</b>	This is a generic message that is used for identification of an activity.
<b>Action</b>	No action required.
<b>INODSE1015</b>	<b>Expanding the database has failed, because the licensed database size would have been exceeded</b>
<b>Explanation</b>	The allowed database size is limited by the amount allowed in your license file. The attempted expansion of the database would have exceeded the allowed size.
<b>Action</b>	Please contact your software supplier for an enhanced license which allows a larger database size.
<b>INODSE1025</b>	<b>Source and destination of the copy operation specify the same object (source)</b>
<b>Explanation</b>	Source and destination of a copy operation must not specify the same object.
<b>Action</b>	Please specify another source or destination for the copy operation.
<b>INODSE1026</b>	<b>Copy operation (src to dest) incomplete, copied done of expect bytes</b>
<b>Explanation</b>	The copy operation was incomplete due to a system error.
<b>Action</b>	Please consult your manufacturer's manual.
<b>INODSE1027</b>	<b>System error errno during operation call on file file</b>
<b>Explanation</b>	There was an operating system error while performing the specified operation on the specified file.
<b>Action</b>	Please consult your manufacturer's manual.
<b>INODSE1028</b>	<b>pathname does not specify a valid raw section (returned type error)</b>
<b>Explanation</b>	The given path does not specify a valid raw section.
<b>Action</b>	Specify a valid raw section.
<b>INODSE1029</b>	<b>Size of raw section section was computed as 0</b>
<b>Explanation</b>	The size of the given raw section could not be determined.
<b>Action</b>	Please contact your software supplier.

---

<b>INODSE1030</b>	<b>Raw section section is not empty and must not be reset</b>
<b>Explanation</b>	The specified raw section is not empty and must not be reset.
<b>Action</b>	Specify another raw section or deallocate all entries from the specified one.
<b>INODSE1031</b>	<b>database space space number of database server in raw section section is in use and must not be changed</b>
<b>Explanation</b>	The specified container is still in use and must not be changed.
<b>Action</b>	Ensure that the container is not in use before trying to change it.
<b>INODSE1032</b>	<b>Incremental backup cannot be used for database creation</b>
<b>Explanation</b>	The backup file selected is an incremental one, but databases can only be created from full backups.
<b>Action</b>	Use a full backup for database creation.
<b>INODSE1036</b>	<b>database space space number of database server in raw section section is in use and must not be deallocated</b>
<b>Explanation</b>	The specified database space is currently in use and must not be deallocated.
<b>Action</b>	No action required.
<b>INODSE1037</b>	<b>database space space number of database server in raw section section is in use and must not be reallocated</b>
<b>Explanation</b>	The specified database space is in use and must not be reallocated.
<b>Action</b>	No action required.
<b>INODSE1042</b>	<b>Incremental backup is not enabled</b>
<b>Explanation</b>	Incremental backup cannot be issued because the feature is not enabled.
<b>Action</b>	Switch on the server parameter for enabling incremental backup.
<b>INODSE1043</b>	<b>Incremental backup is not possible</b>
<b>Explanation</b>	Incremental backup is not possible because there is no valid associated full or incremental backup present, or for some reason the server has deactivated the incremental block collection.
<b>Action</b>	Perform a full backup to resolve this situation.

<b>INODSE1045</b>	<b>Incremental Backup is disabled at the database to be restored</b>
<b>Explanation</b>	The database is not prepared to receive the given incremental backup.
<b>Action</b>	Check the database. Possibly you must restore a full backup first.
<b>INODSE1046</b>	<b>Backup file has invalid or missing incremental backup data</b>
<b>Explanation</b>	The backup file to be restored incrementally has no incremental backup data, or the backup data is corrupted.
<b>Action</b>	Please contact your software supplier.
<b>INODSE1048</b>	<b>Backup numbers do not fit together: database dbnr, backup bcknr</b>
<b>Explanation</b>	The incremental backup file and the database to receive the backup file no not fit together according the backup numbers. The backup number of the backup file must be one higher than the current backup number of the database
<b>Action</b>	Check all your backup files and their numbers.
<b>INODSE1051</b>	<b>Structure level mismatch on log space from session session number</b>
<b>Explanation</b>	The log space was generated by a previous Tamino version.
<b>Action</b>	Use the previous Tamino version for restore/recovery and then switch again to the current version.
<b>INODSE1052</b>	<b>Internal error occurred: error string, location location</b>
<b>Explanation</b>	An internal error has occurred. The database can still be used.
<b>Action</b>	Please contact your software supplier and provide the message text.
<b>INODSE1055</b>	<b>Preparing for an emergency restart</b>
<b>Explanation</b>	The server has terminated due to shortage of journal space. This has caused a situation in which the autorestart processing that will run automatically at the start of the next server session cannot be guaranteed to resolve internal data inconsistencies from the current terminated session. Therefore, the next server session will start with an emergency restart.
<b>Action</b>	Restart the server. If the emergency restart completes without error, the database is in a consistent state and can be used normally. If the emergency start fails, you must recover your data using the latest backup.

---

<b>INODSE1056</b>	<b>During database restart, an error has occurred in an index on doctype doctype (ID). All indexes on this doctype have been dropped.</b>
<b>Explanation</b>	There was an error in an operation on an index during the database restart processing. All indexes on the affected doctype have been dropped, but the doctype still is available.
<b>Action</b>	After the restart has finished, recreate all indexes by choosing the "Check and Repair" function for the database in the Tamino Manager.
<b>INODSE1057</b>	<b>During database restart, an error has occurred on doctype doctype (ID). The doctype is no longer accessible.</b>
<b>Explanation</b>	There was an error in an operation on the doctype during the database restart processing. The doctype has been destroyed.
<b>Action</b>	After the restart has finished, restore the doctype.
<b>INODSE1058</b>	<b>Incremental Backup does not fit to latest database restore (different database backup ID)</b>
<b>Explanation</b>	The incremental backup to be restored into the database cannot be performed because there the associated full database restore was a different one.
<b>Action</b>	Check whether incremental backup file and its restored master full backup fit together.
<b>INODSE1060</b>	<b>Invalid internal database key found</b>
<b>Explanation</b>	The database's internal database key is corrupt.
<b>Action</b>	Please contact your software supplier.
<b>INODSE1061</b>	<b>No space left in raw section pathname for database space space number of database server</b>
<b>Explanation</b>	The specified raw section does not contain enough contiguous space to allocate the specified database space.
<b>Action</b>	Specify another raw section for this database space or free space in the given raw section.
<b>INODSE1063</b>	<b>database space space number of database server already present in raw section section</b>
<b>Explanation</b>	The required database space is already present.
<b>Action</b>	Remove the database space from the specified raw section.

<b>INODSE1066</b>	<b>Associated full backup not found for incremental backup savepoint</b>
<b>Explanation</b>	A full backup as a base of a selected incremental backup was not found.
<b>Action</b>	There is possibly a corruption of the internal configuration store.
<b>INODSE1068</b>	<b>The raw section section overlaps with a mounted file system</b>
<b>Explanation</b>	Raw sections must not overlap with file systems since this can result in data corruption.
<b>Action</b>	Define the raw section so that it does not overlap with a mounted file system.
<b>INODSE1069</b>	<b>Error accessing the mount table</b>
<b>Explanation</b>	The operating system's mount table could not be processed.
<b>Action</b>	Please contact your software supplier.
<b>INODSE1070</b>	<b>Decreasing the size of the raw section section failed</b>
<b>Explanation</b>	An attempt to decrease the size of the specified raw section failed because the required new size is too small. Only free space at the end of a raw section can be removed.
<b>Action</b>	Specify a raw section partition with a larger size.
<b>INODSE1071</b>	<b>Raw section section is already initialized</b>
<b>Explanation</b>	An attempt was made to initialize a raw section that is already initialized. A raw section can be initialized only once.
<b>Action</b>	No action required.
<b>INODSE1072</b>	<b>No space for database space space number of database server at specified position in raw section pathname</b>
<b>Explanation</b>	At the specified position in the raw section there is not enough contiguous space to allocate the specified database space.
<b>Action</b>	Specify another raw section or another position.
<b>INODSE1073</b>	<b>Overflow on raw section section</b>
<b>Explanation</b>	The raw section contains too many database spaces in the management area.
<b>Action</b>	Choose another raw section or remove obsolete database spaces.

---

<b>INODSE1074</b>	<b>Error allocating database space space number of database server on raw section section</b>
<b>Explanation</b>	An error occurred while trying to allocate space on the specified raw section.
<b>Action</b>	Please contact your software supplier.
<b>INODSE1076</b>	<b>System error errno during operation call on raw section section</b>
<b>Explanation</b>	There was an operating system error while performing the specified operation on the specified raw section.
<b>Action</b>	Please consult the manufacturer's manual.
<b>INODSE1077</b>	<b>Raw section section is corrupted or not initialized</b>
<b>Explanation</b>	The data on the specified raw section is corrupted.
<b>Action</b>	Please contact your software supplier if the section had been initialized.
<b>INODSE1079</b>	<b>path is a block device and cannot be used for raw sections</b>
<b>Explanation</b>	An attempt was made to define a raw device on a block device. Raw sections must not be block devices.
<b>Action</b>	No action required.
<b>INODSE1080</b>	<b>I/O error on block no in database space space no (operating system error errno)</b>
<b>Explanation</b>	There has been an I/O error during an operation (initialization of a database space). This does not, however, lead to a loss of data.
<b>Action</b>	Check the affected device: is it on-line, are the permissions correct, can operating system tools access the device? If you cannot find the reason for the read error by yourself, please contact your software supplier.
<b>INODSE1081</b>	<b>Journal space must be writable</b>
<b>Explanation</b>	The system could not write the specified database space.
<b>Action</b>	Check the attributes (e.g. permissions) of the database space.
<b>INODSE1082</b>	<b>Error when opening database space space number (at path)</b>
<b>Explanation</b>	The database space could not be opened.
<b>Action</b>	Check the affected device: is it on-line, are the permissions correct, can operating system tools access the device? If you cannot find the reason for the read error by yourself, please contact your software supplier.

<b>INODSE1083</b>	<b>System error errno when opening database space space no (path)</b>
<b>Explanation</b>	The specified operating system error has occurred.
<b>Action</b>	Please consult the manufacturer's manual.
<b>INODSE1084</b>	<b>Invalid block size block size</b>
<b>Explanation</b>	The given block size is not allowed.
<b>Action</b>	Provide a valid block size.
<b>INODSE1085</b>	<b>No space for source left on path</b>
<b>Explanation</b>	There is not enough space on the device.
<b>Action</b>	Specify another device or free some space.
<b>INODSE1086</b>	<b>Tape handling error: blocking factor not supported</b>
<b>Explanation</b>	The specified tape device cannot be written because the blocking factor is not supported.
<b>Action</b>	Change the blocking factor of the tape device. It must be either variable or a multiple of 1024.
<b>INODSE1087</b>	<b>Data error on source</b>
<b>Explanation</b>	The file structure of the specified file does not match the expectations of the system.
<b>Action</b>	Check the file's content and the defined structure.
<b>INODSE1088</b>	<b>A further extent of source cannot be created (reason reason, error err, errtxt)</b>
<b>Explanation</b>	During any given server session, there is a limit on how much the database can grow. This limit has been reached in the current server session.
<b>Action</b>	Stop the current server session and restart the database. In the new server session, the database can be extended.
<b>INODSE1090</b>	<b>Inconsistency detected when checking backup for timestamp savepoint</b>
<b>Explanation</b>	A series of incremental backups cannot be restored completely.
<b>Action</b>	Check if all incremental backups exist. If no backup is missing, please contact your software supplier.

---

<b>INODSE1091</b>	<b>Incremental Backup does not fit to latest database restore (database modified meanwhile)</b>
<b>Explanation</b>	The incremental backup to be restored into the database cannot be performed because there were some updates to the database in the meantime.
<b>Action</b>	Check if the database has been started between the restore of all involved backups and if there were any updates.
<b>INODSE1092</b>	<b>Incremental Backup does not fit to latest database restore (different backup sequence)</b>
<b>Explanation</b>	The incremental backup to be restored into the database cannot be performed because the latest incremental or full backup restored and the given incremental backup are not in the expected chain.
<b>Action</b>	Check if the incremental backup file and the most recently restored backup file really fit together.
<b>INODSE1093</b>	<b>Options "parallel" and "incremental" are mutually exclusive</b>
<b>Explanation</b>	An incremental parallel backup is not supported.
<b>Action</b>	Select only one of the options.
<b>INODSE1094</b>	<b>Tape device required</b>
<b>Explanation</b>	A tape device is required, but the specified path does not point to a tape device.
<b>Action</b>	Correct the path.
<b>INODSE1095</b>	<b>Incremental backup from timestamp must not be deleted</b>
<b>Explanation</b>	A single incremental backup must not be deleted.
<b>Action</b>	Select only full backups to be deleted. When deleting a full backup, associated incremental backups will be deleted as well.
<b>INODSE1096</b>	<b>Error errno has been signalled in the execution of an asynchronous I/O for id</b>
<b>Explanation</b>	An asynchronous I/O operation has failed due to an operating system error.
<b>Action</b>	Check for problems with the device. Check whether the device is off-line or read-only. In the case of a logical volume, try to access all of its physical devices by using operating system commands. Check the system log file for appropriate error messages.

<b>INODSE1097</b>	<b>An incremental backup must not be used to create a database</b>
<b>Explanation</b>	Only full backups are allowed to be used to create a database.
<b>Action</b>	Select a full backup to create a database.
<b>INODSE1098</b>	<b>Inconsistent backup count count1 found, expected count is count2</b>
<b>Explanation</b>	The existing incremental backups do not represent a valid sequence.
<b>Action</b>	Check if all incremental backups exist. If no backup is missing, please contact your software supplier.
<b>INODSE1099</b>	<b>Ambiguous keyword</b>
<b>Explanation</b>	The input does not uniquely identify a keyword.
<b>Action</b>	Please specify an unambiguous keyword.
<b>INODSE1100</b>	<b>Internal database error error on doctype doctype (ID). No further recovery on this doctype.</b>
<b>Explanation</b>	There was an error in an operation on a doctype. The doctype has been excluded from further recovery processing.
<b>Action</b>	Please contact your software supplier.
<b>INODSE1101</b>	<b>Internal error n f g h r in text index</b>
<b>Explanation</b>	A text index has encountered an error.
<b>Action</b>	Please contact your support center and provide them with the information given in the error message and with a backup copy of your database.
<b>INODSE1102</b>	<b>Internal error n f g h x in text index</b>
<b>Explanation</b>	A text index has encountered an error.
<b>Action</b>	Please contact your support center and provide them with the information given in the error message and with a backup copy of your database.
<b>INODSE1103</b>	<b>Loading of text index failed due to operating system error errno</b>
<b>Explanation</b>	This message indicates an installation error.
<b>Action</b>	Please consult the manufacturer's manual. If you cannot fix the error, contact your software supplier.

<b>INODSE1104</b>	<b>Journal overflow during recovery processing</b>
<b>Explanation</b>	The journal space was insufficient. Recovery processing was terminated.
<b>Action</b>	Provide more journal space. Restart the terminated activity.
<b>INODSE1105</b>	<b>Invalid structure for log space from session session number</b>
<b>Explanation</b>	The log space does not contain correct log information.
<b>Action</b>	Check if files have been moved or copied to the log space location.
<b>INODSE1106</b>	<b>Doctype doctype not found, no further recovery on this doctype</b>
<b>Explanation</b>	A doctype required for recovery processing was not found. The doctype has been excluded from further recovery processing.
<b>Action</b>	If the previous recovery processing aborted, restart the restore and recovery.
<b>INODSE1107</b>	<b>Doctype doctype locked, no further recovery on this doctype</b>
<b>Explanation</b>	A doctype required for recovery processing was locked. The doctype has been excluded from further recovery processing.
<b>Action</b>	The doctype may be locked due to an abort of previous recovery processing. Restart the restore and recovery.
<b>INODSE1108</b>	<b>Internal database error error on index index name of doctype doctype (ID). All indexes on this doctype have been dropped.</b>
<b>Explanation</b>	There was an error in an operation on an index of a doctype. The index of the doctype has been disabled.
<b>Action</b>	After the recovery has finished, recreate the index by choosing the "Check and Repair" function for the database in the Tamino Manager.
<b>INODSE1109</b>	<b>The index of doctype doctype is not accessible, recovery of this doctype will not include index</b>
<b>Explanation</b>	The index remains in a disabled state from a previous abort during recovery processing.
<b>Action</b>	After the recovery has finished, recreate the index by choosing the "Check and Repair" function for the database in the Tamino Manager.

<b>INODSE1111</b>	<b>Utility sub-function has not yet been implemented</b>
<b>Explanation</b>	Although the sub-function is a valid function request, it has not yet been implemented for the utility. This is an internal message.
<b>Action</b>	Please contact your software supplier.
<b>INODSE1112</b>	<b>Utility handling not implemented</b>
<b>Explanation</b>	This is an internal message.
<b>Action</b>	Please contact your software supplier.
<b>INODSE1117</b>	<b>No more memory can be allocated</b>
<b>Explanation</b>	A utility issued a request to allocate temporary memory, but this request failed. The utility will now terminate, and the administration agent will carry out any necessary recovery tasks.
<b>Action</b>	No action required. Please contact your system administrator for further information.
<b>INODSE1118</b>	<b>Internal configuration error</b>
<b>Explanation</b>	An internal configuration error has occurred. The utility will now terminate, and the administration agent will carry out any necessary recovery tasks.
<b>Action</b>	No action required. Please contact your system administrator for further information.
<b>INODSE1119</b>	<b>Invalid date/time specified. Valid format is YYYY-MM-DD:hh:mm:ss</b>
<b>Explanation</b>	The date and time specified is invalid.
<b>Action</b>	Specify a date and time using format YYYY-MM-DD:hh:mm:ss.
<b>INODSE1120</b>	<b>Sub-function is not valid for utility</b>
<b>Explanation</b>	A sub-function was specified that is not valid for the utility.
<b>Action</b>	Specify a valid sub-function for the utility.
<b>INODSE1121</b>	<b>Open of file path has failed due to operating system error errno</b>
<b>Explanation</b>	The virtual operating system could not open the requested file.
<b>Action</b>	Make sure that the file is available.

---

<b>INODSE1122</b>	<b>Service name for server servername not found</b>
<b>Explanation</b>	The service name for the server was not found in the configuration store.
<b>Action</b>	Please contact your software supplier.
<b>INODSE1123</b>	<b>SCM open failed with error rsp</b>
<b>Explanation</b>	Service Control Manager open failed.
<b>Action</b>	Please contact your software supplier.
<b>INODSE1124</b>	<b>Utility cannot run because of a pending autorepair on the database</b>
<b>Explanation</b>	An attempt was made to start a utility against a database that had not terminated correctly.
<b>Action</b>	Start the database, and let the autorepair processing complete. Then rerun the utility.
<b>INODSE1125</b>	<b>A syntax error has occurred in a utility</b>
<b>Explanation</b>	A syntax error was detected in the parameters of a utility.
<b>Action</b>	Correct the syntax error and rerun the utility.
<b>INODSE1127</b>	<b>SCM service open failed with error rsp</b>
<b>Explanation</b>	Service Control Manager open service failed.
<b>Action</b>	Please contact your software supplier.
<b>INODSE1128</b>	<b>System error errno occurred during file synchronization</b>
<b>Explanation</b>	A file synchronization operation has failed at the operating system level.
<b>Action</b>	Check the manufacturer's manual.
<b>INODSE1130</b>	<b>System error errno occurred during semaphore operation</b>
<b>Explanation</b>	An error has occurred while an operation on a semaphore was requested from the operating system.
<b>Action</b>	Check the manufacturer's manual.
<b>INODSE1131</b>	<b>Invalid server session number session number found in log space block block number</b>
<b>Explanation</b>	The log space does not contain correct log information.
<b>Action</b>	Check if files have been moved or copied to the log space location.

<b>INODSE1132</b>	<b>Invalid block sequence found in log space - expected block number1, current is block number2</b>
<b>Explanation</b>	The log space does not contain correct log information.
<b>Action</b>	Check if files have been moved or copied to the log space location.
<b>INODSE1133</b>	<b>Error opening log space: error message</b>
<b>Explanation</b>	The log space could not be opened. The recovery function has been stopped.
<b>Action</b>	Check if files have been moved or copied to the log space location.
<b>INODSE1134</b>	<b>SCM service start failed with error rsp</b>
<b>Explanation</b>	Service Control Manager start service failed.
<b>Action</b>	Please contact your software supplier.
<b>INODSE1135</b>	<b>SCM query service status failed with error rsp</b>
<b>Explanation</b>	Service Control Manager query service status failed.
<b>Action</b>	Please contact your software supplier.
<b>INODSE1136</b>	<b>Transaction aborted due to transaction timeout</b>
<b>Explanation</b>	A transaction has been aborted. All changes of this transaction have been undone.
<b>Action</b>	Check whether a higher transaction timeout value would make sense in your environment. Restart the transaction.
<b>INODSE1137</b>	<b>Transaction aborted due to non-active connection</b>
<b>Explanation</b>	A transaction has been aborted. All changes of this transaction have been undone.
<b>Action</b>	Check the reason for the transaction abort. Restart the transaction.
<b>INODSE1138</b>	<b>Transaction aborted because server session had been stopped by administrator</b>
<b>Explanation</b>	A server session was explicitly stopped by the administrator. All changes of this transaction have been undone.
<b>Action</b>	No action required.

---

<b>INODSE1139</b>	<b>Transaction aborted due to overflow in journal space journal space</b>
<b>Explanation</b>	A transaction has been aborted because there was not enough space to log all the changes of the transaction or because too many transactions were active at the same time. All changes of this transaction have been undone.
<b>Action</b>	Consider enlarging the journal space. Restart the transaction.
<b>INODSE1140</b>	<b>Transaction aborted due to security violation</b>
<b>Explanation</b>	A transaction has been aborted. All changes of this transaction have been undone.
<b>Action</b>	No action required.
<b>INODSE1141</b>	<b>Transaction aborted due to deadlock</b>
<b>Explanation</b>	A transaction has been aborted because its locking requirements caused a deadlock with other transactions. All changes of this transaction have been undone.
<b>Action</b>	Restart the transaction.
<b>INODSE1142</b>	<b>Transaction aborted due to internal error reason</b>
<b>Explanation</b>	A transaction has been aborted. All changes of this transaction have been undone.
<b>Action</b>	Please contact your software supplier.
<b>INODSE1143</b>	<b>Internal database error error has occurred</b>
<b>Explanation</b>	The specified database error has occurred.
<b>Action</b>	Please contact your software supplier.
<b>INODSE1144</b>	<b>The data of doctype doctype is not accessible</b>
<b>Explanation</b>	The doctype may be locked or may have been corrupted by a previous action (e.g. failed server restart).
<b>Action</b>	If the doctype is locked, wait until it is unlocked, then retry. If the doctype was corrupted by a previous action, the system administrator must rebuild the doctype from backups.
<b>INODSE1145</b>	<b>The indexes of doctype doctype are not accessible</b>
<b>Explanation</b>	The indexes may have been corrupted by a previous action (e.g. failed server restart).
<b>Action</b>	Wait for a short while, then retry. If the problem persists, this might indicate that the indexes have to be rebuilt. To rebuild the indexes, choose the "Check and Repair" function for the database in the Tamino Manager.

<b>INODSE1148</b>	<b>I/O error on database space db space number</b>
<b>Explanation</b>	The operating system has signalled an I/O error. This is typically caused by a hardware error.
<b>Action</b>	Check whether any disk devices have gone offline. Check the error log for hardware errors.
<b>INODSE1149</b>	<b>Too many paths specified for a location</b>
<b>Explanation</b>	Only 8 paths are allowed to be specified for a location.
<b>Action</b>	Use less paths for the location to be set up.
<b>INODSE1150</b>	<b>The indexes of doctype doctype are corrupt, reason rsp</b>
<b>Explanation</b>	An internal inconsistency has been found in the indexes.
<b>Action</b>	The indexes have to be rebuilt. To rebuild the indexes, choose the "Check and Repair" function for the database in the Tamino Manager.
<b>INODSE1153</b>	<b>filename is an invalid file name for a database space</b>
<b>Explanation</b>	The specified file name for a database space is not valid.
<b>Action</b>	Specify a valid file name for a database space.
<b>INODSE1154</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INODSE1155</b>	<b>filename is not a database space for server dbname</b>
<b>Explanation</b>	The specified file name is not a database space for the given database name.
<b>Action</b>	Make sure that the file name of the database space is a database space of the specified database.
<b>INODSE1158</b>	<b>I/O subsystem error (e1/e2): error text</b>
<b>Explanation</b>	An error in an I/O related function has occurred.
<b>Action</b>	Please contact your software supplier.

---

<b>INODSE1167</b>	<b>standard length out of range</b>
<b>Explanation</b>	The specified length value is invalid.
<b>Action</b>	Correct the length specification.
<b>INODSE1171</b>	<b>FI only allowed if standard-length is given</b>
<b>Explanation</b>	The FI option is only allowed if a non-zero standard length is given.
<b>Action</b>	Correct the input line.
<b>INODSE1172</b>	<b>Wrong input file assigned</b>
<b>Explanation</b>	The wrong input file has been used for the utility.
<b>Action</b>	Ensure that the correct input file is being used by the utility.
<b>INODSE1173</b>	<b>Checked and repaired database. Number of corrupted indexes was number. Of these, repairing failed for failed.</b>
<b>Explanation</b>	The database could not be completely repaired.
<b>Action</b>	Please contact your software supplier.
<b>INODSE1175</b>	<b>Invalid load data structure at file (ID id, length length)</b>
<b>Explanation</b>	The structure of the data to be loaded is invalid.
<b>Action</b>	Ensure that the correct input file is being used. Send the load files (extension 1C0/1C1) to your software supplier.
<b>INODSE1176</b>	<b>Unable to attach to shared memory</b>
<b>Explanation</b>	It is not possible to attach the process to the shared memory.
<b>Action</b>	Ensure that there is enough available memory, and contact your software supplier if required.
<b>INODSE1181</b>	<b>An unexpected server response (response) has occurred</b>
<b>Explanation</b>	The specified response has been returned by the server.
<b>Action</b>	Determine the reason for the response, or contact your support center.

<b>INODSE1182</b>	<b>Database server is not accessible</b>
<b>Explanation</b>	It is not possible to access the database server.
<b>Action</b>	Determine the reason why the database server is not accessible and retry the operation.
<b>INODSE1189</b>	<b>Reorganize database is not permitted while database is active</b>
<b>Explanation</b>	To preserve data consistency, the database must not be active while reorganize function is processed.
<b>Action</b>	Shut down the database
<b>INODSE1194</b>	<b>An internal buffer is too large (size)</b>
<b>Explanation</b>	The size of an internal buffer has caused a record to overflow.
<b>Action</b>	Please contact your software supplier.
<b>INODSE1198</b>	<b>Event token not supplied</b>
<b>Explanation</b>	The recovery function was started without supplying an event token.
<b>Action</b>	Check the usage of the administration tool.
<b>INODSE1199</b>	<b>Logging not disabled</b>
<b>Explanation</b>	When the recovery function is started, logging must be disabled. In this case, the recovery function was started with logging enabled.
<b>Action</b>	Check the usage of the administration tool.
<b>INODSE1200</b>	<b>Database name is too long</b>
<b>Explanation</b>	The specified database name is too long. If the database name consists of ASCII characters, it can be up to 16 characters long. If the database name consists of multibyte characters, the total number of bytes required to store the database name must not exceed 16.
<b>Action</b>	Please specify a shorter database name.
<b>INODSE1201</b>	<b>Database name contains invalid character "," (comma)</b>
<b>Explanation</b>	A database name cannot contain a comma.
<b>Action</b>	Please modify the database name.

---

<b>INODSE1202</b>	<b>Database name contains an invalid character</b>
<b>Explanation</b>	A database name cannot contain certain characters, such as # " . [ ] .
<b>Action</b>	Please modify the database name.
<b>INODSE1203</b>	<b>Database name contains invalid character "" (backslash)</b>
<b>Explanation</b>	A database name cannot contain a backslash.
<b>Action</b>	Please modify the database name.
<b>INODSE1204</b>	<b>Administration function terminated with error errornumber: errorstring</b>
<b>Explanation</b>	An administration function failed with given error string.
<b>Action</b>	Please restart the command using the option to write a job log and check if there is additional error information. If not, contact your software supplier.
<b>INODSE1205</b>	<b>Replication permission denied for hostname</b>
<b>Explanation</b>	The host name is not in the master's list of permitted databases for replication
<b>Action</b>	Add the host name of the replication instance to allow replication.
<b>INODSE1206</b>	<b>Cannot connect to master dbname on hostname</b>
<b>Explanation</b>	An attempt accessing the master database failed.
<b>Action</b>	Check that the master database is active on the specified node and retry the command.
<b>INODSE1209</b>	<b>Maximum number of space files reached</b>
<b>Explanation</b>	The maximum allowed number of data/index files has been reached.
<b>Action</b>	Please contact your software supplier.
<b>INODSE1210</b>	<b>Size of space file too large</b>
<b>Explanation</b>	The size of the file to be created exceeds the limits of the operating system or of the underlying storage medium. For example, you want to create a file with a size greater than 2GB, but the operating system does not support this.
<b>Action</b>	Select a smaller file size.

<b>INODSE1212</b>	<b>Internal free space error</b>
<b>Explanation</b>	An unexpected free space management error occurred when adding a new database file.
<b>Action</b>	Please contact your software supplier.
<b>INODSE1213</b>	<b>Error error accessing or modifying information in the internal configuration store</b>
<b>Explanation</b>	The information for a log space or a savepoint entry could not be retrieved or set up.
<b>Action</b>	Check the reasons for errors accessing and updating the internal configuration store (for example permissions or low disk space).
<b>INODSE1214</b>	<b>An error occurred during a create index process on doctype doctype</b>
<b>Explanation</b>	The error is caused by an attempt to create a unique index on data that contains non-unique values.
<b>Action</b>	No action required.
<b>INODSE1215</b>	<b>Database name contains a space</b>
<b>Explanation</b>	A database name cannot contain a space.
<b>Action</b>	Please modify the database name.
<b>INODSE1217</b>	<b>Error when opening database space, compressed state is not permitted (at path)</b>
<b>Explanation</b>	The database file has the compressed attribute, which is not permitted, because write errors should be avoided if the device is getting full.
<b>Action</b>	Remove the compressed attribute from the database file.
<b>INODSE1221</b>	<b>Error error when accessing internal information for savepoint savepoint</b>
<b>Explanation</b>	The information for a savepoint entry could not be retrieved.
<b>Action</b>	Contact your software supplier.
<b>INODSE1222</b>	<b>Error error when trying to move or delete file name</b>
<b>Explanation</b>	A backup file or a file for recovery purpose could not be moved or removed.
<b>Action</b>	Contact your software supplier.

---

<b>INODSE1223</b>	<b>Log space not found for savepoint savepoint, session number session number</b>
<b>Explanation</b>	A log space entry for the given savepoint and session number could not be found.
<b>Action</b>	Contact your software supplier.
<b>INODSE1224</b>	<b>Backup space not found for savepoint savepoint</b>
<b>Explanation</b>	A backup space for the given savepoint could not be found.
<b>Action</b>	Contact your software supplier.
<b>INODSE1225</b>	<b>Backup file type file type is invalid for savepoint savepoint</b>
<b>Explanation</b>	The internal information for the file type associated with a savepoint is set up incorrectly.
<b>Action</b>	Contact your software supplier.
<b>INODSE1226</b>	<b>Unexpected return code error when executing function function</b>
<b>Explanation</b>	An internal error occurred.
<b>Action</b>	Please contact your software supplier.
<b>INODSE1231</b>	<b>Errors have occurred during autorepair</b>
<b>Explanation</b>	The autorepair from the crash of the previous server session was not completely successfully.
<b>Action</b>	Check the detailed error messages and repair the affected data.
<b>INODSE1232</b>	<b>Database space is too large</b>
<b>Explanation</b>	The database space specified for the current operation is too large.
<b>Action</b>	Retry the operation specifying a smaller database space.
<b>INODSE1233</b>	<b>The limit of extents for container_name has been reached</b>
<b>Explanation</b>	No more extents of the specified space type can be created because the maximum number has been reached.
<b>Action</b>	Retry the operation with a smaller number of extents specified.

<b>INODSE1234</b>	<b>Server parameter 'number of backup generations' larger than 1 required</b>
<b>Explanation</b>	Supplying replication data requires log spaces to be kept for more than one backup.
<b>Action</b>	For a master server set the server property 'number of backup generations' to value larger than 1.
<b>INODSE1235</b>	<b>Crash dump file filename could not be created due to operating system error system errno (errtxt)</b>
<b>Explanation</b>	The backup file needed for error analysis could not be created due to the given reason.
<b>Action</b>	Please consult the manufacturer's manual.
<b>INODSE1236</b>	<b>Recovery skipping has terminated with an error</b>
<b>Explanation</b>	An error occurred during recovery skipping. This message indicates an internal inconsistency.
<b>Action</b>	Please contact your software supplier.
<b>INODSE1247</b>	<b>Replication processing disabled because master database was restored without full recovery</b>
<b>Explanation</b>	When the master database was restored not using 'recover all' option, synchronization is lost by updates already replicated but not recovered for the master database.
<b>Action</b>	Delete the replication database and set it up again using a backup created after the restore was done.
<b>INODSE1289</b>	<b>Error when opening database space space no (at path): size mismatch</b>
<b>Explanation</b>	The size of the database space is not equal to the size expected by the server.
<b>Action</b>	Please contact your software supplier.
<b>INODSE1290</b>	<b>I/O error occurred on database space space no. System error errno caused by operation operation on block block number.</b>
<b>Explanation</b>	The operating system has signalled that the specified I/O operation has failed.
<b>Action</b>	Please consult the manufacturer's manual.
<b>INODSE1292</b>	<b>Creation of database space space no (path) has failed</b>
<b>Explanation</b>	The database space could not be created at the specified location.
<b>Action</b>	Look for other error messages to find the reason for the failure.

---

<b>INODSE1293</b>	<b>Creation of database space space no (path) has failed due to system error errno</b>
<b>Explanation</b>	The database space could not be created at the specified location because of an error signalled by the operating system.
<b>Action</b>	Please consult the manufacturer's manual.
<b>INODSE1295</b>	<b>Creation of journal space 1 (path) has failed</b>
<b>Explanation</b>	The database space could not be created at the specified location.
<b>Action</b>	Look for other error messages to find the reason for the failure.
<b>INODSE1318</b>	<b>Internal server error during database creation, reason: reason</b>
<b>Explanation</b>	The system has tried to allocate a new database space, probably because the existing database spaces did not contain enough free space. The allocation has failed.
<b>Action</b>	Check which database space was affected by checking the free space. Allocate another database space manually.
<b>INODSE1320</b>	<b>Log space structure error error number</b>
<b>Explanation</b>	The log information which is needed to recover the database is corrupt, so the database recovery was stopped when the corruption was detected.
<b>Action</b>	Send the log space to your software supplier for analysis.
<b>INODSE1358</b>	<b>Creation of database space space no (path) has failed because the file already exists</b>
<b>Explanation</b>	The database space could not be created at the specified location because the file is already present.
<b>Action</b>	Remove or move the file to another location before repeating the action.
<b>INODSE1374</b>	<b>No abbreviation allowed for this keyword</b>
<b>Explanation</b>	The specified keyword must not be abbreviated.
<b>Action</b>	Please specify the keyword in full length.
<b>INODSE1375</b>	<b>Invalid keyword</b>
<b>Explanation</b>	The specified keyword is not recognized or invalid.
<b>Action</b>	Please specify a correct keyword.

<b>INODSE1376</b>	<b>Syntax error</b>
<b>Explanation</b>	An internal syntax error occurred.
<b>Action</b>	Please contact your software supplier to analyze the problem.
<b>INODSE1380</b>	<b>Given value not numeric</b>
<b>Explanation</b>	The given value has to be in a numeric format.
<b>Action</b>	Please specify a numeric value.
<b>INODSE1381</b>	<b>Only number value(s) allowed</b>
<b>Explanation</b>	The number of allowed list elements is exceeded.
<b>Action</b>	Please limit the number of list elements to the maximum allowed.
<b>INODSE1382</b>	<b>Value has to be greater than or equal to minvalue</b>
<b>Explanation</b>	The specified value is too low.
<b>Action</b>	Please enter a value greater than or equal to the required minimum.
<b>INODSE1383</b>	<b>Value has to be less than or equal to maxvalue</b>
<b>Explanation</b>	The specified value is too high.
<b>Action</b>	Please specify a value less than or equal to the allowed maximum.
<b>INODSE1385</b>	<b>Invalid range specified</b>
<b>Explanation</b>	The range specified is invalid.
<b>Action</b>	Please specify a range within the allowed limits.
<b>INODSE1386</b>	<b>At least minnum character(s) required</b>
<b>Explanation</b>	The specified number of characters was too low.
<b>Action</b>	Please specify a sufficient number of characters.
<b>INODSE1387</b>	<b>Only maxnum character(s) allowed</b>
<b>Explanation</b>	The maximum allowed number of characters was exceeded.
<b>Action</b>	Please specify no more than the maximum allowed number of characters.

---

<b>INODSE1390</b>	<b>Missing mandatory parameter param</b>
<b>Explanation</b>	The displayed mandatory parameter could not be found and a default value is not available.
<b>Action</b>	Supply the displayed mandatory parameter.
<b>INODSE1391</b>	<b>Invalid parameter value</b>
<b>Explanation</b>	The specified parameter value is invalid.
<b>Action</b>	Correct the input.
<b>INODSE1413</b>	<b>System error errno when opening database space space no (path)</b>
<b>Explanation</b>	The specified operating system error has occurred.
<b>Action</b>	Please consult the manufacturer's manual.
<b>INODSE1416</b>	<b>architecture mismatch detected, file from platform</b>
<b>Explanation</b>	The crash dump file is from a different platform.
<b>Action</b>	Go to the proper platform.
<b>INODSE1419</b>	<b>Incremental backup from timestamp must not be deleted</b>
<b>Explanation</b>	A single incremental backup must not be deleted.
<b>Action</b>	Select only full backups to be deleted. When deleting a full backup, associated incremental backups will be deleted as well.
<b>INODSE1421</b>	<b>Backup time has become invalid</b>
<b>Explanation</b>	An earlier backup was used for a restore not using the recover all option. Due to new modifications done on this base, the newer backup must not be used for restore/recover.
<b>Action</b>	Use another backup for restore/recover. The selected backup can only be used to create new database.
<b>INODSE1498</b>	<b>unknown option</b>
<b>Explanation</b>	The option specified is unknown.
<b>Action</b>	Correct the input line.

<b>INODSE1506</b>	<b>option not permitted</b>
<b>Explanation</b>	The supplied option is not permitted for this function.
<b>Action</b>	Check the input parameters.
<b>INODSE1512</b>	<b>transition to this level not allowed</b>
<b>Explanation</b>	The specified level number is not allowed in this context.
<b>Action</b>	Correct the input line.
<b>INODSE1523</b>	<b>reserved field name</b>
<b>Explanation</b>	The specified field name is reserved.
<b>Action</b>	Correct the field name.
<b>INODSE1538</b>	<b>Read-only mode is not permitted because the previous session was abnormally terminated</b>
<b>Explanation</b>	The Tamino server cannot be started in read-only mode because the previous session was abnormally terminated.
<b>Action</b>	Start the Tamino server in normal mode to do an autorepair for the abnormal termination. Restart the Tamino server in read-only mode.
<b>INODSE1539</b>	<b>Read-only mode is not permitted because of pending transactions</b>
<b>Explanation</b>	The Tamino server cannot be started in read-only mode because of pending global transactions.
<b>Action</b>	Start the Tamino server in normal mode and close the pending global transactions.
<b>INODSE1603</b>	<b>Error when adding a new type</b>
<b>Explanation</b>	An unexpected error occurred while adding a container.
<b>Action</b>	Check the device and the environment variable relating to the new container.
<b>INODSE1604</b>	<b>Number of additional cont extents currently exhausted</b>
<b>Explanation</b>	The maximum number of created database spaces within one session has been reached.
<b>Action</b>	Shut down and restart the database server and retry the operation.

<b>INODSE1605</b>	<b>No space for extending database space</b>
<b>Explanation</b>	There is no more space on the disk for extending the current database space.
<b>Action</b>	Check the disk size where the latest database space is located. Think about creating a new database space on another disk where space is available.
<b>INODSE1606</b>	<b>Database space to be removed is in use</b>
<b>Explanation</b>	The request to remove a database space failed because the file space at the end of the file is in use.
<b>Action</b>	Ensure that the database space is not in use and retry the operation.
<b>INODSE1633</b>	<b>Recovery terminated with error</b>
<b>Explanation</b>	An error occurred during database recovery.
<b>Action</b>	Check for additional error messages in the event log.
<b>INODSE1769</b>	<b>Invalid database root block header (size blocksize / next block)</b>
<b>Explanation</b>	A database root block linkage is invalid.
<b>Action</b>	Perform a restore/recover of the database.
<b>INODSE1898</b>	<b>The specified doctype is not available.</b>
<b>Explanation</b>	It is not possible to access the specified doctype.
<b>Action</b>	Check that the correct doctype name has been specified, and that it is currently available for use.
<b>INODSE1913</b>	<b>File file not loaded</b>
<b>Explanation</b>	The file with the given number could not be loaded
<b>Action</b>	Check whether the file exists or is not accessible.
<b>INODSE1945</b>	<b>Function not permitted while server is running</b>
<b>Explanation</b>	The given function is invalid with an active server.
<b>Action</b>	Shut down the server.

<b>INODSE1976</b>	<b>Internal database error error during recovery processing</b>
<b>Explanation</b>	While processing a log space, re-applying updates resulted in an error.
<b>Action</b>	Check if the database was in a different state than it was when the original command was executed. This may be caused by using a backup copy and log spaces inconsistently.
<b>INODSE1979</b>	<b>Database space space has reached the upper limit</b>
<b>Explanation</b>	The maximum size of the given database space has been reached. This means the database cannot be extended any more.
<b>Action</b>	A database redesign is necessary. Either delete doctypes from the database or create a second database.
<b>INODSE1984</b>	<b>Allocation of a new data space failed on required index allocation (reason)</b>
<b>Explanation</b>	The database space (data) cannot be enlarged. The new database space requires allocations in the index space, but the index space allocation failed due to the internal reason displayed.
<b>Action</b>	Investigate why the index database space cannot be enlarged.
<b>INODSE1987</b>	<b>Error when extending type</b>
<b>Explanation</b>	A database space extension failed, so the database could not be enlarged.
<b>Action</b>	View the subsequent error message for information about why the database could not be enlarged.
<b>INODSE1992</b>	<b>Invalid container request type</b>
<b>Explanation</b>	An internal error occurred while accessing a database container file.
<b>Action</b>	Contact your software supplier and report the number displayed in the message.
<b>INODSE1995</b>	<b>Access to configuration information for savepoint 'ts' failed: msg</b>
<b>Explanation</b>	The backup with the given representation could not be determined in the database configuration.
<b>Action</b>	Contact your software supplier to analyze the problem.

---

<b>INODSE1996</b>	<b>Database is inconsistent, restore required</b>
<b>Explanation</b>	The database is in an inconsistent state that cannot be handled by the autorepair process. The database must be restored.
<b>Action</b>	The reason for an inconsistent database can be re-applying a mass load during recovery. If no abort timestamp is shown in the event log of the aborted session, perhaps due to a power failure, restart with restore/recover. For any other reasons that will cause the error to re-occur, set up the restore/recover until a timestamp shortly before the recovery abort shown in the event log of the aborted session.
<b>INODSE1999</b>	<b>Internal database error error during recovery processing on doctype doctype</b>
<b>Explanation</b>	While processing a log space, re-applying the updates resulted in an error.
<b>Action</b>	Check if the database is in a different state than it was when the original command was executed. This may be caused by using a backup copy and log spaces inconsistently.
<b>INODSE2000</b>	<b>Starting replication failed</b>
<b>Explanation</b>	Replication processing could not be started.
<b>Action</b>	Check for for additional related messages in the event log.
<b>INODSE2001</b>	<b>Replication processing cannot be continued due to previous replication error</b>
<b>Explanation</b>	An error during the previous replication processing prevents the continuation of the replication.
<b>Action</b>	If the master database is lost, the Reset Replication function can be used to convert the database for usage as a substitution. In any other case, the replication database has to be recreated using a new backup from the master database.
<b>INODSE2004</b>	<b>Invalid operation detected</b>
<b>Explanation</b>	Replication cannot be continued because a function (e.g. restore without full recover) was executed on the master database which is not yet supported for replication
<b>Action</b>	A backup from the master database after the operation in question should be used to recreate the replication database.
<b>INODSE2013</b>	<b>Database identification already in use</b>
<b>Explanation</b>	The database identification supplied is already in use.
<b>Action</b>	Repeat the process using an unused database identification.

<b>INODSE2014</b>	<b>Failed to enumerate databases</b>
<b>Explanation</b>	An internal call has failed to enumerate the defined database names.
<b>Action</b>	Please contact your software supplier.
<b>INODSE2019</b>	<b>No log space data found for session session number</b>
<b>Explanation</b>	The master database could not find the log space to return the required log space data.
<b>Action</b>	Check the database properties for the number of backup generations and increase the value if set too low.
<b>INODSE2020</b>	<b>Replication database(s) defined, rename not allowed</b>
<b>Explanation</b>	The rename function is not allowed for a database which is to be used as a master database for replication purposes.
<b>Action</b>	Remove replication databases first before renaming the database. New replication databases can be created from a backup created after the rename operation.
<b>INODSE2022</b>	<b>Replication permission denied by master database</b>
<b>Explanation</b>	The name of the replication database was not found in the master database's list of permitted databases.
<b>Action</b>	Add the replication database name to the list of permitted replication databases of the master database.
<b>INODSE2023</b>	<b>Replication database origin mismatch</b>
<b>Explanation</b>	The replication database does not match the contents of the master database.
<b>Action</b>	Check whether the replication database was created using a backup from another database than the one specified as master database or check whether another database was renamed using the same database name as the master database's name.
<b>INODSE2024</b>	<b>An internal utility parameter error (location) has occurred</b>
<b>Explanation</b>	An internal parameter error has caused the utility to fail.
<b>Action</b>	Please contact your software supplier.

---

<b>INODSE2031</b>	<b>Internal error occurred: DSIF func [mod - line] what parameter param</b>
<b>Explanation</b>	An internal error occurred.
<b>Action</b>	Please contact your software supplier and provide the message text.
<b>INODSE2033</b>	<b>Internal error occurred: OVO func [mod - line] error</b>
<b>Explanation</b>	An internal error occurred.
<b>Action</b>	Please contact your software supplier and provide the message text.
<b>INODSE2034</b>	<b>Internal error occurred: SMP func [mod - line] error</b>
<b>Explanation</b>	An internal error occurred.
<b>Action</b>	Please contact your software supplier and provide the message text.
<b>INODSE2035</b>	<b>Server communication interface [mod - line] error error</b>
<b>Explanation</b>	An unexpected error was returned by the server communication interface.
<b>Action</b>	Please contact your software supplier and provide the message text.
<b>INODSE2036</b>	<b>path is not a valid directory</b>
<b>Explanation</b>	The directory specified does not exist.
<b>Action</b>	Specify a valid directory name.
<b>INODSE2037</b>	<b>Insufficient free disk space on path - available avail MB, needed needed MB</b>
<b>Explanation</b>	There is not enough space in the given directory to complete the operation.
<b>Action</b>	Free some disk space or specify another directory.
<b>INODSE2042</b>	<b>File file already exists in the destination directory dir</b>
<b>Explanation</b>	The file cannot be created in the destination directory because another file with the same name already exists.
<b>Action</b>	Change the destination directory parameter.
<b>INODSE2043</b>	<b>Infofile cannot be created, because otherwise the full path name of the info file would exceed operating system limit</b>
<b>Explanation</b>	The infofile path is too long.
<b>Action</b>	Please specify another directory for the CD database.

<b>INODSE2045</b>	<b>File path does not exist</b>
<b>Explanation</b>	An invalid path was specified.
<b>Action</b>	Specify a valid path.
<b>INODSE2046</b>	<b>Failed to parse infofile , line 'line'</b>
<b>Explanation</b>	The CD database infofile could not be parsed.
<b>Action</b>	Please contact your software supplier.
<b>INODSE2048</b>	<b>Cannot create database, because there are too many databases already</b>
<b>Explanation</b>	A new database cannot be created because there are too many databases already.
<b>Action</b>	Check if you still need all the databases you created and if possible delete some of them.
<b>INODSE2050</b>	<b>Requested operation not permitted in online mode</b>
<b>Explanation</b>	The server must be offline to perform the requested operation.
<b>Action</b>	Shut down the database.
<b>INODSE2061</b>	<b>Work pool too small</b>
<b>Explanation</b>	The work pool used is too small.
<b>Action</b>	Ensure that a sufficiently large work pool is available.
<b>INODSE2064</b>	<b>Invalid infofile format</b>
<b>Explanation</b>	The CD database information file has an invalid format.
<b>Action</b>	This error should not occur unless the file was modified manually. Avoid manual modification in the information file.
<b>INODSE2065</b>	<b>Incompatible operating system (original database was created on operating system)</b>
<b>Explanation</b>	The CD database cannot be created because the database is incompatible with the target platform.
<b>Action</b>	Create the CD database on the same platform as the original database.

---

<b>INODSE2067</b>	<b>Operation not allowed on read-only or CD databases</b>
<b>Explanation</b>	The required operation cannot be performed on a CD database or read-only database.
<b>Action</b>	Switch the "read only" server parameter to "no". This does not apply to databases on CD.
<b>INODSE2069</b>	<b>Location with the same name already exists</b>
<b>Explanation</b>	A location with the same name already exists.
<b>Action</b>	Choose another location name.
<b>INODSE2070</b>	<b>Cannot delete default location or default backup location</b>
<b>Explanation</b>	There was an attempt to delete the default location or default backup location. Delete operations on these locations are not allowed.
<b>Action</b>	No action required.
<b>INODSE2071</b>	<b>Location with the same path settings already exists</b>
<b>Explanation</b>	A location with the same path settings already exists
<b>Action</b>	Choose another location path.
<b>INODSE2072</b>	<b>Location locname not found</b>
<b>Explanation</b>	The specified location was not found.
<b>Action</b>	Correct the location name parameter and try again.
<b>INODSE2080</b>	<b>Internal error occurred: DSIF func [mod - line] not allowed in this context</b>
<b>Explanation</b>	An internal error occurred.
<b>Action</b>	Please contact your software supplier and provide the message text.
<b>INODSE2081</b>	<b>Internal error occurred: OVO memory what(bytes) [mod - line] error</b>
<b>Explanation</b>	An internal error occurred.
<b>Action</b>	Please contact your software supplier and provide the message text.
<b>INODSE2082</b>	<b>Granting port allocation lock failed with response err - int_err</b>
<b>Explanation</b>	Unexpected response received while trying to lock the port allocation lock.
<b>Action</b>	Please contact your software supplier.

<b>INODSE2084</b>	<b>Invalid port value port detected, valid port values are between portmin and portmax</b>
<b>Explanation</b>	An invalid port value was detected.
<b>Action</b>	Please specify a valid port value.
<b>INODSE2085</b>	<b>Invalid port range r1 - r2 detected, minimum min ports required in range</b>
<b>Explanation</b>	A port range has to contain a minimum number of ports.
<b>Action</b>	Please specify a valid port range.
<b>INODSE2086</b>	<b>Static port range r1 - r2 and dynamic port range r3 - r4 overlap</b>
<b>Explanation</b>	Static and dynamic port range overlap, which is not allowed.
<b>Action</b>	Please specify valid port ranges.
<b>INODSE2087</b>	<b>Port check function could not read static and / or dynamic port range</b>
<b>Explanation</b>	An error occurred while retrieving the static and dynamic port range.
<b>Action</b>	Please contact your software supplier.
<b>INODSE2088</b>	<b>The given dynamic port range r1 - r2 is not free</b>
<b>Explanation</b>	At least one port in the given dynamic port range is already in use by another server.
<b>Action</b>	Please specify a dynamic port range where no ports are used by other servers.
<b>INODSE2092</b>	<b>Internal error occurred: DSIF func [mod - line] invalid combination of parameters</b>
<b>Explanation</b>	An internal error occurred.
<b>Action</b>	Please contact your software supplier and provide the message text.
<b>INODSE2093</b>	<b>Web server webserver not registered</b>
<b>Explanation</b>	The given web server is not registered.
<b>Action</b>	Specify a registered web server.
<b>INODSE2094</b>	<b>Web server webserver not correctly registered</b>
<b>Explanation</b>	The web server is not correctly registered. Either the IP address or the port number is missing.
<b>Action</b>	Correct the web server registration.

---

<b>INODSE2095</b>	<b>Web server webserver not assigned to database dbname</b>
<b>Explanation</b>	The web server is not assigned to the database.
<b>Action</b>	Check your web server registrations.
<b>INODSE2096</b>	<b>Environment extension envext not registered for Tamino what what1</b>
<b>Explanation</b>	The environment extension is not registered in the Tamino configuration.
<b>Action</b>	No action required.
<b>INODSE2097</b>	<b>No environment extension registered for Tamino what what1</b>
<b>Explanation</b>	No environment extension registered for Tamino version or server.
<b>Action</b>	No action required.
<b>INODSE2099</b>	<b>No extension point definitions found for version version</b>
<b>Explanation</b>	No extension point definitions were found for the specified version.
<b>Action</b>	Check your configuration.
<b>INODSE2103</b>	<b>Invalid port range r1 - r2 detected</b>
<b>Explanation</b>	An invalid port range was detected.
<b>Action</b>	Specify a valid port range.
<b>INODSE2104</b>	<b>Component comp already exists for extension point extp in version vers</b>
<b>Explanation</b>	The component already exists for the extension point in the specified version.
<b>Action</b>	No action required.
<b>INODSE2105</b>	<b>Component comp already exists for extensions in version vers</b>
<b>Explanation</b>	The component already exists in the extension section of the specified version.
<b>Action</b>	No action required.
<b>INODSE2106</b>	<b>Component comp does not exist for extension point extp in version vers</b>
<b>Explanation</b>	The specified component is not defined for the given extension point and version.
<b>Action</b>	No action required.

<b>INODSE2107</b>	<b>Component comp does not exist in extensions for version vers</b>
<b>Explanation</b>	The specified component does not exist in the extensions for the given version.
<b>Action</b>	No action required.
<b>INODSE2108</b>	<b>Could not find function func for extension point extp, version vers, component comp</b>
<b>Explanation</b>	The extension point function was not found in the specified extension point library.
<b>Action</b>	Check library name, path and entry points of the extension point library.
<b>INODSE2109</b>	<b>Extension point extp does not exist in version vers</b>
<b>Explanation</b>	The specified extension point does not exist in the given version.
<b>Action</b>	No action required.
<b>INODSE2110</b>	<b>Could not load library lib for extension point extp, version vers, component comp</b>
<b>Explanation</b>	The extension point library could not be loaded via the specified path.
<b>Action</b>	Check the library name and path of the extension point definitions.
<b>INODSE2111</b>	<b>Could not allocate a port, because the static port range is full</b>
<b>Explanation</b>	No port could be allocated in the static port range, because it is full.
<b>Action</b>	Extend the static port range, use a port from outside the static port range or force reusage of a port from the static range.
<b>INODSE2114</b>	<b>Port allocation function could not read static and / or dynamic port range</b>
<b>Explanation</b>	An error occurred while retrieving the static and dynamic port range.
<b>Action</b>	Please contact your software supplier.
<b>INODSE2117</b>	<b>Granting raw section lock failed with response err - int_err</b>
<b>Explanation</b>	Unexpected response received while trying to lock the raw section lock.
<b>Action</b>	Please contact your software supplier.
<b>INODSE2121</b>	<b>Web server webserver is already registered, rename is not allowed</b>
<b>Explanation</b>	The web server specified is already registered. Therefore the rename is not allowed.
<b>Action</b>	Choose another name for the web server or delete the existing web server.

---

<b>INODSE2124</b>	<b>Internal error occurred: func [mod - line] what parameter param</b>
<b>Explanation</b>	An internal error occurred.
<b>Action</b>	Please contact your software supplier and provide the message text.
<b>INODSE2125</b>	<b>Web server webserver is already registered</b>
<b>Explanation</b>	The specified web server is already present.
<b>Action</b>	Update the web server.
<b>INODSE2126</b>	<b>database space of database server in raw section section is in use and must not be reallocated</b>
<b>Explanation</b>	The specified database spaces are in use and must not be reallocated.
<b>Action</b>	No action required.
<b>INODSE2127</b>	<b>database space of database server not present in raw section section</b>
<b>Explanation</b>	The specified database space(s) could not be found in the raw section.
<b>Action</b>	Please contact your software supplier.
<b>INODSE2129</b>	<b>pathname does not specify a regular file (returned type error)</b>
<b>Explanation</b>	The given path does not specify a regular file.
<b>Action</b>	Specify a regular file.
<b>INODSE2130</b>	<b>database space of database server in raw section section is in use and must not be deallocated</b>
<b>Explanation</b>	The specified database spaces are in use and must not be deallocated.
<b>Action</b>	No action required.
<b>INODSE2134</b>	<b>Index recreation not permitted at this item</b>
<b>Explanation</b>	This item has no data records, therefore a reinvert cannot be performed.
<b>Action</b>	Use the X-Machine programming command "admin" to recreate the index.
<b>INODSE2135</b>	<b>database space space number of server server not found</b>
<b>Explanation</b>	The specified database space could not be found.
<b>Action</b>	Correct the database space specification and try again.

**INODSE2136**      **database space of database server in raw section section is in use and must not be changed**

**Explanation**      The specified database space is in use and must not be changed.

**Action**      Ensure that the database space is not in use before changing it.

**INODSE2137**      **Database server is active, database spaces must not be moved**

**Explanation**      The database is active. Therefore database spaces must not be moved.

**Action**      Stop the database before moving any database spaces.

**INODSE2138**      **Granting container move lock failed with response err - int\_err**

**Explanation**      An unexpected response was received while trying to grant the container move lock.

**Action**      Please contact your software supplier.

**INODSE2140**      **Error while reading data reference block block into internal pool**

**Explanation**      An unexpected error occurred while reading a data reference block into the internal cache.

**Action**      Please contact your software supplier.

**INODSE2141**      **Load file has unexpected structure level lev (compatibility comp)**

**Explanation**      The input file for a data load operation has a structure level mismatch, or the file is corrupted.

**Action**      Check if the input file has the wrong structure level or is corrupted.

**INODSE2142**      **Internal error occurred: DSIF func [mod - line] invalid parameter handle (parhdl) supplied**

**Explanation**      An internal error occurred.

**Action**      Please contact your software supplier and provide the message text.

**INODSE2143**      **Server parameter "param" not available in current context**

**Explanation**      A server parameter was requested in an invalid context.

**Action**      Please contact your software supplier.

---

<b>INODSE2144</b>	<b>Invalid server parameter name "param" supplied</b>
<b>Explanation</b>	The given server parameter name is invalid.
<b>Action</b>	Specify a valid server parameter name.
<b>INODSE2145</b>	<b>Static server parameter "param" must not be changed online</b>
<b>Explanation</b>	Static server parameters must not be changed while the server is active.
<b>Action</b>	Stop the server before changing a static parameter.
<b>INODSE2157</b>	<b>Due to license restrictions, raw section access is not allowed</b>
<b>Explanation</b>	The license file does not contain the permission to access raw sections.
<b>Action</b>	Use the file system instead or obtain the required license from your software supplier.
<b>INODSE2160</b>	<b>Upgrade is not allowed for replication database</b>
<b>Explanation</b>	An upgrade is not allowed for a replication database.
<b>Action</b>	If the master database has been upgraded, the replication database must be newly created from the master backup.
<b>INODSE2162</b>	<b>Physical extent count 0 detected at typ</b>
<b>Explanation</b>	The management of physical database spaces has an empty counter.
<b>Action</b>	The database seems to be physically corrupted. Perform a restore/recover.
<b>INODSE2163</b>	<b>First Index blocksize incompatible (bls)</b>
<b>Explanation</b>	The blocksize field of first index space does not match the real blocksize.
<b>Action</b>	No action required.
<b>INODSE2164</b>	<b>Physical extent entry error (typ first - last)</b>
<b>Explanation</b>	The physical management of the database is corrupted.
<b>Action</b>	Perform a restore/recover.
<b>INODSE2167</b>	<b>Check for tape device failed on path. Check that the path is correct and whether tape is in drive.</b>
<b>Explanation</b>	It was no possible to verify that the specified path points to a tape device.
<b>Action</b>	Make sure that the path is correct, that the tape is in the drive, that the tape device is online and the tape device is properly connected to the system.

<b>INODSE2168</b>	<b>Location type mismatch - expected 'type1' , found 'type2'</b>
<b>Explanation</b>	This error can occur during 'Add Location', if the requested location type does not match the actual file type.
<b>Action</b>	Specify the correct location type.
<b>INODSE2169</b>	<b>Received response rsp (intrsp) while starting server</b>
<b>Explanation</b>	Starting the server failed.
<b>Action</b>	Please contact your software supplier.
<b>INODSE2170</b>	<b>Received response rsp (intrsp) while stopping server</b>
<b>Explanation</b>	Stopping the server failed.
<b>Action</b>	Please contact your software supplier.
<b>INODSE2173</b>	<b>Unexpected internal server error: errorstring</b>
<b>Explanation</b>	An internal server call failed with given error string.
<b>Action</b>	Please look into the server job log if there is additional error information. If not, contact your software supplier.
<b>INODSE2175</b>	<b>Unexpected internal server error: errorstring, location location</b>
<b>Explanation</b>	An internal server call failed with given error string.
<b>Action</b>	Please look into the server job log to see if there is additional error information. If not, contact your software supplier.
<b>INODSE2178</b>	<b>Doctype doctype is locked by another user</b>
<b>Explanation</b>	The doctype has a lock conflict with a running action of another user.
<b>Action</b>	Investigate which user is active and what activity is causing the lock.
<b>INODSE2179</b>	<b>Upgrade from version from_version to version to_version not supported</b>
<b>Explanation</b>	The required database conversion between the stated versions is not supported.
<b>Action</b>	Consult the documentation about possible upgrade options.

---

<b>INODSE2187</b>	<b>Cannot determine file type from path</b>
<b>Explanation</b>	An unexpected error occurred while Tamino tried to determine the file type of the displayed location.
<b>Action</b>	Check if the displayed location is accessible. If the location is accessible please contact your software supplier.
<b>INODSE2192</b>	<b>The maximum number of threads allowed per process (max_threads) is too low to start and manage the Tamino server</b>
<b>Explanation</b>	The current parameter configuration does not allow the creation of all necessary threads to start and manage the Tamino server.
<b>Action</b>	Either the system defined maximum number of threads per process is too low and should be increased, or the Tamino parameter configuration should be changed to decrease the number of threads to be created.
<b>INODSE2193</b>	<b>Insufficient system resources to create thread: thread 'name', error error returned by thread create function</b>
<b>Explanation</b>	There are not enough system resources available to create a new thread.
<b>Action</b>	There are not enough system resources available to create a new thread. The reason for that is either that the system defined maximum number of threads per process is exceeded, or that there is not enough memory available to allocate the necessary thread resources.
<b>INODSE2194</b>	<b>Restore from backup made in version old_version not supported to upgrade to new_version</b>
<b>Explanation</b>	A backup made in the old version cannot be used, e.g. because this old version is not supported any more. This only applies for databases that are already in a higher version than the backup.
<b>Action</b>	Use a more recent backup to restore the database.
<b>INODSE2200</b>	<b>Master database master dbname is not active</b>
<b>Explanation</b>	An attempt was made to execute a replication command that requires the master database to be active.
<b>Action</b>	Start the master database and retry the command.

<b>INODSE2201</b>	<b>Replication database replication dbname is active</b>
<b>Explanation</b>	An attempt was made to execute a replication command that requires the replication database to be offline.
<b>Action</b>	Stop the replication database and retry the command.
<b>INODSE2202</b>	<b>Master database must be restarted before a replication database can be set up</b>
<b>Explanation</b>	A restart of the master database is necessary.
<b>Action</b>	Restart the master database and try to set up the replication database again.
<b>INODSE2203</b>	<b>Update server sessions exist</b>
<b>Explanation</b>	The database already has update sessions so it cannot be used to replicate another database.
<b>Action</b>	Use a newly created database and retry this operation.
<b>INODSE2204</b>	<b>Replicate master database master dbname not permitted</b>
<b>Explanation</b>	Permission to replicate the master database was denied.
<b>Action</b>	Ask the administrator to permit replication access to the master database.
<b>INODSE2205</b>	<b>Inconsistency detected while setting the database to replication type</b>
<b>Explanation</b>	This database is not suitable to be set as the replication database of the specified master database. Perhaps the versions are not identical or this one was not created from the backup of the master. Also possible is that this database has its own updates after the creation.
<b>Action</b>	Use another database to replicate the master.
<b>INODSE2206</b>	<b>No permission to modify the type of the database</b>
<b>Explanation</b>	To change the type of a database to a replication database or to set it back to a normal one, the user needs to have administrator rights. Other possible reason: The database is not allowed to replicate the master database.
<b>Action</b>	Log in as administrator and try the operation again and check whether this database is in the permission list of the master database.

---

<b>INODSE2208</b>	<b>Internal error occurred: modification not allowed for replication database.</b>
<b>Explanation</b>	An internal error occurred. The server will be stopped.
<b>Action</b>	Please contact your software supplier and provide the message text.
<b>INODSE2211</b>	<b>No valid location provided for backup</b>
<b>Explanation</b>	There can be a number of reasons for this error, for example no free space or the location directory was deleted outside of Tamino. The exact reason for the error is contained in the job log.
<b>Action</b>	Study the job log to find the exact reason for the error. If the job log indicated that there is no space, free some space on the location device. Alternatively, you may provide another location for the backup.
<b>INODSE2212</b>	<b>The names of master and replication databases cannot be identical</b>
<b>Explanation</b>	Identical names have been supplied for the master and a replication database, but this is not allowed.
<b>Action</b>	Supply different names.
<b>INODSE2213</b>	<b>A former replication database cannot be set to replication type</b>
<b>Explanation</b>	After a replication database has been reset by 'Set Type to Normal Database', it cannot become a replication database any more.
<b>Action</b>	Delete the database, recreate it from a non-initial backup of the master and execute 'Set Type to Replication'.
<b>INODSE2214</b>	<b>Data field layout block rabn, invalid periodic group count count for fieldname</b>
<b>Explanation</b>	The data field layout block with the given number is corrupted.
<b>Action</b>	No action required.
<b>INODSE2215</b>	<b>Activity currently not permitted</b>
<b>Explanation</b>	This error may occur when the server is in the starting or stopping phase. During these phases the server is neither online nor offline. The other reason for this error is when the server is offline and there are some activities on the database in parallel, e.g. adding some index space.
<b>Action</b>	Wait until the server is definitely online or offline and than retry.

<b>INODSE2216</b>	<b>Operation is not permitted during a standby server session</b>
<b>Explanation</b>	The operation cannot run in parallel with another operation that requires the server to be running in standby mode.
<b>Action</b>	A standby session is used for the restore/recover operation. Wait until this operation is finished and the server is shut down.
<b>INODSE2217</b>	<b>Operation not allowed for external backup</b>
<b>Explanation</b>	An external backup is an invalid object for this operation.
<b>Action</b>	Some database operations are not allowed for external backups.
<b>INODSE2218</b>	<b>File currently locked</b>
<b>Explanation</b>	A recovery input file must not be moved because it is used by the server.
<b>Action</b>	Try to perform the operation later. A log space will be unlocked after a session switch. Other recovery input files will be unlocked after the termination of a mass load.
<b>INODSE2219</b>	<b>Savepoint not found for internal key key</b>
<b>Explanation</b>	Necessary configuration information was not found.
<b>Action</b>	Please contact your software supplier.
<b>INODSE2220</b>	<b>File filename does not exist</b>
<b>Explanation</b>	A registered backup or recovery file to be moved or deleted does not exist.
<b>Action</b>	Check the locations used for the database whether files have been lost due to unintended removal or restore operations.
<b>INODSE2221</b>	<b>File filename already exists</b>
<b>Explanation</b>	A registered backup or recovery file to be moved already exists.
<b>Action</b>	Check the locations used for the database whether files are present due to restore operations or files remaining from a deleted database.
<b>INODSE2222</b>	<b>File filename could not be moved</b>
<b>Explanation</b>	Moving a backup or recovery file failed.
<b>Action</b>	Check access control settings of the location where the file is to be moved.

---

<b>INODSE2223</b>	<b>File filename could not be removed</b>
<b>Explanation</b>	Removing a backup or recovery file failed.
<b>Action</b>	Check access control settings of the file to be deleted or of the source file to be moved.
<b>INODSE2229</b>	<b>Backup time has become invalid</b>
<b>Explanation</b>	An earlier backup was used for a restore not using the recover all option. Due to new modifications done on this base, the newer backup must not be used for restore/recover.
<b>Action</b>	Use another backup for restore/recover. The selected backup can only be used to create new database.
<b>INODSE2231</b>	<b>Cannot create initial backup</b>
<b>Explanation</b>	This error can appear during database creation. There are a number of reasons why the creation of the initial backup might fail e.g. a file with the same name already exists in the backup location, a tape is not ready (if the backup medium is tape) or no reading process is attached to a pipe (if backup medium is pipe). The root cause of the error will be given in the job log.
<b>Action</b>	Read the job log to find the root cause of the error. If there is the file with the same name as the initial backup name in the backup location on the file system, remove this file or move it to another place. If the backup medium is tape, ensure that the tape is ready. If the backup medium is a named pipe, ensure that there is a process reading from this pipe.
<b>INODSE2232</b>	<b>XML port must not be set to zero if the communication method includes native TCP/IP</b>
<b>Explanation</b>	If native TCP/IP is used as a communication method for the Tamino server the TCP/IP port used must not be set to zero.
<b>Action</b>	Use a valid port number for TCP/IP communication.
<b>INODSE2233</b>	<b>The database dbname must be online</b>
<b>Explanation</b>	The database must be started for this operation.
<b>Action</b>	Start the database.
<b>INODSE2236</b>	<b>Stopping database failed, reason: reason</b>
<b>Explanation</b>	In specific situations it is not possible to shut down the database with rolling back open transactions. This is: 1. a mass load is active 2. an external backup is active 3. there is a LOG file full situation.
<b>Action</b>	Wait until a mass load or external backup operation is finished and try again. If the log file is full, supply space for the LOG and try again.

<b>INODSE2237</b>	<b>No privilege to modify database, concurrent modifying process is currently active</b>
<b>Explanation</b>	There is another modifying job or process active or the server is within startup. Those actions must be serialized.
<b>Action</b>	Check your database state and wait until the server is up or check other modifying database actions.
<b>INODSE2241</b>	<b>Internal error occurred: DSIF func returncode returncode error error</b>
<b>Explanation</b>	This is an internal error message.
<b>Action</b>	Please contact your software supplier.
<b>INODSE2242</b>	<b>Replication instance replication dbname not found in the permission list</b>
<b>Explanation</b>	An attempt was made to remove a replication instance from the permission list which does not exist.
<b>Action</b>	Retry the command with a correct name.
<b>INODSE2243</b>	<b>Replication instance replication dbname already present in the permission list</b>
<b>Explanation</b>	An attempt was made to add a replication instance to the permission list which already exists .
<b>Action</b>	Retry the command with a correct name.
<b>INODSE2249</b>	<b>Physical file extent (extent) missing</b>
<b>Explanation</b>	The database file has been divided among more than one physical file extents. Now while processing this file the given extent is not specified.
<b>Action</b>	Specify all physical file extents.
<b>INODSE2250</b>	<b>A further extent of source cannot be created, because current file is incomplete</b>
<b>Explanation</b>	The support of multiple physical file extents requires that the current file is completely written. However with network file systems (e.g. NFS) if getting full, the current file is less in size than expected. Therefore the switch to the next location is impossible in this case. A local file system should not have those problems.
<b>Action</b>	Be sure that you have enough space at your file system because this one can only support one single file extent. Or take locally attached file systems.

---

<b>INODSE2258</b>	<b>Inconsistent usage or missing filetype file extent during processing extent extent</b>
<b>Explanation</b>	Multiple physical file extents specified by the user are not consistent. Either the extent is missing, unexpected or specified twice or the file does not come from the same database.
<b>Action</b>	Enter all required file extents and verify if they are from the same database.
<b>INODSE2263</b>	<b>(Re)Move of a single file extent is not possible because there is a reference from another database</b>
<b>Explanation</b>	If the backup consists of multiple file extents it is not possible to (re)move single extents when another database has a reference to it.
<b>Action</b>	Check which database references the backup.
<b>INODSE2264</b>	<b>Function not permitted for a replication database</b>
<b>Explanation</b>	An administration function could not be executed because it must not be used for a replication database.
<b>Action</b>	Check whether the function is to be executed for the master database.
<b>INODSE2265</b>	<b>Database is inconsistent and cannot be used</b>
<b>Explanation</b>	During migration or restore/recover, the database is in an undefined state which cannot be solved. The database cannot be started anymore.
<b>Action</b>	Recover from the latest valid backup or if not possible contact your software supplier.
<b>INODSE2268</b>	<b>Database refused startup after conversion</b>
<b>Explanation</b>	During migration the database cannot be started because of an internal error.
<b>Action</b>	View the server's startup text file (inosrv.txt) for more information.
<b>INODSE2274</b>	<b>Server died during startup</b>
<b>Explanation</b>	The server died during the startup phase.
<b>Action</b>	Inspect the server output file and correct the error.
<b>INODSE2275</b>	<b>Property propertyname must not be changed for read only / replication database</b>
<b>Explanation</b>	The operation mode of the database is not suited for changes in this property. Changing it would jeopardize the database consistency.
<b>Action</b>	For a read only database, if you really want to change the parameter, set the "read only" property to "no", modify the parameter, start the database, stop the database, set "read only" property to "yes".

<b>INODSE2279</b>	<b>Invalid version version of the conversion component</b>
<b>Explanation</b>	There is no conversion utility of the most recent version found.
<b>Action</b>	Upgrade the conversion only to the current one.
<b>INODSE2282</b>	<b>Open of source (path) has failed due to operating system error errno (errtxt)</b>
<b>Explanation</b>	The file specified cannot be opened due to an internal operating system error.
<b>Action</b>	Consult the manufacturer's manual.
<b>INODSE2283</b>	<b>io error error (errtxt) on block block no in database space space no</b>
<b>Explanation</b>	An I/O error has occurred on the given database space.
<b>Action</b>	Analyse the internal operating system error.
<b>INODSE2285</b>	<b>Creation of database space space no (path) has failed due to system error errno (errtxt)</b>
<b>Explanation</b>	A database space could not be created because of an operating system error.
<b>Action</b>	Analyse the system error and consult the manufacturer's manual.
<b>INODSE2289</b>	<b>Due to license restrictions, usage of replication management functions is not permitted</b>
<b>Explanation</b>	Your license does not permit usage of replication databases.
<b>Action</b>	Contact your software supplier for an upgrade of your license.
<b>INODSE2290</b>	<b>Due to license restrictions, server startup for replication database database name is not permitted</b>
<b>Explanation</b>	Your license does not permit usage of replication databases.
<b>Action</b>	Contact your software supplier for an upgrade of your license.
<b>INODSE2291</b>	<b>Due to license restrictions, server startup of database name as a master for replication databases is not permitted</b>
<b>Explanation</b>	Your license does not permit usage of replication databases.
<b>Action</b>	Contact your software supplier for an upgrade of your license.

---

<b>INODSE2293</b>	<b>Due to license restrictions, set version for replication master database dbname is not permitted</b>
<b>Explanation</b>	Your license does not permit usage of replication databases.
<b>Action</b>	Remove all databases from the master database's replication database table or contact your software supplier for an upgrade of your license.
<b>INODSE2298</b>	<b>Cannot establish connection to server</b>
<b>Explanation</b>	The utility cannot connect the server which is assumed to be online. Note that the communication goes over XTS.
<b>Action</b>	Check if the database is reachable over the XTS directory service. If you cannot find the reason switch on the XTS tracing facility.
<b>INODSE2340</b>	<b>Communication error when trying to contact server servername</b>
<b>Explanation</b>	An error was returned from the communication interface when trying to contact the server.
<b>Action</b>	Check whether the communication component is set up correctly and the communication process (e.g. Software AG XTS Directory Server) is running.
<b>INODSE2341</b>	<b>The last backup available must not be deleted</b>
<b>Explanation</b>	The last backup available must not be deleted because in the case of a database crash no restore is possible.
<b>Action</b>	No action required.
<b>INODSE2342</b>	<b>No valid location or directory specified</b>
<b>Explanation</b>	To create a backup, either a valid location or directory must be specified.
<b>Action</b>	Specify a valid location or directory.
<b>INODSE4055</b>	<b>Block size mismatch detected on database_space</b>
<b>Explanation</b>	A block size mismatch has been detected on the specified database space.
<b>Action</b>	Ensure that the block size of the database space to be restored is the same as that in the backup copy.

<b>INODSE4058</b>	<b>Database space storage (container) exhausted</b>
<b>Explanation</b>	The storage for database space is exhausted.
<b>Action</b>	Try to allocate more storage; if this is not possible contact your software supplier.
<b>INODSE4100</b>	<b>Failure accessing file</b>
<b>Explanation</b>	An error has occurred accessing a Tamino file. The file may possibly be corrupt.
<b>Action</b>	Check that it is the correct file and repeat the operation. If the error persists, contact your software supplier.
<b>INODSE4109</b>	<b>Failure calling external backup</b>
<b>Explanation</b>	Tamino could not start external backup processing.
<b>Action</b>	Check that the third party hardware and drivers are installed and working correctly. If the symptoms persist, contact your software supplier.
<b>INODSE4110</b>	<b>Failed to retrieve number of backup generations from internal configuration store</b>
<b>Explanation</b>	There is possibly a corruption of the internal configuration store.
<b>Action</b>	If the symptoms persist, contact your software supplier.
<b>INODSE4111</b>	<b>Failed to remove oldest savepoint information from internal configuration store.</b>
<b>Explanation</b>	There is possibly a corruption of the internal configuration store.
<b>Action</b>	If the symptoms persist, contact your software supplier.
<b>INODSE4113</b>	<b>Failed to retrieve server version</b>
<b>Explanation</b>	There is possibly a corruption of the internal configuration store.
<b>Action</b>	If the symptoms persist, contact your software supplier.
<b>INODSE4114</b>	<b>Failed to enumerate savepoint information</b>
<b>Explanation</b>	There is possibly a corruption of the internal configuration store.
<b>Action</b>	If the symptoms persist, contact your software supplier.
<b>INODSE4118</b>	<b>Failed to downgrade database</b>
<b>Explanation</b>	There is a problem with the database downgrade utility.
<b>Action</b>	If the symptoms persist, contact your software supplier.

---

<b>INODSE4120</b>	<b>Failed to execute inodmp utility</b>
<b>Explanation</b>	The Create/Backup/Restore utility cannot be executed, possibly due to a corruption in the internal configuration store.
<b>Action</b>	If the symptoms persist, contact your software supplier.
<b>INODSE4121</b>	<b>External Restore failed</b>
<b>Explanation</b>	Tamino could not start external restore processing.
<b>Action</b>	Check that the third party hardware and drivers are installed and working correctly. If the symptoms persist, contact your software supplier.
<b>INODSE4122</b>	<b>Failed to retrieve database identity</b>
<b>Explanation</b>	There is possibly a corruption of the internal configuration store.
<b>Action</b>	If the symptoms persist, contact your software supplier.
<b>INODSE5251</b>	<b>An inodmp client terminated with unexpected error err</b>
<b>Explanation</b>	Within parallel backup a client process of the dump utility terminated unexpectedly.
<b>Action</b>	The error value defines the exit code of the client process. There are generally additional error messages describing the situation in detail. Ask your software supplier for the reason of the given error.
<b>INODSE5261</b>	<b>Invalid or unsupported character set charset</b>
<b>Explanation</b>	The specified character set is not supported by the current software version.
<b>Action</b>	Check for possible typing errors in character set name.
<b>INODSE5267</b>	<b>Software configuration error</b>
<b>Explanation</b>	The Tamino software components that you are using are not compatible.
<b>Action</b>	Please request a new version of Tamino from your software supplier.
<b>INODSE5268</b>	<b>Failed to register server with the Software AG XTS Directory Server: why</b>
<b>Explanation</b>	The database server failed to register with the Software AG XTS Directory Server. The error returned from the XTS layer is displayed as part of the message.
<b>Action</b>	Fix the error situation described by the XTS message or contact your software supplier.

- INODSE5271**      **Failed to create the Software AG XTS Directory Server entries: why**  
**Explanation**      The server failed to create the necessary Software AG XTS Directory Server entries and the server startup failed. The reason for the failure is returned by the XTS layer.  
**Action**              Please check that the service "Software AG XTS Directory Server" is running. If not, please start it. On Windows this can be done using the Control Panel. On UNIX please use the scripts provided (which are normally executed at system start). If the service was running when the error occurred, and the XTS message does not specify enough details to fix the problem, please contact your software supplier.
- INODSE5272**      **Parameter setting for the Software AG XTS Directory Server failed: why**  
**Explanation**      The server failed to do the necessary parameter setting for the Software AG XTS Directory Server and the server startup failed. The reason for the failure is returned by the XTS layer.  
**Action**              Fix the error situation described by the XTS message or contact your software supplier.
- INODSE5283**      **Invalid parent field format for collation descriptor**  
**Explanation**      The format for the parent field of a collation descriptor is invalid. The only allowed parent formats are "wide" and "alphanumeric".  
**Action**              Check the collation descriptor definition.
- INODSE5287**      **Invalid collation locale s**  
**Explanation**      The locale name is misspelled or the locale is not supported.  
**Action**              Check the spelling.
- INODSE5300**      **Filename for database space container could not be determined**  
**Explanation**      It was not possible to determine the full filename for the specified database space.  
**Action**              This is an internal error. Please contact your software supplier.
- INODSE5309**      **Key id could not be changed, msg**  
**Explanation**      An internal error occurred changing a key value in the internal configuration store.  
**Action**              Please contact your software supplier.

---

<b>INODSE5310</b>	<b>Database name name could not be changed in the internal configuration store, msg</b>
<b>Explanation</b>	Because of an internal error the internal configuration could not be changed.
<b>Action</b>	Please contact your software supplier.
<b>INODSE5320</b>	<b>Database ID could not be determined, msg</b>
<b>Explanation</b>	Internal error, while requesting database ID information.
<b>Action</b>	Contact your software supplier.
<b>INODSE5321</b>	<b>Database name could not be determined, msg</b>
<b>Explanation</b>	Internal error, while requesting database name information.
<b>Action</b>	Please contact your software supplier.
<b>INODSE5334</b>	<b>Unable to get collator version for locale locale</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INODSE5335</b>	<b>Collation version does not match</b>
<b>Explanation</b>	Most probably, a newer version of the ICU library has been installed and old data is not available In this case, all collating indexes must be rebuilt.
<b>Action</b>	Rebuild the collating index.
<b>INODSE5336</b>	<b>Internal ICU error (error_text) occurred while producing collation key</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INODSE5337</b>	<b>Unable to determine server state</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INODSE5341</b>	<b>Database database name already exists</b>
<b>Explanation</b>	This error can occur during database creation, or when trying to rename an existing database and a database with the same name already exists.
<b>Action</b>	Specify another name.

<b>INODSE5343</b>	<b>External backup failed, reason: reason errcode</b>
<b>Explanation</b>	The attempt to perform an external database backup failed due to the reason specified in the message.
<b>Action</b>	Correct the error indicated and retry the operation.
<b>INODSE5344</b>	<b>External restore failed, reason: reason errcode</b>
<b>Explanation</b>	A database restore with a connected external system failed due to the reason specified in the message.
<b>Action</b>	Correct the error indicated and retry the operation.
<b>INODSE5345</b>	<b>External delete failed, reason: reason errcode</b>
<b>Explanation</b>	The call to delete an external backup failed due to the reason given.
<b>Action</b>	Correct the error indicated and retry the operation.
<b>INODSE5346</b>	<b>EMC request failed: text</b>
<b>Explanation</b>	A call of EMC's SYMAPI failed for the given reason.
<b>Action</b>	Correct the error indicated and retry the operation.
<b>INODSE5354</b>	<b>External backup configuration error, reason: reason</b>
<b>Explanation</b>	Configuring the environment for an external backup failed.
<b>Action</b>	Correct the error indicated and retry the operation.
<b>INODSE5358</b>	<b>Set version already running on this database</b>
<b>Explanation</b>	The "Set version" operation is already running on this database.
<b>Action</b>	Wait for the "set version" operation to complete.
<b>INODSE5359</b>	<b>Function is not permitted because of pending transactions</b>
<b>Explanation</b>	The function cannot be processed because of pending global transactions.
<b>Action</b>	Start the Tamino server in normal mode and close the pending global transactions.
<b>INODSE5360</b>	<b>Function is not permitted because the previous session was abnormally terminated</b>
<b>Explanation</b>	The function cannot be processed because the previous session was abnormally terminated.
<b>Action</b>	Start the Tamino server in normal mode to do an autorepair from the abnormal termination.

---

<b>INODSE5361</b>	<b>Downgrade to version version not supported</b>
<b>Explanation</b>	This message can appear when trying to convert a database to a previous version, but the requested downgrade is not supported.
<b>Action</b>	No action required.
<b>INODSE5402</b>	<b>Maximum number of users exceeded</b>
<b>Explanation</b>	A new user was rejected due to internal reasons.
<b>Action</b>	You can force a memory dump with "inodba database=name trap=9228" for further analysis after reproducing the error.
<b>INODSE5404</b>	<b>Insufficient temporary work space</b>
<b>Explanation</b>	The temporary work space was too small to execute the requested function.
<b>Action</b>	Consider increasing the temporary workspace by adding locations with free space to the temporary working location.
<b>INODSE5405</b>	<b>Insufficient temporary work space</b>
<b>Explanation</b>	The temporary work space was too small to execute the requested function.
<b>Action</b>	Consider increasing the temporary workspace.
<b>INODSE5406</b>	<b>Transaction internally aborted</b>
<b>Explanation</b>	A transaction has been aborted due to internal reasons. All changes of this transaction have been undone.
<b>Action</b>	You can force a memory dump with "inodba database=name trap=9291" for further analysis after reproducing the error.
<b>INODSE5407</b>	<b>Database is corrupt, invalid block block</b>
<b>Explanation</b>	There are structural inconsistencies in the database. The database should not be used any longer.
<b>Action</b>	Restore the database from a backup copy and apply the log files. You can force a memory dump with "inodba database=name trap=9130" for further analysis after reproducing the error.

<b>INODSE5408</b>	<b>buffer pool overflow</b>
<b>Explanation</b>	The current load could not be processed because the buffer pool is too small.
<b>Action</b>	Consider increasing the buffer pool size or force a memory dump with "inodba database=name trap=9138" for further analysis after reproducing the error.
<b>INODSE5410</b>	<b>Database is corrupt, data block damaged</b>
<b>Explanation</b>	There are structural inconsistencies in the database. The database should not be used any longer.
<b>Action</b>	Restore the database from a backup copy and apply the log files. You can force a memory dump with "inodba database=name trap=9127" for further analysis after reproducing the error.
<b>INODSE5411</b>	<b>Database is corrupt</b>
<b>Explanation</b>	There are structural inconsistencies in the database. The database should not be used any longer.
<b>Action</b>	Restore the database from a backup copy and apply the log files. You can force a memory dump with "inodba database=name trap=9123" for further analysis after reproducing the error.
<b>INODSE5416</b>	<b>Database is corrupt, physical structures damaged</b>
<b>Explanation</b>	There are structural inconsistencies in the database. The database should not be used any longer.
<b>Action</b>	Restore the database from a backup copy and apply the log files. You can force a memory dump with "inodba database=name trap=9057" for further analysis after reproducing the error.
<b>INODSE5417</b>	<b>Database is corrupt, allocation error detected</b>
<b>Explanation</b>	There are structural inconsistencies in the database. The database should not be used any longer.
<b>Action</b>	Restore the database from a backup copy and apply the log files. You can force a memory dump with "inodba database=name trap=9058" for further analysis after reproducing the error.
<b>INODSF1008</b>	<b>The location of the license file could not be found</b>
<b>Explanation</b>	The Tamino Server requires a valid license file. The location of the license file could not be determined.
<b>Action</b>	Contact your software supplier.

---

<b>INODSF1011</b>	<b>The license of Tamino has expired</b>
<b>Explanation</b>	The licensing period of Tamino has expired.
<b>Action</b>	Please contact your software supplier for a renewal of your license.
<b>INODSF1012</b>	<b>The version of Tamino and the version used in the license file do not match</b>
<b>Explanation</b>	The Tamino product version and the version used in the license file must match.
<b>Action</b>	Use the license file that has been shipped with your product version.
<b>INODSF1018</b>	<b>Database creation has failed due to license restrictions. Licensed database size is licsize MB, attempted dataspace container size is datasize MB.</b>
<b>Explanation</b>	The dataspace size of a database is limited by the amount given in your current license.
<b>Action</b>	Create a database with a smaller dataspace size.
<b>INODSF1020</b>	<b>Error error accessing the raw section section via mode</b>
<b>Explanation</b>	Accessing the raw section failed due to an unexpected system response.
<b>Action</b>	Please consult your manufacturer's manual.
<b>INODSF1021</b>	<b>Verification error on raw section section (structure level mismatch)</b>
<b>Explanation</b>	An error occurred while verifying the structure level in the raw section management structure.
<b>Action</b>	Please contact your software supplier.
<b>INODSF1022</b>	<b>Verification error on raw section section (wrong architecture byte)</b>
<b>Explanation</b>	An error occurred while verifying the architecture byte in the raw section management structure.
<b>Action</b>	Please contact your software supplier.
<b>INODSF1023</b>	<b>Verification error on raw section section (section management header)</b>
<b>Explanation</b>	An error occurred while verifying the management header in the raw section management structure.
<b>Action</b>	Please contact your software supplier.

<b>INODSF1024</b>	<b>Raw section section is not initialized</b>
<b>Explanation</b>	The raw section is not initialized.
<b>Action</b>	Please initialize the raw section.
<b>INODSF1062</b>	<b>Replacing the license file after expiration failed</b>
<b>Explanation</b>	Replacing the license file after expiration failed.
<b>Action</b>	Provide a valid license to be able to start the server.
<b>INODSF1180</b>	<b>The operating system is not specified within the license file</b>
<b>Explanation</b>	Check operating systems specification in the license file.
<b>Action</b>	Verify that the license file is valid for the operating system used.
<b>INODSF1250</b>	<b>Open of source (path) has failed due to an incompatible file or a compatibility mismatch</b>
<b>Explanation</b>	The file could not be opened because it either does not have the expected compatibility level or a subsequent file extent does not match the previously opened one.
<b>Action</b>	Check that the correct file has been specified for the operation or if 2 physical file extents belong to each other.
<b>INODSF1251</b>	<b>Internal error error occurred</b>
<b>Explanation</b>	An internal error has caused the server to stop.
<b>Action</b>	Please contact your software supplier. Restart the server.
<b>INODSF1254</b>	<b>Unexpected signal signal received in text index procedure call from thread thread</b>
<b>Explanation</b>	An unexpected exception or signal has occurred.
<b>Action</b>	If the exception or the signal was asynchronous (i.e. no access violation etc.), repeat the operation.
<b>INODSF1255</b>	<b>Index too deep</b>
<b>Explanation</b>	The index structure exceeds the maximum levels of indexing supported.
<b>Action</b>	Please contact your software supplier.

---

<b>INODSF1256</b>	<b>Internal error on doctype doctype: second error caused by failed recovery due to the following error: first error</b>
<b>Explanation</b>	An error occurred on the specified doctype. While trying to undo the changes on the doctype, another error has occurred. The server must terminate in order to prevent the database from being corrupted.
<b>Action</b>	Restart the server.
<b>INODSF1257</b>	<b>Log space full</b>
<b>Explanation</b>	The server session has been abnormally terminated because there is no space left for logging.
<b>Action</b>	Provide space for logging and restart the server.
<b>INODSF1259</b>	<b>Error closing a log space: error message</b>
<b>Explanation</b>	The log space could not be closed properly. The server session is aborting.
<b>Action</b>	Try to fix the reason for the error. It is recommended to back up the database. Restart the server.
<b>INODSF1260</b>	<b>Error on doctype doctype during rollback transaction: rspmsg</b>
<b>Explanation</b>	An error occurred during the rollback of a transaction. The server must terminate in order to prevent the database from being corrupted.
<b>Action</b>	Restart the server.
<b>INODSF1261</b>	<b>Assertion failed: assertion</b>
<b>Explanation</b>	A coding error has occurred.
<b>Action</b>	Please inform your software supplier. Restart the server.
<b>INODSF1262</b>	<b>Open of source (path) has failed due to an incorrect file type</b>
<b>Explanation</b>	The file could not be opened because it does not have the expected type. It is possible that the file is internally corrupted. For example there is an index space with entirely binary zeroes in it.
<b>Action</b>	Check that the correct file has been specified for the operation.

<b>INODSF1263</b>	<b>Error error number has occurred in SMP initialization.</b>
<b>Explanation</b>	An internal error has occurred. The server has stopped.
<b>Action</b>	Please contact your software supplier.
<b>INODSF1264</b>	<b>Setting the maximum number of resources to value has failed. Server stopped.</b>
<b>Explanation</b>	The requested system resources were not available.
<b>Action</b>	Check your system configuration.
<b>INODSF1265</b>	<b>Server already active</b>
<b>Explanation</b>	There is another server running for the current database.
<b>Action</b>	Please contact your software supplier.
<b>INODSF1266</b>	<b>Error error number during synchronization call in line line (address address)</b>
<b>Explanation</b>	An internal error has occurred. The server has been stopped.
<b>Action</b>	Please contact your software supplier.
<b>INODSF1267</b>	<b>SMP resource allocation failed with response rsp at line line</b>
<b>Explanation</b>	An internal error has occurred. The server has been stopped.
<b>Action</b>	Please contact your software supplier.
<b>INODSF1268</b>	<b>Error error number during synchronization call in line line</b>
<b>Explanation</b>	An internal error has occurred. The server has been stopped.
<b>Action</b>	Please contact your software supplier.
<b>INODSF1269</b>	<b>Increasing the number of resources by value has failed. Server stopped.</b>
<b>Explanation</b>	The requested system resources were not available.
<b>Action</b>	Check your system configuration.
<b>INODSF1270</b>	<b>Invalid value (value) found at location location</b>
<b>Explanation</b>	An internal error has caused the server to stop.
<b>Action</b>	Please contact your software supplier. Restart the server.

---

<b>INODSF1271</b>	<b>Invalid pointer (value) found at location location</b>
<b>Explanation</b>	An internal error has caused the server to stop.
<b>Action</b>	Please contact your software supplier. Restart the server.
<b>INODSF1272</b>	<b>Internal error error string occurred at location location</b>
<b>Explanation</b>	An internal error has caused the server to stop.
<b>Action</b>	Please contact your software supplier. Restart the server.
<b>INODSF1273</b>	<b>Invalid value (int value) found at location location</b>
<b>Explanation</b>	An internal error has caused the server to stop.
<b>Action</b>	Please contact your software supplier. Restart the server.
<b>INODSF1274</b>	<b>Internal error in block block number occurred at location location</b>
<b>Explanation</b>	An internal error has caused the server to stop.
<b>Action</b>	Please contact your software supplier. Restart the server.
<b>INODSF1275</b>	<b>Invalid value (int value) found on address address at location location</b>
<b>Explanation</b>	An internal error has caused the server to stop.
<b>Action</b>	Please contact your software supplier. Restart the server.
<b>INODSF1276</b>	<b>Invalid values (value 1, value 2) found on address address at location location</b>
<b>Explanation</b>	An internal error has caused the server to stop.
<b>Action</b>	Please contact your software supplier. Restart the server.
<b>INODSF1277</b>	<b>Invalid values (value1, value2) found at location location</b>
<b>Explanation</b>	An internal error has caused the server to stop.
<b>Action</b>	Please contact your software supplier. Restart the server.
<b>INODSF1278</b>	<b>Invalid value (value) found in block block number at location location</b>
<b>Explanation</b>	An internal error has caused the server to stop.
<b>Action</b>	Please contact your software supplier. Restart the server.

<b>INODSF1279</b>	<b>Invalid value (value) found on address address at location location</b>
<b>Explanation</b>	An internal error has caused the server to stop.
<b>Action</b>	Please contact your software supplier. Restart the server.
<b>INODSF1280</b>	<b>Internal error location-c1-c2 occurred</b>
<b>Explanation</b>	An internal error has caused the server to stop.
<b>Action</b>	Please contact your software supplier. Restart the server.
<b>INODSF1282</b>	<b>Received response rsp (intrsp) while loading function(s) for extension point extp</b>
<b>Explanation</b>	Loading a function for an extension point failed.
<b>Action</b>	Please contact your software supplier.
<b>INODSF1283</b>	<b>Internal communication initialization failed</b>
<b>Explanation</b>	The server's internal communication could not be activated.
<b>Action</b>	Please contact your software supplier.
<b>INODSF1284</b>	<b>Internal memory management could not be initialized</b>
<b>Explanation</b>	The initialization of the server's memory management has failed.
<b>Action</b>	Please contact your software supplier.
<b>INODSF1285</b>	<b>Temporary working space could not be allocated</b>
<b>Explanation</b>	The allocation of the working space needed for server operation has failed.
<b>Action</b>	Please contact your software supplier.
<b>INODSF1286</b>	<b>Buffer pool too small. At least minimum value bytes required.</b>
<b>Explanation</b>	The defined buffer pool is too small for the server to start.
<b>Action</b>	Increase the buffer pool parameter and restart the server.
<b>INODSF1287</b>	<b>Buffer pool too small to start the server (internal reason reason)</b>
<b>Explanation</b>	The defined buffer pool is too small for the server to start.
<b>Action</b>	Increase the buffer pool parameter and restart the server.

<b>INODSF1288</b>	<b>Server for this database already active</b>
<b>Explanation</b>	There is already an active server for the same database or at least some resources of the previous server run have not been released yet.
<b>Action</b>	If there is no active server and you cannot determine which resources may cause the conflict, contact your software supplier.
<b>INODSF1291</b>	<b>Not enough memory available to execute process</b>
<b>Explanation</b>	The operating system did not have enough resources to run another process. Possible reasons are too many concurrently active processes or a too small swap/paging space.
<b>Action</b>	Please check the resource usage and the configuration of your computer.
<b>INODSF1296</b>	<b>source (path) is corrupted at offset</b>
<b>Explanation</b>	The data cannot be used.
<b>Action</b>	Please contact your software supplier.
<b>INODSF1297</b>	<b>Creation of source (path) has failed</b>
<b>Explanation</b>	The file could not be created at the specified location.
<b>Action</b>	Look for other error messages to find the reason for the failure.
<b>INODSF1298</b>	<b>source (path) could not be opened: device type not supported</b>
<b>Explanation</b>	An invalid device type was chosen.
<b>Action</b>	Choose a valid device type.
<b>INODSF1299</b>	<b>Open of source (path) has failed due to operating system error errno</b>
<b>Explanation</b>	The file could not be opened.
<b>Action</b>	Please consult the manufacturer's manual.
<b>INODSF1300</b>	<b>Open of source (path) has failed due to an invalid structure</b>
<b>Explanation</b>	The file could not be opened because it does not have the expected structure.
<b>Action</b>	Check if the file origin is the same machine architecture. If you cannot detect the error, please contact your software supplier.

<b>INODSF1301</b>	<b>Open of source (path) has failed. Missing extents or wrong sequence of extents. Please check and retry.</b>
<b>Explanation</b>	The file could not be opened because the sequence in which devices are given (e.g. tapes) is not correct or not all sequences required were specified.
<b>Action</b>	Specify all extents in the correct sequence.
<b>INODSF1302</b>	<b>Open of log space (path) has failed because sequence of log spaces is incorrect</b>
<b>Explanation</b>	The file could not be opened because the sequence in which log spaces are given (e.g. tapes) is not correct.
<b>Action</b>	Use the correct sequence.
<b>INODSF1303</b>	<b>Open of source (path) has failed due to an incorrect file type</b>
<b>Explanation</b>	The file could not be opened because it does not have the expected type.
<b>Action</b>	Check that the correct file has been specified for the operation.
<b>INODSF1305</b>	<b>Open of source has failed due to invalid or missing internal information</b>
<b>Explanation</b>	The file could not be opened because its location was not specified.
<b>Action</b>	Check the database parameters.
<b>INODSF1306</b>	<b>Internal error location occurred: Please report r t h c</b>
<b>Explanation</b>	An internal error has caused the server to stop.
<b>Action</b>	Please contact your software supplier and report the values given with the message. Restart the server.
<b>INODSF1307</b>	<b>Database database name not registered</b>
<b>Explanation</b>	The specified database has not been properly created or the internal entries of this database have been destroyed.
<b>Action</b>	Create the database again.
<b>INODSF1308</b>	<b>Executable name not found</b>
<b>Explanation</b>	The system could not find the executable object specified.
<b>Action</b>	Please check your installation.

---

<b>INODSF1309</b>	<b>System error errno occurred during the creation of another process</b>
<b>Explanation</b>	The system could not create another process. You might have exceeded the amount of available memory or the maximum number of processes.
<b>Action</b>	Please increase the amount of virtual memory available, or increase the number of possible processes. Please refer to the manual of your operating system for details.
<b>INODSF1310</b>	<b>Invalid value (value) found at location location</b>
<b>Explanation</b>	An internal error has caused the server to stop.
<b>Action</b>	Please contact your software supplier. Restart the server.
<b>INODSF1311</b>	<b>Error errno has been signalled during the execution of an asynchronous I/O on log space for id</b>
<b>Explanation</b>	An asynchronous I/O has failed due to an operating system error.
<b>Action</b>	Check for problems with the device. Check whether the device is off-line or read-only. In the case of a logical volume, try to access all of its physical devices by operating system commands. Check the system log file for appropriate error messages.
<b>INODSF1312</b>	<b>Error errno has been signalled during the execution of an asynchronous I/O on journal space for id</b>
<b>Explanation</b>	An asynchronous I/O has failed due to an operating system error.
<b>Action</b>	Check for problems with the device. Check whether the device is off-line or read-only. In the case of a logical volume, try to access all of its physical devices by operating system commands. Check the system log file for appropriate error messages.
<b>INODSF1313</b>	<b>Error errno has been signalled during the execution of an asynchronous I/O for id</b>
<b>Explanation</b>	An asynchronous I/O has failed due to an operating system error.
<b>Action</b>	Check for problems with the device. Check whether the device is off-line or read-only. In the case of a logical volume, try to access all of its physical devices by operating system commands. Check the system log file for appropriate error messages.
<b>INODSF1317</b>	<b>Semaphore could not be created because system limit was reached</b>
<b>Explanation</b>	The system limit for semaphores was reached.
<b>Action</b>	Increase the number of semaphores supported by the operating system.

<b>INODSF1319</b>	<b>Unexpected signal signal received</b>
<b>Explanation</b>	An unexpected exception or signal has occurred.
<b>Action</b>	If the exception or the signal was asynchronous (i.e. no access violation etc.), repeat the operation.
<b>INODSF1321</b>	<b>Error opening sequential file: error</b>
<b>Explanation</b>	An error occurred when opening a sequential file.
<b>Action</b>	Correct the reason for the sequential file open failure and retry the operation.
<b>INODSF1322</b>	<b>Latest savepoint not found</b>
<b>Explanation</b>	Internal information about the latest savepoint could not be found.
<b>Action</b>	Contact your software supplier.
<b>INODSF1323</b>	<b>Path or type of log location not found</b>
<b>Explanation</b>	The internal information for the log location, path or type could not be found.
<b>Action</b>	Contact your software supplier.
<b>INODSF1324</b>	<b>Processing information for a log space is undefined</b>
<b>Explanation</b>	A previous server session process was killed during restore/recover.
<b>Action</b>	Use a later backup if possible or use a recover until a timestamp that is less than the creation date of the log space in question.
<b>INODSF1325</b>	<b>Signal signal number caught. Termination initiated.</b>
<b>Explanation</b>	An unexpected signal was caught. This leads to an immediate termination.
<b>Action</b>	If the signal cannot be explained by the environment (operator initiated or operating system initiated signal), please contact your software supplier.
<b>INODSF1326</b>	<b>database creation not completed</b>
<b>Explanation</b>	The database creation is not finished, or terminated unexpectedly, leaving the database files on disk.
<b>Action</b>	Check if the creation is still in progress. If so, wait until completed. If not, clean up and restart the database creation.

---

<b>INODSF1328</b>	<b>Unexpected buffer pool error</b>
<b>Explanation</b>	An unexpected error has occurred when trying to access the buffer pool.
<b>Action</b>	Repeat the action. If it still fails, contact your support center.
<b>INODSF1329</b>	<b>Unexpected error getting a page from the buffer pool</b>
<b>Explanation</b>	An unexpected error has occurred when trying to get a page from the buffer pool. The operation was cancelled.
<b>Action</b>	Contact your software supplier.
<b>INODSF1330</b>	<b>An unexpected I/O error has occurred</b>
<b>Explanation</b>	An unexpected I/O error has occurred. The operation was cancelled.
<b>Action</b>	Contact your software supplier.
<b>INODSF1331</b>	<b>Unable to extend database space. Reason: ret_code.</b>
<b>Explanation</b>	The specified error has occurred while trying to extend a database space.
<b>Action</b>	Determine the reason for the error code, and retry the operation.
<b>INODSF1332</b>	<b>Index chain is corrupt</b>
<b>Explanation</b>	Corruption has been found for an index on a doctype.
<b>Action</b>	The indexes have to be rebuilt. To rebuild the indexes, choose the "Check and Repair" function for the database in the Tamino Manager, then retry the operation.
<b>INODSF1334</b>	<b>No index summary in input file</b>
<b>Explanation</b>	The input file does not have the required index definitions.
<b>Action</b>	Ensure that the correct input file has been specified.
<b>INODSF1335</b>	<b>No streams available</b>
<b>Explanation</b>	Multi-file mode is being used but no streams are available.
<b>Action</b>	Please contact your software supplier.
<b>INODSF1336</b>	<b>Cannot handle given extent type</b>
<b>Explanation</b>	It is not possible to handle the type of extent specified.
<b>Action</b>	This is an internal error. Please contact your software supplier.

<b>INODSF1337</b>	<b>Shared memory segment of server exists</b>
<b>Explanation</b>	At least one shared memory segment of the server already exists.
<b>Action</b>	Check if the server is already active. If not retry the operation. If the error persists remove the existing shared memory segment and retry.
<b>INODSF1341</b>	<b>Error on temporary storage space</b>
<b>Explanation</b>	An error has occurred when trying to write to a temporary storage space.
<b>Action</b>	Ensure that there are no errors on the device where temporary space is to be used and retry the operation.
<b>INODSF1342</b>	<b>No space for index space</b>
<b>Explanation</b>	There are not enough system resources available for the index space.
<b>Action</b>	Allocate sufficient resources to allow the operation to succeed.
<b>INODSF1343</b>	<b>Error opening data space</b>
<b>Explanation</b>	An error has occurred while opening the data space.
<b>Action</b>	Correct the error and retry the operation.
<b>INODSF1344</b>	<b>Error opening journal space</b>
<b>Explanation</b>	An error has occurred while opening the journal space.
<b>Action</b>	Correct the error and retry the operation.
<b>INODSF1345</b>	<b>Internal error: Provided memory not sufficient</b>
<b>Explanation</b>	An area in memory used as working space was defined too small.
<b>Action</b>	Please contact your software supplier.
<b>INODSF1346</b>	<b>No input slot could be allocated</b>
<b>Explanation</b>	An internal error occurred preventing an input slot being allocated for an index.
<b>Action</b>	Please contact your software supplier.
<b>INODSF1347</b>	<b>No space for preserved slot</b>
<b>Explanation</b>	An internal error occurred preventing a preserved slot being allocated for an index.
<b>Action</b>	Please contact your software supplier.

---

<b>INODSF1348</b>	<b>Invalid database space</b>
<b>Explanation</b>	An internal error occurred.
<b>Action</b>	Please contact your software supplier.
<b>INODSF1349</b>	<b>Error while reading index</b>
<b>Explanation</b>	An internal error occurred while reading the index.
<b>Action</b>	Please contact your software supplier.
<b>INODSF1350</b>	<b>No more temporary space</b>
<b>Explanation</b>	Temporary space has been exhausted.
<b>Action</b>	Ensure that there is enough free space to allocate the required temporary space.
<b>INODSF1351</b>	<b>No slot available</b>
<b>Explanation</b>	An internal error occurred when trying to write to a slot.
<b>Action</b>	Please contact your software supplier.
<b>INODSF1353</b>	<b>More than one block to be written (number)</b>
<b>Explanation</b>	A disk write failed because more than one block was requested to be written. This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INODSF1354</b>	<b>Utility not permitted to run</b>
<b>Explanation</b>	This utility is currently not permitted to run.
<b>Action</b>	Wait until the database is available again.
<b>INODSF1355</b>	<b>Internal sort error</b>
<b>Explanation</b>	An internal sort error has occurred.
<b>Action</b>	Please contact your software supplier.
<b>INODSF1356</b>	<b>Internal error occurred: utility entry not found</b>
<b>Explanation</b>	An internal error occurred.
<b>Action</b>	Please contact your software supplier.

<b>INODSF1359</b>	<b>Invalid value (long value) found on address address at location location</b>
<b>Explanation</b>	An internal error has caused the server to stop.
<b>Action</b>	Please contact your software supplier. Restart the server.
<b>INODSF1360</b>	<b>The tape device is not responding, please ensure that a tape is mounted</b>
<b>Explanation</b>	Response EINVAL was returned by the operating system. The most likely cause is that no tape has been mounted.
<b>Action</b>	Ensure that a tape is mounted and the device is switched on.
<b>INODSF1362</b>	<b>Journal space too small (minimum required size is size MBytes)</b>
<b>Explanation</b>	The journal space is not sufficient for the Tamino server.
<b>Action</b>	Create a database with a larger journal space.
<b>INODSF1363</b>	<b>Journal overflow. Server cannot proceed.</b>
<b>Explanation</b>	The journal space was insufficient. The current server session has to be terminated.
<b>Action</b>	Check if more journal space can be provided. Restart the server.
<b>INODSF1364</b>	<b>Log space not found for savepoint savepoint</b>
<b>Explanation</b>	A log space entry for the given savepoint could not be found.
<b>Action</b>	Contact your software supplier.
<b>INODSF1366</b>	<b>License file not found at path</b>
<b>Explanation</b>	Your license is not at the expected place.
<b>Action</b>	Please move the license file to the place indicated.
<b>INODSF1367</b>	<b>License file not valid (error error)</b>
<b>Explanation</b>	Your license is not valid. It is incomplete or has been edited.
<b>Action</b>	Please acquire a correct license file from your software supplier.
<b>INODSF1369</b>	<b>Internal licensing error error</b>
<b>Explanation</b>	There was an internal error in the processing of the licensing information.
<b>Action</b>	Please contact your software supplier.

---

<b>INODSF1373</b>	<b>Database database name not registered</b>
<b>Explanation</b>	The specified database has not been properly created or the internal entries of this database have been destroyed.
<b>Action</b>	Create the database again.
<b>INODSF1431</b>	<b>Error during autorepair. The database is inconsistent.</b>
<b>Explanation</b>	The last server session terminated abnormally. The database autorepair has failed. The database cannot be used.
<b>Action</b>	Send the journal space and all other error information to your software supplier. Then recover your database from the last backup.
<b>INODSF1432</b>	<b>Start of autorepair information cannot be determined</b>
<b>Explanation</b>	The last server session terminated abnormally. The database autorepair has failed. The database cannot be used.
<b>Action</b>	Send the journal space and all other error information to your software supplier. Then recover your database from the last backup.
<b>INODSF1433</b>	<b>Journal overflow during database autorepair. The database is inconsistent.</b>
<b>Explanation</b>	The last server session terminated abnormally. The database autorepair has failed. The database cannot be used.
<b>Action</b>	Send the journal space and all other error information to your software supplier. Then recover your database from the last backup.
<b>INODSF1436</b>	<b>Terminated with errors</b>
<b>Explanation</b>	A previous error has caused the termination of the process.
<b>Action</b>	Please check the event log for detailed information about previous errors that have caused the process to terminate.
<b>INODSF1454</b>	<b>Internal error occurred: location thread module function. Server stopped.</b>
<b>Explanation</b>	An internal error occurred.
<b>Action</b>	Please contact your software supplier and provide the message text.

<b>INODSF1688</b>	<b>Shared memory of size size MB is not available (internal error errno)</b>
<b>Explanation</b>	The server needs a shared memory of the specified size. However, this shared memory could not be created.
<b>Action</b>	View the previous message which describes the operating system error in detail. Check the manufacturer's manual. Consider increasing the operating system limits on shared memory size or decreasing the needs of the server by decreasing parameters such as buffer pool size.
<b>INODSF2002</b>	<b>Error during replication processing, replication stopped</b>
<b>Explanation</b>	Replication cannot be continued due to a previous error during replication processing
<b>Action</b>	If the master database is lost, the Reset Replication function can be used to convert the database for usage as a substitution. In any other case a new backup from the master database should be used to recreate the replication database.
<b>INODSF2005</b>	<b>Internal replication error error/error info detected when processing data of server session session number - block block number, location record number</b>
<b>Explanation</b>	The data required for replication processing could not be supplied by the master database.
<b>Action</b>	Please check that the log space has not yet been deleted by creating new backups of the master database. If the log space still exists keep the error information and contact your software supplier.
<b>INODSF2075</b>	<b>Failure writing to tape device, please ensure that a tape is loaded</b>
<b>Explanation</b>	The response EFAULT was returned by the operating system. The most likely cause is that no tape is loaded in the device.
<b>Action</b>	Ensure that a tape is loaded and the device is switched on.
<b>INODSF2116</b>	<b>Internal command recovery failure (rsp1) on doctype doctype, caused by: rsp2</b>
<b>Explanation</b>	A internal recovery failed and therefore the server cannot resolve a rollback. The server must terminate in order to prevent the database from being corrupted.
<b>Action</b>	Restart the server.
<b>INODSF2119</b>	<b>Invalid compatibility level: DBMS complev1, backup file complev2 (filename)</b>
<b>Explanation</b>	An invalid compatibility level of DBMS and backup file has been detected.
<b>Action</b>	Please use a DBMS version with the same compatibility level as the backup file, or use a backup file with the compatibility of the DBMS.

---

<b>INODSF2120</b>	<b>IO [mod-line] error error</b>
<b>Explanation</b>	An unexpected error occurred in an I/O function.
<b>Action</b>	Please contact your software supplier and provide the message text.
<b>INODSF2122</b>	<b>Invalid compatibility level: DBMS complev1, database complev2</b>
<b>Explanation</b>	An invalid compatibility level has been detected.
<b>Action</b>	Please contact your software supplier.
<b>INODSF2123</b>	<b>CF [mod-line] error error</b>
<b>Explanation</b>	An internal configuration error occurred.
<b>Action</b>	Please contact your software supplier and provide the error message text.
<b>INODSF2128</b>	<b>Invalid data block detected at block blknr (doc doc, cont cont)</b>
<b>Explanation</b>	An invalid data block was detected which refused a database backup. At least one collection has a data fault.
<b>Action</b>	Repair the database with restore/recover from the latest good backup.
<b>INODSF2188</b>	<b>Failed to enter the new compatibility level in the internal configuration store</b>
<b>Explanation</b>	The new compatibility level could not be entered in the internal configuration store.
<b>Action</b>	Please contact your software supplier and provide the message text.
<b>INODSF2227</b>	<b>Internal error error during flush operation</b>
<b>Explanation</b>	The write operation of the internal buffer cache to disk failed. A detailed error message precedes this message.
<b>Action</b>	Analyse the error code, maybe check your disks and restart server.
<b>INODSF2234</b>	<b>SMP resource allocation failed at module[line] because of a lack of available memory</b>
<b>Explanation</b>	The allocation of memory failed. The reason for that is either that the pagefile is too small or that the available virtual memory is exhausted.
<b>Action</b>	Increase the size of the pagefile. If that doesn't help contact your software supplier.

<b>INODSF2235</b>	<b>Database key mismatch, required keyreq, present keypres</b>
<b>Explanation</b>	The index space has an unexpected key within the first index space. The database space obviously comes from another database.
<b>Action</b>	Check the index container spaces.
<b>INODSF2266</b>	<b>Cannot start Tamino utility of version due to system error errno</b>
<b>Explanation</b>	Submitting a Tamino utility as a subprocess failed due to an operating system error.
<b>Action</b>	Analyze the system error and check the installed version.
<b>INODSF2280</b>	<b>Unexpected I/O error (io operation) on database_space</b>
<b>Explanation</b>	An I/O failed and the process cannot continue.
<b>Action</b>	View any previous or related system error messages and analyse why the I/O operation on the given database space could have failed.
<b>INODSF2284</b>	<b>Error errno (errtxt) has been signalled during the execution of an asynchronous I/O on database space for id</b>
<b>Explanation</b>	A severe read/write error has occurred.
<b>Action</b>	Analyse the operating system error.
<b>INODSF2286</b>	<b>Internal replication error error/error info detected when processing data of mass load recovery input filename</b>
<b>Explanation</b>	The mass load input required for replication processing could not be supplied by the master database.
<b>Action</b>	Please check that the recovery input file has not yet been deleted by creating new backups of the master database. If the log space still exists, keep the error information and contact your software supplier.
<b>INODSF2287</b>	<b>Internal error error detected when processing mass load recovery input with key key</b>
<b>Explanation</b>	The recovery of a mass load activity failed.
<b>Action</b>	Please contact your software supplier.

---

<b>INODSF2288</b>	<b>Cannot grant server synchronization semaphore</b>
<b>Explanation</b>	The server synchronization semaphore cannot be granted.
<b>Action</b>	Check if the semaphore already exists and another process has granted it, or if the permission settings of the semaphore do not allow access.
<b>INODSF2294</b>	<b>Filename for database space container could not be determined</b>
<b>Explanation</b>	It was not possible to determine the full filename for the specified database space. It was obviously missing in the internal configuration store.
<b>Action</b>	This is an internal error. Please contact your software supplier.
<b>INODSF2296</b>	<b>Internal error interr on database space (reason)</b>
<b>Explanation</b>	The writing of relevant information to the given database space (Log, Journal) failed due to an internal error.
<b>Action</b>	Check the location where the database space resides and also analyse the previously given operating system error message.
<b>INODSF2299</b>	<b>Internal error number reading dbspace at block blocknumber</b>
<b>Explanation</b>	Reading the given database block resulted in an internal I/O error.
<b>Action</b>	No action required.
<b>INODSF2306</b>	<b>License timer interval too short</b>
<b>Explanation</b>	The license timer detected an unexpected system data and time.
<b>Action</b>	Please contact your software supplier.
<b>INODSF2307</b>	<b>Invalid combination of customer/partner information found in the license file</b>
<b>Explanation</b>	An invalid combination of customer/partner information was found in the license file.
<b>Action</b>	Please contact your software supplier to extend your license.
<b>INODSF2308</b>	<b>Product usage found in the license file is not allowed for an unlimited license</b>
<b>Explanation</b>	The product usage found in the license file is only allowed for a time-limited license.
<b>Action</b>	Please contact your software supplier to correct your license.

<b>INODSF2309</b>	<b>Server abort because of license expiration</b>
<b>Explanation</b>	The grace period after license termination has expired. The server did an abort.
<b>Action</b>	Please contact your software supplier to extend your license.
<b>INODSF2334</b>	<b>The license for name with ID id has expired, server aborts now</b>
<b>Explanation</b>	The license has expired. The server has stopped operation (abort). Operation can be continued upon restart with a renewed license key.
<b>Action</b>	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager, then restart the server.
<b>INODSF2335</b>	<b>The license for customername sub-licensed by partnername with ID partnerid has expired, server aborts now</b>
<b>Explanation</b>	The license has expired. The server has stopped operation (abort). Operation can be continued upon restart with a renewed license key.
<b>Action</b>	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager, then restart the server.
<b>INODSF2336</b>	<b>The license for customername with ID customerid sub-licensed by partnername has expired, server aborts now</b>
<b>Explanation</b>	The license has expired. The server has stopped operation (abort). Operation can be continued upon restart with a renewed license key.
<b>Action</b>	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager, then restart the server.
<b>INODSF2337</b>	<b>The license for customername with ID customerid sub-licensed by partnername with ID partnerid has expired, server aborts now</b>
<b>Explanation</b>	The license has expired. The server has stopped operation (abort). Operation can be continued upon restart with a renewed license key.
<b>Action</b>	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager, then restart the server.
<b>INODSF2338</b>	<b>Internal error number writing dbspace at block blocknumber</b>
<b>Explanation</b>	Cannot write database block due to an internal I/O error.
<b>Action</b>	Analyse the error number and check the database.

---

<b>INODSF2339</b>	<b>XTS refuses database connection, reason reason_code</b>
<b>Explanation</b>	It is not possible to reach the database via XTS.
<b>Action</b>	Switch on XTS_TRACE, repeat the function and check the trace file.
<b>INODSF4256</b>	<b>Structure level mismatch on database</b>
<b>Explanation</b>	The version of the server differs from the version of the utility.
<b>Action</b>	Run the correct version of the utility or server, or convert the database.
<b>INODSF4258</b>	<b>The database type and/or version does not match the backup</b>
<b>Explanation</b>	This operation can only be performed against a database of the same type and/or version as the backup.
<b>Action</b>	Ensure that the utility is being run against the correct type and version of database.
<b>INODSF4262</b>	<b>Database server mismatch: present db_name</b>
<b>Explanation</b>	A mismatch occurred between the database server parameter and the database server name of the assigned index space.
<b>Action</b>	Ensure that the correct database name is supplied.
<b>INODSF5331</b>	<b>Version version is not installed</b>
<b>Explanation</b>	The required software version is not installed.
<b>Action</b>	please contact your software supplier.
<b>INODSF5332</b>	<b>Invalid structure level strlev</b>
<b>Explanation</b>	An invalid structure level has been detected.
<b>Action</b>	Please contact your software supplier.
<b>INODSI1004</b>	<b>Stop of database successfully initiated - server is going down now</b>
<b>Explanation</b>	All database activities are terminated - the server process is about to terminate.
<b>Action</b>	No action required.
<b>INODSI1010</b>	<b>Backup file from older version version</b>
<b>Explanation</b>	Indicates that the input backup file is from a previous version.
<b>Action</b>	No action required.

<b>INODSI1013</b>	<b>Read-only database, word fragment index cannot be created</b>
<b>Explanation</b>	Read-only database, no database update permitted.
<b>Action</b>	Ensure that the database upon which you wish to carry out the operation is write-enabled.
<b>INODSI1016</b>	<b>Initializing journal space</b>
<b>Explanation</b>	When the database first starts, the entire journal space must be formatted with binary zeroes.
<b>Action</b>	Wait until the operation finished: This could take several seconds or even several minutes if the file is very large.
<b>INODSI1019</b>	<b>Database of older version version</b>
<b>Explanation</b>	The database used for restore is from a previous version.
<b>Action</b>	No action required.
<b>INODSI1034</b>	<b>The Tamino Server that is provided with this Tamino Developer Edition may be used for educational purposes only. For production purposes, you must use the Tamino Server that is included in the Tamino Server Edition.</b>
<b>Explanation</b>	This is an informational message
<b>Action</b>	None
<b>INODSI1039</b>	<b>Function function executed</b>
<b>Explanation</b>	The specified function was executed.
<b>Action</b>	Information only, no action required.
<b>INODSI1041</b>	<b>Starting mode database backup</b>
<b>Explanation</b>	Indicates the start of database backup processing.
<b>Action</b>	No action required.
<b>INODSI1044</b>	<b>Starting restore database using type backup from timestamp</b>
<b>Explanation</b>	Indicates the backup that was used to start restore processing.
<b>Action</b>	No action required.

---

<b>INODSI1049</b>	<b>Starting mode restore of database</b>
<b>Explanation</b>	Indicates that the restore processing has been started.
<b>Action</b>	No action required.
<b>INODSI1059</b>	<b>The time-limited license for the server has expired, switched to an unlimited Community Edition license</b>
<b>Explanation</b>	The time-limited license for the server has expired. The server automatically switched to an unlimited Community Edition license. Some product features may no longer be available.
<b>Action</b>	No action required.
<b>INODSI1110</b>	<b>Waiting time for count users to start a new transaction - min: min seconds, max: max seconds, average: average seconds seconds</b>
<b>Explanation</b>	This message is used to give information about waiting times for users who want to open a new transaction while other users have not yet finished their transaction. This synchronization of all users who do not have an open transaction is required at the end of a backup.
<b>Action</b>	No action required.
<b>INODSI1113</b>	<b>No real modified data for Incremental Backup</b>
<b>Explanation</b>	There is no modification in the database, so an incremental backup will save no new data. Nevertheless a backup with only global data will be created.
<b>Action</b>	No action required.
<b>INODSI1114</b>	<b>Incremental backup from date deleted</b>
<b>Explanation</b>	A full backup to be deleted causes the deletion of dependent incremental backups as well.
<b>Action</b>	No action required.
<b>INODSI1146</b>	<b>Archive Log Location has been reset</b>
<b>Explanation</b>	An Archive Log Location will not be used.
<b>Action</b>	None.

<b>INODSI1147</b>	<b>path set as location name</b>
<b>Explanation</b>	A path or a set of paths has been set for the specified location type.
<b>Action</b>	None.
<b>INODSI1177</b>	<b>Database database name Session session number (name modifier version on system info, process ID pid)</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.
<b>INODSI1178</b>	<b>Database database name Replication Session (name modifier version on system info, processID pid)</b>
<b>Explanation</b>	The server started for a replication database.
<b>Action</b>	No action required.
<b>INODSI1179</b>	<b>Database database name Read-Only Session (name modifier version on system info, process ID pid)</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.
<b>INODSI1183</b>	<b>size MB empty data space found</b>
<b>Explanation</b>	The amount of empty data space assigned to specific doctypes that can be returned to global free space
<b>Action</b>	None.
<b>INODSI1184</b>	<b>No empty data space found</b>
<b>Explanation</b>	Empty data space that can be returned to global free space does not exist
<b>Action</b>	None.
<b>INODSI1188</b>	<b>Creating a temporary backup for free space defragmentation</b>
<b>Explanation</b>	A temporary backup is created to be used for defragmenting free space
<b>Action</b>	Wait until the reorganization is completed.

---

<b>INODSI1190</b>	<b>size MB empty data space converted to global free space</b>
<b>Explanation</b>	The amount of empty data space that was de-allocated from specific doctypes and returned to global free space.
<b>Action</b>	None.
<b>INODSI1191</b>	<b>Free data space in database is size MB (percent %)</b>
<b>Explanation</b>	Information about the amount of global free data space after reorganization.
<b>Action</b>	None.
<b>INODSI1193</b>	<b>Free space less than percent %, no free space defragmentation and data space shrinking</b>
<b>Explanation</b>	The reorganize function converted empty space to global free space, but the amount of free space is less than a minimum value considered as worthwhile performing a free space defragmentation and data space shrinking.
<b>Action</b>	None, if you are satisfied with the minimum value for free space defragmentation and data space shrinking. In any other case, use the reorganize function with a different minimum value.
<b>INODSI1195</b>	<b>Defragmenting free space</b>
<b>Explanation</b>	A temporary backup is used for restore to defragment free space.
<b>Action</b>	Wait until the reorganization is completed.
<b>INODSI1196</b>	<b>Shrinking data space</b>
<b>Explanation</b>	The size of the data space is reduced by de-allocating free space.
<b>Action</b>	Wait until the reorganization is completed.
<b>INODSI1197</b>	<b>No free data space found</b>
<b>Explanation</b>	Free data space does not exist.
<b>Action</b>	None.
<b>INODSI1207</b>	<b>rplname inserted into permission list of dbname</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.

<b>INODSI1208</b>	<b>rplname removed from permission list of dbname</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.
<b>INODSI1211</b>	<b>dbname set as replication server of master on hostname using port number</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.
<b>INODSI1218</b>	<b>dbname set as replication server with simultaneous query, master is masterdb</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.
<b>INODSI1219</b>	<b>dbname set as replication server without simultaneous query, master is masterdb</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.
<b>INODSI1220</b>	<b>Replication server dbname reset to normal server</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.
<b>INODSI1246</b>	<b>Read-only database, word fragment index cannot be removed</b>
<b>Explanation</b>	The database is readonly, so no database update is permitted.
<b>Action</b>	Ensure that the database upon which you wish to carry out this operation is write-enabled.
<b>INODSI1248</b>	<b>No backup exists for dbname - create a backup as soon as possible</b>
<b>Explanation</b>	After converting a replication database to a normal database a backup of the database is not available, thus a restore/recover is not possible until a backup exists.
<b>Action</b>	Create a backup of the database.
<b>INODSI1252</b>	<b>Starting restore database using type backup from timestamp</b>
<b>Explanation</b>	Indicates the backup that was used to start restore processing.
<b>Action</b>	No action required.

---

<b>INODSI1253</b>	<b>Incremental backup from date deleted</b>
<b>Explanation</b>	A full backup to be deleted causes the deletion of dependent incremental backups as well.
<b>Action</b>	No action required.
<b>INODSI1294</b>	<b>Log space of server session session number from time opened</b>
<b>Explanation</b>	The log space of the specified server session has been opened.
<b>Action</b>	No action required.
<b>INODSI1304</b>	<b>Read-only database db_name , startup at startup</b>
<b>Explanation</b>	This message shows the time at which the database was started in read-only mode.
<b>Action</b>	No action required.
<b>INODSI1314</b>	<b>Database db_name, startup at startup</b>
<b>Explanation</b>	This message shows the time at which the database was started.
<b>Action</b>	No action required.
<b>INODSI1315</b>	<b>Log space of server session session number processed until time</b>
<b>Explanation</b>	All information generated before the given end timestamp of the log space of the specified server session was processed.
<b>Action</b>	No action required.
<b>INODSI1316</b>	<b>The backup tape from time has been unregistered</b>
<b>Explanation</b>	The information about the availability of the given backup tape has been removed.
<b>Action</b>	The tape may be removed from the archive.
<b>INODSI1327</b>	<b>Database stopped</b>
<b>Explanation</b>	The database has been stopped.
<b>Action</b>	No action required.
<b>INODSI1333</b>	<b>Log space data processing end time stamp is time</b>
<b>Explanation</b>	This is a progress message about the aborted recovery run or an abort of replication processing.
<b>Action</b>	In the case of a recovery run, the information can be used to start a recover until.

<b>INODSI1339</b>	<b>Replication of server session session number suspended replication data processed until timestamp</b>
<b>Explanation</b>	Replication processing is suspended due to a server shutdown request of the replication database.
<b>Action</b>	No action required.
<b>INODSI1352</b>	<b>Replication of server session session number from timestamp started</b>
<b>Explanation</b>	The replication processing has started to process the log space data of the specified server session of the master database.
<b>Action</b>	No action required.
<b>INODSI1361</b>	<b>Replication of server session session number resumed using replication data from timestamp</b>
<b>Explanation</b>	The server continued replication processing after replication database startup.
<b>Action</b>	No action required.
<b>INODSI1365</b>	<b>Server session session number replicated until time stamp</b>
<b>Explanation</b>	This is the current replication status of the database.
<b>Action</b>	No action required.
<b>INODSI1368</b>	<b>Replication of server session session number resumed using replication data from timestamp. Simultaneous query permitted.</b>
<b>Explanation</b>	The server continued replication processing after replication database startup.
<b>Action</b>	No action required.
<b>INODSI1370</b>	<b>Replication of server session session number from timestamp started. Simultaneous query permitted.</b>
<b>Explanation</b>	The replication processing has started to process the log space data of the specified server session of the master database.
<b>Action</b>	No action required.
<b>INODSI1371</b>	<b>sufficient space in locations, continue</b>
<b>Explanation</b>	Now there is sufficient space on the location where the file was waiting for, the operation now continues
<b>Action</b>	Now there is a subsequent file extent

---

<b>INODSI1384</b>	<b>Setting of parname=parval</b>
<b>Explanation</b>	no description available
<b>Action</b>	no action required
<b>INODSI1389</b>	<b>Backup from backup_date deleted</b>
<b>Explanation</b>	After backup, the number of backup generations is updated, i.e older backups are removed. For further information, please refer to the documentation of the server parameter "number of backup generations".
<b>Action</b>	No action required.
<b>INODSI1393</b>	<b>Backup created with backup key 'backupkey' (from)</b>
<b>Explanation</b>	The identification of the last created backup is displayed.
<b>Action</b>	No action required.
<b>INODSI1394</b>	<b>Backup key 'backupkey' (from)</b>
<b>Explanation</b>	This is a display of backup information.
<b>Action</b>	No action required.
<b>INODSI1397</b>	<b>Deleting disabled backup from backup_date</b>
<b>Explanation</b>	A disabled backup file is being deleted.
<b>Action</b>	No action required.
<b>INODSI1399</b>	<b>Dataset dsn created on date</b>
<b>Explanation</b>	The dataset was created on the specified date.
<b>Action</b>	No action required.
<b>INODSI1400</b>	<b>A transaction has been heuristically rolled back at time</b>
<b>Explanation</b>	The database system has rolled back a transaction for which a decision of the transaction manager was pending.
<b>Action</b>	No action required.

<b>INODSI1417</b>	<b>database database name at structure level for version version</b>
<b>Explanation</b>	This informational message states the structure level of the database.
<b>Action</b>	No action required.
<b>INODSI1420</b>	<b>Dump file at version: vers, level level</b>
<b>Explanation</b>	This informational message states the version and level of the dump file.
<b>Action</b>	Select the version displayed.
<b>INODSI1422</b>	<b>Using backup filename</b>
<b>Explanation</b>	Indicates the backup which is used to create the new database.
<b>Action</b>	No action required.
<b>INODSI1423</b>	<b>Using location location</b>
<b>Explanation</b>	Indicates the location which is to be used for the database spaces.
<b>Action</b>	No action required.
<b>INODSI1451</b>	<b>Creation of word fragment index started</b>
<b>Explanation</b>	The creation of the word fragment index has started.
<b>Action</b>	No action required.
<b>INODSI1452</b>	<b>Server session session number started</b>
<b>Explanation</b>	The server started successfully.
<b>Action</b>	No action required.
<b>INODSI1453</b>	<b>Internal event event has occurred</b>
<b>Explanation</b>	This message indicates a certain event in the server processing. It is not relevant to the user.
<b>Action</b>	No action required.
<b>INODSI1456</b>	<b>The Tamino Server that is provided with the Tamino Developer Edition may be used for test purposes only. For production purposes, you must use the Tamino Server that is included in the Tamino Server Edition.</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	Use the correct Tamino Server.

---

<b>INODSI1457</b>	<b>End of tape tape - rewinding</b>
<b>Explanation</b>	The tape is being rewound.
<b>Action</b>	No action required.
<b>INODSI1458</b>	<b>End of diskette path</b>
<b>Explanation</b>	The diskette is full.
<b>Action</b>	No action required.
<b>INODSI1459</b>	<b>Log space of server session session number from time opened</b>
<b>Explanation</b>	The log space of the specified server session has been opened.
<b>Action</b>	No action required.
<b>INODSI1460</b>	<b>Log space of server session session number completed</b>
<b>Explanation</b>	The log space of the specified server session has been completed.
<b>Action</b>	No action required.
<b>INODSI1463</b>	<b>Database 'database_name' accessed online</b>
<b>Explanation</b>	The specified database has been accessed online.
<b>Action</b>	No action required.
<b>INODSI1464</b>	<b>Database 'database_name' accessed offline</b>
<b>Explanation</b>	The specified database has been accessed offline.
<b>Action</b>	No action required.
<b>INODSI1466</b>	<b>Creation of database space space no (location name) has successfully finished</b>
<b>Explanation</b>	The specified database space has been created.
<b>Action</b>	No action required.
<b>INODSI1467</b>	<b>Tamino name modifier version on system info</b>
<b>Explanation</b>	This is a generic message used to identify an activity.
<b>Action</b>	No action required.

<b>INODSI1468</b>	<b>No index found</b>
<b>Explanation</b>	No index found.
<b>Action</b>	No action required.
<b>INODSI1469</b>	<b>The database server is active on a remote node</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.
<b>INODSI1470</b>	<b>Database spaces for database db_name have been created</b>
<b>Explanation</b>	The database spaces for a database server have been successfully created. The next step of database creation will be restoring the initial contents of the database.
<b>Action</b>	Restore the initial contents of the database.
<b>INODSI1471</b>	<b>Database db_name has been deleted</b>
<b>Explanation</b>	The database with the given name has been successfully deleted.
<b>Action</b>	No action required.
<b>INODSI1474</b>	<b>Read-only database db_name , startup at startup</b>
<b>Explanation</b>	This message shows the time at which the database was started in read-only mode.
<b>Action</b>	No action required.
<b>INODSI1475</b>	<b>Database db_name, startup at startup</b>
<b>Explanation</b>	This message shows the time at which the database was started.
<b>Action</b>	No action required.
<b>INODSI1480</b>	<b>Log space of server session session number processed until time</b>
<b>Explanation</b>	All information generated before the given end timestamp of the log space of the specified server session was processed.
<b>Action</b>	No action required.
<b>INODSI1481</b>	<b>Log space of server session session number skipped</b>
<b>Explanation</b>	The log space of the specified server session was not processed because it contains only information generated after the given end timestamp.
<b>Action</b>	No action required.

---

<b>INODSI1484</b>	<b>No log space information found</b>
<b>Explanation</b>	The initial backup was used for restore, and no log space of another session exists.
<b>Action</b>	No action required.
<b>INODSI1485</b>	<b>Checking finished. No inconsistencies found.</b>
<b>Explanation</b>	The check and repair database action has finished.
<b>Action</b>	No action required.
<b>INODSI1486</b>	<b>Log space of server session session number extent extent number archived</b>
<b>Explanation</b>	A log space extent has been copied to the archive location.
<b>Action</b>	No action required.
<b>INODSI1487</b>	<b>The backup tape from time has been unregistered</b>
<b>Explanation</b>	The information about the availability of the given backup tape has been removed.
<b>Action</b>	The tape may be removed from the archive.
<b>INODSI1488</b>	<b>Previous server session aborted when recovering session session number</b>
<b>Explanation</b>	A previously started restore/recovery run did not complete the recovery phase.
<b>Action</b>	See the instructions within subsequent messages.
<b>INODSI1489</b>	<b>Log space data processing end time stamp is time</b>
<b>Explanation</b>	This is a progress message about the aborted recovery run or an abort of replication processing.
<b>Action</b>	In the case of a recovery run, the information can be used to start a recover until.
<b>INODSI1490</b>	<b>Continuing server startup will disable subsequent backups</b>
<b>Explanation</b>	When the server startup is continued, backups done later than the used one will become invalid.
<b>Action</b>	No action required.
<b>INODSI1491</b>	<b>Due to an unexpected problem, Restore and/or Recover was not successful. Please re-execute the Restore and/or Recover now to ensure data integrity.</b>
<b>Explanation</b>	For reasons stated in the job log, the Restore and/or Recover failed to execute properly. Depending on the reason for the abort, either "restore without recover" or "recover until" can be used to recover your data.
<b>Action</b>	If the reason for the initial recovery abort was a missing or corrupted log space, use "restore without recover" or "recover until".

<b>INODSI1492</b>	<b>Subsequent backups disabled</b>
<b>Explanation</b>	Backups older than the one used for the aborted recovery run are invalid now.
<b>Action</b>	No action possible.
<b>INODSI1493</b>	<b>Tamino server successfully started in read-only mode</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.
<b>INODSI1494</b>	<b>Destruction of word fragment index started</b>
<b>Explanation</b>	Destruction of word fragment index started
<b>Action</b>	No action required
<b>INODSI1495</b>	<b>Creation of word fragment index successfully finished</b>
<b>Explanation</b>	Creation of the word fragment index successfully finished.
<b>Action</b>	No action required
<b>INODSI1496</b>	<b>Destruction of word fragment index successfully finished</b>
<b>Explanation</b>	Destruction of the word fragment index successfully finished
<b>Action</b>	No action required
<b>INODSI1532</b>	<b>referential constraint name dropped (primary primary, foreign foreign)</b>
<b>Explanation</b>	The specified referential integrity constraint has been dropped.
<b>Action</b>	None.
<b>INODSI1535</b>	<b>file file refreshed</b>
<b>Explanation</b>	The specified file has been refreshed.
<b>Action</b>	None.
<b>INODSI1550</b>	<b>function not permitted, referential constraint defined</b>
<b>Explanation</b>	The function not permitted because a referential constraint is defined.
<b>Action</b>	None.

---

<b>INODSI1631</b>	<b>Autorepair completed without errors</b>
<b>Explanation</b>	The autorepair from the crash of the previous server session was successful.
<b>Action</b>	The database can now be used.
<b>INODSI1632</b>	<b>Recovery terminated successfully</b>
<b>Explanation</b>	The recovery has processed all log spaces. All updates have been re-applied.
<b>Action</b>	The server can now be restarted.
<b>INODSI1634</b>	<b>Successful completion</b>
<b>Explanation</b>	The action has completed without errors.
<b>Action</b>	No action required.
<b>INODSI1635</b>	<b>Crash dump of database finished</b>
<b>Explanation</b>	The crash dump is complete.
<b>Action</b>	No action required.
<b>INODSI1636</b>	<b>Tamino server successfully started</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.
<b>INODSI1637</b>	<b>Skipping recovery terminated successfully</b>
<b>Explanation</b>	The operation of skipping the recovery has terminated successfully. The update of the log space information has been completed.
<b>Action</b>	The server can now be restarted.
<b>INODSI1691</b>	<b>Mass load recovery files archived</b>
<b>Explanation</b>	The mass load recovery files have been copied to the archive location.
<b>Action</b>	No action required.
<b>INODSI1732</b>	<b>Calculated RESTART point - BLOCK=block,CHECKPOINT=chkpt</b>
<b>Explanation</b>	Recovery has restarted from the position shown.
<b>Action</b>	No action required.

<b>INODSI1986</b>	<b>no file protection enabled</b>
<b>Explanation</b>	File protection is not enabled
<b>Action</b>	No action required.
<b>INODSI1988</b>	<b>PID pid</b>
<b>Explanation</b>	Process ID.
<b>Action</b>	None.
<b>INODSI2003</b>	<b>Replication of server session session number suspended replication data processed until timestamp</b>
<b>Explanation</b>	Replication processing is suspended due to a server shutdown request of the replication database.
<b>Action</b>	No action required.
<b>INODSI2006</b>	<b>No replication data for server session session number</b>
<b>Explanation</b>	No modifications have been made for a server session on the master database.
<b>Action</b>	No action required.
<b>INODSI2007</b>	<b>Replication of server session session number from timestamp started</b>
<b>Explanation</b>	The replication processing has started to process the log space data of the specified server session of the master database.
<b>Action</b>	No action required.
<b>INODSI2008</b>	<b>Replication of server session session number completed</b>
<b>Explanation</b>	The server completed replication of a master database's server session
<b>Action</b>	No action required.
<b>INODSI2009</b>	<b>Replication of server session session number resumed using replication data from timestamp</b>
<b>Explanation</b>	The server continued replication processing after replication database startup.
<b>Action</b>	No action required.

---

<b>INODSI2010</b>	<b>Server session session number replicated until time stamp</b>
<b>Explanation</b>	This is the current replication status of the database.
<b>Action</b>	No action required.
<b>INODSI2011</b>	<b>Starting replication using data from database master dbname</b>
<b>Explanation</b>	Replication processing has started. The master database must be active to supply replication data.
<b>Action</b>	No action required.
<b>INODSI2012</b>	<b>Initial server session session number for new replication database</b>
<b>Explanation</b>	A replication database is started for replication the first time.
<b>Action</b>	No action required.
<b>INODSI2017</b>	<b>Updating backup generations</b>
<b>Explanation</b>	Older backups are being removed if the number of backup generations has been exceeded.
<b>Action</b>	No action required.
<b>INODSI2018</b>	<b>Using hostname as host name for the Software AG XTS Directory Server entries</b>
<b>Explanation</b>	The specified hostname has been assigned to the server property "server host name". This name will be registered in the Software AG XTS Directory Server as the host where the database is located.
<b>Action</b>	No action required.
<b>INODSI2021</b>	<b>The following file type file was not deleted: file name</b>
<b>Explanation</b>	In the case of abnormal server terminations, log and dump files will be written. To be able to analyze several problems, these files could be helpful and will not be deleted. Be aware that dump files could be very large.
<b>Action</b>	It might be useful to keep the dump and log files for further examination. If you want to generate a new database in the same location you should move those files to a different location by hand.

<b>INODSI2040</b>	<b>File 'name' copied to directory</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No activity required.
<b>INODSI2044</b>	<b>Infofile 'path' created</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.
<b>INODSI2074</b>	<b>Corrupted block repaired on space</b>
<b>Explanation</b>	Due to a previous crash the latest written block may be corrupted (in the journal or log). In some cases this can be detected and repaired.
<b>Action</b>	Check if the previous session was abnormally aborted. Only in this case should this message appear.
<b>INODSI2091</b>	<b>Process can make use of 3GB virtual address space</b>
<b>Explanation</b>	The process can make use of 3GB virtual address space.
<b>Action</b>	No action required.
<b>INODSI2100</b>	<b>Web server configuration changed, server server notified</b>
<b>Explanation</b>	The web server configuration changed and the server was notified.
<b>Action</b>	No action required.
<b>INODSI2115</b>	<b>Execution continues</b>
<b>Explanation</b>	This message is displayed by debug-enabled executables if they have been selected for debugging.
<b>Action</b>	No action required.
<b>INODSI2146</b>	<b>Replication of server session session number resumed using replication data from timestamp. Simultaneous query permitted.</b>
<b>Explanation</b>	The server continued replication processing after replication database startup.
<b>Action</b>	No action required.

---

<b>INODSI2148</b>	<b>At least one replication database allows simultaneous query</b>
<b>Explanation</b>	The replication master writes additional locking information to the log space. A replication database with 'Simultaneous Query' enabled may be accessed with queries while it replicates updates.
<b>Action</b>	No action required.
<b>INODSI2149</b>	<b>No replication databases allow simultaneous query</b>
<b>Explanation</b>	The replication master does not write additional locking information to the log space. A replication database with 'Simultaneous Query' enabled cannot process queries while replicating updates of this session.
<b>Action</b>	No action required.
<b>INODSI2150</b>	<b>Database database name set to replication type with simultaneous query</b>
<b>Explanation</b>	If at least one replication database is defined with 'simultaneous query' the master database writes additional locking information to the log space. If this replication database is the first of this kind, the master switches to a new session.
<b>Action</b>	No action required.
<b>INODSI2151</b>	<b>Database database name set to replication type without simultaneous query</b>
<b>Explanation</b>	If no replication database is defined with 'simultaneous query' the master database does not write additional locking information to the log space. If replication database mentioned is the last of that kind, the master switches to a new session
<b>Action</b>	No action required.
<b>INODSI2154</b>	<b>Replication of server session session number from timestamp started. Simultaneous query permitted.</b>
<b>Explanation</b>	The replication processing has started to process the log space data of the specified server session of the master database.
<b>Action</b>	No action required.
<b>INODSI2158</b>	<b>Backup from backup_date deleted</b>
<b>Explanation</b>	After backup, the number of backup generations is updated, i.e older backups are removed. For further information, please refer to the documentation of the server parameter "number of backup generations".
<b>Action</b>	No action required.

<b>INODSI2166</b>	<b>Initial backup removed</b>
<b>Explanation</b>	After backup, the number of backup generations is updated, i.e older backups are removed. For further information, please refer to the documentation of server parameter "number of backup generations".
<b>Action</b>	No action required.
<b>INODSI2190</b>	<b>Doctype doctype has been loaded</b>
<b>Explanation</b>	The specified doctype has been successfully loaded.
<b>Action</b>	No action required.
<b>INODSI2196</b>	<b>Connection to master database master dbname reestablished</b>
<b>Explanation</b>	The replication database obtained new replication data from its master database.
<b>Action</b>	No action required.
<b>INODSI2199</b>	<b>Replication data of session session was generated with different update or hotfix level of Tamino version version: update level update, hotfix number hotfix</b>
<b>Explanation</b>	At the master database node a new update of a Tamino version was installed.
<b>Action</b>	Install the same update of the Tamino version at the replication database node.
<b>INODSI2239</b>	<b>The backup tape from initial savepoint has been unregistered</b>
<b>Explanation</b>	The information about the availability of the initial backup tape has been removed.
<b>Action</b>	The tape may be removed from the archive.
<b>INODSI2259</b>	<b>Creating / deleting database process active, wait for continue</b>
<b>Explanation</b>	Another job which creates or deletes a database is active on the current node. View running jobs for more information.
<b>Action</b>	Wait until this task has been completed. You should not wait longer than a couple of seconds.
<b>INODSI2267</b>	<b>Convert database to version version</b>
<b>Explanation</b>	The database will be converted to the version displayed.
<b>Action</b>	No action required.

---

<b>INODSI2300</b>	<b>Keep backup file filename</b>
<b>Explanation</b>	The backup file was not deleted because it was selected to be kept by the user.
<b>Action</b>	Keep in mind that there is still a backup file occupying disk space.
<b>INODSI2310</b>	<b>Licensed for name with ID id</b>
<b>Explanation</b>	Display customer/partner information from the license file.
<b>Action</b>	No action required.
<b>INODSI2311</b>	<b>Licensed for customername sub-licensed by partnername with ID partnerid</b>
<b>Explanation</b>	This is a display of customer/partner information from the license file.
<b>Action</b>	No action required.
<b>INODSI2312</b>	<b>Licensed for customername with ID customerid sub-licensed by partnername</b>
<b>Explanation</b>	This is a display of customer/partner information from the license file.
<b>Action</b>	No action required.
<b>INODSI2313</b>	<b>Licensed for customername with ID customerid sub-licensed by partnername with ID partnerid</b>
<b>Explanation</b>	This is a display of customer/partner information from the license file.
<b>Action</b>	No action required.
<b>INODSI2314</b>	<b>Licensed for name with ID id, license expires on date</b>
<b>Explanation</b>	Display customer/partner and expiration information from the license file.
<b>Action</b>	No action required.
<b>INODSI2315</b>	<b>Licensed for customername sub-licensed by partnername with ID partnerid, license expires on date</b>
<b>Explanation</b>	This is a display of customer/partner and expiration information from the license file.
<b>Action</b>	No action required.
<b>INODSI2316</b>	<b>Licensed for customername with ID customerid sub-licensed by partnername, license expires on date</b>
<b>Explanation</b>	This is a display of customer/partner and expiration information from the license file.
<b>Action</b>	No action required.

<b>INODSI2317</b>	<b>Licensed for customername with ID customerid sub-licensed by partnertype with ID partnerid, license expires on date</b>
<b>Explanation</b>	This is a display of customer/partner and expiration information from the license file.
<b>Action</b>	No action required.
<b>INODSI2343</b>	<b>Backup created with backup key 'backupkey' (from)</b>
<b>Explanation</b>	The identification of the last created backup is displayed.
<b>Action</b>	No action required.
<b>INODSI2344</b>	<b>backup key 'backupkey' (from)</b>
<b>Explanation</b>	This is a display of backup information.
<b>Action</b>	No action required.
<b>INODSI2345</b>	<b>backup key 'backupkey' (initial backup)</b>
<b>Explanation</b>	This is a display of backup information.
<b>Action</b>	No action required.
<b>INODSI2346</b>	<b>Deleting disabled backup from backup_date</b>
<b>Explanation</b>	A disabled backup file is being deleted.
<b>Action</b>	No action required.
<b>INODSI3469</b>	<b>Dataset dsn created on date</b>
<b>Explanation</b>	The dataset was created on the specified date.
<b>Action</b>	No action required.
<b>INODSI5263</b>	<b>Restoring pending transactions</b>
<b>Explanation</b>	Pending global transactions are being restored during the server startup processing.
<b>Action</b>	No action required.
<b>INODSI5270</b>	<b>Use parameter "param" to force server registration</b>
<b>Explanation</b>	The server could not register with the XTS directory service, because an entry for the server is already present. If this entry is no longer necessary the specified parameter can be used to overwrite the existing entry.
<b>Action</b>	Set the specified parameter to YES to force server registration.

---

<b>INODSI5282</b>	<b>Overwriting Software AG XTS Directory Server entries</b>
<b>Explanation</b>	The Software AG XTS Directory Server entries already existed. They are overwritten.
<b>Action</b>	No action required.
<b>INODSI5286</b>	<b>New block allocations for database</b>
<b>Explanation</b>	There were container size/blocksize correlations which require new allocations for all files in the database.
<b>Action</b>	No action required.
<b>INODSI5299</b>	<b>Data space container, file file name removed</b>
<b>Explanation</b>	The database space with the qualified type and name has been removed from the file system.
<b>Action</b>	No action required.
<b>INODSI5339</b>	<b>Log space of server session session number from different version - recovery stopped</b>
<b>Explanation</b>	The next log space to be processed was created by another program version.
<b>Action</b>	See the product documentation for further information about migration between program versions.
<b>INODSI5352</b>	<b>Preparing for external backup</b>
<b>Explanation</b>	The database is in synchronized mode, so an external backup can now take place.
<b>Action</b>	No action required.
<b>INODSI5353</b>	<b>Continuing after external backup</b>
<b>Explanation</b>	The synchronized mode of the database has ended. Normal database processing can resume.
<b>Action</b>	No action required
<b>INODSQ1651</b>	<b>The currently inserted tape has been processed</b>
<b>Explanation</b>	The currently inserted tape has been completely filled (backup) or completely read (restore).
<b>Action</b>	Please insert the next tape in the set so that processing may continue.

<b>INODSQ1652</b>	<b>The diskette is full</b>
<b>Explanation</b>	An operation writing to a diskette has completely filled up the diskette.
<b>Action</b>	Provide the information you are prompted for to enable Tamino to switch to a new diskette.
<b>INODSQ1653</b>	<b>Please insert the next sequential tape and verify the selected device name is correct.</b>
<b>Explanation</b>	Another tape is required in the current backup or restore sequence.
<b>Action</b>	Insert the next sequential tape and verify the device name is correct.
<b>INODSQ1654</b>	<b>Please insert diskette diskette number and specify the device name</b>
<b>Explanation</b>	Another diskette is required.
<b>Action</b>	Insert the indicated diskette and specify the device name.
<b>INODSQ1655</b>	<b>First tape required</b>
<b>Explanation</b>	The first tape is required.
<b>Action</b>	Insert the first tape.
<b>INODSQ1656</b>	<b>First diskette required</b>
<b>Explanation</b>	The first diskette is required.
<b>Action</b>	Insert the first diskette.
<b>INODSQ1657</b>	<b>Please insert first tape again and specify the device name</b>
<b>Explanation</b>	The first tape is required.
<b>Action</b>	Insert the first tape and specify the device name.
<b>INODSQ1658</b>	<b>Waiting for space on LOG device</b>
<b>Explanation</b>	The server can no longer perform update operations, because there is no more free space on the LOG device.
<b>Action</b>	Create free space on the LOG device, e.g. by deleting files.
<b>INODSQ1659</b>	<b>Try to get free space on device where LOG is located</b>
<b>Explanation</b>	The server can no longer perform update operations, because there is no more free space on the LOG device.
<b>Action</b>	Create free space on the LOG device, e.g. by deleting files.

---

<b>INODSQ1660</b>	<b>Continue server startup or re-execute restore/recover</b>
<b>Explanation</b>	When you continue the server startup, autorepair will be used. Database modifications not recovered during the recovery run of the previous aborted server session will be lost.
<b>Action</b>	Decide whether to continue or abort the server startup.
<b>INODSQ1661</b>	<b>Please reply "yes" or "no" to continue server startup</b>
<b>Explanation</b>	At this point in time you can continue or abort the server startup.
<b>Action</b>	Enter "yes" to continue the server startup, enter "no" to abort it.
<b>INODSQ2224</b>	<b>Transfer via pipe stalled</b>
<b>Explanation</b>	The backup activity via named pipe is hanging. One reason could be that the partner pipe process died for some reason, for example if the disk is full.
<b>Action</b>	Find out the reason why the pipe processing is hanging and answer 'OK' to continue or 'Abort' to abort the backup processing.
<b>INODSQ2225</b>	<b>Continue or abort ?</b>
<b>Explanation</b>	Continue or abort the processing. If you answer 'abort' the process immediately terminates with an appropriate message. Answer 'OK' to continue processing if you are sure that the pipe process is still active.
<b>Action</b>	no action
<b>INODSQ2256</b>	<b>File extent extnumber missing</b>
<b>Explanation</b>	A physical file extent of e.g. a backup file was not specified.
<b>Action</b>	Enter the file/device name of the required file extent.
<b>INODSQ2257</b>	<b>Enter file/device name</b>
<b>Explanation</b>	Enter here the full qualified file name of the required extent. Pipe or tape devices may be entered as well.
<b>Action</b>	No action required.
<b>INODSQ2295</b>	<b>No location for database space extent no</b>
<b>Explanation</b>	There is no location given for this database space.
<b>Action</b>	Select a valid location.

<b>INODSR1479</b>	<b>Creating database space extent number of number of extents</b>
<b>Explanation</b>	This is an informational message indicating how many extents of a group of extents have been created for the database space.
<b>Action</b>	No action required.
<b>INODSR1483</b>	<b>Deleting database space extent number of number of extents</b>
<b>Explanation</b>	This is an informational message indicating how many extents of a group of extents for the database space have been deleted.
<b>Action</b>	No action required.
<b>INODSR1682</b>	<b>Analyzing journal information</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.
<b>INODSR1683</b>	<b>Re-applying changes. Processing journal block block number.</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.
<b>INODSR1684</b>	<b>Reconstructing consistent index structures. Processing journal block block number.</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.
<b>INODSR1685</b>	<b>Resetting unfinished transactions. Processing journal block block number.</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.
<b>INODSR1686</b>	<b>Recovered from abnormal termination</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.
<b>INODSR1687</b>	<b>Reading parameters</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.

---

<b>INODSR2029</b>	<b>Offline conversion phase</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.
<b>INODSR2077</b>	<b>Re-applying updates started</b>
<b>Explanation</b>	The recover process has started.
<b>Action</b>	No action required.
<b>INODSR2078</b>	<b>Re-applying updates of session session</b>
<b>Explanation</b>	The recover process has started re-applying updates of the next session.
<b>Action</b>	No action required.
<b>INODSR2079</b>	<b>Re-applying updates completed</b>
<b>Explanation</b>	The recover process has finished.
<b>Action</b>	No action required.
<b>INODSR5347</b>	<b>Preparing external backup</b>
<b>Explanation</b>	This is an information message.
<b>Action</b>	No action required.
<b>INODSR5348</b>	<b>Synchronizing database</b>
<b>Explanation</b>	This is an information message.
<b>Action</b>	No action required.
<b>INODSR5349</b>	<b>Processing external backup</b>
<b>Explanation</b>	This is an information message.
<b>Action</b>	No action required.
<b>INODSR5350</b>	<b>Performing final cleanup</b>
<b>Explanation</b>	This is an information message.
<b>Action</b>	No action required.

<b>INODSR5351</b>	<b>Processing external restore</b>
<b>Explanation</b>	This is an information message.
<b>Action</b>	No action required.
<b>INODSR5362</b>	<b>Processing backup</b>
<b>Explanation</b>	A backup operation is currently being processed.
<b>Action</b>	No action required.
<b>INODSR5363</b>	<b>Processing restore</b>
<b>Explanation</b>	A restore operation is currently being processed.
<b>Action</b>	No action required.
<b>INODSS1005</b>	<b>Create database space</b>
<b>Explanation</b>	This message indicates that the specified function is in progress.
<b>Action</b>	No action required.
<b>INODSS1009</b>	<b>Delete database space</b>
<b>Explanation</b>	This message indicates that the specified function is in progress.
<b>Action</b>	No action required.
<b>INODSS1089</b>	<b>Creating database with reorganization ...</b>
<b>Explanation</b>	The database will be created from a backup with defragmentation of the database layout.
<b>Action</b>	No action required.
<b>INODSS1711</b>	<b>Recovering from abnormal termination</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.
<b>INODSS1712</b>	<b>Starting database server</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.

---

<b>INODSS1713</b>	<b>Checking database for index inconsistencies</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.
<b>INODSS1714</b>	<b>Deleting database 'database_name'</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.
<b>INODSS2025</b>	<b>Creating database ...</b>
<b>Explanation</b>	Tamino is creating a new database.
<b>Action</b>	No action required.
<b>INODSS2076</b>	<b>Performing recovery</b>
<b>Explanation</b>	The restore/recover process is in the recover phase.
<b>Action</b>	No action required.
<b>INODSS2159</b>	<b>Converting database</b>
<b>Explanation</b>	The database is being upgraded or downgraded.
<b>Action</b>	No action required.
<b>INODST1751</b>	<b>Start of Tamino name version modifierversionmodifier2 on system info</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.
<b>INODST1752</b>	<b>Database database name Session session number (name modifierversion on system info, process ID pid)</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.
<b>INODST1753</b>	<b>Database database name Read-Only Session (name modifierversion on system info, process ID pid)</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.

<b>INODST1766</b>	<b>Database database name Replication Session (name modifierversion on system info, processID pid)</b>
<b>Explanation</b>	The server started for a replication database.
<b>Action</b>	No action required.
<b>INODST1781</b>	<b>Start of product name on system info</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.
<b>INODSV1053</b>	<b>Database autorepair suppressed</b>
<b>Explanation</b>	The previous server session terminated abnormally. The server attempted to perform an autorepair, but the autorepair has been suppressed by external manipulation. The database might be in an inconsistent state.
<b>Action</b>	Determine what kind of manipulation has occurred and contact your software supplier.
<b>INODSV1129</b>	<b>System error errno occurred</b>
<b>Explanation</b>	A system error has occurred in the context of the current task.
<b>Action</b>	Check the manufacturer's manual.
<b>INODSV1174</b>	<b>No input data available</b>
<b>Explanation</b>	The specified input file is empty.
<b>Action</b>	Ensure that the correct input file is being used.
<b>INODSV1245</b>	<b>Error information: log space of server session session number - block block, location record</b>
<b>Explanation</b>	The information describes the location of the recently processed log space data
<b>Action</b>	Keep this information when log space data analysis is required.
<b>INODSV1258</b>	<b>Journal overflow. Server cannot proceed.</b>
<b>Explanation</b>	The journal space was insufficient. The current server session has to be terminated.
<b>Action</b>	Check if more journal space can be provided. Restart the server.

---

<b>INODSV1281</b>	<b>Component comp called at extension point extp returned response rsp</b>
<b>Explanation</b>	The Tamino server called an external component which returned an error response.
<b>Action</b>	Please contact your software supplier.
<b>INODSV1473</b>	<b>The database server is active on the local node</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.
<b>INODSV1587</b>	<b>Internal event SCLOST has occurred</b>
<b>Explanation</b>	A sort action has failed due to resource problems. A retry will be started automatically.
<b>Action</b>	No action required.
<b>INODSV1801</b>	<b>Previous server session failed during write operation</b>
<b>Explanation</b>	The previous server session was performing a write operation on modified data when the server session terminated abnormally.
<b>Action</b>	If you can be sure that a single write operation is atomic on your system, you can ignore this warning. You can always assume so if there was no power failure and if the previous server session did not abort due to an I/O error. If you cannot be sure, recover your database from the last backup.
<b>INODSV1806</b>	<b>Aborted by operator</b>
<b>Explanation</b>	The operator has explicitly aborted the operation.
<b>Action</b>	No action required.
<b>INODSV1818</b>	<b>Log space of server session session number is empty</b>
<b>Explanation</b>	An input file to be used for recovery is empty.
<b>Action</b>	Check that the correct log space files are present at the log space location.
<b>INODSV2083</b>	<b>Unlocking port allocation lock failed with response err - int_err</b>
<b>Explanation</b>	An unexpected response was received while trying to unlock the port allocation lock.
<b>Action</b>	Please contact your software supplier.

<b>INODSV2118</b>	<b>Unlocking raw section lock failed with response err - int_err</b>
<b>Explanation</b>	Unexpected response received while trying to unlock the raw section lock.
<b>Action</b>	Please contact your software supplier.
<b>INODSV2139</b>	<b>Unlocking raw section lock failed with response err - int_err</b>
<b>Explanation</b>	Unexpected response received while trying to unlock the container move lock.
<b>Action</b>	Please contact your software supplier.
<b>INODSV2226</b>	<b>System error error (string) occurred</b>
<b>Explanation</b>	An internal system service error occurred.
<b>Action</b>	Analyze the error number and the human readable text.
<b>INODSV2273</b>	<b>The server servername is active</b>
<b>Explanation</b>	The specified server is active.
<b>Action</b>	No action required.
<b>INODSV2276</b>	<b>Aborted by High Availability monitor</b>
<b>Explanation</b>	The High Availability monitor detected that the server did not respond within a specific timeout limit and forced an abnormal crash of this server. There could be two cases: either the server is really hanging or there is something very busy that the check by the High Availability monitor takes a very long time (e.g. a huge buffer flush is in progress).
<b>Action</b>	Check if the HA timeout value is reasonable with the context. One dangerous situation can be a long enduring buffer flush which might block applications for a long time. Maybe it is reasonable to run with small flush limit and/or flush group size parameters.
<b>INODSV2281</b>	<b>System error errno (errtxt) when opening database space space no (path)</b>
<b>Explanation</b>	An internal operating system error has occurred while trying to open a database space.
<b>Action</b>	Analyse the error text and consult the manufacturer's manual.
<b>INODSV5266</b>	<b>Journal overflow. Current activity cancelled.</b>
<b>Explanation</b>	The journal space was insufficient. The current activity has been cancelled. Typically, a transaction has been rolled back internally.
<b>Action</b>	Provide more journal space. Restart the terminated activity.

---

<b>INODSV5269</b>	<b>Server is already registered with the Software AG XTS Directory Server</b>
<b>Explanation</b>	When the server starts it registers with the Software AG XTS Directory Server. It is possible that entries for the server are already present (server already started somewhere else or previous server session failed). If this message comes as a warning message, the entry found exactly matches the one that should be entered. If this message comes as an error message, the entry found did not match the entry that the server wanted to add.
<b>Action</b>	If this message comes as a warning message no action is required. If this message comes as an error message the Software AG XTS Directory Server entry found for the server should be checked and, if no longer necessary, the next server start should be done with the parameter for overwriting the Software AG XTS Directory Server entry activated.
<b>INODSW1014</b>	<b>Creation of word fragment index failed</b>
<b>Explanation</b>	Creation of word fragment index failed, because corresponding index tree is inaccessible.
<b>Action</b>	Use the function "check and repair database" and restart the server.
<b>INODSW1017</b>	<b>Due to license restrictions, recovery of the database will not be possible</b>
<b>Explanation</b>	Your license file does not allow logging to be enabled. Due to this restriction, recovery of the database will not be possible.
<b>Action</b>	Contact your software supplier for an upgrade of your license.
<b>INODSW1035</b>	<b>Synchronization semaphore lost and recreated</b>
<b>Explanation</b>	The synchronization semaphore was deleted from outside and a new one was created.
<b>Action</b>	No action required.
<b>INODSW1115</b>	<b>Incremental backup disabled due to buffer pool allocation failure</b>
<b>Explanation</b>	An incremental backup is not possible because no space was available for the information of modified blocks.
<b>Action</b>	Create the next backup as a full backup. To avoid the allocation failure increase the buffer pool.
<b>INODSW1116</b>	<b>Incremental backup disabled due to error error</b>
<b>Explanation</b>	An incremental backup is not possible due to an error when maintaining the information of modified blocks.
<b>Action</b>	Create the next backup as a full backup. If the error persists, contact your software supplier.

<b>INODSW1151</b>	<b>Further recovery for doctype doctype will not include index</b>
<b>Explanation</b>	Due to an error during recovery the index of the doctype has been disabled.
<b>Action</b>	Even though the index was disabled, data has been recovered. The index can be rebuilt using the "Check and Repair" function.
<b>INODSW1340</b>	<b>The last available backup could not be deleted</b>
<b>Explanation</b>	It doesn't make much sense to delete all backups. To avoid the situation that someone deletes the last backup by mistake, this deletion is not allowed.
<b>Action</b>	If you want to delete this special last backup, you have to create a new one.
<b>INODSW1372</b>	<b>Waiting for space on space location</b>
<b>Explanation</b>	The location where the file wants to grow has no more free space and the current request will wait until space is available.
<b>Action</b>	Either delete unused files from the location that has insufficient space or define a new location with enough space for that file.
<b>INODSW1401</b>	<b>A transaction has been heuristically committed at time</b>
<b>Explanation</b>	The database system has committed a transaction for which a decision of the transaction manager was pending.
<b>Action</b>	No action required.
<b>INODSW1406</b>	<b>Log space of server session session number processed until time</b>
<b>Explanation</b>	None of the information generated after the given end timestamp of the log space of the specified server session was processed.
<b>Action</b>	Verify that the skipped part of the log space is the same as was skipped with a previous recovery.
<b>INODSW1407</b>	<b>Replication of server session session number resumed using replication data from timestamp. Simultaneous query will be enabled when replication database is up-to-date.</b>
<b>Explanation</b>	The server continued replication processing after replication database startup.
<b>Action</b>	No action required. The database server will automatically enable simultaneous read when the locking information becomes available, at the latest when replicating the current master database session.

---

<b>INODSW1409</b>	<b>Error when opening database space space no (at path): size mismatch</b>
<b>Explanation</b>	The size of the database space is not equal to the size expected by the server.
<b>Action</b>	Please contact your software supplier.
<b>INODSW1410</b>	<b>Error when opening database space space number (at path)</b>
<b>Explanation</b>	The database space could not be opened.
<b>Action</b>	Check the affected device: is it on-line, are the permissions correct, can operating system tools access the device? If you cannot find the reason for the read error by yourself, please contact your software supplier.
<b>INODSW1411</b>	<b>Error when opening database space, compressed state is not permitted (at path)</b>
<b>Explanation</b>	The database file has the compressed attribute, which is not permitted, because write errors should be avoided if the device is getting full.
<b>Action</b>	Remove the compressed attribute from the database file.
<b>INODSW1412</b>	<b>System error errno when opening database space space no (path)</b>
<b>Explanation</b>	The specified operating system error has occurred.
<b>Action</b>	Please consult the manufacturer's manual.
<b>INODSW1414</b>	<b>System error errno when opening database space space no (path)</b>
<b>Explanation</b>	The specified operating system error has occurred.
<b>Action</b>	Please consult the manufacturer's manual.
<b>INODSW1415</b>	<b>Replication of server session session number from timestamp started. Simultaneous query will be enabled when replication database is up-to-date.</b>
<b>Explanation</b>	The replication processing has started to process the log space data of the specified server session of the master database.
<b>Action</b>	No action required. The database server will automatically enable simultaneous read when the locking information becomes available, at the latest when replicating the current master database session.
<b>INODSW1418</b>	<b>Replication of server session session number stopped. Replication data processed until timestamp.</b>
<b>Explanation</b>	Replication processing is stopped due to an error as described in previous messages. If simultaneous queries were permitted, then the replication database stays online and may be used for further queries.
<b>Action</b>	Try to solve the problem at the master database's side or recreate the replication database from a new backup of the master.

<b>INODSW1455</b>	<b>Database start not allowed because of pending "set version" operation. Please re-execute "set version".</b>
<b>Explanation</b>	A previous "set version" operation aborted. The database may be inconsistent.
<b>Action</b>	Try "set version" again. If it fails also the second time, report the problem to your software supplier.
<b>INODSW1482</b>	<b>Log space of server session session number not to be processed.</b>
<b>Explanation</b>	The log space of the specified server session was not processed because it was skipped by a previous recovery run.
<b>Action</b>	Verify that the skipped log space has also been skipped by the previous recovery run.
<b>INODSW1529</b>	<b>switch internal I/O mode</b>
<b>Explanation</b>	The I/O mode was switched because an internal I/O function is not supported by given platform. This could happen if a platform does not support the call lio_listio().
<b>Action</b>	No action required.
<b>INODSW1602</b>	<b>Insufficient disk space for journal space, resize to: size MB</b>
<b>Explanation</b>	There is insufficient disk space to create journal space of the required size; a reduced size will be used.
<b>Action</b>	No action required.
<b>INODSW1689</b>	<b>Parallel backup not available on Windows, a sequential backup will be performed.</b>
<b>Explanation</b>	The Windows version of backup does not support 'parallel backup', therefore a sequential backup will be performed.
<b>Action</b>	No action required.
<b>INODSW1784</b>	<b>There is a pending autorepair for the database</b>
<b>Explanation</b>	The database had previously not terminated correctly.
<b>Action</b>	When the database has been restarted, it will perform an autorepair operation.
<b>INODSW1800</b>	<b>This is an emergency restart</b>
<b>Explanation</b>	The server stopped the previous server session due to shortage of journal space. If this restart fails, data may be lost or inconsistent.
<b>Action</b>	If the restart fails, please recover your data from the last backup.

<b>INODSW1802</b>	<b>A transaction has been heuristically rolled back at time</b>
<b>Explanation</b>	The database system has rolled back a transaction for which a decision of the transaction manager was pending.
<b>Action</b>	No action required.
<b>INODSW1803</b>	<b>A transaction has been heuristically committed at time</b>
<b>Explanation</b>	The database system has committed a transaction for which a decision of the transaction manager was pending.
<b>Action</b>	No action required.
<b>INODSW1804</b>	<b>Backup task not responding. Ignoring backup activity.</b>
<b>Explanation</b>	A backup task was running when the server came up. The server synchronization with this backup task has failed. The backup will terminate eventually.
<b>Action</b>	Check if the backup activity is still running. If so, it can be terminated. Redo the backup.
<b>INODSW1805</b>	<b>The server cannot proceed until the backup activity has finished</b>
<b>Explanation</b>	The server will wait for the backup activity to complete. When it has finished, the server will continue.
<b>Action</b>	No action required.
<b>INODSW1807</b>	<b>Switched to read-only mode because a database space is not writable</b>
<b>Explanation</b>	The database will not accept updates.
<b>Action</b>	If this behavior is not intended, make all database spaces write-accessible.
<b>INODSW1808</b>	<b>Read-only database</b>
<b>Explanation</b>	The database is read-only. Some functions are disabled.
<b>Action</b>	No action required.
<b>INODSW1809</b>	<b>Error when opening database space space no (at path): size mismatch, expected bytes bytes</b>
<b>Explanation</b>	The size of the database space is not equal to the size expected by the server.
<b>Action</b>	If the operation does not complete successfully, please contact your software supplier.

<b>INODSW1810</b>	<b>database space space no opened for read-only access</b>
<b>Explanation</b>	The specified database space was opened for read-only access. No updates will be possible on this database space.
<b>Action</b>	No action required.
<b>INODSW1811</b>	<b>Database might be corrupted</b>
<b>Explanation</b>	An inconsistency has been found in the database.
<b>Action</b>	Check the database for consistency.
<b>INODSW1812</b>	<b>Backup process is not responding</b>
<b>Explanation</b>	The synchronization between the backup process and the server has been lost. One possible reason is that the backup process has been killed. The backup will not come to a normal end.
<b>Action</b>	Restart the backup.
<b>INODSW1813</b>	<b>Backup process is not communicating completion</b>
<b>Explanation</b>	The synchronization between the backup process and the server has been lost. One possible reason is that the backup process has been killed. The backup will not come to a normal end.
<b>Action</b>	Restart the backup.
<b>INODSW1814</b>	<b>Backup process is not fetching modified data</b>
<b>Explanation</b>	The synchronization between the backup process and the server has been lost. One possible reason is that the backup process has been killed. The backup will not come to a normal end.
<b>Action</b>	Restart the backup.
<b>INODSW1815</b>	<b>Before image mismatch for number instances on doctype doctype</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INODSW1817</b>	<b>Read-only database server accessed</b>
<b>Explanation</b>	A utility is being run against a read-only database server. Certain functions may not be available.
<b>Action</b>	No action required.

---

<b>INODSW1819</b>	<b>Invalid starting block number block number for log space from session session number</b>
<b>Explanation</b>	The log space does not contain correct log information.
<b>Action</b>	Check if files have been moved or copied to the log space location.
<b>INODSW1823</b>	<b>Unable to remove shared memory</b>
<b>Explanation</b>	It has not been possible to remove a shared memory segment.
<b>Action</b>	Remove any allocated shared memory with available system tools.
<b>INODSW1825</b>	<b>Unexpected database error: resp</b>
<b>Explanation</b>	An internal database error has occurred.
<b>Action</b>	Please contact your software supplier.
<b>INODSW1827</b>	<b>Function is deactivated</b>
<b>Explanation</b>	The requested function is not activated at present.
<b>Action</b>	No action required.
<b>INODSW1828</b>	<b>Doctype deleted but de-allocation failed (reason code reason)</b>
<b>Explanation</b>	A doctype has been deleted from the database but it could not be de-allocated.
<b>Action</b>	Determine the cause of the failure from the supplied reason code.
<b>INODSW1829</b>	<b>Unable to remove utility flag and/or write event</b>
<b>Explanation</b>	The utility was in its final cleanup phase but could not complete all required actions.
<b>Action</b>	The utility has terminated successfully, but the cause of the cleanup failure should be determined.
<b>INODSW1830</b>	<b>Event could not be written due to response response</b>
<b>Explanation</b>	The utility has failed to write a final event due to the response reported.
<b>Action</b>	The utility will end successfully. The response code indicates the reason for the failure to write an event.

<b>INODSW1835</b>	<b>Waiting for debugger to attach</b>
<b>Explanation</b>	This message is displayed by debug-enabled executables if they have been selected for debugging.
<b>Action</b>	Please contact your software supplier.
<b>INODSW1836</b>	<b>Mass load recovery files not archived</b>
<b>Explanation</b>	The mass load recovery files could not be copied to the archive location.
<b>Action</b>	Check for a reason why files could not be created at the archive location. Copy the mass load recovery files manually.
<b>INODSW1837</b>	<b>An error occurred during the create index process on doctype doctype</b>
<b>Explanation</b>	The error is caused by an attempt to create a unique index for non-unique data values.
<b>Action</b>	Contact your software supplier.
<b>INODSW1838</b>	<b>Log space of server session session number processed until time</b>
<b>Explanation</b>	None of the information generated after the given end timestamp of the log space of the specified server session was processed.
<b>Action</b>	Verify that the skipped part of the log space is the same as was skipped with a previous recovery.
<b>INODSW1839</b>	<b>Log space of server session session number extent extent number not archived</b>
<b>Explanation</b>	A log space extent could not be copied to the archive location.
<b>Action</b>	Check the log archive location name and for available space.
<b>INODSW1840</b>	<b>Log space of server session session number extent extent number not closed</b>
<b>Explanation</b>	A log space extent could not be closed.
<b>Action</b>	No action required.
<b>INODSW1841</b>	<b>Database successfully checked and repaired. Number of repaired indexes is number.</b>
<b>Explanation</b>	The database has been repaired.
<b>Action</b>	No action required.

---

<b>INODSW1842</b>	<b>Update in internal configuration store could not be logged</b>
<b>Explanation</b>	Configuration was successfully updated, however the update could not be logged. Possible reasons may be - update log file is read-only or there is not enough space on device where Tamino is installed.
<b>Action</b>	In most cases this warning can be ignored. Inform your system administrator about the warning.
<b>INODSW1843</b>	<b>No information about previous recovery processing</b>
<b>Explanation</b>	Recovery processing was aborted without being able to write recovery progress information.
<b>Action</b>	See the instructions within subsequent messages.
<b>INODSW1845</b>	<b>Continuing server startup will disable all existing backups</b>
<b>Explanation</b>	A preceding Restore/Recover operation that specified an "until" date that is earlier than the latest backup was performed. This means that any backup that was performed after the "until" date of the Restore/Recover operation is no longer valid.
<b>Action</b>	Create a new database backup as soon as possible.
<b>INODSW1846</b>	<b>All backups disabled, create a new backup copy</b>
<b>Explanation</b>	No information about previous recovery processing was available, all backups have been disabled.
<b>Action</b>	Create a new database backup as soon as possible.
<b>INODSW1848</b>	<b>Container file could not be extended, but attempt to continue</b>
<b>Explanation</b>	The database could not be extended as the backup file signalled. The restore is continued but later I/O errors are possible.
<b>Action</b>	You can ignore this message if the restore terminates successfully. If the restore fails due to an I/O error you must check why the database could not be extended.
<b>INODSW1980</b>	<b>Skipping recovery terminated with warning status</b>
<b>Explanation</b>	While skipping the recovery a situation occurred that requires further investigation.
<b>Action</b>	Check for additional messages in the event log.

<b>INODSW1981</b>	<b>Recovery terminated with warning status</b>
<b>Explanation</b>	During recovery a situation occurred that requires further investigation.
<b>Action</b>	Check for additional messages in the event log.
<b>INODSW1993</b>	<b>keyword combination not allowed</b>
<b>Explanation</b>	The supplied keyword combination is invalid.
<b>Action</b>	Correct the input parameters.
<b>INODSW1997</b>	<b>Due to license restrictions, the database will be started in readonly mode</b>
<b>Explanation</b>	Your license is restricted to readonly mode. Due to this restriction, updates of the database will not be possible.
<b>Action</b>	Contact your software supplier for an upgrade of your license.
<b>INODSW2047</b>	<b>Version cd database version not installed, using compatible version instead</b>
<b>Explanation</b>	The version of the CD database is not installed on the target system. However a compatible version was found and will be used.
<b>Action</b>	No action required.
<b>INODSW2066</b>	<b>Journal size specified is less than the minimum allowed size of numberMB. Increasing to numberMB.</b>
<b>Explanation</b>	The journal size specified is less than the minimum required to allow correct operation of the server. Tamino is adjusting the journal size up to the minimum size.
<b>Action</b>	No action required.
<b>INODSW2073</b>	<b>Previous log file corrupted (reason: reason). Please perform a database backup as soon as possible.</b>
<b>Explanation</b>	During restart after a database crash it was detected that the log file of the previous session is corrupt. A database recovery may fail, therefore a new backup would resolve this situation. Moreover a further database replication would fail, therefore if the database is or will be a replication master the replication must be newly set up with a new database backup.
<b>Action</b>	Perform a new database backup. Revise replication. Reestablish replication with the new database backup.

---

<b>INODSW2089</b>	<b>Port port already in use as name by server server</b>
<b>Explanation</b>	The port to check is already in use.
<b>Action</b>	Choose another port or be aware that problems with port usage might occur.
<b>INODSW2090</b>	<b>Port port used as name by server server is located in selected dynamic port range</b>
<b>Explanation</b>	An allocated port was found in the dynamic port range.
<b>Action</b>	Specify another dynamic port range or change the allocated port so that it is located outside the dynamic port range.
<b>INODSW2098</b>	<b>Web server webserver assigned to database server</b>
<b>Explanation</b>	The web server is assigned to a database and must not be removed before it is deassigned.
<b>Action</b>	Keep this web server definition or deassign it from all databases.
<b>INODSW2101</b>	<b>Web server configuration changed, notification of server server failed (rc1,rc2,rc3)</b>
<b>Explanation</b>	The web server configuration was changed, but the server notification failed.
<b>Action</b>	The server has to be restarted manually.
<b>INODSW2102</b>	<b>Web server configuration changed for web server webserver, but server notification failed</b>
<b>Explanation</b>	The web server configuration was changed, but the notification of active servers failed.
<b>Action</b>	Restart all active servers which have assigned the web server in question.
<b>INODSW2112</b>	<b>User specified record ID number is not within proposed range</b>
<b>Explanation</b>	The load utility was called with at least one record ID which is within a used range. In the event of a crash the internal doctype may have a corruption.
<b>Action</b>	This is an internal problem. Please contact your software supplier.
<b>INODSW2113</b>	<b>Cleanup of a mass load failed with error</b>
<b>Explanation</b>	The cleanup task, e.g. within a rollback, of a mass load failed for internal reasons.
<b>Action</b>	Please contact your software supplier.

<b>INODSW2133</b>	<b>Nothing to verify, no data available</b>
<b>Explanation</b>	The item only contains index values, therefore no verification is necessary.
<b>Action</b>	No action required.
<b>INODSW2147</b>	<b>Replication of server session session number resumed using replication data from timestamp. Simultaneous query will be enabled when replication database is up-to-date.</b>
<b>Explanation</b>	The server continued replication processing after replication database startup.
<b>Action</b>	No action required. The database server will automatically enable simultaneous read when the locking information becomes available, at the latest when replicating the current master database session.
<b>INODSW2152</b>	<b>Port port is currently active and may not be usable</b>
<b>Explanation</b>	The specified port is currently active and may not be usable by the Tamino server.
<b>Action</b>	Specify another port for the Tamino server or free up the active port before starting the Tamino server.
<b>INODSW2153</b>	<b>Flush limit too high. Value adjusted to new value.</b>
<b>Explanation</b>	The flush limit specified was too high. It has been adjusted to a reasonable value.
<b>Action</b>	To avoid this warning at each startup of the database, configure a lower value.
<b>INODSW2155</b>	<b>Replication of server session session number from timestamp started. Simultaneous query will be enabled when replication database is up-to-date.</b>
<b>Explanation</b>	The replication processing has started to process the log space data of the specified server session of the master database.
<b>Action</b>	No action required. The database server will automatically enable simultaneous read when the locking information becomes available, at the latest when replicating the current master database session.
<b>INODSW2156</b>	<b>Database name1 is fully overlaid with backup from database name2</b>
<b>Explanation</b>	The backup file which was created by a foreign database has been restored into the current database. The previous content of the database has been completely deleted.
<b>Action</b>	No action required.

---

<b>INODSW2161</b>	<b>corrupted data repaired</b>
<b>Explanation</b>	A detected corruption was repaired immediately by Tamino.
<b>Action</b>	No action required.
<b>INODSW2171</b>	<b>Replication data of session session requires new Tamino version version</b>
<b>Explanation</b>	The replication database is using a different Tamino version than the master database.
<b>Action</b>	Install the required Tamino version at the replication database node. If the required version is already installed and the error still exists, re-create the replication database using a backup created from this Tamino version.
<b>INODSW2172</b>	<b>Master database must be restarted before a replication database can be set up</b>
<b>Explanation</b>	The name of the first replication database has been added to the permission list. The database can be set up as a replication database of this master only after the master has been stopped and restarted.
<b>Action</b>	Stop the master database and start it again.
<b>INODSW2180</b>	<b>Connection to server lost, reason reason</b>
<b>Explanation</b>	The working process must be terminated because the server is stopping or has already stopped. There are 2 possible reasons: 0 means the server has stopped, 1 means the server is stopping and has aborted the process.
<b>Action</b>	Check why the server stopped.
<b>INODSW2186</b>	<b>The configured buffer pool size (lbp MB) exceeds the machine's physical memory size (pms MB)</b>
<b>Explanation</b>	The buffer pool size is configured so that it exceeds the physical memory size of the machine. This does not make sense because the buffer pool replacement strategy will collide with the operating systems memory management.
<b>Action</b>	Choose a buffer pool size that is at least smaller than the machine's physical memory size.
<b>INODSW2191</b>	<b>The maximum number of threads allowed per process (max_threads) may not be sufficient to manage the database server</b>
<b>Explanation</b>	The current parameter configuration may not allow the creation of all necessary threads to manage the database server.
<b>Action</b>	Either the system defined maximum number of threads per process is too low and should be increased, or the database parameter configuration should be changed to decrease the number of threads to be created.

<b>INODSW2195</b>	<b>Connection to master database master dbname interrupted</b>
<b>Explanation</b>	The replication database cannot obtain replication data from its master database.
<b>Action</b>	No action required.
<b>INODSW2197</b>	<b>Replication of server session session number stopped. Replication data processed until timestamp.</b>
<b>Explanation</b>	Replication processing is stopped due to an error as described in previous messages. If simultaneous queries were permitted, then the replication database stays online and may be used for further queries.
<b>Action</b>	Try to solve the problem at the master database's side or recreate the replication database from a new backup of the master.
<b>INODSW2198</b>	<b>Update logging in internal configuration store is not active</b>
<b>Explanation</b>	Updates in the internal configuration store are not logged because update logging is not activated in the current process.
<b>Action</b>	Please contact your software supplier.
<b>INODSW2207</b>	<b>No reading process attached to pipe path</b>
<b>Explanation</b>	Backup location is a named pipe and no process has the pipe open for reading. This situation may occur during database backup or database creation, when initial backup is being made.
<b>Action</b>	Start the process that reads from the pipe and perform the backup again.
<b>INODSW2209</b>	<b>Inconsistent location definition (location) - expected type expected, real type real</b>
<b>Explanation</b>	The location type is unexpected. This is typically the result of user intervention , for example the user deletes a location directory and creates a file with the same name.
<b>Action</b>	Make sure that Tamino locations are not modified outside of Tamino.
<b>INODSW2210</b>	<b>Location location is nearly full</b>
<b>Explanation</b>	Not enough disk space is left on the location.
<b>Action</b>	Free some space or use another location.

---

<b>INODSW2230</b>	<b>Logging error in internal configuration store occurred at time, future updates may not be logged</b>
<b>Explanation</b>	The internal configuration store showed an update logging error that occurred in the past. There is a chance that future updates will also not be logged, thus preventing a repair of the internal configuration store after a severe error. This message is displayed at each server startup unless you execute the described actions.
<b>Action</b>	To be sure to be able to recreate all configuration data, you can do the following: Copy your registry (all under the key 'Tamino') to a file. Use the 'export' function of your registry editor. Then clean your registry logging file or use another file. The registry logging file is defined with a string value at the registry key 'Tamino'. Combining both files lets you repair your Tamino registry in the case of a corruption. Finally you can remove the 'registry logging error' string value from the registry either with your registry editor or with the Registry functions of your Tamino manager.
<b>INODSW2238</b>	<b>No space to remove</b>
<b>Explanation</b>	The request to remove database space cannot be performed, because trailing space is in use.
<b>Action</b>	No action required.
<b>INODSW2240</b>	<b>File/path path does not exist or is not accessible</b>
<b>Explanation</b>	The given file/pathname does not exist or is not accessible. It will just be skipped.
<b>Action</b>	Check the file/pathname.
<b>INODSW2244</b>	<b>Cannot create initial backup - reference to original one is not possible; perform backup for the database as soon as possible</b>
<b>Explanation</b>	The initial backup for the new database could not be created. It tries to reference this backup, but the backup is already registered with another active database. So the database is left without a valid backup !
<b>Action</b>	Perform a database backup as soon as possible.
<b>INODSW2245</b>	<b>Cannot create initial backup - but referred to original one</b>
<b>Explanation</b>	The creation of the initial backup of the new database failed. Nevertheless a backup entry was set up pointing to the file/device where the creation-backup comes from. This has the same effect as when the nocopyoption has been used.
<b>Action</b>	No action required.

<b>INODSW2246</b>	<b>Reference to original backup is not possible; perform backup for the database as soon as possible</b>
<b>Explanation</b>	The create from backup was used with the nocopy option, which means that the incoming backup file will just be referenced instead of copied. But it is not permitted to reference a backup file which is already registered with an active database. Now there is no valid backup for the created database
<b>Action</b>	Perform a database backup as soon as possible.
<b>INODSW2247</b>	<b>Location skipped (no space)</b>
<b>Explanation</b>	The given location has not enough space for creating a database file. It skips to the next location if any.
<b>Action</b>	Check the space in this location.
<b>INODSW2248</b>	<b>Location skipped, (internal error err)</b>
<b>Explanation</b>	The current location cannot be used and will be skipped. The internal error displayed gives the detailed reason.
<b>Action</b>	Analyse the error and check the path name of the location.
<b>INODSW2260</b>	<b>create / delete database synchronization failed with (error)</b>
<b>Explanation</b>	The semaphore synchronisation failed with an internal error.
<b>Action</b>	Do not start another create / delete database in parallel.
<b>INODSW2261</b>	<b>Removing backup file (filename) failed due to internal error error</b>
<b>Explanation</b>	The given backup file cannot be removed due to displayed error reason, but it will be unregistered.
<b>Action</b>	Delete the backup file by hand if you decide that it would never be needed any more.
<b>INODSW2262</b>	<b>Problem during referencing initial backup file (file), reason: reason</b>
<b>Explanation</b>	A reference operation (insert/delete) to a backup file failed. A reference will be set up at create database from backup to the source backup file. If the setting of a reference failed, then it may happen that the owner of the backup deletes the backup file although a foreign database has it still registered. If this operation failed at the owner side, it may happen that the backup file remains in the file system although it was logically deleted.
<b>Action</b>	Check the databases where this backup file is registered. Maybe perform a new backup of databases which have this backup file registered.

---

<b>INODSW2269</b>	<b>Failed to load ADABAS interface (library)</b>
<b>Explanation</b>	The Tamino server failed to load the ADABAS interface.
<b>Action</b>	Provide a valid ADABAS interface in one of the locations searched during the library load.
<b>INODSW2277</b>	<b>Buffer pool size set to size MB due to shortage of shared memory</b>
<b>Explanation</b>	The available shared memory was not large enough to allocate the buffer pool with the configured size.
<b>Action</b>	Check whether the configured size of the buffer pool meets the memory resources available within the given environment.
<b>INODSW2297</b>	<b>Perform emergency shutdown, because server is within a space wait situation</b>
<b>Explanation</b>	The server is waiting for space on the log file, therefore a clean shutdown is not possible. It aborts the server with a pending autorepair.
<b>Action</b>	Clean up the log space location and restart the server.
<b>INODSW2318</b>	<b>The license for name with ID id expires in number days</b>
<b>Explanation</b>	The license expires soon. After license expiration the server cannot be used any longer. The server will abort and cannot be restarted.
<b>Action</b>	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.
<b>INODSW2319</b>	<b>The license for customername sub-licensed by partnername with ID partnerid expires in number days</b>
<b>Explanation</b>	The license expires soon. After license expiration the server cannot be used any longer. The server will abort and cannot be restarted.
<b>Action</b>	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.
<b>INODSW2320</b>	<b>The license for customername with ID customerid sub-licensed by partnername expires in number days</b>
<b>Explanation</b>	The license expires soon. After license expiration the server cannot be used any longer. The server will abort and cannot be restarted.
<b>Action</b>	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.

<b>INODSW2321</b>	<b>The license for customername with ID customerid sub-licensed by partnername with ID partnerid expires in number days</b>
<b>Explanation</b>	The license expires soon. After license expiration the server cannot be used any longer. The server will abort and cannot be restarted.
<b>Action</b>	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.
<b>INODSW2322</b>	<b>The license for name with ID id expires in 1 day</b>
<b>Explanation</b>	The license expires soon. After license expiration the server cannot be used any longer. The server will abort and cannot be restarted.
<b>Action</b>	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.
<b>INODSW2323</b>	<b>The license for customername sub-licensed by partnername with ID partnerid expires in 1 day</b>
<b>Explanation</b>	The license expires soon. After license expiration the server cannot be used any longer. The server will abort and cannot be restarted.
<b>Action</b>	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.
<b>INODSW2324</b>	<b>The license for customername with ID customerid sub-licensed by partnername expires in 1 day</b>
<b>Explanation</b>	The license expires soon. After license expiration the server cannot be used any longer. The server will abort and cannot be restarted.
<b>Action</b>	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.
<b>INODSW2325</b>	<b>The license for customername with ID customerid sub-licensed by partnername with ID partnerid expires in 1 day</b>
<b>Explanation</b>	The license expires soon. After license expiration the server cannot be used any longer. The server will abort and cannot be restarted.
<b>Action</b>	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.

---

<b>INODSW2326</b>	<b>The license for name with ID id has expired, server will abort in number days</b>
<b>Explanation</b>	The license has expired. The server will not restart any more. Final abort after a grace period of 10 days after license expiration.
<b>Action</b>	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.
<b>INODSW2327</b>	<b>The license for customername sub-licensed by partnername with ID partnerid has expired, server will abort in number days</b>
<b>Explanation</b>	The license has expired. The server will not restart any more. Final abort after a grace period of 10 days after license expiration.
<b>Action</b>	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.
<b>INODSW2328</b>	<b>The license for customername with ID customerid sub-licensed by partnername has expired, server will abort in number days</b>
<b>Explanation</b>	The license has expired. The server will not restart any more. Final abort after a grace period of 10 days after license expiration.
<b>Action</b>	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.
<b>INODSW2329</b>	<b>The license for customername with ID customerid sub-licensed by partnername with ID partnerid has expired, server will abort in number days</b>
<b>Explanation</b>	The license has expired. The server will not restart any more. Final abort after a grace period of 10 days after license expiration.
<b>Action</b>	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.
<b>INODSW2330</b>	<b>The license for name with ID id has expired, server will abort in 1 day</b>
<b>Explanation</b>	The license has expired. The server will not restart any more. Final abort after a grace period of 10 days after license expiration.
<b>Action</b>	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.
<b>INODSW2331</b>	<b>The license for customername sub-licensed by partnername with ID partnerid has expired, server will abort in 1 day</b>
<b>Explanation</b>	The license has expired. The server will not restart any more. Final abort after a grace period of 10 days after license expiration.
<b>Action</b>	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.

<b>INODSW2332</b>	<b>The license for customername with ID customerid sub-licensed by partnername has expired, server will abort in 1 day</b>
<b>Explanation</b>	The license has expired. The server will not restart any more. Final abort after a grace period of 10 days after license expiration.
<b>Action</b>	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.
<b>INODSW2333</b>	<b>The license for customername with ID customerid sub-licensed by partnername with ID partnerid has expired, server will abort in 1 day</b>
<b>Explanation</b>	The license has expired. The server will not restart any more. Final abort after a grace period of 10 days after license expiration.
<b>Action</b>	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.
<b>INODSW5255</b>	<b>Internal parameter error (param), using default</b>
<b>Explanation</b>	An invalid internal parameter value was found. The default parameter value is used.
<b>Action</b>	Please contact your software supplier.
<b>INODSW5274</b>	<b>number updates excluded on doctype doctype</b>
<b>Explanation</b>	Due to an error during recovery, not all updates have been re-applied.
<b>Action</b>	Check the previous error messages to find more information about the error.
<b>INODSW5275</b>	<b>Updates performed between server startup and recovery start</b>
<b>Explanation</b>	Updates between server startup and recovery start are not allowed.
<b>Action</b>	Please check subsequent messages for more information.
<b>INODSW5294</b>	<b>waiting for buffer flush end</b>
<b>Explanation</b>	The dump utility must wait until the Tamino server completes the buffer flush action.
<b>Action</b>	No action required.
<b>INODSW5329</b>	<b>Sort request couldn't be specified, reason subc</b>
<b>Explanation</b>	A sort request failed, for the reason specified in the message
<b>Action</b>	Contact your software supplier.

---

<b>INODSW5340</b>	<b>Collating key truncated to size bytes</b>
<b>Explanation</b>	The collation key was truncated due to the size limit for index values. Only less important information was truncated.
<b>Action</b>	Normally, collation should be defined only for small pieces of data ( e.g. words), not for the large texts. Consider reviewing your collation definitions.
<b>INODSW5355</b>	<b>File system UNMOUNT problem, reason reason errtxt</b>
<b>Explanation</b>	Restoring an external backup may require the remounting of the file system. This is necessary to flush the file system cache.
<b>Action</b>	Remount the file system manually and contact your software supplier.
<b>INODSW5356</b>	<b>File system MOUNT problem, reason reason errtxt</b>
<b>Explanation</b>	Restoring an external backup may require the remounting of the file system. This is necessary to flush the file system cache
<b>Action</b>	Remount the file system manually and contact your software supplier.
<b>INODSW5400</b>	<b>Internal sort order lost</b>
<b>Explanation</b>	A sort request could not be satisfied due to internal reasons.
<b>Action</b>	You can force a memory dump with "inodba database=name trap=9299" for further analysis after reproducing the error.
<b>INODSW5401</b>	<b>Function not completely executed</b>
<b>Explanation</b>	A request failed due to internal reasons.
<b>Action</b>	You can force a memory dump with "inodba database=name trap=9298" for further analysis after reproducing the error.
<b>INOINE2051</b>	<b>Resetting the unique status on all indices</b>
<b>Explanation</b>	Duplicate values were detected. Therefore the unique status could not be set for the indices.
<b>Action</b>	Resolve any uniqueness conflicts before trying to set the unique status.
<b>INOINE2053</b>	<b>Index name already in use</b>
<b>Explanation</b>	The specified index name is already in use for this doctype.
<b>Action</b>	Retry the required operation with an unused index name.

<b>INOINF2251</b>	<b>Sort file too small or work pool too large</b>
<b>Explanation</b>	The sort file used is too small or the specified work pool is too large for the given sort file.
<b>Action</b>	Ensure that a sufficiently large sort file is available.
<b>INOINF2252</b>	<b>Sort file too small</b>
<b>Explanation</b>	The sort file used is too small.
<b>Action</b>	Ensure that a sufficiently large sort file is available.
<b>INOINF2253</b>	<b>Corrupt index found</b>
<b>Explanation</b>	Corrupt information has been found in the index.
<b>Action</b>	Please contact your software supplier, and/or reload the data to repair the damage.
<b>INOINI2174</b>	<b>Index processing completed on doctype doctype</b>
<b>Explanation</b>	The requested index operation has ended.
<b>Action</b>	No action required.
<b>INOINI2452</b>	<b>Index modification started</b>
<b>Explanation</b>	The database index modification process has started.
<b>Action</b>	No action required.
<b>INOINI2453</b>	<b>Index modification completed</b>
<b>Explanation</b>	The index modification process has completed.
<b>Action</b>	No action required.
<b>INOINI2454</b>	<b>Index cannot be sorted in main memory</b>
<b>Explanation</b>	The index process cannot perform the sort in main memory. This is an informational message. An external sort will be performed.
<b>Action</b>	No action required.
<b>INOINI2455</b>	<b>Index cannot be sorted</b>
<b>Explanation</b>	It is not possible to sort the index, probably due to a lack of space.
<b>Action</b>	Allow more space to be allocated for a main memory sort of the index, if possible.

---

<b>INOINI2456</b>	<b>Index cannot be processed in two passes</b>
<b>Explanation</b>	It is not possible to process the index in two passes due to insufficient temporary storage.
<b>Action</b>	Allocate more temporary storage to allow the index to be processed in two passes.
<b>INOINI2457</b>	<b>Index cannot be processed in one pass</b>
<b>Explanation</b>	It is not possible to process the index in one pass due to a lack of temporary storage.
<b>Action</b>	Allocate more temporary storage to allow the index to be processed in one pass.
<b>INOINI2459</b>	<b>Index verification limit has been reached</b>
<b>Explanation</b>	The number of errors found while verifying the index has reached the allowed limit.
<b>Action</b>	Correct the errors in the index, and run the certification process again.
<b>INOINI2460</b>	<b>Data space passes required: count</b>
<b>Explanation</b>	This is the number of passes of the data space required to perform the index operation.
<b>Action</b>	No action required.
<b>INOINI2461</b>	<b>Sort file efficiency: sorteфф %</b>
<b>Explanation</b>	This is the calculated efficiency of the sort file during the index process.
<b>Action</b>	No action required.
<b>INOINI2462</b>	<b>Work pool efficiency: workeфф %</b>
<b>Explanation</b>	This is the calculated efficiency of the work pool during the index process.
<b>Action</b>	No action required.
<b>INOINI2467</b>	<b>Recommended minimum temporary storage size = size KB</b>
<b>Explanation</b>	This is the recommended (minimum) temporary storage size that will be allocated for the process.
<b>Action</b>	No action required.
<b>INOINI2471</b>	<b>Temporary storage size = size KB</b>
<b>Explanation</b>	This is the size of the required temporary storage.
<b>Action</b>	No action required.

<b>INOINI2472</b>	<b>Temporary storage size (1 pass) = size MB</b>
<b>Explanation</b>	This is the temporary storage size required for 1 pass processing.
<b>Action</b>	No action required.
<b>INOINI2473</b>	<b>Temporary storage size (2 passes) = size MB</b>
<b>Explanation</b>	This is the temporary storage size required for 2 pass processing.
<b>Action</b>	No action required.
<b>INOINI2474</b>	<b>Sorting index</b>
<b>Explanation</b>	The index field is being sorted.
<b>Action</b>	No action required.
<b>INOINI2475</b>	<b>No values for index (desc)</b>
<b>Explanation</b>	No values are present for the index field.
<b>Action</b>	No action required.
<b>INOINI2476</b>	<b>Loading index</b>
<b>Explanation</b>	The index field specified is being loaded.
<b>Action</b>	No action required.
<b>INOINI2477</b>	<b>Verifying index (desc)</b>
<b>Explanation</b>	The index field specified is being verified.
<b>Action</b>	No action required.
<b>INOINI2478</b>	<b>Unique status for specified index is being set</b>
<b>Explanation</b>	The unique status for the specified index field is being set.
<b>Action</b>	No action required.
<b>INOINI2479</b>	<b>Unique status for specified index is being reset</b>
<b>Explanation</b>	The unique status for the specified index field is being reset.
<b>Action</b>	No action required.

---

<b>INOINI2480</b>	<b>Unique status removed for index</b>
<b>Explanation</b>	The unique status of an index field has been removed.
<b>Action</b>	No action required.
<b>INOINI2481</b>	<b>No index fields were found for the specified doctype</b>
<b>Explanation</b>	The index function could not be performed because no index fields were found in the specified doctype.
<b>Action</b>	Check that the correct doctype was specified for the index operation.
<b>INOINI2482</b>	<b>Index processing started on doctype doctype</b>
<b>Explanation</b>	The requested index operation has started.
<b>Action</b>	No action required.
<b>INOINW2800</b>	<b>Errors found for count indices</b>
<b>Explanation</b>	A number of indices were found to be in error during the index process.
<b>Action</b>	Correct the errors and attempt to perform the index process again.
<b>INOINW2801</b>	<b>Number of errors found in index: indexerr</b>
<b>Explanation</b>	This message shows the number of indices found to be in error during index processing.
<b>Action</b>	Correct the indices in error and perform the index operation again.
<b>INOINW2802</b>	<b>Unique conflict detected</b>
<b>Explanation</b>	Duplicate values were detected when trying to create a unique index.
<b>Action</b>	Remove any unique conflicts in the data.
<b>INOLDE3010</b>	<b>Invalid combination of keywords</b>
<b>Explanation</b>	The combination of keywords supplied is not allowed.
<b>Action</b>	Check the keyword combination and retry the operation.
<b>INOLDE3016</b>	<b>FIELDS may be specified only once</b>
<b>Explanation</b>	The parameter FIELDS may be specified only once.
<b>Action</b>	Continue with other parameter settings.

<b>INOLDE3051</b>	<b>Invalid output status returned by user exit</b>
<b>Explanation</b>	A user exit has returned an invalid output status to the load process.
<b>Action</b>	Ensure that the user exit always returns a valid output status.
<b>INOLDE3054</b>	<b>Invalid range of sequence numbers</b>
<b>Explanation</b>	The range of sequence numbers to be deleted is invalid.
<b>Action</b>	Please contact your software supplier.
<b>INOLDE3055</b>	<b>Value must be less than or equal to value</b>
<b>Explanation</b>	A value has exceeded the specified maximum.
<b>Action</b>	Decrease the value specified.
<b>INOLDE3056</b>	<b>Invalid record length</b>
<b>Explanation</b>	The input record length must be a multiple of four for binary data.
<b>Action</b>	Check the input file.
<b>INOLDE3057</b>	<b>Sequence number to be deleted is not present</b>
<b>Explanation</b>	The sequence number to be deleted is either not present or outside the specified doctype's limits.
<b>Action</b>	Ensure that the sequence numbers to be deleted were specified correctly.
<b>INOLDE3058</b>	<b>Dataset dataset, record record, offset offset</b>
<b>Explanation</b>	An error has occurred in the specified dataset at the position indicated.
<b>Action</b>	Correct the input and retry the operation.
<b>INOLDE3059</b>	<b>Index index not defined for doctype doctype</b>
<b>Explanation</b>	The specified index is defined in the load description file but is not present in the doctype to be updated.
<b>Action</b>	Ensure that the load description file contains the correct information and that the correct doctype is specified.

---

<b>INOLDE3060</b>	<b>Read-only database, function not permitted to run</b>
<b>Explanation</b>	The specified database is read-only and the requested function is not allowed for a read-only database.
<b>Action</b>	Ensure that the database being accessed is not read-only for this type of operation.
<b>INOLDF3018</b>	<b>The requested doctype is locked, load aborted</b>
<b>Explanation</b>	The doctype referenced is locked and the load is unable to proceed.
<b>Action</b>	Wait until the doctype is available. If the lock is due to a previous problem or corrupt doctype, a server restart may clear the lock and return the doctype to a usable state.
<b>INOLDF3251</b>	<b>Load aborted in user exit at record number: record</b>
<b>Explanation</b>	The load process has been aborted by a user exit while processing the specified record number.
<b>Action</b>	Check the user exit for the reason for aborting the load process.
<b>INOLDF3252</b>	<b>Record too big for data storage device</b>
<b>Explanation</b>	The record is too large for the data storage device used.
<b>Action</b>	Decrease the size of the input record, or use a data storage device with a larger block size.
<b>INOLDF3253</b>	<b>Incomplete load definition file</b>
<b>Explanation</b>	The input file containing the load definitions is incomplete.
<b>Action</b>	Check the load definition file and ensure that it contains the correct information.
<b>INOLDF3254</b>	<b>Internal buffer overflow</b>
<b>Explanation</b>	An unexpected overflow of an internal buffer has occurred.
<b>Action</b>	Please contact your software supplier.
<b>INOLDF3255</b>	<b>Sort I/O error</b>
<b>Explanation</b>	An I/O error has occurred on the sort data space.
<b>Action</b>	Check the sort data space for system errors.

<b>INOLDF3256</b>	<b>Selection not yet implemented</b>
<b>Explanation</b>	The selection of sequence numbers to be deleted is not yet implemented.
<b>Action</b>	No action possible.
<b>INOLDF3257</b>	<b>Unexpected error while connecting</b>
<b>Explanation</b>	An unexpected error has occurred while trying to connect to the server.
<b>Action</b>	Please contact your software supplier.
<b>INOLDF3260</b>	<b>Error in user store function</b>
<b>Explanation</b>	An error has occurred in a user-supplied store function.
<b>Action</b>	Check and correct any user-supplied store functions.
<b>INOLDF3261</b>	<b>No free sequence numbers</b>
<b>Explanation</b>	An internal shortage of sequence numbers has occurred.
<b>Action</b>	Please contact your software supplier.
<b>INOLDF3263</b>	<b>No free sequence numbers</b>
<b>Explanation</b>	There are no more free sequence numbers available.
<b>Action</b>	Please contact your software supplier.
<b>INOLDF3264</b>	<b>Cannot allocate user-defined sequence number</b>
<b>Explanation</b>	An error has occurred when trying to allocate a user-defined sequence number.
<b>Action</b>	Check that the user routine that allocates sequence numbers is correct.
<b>INOLDF3265</b>	<b>No index read slots</b>
<b>Explanation</b>	An internal error has occurred because there are no read slots available for the index.
<b>Action</b>	Please contact your software supplier.
<b>INOLDF3266</b>	<b>Error while generating index</b>
<b>Explanation</b>	An internal error has occurred while generating an index.
<b>Action</b>	Please contact your software supplier.

---

<b>INOLDF3267</b>	<b>Temp stream overflow</b>
<b>Explanation</b>	A stream overflow has occurred while processing the temporary data space.
<b>Action</b>	Please contact your software supplier.
<b>INOLDF3268</b>	<b>Doctype locking failed</b>
<b>Explanation</b>	It was not possible to lock a doctype for access.
<b>Action</b>	Ensure that nothing else is accessing the doctype to be locked.
<b>INOLDF3269</b>	<b>Unexpected error while removing utility entry</b>
<b>Explanation</b>	An unexpected internal error has occurred while removing a utility entry.
<b>Action</b>	Please contact your software supplier.
<b>INOLDF3270</b>	<b>Unexpected error while opening sort space</b>
<b>Explanation</b>	An unexpected internal error has occurred while opening the sort space.
<b>Action</b>	Ensure that there is enough sort space available.
<b>INOLDF3271</b>	<b>Load description does not match</b>
<b>Explanation</b>	The definitions in the load description file do not match those of the current doctype.
<b>Action</b>	Check that the specifications in the load description file are correct.
<b>INOLDI3002</b>	<b>Preparing documents for load</b>
<b>Explanation</b>	Preparing documents for load.
<b>Action</b>	No action required.
<b>INOLDI3019</b>	<b>Loading documents in collection</b>
<b>Explanation</b>	The collection is being modified.
<b>Action</b>	No action required.
<b>INOLDI3451</b>	<b>Termination forced by user exit</b>
<b>Explanation</b>	A user exit has forced the load process to terminate.
<b>Action</b>	If the termination was unexpected, check the user exit for the reason.

<b>INOLDI3452</b>	<b>Number of records read: records</b>
<b>Explanation</b>	This is the number of input records read during the load process.
<b>Action</b>	No action required.
<b>INOLDI3456</b>	<b>Number of documents added to doctype doctype: number</b>
<b>Explanation</b>	The load process has added the given number of documents to the specified doctype.
<b>Action</b>	No action required.
<b>INOLDI3457</b>	<b>Number of documents deleted from doctype doctype: number</b>
<b>Explanation</b>	The load process has deleted the given number of documents from the specified doctype.
<b>Action</b>	No action required.
<b>INOLDI3458</b>	<b>Number of documents unloaded from doctype doctype: number</b>
<b>Explanation</b>	The load process has unloaded the given number of documents from the specified doctype.
<b>Action</b>	No action required.
<b>INOLDI3459</b>	<b>The specified number of records have been loaded</b>
<b>Explanation</b>	The number of records to be loaded has been reached.
<b>Action</b>	No action required.
<b>INOLDI3460</b>	<b>Preparing existing indices for merge</b>
<b>Explanation</b>	Existing indices are being backed up before creating new ones.
<b>Action</b>	No action required.
<b>INOLDI3461</b>	<b>No index modification</b>
<b>Explanation</b>	No modifications have been made to any indices.
<b>Action</b>	No action required.
<b>INOLDI3464</b>	<b>Data space is being modified</b>
<b>Explanation</b>	The data space is being modified.
<b>Action</b>	No action required.

---

<b>INOLDI3465</b>	<b>Data space prepared for delete</b>
<b>Explanation</b>	The data space will be prepared for deleting records.
<b>Action</b>	No action required.
<b>INOLDI3467</b>	<b>Number of referential integrity violations: number</b>
<b>Explanation</b>	This message indicates the number of referential integrity violations encountered during the load process.
<b>Action</b>	No action required.
<b>INOLDI3468</b>	<b>Erase from referenced doctype is not supported</b>
<b>Explanation</b>	It is not possible to erase from the referenced doctype.
<b>Action</b>	No action possible.
<b>INOLDI3474</b>	<b>Sorting and loading indices</b>
<b>Explanation</b>	The indices are being sorted and loaded.
<b>Action</b>	No action required.
<b>INORBE4002</b>	<b>Function only permitted if restore database</b>
<b>Explanation</b>	A function was chosen that is not permitted in the current context.
<b>Action</b>	Use the function while restoring the database.
<b>INORBE4005</b>	<b>Backup not currently possible; parts of database are locked</b>
<b>Explanation</b>	It is not currently possible to start a backup because parts of the database are locked by other users or operations.
<b>Action</b>	Retry the backup when there are no longer any users or operations locking any parts of the database.
<b>INORBE4006</b>	<b>This function is not permitted on a system file while Tamino server is active</b>
<b>Explanation</b>	To preserve data consistency, the Tamino server should not be active while restoring the database.
<b>Action</b>	Shut down the Tamino server.

<b>INORBE4007</b>	<b>Restore database is not permitted while Tamino server is active</b>
<b>Explanation</b>	To preserve data consistency, the Tamino server should not be active while restoring the database.
<b>Action</b>	Shut down the Tamino server.
<b>INORBE4053</b>	<b>Terminator of backup copy not found</b>
<b>Explanation</b>	The terminator of the backup copy could not be found. The error can occur if the backup was modified outside of Tamino.
<b>Action</b>	Make sure that the backup copy was not modified outside of Tamino. If the problem persists , contact your software supplier.
<b>INORBE4056</b>	<b>Invalid database space size change</b>
<b>Explanation</b>	The value for changing the database space size is invalid.
<b>Action</b>	Specify a valid value.
<b>INORBE4057</b>	<b>No space for database block allocation at database space (number KB at block)</b>
<b>Explanation</b>	The restore requires more space for the database, but it failed. There are two possible reasons: either the database cannot be extended because there is no more space on the disk, or there are internal structure problems.
<b>Action</b>	Make sure that there is enough space for the database to be enlarged.
<b>INORBE4060</b>	<b>Input file is empty</b>
<b>Explanation</b>	The input file specified for the operation is empty.
<b>Action</b>	Check that the correct input file has been specified.
<b>INORBE4061</b>	<b>Invalid sequence of backup copy files</b>
<b>Explanation</b>	The sequence of the specified backup copy files is incorrect.
<b>Action</b>	Check that the correct backup copy files have been specified.
<b>INORBE4064</b>	<b>Synchronization with database server lost</b>
<b>Explanation</b>	The synchronization with the database server has been lost.
<b>Action</b>	Retry the backup operation. If the problem persists, contact your software supplier.

<b>INORBE4065</b>	<b>Invalid block type type</b>
<b>Explanation</b>	I/O from an unexpected database space is going to be logged so command logging has been deactivated.
<b>Action</b>	This is an unexpected error. Please contact your software supplier.
<b>INORBE4067</b>	<b>Unable to open journal space</b>
<b>Explanation</b>	An error has occurred when trying to open the journal space.
<b>Action</b>	Check that the journal space exists and is correctly defined.
<b>INORBE4068</b>	<b>Reference to missing doctype detected</b>
<b>Explanation</b>	A doctype that does not exist has been referenced.
<b>Action</b>	This is an internal error. Please contact your software supplier.
<b>INORBF4013</b>	<b>Server is in startup phase, backup not possible.</b>
<b>Explanation</b>	The server is still in the startup phase and therefore a backup is not possible. This is probably caused by another (offline) backup running, or the server being started.
<b>Action</b>	Wait until the other backup has finished, or the server has started, and run the backup again.
<b>INORBF4251</b>	<b>Invalid block allocation detected (blocks are shared between different doctypes)</b>
<b>Explanation</b>	The database server is in an inconsistent state.
<b>Action</b>	This is an internal error. Please contact your software supplier.
<b>INORBF4253</b>	<b>Error error number during backup: error message</b>
<b>Explanation</b>	A fatal error occurred during backup.
<b>Action</b>	Try to solve the problem based on the text of the error message. Otherwise, contact your software supplier.
<b>INORBF4255</b>	<b>An error occurred when updating the internal configuration store</b>
<b>Explanation</b>	The operation has been terminated because an error occurred while trying to update the internal configuration store.
<b>Action</b>	Please contact your software supplier and provide the message text of all messages displayed.

<b>INORBF4257</b>	<b>Corrupt structure on backup copy</b>
<b>Explanation</b>	The backup copy does not contain the correct structure.
<b>Action</b>	Check your input file assignments, and ensure that the correct backup copy is being used.
<b>INORBF4259</b>	<b>Error occurred in I/O block blockno</b>
<b>Explanation</b>	An I/O error has occurred on the specified block.
<b>Action</b>	The backup copy is corrupt; back up the database again to create another backup copy.
<b>INORBF4260</b>	<b>Online backup already active</b>
<b>Explanation</b>	Another backup function is active. Only one online backup is possible at one time.
<b>Action</b>	No action required.
<b>INORBF4263</b>	<b>Utility not permitted to run</b>
<b>Explanation</b>	This utility is currently not permitted to run.
<b>Action</b>	Wait until the database is available.
<b>INORBF4265</b>	<b>Internal error found in backup copy</b>
<b>Explanation</b>	An internal structure error has occurred in the backup copy. The backup copy may be corrupt. A possible cause of the error is that the backup copy was modified outside of Tamino.
<b>Action</b>	Check that the backup copy was not modified outside of Tamino. If the problem persists, please contact your software supplier.
<b>INORBF4266</b>	<b>Block size of output file too small</b>
<b>Explanation</b>	The block size of the output file is too small.
<b>Action</b>	Use an output device with a larger block size.
<b>INORBF4267</b>	<b>Invalid record detected, block blockno</b>
<b>Explanation</b>	The backup copy file has a structure error with printed information. This backup copy file cannot be used as input for a restore.
<b>Action</b>	Run the backup function again.

---

<b>INORBF4268</b>	<b>Internal configuration delete by Tamino utility failed</b>
<b>Explanation</b>	The final stage of saveset processing failed; the internal configuration is incorrect.
<b>Action</b>	Retry the operation.
<b>INORBF4269</b>	<b>Internal configuration update by Tamino utility failed because key could not be moved</b>
<b>Explanation</b>	A utility attempted to create an internal configuration entry, but this call failed for the stated reason. The utility will now terminate, and the administration agent will carry out any necessary recovery tasks.
<b>Action</b>	No action required. Please contact your system administrator for further information.
<b>INORBF4270</b>	<b>Internal configuration get by Tamino utility failed because value could not be read</b>
<b>Explanation</b>	A utility attempted to read the values for an internal configuration entry, but this call failed for the stated reason. The utility will now terminate, and the administration agent will carry out any necessary recovery tasks.
<b>Action</b>	No action required. Please contact your system administrator for further information.
<b>INORBF4271</b>	<b>Internal configuration set by Tamino utility failed because value could not be set</b>
<b>Explanation</b>	A utility attempted to set the value for an internal configuration entry, but this call failed for the stated reason. The utility will now terminate, and the administration agent will carry out any necessary recovery tasks.
<b>Action</b>	No action required. Please contact your system administrator for further information.
<b>INORBF4272</b>	<b>Internal configuration get by Tamino utility failed because values could not be enumerated</b>
<b>Explanation</b>	A utility attempted to count the number of values for an internal configuration entry, but this call failed for the stated reason. The utility will now terminate, and the administration agent will carry out any necessary recovery tasks.
<b>Action</b>	No action required. Please contact your system administrator for further information.
<b>INORBF4273</b>	<b>Internal configuration create by Tamino utility failed</b>
<b>Explanation</b>	A utility attempted to create a new internal configuration, but this call failed. The utility will now terminate, and the administration agent will carry out any necessary recovery tasks.
<b>Action</b>	No action required. Please contact your system administrator for further information.

<b>INORBF4276</b>	<b>This operation is not allowed while the Tamino server is active</b>
<b>Explanation</b>	The operation cannot be executed when the database has been started.
<b>Action</b>	Stop the database and retry the operation.
<b>INORBI4063</b>	<b>Access to the Tamino server's shared memory is not possible</b>
<b>Explanation</b>	It is not possible to access shared memory of the Tamino server. Synchronization with the server is lost. A possible cause is that the Tamino server has been shut down in the meantime.
<b>Action</b>	Retry the backup operation. If the problem persists, please contact your software supplier.
<b>INORBI4452</b>	<b>Waiting for autorestart</b>
<b>Explanation</b>	The utility action cannot be performed until the database has completed an autorestart.
<b>Action</b>	No action required.
<b>INORBI4453</b>	<b>Initialization phase</b>
<b>Explanation</b>	This is an informational message indicating that a utility is initializing.
<b>Action</b>	No action required.
<b>INORBI4454</b>	<b>Waiting for transactions to commit</b>
<b>Explanation</b>	The requested operation is waiting for all transactions to commit.
<b>Action</b>	No action required.
<b>INORBI4455</b>	<b>Backup copy successfully checked</b>
<b>Explanation</b>	The backup copy has been successfully checked.
<b>Action</b>	No action required.
<b>INORBI4456</b>	<b>No doctype in backup copy</b>
<b>Explanation</b>	The backup copy used for this operation does not contain any doctypes.
<b>Action</b>	No action required.

---

<b>INORBI4457</b>	<b>Restore of database completed successfully</b>
<b>Explanation</b>	The database has been successfully restored.
<b>Action</b>	No action required.
<b>INORBI4459</b>	<b>Within allocation</b>
<b>Explanation</b>	This informational message occurs when a utility is allocating space.
<b>Action</b>	No action required.
<b>INORBI4464</b>	<b>Formatting of database_space completed</b>
<b>Explanation</b>	This informational message indicates the completion time of the formatting operation.
<b>Action</b>	No action required.
<b>INORBI4465</b>	<b>Formatting of database_space started</b>
<b>Explanation</b>	This informational message indicates that the formatting operation has started.
<b>Action</b>	No action required.
<b>INORBI4466</b>	<b>Database identification set to 'database_name'</b>
<b>Explanation</b>	The database identification has been set to the specified name.
<b>Action</b>	No action required.
<b>INORBI4468</b>	<b>Backup of database_space completed</b>
<b>Explanation</b>	The indicated database space has been backed up.
<b>Action</b>	No action required
<b>INORBI4469</b>	<b>Terminator block: type</b>
<b>Explanation</b>	This message shows the value of the terminator block.
<b>Action</b>	No action required.
<b>INORBI4475</b>	<b>New block allocations for doctype doctype</b>
<b>Explanation</b>	New blocks have been allocated for the specified doctype.
<b>Action</b>	No action required.

<b>INORBI4478</b>	<b>Doctype doctype contained in saveset</b>
<b>Explanation</b>	The doctype specified is contained in the backup saveset.
<b>Action</b>	No action required.
<b>INORBI4631</b>	<b>Backup of database completed successfully</b>
<b>Explanation</b>	A database copy has been backed up successfully.
<b>Action</b>	No action required.
<b>INORBQ4000</b>	<b>Error accessing database space extent no at location restore location</b>
<b>Explanation</b>	The database space was not found at the specified location. There are many possible causes for this. The container may be corrupt or missing, the defined 'Location' may be missing or corrupt or you may not have sufficient access privileges for the specified location. If you have replaced a location and/or container that was previously missing, this error appears because the database server did not expect the container to re-appear after it detected it was missing.
<b>Action</b>	Verify that the container exists in the correct location. If you have replaced a previously missing container, please move it out of the way to allow the database server to recreate the container and allow the restore process to continue. If the problem persists, please contact your software supplier.
<b>INORBQ4001</b>	<b>Confirm location for recreation of database space extent no</b>
<b>Explanation</b>	Confirm the location for recreation of the database space.
<b>Action</b>	Enter the location name.
<b>INORBR4681</b>	<b>Backing up database_space</b>
<b>Explanation</b>	The specified server space is being backed up.
<b>Action</b>	No action required.
<b>INORBS4009</b>	<b>Restoring database with reorganization ...</b>
<b>Explanation</b>	The database is being restored and a data reorganization will be done..
<b>Action</b>	No action required.

---

<b>INORBS4458</b>	<b>Restoring database ...</b>
<b>Explanation</b>	The database is being restored.
<b>Action</b>	No action required.
<b>INORBV4012</b>	<b>Doctype loaded = loaded_doctypes; actual number of doctypes = actual_doctypes</b>
<b>Explanation</b>	The number of doctypes loaded differs from the number of doctypes in the backup copy.
<b>Action</b>	Please contact your software supplier with an exact description of the functions that caused the error.
<b>INORBW4010</b>	<b>External backup/restore request failed, detailed info in file filename</b>
<b>Explanation</b>	The specific external backup or restore action failed due to an internal reason. Please view the output file indicated by the error message for the problem.
<b>Action</b>	Analyze the problem in the error file.
<b>INORBW4015</b>	<b>The space size will be increased by size MB</b>
<b>Explanation</b>	The container size specified during create is not sufficient. Tamino is automatically extending the container to accommodate the data.
<b>Action</b>	No action required.
<b>INORBW4803</b>	<b>Database identification could not be changed</b>
<b>Explanation</b>	The database identification could not be changed.
<b>Action</b>	Ensure that the database identification of the new database is correct.
<b>INORBW4805</b>	<b>Waiting for database restart</b>
<b>Explanation</b>	The operation is waiting for the restart of the database (due to its abnormal termination).
<b>Action</b>	Start the database.
<b>INORBW4806</b>	<b>Block block number ignored, run verify and repair function for doctype doctypes</b>
<b>Explanation</b>	During backup a corrupt index block was found which will not be backed up to the backup copy.
<b>Action</b>	Recreate the index of specified doctype and rerun the backup function.

<b>INOSAE7351</b>	<b>Duplicate attribute not allowed in element context</b>
<b>Explanation</b>	The result element will contain multiple attributes of the same name. This is not allowed in XML.
<b>Action</b>	Please verify your query for attribute construction.
<b>INOSAE7352</b>	<b>No serialization for attributes without element context</b>
<b>Explanation</b>	A serialization of attributes without element context was requested but is undefined.
<b>Action</b>	Please verify that the attribute construction belong to an element context.
<b>INOSAE7353</b>	<b>ino:document serialization supports only one document in serialization</b>
<b>Explanation</b>	The ino:document serialization supports only the serialization of a single document.
<b>Action</b>	The query returns more than one document. Correct the query and rerun.
<b>INOSAE7354</b>	<b>ino:serialization supports only the serialization of document nodes</b>
<b>Explanation</b>	The ino:document serialization supports only the serialization of document nodes.
<b>Action</b>	Verify that the query returns only nodes of type document.
<b>INOSAE7356</b>	<b>ino:document serialization has no Query Result</b>
<b>Explanation</b>	The query returned no matching document.
<b>Action</b>	Correct the query so that it delivers one single document node.
<b>INOSAI7355</b>	<b>Internal error</b>
<b>Explanation</b>	During the serialization an internal error occurred.
<b>Action</b>	Please contact your software supplier.
<b>INOSXE6704</b>	<b>Invalid character 'character' in name for compiler settings</b>
<b>Explanation</b>	Names for compiler settings must start with a letter and may be followed by letters or digits.
<b>Action</b>	Use a name that obeys this rule.
<b>INOSXE6705</b>	<b>Settings for default parameter must not be changed</b>
<b>Explanation</b>	The name 'default' is reserved for the compiler settings defined by the Tamino installation.
<b>Action</b>	Use a name other than 'default' to save these compiler settings.

---

<b>INOSXE6706</b>	<b>No configuration parameters found for compiler 'compiler'</b>
<b>Explanation</b>	The current compiler for Direct X-Tension projects is currently set to the compiler indicated; however, one or all of its configuration parameter files have been deleted.
<b>Action</b>	Use the default compiler as your current compiler; check your Tamino installation.
<b>INOSXE6707</b>	<b>X-Tension: COM initialization failed</b>
<b>Explanation</b>	During X-Tension initialization the initialization of the COM library failed. No COM-based extension functions are available during this server session.
<b>Action</b>	If COM-based server extension functions are required, fix the COM problem and start the Tamino server again.
<b>INOSXE6709</b>	<b>Invalid usage entry: 'value'</b>
<b>Explanation</b>	The Usage entry found in file 'Install.xml' could not be recognized.
<b>Action</b>	Check the documentation for valid values.
<b>INOSXE6710</b>	<b>Function 'function' not usable as 'usage'</b>
<b>Explanation</b>	This function cannot be used as the function type indicated. The function's parameter count or parameter datatypes do not correspond to the specified function type.
<b>Action</b>	Please check the 'Usage' entry in file 'Install.xml' as well as the parameter specification of the current function. See the documentation for the parameters required for the given Usage.  It is strongly recommended to use the X-Tension development tools to define new X-Tension functions.
<b>INOSXE6711</b>	<b>Value missing for Init Function 'func'</b>
<b>Explanation</b>	The X-Tension function indicated has been declared as Init Function. However, values are missing for one or more of its parameters.
<b>Action</b>	Use the X-Tension tools to create the X-Tension function and be careful editing the file Install.xml.
<b>INOSXE6712</b>	<b>The server extension crashed or threw an unknown exception</b>
<b>Explanation</b>	Either the server extension has crashed or it threw an exception that could not be caught by the Tamino Server.
<b>Action</b>	Please contact the vendor of the server extension.

<b>INOSXE6713</b>	<b>Extension tried to open message box. Message: 'message'.</b>
<b>Explanation</b>	It is not allowed to display message boxes in a server extension. This terminates the current server extension function.
<b>Action</b>	Please check the server extension code carefully. Maybe the C/C++ runtime system tried to open an assertion box because of programming errors in the server extension.
<b>INOSXE6714</b>	<b>Value is not of the selected data type 'type'</b>
<b>Explanation</b>	The value entered cannot be converted to the data type selected in the 'Add Param' box.
<b>Action</b>	Please check the value entered and the data type selected in the 'Add Param' box. See the documentation of Tamino X-Tension for more details on allowed values.
<b>INOSXE6715</b>	<b>Extension function 'func': Value of parameter 'param' is not of selected data type type</b>
<b>Explanation</b>	The value entered cannot be converted to the data type specified for this parameter.
<b>Action</b>	Please check the value entered and the data type specified for this parameter. See the documentation of Tamino X-Tension for more details on allowed values.  Use the Tamino X-Tension tools to specify parameter values!
<b>INOSXE6716</b>	<b>Unexpected error during callback function 'function'</b>
<b>Explanation</b>	An unexpected error occurred during a call of a callback function. Probably it has been called with one or more incorrect parameters.
<b>Action</b>	Check the documentation and your server extension code for the correct use of this callback function.
<b>INOSXE6717</b>	<b>Server extension function not found</b>
<b>Explanation</b>	The desired function name was not found in the SXS repository. Maybe the function name is incorrect, or the function is not installed or was deinstalled.
<b>Action</b>	Check and correct the function name or server extension installation.
<b>INOSXE6725</b>	<b>Callback not allowed in init function</b>
<b>Explanation</b>	An Sxs SetProperty callback is not allowed from a server extension init function.
<b>Action</b>	Remove the Sxs SetProperty callback from your server extension init function and retry the operation.

---

<b>INOSXE7000</b>	<b>Java server extension must have a package name</b>
<b>Explanation</b>	The package name for a Java server extension must not be empty.
<b>Action</b>	Define a package name, e.g. "package com.softwareag.mysxs".
<b>INOSXE7001</b>	<b>File name 'file.sxp' may not be changed</b>
<b>Explanation</b>	Only the directory may be selected; the file name must remain unchanged.
<b>Action</b>	Select a directory.
<b>INOSXE7006</b>	<b>XML callback failed. Transaction was rolled back.</b>
<b>Explanation</b>	No more information.
<b>Action</b>	Try with a modified XML request.
<b>INOSXE7009</b>	<b>Tamino X-Tension not available</b>
<b>Explanation</b>	It is not possible to call a Tamino server extension because either X-Tension is not licensed or the X-Tension feature is not available on this platform.
<b>Action</b>	If possible, buy a license for Tamino X-Tension.
<b>INOSXE7010</b>	<b>Project must be rebuilt before packing. Reason: 'reason'.</b>
<b>Explanation</b>	The project must be rebuilt. See 'reason' for more information.
<b>Action</b>	Call Build / Build <project name> in the Developer Studio before packing.
<b>INOSXE7014</b>	<b>Main class file cannot be removed</b>
<b>Explanation</b>	In the Packaging Dialogue of the X-Tension Builder, the class file is about to be removed that contains the main class of the current server extension.
<b>Action</b>	Do not remove this class file from the list or select a jar file containing this class.
<b>INOSXE7015</b>	<b>Callback not allowed in event function</b>
<b>Explanation</b>	From Tamino server event functions, XML and ODBC callback are not allowed.
<b>Action</b>	Remove the callback call from your server extension code.
<b>INOSXE7016</b>	<b>Illegal database command in callback</b>
<b>Explanation</b>	A database command that is not allowed in callbacks was called in a callback.
<b>Action</b>	Remove the database command from the callback and try again.

<b>INOSXE7017</b>	<b>Tamino server error when calling callback</b>
<b>Explanation</b>	An error occurred in the Tamino server when processing the callback, perhaps an XML or query syntax error.
<b>Action</b>	Method SXJBase.SXSGetInoMsgNo ( ) gives the error code of the Tamino server.
<b>INOSXE7018</b>	<b>Not enough memory for callback</b>
<b>Explanation</b>	The Tamino server could not allocate enough memory to process the callback.
<b>Action</b>	Try to repeat your query when the Tamino server is less loaded.
<b>INOSXE7019</b>	<b>SQL error when calling ODBC callback</b>
<b>Explanation</b>	An SQL error occurred while processing an ODBC callback, perhaps due to an SQL syntax error.
<b>Action</b>	Method SXJBase.SXSGetSQLMsgNo ( ) gives the SQL error code.
<b>INOSXE7020</b>	<b>Illegal handle type for ODBC callback</b>
<b>Explanation</b>	The ODBC callback methods SxsSQLAllocHandle and SxsSQLFreeHandle are only allowed for statement handles of type SQL_HANDLE_STMT.
<b>Action</b>	We recommend that you use the constant SXJBase.SQL_HANDLE_STMT as the parameter handle type.
<b>INOSXE7021</b>	<b>Commit and rollback are not allowed in callbacks</b>
<b>Explanation</b>	You must not use the database commands "commit" or "rollback" in your server extensions.
<b>Action</b>	Remove these commands from the server extension and try again.
<b>INOSXE7022</b>	<b>Result buffer for callback not initialized</b>
<b>Explanation</b>	Result buffers for callbacks must not be null, but should be initialized with an empty string.
<b>Action</b>	Ensure that all result buffers are initialized.
<b>INOSXE7023</b>	<b>Function 'name' failed, because XML callback failed with error 'no'</b>
<b>Explanation</b>	An XML callback failed while trying to perform a write operation. To avoid inconsistencies, the extension function must return with an error.
<b>Action</b>	Check the error caused by the XML callback and fix the problem that caused it to fail.

---

<b>INOSXE7024</b>	<b>COM error when calling callback</b>
<b>Explanation</b>	A COM error occurred during a callback.
<b>Action</b>	Consult your COM documentation.
<b>INOSXE7025</b>	<b>Another server extension deinstallation is running</b>
<b>Explanation</b>	Only one server extension can be deinstalled at any given time.
<b>Action</b>	Wait until the other deinstallation procedure has finished.
<b>INOSXE7026</b>	<b>Deinstallation timed out. The server extension is in use.</b>
<b>Explanation</b>	A server extension cannot be deinstalled as long as an instance of it is in use. The deinstallation procedure has timed out.
<b>Action</b>	Try it later. If there is a very long running instance of the server extension, try to stop it.
<b>INOSXE7027</b>	<b>The function cannot be executed. The server extension is being deinstalled.</b>
<b>Explanation</b>	This function belongs to a server extension that is just being deinstalled.
<b>Action</b>	The function cannot not be called again. If you need to, contact the database administrator.
<b>INOSXE7032</b>	<b>Cannot create directory 'dir'</b>
<b>Explanation</b>	This directory cannot be created. Maybe the disk drive is unavailable or write protected.
<b>Action</b>	Check the given path and your disk drive.
<b>INOSXE7034</b>	<b>Server extension 'source' threw exception 'errnr', 'errtext'</b>
<b>Explanation</b>	The server extension threw an exception. The number and message of the exception are delivered.
<b>Action</b>	See the documentation of the server extension in question for more information.
<b>INOSXE7040</b>	<b>Extension function name too long: 'name'</b>
<b>Explanation</b>	The complete extension function name, consisting of the extension's name plus the function name plus a dot, must not exceed the length of 80 characters.
<b>Action</b>	Select a shorter name.

<b>INOSXE7041</b>	<b>Wrong character in field: 'char'</b>
<b>Explanation</b>	Some special characters (ampersand, "less than", "greater than") are not allowed in comment fields for a server extension. This affects the "Short description" fields and the "Author" field.
<b>Action</b>	Avoid these characters.
<b>INOSXE7045</b>	<b>X-Tension Trace failed. Transaction was rolled back.</b>
<b>Explanation</b>	An internal server error occurred while X-Tension Trace information was written to the Tamino server.
<b>Action</b>	Deactivate X-Tension Trace
<b>INOSXE7046</b>	<b>XML Callback failed in user session. Transaction must be rolled back.</b>
<b>Explanation</b>	A writing XML call from a server extension failed. The current transaction should be rolled back for consistency reasons.
<b>Action</b>	Perform a rollback request.
<b>INOSXE7047</b>	<b>X-Tension Trace failed in user session. Transaction must be rolled back.</b>
<b>Explanation</b>	An internal server error occurred. The current transaction should be rolled back for consistency reasons.
<b>Action</b>	Deactivate X-Tension Trace
<b>INOSXE7048</b>	<b>Error starting help browser. Reason: 'reason'.</b>
<b>Explanation</b>	The currently configured help browser could not be started. See "reason" for more details.
<b>Action</b>	Use the function "Help/Configure Help Browser" to change your current help browser.
<b>INOSXE7049</b>	<b>'execfile' execution failed: rc = rc</b>
<b>Explanation</b>	The external program 'Program name' was successfully started but it returned with error.
<b>Action</b>	See the context of this error message for more information.
<b>INOSXE7051</b>	<b>COM error 'errno' occurred: 'errtext'</b>
<b>Explanation</b>	A COM error occurred. The COM error number of type HRESULT is delivered.
<b>Action</b>	Consult the COM documentation for more information.

---

<b>INOSXE7052</b>	<b>COM error 'errno' calling 'dllname': 'errtext'</b>
<b>Explanation</b>	A COM error occurred. The COM error code of type HRESULT and the name of the Tamino server extension DLL which was called is delivered.
<b>Action</b>	Consult the COM documentation for more information.
<b>INOSXE7053</b>	<b>Error 'errno' calling data map: 'errtext'</b>
<b>Explanation</b>	An error occurred when the Tamino server extension part of the data map was accessed. The error number and message received from the Tamino data map is delivered.
<b>Action</b>	Look up the delivered error number and see the action described there.
<b>INOSXE7054</b>	<b>X-Tension system function cannot be deleted</b>
<b>Explanation</b>	An attempt was made to delete a function which is needed for the X-Tension administration.
<b>Action</b>	No action required.
<b>INOSXE7055</b>	<b>The server extension threw exception 'errtext'.</b>
<b>Explanation</b>	The server extension threw an exception. The message and occasionally the number of the exception are delivered.
<b>Action</b>	See the documentation of the server extension in question for more information.
<b>INOSXE7056</b>	<b>X-Tension caller: Not enough memory</b>
<b>Explanation</b>	There was not enough memory for execution of the server extension function.
<b>Action</b>	Close some applications and try again.
<b>INOSXE7057</b>	<b>X-Tension caller: internal error</b>
<b>Explanation</b>	Internal errors occurred within the X-Tension administration structure.
<b>Action</b>	Please contact your software supplier.
<b>INOSXE7058</b>	<b>X-Tension caller: got no spinlock. Reason: 'retval'.</b>
<b>Explanation</b>	An error occurred within the thread synchronization. A server extension could not be locked. The return value received from the thread administration is delivered.
<b>Action</b>	Please contact your software supplier.

<b>INOSXE7059</b>	<b>X-Tension caller: could not get data map information</b>
<b>Explanation</b>	The X-Tension caller was unable to get any data map information.
<b>Action</b>	Please contact your software supplier.
<b>INOSXE7060</b>	<b>Mapping function 'n': Wrong number of parameters implemented. Expected: 'm'.</b>
<b>Explanation</b>	A Tamino server extension mapping function does not support the number of parameters needed for this function type.
<b>Action</b>	Install a correctly implemented server extension.
<b>INOSXE7061</b>	<b>Extension function 'n': Wrong type of parameter 'm' implemented</b>
<b>Explanation</b>	A mapping function does not support the correct parameter types.
<b>Action</b>	Compare the parameter type for this type of extension function as described in the manual with the parameter type supported by the extension function (found using Tamino Manager). Install a correctly implemented extension function.
<b>INOSXE7062</b>	<b>X-Tension caller: initialization failed</b>
<b>Explanation</b>	The X-Tension caller was not initialized when the Tamino server was started. It is impossible to call any extension function, maybe because server extension libraries could not be loaded.
<b>Action</b>	Check your Tamino installation.
<b>INOSXE7063</b>	<b>X-Tension caller: 'No' server event calls failed</b>
<b>Explanation</b>	A server event call to some server extensions failed. The number of failures is delivered.
<b>Action</b>	Please contact your software supplier.
<b>INOSXE7064</b>	<b>Unexpected end of file encountered before end of source</b>
<b>Explanation</b>	During the parsing of the X-Tension installation file, IDL file or one of the server extension source files, an unexpected end of file was found.
<b>Action</b>	Check the syntax of the file(s).
<b>INOSXE7065</b>	<b>Syntax error. Token: 'Token'.</b>
<b>Explanation</b>	An unspecified error was encountered during parsing near or at the place specified by 'Token'.
<b>Action</b>	Check the syntax of the X-Tension installation file.

---

<b>INOSXE7066</b>	<b>Unbalanced tag / end tag: 'tag1' / ' tag2'</b>
<b>Explanation</b>	In the X-Tension installation file, the names of begin-tag and end-tag are different.
<b>Action</b>	Check the syntax of the X-Tension installation file.
<b>INOSXE7067</b>	<b>Tag 'tagname' not found</b>
<b>Explanation</b>	The specified mandatory tag was not found in the X-Tension installation file.
<b>Action</b>	Check the syntax of the X-Tension installation file.
<b>INOSXE7068</b>	<b>Tag 'tagname' is not a value</b>
<b>Explanation</b>	A simple value was expected for the specified tag, but a node has been found.
<b>Action</b>	Check the syntax of the X-Tension installation file.
<b>INOSXE7069</b>	<b>Tag 'tagname' is not a node</b>
<b>Explanation</b>	A node was expected for the specified tag, but a simple value has been found.
<b>Action</b>	Check the syntax of the X-Tension installation file.
<b>INOSXE7070</b>	<b>Duplicate name: 'name'</b>
<b>Explanation</b>	The specified tag name was found twice in the X-Tension installation file.
<b>Action</b>	Check the syntax of the X-Tension installation file.
<b>INOSXE7071</b>	<b>Error 'character' expected</b>
<b>Explanation</b>	The specified character was expected but not found in the X-Tension installation file or one of the server extension source files.
<b>Action</b>	Check the syntax of the X-Tension installation file and the server extension source files.
<b>INOSXE7072</b>	<b>Error 'character' expected, eof found</b>
<b>Explanation</b>	The specified character was expected, but an end of file was found in the X-Tension installation file or one of the server extension source files.
<b>Action</b>	Check the syntax of the X-Tension installation file and the server extension source files.

<b>INOSXE7073</b>	<b>IDL file 'segment name' is corrupt</b>
<b>Explanation</b>	A syntax error was found in the IDL file for the definition of the server extension interface at or near the specified keyword.
<b>Action</b>	Check the syntax of the IDL file.
<b>INOSXE7074</b>	<b>'SXF' not defined in interface</b>
<b>Explanation</b>	The specified function has been defined in the X-Tension installation file but it had not been entered into the IDL file for the server extension interface.
<b>Action</b>	Remove the function definition from the X-Tension installation file and use the X-Tension Developer Studio add-in to define a new one.
<b>INOSXE7075</b>	<b>Return type must be HRESULT, not 'type'</b>
<b>Explanation</b>	A COM server extension must always return HRESULT.
<b>Action</b>	Use the [retval] attribute for the last parameter as a return value of the server extension function.
<b>INOSXE7076</b>	<b>Method 'method': Different parameter names: 'param1' / 'param2'</b>
<b>Explanation</b>	The parameter name of the indicated server extension function in the X-Tension installation file is different from that defined in the IDL file.
<b>Action</b>	Check the implementation of the server extension function; use the X-Tension Developer Studio add-in to define a server extension function.
<b>INOSXE7077</b>	<b>Too many parameters: 'SXF'</b>
<b>Explanation</b>	The specified server extension function has been implemented with more parameters than are defined in the X-Tension installation file.
<b>Action</b>	Check the implementation of the server extension function; use the X-Tension Developer Studio add-in to define a server extension function.
<b>INOSXE7078</b>	<b>Cannot map parameter type</b>
<b>Explanation</b>	A parameter type is used in the COM interface that cannot be used for server extension function parameters.
<b>Action</b>	Use the X-Tension Developer Studio add-in to define a server extension function.

---

<b>INOSXE7079</b>	<b>Server extension implementation file could not be found</b>
<b>Explanation</b>	The X-Tension Developer Studio add-in could not find the file with the implementation of the class for the server extension.
<b>Action</b>	Use the X-Tension development tool to create a server extension.
<b>INOSXE7080</b>	<b>Unknown XML data type: 'type'</b>
<b>Explanation</b>	The specification of the XML data type for a server extension function parameter is wrong. See the documentation for allowed data types.
<b>Action</b>	Use the X-Tension Developer Studio add-in to define a new server extension function.
<b>INOSXE7081</b>	<b>Unknown programming language data type: 'type'</b>
<b>Explanation</b>	The function implementation uses a data type for one of its parameters that is not supported when using this function as a server extension function. See the documentation for the allowed data types in this programming language
<b>Action</b>	Use the X-Tension development tools to define a server extension function.
<b>INOSXE7082</b>	<b>Unknown execution mode: 'mode'</b>
<b>Explanation</b>	The specified server extension execution mode is wrong. Allowed modes are: COM-INPROC, COM-LOCAL.
<b>Action</b>	Use the Tamino Manager to change this mode.
<b>INOSXE7083</b>	<b>Wrong numeric value: 'val'</b>
<b>Explanation</b>	The value was expected to be numeric but the given value is not numeric.
<b>Action</b>	Enter a numeric value here.
<b>INOSXE7084</b>	<b>Wrong parameter position</b>
<b>Explanation</b>	The parameter position in the X-Tension installation file must start at 1.
<b>Action</b>	Check the parameter position values. Use X-Tension Developer Studio add-in to define a new server extension function.
<b>INOSXE7085</b>	<b>Cannot open file 'name'</b>
<b>Explanation</b>	The specified file could not be opened.
<b>Action</b>	Check if this file really exists, or if it is locked by another process.

<b>INOSXE7086</b>	<b>Wrong version format: 'string'</b>
<b>Explanation</b>	The server extension version is supposed to be of the form major.minor
<b>Action</b>	Check the server extension version.
<b>INOSXE7087</b>	<b>Event function 'function' not found</b>
<b>Explanation</b>	An event function has been specified in the SXS-EVENT-FUNCTION tag of the X-Tension installation file, but it could not be found in an SXS-FUNCTION tag.
<b>Action</b>	Delete the event function specification tag and use the X-Tension Developer Studio add-in to specify a new one.
<b>INOSXE7088</b>	<b>Wrong document type for X-Tension administration: 'type'</b>
<b>Explanation</b>	The document type (second level tag) of the X-Tension administration file is wrong. Allowed types are: SXS-INSTALL, SXS-DELETE, SXS-SHOW, SXS-RETURN.
<b>Action</b>	For a server extension installation, only SXS-INSTALL is valid.
<b>INOSXE7089</b>	<b>Missing XML attribute 'attribute' for SXS-SHOW</b>
<b>Explanation</b>	No attribute is given for the X-Tension administration type tag SXS-SHOW.
<b>Action</b>	One of the attributes list, object, function, permission, document must be given for the SXS-SHOW tag.
<b>INOSXE7090</b>	<b>Wrong XML attribute: 'attribute'</b>
<b>Explanation</b>	A wrong attribute is given for the X-Tension administration type tag SXS-SHOW.
<b>Action</b>	One of the attributes list, object, function, permission, document must be given for the SXS-SHOW tag.
<b>INOSXE7091</b>	<b>Wrong parameter attribute: 'attribute'</b>
<b>Explanation</b>	A wrong parameter attribute has been specified in the X-Tension installation file. Allowed attributes are: input, output, inout, retval.
<b>Action</b>	Use the X-Tension Developer Studio add-in to define a new server extension function.
<b>INOSXE7092</b>	<b>No current project</b>
<b>Explanation</b>	There is no project open in Developer Studio. The X-Tension add-in will not work.
<b>Action</b>	Open a server extension project first.

---

<b>INOSXE7093</b>	<b>This is not a C/C++ project</b>
<b>Explanation</b>	The X-Tension add-in will not work for Java or Visual Basic projects.
<b>Action</b>	Open a C/C++ project.
<b>INOSXE7094</b>	<b>This is not an X-Tension project</b>
<b>Explanation</b>	The current project has not been created by an X-Tension development tool.
<b>Action</b>	Use the X-Tension development tool to create a server extension.
<b>INOSXE7095</b>	<b>File 'filename' is read-only</b>
<b>Explanation</b>	The specified file is read-only. Therefore, the X-Tension Developer Studio add-in cannot add the specifications for the new server extension function to it.
<b>Action</b>	Change the ReadOnly parameter of the specified file.
<b>INOSXE7096</b>	<b>System error: 'errtext'</b>
<b>Explanation</b>	An operating system error occurred in the X-Tension Developer Studio add-in.
<b>Action</b>	Check the operating system documentation for further details.
<b>INOSXE7099</b>	<b>Cannot write to file 'filename'</b>
<b>Explanation</b>	The file has been opened, but a write operation failed. Possibly the disk is full.
<b>Action</b>	Check your hard disk space.
<b>INOSXE7100</b>	<b>Wrong package file: 'filename'</b>
<b>Explanation</b>	The file specified is not an output file of the X-Tension Developer Studio add-in package function.
<b>Action</b>	Only use package files created by the X-Tension Developer Studio add-in.
<b>INOSXE7101</b>	<b>Could not get XML session status. Server extension function rolled back at request end.</b>
<b>Explanation</b>	The X-Tension caller could not determine whether there was a regular or an anonymous XML session. So the Tamino server event 'rollback' was sent to all server extensions.
<b>Action</b>	No action required.

<b>INOSXE7102</b>	<b>Initialization of server extensions: server events not activated</b>
<b>Explanation</b>	The Tamino server events could not be activated when the Tamino server was started. Server extensions are not initialized and will not work.
<b>Action</b>	Restart the Tamino server. If this does not give the desired result, please contact your software supplier.
<b>INOSXE7103</b>	<b>Developer Studio automation error 'errno' (errtext)</b>
<b>Explanation</b>	The add-in caused an error when executing a Developer Studio command.
<b>Action</b>	Consult the Developer Studio documentation for further information.
<b>INOSXE7104</b>	<b>Method 'method' could not be found in file 'objfile'</b>
<b>Explanation</b>	The method indicated is not defined in the current server extension object file (Java class file or DLL/Shared Object), or another severe error occurred when accessing the server extension object file.
<b>Action</b>	Check the server extension project for the desired method.  Use the X-Tension development tools for developing server extensions!
<b>INOSXE7105</b>	<b>Project must be rebuilt before packing: 'file' is newer</b>
<b>Explanation</b>	One of the project sources is newer than the resulting server extension package.
<b>Action</b>	Call Build / Build <project name> in the Developer Studio before packing.
<b>INOSXE7106</b>	<b>One or more input fields are empty</b>
<b>Explanation</b>	All fields of this form must be set, but at least one field is empty.
<b>Action</b>	Make sure that all fields are correctly set.
<b>INOSXE7107</b>	<b>'name' is not a valid identifier</b>
<b>Explanation</b>	The name entered does not match C/C++ naming conventions.
<b>Action</b>	Check the name for proper syntax.
<b>INOSXE7108</b>	<b>Value for 'valuename' of a server extension not found in data map</b>
<b>Explanation</b>	A value for the specified name of a server extension was expected in the data map but is not present. The problem occurs due to problems at installation or in the repository. Here, the specified name is the name of an expected value.
<b>Action</b>	Re-install the server extension.

---

<b>INOSXE7109</b>	<b>Memory allocation failed</b>
<b>Explanation</b>	Memory allocation failed.
<b>Action</b>	Please contact your software supplier.
<b>INOSXE7110</b>	<b>Character conversion failed; error code = 'errcode'</b>
<b>Explanation</b>	An internal character conversion failed.
<b>Action</b>	See the Tamino documentation for the given error code. Check if Tamino is properly installed.
<b>INOSXE7113</b>	<b>Cannot find function 'funcname' in library 'libname'</b>
<b>Explanation</b>	The specified function name could not be found in the library. Maybe there is a version problem.
<b>Action</b>	Check your Tamino installation.
<b>INOSXE7114</b>	<b>Java error: Errtext: 'errtext'. Stacktrace: 'trace'.</b>
<b>Explanation</b>	A Java error occurred. See "Errtext" for more specific details. "Stacktrace" is the exception stack trace.
<b>Action</b>	See "Errtext" for more specific details and correct the code accordingly.
<b>INOSXE7115</b>	<b>Cannot create Java virtual machine; error 'errcode'</b>
<b>Explanation</b>	The Java virtual machine could not be started.
<b>Action</b>	Check the Java documentation for the given error code.
<b>INOSXE7116</b>	<b>Function 'sxfname' not found in server extension 'sxsname'</b>
<b>Explanation</b>	The function could not be found in the server extension. Probably the server extension implementation has been changed after installation.
<b>Action</b>	Try to re-install the server extension.
<b>INOSXE7117</b>	<b>Illegal call for Java method 'methodname' in class 'classname'</b>
<b>Explanation</b>	An error occurred during a call for a Java method. Probably the parameter count or the type(s) of at least one parameter is incorrect. For a server extension function, its implementation may have changed since the last installation.
<b>Action</b>	Re-install this server extension.

<b>INOSXE7118</b>	<b>'package' not available on this platform</b>
<b>Explanation</b>	The package specified (COM, Java or Direct) is not available on this platform. Server extensions based on this package cannot be executed.
<b>Action</b>	No action possible. This server extension cannot be run.
<b>INOSXE7119</b>	<b>'package' not installed on this platform</b>
<b>Explanation</b>	The package specified (COM or Java) is not installed on this platform.
<b>Action</b>	To run server extensions based on this package, install the specified package.
<b>INOSXE7120</b>	<b>X-Tension caller: parameter overflow, function 'name' parameter number 'no'</b>
<b>Explanation</b>	The input value was too small or too big.
<b>Action</b>	Change the input value and try again.
<b>INOSXE7121</b>	<b>XQL query function 'n': Wrong number of parameters. Required: 'm'.</b>
<b>Explanation</b>	The user passed a wrong number of parameters to a function called from within an XQL query.
<b>Action</b>	Repeat the call with the correct number of parameters.
<b>INOSXE7122</b>	<b>XQL query function 'n': Wrong type of parameter 'm'</b>
<b>Explanation</b>	The user input is of the wrong data type.
<b>Action</b>	Get information about parameter types of called functions (see the Tamino Manager or the third party manual for the corresponding server extension) and repeat the call with the correct input.
<b>INOSXE7123</b>	<b>Java error during initialization of Java server extension: 'errtext'</b>
<b>Explanation</b>	The error text gives detailed information about the error.
<b>Action</b>	Correct the fault and try again.
<b>INOSXE7124</b>	<b>Java error during call: 'errtext'</b>
<b>Explanation</b>	The error text gives detailed information about the error.
<b>Action</b>	Correct the fault and try again.

---

<b>INOSXE7125</b>	<b>Java error during server extension function parameter handling: 'errtext'</b>
<b>Explanation</b>	The error text gives detailed information about the error.
<b>Action</b>	Correct the fault and try again.
<b>INOSXE7126</b>	<b>Server extension failed</b>
<b>Explanation</b>	An error occurred when a Tamino server extension was called. The message is followed by another more detailed message.
<b>Action</b>	Analyze the detailed message and act accordingly.
<b>INOSXE7127</b>	<b>X-Tension : Java initialization failed</b>
<b>Explanation</b>	During X-Tension initialization the initialization of the Java virtual machine failed. No Java-based extension functions are available during this server session.
<b>Action</b>	If Java-based server extension functions are required, fix the Java problem (e.g. paths and internal configuration store entries) and start the Tamino server again.
<b>INOSXE7129</b>	<b>'location': Got no spinlock. Reason: 'retval'.</b>
<b>Explanation</b>	There is no lock available for your thread.
<b>Action</b>	Try again later.
<b>INOSXE7130</b>	<b>Internal error when 'location'</b>
<b>Explanation</b>	An unknown internal error occurred.
<b>Action</b>	Please contact your software supplier.
<b>INOSXE7132</b>	<b>'unusedinfrastructur' infrastructure is not available or currently disabled</b>
<b>Explanation</b>	The X-Tension infrastructure specified is either not available in this environment or is currently configured as disabled in the Tamino server parameters.
<b>Action</b>	If the required infrastructure is available in this environment, turn on the appropriate switch of the Tamino server parameters and restart the Tamino server to activate it. If the infrastructure is not available, the relevant server extension code attempting to use it should be modified to utilise a supported infrastructure.
<b>INOSXE7136</b>	<b>Wrong command line for the server extension wrapper tool: 'arg'</b>
<b>Explanation</b>	The command line for the server extension wrapper tool has incorrect syntax.
<b>Action</b>	Please check the documentation for the command line syntax of the server extension wrapper tool or use the server extension development tools to set up a direct server extension project.

<b>INOSXE7137</b>	<b>Duplicate option 'c'</b>
<b>Explanation</b>	The given option may not occur more than once in the command line for the server extension wrapper tool.
<b>Action</b>	Please check the documentation for the command line syntax of the server extension wrapper tool or use the server extension development tools to set up a direct server extension project.
<b>INOSXE7138</b>	<b>Wrong option 'c'</b>
<b>Explanation</b>	The given option is invalid in the command line for the server extension wrapper tool.
<b>Action</b>	Please check the documentation for the command line syntax of the server extension wrapper tool or use the server extension development tools to set up a direct server extension project.
<b>INOSXE7140</b>	<b>No valid JVM, install valid JVM or switch X-Tension Java Usage to 'NO'</b>
<b>Explanation</b>	Error detected when loading a JVM for current Tamino version
<b>Action</b>	Check if JVM is installed, if a valid JVM Version is installed or switch X-Tension Java Usage to 'NO'.
<b>INOSXE7141</b>	<b>Server extension 'name' already locked</b>
<b>Explanation</b>	The server extension is locked by another operation.
<b>Action</b>	Retry the requested operation when the lock has been removed.
<b>INOSXE7142</b>	<b>Server extension 'name' is active</b>
<b>Explanation</b>	The server extension is in use.
<b>Action</b>	Retry the requested operation when the server extension has finished.
<b>INOSXE7143</b>	<b>Server extension 'name' not found</b>
<b>Explanation</b>	The server extension does not exist.
<b>Action</b>	Correct the server extension name and retry the operation.
<b>INOSXE7144</b>	<b>Server extension function 'name' not found</b>
<b>Explanation</b>	The server extension function does not exist.
<b>Action</b>	Correct the function name and retry the operation.

---

<b>INOSXE7145</b>	<b>Wrong modification operation 'type'</b>
<b>Explanation</b>	The requested modification operation is not implemented.
<b>Action</b>	Correct the modification operation type and retry the operation.
<b>INOSXE7146</b>	<b>Wrong execution mode 'mode'</b>
<b>Explanation</b>	The requested execution mode is not allowed.
<b>Action</b>	Correct the execution mode and retry the operation.
<b>INOSXE7147</b>	<b>Files for server extension 'name' not restored</b>
<b>Explanation</b>	Some files of the server extension have not been restored.
<b>Action</b>	Ensure that the Tamino server has write access to the file system and retry the operation.
<b>INOSXE7148</b>	<b>Files for server extension 'name' not removed</b>
<b>Explanation</b>	Some files of the server extension have not been removed.
<b>Action</b>	Ensure that the files are not locked by another action and retry the operation.
<b>INOSXE7149</b>	<b>Files for server extension 'name' not stored</b>
<b>Explanation</b>	Some files of the server extension have not been stored.
<b>Action</b>	Ensure that the files are not locked by another action and retry the operation.
<b>INOSXE7150</b>	<b>Installation document for server extension 'name' not stored</b>
<b>Explanation</b>	The installation document of the server extension has not been stored.
<b>Action</b>	Ensure that the installation document is not locked by another action and retry the operation.
<b>INOSXE7151</b>	<b>Event Function call failed for server extension: a, Event: b</b>
<b>Explanation</b>	Event functions are for cleaning up server extension data after commit, rollback, session end and so on. See the X-Tension manual (server extension Functions/Server Event Functions), for information about which event failed.
<b>Action</b>	Analyze the cause of failure. If necessary, ask the programmer or vendor of the server extension. Check the data that was written outside the Tamino server by the failed extension for consistency.

<b>INOSXE7152</b>	<b>Attribute 'hidden' cannot be assigned to or removed from this parameter</b>
<b>Explanation</b>	An attempt was made to assign or remove the 'hidden' attribute. This operation is only successful if the parameter has the 'input' direction (for assignment) or the parameter is 'hidden' (for removal).
<b>Action</b>	Check the server extension function and its parameters and read the documentation.
<b>INOSXE7153</b>	<b>This parameter cannot be assigned a default value</b>
<b>Explanation</b>	To assign a default value to a parameter, this parameter must have the 'input' direction.
<b>Action</b>	Check the current server extension function and its parameters.
<b>INOSXE7154</b>	<b>Wrong position for optional / hidden parameter</b>
<b>Explanation</b>	The order for parameters must be: mandatory - optional - hidden - return value.
<b>Action</b>	Please check the order of the server extension function's parameters and their usage.
<b>INOSXE7158</b>	<b>Server extension function parameter 'name' not found</b>
<b>Explanation</b>	The server extension function parameter does not exist.
<b>Action</b>	Correct the parameter name and retry the operation.
<b>INOSXE7160</b>	<b>Duplicate occurrence of 'functiontype'</b>
<b>Explanation</b>	Only one event function or init function may be defined within a server extension.
<b>Action</b>	Check your server extension and delete one of the functions that is superfluous, or use the X-Tension development tools to create and edit the server extension.
<b>INOSXE7161</b>	<b>Invalid input for field: field</b>
<b>Explanation</b>	The user input for the specified field is invalid. Either invalid characters have been used or the format of the characters used is incorrect.
<b>Action</b>	Please correct the specified field.
<b>INOSXE7162</b>	<b>Document not found for specified ino:id/docname</b>
<b>Explanation</b>	A document could not be found using the specified ino:id or docname.
<b>Action</b>	Please specify a valid ino:id or docname.

---

<b>INOSXE7255</b>	<b>Java Exception</b>
<b>Explanation</b>	Specified Java exception occurred
<b>Action</b>	Resolve the specified Java exception
<b>INOSXF6718</b>	<b>Timeout during execution of server extension function</b>
<b>Explanation</b>	Possible reasons are: 1) There is an endless loop in the server extension function. 2) A server extension function is executed with endless recursion.
<b>Action</b>	Check the server extension carefully. For example, calling the callback SxsXmlProcess will result in an endless recursion if the collection name is the same as the current server extension function is assigned to.
<b>INOSXF6719</b>	<b>Process 'exefile' (for Direct Local) has stopped with rc = rc</b>
<b>Explanation</b>	The external process for X-Tension direct infrastructure (local mode) has aborted. See error for more details.
<b>Action</b>	Check your server extension. Probably it killed the external process for local mode.
<b>INOSXF6720</b>	<b>Stack overflow in server extension function</b>
<b>Explanation</b>	A stack overflow occurred during call of a server extension function.
<b>Action</b>	Check your server extension. Perhaps it has endless recursion.
<b>INOSXF7028</b>	<b>Illegal call of Connect/Disconnect</b>
<b>Explanation</b>	This error may occur in a Visual Basic or Natural implementation of a server extension. Reasons for this error may be: The Connect and Disconnect methods of the InoCallback interface have been called outside ISXSConn_Connect or ISXSConn_Disconnect or have been called there more than once.
<b>Action</b>	Implement ISXSConn_Connect and ISXSConn_Disconnect exactly as shown in the documentation. Do not call the Connect and Disconnect methods of InoCallback outside ISXSConn_Connect and ISXSConn_Disconnect.
<b>INOSXF7030</b>	<b>'tool' does not support server extensions of type 'type'</b>
<b>Explanation</b>	The X-Tension Builder tried to open a COM server extension.
<b>Action</b>	With the X-Tension Builder, open Java or Direct server extensions only.

<b>INOSXF7033</b>	<b>Server extension 'sxsname' not properly installed. Reason: 'reason'.</b>
<b>Explanation</b>	One or more installation steps for this server extension have been skipped or failed. See 'Reason' for more information.
<b>Action</b>	Use the X-Tension Administration of the Tamino Manager to install the server extension.
<b>INOSXF7035</b>	<b>Cannot load library sxcall</b>
<b>Explanation</b>	The library sxcall necessary for Tamino X-Tension cannot be loaded. Therefore no server extensions can be executed in this Tamino installation.
<b>Action</b>	Check your Tamino installation.
<b>INOSXF7036</b>	<b>Cannot load a function in library sxcall</b>
<b>Explanation</b>	Not all functions necessary to run Tamino X-Tension can be found in library sxcall. Therefore no server extensions can be executed in this Tamino installation. Probably there is a version mismatch between the library sxcall and the rest of Tamino.
<b>Action</b>	Check your Tamino installation.
<b>INOSXF7037</b>	<b>Internal configuration store entry not found</b>
<b>Explanation</b>	An internal configuration store entry necessary to initialize Tamino X-Tension or one of the Tamino X-Tension components cannot be found. If this error occurs during Tamino startup, no server extensions can be executed in this Tamino installation.
<b>Action</b>	Check your Tamino installation.
<b>INOSXF7038</b>	<b>Cannot find current version in internal configuration store</b>
<b>Explanation</b>	The 'current version' entry in the internal configuration store that is necessary to initialize Tamino X-Tension or one of the Tamino X-Tension components cannot be found. If this error occurs during Tamino startup, no server extensions can be executed in this Tamino installation.
<b>Action</b>	Check your Tamino installation.
<b>INOSXF7039</b>	<b>Cannot load jvm library</b>
<b>Explanation</b>	The jvm library (libraries) necessary to run Java server extensions cannot be loaded. Therefore no server extensions can be executed in this Tamino installation.
<b>Action</b>	Check your Tamino installation as well as your Java installation. Look if \$LD_LIBRARY_PATH on UNIX (or %PATH% on Windows) includes all required JDK directories.

---

<b>INOSXF7042</b>	<b>Cannot find executable file 'execfile'</b>
<b>Explanation</b>	The indicated file could not be found in any of the directories listed in PATH.
<b>Action</b>	Check installation(s) on your computer and check your PATH setting.
<b>INOSXF7043</b>	<b>Tamino X-Tension not properly installed. Reason: 'reason'.</b>
<b>Explanation</b>	The X-Tension development tool cannot create a new server extension project because Tamino X-Tension component is not properly installed on your computer.
<b>Action</b>	Use the Install Tool for a correct installation of Tamino X-Tension.
<b>INOSXF7044</b>	<b>Error calling 'execfile'. Reason: 'reason'.</b>
<b>Explanation</b>	An error occurred while trying to start an external process with the indicated file. See the additional text for more details.
<b>Action</b>	Check the given file for correctness.
<b>INOSXF7097</b>	<b>Tamino X-Tension not properly installed</b>
<b>Explanation</b>	The X-Tension development tool cannot create a new server extension project because Tamino X-Tension component is not properly installed on your computer.
<b>Action</b>	Use the Install Tool for a correct installation of Tamino X-Tension.
<b>INOSXF7098</b>	<b>Fatal error</b>
<b>Explanation</b>	An unspecified error occurred.
<b>Action</b>	Please contact your software supplier.
<b>INOSXF7111</b>	<b>Server extension 'xsxname' not properly installed</b>
<b>Explanation</b>	One or more installation steps for this server extension have been skipped or failed.
<b>Action</b>	Use the X-Tension Administration of the Tamino Manager to install a server extension.
<b>INOSXF7112</b>	<b>Cannot load library 'libname': error 'rc'</b>
<b>Explanation</b>	The specified library could not be loaded. Maybe it has been moved from its original location, or environment variables or internal configuration store entries have been changed since the last Tamino installation.
<b>Action</b>	Check your PATH and your Tamino installation.

<b>INOSXF7133</b>	<b>No class has been found that can be used as a direct server extension class.</b>
<b>Explanation</b>	Either there is no class defined in the given header file or none of the classes defined here can be used as a direct server extension.
<b>Action</b>	Please check the documentation about requirements for direct Server Extension classes or use the X-Tension development tools to create a Server Extension.
<b>INOSXF7134</b>	<b>There are at least two classes ('class1', 'class2') that can be used as direct server extensions</b>
<b>Explanation</b>	A header file that should be processed by the direct server extension wrapper tool may define only one class that can be used as a direct server extension.
<b>Action</b>	Please check the documentation on how to mark C++ classes for use as direct server extensions or move all class definitions except the direct server extension class to a different header file.
<b>INOSXF7155</b>	<b>Internal error: 'id'</b>
<b>Explanation</b>	A severe internal error occurred.
<b>Action</b>	Please note the value of the internal error and contact your software supplier.
<b>INOSXF7156</b>	<b>Cannot start process 'exefile' for X-Tension direct infrastructure (local mode)</b>
<b>Explanation</b>	The system cannot start a new process for X-Tension direct infrastructure (local mode).
<b>Action</b>	Check the existence of the file indicated. It should be located in directory Tamino/<version>/bin.
<b>INOSXF7157</b>	<b>Process 'exefile' (for Direct Local) is not running</b>
<b>Explanation</b>	The external process for X-Tension direct infrastructure (local mode) has aborted or is not running for other reason.
<b>Action</b>	Check your server extension. Perhaps it killed the external process for local mode.
<b>INOSXF7251</b>	<b>Thread could not be attached to JVM, return code 'rc'</b>
<b>Explanation</b>	The current XML worker thread could not be attached to the Java virtual machine. Tamino server extensions were not initialized. The return code is the return value of the JNI call "AttachCurrentThread()".
<b>Action</b>	Analyze why the Java call failed and solve the cause of the problem. Then start Tamino server again.

<b>INOSXF7252</b>	<b>Metadata update failed: id</b>
<b>Explanation</b>	Metadata update has failed.
<b>Action</b>	<p>In the case of CentraSite database startup failure indicated by the production of the console message: "INOSXF7252: Metadata update failed" the following information is essential to analyse the problem.</p> <p>The most useful file in these circumstances is the "inosrv.txt" file. This is normally called something like AABinosrv.HH-MM-SS.txt and would normally be present in the same directory as the actual database data files.</p> <pre>inoadmin set CentraSite "request log" "full" norestart</pre> <pre>inoadmin set CentraSite "X-Tension Java Options" "\$-Dlog4j.configuration=file://{full path to log4j.properties}" restart</pre> <pre>log4j.rootLogger=WARN, file</pre> <pre>log4j.logger.com.centrasite.centrasite.onstartup=DEBUG</pre> <pre>log4j.appender.file=org.apache.log4j.FileAppender</pre> <pre>log4j.appender.file.layout=org.apache.log4j.PatternLayout</pre> <pre>log4j.appender.file.layout.ConversionPattern=%d %8r [%t]%-5p %c{3} %x - %m%n</pre> <pre>log4j.appender.file.File={full path to log file}</pre>
<b>INOSXI6708</b>	<b>X-Tension usage is currently disabled</b>
<b>Explanation</b>	All of the X-Tension infrastructures (COM, Java and Direct) are currently disabled.
<b>Action</b>	Turn on the appropriate switch of the Tamino server parameters and restart the Tamino server.
<b>INOSXI6723</b>	<b>JVM started with user options 'jvm_options'</b>
<b>Explanation</b>	The JVM was started with the specified additional user options.
<b>Action</b>	No action required.
<b>INOSXI7029</b>	<b>Finished searching the file</b>
<b>Explanation</b>	The 'Find What' string has not been found after (Direction <i>Down</i> ) or before (Direction <i>Up</i> ) the current position.
<b>Action</b>	Deselect 'Match case' or select another string.

<b>INOSXI7050</b>	<b>COM for server extension is deactivated</b>
<b>Explanation</b>	COM for server extension is switched off.
<b>Action</b>	Switch on COM for server extension with Tamino Manager.
<b>INOSXI7128</b>	<b>Java for server extension is deactivated</b>
<b>Explanation</b>	Java for server extensions is switched off
<b>Action</b>	Switch on Java for server extension with the Tamino Manager
<b>INOSXI7131</b>	<b>X-Tension 'unusedinfrastructur' usage is currently disabled</b>
<b>Explanation</b>	The specified X-Tension infrastructure (COM, Java or Direct) is currently disabled.
<b>Action</b>	Turn on the appropriate switch of the Tamino server parameters and restart the Tamino server.
<b>INOSXI7253</b>	<b>Metadata update succeeded: id</b>
<b>Explanation</b>	Metadata update has finished successfully.
<b>Action</b>	None
<b>INOSXI7254</b>	<b>Metadata update started.</b>
<b>Explanation</b>	Metadata update has started. This may be a lengthy operation.
<b>Action</b>	None.
<b>INOSXV6726</b>	<b>COM server extensions are deprecated</b>
<b>Explanation</b>	COM server extensions are deprecated and will not be supported in future.
<b>Action</b>	Plan the replacement of your COM server extensions by using a different server extension infrastructure.
<b>INOSXW6700</b>	<b>'function' can no longer be used as 'functype'</b>
<b>Explanation</b>	One of the parameters has been modified or deleted. Therefore this server extension function can no longer be used as the specified function type.
<b>Action</b>	Check the Tamino server extension documentation for the different function types.

---

<b>INOSXW6701</b>	<b>At least one of the help files does not exist. It will be removed from the list.</b>
<b>Explanation</b>	The Install.xml file for your current X-Tension project has an entry for a help file that no longer exists. It will be removed from your list of help files.
<b>Action</b>	Select a new file.
<b>INOSXW6702</b>	<b>Warning: Settings for compiler 'compiler' already exist and will be overwritten</b>
<b>Explanation</b>	Compiler and linker flags already exist for the compiler specified in this warning. Choosing 'OK' will overwrite these settings.
<b>Action</b>	Choose 'OK' to overwrite these settings or 'Cancel' to stop this action.
<b>INOSXW6703</b>	<b>The path 'path' will be added to the list of executable files of Visual Studio</b>
<b>Explanation</b>	Some libraries residing in Tamino system directories are needed to build a server extension. These directories must be listed in the "Executable files" section of your Visual Studio configuration. If not yet present, sxwizard will add these directories automatically.
<b>Action</b>	Click on OK to accept these changes to your Visual Studio configuration. If you click on Cancel, no changes will be made and sxwizard will be stopped.
<b>INOSXW6721</b>	<b>Project will be moved from platform 'platform1' to 'platform2'</b>
<b>Explanation</b>	This (SXS Direct) project has been created on platform1. It is now opened on a different platform platform2, and a new make file will be created such that it can be compiled on this new platform.
<b>Action</b>	Click OK to generate a new make file, or click cancel if you do not want to have a new make file created. However, this project probably cannot be compiled on this platform.
<b>INOSXW6722</b>	<b>Project will be moved from an older Tamino version to platform 'platform'</b>
<b>Explanation</b>	This (SXS Direct) project has been created by an older version of Tamino. It is now opened by a newer Tamino version on a different platform. A new make file will be created such that it can be compiled in this version and on this new platform.
<b>Action</b>	Click OK to generate a new make file, or click cancel if you do not want to have a new make file created. However, this project probably cannot be compiled in this Tamino version.
<b>INOSXW6724</b>	<b>Unable to start JVM with user options 'jvm_options'. Starting with default options instead.</b>
<b>Explanation</b>	Conflicting or incorrect user options were specified for the JVM, so the JVM could not start. The JVM will be started with the default options.
<b>Action</b>	Correct the user options specified for the JVM and restart the server.

<b>INOSXW6727</b>	<b>The server extension generated a warning.</b>
<b>Explanation</b>	The server extension has invoked the warning XML callback. This will insert a warning into the Tamino response.
<b>Action</b>	The warning message is for informational purposes.
<b>INOSXW6728</b>	<b>Execution failed: command</b>
<b>Explanation</b>	The specified operating system command failed.
<b>Action</b>	Check the SXS installation values for faults.
<b>INOSXW7002</b>	<b>Existing server extension project at 'pathname' will be overwritten</b>
<b>Explanation</b>	A server extension project already exists in the given directory. It will be overwritten if you select "Finish".
<b>Action</b>	Press "OK" to overwrite this project or select another directory.
<b>INOSXW7003</b>	<b>Java initialization failed. Reason: 'errno', 'errtxt'.</b>
<b>Explanation</b>	Tamino was not able to create a Java virtual machine. Java based server extensions will not work.
<b>Action</b>	Make the Java virtual machine available to Tamino and start the Tamino server again or switch the server property X-Tension Java Usage to 'NO'.
<b>INOSXW7004</b>	<b>Java thread initialization failed. Reason: 'errno', 'errtxt'.</b>
<b>Explanation</b>	An XML worker thread could not be attached to the Java virtual machine. Java based server extensions will not work.
<b>Action</b>	Fix the problem of Java initialization and start the Tamino server again.
<b>INOSXW7005</b>	<b>Initialization of COM library failed. Reason: 'errno', 'errtxt'.</b>
<b>Explanation</b>	COM based server extensions will not work.
<b>Action</b>	Make the COM library available to the Tamino server, then start it again.
<b>INOSXW7007</b>	<b>No license for Tamino X-Tension</b>
<b>Explanation</b>	A special license must be bought to use the Tamino X-Tension feature.
<b>Action</b>	Buy a license for Tamino X-Tension.

---

<b>INOSXW7008</b>	<b>Tamino X-Tension not available</b>
<b>Explanation</b>	On this platform the Tamino X-Tension feature is not available.
<b>Action</b>	No action required.
<b>INOSXW7011</b>	<b>This will remove all previously selected files from your package list</b>
<b>Explanation</b>	For a server extension package, either one or more class files or ONE jar file can be used. This warning shows up in one of the following cases: 1) A jar file was selected and a class file will be added to the class file list: The jar file will be removed from the list. 2) One or more class files or another jar file were selected, and a jar file will be added: All recently selected files will be removed.
<b>Action</b>	Choose "OK" to confirm or "Cancel" to cancel the current selection
<b>INOSXW7012</b>	<b>Main Class File for server extension missing</b>
<b>Explanation</b>	For a server extension package, either one or more class files or ONE jar file can be used. This warning shows up when none of the selected class files contains the main class of the server extension.
<b>Action</b>	Add another class file that contains the main class of the server extension.
<b>INOSXW7013</b>	<b>Server extension might not run without these class(es)</b>
<b>Explanation</b>	In the Packaging Dialogue of the X-Tension Builder, one of the selected class files is about to be removed. Without this class file the installation of this server extension will be incomplete.
<b>Action</b>	Check if this class file is really unnecessary for the current server extension.
<b>INOSXW7031</b>	<b>Directory 'dir' does not exist and will be created</b>
<b>Explanation</b>	This directory does not exist and will be created.
<b>Action</b>	Select "OK" to create this directory, select "Cancel" to cancel project creation.
<b>INOSXW7135</b>	<b>The given class contains no server extension function</b>
<b>Explanation</b>	The given class does not contain any method that can be used as a server extension function.
<b>Action</b>	Enter some methods using the direct server extension development tools.

<b>INOSXW7139</b>	<b>No valid JVM, install valid JVM or switch X-Tension Java Usage to 'NO'</b>
<b>Explanation</b>	Error detected when loading a JVM for current Tamino version
<b>Action</b>	Check if JVM is installed, if a valid JVM Version is installed or switch X-Tension Java Usage to 'NO'.
<b>INOSXW7159</b>	<b>Value will be set to empty string</b>
<b>Explanation</b>	A default value or configuration parameter (Init Function) may be set to empty string if data type is charstring.
<b>Action</b>	Please check if in this special case this effect is intended.
<b>INOX2E8000</b>	<b>Usage of distributed transaction processing is not supported on this platform</b>
<b>Explanation</b>	It is not possible to use distributed transaction processing features on the Tamino server platform.
<b>Action</b>	None - the platform does not support distributed transaction processing.
<b>INOX2E8001</b>	<b>Conversion of the distributed transaction processing transaction identifier was not possible</b>
<b>Explanation</b>	The transaction identifier provided does not have a defined method to convert it to the internal format.
<b>Action</b>	Contract your software supplier - this is a software error.
<b>INOX2E8002</b>	<b>An internal error occurred dealing with the transaction identifier in distributed transaction</b>
<b>Explanation</b>	The transaction identifier caused an internal error when being processed.
<b>Action</b>	Contract your software supplier - this is a software error.
<b>INOX2E8003</b>	<b>Server encountered an error while performing a distributed transaction processing action</b>
<b>Explanation</b>	A distributed transaction processing action resulted in the server not being able to complete the action requested.
<b>Action</b>	Contract your software supplier - this is a software error.

---

<b>INOX2E8004</b>	<b>The specified distributed transaction processing identifier is unknown by the server</b>
<b>Explanation</b>	A transaction identifier was specified which is unknown to the server. This can happen if a timeout occurred or if the transaction has not been prepared before a server restart.
<b>Action</b>	This message will be given back by the server to the transaction manager.
<b>INOX2E8005</b>	<b>An invalid argument was detected on a distributed transaction processing call</b>
<b>Explanation</b>	An argument supplied by the transaction manager was invalid.
<b>Action</b>	This message will be given back by the server to the transaction manager.
<b>INOX2E8006</b>	<b>Protocol error - an action requested by the transaction manager was invoked in an improper context</b>
<b>Explanation</b>	The specified action cannot be carried out in the current distributed transaction state.
<b>Action</b>	This message will be given back by the server to the transaction manager.
<b>INOX2E8007</b>	<b>An error has occurred which makes server unavailable to process the transaction manager's action</b>
<b>Explanation</b>	The action requested by the transaction manager cannot be fulfilled by Tamino currently.
<b>Action</b>	This message will be given back by the server to the transaction manager.
<b>INOX2E8008</b>	<b>Duplicate distributed transaction identifier encounter while enlisting in a distributed transaction</b>
<b>Explanation</b>	A duplicate transaction identifier was encountered while enlisting in a distributed transaction.
<b>Action</b>	This is an internal error and should be reported to your software supplier.
<b>INOX2E8010</b>	<b>The specified distributed transaction has been rollback</b>
<b>Explanation</b>	The server has decided that this distributed transaction can only be rolled back.
<b>Action</b>	This message is a reply to a transaction manager request.
<b>INOX2E8011</b>	<b>A communications error has occurred</b>
<b>Explanation</b>	A communications error occurred while attempting a distributed transaction processing action sent by the transaction manager.
<b>Action</b>	This message is a reply to a transaction manager request.

<b>INOX2E8012</b>	<b>The server has detected a deadlock involving the specified distributed transaction</b>
<b>Explanation</b>	A deadlock has been detected for the specified distributed transaction. The transaction has been rolled back.
<b>Action</b>	This message is a reply to a transaction manager request.
<b>INOX2E8013</b>	<b>The server has detected an integrity violation for the resources requested by the specified distributed transaction</b>
<b>Explanation</b>	An integrity violation has been detected for the specified distributed transaction. The transaction has been rolled back.
<b>Action</b>	This message is a reply to a transaction manager request
<b>INOX2E8014</b>	<b>The server has detected an unspecified error for the specified distributed transaction</b>
<b>Explanation</b>	An unspecified has been detected for the specified distributed transaction. The transaction has been rolled back.
<b>Action</b>	This message is a reply to a transaction manager request
<b>INOX2E8015</b>	<b>The server has detected an internal protocol error for the specified distributed transaction</b>
<b>Explanation</b>	An internal protocol error has been detected for the specified distributed transaction.
<b>Action</b>	This message is a reply to a transaction manager request.
<b>INOX2E8016</b>	<b>The server has timed out the specified distributed transaction</b>
<b>Explanation</b>	The server timed out the specified distributed transaction.
<b>Action</b>	This message is a reply to a transaction manager request.
<b>INOX2E8017</b>	<b>The server has detected a transient error for the specified distributed transaction</b>
<b>Explanation</b>	The server has detected a transient error for the specified distributed transaction.
<b>Action</b>	This message is a reply to a transaction manager request.
<b>INOX2E8018</b>	<b>The server has heuristically committed the specified distributed transaction</b>
<b>Explanation</b>	The server had to heuristically commit the specified distributed transaction.
<b>Action</b>	This message is reply to a transaction manager request.

---

<b>INOX2E8019</b>	<b>The server has heuristically rolled back the specified distributed transaction</b>
<b>Explanation</b>	The server had to heuristically roll back the specified distributed transaction.
<b>Action</b>	This is message is reply to a transaction manager request.
<b>INOX2E8020</b>	<b>The server has heuristically completed the distributed transaction. The outcome of the transaction is mixed.</b>
<b>Explanation</b>	The server had to heuristically complete the specified distributed transaction. The outcome is however mixed; this means that part of the transaction was committed and the rest was rolled back.
<b>Action</b>	This message is a reply to a transaction manager request.
<b>INOX2E8021</b>	<b>The specified distributed transaction is read-only</b>
<b>Explanation</b>	There were no modifications made to the server by the specified distributed transaction and therefore the server does not need to receive the commit action from the transaction manager.
<b>Action</b>	This message is a reply to a transaction manager request.
<b>INOX2E8022</b>	<b>An error occurred while issuing a call to the transaction manager</b>
<b>Explanation</b>	The transaction manager rejected a request made by Tamino.
<b>Action</b>	See the extended error messages for the transaction manager's reason for rejecting the call.
<b>INOX2E8023</b>	<b>The command is not allowed while a distributed transaction is active within this session</b>
<b>Explanation</b>	An attempt was made to issue either a <code>_DISCONNECT</code> command before the completion of the distributed transaction or a <code>_COMMIT/_ROLLBACK</code> command in the distributed transaction. These are not allowed.
<b>Action</b>	Complete the two phase commit transaction before issuing the <code>_DISCONNECT</code> command.
<b>INOX2E8024</b>	<b>The current session cannot accept commands while the two phase commit transaction completion protocol is active</b>
<b>Explanation</b>	Issuing Tamino commands to a session that is between phase 1 and phase 2 of a two phase commit transaction completion protocol is not allowed. The two phase commit protocol must complete before the session can be used again.
<b>Action</b>	Do not issue commands while the two phase commit transaction completion protocol is active.

<b>INOX2E8025</b>	<b>The transaction manager specified an invalid recovery action</b>
<b>Explanation</b>	The request action on recovery was invalid.
<b>Action</b>	This is an error sent to the transaction manager. It is internal and if seen should be reported to your software supplier.
<b>INOX2E8027</b>	<b>The outcome of a commit was inconsistent</b>
<b>Explanation</b>	The outcome of a commit was inconsistent: one or more data sources failed to commit.
<b>Action</b>	Check the extended error information for a list of which data sources failed to commit the transaction, then perform appropriate repairs.
<b>INOX2E8028</b>	<b>The outcome of a rollback was inconsistent</b>
<b>Explanation</b>	The outcome of a rollback was inconsistent: one or more data sources failed to roll back.
<b>Action</b>	Check the extended error information for a list of which data sources failed to commit the transaction, then perform appropriate repairs.
<b>INOX2E8030</b>	<b>Invalid transaction token</b>
<b>Explanation</b>	An invalid transaction token was specified.
<b>Action</b>	Provide a valid transaction token with the correct format.
<b>INOX2E8047</b>	<b>Recovery of distributed transactions has found outstanding transactions that are not for the current transaction manager</b>
<b>Explanation</b>	After completion by the transaction manager of recovery for distributed transactions, there are outstanding transactions that do not belong to the transaction manager.
<b>Action</b>	Contact your software supplier for help in resolving the outstanding transactions.
<b>INOX2E8049</b>	<b>An internal error occurred in the distributed transaction processing components of the server.</b>
<b>Explanation</b>	An internal error occurred.
<b>Action</b>	This is an internal error. Please contact your software supplier.
<b>INOX2F8026</b>	<b>Cannot find distributed transaction processing (DTP) library ino2pc</b>
<b>Explanation</b>	The shared library/DLL ino2pc cannot be found.
<b>Action</b>	This is a software installation configuration problem. Contact Software AG support for help

---

<b>INOX2I8046</b>	<b>Distributed transaction transaction_token with resource manager identifier rmid has been manually resolved to the 'state' state</b>
<b>Explanation</b>	This event is generated when someone manually resolves a distributed transaction.
<b>Action</b>	No action required. This message helps to track the progress of the distributed transaction.
<b>INOX2I8048</b>	<b>Server start-up detected pending or heuristically complete distributed transactions</b>
<b>Explanation</b>	On starting the server, it has been detected that there are outstanding distributed transactions. These transactions should normally be resolved by the transaction manager.
<b>Action</b>	Check the transaction manager log to check that all outstanding distributed transactions are resolved. If the transactions are not resolved, then contact your software supplier to get help in resolving them.
<b>INOXCE8100</b>	<b>Internal error: duplicate root element</b>
<b>Explanation</b>	Invalid migrated data records with duplicate root elements were detected.
<b>Action</b>	Please contact your software supplier.
<b>INOXCE8102</b>	<b>Internal error: document stack corrupted</b>
<b>Explanation</b>	An internal error has occurred.
<b>Action</b>	Please contact your software supplier.
<b>INOXCE8103</b>	<b>Memory allocation failed</b>
<b>Explanation</b>	There was not enough main memory available to perform the request.
<b>Action</b>	Possibly the machine is overloaded. Try again later.
<b>INOXCE8104</b>	<b>Internal error during document composition</b>
<b>Explanation</b>	An internal error has occurred.
<b>Action</b>	Please contact your software supplier.
<b>INOXCE8105</b>	<b>Invalid X-Tension response</b>
<b>Explanation</b>	An X-Tension function returned a string that is not well-formed XML.
<b>Action</b>	Correct the implementation of the X-Tension function

<b>INOXCE8106</b>	<b>Internal error: unknown request</b>
<b>Explanation</b>	An internal error occurred.
<b>Action</b>	Please contact your software supplier.
<b>INOXCE8107</b>	<b>Map to object: illegal document ID encountered.</b>
<b>Explanation</b>	The query attached to a node with map-type=object is of the form "@ino:id=%parent". The document ID found in the parent node is either zero or contains non-digit characters.
<b>Action</b>	The document ID in the parent node is illegal, correct it.
<b>INOXCE8108</b>	<b>Insufficient mapping information, document cannot be composed</b>
<b>Explanation</b>	An XML document could not be created due to insufficient mapping information.
<b>Action</b>	Look at the <ino:messageline> element in the <ino:response> document to find more information about the cause of the problem.
<b>INOXCE8109</b>	<b>Cannot delete externally mapped data</b>
<b>Explanation</b>	Tamino X-Query is not able to delete XML documents that are composed from external data sources like ODBC or Adabas if those documents have not been stored through Tamino. Typically, when displayed, these documents do not have an "ino:id" attribute. Similarly, X-Query cannot delete data from doctypes with "tsd:pure" mapping.
<b>Action</b>	Modify the query that selects the documents to be deleted. In the case of pure mapping, use XQuery update in order to delete documents.
<b>INOXCE8110</b>	<b>Internal error: document data corrupted</b>
<b>Explanation</b>	An internal error has occurred.
<b>Action</b>	Please contact your software supplier.
<b>INOXCE8111</b>	<b>Error in XNode Adabas processing during conversion of Natural date/time value</b>
<b>Explanation</b>	An error occurred while converting a Natural date or time value. The Tamino response contains details about the offending value, as well as an internal error code.
<b>Action</b>	Analyze the error.

---

<b>INOXCE8114</b>	<b>Document ID unknown, mapping type infofield</b>
<b>Explanation</b>	This error message should never occur.
<b>Action</b>	None
<b>INOXCE8117</b>	<b>Internal error:Document not found</b>
<b>Explanation</b>	An internal error has occurred.
<b>Action</b>	Please contact your software supplier.
<b>INOXCE8118</b>	<b>Mapping type object: number of resulting objects too large</b>
<b>Explanation</b>	This message should never occur
<b>Action</b>	None
<b>INOXCE8119</b>	<b>Internal error: structure description too large</b>
<b>Explanation</b>	An internal error has occurred.
<b>Action</b>	Please contact your software supplier.
<b>INOXDE7500</b>	<b>NOTATION must be restricted by an enumeration</b>
<b>Explanation</b>	NOTATION must be restricted by an enumeration.
<b>Action</b>	Please modify your XML schema accordingly.
<b>INOXDE7501</b>	<b>(a-props-correct.2) default or fixed value is not of declared type</b>
<b>Explanation</b>	If there is a default or fixed value specification, the canonical lexical representation of its value must be valid with respect to the type definition.
<b>Action</b>	Please modify your XML schema accordingly.
<b>INOXDE7502</b>	<b>(a-props-correct.3) If attributes has type ID or a derived type it must not have a value constraint, i.e. a default or fixed value</b>
<b>Explanation</b>	Attributes of type ID or a derived type must not have a value constraint, i.e. a default or fixed value.
<b>Action</b>	Please modify your XML schema accordingly.

<b>INOXDE7503</b>	<b>(e-props-correct.2) default or fixed value is not of declared type</b>
<b>Explanation</b>	If there is a default or fixed value specification, the canonical lexical representation of its value must be valid with respect to the type definition.
<b>Action</b>	Please modify your XML schema accordingly.
<b>INOXDE7504</b>	<b>(e-props-correct.4) Elements of type ID or a derived type must not have a value constraint, i.e. a default or fixed value</b>
<b>Explanation</b>	Elements of type ID or a derived type must not have a value constraint, i.e. a default or fixed value.
<b>Action</b>	Please modify your XML schema accordingly.
<b>INOXDE7505</b>	<b>(ct-props-correct.4) attributes must not have identical names</b>
<b>Explanation</b>	Two distinct attribute declarations in the attribute uses must not have identical names.
<b>Action</b>	Please modify your XML schema accordingly.
<b>INOXDE7506</b>	<b>(ct-props-correct.5) only one attribute may have type ID or a derived type</b>
<b>Explanation</b>	Two distinct attribute declarations in the attribute uses must not have type ID or a derived type.
<b>Action</b>	Please modify your XML schema accordingly.
<b>INOXDE7507</b>	<b>(au-props-correct.2) attribute's fixed value does not match declaration's fixed value</b>
<b>Explanation</b>	If the attribute declaration has a fixed value constraint, then if the attribute use itself has a value constraint, it must also be fixed and its value must match that of the attribute declaration's value constraint.
<b>Action</b>	Please modify your XML schema accordingly.
<b>INOXDE7508</b>	<b>(sch-props-correct.2) name conflict with global declarations</b>
<b>Explanation</b>	Each of the type definitions, element declarations, attribute group definitions, model group definitions and notation declarations must not contain two or more schema components with the same name.
<b>Action</b>	Please modify your XML schema accordingly.

---

<b>INOXDE7509</b>	<b>invalid type of default value</b>
<b>Explanation</b>	If the type definition is a simple type definition, then the string must be valid with respect to that definition.
<b>Action</b>	Please modify your XML schema accordingly.
<b>INOXDE7510</b>	<b>content type is neither a simple type definition nor mixed</b>
<b>Explanation</b>	If an element declaration specifies a default value and the type definition is a complex type definition, then its content type must be a simple type definition or mixed.
<b>Action</b>	Please modify your XML schema accordingly.
<b>INOXDE7511</b>	<b>element default value does not match type</b>
<b>Explanation</b>	If an element declaration specifies a default value and the type definition is a complex type definition and its content type is a simple type definition, then the default value must be of declared type.
<b>Action</b>	Please modify your XML schema accordingly.
<b>INOXDE7512</b>	<b>content type does not allow for default value</b>
<b>Explanation</b>	If an element declaration specifies a default value and the type definition is a complex type definition and its content type is mixed, then the content type's particle must be emptyable.
<b>Action</b>	Please modify your XML schema accordingly.
<b>INOXDE7513</b>	<b>missing name in type definition</b>
<b>Explanation</b>	If the particles contain, either directly, indirectly or implicitly two or more element declaration particles with the same name, then all their type definitions must be the same top-level definitions.
<b>Action</b>	Please modify your XML schema accordingly.
<b>INOXDE7514</b>	<b>type definitions have different names</b>
<b>Explanation</b>	If the particles contain, either directly, indirectly or implicitly two or more element declaration particles with the same name, then all their type definitions must be the same top-level definitions.
<b>Action</b>	Please modify your XML schema accordingly.

<b>INOXDE7515</b>	<b>type definitions have different namespaces</b>
<b>Explanation</b>	If the particles contain, either directly, indirectly or implicitly two or more element declaration particles with the same name, then all their type definitions must be the same top-level definitions.
<b>Action</b>	Please modify your XML schema accordingly.
<b>INOXDE7516</b>	<b>(no-xmlns) attribute name not allowed</b>
<b>Explanation</b>	The name of an attribute declaration must not match xmlns.
<b>Action</b>	Use the targetNamespace attribute of the schema's root node in order to associate the current schema and objects defined therein with a namespace URI. The import element can be used to compose schemas defining objects for different namespaces.
<b>INOXDE7517</b>	<b>Below Attribute there may be only attributeInfo node but no schemaInfo or elementInfo nodes</b>
<b>Explanation</b>	Below Attribute there may be only attributeInfo node but no schemaInfo or elementInfo nodes.
<b>Action</b>	Please modify your XML schema accordingly.
<b>INOXDE7518</b>	<b>(enumeration-valid-restriction) value of enumeration does not match base type definition</b>
<b>Explanation</b>	The value attribute of an enumeration item must match the definition of the restriction's base type.
<b>Action</b>	Adapt your schema.
<b>INOXDE7519</b>	<b>(notation-defined-restriction) value of enumeration is not defined in a global notation element.</b>
<b>Explanation</b>	An enumeration value being used in a type derived from NOTATION must be defined in a global notation element.
<b>Action</b>	Adapt your schema.
<b>INOXDE7520</b>	<b>invalid index</b>
<b>Explanation</b>	It is not possible to define indices on elements or attributes with type "xs:long", "xs:unsignedLong" or "xs:decimal".
<b>Action</b>	Please modify your XML schema accordingly.

---

<b>INOXDE7521</b>	<b>invalid text index</b>
<b>Explanation</b>	It is not possible to define text indices on elements or attributes with numeric types.
<b>Action</b>	Please modify your XML schema accordingly.
<b>INOXDE7522</b>	<b>The element pointed to by tsd:refers needs to have a reference index defined for it</b>
<b>Explanation</b>	(mp-valid-refers.5:) The element pointed to by tsd:refers needs to have a reference index defined for it.
<b>Action</b>	Please modify the schema to include a reference index on the element pointed to by tsd:refers and try to define the schema again.
<b>INOXDE7523</b>	<b>Collations can only be defined for string datatypes (derived types of string in W3C XML schema part 2)</b>
<b>Explanation</b>	Collations can only be defined for string datatypes (derived types of string in W3C XML schema part 2).
<b>Action</b>	Please modify your XML schema accordingly.
<b>INOXDE7524</b>	<b>(src-single-facet-value) Facet is only permitted to be defined once</b>
<b>Explanation</b>	A facet has been specified more than once. This facet is only permitted to be defined once.
<b>Action</b>	Please modify the XML Schema accordingly.
<b>INOXDE7525</b>	<b>(cos-element-consistent) Element declarations are not consistent</b>
<b>Explanation</b>	If the particles contain, either directly, indirectly or implicitly two or more element declaration particles with the same name, then all their type definitions must be the same top-level definitions.
<b>Action</b>	Please modify your XML schema accordingly.
<b>INOXDE7526</b>	<b>(maxInclusive-maxExclusive) 'maxInclusive' and 'maxExclusive' facets cannot be used together</b>
<b>Explanation</b>	A simple type restriction, containing both 'maxInclusive' and 'maxExclusive' facets, has been found.
<b>Action</b>	Remove either of the 'maxInclusive' or 'maxExclusive' facets.

<b>INOXDE7527</b>	<b>(minInclusive-minExclusive) 'minInclusive' and 'minExclusive' facets cannot be used together</b>
<b>Explanation</b>	A simple type restriction, containing both 'minInclusive' and 'minExclusive' facets, has been found.
<b>Action</b>	Remove either of the 'minInclusive' or 'minExclusive' facets.
<b>INOXDE7528</b>	<b>Node declarations are not consistent</b>
<b>Explanation</b>	The schema violates a constraint which is a Tamino-specific extension of the (cos-element-consistent) constraint as imposed by XML schema: If there are two attribute or element declarations in the set of complex type definitions being allowed for a given element node due to usage of the xsi:type attribute, then these attributes (or elements) must be consistent. Consistency requirements cover the datatype as well as physical properties (mapping, indexing,...), or logical properties (collation, trigger, ...).
<b>Action</b>	Modify the schema to avoid violation of the constraint. For example it may help to use the 'block' attribute of <xs:element> or <xs:complexType> , or the 'blockDefault' attribute of <xs:schema> in order to control the {prohibited substitutions} with respect to xsi:type. In particular, you may use blockDefault="#all" if you do not need to allow for usage of the xsi:type attribute in your XML documents.
<b>INOXDE7529</b>	<b>(src-resolve.1.1) Global type reference could not be resolved</b>
<b>Explanation</b>	Reference to a global complex or simple type definition could not be resolved.
<b>Action</b>	Check the names of the global type definition and the associated reference.
<b>INOXDE7530</b>	<b>(src-resolve.1.2) The ref attribute of an attribute needs to reference an existing global attribute</b>
<b>Explanation</b>	An attribute defined in the schema uses the 'ref' attribute, however the global attribute with that name cannot be found.
<b>Action</b>	Check that the global attribute is not missing. Also check that the global attribute name and reference have been correctly specified.
<b>INOXDE7531</b>	<b>(minLength-less-than-equal-to-maxLength) 'minLength' facet value must be 'less than or equal to' that of facet 'maxLength'</b>
<b>Explanation</b>	A simple type restriction, where the value of facet 'minLength' is greater than that of 'maxLength', has been found.
<b>Action</b>	Revise the facet values.

<b>INOXDE7532</b>	<b>Invalid pattern facet value found</b>
<b>Explanation</b>	The schema being defined contains a pattern facet which has an invalid value.
<b>Action</b>	Check the schema and consider revising the pattern facet's value.
<b>INOXDE7533</b>	<b>Below Schema there needs to be exactly one appinfo node which defines Tamino mappings</b>
<b>Explanation</b>	Below Schema there needs to be exactly one appinfo node which defines Tamino mappings.
<b>Action</b>	Modify the XML schema accordingly.
<b>INOXDE7534</b>	<b>(src-import.1.1) Invalid import element. If the namespace attribute is present, then its value must not match the value of the enclosing schema's targetNamespace attribute.</b>
<b>Explanation</b>	The schema being defined contains an import element. The namespace attribute is present and its value is the same as the targetNamespace of the enclosing schema. This is not allowed.
<b>Action</b>	Revise either the namespace attribute of the import element or the targetNamespace of the schema.
<b>INOXDE7535</b>	<b>(src-import.1.2) Invalid import element. If the namespace attribute is not present, then the enclosing schema must have a targetNamespace attribute.</b>
<b>Explanation</b>	The schema being defined contains an import element. The namespace attribute is not present and the enclosing schema does not specify a targetNamespace. This is disallowed.
<b>Action</b>	Revise the import element and/or the schema element.
<b>INOXDE7536</b>	<b>(src-import.2) Invalid import element. Schema reference could not be resolved.</b>
<b>Explanation</b>	The schema being defined contains an import element. The schema referenced using either a schemaLocation or namespace attribute could not be located.
<b>Action</b>	If referencing using schemaLocation, check the name of the referenced schema (and optionally the collection name also). If referencing using namespace alone, check the targetNamespace of the referenced schema.
<b>INOXDE7537</b>	<b>(src-import.3.1) Invalid import element. If there is a namespace attribute, then its value must be identical to the value of the targetNamespace attribute of the referenced schema.</b>
<b>Explanation</b>	The schema being defined contains an import element. The namespace attribute is different from the targetNamespace of the referenced schema. This is not allowed.
<b>Action</b>	Revise either the namespace attribute of the import element or the targetNamespace of the referenced schema.

**INOXDE7538** (src-import.3.2) **Invalid import element. If there is no namespace attribute, then the referenced schema must have no targetNamespace attribute.**

**Explanation** The schema being defined contains an import element. The namespace attribute is not present, but the referenced schema specifies a targetNamespace. This is not allowed.

**Action** Revise the import element and/or the referenced schema element.

**INOXDE7539** **The value of schema attribute targetNamespace is not allowed if another schema in the same database already imports the corresponding namespace using only the namespace attribute of the import element**

**Explanation** The value of the targetNamespace attribute of the schema that you are trying to define is not allowed. This is because another schema in the same database already imports that namespace, using an import element with namespace alone.

**Action** Revise the schema and/or the other schema importing that namespace. Either change the targetNamespace of the current schema, or change the import element of the referencing schema to also use the schemaLocation attribute.

**INOXDE7540** **Found node with a mapped value which is used to construct index entries**

**Explanation** A node with a mapped value must not be used to construct index entries. This restriction applies for text and standard as well as for the components of a compound index referring to an ancestor of the current node.

**Action** Remove index definition causing this conflict.

**INOXDE7541** **Undefine of schema failed. Schema to be undefined is referenced by other schema(s) in the database.**

**Explanation** The undefine of a specific schema was performed. Other schema(s) in the database still reference this schema.

**Action** Before the schema can be undefined, you must first undefine all referencing schemas.

**INOXDE7542** **Attribute targetNamespace of element schema, if present, must not be empty.**

**Explanation** The schema being defined specifies an empty targetNamespace attribute.

**Action** Revise the schema. Either provide the targetNamespace attribute with a value, or completely remove it.

---

<b>INOXDE7543</b>	<b>Import using namespace attribute alone is forbidden, if more than one schema with the corresponding targetNamespace is already stored in the current database</b>
<b>Explanation</b>	The schema being defined contains an import element with only a namespace attribute. More than one schema stored in the current database already contains a corresponding targetNamespace attribute.
<b>Action</b>	Revise the schema and/or other schemas stored inside the current database. Consider using the schemaLocation attribute of import to clarify exactly which schema was intended.
<b>INOXDE7544</b>	<b>An import element must have attributes</b>
<b>Explanation</b>	The schema being defined specifies an import element without attributes.
<b>Action</b>	Revise the schema. Add either namespace or schemaLocation attributes to the import element, or remove it and consider using Tamino's content element with value open.
<b>INOXDE7545</b>	<b>Cannot define standard index or unique constraint based on a node whose associated datatype has a variety of 'union'</b>
<b>Explanation</b>	It is not supported to define an index or unique constraint based on a node whose datatype has a variety of 'union' or which is derived via <xs:list> with an item type whose variety is 'union'.
<b>Action</b>	Modify the schema accordingly.
<b>INOXDE7546</b>	<b>An element defined as a primary key cannot be defined as nillable</b>
<b>Explanation</b>	An element which is defined as a primary key value cannot be defined as nillable.
<b>Action</b>	Revise the schema. Either remove the xsi:nillable attribute or set the value to false.
<b>INOXDE7547</b>	<b>Undefine of collection failed. One or more schemas contained inside the collection to be undefined are referenced by other schema(s), from other collection(s) in the current database.</b>
<b>Explanation</b>	The undefine of a specific collection was performed. Other schema(s) from other collection(s) in the database still reference one or more schemas contained inside the collection to be undefined.
<b>Action</b>	Before the collection can be undefined, you must first undefine all referencing schemas.
<b>INOXDE7548</b>	<b>Cannot define standard index or unique constraint based on this element node with complex content if there is a validly derived complex type with simple content which can be used in an xsi:type attribute on that element node</b>
<b>Explanation</b>	It is not allowed to define a standard index or unique constraint based on an element node whose associated datatype is a complex type with complex content if there is another complex type with simple content which can be validly used in an xsi:type attribute on that element node.

<b>Action</b>	Either remove the index definition or modify type definitions to avoid violation of this constraint.
<b>INOXDE7549</b>	<b>Mapping not allowed for datatype of variety</b>
<b>Explanation</b>	Mapping (ADABAS, SQL and SXS) is not allowed for datatypes derived via xs:list or xs:union.
<b>Action</b>	Please change the datatype and try to define the schema again.
<b>INOXDE7550</b>	<b>ElementInfo node is not allowed with a schema reference to a global element definition</b>
<b>Explanation</b>	Below Element an elementInfo node is only allowed if the element node starts an element definition. An elementInfo is not allowed with a reference to a global element definition.
<b>Action</b>	Please modify your XML schema accordingly.
<b>INOXDE7551</b>	<b>AttributeInfo node is not allowed with a schema reference to a global attribute definition</b>
<b>Explanation</b>	Below Attribute an attributeInfo node is only allowed if the attribute node starts an attribute definition. An attributeInfo is not allowed with a reference to a global attribute definition.
<b>Action</b>	Please modify your XML schema accordingly.
<b>INOXDE7552</b>	<b>The path contains invalid expressions</b>
<b>Explanation</b>	The path can only consists of named child steps with abbreviated XPath syntax. In particular, it cannot contain *, .., // operators.
<b>Action</b>	Modify the XML schema accordingly.
<b>INOXDE7553</b>	<b>The index types of elements and attributes having the same multipath index label must be identical</b>
<b>Explanation</b>	The index types of elements and attributes having the same multipath index label must be identical.
<b>Action</b>	Please change the schema so that multipath definitions with the same label are only used when the index types are identical and then try to define the schema again.

---

<b>INOXDE7554</b>	<b>(src-attribute-group.2) Intentional intersection of namespace constraints is not expressible</b>
<b>Explanation</b>	This may happen e.g. if two attribute wildcards are to be merged due to resolution of a reference to an attributeGroup definition. If those two attribute wildcards both have a namespace constraint ##other, thus referring to different target namespaces, the intentional intersection is not expressible.
<b>Action</b>	Adapt the schema according to XML schema constraint src-attribute-group.2
<b>INOXDE7555</b>	<b>The name attribute of tsd:unique definitions has to be unique within a doctype</b>
<b>Explanation</b>	The name attribute of tsd:unique definitions has to be unique within a doctype.
<b>Action</b>	Please change the duplicate name and try to define the schema again.
<b>INOXDE7556</b>	<b>The elements and attributes pointed to in tsd:unique definitions must have a cardinality of 1</b>
<b>Explanation</b>	The elements and attributes pointed to in tsd:unique definitions must have a cardinality of 1.
<b>Action</b>	Please change the cardinality and try to define the schema again.
<b>INOXDE7557</b>	<b>The path specified the xpath attribute of a field element needs to point to an existing element or attribute</b>
<b>Explanation</b>	The path specified the xpath attribute of a field element needs to point to an existing element or attribute.
<b>Action</b>	Please make sure the specified path is correct and try to define the schema again.
<b>INOXDE7558</b>	<b>multipath index definitions are not allowed in doctypes which have the structureIndex set to none</b>
<b>Explanation</b>	Multipath index definitions are not allowed in doctypes which have the structureIndex set to none.
<b>Action</b>	Please change the structure index to condensed or full and try to define the schema again.
<b>INOXDE7559</b>	<b>The elements and attributes having the same multipath index label must have matching datatypes</b>
<b>Explanation</b>	The elements and attributes having the same multipath index label must have matching datatypes.
<b>Action</b>	Please change the wrong datatype and try to define the schema again.

<b>INOXDE7560</b>	<b>The elements and attributes having the same multipath index label must have matching collations</b>
<b>Explanation</b>	The elements and attributes having the same multipath index label must have matching collations.
<b>Action</b>	Please change the wrong collation and try to define the schema again.
<b>INOXDE7561</b>	<b>The elements and attributes having the same multipath index label must have matching tsd:refers definitions</b>
<b>Explanation</b>	The elements and attributes having the same multipath index label must have matching tsd:refers definitions.
<b>Action</b>	Please change the wrong tsd:refers definition and try to define the schema again.
<b>INOXDE7562</b>	<b>The path defined in tsd:refers has to point to an existing element</b>
<b>Explanation</b>	The path defined in tsd:refers has to point to an existing element.
<b>Action</b>	Please change the path and try to define the schema again.
<b>INOXDE7563</b>	<b>The path defined in tsd:refers has to point to an element which is a predecessor of the element or attribute where it is defined</b>
<b>Explanation</b>	The path defined in tsd:refers has to point to an element which is a predecessor of the element or attribute where it is defined.
<b>Action</b>	Please change the path and try to define the schema again.
<b>INOXDE7564</b>	<b>The path defined in tsd:refers may only point to elements that are locally stored in a Tamino database</b>
<b>Explanation</b>	The path defined in tsd:refers may only point to elements that are locally stored in a Tamino database.
<b>Action</b>	Please change the path and try to define the schema again.
<b>INOXDE7565</b>	<b>The path defined in tsd:refers must point either to the doctype element or to an element for which a tsd:reference is defined</b>
<b>Explanation</b>	The path defined in tsd:refers must point either to the doctype element or to an element for which a tsd:reference is defined.
<b>Action</b>	Please change the path and try to define the schema again.

---

<b>INOXDE7566</b>	<b>The path specified in the xpath attribute of a field element needs to point to an element or attribute that is locally stored in a Tamino database</b>
<b>Explanation</b>	The path specified in the xpath attribute of a field element needs to point to an element or attribute that is locally stored in a Tamino database.
<b>Action</b>	Please change the path and try to define the schema again.
<b>INOXDE7567</b>	<b>The path specified in the xpath attribute of a field element of a compound index definition needs to point to a leaf node (an attribute or element having no children)</b>
<b>Explanation</b>	The path specified in the xpath attribute of a field element of a compound index definition needs to point to a leaf node (an attribute or element having no children).
<b>Action</b>	Please change the path and try to define the schema again.
<b>INOXDE7568</b>	<b>For a uniqueness constraint a certain path may only be defined once</b>
<b>Explanation</b>	For a uniqueness constraint a certain path may only be defined once.
<b>Action</b>	Please change the path and try to define the schema again.
<b>INOXDE7569</b>	<b>A reference index may not be defined for a doctype element</b>
<b>Explanation</b>	A reference index may not be defined for a doctype element.
<b>Action</b>	Please change the reference index value and try to define the schema again.
<b>INOXDE7570</b>	<b>There may only be one tsd:reference index definition per tsd:physical</b>
<b>Explanation</b>	There may only be one tsd:reference index definition per tsd:physical.
<b>Action</b>	Please make sure there is only one tsd:reference index definition per tsd:physical and try to define the schema again.
<b>INOXDE7571</b>	<b>If an index has been defined as a multipath index, there may not be a tsd:refers defined for that same index</b>
<b>Explanation</b>	If an index has been defined as a multipath index, there may not be a tsd:refers defined for that same index.
<b>Action</b>	Please remove either the multipath definition or the tsd:refers and try to define the schema again.

<b>INOXDE7572</b>	<b>For a compound index a certain path may only be defined once</b>
<b>Explanation</b>	For a compound index a certain path may only be defined once.
<b>Action</b>	Please change the schema and try to define it again.
<b>INOXDE7573</b>	<b>(src-resolve.1.4) Reference to an attribute group definition could not be resolved</b>
<b>Explanation</b>	Reference to an attribute group definition could not be resolved.
<b>Action</b>	Check the qualified names of the attribute group definition and the reference.
<b>INOXDE7574</b>	<b>(src-resolve.1.5) Reference to a model group definition could not be resolved</b>
<b>Explanation</b>	Reference to a model group definition could not be resolved.
<b>Action</b>	Check the qualified names of the model group definition and the reference.
<b>INOXDE7575</b>	<b>(src-attribute-group.3) Circular attribute group reference is disallowed</b>
<b>Explanation</b>	A cycle of attribute group references has been found.
<b>Action</b>	Check the attribute group references and remove the circular reference.
<b>INOXDE7576</b>	<b>(mg-props-correct.2) Circular group reference is disallowed</b>
<b>Explanation</b>	Within the particles of a group there must not be at any depth a reference to the group itself.
<b>Action</b>	Check group definition and remove circular reference inside.
<b>INOXDE7577</b>	<b>(src-include.2.1) Target namespace of the including and the included schema do not match.</b>
<b>Explanation</b>	The values of the targetNamespace attributes of the including and the included schema may not differ if both are present.
<b>Action</b>	Check targetNamespace attributes.
<b>INOXDE7578</b>	<b>(src-include.2.2) Included schema has target namespace whereas including has no target namespace.</b>
<b>Explanation</b>	If the including schema has no targetNamespace attribute, the included schema must not have a targetNamespace attribute as well.
<b>Action</b>	Check and adapt the schema documents.

---

<b>INOXDE7579</b>	<b>(src-include.2.3) Target namespace of included schema missing. Tamino does not yet support "chameleon include".</b>
<b>Explanation</b>	This is a current limitation of Tamino.
<b>Action</b>	Define the included schema using the same targetNamespace attribute as the including schema's targetNamespace.
<b>INOXDE7580</b>	<b>(src-include.1) Invalid include element. Schema reference could not be resolved.</b>
<b>Explanation</b>	The schema being defined contains an include element. The schema referenced by the schemaLocation attribute could not be located.
<b>Action</b>	Check the name of the referenced schema and, optionally, the collection name as well.
<b>INOXDE7581</b>	<b>invalid collation language</b>
<b>Explanation</b>	The specified language string is not valid.
<b>Action</b>	Please change the wrong collation language string and try to define the schema again.
<b>INOXDE7583</b>	<b>Invalid open content found in pure X-Node mapped doctype</b>
<b>Explanation</b>	For pure X-Node mapping, no open content is allowed for that doctype. This includes wildcards with processContents being "strict" or "lax" and element nodes with type "xs:anyType" or no type at all.
<b>Action</b>	Ensure that the doctype with the pure X-Node mapping is set to closed content, that any of the doctype's wildcards (xs:any and xs:anyAttribute) in scope have processContents set to "strict", and that all elements in scope have a non-absent type specification different from "xs:anyType".
<b>INOXDE7584</b>	<b>Invalid mixed content found in complex type within a pure X-Node mapped doctype</b>
<b>Explanation</b>	Elements in a pure X-Node mapped doctype must not have a mixed content model.
<b>Action</b>	Set the mixed attribute of the corresponding complex type definition to "false".
<b>INOXDE7585</b>	<b>Invalid mapping found in root element of pure X-Node mapped doctype</b>
<b>Explanation</b>	Currently, only Adabas mapping is allowed for the root node of a pure X-Node mapped doctype.
<b>Action</b>	Check the mapping of the root element.

<b>INOXDE7586</b>	<b>Invalid mapping found in non-root node within pure X-Node mapped doctype</b>
<b>Explanation</b>	All leaf nodes must be mapped corresponding to the mapping type of the root element, e.g. to Adabas fields if the root node is mapped to an Adabas file.
<b>Action</b>	Check the mapping of the node.
<b>INOXDE7587</b>	<b>Found invalid recursion in pure X-Node mapped doctype</b>
<b>Explanation</b>	Within a pure X-Node mapped doctype no recursive structures are permitted.
<b>Action</b>	Remove the recursion.
<b>INOXDE7588</b>	<b>Found empty leaf node in pure X-Node mapped doctype</b>
<b>Explanation</b>	A pure X-Node mapped doctype must not contain empty leaf nodes.
<b>Action</b>	Either remove the node or map to an X-Node data item, i.e. either an Adabas field or an SQL column.
<b>INOXDE7589</b>	<b>Reference index definitions are not allowed in doctypes which have the structureIndex set to none</b>
<b>Explanation</b>	Reference index definitions are not allowed in doctypes which have the structureIndex set to none.
<b>Action</b>	Please correct the schema and try to define it again.
<b>INOXDE7590</b>	<b>Unique index constraints may not be defined on elements or attributes on node of given type</b>
<b>Explanation</b>	Unique index constraints may not be defined on elements or attributes of xs:duration or any data type allowing for an optional timezone indicator, e.g. xs:dateTime.
<b>Action</b>	Please correct the schema and try to define it again.
<b>INOXDE7591</b>	<b>Found xs:include or xs:import referencing current schema</b>
<b>Explanation</b>	An xs:include or xs:import must not reference the current schema.
<b>Action</b>	Adapt the schema.
<b>INOXDE7592</b>	<b>Invalid level of structure index for pure X-Node mapped doctype</b>
<b>Explanation</b>	A pure X-Node mapped doctype must not have a full structure index.
<b>Action</b>	Set the structure index to 'condensed' or 'none'.

<b>INOXDE7593</b>	<b>A default function has been defined at an element node with a complex type</b>
<b>Explanation</b>	A default function may only be defined at a node with a simple type.
<b>Action</b>	Modify the schema in an appropriate way.
<b>INOXDE7594</b>	<b>Default function defined for required attribute node</b>
<b>Explanation</b>	If a default function is defined for an attribute, the attribute must be optional.
<b>Action</b>	Check and adapt schema in an appropriate way.
<b>INOXDE7595</b>	<b>Default function defined for a node which has a value constraint</b>
<b>Explanation</b>	An element or attribute node may define either a default function or a value constraint (i.e. a default or fixed value) but not both.
<b>Action</b>	Adapt the schema correspondingly.
<b>INOXDE7596</b>	<b>Too many tsd:elementInfo or tsd:attributeInfo nodes</b>
<b>Explanation</b>	There may be only one tsd:elementInfo or tsd:attributeInfo node per xs:element or xs:attribute node.
<b>Action</b>	Modify the schema accordingly.
<b>INOXDE7597</b>	<b>(src-list-itemType-or-simpleType) Definition of simple type via &lt;xs:list&gt; contains both 'itemType' attribute and &lt;xs:simpleType&gt; child.</b>
<b>Explanation</b>	Either the 'itemType' attribute or the <xs:simpleType> child of the <xs:list> element must be present, but not both.
<b>Action</b>	Remove either the 'itemType' attribute or the <xs:simpleType> child.
<b>INOXDE7598</b>	<b>(src-restriction-base-or-simpleType) Definition of simple type via &lt;xs:restriction&gt; must contain either 'base' attribute or &lt;xs:simpleType&gt; child.</b>
<b>Explanation</b>	Either the 'base' attribute or the <xs:simpleType> child of the <xs:restriction> element must be present, but not both.
<b>Action</b>	Remove either 'base' attribute or the <xs:simpleType> child.
<b>INOXDE7599</b>	<b>(src-union-memberTypes-or-simpleTypes) The 'memberTypes' attribute of the &lt;xs:union&gt; element is empty and there is no &lt;xs:simpleType&gt; child.</b>
<b>Explanation</b>	Either the 'memberTypes' attribute of the <xs:union> element must be non-empty or there must be at least one <xs:simpleType> child.
<b>Action</b>	Add either the 'memberTypes' attribute of the <xs:union> element or at least one <xs:simpleType> child.

<b>INOXDE7614</b>	<b>The noConversion option may only be changed for empty doctypes</b>
<b>Explanation</b>	Changing the noConversion option could make the existing data in the doctype invalid, so this option may only be modified for empty doctypes.
<b>Action</b>	Adapt the schema so that the noConversion option is not changed or make sure there are no documents stored in the doctype for which you are trying to modify the schema.
<b>INOXDE7619</b>	<b>Invalid type of parameter for server extension</b>
<b>Explanation</b>	The type of the parameter is invalid in the current context.
<b>Action</b>	Check and modify the type of parameter to be passed to the server extension function. for example, parameters being passed to a trigger function may only have a simple predefined type.
<b>INOXDE7620</b>	<b>Invalid parameter value</b>
<b>Explanation</b>	The value of the parameter is not valid with respect to the declared type.
<b>Action</b>	Modify the type or value in order to create a consistent parameter definition.
<b>INOXDE7621</b>	<b>(cos-st-restricts.1.1) Invalid base type definition of simple type</b>
<b>Explanation</b>	The base type definition must be an atomic simple type definition or a built-in primitive datatype.
<b>Action</b>	Adapt the type definitions or type hierarchy.
<b>INOXDE7622</b>	<b>(cos-st-restricts.1.2) Invalid base type of simple type definition - the 'final' attribute does not permit derivation of another simple type</b>
<b>Explanation</b>	The {final} of the {base type definition} of a simple type definition must not contain restriction.
<b>Action</b>	Adapt the schema according to the constraint.
<b>INOXDE7623</b>	<b>(cos-st-restricts.2.1) Invalid item type definition of simple type derived via &lt;xs:list&gt;</b>
<b>Explanation</b>	The {item type definition} must have a {variety} of atomic or union (in which case all the {member type definitions} must be atomic).
<b>Action</b>	Adapt the schema according to the constraint.

---

<b>INOXDE7624</b>	<b>(cos-st-restricts.2.3.1.1) Invalid item type definition of simple type derived via &lt;xs:list&gt;</b>
<b>Explanation</b>	The {final} of the {item type definition} must not contain list.
<b>Action</b>	Adapt the schema according to the constraint.
<b>INOXDE7625</b>	<b>(cos-st-restricts.3.3.2.2) Invalid base type for simple type derived via &lt;xs:restriction&gt;</b>
<b>Explanation</b>	The {final} of the {base type definition} must not contain restriction.
<b>Action</b>	Adapt the schema according to the constraint.
<b>INOXDE7626</b>	<b>(cos-st-restricts.2.3.2.2) Invalid base type for simple type derived via &lt;xs:restriction&gt;</b>
<b>Explanation</b>	The {final} of the {base type definition} must not contain restriction.
<b>Action</b>	Adapt the schema according to the constraint.
<b>INOXDE7627</b>	<b>(cos-st-restricts.2.3.2.4) Invalid facet for simple type derived via &lt;xs:list&gt;</b>
<b>Explanation</b>	Only length, minLength, maxLength, whiteSpace, pattern and enumeration facet components are allowed among the {facets}.
<b>Action</b>	Adapt the schema according to the constraint.
<b>INOXDE7628</b>	<b>(cos-st-restricts.3.1) Invalid member type definition for simple type derived via &lt;xs:union&gt;</b>
<b>Explanation</b>	The {member type definitions} must all have {variety} of atomic or list.
<b>Action</b>	Adapt the schema according to the constraint.
<b>INOXDE7629</b>	<b>(cos-st-restricts.3.3.1.1) Invalid member type definition for simple type derived via &lt;xs:union&gt;</b>
<b>Explanation</b>	All of the {member type definitions} must have a {final} which does not contain union.
<b>Action</b>	Adapt the schema according to the constraint.
<b>INOXDE7630</b>	<b>(cos-st-restricts.3.3.2.4) Invalid facet for simple type derived via &lt;xs:union&gt;</b>
<b>Explanation</b>	Only pattern and enumeration facet components are allowed among the {facets}.
<b>Action</b>	Adapt the schema according to the constraint.

<b>INOXDE7631</b>	<b>(a-props-correct.1) Invalid type of attribute declaration - must be a simple type</b>
<b>Explanation</b>	The type definition of an attribute declaration must be a simple type.
<b>Action</b>	Modify the type definition of the attribute declaration.
<b>INOXDE7632</b>	<b>(st-props-correct.2) Invalid or circular type hierarchy of simple type definition</b>
<b>Explanation</b>	All simple type definitions must be derived ultimately from the simple ur-type definition - circular definitions are disallowed.
<b>Action</b>	Adapt the schema according to the constraint.
<b>INOXDE7633</b>	<b>(ct-props-correct.2) Invalid derivation of complex type with simple base type definition</b>
<b>Explanation</b>	If the {base type definition} is a simple type definition, the {derivation method} must be extension.
<b>Action</b>	Adapt the schema according to the constraint.
<b>INOXDE7634</b>	<b>(ct-props-correct.3) Invalid or circular type hierarchy of complex type definition</b>
<b>Explanation</b>	Circular definitions are disallowed, except for the ur-type definition. That is, it must be possible to reach the ur-type definition by repeatedly following the {base type definition}.
<b>Action</b>	Adapt the schema according to the constraint.
<b>INOXDE7635</b>	<b>(no-xsi) Invalid attribute declaration for targetNamespace</b>
<b>Explanation</b>	The {target namespace} of an attribute declaration, whether local or top-level, must not match <a href="http://www.w3.org/2001/XMLSchema-instance">http://www.w3.org/2001/XMLSchema-instance</a> , unless it is one of the four built-in declarations for <code>xsi:type</code> , <code>xsi:nil</code> , <code>xsi:schemaLocation</code> , <code>xsi:noNamespaceSchemaLocation</code> .
<b>Action</b>	Adapt the schema according to constraint. See XML Schema Part 1 for a valid declaration of the four built-in declarations.
<b>INOXDE7636</b>	<b>(src-ct.1) Invalid base type definition of complex type with complex content</b>
<b>Explanation</b>	If the <code>&lt;complexContent&gt;</code> alternative is chosen, the type definition resolved to by the actual value of the 'base' attribute must be a complex type definition.
<b>Action</b>	Adapt the schema according to the constraint.

<b>INOXDE7637</b>	<b>(src-ct.2.1) Invalid base type definition of complex type simple content</b>
<b>Explanation</b>	The type definition resolved to by the actual value of the 'base' attribute must be one of the following: (1) a complex type definition whose {content type} is a simple type definition; (2) only if the <restriction> alternative is also chosen, a complex type definition whose {content type} is mixed and a particle which is emptiable.
<b>Action</b>	Adapt the schema according to the constraint.
<b>INOXDE7638</b>	<b>(src-ct.2.2) Missing &lt;xs:simpleType&gt; below &lt;xs:restriction&gt; for a complex type with simple content which is derived from a complex type via restriction</b>
<b>Explanation</b>	If the <simpleContent>/<restriction> alternative is chosen with the 'base' attribute resolving to a complex type definition whose {content type} is mixed and a particle which is emptiable, there must be a <simpleType> among the [children] of <restriction>.
<b>Action</b>	Adapt the schema according to the constraint.
<b>INOXDE7639</b>	<b>(cos-ct-extends.1.1) Invalid base type of complex type derived via &lt;xs:extension&gt;</b>
<b>Explanation</b>	The {final} of the {base type definition} must not contain extension.
<b>Action</b>	Adapt the schema according to the constraint.
<b>INOXDE7640</b>	<b>(cos-ct-extends.1.4.1) Simple content types of complex type derived via &lt;xs:extension&gt; and the respective base type definition do not match</b>
<b>Explanation</b>	The {content type} of the {base type definition} and the {content type} of the complex type definition itself must be the same simple type definition.
<b>Action</b>	Adapt the schema according to the constraint.
<b>INOXDE7641</b>	<b>(cos-ct-extends.1.4.2) If the content type of a complex type derived via &lt;xs:extension&gt; is empty, the content type of the respective complex base type definition must be empty as well</b>
<b>Explanation</b>	The {content type} of both the {base type definition} and the complex type definition itself must be empty.
<b>Action</b>	Adapt the schema according to the constraint.
<b>INOXDE7642</b>	<b>(cos-ct-extends.1.4.3.1) Invalid content type of a complex type definition derived via &lt;xs:extension&gt; given the content type of the complex base type definition</b>
<b>Explanation</b>	The {content type} of the complex type definition itself must specify a particle.
<b>Action</b>	Adapt the schema according to the constraint.

<b>INOXDE7643</b>	<b>(cos-ct-extends.1.4.3.2.2.1) Invalid content type of complex type definition derived via &lt;xs:extension&gt; from complex type definition</b>
<b>Explanation</b>	Both {content type}s must be mixed or both must be element-only.
<b>Action</b>	Adapt the schema according to the constraint.
<b>INOXDE7644</b>	<b>(cos-ct-extends.2.2) Invalid base type of complex type definition derived via &lt;xs:extension&gt;</b>
<b>Explanation</b>	The {final} of the {base type definition} must not contain extension.
<b>Action</b>	Adapt the schema according to the constraint.
<b>INOXDE7645</b>	<b>(derivation-ok-restriction.1) Invalid base type definition of complex type derived via &lt;xs:restriction&gt;</b>
<b>Explanation</b>	The {base type definition} must be a complex type definition whose {final} does not contain restriction.
<b>Action</b>	Adapt the schema according to the constraint.
<b>INOXDE7646</b>	<b>(derivation-ok-restriction.2.1.1) Invalid value of 'use' attribute of attribute in complex type definition derived via &lt;xs:restriction&gt; compared to value of 'use' attribute for respective attribute in complex base type definition.</b>
<b>Explanation</b>	If there is an attribute use in the {attribute uses} of the {base type definition} (call this B) whose {attribute declaration} has the same {name} and {target namespace}, then one of the following must be true: (1) B's {required} is false. (2) the restricted type's {required} is true.
<b>Action</b>	Adapt the schema according to the constraint.
<b>INOXDE7647</b>	<b>(derivation-ok-restriction.2.1.2) Invalid type of attribute in complex type definition derived via &lt;xs:restriction&gt; compared to type of respective attribute in complex base type definition.</b>
<b>Explanation</b>	If there is an attribute use in the {attribute uses} of the {base type definition} (call this B) whose {attribute declaration} has the same {name} and {target namespace}, then the restricted type's {attribute declaration}'s {type definition} must be validly derived from B's {type definition}.
<b>Action</b>	Adapt the schema according to the constraint.

<b>INOXDE7648</b>	<b>(derivation-ok-restriction.2.1.3) Invalid value constraint of attribute in complex type definition derived via &lt;xs:restriction&gt; compared to value constraint of respective attribute in complex base type definition</b>
<b>Explanation</b>	If there is an attribute use in the {attribute uses} of the {base type definition} (call this B) whose {attribute declaration} has the same {name} and {target namespace}, then one of the following must be true: (1) B's effective value constraint is absent or default. (2) the restricted type's effective value constraint is fixed with the same string as B's.
<b>Action</b>	Adapt the schema according to the constraint.
<b>INOXDE7649</b>	<b>(derivation-ok-restriction.2.2) Invalid attribute use in complex type definition derived via &lt;xs:restriction&gt;, the complex base type definition neither contains a matching attribute use nor an attribute wildcard.</b>
<b>Explanation</b>	If there is no attribute use in the {attribute uses} of the {base type definition} (call this B) whose {attribute declaration} has the same {name} and {target namespace}, the {base type definition} must have an {attribute wildcard} and the {target namespace} of the restricted type's {attribute declaration} must be valid with respect to that wildcard.
<b>Action</b>	Adapt the schema according to the constraint.
<b>INOXDE7650</b>	<b>(derivation-ok-restriction.3) Invalid value of 'use' attribute of attribute in complex type definition derived via &lt;xs:restriction&gt; compared to value of 'use' attribute for respective attribute in complex base type definition</b>
<b>Explanation</b>	For each attribute use in the {attribute uses} of the {base type definition} whose {required} is true, there must be an attribute use with an {attribute declaration} with the same {name} and {target namespace} as its {attribute declaration} in the {attribute uses} of the complex type definition itself whose {required} is true.
<b>Action</b>	Adapt the schema according to the constraint.
<b>INOXDE7651</b>	<b>(derivation-ok-restriction.4.1) Invalid attribute wildcard in complex type definition derived via &lt;xs:restriction&gt;, complex base type definition does not have an attribute wildcard</b>
<b>Explanation</b>	If there is an {attribute wildcard}, the {base type definition} must also have one.
<b>Action</b>	Adapt the schema according to the constraint.
<b>INOXDE7652</b>	<b>(derivation-ok-restriction.4.2) Invalid attribute wildcard in complex type definition derived via &lt;xs:restriction&gt;, its namespace constraint is not a subset of the namespace constraint of the attribute wildcard in the complex base type definition</b>
<b>Explanation</b>	If there is an {attribute wildcard}, the complex type definition's {attribute wildcard}'s {namespace constraint} must be a subset of the {base type definition}'s {attribute wildcard}'s {namespace constraint}.
<b>Action</b>	Adapt the schema according to the constraint.

**INOXDE7653**      **(derivation-ok-restriction.4.3) Invalid 'processContents' of attribute wildcard in complex type definition derived via <xs:restriction> compared to 'processContents' of attribute wildcard in complex base type definition**

**Explanation**      If there is an {attribute wildcard}, and the {base type definition} is not the ur-type definition, the complex type definition's {attribute wildcard}'s {process contents} must be identical to or stronger than the {base type definition}'s {attribute wildcard}'s {process contents}, where strict is stronger than lax is stronger than skip.

**Action**      Adapt the schema according to the constraint.

**INOXDE7654**      **(derivation-ok-restriction.5.1.2) Invalid base type for complex type with simple content derived via <xs:restriction>**

**Explanation**      If the {content type} of the complex type definition is a simple type definition, one of the following must be true: (1) The {content type} of the {base type definition} must be a simple type definition from which the {content type} is validly derived (2) The {base type definition} must be mixed and have a particle which is emptiable

**Action**      Adapt the schema according to the constraint.

**INOXDE7655**      **(derivation-ok-restriction.5.2.2) Invalid base type for complex type with empty content derived via <xs:restriction>**

**Explanation**      If the {content type} of the complex type is empty, one of the following must be true: (1) The {content type} of the {base type definition} must also be empty. (2) The {content type} of the {base type definition} must be elementOnly or mixed and have a particle which is emptiable

**Action**      Adapt the schema according to the constraint.

**INOXDE7656**      **(derivation-ok-restriction.5.3.1) Invalid base type for complex type with neither simple nor empty content derived via <xs:restriction>**

**Explanation**      If the {content type} of the complex type definition is neither a simple type definition nor empty, one of the following must be true: (1) The {content type} of the complex type definition itself must be element-only (2) The {content type} of the complex type definition itself and of the {base type definition} must be mixed.

**Action**      Adapt the schema according to the constraint.

**INOXDE7657**      **(derivation-ok-restriction.5.3.2) The particle of the complex type derived via restriction does not satisfy the "Particle Valid (Restriction)" constraint with respect to the particle of the complex base type**

**Explanation**      If the {content type} of the complex type definition is neither a simple type definition nor empty, the particle of the complex type definition itself must be a valid restriction of the particle of the {content type} of the {base type definition}.

**Action**      Adapt the schema according to the constraint.

---

<b>INOXDE7658</b>	<b>An element's or attribute's shortname definition does not match Adabas field definition</b>
<b>Explanation</b>	A field with the given shortname does not exist in the Adabas file defined for this element.
<b>Action</b>	Adapt the schema to the corresponding Adabas field and file definitions.
<b>INOXDE7659</b>	<b>The element's or attribute's Adabas format definition does not match the Adabas field definition</b>
<b>Explanation</b>	The Adabas format definition cannot be converted to the format defined in the Adabas FDT.
<b>Action</b>	Adapt your schema to the corresponding Adabas field definitions.
<b>INOXDE7660</b>	<b>An element's periodic group definition does not match the Adabas field definition</b>
<b>Explanation</b>	The corresponding Adabas field is not defined as a periodic group in the Adabas FDT.
<b>Action</b>	Adapt your schema corresponding to the Adabas field definition
<b>INOXDE7661</b>	<b>An element's multiple field definition does not match the Adabas field definition</b>
<b>Explanation</b>	The corresponding Adabas field is not defined as multiple field in Adabas.
<b>Action</b>	Adapt your schema definition to the corresponding Adabas definitions.
<b>INOXDE7662</b>	<b>An element nillable definition does not match the Adabas field definition</b>
<b>Explanation</b>	The element defined as xsi:nil is not defined with NC (SQL NULL-Value Representation) -option in the Adabas FDT.
<b>Action</b>	Adapt the schema corresponding to the Adabas field definition.
<b>INOXDE7663</b>	<b>An element's or attribute's format definition xs:date does not match the Adabas field definition</b>
<b>Explanation</b>	An element defined as xs:date must be mapped to an ADABAS field with format P4.
<b>Action</b>	Adapt the schema to the corresponding Adabas definition.
<b>INOXDE7664</b>	<b>An element's or attribute's format definition xs:dateTime does not match the Adabas field definition</b>
<b>Explanation</b>	The element which is defined as xs:dateTime must be mapped to an Adabas field with format P7.
<b>Action</b>	Adapt the schema definition to the corresponding Adabas format.

<b>INOXDE7665</b>	<b>(c-props-correct.1) An &lt;xs:keyref&gt; refers to an unknown &lt;xs:key&gt;</b>
<b>Explanation</b>	The 'refer' attribute of <xs:keyref> must refer to a sibling node of type <xs:key> with a matching value of its 'name' attribute.
<b>Action</b>	Correct the schema document.
<b>INOXDE7666</b>	<b>(c-props-correct.2) Invalid cardinality of &lt;xs:field&gt; child nodes of &lt;xs:keyref&gt;</b>
<b>Explanation</b>	If the {identity-constraint category} is keyref, the cardinality of the {fields} must equal that of the {fields} of the {referenced key}.
<b>Action</b>	Correct the schema document.
<b>INOXDE7667</b>	<b>(e-props-correct.3) The 'substitutionGroup' resolves to an unknown or invalid global element declaration</b>
<b>Explanation</b>	The 'substitutionGroup' attribute of an element declaration, E1, must resolve to a global element, say E2, whose effective 'block' attribute, i.e. the substitution group exclusions do not contain the value "substitution". The {type definition} of E1 must be validly derived from the {type definition} of E2, using a derivation method not given in the effective 'block' attribute.
<b>Action</b>	Adapt the schema to match this constraint.
<b>INOXDE7668</b>	<b>(cos-equiv-derived-ok-rec.1) Invalid relation of types of current element and its substitution group affiliate</b>
<b>Explanation</b>	The derivation method of the type of the current element must be derived from the type of the substitution group affiliate's (i.e. the global element referenced by the 'substitutionGroup' attribute) type. The derivation method must be compatible with the substitution group exclusions defined by the 'block' attribute of the affiliate and the 'blockDefault' attribute of the respective schema node.
<b>Action</b>	Adapt schema to meet this constraint.
<b>INOXDE7669</b>	<b>(e-props-correct.5) Found circular substitution group</b>
<b>Explanation</b>	Circular substitution groups are disallowed. That is, it must not be possible to return to an element declaration by repeatedly following the {substitution group affiliation} property.
<b>Action</b>	Modify the schema to fulfill the constraint.

---

<b>INOXDE7670</b>	<b>The 'final' attribute of a simple or complex type definition is more restrictive in the new schema compared to the old schema</b>
<b>Explanation</b>	The 'final' attribute must not become more restrictive.
<b>Action</b>	Either adapt the value of the 'final' attribute or use instance validation when updating the schema.
<b>INOXDE7671</b>	<b>A type definition has been set to abstract in the new schema</b>
<b>Explanation</b>	When setting a type definition to abstract, this might cause documents to be invalid with respect to the new schema.
<b>Action</b>	Either make the type definition non-abstract as in the old schema or use instance validation when updating the schema.
<b>INOXDE7672</b>	<b>An element declaration has been set to abstract in the new schema</b>
<b>Explanation</b>	When setting an element declaration to abstract, this might cause documents to be invalid with respect to the new schema.
<b>Action</b>	Either make the element declaration non-abstract as in the old schema or use instance validation when updating the schema.
<b>INOXDE7673</b>	<b>A complex type definition's 'block' attribute has been made more restrictive in the new schema</b>
<b>Explanation</b>	When making a complex type definition's 'block' attribute more restrictive, this might cause documents to be invalid with respect to the new schema.
<b>Action</b>	Either set the complex type definition's 'block' attribute as in the old schema or use instance validation when updating the schema.
<b>INOXDE7674</b>	<b>An element declaration's 'block' attribute has been made more restrictive in the new schema</b>
<b>Explanation</b>	When making an element declaration's 'block' attribute more restrictive, this might cause documents to be invalid with respect to the new schema.
<b>Action</b>	Either set the element declaration's 'block' attribute as in the old schema or use instance validation when updating the schema.
<b>INOXDE7675</b>	<b>An element's 'nillable' attribute was set to false in new schema</b>
<b>Explanation</b>	If an element's 'nillable' attribute is set to false during a schema update, existing documents may become invalid.
<b>Action</b>	Either leave the element declaration's 'nillable' attribute unchanged or use instance validation for schema update.

<b>INOXDE7676</b>	<b>Mismatch of identity constraints found during schema update</b>
<b>Explanation</b>	It is not possible to modify existing or add new identity constraints during a schema update without using instance validation.
<b>Action</b>	Either do not add or modify identity constraints during schema update, or use instance validation.
<b>INOXDE7677</b>	<b>An elements 'substitutionGroup' attribute was omitted or modified during schema update.</b>
<b>Explanation</b>	An element's 'substitutionGroup' attribute may not be omitted or modified during schema update unless instance validation is being used.
<b>Action</b>	Either leave the 'substitutionGroup' attribute as is or use instance validation during schema update.
<b>INOXDE7680</b>	<b>(length valid restriction) the length facet has been changed compared to the length facet of the base type</b>
<b>Explanation</b>	It is an error if length is among the members of {facets} of {base type definition} and {value} is not equal to the {value} of the parent length.
<b>Action</b>	Modify the schema accordingly.
<b>INOXDE7681</b>	<b>(maxLength valid restriction) the maxLength facet has been increased compared to the maxLength facet of the base type</b>
<b>Explanation</b>	It is an error if maxLength is among the members of {facets} of {base type definition} and {value} is greater than the {value} of the parent maxLength.
<b>Action</b>	Modify the schema accordingly.
<b>INOXDE7682</b>	<b>(minLength valid restriction) the minLength facet has been decreased compared to the minLength facet of the base type</b>
<b>Explanation</b>	It is an error if minLength is among the members of {facets} of {base type definition} and {value} is less than the {value} of the parent minLength.
<b>Action</b>	Modify the schema accordingly.
<b>INOXDE7683</b>	<b>(totalDigits valid restriction) the totalDigits facet has been increased compared to the totalDigits facet of the base type</b>
<b>Explanation</b>	It is an error if totalDigits is among the members of {facets} of {base type definition} and {value} is greater than the {value} of the parent totalDigits.
<b>Action</b>	Modify the schema accordingly.

---

<b>INOXDE7684</b>	<b>(fractionDigits valid restriction) the fractionDigits facet has been increased compared to the fractionDigits facet of the base type</b>
<b>Explanation</b>	It is an error if fractionDigits is among the members of {facets} of {base type definition} and {value} is greater than the {value} of the parent totalDigits
<b>Action</b>	Modify the schema accordingly.
<b>INOXDE7685</b>	<b>(maxExclusive valid restriction) the maxExclusive facet has been increased compared to the maxExclusive facet of the base type</b>
<b>Explanation</b>	It is an error if any of the following conditions is true: 1. maxExclusive is among the members of {facets} of {base type definition} and {value} is greater than the {value} of the parent maxExclusive 2. maxInclusive is among the members of {facets} of {base type definition} and {value} is greater than the {value} of the parent maxInclusive 3. minInclusive is among the members of {facets} of {base type definition} and {value} is less than or equal to the {value} of the parent minInclusive 4. minExclusive is among the members of {facets} of {base type definition} and {value} is less than or equal to the {value} of the parent minExclusive
<b>Action</b>	Modify the schema accordingly.
<b>INOXDE7686</b>	<b>(maxInclusive valid restriction) the maxInclusive facet has been increased compared to the maxInclusive facet of the base type</b>
<b>Explanation</b>	It is an error if any of the following conditions is true: 1. maxInclusive is among the members of {facets} of {base type definition} and {value} is greater than the {value} of the parent maxInclusive 2. maxExclusive is among the members of {facets} of {base type definition} and {value} is greater than or equal to the {value} of the parent maxExclusive 3. minInclusive is among the members of {facets} of {base type definition} and {value} is less than the {value} of the parent minInclusive 4. minExclusive is among the members of {facets} of {base type definition} and {value} is less than or equal to the {value} of the parent minExclusive
<b>Action</b>	Modify the schema accordingly.
<b>INOXDE7687</b>	<b>(minExclusive valid restriction) the minExclusive facet has been increased compared to the minExclusive facet of the base type</b>
<b>Explanation</b>	It is an error if any of the following conditions is true: 1. minExclusive is among the members of {facets} of {base type definition} and {value} is less than the {value} of the parent minExclusive 2. maxInclusive is among the members of {facets} of {base type definition} and {value} is greater the {value} of the parent maxInclusive 3. minInclusive is among the members of {facets} of {base type definition} and {value} is less than the {value} of the parent minInclusive 4. maxExclusive is among the members of {facets} of {base type definition} and {value} is greater than or equal to the {value} of the parent maxExclusive
<b>Action</b>	Modify the schema accordingly.

**INOXDE7688 (minInclusive valid restriction) the minInclusive facet has been increased compared to the minInclusive facet of the base type**

**Explanation** It is an error if any of the following conditions is true: 1. minInclusive is among the members of {facets} of {base type definition} and {value} is less than the {value} of the parent minInclusive 2. maxInclusive is among the members of {facets} of {base type definition} and {value} is greater the {value} of the parent maxInclusive 3. minExclusive is among the members of {facets} of {base type definition} and {value} is less than or equal to the {value} of the parent minExclusive 4. maxExclusive is among the members of {facets} of {base type definition} and {value} is greater than or equal to the {value} of the parent maxExclusive

**Action** Modify the schema accordingly.

**INOXDE7689 (whiteSpace valid restriction) the whiteSpace facet has been changed to an invalid value compared to the whiteSpace facet of the base type**

**Explanation** It is an error if whiteSpace is among the members of {facets} of {base type definition} and any of the following conditions is true: 1. {value} is replace or preserve and the {value} of the parent whiteSpace is collapse 2. {value} is preserve and the {value} of the parent whiteSpace is replace

**Action** Modify the schema accordingly.

**INOXDE7690 (facet fixed) attempted to specify a different value for a facet which has fixed="true" in the base type definition**

**Explanation** The value of the facet differs from the value of the facet in the base type definition.

**Action** Omit the facet in the derived value or remove fixed="true" from the base type definition.

**INOXDE7696 Invalid change of schema-required property of collection**

**Explanation** A collection must be either schemaless or schemas are required for all documents to be stored. It is not allowed to change the schema-required property.

**Action** Adapt the collection description correspondingly.

**INOXDE7697 Could not create schemaless doctype in collection ino:etc**

**Explanation** It is not possible to have two schemaless doctypes in collection 'ino:etc' with the same lexical QName but different namespace of the root element.

**Action** A workaround is to change the namespace prefix of the root element of the first instance to be inserted in a new implicit doctype.

---

<b>INOXDE7698</b>	<b>(c-selector-xpath) Found invalid value of xpath attribute in definition of selector of identity constraint</b>
<b>Explanation</b>	The xpath attribute of the selector of an identity constraint must adhere to the (c-selector-xpath) constraint.
<b>Action</b>	Fix the value of the xpath attribute: all name tests must use valid QNames, all namespace prefixes must be declared, no attribute steps allowed.
<b>INOXDE7699</b>	<b>(c-fields-xpaths) Found invalid value of xpath attribute in definition of selector of identity constraint</b>
<b>Explanation</b>	The xpath attribute of all fields of an identity constraint must adhere to the (c-fields-xpaths) constraint.
<b>Action</b>	Fix the value of the xpath attribute: all name tests must use valid QNames, all namespace prefixes must be declared, an attribute step is only allowed at the last position.
<b>INOXDE7700</b>	<b>successful document validation</b>
<b>Explanation</b>	The document validated without error.
<b>Action</b>	No action required.
<b>INOXDE7701</b>	<b>memory allocation failed</b>
<b>Explanation</b>	Memory allocation failed during document validation.
<b>Action</b>	Please contact your software supplier.
<b>INOXDE7702</b>	<b>internal error</b>
<b>Explanation</b>	An internal processing error occurred during document validation.
<b>Action</b>	Please contact your software supplier.
<b>INOXDE7703</b>	<b>validation has detected an error in document</b>
<b>Explanation</b>	The document validation has discovered some invalid document content.
<b>Action</b>	Modify your document.
<b>INOXDE7704</b>	<b>(Parse error): document not well-formed</b>
<b>Explanation</b>	The document content is not well-formed.
<b>Action</b>	Modify your document

<b>INOXDE7705</b>	<b>(Parse error): junk data</b>
<b>Explanation</b>	The document contains junk data after the document content.
<b>Action</b>	Modify your input stream.
<b>INOXDE7706</b>	<b>(Parse error): close element error</b>
<b>Explanation</b>	The document contains a closing tag that does not match opening tag.
<b>Action</b>	Modify your document
<b>INOXDE7707</b>	<b>(Parse error): multiple attr</b>
<b>Explanation</b>	The document contains multiple occurrences of the same attribute.
<b>Action</b>	Modify your document
<b>INOXDE7708</b>	<b>Invalid root error</b>
<b>Explanation</b>	Tamino allows only insertion of documents with root elements whose names correspond to the name of some doctype in the collection where you tried to insert the current document.
<b>Action</b>	Modify your document or schema.
<b>INOXDE7709</b>	<b>Errors detected during document validation</b>
<b>Explanation</b>	Errors were detected during document validation.
<b>Action</b>	Please either modify your XML schema or fix errors in your document(s).
<b>INOXDE7710</b>	<b>(cvc-complex-type.2.1): empty content error</b>
<b>Explanation</b>	The schema requires empty element content but some content was detected.
<b>Action</b>	Modify your document or schema.
<b>INOXDE7711</b>	<b>(cvc-complex-type.2.3): mixed content error</b>
<b>Explanation</b>	The schema does not allow mixed element content but some mixed content was detected.
<b>Action</b>	Modify your document or schema.

---

<b>INOXDE7712</b>	<b>(cvc-complex-type.4): required attribute missing</b>
<b>Explanation</b>	The schema requires an attribute that is not present in document.
<b>Action</b>	Modify your document or schema.
<b>INOXDE7713</b>	<b>(cvc-wildcard.2): undeclared wildcard element</b>
<b>Explanation</b>	Schema contains ANY with processContent = strict but element content's name does not match any globally declared element.
<b>Action</b>	Modify your document or schema.
<b>INOXDE7714</b>	<b>(cvc-id.1): undefined IDREF value</b>
<b>Explanation</b>	The document contains an IDREF value which does not exist as an ID value.
<b>Action</b>	Modify your document.
<b>INOXDE7715</b>	<b>(cvc-id.2): duplicate ID value</b>
<b>Explanation</b>	The document contains multiple copies of the same ID value.
<b>Action</b>	Modify your document.
<b>INOXDE7716</b>	<b>(cvc-assess-attr.1): undeclared attribute</b>
<b>Explanation</b>	No matching declaration can be found in the schema for an attribute, neither as an explicitly named attribute nor as attribute wildcard.
<b>Action</b>	Modify your document.
<b>INOXDE7717</b>	<b>(cvc-type.3.1.1): invalid attribute</b>
<b>Explanation</b>	A simple type description in the schema does not allow attributes here.
<b>Action</b>	Modify your document.
<b>INOXDE7718</b>	<b>(cvc-type.3.1.2): invalid element content</b>
<b>Explanation</b>	A simple type description in the schema does not allow element children here.
<b>Action</b>	Modify your document.
<b>INOXDE7719</b>	<b>(cvc-particle): content of element does not match a particle description</b>
<b>Explanation</b>	Element content cannot be successfully validated against a particle description in schema.
<b>Action</b>	Modify your document.

<b>INOXDE7720</b>	<b>(cvc-particle.1.1): element content missing, minOccurs constraint violation in wildcard declaration</b>
<b>Explanation</b>	The length of the element content sequence does not satisfy the minOccurs constraint.
<b>Action</b>	Modify your document.
<b>INOXDE7721</b>	<b>(cvc-particle.1.2): too much element content, minOccurs constraint violation in wildcard declaration</b>
<b>Explanation</b>	The length of the element content sequence does not satisfy the minOccurs constraint of the wildcard declaration.
<b>Action</b>	Modify your document.
<b>INOXDE7722</b>	<b>(cvc-particle.2.1): element content missing, minOccurs constraint violation in element declaration</b>
<b>Explanation</b>	The length of the element content sequence does not satisfy the minOccurs constraint.
<b>Action</b>	Modify your document.
<b>INOXDE7723</b>	<b>(cvc-particle.2.2): too much element content, minOccurs constraint violation in element declaration</b>
<b>Explanation</b>	The length of the element content sequence does not match the minOccurs constraint for the element declaration.
<b>Action</b>	Modify your document.
<b>INOXDE7724</b>	<b>(cvc-particle.3.1): element content missing, minOccurs constraint violation in all model group declaration</b>
<b>Explanation</b>	The length of the element content sequence does not satisfy the minOccurs constraint.
<b>Action</b>	Modify your document.
<b>INOXDE7725</b>	<b>(cvc-particle.3.1): element content missing, minOccurs constraint violation in choice model group declaration</b>
<b>Explanation</b>	The length of the element content sequence does not satisfy the minOccurs constraint.
<b>Action</b>	Modify your document.

---

<b>INOXDE7726</b>	<b>(cvc-particle.3.1): element content missing, minOccurs constraint violation in sequence model group declaration</b>
<b>Explanation</b>	The length of the element content sequence does not satisfy the minOccurs constraint.
<b>Action</b>	Modify your document.
<b>INOXDE7727</b>	<b>(cvc-particle.3.2): too much element content, maxOccurs constraint violation in all model group declaration</b>
<b>Explanation</b>	The length of the element content sequence does not satisfy the maxOccurs constraint of the all model group declaration.
<b>Action</b>	Modify your document.
<b>INOXDE7728</b>	<b>(cvc-particle.3.2): too much element content, maxOccurs constraint violation in choice model group declaration</b>
<b>Explanation</b>	The length of the element content sequence does not satisfy the maxOccurs constraint of the choice model group declaration.
<b>Action</b>	Modify your document.
<b>INOXDE7729</b>	<b>(cvc-particle.3.2): too much element content, maxOccurs constraint violation in sequence model group declaration</b>
<b>Explanation</b>	The length of the element content sequence does not satisfy the maxOccurs constraint of the sequence model group declaration.
<b>Action</b>	Modify your document.
<b>INOXDE7730</b>	<b>(cvc-model-group.1):invalid end of sequence</b>
<b>Explanation</b>	A sequence does not contain all required elements. In particular, the sequence ends without containing all required elements.
<b>Action</b>	Modify your document.
<b>INOXDE7731</b>	<b>(cvc-model-group.1):invalid sequence</b>
<b>Explanation</b>	A sequence does not contain all required elements.
<b>Action</b>	Modify your document.

<b>INOXDE7732</b>	<b>(cvc-model-group.2):invalid choice</b>
<b>Explanation</b>	An element's child node does not match any choice in schema.
<b>Action</b>	Modify your document.
<b>INOXDE7733</b>	<b>(cvc-model-group.3):invalid all - missing element</b>
<b>Explanation</b>	An element's child node does not contain all required children of the all model group in the schema.
<b>Action</b>	Modify your document.
<b>INOXDE7734</b>	<b>(cvc-model-group.3):invalid all - undeclared element</b>
<b>Explanation</b>	An element's child node does not match any node declared in the all model group in the schema.
<b>Action</b>	Modify your document.
<b>INOXDE7735</b>	<b>(cvc-model-group.3):invalid all - too many child elements</b>
<b>Explanation</b>	All allowed elements in an all model group already appeared, but there are more illegal child elements.
<b>Action</b>	Modify your document.
<b>INOXDE7736</b>	<b>(cvc-model-group.3):invalid all - repeated occurrence of one element</b>
<b>Explanation</b>	Every child element in an all model group may appear at most once, but here the element appears more often.
<b>Action</b>	Modify your document.
<b>INOXDE7737</b>	<b>(cvc-wildcard-namespace): invalid namespace with respect to namespace constraint of wildcard</b>
<b>Explanation</b>	For namespace="##other" a non-absent namespace is required, which differs from the targetNamespace of the schema. For namespace="##targetNamespace" the namespace must match the current schema's targetNamespace. For namespace="##local" the element or attribute matching vs. the wildcard must not belong to any namespace. If the namespace attribute of the wildcard contains a list of URIs the namespace of the element or attribute matching vs. the wildcard must match one of the URIs in the list.
<b>Action</b>	Modify your document or schema.

---

<b>INOXDE7738</b>	<b>(cvc-wildcard-namespace.2.3): invalid namespace for wildcard with namespace="##other"</b>
<b>Explanation</b>	The namespace of an element or attribute does not differ from the current schema's targetNamespace as required by namespace='##other' specified in a wildcard (xs:any or xs:anyAttribute).
<b>Action</b>	Modify your document.
<b>INOXDE7739</b>	<b>(cvc-wildcard-namespace.3): invalid namespace for wildcard with namespace="##local"</b>
<b>Explanation</b>	An element or attribute belongs to a namespace in contradiction to the namespace="##local" attribute of a wildcard (xs:any or xs:anyAttribute).
<b>Action</b>	Modify your document.
<b>INOXDE7740</b>	<b>(cvc-complex-type.2.4): element child error</b>
<b>Explanation</b>	The list of child elements could not to be partitioned in a way that it becomes valid with respect to the content type's particle.
<b>Action</b>	Modify your document or schema.
<b>INOXDE7741</b>	<b>A namespace prefix conflict was detected when attempting to insert default or fixed value</b>
<b>Explanation</b>	A namespace prefix used in a value constraint for a node whose datatype is xs:QName, xs:NOTATION or a derived type cannot be associated with the intended URI as the document already contains a namespace declaration for that prefix mapped to a different URI. Note that the default namespace is always assumed to be used.
<b>Action</b>	Adapt the document to be stored or the fragment to be inserted to avoid conflict.
<b>INOXDE7742</b>	<b>(cvc-elt.4.3) The local type definition given by the xsi:type attribute is not validly derived from the type definition as of the underlying schema</b>
<b>Explanation</b>	The local type definition given by the xsi:type attribute must be derived from the type definition as of the underlying schema. Derivation methods listed in the attribute named "block" of the element declaration or the associated complex type definition may not be used.
<b>Action</b>	Either modify the schema by changing or removing the "block" attribute of the element declaration or complex type definition, or modify or remove the xsi:type attribute from the document to be stored.

<b>INOXDE7743</b>	<b>(cvc-elt.2) For an element information item to be locally valid with respect to an element declaration the declaration's abstract must be 'false'</b>
<b>Explanation</b>	Found an element declaration which is abstract when attempting to validate an element.
<b>Action</b>	Change the value of the 'abstract' property of the respective element declaration.
<b>INOXDE7744</b>	<b>(cvc-complex-type.1) For an element information item to be locally valid with respect to a complex type definition the type definition's abstract must be 'false'</b>
<b>Explanation</b>	Attempted to validate an element against a complex type definition which is abstract.
<b>Action</b>	Either make the type definition non-abstract, or use the xsi:type attribute in the XML document referring to a non-abstract derived type.
<b>INOXDE7745</b>	<b>(cvc-identity-constraint.3) An &lt;x:field&gt; of an identity constraint caused multiple matching nodes or the respective node does not have a simple type</b>
<b>Explanation</b>	For each node in the target node set of an identity constraint, all of the {fields} for a selected context node evaluate to either an empty node-set or a node-set with exactly one member, which must have a simple type.
<b>Action</b>	Check the XML document or remove the identity constraint from the schema.
<b>INOXDE7746</b>	<b>(cvc-identity-constraint.4.1) Found multiple occurrence of same key-sequence for &lt;x:unique&gt; identity constraint</b>
<b>Explanation</b>	No two members of the qualified node set of an <x:unique> may have key-sequences whose members are pairwise equal.
<b>Action</b>	Check the XML document or remove the identity constraint from the schema.
<b>INOXDE7747</b>	<b>(cvc-identity-constraint.4.2.1) A field of an &lt;x:key&gt; identity constraint evaluates to an empty node-set</b>
<b>Explanation</b>	For <x:key>, all the {fields} must evaluate to a node-set with exactly one member.
<b>Action</b>	Check the XML document or remove the identity constraint from the schema.
<b>INOXDE7748</b>	<b>(cvc-identity-constraint.4.2.2) Found multiple occurrence of same key-sequence for &lt;x:key&gt; identity constraint</b>
<b>Explanation</b>	No two members of the qualified node set of an <x:key> may have key-sequences whose members are pairwise equal.
<b>Action</b>	Check the XML document or remove the identity constraint from the schema.

---

<b>INOXDE7749</b>	<b>(cvc-identity-constraint.4.3) Could not locate matching key sequence in node table of &lt;xs:key&gt; identity constraint referenced by &lt;xs:keyref&gt;</b>
<b>Explanation</b>	For each member of the qualified node set of a <xs:keyref> there must be a corresponding entry in the node table of the referenced <xs:key>.
<b>Action</b>	Check the XML document or remove the identity constraint from the schema.
<b>INOXDE7750</b>	<b>(cvc-elt.3.1) Attribute 'xsi:nil' not allowed if the 'nillable' attribute of the element declaration is not set to 'true'</b>
<b>Explanation</b>	The predefined 'xsi:nil' attribute is only allowed on an element information item if the corresponding element declaration in the schema has its 'nillable' attribute to 'true'.
<b>Action</b>	Check the schema or remove the 'xsi:nil' attribute from the document.
<b>INOXDE7751</b>	<b>(cvc-elt.3.2.1) Found character or element content inside element information item with xsi:nil='true'</b>
<b>Explanation</b>	If an element has the xsi:nil='true' attribute, it must not have any character or element content.
<b>Action</b>	Modify the document accordingly.
<b>INOXDE7752</b>	<b>(cvc-elt.3.2.2) Element declaration corresponding to element information item with xsi:nil='true' attribute has a fixed value constraint</b>
<b>Explanation</b>	For an element information item with xsi:nil='true' attribute the corresponding element declaration in the schema must not have a fixed value constraint.
<b>Action</b>	Remove either the 'nillable' or the 'fixed' attribute from the element declaration in the schema.
<b>INOXDE7753</b>	<b>(cos-equiv-derived-ok-rec.2.1) The effective blocking constraint of the element to be substituted contains 'substitution'</b>
<b>Explanation</b>	The blocking constraint of an element to be substituted during validation must not contain 'substitution'.
<b>Action</b>	Adapt the XML document or modify the 'block' or 'blockDefault' attributes in the schema to become consistent with the constraint.
<b>INOXDE7754</b>	<b>(cos-equiv-derived-ok-rec.2.3) Type derivation between type of element to be substituted and type of the substituting element is blocked by the effective 'block' attribute of the element to be substituted</b>
<b>Explanation</b>	The type of the substituting element must be derived from the type of the element to be substituted by means of restriction and/or extension, unless one of those derivation methods is being blocked by the 'block' attribute (if present) of the element to be substituted, or the 'blockDefault' attribute of the parent schema.

<b>Action</b>	Adapt the XML document or modify the 'block' or 'blockDefault' attributes in the schema to become consistent with the constraint.
<b>INOXDE7761</b>	<b>(cvc-datatype-valid) Overflow detected during validation</b>
<b>Explanation</b>	A value overflow has been detected during validation against the XML schema.
<b>Action</b>	Ensure that the values adhere to datatype specific limits.
<b>INOXDE7762</b>	<b>(cvc-datatype-valid) Value out of range detected during validation</b>
<b>Explanation</b>	A value smaller than the valid minimum or larger than the allowed maximum has been detected during validation against the XML schema.
<b>Action</b>	Ensure that the values adhere to the datatype specific minimum and maximum.
<b>INOXDE7763</b>	<b>(cvc-datatype-valid) An invalid value has been found during validation</b>
<b>Explanation</b>	A value outside the lexical space has been detected during validation against the XML schema.
<b>Action</b>	Ensure that the value adheres to the datatype specific lexical space.
<b>INOXDE7764</b>	<b>(cvc-enumeration-valid) A value not defined in the respective enumeration has been found during validation.</b>
<b>Explanation</b>	A value which is not listed in the respective enumeration has been detected during validation against the XML schema.
<b>Action</b>	Ensure that the value matches one of the enumeration values specified in the XML schema.
<b>INOXDE7765</b>	<b>(cvc-length-valid) Facet 'length' was violated by a value during validation.</b>
<b>Explanation</b>	A value whose length does not match the 'length' facet has been detected during validation against the XML schema.
<b>Action</b>	Ensure that the value's length matches the restriction given by the schema.
<b>INOXDE7766</b>	<b>(cvc-attribute.4): fixed value error</b>
<b>Explanation</b>	An attribute declaration in schema requires a fixed value which is different from given value in document.
<b>Action</b>	Modify your document.

---

<b>INOXDE7767</b>	<b>(cvc-elt.5.2.2.2.1): fixed value error</b>
<b>Explanation</b>	The element declaration in schema requires a fixed value which is different from given value in document.
<b>Action</b>	Modify your document.
<b>INOXDE7768</b>	<b>(cvc-au): fixed value error</b>
<b>Explanation</b>	The attribute use declaration in the schema requires a fixed value which is different from the given value in the document.
<b>Action</b>	Modify your document.
<b>INOXDE7769</b>	<b>(cvc-elt.5.2.2.2.2): fixed value error</b>
<b>Explanation</b>	The element declaration in the schema requires a fixed value which is different from given value in document.
<b>Action</b>	Modify your document.
<b>INOXDE7770</b>	<b>(cvc-minLength-valid) Facet 'minLength' was violated by a value during validation</b>
<b>Explanation</b>	A value whose length is less than the 'minLength' facet has been detected during validation against the XML schema.
<b>Action</b>	Ensure that the value's length matches the restriction given by the schema.
<b>INOXDE7771</b>	<b>(cvc-maxLength-valid) Facet 'maxLength' was violated by a value during validation</b>
<b>Explanation</b>	A value whose length is greater than the 'maxLength' facet has been detected during validation against the XML schema.
<b>Action</b>	Ensure that the value's length matches the restriction given by the schema.
<b>INOXDE7772</b>	<b>(cvc-pattern-valid) Facet 'pattern' was violated by a value during validation</b>
<b>Explanation</b>	A value whose pattern does not match the 'pattern' facet has been detected during validation against the XML schema.
<b>Action</b>	Ensure that the value's pattern matches the restriction given by the schema.
<b>INOXDE7773</b>	<b>(cvc-enumeration-valid) Facet 'enumeration' was violated by a value during validation</b>
<b>Explanation</b>	A value has been found which does not match the valid values specified by the 'enumeration' facet, during validation against the XML schema.
<b>Action</b>	Ensure that the value matches the restriction given by the schema.

<b>INOXDE7774</b>	<b>(cvc-maxInclusive-valid) Facet 'maxInclusive' was violated by a value during validation</b>
<b>Explanation</b>	A value has been found which is greater than the 'maxInclusive' facet, during validation against the XML schema.
<b>Action</b>	Ensure that the value matches the restriction given by the schema.
<b>INOXDE7775</b>	<b>(cvc-maxExclusive-valid) Facet 'maxExclusive' was violated by a value during validation</b>
<b>Explanation</b>	A value has been found which is greater or equal to the 'maxExclusive' facet, during validation against the XML schema.
<b>Action</b>	Ensure that the value matches the restriction given by the schema.
<b>INOXDE7776</b>	<b>(cvc-minInclusive-valid) Facet 'minInclusive' was violated by a value during validation</b>
<b>Explanation</b>	A value has been found which is lower than the 'minInclusive' facet, during validation against the XML schema.
<b>Action</b>	Ensure that the value matches the restriction given by the schema.
<b>INOXDE7777</b>	<b>(cvc-minExclusive-valid) Facet 'minExclusive' was violated by a value during validation</b>
<b>Explanation</b>	A value has been found which is less than or equal to the 'minExclusive' facet, during validation against the XML schema.
<b>Action</b>	Ensure that the value matches the restriction given by the schema.
<b>INOXDE7778</b>	<b>(cvc-totalDigits-valid) Facet 'totalDigits' was violated by a value during validation</b>
<b>Explanation</b>	A numerical value has been found with more digits than specified by the 'totalDigits' facet, during validation against the XML schema.
<b>Action</b>	Ensure that the value matches the restriction given by the schema.
<b>INOXDE7779</b>	<b>(cvc-fractionDigits-valid) Facet 'fractionDigits' was violated by a value during validation</b>
<b>Explanation</b>	A numerical value has been found with more fractional digits (i.e. to the right of the decimal point) than specified by the 'fractionDigits' facet, during validation against the XML schema.
<b>Action</b>	Ensure that the value matches the restriction given by the schema.

---

<b>INOXDE7780</b>	<b>Divide by zero error</b>
<b>Explanation</b>	An attempt was made to divide by zero. Division by zero is mathematically undefined.
<b>Action</b>	Make sure that no division by zero occurs.
<b>INOXDE7781</b>	<b>Invalid or unsupported attribute found</b>
<b>Explanation</b>	An attribute was found that is not supported by Tamino.
<b>Action</b>	In order to enable xsi:type processing you have to set the server parameter "reject xsi:type" to "no".
<b>INOXDE7782</b>	<b>Namespace prefix is bound to an invalid URI</b>
<b>Explanation</b>	A namespace prefix must be bound to a non-empty URI in a namespace declaration. In addition, some prefixes must be bound to a fixed URI.
<b>Action</b>	Ensure e.g. that the prefix 'xml' is bound to 'http://www.w3.org/XML/1998/namespace', and that 'ino' is bound to 'http://namespaces.softwareag.com/tamino/response2'.
<b>INOXDE7783</b>	<b>The namespace prefix in an element or attribute value is not declared</b>
<b>Explanation</b>	If an element's or attribute's type is xs:QName or xs:NOTATION, the respective prefix must be declared in the schema document.
<b>Action</b>	Add the missing namespace declaration.
<b>INOXDE7784</b>	<b>Invalid namespace prefix</b>
<b>Explanation</b>	A namespace prefix is invalid.
<b>Action</b>	Modify the namespace definition and repeat the request.
<b>INOXDE7785</b>	<b>The datatype referenced by xsi:type is unknown</b>
<b>Explanation</b>	The value of the xsi:type attribute must reference a datatype predefined by XML Schema or a user-defined global datatype.
<b>Action</b>	Check the type reference via xsi:type in XML document.
<b>INOXDE7786</b>	<b>Invalid prefix bound to URI</b>
<b>Explanation</b>	The URI cannot be bound to the given namespace prefix.
<b>Action</b>	Use an appropriate prefix.

<b>INOXDE7787</b>	<b>Invalid value of 'xsi:nil' attribute</b>
<b>Explanation</b>	The value of the 'xsi:nil' attribute must be a valid boolean, i.e. 'true', 'false', '1', or '0'.
<b>Action</b>	Modify the document accordingly.
<b>INOXDE7821</b>	<b>Class not found</b>
<b>Explanation</b>	Tamino schema tree internal error message.
<b>Action</b>	Please contact your system administrator.
<b>INOXDE7822</b>	<b>Duplicated class name</b>
<b>Explanation</b>	Tamino schema tree internal error message.
<b>Action</b>	Please contact your system administrator.
<b>INOXDE7823</b>	<b>Illegal cast</b>
<b>Explanation</b>	Tamino schema tree internal error message.
<b>Action</b>	Please contact your system administrator.
<b>INOXDE7824</b>	<b>Internal API error</b>
<b>Explanation</b>	Tamino schema tree internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXDE7827</b>	<b>No memory</b>
<b>Explanation</b>	Tamino schema tree internal error message.
<b>Action</b>	Please contact your system administrator.
<b>INOXDE7828</b>	<b>No such element</b>
<b>Explanation</b>	Tamino schema tree internal error message.
<b>Action</b>	Please contact your system administrator.
<b>INOXDE7829</b>	<b>Not implemented</b>
<b>Explanation</b>	Tamino schema tree internal error message.
<b>Action</b>	Please contact your system administrator.

---

<b>INOXDE7830</b>	<b>Too many classes</b>
<b>Explanation</b>	Tamino schema tree internal error message.
<b>Action</b>	Please contact your system administrator.
<b>INOXDE7831</b>	<b>XML parser error</b>
<b>Explanation</b>	Tamino schema tree internal error message.
<b>Action</b>	Please contact your system administrator.
<b>INOXDE7833</b>	<b>Operation failed</b>
<b>Explanation</b>	An internal error occurred.
<b>Action</b>	Please contact your software supplier.
<b>INOXDE7856</b>	<b>Buffer size exceeded</b>
<b>Explanation</b>	Tamino schema tree error message.
<b>Action</b>	Please contact your system administrator.
<b>INOXDE7860</b>	<b>Internal error: invalid node type</b>
<b>Explanation</b>	This is a Tamino schema tree error message.
<b>Action</b>	Please contact your system administrator.
<b>INOXDE7861</b>	<b>Index out of range</b>
<b>Explanation</b>	Tamino schema tree error message.
<b>Action</b>	Please contact your system administrator.
<b>INOXDE7862</b>	<b>User abort</b>
<b>Explanation</b>	Tamino schema tree internal error message.
<b>Action</b>	Please contact your system administrator.
<b>INOXDE7865</b>	<b>Schema cache: access denied</b>
<b>Explanation</b>	Schema cache: access denied.
<b>Action</b>	Please contact your software supplier.

<b>INOXDE7867</b>	<b>Internal error: schema not in cache</b>
<b>Explanation</b>	Internal error: schema not in cache.
<b>Action</b>	Please contact your software supplier.
<b>INOXDE7868</b>	<b>Internal error: write lock expected</b>
<b>Explanation</b>	Internal error: write lock expected.
<b>Action</b>	Please contact your software supplier.
<b>INOXDE7869</b>	<b>Internal error: schema not locked</b>
<b>Explanation</b>	Internal error: schema not locked.
<b>Action</b>	Please contact your software supplier.
<b>INOXDE7883</b>	<b>(p-props-correct.2.1) If maxOccurs has a numeric value, then minOccurs must not be greater than maxOccurs</b>
<b>Explanation</b>	If maxOccurs has a numeric value, then minOccurs must not be greater than maxOccurs.
<b>Action</b>	Modify the XML schema accordingly.
<b>INOXDE7884</b>	<b>(p-props-correct.2.2) If maxOccurs has a numeric value, then maxOccurs must be greater than or equal to 1</b>
<b>Explanation</b>	If maxOccurs has a numeric value, then maxOccurs must be greater than or equal to 1.
<b>Action</b>	Modify the XML schema accordingly.
<b>INOXDE7885</b>	<b>(src-attribute.2) use must have value optional</b>
<b>Explanation</b>	If the attribute's "default" and "use" attributes are both present, then "use" must have the value "optional".
<b>Action</b>	Modify the XML schema accordingly.
<b>INOXDE7886</b>	<b>(src-attribute.4) For attribute the type and simpleType must not both be present</b>
<b>Explanation</b>	For attribute, the type and simpleType must not both be present.
<b>Action</b>	Modify the XML schema accordingly.

---

<b>INOXDE7887</b>	<b>(src-element.1) For element the attributes default and fixed must not both be present</b>
<b>Explanation</b>	For element, the attributes "default" and "fixed" must not both be present.
<b>Action</b>	Modify the XML schema accordingly.
<b>INOXDE7888</b>	<b>(src-element.3) For element the attributes type and either simpleType or complex Type are mutually exclusive</b>
<b>Explanation</b>	For element, the attributes "type" and either "simpleType" or "complex Type" are mutually exclusive.
<b>Action</b>	Modify the XML schema accordingly.
<b>INOXDE7889</b>	<b>(src-element.2.1) For element either the attribute ref or name must be present, but not both</b>
<b>Explanation</b>	For element, either the attribute ref or name must be present, but not both.
<b>Action</b>	Modify the XML schema accordingly.
<b>INOXDE7890</b>	<b>(src-element.2.2) For element if parent is not schema and attribute ref is present, only attributes minOccurs, maxOccurs and id are allowed in addition to ref</b>
<b>Explanation</b>	If the parent of the element is not schema and the attribute ref is present, then all of <xs:complexType>, <xs:simpleType>, <xs:key>, <xs:keyref>, <xs:unique>, nillable, default, fixed, form, block and type must be absent.
<b>Action</b>	Modify the XML schema accordingly.
<b>INOXDE7891</b>	<b>(valid-data-types.1) The type of nodes and base attribute of restriction nodes may only be of the supported types</b>
<b>Explanation</b>	The type of nodes and base attribute of restriction nodes may only be of the supported types, namely: date, decimal, double, float, integer, short, SQLNumeric,, SQLVarchar, string, time, timeinstant, ID, IDREF, IDREFS, NMTOKEN, NMTOKENS. No user-defined complexType or simpleType are allowed for type.
<b>Action</b>	Modify the XML schema accordingly.
<b>INOXDE7895</b>	<b>(valid-data-types.2) The facet is not valid for the base datatype</b>
<b>Explanation</b>	A facet has been specified which is not supported for the base datatype of a restriction.
<b>Action</b>	Modify the XML schema accordingly.

<b>INOXDE7900</b>	<b>(length and minLength or maxLength) Conflict between length facet and either minLength or maxLength</b>
<b>Explanation</b>	It is an error for both length and either of minLength or maxLength to be members of {facets}, unless they are specified in different derivation steps in which case the following must be true: the {value} of minLength <= the {value} of length <= the {value} of maxLength.
<b>Action</b>	Modify the XML schema accordingly.
<b>INOXDE7901</b>	<b>(fractionDigits less than or equal to totalDigits) The value of the fractionDigits facet is greater than the value of totalDigits</b>
<b>Explanation</b>	It is an error for fractionDigits to be greater than totalDigits.
<b>Action</b>	Modify the XML schema accordingly.
<b>INOXDE7902</b>	<b>The root node of a doctype has a non-trivial substitution group</b>
<b>Explanation</b>	The root node of a doctype must not have a non-trivial substitution group. The QName of the root element of an XML document stored in a doctype must be identical to the doctype's QName.
<b>Action</b>	Remove the substitutionGroup reference to the root node from the schema.
<b>INOXDE7906</b>	<b>Found illegal logical or physical property for shadowXML doctype</b>
<b>Explanation</b>	It is not allowed to specify certain logical or physical properties, e.g. XNode mapping, for a shadowXML doctype.
<b>Action</b>	Remove the illegal property below <tsd:logical> and <tsd:physical> for the shadowXML doctype.
<b>INOXDE7907</b>	<b>(src-resolve.1.3) The ref attribute of an element needs to reference an existing global element</b>
<b>Explanation</b>	The ref attribute of an element needs to reference an existing global element.
<b>Action</b>	Modify the XML schema accordingly.
<b>INOXDE7908</b>	<b>Found logical or physical properties for nonXML doctype</b>
<b>Explanation</b>	It is not allowed to specify logical or physical properties for a nonXML doctype.
<b>Action</b>	Remove <tsd:logical> and <tsd:physical> for the nonXML doctype.

---

<b>INOXDE7909</b>	<b>(cos-nonambig.1) Unique Particle Attribution failure</b>
<b>Explanation</b>	A content model must be formed such that during validation of an element information item sequence, the particle contained directly, indirectly or implicitly therein with which to attempt to validate each item in the sequence in turn can be uniquely determined without examining the content or attributes of that item, and without any information about the items in the remainder of the sequence.
<b>Action</b>	Modify the XML schema accordingly.
<b>INOXDE7910</b>	<b>(cos-all-limited.1.2) All group limitation failure</b>
<b>Explanation</b>	The cardinality of an all-model group must be exactly one.
<b>Action</b>	Modify the XML schema accordingly.
<b>INOXDE7911</b>	<b>(cos-all-limited.2) All group limitation failure</b>
<b>Explanation</b>	The maximum cardinality of all elements in all-model group must be 0 or 1.
<b>Action</b>	Modify the XML schema accordingly.
<b>INOXDE7912</b>	<b>(src-attribute.1) For attribute declarations, their attributes default and fixed must not both be present</b>
<b>Explanation</b>	For attribute declarations, the attributes "default" and "fixed" must not both be present.
<b>Action</b>	Modify the XML schema accordingly.
<b>INOXDE7913</b>	<b>(src-attribute.3.1) Either attribute ref or name must be present, but not both</b>
<b>Explanation</b>	Either the attribute "ref" or the attribute "name" must be present, but not both.
<b>Action</b>	Modify the XML schema accordingly.
<b>INOXDE7914</b>	<b>(src-attribute.3.2) If attribute's parent is not schema and ref is present, &lt;simpleType&gt;, form and type are not allowed</b>
<b>Explanation</b>	The form or type attribute as well as a simpleType cannot be specified with attribute declarations if the parent is not the schema node and the ref attribute is present.
<b>Action</b>	Modify the XML schema accordingly.
<b>INOXDE7915</b>	<b>The doctype name needs to be unique within a collection</b>
<b>Explanation</b>	The doctype name needs to be unique within a collection.
<b>Action</b>	Modify the XML schema accordingly.

<b>INOXDE7916</b>	<b>The given path must exist in the current schema</b>
<b>Explanation</b>	The given path must exist in the current schema.
<b>Action</b>	Modify the XML schema accordingly.
<b>INOXDE7917</b>	<b>For each doctype name where the doctype is not of plain non-XML type there must be a matching global element with a matching qualified name</b>
<b>Explanation</b>	For each doctype name where the doctype is not of plain non-XML type there must be a matching global element with a matching qualified name. In particular, for non-XML doctypes with non-XML indexing via a shadow XML document a matching global element must exist.
<b>Action</b>	Modify the XML schema accordingly.
<b>INOXDE7918</b>	<b>For each doctype name where the doctype is of type nonXML there must not be a matching global element with the same name</b>
<b>Explanation</b>	For each doctype name where the doctype is of type non-XML there must not be a matching global element with the same name.
<b>Action</b>	Modify the XML schema accordingly.
<b>INOXDE7919</b>	<b>For accessOptions at least one of read, insert, update or delete needs to be given, but no duplicate entries of these are allowed</b>
<b>Explanation</b>	For accessOptions at least one of read, insert, update or delete needs to be given, but no duplicate entries of these are allowed.
<b>Action</b>	Modify the XML schema accordingly.
<b>INOXDE7920</b>	<b>Invalid node name</b>
<b>Explanation</b>	The name of an element or attribute does not match the repository naming conventions.
<b>Action</b>	Change the name of element or attribute.
<b>INOXDE7921</b>	<b>Attempted to re-use a schema specifying physical properties from a schema belonging to a different collection</b>
<b>Explanation</b>	This constraint has been introduced in order to prevent database inconsistencies. It may vanish in a future version of Tamino.
<b>Action</b>	Change the collection name either of the referenced or the referring schema.

---

<b>INOXDE7922</b>	<b>The given path must exist in the current Schema and lead to the element or attribute for which it is specified</b>
<b>Explanation</b>	The given path must exist in the current schema and lead to the element or attribute for which it is specified.
<b>Action</b>	Modify the XML schema accordingly.
<b>INOXDE7923</b>	<b>No XPath expression may occur twice for one node to avoid conflicting mappings</b>
<b>Explanation</b>	No XPath expression may occur twice for one node in order to avoid conflicting mappings (not even if it specifies the same mapping).
<b>Action</b>	Modify the XML schema accordingly.
<b>INOXDE7924</b>	<b>At most one elementInfo or attributeInfo may have only empty or a nonexistent which-element, which is taken as the default mapping</b>
<b>Explanation</b>	At most one elementInfo or attributeInfo may have only empty or a non-existent which element, which is taken as the default mapping (Note: empty which elements are ignored, so an elementInfo which has both empty and filled which elements is interpreted as an elementInfo with filled which elements).
<b>Action</b>	Modify the XML schema accordingly.
<b>INOXDE7925</b>	<b>Below Schema there may only be one appinfo node which defines Tamino mappings</b>
<b>Explanation</b>	Below Schema there may only be one appinfo node which defines Tamino mappings.
<b>Action</b>	Modify the XML schema accordingly.
<b>INOXDE7926</b>	<b>Below Schema there must be a schemaInfo node but no elementInfo or attributeInfo nodes</b>
<b>Explanation</b>	Below Schema there must be a schemaInfo node but no elementInfo or attributeInfo nodes.
<b>Action</b>	Modify the XML schema accordingly.
<b>INOXDE7927</b>	<b>Below Element there may only be one appinfo node which defines Tamino mappings</b>
<b>Explanation</b>	Below Element there may only be one appinfo node which defines Tamino mappings.
<b>Action</b>	Modify the XML schema accordingly.

<b>INOXDE7928</b>	<b>Below Element there may be only elementInfo node but no schemaInfo or attributeInfo nodes</b>
<b>Explanation</b>	Below Element there may be only elementInfo node but no schemaInfo or attributeInfo nodes.
<b>Action</b>	Modify the XML schema accordingly.
<b>INOXDE7929</b>	<b>Below Attribute there may only be one appinfo node which defines Tamino mappings</b>
<b>Explanation</b>	Below Attribute there may only be one appinfo node which defines Tamino mappings.
<b>Action</b>	Modify the XML schema accordingly.
<b>INOXDE7930</b>	<b>internal error</b>
<b>Explanation</b>	While processing a schema document an internal error occurred.
<b>Action</b>	Please contact your software supplier.
<b>INOXDE7931</b>	<b>An error occurred while processing a schema document</b>
<b>Explanation</b>	An error occurred during processing of a TSD3 schema document.
<b>Action</b>	Details may be supplied by a secondary error message or can be retrieved using the admin-command <code>ino:CheckSchema(collection-name, schema-name)</code> or <code>ino:CheckSchema()</code> for all schemas in all collections. Correct the schema and update it in the database.
<b>INOXDE7932</b>	<b>Errors occurred when checking constraints for schema document</b>
<b>Explanation</b>	A TSD3 schema document does not adhere to all relevant restrictions.
<b>Action</b>	Check the secondary error message for details.
<b>INOXDE7933</b>	<b>Version mismatch occurred during schema processing</b>
<b>Explanation</b>	An attempt was made to load a TSD3 schema into a TSD2 collection or vice versa.
<b>Action</b>	Ensure that used schema language levels are consistent within a single collection.
<b>INOXDE7934</b>	<b>Invalid schema document</b>
<b>Explanation</b>	The XML document does not contain a valid TSD3 schema.
<b>Action</b>	Ensure that the schema document is consistent with the Tamino schema definition language TSD3.

---

<b>INOXDE7935</b>	<b>Schema not found</b>
<b>Explanation</b>	The referenced schema does not exist.
<b>Action</b>	Check for the existence of the referenced TSD3 schema.
<b>INOXDE7936</b>	<b>Invalid define of system collection</b>
<b>Explanation</b>	The schema to be defined refers to a collection reserved for system usage.
<b>Action</b>	Choose a different collection name.
<b>INOXDE7938</b>	<b>Internal error: invalid or unknown version information</b>
<b>Explanation</b>	Internal error occurred when retrieving or checking version information.
<b>Action</b>	Please contact your software supplier.
<b>INOXDE7939</b>	<b>Invalid schema document</b>
<b>Explanation</b>	The schema document contains an invalid or outdated format.
<b>Action</b>	Check the schema document. Possibly you are using TSD2. If so, convert to TSD3 using the Tamino Schema Editor.
<b>INOXDE7940</b>	<b>Invalid modification of doctype: cannot switch between storage of XML, nonXML and indexed nonXML documents</b>
<b>Explanation</b>	An error was detected when updating the schema: an attempt was made to modify between storage of XML, nonXML and indexed nonXML documents.
<b>Action</b>	Check the secondary error message for the context where the error was detected.
<b>INOXDE7941</b>	<b>Must not omit doctype during schema update</b>
<b>Explanation</b>	An error was detected when updating the schema: all doctypes defined in the original schema must occur in the new schema.
<b>Action</b>	Check the secondary error message for the context where the error was detected. Either extend the new schema document or undefine the obsolete doctype(s) before the next attempt to update the schema.
<b>INOXDE7942</b>	<b>Cannot switch doctype to closed content via schema update</b>
<b>Explanation</b>	It is not permitted to turn a doctype back to closed content if it had been configured for open content before.
<b>Action</b>	In order to switch a doctype back to closed content mode you have to undefine and re-create the doctype and reload the data.

<b>INOXDE7943</b>	<b>Mismatch of minOccurs attribute during schema update</b>
<b>Explanation</b>	An error was detected when updating the schema: the new value of the minOccurs attribute must be less than or equal to the old one.
<b>Action</b>	Check the secondary error message the for context where the error was detected.
<b>INOXDE7944</b>	<b>Mismatch of maxOccurs attribute during schema update</b>
<b>Explanation</b>	An error was detected when updating the schema: the new value of the the maxOccurs attribute must be greater than or equal to the old one. If it was previously unbounded, it must not be changed at all.
<b>Action</b>	Check the secondary error message for the context where the error was detected.
<b>INOXDE7945</b>	<b>Mismatch of mapping detected during schema update</b>
<b>Explanation</b>	An error was detected when updating the schema: a path containing mapping information which has been added in the new schema was already valid in the old schema.
<b>Action</b>	Check the secondary error message for the context where the error was detected.
<b>INOXDE7946</b>	<b>Mismatch of element or attribute name detected during schema update</b>
<b>Explanation</b>	An error was detected when updating the schema: names of corresponding elements or attributes in old and new schema are different.
<b>Action</b>	Check the secondary error message for the context where the error was detected.
<b>INOXDE7947</b>	<b>Mismatch of element or attribute type detected during schema update</b>
<b>Explanation</b>	An error was detected when updating the schema: types of corresponding elements or attributes in the old and new schema are different.
<b>Action</b>	Check the secondary error message for the context where the error was detected.
<b>INOXDE7948</b>	<b>Mismatch of content model detected during schema update</b>
<b>Explanation</b>	An error was detected when updating the schema: the content models are not equivalent.
<b>Action</b>	Check the secondary error message for the context where the error was detected.

---

<b>INOXDE7949</b>	<b>Mismatch of content model of sequence detected during schema update</b>
<b>Explanation</b>	An error was detected when updating the schema: the content model inside a sequence of the new schema contains an additional non-optional component.
<b>Action</b>	Check the secondary error message for the context where the error was detected.
<b>INOXDE7950</b>	<b>Mismatch of enumeration detected during schema update</b>
<b>Explanation</b>	An error was detected when updating the schema: it is only possible to add enumeration values in the new schema if there had been at least one enumeration value in the old schema.
<b>Action</b>	Check the secondary error message for the context where the error was detected.
<b>INOXDE7951</b>	<b>Mismatch of fixed attribute detected during schema update</b>
<b>Explanation</b>	An error was detected when updating the schema: the value of the fixed attribute of an element must not be changed.
<b>Action</b>	Check the secondary error message for the context where the error was detected.
<b>INOXDE7952</b>	<b>Mismatch of "default which" detected during schema update</b>
<b>Explanation</b>	An error was detected when updating the schema: no elementInfo or attributeInfo without a which element may be added in the new schema.
<b>Action</b>	Check the secondary error message for the context where the error was detected.
<b>INOXDE7953</b>	<b>Invalid modification of processContents attribute detected during schema update</b>
<b>Explanation</b>	An error was detected when updating the schema: the processContents attribute may only change from "strict" to "lax" to "skip".
<b>Action</b>	Check the secondary error message for the context where the error was detected.
<b>INOXDE7954</b>	<b>Invalid modification of mixed attribute detected during schema update</b>
<b>Explanation</b>	An error was detected when updating the schema: the mixed attribute may only change from "false" to "true".
<b>Action</b>	Check the secondary error message for the context where the error was detected.
<b>INOXDE7955</b>	<b>Invalid modification of components of choice detected during schema update</b>
<b>Explanation</b>	An error was detected when updating the schema: choice in the new schema must contain all components of choice in the old schema in arbitrary order. Additional components may be added for closed content. For open content, components may only be removed from the content model.
<b>Action</b>	Check the secondary error message for the context where the error was detected.

<b>INOXDE7956</b>	<b>Invalid modification of components of sequence detected during schema update</b>
<b>Explanation</b>	An error was detected when updating the schema: sequence in the new schema must contain all components of sequence in the old schema in the same order. Additional optional components with minOccurs=0 may be added in the case of closed content of the doctype. For open content, components may only be removed from the content model.
<b>Action</b>	Check the secondary error message for the context where the error was detected.
<b>INOXDE7957</b>	<b>Invalid modification of element's or attribute's simpleType detected during schema update</b>
<b>Explanation</b>	An error was detected when updating the schema: element or attribute may not be defined with simpleType in the old schema and without simpleType in the new schema or vice versa.
<b>Action</b>	Check the secondary error message for the context where the error was detected.
<b>INOXDE7958</b>	<b>Invalid modification of element's complexType detected during schema update</b>
<b>Explanation</b>	An error was detected when updating the schema: element or attribute may not be defined with complexType in the old schema and without complexType in the new schema or vice versa.
<b>Action</b>	Check the secondary error message for the context where the error was detected.
<b>INOXDE7960</b>	<b>Invalid path in schema definition</b>
<b>Explanation</b>	The specified path inside the which element is invalid for this schema.
<b>Action</b>	Check the path and schema definition.
<b>INOXDE7961</b>	<b>Invalid path in schema definition</b>
<b>Explanation</b>	The specified path inside the which element has an invalid syntax.
<b>Action</b>	Check the path value.
<b>INOXDE7962</b>	<b>Invalid modification of attribute list detected during schema update</b>
<b>Explanation</b>	An error was detected when updating the schema: all attributes defined for an element in the old schema must occur in the new schema in arbitrary order. Optional attributes may be added.
<b>Action</b>	Check the secondary error message for the context where the error was detected.

---

<b>INOXDE7963</b>	<b>Additional attribute must be optional during schema update</b>
<b>Explanation</b>	An error was detected when updating the schema: all additional attributes must be optional in the case of closed content. For open content, attributes may only be removed.
<b>Action</b>	Check the secondary error message for the context where the error was detected.
<b>INOXDE7964</b>	<b>Mismatch of use attribute detected during schema update.</b>
<b>Explanation</b>	An error was detected when updating the schema: the use attribute of an xsd:attribute may only be changed from "required" to "optional".
<b>Action</b>	Check the secondary error message for the context where the error was detected.
<b>INOXDE7965</b>	<b>Invalid modification of components of all detected during schema update</b>
<b>Explanation</b>	Invalid modification of components of all detected during schema update. Additional optional components may be added in the case of closed content. For open content, components may only be removed from the content model.
<b>Action</b>	Please modify your XML schema.
<b>INOXDE7966</b>	<b>Mismatch of targetNamespace attribute detected during schema update</b>
<b>Explanation</b>	The targetNamespace attribute may not be changed during a schema update.
<b>Action</b>	Please adapt your schema.
<b>INOXDE7967</b>	<b>Mismatch of namespace declaration detected during schema update</b>
<b>Explanation</b>	Namespace declarations may not be changed during a schema update.
<b>Action</b>	Please adapt your schema.
<b>INOXDE7968</b>	<b>New global element detected during schema update</b>
<b>Explanation</b>	Global elements may not be added during a schema update if there is an <code>&lt;xs:any&gt;</code> element by which they may be referred to implicitly.
<b>Action</b>	Please check your schema.
<b>INOXDE7969</b>	<b>New global attribute detected during schema update</b>
<b>Explanation</b>	Global attributes may not be added during a schema update if there is an <code>&lt;xs:anyAttribute&gt;</code> element they may be referred by implicitly.
<b>Action</b>	Please check your schema.

<b>INOXDE7970</b>	<b>Invalid attempt to remove an attribute wildcard (xs:anyAttribute) during a schema update</b>
<b>Explanation</b>	An attribute wildcard may not be removed during a schema update.
<b>Action</b>	Please check your schema.
<b>INOXDE7971</b>	<b>Removed global element during schema update</b>
<b>Explanation</b>	Global elements may not be removed during a schema update if there is an <code>&lt;xs:any&gt;</code> element they may be referred by implicitly.
<b>Action</b>	Please check your schema.
<b>INOXDE7972</b>	<b>Removed global attribute during schema update</b>
<b>Explanation</b>	Global attributes may not be removed during a schema update if there is an <code>&lt;xs:anyAttribute&gt;</code> element they may be referred by implicitly.
<b>Action</b>	Please check your schema.
<b>INOXDE7973</b>	<b>Facet added during schema update</b>
<b>Explanation</b>	The new schema contains a facet which is not present in the existing schema.
<b>Action</b>	Consider removing the facet from the new schema or use instance validation.
<b>INOXDE7974</b>	<b>Attempted to make value of facet more restrictive during schema update</b>
<b>Explanation</b>	The new schema definition contains a facet with a value more restrictive than in the existing schema. This is not allowed by the restricting facet.
<b>Action</b>	Consider changing the value of the facet in the new schema or use instance validation.
<b>INOXDE7975</b>	<b>Restriction facet's value must not change during schema update</b>
<b>Explanation</b>	The new schema definition contains a facet with a value different from that in the existing schema. This is not allowed by the restricting facet.
<b>Action</b>	Consider changing the value of the facet in the new schema or use instance validation.
<b>INOXDE7976</b>	<b>Mismatch of pattern detected during schema update</b>
<b>Explanation</b>	An error was detected when updating the schema: It is only possible to add pattern values in the new schema if there had been at least one pattern value in the old schema. It is only possible to remove pattern values from the new schema if this results in having no pattern values in the new schema.
<b>Action</b>	Check the secondary error message for the context where the error was detected.

---

<b>INOXDE7978</b>	<b>Mismatch of namespace declarations found during schema update checks</b>
<b>Explanation</b>	An attempt was made to modify the URI associated with a namespace prefix. This is based on namespace declarations in the schema document. Either a namespace declaration was omitted or the URI has been changed. This is not allowed because it would change the semantics of X-Query requests on namespace-clean doctypes.
<b>Action</b>	Modify the schema accordingly.
<b>INOXDE7979</b>	<b>Invalid schema changes found when adding a unique constraint - no other schema changes are permitted</b>
<b>Explanation</b>	When adding a unique constraint no other schema changes are permitted in the same schema update operation. It is also not permitted to add multiple unique constraints in a single schema update.
<b>Action</b>	Either add a single unique constraint or perform other schema changes in separate steps.
<b>INOXDE7980</b>	<b>At least one doctype contains instances with xsi:type attributes. Schema update requires explicit validation.</b>
<b>Explanation</b>	This error may show up e.g. if the set of global types is going to change due to the schema update. Thus, XML instances containing xsi:type attributes require re-validation. Note that this status of the doctype remains set even after the respective XML documents have been deleted.
<b>Action</b>	Perform a schema update with instance validation ( <code>_mode=validate</code> ).
<b>INOXDE7981</b>	<b>Attempted to remove member of substitution group during schema update for doctype with closed content</b>
<b>Explanation</b>	You cannot remove a member of a substitution group during a schema update for a doctype with closed content without instance validation.
<b>Action</b>	Use instance validation during the schema update.
<b>INOXDE7982</b>	<b>Attempted to add member of substitution group during schema update for doctype with open content</b>
<b>Explanation</b>	You cannot add a member of a substitution group during a schema update for a doctype with open content without using instance validation.
<b>Action</b>	Use instance validation during the schema update.

<b>INOXDE7988</b>	<b>Failed to lock schema document.</b>
<b>Explanation</b>	A schema document could not be locked due to a parallel transaction.
<b>Action</b>	Check for parallel transaction using the same schema with a conflicting type of lock. Typically, commands modifying a schema require a write lock for the schema and will conflict with each other, or with other transactions having a read lock on the schema.
<b>INOXDE7989</b>	<b>Cannot define schema in schemaless collection</b>
<b>Explanation</b>	It is not allowed to define a schema if the collection is defined with schema use 'prohibited'.
<b>Action</b>	Use another collection - or just do not define schema at all. Schemaless collections (like ino:etc) allow documents to be stored without defining a schema. You may also change the collection for optional schema usage.
<b>INOXDE7992</b>	<b>Index migration for doctype 'doctype' in collection 'collection' failed with error code errorCode</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXDE7993</b>	<b>Schema operation failed because the same request has doctype already in use</b>
<b>Explanation</b>	Schemas cannot be modified or deleted from a server extension if the calling command has an affected doctype in use.
<b>Action</b>	Change your application.
<b>INOXDE7996</b>	<b>Doctype requires xsi:type migration - schema update requires instance validation</b>
<b>Explanation</b>	The given doctype contains documents with xsi:type attribute(s) that were stored in previous version of Tamino. As the processing of xsi:type was not complete in previous versions of Tamino up to version 4.2, explicit validation of the documents against the schema is required.
<b>Action</b>	Perform a schema update with instance validation ( <code>_MODE=validate</code> ). Depending on the type definitions being referenced by the xsi:type attribute, the original schema may need to be adapted, as the type being referenced by xsi:type must be validly derived from the default type of the respective element as given in the schema.

---

<b>INOXDE7997</b>	<b>Missing 'type' attribute in definition of computed index.</b>
<b>Explanation</b>	The <tsd:computed> elements must have a 'type' attribute if it is not a compound index.
<b>Action</b>	Fix the schema accordingly.
<b>INOXDE7998</b>	<b>Found unexpected 'type' attribute in definition of computed index with multiple components.</b>
<b>Explanation</b>	For a compound computed index, i.e. with multiple components, only the component definitions may have a 'type' attribute.
<b>Action</b>	Fix the schema accordingly.
<b>INOXDE7999</b>	<b>Found component of a computed index which does not have a simple type.</b>
<b>Explanation</b>	The component of a computed index must have a simple type.
<b>Action</b>	Fix the schema accordingly.
<b>INOXDF7601</b>	<b>XML initialization: failed to define collection/doctype, rsp: rsp</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXDF7613</b>	<b>Unexpected error (rsp,line) occurred during op (parm).</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXDI7582</b>	<b>The path specified in the xpath attribute of a field element may not be empty or start with a slash</b>
<b>Explanation</b>	mp-valid-field.3: The path specified in the xpath attribute of a field element may not be empty or start with a slash.
<b>Action</b>	Please change the schema and try to define it again.
<b>INOXDI7608</b>	<b>Upgrade system collections</b>
<b>Explanation</b>	The system collections need to be upgraded.
<b>Action</b>	No action required.

<b>INOXDI7991</b>	<b>Indexes of doctype 'doctype' in collection 'collection' have been migrated successfully</b>
<b>Explanation</b>	In the given doctype, all indexes marked for migration have been rebuilt successfully.
<b>Action</b>	No action required.
<b>INOXDS7600</b>	<b>Define 'doctype' in collection 'collection'</b>
<b>Explanation</b>	The given system doctype will be defined or upgraded.
<b>Action</b>	No action required.
<b>INOXDS7602</b>	<b>Define collection 'collection'</b>
<b>Explanation</b>	The given system collection will be defined or upgraded.
<b>Action</b>	No action required.
<b>INOXDS7611</b>	<b>Define missing collection objects</b>
<b>Explanation</b>	For all existing collections the respective objects are now being loaded.
<b>Action</b>	No action required.
<b>INOXDW7678</b>	<b>Usage of a non-field element as element or attribute in schema definition</b>
<b>Explanation</b>	Field is defined as phonetic, sub, super or hyper-descriptor in Adabas field definition.
<b>Action</b>	Check your schema definition.
<b>INOXDW7990</b>	<b>Doctype 'doctype' in collection 'collection' requires index migration</b>
<b>Explanation</b>	The referenced doctype contains nodes whose indexes should be newly created.
<b>Action</b>	Refer to the migration related topics in the Tamino documentation.
<b>INOXDW7994</b>	<b>Multipath index 'label' in doctype 'doctype' in collection 'collection' is marked as not available</b>
<b>Explanation</b>	A previous schema update or index repair option could not be finished successfully. The given multipath index is still marked as being not available, and cannot be used for the efficient evaluation of query results.
<b>Action</b>	Update the respective schema in Tamino. This will enforce a rebuild of the respective multipath index.

---

<b>INOXDW7995</b>	<b>Doctype 'doctype' in collection 'collection' requires xsi:type migration</b>
<b>Explanation</b>	The given doctype contains documents with xsi:type attribute(s) that were stored in a previous version of Tamino. As the processing of xsi:type was not complete in previous Tamino versions up to version 4.2, explicit validation of the documents against the schema is required.
<b>Action</b>	Perform a schema update with instance validation (_MODE=validate). Depending on the type definitions being referenced by the xsi:type attribute, the original schema may need to be adapted, as the type being referenced by xsi:type must be validly derived from the default type of the respective element as given in the schema.
<b>INOXHA8259</b>	<b>Start writing XML dump of database, writing to file filename</b>
<b>Explanation</b>	The server has encountered an error situation which causes a crash. In order to enable error analysis, the server writes XML status information to a file in the reserved location.
<b>Action</b>	Report the crash to your software supplier, together with the dump files in the reserved location.
<b>INOXHE8152</b>	<b>Web server ws: specified node host unknown (DNS rsp: rsp).</b>
<b>Explanation</b>	The given web server on the given node is defined as one of the web servers that are allowed to communicate with this Tamino database. Unfortunately the Tamino database is not able to resolve the specified node name.
<b>Action</b>	Check whether the node name is correct. If it is correct, check whether DNS lookups may fail due to network problems. In this case, use the IP address instead of the node name.
<b>INOXHE8153</b>	<b>Insufficient system resources to create thread: thread 'name', error error returned by thread create function</b>
<b>Explanation</b>	There are not enough system resources available to create a new thread.
<b>Action</b>	There are not enough system resources available to create a new thread. The reason is either that the system defined maximum for the number of threads per process is exceeded, or that there is not enough memory available to allocate the necessary thread resources.
<b>INOXHE8201</b>	<b>Cannot connect to server on host host at port port. TCP error code rsp.</b>
<b>Explanation</b>	The web server interface module was not able to connect to the Tamino server.
<b>Action</b>	Check if the Tamino server is active and accessible (e.g. using Telnet).

<b>INOXHE8202</b>	<b>Tamino database unknown</b>
<b>Explanation</b>	The web server interface module was not able to determine the network address (hostname and port number) of the Tamino database server.
<b>Action</b>	Check if the issued URL really points to the desired Tamino database server. If this is OK, check the configuration data of the web server interface module. If this is OK too, please contact your software supplier.
<b>INOXHE8203</b>	<b>Database server and web server interface module not compatible</b>
<b>Explanation</b>	The versions of the Tamino database server and the Tamino web server interface module are not compatible.
<b>Action</b>	Please use compatible versions of the Tamino database server and the Tamino web server interface module.
<b>INOXHE8220</b>	<b>XML initialization:SXS initialization failed: sxsMsg</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHE8254</b>	<b>Failed to create the Software AG XTS Directory Server entries: why</b>
<b>Explanation</b>	The server failed to create the necessary Software AG XTS Directory Server entries and the server startup failed. The reason for the failure is returned by the XTS layer.
<b>Action</b>	Please check that the service "Software AG XTS Directory Server" is running. If not, please start it. On Windows this can be done using the Control Panel. On UNIX please use the scripts provided (which are normally executed at system start). If the service was running when the error occurred, and the XTS message does not specify enough details to fix the problem, please contact your software supplier.
<b>INOXHE8257</b>	<b>Conversion failed, output encoding enc, error code rsp</b>
<b>Explanation</b>	The conversion into the desired document encoding failed.
<b>Action</b>	Check the desired encoding and correct it.
<b>INOXHE8258</b>	<b>Unable to start request</b>
<b>Explanation</b>	There is a resource shortage on the server.
<b>Action</b>	Increase number of XML work threads. If the problem persists, increase the number of data working threads also.

---

<b>INOXHE8261</b>	<b>XML crash dump file filename could not be created due to operating system error system errno</b>
<b>Explanation</b>	The XML crash dump file needed for error analysis could not be created due to the given reason.
<b>Action</b>	Please consult the manufacturer's manual.
<b>INOXHE8270</b>	<b>XML internal error num: Session sess, Rsp rsp, time</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHE8278</b>	<b>Internal error</b>
<b>Explanation</b>	An internal error has occurred.
<b>Action</b>	Please contact your software supplier.
<b>INOXHE8282</b>	<b>Internal error</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHE8283</b>	<b>Internal error</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHE8284</b>	<b>Internal error</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHE8285</b>	<b>Invalid Session ID</b>
<b>Explanation</b>	The specified session does not exist or it is currently executing a different request.
<b>Action</b>	Specify a valid Session ID.
<b>INOXHE8286</b>	<b>Internal error</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Please contact your software supplier.

**INOXHE8287**      **Internal error**  
**Explanation**      Internal error.  
**Action**              Please contact your software supplier.

**INOXHE8288**      **Internal error**  
**Explanation**      Internal error.  
**Action**              Please contact your software supplier.

**INOXHE8289**      **Internal error**  
**Explanation**      Internal error.  
**Action**              Please contact your software supplier.

**INOXHE8290**      **Internal error**  
**Explanation**      Internal error.  
**Action**              Please contact your software supplier.

**INOXHE8291**      **Internal error**  
**Explanation**      Internal error.  
**Action**              Please contact your software supplier.

**INOXHE8292**      **Internal error**  
**Explanation**      Internal error.  
**Action**              Please contact your software supplier.

**INOXHE8293**      **Internal error**  
**Explanation**      Internal error.  
**Action**              Please contact your software supplier.

**INOXHE8294**      **Internal error**  
**Explanation**      Internal error.  
**Action**              Please contact your software supplier.

---

<b>INOXHE8295</b>	<b>Internal error</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHE8296</b>	<b>Internal error</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHE8297</b>	<b>Error occurred in communication with client</b>
<b>Explanation</b>	A communication problem occurred when receiving a request or sending a response to the client.
<b>Action</b>	Please check the web server log files or network configuration for possible reasons.
<b>INOXHE8298</b>	<b>Internal error</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHE8299</b>	<b>Internal error</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHF8155</b>	<b>Communication method 'SSL' requires a certificate</b>
<b>Explanation</b>	The server property 'communication method' is set to 'SSL', but the server property 'SSL certificate file' is not set. A certificate is mandatory for encrypted communication.
<b>Action</b>	Specify the location of the certificate that the server should use.
<b>INOXHF8158</b>	<b>Set version failed. Reason: reason. Internal response d.</b>
<b>Explanation</b>	An error occurred during migration.
<b>Action</b>	Please contact your software supplier and provide the server startup logfile.
<b>INOXHF8159</b>	<b>Exception d occurred during server startup: msg</b>
<b>Explanation</b>	The server could not be started.
<b>Action</b>	Please contact your software supplier.

<b>INOXHF8160</b>	<b>Communication method 'SSL' requires a private key</b>
<b>Explanation</b>	The server property 'communication method' is set to 'SSL', but the server property 'SSL key file' is not set. A private key is mandatory for encrypted communication.
<b>Action</b>	Specify the location of the private key that the server should use.
<b>INOXHF8162</b>	<b>Error in SSL cipher list detected.</b>
<b>Explanation</b>	SSL Cipher list provided shows incorrect syntax.
<b>Action</b>	please correct
<b>INOXHF8200</b>	<b>XML thread initialization failed</b>
<b>Explanation</b>	The initialization of X-Machine failed with the mentioned response code. This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHF8205</b>	<b>XML thread initialization: data map initialization failed, rsp: rsp</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHF8206</b>	<b>XML thread initialization: define of ino:collection failed, rsp: rsp</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHF8207</b>	<b>XML thread initialization: check of ino:collection failed, rsp: rsp</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHF8208</b>	<b>XML thread initialization: check of security collection failed, rsp: rsp</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHF8209</b>	<b>XML thread initialization: insert security collection failed, rsp: rsp</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.

---

<b>INOXHF8210</b>	<b>XML thread initialization: insert vocabulary collection failed, rsp: rsp</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHF8211</b>	<b>XML thread initialization: check of vocabulary collection failed, rsp: rsp</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHF8212</b>	<b>XML thread initialization: security initialization failed, rsp: rsp</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHF8213</b>	<b>XML thread initialization: vocabulary initialization failed, rsp: rsp</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHF8214</b>	<b>XML thread initialization: commit failed, rsp: rsp</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHF8215</b>	<b>XML thread initialization: rollback failed, rsp: rsp</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHF8216</b>	<b>XML thread initialization: Memory allocation failed</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHF8217</b>	<b>XML work thread thid abended</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.

<b>INOXHF8218</b>	<b>XML receive thread thid abended</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHF8219</b>	<b>XML listen thread accept failed, rsp: tprsp</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHF8221</b>	<b>TCP/IP select failed, rsp: tprsp</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHF8223</b>	<b>XML connection initialization failed (error error number)</b>
<b>Explanation</b>	The initialization of the XML communication did not work as expected. The server could not be started.
<b>Action</b>	Repeat the action. If it still fails, contact your software supplier.
<b>INOXHF8224</b>	<b>Unexpected receive count: cnt</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHF8225</b>	<b>XML initialization: data map initialization failed</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHF8226</b>	<b>XML initialization:security initialization failed</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHF8227</b>	<b>XML initialization: internal error</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.

---

<b>INOXHF8228</b>	<b>XML thread initialization: creation of anonymous session failed</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHF8229</b>	<b>XML thread initialization: server extension thread initialization failed, rsp: rsp</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHF8230</b>	<b>XML initialization:TCP/IP startup failed</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHF8233</b>	<b>XML initialization: gethostname failed</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHF8234</b>	<b>XML initialization: gethostbyname failed, host: host, rsp: rsp</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHF8235</b>	<b>XML initialization: invalid port number "port" found for web server webserver</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHF8237</b>	<b>XTS Register Server failed for XML: xtmsg</b>
<b>Explanation</b>	The registration of the Tamino XML server via XTS failed.
<b>Action</b>	Check and correct the XTS configuration and/or directory server.
<b>INOXHF8239</b>	<b>XML initialization: failed to define collection/doctype, rsp: rsp</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.

<b>INOXHF8240</b>	<b>XML thread thread_number has exited due to communication error error_number (text)</b>
<b>Explanation</b>	Either adding the service to the directory server has failed, or registering with the directory server has failed.
<b>Action</b>	Check the XTS configuration.
<b>INOXHF8241</b>	<b>XML thread thread_number has exited due to communication error error_number (text)</b>
<b>Explanation</b>	Either adding the service to the directory has failed, or the registration with the directory server failed.
<b>Action</b>	Check the XTS configuration.
<b>INOXHF8243</b>	<b>XML processing not initialized</b>
<b>Explanation</b>	The initialization of the XML processing did not work as expected. The server could not be started.
<b>Action</b>	Repeat the action. If it still fails, contact your support center.
<b>INOXHF8244</b>	<b>Binding to TCP/IP socket socket number (port type port) has failed</b>
<b>Explanation</b>	The server could not connect to the specified socket. Maybe it is in use.
<b>Action</b>	Check the reason for the error. If the error persists, choose another port number.
<b>INOXHF8255</b>	<b>XML initialization: invalid IP address "ipaddr" found for web server webserver</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHF8256</b>	<b>XML initialization: Memory allocation failed</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHF8262</b>	<b>XML thread initialization: initialization of tokenizer failed, rsp: rsp</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.

---

<b>INOXHF8263</b>	<b>XML initialization: No license for tok tokenizer</b>
<b>Explanation</b>	No valid license found for the default tokenizer.
<b>Action</b>	Please check the setting of database parameter "default tokenizer" and the used license file. If the problem persists, please contact your software supplier.
<b>INOXHF8264</b>	<b>XML thread initialization: Create failed for obj</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHF8266</b>	<b>Invalid default tokenizer: tok</b>
<b>Explanation</b>	The value of the parameter "default tokenizer" is invalid.
<b>Action</b>	Use a valid value.
<b>INOXHF8269</b>	<b>XML thread initialization: data map initialization for server extensions failed, rsp: rsp</b>
<b>Explanation</b>	Internal error: Data map entries needed by X-Tension could not be initialized.
<b>Action</b>	Please contact your software supplier.
<b>INOXHF8271</b>	<b>XML initialization: invalid/unsupported default encoding 'defEnc'</b>
<b>Explanation</b>	An invalid/unsupported MIME or IANA encoding name is specified for the 'default encoding' database parameter.
<b>Action</b>	Please check the setting of the 'default encoding' database parameter. If the problem persists, please contact your software supplier.
<b>INOXHF8272</b>	<b>XML initialization: Word stemming algorithm initialization failed, rsp: rsp</b>
<b>Explanation</b>	This is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXHF8273</b>	<b>Failed to attach definition of system collections</b>
<b>Explanation</b>	The shared library containing in particular the meta schema could not be loaded.
<b>Action</b>	Check your installation.

<b>INOXH8279</b>	<b>Necessary allocation of static port failed</b>
<b>Explanation</b>	The allocation of a necessary static port failed.
<b>Action</b>	Please contact your software supplier.
<b>INOXH8151</b>	<b>Communication method: s</b>
<b>Explanation</b>	The given communication method will be used for the server that is starting. See the user documentation for the server property "Communication Method" for more information.
<b>Action</b>	No action required.
<b>INOXH8156</b>	<b>TCP/IP send failed, rsp: rsp, time</b>
<b>Explanation</b>	The Tamino server failed to respond to a request. The communication method used was TCP/IP. The reported response code is the error which the Tamino server got from TCP/IP "send".
<b>Action</b>	Please check the state of TCP/IP.
<b>INOXH8157</b>	<b>XTS send failed, rsp: rsp, time</b>
<b>Explanation</b>	The Tamino server failed to respond to a request. The communication method used was XTS. The reported response code is the error which the Tamino server got from XTS "SendMessageByRT".
<b>Action</b>	Please check the state of XTS.
<b>INOXH8222</b>	<b>TCP/IP receive failed, rsp: rsp</b>
<b>Explanation</b>	Error in the TCP/IP stack.
<b>Action</b>	Please check the state of TCP/IP.
<b>INOXH8242</b>	<b>Define doctype in collection collection</b>
<b>Explanation</b>	A system doctype with given name is being created in the given collection.
<b>Action</b>	No action required
<b>INOXH8247</b>	<b>Dynamic what worker thread created</b>
<b>Explanation</b>	The server increased the number of worker threads to avoid a possible deadlock.
<b>Action</b>	No action required.

---

<b>INOXHI8251</b>	<b>Overwriting Software AG XTS Directory Server entries</b>
<b>Explanation</b>	The Software AG XTS Directory Server entries already existed. They are overwritten.
<b>Action</b>	No action required.
<b>INOXHI8252</b>	<b>type - 'dsentry'</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.
<b>INOXHI8253</b>	<b>Use switch parameter 'param' to force server registration</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.
<b>INOXHI8260</b>	<b>XML crash dump of database finished</b>
<b>Explanation</b>	The XML crash dump is complete.
<b>Action</b>	No action required.
<b>INOXHI8265</b>	<b>Default tokenizer 'tok'</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.
<b>INOXHI8267</b>	<b>User dictionary 'udict'</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.
<b>INOXHI8274</b>	<b>Word stemming index successfully created</b>
<b>Explanation</b>	The database parameter 'stemming index' is enabled and the stemming index for documents with text indices is created.
<b>Action</b>	No action required.
<b>INOXHI8275</b>	<b>Word stemming index successfully dropped</b>
<b>Explanation</b>	The database parameter 'stemming index' is disabled and the stemming index for documents with text indices is removed.
<b>Action</b>	No action required.

<b>INOXHI8276</b>	<b>Web server configuration updated</b>
<b>Explanation</b>	The web server configuration was changed and is now updated in the server.
<b>Action</b>	No action required.
<b>INOXHI8277</b>	<b>Internal error</b>
<b>Explanation</b>	An internal error has occurred.
<b>Action</b>	Please contact your software supplier.
<b>INOXHR8245</b>	<b>Initializing XML processing</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.
<b>INOXHR8246</b>	<b>Starting XML threads</b>
<b>Explanation</b>	This is an informational message.
<b>Action</b>	No action required.
<b>INOXHV8250</b>	<b>Server is already registered with the Software AG XTS Directory Server</b>
<b>Explanation</b>	When the Tamino server starts it registers with the Software AG XTS Directory Server. It is possible that entries for the server are already present (server already started somewhere else or previous server session failed). If this message comes as a warning message, the entry found exactly matches the one that should be entered. If this message comes as an error message, the entry found did not match the entry that the server wanted to add.
<b>Action</b>	If this message comes as a warning message no action is required. If this message comes as an error message the Software AG XTS Directory Server entry found for the server should be checked and, if no longer necessary, the next server start should be done with the parameter for overwriting the Software AG XTS Directory Server entry activated.
<b>INOXHW8154</b>	<b>TCP connection timed out</b>
<b>Explanation</b>	A violation of Tamino Network Protocol was detected.
<b>Action</b>	Check the client application / network.

<b>INOXHW8161</b>	<b>HTTP connection timed out</b>
<b>Explanation</b>	A violation of Tamino Network Protocol was detected.
<b>Action</b>	Check the client application / network.
<b>INOXHW8204</b>	<b>XML thread initialization: data map initialization for server extension failed, rsp: rsp</b>
<b>Explanation</b>	This is an internal error. Tamino will work as expected unless server extensions are used.
<b>Action</b>	Please contact your software supplier.
<b>INOXHW8231</b>	<b>No license for Tamino XML</b>
<b>Explanation</b>	A special license must be bought to use the Tamino XML feature.
<b>Action</b>	Buy a license for Tamino XML.
<b>INOXHW8232</b>	<b>Only numLic concurrent XML sessions licensed</b>
<b>Explanation</b>	The server parameter "XML maximum sessions" contains a value that is larger than the number of concurrent sessions that is included in the used license.
	Only the number of sessions that is covered by the license used is allowed.
<b>Action</b>	Buy an enhanced license.
<b>INOXHW8236</b>	<b>XML connection refused; current number of connections: totCon</b>
<b>Explanation</b>	Tamino is not able to accept another XML request. The connection attempt is refused.
<b>Action</b>	Increase the number of XML work threads.
<b>INOXHW8238</b>	<b>Unable to free storage.</b>
<b>Explanation</b>	This is an internal error. X-Machine is not able to free all storage during shutdown.
<b>Action</b>	Please contact your software supplier.
<b>INOXHW8248</b>	<b>Maximum number of dynamic what worker threads reached</b>
<b>Explanation</b>	The maximum number of dynamic worker threads is reached. No further threads are created.
<b>Action</b>	The number of worker threads should be increased and the server should be restarted.

<b>INOXHW8249</b>	<b>Creation of dynamic what worker thread failed with response err</b>
<b>Explanation</b>	The server failed to increase the number of worker threads.
<b>Action</b>	No action required.
<b>INOXHW8268</b>	<b>Invalid entry in user dictionary 'tok'</b>
<b>Explanation</b>	The user dictionary contains an invalid entry. It is ignored.
<b>Action</b>	Check the user dictionary contents.
<b>INOXIE8300</b>	<b>No matching document found</b>
<b>Explanation</b>	The specified query did not find any matching documents.
<b>Action</b>	None. This is only an informational error message.
<b>INOXIE8301</b>	<b>Illegal document ID specified</b>
<b>Explanation</b>	The specified document ID is illegal.
<b>Action</b>	Supply a legal document ID.
<b>INOXIE8303</b>	<b>Deleting a document is forbidden</b>
<b>Explanation</b>	A <code>_DELETE</code> operation was issued against a doctype where <code>DELETE</code> is missing in the doctype options as supplied in the schema definition.
<b>Action</b>	Change the doctype options accordingly.
<b>INOXIE8304</b>	<b>Reading a document is forbidden</b>
<b>Explanation</b>	An <code>_XQL</code> operation was issued against a doctype where <code>READ</code> is missing in the doctype options as supplied in the schema definition.
<b>Action</b>	Change the doctype options accordingly.
<b>INOXIE8305</b>	<b>Invalid cursor handle</b>
<b>Explanation</b>	The supplied cursor handle is invalid: either it was never created during the current session, or the corresponding cursor was closed in the meantime.
<b>Action</b>	Supply a correct cursor handle.

---

<b>INOXIE8306</b>	<b>Invalid cursor position</b>
<b>Explanation</b>	The supplied cursor position is invalid: there is no document in the cursor's result set corresponding to the position. In particular, this error will be returned when positioning beyond the end of the cursor result set.
<b>Action</b>	Supply a correct cursor position.
<b>INOXIE8307</b>	<b>Trying to position backwards in a non-scrollable cursor</b>
<b>Explanation</b>	The position supplied with the "fetch cursor" request would result in a backward positioning which is not possible for a non-scrollable cursor.
<b>Action</b>	Supply a correct cursor position.
<b>INOXIE8309</b>	<b>Duplicate in sort key</b>
<b>Explanation</b>	The system cannot handle sort key values which consist of more than a single node.
<b>Action</b>	Change your query expression so that no multiple node is to be sorted.
<b>INOXIE8310</b>	<b>Invalid parameter detected</b>
<b>Explanation</b>	Either the function is unknown or the number of parameters is invalid or the parameter values are invalid.
<b>Action</b>	Please check the function name, the number of parameters and the parameter values and correct them.
<b>INOXIE8312</b>	<b>Version fromVersion is incompatible with Version toVersion</b>
<b>Explanation</b>	The current version of the database is not compatible with the selected version.
<b>Action</b>	Data must be unloaded and loaded into a new database manually.
<b>INOXIE8313</b>	<b>Internal communication error</b>
<b>Explanation</b>	Database cannot be converted because of an internal error.
<b>Action</b>	Check that the database is running.
<b>INOXIE8314</b>	<b>Database's compatibility level is no longer supported</b>
<b>Explanation</b>	Migration from and to this compatibility level is not possible because this compatibility level is no longer supported.
<b>Action</b>	Data must be unloaded and loaded into a new database manually.

<b>INOXIE8315</b>	<b>Duplicate docnames found in ino:collection = 'collection' ino:doctype='doctype'</b>
<b>Explanation</b>	The upgrade has been rejected because because of duplicate docnames.
<b>Action</b>	Use the administration command ino:AdminDocname("check-unique") to get a list of duplicate docnames. Please delete the duplicate docnames and call the administration command ino:AdminDocname("set-unique").
<b>INOXIE8316</b>	<b>Attempted to delete a partial document</b>
<b>Explanation</b>	With _delete, it is only possible to delete complete XML documents.
<b>Action</b>	Supply a query that selects complete documents.
<b>INOXIE8319</b>	<b>Internal error occurred during query processing: unknown request</b>
<b>Explanation</b>	An internal error has occurred.
<b>Action</b>	Please contact your software supplier.
<b>INOXIE8320</b>	<b>Error parsing the XQL query</b>
<b>Explanation</b>	One or more errors occurred while parsing the XQL query.
<b>Action</b>	Correct query appropriately and re-issue
<b>INOXIE8321</b>	<b>Missing end quotation character</b>
<b>Explanation</b>	The end quotation character of a literal was not found. It could also be that the start and end quotation characters do not match.
<b>Action</b>	Correct query appropriately and re-issue.
<b>INOXIE8322</b>	<b>Named axes are not supported</b>
<b>Explanation</b>	The specification of named axes is not supported in Tamino.
<b>Action</b>	No action possible.
<b>INOXIE8331</b>	<b>Failed to set the server parameter</b>
<b>Explanation</b>	Failed to set the server parameter.
<b>Action</b>	Please contact your software supplier.

---

<b>INOXIE8332</b>	<b>The old server parameter could not be deleted</b>
<b>Explanation</b>	The old server parameter could not be deleted.
<b>Action</b>	Please contact your software supplier.
<b>INOXIE8333</b>	<b>An old TSD2 collection could not be deleted</b>
<b>Explanation</b>	An old TSD2 collection could not be deleted.
<b>Action</b>	Please contact your software supplier.
<b>INOXIE8334</b>	<b>The database contains data which uses lite mapping</b>
<b>Explanation</b>	The version to which the database should be upgraded does not support lite mapping.
<b>Action</b>	Please delete the data which uses lite mapping and start the upgrade again.
<b>INOXIE8335</b>	<b>Upgrade of metaschema failed with following response code RESPONSE.</b>
<b>Explanation</b>	The upgrade of the metaschema which was performed during upgrade of the database has failed with the specified response code.
<b>Action</b>	Please contact your software supplier.
<b>INOXIE8336</b>	<b>Upgrade is not supported</b>
<b>Explanation</b>	Upgrade is not supported.
<b>Action</b>	Select another version to upgrade the database.
<b>INOXIE8337</b>	<b>Downgrade is not supported</b>
<b>Explanation</b>	Downgrade to an older Tamino version is not supported.
<b>Action</b>	Please contact your software supplier.
<b>INOXIE8338</b>	<b>Data format 'VERSION' found in collection 'COLLECTION' doctype 'DOCTYPE'.</b>
<b>Explanation</b>	The data format found in the user collection is no longer supported.
<b>Action</b>	Please clean up the user collection.
<b>INOXIE8339</b>	<b>Unknown function</b>
<b>Explanation</b>	The provided function name is unknown.
<b>Action</b>	Check if you provided the correct function name and try again.

<b>INOXIE8340</b>	<b>Truncated index detected</b>
<b>Explanation</b>	An index containing truncated entries was detected at query execution time, though the Data Map had no information about truncation available at compile time. This may occur for an index that has been migrated from Tamino version 4.1.4. As a side effect of the failing query, the index has been marked as truncated in the Data Map.
<b>Action</b>	Repeat the query.
<b>INOXIE8341</b>	<b>Internal error</b>
<b>Explanation</b>	An internal error has occurred.
<b>Action</b>	Please contact your software supplier.
<b>INOXIE8342</b>	<b>Memory allocation failed</b>
<b>Explanation</b>	There was not enough main memory available to perform the request.
<b>Action</b>	Possibly the machine is overloaded. Try again later.
<b>INOXIE8343</b>	<b>Postprocessing not supported for non-XML text search</b>
<b>Explanation</b>	A query that contains a text search operator can be executed on a non-XML doctype only if a text index has been defined for that doctype and the query does not require postprocessing.
<b>Action</b>	Modify your schema definition to contain a non-XML text index or change query to avoid postprocessing.
<b>INOXIE8344</b>	<b>Internal error</b>
<b>Explanation</b>	An internal error has occurred.
<b>Action</b>	Please contact your software supplier.
<b>INOXIE8345</b>	<b>Illegal parent operator follows sort operator</b>
<b>Explanation</b>	A query contains a parent operator which might be applied to a node which serves as input for a sort operator. This is not allowed.
<b>Action</b>	Please change your query so that no parent operator can be applied to a sort input node.

---

<b>INOXIE8346</b>	<b>Malformed proximity expression</b>
<b>Explanation</b>	A subexpression of the query uses either the "adj" or the "near" operator, but there is no corresponding "~=" operator.
<b>Action</b>	Correct the query.
<b>INOXIE8347</b>	<b>Query not supported</b>
<b>Explanation</b>	The specified query is not supported.
<b>Action</b>	Change the query.
<b>INOXIE8348</b>	<b>Wrong arguments for function</b>
<b>Explanation</b>	The function cannot be applied on the current parm settings, i.e. number or type of arguments that a function is called with is not as expected by the function.
<b>Action</b>	Check either the XPath specification for the proper usage of XPath's built in functions or check the documentation for server extension functions.
<b>INOXIE8349</b>	<b>Maximum word length exceeded</b>
<b>Explanation</b>	Text searches are restricted to a maximum word length of 64 characters.
<b>Action</b>	Reduce the length of the search pattern inside the query.
<b>INOXIE8350</b>	<b>No whitespace search is supported with ~=</b>
<b>Explanation</b>	Whitespaces are ignored by a "~=" search, so searching for a whitespace is not possible.
<b>Action</b>	Use the "=" operator to find whitespaces.
<b>INOXIE8351</b>	<b>Wrong direction of result type</b>
<b>Explanation</b>	The result type must be output.
<b>Action</b>	Uninstall the function, change the signature of the external function, install the function again.
<b>INOXIE8352</b>	<b>Operator used outside a document</b>
<b>Explanation</b>	Some operators can only be used inside a document e.g. before/after.
<b>Action</b>	Do not use the operator outside of a document context.

<b>INOXIE8353</b>	<b>Invalid invocation of ino:fullscan</b>
<b>Explanation</b>	The ino:fullscan function can be used only on query level, it cannot be applied to subexpressions.
<b>Action</b>	Correct ino:fullscan invocation.
<b>INOXIE8354</b>	<b>Invalid invocation of ino:explain</b>
<b>Explanation</b>	The ino:explain function can be used only on query level, it can not be applied to subexpressions.
<b>Action</b>	Correct ino:explain invocation.
<b>INOXIE8355</b>	<b>Too many inter-document sort operators</b>
<b>Explanation</b>	The system can process only a single inter-document sort operator. Please note that a &quot;sortby&quot; applied to a root node is also an inter-document sort operator.
<b>Action</b>	Please change your query.
<b>INOXIE8356</b>	<b>Illegal inter-document sort operators</b>
<b>Explanation</b>	Within a query an inter-document sort operator must not follow an intra-document sort operator.
<b>Action</b>	Please change your query.
<b>INOXIE8357</b>	<b>Internal error</b>
<b>Explanation</b>	An internal error has occurred.
<b>Action</b>	Please contact your software supplier.
<b>INOXIE8358</b>	<b>Internal error</b>
<b>Explanation</b>	An internal error has occurred.
<b>Action</b>	Please contact your software supplier.
<b>INOXIE8359</b>	<b>Internal error</b>
<b>Explanation</b>	An internal error has occurred.
<b>Action</b>	Please contact your software supplier.

---

<b>INOXIE8360</b>	<b>Nodeset is empty</b>
<b>Explanation</b>	The current-node (.) or parent (..) operator was applied upon an empty nodeset during query evaluation.
<b>Action</b>	A subquery executed prior to the current-node or parent operation yielded an empty result.
<b>INOXIE8361</b>	<b>Invalid type occurred when executing query</b>
<b>Explanation</b>	Some query operations can only be applied upon objects of a specific type, e.g. current-node (.) or parent (..) only make sense when working upon nodes. This error may also occur when calling XPath functions upon a set of arguments they cannot be applied upon.
<b>Action</b>	Check whether . (=current node) or .. (= parent) are used in connection with nodes, and that an XPath function's usage corresponds to its type.
<b>INOXIE8362</b>	<b>Internal Error : Invalid Node</b>
<b>Explanation</b>	An invalid XML node was encountered during the evaluation of an XPath function.
<b>Action</b>	Please contact your software supplier.
<b>INOXIE8364</b>	<b>Conversion failed</b>
<b>Explanation</b>	In order to execute a query an invalid conversion was attempted. This happens e.g. if a numerical operation is applied upon data that cannot be converted to a number. This error occurs also if an operator requires two operands of the same type (e.g. between) and the operands are of different types.
<b>Action</b>	Check the operand's types.
<b>INOXIE8366</b>	<b>Wrong arguments for function</b>
<b>Explanation</b>	The function cannot be applied on the current parm settings, i.e. number or type of arguments that a function is called with is not as expected by the function.
<b>Action</b>	Check either the XPath specification for the proper usage of XPath's built in functions or check the documentation for server extension functions.
<b>INOXIE8367</b>	<b>Internal error : Missing root node</b>
<b>Explanation</b>	The query postprocessor encountered a missing node in the XPath parsing tree when evaluating an XPath expression.
<b>Action</b>	Please contact your software supplier.

<b>INOXIE8368</b>	<b>ICU collator definition failed</b>
<b>Explanation</b>	An error was received while opening an ICU collator.
<b>Action</b>	Please contact your software supplier.
<b>INOXIE8369</b>	<b>Right side of ~= must be a single string</b>
<b>Explanation</b>	The match operand requires an operand that evaluates to string on its right side.
<b>Action</b>	Check whether your idea of what match does is correct. It typically looks like list-of-nodes ~= 'pattern' or list-of-nodes ~= 'word' . If the right side of your match is detected dynamically from Tamino data, it does not evaluate to a string as you expected. If the right side of your match is given literally in the query, it might help to add quotes.
<b>INOXIE8371</b>	<b>Invalid comparison operator</b>
<b>Explanation</b>	Within 'adjacent' or 'near' statements, currently only the match comparison operator is allowed.
<b>Action</b>	Replace an equal by a match and a not-equal by a match and the XPath function 'not()'
<b>INOXIE8372</b>	<b>Too many match tokens</b>
<b>Explanation</b>	The right side of a ~= contains a string that gets tokenized in order to check the expression on the left side for the occurrence of these tokens in the given sequence. The tokenization must not lead to more than ten tokens.
<b>Action</b>	Shorten the pattern to avoid tokenization into more than ten tokens.
<b>INOXIE8374</b>	<b>Invalid Match Pattern</b>
<b>Explanation</b>	The string provided as the right side of a match (~=) must contain at least one character that is not a separation character, i.e. quote or comma. The string may contain wildcards (*), but only in the forms *x, x*, x*x, or *x*.
<b>Action</b>	Correct the pattern.
<b>INOXIE8375</b>	<b>Sortkey too long</b>
<b>Explanation</b>	The internally generated sort key is too long.
<b>Action</b>	Reduce the number of sort criteria.

---

<b>INOXIE8376</b>	<b>Duplicate in sort key</b>
<b>Explanation</b>	The system cannot handle sort key values which consist of more than a single node.
<b>Action</b>	Please try to fix your data or your query.
<b>INOXIE8378</b>	<b>Server extension returned binary data without setting media type</b>
<b>Explanation</b>	The media type must be defined when a server extension returns binary data.
<b>Action</b>	Use the method SxsSetProperty() with the property of SX_PROPERTY_RSP_MEDIATYPE to define the media type of the binary data.
<b>INOXIE8379</b>	<b>Internal error occurred during query processing: unknown request</b>
<b>Explanation</b>	An internal error has occurred.
<b>Action</b>	Please contact your software supplier.
<b>INOXII8302</b>	<b>Overflow during sorting</b>
<b>Explanation</b>	internal error
<b>Action</b>	Please contact your software supplier.
<b>INOXII8311</b>	<b>Version fromVersion is compatible with Version toVersion</b>
<b>Explanation</b>	The current version of the database is compatible with the selected version.
<b>Action</b>	None
<b>INOXII8317</b>	<b>Internal error during sorting</b>
<b>Explanation</b>	internal error
<b>Action</b>	Please contact your software supplier.
<b>INOXII8318</b>	<b>Locking conflict</b>
<b>Explanation</b>	internal error
<b>Action</b>	Please contact your software supplier.
<b>INOXII8323</b>	<b>Recreation of all indices started in collection COLLECTION, doctype DOCTYPE</b>
<b>Explanation</b>	The administrative command ino:RecreateIndex was issued.
<b>Action</b>	Be aware that the collection is not accessible until index recreation is completed.

**INOXII8324      Recreation of all indices in collection COLLECTION, doctype DOCTYPE terminated with code CODE**

**Explanation**      The administrative command ino:RecreateIndex terminated.

**Action**      Be aware that if the given return code is not 0, the index recreation has been rolled back.

**INOXII8325      Recreation of all text indices started in collection COLLECTION, doctype DOCTYPE**

**Explanation**      The administrative command ino:RecreateTextIndex was issued.

**Action**      Be aware that access to the collection is constricted until the operation is completed.

**INOXII8326      Recreation of all text indices in collection COLLECTION, doctype DOCTYPE terminated successfully**

**Explanation**      The administrative command ino:RecreateTextIndex completed.

**Action**      The collection is fully usable again.

**INOXII8327      Recreation of all text indices in collection COLLECTION, doctype DOCTYPE terminated with error CODE**

**Explanation**      The administrative command ino:RecreateTextIndex aborted due to the stated error code.

**Action**      Repair the indices via the administrative command ino:RepairIndex().

**INOXII8328      Repair indices started in collection COLLECTION, doctype DOCTYPE, mode MODE**

**Explanation**      The administrative command ino:RepairIndex was issued.

**Action**      Be aware that access to the collection is constricted until the operation is completed.

**INOXII8329      Repair indices in collection COLLECTION, doctype DOCTYPE, mode MODE terminated successfully**

**Explanation**      The administrative command ino:RepairIndex completed successfully.

**Action**      Note that if the mode was "drop", the indices have been dropped from the schema.

**INOXII8330      Repair indices in collection COLLECTION, doctype DOCTYPE, mode MODE terminated with error CODE**

**Explanation**      The administrative command ino:RepairIndex aborted due to the given error.

**Action**      Correct the problem if possible and repeat the command.

---

<b>INOXIW8373</b>	<b>The id() function is not supported</b>
<b>Explanation</b>	XPath describes the result of the id() function as being the node-set containing the elements in the same document as the context node that have a unique ID equal to any of the tokens in the id() function's argument list (see XPath 4.1). As specified in XPath, 5.2.1, a unique ID is the value of the attribute that is declared in the DTD as type ID. Since Tamino currently offers no means to declare attributes as type ID, applying the id() function makes no sense, its result will always be the empty node set.
<b>Action</b>	If some attribute 'att1' has the semantics of an ID, retrieving the node for which this attribute is set to a certain value, e.g. 'val1', is achieved via <code>//*[@att1="val1"]</code> .
<b>INOXIW8399</b>	<b>The required function has not been completely executed</b>
<b>Explanation</b>	See details in the warning line accompanying this message. Possible reasons for this warning are: a sort operation was performed based on an index, and that index contains truncated values. The result is sorted according to the truncated values, and not according to the real values.
<b>Action</b>	No action required, this is a warning only.
<b>INOXME8501</b>	<b>Memory allocation failed</b>
<b>Explanation</b>	Allocation of virtual memory failed.
<b>Action</b>	Either extend the amount of memory resources available for Tamino on your system or reduce resource consumption of Tamino, e.g. by using a smaller buffer pool.
<b>INOXME8502</b>	<b>Internal error: DBMS environment not found</b>
<b>Explanation</b>	The DBMS environment could not be found for X-Node - this is an internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXME8503</b>	<b>Invalid or unknown encoding found in input document</b>
<b>Explanation</b>	The encoding of the input document could not be recognized.
<b>Action</b>	Check your input document.
<b>INOXME8504</b>	<b>XML maximum request duration exceeded</b>
<b>Explanation</b>	The request was cancelled because the maximum request duration was exceeded.
<b>Action</b>	Either improve the request performance by tuning the database, or increase the value of the "XML maximum request duration" server parameter.

<b>INOXME8505</b>	<b>ODBC error occurred</b>
<b>Explanation</b>	While issuing a command via ODBC to the SQL system an error occurred.
<b>Action</b>	The text of the external error is provided in the extended message.
<b>INOXME8506</b>	<b>Adabas error occurred</b>
<b>Explanation</b>	An error occurred when accessing an Adabas database via X-Node.
<b>Action</b>	Check the Adabas documentation for the reason for the reported error code.
<b>INOXME8507</b>	<b>Maximum parallel databases for session reached</b>
<b>Explanation</b>	The number of parallel databases allowed for one session has been reached.
<b>Action</b>	No action required.
<b>INOXME8508</b>	<b>X-Node licensing error, insufficient rights</b>
<b>Explanation</b>	An attempt was made to access an X-Node datasource or an Adabas version that has not been licensed.
<b>Action</b>	Check that all datasources defined in the schema are correct, or upgrade the X-Node license.
<b>INOXME8509</b>	<b>X-Node datasource mismatch</b>
<b>Explanation</b>	The datasource DBMS name given (implicitly or explicitly) in the schema does not match that of the DBMS vendor to which this datasource has attempted to connect.
<b>Action</b>	The DBMS name must be the same at execution time as it was at schema creation time.
<b>INOXME8510</b>	<b>Request has been cancelled</b>
<b>Explanation</b>	The request has been cancelled by the operator or accessor.
<b>Action</b>	No action required.
<b>INOXME8511</b>	<b>Internal maximum for parallel ODBC access reached</b>
<b>Explanation</b>	Within one transaction, Tamino keeps track of parallel ODBC access. An internal list reached its maximum.
<b>Action</b>	No action required.

---

<b>INOXME8512</b>	<b>Invalid request ID</b>
<b>Explanation</b>	The given ID is invalid either because the respective request is already terminated or because it is invalid as an accessor-provided unique identifier.
<b>Action</b>	No action required, if the request is already terminated. Otherwise the request ID cannot be used within <code>_admin=ino:Accessor("cancelRequest",...)</code> .
<b>INOXME8513</b>	<b>Cannot create unique text index</b>
<b>Explanation</b>	A unique index cannot be set because duplicate entries are stored in the translated word table.
<b>Action</b>	Please contact your software supplier.
<b>INOXME8514</b>	<b>X-Node SQL column not found or authorization error</b>
<b>Explanation</b>	The specified column was not found in the SQL table or you are not authorized to access the column/table.
<b>Action</b>	Correct the schema.
<b>INOXME8515</b>	<b>X-Node SQL table not found or authorization error</b>
<b>Explanation</b>	The error may occur because: 1. the specified SQL table/schema was not found OR 2. you are not authorized to access the table.
<b>Action</b>	Correct the schema.
<b>INOXME8516</b>	<b>Internal error: cannot lock collection</b>
<b>Explanation</b>	Migration attempted to lock a collection for which it is not possible.
<b>Action</b>	Please contact your software supplier.
<b>INOXME8517</b>	<b>Unlock of collection failed</b>
<b>Explanation</b>	It was not possible to unlock the specified collection.
<b>Action</b>	Please contact your software supplier.
<b>INOXME8518</b>	<b>Unlock of collection failed because the lock is in an incorrect state</b>
<b>Explanation</b>	It was not possible to unlock the specified collection because the lock is in an incorrect state.
<b>Action</b>	Please contact your software supplier.

<b>INOXME8519</b>	<b>Cannot cancel a mass load/unload as a session user</b>
<b>Explanation</b>	Cancelling of a mass load/unload in a session is not possible.
<b>Action</b>	Issue the administration command in an anonymous session.
<b>INOXME8520</b>	<b>Error writing to temporary file during data load</b>
<b>Explanation</b>	An error occurred while writing to a temporary file during a data load request.
<b>Action</b>	Check that temporary directory (\$SAGTMP or \$TMP) is writable and that disk space is available.
<b>INOXME8521</b>	<b>Invalid or unsupported datastore format detected during data load</b>
<b>Explanation</b>	An internal error occurred during data load.
<b>Action</b>	Please contact your software supplier.
<b>INOXME8522</b>	<b>Unsupported datastore descriptor type detected during data load</b>
<b>Explanation</b>	An internal error occurred while data was being loaded.
<b>Action</b>	Please contact your software supplier.
<b>INOXME8523</b>	<b>Unsupported datastore request detected during data load</b>
<b>Explanation</b>	An internal error occurred while data was being loaded.
<b>Action</b>	Please contact your software supplier.
<b>INOXME8524</b>	<b>Value exceeding maximum length detected during data load</b>
<b>Explanation</b>	An internal error occurred while data was being loaded.
<b>Action</b>	Please contact your software supplier.
<b>INOXME8525</b>	<b>Internal error detected in data load module</b>
<b>Explanation</b>	An internal error occurred while data was being loaded.
<b>Action</b>	Please contact your software supplier.
<b>INOXME8527</b>	<b>Data loading/unloading for doctype not supported</b>
<b>Explanation</b>	For data loading: - doctypes of map-type NonXML or Lite are not supported. - doctypes created in Tamino version prior to v2.3 are not supported.  For data unloading: - doc-types of map-type NonXML are not supported
<b>Action</b>	Either migrate your doctype to v2.3 or later or use the XML loaders.

---

<b>INOXME8528</b>	<b>Data loading aborted; cannot create temporary files</b>
<b>Explanation</b>	The data loader was unable to create temporary files.
<b>Action</b>	Using the Tamino Manager or the batch utility "argbatch", check that the settings for the temporary location are correct and that there is space available.
<b>INOXME8529</b>	<b>Data loading into multiple doctypes not supported</b>
<b>Explanation</b>	Data loading is only possible into the collection/doctype given when the data loader is started.
<b>Action</b>	Remove documents from the input file that do not belong to the doctype specified at the start-up of the XML data loader.
<b>INOXME8531</b>	<b>Data load rejected document</b>
<b>Explanation</b>	An error was found while processing the document during a data load operation.
<b>Action</b>	Correct and restart the data loader.
<b>INOXME8536</b>	<b>XML data load recovery of doctype doctype in collection collection was unsuccessful</b>
<b>Explanation</b>	During autorestart, it was detected that a XML data load operation was active in the previous Tamino server session. This message provides information that Tamino could not restore the doctype to the state before the XML data load operation was initiated.
<b>Action</b>	Perform a restore/regenerate of the Tamino database to get it into a consistent state.
<b>INOXME8539</b>	<b>XML data loading failed</b>
<b>Explanation</b>	An XML data load operation was aborted or stopped.
<b>Action</b>	Depending on the reason for the failure, correct and re-process.
<b>INOXME8540</b>	<b>Data loading aborted with rejects</b>
<b>Explanation</b>	Data loading has aborted because a reject was found and the norejects option was chosen.
<b>Action</b>	Either correct the rejected document or load without setting the norejects option.
<b>INOXME8543</b>	<b>Internal error - unexpected response occurred in call to function function, function gave response code(s) codes</b>
<b>Explanation</b>	An internal error has occurred.
<b>Action</b>	Please contact your software supplier with the exact message (the function and codes are important).

<b>INOXME8544</b>	<b>Query using "mapping-type=object" cannot be evaluated</b>
<b>Explanation</b>	The query cannot be evaluated because "mapping-type=object" is involved and the post-processor is needed, or because the "mapping-type=object" node is used within a filter.
<b>Action</b>	Supply a correct query.
<b>INOXME8546</b>	<b>Feature not implemented</b>
<b>Explanation</b>	You attempted to use a feature which is not available in the current environment.
<b>Action</b>	Please contact your software supplier.
<b>INOXME8547</b>	<b>Invalid syntax of _XQL command inside _HTMLREQ</b>
<b>Explanation</b>	An error occurred when converting an _HTMLREQ=_XQL request to an _XQL request.
<b>Action</b>	Check the appropriate documentation.
<b>INOXME8548</b>	<b>Invalid syntax of _PROCESS command inside _HTMLREQ</b>
<b>Explanation</b>	An error occurred when converting an _HTMLREQ=_PROCESS request to a _PROCESS request.
<b>Action</b>	Check the appropriate documentation.
<b>INOXME8549</b>	<b>Doctype not found</b>
<b>Explanation</b>	The doctype indicated in the ino:messageline could not be found during an _UNDEFINE request.
<b>Action</b>	Check the specified name.
<b>INOXME8551</b>	<b>Invalid doctype</b>
<b>Explanation</b>	Storing or deleting documents in the collection "ino:collection" is not permitted.
<b>Action</b>	Check the collection name specified in the request.
<b>INOXME8552</b>	<b>Not a valid request</b>
<b>Explanation</b>	The request has been rejected due to invalid or missing parameters.
<b>Action</b>	Check the request parameters using supplementary error diagnostics in other messages.

---

<b>INOXME8554</b>	<b>No message received</b>
<b>Explanation</b>	The request did not specify any supported operation or command.
<b>Action</b>	Check the parameters of the request.
<b>INOXME8555</b>	<b>Session error occurred</b>
<b>Explanation</b>	An error occurred when attempting to establish a session context.
<b>Action</b>	Check the supplementary diagnostic message for a detailed explanation.
<b>INOXME8557</b>	<b>Request rejected because a deprecated feature is used</b>
<b>Explanation</b>	The used feature will not be supported in the next version.
<b>Action</b>	Change the server parameter to allow and log deprecated features.
<b>INOXME8558</b>	<b>Error during commit in user transaction</b>
<b>Explanation</b>	A user transaction received an error during commit processing.
<b>Action</b>	The error has to be handled in your application.
<b>INOXME8559</b>	<b>Error during rollback of user transaction</b>
<b>Explanation</b>	A user transaction has been rolled back due to an error. However, the indicated error occurred.
<b>Action</b>	Please contact your system administrator.
<b>INOXME8560</b>	<b>Failed to allocate SMP key</b>
<b>Explanation</b>	An internal error occurred when attempting to allocate a key for thread local storage.
<b>Action</b>	Please contact your system administrator.
<b>INOXME8561</b>	<b>Failed to deallocate SMP key</b>
<b>Explanation</b>	An internal error occurred when attempting to release a key for thread local storage.
<b>Action</b>	Please contact your system administrator.
<b>INOXME8562</b>	<b>Invalid handle</b>
<b>Explanation</b>	Internal error: an invalid handle was passed to an internal interface.
<b>Action</b>	Please contact your system administrator.

<b>INOXME8563</b>	<b>Invalid parameter</b>
<b>Explanation</b>	Internal error: an invalid parameter was passed to an internal interface.
<b>Action</b>	Please contact your system administrator.
<b>INOXME8564</b>	<b>Illegal load factor</b>
<b>Explanation</b>	An internal error occurred when creating a hash map.
<b>Action</b>	Please contact your system administrator.
<b>INOXME8565</b>	<b>Illegal initial capacity</b>
<b>Explanation</b>	An internal error occurred when creating a hash map.
<b>Action</b>	Please contact your system administrator.
<b>INOXME8566</b>	<b>Duplicate key</b>
<b>Explanation</b>	An attempt was made to store the same key twice in a hash map.
<b>Action</b>	Please contact your system administrator.
<b>INOXME8570</b>	<b>Locking failed during data load operation</b>
<b>Explanation</b>	The specified collection or doctype could not be locked.
<b>Action</b>	Check the parameters of the data load request.
<b>INOXME8596</b>	<b>Internal error in locking</b>
<b>Explanation</b>	An unexpected server status caused a lock operation failure.
<b>Action</b>	Please contact your software supplier.
<b>INOXME8598</b>	<b>Access violation</b>
<b>Explanation</b>	The request was rejected due to insufficient access permissions.
<b>Action</b>	Check if the request was as intended and if so, try to get the required access privileges from the system administrator.
<b>INOXME8599</b>	<b>Internal error</b>
<b>Explanation</b>	An internal error has occurred.
<b>Action</b>	Please contact your software supplier.

---

<b>INOXMF8530</b>	<b>Internal error occurred during data loading</b>
<b>Explanation</b>	An internal error was detected while data was being loaded.
<b>Action</b>	Please contact your software supplier.
<b>INOXMI8532</b>	<b>XML data load recovery initiated</b>
<b>Explanation</b>	During autorestart, it was detected that a XML data load operation was active in the previous Tamino server session. This message defines the start of recovery handling for cleaning up anything that was left over after the data load operation.
<b>Action</b>	No action required.
<b>INOXMI8533</b>	<b>XML data load recovery completed</b>
<b>Explanation</b>	During autorestart, it was detected that a XML data load operation was active in the previous Tamino server session. This message defines the completion of recovery handling for cleaning up anything that was left over after the data load operation.
<b>Action</b>	No action required.
<b>INOXMI8534</b>	<b>XML data load recovery initiated for doctype doctype in collection collection</b>
<b>Explanation</b>	During autorestart, it was detected that a XML data load operation was active in the previous Tamino server session. This message provides information about which doctypes are being recovered.
<b>Action</b>	No action required.
<b>INOXMI8535</b>	<b>XML data load recovery of doctype doctype in collection collection completed successfully</b>
<b>Explanation</b>	During autorestart, it was detected that a XML data load operation was active in the previous Tamino server session. This message provides information that Tamino has successfully restored the doctype to the state before the XML data load operation was initiated.
<b>Action</b>	No action required.
<b>INOXMI8537</b>	<b>XML data loading initiated for doctype doctype of collection collection</b>
<b>Explanation</b>	This is an information message to indicate the start of XML data load operation.
<b>Action</b>	No action required.

<b>INOXMI8538</b>	<b>XML data loading completed, number of documents processed docsproc, loaded docsload, rejected docsrejected</b>
<b>Explanation</b>	This is an information message to indicate the end of an XML data load operation.
<b>Action</b>	Depending on if there were documents rejected, these may need to be investigated and re-processed.
<b>INOXMV8550</b>	<b>Deprecated feature used: feature</b>
<b>Explanation</b>	The request uses a feature which is planned to be removed in the next product version.
<b>Action</b>	Do not use the deprecated feature.
<b>INOXMW8526</b>	<b>Failed to write XML request log to path</b>
<b>Explanation</b>	An error occurred when attempting to write the XML request log to given location.
<b>Action</b>	Check the location for possible reasons such as: a non-existing XML request log folder may have been specified, the directory cannot be accessed, or the disk is full.
<b>INOXMW8545</b>	<b>ino:docname uniqueness is not removed in downgrade</b>
<b>Explanation</b>	The downgrade does not allow the uniqueness of ino:docnames to be removed.
<b>Action</b>	No action required.
<b>INOXMW8571</b>	<b>Request logging was switched off dynamically due to IO errors</b>
<b>Explanation</b>	Probably the disk is full.
<b>Action</b>	Check the disk. Except for request logging, the Tamino server continues operation.
<b>INOXPE8700</b>	<b>Internal error: inconsistent document retrieval</b>
<b>Explanation</b>	The database storage of the retrieved document is inconsistent.
<b>Action</b>	Please contact your software supplier.
<b>INOXPE8701</b>	<b>Memory allocation failed</b>
<b>Explanation</b>	There was not enough main memory available to perform the request.
<b>Action</b>	Possibly the machine is overloaded. Try again later.

---

<b>INOXPE8702</b>	<b>Invalid document prolog</b>
<b>Explanation</b>	Invalid document prolog found in the file to be loaded.
<b>Action</b>	Please correct the document prolog.
<b>INOXPE8703</b>	<b>Invalid document declaration or more than one declaration found in the file to be loaded</b>
<b>Explanation</b>	Invalid document declaration or more than one declaration found in the file to be loaded.
<b>Action</b>	Correct the document declaration or remove all declarations except for the first.
<b>INOXPE8704</b>	<b>Unknown encoding found</b>
<b>Explanation</b>	Unknown encoding found.
<b>Action</b>	Please correct the document instance.
<b>INOXPE8705</b>	<b>Incompatible encoding found</b>
<b>Explanation</b>	The given encoding isn't supported yet.
<b>Action</b>	Please use another encoding.
<b>INOXPE8706</b>	<b>Entity found twice</b>
<b>Explanation</b>	An entity with same name was found twice.
<b>Action</b>	Please remove one of these entities.
<b>INOXPE8707</b>	<b>Wrong entity definition</b>
<b>Explanation</b>	The definition of an entity isn't correct.
<b>Action</b>	Please correct the entity definition.
<b>INOXPE8708</b>	<b>Document without content</b>
<b>Explanation</b>	An empty document cannot be loaded.
<b>Action</b>	Please provide the document with contents.
<b>INOXPE8709</b>	<b>Encoding not supported</b>
<b>Explanation</b>	The given encoding isn't supported yet.
<b>Action</b>	Please use another encoding.

<b>INOXPE8710</b>	<b>Invalid token found or document incomplete</b>
<b>Explanation</b>	Invalid token found or the document is incomplete.
<b>Action</b>	Please correct the document.
<b>INOXPE8711</b>	<b>Document not well-formed</b>
<b>Explanation</b>	The document to be loaded isn't well-formed.
<b>Action</b>	Please correct the document.
<b>INOXPE8712</b>	<b>Invalid element name</b>
<b>Explanation</b>	The name of the element is either too long or not correct.
<b>Action</b>	Please correct the document.
<b>INOXPE8713</b>	<b>Invalid attribute name</b>
<b>Explanation</b>	The name of the attribute is either too long or not correct.
<b>Action</b>	Please correct the document.
<b>INOXPE8714</b>	<b>Invalid document ID (ino:id) specified</b>
<b>Explanation</b>	The given document ID (ino:id) is either not numeric or not available.
<b>Action</b>	Please correct the document.
<b>INOXPE8715</b>	<b>Inserting or changing a document is forbidden</b>
<b>Explanation</b>	It isn't permitted when using this doctype to insert or to change documents.
<b>Action</b>	Please contact your system administrator.
<b>INOXPE8716</b>	<b>Inserting a document is forbidden</b>
<b>Explanation</b>	It isn't permitted when using this doctype to insert a new document.
<b>Action</b>	Please contact your system administrator.
<b>INOXPE8717</b>	<b>Changing a document is forbidden</b>
<b>Explanation</b>	It isn't permitted while using this doctype to change a document.
<b>Action</b>	Please contact your system administrator.

---

<b>INOXPE8718</b>	<b>Document incomplete</b>
<b>Explanation</b>	The document to be loaded is incomplete.
<b>Action</b>	Please correct the document.
<b>INOXPE8719</b>	<b>Document contains invalid character reference</b>
<b>Explanation</b>	The document contains an invalid character reference.
<b>Action</b>	Please correct the document.
<b>INOXPE8720</b>	<b>Document contains invalid entity reference</b>
<b>Explanation</b>	The document contains a reference to an entity which wasn't defined before.
<b>Action</b>	Please correct the document.
<b>INOXPE8721</b>	<b>Root element does not match doctype declaration</b>
<b>Explanation</b>	The given root element doesn't correspond to the root element of the used doctype.
<b>Action</b>	Please correct the document.
<b>INOXPE8722</b>	<b>Element with wrong obj-type encountered</b>
<b>Explanation</b>	The given element is defined in the schema as an attribute.
<b>Action</b>	Correct either the document or the accompanying schema.
<b>INOXPE8723</b>	<b>Attribute with wrong obj-type encountered</b>
<b>Explanation</b>	The given attribute is defined in the schema as an element.
<b>Action</b>	Correct either the document or the accompanying schema.
<b>INOXPE8724</b>	<b>Invalid attribute value encountered</b>
<b>Explanation</b>	The value of the attribute contains contents which aren't permitted.
<b>Action</b>	Please correct the document.
<b>INOXPE8725</b>	<b>Attribute was found twice</b>
<b>Explanation</b>	An attribute with same name was found twice.
<b>Action</b>	Please remove one of these attributes.

<b>INOXPE8726</b>	<b>Occurrence count does not match multiplicity option</b>
<b>Explanation</b>	The occurrence count of an element or attribute in an XML instance does not match the multiplicity option specified in the schema.
<b>Action</b>	Please correct the document.
<b>INOXPE8727</b>	<b>Document structure does not match schema definition (choice)</b>
<b>Explanation</b>	The document structure does not match the schema definition for the choice case.
<b>Action</b>	Please correct the document.
<b>INOXPE8728</b>	<b>Internal error: parent object not found</b>
<b>Explanation</b>	Accompanying parent object couldn't be found.
<b>Action</b>	Please contact your system administrator.
<b>INOXPE8729</b>	<b>Unclosed CDATA section detected</b>
<b>Explanation</b>	Unclosed CDATA section detected.
<b>Action</b>	Please correct the document.
<b>INOXPE8730</b>	<b>Required child object not specified</b>
<b>Explanation</b>	An element or an attribute which is defined in the schema as mandatory wasn't specified in the document.
<b>Action</b>	Please correct the document.
<b>INOXPE8731</b>	<b>Internal error: Parse in progress</b>
<b>Explanation</b>	The attempt was made to parse a second document while still parsing the first document.
<b>Action</b>	Please contact your system administrator.
<b>INOXPE8732</b>	<b>Value too long</b>
<b>Explanation</b>	The value of a numeric node or of a node mapped to an external datasource or of a node with search type STANDARD is too long.
<b>Action</b>	Please shorten the corresponding value.

---

<b>INOXPE8733</b>	<b>Value not numeric</b>
<b>Explanation</b>	The value for an object with an numeric datatype is not numeric.
<b>Action</b>	Please correct the document.
<b>INOXPE8734</b>	<b>Numeric value too large</b>
<b>Explanation</b>	The value of an object with a numeric datatype is too large.
<b>Action</b>	Please shorten the corresponding value.
<b>INOXPE8735</b>	<b>Insufficient space to convert data according to encoding</b>
<b>Explanation</b>	The length of data in an attribute/element that is defined to AdaField exceeds the defined length in the schema.
<b>Action</b>	Correct either the XML input data or modify the schema to increase the defined length.
<b>INOXPE8736</b>	<b>Internal error: buffer exceeded</b>
<b>Explanation</b>	For InfoFile mapping, the size of a document or the size of parts of a document that are mapped to any InfoField construct (like InfoArray) is limited to 64KB at the node level where map type InfoFile is specified. If there is no node with an explicit map type of InfoFile, the limit of 64KB applies to the root node.
<b>Action</b>	Reduce the number of nodes that are mapped to InfoField constructs. Use map type Native instead.
<b>INOXPE8737</b>	<b>Invalid document update attempted</b>
<b>Explanation</b>	The request tried to modify the document such that it would have generated an SQL UPDATE statement without a WHERE clause. This is not allowed.
<b>Action</b>	To accomplish this, delete the document and insert a new document instead of updating the document.
<b>INOXPE8738</b>	<b>Only a single document may be processed.</b>
<b>Explanation</b>	If the document name or the document ID is given, only a single document can be processed.
<b>Action</b>	Please remove additional documents.

<b>INOXPE8740</b>	<b>Internal error in document serialization module detected</b>
<b>Explanation</b>	An internal error occurred in the serialization module.
<b>Action</b>	Please contact your software supplier.
<b>INOXPE8741</b>	<b>Internal error in document serialization module detected</b>
<b>Explanation</b>	An internal error occurred in serialization module.
<b>Action</b>	Please contact your software supplier.
<b>INOXPE8742</b>	<b>Recursion of entities detected</b>
<b>Explanation</b>	During the processing of references to entities a recursion was discovered.
<b>Action</b>	Please check the entity definition and correct the document.
<b>INOXPE8743</b>	<b>Entity stack overflow</b>
<b>Explanation</b>	Entity stack overflow.
<b>Action</b>	Please reduce the nested entity references.
<b>INOXPE8744</b>	<b>Internal error in index processing module detected</b>
<b>Explanation</b>	An internal error occurred in the index processing module.
<b>Action</b>	Please contact your software supplier.
<b>INOXPE8745</b>	<b>Internal error in index processing module detected</b>
<b>Explanation</b>	An internal error occurred in the index processing module.
<b>Action</b>	Please contact your software supplier.
<b>INOXPE8746</b>	<b>Internal error</b>
<b>Explanation</b>	An internal error occurred during document processing.
<b>Action</b>	Please contact your software supplier.
<b>INOXPE8747</b>	<b>Internal error in index processing module detected</b>
<b>Explanation</b>	An internal error occurred in the index processing module.
<b>Action</b>	Please contact your software supplier.

---

<b>INOXPE8748</b>	<b>Internal error in document processing module detected</b>
<b>Explanation</b>	Processing aborted due to a server internal error.
<b>Action</b>	Please contact your software supplier.
<b>INOXPE8749</b>	<b>Access to XNODEs / trigger functions during massload is not allowed</b>
<b>Explanation</b>	The access to parts of the schema that specify X-Node or trigger function usage is not allowed when loading data with the Tamino Data Loader.
<b>Action</b>	Set "ignore update" for the X-Node or trigger function parts of the schema or use the concurrentWrite option of the Tamino Data Loader.
<b>INOXPE8750</b>	<b>Tag or attribute name is too long</b>
<b>Explanation</b>	The number of characters of a tag or attribute name exceeds the maximum supported value.
<b>Action</b>	Shorten the name of the tag or attribute in question.
<b>INOXPE8751</b>	<b>Storing an object of this mapping type is not permitted</b>
<b>Explanation</b>	Storing an object which is linked to another object is not permitted.
<b>Action</b>	Please correct the document.
<b>INOXPE8752</b>	<b>Document not found in database</b>
<b>Explanation</b>	A document referenced by the current command was not found in the database, because it was deleted by another concurrent access.
<b>Action</b>	Re-issue the command.
<b>INOXPE8753</b>	<b>The element has contents although it is defined with object type "EMPTY"</b>
<b>Explanation</b>	The element has contents although it is defined with object type "EMPTY".
<b>Action</b>	Please correct either the document instance or the schema definition.
<b>INOXPE8754</b>	<b>Comments are not allowed between documents</b>
<b>Explanation</b>	The input file contains a comment between two documents. This is not allowed.
<b>Action</b>	Remove the comment.

<b>INOXPE8755</b>	<b>Invalid document name (ino:docname) specified</b>
<b>Explanation</b>	The document name given in the attribute ino:docname is empty.
<b>Action</b>	Either provide a document name in the attribute ino:docname or remove the ino:docname attribute.
<b>INOXPE8756</b>	<b>Invalid versioning mode</b>
<b>Explanation</b>	The document could not be stored, because the auto-version mode is invalid or the document is not in the correct versioning state.
<b>Action</b>	Make sure that the document is in the checkout-checkin auto-version mode and that the document is not checked out.
<b>INOXQE6250</b>	<b>Feature not implemented</b>
<b>Explanation</b>	The feature you tried to use is not implemented yet.
<b>Action</b>	Try an other method.
<b>INOXQE6251</b>	<b>internal exception</b>
<b>Explanation</b>	An internal exception has occurred.
<b>Action</b>	Please contact your software supplier.
<b>INOXQE6252</b>	<b>Type exception: non-atomic type in element/attribute</b>
<b>Explanation</b>	This error occurs if a non-atomizable type is encountered where a simple type is required, e.g. an element node belonging to a type that allows sub-elements is provided as a parameter for a function that expects a string.
<b>Action</b>	Check the operand's types or adopt the schema definition.
<b>INOXQE6253</b>	<b>Type exception: sequence occurred where atomic value required</b>
<b>Explanation</b>	Some functions and operators do not operate on sequences that contain that more than one entry.
<b>Action</b>	Check the operand types.
<b>INOXQE6254</b>	<b>Type can not be compared / sorted</b>
<b>Explanation</b>	Only totally ordered types such as numeric types, string types, boolean, dateTime, date and time can be compared and sorted.
<b>Action</b>	Try to use a totally ordered type or convert into such a type.

---

<b>INOXQE6255</b>	<b>Invalid argument to aggregation function</b>
<b>Explanation</b>	The atomic values in a sequence upon which the avg() or sum() function is applied must have a common super-type that is either numeric or a date/time type.
<b>Action</b>	Check the values in the sequence.
<b>INOXQE6256</b>	<b>Conversion detected an invalid value</b>
<b>Explanation</b>	An invalid value could not be converted.
<b>Action</b>	Check the query and the data.
<b>INOXQE6257</b>	<b>Invalid type denotation for atomic type</b>
<b>Explanation</b>	A string provided as an atomic type denotation, for example with a user-defined function, does not denote a type.
<b>Action</b>	Use proper type denotations, for example xs:integer or xdt:anyAtomicType.
<b>INOXQE6261</b>	<b>Duplicate function definition</b>
<b>Explanation</b>	A query or a module definition contains two definitions of the same function, or an imported module defines a function that is already defined.
<b>Action</b>	Remove the extra function definition.
<b>INOXQE6262</b>	<b>Module not found</b>
<b>Explanation</b>	An XQuery module import directive could not be satisfied, because there is no such module.
<b>Action</b>	Correct the import directive, or load an appropriate module definition.
<b>INOXQE6263</b>	<b>Invalid server extension type detected</b>
<b>Explanation</b>	A server extension function is called that returns or consumes a type that is not supported by the XQuery processor.
<b>Action</b>	Check the signature of the called server extension function.
<b>INOXQE6264</b>	<b>Cyclic module import</b>
<b>Explanation</b>	A module M may not import another module that directly or indirectly imports module M.
<b>Action</b>	Remove the cycle from the module import dependencies.

<b>INOXQE6300</b>	<b>Internal error</b>
<b>Explanation</b>	An internal error has occurred in the XQuery execution engine.
<b>Action</b>	Please contact your software supplier.
<b>INOXQE6301</b>	<b>Runtime type exception</b>
<b>Explanation</b>	An invalid type was detected at XQuery execution time.
<b>Action</b>	Correct the query.
<b>INOXQE6302</b>	<b>XQuery feature not implemented</b>
<b>Explanation</b>	The query uses an unimplemented language feature. Please see the documentation and release notes for current product limitations.
<b>Action</b>	Change the query.
<b>INOXQE6303</b>	<b>Invalid position for range</b>
<b>Explanation</b>	The first position parameter for 'range' is negative or zero.
<b>Action</b>	Check the query and data to find the wrong position value.
<b>INOXQE6304</b>	<b>Internal error: buffer overflow</b>
<b>Explanation</b>	An intermediate result is too large.
<b>Action</b>	Please contact your software supplier.
<b>INOXQE6305</b>	<b>Division by zero</b>
<b>Explanation</b>	A division by zero was attempted (not defined mathematically).
<b>Action</b>	Make sure that a divide by zero does not occur.
<b>INOXQE6306</b>	<b>numeric overflow has occurred</b>
<b>Explanation</b>	An arithmetic operation yielded a result which is not representable with the data type.
<b>Action</b>	Make sure that results do not exceed the representable range.
<b>INOXQE6307</b>	<b>duplicate attribute name occurred in element constructor</b>
<b>Explanation</b>	An element constructor contained multiple attributes of the same name.
<b>Action</b>	Make sure that attribute names of constructed elements are unique.

---

<b>INOXQE6308</b>	<b>sort utility failed</b>
<b>Explanation</b>	An explicit or implicit invocation of the sorting utility failed. This may occur due to insufficient disk space for temporary files.
<b>Action</b>	Check whether sufficient disk space is available for temporary files.
<b>INOXQE6309</b>	<b>namespace prefix conflict between constructed element and attribute</b>
<b>Explanation</b>	A constructed element contained a conflicting namespace declaration while an attribute was added to it.
<b>Action</b>	Use a different namespace prefix in the attribute's target environment.
<b>INOXQE6310</b>	<b>Processing of data with X-Tension or X-Node mapping is not supported by XQuery</b>
<b>Explanation</b>	Currently no data with X-Tension (server extension) or X-Node mapping can be accessed by an XQuery query.
<b>Action</b>	Formulate your query using Tamino X-Query instead of XQuery.
<b>INOXQE6311</b>	<b>temporary file access failed</b>
<b>Explanation</b>	A problem has occurred while accessing a temporary disk file. This may occur due to insufficient disk space for temporary files.
<b>Action</b>	Check whether sufficient disk space is available for temporary files.
<b>INOXQE6312</b>	<b>Document access error</b>
<b>Explanation</b>	A document did not exist though it was part of a query result. This situation can occur when a query is executed with isolation level "uncommitted document", while another transaction has been rolled back after concurrently inserting the document.
<b>Action</b>	Retry the query or use an isolation level different from "uncommitted document".
<b>INOXQE6313</b>	<b>Runtime type exception: non-atomic type in element/attribute</b>
<b>Explanation</b>	This error occurs if a non-atomizable type is encountered where a simple type is required, e.g. an element node belonging to a type that allows sub-elements is provided as a parameter for a function that expects a string.
<b>Action</b>	Check the operand's types or adopt the schema definition.

<b>INOXQE6314</b>	<b>Value cannot be converted</b>
<b>Explanation</b>	The textual representation of the value does not match the type it is being converted to.
<b>Action</b>	Check the query and the data.
<b>INOXQE6315</b>	<b>Runtime type exception: sequence occurred where atomic value required</b>
<b>Explanation</b>	Some functions and operators do not operate on sequences that contain more than one entry.
<b>Action</b>	Check the operand's types.
<b>INOXQE6316</b>	<b>Run-time encountered non-comparable type</b>
<b>Explanation</b>	Only totally ordered types such as numeric types, string types, boolean, dateTime, date and time can be compared and sorted.
<b>Action</b>	Try to use a totally ordered type or convert into such a type.
<b>INOXQE6317</b>	<b>Run-time encountered invalid argument to aggregation function</b>
<b>Explanation</b>	The atomic values in a sequence upon which the avg() or sum() function is applied must have a common super-type that is either numeric or a date/time type.
<b>Action</b>	Check the values in the sequence.
<b>INOXQE6318</b>	<b>Runtime type exception: empty sequence occurred where atomic value required</b>
<b>Explanation</b>	Some functions and operators do not operate on an empty sequence.
<b>Action</b>	Check the operand's types.
<b>INOXQE6319</b>	<b>Invalid simple type detected</b>
<b>Explanation</b>	In an expression, an invalid simple type was used.
<b>Action</b>	Check the actual type and the expected type with your query.
<b>INOXQE6320</b>	<b>Invalid combination of operand types for an arithmetic operation</b>
<b>Explanation</b>	The type of at least one operand is not valid for an arithmetic operation.
<b>Action</b>	Check where the types can occur in your query and correct it.

---

<b>INOXQE6321</b>	<b>Runtime type exception: invalid node-type</b>
<b>Explanation</b>	Some operations only operate on nodes of certain types.
<b>Action</b>	Check the node's type. Correct the path used to obtain the node.
<b>INOXQE6322</b>	<b>Non-simple type detected</b>
<b>Explanation</b>	A non-simple type was detected where a simple type is required.
<b>Action</b>	Check your query and the data to find a type mismatch.
<b>INOXQE6323</b>	<b>Conversion: facet 'minLength' was violated by a value</b>
<b>Explanation</b>	The value to be converted was too short.
<b>Action</b>	Check the query and the data.
<b>INOXQE6324</b>	<b>Incompatible types for cast operation</b>
<b>Explanation</b>	The source type cannot be cast to the target type.
<b>Action</b>	Check the type of the argument to the cast.
<b>INOXQE6325</b>	<b>Conversion error for comparison</b>
<b>Explanation</b>	During the execution of a comparison, the values must be converted to a common type. This conversion failed, either because of incomparable types or because of invalid data.
<b>Action</b>	Check your query and data to find the mismatch.
<b>INOXQE6326</b>	<b>Comparison undefined</b>
<b>Explanation</b>	Some data types cannot be compared because they are partially ordered.
<b>Action</b>	Check your query and data for undefined comparisons.
<b>INOXQE6327</b>	<b>Invalid last position for range</b>
<b>Explanation</b>	The last position parameter for 'range' is smaller than the first and is not -1.
<b>Action</b>	Check the query and data to find the wrong position value.
<b>INOXQE6328</b>	<b>Value out of range</b>
<b>Explanation</b>	A value could not be converted into the internal representation because it is out of range, for example the allowed range for a month is 1 to 12.
<b>Action</b>	Check your query and/or data.

<b>INOXQE6329</b>	<b>Invalid collation URI exception</b>
<b>Explanation</b>	The specified collation URI is invalid.
<b>Action</b>	Check the collation URI.
<b>INOXQE6330</b>	<b>Invalid collation attributes exception</b>
<b>Explanation</b>	The specified collation attributes are invalid.
<b>Action</b>	Check the collation attributes.
<b>INOXQE6331</b>	<b>Namespace prefix undefined</b>
<b>Explanation</b>	An invalid namespace prefix was detected when casting a string value as a QName at query execution time.
<b>Action</b>	Extend the static namespace context by adding a definition for the missing prefix.
<b>INOXQE6332</b>	<b>Invalid content expression in computed processing instruction</b>
<b>Explanation</b>	The value of the content expression in a computed processing instruction constructor contains the string "?>".
<b>Action</b>	Avoid expressions that may produce strings containing "?>".
<b>INOXQE6333</b>	<b>Invalid name for processing instruction</b>
<b>Explanation</b>	The name of a constructed processing instruction must be different from "XML" (in any combination of upper and lower case).
<b>Action</b>	Avoid expressions that may produce the string "XML".
<b>INOXQE6334</b>	<b>"Treat as" operation has detected two non-matching types during query execution</b>
<b>Explanation</b>	A "Treat as" operation has detected two non-matching types during query execution.
<b>Action</b>	Reformulate your query.
<b>INOXQE6335</b>	<b>Call stack overflow</b>
<b>Explanation</b>	The call stack for user defined functions has exceeded its defined maximum size.
<b>Action</b>	Inspect your XQuery program for potential programming errors, or increase the call stack's maximum size by means of the {?execution?} pragma.

---

<b>INOXQE6336</b>	<b>Memory allocation limit exceeded</b>
<b>Explanation</b>	The memory limit that has been set by an XQuery execution pragma has been exceeded.
<b>Action</b>	Extend the memory limit, or try to reduce the memory requirements by modifying the query.
<b>INOXQE6337</b>	<b>Invalid content expression in computed comment constructor</b>
<b>Explanation</b>	The result of the content expression of a computed comment constructor contains two adjacent hyphens or ends with a hyphen.
<b>Action</b>	Avoid expressions that produce adjacent hyphens or hyphens at the end.
<b>INOXQE6338</b>	<b>Sort buffer overflow</b>
<b>Explanation</b>	An internal sort buffer has overflowed, because the representation of a single tuple did not fit into it.
<b>Action</b>	Modify the query to reduce the size of tuples to be sorted.
<b>INOXQE6339</b>	<b>Multiple element children in document constructor</b>
<b>Explanation</b>	An XQuery document constructor was supplied with more than one element child. This is not supported by the underlying data model.
<b>Action</b>	Correct the query to avoid constructing multiple element children into a document node.
<b>INOXQE6340</b>	<b>XML parsing error while executing fn:parse()</b>
<b>Explanation</b>	An XQuery invoked fn:parse, but the argument could not be parsed successfully as XML.
<b>Action</b>	Provide well-formed XML.
<b>INOXQE6349</b>	<b>fetching result that is not available</b>
<b>Explanation</b>	A non-sensitive cursor pre-calculates a system defined maximum number of result items. A fetch request has tried to access an item that was not pre-calculated.
<b>Action</b>	Please contact your software supplier.
<b>INOXQE6350</b>	<b>Internal error</b>
<b>Explanation</b>	An internal error has occurred in the XQuery compiler.
<b>Action</b>	Please contact your software supplier.

<b>INOXQE6351</b>	<b>XQuery feature not implemented</b>
<b>Explanation</b>	The query uses an unimplemented language feature. Please see the documentation and release notes for current product limitations.
<b>Action</b>	Change the query.
<b>INOXQE6352</b>	<b>XQuery parsing error</b>
<b>Explanation</b>	One or more errors occurred while parsing the query.
<b>Action</b>	Correct the query appropriately and re-issue.
<b>INOXQE6353</b>	<b>End tag does not match start tag</b>
<b>Explanation</b>	The end tag of an element constructor does not match the start tag.
<b>Action</b>	Correct the query.
<b>INOXQE6354</b>	<b>Namespace prefix undefined</b>
<b>Explanation</b>	The namespace declaration is missing.
<b>Action</b>	Include a namespace declaration in the XQuery prolog.
<b>INOXQE6355</b>	<b>Invalid namespace URI specification</b>
<b>Explanation</b>	URIs must be given as string constants.
<b>Action</b>	Declare the URI literally.
<b>INOXQE6356</b>	<b>Attempted to redefine prefix</b>
<b>Explanation</b>	A prefix may only be defined once.
<b>Action</b>	Rename the prefix in subsequent declarations.
<b>INOXQE6357</b>	<b>The prefix 'xml' must be bound to the namespace 'http://www.w3.org/XML/1998/namespace'</b>
<b>Explanation</b>	The prefix 'xml' can only be declared when bound to the XML namespace URL as defined by the W3C.
<b>Action</b>	If your intent was to include the W3C's XML namespace, correct the URL. Otherwise use a different prefix.

---

<b>INOXQE6358</b>	<b>Function unknown</b>
<b>Explanation</b>	This function is unknown. The function name is either misspelt or the wrong prefix is used.
<b>Action</b>	Check the spelling and the function namespace.
<b>INOXQE6359</b>	<b>Variable undefined</b>
<b>Explanation</b>	A variable that is used must be declared in a 'for' or 'let' expression.
<b>Action</b>	Check spelling or add a 'for' or 'let' clause.
<b>INOXQE6360</b>	<b>Unbound path not allowed here</b>
<b>Explanation</b>	Currently access to database data is only allowed via the input() function.
<b>Action</b>	Use the input() function.
<b>INOXQE6361</b>	<b>Type exception: invalid operands for operator</b>
<b>Explanation</b>	Static typing detected invalid operand types for the operator.
<b>Action</b>	Please check the static types for the operator.
<b>INOXQE6362</b>	<b>Invalid path: documents have no parent</b>
<b>Explanation</b>	The path tries to apply the parent axis (or '..') to a document node.
<b>Action</b>	Check the path.
<b>INOXQE6363</b>	<b>Unknown collection</b>
<b>Explanation</b>	The URL refers to a collection that does not exist in the chosen database.
<b>Action</b>	Check the URL.
<b>INOXQE6364</b>	<b>XQuery applied on non-XML doctype</b>
<b>Explanation</b>	XQuery is only applicable to XML data.
<b>Action</b>	Use another tool for querying.
<b>INOXQE6365</b>	<b>XQuery applied on non-namespace-clean doctype:</b>
<b>Explanation</b>	XQuery is only applicable on namespace-clean doctypes.
<b>Action</b>	Apply proper namespace migration to doctype or use X-Query.

<b>INOXQE6366</b>	<b>Type exception: invalid input for function</b>
<b>Explanation</b>	The parameters provided as an input to the function do not have the required type.
<b>Action</b>	Check the correct parameter types in the documentation for the function.
<b>INOXQE6367</b>	<b>Compile time type exception</b>
<b>Explanation</b>	An invalid type has been detected at XQuery compile time
<b>Action</b>	Correct the query.
<b>INOXQE6368</b>	<b>Default element namespaces are not allowed</b>
<b>Explanation</b>	The XQuery draft is still uncertain whether default element namespaces defined in the query prolog or in generated elements pertain to element steps in location paths. To avoid migration problems with subsequent versions of Tamino, the use of default element namespaces is prohibited.
<b>Action</b>	Please use a namespace prefix instead.
<b>INOXQE6369</b>	<b>A prefix must not begin with 'xml'</b>
<b>Explanation</b>	This is stated in the Errata Document for the XML Namespaces Recommendation.
<b>Action</b>	Choose a prefix that does not begin with 'xml'.
<b>INOXQE6370</b>	<b>Processing of data with X-Tension or X-Node mapping is not supported by XQuery</b>
<b>Explanation</b>	Currently no data with X-Tension (server extension) or X-Node mapping can be accessed by an XQuery query.
<b>Action</b>	Formulate your query using Tamino X-Query instead of XQuery.
<b>INOXQE6371</b>	<b>The URI 'http://www.w3.org/XML/1998/namespace' can only be bound to the prefix 'xml'</b>
<b>Explanation</b>	According to "Namespaces in XML Errata, 4 November 2002" ( <a href="http://www.w3.org/XML/xml-names-19990114-errataNE05">http://www.w3.org/XML/xml-names-19990114-errataNE05</a> substantive), the prefix xml is by definition bound to the namespace name <a href="http://www.w3.org/XML/1998/namespace">http://www.w3.org/XML/1998/namespace</a> . It may, but need not, be declared, and must not be bound to any other namespace name. No other prefix may be bound to this namespace name.
<b>Action</b>	Use the prefix 'xml' or a different URI.

---

<b>INOXQE6372</b>	<b>No prefix may be bound to the URI 'http://www.w3.org/2000/xmlns/'</b>
<b>Explanation</b>	This URI is by definition bound to the prefix 'xmlns'. It must not be declared.
<b>Action</b>	Use a different URI.
<b>INOXQE6373</b>	<b>Invalid comparison</b>
<b>Explanation</b>	Items to be compared must be of the same type, or both numeric, or both string or one of the types derived thereof.
<b>Action</b>	Use string comparison via applying the xf:string() function to non-string operands.
<b>INOXQE6374</b>	<b>The prefix xmlns is used only to declare namespace bindings</b>
<b>Explanation</b>	The prefix xmlns cannot be used unless in the form xmlns:prefix="uri" to declare a namespace binding.
<b>Action</b>	Use another prefix.
<b>INOXQE6375</b>	<b>No multiple default collations allowed.</b>
<b>Explanation</b>	Only one default collation can be defined.
<b>Action</b>	To use more than one collation within a single query give the collation's URI explicitly in the comparison function or use the getCollation() function.
<b>INOXQE6376</b>	<b>Collation could not be obtained.</b>
<b>Explanation</b>	The getCollation() function was not applied upon a path that pointed to an appropriate node.
<b>Action</b>	The input to the getCollation() function must be a path that points to an appropriate element or attribute node. A node is appropriate if its corresponding schema definition contains a collation specification.
<b>INOXQE6377</b>	<b>Invalid Collation Identifier</b>
<b>Explanation</b>	This string does not denote a valid collation.
<b>Action</b>	Correct the spelling or make the collection known to the database.
<b>INOXQE6378</b>	<b>Invalid step in path</b>
<b>Explanation</b>	A flat structure, i.e. something that is not a node, cannot be stepped into using any other axis than the self axis.
<b>Action</b>	Either change the object that is stepped into so that it is of type node or node-set, or use only the self axis (or the dot) to refer to the object.

<b>INOXQE6379</b>	<b>Evaluation context undefined</b>
<b>Explanation</b>	Processing of an expression relies on some component of the evaluation context that has not been assigned a value. Many context-sensitive functions like local-name() rely on the context item.
<b>Action</b>	Make sure that expressions relying on the evaluation context are called when an evaluation context is defined as for example within a filter.
<b>INOXQE6382</b>	<b>XQuery cursor request must not specify a serialization method</b>
<b>Explanation</b>	It is not possible to use a serialization method for an XQuery cursor request.
<b>Action</b>	If you want to apply a serialization method to your query result, use a non-cursor query.
<b>INOXQE6383</b>	<b>Type exception: invalid input for internal function</b>
<b>Explanation</b>	The parameters provided as an input to an internal function do not have the required type. Calls to internal functions are, for instance, contained in update queries. This error may thus indicate an invalid update statement.
<b>Action</b>	Reformulate the update statement or check whether the intended update operation is possible at all.
<b>INOXQE6384</b>	<b>Invalid key or value in an optimization pragma.</b>
<b>Explanation</b>	Valid optimization keys are "join" (possible values "default" and "index-only") and "level" (possible values "0" and "1").
<b>Action</b>	Correct the optimization key and/or value.
<b>INOXQE6385</b>	<b>Invalid output handler function detected</b>
<b>Explanation</b>	An invalid output handler has been detected. Please check the signature of the given output handler function.
<b>Action</b>	Please check the signature of the given output handler function.
<b>INOXQE6386</b>	<b>This name must not be local</b>
<b>Explanation</b>	Some names, for example those of user-defined functions, must be in a namespace. They must either be qualified, i.e. consist of a prefix and a local part, or be in a namespace by a default namespace declaration.
<b>Action</b>	Use either a prefix declared in the query or add a default namespace declaration. For user-defined functions the predefined prefix 'local' can be used.

---

<b>INOXQE6387</b>	<b>The prefix 'local' may only be used when declaring a user-defined function.</b>
<b>Explanation</b>	The 'local' prefix is by definition bound to the URI "http://www.w3.org/2003/11/xquery-local-functions" and is reserved for the definition of user-defined, i.e. local, functions.
<b>Action</b>	Use another prefix.
<b>INOXQE6388</b>	<b>The name of a computed node is neither a string nor a QName.</b>
<b>Explanation</b>	The name of a computed node, such as for example element or attribute node, must either be of type string or derived or of type QName.
<b>Action</b>	Ensure that the expression provided as a computed node's name is of an appropriate type.
<b>INOXQE6389</b>	<b>A user-defined function returns a non-matching type</b>
<b>Explanation</b>	If a user-defined function declares a result type, the type of the function's body must match this declaration.
<b>Action</b>	Correct the function's body or delete the result type declaration.
<b>INOXQE6390</b>	<b>The prefix 'xs' must be bound to the namespace 'http://www.w3.org/2001/XMLSchema'</b>
<b>Explanation</b>	The prefix 'xs' can only be declared when bound to the appropriate namespace URL as defined by the W3C's XML Schema spec.
<b>Action</b>	If your intent was to include the W3C's xs namespace, correct the URL. Otherwise use a different prefix.
<b>INOXQE6391</b>	<b>The name of a computed PI node is not an NCName.</b>
<b>Explanation</b>	The name of a computed PI node must be an NCName.
<b>Action</b>	Ensure that the expression provided as a computed PI node's name is of an appropriate type.
<b>INOXQE6392</b>	<b>The content of a generated PI must be a string.</b>
<b>Explanation</b>	The expression provided as the content of a generated PI node must evaluate to a sequence of strings.
<b>Action</b>	Provide suitable content.

<b>INOXQE6393</b>	<b>Pragma not supported in library module</b>
<b>Explanation</b>	An XQuery library module contains a pragma that is valid only in a main module.
<b>Action</b>	Remove the pragma from the library module.
<b>INOXQE6394</b>	<b>Invalid node comparison</b>
<b>Explanation</b>	A node comparison requires that each operand is either a singleton or an empty sequence.
<b>Action</b>	Check the operands. If an operand is possibly a sequence with more than one entry, use round brackets and a [1] filter.
<b>INOXQE6395</b>	<b>Invalid key or value in an serialization pragma.</b>
<b>Explanation</b>	A valid serialization key is "provide-type-information" (possible values "yes" and "no").
<b>Action</b>	Correct the serialization value.
<b>INOXQE6396</b>	<b>Invalid key or value in an execution pragma.</b>
<b>Explanation</b>	Valid execution keys are "memory" (possible values are integers) and "call-stack-depth" (possible values are also integers).
<b>Action</b>	Correct the execution key/value.
<b>INOXQE6397</b>	<b>Duplicate parameter name in user-defined function</b>
<b>Explanation</b>	Each parameter in a user-defined function's parameter list must have a unique name.
<b>Action</b>	Rename one or more parameters.
<b>INOXQE6398</b>	<b>External variable definition does not conform to restricted XQuery syntax</b>
<b>Explanation</b>	An XQuery expression that is supplied to define an external variable is restricted to sequences of constants, type-specific constructor functions and node constructors.
<b>Action</b>	Reformulate the external variable definition to conform to the restrictions.
<b>INOXQE6399</b>	<b>Duplicate import directive</b>
<b>Explanation</b>	Two 'import module' declarations specify the same module namespace.
<b>Action</b>	Remove the extra import directive or replace it by a namespace declaration.

---

<b>INOXQE6400</b>	<b>Duplicate main-module pragma</b>
<b>Explanation</b>	More than a single main-module pragma has been found in an XQuery.
<b>Action</b>	Remove the duplicate pragma.
<b>INOXQE6401</b>	<b>Multiple declarations of element/type default namespace not allowed</b>
<b>Explanation</b>	Only one default namespace for elements/types can be defined.
<b>Action</b>	Delete one of the default namespace declarations.
<b>INOXQE6402</b>	<b>Multiple declarations of function default namespace not allowed</b>
<b>Explanation</b>	Only one default namespace for functions can be defined.
<b>Action</b>	Delete one of the default namespace declarations.
<b>INOXQE6403</b>	<b>Function is in a namespace different from the module's target namespace.</b>
<b>Explanation</b>	The name of every function declared in a library module must have a namespace URI that is the same as the target namespace of the module.
<b>Action</b>	Change the function's namespace or move to another module.
<b>INOXQE6404</b>	<b>A user-defined function is in a forbidden namespace</b>
<b>Explanation</b>	The function name in a function declaration (when expanded) must not be in any of the following namespaces (among others): <a href="http://www.w3.org/XML/1998/namespace">http://www.w3.org/XML/1998/namespace</a> , <a href="http://www.w3.org/2001/XMLSchema">http://www.w3.org/2001/XMLSchema</a> , <a href="http://www.w3.org/2001/XMLSchema-instance">http://www.w3.org/2001/XMLSchema-instance</a> , <a href="http://www.w3.org/2005/04/xpath-functions">http://www.w3.org/2005/04/xpath-functions</a> , <a href="http://www.w3.org/2005/04/xpath-datatypes">http://www.w3.org/2005/04/xpath-datatypes</a> .
<b>Action</b>	Change the user-defined function's namespace by changing the prefix, or the prefix's binding, or the default function namespace.
<b>INOXQE6406</b>	<b>Invalid context for updating function</b>
<b>Explanation</b>	An updating function was invoked in a context where only a non-updating function is permitted.
<b>Action</b>	Modify the query to provide a proper function or context.
<b>INOXQE6407</b>	<b>Invalid context for non-updating function</b>
<b>Explanation</b>	A non-updating function was invoked in a context where only an updating function is permitted.
<b>Action</b>	Modify the query to provide a proper function or context.

<b>INOXQE6408</b>	<b>Invalid name for external variable</b>
<b>Explanation</b>	A qualified name including a prefix is not supported as the name of an external variable.
<b>Action</b>	Use a non-qualified name.
<b>INOXQE6420</b>	<b>Query not found</b>
<b>Explanation</b>	The given handle does not address any prepared query.
<b>Action</b>	Please correct the given query handle.
<b>INOXQE6421</b>	<b>Invalid query handle</b>
<b>Explanation</b>	The format of the given query handle is wrong. The query handle must be an integer.
<b>Action</b>	Correct the query handle.
<b>INOXQE6424</b>	<b>Missing parameter for query execution</b>
<b>Explanation</b>	The prepared query declares external variables. For at least one of these variables, no suitable input parameter was provided.
<b>Action</b>	Provide input parameter.
<b>INOXQE6450</b>	<b>Update results in non-well-formed document</b>
<b>Explanation</b>	The update statement tries a modification that would result in a non-well-formed document, e.g., insert an element into an attribute, or insert a second root element. The error is accompanied by a message that explains the actual reason in more detail.
<b>Action</b>	Correct the update statement.
<b>INOXQE6451</b>	<b>Conflicting update operations</b>
<b>Explanation</b>	An update statement can consist of several atomic update operations. There may be conflicts between those operations, e.g., a subtree cannot be replaced and deleted at the same time.
<b>Action</b>	Correct the update statement.
<b>INOXQE6452</b>	<b>Attempted to insert or modify one of the meta-attributes ino:id or ino:docname</b>
<b>Explanation</b>	Using XQuery update, it is not allowed to modify the meta-attributes ino:id or ino:docname.
<b>Action</b>	Correct your XQuery update statement.

---

<b>INOXQE6453</b>	<b>Attempt to modify a nonxml document</b>
<b>Explanation</b>	It is not possible to modify non-XML documents using an XQuery update statement. Only deletion of complete non-XML documents is allowed by XQuery update.
<b>Action</b>	Use the <code>_process</code> command in order to replace and thus modify a non-XML document.
<b>INOXQE6454</b>	<b>Attempt to update the same XNode-mapped field twice with different values</b>
<b>Explanation</b>	An XNode column/field appears at different paths in the schema, and an XQuery update statement tried to modify at least two paths with different values.
<b>Action</b>	Correct the XQuery update statement.
<b>INOXQE6455</b>	<b>Invalid node type passed to updating function</b>
<b>Explanation</b>	A node was passed to an updating function, but the node type was not suitable for the function. <code>tf:setDocname</code> and <code>tdf:setProperty</code> can be applied to document nodes only, while <code>tf:put</code> can be applied to document or element nodes.
<b>Action</b>	Modify the query to provide a node with a proper node type.
<b>INOXQE6456</b>	<b>Invalid invocation of tdf:setProperty for live property</b>
<b>Explanation</b>	<code>tdf:setProperty</code> was used in an XQuery update on a live property. This is not allowed, live properties cannot be updated this way.
<b>Action</b>	Modify the update statement, removing the invalid invocation of <code>tdf:setProperty</code> .
<b>INOXQE6457</b>	<b>Invalid doctype name</b>
<b>Explanation</b>	The URI used in a call to <code>fn:put</code> contained an invalid doctype name. The provided doctype name was either not a valid QName, or it did not match the root element name of the XML document to be stored.
<b>Action</b>	Provide a valid doctype name in the URI used with <code>fn:put</code> , or omit the doctype name from the URI.
<b>INOXQE6458</b>	<b>XML parsing error while converting nonXML document</b>
<b>Explanation</b>	A nonXML document was passed to <code>fn:put()</code> with a URI indicating an XML doctype. The nonXML content however failed to be parsed successfully as XML.
<b>Action</b>	Provide well-formed XML or store the document into an XML doctype.

<b>INOXQE6459</b>	<b>Cannot update transient node</b>
<b>Explanation</b>	A transient node, i.e. a node resulting from a previous constructor, was detected as the subject of an update operation. XQuery update however can only be applied to persistent nodes.
<b>Action</b>	Modify XQuery update statement to avoid applying update operations to transient nodes.
<b>INOXQW6380</b>	<b>A path expression results in an empty node-set</b>
<b>Explanation</b>	An empty node-set as a result of a path expression might indicate an error in referencing the document structure or in a name spelling.
<b>Action</b>	Ensure that the empty result is not due to a wrong path.
<b>INOXQW6405</b>	<b>Invalid entity or character reference</b>
<b>Explanation</b>	The query contains an invalid entity or a character reference that does not map to a valid character. As a corrective action, the ampersand character has been treated as a literal, not as an entity introducer.
<b>Action</b>	To avoid this warning, correct the query appropriately and re-issue.
<b>INOXQW6423</b>	<b>Execution of prepared query requires recompilation</b>
<b>Explanation</b>	Due to schema, security or structure index changes the compiled query yielded by previous preparation is not longer valid. This requires a recompilation of the prepared query.
<b>Action</b>	Recompile the prepared query.
<b>INOXQW6425</b>	<b>querySearchMode=approximate not applicable for this query</b>
<b>Explanation</b>	This query cannot be executed in a streaming mode, thus the specified request parameter querySearchMode=approximate has no effect.
<b>Action</b>	Do not use this request parameter.
<b>INOXRE8802</b>	<b>Internal error: input parameter error</b>
<b>Explanation</b>	Internal error: Data Map was called with missing or invalid parameters.
<b>Action</b>	Please contact your software supplier.

---

<b>INOXRE8803</b>	<b>Specified name too long</b>
<b>Explanation</b>	The specified name is too long. Length limitations are described in the Tamino documentation.
<b>Action</b>	Modify the schema definition and repeat your request.
<b>INOXRE8805</b>	<b>Invalid collection, element, attribute or server extension name</b>
<b>Explanation</b>	The specified name is not a valid QName. The specified name starts with a colon and/or contains more than one colon.
<b>Action</b>	Correct the schema definition and repeat the request.
<b>INOXRE8806</b>	<b>Collection is currently used by another user</b>
<b>Explanation</b>	The request cannot be executed because at least one of the affected collections is currently held by another user.
<b>Action</b>	Repeat the request.
<b>INOXRE8807</b>	<b>Doctype is currently used by another user</b>
<b>Explanation</b>	There is a persistent lock on a doctype which prevents the current request from continuing.
<b>Action</b>	Repeat the request when the request that has the persistent lock has finished.
<b>INOXRE8808</b>	<b>Index recreation currently not pending on the specified collection</b>
<b>Explanation</b>	There is no index recreation pending to continue or reset. It is not necessary to execute the <code>_admin</code> command.
<b>Action</b>	No action required.
<b>INOXRE8809</b>	<b>Index recreation is pending</b>
<b>Explanation</b>	On the specified doctype an index recreation is pending. The requested action cannot be executed.
<b>Action</b>	Execute the corresponding <code>_admin</code> request to continue or reset the index recreation.
<b>INOXRE8810</b>	<b>Index recreation is running</b>
<b>Explanation</b>	The requested action cannot be executed while an index recreation is running on the specified doctype.
<b>Action</b>	No action required.

<b>INOXRE8811</b>	<b>Collection name not found</b>
<b>Explanation</b>	The specified collection is unknown.
<b>Action</b>	Correct the collection name and repeat the request.
<b>INOXRE8814</b>	<b>Element/attribute name not found</b>
<b>Explanation</b>	The specified element or attribute is unknown.
<b>Action</b>	Correct the element or attribute name and repeat the request.
<b>INOXRE8815</b>	<b>Internal error: mapping already defined</b>
<b>Explanation</b>	Internal error: mapping already defined.
<b>Action</b>	Please contact your software supplier.
<b>INOXRE8816</b>	<b>Internal error while inserting an implicit element or attribute</b>
<b>Explanation</b>	An internal error occurred while inserting an implicit element or attribute.
<b>Action</b>	Please contact your software supplier.
<b>INOXRE8818</b>	<b>Duplicate collection name</b>
<b>Explanation</b>	There is already a collection with the specified name.
<b>Action</b>	Specify another collection name or undefine the existing collection.
<b>INOXRE8819</b>	<b>Duplicate element/attribute name</b>
<b>Explanation</b>	The element or attribute to be inserted is already defined. It is not allowed to specify a schema containing two or more elements or attributes with the same name and the same parent.
<b>Action</b>	Correct the schema definition and repeat the request.
<b>INOXRE8821</b>	<b>Internal error: invalid parent specification</b>
<b>Explanation</b>	Internal error: invalid parent specification.
<b>Action</b>	Please contact your software supplier.
<b>INOXRE8822</b>	<b>Invalid options specification</b>
<b>Explanation</b>	The specified options are incorrect. Either unexpected options are specified or expected options are missing.
<b>Action</b>	Refer to the Tamino documentation, correct your schema definition and repeat the request.

---

<b>INOXRE8823</b>	<b>Internal error: invalid object ID specification</b>
<b>Explanation</b>	Internal error: an invalid ID was specified.
<b>Action</b>	Retry with an increased transaction timeout value. If that doesn't help restart the Tamino database. If the problem still occurs please contact your software supplier.
<b>INOXRE8824</b>	<b>Internal error: invalid collection ID specification</b>
<b>Explanation</b>	Internal error: an invalid ID was specified.
<b>Action</b>	Please contact your software supplier.
<b>INOXRE8825</b>	<b>Invalid multiplicity specification</b>
<b>Explanation</b>	The specified multiplicity is invalid. Either the multiplicity does not correspond with the mapping type, or a multiplicity of + or * is specified for attributes, or a multiplicity not equal to blank is specified for the root element.
<b>Action</b>	Correct the schema definition and repeat the request.
<b>INOXRE8826</b>	<b>Invalid search type specification</b>
<b>Explanation</b>	The search type is invalid or does not match the specified mapping type. For an external document summary file the specified shortname may be invalid.
<b>Action</b>	Correct the schema definition and repeat the request.
<b>INOXRE8827</b>	<b>Internal error: invalid index ID specification</b>
<b>Explanation</b>	Internal error: an invalid ID was specified.
<b>Action</b>	Please contact your software supplier.
<b>INOXRE8830</b>	<b>Invalid schema structure: missing node definition</b>
<b>Explanation</b>	An attempt was made to specify a node with a mapping type which requires at least one child with a specific other mapping type. This element is missing. (Example: Mapping to an SQL table requires at least one child mapped to an SQL column.)
<b>Action</b>	Correct the schema definition and repeat the request.
<b>INOXRE8831</b>	<b>Deletion rejected because of depending objects</b>
<b>Explanation</b>	The server extension object could not be deleted because at least one node references a server extensions function of the object to be deleted.
<b>Action</b>	Update the schema definitions containing referencing nodes and repeat the request.

<b>INOXRE8833</b>	<b>Internal error: file structure/schema definition mismatch</b>
<b>Explanation</b>	Internal error: file structure/schema definition mismatch.
<b>Action</b>	Please contact your software supplier.
<b>INOXRE8834</b>	<b>Data map record could not be stored</b>
<b>Explanation</b>	A Data Map record could not be stored. The definition of one node is too large.
<b>Action</b>	Modify the schema definition and repeat the request. Please inform your software supplier.
<b>INOXRE8835</b>	<b>Data map record could not be updated</b>
<b>Explanation</b>	A data map record could not be updated. The number of children for one collection or node is too large.
<b>Action</b>	Modify the schema definition and repeat the request. Please inform your software supplier.
<b>INOXRE8836</b>	<b>Modifying or deleting of system collection/doctype rejected</b>
<b>Explanation</b>	Collections and doctypes containing the Tamino namespace may not be modified or deleted.
<b>Action</b>	No action required.
<b>INOXRE8841</b>	<b>Invalid mapping specification: invalid or unexpected primary key definition</b>
<b>Explanation</b>	For a mapped SQL table at least one mapped SQL column must be indicated as the primary key using the keyword ino:sqlprimarykeys.
<b>Action</b>	Correct the schema definition and repeat the request.
<b>INOXRE8842</b>	<b>Invalid mapping specification: invalid or unexpected password specification</b>
<b>Explanation</b>	The specified Adabas password is either too long (maximum length is 8 characters) or unexpected (for nodes not mapped to AdaFile).
<b>Action</b>	Correct the schema definition and repeat the request.
<b>INOXRE8843</b>	<b>Invalid mapping specification: invalid parent - child relation</b>
<b>Explanation</b>	The relation between parent node and child node is not allowed. This is mostly caused by the object type of either parent or child node.
<b>Action</b>	Correct the schema definition and repeat the request.

---

<b>INOXRE8844</b>	<b>Invalid mapping specification: invalid parent - child relation</b>
<b>Explanation</b>	The relation between parent node and child node is not allowed. This is caused by either an unexpected mapping type of the child node or a node having a multiplicity of + or * between a node mapped to an SQL table or an Adabas file and the corresponding nodes mapped to an SQL column or Adabas field, multiple field or periodic group.
<b>Action</b>	Correct the schema definition and repeat the request.
<b>INOXRE8845</b>	<b>Invalid schema structure: missing elements</b>
<b>Explanation</b>	The mapping of the node is invalid. It requires other mapping in parent nodes. This error is mostly caused by a node mapped to an SQL column without having a corresponding node mapped to an SQL table, or mapped to an Adabas field without having a corresponding node mapped to an Adabas file.
<b>Action</b>	Correct the schema definition and repeat the request.
<b>INOXRE8847</b>	<b>Invalid mapping specification: invalid or unexpected shortname specification</b>
<b>Explanation</b>	The specification of a shortname is not allowed or does not conform to Adabas shortname rules.
<b>Action</b>	Correct the schema definition and repeat the request.
<b>INOXRE8848</b>	<b>Invalid mapping specification: invalid or unexpected Adabas file specification</b>
<b>Explanation</b>	The specification of a database ID and or file number is missing or invalid (Adabas file mapping) or not allowed (other mappings).
<b>Action</b>	Correct the schema definition and repeat the request.
<b>INOXRE8854</b>	<b>Invalid mapping specification: invalid object reference specification</b>
<b>Explanation</b>	The specified object reference was unexpected or refers to an undefined object. An object reference may only be specified for nodes mapped to another node.
<b>Action</b>	Correct the schema definition and repeat the request.
<b>INOXRE8856</b>	<b>Invalid mapping specification: invalid or unexpected SQL specification</b>
<b>Explanation</b>	For an SQL table mapping the table name was missing or a password was specified without userid. For an SQL column mapping the column was not specified. For other mappings SQL specific keywords are unexpected.
<b>Action</b>	Correct the schema definition and repeat the request.

<b>INOXRE8859</b>	<b>Invalid mapping specification: invalid or unexpected format specification</b>
<b>Explanation</b>	A format specification is either invalid (for Adafield mappings) or unexpected (for other mappings). A list of all valid formats is specified in the Tamino documentation.
<b>Action</b>	Correct the schema and repeat the request.
<b>INOXRE8860</b>	<b>Invalid mapping specification: invalid or unexpected length specification</b>
<b>Explanation</b>	A length specification is either invalid (for Adafield mappings) or unexpected (for other mappings). The length specification must conform to the format specification as defined in Adabas.
<b>Action</b>	Correct the schema definition and repeat the request.
<b>INOXRE8861</b>	<b>Invalid mapping specification: invalid or unexpected precision specification</b>
<b>Explanation</b>	A precision was either specified for a non-SQL column mapping, or is unexpected or out of range for the specified datatype. Dependencies between datatype and precision are described in the Tamino documentation.
<b>Action</b>	Correct the schema and repeat the request.
<b>INOXRE8862</b>	<b>Invalid mapping specification: invalid or unexpected scale specification</b>
<b>Explanation</b>	A scale was either specified for a non-SQL column mapping, or is unexpected or out of range for the specified datatype. Dependencies between datatype, precision and scale are described in the Tamino documentation.
<b>Action</b>	Correct the schema definition and repeat the request.
<b>INOXRE8863</b>	<b>Invalid mapping specification: invalid or unexpected data type specification</b>
<b>Explanation</b>	The specification of a data type is not allowed or does not conform to the list of supported datatypes. Please refer to the Tamino documentation for a list of supported data types.
<b>Action</b>	Correct the schema definition and repeat the request.
<b>INOXRE8865</b>	<b>Invalid mapping specification: invalid or unexpected encoding specification</b>
<b>Explanation</b>	The value for an encoding may only be specified for nodes mapped to an Adabas file or mapped to an Adabas field that has an alphanumeric format. The encoding must be a valid encoding string.
<b>Action</b>	Correct the schema and repeat the request.

---

<b>INOXRE8873</b>	<b>Server extensions: function not found</b>
<b>Explanation</b>	There is no server extension function with the specified function name.
<b>Action</b>	Check the specified function name. Be aware that function names are case sensitive.
<b>INOXRE8887</b>	<b>The request cannot be executed within a session context</b>
<b>Explanation</b>	In a session context it is not possible to recreate indexes for ino:creationDate or ino:lastModified.
<b>Action</b>	Recreate the indexes in a session-less request.
<b>INOXRE8888</b>	<b>Adding a new node definition with the specified attributes is not supported</b>
<b>Explanation</b>	Adding a new node definition with the specified attributes is not supported because of already existing documents.
<b>Action</b>	Remove the affected documents and repeat the request.
<b>INOXRE8889</b>	<b>Modifying an existing node definition with the specified attributes is not supported</b>
<b>Explanation</b>	The requested parameter may not be changed after the schema definition.
<b>Action</b>	Undefine the schema and define the modified schema definition once again.
<b>INOXRE8890</b>	<b>Internal error: unsupported request</b>
<b>Explanation</b>	The internal data map was called for an unsupported request.
<b>Action</b>	Please contact your software supplier.
<b>INOXRE8891</b>	<b>Internal error: Data Map function failed</b>
<b>Explanation</b>	The internal data map encountered an unexpected situation.
<b>Action</b>	Please contact your software supplier.
<b>INOXRE8892</b>	<b>Internal error: Data Map corrupted</b>
<b>Explanation</b>	The internal data map found insufficient data.
<b>Action</b>	Please contact your software supplier.
<b>INOXRE8893</b>	<b>Internal error: conversion services failed</b>
<b>Explanation</b>	An error occurred while the internal data map used conversion services.
<b>Action</b>	Please contact your software supplier.

<b>INOXRE8894</b>	<b>Internal error: invalid file specification</b>
<b>Explanation</b>	An internal error occurred during access to an Infofile.
<b>Action</b>	Please contact your software supplier.
<b>INOXRF8899</b>	<b>Index recreation could not be finished successfully for doctype DOCTYPE in collection COLLECTION</b>
<b>Explanation</b>	An error occurred while finishing the index recreation. The collection is currently not usable.
<b>Action</b>	Restart the server and execute the <code>_admin</code> command to finish the index recreation.
<b>INOXRI8838</b>	<b>Request to create the unique constraint CONSTRAINT for doctype DOCTYPE in collection COLLECTION has failed and will be backed out</b>
<b>Explanation</b>	A request to create a unique constraint was running during server shutdown. The unique constraint is dropped during server start.
<b>Action</b>	Repeat the request to create the unique constraint.
<b>INOXRW8801</b>	<b>Request to create indexes for doctype DOCTYPE in collection COLLECTION is pending</b>
<b>Explanation</b>	A request to create indexes was aborted with an error or was running during server shutdown.
<b>Action</b>	Start the corresponding admin command to continue or reset the index creation.
<b>INOXSE8903</b>	<b>Memory allocation failed</b>
<b>Explanation</b>	There was not enough main memory available to perform the request.
<b>Action</b>	Possibly the machine is overloaded. Try again later.
<b>INOXSE8905</b>	<b>The combination of index-shortname and the search-type and/or map-type is not valid</b>
<b>Explanation</b>	The node with the search-type and/or map-type cannot contain a definition of index-shortname
<b>Action</b>	Check the map-type and the search-type.

---

<b>INOXSE8906</b>	<b>XML parser failure for schema definition</b>
<b>Explanation</b>	The supplied schema definition is not well-formed XML.
<b>Action</b>	Correct the schema definition.
<b>INOXSE8909</b>	<b>Internal error during schema processing</b>
<b>Explanation</b>	An internal error has occurred.
<b>Action</b>	Please contact your software supplier.
<b>INOXSE8910</b>	<b>Invalid element content in schema definition</b>
<b>Explanation</b>	The schema definition contains elements with mixed content, or the ino:file-format attribute has an illegal value.
<b>Action</b>	Correct the schema definition.
<b>INOXSE8911</b>	<b>The specified mapping parameter(s) (adadsfnr, adadsdbid, adavoc...) can only be specified in a node which has the mapping type AdaFile</b>
<b>Explanation</b>	The specifications such as adadsfnr, adadsdbid, adavoc etc. cannot be used with a mapping type other than AdaFile
<b>Action</b>	Remove the mapping parameters or change the mapping type to AdaFile.
<b>INOXSE8913</b>	<b>Invalid structure of schema definition, hierarchy has to be collection - doctype - node</b>
<b>Explanation</b>	The structure of the schema definition is invalid. It should be defined with the hierarchy collection - doctype - node(s).
<b>Action</b>	Check the schema definition and fix the affected nodes.
<b>INOXSE8914</b>	<b>Internal error: buffer overflow</b>
<b>Explanation</b>	An internal error has occurred.
<b>Action</b>	Please contact your software supplier.
<b>INOXSE8915</b>	<b>The keywords index-shortname, adadsdbid, adadsfnr, adavocdbid and adavocfnr are not supported in the current version</b>
<b>Explanation</b>	These keywords are not supported in the current version.
<b>Action</b>	Remove these keywords from the schema definition.

<b>INOXSE8917</b>	<b>Internal error: doctype without root element</b>
<b>Explanation</b>	An internal error has occurred.
<b>Action</b>	Please contact your software supplier.
<b>INOXSE8918</b>	<b>Internal error: unknown object type</b>
<b>Explanation</b>	An internal error has occurred.
<b>Action</b>	Please contact your software supplier.
<b>INOXSE8920</b>	<b>Internal error: unknown mapping type</b>
<b>Explanation</b>	An internal error has occurred.
<b>Action</b>	Please contact your software supplier.
<b>INOXSE8921</b>	<b>ino:format or ino:length specified with SQL mapping</b>
<b>Explanation</b>	ino:format and ino:length must not be specified with SQL mapping.
<b>Action</b>	Correct the schema definition.
<b>INOXSE8922</b>	<b>Value has to be a number</b>
<b>Explanation</b>	The given value could not be converted to a number.
<b>Action</b>	Correct the schema definition.
<b>INOXSE8923</b>	<b>Specified number larger than allowed maximum</b>
<b>Explanation</b>	The specified number was too large.
<b>Action</b>	Correct the schema definition.
<b>INOXSE8924</b>	<b>Invalid doctype option specified</b>
<b>Explanation</b>	An illegal value was specified for ino:options in the <ino:doctype> element.
<b>Action</b>	Correct the schema definition.
<b>INOXSE8926</b>	<b>Collection name missing or invalid</b>
<b>Explanation</b>	The name supplied in the ino:name attribute of the &lt;ino:collection&gt; element was either illegal or missing.
<b>Action</b>	Check the schema document.

---

<b>INOXSE8927</b>	<b>Doctype name missing or invalid</b>
<b>Explanation</b>	The name supplied in the ino:name attribute of the <ino:doctype> element was either illegal or missing.
<b>Action</b>	Correct the schema definition.
<b>INOXSE8929</b>	<b>The node name specified does not conform to the XML specification</b>
<b>Explanation</b>	The name specified in the ino:name attribute of an <ino:node> element does not conform to the XML specification.
<b>Action</b>	Correct the schema definition.
<b>INOXSE8930</b>	<b>Doctype specified without any nodes</b>
<b>Explanation</b>	Each doctype must have at least a root node.
<b>Action</b>	Correct the schema definition.
<b>INOXSE8931</b>	<b>Node key missing</b>
<b>Explanation</b>	The required ino:key attribute was missing for a <ino:node> element.
<b>Action</b>	Correct the schema definition.
<b>INOXSE8932</b>	<b>Node object type missing</b>
<b>Explanation</b>	The required ino:obj-type attribute was missing for a <ino:node> element.
<b>Action</b>	Correct the schema definition.
<b>INOXSE8933</b>	<b>Node parent missing</b>
<b>Explanation</b>	The required ino:parent attribute was missing for a <ino:node> element.
<b>Action</b>	Correct the schema definition.
<b>INOXSE8934</b>	<b>Doctype contains multiple root nodes</b>
<b>Explanation</b>	Each doctype must contain exactly one root node.
<b>Action</b>	Correct the schema definition.
<b>INOXSE8935</b>	<b>Doctype contains no root nodes</b>
<b>Explanation</b>	Each doctype must contain exactly one root node.
<b>Action</b>	Correct the schema definition.

<b>INOXSE8937</b>	<b>Invalid parent reference</b>
<b>Explanation</b>	The ino:parent attribute of an <ino:node> element did not point to another node.
<b>Action</b>	Correct the schema definition.
<b>INOXSE8938</b>	<b>Invalid node option specified</b>
<b>Explanation</b>	An illegal value was specified for ino:options in an <ino:node> element.
<b>Action</b>	Correct the schema definition.
<b>INOXSE8939</b>	<b>Adabas dbid value too large</b>
<b>Explanation</b>	The value specified for an Adabas database ID was too large.
<b>Action</b>	Correct the schema definition.
<b>INOXSE8940</b>	<b>Adabas fnr value too large</b>
<b>Explanation</b>	The value specified for an Adabas file number was too large.
<b>Action</b>	Correct the schema definition.
<b>INOXSE8941</b>	<b>Length value too large</b>
<b>Explanation</b>	The length value specified for an Adabas field was too large.
<b>Action</b>	Correct the schema definition.
<b>INOXSE8942</b>	<b>Internal error: invalid ID reference</b>
<b>Explanation</b>	An internal error has occurred.
<b>Action</b>	Please contact your software supplier.
<b>INOXSE8943</b>	<b>Internal error: bad query</b>
<b>Explanation</b>	An internal error has occurred.
<b>Action</b>	Please contact your software supplier.
<b>INOXSE8944</b>	<b>Object definition missing in the new schema definition</b>
<b>Explanation</b>	One or more objects are missing in the schema definition although they are already defined in the data map. The current version does not support object deletion.
<b>Action</b>	Complete the schema definition.

---

<b>INOXSE8945</b>	<b>Invalid type change</b>
<b>Explanation</b>	Modification of type is not supported if type is CDATA.
<b>Action</b>	Fix the schema definition.
<b>INOXSE8946</b>	<b>Shortname specified for ADAFile without adadsdbid/fnr</b>
<b>Explanation</b>	Shortname specified for ADAFile without adadsdbid/fnr.
<b>Action</b>	Complete the schema definition.
<b>INOXSE8947</b>	<b>Bad value for structure-index</b>
<b>Explanation</b>	The specified value for structure-index of doctype is not supported.
<b>Action</b>	Fix the schema definition.
<b>INOXSE8948</b>	<b>Attribute already declared</b>
<b>Explanation</b>	An attribute is specified more than once.
<b>Action</b>	Fix the schema definition.
<b>INOXSE8949</b>	<b>Different doctype and root element name</b>
<b>Explanation</b>	The doctype and root element must have the same name.
<b>Action</b>	Fix the schema definition.
<b>INOXSE8950</b>	<b>Too many indexes in schema</b>
<b>Explanation</b>	The schema defines more than the maximum possible number of indexes.
<b>Action</b>	Adapt the schema definition. For example, you may use multipath indexes in order to reduce the number of indexes being created.
<b>INOXSE8951</b>	<b>Too many elements/attributes for "lite" mapping"</b>
<b>Explanation</b>	The schema defines more than the maximum possible number of elements/attributes for "lite" mapping".
<b>Action</b>	Correct the schema definition.
<b>INOXSE8952</b>	<b>No more indexes available</b>
<b>Explanation</b>	Attempted to create too many standard or text indexes in the schema definition.
<b>Action</b>	Remove standard or text indexes or use multi-path indexes where applicable.

<b>INOXSE8953</b>	<b>Invalid node search type specified</b>
<b>Explanation</b>	An illegal value was specified for the ino:search-type attribute.
<b>Action</b>	Correct the schema definition.
<b>INOXSE8954</b>	<b>Scale value too large</b>
<b>Explanation</b>	An illegal value was specified for the ino:scale attribute.
<b>Action</b>	Correct the schema definition.
<b>INOXSE8955</b>	<b>Attribute missing</b>
<b>Explanation</b>	There is a required attribute missing.
<b>Action</b>	Fix a schema definition.
<b>INOXSE8956</b>	<b>Required node attribute missing</b>
<b>Explanation</b>	One of the required attributes for the <ino:node> element is missing.
<b>Action</b>	Correct the schema definition.
<b>INOXSE8957</b>	<b>Required doctype attribute missing</b>
<b>Explanation</b>	One of the required attributes for the <ino:doctype> element is missing.
<b>Action</b>	Correct the schema definition.
<b>INOXSE8958</b>	<b>Required collection attribute missing</b>
<b>Explanation</b>	One of the required attributes for the <ino:collection> element is missing.
<b>Action</b>	Correct the schema definition.
<b>INOXSE8959</b>	<b>Unknown node attribute specified</b>
<b>Explanation</b>	An illegal attribute was specified for an <ino:node> element.
<b>Action</b>	Correct the schema definition.
<b>INOXSE8960</b>	<b>Unknown doctype attribute specified</b>
<b>Explanation</b>	An illegal attribute was specified for the <ino:doctype> element.
<b>Action</b>	Correct the schema definition.

---

<b>INOXSE8961</b>	<b>Unknown collection attribute specified</b>
<b>Explanation</b>	An illegal attribute was specified for the <ino:collection> element.
<b>Action</b>	Correct the schema definition.
<b>INOXSE8962</b>	<b>Invalid or missing dbid parameter</b>
<b>Explanation</b>	The explanation text in the< ino:messageline> element gives more information about the cause of the error.
<b>Action</b>	Correct the schema definition.
<b>INOXSE8963</b>	<b>Invalid format value</b>
<b>Explanation</b>	An illegal value was supplied in the ino:format attribute.
<b>Action</b>	Correct the schema definition.
<b>INOXSE8964</b>	<b>Invalid object type value</b>
<b>Explanation</b>	An illegal value was specified for the ino:obj-type attribute.
<b>Action</b>	Correct the schema definition.
<b>INOXSE8965</b>	<b>Invalid data type value</b>
<b>Explanation</b>	An illegal value was specified for the ino:data-type attribute.
<b>Action</b>	Correct the schema definition.
<b>INOXSE8966</b>	<b>Invalid multiplicity value</b>
<b>Explanation</b>	An illegal value was specified for the ino:multiplicity attribute.
<b>Action</b>	Correct the schema definition.
<b>INOXSE8967</b>	<b>Invalid mapping type value</b>
<b>Explanation</b>	An illegal value was specified for the ino:map-type attribute.
<b>Action</b>	Correct the schema definition
<b>INOXSE8968</b>	<b>Invalid shortname value</b>
<b>Explanation</b>	An illegal value was specified for the ino:shortname attribute.
<b>Action</b>	Correct the schema definition.

<b>INOXSE8969</b>	<b>Unknown element name in schema definition</b>
<b>Explanation</b>	Only <ino:collection>, <ino:doctype>, and <ino:node> are allowed as elements in a schema definition.
<b>Action</b>	Correct the schema definition.
<b>INOXSE8970</b>	<b>Duplicate key value in schema definition</b>
<b>Explanation</b>	The ino:key values must be unique within a schema definition.
<b>Action</b>	Correct the schema definition.
<b>INOXSE8971</b>	<b>Invalid primary key reference in schema definition</b>
<b>Explanation</b>	Every column reference in a primary definition for SQL table mapping needs to be declared as an SQL column mapping for one node in a subtree of the SQL table mapped node.
<b>Action</b>	Correct the schema definition.
<b>INOXSE8978</b>	<b>Bad value for compression</b>
<b>Explanation</b>	The specified value for compression of the doctype is not supported.
<b>Action</b>	Fix the schema definition.
<b>INOXSE8979</b>	<b>Collection is currently used by another user</b>
<b>Explanation</b>	The request cannot be executed because at least one of the affected collections is currently held by another user.
<b>Action</b>	Repeat the request.
<b>INOXSE8980</b>	<b>Server extensions: external name and module name / function name are mutually exclusive</b>
<b>Explanation</b>	Do not specify both external name and module name/function name for a server extension.
<b>Action</b>	Correct the schema definition.
<b>INOXTE7400</b>	<b>Internal error</b>
<b>Explanation</b>	A text retrieval internal error has occurred.
<b>Action</b>	Please contact your software supplier.

---

<b>INOXTE7401</b>	<b>Empty search term</b>
<b>Explanation</b>	An empty-valued search term is specified.
<b>Action</b>	Please specify a non-empty search term in the query.
<b>INOXTE7402</b>	<b>Empty search token(s)</b>
<b>Explanation</b>	One or more empty search tokens are specified.
<b>Action</b>	Please specify non-empty search tokens in the query.
<b>INOXTE7403</b>	<b>Empty search term in word function</b>
<b>Explanation</b>	An empty-valued search term is specified in the word function.
<b>Action</b>	Please specify a non-empty search term in the word function.
<b>INOXTE7404</b>	<b>Invalid search term</b>
<b>Explanation</b>	An invalid search term is specified.
<b>Action</b>	Please specify a valid search term in the query.
<b>INOXTE7405</b>	<b>Invalid search token</b>
<b>Explanation</b>	One or more invalid search tokens are specified.
<b>Action</b>	Please specify valid search tokens in the query.
<b>INOXTE7406</b>	<b>Invalid search term in word function</b>
<b>Explanation</b>	An invalid search term is specified in the word function.
<b>Action</b>	Please specify a valid search term in the word function.
<b>INOXTE7407</b>	<b>Maximum number of search tokens exceeded</b>
<b>Explanation</b>	The derived search tokens from the search term or specified search tokens have exceeded the maximum number allowed.
<b>Action</b>	Please correct your search term/tokens in the query.
<b>INOXTE7408</b>	<b>Invalid wildcard usage</b>
<b>Explanation</b>	Invalid wildcards are specified in the query.
<b>Action</b>	Please refer to Tamino documentation for more details.

<b>INOXTE7409</b>	<b>Word function nesting</b>
<b>Explanation</b>	Nesting of word functions is not allowed.
<b>Action</b>	Please correct the query.
<b>INOXTE7410</b>	<b>Invalid highlighting marker</b>
<b>Explanation</b>	Highlighting marker does not conform to an NCName.
<b>Action</b>	Please correct the marker parameter for the highlighting function.
<b>INOXTE7411</b>	<b>Fragmented document reference</b>
<b>Explanation</b>	Highlighting of document fragments is not supported.
<b>Action</b>	Please correct the query for the highlighting function.
<b>INOXTE7412</b>	<b>Invalid node addressing</b>
<b>Explanation</b>	Invalid node addressing of the document has occurred during the highlighting process.
<b>Action</b>	Please correct the query for the highlighting function.
<b>INOXTE7413</b>	<b>No valid document node</b>
<b>Explanation</b>	No valid document node is found for highlighting.
<b>Action</b>	Please correct the query for the highlighting function.
<b>INOXTE7415</b>	<b>Invalid distance for proximity function</b>
<b>Explanation</b>	The distance for a proximity function must be a positive integer.
<b>Action</b>	Correct the distance and try again.
<b>INOXTE7416</b>	<b>index nonXML tsd:onTextInsert shadow X-Tension function not defined</b>
<b>Explanation</b>	A shadow X-Tension function for the insertion of a non-XML text document was expected in the schema.
<b>Action</b>	Define a shadow X-Tension function tsd:onTextInsert in the schema.
<b>INOXTE7417</b>	<b>index nonXML tsd:onBinaryInsert shadow X-Tension function not defined</b>
<b>Explanation</b>	A shadow X-Tension function for the insertion of a non-XML binary object was expected in the schema.
<b>Action</b>	Define a shadow X-Tension function tsd:onBinaryInsert in the schema.

---

<b>INOXTE7418</b>	<b>illegal phonrule definition</b>
<b>Explanation</b>	The number of replace characters must not be higher than the number of characters to be replaced.
<b>Action</b>	Correct the phonrule(s) in question.
<b>INOXTE7419</b>	<b>illegal stemrule definition</b>
<b>Explanation</b>	The number of replace characters must not be higher than the number of characters to be replaced.
<b>Action</b>	Correct the stemrule(s) in question.
<b>INOXXE8600</b>	<b>The group with name ino:admin may not contain any aclref elements</b>
<b>Explanation</b>	The group with name ino:admin may not contain any aclref elements.
<b>Action</b>	Make sure that the group ino:admin contains no aclref elements and try again.
<b>INOXXE8601</b>	<b>Not enough memory for the requested security operation</b>
<b>Explanation</b>	Not enough memory for the requested security operation.
<b>Action</b>	Free up some memory resources and try executing the operation again.
<b>INOXXE8602</b>	<b>This operation is not allowed for the special 2-Phase-Commit user</b>
<b>Explanation</b>	This operation is not allowed for the special 2-Phase-Commit user.
<b>Action</b>	Make sure you specify a user with the needed privileges for this operation.
<b>INOXXE8603</b>	<b>Namespace prefixes specified in ino:ace paths need to be defined</b>
<b>Explanation</b>	Namespace prefixes specified in ino:ace paths need to be defined.
<b>Action</b>	Please specify a namespace definition for each namespace prefix and try again.
<b>INOXXE8604</b>	<b>The aclref attribute may only reference existing documents</b>
<b>Explanation</b>	The aclref attribute may only reference existing documents.
<b>Action</b>	Please check that only valid references to existing documents are specified in the aclref attribute.

<b>INOXXE8610</b>	<b>Definitions for ino:userid, ino:groupname, and ino:aclname in the collection ino:security need to be unique</b>
<b>Explanation</b>	Definitions for ino:userid, ino:groupname, and ino:aclname in the collection ino:security need to be unique.
<b>Action</b>	First delete the existing entry before loading the new one with the same name into the database.
<b>INOXXE8611</b>	<b>Invalid path specified in an ino:ace element</b>
<b>Explanation</b>	Invalid path specified in an ino:ace element. The path must consist of names that are valid for XML element or attribute names, separated by slashes.
<b>Action</b>	Please correct the path specified in the ino:ace element and try loading the security definitions again.
<b>INOXXE8699</b>	<b>Administration command is not available</b>
<b>Explanation</b>	An administration command is not available.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9002</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9003</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9004</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9005</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.

---

<b>INOXYE9006</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9007</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9008</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9009</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9010</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9011</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9012</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9013</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.

**INOXYE9014**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9015**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9016**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9017**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9018**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9019**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9020**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9021**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

---

<b>INOXYE9022</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9023</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9024</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9025</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9026</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9027</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9028</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9029</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.

**INOXYE9030**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9031**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9032**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9033**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9034**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9035**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9036**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9037**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

---

<b>INOXYE9038</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9039</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9040</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9041</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9042</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9043</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9044</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9045</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.

**INOXYE9046**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9047**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9048**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9049**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9050**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9051**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9052**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9053**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

---

<b>INOXYE9054</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9055</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9056</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9057</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9058</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9059</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9060</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9061</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.

**INOXYE9062**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9063**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9064**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9065**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9066**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9067**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9068**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9069**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

---

<b>INOXYE9070</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9071</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9072</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9073</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9074</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9075</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9076</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9077</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.

**INOXYE9078**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9079**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9080**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9081**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9082**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9083**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9084**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9085**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

---

<b>INOXYE9086</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9087</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9088</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9089</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9090</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9091</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9092</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9093</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.

**INOXYE9094**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9095**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9096**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9097**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9098**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9099**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9100**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9101**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

---

<b>INOXYE9102</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9103</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9104</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9105</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9106</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9107</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9108</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9109</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.

**INOXYE9110**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9111**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9112**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9113**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9114**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9115**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9116**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9117**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

---

<b>INOXYE9118</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9119</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9120</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9121</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9122</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9123</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9124</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9125</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.

<b>INOXYE9126</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9127</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9128</b>	<b>Doctype storage limit exceeded</b>
<b>Explanation</b>	The storage limit for a single doctype was exceeded with regard to any of the following: -total number of documents -total collected size of documents -total number of occurrences of elements with reference index.
<b>Action</b>	Please contact your database administrator.
<b>INOXYE9129</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9130</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9131</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9132</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9133</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.

---

<b>INOXYE9134</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9135</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9136</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9137</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9138</b>	<b>Bufferpool too small</b>
<b>Explanation</b>	The buffer pool is too small to keep all data to be processed. In most cases this is caused by large amount of lock data.
<b>Action</b>	Increase the value of database property "buffer pool size".
<b>INOXYE9139</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9140</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9141</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.

**INOXYE9142**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9143**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9144**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9145**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9146**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9147**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9148**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9149**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

<b>INOXYE9150</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9151</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9152</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9153</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9154</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9155</b>	<b>The requested document(s) could not be locked</b>
<b>Explanation</b>	An _XQL request was issued with _LOCKWAIT=no and _ISOLATION=shared/protected. At least one of the requested documents was locked by another user, therefore the lock could not be granted immediately.
<b>Action</b>	Retry the query, or specify _LOCKWAIT=yes.
<b>INOXYE9156</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9157</b>	<b>Locking conflict has occurred</b>
<b>Explanation</b>	The concurrently active transactions have issued conflicting lock requests.
<b>Action</b>	No action required.

**INOXYE9158**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9159**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9160**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9161**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9162**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9163**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9164**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9165**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

---

<b>INOXYE9166</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9167</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9168</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9169</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9170</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9171</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9172</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9173</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.

**INOXYE9174**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9175**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9176**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9177**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9178**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9179**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9180**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9181**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

---

<b>INOXYE9182</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9183</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9184</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9185</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9186</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9187</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9188</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9189</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.

**INOXYE9190**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9191**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9192**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9193**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9194**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9195**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9196**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9197**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

---

<b>INOXYE9198</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9199</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9200</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9201</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9202</b>	<b>Unique constraint violated</b>
<b>Explanation</b>	Tamino detected either a duplicate ino:docname or a duplicate value for a unique constraint.
<b>Action</b>	Either choose a unique ino:docname or modify the documents.
<b>INOXYE9203</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9204</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9205</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.

**INOXYE9206**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9207**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9208**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9209**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9210**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9211**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9212**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9213**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

---

<b>INOXYE9214</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9215</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9216</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9217</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9218</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9219</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9220</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9221</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.

<b>INOXYE9222</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9223</b>	<b>Failed to create an additional database container</b>
<b>Explanation</b>	Tamino failed to create an additional database container. This might be caused for example by a full disk or if the auto-expand option is set to "no".
<b>Action</b>	Analyze and remove the cause of the error. Typically, the job log of the database session will provide more information. In the Tamino Manager, select the node "Job Monitor" below "Tamino", and view the job of the database session in the category "Running Jobs" or "Pending Alerts".
<b>INOXYE9224</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9225</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9226</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9227</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9228</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.

---

<b>INOXYE9229</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9230</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9231</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9232</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9233</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9234</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9235</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9236</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.

**INOXYE9237**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9238**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9239**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9240**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9241**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9242**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9243**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9244**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

---

<b>INOXYE9245</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9246</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9247</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9248</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9249</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9250</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9251</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9252</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.

**INOXYE9253**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9254**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9255**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9256**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9257**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9258**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9259**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9260**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

---

<b>INOXYE9261</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9262</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9263</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9264</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9265</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9266</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9267</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9268</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.

**INOXYE9269**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9270**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9271**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9272**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9273**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9274**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9275**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

**INOXYE9276**      **Internal database error has occurred**  
**Explanation**      An internal error occurred. This could result in incorrect data.  
**Action**              Please contact your software supplier.

---

<b>INOXYE9277</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9278</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9279</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9280</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9281</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9282</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9283</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9284</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.

<b>INOXYE9285</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9286</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9287</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9288</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9289</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9290</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9291</b>	<b>Transaction aborted because it has taken too long</b>
<b>Explanation</b>	The duration of the transaction has exceeded the maximum transaction duration. This can be caused by several circumstances: 1) The transaction could have done too much work to complete in the given time frame. 2) The number of transactions running in parallel has caused considerable delays in transaction execution. 3) The transaction might have waited for a resource that was held by another transaction for a very long time. In particular, this can happen if the number of XML work threads is too low. In this case, the transactions waiting for a resource block the XML work threads, and no XML work thread is available for the transaction holding the resource. 4) The transaction had to wait for a free XML work thread for a long time
<b>Action</b>	The maximum transaction duration and the number of XML work threads can be configured using the Tamino Manager.

---

<b>INOXYE9292</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9293</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9294</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9295</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9296</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9297</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9298</b>	<b>Internal database error has occurred</b>
<b>Explanation</b>	An internal error occurred. This could result in incorrect data.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9484</b>	<b>Marked corrupt index for subsequent repair: collection name = COLL_NAME, node = NODE_PATH</b>
<b>Explanation</b>	A corrupt index has been found and has been marked for index repair. It will not be used for query processing until it has been repaired.
<b>Action</b>	Repair indexes in the corresponding doctype using <code>_admin=ino:RepairIndex()</code> - then retry the operation and recreate the index if necessary.

<b>INOXYE9485</b>	<b>Failed to prepare index marked as corrupt for subsequent repair index: collection name = COLL_NAME, node = NODE_PATH, reason = REASON</b>
<b>Explanation</b>	An error occurred when attempting to prepare a corrupt index for a subsequent index repair.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9486</b>	<b>Failed to mark index as corrupt due to a pending recreate index operation: collection name = COLL_NAME, node = NODE_PATH</b>
<b>Explanation</b>	A corrupt index cannot be marked as corrupt while a recreate index operation or schema update is pending.
<b>Action</b>	Repair the indexes in the corresponding doctype using <code>_admin=ino:RepairIndex()</code> - then retry the operation and recreate the index if necessary.
<b>INOXYE9487</b>	<b>Failed to mark index as corrupt due to recreate index operation in progress: collection name = COLL_NAME, node = NODE_PATH</b>
<b>Explanation</b>	A corrupt index cannot be marked while a recreate index operation or schema update is in progress.
<b>Action</b>	Wait until recreate index operation or schema update on the corresponding doctype is finished, then retry the operation or recreate the index.
<b>INOXYE9488</b>	<b>Error during index or constraint access</b>
<b>Explanation</b>	An index or constraint is corrupted and must be recreated.
<b>Action</b>	Recreate all indexes and constraints of the doctype via <code>ino:RecreateIndex</code> admin command.
<b>INOXYE9489</b>	<b>Error during index or constraint access</b>
<b>Explanation</b>	An index or constraint is corrupted.
<b>Action</b>	Please contact your software supplier.
<b>INOXYE9490</b>	<b>Error during index or constraint access</b>
<b>Explanation</b>	An index or constraint is corrupted and must be recreated.
<b>Action</b>	Recreate the indexes and constraints via the <code>ino:RecreateIndex</code> admin command or update define.

---

<b>INOXYE9491</b>	<b>Transaction aborted due to non-activity timeout</b>
<b>Explanation</b>	The transaction has been aborted because there was no activity for a long time.
<b>Action</b>	The time period for non-activity timeout can be configured using the Tamino Manager (Property "non-activity timeout").
<b>INOXYE9492</b>	<b>Transaction aborted due to administrator action</b>
<b>Explanation</b>	The database administrator has cancelled this transaction.
<b>Action</b>	No action required.
<b>INOXYE9493</b>	<b>Transaction aborted because journal space was too small</b>
<b>Explanation</b>	The journal space could not accommodate all the information that was necessary to back out the update command.
<b>Action</b>	Enlarge the journal space.
<b>INOXYE9494</b>	<b>Request terminated because it tried to modify a replication database</b>
<b>Explanation</b>	The request was sent to a replication database. User requests are not allowed to modify a replication database; only the replication process can do this.
<b>Action</b>	Send your request to the master of this replication database.
<b>INOXYE9495</b>	<b>Request terminated because the replication database is currently not up-to-date</b>
<b>Explanation</b>	The database is set to replication type with 'Simultaneous Query', but the currently replicated log space of the server does not contain additional locking information. Therefore the database cannot process queries while it replicates updates of this log space. Simultaneous query will be enabled, however, when the log space of the current session of the master is replicated.
<b>Action</b>	Wait until the log space of a session is replicated that permits simultaneous queries.  Alternatively, send your request to the master of this replication database.
<b>INOXYE9496</b>	<b>Transaction aborted due to deadlock</b>
<b>Explanation</b>	The lock requests of concurrent transactions have caused a deadlock.
<b>Action</b>	No action required.

<b>INOXYE9497</b>	<b>Transaction terminated because of ongoing replication process</b>
<b>Explanation</b>	There is a replication process in progress that does not allow simultaneous queries.  Because the replication process always has top priority on a replication database, any user transactions that had been active were terminated.
<b>Action</b>	Wait until the replication process has finished or starts another session that allows simultaneous queries.  Alternatively send your request to the master of this replication database.
<b>INOXYE9498</b>	<b>Request terminated due to database shutdown</b>
<b>Explanation</b>	The request has been terminated because the database is being shut down.
<b>Action</b>	No action required.
<b>INOXYE9499</b>	<b>Transaction aborted due to non-activity timeout or administration intervention</b>
<b>Explanation</b>	The transaction has been aborted because there was no activity for a long time or because it was stopped by the database administrator.
<b>Action</b>	The time period for non-activity timeout can be configured using the Tamino Manager (Property "non-activity timeout").
<b>INOXYW9483</b>	<b>Found indexes marked as corrupt which cannot be dropped - subsequent index repair with "continue" option required: collection name = COLL_NAME, doctype = DOCTYPE_NAME</b>
<b>Explanation</b>	A Tamino doctype contains indexes which must not be dropped, e.g. because they are used to implement a unique constraint.
<b>Action</b>	Issue <code>_admin=inoRepairIndex()</code> with the "continue" option for the same doctype in order to fix the corrupt indexes.

# 27

## Trading Network Messages

---

<b>1003</b>	<b>System property {0} is invalid: {1}. To correct the property, go to the TN Properties page of the WmTN package in the Integration Server Administrator, or edit the "packagesWmTNconfigproperties.cnf" file.</b>
<b>Explanation</b>	The system property provided for Trading Networks is invalid.
<b>Action</b>	Correct the property in the Configure Properties page in My webMethods, or edit the 'IntegrationServer_directory\packages\WmTN\config\properties.cnf' file.
<b>1008</b>	<b>"{0}" is required.</b>
<b>Explanation</b>	Required input value is missing.
<b>Action</b>	Provide value for required input fields and try again.
<b>1027</b>	<b>You have attempted to use a feature that is restricted by your license. To be able to use all product features, please contact webMethods or your webMethods OEM solution provider to upgrade to an unrestricted version of Trading Networks.</b>
<b>Explanation</b>	User not allowed to create doctypes, attempt failed.
<b>Action</b>	To be able to use all product features, please contact Software AG Global Support to upgrade to an unrestricted version of Trading Networks.
<b>1035</b>	<b>User Status value(s) {0} already exist.</b>

<b>1046</b>	<b>Error registering TN's XML content handler.</b>
<b>Explanation</b>	Error while registering content handler for "text/xml".
<b>Action</b>	Contact Software AG Global Support.
<b>1119</b>	<b>Encountered error while creating TN document</b>
<b>1157</b>	<b>New verify certificate set not added.</b>
<b>Explanation</b>	In webMethods Trading Networks, if a verify certificate set is not added to a partner, this error shows up.
<b>Action</b>	Add the very certificate set to the partner and try again.
<b>1158</b>	<b>New verify certificate set not updated.</b>
<b>Explanation</b>	In webMethods Trading Networks, if the new verify certificate set for a partner is not updated, this error shows up.
<b>Action</b>	Ensure that the new verify certificcate set for a partner is updated and try again.
<b>1160W</b>	<b>Asset already exists in Trading Networks</b>
<b>Explanation</b>	The asset selected for import already exists in Trading Networks.
<b>Action</b>	To overwrite the existing asset with the one in the imported file, select the "force" option during the import process.
<b>1161E</b>	<b>An error occurred while retrieving package names.</b>
<b>Explanation</b>	My webMethods encountered an error while displaying the names of Integration Server packages.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception and try to perform the action again.
<b>1162W</b>	<b>All processing rules were imported successfully. Processing rules that existed before the import were removed.</b>
<b>Explanation</b>	All the processing rules present in the import file were added to the Trading Networks database. All processing rules that existed before the import process were removed from the database. This happens when the Replace Rule List option is selected during the import of Trading Networks data.

---

1166	<b>Unable to delete doc type. There are some activity logs associated with this doc type. Either delete the associated activity logs or run this service again with "deleteLogs=true" to have them deleted automatically.</b>
<b>Explanation</b>	Unable to delete doc type because there are some activity logs associated with this doc type.
<b>Action</b>	Either delete the associated activity logs or run this service again with "deleteLogs=true" to have them deleted automatically.
1170	<b>Unable to import processing rule {0}. Document type(s) used in the processing rule is not defined.</b>
1171	<b>inserted</b>
1172	<b>updated</b>
1173	<b>deleted</b>
1174	<b>Inserted.</b>
1175	<b>Updated.</b>
1176	<b>Deleted.</b>
1177	<b>Invalid status provided. Provide the proper status.</b>
1178	<b>Manage Export Import</b>
1179	<b>The {0} you are trying to save has been modified by another user. To ensure that you are using the latest version, cancel your changes and reopen the {1}. Modify the latest version and save your changes</b>

**1203E**                    **Error retrieving certificates for keystore alias {0} and key alias {1}. Check the keystore configuration in Integration Server.**

**Explanation**            The keystore was modified or deleted in Integration Server, which caused the keystore mapping in Trading Networks to break.

**Action**                    Check the keystore configuration in Integration Server. If the keystore does not exist in Integration Server, create the keystore. If the keystore mapping in Trading Networks is incorrect, select the correct keystore alias and key name for the certificate.

**1204E**                    **Error retrieving keystore aliases.**

**Explanation**            Trading Networks could not retrieve the keystore from Integration Server.

**Action**                    Check the keystore configuration in Integration Server. If the keystore does not exist in Integration Server, ask the Integration Server administrator to create the keystore.

**1205E**                    **Error retrieving key aliases for the keystore alias {0}.**

**Explanation**            Trading Networks could not retrieve the keystore from Integration Server.

**Action**                    Check the keystore configuration in Integration Server. If the keystore does not exist in Integration Server, ask the Integration Server administrator to create the keystore.

**19000**                    **Invalid facet provided to API - {0}.**

**19001E**                    **Error occurred while initializing Trading Networks charts during initialization of Trading Networks.**

**Explanation**            Trading Networks charts could not be initialized due to an error faced during startup.

**Action**                    Restart Trading Networks.

**19002E**                    **Error occurred while initializing Trading Networks dashboarding store during initialization of Trading Networks.**

**Explanation**            Trading Networks dashboarding store could not be initialized due to an error faced during startup.

**Action**                    Restart Trading Networks.

**19003**                    **Hour value {0} is not in range.**

---

<b>19004</b>	<b>Dashboarding API inputs not valid.</b>
<b>19005E</b>	<b>Error occurred during Analytics API call.</b>
<b>Explanation</b>	An error occurred during Analytics API call.
<b>Action</b>	Check the Trading Networks logs for the cause of the failure and if required, contact your system administrator.
<b>19006E</b>	<b>afterDays parameter cannot be null.</b>
<b>Explanation</b>	afterDays parameter cannot be null.
<b>Action</b>	Supply a value for afterDays parameter.
<b>19007E</b>	<b>afterDays parameter should be a positive integer.</b>
<b>Explanation</b>	afterDays parameter provided is not a positive integer.
<b>Action</b>	Supply a valid value for afterDays parameter. The value must be a positive integer.
<b>19008</b>	<b>batchSize parameter should be a positive integer.</b>
<b>19010</b>	<b>API error</b>
<b>19011</b>	<b>Transaction data {0} written to dashboarding table</b>
<b>2017</b>	<b>Could not delete field definition</b>
<b>2020E</b>	<b>Error occurred while publishing event messages to ERF.</b>
<b>Explanation</b>	An error occurred while publishing event messages to NERV.
<b>Action</b>	Check the Trading Networks logs for the cause of the failure and if required, contact your system administrator.
<b>2021</b>	<b>Successfully published event message of type {0} to ERF.</b>

<b>2023</b>	<b>Error redefining type {0} ({1})</b>
<b>Explanation</b>	Error while updating the document type.
<b>Action</b>	The exception is in the full message. Take appropriate action to resolve the problem described in the exception.
<b>2061</b>	<b>Error initializing type cache.</b>
<b>Explanation</b>	There may have been an SQLException that prevented the initialization of the document type cache.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>2069</b>	<b>Error while defining type {0} ({1}).</b>
<b>Explanation</b>	The error encountered while defining the document type may be due to an SQLException or to a missing mandatory field.
<b>Action</b>	Look at the associated error message or stack trace in the logs and take appropriate action.
<b>2103</b>	<b>MODIFY AND RESUBMIT</b>
<b>2105</b>	<b>Invalid input. Provide a value from the configured list of User Status values.</b>
<b>2120</b>	<b>Error initializing attribute cache.</b>
<b>Explanation</b>	An SQLException may have prevented the attribute cache from being initialized.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>2174</b>	<b>Unable to import init.xml due to exception message: {0}. Manually import init.xml as described in the Installation Guide.</b>
<b>Explanation</b>	An exception occurred while importing init.xml, as described in the message.
<b>Action</b>	Manually import init.xml as described in the Installation Guide.
<b>2200...0</b>	<b>Error encountered while reading USER status from the database. Exception message: {0}.</b>
<b>Explanation</b>	Encountered SQLException while reading user status from database.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

---

2262	<b>Processing of invitation failed. {0}</b>
2263	<b>User not created for the partner.</b>
2264	<b>Updating the partner status to Invited has failed.</b>
2265	<b>Error occurred while changing the status of the invitations.</b>
2266	<b>Error occurred while changing the status of the following invitation: {0}.</b>
2267	<b>Error occurred while changing the status of the following archival service: {0}.</b>
2268	<b>Error occurred while changing the status of the archival services.</b>
2269	<b>Error occurred while changing the status of the invitations. The status should be either {0} or {1}.</b>
2270	<b>Error occurred while changing the status of the archival services. The status should be either {0} or {1}.</b>
2271	<b>Error occurred while changing the status of the queues. The status should be either {0}, {1}, {2}, or {3}.</b>
2272	<b>Error occurred while changing the status of the following invitation: {0}. Check the invite and provide all the necessary details.</b>
2303	<b>Exception encountered while getting TN assets dependency.</b>
<b>Explanation</b>	In the webMethods Trading Networks Export Import feature using MWS, when webMethods Trading Networks fails to get the dependency of the asset type during export, this exception is thrown.
<b>Action</b>	You need to select the dependent asset and perform the export again.

<b>2304</b>	<b>Exception encountered while exporting TN assets.The exception message is : {0}.</b>
<b>Explanation</b>	In the webMethods Trading Networks Export Import feature using MWS, when webMethods Trading Networks fails to get the asset data during export, this exception is thrown.
<b>Action</b>	Contact your system administrator.
<b>2305</b>	<b>Exception encountered while importing TN assets.The exception message is : {0}.</b>
<b>Explanation</b>	In the webMethods Trading Networks Import feature using MWS, when webMethods Trading Networks fails to import data, this exception is thrown.
<b>Action</b>	Contact your system administrator.
<b>2306</b>	<b>The import data file name is null or empty.</b>
<b>Explanation</b>	In webMethods Trading Networks, when you try to import data and the import data file name is null or empty, this error is thrown.
<b>Action</b>	Import the data again after adding the import data file.
<b>2307</b>	<b>The import data file {0} does not exist.</b>
<b>Explanation</b>	In webMethods Trading Networks, when you try to import a data file but the file does not exist, this error is thrown.
<b>Action</b>	Ensure that the file is available and try again.
<b>2308</b>	<b>The import file does not contain valid data.</b>
<b>Explanation</b>	In webMethods Trading Networks, when you try to import a file and it does not contain valid data according to the type format, this error is thrown.
<b>Action</b>	Add a file that contains valid data according to the type format and try to import it again.
<b>24001E</b>	<b>Error occurred for the following Document ID while writing to TRANSACTIONSUMMARYDATA table:{0}.</b>
<b>Explanation</b>	Writing to TransactionSummaryData table might fail due to many reasons. One reason is when the Trading Networks database is down.
<b>Action</b>	Check the Integration Server logs for the cause of the failure and if required, contact your system administrator.

- 24002           **Volume value summary data for the following Document ID was successfully written to CUSTOMATTRIBUTEVOLUMEVALUE table: {0}.**
- 24003           **Error occurred for the following Document ID while writing to CUSTOMATTRIBUTEVOLUMEVALUE table:{0}.**
- 24004           **Success and failed transactions summary data for the following Document ID was successfully written to TRANSACTIONSUCCESSFAILEDDATA and SUCCESSFAILEDCHARTDOCIDMAP tables: {0}.**
- 24005           **Error occurred for the following Document ID while writing to TRANSACTIONSUCCESSFAILEDDATA and SUCCESSFAILEDCHARTDOCIDMAP tables:{0}.**
- 24006           **Success and failed transactions summary data for the following Document ID was successfully updated in TRANSACTIONSUCCESSFAILEDDATA and SUCCESSFAILEDCHARTDOCIDMAP tables: {0}.**
- 24007           **Error occurred for the following Document ID while updating TRANSACTIONSUCCESSFAILEDDATA and SUCCESSFAILEDCHARTDOCIDMAP tables:{0}.**
- 24008           **Late FA summary data for the following Document ID was successfully written to TRANSACTIONLATEFADATA table: {0}.**
- 24009           **Error occurred for the following Document ID while writing to TRANSACTIONLATEFADATA table:{0}.**
- 24010           **The following custom class required to filter run-time events of type Document Attribute Added based on event's attribute name was not found in classpath: {0}**
- 24011           **The following error occurred while trying to filter run-time events of type Document Attribute Added: {0}**

- 24500**                    **Exception {0} occurred during execution of event processor {1}**
- 25002W**                    **Error occurred while subscribing to {0} run-time event. The dashboards may not display any data.**
- Explanation**            Event processor did not subscribe to the run-time event type due to one of the following reasons:- Trading Networks NERV custom bundle was not copied to the NERV config bundles location.- Universal Messaging server was not up and running.
- Action**                    Ensure the following:- If you are using Trading Networks NERV custom bundle, ensure to copy the bundle to the NERV config bundles location. Refer to 9.7 webMethods Trading Networks Administrators guide for details.- If you are using Universal Messaging, ensure the server is up and running.
- 25003W**                    **Error occurred while unsubscribing from {0} run-time event.**
- Explanation**            Event processor did not unsubscribe from the run-time event type due to one of the following reasons:- Event processor did not subscribe to the run-time event type successfully.- Universal Messaging server was down after the processor subscribed to the run-time event type.
- Action**                    Ensure the following:- If the event processor subscribed to the run-time event type successfully.- If you are using Universal Messaging, ensure the server is up and running at all times.
- 25500**                    **The following error occurred while suspending or unsuspending document delivery for a partner: {2}. The PartnerId is {0}, and the Id of the schedule is {1}.**
- 25501**                    **Error occurred while adding a delivery suspension schedule.**
- 25502**                    **Error occurred while updating a delivery suspension schedule.**
- 25503**                    **Error occurred while viewing a delivery suspension schedule.**
- 25504**                    **Error occurred while deleting a delivery suspension schedule.**
- 25505**                    **Error occurred while activating a delivery suspension schedule.**

25506	<b>Error occurred while deactivating a delivery suspension schedule.</b>
25507	<b>Error occurred while changing the Suspension Status of a delivery suspension schedule.</b>
25508	<b>Error occurred while checking the validity of a delivery suspension schedule.</b>
25509	<b>Error occurred while checking or unchecking the Suspend Delivery checkbox.</b>
25510	<b>An exception occurred while switching a deliverySuspendData validity to {0}.</b>
25511	<b>An exception occurred while selecting invalid status deliverySuspendData.</b>
25512	<b>An exception occurred while selecting invalid status deliverySuspendData.</b>
26000	<b>Error occurred while adding a delivery suspension schedule to Integration Server.</b>
26001	<b>Error occurred while updating a delivery suspension schedule on Integration Server.</b>
26002	<b>Error occurred while viewing a delivery suspension schedule on Integration Server.</b>
26003	<b>Error occurred while cancelling a delivery suspension schedule on Integration Server.</b>
26004	<b>Error occurred on Integration Server while changing the status of a delivery suspension schedule to inactive.</b>
26005	<b>Error occurred on Integration Server while changing the status of a delivery suspension schedule to active.</b>

- 26006            **Successfully added the following delivery suspension schedule to Integration Server: {0}**
  
- 26007            **Successfully updated the following delivery suspension schedule on Integration Server: {0}**
  
- 26008            **Successfully fetched the following delivery suspension schedule from Integration Server: {0}**
  
- 26009            **Successfully cancelled the following delivery suspension schedule on Integration Server: {0}**
  
- 26010            **Successfully suspended the following delivery suspension schedule on Integration Server: {0}**
  
- 26011            **Successfully resumed the following delivery suspension schedule on Integration Server: {0}**
  
- 26012            **Error occurred on Integration Server while checking for the existence of a delivery suspension schedule.**
  
- 26013            **Error occurred while parsing the date and time of a delivery suspension schedule.**
  
- 26014            **Error invoking remote service - {0} for alias - {1}.**
  
- 26015            **Error invoking local service - {0}.**
  
- 26016            **Error occurred retrieving VFS list from ActiveTransfer aliases**
  
- 26017            **ActiveTransfer service is not executable, please check alias - {0} is accessible or not.**

---

26018	<b>Large Document Delivery to remote ActiveTransfer not supported</b>
26019	<b>View Transaction Settings</b>
26020	<b>Edit Transaction Settings</b>
26021	<b>Unable to connect to ActiveTransfer. Contact your System Administrator</b>
3011	<b>(username={0})already exists.No new account created.Mapping done.</b>
<b>Explanation</b>	While creating a partner account, Trading Networks found an existing user with the same name. No new account was created. Mapping was completed..
<b>Action</b>	Provide a unique name and try again.
3012	<b>Encountered error while enabling the {0} package.</b>
<b>Explanation</b>	This error shows up when trying to enable the WmTN package.
<b>Action</b>	Contact your system administrator.
3013	<b>Encountered error while disabling the {0} package.</b>
<b>Explanation</b>	This error shows up while trying to disable the WmTN package.
<b>Action</b>	Contact your system administrator.
3017	<b>An error occurred while trying to insert document (doc id = {0}, sender id = {1}) into the database.</b>
<b>Explanation</b>	Exception occurred during inserting the document into the database, possibly due to a database or usage error.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
3023	<b>No such documents: {0}.</b>
3024	<b>Could not instantiate documents {0}.</b>

- 3025E**            **Error occurred while reinitializing Trading Networks JDBC connection pool in Integration Server.**
- Explanation**    Trading Networks reinitializes the JDBC connection pool when a connection error occurs. This reinitialization disconnects all connections to the Trading Networks database. An error occurred during the reinitialization.
- Action**            Use the Integration Server Administrator JDBC Pools page to reinitialize the Trading Networks JDBC connection pool.
- 
- 3027**            **Exception in finding database specific Class: {0}**
- 
- 3028**            **TPA with id {0} is locked**
- 
- 3068**            **Error while persisting queue. For details check the full stack trace.**
- Explanation**    In webMethods Trading Networks, while registering a queue, if there is any error in scheduling the queue, this error is thrown.
- Action**            Check the full stack trace or contact your system administrator.
- 
- 3069**            **Error occurred while changing the status of the following queue: {0}.**
- 
- 3070**            **Error occurred while changing the status of the queues.**
- 
- 3100**            **Exception occurred while clearing TNASSET\_READTIMEKEEPER table.**
- 
- 3243**            **Cannot process message that is not javax.mail.internet.MimeMessage or javax.mail.internet.MimeBodyPart. Current message is: {0}**
- Explanation**    Cannot parse the message as it is not a javax.mail.internet.MimeMessage or javax.mail.internet.MimeBodyPart.
- Action**            Check the error message and take action as appropriate.
- 
- 4000**            **Successfully saved the {1} delivery suspension schedule to Trading Networks database. The Id of the schedule is {0}.**

---

4001	<b>Successfully updated the {1} delivery suspension schedule on Trading Networks database. The Id of the schedule is {0}.</b>
4002	<b>Successfully fetched the following delivery suspension schedule from Trading Networks database: {0}</b>
4003	<b>Successfully deleted the following delivery suspension schedule from Trading Networks database: {0}</b>
4004	<b>Successfully changed the status of the following delivery suspension schedule to {1} on Trading Networks database: {0}</b>
4005	<b>Successfully changed the suspension status of the following delivery suspension schedule to {1} on Trading Networks database: {0}</b>
4006	<b>Successfully fetched the delivery suspension schedule with PartnerId {0} from Trading Networks database.</b>
4007	<b>A delivery suspension schedule with the following name already exists in Trading Networks database: {0}</b>
4008	<b>Error occured while executing Stored Procedures</b>
4024	<b>Invalid Receiver ID</b>
<b>Explanation</b>	In webMethods Trading Networks, while setting the BizDoc envelope attribute, if the receiver ID is not a valid partner ID, this error is thrown.
<b>Action</b>	Enter a valid partner ID (for a receiver ID) and try again.
4168	<b>Exception encountered while listing all the processing rules.</b>
<b>Explanation</b>	Encountered an exception while getting the list of rules from the cache. Either the cache is not updated with data, or there is some exception in the database.
<b>Action</b>	The details of the exception is in the full message. Take appropriate action to resolve the problem described in the exception message.

<b>4169</b>	<b>Access denied, as the User "{0}" does not have the privilege to {1} {2}.</b>
<b>Explanation</b>	You do not have the required permission to take this action on the processing rule.
<b>Action</b>	Request that the Integration Server administrator assign the required permission.
<b>4170</b>	<b>Error while recognizing the document.</b>
<b>Explanation</b>	Error encountered while recognizing the document. The document may be corrupted.
<b>Action</b>	Check if the document is a valid XML document and not a corrupt document.
<b>4177</b>	<b>{0} contacts deleted with ContactID {1}.</b>
<b>Explanation</b>	Encountered data inconsistency issue while contact deletion. Expected exactly one matching contact.
<b>Action</b>	Contact Software AG Global Support.
<b>4178</b>	<b>{0} addresses deleted with AddressID {1}.</b>
<b>Explanation</b>	Encountered data inconsistency issue while address deletion. Expected exactly one matching address.
<b>Action</b>	Contact Software AG Global Support.
<b>4179</b>	<b>{0} connections deleted with ID {1}.</b>
<b>Explanation</b>	Encountered data inconsistency issue while destination deletion. Expected exactly one matching destination.
<b>Action</b>	Contact Software AG Global Support.
<b>4209</b>	<b>Error encountered while getting the host ID</b>
<b>Explanation</b>	The Trading Networks profile cache might be corrupted.
<b>Action</b>	The details of the exception are in the full message. Take appropriate action to resolve the problem described in the exception message.
<b>4210</b>	<b>Error encountered while getting all the Processing Rule matches for the document.</b>
<b>Explanation</b>	Encountered exception while retrieving rules from cache. The cache might not be updated.
<b>Action</b>	The details of the exception are in the full message. Take appropriate action to resolve the problem described in the exception message. Reload the WmTNWeb package.

---

<b>4211</b>	<b>Error encountered while getting all the Delivery Services.</b>
<b>Explanation</b>	Encountered exception while retrieving delivery services from the database.
<b>Action</b>	The details of the exception are in the full message. Take appropriate action to resolve the problem described in the exception message.
<b>4212</b>	<b>Error encountered while getting RuleName with the name - {0}.</b>
<b>Explanation</b>	The rule may have been deleted by someone in a different session.
<b>Action</b>	Refresh the rule cache by executing the search again.
<b>4213</b>	<b>Error encountered while getting Last Change ID.</b>
<b>Explanation</b>	This may be due to an exception while fetching the Last Change ID from the database.
<b>Action</b>	The details of the exception are in the full message. Take appropriate action to resolve the problem described in the exception message.
<b>4214</b>	<b>Error encountered while getting Processing Rule with ID - {0}.</b>
<b>Explanation</b>	The rule may have been deleted by someone in a different session.
<b>Action</b>	Refresh the rule cache by running the search again.
<b>4215</b>	<b>Error encountered while changing the ordinality of the Processing Rule.</b>
<b>Explanation</b>	Changing the ordering of the processing rules in another session might have caused an error while validating or updating the ordinal numbering in the database.
<b>Action</b>	Refresh the rule cache by executing the search again.
<b>4216</b>	<b>Error encountered while deleting the processing rules.</b>
<b>Explanation</b>	The rule might have been deleted by someone in a different session.
<b>Action</b>	Refresh the rule cache by executing the search again.
<b>4217</b>	<b>Error encountered while updating the processing rule with Rule Name - {0}.</b>
<b>Explanation</b>	The rule might have been deleted by someone in a different session.
<b>Action</b>	Refresh the rule cache by executing the search again.

<b>4218</b>	<b>Error encountered while creating the processing rule with Rule Name - {0}.</b>
<b>Explanation</b>	Error encountered while inserting the rule into the database.
<b>Action</b>	The details of the exception are in the full message. Take appropriate action to resolve the problem described in the exception message.
<b>4219</b>	<b>Error encountered while querying the processing rules.</b>
<b>Explanation</b>	The query would have failed while picking the rules. Check the database actions.
<b>Action</b>	The details of the exception are in the full message. Take appropriate action to resolve the problem described in the exception message.
<b>4220</b>	<b>Access denied, as the User "{0}" does not have the permission to {1} processing rule.</b>
<b>Explanation</b>	You do not have the permission to do the necessary action on the processing rule.
<b>Action</b>	Request that the Integration Server administrator assign the required permission.
<b>4221</b>	<b>Access denied, as the User "{0}" does not have the permission to {1} processing rule - "{2}".</b>
<b>Explanation</b>	You do not have the permission to do the necessary action on the processing rule.
<b>Action</b>	Request that the Integration Server administrator assign the required permission.
<b>4228</b>	<b>Exception while changing the processing rule status.</b>
<b>Explanation</b>	The rule might have been deleted by someone in a different session.
<b>Action</b>	Refresh the rule cache by executing the search again.
<b>4237</b>	<b>Error encountered while getting the profiles associated with Profile Group.</b>
<b>Explanation</b>	There might be a database error while retrieving the profile groups.
<b>Action</b>	The details of the exception are in the full message. Take appropriate action to resolve the problem described in the exception message.
<b>4238</b>	<b>Access denied, as the User "{0}" does not have the permission to {1} processing rule - "{2}".</b>
<b>Explanation</b>	You do not have the permission to do the necessary action on the processing rule.
<b>Action</b>	Request that the Integration Server administrator assign the required permission.

---

<b>4241E</b>	<b>Processing rule "{0}" change status failed. Processing rule update collision detected. This rule has been modified by another user. Refresh your rule list and retry this operation.</b>
<b>Explanation</b>	In webMethods Trading Networks, while changing the status of a processing rule, if it is modified by another user, this error is thrown.
<b>Action</b>	Refresh your rule list and try again.
<b>4247E</b>	<b>Exception encountered while moving the processing rule. Invalid Ordinal given in Select Location.</b>
<b>Explanation</b>	In webMethods Trading Networks, while moving the processing rule, if an invalid ordinal location is specified, this error is thrown.
<b>Action</b>	Specify a valid ordinal location and try again.
<b>4258E</b>	<b>Error encountered while creating the processing rule with Rule Name - "{0}". Rule name already exists. Change the name and save again.</b>
<b>Explanation</b>	In webMethods Trading Networks, while creating a processing rule, if the rule name already exists, this error is thrown.
<b>Action</b>	Ensure to give a unique processing rule name and try again.
<b>4274E</b>	<b>Error encountered while querying for the delivery queues.</b>
<b>Explanation</b>	In webMethods Trading Networks, if any error occurs while retrieving registered queues, this error is thrown.
<b>Action</b>	Contact your system administrator.
<b>4305E</b>	<b>The following sender(s) and receiver(s) configured in the processing rule do not exist in the system. Sender(s):"{0}" Receiver(s):"{1}"</b>
<b>Explanation</b>	An error occurred while trying to create or update a processing rule with senders and receivers that do not exist in Trading Networks.
<b>Action</b>	Ensure the senders and receivers are valid.
<b>4306E</b>	<b>The following sender(s) configured in the processing rule do not exist in the system: "{0}"</b>
<b>Explanation</b>	An error occurred while trying to create or update a processing rule with senders that do not exist in Trading Networks.
<b>Action</b>	Ensure the senders are valid.

<b>4307E</b>	<b>The following receiver(s) configured in the processing rule do not exist in the system: "{0}"</b>
<b>Explanation</b>	An error occurred while trying to create or update a processing rule with receivers that do not exist in Trading Networks.
<b>Action</b>	Ensure the receivers are valid.
<b>4415</b>	<b>IS DocType signature (ISDocType ={0}) is invalid. Provide a valid IS DocType signature.</b>
<b>Explanation</b>	Exception encountered while loading the corresponding IS docType.
<b>Action</b>	Check whether the namespace of the corresponding IS docType is correct.
<b>4416</b>	<b>Cannot add extended field definition. Extended field with name "{0}" already exists.</b>
<b>Explanation</b>	Extended field with same name already exists.
<b>Action</b>	Supply different name for extended field.
<b>4417</b>	<b>Cannot update extended field definition. Extended field with name "{0}" already exists.</b>
<b>Explanation</b>	Extended field with same name already exists.
<b>Action</b>	Supply a different name for the extended field.
<b>4422</b>	<b>A problem was encountered deleting the field definition.</b>
<b>4423</b>	<b>Created New Permission "{0}" for role "{1}".</b>
<b>4424</b>	<b>Deleted Permission "{0}" for role "{1}".</b>
<b>4429E</b>	<b>Importing a profile for {0} (id={1}), which is marked as "My Enterprise", but it has different ID than the existing My Enterprise profile for this Trading Network. Cannot change the identity of the My Enterprise profile.</b>
<b>Explanation</b>	You are attempting to import a partner profile marked as "My Enterprise." However, the target Trading Networks server already contains a My Enterprise profile, with a different ID. The existing My Enterprise cannot be overwritten because the IDs are different.
<b>Action</b>	Import the partner data without selecting the "My Enterprise" profile.

---

<b>4430E</b>	<b>Importing a profile for {0} (id={1}), which is marked as "My Enterprise". A "My Enterprise" profile already exists for this Trading Network. If you want to update it, use the Force option.</b>
<b>Explanation</b>	You are attempting to import a partner profile marked as "My Enterprise" without using the "Force import" option; however, the target Trading Networks server already contains a My Enterprise profile.
<b>Action</b>	Import the partner data using the "Force import" option.
<b>4431E</b>	<b>Error encountered while adding DLS artifacts with name {0}. The permissions for role {1} is null or empty.</b>
<b>Explanation</b>	You are attempting to import or add a DLS dataset, but the dataset does not contain any permissions.
<b>Action</b>	If you are adding a DLS dataset, specify the required permissions for the dataset. If you are importing a DLS dataset, make sure that the data is correct.
<b>4432</b>	<b>Error encountered while adding DLS artifacts with name {0}. The role name is null or empty.</b>
<b>Explanation</b>	You are attempting to import or add a DLS dataset, but the dataset does not contain any roles.
<b>Action</b>	If you are adding a DLS dataset, specify the required roles for the dataset. If you are importing a DLS dataset, make sure that the data is correct.
<b>4433E</b>	<b>Error encountered while adding DLS artifacts with name {0}. The partner with name {1} is referenced in DLS data, but this partner does not exist on your Trading Networks system.</b>
<b>Explanation</b>	You are attempting to import or add a DLS dataset, but the partner specified in the dataset is not present in the Trading Networks database.
<b>Action</b>	If this happens while importing a DLS dataset, make sure that the dependent partner profile is also imported along with the DLS dataset.
<b>4434E</b>	<b>Error encountered while adding DLS artifacts with name {0}. The document type with name {1} is referenced in DLS data, but this document type does not exist on your Trading Networks system.</b>
<b>Explanation</b>	You are attempting to import or add a DLS dataset, but the document type specified in the dataset is not present in the Trading Networks database.
<b>Action</b>	If this happens while importing a DLS dataset, make sure that the dependent document type is also imported along with the DLS dataset.

**4435E**                    **Error encountered while adding DLS artifacts with name {0}. The processing rule with name {1} is referenced in DLS data, but this processing rule does not exist on your Trading Networks system.**

**Explanation**            You are attempting to import or add a DLS dataset, but the processing rule specified in the dataset is not present in the Trading Networks database.

**Action**                    If this happens while importing a DLS dataset, make sure that the dependent processing rule is also imported along with the DLS dataset.

**4436W**                    **A deleted profile with the same internal id already exists. Unable to recreate a deleted profile.**

**Explanation**            You are attempting to import a partner. However, the target Trading Networks server already contains a deleted partner with the same ID.

**Action**                    Import the partner using the "Force import" option.

**4461**                    **Profile has errors.**

**Explanation**            In webMethods Trading Networks, while adding a profile information, if the profile has any error, this error message is displayed.

**Action**                    Contact your system administrator.

**4464**                    **Attempt to import extended field "{0}" associated with the fieldgroup "{1}" failed. The extended field "{0}" associated with the fieldgroup "{1}" is not defined on your Trading Networks system.**

**Explanation**            This error occurred because the extended field associated with the fieldgroup is not defined on your Trading Networks system.

**Action**                    Define the extended field associated with the fieldgroup on your Trading Networks system and try again.

**4467**                    **Administering Partner Onboarding**

**4468**                    **The invitation with id "{0}" does not exist.**

**4469**                    **Error occurred while changing the status of the partners.**

---

4470	<b>Error occurred while changing the status of the following partner: {0}.</b>
4471	<b>Partner Delivery Suspended</b>
4472	<b>Partner Delivery Unsuspended</b>
4473	<b>Error encountered deleting contact (contactID={0}).</b>
4474	<b>Error encountered deleting address (addressID={0}).</b>
4500	<b>A database error occurred while deleting a Binary Type.</b>
<b>Explanation</b>	In webMethods Trading Networks, at the time of deleting a binary type, if there is a database error, then this error shows up.
<b>Action</b>	Contact your system administrator.
5030	<b>Exception encountered while adding a new TPA.</b>
<b>Explanation</b>	Encountered an exception while writing the TPA to the database. There might be an SQL Exception while writing to the database or some of the constraints were missed out.
<b>Action</b>	The details of the exception are in the full message. Take appropriate action to resolve the problem described in the exception message.
5031	<b>Exception encountered while updating the TPA.</b>
<b>Explanation</b>	Encountered an exception while writing the TPA to the database. There might be an SQL Exception while writing to the database or some of the constraints were missed out.
<b>Action</b>	The details of the exception are in the full message. Take appropriate action to resolve the problem described in the exception message.
5032	<b>Exception encountered while fetching the TPA.</b>
<b>Explanation</b>	Encountered an exception while fetching the TPA from the database. There might be an SQL Exception while retrieving the TPA from the database or there are TPA caching errors.
<b>Action</b>	The details of the exception are in the full message. Take appropriate action to resolve the problem described in the exception message.

- 5033**                    **Exception encountered while deleting the TPA.**
- Explanation**        Encountered an exception while deleting the TPA from the database. This may be because of SQL Exception during writing to database or may be due to removing the TPA from Cache.
- Action**                The details of the exception are in the full message. Take appropriate action to resolve the problem described in the exception message.
- 
- 5034**                    **No initial value created for tpaData.**
- Explanation**        The tpaData parameter was not created. A wrong service output might have caused the issue.
- Action**                Check if the initService defined in the TPA is correct and generates the correct output. The output of the TPA initService must generate an IData for the "tpaData" parameter.
- 
- 5036E**                 **An exception occurred while retrieving TPA names.**
- Explanation**        My webMethods encountered an error while displaying the TPA names.
- Action**                Take appropriate action to resolve the problem described in the exception and try to perform the action again.
- 
- 5037E**                 **An exception occurred while executing the validation service.**
- Explanation**        My webMethods encountered an error while validating TPA data on the Trading Partner Agreement Details page.
- Action**                Take appropriate action to resolve the problem described in the exception and try to perform the action again.
- 
- 5038**                    **No output data was returned by the validation service.**
- Explanation**        The validation service does not conform to the format of the TPA validation service output record "wm.tn.rec:TPAValidateServiceOutput."
- Action**                Correct the service to pass the output in the format described by the output record "wm.tn.rec:TPAValidateServiceOutput."
- 
- 5042**                    **Queue**
- 
- 5043**                    **TPA updated on {0} at {1}**

---

5096	<b>Document delivered via ActiveTransfer. VFS Path: {0} ActiveTransfer Transaction ID: {1}</b>
6006	<b>Export file location not specified</b>
Explanation	Trading Networks is not able to find the export directory location.
Action	Specify the export directory location in the tn.deployer.export.dir TN property
6011	<b>Asset deletion failed - roll back to previous state failed.</b>
Explanation	Trading Networks is not able to delete the asset, because of which rollback to the previous state has failed.
Action	Contact your system administrator.
6013	<b>The binary file is either corrupt or not as expected.</b>
Explanation	The binary file provided for deployment is not valid.
Action	Provide a valid binary file.
6014	<b>The artifact ID is not available in the corresponding artifact properties file.</b>
Explanation	Trading Networks needs the artifact ID for installing the artifacts for deployment. This is missing from the artifact properties file.
Action	Provide the artifact ID in the artifact properties file or recreate the artifact ID.
6015	<b>checkpointId is required.</b>
Explanation	Trading Networks needs the checkpoint ID as input for the execution of the checkpoint service. This is missing.
Action	Add the checkpointId in the checkpoint service.
6016	<b>Delete Archive Schedule failed during rollback.</b>
Explanation	Trading Networks may need to delete the archive schedule during deployment roll back. This deletion of archive schedule has failed during rollback.
Action	Contact your system administrator.

- 6017**                    **Delete Private Queue for Partner failed during rollback.**
- Explanation**        Trading Networks may need to delete the private queue for Partner during deployment roll back. This deletion of private queue has failed during rollback.
- Action**                Contact your system administrator.
- 
- 6018**                    **Delete Public Queue failed during rollback.**
- Explanation**        Trading Networks may need to delete the public queue during deployment roll back. The deletion of public has failed during rollback.
- Action**                Contact your system administrator.
- 
- 6024**                    **The ProductNamespace "{0}" is not specific to Trading Networks.The expected ProductNamespace is "TN".**
- Explanation**        During deployment, a ProductNamespace, which needs to be passed to the service, is required. The expected ProductNamespace specific to Trading Networks that needs to be passed to the service is "TN".
- Action**                Specify the ProductNamespace as TN.
- 
- 6025**                    **The runtime type is not specific to Trading Networks.**
- Explanation**        The Ping service requires type as input. The value of "type" for Trading Networks is TN.
- Action**                Specify type as TN.
- 
- 6026**                    **deploymentId is required.**
- Explanation**        The deleteDeliveredArtifacts and activateArtifacts services need the deploymentId. This is not specified.
- Action**                Specify the deploymentId as the service input.
- 
- 6030**                    **assetIdentifier(s) is required.**
- Explanation**        The Trading Networks assets that are to be deleted has not been provided.
- Action**                Provide the Trading Networks assets.
- 
- 6032**                    **Asset deletion has failed.**
- Explanation**        If the deletion of a Trading Networks asset has failed, this message is displayed.
- Action**                Based on the additional details in the message, you need to fix the issue and try to delete the Trading Networks asset again.

---

<b>6034</b>	<b>Trading Networks is not able to retrieve the asset references for the asset: "{0}" of asset type: "{1}". "{2}"</b>
<b>Explanation</b>	Trading Networks is not able to retrieve the asset references for the specified asset due to an unexpected error.
<b>Action</b>	Try to delete the asset again. If it still does not go through, contact your system administrator.
<b>6056</b>	<b>Access denied. User "{0}" does not have the permission to {1} {2}, for Sender "{3}" and Receiver "{4}".</b>
<b>Explanation</b>	User does not have the permission required to perform the necessary action on the TPA.
<b>Action</b>	Ask the B2B Administrator to assign the user the required permission.
<b>6057</b>	<b>Access denied. User "{0}" does not have the permission to view {1}.</b>
<b>Explanation</b>	User does not have the permission required to view the TPA.
<b>Action</b>	Request the B2B Administrator to assign user the required permission.
<b>7010</b>	<b>{0} is not a valid Trading Networks version. Rerun this program by specifying the supported version of your old Trading Networks.</b>
<b>Explanation</b>	The Trading Networks version selected for migration is not valid.
<b>Action</b>	Rerun this program by specifying the correct version number.
<b>7011</b>	<b>Source Server version is not provided. Rerun this program by specifying the source server version of Trading Networks.</b>
<b>Explanation</b>	The Trading Networks version selected for migration is not provided.
<b>Action</b>	Rerun the migration utility by specifying the version number.
<b>7019</b>	<b>The property file {0} does not exist.</b>
<b>Explanation</b>	The properties.cnf file does not exist.
<b>Action</b>	Add the properties.cnf file to the "IntegrationServer > packages > WmTN > config" location.

<b>7020E</b>	<b>Document Type with name "{0}" already exists. Change the name and save again.</b>
<b>Explanation</b>	Document type with the same name already exists.
<b>Action</b>	Change the document type name and save again.
<b>7021E</b>	<b>Error while changing the status of the doctype.</b>
<b>Explanation</b>	Document type status update operation failed.
<b>Action</b>	See the stack trace and take appropriate action.
<b>7022E</b>	<b>Error while changing the status of the doctype {0}.</b>
<b>Explanation</b>	Document type status update operation failed.
<b>Action</b>	See the stack trace and take appropriate action.
<b>7023</b>	<b>List of doctypes for changing status can not be empty.</b>
<b>Explanation</b>	List of doctypes is a mandatory field.
<b>Action</b>	Configure a list of doctypes while changing the status.
<b>7031</b>	<b>The Trading Networks configuration file was successfully migrated.</b>
<b>7033</b>	<b>The Trading Networks data was successfully migrated.</b>
<b>7034</b>	<b>Started migrating onboarding templates data.</b>
<b>7035</b>	<b>Successfully completed migrating onboarding templates data.</b>
<b>7036</b>	<b>Migrating onboarding templates data failed.</b>
<b>7037</b>	<b>Started migrating onboarding idtype.</b>
<b>7038</b>	<b>Successfully completed migrating onboarding idtype.</b>

---

7039	Migrating onboarding idtype failed.
7040	Migrating Trading Networks dashboard data.
7041	Trading Networks dashboard data
7042	Trading Networks dashboard data was successfully migrated.
7043	Migrating summary data from runtime tables.
7044	Successfully migrated Trading Networks dashboard data.
7045	Failed to migrate Trading Networks dashboard data.
7046	Migrate Trading Networks dashboard data? (Note: This will take longer if runtime data size is big. This operation involves purging of existing data in the dashboard tables, followed by populating data in the dashboard tables from runtime tables.)
7047	Migration selected for Trading Networks dashboard data.
7048	Migration not selected for Trading Networks dashboard data.
7059	Exception while fetching codes list for document type "{0}" and UUID "{1}" .
7060	Invalid document type passed while fetching codes list for document type "{0}" and UUID "{1}" .
8001E	<code>new String[]{"Cannot process message that is not javax.mail.internet.MimeMessage or javax.mail.internet.MimeBodyPart. Current message is: {0} ","","0"}</code>
<b>Explanation</b>	Message cannot be parsed because it is neither a MimeMessage, nor a MimeBodyPart.
<b>Action</b>	Check the message type before invoking the service.

**8013E**                    **Error encountered while downloading sample csv file. Please see error log for more details, contact your Administrator.**

**Explanation**            In webMethods Trading Networks, in Partner Onboarding, while downloading a sample csv file for uploading a partner, if any error is encountered, this message appears.

**Action**                    Contact your system administrator.

**8050**                    **A template field with this name already exists: {0}.**

**Explanation**            In webMethods Trading Networks, while creating a new template field, if the name is not unique, this error shows up.

**Action**                    Ensure to have a unique template field name and try again.

**8052**                    **An exception occurred while inserting template field (ID = "{0}", Name = "{1}").**

**Explanation**            In webMethods Trading Networks, while adding a template field, if an exception occurs while adding a new template field, this error is thrown.

**Action**                    See the exception stack trace to find out the reason for this error.

**8053**                    **An exception occurred while updating template field (ID = "{0}", Name = "{1}").**

**Explanation**            In webMethods Trading Networks, while updating a template field, if an exception occurs while updating the template field, this error occurs.

**Action**                    Check the exception stack trace to find out the reason for the error.

**8054**                    **An exception occurred while inserting template group (ID = "{0}", Name = "{1}").**

**Explanation**            In webMethods Trading Networks, while inserting a template field group, if an exception occurs while updating the template field, this error occurs.

**Action**                    Check the exception stack trace to find out the reason for the error.

**8055**                    **A group with this name already exists: {0}.**

**Explanation**            In webMethods Trading Networks, while adding a group to a questionnaire template, if the name already exists, this error shows up.

**Action**                    Ensure to use a unique group name and try again.

---

8056	<b>An exception occurred while fetching template fields for group(ID = "{0}", Name = "{1}").</b>
<b>Explanation</b>	In webMethods Trading Networks, while fetching template fields for a group, if an exception occurs, this error shows up.
<b>Action</b>	Check the exception stack trace to find out the reason for the error.
8057	<b>A template with this name already exists: {0}.</b>
<b>Explanation</b>	In webMethods Trading Networks, while adding a questionnaire template, if the name already exists, this error shows up.
<b>Action</b>	Ensure to use a unique questionnaire template name and try again.
8059	<b>The invitation has expired. Contact your administrator.</b>
8060	<b>The invitation is disabled now. Contact your administrator.</b>
8061	<b>An exception occurred while querying templates.</b>
8062	<b>changed as following:</b>
8146	<b>VFS Path</b>
8146...0	<b>Sending the new email invitation failed.</b>
9000	<b>Invalid facet provided to API - {0}</b>
9001	<b>Access denied, as the User "{0}" doesnot have the permission to {1} {2}.</b>
<b>Explanation</b>	The corresponding user does not have permissions to perform the associated actions.
<b>Action</b>	Contact a B2B Administrator for granting the corresponding permissions.
9001...0	<b>Please supply the required value.</b>

- 9002**                    **Error encountered while fetching search results, page {0} requested is not found for queryId={1}. Contact your administrator to optimize the configuration of the TNQueryResults cache.**
- Explanation**            In webMethods Trading Networks, while getting the query results, if the page request for a query ID is null, this error is thrown.
- Action**                    Contact your administrator to optimize the configuration of the TNQueryResults cache.
- 
- 9002...0**                **Please restore the original version of this service.**
- 
- 9003**                    **Access denied, as the User "{0}" doesnot have the privilege to {1} {2}.**
- Explanation**            The corresponding user does not have permissions to perform the associated action.
- Action**                    Contact a B2B Administrator for granting the corresponding permissions.
- 
- 9003...0**                **Could not configure Ehcache. Either the SoftwareAG-IS-TN.xml file is missing from the config folder or it is an invalid XML file.**
- 
- 9004**                    **Access denied, as the User "{0}" doesnot have the privilege to view {1}.**
- Explanation**            The corresponding user does not have permissions to view the corresponding Trading Networks asset.
- Action**                    Contact a B2B Administrator for granting the corresponding permissions.
- 
- 9004...0**                **Trading Networks Server startup failed. Error initializing Ehcache manager {0}. Contact your administrator to restore the SoftwareAG-IS-TN.xml file.**
- 
- 9005**                    **Recipient info is not available for the recipientCert**
- 
- 9006E**                    **Primary and secondary certificates already exist for this owner, partner, and usage combination.**
- Explanation**            A maximum of two certificates can be uploaded per unique combination of owner, partner, and usage.
- Action**                    Delete the primary or secondary certificate before uploading an additional certificate.

<b>9007</b>	<b>Error occurred while initializing Ehcache cache manager and accessing cache from it. Error message : {0}.</b>
<b>Explanation</b>	An error occurred while initializing the Ehcache cache manager and accessing cache from it.
<b>Action</b>	Contact your system administrator.
<b>9008</b>	<b>Failed to initialize cache manager for Ehcache. The SoftwareAG_IS_TN.xml file is missing, replaced, or invalid.</b>
<b>Explanation</b>	webMethods Trading Networks failed to initialize the cache manager for Ehcache. The SoftwareAG_IS_TN.xml file is missing, replaced, or invalid.
<b>Action</b>	Add a valid SoftwareAG_IS_TN.xml file in the configurations folder.
<b>9009E</b>	<b>Error occurred while initializing Trading Networks because the following caches are not configured: {0}</b>
<b>Explanation</b>	An error occurred while initializing Trading Networks because one or more caches are not configured.
<b>Action</b>	Check the cache manager SoftwareAG.IS.TN, configure the missing caches, and restart Integration Server.
<b>9010</b>	<b>API error</b>
<b>9012E</b>	<b>Certificate with certificate ID {0} is already the primary certificate.</b>
<b>Explanation</b>	The wm.tn.security:setPrimaryCertificate service was called incorrectly using the certificate ID of a primary certificate.
<b>Action</b>	Specify the certificate ID of the secondary certificate as input to wm.tn.security:setPrimaryCertificate service.
<b>9015</b>	<b>Database error in getting prepared statement or Set proper dequeue strategy map entry</b>
<b>9016</b>	<b>Error encountered in wm.tn.security:setPrimaryCertificate.</b>
<b>TNS.0000.1010E</b>	<b>Error while running archive operation: {0}.</b>
<b>Explanation</b>	Trading Networks encountered an exception while archiving documents.
<b>Action</b>	See the exception in the full message. Take appropriate action to resolve the problem described in the exception.

- TNS.0000.1013**      **{0} could not be completed because another {1} operation was under way or Archive\_WorkTable has contents that were not cleaned up. If there is no archive/deletion service running, cleanup the table to complete the operation.**
- Explanation**      Trading Networks cannot complete the archive or delete operation either because another archive or delete operation is in progress or because the Archive\_WorkTable has contents that need to be cleaned up.
- Action**            If no other archive or delete operation is in progress, clean up the Archive\_WorkTable contents and restart the incomplete archive or delete operation.
- 
- TNS.0000.2004E**    **Cannot save a {0} without a {1}.**
- Explanation**      Trading Networks cannot save the specified profile component because a required field is missing.
- Action**            Enter the value for the required field.
- 
- TNS.0000.2005E**    **Error logging database event.**
- Explanation**      Trading Networks encountered an exception while writing an activity log entry to the database.
- Action**            See the exception written to the server log. Take appropriate action to resolve the problem described in the exception.
- 
- TNS.0000.2006E**    **Error encountered while deleting {0}. {1} rows changed in the database.**
- Explanation**      Instead of deleting exactly one row from a table in the database, Trading Networks deleted the specified number of rows.
- Action**            See the exception written to the server log. Take appropriate action to resolve the problem described in the exception.
- 
- TNS.0000.2008E**    **Table not recognized: {0}.**
- Explanation**      Trading Networks found a profile field in the database that refers to a nonexistent table.
- Action**            Ensure that your query is for an existing profile field.
- 
- TNS.0000.2009E**    **Error while inserting document {0}.**
- Explanation**      Trading Networks encountered an exception while writing a document to the database.
- Action**            See the exception in the full message. Take appropriate action to resolve the problem described in the exception.

---

<b>TNS.0000.2011E</b>	<b>Error while querying documents: {0}. Original SQL: {1}.</b>
<b>Explanation</b>	Encountered an SQLException while performing a document query.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0000.2012E</b>	<b>Inserting field definition failed.</b>
<b>Explanation</b>	Attempted to add a profile field definition, but the database was unchanged.
<b>Action</b>	Contact webMethods Customer Care.
<b>TNS.0000.2016E</b>	<b>An attempt was made to access the SQL statement {0}, which was not defined in the configuration file.</b>
<b>Explanation</b>	Attempted to execute an SQL statement that is not available in the file of externalized SQL statements (dbops.sql).
<b>Action</b>	If you have modified the dbops.sql file, restore the file to its prior state.
<b>TNS.0000.2026E</b>	<b>An attempt was made to save an extended field with an unsupported data type. Name={0}, Data type={1}.</b>
<b>Explanation</b>	Attempted to save an extended field for a partner, but the field's value is not a supported data type.
<b>Action</b>	Supply a value that is one of the supported data types for an extended field.
<b>TNS.0000.2027D</b>	<b>Could not update type {0} for attribute {1}.</b>
<b>Explanation</b>	Attempted to save a document attribute, but the attribute did not reference a valid document type.
<b>Action</b>	If you are explicitly calling services to save an attribute, ensure that the attribute refers to a valid document type.
<b>TNS.0000.2029E</b>	<b>The database has no version information. Either it has not been initialized, or it has been changed to an invalid state by an external process.</b>
<b>Explanation</b>	The TNModelVersion table is missing. Data from this table was accidentally deleted, the table was dropped, or the database is corrupt.
<b>Action</b>	Restore this table from the most recent backup. If the database is corrupt, work with your DBA to determine the cause. In this case, you will need to restore the entire database to the most recent backup.

<b>TNS.0000.2031S</b>	<b>No model version information was available from the database.</b>
<b>Explanation</b>	The TNModelVersion table is missing. Data from this table was accidentally deleted, the table was dropped, or the database is corrupt.
<b>Action</b>	Restore this table from the most recent backup. If the database is corrupt, work with your DBA to determine the cause. In this case, you will need to restore the entire database to the most recent backup.
<b>TNS.0000.2036E</b>	<b>Unsupported encoding {0} declared in the TN config file (tn.store.encoding).</b>
<b>Explanation</b>	The tn.store.encoding property was set to an invalid value.
<b>Action</b>	Set the tn.store.encoding property to a valid value.
<b>TNS.0000.2037S</b>	<b>The model version specified (tnmv:) seems to be missing from the dbops.sql file in your WmTN package. Check the file and try again.</b>
<b>Explanation</b>	The dbops.sql file must begin with "-- tnmv: x.x", where "x.x" is the current TNModelVersion number. This line has been removed or altered.
<b>Action</b>	Restore the dbops.sql file to the correct state.
<b>TNS.0000.2039S</b>	<b>There was an error while reading the dbops.sql file in your WmTN package. The original error message was: {0}.</b>
<b>Explanation</b>	Encountered an exception while reading the dbops.sql file. See the exception message for details.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0000.2040E</b>	<b>Error encountered while updating {0}. {1} rows changed in the database.</b>
<b>Explanation</b>	Instead of updating exactly one row in a table in the database, Trading Networks updated the specified number of rows.
<b>Action</b>	Contact webMethods Customer Care.
<b>TNS.0000.2041W</b>	<b>Error while redefining attribute {0} ({1}).</b>
<b>Explanation</b>	Encountered an SQLException while updating a document attribute.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.

<b>TNS.0000.2042E</b>	<b>Error encountered while updating {0}. {1} rows changed in the database for {2}.</b>
<b>Explanation</b>	Instead of updating exactly one row in a table in the database, Trading Networks updated the specified number of rows.
<b>Action</b>	Contact webMethods Customer Care.
<b>TNS.0000.2047E</b>	<b>No extended fields were deleted for group {0} (partnerID={1}).</b>
<b>Explanation</b>	Expected to delete exactly one row in the PartnerProfileField table in the database. Instead, Trading Networks did not delete any rows.
<b>Action</b>	There seems to be an error while deleting. Find out why the row did not get deleted.
<b>TNS.0000.2051E</b>	<b>Unable to insert binary object (partnerID={0}).</b>
<b>Explanation</b>	An INSERT statement was unsuccessful in adding a row to the database.
<b>Action</b>	The exception is in the full message. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0000.2064S</b>	<b>There was an error interpreting the model version specifier (tnmv:) in the dbops.sql file in your WmTN package. The original error message was: {0}.</b>
<b>Explanation</b>	The dbops.sql table must begin with "-- tnmv: x.x", where "x.x" is the current TN Model Version number. This line has been altered.
<b>Action</b>	Restore this line to its correct state.
<b>TNS.0000.2066E</b>	<b>The main connection to the data store has not been initialized. Check the Trading Networks JDBC connection pool.</b>
<b>Explanation</b>	There is no connection to the Trading Networks database.
<b>Action</b>	Use the Integration Server Administrator JDBC Pools page to test the connection to the Trading Networks database. You may need to adjust the connection pool settings or verify that the database is functioning normally.
<b>TNS.0000.2067E</b>	<b>Extended field (fieldID={0}) not deleted (partnerID={1}).</b>
<b>Explanation</b>	A DELETE statement was unsuccessful in removing a row from the database.
<b>Action</b>	Check the database connection or see the logs for more detailed stack trace information and take appropriate action.

<b>TNS.0000.2079E</b>	<b>More than one extended field (fieldID={0}) removed in a single delete operation (partnerID={1}).</b>
<b>Explanation</b>	Instead of deleting exactly one extended field in the database, Trading Networks deleted the specified number of fields.
<b>Action</b>	Check which other extended fields could have been deleted along with the intended one, then recreate the appropriate extended fields and redo the mapping.
<b>TNS.0000.2085E</b>	<b>Cannot change a {0} without a {1}.</b>
<b>Explanation</b>	Attempting to update a profile component, but a required field is missing.
<b>Action</b>	Supply a value for the missing field.
<b>TNS.0000.2089E</b>	<b>Trading Networks could not retrieve data from your database. Go to the JDBC Pools page in the Integration Server Administrator and make sure your database URL, user name, and password are set correctly. Also make sure you created the Trading Networks database tables as described in the webMethods Installation Guide.</b>
<b>Explanation</b>	The TNModelVersion table is missing from the Trading Networks database. The reason can be one of the following: 1) The Trading Networks database tables have not yet been created. 2) Data from TNModelVersion table was accidentally deleted. 3) The TNModelVersion table was dropped. 4) Your database is corrupt.
<b>Action</b>	Check your database. If the Trading Networks tables have not been created, create them. If the TNModelVersion table is missing or not valid, recreate it. If your database is corrupt, work with your database administrator to determine the cause. You might need to restore your entire database from the most recent backup.
<b>TNS.0000.2096E</b>	<b>Document {0} from this sender was not successfully stored in the data store. The original exception message was: {1}.</b>
<b>Explanation</b>	Encountered an exception while writing a document to the database.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0000.2104E</b>	<b>An attempt was made to access the SQL statement {0} before SQL statements were read from the disk.</b>
<b>Explanation</b>	An SQL statement was used before the SQL statement cache was initialized.
<b>Action</b>	If your package uses Trading Networks facilities, be sure to declare a dependency on the WmTN package in your package's manifest.v3 file.

<b>TNS.0000.2110E</b>	<b>Error decoding type {0}.</b>
<b>Explanation</b>	Encountered an IOException while decoding binary data from the database into a BizDocType object.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0000.2112E</b>	<b>Document type not saved. A document type with the name [{0}] already exists. Cannot have two document types with the same name but different IDs.</b>
<b>Explanation</b>	You cannot have two document types with the same name.
<b>Action</b>	Change the name of the document type and save it again.
<b>TNS.0000.2114E</b>	<b>The system could not load the JDBC driver {0} for connection to the data store. Check the CLASSPATH setting and try again.</b>
<b>Explanation</b>	The driver specified for the Trading Networks functional alias on the JDBC Pools Configuration page of the Integration Server could not be found.
<b>Action</b>	Make sure the driver is in your classpath.
<b>TNS.0000.2119E</b>	<b>Unknown or deleted attribute {0}.</b>
<b>Explanation</b>	The wm.tn.doc:setAttribute service was supplied an invalid attribute ID or name.
<b>Action</b>	Supply a valid attribute ID or name.
<b>TNS.0000.2127E</b>	<b>Error encountered while updating Contact. {0} rows changed in database for {1} {2}.</b>
<b>Explanation</b>	Instead of updating exactly one row in the Contact table in the database, Trading Networks updated the specified number of rows.
<b>Action</b>	Check the affected details and verify whether the data can be recreated.
<b>TNS.0000.2131E</b>	<b>Could not find doc {0}; no document type {1}.</b>
<b>Explanation</b>	Could not create a bizdoc from binary data in the database. The TN document type it references does not exist.
<b>Action</b>	The document type corresponding to the bizdoc may have been deleted, or the associated data may be corrupted. Contact Customer Care.

<b>TNS.0000.2132E</b>	<b>Could not archive documents.</b>
<b>Explanation</b>	Encountered an SQLException while archiving documents.
<b>Action</b>	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0000.2133E</b>	<b>Could not delete archived documents.</b>
<b>Explanation</b>	Encountered an SQLException while deleting archived documents.
<b>Action</b>	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0000.2134E</b>	<b>Could not delete documents.</b>
<b>Explanation</b>	Encountered an SQLException while deleting documents.
<b>Action</b>	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0000.2135E</b>	<b>Could not queue documents.</b>
<b>Explanation</b>	Encountered an SQLException while queuing a document for polling.
<b>Action</b>	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0000.2136E</b>	<b>Could not poll documents.</b>
<b>Explanation</b>	Encountered an SQLException while polling for documents.
<b>Action</b>	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0000.2137E</b>	<b>Could not accept document.</b>
<b>Explanation</b>	Encountered an SQLException while accepting a polled document.
<b>Action</b>	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0000.2138E</b>	<b>Could not query the event table.</b>
<b>Explanation</b>	Encountered an SQLException while querying activity log entries.
<b>Action</b>	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

---

<b>TNS.0000.2139E</b>	<b>Could not delete the events.</b>
<b>Explanation</b>	Encountered an SQLException while deleting activity log entries.
<b>Action</b>	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0000.2140E</b>	<b>Could not instantiate document {0}.</b>
<b>Explanation</b>	Encountered an SQLException while retrieving a document.
<b>Action</b>	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0000.2141E</b>	<b>Could not check uniqueness {0}.</b>
<b>Explanation</b>	Encountered an SQLException while querying the database to determine if a document is unique.
<b>Action</b>	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0000.2142E</b>	<b>Could not get the user status.</b>
<b>Explanation</b>	Encountered an SQLException while retrieving the user status of a document.
<b>Action</b>	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0000.2143E</b>	<b>Could not insert the new document.</b>
<b>Explanation</b>	Encountered an SQLException while saving a new document.
<b>Action</b>	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0000.2144E</b>	<b>Could not change status for {0}.</b>
<b>Explanation</b>	Encountered an SQLException while changing the status of a document.
<b>Action</b>	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0000.2145E</b>	<b>One of (fromdoc,todoc) must be persisted.</b>
<b>Explanation</b>	Attempted to relate two documents, but neither of them has been saved to the database.
<b>Action</b>	Save one or both of the documents to be related.

<b>TNS.0000.2146E</b>	<b>Could not relate {0} and {1}.</b>
<b>Explanation</b>	Encountered an SQLException while relating two documents.
<b>Action</b>	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0000.2147E</b>	<b>Could not get rels: doc={0}, gr={1}.</b>
<b>Explanation</b>	Encountered an SQLException while retrieving related documents.
<b>Action</b>	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0000.2148E</b>	<b>The following exceptions occurred:</b>
<b>Explanation</b>	The following exceptions were encountered while retrieving the full set of TN document types.
<b>Action</b>	See each of the following exceptions for details. Take appropriate action to resolve the problem described in each exception.
<b>TNS.0000.2149E</b>	<b>Database error while fetching all types: {0}.</b>
<b>Explanation</b>	Encountered an SQLException while retrieving the full set of TN document types.
<b>Action</b>	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0000.2150E</b>	<b>Database error while adding type {0}: {1}.</b>
<b>Explanation</b>	Encountered an SQLException while saving a new TN document type.
<b>Action</b>	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0000.2151E</b>	<b>Encoding error while putting type {0}: {1}.</b>
<b>Explanation</b>	Encountered an IOException while saving a new TN document type.
<b>Action</b>	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0000.2152E</b>	<b>Database error while updating type {0}: {1}.</b>
<b>Explanation</b>	Encountered an SQLException while updating a TN document type.
<b>Action</b>	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

---

<b>TNS.0000.2153E</b>	<b>Encoding error while updating type {0}: {1}.</b>
<b>Explanation</b>	Encountered an IOException while saving a new TN document type.
<b>Action</b>	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0000.2154E</b>	<b>Cannot aggregate STRING attributes.</b>
<b>Explanation</b>	Attempted to execute an aggregation operation (SUM, AVG, MIN, MAX) on a String attribute.
<b>Action</b>	Do not specify the aggregation operation.
<b>TNS.0000.2160E</b>	<b>Could not queue document for delivery (id={0}).</b>
<b>Explanation</b>	Encountered an SQLException while changing the status of a document to "QUEUED".
<b>Action</b>	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0000.2162E</b>	<b>Trading Networks database pool is not configured. Please configure a database pool for functional alias "TN" and restart the WmTN package.</b>
<b>Explanation</b>	Data required to configure a connection to the database is missing or invalid.
<b>Action</b>	Use the Integration Server Administrator JDBC Pools page to recreate this data.
<b>TNS.0000.2164E</b>	<b>Error while logging an activity entry to the audit sub system. The exception message is : {0}.</b>
<b>Explanation</b>	Encountered an exception while publishing an activity log entry.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0000.2165E</b>	<b>Error while reading the database configuration. The exception message is : {0}.</b>
<b>Explanation</b>	Trading Networks encountered an exception while reading the database configuration data.
<b>Action</b>	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception. You might need to use the JDBC Pools page in the Integration Server Administrator to recreate this data.

**TNS.0000.2168E**      **Trading Networks database pool is not configured properly. Make sure that a valid database pool is assigned for functional alias "TN" and restart the WmTN package.**

**Explanation**      Data required to configure a connection to the database is missing or invalid.

**Action**             Use the Integration Server Administrator JDBC Pools page to recreate this data.

**TNS.0000.2169E**      **Unable to locate the database configuration information. File {0} does not exist.**

**Explanation**      A file required to configure a connection to the database is missing.

**Action**             Use the Integration Server Administrator JDBC Pools page to recreate this data.

**TNS.0000.2170E**      **Trading Networks database pool is not configured properly. Make sure that a valid database pool is assigned to functional alias "TN" and try again.**

**Explanation**      Data required to configure a connection to the database is missing or invalid.

**Action**             Use the Integration Server Administrator JDBC Pools page to recreate this data.

**TNS.0000.2175E**      **The database connection pool associated with TN should allow at least 2 connections. Your TN pool is currently configured with a maximum of {0} connections. Aborting TN startup. Please increase your TN database pool maximum and restart the server.**

**Explanation**      Trading Networks requires at least two connections for its pool. Trading Networks will not initialize with fewer than two connections.

**Action**             Use the Integration Server Administrator JDBC Pools page to increase the number of connections allowed for the Trading Networks database pool. Then restart your server.

**TNS.0000.2180U**      **Database error while deleting document type {0}: {1}.**

**Explanation**      Encountered an SQLException while deleting a document type.

**Action**             The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

**TNS.0000.2181E**      **A BizDocType with this name already exists: {0}.**

**Explanation**      You cannot have two document types with the same name.

**Action**             Save the document type with a different name.

---

<b>TNS.0000.2184E</b>	<b>The profile field definition "{0}" already exists with a different ID. The field definition was not imported.</b>
<b>Explanation</b>	This error can occur when importing extended profile fields. The most likely cause is that the field was already manually created on the target server.
<b>Action</b>	If you do not intend to import extended field values, this error can be ignored. If you do intend to import extended field values, and no partner yet has a value for this field on your target server, you can change the ID of the field definition to match the one on the source server. Carefully update the ProfileFieldID key in the ProfileField table of the database into which you are importing.
<b>TNS.0000.2185E</b>	<b>An IDType with a key of "{0}" already exists with a different ID description. The IDType "{1}" was not imported. You will need to directly edit the IDType table in your database to correct this problem.</b>
<b>Explanation</b>	The error can occur when importing extended ID types. The most likely cause is that the IDType was already manually created on the target server.
<b>Action</b>	Change the Type column of the IDType table on the target database to match that of the source database.
<b>TNS.0000.2186</b>	<b>Could not update comments for document {0}.</b>
<b>Explanation</b>	Encountered SQLException while updating comments for document.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0000.2199</b>	<b>Error encountered while reading routing status from the database. Exception message: {0}.</b>
<b>Explanation</b>	Encountered SQLException while reading routing status from database.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0000.2212</b>	<b>A scheduled archival service with this name already exists.</b>
<b>Explanation</b>	A scheduled archival service with the same name already exists.
<b>Action</b>	Change the name of the scheduled archival service and save again.
<b>TNS.0000.2215</b>	<b>Unable to save scheduled archive service "{0}".</b>
<b>Explanation</b>	Error encountered while updating the archive service.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

<b>TNS.0000.2221</b>	<b>Interval is not a valid integer.</b>
<b>Explanation</b>	Interval set in the schedule is wrong; it must be a valid integer.
<b>Action</b>	Correct the interval field in the schedule and save the schedule again.
<b>TNS.0000.2222</b>	<b>Interval must be greater than zero.</b>
<b>Explanation</b>	Interval set in the schedule is wrong; it must be greater than zero.
<b>Action</b>	Correct the interval field in the schedule and save the schedule again.
<b>TNS.0000.2223</b>	<b>The scheduled {0} is invalid. Format must be YYYY/MM/DD.</b>
<b>Explanation</b>	Schedule date must be of format YYYY/MM/DD.
<b>Action</b>	Change the schedule according to the format and save it again.
<b>TNS.0000.2224</b>	<b>The scheduled {0} is invalid. Format must be hh:mm:ss.</b>
<b>Explanation</b>	Schedule time must be of format hh:mm:ss.
<b>Action</b>	Change the schedule according to the format and save it again.
<b>TNS.0000.2231</b>	<b>The scheduled delivery date/time is in the past.</b>
<b>Explanation</b>	Schedule delivery date/time set must not be in the past.
<b>Action</b>	Change the delivery schedule with the date/time in the future.
<b>TNS.0000.2232</b>	<b>If an end time is supplied, an end date must also be supplied.</b>
<b>Explanation</b>	End date has to be supplied along with end time.
<b>Action</b>	Set the end date along with the end time, and save the schedule.
<b>TNS.0000.2233</b>	<b>End date/time is in the past.</b>
<b>Explanation</b>	End date/time must not be set in the past.
<b>Action</b>	End date/time should always be later than the start date/time. Correct the end date/time and save the schedule again.
<b>TNS.0000.2234</b>	<b>End date/time is before start date/time.</b>
<b>Explanation</b>	End date/time must not be before the start date/time.
<b>Action</b>	End date/time should always be later than the start date/time. Correct the end date/time and save the schedule again.

<b>TNS.0000.2235</b>	<b>Could not construct a valid timestamp from this schedule. Dates must be in YYYY/MM/DD format and times must be in hh:mm:ss format.</b>
<b>Explanation</b>	Delivery schedule created with an incorrectly formatted date.
<b>Action</b>	Correct the date format and save the delivery schedule.
<b>TNS.0000.2236</b>	<b>Delivery schedule dates must be in the format "YYYY/MM/DD" and times must be in the format "hh:mm:ss".</b>
<b>Explanation</b>	Delivery schedule created with an incorrectly formatted date.
<b>Action</b>	Correct the date format and save the delivery schedule.
<b>TNS.0000.2244</b>	<b>Unable to remove scheduled archival service "{0}".</b>
<b>Explanation</b>	Encountered exception while deleting archival service from database.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0000.2246</b>	<b>Unable to update scheduled archival service "{0}".</b>
<b>Explanation</b>	Encountered exception while updating archival service to database.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0000.2301</b>	<b>An exception occurred while listing the document attributes.</b>
<b>Explanation</b>	Encountered exception while getting document attributes from cache or database.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0000.3001E</b>	<b>Persistence Service Failed.</b>
<b>Explanation</b>	Encountered an exception while saving the document to the database.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0000.3002E</b>	<b>An error occurred while trying to insert this document into the database. The original error message was: {0}.</b>
<b>Explanation</b>	Encountered an exception while saving the document to the database.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

<b>TNS.0000.3007E</b>	<b>Non-unique ID(s) detected.</b>
<b>Explanation</b>	This incoming document already exists in the database. This is a duplicate document, based on the unique document criteria.
<b>Action</b>	Notify the document sender that the document sent is a duplicate.
<b>TNS.0000.3008W</b>	<b>This document is not unique. It matched {0} existing documents in the database.</b>
<b>Explanation</b>	This incoming document already exists in the database. This is a duplicate document, based on the unique document criteria.
<b>Action</b>	Notify the document sender that the document sent is a duplicate.
<b>TNS.0000.3015E</b>	<b>Could not get the document bytes.</b>
<b>Explanation</b>	An exception was thrown while adding the document content to the BizDocEnvelope. The document might be corrupt.
<b>Action</b>	Trading Networks wrote the exception to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0000.3016E</b>	<b>No such document: {0}.</b>
<b>Explanation</b>	The wm.tn.doc:view service was passed an invalid internal document ID.
<b>Action</b>	Supply a valid internal document ID to the wm.tn.doc:view service.
<b>TNS.0000.3018E</b>	<b>Invalid duplicate checking service.</b>
<b>Explanation</b>	Custom duplicate check was selected, but either a duplicate check service was not specified or the specified duplicate check service was invalid.
<b>Action</b>	Using My webMethods Server, update the TN document type and/or the processing rule and specify a valid duplicate checking service.
<b>TNS.0000.3019E</b>	<b>The BizDocType refers to a non-existent duplicate checking service: {0}. It may have been renamed, disabled, or deleted.</b>
<b>Explanation</b>	Custom duplicate check was selected, but no duplicate check service was specified or the specified duplicate check service was invalid. This error could also occur when the specified duplicate check service has been renamed, disabled, or deleted.
<b>Action</b>	Using My webMethods Server, update the TN document type and/or the processing rule and specify a valid duplicate checking service.

<b>TNS.0000.3020E</b>	<b>Duplicate document detected.</b>
<b>Explanation</b>	You received a document that failed a custom duplicate document check. The custom duplicate checking service flagged the document as a duplicate.
<b>Action</b>	You can ignore this message, or you can notify the sender of the document that you have received a duplicate.
<b>TNS.0001.1001E</b>	<b>Content Part {0} does not exist in document {1}.</b>
<b>Explanation</b>	The document does not contain the requested content part.
<b>Action</b>	Request a different content part, or request this content part from a different document.
<b>TNS.0001.1002E</b>	<b>Content for Part {0} of document {1} does not exist in TSpace.</b>
<b>Explanation</b>	This is a large document and the requested content part was not found in the temporary storage.
<b>Action</b>	Request a different content part, or request this content part from a different document.
<b>TNS.0001.1003E</b>	<b>Error retrieving content of content part {0} of document {1}. The exception message is : {2}. The stack trace is : {3}</b>
<b>Explanation</b>	An exception was thrown while retrieving the document content.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception message.
<b>TNS.0001.1004E</b>	<b>Unable to find a document type for the given document type name, {0}.</b>
<b>Explanation</b>	Could not find the document type specified for deleting.
<b>Action</b>	Provide a valid TN document type name to the wm.tn.doc:deleteDocuments service.
<b>TNS.0001.1006E</b>	<b>Attempted to update system attributes for the document, but no rows were changed in the database.</b>
<b>Explanation</b>	Trading Networks encountered an error while attempting to update the system attributes of the document.
<b>Action</b>	Retrieve this document from the database and examine it to determine why the error occurred.
<b>TNS.0001.1017</b>	<b>System Attribute update failed.</b>
<b>Explanation</b>	Encountered an exception while updating the system attribute.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

<b>TNS.0001.1018E</b>	<b>Error when adding large content part named {0} to this document</b>
<b>Explanation</b>	Encountered an exception while adding a large content part to the document.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0001.1019E</b>	<b>The actual exception is {0}.</b>
<b>Explanation</b>	Encountered an exception while adding a large content part to a document.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0001.1020E</b>	<b>User{0} is not an administrator and attempted to retrieve a document (docID={1}) that does not belong to him.</b>
<b>Explanation</b>	Users without administrative rights can only retrieve documents that they have either sent or received.
<b>Action</b>	None.
<b>TNS.0001.1021E</b>	<b>You do not have the authority to retrieve this document. Only administrators may access documents that they did not send or receive.</b>
<b>Explanation</b>	Users without administrative rights can only retrieve documents that they have either sent or received.
<b>Action</b>	Request a user with administrative rights to access the document.
<b>TNS.0001.2035E</b>	<b>Recognize: unable to get XML DTD for comparison: {0} {1} {2} {3}</b>
<b>Explanation</b>	The DTD statement in the document may be incorrect.
<b>Action</b>	Check the document that is being processed to ensure that it is structured correctly. If it is not, notify the responsible party about this document.
<b>TNS.0001.2036E</b>	<b>BizDocTypeReg: ERROR invoking recognize for {0}</b>
<b>Explanation</b>	See the exception message for details.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0001.2040E</b>	<b>{0}: No envelope queries specified</b>
<b>Explanation</b>	The TN document type has no envelope queries defined.
<b>Action</b>	Use My webMethods to edit the TN document type and define envelope queries.

---

<b>TNS.0001.2041E</b>	<b>Error filling BizDocTypeStore cache</b>
<b>Explanation</b>	Encountered an error while reading the TN document types from the database and caching them in memory.
<b>Action</b>	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database.
<b>TNS.0001.2042E</b>	<b>Doctype info not initialized</b>
<b>Explanation</b>	The BizDocType Registry was not initialized.
<b>Action</b>	Try reloading the WmTN package.
<b>TNS.0001.2043E</b>	<b>Unknown type name: {0}</b>
<b>Explanation</b>	The wm.tn.doctype:view service was passed an invalid TN document type name.
<b>Action</b>	Pass a valid TN document type name to the service.
<b>TNS.0001.2044E</b>	<b>Unknown type id: {0}</b>
<b>Explanation</b>	The wm.tn.doctype:view service was passed an invalid TN document type ID.
<b>Action</b>	Pass a valid TN document type ID to this service.
<b>TNS.0001.2045E</b>	<b>Operation not supported for RecordDocType</b>
<b>Explanation</b>	You cannot create an instance of the RecordDocType.
<b>Action</b>	Creating an instance of the RecordDocType is not allowed.
<b>TNS.0001.2054E</b>	<b>IOException encoding pipeline</b>
<b>Explanation</b>	Encountered an exception while binary-encoding the data for an unknown document type. See the nested exception for details.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0001.2056E</b>	<b>Query or Transform Failed</b>
<b>Explanation</b>	Encountered an exception while extracting a document attribute and converting its value.
<b>Action</b>	Verify that the attribute extraction query in the TN document type is valid.

<b>TNS.0001.2057E</b>	<b>Transform Failed</b>
<b>Explanation</b>	An error occurred while converting the attribute value.
<b>Action</b>	Use My webMethods to verify that the attribute details about the TN document type are correct. If they are, gather details about the error and contact Software AG Global Support.
<b>TNS.0001.2058E</b>	<b>Error generating query expression</b>
<b>Explanation</b>	Encountered an exception while generating an XML query to extract a document attribute.
<b>Action</b>	Correct the attribute extraction query on the TN document type.
<b>TNS.0001.2059E</b>	<b>No such BizDocType: {0}</b>
<b>Explanation</b>	The wm.tn.doc:createReply service was passed an invalid replyTypeId.
<b>Action</b>	Pass a valid replyTypeId to the service.
<b>TNS.0001.2060E</b>	<b>Doctype info not initialized. BizDocType registry has not been created.</b>
<b>Explanation</b>	The BizDocType Registry was not initialized.
<b>Action</b>	Try reloading the WmTN package.
<b>TNS.0001.2061E</b>	<b>An error occurred when constructing the XML Document object</b>
<b>Explanation</b>	A document object could not be constructed from the XML. See the nested exception for details.
<b>Action</b>	Take appropriate action to resolve the problem described in the nested exception.
<b>TNS.0001.2062E</b>	<b>Recognition failed.</b>
<b>Explanation</b>	Unable to recognize document. See the next message for details.
<b>Action</b>	Take appropriate action to resolve the problem described in the next message.
<b>TNS.0001.2063E</b>	<b>There is not enough space on TSpace storage system to store the content of this large document</b>
<b>Explanation</b>	The HDD partition used for temporary storage of large documents is full.
<b>Action</b>	Either change the value of the tn.tspace.location property, or increase the size of the partition.

---

<b>TNS.0001.2065E</b>	<b>Unknown datatype encountered transforming attribute for FFDocType {0}</b>
<b>Explanation</b>	The attribute value supplied in the pipeline for the flat file document is not a String.
<b>Action</b>	Correct the document gateway service that puts this value in the pipeline. The attribute value must be a String.
<b>TNS.0001.2066E</b>	<b>FFDocType {0} encountered an unknown datatype while applying the {1} transformation to the "{2}" attribute.</b>
<b>Explanation</b>	The attribute value supplied in the pipeline for the flat file document is not a String.
<b>Action</b>	Correct the document gateway service that puts this value in the pipeline. The attribute value must be a String.
<b>TNS.0001.2067E</b>	<b>The {0} attribute is required by the {1} doctype. It is missing.</b>
<b>Explanation</b>	The attribute that is required for the flat file TN document type is missing in the pipeline.
<b>Action</b>	Correct the document gateway service that supplies the value for this attribute.
<b>TNS.0001.2068E</b>	<b>FFDocType {0} encountered an error transforming an attribute.</b>
<b>Explanation</b>	The specified flat file document type extracts an attribute. Trading Networks encountered an error while transforming the attribute value.
<b>Action</b>	Use My webMethods to verify that the attribute details for the TN document type are correct. If they are, gather details about the error and contact Software AG Global Support.
<b>TNS.0001.2069E</b>	<b>FFDocType {0} encountered an error while applying the {1} transformation to the "{2}" attribute: {3} : {4}</b>
<b>Explanation</b>	An error occurred while transforming the attribute value.
<b>Action</b>	Use My webMethods to verify that the attribute details for the TN document type are correct. If they are, gather details about the error and contact Software AG Global Support.
<b>TNS.0001.2070E</b>	<b>FFDocType {0} encountered an error reading the document bytes.</b>
<b>Explanation</b>	Encountered a problem while processing the "ffdata" InputStream.
<b>Action</b>	See the entire message for details.

<b>TNS.0001.2071E</b>	<b>FFDocType {0} encountered an error reading the document bytes. {1} : {2}</b>
<b>Explanation</b>	Encountered an exception while reading the "ffdata" InputStream. See the exception message and stack trace for details.
<b>Action</b>	Verify that your document gateway service is not corrupting the "ffdata" InputStream. Resend the document.
<b>TNS.0001.2072E</b>	<b>Cannot unregister a built-in DocType Category: {0}</b>
<b>Explanation</b>	The wm.tn.doctype:unregisterCategory service was passed the name of a built-in TN document type category, such as "XML", or "Flat file".
<b>Action</b>	Do not unregister a built-in category.
<b>TNS.0001.2079E</b>	<b>Could not determine document sender.</b>
<b>Explanation</b>	The TN document type is configured to determine the document sender from the connected user but it could not.
<b>Action</b>	See the entire message for details.
<b>TNS.0001.2080E</b>	<b>Could not determine document sender for doctype "{0}" because there is no connected user.</b>
<b>Explanation</b>	The TN document type is configured to determine the document sender from the connected user but it could not. A possible reason for the error is the lack of a connected user.
<b>Action</b>	Determine why there is not a connected user. Perhaps the document has been submitted by a background thread.
<b>TNS.0001.2081E</b>	<b>Could not get ProfileSummary for sender from connected user "{0}".</b>
<b>Explanation</b>	The TN document type is configured to determine the document sender from the connected user but it could not. There is a connected user, but it does not have a partner profile.
<b>Action</b>	Create a partner profile for the user, or instruct the user to log on the system using a valid partner account.
<b>TNS.0001.2083E</b>	<b>FFDocType {0} encountered an error reading the document bytes. Key "ffdata" is not found in the pipeline</b>
<b>Explanation</b>	The "ffdata" InputStream is missing in the pipeline.
<b>Action</b>	Verify that your document gateway service is not dropping "ffdata" from the pipeline. Resend the document.

---

<b>TNS.0001.2084E</b>	<b>FFDocType {0} encountered an error reading the content of document {1}.</b>
<b>Explanation</b>	This is a large document and Trading Networks encountered an error while reading the document's InputStream from Tspace (hard disk drive space). See the nested exception for details.
<b>Action</b>	Take appropriate action to resolve the problem described in the nested exception.
<b>TNS.0001.2085E</b>	<b>Error turning stream into bytes (docid={0})</b>
<b>Explanation</b>	The document has an unsupported encoding. See the server log or open this document in Transaction Analysis to see details about the error.
<b>Action</b>	Request the document to be resend using supported encoding.
<b>TNS.0001.2086E</b>	<b>Attribute transformation "{0}" has no data</b>
<b>Explanation</b>	The attribute referenced by this transformation is null.
<b>Action</b>	Gather details about this error, and contact Software AG Global Support.
<b>TNS.0001.2088E</b>	<b>A corrupted document was encountered in recognition: {0}</b>
<b>Explanation</b>	Trading Networks received an XML document that was not structured well.
<b>Action</b>	Correct the original document and resend it.
<b>TNS.0001.2090E</b>	<b>Unable to load the following TN document types because their classes are not found in the classpath: {0}. Either correct the classpath to include the required classes and restart the Server or, if you no longer use these document types, delete them using the wm.tn.doctype:delete service and then restart the Server.</b>
<b>Explanation</b>	There are TN document types in the database that are not available on the classpath.
<b>Action</b>	Correct the classpath to include the required classes and restart the server; or, if you no longer use these TN document types, delete them using the wm.tn.doctype:delete service, and then restart the server.
<b>TNS.0001.2091</b>	<b>Encountered an unsupported encoding</b>
<b>Explanation</b>	Encoding passed in the document is not supported by Integration Server.
<b>Action</b>	Change the document to a supported encoding.

<b>TNS.0001.2092</b>	<b>Error turning stream into bytes: {0}</b>
<b>Explanation</b>	Error encountered while converting the stream to bytes. This could happen if the stream was closed while still being read.
<b>Action</b>	Examine why the connection dropped while reading the stream.
<b>TNS.0001.2093E</b>	<b>This operation is not supported for MissingDocType.</b>
<b>Explanation</b>	The operation attempted to create a BizDocEnvelope from the MissingDocType class.
<b>Action</b>	If you developed code that creates instances of (No Suggestions) ensure that it does not attempt to create a BizDocEnvelope from the MissingDocType class.
<b>TNS.0001.2094E</b>	<b>ERROR: The Java class for this document type was not found.</b>
<b>Explanation</b>	The JAR file that holds the TN document type editor was not found.
<b>Action</b>	If you are viewing a Trading Networks XML or flat file document type, make sure that the tnclient.jar file is in the webMethods6\IntegrationServer\packages\WmTN\code\jars directory on the Integration Server file system. If you are viewing another category of TN document type, make sure that the JAR file with that TN document type editor is in the IntegrationServer\packages\WmTN\code\jars directory.
<b>TNS.0001.2097</b>	<b>Encountered an error while creating MAPI event to Optimize for EventMap {0} and for Sender with PartnerID {1}.</b>
<b>Explanation</b>	The error may be caused due to Broker being stopped.
<b>Action</b>	Start the associated Broker if it is stopped.
<b>TNS.0001.3000E</b>	<b>Unable to construct mime message</b>
<b>Explanation</b>	Source data used to construct the MIME message is not a properly structured MIME message.
<b>Action</b>	Check the input data. Fix the message to conform to the MIME standard.
<b>TNS.0001.3001</b>	<b>Unable to read mime message data source</b>
<b>Explanation</b>	The MIME message is not a properly structured MIME message.
<b>Action</b>	Check the input data. Fix the message to conform to the MIME standard.

---

<b>TNS.0001.3002E</b>	<b>Unable to read mime message data source</b>
<b>Explanation</b>	Problem while reading from input data source.
<b>Action</b>	Check input data source for errors.
<b>TNS.0001.3003E</b>	<b>Unable to construct mime message</b>
<b>Explanation</b>	Source data used to construct the MIME message is not a properly structured MIME message.
<b>Action</b>	Check the input data. Fix the message to conform to the MIME standard.
<b>TNS.0001.3004E</b>	<b>Unable to handle data of type: {0}</b>
<b>Explanation</b>	Attempted to add a message of type <msgType> to a multi-part MIME message. This type cannot be part of a multi-part MIME message.
<b>Action</b>	Check the message type that is being added to the multi-part MIME message. It must be either a multi-part MIME or a MIME message.
<b>TNS.0001.3005E</b>	<b>Unable to handle null data source</b>
<b>Explanation</b>	Cannot construct a MIME message from null data source.
<b>Action</b>	Pass valid, non-null data source to the service.
<b>TNS.0001.3006</b>	<b>Unable to read mime message data source</b>
<b>Explanation</b>	Problem while reading from input data source.
<b>Action</b>	Check input data source for errors.
<b>TNS.0001.3007</b>	<b>Unable to construct mime message</b>
<b>Explanation</b>	Source data used to construct the MIME message is not a properly structured MIME message.
<b>Action</b>	Check the input data. Fix the message to conform to the MIME standard.
<b>TNS.0001.3008E</b>	<b>Can not replace existing body part</b>
<b>Explanation</b>	Attempted to add a MIME body part to a MIME message that already contains a body part.
<b>Action</b>	Set the input flag 'replace' on the wm.tn.mime:addBodyPart service to 'yes'. This will replace the existing body part with the new one. Another solution is to set the flag 'multipart' to 'yes'. This will append the new body part to the existing one, making the message a multi-part MIME message.

<b>TNS.0001.3009</b>	<b>Unable to construct mime message</b>
<b>Explanation</b>	Source data used to construct the MIME message is not a properly structured MIME message.
<b>Action</b>	Check the input data. Fix the message to conform to the MIME standard.
<b>TNS.0001.3010</b>	<b>Unable to read mime message data source</b>
<b>Explanation</b>	Problem while reading the input data source.
<b>Action</b>	Check input data source for errors.
<b>TNS.0001.3011E</b>	<b>getBodyPart not supported on non multipart message</b>
<b>Explanation</b>	Attempted to get a MIME body part other than zero from a non-multipart MIME message.
<b>Action</b>	The number '0' (zero) is the only valid value for the input parameter 'index' of the wm.tn.mime:getBodyPartHeader and wm.tn.mime:getBodyPartContent services when the input MIME message is not a multi-part MIME message.
<b>TNS.0001.3012</b>	<b>Unable to construct mime message</b>
<b>Explanation</b>	Source data used to construct the MIME message is not a properly structured MIME message.
<b>Action</b>	Check the input data. Fix the message to conform to the MIME standard.
<b>TNS.0001.3013</b>	<b>Unable to read mime message data source</b>
<b>Explanation</b>	Problem while reading the input data source.
<b>Action</b>	Check input data source for errors.
<b>TNS.0001.3014</b>	<b>Unable to construct mime message</b>
<b>Explanation</b>	Source data used to construct the MIME message is not a properly structured MIME message.
<b>Action</b>	Check the input data. Fix the message to conform to the MIME standard.
<b>TNS.0001.3015</b>	<b>Unable to read mime message data source</b>
<b>Explanation</b>	Problem while reading the input data source.
<b>Action</b>	Check input data source for errors.

---

<b>TNS.0001.3016</b>	<b>Unable to construct mime message</b>
<b>Explanation</b>	Source data used to construct the MIME message is not a properly structured MIME message.
<b>Action</b>	Check the input data. Fix the message to conform to the MIME standard.
<b>TNS.0001.3017</b>	<b>Unable to construct mime message</b>
<b>Explanation</b>	Source data used to construct the MIME message is not a properly structured MIME message.
<b>Action</b>	Check the input data. Fix the message to conform to the MIME standard.
<b>TNS.0001.3018</b>	<b>Unable to construct mime message</b>
<b>Explanation</b>	Source data used to construct the MIME message is not a properly structured MIME message.
<b>Action</b>	Check the input data. Fix the message to conform to the MIME standard.
<b>TNS.0001.3019</b>	<b>Unable to construct mime message</b>
<b>Explanation</b>	Source data used to construct the MIME message is not a properly structured MIME message.
<b>Action</b>	Check the input data. Fix the message to conform to the MIME standard.
<b>TNS.0001.3020</b>	<b>Unable to construct mime message</b>
<b>Explanation</b>	Source data used to construct the MIME message is not a properly structured MIME message.
<b>Action</b>	Check the input data. Fix the message to conform to the MIME standard.
<b>TNS.0001.3021</b>	<b>Unable to construct mime message</b>
<b>Explanation</b>	Source data used to construct the MIME message is not a properly structured MIME message.
<b>Action</b>	Check the input data. Fix the message to conform to the MIME standard.
<b>TNS.0001.3022</b>	<b>Unable to construct mime message</b>
<b>Explanation</b>	Source data used to construct the MIME message is not a properly structured MIME message.
<b>Action</b>	Check the input data. Fix the message to conform to the MIME standard.

<b>TNS.0001.3023</b>	<b>Unable to construct mime message</b>
<b>Explanation</b>	Source data used to construct the MIME message is not a properly structured MIME message.
<b>Action</b>	Check the input data. Fix the message to conform to the MIME standard.
<b>TNS.0001.3024E</b>	<b>Unable to determine Content type</b>
<b>Explanation</b>	MIME message does not contain content-type information. Message is improperly structured.
<b>Action</b>	Inform the message sender about the error.
<b>TNS.0001.3025E</b>	<b>Unable to get boundary for multipart mime message</b>
<b>Explanation</b>	MIME message does not contain message boundary information. Message is improperly structured.
<b>Action</b>	Inform the message sender about the error.
<b>TNS.0001.3026</b>	<b>Unable to determine content-type</b>
<b>Explanation</b>	MIME message does not contain content-type information. Message is improperly structured.
<b>Action</b>	Inform the message sender about the error.
<b>TNS.0001.3027</b>	<b>Unable to construct mime message</b>
<b>Explanation</b>	Source data used to construct the MIME message is not a properly structured MIME message.
<b>Action</b>	Check the input data. Fix the message to conform to the MIME standard.
<b>TNS.0001.3028</b>	<b>Unable to read mime message data source</b>
<b>Explanation</b>	The MIME message is not a properly structured MIME message.
<b>Action</b>	Check the input data. Fix the message to conform to the MIME standard.
<b>TNS.0001.3029</b>	<b>Unable to construct mime message</b>
<b>Explanation</b>	Source data used to construct the MIME message is not a properly structured MIME message.
<b>Action</b>	Check the input data. Fix the message to conform to the MIME standard.

---

<b>TNS.0001.3030</b>	<b>Unable to determine content-type</b>
<b>Explanation</b>	MIME message does not contain content-type information. Message is improperly structured.
<b>Action</b>	Inform the message sender about the error.
<b>TNS.0001.3031E</b>	<b>Unable to determine content-type</b>
<b>Explanation</b>	MIME message does not contain content-type information. Message is improperly structured.
<b>Action</b>	Inform the message sender about the error.
<b>TNS.0001.3032E</b>	<b>Unable to read mime message data source</b>
<b>Explanation</b>	The MIME message is not a properly structured MIME message.
<b>Action</b>	Check the input data. Fix the message to conform to the MIME standard.
<b>TNS.0001.3033E</b>	<b>Unable to construct mime message</b>
<b>Explanation</b>	Source data used to construct the MIME message is not a properly structured MIME message.
<b>Action</b>	Check the input data. Fix the message to conform to the MIME standard.
<b>TNS.0001.3034E</b>	<b>Unable to parse Content-Type string</b>
<b>Explanation</b>	MIME message does not contain content-type information. Message is improperly structured.
<b>Action</b>	Inform the message sender about the error.
<b>TNS.0001.3035E</b>	<b>Cannot write message to outputStream, content is null</b>
<b>Explanation</b>	Message does not contain any data.
<b>Action</b>	Construct a MIME message with valid input data.
<b>TNS.0001.3036E</b>	<b>Operation can only be performed on parsed message.</b>
<b>Explanation</b>	The size of a MIME body part can only be determined for MIME messages that are parsed from a complete message. The size of each part cannot be determined when composing a MIME message.
<b>Action</b>	Do not attempt to obtain the size of a MIME body part that is part of a message that is being composed.

<b>TNS.0001.3037E</b>	<b>Unable to parse "Content-Disposition"</b>
<b>Explanation</b>	MIME message does not contain content-disposition information. Message is improperly structured.
<b>Action</b>	Inform the message sender about the error.
<b>TNS.0001.3039E</b>	<b>Unable to get content.</b>
<b>Explanation</b>	Error occurred while reading the message content.
<b>Action</b>	Check input data source for errors.
<b>TNS.0001.3040E</b>	<b>Message Digest Algorithm "{0}" not supported.</b>
<b>Explanation</b>	User has specified an invalid value for the 'digestAlgorithm' input parameter of the wm.tn.mime:setDigestAlgorithm service.
<b>Action</b>	Specify a valid value of either "MD5" or "SHA-1" for the 'digestAlgorithm' input parameter.
<b>TNS.0001.3041E</b>	<b>Cannot set header for message that is not multipart. Either specify subType or set header using addBodyPart</b>
<b>Explanation</b>	When calling the wm.tn.mime:createMimeData service, header for a non-multipart message cannot be set .
<b>Action</b>	Specify a value for subType, which will create a multi-part MIME message. Alternatively, for a MIME message that is not multi-part, headers can be specified when calling the wm.tn.mime:addBodyPart service.
<b>TNS.0001.3101E</b>	<b>Parameter input must be an InputStream</b>
<b>Explanation</b>	Input parameter 'input' must be an InputStream object.
<b>Action</b>	Pass in an InputStream object.
<b>TNS.0001.3102</b>	<b>Parameter mimeType cannot be null</b>
<b>Explanation</b>	Input parameter 'mimeType' must be sent.
<b>Action</b>	Pass in an mimeType object.
<b>TNS.0001.3103E</b>	<b>content cannot be null when adding a mime body part</b>
<b>Explanation</b>	Content cannot be null when adding a MIME body part
<b>Action</b>	Specify valid content.

---

<b>TNS.0001.3104E</b>	<b>Unable to handle content of type {0}</b>
<b>Explanation</b>	Input parameter 'content' must be one of the following types: InputStream, byte, array, or MIME message.
<b>Action</b>	Specify the value of the 'content' input parameter using one of the three allowed types.
<b>TNS.0001.3105E</b>	<b>Parameter index must be of type int</b>
<b>Explanation</b>	Specified a non-integer value for the 'index' input parameter when attempting to obtain a MIME body part.
<b>Action</b>	Check the value of the input parameter 'index' to ensure it is a non-negative integer.
<b>TNS.0001.3106E</b>	<b>outputStream required</b>
<b>Explanation</b>	Calls to the wm.tn.mime:writeToStream service require an OutputStream object to be specified for the 'outputStream' parameter.
<b>Action</b>	Pass an OutputStream object to the wm.tn.mime:writeToStream service.
<b>TNS.0001.3107E</b>	<b>Unknown digest algorithm {0}</b>
<b>Explanation</b>	User has specified an invalid value for the 'digestAlgorithm' input parameter.
<b>Action</b>	Specify a valid value of either "MD5" or "SHA-1" for the 'digestAlgorithm' input parameter.
<b>TNS.0001.3108E</b>	<b>Parameter mimeType cannot be null</b>
<b>Explanation</b>	The 'mimeType' input parameter has a null value.
<b>Action</b>	Specify a valid value for the 'mimeType' parameter.
<b>TNS.0001.3109E</b>	<b>Parameter headerName cannot be null</b>
<b>Explanation</b>	The headerName parameter cannot be null.
<b>Action</b>	Specify a valid value for the 'headerName' parameter.
<b>TNS.0001.3112E</b>	<b>A digest algorithm must be specified when creating a message digest.</b>
<b>Explanation</b>	The user has specified an invalid value for the 'digestAlgorithm' input parameter.
<b>Action</b>	Specify a valid value of either "MD5" or "SHA-1" for the 'digestAlgorithm' input parameter.

<b>TNS.0001.3200E</b>	<b>Cannot recognize certificates</b>
<b>Explanation</b>	Cannot recognize certificates.
<b>Action</b>	Certificates must be passed in as byte array objects.
<b>TNS.0001.3201E</b>	<b>Cannot recognize certificate</b>
<b>Explanation</b>	Cannot recognize certificates.
<b>Action</b>	Check the certificate format. The certificates must be a DER encoded ASN.1 format.
<b>TNS.0001.3202E</b>	<b>Cannot recognize certificate at index {0}</b>
<b>Explanation</b>	Cannot recognize certificate in chain at index: <index>.
<b>Action</b>	Check the certificate format. The certificate must be a DER encoded ASN.1 format.
<b>TNS.0001.3203E</b>	<b>Certificate at index {0} is not valid</b>
<b>Explanation</b>	Cannot recognize certificate at index: <index>
<b>Action</b>	Certificate must be passed in as byte array object.
<b>TNS.0001.3204E</b>	<b>Error attempting to parse message contents</b>
<b>Explanation</b>	Source data used to construct the MIME message is not a properly structured MIME message.
<b>Action</b>	Check the input data. Fix the message to conform to the MIME standard.
<b>TNS.0001.3205E</b>	<b>Error attempting to read from message source</b>
<b>Explanation</b>	An error occurred while reading message content.
<b>Action</b>	Check input data source for errors.
<b>TNS.0001.3206E</b>	<b>Recipient certificate is not valid</b>
<b>Explanation</b>	Cannot recognize certificates.
<b>Action</b>	Check the certificate format. The certificate must be a DER encoded ASN.1 format.
<b>TNS.0001.3207</b>	<b>Cannot recognize recipient certificate at index {0}</b>
<b>Explanation</b>	Cannot recognize certificate in chain at index: <index>
<b>Action</b>	Check certificate format. The certificate must be a DER encoded ASN.1 format.

---

<b>TNS.0001.3208</b>	<b>Cannot recognize recipient certificate at index {0}</b>
<b>Explanation</b>	Cannot recognize certificate in chain at index: <index>
<b>Action</b>	Check certificate format. The certificate must be a DER encoded ASN.1 format.
<b>TNS.0001.3209E</b>	<b>Cannot recognize recipient certificate at index {0}</b>
<b>Explanation</b>	Cannot recognize certificate at index: <index>.
<b>Action</b>	Check the certificate format. The certificate must be a DER encoded ASN.1 format.
<b>TNS.0001.3210E</b>	<b>Certificate format is invalid for recipient certificate at index {0}</b>
<b>Explanation</b>	Cannot recognize certificate in chain at index: <index>.
<b>Action</b>	Check the certificate format. The certificate must be a DER encoded ASN.1 format.
<b>TNS.0001.3211E</b>	<b>Specified keylength {0}, is not allowed</b>
<b>Explanation</b>	Invalid value specified for key length of RC2 encryption algorithm.
<b>Action</b>	Specify one of the allowed key length values: "40", "64", or "128".
<b>TNS.0001.3212E</b>	<b>Specified algorithm '{0}', is not supported</b>
<b>Explanation</b>	Invalid encryption algorithm is specified.
<b>Action</b>	Specify one of the supported encryption algorithms: "TripleDES", "RC2", or "DES".
<b>TNS.0001.3213E</b>	<b>In getEncryptedMimeObject: Cannot handle datasource of type: {0}</b>
<b>Explanation</b>	When trying to create an encrypted message, the 'mimeSrc' object must be a MimeData object.
<b>Action</b>	Pass in a MimeData object. MimeData objects are created using the wm.tn.mime:createMimeData service.
<b>TNS.0001.3214E</b>	<b>In getEncryptedMimeObject: Cannot handle null datasource</b>
<b>Explanation</b>	The 'mimeSrc' input parameter cannot be null.
<b>Action</b>	Specify a valid MimeData object in the 'mimeSrc' parameter.
<b>TNS.0001.3215</b>	<b>Unable to get signer's private key</b>
<b>Explanation</b>	Private key for sender may be missing.
<b>Action</b>	Ensure in My webMethods that the sender's private key is associated.

<b>TNS.0001.3216E</b>	<b>Unable to get signer's private key</b>
<b>Explanation</b>	Cannot recognize the private key.
<b>Action</b>	Check the supplied private key. It should be a DER encoded ASN.1 representation of an RSA private key.
<b>TNS.0001.3217E</b>	<b>Unable to get recipient certificate(s).</b>
<b>Explanation</b>	Cannot recognize the certificates.
<b>Action</b>	Check the certificate format. The certificate must be a DER encoded ASN.1 format.
<b>TNS.0001.3218E</b>	<b>Signer's certificate is not a valid data format</b>
<b>Explanation</b>	Cannot recognize certificates.
<b>Action</b>	Check the certificate format. The certificate must be a DER encoded ASN.1 format.
<b>TNS.0001.3219E</b>	<b>Signer's certificate is not recognized</b>
<b>Explanation</b>	Cannot recognize certificates.
<b>Action</b>	Check the certificate format. The certificate must be a DER encoded ASN.1 format.
<b>TNS.0001.3220E</b>	<b>Input parameter mimeSrc to service createSignedData cannot be of type {0}. It should be of type MimeData.</b>
<b>Explanation</b>	When trying to create a signed message, the 'mimeSrc' object must be a MimeData object.
<b>Action</b>	Pass in a MimeData object. MimeData objects are created using the wm.tn.mime:createMimeData service.
<b>TNS.0001.3221E</b>	<b>Input parameter mimeSrc to service createSignedData cannot be null. It should be of type MimeData.</b>
<b>Explanation</b>	When trying to create a signed message, the 'mimeSrc' object must be a MimeData object.
<b>Action</b>	Pass in a MimeData object. MimeData objects are created using the wm.tn.mime:createMimeData service.
<b>TNS.0001.3222E</b>	<b>Unable to parse message</b>
<b>Explanation</b>	Source data used to construct the MIME message is not a properly structured MIME message.
<b>Action</b>	Check the input data. Fix the message to conform to the MIME standard.

---

<b>TNS.0001.3223E</b>	<b>Input parameter mimeSrc should be of type MimeData</b>
<b>Explanation</b>	The 'mimeSrc' object must be a MimeData object or an InputStream object.
<b>Action</b>	Pass in a MimeData or InputStream object. MimeData objects are created using the wm.tn.mime:createMimeData service.
<b>TNS.0001.3224E</b>	<b>Could not obtain message content</b>
<b>Explanation</b>	Error occurred while reading the message content.
<b>Action</b>	Check input data source for errors.
<b>TNS.0001.3225E</b>	<b>Content is not of a recognized encryption type</b>
<b>Explanation</b>	Cannot process the encrypted message.
<b>Action</b>	Contact the sender to re-send the message using the correct format.
<b>TNS.0001.3226E</b>	<b>Given certificate does not decrypt message</b>
<b>Explanation</b>	The message was not encrypted for the certificate that was passed to the service.
<b>Action</b>	First, validate that the correct certificate is used to decrypt the message. Then, if the certificate is the correct one, contact the message sender to determine which certificate was actually used to create the encrypted message.
<b>TNS.0001.3229E</b>	<b>Cannot Process this object. Write this MimeData to stream, then process that stream.</b>
<b>Explanation</b>	Cannot process the object.
<b>Action</b>	Write the MimeData to a stream and then process the stream again.
<b>TNS.0001.3230E</b>	<b>Input parameter mimeType must be a MimeData object</b>
<b>Explanation</b>	The 'mimeType' input parameter is not a MimeData object.
<b>Action</b>	Pass in a MimeData object. MimeData objects are created using the wm.tn.mime:createMimeData service.
<b>TNS.0001.3231E</b>	<b>Message content is not certificates only data. Message could not be processed.</b>
<b>Explanation</b>	The message cannot be handled by the wm.tn.mime:processCertsOnlyData service.
<b>Action</b>	Use the wm.tn.mime:createMimeMessage service to determine if the message is signed or encrypted. Then use either wm.tn.mime:processSignedData or wm.tn.mime:processEncryptedData as appropriate.

<b>TNS.0001.3232E</b>	<b>Input parameter mimeSrc must be a MimeData object</b>
<b>Explanation</b>	The 'mimeSrc' object must be a MimeData object.
<b>Action</b>	Pass a MimeData object. MimeData objects are created using the wm.tn.mime:createMimeData service.
<b>TNS.0001.3233E</b>	<b>Message content is not signed data. Message could not be processed</b>
<b>Explanation</b>	The message cannot be handled by the wm.tn.mime:processSignedData service.
<b>Action</b>	Use the wm.tn.mime:createMimeMessage service to determine if the message is signed or encrypted. Then use either wm.tn.mime:processSignedData or wm.tn.mime:processEncryptedData as appropriate.
<b>TNS.0001.3234E</b>	<b>Signing key is not valid</b>
<b>Explanation</b>	The key used to sign the message is invalid.
<b>Action</b>	Check certificate format. The certificate must be a DER encoded ASN.1 format.
<b>TNS.0001.3235E</b>	<b>Unable to sign document</b>
<b>Explanation</b>	The key used to sign the message is invalid.
<b>Action</b>	Check certificate format. The certificate must be a DER encoded ASN.1 format.
<b>TNS.0001.3236E</b>	<b>Invalid signer certificate file information</b>
<b>Explanation</b>	The signer certificate chain is invalid.
<b>Action</b>	The signer certificate chain must be an array of certificates.
<b>TNS.0001.3237E</b>	<b>Certificate at index {0} not in recognizable format</b>
<b>Explanation</b>	Cannot recognize certificate in chain at index: <index>.
<b>Action</b>	Check certificate format. The certificate must be a DER encoded ASN.1 format.
<b>TNS.0001.3238E</b>	<b>Invalid certificate input at index {0}</b>
<b>Explanation</b>	Cannot recognize certificate in chain at index: <index>.
<b>Action</b>	Check certificate format. The certificate must be a DER encoded ASN.1 format.

---

<b>TNS.0001.3239E</b>	<b>Signature could not be verified</b>
<b>Explanation</b>	The signature is invalid. The signature cannot be validated.
<b>Action</b>	Contact the message creator to determine what message was originally sent.
<b>TNS.0001.3240E</b>	<b>Expired certificate chain</b>
<b>Explanation</b>	A certificate used to sign the message has expired.
<b>Action</b>	Notify the message creator that the certificates used to sign the message are invalid.
<b>TNS.0001.3241E</b>	<b>Error in certificate chain</b>
<b>Explanation</b>	The certificate chain is invalid.
<b>Action</b>	Check certificate format. The certificates must be a DER encoded ASN.1 format. Ensure that the certificates form a chain. If the chain consists of Cert A and Cert B, the issuer of Cert A should be the same as the subject of Cert B.
<b>TNS.0001.3242E</b>	<b>Untrusted certificate</b>
<b>Explanation</b>	The certificate used to sign the message is not signed by a trusted certificate authority. On the other hand, the signature is structured correctly.
<b>Action</b>	The message should not be trusted because the certificate authority is not trusted. Add the certificate authority to the trusted certificate authorities, or the message creator must use a certificate issued by a trusted certificate authority to sign the message.
<b>TNS.0001.3244E</b>	<b>Error using temporary storage space</b>
<b>Explanation</b>	An error occurred when using the temporary storage system.
<b>Action</b>	See the webMethods Integration Server User Guide for more details. Additional details are available in the exception message.
<b>TNS.0001.3245E</b>	<b>Unable to parse Encrypted Content. Invalid encrypted data.</b>
<b>Explanation</b>	The message cannot be decrypted.
<b>Action</b>	Check the server log for additional error information. The stack trace of this error should contain additional information why this message cannot be decrypted.

<b>TNS.0001.3246E</b>	<b>Unable to decrypt data.</b>
<b>Explanation</b>	The message could not be decrypted.
<b>Action</b>	Check the server log for additional error information. The stack trace of this error should contain additional information why this message cannot be decrypted.
<b>TNS.0001.3247E</b>	<b>Unable to parse Encrypted Content. Private key does not decrypt data.</b>
<b>Explanation</b>	The private key used to decrypt the message cannot decrypt the message.
<b>Action</b>	First, validate that the correct private key is used to decrypt the message. Then, if the private key is correct, contact the message sender to determine which certificate was used to create the encrypted message.
<b>TNS.0001.3248E</b>	<b>Unable to determine hash algorithm. Parameter micalg was null</b>
<b>Explanation</b>	Source data used to construct the MIME message is not a properly structured MIME message.
<b>Action</b>	Check the input data. Fix the message to conform to the MIME standard.
<b>TNS.0001.3249E</b>	<b>Unable to determine hash algorithm. Unknown micalg: {0}</b>
<b>Explanation</b>	Source data used to construct the MIME message is not a properly structured MIME message.
<b>Action</b>	Check the input data. Fix the message to conform to the MIME standard.
<b>TNS.0001.3250E</b>	<b>Improperly formed multipart/signed message</b>
<b>Explanation</b>	Source data used to construct the MIME message is not a properly structured MIME message.
<b>Action</b>	Check the input data. Fix the message to conform to the MIME standard.
<b>TNS.0001.3251E</b>	<b>Cannot process body part of type {0}</b>
<b>Explanation</b>	Error occurred while processing the message.
<b>Action</b>	Check the error message and take action as appropriate.
<b>TNS.0001.3252E</b>	<b>Cannot process signed data with content type {0}</b>
<b>Explanation</b>	Message does not seem to be a signed message and thus cannot be processed by the wm.tn.mime:processSignedData service.
<b>Action</b>	Use the wm.tn.mime:createMimeMessage service to determine if the message is signed or encrypted. Then, use either wm.tn.mime:processSignedData or wm.tn.mime:processEncryptedData as appropriate. Otherwise, obtain the message content by using the wm.tn.mime:getBodyPartContent service.

---

<b>TNS.0001.3253E</b>	<b>Unable to parse Content Type</b>
<b>Explanation</b>	Source data used to construct the MIME message is not a properly structured MIME message.
<b>Action</b>	Check the input data. Fix the message to conform to the MIME standard.
<b>TNS.0001.3254E</b>	<b>Unable to compute message digest using algorithm: {0}</b>
<b>Explanation</b>	The digest algorithm is either invalid or is not a supported algorithm.
<b>Action</b>	Specify a supported algorithm. Valid values for the digest algorithm are: "SHA-1" or "MD5".
<b>TNS.0001.3255E</b>	<b>Either "profileAlias" or ("privKey","signerCert") are required</b>
<b>Explanation</b>	To execute properly, the service requires either a valid value for 'profileAlias' or a valid value for the 'privKey' and 'signerCert' input parameters.
<b>Action</b>	Specify a value for either 'profileAlias', or 'privKey' and 'signerCert'. See the webMethods Trading Networks Built-In Services Reference for more details about this service.
<b>TNS.0001.3256E</b>	<b>Either "profileAlias" or ("privKey","recipientCert") are required</b>
<b>Explanation</b>	To execute properly, the service requires either a valid value for 'profileAlias', or a valid value for the 'privKey' and 'recipientCert' input parameters.
<b>Action</b>	Specify a value for either 'profileAlias', or 'privKey' and 'recipientCert'. See the webMethods Trading Networks Built-In Services Reference for more details about this service.
<b>TNS.0001.3257E</b>	<b>Algorithm {0} not supported</b>
<b>Explanation</b>	The message was encrypted using the <algorithmName> algorithm. Cannot decrypt messages encrypted with this algorithm.
<b>Action</b>	Can decrypt messages that are encrypted with RC2, TripleDes, or DES algorithms only.
<b>TNS.0001.3258E</b>	<b>Invalid RC2 parameter version: {0}</b>
<b>Explanation</b>	This version of the RC2 algorithm is unsupported or invalid. The RC2 algorithm is supported with 40, 64, or 128 bit keys.
<b>Action</b>	Contact the message sender to ensure that a supported RC2 key length is being used.

<b>TNS.0001.3259</b>	<b>Supplied certificate cannot decrypt content</b>
<b>Explanation</b>	Decryption failed as the available certificates failed to decrypt content.
<b>Action</b>	Check if the certificates are correctly mapped to the user.
<b>TNS.0001.3300E</b>	<b>No algorithm specified</b>
<b>Explanation</b>	Mandatory 'algorithm' input parameter contained no value.
<b>Action</b>	Specify a valid value for the 'algorithm' input parameter. Valid values are either "SHA-1" or "MD5".
<b>TNS.0001.3301E</b>	<b>Specified algorithm {0}, not supported</b>
<b>Explanation</b>	The 'algorithm' Input parameter contained an invalid value.
<b>Action</b>	Specify a valid value for the 'algorithm' input parameter. Valid values are either "SHA-1" or "MD5".
<b>TNS.0001.3302E</b>	<b>Security provider not found</b>
<b>Explanation</b>	An internal error occurred.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0001.3303E</b>	<b>Input to createMessageDigest must be byte[] or InputStream</b>
<b>Explanation</b>	The 'input' parameter must be a byte array or InputStream object.
<b>Action</b>	Specify a byte array or InputStream for the 'input' parameter.
<b>TNS.0001.3304E</b>	<b>Parameter "data" must be a byte[] or InputStream</b>
<b>Explanation</b>	The 'data' input parameter must be a byte array or InputStream object.
<b>Action</b>	Specify a byte array or InputStream for the 'data' parameter.
<b>TNS.0001.3305E</b>	<b>Parameter "signerInfo" cannot be null</b>
<b>Explanation</b>	Mandatory 'signerInfo' input parameter must contain a value.
<b>Action</b>	Specify valid information for the 'signerInfo' input parameter.
<b>TNS.0001.3306E</b>	<b>Unable to process "signerInfo" at index {0}</b>
<b>Explanation</b>	An error occurred attempting to process the signerInfo at index <index>.
<b>Action</b>	The server error log contains a stack trace with additional information about the error.

---

<b>TNS.0001.3307E</b>	<b>Invalid certificate chain</b>
<b>Explanation</b>	Cannot recognize certificates.
<b>Action</b>	Check certificate format. The certificate must be a DER encoded ASN.1 format.
<b>TNS.0001.3308E</b>	<b>Invalid certificate at index {0}</b>
<b>Explanation</b>	Cannot recognize certificate in chain at index: <index>.
<b>Action</b>	Check certificate format. The certificate must be a DER encoded ASN.1 format.
<b>TNS.0001.3309E</b>	<b>Required parameter "signatureStream" cannot be null.</b>
<b>Explanation</b>	Required 'signatureStream' parameter cannot be null.
<b>Action</b>	Pass an OutputStream object to the wm.tn.mime:sign service, in the 'signatureStream' parameter.
<b>TNS.0001.3310E</b>	<b>Error occured reading input stream, cannot construct signature.</b>
<b>Explanation</b>	Error occurred while reading the message content.
<b>Action</b>	Check input data source for errors.
<b>TNS.0001.3311E</b>	<b>Hash Algorithm {0} not supported for signer at index {1}</b>
<b>Explanation</b>	Hash Algorithm <algorithmName> not supported for signer at index <index>.
<b>Action</b>	Change the <algorithmName> at <index> to be one of the allowed algorithm names: "MD5" or "SHA-1".
<b>TNS.0001.3312E</b>	<b>Bad certificate. Unable to set signer certificates.</b>
<b>Explanation</b>	Cannot recognize certificate in chain at index: <index>.
<b>Action</b>	Check certificate format. The certificate must be a DER encoded ASN.1 format.
<b>TNS.0001.3313E</b>	<b>Input parameter "signature" cannot be null.</b>
<b>Explanation</b>	The 'signature' input parameter cannot be null.
<b>Action</b>	Pass the signature to verify into the service in the 'signature' input parameter. The 'signature' object should be either a byte array or an InputStream object.

<b>TNS.0001.3314E</b>	<b>Input parameter "signature" must be a byte[] or InputStream</b>
<b>Explanation</b>	The 'signature' input parameter must be a byte[] or InputStream.
<b>Action</b>	The 'signature' input parameter must be a byte[] or InputStream.
<b>TNS.0001.3315E</b>	<b>Input parameter "data" required for verifying detached signature</b>
<b>Explanation</b>	The 'data' input parameter cannot be null.
<b>Action</b>	Pass in the 'data' input parameter of the service, the data that is to be verified. The 'data' object should be either a byte array or an InputStream object.
<b>TNS.0001.3316E</b>	<b>Input parameter "data" must be a byte[] or InputStream</b>
<b>Explanation</b>	The 'data' input parameter must be a byte[] or InputStream.
<b>Action</b>	The 'data' input parameter must be a byte[] or InputStream.
<b>TNS.0001.3317E</b>	<b>An error occurred while attempting to verify the signature.</b>
<b>Explanation</b>	Problem while reading from input data source.
<b>Action</b>	Check input data source for errors.
<b>TNS.0001.3318E</b>	<b>Signature provided is not PKCS#7 SignedData</b>
<b>Explanation</b>	Signature provided is not PKCS#7 SignedData.
<b>Action</b>	The wm.tn.mime:verify service can verify PKCS#7 SignedData signature only.
<b>TNS.0001.3319E</b>	<b>Input parameter "outputStream" must be an OutputStream</b>
<b>Explanation</b>	The 'outputStream' input parameter must be an OutputStream.
<b>Action</b>	The 'outputStream' input parameter must be an OutputStream.
<b>TNS.0001.3320E</b>	<b>Input contained no signer information when processed as {0} type signature</b>
<b>Explanation</b>	The message is not properly signed.
<b>Action</b>	This message cannot be verified. Contact the message creator to verify the proper message structure.
<b>TNS.0001.3321E</b>	<b>Parameter "data" must be null when parameter detachedSignature equals false.</b>
<b>Explanation</b>	The 'data' parameter must be null when 'detachedSignature' parameter equals to false.
<b>Action</b>	If the signature is detached, then set the 'detachedSignature' parameter to "true". Otherwise, do not pass in a value for 'data'. The signed message should be passed in via the 'signature' input parameter.

---

<b>TNS.0001.3322</b>	<b>Parameter "data" must not be null</b>
<b>Explanation</b>	The 'data' input parameter cannot be null.
<b>Action</b>	Pass the data into the service in the 'data' input parameter. The 'data' object should be either a byte array or an InputStream object.
<b>TNS.0001.3323E</b>	<b>Certificate chain cannot be null</b>
<b>Explanation</b>	Certificate chain cannot be null.
<b>Action</b>	Specify a certificate chain to use to sign this message.
<b>TNS.0001.3324E</b>	<b>Private key or keyAlias required</b>
<b>Explanation</b>	Private key or keyAlias required.
<b>Action</b>	To sign this message, specify either a private key, or use a keyAlias.
<b>TNS.0001.3325E</b>	<b>Unable to decode signed message. Verify that signature type specified (detached or implicit) matches actual type.</b>
<b>Explanation</b>	Unable to decode the signed message.
<b>Action</b>	Verify that the specified signature type (detached or implicit) matches the actual type.
<b>TNS.0001.3326</b>	<b>Unable to create digest. Input parameter "data" must be of type com.wm.app.tn.mime.DigestableInputStream or byte[].</b>
<b>Explanation</b>	Error while creating message digest.
<b>Action</b>	Check that the input parameter is passed correctly. Input parameter 'data' must be of type com.wm.app.tn.mime.DigestableInputStream, or byte[].
<b>TNS.0001.3327E</b>	<b>Unable to write message to outputStream.</b>
<b>Explanation</b>	Error occurred while writing the signed message.
<b>Action</b>	The server error log contains a stack trace with additional information about the error.
<b>TNS.0001.3328E</b>	<b>Only one "{0}" can be specified in "signerInfo"</b>
<b>Explanation</b>	When signing a message using a profile alias, you can only use one alias.
<b>Action</b>	Sign the message with only one profile alias.

<b>TNS.0001.3400E</b>	<b>Values are required for both input parameters type and id</b>
<b>Explanation</b>	Values are required for both 'type' and 'id' input parameters.
<b>Action</b>	Set the 'type' input parameter to "file" and the 'id' parameter to the name of the file that the InputStream will read from.
<b>TNS.0001.3401E</b>	<b>Input parameter type cannot be null</b>
<b>Explanation</b>	Values are required for both 'type' and 'id' input parameters.
<b>Action</b>	Set the 'type' input parameter to "file" and the 'id' parameter to the name of the file that the InputStream will read from.
<b>TNS.0001.3402E</b>	<b>Input parameter id cannot be null</b>
<b>Explanation</b>	Values are required for both 'type' and 'id' input parameters.
<b>Action</b>	Set the 'type' input parameter to "file" and the 'id' parameter to the name of the file that the InputStream will read from.
<b>TNS.0001.3403E</b>	<b>Unable to open SharedInputStream</b>
<b>Explanation</b>	An error occurred while reading from the specified data source.
<b>Action</b>	Check that the specified data source exists. The Integration Server error log should contain additional error information.
<b>TNS.0001.3404E</b>	<b>Value "{0}" for parameter type is not supported. Please select from allowed values.</b>
<b>Explanation</b>	The 'type' input parameter must be set to "file".
<b>Action</b>	Provide an allowed value. The 'type' input parameter must be set to "file".
<b>TNS.0001.3501E</b>	<b>Parameter "{0}" must not be null</b>
<b>Explanation</b>	The parameter called <parameterName> must be available but it does not exist in the pipeline .
<b>Action</b>	Specify a valid value for the <parameterName> parameter.
<b>TNS.0001.4001E</b>	<b>No profile store to validate partner ID</b>
<b>Explanation</b>	Unable to retrieve the profile store, probably due to a database error or a validation error.
<b>Action</b>	Check that the data is not corrupted or the database connection is active.

---

<b>TNS.0001.4002E</b>	<b>Error transforming attribute {0}: {1}</b>
<b>Explanation</b>	An exception was thrown while transforming a document attribute value.
<b>Action</b>	The exception was written to the server log. See the log for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0001.4003E</b>	<b>BizDocAttribute: can't connect to profile store</b>
<b>Explanation</b>	Encountered an exception during initialization.
<b>Action</b>	Contact Software AG Global Support. Prepare the following information: server and error logs, a copy of the Support Information page from the Trading Networks Console, and the WmTN/config/properties.cnf file.
<b>TNS.0001.4006E</b>	<b>No profile store to transform attribute {0}</b>
<b>Explanation</b>	Trading Networks was unable to retrieve the profile store.
<b>Action</b>	The exception was written to the server log. See the log for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0001.4007E</b>	<b>Unable to transform attribute {0}: attribute type {1} doesn't match function type {2}</b>
<b>Explanation</b>	Trading Networks could not transform the value of the attribute because the selected transformation is inappropriate for the data type of the attribute.
<b>Action</b>	Using My webMethods, update the TN document type that specifies the invalid transformation for the specified attribute. Select a transformation that is appropriate for the data type of the attribute.
<b>TNS.0001.4008E</b>	<b>Error fetching all attributes: {0}</b>
<b>Explanation</b>	An exception was thrown while reading all attributes from the database.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0001.4009E</b>	<b>Error defining attribute {0}: {1}</b>
<b>Explanation</b>	An exception was thrown while saving an attribute to the database.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0001.4010E</b>	<b>Error listing types for {0}: {1}</b>
<b>Explanation</b>	An exception was thrown while retrieving all TN document types that use an attribute.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.

<b>TNS.0001.4011E</b>	<b>Error redefining attribute {0}: {1}</b>
<b>Explanation</b>	An exception was thrown while updating an attribute in the database.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0001.4012E</b>	<b>Supplied value must be a number</b>
<b>Explanation</b>	A processing rule contains extended criteria that uses a custom attribute with a NUMBER data type. However, the value you specified in the condition for this attribute is not a numeric value.
<b>Action</b>	Using My webmethods, update the extended criteria in the processing rule to provide a numeric value for attributes that have a NUMBER data type.
<b>TNS.0001.4013E</b>	<b>Supplied value can not be transformed to a date</b>
<b>Explanation</b>	A processing rule contains extended criteria that uses a custom attribute with a DATETIME data type. However, the value you specified in the condition for this attribute is not a date.
<b>Action</b>	Using My webmethods, update the extended criteria in the processing rule to supply a date value for attributes that have a DATETIME data type.
<b>TNS.0001.4014E</b>	<b>{0} attribute value is a date but there is no transform.</b>
<b>Explanation</b>	A TN document type indicates that a custom attribute with a DATETIME data type should be extracted from a document. However, the TN document type does not specify a date transformation for the custom attribute.
<b>Action</b>	Using My webmethods, update the TN document type to specify an appropriate date transformation for the custom attribute.
<b>TNS.0001.4015E</b>	<b>{0} attribute is configured for custom transformation, but no transformation service is specified.</b>
<b>Explanation</b>	A TN document type indicates that a custom attribute should perform custom attribute transformation. However, the TN document type does not specify a transformation service.
<b>Action</b>	Using My webMethods, update the TN document type to specify a transformation service.
<b>TNS.0001.4016E</b>	<b>Error performing custom transformation on the {0} attribute.</b>
<b>Explanation</b>	Encountered an exception while updating an attribute in the database.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

<b>TNS.0001.4017E</b>	<b>Custom transformation {0} for the {1} attribute returned the wrong type. Should be {2}</b>
<b>Explanation</b>	Custom attribute transformation did not return the data type that matches the data type of the associated attribute.
<b>Action</b>	Modify the custom attribute transformation service to return the correct data type specified in the error message.
<b>TNS.0001.4018E</b>	<b>Custom transformation service {0} for the {1} attribute did not return "newValues" in the pipeline.</b>
<b>Explanation</b>	Custom attribute transformation service did not return the required output parameter 'newValues'.
<b>Action</b>	Modify the custom attribute transformation service to return the 'newValues' output parameter.
<b>TNS.0001.4019E</b>	<b>{0} attribute value is a date list but there is no transform.</b>
<b>Explanation</b>	The TN document type does not specify a transformation for a date list type attribute.
<b>Action</b>	Using My webMethods, update the TN document type to specify a transformation service.
<b>TNS.0001.4020E</b>	<b>Unable to parse the given value. Value {0} could not be converted to date format</b>
<b>Explanation</b>	Unable to convert the value extracted from the document to a date format.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0001.4021E</b>	<b>Attribute transformation for {0} of doctype {1} generated an exception. The original exception message is: {2}.</b>
<b>Explanation</b>	Encountered an exception while updating an attribute in the database.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0001.4022E</b>	<b>Attribute transformation function code {0} is invalid.</b>
<b>Explanation</b>	A TN document type indicates an invalid attribute transformation function.
<b>Action</b>	Using My webMethods, update the TN document type to specify a valid transformation function.

<b>TNS.0001.5006E</b>	<b>Converting the signed body of this document into a string failed. Verification cannot continue. The original signed body was {0}.</b>
<b>Explanation</b>	Conversion failed for a document.
<b>Action</b>	If the signed body of the document is invalid, notify the document sender.
<b>TNS.0001.5008E</b>	<b>This doctype ({0}) has no verification service defined. Verification cannot continue.</b>
<b>Explanation</b>	This TN document type (<doctypeName>) has no verification service defined.
<b>Action</b>	If you are using a built-in TN document type, contact Software AG Global Support. If you are using your own TN document type, specify a verification service for it.
<b>TNS.0001.5009E</b>	<b>No Verification Service</b>
<b>Explanation</b>	The TN document type has no verification service defined. Verification cannot continue.
<b>Action</b>	If you are using a built-in TN document type, contact Software AG Global Support. If you are using your own TN document type, specify a verification service for it.
<b>TNS.0001.5011E</b>	<b>The signature query for doctype {0} ({1}) generated an error. The error was {2}.</b>
<b>Explanation</b>	The signature query (<query>) for the TN document type (<doctypeName>) generated an error. The error was <exceptionMessage>.
<b>Action</b>	If the signed body of the document is invalid, notify the document sender.
<b>TNS.0001.5015E</b>	<b>Query Failed</b>
<b>Explanation</b>	A signature query was defined for the TN document type but it failed to produce a result for this document.
<b>Action</b>	Either adjust the signature query that is defined in the TN document type, or notify the document sender that the structure of the document is incorrect.
<b>TNS.0001.5017E</b>	<b>This document type ({0}) is missing one or both of its signature queries (Signature and SignedBody). Verification cannot proceed.</b>
<b>Explanation</b>	One or both of this document type signature queries (Signature and SignedBody) may be missing.
<b>Action</b>	Using My webMethods, update the TN document type to specify both, a signature query and a signed body query.

---

<b>TNS.0001.5018E</b>	<b>Missing Signature Query(s)</b>
<b>Explanation</b>	This TN document type is missing one or both of its signature queries (Signature and SignedBody). Trading Networks cannot proceed with the verification of the signature.
<b>Action</b>	Using My webMethods, update the TN document type to specify both, a signature query and a signed body query.
<b>TNS.0001.5019E</b>	<b>The signed body query for doctype {0} ({1}) generated an error. The error was {2}.</b>
<b>Explanation</b>	The signed body query (<query>) for the TN document type (<doctypeName>) generated an error. The error was <exceptionMessage>.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception. If the structure of the document is incorrect, notify the document sender.
<b>TNS.0001.5020E</b>	<b>The signature of this document was invalid; no information was available about the party or parties that signed it.</b>
<b>Explanation</b>	The signature of this document might be invalid.
<b>Action</b>	Notify the document sender.
<b>TNS.0001.5021E</b>	<b>No Signer Info Available</b>
<b>Explanation</b>	The signature of this document was not valid. No information was available about the party or parties that signed it.
<b>Action</b>	Notify the document sender.
<b>TNS.0001.5022E</b>	<b>The PKCS verification service, pub.security.pkcs7:verify, produced an error trying to verify this document. The error was {0}.</b>
<b>Explanation</b>	Encountered an exception while verifying a document signature.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception. If the signature is invalid, notify the document sender.
<b>TNS.0001.5023E</b>	<b>PKCS Service Error</b>
<b>Explanation</b>	The PKCS verification service pub.security.pkcs7:verify, produced an error while trying to verify this document.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception. If the signature is invalid, notify the document sender.

**TNS.0001.5024E**      **The verification service for this document ({0}) generated an error. The original error was {1}.**

**Explanation**      An exception was thrown while verifying a document signature.

**Action**            Take appropriate action to resolve the problem described in the exception. If the signature is invalid, notify the document sender.

**TNS.0001.5025E**      **Verification Failed**

**Explanation**      An exception was thrown while verifying a document signature.

**Action**            Take appropriate action to resolve the problem described in the exception. If the signature is invalid, notify the document sender.

**TNS.0001.5026E**      **The signature query for doctype {0} ({1}) failed to produce a value. Without a signature, verification cannot proceed.**

**Explanation**      A signature query was defined for the TN document type but it failed to produce a result for this document.

**Action**            Either update the TN document type to adjust the signature query, or notify the document sender that the structure of the document is incorrect.

**TNS.0001.5028E**      **The signed body query for doctype {0} ({1}) failed to produce a value. Without a signed body, verification cannot proceed.**

**Explanation**      A signed body query was defined for the TN document type but it failed to produce a result for this document.

**Action**            Either update the TN document type to adjust the signed body query, or notify the document sender that the structure of the document is incorrect.

**TNS.0001.5030E**      **Base-64 decoding the signature for this document failed to produce a value. The signature (before decoding) was {0,number} bytes.**

**Explanation**      An error occurred while decoding the signature. The signature might be invalid.

**Action**            Notify the document sender.

**TNS.0001.5031E**      **Decoding Error**

**Explanation**      Trading Networks could not decode the signature. The signature might be invalid.

**Action**            Notify the document sender.

---

<b>TNS.0001.5032E</b>	<b>XML {0} failed: does not apply to non-XML documents</b>
<b>Explanation</b>	Trading Networks attempted to perform an operation on a non-XML document. However, the operation can be performed only on XML documents.
<b>Action</b>	Check whether the input document is a valid XML document.
<b>TNS.0001.5033E</b>	<b>XML {0} failed: no document content available</b>
<b>Explanation</b>	Trading Networks attempted to perform an operation that failed because the document has no content.
<b>Action</b>	Notify the document sender.
<b>TNS.0001.5034E</b>	<b>Bad XML content</b>
<b>Explanation</b>	An exception was thrown while retrieving the document.
<b>Action</b>	The document may not be a valid XML document.
<b>TNS.0001.5035E</b>	<b>An error prevented fetching the content of this XML document for {0}. The original error was {2}.</b>
<b>Explanation</b>	An exception was thrown while retrieving the document.
<b>Action</b>	Check the database and make sure that the data is not corrupted.
<b>TNS.0001.5036E</b>	<b>Signature Verification failed : The verification service, {0} aborted processing of this document. The message was {1}.</b>
<b>Explanation</b>	A RoutingAbortedException was thrown by the verification service that caused the document processing to abort.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception. If the document is invalid, notify the sender.
<b>TNS.0001.5037E</b>	<b>The signing service, {0} aborted processing of this document. The message was {1}.</b>
<b>Explanation</b>	A RoutingAbortedException was thrown by the verification service, which caused the document processing to abort.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception. If the document is invalid, notify the sender.

<b>TNS.0001.6001E</b>	<b>Attribute transform for {0} of doctype {1} failed to produce a value. The transform function was {3}, the first original value was {2}.</b>
<b>Explanation</b>	The data type of the attribute might not match the type of the data extracted from the document.
<b>Action</b>	Make sure that the data type of the attribute matches the type of the data extracted from the document. If this is an XML TN document type, make sure that the XQL query that extracts the attribute is correct.
<b>TNS.0001.6002E</b>	<b>Attribute query for {0} of doctype {1} failed to produce a result. The document may not be complete. The query was: {2}</b>
<b>Explanation</b>	The XQL query for the attribute did not return a value.
<b>Action</b>	Change the XQL query accordingly to return correct result.
<b>TNS.0001.6003E</b>	<b>Attribute query for {0} of doctype {1} generated an exception. The original exception message is: {2}.</b>
<b>Explanation</b>	There is either a problem with the document, or with the query.
<b>Action</b>	Examine the document to see if it is well-structured XML. Correct and resubmit if needed. Examine the query to ensure that it is valid. Change the query if needed.
<b>TNS.0001.6004E</b>	<b>Unable to get XML content for corrupted doc {0}. The original exception message is: {1}.</b>
<b>Explanation</b>	The document may be corrupted.
<b>Action</b>	Fix the document and submit it again.
<b>TNS.0001.6005E</b>	<b>Transform for {0} of doctype {1} generated an exception. The transform function was {2}. The original exception message is: {3}.</b>
<b>Explanation</b>	There is either a problem with the document, or with the query.
<b>Action</b>	Examine the document to ensure that it is well-structured XML. Correct and resubmit if needed. Examine the query to ensure that it is valid. Adjust the query if needed.
<b>TNS.0001.6006E</b>	<b>Transform for {0} of doctype {1} failed to produce a value. The transform function was {3}, the first original value was {2}.</b>
<b>Explanation</b>	Perhaps the data type of the attribute does not match the type of the data extracted from the document.
<b>Action</b>	Make sure that the data extracted from the document is the same type as the attribute. If this is an XML TN document type, make sure that the XQL query that extracts the attribute is correct.

<b>TNS.0001.6007E</b>	<b>Envelope query for {0} of doctype {1} failed to produce a result. The document may not be complete. The query was: {2}</b>
<b>Explanation</b>	The XQL query for the attribute did not return a value.
<b>Action</b>	Fix the XQL query, if needed.
<b>TNS.0001.6008E</b>	<b>Envelope query for {0} of doctype {1} generated an exception. The original exception message is: {2}.</b>
<b>Explanation</b>	The document may be corrupted.
<b>Action</b>	Correct the document and submit it again.
<b>TNS.0001.6009E</b>	<b>There was an error in trying to get XML header information (DOCTYPE and DTD). The document ({0}) is probably not valid XML.</b>
<b>Explanation</b>	Probably, the document is not a well-structured XML.
<b>Action</b>	Correct the document and submit it again.
<b>TNS.0001.6010E</b>	<b>There was an error in trying to get XML header information (DOCTYPE and DTD). The document ({0}) is probably not valid XML. The original exception message is: {1}</b>
<b>Explanation</b>	Probably, the document is not a well-structured XML.
<b>Action</b>	Correct the document and submit it again.
<b>TNS.0001.6011E</b>	<b>XQL query {1} failed recognizing document {0}. The document is probably not valid XML. The original exception message is: {2}.</b>
<b>Explanation</b>	Probably, the document is not a well-structured XML. See the exception message for details.
<b>Action</b>	Correct the document and submit it again.
<b>TNS.0001.6013E</b>	<b>No bizdoc supplied to lookup validation schema</b>
<b>Explanation</b>	The wm.tn.doc.xml:getRecordBlueprint service was invoked with no BizDocEnvelope in the pipeline.
<b>Action</b>	Supply a BizDocEnvelope when invoking the wm.tn.doc.xml:getRecordBlueprint service.

<b>TNS.0001.6014E</b>	<b>Non-XML bizdoc supplied to lookup validation schema</b>
<b>Explanation</b>	The BizDocEnvelope passed to the wm.tn.doc.xml:getRecordBlueprint service is not an XML document type.
<b>Action</b>	Supply a BizDocEnvelope that matches an XML TN document type when invoking the wm.tn.doc.xml:getRecordBlueprint service.
<b>TNS.0001.6015E</b>	<b>No bizdoc ID supplied for testing validation</b>
<b>Explanation</b>	The wm.tn.doc.xml:testValidate service was invoked with no internal document ID in the pipeline.
<b>Action</b>	Supply an internal document ID (docID) when invoking the wm.tn.doc.xml:testValidate service.
<b>TNS.0001.6016E</b>	<b>No such bizdoc: {0}</b>
<b>Explanation</b>	The wm.tn.doc.xml:testValidate service was invoked with an invalid internal document ID in the pipeline.
<b>Action</b>	Provide a valid internal document ID when invoking the wm.tn.doc.xml:testValidate service.
<b>TNS.0001.6017E</b>	<b>Required attribute is missing</b>
<b>Explanation</b>	An attribute is defined as required by the document type but the document that matched the document type did not contain this attribute.
<b>Action</b>	Either change the document type so that this attribute is no longer required, or instruct the document sender to supply a value for the attribute.
<b>TNS.0001.6018E</b>	<b>The {0} attribute is required by the {1} doctype. The query {2} did not return any results</b>
<b>Explanation</b>	An attribute is defined as required by the document type but the document that matched the document type did not contain this attribute.
<b>Action</b>	Either change the document type so that this attribute is no longer required, or instruct the document sender to supply a value for the attribute.
<b>TNS.0001.6019E</b>	<b>Attribute transformation for {0} of doctype {1} generated an exception. The query is {2}. The original exception message is: {3}.</b>
<b>Explanation</b>	Encountered an exception.
<b>Action</b>	If the document is corrupted, notify the document sender.

---

<b>TNS.0001.7003</b>	<b>Error while getting {0}. Find if the EDI package is enabled and running in Integration Server.</b>
<b>Explanation</b>	WmEDI Package may be disabled.
<b>Action</b>	Check if the WmEDI package is enabled and running in Integration Server.
<b>TNS.0001.7004</b>	<b>Error while getting EDI Standards. Input for standard field cannot be null, its is a mandatory field.</b>
<b>Explanation</b>	Input for standard field cannot be null, it is a mandatory field.
<b>Action</b>	Configure the standard field in the input and run the service.
<b>TNS.0001.7005</b>	<b>Error while getting EDI Transactions. Input for standard field cannot be null, its is a mandatory field.</b>
<b>Explanation</b>	Input for standard field cannot be null, it is a mandatory field.
<b>Action</b>	Configure the standard field and run the query again.
<b>TNS.0001.7006</b>	<b>Error while getting EDI Transactions. Input for version field cannot be null, its is a mandatory field.</b>
<b>Explanation</b>	Input for version field cannot be null, it is a mandatory field.
<b>Action</b>	Configure the version field and run the query again.
<b>TNS.0001.7007</b>	<b>Error while getting {0}. Input for {1} field cannot be null, its is a mandatory field.</b>
<b>Explanation</b>	Input field suggested in error message is a mandatory field.
<b>Action</b>	Configure the input field and run the query again.
<b>TNS.0001.7008</b>	<b>Error while querying for document attributes.</b>
<b>Explanation</b>	Encountered an exception while querying document attributes.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0001.7009</b>	<b>Error while getting the related doctypes for doctype attribute {0}.</b>
<b>Explanation</b>	An error occurred while getting related doctypes for the associated doctype attribute. The error may be because of an SQLException.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

<b>TNS.0001.7010</b>	<b>Error while changing the status of the doctype attributes.</b>
<b>Explanation</b>	An error occurred while changing the status of the doctype attributes.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0001.7011</b>	<b>Error while getting doctype attribute for doctype attribute ID {0}.</b>
<b>Explanation</b>	An error occurred while getting doctype attribute for the associated attribute ID. This may be because of an SQLException while querying the attribute.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0001.7012</b>	<b>Error while updating doctype attribute for doctype attribute ID {0}.</b>
<b>Explanation</b>	An error occurred while updating the doctype attribute. This may be because of an SQLException while updating the attribute.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0001.7013</b>	<b>Error while changing the status of the doctype attribute ID {0}.</b>
<b>Explanation</b>	An error occurred while updating the doctype attribute. This may be because of an SQLException while updating the attribute.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0001.7014</b>	<b>Error while viewing doctype attribute. Input for docAttrID field cannot be null, its is a mandatory field.</b>
<b>Explanation</b>	An error occurred while viewing the doctype attribute. This may be because of an SQLException while querying for the attribute.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0001.7015</b>	<b>Error while updating doctype attribute. Input for docAttrID field cannot be null, its is a mandatory field.</b>
<b>Explanation</b>	Input for docAttrID field cannot be null, it is a mandatory field.
<b>Action</b>	Configure the docAttrID field while updating the doctype attribute.

<b>TNS.0001.7016</b>	<b>Error while adding doctype attribute. Check whether all input variables have been passed properly.</b>
<b>Explanation</b>	Some mandatory fields may not have been passed before calling the service.
<b>Action</b>	Configure all input variables before calling the service.
<b>TNS.0001.7017E</b>	<b>Attribute name "{0}" already exists. Change the name and save again.</b>
<b>Explanation</b>	Attribute with the same name already exists.
<b>Action</b>	Change the attribute name and save.
<b>TNS.0001.7018</b>	<b>Error while updating doctype attribute. Attribute name with "{0}" already exists. Change the name and save again.</b>
<b>Explanation</b>	Attribute with same name already exists.
<b>Action</b>	Change the name and save.
<b>TNS.0001.7019</b>	<b>Error while querying for document attributes {0}.</b>
<b>Explanation</b>	An error occurred while querying doctype attributes. This may be because of an SQLException while querying the attribute.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0002.1001E</b>	<b>"{0}" is empty. At least one {1} must be supplied. Please supply the required value.</b>
<b>Explanation</b>	You did not supply a value for the specified variable. At least one value is required.
<b>Action</b>	Supply at least one value for the specified field and try again.
<b>TNS.0002.1002E</b>	<b>"{0}" and "{1}" are required ({0}={2}, {1}={3}). Please supply the required values.</b>
<b>Explanation</b>	Both values are required.
<b>Action</b>	Supply both values.
<b>TNS.0002.1009E</b>	<b>The value originally supplied as sender ID for this document was not a valid partner ID. The value was {0}.</b>
<b>Explanation</b>	Partner ID supplied as sender ID is not being recognized as valid partner.
<b>Action</b>	Either create a partner profile for the document sender, add this ID to an existing partner's profile, or tell the document sender to resend the document using a different sender ID value.

<b>TNS.0002.1010E</b>	<b>Error formatting error message {0}: {1}</b>
<b>Explanation</b>	Unable to format the error message.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0002.1011E</b>	<b>The value originally supplied as receiver ID for this document was not a valid partner ID. The value was {0}.</b>
<b>Explanation</b>	Partner ID supplied as receiver ID is not being recognized as valid partner.
<b>Action</b>	Either create a partner profile for the document receiver, add this ID to an existing partner's profile, or tell the document sender to resend the document using a different receiver ID value.
<b>TNS.0002.1012E</b>	<b>{0} is null.</b>
<b>Explanation</b>	An internal variable is unexpectedly null.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0002.1013E</b>	<b>At least one of "{0}" and "{1}" is required.</b>
<b>Explanation</b>	At least one of the input fields is required, either its null or empty.
<b>Action</b>	Provide non-null value for at least one input parameter and try again.
<b>TNS.0002.1016E</b>	<b>"sourceVersion" is required. Please supply the required value.</b>
<b>Explanation</b>	A required value is missing.
<b>Action</b>	Supply the required value.
<b>TNS.0002.1017E</b>	<b>"feature" is required. Please supply the required value.</b>
<b>Explanation</b>	A required value is missing.
<b>Action</b>	Supply the required value.
<b>TNS.0002.1018E</b>	<b>At least one input is required.</b>
<b>Explanation</b>	All input fields are found to be null, at least one input should not be null.
<b>Action</b>	Provide at least one non-null value for input and try again.

---

<b>TNS.0002.1019E</b>	<b>Enumeration contains elements that are not Strings.</b>
<b>Explanation</b>	An unexpected value was passed to an internal method.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0002.1021E</b>	<b>schema cannot be null.</b>
<b>Explanation</b>	Attempted to create a Trading Networks IData object with an empty set of name/value pairs.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0002.1022E</b>	<b>schema rows must be 2 wide</b>
<b>Explanation</b>	Attempted to create a Trading Networks IData object without set of name/value pairs.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0002.1023E</b>	<b>keys cannot be null</b>
<b>Explanation</b>	Attempted to create a Trading Networks IData object with keys as null. Keys cannot be null.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0002.1024E</b>	<b>index out of bounds: {0}</b>
<b>Explanation</b>	Attempted to seek beyond the end of or before the start of a TNFixedData object.
<b>Action</b>	Supply a valid index to the seek method.
<b>TNS.0002.1025E</b>	<b>TNFixedData does not support setKey</b>
<b>Explanation</b>	Attempted to use an unsupported method.
<b>Action</b>	Do not call the setKey method.
<b>TNS.0002.1027E</b>	<b>TNFixedData does not support delete</b>
<b>Explanation</b>	Attempted to use an unsupported method.
<b>Action</b>	Do not call the delete method.
<b>TNS.0002.1028E</b>	<b>illegal null key</b>
<b>Explanation</b>	Supplied a null key to the keyMatch method on a TNFixedData object.
<b>Action</b>	Supply a valid key value.

<b>TNS.0002.1031E</b>	<b>Must supply props</b>
<b>Explanation</b>	A required value(props) is missing for wm.tn.admin:setProperties().
<b>Action</b>	Supply the required value for field(props) and try again.
<b>TNS.0002.1032E</b>	<b>Must shutdown before starting up again</b>
<b>Explanation</b>	Invoked the wm.tn.admin:startup service while the WmTN package is enabled and loaded.
<b>Action</b>	Use the Integration Server Administrator to stop and start the WmTN package. Do not invoke the wm.tn.admin:start service directly.
<b>TNS.0002.1042E</b>	<b>No such enum: {0}</b>
<b>Explanation</b>	A wm.tn.enumerate service was invoked with an invalid query enumeration identifier.
<b>Action</b>	Supply a valid enumeration identifier.
<b>TNS.0002.1043E</b>	<b>Either {0} or {1} must be supplied. Please supply one of these values.</b>
<b>Explanation</b>	A valid value for either of the required field was not supplied.
<b>Action</b>	Supply one of the valid values which are listed in the error message.
<b>TNS.0002.1044E</b>	<b>{0} is required whenever a value for {1} is supplied. Please supply a value for {0}.</b>
<b>Explanation</b>	A storageRef value was supplied, but no value was supplied for storageType.
<b>Action</b>	Supply a value for the storageType variable. Either supply value for both related fields or keep both fields null and try again.
<b>TNS.0002.1047E</b>	<b>The following TN properties can only take numeric values: {0}</b>
<b>Explanation</b>	Attempted to assign non-numeric values to numeric system properties.
<b>Action</b>	Supply numeric values for numeric system properties.
<b>TNS.0002.1048E</b>	<b>Error setting features on SAX parser. Exception message is: {0}</b>
<b>Explanation</b>	Threw a SAXException while initializing the SAX parser.
<b>Action</b>	Contact Software AG Global Support.

---

<b>TNS.0002.1056E</b>	<b>The {0} service is for Trading Networks internal use only.</b>
<b>Explanation</b>	The specified service was invoked, but not by Trading Networks. This service is for Trading Networks internal use only.
<b>Action</b>	Do not invoke this service.
<b>TNS.0002.1057E</b>	<b>Error encountered in invoking service wm.tn.samples.helpServices:installTNSamplesACLs</b>
<b>Explanation</b>	Internal error installing ACLs for Trading Networks Sample services.
<b>Action</b>	If you want to protect the WmTNSamples services, invoke the wm.tn.samples:installTNSamplesACLs service.
<b>TNS.0002.1058E</b>	<b>Error encountered in writing TN ACL information to disk</b>
<b>Explanation</b>	An exception was thrown saving the Trading Networks ACLs to the file system.
<b>Action</b>	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0002.1059E</b>	<b>ThreadQueue: too many jobs waiting</b>
<b>Explanation</b>	Attempted to spawn more threads than the configured limit.
<b>Action</b>	Use the wm.tn.admin:setThreadQueueConfig service to increase the value of the tn.thread.maxWaiting system property.
<b>TNS.0002.1061E</b>	<b>{0} is not an Integer</b>
<b>Explanation</b>	Invalid data type supplied to a service, expected an Integer value
<b>Action</b>	Supply an Integer for the specified field.
<b>TNS.0002.1065</b>	<b>Error encountered while unregistering TN's XML content handler. The exception message is: {0}</b>
<b>Explanation</b>	Error occurred while unregistering TN's content handler and activating default XML content handler.
<b>Action</b>	See the server log for details. Take appropriate action to resolve the problem described in the exception.

<b>TNS.0002.1066</b>	<b>When scheduleType is {0}, a value must be supplied for {1}. Please supply a value for {1}.</b>
<b>Explanation</b>	Attempted to create new queue with schedule values null for a selected scheduleType.
<b>Action</b>	Supply valid values corresponding to selected schedule type.
<b>TNS.0002.1067E</b>	<b>Unable to update password for {0} with handle {1}</b>
<b>Explanation</b>	An exception was thrown when Trading Networks attempted to update the password associated with a profile delivery method.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0002.1068E</b>	<b>Unable to retrieve password for {0} with handle {1}</b>
<b>Explanation</b>	An exception was thrown when Trading Networks attempted to retrieve the password associated with a profile delivery method.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0002.1069E</b>	<b>Unable to insert password for {0} with handle {1}</b>
<b>Explanation</b>	An exception was thrown when Trading Networks attempted to insert the password associated with a profile delivery method.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0002.1070E</b>	<b>Unable to save password for {0} with handle {1}</b>
<b>Explanation</b>	An exception was thrown when Trading Networks attempted to save the password associated with a profile delivery method.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0002.1071E</b>	<b>Unable to delete password for {0} with handle {1}</b>
<b>Explanation</b>	An exception was thrown when Trading Networks attempted to delete the password associated with a profile delivery method.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0002.1072E</b>	<b>Either {0} or {1} must be supplied, but not both. Please supply a value for only one of these.</b>
<b>Explanation</b>	You supplied the specified two values; however, only one value can be specified.
<b>Action</b>	Supply value for either partByets or partStream and try again.

<b>TNS.0002.1073</b>	<b>Unable to import document type {0}. Attribute {1} is used in the document type but, it is not defined.</b>
<b>Explanation</b>	While importing a doctype, related attribute not found, so unable to import the doctype.
<b>Action</b>	Please either import the related attribute or define before importing the doctype.
<b>TNS.0002.1075</b>	<b>Unable to import processing rule {0}. Sender profile {1} is used in the processing rule but, it is not defined.</b>
<b>Explanation</b>	While importing a processing rule, related sender profile not found, so unable to import the processing rule.
<b>Action</b>	Either import the related sender profile or define it before importing the processing rule.
<b>TNS.0002.1076</b>	<b>Unable to import processing rule {0}. Receiver profile {1} is used in the processing rule but, it is not defined.</b>
<b>Explanation</b>	While importing a processing rule, related receiver profile not found, so unable to import the processing rule.
<b>Action</b>	Either import the related receiver profile or define it before importing the processing rule.
<b>TNS.0002.1077</b>	<b>Unable to import processing rule {0}. Document type {1} is used in the processing rule but, it is not defined.</b>
<b>Explanation</b>	While importing a processing rule, related Document Type not found, so unable to import the processing rule.
<b>Action</b>	Either import the related document type or define it before importing the processing rule.
<b>TNS.0002.1081</b>	<b>Error encountered while extracting doctype with doctypeID {0}. Please check whether it is a valid ID.</b>
<b>Explanation</b>	Could not retrieve Document Type from BizDocStore with provided docTypeID, would not be able to enable/update doc type for monitoring.
<b>Action</b>	Please check whether provided docTypeID is a valid ID, as system was not able to retrieve corresponding Document Type from store.

<b>TNS.0002.1083</b>	<b>Error encountered while setting TN BAM Monitoring status to {0}</b>
<b>Explanation</b>	Error encountered while enabling/disabling TN BAM monitoring. This happened while setting monitoring properties invoking service <code>wm.tn.admin:setProperties()</code> .
<b>Action</b>	Please see the error log.
<b>TNS.0002.2005S</b>	<b>Error(s) encountered in WmTN initialization: {0}</b>
<b>Explanation</b>	Encountered an exception while Trading Networks was initializing. This happened during filling the cache of attribute, type, routing rule and profile.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception and try to reload the package.
<b>TNS.0002.2013S</b>	<b>The <code>wm.tn.access:getConsoleRestrictions</code> service has been deleted, renamed or replaced. Aborting Trading Networks initialization.</b>
<b>Explanation</b>	Aborting Trading Networks initialization as the <code>wm.tn.access:getConsoleRestrictions</code> service has been tempered.
<b>Action</b>	Please contact your administrator to restore the original version of this service.
<b>TNS.0002.2014E</b>	<b>Error filling BizDocAttributeStore cache</b>
<b>Explanation</b>	Encountered an error while reading the document attributes from the database during startup.
<b>Action</b>	An exception was written to the server log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0002.2018W</b>	<b>Unable to register content types with the FlatFile Content Handler. The WmFlatFile package may be disabled. The WmFlatFile package must be enabled in order to use FlatFile capabilities in Trading Networks.</b>
<b>Explanation</b>	The WmFlatFile package is disabled. Unable to register content types with the FlatFile Content Handler.
<b>Action</b>	The WmFlatFile package may be disabled. The WmFlatFile package must be enabled in order to use FlatFile capabilities in Trading Networks.
<b>TNS.0002.3007E</b>	<b><code>wm.tn.admin:installACLs</code>: Unable to find group, {0}</b>
<b>Explanation</b>	The specified group, <code>&lt;group&gt;</code> , has not been created.
<b>Action</b>	Run the <code>wm.tn.admin:install</code> service to create the Trading Networks user groups.

---

<b>TNS.0002.3010S</b>	<b>Can not create IS user group {0}</b>
<b>Explanation</b>	An exception was thrown while creating a user group during server startup.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0002.3011E</b>	<b>Can not create IS user {0}</b>
<b>Explanation</b>	An exception was thrown while creating a user during server startup.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0002.4011E</b>	<b>Error encountered during TN server starting: {0}</b>
<b>Explanation</b>	An exception was thrown while Trading Networks was starting.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0002.4012E</b>	<b>Error encountered during TN server stopping: {0}</b>
<b>Explanation</b>	An exception was thrown while Trading Networks was stopping.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0002.4013E</b>	<b>Error encountered during TN server restarting: {0}</b>
<b>Explanation</b>	An exception was thrown while Trading Networks was restarting.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0002.4019E</b>	<b>TN database connection pool failed: error initializing Datastore</b>
<b>Explanation</b>	An exception was thrown while initializing the Trading Networks database connection pool.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception. Check TN DB configuration details.
<b>TNS.0002.4020E</b>	<b>TN Server failed starting up: error initializing database connection pool</b>
<b>Explanation</b>	An exception was thrown while initializing the Trading Networks database connection pool.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception. Check TN DB configuration details.

<b>TNS.0002.4021E</b>	<b>TN Server failed starting up: OEM restriction was hacked</b>
<b>Explanation</b>	A user or developer attempted to bypass the OEM restrictions. The server will not start.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0002.4024E</b>	<b>TN task manager encountered error: {0}</b>
<b>Explanation</b>	An exception was thrown that has terminated execution of the task manager.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception. You might need to contact Software AG Global Support.
<b>TNS.0002.4025E</b>	<b>TN temporary storage space initialization failed: {0}</b>
<b>Explanation</b>	An exception was thrown while preparing temporary disk space for large files.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception. You might need to change the tn.tspace.location system property to a disk partition that has more free space.
<b>TNS.0002.4028E</b>	<b>Invalid notification type encountered in pkginit:sendNotif</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0002.4039E</b>	<b>MBean cannot record statistics for document id {0}. Document does not exist.</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0002.4040E</b>	<b>Exception thrown while saving document processing statistics.</b>
<b>Explanation</b>	Error encountered while saving document processing statistics to DB.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.1001E</b>	<b>Invalid datatype. "cert" must be a byte[] or a X509Certificate.</b>
<b>Explanation</b>	You invoked a service and supplied a digital certificate value that is not a recognized data type.
<b>Action</b>	Supply either an X509Certificate or the bytes from an X509Certificate.

---

<b>TNS.0003.1005E</b>	<b>The user associated with this certificate ({0}) does not have a TN profile.</b>
<b>Explanation</b>	The supplied digital certificate is associated with an Integration Server user, but that user is not a Trading Networks partner.
<b>Action</b>	Either create a partner profile for the user, or supply a certificate that is associated with a Trading Networks partner.
<b>TNS.0003.1007E</b>	<b>An error occurred when the intended receiver tried to accept this document. The original error message was {0}.</b>
<b>Explanation</b>	An exception was thrown while accepting a polled document.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.1008E</b>	<b>Unable to retrieve partner profile associated with supplied certificate.</b>
<b>Explanation</b>	An exception was thrown while retrieving the partner associated with a digital certificate.
<b>Action</b>	Trading Networks wrote the exception to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.1010E</b>	<b>Unable to save partner's certificate.</b>
<b>Explanation</b>	An exception was thrown while saving a partner's certificate.
<b>Action</b>	Trading Networks wrote the exception to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.1015E</b>	<b>Unable to retrieve signing keys to be used for sending documents to specified partner.</b>
<b>Explanation</b>	The wm.tn.access:getSigningKeys service was unable to retrieve the security information needed to sign documents sent to a partner.
<b>Action</b>	Trading Networks wrote the exception to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.1028E</b>	<b>Invalid feature specified.</b>
<b>Explanation</b>	While checking whether a feature was enabled, Trading Networks discovered that an invalid feature was specified.
<b>Action</b>	Contact Software AG Global Support.

<b>TNS.0003.1029E</b>	<b>Error retrieving Console restrictions.</b>
<b>Explanation</b>	An exception was thrown while determining what features are available to My webMethods Server.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0003.1030E</b>	<b>No session available</b>
<b>Explanation</b>	Attempted an action that requires an active session, but no active session was found.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0003.1031E</b>	<b>No user available from session</b>
<b>Explanation</b>	Unable to determine the connected user as session doesn't have any user defined.
<b>Action</b>	Try defining users and retry or contact your administrator to check database and Integttation Server status.
<b>TNS.0003.1032E</b>	<b>Group TNPartners not defined</b>
<b>Explanation</b>	TNPartners Group was not found
<b>Action</b>	Run the wm.tn.admin:install service to create TNPartners and other required user groups.
<b>TNS.0003.1033</b>	<b>Empty or null username for partner {0}.Also,The username may not have whitespace.</b>
<b>Explanation</b>	Encountered validation error while creating partner account. Iinput field username can't be null and should not contain spaces.
<b>Action</b>	Provide a valid user name and try again.
<b>TNS.0003.2002E</b>	<b>An ID type named {0} already exists.</b>
<b>Explanation</b>	Trading Networks attempted to create an external ID type with the provided name, but an external ID type with that name already exists.
<b>Action</b>	Specify the name of an external ID type that does not already exist when creating an external ID type.
<b>TNS.0003.2003E</b>	<b>A contact type named {0} already exists.</b>
<b>Explanation</b>	Trading Networks attempted to create a contact type with the provided name, but a contact type with that name already exists.
<b>Action</b>	Specify the name of a contact type that does not already exist when creating a contact type.

---

<b>TNS.0003.2004E</b>	<b>A field group named {0} already exists.</b>
<b>Explanation</b>	Trading Networks attempted to create a field group with the provided name, but a field group with that name already exists.
<b>Action</b>	Specify the name of a field group that does not already exist when creating a field group.
<b>TNS.0003.2005E</b>	<b>Could not get profile dictionary</b>
<b>Explanation</b>	Trading Networks encountered an unexpected error during profile dictionary initialization.
<b>Action</b>	The exception was written to the server log. See the server log for details. Take action appropriate to resolve the problem described in the exception.
<b>TNS.0003.2006E</b>	<b>Could not retrieve field definitions</b>
<b>Explanation</b>	An exception was thrown while retrieving profile field definitions.
<b>Action</b>	The exception was written to the server log. See the server log for details. Take action appropriate to resolve the problem described in the exception.
<b>TNS.0003.2007E</b>	<b>Could not add field definition</b>
<b>Explanation</b>	An exception was thrown while saving a profile field definition.
<b>Action</b>	The exception was written to the server log. See the server log for details. Take action appropriate to resolve the problem described in the exception.
<b>TNS.0003.2008E</b>	<b>Could not update field definition</b>
<b>Explanation</b>	An exception was thrown while updating a profile field definition.
<b>Action</b>	The exception was written to the server log. See the server log for details. Take action appropriate to resolve the problem described in the exception.
<b>TNS.0003.2009E</b>	<b>"definition" is required.</b>
<b>Explanation</b>	A required field value was not supplied.
<b>Action</b>	Supply the required value.
<b>TNS.0003.3010E</b>	<b>Unable to map certificate to user for new partner {0}.</b>
<b>Explanation</b>	The wm.tn.security:setVerifyCertificateSet service was unable to save certificates for a new trading partner.
<b>Action</b>	Save the partner's profile with no certificates and then add the partner's certificates.

<b>TNS.0003.3019E</b>	<b>{0} could not retrieve the ProfileStore.</b>
<b>Explanation</b>	The Profile Store is inaccessible.
<b>Action</b>	Reload the WmTN package or restart the Integration Serve that hosts Trading Networks Server.
<b>TNS.0003.3030E</b>	<b>Unable to retrieve the {0} ID for partner {1}.</b>
<b>Explanation</b>	Could not convert the internal partner ID into an external ID.
<b>Action</b>	Make sure the partner has a value for this type of external ID.
<b>TNS.0003.3034W</b>	<b>An invalid or expired certificate was received from {0} and rejected.</b>
<b>Explanation</b>	An invalid or expired certificate was received and rejected from the Trading Partner specified in the message.
<b>Action</b>	Notify the Trading Partner specified in the message that their certificate is either invalid or expired.
<b>TNS.0003.3037W</b>	<b>Received a certificate issued by {0}, who is not on your list of trusted Certificate Authorities.</b>
<b>Explanation</b>	The Certificate Authority specified in the message is not on your list of trusted sources.
<b>Action</b>	You either can add this Certificate Authority to your list of trusted Certificate Authorities, or you can notify the trading partner that you do not trust their Certificate Authority.
<b>TNS.0003.3038E</b>	<b>Problem creating B2B account for partner (username={0}).</b>
<b>Explanation</b>	An account could not be created on the Integration Server for the partner.
<b>Action</b>	Create the account manually for the partner. The user name must match the partner's required external ID.
<b>TNS.0003.3050E</b>	<b>If {0} is supplied, {1} must also be supplied.</b>
<b>Explanation</b>	You must supply either both values or neither value.
<b>Action</b>	Supply both values or neither value.
<b>TNS.0003.3085W</b>	<b>The Trading Networks user does not have permission to change System properties. The certificate chain verifier is not correctly initialized. All incoming certificate chains will be trusted.</b>
<b>Explanation</b>	The watt.security.cert.wmChainVerifier.trustByDefault property might not be set correctly.
<b>Action</b>	Ask the Administrator to set the watt.security.cert.wmChainVerifier.trustByDefault property appropriately.

---

<b>TNS.0003.3102E</b>	<b>Either {0} or {1} must be supplied.</b>
<b>Explanation</b>	A value must be supplied for one of the two variables, but no value was supplied for either variable.
<b>Action</b>	Supply a value for one of the variables.
<b>TNS.0003.4001E</b>	<b>Could not delete field group.</b>
<b>Explanation</b>	An exception was thrown while deleting a profile field group.
<b>Action</b>	The exception was written to the error log. See the log for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4003E</b>	<b>Could not add partner profile for {0}.</b>
<b>Explanation</b>	An exception was thrown while saving a partner profile.
<b>Action</b>	The exception was written to the error log. See the log for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4005E</b>	<b>The partner specified (id={0}) has a {1} ID of {2}, but there is no matching IS user account.</b>
<b>Explanation</b>	Trading Networks could not find an Integration Server user account for this partner.
<b>Action</b>	Verify that the partner has a user account on the Integration Server and that the account name matches the partner's required external ID value.
<b>TNS.0003.4006E</b>	<b>Attempted to save an extended field value with an unknown field ID (id={0}).</b>
<b>Explanation</b>	Field with this ID doesn't exist. Trading Networks could not save the extended field for this ID.
<b>Action</b>	Specify a valid field ID.
<b>TNS.0003.4008E</b>	<b>Got null or empty extended profile fields</b>
<b>Explanation</b>	The "fields" input variable is required.
<b>Action</b>	Pass the extended fields you want to save in the "fields" variable.
<b>TNS.0003.4009E</b>	<b>Attempted to save an external ID that has an unknown type (type code={0}).</b>
<b>Explanation</b>	Trading Networks attempted to save an external ID for a partner, but the external ID is associated with an external ID type that has not been defined.
<b>Action</b>	To save a new type of external ID for a partner, you must first define the external ID type. To do so, use the <code>wm.tn.dictionary:addIDType</code> service.

<b>TNS.0003.4010E</b>	<b>ID Type {0} is not valid. Not found in the Trading Networks database.</b>
<b>Explanation</b>	ID Type provided is not recognized by Trading Networks.
<b>Action</b>	Supply a valid external ID type. Use the wm.tn.dictionary:addIDType service to define a new external ID type.
<b>TNS.0003.4011E</b>	<b>Attempted to save a contact that has an unknown type (type code={0}).</b>
<b>Explanation</b>	Trading Networks attempted to save a contact for a partner, but the contact is associated with a contact type that has not been defined.
<b>Action</b>	To save a new type of contact for a partner, you must first define the contact type. To do so, use the wm.tn.dictionary:addContactType service.
<b>TNS.0003.4012E</b>	<b>Cannot delete a standard field</b>
<b>Explanation</b>	Attempted to delete a standard profile field. You can only delete extended profile fields.
<b>Action</b>	No action required.
<b>TNS.0003.4014E</b>	<b>{0} not a valid Group ID. Must be greater than {1}.</b>
<b>Explanation</b>	Group ID provided is not a positive integer.
<b>Action</b>	Supply a valid group ID value. It should be positive integer.
<b>TNS.0003.4015E</b>	<b>Port must be a positive integer</b>
<b>Explanation</b>	When specifying a partner's host and port, the port value must be greater than zero.
<b>Action</b>	Supply a valid value that is greater than zero for the port number.
<b>TNS.0003.4016E</b>	<b>Could not decode bizdoc</b>
<b>Explanation</b>	Trading Networks created an internal BizDocEnvelope to validate the profile data, but could not decode the BizDocEnvelope.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0003.4017E</b>	<b>Could not add {0}. A {0} with an ID of {1} already exists.</b>
<b>Explanation</b>	While adding lookup type (Contact Type/ ID Type/ Binary Type), Trading Networks found that a similar lookup type with same ID already exists. Trading Networks did not add the lookup type.
<b>Action</b>	Save this type with a different ID.

---

<b>TNS.0003.4018E</b>	<b>A profile already exists for the host of this Trading Network. Turn off the SELF setting on the corporate component of the profile and save it again.</b>
<b>Explanation</b>	The Enterprise profile already exists.
<b>Action</b>	If you are programmatically saving profiles, set the Self? variable to false before attempting to save the profile. If you are using My webMethods to save profiles, contact Software AG Global Support.
<b>TNS.0003.4019E</b>	<b>Could not validate profile: received null bizdoc</b>
<b>Explanation</b>	Trading Networks should have created an internal BizDocEnvelope to validate profile data, but the BizDocEnvelope is null.
<b>Action</b>	Contact Software AG Global Support. Please have the server and error logs and the WmTN/config/properties.cnf file available.
<b>TNS.0003.4020E</b>	<b>No "{0}" element found in bizdoc</b>
<b>Explanation</b>	Trading Networks created an internal BizDocEnvelope to validate profile data, but the BizDocEnvelope did not contain the "errors" element.
<b>Action</b>	Contact Software AG Global Support. Please have the server and error logs and the WmTN/config/properties.cnf file available.
<b>TNS.0003.4021E</b>	<b>Cannot set extended fields.</b>
<b>Explanation</b>	An exception was thrown while saving extended fields to the database.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4024E</b>	<b>Cannot access profile store.</b>
<b>Explanation</b>	An exception was thrown while accessing the Profile store.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0003.4026E</b>	<b>You are using webMethods Trading Partners. To be able to add more partner profiles, please upgrade to webMethods Trading Networks.</b>
<b>Explanation</b>	When using webMethods Trading Partners, you are allowed to create only one profile other than your own.
<b>Action</b>	If you need to create additional partner profiles, upgrade to webMethods Trading Networks.

<b>TNS.0003.4027E</b>	<b>Could not retrieve {0} using {1}</b>
<b>Explanation</b>	Invalid id is provided. Trading Networks could not retrieve partner details using this ID.
<b>Action</b>	Supply a valid value.
<b>TNS.0003.4028E</b>	<b>An error occurred while retrieving company logos.</b>
<b>Explanation</b>	An exception was thrown while retrieving company logos.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4029E</b>	<b>Importing a profile for {0} (id={1}), which is marked as "My Enterprise", but it has different ID than the existing My Enterprise profile for this Trading Network. Cannot change the identity of the My Enterprise profile. Process terminated.</b>
<b>Explanation</b>	You attempted to import the Enterprise. However, the target Trading Networks system already has an Enterprise profile, which has a different ID than the one you are attempting to import. Trading Networks cannot import the Enterprise profile.
<b>Action</b>	Import Enterprise profile carefully only to those Trading Networks Servers where it's not already defined.
<b>TNS.0003.4030E</b>	<b>Could not get profile for user (username={0}).</b>
<b>Explanation</b>	An exception was thrown while retrieving a partner profile for a user.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4032E</b>	<b>Extended fields cannot have a column name.</b>
<b>Explanation</b>	Validation of profile fields failed. The column name on an extended profile field should be null.
<b>Action</b>	If you are programmatically creating extended fields, do not set the Column Name.
<b>TNS.0003.4033E</b>	<b>Extended fields cannot have a table name.</b>
<b>Explanation</b>	Validation of profile fields failed. The table name on an extended profile field should be null.
<b>Action</b>	If you are programmatically creating extended fields, do not set the Table Name.

---

<b>TNS.0003.4034E</b>	<b>Partner status can only be "Active" or "Inactive" when adding a new profile.</b>
<b>Explanation</b>	Invalid status provided for profile to be added.
<b>Action</b>	Supply a valid value for the Partner Status field.
<b>TNS.0003.4035E</b>	<b>Corporation is invalid: no partnerID.</b>
<b>Explanation</b>	Trading Networks attempted to update a partner profile, but the corporation component has no partner ID.
<b>Action</b>	Set the partnerID field to a valid value.
<b>TNS.0003.4036E</b>	<b>Attempted to save a binary object that has an unknown type (type code={0}).</b>
<b>Explanation</b>	The database does not have binary types defined.
<b>Action</b>	Populate your database with initial values by importing the file <IntegrationServer>/packages/WmTN/bin/init.xml, where <IntegrationServer> is the location where your server is installed.
<b>TNS.0003.4037E</b>	<b>Could not add Field Group {0}.</b>
<b>Explanation</b>	An exception was thrown while adding a profile field group.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4039E</b>	<b>Could not get {0} for partner (partnerID={1}).</b>
<b>Explanation</b>	An exception was thrown while retrieving protocol information for a partner.
<b>Action</b>	Verify whether the database connection is available. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4041E</b>	<b>Cannot delete the External ID, there has to be at least one external ID</b>
<b>Explanation</b>	Each partner must have a value for the required external ID type. The required external ID value is used for the user name of the partner's Integration Server user account.
<b>Action</b>	Do not attempt to delete the required external ID from a partner's profile.
<b>TNS.0003.4042E</b>	<b>The value for profile field {0} is not one of the valid values.</b>
<b>Explanation</b>	Invalid value provided for profile field.
<b>Action</b>	Supply a valid value.

<b>TNS.0003.4044E</b>	<b>Standard fields must have a column name.</b>
<b>Explanation</b>	Profile field Validation failed. The column name on a standard profile field is null.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0003.4045E</b>	<b>Could not update {0}.</b>
<b>Explanation</b>	An exception was thrown while updating a profile component.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4046E</b>	<b>A profile already exists in the database with the supplied PartnerID ({0}).</b>
<b>Explanation</b>	Trading Networks attempted to save a new profile with the same partnerID as an existing profile.
<b>Action</b>	Do not specify a value for the partnerID when creating a new profile. Trading Networks will generate a unique ID for you.
<b>TNS.0003.4047</b>	<b>{0} cannot be null.</b>
<b>Explanation</b>	Partner ID is required field while fetching the Profile and it should not be null.
<b>Action</b>	Supply Partner ID to fetch profile.
<b>TNS.0003.4048E</b>	<b>Could not get profile for partner (id={0})</b>
<b>Explanation</b>	An exception was thrown while retrieving a partner profile.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4049E</b>	<b>webMethods Trading Partners is restricted to the creation of one profile in addition to your own.</b>
<b>Explanation</b>	When using webMethods Trading Partners, you can create only one profile other than your own.
<b>Action</b>	If you need to create additional partner profiles, upgrade to webMethods Trading Networks.
<b>TNS.0003.4050E</b>	<b>Could not upgrade your profile. Please contact webMethods Customer Service.</b>
<b>Explanation</b>	An exception was thrown while upgrading your profile from webMethods for Partners to webMethods Trading Networks.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception. If necessary, contact Software AG Global Support.

---

<b>TNS.0003.4051E</b>	<b>At least 1 field has been defined for this group. Cannot delete.</b>
<b>Explanation</b>	Found at least one field still associated to group. Unable to delete this group.
<b>Action</b>	To delete this field group, you must first delete all extended profile fields in the group, or assign them to other groups.
<b>TNS.0003.4053E</b>	<b>Could not delete {0} ({1}={2}).</b>
<b>Explanation</b>	An exception was thrown while deleting a profile component.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4054E</b>	<b>Cannot set valid values for a standard field</b>
<b>Explanation</b>	You cannot define a list of valid values for standard fields.
<b>Action</b>	Do not attempt to define a list of valid values for a standard field. Valid values are applicable for extended fields.
<b>TNS.0003.4056E</b>	<b>Errors encountered validating profile/profile fields</b>
<b>Explanation</b>	A list of one or more validation errors follows this message after invoking wm.tn:submit.
<b>Action</b>	Take appropriate action to resolve the errors.
<b>TNS.0003.4058E</b>	<b>Another partner profile with the name "{0}" already exists. Cannot have duplicate partner names. Please enter a different name.</b>
<b>Explanation</b>	You are attempting to create a profile; however, a profile with the Corporation Name and User Name that you specified already exists in Trading Networks.
<b>Action</b>	Supply a different Corporation Name and/or Unit Name.
<b>TNS.0003.4060E</b>	<b>You must add a profile for your enterprise before you can upgrade to webMethods Trading Networks. Please create a profile for your enterprise.</b>
<b>Explanation</b>	You have not defined the Enterprise profile. The Enterprise profile must exist before you can upgrade Trading Networks.
<b>Action</b>	Create the Enterprise profile.
<b>TNS.0003.4062E</b>	<b>Cannot undelete a standard field</b>
<b>Explanation</b>	Standard fields cannot be deleted or undeleted.
<b>Action</b>	Do not attempt to delete or undelete a standard field.

<b>TNS.0003.4064E</b>	<b>{0}, no change made on server</b>
<b>Explanation</b>	Trading Networks encountered an error while saving partner profile information. See the error message for details.
<b>Action</b>	Take appropriate action to resolve the problem described in the error message.
<b>TNS.0003.4065E</b>	<b>An error was encountered deleting a partner's profile (partnerID={0}).</b>
<b>Explanation</b>	An exception was thrown while deleting a partner profile.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4066E</b>	<b>Could not get host profile.</b>
<b>Explanation</b>	An exception was thrown while retrieving the Enterprise profile.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4068E</b>	<b>{0} is required.</b>
<b>Explanation</b>	No value was supplied for a required input variable.
<b>Action</b>	Supply the required value.
<b>TNS.0003.4069E</b>	<b>Standard fields must have a table name.</b>
<b>Explanation</b>	Trading Networks encountered an invalid field definition in the Trading Networks database.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0003.4072E</b>	<b>Error initializing ProfileStore</b>
<b>Explanation</b>	Encountered error while initializing Profile Store.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0003.4073E</b>	<b>Could not set binary object for partner (id={0}).</b>
<b>Explanation</b>	An exception was thrown while saving binary data to the Trading Networks database.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

---

<b>TNS.0003.4075E</b>	<b>Could not get Extended Field template (group={0}).</b>
<b>Explanation</b>	An exception was thrown while creating a new extended field.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0003.4076E</b>	<b>Invalid group specified.</b>
<b>Explanation</b>	The group that was specified is not a valid group.
<b>Action</b>	Use the <code>wm.tn.dictionary:getFieldGroups</code> service to retrieve a list of valid groups.
<b>TNS.0003.4077E</b>	<b>{0} must be specified for partner {1}</b>
<b>Explanation</b>	Profile validation failed! Required data is missing from a partner profile.
<b>Action</b>	Supply a value for the required fields.
<b>TNS.0003.4078E</b>	<b>Datatype cannot be null.</b>
<b>Explanation</b>	Found Datatype parameter null while setting it to profile.
<b>Action</b>	Supply a valid data type.
<b>TNS.0003.4079E</b>	<b>Your webmethods Trading Networks server is restricted to the creation of {0} profiles in addition to your own.</b>
<b>Explanation</b>	Your Trading Networks Server is restricted to the creation of the number of profiles specified in the message.
<b>Action</b>	If you need to add more profiles, contact Software AG Global Support to upgrade your server.
<b>TNS.0003.4080E</b>	<b>Attempted to set the datatype of a field to an unrecognized value: {0}.</b>
<b>Explanation</b>	Provided datatype is not recognized by Trading Networks.
<b>Action</b>	Supply a valid data type.
<b>TNS.0003.4082E</b>	<b>Binary type not found in the Trading Networks database: {0}.</b>
<b>Explanation</b>	Trading Networks attempted to set the value of a binary object, but the type does not exist in the database.
<b>Action</b>	Supply a valid <code>binaryTypeDescription</code> or <code>binaryTypeCode</code> . If you have specified a valid binary type and the problem persists, import the <code>init.xml</code> file from the <code>&lt;IntegrationServer&gt;packages/WmTN/bin</code> directory, where <code>&lt;IntegrationServer&gt;</code> is the location where you installed your server.

<b>TNS.0003.4083E</b>	<b>Could not change {0} Type {1}.</b>
<b>Explanation</b>	An exception was thrown while attempting to update an external ID type or contact type.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4084E</b>	<b>Standard fields cannot have a set of extended valid values</b>
<b>Explanation</b>	Trading Networks encountered an invalid field definition in the Trading Networks database.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0003.4085E</b>	<b>The specified delivery data (id={0}) does not exist in the database. Cannot delete.</b>
<b>Explanation</b>	Trading Networks was unable to perform the specified database action because the Destination data does not exist.
<b>Action</b>	Contact Software AG Global Support. Have the server and error logs and the WmTN/config/properties.cnf file available.
<b>TNS.0003.4086E</b>	<b>Standard fields cannot have an extended default value</b>
<b>Explanation</b>	Trading Networks encountered an invalid field definition in the Trading Networks database.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0003.4087E</b>	<b>The value for {0} must be a String.</b>
<b>Explanation</b>	Found unexpected non-String value when datatype is String, validation failed.
<b>Action</b>	Supply a String value for the field.
<b>TNS.0003.4088E</b>	<b>A {0} ID of {1} already exists in the database. External IDs must be unique.</b>
<b>Explanation</b>	Cannot have two external IDs of the same external ID type that have the same value.
<b>Action</b>	Supply another value for this external ID.
<b>TNS.0003.4089E</b>	<b>Could not get internal ID for partner (id={0}, typeCode={1}, typeDesc={2}).</b>
<b>Explanation</b>	An exception was thrown while retrieving the internal partnerID.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

---

<b>TNS.0003.4090E</b>	<b>Fields must have a datatype</b>
<b>Explanation</b>	Trading Networks encountered an invalid field definition in the Trading Networks database.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0003.4091E</b>	<b>Could not get profile summaries.</b>
<b>Explanation</b>	An exception was thrown while retrieving profile summaries.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4092E</b>	<b>{0} cannot be null. {1} not {2}.</b>
<b>Explanation</b>	Trading Networks did not add or update the changes because a required value is missing.
<b>Action</b>	Supply the required value.
<b>TNS.0003.4093E</b>	<b>{0} must be equal or greater than {1}</b>
<b>Explanation</b>	Numeric field validation failed as supplied value found lesser than limit value, should be greater or equal to limit value.
<b>Action</b>	Supply a valid value.
<b>TNS.0003.4094E</b>	<b>You are already using webMethods Trading Networks. No upgrade is necessary.</b>
<b>Explanation</b>	Attempted to upgrade from webMethods for Partners to webMethods Trading Networks, but you are already using webMethods Trading Networks.
<b>Action</b>	No action required.
<b>TNS.0003.4096E</b>	<b>Could not get {0}.</b>
<b>Explanation</b>	An exception was thrown while retrieving a profile component.
<b>Action</b>	An exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4099E</b>	<b>Status was not changed to {0} because the profile has the following errors {1}</b>
<b>Explanation</b>	The profile has issues that must be resolved before the status can be changed.
<b>Action</b>	Take appropriate action to resolve the problem described in the errors.

<b>TNS.0003.4100E</b>	<b>Cannot set Column Name for an extended field</b>
<b>Explanation</b>	It is not valid for an extended profile field to have a value for Column Name.
<b>Action</b>	Do not attempt to set a value for Column Name for an extended profile field.
<b>TNS.0003.4102E</b>	<b>Cannot set Table Name for an extended field</b>
<b>Explanation</b>	It is not valid for an extended profile field to have a value for Table Name.
<b>Action</b>	Do not attempt to set a value for Table Name for an extended profile field.
<b>TNS.0003.4105E</b>	<b>Could not add {0} Type {1}.</b>
<b>Explanation</b>	An exception was thrown while attempting to create an IDType or ContactType.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4106E</b>	<b>Could not get profile summary (partnerID={0}).</b>
<b>Explanation</b>	An exception was thrown while attempting to retrieve a profile summary.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4107E</b>	<b>An error occurred while retrieving polling frequencies.</b>
<b>Explanation</b>	An exception was thrown while retrieving a partner's polling frequency.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4108E</b>	<b>Could not delete External Partner ID (internal PartnerID={0}).</b>
<b>Explanation</b>	An exception was thrown while deleting a partner's external ID.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4109E</b>	<b>Got null profile field metadata for extended field at index {0}</b>
<b>Explanation</b>	Required internal data is missing.
<b>Action</b>	Contact Software AG Global Support.

---

<b>TNS.0003.4110E</b>	<b>Could not undelete profile for partner (id={0}).</b>
<b>Explanation</b>	An exception was thrown while undeleting a partner profile.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4113E</b>	<b>Attempted to save a field definition for an unknown group (group id={0}).</b>
<b>Explanation</b>	The specified field group does not exist and is not valid.
<b>Action</b>	Supply a valid field group. If you are using the Trading Networks Console to create an extended field, contact Software AG Global Support.
<b>TNS.0003.4114E</b>	<b>Could not get profile summary (username={0}).</b>
<b>Explanation</b>	An exception was thrown while retrieving a profile summary.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4115E</b>	<b>Profile has errors. Saved with a status of {0}.</b>
<b>Explanation</b>	Validation error found for the provided profile, saving with status as inactive.
<b>Action</b>	Take appropriate action to resolve the errors listed below this message.
<b>TNS.0003.4116E</b>	<b>Could not add external ID data for partner (id={1}).</b>
<b>Explanation</b>	Encountered an Exception while saving a profile component.
<b>Action</b>	See the Exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4117E</b>	<b>webMethods Trading Networks requires a special license key. Please contact webMethods to get a Trading Networks key. Until you do so, you will be limited to the creation of one profile in addition to your own.</b>
<b>Explanation</b>	You currently have a webMethods for Partners license key, which allows you to create only a single partner profile.
<b>Action</b>	If you need to create additional partner profiles, upgrade to webMethods Trading Networks.

<b>TNS.0003.4118E</b>	<b>Profile status may only be changed to {0} or {1}.</b>
<b>Explanation</b>	Attempted to change the profile status to an invalid status.
<b>Action</b>	Supply a valid value.
<b>TNS.0003.4120E</b>	<b>Could not change partner's status.</b>
<b>Explanation</b>	An exception was thrown while updating the status of a partner profile.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4121E</b>	<b>{0} {1} delivery data already exists in the database for this partner.</b>
<b>Explanation</b>	You attempted to add a delivery method for a partner that is already defined for the partner. You cannot have two instances of the same delivery method for a partner.
<b>Action</b>	If the existing delivery method contains the information you want, no action is required. Otherwise, you can update the information for the existing delivery method.
<b>TNS.0003.4122E</b>	<b>Extended fields must have a name.</b>
<b>Explanation</b>	You did not specify a name for the extended profile field.
<b>Action</b>	Supply the required value.
<b>TNS.0003.4123E</b>	<b>Problem initializing Profile services.</b>
<b>Explanation</b>	An exception was thrown during initialization.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4124E</b>	<b>Cannot set default value for a standard field.</b>
<b>Explanation</b>	You cannot define a default value for a standard profile field.
<b>Action</b>	Do not attempt to define a default value for a standard profile field.
<b>TNS.0003.4125E</b>	<b>Could not retrieve extended fields.</b>
<b>Explanation</b>	An exception was thrown while retrieving extended fields for a partner.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

---

<b>TNS.0003.4126E</b>	<b>Standard fields cannot be marked as deleted</b>
<b>Explanation</b>	You cannot delete a standard profile field.
<b>Action</b>	Do not attempt to delete a standard profile field.
<b>TNS.0003.4129E</b>	<b>Following errors occurred during updating profile</b>
<b>Explanation</b>	A list of one or more errors follows this message.
<b>Action</b>	Take appropriate action to resolve the problems described in the errors.
<b>TNS.0003.4130E</b>	<b>Cannot delete preferred delivery method</b>
<b>Explanation</b>	The delivery method you tried to delete is the preferred delivery method for the partner.
<b>Action</b>	Before you can delete this delivery method, choose another delivery method to be "preferred."
<b>TNS.0003.4131E</b>	<b>Could not delete {0} Type {1}.</b>
<b>Explanation</b>	An exception was thrown while deleting profile data.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4132E</b>	<b>Could not update corporation.</b>
<b>Explanation</b>	An exception was thrown while updating the Corporate component of a partner profile.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4133E</b>	<b>Could not update addresses.</b>
<b>Explanation</b>	An exception was thrown while updating one or more addresses on a partner profile.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4136E</b>	<b>Could not delete connection ({1}={2}).</b>
<b>Explanation</b>	An exception was thrown while deleting a delivery method from a partner profile.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

<b>TNS.0003.4138E</b>	<b>Could not update external IDs.</b>
<b>Explanation</b>	An exception was thrown while updating one or more external IDs in a partner profile.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4141E</b>	<b>Could not get binary object for partner (partnerID={1}).</b>
<b>Explanation</b>	An exception was thrown while retrieving a binary object for a partner profile.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4142E</b>	<b>"extID" is required.</b>
<b>Explanation</b>	You attempted to invoke a service that requires a value for the extID input variable, but no value was supplied.
<b>Action</b>	Supply the required value.
<b>TNS.0003.4143E</b>	<b>Either idTypeCode or idTypeDesc must be supplied (idTypeCode={0}, idTypeDesc={1}).</b>
<b>Explanation</b>	You invoked a service without providing a required input variable to identify the external ID type.
<b>Action</b>	Supply one of the required values.
<b>TNS.0003.4144E</b>	<b>partnerID is required.</b>
<b>Explanation</b>	You invoked a service without providing a required input variable to identify the partner.
<b>Action</b>	Supply the required value.
<b>TNS.0003.4145E</b>	<b>Could not get external ID for partner (partnerID={0}).</b>
<b>Explanation</b>	An exception was thrown while retrieving an external ID for a partner profile.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4146E</b>	<b>Error encountered updating binary object in the database (partnerID={0}).</b>
<b>Explanation</b>	An exception was thrown while updating a binary object for a partner profile.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

---

<b>TNS.0003.4147E</b>	<b>{0} must be supplied.</b>
<b>Explanation</b>	You called a Java method without supplying a value for a required field (<fieldName>).
<b>Action</b>	Supply the required value.
<b>TNS.0003.4148E</b>	<b>A status of {0} is not one of the permitted values.</b>
<b>Explanation</b>	Attempted to set the status to an invalid value.
<b>Action</b>	Supply a valid value.
<b>TNS.0003.4149E</b>	<b>Error encountered changing partner status.</b>
<b>Explanation</b>	An exception was thrown while updating the status of a partner profile.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4151E</b>	<b>A profile is required.</b>
<b>Explanation</b>	While adding profile to the Data store, profile found to be null.
<b>Action</b>	Supply the valid profile data.
<b>TNS.0003.4152E</b>	<b>Error encountered adding profile to the database.</b>
<b>Explanation</b>	An exception was thrown while adding a partner profile.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4153E</b>	<b>Error encountered adding contacts to the database.</b>
<b>Explanation</b>	An exception was thrown while adding one or more contacts to a partner profile.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4155E</b>	<b>Error encountered adding destinations to the database.</b>
<b>Explanation</b>	An exception was thrown while adding one or more delivery methods (destinations) to a partner profile.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

<b>TNS.0003.4156E</b>	<b>Error encountered adding IDs to the database.</b>
<b>Explanation</b>	An exception was thrown while adding one or more external IDs to a partner profile.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4157E</b>	<b>Error encountered adding addresses to the database.</b>
<b>Explanation</b>	An exception was thrown while adding one or more addresses to a partner profile.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4158E</b>	<b>Error encountered adding binary objects to the database.</b>
<b>Explanation</b>	An exception was thrown while adding one or more binary objects to a partner profile.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4160E</b>	<b>{0} cannot be null.</b>
<b>Explanation</b>	When attempting to delete a profile-related asset from the Profile store, required asset ID was not provided.
<b>Action</b>	Supply the required asset ID.
<b>TNS.0003.4161E</b>	<b>Error encountered deleting profile from the database.</b>
<b>Explanation</b>	An exception was thrown while deleting a partner profile.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4162E</b>	<b>Error encountered undeleting profile from the database.</b>
<b>Explanation</b>	An exception was thrown while undeleting a partner profile.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4163E</b>	<b>Error encountered deleting contact (contactID={0}, partnerID={1}).</b>
<b>Explanation</b>	An exception was thrown while deleting a contact from a partner profile.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

---

<b>TNS.0003.4164E</b>	<b>Error encountered deleting address (addressID={0}, partnerID={1}).</b>
<b>Explanation</b>	An exception was thrown while deleting an address from a partner profile.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4165E</b>	<b>Error encountered deleting destination (destID={0}).</b>
<b>Explanation</b>	An exception was thrown while deleting a delivery method (destination) from a partner profile.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4166E</b>	<b>Error encountered deleting external id (id={0}).</b>
<b>Explanation</b>	An exception was thrown while deleting an external ID from a partner profile.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4167E</b>	<b>Error encountered retrieving extended fields.</b>
<b>Explanation</b>	An exception was thrown while retrieving extended fields for a partner.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4168E</b>	<b>Error encountered adding extended field {0} to the database (partnerID={1}).</b>
<b>Explanation</b>	An exception was thrown while adding an extended profile field for a partner.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4170E</b>	<b>Error encountered retrieving contact {0} (partnerID={1}).</b>
<b>Explanation</b>	Encountered an exception while retrieving a contact for a partner.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4171E</b>	<b>Error encountered retrieving binary type {0} (partnerID={1}).</b>
<b>Explanation</b>	An exception was thrown while retrieving a binary object for a partner.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

<b>TNS.0003.4172E</b>	<b>Invalid binary type: {0}.</b>
<b>Explanation</b>	The supplied binary type is not recognized as a valid binary type. It does not match any existing binary type.
<b>Action</b>	Supply a valid binary type value.
<b>TNS.0003.4173E</b>	<b>A connection was requested for an unknown partner (partnerID={0}).</b>
<b>Explanation</b>	Attempted to establish a connection to a partner's server, but the supplied partnerID was invalid.
<b>Action</b>	Supply a valid partner ID.
<b>TNS.0003.4174E</b>	<b>Delivery method is {0}. Can only create contexts for HTTP or HTTPS destinations.</b>
<b>Explanation</b>	A webMethods context can only be established when using HTTP or HTTPS.
<b>Action</b>	If you want to connect to a partner's server with a different protocol (e.g., FTP or SMTP) use the appropriate service in the WmPublic package or one of the delivery services in the wm.tn.transport folder.
<b>TNS.0003.4175E</b>	<b>Error encountered connecting to partner's server.</b>
<b>Explanation</b>	An exception was thrown while connecting to a partner's server.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4181E</b>	<b>constant must start with FLD_[TBL]_</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0003.4182E</b>	<b>bad constant results in non or multiple fields</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0003.4184E</b>	<b>RetryFactor cannot be zero</b>
<b>Explanation</b>	Supplied RetryFactor is unexpectedly lower than 1, RetryFactor should be greater than or equal to 1.
<b>Action</b>	Supply a valid value for RetryFactor. It should be greater than or equal to 1.

---

<b>TNS.0003.4187E</b>	<b>External Field: {0} has errors. Error = {1}</b>
<b>Explanation</b>	See the errors listed in the message.
<b>Action</b>	Take appropriate action to resolve the problems described in the errors.
<b>TNS.0003.4188E</b>	<b>Is a required External Field</b>
<b>Explanation</b>	No data was supplied for a required extended profile field.
<b>Action</b>	Supply a value for this field.
<b>TNS.0003.4189E</b>	<b>Field value must be of data type java.lang.String</b>
<b>Explanation</b>	Data type for the extended profile field is String, value must be a String.
<b>Action</b>	Supply a String value.
<b>TNS.0003.4190E</b>	<b>Invalid value selected</b>
<b>Explanation</b>	Supplied value for extended profile field found to be invalid.
<b>Action</b>	Supply a valid value.
<b>TNS.0003.4192E</b>	<b>Could not retrieve ID Types from database</b>
<b>Explanation</b>	An exception was thrown while retrieving external ID types.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4193E</b>	<b>Could not retrieve IDType Descriptions from database</b>
<b>Explanation</b>	An exception was thrown while retrieving external ID type descriptions.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4194E</b>	<b>A database error occurred while adding an ID Type.</b>
<b>Explanation</b>	An exception was thrown while adding an external ID type.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

<b>TNS.0003.4195E</b>	<b>A database error occurred while changing an ID Type.</b>
<b>Explanation</b>	An exception was thrown while updating an external ID type.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4196E</b>	<b>A database error occurred while deleting an External ID Type.</b>
<b>Explanation</b>	An exception was thrown while deleting an external ID type.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4197E</b>	<b>Could not retrieve Contact Types from database</b>
<b>Explanation</b>	An exception was thrown while retrieving contact types.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4198E</b>	<b>A database error occurred while adding a Contact Type.</b>
<b>Explanation</b>	An exception was thrown while adding a contact type.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4199E</b>	<b>A database error occurred while changing a Contact Type.</b>
<b>Explanation</b>	An exception was thrown while updating a contact type.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4200E</b>	<b>A database error occurred while deleting a Contact Type.</b>
<b>Explanation</b>	An exception was thrown while deleting a contact type.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4201E</b>	<b>Could not retrieve Binary Types from database</b>
<b>Explanation</b>	An exception was thrown while retrieving binary types.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

---

<b>TNS.0003.4202E</b>	<b>Could not retrieve Field Groups from database</b>
<b>Explanation</b>	An exception was thrown while retrieving field groups.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4203E</b>	<b>A database error occurred while adding a Field Group.</b>
<b>Explanation</b>	An exception was thrown while adding a field group.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4204E</b>	<b>A database error occurred while changing a Field Group.</b>
<b>Explanation</b>	An exception was thrown while updating a field group.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4205E</b>	<b>A database error occurred while deleting a Field Group.</b>
<b>Explanation</b>	An exception was thrown while deleting a field group.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4206E</b>	<b>Error initializing Profile Dictionary.</b>
<b>Explanation</b>	An exception was thrown during initialization.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0003.4207E</b>	<b>pfmd cannot be null.</b>
<b>Explanation</b>	You did not supply a required value.
<b>Action</b>	Supply the required data.
<b>TNS.0003.4208E</b>	<b>A problem was encountered updating the field defintion.</b>
<b>Explanation</b>	An exception was thrown while updating a field definition.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

<b>TNS.0003.4209E</b>	<b>Cannot add a standard field definition. Set Extended to true before saving this definition.</b>
<b>Explanation</b>	Attempted to add a standard profile field. You cannot add standard profile fields.
<b>Action</b>	Add the profile field as an extended profile field.
<b>TNS.0003.4210E</b>	<b>A problem was encountered adding the field definition.</b>
<b>Explanation</b>	An exception was thrown while adding a field definition.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4211E</b>	<b>Error retrieving profile</b>
<b>Explanation</b>	Encountered an exception while retrieving a partner profile.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4212E</b>	<b>Could not retrieve profile from database using external ID</b>
<b>Explanation</b>	An exception was thrown while retrieving a partner profile.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4213E</b>	<b>Could not retrieve Profile Summaries from database</b>
<b>Explanation</b>	An exception was thrown while retrieving a profile summary.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4216E</b>	<b>Could not retrieve Custom Fields from database</b>
<b>Explanation</b>	An exception was thrown while retrieving extended profile fields.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4218E</b>	<b>Could not retrieve internal ID from database using PartnerIDID ({0}).</b>
<b>Explanation</b>	An exception was thrown while retrieving a partner profile ID.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

---

<b>TNS.0003.4219E</b>	<b>Could not retrieve internal ID from database using DestinationID ({0}).</b>
<b>Explanation</b>	An exception was thrown while retrieving a partner profile ID.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4220E</b>	<b>Error retrieving {0} external ID for {1}.</b>
<b>Explanation</b>	An exception was thrown while retrieving the external ID for a partner.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4221E</b>	<b>Could not retrieve IDType from database using PartnerIDID ({0}).</b>
<b>Explanation</b>	An exception was thrown while retrieving an external ID type.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4222E</b>	<b>Could not update profile.</b>
<b>Explanation</b>	An exception was thrown while updating a profile that has been marked deleted.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4223E</b>	<b>Corporation can not be null.</b>
<b>Explanation</b>	Required Corporate information was not supplied.
<b>Action</b>	Supply the required Corporate information.
<b>TNS.0003.4224E</b>	<b>Could not update Corporation.</b>
<b>Explanation</b>	An exception was thrown while updating a partner profile.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4225E</b>	<b>Contacts can not be null.</b>
<b>Explanation</b>	Required Contact information was not supplied.
<b>Action</b>	Supply the required data.

<b>TNS.0003.4226E</b>	<b>At least one Contact is required.</b>
<b>Explanation</b>	The supplied Vector must contain at least one contact.
<b>Action</b>	Supply the required data.
<b>TNS.0003.4227E</b>	<b>Could not update Contacts.</b>
<b>Explanation</b>	An exception was thrown while updating a partner's contact information.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4228E</b>	<b>Address can not be null.</b>
<b>Explanation</b>	Required address information was not supplied.
<b>Action</b>	Supply the required data.
<b>TNS.0003.4229E</b>	<b>At least one Address is required.</b>
<b>Explanation</b>	The supplied vector must contain at least one address.
<b>Action</b>	Supply the required data.
<b>TNS.0003.4230E</b>	<b>Could not update Addresses.</b>
<b>Explanation</b>	An exception was thrown while updating a partner's address information.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4231E</b>	<b>Destinations can not be null.</b>
<b>Explanation</b>	Required delivery method (destination) information was not supplied.
<b>Action</b>	Supply the required data.
<b>TNS.0003.4232E</b>	<b>At least one Destination is required.</b>
<b>Explanation</b>	The supplied vector must contain at least one delivery method (destination).
<b>Action</b>	Supply the required data.
<b>TNS.0003.4233E</b>	<b>Could not update Destinations.</b>
<b>Explanation</b>	An exception was thrown while updating a partner's delivery method (destination) information.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

---

<b>TNS.0003.4235E</b>	<b>At least one ID is required.</b>
<b>Explanation</b>	The supplied vector must contain at least one external ID.
<b>Action</b>	Supply the required data.
<b>TNS.0003.4236E</b>	<b>Could not update IDs.</b>
<b>Explanation</b>	An exception was thrown while updating a partner's external ID information.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4237E</b>	<b>A vector of Contacts is required</b>
<b>Explanation</b>	The first argument to ProfileStore.addContacts is null.
<b>Action</b>	Supply the required data.
<b>TNS.0003.4238E</b>	<b>A vector of Destinations is required</b>
<b>Explanation</b>	The first argument to ProfileStore.addDestinations is null.
<b>Action</b>	Supply the required data.
<b>TNS.0003.4239E</b>	<b>A vector of IDs is required</b>
<b>Explanation</b>	The first argument to ProfileStore.addIDs is null.
<b>Action</b>	Supply the required data.
<b>TNS.0003.4240E</b>	<b>A vector of Addresses is required</b>
<b>Explanation</b>	The first argument to ProfileStore.addAddresses is null.
<b>Action</b>	Supply the required data.
<b>TNS.0003.4242E</b>	<b>"addresses" is empty. At least one Address must be supplied.</b>
<b>Explanation</b>	No address was supplied.
<b>Action</b>	Supply the required value.
<b>TNS.0003.4243E</b>	<b>"connections" is empty. At least one Destination must be supplied.</b>
<b>Explanation</b>	No delivery method (destination) was supplied.
<b>Action</b>	Supply the required value.

<b>TNS.0003.4244E</b>	<b>Could not validate profile extended fields: received null bizdoc</b>
<b>Explanation</b>	Internal error occurred during profile validation.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0003.4245E</b>	<b>No extended fields found in bizdoc</b>
<b>Explanation</b>	Internal error occurred during profile validation.
<b>Action</b>	This error can be safely ignored. If it persists, contact Software AG Global Support.
<b>TNS.0003.4246E</b>	<b>Could not validate profile standard fields: received null bizdoc</b>
<b>Explanation</b>	Internal error occurred during profile validation.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0003.4247E</b>	<b>No standard fields found in bizdoc</b>
<b>Explanation</b>	Internal error occurred during profile validation.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0003.4252E</b>	<b>Attempted to import extended field "{0}" for partner ID {1}, but this partner does not exist on your Trading Networks system.</b>
<b>Explanation</b>	Attempted to import extended field for a partner, but this partner does not exist on your Trading Networks.
<b>Action</b>	You must import the partner's profile before you can import extended fields for the partner.
<b>TNS.0003.4253E</b>	<b>Attempted to import extended field "{0}" that has an extended profile field ID of {1}, but this extended field is not defined on your Trading Networks system.</b>
<b>Explanation</b>	Cannot import the value of the extended profile field because there is no definition for the extended field.
<b>Action</b>	You must import the extended field definitions before you can import extended field values.
<b>TNS.0003.4254E</b>	<b>Error encountered invoking wm.tn.profile:addProfile {0}.</b>
<b>Explanation</b>	An exception was thrown while saving a new partner profile.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.

---

<b>TNS.0003.4257E</b>	<b>Error encountered refreshing ID cache.</b>
<b>Explanation</b>	An exception was thrown while refreshing an internal cache.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4258E</b>	<b>Could not get external IDs for partner (partnerID={0}).</b>
<b>Explanation</b>	An exception was thrown while retrieving external IDs.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4259E</b>	<b>At least one ID must be specified for partner {0}.</b>
<b>Explanation</b>	Because the value of the required external ID type is used as the user name for an Integration Server user account, it must be specified.
<b>Action</b>	Specify the required external ID.
<b>TNS.0003.4260E</b>	<b>Could not retrieve Profile Groups from database.</b>
<b>Explanation</b>	Encountered a SQLException while retrieving profile group information from the database.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4262E</b>	<b>profileGroupName can not be null or empty.</b>
<b>Explanation</b>	Trading Networks cannot accept null or an empty string for the profile group name.
<b>Action</b>	Specify a non-null a profile group name.
<b>TNS.0003.4263E</b>	<b>profileGroupName {0} already exists in database.</b>
<b>Explanation</b>	Trading Networks cannot accept a duplicate profile group name.
<b>Action</b>	Specify a unique profile group name.
<b>TNS.0003.4264E</b>	<b>A database error occurred while adding Profile Group {0}.</b>
<b>Explanation</b>	Encountered a SQLException while adding the new profile group.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

<b>TNS.0003.4265E</b>	<b>A database error occurred while changing Profile Group {0}.</b>
<b>Explanation</b>	Encountered a SQLException while changing the profile group name from its old name to a new name.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4266E</b>	<b>A database error occurred while deleting Profile Group {0}.</b>
<b>Explanation</b>	Encountered a SQLException while deleting the profile group from the database.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4267E</b>	<b>A database error occurred while querying profile information.</b>
<b>Explanation</b>	Encountered a SQLException while executing a profile query.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4275E</b>	<b>Error encountered invoking service {0}</b>
<b>Explanation</b>	Encountered an exception while invoking the specified service.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4276E</b>	<b>{0} can not be null or a 0-length array.</b>
<b>Explanation</b>	The input signature profileGroupIds should be a non-null array.
<b>Action</b>	Specify non-null values for the profileGroupIds input.
<b>TNS.0003.4281E</b>	<b>Attempted to import security data for partner ID {0}, but this partner does not exist on your Trading Networks system.</b>
<b>Explanation</b>	You attempted to import a trading partner's security data without first importing this trading partner's profile.
<b>Action</b>	Import the trading partner's profile before you attempt to import the security data for this trading partner.
<b>TNS.0003.4282E</b>	<b>No {0} {1} delivery data exists in the database for this partner. Cannot update.</b>
<b>Explanation</b>	The profile update operation cannot be completed because the delivery protocol data is not available.
<b>Action</b>	Provide the delivery protocol details.

---

<b>TNS.0003.4283E</b>	<b>Could not add contact data for partner (id="{0}").</b>
<b>Explanation</b>	Encountered an exception while invoking wm.tn.profile:addContacts. The operation cannot be completed.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4284E</b>	<b>Could not add address data for partner (id="{0}").</b>
<b>Explanation</b>	Encountered an exception while invoking wm.tn.profile:addAddresses. The operation cannot be completed.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4285E</b>	<b>Could not add delivery data for partner (id="{0}").</b>
<b>Explanation</b>	Encountered an exception while invoking wm.tn.profile:addConnections. The operation cannot be completed.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4287E</b>	<b>Could not delete profile group {0}, it is still in use.</b>
<b>Explanation</b>	The delete operation cannot be completed because the profile group is in use.
<b>Action</b>	Check the trading partner profiles to make sure that no partner belongs to the group you are attempting to delete.
<b>TNS.0003.4289E</b>	<b>Database error in adding partner {0} to profile groups. Import operation aborted.</b>
<b>Explanation</b>	Trading Networks encountered a problem with its database. There is a problem in the database or database driver.
<b>Action</b>	Use the JDBC Pools page on the Integration Server Administrator to ensure that the Integration Server can connect to the Trading Networks database. Correct all connection problems. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4290E</b>	<b>Cannot import partner profile(s) without My Enterprise profile.</b>
<b>Explanation</b>	You are attempting to import one or more partner profiles; however, the target Trading Networks server does not have an Enterprise profile.
<b>Action</b>	Create an Enterprise profile on the target server. Then, import the partner profiles.

<b>TNS.0003.4291E</b>	<b>SQLException encountered in ProfileStore.addPartnerCertificate().</b>
<b>Explanation</b>	Trading Networks encountered a problem with its database. There is a problem in the database or database driver.
<b>Action</b>	Use the JDBC Pools page on the Integration Server Administrator to ensure that the Integration Server can connect to the Trading Networks database. Correct all connection problems. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4292E</b>	<b>EXMLException encountered in ProfileStore.addPartnerCertificate().</b>
<b>Explanation</b>	Trading Networks encountered a problem when attempting to save a certificate for a partner.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4293E</b>	<b>SQLException encountered in ProfileStore.getPartnerIDForCertificate().</b>
<b>Explanation</b>	Trading Networks encountered a problem with its database. There is a problem in the database or database driver.
<b>Action</b>	Use the JDBC Pools page on the Integration Server Administrator to ensure that the Integration Server can connect to the Trading Networks database. Correct all connection problems. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4294E</b>	<b>EXMLException encountered in ProfileStore.getPartnerIDForCertificate().</b>
<b>Explanation</b>	Trading Networks encountered a problem when attempting to retrieve a certificate for a partner.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4295E</b>	<b>Cannot deliver to My Enterprise. The supplied partnerID ({0}) is the partnerID of the My Enterprise profile. Please supply a different partnerID.</b>
<b>Explanation</b>	The document receiver is the Enterprise profile, which indicates Trading Networks is to deliver the document to itself. This is not valid; Trading Networks cannot deliver a document to itself.
<b>Action</b>	Either change the receiver to specify a trading partner, or do not attempt to deliver this document.

<b>TNS.0003.4296E</b>	<b>A deleted partner profile with the name "{0}" already exists. Cannot have duplicate partner names. Please enter a different name.</b>
<b>Explanation</b>	You attempted to create a profile. However, the Corporation Name and Unit Name you specify will make the profile a duplicate of a profile that was previously deleted. Although a profile is deleted, Trading Networks continues to maintain information about it in its database. As a result, you cannot create another profile using the same Corporation Name and Unit Name.
<b>Action</b>	If you want to reinstate the deleted profile, use the <code>wm.tn.profile:undeleteProfile</code> service. Otherwise, enter a different Corporation Name and Unit Name when creating a profile.
<b>TNS.0003.4297E</b>	<b>Importing a profile for {0} (id={1}), which is marked as "My Enterprise". A "My Enterprise" profile already exists for this Trading Network. If you want to update it, use the Force option. Process terminated.</b>
<b>Explanation</b>	You attempted to import an Enterprise profile into a Trading Networks system that already has an Enterprise profile.
<b>Action</b>	If you want to replace the existing Enterprise profile with the profile you are trying to import, use the Force option.
<b>TNS.0003.4298E</b>	<b>A deleted profile with the name "{0}" already exists. Unable to recreate a deleted profile.</b>
<b>Explanation</b>	A deleted partner profile with this Corporation Name already exists. Trading Networks maintains information about deleted profiles in its database and does not allow duplicate partner names.
<b>Action</b>	You can either use a different Corporation Name, or use the <code>wm.tn.profile:undeleteProfile</code> service to reinstate the deleted partner profile.
<b>TNS.0003.4299</b>	<b>Could not get Users for partner (partnerID={0}).</b>
<b>Explanation</b>	Encountered SQL Exception, not able to fetch users for specified partner.
<b>Action</b>	Check database connection
<b>TNS.0003.4300</b>	<b>Could not get partners for user (username={0}).</b>
<b>Explanation</b>	Encountered SQL Exception, not able to fetch partners for specified user.
<b>Action</b>	Check database connection

<b>TNS.0003.4301</b>	<b>Could not add users data for partner (id={1}).</b>
<b>Explanation</b>	An exception was thrown while adding users to a partner.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4302</b>	<b>Could not delete users data for partner (id={1}).</b>
<b>Explanation</b>	An exception was thrown while deleting users for a partner.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4303</b>	<b>Attempted to import a field definition "{0}" that uses a field group {1}, but this field group is not defined on your Trading Networks system.</b>
<b>Explanation</b>	You attempted to import a field definition that uses a field group, but this field group is not defined on your Trading Networks.
<b>Action</b>	Try importing field group before importing the field definition.
<b>TNS.0003.4304</b>	<b>Attempted to import a profile "{0}" that uses a contact type {1}, but this Contact Type is not defined on your Trading Networks system.</b>
<b>Explanation</b>	You attempted to import a profile that uses a contact type, but this contact type is not defined on your Trading Networks system.
<b>Action</b>	Try importing contact type before importing the profile.
<b>TNS.0003.4305</b>	<b>Attempted to import a profile "{0}" that uses an external id type {1}, but this external id type is not defined on your Trading Networks system.</b>
<b>Explanation</b>	You attempted to import a profile that uses an external ID type, but this external ID type is not defined on your Trading Networks system.
<b>Action</b>	Try importing external ID before importing the profile.
<b>TNS.0003.4306</b>	<b>Attempted to import a profile "{0}" that uses a profile group {1}, but this profile group is not defined on your Trading Networks system.</b>
<b>Explanation</b>	You attempted to import a profile that uses a profile group, but this profile group is not defined on your Trading Networks system.
<b>Action</b>	Try importing profile group before importing the profile.

<b>TNS.0003.4309</b>	<b>Could not validate the EXTERNAL ID with (idType={0}) and (externalID={1})</b>
<b>Explanation</b>	An exception was thrown while validating the specified external ID.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4310</b>	<b>Error encountered while getting the External IDs associated with partner with (partnerID={0})</b>
<b>Explanation</b>	Error encountered while getting the External IDs associated with the supplied partnerID.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4311</b>	<b>Following errors occurred during updating externalID</b>
<b>Explanation</b>	Errors occurred during updating external ID.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4312</b>	<b>ID not added as the (externalIDType={0}) given is not a valid one.</b>
<b>Explanation</b>	Validation failed while updating the set of external IDs associated with a profile.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4313</b>	<b>The partner specified (partnerID={0}) doesnot exist in the trading networks. Give a correct one.</b>
<b>Explanation</b>	Supplied partnerID does not exist in the Trading Networks.
<b>Action</b>	Supply valid partner ID.
<b>TNS.0003.4314</b>	<b>ID not added as the (externalIDType={0}) given already exists.</b>
<b>Explanation</b>	ID not added as the externalIDType=0 supplied already exists.
<b>Action</b>	Supply valid ID
<b>TNS.0003.4316</b>	<b>Error encountered while getting registered EDI IDTypes.</b>
<b>Explanation</b>	Error encountered while fetching registered EDI IDTypes.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

<b>TNS.0003.4317</b>	<b>Error encountered while cleaning up registered EDI IDTypes.</b>
<b>Explanation</b>	Error encountered while deregistering EDI ID Types.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4318</b>	<b>Error encountered while getting the Internal ID of the Enterprise profile.</b>
<b>Explanation</b>	Error encountered while getting the Internal ID of the Enterprise profile.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4319</b>	<b>Error encountered while getting the Internal Identifier for the environment.</b>
<b>Explanation</b>	Error encountered while getting the Internal Identifier for the environment.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4320</b>	<b>"deliveryInfo" is empty. At least one Destination must be supplied.</b>
<b>Explanation</b>	While adding delivery settings, no destination supplied. At least one destination must be supplied.
<b>Action</b>	Supply at least one destination.
<b>TNS.0003.4321</b>	<b>"DestinationID" is empty. At least one DestinationID must be supplied.</b>
<b>Explanation</b>	While removing delivery settings, no destination ID supplied. At least one destination ID must be supplied.
<b>Action</b>	Supply at least one destination ID.
<b>TNS.0003.4322</b>	<b>Error encountered while adding the (externalIDType={0}).</b>
<b>Explanation</b>	Error encountered while adding the External ID type to Trading Networks.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4323</b>	<b>Service Signature given (Service Signature ={0}) is invalid. Give a valid one.</b>
<b>Explanation</b>	Validation failed while retrieving the input or output signature of a specified service.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

---

<b>TNS.0003.4324</b>	<b>Error encountered while extracting Registered delivery Services.</b>
<b>Explanation</b>	Error encountered while extracting registered delivery Services.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4325</b>	<b>Cannot set extended field {0} for partnerID {1}.</b>
<b>Explanation</b>	Error encountered while updating extended field for a profile.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4326</b>	<b>Could not add user mapping for partnerID {0} and User {1}.</b>
<b>Explanation</b>	Error encountered while adding user mapping for a profile.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4327</b>	<b>Either one of the inputs of simpleQuery or queryInput is mandatory for querying the profile.</b>
<b>Explanation</b>	Neither input of simpleQuery nor queryInput fields supplied for querying the profile.
<b>Action</b>	Supply either input of simpleQuery or queryInput fields for querying the profile.
<b>TNS.0003.4328</b>	<b>Error encountered while executing Profile Query</b>
<b>Explanation</b>	Error encountered while executing Profile Query
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4329</b>	<b>My Enterprise Profile with specified (partnerID={0}) cannot be deleted.</b>
<b>Explanation</b>	You tried to delete the Enterprise Profile, but the Enterprise profile cannot be deleted.
<b>Action</b>	Don not attempt to delete the Enterprise profile.
<b>TNS.0003.4332</b>	<b>Please specify correct value for routing field. Mandatory values for it are true and false.</b>
<b>Explanation</b>	Supplied value for routing field is neither true nor false.
<b>Action</b>	Supply valid routing field value. It should be either true or false.

<b>TNS.0003.4334</b>	<b>Error encountered while adding DLS artifacts with name ({0}).</b>
<b>Explanation</b>	Error encountered while adding DLS artifacts, found artifact with specified name as null.
<b>Action</b>	Supply valid value for specified artifact name.
<b>TNS.0003.4336</b>	<b>Error encountered while querying on DLS Rules.</b>
<b>Explanation</b>	Error encountered while querying on DLS Rules and roles.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4337</b>	<b>Pipeline for modifying the Rules and RuleRoleInfo shouldn't be null.</b>
<b>Explanation</b>	Input fields found to be null, while modifying the Rules and RuleRoleInfo.
<b>Action</b>	Supply the input fields containing IData/pipeline.
<b>TNS.0003.4338</b>	<b>Either of the Rules or RoleRoleInfo shouldn't be present.</b>
<b>Explanation</b>	Either Rules or RoleRoleInfo should be present while modifying.
<b>Action</b>	Supply either Rules or RoleRoleInfo.
<b>TNS.0003.4339</b>	<b>Error while Rule Addition/Modification, as a Rule already exists with the name ({0}).</b>
<b>Explanation</b>	Error encountered while adding or modifying rule, because a rule with the same name already exists.
<b>Action</b>	Supply rule with a different name.
<b>TNS.0003.4340</b>	<b>Error while Role Addition/Modification, as a Role already exists with the name ({0}).</b>
<b>Explanation</b>	Error encountered while adding or modifying a role, because a role with the same name already exists.
<b>Action</b>	Supply a role with different name.
<b>TNS.0003.4341</b>	<b>Please specify either Permission or ProfileID. Both of them are either null or empty. Either one of them is mandatory.</b>
<b>Explanation</b>	Found that Permission and ProfileID both are either null or empty while checking whether the current user can perform the required action.
<b>Action</b>	Supply either Permission and ProfileID.

---

<b>TNS.0003.4342</b>	<b>Please specify Permission. Either it is null or empty. Its a mandatory field.</b>
<b>Explanation</b>	During functional permission check, input field Permission found to be null or empty.
<b>Action</b>	Supply mandatory input field Permission.
<b>TNS.0003.4343</b>	<b>Error encountered while during operation on Functional Privileges.</b>
<b>Explanation</b>	Error encountered while checking functional privileges.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4344</b>	<b>Error encountered while querying for Functional Privileges.</b>
<b>Explanation</b>	Error encountered while querying for functional privileges.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4345</b>	<b>Please specify either Add or Remove. Both of them are either null or empty. Either one of them is mandatory.</b>
<b>Explanation</b>	While modifying functional privileges, both of the input field Add/Remove found empty or null.
<b>Action</b>	Supply valid values for the field Add/Remove.
<b>TNS.0003.4346</b>	<b>Access denied, as the User "{0}" does not have the permission to {1} {2}.</b>
<b>Explanation</b>	User is not permitted to perform the specified action.
<b>Action</b>	Contact your administrator.
<b>TNS.0003.4347</b>	<b>Access denied, as the User "{0}" does not have the permission to view {1}.</b>
<b>Explanation</b>	User is not allowed to perform the specified action.
<b>Action</b>	Contact your administrator.
<b>TNS.0003.4348</b>	<b>Access denied, as the User "{0}" does not have the privilege to {1} {2}.</b>
<b>Explanation</b>	User is not allowed to perform the specified action.
<b>Action</b>	Contact your administrator.

<b>TNS.0003.4349</b>	<b>Access denied, as the User "{0}" does not have the privilege to view {1}.</b>
<b>Explanation</b>	User is not allowed to perform the specified action.
<b>Action</b>	Contact your administrator.
<b>TNS.0003.4393</b>	<b>Access Denied. User "{0}" does not have permission to query expired certificates.</b>
<b>Explanation</b>	Specified user does not have permission to query expired certificates.
<b>Action</b>	Contact your administrator.
<b>TNS.0003.4399</b>	<b>Error encountered while getting list of permissions for the user "{0}".</b>
<b>Explanation</b>	Error encountered while getting list of permissions for the specified user.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4401</b>	<b>Error encountered while profile "{0}" disassociation with DataSet "{1}".</b>
<b>Explanation</b>	Error encountered while profile disassociation with DataSet.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.4402</b>	<b>Disassociation of profile "{0}" from DataSet "{1}" is disallowed. Dissassociation would have made profile disappear from your profile list.</b>
<b>Explanation</b>	Disassociation of profile from DataSet is disallowed. Dissassociation would have made profile disappear from your profile list.
<b>Action</b>	No action required.
<b>TNS.0003.4404</b>	<b>Could not create delivery service {0}. A delivery service named {0} already exists.</b>
<b>Explanation</b>	Delivery service with the same name already exists in Trading Networks.
<b>Action</b>	Add delivery service with different name.
<b>TNS.0003.4405</b>	<b>The WmTN Property file {0} does not exist</b>
<b>Explanation</b>	Not able to locate Trading Networks properties file at expected location.
<b>Action</b>	Restore the TN Properties file. Contact Software AG Global Support.

---

<b>TNS.0003.4406</b>	<b>The WmTN Property file {0} is read only</b>
<b>Explanation</b>	Not able to write to the Trading Networks properties file.
<b>Action</b>	Make the Trading Networks properties file writable. Contact Software AG Global Support.
<b>TNS.0003.5001E</b>	<b>This document type ({0}) is missing one or both of its signature queries (Signature and SignedBody). Signing cannot proceed.</b>
<b>Explanation</b>	Trading Networks cannot create a digital signature because the TN document type did not instruct Trading Networks to extract the signature or signed body system attributes.
<b>Action</b>	Add queries to extract the Signature and SignedBody system attributes to the TN document type. For instructions, see the Trading Networks documentation.
<b>TNS.0003.5002E</b>	<b>The signing service for this document ({0}) generated an error. The original error was {1}.</b>
<b>Explanation</b>	Error encountered while signing the specified document.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.5003E</b>	<b>Signing Failed</b>
<b>Explanation</b>	See message TRNSERV.000013.000002 for full details.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception displayed with message TRNSERV.000013.000002.
<b>TNS.0003.5005E</b>	<b>Base-64 encoding the signed body for this document failed to produce a value. The signed body (before encoding) was {0}.</b>
<b>Explanation</b>	The query used to extract the signed body from the document might be invalid. You specify the query that Trading Networks uses in the TN document type used for the document.
<b>Action</b>	If the query used for the signed body returned an empty string, adjust the signed body query for this TN document type. For instructions, see the Trading Networks documentation.
<b>TNS.0003.5006E</b>	<b>Encoding Error</b>
<b>Explanation</b>	See message TRNSERV.000013.000005 for full details.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception displayed with message TRNSERV.000013.000005.

<b>TNS.0003.5007E</b>	<b>An error prevented fetching certificate info for the sender of this document.</b>
<b>Explanation</b>	An exception was thrown while retrieving certificates needed to sign a document.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.5008E</b>	<b>Error fetching cert info</b>
<b>Explanation</b>	See message TRNSERV.000013.000007 for full details.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception displayed with message TRNSERV.000013.000007.
<b>TNS.0003.5010E</b>	<b>No private key information was available for the sender of this document. {0}</b>
<b>Explanation</b>	Trading Networks encountered an error while fetching a private key. See the error message for details.
<b>Action</b>	You might need to import security data for this partner.
<b>TNS.0003.5012E</b>	<b>Applying the {1} query to this document failed. The error: {2}</b>
<b>Explanation</b>	Trading Networks encountered an error while executing the query to extract the signature from a document. See the exception for details.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.5013E</b>	<b>Query Error</b>
<b>Explanation</b>	See message TRNSERV.000013.000012 for full details.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception displayed with message TRNSERV.000013.000012.
<b>TNS.0003.5014E</b>	<b>The signature query for doctype {0} identified the {1} node as the target of the signature, but this node is missing in this document. Signing cannot proceed.</b>
<b>Explanation</b>	The query used to extract the signature from the document identified a node that is not in the document. You specify the query that Trading Networks uses in the TN document type used for the document.
<b>Action</b>	Adjust the signature and/or signed body query for this TN document type. For instructions, see the Trading Networks documentation.

<b>TNS.0003.5015E</b>	<b>Missing Document Node</b>
<b>Explanation</b>	See message TRNSERV.000013.000014 for full details.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception displayed with message TRNSERV.000013.000014.
<b>TNS.0003.5017E</b>	<b>No cert chains are available for the sender of this document. {0}</b>
<b>Explanation</b>	Trading Networks encountered an error while fetching a certificate chain. See the error message for details.
<b>Action</b>	Take appropriate action to resolve the problem described in the error.
<b>TNS.0003.5019E</b>	<b>Cannot sign documents from UNKNOWN sender</b>
<b>Explanation</b>	The sender of the document is unknown to Trading Networks. Reasons that Trading Networks might be unable to determine the sender are: 1) The query that Trading Networks uses to extract the Sender value from the document might be incorrect. The query is defined in the TN document type. 2) The value extracted from the document for the Sender query does not match the external ID of any partner in the Trading Networks database. 3) The structure of the document is incorrect.
<b>Action</b>	Do one of the following: 1) If the query used to extract the Sender value is not valid, adjust the query in the TN document type. For instructions, see the Trading Networks documentation. 2) If the value extracted for the Sender query does not match an external ID in the Trading Networks database, add the external ID to the appropriate partner's profile. For instructions, see the Trading Networks documentation. 3) If the document structure is incorrect, notify the partner that sent the document.
<b>TNS.0003.5021E</b>	<b>This doctype ({0}) has no signing service defined. Signing cannot continue.</b>
<b>Explanation</b>	This TN document type has no signing service defined, so Trading Networks cannot continue with signing.
<b>Action</b>	If this is an XML TN document type, contact Software AG Global Support. If this is not an XML TN document type and the TN document type supports signing services, define a signing service for the TN document type.
<b>TNS.0003.5024E</b>	<b>The signature query for doctype {0} ({1}) failed to identify a node to insert the signature into. Signing cannot proceed.</b>
<b>Explanation</b>	Either the query that Trading Networks uses to extract the signature is incorrect in the TN document type or the structure of the document is incorrect.
<b>Action</b>	If the query is not correct, adjust the signature query for this TN document type. For instructions, see the Trading Networks documentation. If the document structure is incorrect, notify the document sender.

<b>TNS.0003.5025E</b>	<b>The signature query for doctype {0} identified the {1} node as the target of the signature, but this node is not unique in this document. Signing cannot proceed.</b>
<b>Explanation</b>	Either the structure of the document is incorrect or the query that Trading Networks uses to extract the signature is incorrect in the TN document type.
<b>Action</b>	If the document structure is incorrect, notify the document sender. If the query is not correct, adjust the signature query for this TN document type. For instructions, see the Trading Networks documentation. Note that if your XQL query is returning an array of nodes, you can force it to return a single node by adding a subscript. For example, change <code>"/anXMLtag"</code> to <code>"/anXMLtag[0]"</code> .
<b>TNS.0003.5027W</b>	<b>No signing service for doctype {0}</b>
<b>Explanation</b>	This TN document type has no signing service defined, so Trading Networks cannot continue with signing.
<b>Action</b>	If this is an XML TN document type, contact Software AG Global Support. If this is not an XML TN document type and the TN document type supports signing services, define a signing service for the TN document type.
<b>TNS.0003.5030E</b>	<b>Trading Networks will not sign documents originating from the Unknown partner. Signing fails.</b>
<b>Explanation</b>	The sender of the document is unknown to Trading Networks. Reasons that Trading Networks might be unable to determine the sender are: 1) The query that Trading Networks uses to extract the Sender value from the document might be incorrect. The query is defined in the TN document type. 2) The value extracted from the document for the Sender query does not match the external ID of any partner in the Trading Networks database. 3) The structure of the document is incorrect.
<b>Action</b>	Do one of the following: 1) If the query used to extract the Sender value is not valid, adjust the query in the TN document type. For instructions, see the Trading Networks documentation. 2) If the value extracted for the Sender query does not match an external ID in the Trading Networks database, add the external ID to the appropriate partner's profile. For instructions, see the Trading Networks documentation. 3) If the document structure is incorrect, notify the partner that sent the document.
<b>TNS.0003.5031E</b>	<b>The signed body query for this document type ({0}) failed to produce a value. Signing the document fails. The query was {1}.</b>
<b>Explanation</b>	Either the query that Trading Networks uses to extract the signature is incorrect in the TN document type or the structure of the document is incorrect.
<b>Action</b>	If the query is not correct, adjust the signature query for this TN document type. For instructions, see the Trading Networks documentation. If the document structure is incorrect, notify the document sender.

---

<b>TNS.0003.6001E</b>	<b>Cannot persist a TPA</b>
<b>Explanation</b>	An exception was thrown while saving a TPA to the database.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.6002E</b>	<b>Cannot retrieve a TPA</b>
<b>Explanation</b>	An exception was thrown while reading a TPA from the database.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.6006E</b>	<b>Cannot delete a TPA with status="agreed"</b>
<b>Explanation</b>	You cannot delete a TPA with status Agreed.
<b>Action</b>	Change the TPA's status to Proposed and then delete it.
<b>TNS.0003.6007E</b>	<b>Cannot delete a TPA</b>
<b>Explanation</b>	An exception was thrown while deleting a TPA from the database.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.6008E</b>	<b>Cannot update a TPA that has status="agreed"</b>
<b>Explanation</b>	A TPA in "Agreed" status cannot be revised.
<b>Action</b>	Change the TPA's status to "Proposed" before updating the TPA.
<b>TNS.0003.6009E</b>	<b>Cannot update a TPA</b>
<b>Explanation</b>	An exception was thrown while updating a TPA in the database.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.6010E</b>	<b>Cannot get a TPA lock</b>
<b>Explanation</b>	An exception was thrown while getting a lock on a TPA in the database.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

<b>TNS.0003.6011E</b>	<b>Cannot update controlNumber for a TPA</b>
<b>Explanation</b>	An exception was thrown while updating the control number of a TPA in the database.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.6014E</b>	<b>Cannot update tpaData when status="agreed" and dataStatus="immutable"</b>
<b>Explanation</b>	You attempted to update the TPA data that is associated with a TPA. The Agreement Status of the TPA is "Agreed" and the Data Status is "Non-modifiable." You cannot update the TPA data when the Data Status is "Non-modifiable."
<b>Action</b>	To be able to update the TPA data, perform one of the following actions: 1) change the Data Status to "Modifiable," or 2) change the Agreement Status to "Proposed."
<b>TNS.0003.6017E</b>	<b>Cannot update tpaData</b>
<b>Explanation</b>	An exception was thrown while updating the TPA data in a TPA in the database.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.6018E</b>	<b>Cannot get the next controlNumber for a TPA</b>
<b>Explanation</b>	An exception was thrown while determining the next control number for a TPA in the database.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.6020E</b>	<b>Cannot change status for a TPA</b>
<b>Explanation</b>	An exception was thrown while changing the status of a TPA in the database.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.6021E</b>	<b>A TPA that matches senderID, receiverID and agreementID does not exists</b>
<b>Explanation</b>	Internal error
<b>Action</b>	Contact Software AG Global Support.

---

<b>TNS.0003.6022E</b>	<b>Missing senderID, or receiverID, or agreementID or initService</b>
<b>Explanation</b>	Internal error
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0003.6023E</b>	<b>Cannot invoke initService</b>
<b>Explanation</b>	Unable to initialize the data in a TPA because the TPA's initialization service could not be invoked.
<b>Action</b>	Make sure the TPA's initialization service is an existing service in an enabled package.
<b>TNS.0003.6025E</b>	<b>Query TPA exception</b>
<b>Explanation</b>	An exception was thrown while executing a TPA database query.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.6026E</b>	<b>Cannot get all TPAs</b>
<b>Explanation</b>	An exception was thrown while retrieving a list of TPAs from the database.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.6027E</b>	<b>Cannot import TPA</b>
<b>Explanation</b>	An exception was thrown while importing one or more TPAs.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.6028E</b>	<b>Missing data schema</b>
<b>Explanation</b>	No IS document type is defined for the TPA.
<b>Action</b>	Define an IS document type for the TPA.
<b>TNS.0003.6029E</b>	<b>Missing TPA data</b>
<b>Explanation</b>	The TPA Data field in the TPA is empty.
<b>Action</b>	Enter values into the TPA Data field.

<b>TNS.0003.6030E</b>	<b>Cannot invoke validation service</b>
<b>Explanation</b>	An exception was thrown while invoking the pub.schema:validate service while validating the structure of the IS document type in the TPA.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.6031E</b>	<b>Missing {0}</b>
<b>Explanation</b>	A required input variable was not supplied to the wm.tn.tpa:updateTPA service.
<b>Action</b>	Supply a value for the required variable.
<b>TNS.0003.6032E</b>	<b>A TPA that matches senderID, receiverID and agreementID already exists</b>
<b>Explanation</b>	Cannot save this TPA because it would duplicate an existing TPA.
<b>Action</b>	Either add the data in this TPA to the one that already exists, or specify a different agreementID.
<b>TNS.0003.6033E</b>	<b>A TPA that matches senderID, receiverID and agreementID does not exist</b>
<b>Explanation</b>	Cannot update the TPA because Trading Networks cannot locate a TPA in the database that has the supplied senderID, receiverID, and agreementID.
<b>Action</b>	Specify a senderID, receiverID and agreementID that matches an existing TPA.
<b>TNS.0003.6034E</b>	<b>controlNumber cannot not be null</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0003.6035E</b>	<b>tpaData cannot not be null</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0003.6036E</b>	<b>Cannot update tpaData when dataStatus="immutable"</b>
<b>Explanation</b>	You cannot make changes to a TPA's data when the TPA's Data Status is "Non-modifiable."
<b>Action</b>	To make changes to the TPA data, change the TPA's Data Status to "Modifiable."

---

<b>TNS.0003.6037E</b>	<b>Cannot update controlNumber</b>
<b>Explanation</b>	An exception was thrown while updating the control number of a TPA in the database.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.6038E</b>	<b>There are more than one TPA that matches senderID, receiverID and agreementID</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0003.6039E</b>	<b>Cannot serialize tpaData</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0003.6040E</b>	<b>Cannot de-serialize tpaData</b>
<b>Explanation</b>	The supplied control number is not a valid integer.
<b>Action</b>	Supply a valid integer value.
<b>TNS.0003.6041</b>	<b>New controlNumber is not an integer</b>
<b>Explanation</b>	Encountered error while parsing supplied controlNumber because it is not an integer.
<b>Action</b>	Supply an integer value for controlNumber.
<b>TNS.0003.6042E</b>	<b>A TPA with the supplied ID ({0}) does not exist.</b>
<b>Explanation</b>	An invalid value was supplied for the tpaID field.
<b>Action</b>	Supply a valid TPA ID.
<b>TNS.0003.6043E</b>	<b>If "tpaID" is not supplied, then "senderID", "receiverID" and "agreementID" must be supplied.</b>
<b>Explanation</b>	The user did not supply the correct required inputs.
<b>Action</b>	Supply the required inputs.
<b>TNS.0003.6044</b>	<b>Attempted to import a TPA for Sender {0}, but the sender's profile is not defined on your Trading Networks system.</b>
<b>Explanation</b>	Attempted to import a TPA for Sender, but the sender's profile is not defined on your Trading Networks system.
<b>Action</b>	Import Sender's profile first.

**TNS.0003.6045**      **Attempted to import a TPA for Receiver {0}, but the receiver's profile is not defined on your Trading Networks system.**

**Explanation**      Attempted to import a TPA for Receiver, but the receiver's profile is not defined on your Trading Networks system.

**Action**             Import Receiver's profile first.

**TNS.0003.6050**      **Attempted to import a Archive Scheduled Service for Sender {0}, but the sender's profile is not defined on your Trading Networks system.**

**Explanation**      Attempted to import a Archive Scheduled Service for specified Sender, but the sender's profile is not defined on your Trading Networks system.

**Action**             Import Sender's profile first.

**TNS.0003.6051**      **Attempted to import a Archive Scheduled Service for Receiver {0}, but the receiver's profile is not defined on your Trading Networks system.**

**Explanation**      Attempted to import a Archive Scheduled Service for Receiver, but the receiver's profile is not defined on your Trading Networks system.

**Action**             Import Receiver's profile first.

**TNS.0003.7002E**      **Document type {0} has no validation service defined. Validation fails.**

**Explanation**      Supplied document type has no validation service defined.

**Action**             Contact Software AG Global Support.

**TNS.0003.7003E**      **No Validation Service**

**Explanation**      A TN document type has no validation service defined. Validation fails.

**Action**             Contact Software AG Global Support.

**TNS.0003.7004E**      **{0}: {1}**

**Explanation**      A document sent to Trading Networks failed validation.

**Action**             Notify the document sender.

**TNS.0003.7005W**      **Doctype {0}: no validation svc. defined; validation skipped**

**Explanation**      Document type has no validation service defined. Validation fails.

**Action**             Contact Software AG Global Support.

---

<b>TNS.0003.7010E</b>	<b>The doctype for this document ({0}) does not have a validation schema defined; validation fails.</b>
<b>Explanation</b>	The document matches a TN document type that indicates the document's structure should be validated, but no schema was defined.
<b>Action</b>	Update the TN document type, and specify the schema to use for document validation.
<b>TNS.0003.7011E</b>	<b>No Validation Schema</b>
<b>Explanation</b>	The document matches a processing rule that indicates the document's structure should be validated, but no schema was defined.
<b>Action</b>	Update the TN document type that the document matches to specify the schema to use for document validation.
<b>TNS.0003.7012E</b>	<b>The validation service for this XML document, {0}, could not be successfully invoked. The original exception message is: {1}</b>
<b>Explanation</b>	The service used to validate the document's structure threw an exception.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.7013E</b>	<b>The validation service used for this document ({0}) failed with the following exception message: {1}</b>
<b>Explanation</b>	The service used to validate the document's structure threw an exception.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.7014E</b>	<b>Validation Service Failed</b>
<b>Explanation</b>	The service used to validate the document's structure threw an exception.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0003.7015E</b>	<b>XML validation failed: does not apply to non-XML documents.</b>
<b>Explanation</b>	Invoked the wm.tn.doc.xml:validate service with a document that is not XML.
<b>Action</b>	Supply an XML document.
<b>TNS.0003.7016E</b>	<b>XML validation failed: no document content available</b>
<b>Explanation</b>	Document is empty.
<b>Action</b>	Supply an XML document that has content.

<b>TNS.0003.7017E</b>	<b>The validation service, {0} aborted processing of this document. The message was {1}.</b>
<b>Explanation</b>	The document is not valid XML.
<b>Action</b>	Notify the document sender.
<b>TNS.0003.7019E</b>	<b>Flat file validation failed. Document type is not "flat file".</b>
<b>Explanation</b>	Attempted to use a flat file validation service to validate a document that is not a flat file.
<b>Action</b>	Supply a flat file document.
<b>TNS.0003.7020E</b>	<b>Flat file validation failed: no document content available</b>
<b>Explanation</b>	Document is empty.
<b>Action</b>	Supply a flat file document that has content.
<b>TNS.0003.7021E</b>	<b>Flat file validation failed. Document type "{0}" has no parsing schema.</b>
<b>Explanation</b>	The document matches a TN document type that indicates the document's structure should be validated, but no schema was defined.
<b>Action</b>	Update the TN document type, and specify the schema to use for document validation.
<b>TNS.0003.7022E</b>	<b>Validation error</b>
<b>Explanation</b>	The flat file document structure is invalid.
<b>Action</b>	Notify the document sender.
<b>TNS.0004.1001E</b>	<b>Invalid or missing page number.</b>
<b>Explanation</b>	This error occurs if a value for the pageNum variable is not specified for the wm.tn.enumerate:nth service or if a value for the pageNumber variable is not specified for the wm.tn.query:getQueryResults service.
<b>Action</b>	Specify a value for the pageNum variable or pageNumber variable.
<b>TNS.0004.1002E</b>	<b>id is required.</b>
<b>Explanation</b>	A value for the id input variable was not specified for either the wm.tn.enumerate:nth service or the wm.tn.enumerate:first service.
<b>Action</b>	Specify a value for the input variable id.

---

<b>TNS.0004.1004E</b>	<b>Invalid time interval {0} for query.</b>
<b>Explanation</b>	The wm.tn.query:createDocumentQuery service was supplied an invalid value for the input variable timeInterval.
<b>Action</b>	Provide a valid value for the input variable timeInterval.
<b>TNS.0004.1005E</b>	<b>Unknown attribute ID: {0}.</b>
<b>Explanation</b>	The wm.tn.query:createDocumentQuery service was provided an invalid value for the input variable attribId.
<b>Action</b>	Provide a valid value for the input variable attribId.
<b>TNS.0004.1006E</b>	<b>Unknown attribute name: {0}.</b>
<b>Explanation</b>	The wm.tn.query:createDocumentQuery service was provided an invalid value for the input variable attribName.
<b>Action</b>	Provide a valid value for the input variable attribName.
<b>TNS.0004.1007E</b>	<b>Unknown op: {0}.</b>
<b>Explanation</b>	The wm.tn.query:createDocumentQuery service was provided an invalid value for the input variable op.
<b>Action</b>	Provide a valid value for the input variable op. For more information about valid values, refer to the Trading Networks documentation.
<b>TNS.0004.1008E</b>	<b>Invalid entry type {0} for event.</b>
<b>Explanation</b>	The wm.tn.query:createEventQuery service was provided an invalid value for the input variable entryType.
<b>Action</b>	Provide a valid value for the input variable entryType.
<b>TNS.0004.1009E</b>	<b>Invalid time interval {0} for query</b>
<b>Explanation</b>	Either the wm.tn.query:createEventQuery service or the wm.tn.query:createTPAQuery service has an invalid value specified for the input variable timeInterval.
<b>Action</b>	Specify a valid value for the input variable timeInterval.
<b>TNS.0004.1010E</b>	<b>Invalid timeCreated interval {0} for query</b>
<b>Explanation</b>	The wm.tn.query:createTaskQuery service has an invalid value specified for the input variable timeCreated.
<b>Action</b>	Specify a valid value for the input variable timeCreated.

<b>TNS.0004.1012D</b>	<b>Requested page is not available</b>
<b>Explanation</b>	Requested page is not available. This error occurs when Trading Networks attempts to read beyond the end of the query results while invoking the wm.tn.enumerate:nth service. This error can also occur when data corresponding to the pageNumber input variable for the service wm.tn.query:getQueryResults is not available to Trading Networks.
<b>Action</b>	If the error occurs while invoking the wm.tn.enumerate:nth service, ensure the value specified for pageNum is valid. If the error occurs while invoking the wm.tn.query:getQueryResults service, ensure the value specified for pageNumber is valid. If the problem still persists, refresh the query.
<b>TNS.0004.1013D</b>	<b>Unable to retrieve page. Operation timed out.</b>
<b>Explanation</b>	The Integration Server might be busy doing other work.
<b>Action</b>	Attempt to retrieve the page again, or re-execute the query.
<b>TNS.0004.1014E</b>	<b>Query execution failed.</b>
<b>Explanation</b>	An exception occurred while executing a database query.
<b>Action</b>	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0004.1015E</b>	<b>External ID value is required.</b>
<b>Explanation</b>	You created a profile query that specifies an externalIDType, but did not specify an externalIDValue.
<b>Action</b>	Provide a valid value for the externalIDValue input variable to the createProfileQuery service.
<b>TNS.0004.1016E</b>	<b>fieldId[{0}] is null or empty.</b>
<b>Explanation</b>	You created a profile query that specifies an externalIDValue, but you did not specify an externalIDType.
<b>Action</b>	Supply a valid value for the externalIDType input variable to the createProfileQuery service.
<b>TNS.0004.2001E</b>	<b>Illegal query type: {0}.</b>
<b>Explanation</b>	The query type specified as the input to the service is not valid.
<b>Action</b>	Supply a valid value for the query type. For a list of valid values, see the Trading Networks documentation.

---

<b>TNS.0004.2002E</b>	<b>pageNumber should be a positive integer.</b>
<b>Explanation</b>	The wm.tn.query:getQueryResults service was supplied an invalid value for the input variable pageNumber.
<b>Action</b>	Supply a valid value for the input variable pageNumber. The value must be a positive integer.
<b>TNS.0004.2003E</b>	<b>A valid pageNumber is required.</b>
<b>Explanation</b>	The pageNumber input variable for the wm.tn.query:getQueryResults service is not valid.
<b>Action</b>	Specify a valid value for pageNumber. The value must be a positive integer.
<b>TNS.0004.2005E</b>	<b>Got null query result data for queryId={0}, page={1}.</b>
<b>Explanation</b>	The wm.tn.query:getQueryResults service is not able to find the data corresponding to the specified queryId and pageNumber.
<b>Action</b>	Ensure the queryId and pageNumber are correct. If the issue persists, resubmit the query.
<b>TNS.0004.2006E</b>	<b>Got null row at index {0}.</b>
<b>Explanation</b>	There is no data corresponding to the specified index.
<b>Action</b>	Make sure the specified index is correct.
<b>TNS.0004.2008I</b>	<b>Can not retrieve task {0}.</b>
<b>Explanation</b>	While searching for tasks in My webMethods Server, no data corresponding to the specified taskId was found.
<b>Action</b>	Make sure the taskId is correct. If you update the taskId, then you must resubmit the query.
<b>TNS.0004.2010E</b>	<b>User does not have adequate privilege to obtain requested data.</b>
<b>Explanation</b>	The user's attempt to view the data failed because the user does not have permission to view the requested data.
<b>Action</b>	An administrator can grant permission to the user. For information about assigning permissions, refer to the Trading Networks documentation.

<b>TNS.0004.2011E</b>	<b>Bizdoc with internal id={0} does not exist.</b>
<b>Explanation</b>	The bizdoc with the specified docId cannot be found in the Trading Networks database .
<b>Action</b>	Make sure the docId is correct. If you change the docId, resubmit the query.
<b>TNS.0004.2012E</b>	<b>Null bizdoc retrieved for internal id = {0}.</b>
<b>Explanation</b>	The bizdoc with the specified docID cannot be found in the Trading Networks database.
<b>Action</b>	Make sure the specified docId is correct. If you change the docId, then you must resubmit the query.
<b>TNS.0004.2013E</b>	<b>Can not parse {0}: {1}.</b>
<b>Explanation</b>	The specified input value must be an integer.
<b>Action</b>	Supply a valid integer for the specified input value.
<b>TNS.0004.2017E</b>	<b>Retrieved null content part for document id = {0}, part name = {1}.</b>
<b>Explanation</b>	There are no content parts available for the bizdoc that corresponds to the specified docId.
<b>Action</b>	Make sure that the specified docId is correct and the content parts are recieved. After specifying the correct docId, resubmit the query.
<b>TNS.0004.2019</b>	<b>{0} encountered execution error.</b>
<b>Explanation</b>	An exception occurred while executing the service <code>wm.tn.portal.queries.getContentPartBytes</code> .
<b>Action</b>	The exception is in the full message. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0004.2027</b>	<b>{0} encountered error resubmitting internalDocIDs[{1}] = {2}.</b>
<b>Explanation</b>	In webMethods Trading Networks, when you resubmit the Bizdocs, this exception is thrown if the resubmission fails.
<b>Action</b>	Contact your system administrator.

<b>TNS.0004.2028</b>	<b>{0} encountered error while resubmitting following internalDocIDs: {1}. Access denied, as user {2} doesn't have permission to resubmit these documents.</b>
<b>Explanation</b>	In webMethods Trading Networks, while resubmitting the BizDoc documents, if the user does not have access permission to resubmit these documents, this error is thrown.
<b>Action</b>	The administrator needs to give permission to the user for resubmitting the BizDoc documents.
<b>TNS.0004.2030</b>	<b>{0} encountered null or empty internalDocIDs[{1}], this document was not reprocessed.</b>
<b>Explanation</b>	In webMethods Trading Networks, while reprocessing BizDocs, if null or empty internal DocIDs are passed, this error is thrown.
<b>Action</b>	Ensure that the internal DocIDs are not null or empty.
<b>TNS.0004.2031</b>	<b>{0} encountered error reprocessing internalDocIDs[{1}] {2}.</b>
<b>Explanation</b>	In webMethods Trading Networks, if an error is encountered while reprocessing BizDocs, this error is thrown.
<b>Action</b>	Contact your system administrator.
<b>TNS.0004.2032</b>	<b>{0} encountered error while reprocessing following internalDocIDs: {1}. Access denied, as user {2} doesn't have permission to reprocess these documents.</b>
<b>Explanation</b>	In webMethods Trading Networks, if an error is encountered while reprocessing BizDocs, access is denied as the user does not have permission to reprocess the documents.
<b>Action</b>	Ensure that the administrator gives permission to the user to reprocess BizDocs.
<b>TNS.0004.2034</b>	<b>{0} encountered null or empty taskIDs[{1}] {2}, this task was not stopped.</b>
<b>Explanation</b>	In webMethods Trading Networks, while stopping the tasks, if null or empty taskIDs are passed, this error is thrown.
<b>Action</b>	Ensure that the taskID is not null or empty and try again.
<b>TNS.0004.2035</b>	<b>{0} encountered error stopping taskIDs[{1}] {2}.</b>
<b>Explanation</b>	In webMethods Trading Networks, while stopping the tasks, if the stopping fails for any reason, this error is thrown
<b>Action</b>	Contact your system administrator.

<b>TNS.0004.2036</b>	<b>{0} encountered error while stopping following tasks: {1}. Access denied, as user {2} doesn't have permission to stop these tasks.</b>
<b>Explanation</b>	In webMethods Trading Networks, while stopping the tasks, if the user does not have permission to stop the tasks, this error is thrown.
<b>Action</b>	Ensure that the user has permission to stop the tasks.
<b>TNS.0004.2038</b>	<b>{0} encountered null or empty taskIDs[{1}], this task was not restarted.</b>
<b>Explanation</b>	In webMethods Trading Networks, while restarting tasks, if null or empty taskIDs are passed, this error is thrown.
<b>Action</b>	Ensure that the taskID is not null or empty and try again.
<b>TNS.0004.2039</b>	<b>{0} encountered error restarting taskIDs[{1}] {2}.</b>
<b>Explanation</b>	In webMethods Trading Networks, if restarting tasks fails, this error is thrown.
<b>Action</b>	Contact your system administrator.
<b>TNS.0004.2040</b>	<b>{0} encountered error while restarting following tasks: {1}. Access denied, as user {2} doesn't have permission to restart these tasks.</b>
<b>Explanation</b>	In webMethods Trading Networks, while restarting tasks, if access is denied to the user, this error is thrown.
<b>Action</b>	Ensure that the user has access permission to restart tasks and try again.
<b>TNS.0004.2042</b>	<b>{0} encountered null or empty taskIDs[{1}], this task was not deleted.</b>
<b>Explanation</b>	In webMethods Trading Networks, while deleting tasks, if null or empty taskIDs are passed, this error is thrown.
<b>Action</b>	Ensure that the taskIDs passed are not null or empty, and try again.
<b>TNS.0004.2043</b>	<b>{0} encountered error deleting taskIDs[{1}] {2}.</b>
<b>Explanation</b>	In webMethods Trading Networks, if an error occurs while deleting the tasks, this error is thrown.
<b>Action</b>	Contact your system administrator.
<b>TNS.0004.2044</b>	<b>{0} encountered error while deleting following tasks: {1}. Access denied, as user{2} doesn't have permission to delete these tasks.</b>
<b>Explanation</b>	In webMethods Trading Networks, while deleting tasks, if the user does not have permission, this error is thrown.
<b>Action</b>	Ensure that the user has permission to delete tasks, and try again.

---

<b>TNS.0004.2048</b>	<b>{0} encountered error while updating User Status for internalDocID {1}. Access denied, as user {2} doesn't have permission to change UserStatus for this document.</b>
<b>Explanation</b>	In webMethods Trading Networks, while updating the user status for XXX, if access is denied because the user does not have permission to change UserStatus for this document, this error is thrown.
<b>Action</b>	Ensure to give permission to the user to change UserStatus for the document, and try again.
<b>TNS.0004.2050</b>	<b>{0} encountered error while updating comments for internalDocID {1}. Access denied, as user {2} doesn't have permission to edit comments for this document.</b>
<b>Explanation</b>	In webMethods Trading Networks, while updating comments for an internal document, if access is denied because the user does not have access permissions, this error is thrown.
<b>Action</b>	Ensure that the user has access permissions and try again.
<b>TNS.0004.2052</b>	<b>{0} encountered error while deleting following ActivityLogIDs: {1}. Access denied, as user {2} doesn't have permission to delete these activity logs.</b>
<b>Explanation</b>	In webMethods Trading Networks, while deleting activity logs, if access is denied because the user does not have access permissions, this error is thrown.
<b>Action</b>	Ensure that the user has access permissions, and try again.
<b>TNS.0004.2054</b>	<b>{0} can not reassign task {1} to {2}.</b>
<b>Explanation</b>	In webMethods Trading Networks, while reassigning the task to another server, if it is unsuccessful, this error is thrown.
<b>Action</b>	Contact your system administrator.
<b>TNS.0004.2055</b>	<b>{0} encountered error while reassigning following tasks. Access denied, as user {2} doesn't have permission to reassign these tasks.</b>
<b>Explanation</b>	In webMethods Trading Networks, while reassigning tasks to another server, if the user does not have access permissions, this error is thrown.
<b>Action</b>	Ensure that the user has access permissions, and try again.
<b>TNS.0004.2057</b>	<b>ws.monitor.process.instance:getList returns null output.</b>
<b>Explanation</b>	In webMethods Trading Networks, while getting process information, if ws.monitor.process.instance:getList service returns null output, this error is thrown.
<b>Action</b>	Ensure that the ws.monitor.process.instance:getList service does not return null output, and try again.

<b>TNS.0004.2058</b>	<b>{0} can not get instance information for conversationId {1}.</b>
<b>Explanation</b>	In webMethods Trading Networks, when the user gets a null value of the process information for the conversation ID, this error is thrown.
<b>Action</b>	Ensure the conversation ID is valid and try again.
<b>TNS.0004.2060</b>	<b>{0} retrieved null instance at index 0 for conversationId {1}.</b>
<b>Explanation</b>	In webMethods Trading Networks, while getting process information for a conversation ID, if the instance at index 0 is null, this error is thrown.
<b>Action</b>	Ensure that the instance at index 0 is not null and try again.
<b>TNS.0004.2065</b>	<b>WmMonitor package is not enabled.</b>
<b>Explanation</b>	In webMethods Trading Networks, while checking process information, the WmMonitor package is not installed or enabled.
<b>Action</b>	Ensure that the WmMonitor package is installed and enabled.
<b>TNS.0004.2066</b>	<b>{0} can not submit document.</b>
<b>Explanation</b>	In webMethods Trading Networks, if resubmission of a modified document fails, this error is thrown.
<b>Action</b>	Contact your system administrator.
<b>TNS.0004.2067</b>	<b>{0} encountered error retrieving submitted document from pipeline.</b>
<b>Explanation</b>	In webMethods Trading Networks, while resubmitting documents with modifications, if the retrieved BizDoc is null, this error is encountered.
<b>Action</b>	Ensure that the resubmitted BizDoc is not null and try again.
<b>TNS.0004.2071</b>	<b>{0} encountered error while modifying &amp; resubmitting following document {1}. Access denied, as user {2} doesn't have permission to modify and resubmit this document.</b>
<b>Explanation</b>	In webMethods Trading Networks, while resubmitting modified BizDoc documents, if the user does not have access permissions, this error is displayed.
<b>Action</b>	Ensure that the user has access permissions to resubmit and modify BizDoc documents, and try again.

---

<b>TNS.0004.2072</b>	<b>{0} encountered execution error.</b>
<b>Explanation</b>	In webMethods Trading Networks, if the execution of any query related service fails, this error is displayed.
<b>Action</b>	Contact your system administrator.
<b>TNS.0004.2074</b>	<b>can not parse {0} to long number.</b>
<b>Explanation</b>	In webMethods Trading Networks Server portal util, in the getTimestampFromLong utility, if the time is not in numbered format, this error is thrown.
<b>Action</b>	Enter time in a numbered format and try again.
<b>TNS.0004.2075</b>	<b>null or empty field name</b>
<b>Explanation</b>	In webMethods Trading Networks portal util, the checkQueryColumnName utility throws this exception when the column name is null or empty.
<b>Action</b>	Enter a column name that is not null.
<b>TNS.0004.2076</b>	<b>Invalid query column name: {0}.</b>
<b>Explanation</b>	In webMethods Trading Networks portal util, the checkQueryColumnName utility throws an exception if the column name is invalid.
<b>Action</b>	Enter a valid column name and try again.
<b>TNS.0004.2077</b>	<b>Invalid document attribute "{0}".</b>
<b>Explanation</b>	In webMethods Trading Networks portal util, the checkQueryColumnName utility throws an exception if the query type is of doc query and the attribute list of the document does not contain the name passed to the utility.
<b>Action</b>	Ensure that the attribute list of the document contains the name passed to the utility and try again.
<b>TNS.0004.2078</b>	<b>Invalid whichQuery value ({0}) for PortalUtils.checkQueryColumnName().</b>
<b>Explanation</b>	In webMethods Trading Networks portal util, the checkQueryColumnName utility throws an exception if the query type passed to the utility is invalid.
<b>Action</b>	Ensure to enter a valid query type and try again.

<b>TNS.0004.2079</b>	<b>Invalid value for {0}: null or empty.</b>
<b>Explanation</b>	In webMethods Trading Networks portal util, the validateOperator utility throws an exception if the operator passed to the utility is null or empty.
<b>Action</b>	Pass a valid operator to the utility and try again.
<b>TNS.0004.2080</b>	<b>Invalid operator {0} for data type {1}.</b>
<b>Explanation</b>	In webMethods Trading Networks portal util, the validateOpValPair utility throws an exception if the operator passed to the utility is null or empty.
<b>Action</b>	Enter a valid operator and try again.
<b>TNS.0004.2081</b>	<b>Invalid null value for {0}, corresponding operator is {1}.</b>
<b>Explanation</b>	In webMethods Trading Networks portal util, the validateOpValPair utility throws an exception if the value supplied corresponding to an operator is null.
<b>Action</b>	Enter a not null value corresponding to the operator.
<b>TNS.0004.2082</b>	<b>Illegal value for number query, {0}: {1}.</b>
<b>Explanation</b>	In webMethods Trading Networks portal util, the validateOpValPair utility throws this exception if the value passed to this utility corresponding to an operator is not in numeric value.
<b>Action</b>	Pass the value to the utility in numeric value and try again.
<b>TNS.0004.2083</b>	<b>Illegal value for date and time query, {0}: {1}.</b>
<b>Explanation</b>	In webMethods Trading Networks portal util, the validateOpValPair utility throws this exception if the value passed to this utility corresponding to an operator is not parsed to a long value.
<b>Action</b>	Enter a numeric long value for the date and time query and try again.
<b>TNS.0004.2084</b>	<b>Unable to display the error message. An internal error has occurred. Please contact customer support.</b>
<b>Explanation</b>	In webMethods Trading Networks portal util, the decodeErrorMessage2 utility throws an exception and is unable to decode the error message.
<b>Action</b>	Contact your system administrator.

<b>TNS.0004.2085</b>	<b>Can not get related document information for docId={0}: null data returned</b>
<b>Explanation</b>	In webMethods Trading Networks, while getting document information for a document ID, If the data extracted for the document ID is null, it throws an error.
<b>Action</b>	Contact your system administrator.
<b>TNS.0004.2086</b>	<b>Invalid whichQuery value {0}.</b>
<b>Explanation</b>	In webMethod Trading Networks, this error message is shown if the query type (whichQuery) for creating a query is invalid.
<b>Action</b>	Enter a valid query type (whichQuery) in creating a query.
<b>TNS.0004.2088</b>	<b>Invalid non-number value for queryInput/pageSize: {0}.</b>
<b>Explanation</b>	In webMethods Trading Networks, in creating a query, the query input or page size entered is a non-number value.
<b>Action</b>	Enter a valid numeric value for the query input or the page size.
<b>TNS.0004.2089</b>	<b>queryInput/pageSize value is equal or less than 0.</b>
<b>Explanation</b>	In the webMethods Trading Networks, while creating or retrieving a query, the queryInput or pageSize value entered is not valid because it is equal to or less than 0.
<b>Action</b>	Enter a valid queryInput or pageSize value for creating or retrieving a query.
<b>TNS.0004.2090</b>	<b>queryInput/criteria/dateRange/startDate {0} is after queryInput/criteria/dateRange/endDate {1}.</b>
<b>Explanation</b>	In webMethods Trading Networks, while creating a query, if the start time is earlier than the end time, this error is shown.
<b>Action</b>	Ensure to correct the start time.
<b>TNS.0004.2091</b>	<b>Invalid null value for queryInput/sortOrder[{0}].</b>
<b>Explanation</b>	In webMethods Trading Networks, while creating or retrieving a query, if any of the sorting columns is null, this error is shown.
<b>Action</b>	Ensure that the sorting column is not null.

<b>TNS.0004.2092</b>	<b>{0} queryInput/sortOrder[{1}]/columnName ({2}) is not valid, ignored this column for query sorting.</b>
<b>Explanation</b>	In webMethods Trading Networks, while creating a query, if the sorting column specified in the query input is not valid, the column is ignored for query sorting.
<b>Action</b>	Ensure to enter a valid sorting column in the query.
<b>TNS.0004.2093</b>	<b>Invalid null value for queryInput/criteria/fields[{0}].</b>
<b>Explanation</b>	In webMethods Trading Networks, while creating a query, if any of the given fields is null, this error is shown.
<b>Action</b>	Ensure to enter a valid value (not null) for all the fields.
<b>TNS.0004.2094</b>	<b>Invalid null or empty queryInput/criteria/fields[{0}]/fieldName value.</b>
<b>Explanation</b>	In webMethods Trading Networks, while creating a query, if the field name is null or empty, this error is thrown.
<b>Action</b>	Ensure that all field names are valid.
<b>TNS.0004.2095</b>	<b>query criteria for field {0} already exists, additional criteria found at index {1}.</b>
<b>Explanation</b>	In webMethods Trading Networks, while creating a query, if the query criteria for the field already exists, this error is thrown.
<b>Action</b>	Enter a query criteria that is unique.
<b>TNS.0004.2096</b>	<b>Invalid value: {0} for queryInput/criteria/fields/isOrQuery.</b>
<b>Explanation</b>	In webMethods Trading Networks, while creating a query, an invalid value is entered for the IsOrQuery (value of OR is undefined).
<b>Action</b>	Enter a valid value for the IsOrQuery (value of OR).
<b>TNS.0004.2097</b>	<b>queryInput/criteria/fields[{0}]/criteria is null or 0-length.</b>
<b>Explanation</b>	In webMethods Trading Networks, while creating a query object based on filter criteria, the criteria list for query fields is null or empty.
<b>Action</b>	Enter a valid criteria list for query fields in queryInput.
<b>TNS.0004.2100</b>	<b>Invalid value for {0}: null or empty.</b>
<b>Explanation</b>	In webMethods Trading Networks, while creating a query object based on filter criteria, if the criteria does not contain any operator, this error is thrown.
<b>Action</b>	Enter the operator for the criteria.

<b>TNS.0004.2101</b>	<b>{0} criteria can only be a list plus a dynamic profile query.</b>
<b>Explanation</b>	In webMethods Trading Networks, while creating a query object based on filter criteria, if the query type is a doc query, there should be only one list of values and profile query in the sender and receiver criteria.
<b>Action</b>	Enter only one list of values and profile query in the sender and receiver criteria and try again.
<b>TNS.0004.2102</b>	<b>Invalid value for {0}.</b>
<b>Explanation</b>	In webMethods Trading Networks, while creating a query object based on filter criteria, if the query is of jobQuery type, the internal doc ID or the sender ID or the task ID or the server ID or the instance ID cannot be null.
<b>Action</b>	Ensure that the internal doc ID or the sender ID or the task ID or the server ID or the instance ID are not null and try again.
<b>TNS.0004.2103</b>	<b>Can not understand query {0}.</b>
<b>Explanation</b>	In webMethods Trading Networks, while performing a query, if the query type is not a doc, task, event, profile, bizdoc type, attrib, tpa, or invite type of query, this error message is thrown.
<b>Action</b>	Enter the valid query type and try again.
<b>TNS.0005.1003E</b>	<b>Service manager create failed for server {0} - {1}</b>
<b>Explanation</b>	Encountered a problem while communicating with the database. See the text in the SQL exception for details.
<b>Action</b>	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.1005E</b>	<b>Unable to get profile for {0} - {1}</b>
<b>Explanation</b>	Encountered a problem while communicating with the database. See the text in the SQL exception for details.
<b>Action</b>	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

<b>TNS.0005.1006E</b>	<b>Unable to remove delivery service {0} - {1}</b>
<b>Explanation</b>	Encountered a problem while communicating with the database. See the text in the SQL exception for details.
<b>Action</b>	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.1014E</b>	<b>Unable to create delivery task {0} - service {1} does not exist</b>
<b>Explanation</b>	Attempted to deliver a document using a non-existent delivery service.
<b>Action</b>	Correct the serviceName parameter sent to wm.tn.delivery:deliver.
<b>TNS.0005.1027E</b>	<b>Unable to create service data for partner {0} - {1}</b>
<b>Explanation</b>	Attempted to deliver a document to a partner that cannot receive the document. Receiver is either INACTIVE or is My Enterprise (the entity hosting this Trading Network).
<b>Action</b>	Deliver the document to a valid trading partner with an ACTIVE status.
<b>TNS.0005.1028E</b>	<b>Unable to set private key and certificate chain - {0}</b>
<b>Explanation</b>	Encountered an exception while setting the certificate chain and private key in preparation to deliver a document. See the exception message for details.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.1032E</b>	<b>{0} refreshing {1} cache: {2}</b>
<b>Explanation</b>	Encountered an exception while refreshing an internal cache. See the exception message for details.
<b>Action</b>	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.1038E</b>	<b>Error transporting via {0}: {1}</b>
<b>Explanation</b>	Encountered an exception while delivering a document. See the exception message for details.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception, if possible. It may be a network error beyond your control.

---

<b>TNS.0005.1040E</b>	<b>{0} initializing task store: {1}</b>
<b>Explanation</b>	Encountered an exception while initializing internal caches used for document delivery. See the exception message for details.
<b>Action</b>	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.1041E</b>	<b>{0} deleting delivery service {1}: {2}</b>
<b>Explanation</b>	Encountered an exception while removing a registered delivery service from the database.
<b>Action</b>	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.1050E</b>	<b>{0} deleting task {1}: {2}</b>
<b>Explanation</b>	Encountered an exception while deleting a delivery or routing task.
<b>Action</b>	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.1054E</b>	<b>DeliveryUtils init error: Unable to get profile store: {0}</b>
<b>Explanation</b>	Could not access the profile store during server initialization.
<b>Action</b>	Copy the exception details and call Software AG Global Support.
<b>TNS.0005.1055E</b>	<b>Unable to register delivery service {0} - {1}</b>
<b>Explanation</b>	Encountered an exception while registering a delivery service.
<b>Action</b>	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.1064E</b>	<b>Unable to initialize delivery interface</b>
<b>Explanation</b>	Encountered an exception while initializing the Delivery Service Manager.
<b>Action</b>	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

<b>TNS.0005.1065E</b>	<b>Unable to register delivery defaults</b>
<b>Explanation</b>	Encountered an exception while registering the built-in delivery services.
<b>Action</b>	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.1066E</b>	<b>Unable to deliver bizdoc by service</b>
<b>Explanation</b>	Encountered an exception when wm.tn.deliver:deliverByService was invoked.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception, if possible. It may be a network error beyond your control.
<b>TNS.0005.1067E</b>	<b>Error delivering bizdoc</b>
<b>Explanation</b>	Encountered an exception while delivering a document.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception, if possible. It may be a network error beyond your control.
<b>TNS.0005.1068E</b>	<b>Error getting delivery job</b>
<b>Explanation</b>	Encountered an exception while retrieving a delivery job.
<b>Action</b>	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.1069E</b>	<b>Error getting delivery job output</b>
<b>Explanation</b>	Encountered an exception while retrieving the output of a reliable delivery job.
<b>Action</b>	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.1070E</b>	<b>Error getting delivery job status</b>
<b>Explanation</b>	Encountered an exception while retrieving the status of a delivery job.
<b>Action</b>	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

---

<b>TNS.0005.1071E</b>	<b>Error removing delivery job</b>
<b>Explanation</b>	Encountered an exception while removing a reliable delivery job.
<b>Action</b>	Use the JDBC Pools page on the Integration Server Administrator to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.1072E</b>	<b>Error restarting delivery job</b>
<b>Explanation</b>	Encountered an exception while restarting a reliable delivery job.
<b>Action</b>	Use the JDBC Pools page on the Integration Server Administrator to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.1073E</b>	<b>Error getting registered delivery service {0}</b>
<b>Explanation</b>	Encountered an exception while retrieving a registered delivery service.
<b>Action</b>	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.1074E</b>	<b>Error getting registered delivery services</b>
<b>Explanation</b>	Encountered an exception while retrieving the set of registered delivery services.
<b>Action</b>	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.1075E</b>	<b>Error determining if delivery service {0} is registered</b>
<b>Explanation</b>	Encountered an exception while retrieving a named registered delivery service.
<b>Action</b>	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.1076E</b>	<b>Error refreshing service cache</b>
<b>Explanation</b>	Encountered an exception while refreshing the cache of registered delivery services.
<b>Action</b>	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

<b>TNS.0005.1077E</b>	<b>Error registering service {0}</b>
<b>Explanation</b>	Encountered an exception while registering a delivery service.
<b>Action</b>	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.1078E</b>	<b>Error removing service {0}</b>
<b>Explanation</b>	Encountered an exception while unregistering a delivery service.
<b>Action</b>	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.1081E</b>	<b>Couldn't query delivery service table</b>
<b>Explanation</b>	Encountered a SQLException while reading delivery services.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception, if possible.
<b>TNS.0005.1082E</b>	<b>Couldn't query delivery job table</b>
<b>Explanation</b>	Encountered a SQLException while reading delivery jobs.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception, if possible.
<b>TNS.0005.1083E</b>	<b>Property watt.server.smtpServer is not set</b>
<b>Explanation</b>	Cannot send e-mail messages because the system property, watt.server.smtpServer, has not been set.
<b>Action</b>	Use the Properties page of the Integration Server Administrator to supply a value for the watt.server.smtpServer property.
<b>TNS.0005.1084E</b>	<b>Receiver of document cannot be self</b>
<b>Explanation</b>	A document is being sent from this Trading Networks server and the receiver of the document is a host of Trading Network. You cannot send a document to yourself.
<b>Action</b>	Ensure that the receiver of the document is not a host of Trading Networks.
<b>TNS.0005.1085E</b>	<b>Receiver of document is not Active</b>
<b>Explanation</b>	Status of the partner profile for the receiver of the document is not in active state. Documents can only be sent to active partners.
<b>Action</b>	Ensure the receiver of the document is an active partner.

---

<b>TNS.0005.1086E</b>	<b>Unknown protocol: {0}</b>
<b>Explanation</b>	Attempted to send a document via an unknown protocol. Documents must be sent using one of the registered delivery services.
<b>Action</b>	Use a registered delivery service to send the document.
<b>TNS.0005.1087E</b>	<b>Destination info not found</b>
<b>Explanation</b>	Attempting to send a document, but the receiver's destination information cannot be found.
<b>Action</b>	Examine the document to learn the intended receiver. Make sure the receiver's profile has valid delivery method information.
<b>TNS.0005.1090E</b>	<b>Unable to initialize DeliveryStore {0}</b>
<b>Explanation</b>	Encountered an exception during initialization.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.1092E</b>	<b>Service not registered</b>
<b>Explanation</b>	Attempted to remove a delivery service that is not registered.
<b>Action</b>	Check the name of the registered delivery service you want to remove.
<b>TNS.0005.1096E</b>	<b>Delivery queue {0} refers to Delivery service {1} which is not registered.</b>
<b>Explanation</b>	In webMethods Trading Networks, during batch delivery of queued tasks, if the delivery service used is not registered and the delivery queue refers to it, this error is thrown.
<b>Action</b>	Use the webMethods Trading Networks to update the delivery queue so that it uses a valid batch delivery service.
<b>TNS.0005.1097E</b>	<b>Cannot deliver document. Receiver is not active. (DocID={0}, ReceiverD={1})</b>
<b>Explanation</b>	Queued a document for scheduled delivery, but the receiver is inactive and cannot receive documents.
<b>Action</b>	Activate the receiver's trading partner profile, if appropriate.
<b>TNS.0005.1098E</b>	<b>Unable to get document content for delivery. (DocID={0})</b>
<b>Explanation</b>	Queued a document for scheduled delivery and encountered an error while retrieving document content.
<b>Action</b>	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

<b>TNS.0005.1099E</b>	<b>Cannot register a delivery service with the same name as a built-in delivery service ({0}).</b>
<b>Explanation</b>	This name is reserved for a built-in Trading Networks delivery service.
<b>Action</b>	Change the delivery service's name.
<b>TNS.0005.1101E</b>	<b>Cannot get certificate information from security store for partner {0} in getting delivery information: {1}</b>
<b>Explanation</b>	Encountered an exception while retrieving the certificate chain and private key for a trading partner.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.1105E</b>	<b>Unable to get profile for partner {0} - {1}</b>
<b>Explanation</b>	Encountered an exception while retrieving a trading partner profile.
<b>Action</b>	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.1106E</b>	<b>Unable to get destination info for partner {0} - {1}</b>
<b>Explanation</b>	Encountered an exception while retrieving destination information from a trading partner profile in preparation for document delivery.
<b>Action</b>	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.1107E</b>	<b>Encountered error while delivering by context: {0}</b>
<b>Explanation</b>	Encountered an exception while delivering a document using an internal webMethods protocol.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception, if possible. It may be a network error beyond your control.
<b>TNS.0005.1108E</b>	<b>Unable to deliver document {0}. Delivery service [{1}] does not exist</b>
<b>Explanation</b>	Document delivery failed because the associated delivery service does not exist.
<b>Action</b>	Create the missing delivery service or specify a different delivery service.

---

<b>TNS.0005.1109</b>	<b>The document (id={0}) was not persisted. The "{1}" delivery service will not be invoked. The document will not be delivered.</b>
<b>Explanation</b>	In webMethods Trading Networks, while delivering documents, if the BizDoc is not persisted, the delivery service is not invoked and the document is not delivered.
<b>Action</b>	Contact your system administrator.
<b>TNS.0005.1115</b>	<b>Event found to be null</b>
<b>Explanation</b>	In webMethods Trading Networks, while writing routing events, if the event is found to be null, then this error is thrown.
<b>Action</b>	Contact your system administrator.
<b>TNS.0005.1117</b>	<b>Encountered error while creating TN document from service response: {0}</b>
<b>Explanation</b>	In webMethods Trading Networks, while delivering a document via WebService, if the document cannot be created from response data, this error is thrown.
<b>Action</b>	Contact your system administrator.
<b>TNS.0005.1118</b>	<b>Encountered error while adding service response to bizdoc: {0}</b>
<b>Explanation</b>	In webMethods Trading Networks, while delivering a document via WebService, if the response data cannot be added as content to the BizDoc, this error is thrown.
<b>Action</b>	Contact your system administrator.
<b>TNS.0005.2002E</b>	<b>An error occurred when this partner polled for documents on this server. The original error message was {0}.</b>
<b>Explanation</b>	An exception was thrown while polling for documents.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.2014E</b>	<b>Error polling for documents</b>
<b>Explanation</b>	An exception was thrown while polling for documents.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.2017E</b>	<b>An error occurred when trying to connect to this partner for polling. The original error was: {0}</b>
<b>Explanation</b>	In webMethods Trading Networks, during a remote checking of a partner, if the connection to the partner cannot be made, this error is thrown.
<b>Action</b>	Ensure that the partner connection information is valid and try again.

<b>TNS.0005.2018E</b>	<b>Error connecting for polling</b>
<b>Explanation</b>	An error occurred when trying to connect to this partner for polling.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception. You might need to contact your trading partner about the error.
<b>TNS.0005.2021E</b>	<b>The user account that schedules polling jobs is {0}. The account does not exist on the B2B Server.</b>
<b>Explanation</b>	In webMethods Trading Networks, during scheduling of a polling job, if the user account that starts the polling job does not exist on the B2B server, this error is thrown.
<b>Action</b>	Create a user account for the user and reload the WmTN package or restart the Integration Server.
<b>TNS.0005.2031E</b>	<b>An error occurred in the process of accepting a document polled from this partner. The original document ID was {0}. The original error message was {1}.</b>
<b>Explanation</b>	In webMethods Trading Networks, if any error occurs during the process of submitting a document locally that is polled from a remote partner, this error is thrown.
<b>Action</b>	Contact your system administrator.
<b>TNS.0005.2037E</b>	<b>Error accepting document</b>
<b>Explanation</b>	An exception was thrown while accepting a document polled from a partner.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.2052E</b>	<b>Unable to initialize TN Polling.</b>
<b>Explanation</b>	An exception was thrown during initialization.
<b>Action</b>	The exception was written to the server log. See the log for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.2053E</b>	<b>User {0} is not an administrator and attempted to accept a document (docID={1}) that does not belong to him.</b>
<b>Explanation</b>	A partner attempted to accept a pollable document; however, the partner is not the specified receiver of the document.
<b>Action</b>	Review the log message. Contact the partner identified in the log message to explain that a partner can only accept pollable documents for which that partner is the specified receiver.

---

<b>TNS.0005.2054E</b>	<b>You do not have the authority to accept this document. Only administrators may accept documents that they did not receive.</b>
<b>Explanation</b>	A partner attempted to accept a pollable document; however, the partner is not the specified receiver of the document.
<b>Action</b>	Review the log message. Contact the partner identified in the log message to explain that a partner can only accept pollable documents for which that partner is the specified receiver.
<b>TNS.0005.2055E</b>	<b>No document with an ID of {0} exists. No document accepted.</b>
<b>Explanation</b>	A partner is trying to accept a pollable document that does not exist within Trading Networks.
<b>Action</b>	Review the log message. Work with the partner specified in the log message to resolve the issue.
<b>TNS.0005.3001E</b>	<b>{0} is required.</b>
<b>Explanation</b>	A service was invoked, and a required input variable was not supplied.
<b>Action</b>	Supply a value for the specified variable.
<b>TNS.0005.3002E</b>	<b>Unable to save queue "{0}".</b>
<b>Explanation</b>	Attempt to insert queue information into the Trading Networks database failed.
<b>Action</b>	Ask your database administrator (DBA) to examine the database logs to determine the cause of the problem.
<b>TNS.0005.3003E</b>	<b>Cannot reassign tasks to a private queue.</b>
<b>Explanation</b>	Each partner might have its own private queue. Private queues are defined in the profile for a partner. A private queue can contain only tasks for the partner identified by the profile; private queues cannot contain tasks from other partners.
<b>Action</b>	You can reassign these tasks to a public queue.
<b>TNS.0005.3004E</b>	<b>Unable to remove queue "{0}".</b>
<b>Explanation</b>	Attempt to delete queue information from the Trading Networks database failed.
<b>Action</b>	Ask your database administrator (DBA) to examine the database logs to determine the cause of the problem.

<b>TNS.0005.3005E</b>	<b>Unable to update queue "{0}".</b>
<b>Explanation</b>	Attempt to update queue information in the Trading Networks database failed.
<b>Action</b>	Ask your database administrator (DBA) to examine the database logs to determine the cause of the problem.
<b>TNS.0005.3006E</b>	<b>The queue cannot be deleted because there is data that depends on it.</b>
<b>Explanation</b>	The queue cannot be deleted for one or more of the following reasons: 1) There might be tasks currently on the queue. 2) There are partner profiles and/or processing rules that refer to the queue. A list of objects that depend on the queue follow this message.
<b>Action</b>	Take one or more of the following actions: 1) If there are tasks on the queue, place it in a DRAINING state so that the queue will empty. After all tasks in the queue are processed, you can delete the queue. 2) If there are profiles and/or processing rules that refer to the queue, remove those references. After you remove the references, you can delete the queue.
<b>TNS.0005.3007E</b>	<b>There are {0} tasks on the queue.</b>
<b>Explanation</b>	The queue cannot be removed because it has tasks on it.
<b>Action</b>	Place the queue in a DRAINING state so that the queue will empty. After the tasks in the queue have been processed, you can delete it.
<b>TNS.0005.3008E</b>	<b>There are {0} partner profiles that refer to the queue.</b>
<b>Explanation</b>	The queue cannot be removed because one or more partner profiles refers to it.
<b>Action</b>	This message is followed by a list of partners whose profiles refer to the queue. Modify these profiles so they no longer refer to the queue being removed. After you remove the references, you can delete the queue.
<b>TNS.0005.3009E</b>	<b>There are {0} processing rules that refer to the queue.</b>
<b>Explanation</b>	The queue cannot be removed because one or more processing rules refers to it.
<b>Action</b>	This message is followed by a list of processing rules that refer to the queue. Modify these processing rules so they no longer refer to the queue being removed. After you remove the references, you can delete the queue.
<b>TNS.0005.3012E</b>	<b>There is no task with the supplied ID ({0}).</b>
<b>Explanation</b>	The wm.tn.queuing:updateQueuedTask service was supplied an invalid task ID.
<b>Action</b>	Supply a valid task ID.

---

<b>TNS.0005.3013E</b>	<b>updateQueuedTask may only be invoked for tasks that are currently being processed from a DeliveryQueue. This task ({0}) has a status of {1}.</b>
<b>Explanation</b>	You attempted to run the wm.tn.queuing:updateQueuedTask service for a task; however, you did not first invoke the wm.tn.queuing:getQueuedTask service.
<b>Action</b>	Be sure to use the wm.tn.queuing:getQueuedTask service to retrieve a task from a queue.
<b>TNS.0005.3018E</b>	<b>Attempted to update a DeliveryQueue that has not been registered (queue name={0}).</b>
<b>Explanation</b>	The specified queue does not exist.
<b>Action</b>	Either supply a valid queue name or use My webMethods to define the delivery queue.
<b>TNS.0005.3019E</b>	<b>status must be "success" or "fail". {0} was supplied.</b>
<b>Explanation</b>	The wm.tn.queuing:updateQueuedTask service was supplied an invalid status.
<b>Action</b>	Supply a valid status value.
<b>TNS.0005.3020E</b>	<b>Attempted to remove a DeliveryQueue that has not been registered (queue name={0}).</b>
<b>Explanation</b>	The specified queue does not exist.
<b>Action</b>	Supply a valid queue name.
<b>TNS.0005.3021E</b>	<b>Unable to decode TypeData for a DeliveryJob (ID={0}) while dequeuing from {1}</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0005.3023E</b>	<b>The scheduled delivery date/time is in the past.</b>
<b>Explanation</b>	Trading Networks cannot schedule delivery to run in the past.
<b>Action</b>	Supply a future date and time.
<b>TNS.0005.3024E</b>	<b>The delivery schedule is empty. It has been ignored.</b>
<b>Explanation</b>	The delivery queue does not have a delivery schedule. The operation has failed.
<b>Action</b>	If you receive this error while invoking a service, make sure that you are supplying a valid DeliveryQueue object that contains a DeliverySchedule. If you receive this error while using My webMethods, contact Software AG Global Support.

<b>TNS.0005.3025E</b>	<b>Delivery schedule dates must be in the format "YYYY/MM/DD" and times must be in the format "hh:mm:ss"</b>
<b>Explanation</b>	A date and/or time in the delivery schedule is invalid.
<b>Action</b>	All dates and times in the delivery schedule must be in the specified formats.
<b>TNS.0005.3027E</b>	<b>Unable to schedule delivery for queue "{0}". The pipeline for the delivery service does not contain "queue".</b>
<b>Explanation</b>	The variable "queue" was not supplied in the pipeline.
<b>Action</b>	Supply the name of the delivery queue.
<b>TNS.0005.3028E</b>	<b>The delivery schedule has no schedule type. It has been ignored.</b>
<b>Explanation</b>	The delivery schedule must have a type of "repeat", "complex", or "once".
<b>Action</b>	Set the type on the delivery schedule to a valid value.
<b>TNS.0005.3029E</b>	<b>The queue "{0}" does not exist.</b>
<b>Explanation</b>	In webMethods Trading Networks, while updating a queue, if the queue does not exist, this error is thrown.
<b>Action</b>	Ensure that the queue that is to be updated exists, and try again.
<b>TNS.0005.3037E</b>	<b>Scheduled delivery failed. No more retries.</b>
<b>Explanation</b>	The final attempt to delivery a document failed.
<b>Action</b>	See the message TRNSERV.000022.000038 for full details.
<b>TNS.0005.3038E</b>	<b>Scheduled delivery of document {0} failed. No more retries. {1}</b>
<b>Explanation</b>	The final attempt to deliver a document failed.
<b>Action</b>	See the error message for details. You might need to contact your trading partner.
<b>TNS.0005.3039E</b>	<b>The queue "{0}" has a status of "{1}". It is not accepting documents. This document will not be delivered.</b>
<b>Explanation</b>	Attempted to route a document to a delivery queue that is either disabled or draining. Queues in either of these statuses cannot accept documents.
<b>Action</b>	Either change the status of this queue or route the document to a different queue.

<b>TNS.0005.3040E</b>	<b>Unable to validate private queue/partner relationship (id={0}) because the partner could not be retrieved. The queue has been saved with a "disabled" status.</b>
<b>Explanation</b>	You can only create a private queue for a partner that has an active profile. The specified partnerID identifies a partner that does not exist or whose profile is not active.
<b>Action</b>	Perform one of the following actions: 1) Specify a different queue. 2) If the profile is not active, change its status to active.
<b>TNS.0005.3041E</b>	<b>Private queue "{0}" has a status of "{1}", but the partner's profile is not active. The queue has been saved with a "disabled" status.</b>
<b>Explanation</b>	Trading Networks attempted to route a document to a private queue that is defined for a profile that is not active. Trading Networks can only route documents to private queues belonging to active partners; it cannot route documents to private queues of inactive partners. Trading Networks has disabled the queue.
<b>Action</b>	Enable the partner by changing the profile status to active. Then enable the partner's private queue.
<b>TNS.0005.3042E</b>	<b>Delivery not scheduled from queue.</b>
<b>Explanation</b>	In webMethods Trading Networks, while scheduling delivery of documents from queues, if the queue is private and the partner is either inactive or not found, this error is thrown.
<b>Action</b>	Ensure that the partner of the private queue is available and active, and try again.
<b>TNS.0005.3044E</b>	<b>Document was not queued for delivery on queue {0}. The receiver's profile was not found. (receiverID={1}).</b>
<b>Explanation</b>	A processing rule indicated that the document should be delivered to a queue that is associated with a receiver. However, there is no profile for the receiver.
<b>Action</b>	Use My webMethods to determine who the intended receiver is. If the receiver is valid but does not have a profile, create a partner profile for the receiver. If the receiver is not valid, notify the document sender that the receiver information in the document is incorrect.
<b>TNS.0005.3045E</b>	<b>Document was not queued for delivery on queue {0}. The receiver is not active (receiverID={1}).</b>
<b>Explanation</b>	A processing rule indicated that the document should be delivered to a queue that is associated with a receiver. However, the receiver's profile is not active. Trading Networks can only route documents to active partners.
<b>Action</b>	Enable the partner by changing the profile status to active. Then enable the partner's private queue.

<b>TNS.0005.3046E</b>	<b>The queue "{0}" does not exist.</b>
<b>Explanation</b>	The wm.tn.queuing:deliverBatch service was supplied an invalid queue name.
<b>Action</b>	Supply the name of an existing queue.
<b>TNS.0005.3048E</b>	<b>The scheduled {0} is invalid. Format must be YYYY/MM/DD</b>
<b>Explanation</b>	In webMethods Trading Networks, while validating scheduling of tasks, if the format of the schedule date is invalid, this error is thrown.
<b>Action</b>	Enter the schedule date in the correct format and try again.
<b>TNS.0005.3049E</b>	<b>The scheduled {0} is invalid. Format must be hh:mm:ss</b>
<b>Explanation</b>	In webMethods Trading Networks, while validating the schedule task, if the format of the time is invalid, this error is thrown.
<b>Action</b>	Enter the schedule time in the correct format and try again.
<b>TNS.0005.3056E</b>	<b>Interval is required.</b>
<b>Explanation</b>	An interval must be specified for repeating tasks.
<b>Action</b>	Supply an interval value.
<b>TNS.0005.3057E</b>	<b>Interval is not a valid integer.</b>
<b>Explanation</b>	In webMethods Trading Networks, while validating a scheduling task, if the time interval is not a valid integer, this error is thrown.
<b>Action</b>	Enter the time interval as a valid integer and try again.
<b>TNS.0005.3058E</b>	<b>Interval must be greater than zero.</b>
<b>Explanation</b>	In webMethods Trading Networks, while validating a scheduling task, if the time interval is not greater than zero, this error is thrown.
<b>Action</b>	Enter the time interval as a valid integer greater than zero and try again.
<b>TNS.0005.3059E</b>	<b>End date/time is in the past.</b>
<b>Explanation</b>	In webMethods Trading Networks, while validating a scheduling task, if the end date/time is occurring in the past, this error is thrown.
<b>Action</b>	Enter a valid end date/time and try again.

---

<b>TNS.0005.3060E</b>	<b>End date/time is before start date/time.</b>
<b>Explanation</b>	In webMethods Trading Networks, while validating a scheduling task, if the end date/time occurs before the start date/time, this error is thrown.
<b>Action</b>	Enter the valid end date/time and try again.
<b>TNS.0005.3061E</b>	<b>Could not construct a valid timestamp from this schedule. Dates must be in YYYY/MM/DD format and times must be in hh:mm:ss format.</b>
<b>Explanation</b>	In webMethods Trading Networks, while validating the scheduling task, if the end date is not in YYYY/MM/DD format and the end time is not in hh:mm:ss format, this error is thrown.
<b>Action</b>	Ensure that the end date and time are in the correct format and try again.
<b>TNS.0005.3062E</b>	<b>A queue with this name already exists.</b>
<b>Explanation</b>	In webMethods Trading Networks, while registering a queue, if a queue with this name already exists, this error is thrown.
<b>Action</b>	Ensure to have a unique queue name and try again.
<b>TNS.0005.3063E</b>	<b>There is a task on the queue (task id={0}).</b>
<b>Explanation</b>	The queue cannot be removed because it has tasks on it.
<b>Action</b>	Place the queue in a DRAINING state so that the queue will empty. After the tasks in the queue have been processed, you can delete it.
<b>TNS.0005.3064E</b>	<b>The profile for {0} refers to the queue (partner id={1}).</b>
<b>Explanation</b>	The queue cannot be removed because one or more partner profiles refers to it.
<b>Action</b>	This message is followed by a list of partners whose profiles refer to the queue. Modify these profiles so they no longer refer to the queue being removed. After you remove the references, you can delete the queue.
<b>TNS.0005.3065E</b>	<b>The {0} processing rule refers to the queue.</b>
<b>Explanation</b>	The queue cannot be removed because one or more processing rules refers to it.
<b>Action</b>	This message is followed by a list of processing rules that refer to the queue. Modify these processing rules so they no longer refer to the queue being removed. After you remove the references, you can delete the queue.

<b>TNS.0005.3066E</b>	<b>If an end time is supplied, an end date must also be supplied.</b>
<b>Explanation</b>	In webMethods Trading Networks, while validating a scheduling task, if the delivery schedule is of complex type, and the end time is supplied but the end date is not supplied, this error is thrown.
<b>Action</b>	Ensure to also supply the end date along with the end time and try again.
<b>TNS.0005.3067</b>	<b>Unable to import partner private queue {0}. Partner profile for {1} does not exist.</b>
<b>Explanation</b>	In webMethods Trading Networks, while importing Trading Networks assets, if the partner profile for which a partner private queue is to be imported does not exist, this error is thrown.
<b>Action</b>	Ensure that the partner profile exists, and try again.
<b>TNS.0005.4002E</b>	<b>Processing recursion was detected: the processing rule {0} invoked itself, most recently with document {1}. Processing fails.</b>
<b>Explanation</b>	A processing rule recursed. Either no recursion is allowed, or recursion is allowed, and the maximum recursion level was exceeded.
<b>Action</b>	If you want a processing rule to recurse (to call itself), set the tn.recursion.max property to an appropriate value. If you do not want the processing rule to recurse, check the service that the processing rule invokes. The service is submitting a document that matches the same routing rule.
<b>TNS.0005.4004E</b>	<b>If alertPartner is not specified, neither alertContact, alertSubject nor alertMessage may be specified.</b>
<b>Explanation</b>	An invalid combination of input values was sent to wm.tn.route:create.
<b>Action</b>	If you are not supplying a value for alertPartner, do not supply a value for alertContact, alertSubject, or alertMessage.
<b>TNS.0005.4008E</b>	<b>Error sending mail: {0}</b>
<b>Explanation</b>	Encountered an exception while sending an email alert.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.4011E</b>	<b>An error occurred invoking the processing service ({2}) for this document. The original error was of type {0}; the message was {1} and the service output this pipeline: {3}</b>
<b>Explanation</b>	A processing rule invoked a service, and that service returned an error.
<b>Action</b>	Take appropriate action to resolve the problem described in the error message.

---

<b>TNS.0005.4012E</b>	<b>Error signaled in processing service</b>
<b>Explanation</b>	A processing rule invoked a service, and that service returned an error.
<b>Action</b>	See the full message (TRNSERV.000014.000012) for details.
<b>TNS.0005.4013E</b>	<b>An internal error prevented processing from finishing normally on this document. The aborted rule was {0}, and the original error message was {1}.</b>
<b>Explanation</b>	See the exception message for details.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.4014E</b>	<b>Internal processing error</b>
<b>Explanation</b>	See the full message (TRNSERV.000014.000013) for details.
<b>Action</b>	See the full message for details.
<b>TNS.0005.4017E</b>	<b>{0} loading rules</b>
<b>Explanation</b>	Encountered an exception while reading processing rules from the database.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.4023S</b>	<b>{0} saving rules</b>
<b>Explanation</b>	Encountered an exception while saving processing rules to the database. Trading Networks wrote the exception to the server log.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.4027E</b>	<b>An exception occurred invoking a processing service for document {0}. The processing service was {1}, and the original error message was: {2}.</b>
<b>Explanation</b>	A processing rule invoked a service, and that service threw an exception.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.4028E</b>	<b>An error occurred invoking the processing service {0} for this document. The original error was {1}.</b>
<b>Explanation</b>	A processing rule invoked a service, and that service threw an exception.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.

<b>TNS.0005.4029E</b>	<b>Service invoke err: {0}</b>
<b>Explanation</b>	A processing rule invoked a service, and that service threw an exception.
<b>Action</b>	See the full message for details.
<b>TNS.0005.4034E</b>	<b>Error sending via {0}</b>
<b>Explanation</b>	Error encountered.
<b>Action</b>	See the full message for details.
<b>TNS.0005.4035E</b>	<b>Fatal processing error: {0}</b>
<b>Explanation</b>	Encountered an exception while processing a document. See the exception for details.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.4038W</b>	<b>Changing the user status on document {0} generated an error. The original error message was: {1}</b>
<b>Explanation</b>	Encountered an exception while changing the status for a document. See the exception for details.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.4039E</b>	<b>Error changing status</b>
<b>Explanation</b>	Encountered an exception while changing the status for a document. See the exception for details.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.4040E</b>	<b>An error occurred sending via protocol {0}. The original error message was: {1}</b>
<b>Explanation</b>	Encountered an exception while sending a document. See the exception message for details.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.4041E</b>	<b>Error delivering document</b>
<b>Explanation</b>	Encountered an exception while sending a document.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.

---

<b>TNS.0005.4052E</b>	<b>Processing Alert Failed</b>
<b>Explanation</b>	Encountered an error while sending an email alert.
<b>Action</b>	See full message for details.
<b>TNS.0005.4053E</b>	<b>The server was unable to send email to {0} during processing. The subject of the email was {1}. The error message was: {2}.</b>
<b>Explanation</b>	Encountered an error while sending an email alert.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.4054E</b>	<b>PROCESSING ERROR: partner contact {0}/{1} is not defined</b>
<b>Explanation</b>	Processing is configured to send alerts to a specific contact type, but the partner profile does not have a contact of that type.
<b>Action</b>	Either change the processing rule to send alerts to a different contact type (or use a hard-coded email address), or create a contact of this type for the partner.
<b>TNS.0005.4055E</b>	<b>Partner {1} sent this document posing as {0}.</b>
<b>Explanation</b>	When Trading Networks receives a document, it determines the partner initiating the request based on the user account that sent the document. The partner that sent the request does not match the sender from within the document content.
<b>Action</b>	You might want to notify the partner who sent the document and/or the partner being impersonated.
<b>TNS.0005.4056E</b>	<b>Partner {1} sent document {2} posing as {0}.</b>
<b>Explanation</b>	When Trading Networks receives a document, it determines the partner initiating the request based on the user account that sent the document. The partner that sent the request does not match the sender from within the document content.
<b>Action</b>	You might want to notify the partner who sent the document and/or the partner being impersonated.
<b>TNS.0005.4057E</b>	<b>Partner ID mismatch</b>
<b>Explanation</b>	The partner who sent the document does not match the partner in the document content.
<b>Action</b>	See full message for details.

**TNS.0005.4058E      The sender of this document ({0}) has been deleted. Documents from this partner are not permitted at this time.**

**Explanation**      Trading Networks received a document from a partner whose profile was deleted. Although Trading Networks still maintains a copy of the deleted profile in its database, it will not accept documents nor process documents from the partner.

**Action**              If you do not want to accept documents from the partner, you can either ignore this error or notify the partner to stop sending documents. If you want to receive and process documents from this partner, use the `wm.tn.profile:undeleteProfile` service to reinstate the partner's profile.

**TNS.0005.4059E      The sender of document {2} ({0}) had been deleted. Documents from this partner are not permitted at this time.**

**Explanation**      Trading Networks received a document from a partner whose profile was deleted. Although Trading Networks still maintains a copy of the deleted profile in its database, it will not accept documents nor process documents from the partner.

**Action**              If you do not want to accept documents from the partner, you can either ignore this error or notify the partner to stop sending documents. If you want to receive and process documents from this partner, use the `wm.tn.profile:undeleteProfile` service to reinstate the partner's profile.

**TNS.0005.4060E      Partner deleted**

**Explanation**      Received a document from a partner whose profile was deleted.

**Action**              See full message for details.

**TNS.0005.4067E      An attempt was made to send email to the {0} contact of the Unknown partner. No email was sent.**

**Explanation**      The processing rule is configured to send an alert to a partner's contact, but Trading Networks could not identify the partner.

**Action**              Examine the document content and the Sender/Receiver queries on the document type to determine why Trading Networks could not identify the partner.

**TNS.0005.4068E      Can't send to UNKNOWN**

**Explanation**      The processing rule is configured to send an alert to a partner, but Trading Networks could not identify the partner.

**Action**              Examine the document content and the Sender/Receiver queries on the document type to determine why Trading Networks could not identify the partner.

---

<b>TNS.0005.4070E</b>	<b>Processing aborted</b>
<b>Explanation</b>	Threw a RoutingAbortedException while processing the document.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.4071E</b>	<b>The processing service, {0} aborted processing of this document. The message was {1}.</b>
<b>Explanation</b>	Threw a RoutingAbortedException while processing the document.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.4074E</b>	<b>The user that posted this document ({0}) could not be associated with a partner to check their identity.</b>
<b>Explanation</b>	Received a document from someone other than a trading partner.
<b>Action</b>	You can either ignore this error or contact the document sender. The sender is using a valid Integration Server account, but not the account associated with their profile.
<b>TNS.0005.4075E</b>	<b>The user that posted document {1} ({0}) could not be associated with a partner to check their identity.</b>
<b>Explanation</b>	Received a document from someone other than a trading partner.
<b>Action</b>	You can either ignore this error or contact the document sender. The sender is using a valid Integration Server account, but not the account associated with their profile.
<b>TNS.0005.4076E</b>	<b>No user ID</b>
<b>Explanation</b>	Received a document from someone other than a trading partner.
<b>Action</b>	You can either ignore this error or contact the document sender. The sender is using a valid Integration Server account, but not the account associated with their profile.
<b>TNS.0005.4078E</b>	<b>No email address</b>
<b>Explanation</b>	Could not determine the address to send an email alert.
<b>Action</b>	Examine the processing rule and the receiver's profile. You must specify an address either in the processing rule or the receiver's profile.
<b>TNS.0005.4079E</b>	<b>No email address was available for sending to {0} ({1}). No email was sent.</b>
<b>Explanation</b>	Could not determine the address to send an email alert.
<b>Action</b>	Examine the processing rule and the receiver's profile. You must specify an address either in the processing rule or the receiver's profile.

<b>TNS.0005.4086E</b>	<b>No SMTP server defined: check property watt.server.smtpServer</b>
<b>Explanation</b>	The processing rule is configured to send an email alert, but no email server is defined.
<b>Action</b>	Set the SMTP Server on the Settings > Logging page of the Integration Server Administrator, or directly set the watt.server.smtpServer property.
<b>TNS.0005.4087E</b>	<b>Cannot specify a Sender of {0} and also supply a specific senderId"s.</b>
<b>Explanation</b>	When invoking wm.tn.route:create, you cannot specify that the processing rule matches 'Any' sender or the 'Unknown' sender, and also supply specific senderIDs.
<b>Action</b>	Either remove "Any", "Unknown", or the specific senderIDs.
<b>TNS.0005.4089E</b>	<b>Cannot specify a DocType of {0} and also supply specific docTypeId"s.</b>
<b>Explanation</b>	When invoking wm.tn.route:create, you cannot specify that the processing rule matches 'Any' document type or the document type is 'Unknown', and also supply specific document type IDs.
<b>Action</b>	Either remove "Any", "Unknown", or the specific document type IDs.
<b>TNS.0005.4090E</b>	<b>An exception prevented the sender"s identity from being completely checked. The original exception was {0}.</b>
<b>Explanation</b>	Threw a ProfileStoreException while checking the identity of the document sender.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0005.4094E</b>	<b>The sender of this document ({0}/{1}) is in status {2}. Documents from this partner are not permitted at this time.</b>
<b>Explanation</b>	The document sender is not active. Inactive partners are not allowed to send documents to Trading Networks.
<b>Action</b>	You can ignore this error, activate this partner's profile, or notify the partner to stop sending documents.
<b>TNS.0005.4095E</b>	<b>The sender of document {3} ({0}/{1}) is in status {2}. Documents from this partner are not permitted at this time.</b>
<b>Explanation</b>	The document sender is not active. Inactive partners are not allowed to send documents to Trading Networks.
<b>Action</b>	You can ignore this error, activate this partner's profile, or notify the partner to stop sending documents.

---

<b>TNS.0005.4096E</b>	<b>Bad status</b>
<b>Explanation</b>	The document sender is not active. Inactive partners are not allowed to send documents to Trading Networks.
<b>Action</b>	You can ignore this error, activate this partner's profile, or notify the partner to stop sending documents.
<b>TNS.0005.4097E</b>	<b>An error occurred trying to send this document via {0} (intended receiver: {1}). The original error message was: {2}.</b>
<b>Explanation</b>	Encountered an exception while sending a document. See the exception message for details.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.4098E</b>	<b>An error occurred trying to send this document via {0} (sender: {1}). The original error message was: {2}.</b>
<b>Explanation</b>	Encountered an exception while sending a document. See the exception message for details.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.4099E</b>	<b>Couldn't send doc {0} via {1}: {2}</b>
<b>Explanation</b>	Encountered an exception while sending a document. See the exception message for details.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.4100E</b>	<b>An error occurred trying to fetch profile information for sending email to the {1} contact of partner {0}. The original error was: {2}</b>
<b>Explanation</b>	Unable to retrieve the partner profile while sending an email alert. See the exception message for details.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0005.4101E</b>	<b>Profile error</b>
<b>Explanation</b>	Unable to retrieve the partner profile while sending an email alert. See the exception message for details.
<b>Action</b>	Contact Software AG Global Support.

<b>TNS.0005.4102E</b>	<b>Processing aborted: {0}</b>
<b>Explanation</b>	Threw a RoutingAbortedException while processing the document.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.4104E</b>	<b>{0} is not a known document attribute.</b>
<b>Explanation</b>	The wm.tn.route:create service was supplied an invalid attribute name.
<b>Action</b>	Supply only names of existing document attributes.
<b>TNS.0005.4107E</b>	<b>No preferred protocol. Status changed to POLLABLE.</b>
<b>Explanation</b>	The processing rule was configured to send the document using the receiver's preferred protocol, but the receiver does not have a preferred protocol.
<b>Action</b>	Signify one of the receiver's delivery methods as the preferred protocol.
<b>TNS.0005.4111E</b>	<b>No profile summary was available for the sender of this document</b>
<b>Explanation</b>	Could not process the document because Trading Networks could not find a partner profile for the sender.
<b>Action</b>	Modify either the sender identification in the document or the external ID in the profile.
<b>TNS.0005.4112E</b>	<b>No profile summary was available for the sender of document {2}. The sender ID was {0}, and the sender logged in as {1}.</b>
<b>Explanation</b>	Could not process the document because Trading Networks could not find a partner profile for the sender.
<b>Action</b>	Modify either the sender identification in the document or the external ID in the profile.
<b>TNS.0005.4113E</b>	<b>No profile summary available</b>
<b>Explanation</b>	Could not process the document because Trading Networks could not find a partner profile for the sender.
<b>Action</b>	Modify either the sender identification in the document or the external ID in the profile.

---

<b>TNS.0005.4114E</b>	<b>A supplied attribute condition has an invalid combination of datatype, operator and value ({0} {1} {2}).</b>
<b>Explanation</b>	The wm.tn.route:create service was supplied an invalid attribute condition.
<b>Action</b>	Correct the attribute condition.
<b>TNS.0005.4115E</b>	<b>An invalid value was supplied for the tn.recursion.max property. No recursion of processing rules will be allowed.</b>
<b>Explanation</b>	The value of the tn.recursion.max property is not a valid number.
<b>Action</b>	Supply a valid number for this property.
<b>TNS.0005.4116E</b>	<b>Processing recursion exceeded the allowed recursion depth of {0}. The processing rule {1} invoked itself, most recently with document {2}. Processing fails.</b>
<b>Explanation</b>	One or more processing rules invoked services that resubmitted documents to Trading Networks, exceeding the recursion limit defined by the tn.recursion.max property.
<b>Action</b>	Increase the value of the tn.recursion.max property, or configure your processing rules not to resubmit documents.
<b>TNS.0005.4117E</b>	<b>Couldn't load routing schedule: {0}</b>
<b>Explanation</b>	Encountered an exception while reading the set of processing rules from the database.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.4118E</b>	<b>Couldn't save routing schedule: {0}</b>
<b>Explanation</b>	Encountered an exception while saving the set of processing rules to the database.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.4119E</b>	<b>Cannot specify a Receiver of Any and also supply a specific receiverId's.</b>
<b>Explanation</b>	When invoking the wm.tn.route:create service, you cannot specify that the processing rule matches 'Any' receiver and also supply specific receivers.
<b>Action</b>	Remove either "Any" or the specific receivers.
<b>TNS.0005.4120E</b>	<b>Cannot specify a Receiver of Unknown and also supply a specific receiverId's.</b>
<b>Explanation</b>	When invoking the wm.tn.route:create service, you cannot specify that the processing rule matches an 'Unknown' receiver and also supply specific receivers.
<b>Action</b>	Remove either "Unknown" or the specific receivers.

<b>TNS.0005.4121E</b>	<b>Cannot specify a DocType of Any and also supply specific docTypeIds.</b>
<b>Explanation</b>	When invoking the wm.tn.route:create service, you cannot specify that the processing rule matches 'Any' TN document type and also supply specific TN document types.
<b>Action</b>	Remove either "Any" or the specific TN document types.
<b>TNS.0005.4122E</b>	<b>Cannot specify a DocType of Unknown and also supply specific docTypeIds.</b>
<b>Explanation</b>	When invoking the wm.tn.route:create service, you cannot specify that the processing rule matches the 'Unknown' TN document type and also supply specific TN document types.
<b>Action</b>	Remove either "Unknown" or the specific TN document types.
<b>TNS.0005.4123E</b>	<b>If deliverUsing is "Queue for delivery", then deliveryQueue cannot be null</b>
<b>Explanation</b>	An invalid combination of input values was sent to the wm.tn.route:create service.
<b>Action</b>	Supply a value for the "deliveryQueue" variable.
<b>TNS.0005.4125E</b>	<b>Cannot queue a bizdoc for deliver that has not been persisted. This bizdoc (id={0}) has not been persisted.</b>
<b>Explanation</b>	The scheduled delivery mechanism requires that the document be saved to the database.
<b>Action</b>	Change the TN document type or processing rule to save documents of this type.
<b>TNS.0005.4130E</b>	<b>qname is required</b>
<b>Explanation</b>	Attempted to enqueue a delivery job without supplying a queue name for the "qname" parameter.
<b>Action</b>	Supply a valid queue name for the "qname" parameter.
<b>TNS.0005.4131E</b>	<b>Invalid queue name ({0}).</b>
<b>Explanation</b>	Attempted to enqueue a delivery job without supplying a queue name for the "qname" parameter.
<b>Action</b>	Supply a valid queue name for the "qname" parameter.
<b>TNS.0005.4132E</b>	<b>Receiver does not have a delivery queue.</b>
<b>Explanation</b>	The processing rule is configured to send the document to the receiver's private delivery queue, but the receiver does not have a delivery queue.
<b>Action</b>	Change the processing rule to deliver the document by a different means, or create a delivery queue for the receiver.

---

<b>TNS.0005.4133E</b>	<b>Receiver does not have a delivery queue. Document has been made POLLABLE (document id={0})</b>
<b>Explanation</b>	The processing rule is configured to send the document to the receiver's private delivery queue, but the receiver's profile does not contain a definition for a delivery queue.
<b>Action</b>	Change the processing rule to deliver the document by a different means, or update the receiver's profile to specify a delivery queue.
<b>TNS.0005.4134E</b>	<b>Receiver does not have a preferred protocol. Document has been made POLLABLE. (document id={0})</b>
<b>Explanation</b>	The processing rule is configured to send the document by the receiver's preferred delivery method, but the receiver does not have a preferred delivery method.
<b>Action</b>	Change the processing rule to deliver the document by a different means, or signify one of the delivery methods on the receiver's profile as "preferred".
<b>TNS.0005.4135E</b>	<b>Error encountered in RoutingActions.invoke(): can not clone input pipeline.</b>
<b>Explanation</b>	An internal error occurred while invoking a service to process the document.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0005.4136E</b>	<b>Unable to save document: {0}.</b>
<b>Explanation</b>	Encountered an exception while saving the document to the database.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.4138E</b>	<b>The processing rule list has been modified by another user. Added this rule to the bottom of the list. Refresh your rule list.</b>
<b>Explanation</b>	The rule list displayed on your Trading Networks Console is not the current list that resides in the database. As a result, the newly added rule is appended to the end of the rule list rather than the specific position required in the list.
<b>Action</b>	Refresh your routing rule list and move the newly added rule to the desired position.
<b>TNS.0005.4139E</b>	<b>Error encountered while inserting processing rule {0}. The exception message is : {1}.</b>
<b>Explanation</b>	Encountered an exception while inserting a processing rule.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

**TNS.0005.4140E      Error encountered while updating processing rule {0}. The rule index cannot be changed during an update operation.**

**Explanation**      You attempted to update both the contents of a processing rule and its location within the list of processing rules (its index) at the same time. You cannot make both these changes at the same time.

**Action**            Please update the rule first, and then move the rule to a new position in the rule list.

**TNS.0005.4141E      Error encountered while updating processing rule {0}. The exception message is : {1}.**

**Explanation**      Encountered an exception while updating a processing rule.

**Action**            See the exception message for details. Take appropriate action to resolve the problem described in the exception.

**TNS.0005.4142E      Processing rule update failed. Processing rule update collision detected. This rule has been modified by another user. Refresh your rule list and retry this operation.**

**Explanation**      While you were updating this processing rule, another user edited and saved the same processing rule. To prevent your changes from overwriting those made by the other user, Trading Networks did not save your changes.

**Action**            Refresh the list of processing rules and update the processing rule again.

**TNS.0005.4145S      Error encountered while deleting processing rule(s). The exception message is : {0}.**

**Explanation**      Encountered an exception while deleting processing rule(s).

**Action**            See the exception message for details. Take appropriate action to resolve the problem described in the exception.

**TNS.0005.4146E      Processing rule delete operation aborted. The processing rule list has been modified by another user. Refresh your rule list and retry this operation.**

**Explanation**      While you were deleting this processing rule, another user edited and saved the rule. So that your changes do not overwrite those made by the other user, your changes have not been saved.

**Action**            Refresh your rule list, and then delete the rule again.

**TNS.0005.4147E      Processing rule {0} does not exist.**

**Explanation**      The specified routing rule cannot be retrieved because the rule ID does not exist in the database.

**Action**            Check that the rule ID is correct, modify it if necessary, and then attempt to retrieve it again.

---

<b>TNS.0005.4148S</b>	<b>Error encountered while reading processing rules from the database. The exception message is : {0}.</b>
<b>Explanation</b>	Encountered an exception while retrieving processing rules from the database.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.4149S</b>	<b>Error encountered while moving processing rules. The exception message is : {0}.</b>
<b>Explanation</b>	Encountered an exception while moving processing rules in the rule list.
<b>Action</b>	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.4150E</b>	<b>Processing rule move operation aborted. The processing rule list has been modified by another user. Refresh your rule list and retry this operation.</b>
<b>Explanation</b>	While you were moving this processing rule, another user edited and saved the rule list. So that your changes do not overwrite those made by the other user, your changes have not been saved.
<b>Action</b>	Refresh the rule list, and then move the rule again.
<b>TNS.0005.4151E</b>	<b>Illegal move operation. The insertAt position cannot be within the range of rules to be moved.</b>
<b>Explanation</b>	The insertAt position must be outside the range of rules to be moved.
<b>Action</b>	Change the insertAt position to be outside of the range of rules to be moved.
<b>TNS.0005.4152E</b>	<b>Illegal move operation. You cannot move a non-contiguous set of rules.</b>
<b>Explanation</b>	You attempted to change the order of processing rules by moving a non-contiguous set of rules. Trading Networks does not support this type of operation.
<b>Action</b>	Define a contiguous set of rules to be moved.
<b>TNS.0005.4156E</b>	<b>Encountered an error retrieving the Profile Summary for partner ID {0}.</b>
<b>Explanation</b>	An error occurred attempting to look up the Profile Summary.
<b>Action</b>	Ensure that the partner IDs on the document being processed are valid.

**TNS.0005.4157E**      **Encountered an error while sending MAPI event to Optimize for EventMap {0} and for Sender with PartnerID {1}.**

**Explanation**      In webMethods Trading Networks, while routing a document, if a TN BAM monitoring event cannot be logged in Optimize, this error is thrown.

**Action**              Contact your system administrator.

**TNS.0005.4160E**      **The content-length ({0}) specified in handleLargeDoc is less than the length of the content ({1}) sent.**

**Explanation**      In webMethods Trading Networks, in a document transaction, while handling large documents, if the content length specified in the handleLargeDoc is less than the length of the BizDoc content, this error is thrown.

**Action**              Ensure that the content length specified in the handleLargeDoc is equal to the length of the BizDoc content and try again.

**TNS.0005.4162E**      **Routing Aborted as the Receiver is disabled.**

**Explanation**      In webMethods Trading Networks, while routing a document, if the receiver is in an inactive state, this error is thrown.

**Action**              Ensure to set the receiver to active state and try again.

**TNS.0005.4163E**      **Routing Aborted as the Receiver is deleted.**

**Explanation**      In webMethods Trading Networks, while routing a document, if the receiver is in deleted state, this error is thrown.

**Action**              Ensure to set the receiver profile is not deleted and try again.

**TNS.0005.4164E**      **Routing Aborted as the Sender is disabled.**

**Explanation**      In webMethods Trading Networks, while routing a document, if the sender is in inactive state, this error is thrown.

**Action**              Ensure to set the sender to active state and try again.

**TNS.0005.4165E**      **Routing Aborted as the Sender is deleted.**

**Explanation**      In webMethods Trading Networks, while routing a document, if the sender is deleted, this error is thrown.

**Action**              Ensure to set the sender profile is not deleted and try again.

---

<b>TNS.0005.4166E</b>	<b>The processing service aborted processing of this document. The message was {0}.</b>
<b>Explanation</b>	In webMethods Trading Networks, while routing a document, if an error occurs in processing the document, this error is thrown.
<b>Action</b>	Contact your system administrator.
<b>TNS.0005.4167E</b>	<b>Posting of BAM events failed because of following errors - {0}.</b>
<b>Explanation</b>	In webMethods Trading Networks, if any error occurs while posting BAM events, this error is thrown.
<b>Action</b>	Contact your system administrator.
<b>TNS.0005.5002E</b>	<b>Delivery service for {0} failed with a status of {1} and status message of {2}</b>
<b>Explanation</b>	Unable to deliver the document, possibly due to a problem with the network or the destination server.
<b>Action</b>	Verify that your server has network connectivity. If a problem exists with the destination server, contact the person responsible for that server.
<b>TNS.0005.5004E</b>	<b>Unable to get output for task {0} - Task has not finished. Status is {1}</b>
<b>Explanation</b>	The task was still executing when the request for output expired.
<b>Action</b>	Request the output again.
<b>TNS.0005.5005E</b>	<b>Unable to refresh {0} cache on server {1} - {2}</b>
<b>Explanation</b>	A cache could not be refreshed, probably due to a database problem.
<b>Action</b>	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. Verify that your database is successfully processing requests.
<b>TNS.0005.5007E</b>	<b>Unable to remove task {0} - Does not exist</b>
<b>Explanation</b>	An invalid task ID was supplied.
<b>Action</b>	Supply a valid task ID.
<b>TNS.0005.5011S</b>	<b>Disabling reliable task manager at {0} - Fatal error: {1}</b>
<b>Explanation</b>	Encountered an exception that requires the task manager to shut down.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.

<b>TNS.0005.5013W</b>	<b>Unable to restart task {0} upon initialization</b>
<b>Explanation</b>	The task status could not be updated to "Pending" in the database.
<b>Action</b>	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. Verify that your database is successfully processing requests.
<b>TNS.0005.5015E</b>	<b>Unable to persist task {0}</b>
<b>Explanation</b>	Encountered an exception while saving the task to the database.
<b>Action</b>	See the full message (TRNSERV.000015.000089) for details.
<b>TNS.0005.5019E</b>	<b>Task {0} unable to move to server {1} - {2}</b>
<b>Explanation</b>	Task has already completed. Status is "Done".
<b>Action</b>	No action required.
<b>TNS.0005.5020E</b>	<b>Unable to refresh {0} cache - {1}</b>
<b>Explanation</b>	See the exception message for details.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.5025E</b>	<b>Task {0} failed, status changed to {1}</b>
<b>Explanation</b>	The task has failed. No more retries.
<b>Action</b>	See full message (TRNSERV.000015.000036) for details.
<b>TNS.0005.5026E</b>	<b>Unable to init task manager for server {0} - {1}</b>
<b>Explanation</b>	The task manager could not be initialized, probably due to a database problem.
<b>Action</b>	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. Verify that your database is successfully processing requests.
<b>TNS.0005.5031E</b>	<b>Error invoking service {0} - message: {1} - stacktrace: {2}</b>
<b>Explanation</b>	The task manager invoked a service to process a document, and that service threw an exception.
<b>Action</b>	See the exception message for details. Correct the invoked service to handle the exception condition.

---

<b>TNS.0005.5036E</b>	<b>Task {0} failed with no more retries available. Reason for failure - {1}</b>
<b>Explanation</b>	See the status message for details.
<b>Action</b>	If the failure is due to an error on another server, contact the person responsible for that server.
<b>TNS.0005.5037E</b>	<b>Unable to restart task {0} - {1}</b>
<b>Explanation</b>	The task status is neither "Failed" nor "Stopped", so the task cannot be restarted.
<b>Action</b>	No action necessary.
<b>TNS.0005.5039E</b>	<b>Unable to shut down the task manager.</b>
<b>Explanation</b>	The wm.tn.task:shutdown service was unable to stop the task manager. See the nested exception for details.
<b>Action</b>	Take appropriate action to resolve the problem described in the nested exception.
<b>TNS.0005.5042E</b>	<b>Unable to initialize task manager.</b>
<b>Explanation</b>	The wm.tn.task:init service was unable to start the task manager. See the nested exception for details.
<b>Action</b>	Take appropriate action to resolve the problem described in the nested exception.
<b>TNS.0005.5043E</b>	<b>Unable to reset task manager.</b>
<b>Explanation</b>	The wm.tn.task:restart service was unable to restart the task manager. See the nested exception for details.
<b>Action</b>	Take appropriate action to resolve the problem described in the nested exception.
<b>TNS.0005.5044E</b>	<b>Unable to retrieve tasks.</b>
<b>Explanation</b>	The wm.tn.task:getTasks service was unable to get tasks from the task manager. See the nested exception for details.
<b>Action</b>	Take appropriate action to resolve the problem described in the nested exception.
<b>TNS.0005.5045E</b>	<b>Unable to retrieve task {0}.</b>
<b>Explanation</b>	The wm.tn.task:getTask service was unable to get a task from the task manager. See the nested exception for details.
<b>Action</b>	Take appropriate action to resolve the problem described in the nested exception.

<b>TNS.0005.5046E</b>	<b>Unable to get output for task {0}.</b>
<b>Explanation</b>	The wm.tn.task:getTaskOutput service was unable to get output for a task. See the nested exception for details.
<b>Action</b>	Take appropriate action to resolve the problem described in the nested exception.
<b>TNS.0005.5047E</b>	<b>Unable to get status for task {0}.</b>
<b>Explanation</b>	The wm.tn.task:getTaskStatus service was unable to get the status of a task. See the nested exception for details.
<b>Action</b>	Take appropriate action to resolve the problem described in the nested exception.
<b>TNS.0005.5048E</b>	<b>Unable to change server for task {0}.</b>
<b>Explanation</b>	The wm.tn.task:changeServerForTask service was unable to move a task from one server to another. See the nested exception for details.
<b>Action</b>	Take appropriate action to resolve the problem described in the nested exception.
<b>TNS.0005.5049E</b>	<b>Unable to remove task {0}.</b>
<b>Explanation</b>	The wm.tn.task:removeTask service was unable to remove a task from the task manager. See the nested exception for details.
<b>Action</b>	Take appropriate action to resolve the problem described in the nested exception.
<b>TNS.0005.5050E</b>	<b>Unable to restart task {0}.</b>
<b>Explanation</b>	The wm.tn.task:restartTask service was unable to restart a task in the task manager. See the nested exception for details.
<b>Action</b>	Take appropriate action to resolve the problem described in the nested exception.
<b>TNS.0005.5051E</b>	<b>Unable to stop task {0}.</b>
<b>Explanation</b>	The wm.tn.task:stopTask service was unable to stop a task in the task manager. See the nested exception for details.
<b>Action</b>	Take appropriate action to resolve the problem described in the nested exception.
<b>TNS.0005.5052E</b>	<b>Unable to move task {0} to server {1}. Task does not exist.</b>
<b>Explanation</b>	An invalid task ID was supplied.
<b>Action</b>	Supply a valid task ID.

---

<b>TNS.0005.5053E</b>	<b>Unable to move task {0} to server {1}. Task has completed.</b>
<b>Explanation</b>	Task status is "Done". Cannot move a completed task.
<b>Action</b>	No action necessary.
<b>TNS.0005.5054E</b>	<b>Unable to move task {0} to server {1}. Could not "ping" server: {2}</b>
<b>Explanation</b>	Invoked the wm.server:ping service on the other server, and it threw an exception.
<b>Action</b>	Take appropriate action to resolve the problem on the other server as described in the exception.
<b>TNS.0005.5055E</b>	<b>Unable to move task {0} to server {1}. Server {2} is up, but the task has not failed.</b>
<b>Explanation</b>	The server that created this task is running. Therefore, the task cannot be moved because the task status is neither "Failed" nor "Stopped".
<b>Action</b>	No action necessary.
<b>TNS.0005.5056E</b>	<b>Unable to move task {0} to server {1}. Server {2} is down, but the task is done.</b>
<b>Explanation</b>	Task status is "Done". Cannot move a completed task.
<b>Action</b>	No action necessary.
<b>TNS.0005.5057E</b>	<b>Unable to stop task {0}. Job has completed.</b>
<b>Explanation</b>	Cannot stop a completed task.
<b>Action</b>	No action necessary.
<b>TNS.0005.5058E</b>	<b>Unable to stop task {0}. Job does not exist.</b>
<b>Explanation</b>	An invalid task ID was supplied.
<b>Action</b>	Supply a valid task ID.
<b>TNS.0005.5060E</b>	<b>Delivery Job Manager error: task {0} is not NEW.</b>
<b>Explanation</b>	Cannot start a task that does not have a "New" status.
<b>Action</b>	No action necessary. Task has already started.
<b>TNS.0005.5061E</b>	<b>Delivery Job Manager error with task {0}. {1}</b>
<b>Explanation</b>	Encountered an exception while writing to the database. See the exception message for details.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.

<b>TNS.0005.5062E</b>	<b>Task {0} unable to restart. Does not exist.</b>
<b>Explanation</b>	An invalid task ID was supplied.
<b>Action</b>	Supply a valid task ID.
<b>TNS.0005.5064E</b>	<b>Unable to remove task {0}. {1}</b>
<b>Explanation</b>	Encountered an exception while writing to the database. See the exception message for details.
<b>Action</b>	Take appropriate action to resolve the problem described in the exception.
<b>TNS.0005.5065E</b>	<b>Cannot get job output. Job does not exist.</b>
<b>Explanation</b>	An invalid task ID was supplied.
<b>Action</b>	Supply a valid task ID.
<b>TNS.0005.5066E</b>	<b>Unable to initialize task manager. ServerId is null.</b>
<b>Explanation</b>	Unable to determine server ID.
<b>Action</b>	Supply a value for the watt.net.localhost property in the server.cnf file on the Integration Server.
<b>TNS.0005.5068E</b>	<b>Unable to delete tasks. There are {0} active jobs in the list of jobs to be deleted. Stop the active jobs and retry</b>
<b>Explanation</b>	Cannot delete active tasks.
<b>Action</b>	If you want to delete tasks that are active, stop them first.
<b>TNS.0005.5069E</b>	<b>Unable to get task</b>
<b>Explanation</b>	The wm.tn.route:getTask service can only retrieve tasks that are service execution tasks. A taskID of a delivery task was supplied.
<b>Action</b>	Request only service execution tasks from the wm.tn.route:getTask service.
<b>TNS.0005.5070E</b>	<b>Error getting task</b>
<b>Explanation</b>	The wm.tn.route:getTask service encountered an exception while retrieving a task. See the nested exception for details.
<b>Action</b>	Take appropriate action to resolve the problem described in the nested exception.

<b>TNS.0005.5072E</b>	<b>Unable to restart queued task (id={0}). Its delivery queue no longer exists. You can resubmit the document to process it again.</b>
<b>Explanation</b>	The delivery queue for this document has been deleted. Cannot be requeued.
<b>Action</b>	Verify that the processing rule that handles this document is configured to use a valid delivery queue. Resubmit the document.
<b>TNS.0005.5081E</b>	<b>Error invoking service, {0} - Service did not return valid output</b>
<b>Explanation</b>	The task manager invoked a service to process a document. The output of the service did not conform to the expected format.
<b>Action</b>	If this is a delivery service, make sure the output matches the <code>wm.tn.rec:DeliveryServiceOutput</code> IS document type. If this is a service invoked by a service execution task, make sure the output matches the <code>wm.tn.rec:reliableServiceOutput</code> IS document type.
<b>TNS.0005.5082E</b>	<b>ERROR: Unable to update task {0} due to database error : {1}. Since task update retry is turned off, manual correction is required. Please correct the database errors and manually update the task using the additional task details provided. Additional Details of this task : Task ID={2}; DocID={3}; TaskStatus={4}; Retries={5}; TransportStatus={6}; TransportStatusMessage={7}; TransportTime={8}</b>
<b>Explanation</b>	Could not update the task. See exception message for details.
<b>Action</b>	Manually update the task in My webMethods using the details provided in the message.
<b>TNS.0005.5089E</b>	<b>ERROR: Unable to update task {0} due to IOException : {1}. Task update will continue to fail until this exception is rectified. Until this error is rectified, manual correction is required. Manually update the task using the additional task details provided. Additional Details of this task : Task ID={2}; DocID={3}; TaskStatus={4}; Retries={5}; TransportStatus={6}; TransportStatusMessage={7}; TransportTime={8}</b>
<b>Explanation</b>	Could not update the task. See exception message for details.
<b>Action</b>	Manually update the task in My webMethods using the details provided in the message.
<b>TNS.0005.5091S</b>	<b>TN Job Manager sweep time property <code>tn.task.sweepTime</code> contains ({0}), which is not a numeric value. Using the default value 300 seconds</b>
<b>Explanation</b>	The <code>tn.task.sweepTime</code> property contains an invalid value.
<b>Action</b>	Supply a valid numeric value.

<b>TNS.0005.5094E</b>	<b>Task {0} failed at {1}: Probable reason for failure - {2}. {3} more retries left.</b>
<b>Explanation</b>	In webMethods Trading Networks, if any error occurs while disabling the delivery for a partner, this error is thrown.
<b>Action</b>	Contact your system administrator.
<b>TNS.0006.1001E</b>	<b>Cannot setIData for CertificateData because the supplied data is null.</b>
<b>Explanation</b>	The setIData method on a CertificateData object passed a null IData object.
<b>Action</b>	If your code is calling CertificateData.setIData, supply an IData object that is not null. If it is not your code that is calling this method, contact Software AG Global Support.
<b>TNS.0006.1002E</b>	<b>Cannot setIData for CertificateData.</b>
<b>Explanation</b>	The setIData method on a CertificateData object was not successful.
<b>Action</b>	If Integration Server logging is set to logging level 4 or higher, the exception was written to the server log. See the server log for more information. Take the appropriate action to resolve the problem described in the exception.
<b>TNS.0006.1003S</b>	<b>Certificate provider Entrust/IAIK was not found, so Trading Networks cannot convert byte[] to java.security.cert.X509Certificate. Please ensure that entrust jar files are in the Integration Server's classpath.</b>
<b>Explanation</b>	The Entrust jar files are missing from the Integration Server's classpath.
<b>Action</b>	Place the Entrust jar files in the Integration Server's classpath. If you need assistance, contact Software AG Global support.
<b>TNS.0006.1004E</b>	<b>CertificateException encountered; Trading Networks cannot convert byte[] to java.security.cert.X509Certificat.</b>
<b>Explanation</b>	Trading Networks encountered a certificateException when attempting to convert a byte array to a java.security.cert.X509Certificat.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, the exception was written to the server log. See the server log for details. Take the appropriate action to resolve the problem described in the exception.
<b>TNS.0006.1005E</b>	<b>Cannot convert byte[][] to X509Certificate[], exception encountered at index {0}.</b>
<b>Explanation</b>	Trading Networks could not create a certificate chain from the bytes. Trading Networks encountered the error at <zeroBasedIndexNum> certificate.
<b>Action</b>	Check the byte array to ensure that it is in the correct format.

---

<b>TNS.0006.1006E</b>	<b>Cannot convert byte[] to java.security.PrivateKey.</b>
<b>Explanation</b>	Trading Networks could not create a private key object from bytes.
<b>Action</b>	Check the byte array to ensure that it is in the correct format.
<b>TNS.0006.1007E</b>	<b>Cannot convert X509Certificate[] to byte[][], CertificateEncodingException encountered at index {0}. Please verify that the certificate is valid.</b>
<b>Explanation</b>	The certificate chain is not valid.
<b>Action</b>	Provide a valid certificate chain.
<b>TNS.0006.1008E</b>	<b>Cannot convert PKCS7 formatted byte[] into .der formatted byte[][].</b>
<b>Explanation</b>	The PKCS7-formatted bytes are not valid.
<b>Action</b>	Check the byte array to ensure that it is in the correct format. Provide a valid byte array.
<b>TNS.0006.1009E</b>	<b>Cannot load certificate from null File. Please supply a valid File.</b>
<b>Explanation</b>	The supplied certificate file is null.
<b>Action</b>	Supply a certificate file that is not null.
<b>TNS.0006.1010S</b>	<b>Certificate provider Entrust/IAIK not found, so Trading Networks cannot load java.security.cert.X509Certificate from file &lt;filename&gt;. Ensure that entrust jar files are in the Integration Server's classpath.</b>
<b>Explanation</b>	The Entrust jar files are missing from the Integration Server's classpath.
<b>Action</b>	Place the Entrust jar files in the Integration Server's classpath. If you need assistance, contact Software AG Global Support.
<b>TNS.0006.1011E</b>	<b>CertificateException encountered getting certificate from file {0}.</b>
<b>Explanation</b>	An error occurred while attempting to load certificates from the specified file.
<b>Action</b>	Check the certificate file to ensure that it is in the correct format.
<b>TNS.0006.1012E</b>	<b>Cannot load private key from null File.</b>
<b>Explanation</b>	Trading Networks attempted to load the private key from a file; however, the file is null.
<b>Action</b>	Supply a private key file that is not null.

<b>TNS.0006.1013E</b>	<b>IOException encountered loading RSA private key from file {0}.</b>
<b>Explanation</b>	An error occurred while the server attempted to load a private key from the specified file.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem described in the exception.
<b>TNS.0006.1014E</b>	<b>InvalidKeyException encountered loading RSA private key from file {0}.</b>
<b>Explanation</b>	An error occurred while the server attempted to load a private key from the specified file.
<b>Action</b>	Check the private key file to ensure that it is in the correct format.
<b>TNS.0006.1015E</b>	<b>Cannot determine whether the certificate is self-signed because the certificate byte[] is null.</b>
<b>Explanation</b>	The supplied certificate byte array is null.
<b>Action</b>	Supply a non-null certificate byte array.
<b>TNS.0006.1016E</b>	<b>Cannot determine whether the certificate is self-signed because both the subject and issuer are null.</b>
<b>Explanation</b>	The supplied certificate is not in a valid format. Both the subject and issuer are null.
<b>Action</b>	Supply a valid certificate.
<b>TNS.0006.1017E</b>	<b>Cannot determine whether the certificate is self-signed because the certificate is null.</b>
<b>Explanation</b>	The supplied certificate is null.
<b>Action</b>	Supply a non-null certificate.
<b>TNS.0006.1018E</b>	<b>Integration Server's certificate file {0} not found.</b>
<b>Explanation</b>	Trading Networks could not find the specified file that contains the Integration Server's client certificate.
<b>Action</b>	Specify a file that contains a client certificate for the Integration Server.

---

<b>TNS.0006.1019E</b>	<b>Integration Server's CA certificate file {0} not found.</b>
<b>Explanation</b>	Trading Networks could not find the specified file that contains the Integration Server's CA certificate.
<b>Action</b>	Specify a file that contains the Integration Server's CA certificate.
<b>TNS.0006.1020E</b>	<b>IOException encountered when retrieving the Integration Server's private key from {0}.</b>
<b>Explanation</b>	IOException thrown when Trading Networks was attempting to retrieve the Integration Server's private key from the specified file.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem described in the exception.
<b>TNS.0006.1021E</b>	<b>InvalidKeyException encountered when retrieving the Integration Server's private key from {0}.</b>
<b>Explanation</b>	An error occurred when Trading Networks was attempting to retrieve the Integration Server's private key from the specified file.
<b>Action</b>	Specify a file that contains a valid private key for the Integration Server.
<b>TNS.0006.1022E</b>	<b>Certificate chain bytes cannot be null or zero length.</b>
<b>Explanation</b>	The certificate chainBytes parameter is either null or has a length of zero.
<b>Action</b>	Supply a valid certificate chain.
<b>TNS.0006.1023E</b>	<b>Certificate chain contains a single certificate, and that certificate is not self-signed.</b>
<b>Explanation</b>	The certificate chain is not valid. The certificate chain contains only one certificate, and that certificate is not self-signed. When you are not using a self-signed certificate, a certificate chain must include a certificate and its corresponding CA certificate(s).
<b>Action</b>	Supply a valid certificate chain. That is a single self-signed certificate or a certificate and its corresponding CA certificates.
<b>TNS.0006.1024E</b>	<b>Entrust cannot verify the certificate chain: {0}</b>
<b>Explanation</b>	Entrust could not verify the certificate chain.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take appropriate action to resolve the problem.

<b>TNS.0006.1027E</b>	<b>Cannot determine whether to trust the sign/verify certificate because there is no Enterprise profile.</b>
<b>Explanation</b>	Trading Networks cannot determine whether to trust the sign/verify certificate because there is no Enterprise profile.
<b>Action</b>	Create an Enterprise profile. For information about creating profiles, see the Trading Networks documentation.
<b>TNS.0006.1028E</b>	<b>Cannot set sign/verify certificate for receiver, Enterprise, because a CertificateException was encountered when determining whether the Integration Server trusts the certificate chain.</b>
<b>Explanation</b>	Before setting the sign/verify certificates that are specified in the Enterprise profile, Trading Networks ensures that the Integration Server trusts the certificates. A CertificateException was thrown when determining whether the Integration Server trusts the certificates.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take appropriate action to resolve the problem.
<b>TNS.0006.1029W</b>	<b>Cannot set sign/verify certificate for receiver, Enterprise, because the Integration Server is not set up to trust the certificate specified in the Enterprise profile.</b>
<b>Explanation</b>	Before setting the sign/verify certificate that is specified in the Enterprise profile, Trading Networks ensures that the Integration Server trusts the certificate. The certificate supplied in the Enterprise profile is not among the certificates that the Integration Server trusts.
<b>Action</b>	Add this certificate to the Integration Server's directory of trusted certificates.
<b>TNS.0006.1031E</b>	<b>SQLException encountered when setting certificate data for partner {0}; error message is {1}.</b>
<b>Explanation</b>	An error occurred when Trading Networks attempted to set the certificate data for the partner with the specified partner ID.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
<b>TNS.0006.1032E</b>	<b>SQLException encountered when retrieving certificate data for partner {0}; error message is {1}.</b>
<b>Explanation</b>	An error occurred when Trading Networks attempted to retrieve the certificate data for the partner with the specified partner ID.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem described in the exception.

<b>TNS.0006.1035E</b>	<b>Cannot setIData() for CertData: CertData is null.</b>
<b>Explanation</b>	The setIData method on a CertData object passed a null IData object.
<b>Action</b>	If your code is calling CertData.setIData, supply a non-null IData object. If it is not your code that is calling this method, contact Software AG Global Support.
<b>TNS.0006.1036E</b>	<b>EXMLException encountered in CertData.setIData().</b>
<b>Explanation</b>	com.wm.app.tn.err.EXMLException was thrown in the setIData() method.
<b>Action</b>	If your code is calling CertData.setIData, check the server log for a stack trace. Take the appropriate action to resolve the problem described in the exception. If it is not your code that is calling this method, contact Software AG Global Support.
<b>TNS.0006.1037E</b>	<b>Cannot get expiration date for node certificate.</b>
<b>Explanation</b>	The certificate does not have expiration date information.
<b>Action</b>	Ensure that the certificate is in a valid format.
<b>TNS.0006.1038E</b>	<b>Cannot convert byte array to java.lang.PrivateKey.</b>
<b>Explanation</b>	Trading Networks could not convert the byte array because it is corrupted.
<b>Action</b>	Ensure that the byte array in the private key file is in a valid format.
<b>TNS.0006.1039E</b>	<b>Cannot set illegal usage {0} for CertData.</b>
<b>Explanation</b>	The CertData object contains a certificate usage parameter that is not legal.
<b>Action</b>	Ensure the certificate usage parameter in the CertData object has one of the following values: "sign", "decrypt", or "ssl".
<b>TNS.0006.1040E</b>	<b>Cannot insert CertData into database, CertData is null.</b>
<b>Explanation</b>	The CertData object is null.
<b>Action</b>	Supply a non-null CertData object.
<b>TNS.0006.1041E</b>	<b>Cannot insert CertData into database because data already exists for supplied owner={0}, partner={1} and usage={2}.</b>
<b>Explanation</b>	You attempted to add certificate information for the specified owner/partner/usage combination. However, there is already certificate information for this owner/partner/usage combination in the Trading Networks database.
<b>Action</b>	If you want to update the certificate information for the specified owner/partner/usage combination, use the update operation instead of insert operation. Otherwise, specify a unique owner/partner/usage combination that does not already exist in the Trading Networks database.

<b>TNS.0006.1042E</b>	<b>Error inserting CertData into the database; update row count is not 1.</b>
<b>Explanation</b>	Trading Networks encountered a database error when performing the insert operation.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1043E</b>	<b>Error inserting CertData into the database; IOException encountered encoding data into binary format.</b>
<b>Explanation</b>	Trading Networks encountered an error when performing the insert operation; an IOException was thrown when encoding data into binary format.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1044E</b>	<b>Error inserting CertData into the database; SQLException encountered with the error message {0}.</b>
<b>Explanation</b>	An SQLException occurred while Trading Networks was attempting to perform a database insert operation.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1045E</b>	<b>Cannot update CertData because the supplied CertData object is null.</b>
<b>Explanation</b>	Trading Networks was attempting to perform a database update operation to update certificate information. However, the supplied CertData object that Trading Networks is to use to update the existing certificate information is null. As a result, Trading Networks cannot perform the database update operation.
<b>Action</b>	Supply a non-null CertData object.
<b>TNS.0006.1046E</b>	<b>Cannot update CertData because the supplied CertID is null.</b>
<b>Explanation</b>	Trading Networks is not able to update the certificate information because the supplied unique identifier, CertID, is null.
<b>Action</b>	Supply a non-null CertID.

---

<b>TNS.0006.1047E</b>	<b>Cannot update CertData because the specified CertID, {0} does not match the CertID that Trading Networks has for the supplied owner/partner/usage.</b>
<b>Explanation</b>	You attempted to update certificate information for the specified owner/partner/usage combination. However, the supplied CertID does not match CertID that Trading Networks has for this owner/partner/usage combination.
<b>Action</b>	Retrieve the correct CertID for the owner/partner/usage combination from database, and issue the request again. This time specify the correct CertID for the owner/partner/usage combination.
<b>TNS.0006.1048E</b>	<b>Error updating CertData; the update count from the update operation is not 1.</b>
<b>Explanation</b>	Trading Networks encountered a database error when performing the update operation.
<b>Action</b>	If the Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1049E</b>	<b>Error updating CertData in the database; IOException encountered encoding data into binary format.</b>
<b>Explanation</b>	Trading Networks encountered an error when performing the update operation; an IOException was thrown when encoding data into binary format.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1050E</b>	<b>Error updating CertData in the database; SQLException encountered with the error message {0}.</b>
<b>Explanation</b>	An SQLException occurred when Trading Networks was attempting to perform a database update operation.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1051E</b>	<b>Cannot delete CertData because the supplied CertID is null.</b>
<b>Explanation</b>	Trading Networks is not able to delete the certificate information because the supplied unique identifier, CertID, is null.
<b>Action</b>	Supply a non-null CertID.

<b>TNS.0006.1052E</b>	<b>Error deleting CertData; the delete count from the delete operation is not 1.</b>
<b>Explanation</b>	Trading Networks encountered a database error when performing the delete operation.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1053E</b>	<b>Error deleting CertData from the database; SQLException encountered with the error message {0}.</b>
<b>Explanation</b>	An SQLException was thrown when Trading Networks was attempting to perform a database delete operation.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1054E</b>	<b>Cannot construct new CertData from SecurityOps.getCertificateData().</b>
<b>Explanation</b>	Internal error
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0006.1055E</b>	<b>Error selecting CertData for ownerId={0}, partnerId={1}, usage={2}; IOException encountered decoding bytes to IData.</b>
<b>Explanation</b>	When Trading Networks was attempting to select CertData for the owner/partner/usage combination, an IOException was thrown when decoding bytes to IData.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1056E</b>	<b>Error selecting CertData for ownerId={0}, partnerId={1}, usage={2}; SQLException encountered with the error message {3}.</b>
<b>Explanation</b>	An SQLException occurred while Trading Networks was attempting select CertData for the owner/partner/usage combination.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

---

<b>TNS.0006.1057E</b>	<b>Cannot construct new CertData from SecurityOps.getCertificateDataByCertID().</b>
<b>Explanation</b>	Internal error
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0006.1058E</b>	<b>Error selecting CertData for CertId=&lt;certID&gt;; IOException encountered decoding bytes to IData.</b>
<b>Explanation</b>	When Trading Networks was attempting to select CertData with the specified CertID, an IOException was thrown when decoding bytes to IData.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1059E</b>	<b>Error selecting CertData for CertId={0}; SQLException encountered with the error message {1}.</b>
<b>Explanation</b>	An SQLException occurred while Trading Networks was attempting select CertData with the specified CertID.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1060E</b>	<b>Cannot construct new CertData from SecurityOps.getCertificateDataForOwner().</b>
<b>Explanation</b>	Internal error
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0006.1061E</b>	<b>Error selecting CertData for ownerId={0}; IOException encountered decoding bytes to IData.</b>
<b>Explanation</b>	When Trading Networks was attempting to select CertData for the specified owner, an IOException was thrown while decoding bytes to IData.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1062E</b>	<b>Error selecting CertData for ownerId={0}; SQLException encountered with the error message {1}.</b>
<b>Explanation</b>	An SQLException occurred while Trading Networks was attempting to select CertData for the specified owner.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

<b>TNS.0006.1063E</b>	<b>Cannot search certificate data because the expiration date is null.</b>
<b>Explanation</b>	The certificate expiration date search criterion is null.
<b>Action</b>	Supply a valid certificate expiration date for this search criterion.
<b>TNS.0006.1064E</b>	<b>Cannot construct new CertData from SecurityOps.getCertificateDataForUpdate().</b>
<b>Explanation</b>	Internal error
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0006.1065E</b>	<b>Error selecting CertData for ownerId={0} and expDate={1}; IOException encountered decoding bytes to IData.</b>
<b>Explanation</b>	While Trading Networks was attempting to select CertData for the specified owner and with the specified expiration date, an IOException was thrown when decoding bytes to IData.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1066E</b>	<b>Error selecting CertData for ownerId={0} and expDate={1}; SQLException encountered with the error message {2}.</b>
<b>Explanation</b>	An SQLException occurred while Trading Networks was attempting to select CertData for the specified owner and with the specified expiration date.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1067E</b>	<b>Cannot construct new CertData from SecurityOps.getCertificateDataForPartnerAndUsage().</b>
<b>Explanation</b>	Internal error
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0006.1068E</b>	<b>Error selecting CertData for partnerId={0} with usage={1}; IOException encountered decoding bytes to IData.</b>
<b>Explanation</b>	While Trading Networks was attempting to select CertData for the specified partner and with the specified certificate usage, an IOException was thrown when decoding bytes to IData.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

<b>TNS.0006.1069E</b>	<b>Error selecting CertData for partnerId={0} with usage={1}; SQLException encountered with the error message {2}.</b>
<b>Explanation</b>	An SQLException occurred while Trading Networks was attempting to select CertData for the specified partner and with the specified certificate usage.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1070E</b>	<b>Cannot get profile store or profile summary list, so Trading Networks cannot migrate certificates.</b>
<b>Explanation</b>	An exception was thrown while retrieving profile data.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1071W</b>	<b>Cannot get partner's ({0}) profile data; skip migrating this partner's certificate set.</b>
<b>Explanation</b>	Trading Networks was not able to find profile data for the partner with the specified partner ID. As a result, Trading Networks cannot migrate this partners certificate set.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0006.1074E</b>	<b>Error loading partner's ({0}) certificate; skip migrating this partner's certificate set.</b>
<b>Explanation</b>	An exception occurred while loading certificate data for the partner with the specified partner ID. As a result, Trading Networks cannot migrate this partner's certificate set.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1075E</b>	<b>Cannot migrate partner's ({0}) certificate set because the certificate is null.</b>
<b>Explanation</b>	While Trading Networks was attempting to migrate the specified partner's certificate set, it encountered a null certificate. As a result, Trading Networks cannot migrate the certificate set.
<b>Action</b>	Supply a valid, non-null certificate.
<b>TNS.0006.1077E</b>	<b>Error loading partner's ({0}) CACertificate; skip migrating this partner's certificate set.</b>
<b>Explanation</b>	An exception was thrown while loading certificate data for the partner with the specified partner ID. As a result, Trading Networks cannot migrate this partner's certificate set.

**Action** If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

**TNS.0006.1078E** **Cannot migrate partner's ({0}) certificate set because a CA certificate is null.**

**Explanation** While Trading Networks was attempting to migrate the specified partner's certificate set, it encountered a null CA certificate. As a result, Trading Networks cannot migrate the certificate set.

**Action** Supply a valid CA certificate.

**TNS.0006.1079E** **Error loading partner's ({0}) private key; skip migrating this partner's certificate set.**

**Explanation** An exception occurred while loading the private key for the partner with the specified partner ID. As a result, Trading Networks cannot migrate this partner's certificate set.

**Action** If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

**TNS.0006.1080E** **Cannot migrate partner's ({0}) certificate set because the private key is null.**

**Explanation** The private key is null. When Trading Networks was attempting to migrate the specified partner's certificate set, it encountered a null private key. As a result, Trading Networks cannot migrate the certificate set.

**Action** If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

**TNS.0006.1081E** **Error adding partner's verify certificate to Trading Networks database (partner ID={0}, Integration Server user account={1}); skip migrating this partner's verify certificate set.**

**Explanation** An exception was thrown while attempting to add the verify certificate to the database. As a result, Trading Networks cannot migrate this partner's verify certificate set.

**Action** If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

---

<b>TNS.0006.1082E</b>	<b>Found null node certificate for CertId={0} in migration.</b>
<b>Explanation</b>	Trading Networks cannot migrate the certificate with the specified CertID because the node certificate is null.
<b>Action</b>	Supply a valid certificate.
<b>TNS.0006.1083E</b>	<b>IOException encountered in migration, CertID={0}.</b>
<b>Explanation</b>	IOException thrown when Trading Networks attempted to migrate the certificate with the specified CertID.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1084E</b>	<b>Error duplicating sign certificate data to SSL certificate data for owner={0}, partner={1}.</b>
<b>Explanation</b>	Internal error
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0006.1085E</b>	<b>Cannot migrate certificate information. Cannot get current Trading Networks version from database.</b>
<b>Explanation</b>	Trading Networks cannot migrate certificate information because it cannot determine the Trading Networks version. The database information is not up-to-date or the database is not running.
<b>Action</b>	Ensure that the Trading Networks database is running. Use the JDBC Pools page on the Integration Server Administrator to ensure that the Integration Server can connect to the Trading Networks database.
<b>TNS.0006.1087E</b>	<b>fromVersion is required to run wm.tn.admin.migrate:migrateCerts.</b>
<b>Explanation</b>	The required fromVersion parameter was not supplied.
<b>Action</b>	Supply a valid fromVersion.
<b>TNS.0006.1092E</b>	<b>SQLException encountered in wm.tn.admin.migrate:migrateCerts.</b>
<b>Explanation</b>	An SQLException thrown was when executing the wm.tn.admin.migrate:migrateCerts service.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

<b>TNS.0006.1093E</b>	<b>Error encountered in wm.tn.admin.migrate:migrateCerts.</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0006.1094E</b>	<b>Error encountered invoking service {0}.</b>
<b>Explanation</b>	An error occurred when invoking the specified service.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1098E</b>	<b>Cannot get certificate for verification of sender={0}, receiver={1}.</b>
<b>Explanation</b>	The certificates used to verify the Sender-Receiver partner pair are not available.
<b>Action</b>	Specify the certificates that you want to use for the partners in the Trading Networks profiles.
<b>TNS.0006.1099E</b>	<b>Cannot get certificate for verification of sender={0}, receiver={1}, stack trace is {2}.</b>
<b>Explanation</b>	Trading Networks could not retrieve the verify certificate for the specified sender and receiver.
<b>Action</b>	Ensure the verify certificate information is provided for specified sender and receiver.
<b>TNS.0006.1101I</b>	<b>No chain for signer {0} ({1}).</b>
<b>Explanation</b>	Required security data is missing.
<b>Action</b>	If your application code is creating or updating certificates, ensure that you supply all required certificate data to the services you are invoking. If you receive this error while using the Trading Networks Console, contact Software AG Global Support.
<b>TNS.0006.1102E</b>	<b>Cannot find verification cert.</b>
<b>Explanation</b>	Trading Networks could not retrieve a verify certificate.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0006.1103E</b>	<b>Cannot find verification cert for sender={0}, receiver={1}.</b>
<b>Explanation</b>	Trading Networks could not retrieve the verify certificate for the specified sender and receiver.
<b>Action</b>	Ensure the verify certificate information is provided for specified sender and receiver.

---

<b>TNS.0006.1104E</b>	<b>Error encountered verifying XML document.</b>
<b>Explanation</b>	An error was thrown when verifying an XML document.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1109E</b>	<b>Error encountered signing XML document.</b>
<b>Explanation</b>	An error was thrown while signing an XML document.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1110E</b>	<b>Signing certificate for sender={0} receiver={1} not valid.</b>
<b>Explanation</b>	The signing certificate for the specified sender and receiver is not valid.
<b>Action</b>	Provide a valid signing certificate for the sender/receiver pair.
<b>TNS.0006.1111E</b>	<b>Verify certificate for sender={0} receiver={1} not valid.</b>
<b>Explanation</b>	The verify certificate for the specified sender and receiver is not valid.
<b>Action</b>	Provide a valid verify certificate for the sender/receiver pair.
<b>TNS.0006.1115E</b>	<b>Error encountered invoking wm.tn.security:getDecryptCACertificates.</b>
<b>Explanation</b>	An error was encountered while invoking the wm.tn.security:getDecryptCACertificates service.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1116E</b>	<b>Error encountered invoking wm.tn.security:getDecryptCertificate.</b>
<b>Explanation</b>	An error was encountered while invoking the wm.tn.security:getDecryptCertificate service.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

<b>TNS.0006.1117E</b>	<b>Error encountered invoking wm.tn.security:getDecryptKey.</b>
<b>Explanation</b>	An error was encountered while invoking the wm.tn.security:getDecryptKey service.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1118E</b>	<b>Error encountered invoking wm.tn.security:getEncryptCACertificates.</b>
<b>Explanation</b>	An error was encountered while invoking the wm.tn.security:getEncryptCACertificates service.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1119E</b>	<b>Error encountered invoking wm.tn.security:getEncryptCertificate.</b>
<b>Explanation</b>	An error was encountered while invoking the wm.tn.security:getEncryptCertificate service.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1120E</b>	<b>Error encountered invoking wm.tn.security:getEncryptKey.</b>
<b>Explanation</b>	An error was encountered while invoking the wm.tn.security:getEncryptKey service.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1121E</b>	<b>Error encountered invoking wm.tn.security:getSecurity.</b>
<b>Explanation</b>	An error was encountered while invoking the wm.tn.security:getSecurity service.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1122E</b>	<b>Error encountered invoking wm.tn.security:getSignCACertificates.</b>
<b>Explanation</b>	An error was encountered while invoking the wm.tn.security:getSignCACertificates service.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

---

<b>TNS.0006.1123E</b>	<b>Error encountered invoking <code>wm.tn.security:getSignCertificate</code>.</b>
<b>Explanation</b>	An error was encountered while invoking the <code>wm.tn.security:getSignCertificate</code> service.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1124E</b>	<b>Error encountered invoking <code>wm.tn.security:getSignKey</code>.</b>
<b>Explanation</b>	An error was encountered while invoking the <code>wm.tn.security:getSignKey</code> service.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1125E</b>	<b>Error encountered invoking <code>wm.tn.security:getVerifyCACertificates</code>.</b>
<b>Explanation</b>	An error was encountered while invoking the <code>wm.tn.security:getVerifyCACertificates</code> service.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1126E</b>	<b>Error encountered invoking <code>wm.tn.security:getVerifyCertificate</code>.</b>
<b>Explanation</b>	An error was encountered while invoking the <code>wm.tn.security:getVerifyCertificate</code> service.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1132E</b>	<b>Error encountered invoking <code>wm.tn.security:setDecryptCertificateSet</code>.</b>
<b>Explanation</b>	An error was encountered while invoking the <code>wm.tn.security:setDecryptCertificateSet</code> service.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

<b>TNS.0006.1133E</b>	<b>cert is null; however, CACerts is not null.</b>
<b>Explanation</b>	You provided information in CACerts to specify CA certificates; however, you did not specify a certificate for the cert variable.
<b>Action</b>	Provide a valid certificate for the cert variable.
<b>TNS.0006.1134E</b>	<b>CACerts is required when the certificate is not self-signed.</b>
<b>Explanation</b>	You did not specify CA certificates for the CACerts variable. CA certificates are required unless the certificate you specify is self-signed.
<b>Action</b>	Provide valid CA certificates for the CACerts variable.
<b>TNS.0006.1137E</b>	<b>Error encountered invoking wm.tn.security:setEncryptCertificateSet.</b>
<b>Explanation</b>	An error was encountered while invoking the wm.tn.security:setEncryptCertificateSet service.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1151E</b>	<b>Error encountered invoking wm.tn.security:setSecurity.</b>
<b>Explanation</b>	An error was encountered while invoking the wm.tn.security:setSecurity service.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1152E</b>	<b>privateKey and cert should be both null or neither null.</b>
<b>Explanation</b>	You specified a value for either privateKey or cert, but not for both. The values for privateKey and cert must either both be null or both have non-null values.
<b>Action</b>	Provide valid values for privateKey and cert.
<b>TNS.0006.1153W</b>	<b>CACerts is required for non self signed certificates.</b>
<b>Explanation</b>	A value for CACerts must be specified for non self-signed certificates.
<b>Action</b>	Provide valid value for CACerts.

<b>TNS.0006.1156E</b>	<b>Error encountered invoking <code>wm.tn.security:setSignCertificateSet</code>.</b>
<b>Explanation</b>	An error was encountered while invoking the <code>wm.tn.security:setSignCertificateSet</code> service.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1159E</b>	<b>Error encountered invoking <code>wm.tn.security:setVerifyCertificateSet</code>.</b>
<b>Explanation</b>	An error was encountered while invoking the <code>wm.tn.security:setVerifyCertificateSet</code> service.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1164E</b>	<b>Error encountered invoking <code>wm.tn.security:updateCertificate</code>.</b>
<b>Explanation</b>	An error was encountered while invoking the <code>wm.tn.security:updateCertificate</code> service.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1165E</b>	<b>Error encountered in <code>wm.tn.security:addCertificateData</code>.</b>
<b>Explanation</b>	An error was encountered while executing the <code>wm.tn.security:addCertificateData</code> service.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1166E</b>	<b>Cannot get existing Certificate Data from supplied <code>certID={0}</code>.</b>
<b>Explanation</b>	Cannot get existing certificate data for the certificate information with <code>certID=&lt;certID&gt;</code> . The supplied <code>certID</code> might be invalid.
<b>Action</b>	Ensure that the value for <code>certID</code> is valid.
<b>TNS.0006.1167E</b>	<b>Cannot get existing CertID from supplied <code>ownerID={0}</code> <code>partnerID={1}</code> and <code>usage={2}</code>.</b>
<b>Explanation</b>	Cannot get existing CertID for certificate data that is associated with <code>ownerID=&lt;ownerID&gt;</code> <code>partnerID=&lt;partnerID&gt;</code> and <code>usage=&lt;certificateUsage&gt;</code> .
<b>Action</b>	Ensure that the values for <code>ownerID</code> , <code>partnerID</code> , and <code>usage</code> are valid.

<b>TNS.0006.1168E</b>	<b>Cannot construct new CertData in wm.tn.security:updateCertificateData.</b>
<b>Explanation</b>	Internal error.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0006.1169E</b>	<b>Error encountered in wm.tn.security:updateCertificateData.</b>
<b>Explanation</b>	An error was encountered while executing the wm.tn.security:updateCertificateData service.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1170E</b>	<b>Cannot delete non-existing CertData for ownerID={0}, partnerID={1} and usage={2}.</b>
<b>Explanation</b>	Trading Networks could not locate certificate data for the specified ownerID, partnerID, or usage.
<b>Action</b>	Ensure the values for ownerID, partnerID, and usage are valid.
<b>TNS.0006.1171E</b>	<b>Error encountered in wm.tn.security:deleteCertificateData.</b>
<b>Explanation</b>	An error was encountered while executing the wm.tn.security:deleteCertificateData service.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1172E</b>	<b>Error encountered in wm.tn.security:getCertificateData.</b>
<b>Explanation</b>	An error was encountered while executing the wm.tn.security:getCertificateData service.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1175E</b>	<b>Error encountered in wm.tn.security:getSigningKeyAndChain.</b>
<b>Explanation</b>	An error was encountered while executing the wm.tn.security:getSigningKeyAndChain service.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

---

<b>TNS.0006.1176E</b>	<b>Error encountered in wm.tn.security:getVerifyingChain.</b>
<b>Explanation</b>	An error was encountered while executing the wm.tn.security:getVerifyingChain service.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1178E</b>	<b>Error encountered in wm.tn.security:getDecryptionKeyAndCert.</b>
<b>Explanation</b>	An error was encountered while executing the wm.tn.security:getDecryptionKeyAndCert service.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1179E</b>	<b>Error encountered in wm.tn.security:getEncryptionChain.</b>
<b>Explanation</b>	An error was encountered while executing the wm.tn.security:getEncryptionChain service.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1182E</b>	<b>{0} private key not defined.</b>
<b>Explanation</b>	The private key for the SSL client certificate set was not defined.
<b>Action</b>	Provide a valid SSL private key for the SSL client certificate set.
<b>TNS.0006.1183E</b>	<b>{0} certificate chain not defined.</b>
<b>Explanation</b>	The certificate chain for the SSL client certificate set was not defined.
<b>Action</b>	Provide a valid SSL certificate chain for the SSL client certificate set.
<b>TNS.0006.1184E</b>	<b>Error encountered in wm.tn.security:getSSLKeyAndChain.</b>
<b>Explanation</b>	Error encountered when executing the wm.tn.security:getSSLKeyAndChain service.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

<b>TNS.0006.1185E</b>	<b>No SSL key and cert defined.</b>
<b>Explanation</b>	The SSL private key and certificate are not defined.
<b>Action</b>	Provide a valid SSL private key and certificates.
<b>TNS.0006.1187E</b>	<b>Error encountered in wm.tn.security:setSSLKeyAndChain.</b>
<b>Explanation</b>	An error was encountered while executing the wm.tn.security:setSSLKeyAndChain service.
<b>Action</b>	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
<b>TNS.0006.1190E</b>	<b>Certificate chain bytes cannot be null or zero length.</b>
<b>Explanation</b>	The certificate chainBytes value is either null or a zero length. The certificate chain must contain data.
<b>Action</b>	Provide valid certificate chain byte array.
<b>TNS.0006.1191E</b>	<b>Invalid RSA Private Key file.</b>
<b>Explanation</b>	The RSA private key file is not valid.
<b>Action</b>	Provide a valid RSA private key file.
<b>TNS.0006.1192E</b>	<b>Cannot construct new CertData.</b>
<b>Explanation</b>	Internal Error.
<b>Action</b>	Contact Software AG Global Support.
<b>TNS.0006.1193E</b>	<b>Bad private key for usage {0}: {1}</b>
<b>Explanation</b>	The private key that was provide is not valid.
<b>Action</b>	Provide a valid private key.
<b>TNS.0006.1194</b>	<b>Unable to import security data for owner {0} because the owner is not defined in your Trading Networks system.</b>
<b>Explanation</b>	In webMethods Trading Networks, it is not possible to import the security data for the owner as the owner is not defined.
<b>Action</b>	Define the owner in webMethods Trading Networks and try again.

<b>TNS.0006.1196</b>	<b>Unable to import security data of owner {0} for partner {1} because the partner {1} is not defined in your Trading Networks system.</b>
<b>Explanation</b>	In webMethods Trading Networks, if the partner is not defined as the owner of the certificate, the security data cannot be imported.
<b>Action</b>	Ensure that the partner is the owner of the certificate and try again.
<b>TNS.0006.1198</b>	<b>Error encountered while viewing certificate data for partnerID={0}. The error is {1}</b>
<b>Explanation</b>	In webMethods Trading Networks, an error is encountered while viewing certificate data for the partner.
<b>Action</b>	Contact your system administrator.
<b>TNS.0006.1199</b>	<b>Error encountered in wm.tn.security:updateCertificateData for partnerID={0}. The error is {1}</b>
<b>Explanation</b>	In webMethods Trading Networks, an error is encountered while updating a certificate.
<b>Action</b>	Contact your system administrator.
<b>TNS.0006.1200</b>	<b>Error encountered while validating chain The error is {0}</b>
<b>Explanation</b>	In webMethods Trading Networks, an error is encountered when the certificate details that are entered is not correct.
<b>Action</b>	Ensure to define the certificate details correctly and try again.
<b>TNS.0006.1201</b>	<b>Unable to import security data for partner {0} because this partner is not defined in your Trading Networks system.</b>
<b>Explanation</b>	webMethods Trading Networks is unable to import security data for the partner because this partner is not defined in your webMethods Trading Networks system.
<b>Action</b>	Define the partner in your webMethods Trading Networks system and try again.
<b>TNS.0007.1001E</b>	<b>{0} is required.</b>
<b>Explanation</b>	A value was not supplied for the specified variable.
<b>Action</b>	Supply the required value.

<b>TNS.0007.1002E</b>	<b>wm.tnweb.wrapper:xmlEncode: could not encode IData to binary</b>
<b>Explanation</b>	An exception was thrown while encoding an IData.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1003E</b>	<b>wm.tnweb.wrapper:xmlDecode: could not decode binary to IData</b>
<b>Explanation</b>	An exception was thrown while decoding an IData.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1004E</b>	<b>wm.tnweb.wrapper:xmlDecode2: could not decode binary to Values</b>
<b>Explanation</b>	An exception was thrown while decoding an IData.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1005E</b>	<b>wm.tnweb.wrapper:removeNullAlerts: error caught in removing null alerts</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1006E</b>	<b>wm.tnweb.wrapper:compareRights: error caught in comparing rights</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1007E</b>	<b>wm.tnweb.wrapper:getTNRights: error caught in getting Trading Networks partner ACL privilege</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1008E</b>	<b>wm.tnweb.wrapper:getUserGroups: error caught in getting Trading Networks partner ACL group memberships</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1009E</b>	<b>wm.tnweb.wrapper:getUserInfo: error caught in getting Trading Networks partner IS login name</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.

---

<b>TNS.0007.1010E</b>	<b>wm.tnweb.wrapper:getHashKeys: error caught in getting Hashtable keys</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1011E</b>	<b>{0} cannot be null</b>
<b>Explanation</b>	A value was not supplied for the specified variable.
<b>Action</b>	Supply the required value.
<b>TNS.0007.1012E</b>	<b>wm.tnweb.wrapper:IntegerToStrng: error caught converting Integer datatype to String datatype</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1013E</b>	<b>wm.tnweb.wrapper:ShortToStrng: error caught converting Short datatype to String datatype</b>
<b>Explanation</b>	Trading Networks encountered an internal error
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1014E</b>	<b>wm.tnweb.wrapper:isBIEnabled: error caught in retrieving enabled Integration Server packages</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1015E</b>	<b>wm.tnweb.wrapper:isBIEnabled: could not find if Business Integrator (ProcessMonitor) package is installed and enabled</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1016E</b>	<b>wm.tnweb.wrapper:getStringFromBundle: could not get String from resource bundle wm.tnweb.wrapper_bundle for key = {0}</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.

<b>TNS.0007.1017E</b>	<b>wm.tnweb.querySvc:getQuery: could not get pre-saved query ({0}) for partnerID={1}.</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1018E</b>	<b>{0} cannot be null or empty</b>
<b>Explanation</b>	A value was not supplied for the specified variable.
<b>Action</b>	Supply the required value.
<b>TNS.0007.1019E</b>	<b>partnerID is null or empty in invoking wm.tnweb.querySvc:getSavedQueries</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1020E</b>	<b>wm.tnweb.querySvc:getSavedQueries: could not get pre-saved queries for partnerID={0}</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1021E</b>	<b>wm.tnweb.querySvc:getDocuments: could not get documents</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1022E</b>	<b>wm.tnweb.querySvc:createTaskQuery: could not create task query for document id={0}</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1023E</b>	<b>wm.tnweb.querySvc:getCalendar: invalid input {0}</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1024E</b>	<b>wm.tnweb.querySvc:getCalendar: could not get calender for year={0}, month={1}</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.

<b>TNS.0007.1025E</b>	<b>wm.tnweb.querySvc:getQueryRestriction: could not get document query restriction for document id = {0}</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1026E</b>	<b>Could not get profile store</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1027E</b>	<b>Could not get document attributes for id = {0}</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1028E</b>	<b>Could not get internal document type id for name = {0}</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1029E</b>	<b>wm.tnweb.configSvc:checkDefaultConfigLoaded: could not check if default config is loaded</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1030E</b>	<b>wm.tnweb.configSvc:getHashes: could not construct Hashtables for TNAdministrators and TNPartners</b>
<b>Explanation</b>	Internal error Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1035E</b>	<b>wm.tnweb.configSvc:getUserConfig: could not get membership info for user {0}.</b>
<b>Explanation</b>	The user account for the specified user does not exist in the Integration Server.
<b>Action</b>	If you have deleted the user account for this user, use the Integration Server Administrator to create the user account again.  If this is for an external user, ensure that the user account is a member of the TNPartners group.

**TNS.0007.1039E**      **wm.tnweb.configSvc:getUserConfig: could not get partner specific config for {0}**  
**Explanation**      Trading Networks encountered an internal error.  
**Action**              Gather error information from the logs and contact Software AG Global Support.

**TNS.0007.1040E**      **wm.tnweb.configSvc:getGroupConfig: could not get group specific config for {0}**  
**Explanation**      Trading Networks encountered an internal error.  
**Action**              Gather error information from the logs and contact Software AG Global Support.

**TNS.0007.1041E**      **wm.tnweb.configSvc:getTNPartners: could not get partner information**  
**Explanation**      Trading Networks encountered an internal error.  
**Action**              Gather error information from the logs and contact Software AG Global Support.

**TNS.0007.1042E**      **wm.tnweb.configSvc:getTNGroups: could not get IS group information**  
**Explanation**      Trading Networks encountered an internal error.  
**Action**              Gather error information from the logs and contact Software AG Global Support.

**TNS.0007.1043E**      **wm.tnweb.configSvc:getTNUsers: could not get Trading Networks IS user information**  
**Explanation**      Trading Networks encountered an internal error.  
**Action**              Gather error information from the logs and contact Software AG Global Support.

**TNS.0007.1044E**      **wm.tnweb.configSvc:getUserConfigDisplay: could not get specific user config information**  
**Explanation**      Trading Networks encountered an internal error.  
**Action**              Gather error information from the logs and contact Software AG Global Support.

**TNS.0007.1045E**      **wm.tnweb.configSvc:getAvailableStatus: could not get user status from database**  
**Explanation**      Trading Networks encountered an internal error.  
**Action**              Gather error information from the logs and contact Software AG Global Support.

**TNS.0007.1047E**      **wm.tnweb.configSvc:saveCustomPages: error encountered in saving new custom pages setting**  
**Explanation**      Trading Networks encountered an internal error.  
**Action**              Gather error information from the logs and contact Software AG Global Support.

---

<b>TNS.0007.1048E</b>	<b>wm.tnweb.configSvc:addToHashes: invalid type value</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1049E</b>	<b>wm.tnweb.configSvc:addToHashes: could not add new config IData to hashtable</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1050E</b>	<b>wm.tnweb.configSvc:changeConfig: could not change config setting</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1051E</b>	<b>wm.tnweb.querySvc:getQueryRestriction: do not have privilege to check query restriction</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1053E</b>	<b>wm.tnweb.wrapper:logBrowserLocale: error encountered in getting browser locale</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1054E</b>	<b>cert is null</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1055E</b>	<b>CACerts is null</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1056E</b>	<b>CACerts[{}] is null</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.

<b>TNS.0007.1057E</b>	<b>privateKey is null</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1058E</b>	<b>Can not get user specific configuration: no such user {0}</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1059E</b>	<b>Error encountered calling wm.tnweb.configSvc:checkAndUpdateConfig</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1061E</b>	<b>Error updating/retrieving configuration info from repo</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1062E</b>	<b>Error encountered in invoking service wm.tnweb.querySvc:getPartnerNameAndID</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1063E</b>	<b>Can not get valid profile summary list: list is null or empty</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1064E</b>	<b>Error encountered in invoking service wm.tnweb.querySvc:runTaskQuery</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1065E</b>	<b>Error encountered in invoking service wm.tnweb.querySvc:taskQueryById</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.

---

<b>TNS.0007.1066E</b>	<b>Error encountered in invoking service wm.tnweb.querySvc:getDocDetails</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1067E</b>	<b>Got null bizdoc, docId = {0}</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1068E</b>	<b>Got null or 0-length bizdoc content parts, docId = {0}</b>
<b>Explanation</b>	The contents of this document might not have been saved to the Trading Networks database.
<b>Action</b>	Check the corresponding TN document type and processing rule to determine whether Trading Networks has saved the document contents to the database.
<b>TNS.0007.1069E</b>	<b>Invalid startIndex = {0}</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1070E</b>	<b>Can not convert content bytes to String: unsupported encoding</b>
<b>Explanation</b>	Trading Networks encountered an internal error.
<b>Action</b>	Gather error information from the logs and contact Software AG Global Support.
<b>TNS.0007.1071E</b>	<b>NOTE: No privilege to view contents of this document</b>
<b>Explanation</b>	You attempted to view a document of which you are neither the sender nor the receiver.
<b>Action</b>	You can only view a document that you have sent or received.
<b>TNS.0007.1072E</b>	<b>NOTE: No more data to display</b>
<b>Explanation</b>	Either the document has no content or the startIndex is beyond the end of the content.
<b>Action</b>	If you determine that this is an error, gather error information and contact webMethods Customer Care.

**TNS.0007.1073E**      **Got null bizdoc content part, docId={0}, content part name={2}**  
**Explanation**      The content of this document might not have been saved to the Trading Networks database.  
**Action**              Check the corresponding TN document type and processing rule to determine whether Trading Networks saved the document content to the database.

**TNS.0007.1074E**      **Error encountered in invoking service wm.tnweb.wrapper:getTNInfo**  
**Explanation**      Trading Networks encountered an internal error.  
**Action**              Gather error information from the logs and contact Software AG Global Support.

**TNS.0007.1075E**      **Error encountered in invoking service wm.tnweb.wrapper:registerTNonIntegrationServer**  
**Explanation**      Trading Networks encountered an internal error.  
**Action**              Gather error information from the logs and contact Software AG Global Support.

**TNS.0007.1076E**      **Error encountered parsing date {0} or {1}.**  
**Explanation**      Trading Networks encountered an internal error.  
**Action**              Gather error information from the logs and contact Software AG Global Support.

**TNS.0007.1077E**      **Error encountered in invoking service wm.tnweb.wrapper:installTNWebACLs**  
**Explanation**      Trading Networks encountered an internal error.  
**Action**              Gather error information from the logs and contact Software AG Global Support.

**TRNSERV.000018.000001 – new String[]{"{0} is required","Please supply the required value","0"}**  
**Explanation**      A value for the specified input field is not supplied.  
**Action**              Supply a valid value for the specified input field.

**TRNSERV.000018.000018 – new String[]{"{0} cannot be null or empty","","0"}**  
**Explanation**      The specified input field does not contain a value. A value for this input field is required.  
**Action**              Supply a valid value for the specified input field.

---

**TRNSERV.000018.000025 – new String[]{"wm.tnweb.querySvc:getQueryRestriction: could not get document query restriction for document id = {0}","","0"}**

**Explanation** An error occurred while fetching a document query restriction for specified document.

**Action** The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

**TRNSERV.000018.000051 – new String[]{"wm.tnweb.querySvc:getQueryRestriction: do not have privilege to check query restriction","","0"}**

**Explanation** You are not allowed to check the query restriction.

**Action** Contact your administrator.

**TRNSERV.000018.000066 – new String[]{"Error encountered in invoking service wm.tnweb.querySvc:getDocDetails","","0"}**

**Explanation** An error occurred while retrieving content part bytes.

**Action** The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

**TRNSERV.000018.000067 – new String[]{"Got null bizdoc, docId = {0}","","0"}**

**Explanation** While checking the query restriction, a null bizdoc was found for the specified docID.

**Action** Supply a valid docId.

**TRNSERV.000024.000204 – new String[]{"Error attempting to parse message contents","","0"}**

**Explanation** A MessagingException error occurred while parsing the MIME message.

**Action** The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

**TRNSERV.000024.000205 – new String[]{"Error attempting to read from message source","","0"}**

**Explanation** An IOException error occurred while reading a MIME message from the message source.

**Action** The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

**bizDocDeletionError – You did not select an item to delete. Select at least one item to delete.**

**Explanation** You did not select an item to delete.  
**Action** Select at least one item to delete.

**bizDocSelectionError – You did not select an item to archive. Select at least one item to archive.**

**Explanation** You did not select an item to archive.  
**Action** Select at least one item to archive.

**cert.err An error occurred while validating the certificate chain. Take corrective action based on the error details.**

**Explanation** An error occurred while validating the certificate chain.  
**Action** Take corrective action based on the error details.

**corp.name.required You did not supply a value for the required Corporation Name field. Provide a value for this field.**

**Explanation** You did not supply a value for the required Corporation Name field.  
**Action** Provide a value for this field.

**date.is.required You did not specify a date. Specify a date to proceed.**

**Explanation** You did not specify a date.  
**Action** Specify a date to proceed.

**default.connection.error.msg – Trading Networks Server is not configured, or it is not available.**

**Explanation** Trading Networks server is not configured, or it is not available.  
**Action** Contact the Administrator.

**dlscheck.dialogMessage – You do not have permission to perform this action. Contact your system administrator for the required privileges.**

**Explanation** You do not have permission to perform this action.  
**Action** Contact your system administrator for the required privileges.

---

**docTypeDetails\_NameRequiredError – The document type name is a required field. Provide a document type name.**

**Explanation** The document type name is required.

**Action** Provide a document type name.

**docTypeSearch.fileInput.required.msg – No document was provided for testing. Provide the document.**

**Explanation** No document was provided for testing.

**Action** Provide the document.

**doctype.instantiation.error – The EDI document type could not be instantiated. Make sure that a valid schema standard is specified.**

**Explanation** The EDI document type could not be instantiated.

**Action** Make sure that a valid schema standard is specified.

**editor.detailsid.missing.error – Document Type ID is missing.**

**Explanation** In webMethods Trading Networks, if the Document Type ID is missing, this error shows up.

**Action** Ensure to log out and log in again to webMethods Trading Networks.

**empty.attribute.name.error – The Name field cannot be blank. Provide a valid value for this field.**

**Explanation** The Name field cannot be blank.

**Action** Provide a valid value for this field.

**error.InvalidDefaultValue – You specified a default value of %1\$s. This value is not valid. Select a value from the list of valid values.**

**Explanation** The specified default value is not valid.

**Action** Select a value from the list of valid values.

**error.InvalidFieldId – Invalid Field Id Specified: %1\$s**

**Explanation** In webMethods Trading Networks, if the Field Definition ID of the profile is null or invalid, this error shows up.

**Action** Contact your system administrator.

**error.InvalidFieldLength** – You specified a field length of %1\$s. This field length is not valid. Specify a positive integer value.

**Explanation** The specified field length is not valid.

**Action** Specify a positive integer value.

**error.WmEDIPackageNotEnabled** – The WmEDI package is not enabled on the Integration Server. Enable the package.

**Explanation** The WmEDI package is not enabled on the Integration Server.

**Action** Enable the package.

**error.days.greaterthan.zero** – You entered a value for Days that is not valid. Enter an integer value greater than zero.

**Explanation** You entered a value for Days that is not valid.

**Action** Enter an integer value greater than zero.

**error.defValue.exceeds.maxLength** – Default Value %1\$s exceeds specified Maximum Length %2\$s

**Explanation** In webMethods Trading Networks, if the default value of a field definition exceeds the maximum length permissible, this error throws up.

**Action** Enter a field definition with default value within the permissible maximum length, and try again.

**error.delete** The activity log(s) could not be deleted. Take corrective action based on the error details.

**Explanation** The activity log(s) could not be deleted.

**Action** Take corrective action based on the error details.

**error.enter.valid.file.name** – Enter a valid file name

**Explanation** The file name is empty or contains invalid characters such as ", /, \, \*, or ?.

**Action** Specify a valid file name.

**error.enter.valid.solution.name** – Enter a valid solution name

**Explanation** The solution name is empty or contains invalid characters such as ", /, \, \*, or ?.

**Action** Specify a valid solution name.

<b>error.extract.file</b>	<b>The file you uploaded is not in a valid format. Provide an XML or a binary file containing valid asset data to import.</b>
<b>Explanation</b>	The file you uploaded is not in a valid format.
<b>Action</b>	Provide an XML or a binary file containing valid asset data to import.
<b>error.getComment</b>	<b>An error occurred while retrieving comments from Trading Networks. Take corrective action based on the error details and trace.</b>
<b>Explanation</b>	An error occurred while retrieving comments from Trading Networks.
<b>Action</b>	Take corrective action based on the error details and trace.
<b>error.getEDIINTProperties – My webMethods encountered an error while trying to retrieve WmEDIforTN package properties.</b>	<b>Take corrective action based on the error details.</b>
<b>Explanation</b>	My webMethods Server encountered an error while trying to retrieve WmEDIforTN package properties.
<b>Action</b>	Take corrective action based on the error details.
<b>error.getEDIProperties – My webMethods Server encountered an error while trying to retrieve WmEDI package properties.</b>	<b>Take corrective action based on the error details.</b>
<b>Explanation</b>	My webMethods Server encountered an error while trying to retrieve WmEDI package properties.
<b>Action</b>	Take corrective action based on the error details.
<b>error.getTNProperties – My webMethods Server encountered an error while trying to retrieve Trading Networks properties.</b>	<b>Make sure the WmTN package is properly installed and loaded.</b>
<b>Explanation</b>	My webMethods Server encountered an error while trying to retrieve Trading Networks properties.
<b>Action</b>	Make sure the WmTN package is properly installed and loaded.
<b>error.message</b>	<b>Download action failed.</b>
<b>Explanation</b>	An exception occurred while downloading the file.
<b>Action</b>	Check the server connection. Contact the system administrator to check your security and locale settings.

**error.message.edi.not.installed** – This feature requires the WmEDI and WmEDIforTN packages. These packages are either not loaded or are disabled. Enable these packages.

**Explanation** This feature requires the WmEDI and WmEDIforTN packages.

**Action** These packages are either not loaded or are disabled. Enable these packages.

**error.name.already.exists** – The name you have chosen for this field, %1\$s, already exists. Enter a different name.

**Explanation** The name you have chosen for this field already exists.

**Action** Enter a different name.

**error.noserver** My WebMethods Server could not reassign the task(s) because no target was specified. Specify the target server.

**Explanation** My webMethods Server could not reassign the task(s) because no target was specified.

**Action** Specify the target server.

**error.reassign** My WebMethods Server encountered an error while reassigning the task(s). Take corrective action based on the error details.

**Explanation** My webMethods Server encountered an error while reassigning the task(s).

**Action** Take corrective action based on the error details.

**error.restart** My WebMethods Server encountered an error while restarting the task(s). Take corrective action based on the error details.

**Explanation** My webMethods Server encountered an error while restarting the task(s).

**Action** Take corrective action based on the error details.

**error.saveEDIFormatSettings** – My webMethods encountered an error while trying to update EDI Module format settings. Take corrective action based on the error details.

**Explanation** My webMethods Server encountered an error while trying to update EDI Module format settings.

**Action** Take corrective action based on the error details.

**error.saveEDIINTProperties** – My webMethods encountered an error while trying to update EDI Module configuration properties. Take corrective action based on the error details.

**Explanation** My webMethods Server encountered an error while trying to update EDI Module configuration properties.

**Action** Take corrective action based on the error details.

**error.saveEDIProperties – My webMethods encountered an error while trying to save EDI Module configuration properties. Take corrective action based on the error details.**

**Explanation** My webMethods Server encountered an error while trying to save EDI Module configuration properties.

**Action** Take corrective action based on the error details.

**error.saveTNProperties – My webMethods Server encountered an error while trying to save Trading Networks properties. Make sure the WmTN package is properly installed and loaded.**

**Explanation** My webMethods Server encountered an error while trying to save Trading Networks properties.

**Action** Make sure the WmTN package is properly installed and loaded.

**error.setComment An error occurred while setting comments from Trading Networks. Take corrective action based on the error details and trace.**

**Explanation** An error occurred while setting comments from Trading Networks.

**Action** Take corrective action based on the error details and trace.

**error.stop My WebMethods Server encountered an error while stopping the task(s). Take corrective action based on the error details.**

**Explanation** My webMethods Server encountered an error while stopping the task(s).

**Action** Take corrective action based on the error details.

**error.submitDocument – An error occurred while submitting the document to Trading Networks. Check the file path and resubmit the document.**

**Explanation** An error occurred while submitting the document to Trading Networks.

**Action** Check the file path and resubmit the document.

**file.validation.messageE – Invalid file format. Supported format: csv**

**Explanation** The file uploaded is not a valid file format.

**Action** Upload .csv files.

**g11n.wm\_tn\_bam\_attributes.default.optimize\_not\_installed – Optimize is not installed. Install webMethods Optimize.**

**Explanation** Optimize is not installed.

**Action** Install webMethods Optimize.

**g11n.wm\_tn\_bam\_doctypes.default.optimize\_not\_installed – Optimize is not installed. Install webMethods Optimize.**

**Explanation** Optimize is not installed.  
**Action** Install webMethods Optimize.

**g11n.wm\_tn\_dls\_viewDataSet.default.at\_least\_one\_permission – Permissions have not yet been granted to this role. Grant at least one permission to this role on the Permissions tab.**

**Explanation** Permissions have not yet been granted to this role.  
**Action** On the Permissions tab, grant at least one permission to this role.

**g11n.wm\_tn\_pf\_profile.users.invalid\_user\_name – You did not specify a user name. Provide a valid user name.**

**Explanation** You did not specify a user name.  
**Action** Provide a valid user name.

**g11n.wm\_tn\_pf\_profile.users.no\_password – The password is missing. Provide and confirm the password.**

**Explanation** The password is missing.  
**Action** Provide and confirm the password.

**g11n.wm\_tn\_pf\_profile.users.passwords\_do\_not\_match – The values for Password and Confirm Password do not match. Enter the same values for these fields.**

**Explanation** The values for Password and Confirm Password do not match.  
**Action** Enter the same values for these fields.

**g11n.wm\_tn\_pf\_profile.users.user\_already\_exists\_please – The specified user name already exists. Provide a unique user name.**

**Explanation** The specified user name already exists.  
**Action** Provide a unique user name.

**g11n.wm\_tn\_pf\_profile.users.user\_name\_invalid – The user name provided is not valid because it contains special characters. Specify a user name that contains only alphanumeric characters.**

**Explanation** The user name provided is not valid because it contains special characters.  
**Action** Specify a user name that contains only alphanumeric characters.

**id.generate.error**      **Can not generate EDI document type ID. Try again.**  
**Explanation**            Cannot generate EDI document type ID.  
**Action**                    Try again.

**invalid.fileE**            **Invalid file format. Supported formats: xml,txt**  
**Explanation**            The file uploaded is not a valid file format.  
**Action**                    Upload .xml or .txt files.

**invalid.integer.value.detail** – **The value you provided for the Control Number Minimum is not an integer. For the VDA standard, enter an integer value greater than or equal to 0. For other standards, enter an integer value greater than or equal to 1.**

**Explanation**            The value you provided for the Control Number Minimum is not an integer.  
**Action**                    For the VDA standard, enter an integer value greater than or equal to 0. For other standards, enter an integer value greater than or equal to 1.

**invalid.message.minimum.value** – **The value you provided for the Control Number Minimum is not valid. For the VDA standard, enter a value greater than or equal to 0. For other standards, enter a value greater than or equal to 1.**

**Explanation**            The value you provided for the Control Number Minimum is not valid.  
**Action**                    For the VDA standard, enter a value greater than or equal to 0. For other standards, enter a value greater than or equal to 1.

**invalid.role**            **You cannot add or remove privileges for Trading Networks or My webMethods administrators. Contact your system administrator.**  
**Explanation**            You cannot add or remove privileges for Trading Networks or My webMethods administrators.  
**Action**                    Contact your system administrator.

**invalid.value.inputcontrol** – **The value you provided for the Control Number Minimum is not valid. Enter an integer value. For the VDA standard, enter a value greater than or equal to 0. For other standards, enter a value greater than or equal to 1.**

**Explanation**            The value you provided for the Control Number Minimum is not valid. Enter an integer value.  
**Action**                    For the VDA standard, enter a value greater than or equal to 0. For other standards, enter a value greater than or equal to 1.

**label.error.maxrowsexceededE – Number of records to fetch exceeds the maximum limit.**

**Explanation** Error occurred while trying to access Trading Networks dashboard because the number of records to fetch from the dashboard table (TransactionSummaryData table) exceeds the maximum limit.

**Action** Contact your system administrator to either purge records or specify a larger value for the tn.chart.fetchMaxRows property.

**missing.required.extended – The required extended field {1} of group {0} is missing. Provide a value for this extended field.**

**Explanation** The required extended field is missing.

**Action** Provide a value for this field.

**msg.badDateRange The start date is later than the end date. Correct the start date so that it occurs before the end date.**

**Explanation** The start date is later than the end date.

**Action** Correct the start date so that it occurs before the end date.

**msg.badDynamicData You submitted dynamic query criteria that are incomplete. Provide all expected elements for the dynamic query.**

**Explanation** The dynamic query criteria are incomplete.

**Action** Provide all expected elements for the dynamic query.

**msg.errSave The content viewer page size is empty or is not valid. Enter an integer value greater than zero.**

**Explanation** The content viewer page size is empty or is not valid.

**Action** Enter an integer value greater than zero.

**msg.maxReprocessDocuments – You cannot reprocess more than {0} documents. To change this limit, contact your system administrator.**

**Explanation** Reprocessing limit exceeded.

**Action** To change this limit, contact your system administrator.

**msg.maxResubmitDocuments** – You cannot resubmit more than {0} documents. To change this limit, contact your system administrator.

**Explanation** Resubmission limit exceeded.

**Action** To change this limit, contact your system administrator.

**name.is.required** You did not specify a queue name. Specify a queue name to proceed.

**Explanation** You did not specify a queue name.

**Action** Specify a queue name to proceed.

**no.data.set** My webMethods was unable to find the dataset for the specified ID. Log in to My webMethods again.

**Explanation** Unable to find the dataset for the specified ID.

**Action** Log in to My webMethods again.

**no.return.url** My webMethods could not navigate to the specified page because of a caching issue. Log in to My webMethods again.

**Explanation** My webMethods could not navigate to the specified page because of a caching issue.

**Action** Log in to My webMethods again.

**no.root.vailable.error** – The sample document used for creating the XML document type does not contain a Root tag. Provide a properly formatted document that contains a Root tag.

**Explanation** The sample document used for creating XML document type does not contain a Root tag.

**Action** Provide a properly formatted document that contains a Root tag.

**not.valid.document** You uploaded a sample document that is not valid. Provide a sample document with a valid root node.

**Explanation** You uploaded a sample document that is not valid.

**Action** Provide a sample document with a valid root node.

**optionsTab.check.duplicate.doc.error.msg** – You selected the "Check for Duplicate Document" option but did not specify a duplication service. Select a service.

**Explanation** You selected the "Check for Duplicate Document" option but did not specify a duplication service.

**Action** Select a service.

**partnerid.missing.message** – The partner ID is missing. Click here to go to the Partner Profiles page, and then specify a valid partner ID.

**Explanation** The partner ID is missing.

**Action** Click here to go to the Partner Profiles page, and then specify a valid partner ID.

**problem.AccessException** – You do not have permission to perform the requested action. Check with your system administrator.

**Explanation** You do not have permission to perform the requested action.

**Action** Request that your system administrator assign you the permission.

**problem.ConnectException** – My webMethods Server could not connect to the Trading Networks Server because that server is not available. Make sure the server is running on the specified host and port "{0}".

**Explanation** The specified Trading Networks server is not available.

**Action** Make sure the server is running on the specified host and port.

**problem.UnknownHostException** – My webMethods Server could not connect to the Trading Networks Server named "{0}" because that server is either not available or its host name is not recognized. Start the Trading Networks Server or specify a different server to connect to.

**Explanation** The specified Trading Networks server is not available.

**Action** Verify the host name of the Trading Networks Server.

**problem.noSelection** – You did not select any items to act on. Select one or more items and retry the action.

**Explanation** You did not select any items to act on.

**Action** Select one or more items and then retry the action.

**proc.rules.detailsno.server.error** – Trading Networks Server is not configured, or it is not available.

**Explanation** The configured Trading Networks instance may be down, or the system administrator may not have granted you permission to access the Trading Networks Server.

**Action** Make sure the server is running. If it is, contact the system administrator for permission to access the server.

**procrule.details.name.invalid.errorE – Invalid Processing rule name. Special characters are not allowed.**

**Explanation** Processing rule name cannot have special characters.

**Action** Provide a valid name for the processing rule.

**profile.externalid.required – You did not specify an external ID for this profile. Provide the external ID.**

**Explanation** You did not specify an external ID for this profile.

**Action** Provide an external ID.

**query.not.found.error – You uploaded a sample document that does not contain a valid root node. Provide a sample document with a valid root node.**

**Explanation** You uploaded a sample document that does not contain a valid root node.

**Action** Provide a sample document with a valid root node.

**query.not.match Your query does not match any of the nodes present in the sample document. Resubmit the query with a valid node.**

**Explanation** Your query does not match any of the nodes present in the sample document.

**Action** Resubmit the query with a valid node.

**role.is.required Permissions have not yet been granted to any roles. Grant permission(s) to at least one role on the Permissions tab.**

**Explanation** Permissions have not yet been granted to any roles.

**Action** On the Permissions tab, grant permission(s) to at least one role.

**rule.name.is.required – The dataset could not be created or updated because no dataset name was specified. Provide the dataset name.**

**Explanation** Dataset name not specified while creating or updating the dataset.

**Action** Enter the dataset name.

**std.version.trans.not.sel.error – You did not specify a standard, version, or transaction while creating the EDI document type. Select a standard, version, and transaction.**

**Explanation** You did not specify a standard, version, or transaction while creating the EDI document type.

**Action** Select a standard, version, and transaction.

**text.futuredate.validationE – Date selected cannot be in the future.**

**Explanation** Error occurred while trying to retrieve records from the TransactionSummaryData table because the date selected was a future date.

**Action** Select an appropriate date to view data.

**text.response.nodataI – No records found for the selected date.**

**tn.srvr.displayGroup – Trading Networks**

**tn.srvr.displayName – Server**

**tpa.details.agreementID.required.error – Agreement ID cannot be empty.**

**Explanation** Agreement ID is empty.

**Action** Provide an Agreement ID.

**tpa.details.controlnumber.notInteger – Control Number must be an integer. Provide an integer value.**

**Explanation** Control Number must be an integer.

**Action** Provide an integer value.

**tpa.details.profiles.required.error – Sender or Receiver fields cannot be empty.**

**Explanation** Sender or Receiver field is empty.

**Action** Specify Sender and Receiver.

**tree.load.error My webMethods encountered an error while loading the XML node tree. Click Upload to try loading the tree again.**

**Explanation** My webMethods Server encountered an error while loading the XML node tree.

**Action** Click Upload to try loading the tree again.

**updateFAStatus.errorMessage – Error in updating EDI FA status.**

**Explanation** Error in updating EDI FA status.

**Action** Take corrective action according to the error details.

**warn.noFileSelected** – No document was chosen for submission. Specify the file path to the document to be submitted.

**Explanation**            No document was chosen for submission.

**Action**                 Specify the file path to the document to be submitted.



# 28

## webMethods Social BPM Messages

---

<b>SBPAPIE0000</b>	<b>Could not establish session for {0} server. Status: {1}</b>
<b>Explanation</b>	Connection to the client failed.
<b>Action</b>	Check the connection settings for the client.
<b>SBPAPIE0001</b>	<b>Could not send the email. Enter the recipients' email address, subject, and message in their respective fields.</b>
<b>Explanation</b>	The values for the recipients' email address, subject, and message fields cannot be null or invalid.
<b>Action</b>	Make sure the email address, subject, and message fields are not empty.
<b>SBPAPIE0002</b>	<b>Could not send the email. Read the log file for more details.</b>
<b>Explanation</b>	The email address might be wrong or empty.
<b>Action</b>	Check the error details in the log file. Provide the correct email address.
<b>SBPAPIE0004</b>	<b>The remote resource, {0} did not return a valid session.</b>
<b>Explanation</b>	Client connection is not valid.
<b>Action</b>	Check the connection settings.
<b>SBPAPIE0005</b>	<b>{0} HTTP method is not supported.</b>
<b>Explanation</b>	Only GET, POST, PUT, and DELETE methods are supported.
<b>Action</b>	Use only GET, POST, PUT, or DELETE methods.

<b>SBPAPIE0006</b>	<b>You do not have the required privileges to view task data. Contact the Administrator.</b>
<b>Explanation</b>	Only users with the required privileges can view task data.
<b>Action</b>	Request the Administrator to provide you the privileges to view task data.
<b>SBPAPIE0007</b>	<b>Task ID cannot be null.</b>
<b>Explanation</b>	A valid Task ID is required.
<b>Action</b>	Provide a valid Task ID.
<b>SBPAPIE0008</b>	<b>At least one group is required if you set {groupByField=&lt;field&gt; / groupByTaskType = &lt;true&gt; parameter.</b>
<b>Explanation</b>	You cannot use groupByField or groupByTaskType when there are no groups.
<b>Action</b>	Use groupByField or groupByTaskType only when there are groups.
<b>SBPAPIE0009</b>	<b>Wrong operator specified for task list search.</b>
<b>Explanation</b>	The criteria for task list search is incorrect.
<b>Action</b>	Provide the correct search criteria.
<b>SBPAPIE0010</b>	<b>AppSpace not found. You might not have access to the AppSpace or the AppSpace might have been removed.</b>
<b>Explanation</b>	Either the Administrator might have removed the AppSpace or you do not have the privileges to view the AppSpace.
<b>Action</b>	Request the Administrator to verify the AppSpace availability or provide you the privileges to view the AppSpace.
<b>SBPAPIE0011</b>	<b>Invalid input. The JSON payload for the {0} is not valid.</b>
<b>Explanation</b>	The input to the RESTful service is invalid.
<b>Action</b>	Verify the JSON payload to the RESTful service.
<b>SBPAPIE0012</b>	<b>Avoid using reserved words for {0} name</b>
<b>Explanation</b>	The dashboard name should not contain programming keywords such as null or var.
<b>Action</b>	Do not use programming keywords in the dashboard name.

---

<b>SBPAPIE0013</b>	<b>Insufficient Privileges. You cannot view {0}.</b>
<b>Explanation</b>	You do not have the privileges to view the dashboard.
<b>Action</b>	Request the Administrator to provide you the privileges to view the dashboard.
<b>SBPAPIE0014</b>	<b>Insufficient Privileges. You cannot edit {0}.</b>
<b>Explanation</b>	You do not have the privileges to edit the dashboard.
<b>Action</b>	Request the Administrator to provide you the privileges to edit the dashboard.
<b>SBPAPIE0015</b>	<b>Insufficient Privileges. You cannot delete {0}.</b>
<b>Explanation</b>	You do not have the privileges to delete the dashboard.
<b>Action</b>	Request the Administrator to provide you the privileges to delete the dashboard.
<b>SBPAPIE0016</b>	<b>Insufficient Privileges. You cannot create {0}.</b>
<b>Explanation</b>	You do not have the privileges to create the dashboard.
<b>Action</b>	Request the Administrator to provide you the privileges to create the dashboard.
<b>SBPAPIE0017</b>	<b>Unable to remove the delegation. You cannot remove delegations done by other users.</b>
<b>Explanation</b>	You cannot remove delegations done by other users.
<b>Action</b>	Request the user who has delegated the task to remove the delegation.
<b>SBPAPIE0047</b>	<b>Cannot retrieve the preferences for {0}</b>
<b>Explanation</b>	Cannot retrieve the preference settings.
<b>Action</b>	Verify if the preferences set in Business Console are available.
<b>SBPAPII0003</b>	<b>Task ID not found.</b>
<b>Explanation</b>	The task instance is not available in the database.
<b>Action</b>	Request the Administrator to verify the task instance availability.
<b>SBPAPII0018</b>	<b>Invalid email</b>
<b>Explanation</b>	Cannot send task reminder to an invalid email.
<b>Action</b>	Provide a valid email.

<b>SBPAPII0019</b>	<b>Internal server error</b>
<b>Explanation</b>	Cannot send task reminder because of an internal server error.
<b>Action</b>	Contact the Administrator for resolving this error.
<b>SBPAPII0020</b>	<b>Integration Server connection error</b>
<b>Explanation</b>	Cannot connect to the Integration Server.
<b>Action</b>	Contact the Administrator for resolving this error.
<b>SBPAPII0023</b>	<b>AgileApps server connection error</b>
<b>Explanation</b>	Cannot connect to the AgileApps server.
<b>Action</b>	Contact the Administrator for resolving this error.
<b>SBPAPII0024</b>	<b>Failed to retrieve the 'isDelegated' property from task: {0}</b>
<b>Explanation</b>	Cannot retrieve the delegation status of the task.
<b>Action</b>	Contact the Administrator for resolving this error.
<b>SBPAPII0025</b>	<b>No delegation to remove. The task ID {0} is not delegated.</b>
<b>Explanation</b>	The task is not delegated to a user.
<b>Action</b>	Contact the Administrator for resolving this error.
<b>SBPAPII0027</b>	<b>Invalid input parameters</b>
<b>Explanation</b>	The input parameters specified for the AppSpace is not valid.
<b>Action</b>	Verify the input parameters.
<b>SBPAPII0028</b>	<b>The task {0} is not active.</b>
<b>Explanation</b>	You cannot set the status because the task is not active.
<b>Action</b>	Contact the Administrator for resolving this error.
<b>SBPAPII0029</b>	<b>Insufficient privileges</b>
<b>Explanation</b>	You do not have the privileges to perform this action.
<b>Action</b>	Request the Administrator to provide you the required privileges.

---

<b>SBPAPII0030</b>	<b>User, group, or role name is null or does not exist.</b>
<b>Explanation</b>	User, group, or role name is null or does not exist.
<b>Action</b>	Use a valid user, group, or role name.
<b>SBPAPII0031</b>	<b>Insufficient privileges. {0} does not have the privileges to add comments.</b>
<b>Explanation</b>	You do not have the privileges to add comments.
<b>Action</b>	Request the Administrator to provide you the privileges to add comments.
<b>SBPAPII0032</b>	<b>The task ID: {0} is not found.</b>
<b>Explanation</b>	The task ID is not found.
<b>Action</b>	Verify if the task ID is correct or contact the Administrator.
<b>SBPAPII0033</b>	<b>Profile picture not loaded</b>
<b>Explanation</b>	Cannot load the profile picture.
<b>Action</b>	Contact the Administrator for resolving this error.
<b>SBPAPII0034</b>	<b>Insufficient privileges. {0} cannot update the profile of {1}.</b>
<b>Explanation</b>	You do not have the privileges to update the profile.
<b>Action</b>	Request the Administrator to provide you the privileges to update the profile.
<b>SBPAPII0035</b>	<b>Cannot retrieve the file.</b>
<b>Explanation</b>	The file is not found.
<b>Action</b>	Contact the Administrator for resolving this error.
<b>SBPAPII0036</b>	<b>The Task Engine host: {0} not found.</b>
<b>Explanation</b>	The specified host name for the Task Engine is not found.
<b>Action</b>	Contact the Administrator for resolving this error.
<b>SBPAPII0037</b>	<b>Task Engine server connection error</b>
<b>Explanation</b>	Cannot connect to the Task Engine server.
<b>Action</b>	Contact the Administrator for resolving this error.

<b>SBPAPII0038</b>	<b>I/O exception in Task Engine: {0}</b>
<b>Explanation</b>	Cannot resolve the Task Engine URL.
<b>Action</b>	Contact the Administrator for resolving this error.
<b>SBPAPII0039</b>	<b>Exception in Task Engine: {0}</b>
<b>Explanation</b>	An error has occurred in Task Engine.
<b>Action</b>	Contact the Administrator for resolving this error.
<b>SBPAPII0040</b>	<b>Task definition URI error</b>
<b>Explanation</b>	Cannot resolve the task definition URI.
<b>Action</b>	Provide a valid task definition URI.
<b>SBPAPII0041</b>	<b>You are not logged on.</b>
<b>Explanation</b>	You must log on to perform the action.
<b>Action</b>	Log on to perform the action.
<b>SBPAPII0044</b>	<b>Invalid search</b>
<b>Explanation</b>	Search is not valid.
<b>Action</b>	Use valid search criteria.
<b>SBPAPII0045</b>	<b>Cannot sync {0} task types.</b>
<b>Explanation</b>	Cannot sync the indicated number of task types from Task Engine.
<b>Action</b>	Contact the Administrator for resolving this error.
<b>SBPAPII0046</b>	<b>Invalid URL: {0}</b>
<b>Explanation</b>	Cannot resolve the URL.
<b>Action</b>	Provide a valid URL.
<b>SBPCORI1046</b>	<b>Duration</b>

# 29

## Web Services Stack Messages

---

<b>WSSAPE0029</b>	<b>Failed to initialize argus configuration due to the following: {0}.</b>
<b>Explanation</b>	An argus configuration file is invalid or unavailable, or a WS_STACK_HOME variable is not set.
<b>Action</b>	Make sure that the WS_STACK_HOME environment variable is properly set. Check the path to the argus configuration file and make sure that the argus configuration file is valid and not empty.
<b>WSSAPE0030</b>	<b>Unknown user: {0}.</b>
<b>Explanation</b>	The user cannot be authenticated because the supplied username is not correct.
<b>Action</b>	Provide a valid username.
<b>WSSAPE0031</b>	<b>Unknown password callback type: {0}</b>
<b>Explanation</b>	Only UsernameToken authentication is supported. You use a different authentication mechanism.
<b>Action</b>	Provide a valid username and password.
<b>WSSAPE0032</b>	<b>An argus username is not configured in the argus agents properties file.</b>
<b>Explanation</b>	The entries in argus agents properties file must be initialized. The "wsstack.adminservice.user" property does not contain a valid value.
<b>Action</b>	Provide a valid, non-empty value for "wsstack.adminservice.user" property in the argus agents properties file.

<b>WSSARE0000</b>	<b>Login failed.</b>
<b>Explanation</b>	Authentication fails. Invalid or empty credentials provided.
<b>Action</b>	Provide valid, non-empty username and password.
<b>WSSARE0001</b>	<b>The following Web service archive does not comply with the naming standards: {0}. The archive is not deployed.</b>
<b>Explanation</b>	The artifact name and extension contain invalid characters or do not comply with the correct name format.
<b>Action</b>	Edit the current artifact to conform to the AAR standards. Rename the archive using a valid name. The '.aar' extension cannot contain capital letters.
<b>WSSARE0030</b>	<b>A problem occurred while executing a Web service. The Web service name is "{0}" with request payload "{1}".</b>
<b>Explanation</b>	There is a problem while executing the Web service.
<b>Action</b>	Make sure that the requested Web service is operational.
<b>WSSARI0027</b>	<b>Version information.</b>
<b>Explanation</b>	A version information label.
<b>Action</b>	None.
<b>WSSASE0000</b>	<b>Cannot find library jar file "{0}"</b>
<b>Explanation</b>	The message appears when Web Services Stack administration service is trying to locate the axis2-kernel jar but the file does not exist or its location cannot be determined.
<b>Action</b>	Assert that the reported file exists and it is not locked by another process on the system.
<b>WSSASE0009</b>	<b>Cannot find library directory "{0}"</b>
<b>Explanation</b>	The message appears when Web Services stack administration service is trying to locate the library directory with the jar files used by the Web Services Stack runtime.
<b>Action</b>	Assert that the reported path exists and it is a valid directory.
<b>WSSCLE0001</b>	<b>Deployment configuration file cannot be null.</b>
<b>Explanation</b>	A valid deployment configuration file was not specified or an empty value for deployment configuration file was provided.
<b>Action</b>	Specify a valid deployment configuration file.

---

<b>WSSCLE0002</b>	<b>[[0]] object cannot be null.</b>
<b>Explanation</b>	Deployment configurator is not initialized correctly and returns null.
<b>Action</b>	You must initialize the deployment configurator with a valid, non-empty deployment configuration file or valid deployment configuration properties.
<b>WSSCLE0003</b>	<b>The specified transport protocol [[0]] is not supported.</b>
<b>Explanation</b>	The transport protocol defined in the DeploymentConfigurator is not supported.
<b>Action</b>	Set HTTP or HTTPS transport in the DeploymentConfigurator.
<b>WSSCLE0004</b>	<b>Deployment configuration properties object cannot be null.</b>
<b>Explanation</b>	Valid deployment configuration properties are not specified or empty values for deployment configuration properties are provided.
<b>Action</b>	Specify valid, non-empty deployment configuration properties.
<b>WSSCLE0005</b>	<b>Problems while loading the deployment configuration from the file with the following location path: [[0]].</b>
<b>Explanation</b>	Deployment configuration cannot be loaded from the specified file.
<b>Action</b>	Check whether the provided configuration file is valid and whether its location path is correct.
<b>WSSCLE0006</b>	<b>"Servlet context" configuration is not found. The needed "servlet context" configuration is not set into the deployment configuration file.</b>
<b>Explanation</b>	The deployment configuration property that specifies the servlet context is not set into the deployment configuration file.
<b>Action</b>	Set the servlet deployment configuration property into the deployment configuration file.
<b>WSSCLE0007</b>	<b>"Host name" configuration is not found. The needed "host name" configuration is not set into the deployment configuration file.</b>
<b>Explanation</b>	The deployment configuration property hostname is not set into the deployment configuration file or the given value cannot be resolved.
<b>Action</b>	Set a valid, non-empty value for the hostname property into the deployment configuration file.

**WSSCLE0008**      **Unknown "host name" configuration found. You can find the needed "host name" configuration into the deployment configuration file.**

**Explanation**      The deployment configuration property hostname is set with a value that cannot be resolved.

**Action**            Set a valid, non-empty value for the hostname property into the deployment configuration file.

**WSSCLE0009**      **Invalid "port number" configuration found. You can find the needed "port number" configuration into the deployment configuration file.**

**Explanation**      In the deployment configuration property port is set an invalid value.

**Action**            Set a valid port property into the deployment configuration file.

**WSSCLE0010**      **Service name [{0}] for undeployment is invalid.**

**Explanation**      The Web service added for undeployment does not have a valid service name.

**Action**            Add a valid service name for the Web service that you want to undeploy.

**WSSCLE0011**      **Archive data unit must not be "null".**

**Explanation**      The archive file added for deployment is null or invalid.

**Action**            Add a valid archive file for deployment.

**WSSCLE0012**      **Failed to parse the configured [{0}] with value [{1}]. The default value [{2}] will be used.**

**Explanation**      The given value for maxConnectionsPerHost is invalid or cannot be processed. A default value will be used instead.

**Action**            Set a valid positive integer for the value of maxConnectionsPerHost. Otherwise, an alternative default value will be used.

**WSSCLE0013**      **Failed to parse the configured [{0}] with value [{1}]. The default value [{2}] will be used.**

**Explanation**      The given value for maxTotalConnections is invalid or cannot be processed. A default value will be used instead.

**Action**            Set a valid positive integer for the value of maxTotalConnections. Otherwise, an alternative default value will be used.

---

<b>WSSCLE0014</b>	<b>There are no archives added for deployment.</b>
<b>Explanation</b>	Web service archives are not added for deployment or undeployment.
<b>Action</b>	Add Web service archives for deployment or undeployment.
<b>WSSCLE0015</b>	<b>An error is thrown during the retrieval of the deployment result.</b>
<b>Explanation</b>	Deployment result cannot be retrieved because of an error while executing the remote operation.
<b>Action</b>	Check the connection to the server and the error log.
<b>WSSCLE0016</b>	<b>An error is thrown during the retrieval of the deployment result. The cause of the error is: {0}</b>
<b>Explanation</b>	Deployment result cannot be retrieved because of an error while executing the remote operation.
<b>Action</b>	Check the connection to the server and the error log.
<b>WSSCLE0017</b>	<b>The URI given for deployment is invalid. The passed value is [{0}].</b>
<b>Explanation</b>	The given URI for deployment is empty or the given value cannot be parsed as a URI reference.
<b>Action</b>	Provide a valid, non-empty URI for deployment.
<b>WSSCLE0018</b>	<b>The org.apache.commons.httpclient.HostConfiguration object passed is "null".</b>
<b>Explanation</b>	The HostConfiguration is empty.
<b>Action</b>	Check that the properties set for the host have valid, non-empty values and check the connection.
<b>WSSCLE0019</b>	<b>An error while deploying Web services occurs due to a problem while invoking the operation on the remote server . Reason: {0}.</b>
<b>Explanation</b>	An error occurs during the deployment. The services cannot be deployed.
<b>Action</b>	Check the error log for details.
<b>WSSCLE0020</b>	<b>An error while undeploying services occurs due to a problem while invoking the operation on the remote server. Reason: {0}.</b>
<b>Explanation</b>	An error occurs during undeployment. The services cannot be undeployed.
<b>Action</b>	Check the error log for details.

<b>WSSCLE0021</b>	<b>An error while listing the Web services occurs due to a problem while invoking the operation on the remote server. Reason: {0}.</b>
<b>Explanation</b>	An error occurs while listing services.
<b>Action</b>	Check the error log for details.
<b>WSSCLE0022</b>	<b>An error while listing properties occurs due to a problem while invoking the operation on the remote server. Reason: {0}.</b>
<b>Explanation</b>	An error occurs while listing properties.
<b>Action</b>	Check the error log for details.
<b>WSSCLE0023</b>	<b>The given keystore file {0} cannot be converted to a URL.</b>
<b>Explanation</b>	The given value for the keystore file cannot be parsed.
<b>Action</b>	Provide a valid, non-empty value for the keystore file and check its location path.
<b>WSSCLE0024</b>	<b>The given truststore file {0} cannot be converted to a URL.</b>
<b>Explanation</b>	The given value for the truststore file cannot be parsed.
<b>Action</b>	Provide a valid, non-empty value for the truststore file and check its location path.
<b>WSSCLE0025</b>	<b>The given proxy port with value [{0}] is invalid.</b>
<b>Explanation</b>	The value provided for a proxy port is not in the correct format.
<b>Action</b>	Provide a valid proxy port. If you do not want to use a proxy port do not set a value to it.
<b>WSSCLE0030</b>	<b>The WSDL definition cannot be null.</b>
<b>Explanation</b>	You have not specified a WSDL definition.
<b>Action</b>	Specify a valid, non-empty WSDL definition.
<b>WSSCLE0031</b>	<b>The WSDL URL cannot be null.</b>
<b>Explanation</b>	You have not specified a WSDL URL or you have provided a null or empty value.
<b>Action</b>	Specify a valid, non-empty WSDL URL.

---

<b>WSSCLE0032</b>	<b>The constructor is not found.</b>
<b>Explanation</b>	You did not provide a valid constructor for the class.
<b>Action</b>	Check the parameters you used. One or more of them are not suitable for the class. Use one of the available constructors for instantiating the class.
<b>WSSCLE0033</b>	<b>This action is not supported.</b>
<b>Explanation</b>	You are trying to use functionality that is not yet implemented.
<b>Action</b>	This action is not supported. Contact Software AG Global Support.
<b>WSSCLE0034</b>	<b>Service [{0}] is not found.</b>
<b>Explanation</b>	The service with the specified name [{0}] is not available.
<b>Action</b>	Check the service name.
<b>WSSCLE0035</b>	<b>Problem getting the WSDL, HTTP error code: {0}.</b>
<b>Explanation</b>	The operation for getting the WSDL encounters a problem.
<b>Action</b>	Check the causes for the HTTP status error code.
<b>WSSCLE0036</b>	<b>Cannot apply Web service client policy.</b>
<b>Explanation</b>	Policy cannot be applied to the description hierarchy.
<b>Action</b>	Check and validate the configuration and the policy.
<b>WSSCLE0037</b>	<b>Cannot locate the security configuration file "{0}" specified in the axis2 configuration under the key "securityConfigFile".</b>
<b>Explanation</b>	The specified configuration security in the axis2 configuration file cannot be found. The properties cannot be loaded.
<b>Action</b>	If you want to load security properties from a custom security configuration file it must be placed in the proper place. The file is searched as defined in axis2 configuration under the key "securityConfigFile". Check the path and the file name.
<b>WSSCLE0038</b>	<b>Cannot close security configuration file properly.</b>
<b>Explanation</b>	An error occurs during close operation of the security configuration file.
<b>Action</b>	None.

<b>WSSCLE0039</b>	<b>The WSDL file or WSDL definition cannot be found.</b>
<b>Explanation</b>	In order to extract policies, either the WSDL location or the WSDL4J definition object must be valid. They are both missing or empty.
<b>Action</b>	Provide either a WSDL file or a valid WSDL definition.
<b>WSSCLE0040</b>	<b>The class of the supplied callback must extend org.apache.axis2.client.async.Callback.</b>
<b>Explanation</b>	The class of the supplied callback does not extend org.apache.axis2.client.async.Callback. It cannot be used.
<b>Action</b>	Provide a valid callback class.
<b>WSSCLE0041</b>	<b>Failed to create a new client factory instance.</b>
<b>Explanation</b>	Client factory instance cannot be created because the class cannot be found or instantiated.
<b>Action</b>	Check the configuration and the validity of the used constructor.
<b>WSSCLE0042</b>	<b>Failed to create new client factory instance.</b>
<b>Explanation</b>	The supplied factory class name argument does not resolve to a valid com.softwareag.wsstack.client.api.AbstractClientFactory implementation. Client factory instance cannot be created because the class name argument is not a com.softwareag.wsstack.client.api.AbstractClientFactory implementation.
<b>Action</b>	Give a fully qualified name of the factory implementation class that is going to be instantiated.
<b>WSSCLE0043</b>	<b>Output stream cannot be null.</b>
<b>Explanation</b>	The given output stream is not initialized or empty.
<b>Action</b>	Give a valid, non-empty output stream.
<b>WSSCLE0044</b>	<b>Policy input stream cannot be null.</b>
<b>Explanation</b>	The given policy input stream is not initialized or empty.
<b>Action</b>	Give a valid, non-empty policy input stream.

---

<b>WSSCLE0045</b>	<b>Failed to close the WSDL input stream after reading.</b>
<b>Explanation</b>	The close operation for the used WSDL input stream did not finish successfully.
<b>Action</b>	None.
<b>WSSCLE0046</b>	<b>The provided content is too large to be buffered: {0} bytes.</b>
<b>Explanation</b>	The content exceeds the maximum possible value that can be buffered.
<b>Action</b>	Contact Software AG Global Support.
<b>WSSCLE0047</b>	<b>Cannot create DataObject for type {0}.</b>
<b>Explanation</b>	The requested type {0} cannot be identified.
<b>Action</b>	The used data type is not supported. Use an alternative data type.
<b>WSSCLE0048</b>	<b>Failed to create a wsstack client instance out of the following class: "{0}".</b>
<b>Explanation</b>	A client instance cannot be created because the class cannot be found or instantiated.
<b>Action</b>	Check whether the name of the used class is correct.
<b>WSSCLE0049</b>	<b>Failed to create a wsstack client instance. The class "{0}" is not a valid IWSBasicClient implementation.</b>
<b>Explanation</b>	The defined class exists but its usage is incorrect. The class "{0}" cannot be used for instantiating a wsstack client because it is not a valid IWSBasicClient implementation.
<b>Action</b>	Define a valid implementation class.
<b>WSSCLE0050</b>	<b>The services are not added for undeployment</b>
<b>Explanation</b>	Web service archives are not added for undeployment.
<b>Action</b>	Add service archives for undeployment.
<b>WSSCLE0051</b>	<b>The WS-Stack Java version is older than the Java version of the compiled archive "{0}".</b>
<b>Explanation</b>	You compiled your archive with a newer Java version than the available in WS-Stack. The service cannot be deployed successfully.
<b>Action</b>	Compile the archive with an older Java version. You can check the supported Java version in the validation page of WS-Stack listed as java.version.

<b>WSSCLE0052</b>	<b>There is a corrupted Java class file in the following archive: "{0}".</b>
<b>Explanation</b>	One or more of the class files in the archive is corrupted or it is not a valid Java class file.
<b>Action</b>	Check the classes in your archive. Compile them with a supported Java version in WS-Stack and deploy the archive again.
<b>WSSCLE0053</b>	<b>An error occurred while reading the archive "{0}"; the archive is corrupted or empty.</b>
<b>Explanation</b>	The archive that you want to deploy is not valid. It may be empty or cannot be read.
<b>Action</b>	Check and validate the content of archive "{0}". You may need to repack the content and deploy it again.
<b>WSSCLE0054</b>	<b>An error occurred while manipulating the archive "{0}". The archive is locked or another Input/Output related problem has occurred.</b>
<b>Explanation</b>	Other processes locked the archive and it cannot be processed or an Input/Output related problem has interrupted the execution of the command.
<b>Action</b>	Deploy the archive again.
<b>WSSCLE0056</b>	<b>Cannot configure client factory thread pool.</b>
<b>Explanation</b>	The error occurs when the WSSStack client factory tries to configure a client instance to use a thread pool, and the client already has a thread pool set.
<b>Action</b>	Contact Software AG Global Support.
<b>WSSCLE0057</b>	<b>The specified attachment lifecycle manager instance is not valid.</b>
<b>Explanation</b>	The error occurs when the WSSStack client factory configures a client instance to use an attachment lifecycle manager set by the user, and the specified lifecycle manager property is not a valid instance of <code>org.apache.axiom.attachments.lifecycle.LifecycleManager</code> .
<b>Action</b>	Specify a valid instance of " <code>org.apache.axiom.attachments.lifecycle.LifecycleManager</code> " under the client factory property key " <code>attachmentsLifecycleManager</code> ".
<b>WSSCLE0058</b>	<b>Cannot configure attachment lifecycle manager for a client instance.</b>
<b>Explanation</b>	The error occurs when the Web Services Stack client factory configures a client instance to use a specific attachment lifecycle manager set by the user. Essentially, the error occurs when the attachment lifecycle parameter is locked.
<b>Action</b>	Contact Software AG Global Support.

---

<b>WSSCLE0059</b>	<b>The supplier object (an instance of {0}) is not a proxy instance.</b>
<b>Explanation</b>	The Web Services Stack client registry API provides a utility for retrieving the internal client configuration from a Web service proxy object. This error indicates that the tool is being used with a wrong proxy implementation (it is not a WSS compliant Web service client proxy).
<b>Action</b>	Modify your client implementation as the utility is used only with proxies created by the Web Services Stack registry API.
<b>WSSCLI0000</b>	<b>Unable to locate the default security configuration file "{0}".</b>
<b>Explanation</b>	The default security configuration file cannot be found and its properties are not loaded.
<b>Action</b>	If you want to load security properties from the default security configuration file, the file must be placed in the proper directory. The default security configuration file name is "wsclientsec.properties" and it must be either in the current working directory, or in "<REPOSITORY_DIRECTORY>/conf".
<b>WSSCLI0026</b>	<b>An XMLStreamException thrown.</b>
<b>Explanation</b>	The close operation for the used XMLStreamWriter did not finish successfully.
<b>Action</b>	None.
<b>WSSCLW0027</b>	<b>Unable to locate the default security configuration file: "{0}".</b>
<b>Explanation</b>	The default security configuration file cannot be found. Its properties are not loaded.
<b>Action</b>	If you want to load security properties from the default security configuration file you must put it in the proper place. The file is searched on the following location: "{0}".
<b>WSSCLW0028</b>	<b>The service policy is not set; cannot write service policy to the given stream.</b>
<b>Explanation</b>	The service policy is not set.
<b>Action</b>	To associate a policy, use one of the setPolicy methods first.
<b>WSSCLW0029</b>	<b>Overwriting an existing policy.</b>
<b>Explanation</b>	This is an existing policy and it is going to be overwritten.
<b>Action</b>	Do not use this method if you expect different behavior.

**WSSCLW0055**      **The parameters for max connections settings passed to configure the connection manager, associated with the HttpClient, caused a problem.**

**Explanation**      The default parameters will be used for the non-standard ones. \n  
 MAX\_HOST\_CONNECTIONS parameter passed is "{0}". \n  
 MAX\_TOTAL\_CONNECTIONS parameter passed is "{1}".

**Action**            None.

**WSSCME0001**      **Key value cannot be null or empty**

**Explanation**      The error appears when you prepare configuration properties parser of a security module. This implementation is used only in private constructors and therefore the error appears only if a severe implementation fault occurs.

**Action**            The error indicates a severe fault in the Web Services Stack implementation. If the error occurs, report it to the software development team.

**WSSCME0002**      **Rampart configuration element value cannot be null or empty**

**Explanation**      The message appears in an application program interface (API) method and reflects to an error in the implementation. The error appears when you update the security module configuration. It shows that you did not provide configuration to the update process.

**Action**            When you call a  
 WSCliientSecurityProperty#updateRampartConfigElement(OMEElement, String) the implementation ensures that the given OMEElement argument is not null or empty. Specify a valid entry for the OMEElement.

**WSSCME0003**      **Invalid value is configured for time-to-live timestamp: "{0}"**

**Explanation**      The configured time-to-live value for the timestamp used by the security module is invalid. The system expects an integer as a configuration value.

**Action**            Security module configuration for timestamp time-to-live must be an integer.

**WSSCME0004**      **Invalid value is configured for max skew timestamp: "{0}"**

**Explanation**      The configured max skew value for the timestamp used by the security module is invalid. The system expects an integer as a configuration value.

**Action**            Security module configuration for timestamp max skew must be an integer.

---

<b>WSSCME0005</b>	<b>Property name cannot be null or empty</b>
<b>Explanation</b>	You updated the security module configuration and did not specify a property for update.
<b>Action</b>	The error indicates a severe fault in the Web Services Stack implementation. If the error occurs, report it to the software development team.
<b>WSSCME0009</b>	<b>Rampart configuration assertion update error</b>
<b>Explanation</b>	The error occurs when xml serialization of an existing rampart configuration assertion fails. Prior to the update, the configuration assertion is serialized to stax stream and parsed with axiom. An invalid rampart configuration assertion can cause the error.
<b>Action</b>	If you configure the rampart configuration assertion manually, an invalid configuration can cause the error. Use the Web Services Stack configuration properties instead of providing manual configuration.
<b>WSSCME0019</b>	<b>Failed to decode the basic authentication header.</b>
<b>Explanation</b>	Web Services Stack security utility failed to decode the received HTTP Basic authentication header. The header should be encoded with base64 encoding. The error suggests that an illegal character (non-ASCII) was found within the header value.
<b>Action</b>	Make sure the http client sends an HTTP basic authentication header properly encoded in base64 encoding.
<b>WSSCMI0000</b>	<b>Cannot recognize the security configuration key "{0}"; the key is ignored.</b>
<b>Explanation</b>	Rampart configuration updater searches through the client options and dynamic service parameters for keys that refer to the security module configuration. The message is logged when it encounters an unrecognized key. For example, a general purpose key that does not control Rampart specific configuration.
<b>Action</b>	None.
<b>WSSCMW0020</b>	<b>Axis2 configuration file: '{0}' does not exist. Password change will be disabled.</b>
<b>Explanation</b>	The axis2 configuration file is missing. This disables the password change functionality.
<b>Action</b>	Contact Software AG global support.
<b>WSSCMW0021</b>	<b>Axis2 configuration file: '{0}' cannot be written. Password change will be disabled.</b>
<b>Explanation</b>	The axis2 configuration file cannot be written. This disables the password change functionality.
<b>Action</b>	Ensure that you can write in the axis2 configuration file.

<b>WSSCMW0022</b>	<b>Axis2 configuration URL '{0}' does not denote a valid file path. Password change will be disabled.</b>
<b>Explanation</b>	The path to the axis2 configuration file is invalid.
<b>Action</b>	Ensure that the URL to the axis2 configuration file is valid and that it is using file protocol.
<b>WSSCMW0023</b>	<b>AxisConfiguration instance does not have a valid configuration file URL set. Password change will be disabled.</b>
<b>Explanation</b>	AxisConfiguration is missing.
<b>Action</b>	Contact SoftwareAG global support.
<b>WSSCMW0025</b>	<b>Failed to close input stream to Axis2 configuration file: {0}</b>
<b>Explanation</b>	Internal error. Cannot change the axis2 configuration.
<b>Action</b>	Contact SoftwareAG global support.
<b>WSSCMW0026</b>	<b>Failed to close output stream to Axis2 configuration file: {0}</b>
<b>Explanation</b>	Internal error. Cannot change the axis2 configuration.
<b>Action</b>	Contact SoftwareAG global support.
<b>WSSDAE0000</b>	<b>Unsupported algorithm exception: {0}</b>
<b>Explanation</b>	A particular cryptographic algorithm is requested but is not available in the environment.
<b>Action</b>	Ensure that you have enabled unlimited strength JCE (Java Cryptographic Extension) on your machine. If you already have it enabled, contact Software AG Global Support.
<b>WSSDAE0016</b>	<b>Keystore exception: {0}</b>
<b>Explanation</b>	Keystore file can not be processed.
<b>Action</b>	Ensure that the keystore file is not corrupted and all required certificates are available in it.
<b>WSSDAE0017</b>	<b>Key management exception: {0}</b>
<b>Explanation</b>	Keystore file can not be processed.
<b>Action</b>	Ensure that the keystore file is not corrupted and all required certificates are available in it.

---

<b>WSSDAE0018</b>	<b>I/O error reading keystore/truststore file: {0}</b>
<b>Explanation</b>	Keystore file can not be processed.
<b>Action</b>	Ensure that the keystore file is available in the particular location.
<b>WSSDIE0000</b>	<b>Invalid or unsupported service scope set to AxisService: {0}.</b>
<b>Explanation</b>	The message appears when a service with an invalid scope is created or accessed. The following scopes are supported by Web Services Stack: application; transportsession; soapsession; request.
<b>Action</b>	Recreate your service using one of the following scopes: application; transportsession; soapsession; request.
<b>WSSDIE0001</b>	<b>Cannot create valid policy manager factory implementation.</b>
<b>Explanation</b>	The abstract policy manager factory fails to instantiate the default policy manager factory instance. The default factory implementation class is either not available or the user does not have permissions to access it.
<b>Action</b>	Ensure that the wsstack deployer-impl-[VERSION].jar is available on the classpath and the user who starts the java process has the proper permissions to access it.
<b>WSSDIE0002</b>	<b>Cannot create valid policy repository factory implementation.</b>
<b>Explanation</b>	The abstract policy repository factory fails to instantiate the default policy repository factory instance. The default factory implementation class is either not available or the user does not have permissions to access it.
<b>Action</b>	Ensure that the wsstack deployer-impl-[VERSION].jar is available on the classpath and that the user who starts the java process has the proper permissions to access it.
<b>WSSDIE0003</b>	<b>Cannot close a policy stream after parsing it.</b>
<b>Explanation</b>	Policy supplier cannot close the policy stream after parsing it.
<b>Action</b>	Ensure that the stream source is available and it is not locked by another process.
<b>WSSDIE0004</b>	<b>Cannot initialize the local policy repository; the axis configuration is not available.</b>
<b>Explanation</b>	Axis runtime configuration is not available to the policy repository. This means that the code is not executed in a properly initialized runtime.
<b>Action</b>	Ensure that you access the policy repository inside a properly initialized and started wsstack runtime.

<b>WSSDIE0005</b>	<b>Cannot create an invalid policies directory; the policy repository is null.</b>
<b>Explanation</b>	Invalid policies are automatically moved to a directory inside the policy repository. If the policy repository directory is not available, the invalid policies directory cannot be created.
<b>Action</b>	Ensure that the policy repository is properly initialized.
<b>WSSDIE0006</b>	<b>Duplicate policy ID; the policy file is moved to {0}.</b>
<b>Explanation</b>	The system detects that a policy is deployed with an ID that already exists in the policy repository. The new policy is moved to the invalid policies directory.
<b>Action</b>	When you deploy a policy, ensure that a policy with the same ID does not exist in the repository.
<b>WSSDIE0007</b>	<b>Cannot verify module support for a policy with the following ID: {0}.</b>
<b>Explanation</b>	The policy repository cannot verify whether a policy is supported (all assertions in it are recognized and there are modules deployed in the runtime that handle those assertions). The error occurs when the policy is invalid and/or does not contain any assertions.
<b>Action</b>	Ensure that the verified policy is valid and contains valid policy assertions.
<b>WSSDIE0008</b>	<b>Policy with the following key: {0} exists in the repository.</b>
<b>Explanation</b>	The policy repository contains a policy with the same ID as the policy that is deployed and the "updateIfPresent" flag is set to false.
<b>Action</b>	Ensure that the policy does not contain a policy with the same ID as the deployed one or set the flag "updateIfPresent" to true; that enables the update of the existing policy in the repository.
<b>WSSDIE0009</b>	<b>An error occurred during policy deployment.</b>
<b>Explanation</b>	An unexpected error occurs during policy deployment.
<b>Action</b>	Contact Software AG Global Support
<b>WSSDIE0010</b>	<b>The given policy does not contain any policy alternatives.</b>
<b>Explanation</b>	Cannot verify the policy against modules that support it because it does not contain any policy alternatives.
<b>Action</b>	Ensure that the deployed policy is valid and contains at least one policy alternative.

---

<b>WSSDIE0011</b>	<b>Cannot find a module to process the following assertion: {0}</b>
<b>Explanation</b>	There is no module deployed in the wsstack runtime that supports the given assertion.
<b>Action</b>	If the assertion requires additional processing by a specific module, ensure that the corresponding module is deployed on the wsstack runtime.
<b>WSSDIE0012</b>	<b>The following module: {0}; cannot process the assertion: {1}.</b>
<b>Explanation</b>	Although the module is registered to handle a certain policy assertion namespace, the module does not support the particular assertion.
<b>Action</b>	Ensure that the policy and all of its assertions are valid and can be processed by the module.
<b>WSSDIE0013</b>	<b>Cannot find a policy with the specified ID: {0}.</b>
<b>Explanation</b>	You are searching for a policy ID that is not available in the policy repository.
<b>Action</b>	Ensure that the policy you use is deployed to the policy repository.
<b>WSSDIE0014</b>	<b>The policy XML does not contain an ID, or a name that can be associated with the ID.</b>
<b>Explanation</b>	When a policy is deployed to the policy repository, the repository attempts to parse it and get its ID, or its name if an ID is not available. The ID or name afterward is used as a key for retrieving the policy from the repository. If there is no ID or a name in the policy XML, the repository cannot deploy it.
<b>Action</b>	Ensure that the policy XML that is deployed in the repository has either a valid (not empty) ID or a valid (not empty) name so that it can be deployed.
<b>WSSDIE0015</b>	<b>Cannot find an element with the following name: {0} and the following namespace: {1} in the policy input stream; the policy document is invalid.</b>
<b>Explanation</b>	When a policy is deployed to the policy repository, the repository attempts to parse it and get its ID, or its name if an ID is not available. The ID or name is used afterward as a key for retrieving the policy from the repository. If there is no ID or a name in the policy XML the repository cannot deploy it.
<b>Action</b>	Ensure that the policy XML includes a name or a wsu:Id attribute declared.
<b>WSSDIE0016</b>	<b>An exception occurs while trying to parse the policy input stream.</b>
<b>Explanation</b>	The policy repository fails to parse the policy XML stream.
<b>Action</b>	Assert that the deployed policy source is a valid XML.

<b>WSSDIE0017</b>	<b>Cannot close policy file input stream.</b>
<b>Explanation</b>	The policy repository cannot close policy stream after reading it.
<b>Action</b>	Ensure that the policy source is available.
<b>WSSDIE0018</b>	<b>Cannot initialize local policy repository; the following repository path is incorrect: "{0}".</b>
<b>Explanation</b>	When the policy repository is initialized it tries to create its directory or use the one that exists. This error occurs when the repository path exists on the file system but it is not a directory.
<b>Action</b>	Ensure that the repository path is a directory on the file system or does not exist (so that the policy repository can create it). Alternatively, you can configure another repository path if the configured one cannot be used.
<b>WSSDIE0019</b>	<b>Cannot move the following invalid policy file: "{0}"; to the invalid policies directory.</b>
<b>Explanation</b>	The policy repository detects that an invalid policy is deployed. The repository cannot move the invalid policy into the invalid policies directory.
<b>Action</b>	Ensure that you deploy a valid XML policy.
<b>WSSDIE0020</b>	<b>Cannot load a policy file during policy repository initialization.</b>
<b>Explanation</b>	The policy repository fails to deploy a problematic policy file.
<b>Action</b>	Ensure that the policy files in the policy repository are valid XML policies.
<b>WSSDIE0021</b>	<b>Cannot initialize local policy repository; the following repository path: "{0}" does not exist and cannot be created.</b>
<b>Explanation</b>	While the policy repository is initialized it checks whether the repository directory exists and if it does not, the repository attempts to create it. This message shows that the creation of the directory fails. The policy repository is not functional.
<b>Action</b>	Ensure that either the repository directory exists or the user who starts the java processes is authorized to create it.
<b>WSSDIE0022</b>	<b>Cannot initialize a local policy repository; the following repository path is incorrect: "{0}".</b>
<b>Explanation</b>	When the policy repository is initialized it tries to determine the repository directory path but it fails. The reason is that the code is not invoked inside an initialized wsstack runtime or the wsstack repository directory is not available (in case if a URL configurator is used, for example).
<b>Action</b>	Ensure that either the wsstack repository directory is available or configure a specific directory to be used as a policy repository directory.

---

<b>WSSDIE0023</b>	<b>Cannot create a default policy supplier object; the following policy file: "{0}" is not a valid file.</b>
<b>Explanation</b>	The file argument of the policy file that is deployed through a default policy supplier is either null or does not exist.
<b>Action</b>	When you deploy a file through the default policy supplier, ensure that the policy file exists on the file system at the time it is detected by the policy repository.
<b>WSSDIE0024</b>	<b>The following policy file does not exist: "{0}".</b>
<b>Explanation</b>	When a policy stream is retrieved through a default policy supplier instance, the policy file that is used by the supplier is not available.
<b>Action</b>	Ensure that the file with the policy you try to access is available in the policy repository.
<b>WSSDIE0025</b>	<b>Policy repository location must not be null.</b>
<b>Explanation</b>	Policy repository path is not available and therefore the default policy supplier cannot be created since it cannot store the policy in the repository.
<b>Action</b>	Ensure that the policy repository is properly initialized.
<b>WSSDIE0026</b>	<b>Cannot copy a policy to the repository.</b>
<b>Explanation</b>	When a policy stream is deployed through the default policy supplier, the supplier attempts to store the policy in repository directory. However, the copy procedure of the policy file to the repository directory fails.
<b>Action</b>	Ensure that the user who starts the java process is authorized to write to the policy repository directory. Another reason for the error is that the stream is closed before policy file is copied.
<b>WSSDIE0027</b>	<b>An error occurred during policy deployment while trying to close the file output stream.</b>
<b>Explanation</b>	A policy stream is deployed in the policy repository through a default policy supplier instance. While storing the stream to the policy repository directory, the supplier fails to close the original stream. However, the policy XML is successfully stored in the repository and the policy is effectively deployed.
<b>Action</b>	None.
<b>WSSDIE0028</b>	<b>The following policy repository does not exist and cannot be created: {0}.</b>
<b>Explanation</b>	The policy repository directory does not exist and cannot be created.
<b>Action</b>	Ensure that the policy repository is properly initialized. Ensure that the user who starts the java process is authorized to write in the specified repository directory.

<b>WSSDIE0029</b>	<b>Failed to delete a policy file.</b>
<b>Explanation</b>	A policy file deployed through a default policy supplier cannot be deleted.
<b>Action</b>	Ensure that the policy file is not locked by another process.
<b>WSSDIE0138</b>	<b>Cannot assign a policy to a service; a policy with the following ID cannot be found: "{0}".</b>
<b>Explanation</b>	The policy manager is requested to assign a policy to a certain service but the policy denoted by the supplied policy ID cannot be found in the policy repository.
<b>Action</b>	Ensure that the policy you attach exists in the policy repository.
<b>WSSDIE0144</b>	<b>Unsupported IDynamicDescription implementation; the WSPolicyManager implementation works only with dynamic description instances of type {0} but {1} is available.</b>
<b>Explanation</b>	Encountered an unrecognized dynamic description instance. Web Services Stack policy manager is intended to work with a specific implementation of the underlying dynamic description.
<b>Action</b>	If you use the default Web Services Stack policy manager, implement your dynamic assets so that they extend the default implementation of the deployer API.
<b>WSSDIE0158</b>	<b>Service {0} does not use a standard deployment classloader; the resource jar is not appended to the classpath of the classloader.</b>
<b>Explanation</b>	Service resource jar cannot be added to the service classpath. The service class loader is not an instance of org.apache.axis2.deployment.DeploymentClassLoader.
<b>Action</b>	Contact Software AG Global Support.
<b>WSSDIE0162</b>	<b>The method can be called on a deployed unit only.</b>
<b>Explanation</b>	The boolean isEngaged(String, boolean) method is called on an AxisDescription instance that has not been deployed on the Web Services Stack runtime yet. Therefore, it has no AxisConfiguration instance associated with it.
<b>Action</b>	Assert that the isEngaged module check is invoked on the deployed instance.
<b>WSSDIE0164</b>	<b>Web Services Stack policy manager failed to update or remove policy from associated services when handling a "policy file deleted" event fired by the policy repository due to: "{0}".</b>
<b>Explanation</b>	By default, the Web Services Stack policy manager is registered as a policy repository listener so it is notified when the policy repository detects that a policy file has been deleted. When such an event is received the policy manager attempts to remove the deleted policy from any associated attachment points (services, operations, or messages) and in the course of these actions the error occurs.
<b>Action</b>	This is an internal error. Contact Software AG Global Support.

---

<b>WSSDIE0165</b>	<b>Web Services Stack policy manager fails to update or remove policy from associated services when handling a "policy file updated" event fired by the policy repository due to: "{0}".</b>
<b>Explanation</b>	By default, the Web Services Stack policy manager is registered as a policy repository listener so it is notified when the policy repository detects that a policy file has been updated. When such an event is received the policy manager attempts to remove the policy from any associated attachment points (services, operations, or messages) in case the new policy has a different ID. If the new policy has the same ID as the previously deployed one (true update) it tries to refresh the policy attached to the respective subjects. In the course of these actions the error occurs.
<b>Action</b>	This is an internal error. Contact Software AG Global Support.
<b>WSSDIE0166</b>	<b>Cannot deploy policy file "{0}" as the policy is invalid. A file with name "{0}" already exists in the invalid policies directory. The existing file is overwritten.</b>
<b>Explanation</b>	You try to deploy more than once an invalid policy. A policy file with the same name already exists in the directory, in which invalid policies are maintained. The existing file is overwritten with the new one (the file is updated).
<b>Action</b>	Check the policy you want to deploy.
<b>WSSDIE0167</b>	<b>The policy ID or name is invalid. The policy is not deployed.</b>
<b>Explanation</b>	The policy ID or name, if available, cannot contain whitespace characters inside. If whitespace characters are found inside, the policy is considered invalid and the policy file is moved to the invalid folder.
<b>Action</b>	Check the policy ID or name for whitespace characters and remove them, if any.
<b>WSSDIE0168</b>	<b>Cannot deploy policy "{0}"; the policy is invalid and cannot be processed.</b>
<b>Explanation</b>	There is a problem while processing the policy. The policy file is corrupted or the XML is invalid.
<b>Action</b>	Check and validate the policy XML, check for typographical errors, and so on. Finally, deploy the policy again.
<b>WSSDIE0169</b>	<b>Failed to roll back disengage of the following module: {0}.</b>
<b>Explanation</b>	An error occurs while disengaging modules, the system attempts to re-engage them but the corresponding module fails.
<b>Action</b>	Contact Software AG Global Support.

<b>WSSDIE0170</b>	<b>Failed to disengage module {0}. Reason: {1}</b>
<b>Explanation</b>	While removing policy components for the current DynamicDescription instance, the system attempts to disengage a referenced module but it fails.
<b>Action</b>	Contact Software AG Global Support.
<b>WSSDIE0171</b>	<b>Exceptions must not be generated when skipping module disengagement.</b>
<b>Explanation</b>	Policy cleanup must not generate any exceptions if module disengagement argument is not set.
<b>Action</b>	Contact Software AG Global Support.
<b>WSSDIE0172</b>	<b>Cannot refresh services after the "{0}" policy is updated due to the following: "{1}".</b>
<b>Explanation</b>	Web Services Stack policy manager is automatically updating policy subjects upon a policy update with a certain ID. The update fails when applying the new policy to the subjects.
<b>Action</b>	Contact Software AG Global Support.
<b>WSSDIE0173</b>	<b>Failed to create a dynamic deployer instance.</b>
<b>Explanation</b>	The exception occurs while trying to initialize the default policy manager instance and it fails to initialize the dynamic deployer. This happens when no valid Axis configuration is found.
<b>Action</b>	Ensure that the code is running in properly started and initialized Web Services Stack runtime.
<b>WSSDIE0174</b>	<b>Cannot clean policy of the following Web service: "{0}".</b>
<b>Explanation</b>	The policy manager failed to remove policies for the given Web service. Generally, the exception is generated when the disengageModules flag is set to true. However, this is not what causes the problem in this invocation.
<b>Action</b>	Redeploy your Web service.
<b>WSSDIE0175</b>	<b>Cannot clean policy of the Web service "{0}" operation "{1}".</b>
<b>Explanation</b>	The policy manager failed to clean the policy on the given operation of the given Web service. Generally, the exception is thrown only when the disengageModules flag is set to true. However, this is not what causes the problem in this invocation.
<b>Action</b>	Redeploy your Web service.

---

<b>WSSDIE0176</b>	<b>Cannot clean message policy for service "{0}" operation "{1}".</b>
<b>Explanation</b>	The policy manager failed to clean the message policy on the given operation of the given service. Generally, the exception is thrown only when the disengageModules flag is set to true. However, this is not what causes the problem in this invocation.
<b>Action</b>	Redeploy your Web service.
<b>WSSDIE0178</b>	<b>Failed to retrieve the following service group after persisting and redeploying it: "{0}".</b>
<b>Explanation</b>	The Dynamic deployer API was used to persist a service group but after redeploying the service group could not be found in Web Services Stack runtime. A possible cause for the error is a problem during the deployment.
<b>Action</b>	Ensure that the service group file or directory is not locked, and the current user has the credentials to write to it. Redeploy your Web service manually.
<b>WSSDIE0179</b>	<b>Exception occurs while trying to obtain policy manager instance and the policy manager cannot be notified about redeployed Web services.</b>
<b>Explanation</b>	When a service is persisted the Web Services Stack runtime undeploys and redeploys it again. That makes any references kept to the previous Web service invalid. Since the policy manager keeps associations between policies and attachment points (such as Web services) it needs to be notified to synchronize its cache.
<b>Action</b>	The system is automatically recovered but the policy manager's cached association for the updated Web services are lost.
<b>WSSDIE0180</b>	<b>Failed to retrieve the following Web service "{0}" after persisting and redeploying it.</b>
<b>Explanation</b>	The Dynamic deployer API was used to persist a Web service but after redeploying the Web service cannot be found in the Web Services Stack runtime. A possible cause for the error is a problem during the deployment.
<b>Action</b>	Ensure that the Web service file or directory is not locked and the current user has permissions to write to it. Redeploy your Web service manually.
<b>WSSDIE0181</b>	<b>Web Services Stack policy engine failed to parse the deployed policy.</b>
<b>Explanation</b>	An exception occurred while the policy engine was processing a freshly deployed policy. Most probably the policy xml is invalid.
<b>Action</b>	Correct the policy xml and redeploy it.

<b>WSSDIE0184</b>	<b>Security exception during fetch of class field.</b>
<b>Explanation</b>	This is an internal error caused by an API inconsistency.
<b>Action</b>	Contact SoftwareAG global support.
<b>WSSDIE0185</b>	<b>Unreachable field with name {0} in class {1}</b>
<b>Explanation</b>	This is an internal error caused by an API inconsistency.
<b>Action</b>	Contact SoftwareAG global support.
<b>WSSDIE0186</b>	<b>Illegal argument: engageModules passed to method.</b>
<b>Explanation</b>	This is an internal error caused by an API inconsistency.
<b>Action</b>	Contact SoftwareAG global support.
<b>WSSDIE0187</b>	<b>Illegal access to field with name {0} in class {1}</b>
<b>Explanation</b>	This is an internal error caused by an API inconsistency.
<b>Action</b>	Contact SoftwareAG global support.
<b>WSSDIE0189</b>	<b>Failed to read the policy file.</b>
<b>Explanation</b>	The policy file could not be read or is invalid.
<b>Action</b>	Verify that your policy file is compliant with WS Security specification.
<b>WSSDIW0163</b>	<b>Modules cannot be engaged at the following binding hierarchy - Endpoint (port), Binding, Binding operation, Binding Message.</b>
<b>Explanation</b>	Axis2 does not support engaging modules at the listed subjects and respectfully calling isEngaged on those axis objects throws an UnsupportedOperationException.
<b>Action</b>	Invalid invocation. This method cannot be invoked on IDynamicPort, IDynamicBinding, IDynamicBindingOperation, or IDynamicBindingMessage.
<b>WSSDIW0177</b>	<b>Parent service group is not found for the following Web service: "{0}".</b>
<b>Explanation</b>	The dynamic deployer could not find the parent service group of the given Web service.
<b>Action</b>	Ensure that the Web service is properly deployed or redeploy it.

<b>WSSDIW0190</b>	<b>Expected dialect "{0}" but found "{1}" ,cannot proceed.</b>
<b>Explanation</b>	Found unexpected dialect in the specified request.
<b>Action</b>	Set proper dialect. If you are unable to do so, contact Software AG global support.
<b>WSSDIW0191</b>	<b>Null or empty policy identifier given, cannot proceed.</b>
<b>Explanation</b>	Policy identifier is invalid.
<b>Action</b>	Set proper identifier. If you are unable to do so, contact Software AG global support.
<b>WSSDSE0000</b>	<b>In order to deploy JAX-WS services you must have a JAX-WS Deployer configured in your axis2.xml.</b>
<b>Explanation</b>	The <deployer extension=".jar" directory="servicejars" class="org.apache.axis2.jaxws.framework.JAXWSDeployer"/> line in your axis2.xml is commented or missing.
<b>Action</b>	Uncomment the <deployer extension=".jar" directory="servicejars" class="org.apache.axis2.jaxws.framework.JAXWSDeployer"/> line in the axis2.xml, or add it if it is missing.
<b>WSSDSE0011</b>	<b>An error occurs while trying to remove the following security provider: "{0}".</b>
<b>Explanation</b>	Before the SAGAdminServlet is destroyed, it checks whether the BouncyCastle and JuiCE are added to the java security providers and whether they are loaded by the current web application classloader. If it is true, the servlet tries to remove them, as they are not available to other web applications. This error occurs when the servlet tries to cleanup the BouncyCastle and JuiCE providers from the list.
<b>Action</b>	Contact Software AG Global Support
<b>WSSDSE0012</b>	<b>DeployServlet requires the following instance in the servlet context but cannot find it: "{0}".</b>
<b>Explanation</b>	An Axis2 "org.apache.axis2.deployment.DeploymentEngine" instance has to be available in Web Services Stack DeployServlet's servlet context under the DEPLOYER servlet context attribute but such an attribute is not found.
<b>Action</b>	The reason for the error is that Web Services Stack Administration servlet fails to initialize. Make sure that the servlet is properly initialized.
<b>WSSDSW0013</b>	<b>Cannot find the axi2.xml file location in the known locations.</b>
<b>Explanation</b>	The axis2 configuration file is missing.
<b>Action</b>	Make sure the axis2 configuration file is the proper location.

<b>WSSDSW0014</b>	<b>Cannot find the axi2.xml location due to an error.</b>
<b>Explanation</b>	The axis2 configuration could not be obtained.
<b>Action</b>	Contact SoftwareAG global support.
<b>WSSJCE0012</b>	<b>Module "{0}" is engaged but configuration for a JAX-WS handler-chain was not found.</b>
<b>Explanation</b>	The module is engaged, but it does not contain any JAX-WS handlers configured into the chain.
<b>Action</b>	Inspect the engaged module if it contains the expected JAX-WS handlers.
<b>WSSJCE0015</b>	<b>The JAX-WS handler chain cannot be loaded.</b>
<b>Explanation</b>	The JAX-WS handler-chain descriptor (XML) file is not correct or the handler instances configured in it cannot be loaded.
<b>Action</b>	Inspect and correct the JAX-WS handler-chain descriptor (XML) file.
<b>WSSJCE0018</b>	<b>An incorrect property value is set for the JAX-WS handler-chain.</b>
<b>Explanation</b>	The JAX-WS handler-chain descriptor (XML) file has an incorrect property value set for a JAX-WS handler.
<b>Action</b>	Check and correct the JAX-WS handler-chain descriptor (XML) file.
<b>WSSJCE0019</b>	<b>An error occurs in the JAX-WS handler-chain execution.</b>
<b>Explanation</b>	At the invocation of JAX-WS in/out flow, an exception is thrown while processing the chain.
<b>Action</b>	For more information about the failure, see the AxisFault response message. Check the JAX-WS chain configuration.
<b>WSSJCW0001</b>	<b>A handler class of the handler chain cannot be found.</b>
<b>Explanation</b>	Classes are missing for some handler instances configured into the handler-chain descriptor (XML) file.
<b>Action</b>	Check that the handler classes configured into the handler-chain descriptor (XML) file are available into the jar library (class-path).

---

<b>WSSJCW0002</b>	<b>A handler of the handler chain cannot be instantiated.</b>
<b>Explanation</b>	A class of the handler available into the classpath is not a standard one.
<b>Action</b>	Check that the handler class available into the jar library is the original one provided by the product and was not modified improperly.
<b>WSSJCW0004</b>	<b>The configuration of a class from the handler chain is incorrect.</b>
<b>Explanation</b>	A class of the handler available into the classpath is not a standard one.
<b>Action</b>	Check that the handler class available into the jar library is the original one provided by the product and was not modified improperly.
<b>WSSJCW0005</b>	<b>An error occurs while loading the JAX-WS handler chain.</b>
<b>Explanation</b>	A class of the handler available into the classpath is not a standard one.
<b>Action</b>	Check that the handler class available into the jar library is the original one provided by the product and was not modified improperly.
<b>WSSJCW0009</b>	<b>An error occurs while executing PreDestroy methods of the JAX-WS handlers. {0}</b>
<b>Explanation</b>	A JAX-WS handler executed into the chain, throws an exception while destroying it after being used.
<b>Action</b>	Check that the handler class available into the jar library or its XML configuration file were not modified improperly.
<b>WSSJCW0011</b>	<b>An error occurs while executing PostConstruct methods of the JAX-WS handlers. {0}</b>
<b>Explanation</b>	A JAX-WS handler executed into the chain throws an exception during its initialization.
<b>Action</b>	Check that the handler jar archive or its XML configuration file were not modified improperly.
<b>WSSJHE0003</b>	<b>An error occurs during the completion of a JAX-WS handler.</b>
<b>Explanation</b>	An error occurs into the flow when closing a JAX-WS handler.
<b>Action</b>	Check whether the handler class that is available into the jar library or its XML configuration file are not modified improperly.

<b>WSSJHE0004</b>	<b>JAX-WS handler PreDestroy method failed.</b>
<b>Explanation</b>	An error occurs when invoking a JAX-WS handler PreDestroy method.
<b>Action</b>	Check whether the Handler class that is available into the jar library or its XML configuration file are not modified improperly.
<b>WSSJHE0008</b>	<b>A JAX-WS handler failed.</b>
<b>Explanation</b>	An error occurs when invoking a JAX-WS handler.
<b>Action</b>	Check whether the handler class that is available into the jar library or its XML configuration file are not modified improperly.
<b>WSSJHE0010</b>	<b>A JAX-WS handler instantiation failed for the following classname: {0}.</b>
<b>Explanation</b>	An error occurs during JAX-WS handler instantiation.
<b>Action</b>	Check whether the handler class that is available into the jar library or its XML configuration file are not modified improperly.
<b>WSSJHE0011</b>	<b>The JAX-WS handler {1} is not type {0}.</b>
<b>Explanation</b>	An error occurs during JAX-WS handler invocation.
<b>Action</b>	Check whether the handler class that is available into the jar library or its XML configuration file are not modified improperly.
<b>WSSJNE0000</b>	<b>Could not read the value, Illegal state exception.</b>
<b>Explanation</b>	The provided JSON data is invalid.
<b>Action</b>	Make sure the provided JSON data is valid.
<b>WSSJNE0001</b>	<b>IO error while reading JSON stream.</b>
<b>Explanation</b>	An error during reading/writing JSON data.
<b>Action</b>	Check your connectivity and try again.
<b>WSSJNE0004</b>	<b>Could not load configured json type converter "{0}".</b>
<b>Explanation</b>	Missing JSON type converter class.
<b>Action</b>	Make sure that the service archive (aar file) contains a configured JSON type converter class.

---

<b>WSSJNE0005</b>	<b>Could not instantiate configured json type converter "{0}".</b>
<b>Explanation</b>	Invalid converter class definition.
<b>Action</b>	Check the converter class definition.
<b>WSSJNE0006</b>	<b>Could not access configured json type converter class "{0}".</b>
<b>Explanation</b>	Invalid converter class definition.
<b>Action</b>	Check the converter class definition. Make your class/default constructor public.
<b>WSSJNE0007</b>	<b>Could not load configured json type converter "{0}".</b>
<b>Explanation</b>	Missing JSON type converter class.
<b>Action</b>	Make sure that the service archive (aar file) contains a configured JSON type converter class.
<b>WSSJNE0008</b>	<b>Configured json type converter class "{0}" cannot be cast to type converter interface class "{1}".</b>
<b>Explanation</b>	Invalid converter class definition.
<b>Action</b>	Check the converter class definition and ensure it implements the type converter interface.
<b>WSSJNE0014</b>	<b>Failed to configure type converter, the JSON formatter will use the default type converter. Reason: {0}</b>
<b>Explanation</b>	Could not load the configured custom JSON type converter.
<b>Action</b>	Ensure the configured custom JSON type converter class is valid and available on the classpath.
<b>WSSJNW0010</b>	<b>Could not load configured json type converter "{0}" using class loader of service "{1}", falling back to Web Services Stack class loader.</b>
<b>Explanation</b>	The configured JSON type converter could not be loaded from service archive (aar file) and Web Services Stack will attempt to load it using Web Services Stack class loader.
<b>WSSJNW0011</b>	<b>{0} - Ignoring "{1}" parameter with null value.</b>
<b>Explanation</b>	The configured JSON type converter parameter has a null value.
<b>Action</b>	Check the configured 'json.type.converter' parameter definition and ensure it specifies a non-null value.

<b>WSSJNW0012</b>	<b>Unable to obtain current element class name due to {0}</b>
<b>Explanation</b>	Current class name element could not be obtained.
<b>Action</b>	Contact SoftwareAG global support.
<b>WSSJNW0013</b>	<b>{0} - Ignoring "{1}" parameter with a non-String value ({2})</b>
<b>Explanation</b>	The configured JSON type converter parameter has a non-String value.
<b>Action</b>	Check the configured 'json.type.converter' parameter definition and ensure it specifies a String value.
<b>WSSMRE0003</b>	<b>The service does not define adapter class parameter: "{0}"</b>
<b>Explanation</b>	When com.softwareag.wsstack.message receivers.AdapterMessageReceiver is invoked, it tries to find a parameter named adapter in the currently invoked service. The adapter parameter denotes a name of a class that implements the com.softwareag.wsstack.adapter.api.Adapter interface. The message receiver attempts to instantiate and execute the configured adapter.
<b>Action</b>	Add an adapter parameter to your service definition (in your services.xml file). As a value to the parameter, set the required adapter implementation class.
<b>WSSMRE0004</b>	<b>The configured adapter class is invalid: "{0}"</b>
<b>Explanation</b>	When com.softwareag.wsstack.message receivers.AdapterMessageReceiver is invoked, it tries to find a parameter named adapter in the currently invoked service. The adapter parameter denotes a name of a class that implements the com.softwareag.wsstack.adapter.api.Adapter interface. The message receiver attempts to instantiate and execute the configured adapter.
<b>Action</b>	Specify a valid adapter class name as a value to the adapter parameter in your service definition.
<b>WSSOGE0000</b>	<b>Failed to add service {0}</b>
<b>Explanation</b>	Failed to add service.
<b>Action</b>	Contact SoftwareAG global support.
<b>WSSOGE0001</b>	<b>Failed to handle service modification {0}</b>
<b>Explanation</b>	Failed to handle service modification.
<b>Action</b>	Contact SoftwareAG global support.

---

<b>WSSOGE0002</b>	<b>Failed to handle service removal {0}</b>
<b>Explanation</b>	Failed to handle service removal.
<b>Action</b>	Contact SoftwareAG global support.
<b>WSSOGE0003</b>	<b>Failed to add service {0}</b>
<b>Explanation</b>	Internal error. Failed to add service.
<b>Action</b>	Contact SoftwareAG global support.
<b>WSSOGE0004</b>	<b>Failed to handle service removal {0}</b>
<b>Explanation</b>	Internal error. Failed to handle service removal.
<b>Action</b>	Contact SoftwareAG global support.
<b>WSSOGE0010</b>	<b>The specified {0} property points to a non-existing or non-readable file. Using default.</b>
<b>Explanation</b>	The main axis2.xml configuration file is missing.
<b>Action</b>	Make sure that the configured axis2.xml file is in the correct location and is readable.
<b>WSSOGE0013</b>	<b>Cannot set axi2.xml URL as axisConfig parameter.</b>
<b>Explanation</b>	Internal error. Cannot set the axi2.xml URL as an axisConfig parameter.
<b>Action</b>	Contact SoftwareAG global support.
<b>WSSOGE0016</b>	<b>Error during module shutdown: {0}</b>
<b>Explanation</b>	Internal error. The error occurred during module shutdown.
<b>Action</b>	Contact SoftwareAG global support.
<b>WSSOGE0021</b>	<b>Failed to remove group {0}</b>
<b>Explanation</b>	Internal error. Failed to remove group.
<b>Action</b>	Contact Software AG global support.
<b>WSSOGE0023</b>	<b>Failed to resolve relative resource: {0} from bundle {1}</b>
<b>Explanation</b>	Internal error. Failed to resolve resource from a bundle.
<b>Action</b>	Contact Software AG global support.

<b>WSSOGE0025</b>	<b>Failed to resolve relative resource {0} from bundle {1}</b>
<b>Explanation</b>	Internal error. Failed to resolve resource from a bundle.
<b>Action</b>	Contact Software AG global support.
<b>WSSOGE0031</b>	<b>AxisConfigurator instance (class '{0}') does not derive from {1}, Web Services Stack Deploy Servlet will not be functional.</b>
<b>Explanation</b>	Provided axis configurator is not aware of the axis deploy engine.
<b>Action</b>	Contact Software AG global support.
<b>WSSPWE0000</b>	<b>UsernameToken authentication failed.</b>
<b>Explanation</b>	Invalid or empty password provided.
<b>Action</b>	Provide valid credentials.
<b>WSSPWE0001</b>	<b>Unknown password callback type: {0}.</b>
<b>Explanation</b>	Invalid usage of the password callback handler. Valid usage is for signing, decryption, and username password validation.
<b>Action</b>	Provide a valid usage of the callback handler.
<b>WSSPWE0004</b>	<b>The system cannot load the LDAP configuration for the password callback handler: {0}.</b>
<b>Explanation</b>	The password callback handler needs LDAP configuration. If it is not configured, the default LDAP configuration ldap.properties is used. LDAP configuration file cannot be loaded.
<b>Action</b>	Provide valid LDAP configuration.
<b>WSSPWE0008</b>	<b>Invalid LDAP configuration for the password callback handler.</b>
<b>Explanation</b>	One or more of the required LDAP configuration properties are not available in the LDAP configuration.
<b>Action</b>	Provide all required LDAP configuration properties.
<b>WSSPWE0009</b>	<b>UsernameToken authentication failed.</b>
<b>Explanation</b>	Invalid or empty password provided. The user cannot be authenticated.
<b>Action</b>	Provide valid, non-empty values for username and password.

---

<b>WSSPWE0010</b>	<b>Cannot recognize the following user ID: "{0}".</b>
<b>Explanation</b>	Invalid or empty username, or certificate alias provided.
<b>Action</b>	Check the spelling and provide a valid, non-empty value for username, or certificate alias (depending on the use case).
<b>WSSPWE0012</b>	<b>System cannot load the password callback handler configuration file: {0}.</b>
<b>Explanation</b>	The password callback handler configuration file is not found and cannot be loaded.
<b>Action</b>	Check if the configuration file exists and if the path to the file is correct.
<b>WSSPWE0013</b>	<b>Cannot convert the configuration from a stream to an OMElement: {0}.</b>
<b>Explanation</b>	A problem occurs while converting the configuration file content to an OMElement.
<b>Action</b>	Check and validate the XML format of the configuration file.
<b>WSSRME0000</b>	<b>Exception on callback.</b>
<b>Explanation</b>	Internal error. Failed to receive message on callback.
<b>Action</b>	Contact Software AG global support.
<b>WSSRME0001</b>	<b>Exception on callback.</b>
<b>Explanation</b>	Internal error. Failed to receive message on callback.
<b>Action</b>	Contact Software AG global support.
<b>WSSTLW0013</b>	<b>Password must comply with 3 out of the following 4 rules: at least 1 uppercase character, 1 lowercase character, 1 digit, and 1 special character. Minimum password length is 10 characters.</b>
<b>WSSTRE0001</b>	<b>Cannot close the input stream of the file; the file absolute path value is [{0}]. The exception message is: {1}.</b>
<b>Explanation</b>	Cannot close a file input stream or cannot release system resources associated with the stream.
<b>Action</b>	Check the file state. For example, it can be locked by another process.

<b>WSSTRE0002</b>	<b>The used key cannot be "null".</b>
<b>Explanation</b>	The key that is used for a property is null.
<b>Action</b>	Contact Software AG Global Support.
<b>WSSTRE0003</b>	<b>Cannot close an input/output stream of type {{0}}; the exception message is: {1}</b>
<b>Explanation</b>	There is an exception during input/output stream closure.
<b>Action</b>	Contact Software AG Global Support.
<b>WSSTRE0004</b>	<b>There is an error while manipulating an input/output stream in use.</b>
<b>Explanation</b>	There is an exception during input/output stream processing.
<b>Action</b>	Contact Software AG Global Support.
<b>WSSTRE0005</b>	<b>The repository listener is not initialized.</b>
<b>Explanation</b>	The repository listener is not initialized.
<b>Action</b>	Contact Software AG Global Support.
<b>WSSTRE0006</b>	<b>The following operation is not supported: {{0}}.</b>
<b>Explanation</b>	Non existing operation requested.
<b>Action</b>	Check that an operation with the specified name exists. Contact Software AG Global Support.
<b>WSSTRE0007</b>	<b>Cannot delete the file with the following file path: {{0}}.</b>
<b>Explanation</b>	There is a problem deleting the file.
<b>Action</b>	Check that the file exists and it is not locked. Check that you have sufficient permissions to delete the file.
<b>WSSTRE0008</b>	<b>Cannot create a directory in the following location: {{0}}.</b>
<b>Explanation</b>	There is a problem while creating a "services" directory.
<b>Action</b>	Contact Software AG Global Support.
<b>WSSTRE0009</b>	<b>The following Web service element cannot be null: {0}.</b>
<b>Explanation</b>	The Web service element is null.
<b>Action</b>	Check the content structure of the Web service that is deployed dynamically.

---

<b>WSSTRE0010</b>	<b>The name of the Web service client {0} must not be null or empty.</b>
<b>Explanation</b>	The name of the Web service client that is instantiated is null or empty.
<b>Action</b>	Check the Web service client implementation.
<b>WSSTRE0011</b>	<b>Cannot delete the following directory: [{0}].</b>
<b>Explanation</b>	There is a problem while deleting a Web service directory.
<b>Action</b>	Check that the Web service directory is not locked and check that you have sufficient permissions to delete the directory.
<b>WSSXTE0000</b>	<b>{0}: An XML document that is empty, invalid or does not exist.</b>
<b>Explanation</b>	The document is empty or invalid.
<b>Action</b>	Provide a valid, non-empty XML document.
<b>WSSXTE0013</b>	<b>Unexpected element found after the SOAP Body element: "{0}"</b>
<b>Explanation</b>	Web Services Stack is processing an invalid message. The sent message contains an unexpected element in the SOAP Envelope after the SOAP Body element. A SOAP Envelope is expected to contain only an optional SOAP Header element followed by one SOAP Body element.
<b>Action</b>	Inform the web service conversation partner that they are generating invalid web service messages.
<b>WSSXTE0014</b>	<b>Unexpected element found after the SOAP envelope has been consumed: "{0}"</b>
<b>Explanation</b>	Web Services Stack is processing an invalid message. The sent message contains an unexpected element after the already consumed SOAP Envelope. A web service message is expected to contain a single SOAP Envelope element.
<b>Action</b>	Inform the web service conversation partner that they are generating invalid web service messages.
<b>WSSXTE0016</b>	<b>Failed to marshall response object.</b>
<b>Explanation</b>	Internal error. Failed to marshall response object.
<b>Action</b>	Contact Software AG global support.

<b>WSSXTE0017</b>	<b>Could not close piped output stream.</b>
<b>Explanation</b>	Internal error. Could not close piped output stream.
<b>Action</b>	Contact Software AG global support.
<b>WSSXTE0018</b>	<b>Invalid timeout value format: not a number.</b>
<b>Explanation</b>	Illegal number for timeout config parameter.
<b>Action</b>	Check timeout parameters: SO_TIMEOUT, CONNECTION_TIMEOUT
<b>WSSXTW0019</b>	<b>Could not obtain inbound message context.</b>
<b>Explanation</b>	The obtained axis2 message context is invalid.
<b>Action</b>	Contact SoftwareAG global support.

# 30 Universal Messaging Messages

---

<b>NUMSPME0001</b>	<b>Unexpected exception encountered.</b>
<b>Explanation</b>	An unexpected exception occurred.
<b>Action</b>	Check the detailed error message. Contact Software AG Global Support for further assistance.
<b>NUMSPME0002</b>	<b>An error occurred while identifying the inventory components of Universal Messaging.</b>
<b>Explanation</b>	Unexpected exception occurred while identifying the inventory components of Universal Messaging.
<b>Action</b>	Please contact webMethods Administrator.
<b>NUMSPME0003</b>	<b>An error occurred while retrieving the interfaces configured for Universal Messaging.</b>
<b>Explanation</b>	Unable to read the adapters.nst file.
<b>Action</b>	Please contact webMethods Administrator.
<b>NUMSPME0005</b>	<b>Invalid configuration instance. {0} entered.</b>
<b>Explanation</b>	Format of the port configuration is wrong.
<b>Action</b>	Contact your webMethods product administrator and re-configure the port settings.

<b>NUMSPME0006</b>	<b>Invalid configuration object. {0} expected.</b>
<b>Explanation</b>	Format of the port configuration is wrong.
<b>Action</b>	Contact your webMethods product administrator and re-configure the port settings.
<b>NUMSPME0007</b>	<b>Invalid input for the port alias.</b>
<b>Explanation</b>	The input for the port alias is not valid.
<b>Action</b>	Input a valid port alias or keep the port alias field empty.
<b>NUMSPME0008</b>	<b>SSL configuration cannot be set for a non-SSL port.</b>
<b>Explanation</b>	SSL configuration can be set only for the SSL ports.
<b>Action</b>	Remove the SSL configuration from the non-SSL port and try again.
<b>NUMSPME0009</b>	<b>The configuration instance ID argument is missing.</b>
<b>Explanation</b>	The configuration instance ID is required to load the port configuration.
<b>Action</b>	Specify the configuration instance ID.
<b>NUMSPME0010</b>	<b>No port matches the provided configuration instance ID.</b>
<b>Explanation</b>	The provided configuration instance ID is incorrect.
<b>Action</b>	Verify the configuration instance ID provided for configuration update.
<b>NUMSPME0011</b>	<b>Protocol entered for the interface is incorrect.</b>
<b>Explanation</b>	The protocol can only be NSP, NHP, NSPS, or NHPS.
<b>Action</b>	Verify the protocol value entered for the port.
<b>NUMSPME0012E</b>	<b>Unable to connect to the UM realm server.</b>
<b>Explanation</b>	Unable to connect to the UM realm server. None of the interfaces can connect to the realm server.
<b>Action</b>	Verify if at least one interface is available for the realm server.
<b>NUMSPME0013</b>	<b>At least one port must be specified.</b>
<b>Explanation</b>	Port configuration is not specified in the port settings input.
<b>Action</b>	Add the port configuration to the port settings input.

---

<b>NUMSPME0014</b>	<b>Error occurred while saving the port configurations.</b>
<b>Explanation</b>	Unable to save the port configurations.
<b>Action</b>	See the detailed error message and verify the cause of failure.
<b>NUMSPME0015</b>	<b>Only one set of port settings is allowed.</b>
<b>Explanation</b>	More than one set of port settings are passed in the input.
<b>Action</b>	Configure only one set of port setting.
<b>NUMSPME0016</b>	<b>Universal Messaging port number must not be changed.</b>
<b>Explanation</b>	Attempted to change the Universal Messaging port number.
<b>Action</b>	Do not modify the port number.
<b>NUMSPME0017</b>	<b>Universal Messaging Server port type must be STANDARD.</b>
<b>Explanation</b>	Universal Messaging Server port type is not STANDARD.
<b>Action</b>	Set the Universal Messaging Server port type as STANDARD.
<b>NUMSPME0018</b>	<b>Universal Messaging Server protocol must be NSP, NHP, NHPS, or NSPS.</b>
<b>Explanation</b>	Universal Messaging Server protocol is not valid.
<b>Action</b>	Set NSP, NHP, NSPS, or NHPS as the Universal Messaging port protocol.
<b>NUMSPME0019</b>	<b>Do not modify the BindAddress.</b>
<b>Explanation</b>	Attempted to modify the BindAddress.
<b>Action</b>	Do not modify the BindAddress in the input.
<b>NUMSPME0020</b>	<b>Invalid argument provided.</b>
<b>Explanation</b>	Invalid value provided for argument. Port cannot be configured.
<b>Action</b>	Verify and provide correct value for all the arguments. Refer to the Universal Messaging documentaion for more information about argument values.
<b>NUMSPME0021</b>	<b>IPAccess is not supported by Universal Messaging.</b>
<b>Explanation</b>	IPAccess is set, but Universal Messaging does not support IPAccess.
<b>Action</b>	Do not set the IPAccess.

<b>NUMSPME0022</b>	<b>KeepAliveTimeout is not supported by Universal Messaging.</b>
<b>Explanation</b>	KeepAliveTimeout is set, but Universal Messaging does not support KeepAliveTimeout.
<b>Action</b>	Do not set the KeepAliveTimeout.
<b>NUMSPME0023</b>	<b>ThreadPool is not supported by Universal Messaging.</b>
<b>Explanation</b>	ThreadPool is set, but Universal Messaging does not support ThreadPool.
<b>Action</b>	Do not set the ThreadPool.
<b>NUMSPME0024</b>	<b>URLAccess is not supported by Universal Messaging.</b>
<b>Explanation</b>	URLAccess is set, but Universal Messaging does not support URLAccess.
<b>Action</b>	Do not set the URLAccess.
<b>NUMSPME0025</b>	<b>Keystore definition must not be null.</b>
<b>Explanation</b>	Keystore definition for SSL in the port configuration input is set to Null.
<b>Action</b>	Set a valid value for the keystore definition.
<b>NUMSPME0026</b>	<b>Truststore definition must not be null.</b>
<b>Explanation</b>	Truststore definition for SSL in the port configuration input is set to Null.
<b>Action</b>	Set a valid value for the truststore definition.
<b>NUMSPME0027</b>	<b>Cannot delete this interface. At least one interface is required for a Universal Messaging server.</b>
<b>Explanation</b>	At least one interface must exist for a Universal Messaging server.
<b>Action</b>	Make sure you retain at least one interface for a Universal Messaging server.
<b>NUMSPME0028</b>	<b>Unexpected error occurred while fetching the monitoring data.</b>
<b>Explanation</b>	An internal error occurred while fetching the monitoring data.
<b>Action</b>	Contact Software AG Global Support for further assistance.
<b>NUMSPME0029</b>	<b>The primary port cannot be stopped.</b>
<b>Explanation</b>	The primary port of a ream server cannot be stopped.
<b>Action</b>	Do not attempt to stop the primary port of a ream server.

---

<b>NUMSPME0030</b>	<b>Keystore definition type can only be JKS.</b>
<b>Explanation</b>	Keystore definition type can only be JKS.
<b>Action</b>	Specify JKS in the keystore type.
<b>NUMSPME0031</b>	<b>Truststore definition type can only be JKS.</b>
<b>Explanation</b>	Truststore definition type can only be JKS.
<b>Action</b>	Specify JKS for the Truststore type.
<b>NUMSPME0032</b>	<b>Client Authentication cannot be set to REQUEST_CERTIFICATE.</b>
<b>Explanation</b>	Only values supported for client authentication is REQUIRE_CERTIFICATE or NONE.
<b>Action</b>	Use either REQUIRE_CERTIFICATE or NONE.
<b>NUMSPME0033</b>	<b>Universal Messaging instance management operation failed.</b>
<b>Explanation</b>	An error occurred during the instance management operation.
<b>Action</b>	Contact Software AG Global Support for further assistance.
<b>NUMSPME0034</b>	<b>Universal Messaging instance creation operation failed for the instance with name {0}.</b>
<b>Explanation</b>	An error occurred while creating the Universal Messaging instance.
<b>Action</b>	Contact Software AG Global Support for further assistance.
<b>NUMSPME0035</b>	<b>Universal Messaging instance deletion operation failed for the instance with name {0}.</b>
<b>Explanation</b>	An error occurred while deleting the Universal Messaging instance.
<b>Action</b>	Contact Software AG Global Support for further assistance.
<b>NUMSPME0036</b>	<b>Universal Messaging instance management read operation failed for the runtime component {0}.</b>
<b>Explanation</b>	An error occurred while reading the Universal Messaging instance.
<b>Action</b>	Contact Software AG Global Support for further assistance.

**NUMSPME0037**    **Universal Messaging instance management does not support the operation called on the runtime component {0}.**

**Explanation**    The specified operation is not supported by Universal Messaging instance management.

**Action**    Contact Software AG Global Support for further assistance.

**NUMSPME0038**    **Universal Messaging instance management operation was called with an invalid server name for the runtime component {0}.**

**Explanation**    Universal Messaging instance name specified for the operation is invalid or empty.

**Action**    Provide a valid Universal Messaging instance name.

**NUMSPME0039**    **Universal Messaging instance management operation was called with an empty server name for product-id {0}.**

**Explanation**    Universal Messaging instance name specified for the operation is invalid or empty.

**Action**    Provide a valid Universal Messaging instance name.

**NUMSPME0040**    **Universal Messaging instance management operation was called with an empty port for product-id {0}.**

**Explanation**    The port specified for the Universal Messaging instance management operation is invalid or empty.

**Action**    Provide a valid port number for the Universal Messaging instance.

**NUMSPME0041**    **Universal Messaging instance name, {0}, already exists.**

**Explanation**    The Universal Messaging instance name specified already exists.

**Action**    Choose a Universal Messaging instance name, which is not already present.

**NUMSPME0042**    **Universal Messaging instance management operation was called with the wrong product id, {0}.**

**Explanation**    An error occurred during the instance management operation.

**Action**    Contact Software AG Global Support for further assistance.

**NUMSPME0043**    **Universal Messaging user repository file does not exist.**

**Explanation**    The new repository file for the Universal Messaging users does not exist on the file system.

**Action**    Contact Software AG Global Support for further assistance.

---

<b>NUMSPME0044</b>	<b>Universal Messaging cluster update operation failed for the instance with name {0}.</b>
<b>Explanation</b>	An error occurred while updating the cluster details of the Universal Messaging instance.
<b>Action</b>	Check the detailed error message. Contact Software AG Global Support for further assistance.
<b>NUMSPME0045</b>	<b>Universal Messaging cluster management operation failed.</b>
<b>Explanation</b>	An error occurred during the cluster management operation.
<b>Action</b>	Contact Software AG Global Support for further assistance.
<b>NUMSPME0046</b>	<b>Universal Messaging cluster get operation failed for the instance with name {0}.</b>
<b>Explanation</b>	An error occurred while getting the cluster details of the Universal Messaging instance.
<b>Action</b>	Contact Software AG Global Support for further assistance.
<b>NUMSPME0047</b>	<b>The configuration instance ID argument is missing.</b>
<b>Explanation</b>	The configuration instance ID is required to load the cluster configuration.
<b>Action</b>	Specify the configuration instance ID.
<b>NUMSPME0049</b>	<b>Universal Messaging cluster operation failed. Minimum of two Universal Messaging server instances are required in the cluster.</b>
<b>Explanation</b>	Minimum of two Universal Messaging server instances are required in the cluster.
<b>Action</b>	Make sure the cluster has a minimum of two Universal Messaging server instances. Contact Software AG Global Support for further assistance.
<b>NUMSPME0050</b>	<b>Cannot update the {0} site information for {1} Universal Messaging server instance in {2} cluster.</b>
<b>Explanation</b>	Failed to add or delete the site information to a server node in the cluster.
<b>Action</b>	Contact Software AG Global Support for further assistance.
<b>NUMSPME0051</b>	<b>Cannot update {0} prime site for {1} cluster. The specified prime site does not belong to the cluster.</b>
<b>Explanation</b>	Failed to update the prime site of the cluster. Only a site defined in the cluster can be specified as the prime site.
<b>Action</b>	Specify one of the sites defined in the cluster as the prime site. Contact Software AG Global Support for further assistance.

**NUMSPME0052**      **Cannot create the {0} site information for {1} Universal Messaging server instance in {2} cluster.**

**Explanation**      Failed to create the site for the server node in the cluster.

**Action**            Check the detailed error message. Contact Software AG Global Support for further assistance.

**NUMSPME0053**      **Universal Messaging cluster create operation failed.**

**Explanation**      An error occurred while creating the Universal Messaging cluster.

**Action**            Check the detailed error message. Contact Software AG Global Support for further assistance.

**NUMSPME0054**      **Universal Messaging cluster delete operation failed for the cluster with name {0}.**

**Explanation**      An error occurred while deleting the Universal Messaging cluster.

**Action**            Check the detailed error message. Contact Software AG Global Support for further assistance.

**NUMSPME0055**      **Universal Messaging cluster create operation failed because the cluster name is not provided.**

**Explanation**      To create a Universal Messaging cluster, you must provide a cluster name.

**Action**            Specify the cluster name in the input for Universal Messaging cluster creation.

**NUMSPME0056**      **Universal Messaging server instance {0} is either offline or not reachable.**

**Explanation**      For performing cluster management operations, all the nodes of the cluster must be online.

**Action**            Make sure that the Universal Messaging server instance is online. Contact Software AG Global Support for further assistance.

**NUMSPME0057**      **The cluster update operation failed because there is a mismatch in the cluster name. Actual cluster name is {0} where as the cluster name input is {1}.**

**Explanation**      There is a mismatch between the cluster name specified in the input and the name of the existing cluster.

**Action**            Input the correct cluster name. Contact Software AG Global Support for further assistance.

<b>NUMSPME0058</b>	<b>The license file you have provided is invalid. Provide a valid license file.</b>
<b>Explanation</b>	Invalid license file provided.
<b>Action</b>	Provide a valid Software AG license file. Please contact Software AG Global Support for further assistance.
<b>NUMSPME0060</b>	<b>Unable to configure the Universal Messaging server properties.</b>
<b>Explanation</b>	An error occurred while configuring server properties.
<b>Action</b>	Contact Software AG Global Support for further assistance.
<b>NUMSPME0061</b>	<b>Unable to load the Universal Messaging server configuration properties. Provide a valid configuration instance ID.</b>
<b>Explanation</b>	Configuration instance ID is invalid or not provided.
<b>Action</b>	Provide a valid configuration instance ID.
<b>NUMSPME0062</b>	<b>Parameter validation failed. Unable to update the Universal Messaging server configuration parameters.</b>
<b>Explanation</b>	Incorrect configuration parameter values provided.
<b>Action</b>	See the Universal Messaging documentation for information about valid configuration parameter values.
<b>NUMSPME0063</b>	<b>Unable to update Universal Messaging server configuration parameters.</b>
<b>Explanation</b>	An error occurred when updating the Universal Messaging server configuration properties.
<b>Action</b>	Contact Software AG Global Support for further assistance.
<b>NUMSPME0064</b>	<b>The Universal Messaging server configuration parameter provided is null or does not exist within the group.</b>
<b>Explanation</b>	The Universal Messaging server parameter is null or does not exist.
<b>Action</b>	See the Command Central Help and Universal Messaging documentation for information about valid parameters and values.
<b>NUMSPME0065</b>	<b>Cannot create the {0} site information for {1} Universal Messaging server instance in {2} cluster within the event time interval.</b>
<b>Explanation</b>	Failed to create the site information for the server node in the cluster, in the time interval.
<b>Action</b>	Contact Software AG Global Support for further assistance.

<b>NUMSPME0066</b>	<b>An error occurred while initializing the Universal Messaging Context.</b>
<b>Explanation</b>	An error occurred while initializing the Universal Messaging Context for the Universal Messaging server.
<b>Action</b>	Ensure that the Universal Messaging server is running.
<b>NUMSPME0067</b>	<b>An error occurred while initializing the Universal Messaging Context for Universal Messaging server {0}.</b>
<b>Explanation</b>	An error occurred while initializing the Universal Messaging Context for the Universal Messaging server.
<b>Action</b>	Ensure that the Universal Messaging server is running.
<b>NUMSPME0068</b>	<b>An error occurred while retrieving the JNDI connection factory entries.</b>
<b>Explanation</b>	An error occurred while retrieving the JNDI connection factory entries from the Universal Messaging server.
<b>Action</b>	Ensure that the Universal Messaging server is running and the JNDI connection factories are present on the server.
<b>NUMSPME0069</b>	<b>An error occurred while retrieving the JNDI connection factory entries for the Universal Messaging server {0}.</b>
<b>Explanation</b>	An error occurred while retrieving the JNDI connection factory entries from the Universal Messaging server.
<b>Action</b>	Ensure that the Universal Messaging server is running and the JNDI connection factories are present on the server.
<b>NUMSPME0070</b>	<b>An error occurred while retrieving JNDI connection factory {0} for Universal Messaging server {1}.</b>
<b>Explanation</b>	An error occurred while retrieving the JNDI connection factory entry from the Universal Messaging server.
<b>Action</b>	Ensure that the Universal Messaging server is running and the JNDI connection factory is present on the server.
<b>NUMSPME0071</b>	<b>An error occurred while deleting the JNDI connection factory.</b>
<b>Explanation</b>	An error occurred while deleting the JNDI connection factory from the Universal Messaging server.
<b>Action</b>	Ensure that the JNDI connection factory is present on the server.

---

<b>NUMSPME0072</b>	<b>An error occurred while deleting the JNDI connection factory {0} for Universal Messaging server {1}.</b>
<b>Explanation</b>	An error occurred while deleting the JNDI connection factory from the Universal Messaging server.
<b>Action</b>	Ensure that the JNDI connection factory is present on the server.
<b>NUMSPME0073</b>	<b>An error occurred while binding the JNDI connection factory.</b>
<b>Explanation</b>	An error occurred while binding the JNDI connection factory for the Universal Messaging server.
<b>Action</b>	Ensure that the Universal Messaging server is running.
<b>NUMSPME0074</b>	<b>An error occurred while binding the JNDI connection factory {0} for Universal Messaging server {1}.</b>
<b>Explanation</b>	An error occurred while binding the JNDI connection factory for the Universal Messaging server.
<b>Action</b>	Ensure that the Universal Messaging server is running.
<b>NUMSPME0075</b>	<b>An error occurred while updating the JNDI connection factory.</b>
<b>Explanation</b>	An error occurred while updating the JNDI connection factory for the Universal Messaging server.
<b>Action</b>	Ensure that the Universal Messaging server is running and the JNDI connection factory is present on the server.
<b>NUMSPME0076</b>	<b>An error occurred while updating the JNDI connection factory {0} for Universal Messaging server {1}.</b>
<b>Explanation</b>	An error occurred while updating the JNDI connection factory for the Universal Messaging server.
<b>Action</b>	Ensure that the Universal Messaging server is running and the JNDI connection factory is present on the server.
<b>NUMSPME0077</b>	<b>An error occurred while loading the JNDI connection factory type for Universal Messaging server {0}.</b>
<b>Explanation</b>	An error occurred while loading the JNDI connection factory type for the Universal Messaging server.
<b>Action</b>	Ensure that the Universal Messaging server is running.

**NUMSPME0078**     **An error occurred while creating the JNDI connection factory type {0} for Universal Messaging server {1}.**

**Explanation**     An error occurred while creating the JNDI connection factory type for the Universal Messaging server.

**Action**     Ensure that the Universal Messaging server is running.

**NUMSPME0079**     **An error occurred while binding the JNDI destination.**

**Explanation**     An error occurred while binding the JNDI destination on the Universal Messaging server.

**Action**     Ensure that the Universal Messaging server is running.

**NUMSPME0080**     **An error occurred while binding the JNDI destination {0} on Universal Messaging server {1}.**

**Explanation**     An error occurred while binding the JNDI destination on the Universal Messaging server.

**Action**     Ensure that the Universal Messaging server is running.

**NUMSPME0081**     **An error occurred while retrieving the JNDI destination.**

**Explanation**     An error occurred while retrieving the JNDI destination from the Universal Messaging server.

**Action**     Ensure that the Universal Messaging server is running and JNDI destinations are present on the server.

**NUMSPME0082**     **An error occurred while retrieving the JNDI destination from Universal Messaging server {0}.**

**Explanation**     An error occurred while retrieving the JNDI destination from the Universal Messaging server.

**Action**     Ensure that the Universal Messaging server is running and JNDI destinations are present on the server.

**NUMSPME0083**     **An error occurred while retrieving the JNDI destination {0} from Universal Messaging server {1}.**

**Explanation**     An error occurred while retrieving the JNDI destination from the Universal Messaging server.

**Action**     Ensure that the Universal Messaging server is running and JNDI destinations are present on the server.

---

<b>NUMSPME0084</b>	<b>An error occurred while deleting the JNDI destination.</b>
<b>Explanation</b>	An error occurred while deleting the JNDI destination from the Universal Messaging server.
<b>Action</b>	Ensure that the Universal Messaging server is running and the JNDI destinations are present on the server.
<b>NUMSPME0085</b>	<b>An error occurred while deleting the JNDI destination {0} from Universal Messaging server {1}.</b>
<b>Explanation</b>	An error occurred while deleting the JNDI destination from the Universal Messaging server.
<b>Action</b>	Ensure that the Universal Messaging server is running and the JNDI destinations are present on the server.
<b>NUMSPME0086</b>	<b>An error occurred while loading the JNDI destination type for Universal Messaging server {0}.</b>
<b>Explanation</b>	An error occurred while loading the JNDI destination type for Universal Messaging server.
<b>Action</b>	Ensure that the Universal Messaging server is running.
<b>NUMSPME0087</b>	<b>An error occurred while creating the JNDI destination {0} for Universal Messaging server {1}.</b>
<b>Explanation</b>	An error occurred while creating the JNDI destination on the Universal Messaging server.
<b>Action</b>	Ensure that the Universal Messaging server is running.
<b>NUMSPME0088</b>	<b>Updating a JNDI destination type is not supported.</b>
<b>Explanation</b>	Update operation for a JNDI destination type is not supported for Universal Messaging server.
<b>Action</b>	No action required.
<b>NUMSPME0089</b>	<b>The Universal Messaging server is unavailable, check the status of the Universal Messaging server.</b>
<b>Explanation</b>	The Universal Messaging server might not be running.
<b>Action</b>	Ensure that the Universal Messaging server is running.

<b>NUMSPME0090</b>	<b>An error occurred while retrieving the Universal Messaging session.</b>
<b>Explanation</b>	An error occurred while retrieving the Universal Messaging session.
<b>Action</b>	Ensure that the Universal Messaging server is running.
<b>NUMSPME0091</b>	<b>An error occurred while retrieving the session for Universal Messaging server {0}.</b>
<b>Explanation</b>	An error occurred while retrieving the session for Universal Messaging server {0}.
<b>Action</b>	Ensure that the Universal Messaging server is running.
<b>NUMSPME0092</b>	<b>JNDI connection factory name is either empty or contains invalid characters.</b>
<b>Explanation</b>	JNDI connection factory name is either empty or contains invalid characters.
<b>Action</b>	Provide a valid JNDI connection factory name.
<b>NUMSPME0093</b>	<b>Updating JNDI connection factory name is not supported.</b>
<b>Explanation</b>	Update operation for JNDI connection factory name is not supported for the Universal Messaging server.
<b>Action</b>	No action required.
<b>NUMSPME0094</b>	<b>Updating JNDI connection factory {0} name is not supported.</b>
<b>Explanation</b>	Update operation for JNDI connection factory name is not supported for the Universal Messaging server.
<b>Action</b>	No action required.
<b>NUMSPME0095</b>	<b>Invalid JNDI connection factory type. Allowed types are Connection Factory, Topic Connection Factory, Queue Connection Factory, and XA Connection Factory.</b>
<b>Explanation</b>	Invalid JNDI connection factory type. Allowed types are Connection Factory, Topic Connection Factory, Queue Connection Factory, and XA Connection Factory.
<b>Action</b>	Provide a valid JNDI connection factory type.
<b>NUMSPME0096</b>	<b>JNDI connection factory URL is either empty or invalid.</b>
<b>Explanation</b>	JNDI connection factory URL is either empty or invalid.
<b>Action</b>	Provide a valid JNDI connection factory URL.

<b>NUMSPME0097</b>	<b>Invalid value provided for JNDI connection factory shared durable property. Allowed values are true and false.</b>
<b>Explanation</b>	Invalid value provided for JNDI connection factory shared durable property. Allowed values are true and false.
<b>Action</b>	Provide true to enable and false to disable shared durable for the JNDI connection factory.
<b>NUMSPME0098</b>	<b>JNDI destination name is either empty or contains invalid characters.</b>
<b>Explanation</b>	JNDI destination name is either empty or contains invalid characters.
<b>Action</b>	Provide a valid JNDI destination name.
<b>NUMSPME0099</b>	<b>Invalid JNDI destination type. Allowed types are Topic and Queue.</b>
<b>Explanation</b>	Invalid JNDI destination type. Allowed types are Topic and Queue.
<b>Action</b>	Provide a valid JNDI destination type.
<b>NUMSPME0100</b>	<b>JNDI store name is either empty or contains invalid characters.</b>
<b>Explanation</b>	JNDI store name is either empty or contains invalid characters.
<b>Action</b>	Provide a valid JNDI store name.
<b>NUMSPME0101</b>	<b>Invalid value provided for the JNDI destination auto-create option. Allowed values are true and false</b>
<b>Explanation</b>	Invalid value provided for the JNDI destination auto-create option. Allowed values are true and false.
<b>Action</b>	Provide true to enable and false to disable auto-creation of JNDI destinations.
<b>NUMSPME0102</b>	<b>An error occurred while creating a channel on the Universal Messaging server.</b>
<b>Explanation</b>	An error occurred while creating a channel on the Universal Messaging server.
<b>Action</b>	Ensure that the Universal Messaging server is running.
<b>NUMSPME0103</b>	<b>An error occurred while creating channel {0} on Universal Messaging server {1}.</b>
<b>Explanation</b>	An error occurred while creating a channel on the Universal Messaging server.
<b>Action</b>	Ensure that the Universal Messaging server is running.

<b>NUMSPME0104</b>	<b>An error occurred while creating a queue on the Universal Messaging server.</b>
<b>Explanation</b>	An error occurred while creating a queue on the Universal Messaging server.
<b>Action</b>	Ensure that the Universal Messaging server is running.
<b>NUMSPME0105</b>	<b>An error occurred while creating queue {0} on Universal Messaging server {1}.</b>
<b>Explanation</b>	An error occurred while creating a queue on the Universal Messaging server.
<b>Action</b>	Ensure that the Universal Messaging server is running.
<b>NUMSPME0106</b>	<b>The JNDI connection factory already exists on the Universal Messaging server.</b>
<b>Explanation</b>	The JNDI connection factory already exists on the Universal Messaging server.
<b>Action</b>	Provide a different name for the JNDI connection factory.
<b>NUMSPME0107</b>	<b>JNDI connection factory {0} already exists on Universal Messaging server {1}.</b>
<b>Explanation</b>	JNDI connection factory already exists on the Universal Messaging server.
<b>Action</b>	Provide a different name for the JNDI connection factory.
<b>NUMSPME0108</b>	<b>The JNDI destination already exists on the Universal Messaging server.</b>
<b>Explanation</b>	The JNDI destination already exists on the Universal Messaging server.
<b>Action</b>	Provide a different name for the JNDI destination.
<b>NUMSPME0109</b>	<b>JNDI destination {0} already exists on Universal Messaging server {1}.</b>
<b>Explanation</b>	JNDI destination already exists on Universal Messaging server.
<b>Action</b>	Provide a different name for the JNDI destination.
<b>NUMSPME0110</b>	<b>Unable to load Universal Messaging server configuration properties user interface.</b>
<b>Explanation</b>	An error occurred while reading or writing configuration properties.
<b>Action</b>	Contact Software AG Global Support for further assistance.
<b>NUMSPME0111</b>	<b>Unable to establish connection with the Universal Messaging server.</b>
<b>Explanation</b>	An error occurred while retrieving the session from the Universal Messaging server.
<b>Action</b>	Ensure that the Universal Messaging server is running.

<b>NUMSPME0112</b>	<b>Unable to retrieve the session attribute object associated with with Universal Messaging server session.</b>
<b>Explanation</b>	An exception occurred while retrieving the session attribute.
<b>Action</b>	Ensure that the Universal Messaging server is running.
<b>NUMSPME0113</b>	<b>Unable to find the Universal Messaging channel on this Universal Messaging sever.</b>
<b>Explanation</b>	An error occurred while retrieving the Universal Messaging channel on the Universal Messaging realm server connected to this session, or a joined realm.
<b>Action</b>	Please check if the channel exists on this Universal Messaging sever.
<b>NUMSPME0114</b>	<b>Unable to retrieve the named object on this channel.</b>
<b>Explanation</b>	An error occurred while retrieving the named object details from this channel on the Universal Messaging server.
<b>Action</b>	Please check if the namd object exists on this channel.
<b>NUMSPME0115</b>	<b>Unable to delete the named object on this channel.</b>
<b>Explanation</b>	An error occurred while deleting the named object from this channel on the Universal Messaging server.
<b>Action</b>	Please check if the named object exists on this channel.
<b>NUMSPME0116</b>	<b>Missing argument: {0}.</b>
<b>Explanation</b>	Arguments not provided. Please provide both the channel and durable subscriber names to view details or delete a durable subscriber.
<b>Action</b>	Provide valid arguments for durable subscriber or channel.
<b>NUMSPME0117</b>	<b>Unable to connect to the Universal Messaging server.</b>
<b>Explanation</b>	An error occurred while retrieving the session from the Universal Messaging server.
<b>Action</b>	Please check if the Universal Messaging server is running.
<b>NUMSPME0118</b>	<b>Unable to retrieve the channel/queue {0} from Universal Messaging server {1}.</b>
<b>Explanation</b>	An error occurred while retrieving the channel/queue from the Universal Messaging server.
<b>Action</b>	Ensure that the Universal Messaging server is running and the specified channel/queue exists on the server.

<b>NUMSPME0119</b>	<b>Unable to establish connection with the Universal Messaging server {0}.</b>
<b>Explanation</b>	An error occurred while connecting to the Universal Messaging server.
<b>Action</b>	Ensure that the Universal Messaging server exists and is running.
<b>NUMSPME0120</b>	<b>An error occurred while loading channel configuration for the Universal Messaging server {0}.</b>
<b>Explanation</b>	An error occurred while loading channel configuration for the Universal Messaging server.
<b>Action</b>	Ensure that the Universal Messaging server is running.
<b>NUMSPME0121</b>	<b>Unable to retrieve the channel list for the Universal Messaging server {0}.</b>
<b>Explanation</b>	An error occurred while retrieving the list of channels for the Universal Messaging server.
<b>Action</b>	Check if the Universal Messaging server is running and if the channels are configured.
<b>NUMSPME0122</b>	<b>Unable to retrieve the details of channel {0} in Universal Messaging server {1}.</b>
<b>Explanation</b>	An error occurred while retrieving the channel details for the Universal Messaging server.
<b>Action</b>	Check if the Universal Messaging server is running and if the channel exists on the server.
<b>NUMSPME0123</b>	<b>Unable to connect to the Universal Messaging server {0}.</b>
<b>Explanation</b>	An error occurred while connecting to the Universal Messaging server.
<b>Action</b>	Ensure that the Universal Messaging server exists and is running.
<b>NUMSPME0124</b>	<b>An error occurred while loading the queues for the Universal Messaging server {0}.</b>
<b>Explanation</b>	An error occurred while loading the queues for the Universal Messaging server.
<b>Action</b>	Ensure that the Universal Messaging server exists and is running.
<b>NUMSPME0125</b>	<b>Unable to retrieve the queue list for the Universal Messaging server {0}.</b>
<b>Explanation</b>	An error occurred while retrieving the queue list for the Universal Messaging server.
<b>Action</b>	Please check if the Universal Messaging server is running and has queues configured.

---

<b>NUMSPME0126</b>	<b>Unable to retrieve the details of the queue {0} in Universal Messaging server {1}.</b>
<b>Explanation</b>	An error occurred while retrieving the queue details from the Universal Messaging server.
<b>Action</b>	Please check if Universal Messaging server is running and the queue exists on the server.
<b>NUMSPME0127</b>	<b>Universal Messaging instance management operation failed, exit code - {0}, full command - {1}, standard output - {2}</b>
<b>Explanation</b>	The Universal Messaging instance management operation failed due to an error.
<b>Action</b>	Check the Platform Manager and Universal Messaging logs to find the error, resolve the error and retry.
<b>NUMSPME0128</b>	<b>Unable to create or update the channel as the channel name is not provided or is invalid.</b>
<b>Explanation</b>	Cannot create or update the channel with an empty or invalid name.
<b>Action</b>	Provide a valid channel name.
<b>NUMSPME0129</b>	<b>Unable to create or update the channel as the channel TTL value provided is invalid.</b>
<b>Explanation</b>	Cannot create or update a channel as the TTL is negative.
<b>Action</b>	Provide a TTL value between 0 to 2147483647.
<b>NUMSPME0130</b>	<b>Unable to create or update the channel as the provided channel capacity value is invalid.</b>
<b>Explanation</b>	Cannot create or update a channel as the provided value for the channel capacity is in negative.
<b>Action</b>	Provide a capacity value between 0 to 2147483647.
<b>NUMSPME0131</b>	<b>Unable to create or update the channel as the channel type provided is invalid.</b>
<b>Explanation</b>	Cannot create or update a channel because the channel type provided is invalid.
<b>Action</b>	Provide a valid channel type.
<b>NUMSPME0132</b>	<b>Unable to create or update the channel as the channel engine provided is invalid</b>
<b>Explanation</b>	Cannot create or update the channel because the channel engine type provided is invalid.
<b>Action</b>	Provide a valid channel engine type.

<b>NUMSPME0133</b>	<b>Unable to create or update the channel as the publish key name provided is invalid.</b>
<b>Explanation</b>	Cannot create or update a channel because the publish key name provided is invalid .
<b>Action</b>	Provide a valid channel publish key name.
<b>NUMSPME0134</b>	<b>Unable to create or update the channel as the key depth value provided is invalid.</b>
<b>Explanation</b>	Cannot create or update a channel because the key depth value provided is invalid.
<b>Action</b>	Provide a valid channel key depth.
<b>NUMSPME0135</b>	<b>Unable to create or update the channel as the priority value provided is invalid.</b>
<b>Explanation</b>	Cannot create or update a channel because the priority value provided is invalid.
<b>Action</b>	Provide a value between 0 to 9.
<b>NUMSPME0136</b>	<b>Unable to create or update the channel as the selected stamp dictionary is invalid.</b>
<b>Explanation</b>	Cannot create /update a channel with an invalid stamping dictionary
<b>Action</b>	Select a valid stamp dictionary.
<b>NUMSPME0137</b>	<b>Unable to create the channel {0} on Universal Messaging server {1}.</b>
<b>Explanation</b>	An error occurred while creating the channel on the Universal Messaging server.
<b>Action</b>	Ensure that the Universal Messaging server is running.
<b>NUMSPME0138</b>	<b>Unable to create/update the channel attributes as the provided parameters are invalid.</b>
<b>Explanation</b>	An error occurred while creating/updating the channel attributes as the provided input parameters are invalid.
<b>Action</b>	Ensure that the provided input channel parameter values are valid.
<b>NUMSPME0139</b>	<b>Unable to create/update the channel as the dead event store provided is invalid.</b>
<b>Explanation</b>	An error occurred while creating/updating the channel as the provided dead event store does not exist on the Universal Messaging server.
<b>Action</b>	Ensure that the dead event store channel or queue provided exists on the server.

<b>NUMSPME0140</b>	<b>Unable to create the channel as channel {0} already exists on server {1}.</b>
<b>Explanation</b>	Channel already exists on the server.
<b>Action</b>	Create a channel with a different name.
<b>NUMSPME0141</b>	<b>Unable to delete the channel or queue {0} on Universal Messaging server {1}.</b>
<b>Explanation</b>	An error occurred while deleting the channel or queue on the Universal Messaging server.
<b>Action</b>	Check if the Universal Messaging server is running.
<b>NUMSPME0142</b>	<b>Unable to update the channel or queue {0} on Universal Messaging server {1}.</b>
<b>Explanation</b>	An error occurred while updating the channel or queue on the Universal Messaging server.
<b>Action</b>	Check if the Universal Messaging server is running.
<b>NUMSPME0143</b>	<b>Cannot update the channel or queue {0} on Universal Messaging server {1} because of invalid input parameters.</b>
<b>Explanation</b>	An error occurred while updating the channel or queue for the Universal Messaging server because of invalid input parameters.
<b>Action</b>	Ensure that the input parameters are valid and correct.
<b>NUMSPME0144</b>	<b>Unable to update the channel or queue {0} on Universal Messaging server {1}.</b>
<b>Explanation</b>	Update failed because an error occurred while copying the new configuration over the existing channel or queue configuration.
<b>Action</b>	Ensure that the Universal Messaging server is running.
<b>NUMSPME0145</b>	<b>Unable to create or update the channel or queue {0} on Universal Messaging server {1}.</b>
<b>Explanation</b>	An error occurred while creating or updating the channel or queue on Universal Messaging server because of invalid input storage parameters.
<b>Action</b>	Ensure that the input storage parameters are valid and correct.
<b>NUMSPME0146</b>	<b>Unable to create queue {0} on Universal Messaging server {1}.</b>
<b>Explanation</b>	An error occurred while creating the queue on Universal Messaging server.
<b>Action</b>	Ensure that the Universal Messaging server is running.

<b>NUMSPME0147</b>	<b>Unable to create or update the queue.</b>
<b>Explanation</b>	Cannot create or update the queue because of empty or invalid name.
<b>Action</b>	Ensure that you provide a valid name.
<b>NUMSPME0148</b>	<b>Unable to create or update the queue because the TTL value is invalid.</b>
<b>Explanation</b>	Cannot create or update a queue as the TTL value is negative.
<b>Action</b>	Please provide a TTL between 0 to 2147483647 (exclusive)
<b>NUMSPME0149</b>	<b>Unable to create or update the queue as the channel capacity value is invalid.</b>
<b>Explanation</b>	Cannot create or update a queue as the capacity is negative.
<b>Action</b>	Enter a capacity value between 0 to 2147483647.
<b>NUMSPME0150</b>	<b>Unable to create or update the channel because the queue type is invalid.</b>
<b>Explanation</b>	Cannot create or update a queue with an invalid type.
<b>Action</b>	Provide a valid queue type.
<b>NUMSPME0151</b>	<b>Unable to create or update the channel because the priority value is invalid.</b>
<b>Explanation</b>	Cannot create or update a channel with an invalid event priority.
<b>Action</b>	Provide a priority value between 0 to 9 (lowest to highest) .
<b>NUMSPME0152</b>	<b>Unable to create or update the channel as the stamping dictionary value provided is invalid.</b>
<b>Explanation</b>	Cannot create or update a channel with an invalid stamping dictionary.
<b>Action</b>	Provide a valid stamping dictionary value.
<b>NUMSPME0153</b>	<b>Unable to create the queue attributes as the provided parameters are invalid.</b>
<b>Explanation</b>	An error occurred while creating the queue attributes as the input parameters are invalid.
<b>Action</b>	Provide valid queue parameters.
<b>NUMSPME0154</b>	<b>Unable to create the channel attributes as the dead event store is invalid.</b>
<b>Explanation</b>	An error occurred while creating the channel attributes as the provided dead event store does not exist on the Universal messaging server.
<b>Action</b>	Ensure that the dead event store channel or queue exists on the server.

---

<b>NUMSPME0155</b>	<b>Unable to create the queue as queue {0} already exists on server {1}.</b>
<b>Explanation</b>	Queue exists on the server.
<b>Action</b>	Create a queue with a different name.
<b>NUMSPME0156</b>	<b>Missing argument: {0}.</b>
<b>Explanation</b>	Arguments not provided. Provide the channel name to view status of a channel.
<b>Action</b>	Provide a valid channel name.
<b>NUMSPME0157</b>	<b>Unable to retrieve the status of channel {0} in Universal Messaging server {1}.</b>
<b>Explanation</b>	An error occurred while retrieving the channel details from the Universal Messaging server.
<b>Action</b>	Ensure that the Universal Messaging server is running and the channel exists on the server.
<b>NUMSPME0158</b>	<b>Arguments not provided.</b>
<b>Explanation</b>	Arguments not provided. Provide the queue name to view status of a queue.
<b>Action</b>	Provide queue name as the argument.
<b>NUMSPME0159</b>	<b>Unable to retrieve the status of queue {0} for Universal Messaging server {1}.</b>
<b>Explanation</b>	An error occurred while retrieving the queue status from the Universal Messaging server.
<b>Action</b>	Ensure that the Universal Messaging server is running and the queue exists on the server.
<b>NUMSPME0160</b>	<b>Unable to retrieve ACLs for channel {0}.</b>
<b>Explanation</b>	An error occurred while retrieving ACLs for channel {0}.
<b>Action</b>	Check the Platform Manager and Universal Messaging logs to find the error resolve the error and retry.
<b>NUMSPME0161</b>	<b>Unable to add ACLs for channel {0}.</b>
<b>Explanation</b>	An error occurred while adding ACLs to a channel.
<b>Action</b>	Check the Platform Manager and Universal Messaging logs to find the error; resolve the error and retry.

<b>NUMSPME0162</b>	<b>Unable to update ACLs for channel {0}.</b>
<b>Explanation</b>	An error occurred while updating ACLs for channel {0}.
<b>Action</b>	Check the Platform Manager and Universal Messaging logs to find the error; resolve the error and retry.
<b>NUMSPME0163</b>	<b>Unable to create an ACL entry with subject {0} for channel {1}.</b>
<b>Explanation</b>	An error occurred when creating an ACL entry object for the channel.
<b>Action</b>	Check the Platform Manager and Universal Messaging logs to find the error; resolve the error and retry.
<b>NUMSPME0164</b>	<b>Unable to retrieve ACLs for queue {0}.</b>
<b>Explanation</b>	An error occurred when retrieving ACLs for the queue.
<b>Action</b>	Check the Platform Manager and Universal Messaging logs to find the error; resolve the error and retry.
<b>NUMSPME0165</b>	<b>Unable to add ACLs for queue {0}.</b>
<b>Explanation</b>	Adding ACLs to a queue failed due to an error.
<b>Action</b>	Check the Platform Manager and Universal Messaging logs to find the error; resolve the error and retry.
<b>NUMSPME0166</b>	<b>Unable to update ACLs for queue {0}.</b>
<b>Explanation</b>	An error occurred when updating ACLs for a queue.
<b>Action</b>	Check the Platform Manager and Universal Messaging logs to find the error; resolve the error and retry.
<b>NUMSPME0167</b>	<b>Unable to create the ACL entry with name {0} for queue {1}.</b>
<b>Explanation</b>	An error occurred in creating ACL entry object with name {0} for queue {1}.
<b>Action</b>	Check the Platform Manager and Universal Messaging logs to find the error; resolve the error and retry.
<b>NUMSPME0168</b>	<b>Unable to create the ACL entry with subject {0} for channel {1}.</b>
<b>Explanation</b>	Invalid group name provided for ACL entry object with subject {0} for channel {1}.
<b>Action</b>	Provide a valid group name.

---

<b>NUMSPME0169</b>	<b>Unable to create the ACL entry with name {0} for queue {1}.</b>
<b>Explanation</b>	Invalid group name provided for ACL entry with name {0}, for queue {1}.
<b>Action</b>	Provide a valid group name.
<b>NUMSPME0170</b>	<b>Unable to create a join from {0} to {1} because the operation is unsupported.</b>
<b>Explanation</b>	An error occurred while creating the join.
<b>Action</b>	Ensure that the source node is a valid channel. For archived join, ensure that the destination node is a queue.
<b>NUMSPME0171</b>	<b>Unable to create a join from {0} to {1}.</b>
<b>Explanation</b>	An error occurred while creating the join.
<b>Action</b>	Ensure that the source is a valid channel and the Universal Messaging server is running.
<b>NUMSPME0172</b>	<b>Unable to delete the join from {0} to {1} as this operation is unsupported.</b>
<b>Explanation</b>	An error occurred while deleting the join.
<b>Action</b>	Ensure that the source node is a valid channel.
<b>NUMSPME0173</b>	<b>Unable to delete the join from {0} to {1}.</b>
<b>Explanation</b>	An error occurred while deleting the join.
<b>Action</b>	Ensure that the source is a valid channel and the Universal Messaging server is running.
<b>NUMSPME0174</b>	<b>Unable to delete the join from {0} to {1} as this is not a source node.</b>
<b>Explanation</b>	An error occurred while deleting the join.
<b>Action</b>	Delete the join from the source node. A join cannot be deleted from a destination node.
<b>NUMSPME0175</b>	<b>Unable to create the cluster.</b>
<b>Explanation</b>	Unable to create the cluster because the Universal Messaging server instance is already part of another cluster or the server instance already exists in the cluster or a local store is configured in one of the server instances that you are adding to the cluster.
<b>Action</b>	Ensure that the Universal Messaging server instance added to the cluster complies to the restrictions provided in the error message explanation.

<b>NUMSPME0176</b>	<b>Unable to create the cluster.</b>
<b>Explanation</b>	Session error.
<b>Action</b>	Check the detailed error message in the Command Central and Universal Messaging logs. Resolve the error and retry.
<b>NUMSPME0177</b>	<b>Unable to create the cluster.</b>
<b>Explanation</b>	Request timed out.
<b>Action</b>	Retry creating the cluster.
<b>NUMSPME0178</b>	<b>Unable to create the cluster.</b>
<b>Explanation</b>	Error in the response received from the realm server.
<b>Action</b>	Check for the detailed error message in the Universal Messaging logs. Resolve the error and retry.
<b>NUMSPME0179</b>	<b>Unable to create the cluster.</b>
<b>Explanation</b>	The Universal Messaging server instance is currently unreachable.
<b>Action</b>	Check for the detailed error message in the Universal Messaging logs. Resolve the error and retry.
<b>NUMSPME0180</b>	<b>Unable to create the cluster.</b>
<b>Explanation</b>	Conflicting realm names provided.
<b>Action</b>	Ensure that you provide the correct realm names to create the cluster.
<b>NUMSPME0181</b>	<b>Unable to create the cluster.</b>
<b>Explanation</b>	The Universal Messaging server instance could not be found.
<b>Action</b>	Check for detailed error messages in the Command Central and Universal Messaging logs. Contact Software AG Global Support for further assistance.
<b>NUMSPME0182</b>	<b>Unable to create the cluster.</b>
<b>Explanation</b>	You do not have the required administration rights for the realm.
<b>Action</b>	Ensure that you have the relevant administration rights for the realm.

---

<b>NUMSPME0183</b>	<b>Channel created successfully but cannot create a join from {0} to {1} because the operation is not supported.</b>
<b>Explanation</b>	An error occurred while creating the join.
<b>Action</b>	Ensure that the source is a valid channel. For archived join, ensure that the destination node is a queue.
<b>NUMSPME0184</b>	<b>Channel created successfully but cannot create a join from {0} to {1}.</b>
<b>Explanation</b>	An error occurred while creating the join.
<b>Action</b>	Ensure that the source is a valid channel and the Universal Messaging server is running.
<b>NUMSPME0185</b>	<b>Unable to create a join from {0} to {1} because the operation is not supported. The other channel properties are successfully updated.</b>
<b>Explanation</b>	An error occurred while creating the join.
<b>Action</b>	Ensure that the source is a valid channel. For archived join, ensure that the destination node is a queue.
<b>NUMSPME0186</b>	<b>Unable to create a join from {0} to {1}. The other channel properties are successfully updated.</b>
<b>Explanation</b>	An error occurred while creating the join.
<b>Action</b>	Ensure that the source is a valid channel and the Universal Messaging server is running.
<b>NUMSPME0187</b>	<b>Unable to delete the join from {0} to {1} as the operation is not supported. Other channel properties are updated.</b>
<b>Explanation</b>	An error occurred while deleting the join.
<b>Action</b>	Ensure that the source node is a valid channel.
<b>NUMSPME0188</b>	<b>Unable to delete the join from {0} to {1}. Other channel properties are updated.</b>
<b>Explanation</b>	An error occurred while deleting the join.
<b>Action</b>	Ensure that the source is a valid channel and the Universal Messaging server is running.

<b>NUMSPME0189</b>	<b>Cannot delete the join from {0} to {1} because {0} is not the source node. Other channel properties are updated.</b>
<b>Explanation</b>	An error occurred while deleting the join.
<b>Action</b>	Delete the join from the source node. A join cannot be deleted from a destination node.
<b>NUMSPME0190</b>	<b>Unable to create or update the channel as the protobuf descriptor file does not exist.</b>
<b>Explanation</b>	Cannot create or update a channel with an invalid protobuf descriptor file.
<b>Action</b>	Ensure that the protobuf descriptor file exists in the provided path.
<b>NUMSPME0191</b>	<b>Unable to create or update the channel as the protobuf descriptor file provided is invalid.</b>
<b>Explanation</b>	An error occurred while creating or updating the channel because the protobuf descriptor file provided is invalid.
<b>Action</b>	Provide a valid protobuf descriptor file.
<b>NUMSPME0192</b>	<b>Unable to create or update the queue as the protobuf descriptor file does not exist.</b>
<b>Explanation</b>	Cannot create or update a queue with an invalid protobuf descriptor file.
<b>Action</b>	Ensure that the protobuf descriptor file exists in the provided path.
<b>NUMSPME0193</b>	<b>Unable to create or update the queue as the protobuf descriptor provided is invalid.</b>
<b>Explanation</b>	An error occurred while creating or updating the queue because the protobuf descriptor file provided is invalid.
<b>Action</b>	Provide a valid protobuf descriptor file.
<b>NUMSPME0194</b>	<b>Unable to edit the name of the channel.</b>
<b>Explanation</b>	You cannot edit the name of a channel, operation not supported.
<b>Action</b>	Delete and recreate the channel.
<b>NUMSPME0195</b>	<b>Unable to edit the name of the queue.</b>
<b>Explanation</b>	You cannot edit the name of a queue, operation not supported.
<b>Action</b>	Delete and recreate the queue.

<b>NUMSPME0196</b>	<b>Unable to retrieve the channel or queue {0} from Universal Messaging server {1}.</b>
<b>Explanation</b>	An error occurred while retrieving the channel or queue from the Universal Messaging server as the node addition has failed.
<b>Action</b>	Ensure that the Universal Messaging server instances are not clustered.
<b>NUMSPME0197</b>	<b>An error occurred while creating the join.</b>
<b>Explanation</b>	Cannot create the join between {0} and {1} because remote node {1} is not a valid node.
<b>Action</b>	Ensure that the remote node is a valid channel or queue and the Universal Messaging server is running.
<b>NUMSPME0198</b>	<b>Cannot edit a channel join. Operation not supported.</b>
<b>Explanation</b>	Channel joins can only be created and deleted. Editing is not supported.
<b>Action</b>	Delete and recreate the join with the new join attributes.
<b>NUMSPME0199</b>	<b>Missing argument: {0}.</b>
<b>Explanation</b>	Arguments not provided. Please provide both the channel and durable subscriber names to delete a durable subscriber.
<b>Action</b>	Provide valid arguments for durable subscriber or channel.
<b>NUMSPME0200</b>	<b>An error occurred while creating file {0} for the Universal Messaging server instance {1}.</b>
<b>Explanation</b>	An error occurred while creating the file for Universal Messaging instance {1}.
<b>Action</b>	Check the Platform Manager logs for more information about the error.
<b>NUMSPME0201</b>	<b>Invalid cluster configuration. Cluster name not provided for Universal Messaging server instance {0}.</b>
<b>Explanation</b>	Invalid cluster configuration provided. Cluster name not provided for Universal Messaging server instance {0}.
<b>Action</b>	Provide a valid cluster name in the cluster configuration.
<b>NUMSPME0202</b>	<b>Invalid cluster configuration. Servers element is required and is not provided for the Universal Messaging server instance {0}.</b>
<b>Explanation</b>	Invalid cluster configuration. Servers element is required in the cluster configuration and is not provided for the Universal Messaging server instance {0}.
<b>Action</b>	Provide valid cluster configuration with the necessary servers element.

<b>NUMSPME0203</b>	<b>Invalid cluster configuration. Server name is required and is not provided for the Universal Messaging server instance {0}.</b>
<b>Explanation</b>	Invalid cluster configuration. Server name is required and is not provided for the Universal Messaging server instance {0}.
<b>Action</b>	Provide a valid server name in the cluster configuration.
<b>NUMSPME0204</b>	<b>Invalid cluster configuration. Server URL {0} is not provided or is invalid for Universal Messaging server name {1} for server instance {2}.</b>
<b>Explanation</b>	Invalid cluster configuration. Server URL {0} is not provided or is invalid for Universal Messaging server name {1} for server instance {2}.
<b>Action</b>	Provide a valid server URL in the cluster configuration.
<b>NUMSPME0205</b>	<b>Unable to establish connection with the Universal Messaging server {0}.</b>
<b>Explanation</b>	An error occurred while connecting to the Universal Messaging server.
<b>Action</b>	Ensure that the Universal Messaging server exists and is running.
<b>NUMSPME0206</b>	<b>An error occurred while loading the realm ACL configuration for the Universal Messaging server {0}.</b>
<b>Explanation</b>	An error occurred while loading the realm ACL configuration for the Universal Messaging server.
<b>Action</b>	Ensure that the Universal Messaging server is running.
<b>NUMSPME0207</b>	<b>Unable to retrieve the realm ACLs for Universal Messaging server {0}.</b>
<b>Explanation</b>	An error occurred while retrieving the realm ACLs for {0}.
<b>Action</b>	Check the Platform Manager and Universal Messaging logs to find the error; resolve the error and retry.
<b>NUMSPME0208</b>	<b>Unable to update realm ACLs for Universal Messaging server {0}.</b>
<b>Explanation</b>	An error occurred while updating ACLs for Universal Messaging server {0}.
<b>Action</b>	Check the Platform Manager and Universal Messaging logs to find the error; resolve the error and retry.

---

<b>NUMSPME0209</b>	<b>Unable to create an ACL entry with subject {0} for Universal Messaging server {1}.</b>
<b>Explanation</b>	An error occurred when creating an ACL entry for the realm.
<b>Action</b>	Check the Platform Manager and Universal Messaging logs to find the error; resolve the error and retry.
<b>NUMSPME0210</b>	<b>Unable to create the ACL entry with subject {0} for Universal Messaging server {1}.</b>
<b>Explanation</b>	Invalid group name provided for ACL entry object with subject {0} for realm {1}.
<b>Action</b>	Provide an existing group name.
<b>NUMSPME0211</b>	<b>Purge operation not supported on the durable subscriber of type {0}.</b>
<b>Explanation</b>	Purge operation is not allowed for this durable subscriber type.
<b>Action</b>	Purge events on a different durable type.
<b>NUMSPME0212</b>	<b>Unable to establish connection to the Universal Messaging server.</b>
<b>Explanation</b>	An error occurred while retrieving the session from the Universal Messaging server.
<b>Action</b>	Ensure that the Universal Messaging server is running.
<b>NUMSPME0213</b>	<b>An error occurred while trying to view events on the durable subscriber.</b>
<b>Explanation</b>	An error occurred while trying to view events on the durable subscriber.
<b>Action</b>	Ensure that the channel and durable type exists, and the Universal Messaging server is running.
<b>NUMSPME0214</b>	<b>An error occurred while purging events on the durable subscriber.</b>
<b>Explanation</b>	An error occurred while purging events on the durable subscriber.
<b>Action</b>	Ensure that the channel and durable type exists, and the Universal Messaging server is running.
<b>NUMSPME0215</b>	<b>An error occurred while parsing the event header.</b>
<b>Explanation</b>	An error occurred while parsing the event header.
<b>Action</b>	Ensure that the header does not contain corrupted information.

<b>NUMSPME0217</b>	<b>Invalid arguments provided.</b>
<b>Explanation</b>	Invalid arguments provided.
<b>Action</b>	Ensure that you provide valid arguments and try again.
<b>NUMSPME0227</b>	<b>Creation of realm ACLs for Universal Messaging server is not supported.</b>
<b>Explanation</b>	Create operation for realm ACLs is not supported for a Universal Messaging server.
<b>NUMSPME0228</b>	<b>Deletion of realm ACLs for Universal Messaging server is not supported.</b>
<b>Explanation</b>	Delete operation for realm ACLs is not supported for Universal Messaging server.
<b>NUMSPME0229</b>	<b>Universal Messaging cluster update operation failed for the instance with name {0}.</b>
<b>Explanation</b>	An error occurred while updating the cluster details of the Universal Messaging instance.
<b>Action</b>	Ensure that all the cluster nodes are online and the cluster has the quorum.
<b>NUMSPME0239</b>	<b>XA Connection Factory does not support round robin URL.</b>
<b>Action</b>	Change the connection factory type or the URL.
<b>NUMSPME0240</b>	<b>An error occurred while loading the Groups configuration for the Universal Messaging server {0}.</b>
<b>Explanation</b>	An error occurred while loading the groups for the Universal Messaging server.
<b>NUMSPME0241</b>	<b>Unable to retrieve the Groups for Universal Messaging server {0}.</b>
<b>Explanation</b>	An error occurred while retrieving the groups list for the Universal Messaging server.
<b>NUMSPME0242</b>	<b>Unable to add entry with subject {0} for Group {1}.</b>
<b>Explanation</b>	An error occurred while adding the subject to the group as it might be a non-existent group
<b>Action</b>	Provide an existing group name or provide a subject in the format user@host.

<b>NUMSPME0243</b>	<b>Unable to create group {0} for the Universal Messaging server {1}.</b>
<b>Explanation</b>	An error occurred while creating a group for the Universal Messaging server.
<b>NUMSPME0244</b>	<b>Unable to delete group {0} for the Universal Messaging server {1}.</b>
<b>Explanation</b>	An error occurred while deleting a group for the Universal Messaging server.
<b>NUMSPME0245</b>	<b>Unable to update group {0} for the Universal Messaging server {1}.</b>
<b>Explanation</b>	An error occurred while updating a group for the Universal Messaging server.
<b>NUMSPME0246</b>	<b>Unable to add entry with subject {0} for the Group {1}.</b>
<b>Explanation</b>	An error occurred while adding a subject to the group.
<b>NUMSPME0247</b>	<b>Unable to connect to the Universal Messaging server {0}.</b>
<b>Explanation</b>	An error occurred while connecting to the Universal Messaging server.
<b>NUMSPME0248</b>	<b>Unable to create group as the group name is not provided or is invalid.</b>
<b>Explanation</b>	Cannot create or update group with an empty or invalid name.
<b>Action</b>	Provide a valid group name.
<b>NUMSPME0249</b>	<b>Unable to create zone {0} with Universal Messaging server {1}.</b>
<b>Explanation</b>	An error occurred while creating a zone with the Universal Messaging server.
<b>Action</b>	Check the detailed error message. Contact Software AG Global Support for further assistance.
<b>NUMSPME0250</b>	<b>Unable to create or update the channel as the read buffer size value provided is invalid.</b>
<b>Explanation</b>	Cannot create or update a channel because the read buffer size value provided is invalid.
<b>Action</b>	Provide a read buffer size value between 0 to 2147483647.
<b>NUMSPME0251</b>	<b>Unable to create or update the channel as the events per spindle value provided is invalid.</b>
<b>Explanation</b>	Cannot create or update a channel because the events per spindle value provided is invalid.
<b>Action</b>	Provide a value between 0 to 2147483647.

**NUMSPME0252**     **Unable to create or update the channel as the sync batch property values provided are invalid.**

**Explanation**     Cannot create or update a channel because the sync batch property values provided are invalid.

**Action**     Provide a sync batch property value between 0 to 2147483647.

**NUMSPME0253**     **Unable to create or update the queue as the read buffer size value provided is invalid.**

**Explanation**     Cannot create or update a queue because the read buffer size value provided is invalid.

**Action**     Provide a read buffer size value between 0 to 2147483647.

**NUMSPME0254**     **Unable to create or update the queue as the events per spindle value provided is invalid.**

**Explanation**     Cannot create or update a queue because the events per spindle value provided is invalid.

**Action**     Provide a events per spindle value between 0 to 2147483647.

**NUMSPME0255**     **Unable to create or update the queue as the sync batch property values provided are invalid.**

**Explanation**     Cannot create or update a queue because the sync batch property values provided are invalid.

**Action**     Provide a sync batch property value between 0 to 2147483647.

**NUMSPME0256**     **Unable to update zone {0} with Universal Messaging server {1}.**

**Explanation**     An error occurred while updating a zone with the Universal Messaging server.

**Action**     Check the detailed error message in the Universal Messaging server logs.

**NUMSPME0257**     **Unable to remove link from Universal Messaging server {0} to Universal Messaging server {1}.**

**Explanation**     An error occurred while removing links between Universal Messaging servers in the zone.

**Action**     Check for the detailed error message in the Universal Messaging logs. Resolve the error and retry.

<b>NUMSPME0258</b>	<b>Failed to remove cluster link from cluster {0} to cluster {1}.</b>
<b>Explanation</b>	An error occurred while removing links between clusters in the zone.
<b>Action</b>	Ensure the clusters are available and connected.
<b>NUMSPME0259</b>	<b>Unable to retrieve zone details for Universal Messaging server {0}.</b>
<b>Explanation</b>	An error occurred while retrieving the zone members list for the Universal Messaging server.
<b>Action</b>	Ensure that the Universal Messaging server is running.
<b>NUMSPME0260</b>	<b>The Universal Messaging server instance is currently not accessible .</b>
<b>Explanation</b>	Check for the detailed error messages in the Universal Messaging logs. Resolve the error and retry.
<b>Action</b>	Ensure that the Universal Messaging server is running.
<b>NUMSPME0261</b>	<b>An error occurred while creating a zone.</b>
<b>Explanation</b>	Zone members are incompatible, clustered and non-clustered Universal Messaging server instances cannot be in the same zone.
<b>Action</b>	Ensure that the clustered and non-clustered Universal Messaging server instances are not added to the same zone. Clustered and non-clustered Universal Messaging server instances need to be grouped in separate zones.
<b>NUMSPME0262</b>	<b>Unable to create a link to the Universal Messaging server {0} from Universal Messaging server {1}.</b>
<b>Explanation</b>	An error occurred while linking the Universal Messaging servers. Rolling back the created links.
<b>Action</b>	Ensure that all the Universal Messaging servers that are being linked are running.
<b>NUMSPME0263</b>	<b>Unable to rollback the added Universal Messaging server instance links.</b>
<b>Explanation</b>	An error occurred when rolling back the Universal Messaging instance links added to the zone.
<b>Action</b>	Check the detailed error message.

<b>NUMSPME0264</b>	<b>Unable to delete zone {0} with Universal Messaging server {1}.</b>
<b>Explanation</b>	An error occurred while deleting a zone with the Universal Messaging server.
<b>Action</b>	Check the detailed error message.
<b>NUMSPME0265</b>	<b>Unable to create or update the cluster as the server URL provided is invalid.</b>
<b>Explanation</b>	The URL provided for the Universal Messaging server instance is invalid.
<b>Action</b>	Please provide a valid URL for the Universal Messaging server instance.
<b>NUMSPME0266</b>	<b>Cannot disable this interface. At least one interface needs to be enabled.</b>
<b>Explanation</b>	At least one interface should be enabled for a Universal Messaging server.
<b>Action</b>	Ensure that you enable at least one interface for a Universal Messaging server.
<b>NUMSPME0267</b>	<b>The specified prime site is invalid, the prime site specified does not belong to the cluster.</b>
<b>Explanation</b>	The specified prime site is invalid.
<b>Action</b>	Specify one of the sites defined in the cluster as the prime site.
<b>NUMSPME0268</b>	<b>Unable to create the zone as the zone name is not provided or is invalid.</b>
<b>Explanation</b>	Cannot create or update a zone with an empty or invalid name.
<b>Action</b>	Provide a valid zone name.
<b>NUMSPME0269</b>	<b>Unable to add Universal Messaging server {0} to the zone. Universal Messaging server {0} is already part of zone {1}.</b>
<b>Explanation</b>	Unable to add Universal Messaging server to the zone as it is already a part of another zone.
<b>Action</b>	Provide a different Universal Messaging server or remove the server from the other zone.
<b>NUMSPME0270</b>	<b>Unable to create or update the zone as the server URL provided is invalid.</b>
<b>Explanation</b>	The URL provided for the Universal Messaging server instance is invalid.
<b>Action</b>	Provide a valid URL for the Universal Messaging server instance.

<b>NUMSPME0271</b>	<b>Unable to update the zone because the zone should contain at least one member.</b>
<b>Explanation</b>	Zone update cannot be performed because a zone should contain at least one cluster.
<b>Action</b>	Ensure at least one cluster is part of the zone after modification.
<b>NUMSPME0272</b>	<b>Unable to retrieve the configured user repository file path for instance {0}.</b>
<b>Explanation</b>	Unable to retrieve the configured user repository file path for instance {0}.
<b>Action</b>	Verify if the user repository file is configured for the instance {0}.
<b>NUMSPMI0048</b>	<b>The Universal Messaging server instance {0} is not a part of any cluster.</b>
<b>Explanation</b>	This Universal Messaging sever instance is not a part of any cluster.
<b>Action</b>	No action required.
<b>NUMSPMW0004</b>	<b>Unable to connect to the Command Central interface of the Universal Messaging server {0}.</b>
<b>Explanation</b>	Interface factory could not connect to any interface.
<b>Action</b>	Please contact webMethods Administrator.

