

# **webMethods EntireX**

## **Administration under IBM i**

Version 10.1

October 2017

This document applies to webMethods EntireX Version 10.1 and all subsequent releases.

Specifications contained herein are subject to change and these changes will be reported in subsequent release notes or new editions.

Copyright © 1997-2017 Software AG, Darmstadt, Germany and/or Software AG USA, Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA, Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

Use of this software is subject to adherence to Software AG's licensing conditions and terms. These terms are part of the product documentation, located at <http://softwareag.com/licenses/> and/or in the root installation directory of the licensed product(s).

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third-Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

Use, reproduction, transfer, publication or disclosure is prohibited except as specifically provided for in your License Agreement with Software AG.

**Document ID: EXX-ADMIN\_OS400-101-20191129**

## Table of Contents

EntireX Administration under IBM i .....	v
1 About this Documentation .....	1
Document Conventions .....	2
Online Information and Support .....	2
Data Protection .....	3
2 Administering the RPC Server for IBM i .....	5
General Rules and Conventions .....	6
Locating and Calling the Target Server .....	7
Configuring the RPC Server .....	9
Scalability of the RPC Server .....	16
Starting the RPC Server .....	18
Troubleshooting .....	20
Activating Tracing for the RPC Server .....	20
3 Administering Broker Stubs under IBM i .....	23
Using the Security Exit .....	24
Tracing for Broker Stubs under IBM i .....	25
4 Natural RPC Server Configuration for the IDL Extractor for Natural .....	27
Natural Steplib Configuration .....	28
Natural RPC Server Configuration when Natural Security is not used .....	28
Natural RPC Server Configuration when Natural Security is used .....	29
Natural RPC Server Parameter Configuration .....	29



---

## EntireX Administration under IBM i

---

<i>Administering the RPC Server for IBM i</i>	General Rules and Conventions, Setting the Broker and Server Parameters for the RPC Server, Starting the RPC Server, Stopping the RPC Server and Principles of Calling a Server Application.  <b>Note:</b> The EntireX RPC Server for IBM i of EntireX version 7.1.1 running under IBM i (AS/400) will no longer be supported in the next version of EntireX. We strongly recommend using the new <i>RPC Server for AS/400</i> or the EntireX Adapter. See also <i>Connection Parameters for AS/400 Connections</i> .
<i>Administering Broker Stubs under IBM i</i>	Using the Broker Stub with Natural RPC, Using the Security Exit and Tracing.
<i>Natural RPC Server Configuration for the IDL Extractor for Natural</i>	This document describes how to configure the Natural RPC Server when using the IDL Extractor for Natural.

## Related Literature

---

- *Installing EntireX under IBM i*
- *Creating an RPG User Application under IBM i*
- *Creating a C User Application under IBM i*
- *Creating a COBOL User Application under IBM i*
- *Component Return Codes in EntireX*
- *Using the C Wrapper*
- *Using the COBOL Wrapper*
- *Using EntireX RPC for RPG under IBM i*
- *Using EntireX RPC for CL under IBM i*

---

# 1 About this Documentation

---

- Document Conventions ..... 2
- Online Information and Support ..... 2
- Data Protection ..... 3

## Document Conventions

---

Convention	Description
<b>Bold</b>	Identifies elements on a screen.
Monospace font	Identifies service names and locations in the format <code>folder.subfolder.service</code> , APIs, Java classes, methods, properties.
<i>Italic</i>	Identifies:  Variables for which you must supply values specific to your own situation or environment. New terms the first time they occur in the text. References to other documentation sources.
Monospace font	Identifies:  Text you must type in. Messages displayed by the system. Program code.
{ }	Indicates a set of choices from which you must choose one. Type only the information inside the curly braces. Do not type the { } symbols.
	Separates two mutually exclusive choices in a syntax line. Type one of these choices. Do not type the   symbol.
[ ]	Indicates one or more options. Type only the information inside the square brackets. Do not type the [ ] symbols.
...	Indicates that you can type multiple options of the same type. Type only the information. Do not type the ellipsis (...).

## Online Information and Support

---

### Software AG Documentation Website

You can find documentation on the Software AG Documentation website at <http://documentation.softwareag.com>. The site requires credentials for Software AG's Product Support site Empower. If you do not have Empower credentials, you must use the TECHcommunity website.

### Software AG Empower Product Support Website

If you do not yet have an account for Empower, send an email to [empower@softwareag.com](mailto:empower@softwareag.com) with your name, company, and company email address and request an account.

Once you have an account, you can open Support Incidents online via the eService section of Empower at <https://empower.softwareag.com/>.

You can find product information on the Software AG Empower Product Support website at <https://empower.softwareag.com>.

To submit feature/enhancement requests, get information about product availability, and download products, go to [Products](#).

To get information about fixes and to read early warnings, technical papers, and knowledge base articles, go to the [Knowledge Center](#).

If you have any questions, you can find a local or toll-free number for your country in our Global Support Contact Directory at [https://empower.softwareag.com/public\\_directory.asp](https://empower.softwareag.com/public_directory.asp) and give us a call.

### **Software AG TECHcommunity**

You can find documentation and other technical information on the Software AG TECHcommunity website at <http://techcommunity.softwareag.com>. You can:

- Access product documentation, if you have TECHcommunity credentials. If you do not, you will need to register and specify "Documentation" as an area of interest.
- Access articles, code samples, demos, and tutorials.
- Use the online discussion forums, moderated by Software AG professionals, to ask questions, discuss best practices, and learn how other customers are using Software AG technology.
- Link to external websites that discuss open standards and web technology.

## **Data Protection**

---

Software AG products provide functionality with respect to processing of personal data according to the EU General Data Protection Regulation (GDPR). Where applicable, appropriate steps are documented in the respective administration documentation.

---

## 2 Administering the RPC Server for IBM i

---

▪ General Rules and Conventions .....	6
▪ Locating and Calling the Target Server .....	7
▪ Configuring the RPC Server .....	9
▪ Scalability of the RPC Server .....	16
▪ Starting the RPC Server .....	18
▪ Troubleshooting .....	20
▪ Activating Tracing for the RPC Server .....	20

The EntireX RPC Server for IBM i enables you to call server programs written in all ILE-based languages, for example C, COBOL, RPG.



**Note:** The EntireX RPC Server for IBM i of EntireX version 7.1.1 running under IBM i (AS/400) will no longer be supported in the next version of EntireX. We strongly recommend using the new *RPC Server for AS/400* or the EntireX Adapter. See also *Connection Parameters for AS/400 Connections*.

## General Rules and Conventions

---

The following rules apply to all server and client applications written in C under IBM i.

- Only ILE (Integrated Language Environment) program objects are supported.

The EntireX RPC Server does not support OPM (Original Program Model) and EPM (Extended Program Model) objects.

- The servers run in a multithreaded environment. Therefore your application server programs must be thread-safe. This implies that all commands and subprograms accessed in your servers must allow multithreads.
- When linking servers, the binding parameter `ACTGRP(*CALLER)` must be specified. This guarantees that a server application runs in the same activation group as the calling RPC server. Before processing a server program, the RPC Server verifies if the application was bound with `ACTGRP(*CALLER)`. If not, the RPC Server rejects the call and sends a message to the system operator.
- The IBM i terms “bind” or “binding” are equivalent to the terms “link” or “linking” in the current manual.
- Under IBM i, the term “service program” for a `*SRVPGM` program is equivalent to “shared library” under UNIX.



**Caution:** When you compile ILE programs, do *not* use the PDM source compiling option 14. Use only the ILE commands `CRTBNDxxx` or `CRTxxxMOD` with `CRTPGM`, where `xxx` denotes the source language such as CBL for COBOL, RPG or CL for command language.

---

## Locating and Calling the Target Server

---

- [Types of Target Server](#)
- [Finding a Server Program](#)
- [Passing Parameters to the Server](#)

The library and program names that come from the client are used to locate the target server. This two-level IDL concept (library and program) has to be mapped in some way to the RPC Server environment.

### Types of Target Server

The RPC Server under IBM i supports target servers as:

#### ■ ILE-C applications

The servers and their stubs are implemented as IBM i service programs of type \*SRCPGM, written according to *EntireX C Wrapper*. ILE-C applications have a two-level concept. The IDL library and program names that come from the client are mapped as follows:

- The library name is used to form the file names of the target server shared library/object and stub shared library/object
- The program name is used to form the entry point names for the target server shared library/object and stub shared library/object.

#### ■ ILE-RPG, ILE-COBOL and/or ILE-CL applications

For these applications, the servers are called directly without any stubs. The IDL library and program names that come from the client for this type of target servers are mapped as follows:

- The library name is used to form the IBM i library name.
- The program name is used to form the IBM i program name, which is implemented as a bound program of type \*PGM.

Under IBM i, the RPC Server uses various methods to call the two kinds of server implementations, depending on the programming language you have used to develop your application. The next section describes how the RPC Server under IBM i distinguishes between the two implementations.

## Finding a Server Program

The RPC Server searches for a server in the following order:

### First Preference

The RPC Server first assumes that the server was developed in ILE-C. It therefore tries to run two service programs of type \*SRCPGM located in the library list of the user who submitted the RPC Server. The service programs represent the shared libraries of:

- the server stub, which is named by default `DMy_shared_library` and
- the server implementation, named by default `My_shared_library`, which contains the application functions.

`My_shared_library` corresponds to the library name in the IDL file. The program names specified in the IDL file are used to form the entry point names, e.g. `DCALC` and `CALC`. They represent C functions in the server program. Based on the IDL layout, the sources of the stub and the server frame must be generated from templates using the *EntireX Workbench* function “Generate C Server” or the corresponding Software AG IDL Compiler command.

Generating C stubs and servers is described in detail under *Using the C Wrapper*. Extensions specific to IBM i are described under *Using the C Wrapper for the Server Side (z/OS, UNIX, Windows, BS2000, IBM i)*. You can find an example of a C application server under *Step 4: Verify the RPC Server using C*.

To locate the target server, the library parameter is also used as a kind of search sequence. See [Possible Values for library](#). The default for the library parameter is set to `PREFIX(D) - PREFIX()` to be compatible with server stubs and target servers written according to *EntireX C Wrapper*.

### Second Preference

If no appropriate server written in C can be found in the RPC Server job's library list, the RPC Server assumes that the server was developed in ILE-COBOL, ILE-RPG or ILE-CL. It tries to execute a stubless ILE program of type \*PGM, where

- the IBM i program name is derived from the IDL program name that comes from the client, and
- the IBM i library name is derived from the IDL library name that comes from the client. Changing the default setting `FIX() file` gives you control and independence over the library name that comes from the client. You can reroute the call to a target library of your choice (currently restricted to 8-character names) by setting the server parameter `Library=FIX(MyLib)` in the configuration file of the RPC Server. In this case, the library name sent with the client request is ignored.

See *Using EntireX RPC for CL under IBM i* for how to use RPC servers in RPG, *Using the COBOL Wrapper* on how to use RPC servers in COBOL and *Using EntireX RPC for CL under IBM i* for how to use RPC servers in CL.

You will find an IBM i example of a COBOL application server under *Step 3: Verify the RPC Server using COBOL*.

If both access approaches fail, an error message is sent back to the client.

### Passing Parameters to the Server

The number of Level 01 parameters passed is predetermined by the client and the IDL definition. If this number does not match the number specified in the linkage section of your ILE server program, the operating system will reject the call.



**Note:** For stubless access to servers written in ILE-RPG, ILE-COBOL and ILE-CL, currently up to 16 level-01 parameters are supported. More parameters are ignored. Parameter fields of type floating point are not supported.

## Configuring the RPC Server

---

The following rules apply:

- In the configuration file:
  - Comments must be on a separate line.
  - Comment lines can begin with '\*', '/' and ';'.
  - Empty lines are ignored.
  - Headings in square brackets [<topic>] are ignored.
  - Keywords are not case-sensitive.
- Underscored letters in a parameter indicate the minimum number of letters that can be used for an abbreviated command.

For example, in `brokerid=localhost`, `brok` is the minimum number of letters that can be used as an abbreviation, that is, the commands/parameters `broker=localhost` and `brok=localhost` are equivalents.

**Table of Server Parameters**

Configuration File Parameter Syntax	Value	Req. Opt.	Description	Notes
<code>brokerid=localhost</code>	string	R	Broker ID used by the server.	Corresponds to the <code>BROKER-ID</code> field of the Broker ACI control block.
<code>class=RPC</code>	case-sensitive, up to 32 characters	R	Server class used by the server.	Corresponds to the <code>SERVER-CLASS</code> field of the Broker ACI control block.
<code>codepage=</code>		O	<p>The codepage tells the broker the encoding of the data. The application must ensure the encoding of the data matches the codepage. The RPC server itself does not convert your application data. The application's data is shipped and received as given. Often, the codepage must also match the encoding used in the RPC server environment for file and terminal IO, otherwise unpredictable results may occur.</p> <p>By default, no codepage is transferred to the broker. It is assumed the broker's locale string defaults match. See <i>Locale String Mapping</i> If they do not match, provide the codepage here.</p> <p>Enable character conversion in the broker by setting the service-specific attribute <code>CONVERSION</code> to "SAGTRPC". See also <i>Configuring ICU Conversion</i> under <i>Configuring Broker for Internationalization</i> in the platform-specific Administration documentation. More information can be found under <i>Internationalization with EntireX</i>.</p>	
<code>compresslevel=0</code>	0-9 or Y   N	O	Enforce compression when data is transferred between broker and server.	See <i>Data Compression in EntireX Broker</i> .
<code>etb_apivers= 0</code>	<i>n</i>	O	Determines the Broker API to use.	Corresponds to the <code>API-VERSION</code> field of

Configuration File Parameter Syntax	Value	Req. Opt.	Description	Notes
				the Broker ACI control block. We recommend either not configuring the API Version or setting it to 0. This allows the EntireX Broker and the EntireX RPC server to autodetect the best API version to use. For compatibility with older Brokers, the API version can be set manually.
<u>logon=</u> YES	<u>YES</u>   NO	O	YES executes the Broker functions LOGON/LOGOFF. NO does not.	Specify NO for compatibility with EntireX Broker prior to Version 4.1.1.
<u>servername=</u> SRV1	case-sensitive, up to 32 characters	R	Server Name used by the server.	Corresponds to the SERVER-NAME field of the Broker ACI control block.
<u>service=</u> CALLNAT	case-sensitive, up to 32 characters	R	Service used by the server.	Corresponds to the SERVICE field of the Broker ACI control block.
<u>timeout=</u> 60	<i>n</i>	O	Timeout in seconds, used by the server to wait for Broker requests.	Corresponds to the WAIT field in the Broker ACI control block. See also <a href="#">Scalability of the RPC Server</a> .
<u>userid=</u> ERX-SRV	case-sensitive, up to 32 characters	R	Used to identify the server to the broker.	Corresponds to the USER-ID field of the Broker ACI control block.
<u>password=</u>	case-sensitive, up to 32 characters	O	Password for Broker logon.	Corresponds to the PASSWORD field of the Broker ACI control block.
<u>kernelsecurity =</u> level	Y yes   N no   U user	O	Dynamic enablement if EntireX security is active.	Corresponds to the KERNELSECURITY field of the Broker ACI control block.

Configuration File Parameter Syntax	Value	Req. Opt.	Description	Notes
<code>endworkers=timeout</code>	See <a href="#">Possible Values for endworkers</a>	O	Defines the behavior of worker tasks on completion of client requests.	See <a href="#">Scalability of the RPC Server</a> .
<code>minworkers= 1</code>	<i>n</i>	O	Minimum number of parallel worker threads started.	
<code>maxworkers=10</code>	<i>n</i>	O	Maximum number of parallel worker threads started.	
<code>tracelevel=None</code>	None   Standard   Advanced   Support	O	Select the trace level for this server.	See <a href="#">Activating Tracing for the RPC Server</a> .
<code>tracedest=</code>		O	The name of the destination file for trace output.	
<code>traceoption=</code>	none   STUBLOG   NOTRUNC	O	Additional trace option if trace is active.  None No additional trace options.  STUBLOG If <code>tracelevel</code> is Advanced or Support, the trace additionally activates the broker stub log.  NOTRUNC Normally if a data buffer larger than 8 KB is traced, the buffer trace is truncated. Set this option to write the full amount of data without truncation.  <b>Note:</b> This can increase the amount of trace output data dramatically if you transfer large data buffers.  Example:	
<code>library=</code>	library = PREFIX(D) - PREFIX()	O	Specifies criteria to locate target servers and any client interface objects. The following coding rules apply:	

Configuration File Parameter Syntax	Value	Req. Opt.	Description	Notes
			<ul style="list-style-type: none"> <li>■ Up to five library entries can be specified as a sequence.</li> <li>■ Library entries are separated by a hyphen "-".</li> <li>■ Library entries are used from left to right by the RPC Server.</li> </ul>	
<code>restartcycles=15</code>	<i>n</i>	O	<p>Number of restart attempts if the broker is not available. This can be used to keep the RPC Server for IBM i running while the broker is down for a short time. A restart cycle will be repeated every 60 seconds.</p> <p>When the number of specified cycles is reached and a connection to the broker is not possible, the RPC server stops.</p> <p>Example:</p> <p>The server waits up to 30 minutes before it terminates due to a missing broker connection.</p>	This may occur when the RPC server is started prior to the broker or when the broker is shut down before the RPC server is shut down.
<code>runoption=</code>		O	<p>Provides EntireX RPC Server with additional information when calling target servers without stubs. Default:</p> <pre>runoption= P_SIGNED N_SIGNED DIRECT_CALL</pre>	

### Possible Values for runoption

The runoptions are important for EntireX RPC Servers when the servers are called directly without server stubs, that is on z/VSE Batch, z/OS IMS, CICS, IBM i platforms or with a callable RPC server. When there is no server stub information, it is not known how to align and unmarshal to the target data type (and marshal the data back). With the `runoption` parameter, it is possible to provide the EntireX RPC Server with such information.

The runoptions are normally set to meet the platform's requirements. In most cases it should not be necessary to modify them.

Keyword	Description
I2_ALIGNED NOT_I2_ALIGNED	Aligns Integer (medium) data types. See <i>Mapping of Software AG IDL Data Type I2</i> to your target programming language COBOL   RPG.
I4_ALIGNED NOT_I4_ALIGNED	Aligns Integer (large) data types. See <i>Mapping of Software AG IDL Data Type I4</i> to your target programming language COBOL   RPG.
F4_ALIGNED NOT_F4_ALIGNED	Aligns Floating point (small) data types. See <i>Mapping of Software AG IDL Data Type F4</i> to your target programming language COBOL   RPG.
F8_ALIGNED NOT_F8_ALIGNED	Aligns Floating point (large) data types. See <i>Mapping of Software AG IDL Data Type F8</i> to your target programming language COBOL   RPG.
P_SIGNED NOT_P_SIGNED	Treats Packed decimal data types as signed packed. See <i>Mapping of Software AG IDL Data Type P number1 [. number2 ]</i> to your target programming language COBOL   RPG.
N_SIGNED NOT_N_SIGNED	Treats Unpacked decimal data types as signed numeric. See <i>Mapping of Software AG IDL Data Type N number1 [. number2 ]</i> to your target programming language COBOL   RPG.
COBOL_TIME NOT_COBOL_TIME	Maps Time and Date data types to the COBOL format PIC 9(21). See <i>Mapping of Software AG IDL Data Type T</i> to your target programming language COBOL   RPG.
DIRECT_CALL NOT_DIRECT_CALL	Forces calling server directly without server stub.
C_STRING NOT_C_STRING	Provides string variables (A) in C style: The string is guaranteed to be limited with a terminating byte, thus the size is increased. For example, A10 will be mapped to a maximum of 11 bytes.
NUMERIC_DOUBLE NON_NUMERIC_DOUBLE	Maps numeric data types (N, P) to double.

The `runoption` keyword can be issued multiple times:

### Possible Values for endworkers

The server is able to adjust the number of worker threads to the current number of client requests. This is configured with the parameter `endworkers` and several others. See [Scalability of the RPC Server](#) for information on how the various parameters work together and what combinations can be specified.

Value	Explanation
N	<b>Never</b> The number of worker threads is fixed. No additional worker threads are started. <code>minworkers</code> determines the number of workers started.
T	<b>Timeout is used</b> The number of worker threads ranges between the <code>minworkers</code> and <code>maxworkers</code> settings, depending on the number of currently active client requests. Until <code>maxworkers</code> has been reached, the server tries to maintain enough free worker threads to accept all incoming clients.

Value	Explanation
	The server stops all worker threads not used in the time specified by the <code>timeout</code> server parameter (see <a href="#">timeout</a> ), except for the number of workers specified in <code>minworkers</code> .
I	<p><b>Immediately</b></p> <p>The number of worker threads ranges between the <code>minworkers</code> and <code>maxworkers</code> settings, depending on the number of client requests currently active. Until <code>maxworkers</code> has been reached, the server tries to maintain enough free worker threads to accept all incoming clients.</p> <p>The server stops a thread immediately as soon as it has finished its conversation. When the number of active workers falls below the number of workers specified in <code>minworkers</code>, a new thread will be started.</p>

### Possible Values for library

Type of Target Server	Configuration	Description
Target servers in ILE COBOL   RPG   CL	FIX( <i>library</i> )   F( <i>library</i> )	The library sent with the client request is ignored. The configured library <i>library</i> is used to locate the target server.
Target servers and their stubs compatible with C Wrapper	FIX()   F()	The library name sent with the client request is ignored. The program name sent with the client request is used to locate the target server.
	FIX( <i>library</i> )   F( <i>library</i> )	The library sent with the client request is ignored. The configured library <i>library</i> is used to locate the target server and any stubs on the platform.
	PREFIX()   P()	The library name sent with the client request is used to locate the target server and any stubs on the platform.
	PREFIX( <i>prefix</i> )   P( <i>prefix</i> )	The library name sent with the client request is prefixed with the value in "prefix" before locating the target server and any stubs on the platform.

**Example:** `library = PREFIX(D) - PREFIX()`

The default for the `library` parameter is set to satisfy the environment specifics best. Under normal circumstances it is not necessary to change the `library` parameter.

For an explanation of the approach to locating the target server, see [Locating and Calling the Target Server](#).

## Scalability of the RPC Server

- [Parameters](#)
- [Configuration Examples](#)
- [Suggested Configuration on First Usage](#)

### Parameters

The RPC server can be configured to adjust the number of worker threads to the current number of client requests. When more clients are active, more worker threads are needed to achieve the best throughput. Depending on the configuration, worker threads are started on demand and stopped as soon as they are no longer needed.

This mechanism can be configured with the following parameters:

Configuration	endworkers	minworkers	maxworkers	timeout
Fixed number of workers.	Never.	Determines the number of workers started.	Unused.	Not used with this configuration.
Scaling number of workers between minworkers and maxworkers without any idle time.	Immediately.	Determines the minimum number of workers started.	The upper limit of workers started.	Not used with this configuration.
Scaling number of workers between minworkers and maxworkers with configurable idle time.	Timeout.			The idle time for workers can be configured, i.e. a worker is stopped when, for the period defined by timeout, no client request has to be served and the minimum number of workers has not been reached.

### Configuration Examples

- [Configuration 1: Medium Lifespan of Worker Threads](#)
- [Configuration 2: Shortest Lifespan of Worker Threads](#)

- [Configuration 3: Fixed Number of Workers](#)

**Configuration 1: Medium Lifespan of Worker Threads**

- `endworkers=T` (timeout)
- `timeout=600`
- `minworkers=1`
- `maxworkers=10`

The `endworkers` parameter determines the condition under which a worker will be stopped. The value is the period of time specified by the parameter `timeout` (600 seconds, i.e. 10 minutes). Active workers will be stopped if no client requests arrive within the timeout period, except for the number of threads specified in `minworkers`.

`Minworkers` specifies the minimum number of workers that must be available to handle incoming client requests. The server is started (manually) and the first worker (`minworkers=1`) waits for client requests. When the first client request arrives, a second worker is started. This ensures that there will be at least one free worker (`minworkers=1`) to handle the next incoming client request.

When the first client request has been worked off (in conversational mode when the conversation has been ended, and in non-conversational mode when the request has been answered), there will be two workers active. For the next incoming client request (second request) no additional worker will be started because the second worker is still free. A third worker will only be started if a third client request arrives before the second request has been finished, in which case there will be three active workers, and so on.

The `maxworkers` parameter specifies the maximum number of active worker tasks permitted (default is 10).

**Configuration 2: Shortest Lifespan of Worker Threads**

- `endworkers=I` (immediately)
- `timeout=600`
- `minworkers=1`
- `maxworkers=10`

In this example the `endworkers` parameter has been set to "I" (immediately). This setting will stop worker threads immediately when client requests are completed, except for the number of threads specified in `minworkers`. All other behavior is the same as for [Configuration 1: Medium Lifespan of Worker Threads](#).

### Configuration 3: Fixed Number of Workers

- `endworkers=N` (never)
- `timeout=600`
- `minworkers=10`
- `maxworkers=`

This configuration determines a fixed number of workers. The `maxworkers` parameter is ignored and the `endworkers` parameter is set to "N" (never). All worker threads are started immediately with the server and will never stop. This method is useful in minimizing system resources.

### Suggested Configuration on First Usage

When you first start using EntireX RPC Server, we suggest the following settings for scaling the server.

`Endworkers=T` (timeout) and a low value for `minworkers` is suggested (e.g. `minworkers=2`). The `maxworkers` setting depends on the expected maximum number of clients active in parallel (e.g. `maxworkers=10`). The timeout parameter can be set e.g. to 2 minutes i.e. `timeout=120`.

## Starting the RPC Server

---

 **Important:** The EntireX RPC Server under IBM i can only be started as a batch job for multi-threading reasons. You must use the `SBMJOB` parameter `ALWMLTTHD=*YES` to allow multiple threads. Ensure that the subsystem you are submitting to the RPC server allows multiple threads. Use the command `WRKJOB` to verify the relevant job description.

### > To start the RPC Server

- 1 Ensure that the EntireX product library `EXX` is in your library list.
- 2 Create a startup procedure that submits the RPC Server to batch. The RPC Server is called `XSERVER` (of type `*PGM`) and is usually located in the EntireX product library `EXX`.

The following startup procedure shows the sample procedure `STR_RPCSRV` that is delivered in the library `EXAMPLE`:

```

PGM
/*-----*/
/* Example start procedure for the EntireX RPC Server.          */
/*                                                              */
/* Make sure that the RPC Server PGM and the configuration file  */
/* would be found in the library list.                          */
/*-----*/
      DCL      VAR(&NULL)   TYPE(*CHAR) LEN(2)  +
              VALUE(X'0000')
      DCL      VAR(&PARAM1) TYPE(*CHAR) LEN(40) +
              VALUE('CFG=*LIBL/QCLSRC(SERVER_CFG)')
      DCL      VAR(&PARAM2) TYPE(*CHAR) LEN(4)  VALUE('-S')
/*-----*/
/* C-Language binding requires each command-line parameter to be */
/* terminated with a NULL character                               */
/*-----*/
      CHGVAR   VAR(&PARAM1) VALUE(&PARAM1 *TCAT &NULL)
      CHGVAR   VAR(&PARAM2) VALUE(&PARAM2 *TCAT &NULL)
/*-----*/
SBMJOB  CMD(CALL PGM(*LIBL/XSERVER) +
           PARM(&PARAM1 &PARAM2)) +
           JOB(RPCSERVER) ALWMLTTHD(*YES)
        SNDPGMMSG MSG('EntireX RPC Server job submitted to +
           batch') MSGTYPE(*COMP)
ENDPGM

```

One or two parameters are passed to the RPC server:

- Parameter 1 specifies the RPC server configuration file (for details see the next step), and
- The optional parameter 2 “-S”, which runs the server in silent mode, that is: no terminal input will be required (e.g. acknowledge error messages). This is recommended for background jobs.



**Note:** C programming conventions require that each parameter must be terminated with a two-byte hexadecimal zero (variable &NULL in the procedure sample).

### 3 Create/adjust the RPC server configuration file.

The IBM i configuration file is derived from the file used for RPC Servers under UNIX. A sample data set is provided in the text member EXAMPLE/QCLSRC(RPCSRV\_CFG) delivered with the IBM i installation kit. Edit the individual parameters as described in [Configuring the RPC Server](#). (For the keywords for the server parameter runoption see [Possible Values for runoption](#))

Most important are the BrokerID=localhost:1971 of the remote Broker with which you want to register your server, and the ServerName=SRV1 that identifies your service.

Some parameters are not supported under IBM i (see the comment line in the text member referring to this).

- 4 Run the startup procedure. Make sure that the configuration file is available in your library list. When the RPC server is up and running, a corresponding entry should appear in the Active Jobs list that can be verified with command `WRKACTJOB`. If you use the sample procedure described above, the server will be named `RPCSERVER` as specified in the `SBMJOB` parameter `JOB`.

## Troubleshooting

---

Follow the hints and recommendations given below if the RPC Server does not return the expected results:

- If the client process receives an EntireX error message, read the relevant explanation under *Error Messages and Codes*.
- Use the command `WRKACTJOB` to determine whether the `RPCSERVER` process is still up and running.
- If the `RPCSERVER` is still running, invoke the job with option 5 (work with ...) and select command 10 to display the job log. Examine the log for system messages and exceptions.
- If the `RPCSERVER` is no longer active, search for a printed job log in the spooler of the user that submitted the RPC server. Usually, the IBM i system uses the default name `QPJOBLOG` for the print file.
- For many exceptions, the RPC Server writes messages to the system operator. Use the command `WRKMSG MSGQ(*SYSOPR)` to query the operator's message queue.
- To monitor the traffic of the RPC Server and to detect problems, restart the RPC Server with tracing activated. To do so, provide a valid log file and enable the tracing with the parameters `TraceLevel` and `TraceDestination` in the RPC Server configuration file member. See [Activating Tracing for the RPC Server](#) for details.

## Activating Tracing for the RPC Server

---

### ➤ To switch on tracing for the RPC Server

- 1 In the RPC Server configuration file, set the parameters `TraceLevel` and `TraceDestination`. See [Table of Server Parameters](#).

See also [Starting the RPC Server](#) for information on how to specify the parameters in the RPC Server configuration file under IBM i.

- 2 Evaluate the return codes. See *Error Messages and Codes*.

## Supported Trace Levels

Trace Level	Description
None	No tracing.
Standard	Traces the interface parameters.
Advanced	Traces the interface parameter, Broker calls and internal information needed for support.

## Trace Destination

### ➤ To assign a valid log file to the RPC Server

- 1 Use program `EXX/EXACRTLOG` to create file `LOG` in the target library, which is usually your current library.
- 2 Specify the Trace Destination in the RPC Server configuration file. Trace destination is a generic name including environment variables, e.g., `%TEMP%;@PID` (process ID), `@TID` (thread ID), `@RANGE[n,m]`, where `m` must be greater than `n`, range is from 0 - 999. Using the `RANGE` option under IBM i, you can specify the following syntax:

```
TraceDestination=MyLib/LOG(MyMember@RANGE[n-m])
```

where *MyLib* is the target library of the file `LOG` and *MyMember* is the prefix of the member name. Every time a new RPC Server session has been started, a new log member will be created in the log file.



**Note:** Under IBM i, a process ID (@PID) is assigned to a session and *not* changed during session lifetime.

- 3 When the RPC Server is up and running, use the command `WRKACTJOB` to verify that the server batch job has opened the log file successfully.
- 4 To evaluate the return codes, see *Error Messages and Codes*.

## Example

The following excerpt from an RPC server configuration file demonstrates the usage of the `Tracelevel` and the `Tracedestination`:

```
...  
Tracelevel=Support  
TraceDestination=*CURLIB/LOG(RPC@RANGE[1-100])  
...
```

When the RPC Server is first started, the member RPC001 will be created in file LOG. The next time, RPC002 will be created and so on.

# 3 Administering Broker Stubs under IBM i

---

- Using the Security Exit ..... 24
- Tracing for Broker Stubs under IBM i ..... 25

## Using the Security Exit

When you start a Broker ACI application program, the ACI service program searches your library list for the Security Exit service `SECUEXIT`. If it is found, it will be used automatically.

### Using the Security Exit supplied by Software AG

In this delivery package, a Security Exit named `X_SECUEXIT` is provided by Software AG. However, this file does not match the required name `SECUEXIT`. So by default, the Broker ACI runs without using a Security Exit.

#### ➤ To use the Software AG-supplied Security Exit Program

- 1 Rename the \*SRVPGM-type program `X_SECUEXIT` to `SECUEXIT` and
- 2 Start your user application. The bound Broker ACI will find and use the exit.

For detailed information, see *Sample Security Exits for Broker Security*.

### Creating your own Security Exit Program

A user-supplied security exit must meet the following minimum requirements:

Entry points	<pre>etbueva etbupre</pre>
Service program exports	<pre>STRPGMEXP PGMLVL(*CURRENT) LVLCHK(*NO) EXPORT SYMBOL('etbupre') EXPORT SYMBOL('etbueva') ENDPGMEXP</pre> <p>Sample: QSRVSRC(SECUEXIT) Type *BND</p>
Calling convention	<pre>... int etbueva(ETBCB *pEtbCb, void *pEncBuf, void *pReserved, char *pErrTxt) ... int etbupre(ETBCB *pEtbCb, void *pSndBuf, void *pReserved, char *pErrTxt)</pre> <p>Sample source: EXASRC(SECUEXIT)</p>

Create a Service Program for a security user exit	Sample source: EXASRC(EXACRTSXIT) This CL procedure creates module SECUEXIT from a C source and binds it to the service program SUEXIT.
---	--

### ➤ To create a security exit program

- 1 Write the source code. The supplied C example SECUEXIT provides a framework for the basic functionality.
- 2 Create a source file of type \*BND for the service program exports.
- 3 Compile the source code.
- 4 Create the service program.

See the CL Program sample EXACRTSXIT that contains the relevant commands (CRTCMOD and CRTSRVPGM) for compiling and creating a service program. In that example a service program named SUEXIT is created.

- 5 Usually, the Software AG-supplied security exit is named X\_SECUEXIT. If you have previously renamed it SECUEXIT, rename it back now to X\_SECUEXIT for backup reasons.

Then rename the security exit service program SUEXIT you have just created to SECUEXIT.

- 6 Test the application. When you start your application program, the Broker ACI automatically finds and uses the Security Exit SECUEXIT.

The samples above are based on C examples. For other languages such as ILE COBOL and ILE RPG, use the respective compiler.

## Tracing for Broker Stubs under IBM i

To request a log file from the Broker stub, the environment variable ETB\_STUBLOG must be set. The value of this variable defines how detailed the log will be.

The following table describes the trace values for ETB\_STUBLOG:

Trace Value	Trace Level	Description
0	NONE	No tracing.
1	STANDARD	Traces initialization, errors, and all ACI request/reply strings.
2	ADVANCED	Used primarily by system engineers, traces everything from level 1 and provides additional information - for example the Broker ACI control block - as well as transport information.
3	SUPPORT	This is full tracing through the stub, including detailed traces of control blocks, message information, etc.

➤ **To evaluate error conditions**

- 1 Set the environment variable: run the program `EXASETENV` or use the command:

```
ADDENVVAR ENVVAR(ETB_STUBLOG) VALUE(3)
```

To change the value of the variable, use the command `WRKENVVAR` or change and recompile the source file in `EXASRC`.

- 2 Rerun the example programs.

The member names in the file `LOG` are created with the prefix `ETB` and the six-digit process ID (`ETBpppppp`).



**Note:** The file will be overwritten if you restart your application in the same session.

# 4 Natural RPC Server Configuration for the IDL Extractor for

## Natural

---

- Natural Steplib Configuration ..... 28
- Natural RPC Server Configuration when Natural Security is not used ..... 28
- Natural RPC Server Configuration when Natural Security is used ..... 29
- Natural RPC Server Parameter Configuration ..... 29

This chapter describes how to configure the Natural RPC Server when using the IDL Extractor for Natural.



**Note:** Natural Wrapper is not supported under IBM i.

## Natural Steplib Configuration

---

The Natural IDL Generator server library SYSIDL relies on the following Natural system libraries to function correctly:

Library	Function
SYSIDL	IDL Extractor for Natural server library
SYSRPC	Natural RPC system library
SYSEXT	Natural interface library
SYSLIBS	Natural system library

Depending on whether the Natural RPC Server is used in a Natural Security environment or not, steplibs are defined differently.

## Natural RPC Server Configuration when Natural Security is not used

---

### Defining Steplibs when Natural Security is not used

#### > To define Steplibs

- Specify the required steplibs in the Natural parameter module used for the Natural RPC Server. See *Profile Parameters* in the Natural documentation.

### Installation Notes when Natural Security is not used

- If your Natural user applications supported by the Natural RPC Server need more than four steplibs, a separate Natural RPC Server instance must be set up for Natural IDL generation only. You cannot use Natural IDL generation from the same Natural RPC Server instance on which your Natural user application is running. Please remember that Natural supports a maximum of eight steplibs.

## Natural RPC Server Configuration when Natural Security is used

---

### Defining Steplibs when Natural Security is used

In a Natural Security environment, the required steplibs must be defined in the library profile of:

- the IDL Extractor for Natural server library SYSIDL
- every user library from which Natural IDL generation is to be performed (see [installation note 1](#) below).

### Natural Security Definitions

In a Natural Security environment, clients using the IDL Extractor for Natural need to be defined in Natural Security with access to

- the library SYSIDL
- all libraries from which IDL generation has to be performed

### Installation Notes when Natural Security is used

1. If your Natural user applications supported by the Natural RPC Server need more than four steplibs, a separate Natural Security file FSEC and Natural RPC Server instance must be set up for Natural IDL generation only. You cannot use the same Natural Security file FSEC and Natural RPC Server instance on which your Natural user application is running.
2. You cannot use the `STACK` parameter to set steplibs if Natural Security is used.
3. Under Natural Security, start the Natural RPC Server with `LOGONRQ=ON`. If this setting conflicts with your Natural user applications, we recommended setting up a separate Natural RPC Server instance for IDL Generation.

## Natural RPC Server Parameter Configuration

---

Basically all parameters valid for Natural and Natural RPC Server are valid for use with the IDL Extractor for Natural server library SYSIDL.

The most important Natural RPC Server parameters to be set are:

Parameter	Optional/Required	Explanation and Notes
SRVNODE=<value>	Required	The Broker ID.
SRVNAME=<value>	Required	The server name as defined under SERVER under <i>Broker Attributes</i> .
TIMEOUT=55	Optional	Wait timeout for the Natural RPC Server. The default value 55 is suitable for most installations. It can be adapted if necessary.
LOGONRQ=ON	Required to be ON if Natural Security is used.	Forces clients to log on to Natural libraries.
MADIO=0	Required	No limit on DB Calls.
MAXCL=0	Required	No limit on PGM Calls.
YSLW=1979	Optional, but recommended to be set.	<p>The century of save and compile (catalog) dates of Natural objects may be displayed incorrectly if you do not set a Year Sliding or Fixed Window. We suggest setting a fixed window starting from 1979 on. This ensures a correct century in the range 1979 (first release of Natural programs) up to the year 2078. If this window setting conflicts with your application requirements, consider</p> <ul style="list-style-type: none"> <li>■ using a separate RPC server for the server library SYSIDL.</li> <li>■ using other YSLW settings which may also solve the problem. See your Natural documentation for more information.</li> </ul> <p>Displaying an incorrect century does not have any impact on IDL generation - only the timestamp in the browse dialogs will be incorrect.</p>

You will find the above parameters in your NATPARM module or you can set them dynamically.

See your Natural documentation for more information.